

**ORIGINAL**

**UNITED STATES  
DEPARTMENT OF THE INTERIOR  
BUREAU OF LAND MANAGEMENT**

FIELD NOTES

OF THE

DEPENDENT RESURVEY OF THE SOUTH BOUNDARY  
AND A PORTION OF THE SUBDIVISIONAL LINES,

AND THE SURVEY OF

THE EAST AND WEST BOUNDARIES

AND A PORTION OF THE SUBDIVISIONAL LINES,

**TOWNSHIP 24 NORTH, RANGE 30 EAST,**

OF THE GILA AND SALT RIVER MERIDIAN,

IN THE STATE OF ARIZONA.

**EXECUTED BY**

**Jones Curtiss and Leonard R. Sandoval, Cadastral Surveyors**

Under Special Instructions dated and approved January 22, 2001, and Supplemental Special Instructions dated and approved October 2, 2001, which provided for the surveys included under Group No. 863, and assignment instructions dated January 22, 2001.

**Survey commenced August 27, 2001**

**Survey completed November 28, 2001**

## INDEX DIAGRAM

TOWNSHIP 24 NORTH,            RANGE 30 EAST,  
GILA AND SALT RIVER MERIDIAN, ARIZONA

47	86 6	86 5	74 4	65 3	60 2	55 1	38
46	84 7	83 8	72 9	63 10	58 11	52 12	37
44	82 18	81 17	71 16	32 15	26 14	51 13	36
43	80 19	79 20	69 21	30 22	24 23	17 24	50 35
41	78 30	77 29	68 28	27 27	20 26	15 25	50 34
40	76 31	75 32	66 33	61 34	56 35	12 36	49 33
	10	8	8	6	6	4	

**T. 24 N., R. 30 E., Gila and Salt River Meridian, Arizona**

## CHAINS

The following field notes describe the dependent resurvey of the south boundary and a portion of the subdivisional lines, and the survey of the east and west boundaries and a portion of the subdivisional lines, T. 24 N., R. 30 E., Gila and Salt River Meridian, Arizona.

The W. bdy. of T. 23 N., R. 31 E., was surveyed by W. R. Fitzgerald in 1882. The 6th Std. Par. N., (S. bdy.), T. 25 N., R. 29 E., was surveyed by Frank Follman in 1883. A portion of the S. bdy. of sec. 36, and a portion of the subdivisional lines, were surveyed by Charles L. Campbell in 1907. The E. bdy., T. 23 N., R. 29 E., was surveyed by Sidney E. Blout in 1920. The E. bdy. of T. 23 N., R. 30 E. and a portion of the S. bdy. of sec. 36 was resurveyed and the remaining S. bdy. of the Tp. was surveyed by Loyd E. Sechrist and William D. Wilson in 1920. The 6th Std. Par. N., (S. bdy.), T. 25 N., R. 29 E., was dependently resurveyed by Sidney E. Blout in 1927. The 6th Std. Par. N., (S. bdy.), T. 25 N., R. 30 E., was surveyed by Sidney E. Blout in 1927. The 6th Std. Par. N., (S. bdy.), T. 25 N., R. 29 E., was dependently resurveyed by Kevin R. DeRossett in 1985-86. Portions of the 6th Std. Par. N., (S. bdy.), Tps. 25 N., Rs. 29-30 E., were dependently resurveyed by Jones Curtiss, in 2001, concurrently under this same group.

The survey was executed in accordance with the specifications as set forth in the Manual of Instructions for the Survey of the Public Lands of the United States, 1973, the Special Instructions dated January 22, 2001, and the Supplemental Special Instructions dated October 2, 2001, for Group No. 863, Arizona.

The true meridian direction and length of all lines were determined by real time kinematic global positioning system observations using Trimble Navigation 4400 and 4700 model receivers.

Preliminary to the resurvey, the lines of the prior surveys were retraced and search was made for all corners and other calls of record. Identified corners were remonumented in their original positions. Lost corners were reestablished and remonumented at proportionate positions based on the official record. The retracement data were thoroughly verified and only the true line field notes are given herein.

Geodetic control was derived from Global Positioning System (GPS) static observations post processed by National Geodetic Survey's Online Positioning User Service (OPUS), utilizing Continuously Operating Reference Stations (CORS) AZTEC, COSA and PIE TOWN VLBA. The NAD 83 (CORS92) (EPOCH: 2001), geographic position of the southeast cor. of the Tp., is as follows:

Latitude: 35°25'43.51" N.

Longitude: 109°06'20.70" W.

**T. 24 N., R. 30 E., Gila and Salt River Meridian, Arizona**

CHAINS

The mean magnetic declination is  $11 \frac{1}{2}^{\circ}$  E.

---

**Dependent Resurvey of the South Boundary,  
T. 24 N., R. 30 E., Gila and Salt River Meridian, Arizona**

---

Restoring the survey executed by  
Loyd E. Sechrist, in 1920

---

Beginning at the cor. of Tps. 23 and 24 N., Rs. 30 and 31 E., monumented with an iron post, 3 ins. diam., firmly set, projecting 8 ins. above a mound of stone, 3 ft. base, 1 ft. high, with brass cap mkd. T24N R30E R31E S36 S31 S1 S6 T23N 1920.

from which the remaining 1920 bearing trees

A ponderosa pine, 18 ins. diam., bears N.  $70 \frac{3}{4}^{\circ}$  E., 49 lks. dist., with healed blaze.

A ponderosa pine, 19 ins. diam., bears S.  $74^{\circ}$  E., 1.22 chs. dist., with healed blaze.

A juniper, 8 ins. diam., bears S.  $14^{\circ}$  W., 41 lks. dist., with scribe marks T23N R30E S1 BT visible on open blaze. (Record: 39 lks. dist.)

Add the marks 2001 to the brass cap.

From this cor. point, a rebar,  $\frac{5}{8}$  in. diam., firmly set, projecting  $4 \frac{1}{2}$  ins. above sandstone bedrock, bears S.  $43^{\circ}42'$  W., 3.53 chs. dist., with aluminum cap mkd. B-32 1968, established by Ernest V. Echohawk, R.L.S. 2311, in 1968, as an angle point in a land withdrawal boundary survey.

S.  $89^{\circ}42'$  W., bet. secs. 1 and 36.

Over rolling land, atop a ridge.

- |       |   |
|-------|---|
| 3.60  | W. rim of a ridge, bears S. $20^{\circ}$ E. and N. $20^{\circ}$ W.; thence over broken land, on abrupt descent.   |
| 29.23 | E. right-of-way fence of Navajo Route 12, barbed wire, 5 strands, parallels highway.  |
| 29.90 | A brass tablet, 3 ins. diam., set flush in a concrete collar, 6 ins. diam. firmly set, projecting 2 ins. above ground, bears North, 2.38 chs. dist., with top mkd. B.I.A. ROADS 19, and witnessed by an angle iron to the S., mkd. 870+98.60 on a side. |

**Dependent Resurvey of the South Boundary,  
T. 24 N., R. 30 E., Gila and Salt River Meridian, Arizona**

CHAINS	
30.15	Navajo Route 12, asphalt pavement, 40 ft. wide, bears S. 20° E. and N. 20° W.
31.38	W. right-of-way fence of Navajo Route 12, barbed wire, 5 strands, parallels highway.  Thence over rolling land, on ascent.
39.95	The 1/4 sec. cor. of secs. 1 and 36, monumented with an iron post, 1 in. diam., firmly set, projecting 8 ins. above ground, there is no remaining evidence of the original corner stone, with brass cap mkd. 1/4 S36 S1 1920.  from which the remaining 1907 bearing tree  A piñon, 21 ins. diam., bears S. 87 1/2° W., 92 lks. dist., with scribe marks 1/4 S BT visible on partially healed blaze.  Add the marks T24N R30E T23N 2001 to the brass cap.  <hr style="width: 20%; margin: auto;"/> <p style="text-align: center;">Restoring the resurvey executed by Loyd E. Sechrist, in 1920</p> <hr style="width: 20%; margin: auto;"/>  S. 89°28' W., beginning new measurement.  Over rolling and broken land.
40.14	The cor. of secs. 1, 2, 35 and 36, monumented with an iron post, 2 ins. diam., firmly set, projecting 3 ins. above a mound of stone, 3 ft. base, 2 1/2 ft. high, with brass cap mkd. T24N R30E S35 S36 S2 S1 T23N 1920.  from which the remaining 1907 bearing trees  A ponderosa pine, 16 ins. diam., bears N. 58° E., 52 lks. dist., with illegible scribe marks visible on partially healed blaze. (1920 Record: 55 lks. dist.)  A ponderosa pine, 18 ins. diam., bears N. 37 3/4° W., 54 lks. dist., with scribe marks T24N R30E S35 BT visible on open blaze.

**Dependent Resurvey of the South Boundary,  
T. 24 N., R. 30 E., Gila and Salt River Meridian, Arizona**

CHAINS	
	<p>Add the marks 2001 to the brass cap.</p> <hr/> <p style="text-align: center;">Restoring the survey executed by Lloyd E. Sechrist, in 1920</p> <hr/> <p>N. 89°58' W., bet. secs. 2 and 35.</p> <p>Over rolling and broken land.</p>
40.02	<p>The 1/4 sec. cor. of secs. 2 and 35, monumented with an iron post, 1 in. diam., firmly set, projecting 10 ins. above ground, with brass cap mkd. 1/4 S35 S2 1920.</p> <p>from which the original bearing trees</p> <p style="padding-left: 40px;">A piñon, 11 ins. diam., bears N. 46° E., 23 lks. dist., with scribe marks 1/4 S35 BT visible on partially healed blaze.</p> <p style="padding-left: 40px;">A forked piñon, 12 ins. diam. at base, bears S. 41° E., 46 lks. dist., with scribe marks 1/4 S2 BT visible on open blaze.</p> <p>Add the marks T24N R30E T23N 2001 to the brass cap.</p> <hr/> <p>West, beginning new measurement.</p> <p>Over rolling and broken land.</p>
16.20	<p>S. rim of canyon of Black Creek, bears N. 70° E. and S. 70° W.</p>
33.40	<p>S. rim of canyon of Black Creek, bears S. 40° E. and N. 40° W.</p>
40.01	<p>The cor. of sec. 2, 3, 34 and 35, monumented with an iron post, 2 ins. diam., firmly set, projecting 10 ins. above ground, with brass cap mkd. T24N R30E S34 S35 S3 S2 T23N 1920.</p> <p>from which the remaining original bearing tree</p> <p style="padding-left: 40px;">A piñon, 6 ins. diam., bears S. 21 1/2° E., 35 lks. dist., with scribe marks T23N R30E S2 BT visible on open blaze. (Record: S. 20 1/4° E.)</p> <p>Add the marks 2001 to the brass cap.</p> <hr/> <p>S. 89°57' W., bet. secs. 3 and 34.</p> <p>Over rolling and broken land.</p>

**Dependent Resurvey of the South Boundary,  
T. 24 N., R. 30 E., Gila and Salt River Meridian, Arizona**

CHAINS	
13.40	S. rim of canyon of Black Creek, bears N. 60° E. and S. 60° W.
27.50	S. rim of canyon of Black Creek, bears S. 70° E. and N. 70° W.
40.01	<p>The 1/4 sec. cor. of secs. 3 and 34, monumented with an iron post, 1 in. diam., firmly set, projecting 12 ins. above ground, with brass cap mkd. 1/4 S34 S3 1920. from which the remaining original bearing tree</p> <p style="padding-left: 40px;">A piñon, 9 ins. diam., bears N. 20 3/4° W., 45 lks. dist., with scribe marks S34 BT visible on partially healed blaze.</p> <p>Add the marks T24N R30E T23N 2001 to the brass cap.</p> <p>Cor. is located 1.80 chs. S. of S. rim of canyon of Black Creek, bears S. 60° E. and N. 60° W.</p> <hr style="width: 20%; margin: 10px auto;"/> <p>West, beginning new measurement.</p> <p>Over rolling and broken land.</p>
16.90	E. rim of canyon of Black Creek, bears N. 60° E. and S. 60° W.
40.00	<p>The cor. of secs. 3, 4, 33 and 34, monumented with an iron post, 2 ins. diam., firmly set, projecting 2 ins. above ground, with brass cap mkd. T24N R30E S33 S34 S4 S3 T23N 1920. from which the original bearing trees</p> <p style="padding-left: 40px;">A piñon, 9 ins. diam., bears N. 37 3/4° E., 32 lks. dist., with scribe marks T24N R30E S34 BT visible on open blaze.</p> <p style="padding-left: 40px;">A piñon, 9 ins. diam., bears S. 9 3/4° E., 56 1/2 lks. dist., with scribe marks T23N R30E S3 BT visible on open blaze. (Record: 54 lks. dist.)</p> <p style="padding-left: 40px;">A piñon, 14 ins. diam., bears S. 18 1/2° W., 51 lks. dist., with scribe marks T23N R30E S4 BT visible on open blaze. (Record: 50 lks. dist.)</p> <p style="padding-left: 40px;">A piñon stump, 9 ins. diam., bears N. 85 1/4° W., 32 lks. dist., with severed trunk lying nearby, marked T24N R30E S33 BT on open blaze. (Record: 12 ins. diam., N. 84° W., 31 lks. dist.)</p> <p>Add the marks 2001 to the brass cap.</p>

**Dependent Resurvey of the South Boundary,  
T. 24 N., R. 30 E., Gila and Salt River Meridian, Arizona**

CHAINS									
	<p>Cor. is located in the canyon of Black Creek, 2.10 chs. S. of Black Creek, a wash, 10 ft. wide, 2 ft. deep, drains W.</p> <hr/> <p>West, bet. secs. 4 and 33.</p> <p>Over rolling to broken land.</p>								
8.30	Black Creek, a wash, 10 ft. wide, 2 ft. deep, drains S. 25° W.								
39.90	W. rim of canyon of Black Creek, bears N. and S.								
40.01	<p>The 1/4 sec. cor. of secs. 4 and 33, monumented with an iron post, 1 in. diam., firmly set, flush with a mound of stone, 4 ft. base, 2 1/2 ft. high, with brass cap mkd. 1/4 S33 S4 1920.</p> <p>Add the marks T24N R30E T23N 2001 to the brass cap.</p> <hr/> <p>West, beginning new measurement.</p> <p>Over rolling land, atop a plateau.</p>								
40.01	<p>The cor. of secs. 4, 5, 32 and 33, monumented with an iron post, 2 ins. diam., loosely set, projecting 24 ins. above ground, in a scattered mound of stone, with brass cap mkd. T24N R30E S32 S33 S5 S4 T23N 1920.</p> <p>At the cor. point</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center;"> <table border="1"> <tr> <td>T 24 N</td> <td>R 30 E</td> </tr> <tr> <td>S 32</td> <td>S 33</td> </tr> <tr> <td>S 5</td> <td>S 4</td> </tr> <tr> <td colspan="2">T 23 N</td> </tr> </table> <p>2001</p> </div> <p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p> <p>Bury the original iron post, 36 ins. long, alongside the stainless steel post.</p> <hr/> <p>N. 89°59' W., bet. secs. 5 and 32.</p> <p>Over gently rolling land, atop a plateau.</p>	T 24 N	R 30 E	S 32	S 33	S 5	S 4	T 23 N	
T 24 N	R 30 E								
S 32	S 33								
S 5	S 4								
T 23 N									



**Dependent Resurvey of the South Boundary,  
T. 24 N., R. 30 E., Gila and Salt River Meridian, Arizona**

CHAINS	
40.02	<p>The 1/4 sec. cor. of secs. 5 and 32, monumented with an iron post, 1 in. diam., firmly set and bent, projecting 12 ins. above ground, with brass cap mkd. 1/4 S32 S5 1920.</p> <p>At the cor. point</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center; margin: 10px 0;">           T 24 N R 30 E                      S 32            1/4 ———                      S 5            T 23 N         </div> <p style="text-align: center; margin: 10px 0;">2001</p> <p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p> <p>Bury the original iron post, 36 ins. long, alongside the stainless steel post.</p> <hr style="width: 30%; margin: 10px auto;"/> <p>S. 89°59' W., beginning new measurement.</p> <p>Over gently rolling land, atop a plateau.</p>
40.04	<p>The cor. of secs. 5, 6, 31 and 32, monumented with an iron post, 2 ins. diam., loosely set, projecting 22 ins. above ground, in a scattered mound of stone, with brass cap mkd. T24N R30E S31 S32 S6 S5 T23N 1920.</p> <p>from which the remaining original bearing tree</p> <div style="text-align: center; margin: 10px 0;">           A ponderosa pine, 18 ins. diam., bears N. 8 3/4° W.,            98 lks. dist., with healed blaze.         </div> <p>At the cor. point</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center; margin: 10px 0;">           T 24 N R 30 E            S 31   S 32            ————            S 6   S 5            T 23 N         </div> <p style="text-align: center; margin: 10px 0;">2001</p> <p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p>

**Dependent Resurvey of the South Boundary,  
T. 24 N., R. 30 E., Gila and Salt River Meridian, Arizona**

CHAINS	
40.06	<p>Bury the original iron post, 36 ins. long, alongside the stainless steel post.</p> <hr/> <p>S. 89°57' W., bet. secs. 6 and 31.</p> <p>Over gently rolling land, atop a plateau.</p> <p>The 1/4 sec. cor. of secs. 6 and 31, monumented with an iron post, 1 in. diam., loosely set, projecting 26 ins. above ground, in a scattered mound of stone, with brass cap mkd. 1/4 S31 S6 1920.</p> <p>from which the original bearing trees</p> <p style="padding-left: 40px;">A ponderosa pine, 20 ins. diam., bears S. 73 1/2° W., 77 lks. dist., with healed blaze.</p> <p style="padding-left: 40px;">A ponderosa pine, 13 ins. diam., bears N. 39 1/2° W., 40 lks. dist., with scribe marks 1/4 S31 BT visible on open blaze. (Record: N. 41 1/4° W., 41 lks. dist.)</p> <p>At the cor. point</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 22 ins. in the ground, in a collar of stone, with brass cap mkd.</p> <div style="text-align: center; margin: 10px 0;"> <p>T 24 N R 30 E</p> <p style="padding-left: 40px;">S 31</p> <p style="padding-left: 20px;">1/4 ———</p> <p style="padding-left: 40px;">S 6</p> <p>T 23 N</p> <p style="margin-top: 10px;">2001</p> </div> <p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p> <p>Bury the original iron post, 36 ins. long, alongside the stainless steel post.</p> <hr/> <p>N. 89°58' W., beginning new measurement.</p> <p>Over rolling and broken land, across a small canyon.</p>
28.73	<p>The cor. of Tps. 23 and 24 N., R. 30 E. only, monumented with an iron post, 3 ins. diam., firmly set, projecting 13 ins. above ground, with brass cap mkd. T24N R29E R30E S31 S36 S6 T23N 1920.</p>

**Dependent Resurvey of the South Boundary,  
T. 24 N., R. 30 E., Gila and Salt River Meridian, Arizona**

CHAINS

from which the original bearing trees

A piñon, 14 ins. diam., bears N. 74° E., 1.82 chs. dist., with scribe marks T2 R30E S31 BT visible on open blaze.

A piñon, 14 ins. diam., bears S. 70 3/4° E., 3.04 chs. dist., with scribe marks T23N R30E S6 BT visible on open blaze. (Record: S. 70° E., 303 lks. dist.)

A piñon, 12 ins. diam., bears N. 82 3/4° W., 1.10 chs. dist., with scribe marks T24N R29E S36 BT visible on open blaze.

Add the marks 2001 to the brass cap.

From this cor. point, the cor. of Tps. 23 and 24 N., R. 29 E. only, bears S. 0°06' W., 3.55 chs. dist., monumented with an iron post, 3 ins. diam., firmly set, projecting 12 ins. above ground, with brass cap mkd. T24N R29E R30E S36 S6 S1 T23N 1920.

from which the original bearing trees

A piñon, 9 ins. diam., bears S. 48° W., 1.41 chs. dist., with scribe marks T23N R29 S1 BT visible on open blaze.

A piñon, 10 ins. diam., bears N. 70° W., 1.20 chs. dist., with scribe marks T24N R29E S36 BT visible on open blaze. (Record: N. 70 1/2° W.)

Add the marks T23N to the NE quadrant, and the marks 2001 at the bottom of the brass cap.

---

**Dependent Resurvey of a Portion of the Subdivisional Lines,  
T. 24 N., R. 30 E., Gila and Salt River Meridian, Arizona**

---

Restoring the survey executed by  
Charles L. Campbell, in 1907

---

From the cor. of secs. 1, 2, 35 and 36, on the S. bdy. of the Tp., hereinbefore described.

N. 0°01' W., bet. secs. 35 and 36.

Over broken to nearly level land, entering Oak Spring Valley.

40.10

Trail road, bears S. 75° E. and N. 75° W.

**Dependent Resurvey of a Portion of the Subdivisional Lines,  
T. 24 N., R. 30 E., Gila and Salt River Meridian, Arizona**

CHAINS	
40.38	<p>The 1/4 sec. cor. of secs. 35 and 36, monumented with a sandstone, 22 x 9 x 7 ins., firmly set, projecting 7 ins. above ground, mkd. 1/4 on W. face, with a mound of stone, 1 1/2 ft. base, 1/2 ft. high, E.</p> <p>At the cor. point</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 22 ins. in the ground, in a collar of stone, with brass cap mkd.</p> <p style="text-align: center;">T 24 N R 30 E 1/4 S 35   S 36</p> <p style="text-align: center;">2001</p> <p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p> <p>Bury the original stone alongside the stainless steel post.</p> <hr style="width: 20%; margin: 10px auto;"/>
40.06	<p>N. 0°08' W., beginning new measurement.</p> <p>Over nearly level land, in Oak Spring Valley.</p> <p>The cor. of secs. 25, 26, 35 and 36, monumented with a sandstone, 12 x 9 x 5 ins., firmly set, projecting 3 ins. above ground, mkd. with 1 groove on S. face and 1 notch on E. edge.</p> <p>At the cor. point</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T 24 N R 30 E S 26   S 25 S 35   S 36</p> <p style="text-align: center;">2001</p> <p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p> <p>Bury the original stone alongside the stainless steel post.</p> <hr style="width: 20%; margin: 10px auto;"/>
	<p>From the 1/4 sec. cor. of secs. 25 and 36, monumented with a sandstone, 22 x 12 x 8 ins., firmly set, projecting 8 ins. above ground, mkd. 1/4 on N. face.</p>

**Dependent Resurvey of a Portion of the Subdivisional Lines,  
T. 24 N., R. 30 E., Gila and Salt River Meridian, Arizona**

CHAINS	
	<p>from which the remaining bearing tree</p> <p>A ponderosa pine, 32 ins. diam., bears S. 37° W., 41 lks. dist., with scribe marks 1/4 S36 BT visible on open blaze. (Record: 48 ins. diam.)</p> <p>At the cor. point</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 22 ins. in the ground, in a collar of stone, with brass cap mkd.</p> <p style="text-align: center;">T 24 N R 30 E S 25 1/4 ——— S 36</p> <p style="text-align: center;">2001</p> <p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p> <p>Bury the original stone alongside the stainless steel post.</p> <p>Cor. is located 1.00 ch. W. of base of a high sandstone cliff, bears N. and S.</p> <p>S. 89°49' W., bet. secs. 25 and 36.</p> <p>Over rolling land, on descent into Oak Spring Valley.</p>
22.81	E. right-of-way fence of Navajo Route 12, barbed wire, 5 strands, parallels highway.
24.01	Navajo Route 12, asphalt pavement, 35 ft. wide, bears S. 20° E. and N. 20° W.
25.20	W. right-of-way fence of Navajo Route 12, barbed wire, 5 strands, parallels highway; thence over nearly level land, in Oak Spring Valley.
40.03	The cor. of secs. 25, 26, 35 and 36.
	<hr/> <p>N. 0°13' W., bet. secs. 25 and 26.</p> <p>Over nearly level land, in Oak Spring Valley.</p>
36.97	S. right-of-way fence of Navajo Route 12, barbed wire, 5 strands, parallels highway.
40.02	Navajo Route 12, asphalt pavement, 40 ft. wide, bears S. 20° E. and N. 20° W.

**Dependent Resurvey of a Portion of the Subdivisional Lines,  
T. 24 N., R. 30 E., Gila and Salt River Meridian, Arizona**

CHAINS							
40.09	<p>Point for the 1/4 sec. cor. of secs. 25 and 26, at proportionate dist.; there is no remaining evidence of the original cor.</p> <p>Set a P-K nail, flush with the surface of asphalt pavement.</p> <p>from which</p> <p>A stainless steel post, 28 ins. long, 2 1/2 ins. diam., set 24 ins. in the ground for a reference monument, bears N. 80°00' E., 75.0 ft. dist. with brass cap mkd. RM T24N R30E 1/4 S25 75.0 FT. TO COR. 2001 and an arrow pointing to the corner. Deposit a magnet in a white plastic case at the base of the stainless steel post.</p> <p>A stainless steel post, 28 ins. long, 2 1/2 ins. diam., set 24 ins. in the ground for a reference monument, bears S. 80°00' W., 80.0 ft. dist. with brass cap mkd. RM T24N R30E 1/4 S26 80.0 FT. TO COR. 2001 and an arrow pointing to the corner. Deposit a magnet in a white plastic case at the base of the stainless steel post.</p> <p>Cor. is located in Navajo Route 12, asphalt pavement, 40 ft. wide, 2.93 chs. S. of N. right-of way fence of Navajo Route 12, barbed wire, 5 strands, both bear S. 20° E. and N. 20° W.</p>						
58.75	Woven wire fence, bears N. 50° E. and S. 50° W.						
59.40	Apache County Road C402, a graded road, 25 ft. wide, bears N. 50° E. and S. 50° W.						
68.60	Black Creek, a wash, 50 ft. wide, 6 ft deep, drains S. 70° W.						
75.64	Barbed wire fence, 4 strands, bears N. 60° E. and S. 60° W.						
80.18	<p>Point for the cor. of secs. 23, 24, 25 and 26, at proportionate dist.; found fragments of the original sandstone, with overall dimensions of 16 x 8 x 5 ins., lying loose nearby, with 2 grooves on one face and 1 groove on another face.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <table border="0" data-bbox="813 1577 1040 1682" style="margin-left: auto; margin-right: auto;"> <tr> <td>T 24 N</td> <td>R 30 E</td> </tr> <tr> <td>S 23</td> <td>S 24</td> </tr> <tr> <td>S 26</td> <td>S 25</td> </tr> </table> <p align="center">2001</p>	T 24 N	R 30 E	S 23	S 24	S 26	S 25
T 24 N	R 30 E						
S 23	S 24						
S 26	S 25						
	Deposit a magnet in a white plastic case at the base of the stainless steel post.						

**Dependent Resurvey of a Portion of the Subdivisional Lines,  
T. 24 N., R. 30 E., Gila and Salt River Meridian, Arizona**

CHAINS	
	<p>Bury the fragments of the original stone alongside the stainless steel post and set a steel fence post nearby.</p> <p>Cor. is located 28 lks. W. of a barbed wire fence, 5 strands, bears N. and S.; and 1.35 chs. W. of a wash, 9 ft. wide, 3 ft. deep, drains S. 15° E.</p> <hr/> <p>From the 1/4 sec. cor. of secs. 24 and 25, monumented with a sandstone, 16 x 8 x 4 ins., loosely set 2 ins. in the ground, mkd. 1/4 on top face.</p> <p>At the cor. point</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T 24 N R 30 E S 24 1/4 ——— S 25</p> <p style="text-align: center;">2001</p> <p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p> <p>Bury the original stone alongside the stainless steel post.</p> <p>Cor. is located 2.00 chs. E. of a graded road, 20 ft. wide, bears S. 40° E. and N. 40° W.</p> <p>S. 89°43' W., bet. secs. 24 and 25.</p> <p>Over gently rolling land, in Oak Spring Valley.</p>
28.30	Apache County Road C402, a graded road, 25 ft. wide, bears N. 30° E. and S. 30° W.
30.10	Black Creek, a wash, 120 ft. wide, 8 ft. deep, drains S. 30° W.
39.90	The cor. of secs. 23, 24, 25 and 26.
	<hr/> <p>N. 0°11' E., bet. secs. 23 and 24.</p> <p>Over gently rolling land, in Oak Spring Valley.</p>
19.52	Woven wire and barbed wire fence, bears N. 80° E. and S. 80° W.
40.09	The 1/4 sec. cor. of secs. 23 and 24, monumented with a sandstone, 20 x 6 x 6 ins., firmly set, projecting 8 ins. above ground, in a scattered mound of stone, mkd. 1/4 on W. face.

**Dependent Resurvey of a Portion of the Subdivisional Lines,  
T. 24 N., R. 30 E., Gila and Salt River Meridian, Arizona**

CHAINS	
	At the cor. point
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, in a collar of stone, with brass cap mkd.
	<p style="text-align: center;">T 24 N R 30 E 1/4 S 23   S 24</p> <p style="text-align: center;">2001</p>
	Deposit a magnet in a white plastic case at the base of the stainless steel post.
	Bury the original stone alongside the stainless steel post.
	From this cor. point, a third order U. S. Geological Survey benchmark bears N. 58°22' W., 21.66 chs. dist., monumented with a standard aluminum tablet, 3 3/4 ins. diam., set flush in a concrete collar, 7 ins. square, firmly set, projecting 4 ins. above ground, with top mkd. 70 DOR 6499 1970 RESET.
	<hr style="width: 20%; margin: auto;"/> <p>N. 0°10' W., beginning new measurement.</p>
14.37	Barbed wire fence, 6 strands, bears N. 80° E. and S. 80° W.
40.03	Barbed wire fence, 5 strands, bears E. and W.
40.12	The cor. of secs. 13, 14, 23 and 24, monumented with a sandstone, 30 x 18 x 4 ins., firmly set, projecting 8 ins. above ground, mkd. with 1 groove on E. face and 1 groove on fractured S. face
	from which the original bearing trees
	<p style="padding-left: 40px;">A piñon, 22 ins. diam., bears N. 86 3/4° E., 2.855 chs. dist., with charred open blaze. (Record: N. 87 1/2° E., 288 lks. dist.)</p>
	<p style="padding-left: 40px;">A piñon stump, 21 ins. diam., bears S. 60° E., 2.515 chs. dist., with scribe marks R30E S24 BT visible on remnant of open blaze. (Record: 254 lks. dist.)</p>
	At the cor. point
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.



**Dependent Resurvey of a Portion of the Subdivisional Lines,  
T. 24 N., R. 30 E., Gila and Salt River Meridian, Arizona**

CHAINS

T 24 N	R 30 E
S 14	S 13
S 23	S 24

2001

Deposit a magnet in a white plastic case at the base of the stainless steel post.

Bury the original stone alongside the stainless steel post.

From the original witness cor. to the cor. of secs. 13, 18, 19 and 24, monumented with a sandstone, 16 x 15 x 6 ins., firmly set, projecting 8 ins. above ground, mkd. with 3 notches on N. edge and 3 notches on S. edge.

from which the original bearing trees

A piñon, 8 ins. diam., bears N. 70° E., 1.025 chs. dist., with scribe marks WC T24N R31E S visible on open blaze. (Record: 106 lks. dist.)

A piñon, 14 ins. diam., bears S. 40 1/4° E., 39 lks. dist., with healed blaze. (Record: S. 55° E., 35 lks. dist.)

A piñon, 16 ins. diam., bears N. 31 3/4° W., 3.13 chs. dist., with healed blaze. (Record: N. 29° W., 364 lks. dist.)

This point now serves only as an Angle Point on the line bet. secs. 13 and 24.

At the cor. point

Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.

T 24 N	R 30 E
S 13	
AP	_____
S 24	

2001

Deposit a magnet in a white plastic case at the base of the stainless steel post.

Bury the original stone alongside the stainless steel post.

S. 89°42' W., bet. secs. 13 and 24.

**Dependent Resurvey of a Portion of the Subdivisional Lines,  
T. 24 N., R. 30 E., Gila and Salt River Meridian, Arizona**

CHAINS	
	Over gently rolling land, in a valley.
8.30	Apache County Road C402, a graded road, 18 ft. wide, bears N. 20° E. and S. 20° W.
23.70	Black Creek, a wash, 60 ft. wide, 8 ft. deep, drains S. 20° E.
27.02	The 1/4 sec. cor. of secs. 13 and 24, monumented with a sandstone, 16 x 11 x 5 ins., firmly set, projecting 1 in. above ground, mkd. 1/4 on N. face.
	At the cor. point
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.
	T 24 N R 30 E S 13 1/4 ——— S 24  2001
	Deposit a magnet in a white plastic case at the base of the stainless steel post.
	Bury the original stone alongside the stainless steel post.
	_____
	N. 89°56' W., beginning new measurement.
	Over gently rolling land, in a valley.
27.30	Top of a narrow hogback ridge, bears S. 10° E. and N. 10° W.; thence descend abruptly into Oak Spring Valley.
40.03	The cor. of secs. 13, 14, 23 and 24.
	_____
	N. 0°10' W., bet. secs. 13 and 14.
	Over gently rolling land, along E. edge of Oak Spring Valley.
40.19	The 1/4 sec. cor. of secs. 13 and 14, determined at record bearing and distance from the original bearing tree
	A piñon, 23 ins. diam., bears S. 78° E., 2.86 chs. dist., with scribe marks 1/ visible on partially healed blaze.
	There is no remaining evidence of the original stone.
	At the cor. point

**Dependent Resurvey of a Portion of the Subdivisional Lines,  
T. 24 N., R. 30 E., Gila and Salt River Meridian, Arizona**

CHAINS

Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam.,  
24 ins. in the ground, with brass cap mkd.

T 24 N R 30 E  
1/4  
S 14 | S 13

2001

Deposit a magnet in a white plastic case at the base of the  
stainless steel post.

From this cor. point, a rebar, 5/8 in. diam., firmly set,  
projecting 1 in. above ground, bears N. 71°48' W., 14.47 chs.  
dist., with aluminum cap mkd. ONLA.

---

N. 0°18' W., beginning new measurement.

Over gently rolling land, on E. edge of Oak Spring Valley.

40.05

The cor. of secs. 11, 12, 13 and 14, determined at record  
bearings and distances from the original bearing trees

A piñon, 9 ins. diam., bears N. 79° E., 1.06 chs. dist.,  
with scribe marks T24N R30E 12 BT visible on partially  
healed blaze.

A piñon, 14 ins. diam., bears S. 85° E., 1.15 chs. dist.,  
with illegible scribe marks visible on partially healed  
blaze.

There is no remaining evidence of the original stone.

At the cor. point

Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam.,  
24 ins. in the ground, with brass cap mkd.

T 24 N R 30 E  
S 11 | S 12  
S 14 | S 13

2001

Deposit a magnet in a white plastic case at the base of the  
stainless steel post.

---

From the cor. of secs. 25, 26, 35 and 36.

S. 89°44' W., bet. secs. 26 and 35.

**Dependent Resurvey of a Portion of the Subdivisional Lines,  
T. 24 N., R. 30 E., Gila and Salt River Meridian, Arizona**

CHAINS	
	Over gently rolling land, in Oak Spring Valley.
23.90	Black Creek, a wash, 60 ft. wide, 3 ft. deep, drains S. 60° W.
40.01	The 1/4 sec. cor. of secs. 26 and 35, monumented with a sandstone, 22 x 10 x 8 ins., firmly set, projecting 16 ins. above ground, in an embedded mound of stone, 2 1/2 ft. base, mkd. 1/4 on N. face.
	from which the original bearing trees
	<p style="padding-left: 40px;">A piñon, 12 ins. diam., bears S. 68° E., 47 lks. dist., with scribe marks 1/4 S35 BT visible on open blaze. (Record: S. 70° E.)</p>
	<p style="padding-left: 40px;">The root hole of an uprooted piñon, 14 ins. diam., lying nearby, bears N. 72 3/4° W., 56 lks. dist., with scribe marks 1/4 S26 visible on partially healed blaze. (Record: N. 70° W., 54 lks. dist.)</p>
	At the cor. point
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 15 ins. in the ground, to bedrock, in a supporting mound of stone, 4 ft. base, to top, with brass cap mkd.
	<p style="text-align: center;">T 24 N R 30 E S 26 1/4 ——— S 35</p> <p style="text-align: center;">2001</p>
	Deposit a magnet in a white plastic case at the base of the stainless steel post.
	Bury the original stone alongside the stainless steel post.
	<hr/> <p>From the cor. of secs. 23, 24, 25 and 26.</p> <p>S. 89°55' W., bet. secs. 23 and 26.</p>
	Over gently rolling land, in Oak Spring Valley.
10.74	A brass tablet, 3 1/2 ins. diam., set flush in a PVC lined concrete collar, 7 ins. diam., set flush with the surface of the ground, bears North, 35 lks. dist., with top mkd. B.I.A. ROADS 19, and witnessed by an angle iron to the S., mkd. PT 23+496.62 on a side.
10.75	E. right-of-way fence of Navajo Route 12, barbed wire, 5 strands, parallels highway.

**Dependent Resurvey of a Portion of the Subdivisional Lines,  
T. 24 N., R. 30 E., Gila and Salt River Meridian, Arizona**

CHAINS	
11.89	Navajo Route 12, asphalt pavement, 40 ft. wide, bears N. and S.
13.01	W. right-of-way fence of Navajo Route 12, barbed wire, 5 strands, parallels highway.
13.02	A brass tablet, 3 1/2 ins. diam., set flush in a PVC lined concrete collar, 7 ins. diam., firmly set, projecting 3 ins. above ground, bears North, 40 lks. dist., with top mkd. B.I.A. ROADS 19, and witnessed by an angle iron to the N., mkd. PT 23+496.62 on a side.
37.28	Woven wire and barbed wire fence, bears S. 10° E. and N. 10° W.
39.90	<p>The 1/4 sec. cor. of secs. 23 and 26, determined at record bearing and distance from the remaining original bearing tree</p> <p style="padding-left: 40px;">A piñon, 18 ins. diam., bears S. 81° W., 3.42 chs. dist., with illegible scribe marks visible on partially healed blaze.</p>
	There is no remaining evidence of the original stone.
	At the cor. point
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.
	<p>T 24 N R 30 E</p> <p style="padding-left: 40px;">S 23</p> <p style="padding-left: 40px;">1/4 ———</p> <p style="padding-left: 40px;">S 26</p>
	2001
	Deposit a magnet in a white plastic case at the base of the stainless steel post.
	From this cor. point, a galvanized iron pipe, 3/4 ins. diam., firmly set, projecting 2 ins. above ground, bears S. 42°06' E., 10.05 chs. dist., without cap or markings; of unknown origin.
	—————
	N. 89°55' W., beginning new measurement.
	Over rolling land, on ascent from Oak Spring Valley.
36.90	Apache County Road C404, a graded road, 20 ft. wide, bears S. 40° E. in curve to right.
38.00	Barbed wire fence, 6 strands, bears S. 50° E. and N. 50° W.

**Dependent Resurvey of a Portion of the Subdivisional Lines,  
T. 24 N., R. 30 E., Gila and Salt River Meridian, Arizona**

CHAINS							
39.10	E. bank of a small flood plain, 8 ft. high, bears S. 30° E. and N. 30° W.						
39.83	<p>Point for the cor. of secs. 22, 23, 26 and 27, at proportionate dist.; there is no remaining evidence of the original witness cor.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <table border="1" data-bbox="808 611 1040 716"> <tr> <td colspan="2">T 24 N R 30 E</td> </tr> <tr> <td>S 22</td> <td>S 23</td> </tr> <tr> <td>S 27</td> <td>S 26</td> </tr> </table> <p align="center">2001</p> <p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p> <p>Cor. is located 15 lks. E. of a wash, 4 ft. wide, 2 ft. deep, drains S. 20° E.; 80 lks. E. of W. bank of flood plain, 8 ft. high, bears S. 20° E. and N. 20° W.; 1.23 chs. S. of a barbed wire fence, 6 strands, bears S. 50° E. and N. 50° W.; and 2.50 chs. S. of Apache County Road C404, a graded road, 20 ft. wide, bears S. 60° E. and N. 60° W.</p>	T 24 N R 30 E		S 22	S 23	S 27	S 26
T 24 N R 30 E							
S 22	S 23						
S 27	S 26						
	<p>S. 0°24' E., bet. secs. 26 and 27.</p> <p>Over rolling land, on gradual ascent.</p>						
40.08	<p>The 1/4 sec. cor. of secs. 26 and 27, established at record bearing and distance from the remaining original bearing tree</p> <p align="center">A multiple forked juniper, 15 ins. diam. on main trunk, bears S. 87° E., 71 lks. dist., with scribe marks 1/4 S26 BT visible on open blaze.</p> <p>There is no remaining evidence of the original stone.</p> <p>At the cor. point</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <table border="1" data-bbox="808 1675 1040 1780"> <tr> <td colspan="2">T 24 N R 30 E</td> </tr> <tr> <td colspan="2">1/4</td> </tr> <tr> <td>S 27</td> <td>S 26</td> </tr> </table> <p align="center">2001</p>	T 24 N R 30 E		1/4		S 27	S 26
T 24 N R 30 E							
1/4							
S 27	S 26						

**Dependent Resurvey of a Portion of the Subdivisional Lines,  
T. 24 N., R. 30 E., Gila and Salt River Meridian, Arizona**

CHAINS	
	<p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p> <p>Cor. is located 2.30 chs. N. of base of N. slope of a plateau, bears S. 30° E. and N. 30° W.</p> <hr/> <p>From the cor. of secs. 22, 23, 26 and 27.</p> <p>N. 0°15' W., bet. secs. 22 and 23.</p> <p>Over rolling land.</p>
2.92	A well casing, at center of a sandstone and concrete block, 4 ft. square, 4 ft. high, bears East, 1.03 chs. dist.
3.40	The SE cor. of abandoned stone building, 53 x 27 1/2 ft., bears West, 14 lks. dist., long side bears N. 10° W.
40.08	<p>Point for the 1/4 sec. cor. of secs. 22 and 23, at proportionate dist.; there is no remaining evidence of the original cor.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T 24 N R 30 E 1/4 S 22   S 23</p> <p style="text-align: center;">2001</p>
	<p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p> <p>Cor. is located atop left bank of a wash, 20 ft. wide, 6 ft. deep, drains S. 20° E.</p>
80.16	<p>The cor. of secs. 14, 15, 22 and 23, monumented with a sandstone, 21 x 13 x 4 ins. firmly set, projecting 10 ins. above ground, mkd. with 2 grooves on E. face and 3 grooves on S. face.</p> <p>from which the remaining original bearing trees</p> <p style="padding-left: 40px;">A juniper, 14 ins. diam., bears N. 27° E., 1.64 chs. dist., with scribe marks 24 30 14 visible on rotting open blaze.</p> <p style="padding-left: 40px;">A forked piñon, 19 ins. diam. at base, bears N. 17 1/4° W., 2.955 chs. dist., with scribe marks T24N R30E S BT visible on rotting open blaze. (Record: N. 18° W., 294 lks. dist.)</p> <p>At the cor. point</p>

**Dependent Resurvey of a Portion of the Subdivisional Lines,  
T. 24 N., R. 30 E., Gila and Salt River Meridian, Arizona**

CHAINS	
	<p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p align="center">           T 24 N R 30 E            S 15   S 14            S 22   S 23            2001         </p> <p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p> <p>Bury the original stone alongside the stainless steel post.</p> <hr/> <p>From the cor. of secs. 13, 14, 23 and 24.</p> <p>S. 89°58' W., bet. secs. 14 and 23.</p> <p>Over rolling land, in Oak Spring Valley.</p>
15.53	E. right-of-way fence of Navajo Route 12, barbed wire, 5 strands, parallels highway.
16.67	Navajo Route 12, asphalt pavement, 40 ft. wide, bears N. and S.
17.81	W. right-of-way fence of Navajo Route 12, barbed wire fence, 5 strands, parallels highway.
37.25	Barbed wire fence, 5 strands, bears N. 40° E. and S. 40° W.
38.00	Wash, 50 ft. wide, 8 ft. deep, drains S. 40° W.
38.70	Apache County Road C400, a graded road, 20 ft. wide, bears S. 50° E. and N. 50° W; and a power line, bears N. 30° E. and S. 30° W.
40.04	<p>Point for the 1/4 sec. cor. of secs. 14 and 23, at proportionate dist.; there is no remaining evidence of the original cor.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 12 ins. below the surface of the ground, with brass cap mkd.</p> <p align="center">           T 24 N R 30 E            S 14            1/4 ———            S 23            2001         </p>



**Dependent Resurvey of a Portion of the Subdivisional Lines,  
T. 24 N., R. 30 E., Gila and Salt River Meridian, Arizona**

CHAINS	
	from which
	<p>A stainless steel post, 28 ins. long, 2 1/2 ins. diam., set 24 ins. in the ground for a reference monument, bears S. 45°00' E., 265.0 ft. dist. with brass cap mkd. RM T24N R30E 1/4 S23 265.0 FT. TO COR. 2001 and an arrow pointing to the corner. Deposit a magnet in a white plastic case at the base of the stainless steel post.</p>
	<p>A steel manhole cover, in a concrete casing, 4 ft. diam., projecting 5 ins. above ground, bears S. 88 1/4° W., 91 1/2 lks. dist., mkd. SEWER.</p>
	<p>A stainless steel post, 28 ins. long, 2 1/2 ins. diam., set 24 ins. in the ground for a reference monument, bears N. 45°00' W., 75.0 ft. dist. with brass cap mkd. RM T24N R30E 1/4 S14 75.0 FT. TO COR. 2001 and an arrow pointing to the corner. Deposit a magnet in a white plastic case at the base of the stainless steel post.</p>
	<p>Deposit a magnet in a white plastic case at the base of the stainless steel post at the 1/4 sec. cor.</p>
	<p>Cor. is located in a graded road, 20 ft. wide, bears N. 60° E. and S. 60° W.</p>
80.08	The cor. of secs. 14, 15, 22 and 23.
	<hr/> <p>N. 0°15' W., bet. secs. 14 and 15.</p>
	Over rolling land.
40.08	<p>Point for the 1/4 sec. cor. of secs. 14 and 15, at proportionate dist.; there is no remaining evidence of the original cor.</p>
	<p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p>
	<p style="text-align: center;">T 24 N R 30 E 1/4 S 15   S 14</p>
	<p style="text-align: center;">2001</p>
	<p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p>
	<p>Cor. is located 77 lks. E. of a woven wire fence, bears S. 50° E. and N. 50° W.</p>

**Dependent Resurvey of a Portion of the Subdivisional Lines,  
T. 24 N., R. 30 E., Gila and Salt River Meridian, Arizona**

CHAINS							
80.16	<p>The cor. of secs. 10, 11, 14 and 15, monumented with a sandstone, 18 x 9 x 7 ins., firmly set, projecting 7 ins. above ground, mkd. with 2 grooves on E. face and 4 grooves on S. face.</p> <p>from which the original bearing trees</p> <p>A forked juniper, 15 ins. diam. at base, bears N. 65° E., 19 lks. dist., with scribe marks T24N R30E S11 BT visible on open blaze. (Record: 17 lks. dist.)</p> <p>A forked juniper, 21 ins. diam. at base, bears S. 31° E., 57 1/2 lks. dist., with scribe marks T24N R30E S14 BT visible on open blaze. (Record: 28 ins. diam., 56 lks. dist.)</p> <p>A forked juniper, 18 ins. diam. at base, bears S. 73 1/2° W., 20 lks. dist., with scribe marks T24N R30E S15 BT visible on open blaze. (Record: S. 65° W., 17 lks. dist.)</p> <p>A forked juniper, 35 ins. diam. at base, bears N. 25° W., 50 lks. dist., with scribe marks T24N R30E S BT visible on open blaze.</p> <p>At the cor. point</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <table data-bbox="812 1176 1039 1281" style="margin-left: auto; margin-right: auto;"> <tr> <td colspan="2" style="text-align: center;">T 24 N R 30 E</td> </tr> <tr> <td style="text-align: center;">S 10</td> <td style="text-align: center;">S 11</td> </tr> <tr> <td style="text-align: center;">S 15</td> <td style="text-align: center;">S 14</td> </tr> </table> <p style="text-align: center;">2001</p> <p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p> <p>Bury the original stone alongside the stainless steel post.</p> <hr/> <p>From the cor. of secs. 11, 12, 13 and 14.</p> <p>S. 89°55' W., bet. secs. 11 and 14.</p> <p>Over rolling land, in Oak Spring Valley.</p>	T 24 N R 30 E		S 10	S 11	S 15	S 14
T 24 N R 30 E							
S 10	S 11						
S 15	S 14						
14.29	<p>A brass tablet, 3 ins. diam., set flush in a concrete collar, 6 ins. diam., firmly set, projecting 3 ins. above ground, bears North, 26 lks. dist., with top mkd. B.I.A. ROADS 19; and witnessed by an angle iron to the S., mkd. PT 20+261.92 on a side.</p>						

**Dependent Resurvey of a Portion of the Subdivisional Lines,  
T. 24 N., R. 30 E., Gila and Salt River Meridian, Arizona**

CHAINS	
14.33	E. right-of-way fence of Navajo Route 12, barbed wire, 4 strands, parallels highway.
15.42	Navajo Route 12, asphalt pavement, 40 ft. wide, bears N. and S.
16.56	A brass tablet, 3 ins. diam., set flush in a concrete collar, 6 ins. diam., firmly set, projecting 2 ins. above ground, bears North, 23 lks. dist., with top mkd. B.I.A. ROADS 19; and witnessed by an angle iron to the S., mkd. PT 20+261.92 on a side.
40.06	The 1/4 sec. cor. of secs. 11 and 14, monumented with a sandstone, 13 x 10 x 3 ins., firmly set, projecting 5 ins. above ground, mkd. 1/4 on N. face.
	At the cor. point
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.
	T 24 N R 30 E S 11 1/4 ——— S 14
	2001
	Deposit a magnet in a white plastic case at the base of the stainless steel post.
	Bury the original stone alongside the stainless steel post.
	Cor. is located 1.10 chs. E. of left bank of a wash, 40 ft. wide, 20 ft. deep, bears S. 30° E. and N. 30° W.
	_____
	S. 89°53' W., beginning new measurement.
	Over rolling land, on ascent.
40.02	The cor. of secs. 10, 11, 14 and 15.
	_____
	From the cor. of secs. 22, 23, 26 and 27.
	S. 89°49' W., bet. secs. 22 and 27.
	Over rolling to broken land, on ascent of E. slope of a plateau.
39.83	The 1/4 sec. cor. of secs. 22 and 27, monumented with a sandstone, 16 x 15 x 9 ins., firmly set, projecting 8 ins. above ground, in an embedded collar of stone, mkd. 1/4 on N. face.



Dependent Resurvey of a Portion of the Subdivisional Lines,  
T. 24 N., R. 30 E., Gila and Salt River Meridian, Arizona

CHAINS

A juniper, 10 ins. diam., bears N.  $79\frac{1}{4}^{\circ}$  W., 28  $\frac{1}{2}$  lks. dist., with scribe marks 24 30E visible on partially healed blaze. (Record: piñon, 12 ins. diam., N.  $76^{\circ}$  W., 26 lks. dist.)

At the cor. point

Set a stainless steel post, 28 ins. long, 2  $\frac{1}{2}$  ins. diam., 24 ins. in the ground, with brass cap mkd.

T 24 N	R 30 E
S 21	S 22
S 28	S 27

2001

Deposit a magnet in a white plastic case at the base of the stainless steel post.

Bury the original stone alongside the stainless steel post.

---

N.  $0^{\circ}20'$  E., bet. secs. 21 and 22.

Over rolling and broken land, across E. slope of a plateau.

22.60 Wash, 10 ft. wide, 3 ft. deep, drains S.  $70^{\circ}$  E.

23.40 Apache County Road C404, a graded road, 20 ft. wide, bears E. and W.

40.15 The  $\frac{1}{4}$  sec. cor. of secs. 21 and 22, monumented with a sandstone, 16 x 9 x 5 ins., firmly set, projecting 9 ins. above ground, in an embedded collar of stone, mkd.  $\frac{1}{4}$  on W. face.

At the cor. point

Set a stainless steel post, 28 ins. long, 2  $\frac{1}{2}$  ins. diam., 24 ins. in the ground, with brass cap mkd.

T 24 N	R 30 E
	$\frac{1}{4}$
S 21	S 22

2001

Deposit a magnet in a white plastic case at the base of the stainless steel post.

**Dependent Resurvey of a Portion of the Subdivisional Lines,  
T. 24 N., R. 30 E., Gila and Salt River Meridian, Arizona**

CHAINS

Bury the original stone alongside the stainless steel post.

---

N. 0°21' W., beginning new measurement.

Over rolling and broken land, on descent across E. slope of a plateau.

40.05

The cor. of secs. 15, 16, 21 and 22, monumented with a sandstone, 18 x 12 x 9 ins., firmly set, projecting 6 ins. above ground, mkd. with 3 grooves on S. face and 3 grooves on E. face.

from which the original bearing trees

A piñon, 10 ins. diam., bears N. 63 1/2° E., 14 1/2 lks. dist., with scribe marks T24N R30E S15 BT visible on open blaze. (Record: N. 60° E., 13 lks. dist.)

A piñon, 10 ins. diam., bears S. 59 1/4° E., 69 1/2 lks. dist., with scribe marks T24N R30E S22 BT visible on open blaze. (Record: S. 58° E., 71 lks. dist.)

A piñon, 9 ins. diam., bears S. 35° W., 48 lks. dist., with scribe marks T24N R30E S21 BT visible on open blaze. (Record: 10 ins. diam.)

A piñon, 9 ins. diam., bears N. 51 3/4° W., 53 lks. dist., with scribe marks T24N R30E S16 BT visible on open blaze. (Record: 10 ins. diam., N. 54° W., 51 lks. dist.)

At the cor. point

Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.

T 24 N	R 30 E
S 16	S 15
S 21	S 22

2001

Deposit a magnet in a white plastic case at the base of the stainless steel post.

Bury the original stone alongside the stainless steel post.

---

From the cor. of secs. 14, 15, 22 and 23.

S. 89°52' W., bet. secs. 15 and 22.

**Dependent Resurvey of a Portion of the Subdivisional Lines,  
T. 24 N., R. 30 E., Gila and Salt River Meridian, Arizona**

CHAINS	
	Over rolling land, on gradual ascent.
40.11	The 1/4 sec. cor. of secs. 15 and 22, monumented with a sandstone, 24 x 16 x 5 ins., firmly set, projecting 12 ins. above ground, mkd. 1/4 on N. face.
	from which the remaining original bearing tree
	A piñon, 10 ins. diam., bears S. 49° W., 46 1/2 lks. dist., with scribe marks 1/4 S22 BT visible on open blaze. (Record: S. 50° W., 44 lks. dist.)
	At the cor. point
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.
	<p align="center">T 24 N R 30 E S 15 1/4 ——— S 22</p> <p align="center">2001</p>
	Deposit a magnet in a white plastic case at the base of the stainless steel post.
	Bury the original stone alongside the stainless steel post.
	S. 89°34' W., beginning new measurement.
	Over rolling and broken land, on ascent of E. slope of a plateau.
39.33	The cor. of secs. 15, 16, 21 and 22.
	N. 0°12' E., bet. secs. 15 and 16.
	Over broken and rolling land, on descent across E. slope of a plateau.
39.89	The 1/4 sec. cor. of secs. 15 and 16, monumented with a sandstone, 18 x 15 x 13 ins., firmly set, projecting 8 ins. above ground, mkd. 1/4 on W. face.
	from which the original bearing trees
	A piñon, 9 ins. diam., bears N. 75° E., 16 lks. dist., with scribe marks 1/4 S15 BT visible on open blaze. (Record: 18 lks. dist.)

**Dependent Resurvey of a Portion of the Subdivisional Lines,  
T. 24 N., R. 30 E., Gila and Salt River Meridian, Arizona**

CHAINS	
	<p>A tap root of an uprooted piñon, 12 ins. diam., lying nearby, bears N. 3° W., 39 lks. dist., with illegible scribe marks visible on open blaze.</p> <p>At the cor. point</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T 24 N R 30 E 1/4 S 16   S 15</p> <p style="text-align: center;">2001</p> <p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p> <p>Bury the original stone alongside the stainless steel post.</p> <hr/> <p>N. 0°14' W., beginning new measurement.</p> <p>Over rolling land, across ridges.</p>
40.07	<p>The cor. of secs. 9, 10, 15 and 16, monumented with a sandstone, 30 x 13 x 4 ins., firmly set, projecting 15 ins. above ground, mkd. with 4 grooves on S. face and 3 grooves on E. face.</p> <p>At the cor. point</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T 24 N R 30 E S 9   S 10 S 16   S 15</p> <p style="text-align: center;">2001</p> <p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p> <p>Bury the original stone alongside the stainless steel post.</p> <hr/> <p>From the cor. of secs. 10, 11, 14 and 15.</p> <p>S. 89°34' W., bet. secs. 10 and 15.</p>
39.56	<p>Point for the 1/4 sec. cor. of secs. 10 and 15, at proportionate dist.; there is no remaining evidence of the original cor.</p>



**Dependent Resurvey of a Portion of the Subdivisional Lines,  
T. 24 N., R. 30 E., Gila and Salt River Meridian, Arizona**

CHAINS	
	<p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p>
	<p style="text-align: center;">T 24 N   R 30 E           S 10           1/4 ———           S 15</p> <p style="text-align: center;">2001</p>
79.12	<p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p>
	<p>The cor. of secs. 9, 10, 15 and 16.</p>
	<hr/> <p style="text-align: center;"><b>Survey of the East Boundary, T. 24 N., R. 30 E., Gila and Salt River Meridian, Arizona</b></p> <hr/>
	<p>From the cor. of Tps. 23 and 24 N., Rs. 30 and 31 E., hereinbefore described.</p>
	<p>North, bet. secs. 31 and 36.</p>
	<p>Over rolling and broken land, on gradual ascent along E. slope of a ridge.</p>
40.00	<p>Point for the 1/4 sec. cor. of secs. 31 and 36.</p>
	<p>Set a brass tablet, 3 1/4 ins. diam., 2 1/2 ins. stem., cemented in place, in a drill hole, in sandstone bedrock, with top mkd.</p>
	<p style="text-align: center;">T 24 N R 30 E R 31 E           1/4 S 36   S 31</p> <p style="text-align: center;">2001</p>
80.00	<p>Deposit a magnet in a white plastic case in the drill hole beneath the brass tablet.</p>
	<p>Point for the cor. of secs. 25, 30, 31 and 36.</p>
	<p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., flush with the surface of the ground, with brass cap mkd.</p>

**Survey of the East Boundary,  
T. 24 N., R. 30 E., Gila and Salt River Meridian, Arizona**

CHAINS									
	<table border="1"> <tr><td align="center" colspan="2">T 24 N</td></tr> <tr><td align="center">R 30 E</td><td align="center">R 31 E</td></tr> <tr><td align="center">S 25</td><td align="center">S 30</td></tr> <tr><td align="center">S 36</td><td align="center">S 31</td></tr> </table>	T 24 N		R 30 E	R 31 E	S 25	S 30	S 36	S 31
T 24 N									
R 30 E	R 31 E								
S 25	S 30								
S 36	S 31								
	2001								
	Deposit a magnet in a white plastic case at the base of the stainless steel post.								
	Cor. is located in a faint trail road, bears N. 50° E. and S. 50° W.								
	Land, rolling and broken. Soil, sandy and rocky clay. Timber, ponderosa pine, piñon and juniper; undergrowth, brush and native grasses.								
	-----								
	North, bet. secs. 25 and 30.								
	Over rolling land, across a small valley.								
13.10	Graded road, 15 ft. wide, bears S. 50° E. and N. 50° W.								
29.50	Base of S. slope of a ridge, bears S. 40° E. and N. 40° W.; thence ascend.								
40.00	Point for the 1/4 sec. cor. of secs. 25 and 30.								
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.								
	<table border="1"> <tr><td align="center" colspan="2">T 24 N</td></tr> <tr><td align="center">R 30 E</td><td align="center">R 31 E</td></tr> <tr><td align="center" colspan="2">1/4</td></tr> <tr><td align="center">S 25</td><td align="center">S 30</td></tr> </table>	T 24 N		R 30 E	R 31 E	1/4		S 25	S 30
T 24 N									
R 30 E	R 31 E								
1/4									
S 25	S 30								
	2001								
	Deposit a magnet in a white plastic case at the base of the stainless steel post.								
	Thence over rolling and broken land, on steep descent of S. slope of a ridge.								
69.30	S. rim of same ridge, bears S. 30° E. and N. 30° W.; thence over rolling land, atop same ridge.								
80.00	Point for the cor. of secs. 19, 24, 25 and 30.								

**Survey of the East Boundary,  
T. 24 N., R. 30 E., Gila and Salt River Meridian, Arizona**

CHAINS									
	<p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <table style="margin-left: auto; margin-right: auto;"> <tr><td colspan="2" style="text-align: center;">T 24 N</td></tr> <tr><td style="text-align: center;">R 30 E</td><td style="text-align: center;">R 31 E</td></tr> <tr><td style="text-align: center;">S 24</td><td style="text-align: center;">S 19</td></tr> <tr><td style="text-align: center;">S 25</td><td style="text-align: center;">S 30</td></tr> </table> <p style="text-align: center;">2001</p> <p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p> <p>Land, rolling and broken. Soil, sandy and rocky clay with sandstone outcrops. Timber, piñon, juniper and ponderosa pine; undergrowth, brush and native grasses.</p> <hr/> <p>North, bet. secs. 19 and 24.</p> <p>Over rolling land, atop a ridge.</p>	T 24 N		R 30 E	R 31 E	S 24	S 19	S 25	S 30
T 24 N									
R 30 E	R 31 E								
S 24	S 19								
S 25	S 30								
3.30	N. rim of same ridge, bears N. 80° E. and S. 80° W.; thence over broken land, across a canyon and another ridge.								
40.00	<p>Point for the 1/4 sec. cor. of secs. 19 and 24.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <table style="margin-left: auto; margin-right: auto;"> <tr><td colspan="2" style="text-align: center;">T 24 N</td></tr> <tr><td style="text-align: center;">R 30 E</td><td style="text-align: center;">R 31 E</td></tr> <tr><td colspan="2" style="text-align: center;">1/4</td></tr> <tr><td style="text-align: center;">S 24</td><td style="text-align: center;">S 19</td></tr> </table> <p style="text-align: center;">2001</p> <p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p>	T 24 N		R 30 E	R 31 E	1/4		S 24	S 19
T 24 N									
R 30 E	R 31 E								
1/4									
S 24	S 19								
43.30	Base of N. slope of a ridge, bears N. 80° E. and S. 80° W.; thence across a narrow valley.								
51.20	Base of S. slope of a ridge, bears S. 80° E. and N. 80° W.; thence over broken land, on steep ascent.								
64.20	S. rim of same ridge, bears N. 70° E. and S. 70° W.; thence over rolling land, atop same ridge.								
80.00	Point for the cor. of secs. 13, 18, 19 and 24.								

**Survey of the East Boundary,  
T. 24 N., R. 30 E., Gila and Salt River Meridian, Arizona**

CHAINS									
	<p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <table style="margin-left: auto; margin-right: auto;"> <tr><td colspan="2" style="text-align: center;">T 24 N</td></tr> <tr><td style="text-align: center;">R 30 E</td><td style="text-align: center;">R 31 E</td></tr> <tr><td style="text-align: center;">S 13</td><td style="text-align: center;">S 18</td></tr> <tr><td style="text-align: center;">S 24</td><td style="text-align: center;">S 19</td></tr> </table> <p style="text-align: center;">2001</p> <p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p> <p>Land, rolling and broken. Soil, sandy and rocky clay with sandstone outcrops. Timber, piñon, juniper and ponderosa pine; undergrowth, brush and native grasses.</p> <hr/> <p>North, bet. secs. 13 and 18.</p> <p>Over rolling land, atop a ridge.</p>	T 24 N		R 30 E	R 31 E	S 13	S 18	S 24	S 19
T 24 N									
R 30 E	R 31 E								
S 13	S 18								
S 24	S 19								
5.10	N. rim of same ridge, bears N. 30° E. and S. 30° W.; thence over broken land, on steep descent into a valley.								
19.40	Apache County Road C402, a graded road, 24 ft. wide, bears N. 60° E. and S. 60° W.; thence over gently rolling land, in a valley.								
23.50	Black Creek, a wash, 50 ft. wide, 15 ft. deep, drains N. 50° W.								
36.07	Woven wire and barbed wire fence, on S. edge of a formerly cultivated field, bears N. 15° E. and S. 15° W.; thence across a field.								
40.00	<p>Point for the 1/4 sec. cor. of secs. 13 and 18.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <table style="margin-left: auto; margin-right: auto;"> <tr><td colspan="2" style="text-align: center;">T 24 N</td></tr> <tr><td style="text-align: center;">R 30 E</td><td style="text-align: center;">R 31 E</td></tr> <tr><td colspan="2" style="text-align: center;">1/4</td></tr> <tr><td style="text-align: center;">S 13</td><td style="text-align: center;">S 18</td></tr> </table> <p style="text-align: center;">2001</p> <p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p>	T 24 N		R 30 E	R 31 E	1/4		S 13	S 18
T 24 N									
R 30 E	R 31 E								
1/4									
S 13	S 18								

**Survey of the East Boundary,  
T. 24 N., R. 30 E., Gila and Salt River Meridian, Arizona**

CHAINS									
	<p>Cor. is located in an formerly cultivated field, 1.76 chs. S. of a woven wire and barbed wire fence, bears S. 70° E. and N. 70° W.; and 1.22 chs. W. of a woven wire and barbed wire fence, bears N. 20° E. and S. 20° W.</p> <p>From this cor. point, a sandstone, 20 x 7 x 6 ins., lying atop a mound of stone, 2 ft. base, 1 ft. high, bears S. 64°21' W., 15.12 chs. dist., mkd. 1/4 on a face; of unknown origin, and not utilized during the course of this survey.</p> <p>Thence over gently rolling to broken land, on ascent from a valley.</p>								
79.85	S. edge of a sandstone ledge, 12 ft. high, bears E. and W.								
80.00	<p>Point for the cor. of secs. 7, 12, 13 and 18.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <table border="1" data-bbox="808 915 1049 1045"> <tr><td colspan="2" style="text-align:center">T 24 N</td></tr> <tr><td style="text-align:center">R 30 E</td><td style="text-align:center">R 31 E</td></tr> <tr><td style="text-align:center">S 12</td><td style="text-align:center">S 7</td></tr> <tr><td style="text-align:center">S 13</td><td style="text-align:center">S 18</td></tr> </table> <p style="text-align:center">2001</p> <p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p> <p>Land, rolling, gently rolling and broken. Soil, sandy and rocky clay with sandstone outcrops. Timber, piñon, juniper and ponderosa pine on ridges; undergrowth, brush and native grasses.</p>	T 24 N		R 30 E	R 31 E	S 12	S 7	S 13	S 18
T 24 N									
R 30 E	R 31 E								
S 12	S 7								
S 13	S 18								
40.00	<p>North, bet. secs. 7 and 12.</p> <p>Over rolling and broken land, across E. slope of a mesa.</p> <p>Point for the 1/4 sec. cor. of secs. 7 and 12.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <table border="1" data-bbox="824 1682 1032 1797"> <tr><td colspan="2" style="text-align:center">T 24 N</td></tr> <tr><td style="text-align:center">R 30 E</td><td style="text-align:center">R 31 E</td></tr> <tr><td colspan="2" style="text-align:center">1/4</td></tr> <tr><td style="text-align:center">S 12</td><td style="text-align:center">S 7</td></tr> </table> <p style="text-align:center">2001</p>	T 24 N		R 30 E	R 31 E	1/4		S 12	S 7
T 24 N									
R 30 E	R 31 E								
1/4									
S 12	S 7								

**Survey of the East Boundary,  
T. 24 N., R. 30 E., Gila and Salt River Meridian, Arizona**

CHAINS									
	Deposit a magnet in a white plastic case at the base of the stainless steel post.								
71.10	S. rim of a ridge, bears N. 20° E. and S. 20° W.; thence over rolling land, atop a ridge.								
80.00	Point for the cor. of secs. 1, 6, 7 and 12.  Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.								
	<table style="margin-left: auto; margin-right: auto;"> <tr><td colspan="2" style="text-align: center;">T 24 N</td></tr> <tr><td style="text-align: center;">R 30 E</td><td style="text-align: center;">R 31 E</td></tr> <tr><td style="text-align: center;">S 1</td><td style="text-align: center;">S 6</td></tr> <tr><td style="text-align: center;">S 12</td><td style="text-align: center;">S 7</td></tr> </table>	T 24 N		R 30 E	R 31 E	S 1	S 6	S 12	S 7
T 24 N									
R 30 E	R 31 E								
S 1	S 6								
S 12	S 7								
	2001								
	Deposit a magnet in a white plastic case at the base of the stainless steel post.								
	Land, rolling and broken. Soil, sandy and rocky clay with sandstone outcrops. Timber, piñon, juniper and ponderosa pine; undergrowth, brush and native grasses.								
	North, bet. secs. 1 and 6.								
	Over rolling and broken land, atop a ridge.								
40.00	Point for the 1/4 sec. cor. of secs. 1 and 6.  Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.								
	<table style="margin-left: auto; margin-right: auto;"> <tr><td colspan="2" style="text-align: center;">T 24 N</td></tr> <tr><td style="text-align: center;">R 30 E</td><td style="text-align: center;">R 31 E</td></tr> <tr><td colspan="2" style="text-align: center;">1/4</td></tr> <tr><td style="text-align: center;">S 1</td><td style="text-align: center;">S 6</td></tr> </table>	T 24 N		R 30 E	R 31 E	1/4		S 1	S 6
T 24 N									
R 30 E	R 31 E								
1/4									
S 1	S 6								
	2001								
	Deposit a magnet in a white plastic case at the base of the stainless steel post.								
80.00	Point for the 80 1/16 sec. cor. of secs. 1 and 6.  Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.								

**Survey of the East Boundary,  
T. 24 N., R. 30 E., Gila and Salt River Meridian, Arizona**

CHAINS	<p style="text-align: center;">T 24 N R 30 E R 31 E 80 1/16 S 1   S 6</p> <p style="text-align: center;">2001</p> <p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p>
90.24	<p>Point for the closing cor. of Tps. 24 N., Rs. 30 and 31 E., at intersection with the Sixth Standard Parallel North, on the N. bdy. of the Tp.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T 25 N R 30 E S 35 ----- S 1   S 6 R 30 E   R 31 E T 24 N CC</p> <p style="text-align: center;">2001</p> <p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p> <p>From this cor. point, the stan. cor. of secs. 35 and 36, T. 25 N., R. 30 E., bears S. 89°58' E., 29.515 chs. dist., monumented with a stainless steel post, 2 1/2 ins. diam., with brass cap, set, mkd. and witnessed as described in the field notes of the dependent resurvey of a portion of the Sixth Standard Parallel North, (south boundary), T. 25 N., R. 30 E., executed concurrently under this same group.</p> <p>From this same cor. point, the stan. 1/4 sec. cor. of sec. 35, T. 25 N., R. 30 E., bears N. 89°58' W., 10.525 chs. dist., monumented with an iron post, 1 in. diam., with brass cap, set, mkd. and witnessed as described in the field notes of the dependent resurvey of a portion of the Sixth Standard Parallel North, (south boundary), T. 25 N., R. 30 E., executed concurrently under this same group.</p>

**Survey of the East Boundary,  
T. 24 N., R. 30 E., Gila and Salt River Meridian, Arizona**

CHAINS

Land, rolling and broken.  
Soil, sandy and rocky clay with sandstone outcrops.  
Timber, piñon, juniper and ponderosa pine; undergrowth, brush and native grasses.

---

**Survey of the West Boundary,  
T. 24 N., R. 30 E., Gila and Salt River Meridian, Arizona**

---

From the cor. of Tps. 23 and 24 N., R. 30 E. only, hereinbefore described.

North, on the W. bdy. of sec. 31.

Over gently rolling land, atop a plateau.

36.45 Point for the 1/4 sec. cor. of sec. 36 only, T. 24 N., R. 29 E., at 40 chs. northing from the cor. of Tps. 23 and 24 N., R. 29 E. only, hereinbefore described.

Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.

T 24 N  
R 29 E | R 30 E  
1/4 S 36 |

2001

Deposit a magnet in a white plastic case at the base of the stainless steel post.

Cor. is located 50 lks. W. of a trail road, bears S. 30° E. and N. 30° W.

40.00 Point for the 1/4 sec. cor. of sec. 31 only, T. 24 N., R. 30 E.

Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.

T 24 N  
R 29 E | R 30 E  
| 1/4 S 31

2001

Deposit a magnet in a white plastic case at the base of the stainless steel post.

Cor. is located 70 lks. E. of a trail road, bears S. 20° E. and N. 20° W.



**Survey of the West Boundary,  
T. 24 N., R. 30 E., Gila and Salt River Meridian, Arizona**

CHAINS													
76.45	<p>Point for the cor. of secs. 25 and 36 only, T. 24 N., R. 29 E.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <table style="margin-left: auto; margin-right: auto; border-collapse: collapse;"> <tr> <td style="padding: 0 5px;">T 24 N</td> <td style="border-left: 1px solid black; padding: 0 5px;">T 24 N</td> <td></td> </tr> <tr> <td style="padding: 0 5px;">S 25</td> <td style="border-left: 1px solid black; padding: 0 5px;"></td> <td></td> </tr> <tr> <td style="padding: 0 5px;">S 36</td> <td style="border-left: 1px solid black; padding: 0 5px;">R30E</td> <td></td> </tr> <tr> <td style="padding: 0 5px;">R 29 E</td> <td style="border-left: 1px solid black; padding: 0 5px;">S 31</td> <td></td> </tr> </table> <p style="text-align: center;">2001</p> <p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p> <p>Cor. is located 1.40 chs. E. of a trail road, bears N. 5° E. and S. 5° W.</p>	T 24 N	T 24 N		S 25			S 36	R30E		R 29 E	S 31	
T 24 N	T 24 N												
S 25													
S 36	R30E												
R 29 E	S 31												
80.00	<p>Point for the cor. of secs. 30 and 31 only, T. 24 N., R. 30 E.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <table style="margin-left: auto; margin-right: auto; border-collapse: collapse;"> <tr> <td style="padding: 0 5px;">T 24 N</td> <td style="border-left: 1px solid black; padding: 0 5px;">T 24 N</td> <td></td> </tr> <tr> <td style="padding: 0 5px;">R 29 E</td> <td style="border-left: 1px solid black; padding: 0 5px;">S 30</td> <td></td> </tr> <tr> <td style="padding: 0 5px;">S 25</td> <td style="border-left: 1px solid black; padding: 0 5px;">S 31</td> <td></td> </tr> <tr> <td style="padding: 0 5px;"></td> <td style="border-left: 1px solid black; padding: 0 5px;">R 30 E</td> <td></td> </tr> </table> <p style="text-align: center;">2001</p> <p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p> <p>Cor. is located 1.25 chs. E. of a trail road, bears N. and S.</p> <p>Land, gently rolling. Soil, sandy and rocky clay. Timber, ponderosa pine, piñon and juniper; undergrowth, brush and native grasses.</p> <hr style="width: 50%; margin-left: 0;"/> <p>North, on the W. bdy. of sec. 30.</p> <p>Over gently rolling land, atop a plateau.</p>	T 24 N	T 24 N		R 29 E	S 30		S 25	S 31			R 30 E	
T 24 N	T 24 N												
R 29 E	S 30												
S 25	S 31												
	R 30 E												
36.45	<p>Point for the 1/4 sec. cor. of sec. 25 only, T. 24 N., R. 29 E.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p>												

**Survey of the West Boundary,  
T. 24 N., R. 30 E., Gila and Salt River Meridian, Arizona**

CHAINS																
	T 24 N R 29 E   R 30 E 1/4 S 25															
	2001															
	Deposit a magnet in a white plastic case at the base of the stainless steel post.															
40.00	Point for the 1/4 sec. cor. of sec. 30 only, T. 24 N., R. 30 E.  Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.															
	T 24 N R 29 E   R 30 E   1/4 S 30															
	2001															
	Deposit a magnet in a white plastic case at the base of the stainless steel post.															
67.10	S. rim of canyon of West Fork Black Creek, bears S. 40° E. and N. 40° W.; thence across canyon.															
73.40	N. rim of same canyon, bears S. 50° E. and N. 50° W.; thence over rolling land, atop a plateau.															
76.45	Point for the cor. of secs. 24 and 25 only, T. 24 N., R. 29 E.  Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.															
	<table border="0"> <tr> <td>T 24 N</td> <td> </td> <td>T 24 N</td> </tr> <tr> <td>S 24</td> <td> </td> <td></td> </tr> <tr> <td colspan="2"><hr/></td> <td>R30E</td> </tr> <tr> <td>S 25</td> <td> </td> <td></td> </tr> <tr> <td>R 29 E</td> <td> </td> <td>S 30</td> </tr> </table>	T 24 N		T 24 N	S 24			<hr/>		R30E	S 25			R 29 E		S 30
T 24 N		T 24 N														
S 24																
<hr/>		R30E														
S 25																
R 29 E		S 30														
	2001															
	Deposit a magnet in a white plastic case at the base of the stainless steel post.															
80.00	Point for the cor. of secs. 19 and 30 only, T. 24 N., R. 30 E.  Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.															

**Survey of the West Boundary,  
T. 24 N., R. 30 E., Gila and Salt River Meridian, Arizona**

CHAINS	<table style="margin-left: auto; margin-right: auto; border-collapse: collapse;"> <tr> <td style="border-right: 1px solid black; padding: 2px 10px;">T 24 N</td> <td style="padding: 2px 10px;">T 24 N</td> </tr> <tr> <td style="border-right: 1px solid black; padding: 2px 10px;"></td> <td style="padding: 2px 10px;">S 19</td> </tr> <tr> <td style="border-right: 1px solid black; padding: 2px 10px;">R 29 E</td> <td style="padding: 2px 10px;">S 30</td> </tr> <tr> <td style="border-right: 1px solid black; padding: 2px 10px;">S 24</td> <td style="padding: 2px 10px;">R 30 E</td> </tr> </table> <p align="center">2001</p> <p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p> <p>Land, gently rolling to broken to rolling. Soil, sandy and rocky clay with sandstone outcrops. Timber, ponderosa pine, piñon and juniper; undergrowth, brush and native grasses.</p> <hr/> <p>North, on the W. bdy. of sec. 19.</p> <p>Over gently rolling land, atop a plateau.</p>	T 24 N	T 24 N		S 19	R 29 E	S 30	S 24	R 30 E
T 24 N	T 24 N								
	S 19								
R 29 E	S 30								
S 24	R 30 E								
36.45	<p>Point for the 1/4 sec. cor. of sec. 24 only, T. 24 N., R. 29 E.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <table style="margin-left: auto; margin-right: auto; border-collapse: collapse;"> <tr> <td colspan="2" style="padding: 2px 10px;">T 24 N</td> </tr> <tr> <td style="border-right: 1px solid black; padding: 2px 10px;">R 29 E</td> <td style="padding: 2px 10px;">R 30 E</td> </tr> <tr> <td style="border-right: 1px solid black; padding: 2px 10px;">1/4 S 24</td> <td style="padding: 2px 10px;"></td> </tr> </table> <p align="center">2001</p> <p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p>	T 24 N		R 29 E	R 30 E	1/4 S 24			
T 24 N									
R 29 E	R 30 E								
1/4 S 24									
40.00	<p>Point for the 1/4 sec. cor. of sec. 19 only, T. 24 N., R. 30 E.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <table style="margin-left: auto; margin-right: auto; border-collapse: collapse;"> <tr> <td colspan="2" style="padding: 2px 10px;">T 24 N</td> </tr> <tr> <td style="border-right: 1px solid black; padding: 2px 10px;">R 29 E</td> <td style="padding: 2px 10px;">R 30 E</td> </tr> <tr> <td style="border-right: 1px solid black; padding: 2px 10px;"></td> <td style="padding: 2px 10px;">1/4 S 19</td> </tr> </table> <p align="center">2001</p> <p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p>	T 24 N		R 29 E	R 30 E		1/4 S 19		
T 24 N									
R 29 E	R 30 E								
	1/4 S 19								
67.50	<p>S. rim of canyon of West Fork Black Creek, bears S. 40° E. and N. 40° W.; thence across canyon.</p>								

**Survey of the West Boundary,  
T. 24 N., R. 30 E., Gila and Salt River Meridian, Arizona**

CHAINS											
75.80	N. rim of same canyon, bears S. 40° E. and N. 40° W.; thence over gently rolling land, atop a plateau.										
76.45	Point for the cor. of secs. 13 and 24 only, T. 24 N., R. 29 E.  Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.  <table style="margin-left: auto; margin-right: auto; border-collapse: collapse;"> <tr> <td style="padding: 0 5px;">T 24 N</td> <td style="border-left: 1px solid black; padding: 0 5px;">T 24 N</td> </tr> <tr> <td style="padding: 0 5px;">S 13</td> <td style="border-left: 1px solid black; padding: 0 5px;"></td> </tr> <tr> <td style="border-top: 1px solid black; padding: 0 5px;">S 24</td> <td style="border-left: 1px solid black; padding: 0 5px;">R30E</td> </tr> <tr> <td style="padding: 0 5px;">R 29 E</td> <td style="border-left: 1px solid black; padding: 0 5px;">S 19</td> </tr> </table> <p align="center">2001</p> <p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p>	T 24 N	T 24 N	S 13		S 24	R30E	R 29 E	S 19		
T 24 N	T 24 N										
S 13											
S 24	R30E										
R 29 E	S 19										
80.00	Point for the cor. of secs. 18 and 19 only, T. 24 N., R. 30 E.  Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.  <table style="margin-left: auto; margin-right: auto; border-collapse: collapse;"> <tr> <td style="padding: 0 5px;">T 24 N</td> <td style="border-left: 1px solid black; padding: 0 5px;">T 24 N</td> </tr> <tr> <td style="padding: 0 5px;"></td> <td style="border-left: 1px solid black; padding: 0 5px;">S 18</td> </tr> <tr> <td style="padding: 0 5px;">R 29 E</td> <td style="border-left: 1px solid black; padding: 0 5px;"></td> </tr> <tr> <td style="padding: 0 5px;"></td> <td style="border-left: 1px solid black; padding: 0 5px;">S 19</td> </tr> <tr> <td style="padding: 0 5px;">S 13</td> <td style="border-left: 1px solid black; padding: 0 5px;">R 30 E</td> </tr> </table> <p align="center">2001</p> <p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p> <p>Land, gently rolling and broken. Soil, sandy and rocky clay with sandstone outcrops. Timber, ponderosa pine, piñon and juniper; undergrowth, brush and native grasses.</p> <hr/> <p>North, on the W. bdy. of sec. 18.</p> <p>Over rolling land, atop a plateau.</p>	T 24 N	T 24 N		S 18	R 29 E			S 19	S 13	R 30 E
T 24 N	T 24 N										
	S 18										
R 29 E											
	S 19										
S 13	R 30 E										
28.50	Apache County Road C404, a graded road, 26 ft. wide, bears S. 70° E. and N. 70° W.										
36.45	Point for the 1/4 sec. cor. of sec. 13 only, T. 24 N., R. 29 E.  Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.										

**Survey of the West Boundary,  
T. 24 N., R. 30 E., Gila and Salt River Meridian, Arizona**

CHAINS									
	T 24 N R 29 E   R 30 E 1/4 S 13								
	2001								
	Deposit a magnet in a white plastic case at the base of the stainless steel post.								
40.00	Point for the 1/4 sec. cor. of sec. 18 only, T. 24 N., R. 30 E.  Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.								
	T 24 N R 29 E   R 30 E   1/4 S 18								
	2001								
	Deposit a magnet in a white plastic case at the base of the stainless steel post.								
76.45	Point for the cor. of secs. 12 and 13 only, T. 24 N., R. 29 E.  Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.								
	<table style="margin: auto;"> <tr> <td style="border-right: 1px solid black; padding-right: 5px;">T 24 N</td> <td style="padding-left: 5px;">T 24 N</td> </tr> <tr> <td style="border-right: 1px solid black; padding-right: 5px;">S 12</td> <td style="padding-left: 5px;">R30E</td> </tr> <tr> <td style="border-right: 1px solid black; padding-right: 5px;">S 13</td> <td style="padding-left: 5px;">S 18</td> </tr> <tr> <td style="border-right: 1px solid black; padding-right: 5px;">R 29 E</td> <td style="padding-left: 5px;"></td> </tr> </table>	T 24 N	T 24 N	S 12	R30E	S 13	S 18	R 29 E	
T 24 N	T 24 N								
S 12	R30E								
S 13	S 18								
R 29 E									
	2001								
	Deposit a magnet in a white plastic case at the base of the stainless steel post.								
80.00	Point for the cor. of secs. 7 and 18 only, T. 24 N., R. 30 E.  Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.								
	<table style="margin: auto;"> <tr> <td style="border-right: 1px solid black; padding-right: 5px;">T 24 N</td> <td style="padding-left: 5px;">T 24 N</td> </tr> <tr> <td style="border-right: 1px solid black; padding-right: 5px;">R 29 E</td> <td style="padding-left: 5px;">S 7</td> </tr> <tr> <td style="border-right: 1px solid black; padding-right: 5px;">S 12</td> <td style="padding-left: 5px;">S 18</td> </tr> <tr> <td style="border-right: 1px solid black; padding-right: 5px;"></td> <td style="padding-left: 5px;">R 30 E</td> </tr> </table>	T 24 N	T 24 N	R 29 E	S 7	S 12	S 18		R 30 E
T 24 N	T 24 N								
R 29 E	S 7								
S 12	S 18								
	R 30 E								
	2001								

**Survey of the West Boundary,  
T. 24 N., R. 30 E., Gila and Salt River Meridian, Arizona**

CHAINS	
	<p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p> <p>Land, rolling. Soil, sandy and rocky clay. Timber, ponderosa pine, piñon and juniper; undergrowth, brush and native grasses.</p> <hr/> <p>North, on the W. bdy. of sec. 7.</p> <p>Over rolling land, atop a plateau.</p>
16.70	S. rim of canyon of West Fork Black Creek, bears S. 50° E. and N. 50° W.; thence across canyon.
20.20	N. rim of same canyon, bears S. 80° E. and N. 80° W.; thence over rolling land, atop a plateau.
36.45	<p>Point for the 1/4 sec. cor. of sec. 12 only, T. 24 N., R. 29 E.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 23 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center;"> <p>T 24 N R 29 E   R 30 E 1/4 S 12  </p> <p>2001</p> </div>
40.00	<p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p> <p>Point for the 1/4 sec. cor. of sec. 7 only, T. 24 N., R. 30 E.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center;"> <p>T 24 N R 29 E   R 30 E   1/4 S 7</p> <p>2001</p> </div>
76.45	<p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p> <p>Point for the cor. of secs. 1 and 12 only, T. 24 N., R. 29 E.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 22 ins. in the ground, in a collar of stone, with brass cap mkd.</p>

**Survey of the West Boundary,  
T. 24 N., R. 30 E., Gila and Salt River Meridian, Arizona**

CHAINS									
	<table style="margin-left: auto; margin-right: auto;"> <tr> <td style="border-right: 1px solid black; padding: 0 5px;">T 24 N</td> <td style="padding: 0 5px;">T 24 N</td> </tr> <tr> <td style="border-right: 1px solid black; padding: 0 5px;">S 1</td> <td style="padding: 0 5px;">R30E</td> </tr> <tr> <td style="border-right: 1px solid black; padding: 0 5px;">S 12</td> <td style="padding: 0 5px;">S 7</td> </tr> <tr> <td style="border-right: 1px solid black; padding: 0 5px;">R 29 E</td> <td style="padding: 0 5px;"></td> </tr> </table>	T 24 N	T 24 N	S 1	R30E	S 12	S 7	R 29 E	
T 24 N	T 24 N								
S 1	R30E								
S 12	S 7								
R 29 E									
	2001								
	Deposit a magnet in a white plastic case at the base of the stainless steel post.								
	Cor. is located 40 lks. W. of W. rim of canyon of West Fork Black Creek, bears S. 10° E. and N. 10° W.								
80.00	Point for the cor. of secs. 6 and 7 only, T. 24 N., R. 30 E.								
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.								
	<table style="margin-left: auto; margin-right: auto;"> <tr> <td style="border-right: 1px solid black; padding: 0 5px;">T 24 N</td> <td style="padding: 0 5px;">T 24 N</td> </tr> <tr> <td style="border-right: 1px solid black; padding: 0 5px;">R 29 E</td> <td style="padding: 0 5px;">S 6</td> </tr> <tr> <td style="border-right: 1px solid black; padding: 0 5px;">S 1</td> <td style="padding: 0 5px;">S 7</td> </tr> <tr> <td style="border-right: 1px solid black; padding: 0 5px;"></td> <td style="padding: 0 5px;">R 30 E</td> </tr> </table>	T 24 N	T 24 N	R 29 E	S 6	S 1	S 7		R 30 E
T 24 N	T 24 N								
R 29 E	S 6								
S 1	S 7								
	R 30 E								
	2001								
	Deposit a magnet in a white plastic case at the base of the stainless steel post.								
	Cor. is located 1.00 ch. W. of W. rim of canyon of West Fork Black Creek, bears N. and S.								
	Land, rolling and broken. Soil, sandy and rocky clay with sandstone outcrops. Timber, ponderosa pine, piñon and juniper; undergrowth, brush and native grasses.								
	North, on the W. bdy. of sec. 6.								
	Over rolling and broken land, atop a plateau.								
15.90	Top of descent into West Fork Black Creek, bears S. 70° E. and N. 70° W.								
24.50	Top of ascent from West Fork Black Creek, bears S. 70° E. and N. 70° W.								
36.45	Point for the 1/4 sec. cor. of sec. 1 only, T. 24 N., R. 29 E.								
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.								

**Survey of the West Boundary,  
T. 24 N., R. 30 E., Gila and Salt River Meridian, Arizona**

CHAINS	
	T 24 N R 29 E   R 30 E 1/4 S 1
	2001
	Deposit a magnet in a white plastic case at the base of the stainless steel post.
40.00	Point for the 1/4 sec. cor. of sec. 6 only, T. 24 N., R. 30 E.
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.
	T 24 N R 29 E   R 30 E   1/4 S 6
	2001
	Deposit a magnet in a white plastic case at the base of the stainless steel post.
76.45	Point for the 80 1/16 sec. cor. of sec. 1 only, T. 24 N., R. 29 E.
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.
	T 24 N R 29 E   R 30 E 80 1/16   S 1
	2001
	Deposit a magnet in a white plastic case at the base of the stainless steel post.
80.00	Point for the 80 1/16 sec. cor. of sec. 6 only, T. 24 N., R. 30 E.
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.
	T 24 N R 29 E   R 30 E   80 1/16   S 6
	2001



**Survey of the West Boundary,  
T. 24 N., R. 30 E., Gila and Salt River Meridian, Arizona**

CHAINS	<p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p>																				
90.79	<p>Point for the closing cor. of Tps. 24 N., Rs. 29 and 30 E., at intersection with the Sixth Standard Parallel North, on the N. bdy. of the Tp.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center; margin: 10px 0;"> <table style="margin: auto; border-collapse: collapse;"> <tr> <td colspan="2">T 25 N</td> <td colspan="2">R 29 E</td> </tr> <tr> <td colspan="4">S 35</td> </tr> <tr> <td style="border-right: 1px solid black; padding: 0 5px;">S 1</td> <td style="padding: 0 5px;">S 6</td> <td style="border-right: 1px solid black; padding: 0 5px;">R 29 E</td> <td style="padding: 0 5px;">R 30 E</td> </tr> <tr> <td colspan="4">T 24 N</td> </tr> <tr> <td colspan="4">CC</td> </tr> </table> <p>2001</p> </div> <p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p> <p>From this cor. point, the stan. cor. of secs. 35 and 36, T. 25 N., R. 29 E., bears N. 89°59' E., 17.94 chs. dist., monumented with an iron post, 2 ins. diam., with brass cap, set, mkd. and witnessed as described in the field notes of the dependent resurvey of a portion of the Sixth Standard Parallel North, (south boundary), T. 25 N., R. 29 E., executed concurrently under this same group.</p> <p>From this same cor. point, the stan. 1/4 sec. cor. of sec. 35, T. 25 N., R. 29 E., bears S. 89°59' W., 22.05 chs. dist., monumented with a stainless steel post, 2 1/2 ins. diam., set, mkd. and witnessed as described in the field notes of the dependent resurvey of a portion of the Sixth Standard Parallel North, (south boundary), T. 25 N., R. 29 E., executed concurrently under this same group.</p> <p>Land, rolling and broken. Soil, sandy and rocky clay with sandstone outcrops. Timber, ponderosa pine, piñon and juniper; undergrowth, brush and native grasses.</p> <hr style="width: 60%; margin: 20px auto;"/> <p align="center"><b>Survey of a Portion of the Subdivisional Lines, T. 24 N., R. 30 E., Gila and Salt River Meridian, Arizona</b></p> <hr style="width: 60%; margin: 20px auto;"/> <p>From the cor. of secs. 25, 30, 31 and 36, on the E. bdy. of the Tp., hereinbefore described.</p> <p>S. 89°59' W., bet. secs. 25 and 36.</p>	T 25 N		R 29 E		S 35				S 1	S 6	R 29 E	R 30 E	T 24 N				CC			
T 25 N		R 29 E																			
S 35																					
S 1	S 6	R 29 E	R 30 E																		
T 24 N																					
CC																					

**Survey of a Portion of the Subdivisional Lines,  
T. 24 N., R. 30 E., Gila and Salt River Meridian, Arizona**

CHAINS	
	Over rolling and broken land, on ascent of E. slope of a ridge.
31.30	W. rim of same ridge, bears S. 20° E. and N. 20° W.; thence over broken land, on abrupt descent.
40.14	The 1/4 sec. cor. of secs. 25 and 36, hereinbefore described.  Land, rolling and broken. Soil, sandy and rocky clay and sandstone outcrops. Timber, ponderosa pine, piñon and juniper; undergrowth, brush and native grasses.
	<hr/>
	From the cor. of secs. 19, 24, 25 and 30, on the E. bdy. of the Tp., hereinbefore described.
	N. 89°39' W., bet. secs. 24 and 25.
	Over rolling land, atop a ridge.
3.10	W. rim of a ridge, bears N. 10° E. and S. 10° W.; thence over broken land, on descent of W. slope of same ridge.
25.60	Base of W. slope of same ridge, bears N. 10° E. and S. 10° W.; thence over rolling land, in a valley.
33.10	Wash, 15 ft. wide, 18 ft. deep, drains N. 10° E.
40.55	The 1/4 sec. cor. of secs. 24 and 25, hereinbefore described.  Land, rolling and broken. Soil, sandy and rocky clay and sandstone outcrops. Timber, ponderosa pine, piñon and juniper on ridge; undergrowth, brush and native grasses.
	<hr/>
	From the cor. of secs. 13, 18, 19 and 24, on the E. bdy. of the Tp., hereinbefore described.
	N. 88°26' W., bet. secs. 13 and 24.
	Over rolling land, atop a ridge.
5.50	W. rim of same ridge, bears N. 50° E. and S. 50° W.; thence over broken land, on abrupt descent.
13.38	An Angle Point on the line bet. secs. 13 and 24, hereinbefore described.

**Survey of a Portion of the Subdivisional Lines,  
T. 24 N., R. 30 E., Gila and Salt River Meridian, Arizona**

CHAINS	
	<p>Land, rolling and broken. Soil, sandy and rocky clay and sandstone outcrops. Timber, ponderosa pine, piñon and juniper; undergrowth, brush and native grasses.</p> <hr/> <p>From the cor. of secs. 7, 12, 13 and 18, on the E. bdy. of the Tp., hereinbefore described.</p> <p>N. 89°39' W., bet. secs. 12 and 13.</p> <p>Over broken land, on ascent of E. slope of a ridge.</p>
24.60	E. rim of same ridge, bears N. 20° E. and S. 20° W.; thence over rolling land, continuing ascent.
40.74	<p>Point for the 1/4 sec. cor. of secs. 12 and 13, at 40.00 chs. easting from the cor. of secs. 11, 12, 13 and 14, hereinbefore described.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center;"> <p>T 24 N R 30 E S 12 1/4 ——— S 13</p> <p>2001</p> </div> <p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p>
49.80	W. rim of same ridge, bears N. 10° E. and S. 10° W.; thence over broken land, on steep descent into a narrow valley and ascent of a narrow ridge.
71.80	Top of a narrow ridge, bears N. 10° E. and S. 10° W.; thence over broken land, on abrupt descent.
80.74	<p>The cor. of secs. 11, 12, 13 and 14, hereinbefore described.</p> <p>Land, broken and rolling. Soil, sandy and rocky clay and sandstone outcrops. Timber, ponderosa pine, piñon and juniper; undergrowth, brush and native grasses.</p> <hr/> <p>N. 0°01' W., bet. secs. 11 and 12.</p> <p>Over rolling land, along E. edge of a narrow valley.</p>
37.90	Wash, 10 ft. wide, 4 ft. deep, drains S. 70° W.

**Survey of a Portion of the Subdivisional Lines,  
T. 24 N., R. 30 E., Gila and Salt River Meridian, Arizona**

CHAINS	
40.00	<p>Point for the 1/4 sec. cor. of secs. 11 and 12.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T 24 N R 30 E 1/4 S 11   S 12</p> <p style="text-align: center;">2001</p> <p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p>
80.00	<p>Point for the cor. of secs. 1, 2, 11 and 12.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T 24 N R 30 E S 2   S 1 S 11   S 12</p> <p style="text-align: center;">2001</p> <p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p> <p>Land, rolling. Soil, sand and rocky clay. Timber, piñon and juniper; undergrowth, brush and native grasses.</p> <hr/> <p>From the cor. of secs. 1, 6, 7 and 12, on the E. bdy. of the Tp., hereinbefore described.</p> <p>N. 89°39' W., bet. secs. 1 and 12.</p> <p>Over rolling and broken land, on ascent of E. slope of a ridge.</p>
40.74	<p>Point for the 1/4 sec. cor. of secs. 1 and 12, at 40.00 chs. easting from the cor. of secs. 1, 2, 11 and 12.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p>

**Survey of a Portion of the Subdivisional Lines,  
T. 24 N., R. 30 E., Gila and Salt River Meridian, Arizona**

CHAINS	
	T 24 N R 30 E S 1 1/4 ——— S 12  2001
	Deposit a magnet in a white plastic case at the base of the stainless steel post.
	Cor. is located near top of W. slope of a ridge, bears N. 20° E. and S. 20° W.; thence over broken land, across a narrow valley.
54.70	Top of a narrow ridge, bears N. 10° E. and S. 10° W.; thence over broken land, across a narrow valley.
80.74	The cor. of secs. 1, 2, 11 and 12.  Land, rolling and broken. Soil, sandy and rocky clay and sandstone outcrops. Timber, ponderosa pine, piñon and juniper; undergrowth, brush and native grasses.
	—————
	N. 0°01' W., bet. secs. 1 and 2.  Over rolling land, on gradual ascent.
30.46	Navajo Route 12, asphalt pavement, 40 ft. wide, bears N. 30° E. and S. 30° W.
40.00	Point for the 1/4 sec. cor. of secs. 1 and 2.  Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.
	T 24 N R 30 E 1/4 S 2   S 1  2001
	Deposit a magnet in a white plastic case at the base of the stainless steel post.
	Thence over rolling and broken land, on gradual ascent.
80.00	Point for the 80 1/16 sec. cor. of secs. 1 and 2.  Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.

**Survey of a Portion of the Subdivisional Lines,  
T. 24 N., R. 30 E., Gila and Salt River Meridian, Arizona**

CHAINS	<p style="text-align: center;">T 24 N R 30 E 80 1/16 S 2   S 1  2001</p> <p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p> <p>Cor. is located 1.10 chs. S. of a wash, 15 ft. wide, 3 ft. deep, drains S. 40° E.; thence over broken land, on steep ascent.</p> <p>89.67 Point for the closing cor. of secs. 1 and 2, at intersection with the Sixth Standard Parallel North, on the N. bdy. of the Tp.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T 25 N R 30 E S 34 ----- S 2   S 1 T 24 N R 30 E CC  2001</p> <p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p> <p>From this cor. point, the stan. cor. of secs. 34 and 35, T. 25 N., R. 30 E., bears N. 89°54' E., 30.20 chs. dist., monumented with a stainless steel post, 2 1/2 ins diam., with brass cap, set, mkd. and witnessed as described in the field notes of the dependent resurvey of a portion of the Sixth Standard Parallel North, (south boundary), T. 25 N., R. 30 E., executed concurrently under this same group.</p> <p>From this same cor. point, the 1/4 sec. cor. of sec. 34, T. 25 N., R. 30 E., bears S. 89°54' W., 9.80 chs. dist., monumented with a stainless steel post, 2 1/2 ins. diam., with brass cap, set, mkd. and witnessed as described in the field notes of the dependent resurvey of a portion of the Sixth Standard Parallel North, (south boundary), T. 25 N., R. 30 E., executed concurrently under this same group.</p>
--------	---

**Survey of a Portion of the Subdivisional Lines,  
T. 24 N., R. 30 E., Gila and Salt River Meridian, Arizona**

CHAINS	
	<p>Land, rolling and broken. Soil, sandy and rocky clay. Timber, piñon and juniper; undergrowth, brush and native grasses.</p> <hr/> <p>Point for the 1/4 sec. cor. of sec. 1 only, T. 24 N., R. 30 E., at 40.00 chs. easting from the closing cor. of secs. 1 and 2, on the N. bdy. of sec. 1.</p> <p>Set a brass tablet, 3 1/4 ins. diam., 2 1/2 ins. stem, cemented in place, in a drill hole, in sandstone bedrock, with top mkd.</p> <p style="text-align: center;">T 25 N R 30 E ----- 1/4 S 1 T 24 N R 30 E</p> <p style="text-align: center;">2001</p> <p>Deposit a magnet in a white plastic case in the drill hole beneath the brass tablet.</p> <p>Cor. is located on W. slope of a sandstone ridge, bears N. 20° E. and S. 20° W.</p> <p>From this cor. point, the stan. 1/4 sec. cor. of sec. 35, T. 25 N., R. 30 E., bears N. 89°58' E., 30.21 chs. dist., hereinbefore described.</p> <p>From this same cor. point, the stan. cor. of secs. 34 and 35, T. 25 N., R. 30 E., bears S. 89°58' W., 9.80 chs. dist.</p> <hr/> <p>From the cor. of secs. 2, 3, 34 and 35, on the S. bdy. of the Tp., hereinbefore described.</p> <p>N. 0°01' W., bet. secs. 34 and 35.</p> <p>Over rolling land, atop a plateau.</p>
5.40	S. rim of canyon of Black Creek, bears S. 80° E. and N. 80° W.; thence over rugged land, on abrupt descent into canyon.
24.90	Black Creek, a wash, 150 ft. wide, 15 ft. deep, drains S. 80° W.; thence over rugged land, on ascent of N. slope of same canyon.
40.00	<p>Point for the 1/4 sec. cor. of secs. 34 and 35.</p> <p>Set a brass tablet, 3 1/4 ins. diam., 2 1/2 ins. stem., cemented in place, in a drill hole, in sandstone bedrock, with top mkd.</p>

**Survey of a Portion of the Subdivisional Lines,  
T. 24 N., R. 30 E., Gila and Salt River Meridian, Arizona**

CHAINS	
	T 24 N R 30 E 1/4 S 34   S 35  2001  Deposit a magnet in a white plastic case in the drill hole beneath the brass tablet.  Raise a mound of stone, 3 ft. base, 1 ft. high, W. of cor.
50.80	N. rim of canyon of Black Creek, bears N. 50° E. and S. 50° W.; thence over rolling land, atop a plateau.
72.20	N. rim of a plateau, bears S. 50° E. and N. 50° W.; thence over broken land, on descent from plateau.
80.00	Point for the cor. of secs. 26, 27, 34 and 35.  Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 16 ins. in the ground, to bedrock, in a supporting mound of stone, 3 ft. base, to top, with brass cap mkd.  T 24 N R 30 E S 27   S 26 S 34   S 35  2001  Deposit a magnet in a white plastic case at the base of the stainless steel post.  Land, rolling, rugged and broken. Soil, sandy and rocky clay with sandstone outcrops. Timber, ponderosa pine, piñon and juniper; undergrowth, brush and native grasses.
	<hr/> From the 1/4 sec. cor. of secs. 26 and 35, hereinbefore described.  S. 89°40' W., bet. secs. 26 and 35.  Over broken land, on ascent of E. slope of a plateau.
39.93	The cor. of secs. 26, 27, 34 and 35.



**Survey of a Portion of the Subdivisional Lines,  
T. 24 N., R. 30 E., Gila and Salt River Meridian, Arizona**

CHAINS	
	<p>Land, broken. Soil, rocky clay and sandstone outcrops. Timber, piñon and juniper; undergrowth, brush and native grasses.</p> <hr/> <p>N. 0°15' E., bet. secs. 26 and 27.</p> <p>Over broken land, on descent of N. slope of a plateau.</p>
40.53	<p>The 1/4 sec. cor. of secs. 26 and 27, hereinbefore described.</p> <p>Land, broken. Soil, rocky clay and sandstone outcrops. Timber, piñon and juniper; undergrowth, brush and native grasses.</p> <hr/> <p>From the cor. of secs. 10, 11, 14 and 15, hereinbefore described.</p> <p>N. 0°01' W., bet. secs. 10 and 11.</p> <p>Over rolling land, across a small valley.</p>
26.30	<p>Wash, 100 ft. wide, 8 ft. deep, drains S. 20° E.</p>
40.00	<p>Point for the 1/4 sec. cor. of secs. 10 and 11.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p align="center">T 24 N R 30 E 1/4 S 10   S 11  2001</p>
80.00	<p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p> <p>Point for the cor. of secs. 2, 3, 10 and 11.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p align="center">T 24 N R 30 E S 3   S 2 <hr/>S 10   S 11  2001</p>

**Survey of a Portion of the Subdivisional Lines,  
T. 24 N., R. 30 E., Gila and Salt River Meridian, Arizona**

CHAINS	
	<p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p>
	<p>Land, rolling. Soil, sandy and rocky clay. Timber, piñon and juniper; undergrowth, brush and native grasses.</p> <hr/>
	<p>From the cor. of secs. 1, 2, 11 and 12.</p>
	<p>S. 89°54' W., bet. secs. 2 and 11.</p>
	<p>Over rolling and broken land, across ridges.</p>
13.31	<p>Navajo Route 12, asphalt pavement, 40 ft. wide, bears N. 10° E. and S. 10° W.</p>
40.04	<p>Point for the 1/4 sec. cor. of secs. 2 and 11.</p>
	<p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p>
	<p align="center">T 24 N R 30 E S 2 1/4 ——— S 11</p>
	<p align="center">2001</p>
	<p>from which</p>
	<p align="center">The marks X B0, chiseled atop a sandstone boulder, 6 x 3 x 2 ft. high, bear S. 13 1/4° E., 21 lks. dist.</p>
	<p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p>
80.08	<p>The cor. of secs. 2, 3, 10 and 11.</p>
	<p>Land, rolling and broken. Soil, sandy and rocky clay with sandstone outcrops. Timber, piñon and juniper; undergrowth, brush and native grasses.</p> <hr/>
	<p>N. 0°01' W., bet. secs. 2 and 3.</p>
	<p>Over broken land, across E. slope of a plateau.</p>
40.00	<p>Point for the 1/4 sec. cor. of secs. 2 and 3.</p>

**Survey of a Portion of the Subdivisional Lines,  
T. 24 N., R. 30 E., Gila and Salt River Meridian, Arizona**

CHAINS	
	<p>Set a brass tablet, 3 1/4 ins. diam., 2 1/2 ins. stem, cemented in place, in a drill hole, in sandstone bedrock, with top mkd.</p> <p style="text-align: center;">T 24 N R 30 E 1/4 S 3   S 2</p> <p style="text-align: center;">2001</p> <p>Deposit a magnet in a white plastic case in the drill hole beneath the brass tablet.</p>
80.00	<p>Point for the 80 1/16 sec. cor. of secs. 2 and 3.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T 24 N R 30 E 80 1/16 S 3   S 2</p> <p style="text-align: center;">2001</p> <p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p>
89.86	<p>Point for the closing cor. of secs. 2 and 3, at intersection with the Sixth Standard Parallel North, on the N. bdy. of the Tp.</p> <p>Set a brass tablet, 3 1/4 ins. diam., 2 1/2 ins. stem, cemented in place, in a drill hole, in sandstone bedrock, with top mkd.</p> <p style="text-align: center;">T 25 N R 30 E S 33 ----- S 3   S 2 T 24 N R 30 E CC</p> <p style="text-align: center;">2001</p> <p>Deposit a magnet in a white plastic case in the drill hole beneath the brass tablet.</p> <p>From this cor. point, the stan. cor. of secs. 33 and 34, T. 25 N., R. 30 E., bears S. 89°58' E., 30.33 chs. dist., monumented with a brass tablet, 3 1/2 ins. diam., set, mkd. and witnessed as described in the field notes of the dependent resurvey of a portion of the Sixth Standard Parallel North, (south boundary), T. 25 N., R. 30 E., executed concurrently under this same group.</p>

**Survey of a Portion of the Subdivisional Lines,  
T. 24 N., R. 30 E., Gila and Salt River Meridian, Arizona**

CHAINS	
	<p>From this same cor. point, the stan. 1/4 sec. cor. of sec. 33, T. 25 N., R. 30 E., bears N. 89°58' W., 9.72 chs. dist., monumented with a stainless steel post, 2 1/2 ins. diam., with brass cap, set, mkd. and witnessed as described in the field notes of the dependent resurvey of a portion of the Sixth Standard Parallel North, (south boundary), T. 25 N., R. 30 E., executed concurrently under this same group.</p> <hr/> <p>Point for the 1/4 sec. cor. of sec. 2 only, T. 24 N., R. 30 E., at midpoint on the N. bdy. of sec. 2.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p align="center">T 25 N R 30 E ----- 1/4 S 2 T 24 N R 30 E</p> <p align="center">2001</p> <p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p> <p>From this cor. point, the stan. 1/4 sec. cor. of sec. 34, T. 25 N., R. 30 E., bears S. 89°55' E., 30.24 chs. dist.</p> <p>From this same cor. point, the stan. cor. of secs. 33 and 34, T. 25 N., R. 30 E., bears N. 89°55' W., 9.71 chs. dist.</p> <hr/> <p>From the cor. of secs. 3, 4, 33 and 34, on the S. bdy. of the Tp., hereinbefore described.</p> <p>N. 0°02' W., bet. secs. 33 and 34.</p> <p>Over rolling to rugged land, in canyon of Black Creek.</p>
32.40	N. rim of canyon of Black Creek, bears N. 50° E. and S. 50° W.; thence over rolling land, atop a plateau.
40.00	<p>Point for the 1/4 sec. cor. of secs. 33 and 34.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p align="center">T 24 N R 30 E 1/4 S 33   S 34</p> <p align="center">2001</p>

**Survey of a Portion of the Subdivisional Lines,  
T. 24 N., R. 30 E., Gila and Salt River Meridian, Arizona**

CHAINS									
	Deposit a magnet in a white plastic case at the base of the stainless steel post.								
80.00	Point for the cor. of secs. 27, 28, 33 and 34.								
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.								
	<table border="0" style="margin-left: auto; margin-right: auto;"> <tr> <td>T 24 N</td> <td>R 30 E</td> </tr> <tr> <td>S 28</td> <td>S 27</td> </tr> <tr> <td>S 33</td> <td>S 34</td> </tr> </table>	T 24 N	R 30 E	S 28	S 27	S 33	S 34		
T 24 N	R 30 E								
S 28	S 27								
S 33	S 34								
	2001								
	Deposit a magnet in a white plastic case at the base of the stainless steel post.								
	<p>Land, rugged and rolling. Soil, sandy and rocky clay and sandstone outcrops. Timber, ponderosa pine, piñon and juniper; undergrowth, brush and native grasses.</p>								
	From the cor. of secs. 26, 27, 34 and 35.								
	S. 89°58' W., bet. secs. 27 and 34.								
	Over broken land, on ascent of E. slope of a plateau.								
3.90	E. rim of a plateau, bears S. 30° E. and N. 30° W.; thence over rolling land, atop a plateau.								
40.01	Point for the 1/4 sec. cor. of secs. 27 and 34.								
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 21 ins. in the ground, to bedrock, in a mound of stone, 3 ft. base, to top, with brass cap mkd.								
	<table border="0" style="margin-left: auto; margin-right: auto;"> <tr> <td>T 24 N</td> <td>R 30 E</td> </tr> <tr> <td></td> <td>S 27</td> </tr> <tr> <td>1/4</td> <td>_____</td> </tr> <tr> <td></td> <td>S 34</td> </tr> </table>	T 24 N	R 30 E		S 27	1/4	_____		S 34
T 24 N	R 30 E								
	S 27								
1/4	_____								
	S 34								
	2001								
	Deposit a magnet in a white plastic case at the base of the stainless steel post.								
80.02	The cor. of secs. 27, 28, 33 and 34.								

**Survey of a Portion of the Subdivisional Lines,  
T. 24 N., R. 30 E., Gila and Salt River Meridian, Arizona**

CHAINS	
	<p>Land, broken to rolling. Soil, sandy and rocky clay and sandstone outcrops. Timber, ponderosa pine, piñon and juniper; undergrowth, brush and native grasses.</p> <hr/>
40.11	<p>N. 0°04' E., bet. secs. 27 and 28.</p> <p>Over rolling land, atop a plateau.</p> <p>Point for the 1/4 sec. cor. of secs. 27 and 28.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in sandstone bedrock, with brass cap mkd.</p> <p align="center">T 24 N R 30 E 1/4 S 28   S 27</p> <p align="center">2001</p>
80.22	<p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p> <p>The cor. of secs. 21, 22, 27 and 28, hereinbefore described.</p> <p>Land, rolling. Soil, sandy and rocky clay with sandstone outcrops. Timber, ponderosa pine, piñon and juniper; undergrowth, brush and native grasses.</p> <hr/>
40.00	<p>From the cor. of secs. 9, 10, 15 and 16, hereinbefore described.</p> <p>N. 0°02' W., bet. secs. 9 and 10.</p> <p>Over rolling and broken land, on ascent of S. slope of a spur ridge.</p> <p>Point for the 1/4 sec. cor. of secs. 9 and 10.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in sandstone bedrock, with brass cap mkd.</p> <p align="center">T 24 N R 30 E 1/4 S 9   S 10</p> <p align="center">2001</p> <p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p>

**Survey of a Portion of the Subdivisional Lines,  
T. 24 N., R. 30 E., Gila and Salt River Meridian, Arizona**

CHAINS									
51.50	Base of S. slope of a plateau, bears N. 70° E. and S. 70° W.; thence over broken land, on steep ascent.								
60.70	S. rim of same plateau, bears N. 40° E. and S. 40° W.; thence over rolling land, atop same plateau.								
80.00	Point for the cor. of secs. 3, 4, 9 and 10.  Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.  <div style="text-align: center;"> <table border="0"> <tr><td>T 24 N</td><td>R 30 E</td></tr> <tr><td>S 4</td><td>S 3</td></tr> <tr><td>S 9</td><td>S 10</td></tr> </table> <p>2001</p> </div> <p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p> <p>Land, rolling and broken. Soil, sandy and rocky clay and sandstone outcrops. Timber, ponderosa pine, piñon and juniper; undergrowth, brush and native grasses.</p> <hr/> <p>From the cor. of secs. 2, 3, 10 and 11. S. 89°34' W., bet. secs. 3 and 10. Over rolling and broken land, across spur ridges.</p>	T 24 N	R 30 E	S 4	S 3	S 9	S 10		
T 24 N	R 30 E								
S 4	S 3								
S 9	S 10								
39.56	Point for the 1/4 sec. cor. of secs. 3 and 10.  Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.  <div style="text-align: center;"> <table border="0"> <tr><td>T 24 N</td><td>R 30 E</td></tr> <tr><td>S 3</td><td></td></tr> <tr><td>1/4</td><td>—</td></tr> <tr><td>S 10</td><td></td></tr> </table> <p>2001</p> </div> <p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p>	T 24 N	R 30 E	S 3		1/4	—	S 10	
T 24 N	R 30 E								
S 3									
1/4	—								
S 10									
47.20	Base of E. slope of a plateau, bears N. 40° E. and S. 40° W.; thence over broken land, on steep ascent.								
67.40	E. rim of same plateau, bears N. and S.; thence over rolling land, atop same plateau.								

**Survey of a Portion of the Subdivisional Lines,  
T. 24 N., R. 30 E., Gila and Salt River Meridian, Arizona**

CHAINS	
79.12	<p>The cor. of secs. 3, 4, 9 and 10.</p> <p>Land, rolling and broken. Soil, sandy and rocky clay and sandstone outcrops. Timber, ponderosa pine, piñon and juniper; undergrowth, brush and native grasses.</p> <hr/> <p>N. 0°02' W., bet. secs. 3 and 4.</p> <p>Over gently rolling land, atop a plateau.</p>
40.00	<p>Point for the 1/4 sec. cor. of secs. 3 and 4.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T 24 N R 30 E 1/4 S 4   S 3  2001</p> <p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p>
80.00	<p>Point for the 80 1/16 sec. cor. of secs. 3 and 4.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T 24 N R 30 E 80 1/16 S 4   S 3  2001</p> <p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p>
90.52	<p>Point for the closing cor. of secs. 3 and 4 , at intersection with the Sixth Standard Parallel North, on the N. bdy. of the Tp.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p>



**Survey of a Portion of the Subdivisional Lines,  
T. 24 N., R. 30 E., Gila and Salt River Meridian, Arizona**

CHAINS

T 25 N R 30 E  
 S 32  
 S 4 | S 3  
 T 24 N R 30 E  
 CC

2001

Deposit a magnet in a white plastic case at the base of the stainless steel post.

From this cor. point, the stan. cor. of secs. 32 and 33, T. 25 N., R. 30 E., bears S. 89°52' E., 29.33 chs. dist., monumented with an iron post, 2 ins. diam., set and mkd. as described in the field notes of the dependent resurvey of a portion of the Sixth Standard Parallel North, (south boundary), T. 25 N., R. 30 E., executed concurrently under this same group.

From this same cor. point, the stan. 1/4 sec. cor. of sec. 32, T. 25 N., R. 30 E., bears N. 89°52' W., 10.67 chs. dist., monumented with an iron post, 1 in. diam., with brass cap, set and mkd. as described in the field notes of the dependent resurvey of a portion of the Sixth Standard Parallel North, (south boundary), T. 25 N., R. 30 E., executed concurrently under this same group.

Land, gently rolling.

Soil, sandy and rocky clay.

Timber, piñon and juniper; undergrowth, brush and native grasses.

---

Point for the 1/4 sec. cor. of sec. 3 only, T. 24 N., R. 30 E., at midpoint on the N. bdy. of sec. 3.

Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.

T 25 N R 30 E  
 1/4 S 3  
 T 24 N R 30 E

2001

Deposit a magnet in a white plastic case at the base of the stainless steel post.

From this cor. point, the stan. 1/4 sec. cor. of sec. 33, bears East, 29.83 chs. dist.

**Survey of a Portion of the Subdivisional Lines,  
T. 24 N., R. 30 E., Gila and Salt River Meridian, Arizona**

CHAINS	
	<p>From this same cor. point, the stan cor. of secs. 32 and 33, bears West, 10.22 chs. dist.</p> <hr/> <p>From the cor. of secs. 4, 5, 32 and 33, on the S. bdy. of the Tp., hereinbefore described.</p> <p>N. 0°03' W., bet. secs. 32 and 33.</p> <p>Over gently rolling land, atop a plateau.</p>
40.00	<p>Point for the 1/4 sec. cor. of secs. 32 and 33.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in sandstone bedrock, with brass cap mkd.</p> <div style="text-align: center;"> <p>T 24 N R 30 E 1/4 S 32   S 33</p> <p>2001</p> </div> <p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p> <p>Cor. is located 1.75 chs. S. of a trail road, bears N. 60° E. and S. 60° W.</p>
80.00	<p>Point for the cor. of secs. 28, 29, 32 and 33.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center;"> <p>T 24 N R 30 E S 29   S 28 S 32   S 33</p> <p>2001</p> </div> <p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p> <p>Cor. is located 2.75 chs. W. of a trail road, bears N. 10° E. and S. 10° W.</p> <p>Land, gently rolling. Soil, sandy and rocky clay. Timber, piñon and juniper; undergrowth, brush and native grasses.</p> <hr/> <p>From the cor. of secs. 27, 28, 33 and 34.</p>

**Survey of a Portion of the Subdivisional Lines,  
T. 24 N., R. 30 E., Gila and Salt River Meridian, Arizona**

CHAINS	
	West, bet. secs. 28 and 33.  Over gently rolling land, atop a plateau.
40.01	Point for the 1/4 sec. cor. of secs. 28 and 33.  Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.  <div style="text-align: center;">           T 24 N R 30 E                      S 28                  1/4 ———                      S 33             2001         </div>
80.02	Deposit a magnet in a white plastic case at the base of the stainless steel post.  The cor. of secs. 28, 29, 32 and 33.  Land, gently rolling. Soil, sandy and rocky clay. Timber, ponderosa pine, piñon and juniper; undergrowth, brush and native grasses.
40.00	<hr/> N. 0°03' W., bet. secs. 28 and 29.  Over gently rolling land, atop a plateau.  Point for the 1/4 sec. cor. of secs. 28 and 29.  Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 22 ins. in the ground, with brass cap mkd.  <div style="text-align: center;">           T 24 N R 30 E                      1/4                  S 29   S 28             2001         </div>
79.00	Deposit a magnet in a white plastic case at the base of the stainless steel post.  Cor. is located 2.50 chs. W. of a trail road, bears N. 20° E. and S. 20° W.
80.00	Trail road, bears N. 60° E. and S. 60° W.  Point for the cor. of secs. 20, 21, 28 and 29.

**Survey of a Portion of the Subdivisional Lines,  
T. 24 N., R. 30 E., Gila and Salt River Meridian, Arizona**

CHAINS									
	<p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p align="center"> <table border="0"> <tr> <td>T 24 N</td> <td>R 30 E</td> </tr> <tr> <td>S 20</td> <td>S 21</td> </tr> <tr> <td>S 29</td> <td>S 28</td> </tr> </table> </p> <p align="center">2001</p> <p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p> <p>Cor. is located 1.65 chs. W. of a trail road, bears N. 60° E. and S. 60° W.</p> <p>Land, gently rolling. Soil, sandy and rocky clay. Timber, ponderosa pine, piñon and juniper; undergrowth, brush and native grasses.</p> <hr/> <p>From the cor. of secs. 21, 22, 27 and 28, hereinbefore described.</p> <p>S. 89°50' W., bet. secs. 21 and 28.</p> <p>Over gently rolling land, atop a plateau.</p>	T 24 N	R 30 E	S 20	S 21	S 29	S 28		
T 24 N	R 30 E								
S 20	S 21								
S 29	S 28								
40.08	<p>Point for the 1/4 sec. cor. of secs. 21 and 28.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p align="center"> <table border="0"> <tr> <td>T 24 N</td> <td>R 30 E</td> </tr> <tr> <td></td> <td>S 21</td> </tr> <tr> <td>1/4</td> <td>—</td> </tr> <tr> <td></td> <td>S 28</td> </tr> </table> </p> <p align="center">2001</p> <p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p>	T 24 N	R 30 E		S 21	1/4	—		S 28
T 24 N	R 30 E								
	S 21								
1/4	—								
	S 28								
80.16	<p>The cor. of secs. 20, 21, 28 and 29.</p> <p>Land, gently rolling. Soil, sandy and rocky clay. Timber, ponderosa pine, piñon and juniper; undergrowth, brush and native grasses.</p> <hr/> <p>N. 0°03' W., bet. secs. 20 and 21.</p>								

**Survey of a Portion of the Subdivisional Lines,  
T. 24 N., R. 30 E., Gila and Salt River Meridian, Arizona**

CHAINS	
	Over rolling land, atop a plateau.
40.00	Point for the 1/4 sec. cor. of secs. 20 and 21.  Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.  <div style="text-align: center;">                     T 24 N R 30 E                          1/4                      S 20   S 21                       2001                 </div>
	Deposit a magnet in a white plastic case at the base of the stainless steel post.
61.00	Apache County Road C404, a graded road, 20 ft. wide, bears S. 60° E. and N. 60° W.
80.00	Point for the cor. of secs. 16, 17, 20 and 21.  Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.  <div style="text-align: center;">                     T 24 N R 30 E                      S 17   S 16  <hr style="width: 50%; margin: 0 auto;"/>                     S 20   S 21                       2001                 </div>
	Deposit a magnet in a white plastic case at the base of the stainless steel post.
	Land, rolling. Soil, sandy and rocky clay. Timber, ponderosa pine, piñon and juniper; undergrowth, brush and native grasses.
	From the cor. of secs. 15, 16, 21 and 22, hereinbefore described.  S. 89°42' W., bet. secs. 16 and 21.
	Over rolling and broken land, atop a plateau.
40.10	Point for the 1/4 sec. cor. of secs. 16 and 21.  Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.

**Survey of a Portion of the Subdivisional Lines,  
T. 24 N., R. 30 E., Gila and Salt River Meridian, Arizona**

CHAINS	
	T 24 N R 30 E S 16 1/4 ——— S 21  2001  Deposit a magnet in a white plastic case at the base of the stainless steel post.
80.20	The cor. of secs. 16, 17, 20 and 21.  Land, rolling and broken. Soil, sandy and rocky clay. Timber, ponderosa pine, piñon and juniper; undergrowth, brush and native grasses.
	N. 0°03' W., bet. secs. 16 and 17.  Over rolling land, on descent.
40.00	Point for the 1/4 sec. cor. of secs. 16 and 17.  Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.
	T 24 N R 30 E 1/4 S 17   S 16  2001  Deposit a magnet in a white plastic case at the base of the stainless steel post.
	Thence over rolling and broken land, across a drainage and a spur ridge.
80.00	Point for the cor. of secs. 8, 9, 16 and 17.  Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.
	T 24 N R 30 E S 8   S 9 S 17   S 16  2001  Deposit a magnet in a white plastic case at the base of the stainless steel post.

**Survey of a Portion of the Subdivisional Lines,  
T. 24 N., R. 30 E., Gila and Salt River Meridian, Arizona**

CHAINS	
	<p>Land, rolling and broken. Soil, sandy and rocky clay and sandstone outcrops. Timber, ponderosa pine, piñon and juniper; undergrowth, brush and native grasses.</p> <hr/>
	<p>From the cor. of secs. 9, 10, 15 and 16, hereinbefore described. S. 89°44' W., bet. secs. 9 and 16. Over rolling and broken land, on ascent of E. slope of a spur ridge.</p>
40.11	<p>Point for the 1/4 sec. cor. of secs. 9 and 16. Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 22 ins. in the ground, in a collar of stone, with brass cap mkd.</p> <p align="center">T 24 N R 30 E S 9 1/4 ——— S 16</p> <p align="center">2001</p> <p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p> <p>Thence over rolling and broken land, across a drainage and onto another spur ridge.</p>
80.22	<p>The cor. of secs. 8, 9, 16 and 17. Land, rolling and broken. Soil, sandy and rocky clay. Timber, ponderosa pine, piñon and juniper; undergrowth, brush and native grasses.</p> <hr/>
	<p>N. 0°03' W., bet. secs. 8 and 9. Over broken land, on steep ascent onto a plateau.</p>
40.00	<p>Point for the 1/4 sec. cor. of secs. 8 and 9. Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p align="center">T 24 N R 30 E 1/4 S 8   S 9</p> <p align="center">2001</p>

**Survey of a Portion of the Subdivisional Lines,  
T. 24 N., R. 30 E., Gila and Salt River Meridian, Arizona**

CHAINS									
	<p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p> <p>Thence over rolling land, atop a plateau.</p>								
80.00	<p>Point for the cor. of secs. 4, 5, 8 and 9.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center;"> <table border="1"> <tr><td>T 24 N</td><td>R 30 E</td></tr> <tr><td>S 5</td><td>S 4</td></tr> <tr><td>S 8</td><td>S 9</td></tr> </table> <p>2001</p> </div>	T 24 N	R 30 E	S 5	S 4	S 8	S 9		
T 24 N	R 30 E								
S 5	S 4								
S 8	S 9								
	<p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p> <p>Land, broken to rolling. Soil, sandy and rocky clay and sandstone outcrops. Timber, ponderosa pine, piñon and juniper; undergrowth, brush and native grasses.</p>								
	<p>From the cor. of secs. 3, 4, 9 and 10.</p> <p>S. 89°44' W., bet. secs. 4 and 9.</p> <p>Over rolling land, atop a plateau.</p>								
40.11	<p>Point for the 1/4 sec. cor. of secs. 4 and 9.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center;"> <table border="1"> <tr><td>T 24 N</td><td>R 30 E</td></tr> <tr><td>S 4</td><td></td></tr> <tr><td>1/4</td><td>—</td></tr> <tr><td>S 9</td><td></td></tr> </table> <p>2001</p> </div>	T 24 N	R 30 E	S 4		1/4	—	S 9	
T 24 N	R 30 E								
S 4									
1/4	—								
S 9									
80.22	<p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p> <p>The cor. of secs. 4, 5, 8 and 9.</p>								



**Survey of a Portion of the Subdivisional Lines,  
T. 24 N., R. 30 E., Gila and Salt River Meridian, Arizona**

CHAINS	
	<p>Land, rolling. Soil, sandy and rocky clay. Timber, ponderosa pine, piñon and juniper; undergrowth, brush and native grasses.</p> <hr/> <p>N. 0°03' W., bet. secs. 4 and 5.</p> <p>Over rolling land, atop a plateau.</p>
40.00	<p>Point for the 1/4 sec. cor. of secs. 4 and 5.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T 24 N R 30 E 1/4 S 5   S 4  2001</p> <p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p>
80.00	<p>Point for the 80 1/16 sec. cor. of secs. 4 and 5.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T 24 N R 30 E 80 1/16 S 5   S 4  2001</p> <p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p>
90.92	<p>Point for the closing cor. of secs. 4 and 5, at intersection with the Sixth Standard Parallel North, on the N. bdy. of the Tp.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p>

**Survey of a Portion of the Subdivisional Lines,  
T. 24 N., R. 30 E., Gila and Salt River Meridian, Arizona**

CHAINS

T 25 N R 30 E  
           S 31  


---

 S 5 | S 4  
 T 24 N R 30 E  
           CC

2001

Deposit a magnet in a white plastic case at the base of the stainless steel post.

From this cor. point, the stan. cor. of secs. 31 and 32, T. 25 N., R. 30 E., bears N. 89°48' E., 29.55 chs. dist., monumented with an iron post, 2 ins. diam., set, mkd. and witnessed as described in the field notes of the dependent resurvey of a portion of the Sixth Standard Parallel North, (south boundary), T. 25 N., R. 30 E., executed concurrently under this same group.

From this same cor. point, the stan. 1/4 sec. cor. of sec. 31, T. 25 N., R. 30 E., bears S. 89°48' W., 10.45 chs. dist., monumented with a stainless steel post, 2 1/2 ins. diam., with brass cap, set, mkd. and witnessed as described in the field notes of the dependent resurvey of a portion of the Sixth Standard Parallel North, (south boundary), T. 25 N., R. 30 E., executed concurrently under this same group.

Land, rolling.

Soil, sandy and rocky clay.

Timber, ponderosa pine, piñon and juniper; undergrowth, brush and native grasses.

---

Point for the 1/4 sec. cor. of sec. 4 only, T. 24 N., R. 30 E., at midpoint on the N. bdy. of sec. 4.

Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.

T 25 N R 30 E  


---

 1/4 S 4  
 T 24 N R 30 E

2001

Deposit a magnet in a white plastic case at the base of the stainless steel post.

From this cor. point, the stan. 1/4 sec. cor. of sec. 32, bears S. 89°52' E., 29.44 chs. dist.

**Survey of a Portion of the Subdivisional Lines,  
T. 24 N., R. 30 E., Gila and Salt River Meridian, Arizona**

CHAINS	
	<p>From this same cor. point, the stan cor. of secs. 31 and 32, bears N. 89°52' W., 10.56 chs. dist.</p> <hr/> <p>From the cor. of secs. 5, 6, 31 and 32, on the S. bdy. of the Tp., hereinbefore described.</p> <p>N. 0°03' W., bet. secs. 31 and 32.</p> <p>Over gently rolling land, atop a plateau.</p>
40.00	<p>Point for the 1/4 sec. cor. of secs. 31 and 32.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p align="center">T 24 N R 30 E 1/4 S 31   S 32</p> <p align="center">2001</p> <p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p>
80.00	<p>Point for the cor. of secs. 29, 30, 31 and 32.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p align="center">T 24 N R 30 E S 30   S 29 S 31   S 32</p> <p align="center">2001</p> <p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p> <p>Land, gently rolling. Soil, sandy and rocky clay. Timber, piñon and juniper; undergrowth, brush and native grasses.</p> <hr/> <p>From the cor. of secs. 28, 29, 32 and 33.</p> <p>West, bet. secs. 29 and 32.</p> <p>Over gently rolling land, atop a plateau.</p>
40.03	<p>Point for the 1/4 sec. cor. of secs. 29 and 32.</p>

**Survey of a Portion of the Subdivisional Lines,  
T. 24 N., R. 30 E., Gila and Salt River Meridian, Arizona**

CHAINS	
	<p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 14 ins. in the ground, to bedrock, in a supporting mound of stone, 3 ft. base, to top, with brass cap mkd.</p> <p align="center">T 24 N R 30 E S 29 1/4 ——— S 32</p> <p align="center">2001</p> <p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p>
80.06	<p>The cor. of secs. 29, 30, 31 and 32.</p> <p>Land, gently rolling. Soil, sandy and rocky clay. Timber, piñon and juniper; undergrowth, brush and native grasses.</p> <hr/>
	<p>S. 89°59' W., bet. secs. 30 and 31.</p> <p>Over gently rolling land, atop a plateau.</p>
40.00	<p>Point for the 1/4 sec. cor. of secs. 30 and 31.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p align="center">T 24 N R 30 E S 30 1/4 ——— S 31</p> <p align="center">2001</p> <p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p>
68.71	<p>The cor. of secs. 30 and 31 only, T. 24 N., R. 30 E., on the W. bdy. of the Tp., hereinbefore described.</p> <p>Land, gently rolling. Soil, sandy and rocky clay. Timber, piñon and juniper; undergrowth, brush and native grasses.</p> <hr/>
	<p>From the cor. of secs. 29, 30, 31 and 32.</p> <p>N. 0°03' W., bet. secs. 29 and 30.</p>

**Survey of a Portion of the Subdivisional Lines,  
T. 24 N., R. 30 E., Gila and Salt River Meridian, Arizona**

CHAINS	
40.00	<p>Over gently rolling land, atop a plateau.</p> <p>Point for the 1/4 sec. cor. of secs. 29 and 30.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p align="center">T 24 N R 30 E 1/4 S 30   S 29</p> <p align="center">2001</p> <p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p>
80.00	<p>Point for the cor. of secs. 19, 20, 29 and 30.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p align="center">T 24 N R 30 E S 19   S 20 S 30   S 29</p> <p align="center">2001</p> <p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p> <p>Land, gently rolling. Soil, sandy and rocky clay. Timber, piñon and juniper; undergrowth, brush and native grasses.</p> <hr/> <p>From the cor. of secs. 20, 21, 28 and 29.</p> <p>West, bet. secs. 20 and 29.</p> <p>Over gently rolling land, atop a plateau.</p>
40.03	<p>Point for the 1/4 sec. cor. of secs. 20 and 29.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., flush with the surface of the ground, with brass cap mkd.</p>

**Survey of a Portion of the Subdivisional Lines,  
T. 24 N., R. 30 E., Gila and Salt River Meridian, Arizona**

CHAINS	
	<p align="center">T 24 N R 30 E S 20 1/4 ——— S 29</p> <p align="center">2001</p> <p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p> <p>Set a steel fence post nearby.</p> <p>Cor. is located on W. edge of a trail road, bears N. and S.; and 45 lks. E. of another trail road, bears N. 40° E. and S. 40° W.</p>
80.06	<p>The cor. of secs. 19, 20, 29 and 30.</p> <p>Land, gently rolling. Soil, sandy and rocky clay. Timber, ponderosa pine, piñon and juniper; undergrowth, brush and native grasses.</p>
40.00	<hr/> <p>S. 89°59' W., bet. secs. 19 and 30.</p> <p>Over gently rolling land, atop a plateau.</p> <p>Point for the 1/4 sec. cor. of secs. 19 and 30.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p>
55.70	<p align="center">T 24 N R 30 E S 19 1/4 ——— S 30</p> <p align="center">2001</p> <p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p>
68.62	<p>E. rim of canyon of West Fork Black Creek, bears N. 40° E. and S. 40° W.; thence across canyon, and then gently rolling land.</p>
	<p>The cor. of secs. 19 and 30 only, T. 24 N., R. 30 E., on the W. bdy. of the Tp., hereinbefore described.</p>

**Survey of a Portion of the Subdivisional Lines,  
T. 24 N., R. 30 E., Gila and Salt River Meridian, Arizona**

CHAINS	
	<p>Land, gently rolling and broken. Soil, sandy and rocky clay and sandstone outcrops. Timber, piñon, juniper and ponderosa pine; undergrowth, brush and native grasses.</p> <hr/>
40.00	<p>From the cor. of secs. 19, 20, 29 and 30. N. 0°03' W., bet. secs. 19 and 20. Over rolling land, atop a plateau.</p>
	<p>Point for the 1/4 sec. cor. of secs. 19 and 20.</p>
	<p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p>
	<p align="center">T 24 N R 30 E 1/4 S 19   S 20  2001</p>
	<p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p>
80.00	<p>Point for the cor. of secs. 17, 18, 19 and 20.</p>
	<p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p>
	<p align="center">T 24 N R 30 E S 18   S 17 S 19   S 20  2001</p>
	<p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p>
	<p>Land, rolling. Soil, sandy and rocky clay. Timber, piñon and juniper; undergrowth, brush and native grasses.</p> <hr/>
	<p>From the cor. of secs. 16, 17, 20 and 21.</p>
	<p>West, bet. secs. 17 and 20.</p>
	<p>Over gently rolling land, atop a plateau.</p>

**Survey of a Portion of the Subdivisional Lines,  
T. 24 N., R. 30 E., Gila and Salt River Meridian, Arizona**

CHAINS	
40.03	<p>Point for the 1/4 sec. cor. of secs. 17 and 20.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T 24 N R 30 E S 17 1/4 ——— S 20</p> <p style="text-align: center;">2001</p> <p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p> <p>Cor. is located 60 lks. N. and 1.50 chs. E. of Apache County Road C404, a graded road, 26 ft. wide, bears S. 70° E. and N. 70° W.</p>
80.06	<p>The cor. of secs. 17, 18, 19 and 20.</p> <p>Land, gently rolling. Soil, sandy and rocky clay. Timber, piñon and juniper; undergrowth, brush and native grasses.</p> <hr/> <p>S. 89°59' W., bet. secs. 18 and 19.</p> <p>Over rolling and broken land, atop a plateau.</p>
40.00	<p>Point for the 1/4 sec. cor. of secs. 18 and 19.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T 24 N R 30 E S 18 1/4 ——— S 19</p> <p style="text-align: center;">2001</p> <p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p>
68.53	<p>The cor. of secs. 18 and 19 only, T. 24 N., R. 30 E., on the W. bdy. of the Tp., hereinbefore described.</p>



**Survey of a Portion of the Subdivisional Lines,  
T. 24 N., R. 30 E., Gila and Salt River Meridian, Arizona**

CHAINS	
	<p>Land, rolling and broken. Soil, sandy and rocky clay. Timber, piñon and juniper; undergrowth, brush and native grasses.</p> <hr/>
	<p>From the cor. of secs. 17, 18, 19 and 20.</p>
	<p>N. 0°03' W., bet. secs. 17 and 18.</p>
	<p>Over rolling land, atop a plateau.</p>
15.00	<p>Apache County Road C404, a graded road, 26 ft. wide, bears S. 70° E. and N. 70° W.</p>
40.00	<p>Point for the 1/4 sec. cor. of secs. 17 and 18.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p>
	<p align="center">T 24 N R 30 E 1/4 S 18   S 17  2001</p>
	<p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p>
80.00	<p>Point for the cor. of secs. 7, 8, 17 and 18.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p>
	<p align="center">T 24 N R 30 E S 7   S 8 S 18   S 17  2001</p>
	<p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p>
	<p>Land, rolling. Soil, sandy and rocky clay. Timber, piñon and juniper; undergrowth, brush and native grasses.</p> <hr/>
	<p>From the cor. of secs. 8, 9, 16 and 17.</p>
	<p>West, bet. secs. 8 and 17.</p>

**Survey of a Portion of the Subdivisional Lines,  
T. 24 N., R. 30 E., Gila and Salt River Meridian, Arizona**

CHAINS	
	Over broken to rolling land, atop a plateau.
40.03	Point for the 1/4 sec. cor. of secs. 8 and 17.
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.
	<p align="center">T 24 N R 30 E S 8 1/4 ——— S 17</p>
	2001
	Deposit a magnet in a white plastic case at the base of the stainless steel post.
80.06	The cor. of secs. 7, 8, 17 and 18.
	Land, broken to rolling.
	Soil, sandy and rocky clay and sandstone outcrops.
	Timber, ponderosa pine, piñon and juniper; undergrowth, brush and native grasses.
	S. 89°59' W., bet. secs. 7 and 18.
	Over gently rolling land, atop a plateau.
40.00	Point for the 1/4 sec. cor. of secs. 7 and 18.
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.
	<p align="center">T 24 N R 30 E S 7 1/4 ——— S 18</p>
	2001
	Deposit a magnet in a white plastic case at the base of the stainless steel post.
68.45	The cor. of secs. 7 and 18 only, T. 24 N., R. 30 E., on the W. bdy. of the Tp.

**Survey of a Portion of the Subdivisional Lines,  
T. 24 N., R. 30 E., Gila and Salt River Meridian, Arizona**

CHAINS	
	<p>Land, gently rolling. Soil, sandy and rocky clay. Timber, piñon and juniper; undergrowth, brush and native grasses.</p> <hr/> <p>From the cor. of secs. 7, 8, 17 and 18.</p> <p>N. 0°03' W., bet. secs. 7 and 8.</p> <p>Over gently rolling land, atop a plateau.</p>
40.00	<p>Point for the 1/4 sec. cor. of secs. 7 and 8.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T 24 N R 30 E 1/4 S 7   S 8</p> <p style="text-align: center;">2001</p> <p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p>
80.00	<p>Point for the cor. of secs. 5, 6, 7 and 8.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T 24 N R 30 E S 6   S 5 S 7   S 8</p> <p style="text-align: center;">2001</p> <p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p> <p>Land, gently rolling. Soil, sandy and rocky clay. Timber, piñon and juniper; undergrowth, brush and native grasses.</p> <hr/> <p>From the cor. of secs. 4, 5, 8 and 9.</p> <p>West, bet. secs. 5 and 8.</p> <p>Over rolling land, atop a plateau.</p>

**Survey of a Portion of the Subdivisional Lines,  
T. 24 N., R. 30 E., Gila and Salt River Meridian, Arizona**

CHAINS	
40.03	<p>Point for the 1/4 sec. cor. of secs. 5 and 8.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center;"> <p>T 24 N R 30 E</p> <p>S 5</p> <p>1/4 ———</p> <p>S 8</p> <p>2001</p> </div> <p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p>
80.06	<p>The cor. of secs. 5, 6, 7 and 8.</p> <p>Land, rolling. Soil, sandy and rocky clay. Timber, ponderosa pine, piñon and juniper; undergrowth, brush and native grasses.</p> <hr/> <p>S. 89°59' W., bet. secs. 6 and 7.</p> <p>Over broken and rolling land, atop a plateau.</p>
40.00	<p>Point for the 1/4 sec. cor. of secs. 6 and 7.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center;"> <p>T 24 N R 30 E</p> <p>S 6</p> <p>1/4 ———</p> <p>S 7</p> <p>2001</p> </div> <p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p>
68.36	<p>The cor. of secs. 6 and 7 only, T. 24 N., R. 30 E., on the W. bdy. of the Tp., hereinbefore described.</p> <p>Land, broken and rolling. Soil, sandy and rocky clay and sandstone outcrops. Timber, piñon, juniper and ponderosa pine; undergrowth, brush and native grasses.</p> <hr/> <p>From the cor. of secs. 5, 6, 7 and 8.</p>

**Survey of a Portion of the Subdivisional Lines,  
T. 24 N., R. 30 E., Gila and Salt River Meridian, Arizona**

CHAINS	
	<p>N. 0°03' W., bet. secs. 5 and 6.</p> <p>Over rolling and broken land, atop a plateau, on gradual ascent along or near a drainage.</p>
40.00	<p>Point for the 1/4 sec. cor. of secs. 5 and 6.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p align="center">T 24 N R 30 E 1/4 S 6   S 5  2001</p>
80.00	<p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p> <p>Point for the 80 1/16 sec. cor. of secs. 5 and 6.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p align="center">T 24 N R 30 E 80 1/16 S 6   S 5  2001</p>
90.83	<p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p> <p>Point for the closing cor. of secs. 5 and 6, at intersection with the Sixth Standard Parallel North, on the N. bdy. of the Tp.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, in a collar of stone, with brass cap mkd.</p> <p align="center">T 25 N R 29 E S 36 ----- S 6   S 5 T 24 N R 30 E CC  2001</p> <p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p>

**Survey of a Portion of the Subdivisional Lines,  
T. 24 N., R. 30 E., Gila and Salt River Meridian, Arizona**

<p>CHAINS</p>	<p>From this cor. point, the stan. cor. of Tps. 25 N., Rs. 29 and 30 E., bears S. 89°59' E., 29.63 chs. dist., monumented with an iron post, 3 ins. diam., with brass cap, set, mkd. and witnessed as described in the field notes of the dependent resurvey of a portion of the Sixth Standard Parallel North, (south boundary), T. 25 N., R. 29 E., executed concurrently under this same group.</p> <p>From this same cor. point, the stan. 1/4 sec. cor. of sec. 36, T. 25 N., R. 29 E., bears N. 89°59' W., 10.34 chs. dist., monumented with an iron post, 1 in. diam., with brass cap, set, mkd. and witnessed as described in the field notes of the dependent resurvey of a portion of the Sixth Standard Parallel North, (south boundary), T. 25 N., R. 29 E., executed concurrently under this same group.</p> <p>Land, rolling and broken. Soil, sandy and rocky clay and sandstone outcrops. Timber, ponderosa pine, piñon and juniper; undergrowth, brush and native grasses.</p> <hr/> <p>Point for the 1/4 sec. cor. of sec. 5 only, T. 24 N., R. 30 E., at midpoint on the N. bdy. of sec. 5.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T 25 N R 30 E ----- 1/4 S 5 T 24 N R 30 E</p> <p style="text-align: center;">2001</p> <p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p> <p>From this cor. point, the stan. 1/4 sec. cor. of sec. 31, T. 25 N., R. 30 E., bears N. 89°54' E., 29.58 chs. dist.</p> <p>From this same cor. point, the stan. cor. of Tps. 25 N., Rs. 29 and 30 E., bears S. 89°54' W., 10.40 chs. dist.</p> <hr/> <p>Point for the 1/4 sec. cor. of sec. 6 only, T. 24 N., R. 30 E., at 40.00 chs. westing from the closing cor. of secs. 5 and 6, on the N. bdy. of sec. 6.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p>
---------------	--

Survey of a Portion of the Subdivisional Lines,  
T. 24 N., R. 30 E., Gila and Salt River Meridian, Arizona

CHAINS

T 25 N R 29 E

---

1/4 S 6

T 24 N R 30 E

2001

Deposit a magnet in a white plastic case at the base of the stainless steel post.

From this cor. point, the stan. 1/4 sec. cor. of sec. 36, T. 25 N., R. 29 E., bears N. 89°55' E., 29.66 chs. dist.

From this same cor. point, the stan. cor. of secs. 35 and 36, T. 25 N., R. 29 E., bears S. 89°55' W., 10.32 chs. dist., hereinbefore described.

---

**T. 24 N., R. 30 E., Gila and Salt River Meridian, Arizona**

CHAINS

## GENERAL DESCRIPTION

---

The area surveyed is within the Navajo Indian Reservation, and contains the community of Oak Springs. The terrain is gently rolling in Oak Spring Valley and atop the large plateau, and broken and rugged in the canyon of Black Creek and on the slopes of the plateau. Drainage is southerly. Black Creek, a wash, is the principal drainage, which enters the township in section 13 and exits in section 33.

The elevation varies from 6400 to 7360 feet above sea level. The soil is mostly sandy and rocky clay, with some sandstone outcrops. The timber is generally healthy stands of ponderosa pine, piñon and juniper. Undergrowth is brush and native grasses.

Principal access to the township is provided by Navajo Route 12, a paved road, which enters the township in section 36 and exits in section 1. There are graded roads and trail roads on the plateau and in the valleys. Much of the area is used for grazing livestock. There are numerous residences in the valleys, and a few on the plateau. There is no mining activity in the township.

The mean magnetic declination of  $11\ 1/2^\circ$  E. was derived from the computer program GEOMAGIX, utilizing the World Magnetic Model for Epoch 2000 for the dates of survey.

---



**UNITED STATES  
DEPARTMENT OF THE INTERIOR  
BUREAU OF LAND MANAGEMENT**

**FIELD ASSISTANTS**

NAMES	CAPACITY
Daniel L. Maxey	Cadastral Surveyor
William F. Olver	Cadastral Surveyor
James L. Werdel	Cadastral Surveyor
Daniel Bryan	Engineering Technician
Wilfred Chee	Engineering Technician
Edward Clarke	Engineering Technician
Reuben Mason	Engineering Technician
Barney Woodie	Engineering Technician

CERTIFICATE OF SURVEY

We, Jones Curtiss and Leonard R. Sandoval, Cadastral Surveyors, HEREBY CERTIFY upon honor, that in pursuance of special instructions bearing date of the 22nd day of January, 2001, and supplemental special instructions bearing date of the 2nd day of October, 2001, we have dependently resurveyed the south boundary and a portion of the subdivisional lines, and surveyed the east and west boundaries and a portion of the subdivisional lines, T. 24 N., R. 30 E., of the Gila and Salt River Meridian, in the State of Arizona, which are represented in the foregoing field notes as having been executed by us and under our direction. Said surveys have been made in strict conformity with said special instructions, supplemental special instructions, the Manual of Instructions for the Survey of the Public Lands of the United States, 1973, and in specific manner described in the foregoing field notes.

4-27-04  
(Date)

Jones Curtiss  
(Cadastral Surveyor)

4-27-04  
(Date)

Leonard R. Sandoval  
(Cadastral Surveyor)

CERTIFICATE OF APPROVAL

BUREAU OF LAND MANAGEMENT  
Phoenix, Arizona

The foregoing field notes of the dependent resurvey of the south boundary and a portion of the subdivisional lines, and the survey of the east and west boundaries and a portion of the subdivisional lines, T. 24 N., R. 30 E., Gila and Salt River Meridian, in the State of Arizona, executed by Jones Curtiss and Leonard R. Sandoval, Cadastral Surveyors, having been critically examined and found correct, are hereby approved.

May 18, 2004  
(Date)

Kenny D. Ravnikar  
(Chief Cadastral Surveyor of Arizona)

~~CERTIFICATE OF TRANSCRIPT~~

~~I CERTIFY That the foregoing transcript of the field notes of the above described surveys in T. 24 N., R. 30 E., Gila and Salt River Meridian, Arizona, is a true copy of the original field notes.~~

~~\_\_\_\_\_  
(Date)~~

~~\_\_\_\_\_  
(Chief Cadastral Surveyor of Arizona)~~