

ORIGINAL

**UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT**

FIELD NOTES

OF THE

DEPENDENT RESURVEY

**OF A PORTION OF THE SUBDIVISIONAL LINES
AND THE SUBDIVISION OF SECTIONS 9, 10 AND 14,
TOWNSHIP 18 SOUTH, RANGE 29 EAST,
OF THE GILA AND SALT RIVER MERIDIAN,
IN THE STATE OF ARIZONA**

EXECUTED BY

Adrien J. Rodriguez, Cadastral Surveyor

Under Special Instructions dated April 4, 2002, approved April 4, 2002,
which provided for the surveys included under Group No. 884, and
assignment instructions dated April 4, 2002.

Survey commenced April 23, 2002

Survey completed January 16, 2003

INDEX DIAGRAM

TOWNSHIP 18 SOUTH RANGE 29 EAST

6	5	4	3	2	1
7	8	16 16 9	14 12 10	11 11	12
18	17	15 15 16	12 15	10 8 14	5 13
19	20	21	22	6 23	5 4 24
30	29	28	27	26	25
31	32	33	34	35	36

Subdivision of Section 9 Pages 19-21
 Subdivision of Section 10 Pages 22-24
 Subdivision of Section 14 Pages 25-32

T. 18 S., R. 29 E., Gila and Salt River Meridian, Arizona

CHAINS

The following field notes describe the dependent resurvey of a portion of the subdivisional lines and the subdivision of sections 9, 10 and 14, Township 18 South, Range 29 East, Gila and Salt River Meridian, Arizona.

The history of surveys pertaining to this resurvey is as follows:

Theodore F. White surveyed the west boundary, a portion of the south and north boundaries and a portion of the subdivisional lines in 1882. Jno. P. Walker resurveyed portions of the south and west boundaries and a portion of the subdivisional lines and surveyed section 15 in the course of surveying the Chiricahua Forest Reserve Boundary in 1905. John F. Hesse and Alfred N. Oliver surveyed the east boundary, a portion of the south and north boundaries and a portion of the subdivisional lines in 1911. Wallace R. Ott remonumented certain corners in 1964.

In connection with the 1905 resurvey, some Forest Reserve Boundary monuments were established as witness corners a few links from the true monumented corner positions. These witness monuments were iron posts, 4 ft. long, 4 ins. diam., with brass caps. As these posts are sometimes locally accepted as the true corner position, the monuments encountered in the course of this survey were removed and destroyed.

The survey was executed in accordance with the specifications as set forth in the Manual of Instructions for the Survey of the Public Lands of the United States, 1973, and the Special Instructions dated April 4, 2002, for Group No. 884, Arizona.

The true meridian direction and length of all lines were determined by real time kinematic and static global positioning system observations using Trimble Navigation 4400 model receivers.

Preliminary to the resurvey, the lines of the prior surveys were retraced and search was made for all corners and other calls of record. Identified corners were remonumented in their original positions. Lost corners were reestablished and remonumented at proportionate positions based on the official record. The retracement data were thoroughly verified and only the true line field notes are given herein.

Geodetic control was derived from Global Positioning System (GPS) static observations post processed by National Geodetic Survey, Online Positioning User Service (OPUS), utilizing Continuously Operating Reference Stations (CORS) PIETOWN, WHITE SANDS and EL PASO 3. The NAD 83 (CORS96) (EPOCH: 2002), geographic position of the 1/4 section corner of sections 23 and 24, is as follows:

T. 18 S., R. 29 E., Gila and Salt River Meridian, Arizona

CHAINS

Latitude: 31° 51' 15.31" N. Longitude: 109° 21' 18.92" W.

The mean magnetic declination is 11° E.

**Dependent Resurvey of a Portion of the Subdivisional Lines,
T. 18 S., R. 29 E., Gila and Salt River Meridian, Arizona**

Restoring the surveys executed by
Theodore F. White, in 1882,
Jno P. Walker, in 1905 and
John F. Hesse and Alfred N. Oliver, in 1911

Beginning at the 1/4 sec. cor. of secs. 23 and 24, monumented with an iron post, 1 in. diam., loosely set, projecting 24 ins. above ground, in a scattered mound of stone, with brass cap mkd. 1/4 S23 S24 191.

At the corner point

Reset original iron post, 36 ins. long, 12 ins. in the ground to bedrock, in a supporting mound of stone, 3 ft. base, 2 ft. high.

Add the marks T18S R29E 2002 to the brass cap.

Deposit a magnet in a white plastic case at the base of the iron post.

N. 3°14' W., bet. secs. 23 and 24.

Over mountainous terrain, through dense brush and scattering timber.

39.92

Point for the cor. of secs. 13, 14, 23 and 24, at proportionate dist., there is no remaining evidence of the original cor.

Set a stainless steel post, 28 ins. long, 2½ ins. diam., 18 ins. in the ground, in a mound of stone, 4 ft. base, to top, with brass cap mkd.

T18S R29E	
S14	S13
S23	S24
2002	

from which

A pine, 24 ins. diam., bears N. 66¾° E., 73 lks. dist.,
mkd. T18S R29E S13 BT.

Dependent Resurvey of a Portion of the Subdivisional Lines,
T. 18 S., R. 29 E., Gila and Salt River Meridian, Arizona

CHAINS	
39.83	<p>A pine, 18 ins. diam., bears S. 80½° E., 114 lks. dist., mkd. T18S R29E S24 BT.</p> <p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p> <p>Cor. is located 85 lks. N. of a limestone rock face, 50 ft. high, bears N. 64' E. and W.</p> <hr/> <p>From the 1/4 sec. cor. of secs. 13 and 24, monumented with an iron post, 1 in. diam., firmly set, projecting 16 ins. above ground, with brass cap mkd. 1/4 S13 S24 1911.</p> <p>Add the marks T18S R29E 2002 to the brass cap.</p> <p>Raise a mound of stone, 4 ft. base, 2 ft. high, around iron post.</p> <p>N. 88°27' W., bet. secs. 13 and 24.</p> <p>Over mountainous terrain, through dense brush and heavy timber.</p> <p>The cor. of secs. 13, 14, 23 and 24.</p> <hr/> <p>N. 3°28' E., bet. secs. 13 and 14.</p> <p>Over mountainous terrain, through dense underbrush and heavy timber.</p>
17.14	Turkey Creek Road, 20 ft. wide, bears N. 70° E. and W.
17.80	Turkey Creek, 18 ft. wide, course N. 70° W.
19.965	<p>Point for the S. 1/16 sec. cor. of secs. 13 and 14.</p> <p>Set a stainless steel post, 28 ins. long, 2½ ins. diam., 32 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T18S R29E S 1/16 S14 S13 2002</p> <p>from which</p> <p>An unmarked USDA brass cap, 3½ ins. diam, located on the SE cor. of a curb of a bridge, bears S. 17' E., 266 lks. dist.</p>

Dependent Resurvey of a Portion of the Subdivisional Lines,
T. 18 S., R. 29 E., Gila and Salt River Meridian, Arizona

CHAINS	
39.93	<p>An X BO, chiseled on the SE curb of bridge, 15 ft. wide, bears S. 5' E., 255 lks. dist.</p> <p>A limestone rock outcrop, 100 x 80 x 50 ft., bears N. 57¼' W., 180 lks. dist., mkd. X BO on top.</p> <p>Cor. falls in the middle of a dirt road, 10 ft. wide, bears S. 80' E. and W.</p> <p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p> <p>The 1/4 sec. cor. of secs. 13 and 14, monumented with a mound of stone, 4 ft. base, 2 ft. high, with an iron post, 1 in. diam., lying loosely alongside, with brass cap mkd. 1/4 S13 S14 1911.</p> <p>At the corner point</p> <p>Set a stainless steel post, 28 ins. long, 2½ ins. diam., 6 ins. in the ground, in a mound of stone, 5 ft. base, to top, with brass cap mkd.</p> <p style="text-align: center;">T18S R29E 1/4 S14 S13 2002</p> <p>Deposit a magnet in a white plastic case at the base of the stainless steel post and place the iron post inside the stainless steel post.</p>
39.24	<p>N. 0°08' E., bet. secs. 13 and 14.</p> <p>Over mountainous terrain, through dense underbrush and heavy timber.</p> <p>The cor. of secs. 11, 12, 13 and 14, monumented with an iron post, 2 ins. diam., firmly set, projecting 16 ins. above ground, with brass cap mkd. T18S R29E S11 S12 S14 S13 1911.</p> <p>Add the marks 2002 to the brass cap.</p> <p>Raise a mound of stone, 6 ft. base, to top, around the post.</p> <hr/> <p>From the cor. of secs. 13, 14, 23 and 24.</p> <p>S. 88°32' W., bet. secs. 14 and 23.</p> <p>Over mountainous terrain, through dense brush and heavy timber.</p>

Dependent Resurvey of a Portion of the Subdivisional Lines,
T. 18 S., R. 29 E., Gila and Salt River Meridian, Arizona

CHAINS	
19.89	<p>Point for the E. 1/16 sec. cor. of secs. 14 and 23.</p> <p>Set a stainless steel post, 28 ins. long, 2½ ins. diam., 14 ins. in the ground, in a mound of stone, 5 ft. base, to top, with brass cap mkd.</p> <div style="text-align: center;"> <p>T18S R29E S14 E 1/16 ——— S23 2002</p> </div>
39.78	<p>The 1/4 sec. cor. of secs. 14 and 23, monumented with an iron post, 1 in. diam., firmly set, projecting 21 ins. above ground, with brass cap mkd. 1/4 S14 S23 1911, from which the original bearing trees</p> <p style="padding-left: 40px;">A pinon, 9 ins. diam., bears S. 10° W., 31 lks. dist., with scribe marks 1/4 BT visible on partially opened blaze. (Record: S. 7'45' W.)</p> <p style="padding-left: 40px;">A juniper, 24 ins. diam., bears N. 28½° W., 98 lks. dist., with scribe marks 1/4 BT visible on partially opened blaze.</p> <p>Add the marks T18S R29E 2002 to the brass cap.</p> <p>Raise mound of stone, 5 ft. base, to top, around the post.</p> <hr style="width: 20%; margin: 10px auto;"/> <p>N. 89°58' W., beginning new measurement.</p> <p>Over mountainous terrain, through brush and heavy timber.</p>
1.20	<p>Top of ridge, bears S. 50' E. and N. 50' W.</p>
18.90	<p>Point for the W. 1/16 sec. cor. of secs. 14 and 23.</p> <p>Set a stainless steel post, 28 ins. long, 2½ ins. diam., 26 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center;"> <p>T18S R29E S14 W 1/16 ——— S23 2002</p> </div> <p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p> <p>Raise a mound of stone, 4 ft. base, 2 ft. high, to the N.</p>

Dependent Resurvey of a Portion of the Subdivisional Lines,
T. 18 S., R. 29 E., Gila and Salt River Meridian, Arizona

CHAINS	
37.80	<p>Cor. is located on the S. top edge of a drain, 20 ft. wide, 6 ft. deep, drains S. 80' W.</p> <p>The cor. of secs. 14, 15, 22 and 23, monumented with an iron post, 2 ins. diam., firmly set, projecting 14 ins. above ground, in a collar of stone, with brass cap mkd. T18S R29E S15 S14 S22 S23 1911, from which the original bearing trees</p> <p>An oak snag, 14 ins. diam., bears N. 68° E., 84 lks. dist., with a healed blaze. (Record: N. 71'55' E.)</p> <p>A rotted pine stump, 20 ins. diam., bears S. 6½° E., 71 lks. dist.</p> <p>A rotted pine, size indeterminate, bears S. 81¼° W., 62 lks. dist., with scribe marks T18S R29E S22 BT visible on partial remains of blaze.</p> <p>A pine snag, 20 ins. diam., bears N. 16¼° W., 207 lks. dist., with scribe marks T18S R29E S15 BT visible on partially opened blaze.</p> <p>Raise mound of stone, 7 ft. base, to top, around the post.</p> <p>From this cor. point, the cor. of barbed wire fences, bears N. 13° W., 40 lks. dist., with fences extending N. 14' E., S. 49' E. and N. 66' W,</p> <p>From this same cor. point, a 1905 witness cor., bears N. 2'23' W., 8 lks. dist., monumented with an iron post, 6 ins. diam, firmly set, projecting 24 ins. above ground, in a mound of stone, 5 ft. base, 2½ ft. high, mkd. WC T18S R29E S15 S14 S22 S23 82 RESERVE. Remove and destroy iron post.</p>
20.08	<p>North, bet. secs. 14 and 15.</p> <p>Over mountainous terrain, through dense brush and heavy timber.</p> <p>Point for the S. 1/16 sec. cor. of secs. 14 and 15.</p> <p>Set a stainless steel post, 28 ins. long, 2½ ins. diam., 6 ins. in the ground to bedrock, in a mound of stone, 5 ft. base, to top, with brass cap mkd.</p> <p style="text-align: center;">T18S R29E S 1/16 S15 S14 2002</p> <p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p>

Dependent Resurvey of a Portion of the Subdivisional Lines,
T. 18 S., R. 29 E., Gila and Salt River Meridian, Arizona

CHAINS	
	Cor. is located 7 lks. E. of an irregular fence, bears N. 40' E. and S. 35' W.
30.12	Point for the N-S 1/64 sec. cor. of secs. 14 and 15.
	Set a stainless steel post, 28 ins. long, 2½ ins. diam., 28 ins. in the ground, with brass cap mkd.
	<p style="text-align: center;">T18S R29E N-S 1/64 S15 S14 2002</p>
	Deposit a magnet in a white plastic case at the base of the stainless steel post.
	Cor. is located 30 lks. W. of an irregular fence, bears N. 51' E. and S. 23' W.
39.30	Turkey Creek Road, 20 ft. wide, bears S. 82° E. and N. 82° W.
40.05	The witness cor. to the 1/4 sec. cor. of secs. 14 and 15, monumented with an iron post, 1 in. diam, firmly set, projecting 16 ins. above ground, in a mound of stone and cement, 2 ft. base, ½ ft. high, mkd. 1/4 S15 S14 1911, from which the original bearing trees
	<p style="text-align: center;">A forked juniper stump, 32 ins. diam., bears S. 72¼° E., 156 lks. dist., with a healed blaze. (Record: S. 81'26' E.)</p>
	<p style="text-align: center;">A forked juniper, 24 ins. diam., bears N. 70¼° W., 60 lks. dist., with a healed blaze. (Record: N. 64'35' W.)</p>
	Add the marks T18S R29E WC 2002 to the brass cap.
	Raise mound of stone, 4 ft. base, to top, around the post.
	<p style="text-align: center;">_____</p> <p>N. 0°01' W., beginning new measurement.</p>
0.11	True point for the 1/4 sec. cor. of secs. 14 and 15, falls in Turkey Creek, dry, 20 ft. wide, draining E., where it is impracticable to establish a permanent monument.
7.00	Dirt road, 15 ft. wide, bears S. 75° E. and N. 75° W.
20.125	Point for the N. 1/16 sec. cor. of secs. 14 and 15.

Dependent Resurvey of a Portion of the Subdivisional Lines,
T. 18 S., R. 29 E., Gila and Salt River Meridian, Arizona

CHAINS	
40.14	<p>Set a brass tablet, $3\frac{1}{4}$ ins. diam, $3\frac{1}{2}$ in. stem, in drill hole in limestone rock outcrop, with top mkd.</p> <p style="text-align: center;">T18S R29E N 1/16 S15 S14 2002</p> <p>Deposit a magnet at the base of the drill hole.</p> <p>Raise a mound of stone, 3 ft. base, 2 ft. high, to the N.</p> <p>The cor. of secs. 10, 11, 14 and 15, monumented with an iron post, 2 ins. diam., loosely set, projecting 24 ins. above ground, in a collar of stone, with brass cap mkd. T18S R29E S10 S11 S15 S14 1911, from which the 1905 bearing trees</p> <p style="padding-left: 40px;">An oak stump, 14 ins. diam., bears N. 32° E., 106 lks. dist. (Record: N. $33^{\circ}15'$ E., 108 lks. dist.)</p> <p style="padding-left: 40px;">An oak snag, 21 ins. diam., bears N. $72\frac{1}{2}^{\circ}$ E., 116 lks. dist., with healed blaze.</p> <p>Add the marks 2002 to the brass cap.</p> <p>Raise a mound of stone, 7 ft. base, to top, around the post.</p> <p>From this cor. point, the cor. of barbed wire fences, bears N. 26° E., 10 lks. dist., with fences extending N. 4' E., S. 4' W. and W.</p> <p>From this same cor. point, a witness cor., bears N. $78^{\circ}00'$ W., 8 lks. dist., monumented with an iron post, 4 ins. diam, firmly set, projecting 48 ins. above ground, in a mound of stone, 4 ft. base, 3 ft. high, mkd. WC T18S R29E S10 S11 S14 S15 81 RESERVE. Remove and destroy iron post.</p> <hr/> <p>From the cor. of secs. 11, 12, 13 and 14.</p> <p>West, bet. secs. 11 and 14.</p> <p>Over rolling terrain through dense underbrush and heavy timber.</p>
39.93	<p>The $\frac{1}{4}$ sec. cor. of secs. 11 and 14, monumented with an iron post, 1 in. diam., loosely set, projecting 24 ins. above ground, in a collar of stone, with brass cap mkd. $\frac{1}{4}$ S11 S14 1911, from which the original bearing trees</p> <p style="padding-left: 40px;">An oak, 19 ins. diam., bears S. $6\frac{1}{2}^{\circ}$ W., 55 lks. dist., with a healed blaze. (Record: juniper, S. $5^{\circ}30'$ W., 120 lks. dist.)</p>

Dependent Resurvey of a Portion of the Subdivisional Lines,
T. 18 S., R. 29 E., Gila and Salt River Meridian, Arizona

CHAINS	
20.075	<p>A juniper, 45 ins. diam., bears N. 0¼° W., 118 lks. dist., with scribe marks 1/4 S11 BT visible on partially opened blaze. (Record: oak, N. 0'23' E., 55 lks. dist.)</p> <p>Add the marks T18S R29E 2002 to the brass cap.</p> <p>Raise a mound of stone, 6 ft. base, to top, around the post.</p> <hr/> <p>N. 89°52' W., beginning new measurement.</p> <p>Over rolling terrain through dense underbrush and heavy timber.</p> <p>Point for the W. 1/16 sec. cor. of secs. 11 and 14.</p> <p>Set a stainless steel post, 28 ins. long, 2½ ins. diam., 15 ins. in the ground to bedrock, in a mound of stone, 6 ft. base, to top, with brass cap mkd.</p> <div style="text-align: center;"> <p>T18S R29E S11 W 1/16 ——— S14 2002</p> </div> <p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p>
40.15	<p>The cor. of secs. 10, 11, 14 and 15.</p> <hr/> <p>North, bet. secs. 10 and 11.</p> <p>Over mountainous terrain through dense brush and scattering timber.</p>
39.80	<p>The 1/4 sec. cor. of secs. 10 and 11, monumented with an iron post, 1 in. diam., loosely set, projecting 15 ins. above ground, in a mound of stone, 4 ft. base, 1½ ft. high, with brass cap mkd. 1/4 S10 S11 1911, from which the remaining original bearing tree</p> <p>An oak snag, 11 ins. diam., bears N. 70¼° W., 62 lks. dist., with a healed blaze. (Record: 66 lks. dist.)</p> <p>Add the marks T18S R29E 2002 to the brass cap.</p> <p>Raise mound of stone, 5 ft. base, to top, around the post.</p> <p>The bearing tree is utilized as a fence cor. with fences extending N. and N. 60° W.</p>

Dependent Resurvey of a Portion of the Subdivisional Lines,
T. 18 S., R. 29 E., Gila and Salt River Meridian, Arizona

CHAINS	
40.09	<p>From the cor. of secs. 10, 11, 14 and 15.</p> <p>N. 89°57' W., bet. secs. 10 and 15.</p> <p>The 1/4 sec. cor. of secs. 10 and 15, monumented with an iron post, 1 in. diam., loosely set, projecting 27 ins. above ground, in a mound of stone, 3 ft. base, ½ ft. high, with brass cap mkd. 1/4 S10 S15 1911.</p> <p>Add the marks T18S R29E 2002 to the brass cap.</p> <p>Raise mound of stone, 4 ft. base, to top, around the post.</p> <p>Cor. is located 5 lks. S. of a 4 strand barbed wire fence cor., with fences extending N. 70' E. and W.</p> <hr/> <p>N. 89°53' W., beginning new measurement.</p> <p>Over rolling terrain through dense brush and scattering timber.</p>
40.30	<p>The cor. of secs. 9, 10, 15 and 16, monumented with an iron post, 2½ ins. diam., firmly set, in a collar of cement, projecting 7 ins. above ground, with brass cap mkd. T18S R29E S9 S10 S16 S15 1964, from which the remaining 1905 bearing trees</p> <p style="padding-left: 40px;">A juniper stump, 12 ins. diam., bears N. 21¼° E., 103 lks. dist., with illegible marks visible on partially opened blaze.</p> <p style="padding-left: 40px;">A juniper stump, 30 ins. diam., bears S. 66½° W., 53 lks. dist., with a healed blaze.</p> <p>Add the marks 2002 to the brass cap.</p> <hr/> <p>N. 0°02' W., bet. secs. 9 and 10.</p> <p>Over rolling terrain through dense brush and scattering timber.</p>
40.16	<p>The 1/4 sec. cor. of secs. 9 and 10, monumented with an iron post, 2½ ins. diam., firmly set, projecting 5 ins. above ground, in a mound of stone, 4 ft. base, to top, with an accessory mound of stone, 3 ft. base, 2 ft. high to the W., with brass cap mkd. T18S R29E 1/4 S9 S10 1964, from which the remaining 1905 bearing tree</p> <p style="padding-left: 40px;">A juniper, 19 ins. diam., bears S. 29¼° W., 115 lks. dist., with a healed blaze.</p> <p>and the 1964 bearing trees</p>

Dependent Resurvey of a Portion of the Subdivisional Lines,
T. 18 S., R. 29 E., Gila and Salt River Meridian, Arizona

CHAINS	
	<p>A juniper, 9 ins. diam., bears N. $39\frac{1}{4}^{\circ}$ E., 8 lks. dist., with a healed blaze.</p> <p>A pinon, 7 ins. diam., bears N. 52° W., 7 lks. dist., with a healed blaze.</p> <p>From this cor. point, the cor. of barbed wire fences, bears N. 42° W., 13 lks. dist., with fences extending E., S. 10' W. and W.</p> <hr/> <p>N. $0^{\circ}23'$ E., beginning new measurement.</p>
20.06	<p>Point for the N. 1/16 sec. cor. of secs. 9 and 10.</p> <p>Set a brass tablet, $3\frac{1}{4}$ ins. diam, $3\frac{1}{2}$ in. stem, in drill hole in limestone rock outcrop, with top mkd.</p> <p style="text-align: center;">T18S R29E N 1/16 S9 S10 2002</p> <p>Deposit a magnet at the base of the drill hole.</p> <p>Raise a mound of stone, 3 ft. base, 3 ft. high, to the W.</p>
30.09	<p>Point for the N-N 1/64 sec. cor. of secs. 9 and 10.</p> <p>Set a stainless steel post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 27 ins. in the ground, in a collar of stone, with brass cap mkd.</p> <p style="text-align: center;">T18S R29E N-N 1/64 S9 S10 2002</p> <p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p>
40.12	<p>From this cor. point, the cor. of barbed wire fences, bears N. 65° W., 8 lks. dist., with fences extending N. 60' E., S. 10' E. and N. 80' W.</p> <p>The cor. of secs. 3, 4, 9 and 10, monumented with an iron post, $2\frac{1}{2}$ ins. diam., firmly set, projecting 5 ins. above ground, with an accessory mound of stone, 3 ft. base, 1 ft. high, to the W., with brass cap mkd. T18S R29E S4 S3 S9 S10 1964, from which bearing trees of unknown origin reported in 1964</p>

Dependent Resurvey of a Portion of the Subdivisional Lines,
T. 18 S., R. 29 E., Gila and Salt River Meridian, Arizona

CHAINS	
	<p>An oak, 20 ins. diam., bears N. 61° E., 106 lks. dist., with a healed blaze.</p> <p>A juniper snag, 14 ins. diam., bears S. 65½° E., 106 lks. dist., with scribe marks T18S R29E visible on partially opened blaze. (Record: S. 63½'E.)</p> <p>A juniper snag, 14 ins. diam., bears S. 40¾° W., 106 lks. dist., with scribe marks T18S R29E S10 BT visible on partially opened blaze. (Record: S. 43¾' W.)</p> <p>An oak, 18 ins. diam., bears N. 56° W., 53 lks. dist., with a healed blaze.</p> <p>and the 1964 bearing trees</p> <p>A juniper, 12 ins. diam., bears N. 40½° E., 103 lks. dist., with scribe marks T18S R29E S3 BT visible on partially opened blaze. (Record: N. 42' E.)</p> <p>A juniper, 6 ins. diam., bears S. 40½° E., 34 lks. dist., with scribe marks T18S R29E S10 BT visible on partially opened blaze.</p> <p>A juniper, 10 ins. diam., bears N. 29½° W., 29 lks. dist., with scribe marks T18S R29E S4 BT visible on partially opened blaze.</p> <p>Add the marks 2002 to the brass cap.</p> <p>Raise mound of stone, 3 ft. base, 2½ ft. high, to the W.</p> <hr/> <p>From the 1/4 sec. cor. of secs. 3 and 10, monumented with an iron post, 1 in. diam., firmly set, projecting 19 ins. above ground, in a mound of stone, 2 ft. base, 1 ft. high, with brass cap mkd. 1/4 S3 S10 1911, from which the remaining original bearing tree</p> <p>A juniper snag, 29 ins. diam., bears S. 9¾° W., 114 lks. dist., with scribe marks 1/4 S10 BT visible on partially opened blaze.</p> <p>Add the marks T18S R29E 2002 to the brass cap.</p> <p>Raise mound of stone, 5 ft. base, to top, around the iron post.</p> <p>N. 89°55' W., bet. secs. 3 and 10.</p> <p>Over rolling terrain through dense brush and scattering timber.</p> <p>20.06 Point for the W. 1/16 sec. cor. of secs. 3 and 10.</p>

**Dependent Resurvey of a Portion of the Subdivisional Lines,
T. 18 S., R. 29 E., Gila and Salt River Meridian, Arizona**

CHAINS	
	<p>Set a stainless steel post, 28 ins. long, 2½ ins. diam., 16 ins. in the ground, in a mound of stone, 4 ft. base, to top, with brass cap mkd.</p> <p align="center">T18S R29E S3 W 1/16 ——— S10 2002</p> <p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p>
40.12	<p>The cor. of secs. 3, 4, 9 and 10.</p> <hr/> <p>From the witness cor. to the cor. of secs. 8, 9, 16 and 17, monumented with a limestone, 12 X 8 X 6 ins., firmly set, projecting 12 ins. above the ground, with an accessory mound of stone, 3 ft. base, 1 ft. high, to the W., mkd. WC on the S. face, with 4 notches on the E. and S. faces, from which the remaining 1905 bearing tree</p> <p align="center">An oak, 12 ins. diam., bears N. 26½° E., 66 lks. dist., with a healed blaze.</p> <p>Cor. is located alongside a 4 strand barbed wire fence, bears N. and S.</p> <p>From this cor. point, the 1/4 sec. cor. of secs. 16 and 17, monumented with a mound of stone, 5 ft. base, 1 ft. high, bears S. 0°03' E., 39.31 chs. dist. Not remonumented.</p> <p>N. 0°03' W., bet. secs. 16 and 17.</p> <p>Over rolling terrain through brush and scattering timber.</p>
0.80	<p>True point for the cor. of secs. 8, 9, 16 and 17, falls in a wash. Not monumented.</p> <hr/>
	<p>From the cor. of secs. 9, 10, 15 and 16.</p> <p>N. 89°58' W., bet. secs. 9 and 16.</p>
39.80	<p>Point for the 1/4 sec. cor. of secs. 9 and 16, at proportionate dist.; there is no remaining evidence of the original cor., not monumented.</p>

Dependent Resurvey of a Portion of the Subdivisional Lines,
T. 18 S., R. 29 E., Gila and Salt River Meridian, Arizona

CHAINS	
79.60	<p>The true point for the cor. of secs. 8, 9, 16 and 17.</p> <hr/> <p>N. 0°03' W., bet. secs. 8 and 9.</p> <p>Over mountainous terrain through brush and scattering timber.</p>
40.04	<p>The 1/4 sec. cor. of secs. 8 and 9, monumented with a limestone rock outcrop, 100 X 50 X 10 ft. above the ground, with an accessory mound of stone, 3 ft. base, 1 ft. high to the W., mkd. with a small X and 1/4 chiseled on the W. edge of the rock ledge, from which the 1905 bearing trees</p> <p style="padding-left: 40px;">A pinon, 10 ins. diam., bears N. 22¾° E., 70 lks. dist., with a healed blaze.</p> <p style="padding-left: 40px;">A pinon, 9 ins. diam., bears S. 85° W., 85 lks. dist., with a healed blaze.</p> <p>At the corner point</p> <p>Set a brass tablet, 3¼ ins. diam, 3½ in. stem, in drill hole in limestone rock outcrop, with top mkd.</p> <div style="text-align: center;"> <p>T18S R29E</p> <p>1/4</p> <p>S8 S9</p> <p>2002</p> </div> <p>Deposit a magnet at the base of the drill hole.</p> <p>From this cor. point, a witness cor., bears S. 89°40' W., 20 lks. dist., monumented with an iron post, 4 ins. diam, firmly set, projecting 42 ins. above ground, in a mound of stone, 7 ft. base, 3 ft. high, mkd. WC 1/4 S8 S9 78 RESERVE. Remove and destroy.</p> <hr/> <p>N. 0°46' W., beginning new measurement.</p> <p>Over mountainous terrain though dense brush and scattering timber.</p>
39.97	<p>Point for the cor. of secs. 4, 5, 8 and 9, at proportionate dist.; there is no remaining evidence of the original cor.</p> <p>Set a stainless steel post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.</p>

Dependent Resurvey of a Portion of the Subdivisional Lines,
T. 18 S., R. 29 E., Gila and Salt River Meridian, Arizona

CHAINS

T18S R29E	
S5	S4
S8	S9
2003	

Deposit a magnet in a white plastic case at the base of the stainless steel post.

From this cor. point, the cor. of secs. 1, 6, 7 and 12, on the W. bdy. of the Tp., bears S. 89°58' W., 159.17 chs. dist., monumented with an iron post, 2½ ins. diam., firmly set, projecting 12 ins. above the ground, in a mound of stone, 6 ft. base, to top, with an accessory mound of stone, 3½ ft. base, 2 ft. high, to the W., mkd. T18S R28E R29E S1 S6 S12 S7 1964.

Add the marks 2002 to the brass cap.

Cor is located 6 lks. E. of a 4 strand barbed wire fence, bears N. and S.

From this same cor. point, the cor. of secs. 4, 5, 32 and 33, at proportionate dist., on the N. bdy. of the Tp., bears N. 0°08' W., 80.10 chs. dist.; there is no remaining evidence of the original cor.

At the corner point

Set a stainless steel post, 28 ins. long, 2½ ins. diam., 1 in. in the ground, in a supporting mound of stone, 6 ft. base, to top, with brass cap mkd.

T17S R29E	
S32	S33
S 5	S 4
T18S	
2002	

from which

A forked juniper, 10 ins. diam., bears S. 89¼° W., 39 lks. dist., mkd. T18S R29E S5 BT.

Deposit a magnet in a white plastic case at the base of the stainless steel post.

From this sec. cor., the 1/4 sec. cor. of secs. 3 and 34, on the N. bdy. of the Tp., bears S. 89°57' E., 120.67 chs. dist., monumented with an iron post, 1 in. diam., loosely set, projecting 20 ins. above the ground, in a scattered mound of stone, mkd. S34 1/4 S3 1911.

**Dependent Resurvey of a Portion of the Subdivisional Lines,
T. 18 S., R. 29 E., Gila and Salt River Meridian, Arizona**

CHAINS	
	<p>Add the marks T17S R29E T18S 2002 to the brass cap.</p> <p>Raise mound of stone, 3½ ft. base, to top, around the iron post.</p> <p>From this same sec. cor., the cor. of Tps. 17 and 18 S., Rs. 28 and 29 E., bears N. 89°57' W., 158.94 chs. dist., monumented with an iron post, 2½ ins. diam., firmly set, projecting 16 ins. above the ground, in a mound of stone, 4 ft. base, to top, with brass cap mkd. T17S R28E R29E S36 S31 S1 S6 T18S 1964, from which the remaining 1905 bearing tree</p> <p style="padding-left: 40px;">A pinon, 9 ins. diam, bears N. 74¼' E., 94 lks. dist., with a healed blaze.</p> <p>Add the marks 2002 to the brass cap.</p> <p>Cor is located 36 lks. E. of a barbed wire fence, bears N. and S.</p> <p>These control lines were fully retraced and careful search was made for evidence of intervening cors., none of which was recovered.</p>
	<p>From the cor. of secs. 3, 4, 9 and 10.</p> <p>S. 89°50' W., bet. secs. 4 and 9.</p> <p>Over mountainous terrain through brush and scattering timber.</p>
20.10	<p>Point for the E. 1/16 sec. cor. of secs. 4 and 9.</p> <p>Set a stainless steel post, 28 ins. long, 2½ ins. diam., 12 ins. in the ground, in a supporting mound of stone, 4 ft. base, to top, with brass cap mkd.</p> <div style="text-align: center; margin: 20px 0;"> <p>T18S R29E</p> <p style="padding-left: 100px;">S4</p> <hr style="width: 100px; margin: 0 auto;"/> <p style="padding-left: 100px;">S9</p> <p>2003</p> </div> <p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p>
40.20	<p>Point for the 1/4 sec. cor. of secs. 4 and 9, at proportionate dist.; there is no remaining evidence of the original cor.</p> <p>Set a stainless steel post, 28 ins. long, 2½ ins. diam., 12 ins. in the ground, in a mound of stone, 5 ft. base, to top, with brass cap mkd.</p>

Dependent Resurvey of a Portion of the Subdivisional Lines,
T. 18 S., R. 29 E., Gila and Salt River Meridian, Arizona

CHAINS	
	<p style="text-align: center;">T18S R29E S4 1/4 ——— S9 2003</p> <p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p>
80.40	<p>The cor. of secs. 4, 5, 8 and 9.</p>
<hr/> <p>Subdivision of Section 9, T. 18 S., R. 29 E., Gila and Salt River Meridian, Arizona</p> <hr/>	
	<p>From the point for the 1/4 sec. cor. of secs. 9 and 16. N. 0°07' W., on the N. and S. centerline of sec. 9 Over rolling terrain through brush and scattering juniper.</p>
40.10	<p>Point for the center 1/4 sec. cor. of sec. 9, at intersection with the E. and W. centerline of sec. 9. Set a stainless steel post, 28 ins. long, 2½ ins. diam., flush with the ground, with brass cap mkd.</p>
	<p style="text-align: center;">T18S R29E C 1/4 S9 2003</p> <p>from which</p> <p style="padding-left: 40px;">A forked juniper, 15 ins. diam., bears N. 80½° W., 34 lks. dist., mkd. X BT.</p> <p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p> <p>Raise a mound of stone, 3 ft. base, 1½ ft. high, to the W.</p> <p>Cor. falls on the W. edge of dry sandy drain, 6 ft. wide, drains N. 38° W.</p> <p>From this cor. point, a mound of stone, 3 ft. base, 1 ft. high, with a rotten post in the middle, bears S. 85°42' W., 0.34 ch. dist.</p>
60.12	<p>Point for the center N. 1/16 sec. cor. of sec. 9.</p>

Subdivision of Section 9,
T. 18 S., R. 29 E., Gila and Salt River Meridian, Arizona

CHAINS	
80.14	<p>Set a stainless steel post, 28 ins. long, 2½ ins. diam., 12 ins. in the ground, in a supporting mound of stone, 5 ft. base, to top, with brass cap mkd.</p> <p style="text-align: center;">T18S R29E C N 1/16 S9 C 2003</p> <p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p> <p>The 1/4 sec. cor. of secs. 4 and 9.</p> <hr/> <p>From the 1/4 sec. cor. of secs. 9 and 10.</p> <p>S. 89°57' W., on the E. and W. centerline of sec. 9.</p> <p>Over rolling terrain through brush and scattering timber.</p>
19.93	<p>True point for the center E. 1/16 sec. cor. of sec. 9, falls in the middle of a drain, 30 ft. wide, 10 ft. deep, drains N. 55° W., where it is impracticable to establish a permanent monument.</p> <p>From this point, the point selected for a witness cor. to the E. 1/16 sec. cor. of sec. 9, bears N. 27°52' W., 0.94 ch. dist.</p> <p>Set a stainless steel post, 28 ins. long, 2½ ins. diam., flush with the ground, with brass cap mkd.</p> <p style="text-align: center;">WC T18S R29E E 1/16 C ——— C S9 2003 ↘</p> <p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p>
39.86	<p>The center 1/4 sec. cor. of sec. 9.</p>
79.61	<p>The 1/4 sec. cor. of secs. 8 and 9.</p> <hr/> <p style="text-align: center;">NE 1/4 Sec. 9</p> <hr/> <p>From the true point for the center E. 1/16 sec. cor. of sec. 9.</p>

Subdivision of Section 9,
T. 18 S., R. 29 E., Gila and Salt River Meridian, Arizona

CHAINS	
	N. 0°08' E., on the N. and S. centerline of the NE 1/4 of sec. 9.
20.04	Point for the NE 1/16 sec. cor. of sec. 9, at intersection with the E. and W. centerline of the NE 1/4 of sec. 9. Set a stainless steel post, 28 ins. long, 2½ ins. diam., 26 ins. in the ground, with brass cap mkd. T18S R29E NE 1/16 S9 2003 Deposit a magnet in a white plastic case at the base of the stainless steel post.
30.06	Point for the center N-NE 1/64 sec. cor. of sec. 9. Set a stainless steel post, 28 ins. long, 2½ ins. diam., 18 ins. in the ground, in a mound of stone, 3 ft. base, to top, with brass cap mkd. T18S R29E S9 C-N-NE 1/64 2003 Deposit a magnet in a white plastic case at the base of the stainless steel post.
40.08	The E. 1/16 sec. cor. of secs. 4 and 9. <hr/>
	From the N. 1/16 sec. cor. of secs. 9 and 10. S. 89°53' W., on the E. and W. centerline of the NE 1/4 of sec. 9.
20.015	The NE 1/16 sec. cor. of sec. 9.
40.03	The center N. 1/16 sec. cor. of sec. 9. <hr/>
	From the N-N 1/64 sec. cor. of secs. 9 and 10. S. 89°52' W., on the E. and W. centerline of the NE 1/4 of the NE 1/4 of sec. 9.
20.06	The center N-NE 1/64 sec. cor. of sec. 9. <hr/>

Subdivision of Section 10,
T. 18 S., R. 29 E., Gila and Salt River Meridian, Arizona

CHAINS	
40.00	<p>From the 1/4 sec. cor. of secs. 10 and 15.</p> <p>N. 0°03' E., on the N. and S. centerline of sec. 10.</p> <p>Over mountainous terrain through brush and scattering timber.</p> <p>Point for the center 1/4 sec. cor. of sec. 10, at intersection with the E. and W. centerline of sec. 10.</p> <p>Set a stainless steel post, 28 ins. long, 2½ ins. diam., 8 ins. in the ground, in a supporting mound of stone, 4 ft. base, to top, with brass cap mkd.</p> <p style="text-align: center;">T18S R29E C 1/4 S10 2002</p> <p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p>
60.15	<p>Point for the center N. 1/16 sec. cor. of sec. 10.</p> <p>Set a stainless steel post, 28 ins. long, 2½ ins. diam., 16 ins. in the ground, in a mound of stone, 5 ft. base, to top, with brass cap mkd.</p> <p style="text-align: center;">T18S R29E C N 1/16 S10 C 2002</p> <p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p>
80.30	<p>The 1/4 sec. cor. of secs. 3 and 10.</p> <hr/> <p>From the 1/4 sec. cor. of secs. 10 and 11.</p> <p>N. 89°40' W., on the E. and W. centerline of sec. 10.</p> <p>Over mountainous terrain through brush and scattering timber.</p>
40.06	<p>The center 1/4 sec. cor. of sec. 10.</p>
60.24	<p>Point for the center W. 1/16 sec. cor. of sec. 10.</p> <p>Set a stainless steel post, 28 ins. long, 2½ ins. diam., 10 ins. in the ground, in a mound of stone, 4 ft. base, to top, with brass cap mkd.</p>

Subdivision of Section 10,
T. 18 S., R. 29 E., Gila and Salt River Meridian, Arizona

CHAINS	
75.375	<p style="text-align: center;">T18S R29E W 1/16 C ——— C S10 2002</p> <p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p> <p>Point for the center W-W-W 1/256 sec. cor. of sec. 10.</p> <p>Set a stainless steel post, 28 ins. long, 2½ ins. diam., 26 ins. in the ground, with brass cap mkd.</p>
80.42	<p style="text-align: center;">T18S R29E W-W-W 1/256 C ——— C S10 2002</p> <p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p> <p>Raise a mound of stone, 3½ ft. base, 2 ft. high, to the N.</p> <p>From this cor. point, the cor. of barbed wire fences, bears N. 20° E., 12 lks. dist., with fences extending N., S. 80' E and N. 85' W.</p> <p>The 1/4 sec. cor. of secs. 9 and 10.</p> <hr style="width: 100%;"/> <p style="text-align: center;">NW 1/4 Sec. 10</p> <hr style="width: 100%;"/> <p>From the center W. 1/16 sec. cor. of sec. 10.</p> <p>N. 0°13' E., on the N. and S. centerline of the NW 1/4 of sec. 10.</p> <p>Over rolling terrain through brush and scattering timber.</p>
20.11	<p>Point for the NW 1/16 sec. cor. of sec. 10, at intersection with the E. and W. centerline of the NW 1/4 of sec. 10.</p> <p>Set a stainless steel post, 28 ins. long, 2½ ins. diam., 23 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T18S R29E NW 1/16 S10 2002</p>

**Subdivision of Section 10,
T. 18 S., R. 29 E., Gila and Salt River Meridian, Arizona**

CHAINS	
	Deposit a magnet in a white plastic case at the base of the stainless steel post.
40.22	The W. 1/16 sec. cor. of secs. 3 and 10.
	From the center N. 1/16 sec. cor. of sec. 10. N. 89°48' W., on the E. and W. centerline of the NW 1/4 of sec. 10. Over rolling terrain through brush and scattering timber.
20.12	The NW 1/16 sec. cor. of sec. 10.
35.21	Point for the center W-W-NW 1/256 sec. cor. of sec. 10. Set a stainless steel post, 28 ins. long, 2½ ins. diam., 22 ins. in the ground, with brass cap mkd.
	T18S R29E S10 C-W-W-NW 1/256 2002
	Deposit a magnet in a white plastic case at the base of the stainless steel post.
	Raise a mound of stone, 4 ft. base, 2½ ft. high, to the N.
40.24	The N. 1/16 sec. cor. of secs. 9 and 10.
	From the center W-W-W 1/256 sec. cor. of sec. 10. N. 0°20' E., on the N. and S. centerline of the SW 1/4 of SW 1/4 of the NW 1/4 of sec. 10.
10.04	Point for the center W-SW-NW 1/256 sec. cor. of sec. 10, not monumented.
	N. 0°20' E., on the N. and S. centerline of the NW 1/4 of SW 1/4 of the NW 1/4 of sec. 10.
10.04	The center W-W-NW 1/256 sec. cor. of sec. 10.

Subdivision of Section 14,
T. 27 N., R. 19 E., Gila and Salt River Meridian, Arizona

CHAINS	
10.135	<p>From the 1/4 sec. cor. of secs. 14 and 23.</p> <p>N. 1°41' E., on the N. and S. center line of sec. 14.</p> <p>Over mountainous terrain through brush and heavy timber.</p> <p>Point for the center S-S 1/64 sec. cor. of sec. 14.</p> <p>Set a stainless steel post, 28 ins. long, 2½ ins. diam., 12 ins. in the ground, in a mound of stone, 5 ft. base, to top, with brass cap mkd.</p> <p style="text-align: center;">T18S R29E C S-S 1/64 S14 C 2002</p> <p>from which</p> <p style="text-align: center;">A limestone rock outcrop, 20 X 10 X 10 ft. above ground, bears S. 16½' W., 38 lks. dist., mkd X BO on the NE face.</p> <p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p>
20.27	<p>Point for the center S. 1/16 sec. cor. of sec. 14.</p> <p>Set a stainless steel post, 28 ins. long, 2½ ins. diam., 14 ins. in the ground, in a mound of stone, 4½ ft. base, to top, with brass cap mkd.</p> <p style="text-align: center;">T18S R29E C S 1/16 S14 C 2002</p> <p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p>
30.405	<p>Point for the center N-S 1/64 sec. cor. of sec. 14.</p> <p>Set a stainless steel post, 28 ins. long, 2½ ins. diam., 26 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T18S R29E C N-S 1/64 S14 C 2002</p>

**Subdivision of Section 14,
T. 27 N., R. 19 E., Gila and Salt River Meridian, Arizona**

CHAINS	
40.54	<p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p> <p>Raise a mound of stone, 5 ft. base, 2 ft. high, to the W.</p> <p>Cor. falls on the S. edge of a dirt road, 10 ft. wide, bears S. 20' E. and N. 40' W.</p> <p>Cor. is located 17 lks. N. of Turkey Creek, dry, 20 ft. wide, drains S. 65' W.</p> <p>Point for the center 1/4 sec. cor. of sec. 14, at intersection with the E. and W. centerline of sec. 14.</p> <p>Set a stainless steel post, 28 ins. long, 2½ ins. diam., 5 ins. in the ground to bedrock, in a supporting mound of stone, 4 ft. base, to top, with brass cap mkd.</p> <p style="text-align: center;">T18S R29E C 1/4 S14 2002</p> <p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p>
50.44	<p>Point for the center S-N 1/64 sec. cor. of sec. 14.</p> <p>Set a stainless steel post, 28 ins. long, 2½ ins. diam., 4 ins. in the ground to bedrock, in a supporting mound of stone, 5 ft. base, to top, with brass cap mkd.</p> <p style="text-align: center;">T18S R29E C S-N 1/64 S14 C 2002</p> <p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p> <p>Cor. falls on the W. top edge of a drain, 30 ft. wide, 15 ft. deep, drains S. 60' W.</p>
60.34	<p>True point for the center N. 1/16 sec. cor. of sec. 14, falls on a precipitous and unsafe slope where it is impracticable to establish a permanent monument.</p> <p>From this point, the point selected for the witness cor. to the N. 1/16 sec. cor. of sec. 14, bears N. 89'11' W., 1.07 chs. dist.</p>

Subdivision of Section 14,
T. 18 S., R. 29 E., Gila and Salt River Meridian, Arizona

CHAINS	
80.14	<p>Set a stainless steel post, 28 ins. long, 2½ ins. diam., 20 ins. in the ground, in a mound of stone, 4 ft. base, to top, with brass cap mkd.</p> <div style="text-align: center;"> <p>WC T18S R29E C → N 1/16 S14 C 2002</p> </div> <p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p> <p>The 1/4 sec. cor. of secs. 11 and 14.</p> <hr/> <p>From the 1/4 sec. cor. of secs. 13 and 14.</p> <p>S. 89°31' W., on the E. and W. centerline of sec. 14.</p> <p>Over mountainous terrain through dense brush and scattering timber.</p>
20.50	<p>Point for the center E. 1/16 sec. cor. of sec. 14.</p> <p>Set a stainless steel post, 28 ins. long, 2½ ins. diam., 18 ins. in the ground, in a mound of stone, 4 ft. base, to top, with brass cap mkd.</p> <div style="text-align: center;"> <p>T18S R29E E 1/16 C ——— C S14 2002</p> </div> <p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p> <p>Cor. falls on a steep rocky SW slope.</p>
41.00	<p>The center 1/4 sec. cor. of sec. 14.</p>
60.49	<p>Point for the center W. 1/16 sec. cor. of sec. 14, not monumented.</p>
79.98	<p>The true point for the 1/4 sec. cor. of secs. 14 and 15.</p> <hr/>

Subdivision of Section 14,
T. 18 S., R. 29 E., Gila and Salt River Meridian, Arizona

CHAINS	SE 1/4 Sec. 14
	<hr style="width: 30%; margin: auto;"/>
	<p>From the E. 1/16 sec. cor. of secs. 14 and 23.</p> <p>N. 2°34' E., on the N. and S. centerline of the SE 1/4 of sec. 14.</p>
10.055	<p>Point for the center S-SE 1/64 sec. cor. of sec. 14.</p> <p>Set a stainless steel post, 28 ins. long, 2½ ins. diam., 28 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T18S R29E S14 C-S-SE 1/64 2002</p>
	<p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p>
20.11	<p>Point for the SE 1/16 sec. cor. of sec. 14, at intersection with the E. and W. centerline of the SE 1/4 of sec. 14.</p> <p>Set a stainless steel post, 28 ins. long, 2½ ins. diam., 14 ins. in the ground, in a mound of stone, 5 ft. base, to top, with brass cap mkd.</p> <p style="text-align: center;">T18S R29E SE 1/16 S14 2002</p>
	<p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p>
	<p>Cor. falls on top of S. top bank of Turkey Creek.</p>
20.60	<p>Turkey Creek, 15 ft. wide, course N. 85° W.</p>
30.165	<p>Point for the center N-SE 1/64 sec. cor. of sec. 14.</p> <p>Set a stainless steel post, 28 ins. long, 2½ ins. diam., 16 ins. in the ground, in a supporting mound of stone, 3½ ft. base, to top, with brass cap mkd.</p> <p style="text-align: center;">T18S R29E S14 C-N-SE 1/64 2002</p>

Subdivision of Section 14,
T. 18 S., R. 29 E., Gila and Salt River Meridian, Arizona

CHAINS	
	<p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p> <p>Cor. falls on steep S. slope.</p>
40.22	<p>The center E. 1/16 sec. cor. of sec. 14.</p> <hr/> <p>From the S. 1/16 sec. cor. of secs. 13 and 14.</p> <p>S. 89°02' W., on the E. and W. centerline of the SE 1/4 of sec. 14.</p>
20.195	<p>The SE 1/16 sec. cor. of sec. 14.</p>
40.39	<p>The center S. 1/16 sec. cor. of sec. 14.</p> <hr/> <p>From the center S-SE 1/64 sec. cor. of sec. 14.</p> <p>S. 88°47' W., on the E. and W. centerline of the SW 1/4 of the SE 1/4 of sec. 14.</p>
20.04	<p>The center S-S 1/64 sec. cor. of sec. 14.</p> <hr/> <p>From the center N-SE 1/64 sec. cor. of sec. 14.</p> <p>S. 89°16' W., on the E. and W. centerline of the NW 1/4 of the SE 1/4 of sec. 14.</p>
20.35	<p>The center N-S 1/64 sec. cor. of sec. 14.</p> <hr/> <p style="text-align: center;">SW 1/4 Sec. 14</p> <hr/> <p>From the W. 1/16 sec. cor. of secs. 14 and 23.</p> <p>N. 0°50' E., on the N. and S. centerline of the SW 1/4 of sec. 14.</p>
20.18	<p>Point for the SW 1/16 sec. cor. of sec. 14, at intersection with the E. and W. centerline of the SW 1/4 of sec. 14.</p> <p>Set a stainless steel post, 28 ins. long, 2½ ins. diam., 6 ins. in the ground, in a supporting mound of stone, 5 ft. base, to top, with brass cap mkd.</p> <p style="text-align: center;">T18S R29E SW 1/16 S14 2002</p>

**Subdivision of Section 14,
T. 18 S., R. 29 E., Gila and Salt River Meridian, Arizona**

CHAINS	
	<p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p> <p>Cor. falls on the SE. edge of ridge, bears S. 50' E and N. 50' W.</p>
30.27	<p>Point for the center N-SW 1/64 sec. cor. of sec. 14.</p> <p>Set a stainless steel post, 28 ins. long, 2½ ins. diam., 16 ins. in the ground, in a mound of stone, 6 ft. base, to top, with brass cap mkd.</p> <p style="text-align: center;">T18S R29E S14 C-N-SW 1/64 2002</p>
40.36	<p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p> <p>The point for the center W. 1/16 sec. cor. of sec. 14.</p> <hr/> <p>From the center S. 1/16 sec. cor. of sec. 14.</p> <p>S. 89°46' W., on the E. and W. centerline of the SW 1/4 of sec. 14.</p>
19.20	<p>The SW 1/16 sec. cor. of sec. 14.</p>
38.40	<p>The S. 1/16 sec. cor. of secs. 14 and 15.</p> <hr/> <p>From the center N-SW 1/64 sec. cor. of sec. 14.</p> <p>S. 89°38' W., on the E. and W. centerline of the NW 1/4 of the SW 1/4 of sec. 14.</p>
19.34	<p>The N-S 1/64 sec. cor. of secs. 14 and 15.</p> <hr/> <p style="text-align: center;">NW 1/4 Sec. 14</p> <hr/> <p>From the point for the center W. 1/16 sec. cor. of sec. 14.</p> <p>N. 0°50' E., on the N. and S. centerline of the NW 1/4 of sec. 14.</p>
9.955	<p>Point for the center S-NW 1/64 sec. cor. of sec. 14.</p>

**Subdivision of Section 14,
T. 18 S., R. 29 E., Gila and Salt River Meridian, Arizona**

CHAINS	
	<p>Set a brass tablet, 3¼ ins. diam, 3½ in. stem, in drill hole in limestone rock outcrop, with top mkd.</p> <p style="text-align: center;">T18S R29E S14 C-S-NW 1/64 2002</p> <p>Deposit a magnet at the base of the drill hole.</p> <p>Raise a mound of stone, 4 ft. base, 4 ft. high, to the W.</p> <p>Cor. falls on a limestone rock outcrop, 100 X 50 X 50 ft. above ground, bears S. 40' E. and N. 40' W.</p>
19.91	<p>Point for the NW 1/16 sec. cor. of sec. 14, at intersection with the E. and W. centerline of the NW 1/4 of sec. 14.</p> <p>Set a stainless steel post, 28 ins. long, 2½ ins. diam., 22 ins. in the ground, in a mound of stone, 4 ft. base, to top, with brass cap mkd.</p> <p style="text-align: center;">T18S R29E NW 1/16 S14 2002</p> <p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p> <p>Cor. is located 23 lks. W. of a limestone rock face, 30 ft. high, bears S. 20' E and N. 10' W. on a W. slope.</p>
39.82	<p>The W. 1/16 sec. cor. of secs. 11 and 14.</p> <hr/> <p>From the true point for the center N. 1/16 sec. cor. of sec. 14.</p> <p>S. 89°50' W., on the E. and W. centerline of the NW 1/4 of sec. 14.</p>
19.78	<p>The NW 1/16 sec. cor. of sec. 14.</p>
39.56	<p>The N. 1/16 sec. cor. of secs. 14 and 15.</p> <hr/> <p>From the center S-N 1/64 sec. cor. of sec. 14.</p> <p>S. 89°40' W., on the E. and W. centerline of the SE 1/4 of the NW 1/4 of sec. 14.</p>

Subdivision of Section 14,
T. 18 S., R. 29 E., Gila and Salt River Meridian, Arizona

<p>CHAINS 19.63</p>	<p>The center S-NW 1/64 sec. cor. of sec. 14.</p> <hr/> <p style="text-align: center;">GENERAL DESCRIPTION</p> <hr/> <p>This survey is located near Willcox, Arizona. Elevations range from about 6000 to 7500 feet above sea level.</p> <p>The land is extremely rough and mountainous, covered with a dense growth of underbrush with oak, pine, and juniper timber.</p> <p>Access is by way of County Road 186.</p> <p>The mean magnetic declination of 11° E. was derived from the United States Geological Survey computer program GEOMAG, utilizing the World Magnetic Model for Epoch 2000 for the dates of survey.</p> <hr/>
-------------------------	--

