

ORIGINAL

**UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT**

FIELD NOTES
OF THE
DEPENDENT RESURVEY
OF
THE SIXTH STANDARD PARALLEL NORTH (SOUTH BOUNDARY),
THE SIXTH GUIDE MERIDIAN EAST (EAST BOUNDARY),
AND A PORTION OF THE NORTH BOUNDARY
AND
THE SURVEY OF A PORTION OF THE NORTH BOUNDARY,
AND
THE SUBDIVISIONAL LINES,
TOWNSHIP 25 NORTH, RANGE 24 EAST,
OF THE GILA AND SALT RIVER MERIDIAN,
IN THE STATE OF ARIZONA.

EXECUTED BY

Jones Curtiss, Cadastral Surveyor

Under Special Instructions dated and approved January 22, 2001, which provided for the surveys included under Group No. 863, and assignment instructions dated January 22, 2001.

Survey commenced December 11, 2001

Survey completed February 28, 2002

INDEX DIAGRAM

TOWNSHIP 25 NORTH RANGE 24 EAST
 GILA AND SALT RIVER MERIDIAN, ARIZONA

18 6 63	17 5 51	17 4 42	16 3 34	15 2 26	14 1 13
62 7 61	62 8 49	50 9 40	42 10 32	33 11 24	25 12 12
60 18 58	59 17 48	48 16 39	40 15 31	31 14 23	24 13 11
58 19 56	57 20 46	47 21 38	39 22 29	30 23 22	22 24 10
56 30 54	55 29 45	46 28 36	37 27 28	29 26 20	21 25 10
53 31 52 4	53 32 44 5	44 33 35 6	36 34 27 6	27 35 19 7	20 36 8 8

T. 25 N., R. 24 E., Gila and Salt River Meridian, Arizona

CHAINS

The following field notes describe the dependent resurvey of the Sixth Standard Parallel North (south boundary), the Sixth Guide Meridian East (east boundary), and a portion of the north boundary and the survey of a portion of the north boundary, and the subdivisional lines, Township 25 North, Range 24 East, Gila and Salt River Meridian, Arizona.

The history of surveys pertaining to this survey is as follows:

The Sixth Standard Parallel North, through Range 24 East, was surveyed by Frank Follman in 1883. The Sixth Guide Meridian East, through Township 25 North, and a portion of the north boundary of Township 25 North, Range 24 East, was surveyed by Frederick C. Miller in 1915. The west boundary was surveyed by Jones Curtiss in 2001-02, executed concurrently under this same group.

The survey was executed in accordance with the specifications as set forth in the Manual of Instructions for the Survey of the Public Lands of the United States, 1973, and the Special Instructions dated January 22, 2001, for Group No. 863, Arizona.

The true meridian direction and length of all lines were determined by real time kinematic global positioning system observations using Trimble Navigation 5700 model receivers.

Preliminary to the resurvey, the lines of the prior surveys were retraced and search was made for all corners and other calls of record. Identified corners were remonumented in their original positions. Lost corners were reestablished and remonumented at proportionate positions based on the official record. The retracement data were thoroughly verified and only the true line field notes are given herein.

Geodetic control was derived from first order U. S. Coast and Geodetic Survey triangulation station "INDIAN 1951" and second order U. S. Geological Survey triangulation station "GREASEWOOD 1972", as published by the National Geodetic Survey, NAD 83 (1992). The geographic position of the southeast corner of the township is as follows:

Latitude: 35°31'03.89" N. Longitude: 109°43'12.35" W.

The mean magnetic declination is 11 1/2° E.

Dependent Resurvey of the Sixth Standard Parallel North (South Boundary),
T. 25 N., R. 24 E., Gila and Salt River Meridian, Arizona

CHAINS	
	<p style="text-align: center;">Restoring the survey executed by Frank Follman, in 1883</p> <hr style="width: 20%; margin: auto;"/> <p>Beginning at the stan. cor. of Tps. 25 N., Rs. 23 and 24 E., monumented with a stainless steel post, 2 1/2 ins. diam., with brass cap, set, mkd. and witnessed, as described in the field notes of the dependent resurvey of the Sixth Standard Parallel North, (south boundary), T. 25 N., R. 23 E., executed concurrently under this same group.</p> <p>Cor. is located 47 lks. W. of Navajo Route 6322, a graded road, 18 ft. wide, bears NE and SW.</p> <p>S. 89°55' E., on the S. bdy. of sec. 31.</p> <p>Over rolling land.</p>
40.17	<p>Point for the stan. 1/4 sec. cor. of sec. 31, at proportionate dist.; there is no remaining evidence of the original cor.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p>
	<p style="text-align: center;">SC T 25 N R 24 E 1/4 S 31</p> <hr style="width: 10%; margin: auto;"/> <p style="text-align: center;">2001</p>
	<p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p>
46.70	<p>W. rim of a mesa, bears SSE and NNW.</p>
65.00	<p>NE rim of the same mesa, bears N. and S., thence descend over N. slope.</p>
80.34	<p>Point for the stan. cor. of secs. 31 and 32, at proportionate dist.; there is no remaining evidence of the original cor.</p>
	<p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p>
	<p style="text-align: center;">SC T 25 N R 24 E S 31 S 32</p> <hr style="width: 10%; margin: auto;"/> <p style="text-align: center;">° 2001</p>
	<p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p>

Dependent Resurvey of the Sixth Standard Parallel North (South Boundary),
T. 25 N., R. 24 E., Gila and Salt River Meridian, Arizona

CHAINS	
	<p>Cor. is located on a steep N. slope, 15 lks. S. and 61 lks. W. of a sandstone ledge, bears ESE and WNW.</p> <hr/>
	<p>S. 89°55' E., on the S. bdy. of sec. 32. Over rolling and broken land.</p>
35.40	<p>W. rim of a mesa, bears N. and S., thence over rolling land.</p>
40.17	<p>Point for the stan. 1/4 sec. cor. of sec. 32, at proportionate dist.; there is no remaining evidence of the original cor.</p>
	<p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">SC T 25 N R 24 E <u>1/4 S 32</u></p> <p style="text-align: center;">2001</p>
	<p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p>
52.70	<p>E. rim of a mesa, bears N. and S., thence descend into rugged and broken land.</p>
80.34	<p>Point for the stan. cor. of secs. 32 and 33, at proportionate dist.; there is no remaining evidence of the original cor.</p>
	<p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">SC T 25 N R 24 E <u>S 32 S 33</u></p> <p style="text-align: center;">2001</p>
	<p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p> <p>From this cor. point, the remains of U. S. Geological Survey triangulation station "GREASEWOOD 1972", bears S. 51°21' E., 13.60 chs. dist., monumented with a 5/8 in. square impression, as an indication mark of the stem end of a standard brass tablet, in the center of a concrete block, 7 ins. square, firmly set, projecting 4 ins. above ground, with top broken, and in a mound of stone, 3 ft. base, 1 ft. high.</p> <hr/>

Dependent Resurvey of the Sixth Standard Parallel North (South Boundary),
T. 25 N., R. 24 E., Gila and Salt River Meridian, Arizona

CHAINS	
	<p>S. 89°55' E., on the S. bdy. of sec. 33.</p> <p>Over rolling land.</p>
40.17	<p>Point for the stan. 1/4 sec. cor. of sec. 33, at proportionate dist.; there is no remaining evidence of the original cor.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p>
	<p style="text-align: center;">SC T 25 N R 24 E 1/4 S 33</p> <hr style="width: 10%; margin: auto;"/>
	<p style="text-align: center;">2001</p> <p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p>
80.34	<p>Point for the stan. cor. of sec. 33 and 34, at proportionate dist.; there is no remaining evidence of the original cor.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p>
	<p style="text-align: center;">SC T 25 N R 24 E S 33 S 34</p> <hr style="width: 10%; margin: auto;"/>
	<p style="text-align: center;">2001</p> <p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p>
	<p>Cor. is located 1.00 ch. S. and 60 lks. W. of Navajo Route 28, a graded road, 25 ft. wide, bears SSE and NNW.</p> <hr/>
	<p>S. 89°55' E., on the S. bdy. of sec. 34.</p> <p>Over rolling land.</p>
40.17	<p>Point for the stan. 1/4 sec. cor. of sec. 34, at proportionate dist.; there is no remaining evidence of the original cor.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p>

Dependent Resurvey of the Sixth Standard Parallel North (South Boundary),
T. 25 N., R. 24 E., Gila and Salt River Meridian, Arizona

CHAINS	
	<p style="text-align: center;">SC T 25 N R 24 E <u>1/4 S 34</u></p> <p style="text-align: center;">2001</p>
	<p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p>
60.20	<p>High voltage transmission line, bears NE and SW.</p>
80.34	<p>Point for the stan. cor. of secs. 34 and 35, at proportionate dist.; there is no remaining evidence of the original cor.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p>
	<p style="text-align: center;">SC T 25 N R 24 E <u>S 34 S 35</u></p> <p style="text-align: center;">2001</p>
	<p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p>
	<hr/> <p>S. 89°55' E., on the S. bdy. of sec. 35.</p>
	<p>Over rolling land.</p>
40.17	<p>Point for the stan. 1/4 sec. cor. of sec. 35, at proportionate dist.; there is no remaining evidence of the original cor.</p>
	<p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p>
	<p style="text-align: center;">SC T 25 N R 24 E <u>1/4 S 35</u></p> <p style="text-align: center;">2001</p>
	<p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p>
80.34	<p>Point for the stan. cor. of secs. 35 and 36, at proportionate dist.; there is no remaining evidence of the original cor.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p>

Dependent Resurvey of the Sixth Standard Parallel North (South Boundary),
T. 25 N., R. 24 E., Gila and Salt River Meridian, Arizona

CHAINS	
	<p style="text-align: center;">SC T 25 N R 24 E <u>S 35 S 36</u></p> <p style="text-align: center;">2001</p>
	<p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p> <hr/>
	<p>S. 89°55' E., on the S. bdy. of sec. 36.</p>
	<p>Over rolling land.</p>
40.04	<p>Barbed wire fence, 5 strands, bears N. and S., from which the cor. of fences bears South, 11 1/2 lks. dist., with fences extending N. and SSE.</p>
40.17	<p>Point for the stan. 1/4 sec. cor. of sec. 36, at proportionate dist.; there is no remaining evidence of the original cor.</p>
	<p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p>
	<p style="text-align: center;">SC T 25 N R 24 E <u>1/4 S 36</u></p>
	<p style="text-align: center;">2001</p>
	<p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p>
80.34	<p>The cor. of Tps. 25 N., Rs. 24 and 25 E., monumented with a stainless steel post, 2 1/2 ins. diam., with brass cap, set and mkd., as described in the field notes of the dependent resurvey of the Sixth Standard Parallel North, (south boundary), T. 25 N., R. 22 E., executed concurrently under this same group.</p>
	<p style="text-align: center;">Dependent Resurvey of the Sixth Guide Meridian East (East Boundary), T. 25 N., R. 24 E., Gila and Salt River Meridian, Arizona</p> <hr/>
	<p style="text-align: center;">Restoring the survey executed by Frederick C. Miller, in 1915</p> <hr/>
	<p>N. 0°04' E., bet. secs. 31 and 36.</p>
	<p>Over rolling land.</p>

Dependent Resurvey of the Sixth Guide Meridian East (East Boundary),
T. 25 N., R. 24 E., Gila and Salt River Meridian, Arizona

CHAINS	
19.14	Barbed wire fence, 5 strands, bears ESE & WNW.
39.98	The 1/4 sec. cor. of secs. 31 and 36, monumented with an iron post, 36 ins. long, 1 in., diam., firmly set, projecting 24 ins. above ground, with brass cap mkd. 1/4 S36 S31 1915.
	At the corner point
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.
	T 25 N R 24 E R 25 E 1/4 S 36 S 31
	2001
	Deposit a magnet in a white plastic case at the base of the stainless steel post.
	Bury the iron post alongside the stainless steel post.
	<hr style="width: 20%; margin: auto;"/> N. 0°12' E., beginning new measurement.
35.00	Barbed wire fence, 5 strands, bears E. and W.
40.00	The cor. of secs. 25, 30, 31 and 36, monumented with an iron post, 36 ins. long, 3 ins. diam., firmly set, projecting 3 ins. above ground, with brass cap, badly damaged and barely legible, mkd. T25N R24E R25E S25 S30 S31 S36 1915, from which the remains of an original bearing tree
	A piñon stump, 12 ins. diam., projecting 8 ins. above ground, bears N. 50 1/2° E., 87 1/2 lks.; the cut trunk lying nearby mkd. T24N R25E S30 BT on open blaze. (Record: N. 49 1/4° E., 109 lks. dist.)
	At the corner point
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.
	T 25 N R 24 E R 25 E S 25 S 30 <hr style="width: 10%; margin: auto;"/> S 36 S 31
	2002
	Deposit a magnet in a white plastic case at the base of the stainless steel post.

Dependent Resurvey of the Sixth Guide Meridian East (East Boundary),
T. 25 N., R. 24 E., Gila and Salt River Meridian, Arizona

CHAINS	
	<p>Bury the iron post alongside the stainless steel post.</p> <hr/> <p>N. 0°08' E., bet. secs. 25 and 30.</p> <p>Over rolling land.</p>
5.80	Big Dam Wash, 40 ft. wide, 15 ft. deep, drains WSW.
40.04	<p>The 1/4 sec. cor. of secs. 25 and 30, determined from the remaining bearing tree</p> <p style="padding-left: 40px;">A piñon, 12 ins. diam., bears N. 69 1/2° E., 55 lks. dist., mkd. 1/4 S30 BT on open blaze.</p> <p>At the corner point</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center; padding: 10px 0;"> <p>T 25 N</p> <p>R 24 E R 25 E</p> <p>1/4</p> <p>S 25 S 30</p> <p>2002</p> </div> <p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p> <hr/> <p>N. 0°04' E., beginning new measurement.</p>
40.02	<p>The cor. of secs. 19, 24, 25 and 30, monumented with an iron post, 3 ins. diam., firmly set, projecting 6 ins. above ground, with brass cap mkd. T25N R24E R25E S24 S19 S25 S30 1915.</p> <p>Add the marks 2001 to the brass cap.</p> <hr/> <p>North, bet. secs. 19 and 24.</p> <p>Over rolling land.</p>
37.45	Navajo Route 9205, a graded road, 20 ft. wide, bears ESE and WNW.
40.08	<p>The 1/4 sec. cor. of secs. 19 and 24, determined from the original bearing trees</p> <p style="padding-left: 40px;">A piñon stump, 12 ins. diam., bears N. 37 1/4° E., 49 lks. dist., with scribe mks. BT visible on open blaze. (Record: N. 38° E.)</p>

Dependent Resurvey of the Sixth Guide Meridian East (East Boundary),
T. 25 N., R. 24 E., Gila and Salt River Meridian, Arizona

CHAINS	
	<p>A forked piñon, 18 ins. diam. at the base, bears N. 35 1/2° W., 76 lks. dist., mkd. 1/4 S24 BT on partially healed blaze.</p> <p>At the corner point</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T 25 N R 24 E R 25 E 1/4 S 24 S 19</p> <p style="text-align: center;">2002</p> <p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p> <hr/> <p>N. 0°05' W., beginning new measurement.</p>
5.60	Underground power line, bears E. and W.
6.60	Underground gas pipeline, bears E. and W.
39.85	<p>The cor. of secs. 13, 18, 19 and 24, monumented with an iron post, 3 ins. diam., firmly set, projecting 7 ins. above ground, with brass cap mkd. T25N R24E R25E S13 S18 S19 S24 1915, from which the original bearing trees</p> <p style="padding-left: 40px;">A forked piñon, 14 ins. diam. at the base, bears N. 83 1/2° E., 32 lks. dist., with a healed blaze. (Record: S. 81 1/2° E.)</p> <p style="padding-left: 40px;">A piñon, 12 ins. diam., bears S. 9° E., 50 lks. dist., erroneously mkd. T25N R24E S24 BT on open blaze. (Record: S. 8° W., 75 lks.)</p> <p>Add the marks 2001 to the brass cap.</p> <hr/> <p>N. 0°06' E., bet. secs. 13 and 18.</p> <p>Over rolling and broken land.</p>
15.70	High voltage transmission line, bears NE and SW.
39.99	The 1/4 sec. cor. of secs. 13 and 18, monumented with an iron post, 1 in. diam., firmly set, projecting 16 ins. above ground, with brass cap mkd. 1/4 S13 S18 1915, from which the remaining original bearing tree

Dependent Resurvey of the Sixth Guide Meridian East (East Boundary),
T. 25 N., R. 24 E., Gila and Salt River Meridian, Arizona

CHAINS	
	<p>A piñon, 8 ins. diam., bears N. 8 1/4° W., 5 lks. dist., erroneously mkd. 1/4 S18 BT on partially healed blaze. (Record: N. 1° E.)</p> <p>Add the marks T25N R24E R25E 2001 to the brass cap.</p> <hr/> <p>N. 0°02' E., beginning new measurement.</p> <p>Over rolling and broken land.</p>
39.97	<p>The cor. of secs. 7, 12, 13 and 18, monumented with an iron post, 3 ins. diam., firmly set, projecting 16 ins. above ground, with brass cap mkd. T25N R24E R25E S12 S7 S13 S18 1915, from which the original bearing trees</p> <p>A forked piñon, 16 ins. diam. at the base, bears N. 66 3/4° E., 34 1/2 lks. dist., with scribe mks. TN RE visible on open blaze. (Record: N. 69° E., 36 lks.)</p> <p>A piñon, 8 ins. diam., bears S. 48 3/4° E., 23 lks. dist., mkd. T25N R25E S18 on partially healed blaze. (Record: 27 lks.)</p> <p>A forked piñon, 9 ins. diam. at the base, bears S. 26 3/4° W., 25 lks. dist., mkd. T25N R24E S13 on partially healed blaze. (Record: S. 23° W.)</p> <p>Add the marks 2001 to the brass cap.</p> <hr/> <p>N. 0°01' W., bet. secs. 7 and 12.</p> <p>Over rolling and broken land.</p>
14.65	Big Wilderness Wash, 10 ft. wide, 5 ft. deep, drains W.
19.50	Big Wilderness Wash, 10 ft. wide, 5 ft. deep, drains NE.
22.65	Big Wilderness Wash, 15 ft. wide, 10 ft. deep, drains WSW.
40.02	<p>Point for the 1/4 sec. cor. of secs. 7 and 12, at proportionate dist.; there is no remaining evidence of the original cor.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T 25 N R 24 E R 25 E 1/4 S 12 S 7</p> <p style="text-align: center;">2002</p>

Dependent Resurvey of the Sixth Guide Meridian East (East Boundary),
T. 25 N., R. 24 E., Gila and Salt River Meridian, Arizona

CHAINS	
	<p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p>
80.04	<p>The cor. of secs. 1, 6, 7 and 12, monumented with an iron post, 3 ins. diam., firmly set, projecting 11 ins. above ground, with brass cap mkd. T25N R24E R25E S1 S6 S12 S7 1915.</p> <p>Add the marks 2001 to the brass cap.</p> <hr/>
	<p>N. 0°01' E., bet. secs. 1 and 6.</p> <p>Over rolling land.</p>
39.98	<p>The 1/4 sec. cor. of secs. 1 and 6, monumented with an iron post, 36 ins. long, 1 in. diam., loosely set, projecting 10 ins. above ground, with brass cap mkd. 1/4 S1 S6 1915, from which the remaining original bearing tree</p> <p style="padding-left: 40px;">A forked juniper, the southerly fork, 14 ins. diam., trunk bears N. 40° W., 1.01 chs. dist., fork mkd. 1/4 S1 BT on partially healed blaze. (Record: N. 42° W., 100 lks.)</p> <p>At the corner point</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center;"> <p>T 25 N R 24 E R 25 E 1/4 S 1 S 6 2002</p> </div> <p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p> <p>Bury the iron post alongside the stainless steel post.</p> <hr/>
	<p>N. 0°01' E., beginning new measurement.</p>
40.04	<p>The cor. of Tps. 25 and 26 N., Rs. 24 and 25 E., monumented with an iron post, 3 ins. diam., firmly set, projecting 12 ins. above ground, with brass cap mkd. T26N R24E R25E S36 S31 S1 S6 T25N 1915.</p> <p>Add the marks 2002 to the brass cap.</p>

Dependent Resurvey of a Portion of the North Boundary,
T. 25 N., R. 24 E., Gila and Salt River Meridian, Arizona

CHAINS	
	<p style="text-align: center;">Restoring the survey executed by Frederick C. Miller, in 1915</p> <hr/> <p>From the cor. of Tps. 25 and 26 N., Rs. 24 and 25 E., hereinbefore described.</p> <p>S. 89°59' W., bet. secs. 1 and 36.</p> <p>Over rolling and broken land.</p> <p>40.04 The 1/4 sec. cor. of secs. 1 and 36, determined South, 1 lk. dist. from the S. edge of the original mound of stone, 3 ft. base and 1 ft. high.</p> <p>At the corner point</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T 26 N R 24 E S 36 1/4 ——— S 1 T 25 N</p> <p style="text-align: center;">2002</p> <p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p> <p>Cor. is located on a narrow, pointed spur on the rim of a mesa, 62 lks. wide, bears ESE and WNW.</p> <hr/> <p>N. 89°59' W., beginning new measurement.</p> <p>12.50 Apache County Road C414, a graded road, 25 ft. wide, bears ENE and WSW.</p> <p>40.04 Point for the cor. of secs. 1, 2, 35 and 36, at proportionate dist.; there is no remaining evidence of the original cor.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p>

Dependent Resurvey of a Portion of the North Boundary,
T. 25 N., R. 24 E., Gila and Salt River Meridian, Arizona

CHAINS									
	<table border="0"> <tr> <td>T 26 N</td> <td>R 24 E</td> </tr> <tr> <td>S 35</td> <td>S 36</td> </tr> <tr> <td>S 2</td> <td>S 1</td> </tr> <tr> <td colspan="2">T 25 N</td> </tr> </table>	T 26 N	R 24 E	S 35	S 36	S 2	S 1	T 25 N	
T 26 N	R 24 E								
S 35	S 36								
S 2	S 1								
T 25 N									
	2002								
	Deposit a magnet in a white plastic case at the base of the stainless steel post.								

	N. 89°59' W., on the S. bdy. of sec. 35, T. 26 N., R. 24 E.								
	Over rolling and broken Land.								
19.80	Pueblo Colorado Wash, 15 ft. wide, 2 ft. deep, drains SSW.								
27.47	An iron well casing, 13 ins. diam., in the center of a windmill, bears South, 2.00 chs. dist.								
32.18	Navajo Route 15, asphalt pavement, 27 ft. wide, bears NNE and SSW.								
40.04	Point for the 1/4 sec. cor. of secs. 2 and 35, at proportionate dist.; there is no remaining evidence of the original cor. This cor. now functions as the 1/4 sec. cor. of sec. 35 only.								
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.								
	<table border="0"> <tr> <td>T 26 N</td> <td>R 24 E</td> </tr> <tr> <td>1/4 S 35</td> <td></td> </tr> <tr> <td colspan="2">-----</td> </tr> <tr> <td>T 25 N</td> <td>R 24 E</td> </tr> </table>	T 26 N	R 24 E	1/4 S 35		-----		T 25 N	R 24 E
T 26 N	R 24 E								
1/4 S 35									

T 25 N	R 24 E								
	2002								
	Deposit a magnet in a white plastic case at the base of the stainless steel post.								
	Cor. is located 3 lks. E. of a sandstone ledge, 5 ft. high, bears NNE and SSW, on the E. slope of a mesa.								
80.08	The cor. of secs. 2, 3, 34 and 35, monumented with an iron post, 3 ins. diam., firmly set, projecting 8 ins. above ground, with brass cap mkd. T26N R24E S34 S35 S3 S2 T25N 1915, with a mound of stone, 3 ft. base 2 ft. high, W. of cor. This cor. now functions as the cor. of secs. 34 and 35 only.								
	Remark the brass cap to read								

**Dependent Resurvey of a Portion of the North Boundary,
T. 25 N., R. 24 E., Gila and Salt River Meridian, Arizona**

CHAINS	
	<p style="text-align: center;">T26N R24E S 34 S 35 ----- T25N R24E S2</p> <p style="text-align: center;">2002 1915</p> <p>Cor. is located 1.15 chs. W. and 2.60 chs. N. of a wash, 15 ft. wide, 20 ft. deep, drains SSW.</p> <hr/> <p style="text-align: center;">Survey of a Portion of the North Boundary, T. 25 N., R. 24 E., Gila and Salt River Meridian, Arizona</p> <hr/> <p>From the cor. of secs. 34 and 35 only, hereinbefore described.</p> <p>N. 89°52' W., on the S. bdy. of sec. 34.</p> <p>Over rolling land.</p>
40.00	<p>Point for the 1/4 sec. cor. of sec. 34 only.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T 26 N R 24 E 1/4 S 34 ----- T 25 N R 24 E</p> <p style="text-align: center;">2002</p> <p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p> <p>Cor. is located 35 lks. W. of a wash, 5 ft. wide, 10 ft. deep, drains SSW.</p>
80.00	<p>Point for the cor. of secs. 33 and 34 only.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T 26 N R 24 E S 33 S 34 ----- T 25 N R 24 E S3</p> <p style="text-align: center;">2002</p>

**Survey of a Portion of the North Boundary,
T. 25 N., R. 24 E., Gila and Salt River Meridian, Arizona**

CHAINS	
	<p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p> <p>Land, rolling and broken Soil sand and sandy clay. Timber, piñon and juniper; undergrowth, sagebrush and native grasses.</p> <hr/> <p>N. 89°52' W., on the S. bdy. of sec. 33.</p> <p>Over rolling and broken land.</p>
40.00	<p>Point for the 1/4 sec. cor. of sec. 33 only.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T 26 N R 24 E 1/4 S 33 <hr style="width: 50px; margin: auto;"/>T 25 N R 24 E</p> <p style="text-align: center;">2002</p>
80.00	<p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p> <p>Point for the cor. of secs. 32 and 33 only.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T 26 N R 24 E S 32 S 33 <hr style="width: 50px; margin: auto;"/>T 25 N R 24 E</p> <p style="text-align: center;">S4</p> <p style="text-align: center;">2002</p> <p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p> <p>Land, rolling and broken land. Soil, sand and sandy clay. Timber, piñon and juniper; undergrowth, sagebrush and native grasses.</p> <hr/> <p>N. 89°52' W., on the S. bdy. of sec. 32.</p> <p>Over rolling land.</p>

Survey of a Portion of the North Boundary,
T. 25 N., R. 24 E., Gila and Salt River Meridian, Arizona

CHAINS	
40.00	<p>Point for the 1/4 sec. cor. of sec. 32 only.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T 26 N R 24 E 1/4 S 32 <hr style="width: 10%; margin: auto;"/>T 25 N R 24 E</p> <p style="text-align: center;">2002</p> <p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p>
80.00	<p>Point for the cor. of secs. 31 and 32 only.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T 26 N R 24 E S 31 S 32 <hr style="width: 10%; margin: auto;"/>T 25 N R 24 E S5</p> <p style="text-align: center;">2002</p> <p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p> <p>Land, rolling. Soil, sand and sandy clay. No timber; greasewood, scattered brush and native grasses.</p> <hr style="width: 80%; margin: 10px auto;"/> <p>N. 89°52' W., on the S. bdy. of sec. 31.</p> <p>Over rolling and broken land.</p>
40.00	<p>Point for the 1/4 sec. cor. of sec. 31 only.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T 26 N R 24 E 1/4 S 31 <hr style="width: 10%; margin: auto;"/>T 25 N R 24 E</p> <p style="text-align: center;">2002</p> <p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p>

**Survey of a Portion of the North Boundary,
T. 25 N., R. 24 E., Gila and Salt River Meridian, Arizona**

CHAINS	
81.71	<p>The cor. of Tps. 25 and 26 N., Rs. 23 and 24 E., monumented with a stainless steel post, 2 1/2 ins. diam., with brass cap, set and mkd., as described in the field notes of the survey of the east boundary, T. 25 N., R. 23 E., executed concurrently under this same group.</p> <p>Land, rolling and broken. Soil, sand and sandy clay. Timber, scattered juniper; undergrowth, greasewood, scattered brush and native grasses.</p>
o	<p align="center">Survey of the Subdivisional Lines, T.25 N., R.24 E., Gila and Salt River Meridian, Arizona</p>
	<p>From the stan. cor. of secs. 35 and 36, on the S. bdy. of the Tp., hereinbefore described.</p> <p>N. 0°02' E., bet. secs. 35 and 36.</p> <p>Over rolling land.</p>
40.00	<p>Point for the 1/4 sec. cor. of secs. 35 and 36.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p>
	<p align="center">T 25 N R 24 E 1/4 S 35 S 36 2002</p> <p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p>
80.00	<p>Point for the cor. of secs. 25, 26, 35, and 36.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p>
	<p align="center">T 25 N R 24 E S 26 S 25 S 35 S 36 2002</p> <p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p>

Survey of the Subdivisional Lines,
T. 25 N., R. 24 E., Gila and Salt River Meridian, Arizona

CHAINS	
	<p>Land, rolling. Soil, sand and sandy clay. Timber, scattered piñon and juniper; undergrowth, scattered brush and native grasses.</p> <hr/> <p>From the cor. of secs. 25, 30, 31 and 36, on the E. bdy. of the Tp., hereinbefore described.</p> <p>N. 89°54' W., bet. secs. 25 and 36.</p> <p>Over rolling and broken land.</p>
40.23	<p>Point for the 1/4 sec. cor. of secs. 25 and 36.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T 25 N R 24 E S 25 1/4 ——— S 36</p> <p style="text-align: center;">2002</p> <p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p>
80.46	<p>The cor. of secs. 25, 26, 35, and 36.</p> <p>Land, rolling and broken. Soil, sand and sandy clay. Timber, piñon and juniper; undergrowth, greasewood, scattered brush and native grasses.</p> <hr/> <p>N. 0°02' E., bet. secs. 26 and 25.</p> <p>Over rolling and broken land.</p>
14.20	<p>Big Dam Wash, 20 ft. wide, 1 ft. deep, drains NW.</p>
40.00	<p>Point for the 1/4 sec. cor. of secs. 25 and 26.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T 25 N R 24 E 1/4 S 26 S 25</p> <p style="text-align: center;">2002</p>

Survey of the Subdivisional Lines,
T. 25 N., R. 24 E., Gila and Salt River Meridian, Arizona

CHAINS									
	Deposit a magnet in a white plastic case at the base of the stainless steel post.								
56.30	High voltage transmission line, bears NE and SW.								
80.00	Point for the cor. of secs. 23, 24, 25 and 26. Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.								
	<table style="margin: auto; border-collapse: collapse;"> <tr> <td style="padding: 0 10px;">T 25 N</td> <td style="padding: 0 10px;">R 24 E</td> </tr> <tr> <td style="padding: 0 10px; border-right: 1px solid black;">S 23</td> <td style="padding: 0 10px;">S 24</td> </tr> <tr> <td style="padding: 0 10px; border-right: 1px solid black;">S 26</td> <td style="padding: 0 10px;">S 25</td> </tr> </table>	T 25 N	R 24 E	S 23	S 24	S 26	S 25		
T 25 N	R 24 E								
S 23	S 24								
S 26	S 25								
	2002								
	Deposit a magnet in a white plastic case at the base of the stainless steel post.								
	Land, rolling and broken. Soil, sand and sandy clay. Timber, piñon and juniper; undergrowth, greasewood, scattered brush and native grasses.								
	From the cor. of secs. 19, 24, 25 and 30, on the E. bdy. of the Tp., hereinbefore described.								
	N. 89°57' W., bet. secs. 24 and 25.								
	Over rolling land.								
40.26	Point for the 1/4 sec. cor. of secs. 24 and 25. Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.								
	<table style="margin: auto; border-collapse: collapse;"> <tr> <td style="padding: 0 10px;">T 25 N</td> <td style="padding: 0 10px;">R 24 E</td> </tr> <tr> <td></td> <td style="padding: 0 10px;">S 24</td> </tr> <tr> <td></td> <td style="padding: 0 10px;">1/4 ———</td> </tr> <tr> <td></td> <td style="padding: 0 10px;">S 25</td> </tr> </table>	T 25 N	R 24 E		S 24		1/4 ———		S 25
T 25 N	R 24 E								
	S 24								
	1/4 ———								
	S 25								
	2002								
	Deposit a magnet in a white plastic case at the base of the stainless steel post.								
63.00	High voltage transmission line, bears NE and SW.								
80.52	The cor. of secs. 23, 24, 25 and 26.								

Survey of the Subdivisional Lines,
T. 25 N., R. 24 E., Gila and Salt River Meridian, Arizona

CHAINS	
	<p>Land, rolling. Soil, sand and sandy clay. Timber, sparse piñon and juniper; undergrowth, scattered brush, greasewood and native grasses.</p> <hr/> <p>N. 0°02' E., bet. secs. 23 and 24.</p> <p>Over rolling land.</p>
40.00	<p>Point for the 1/4 sec. cor. of secs. 23 and 24.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T 25 N R 24 E 1/4 S 23 S 24</p> <p style="text-align: center;">2002</p> <p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p>
50.20	<p>Underground gas pipeline, bears E. and W.</p>
80.00	<p>Point for the cor. of secs. 13, 14, 23 and 24.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T 25 N R 24 E S 14 S 13 S 23 S 24</p> <p style="text-align: center;">2002</p> <p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p> <p>Land, rolling. Soil, sand sandy and clay. No timber; scattered brush and native grasses.</p> <hr/> <p>From the cor. of secs. 13, 18, 19 and 24, on the E. bdy. of the Tp., hereinbefore described.</p> <p>N. 89°54' W., bet. secs. 13 and 24.</p> <p>Over rolling and broken land.</p>
21.40	<p>High voltage transmission line, bears NE and SW.</p>

Survey of the Subdivisional Lines,
T. 25 N., R. 24 E., Gila and Salt River Meridian, Arizona

CHAINS	
40.21	<p>Point for the 1/4 sec. cor. of secs. 13 and 24.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T 25 N R 24 E S 13 1/4 ——— S 24</p> <p style="text-align: center;">2002</p> <p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p>
52.40	Navajo Route 9205, a graded road, 26 ft. wide, bears SSE and NNW.
52.80	Underground water pipeline, bears SSE and NNW.
80.42	<p>The cor. of secs. 13, 14, 23 and 24.</p> <p>Land, rolling and broken. Soil, sand and sandy clay. Timber, piñon and juniper; undergrowth scattered brush, cacti and native grasses.</p> <hr/> <p>N. 0°02' E., bet. secs. 13 and 14.</p> <p>Over rolling land.</p>
40.00	<p>Point for the 1/4 sec. cor. of secs. 13 and 14.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass</p> <p style="text-align: center;">T 25 N R 24 E 1/4 S 14 S 13</p> <p style="text-align: center;">2002</p> <p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p>
80.00	<p>Point for the cor. of secs. 11, 12, 13 and 14.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p>

Survey of the Subdivisional Lines,
T. 25 N., R. 24 E., Gila and Salt River Meridian, Arizona

CHAINS									
	<div style="text-align: center;"> <table border="1"> <tr> <td>T 25 N</td> <td>R 24 E</td> </tr> <tr> <td>S 11</td> <td>S 12</td> </tr> <tr> <td>S 14</td> <td>S 13</td> </tr> </table> <p>2002</p> <p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p> <p>Land, rolling. Soil, sand and sandy clay. No timber; scattered brush and native grasses.</p> <hr/> <p>From the cor. of secs. 7, 12, 13 and 18, on the E. bdy. of the Tp., hereinbefore described.</p> <p>N. 89°52' W., bet. secs. 12 and 13.</p> <p>Over rolling and broken land.</p> </div>	T 25 N	R 24 E	S 11	S 12	S 14	S 13		
T 25 N	R 24 E								
S 11	S 12								
S 14	S 13								
40.22	<p>Point for the 1/4 sec. cor. of secs. 12 and 13.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center;"> <table border="1"> <tr> <td>T 25 N</td> <td>R 24 E</td> </tr> <tr> <td>S 12</td> <td></td> </tr> <tr> <td>1/4</td> <td>—</td> </tr> <tr> <td>S 13</td> <td></td> </tr> </table> <p>2002</p> <p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p> </div>	T 25 N	R 24 E	S 12		1/4	—	S 13	
T 25 N	R 24 E								
S 12									
1/4	—								
S 13									
66.30	Navajo Route 9205, a graded road, 26 ft. wide, bears N. and S.								
66.80	Underground water pipeline, bears N. and S.								
80.44	<p>The cor. of secs. 11, 12, 13 and 14.</p> <p>Land, rolling. Soil, sand and sandy clay. Timber, piñon and juniper; undergrowth, greasewood, scattered brush and native grasses.</p> <hr/> <p>N. 0°02' E., bet. secs. 11 and 12.</p> <p>Over rolling land.</p>								
40.00	Point for the 1/4 sec. cor. of secs. 11 and 12.								

Survey of the Subdivisional Lines,
T. 25 N., R. 24 E., Gila and Salt River Meridian, Arizona

CHAINS	
	<p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T 25 N R 24 E 1/4 S 11 S 12 2002</p> <p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p>
65.30	Underground water pipeline, bears SSE and NNW.
66.20	Navajo Route 9205, a graded road, 26 ft. wide, bears SSE and NNW.
80.00	<p>Point for the cor. of secs. 1, 2, 11 and 12.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T 25 N R 24 E S 2 S 1 S 11 S 12 2002</p> <p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p> <p>Land, rolling. Soil, sand and sandy clay. Timber, scattered juniper; undergrowth, greasewood, scattered brush and native grasses.</p> <hr/> <p>From the cor. of secs. 1, 6, 7 and 12, on the E. bdy. of the Tp., hereinbefore described.</p> <p>N. 89°54' W., bet. secs. 1 and 12.</p> <p>Over rolling land.</p>
40.19	<p>Point for the 1/4 sec. cor. of secs. 1 and 12.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p>

Survey of the Subdivisional Lines,
T. 25 N., R. 24 E., Gila and Salt River Meridian, Arizona

CHAINS	
	T 25 N R 24 E S 1 1/4 ——— S 12 2002
	Deposit a magnet in a white plastic case at the base of the stainless steel post.
48.50	E. bank of Big Wilderness Wash, 25 ft. high, bears N. and S.
49.50	Big Wilderness Wash, 30 ft. wide, 25 ft. deep, drains N.
80.38	The cor. of secs. 1, 2, 11 and 12.
	Land, rolling. Soil, sand and sandy clay. Timber, scattered juniper; undergrowth, greasewood, scattered brush and native grasses.
	N. 0°13' E., bet. secs. 1 and 2.
	Over rolling and broken land.
26.20	Big Wilderness Wash, 20 ft. wide, 2 ft. deep, drains NW.
40.00	Point for the 1/4 sec. cor. of secs. 1 and 2.
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.
	T 25 N R 24 E 1/4 S 2 S 1 2002
	Deposit a magnet in a white plastic case at the base of the stainless steel post.
42.80	Ruins Wash, 15 ft. wide, 1 ft. deep, drains SW.
76.30	Apache County Road C414, a graded road, 25 ft. wide, bears NE and SW.
79.87	The cor. of secs. 1, 2, 35 and 36, on the N. bdy. of the Tp., hereinbefore described.

Survey of the Subdivisional Lines,
T. 25 N., R. 24 E., Gila and Salt River Meridian, Arizona

CHAINS	<p>Land, rolling and broken. Soil, sand and sandy clay. Timber, scattered juniper; undergrowth, greasewood, scattered brush and native grasses.</p> <hr/> <p>From the stan. cor. of secs. 34 and 35, on the S. bdy. of the Tp., hereinbefore described.</p> <p>N. 0°01' E., bet. secs. 34 and 35.</p> <p>Over rolling land.</p> <p>27.20 High voltage transmission line, bears NE and SW.</p> <p>40.00 Point for the 1/4 sec. cor. of secs. 34 and 35.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center;"> <p>T 25 N R 24 E 1/4 S 34 S 35</p> <p>2002</p> </div> <p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p> <p>80.00 Point for the cor. of secs. 26, 27, 34 and 35.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center;"> <p>T 25 N R 24 E S 27 S 26 S 34 S 35</p> <p>2002</p> </div> <p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p> <p>Land, rolling. Soil, sand and sandy clay. Timber, scattered juniper; undergrowth, greasewood, scattered brush and native grasses.</p> <hr/> <p>From the cor. of secs. 25, 26, 35 and 36.</p> <p>N. 89°55' W., bet. secs. 26 and 35.</p>
--------	---

Survey of the Subdivisional Lines,
T. 25 N., R. 24 E., Gila and Salt River Meridian, Arizona

CHAINS	
	Over rolling land.
40.17	Point for the 1/4 sec. cor. of secs. 26 and 35. Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd. <div style="text-align: center;"> T 25 N R 24 E S 26 1/4 ——— S 35 2002 </div>
	Deposit a magnet in a white plastic case at the base of the stainless steel post.
41.43	High voltage transmission line, bears NE and SW.
80.34	The cor. of secs. 26, 27, 34 and 35. Land, rolling. Soil, sand and sandy clay. Timber, scattered juniper; undergrowth, greasewood, scattered brush and native grasses.
	----- N. 0°01' E., bet. secs. 26 and 27. Over rolling and broken land.
20.70	Big Dam Wash, 20 ft. wide, 20 ft. deep, drains WSW, thence in the wash.
34.50	Big Dam Wash, 15 ft. wide, 20 ft. deep, on a curve, bears NE and drains SE, leave wash.
40.00	Point for the 1/4 sec. cor. of secs. 26 and 27. Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, in a collar of stone, with brass cap mkd. <div style="text-align: center;"> T 25 N R 24 E 1/4 S 27 S 26 2002 </div>
	Deposit a magnet in a white plastic case at the base of the stainless steel post.
80.00	Point for the cor. of secs. 22, 23, 26, and 27.

Survey of the Subdivisional Lines,
T. 25 N., R. 24 E., Gila and Salt River Meridian, Arizona

CHAINS									
	<p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p>								
	<table style="margin-left: auto; margin-right: auto;"> <tr> <td>T 25 N</td> <td>R 24 E</td> </tr> <tr> <td>S 22</td> <td>S 23</td> </tr> <tr> <td>S 27</td> <td>S 26</td> </tr> </table>	T 25 N	R 24 E	S 22	S 23	S 27	S 26		
T 25 N	R 24 E								
S 22	S 23								
S 27	S 26								
	<p style="text-align: center;">2002</p>								
	<p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p>								
	<p>Land, rolling and broken. Soil, sand and sandy clay. Timber, piñon and juniper; undergrowth, greasewood, scattered brush and native grasses.</p>								
	<hr/>								
	<p>From the cor. of secs. 23, 24, 25 and 26.</p>								
	<p>N. 89°55' W., bet. secs. 23 and 26.</p>								
	<p>Over rolling land.</p>								
<p>40.17</p>	<p>Point for the 1/4 sec. cor. of secs. 23 and 26.</p>								
	<p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p>								
	<table style="margin-left: auto; margin-right: auto;"> <tr> <td>T 25 N</td> <td>R 24 E</td> </tr> <tr> <td>S 23</td> <td></td> </tr> <tr> <td>1/4</td> <td>—</td> </tr> <tr> <td>S 26</td> <td></td> </tr> </table>	T 25 N	R 24 E	S 23		1/4	—	S 26	
T 25 N	R 24 E								
S 23									
1/4	—								
S 26									
	<p style="text-align: center;">2002</p>								
	<p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p>								
<p>80.34</p>	<p>The cor. of secs. 22, 23, 26 and 27.</p>								
	<p>Land, rolling. Soil, sand and sandy clay. No timber; greasewood, scattered brush and native grasses.</p>								
	<hr/>								
	<p>N. 0°01' E., bet. secs. 22 and 23.</p>								
	<p>Over rolling land.</p>								
<p>40.00</p>	<p>Point for the 1/4 sec. cor. of secs. 22 and 23.</p>								

Survey of the Subdivisional Lines,
T. 25 N., R. 24 E., Gila and Salt River Meridian, Arizona

CHAINS	
	<p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T 25 N R 24 E 1/4 S 22 S 23</p> <p style="text-align: center;">2002</p> <p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p>
53.00	Underground gas pipeline, bears E. and W.
80.00	Point for the cor. of secs. 14, 15, 22 and 23.
	<p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T 25 N R 24 E S 15 S 14 S 22 S 23</p> <p style="text-align: center;">2002</p> <p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p> <p>Land, rolling. Soil, sand and sandy clay. No timber; scattered brush and native grasses.</p> <hr/> <p>From the cor. of secs. 13, 14, 23 and 24.</p> <p>N. 89°55' W., bet. secs. 14 and 23.</p> <p>Over rolling land.</p>
40.17	<p>Point for the 1/4 sec. cor. of secs. 14 and 23.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T 25 N R 24 E S 14 1/4 ——— S 23</p> <p style="text-align: center;">2002</p> <p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p>

Survey of the Subdivisional Lines,
T. 25 N., R. 24 E., Gila and Salt River Meridian, Arizona

CHAINS	
73.45	Trail road, bears ESE and WNW.
80.34	The cor. of secs. 14, 15, 22 and 23. Land, rolling. Soil, sand and sandy clay. No timber; scattered brush and native grasses.
	N. 0°01' E., bet. secs. 14 and 15. Over rolling land.
2.80	Trail road, bears ESE and WNW.
40.00	Point for the 1/4 sec. cor. of secs. 14 and 15. Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd. <div style="text-align: center;"> T 25 N R 24 E 1/4 S 15 S 14 2002 </div>
	Deposit a magnet in a white plastic case at the base of the stainless steel post.
80.00	Point for the cor. of secs. 10, 11, 14 and 15. Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd. <div style="text-align: center;"> T 25 N R 24 E S 10 S 11 S 15 S 14 2002 </div>
	Deposit a magnet in a white plastic case at the base of the stainless steel post. Land, rolling. Soil, sand and sandy clay. Timber, sparse piñon and juniper; undergrowth, scattered brush, cacti and native grasses.
	From the cor. of secs. 11, 12, 13 and 14. N. 89°55' W., bet. secs. 11 and 14.

Survey of the Subdivisional Lines,
T. 25 N., R. 24 E., Gila and Salt River Meridian, Arizona

CHAINS	
	Over rolling and broken land.
40.17	Point for the 1/4 sec. cor. of secs. 11 and 14. Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd. <div style="text-align: center;"> T 25 N R 24 E S 11 1/4 ——— S 14 2002 </div>
	Deposit a magnet in a white plastic case at the base of the stainless steel post.
	Cor. is located 1.00 ch. W. of a wash, 20 ft. wide, 8 ft. deep, drains ENE.
80.34	The cor. of secs. 10, 11, 14 and 15. Land, rolling and broken. Soil, sand and sandy clay. Timber, scattered piñon and juniper; undergrowth, greasewood, scattered brush and native grasses.

	N. 0°01' E., bet. secs. 10 and 11.
	Over rolling and broken land.
40.00	Point for the 1/4 sec. cor. of secs. 10 and 11. Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in sandstone bedrock, with brass cap mkd. <div style="text-align: center;"> T 25 N R 24 E 1/4 S 10 S 11 2002 </div>
	Deposit a magnet in a white plastic case at the base of the stainless steel post.
55.40	S. flood bank of Pueblo Colorado Wash, 3 ft. high, bears NNE and SSW.
73.10	N. flood bank of Pueblo Colorado Wash, 2 ft. high, bears NE and SW.
80.00	Point for the cor. of secs. 2, 3, 10 and 11.

Survey of the Subdivisional Lines,
T. 25 N., R. 24 E., Gila and Salt River Meridian, Arizona

CHAINS	
	<p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T 25 N R 24 E S 3 S 2 ----- S 10 S 11</p> <p style="text-align: center;">2002</p> <p>from which</p> <p style="text-align: center;">The SW cor. of the SE extension of an L-shaped wood frame house, 32 x 32 ft., bears N. 50 1/2° W., 90 lks. dist., front side of house bears NE.</p> <p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p> <p>Land, rolling and broken. Soil, sand and sandy clay. No timber; greasewood, scattered brush and native grasses.</p> <hr/> <p>From the cor. of secs. 1, 2, 11 and 12.</p> <p>N. 89°55' W., bet. secs. 2 and 11.</p> <p>Over rolling and broken land.</p>
8.70	Navajo Route 9205, a graded road, 20 ft. wide, bears SSE and NNW.
9.20	Underground water pipeline, bears SSE and NNW.
40.17	Point for the 1/4 sec. cor. of secs. 2 and 11.
	<p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T 25 N R 24 E S 2 1/4 ——— S 11</p> <p style="text-align: center;">2002</p> <p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p>
48.60	W. rim of a mesa, bears ENE and WSW, thence descend into Pueblo Colorado Wash Valley.

Survey of the Subdivisional Lines,
T. 25 N., R. 24 E., Gila and Salt River Meridian, Arizona

CHAINS	
71.10	E. bank of Pueblo Colorado Wash, 1 ft. high, bears NNE and SSW, thence along the bed of the wash.
75.70	W. bank of Pueblo Colorado Wash, 4 ft. high, bears NNE and SSW, leave bed of wash.
80.34	The cor. of secs. 2, 3, 10 and 11. Land, rolling. Soil, sand and sandy clay. No timber; greasewood, scattered brush and native grasses.
	N. 0°01' E., bet. secs. 2 and 3. Over rolling and broken land.
9.32	Navajo Route 15, asphalt pavement, 25 ft. wide, bears NE and SW, thence ascend out of the valley.
14.60	S. rim of a mesa, bears NNE and SSW, thence over rolling land.
40.00	Point for the 1/4 sec. cor. of secs. 2 and 3. Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd. <div style="text-align: center;"> T 25 N R 24 E 1/4 S 3 S 2 2002 </div>
	Deposit a magnet in a white plastic case at the base of the stainless steel post.
79.77	Point for the closing cor. of secs. 2 and 3, at the intersection with the N. bdy. of the Tp. Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd. <div style="text-align: center;"> T 26 N R 24 E S 34 ----- S 3 S 2 T 25 N R 24 E CC 2002 </div>
	Deposit a magnet in a white plastic case at the base of the stainless steel post.

**Survey of the Subdivisional Lines,
T. 25 N., R. 24 E., Gila and Salt River Meridian, Arizona**

CHAINS	
	<p>From this cor. point, the cor. of secs. 34 and 35 only, T. 26 N., R. 24 E., bears S. 89°52' E., 52 lks. dist., hereinbefore described.</p> <hr/> <p>Point for the 1/4 sec. cor. of sec. 2 only, T. 25 N., R. 24 E., at midpoint on the N. bdy. of sec. 2.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T 26 N R 24 E <hr style="width: 10%; margin: auto;"/> 1/4 S 2 T 25 N R 24 E</p> <p style="text-align: center;">2002</p> <p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p> <p>From this cor. point, the 1/4 sec. cor. of sec. 35 only, T. 25 N., R. 24 E., bears S. 89°59' E., 26 lks. dist., hereinbefore described.</p> <hr/> <p>From the stan. cor. of secs. 33 and 34, on the S. bdy. of the Tp., hereinbefore described.</p> <p>N. 0°01' E., bet. secs. 33 and 34.</p> <p>Over rolling land.</p>
40.00	<p>Point for the 1/4 sec. cor. of secs. 33 and 34.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T 25 N R 24 E 1/4 S 33 S 34</p> <p style="text-align: center;">2002</p> <p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p>
80.00	<p>Point for the cor. of secs. 27, 28, 33 and 34.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p>

Survey of the Subdivisional Lines,
T. 25 N., R. 24 E., Gila and Salt River Meridian, Arizona

CHAINS									
	<table style="margin: auto;"> <tr> <td>T 25 N</td> <td>R 24 E</td> </tr> <tr> <td>S 28</td> <td>S 27</td> </tr> <tr> <td>S 33</td> <td>S 34</td> </tr> </table>	T 25 N	R 24 E	S 28	S 27	S 33	S 34		
T 25 N	R 24 E								
S 28	S 27								
S 33	S 34								
	2002								
	Deposit a magnet in a white plastic case at the base of the stainless steel post.								
	Land, rolling. Soil, sand and sandy clay. Timber, scattered juniper; undergrowth, greasewood, scattered brush and native grasses.								

	From the cor. of secs. 26, 27, 34 and 35. N. 89°55' W., bet. secs. 27 and 34. Over rolling and broken land.								
40.17	Point for the 1/4 sec. cor. of secs. 27 and 34. Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.								
	<table style="margin: auto;"> <tr> <td>T 25 N</td> <td>R 24 E</td> </tr> <tr> <td></td> <td>S 27</td> </tr> <tr> <td>1/4</td> <td>-----</td> </tr> <tr> <td></td> <td>S 34</td> </tr> </table>	T 25 N	R 24 E		S 27	1/4	-----		S 34
T 25 N	R 24 E								
	S 27								
1/4	-----								
	S 34								
	2002								
	Deposit a magnet in a white plastic case at the base of the stainless steel post.								
80.34	The cor. of secs. 27, 28, 33 and 34. Land, rolling and broken. Soil, sand and sandy clay. Timber, sparse piñon and juniper; undergrowth, scattered brush and native grasses.								

	N. 0°01' E., bet. secs. 27 and 28. Over rolling and broken land.								
40.00	Point for the 1/4 sec. cor. of secs. 27 and 28. Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.								

Survey of the Subdivisional Lines,
T. 25 N., R. 24 E., Gila and Salt River Meridian, Arizona

CHAINS	
	T 25 N R 24 E 1/4 S 28 S 27 2002
	Deposit a magnet in a white plastic case at the base of the stainless steel post.
60.10	S. rim of Big Dam Wash canyon, bears E. and W.
70.40	Big Dam Wash, 25 ft. wide, 5 ft. deep, drains WSW.
80.00	Point for the cor. of secs. 21, 22, 27 and 28.
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.
	T 25 N R 24 E S 21 S 22 S 28 S 27 2002
	Deposit a magnet in a white plastic case at the base of the stainless steel post.
	Land, rolling and broken. Soil, sand and sandy clay. Timber, sparse piñon and juniper; undergrowth, scattered brush, greasewood and native grasses.
	From the cor. of secs. 22, 23, 26 and 27.
	N. 89°55' W., bet. secs. 22 and 27.
	Over rolling and broken land.
33.00	E. rim of the N. fork of a narrow canyon, bears NE and SW, thence descend into rugged and broken land.
40.17	Point for the 1/4 sec. cor. of secs. 22 and 27.
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.
	T 25 N R 24 E S 22 1/4 ——— S 27 2002

Survey of the Subdivisional Lines,
T. 25 N., R. 24 E., Gila and Salt River Meridian, Arizona

CHAINS	
	Deposit a magnet in a white plastic case at the base of the stainless steel post.
75.10	E. rim of Big Dam Wash canyon, bears SSE and NNW, thence descend into the canyon.
80.34	The cor. of secs. 21, 22, 27 and 28. Land, rolling and broken. Soil, sand and sandy clay. Timber, scattered piñon and juniper; undergrowth, greasewood, scattered brush and native grasses.
	N. 0°01' E., bet. secs. 21 and 22.
	Over rolling and broken land, ascend out of the canyon.
8.50	N. rim of Big Dam Wash canyon, bears ENE and WSW.
37.00	W. rim of a mesa, bears ENE and WSW, thence descend into narrow canyon.
40.00	Point for the 1/4 sec. cor. of secs. 21 and 22. Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.
	T 25 N R 24 E 1/4 S 21 S 22 2002
	Deposit a magnet in a white plastic case at the base of the stainless steel post.
49.20	N. rim of the narrow canyon, bears E. and W., thence over rolling land.
55.30	Underground gas pipeline, bears ENE and WSW.
80.00	Point for the cor. of secs. 15, 16, 21 and 22. Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass
	T 25 N R 24 E S 16 S 15 S 21 S 22 2002

Survey of the Subdivisional Lines,
T. 25 N., R. 24 E., Gila and Salt River Meridian, Arizona

CHAINS	
	<p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p> <p>Land, rolling and broken. Soil, sand and sandy clay. Timber, sparse piñon and juniper; undergrowth, scattered brush, greasewood and native grasses.</p> <hr/> <p>From the cor. of secs. 14, 15, 22 and 23.</p> <p>N. 89°55' W., bet. secs. 15 and 22.</p> <p>Over rolling land.</p>
40.17	<p>Point for the 1/4 sec. cor. of secs. 15 and 22.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center;"> <p>T 25 N R 24 E S 15 1/4 ——— S 22</p> <p>2002</p> </div>
80.34	<p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p> <p>The cor. of secs. 15, 16, 21 and 22.</p> <p>Land, rolling. Soil, sand and sandy clay. Timber, scattered piñon and juniper; undergrowth, greasewood, scattered brush and native grasses.</p> <hr/> <p>N. 0°01' E., bet. secs. 15 and 16.</p> <p>Over rolling land.</p>
40.00	<p>Point for the 1/4 sec. cor. of secs. 15 and 16.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center;"> <p>T 25 N R 24 E 1/4 S 16 S 15</p> <p>2002</p> </div>

Survey of the Subdivisional Lines,
T. 25 N., R. 24 E., Gila and Salt River Meridian, Arizona

CHAINS									
80.00	<p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p> <p>Point for the cor. of secs. 9, 10, 15 and 16.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center;"> <table style="margin: auto;"> <tr><td>T 25 N</td><td>R 24 E</td></tr> <tr><td>S 9</td><td>S 10</td></tr> <tr><td>S 16</td><td>S 15</td></tr> </table> <p>2002</p> </div> <p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p> <p>Land, rolling and broken. Soil, sand and sandy clay. Timber, scattered piñon and juniper; undergrowth, greasewood, scattered brush and native grasses.</p> <hr/> <p>From the cor. of secs. 10, 11, 14 and 15.</p> <p>N. 89°55' W., bet. secs. 10 and 15.</p> <p>Over rolling land.</p>	T 25 N	R 24 E	S 9	S 10	S 16	S 15		
T 25 N	R 24 E								
S 9	S 10								
S 16	S 15								
40.17	<p>Point for the 1/4 sec. cor. of secs. 10 and 15.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center;"> <table style="margin: auto;"> <tr><td>T 25 N</td><td>R 24 E</td></tr> <tr><td>S 10</td><td></td></tr> <tr><td>1/4</td><td>—</td></tr> <tr><td>S 15</td><td></td></tr> </table> <p>2002</p> </div> <p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p>	T 25 N	R 24 E	S 10		1/4	—	S 15	
T 25 N	R 24 E								
S 10									
1/4	—								
S 15									
80.34	<p>The cor. of secs. 9, 10, 15 and 16.</p> <p>Land, rolling. Soil, sand and sandy clay. Timber, scattered piñon and juniper; undergrowth, greasewood, scattered brush and native grasses.</p> <hr/> <p>N. 0°01' E., bet. secs. 9 and 10.</p>								

Survey of the Subdivisional Lines,
T. 25 N., R. 24 E., Gila and Salt River Meridian, Arizona

CHAINS	
	Over rolling and broken land, across Pueblo Colorado Wash.
14.90	Pueblo Colorado Wash, 20 ft. wide, 1 ft. deep, drains WSW.
40.00	Point for the 1/4 sec. cor. of secs. 9 and 10. Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.
	T 25 N R 24 E 1/4 S 9 S 10 2002
	Deposit a magnet in a white plastic case at the base of the stainless steel post.
42.20	Power line, bears ENE and WSW.
43.56	A brass tablet, 3 ins. diam., set flush in a concrete collar, 6 ins. diam., firmly set, projecting 3 ins. above ground, bears West, 81 lks. dist., with top mkd. BIA ROADS 19, with an angle iron set nearby.
44.85	Navajo Route 15, asphalt pavement, 27 ft. wide, bears ENE and WSW.
45.80	A brass tablet, 3 ins. diam., set flush in a concrete collar, 6 ins. diam., firmly set, projecting 20 ins. above ground, bears West, 1.21 chs. dist., with top mkd. BIA ROADS 19, thence ascend out of the valley.
63.10	S. rim of a mesa, bears ESE and WNW, thence over rolling land.
80.00	Point for the cor. of secs. 3, 4, 9 and 10. Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.
	T 25 N R 24 E S 4 S 3 S 9 S 10 2002
	Deposit a magnet in a white plastic case at the base of the stainless steel post.

Survey of the Subdivisional Lines,
T. 25 N., R. 24 E., Gila and Salt River Meridian, Arizona

CHAINS	
	<p>Land, rolling and broken. Soil, sand and sandy clay. Timber, scattered juniper; undergrowth, greasewood, scattered brush and native grasses.</p> <hr/> <p>From the cor. of secs. 2, 3, 10 and 11. N. 89°55' W., bet. secs. 3 and 10. Over rolling and broken land.</p>
6.25	Barbed wire fence, 4 strands, bears NE and SW.
6.50	Power line, bears NE and SW.
8.98	Navajo Route 15, asphalt pavement, 26 ft. wide, bears NE and SW, thence ascend out of the valley.
14.56	SE rim of a mesa, bears N. and S.
21.00	E. rim of a canyon, bears NE and SW, thence across the canyon.
34.10	W. rim of the canyon, bears N. and S., thence over rolling land.
40.17	Point for the 1/4 sec. cor. of secs. 3 and 10. Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.
	<p>T 25 N R 24 E S 3 1/4 ——— S 10</p> <p>2002</p>
	Deposit a magnet in a white plastic case at the base of the stainless steel post.
80.34	The cor. of secs. 3, 4, 9 and 10. Land, rolling and broken. Soil, sand and sandy clay. No timber; greasewood, scattered brush and native grasses.
	<hr/> <p>N. 0°01' E., bet. secs. 3 and 4. Over rolling land.</p>
40.00	Point for the 1/4 sec. cor. of secs. 3 and 4.

Survey of the Subdivisional Lines,
T. 25 N., R. 24 E., Gila and Salt River Meridian, Arizona

CHAINS	
	<p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T 25 N R 24 E 1/4 S 4 S 3</p> <p style="text-align: center;">2002</p> <p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p>
79.83	<p>Point for the closing cor. of secs. 3 and 4, at the intersection with the N. bdy. of the Tp.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T 26 N R 24 E S 33 ----- S 4 S 3 T 25 N R 24 E CC</p> <p style="text-align: center;">2002</p> <p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p> <p>From this cor. point, the cor. of secs. 33 and 34 only, T. 26 N., R. 24 E., bears S. 89°52' E., 86 lks. dist., hereinbefore described.</p> <hr/> <p>Point for the 1/4 sec. cor. of sec. 3 only, T. 25 N., R. 24 E., at midpoint on the N. bdy. of sec. 3.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T 26 N R 24 E ----- 1/4 S 3 T 25 N R 24 E</p> <p style="text-align: center;">2002</p> <p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p> <p>From this cor. point, the 1/4 sec. cor. of sec. 34 only, T. 25 N., R. 24 E., bears S. 89°52' E., 69 lks. dist., hereinbefore described.</p>

**Survey of the Subdivisional Lines,
T. 25 N., R. 24 E., Gila and Salt River Meridian, Arizona**

CHAINS	
	<p>From the stan. cor. of secs. 32 and 33, on the S. bdy. of the Tp., hereinbefore described.</p> <p>North, bet. secs. 32 and 33.</p> <p>Over rolling and broken land.</p>
40.00	<p>Point for the 1/4 sec. cor. of secs. 32 and 33.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T 25 N R 24 E 1/4 S 32 S 33</p> <p style="text-align: center;">2002</p> <p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p>
80.00	<p>Point for the cor. of secs. 28, 29, 32 and 33.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T 25 N R 24 E S 29 S 28 S 32 S 33</p> <p style="text-align: center;">2002</p> <p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p> <p>Land, rolling and broken. Soil, Sand and sandy clay. Timber, scattered juniper; undergrowth, greasewood, scattered brush and native grasses.</p> <hr/> <p>From the cor. of secs. 27, 28, 33 and 34.</p> <p>N. 89°55' W., bet. secs. 28 and 33.</p> <p>Over rolling land.</p>
40.17	<p>Point for the 1/4 sec. cor. of secs. 28 and 33.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p>

Survey of the Subdivisional Lines,
T. 25 N., R. 24 E., Gila and Salt River Meridian, Arizona

CHAINS	
	T 25 N R 24 E S 28 1/4 ——— S 33 2002
	Deposit a magnet in a white plastic case at the base of the stainless steel post.
42.70	Navajo Route 28, a graded road, 25 ft. wide, bears SSE and NNW.
80.34	The cor. of secs. 28, 29, 32 and 33. Land, rolling. Soil, sand and sandy clay. Timber, scattered juniper; undergrowth, greasewood, scattered brush and native grasses.
	North, bet. secs. 28 and 29. Over rolling and broken land.
40.00	Point for the 1/4 sec. cor. of secs. 28 and 29. Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.
	T 25 N R 24 E 1/4 S 29 S 28 2002
	Deposit a magnet in a white plastic case at the base of the stainless steel post.
68.50	Navajo Route 28, a graded road, 30 ft. wide, bears ESE and W.
80.00	Point for the cor. of secs. 20, 21, 28 and 29. Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.
	T 25 N R 24 E S 20 S 21 S 29 S 28 2002
	Deposit a magnet in a white plastic case at the base of the stainless steel post.

Survey of the Subdivisional Lines,
T. 25 N., R. 24 E., Gila and Salt River Meridian, Arizona

CHAINS	
	<p>Land, rolling and broken. Soil, sand and sandy clay. Timber, scattered juniper; undergrowth, greasewood, scattered brush and native grasses.</p> <hr/> <p>From the cor. of secs. 21, 22, 27 and 28.</p> <p>N. 89°55' W., bet. secs. 21 and 28.</p> <p>Over rolling and broken land.</p>
7.30	Big Dam Wash, 20 ft. wide, 8 ft. deep, drains NW, thence ascend out of the canyon.
16.00	W. rim of Big Dam Wash canyon, bears NE and SW, thence over rolling land.
40.17	Point for the 1/4 sec. cor. of secs. 21 and 28.
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.
	<p>T 25 N R 24 E S 21 1/4 ——— S 28</p> <p>2002</p>
	Deposit a magnet in a white plastic case at the base of the stainless steel post.
80.34	The cor. of secs. 20, 21, 28 and 29.
	<p>Land, rolling and broken. Soil, sand and sandy clay. Timber, scattered juniper; undergrowth, greasewood, scattered brush and native grasses.</p> <hr/> <p>North, bet. secs. 20 and 21.</p> <p>Over rolling land.</p>
20.20	Underground gas pipeline, bears ENE and WSW.
40.00	Point for the 1/4 sec. cor. of secs. 20 and 21.
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.

Survey of the Subdivisional Lines,
T. 25 N., R. 24 E., Gila and Salt River Meridian, Arizona

CHAINS	
	<p style="text-align: center;">T 25 N R 24 E 1/4 S 20 S 21</p> <p style="text-align: center;">2002</p> <p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p>
62.50	Big Dam Wash, 20 ft. wide, 10 ft. deep, drains WNW.
80.00	Point for the cor. of secs. 16, 17, 20 and 21.
	<p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T 25 N R 24 E S 17 S 16 S 20 S 21</p> <p style="text-align: center;">2002</p> <p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p> <p>Land, rolling. Soil, sand and sandy clay. No timber; greasewood, scattered brush and native grasses.</p> <hr/> <p>From the cor. of secs. 15, 16, 21 and 22.</p> <p>N. 89°55' W., bet. secs. 16 and 21.</p> <p>Over rolling and broken.</p>
24.70	W. rim of a mesa, bears N. and S., thence descend into a valley.
40.17	Point for the 1/4 sec. cor. of secs. 16 and 21.
	<p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T 25 N R 24 E S 16 1/4 ——— S 21</p> <p style="text-align: center;">2002</p> <p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p>

Survey of the Subdivisional Lines,
T. 25 N., R. 24 E., Gila and Salt River Meridian, Arizona

CHAINS	
80.34	<p>The cor. of secs. 16, 17, 20 and 21.</p> <p>Land, rolling and broken. Soil, sand and sandy clay. Timber, scattered juniper; undergrowth, greasewood, scattered brush and native grasses.</p> <hr/> <p>North, bet. secs. 16 and 17.</p> <p>Over rolling land.</p>
40.00	<p>Point for the 1/4 sec. cor. of secs. 16 and 17.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T 25 N R 24 E 1/4 S 17 S 16</p> <p style="text-align: center;">2002</p> <p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p>
60.10	S. bank of Pueblo Colorado Wash, 4 ft. high, bears ESE and WNW.
63.90	N. Bank of Pueblo Colorado Wash, 1 ft. high, bears ENE and WSW.
80.00	<p>Point for the cor. of secs. 8, 9, 16 and 17.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T 25 N R 24 E S 8 S 9 S 17 S 16</p> <p style="text-align: center;">2002</p> <p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p> <p>Land, rolling. Soil, sand and sandy clay. No timber; greasewood, scattered brush and native grasses.</p> <hr/> <p>From the cor. of secs. 9, 10, 15 and 16.</p> <p>N. 89°55' W., bet. secs. 9 and 16.</p>

Survey of the Subdivisional Lines,
T. 25 N., R. 24 E., Gila and Salt River Meridian, Arizona

CHAINS	
	Over gently rolling land.
8.30	E. bank of Pueblo Colorado Wash, 5 ft. high, bears ENE and WSW, thence along the bed of the wash.
19.40	W. bank of Pueblo Colorado Wash, 5 ft. high, bears NNE and SSW, thence over nearly level land.
36.80	N. bank of Pueblo Colorado Wash, 2 ft. high, bears SE and NW, thence along the N. edge of the wash.
40.17	Point for the 1/4 sec. cor. of secs. 9 and 16. Set a magnet in a white plastic case, 24 ins. in the ground. from which A stainless steel post, 28 ins. long, 2 1/2 ins. diam., set 24 ins. in the ground for a reference monument, bears N. 80°00' E., 200.00 ft. dist. with brass cap mkd. RM T25N R24E S9 200.0 FT. TO COR. 2002 and an arrow pointing to the corner. Deposit a magnet in a white plastic case at the base of the stainless steel post. A stainless steel post, 28 ins. long, 2 1/2 ins. diam., set 24 ins. in the ground for a reference monument, bears N. 10°00' W., 200.00 ft. dist. with brass cap mkd. RM T25N R24E S9 200.0 FT. TO COR. 2002 and an arrow pointing to the corner. Deposit a magnet in a white plastic case at the base of the stainless steel post. Cor. is located on the N. edge of Pueblo Colorado Wash, drains WSW.
53.50	N. bank of Pueblo Colorado Wash, 4 ft. high, bears NE and SW, thence over nearly level land.
80.34	The cor. of secs. 8, 9, 16 and 17. Land, nearly level. Soil, sand and sandy clay. No timber; greasewood, scattered brush and native grasses.
	North, bet. secs. 8 and 9. Over rolling and broken land.
26.61	A brass tablet, 3 ins. diam., set flush in a concrete collar, 6 ins. diam., firmly set, projecting 3 ins. above ground, bears East, 83 lks. dist., with top mkd. BIA ROADS 19, with an angle iron set nearby.

Survey of the Subdivisional Lines,
T. 25 N., R. 24 E., Gila and Salt River Meridian, Arizona

CHAINS	
27.47	Navajo Route 15, asphalt pavement, 25 ft. wide, bears ENE and WSW, thence ascend out of the valley.
40.00	Point for the 1/4 sec. cor. of secs. 8 and 9. Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd. <div style="text-align: center;"> T 25 N R 24 E 1/4 S 8 S 9 2002 </div> Deposit a magnet in a white plastic case at the base of the stainless steel post.
73.70	S. rim of a mesa, bears ESE and WNW.
80.00	Point for the cor. of secs. 4, 5, 8 and 9. Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd. <div style="text-align: center;"> T 25 N R 24 E S 5 S 4 --- S 8 S 9 2002 </div> Deposit a magnet in a white plastic case at the base of the stainless steel post. Land, rolling and broken. Soil, sand and sandy clay. No timber; greasewood, scattered brush and native grasses.
40.17	<hr/> From the cor. of secs. 3, 4, 9 and 10. N. 89°55' W., bet. secs. 4 and 9. Over rolling and broken land, descend across a canyon. Point for the 1/4 sec. cor. of secs. 4 and 9. Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.

Survey of the Subdivisional Lines,
T. 25 N., R. 24 E., Gila and Salt River Meridian, Arizona

CHAINS	
	T 25 N R 24 E S 4 1/4 ——— S 9 2002
	Deposit a magnet in a white plastic case at the base of the stainless steel post. Cor. is located 8 lks. E. of the base of a sandstone cliff, 20 ft. high, bears NNE and SSW.
40.80	W. rim of a canyon, bears NNE and SSW, thence over rolling land.
80.34	The cor. of secs. 4, 5, 8 and 9. Land, rolling and broken. Soil, sand and sandy clay. No timber; greasewood, scattered brush and native grasses.
	—————
	North, bet. secs. 4 and 5. Over rolling land.
40.00	Point for the 1/4 sec. cor. of secs. 4 and 5. Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.
	T 25 N R 24 E 1/4 S 5 S 4 2002
	Deposit a magnet in a white plastic case at the base of the stainless steel post.
79.88	Point for the closing cor. of secs. 4 and 5, at the intersection with the N. bdy. of the Tp. Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.
	T 26 N R 24 E S 32 ——— S 5 S 4 T 25 N R 24 E CC 2002

**Survey of the Subdivisional Lines,
T. 25 N., R. 24 E., Gila and Salt River Meridian, Arizona**

CHAINS	<p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p> <p>From this cor. point, the cor. of secs. 32 and 33 only, T. 26 N., R. 24 E., bears S. 89°52' E., 1.20 chs. dist., hereinbefore described.</p> <p>Land, rolling. Soil, sand and sandy clay. No timber; greasewood, scattered brush and native grasses.</p> <hr/> <p>The point for the 1/4 sec. cor. of sec. 4 only, T. 25 N , R 24 E., at midpoint on the N. bdy. of sec. 4.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T 26 N R 24 E ----- 1/4 S 4 T 25 N R 24 E</p> <p style="text-align: center;">2002</p> <p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p> <p>From this cor. point, the 1/4 sec. cor. of sec. 33 only, T. 26 N., R. 24 E., bears S. 89°52' E., 1.03 chs. dist., hereinbefore described.</p> <hr/> <p>From the stan. cor. of secs. 31 and 32, on the S. bdy. of the Tp., hereinbefore described.</p> <p>N. 0°01' W., bet. secs. 31 and 32.</p> <p>Over rolling and broken land.</p>
40.00	<p>Point for the 1/4 sec. cor. of secs. 31 and 32.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T 25 N R 24 E 1/4 S 31 S 32</p> <p style="text-align: center;">2002</p> <p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p>

Survey of the Subdivisional Lines,
T. 25 N., R. 24 E., Gila and Salt River Meridian, Arizona

CHAINS									
80.00	<p>Point for the cor. of secs. 29, 30, 31 and 32.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center;"> <table style="margin: auto;"> <tr> <td>T 25 N</td> <td>R 24 E</td> </tr> <tr> <td>S 30</td> <td>S 29</td> </tr> <tr> <td>S 31</td> <td>S 32</td> </tr> </table> <p>2002</p> </div> <p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p> <p>Land, rolling and broken. Soil, sand and sandy clay. No timber; scattered brush and native grasses.</p> <hr/> <p>From the cor. of secs. 28, 29, 32 and 33.</p> <p>N. 89°55' W., bet. secs. 29 and 32.</p> <p>Over rolling and broken land.</p>	T 25 N	R 24 E	S 30	S 29	S 31	S 32		
T 25 N	R 24 E								
S 30	S 29								
S 31	S 32								
40.17	<p>Point for the 1/4 sec. cor. of secs. 29 and 32.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center;"> <table style="margin: auto;"> <tr> <td>T 25 N</td> <td>R 24 E</td> </tr> <tr> <td></td> <td>S 29</td> </tr> <tr> <td>1/4</td> <td>_____</td> </tr> <tr> <td></td> <td>S 32</td> </tr> </table> <p>2002</p> </div> <p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p> <p>Cor. is located 76 lks. N. of the top of a sandstone ledge, bears ENE and WSW, on the N. slope of a mesa, bears ENE and WSW.</p>	T 25 N	R 24 E		S 29	1/4	_____		S 32
T 25 N	R 24 E								
	S 29								
1/4	_____								
	S 32								
80.34	<p>The cor. of secs. 29, 30, 31 and 32.</p> <p>Land, rolling and broken. Soil, sand and sandy clay. No timber; greasewood, scattered brush and native grasses.</p> <hr/> <p>N. 89°55' W., bet. secs. 30 and 31.</p> <p>Over rolling land.</p>								

Survey of the Subdivisional Lines,
T. 25 N., R. 24 E., Gila and Salt River Meridian, Arizona

CHAINS	
7.54	Barbed wire fence, 4 strands, bears NNE and SSW.
40.00	Point for the 1/4 sec. cor. of secs. 30 and 31. Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd. <div style="text-align: center;"> T 25 N R 24 E S 30 1/4 ——— S 31 2002 </div> Deposit a magnet in a white plastic case at the base of the stainless steel post.
65.80	Navajo Route 6322, a graded road, 25 ft. wide, bears SE and NW.
80.31	The cor. of secs. 25, 30, 31 and 36, on the W. bdy. on the Tp., monumented with a stainless steel post, 2 1/2 ins. diam., with brass cap, set and mkd. as described in the field notes of the survey of the east boundary, T. 25 N., R. 23 E., executed concurrently under this same group. Land, rolling. Soil, sand and sandy clay. No timber; greasewood, scattered brush and native grasses.
	<hr/> From the cor. of secs. 29, 30, 31 and 32. N. 0°01' W., bet. secs. 29 and 30. Over rolling land.
40.00	Point for the 1/4 sec. cor. of secs. 29 and 30. Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd. <div style="text-align: center;"> T 25 N R 24 E 1/4 S 30 S 29 2002 </div> Deposit a magnet in a white plastic case at the base of the stainless steel post.
57.35	Barbed wire fence, 3 strands, bears ENE and WSW.
58.60	Navajo Route 28, a graded road, 25 ft. wide, bears ENE and WSW.

**Survey of the Subdivisional Lines,
T. 25 N., R. 24 E., Gila and Salt River Meridian, Arizona**

CHAINS									
62.80	Underground gas pipeline, bears ENE and WSW.								
80.00	Point for the cor. of secs. 19, 20, 29, and 30. Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.								
	<table style="margin-left: auto; margin-right: auto;"> <tr> <td>T 25 N</td> <td>R 24 E</td> </tr> <tr> <td>S 19</td> <td>S 20</td> </tr> <tr> <td>S 30</td> <td>S 29</td> </tr> </table>	T 25 N	R 24 E	S 19	S 20	S 30	S 29		
T 25 N	R 24 E								
S 19	S 20								
S 30	S 29								
	2002								
	Deposit a magnet in a white plastic case at the base of the stainless steel post.								
	Land, rolling. Soil, sand and sandy clay. No timber; greasewood, scattered brush and native grasses.								
	<hr/>								
	From the cor. of secs. 20, 21, 28 and 29.								
	N. 89°55' W., bet. secs. 20 and 29.								
	Over rolling land.								
28.60	Navajo Route 28, a graded road, 25 ft. wide, bears ESE and WNW.								
33.55	The same graded road, 25 ft. wide, bears ENE and WSW.								
40.17	Point for the 1/4 sec. cor. of secs. 20 and 29. Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.								
	<table style="margin-left: auto; margin-right: auto;"> <tr> <td>T 25 N</td> <td>R 24 E</td> </tr> <tr> <td></td> <td>S 20</td> </tr> <tr> <td></td> <td>1/4 ———</td> </tr> <tr> <td></td> <td>S 29</td> </tr> </table>	T 25 N	R 24 E		S 20		1/4 ———		S 29
T 25 N	R 24 E								
	S 20								
	1/4 ———								
	S 29								
	2002								
	Deposit a magnet in a white plastic case at the base of the stainless steel post.								
42.35	Underground gas pipeline, bears ENE and WSW.								
80.34	The cor. of secs. 19, 20, 29 and 30.								

Survey of the Subdivisional Lines,
T. 25 N., R. 24 E., Gila and Salt River Meridian, Arizona

CHAINS	
	<p>Land, rolling. Soil, sand and sandy clay. No timber; greasewood, scatter brush and native grasses.</p> <hr/> <p>N. 89°55' W., bet. secs. 19 and 30.</p> <p>Over rolling land.</p>
40.00	<p>Point for the 1/4 sec. cor. of secs. 19 and 30.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T 25 N R 24 E S 19 1/4 ——— S 30</p> <p style="text-align: center;">2002</p> <p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p>
78.65	<p>E. bank of Pueblo Colorado Wash, 1 1/2 ft. high, bears N. and S.</p>
80.28	<p>The cor. of secs. 19, 24, 25 and 30, on the W. bdy. of the Tp., monumented with a magnet in a white plastic case, set and witnessed as described in the field notes of the survey of the east boundary, T. 25 N., R. 23 E., executed concurrently under this same group.</p> <p>Cor. is located in Pueblo Colorado Wash, 23 lks. E. of W. bank, 1 1/2 ft. high, bears N. and S.</p> <p>Land, rolling. Soil, sand and sandy clay. No timber; greasewood, scattered brush and native grasses.</p> <hr/> <p>From the cor. of secs. 19, 20, 29 and 30.</p> <p>N. 0°01' W., bet. secs. 19 and 20.</p> <p>Over rolling land.</p>
40.00	<p>Point for the 1/4 sec. cor. of secs. 19 and 20.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p>

Survey of the Subdivisional Lines,
T. 25 N., R. 24 E., Gila and Salt River Meridian, Arizona

CHAINS	
	<p style="text-align: center;">T 25 N R 24 E 1/4 S 19 S 20</p> <p style="text-align: center;">2002</p>
80.00	<p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p> <p>Point for the cor. of secs. 17, 18, 19 and 20.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p>
	<p style="text-align: center;">T 25 N R 24 E S 18 S 17 S 19 S 20</p> <p style="text-align: center;">2002</p> <p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p> <p>Land, rolling. Soil, sand and sandy clay. No timber; greasewood, scattered brush and native grasses.</p>
	<hr/> <p>From the cor. of secs. 16, 17, 20 and 21.</p> <p>N. 89°55' W., bet. secs. 17 and 20.</p> <p>Over rolling land.</p>
40.17	<p>Point for the 1/4 sec. cor. of secs. 17 and 20.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p>
	<p style="text-align: center;">T 25 N R 24 E S 17 1/4 ——— S 20</p> <p style="text-align: center;">2002</p> <p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p>
41.40	<p>Big Dam Wash, 15 ft. wide, 2 ft. deep, drains NW.</p>
80.34	<p>The cor. of secs. 17, 18, 19 and 20.</p>

Survey of the Subdivisional Lines,
T. 25 N., R. 24 E., Gila and Salt River Meridian, Arizona

CHAINS	
	<p>Land, rolling. Soil, sand and sandy clay. No timber; greasewood, scattered brush and native grasses.</p> <hr/> <p>N. 89°55' W., bet. secs. 18 and 19.</p> <p>Over rolling land.</p>
40.00	<p>Point for the 1/4 sec. cor. of secs. 18 and 19.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T 25 N R 24 E S 18 1/4 ——— S 19</p> <p style="text-align: center;">2002</p> <p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p>
51.30	Pueblo Colorado Wash, 60 ft. wide, 2 ft. deep, drains SW.
68.85	Navajo Route 15, asphalt pavement, 26 ft. wide, bears ENE and WSW.
80.26	The cor. of secs. 13, 18, 19 and 24, on the W. bdy. of the Tp., monumented with a stainless steel post, 2 1/2 ins. diam., with brass cap, set and mkd. as described in the field notes of the survey of the east boundary, T. 25 N., R. 23 E., executed concurrently under this same group.
	<p>Land, rolling. Soil, sand and sandy clay. No timber; greasewood, scattered brush and native grasses.</p> <hr/> <p>From the cor. of secs. 17, 18, 19 and 20.</p> <p>N. 0°01' W., bet. secs. 17 and 18.</p> <p>Over rolling land.</p>
40.00	<p>Point for the 1/4 sec. cor. of secs. 17 and 18.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p>

Survey of the Subdivisional Lines,
T. 25 N., R. 24 E., Gila and Salt River Meridian, Arizona

CHAINS	
	T 25 N R 24 E 1/4 S 18 S 17 2002
	Deposit a magnet in a white plastic case at the base of the stainless steel post. Cor. is located in an area of drifting sand. Set a steel fence post nearby.
45.80	Pueblo Colorado Wash, 70 ft. wide, 1 ft. deep, drains WSW.
65.58	Navajo Route 15, asphalt pavement, 26 ft. wide, bears ENE and WSW.
80.00	Point for the cor. of secs. 7, 8, 17 and 18. Set a magnet in a white plastic case, 24 ins. in the ground. From which A stainless steel post, 28 ins. long, 2 1/2 ins. diam., set 24 ins. in the ground for a reference monument, bears N. 45°00' E., 30.00 ft. dist., with brass cap mkd. RM T25N R24E S8 30.0 FT. TO COR. 2002 and an arrow pointing to the corner. Deposit a magnet in a white plastic case at the base of the stainless steel post. A stainless steel post, 28 ins. long, 2 1/2 ins. diam., set 24 ins. in the ground for a reference monument, bears S. 45°00' W., 30.00 ft. dist., with brass cap mkd. RM T25N R24E S18 30.0 FT. TO COR. 2002 and an arrow pointing to the corner. Deposit a magnet in a white plastic case at the base of the stainless steel post. Cor. is located in the center of a wash, 10 ft. wide, 2 ft. deep, drains SSW. Land, rolling. Soil, sand and sandy clay. No timber; greasewood, scattered brush and native grasses.
	<hr/> From the cor. of secs. 8, 9, 16 and 17. N. 89°55' W., bet. secs. 8 and 17. Over rolling land.
36.17	Power line, bears ENE and WSW.

Survey of the Subdivisional Lines,
T. 25 N., R. 24 E., Gila and Salt River Meridian, Arizona

CHAINS	
40.17	<p>Point for the 1/4 sec. cor. of secs. 8 and 17.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T 25 N R 24 E S 8 1/4 ——— S 17</p> <p style="text-align: center;">2002</p> <p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p> <p>From this cor. point, a third order U. S. Geological Survey bench mark, bears N. 12°22' W., 4.165 chs. dist., monumented with an aluminum tablet, 3 1/2 diam., set flush in a concrete collar, 6 ins. square, firmly set, projecting 4 ins. above ground, with top mkd. U.S. GEOLOGICAL SURVEY EL. 6020, 33 MPS 1972.</p>
52.61	Navajo Route 15, asphalt pavement, 26 ft. wide, bears ENE and WSW.
80.34	<p>The cor. of secs. 7, 8, 17 and 18.</p> <p>Land, rolling. Soil, sand and sandy clay. No timber; greasewood, scattered brush and native grasses.</p> <hr/> <p>N. 89°55' W., bet. secs. 7 and 18.</p> <p>Over rolling and broken land, ascend out of the valley.</p>
17.60	S. rim of a mesa, 120 ft. high, bears NNE and SSW, thence over rolling land.
40.00	<p>Point for the 1/4 sec. cor. of secs. 7 and 18.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd</p> <p style="text-align: center;">T 25 N R 24 E S 7 1/4 ——— S 18</p> <p style="text-align: center;">2002</p> <p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p>

**Survey of the Subdivisional Lines,
T. 25 N., R. 24 E., Gila and Salt River Meridian, Arizona**

CHAINS	
51.30	W. rim of a mesa, 80 ft. high, bears NE and SW, thence descend into a valley.
61.50	Navajo Route 152, a graded road, 15 ft. wide, bears NNE and SSW.
80.23	The cor. of secs. 7, 12, 13 and 18, on the W. bdy. of the Tp., monumented with a stainless steel post, 2 1/2 ins. diam., with brass cap, set and mkd. as described in the field notes of the survey of the east boundary, T. 25 N., R. 23 E., executed concurrently under this same group. Land, rolling and broken. Soil, sand and sandy clay. Timber, scattered juniper; undergrowth, greasewood, scattered brush and native grasses.
	From the cor. of secs. 7, 8, 17 and 18. N. 0°01' W., bet. secs. 7 and 8. Over rolling and broken land, ascend out of the valley.
10.90	S. rim of a mesa, 110 ft. high, bears ENE and WSW.
40.00	Point for the 1/4 sec. cor. of secs. 7 and 8. Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd. <div style="text-align: center;"> T 25 N R 24 E 1/4 S 7 S 8 2002 </div>
	Deposit a magnet in a white plastic case at the base of the stainless steel post.
77.10	Descend the N. slope of a sandy ridge, bears NE and SE.
80.00	Point for the cor. of secs. 5, 6, 7 and 8. Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd. <div style="text-align: center;"> T 25 N R 24 E S 6 S 5 S 7 S 8 2002 </div>

Survey of the Subdivisional Lines,
T. 25 N., R. 24 E., Gila and Salt River Meridian, Arizona

CHAINS	
	<p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p> <p>Cor. is located 4 1/2 lks. W. of a sandstone ledge, 2 ft. high, bears NE and SW.</p> <p>Land, rolling and broken. Soil, sand and sandy clay. Timber, scattered piñon and juniper; undergrowth, scattered brush and native grasses.</p> <hr/> <p>From the cor. of secs. 4, 5, 8 and 9.</p> <p>N. 89°55' W., bet. secs. 5 and 8.</p> <p>Over rolling land.</p>
40.17	<p>Point for the 1/4 sec. cor. of secs. 5 and 8.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center;"> <p>T 25 N R 24 E</p> <p>S 5</p> <p>1/4 ———</p> <p>S 8</p> <p>2002</p> </div>
80.34	<p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p> <p>Thence descend the W. slope of sandy ridge, bears ENE and WSW.</p> <p>The cor. of secs. 5, 6, 7 and 8.</p> <p>Land, rolling and broken. Soil, sand and sandy clay. Timber, scattered piñon and juniper; undergrowth, scattered brush and native grasses</p> <hr/> <p>N. 89°55' W., bet. secs. 6 and 7.</p> <p>Over rolling land.</p>
40.00	<p>Point for the 1/4 sec. cor. of secs. 6 and 7.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p>

Survey of the Subdivisional Lines,
T. 25 N., R. 24 E., Gila and Salt River Meridian, Arizona

CHAINS	
	T 25 N R 24 E S 6 1/4 ——— S 7 2002
	Deposit a magnet in a white plastic case at the base of the stainless steel post.
80.20	The cor. of secs. 1, 6, 7 and 12, on the W. bdy of the Tp., monumented with a stainless steel post, 2 1/2 ins. diam., with brass cap, set and mkd. as described in the field notes of the survey of the east boundary, T. 25 N., R. 23 E., executed concurrently under this same group. Cor. is located 1.45 chs. N. of the top of a rock ledge, 5 ft. high, bears ENE and WSW and halfway up the S. slope of a mesa. Land, rolling. Soil, sand and sandy clay. Timber, scattered piñon and juniper; undergrowth, greasewood, scattered brush and native grasses.
	From the cor. of secs. 5, 6, 7 and 8. N. 0°01' W., bet. secs. 5 and 6. Over rolling land.
38.00	Trail road, bears ESE and WNW.
40.00	Point for the 1/4 sec. cor. of secs. 5 and 6. Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.
	T 25 N R 24 E 1/4 S 6 S 5 2002
	Deposit a magnet in a white plastic case at the base of the stainless steel post.
79.94	Point for the closing cor. of secs. 5 and 6, at the intersection with the N. bdy. of the Tp. Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.

Survey of the Subdivisional Lines,
T. 25 N., R. 24 E., Gila and Salt River Meridian, Arizona

CHAINS

T 26 N R 24 E
 S 31

 S 6 | S 5
 T 25 N R 24 E
 CC

2002

Deposit a magnet in a white plastic case at the base of the stainless steel post.

From this cor. point, the cor. of secs. 31 and 32 only, T. 26 N., R. 24 E., bears S. 89°52' E., 1.54 chs. dist., hereinbefore described.

The point for the 1/4 sec. cor. of sec. 5 only, T. 25 N., R. 24 E., at midpoint on the N. bdy. of sec. 5.

Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.

T 26 N R 24 E

 1/4 S 5
 T 25 N R 24 E

2002

Deposit a magnet in a white plastic case at the base of the stainless steel post.

From this cor. point, the 1/4 sec. cor. of sec. 32 only, T. 26 E., R. 24 E., bears S. 89°52' E., 1.37 chs. dist., hereinbefore described.

Point for the 1/4 sec. cor. of sec. 6 only, T. 25 N., R. 24 E., at 40.00 chs. in westing from the closing cor. of secs. 5 and 6, on the N. bdy. of sec. 6.

Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.

T 26 N R 24 E

 1/4 S 6
 T 25 N R 24 E

2002

Deposit a magnet in a white plastic case at the base of the stainless steel post.

Survey of the Subdivisional Lines,
T. 25 N., R. 24 E., Gila and Salt River Meridian, Arizona

CHAINS

From this cor. point, the 1/4 sec. cor. of sec. 31 only,
T. 26 N., R. 24 E., bears S. 89°52' E., 1.54 chs. dist.,
hereinbefore described.

Land, rolling.

Soil, sand and sandy clay.

No timber; greasewood, scattered brush and native grasses.

T. 25 N., R. 24 E., Gila and Salt River Meridian, Arizona

CHAINS	<p data-bbox="776 306 1078 331" style="text-align: center;">GENERAL DESCRIPTION</p> <hr/> <p data-bbox="404 401 1446 758">The area surveyed is within the Navajo Indian Reservation, approximately four miles northeast of the community of Greasewood, Arizona. The community of Sunrise Springs is located in the northeastern portion of the township. The terrain is low rolling and broken mesas in the southeastern and the northwestern portions of the township, with Pueblo Colorado Wash Valley, extends through the center from the northeast to southwest and is the principal drainage. Big Dam Wash, which enters the township in section 25 and drains northwesterly into the Pueblo Colorado Wash. Big Wilderness Wash which enters the township in section 12, drains northerly into Pueblo Colorado Wash.</p> <p data-bbox="404 791 1446 1031">The elevation varies from 5900 to 6500 feet above sea level. The soil is sand and sandy clay. There is a moderate growth of piñon and juniper trees in the higher elevation of the township mainly in the east and in a portion of the north central area of the township. Cottonwood, Russian olive, and salt cedar are found along the flood plains of Pueblo Colorado Wash. Undergrowth principally consists of sagebrush, greasewood, rabbit brush, cacti, and native grasses.</p> <p data-bbox="404 1064 1446 1272">Principal access to the township is provided by Navajo Route 15, which enters the township in section 2 and extends southwesterly and exits in sections 19. There are several major graded roads and numerous trail roads throughout the township. Much of this area is used for the grazing of livestock. There are numerous permanent home sites through out the township. There is no mining activity in this township.</p> <p data-bbox="404 1306 1446 1394">The mean magnetic declination of $11 \frac{1}{2}^{\circ}$ E. was derived from the computer program GEOMAGIX, utilizing the World Magnetic Model for Epoch 2000 for the dates of survey.</p> <hr/>
--------	---

**UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT**

FIELD ASSISTANTS

NAMES	CAPACITY
William F. Olver	Cadastral Surveyor
Daniel Bryan	Engineering Technician
Wilfred Chee	Engineering Technician
Edward Clark	Engineering Technician
Reuben Mason	Engineering Technician
Barney Woodie	Engineering Technician

CERTIFICATE OF SURVEY

I, Jones Curtiss, Cadastral Surveyor, HEREBY CERTIFY upon honor, that in pursuance of special instructions bearing date of the 22nd day of January, 2001, I have dependently resurveyed the Sixth Standard Parallel North (south boundary), the Sixth Guide Meridian East (east boundary), and a portion of the north boundary and the survey of a portion of the north boundary, and the subdivisional lines, T. 25 N., R. 24 E., of the Gila and Salt River Meridian, in the State of Arizona, which are represented in the foregoing field notes as having been executed by me and under my direction. Said survey has been made in strict conformity with said special instructions, the Manual of Instructions for the Survey of the Public Lands of the United States, 1973, and in specific manner described in the foregoing field notes.

October 21, 2004
(Date)

Jones Curtiss
(Cadastral Surveyor)

CERTIFICATE OF APPROVAL

BUREAU OF LAND MANAGEMENT
Phoenix, Arizona

The foregoing field notes of the dependent resurvey of the Sixth Standard Parallel North (south boundary), the Sixth Guide Meridian East (east boundary), and a portion of the north boundary and the survey of a portion of the north boundary, and the subdivisional lines, T. 25 N., R. 24 E., Gila and Salt River Meridian, in the State of Arizona, executed by Jones Curtiss, Cadastral Surveyor, having been critically examined and found correct, are hereby approved.

11/12/04
(Date)

Stephen K. Hansen
(Acting Chief Cadastral Surveyor of Arizona)

~~CERTIFICATE OF TRANSCRIPT~~

~~I CERTIFY That the foregoing transcript of the field notes of the above described surveys in T. 25 N., R. 24 E., Gila and Salt River Meridian, Arizona, is a true copy of the original field notes.~~

~~_____
(Date)~~

~~_____
(Acting Chief Cadastral Surveyor of Arizona)~~