

ORIGINAL

**UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT**

FIELD NOTES

OF THE

DEPENDENT RESURVEY OF THE
EAST, SOUTH AND WEST BOUNDARIES

AND

THE SUBDIVISIONAL LINES

AND

A PORTION OF THE BOUNDARY,
MANAGEMENT DISTRICT No. 6, HOPI INDIAN RESERVATION

TOWNSHIP 26 NORTH, RANGE 15 EAST,
OF THE GILA AND SALT RIVER MERIDIAN,
IN THE STATE OF ARIZONA.

EXECUTED BY

Adrien J. Rodriguez, Cadastral Surveyor

Under Special Instructions dated July 16, 2002, approved July 16, 2002,
which provided for the surveys included under Group No. 892, and
assignment instructions dated July 16, 2002.

Survey commenced July 29, 2002

Survey completed September 25, 2002

INDEX DIAGRAM

TOWNSHIP 26 NORTH RANGE 15 EAST

15	6	52	5	43	4	35	3	28	2	22	1	11
	52		51		43		34		28		21	
14	7	51	8	42	9	33	10	27	11	20	12	10
	50		50		41		33		27		20	
14	18	49	17	40	16	32	15	26	14	19	13	10
	48		48		40		32		25		19	
13	19	47	20	39	21	31	22	25	23	18	24	9
	47		46		38		30		24		18	
12	30	46	29	37	28	30	27	24	26	17	25	9
	45		45		37		29		23		16	
12	31	44	32	36	33	29	34	22	35	15	36	8
	7		7		6		5		5		4	

T. 26 N., R. 15 E., Gila and Salt River Meridian, Arizona

CHAINS

The following field notes describe the dependent resurvey of the east, south and west boundaries, the subdivisional lines and a portion of the Boundary, Management District No. 6, Hopi Indian Reservation in Township 26 North, Range 15 East, Gila and Salt River Meridian, Arizona.

The history of surveys pertaining to this resurvey is as follows:

L. D. Chillson surveyed a portion of the north boundary in 1891. Sidney E. Blout resurveyed portions of the north boundary and surveyed the north, east, south, west boundary and the subdivisional lines in 1908-1909. Leonard W. Murphy and Wallace R. Ott surveyed the boundary of Management District No. 6, Hopi Indian Reservation in 1963-1964.

The survey was executed in accordance with the specifications as set forth in the Manual of Instructions for the Survey of the Public Lands of the United States, 1973, and the Special Instructions dated July 16, 2002, for Group No. 892, Arizona.

The true meridian direction and length of all lines were determined by real time kinematic global positioning system observations using Trimble Navigation 4400 model receivers.

Preliminary to the resurvey, the lines of the prior surveys were retraced and search was made for all corners and other calls of record. Identified corners were remonumented in their original positions. Lost corners were reestablished and remonumented at proportionate positions based on the official record. The retracement data were thoroughly verified and only the true line field notes are given herein.

Geodetic control was derived from first order U. S. Geological Survey triangulation station W 70, as published by the National Geodetic Survey, NAD 83 (1992). The geographic position of the southeast corner of the township, is as follows:

Latitude: 35° 36' 24.20" N. Longitude: 110° 40' 42.88" W.

The mean magnetic declination is 12° E.

**Dependent Resurvey of the South Boundary,
T. 26 N., R. 15 E., Gila and Salt River Meridian, Arizona**

CHAINS	
	<p>Restoring the survey executed by Sidney E. Blout, in 1908-1909</p> <hr/>
	<p>Beginning at the point for the cor. of Tps. 25 and 26 N., Rs. 15 and 16 E., at proportionate dist.; the original iron post, 3 ins. diam., 48 ins. long, with the brass cap mkd. T26N R15E R16E S36 S31 S1 S6 T25N, was found lying loose on its side nearby.</p> <p>Set original iron post, 36 ins. in the ground and set a steel fence post 3 ft. N. of cor. Add the marks 2002 to the brass cap. Deposit a magnet in a white plastic case at the base of the iron post.</p> <p>From this point the sec. cor. of secs. 5, 6, 31 and 32, of Tps. 25 N. and 26 N., Rg. 16 E., bears S. 89°48' E., 80.31 chs. dist., monumented with an iron post, 3 ins. diam., firmly set, projecting 17 ins. above ground, with brass cap mkd. T26N R16E T25N S31 S32 S6 S5. Add the marks 2002 to the brass cap. Set a steel fence post 3 ft. N. of cor.</p> <p>From the same point, the 1/4 sec. cor. of secs. 1 and 6, of Tp. 25 N., Rs. 15 E. and 16 E., bears south, 40.02 chs. dist., monumented with an iron post, 1 in. diam., firmly set, projecting 6 ins. above ground, with brass cap mkd. S1 1/4 S6 1908. Add the marks T25N R15E R16E 2002 to the brass cap. Set a steel fence post 3 ft. N. of cor.</p> <p>N. 89°55' W., bet. secs. 1 and 36.</p> <p>Over rolling sandy land covered with scattered grasses.</p>
40.03	<p>The 1/4 sec. cor. of secs. 1 and 36, monumented with an iron post, 1 in. diam., firmly set, projecting 8 ins. above ground, with brass cap mkd. S36 1/4 S1.</p> <p>Add the marks T25N T26N R15E 2002 to the brass cap.</p> <p>Set a steel fence post 3 ft. N. of cor.</p> <p>Drove iron post into ground, now projects 3 ins. above ground.</p> <hr/> <p>N. 89°52' W., beginning new measurement.</p>
40.01	<p>The cor. of secs. 1, 2, 35 and 36, monumented with an iron post, 3 ins. diam., firmly set projecting 10 ins. above ground, with brass cap mkd. R15E T26N T25N S36 S1 S35 S2.</p> <p>Add the marks 2002 to the brass cap.</p>

**Dependent Resurvey of the South Boundary,
T. 26 N., R. 15 E., Gila and Salt River Meridian, Arizona**

CHAINS	
	<p>Set a steel fence post 3 ft. N. of cor.</p> <hr/> <p>N. 89°50' W., bet. secs. 2 and 35.</p> <p>Over rolling sandy land covered with scattered grasses.</p>
40.03	<p>The 1/4 sec. cor. of secs. 2 and 35, monumented with an iron post, 1 in. diam., firmly set, projecting 9 ins. above ground, with brass cap mkd. S35 1/4 S2.</p> <p>Add the marks T25N T26N R15E 2002 to the brass cap.</p> <p>Set a steel fence post 3 ft. N. of cor.</p> <hr/> <p>N. 89°56' W., beginning new measurement.</p>
16.68	<p>Point for crossing closing cor. bet. secs. 2 and 35, at intersection with the boundary of Management District No. 6, Hopi Indian Reservation, hereinafter described.</p>
40.03	<p>The cor. of secs. 2, 3, 34 and 35, monumented with an iron post, 3 ins. diam., firmly set, 6 ins. below ground, with brass cap mkd. R15E T26N T25N S35 S2 S34 S3.</p> <p>Raised iron post in same position, now projects 8 ins. above ground.</p> <p>Add the marks 2002 to the brass cap.</p> <p>Deposit a magnet in a white plastic case at the base of the iron post and set a steel fence post 3 ft. N. of cor.</p> <hr/> <p>N. 89°51' W., bet. secs. 3 and 34.</p> <p>Over rolling sandy land covered with scattered grasses.</p>
40.04	<p>The 1/4 sec. cor. of secs. 3 and 34, monumented with an iron post, 1 in. diam., loosely set, projecting 11 ins. above ground, badly rusted, with brass cap mkd. S34 1/4 S3.</p> <p>At the corner point</p> <p>Set a stainless steel post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.</p>

**Dependent Resurvey of the South Boundary,
T. 26 N., R. 15 E., Gila and Salt River Meridian, Arizona**

CHAINS	
	T26N R15E S34 1/4 ——— S3 T25N 2002
	<p>Deposit a magnet in a white plastic case at the base of the stainless steel post and place the iron post inside it.</p> <hr/> <p>N. 89°56' W., beginning new measurement.</p>
40.03	<p>The cor. of secs. 3, 4, 33 and 34, monumented with an iron post, 3 ins. diam., firmly set, projecting 11 ins. above ground, with brass cap mkd. R15E T26N T25N S34 S3 S33 S4.</p> <p>Add the marks 2002 to the brass cap.</p> <hr/>
	<p>N. 89°54' W., bet. secs. 4 and 33.</p> <p>Over rolling sandy land covered with scattered grasses.</p>
39.99	<p>Point for the 1/4 sec. cor. of secs. 4 and 33, at proportionate dist.; there is no remaining evidence of the original cor.</p> <p>True point falls in a wash, 20 ft. wide, 20 ft. deep, drains S. 30° W., where it is impracticable to establish a permanent monument.</p> <p>From this point, point selected for the witness 1/4 sec. cor. of secs. 4 and 33 bears N. 34°59' E., 2.00 chs. dist.</p> <p>At the witness point set a stainless steel post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">WC T26N R15E S33 1/4 ——— S4 T25N 2002</p> <p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p> <p>Set a steel fence post 3 ft. N. of cor.</p>

**Dependent Resurvey of the South Boundary,
T. 26 N., R. 15 E., Gila and Salt River Meridian, Arizona**

CHAINS	
79.98	<p>The cor. of secs. 4, 5, 32 and 33, monumented with an iron post, 3 ins. diam., firmly set, flush with the ground, with brass cap mkd. R15E T26N T25N S33 S4 S32 S5.</p> <p>Add the marks 2002 to the brass cap.</p> <p>Set a steel fence post 3 ft. N. of cor.</p> <hr/> <p>S. 89°56' W., bet. secs. 5 and 32.</p> <p>Over rolling sandy land covered with scattered grasses.</p>
40.04	<p>The 1/4 sec. cor. of secs. 5 and 32, monumented with an iron post, 1 in. diam., firmly set, 4 ins. below ground, badly rusted, with brass cap mkd. S32 1/4 S5.</p> <p>At the corner point</p> <p>Set a stainless steel post, 28 ins. long, 2½ ins. diam., 22 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center; margin: 10px 0;"> <p>T26N R15E</p> <p>S32</p> <p>1/4 ———</p> <p>S5</p> <p>T25N</p> <p>2002</p> </div> <p>Deposit a magnet in a white plastic case at the base of the stainless steel post and place the iron post inside of it.</p> <hr style="width: 20%; margin: 10px auto;"/> <p>N. 89°57' W., beginning new measurement.</p>
39.99	<p>The cor. of secs. 5, 6, 31 and 32, monumented with an iron post, 3 ins. diam., loosely set, projecting 21 ins. above ground, with brass cap mkd. R15E T26N T25N S32 S5 S31 S6.</p> <p>Add the marks 2002 to the brass cap.</p> <p>Reset iron post in same position, now projects 12 ins. above ground.</p> <p>Deposit a magnet in a white plastic case at the base of the iron post.</p> <hr/> <p>N. 89°56' W., bet. secs. 6 and 31.</p>

**Dependent Resurvey of the South Boundary,
T. 26 N., R. 15 E., Gila and Salt River Meridian, Arizona**

CHAINS	
	Over level sandy land covered with scattered grasses.
1.40	Left bank of Oraibi Wash, bears N. 10' E. and S. 20' W.
40.02	The 1/4 sec. cor. of secs. 6 and 31, monumented with an iron post, 1 in. diam., firmly set, projecting 1 in. above ground, with brass cap mkd. S31 1/4 S6.
	Add the marks T25N T26N R15E 2002 to the brass cap.

	N. 89°57' W., beginning new measurement.
37.85	Center line of Highway 87, 30 ft. wide, bears N. 49° E. and S. 49° W.
40.79	The cor. of Tps. 25 and 26 N., Rs. 14 and 15 E., monumented with an iron post, 3 ins. diam., firmly set, projecting 11 ins. above ground, with brass cap mkd. T26N R14E R15E S36 S31 S1 S6 T25N.
	Add the marks 2002 to the brass cap.
	Set a steel fence post 3 ft. N. of cor.
	Cor. is located 55 lks. W. of a 5 strand barbed wire fence, bears N. 50° E. and S. 50° W.

	Dependent Resurvey of the East Boundary, T. 26 N., R. 15 E., Gila and Salt River Meridian, Arizona

	Restoring the survey executed by Sidney E. Blout, in 1908-1909

	From the cor. of Tps. 25 and 26 N., Rs. 15 and 16 E, hereinbefore described.
	N. 0°01' W., bet. secs. 31 and 36.
	Over rolling sandy land covered with scattered grasses.
40.02	The 1/4 sec. cor. of secs. 31 and 36, monumented with an iron post, 1 in. diam., firmly set, projecting 12 ins. above ground, with brass cap mkd. S36 1/4 S31 1908.
	Add the marks T26N R15E R16E 2002 to the brass cap.
	Set a steel fence post 3 ft. N. of cor.

**Dependent Resurvey of the East Boundary,
T. 26 N., R. 15 E., Gila and Salt River Meridian, Arizona**

CHAINS	
40.00	<p>N. 0°01' W., beginning new measurement.</p> <p>The cor. of secs. 25, 30, 31 and 36, monumented with an iron post, 3 ins. diam., firmly set, projecting 15 ins. above ground, with brass cap mkd. T26N R15E R16E S25 S30 S36 S31.</p> <p>Add the marks 2002 to the brass cap.</p> <p>Set a steel fence post 3 ft. N. of cor.</p> <hr/>
40.00	<p>N. 0°03' W., bet. secs. 25 and 30.</p> <p>Over rolling sandy land covered with scattered grasses.</p> <p>The 1/4 sec. cor. of secs. 25 and 30, monumented with an iron post, 1 in. diam., firmly set, projecting 1 in. above ground, with brass cap mkd. S25 1/4 S30 1908.</p> <p>Add the marks T26N R15E R16E 2002 to the brass cap.</p> <p>Set a steel fence post 3 ft. N. of cor.</p> <hr/>
40.01	<p>N. 0°03' W., beginning new measurement.</p> <p>The cor. of secs. 19, 24, 25 and 30, monumented with an iron post, 3 ins. diam., firmly set, projecting 20 ins. above ground, with brass cap mkd. T26N R15E R16E S25 S30 S36 S31.</p> <p>Add the marks 2002 to the brass cap.</p> <p>Set a steel fence post 3 ft. N. of cor.</p> <hr/>
40.00	<p>N. 0°03' W., bet. secs. 19 and 24.</p> <p>Over rolling sandy land covered with scattered grasses.</p> <p>The 1/4 sec. cor. of secs. 19 and 24, monumented with an iron post, 1 in. diam., firmly set, projecting 6 ins. above ground, with brass cap mkd. S24 1/4 S19 1908.</p> <p>Add the marks T26N R15E R16E 2002 to the brass cap.</p> <p>Set a steel fence post 3 ft. N. of cor.</p> <hr/>
	<p>N. 0°03' W., beginning new measurement.</p>

**Dependent Resurvey of the East Boundary,
T. 26 N., R. 15 E., Gila and Salt River Meridian, Arizona**

CHAINS	
39.99	<p>The cor. of secs. 13, 18, 19 and 24, monumented with an iron post, 3 ins. diam., firmly set, projecting 15 ins. above ground, with brass cap mkd. T26N R15E R16E S13 S18 S24 S19.</p> <p>Add the marks 2002 to the brass cap.</p> <p>Set a steel fence post 3 ft. N. of cor.</p> <hr/> <p>N. 0°02' W., bet. secs. 13 and 18.</p> <p>Over rolling sandy land covered with scattered grasses.</p>
40.02	<p>Point for the 1/4 sec. cor. of secs. 13 and 18, at proportionate dist.; there is no remaining evidence of the original cor.</p> <p>Set a stainless steel post, 28 ins. long, 2½ ins. diam., 26 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center; margin: 10px 0;"> <p>T26N R15E R16E 1/4 S13 S18 2002</p> </div> <p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p> <p>Set a steel fence post 3 ft. N. of cor.</p>
80.04	<p>The cor. of secs. 7, 12, 13 and 18, monumented with an iron post, 3 ins. diam., firmly set, projecting 21 ins. above ground, with brass cap mkd. T26N R15E R16E S12 S7 S13 S18.</p> <p>Add the marks 2002 to the brass cap.</p> <p>Set a steel fence post 3 ft. N. of cor.</p> <hr/> <p>N. 0°02' W., bet. secs. 7 and 12.</p> <p>Over rolling sandy land covered with scattered grasses.</p>
40.02	<p>Point for the 1/4 sec. cor. of secs. 7 and 12, at proportionate dist.; there is no remaining evidence of the original cor.</p> <p>Set a brass tablet, 3 1/4 ins. diam., 3 1/2 in. stem, in drill hole in a sandstone rock outcrop with top mkd.</p>

**Dependent Resurvey of the East Boundary,
T. 26 N., R. 15 E., Gila and Salt River Meridian, Arizona**

CHAINS	
	T26N R15E R16E 1/4 S12 S7 2002
	Deposit a magnet at the base of the drill hole. Cor. falls on sandstone rock outcrop, 100 x 100 x 50 ft. high, bears N. 20° E. and S. 20 ° W.
80.04	The cor. of secs. 1, 6, 7 and 12, monumented with an iron post, 3 ins. diam., firmly set, projecting 15 ins. above ground, with brass cap mkd. T26N R15E R16E S1 S6 S12 S7. Add the marks 2002 to the brass cap. Set a steel fence post 3 ft. N. of cor.
	<hr/> N. 0°02' W., bet. secs. 1 and 6. Over rolling sandy land covered with scattered grasses.
40.03	The 1/4 sec. cor. of secs. 1 and 6, monumented with an iron post, 1 in. diam., firmly set, projecting 6 ins. above ground, with brass cap mkd. S1 1/4 S6 1908. Add the marks T26N R15E R16E 2002 to the brass cap. Set a steel fence post 3 ft. N. of cor.
	<hr/> N. 0°02' W., beginning new measurement.
40.03	The cor. of Tps. 26 and 27 N., Rs. 15 and 16 E., monumented with an iron post, 3 ins. diam., firmly set, projecting 12 ins. above ground, with a accessory mound of stone, 2 ft. base, 2 ft., high, to the S., with brass cap mkd. T27N R15E R16E S36 S31 S1 S6 R15E R16E T26N 2002. Set a steel fence post 3 ft. N. of cor.

Dependent Resurvey of the West Boundary,
T. 26 N., R. 15 E., Gila and Salt River Meridian, Arizona

CHAINS	
	<p>Restoring the survey executed by Sidney E. Blout, in 1908-1909</p> <hr/> <p>From the cor. of Tps. 25 and 26 N, Rs. 14 and 15 E., hereinbefore described.</p> <p>N. 0°01' E., bet. secs. 31 and 36.</p>
40.00	<p>Point for the 1/4 sec. cor. of secs. 31 and 36, at proportionate dist.; there is no remaining evidence of the original cor.</p> <p>Set a stainless steel post, 28 ins. long, 2½ ins. diam., 25 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center;"> <p>T26N R14E R15E 1/4 S36 S31 2002</p> </div> <p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p> <p>Set a steel fence post 3 ft. N. of cor.</p>
80.00	<p>Point for the cor. of secs. 25, 30, 31 and 36, at proportionate dist.; there is no remaining evidence of the original cor.</p> <p>Set a stainless steel post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center;"> <p>T26N R14E R15E S25 S30 S36 S31 2002</p> </div> <p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p> <p>Set a steel fence post 3 ft. N. of cor.</p> <hr/> <p>N. 0°01' E., bet. secs. 25 and 30.</p> <p>Over rolling sandy land covered with scattered grasses.</p>

**Dependent Resurvey of the West Boundary,
T. 26 N., R. 15 E., Gila and Salt River Meridian, Arizona**

CHAINS	
40.00	<p>The 1/4 sec. cor. of secs. 25 and 30, monumented with an iron post, 1 in. diam., firmly set, projecting 5 ins. above ground, with brass cap mkd. S25 1/4 S30.</p> <p>Add the marks T26N R14E R15E 2002 to the brass cap.</p> <p>Set a steel fence post 3 ft. N. of cor.</p> <hr style="width: 30%; margin: 10px auto;"/> <p>N. 0°01' E., beginning new measurement.</p>
40.00	<p>The cor. of secs. 19, 24, 25 and 30, monumented with an iron post, 3 ins. diam., firmly set, projecting 8 ins. above ground, with brass cap mkd. T26N R14E R15E S24 S19 S25 S30.</p> <p>Add the marks 2002 to the brass cap.</p> <p>Set a steel fence post 3 ft. N. of cor.</p> <hr style="width: 80%; margin: 10px auto;"/> <p>North, bet. secs. 19 and 24.</p> <p>Over rolling sandy land covered with scattered grasses.</p>
40.00	<p>Point for the 1/4 sec. cor. of secs. 19 and 24, at proportionate dist.; there is no remaining evidence of the original cor.</p> <p>Set a stainless steel post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center; margin: 10px 0;"> <p>T26N R14E R15E 1/4 S24 S19 2002</p> </div> <p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p> <p>Set a steel fence post 3 ft. N. of cor.</p>
80.00	<p>The cor. of secs. 13, 18, 19 and 24, monumented with an iron post, 3 ins. diam., firmly set, projecting 14 ins. above ground, with brass cap mkd. T26N R14E R15E S13 S18 S24 S19.</p> <p>Add the marks 2002 to the brass cap.</p> <p>Set a steel fence post 3 ft. N. of cor.</p> <hr style="width: 80%; margin: 10px auto;"/>

Dependent Resurvey of the West Boundary,
T. 26 N., R. 15 E., Gila and Salt River Meridian, Arizona

CHAINS	
	<p>N. 0°02' E., bet. secs. 13 and 18.</p> <p>Over rolling sandy land covered with scattered grasses.</p> <p>39.99 The 1/4 sec. cor. of secs. 13 and 18, monumented with an iron post, 1 in. diam., firmly set, 1 in. below ground, badly rusted, with brass cap mkd. S13 1/4 S18.</p> <p>At the corner point.</p> <p>Set a stainless steel post, 28 ins. long, 2½ ins. diam., 23 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T26N R14E R15E 1/4 S13 S18 2002</p> <p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p> <p>Set a steel fence post 3 ft. N. of cor.</p> <hr style="width: 30%; margin: 10px auto;"/>
39.98	<p>N. 0°01' E., beginning new measurement.</p> <p>The cor. of secs. 7, 12, 13 and 18, monumented with an iron post, 3 ins. diam., firmly set, projecting 8 ins. above ground, with brass cap mkd. T26N R14E R15E S12 S7 S13 S18.</p> <p>Add the marks 2002 to the brass cap.</p> <p>Set a steel fence post 3 ft. N. of cor.</p> <hr/>
13.03	<p>North, bet. secs. 7 and 12.</p> <p>Over rolling sandy land covered with scattered grasses.</p> <p>Point for crossing closing cor. bet. secs. 7 and 12, at intersection with the boundary of Management District No. 6, Hopi Indian Reservation, hereinafter described.</p>
40.00	<p>The 1/4 sec. cor. of secs. 7 and 12, monumented with an iron post, 1 in. diam., firmly set, projecting 5 ins. above ground, with brass cap mkd. S12 1/4 S7.</p> <p>Add the marks T26N R14E R15E 2002 to the brass cap.</p>



**Dependent Resurvey of the West Boundary,
T. 26 N., R. 15 E., Gila and Salt River Meridian, Arizona**

CHAINS	
	<p>Set a steel fence post 3 ft. N. of cor.</p> <hr/> <p>North, beginning new measurement.</p>
39.98	<p>The cor. of secs. 1, 6, 7 and 12, monumented with an iron post, 3 ins. diam., firmly set, projecting 13 ins. above ground, with brass cap mkd. T26N R14E R15E S1 S6 S12 S7.</p> <p>Add the marks 2002 to the brass cap.</p> <p>Set a steel fence post 3 ft. N. of cor.</p> <hr/>
	<p>North, bet. secs. 1 and 6.</p> <p>Over rolling sandy land covered with scattered grasses.</p>
40.00	<p>The 1/4 sec. cor. of secs. 1 and 6, monumented with an iron post, 1 in. diam., firmly set, projecting 6 ins. above ground, with brass cap mkd. S1 1/4 S6.</p> <p>Add the marks T26N R14E R15E 2002 to the brass cap.</p> <p>Set a steel fence post 3 ft. N. of cor.</p> <hr/>
	<p>N. 0°02' W., beginning new measurement.</p>
40.00	<p>The cor. of Tps. 26 and 27 N., Rs. 14 and 15 E., monumented with an iron post, 3 ins. diam., firmly set, projecting 9 ins. above ground, with brass cap mkd. T27N R14E R15E S36 S31 S1 S6 T26N 2002.</p> <p>Set a steel fence post 3 ft. N. of cor.</p> <hr/>
	<p align="center">Dependent Resurvey of the Subdivisional Lines, T. 26 N., R. 15 E., Gila and Salt River Meridian, Arizona</p> <hr/>
	<p align="center">Restoring the survey executed by Sidney E. Blout, in 1908-1909</p> <hr/>
	<p>From the cor. of secs. 1, 2, 35 and 36, on the S. bdy. of the Tp., hereinbefore described.</p>
	<p>North, bet. secs. 35 and 36.</p> <p>Over rolling sandy land covered with scattered grasses.</p>

Dependent Resurvey of the Subdivisional Lines,
T. 26 N., R. 15 E., Gila and Salt River Meridian, Arizona

CHAINS	
40.00	<p>Point for the 1/4 sec. cor. of secs. 35 and 36, at proportionate dist.; there is no remaining evidence of the original cor.</p> <p>Set a stainless steel post, 28 ins. long, 2½ ins. diam., 26 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center;"> <p>T26N R15E</p> <p>1/4</p> <p>S35 S36</p> <p>2002</p> </div> <p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p> <p>Set a steel fence post 3 ft. N. of cor.</p>
80.00	<p>The cor. of secs. 25, 26, 35 and 36, monumented with an iron post, 2 ins. diam., firmly set, projecting 12 ins. above ground, with brass cap mkd. T26N R15E S26 S25 S35 S36 1909.</p> <p>Add the marks 2002 to the brass cap.</p> <p>Set a steel fence post 3 ft. N. of cor.</p>
	<hr/> <p>From the cor. of secs. 25, 30, 31 and 36, on the E. bdy. of the Tp., hereinbefore described.</p> <p>N. 89°54' W., bet. secs. 25 and 36.</p> <p>Over rolling sandy land covered with scattered grasses.</p>
40.00	<p>Point for the 1/4 sec. cor. of secs. 25 and 36, at proportionate dist.; there is no remaining evidence of the original cor.</p> <p>Set a stainless steel post, 28 ins. long, 2½ ins. diam., 23 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center;"> <p>T26N R15E</p> <p>S25</p> <p>1/4 ———</p> <p>S36</p> <p>2002</p> </div> <p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p>

Dependent Resurvey of the Subdivisional Lines,
T. 26 N., R. 15 E., Gila and Salt River Meridian, Arizona

CHAINS	
80.00	<p>Set a steel fence post 3 ft. N. of cor.</p> <p>The cor. of secs. 25, 26, 35 and 36.</p> <hr/>
39.99	<p>North, bet. secs. 25 and 26.</p> <p>Over rolling sandy land covered with scattered grasses.</p> <p>Point for the 1/4 sec. cor. of secs. 25 and 26, at proportionate dist.; there is no remaining evidence of the original cor.</p> <p>True point falls in a wash, 10 ft. wide, 8 ft. deep, drains S. 30° E., where is it is impracticable to establish a permanent monument.</p> <p>From this point, point selected for the witness 1/4 sec. cor. of secs. 25 and 26 bears S. 45°00' E., 2.00 chs. dist.</p> <p>At the witness point set a stainless steel post, 28 ins. long, 2½ ins. diam., 26 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center;"> <p>WC</p> <p>T26N R15E</p>  </div> <p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p> <p>Set a steel fence post 3 ft. N. of cor.</p>
79.98	<p>The cor. of secs. 23, 24, 25 and 26, determined by a mound of stones, 3 ft. base, 1 1/2 ft. high.</p> <p>At the corner point</p> <p>Set a stainless steel post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center;"> <p>T26N R15E</p>  </div>

Dependent Resurvey of the Subdivisional Lines,
T. 26 N., R. 15 E., Gila and Salt River Meridian, Arizona

CHAINS	
	<p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p> <p>Set a steel fence post 3 ft. N. of cor.</p>
<p>39.92</p>	<hr/> <p>From the cor. of secs. 19, 24, 25 and 30, on the E. bdy. of the Tp., hereinbefore described.</p> <p>N. 89°56' W., bet. secs. 24 and 25.</p> <p>Over rolling sandy land covered with scattered grasses.</p> <p>The 1/4 sec. cor. of secs. 24 and 25, monumented with an iron post, 1 in. diam., firmly set, projecting 3 ins. above ground, with brass cap mkd. S24 1/4 S25 1909.</p> <p>Add the marks T26N R15E 2002 to the brass cap.</p> <p>Set a steel fence post 3 ft. N. of cor.</p> <hr/> <p>N. 89°56' W., beginning new measurement.</p>
<p>40.01</p>	<p>The cor. of secs. 23, 24, 25 and 26.</p> <hr/> <p>North, bet. secs. 23 and 24.</p> <p>Over rolling sandy land covered with scattered grasses.</p>
<p>39.98</p>	<p>Point for the 1/4 sec. cor. of secs. 23 and 24, at proportionate dist.; there is no remaining evidence of the original cor.</p> <p>Set a stainless steel post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center; margin: 20px 0;"> <p>T26N R15E</p> <p>1/4</p> <p>S23 S24</p> <p>2002</p> </div> <p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p> <p>Set a steel fence post 3 ft. N. of cor.</p>

Dependent Resurvey of the Subdivisional Lines,
T. 26 N., R. 15 E., Gila and Salt River Meridian, Arizona

CHAINS	
79.96	<p>The cor. of secs. 13, 14, 23 and 24, monumented with an iron post, 2 ins. diam., firmly set, projecting 10 ins. above ground, with an scattered accessory mound of stone to the W., with brass cap mkd. T26N R15E S14 S13 S23 S24 1909.</p> <p>Add the marks 2002 to the brass cap.</p> <p>Set a steel fence post 3 ft. N. of cor.</p> <p>From this cor., U. S. Geological Survey third order triangulation station "SHONTO", bears S. 38°49' E., 12.05 chs. dist., monumented with a brass tablet, 3½ ins. diam., in concrete form, projecting 3 ins. above ground, with brass cap mkd. SHONTO 1965.</p> <hr/> <p>From the cor. of secs. 13, 18, 19 and 24, on the E. bdy of the Tp., hereinbefore described.</p> <p>N. 89°57' W., bet. secs. 13 and 24.</p> <p>Over rolling sandy land covered with scattered grasses.</p>
39.93	<p>Point for the 1/4 sec. cor. of secs. 13 and 24, at proportionate dist.; there is no remaining evidence of the original cor.</p> <p>Set a stainless steel post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center; margin: 20px 0;"> <p>T26N R15E</p> <p>S13</p> <p>1/4 ———</p> <p>S24</p> <p>2002</p> </div> <p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p> <p>Set a steel fence post 3 ft. N. of cor.</p>
79.86	<p>The cor. of secs. 13, 14, 23 and 24.</p> <hr/> <p>N. 0°02' W., bet. secs. 13 and 14.</p> <p>Over rolling sandy land covered with scattered grasses.</p>
39.98	<p>Point for the 1/4 sec. cor. of secs. 13 and 14, at proportionate dist.; there is no remaining evidence of the original cor.</p>

Dependent Resurvey of the Subdivisional Lines,
T. 26 N., R. 15 E., Gila and Salt River Meridian, Arizona

CHAINS	
79.96	<p>Set a stainless steel post, 28 ins. long, 2½ ins. diam., 20 ins. in the ground, in a collar of stone, with brass cap mkd.</p> <div style="text-align: center;"> <p>T26N R15E</p> <p>1/4</p> <p>S14 S13</p> <p>2002</p> </div> <p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p> <p>Set a steel fence post 3 ft. N. of cor.</p> <p>Cor. is located, 40 lks., N. of a drain, 6 ft. wide, 100 ft. deep, drains S. 20° W.</p> <p>The cor. of secs. 11, 12, 13 and 14, monumented with an iron post, 2 ins. diam., firmly set, projecting 5 ins. above ground, with brass cap mkd. T26N R15E S11 S12 S14 S13 1909.</p> <p>Add the marks 2002 to the brass cap.</p> <p>Set a steel fence post 3 ft. N. of cor.</p>
39.93	<hr/> <p>From the cor. of secs. 7, 12, 13 and 18, on the E. bdy of the Tp., hereinbefore described.</p> <p>S. 89°58' W., bet. secs. 12 and 13.</p> <p>Over rolling sandy land covered with scattered grasses.</p> <p>The 1/4 sec. cor. of secs. 12 and 13, monumented with an iron post, 1 in. diam., firmly set, projecting 2 ins. above ground, with brass cap mkd. 1/4 S12 S13 1909.</p> <p>Add the marks T26N R15E 2002 to the brass cap.</p> <p>Set a steel fence post 3 ft. N. of cor.</p>
39.90	<hr/> <p>N. 89°59' W., beginning new measurement.</p> <p>The cor. of secs. 11, 12, 13 and 14.</p> <hr/> <p>North, bet. secs. 11 and 12.</p>

**Dependent Resurvey of the Subdivisional Lines,
T. 26 N., R. 15 E., Gila and Salt River Meridian, Arizona**

CHAINS	
40.03	<p>Over rolling sandy land covered with scattered grasses.</p> <p>The 1/4 sec. cor. of secs. 11 and 12, determined by a mound of stone, 3 ft. base, 1 ft high. This position is harmoniously related to existing original cors. and is accepted as the best available evidence of the original cor. position.</p> <p>At the corner point</p> <p>Set a stainless steel post, 28 ins. long, 2½ ins. diam., 10 ins. in the ground, in a mound of stone, 4 ft. base, to top, with brass cap mkd.</p> <div style="text-align: center;"> <p>T26N R15E</p> <p>1/4</p> <p>S11 S12</p> <p>2002</p> </div> <p>Set a steel fence post 3 ft. N. of cor.</p> <hr style="width: 20%; margin: auto;"/> <p>N. 0°11' W., beginning new measurement.</p>
40.02	<p>The cor. of secs. 1, 2, 11 and 12, monumented with an iron post, 2 ins. diam., firmly set, projecting 10 ins. above ground, with brass cap mkd. T26N R15E S2 S1 S11 S12.</p> <p>Add the marks 2002 to the brass cap.</p> <p>Set a steel fence post 3 ft. N. of cor.</p> <hr/> <p>From the cor. of secs. 1, 6, 7 and 12, on the E. bdy. of the Tp., hereinbefore described.</p> <p>S. 89°59' W., bet. secs. 1 and 12.</p> <p>Over rolling sandy land covered with scattered grasses.</p>
39.94	<p>The 1/4 sec. cor. of secs. 1 and 12, monumented with an iron post, 1 in. diam., firmly set, projecting 11 ins. above ground, with brass cap mkd. S1 1/4 S12 1909.</p> <p>Add the marks T26N R15E 2002 to the brass cap.</p> <p>Drove iron post into ground, now projects 3 ins. above ground.</p>

Dependent Resurvey of the Subdivisional Lines,
T. 26 N., R. 15 E., Gila and Salt River Meridian, Arizona

CHAINS	
39.96	<p>Set a steel fence post 3 ft. N. of cor.</p> <hr/> <p>West, beginning new measurement.</p> <p>The cor. of secs. 1, 2, 11 and 12.</p> <hr/>
40.02	<p>N. 0°06' W., bet. secs. 1 and 2.</p> <p>Point for the 1/4 sec. cor. of secs. 1 and 2, at proportionate dist.; there is no remaining evidence of the original cor.</p> <p>Set a stainless steel post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center;"> <p>T26N R15E</p> <p>1/4</p> <p>S2 S1</p> <p>2002</p> </div> <p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p> <p>Set a steel fence post 3 ft. N. of cor.</p>
80.18	<p>The cor. secs. 1, 2, 35 and 36, on the N. bdy. of the Tp., monumented with an iron post, 3 ins. diam., firmly set, projecting 6 ins. above ground, with brass cap mkd. T27N R15E S35 S36 S2 S1 T26N 2002.</p> <p>Set a steel fence post 3 ft. N. of cor.</p> <hr/>
22.59	<p>From the cor. of secs. 2, 3, 34 and 35, on the S. bdy. of the Tp., hereinbefore described.</p> <p>N. 0°01' E., bet. secs. 34 and 35.</p> <p>Over rolling sandy land covered with scattered grasses.</p>
40.02	<p>Point for crossing closing cor. bet. secs. 34 and 35, at intersection with the boundary of Management District No. 6, Hopi Indian Reservation, hereinafter described.</p> <p>Point for the 1/4 sec. cor. of secs. 34 and 35, at proportionate dist.; there is no remaining evidence of the original cor.</p>

Dependent Resurvey of the Subdivisional Lines,
T. 26 N., R. 15 E., Gila and Salt River Meridian, Arizona

CHAINS	
80.04	<p>Set a stainless steel post, 28 ins. long, 2½ ins. diam., 26 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T26N R15E 1/4 S34 S35 2002</p> <p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p> <p>Set a steel fence post 3 ft. N. of cor.</p> <p>Point for the cor. of secs. 26, 27, 34 and 35, at proportionate dist.; there is no remaining evidence of the original cor.</p> <p>Set a stainless steel post, 28 ins. long, 2½ ins. diam., 26 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T26N R15E S27 S26 S34 S35 2002</p> <p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p> <p>Set a steel fence post 3 ft. N. of cor.</p>
40.01	<p>From the cor. of secs. 25, 26, 35 and 36.</p> <p>N. 89°51' W., bet. secs. 26 and 35.</p> <p>Over rolling sandy land covered with scattered grasses.</p> <p>The 1/4 sec. cor. of secs. 26 and 35, monumented with an iron post, 1 in. diam., firmly set, flush with the ground, with brass cap mkd. S26 1/4 S35.</p> <p>Add the marks T26N R15E 2002 to the brass cap.</p> <p>Set a steel fence post 3 ft. N. of cor.</p>

**Dependent Resurvey of the Subdivisional Lines,
T. 26 N., R. 15 E., Gila and Salt River Meridian, Arizona**

CHAINS	
	N. 89°53' W., beginning new measurement.
40.00	The cor. of secs. 26, 27, 34 and 35.
	<hr/>
	North, bet. secs. 26 and 27.
	Over rolling sandy land covered with scattered grasses.
40.02	The 1/4 sec. cor. of secs. 26 and 27, monumented with an iron post, 1 in. diam., firmly set, projecting 1 in. above ground, with brass cap mkd. S27 1/4 S26 1909.
	Add the marks T26N R15E 2002 to the brass cap.
	Raise accessory mound of stone, 3 ft. base, 2 ft. high, W. of cor.
	<hr/>
	N. 0°03' E., beginning new measurement.
39.98	Point for the cor. of secs. 22, 23, 26 and 27, at proportionate dist.; the original iron post, 2 ins. diam., 36 ins. long, mkd. T26N R15E S22 S23 S27 S26 1909, was found lying on its side nearby.
	Set original iron post 30 ins. in the ground and add the marks 2002 to the brass cap.
	Deposit a magnet in a white plastic case at the base of the iron post.
	Set a steel fence post 3 ft. N. of cor.
	<hr/>
	From the cor. of secs. 23, 24, 25 and 26.
	S. 89°48' W., bet. secs. 23 and 26.
	Over rolling sandy land covered with scattered grasses.
39.90	The 1/4 sec. cor. of secs. 23 and 26, monumented with an iron post, 1 in. diam., loosely set, with an accessory mound of stone, 2 ft. base, 1 ft. high to the N., with brass cap mkd. S23 1/4 S26 1909.
	At the corner point
	Set a stainless steel post, 28 ins. long, 2½ ins. diam., 4 ins. in the ground, to bedrock, in a supporting mound of stone, 4 ft. base, to top, with brass cap mkd.

Dependent Resurvey of the Subdivisional Lines,
T. 26 N., R. 15 E., Gila and Salt River Meridian, Arizona

CHAINS	
	T26N R15E S23 1/4 ——— S26 2002
	Deposit a magnet in a white plastic case at the base of the stainless steel post and place the iron post inside it. <hr/> N. 89°29' W., beginning new measurement.
40.07	The cor. of secs. 22, 23, 26 and 27. <hr/> N. 0°01' W., bet. secs. 22 and 23. Over rolling sandy land covered with scattered grasses.
39.98	The 1/4 sec. cor. of secs. 22 and 23, monumented with an iron post, 1 in. diam., firmly set, projecting 12 ins. above ground, in a mound of stone, 3 ft. base, 2 ft., high, with brass cap mkd. S22 1/4 S23 1909. Add the marks T26N R15E 2002 to the brass cap. <hr/> N. 0°01' W., beginning new measurement.
39.99	The cor. of secs. 14, 15, 22 and 23, monumented with an iron post, 2 ins. diam., firmly set, projecting 8 ins. above ground, with a scattered mound of stone to the W., with brass cap mkd. T26N R15E S15 S14 S22 S23 1909. Add the marks 2002 to the brass cap. Raise mound of stone 3 ft. base., 1 ft. high, W. of cor. Set a steel fence post 3 ft. N. of cor. <hr/> From the cor. of secs. 13, 14, 23 and 24. N. 89°50' W., bet. secs. 14 and 23. Over rolling sandy land covered with scattered grasses.

**Dependent Resurvey of the Subdivisional Lines,
T. 26 N., R. 15 E., Gila and Salt River Meridian, Arizona**

CHAINS	
39.99	<p>Point for the 1/4 sec. cor. of secs. 14 and 23, at proportionate dist.; there is no remaining evidence of the original cor.</p> <p>True point falls on an eroding precipitous slope, where it is impracticable to establish a permanent monument.</p> <p>From this point, point selected for the witness 1/4 sec. cor. of secs. 14 and 23 bears N. 35°01' E., 1.80 chs. dist.</p> <p>At the witness point set a stainless steel post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center; margin: 10px 0;"> <p>WC T26N R15E S14 1/4 ————— ↙ S23 2002</p> </div> <p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p> <p>Set a steel fence post 3 ft. N. of cor.</p>
79.98	<p>The cor. of secs. 14, 15, 22 and 23.</p> <hr style="border: 0.5px solid black; margin: 10px 0;"/> <p>N. 0°02' W., bet. secs. 14 and 15.</p> <p>Over rolling sandy land covered with scattered grasses.</p>
39.99	<p>The 1/4 sec. cor. of secs. 14 and 15, monumented with an iron post, 1 in. diam., firmly set, 6 ins. below ground, with brass cap mkd. S15 1/4 S14 1909.</p> <p>Add the marks T26N R15E 2002 to the brass cap.</p> <p>Set a steel fence post 3 ft. N. of cor.</p> <hr style="border: 0.5px solid black; margin: 10px 0;"/> <p>N. 0°03' W., beginning new measurement.</p>
39.89	<p>The cor. of secs. 10, 11, 14 and 15, monumented with an iron post, 2 ins. diam., firmly set, projecting 2 ins. above ground, with brass cap mkd. T26N R15E S10 S11 S15 S14 1909.</p> <p>Add the marks 2002 to the brass cap.</p> <p>Set a steel fence post 3 ft. N. of cor.</p> <hr style="border: 0.5px solid black; margin: 10px 0;"/>

Dependent Resurvey of the Subdivisional Lines,
T. 26 N., R. 15 E., Gila and Salt River Meridian, Arizona

CHAINS	
	<p>From the cor. of secs. 11, 12, 13 and 14.</p> <p>N. 89°53' W., bet. secs. 11 and 14.</p> <p>Over rolling sandy land covered with scattered grasses.</p>
39.99	<p>The 1/4 sec. cor. of secs. 11 and 14, monumented with an iron post, 1 in. diam., firmly set, projecting 10 ins. above ground, with brass cap mkd. S11 1/4 S14 1909.</p> <p>Add the marks T26N R15E 2002 to the brass cap.</p> <p>Set a steel fence post 3 ft. N. of cor.</p> <hr style="width: 30%; margin: 10px auto;"/> <p>N. 89°53' W., beginning new measurement.</p>
39.99	<p>The cor. of secs. 10, 11, 14 and 15.</p> <hr style="width: 60%; margin: 10px auto;"/> <p>N. 0°03' W., bet. secs. 10 and 11.</p> <p>Over rolling sandy land covered with scattered grasses.</p>
40.00	<p>Point for the 1/4 sec. cor. of secs. 10 and 11, at proportionate dist.; there is no remaining evidence of the original cor.</p> <p>Set a stainless steel post, 28 ins. long, 2½ ins. diam., 20 ins. in the ground, in a mound of stone, 3 ft. base, to top, with brass cap mkd.</p> <div style="text-align: center; margin: 20px 0;"> <p>T26N R15E</p> <p>1/4</p> <p>S10 S11</p> <p>2002</p> </div> <p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p> <p>Set a steel fence post 3 ft. N. of cor.</p> <p>Cor. is located, 67 lks. S. of a ledge, bears N. 45° E. and S. 50° W.</p>
80.00	<p>The cor. of secs. 2, 3, 10 and 11, monumented with an iron post, 2 ins. diam., firmly set, projecting 7 ins. above ground, with brass cap mkd. T26N R15E S3 S2 S10 S11 1909.</p>

Dependent Resurvey of the Subdivisional Lines,
T. 26 N., R. 15 E., Gila and Salt River Meridian, Arizona

CHAINS	
	<p>Add the marks 2002 to the brass cap.</p> <p>Set a steel fence post 3 ft. N. of cor.</p> <hr/> <p>From the cor. of secs. 1, 2, 11 and 12.</p> <p>N. 89°55' W., bet. secs. 2 and 11.</p> <p>Over rolling sandy land covered with scattered grasses.</p>
39.96	<p>Point for the 1/4 sec. cor. of secs. 2 and 11, at proportionate dist.; there is no remaining evidence of the original cor.</p> <p>Set a stainless steel post, 28 ins. long, 2½ ins. diam., 22 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T26N R15E</p> <p style="text-align: center;">S2</p> <p style="text-align: center;">1/4 <u> </u></p> <p style="text-align: center;">S11</p> <p style="text-align: center;">2002</p> <p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p> <p>Set a steel fence post 3 ft. N. of cor.</p>
79.92	<p>The cor. of secs. 2, 3, 10 and 11.</p> <hr/> <p>N. 0°09' W., bet. secs. 2 and 3.</p> <p>Over level sandy land covered with scattered grasses.</p>
40.00	<p>The 1/4 sec. cor. of secs. 2 and 3, monumented with an iron post, 1 in. diam., firmly set, projecting 7 ins. above ground, with brass cap mkd. S3 1/4 S2 1909.</p> <p>Add the marks T26N R15E 2002 to the brass cap.</p> <hr/> <p>N. 0°07' W., beginning new measurement.</p>
40.14	<p>The cor. of secs. 2, 3, 34 and 35, on the N. bdy. of the Tp., monumented with an iron post, 3 ins. diam., firmly set, projecting 7 ins. above ground, with brass cap mkd. T27N R15E S34 S35 S3 S2 T26N 2002.</p> <hr/>

Dependent Resurvey of the Subdivisional Lines,
T. 26 N., R. 15 E., Gila and Salt River Meridian, Arizona

CHAINS	
	<p>From the cor. secs. 3, 4, 33 and 34, on the S. bdy. of the Tp., hereinbefore described.</p>
	<p>N. 0°01' W., bet. secs. 33 and 34.</p>
	<p>Over rolling sandy land covered with scattering grasses.</p>
40.00	<p>The 1/4 sec. cor. of secs. 33 and 34, monumented with an iron post, 1 in. diam., firmly set, projecting 5 ins. above ground, with brass cap mkd. S33 1/4 S34.</p>
	<p>Add the marks T26N R15E 2002 to the brass cap.</p>
	<p>Set a steel fence post 3 ft. N. of cor.</p>
	<hr/> <p>N. 0°01' E., beginning new measurement.</p>
40.02	<p>Point for the cor. secs. 27, 28, 33 and 34, at proportionate dist.; the original iron post, 2 ins. diam., 36 ins. long, mkd. T26N R15E S28 S27 S33 S34 1909, was found lying on its side nearby.</p>
	<p>Set original iron post, 25 ins. in the ground and add the marks 2002 to the brass cap.</p>
	<p>Deposit a magnet in a white plastic case at the base of the iron post.</p>
	<p>Set a steel fence post 3 ft. N. of cor.</p>
	<hr/> <p>From the cor. of secs. 26, 27, 34 and 35.</p>
	<p>N. 89°53' W., bet. secs. 27 and 34.</p>
	<p>Over rolling sandy land covered with scattered grasses.</p>
40.03	<p>The 1/4 sec. cor. of secs. 27 and 34, monumented with an iron post, 1 in. diam., firmly set, projecting 6 ins. above ground, with brass cap mkd. S27 1/4 S34 1909.</p>
	<p>Add the marks T26N R15E 2002 to the brass cap.</p>
	<p>Set a steel fence post 4 ft. S. of cor.</p>
	<hr/> <p>N. 89°55' W., beginning new measurement.</p>

**Dependent Resurvey of the Subdivisional Lines,
T. 26 N., R. 15 E., Gila and Salt River Meridian, Arizona**

CHAINS	
19.33	Point for crossing closing cor. bet. secs. 27 and 34, at intersection with the boundary of Management District No. 6, Hopi Indian Reservation, hereinafter described.
40.04	The cor. of secs. 27, 28, 33 and 34. <hr/>
	N. 0°03' E., bet. secs. 27 and 28. Over rolling sandy land covered with scattered grasses.
20.04	Point for crossing closing cor. bet. secs. 27 and 28, at intersection with the boundary of Management District No. 6, Hopi Indian Reservation, hereinafter described.
40.02	The 1/4 sec. cor. of secs. 27 and 28, monumented with an iron post, 1 in. diam., firmly set, projecting 8 ins. above ground, with brass cap mkd. S28 1/4 S27 1909. Add the marks T26N R15E 2002 to the brass cap. Set a steel fence post 3 ft. N. of cor. <hr/>
	N. 0°01' E., beginning new measurement.
40.02	The cor. of secs. 21, 22, 27 and 28, monumented with an iron post, 2 ins. diam., firmly set, flush with the ground, with brass cap mkd. T26N R15E S21 S22 S27 S28 1909. Add the marks 2002 to the brass cap. Set a steel fence post 3 ft. N. of cor. <hr/>
	From the cor. of secs. 22, 23, 26 and 27. N. 89°53' W., bet. secs. 22 and 27. Over rolling sandy land covered with scattered grasses.
40.02	Point for the 1/4 sec. cor. of secs. 22 and 27, at proportionate dist.; there is no remaining evidence of the original cor. Set a stainless steel post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.

Dependent Resurvey of the Subdivisional Lines,
T. 26 N., R. 15 E., Gila and Salt River Meridian, Arizona

CHAINS	
	<p>T26N R15E</p> <p style="margin-left: 100px;">S22</p> <p style="margin-left: 50px;">1/4 ———</p> <p style="margin-left: 100px;">S27</p> <p style="margin-left: 100px;">2002</p>
	<p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p> <p>Set a steel fence post 3 ft. N. of cor.</p>
80.04	<p>The cor. of secs. 21, 22, 27 and 28.</p> <hr/> <p>North, bet. secs. 21 and 22.</p> <p>Over rolling sandy land covered with scattered grasses.</p>
40.00	<p>Point for the 1/4 sec. cor. of secs. 21 and 22., at proportionate dist.; there is no remaining evidence of the original cor.</p> <p>Set a stainless steel post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.</p>
	<p>T26N R15E</p> <p style="margin-left: 100px;">1/4</p> <p style="margin-left: 50px;">S21 S22</p> <p style="margin-left: 100px;">2002</p>
	<p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p> <p>Set a steel fence post 3 ft. N. of cor.</p>
80.00	<p>The cor. of secs. 15, 16, 21 and 22, monumented with an iron post, 2 ins. diam., firmly set, projecting 10 ins. above ground, with brass cap mkd. T26N R15E S16 S15 S21 S22 1909.</p> <p>Add the marks 2002 to the brass cap.</p> <p>Set a steel fence post 3 ft. N. of cor.</p> <hr/> <p>From the cor. of secs. 14, 15, 22 and 23.</p>

Dependent Resurvey of the Subdivisional Lines,
T. 26 N., R. 15 E., Gila and Salt River Meridian, Arizona

CHAINS	
40.01	<p>N. 89°51' W., bet. secs. 15 and 22.</p> <p>Over rolling sandy land covered with scattered grasses.</p> <p>The 1/4 sec. cor. of secs. 15 and 22, monumented with an iron post, 1 in. diam., firmly set, 3 ft. below ground, with brass cap mkd. 1/4 S15 S22 1909.</p> <p>At the corner point</p> <p>Set a stainless steel post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, above the existing iron post, with brass cap mkd.</p> <div style="text-align: center;"> <p>T26N R15E</p> <p>S15</p> <p>1/4 ———</p> <p>S22</p> <p>2002</p> </div> <p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p> <p>Set a steel fence post 3 ft. N. of cor.</p> <hr style="width: 30%; margin-left: auto; margin-right: auto;"/>
40.00	<p>N. 89°52' W., beginning new measurement.</p> <p>The cor. of secs. 15, 16, 21 and 22.</p> <hr/>
39.99	<p>N. 0°01' W., bet. secs. 15 and 16.</p> <p>Over level sandy land covered with scattered grasses.</p> <p>The 1/4 sec. cor. of secs. 15 and 16, monumented with an iron post, 1 in. diam., firmly set, projecting 6 ins. above ground, with brass cap mkd. S16 1/4 S15 1909.</p> <p>Add the marks T26N R15E 2002 to the brass cap.</p> <p>Set a steel fence post 3 ft. N. of cor.</p> <hr style="width: 30%; margin-left: auto; margin-right: auto;"/> <p>N. 0°01' W., beginning new measurement.</p>
40.02	<p>The cor. of secs. 9, 10, 15 and 16, monumented with an iron post, 2 ins. diam., firmly set, projecting 6 ins. above ground, with brass cap mkd. T26N R15E S9 S10 S16 S15 1909.</p>

**Dependent Resurvey of the Subdivisional Lines,
T. 26 N., R. 15 E., Gila and Salt River Meridian, Arizona**

CHAINS	
39.97	<p>Add the marks 2002 to the brass cap.</p> <p>Set a steel fence post 3 ft. N. of cor.</p> <hr/> <p>From the cor. of secs. 10, 11, 14 and 15.</p> <p>N. 89°46' W., bet. secs. 10 and 15.</p> <p>Over rolling sandy land covered with scattered grasses.</p> <p>The 1/4 sec. cor. of secs. 10 and 15, monumented with an iron post, 1 in. diam., firmly set, 2 ins. below ground, with brass cap mkd. S10 1/4 S15 1909.</p> <p>Add the marks T26N R15E 2002 to the brass cap.</p> <p>Set a steel fence post 6 ft. W. of cor.</p> <hr/> <p>N. 89°47' W., beginning new measurement.</p>
39.99	<p>The cor. of secs. 9, 10, 15 and 16.</p> <hr/> <p>N. 0°02' W., bet. secs. 9 and 10</p> <p>Over level sandy land covered with scattered grasses.</p>
40.02	<p>The 1/4 sec. cor. of secs. 9 and 10, monumented with an iron post, 1 in. diam., loosely set, projecting 6 ins. above ground, badly rusted, with brass cap mkd. S9 1/4 S10 1909.</p> <p>At the corner point</p> <p>Set a stainless steel post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center; margin: 10px 0;"> <p>T26N R15E</p> <p>1/4</p> <p>S9 S10</p> <p>2002</p> </div> <p>Deposit a magnet in a white plastic case at the base of the stainless steel post and place the iron post inside it.</p> <p>Set a steel fence post 6 ft. E. of cor.</p>

**Dependent Resurvey of the Subdivisional Lines,
T. 26 N., R. 15 E., Gila and Salt River Meridian, Arizona**

CHAINS					
40.01	<p>Cor is located 20 lks. E. of a wash, 10 ft. deep, 20 ft. wide, drains S. 40° W.</p> <hr style="width: 30%; margin: 10px auto;"/> <p>North, beginning new measurement.</p> <p>Point for the cor. of secs. 3, 4, 9 and 10, at proportionate dist.; there is no remaining evidence of the original cor.</p> <p>Set a stainless steel post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T26N R15E</p> <table style="margin-left: auto; margin-right: auto; border-collapse: collapse;"> <tr> <td style="border-right: 1px solid black; padding: 2px 5px;">S4</td> <td style="padding: 2px 5px;">S3</td> </tr> <tr> <td style="border-right: 1px solid black; padding: 2px 5px;">S9</td> <td style="padding: 2px 5px;">S10</td> </tr> </table> <p style="text-align: center;">2002</p> <p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p> <p>Set a steel fence post 3 ft. N. of cor.</p> <hr style="width: 80%; margin: 10px auto;"/> <p>From the cor. of secs. 2, 3, 10 and 11.</p> <p>N. 89°43' W., bet. secs. 3 and 10.</p> <p>Over level sandy land covered with scattered grasses.</p>	S4	S3	S9	S10
S4	S3				
S9	S10				
39.95	<p>The 1/4 sec. cor. of secs. 3 and 10, monumented with an iron post, 1 in. diam., lying on its side, broken off at point where the post enters the ground, with brass cap mkd. 1/4 S3 S10 1909. Cor. position determined from the portion of iron post remaining in the ground.</p> <p>True point falls on an eroding slope, where is it is impracticable to establish a permanent monument.</p> <p>From this point, point selected for the witness 1/4 sec. cor. of secs. 3 and 10 bears N. 43°57' W., 2.00 chs. dist.</p> <p>At the witness point set a stainless steel post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.</p>				

Dependent Resurvey of the Subdivisional Lines,
T. 26 N., R. 15 E., Gila and Salt River Meridian, Arizona

CHAINS	
	<p style="text-align: center;">WC T26N R15E</p> <p style="text-align: center;">S3</p> <p style="text-align: center;">1/4 ———</p> <p style="text-align: center;">S10 ↘</p> <p style="text-align: center;">2002</p> <p>Deposit a magnet in a white plastic case at the base of the stainless steel post and place the iron post inside it.</p> <hr/> <p>N. 89°47' W., beginning new measurement.</p>
39.94	<p>The cor. of secs. 3, 4, 9 and 10.</p> <hr/>
	<p>N. 0°14' W., bet. secs. 3 and 4.</p> <p>Over level sandy land covered with scattered grasses.</p>
17.80	<p>Center line of Arizona Highway 87, 30 ft. wide, bears N. 25° E. and S. 25° W.</p>
40.01	<p>Point for the 1/4 sec. cor. of secs. 3 and 4, at proportionate dist.; there is no remaining evidence of the original cor.</p> <p>Set a stainless steel post, 28 ins. long, 2½ ins. diam., 25 ins. in the ground, with brass cap mkd.</p>
	<p style="text-align: center;">T26N R15E</p> <p style="text-align: center;">1/4</p> <p style="text-align: center;">S4 S3</p> <p style="text-align: center;">2002</p> <p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p> <p>Set a steel fence post 3 ft. N. of cor.</p>
79.88	<p>The cor. of secs. 3, 4, 33 and 34, on the N. bdy. of the Tp. monumented with an iron post, 3 ins. diam., firmly set, 12 ins. below ground, badly rusted, with brass cap mkd. T27N R15E S33 S34 S4 S3 T26N. Iron post was lowered an additional 12 ins.</p> <p>At the corner point</p>

**Dependent Resurvey of the Subdivisional Lines,
T. 26 N., R. 15 E., Gila and Salt River Meridian, Arizona**

CHAINS					
	<p>Set a stainless steel post, 28 ins. long, 2½ ins. diam., 23 ins. in the ground, above the original iron post, with brass cap mkd.</p> <p align="center">T27N R15E</p> <table border="1" data-bbox="889 428 1003 527"> <tr> <td>S33</td> <td>S34</td> </tr> <tr> <td>S4</td> <td>S3</td> </tr> </table> <p align="center">T26N 2002</p> <p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p>	S33	S34	S4	S3
S33	S34				
S4	S3				
	<p>From the cor. of secs. 4, 5, 32 and 33, on the S. bdy. of the Tp., hereinbefore described.</p> <p>N. 0°01' W., bet. secs. 32 and 33.</p> <p>Over rolling sandy land covered with scattered grasses.</p>				
40.01	<p>Point for the 1/4 sec. cor. of secs. 32 and 33, at proportionate dist.; original iron post was found laying nearby.</p> <p>Set a stainless steel post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p align="center">T26N R15E</p> <table border="1" data-bbox="889 1226 1003 1367"> <tr> <td colspan="2" style="text-align: center;">1/4</td> </tr> <tr> <td>S32</td> <td>S33</td> </tr> </table> <p align="center">2002</p> <p>Deposit a magnet in a white plastic case at the base of the stainless steel post and place the iron post inside it.</p> <p>Set a steel fence post 3 ft. N. of cor.</p>	1/4		S32	S33
1/4					
S32	S33				
80.02	<p>The cor. of secs. 28, 29, 32 and 33, monumented with an iron post, 2 ins. diam., firmly set, projecting 12 ins. above ground, with no brass cap.</p> <p>At the corner point</p> <p>Set a stainless steel post, 28 ins. long, 2½ ins. diam., 25 ins. in the ground, with brass cap mkd.</p>				

**Dependent Resurvey of the Subdivisional Lines,
T. 26 N., R. 15 E., Gila and Salt River Meridian, Arizona**

CHAINS					
	<p>T26N R15E</p> <table style="margin: auto;"> <tr> <td style="border-right: 1px solid black; padding: 0 5px;">S29</td> <td style="padding: 0 5px;">S28</td> </tr> <tr> <td style="border-right: 1px solid black; padding: 0 5px;">S32</td> <td style="padding: 0 5px;">S33</td> </tr> </table> <p>2002</p> <p>Deposit a magnet in a white plastic case at the base of the stainless steel post and place the iron post inside it.</p> <p>Set a steel fence post 3 ft. N. of cor.</p> <hr/> <p>From the cor. of secs. 27, 28, 33 and 34.</p> <p>N. 89°54' W., bet. secs. 28 and 33.</p> <p>Over rolling sandy land covered with scattered grasses.</p>	S29	S28	S32	S33
S29	S28				
S32	S33				
39.99	<p>Point for the 1/4 sec. cor. of secs. 28 and 33, at proportionate dist.; there is no remaining evidence of the original cor.</p> <p>Set a stainless steel post, 28 ins. long, 2½ ins. diam., 25 ins. in the ground, with brass cap mkd.</p>				
	<p>T26N R15E</p> <table style="margin: auto;"> <tr> <td style="padding: 0 5px;">1/4</td> <td style="border-top: 1px solid black; border-bottom: 1px solid black; padding: 0 5px;">S28</td> </tr> <tr> <td></td> <td style="padding: 0 5px;">S33</td> </tr> </table> <p>2002</p> <p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p> <p>Set a steel fence post 3 ft. N. of cor.</p>	1/4	S28		S33
1/4	S28				
	S33				
79.98	<p>The cor. of secs. 28, 29, 32 and 33.</p> <hr/> <p>N. 0°01' W., bet. secs. 28 and 29.</p> <p>Over level sandy land covered with scattered grasses.</p>				
40.03	<p>The 1/4 sec. cor. of secs. 28 and 29, monumented with an iron post, 1 in. diam., firmly set, 18 ins. below ground, badly rusted, with brass cap mkd. S29 1/4 S28 1909.</p>				

Dependent Resurvey of the Subdivisional Lines,
T. 26 N., R. 15 E., Gila and Salt River Meridian, Arizona

CHAINS

At the corner point

Set a stainless steel post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.

T26N R15E

1/4

S29 | S28

2002

Deposit a magnet in a white plastic case at the base of the stainless steel post and place the iron post inside it.

Set a steel fence post 3 ft. N. of cor.

N. 0°01' E., beginning new measurement.

40.02

Point for the cor. of secs. 20, 21, 28 and 29, at proportionate dist.; there is no remaining evidence of the original cor.

True point falls on an eroding slope, where is it is impracticable to establish a permanent monument.

From this point, point selected for the witness cor. of secs. 20, 21, 28 and 29, bears S. 45°00' E., 5.00 chs. dist.

At the witness point set a stainless steel post, 28 ins. long, 2½ ins. diam., 23 ins. in the ground, with brass cap mkd.

WC

T26N R15E

S20 | S21

S29 | S28

2002

Deposit a magnet in a white plastic case at the base of the stainless steel post.

Set a steel fence post 3 ft. N. of cor.

From the cor. of secs. 21, 22, 27 and 28.

N. 89°54' W., bet. secs. 21 and 28.

**Dependent Resurvey of the Subdivisional Lines,
T. 26 N., R. 15 E., Gila and Salt River Meridian, Arizona**

CHAINS	
	Over rolling sandy land covered with scattered grasses.
40.00	<p>The 1/4 sec. cor. of secs. 21 and 28, monumented with an iron post, 1 in. diam., firmly set, 18 ins. below ground, badly rusted, with brass cap mkd. S21 1/4 S28 1909.</p> <p>At the corner point</p> <p>Set a stainless steel post, 28 ins. long, 2½ ins. diam., 22 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center; margin: 20px 0;"> <p>T26N R15E</p> <p>S21</p> <p>1/4 <u> </u></p> <p>S28</p> <p>2002</p> </div> <p>Deposit a magnet in a white plastic case at the base of the stainless steel post and place the iron post inside it.</p> <p>Set a steel fence post 3 ft. N. of cor.</p> <hr style="width: 30%; margin: 10px auto;"/> <p>N. 89°53' W., bet. secs. 21 and 28.</p>
22.22	Point for crossing closing cor. bet. secs. 21 and 28, at intersection with the boundary of Management District No. 6, Hopi Indian Reservation, hereinafter described.
40.01	The cor. of secs. 20, 21, 28 and 29.
	<hr style="width: 100%;"/> <p>N. 0°04' W., bet. secs. 20 and 21.</p> <p>Over level sandy land covered with scattered grasses.</p>
17.15	Point for crossing closing cor. bet. secs. 20 and 21, at intersection with the boundary of Management District No. 6, Hopi Indian Reservation, hereinafter described.
40.02	<p>The 1/4 sec. cor. of secs. 20 and 21, determined by remaining remnants of a rust ring of the original iron post in the ground.</p> <p>At the corner point</p> <p>Set a stainless steel post, 28 ins. long, 2½ ins. diam., 25 ins. in the ground, with brass cap mkd.</p>

**Dependent Resurvey of the Subdivisional Lines,
T. 26 N., R. 15 E., Gila and Salt River Meridian, Arizona**

CHAINS	
40.03	<p align="center">T26N R15E 1/4 S20 S21 2002</p> <p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p> <hr/> <p>N. 0°01' W., beginning new measurement.</p> <p>The cor. of secs. 16, 17, 20 and 21, monumented with an iron post, 2 ins. diam., firmly set, projecting 7 ins. above ground, with brass cap mkd. T26N R15E S17 S16 S20 S21 1909.</p> <p>Add the marks 2002 to the brass cap.</p> <hr/>
40.03	<p>From the cor. of secs. 15, 16, 21 and 22.</p> <p>N. 89°52' W., bet. secs. 16 and 21.</p> <p>Over rolling sandy land covered with scattered grasses.</p> <p>Point for the 1/4 sec. cor. of secs. 16 and 21, at proportionate dist.; there is no remaining evidence of the original cor.</p> <p>Set a stainless steel post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.</p>
80.06	<p align="center">T26N R15E S16 1/4 ——— S21 2002</p> <p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p> <p>Set a steel fence post 3 ft. N. of cor.</p> <p>The cor. of secs. 16, 17, 20 and 21.</p> <hr/> <p>North, bet. secs. 16 and 17.</p>

**Dependent Resurvey of the Subdivisional Lines,
T. 26 N., R. 15 E., Gila and Salt River Meridian, Arizona**

CHAINS	
	Over level land covered with scattered grasses.
22.50	Center line of Arizona Highway 87, 30 ft. wide, bears N. 31° E. and S. 31° W.
40.02	Point for the 1/4 sec. cor. of secs. 16 and 17, at proportionate dist.; there is no remaining evidence of the original cor. Set a stainless steel post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd. <div style="text-align: center;"> <p>T26N R15E</p> <p>1/4</p> <p>S17 S16</p> <p>2002</p> </div> Deposit a magnet in a white plastic case at the base of the stainless steel post. From this cor., U. S. Geological Survey triangulation station "W 70", bears S. 82°44' E., 8.38 chs. dist., monumented with a brass tablet, 3½ ins. diam., in concrete form, projecting 3 ins. above ground, with brass cap mkd. W70 1934.
80.04	The cor. of secs. 8, 9, 16 and 17, monumented with an iron post, 2 ins. diam., loosely set, projecting 12 ins. above ground, with brass cap mkd. T26N R15E S8 S9 S17 S16 1909. Reset iron post in same position, now projects 10 ins. above ground. Add the marks 2002 to the brass cap. Deposit a magnet in a white plastic case at the base of the iron post.
	From the cor. of secs. 9, 10, 15 and 16. N. 89°50' W., bet. secs. 9 and 16. Over level sandy land covered with scattered grasses.
40.01	Point for the 1/4 sec. cor. of secs. 9 and 16, at proportionate dist.; there is no remaining evidence of the original cor. Set a stainless steel post, 28 ins. long, 2½ ins. diam., 26 ins. in the ground, with brass cap mkd.

Dependent Resurvey of the Subdivisional Lines,
T. 26 N., R. 15 E., Gila and Salt River Meridian, Arizona

CHAINS	
	<p style="text-align: center;">T26N R15E</p> <p style="text-align: center;">S9</p> <p style="text-align: center;">1/4 ———</p> <p style="text-align: center;">S16</p> <p style="text-align: center;">2002</p>
	<p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p>
	<p>Set a steel fence post 3 ft. N. of cor.</p>
46.30	<p>Center line of Arizona Highway 87, 30 ft. wide, bears N. 30° E. and S. 30° W.</p>
80.02	<p>The cor. of secs. 8, 9, 16 and 17.</p> <hr/>
	<p>N. 0°02' W., bet. secs. 8 and 9.</p>
	<p>Over rolling sandy land covered with scattered grasses.</p>
39.96	<p>Point for the 1/4 sec. cor. of secs. 8 and 9, at proportionate dist.; there is no remaining evidence of the original cor.</p>
	<p>Set a stainless steel post, 28 ins. long, 2½ ins. diam., 26 ins. in the ground, with brass cap mkd.</p>
	<p style="text-align: center;">T26N R15E</p> <p style="text-align: center;">1/4</p> <p style="text-align: center;">S8 S9</p> <p style="text-align: center;">2002</p>
	<p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p>
	<p>Set a steel fence post 3 ft. N. of cor.</p>
79.92	<p>Point for the cor. of secs. 4, 5, 8 and 9, at proportionate dist.; there is no remaining evidence of the original cor.</p>
	<p>Set a stainless steel post, 28 ins. long, 2½ ins. diam., 28 ins. in the ground, with brass cap mkd.</p>

**Dependent Resurvey of the Subdivisional Lines,
T. 26 N., R. 15 E., Gila and Salt River Meridian, Arizona**

CHAINS						
	<p>T26N R15E</p> <table style="margin: auto; border-collapse: collapse;"> <tr> <td style="border-right: 1px solid black; padding: 2px 5px;">S5</td> <td style="padding: 2px 5px;">S4</td> </tr> <tr> <td style="border-right: 1px solid black; padding: 2px 5px;">S8</td> <td style="padding: 2px 5px;">S9</td> </tr> </table> <p>2002</p> <p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p> <p>Set a steel fence post 3 ft. N. of cor.</p> <hr style="border: 0.5px solid black;"/> <p>From the cor. of secs. 3, 4, 9 and 10.</p> <p>N. 89°55' W., bet. secs. 4 and 9.</p> <p>Over level sandy land covered with scattered grasses.</p>	S5	S4	S8	S9	
S5	S4					
S8	S9					
7.80	Center line of Arizona Highway 87, 30 lks. wide, bears N. 20° E. and S. 20° W.					
40.01	<p>Point for the 1/4 sec. cor. of secs. 4 and 9, at proportionate dist.; there is no remaining evidence of the original cor.</p> <p>Set a stainless steel post, 28 ins. long, 2½ ins. diam., 28 ins. in the ground, with brass cap mkd.</p>					
	<p>T26N R15E</p> <table style="margin: auto; border-collapse: collapse;"> <tr> <td style="padding: 2px 5px;">S4</td> </tr> <tr> <td style="border-right: 1px solid black; padding: 2px 5px;">1/4</td> <td style="padding: 2px 5px;">—</td> </tr> <tr> <td style="padding: 2px 5px;">S9</td> <td style="padding: 2px 5px;"></td> </tr> </table> <p>2002</p> <p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p> <p>Set a steel fence post 3 ft. N. of cor.</p>	S4	1/4	—	S9	
S4						
1/4	—					
S9						
80.02	<p>The cor. of secs. 4, 5, 8 and 9.</p> <hr style="border: 0.5px solid black;"/> <p>N. 0°12' W., bet. secs. 4 and 5.</p> <p>Over rolling sandy land covered with scattered grasses.</p>					

**Dependent Resurvey of the Subdivisional Lines,
T. 26 N., R. 15 E., Gila and Salt River Meridian, Arizona**

CHAINS					
39.96	<p>The 1/4 sec. cor. of secs. 4 and 5, monumented with an iron post, 1 in. diam., firmly set, projecting 2 ins. above ground, with brass cap mkd. S5 1/4 S4 1909.</p> <p>Add the marks T26N R15E 2002 to the brass cap.</p> <hr style="width: 20%; margin: 10px auto;"/> <p>N. 0°13' W., beginning new measurement.</p>				
39.87	<p>The cor. of secs. 4, 5, 32 and 33, on the N. bdy. of the Tp., monumented with an iron post, 3 ins. diam., firmly set, projecting 4 ins. above ground, with brass cap mkd. T27N R15E S4 S5 S32 S33 T26N 2002.</p> <hr style="width: 20%; margin: 10px auto;"/> <p>From the cor. of secs. 5, 6, 31 and 32, on the S. bdy. of the Tp., hereinbefore described.</p> <p>N. 0°02' W., bet. secs. 31 and 32.</p> <p>Over level sandy land covered with scattered grasses.</p>				
40.03	<p>The 1/4 sec. cor. of secs. 31 and 32, monumented with an iron post, 1 in. diam., firmly set, projecting 6 ins. above ground, with brass cap mkd. S31 1/4 S32 1909.</p> <p>Add the marks T26N R15E 2002 to the brass cap.</p> <hr style="width: 20%; margin: 10px auto;"/> <p>N. 0°03' W., beginning new measurement.</p> <p>Over rolling sandy land covered with scattered grasses.</p>				
39.60	<p>Center line of Arizona Highway 87, 30 ft. wide, bears N. 40° E. and S. 40° W.</p>				
40.00	<p>Point for the cor. of secs. 29, 30, 31 and 32, at proportionate dist.; there is no remaining evidence of the original cor.</p> <p>Set a stainless steel post, 28 ins. long, 2½ ins. diam., 40 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center; margin-top: 20px;"> <p>T26N R15E</p> <table style="margin: auto; border-collapse: collapse;"> <tr> <td style="border-right: 1px solid black; padding: 2px 5px;">S30</td> <td style="padding: 2px 5px;">S29</td> </tr> <tr> <td style="border-right: 1px solid black; padding: 2px 5px;">S31</td> <td style="padding: 2px 5px;">S32</td> </tr> </table> <p>2002</p> </div>	S30	S29	S31	S32
S30	S29				
S31	S32				

**Dependent Resurvey of the Subdivisional Lines,
T. 26 N., R. 15 E., Gila and Salt River Meridian, Arizona**

CHAINS	
40.02	<p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p> <hr/> <p>From the cor. of secs. 28, 29, 32 and 33.</p> <p>Over rolling sandy land covered with scattered grasses.</p> <p>N. 89°59' W., bet. secs. 29 and 32.</p> <p>The 1/4 sec. cor. of secs. 29 and 32, monumented with an iron post, 1 in. diam., loosely set, projecting 9 ins. above ground, badly rusted, with brass cap mkd. 1/4 S29 S32 1909.</p> <p>At the corner point</p> <p>Set a stainless steel post, 28 ins. long, 2½ ins. diam., 27 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center; margin: 10px 0;"> <p>T26N R15E</p> <p>S29</p> <p>1/4 ———</p> <p>S32</p> <p>2002</p> </div> <p>Deposit a magnet in a white plastic case at the base of the stainless steel post and place the iron post inside it.</p> <p>Set a steel fence post 3 ft. N. of cor.</p> <hr style="width: 20%; margin: 10px auto;"/> <p>West, beginning new measurement.</p>
39.70	Center line of Arizona Highway 87, 30 ft. wide, bears N. 40° E. and S. 40° W.
40.02	The cor. of secs. 29, 30, 31 and 32.
40.00	<p>N. 89°54' W., bet. secs. 30 and 31.</p> <p>Over rolling sandy land covered with scattered grasses.</p> <p>The 1/4 sec. cor. of secs. 30 and 31, monumented with an iron post, 1 in. diam., firmly set, projecting 6 ins. above ground, with brass cap mkd. 1/4 S30 S31 1909.</p> <p>Add the marks T26N R15E 2002 to the brass cap.</p>

**Dependent Resurvey of the Subdivisional Lines,
T. 26 N., R. 15 E., Gila and Salt River Meridian, Arizona**

CHAINS	
40.72	<p>Set a steel fence post 3 ft. N. of cor.</p> <hr style="width: 30%; margin-left: auto; margin-right: auto;"/> <p>S. 89°59' W., bet. secs. 30 and 31.</p> <p>The cor. of secs. 25, 30, 31 and 36, on the W. bdy. of the Tp., hereinbefore described.</p> <hr/>
40.00	<p>From the cor of 29, 30, 31 and 32.</p> <p>N. 0°01' E., bet. secs. 29 and 30.</p> <p>Over rolling sandy terrain covered with scattered grasses.</p> <p>The 1/4 sec. cor of secs. 29 and 30, monumented with an iron post, 1 in. diam., firmly set, projecting 7 ins. above ground, with brass cap mkd. S30 1/4 S29 1909.</p> <p>Add the marks T26N R15E 2002 to the brass cap.</p> <p>Set a steel fence post 3 ft. N. of cor.</p> <hr style="width: 30%; margin-left: auto; margin-right: auto;"/>
40.02	<p>N. 0°01' W., beginning new measurement.</p> <p>The cor. of secs. 19, 20, 29 and 30, monumented with an iron post, 2 ins. diam., firmly set, projecting 6 ins. above ground, with brass cap mkd. T26N R15E S19 S20 S30 S29 1909.</p> <p>Add the marks 2002 to the brass cap.</p> <p>Set a steel fence post 3 ft. N. of cor.</p> <hr/>
40.01	<p>From the cor. of secs. 20, 21, 28 and 29.</p> <p>S. 89°59' W., bet. secs. 20 and 29.</p> <p>Over level sandy land covered with scattered grasses.</p> <p>Point for the 1/4 sec. cor. of secs. 20 and 29, at proportionate dist.; there is no remaining evidence of the original cor.</p> <p>Set a stainless steel post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.</p>

**Dependent Resurvey of the Subdivisional Lines,
T. 26 N., R. 15 E., Gila and Salt River Meridian, Arizona**

CHAINS	
	T26N R15E S20 1/4 ————— S29 2002
	Deposit a magnet in a white plastic case at the base of the stainless steel post. Set a steel fence post 3 ft. N. of cor.
56.40	Center line of Arizona Highway 87, 30 ft. wide, bears N. 10° E. and S. 10° W.
80.02	The cor. of secs. 19, 20, 29 and 30.
	N. 89°58' W., bet. secs. 19 and 30. Over rolling sandy land covered with scattered grasses.
40.03	Point for the 1/4 sec. cor. of secs. 19 and 30, at proportionate dist.; there is no remaining evidence of the original cor. Set a stainless steel post, 28 ins. long, 2½ ins. diam., 22 ins. in the ground, with brass cap mkd.
	T26N R15E S19 1/4 ————— S30 2002
	Deposit a magnet in a white plastic case at the base of the stainless steel post. Set a steel fence post 3 ft. N. of cor.
80.69	The cor. of secs. 19, 24, 25 and 30, on the W. bdy of the Tp., hereinbefore described.
	From the cor. of secs. 19, 20, 29 and 30. N. 0°01' W., bet. secs. 19 and 20.

**Dependent Resurvey of the Subdivisional Lines,
T. 26 N., R. 15 E., Gila and Salt River Meridian, Arizona**

CHAINS	
	Over rolling sandy land covered with scattered grasses.
40.02	<p>The 1/4 sec. cor. of secs. 19 and 20, monumented with an iron post, 1 in. diam., firmly set, projecting 8 ins. above ground, with brass cap mkd. S19 1/4 S20 1909.</p> <p>Add the marks T26N R15E 2002 to the brass cap.</p> <p>Drove iron post flush with the ground.</p> <p>Set a steel fence post 3 ft. N. of cor.</p> <hr style="width: 20%; margin-left: auto; margin-right: auto;"/> <p>N. 0°02' W., beginning new measurement.</p>
40.01	<p>The cor. of secs. 17, 18, 19 and 20, monumented with an iron post, 2 ins. diam., firmly set, projecting 9 ins. above ground, with brass cap mkd. T26N R15E S18 S17 S19 S20 1909.</p> <p>Add the marks 2002 to the brass cap.</p> <p>Set a steel fence post 3 ft. N. of cor.</p> <hr/> <p>From the cor. of secs. 16, 17 20 and 21.</p> <p>N. 89°59' W., bet. secs. 17 and 20.</p> <p>Over level sandy land covered with scattered grasses.</p>
13.20	Center line of Arizona Highway 87, 30 ft. wide, bears N. 30° E. and S. 30° W.
40.03	<p>The 1/4 sec. cor. of secs. 17 and 20, monumented with an iron post, 1 in. diam., firmly set, 3 ins. below ground, with brass cap mkd. S17 1/4 S20 1909.</p> <p>Add the marks T26N R15E 2002 to the brass cap.</p> <hr style="width: 20%; margin-left: auto; margin-right: auto;"/> <p>S. 89°57' W., beginning new measurement.</p>
24.64	Point for crossing closing cor. bet. secs. 17 and 20, at intersection with the boundary of Management District No. 6, Hopi Indian Reservation, hereinafter described.
39.96	<p>The cor. of secs. 17, 18, 19 and 20.</p> <hr/> <p>N. 89°59' W., bet. secs. 18 and 19.</p>

**Dependent Resurvey of the Subdivisional Lines,
T. 26 N., R. 15 E., Gila and Salt River Meridian, Arizona**

CHAINS	
39.99	<p>Point for the 1/4 sec. cor. of secs. 18 and 19, at proportionate dist.; there is no remaining evidence of the original cor.</p> <p>Set a stainless steel post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T26N R15E</p> <p style="text-align: center;">S18 1/4 ——— S19</p> <p style="text-align: center;">2002</p> <p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p> <p>Set a steel fence post 3 ft. N. of cor.</p>
80.64	<p>The cor. of secs. 13, 18, 19 and 24, on W. bdy. of the Tp. hereinbefore described.</p> <hr/> <p>From the cor. of secs. 17, 18, 19 and 20.</p> <p>N. 0°02' W., bet. secs. 17 and 18.</p> <p>Over rolling sandy land covered with scattered grasses.</p>
14.89	<p>Point for crossing closing cor. bet. secs. 17 and 18, at intersection with the boundary of Management District No. 6, Hopi Indian Reservation, hereinafter described.</p>
40.02	<p>The 1/4 sec. cor. of secs. 17 and 18, monumented with an iron post, 1 in. diam., firmly set, 6 ins. below ground, rusted badly, with brass cap mkd. S18 1/4 S17 1909..</p> <p>At the corner point</p> <p>Set a stainless steel post, 28 ins. long, 2½ ins. diam., 20 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T26N R15E</p> <p style="text-align: center;">1/4 S18 S17</p> <p style="text-align: center;">2002</p>

Dependent Resurvey of the Subdivisional Lines,
T. 26 N., R. 15 E., Gila and Salt River Meridian, Arizona

CHAINS	
	<p>Deposit a magnet in a white plastic case at the base of the stainless steel post and place the iron post inside it.</p> <hr/> <p>N. 0°03' W., beginning new measurement.</p>
39.99	<p>The cor. of secs. 7, 8, 17 and 18, monumented with an iron post, 2 ins. diam., firmly set, projecting 13 ins. above ground, with an accessory mound of stone, 3 ft. base, 2 ft. high, W. of cor., with brass cap mkd. T26N R15E S7 S8 S18 S17 1909.</p> <p>Add the marks 2002 to the brass cap.</p> <hr/>
	<p>From the cor. of secs. 8, 9, 16 and 17.</p> <p>S. 89°57' W., bet. secs. 8 and 17.</p> <p>Over rolling sandy land covered with scattered grasses.</p>
40.02	<p>The 1/4 sec. cor. of secs. 8 and 17, monumented with an iron post, 1 in. diam., firmly set, projecting 6 ins. above ground, with brass cap mkd. S8 1/4 S17 1909.</p> <p>Add the marks T26N R15E 2002 to the brass cap.</p> <hr/>
	<p>S. 89°57' W., beginning new measurement.</p>
40.01	<p>The cor. of secs. 7, 8, 17 and 18.</p> <hr/> <p>S. 89°59' W., bet. secs. 7 and 18.</p> <p>Over rolling sandy land covered with scattered grasses.</p>
39.97	<p>Point for the 1/4 sec. cor. of secs. 7 and 18, at proportionate dist.; there is no remaining evidence of the original cor.</p> <p>True point falls on an eroding sandy slope, where it is impracticable to establish a permanent monument.</p> <p>From this point, point selected for the witness 1/4 sec. cor. of secs. 7 and 18 bears N. 45°01' W., 1.00 ch. dist.</p> <p>At the witness point set a stainless steel post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.</p>

Dependent Resurvey of the Subdivisional Lines,
T. 26 N., R. 15 E., Gila and Salt River Meridian, Arizona

CHAINS	
	<p style="text-align: center;">WC T26N R15E S7 1/4 ————— S18 ↘ 2002</p>
	<p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p>
	<p>Cor. is located on top of a sandy ridge, 50 ft. wide, bears N. 40° E. and S. 50° W.</p>
67.09	<p>Point for crossing closing cor. bet. secs. 7 and 18, at intersection with the boundary of Management District No. 6, Hopi Indian Reservation, hereinafter described.</p>
80.53	<p>The cor. of secs. 7, 12, 13 and 18, on the W. bdy. of the Tp., hereinbefore described.</p> <hr/>
	<p>From the cor. of secs. 7, 8, 17 and 18. N. 0°06' W., bet. secs. 7 and 8. Over rolling sandy land covered with scattered grasses.</p>
40.02	<p>The 1/4 sec. cor. of secs. 7 and 8, monumented with an iron post, 1 in. diam., firmly set, projecting 6 ins. above ground, with brass cap mkd. S7 1/4 S8 1909. Add the marks T26N R15E 2002 to the brass cap.</p> <hr/>
	<p>N. 0°07' W., beginning new measurement.</p>
40.02	<p>The cor. of secs. 5, 6, 7 and 8, monumented with an iron post, 20 ins. diam., firmly set, projecting 8 ins. above ground, with brass cap mkd. T26N R15E S6 S5 S7 S8 1909. Add the marks 2002 to the brass cap.</p> <hr/>
	<p>From the cor. of secs. 4, 5, 8 and 9. N. 89°58' W., bet. secs. 5 and 8. Over rolling sandy land covered with scattered grasses.</p>



**Dependent Resurvey of the Subdivisional Lines,
T. 26 N., R. 15 E., Gila and Salt River Meridian, Arizona**

CHAINS	
40.04	<p>The 1/4 sec. cor. of secs. 5 and 8, monumented with an iron post, 1 in. diam., firmly set, projecting 6 ins. above ground, with brass cap mkd. S5 1/4 S8 1909.</p> <p>Add the marks 2002 to the brass cap.</p> <hr style="width: 30%; margin: 10px auto;"/> <p>N. 89°57' W., beginning new measurement.</p>
40.07	<p>The cor. of secs. 5, 6, 7 and 8.</p> <hr/> <p>S. 89°56' W., bet. secs. 6 and 7.</p> <p>Over rolling sandy land covered with scattered grasses.</p>
39.99	<p>Point for the 1/4 sec. cor. of secs. 6 and 7, at proportionate dist.; there is no remaining evidence of the original cor.</p> <p>Set a stainless steel post, 28 ins. long, 2½ ins. diam., 25 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T26N R15E</p> <p style="text-align: center;">S6</p> <p style="text-align: center;">1/4 ———</p> <p style="text-align: center;">S7</p> <p style="text-align: center;">2002</p> <p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p>
80.37	<p>The cor. of secs. 1, 6, 7 and 12, on the W. bdy. of the Tp. hereinbefore described.</p> <hr/> <p>From the cor. of secs. 5, 6, 7 and 8.</p> <p>N. 0°09' W., bet. secs. 5 and 6.</p> <p>Over rolling sandy land covered with scattered grasses.</p>
40.01	<p>Point for the 1/4 sec. cor. of secs. 5 and 6, at proportionate dist.; there is no remaining evidence of the original cor.</p> <p>Set a stainless steel post, 28 ins. long, 2½ ins. diam., 23 ins. in the ground, with brass cap mkd.</p>

**Dependent Resurvey of the Subdivisional Lines,
T. 26 N., R. 15 E., Gila and Salt River Meridian, Arizona**

CHAINS	
79.84	<p align="center">T26N R15E 1/4 S6 S5 2002</p> <p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p> <p>The cor. of 5, 6, 31 and 32, on the N. bdy. of the Tp. monumented with an iron post, 3 ins. diam., firmly set, projecting 6 ins. above ground, with brass cap mkd. T27N R15E S31 S32 S6 S5 T26N 2002.</p> <hr/> <p align="center">Dependent Resurvey of a Portion of the Boundary, Management District No. 6, Hopi Indian Reservation, T. 26 N., R. 15 E., Gila and Salt River Meridian, Arizona</p> <hr/> <p align="center">Restoring the survey executed by Leonard W. Murphy and Wallace R. Ott, in 1963-1964</p> <hr/> <p>From cor. MP 114½, monumented with an iron post, 2 1/2 ins. diam., firmly set, projecting 7 ins. above ground, with brass cap mkd. MP 114½ HOPI 1964. Add the marks 2002 to the brass cap. Cor. is located 6 lks., E., of a 5 strand barbed wire fence, bears S. 46° E. and N. 46° W.</p> <p>N. 45°49' W., along a portion of the 115th mile.</p>
1.08	<p>Angle Point 496, at grant boundary adjustment, not monumented.</p> <hr/> <p>N. 45°27' W., beginning new measurement.</p>
19.40	<p>Angle Point 497, at grant boundary adjustment, not monumented.</p> <hr/> <p>N. 45°54' W., beginning new measurement.</p>
8.94	<p>Point for crossing closing cor. bet. secs. 2 and 35, at intersection with the boundary of Management District No. 6, Hopi Indian Reservation.</p>


Dependent Resurvey of a Portion of the Boundary,
 Management District No.6, Hopi Indian Reservation,
 T. 26 N., R. 15 E., Gila and Salt River Meridian, Arizona

CHAINS	
19.52	<p>Set a stainless steel post, 28 ins. long, 2½ ins. diam., 28 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center;">  </div> <p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p>
21.92	<p>The 115 mile cor., monumented with an iron post, 2 1/2 ins. diam., firmly set, projecting 6 ins. above ground, with brass cap mkd. MP 115 HOPI 1964. Add the marks 2002 to the brass cap. Cor. is alongside a 5 strand barbed wire fence, bears S. 46° E. and N. 46° W.</p> <hr/> <p>N. 45°54' W., along the 116th mile.</p> <p>Point for crossing closing cor. bet. secs. 34 and 35, at intersection with the boundary of Management District No. 6, Hopi Indian Reservation.</p>
39.99	<p>Set a stainless steel post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center;">  </div> <p>Cor. is located 2 lks. W. of a 5 strand barbed wire fence, bears S. 46' E and N. 46' W.</p> <p>The 115½ mile cor., monumented with an iron post, 2 1/2 ins. diam., firmly set, projecting 6 ins. above ground, with brass cap mkd. MP 115½ HOPI 1964. Add the marks 2002 to the brass cap. Cor. is located 5 lks., E., of a 5 strand barbed wire fence, bears S. 46' E. and N. 46' W.</p> <hr/> <p>N. 45°53' W., beginning new measurement.</p>



**Dependent Resurvey of a Portion of the Boundary,
Management District No.6, Hopi Indian Reservation,
T. 26 N., R. 15 E., Gila and Salt River Meridian, Arizona**

CHAINS	
40.00	<p>The 116 mile cor., monumented with an iron post, 2 1/2 ins. diam., firmly set, projecting 6 ins. above ground, with brass cap mkd. MP 116 HOPI 1964. Add the marks 2002 to the brass cap. Cor. is located 7 lks. W. of a 5 strand barbed wire fence, bears S. 46° E. and N. 46° W.</p> <hr/> <p>N. 45°52' W., along the 117th mile.</p>
24.61	<p>Point for crossing closing cor. bet. secs. 27 and 34, at intersection with the boundary of Management District No. 6, Hopi Indian Reservation.</p> <p>Set a stainless steel post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T26N R15E</p> <div style="text-align: center;"> <p>S27 S34 CCC 2002</p> </div> <p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p> <p>Cor. is located 6 lks. W. of a 5 strand barbed wire fence, bears S. 46° E. and N. 46° W.</p>
39.99	<p>The 116½ mile cor., monumented with an iron post, 2 1/2 ins. diam., firmly set, projecting 10 ins. above ground, with brass cap mkd. MP 116½ HOPI 1964. Add the marks 2002 to the brass cap. Cor. is located 7 lks. E. of a 5 strand barbed wire fence, bears S. 46° E. and N. 46° W.</p> <hr/> <p>N. 45°54' W., beginning new measurement.</p>
13.44	<p>Point for crossing closing cor. bet. secs. 27 and 28, at intersection with the boundary of Management District No. 6, Hopi Indian Reservation.</p> <p>Set a stainless steel post, 28 ins. long, 2½ ins. diam., 26 ins. in the ground, with brass cap mkd.</p>


**Dependent Resurvey of a Portion of the Boundary,
Management District No. 6, Hopi Indian Reservation,
T. 26 N., R. 15 E., Gila and Salt River Meridian, Arizona**

CHAINS	
	<p>T26N R15E</p>  <p>CCC 2002</p>
	<p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p> <p>Cor. is located 7 lks. E. of a 5 strand barbed wire fence, bears S. 46' E. and N. 46' W.</p>
40.00	<p>Point for the 117 mile cor., the original iron post, 2½ ins. diam., 29 ins. long, mkd. MP 117 HOPI 1964, was found set on top of a fence post of the Hopi Management District No. 6, fence line, at grant boundary adjustment.</p> <p>Set original iron post, 24 ins. in the ground and add the marks 2002 to the brass cap.</p> <p>Deposit a magnet in a white plastic case at the base of the iron post.</p> <hr/> <p>N. 46°01' W., along the 118th mile.</p>
40.00	<p>Point for the 117½ mile cor., the original iron post, 2½ ins. diam., 29 ins. long, mkd. MP 117½ HOPI 1964, was found lying loose on the ground nearby, at grant boundary adjustment.</p> <p>Set original iron post, 26 ins. in the ground and add the marks 2002 to the brass cap.</p> <p>Deposit a magnet in a white plastic case at the base of the iron post.</p> <p>Cor. is located alongside a 5 strand barbed wire fence, bears S. 46' E. and N. 46' W.</p> <hr/> <p>N. 46°01' W., beginning new measurement.</p>
19.94	<p>Point for crossing closing cor. bet. secs. 21 and 28, at intersection with the boundary of Management District No. 6, Hopi Indian Reservation.</p> <p>Set a stainless steel post, 28 ins. long, 2½ ins. diam., 28 ins. in the ground, with brass cap mkd.</p>


Dependent Resurvey of a Portion of the Boundary,
 Management District No.6, Hopi Indian Reservation,
 T. 26 N., R. 15 E., Gila and Salt River Meridian, Arizona

CHAINS	
40.00	<div style="text-align: center;"> <p>T26N R15E</p>  <p>CCC 2002</p> </div> <p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p> <p>Cor. is located 5 lks. E. of a 5 strand barbed wire fence, bears S. 46° E. and N. 46° W.</p> <p>The 118 mile cor., monumented with an iron post, 2 1/2 ins. diam., firmly set, projecting 7 ins. above ground, with brass cap mkd. MP 118 HOPI 1964. Add the marks 2002 to the brass cap. Cor. is located 9 lks. E. of a 5 strand barbed wire fence, bears S. 46° E. and N. 46° W.</p>
4.70	<hr/> <p>N. 46°01' W., along the 119th mile.</p> <p>Point for crossing closing cor. bet. secs. 20 and 21, at intersection with the boundary of Management District No. 6, Hopi Indian Reservation.</p> <p>Set a stainless steel post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center;"> <p>T26N R15E</p>  <p>CCC 2002</p> </div> <p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p> <p>Cor. is located 9 lks. E. of a 5 strand barbed wire fence, bears S. 46° E. and N. 46° W.</p>
10.59	<hr/> <p>Angle Point 499, at grant boundary adjustment, not monumented.</p> <hr/> <p>N. 45°43' W., beginning new measurement.</p>



Dependent Resurvey of a Portion of the Boundary,
Management District No.6, Hopi Indian Reservation,
T. 26 N., R. 15 E., Gila and Salt River Meridian, Arizona

CHAINS	
29.36	<p>The 118½ mile cor., monumented with an iron post, 2 1/2 ins. diam., firmly set, flush with the ground, with brass cap mkd. MP 118½ HOPI 1964. Add the marks 2002 to the brass cap. Cor. is located alongside a 5 strand barbed wire fence, bears S. 46' E. and N. 46' W.</p> <hr style="width: 30%; margin: 10px auto;"/>
	<p>N. 45°53' W., beginning new measurement.</p>
8.85	<p>Point for witness point on the management district boundary, there is no remaining evidence of the original cor., at grant boundary adjustment, not monumented.</p>
40.01	<p>Point for the 119 mile cor., the original iron post, 2½ ins. diam., 29 ins. long, mkd. MP 119 HOPI 1963, was found lying loose on the ground nearby, at grant boundary adjustment.</p> <p>Set original iron post, 24 ins. in the ground and add the marks 2002 to the brass cap.</p> <p>Deposit a magnet in a white plastic case at the base of the iron post.</p> <p>Cor. is located alongside a 5 strand barbed wire fence, bears S. 46' E. and N. 46' W</p> <hr style="width: 30%; margin: 10px auto;"/>
	<p>N. 45°53' W., along the 120th mile.</p>
14.96	<p>Point for crossing closing cor. bet. secs. 17 and 20, at intersection with the boundary of Management District No. 6, Hopi Indian Reservation.</p> <p>Set a stainless steel post, 28 ins. long, 2½ ins. diam., 25 ins. in the ground, with brass cap mkd.</p>
	<div style="text-align: center;"> <p>T26N R15E</p>  </div>
	<p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p>
	<p>Cor is located, 11 lks. E. of a 5 strand barbed wire fence, bears S. 46' E and N. 46' W.</p>

Dependent Resurvey of a Portion of the Boundary,
Management District No.6, Hopi Indian Reservation,
T. 26 N., R. 15 E., Gila and Salt River Meridian, Arizona

CHAINS	
36.32	<p>Point for crossing closing cor. bet. secs. 17 and 18, at intersection with the boundary of Management District No. 6, Hopi Indian Reservation.</p> <p>Set a stainless steel post, 28 ins. long, 2½ ins. diam., 25 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T26N R15E</p> <div style="text-align: center;">  </div> <p style="text-align: center;">CCC 2002</p> <p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p> <p>Cor is located, 4 lks. E. of a 5 strand barbed wire fence, bears S. 46° E and N. 46° W.</p>
40.01	<p>Point for the 119½ mile cor., the original iron post, 2½ ins. diam., 29 ins. long, mkd. MP 119½ HOPI 1963, was found projecting 22 ins above ground, loosely set nearby, at grant boundary adjustment.</p> <p>Set original iron post, 24 ins. in the ground and add the marks 2002 to the brass cap.</p> <p>Deposit a magnet in a white plastic case at the base of the iron post.</p> <p>Cor. is located alongside a 5 strand barbed wire fence, bears S. 46° E. and N. 46° W</p> <hr style="width: 30%; margin: 10px auto;"/> <p>N. 45°53' W., beginning new measurement.</p>
40.01	<p>The 120th mile cor., monumented with an iron post, 2 1/2 ins. diam., firmly set, projecting 9 ins. above ground, with brass cap mkd. MP 120 HOPI 1964. Add the marks 2003 to the brass cap. Cor. is located alongside a 5 strand barbed wire fence, bears S. 46° E. and N. 46° W.</p> <hr style="width: 60%; margin: 10px auto;"/> <p>N. 45°53' W., along the 121st mile.</p>

**Dependent Resurvey of a Portion of the Boundary,
Management District No.6, Hopi Indian Reservation,
T. 26 N., R. 15 E., Gila and Salt River Meridian, Arizona**

CHAINS	
40.00	<p>The 120½ mile cor., monumented with an iron post, 2 1/2 ins. diam., firmly set, projecting 10 ins. above ground, with brass cap mkd. MP 120½ HOPI 1964. Add the marks 2002 to the brass cap. Cor. is located 18 lks. E. of a 5 strand barbed wire fence, bears S. 46' E. and N. 46' W.</p> <hr style="width: 20%; margin: 10px auto;"/> <p>N. 45°54' W., beginning new measurement.</p>
9.83	<p>Point for crossing closing cor. bet. secs. 7 and 18, at intersection with the boundary of Management District No. 6, Hopi Indian Reservation.</p> <p>Set a stainless steel post, 28 ins. long, 2½ ins. diam., 26 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center;"> <p>T26N R15E</p>  <p>S7</p> <p>18</p> <p>CCC 2002</p> </div> <p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p> <p>Cor. is located alongside a 5 strand barbed wire fence, bears S. 46' E. and N. 46' W.</p>
28.55	<p>Point for crossing closing cor. bet. secs. 7 and 12, at intersection with the boundary of Management District No. 6, Hopi Indian Reservation.</p> <p>Set a stainless steel post, 28 ins. long, 2½ ins. diam., 22 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center;"> <p>T26N R14E R15E</p>  <p>S12</p> <p>S7</p> <p>CCC 2002</p> </div> <p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p>

**Dependent Resurvey of a Portion of the Boundary,
Management District No.6, Hopi Indian Reservation,
T. 26 N., R. 15 E., Gila and Salt River Meridian, Arizona**

<p>CHAINS</p> <p>40.00</p>	<p>The 121 mile cor., monumented with an iron post, 2 1/2 ins. diam., firmly set, projecting 6 ins. above ground, with brass cap mkd. MP 121 HOPI 1964. Add the marks 2002 to the brass cap. Cor. is located 15 lks., E., of a 5 strand barbed wire fence, bears S. 46° E. and N. 46° W.</p> <hr/> <p style="text-align: center;">GENERAL DESCRIPTION</p> <hr/> <p>This survey is located near Kykotsmovi, Arizona. Elevations range from about 5000 to 6000 ft. above sea level.</p> <p>The land is rolling to broken story mesas with scattered grasses.</p> <p>Access is by way of Interstate 40 and Arizona Highway 87.</p> <p>The mean magnetic declination of 12° E. was derived from the United States Geological Survey computer program GEOMAG, utilizing the World Magnetic Model for Epoch 2000 for the dates of survey.</p> <hr/>
----------------------------	-----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------

CERTIFICATE OF SURVEY

I, Adrien J. Rodriguez, Cadastral Surveyor, HEREBY CERTIFY upon honor, that in pursuance of special instructions bearing date of the 16th day of July, 2002, I have dependently resurveyed the east, south and west boundaries, the subdivisional lines and a portion of the Boundary, Management District No. 6, Hopi Indian Reservation, T. 26 N., R. 15 E., Gila and Salt River Meridian, Arizona, which are represented in the foregoing field notes as having been executed by me and under my direction. Said survey has been made in strict conformity with said special instructions, the Manual of Instructions for the Survey of the Public Lands of the United States, and in specific manner described in the foregoing field notes.

DECEMBER 8th, 2004
(Date)

Adrien J. Rodriguez
(Cadastral Surveyor)

CERTIFICATE OF APPROVAL

BUREAU OF LAND MANAGEMENT
Phoenix, Arizona

The foregoing field notes of the dependent resurvey of the east, south and west boundaries, the subdivisional lines and a portion of the Boundary, Management District No. 6, Hopi Indian Reservation, T. 26 N., R. 15 E., Gila and Salt River Meridian, Arizona, executed by Adrien J. Rodriguez, Cadastral Surveyor, having been critically examined and found correct, are hereby approved.

Jan. 4, 2005
(Date)

Stephen K. Hansen
(Acting Chief Cadastral Surveyor of Arizona)

~~CERTIFICATE OF TRANSCRIPT~~

~~I CERTIFY That the foregoing transcript of the field notes of the above described surveys in T. 26 N., R. 15 E., Gila and Salt River Meridian, Arizona, is a true copy of the original field notes.~~

~~_____~~
(Date)

~~_____~~
(Acting Chief Cadastral Surveyor of Arizona)