

ORIGINAL

**UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT**

FIELD NOTES
OF THE
DEPENDENT RESURVEY OF A PORTION OF THE SOUTH BOUNDARY
AND
THE SURVEY OF THE EAST BOUNDARY
AND
THE SUBDIVISIONAL LINES

TOWNSHIP 26 NORTH, RANGE 21 EAST,
OF THE GILA AND SALT RIVER MERIDIAN,
IN THE STATE OF ARIZONA.

EXECUTED BY

**W. William Foster, Cadastral Surveyor
Jones Curtiss, Cadastral Surveyor**

Under Special Instructions dated November 12, 2002, approved November 12, 2002, which provided for the surveys included under Group No. 898, and assignment instructions dated November 12, 2002.

Survey commenced November 18, 2002

Survey completed June 11, 2003

INDEX DIAGRAM

TOWNSHIP 26 NORTH

RANGE 21 EAST

6	63 5	49 4	40 3	31 2	21 1 12
62	61	49	40	30	20
7	60 8	48 9	39 10	29 11	19 12 10
59	59	47	38	28	18
18	57 17	46 16	36 15	26 14	16 13 9
56	56	45	36	25	16
19	55 20	44 21	35 22	25 23	15 24 8
54	53	44	34	24	15
30	52 29	43 28	33 27	23 26	14 25 7
52	51	42	33	22	13
31	50 32	41 33	32 34	21 35	12 36 6
			5	4	4

T 26 N., R. 21 E., Gila and Salt River Meridian, Arizona

CHAINS

The following field notes describe the dependent resurvey of a portion of the south boundary and the survey of the east boundary and the subdivisional lines, Township 26 North, Range 21 East, Gila and Salt River Meridian.

The history of surveys pertaining to this survey is as follows:

Sidney E. Blout surveyed the S. bdy in 1910. Kenneth A. Krenke, Shirley B. Hjellum and Marvin T. Koppang dependently resurveyed a portion of the south boundary in 1977-78. Kenneth A. Krenke, Shirley B. Hjellum and Marvin T. Koppang surveyed the Hopi-Navajo Partition Line Segment "A" in 1977 - 1979. Geoffery A. Graham resurveyed a portion of the 5th Guide Meridian East (West Boundary) in 2002. Adrien J. Rodriguez surveyed the north boundary in 2002.

The survey was executed in accordance with the specifications as set forth in the Manual of Instructions for the Survey of the Public Lands of the United States, 1973, and the Special Instructions dated November 12, 2002, for Group No. 898, Arizona.

The true meridian direction and length of all lines were determined by real time kinematic global positioning system observations using Trimble Navigation 4700 model receivers.

Preliminary to the survey and resurvey, the lines of the prior surveys were retraced and search was made for all corners and other calls of record. Identified corners were remonumented in their original positions. Lost corners were reestablished and remonumented at proportionate positions based on the official record. The retracement data were thoroughly verified and only the true line field notes are given herein.

Geodetic control was derived from Global Positioning System (GPS) static observations, post processed by National Geodetic Survey, Online Positioning User Service (OPUS), utilizing Continuously Operating Reference Stations (CORS) PIETOWN, (CORS) FLAGSTAFF 1 AND (CORS) SCOTTSDALE. The NAD 83(CORS96), geographic position of southeast corner of the township is as follows:

Latitude: 35°36'18.42" N. Longitude: 110°02'26.62" W.

The mean magnetic declination is 11 3/4° E.

**Dependent Resurvey of a Portion of the South Boundary
T 26 N., R. 21 E., Gila and Salt River Meridian, Arizona**

CHAINS

Restoring the survey executed by
Sidney E. Blout, in 1910

Beginning at the cor. of Tps. 25 and 26 N., Rgs. 21 and 22 E.,
monumented with an iron post, 3 ins. diam., firmly set,
projecting 13 ins. above the ground, with brass cap mkd. T26N
R21E R22E S36 S31 S1 S6 R21E R22E T25N 1910.

Add the marks 2002 to the brass cap.

N. 89°53' W., bet. secs. 1 and 36, on the S. bdy. of the Tp.

Over level land through scattered grasses.

40.01 Point for the 1/4 sec. cor. of secs. 1 and 36 at proportionate
dist., there is no remaining evidence of the original cor.

Set a stainless steel post, 28 ins. long, 2½ ins. diam., 24 ins.
in the ground, with brass cap mkd.

T 26 N R 21 E
S 36
1/4 ———
S 1
T 25 N

2002

Deposit a magnet in a white plastic case at the base of the
stainless steel post.

80.02 The cor. of secs. 1, 2, 35 and 36, monumented with an iron post,
3 ins. diam., loosely set, projecting 18 ins. above the ground.

At the corner point

Set a stainless steel post, 28 ins. long, 2½ ins. diam., 24 ins.
in the ground, with brass cap mkd.

T 26 N R 21 E
S 35 | S 36
S 2 | S 1
T 25 N

2002

Deposit a magnet in a white plastic case at the base of the
stainless steel post.

N. 89°53' W., bet. secs. 2 and 35, on the S. bdy. of the Tp.

**Dependent Resurvey of a Portion of the South Boundary
T 26 N., R. 21 E., Gila and Salt River Meridian, Arizona**

CHAINS	
	Over level land, through scattered native grasses.
25.75	Graded road, 25 ft. wide , bears S. 49° E., and N. 49° W.
40.02	Point for the 1/4 sec. cor. of secs. 2 and 35 at proportionate dist., there is no remaining evidence of the original cor. Set a stainless steel post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd. <div style="text-align: center;"> T 26 N R 21 E S 35 1/4 ——— S 2 T 25 N 2002 </div>
	Deposit a magnet in a white plastic case at the base of the stainless steel post.
	Cor. located 1.65 chs. S. of highway (NR9062), 30 ft. wide, bears ESE and WNW.
41.23	Barbed wire fence, bears N. and S.
42.74	Center line State Highway No. 7, 25 ft. wide, bears N. 10° E. and S. 10° W.
44.29	Barbed wire fence, bears N. and S.
80.04	The cor. of secs. 2, 3, 34 and 35, monumented with an iron post, 3 ins. diam, firmly set, projecting 10 ins. above the ground, with brass cap mkd. R21E T26N T25N S35 S2 S34 S3 1911. Cap is oriented incorrectly. Remark the brass cap to read T26N R21E S34 S35 1911 S3 S2 T25N 2002. Cor. located beneath a 5 strand barbed wire fence, bears N. and S.

	N. 89°54' W., bet. secs. 3 and 34, on the S. bdy of the Tp.
40.01	Point for the 1/4 sec. cor of secs. 3 and 34 at proportionate dist., the original iron post, 1 in. diam., 36 ins. long was found laying loose on the ground. Set a stainless steel post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.

**Dependent Resurvey of a Portion of the South Boundary
T 26 N., R. 21 E., Gila and Salt River Meridian, Arizona**

CHAINS	
	<p align="center">T 26 N R 21 E S 34 1/4 ——— S 3 T 25 N</p> <p align="center">2002</p>
80.02	<p>Deposit a magnet in a white plastic case at the base of the stainless steel post, and bury the iron post alongside.</p> <p>The cor. of secs. 3, 4, 33 and 34, monumented with an iron post, 3 ins. diam., firmly set, projecting 4 ins. above the ground, with brass cap mkd. R21E T26N T25N S34 S3 S33 S4 1910. Cap is oriented incorrectly. Remark cap to read T26N R21E S33 S34 S4 S3 1910 2002.</p>
	<p align="center">Survey of the East Boundary, T. 26 N., R. 21 E., Gila and Salt River Meridian, Arizona</p>
40.00	<p>From the cor. of Tps. 25 and 26, Rgs. 21 and 22 E., hereinbefore described.</p> <p>North, bet. secs. 31 and 36, on the E. bdy of the Tp.</p> <p>Over level land, through scattered native grasses.</p>
80.00	<p>Point for the 1/4 sec. cor. of secs. 31 and 36.</p> <p>Set a stainless steel post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.</p>
	<p align="center">T 26 N R 21 E R 22 E 1/4 S 36 S 31</p> <p align="center">2002</p>
80.00	<p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p> <p>Point for the cor. of secs. 25, 31, 31 and 36.</p> <p>Set a stainless steel post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.</p>

Survey of the East Boundary
T 26 N., R. 21 E., Gila and Salt River Meridian, Arizona

CHAINS	
	T 26 N R 21 E R 22 E S 25 S 30 ----- S 36 S 31
	2002
	Deposit a magnet in a white plastic case at the base of the stainless steel post.
	Land, level. Soil, sandy. Undergrowth, native grasses.

	North, bet. secs. 25 and 30.
	Over level land, through scattered native grasses.
40.00	Point for the 1/4 sec. cor. of secs. 25 and 30.
	Set a stainless steel post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.
	T 26 N R 21 E R 22 E 1/4 S 25 S 30
	2002
	from which
	The SW cor. of a stucco house, 42 ft. X 32 ft., bears N. 31°15' E., 77 lks. dist., long side bears NNE.
	The NE cor. of a stucco house, 54 ft. X 30 ft., bears S. 34°44' W., 1.39 chs. dist., long side bears SSW.
	Deposit a magnet in a white plastic case at the base of the stainless steel post.
80.00	Point for the cor. of secs. 19, 24, 25 and 30.
	Set a stainless steel post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.

Survey of the East Boundary
T 26 N., R. 21 E., Gila and Salt River Meridian, Arizona

CHAINS	
	T 26 N R 21 E R 22 E S 24 S 19 S 25 S 30
	2002
	Deposit a magnet in a white plastic case at the base of the stainless steel post.
	Land, level. Soil, sandy. Undergrowth, native grasses.
	North, bet. secs. 19 and 24.
	Over level land, through scattered native grasses.
12.40	Graded road, NR9061, 15 ft. wide, bears S. 57° E. and N. 57° W.
40.00	Point for the 1/4 sec. cor. of secs. 19 and 24.
	Set a stainless steel post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.
	T 26 N R 21 E R 22 E 1/4 S 24 S 19
	2002
	Deposit a magnet in a white plastic case at the base of the stainless steel post.
65.10	Graded road, NR9000, 25 ft. wide, bears N. 64° E. and S. 64° W.
80.00	Point for the cor. of secs. 13, 18, 19 and 24.
	Set a stainless steel post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.
	T 26 N R 21 E R 22 E S 13 S 18 S 24 S 19
	2002
	Deposit a magnet in a white plastic case at the base of the stainless steel post.

Survey of the East Boundary
T 26 N., R. 21 E., Gila and Salt River Meridian, Arizona

CHAINS	
	<p>Land, level. Soil, sandy. Undergrowth, native grasses.</p> <hr/> <p>North, bet. secs. 13 and 18.</p> <p>Over level land, through scattered native grasses.</p>
.65	<p>Point for the crossing closing cor., at intersection with the Hopi-Navajo partition line, segment "A".</p> <p>Set a stainless steel post, 28 ins. long, 2½ ins. diam., 26 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T26N R21E R22E HOPI S 13 S 18 NAVAJO C-C-C 2002</p> <p>From this point, AP-A118 on the Hopi-Navajo Partition line, segment "A", monumented with an iron post, 2½ ins. diam., firmly set, projecting 4 ins. above the ground, with brass cap mkd. HOPI NAVAJO AP A-118 1977 2002, bears N. 89°58' W., 41.02 chs. dist.</p> <p>From this same point, AP-A119 on the Hopi-Navajo partition line, segment "A", monumented with an iron post, 2½ ins. diam., firmly set, projecting 4 ins. above the ground, with brass cap mkd. HOPI NAVAJO AP A-119 1977 2002, bears S. 89°58' E., 98 lks. dist.</p> <p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p> <p>Cor. located beneath a five strand barbed wire fence, bears E. and W.</p> <p>Leave the Navajo reservation, enter the Hopi reservation.</p>
18.50	<p>Toe of spur, bears E. and W., ascend.</p>
40.00	<p>Point for the 1/4 sec. cor. of secs. 13 and 18.</p> <p>Set a stainless steel post, 28 ins. long, 2½ ins. diam., 16 ins. in the ground, in a mound of stone, 3 ft. base, to top, with brass cap mkd.</p>

**Survey of the East Boundary
T 26 N., R. 21 E., Gila and Salt River Meridian, Arizona**

CHAINS	
	T 26 N R 21 E R 22 E 1/4 S 13 S 18 2002
	Deposit a magnet in a white plastic case at the base of the stainless steel post.
	Cor. located on S. face of steep slope.
54.00	N. toe of spur, bears N. 25° E., and S. 25° W., across level land, through sage brush and native grasses.
64.90	S. toe of spur, bears N. 80° E., and W.
72.35	N. toe of spur, bears S. 45° E., and N. 45° W., across level to broken land, through sage brush and native grasses.
80.00	Point for the cor. of secs. 7, 12, 13, and 18.
	Set a stainless steel post, 28 ins. long, 2½ ins. diam., 23 ins. in the ground, with brass cap mkd.
	T 26 N R 21 E R 22 E S 12 S 7 <hr style="width: 50%; margin: 0 auto;"/> S 13 S 18 2002
	Deposit a magnet in a white plastic case at the base of the stainless steel post.
	Land, level to rolling and broken. Soil, sandy. Undergrowth, sage brush and native grasses.
	<hr/> North, bet. secs. 7 and 12.
	Over broken land, through medium growth scrub piñon and juniper trees.
8.65	N. edge of mesa, bears S. 60° E., and N. 60° W.
32.70	S. edge of deep arroyo, bears N. 80° E., and S. 80° W.
38.85	N. edge of deep arroyo, bears N. 20° E., and S. 20° W.
40.00	Point for the 1/4 sec. cor. of secs. 7 and 12.

Survey of the East Boundary
T 26 N., R. 21 E., Gila and Salt River Meridian, Arizona

CHAINS	
	<p>Set a stainless steel post, 28 ins. long, 2½ ins. diam., 16 ins. in the ground, in a mound of stone, 3 ft. base, to top, with brass cap mkd.</p>
	<p>T 26 N R 21 E R 22 E 1/4 S 12 S 7</p>
	<p>2002</p>
	<p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p>
	<p>from which</p>
	<p style="padding-left: 40px;">A piñon, 8 ins. diam., bears N. 39 3/4° E., 86 lks. dist., mkd. 1/4 S7 BT.</p>
	<p style="padding-left: 40px;">A piñon, 10 ins. diam., bears S. 35° W., 1.88 chs. dist., mkd. 1/4 S12 BT.</p>
<p>79.25</p>	<p>Center of dry, sandy wash, 10 ft. wide, 1 ft. deep, drains S. 60° E.</p>
<p>80.00</p>	<p>Point for the cor. of secs. 1, 6, 7, and 12, falls on S. face of steep slope and is impractical to monument.</p>
	<p>From this point, the point selected for a witness cor. to the sec. cor., bears N. 35°24' W., 70 lks. dist., with brass cap mkd.</p>
	<p>WC T 26 N R 21 E R 22 E S 1 S 6 S 12 S 7 ↘</p>
	<p>2003</p>
	<p>from which</p>
	<p style="padding-left: 40px;">A piñon, 8 ins. diam., bears N. 65 3/4° E., 1.5 chs. dist., mkd. T26N R21E S6 WC BT.</p>
	<p style="padding-left: 40px;">A piñon, 5 ins. diam., bears S. 70 1/4° E., 1.33 chs. dist., mkd. "X" BT.</p>
	<p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p>

**Survey of the East Boundary
T 26 N., R. 21 E., Gila and Salt River Meridian, Arizona**

CHAINS	
	<p>Land, broken. Soil, rocky and sandy. Undergrowth, sage brush, juniper and piñon.</p> <hr/> <p>North, bet. secs. 1 and 6.</p> <p>Over broken land, through scattered cedar, piñon and juniper trees.</p>
40.00	<p>Point for the 1/4 sec. cor. of secs. 1 and 6.</p> <p>Set a stainless steel post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T 26 N 1/4 R 21 E R 22 E S 1 S 6</p> <p style="text-align: center;">2002</p> <p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p>
74.64	Barbed wire fence, 5 strand, bears N. 55° E. and S. 55° W.
76.00	Trail road, bears N. 50° E. and S. 50° W.
80.00	<p>The cor. of secs. 1, 6, 31 and 36, on the N. bdy. of the Tp., monumented with a stainless steel post, 2½ ins. diam., firmly set, projecting 3 ins. above ground, with brass cap mkd. T27N R21E R22E S36 S31 S1 S6 T26N 2002.</p> <p>Land, broken. Soil, rocky and sandy. Undergrowth, sage brush, juniper and piñon.</p> <hr/> <p style="text-align: center;">Survey of the Subdivisional Lines, T. 26 N., R. 21 E., Gila and Salt River Meridian, Arizona</p> <hr/> <p>From the sec. cor. of secs. 1, 2, 35 and 36, on the S. bdy. of the Tp., hereinbefore described.</p> <p>N. 0°01' W., bet. secs. 35 and 36.</p> <p>Over level land, through scattered native grasses.</p>
40.00	Point for the 1/4 sec. cor. of secs. 35 and 36.

Survey of the Subdivisional Lines
T 26 N., R. 21 E., Gila and Salt River Meridian, Arizona

CHAINS	
	<p>Set a stainless steel post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T 26 N R 21 E 1/4 S 35 S 36</p> <p style="text-align: center;">2002</p> <p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p> <p>Cor. located 3.20 chs. N. of trail road, bears NNE and SSW.</p>
80.00	<p>Point for the cor. of secs. 25, 26, 35 and 36.</p> <p>Set a stainless steel post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T 26 N R 21 E S 26 S 25 S 35 S 36</p> <p style="text-align: center;">2002</p> <p>from which</p> <p style="padding-left: 40px;">The most NW cor. of an L shaped house, 48 X 52 ft. on the outer side, bears N. 68°15' E., 1.86 chs. dist., long side bears SSW.</p> <p style="padding-left: 40px;">The NW cor. of a stucco house, 60 X 25 ft. bears S. 10°07' E., 1.39 chs. dist., long side bears SSW.</p> <p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p> <p>Land, level. Soil, sandy. Undergrowth, native grasses.</p> <hr/> <p>From the cor. of secs. 25, 30, 31 and 36, on the E. bdy. of the Tp., hereinbefore described.</p> <p>N. 89°53' W., bet. secs. 25 and 36.</p> <p>Over level land, through scattered native grasses.</p>
40.01	<p>Point for the 1/4 sec. cor. of secs. 25 and 36.</p>

**Survey of the Subdivisional Lines
T 26 N., R. 21 E., Gila and Salt River Meridian, Arizona**

CHAINS	<p>Set a stainless steel post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p align="center">T 26 N R 21 E S 25 1/4 ——— S 36</p> <p align="center">2002</p> <p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p>
80.02	<p>The cor. of secs. 25, 26, 35 and 36.</p> <p>Land, level. Soil, sandy. Undergrowth, native grasses.</p> <hr/> <p>N. 0°01' W., bet. secs. 25 and 26.</p> <p>Over level land, through scattered native grasses.</p>
40.00	<p>Point for the 1/4 sec. cor. of secs. 25 and 26.</p> <p>Set a stainless steel post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p align="center">T 26 N R 21 E 1/4 S 26 S 25</p> <p align="center">2002</p> <p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p>
80.00	<p>Point for the cor. of secs. 23, 24, 25 and 26.</p> <p>Set a stainless steel post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p align="center">T 26 N R 21 E S 23 S 24 S 26 S 25</p> <p align="center">2002</p> <p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p>

Survey of the Subdivisional Lines
T 26 N., R. 21 E., Gila and Salt River Meridian, Arizona

CHAINS	
	<p>Land, level. Soil, sandy. Undergrowth, scattered native grasses.</p> <hr/> <p>From the cor. of secs 19, 24, 25 and 30, on the E. bdy. of the Tp., hereinbefore described.</p> <p>N. 89°53' W., bet. secs. 24 and 25.</p> <p>Over level land, through scattered native grasses.</p>
40.01	<p>Point for the 1/4 sec. cor. of secs. 24 and 25.</p> <p>Set a stainless steel post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T 26 N R 21 E S 24 1/4 ——— S 25</p> <p style="text-align: center;">2002</p> <p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p>
80.02	<p>The cor. of secs. 23, 24, 25 and 26.</p> <p>Land, level. Soil, sandy. Undergrowth, native grasses.</p> <hr/> <p>N. 0°01' W., bet. secs. 23 and 24.</p> <p>Over level land, through scattered native grasses.</p>
19.45	<p>Graded road, 35 ft. wide, bears N. 63° E. and S. 63° W.</p>
22.62	<p>Barbed wire fence, bears N. 80° E. and S. 80° W.</p>
40.00	<p>Point for the 1/4 sec. cor. of secs. 23 and 24.</p> <p>Set a stainless steel post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T 26 N R 21 E 1/4 S 23 S 24</p> <p style="text-align: center;">2002</p>

**Survey of the Subdivisional Lines
T 26 N., R. 21 E., Gila and Salt River Meridian, Arizona**

CHAINS	<p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p>								
80.00	<p>Point for the cor. of secs. 13, 14, 23 and 24.</p> <p>Set a stainless steel post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center; margin: 10px 0;"> <table style="margin: auto; border-collapse: collapse;"> <tr> <td style="padding: 0 10px;">T 26 N</td> <td style="padding: 0 10px;">R 21 E</td> </tr> <tr> <td style="padding: 0 10px; border-right: 1px solid black;">S 14</td> <td style="padding: 0 10px;">S 13</td> </tr> <tr> <td style="padding: 0 10px; border-right: 1px solid black;">S 23</td> <td style="padding: 0 10px;">S 24</td> </tr> </table> </div> <p align="center">2002</p> <p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p> <p>Land, level. Soil, sandy. Undergrowth, native grasses.</p> <hr style="width: 80%; margin: 20px auto;"/> <p>From the cor. of 13, 18, 19 and 24, on the E. bdy. of the Tp., hereinbefore described.</p> <p>N. 89°53' W., bet. secs. 13 and 24.</p> <p>Over level land, through scattered native grasses.</p>	T 26 N	R 21 E	S 14	S 13	S 23	S 24		
T 26 N	R 21 E								
S 14	S 13								
S 23	S 24								
40.01	<p>Point for the 1/4 sec. cor. of secs. 13 and 24.</p> <p>Set a stainless steel post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center; margin: 10px 0;"> <table style="margin: auto; border-collapse: collapse;"> <tr> <td style="padding: 0 10px;">T 26 N</td> <td style="padding: 0 10px;">R 21 E</td> </tr> <tr> <td style="padding: 0 10px;"></td> <td style="padding: 0 10px;">S 13</td> </tr> <tr> <td style="padding: 0 10px;">1/4</td> <td style="padding: 0 10px; border-top: 1px solid black;">—</td> </tr> <tr> <td style="padding: 0 10px;"></td> <td style="padding: 0 10px;">S 24</td> </tr> </table> </div> <p align="center">2002</p> <p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p>	T 26 N	R 21 E		S 13	1/4	—		S 24
T 26 N	R 21 E								
	S 13								
1/4	—								
	S 24								
80.02	<p>The cor. of secs. 13, 14, 23 and 24.</p> <p>Land, level. Soil, sandy. Undergrowth, native grasses.</p> <hr style="width: 80%; margin: 20px auto;"/> <p>N. 0°01' W., bet. secs. 13 and 14.</p>								

Survey of the Subdivisional Lines
T 26 N., R. 21 E., Gila and Salt River Meridian, Arizona

CHAINS	
	Over level land, through native grasses.
0.54	Point for the crossing closing cor., at intersection with the Hopi-Navajo partition line, segment "A". Set a stainless steel post, 28 ins. long, 2½ ins. diam., 23 ins. in the ground, with brass cap mkd. <div style="text-align: center;">T 26 N R 21 E HOPI S 14 S 13 NAVAJO C-C-C 2002</div>
	Deposit a magnet in a white plastic case at the base of the stainless steel post.
	From this cor. point, AP A-118, on the Hopi-Navajo partition line, segment "A", bears S. 89°58' E., 39.01 chs. dist., hereinbefore described.
	From this same cor. point, AP A-117, on the Hopi-Navajo partition line, segment "A", monumented with an iron post, 2½ ins. diam., firmly set, in a concrete block, 10 X 12 ins., projecting 10 ins. above the ground, with brass cap mkd. HOPI NAVAJO AP A-117 1977, bears N. 89°58' W., 1.27 chs. dist. Add the mks. 2002 to the brass cap.
	Cor. located beneath a five strand barbed wire fence, bears E. and W.
	Leave the Navajo reservation, enter the Hopi reservation.
13.85	Wash, 12 ft. wide, 2 ft. deep, drains S. 70° E.
15.00	Wash, 15 ft. wide, 2 ft. deep, drains S. 50° W.
20.60	Wash, 10 ft. wide, 2 ft. deep, drains S. 55° E.
40.00	Point for the 1/4 sec. cor. of secs. 13 and 14. Set a stainless steel post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd. <div style="text-align: center;">T 26 N R 21 E 1/4 S 14 S 13 2002</div>

Survey of the Subdivisional Lines
T 26 N., R. 21 E., Gila and Salt River Meridian, Arizona

CHAINS									
	<p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p>								
74.80	<p>Toe of slope, bears N. 30° E., and S. 30° W.</p>								
80.00	<p>Point for the cor. of secs. 11, 12, 13 and 14.</p> <p>Set a stainless steel post, 28 ins. long, 2½ ins. diam., 14 ins. in the ground, in a mound of stone, 3 ft. base, to top, with brass cap mkd.</p> <div style="text-align: center;"> <table style="margin: auto;"> <tr><td>T 26 N</td><td>R 21 E</td></tr> <tr><td>S 11</td><td>S 12</td></tr> <tr><td>S 14</td><td>S 13</td></tr> </table> <p>2002</p> </div> <p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p> <p>Land, level to broken. Soil, sandy and rocky. Undergrowth, scattered sage brush and native grasses.</p> <hr/> <p>From the cor. of secs. 7, 12, 13 and 18, on the E. bdy. of the Tp., hereinbefore described.</p> <p>N. 89°53' W., bet. secs. 12 and 13.</p> <p>Over broken land, through medium growth piñon, juniper trees and sage brush.</p>	T 26 N	R 21 E	S 11	S 12	S 14	S 13		
T 26 N	R 21 E								
S 11	S 12								
S 14	S 13								
40.01	<p>Point for the 1/4 sec. cor. of secs. 12 and 13.</p> <p>Set a stainless steel post, 28 ins. long, 2½ ins. diam., 23 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center;"> <table style="margin: auto;"> <tr><td>T 26 N</td><td>R 21 E</td></tr> <tr><td></td><td>S 12</td></tr> <tr><td>1/4</td><td>—</td></tr> <tr><td></td><td>S 13</td></tr> </table> <p>2002</p> </div> <p>from which</p> <p style="padding-left: 40px;">A piñon, 10 ins. diam., bears N. 48° E., 73 lks. dist., mkd. 1/4 S 12 BT.</p> <p style="padding-left: 40px;">A piñon pine, 4 ins. diam., bears S. 12 1/4° E., 47.5 lks. dist., mkd. X BT.</p>	T 26 N	R 21 E		S 12	1/4	—		S 13
T 26 N	R 21 E								
	S 12								
1/4	—								
	S 13								

**Survey of the Subdivisional Lines
T 26 N., R. 21 E., Gila and Salt River Meridian, Arizona**

CHAINS	<p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p>
80.02	<p>The cor. of secs. 11, 12, 13 and 14.</p> <p>Land, rolling to broken. Soil, sandy and rocky. Undergrowth, scattered piñon, juniper trees and medium growth sage brush.</p> <hr/> <p>N. 0°01' W., bet. secs. 11 and 12.</p> <p>Over broken land, through medium to heavy scrub juniper, piñon and sage brush.</p>
39.20	<p>Wash, 6 ft. wide, 6 ins. deep, drains S. 30° E.</p>
40.00	<p>Point for the 1/4 sec. cor. of secs. 11 and 12.</p> <p>Set a stainless steel post, 28 ins. long, 2½ ins. diam., 23 ins. in the ground, with brass cap mkd.</p> <p align="center">T 26 N R 21 E 1/4 S 11 S 12 2002</p> <p>from which</p> <p style="padding-left: 40px;">A piñon, 10 ins. diam., bears S. 72 1/4° E., 71 lks. dist., mkd. 1/4 S12 BT.</p> <p style="padding-left: 40px;">A piñon, 10 ins. diam., bears N. 55 3/4° W., 71 lks. dist., mkd. T26N R21E S11 BT.</p>
80.00	<p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p> <p>Point for the cor. of secs. 1, 2, 11 and 12.</p> <p>Set a stainless steel post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p align="center">T 26 N R 21 E S 2 S 1 ----- S 11 S 12 2002</p> <p>from which</p>

**Survey of the Subdivisional Lines
T 26 N., R. 21 E., Gila and Salt River Meridian, Arizona**

CHAINS	<p>A piñon, 4 ins. diam., bears N. 62 1/2° E., 50 lks. dist., mkd. X BT.</p> <p>A piñon, 8 ins. diam., bears S. 31 3/4° W., 50 lks. dist., mkd. T26N R21E S11 BT.</p> <p>A piñon, 6 ins. diam., bears N. 15 3/4° W., 50 lks. dist., mkd. T26N R21E S2 BT.</p> <p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p> <p>Land, rolling to broken. Soil, rocky and sandy. Undergrowth, scrub juniper and cedar, scattered sage brush.</p> <hr/> <p>From the cor. of secs. 1, 6, 7 and 12, on the E. bdy. of the Tp., hereinbefore described.</p> <p>N. 89°53' W., bet. secs. 1 and 12.</p> <p>Over rolling to broken land, through scattered sage brush, medium to heavy growth scrub juniper and piñon.</p>
40.01	<p>Point for the 1/4 sec. cor. of secs. 1 and 12.</p> <p>Set a stainless steel post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p align="center">T 26 N R 21 E S 1 1/4 ——— S 12</p> <p align="center">2002</p> <p>from which</p> <p>A piñon, 10 ins. diam., bears N. 58 1/2° E., 12 lks. dist., mkd. 1/4 S1 BT.</p> <p>A piñon, 4 ins. diam., bears S. 45 1/4° E., 1.39 chs. dist., mkd. X BT.</p> <p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p>
80.02	<p>The cor. of secs. 1, 2, 11 and 12.</p>

Survey of the Subdivisional Lines
T 26 N., R. 21 E., Gila and Salt River Meridian, Arizona

CHAINS	
	<p>Land, rolling to broken. Soil, rocky and sandy. Undergrowth, sage brush, scrub juniper and piñon.</p> <hr/> <p>N. 0°01' E., bet. secs. 1 and 2.</p> <p>Over broken land, through scattered scrub juniper and piñon.</p>
40.00	<p>Point for the 1/4 sec. cor. secs. 1 and 2.</p> <p>Set a stainless steel post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T 26 N R 21 E 1/4 S 2 S 1</p> <p style="text-align: center;">2003</p> <p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p>
60.08	<p>Trail road, bears N. 30° E. and S. 30° W.</p>
79.90	<p>The cor. of secs. 1, 2, 35 and 36, on the N. bdy. of the Tp., monumented with a stainless steel post, 2½ ins. diam., firmly set, projecting 3 ins. above ground, with brass cap mkd. T27N R21E S35 S36 S2 S1 T26N 2002.</p> <p>Land, broken. Soil, sandy and rocky. Undergrowth, scrub piñon and juniper.</p> <hr/> <p>From the cor. of secs. 3, 4, 34 and 35, on the S. bdy. of the Tp., hereinbefore described.</p> <p>N. 0°01' W., bet. secs. 34 and 35.</p> <p>Over level ground, through native grasses.</p>
28.72	<p>Graded road, 15 ft. wide, bears S. 75° E. and N. 75° W.</p>
40.00	<p>Point for the 1/4 sec. cor. of secs. 34 and 35.</p> <p>Set a stainless steel post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.</p>

Survey of the Subdivisional Lines
T 26 N., R. 21 E., Gila and Salt River Meridian, Arizona

CHAINS	
	T 26 N R 21 E 1/4 S 34 S 35 2002
	Deposit a magnet in a white plastic case at the base of the stainless steel post.
80.00	Point for the sec. cor. of secs. 26, 27, 34 and 35.
	Set a stainless steel post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.
	T 26 N R 21 E S 27 S 26 S 34 S 35 2002
	Deposit a magnet in a white plastic case at the base of the stainless steel post.
	Land, level. Soil, sandy. Undergrowth, native grasses.
	From the cor. of secs. 25, 26, 35 and 36.
	N. 89°53' W., bet. secs. 26 and 35.
	Over level land, through scattered native grasses.
26.66	E. right-of-way fence, Navajo Route No. 6, 5 strand barbed wire, bears N. 10° E. and S. 10° W.
28.19	Center of Navajo Route No. 6, paved asphalt, 29 ft. wide, bears N. 10° E. and S. 10° W.
29.74	W. right-of-way fence, Navajo Route No. 6, 5 strand barbed wire, bears N. 10° E. and S. 10° W.
32.40	Single phase power distribution line, bears N. and S.
40.02	Point for the 1/4 sec. cor. secs. 26 and 35.
	Set a stainless steel post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.

Survey of the Subdivisional Lines
T 26 N., R. 21 E., Gila and Salt River Meridian, Arizona

CHAINS	
	T 26 N R 21 E S 26 1/4 ——— S 35 2002
	from which An iron pipe, 2¼ ins. diam., firmly set, projecting 17 ins. above the ground, with a steel cap (plug) mkd. "D" PROP. CORNER and an arrow pointing NE and NW, bears S. 7°21' E., 8.77 chs. dist.
80.04	The cor. of secs. 26, 27, 34 and 35. Land, level. Soil, sandy. Undergrowth, native grasses.
	<hr/> N. 0°01' W., bet. secs. 26 and 27. Over level land, through native grasses.
40.00	Point for the 1/4 sec. cor. of secs. 26 and 27, cor. falls in trail road, bears N. 45° E. and S. 45° W. Set a stainless steel post, 28 ins. long, 2½ ins. diam., flush with the ground, with brass cap mkd.
	T 26 N R 21 E 1/4 S 27 S 26 2002
	Deposit a magnet in a white plastic case at the base of the stainless steel post. Set a steel fence post alongside the stainless steel post.
77.20	Toe of mesa, bears NE and SW.
80.00	Point for the cor. of secs. 22, 23, 26 and 27. Set a stainless steel post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.

**Survey of the Subdivisional Lines
T 26 N., R. 21 E., Gila and Salt River Meridian, Arizona**

CHAINS									
	<table border="0"> <tr> <td>T 26 N</td> <td>R 21 E</td> </tr> <tr> <td>S 22</td> <td>S 23</td> </tr> <tr> <td>S 27</td> <td>S 26</td> </tr> </table>	T 26 N	R 21 E	S 22	S 23	S 27	S 26		
T 26 N	R 21 E								
S 22	S 23								
S 27	S 26								
	2002								
	Deposit a magnet in a white plastic case at the base of the stainless steel post.								
	Land, level. Soil, sandy. Undergrowth, native grasses.								
	<hr/>								
	From the cor. of secs. 23, 24, 25 and 26.								
	N. 89°53' W., bet. secs. 23 and 26.								
	Over level ground, through native grasses.								
12.08	E. right-of-way fence, Navajo Route No. 6, 5 strand barbed wire, bears N. 10° E. and S. 10° W.								
31.61	Center of Navajo Route No. 6, paved asphalt, 29 ft. wide, bears N. 10° E. and S. 10° W.								
15.15	W. right-of-way fence, Navajo Route No. 6, 5 strand barbed wire, bears N. 10° E. and S. 10° W.								
37.10	Single phase power distribution line, bears N. and S.								
40.02	Point for the 1/4 sec. cor. of secs. 23 and 26.								
	Set a stainless steel post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.								
	<table border="0"> <tr> <td>T 26 N</td> <td>R 21 E</td> </tr> <tr> <td></td> <td>S 23</td> </tr> <tr> <td>1/4</td> <td>—</td> </tr> <tr> <td></td> <td>S 26</td> </tr> </table>	T 26 N	R 21 E		S 23	1/4	—		S 26
T 26 N	R 21 E								
	S 23								
1/4	—								
	S 26								
	2002								
	Deposit a magnet in a white plastic case at the base of the stainless steel post.								
73.00	Toe of mesa, bears NE and SW.								
80.04	The cor. of secs. 22, 23, 26 and 27.								

Survey of the Subdivisional Lines
T 26 N., R. 21 E., Gila and Salt River Meridian, Arizona

CHAINS	
	<p>Land, level. Soil, sandy. Undergrowth, native grasses.</p> <hr/>
	<p>N. 0°01' W., bet. secs. 22 and 23. Over level to broken land.</p>
11.10	Top of mesa, bears ENE and WSW.
40.00	<p>Point for the 1/4 sec. cor. of secs. 22 and 23.</p> <p>Set a stainless steel post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T 26 N R 21 E 1/4 S 22 S 23</p> <p style="text-align: center;">2002</p>
	<p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p>
80.00	<p>Point for the cor. of secs. 14, 15, 22 and 23.</p> <p>Set a stainless steel post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T 26 N R 21 E S 15 S 14 S 22 S 23</p> <p style="text-align: center;">2002</p>
	<p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p>
	<p>Land, level to broken. Soil, sandy and rocky. Undergrowth, native grasses.</p> <hr/>
	<p>From the cor. of secs. 13, 14, 23 and 24.</p>
	<p>N. 89°53' W., bet secs. 14 and 23.</p>
	<p>Over rolling land, through scattered sage brush and native grasses.</p>

**Survey of the Subdivisional Lines
T 26 N., R. 21 E., Gila and Salt River Meridian, Arizona**

CHAINS	
1.91	E. right-of-way fence, Navajo Route No. 6, 5 strand barbed wire, bears S. 8° E. and N. 8° W.
3.47	Center of Navajo Route No. 6, paved asphalt, 29 ft. wide, bears S. 8° E. and N. 8° W.
4.97	W. right-of-way fence, Navajo Route No. 6, 5 strand barbed wire, bears S. 8° E. and N. 8° W.
31.40	Toe of mesa, bears ESE and WNW.
36.70	Top of mesa, bears ENE and WSW.
40.02	Point for the 1/4 sec. cor. of secs. 14 and 23. Set a stainless steel post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd. <div style="text-align: center;"> T 26 N R 21 E S 14 1/4 ——— S 23 2002 </div>
80.04	Deposit a magnet in a white plastic case at the base of the stainless steel post. The cor. of secs. 14, 15, 22 and 23. Land, rolling. Soil, rocky and sandy. Undergrowth, sage brush and native grasses. _____
0.42	N. 0°01' W., bet. secs. 14 and 15. Over level to rolling land, through dense sage brush and native grasses. Point for the crossing closing cor., at intersection with the Hopi-Navajo partition line, segment "A". Set a stainless steel post, 28 ins. long, 2½ ins. diam., 25 ins. in the ground, with brass cap mkd. <div style="text-align: center;"> T 26 N R 21 E HOPI S 15 S 14 NAVAJO CCC 2003 </div>

Survey of the Subdivisional Lines
T 26 N., R. 21 E., Gila and Salt River Meridian, Arizona

CHAINS

Deposit a magnet in a white plastic case at the base of the stainless steel post.

From this cor. point, AP A-115, on the Hopi-Navajo partition line, monumented with an iron post, 2½ ins. diam, firmly set, projecting 7 ins. above the ground, with brass cap mkd. HOPI NAVAJO AP A-115 1977, bears N. 89°59' W., 78 lks. dist. From which the original bearing trees:

A forked piñon, 14 in. diam., bears S. 39 3/4° E., 83 lks. dist., with scribe marks APA115 NIR BT visible on partially open blaze, on main fork of tree. (Record: S. 18 1/2° E.)

A piñon, 10 ins. diam., bears N. 21 3/4° W., 23 lks. dist., with scribe marks APA115 HIR BT visible on partially open blaze. (Record: N. 1/4° E.)

From this same cor. point, AP A-116, on the Hopi Navajo partition line, monumented with an iron post, 2½ ins. diam., firmly set, projecting 6 ins. above a concrete collar, 13 ins. diam., with brass cap mkd. HOPI NAVAJO AP A-116 1977, bears S. 89°59' E., 41.50 chs. dist. From which the original bearing trees:

A multiple fork piñon, 14 ins. diam. at the base, bears S. 8° W., 1.65 chs. dist., with scribe marks APA116 NIR visible on partially open blaze, on main fork of tree.

A piñon, 8 ins. diam., bears N. 64 1/2° W., 77 lks dist., with scribe marks APA116 HIR BT visible on partially open blaze.

Cor. located beneath a five strand barbed wire fence, bears E. and W.

Leave Navajo Indian reservation, enter Hopi Indian reservation.

40.00

Point for the 1/4 sec. cor. of secs. 14 and 15.

Set a stainless steel post, 28 ins. long, 2½ ins. diam., 25 ins. in the ground, with brass cap mkd.

T 26 N R 21 E

1/4

S 15 | S 14

2003

from which

A piñon, 10 ins. diam., bears N. 24 1/2° E., 97.5 lks. dist., mkd. 1/4 S 14 BT.

Survey of the Subdivisional Lines
T 26 N., R. 21 E., Gila and Salt River Meridian, Arizona

CHAINS							
	<p style="text-align: center;">A piñon, 12 ins. diam., bears N. 45° W., 72 lks. dist., mkd. 1/4 S15 BT.</p> <p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p>						
43.20	Top of Mesa, bears ENE and WSW.						
67.25	Right bank of a dry, sandy wash, bears N. and S.						
68.85	Center of a dry, sandy wash, 1 ch. wide, 20 ft. deep, drains N. 25° E.						
71.60	Left bank of a dry, sandy wash, bears NE and SW.						
74.10	Bottom of a dry, sandy wash, drains N. 80° E.						
77.10	Left bank of a dry, sandy wash, bears E and SW.						
80.00	Point for the cor. of secs. 10, 11, 14 and 15.						
	<p>Set a stainless steel post, 28 ins. long, 2½ ins. diam., 25 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center;"> <table style="margin: auto;"> <tr> <td>T 26 N</td> <td>R 21 E</td> </tr> <tr> <td>S 10</td> <td>S 11</td> </tr> <tr> <td>S 15</td> <td>S 14</td> </tr> </table> <p>2003</p> </div> <p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p> <p>Land, level. Soil, sandy. Undergrowth, sage brush and native grasses.</p> <hr/> <p>From the cor. of secs. 11, 12, 13 and 14.</p> <p>N. 89°53' W., bet. secs. 11 and 14.</p> <p>Over level land, through scattered sage brush and native grasses.</p>	T 26 N	R 21 E	S 10	S 11	S 15	S 14
T 26 N	R 21 E						
S 10	S 11						
S 15	S 14						
38.30	Top of spur, bears N. 35° E. and S. 15° W.						
40.02	Point for the 1/4 sec. cor. of secs. 11 and 14.						
	<p>Set a stainless steel post, 28 ins. long, 2½ ins. diam., 23 ins. in the ground, with brass cap mkd.</p>						

Survey of the Subdivisional Lines
T 26 N., R. 21 E., Gila and Salt River Meridian, Arizona

CHAINS	
	T 26 N R 21 E S 11 1/4 ——— S 14 2003
	Deposit a magnet in a white plastic case at the base of the stainless steel post.
41.65	Center of dry, sandy wash, 30 ft. wide, 10 ft. deep, drains S. 20° W.
43.25	E. toe of spur, bears N. 15° E. and S. 20° W.
46.35	W. toe of spur, bears N. 30° E. and S. 10° W.
55.05	Left bank of dry, sandy wash, bears S. 40° E. and N. 40° W.
56.10	Right bank of dry, sandy wash, bears S. 10° E. and N. 10° W.
64.33	E. right-of-way fence, Navajo Route No. 6, 5 strand barbed wire, bears S. 58° E. and N. 58° W.
67.19	Center of Navajo Route No. 6, paved asphalt, 29 ft. wide, bears S. 58° E. and N. 58° W.
70.07	W. right-of-way fence, Navajo Route No. 6, 5 strand barbed wire, bears S. 58° E. and N. 58° W.
80.04	The cor. of secs. 10, 11, 14 and 15. Land, level. Soil, sandy. Undergrowth, sage brush and native grasses.
	N. 0°01' W., bet. secs. 10 and 11. Over rolling to broken land, through scattered scrub juniper, piñon, light sage brush and native grasses.
5.27	S. right-of-way fence, Navajo Route No. 6, 5 strand barbed wire, bears S. 63° E. and N. 63° W.
6.98	Center of Navajo Route No. 6, paved asphalt, 29 ft. wide, bears S. 63° E. and N. 63° W.
8.67	N. right-of-way fence, Navajo Route No. 6, 5 strand barbed wire, bears S. 63° E. and N. 63° W.
16.95	Toe of spur, bears N. and S.

Survey of the Subdivisional Lines
T 26 N., R. 21 E., Gila and Salt River Meridian, Arizona

CHAINS	
25.70	Top of spur, bears E. and W.
40.00	Point for the 1/4 sec. cor. of secs. 10 and 11. Set a stainless steel post, 28 ins. long, 2½ ins. diam., 25 ins. in the ground, with brass cap mkd. <div style="text-align: center;"> T 26 N R 21 E 1/4 S 10 S 11 2003 </div>
	Deposit a magnet in a white plastic case at the base of the stainless steel post.
61.30	Top of ridge, bears N. 60° E. and S. 60° W.
78.82	Barbed wire fence, bears N. 60° E. and S. 60° W.
80.00	Point for the cor. of secs. 2, 3, 10 and 11. Set a stainless steel post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd. <div style="text-align: center;"> T 26 N R 21 E S 3 S 2 --- S 10 S 11 2003 </div>
	Deposit a magnet in a white plastic case at the base of the stainless steel post.
	Cor. is located on the S. edge of a abandoned trail road, 10 ft. wide, bears N. 50° E. and S. 50° W.
	Land, rolling to broken. Soil, rocky and sandy. Undergrowth, scattered scrub juniper and cedar, light sage brush and native grasses.

	From the sec. cor. of secs. 1, 2, 11 and 12.
	N. 89°53' W., bet. secs. 2 and 11.
	Over rolling to broken land, through scattered scrub juniper, light sage brush and native grasses.
15.30	Center of dry, sandy wash, 15 ft. wide, 4 ft. deep, drains S. 35° W.

Survey of the Subdivisional Lines
T 26 N., R. 21 E., Gila and Salt River Meridian, Arizona

CHAINS	
36.40	Leave broken land, enter level ground.
40.02	Point for the 1/4 sec. cor. of secs. 2 and 11. Set a stainless steel post, 28 ins. long, 2½ ins. diam., 23 ins. in the ground, with brass cap mkd. <div style="text-align: center;"> T 26 N R 21 E S 2 1/4 ——— S 11 2003 </div>
	Deposit a magnet in a white plastic case at the base of the stainless steel post.
59.95	Trail road, bears N. 22° E. and S. 22° W.
60.80	Trail road, bears S. 8° E. and N. 8° W.
77.90	Barbed wire fence, bears N. 60° E. and S. 60° W.
80.04	The cor. of secs. 2, 3, 10 and 11. Land, level to broken. Soil, rocky and sandy. Undergrowth, scrub juniper, sagebrush and native grasses.
	<hr/> N. 0°02' E., bet. secs. 2 and 3. Over rolling land, through medium growth sage brush and native grasses.
0.13	Trail road, bears N. 50° E. and S. 50° W.
40.00	Point for the 1/4 sec. cor. of secs. 2 and 3. Set a stainless steel post, 28 ins. long, 2½ ins. diam., 25 ins. in the ground, with brass cap mkd. <div style="text-align: center;"> T 26 N R 21 E 1/4 S 3 S 2 2003 </div>
	Deposit a magnet in a white plastic case at the base of the stainless steel post.

Survey of the Subdivisional Lines
T 26 N., R. 21 E., Gila and Salt River Meridian, Arizona

CHAINS	
79.79	<p>The sec. cor. of secs. 2, 3, 34 and 35, on the N. bdy. of the TP., monumented with a stainless steel post, 2½ ins. diam., firmly set, projecting 3 ins. above ground, with brass cap mkd. T27N R21E S34 S35 S3 S2 T26N 2002.</p> <p>Land, rolling. Soil, sandy. Undergrowth, sagebrush and native grasses.</p> <hr/> <p>From the cor. of secs. 3, 4, 33 and 34, on the S. bdy. of the Tp., hereinbefore described.</p> <p>N. 0°02' W., bet. secs. 33 and 34.</p> <p>Over level land, through scattered native grasses.</p>
40.00	<p>Point for the 1/4 sec. cor. of secs. 33 and 34.</p> <p>Set a stainless steel post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T 26 N R 21 E 1/4 S 33 S 34 2002</p> <p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p> <p>Cor. is located 1.10 chs. S. of trail road, bears NE and SW.</p>
80.00	<p>Point for the cor. of secs. 27, 28, 33 and 34.</p> <p>Set a stainless steel post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T 26 N R 21 E S 28 S 27 S 33 S 34 2002</p> <p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p> <p>Cor. is located 73 lks. N. of under ground water line, bears E. and W., and 1.80 chs. S. of trail road, bears E. and W.</p>

Survey of the Subdivisional Lines
T 26 N., R. 21 E., Gila and Salt River Meridian, Arizona

CHAINS	
	<p>Land, level. Soil, sandy. Undergrowth, naïve grasses.</p> <hr/> <p>From the cor. of secs. 26, 27, 34 and 35. N. 89°54' W., bet. secs. 27 and 34. Over level land, through native grasses.</p>
40.01	<p>Point for the 1/4 sec. cor. of secs. 27 and 34.</p> <p>Set a stainless steel post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T 26 N R 21 E S 27 1/4 ——— S 34</p> <p style="text-align: center;">2002</p> <p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p>
80.02	<p>The cor. of secs. 27, 28, 33 and 34.</p> <p>Land, level. Soil, sandy. Undergrowth, native grasses.</p> <hr/> <p>N. 0°02' W., bet. secs. 27 and 28. Over level to broken land, through sage brush and native grasses.</p>
40.00	<p>Point for the 1/4 sec. cor. of secs. 27 and 28.</p> <p>Set a stainless steel post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T 26 N R 21 E 1/4 S 28 S 27</p> <p style="text-align: center;">2002</p> <p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p>
41.40	<p>Toe of mesa, bears ENE and WSW.</p>

**Survey of the Subdivisional Lines
T 26 N., R. 21 E., Gila and Salt River Meridian, Arizona**

CHAINS									
43.90	Top of mesa, bears E. and W.								
47.50	Toe of mesa, bears NE and SW.								
50.90	Top of mesa, bears NE and SW.								
72.30	Toe of mesa, bears SE and NW.								
78.50	Top of mesa, bears ENE and WSW.								
80.00	Point for the cor. of secs. 21, 22, 27 and 28. Set a stainless steel post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.								
	<table border="1"> <tr> <td>T 26 N</td> <td>R 21 E</td> </tr> <tr> <td>S 21</td> <td>S 22</td> </tr> <tr> <td>S 28</td> <td>S 27</td> </tr> </table>	T 26 N	R 21 E	S 21	S 22	S 28	S 27		
T 26 N	R 21 E								
S 21	S 22								
S 28	S 27								
	2002								
	Deposit a magnet in a white plastic case at the base of the stainless steel post.								
	Cor. located 70 lks. S. of rim of mesa, bears ENE and WSW.								
	Land, rolling and broken. Soil, sandy and rocky. Undergrowth, sage brush and native grasses.								
	<hr/>								
	From the cor. of secs. 22, 23, 26 and 27.								
	N. 89°54' W., bet. secs. 22 and 27.								
	Over rolling land, through sage brush and native grasses.								
21.60	Top of mesa, bears NNE and SSW.								
33.40	Top of mesa, N. and S.								
40.01	Point for the 1/4 sec. cor. of secs. 22 and 27. Set a stainless steel post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.								
	<table border="1"> <tr> <td>T 26 N</td> <td>R 21 E</td> </tr> <tr> <td>S 22</td> <td></td> </tr> <tr> <td>1/4</td> <td>—</td> </tr> <tr> <td></td> <td>S 27</td> </tr> </table>	T 26 N	R 21 E	S 22		1/4	—		S 27
T 26 N	R 21 E								
S 22									
1/4	—								
	S 27								
	2002								

**Survey of the Subdivisional Lines
T 26 N., R. 21 E., Gila and Salt River Meridian, Arizona**

CHAINS	<p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p> <p>Cor. located 33 lks. N. of S. edge of rim of mesa, bears S. 60° E. and N. 60° W.</p>
80.02	<p>The cor. of secs. 21, 22, 27 and 28.</p> <p>Land, rolling. Soil, sandy and rocky. Undergrowth, sage brush and native grasses.</p> <hr/> <p>N. 0°02' W., bet. secs. 21 and 22.</p> <p>Over level land, through native grasses.</p>
40.00	<p>Point for the 1/4 sec. cor. of secs. 21 and 22.</p> <p>Set a stainless steel post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p align="center">T 26 N R 21 E 1/4 S 21 S 22 2002</p>
80.00	<p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p> <p>Point for the cor. of secs. 15, 16, 21 and 22.</p> <p>Set a stainless steel post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p align="center">T 26 N R 21 E S 16 S 15 S 21 S 22 2002</p> <p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p> <p>Land, level. Soil, sandy. Undergrowth, native grasses.</p> <hr/> <p>From the cor. of secs. 14, 15, 22 and 23.</p>

Survey of the Subdivisional Lines
T 26 N., R. 21 E., Gila and Salt River Meridian, Arizona

CHAINS	
40.01	<p>N. 89°54' W., bet. secs. 15 and 22.</p> <p>Over level land, through native grasses.</p> <p>Point for the 1/4 sec. cor. of secs. 15 and 22.</p> <p>Set a stainless steel post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center;"> <p>T 26 N R 21 E</p> <p>S 15</p> <p>1/4 ———</p> <p>S 22</p> <p>2002</p> </div> <p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p> <p>Cor. located 36 lks. S. of Navajo-Hopi partition fence, 5 strand barbed wire, bears E. and W.</p>
80.02	<p>The cor. of secs. 15, 16, 21 and 22.</p> <p>Land, level. Soil, sandy. Undergrowth, native grasses.</p> <hr/> <p>N. 0°02' W., bet. secs. 15 and 16.</p> <p>Over level land, through native grasses and dense sage brush.</p>
0.30	<p>Point for the crossing closing cor., at intersection with the Hopi-Navajo partition line, segment "A".</p> <p>Set a stainless steel post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center;"> <p>T 26 N R 21 E</p> <p>HOPI</p> <p>S 16 S 15</p> <p>— —</p> <p>c cc</p> <p>NAVAJO</p> <p>2003</p> </div> <p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p>

Survey of the Subdivisional Lines
T 26 N., R. 21 E., Gila and Salt River Meridian, Arizona

CHAINS	
	<p>From this cor. point, AP A-113, on the Hopi-Navajo partition line, segment "A", monumented with an iron post, 2½ ins. diam, firmly set, projecting 3 ins. above a concrete block, 10 X 12 ins., with brass cap mkd. HOPI NAVAJO AP A-113 1977, bears N. 89°59' W., 68 lks. dist. No evidence of original BT's.</p> <p>From this same cor. point, AP A-114, on the Hopi-Navajo partition line, segment "A", monumented with an iron post, 2½ ins. diam., firmly set, projecting 4 ins. above a concrete collar, 12 ins. diam., with brass cap mkd. HOPI NAVAJO AP A-114 1977, bears S. 89°59' E., 39.18 chs. dist. From which the remaining original bearing tree.</p> <p style="padding-left: 40px;">A piñon, 7 ins. diam., bears N. 2 1/4° E., 41 lks. dist., with scribe marks "X" BT visible on open blaze.</p> <p>Cor. located beneath a five strand barbed wire fence, bears E. and W.</p> <p>Leave Navajo Indian reservation, enter Hopi Indian reservation.</p>
38.30	Trail road, bears N. 25° E. and S. 25° W.
40.00	<p>Point for the 1/4 sec. cor. of secs. 15 and 16.</p> <p>Set a stainless steel post, 28 ins. long, 2½ ins. diam., 23 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center;"> <p>T 26 N R 21 E</p> <p style="margin-left: 40px;">1/4</p> <p style="margin-left: 40px;">S 16 S 15</p> <p>2003</p> </div> <p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p>
41.75	Y intersection of two trail roads, bears N. 20° E., S. 15° E. and N. 20° W.
80.00	<p>Point for the cor. of secs. 9, 10, 15 and 16.</p> <p>Set a stainless steel post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center;"> <p>T 26 N R 21 E</p> <p style="margin-left: 40px;">S 9 S 10</p> <hr style="width: 100%; border: 0.5px solid black;"/> <p style="margin-left: 40px;">S 16 S 15</p> <p>2003</p> </div> <p>from which</p>

Survey of the Subdivisional Lines
T 26 N., R. 21 E., Gila and Salt River Meridian, Arizona

CHAINS	
	<p>A piñon, 18 ins. diam., bears N. 85° E., 62 lks. dist., mkd. T26N R21E S10 BT.</p> <p>A piñon, 19 ins. diam., bears S. 10 1/2° E., 25 lks. dist., mkd. T26N R21E S15 BT.</p> <p>A piñon, 24 ins. diam., bears S. 64 3/4° W., 1.05 chs. dist., mkd. T26N R21E S16 BT.</p> <p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p> <p>Land, rolling. Soil, sandy. Undergrowth, scattered juniper, cedar and dense sage brush.</p> <hr/> <p>From the cor. of secs. 10, 11, 14 and 15.</p> <p>N. 89°54' W., bet. secs. 10 and 15.</p> <p>Over rolling to broken land, through scattered scrub piñon, juniper and medium growth sage brush.</p>
2.40	Left bank, dry, sandy wash, bears S. 35° E., and N. 50° W.
3.90	Center of dry, sandy wash, 3 chs. wide, 16 ft. deep, drains S. 35° E.
6.60	Right bank, dry, sandy wash, bears S. 45° E., and N. 45° W.
40.01	<p>Point for the 1/4 sec. cor. of secs. 10 and 15.</p> <p>Set a stainless steel post, 28 ins. long, 2½ ins. diam., 25 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center;"> <p>T 26 N R 21 E</p> <p>S 10</p> <p>1/4 ———</p> <p>S 15</p> <p>2003</p> </div> <p>from which</p> <p>A piñon, 16 ins. diam., bears S. 51 1/2° E., 1.06 chs. dist., mkd. 1/4 S15 BT.</p> <p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p>
80.02	The cor. of secs. 9, 10, 15 and 16.

Survey of the Subdivisional Lines
T 26 N., R. 21 E., Gila and Salt River Meridian, Arizona

CHAINS	
	<p>Land, rolling to broken. Soil, rocky and sandy. Undergrowth, scattered piñon, juniper and medium growth sage brush.</p> <hr/> <p>N. 0°02' W., bet. secs. 9 and 10.</p> <p>Over rolling land, through dense sage brush and medium growth scrub juniper and piñon.</p>
1.70	Trail road, bears N. 85° E. and S. 80° W.
40.00	<p>Point for the 1/4 sec. cor. of secs. 9 and 10.</p> <p>Set a stainless steel post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center;"> <p>T 26 N R 21 E 1/4 S 9 S 10</p> <p>2003</p> </div> <p>from which</p> <p style="padding-left: 40px;">A piñon, 4 ins. diam., bears N. 89 1/2° E., 50 lks. dist., mkd. X BT.</p> <p style="padding-left: 40px;">A piñon, 4 ins. diam., bears S. 63° W., 17 lks. dist., mkd. X BT.</p> <p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p>
50.54	Bladed road, 15 ft. wide, bears N. 15° E., and S. 15° W.
80.00	<p>Point for the cor. of secs. 3, 4, 9 and 10.</p> <p>Set a stainless steel post, 28 ins. long, 2½ ins. diam., 25 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center;"> <p>T 26 N R 21 E S 4 S 3 ———— S 9 S 10</p> <p>2002</p> </div> <p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p>

Survey of the Subdivisional Lines
T 26 N., R. 21 E., Gila and Salt River Meridian, Arizona

CHAINS	
	<p>Land, level to rolling. Soil, sandy. Undergrowth, dense sage brush.</p> <hr/> <p>From the cor. of secs. 2, 3, 10 and 11. N. 89°54' W., bet. secs. 3 and 10. Over rolling land, through heavy growth sage brush and native grasses.</p>
0.15	Trail road, bears N. 50° E. and S. 50° W.
40.01	<p>Point for the 1/4 sec. cor. of secs. 3 and 10.</p> <p>Set a stainless steel post, 28 ins. long, 2½ ins. diam., 25 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center;"> <p>T 26 N R 21 E S 3 1/4 ——— S 10</p> <p>2003</p> </div> <p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p>
62.13	E. right-of-way fence, Navajo Route No. 6, 5 strand barbed wire, bears S. 17° E., and N. 17° W.
63.72	Center of Navajo Route No. 6, paved asphalt, 29 ft. wide, bears S. 17° E. and N. 17° W.
65.31	W. right-of-way fence, Navajo Route No. 6, 5 strand barbed wire, bears S. 17° E., and N. 17° W.
80.02	<p>The cor. of secs. 3, 4, 9 and 10.</p> <p>Land, rolling. Soil, sandy. Undergrowth, sage brush and native grasses.</p> <hr/> <p>N. 0°02' E., bet. secs. 3 and 4. Over rolling to level ground.</p>
40.00	<p>Point for the 1/4 sec. cor. of secs. 3 and 4.</p> <p>Set a stainless steel post, 28 ins. long, 2½ ins. diam., 26 ins. in the ground, with brass cap mkd.</p>

Survey of the Subdivisional Lines
T 26 N., R. 21 E., Gila and Salt River Meridian, Arizona

CHAINS	
	T 26 N R 21 E 1/4 S 4 S 3 2002
	Deposit a magnet in a white plastic case at the base of the stainless steel post.
47.47	S. right-of-way fence, Navajo Route No. 6, 5 strand barbed wire, bears S. 17° E., and N. 17° W.
52.56	Center of Navajo Route No. 6, paved asphalt, 29 ft. wide, bears S. 17° E. and N. 17° W.
57.65	N. right-of-way fence, Navajo Route No. 6, 5 strand barbed wire, bears S. 17° E. and N. 17° W.
75.58	Power line, bears N. 60° E. and S. 60° W.
79.70	The cor. of secs. 3, 4, 33 and 34, on the N. bdy. of the Tp., monumented with a stainless steel post, 2½ ins. diam., firmly set, projecting 4 ins. above ground, with brass cap mkd. T27N R21E S33 S34 S4 S3 T26N 2002.
	Land, rolling. Soil, sandy. Undergrowth, sage brush and native grasses.
	<hr/> From the cor. of secs. 4, 5, 32 and 33, on the S. bdy. of the Tp., monumented with an iron post, 3 ins. diam, loosely set, projecting 18 ins. above the ground, with brass cap mkd., R21E T26N T25N S32 S33 S5 S4 1910 77.
	At the corner point.
	Set a stainless steel post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.
	T 26 N R 21 E S 32 S 33 S 5 S 4 T 25 N 2002
	Bury the iron post alongside and deposit a magnet in a white plastic case at the base of the stainless steel post.
	N. 0°03' W., bet. secs. 32 and 33.

Survey of the Subdivisional Lines
T 26 N., R. 21 E., Gila and Salt River Meridian, Arizona

CHAINS	
	Over level land, through native grasses.
18.00	Graded road, 20 ft. wide, bears S. 63° E. and N. 63° W.
40.00	Point for the 1/4 sec. cor. of secs. 32 and 33. Set a stainless steel post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.
	T 26 N R 21 E 1/4 S 32 S 33 2002
	Deposit a magnet in a white plastic case at the base of the stainless steel post.
	Cor. located 36 lks. S. of trail road, bears SE and NW.
80.00	Point for the cor. of secs. 28, 29, 32 and 33. Set a stainless steel post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.
	T 26 N R 21 E S 29 S 28 S 32 S 33 2002
	from which
	The most NW cor. of a hexagon shaped hogan, 13.5 ft. each side, bears S. 58°45' E., 2.54 chs. dist.
	Deposit a magnet in a white plastic case at the base of the stainless steel post.
	<hr/>
	From the cor. of secs. 27, 28, 33 and 34.
	N. 89°53' W., bet. secs. 28 and 33.
	Over level land, through native grasses.
37.10	Power line, 69 KV, 4 strand, bears S. 15° E. and N. 15° W.
40.06	Point for the 1/4 sec. cor. of secs. 28 and 33. Set a stainless steel post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.

**Survey of the Subdivisional Lines
T 26 N., R. 21 E., Gila and Salt River Meridian, Arizona**

CHAINS	
	T 26 N R 21 E S 28 1/4 ——— S 33 2002
	Deposit a magnet in a white plastic case at the base of the stainless steel post. Cor. located 1.85 chs. N. of trail road, bears ENE and WSW.
57.10	Graded road, 15 ft. wide, bears N. and S.
80.12	The cor. of secs. 28, 29, 32 and 33. Land, level. Soil, sandy. Undergrowth, native grasses.
	<hr/> N. 0°03' W., bet. secs. 28 and 29. Over level land, through native grasses.
40.00	Set a stainless steel post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.
	T 26 N R 21 E 1/4 S 29 S 28 2002
56.20	Deposit a magnet in a white plastic case at the base of the stainless steel post. Top of mesa, bears E. and W., ascending over broken land.
80.00	Point for the cor. of secs. 20, 21, 28 and 29. Set a stainless steel post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.
	T 26 N R 21 E S 20 S 21 ———— S 29 S 28 2002
	Deposit a magnet in a white plastic case at the base of the stainless steel post.

Survey of the Subdivisional Lines
T 26 N., R. 21 E., Gila and Salt River Meridian, Arizona

CHAINS	
	<p>Land, level to broken. Soil, sandy and rocky. Undergrowth, native grasses and sage brush.</p> <hr/> <p>From the sec. cor. of secs. 21, 22, 27 and 28. N. 89°53' W., bet. secs. 21 and 28. Over rolling land, through native grasses and sage brush.</p>
40.06	<p>Point for the 1/4 sec. cor. of secs. 21 and 28. Set a stainless steel post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T 26 N R 21 E S 21 1/4 ——— S 28</p> <p style="text-align: center;">2002</p> <p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p>
54.30	Graded road, 15 ft. wide, bears S. 45° E. and N. 45° W.
59.00	Power line, 69 KV, 4 strand, bears S. 15° E. and N. 15° W.
80.12	<p>The cor. of secs. 20, 21, 28 and 29.</p> <p>Land, rolling. Soil, sandy. Undergrowth, native grasses and sage brush.</p> <hr/> <p>N. 0°03' W., bet. secs. 20 and 21. Over level land, through native grasses.</p>
24.90	Graded road, 15 ft. wide, bears S. 46° E. and N. 46° W.
40.00	<p>Point for the 1/4 sec. cor. of secs. 20 and 21. Set a stainless steel post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T 26 N R 21 E 1/4 S 20 S 21</p> <p style="text-align: center;">2002</p>

**Survey of the Subdivisional Lines
T 26 N., R. 21 E., Gila and Salt River Meridian, Arizona**

CHAINS	<p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p>								
77.00	<p>Power line, 69 KV, 4 strand, bears S. 15° E. and N. 15° W.</p>								
80.00	<p>Point for the cor. of secs. 16, 17, 20 and 21.</p> <p>Set a stainless steel post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center; margin: 10px 0;"> <table border="0"> <tr> <td>T 26 N</td> <td>R 21 E</td> </tr> <tr> <td>S 17</td> <td>S 16</td> </tr> <tr> <td>S 20</td> <td>S 21</td> </tr> </table> </div> <p align="center">2002</p> <p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p> <p>Land, level. Soil, sandy. Undergrowth, native grasses and sage brush.</p> <hr/> <p>From the cor. of secs. 15, 16, 21 and 22.</p> <p>N. 89°53' W., bet. secs. 16 and 21.</p> <p>Over level land, through native grasses.</p>	T 26 N	R 21 E	S 17	S 16	S 20	S 21		
T 26 N	R 21 E								
S 17	S 16								
S 20	S 21								
40.06	<p>Point for the 1/4 sec. cor. of secs. 16 and 21.</p> <p>Set a stainless steel post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center; margin: 10px 0;"> <table border="0"> <tr> <td>T 26 N</td> <td>R 21 E</td> </tr> <tr> <td></td> <td>S 16</td> </tr> <tr> <td>1/4</td> <td>—</td> </tr> <tr> <td></td> <td>S 21</td> </tr> </table> </div> <p align="center">2002</p> <p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p> <p>Cor. is located 24 lks. S. of Navajo-Hopi partition line fence, 5 strand barbed wire, bears E. and W.</p>	T 26 N	R 21 E		S 16	1/4	—		S 21
T 26 N	R 21 E								
	S 16								
1/4	—								
	S 21								
80.12	<p>The cor. of secs. 16, 17, 20 and 21.</p>								

**Survey of the Subdivisional Lines
T 26 N., R. 21 E., Gila and Salt River Meridian, Arizona**

CHAINS	<p>Land, level. Soil, sandy. Undergrowth, native grasses.</p> <hr/> <p>N. 0°03' W., bet. secs. 16 and 17</p> <p>Over rolling land, through medium growth sage brush and native grasses.</p>												
0.17	<p>Point for the crossing closing cor., at intersection with the Hopi-Navajo partition line, segment "A".</p> <p>Set a stainless steel post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center; margin: 10px 0;"> <table border="1" style="margin: auto; border-collapse: collapse;"> <tr> <td style="padding: 2px;">T 26 N</td> <td style="padding: 2px;">R 21 E</td> </tr> <tr> <td style="padding: 2px;">HOPI</td> <td style="padding: 2px;"> </td> </tr> <tr> <td style="padding: 2px;">S 17</td> <td style="padding: 2px;">S 16</td> </tr> <tr> <td style="padding: 2px;">NAV</td> <td style="padding: 2px;">AJO</td> </tr> <tr> <td colspan="2" style="padding: 2px;">CCC</td> </tr> <tr> <td colspan="2" style="padding: 2px;">2003</td> </tr> </table> </div> <p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p> <p>From this cor. point, AP A-110, on the Hopi-Navajo partition line, segment "A", monumented with an iron post, 2½ ins. diam, firmly set, projecting 11 ins. above a concrete block, 10 X 12 ins., projecting 10 ins. above the ground, with brass cap mkd. HOPI NAVAJO AP A-110 1977, bears N. 89°59' W., 38.08 chs. dist. From which the original bearing tree:</p> <p style="margin-left: 40px;">A forked juniper, 10 ins. diam., bears N. 17 3/4° E., 1.53 chs. dist., with scribe marks AP HIR BT visible on partially open blaze.</p> <p>From this same cor. point, AP A-111, on the Hopi-Navajo partition line, segment "A", monumented with an iron post, 2½ ins. diam., firmly set, projecting 6 ins. above a concrete block, 10 X 12 ins., with brass cap mkd. HOPI NAVAJO AP A-111 1977, bears S. 89°59' E., 25 lks. dist.</p> <p>Cor. located beneath a five strand barbed wire fence, bears E. and W.</p> <p>Leave Navajo Indian reservation, enter Hopi Indian reservation.</p>	T 26 N	R 21 E	HOPI		S 17	S 16	NAV	AJO	CCC		2003	
T 26 N	R 21 E												
HOPI													
S 17	S 16												
NAV	AJO												
CCC													
2003													
40.00	<p>Point for the 1/4 sec. cor. of secs. 16 and 17.</p> <p>Set a stainless steel post, 28 ins. long, 2½ ins. diam., 23 ins. in the ground, with brass cap mkd.</p>												

**Survey of the Subdivisional Lines
T 26 N., R. 21 E., Gila and Salt River Meridian, Arizona**

CHAINS	<p align="center">T 26 N R 21 E 1/4 S 17 S 16</p> <p align="center">2003</p> <p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p> <p>43.95 Graded road, 15 ft. wide, bears N. 15° E. and S. 15° W.</p> <p>80.00 Point for the cor. of secs. 8, 9, 16 and 17.</p> <p>Set a stainless steel post, 28 ins. long, 2½ ins. diam., 23 ins. in the ground, with brass cap mkd.</p> <p align="center">T 26 N R 21 E S 8 S 9 ----- S 17 S 16</p> <p align="center">2003</p> <p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p> <p>Land, rolling. Soil, sandy. Undergrowth, sage brush and native grasses.</p> <hr/> <p>From the cor. of secs. 9, 10, 15 and 16.</p> <p>N. 89°53' W., bet. secs. 9 and 16.</p> <p>Over rolling land, through heavy growth sage brush and native grasses.</p> <p>40.06 Point for the 1/4 sec. cor. of secs. 9 and 16.</p> <p>Set a stainless steel post, 28 ins. long, 2½ ins. diam., 25 ins. in the ground, with brass cap mkd.</p> <p align="center">T 26 N R 21 E S 9 1/4 ——— S 16</p> <p align="center">2003</p> <p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p>
--------	--

Survey of the Subdivisional Lines
T 26 N., R. 21 E., Gila and Salt River Meridian, Arizona

CHAINS	
80.12	<p>The cor. of secs. 8, 9, 16 and 17.</p> <p>Land, rolling. Soil, sandy. Undergrowth, sage brush and native grasses.</p> <hr/> <p>N. 0°03' W., bet. secs. 8 and 9.</p> <p>Over rolling land, through heavy growth sage brush and native grasses.</p>
40.00	<p>Point for the 1/4 sec. cor. of secs. 8 and 9.</p> <p>Set a stainless steel post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T 26 N R 21 E 1/4 S 8 S 9</p> <p style="text-align: center;">2003</p> <p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p>
80.00	<p>Point for the cor. of secs. 4, 5, 8 and 9.</p> <p>Set a stainless steel post, 28 ins. long, 2½ ins. diam., 25 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T 26 N R 21 E S 5 S 4 S 8 S 9</p> <p style="text-align: center;">2002</p> <p>from which</p> <p style="padding-left: 40px;">A piñon, 12 ins. diam., bears N. 44 1/4° E., 2.13 chs. dist., mkd. T26N R21E S4 BT.</p> <p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p> <p>Land, rolling. Soil, sandy. Undergrowth, sage brush and native grasses.</p> <hr/> <p>From the cor. of secs. 3, 4, 9 and 10.</p>

**Survey of the Subdivisional Lines
T 26 N., R. 21 E., Gila and Salt River Meridian, Arizona**

CHAINS	
	N. 89°53' W., bet. secs. 4 and 9.
	Over rolling land, through dense sage brush, scattered juniper and piñon
26.85	Trail road, bears S. 52° E. and N. 60° W.
40.06	Point for the 1/4 sec. cor. of secs. 4 and 9.
	Set a stainless steel post, 28 ins. long, 2½ ins. diam., 23 ins. in the ground, with brass cap mkd.
	<p align="center">T 26 N R 21 E S 4 1/4 ——— S 9</p>
	2002
	from which
	<p align="center">A piñon, 12 ins. diam., bears N. 83 1/2° E., 37 lks. dist., mkd. 1/4 S4 BT.</p>
	Deposit a magnet in a white plastic case at the base of the stainless steel post.
49.85	Trail road, bears N. 10° E. and S. 10° W.
50.15	Underground water line, bears N. 10° E. and S. 10° W.
80.12	The cor. of secs. 4, 5, 8 and 9.
	Land, rolling. Soil, sandy.
	Undergrowth, sage brush, native grasses, scrub juniper and piñon.
	<hr/> N. 0°06' E., bet. secs. 4 and 5.
	Over rolling land, through dense sage brush and native grasses.
28.50	Trail road and under ground water line, bears E. and W.
40.00	Point for the 1/4 sec. cor. of secs. 4 and 5.
	Set a stainless steel post, 28 ins. long, 2½ ins. diam., 23 ins. in the ground, with brass cap mkd.

Survey of the Subdivisional Lines
T 26 N., R. 21 E., Gila and Salt River Meridian, Arizona

CHAINS	
	T 26 N R 21 E 1/4 S 5 S 4 2002
	Deposit a magnet in a white plastic case at the base of the stainless steel post.
42.40	Trail road, bears S. 22° E. and N. 22° W.
54.40	Trail road, bears N. 45° E. and S. 70° W.
59.90	Toe of slope, bears E. and W.
79.60	The cor. of secs. 4, 5, 32 and 33, on the N. bdy. of the Tp., monumented with a stainless steel post, 2½ ins. diam., firmly set, projecting 4 ins. above ground, with brass cap mkd. T27N R21E S32 S33 S5 S4 T26N 2002.
	Land, rolling. Soil, sandy. Undergrowth, sage brush and native grasses.
	From the cor. of secs. 5, 6, 31 and 32, on the S. bdy. of the Tp., monumented with an iron post, 3 ins. diam, firmly set, projecting 2 ins. above a concrete block, 11 X 11 ins., with brass cap mkd., R21E T26N T25N S32 S31 S6 S5 AP A-99 1910. Add the mks. NAVAJO HOPI 2002 to the brass cap.
	N. 0°03' W., bet. secs. 31 and 32.
	Over level land, through native grasses.
40.00	Point for the 1/4 sec. cor. of secs. 31 and 32.
	Set a stainless steel post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.
	T 26 N R 21 E 1/4 S 31 S 32 2002
	Deposit a magnet in a white plastic case at the base of the stainless steel post.
51.10	Graded road, NR9062, 20 ft. wide, bears N. 75° E. and S. 75° W.
69.50	Graded road, 12 ft. wide, bears S. 57° E. and N. 57° W.

Survey of the Subdivisional Lines
T 26 N., R. 21 E., Gila and Salt River Meridian, Arizona

CHAINS									
80.00	<p>Point for the cor. of secs. 29, 30, 31 and 32.</p> <p>Set a stainless steel post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center;"> <table style="margin: auto;"> <tr> <td>T 26 N</td> <td>R 21 E</td> </tr> <tr> <td>S 30</td> <td>S 29</td> </tr> <tr> <td>S 31</td> <td>S 32</td> </tr> </table> <p>2002</p> </div> <p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p> <p>Cor. located 1.97 chs. E. of trail road, bears NNE and SSW.</p> <p>Land, level. Soil, sandy. Undergrowth, native grasses.</p> <hr/> <p>From the cor. of secs. 28, 29, 32 and 33.</p> <p>N. 89°54' W., bet. secs. 29 and 32.</p> <p>Over level land, through native grasses.</p>	T 26 N	R 21 E	S 30	S 29	S 31	S 32		
T 26 N	R 21 E								
S 30	S 29								
S 31	S 32								
39.94	<p>Point for the 1/4 sec. cor. of secs. 29 and 32.</p> <p>Set a stainless steel post, 28 ins. long, 2½ ins. diam., flush with the ground, with brass cap mkd.</p> <div style="text-align: center;"> <table style="margin: auto;"> <tr> <td>T 26 N</td> <td>R 21 E</td> </tr> <tr> <td></td> <td>S 29</td> </tr> <tr> <td>1/4</td> <td>—</td> </tr> <tr> <td></td> <td>S 32</td> </tr> </table> <p>2002</p> </div> <p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p> <p>from which</p> <div style="text-align: center;"> <p>The SW cor. of a wood frame house, 42 X 24 ft., long side bears NNE, bears N. 15°19' E., 60 lks. dist.</p> </div> <p>Cor. located 62 lks. W. of trail road, bears NNE and SSW.</p>	T 26 N	R 21 E		S 29	1/4	—		S 32
T 26 N	R 21 E								
	S 29								
1/4	—								
	S 32								
79.88	<p>The cor. of secs. 29, 30, 31 and 32.</p>								

Survey of the Subdivisional Lines
T 26 N., R. 21 E., Gila and Salt River Meridian, Arizona

CHAINS	
	<p>Land, level. Soil, sandy. Undergrowth, native grasses.</p> <hr/> <p>N. 89°58' W., bet. secs. 30 and 31.</p> <p>Over level land, through native grasses.</p>
17.50	Graded road, 12 ft. wide, bears S. 60° E. and N. 60° W.
40.00	<p>Point for the 1/4 sec. cor. of secs. 30 and 31.</p> <p>Set a brass tablet, 3¼ ins. diam., 3½ in. stem, in drill hole, in sandstone, with brass cap mkd.</p> <p style="text-align: center;">T 26 N R 21 E S 30 1/4 ——— S 31</p> <p style="text-align: center;">2002</p> <p>Deposit a magnet in a white plastic case at the base of the brass tablet.</p>
78.45	<p>The cor. of secs. 25, 30, 31 and 36, on the W. bdy. of the Tp., monumented with an iron post, 3 ins. diam., firmly set in concrete, projecting 21 ins. above ground, with brass cap mkd. T26N R20E R21E S25 S30 S36 S31 HOPI NAVAJO APA-103 78 1910 2002.</p> <p>Land, level. Soil, sandy. Undergrowth, native grasses.</p> <hr/> <p>From the cor. of secs. 29, 30, 31 and 32.</p> <p>N. 0°03' W., bet. secs. 29 and 30.</p> <p>Over level land, through native grasses.</p>
40.00	<p>Point for the 1/4 sec. cor. of secs. 29 and 30.</p> <p>Set a stainless steel post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T 26 N R 21 E 1/4 S 30 S 29</p> <p style="text-align: center;">2002</p>

**Survey of the Subdivisional Lines
T 26 N., R. 21 E., Gila and Salt River Meridian, Arizona**

CHAINS	<p>from which</p> <p style="padding-left: 40px;">The NW cor. of wood frame house, 63 X 32 ft., long side bears SSE, bears N. 63°43' E., 2.07 chs. dist.</p> <p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p>								
80.00	<p>Point for the cor. of secs. 19, 20, 29 and 30.</p> <p>Set a stainless steel post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <table style="margin-left: auto; margin-right: auto; border-collapse: collapse;"> <tr> <td style="padding: 0 10px;">T 26 N</td> <td style="padding: 0 10px;">R 21 E</td> </tr> <tr> <td style="border-right: 1px solid black; padding: 0 5px;">S 19</td> <td style="padding: 0 5px;">S 20</td> </tr> <tr> <td style="border-right: 1px solid black; padding: 0 5px;">S 30</td> <td style="padding: 0 5px;">S 29</td> </tr> </table> <p style="text-align: center;">2002</p> <p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p> <p>Land, level. Soil, sandy. Undergrowth, native grasses.</p> <hr style="width: 50%; margin-left: auto; margin-right: auto;"/> <p>From the cor. of secs. 20, 21, 28 and 29.</p> <p>N. 89°54' W., bet. secs. 20 and 29.</p> <p>Over level to rolling land, through sage brush and native grasses.</p>	T 26 N	R 21 E	S 19	S 20	S 30	S 29		
T 26 N	R 21 E								
S 19	S 20								
S 30	S 29								
39.94	<p>Point for the 1/4 sec. cor. of secs. 20 and 29.</p> <p>Set a stainless steel post, 28 ins. long, 2½ ins. diam., 22 ins. in the ground, with brass cap mkd.</p> <table style="margin-left: auto; margin-right: auto; border-collapse: collapse;"> <tr> <td style="padding: 0 10px;">T 26 N</td> <td style="padding: 0 10px;">R 21 E</td> </tr> <tr> <td style="padding: 0 10px;"></td> <td style="padding: 0 10px;">S 20</td> </tr> <tr> <td style="padding: 0 10px;"></td> <td style="padding: 0 10px;">1/4 ———</td> </tr> <tr> <td style="padding: 0 10px;"></td> <td style="padding: 0 10px;">S 29</td> </tr> </table> <p style="text-align: center;">2002</p> <p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p>	T 26 N	R 21 E		S 20		1/4 ———		S 29
T 26 N	R 21 E								
	S 20								
	1/4 ———								
	S 29								
46.60	<p>Edge of mesa, bears NNE and SSW.</p>								
48.40	<p>Toe of mesa, bears NNE and SSW.</p>								

Survey of the Subdivisional Lines
T 26 N., R. 21 E., Gila and Salt River Meridian, Arizona

CHAINS	
79.88	<p>The cor. of secs. 19, 20, 29 and 30.</p> <p>Land, level to rolling. Soil, sandy and rocky. Undergrowth, sage brush and native grasses.</p> <hr/> <p>N. 89°58' W., bet. secs. 19 and 30.</p> <p>Over level land, through native grasses.</p>
40.00	<p>Point for the 1/4 sec. cor. of secs. 19 and 30.</p> <p>Set a stainless steel post, 28 ins. long, 2½ ins. diam., flush with the ground, with brass cap mkd.</p> <div style="text-align: center;"> <p>T 26 N R 21 E</p> <p>S 19</p> <p>1/4 ———</p> <p>S 30</p> <p>2002</p> </div> <p>from which</p> <p style="padding-left: 40px;">The SW cor. of frame house, 42 X 32 ft., long side bears NNE, bears N. 87°03' E., 19 lks. dist.</p> <p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p> <p>Cor. located 1.40 chs. W. of trail road, bears NNE and SSW, and 2.31 chs. W. of power line, bears SSE and NNW.</p>
78.27	<p>The cor. of secs. 19, 24, 25 and 30, on the W. bdy. of the Tp., monumented with a magnet in a white plastic case, 18 ins. below ground. Falls in dry wash, 36 ft. wide, 4 ft. deep, drains SW.</p> <p>from which</p> <p style="padding-left: 40px;">A stainless steel post, 28 ins. long, 2½ ins. diam., set 24 ins. in the ground, for a reference monument, bears S. 57°24' W., 51.8 ft. dist., with brass cap mkd. RM T26N R20E S25 51.8 FT TO COR 2002 and an arrow pointing to the corner.</p> <p style="padding-left: 40px;">A stainless steel post, 28 ins. long, 2½ ins. diam., set 24 ins. in the ground, for a reference monument, bears N. 35°39' W., 44.6 ft. dist., with brass cap mkd. RM T26N R20E S24 44.6 FT TO COR 2002 and an arrow pointing to the corner.</p>

Survey of the Subdivisional Lines
T 26 N., R. 21 E., Gila and Salt River Meridian, Arizona

CHAINS	
	<p>Land, level. Soil, sandy. Undergrowth, native grasses.</p> <hr/> <p>N. 0°03' W., bet secs. 19 and 20.</p> <p>Over level to broken land, through sage brush and native grasses.</p>
40.00	<p>Point for the 1/4 sec. cor. of secs. 19 and 20.</p> <p>Set a stainless steel post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T 26 N R 21 E 1/4 S 19 S 20</p> <p style="text-align: center;">2002</p> <p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p> <p>Cor. located 55 lks. N. of trail road, bears E. and W. and 90 lks. S. of base of mesa bears SE and WSW.</p>
43.70	<p>Top of mesa, bears ESE and SSW.</p>
80.00	<p>Point for the cor. of secs. 17, 18 , 19 and 20.</p> <p>Set a stainless steel post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T 26 N R 21 E S 18 S 17 S 19 S 20</p> <p style="text-align: center;">2002</p> <p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p> <p>Cor. located 20 lks. E. of top of pointed mesa, bears ENE and WSW.</p> <p>Land, level to broken. Soil, sandy and rocky. Undergrowth, sagebrush and native grasses.</p> <hr/> <p>From the cor. of secs. 16, 17, 20 and 21.</p>

Survey of the Subdivisional Lines
T 26 N., R. 21 E., Gila and Salt River Meridian, Arizona

CHAINS	
	N. 89°54' W., bet. secs. 17 and 20.
	Over level land, through native grasses.
7.70	Graded road, 15 ft. wide, bears N. and S.
39.94	Point for the 1/4 sec. cor. of secs. 17 and 20.
	Set a stainless steel post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.
	T 26 N R 21 E S 17 1/4 ——— S 20 2002
	Deposit a magnet in a white plastic case at the base of the stainless steel post.
	Cor. located 10 lks. S. of Navajo-Hopi partition line, segment "A", fence line, 5 strand barbed wire, bears E. and W.
79.88	The cor. of secs. 17, 18, 19 and 20.
	Land, level. Soil, sandy. Undergrowth, native grasses.
	N. 89°58' W., bet secs. 18 and 19.
	Over level to broken land, through sage brush, native grasses and scrub juniper.
9.50	Edge of mesa, bears NE and SW.
12.10	Toe of mesa, bears NNE and SSW.
31.13	Barbed wire fence, 4 strand, bears NNE and SSW.
40.00	Point for the 1/4 sec. cor. of secs. 18 and 19.
	Set a stainless steel post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.
	T 26 N R 21 E S 18 1/4 ——— S 19 2002

Survey of the Subdivisional Lines
T 26 N., R. 21 E., Gila and Salt River Meridian, Arizona

CHAINS	
78.11	<p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p> <p>Cor. located 3 lks. S. of Navajo-Hopi partition line, segment "A", fence line, 5 strand barbed wire, bears E. and W.</p> <p>The cor. of secs. 13, 18, 19 and 24, on the W. bdy. of the Tp., identical with AP A-107 of the Navajo-Hopi partition line, segment "A", monumented with an iron post, 3 ins. diam, firmly set in concrete, projecting 14 ins. above the ground, with brass cap mkd. T26N R20E R21E S13 S18 HOPI S24 S19 AP-A107 NAVAJO 77 1910 2002.</p> <p>Land, broken. Soil, sandy and rocky. Undergrowth, sage brush, native grasses and scrub juniper.</p> <hr/> <p>N. 0°03' W., bet. secs. 17 and 18.</p> <p>Over broken land, through sage brush and native grasses.</p>
0.05	<p>Point for the crossing closing cor., at intersection with the Hopi-Navajo partition line, segment "A".</p> <p>Set a stainless steel post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T 26 N R 21 E HOPI</p> <p style="text-align: center;">S 18 S 17 NAVAJO CCC 2003</p> <p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p> <p>From this cor. point, AP A-108, on the Hopi-Navajo partition line, segment "A", monumented with an iron post, 2½ ins. diam., firmly set, flush in concrete block, 10 X 12 ins., with brass cap mkd. HOPI NAVAJO AP A-108 1977, bears West, 38.06 chs. dist., from which the original bearing tree</p> <p style="text-align: center;">A piñon, 8 ins. diam., bears N. 36 3/4° E., 53 lks. dist., with scribe marks X BT visible on partially open blaze.</p>

Survey of the Subdivisional Lines
T 26 N., R. 21 E., Gila and Salt River Meridian, Arizona

CHAINS					
	<p>From this same cor. point, AP A-109, on the Hopi-Navajo partition line, segment "A", monumented with an iron post, 2½ ins. diam., firmly set in a concrete collar, 10 X 12 ins., projecting 13 ins. above the ground, with brass cap mkd. HOPI NAVAJO AP A-109 1977, bears East, 1.78 chs. dist., from which the original bearing trees.</p> <p style="padding-left: 40px;">A forked juniper, NE main fork, 9 ins. diam., bears N. 7 1/4° E., 76 lks. dist., with scribe marks APA 109 HIR BT visible on partially open blaze.</p> <p style="padding-left: 40px;">A juniper, 17 ins. diam., bears S. 82° W., 92 lks. dist., with scribe marks APA109 NIR BT visible on partially open blaze.</p> <p>Cor. located beneath a five strand barbed wire fence, bears E. and W.</p> <p>Leave Navajo Indian reservation, enter Hopi Indian reservation.</p>				
37.25	Dry sandy wash, 3 ft. wide, 1 ft. deep, drains S. 10° W.				
40.00	<p>Point for the 1/4 sec. cor. of secs. 17 and 18.</p> <p>Set a stainless steel post, 28 ins. long, 2½ ins. diam., 20 ins. in the ground, in a collar of stone, with brass cap mkd.</p> <div style="text-align: center;"> <p>T 26 N R 21 E</p> <p style="margin-left: 40px;">1/4</p> <p style="margin-left: 40px;">S 18 S 17</p> <p>2003</p> </div> <p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p>				
47.25	Top of spur, bears N. 55° E. and S. 55° W.				
80.00	<p>Point for the cor. of secs. 7, 8, 17 and 18.</p> <p>Set a stainless steel post, 28 ins. long, 2½ ins. diam., 27 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center;"> <p>T 26 N R 21 E</p> <table style="margin-left: auto; margin-right: auto; border-collapse: collapse;"> <tr> <td style="border-right: 1px solid black; padding: 0 5px;">S 7</td> <td style="padding: 0 5px;">S 8</td> </tr> <tr> <td style="border-right: 1px solid black; padding: 0 5px;">S 18</td> <td style="padding: 0 5px;">S 17</td> </tr> </table> <p>2003</p> </div> <p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p>	S 7	S 8	S 18	S 17
S 7	S 8				
S 18	S 17				

Survey of the Subdivisional Lines
T 26 N., R. 21 E., Gila and Salt River Meridian, Arizona

CHAINS	
	<p>Land, rolling to broken. Soil, sandy and rocky. Undergrowth, scattered scrub piñon and juniper.</p> <hr/> <p>From the cor. of secs. 8, 9, 16 and 17. N. 89°54' W., bet. secs. 8 and 17. Over rolling land, through scattered piñon, native grasses and medium growth sage brush.</p>
39.94	<p>Point for the 1/4 sec. cor. of secs. 8 and 17. Set a stainless steel post, 28 ins. long, 2½ ins. diam., 23 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center;"> <p>T 26 N R 21 E S 8 1/4 ——— S 17</p> <p>2003</p> </div> <p>from which</p> <p style="padding-left: 40px;">A piñon, 4 ins. diam., bears N. 3 1/4° E., 22 lks. dist., mkd. X BT.</p> <p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p>
79.88	<p>The cor. of secs. 7, 8, 17 and 18. Land, rolling. Soil, sandy and rocky. Undergrowth, native grasses, sage brush and scattered piñon.</p> <hr/> <p>N. 89°59' W., bet. secs. 7 and 18. Over broken land, through scattered scrub juniper and piñon.</p>
40.00	<p>Point for the 1/4 sec. cor. of secs. 7 and 18, falls on N. face of steep slope, impractical to monument. From this point, the point selected for an off line witness cor. to the 1/4 sec. cor. of secs. 7 and 18 bears N. 82°59' E., 2.11 chs. dist. Set a stainless steel post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.</p>

Survey of the Subdivisional Lines
T 26 N., R. 21 E., Gila and Salt River Meridian, Arizona

CHAINS	
	WC T 26 N R 21 E S 7 1/4 ——— ↙ S 18 2003
	Deposit a magnet in a white plastic case at the base of the stainless steel post.
77.93	Point for the cor. of secs. 7, 12, 13 and 18 on the W. bdy. of the Tp., falls in dry sandy wash. From which the witness cor. to the sec. cor., a iron post, 3 ins. diam., firmly set, projecting 9 ins. above ground, with brass cap mkd. WC T26N R20E R21E S7 S12 S13 S18 1910 2002, bears N. 0°04' E., 1.40 chs. dist., from which the original bearing trees A trunk of a piñon, 12 ins. diam., bears N. 18 3/4° E., 107 lks. dist., with scribe marks WC T26N R21E S7 BT visible on open blaze. A juniper, 13 ins. diam., bears S. 46 1/2° E., 114 lks. dist., with scribe marks WC T26N R21E S18 BT visible on partially healed blaze. A juniper stump, 18 ins. diam., bears S. 39 1/2° W., 68 lks. dist., with no remaining scribe marks visible. A piñon stumphole, 13 ins. diam., bears N. 21° W., 73 lks. dist. Land, broken. Soil, sandy and rocky. Undergrowth, scrub juniper and piñon.
	From the cor. of secs. 7, 8, 17 and 18. N. 0°03' W., bet. secs. 7 and 8. Over broken land, through scattered scrub piñon and juniper.
40.00	Point for the 1/4 sec. cor. of secs. 7 and 8. Set a stainless steel post, 28 ins. long, 2½ ins. diam., 22 ins. in the ground, in a collar of stone, with brass cap mkd. T 26 N R 21 E 1/4 S 7 S 8 2003

Survey of the Subdivisional Lines
T 26 N., R. 21 E., Gila and Salt River Meridian, Arizona

CHAINS									
	<p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p>								
80.00	<p>Point for the cor. of secs. 5, 6, 7 and 8.</p> <p>Set a stainless steel post, 28 ins. long, 2½ ins. diam., 23 ins. in the ground, in a collar of stone, with brass cap mkd.</p> <div style="text-align: center;"> <table style="margin: auto;"> <tr><td>T 26 N</td><td>R 21 E</td></tr> <tr><td>S 6</td><td>S 5</td></tr> <tr><td colspan="2" style="border-top: 1px solid black;"></td></tr> <tr><td>S 7</td><td>S 8</td></tr> </table> <p>2003</p> </div> <p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p> <p>Cor. located on right edge of dry, sandy wash, 10 ft. wide, 1 ft. deep, drains S. 60° E.</p> <p>Land, broken. Soil, sandy and rocky. Undergrowth, scrub piñon and juniper.</p> <hr/> <p>From the cor. of secs. 4, 5, 8 and 9.</p> <p>N. 89°54' W., bet. secs. 5 and 8.</p> <p>Over rolling land, through dense sage brush, scattered piñon and juniper trees.</p>	T 26 N	R 21 E	S 6	S 5			S 7	S 8
T 26 N	R 21 E								
S 6	S 5								
S 7	S 8								
18.10	Trail road, bears S. 14° E. and N. 14° W.								
39.94	<p>Point for the 1/4 sec. cor. of secs. 5 and 8.</p> <p>Set a stainless steel post, 28 ins. long, 2½ ins. diam., 23 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center;"> <table style="margin: auto;"> <tr><td>T 26 N</td><td>R 21 E</td></tr> <tr><td></td><td>S 5</td></tr> <tr><td>1/4</td><td>——</td></tr> <tr><td></td><td>S 8</td></tr> </table> <p>2002</p> </div> <p>from which</p> <p style="padding-left: 40px;">A juniper, 14 ins. diam., bears N. 27 1/2° E., 67 lks. dist., mkd. 1/4 S5 BT.</p>	T 26 N	R 21 E		S 5	1/4	——		S 8
T 26 N	R 21 E								
	S 5								
1/4	——								
	S 8								

Survey of the Subdivisional Lines
T 26 N., R. 21 E., Gila and Salt River Meridian, Arizona

CHAINS	
	<p style="text-align: center;">A piñon, 4 ins. diam., bears S. 26 3/4° E., 27 lks. dist., mkd. X BT.</p> <p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p>
44.55	Power line, 69 KV, 4 strand, bears S. 15° E. and N. 15° W.
64.10	Top of ridge, bears N. 30° E., and S. 30° W.
74.85	Dry, sandy wash, 10 ft. wide, 2 ft. deep, drains S. 35° W.
79.88	The cor. of secs. 5, 6, 7 and 8.
	<p>Land, broken. Soil, sandy and broken. Undergrowth, sage brush, scrub piñon and juniper.</p> <hr/> <p>S. 89°50' W., bet. secs. 6 and 7.</p> <p>Over broken land, through scattered piñon and juniper.</p>
12.90	Top of ridge, bears N. 50° E. and S. 50° W.
26.00	Dry, sandy wash, 12 ft. wide, 2 ft. deep, drains S. 10° W.
40.00	Point for the 1/4 sec. cor. of secs. 6 and 7.
	<p>Set a stainless steel post, 28 ins. long, 2½ ins. diam., 22 ins. in the ground, in a collar of stone, with brass cap mkd.</p> <p style="text-align: center;">T 26 N R 21 E S 6 1/4 ——— S 7</p> <p style="text-align: center;">2003</p>
	<p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p>
46.80	Trail road and top of ridge, bears N. 39° E. and S. 35° W.
77.77	<p>Point for the cor. of secs. 1, 6, 7 and 12, on the W. bdy. of the Tp., monumented with an iron post, 3 ins. diam., firmly set, projecting 13 ins. above ground, with brass cap mkd. T26N R20E R21E S1 S6 S12 S7 1910 2002, bears N. 0°04' E., 1.40 chs. dist., from which the original bearing trees</p> <p style="text-align: center;">A dead piñon, 12 ins. diam., bears N. 18 1/2° E., 2.08 chs. dist., with scribe marks T26N R21E S6 BT visible on weathered blaze.</p>

Survey of the Subdivisional Lines
T 26 N., R. 21 E., Gila and Salt River Meridian, Arizona

CHAINS	
	<p>The base of a dead and down piñon, 7 ins. diam., bears S. 59 1/4° E., 39 lks. dist., with scribe marks T26N R21E S7 BT visible on a weathered blaze.</p> <p>A juniper, 9 ins. diam., bears S. 16 1/2° W., 1.20 chs. dist., with scribe marks T26N R20E S12 BT visible on partially healed blaze.</p> <p>A double blazed piñon, 11 ins. diam., bears N. 15 1/2° W., 1.34 chs. dist., with scribe marks T26N R20E S1 visible on upper blaze and marks BT visible on lower blaze.</p> <p>Land, broken. Soil, sandy and rocky. Undergrowth, piñon and juniper.</p> <hr/> <p>From the cor. of secs. 5, 6, 7 and 8.</p> <p>North, bet. secs. 5 and 6.</p> <p>Over rolling to broken land, through dense sage brush, scattered piñon and juniper.</p>
40.00	<p>Point for the 1/4 sec. cor. of secs. 5 and 6.</p> <p>Set a stainless steel post, 28 ins. long, 2½ ins. diam., 25 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T 26 N R 21 E 1/4 S 6 S 5</p> <p style="text-align: center;">2003</p> <p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p>
42.90	Barbed wire fence, 4 strand, bears E. and W.
45.10	Trail road, bears N. 45° E. and S. 45° W.
79.52	<p>The cor. of secs. 5, 6, 31 and 32 on the N. bdy. of the Tp., monumented with a stainless steel post, 2½ ins. diam., firmly set, projecting 4 ins. above ground, with brass cap mkd. T27N R21E S31 S32 S6 S5 T26N 2002.</p> <p>Land, rolling to broken. Soil, sandy and rocky. Undergrowth, sage brush, piñon and juniper trees.</p> <hr/>

T 26 N., R. 21 E., Gila and Salt River Meridian, Arizona

CHAINS

GENERAL DESCRIPTION

The area surveyed is split between the Hopi and Navajo Indian reservations. The terrain is level to rolling and broken. The drainage is southwesterly via many small washes.

The elevation varies from 6000 to 6700 feet above sea level. The soil is mostly sandy. The vegetation principally consists of sage brush and native grasses with piñon and juniper trees growing in the north 1/3 of the township.

Principal access to the township is provided by Navajo route No. 6. There are numerous trail roads throughout the township. Much of the township is used for grazing of live stock. There is no evidence of current mining activity.

The mean magnetic declination of $11 \frac{3}{4}^{\circ}$ E. was derived from the United States Geological Survey computer program GEOMAG, utilizing the World Magnetic Model for Epoch 2000 for the dates of survey.

**UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT**

FIELD ASSISTANTS

NAMES	CAPACITY
Mike M. Barnett	Surveying Technician
Robert J. Lyle	Surveying Technician
Richard M. McDonald	Surveying Technician
Joseph Paulin	Surveying Technician
Mark S. Searles	Surveying Technician
Daniel Bryan	Engineering Technician
Wilfred Chee	Engineering Technician
Edward Clarke	Engineering Technician
Reuben Mason	Engineering Technician
Barney Woodie	Engineering Technician

CERTIFICATE OF SURVEY

We, W. William Foster and Jones Curtiss, Cadastral Surveyors, HEREBY CERTIFY upon honor, that in pursuance of special instructions bearing date of the 12th day of November, 2002, we dependently resurveyed a portion of the south boundary and surveyed the east boundary and the subdivisional lines, T. 26 N., R. 21 E., of the Gila and Salt River Meridian, in the State of Arizona, which are represented in the foregoing field notes as having been executed by us and under our direction. Said survey has been made in strict conformity with said special instructions, the Manual of Instructions for the Survey of the Public Lands of the United States, and in specific manner described in the foregoing field notes.

6/07/04
(Date)

W. William Foster
(Cadastral Surveyor)

6/29/04
(Date)

Jones Curtiss
(Cadastral Surveyor)

CERTIFICATE OF APPROVAL

BUREAU OF LAND MANAGEMENT
Phoenix Arizona

The foregoing field notes of the dependent resurvey of a portion of the south boundary and the survey of the east boundary and the subdivisional lines, T. 26 N., R. 21 E., Gila and Salt River Meridian, in the State of Arizona, executed by W. William Foster and Jones Curtiss, Cadastral Surveyors, having been critically examined and found correct, are hereby approved.

11/31/05
(Date)

ACTING Stephen K. Hansen
(Chief Cadastral Surveyor of Arizona)

~~CERTIFICATE OF TRANSCRIPT~~

~~I CERTIFY That the foregoing transcript of the field notes of the above described surveys in T. 26 N., R. 21 E., Gila and Salt River Meridian, Arizona, is a true copy of the original field notes.~~

~~_____
(Date)~~

~~_____
(Chief Cadastral Surveyor of Arizona)~~