

ORIGINAL

**UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT**

FIELD NOTES
OF THE
DEPENDENT RESURVEY
OF
THE SOUTH, EAST, WEST AND NORTH BOUNDARIES,
AND
THE SUBDIVISIONAL LINES
TOWNSHIP 23 NORTH, RANGE 26 EAST,
OF THE GILA AND SALT RIVER MERIDIAN,
IN THE STATE OF ARIZONA

EXECUTED BY

Jones Curtiss and Leonard R. Sandoval, Cadastral Surveyors

Under Special Instructions dated and approved May 1, 2002, and Supplemental Special Instructions dated and approved September 23, 2002, which provided for the surveys included under Group No. 886, and assignment instructions dated May 1, 2002.

Survey commenced August 20, 2003

Survey completed December 18, 2003

INDEX DIAGRAM

TOWNSHIP 23 NORTH RANGE 26 EAST
Gila and Salt River Meridian, Arizona

17	22	21	21	20	19	18					
6	59	5	50	4	43	3	36	2	29	1	13
16	59	58	49	42	35	29					
7	57	8	48	9	41	10	35	11	28	12	12
16	57	56	48	41	34	27					
18	56	17	47	16	40	15	33	14	27	13	11
15	55	55	47	40	33	26					
19	54	20	46	21	39	22	32	23	25	24	10
14	53	53	45	38	32	25					
30	52	29	44	28	38	27	31	26	24	25	9
13	51	51	44	37	30	24					
31	50	32	43	33	36	34	29	35	23	36	9
8		7		6		5		4		4	

T. 23 N., R. 26 E., Gila and Salt River Meridian, Arizona

CHAINS

The following field notes describe the dependent resurvey of the south, east, west and north boundaries, and the subdivisional lines, Township 23 North, Range 26 East, Gila and Salt River Meridian, Arizona.

The history of surveys pertaining to this survey is as follows:

The south, east, west and north boundaries and the subdivisional lines were surveyed by Frank Follman in 1882. The west boundary, Township 22 North, Range 27 East, was dependently resurveyed by Jones Curtiss, in 2002-03, concurrently under this same group.

The survey was executed in accordance with the specifications as set forth in the Manual of Instructions for the Survey of the Public Lands of the United States, 1973, and the Special Instructions dated May 1, 2003 and the Supplemental Special Instructions dated and approved September 23, 2003, for Group No. 886, Arizona.

The true meridian direction and length of all lines were determined by real time kinematic global positioning system observations using Trimble Navigation Model 5700 receivers.

Preliminary to the resurvey, the lines of the prior surveys were retraced and search was made for all corners and other calls of record. Identified corners were remonumented in their original positions. Lost corners were reestablished and remonumented at proportionate positions based on the official record. The retracement data were thoroughly verified and only the true line field notes are given herein.

Geodetic control was derived from Global Positioning System (GPS) static observations post processed by National Geodetic Survey's Online Positioning User Service (OPUS), utilizing Continuously Operating Reference Stations (CORS) FERNO MESA, FLAGSTAFF AND PIE TOWN VLBA. The NAD83(CORS96)(EPOCH:2003) geographic position of the southeast corner of the township is as follows:

Latitude: 35°40'42.51" N. Longitude: 109°31'34.54" W.

The mean magnetic declination is 11 3/4° E.

**Dependent Resurvey of the South Boundary,
T. 23 N., R. 26 E., Gila and Salt River Meridian, Arizona**

CHAINS	
	<p>Restoring the survey executed by Frank Follman, in 1882</p> <hr/>
	<p>Beginning at the cor. of Tps. 22 and 23 N., Rs. 26 and 27 E., monumented with a stainless steel post, 2 1/2 ins. diam., with brass cap, set and mkd. as described in the field notes of the dependent resurvey of the W. bdy., T. 22 N., R. 27 E., executed concurrently under this same group.</p>
	<p>N. 89°52' W., bet. secs. 1 and 36.</p> <p>Over rolling land.</p>
39.88	<p>Point for the 1/4 sec. cor. of secs. 1 and 36, at proportionate dist.; there is no remaining evidence of the original cor.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center;"> <p>T 23 N R 26 E S 36 1/4 ——— S 1 T 22 N 2003</p> </div> <p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p>
79.76	<p>Point for the cor. of secs. 1, 2, 35 and 36, at proportionate dist.; there is no remaining evidence of the original cor.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center;"> <p>T 23 N R 26 E S 35 S 36 S 2 S 1 T 22 N 2003</p> </div> <p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p> <p>Cor. is located 30 lks. W. of a trail road, bears SSE and NNW.</p> <hr/> <p>N. 89°52' W., bet. secs. 2 and 35.</p> <p>Over rolling land.</p>

**Dependent Resurvey of the South Boundary,
T. 23 N., R. 26 E., Gila and Salt River Meridian, Arizona**

CHAINS	
16.20	Wash, 20 ft. wide, 5 ft. deep, drains N.
32.20	Wash, 20 ft. wide, 2 ft. deep, drains N.
39.88	<p>Point for the 1/4 sec. cor. of secs. 2 and 35, at proportionate dist.; there is no remaining evidence of the original cor.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T 23 N R 26 E S 35 1/4 ——— S 2 T 22 N</p> <p style="text-align: center;">2003</p> <p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p>
79.76	<p>Point for the cor. of secs. 2, 3, 34 and 35, at proportionate dist.; there is no remaining evidence of the original cor.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T 23 N R 26 E S 34 S 35 S 3 S 2 T 22 N</p> <p style="text-align: center;">2003</p> <p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p> <hr/> <p>N. 89°52' W., bet. secs. 3 and 34.</p> <p>Over rolling land.</p>
39.88	<p>Point for the 1/4 sec. cor. of secs. 3 and 34, at proportionate dist.; there is no remaining evidence of the original cor.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p>

**Dependent Resurvey of the South Boundary,
T. 23 N., R. 26 E., Gila and Salt River Meridian, Arizona**

CHAINS	
	T 23 N R 26 E S 34 1/4 ——— S 3 T 22 N 2003
	Deposit a magnet in a white plastic case at the base of the stainless steel post.
55.00	Wide Ruins Wash, 10 ft. wide, 10 ft. deep, drains SW.
79.76	Point for the cor. of secs. 3, 4, 33 and 34, at proportionate dist.; there is no remaining evidence of the original cor.
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.
	T 23 N R 26 E S 33 S 34 ———— S 4 S 3 T 22 N 2003
	Deposit a magnet in a white plastic case at the base of the stainless steel post.
	<hr/> N. 89°52' W., bet. secs. 4 and 33. Over rolling land.
25.90	Navajo Route 9410, a graded road, 18 ft. wide, bears SSE and NNW.
37.30	Navajo Route 9401, a graded road, 30 ft. wide, bears NE and SW.
39.88	Point for the 1/4 sec. cor. of secs. 4 and 33, at proportionate dist.; there is no remaining evidence of the original cor.
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.
	T 23 N R 26 E S 33 1/4 ——— S 4 T 22 N 2003

**Dependent Resurvey of the South Boundary,
T. 23 N., R. 26 E., Gila and Salt River Meridian, Arizona**

CHAINS											
79.76	<p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p> <p>Cor. is located 90 lks. N. of a trail road, bears E. and W.</p> <p>Point for the cor. of secs. 4, 5, 32 and 33, at proportionate dist.; there is no remaining evidence of the original cor.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center;"> <table style="border-collapse: collapse; margin: auto;"> <tr> <td style="padding: 0 5px;">T 23 N</td> <td style="padding: 0 5px;">R 26 E</td> </tr> <tr> <td style="padding: 0 5px; border-right: 1px solid black;">S 32</td> <td style="padding: 0 5px;">S 33</td> </tr> <tr> <td style="padding: 0 5px; border-right: 1px solid black;">S 5</td> <td style="padding: 0 5px;">S 4</td> </tr> <tr> <td colspan="2" style="padding: 0 5px;">T 22 N</td> </tr> </table> <p>2003</p> </div> <p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p> <p>Cor. is located 10 lks. N. of a trail road, bears ESE and WNW.</p> <p>Set a steel fence post near the stainless steel post.</p> <hr/> <p>N. 89°52' W., bet. secs. 5 and 32.</p> <p>Over rolling land.</p>	T 23 N	R 26 E	S 32	S 33	S 5	S 4	T 22 N			
T 23 N	R 26 E										
S 32	S 33										
S 5	S 4										
T 22 N											
39.88	<p>Point for the 1/4 sec. cor. of secs. 2 and 35, at proportionate dist.; there is no remaining evidence of the original cor.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center;"> <table style="border-collapse: collapse; margin: auto;"> <tr> <td style="padding: 0 5px;">T 23 N</td> <td style="padding: 0 5px;">R 26 E</td> </tr> <tr> <td colspan="2" style="padding: 0 5px;">S 32</td> </tr> <tr> <td colspan="2" style="padding: 0 5px;">1/4 ———</td> </tr> <tr> <td colspan="2" style="padding: 0 5px;">S 5</td> </tr> <tr> <td colspan="2" style="padding: 0 5px;">T 22 N</td> </tr> </table> <p>2003</p> </div>	T 23 N	R 26 E	S 32		1/4 ———		S 5		T 22 N	
T 23 N	R 26 E										
S 32											
1/4 ———											
S 5											
T 22 N											
79.76	<p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p> <p>Point for the cor. of secs. 5, 6, 31 and 32, at proportionate dist.; there is no remaining evidence of the original cor.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p>										

**Dependent Resurvey of the South Boundary,
T. 23 N., R. 26 E., Gila and Salt River Meridian, Arizona**

CHAINS	
	T 23 N R 26 E S 31 S 32 S 6 S 5 T 22 N 2003
	Deposit a magnet in a white plastic case at the base of the stainless steel post.
	<hr/> N. 89°52' W., bet. secs. 6 and 31. Over rolling land.
2.85	Trail road, bears ENE and WSW.
39.88	Point for the 1/4 sec. cor. of secs. 6 and 31, at proportionate dist.; there is no remaining evidence of the original cor. Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.
	T 23 N R 26 E S 31 1/4 ——— S 6 T 22 N 2003
	Deposit a magnet in a white plastic case at the base of the stainless steel post.
75.90	Trail road, bears NE and SW.
78.73	The cor. of Tps. 22 and 23 N., Rs. 25 and 26 E., monumented with a stainless steel post, 2 1/2 ins. diam., with brass cap, set and mkd. as described in the field notes of the dependent resurvey of the W. bdy., T. 22 N., R. 27 E., executed concurrently under this same group. Cor. is located 2.70 chs. N. of the same trail road, bears NE and SW.
	<hr/> Dependent Resurvey of the East Boundary, T. 23 N., R. 26 E., Gila and Salt River Meridian, Arizona <hr/> Restoring the survey executed by Frank Follman, in 1882

**Dependent Resurvey of the East Boundary,
T. 23 N., R. 26 E., Gila and Salt River Meridian, Arizona**

CHAINS	
	<p>From the cor. of Tps. 22 and 23 N., Rs. 26 and 27 E., hereinbefore described.</p> <p>North, bet. secs. 31 and 36.</p> <p>Over rolling land.</p>
40.52	<p>Point for the 1/4 sec. cor. of secs. 31 and 36, at proportionate dist.; there is no remaining evidence of the original cor.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center;"> <p>T 23 N R 26 E R 27 E 1/4 S 36 S 31</p> <p>2003</p> </div> <p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p>
81.04	<p>Point for the cor. of secs. 25, 30, 31 and 36, at proportionate dist.; there is no remaining evidence of the original cor.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center;"> <p>T 23 N R 26 E R 27 E S 25 S 30 S 36 S 31</p> <p>2003</p> </div> <p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p> <hr/> <p>North, bet. secs. 25 and 30.</p> <p>Over rolling land.</p>
40.52	<p>Point for the 1/4 sec. cor. of secs. 25 and 30, at proportionate dist.; there is no remaining evidence of the original cor.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p>

**Dependent Resurvey of the East Boundary,
T. 23 N., R. 26 E., Gila and Salt River Meridian, Arizona**

CHAINS	
	<p style="text-align: center;">T 23 N R 26 E R 27 E 1/4 S 25 S 30</p> <p style="text-align: center;">2003</p>
81.04	<p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p> <p>The cor. of secs. 19, 24, 25 and 30, monumented with a stainless steel post, 2 1/2 ins. diam., with brass cap, set and mkd. as described in the field notes of the dependent resurvey of the W. bdy., T. 22 N., R. 27 E., executed concurrently under this same group.</p>
	<p>N. 0°07' E., bet. secs. 19 and 24.</p>
	<p>Over rolling land.</p>
5.93	<p>Barbed wire fence, 5 strands, bears NE and SW.</p>
38.83	<p>Point for the 1/4 sec. cor. of secs. 19 and 24, at proportionate dist.; there is no remaining evidence of the original cor.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p>
	<p style="text-align: center;">T 23 N R 26 E R 27 E 1/4 S 24 S 19</p> <p style="text-align: center;">2003</p>
	<p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p>
51.80	<p>Barbed wire fence, 6 strands, bears SSE and NNW.</p>
79.66	<p>Point for the cor. of secs. 13, 18, 19 and 24, at proportionate dist.; there is no remaining evidence of the original cor.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p>
	<p style="text-align: center;">T 23 N R 26 E R 27 E S 13 S 18 ----- S 24 S 19</p> <p style="text-align: center;">2003</p>

**Dependent Resurvey of the East Boundary,
T. 23 N., R. 26 E., Gila and Salt River Meridian, Arizona**

CHAINS	
	<p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p> <p>Cor. is located 2.70 chs. E. of a trail road, bears NE and SW.</p> <hr/> <p>N. 0°07' E., bet. secs. 13 and 18.</p> <p>Over rolling land.</p>
2.50	Trail road, bears NE and SW.
35.60	Barbed wire fence, 5 strands, bears ESE and WNW.
39.83	<p>Point for the 1/4 sec. cor. of secs. 13 and 18, at proportionate dist.; there is no remaining evidence of the original cor.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center;"> <p>T 23 N R 26 E R 27 E 1/4 S 13 S 18</p> <p>2003</p> </div>
	<p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p>
56.55	Barbed wire fence, 5 strands, bears ENE and WSW.
57.00	Navajo Route 9401, a graded road, 20 ft. wide, bears ENE and WSW.
79.66	<p>Point for the cor. of secs. 7, 12, 13 and 18, at proportionate dist.; there is no remaining evidence of the original cor.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center;"> <p>T 23 N R 26 E R 27 E S 12 S 7 <hr/>S 13 S 18</p> <p>2003</p> </div>
	<p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p> <hr/> <p>N. 0°07' E., bet. secs. 7 and 12.</p>

**Dependent Resurvey of the East Boundary,
T. 23 N., R. 26 E., Gila and Salt River Meridian, Arizona**

CHAINS	
	Over rolling land.
39.83	<p>Point for the 1/4 sec. cor. of secs. 7 and 12, at proportionate dist.;; there is no remaining evidence of the original cor.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T 23 N R 26 E R 27 E 1/4 S 12 S 7</p> <p style="text-align: center;">2003</p> <p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p>
79.66	<p>The cor. of secs. 1, 6, 7 and 12, determined from the remains of the original bearing trees</p> <p style="padding-left: 40px;">A forked juniper, 9 ins. diam. at the base, bears S. 51° E., 21 lks. dist., mkd. TXXIIIIN RXXVIIIE SVII BT on partially healed blaze. (Record: S. 40° E.)</p> <p style="padding-left: 40px;">A piñon stump, 8 ins. diam., 6 ins. high, bears S. 5° W., 20 lks. dist., with remains of a blaze. (Record: S. 1° W.)</p> <p>At the corner point</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T 23 N R 26 E R 27 E S 1 S 6 ----- S 12 S 7</p> <p style="text-align: center;">2002</p> <p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p> <p>Cor. is located on the N. edge of a wash, 3 ft. wide, 1 ft. deep, drains WSW.</p> <hr/> <p>NOTE: Due to the lack of recovered evidence in this township, and because other concurrent dependent resurveys in the area did not recover original evidence from the 1882 surveys, the remainder of this boundary is extended by using the 1882 record bearing and distance.</p>

**Dependent Resurvey of the East Boundary,
T. 23 N., R. 26 E., Gila and Salt River Meridian, Arizona**

CHAINS	<p>North, on record bearing, bet. secs. 1 and 6.</p> <p>Over rolling land.</p>
40.00	<p>Point for the 1/4 sec. cor. of secs. 1 and 6, at record dist.; there is no remaining evidence of the original cor.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p align="center"> T 23 N R 26 E R 27 E 1/4 S 1 S 6 2002 </p> <p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p>
80.00	<p>Point for the cor of Tps. 23 and 24 N., Rs. 26 and 27 E., at record dist.; there is no remaining evidence of the original cor.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p align="center"> T 24 N R 26 E R 27 E S 36 S 31 S 1 S 6 T 23 N 2002 </p> <p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p> <hr/> <p align="center"> Dependent Resurvey of the West Boundary, T. 25 N., R. 27 E., Gila and Salt River Meridian, Arizona </p> <hr/> <p align="center"> Restoring the survey executed by Frank Follman, in 1882 </p> <hr/> <p>From the cor. of Tps. 22 and 23 N., Rs. 25 and 26 E., on the S. bdy. of the Tp., hereinbefore described.</p> <p>N. 0°03' E., bet. secs. 31 and 36.</p> <p>Over rolling land.</p>

**Dependent Resurvey of the West Boundary,
T. 23 N., R. 26 E., Gila and Salt River Meridian, Arizona**

CHAINS					
39.98	<p>Point for the 1/4 sec. cor. of secs. 31 and 36, at proportionate dist.; there is no remaining evidence of the original cor.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center; margin: 10px 0;"> <table style="margin: auto;"> <tr><td>T 23 N</td></tr> <tr><td>R 25 E R 26 E</td></tr> <tr><td>1/4</td></tr> <tr><td>S 36 S 31</td></tr> </table> <p>2003</p> </div> <p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p>	T 23 N	R 25 E R 26 E	1/4	S 36 S 31
T 23 N					
R 25 E R 26 E					
1/4					
S 36 S 31					
79.96	<p>Point for the cor. of secs. 25, 30, 31 and 36, at proportionate dist.; there is no remaining evidence of the original cor.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center; margin: 10px 0;"> <table style="margin: auto;"> <tr><td>T 23 N</td></tr> <tr><td>R 25 E R 26 E</td></tr> <tr><td>S 25 S 30</td></tr> <tr><td>S 36 S 31</td></tr> </table> <p>2003</p> </div> <p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p> <hr style="border: 0.5px solid black; margin: 10px 0;"/> <p>N. 0°03' E., bet. secs. 25 and 30.</p> <p>Over rolling land.</p>	T 23 N	R 25 E R 26 E	S 25 S 30	S 36 S 31
T 23 N					
R 25 E R 26 E					
S 25 S 30					
S 36 S 31					
39.98	<p>Point for the 1/4 sec. cor. of secs. 25 and 30, at proportionate dist.; there is no remaining evidence of the original cor.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center; margin: 10px 0;"> <table style="margin: auto;"> <tr><td>T 23 N</td></tr> <tr><td>R 25 E R 26 E</td></tr> <tr><td>1/4</td></tr> <tr><td>S 25 S 30</td></tr> </table> <p>2003</p> </div> <p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p>	T 23 N	R 25 E R 26 E	1/4	S 25 S 30
T 23 N					
R 25 E R 26 E					
1/4					
S 25 S 30					

**Dependent Resurvey of the West Boundary,
T. 23 N., R. 26 E., Gila and Salt River Meridian, Arizona**

CHAINS									
79.96	<p>The cor. of secs. 19, 24, 25 and 30, monumented with a sandstone, 16 x 8 x 7 ins., firmly set, projecting 8 ins. above ground, mkd. 2 grooves on S. face and 4 grooves on N. face.</p> <p>At the corner point</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center; margin: 10px 0;"> <table style="margin: auto; border-collapse: collapse;"> <tr> <td colspan="2" style="padding: 0 10px;">T 23 N</td> </tr> <tr> <td style="padding: 0 5px;">R 25 E</td> <td style="border-left: 1px solid black; padding: 0 5px;">R 26 E</td> </tr> <tr> <td style="padding: 0 5px;">S 24</td> <td style="border-left: 1px solid black; padding: 0 5px;">S 19</td> </tr> <tr> <td style="padding: 0 5px;">S 25</td> <td style="border-left: 1px solid black; padding: 0 5px;">S 30</td> </tr> </table> </div> <p style="text-align: center; margin: 5px 0;">2002</p> <p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p> <p>Bury the original sandstone alongside the stainless steel post.</p> <hr style="width: 50%; margin: 10px auto;"/> <p style="text-align: center; margin: 10px 0;">NOTE: Due to the lack of recovered evidence in this township, and because other concurrent dependent resurveys in the area did not recover original evidence from the 1882 surveys, the remainder of this boundary is extended by using the 1882 record bearing and distance.</p> <p>North, on record bearing, bet. secs. 19 and 24.</p> <p>Over rolling and broken land.</p>	T 23 N		R 25 E	R 26 E	S 24	S 19	S 25	S 30
T 23 N									
R 25 E	R 26 E								
S 24	S 19								
S 25	S 30								
5.40	<p>Apache County Road C323, a graded road, 20 ft. wide, bears ESE and WNW.</p>								
40.00	<p>Point for the 1/4 sec. cor. of secs. 19 and 24, at record dist.; there is no remaining evidence of the original cor.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center; margin: 10px 0;"> <table style="margin: auto; border-collapse: collapse;"> <tr> <td colspan="2" style="padding: 0 10px;">T 23 N</td> </tr> <tr> <td style="padding: 0 5px;">R 25 E</td> <td style="border-left: 1px solid black; padding: 0 5px;">R 26 E</td> </tr> <tr> <td colspan="2" style="padding: 0 10px;">1/4</td> </tr> <tr> <td style="padding: 0 5px;">S 24</td> <td style="border-left: 1px solid black; padding: 0 5px;">S 19</td> </tr> </table> </div> <p style="text-align: center; margin: 5px 0;">2002</p> <p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p>	T 23 N		R 25 E	R 26 E	1/4		S 24	S 19
T 23 N									
R 25 E	R 26 E								
1/4									
S 24	S 19								
80.00	<p>Point for the cor. of secs. 13, 18, 19 and 24, at record dist.; there is no remaining evidence of the original cor.</p>								

**Dependent Resurvey of the West Boundary,
T. 23 N., R. 26 E., Gila and Salt River Meridian, Arizona**

CHAINS									
	<p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <table border="0" style="margin-left: auto; margin-right: auto;"> <tr><td colspan="2" style="text-align: center;">T 23 N</td></tr> <tr><td style="text-align: center;">R 25 E</td><td style="text-align: center;">R 26 E</td></tr> <tr><td style="text-align: center;">S 13</td><td style="text-align: center;">S 18</td></tr> <tr style="border-top: 1px solid black;"><td style="text-align: center;">S 24</td><td style="text-align: center;">S 19</td></tr> </table> <p style="text-align: center;">2002</p> <p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p> <hr/>	T 23 N		R 25 E	R 26 E	S 13	S 18	S 24	S 19
T 23 N									
R 25 E	R 26 E								
S 13	S 18								
S 24	S 19								
	<p>North, on record bearing, bet. secs. 13 and 18.</p> <p>Over rolling land.</p>								
40.00	<p>Point for the 1/4 sec. cor. of secs. 13 and 18, at record dist.; there is no remaining evidence of the original cor.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <table border="0" style="margin-left: auto; margin-right: auto;"> <tr><td colspan="2" style="text-align: center;">T 23 N</td></tr> <tr><td style="text-align: center;">R 25 E</td><td style="text-align: center;">R 26 E</td></tr> <tr><td colspan="2" style="text-align: center;">1/4</td></tr> <tr><td style="text-align: center;">S 13</td><td style="text-align: center;">S 18</td></tr> </table> <p style="text-align: center;">2002</p> <p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p>	T 23 N		R 25 E	R 26 E	1/4		S 13	S 18
T 23 N									
R 25 E	R 26 E								
1/4									
S 13	S 18								
80.00	<p>Point for the cor. of secs. 7, 12, 13 and 18, at record dist.; there is no remaining evidence of the original cor.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <table border="0" style="margin-left: auto; margin-right: auto;"> <tr><td colspan="2" style="text-align: center;">T 23 N</td></tr> <tr><td style="text-align: center;">R 25 E</td><td style="text-align: center;">R 26 E</td></tr> <tr><td style="text-align: center;">S 12</td><td style="text-align: center;">S 7</td></tr> <tr style="border-top: 1px solid black;"><td style="text-align: center;">S 13</td><td style="text-align: center;">S 18</td></tr> </table> <p style="text-align: center;">2002</p> <p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p> <hr/> <p>North, on record bearing, bet. secs. 7 and 12.</p>	T 23 N		R 25 E	R 26 E	S 12	S 7	S 13	S 18
T 23 N									
R 25 E	R 26 E								
S 12	S 7								
S 13	S 18								

Dependent Resurvey of the West Boundary,
T. 23 N., R. 26 E., Gila and Salt River Meridian, Arizona

CHAINS	<p>Over rolling and broken land.</p>										
40.00	<p>Point for the 1/4 sec. cor. of secs. 7 and 12, at record dist.; there is no remaining evidence of the original cor.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center; margin: 10px 0;"> <table style="margin: auto; border-collapse: collapse;"> <tr><td colspan="2">T 23 N</td></tr> <tr><td>R 25 E</td><td>R 26 E</td></tr> <tr><td colspan="2">1/4</td></tr> <tr><td>S 12</td><td> S 7</td></tr> </table> </div> <p style="text-align: center;">2002</p> <p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p>	T 23 N		R 25 E	R 26 E	1/4		S 12	S 7		
T 23 N											
R 25 E	R 26 E										
1/4											
S 12	S 7										
80.00	<p>Point for the cor. of secs. 1, 6, 7 and 12, at record dist.; there is no remaining evidence of the original cor.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center; margin: 10px 0;"> <table style="margin: auto; border-collapse: collapse;"> <tr><td colspan="2">T 23 N</td></tr> <tr><td>R 25 E</td><td> R 26 E</td></tr> <tr><td>S 1</td><td> S 6</td></tr> <tr><td colspan="2" style="border-top: 1px solid black;">S 12</td></tr> <tr><td colspan="2" style="border-top: 1px solid black;"> S 7</td></tr> </table> </div> <p style="text-align: center;">2002</p> <p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p> <p>Cor. is located 1.20 chs. S. and 20 lks. E. of the top of a ridge, bears NNE and SSW.</p> <hr style="width: 60%; margin: 10px auto;"/> <p>North, on record bearing, bet. secs. 1 and 6.</p> <p>Over rolling and broken land.</p>	T 23 N		R 25 E	R 26 E	S 1	S 6	S 12		S 7	
T 23 N											
R 25 E	R 26 E										
S 1	S 6										
S 12											
S 7											
40.00	<p>Point for the 1/4 sec. cor. of secs. 1 and 6, at record dist.; there is no remaining evidence of the original cor.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p>										

**Dependent Resurvey of the West Boundary,
T. 23 N., R. 26 E., Gila and Salt River Meridian, Arizona**

CHAINS	
80.00	<p align="center">T 23 N R 25 E R 26 E 1/4 S 1 S 6</p> <p align="center">2002</p> <p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p> <p>Point for the cor. of Tps. 23 and 24 N., Rs. 25 and 26 E., at record dist.; there is no remaining evidence of the original cor.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p align="center">T 24 N R 25 E R 26 E S 36 S 31 ----- S 1 S 6 T 23 N</p> <p align="center">2002</p> <p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p>
39.92	<hr/> <p align="center">Dependent Resurvey of the North Boundary, T. 23 N., R. 26 E., Gila and Salt River Meridian, Arizona</p> <hr/> <p align="center">Restoring the survey executed by Frank Follman, in 1882</p> <hr/> <p>From the cor. of Tps. 23 and 24 N., Rs. 26 and 27 E., on the N. bdy. of the Tp., hereinbefore described.</p> <p>West, bet. secs. 1 and 36.</p> <p>Over rolling and broken land.</p> <p>Point for the 1/4 sec. cor. of secs. 1 and 36, at proportionate dist.; there is no remaining evidence of the original cor.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p>

Dependent Resurvey of the North Boundary,
T. 23 N., R. 26 E., Gila and Salt River Meridian, Arizona

CHAINS	
	<p style="text-align: center;">T 24 N R 26 E S 36 1/4 ——— S 1 T 23 N</p> <p style="text-align: center;">2002</p>
	<p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p>
55.07	<p>Barbed wire fence, 3 strands, bears N. and S.</p>
77.00	<p>Barbed wire fence, 5 strands, bears N. and S.</p>
79.84	<p>Point for the cor. of secs. 1, 2, 35 and 36, at proportionate dist.; there is no remaining evidence of the original cor.</p>
	<p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p>
	<p style="text-align: center;">T 24 N R 26 E S 35 S 36 ——— ——— S 2 S 1 T 23 N</p> <p style="text-align: center;">2002</p>
	<p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p> <hr/>
	<p>West, bet. secs. 2 and 35.</p>
	<p>Over rolling and broken land.</p>
39.92	<p>Point for the 1/4 sec. cor. of secs. 2 and 35, at proportionate dist.; there is no remaining evidence of the original cor.</p>
	<p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p>
	<p style="text-align: center;">T 24 N R 26 E S 35 1/4 ——— S 2 T 23 N</p> <p style="text-align: center;">2002</p>
	<p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p>

**Dependent Resurvey of the North Boundary,
T. 23 N., R. 26 E., Gila and Salt River Meridian, Arizona**

CHAINS											
79.84	<p>Point for the cor. of secs. 2, 3, 34 and 35, at proportionate dist.; there is no remaining evidence of the original cor.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center;"> <table style="margin: auto;"> <tr><td>T 24 N</td><td>R 26 E</td></tr> <tr><td>S 34</td><td>S 35</td></tr> <tr><td>S 3</td><td>S 2</td></tr> <tr><td colspan="2">T 23 N</td></tr> </table> <p>2002</p> </div> <p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p> <hr/> <p>West, bet. secs. 3 and 34.</p> <p>Over rolling and broken land.</p>	T 24 N	R 26 E	S 34	S 35	S 3	S 2	T 23 N			
T 24 N	R 26 E										
S 34	S 35										
S 3	S 2										
T 23 N											
14.40	<p>Apache County Road C281, a graded road, 20 ft. wide, bears NNE and SSW.</p>										
39.92	<p>Point for the 1/4 sec. cor. of secs. 3 and 34, at proportionate dist.; there is no remaining evidence of the original cor.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center;"> <table style="margin: auto;"> <tr><td>T 24 N</td><td>R 26 E</td></tr> <tr><td colspan="2">S 34</td></tr> <tr><td colspan="2">1/4 ———</td></tr> <tr><td colspan="2">S 3</td></tr> <tr><td colspan="2">T 23 N</td></tr> </table> <p>2002</p> </div> <p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p>	T 24 N	R 26 E	S 34		1/4 ———		S 3		T 23 N	
T 24 N	R 26 E										
S 34											
1/4 ———											
S 3											
T 23 N											
48.50	<p>Apache County Road C424, a graded road, 20 ft. wide, bears NE and SW.</p>										
79.84	<p>Point for cor. of secs. 3, 4, 33 and 34, at proportionate dist.; there is no remaining evidence of the original cor.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p>										

Dependent Resurvey of the North Boundary,
T. 23 N., R. 26 E., Gila and Salt River Meridian, Arizona

CHAINS	
	T 24 N R 26 E S 33 S 34 S 4 S 3 T 23 N 2002 Deposit a magnet in a white plastic case at the base of the stainless steel post. <hr/> West, bet. secs. 4 and 33. Over rolling and broken land.
39.92	Point for the 1/4 sec. cor. of secs. 4 and 33, at proportionate dist.; there is no remaining evidence of the original cor. Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd. <div style="text-align: center;"> T 24 N R 26 E S 33 1/4 ——— S 4 T 23 N 2002 </div> Deposit a magnet in a white plastic case at the base of the stainless steel post.
79.84	Point for the cor. of secs. 4, 5, 32 and 33, at proportionate dist.; there is no remaining evidence of the original cor. Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd. <div style="text-align: center;"> T 24 N R 26 E S 32 S 33 S 5 S 4 T 23 N 2002 </div> Deposit a magnet in a white plastic case at the base of the stainless steel post. <hr/> West, bet. secs. 5 and 32. Over rolling and broken land.

**Dependent Resurvey of the North Boundary,
T. 23 N., R. 26 E., Gila and Salt River Meridian, Arizona**

CHAINS	
39.92	<p>Point for the 1/4 sec. cor. of secs. 2 and 35, at proportionate dist.; there is no remaining evidence of the original cor.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T 24 N R 26 E S 32 1/4 ——— S 5 T 23 N</p> <p style="text-align: center;">2002</p> <p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p>
79.84	<p>Point for the cor. of secs. 1, 2, 35 and 36, at proportionate dist.; there is no remaining evidence of the original cor.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T 24 N R 26 E S 31 S 32 ——— ——— S 6 S 5 T 23 N</p> <p style="text-align: center;">2002</p> <p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p> <hr/> <p>West, bet. secs. 1 and 36.</p> <p>Over rolling and broken land.</p>
39.92	<p>Point for the 1/4 sec. cor. of secs. 1 and 36, at proportionate dist.; there is no remaining evidence of the original cor.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T 24 N R 26 E S 31 1/4 ——— S 6 T 23 N</p> <p style="text-align: center;">2002</p>

**Dependent Resurvey of the North Boundary,
T. 23 N., R. 26 E., Gila and Salt River Meridian, Arizona**

CHAINS	
78.10	<p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p> <p>The cor. of Tps. 23 and 24 N., Rs. 25 and 26 E., hereinbefore described.</p> <hr/> <p style="text-align: center;">Dependent Resurvey of the Subdivisional Lines, T. 23 N., R. 26 E., Gila and Salt River Meridian, Arizona</p> <hr/> <p style="text-align: center;">Restoring the survey executed by Frank Follman, in 1882</p> <hr/> <p>From the cor. of secs. 1, 2, 35 and 36, on the S. bdy. of the Tp., hereinbefore described.</p> <p>N. 0°26' W., bet. secs. 35 and 36.</p> <p>Over rolling land.</p>
40.06	<p>Point for the 1/4 sec. cor. of secs. 35 and 36, at proportionate dist.; there is no remaining evidence of the original cor.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T 23 N R 26 E 1/4 S 35 S 36</p> <p style="text-align: center;">2003</p> <p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p>
80.12	<p>Point for the cor. of secs. 25, 26, 35 and 36, at proportionate dist.; there is no remaining evidence of the original cor.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T 23 N R 26 E S 26 S 25 S 35 S 36</p> <p style="text-align: center;">2003</p>

Dependent Resurvey of the Subdivisional Lines,
T. 23 N., R. 26 E., Gila and Salt River Meridian, Arizona

CHAINS	
	<p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p> <hr/>
	<p>From the cor. of secs. 25, 30, 31 and 36, on the E. bdy. of the Tp., hereinbefore described.</p> <p>S. 89°28' W., bet. secs. 25 and 36.</p> <p>Over rolling land.</p>
<p>40.18</p>	<p>Point for the 1/4 sec. cor. of secs. 25 and 36, at proportionate dist.; there is no remaining evidence of the original cor.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center;"> <p>T 23 N R 26 E</p> <p>S 25</p> <p>1/4 ———</p> <p>S 36</p> <p>2003</p> </div>
	<p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p>
<p>80.36</p>	<p>The cor. of secs. 25, 26, 35 and 36.</p> <hr/> <p>N. 0°25' E., bet. secs. 25 and 26.</p> <p>Over nearly level land.</p>
<p>40.06</p>	<p>Point for the 1/4 sec. cor. of secs. 25 and 26, at proportionate dist.; there is no remaining evidence of the original cor.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center;"> <p>T 23 N R 26 E</p> <p>1/4</p> <p>S 26 S 25</p> <p>2003</p> </div>
<p>41.60</p>	<p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p> <p>Wide Ruins Wash, 20 ft. wide, 4 ft. deep, drains W., thence gradually ascend into rolling land.</p>

**Dependent Resurvey of the Subdivisional Lines,
T. 23 N., R. 26 E., Gila and Salt River Meridian, Arizona**

CHAINS									
80.12	<p>Point for the cor. of secs. 23, 24, 25 and 26, at proportionate dist.; there is no remaining evidence of the original cor.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center;"> <table style="margin: auto;"> <tr><td>T 23 N</td><td>R 26 E</td></tr> <tr><td>S 23</td><td>S 24</td></tr> <tr><td>S 26</td><td>S 25</td></tr> </table> <p>2003</p> </div> <p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p> <hr/> <p>From the cor. of secs. 19, 24, 25 and 30, on the E. bdy. of the Tp., hereinbefore described.</p> <p>S. 88°48' W., bet. secs. 24 and 25.</p> <p>Over nearly level land.</p>	T 23 N	R 26 E	S 23	S 24	S 26	S 25		
T 23 N	R 26 E								
S 23	S 24								
S 26	S 25								
34.00	Wide Ruins Wash, 50 ft. wide, 5 ft. deep, drains SSW.								
39.89	<p>Point for the 1/4 sec. cor. of secs. 24 and 25, at proportionate dist.; there is no remaining evidence of the original cor.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center;"> <table style="margin: auto;"> <tr><td>T 23 N</td><td>R 26 E</td></tr> <tr><td>S 24</td><td></td></tr> <tr><td>1/4</td><td>—</td></tr> <tr><td>S 25</td><td></td></tr> </table> <p>2003</p> </div> <p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p> <p>Thence gradually ascend out of the valley, into rolling land.</p>	T 23 N	R 26 E	S 24		1/4	—	S 25	
T 23 N	R 26 E								
S 24									
1/4	—								
S 25									
79.78	<p>The cor. of secs. 23, 24, 25 and 26.</p> <hr/> <p>N. 0°16' E., bet. secs. 23 and 24.</p> <p>Over rolling land, through scattered juniper.</p>								
40.06	<p>Point for the 1/4 sec. cor. of secs. 23 and 24, at proportionate dist.; there is no remaining evidence of the original cor.</p>								

Dependent Resurvey of the Subdivisional Lines,
T. 23 N., R. 26 E., Gila and Salt River Meridian, Arizona

CHAINS	
	<p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T 23 N R 26 E 1/4 S 23 S 24</p> <p style="text-align: center;">2003</p> <p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p>
80.12	<p>Point for the cor. of secs. 13, 14, 23 and 24, at proportionate dist.; there is no remaining evidence of the original cor.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T 23 N R 26 E S 14 S 13 ----- S 23 S 24</p> <p style="text-align: center;">2003</p> <p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p> <p>Cor. is located 1.40 chs. SE of a wash, 10 ft. wide, 3 ft. deep, drains WSW.</p>
39.78	<hr/> <p>From the cor. of secs. 13, 18, 19 and 24, on the E. bdy. of the Tp., hereinbefore described.</p> <p>S. 89°08' W., bet. secs. 13 and 24.</p> <p>Over rolling land, through scattered juniper.</p> <p>Point for the 1/4 sec. cor. of secs. 13 and 24, at proportionate dist.; there is no remaining evidence of the original cor.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T 23 N R 26 E S 13 1/4 ——— S 24</p> <p style="text-align: center;">2003</p> <p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p>

**Dependent Resurvey of the Subdivisional Lines,
T. 23 N., R. 26 E., Gila and Salt River Meridian, Arizona**

CHAINS	
79.56	<p>The cor. of secs. 13, 14, 23 and 24.</p> <hr/> <p>N. 0°07' W., bet. secs. 13 and 14.</p> <p>Over rolling land, through scattered juniper.</p>
18.35	<p>Navajo Route 9401, a graded road, 25 ft. wide, bears NE and SW.</p>
40.06	<p>Point for the 1/4 sec. cor. of secs. 13 and 14, at proportionate dist.; there is no remaining evidence of the original cor.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T 23 N R 26 E 1/4 S 14 S 13</p> <p style="text-align: center;">2003</p> <p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p>
80.12	<p>Point for the cor. of secs. 11, 12, 13 and 14, at proportionate dist.; there is no remaining evidence of the original cor.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T 23 N R 26 E S 11 S 12 S 14 S 13</p> <p style="text-align: center;">2003</p> <p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p> <p>From this cor. point, a rebar, 1/2 in. diam., firmly set, projecting 4 ins. above ground, with no cap, for the SE cor. of a homesite lease, bears N. 44 45' W., 99.5 lks. dist.</p> <hr/> <p>From the cor. of secs. 7, 12, 13 and 18, on the E. bdy. of the Tp., hereinbefore described.</p> <p>S. 89°28' W., bet. secs. 12 and 13.</p> <p>Over rolling land, through scattered juniper.</p>
39.94	<p>Point for the 1/4 sec. cor. of secs. 12 and 13, at proportionate dist.; there is no remaining evidence of the original cor.</p>

Dependent Resurvey of the Subdivisional Lines,
T. 23 N., R. 26 E., Gila and Salt River Meridian, Arizona

CHAINS	
	<p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T 23 N R 26 E S 12 1/4 ——— S 13</p> <p style="text-align: center;">2003</p> <p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p>
79.88	<p>The cor. of secs. 11, 12, 13 and 14.</p> <hr/>
	<p>N. 0°13' E., bet. secs. 11 and 12.</p> <p>Over rolling and broken land, through scattered juniper.</p>
40.06	<p>Point for the 1/4 sec. cor. of secs. 11 and 12, at proportionate dist.; there is no remaining evidence of the original cor.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T 23 N R 26 E 1/4 S 11 S 12</p> <p style="text-align: center;">2003</p> <p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p>
80.12	<p>Point for the cor. of secs. 1, 2, 11 and 12, at proportionate dist.; there is no remaining evidence of the original cor.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T 23 N R 26 E S 2 S 1 ——— S 11 S 12</p> <p style="text-align: center;">2003</p> <p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p> <hr/>
	<p>From the cor. of secs. 1, 6, 7 and 12, on the E. bdy. of the Tp., hereinbefore described.</p>

Dependent Resurvey of the Subdivisional Lines,
T. 23 N., R. 26 E., Gila and Salt River Meridian, Arizona

CHAINS	<p>S. 89°47' W., bet. secs. 1 and 12.</p> <p>Over rolling and broken land, through scattered juniper.</p> <p>37.85 Trail road, bears SSE and NNW.</p> <p>39.86 Point for the 1/4 sec. cor. of secs. 1 and 12, at proportionate dist.; there is no remaining evidence of the original cor.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T 23 N R 26 E S 1 1/4 — S 12</p> <p style="text-align: center;">2003</p> <p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p> <p>79.72 The cor. of secs. 1, 2, 11 and 12.</p> <hr/> <p>N. 0°06' W., bet. secs. 1 and 2.</p> <p>Over rolling and broken land, through scattered juniper.</p> <p>40.06 Point for the 1/4 sec. cor. of secs 1 and 2, at proportionate dist.; there is no remaining evidence of the original cor.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T 23 N R 26 E 1/4 S 2 S 1</p> <p style="text-align: center;">2003</p> <p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p> <p>80.30 The cor. of secs. 1, 2, 35 and 36, on the N. bdy. of the Tp., hereinbefore described.</p> <hr/> <p>From the cor. of secs. 2, 3, 34 and 35, on the S. bdy. of the Tp., hereinbefore described.</p> <p>N. 0°40' W., bet. secs. 34 and 35.</p>
--------	---

**Dependent Resurvey of the Subdivisional Lines,
T. 23 N., R. 26 E., Gila and Salt River Meridian, Arizona**

CHAINS	
	Over rolling land, through scattered juniper.
31.90	Wide Ruins Wash, 15 ft. wide, 3 ft. deep, drains SW, thence over nearly level land.
40.65	Point for the 1/4 sec. cor. of secs. 34 and 35, at proportionate dist.; there is no remaining evidence of the original cor. Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd. <div style="text-align: center;"> T 23 N R 26 E 1/4 S 34 S 35 2003 </div>
	Deposit a magnet in a white plastic case at the base of the stainless steel post.
81.30	The cor. of secs. 26, 27, 34 and 35, monumented with a sandstone, 13 x 10 x 7 ins., firmly set, projecting 4 ins. above ground, mkd. 2 grooves on E. face and 2 grooves on S. face. At the corner point Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd. <div style="text-align: center;"> T 23 N R 26 E S 27 S 26 S 34 S 35 2003 </div>
	Deposit a magnet in a white plastic case at the base of the stainless steel post. Bury the original sandstone alongside the stainless steel post. Cor. is located 15 lks. N. of a trail road, bears NE and SW.
	From the cor. of secs. 25, 26, 35 and 36. N. 89°01' W., bet. secs. 26 and 35. Over nearly level land.
37.65	Trail road, bears NE and SW.
40.04	Point for the 1/4 sec. cor. of secs. 26 and 35, at proportionate dist.; there is no remaining evidence of the original cor.

Dependent Resurvey of the Subdivisional Lines,
T. 23 N., R. 26 E., Gila and Salt River Meridian, Arizona

CHAINS	
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.
	<p style="text-align: center;">T 23 N R 26 E S 26 1/4 ——— S 35</p>
	2003
	Deposit a magnet in a white plastic case at the base of the stainless steel post.
48.70	Wide Ruins Wash, 10 ft. wide, 2 ft. deep, drains WSW.
80.08	The cor. of secs. 26, 27, 34 and 35.
	<hr/> <p>N. 0°30' E., bet. secs. 26 and 27.</p>
	Over rolling land, through scattered juniper.
39.89	Point for the 1/4 sec. cor. of secs. 26 and 27, at proportionate dist.; there is no remaining evidence of the original cor.
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.
	<p style="text-align: center;">T 23 N R 26 E 1/4 S 27 S 26</p>
	2003
	Deposit a magnet in a white plastic case at the base of the stainless steel post.
79.78	Point for the cor. of secs. 22, 23, 26 and 27, at proportionate dist.; there is no remaining evidence of the original cor.
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.
	<p style="text-align: center;">T 23 N R 26 E S 22 S 23 S 27 S 26</p>
	2003

**Dependent Resurvey of the Subdivisional Lines,
T. 23 N., R. 26 E., Gila and Salt River Meridian, Arizona**

CHAINS	
	<p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p> <hr/> <p>From the cor. of secs. 23, 24, 25 and 26.</p> <p>N. 89°16' W., bet. secs. 23 and 26.</p> <p>Over rolling land.</p>
39.97	<p>Point for the 1/4 sec. cor. of secs. 23 and 26, at proportionate dist.; there is no remaining evidence of the original cor.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T 23 N R 26 E S 23 1/4 ——— S 26</p> <p style="text-align: center;">2003</p> <p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p>
79.94	<p>The cor. of secs. 22, 23, 26 and 27.</p> <hr/> <p>N. 0°04' E., bet. secs. 22 and 23.</p> <p>Over rolling and broken land, through scattered juniper.</p>
1.75	<p>Navajo Route 9401, a graded road, 20 ft. wide, bears NE and SW.</p>
39.89	<p>Point for the 1/4 sec. cor. of secs. 22 and 23, at proportionate dist.; there is no remaining evidence of the original cor.</p> <p style="text-align: center;">T 23 N R 26 E 1/4 S 22 S 23</p> <p style="text-align: center;">2003</p> <p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p> <p>Cor. is located 40 lks. S. of a wash, 10 ft wide, 30 ft. deep, drains SW.</p>
67.25	<p>Apache County Road C323, a graded road, 22 ft. wide, bears ENE and WSW.</p>

**Dependent Resurvey of the Subdivisional Lines,
T. 23 N., R. 26 E., Gila and Salt River Meridian, Arizona**

CHAINS									
79.78	<p>Point for the cor. of secs. 14, 15, 22 and 23, at proportionate dist.; there is no remaining evidence of the original cor.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center;"> <table style="margin: auto;"> <tr><td>T 23 N</td><td>R 26 E</td></tr> <tr><td>S 15</td><td>S 14</td></tr> <tr><td>S 22</td><td>S 23</td></tr> </table> <p>2003</p> </div> <p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p> <hr/> <p>From the cor. of secs. 13, 14, 23 and 24.</p> <p>N. 89°30' W., bet. secs. 14 and 23.</p> <p>Over rolling land.</p>	T 23 N	R 26 E	S 15	S 14	S 22	S 23		
T 23 N	R 26 E								
S 15	S 14								
S 22	S 23								
1.20	Wash, 10 ft. wide, 3 ft. deep, drains WSW.								
15.55	Navajo Route 9401, a graded road, 20 ft. wide, bears NE and SW.								
40.10	<p>Point for the 1/4 sec. cor. of secs. 14 and 23, at proportionate dist.; there is no remaining evidence of the original cor.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center;"> <table style="margin: auto;"> <tr><td>T 23 N</td><td>R 26 E</td></tr> <tr><td>S 14</td><td></td></tr> <tr><td>1/4</td><td>—</td></tr> <tr><td>S 23</td><td></td></tr> </table> <p>2003</p> </div> <p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p> <p>Cor. is located 2.70 chs. N. of Apache County Road C323, a graded road, 22 ft. wide, bears ESE and WNW.</p>	T 23 N	R 26 E	S 14		1/4	—	S 23	
T 23 N	R 26 E								
S 14									
1/4	—								
S 23									
80.20	<p>The cor. of secs. 14, 15, 22 and 23.</p> <hr/> <p>N. 0°03' W., bet. secs. 14 and 15.</p> <p>Over rolling land, through scattered juniper.</p>								

Dependent Resurvey of the Subdivisional Lines,
T. 23 N., R. 26 E., Gila and Salt River Meridian, Arizona

CHAINS	
39.89	<p>Point for the 1/4 sec. cor. of secs. 14 and 15, at proportionate dist.; there is no remaining evidence of the original cor.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T 23 N R 26 E 1/4 S 15 S 14</p> <p style="text-align: center;">2003</p> <p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p>
79.78	<p>Point for the cor. of secs. 10, 11, 14 and 15, at proportionate dist.; there is no remaining evidence of the original cor.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T 23 N R 26 E S 10 S 11 S 15 S 14</p> <p style="text-align: center;">2003</p> <p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p> <hr/> <p>From the cor. of secs. 11, 12, 13 and 14.</p> <p>N. 89°44' W., bet. secs. 11 and 14.</p> <p>Over rolling land, through scattered juniper.</p>
40.03	<p>Point for the 1/4 sec. cor. of secs. 11 and 14, at proportionate dist.; there is no remaining evidence of the original cor.</p> <p style="text-align: center;">T 23 N R 26 E S 11 1/4 ——— S 14</p> <p style="text-align: center;">2003</p> <p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p>
67.45	<p>Apache County Road C281, a graded road, 22 ft. wide, bears SSE and NNW.</p>

**Dependent Resurvey of the Subdivisional Lines,
T. 23 N., R. 26 E., Gila and Salt River Meridian, Arizona**

CHAINS	
80.06	<p>The cor. of secs. 10, 11, 14 and 15.</p> <hr/> <p>N. 0°18' E., bet. secs. 10 and 11.</p> <p>Over rolling land, through scattered juniper.</p>
31.85	<p>Apache County Road C281, a graded road, 22 ft. wide, bears ENE and WSW.</p>
39.89	<p>Point for the 1/4 sec. cor. of secs. 10 and 11, at proportionate dist.; there is no remaining evidence of the original cor.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T 23 N R 26 E 1/4 S 10 S 11</p> <p style="text-align: center;">2003</p> <p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p>
79.78	<p>Point for the cor. of secs. 2, 3, 10 and 11, at proportionate dist.; there is no remaining evidence of the original cor.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T 23 N R 26 E S 3 S 2 S 10 S 11</p> <p style="text-align: center;">2003</p> <p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p> <hr/> <p>From the cor. of secs. 1, 2, 11 and 12.</p> <p>N. 89°58' W., bet. secs. 2 and 11.</p> <p>Over rolling and broken land.</p>
39.97	<p>Point for the 1/4 sec. cor. of secs. 2 and 11, at proportionate dist.; there is no remaining evidence of the original cor.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p>

**Dependent Resurvey of the Subdivisional Lines,
T. 23 N., R. 26 E., Gila and Salt River Meridian, Arizona**

CHAINS	
	T 23 N R 26 E S 2 1/4 ——— S 11 2003
	Deposit a magnet in a white plastic case at the base of the stainless steel post.
79.94	The cor. of secs. 2, 3, 10 and 11.
	<hr/> N. 0°02' W., bet. secs. 2 and 3. Over rolling and broken land, through scattered juniper.
39.89	Point for the 1/4 sec. cor. of secs. 2 and 3, at proportionate dist.; there is no remaining evidence of the original cor.
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.
	T 23 N R 26 E 1/4 S 3 S 2 2003
	Deposit a magnet in a white plastic case at the base of the stainless steel post.
80.24	The cor. of secs. 2, 3, 34 and 35, on the N. bdy. of the Tp., hereinbefore described.
	<hr/> From the cor. of secs. 3, 4, 33 and 34, on the S. bdy. of the Tp., hereinbefore described. N. 1°02' W., bet. secs. 33 and 34. Over nearly level land.
38.95	Trail road, bears E. and W.
40.59	Point for the 1/4 sec. cor. of secs. 33 and 34, at proportionate dist.; there is no remaining evidence of the original cor.
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.

Dependent Resurvey of the Subdivisional Lines,
T. 23 N., R. 26 E., Gila and Salt River Meridian, Arizona

CHAINS	
	T 23 N R 26 E 1/4 S 33 S 34 2003 Deposit a magnet in a white plastic case at the base of the stainless steel post.
47.40	Navajo Route 9401, a graded road, 20 ft. wide, bears NE and SW, thence gradually ascend into rolling land.
81.18	The cor. of secs. 27, 28, 33 and 34, monumented with a sandstone, 16 x 8 x 7 ins., firmly set, projecting 6 ins. above ground, mkd. 1 groove on S. face and 3 grooves on E. face. At the corner point Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd. <div style="text-align: center;"> T 23 N R 26 E S 28 S 27 --- S 33 S 34 2003 </div> Deposit a magnet in a white plastic case at the base of the stainless steel post. Bury the original sandstone alongside the stainless steel post.
40.13	<hr/> From the cor. of secs. 26, 27, 34 and 35. N. 89°58' W., bet. secs. 27 and 34. Over rolling land. Point for the 1/4 sec. cor. of secs. 27 and 34, at proportionate dist.; a sandstone, 17 x 14 x 3 ins., mkd. 1/4 on up face, lying loose nearby. Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd. <div style="text-align: center;"> T 23 N R 26 E S 27 1/4 ——— S 34 2003 </div>

**Dependent Resurvey of the Subdivisional Lines,
T. 23 N., R. 26 E., Gila and Salt River Meridian, Arizona**

CHAINS	
	<p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p> <p>Destroy the original sandstone.</p> <p>Cor. is located 1.60 chs. S. of a trail road, bears E. and W.</p>
53.60	Navajo Route 9401, a graded road, 22 ft. wide, bears NE and SW.
80.26	The cor. of secs. 27, 28, 33 and 34.
	<hr/> <p>N. 0°32' E., bet. secs. 27 and 28.</p> <p>Over rolling and broken land, through scattered juniper.</p>
39.95	<p>Point for the 1/4 sec. cor. of secs. 27 and 28, at proportionate dist.; there is no remaining evidence of the original cor.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T 23 N R 26 E 1/4 S 28 S 27</p> <p style="text-align: center;">2003</p>
	<p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p>
79.90	<p>Point for the cor. of secs. 21, 22, 27 and 28, at proportionate dist.; there is no remaining evidence of the original cor.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T 23 N R 26 E S 21 S 22 S 28 S 27</p> <p style="text-align: center;">2003</p>
	<p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p> <hr/> <p>From the cor. of secs. 22, 23, 26 and 27.</p> <p>N. 89°53' W., bet. secs. 22 and 27.</p> <p>Over rolling and broken land, through scattered juniper.</p>

**Dependent Resurvey of the Subdivisional Lines,
T. 23 N., R. 26 E., Gila and Salt River Meridian, Arizona**

CHAINS	
1.75	Navajo Route 9401, a graded road, 22 ft. wide, bears NE and SW.
40.10	Point for the 1/4 sec. cor. of secs. 22 and 27, at proportionate dist.; there is no remaining evidence of the original cor. Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd. <div style="text-align: center;"> T 23 N R 26 E S 22 1/4 ——— S 27 2003 </div> Deposit a magnet in a white plastic case at the base of the stainless steel post.
80.20	The cor. of secs. 21, 22, 27 and 28. <hr/> N. 0°25' E., bet. secs. 21 and 22. Over rolling and broken land, through scattered juniper.
12.25	Apache County Road C323, a graded road, 20 ft. wide, bears NNE and SSW.
39.95	Point for the 1/4 sec. cor. of secs. 21 and 22, at proportionate dist.; there is no remaining evidence of the original cor. Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd. <div style="text-align: center;"> T 23 N R 26 E 1/4 S 21 S 22 2003 </div> Deposit a magnet in a white plastic case at the base of the stainless steel post.
79.90	Point for the cor. of secs. 15, 16, 21 and 22, at proportionate dist.; there is no remaining evidence of the original cor. Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.

Dependent Resurvey of the Subdivisional Lines,
T. 23 N., R. 26 E., Gila and Salt River Meridian, Arizona

CHAINS	
	<p style="text-align: center;">T 23 N R 26 E S 16 S 15 ----- S 21 S 22</p> <p style="text-align: center;">2003</p>
	<p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p> <hr/>
<p>39.85</p>	<p>From the cor. of secs. 14, 15, 22 and 23.</p> <p>N. 89°48' W., bet. secs. 15 and 22.</p> <p>Over rolling and broken land, through scattered juniper.</p> <p>Point for the 1/4 sec. cor. of secs. 15 and 22, at proportionate dist.; there is no remaining evidence of the original cor.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p>
	<p style="text-align: center;">T 23 N R 26 E S 15 1/4 ——— S 22</p> <p style="text-align: center;">2003</p>
<p>79.70</p>	<p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p> <hr/> <p>The cor. of secs. 15, 16, 21 and 22.</p> <hr/>
	<p>N. 0°06' E., bet. secs. 15 and 16.</p> <p>Over rolling and broken land, through scattered juniper.</p>
<p>39.95</p>	<p>Point for the 1/4 sec. cor. of secs. 15 and 16, at proportionate dist.; there is no remaining evidence of the original cor.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p>
	<p style="text-align: center;">T 23 N R 26 E 1/4 S 16 S 15</p> <p style="text-align: center;">2003</p>

Dependent Resurvey of the Subdivisional Lines,
T. 23 N., R. 26 E., Gila and Salt River Meridian, Arizona

CHAINS	<p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p>								
79.90	<p>Point for the cor. of secs. 9, 10, 15 and 16, at proportionate dist.; there is no remaining evidence of the original cor.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center; margin: 10px 0;"> <table style="margin: auto; border-collapse: collapse;"> <tr> <td style="padding: 0 10px;">T 23 N</td> <td style="padding: 0 10px;">R 26 E</td> </tr> <tr> <td style="padding: 0 10px; border-right: 1px solid black;">S 9</td> <td style="padding: 0 10px;">S 10</td> </tr> <tr> <td style="padding: 0 10px; border-right: 1px solid black;">S 16</td> <td style="padding: 0 10px;">S 15</td> </tr> </table> </div> <p style="text-align: center; margin: 5px 0;">2003</p> <p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p> <hr style="width: 80%; margin: 10px auto;"/> <p>From the cor. of secs. 10, 11, 14 and 15.</p> <p>N. 89°44' W., bet. secs. 10 and 15.</p> <p>Over rolling and broken land, through scattered juniper.</p>	T 23 N	R 26 E	S 9	S 10	S 16	S 15		
T 23 N	R 26 E								
S 9	S 10								
S 16	S 15								
39.74	<p>Point for the 1/4 sec. cor. of secs. 10 and 15, at proportionate dist.; there is no remaining evidence of the original cor.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center; margin: 10px 0;"> <table style="margin: auto; border-collapse: collapse;"> <tr> <td style="padding: 0 10px;">T 23 N</td> <td style="padding: 0 10px;">R 26 E</td> </tr> <tr> <td style="padding: 0 10px;"></td> <td style="padding: 0 10px;">S 10</td> </tr> <tr> <td style="padding: 0 10px;">1/4</td> <td style="padding: 0 10px;">—</td> </tr> <tr> <td style="padding: 0 10px;"></td> <td style="padding: 0 10px;">S 15</td> </tr> </table> </div> <p style="text-align: center; margin: 5px 0;">2003</p> <p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p>	T 23 N	R 26 E		S 10	1/4	—		S 15
T 23 N	R 26 E								
	S 10								
1/4	—								
	S 15								
79.48	<p>The cor. of secs. 9, 10, 15 and 16.</p> <hr style="width: 80%; margin: 10px auto;"/> <p>N. 0°07' W., bet. secs. 9 and 10.</p> <p>Over rolling and broken land, through scattered juniper.</p>								
39.94	<p>Point for the 1/4 sec. cor. of secs. 9 and 10, at proportionate dist.; there is no remaining evidence of the original cor.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p>								

**Dependent Resurvey of the Subdivisional Lines,
T. 23 N., R. 26 E., Gila and Salt River Meridian, Arizona**

CHAINS	
	T 23 N R 26 E 1/4 S 9 S 10 2003 Deposit a magnet in a white plastic case at the base of the stainless steel post.
79.88	Point for the cor. of secs. 3, 4, 9 and 10, at proportionate dist.; there is no remaining evidence of the original cor. Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd. <div style="text-align: center;"> T 23 N R 26 E S 4 S 3 --- S 9 S 10 2003 </div> Deposit a magnet in a white plastic case at the base of the stainless steel post.
	<hr/> From the cor. of secs. 2, 3, 10 and 11. N. 89°39' W., bet. secs. 3 and 10. Over rolling and broken land, through scattered juniper.
28.75	Apache County Road C281, a graded road, 20 ft. wide, bears NNE and SSW.
35.92	Woven wire and barbed wire fence, 2 strands, bears SE and NW.
40.02	Point for the 1/4 sec. cor. of secs. 3 and 10, at proportionate dist.; there is no remaining evidence of the original cor. Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd. <div style="text-align: center;"> T 23 N R 26 E S 3 1/4 ——— S 10 2003 </div> Deposit a magnet in a white plastic case at the base of the stainless steel post.

**Dependent Resurvey of the Subdivisional Lines,
T. 23 N., R. 26 E., Gila and Salt River Meridian, Arizona**

CHAINS	
	Cor. is located 95 lks. S. of a woven wire fence with 2 strands barbed wire, bears NE and SW.
41.25	The same woven wire and barbed wire fence, bears NE and SW.
80.04	The cor. of secs. 3, 4, 9 and 10.
	<hr/>
	N. 0°05' E., bet. secs. 3 and 4.
	Over rolling and broken land, through scattered juniper.
37.60	Apache County Road C424, a graded road, 20 ft. wide, bears NNE and SSW.
39.95	Point for the 1/4 sec. cor. of secs. 3 and 4, at proportionate dist.; there is no remaining evidence of the original cor.
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.
	T 23 N R 26 E 1/4 S 4 S 3 2003
	Deposit a magnet in a white plastic case at the base of the stainless steel post.
79.76	The cor. of secs. 3, 4, 33 and 34, on the N. bdy. of the Tp., hereinbefore described.
	<hr/>
	From the cor. of secs. 4, 5, 32 and 33, on the S. bdy. of the Tp., hereinbefore described.
	N. 0°43' W., bet. secs. 32 and 33.
	Over gently rolling land.
40.04	Point for the 1/4 sec. cor. of secs. 32 and 33, at proportionate dist.; there is no remaining evidence of the original cor.
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.
	T 23 N R 26 E 1/4 S 32 S 33 2003

**Dependent Resurvey of the Subdivisional Lines,
T. 23 N., R. 26 E., Gila and Salt River Meridian, Arizona**

CHAINS									
	Deposit a magnet in a white plastic case at the base of the stainless steel post.								
80.08	Point for the cor. of secs. 28, 29, 32 and 33, at proportionate dist.; there is no remaining evidence of the original cor. Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd. <div style="text-align: center;"> <table style="margin-left: auto; margin-right: auto;"> <tr> <td>T 23 N</td> <td>R 26 E</td> </tr> <tr> <td style="border-right: 1px solid black;">S 29</td> <td>S 28</td> </tr> <tr> <td style="border-right: 1px solid black;">S 32</td> <td>S 33</td> </tr> </table> <p>2003</p> </div>	T 23 N	R 26 E	S 29	S 28	S 32	S 33		
T 23 N	R 26 E								
S 29	S 28								
S 32	S 33								
	Deposit a magnet in a white plastic case at the base of the stainless steel post.								
	From the cor. of secs. 27, 28, 33 and 34. S. 89°20' W., bet. secs. 28 and 33. Over rolling and broken land, through scattered juniper.								
39.64	Point for the 1/4 sec. cor. of secs. 28 and 33, at proportionate dist.; there is no remaining evidence of the original cor. Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd. <div style="text-align: center;"> <table style="margin-left: auto; margin-right: auto;"> <tr> <td>T 23 N</td> <td>R 26 E</td> </tr> <tr> <td></td> <td>S 28</td> </tr> <tr> <td>1/4</td> <td>—</td> </tr> <tr> <td></td> <td>S 33</td> </tr> </table> <p>2003</p> </div>	T 23 N	R 26 E		S 28	1/4	—		S 33
T 23 N	R 26 E								
	S 28								
1/4	—								
	S 33								
	Deposit a magnet in a white plastic case at the base of the stainless steel post.								
79.28	The cor. of secs. 28, 29, 32 and 33. N. 0°36' E., bet. secs. 28 and 29. Over gently rolling land.								
35.60	Apache County Road C323, a graded road, 20 ft. wide, bears ENE and WSW.								
38.19	Barbed wire fence, 4 strands, bears E. and W.								

**Dependent Resurvey of the Subdivisional Lines,
T. 23 N., R. 26 E., Gila and Salt River Meridian, Arizona**

CHAINS	
40.04	<p>Point for the 1/4 sec. cor. of secs. 28 and 29, at proportionate dist.; there is no remaining evidence of the original cor.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T 23 N R 26 E 1/4 S 29 S 28</p> <p style="text-align: center;">2003</p> <p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p>
80.08	<p>Point for the cor. of secs. 20, 21, 28 and 29, at proportionate dist.; there is no remaining evidence of the original cor.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T 23 N R 26 E S 20 S 21 S 29 S 28</p> <p style="text-align: center;">2003</p> <p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p> <hr/> <p>From the cor. of secs. 21, 22, 27 and 28.</p> <p>S. 89°55' W., bet. secs. 21 and 28.</p> <p>Over rolling land.</p>
9.00	<p>Apache County Road C323, a graded road, 20 ft. wide, bears NE and SW.</p>
39.63	<p>The 1/4 sec. cor of secs. 21 and 28, monumented with a sandstone, 14 x 9 x 5 ins., loosely set, projecting 9 ins. above ground, dimly mkd. 1/4 on N. face.</p> <p>At the corner point</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p>

**Dependent Resurvey of the Subdivisional Lines,
T. 23 N., R. 26 E., Gila and Salt River Meridian, Arizona**

CHAINS	
	T 23 N R 26 E S 21 1/4 ——— S 28 2003
	Deposit a magnet in a white plastic case at the base of the stainless steel post. Bury the original sandstone alongside the stainless steel post. <hr style="width: 20%; margin: auto;"/> S. 89°01' W., beginning new measurement. Over rolling land.
39.53	The cor. of secs. 20, 21, 28 and 29. <hr style="width: 80%; margin: auto;"/> N. 0°13' E., bet. secs. 20 and 21. Over rolling and broken land, through scattered juniper.
40.03	Point for the 1/4 sec. cor. of secs. 20 and 21, at proportionate dist.; there is no remaining evidence of the original cor. Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.
	T 23 N R 26 E 1/4 S 20 S 21 2003
80.06	Deposit a magnet in a white plastic case at the base of the stainless steel post. Point for the cor. of secs. 16, 17, 20 and 21, at proportionate dist.; there is no remaining evidence of the original cor. Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.
	T 23 N R 26 E S 17 S 16 <hr style="width: 20%; margin: auto;"/> S 20 S 21 2003

**Dependent Resurvey of the Subdivisional Lines,
T. 23 N., R. 26 E., Gila and Salt River Meridian, Arizona**

CHAINS	
	<p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p> <hr/> <p>From the cor. of secs. 15, 16, 21 and 22.</p> <p>S. 89°36' W., bet. secs. 16 and 21.</p> <p>Over rolling and broken land, through scattered juniper.</p>
39.70	<p>Point for the 1/4 sec. cor. of secs. 16 and 21, at proportionate dist.; there is no remaining evidence of the original cor.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T 23 N R 26 E S 16 1/4 ——— S 21</p> <p style="text-align: center;">2003</p> <p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p>
79.40	<p>The cor. of secs. 16, 17, 20 and 21.</p> <hr/> <p>N. 0°10' W., bet. secs. 16 and 17.</p> <p>Over nearly level land.</p>
40.03	<p>Point for the 1/4 sec. cor. of secs. 16 and 17, at proportionate dist.; there is no remaining evidence of the original cor.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T 23 N R 26 E 1/4 S 17 S 16</p> <p style="text-align: center;">2003</p> <p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p>
41.55	<p>Trail road, bears NNE and SSW.</p>
80.06	<p>Point for the cor. of secs. 8, 9, 16 and 17, at proportionate dist.; there is no remaining evidence of the original cor.</p>

Dependent Resurvey of the Subdivisional Lines,
T. 23 N., R. 26 E., Gila and Salt River Meridian, Arizona

CHAINS							
	<p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <table border="0" style="margin-left: auto; margin-right: auto;"> <tr> <td>T 23 N</td> <td>R 26 E</td> </tr> <tr> <td>S 8</td> <td>S 9</td> </tr> <tr> <td>S 17</td> <td>S 16</td> </tr> </table> <p style="text-align: center;">2003</p> <p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p> <hr/>	T 23 N	R 26 E	S 8	S 9	S 17	S 16
T 23 N	R 26 E						
S 8	S 9						
S 17	S 16						
	<p>From the cor. of secs. 9, 10, 15 and 16.</p> <p>S. 89°43' W., bet. secs. 9 and 16.</p> <p>Over rolling and broken land, through scattered juniper.</p>						
39.89	<p>Point for the 1/4 sec. cor. of secs. 9 and 16, at proportionate dist.; there is no remaining evidence of the original cor.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <table border="0" style="margin-left: auto; margin-right: auto;"> <tr> <td>T 23 N</td> <td>R 26 E</td> </tr> <tr> <td>S 9</td> <td>1/4 —</td> </tr> <tr> <td>S 16</td> <td></td> </tr> </table> <p style="text-align: center;">2003</p> <p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p>	T 23 N	R 26 E	S 9	1/4 —	S 16	
T 23 N	R 26 E						
S 9	1/4 —						
S 16							
79.78	<p>The cor. of secs. 8, 9, 16 and 17.</p> <hr/> <p>N. 0°02' E., bet. secs. 8 and 9.</p> <p>Over rolling and broken land, through scattered juniper.</p>						
30.70	<p>Apache County Road C424, a graded road, 20 ft. wide, bears ESE and WNW.</p>						
40.03	<p>Point for the 1/4 sec. cor. of secs. 8 and 9, at proportionate dist.; there is no remaining evidence of the original cor.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p>						

Dependent Resurvey of the Subdivisional Lines,
T. 23 N., R. 26 E., Gila and Salt River Meridian, Arizona

CHAINS	
	<p style="text-align: center;">T 23 N R 26 E 1/4 S 8 S 9</p> <p style="text-align: center;">2003</p>
80.06	<p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p> <p>Point for the cor. of secs. 4, 5, 8 and 9, at proportionate dist.; there is no remaining evidence of the original cor.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p>
	<p style="text-align: center;">T 23 N R 26 E S 5 S 4 S 8 S 9</p> <p style="text-align: center;">2003</p> <p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p> <hr/> <p>From the cor. of secs. 3, 4, 9 and 10.</p> <p>S. 89°51' W., bet. secs. 4 and 9.</p> <p>Over rolling and broken land, through scattered juniper.</p>
16.80	<p>Apache County Road C424, a graded road, 20 ft. wide, bears NE and SW.</p>
36.75	<p>Trail road, bears ENE and WSW.</p>
39.78	<p>Point for the 1/4 sec. cor. of secs. 4 and 9, at proportionate dist.; there is no remaining evidence of the original cor.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T 23 N R 26 E S 4 1/4 ——— S 9</p> <p style="text-align: center;">2003</p>
42.45	<p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p> <p>Trail road, bears NE and SW.</p>

**Dependent Resurvey of the Subdivisional Lines,
T. 23 N., R. 26 E., Gila and Salt River Meridian, Arizona**

CHAINS	
43.25	From this point, the NE cor. of an octagonal wood frame hogan, bears South, 2.33 chs., with 10 ft. sides, bears SE and WNW.
44.80	From this point, the NW cor. of a wood frame house, 36 x 24 ft., bears South, 2.24 chs. dist., with long side bears ESE.
46.90	From this point, the SE cor. of a stucco house, 30 x 30 ft., bears North, 57 lks. dist., with sides bears N and W.
79.56	The cor. of secs. 4, 5, 8 and 9.
	<hr/> N. 0°08' W., bet. secs. 4 and 5. Over rolling and broken land, through scattered juniper.
40.04	Point for the 1/4 sec. cor. 4 and 5, at proportionate dist.; there is no remaining evidence of the original cor. Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.
	T 23 N R 26 E 1/4 S 5 S 4 2003
	Deposit a magnet in a white plastic case at the base of the stainless steel post.
79.97	The cor. of secs. 4, 5, 32 and 33, on the N. bdy. of the Tp., hereinbefore described.
	<hr/> From the cor. of secs. 5, 6, 31 and 32, on the S. bdy. of the Tp., hereinbefore described. N. 0°29' W., bet. secs. 31 and 32. Over nearly level land.
40.04	Point for the 1/4 sec. cor. of secs. 31 and 32, at proportionate dist.; there is no remaining evidence of the original cor. Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.
	T 23 N R 26 E 1/4 S 31 S 32 2003

Dependent Resurvey of the Subdivisional Lines,
T. 23 N., R. 26 E., Gila and Salt River Meridian, Arizona

CHAINS									
	Deposit a magnet in a white plastic case at the base of the stainless steel post.								
79.20	Trail road, bears E. and W.								
80.08	Point for the cor. of secs. 29, 30, 31 and 32, at proportionate dist.; there is no remaining evidence of the original cor. Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd. <div style="text-align: center;"> <table border="0"> <tr><td>T 23 N</td><td>R 26 E</td></tr> <tr><td>S 30</td><td>S 29</td></tr> <tr><td>S 31</td><td>S 32</td></tr> </table> <p>2003</p> </div>	T 23 N	R 26 E	S 30	S 29	S 31	S 32		
T 23 N	R 26 E								
S 30	S 29								
S 31	S 32								
	Deposit a magnet in a white plastic case at the base of the stainless steel post.								
	<hr/> From the cor. of secs. 28, 29, 32 and 33. N. 89°52' W., bet. secs. 29 and 32. Over rolling land, through scattered juniper.								
39.71	Point for the 1/4 sec. cor. of secs. 29 and 32, at proportionate dist.; there is no remaining evidence of the original cor. Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd. <div style="text-align: center;"> <table border="0"> <tr><td>T 23 N</td><td>R 26 E</td></tr> <tr><td>S 29</td><td></td></tr> <tr><td>1/4</td><td>—</td></tr> <tr><td>S 32</td><td></td></tr> </table> <p>2003</p> </div>	T 23 N	R 26 E	S 29		1/4	—	S 32	
T 23 N	R 26 E								
S 29									
1/4	—								
S 32									
	Deposit a magnet in a white plastic case at the base of the stainless steel post.								
79.42	The cor. of secs. 29, 30, 31 and 32. <hr/> N. 89°57' W., bet. secs. 30 and 31. Over rolling land, through scattered juniper.								
5.95	Trail road, bears ESE and curves right.								

**Dependent Resurvey of the Subdivisional Lines,
T. 23 N., R. 26 E., Gila and Salt River Meridian, Arizona**

CHAINS	
39.75	<p>Point for the 1/4 sec. cor. of secs. 30 and 31, at proportionate dist.; there is no remaining evidence of the original cor.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T 23 N R 26 E S 30 1/4 ——— S 31</p> <p style="text-align: center;">2003</p> <p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p>
61.30	Trail road, bears ESE and WNW.
77.99	The cor. of secs. 25, 30, 31 and 36, on the W. bdy. of the Tp., hereinbefore described.
	<hr/> <p>From the cor. of secs. 29, 30, 31 and 32.</p> <p>N. 0°19' E., bet. secs. 29 and 30.</p> <p>Over rolling land, through scattered juniper.</p>
40.04	<p>Point for the 1/4 sec. cor. of secs. 29 and 30, at proportionate dist.; there is no remaining evidence of the original cor.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T 23 N R 26 E 1/4 S 30 S 29</p> <p style="text-align: center;">2003</p> <p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p>
65.90	Apache County Road C323, a graded road, 20 ft. wide, bears ENE and WSW.
80.08	<p>Point for the cor. of secs. 19, 20, 29 and 30, at proportionate dist.; a sandstone, 14 x 9 x 9 ins., mkd. 2 grooves on one face and 5 grooves on adjacent face, lying loose nearby.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p>

Dependent Resurvey of the Subdivisional Lines,
T. 23 N., R. 26 E., Gila and Salt River Meridian, Arizona

CHAINS	
	<p style="text-align: center;">T 23 N R 26 E S 19 S 20 ----- S 30 S 29</p>
	<p style="text-align: center;">2003</p>
	<p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p>
	<p>Destroy the original sandstone.</p>
	<hr/> <p>From the cor. of secs. 20, 21, 28 and 29.</p>
	<p>N. 89°51' W., bet. secs. 20 and 29.</p>
	<p>Over rolling land.</p>
<p>39.90</p>	<p>Point for the 1/4 sec. cor. of secs. 20 and 29, at proportionate dist.; there is no remaining evidence of the original cor.</p>
	<p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p>
	<p style="text-align: center;">T 23 N R 26 E S 20 1/4 ——— S 29</p>
	<p style="text-align: center;">2003</p>
	<p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p>
<p>57.69</p>	<p>From this point, the well casing of a water well, 6 ins. diam., bears South, 1.5 lks. dist., with windmill mkd. No. 17M 117.</p>
<p>79.80</p>	<p>The cor. of secs. 19, 20, 29 and 30.</p>
	<hr/> <p>S. 89°58' W., bet. secs. 19 and 30.</p>
	<p>Over rolling land, through scattered juniper.</p>
<p>39.82</p>	<p>Point for the 1/4 sec. cor. of secs. 19 and 30, at proportionate dist.; there is no remaining evidence of the original cor.</p>
	<p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p>

**Dependent Resurvey of the Subdivisional Lines,
T. 23 N., R. 26 E., Gila and Salt River Meridian, Arizona**

CHAINS	
	T 23 N R 26 E S 19 1/4 ——— S 30 2003
	Deposit a magnet in a white plastic case at the base of the stainless steel post.
61.90	Apache County Road C323, a graded road, 20 ft. wide, bears ESE and WNW.
78.34	The cor. of secs. 19, 24, 25 and 30, on the W. bdy. of the Tp., hereinbefore described.
	<hr/> From the cor. of secs. 19, 20, 29 and 30. N. 0°01' W., bet. secs. 19 and 20. Over nearly level land.
40.04	Point for the 1/4 sec. cor. of secs. 19 and 20, at proportionate dist.; there is no remaining evidence of the original cor. Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.
	T 23 N R 26 E 1/4 S 19 S 20 2003
	Deposit a magnet in a white plastic case at the base of the stainless steel post.
80.08	Point for the cor. of secs. 17, 18, 19 and 20, at proportionate dist.; there is no remaining evidence of the original cor. Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.
	T 23 N R 26 E S 18 S 17 ——— S 19 S 20 2003

**Dependent Resurvey of the Subdivisional Lines,
T. 23 N., R. 26 E., Gila and Salt River Meridian, Arizona**

CHAINS	
40.06	<p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p> <hr/> <p>From the cor. of secs. 16, 17, 20 and 21.</p> <p>N. 89°51' W., bet. secs. 17 and 20.</p> <p>Over rolling land.</p> <p>Point for the 1/4 sec. cor. of secs. 17 and 20, at proportionate dist.; there is no remaining evidence of the original cor.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center;"> <p>T 23 N R 26 E</p> <p>S 17</p> <p>1/4 ———</p> <p>S 20</p> <p>2003</p> </div>
80.12	<p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p> <p>The cor. of secs. 17, 18, 19 and 20.</p> <hr/> <p>S. 89°55' W., bet. secs. 18 and 19.</p> <p>Over nearly level land.</p>
2.80	Trail road, bears SSE and NNW.
3.00	Barbed wire fence, 5 strands, bears N. and S.
39.88	<p>Point for the 1/4 sec. cor. of secs. 18 and 19, at proportionate dist.; there is no remaining evidence of the original cor.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center;"> <p>T 23 N R 26 E</p> <p>S 18</p> <p>1/4 ———</p> <p>S 19</p> <p>2003</p> </div> <p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p>

**Dependent Resurvey of the Subdivisional Lines,
T. 23 N., R. 26 E., Gila and Salt River Meridian, Arizona**

CHAINS	
78.30	<p>The cor. of secs. 13, 18, 19 and 24, on the W. bdy. of the Tp., hereinbefore described.</p> <hr/> <p>From the cor. of secs. 17, 18, 19 and 20. N. 0°02' W., bet. secs. 17 and 18. Over nearly level land.</p>
40.04	<p>Point for the 1/4 sec. cor. of secs. 17 and 18, at proportionate dist.; there is no remaining evidence of the original cor.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T 23 N R 26 E 1/4 S 18 S 17 2003</p> <p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p> <p>Cor. is located 3.20 chs. E. of a trail road, bears SSE and NNW.</p>
80.08	<p>Point for the cor. of secs. 7, 8, 17 and 18, at proportionate dist.; there is no remaining evidence of the original cor.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T 23 N R 26 E S 7 S 8 S 18 S 17 2003</p> <p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p> <hr/>
39.96	<p>From the cor. of secs. 8, 9, 16 and 17. N. 89°50' W., bet. secs. 8 and 17. Over rolling and broken land, through scattered juniper.</p> <p>Point for the 1/4 sec. cor. of secs. 8 and 17, at proportionate dist.; there is no remaining evidence of the original cor.</p>

**Dependent Resurvey of the Subdivisional Lines,
T. 23 N., R. 26 E., Gila and Salt River Meridian, Arizona**

CHAINS	
	<p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T 23 N R 26 E S 8 1/4 ——— S 17</p> <p style="text-align: center;">2003</p> <p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p>
79.92	<p>The cor. of secs. 7, 8, 17 and 18.</p> <hr/> <p>S. 89°51' W., bet. secs. 7 and 18.</p> <p>Over rolling land.</p>
2.35	Trail road, bears NNE and SSW.
2.50	Barbed wire fence, 4 strands, bears NNE and SSW.
39.92	<p>Point for the 1/4 sec. cor. of secs. 7 and 18, at proportionate dist.; there is no remaining evidence of the original cor.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T 23 N R 26 E S 7 1/4 ——— S 18</p> <p style="text-align: center;">2003</p> <p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p>
78.25	<p>The cor. of secs. 7, 12, 13 and 18, on the W. bdy. of the Tp., hereinbefore described.</p> <hr/> <p>From the cor. of secs. 7, 8, 17 and 18.</p> <p>N. 0°10' E., bet. secs. 7 and 8.</p> <p>Over nearly level land.</p>
15.35	Apache County Road C424, a graded road, 20 ft. wide, bears E. and W.

Dependent Resurvey of the Subdivisional Lines,
T. 23 N., R. 26 E., Gila and Salt River Meridian, Arizona

CHAINS	
40.04	<p>Point for the 1/4 sec. cor. of secs. 7 and 8, at proportionate dist.; there is no remaining evidence of the original cor.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T 23 N R 26 E 1/4 S 7 S 8 2003</p> <p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p> <p>Cor. is located 1.30 chs. W. of a trail road, bears NNE and SSW.</p>
80.08	<p>Point for the cor. of secs. 5, 6, 7 and 8, at proportionate dist.; there is no remaining evidence of the original cor.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T 23 N R 26 E S 6 S 5 ----- S 7 S 8 2003</p> <p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p> <hr/> <p>From the cor. of secs. 4, 5, 8 and 9.</p> <p>N. 89°49' W., bet. secs. 5 and 8.</p> <p>Over rolling land, through scattered juniper.</p>
39.86	<p>Point for the 1/4 sec. cor. of secs. 5 and 8, at proportionate dist.; there is no remaining evidence of the original cor.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T 23 N R 26 E S 5 1/4 ----- S 8 2003</p>

**Dependent Resurvey of the Subdivisional Lines,
T. 23 N., R. 26 E., Gila and Salt River Meridian, Arizona**

CHAINS	
	Deposit a magnet in a white plastic case at the base of the stainless steel post.
79.72	The cor. of secs. 5, 6, 7 and 8. <hr/>
	S. 89°48' W., bet. secs. 6 and 7. Over rolling land, through scattered juniper.
39.93	Point for the 1/4 sec. cor. of secs. 6 and 7, at proportionate dist.; there is no remaining evidence of the original cor. Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd. <div style="text-align: center;"> T 23 N R 26 E S 6 1/4 ——— S 7 2003 </div>
	Deposit a magnet in a white plastic case at the base of the stainless steel post.
78.47	The cor. of secs. 1, 6, 7 and 12, on the W. bdy. of the Tp., hereinbefore described. <hr/>
	From the cor. of secs. 5, 6, 7 and 8. N. 0°15' W., bet. secs. 5 and 6. Over nearly level land.
39.90	Trail road, bears SE and NW.
40.04	Point for the 1/4 sec. cor. of secs. 5 and 6, at proportionate dist.; there is no remaining evidence of the original cor. Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd. <div style="text-align: center;"> T 23 N R 26 E 1/4 S 6 S 5 2003 </div>
	Deposit a magnet in a white plastic case at the base of the stainless steel post.

**Dependent Resurvey of the Subdivisional Lines,
T. 23 N., R. 26 E., Gila and Salt River Meridian, Arizona**

CHAINS	
79.72	<p>The cor. of secs. 5, 6, 31 and 32, on the N. bdy. of the Tp., hereinbefore described.</p> <hr/> <p style="text-align: center;">GENERAL DESCRIPTION</p> <hr/> <p>The area surveyed is within the Navajo Indian Reservation and approximately 2 miles W. of the community of Wide Ruins, Arizona. The terrain is rolling and broken. The drainage is south and southwesterly in the township, with Wide Ruins Wash being the principal drainage.</p> <p>The elevation varies from 5900 to 6600 feet above sea level. The soil is sand and sandy clay. The timber consist of scattered juniper and piñon with undergrowth consisting of greasewood, cacti, scattered brush and native grasses, throughout the township.</p> <p>Principal access to the township is provided by Navajo Route 9401 and Apache County Road C424, graded roads, which enter the township from the east and northeast. From these two main roads, there are numerous trail roads throughout the township. There are no mining activities in this township and much of the area is used for grazing livestock with some permanent home sites in the area.</p> <p>The mean magnetic declination of $11 \frac{3}{4}^{\circ}$ E. was derived from the computer program GEOMAGIX, utilizing the World Magnetic Model for Epoch 2000 for the dates of survey.</p> <hr/>

**UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT**

FIELD ASSISTANTS

NAMES	CAPACITY
William F. Olver	Cadastral Surveyor
Daniel Bryan	Engineering Technician
Wilfred Chee	Engineering Technician
Edward Clarke	Engineering Technician
Reuben Mason	Engineering Technician
Barney Woodie	Engineering Technician

CERTIFICATE OF SURVEY

We, Jones Curtiss and Leonard R. Sandoval, Cadastral Surveyors, HEREBY CERTIFY upon honor, that in pursuance of special instructions bearing date of the 1st day of May, 2002 and supplemental special instructions bearing date of the 23rd day of September, 2002, we have dependently resurveyed the south, east, west and north boundaries, and the subdivisonal lines, T. 23 N., R. 26 E., of the Gila and Salt River Meridian, in the State of Arizona, which are represented in the foregoing field notes as having been executed by us and under our direction. Said survey has been made in strict conformity with said special instructions, supplemental special instructions, the Manual of Instructions for the Survey of the Public Lands of the United States, 1973, and in specific manner described in the foregoing field notes.

4-25-05
(Date)

Jones Curtiss
(Cadastral Surveyor)

4-25-05
(Date)

Leonard R. Sandoval
(Cadastral Surveyor)

CERTIFICATE OF APPROVAL

BUREAU OF LAND MANAGEMENT
Phoenix, Arizona

The foregoing field notes of the dependent resurvey of the south, east, west and north boundaries, and the subdivisonal lines, T. 23 N., R. 26 E., Gila and Salt River Meridian, in the State of Arizona, executed by Jones Curtiss and Leonard R. Sandoval, Cadastral Surveyors, having been critically examined and found correct, are hereby approved.

5/13/05
(Date)

Stephen K. Hansen
(Acting Chief Cadastral Surveyor of Arizona)

~~CERTIFICATE OF TRANSCRIPT~~

~~I CERTIFY That the foregoing transcript of the field notes of the above described surveys in T. 23 N., R. 26 E., Gila and Salt River Meridian, Arizona, is a true copy of the original field notes.~~

~~_____~~
(Date)

~~_____~~
(Acting Chief Cadastral Surveyor of Arizona)