

ORIGINAL

**UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT**

FIELD NOTES
OF THE
SURVEY
OF
THE EAST AND WEST BOUNDARIES,
AND
THE SUBDIVISIONAL LINES,
TOWNSHIP 24 NORTH, RANGE 26 EAST,
OF THE GILA AND SALT RIVER MERIDIAN,
IN THE STATE OF ARIZONA

EXECUTED BY

Jones Curtiss, Cadastral Surveyor

Under Special Instructions dated and approved May 1, 2002, and Supplemental Special Instructions dated and approved September 23, 2002, which provided for the surveys included under Group No. 886, and assignment instructions dated May 1, 2002.

Survey commenced September 26, 2002

Survey completed October 29, 2002

INDEX DIAGRAM

TOWNSHIP 24 NORTH RANGE 26 EAST
GILA & SALT RIVER MERIDIAN, ARIZONA

14	62 6	61 60 5	50 48 4	41 40 3	33 32 2	25 23 1 8
13	59 7	59 58 8	48 47 9	40 39 10	31 31 11	22 22 12 7
12	57 18	57 56 17	47 46 16	38 38 15	30 29 14	21 20 13 6
12	55 19	55 54 20	45 45 21	37 36 22	29 28 23	19 18 24 5
11	53 30	53 52 29	44 43 28	36 35 27	27 27 26	18 17 25 4
10	51 31	51 50 32	43 42 33	34 34 34	26 25 35	16 16 36 4

T. 24 N., R. 26 E., Gila and Salt River Meridian, Arizona

CHAINS

The following field notes describe the survey of the east and west boundaries, and the subdivisional lines, Township 24 North, Range 26 East, of Gila and Salt River Meridian, Arizona.

The history of surveys pertaining to this survey is as follows:

Frank Follman surveyed the north boundary, Township 23 North, Range 26 East in 1882 and the Sixth Standard Parallel North (south boundary), Townships 25 North, Ranges 25 and 26 East in 1883. Jones Curtiss dependently resurveyed a portion of the Sixth Standard Parallel North (south boundary), Township 25 North, Range 25 East, and the Sixth Standard Parallel North (south boundary), Township 25 North, Range 26 East in 2002, concurrently under this same group. Jones Curtiss and Leonard R. Sandoval dependently resurveyed the east, west and north boundaries, Township 23 North, Range 26 East in 2003, concurrently under this same group.

The survey was executed in accordance with the specifications as set forth in the Manual of Instructions for the Survey of the Public Lands of the United States, 1973, and the Special Instructions dated May 1, 2002, and the Supplemental Special Instructions dated and approved September 23, 2002 for Group No. 886, Arizona.

The true meridian direction and length of all lines were determined by real time kinematic global positioning system observations using Trimble Navigation Model 5700 receivers.

Geodetic control was derived from Global Positioning System (GPS) static observations post processed by National Geodetic Survey's Online Positioning User Service (OPUS), utilizing Continuously Operating Reference Stations (CORS) FERNO MESA, FLAGSTAFF AND PIE TOWM VLBA. The NAD83(CORS96)(EPOCH:2002) geographic position of the southeast corner of the township is as follows:

Latitude: 35°25'56.41" N. Longitude: 109°31'34.14" W.

The mean magnetic declination is 11 1/2° E.

**Survey of the East Boundary,
T. 24 N., R. 26 E., Gila and Salt River Meridian, Arizona**

CHAINS													
	<p>Beginning at the cor. of Tps. 23 and 24 N., Rs. 26 and 27 E., monumented with a stainless steel post, 2 1/2 ins. diam., with brass cap, set and mkd. as described in the field notes of the dependent resurvey of the east boundary, T. 23 N., R 26 E., executed concurrently under this same group.</p> <p>North, on the E. bdy. of sec. 36.</p> <p>Over rolling and broken land.</p>												
40.00	<p>Point for the 1/4 sec. cor. of sec. 36 only.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center;"> <table style="margin: auto;"> <tr><td>T 24 N</td><td></td></tr> <tr><td>R 26 E</td><td>R 27 E</td></tr> <tr><td>1/4</td><td> </td></tr> <tr><td>S 36</td><td> </td></tr> </table> <p>2002</p> </div> <p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p>	T 24 N		R 26 E	R 27 E	1/4		S 36					
T 24 N													
R 26 E	R 27 E												
1/4													
S 36													
80.00	<p>Point for the cor. of secs. 25 and 36 only.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center;"> <table style="margin: auto;"> <tr><td>T 24 N</td><td> </td><td>T 24 N</td></tr> <tr><td>S 25</td><td> </td><td>R 27 E</td></tr> <tr><td>S 36</td><td> </td><td>S 30</td></tr> <tr><td>R 26 E</td><td></td><td></td></tr> </table> <p>2002</p> </div> <p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p> <p>Land, rolling and broken. Soil, sandy and sandy clay. Timber, piñon and juniper; undergrowth, rabbit brush, cacti and native grasses.</p> <hr/> <p>North, on the E. bdy. of sec. 25.</p> <p>Over rolling and broken land.</p>	T 24 N		T 24 N	S 25		R 27 E	S 36		S 30	R 26 E		
T 24 N		T 24 N											
S 25		R 27 E											
S 36		S 30											
R 26 E													

**Survey of the East Boundary,
T. 24 N., R. 26 E., Gila and Salt River Meridian, Arizona**

CHAINS													
40.00	<p>Point for the 1/4 sec. cor. of sec. 25 only.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center;"> <table style="margin: auto;"> <tr><td>T 24 N</td><td></td></tr> <tr><td>R 26 E</td><td>R 27 E</td></tr> <tr><td>1/4</td><td> </td></tr> <tr><td>S 25</td><td> </td></tr> </table> <p>2002</p> </div> <p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p>	T 24 N		R 26 E	R 27 E	1/4		S 25					
T 24 N													
R 26 E	R 27 E												
1/4													
S 25													
54.30	<p>Apache County Road C424, a graded road, 20 ft. wide, bears NNE and SSW.</p>												
80.00	<p>Point for the cor. of secs. 24 and 25 only.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center;"> <table style="margin: auto;"> <tr><td>T 24 N</td><td> </td><td>T 24 N</td></tr> <tr><td>S 24</td><td> </td><td>R 27 E</td></tr> <tr><td>S 25</td><td> </td><td>S 19</td></tr> <tr><td>R 26 E</td><td></td><td></td></tr> </table> <p>2002</p> </div> <p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p> <p>Cor. is located 35 lks. N. of a wash, 5 ft. wide, drains NE.</p> <p>Land, rolling and broken. Soil, sandy and sandy clay. Timber, piñon and juniper; undergrowth, sagebrush, cacti and native grasses.</p> <hr/> <p>North, on the E. bdy. of sec. 24.</p> <p>Over rolling and broken land.</p>	T 24 N		T 24 N	S 24		R 27 E	S 25		S 19	R 26 E		
T 24 N		T 24 N											
S 24		R 27 E											
S 25		S 19											
R 26 E													
5.65	<p>W. right-of-way fence of U. S. Highway 191, barbed wire, 5 strands, parallels highway.</p>												
8.18	<p>U. S. Highway 191, asphalt pavement, 30 ft. wide, bears SE and NW.</p>												
10.88	<p>E. right-of-way fence of U. S. Highway 191, barbed wire, 5 strands, parallels highway.</p>												

Survey of the East Boundary,
T. 24 N., R. 26 E., Gila and Salt River Meridian, Arizona

CHAINS													
40.00	<p>Point for the 1/4 sec. cor. of sec. 24 only.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center;"> <table style="margin: auto;"> <tr><td>T 24 N</td><td></td></tr> <tr><td>R 26 E</td><td>R 27 E</td></tr> <tr><td>1/4</td><td> </td></tr> <tr><td>S 24</td><td> </td></tr> </table> <p>2002</p> </div> <p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p>	T 24 N		R 26 E	R 27 E	1/4		S 24					
T 24 N													
R 26 E	R 27 E												
1/4													
S 24													
80.00	<p>Point for the cor. of secs. 13 and 24 only.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center;"> <table style="margin: auto;"> <tr><td>T 24 N</td><td> </td><td>T 24 N</td></tr> <tr><td>S 13</td><td> </td><td>R 27 E</td></tr> <tr><td>S 24</td><td> </td><td>S 18</td></tr> <tr><td>R 26 E</td><td></td><td></td></tr> </table> <p>2002</p> </div> <p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p> <p>Land, rolling and broken. Soil, sandy and sandy clay. Timber, piñon and juniper; undergrowth, sagebrush, cacti and native grasses.</p> <hr/> <p>North, on the E. bdy. of sec. 13.</p> <p>Over rolling and broken land.</p>	T 24 N		T 24 N	S 13		R 27 E	S 24		S 18	R 26 E		
T 24 N		T 24 N											
S 13		R 27 E											
S 24		S 18											
R 26 E													
40.00	<p>Point for the 1/4 sec. cor. of sec. 13 only.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center;"> <table style="margin: auto;"> <tr><td>T 24 N</td><td></td></tr> <tr><td>R 26 E</td><td>R 27 E</td></tr> <tr><td>1/4</td><td> </td></tr> <tr><td>S 13</td><td> </td></tr> </table> <p>2002</p> </div>	T 24 N		R 26 E	R 27 E	1/4		S 13					
T 24 N													
R 26 E	R 27 E												
1/4													
S 13													

**Survey of the East Boundary,
T. 24 N., R. 26 E., Gila and Salt River Meridian, Arizona**

CHAINS									
	Deposit a magnet in a white plastic case at the base of the stainless steel post.								
77.38	Barbed wire fence, 5 strands, bears NE and SW.								
80.00	Point for the cor. of secs. 12 and 13 only.								
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.								
	<table style="margin-left: auto; margin-right: auto;"> <tr> <td style="border-right: 1px solid black; padding: 0 5px;">T 24 N</td> <td style="padding: 0 5px;">T 24 N</td> </tr> <tr> <td style="border-right: 1px solid black; padding: 0 5px;">S 12</td> <td style="padding: 0 5px;">R 27 E</td> </tr> <tr> <td style="border-right: 1px solid black; padding: 0 5px;">S 13</td> <td style="padding: 0 5px;">S 7</td> </tr> <tr> <td style="border-right: 1px solid black; padding: 0 5px;">R 26 E</td> <td></td> </tr> </table>	T 24 N	T 24 N	S 12	R 27 E	S 13	S 7	R 26 E	
T 24 N	T 24 N								
S 12	R 27 E								
S 13	S 7								
R 26 E									
	2002								
	Deposit a magnet in a white plastic case at the base of the stainless steel post.								
	Cor. is located 14 lks. W. of a barbed wire fence, bears N. and S.								
	Land, rolling.								
	Soil, sandy and sandy clay.								
	Timber, piñon and juniper; undergrowth, rabbit brush, cacti and native grasses.								
	North, on the E. bdy. of sec. 12.								
	Over rolling land.								
40.00	Point for the 1/4 sec. cor. of sec. 12 only.								
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.								
	<table style="margin-left: auto; margin-right: auto;"> <tr> <td style="padding: 0 10px;">T 24 N</td> <td></td> </tr> <tr> <td style="padding: 0 10px;">R 26 E</td> <td style="padding: 0 10px;">R 27 E</td> </tr> <tr> <td style="padding: 0 10px;">1/4</td> <td style="border-left: 1px solid black; padding-left: 5px;"> </td> </tr> <tr> <td style="padding: 0 10px;">S 12</td> <td style="border-left: 1px solid black; padding-left: 5px;"> </td> </tr> </table>	T 24 N		R 26 E	R 27 E	1/4		S 12	
T 24 N									
R 26 E	R 27 E								
1/4									
S 12									
	2002								
	from which								
	A stainless steel post, 28 ins. long, 2 1/2 ins. diam., set 24 ins. in the ground for a reference monument, bears S. 45°00' W., 105.00 ft. dist. with brass cap mkd. T24N R26E 1/4 S12 RM 105.0 FT. TO COR. 2002 and an arrow pointing to the corner. Deposit a magnet in a white plastic case at the base of the stainless steel post.								

**Survey of the East Boundary,
T. 24 N., R. 26 E., Gila and Salt River Meridian, Arizona**

CHAINS													
	<p>A stainless steel post, 28 ins. long, 2 1/2 ins. diam., set 24 ins. in the ground for a reference monument, bears N. 45°00' W., 73.00 ft. dist. with brass cap mkd. T24N R26E 1/4 S12 RM 73.0 FT. TO COR. 2002 and an arrow pointing to the corner. Deposit a magnet in a white plastic case at the base of the stainless steel post.</p> <p>Deposit a magnet in a white plastic case at the base of the stainless steel post at the 1/4 sec. cor.</p> <p>Set a steel fence post nearby.</p> <p>Cor. is located in an area enclosed, for a sewer lagoon, with a woven wire fence with 2 strands of barbed wire; 1.30 chs. N. of the southerly fence, bears E. and W. and 1.12 chs. S. of northerly fence, bears ENE and WSW.</p>												
57.10	Navajo Route 9353, a graded road, 20 ft. wide, bears ESE and WNW.												
80.00	<p>Point for the cor. of secs. 1 and 12 only.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center;"> <table border="1" style="margin-left: auto; margin-right: auto;"> <tr> <td style="padding: 2px;">T 24 N</td> <td style="padding: 2px;"> </td> <td style="padding: 2px;">T 24 N</td> </tr> <tr> <td style="padding: 2px;">S 1</td> <td style="padding: 2px;"> </td> <td style="padding: 2px;">R 27 E</td> </tr> <tr> <td style="padding: 2px;">S 12</td> <td style="padding: 2px;"> </td> <td style="padding: 2px;">S 6</td> </tr> <tr> <td style="padding: 2px;">R 26 E</td> <td style="padding: 2px;"> </td> <td></td> </tr> </table> <p>2002</p> </div> <p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p> <p>Land, rolling. Soil, sandy and sandy clay. Timber, piñon and juniper; undergrowth, sagebrush, rabbit brush cacti and native grasses.</p> <hr style="width: 50%; margin-left: 0;"/> <p>North, on the E. bdy. of sec. 1.</p> <p>Over rolling land.</p>	T 24 N		T 24 N	S 1		R 27 E	S 12		S 6	R 26 E		
T 24 N		T 24 N											
S 1		R 27 E											
S 12		S 6											
R 26 E													
5.80	Sand Spring Wash, 40 ft. wide, 4 ft. deep, drains SE.												
11.70	Navajo Route 28, a graded road, 25 ft. wide, bears ENE and WSW.												
40.00	<p>Point for the 1/4 sec. cor. of sec. 1 only.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p>												

**Survey of the East Boundary,
T. 24 N., R. 26 E., Gila and Salt River Meridian, Arizona**

CHAINS	
	T 24 N R 26 E R 27 E 1/4 S 1
	2002
	Deposit a magnet in a white plastic case at the base of the stainless steel post.
	Cor. is located 25 lks. N. of a trail road, bears NE and SW.
54.69	E. right-of-way fence of U. S. Highway 191, barbed wire, 5 strands, parallels highway.
66.01	U. S. Highway 191, asphalt pavement, 25 ft. wide, bears N. and S.
70.51	Point for the closing cor. of Tps. 24 N., Rs. 26 and 27 E., at intersection with Sixth Standard Parallel North, on the N. bdy. of the Tp.
	Set a P-K nail flush with the surface of the asphalt pavement.
	from which
	A stainless steel post, 28 ins. long, 2 1/2 ins. diam., set 24 ins. in the ground for a reference monument, bears S. 30°00' E., 209.00 ft. dist. with brass cap mkd. T24N R27E CC S6 RM 209.0 FT. TO COR. 2002 and an arrow pointing to the corner. Deposit a magnet in a white plastic case at the base of the stainless steel post.
	A stainless steel post, 28 ins. long, 2 1/2 ins. diam., set 24 ins. in the ground for a reference monument, bears S. 60°00' W., 109.00 ft. dist. with brass cap mkd. T24N R26E CC S1 RM 109.0 FT. TO COR. 2002 and an arrow pointing to the corner. Deposit a magnet in a white plastic case at the base of the stainless steel post.
	Cor. is located 11 lks. E. of the westerly edge of the asphalt pavement of U. S. Highway 191, 27 ft. wide, bears N. and S.
	From this cor. point, the stan. cor. of secs. 35 and 36, T. 25 N., R. 26 E., bears N. 89°56' E., 5.50 chs. dist., monumented with a stainless steel post, 2 1/2 ins. diam., with brass cap, set and mkd. as described in the field notes of the dependent resurvey of the Sixth Standard Parallel North (south boundary), T. 25 N., R. 26 E., executed concurrently under this same group.

**Survey of the East Boundary,
T. 24 N., R. 26 E., Gila and Salt River Meridian, Arizona**

CHAINS	<p>From this same cor. point, the stan. 1/4 sec. cor. of sec. 35, T. 25 N., R. 26 E., bears S. 89°56' W., 34.36 chs. dist., monumented with a stainless steel post, 2 1/2 ins. diam., with brass cap, set, mkd. and witnessed as described in the field notes of the dependent resurvey of the Sixth Standard Parallel North (south boundary), T. 25 N., R. 26 E., executed concurrently under this same group.</p> <p>Land, rolling. Soil, sandy and sandy clay. Timber, piñon and juniper; undergrowth, sagebrush, rabbit brush cacti and native grasses.</p> <hr/> <p align="center">Survey of the West Boundary, T. 24 N., R. 26 E., Gila and Salt River Meridian, Arizona</p> <hr/> <p>From the cor. of Tps. 23 and 24 N., Rs. 25 and 26 E., monumented with a stainless steel post, 2 1/2 ins. diam., with brass cap, set and mkd. as described in the field notes of the dependent resurvey of the west boundary, T. 23 N., R 26 E., executed concurrently under this same group.</p> <p>North, bet. secs. 31 and 36.</p> <p>Over rolling and broken land.</p> <p>40.00 Point for the 1/4 sec. cor. of secs. 31 and 36.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p align="center">T 24 N R 25 E R 26 E 1/4 S 36 S 31</p> <p align="center">2002</p> <p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p> <p>80.00 Point for the cor. of secs. 25, 30, 31 and 36.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p>
--------	---

**Survey of the West Boundary,
T. 24 N., R. 26 E., Gila and Salt River Meridian, Arizona**

CHAINS									
	<table style="margin: auto; border-collapse: collapse;"> <tr><td colspan="2" style="text-align: center;">T 24 N</td></tr> <tr><td style="text-align: center;">R 25 E</td><td style="text-align: center;">R 26 E</td></tr> <tr><td style="text-align: center;">S 25</td><td style="text-align: center;">S 30</td></tr> <tr style="border-top: 1px solid black;"><td style="text-align: center;">S 36</td><td style="text-align: center;">S 31</td></tr> </table>	T 24 N		R 25 E	R 26 E	S 25	S 30	S 36	S 31
T 24 N									
R 25 E	R 26 E								
S 25	S 30								
S 36	S 31								
	2002								
	Deposit a magnet in a white plastic case at the base of the stainless steel post.								
	Land, rolling and broken. Soil, sandy and sandy clay. Timber, piñon and juniper; undergrowth, greasewood, rabbit brush cacti and native grasses.								
	North, bet. secs. 25 and 30.								
	Over rolling and broken land.								
40.00	Point for the 1/4 sec. cor. of secs. 25 and 30. Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.								
	<table style="margin: auto; border-collapse: collapse;"> <tr><td colspan="2" style="text-align: center;">T 24 N</td></tr> <tr><td style="text-align: center;">R 25 E</td><td style="text-align: center;">R 26 E</td></tr> <tr><td colspan="2" style="text-align: center;">1/4</td></tr> <tr><td style="text-align: center;">S 25</td><td style="text-align: center;">S 30</td></tr> </table>	T 24 N		R 25 E	R 26 E	1/4		S 25	S 30
T 24 N									
R 25 E	R 26 E								
1/4									
S 25	S 30								
	2002								
	Deposit a magnet in a white plastic case at the base of the stainless steel post.								
80.00	Point for the cor. of secs. 19, 24, 25 and 30. Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.								
	<table style="margin: auto; border-collapse: collapse;"> <tr><td colspan="2" style="text-align: center;">T 24 N</td></tr> <tr><td style="text-align: center;">R 25 E</td><td style="text-align: center;">R 26 E</td></tr> <tr><td style="text-align: center;">S 24</td><td style="text-align: center;">S 19</td></tr> <tr style="border-top: 1px solid black;"><td style="text-align: center;">S 25</td><td style="text-align: center;">S 30</td></tr> </table>	T 24 N		R 25 E	R 26 E	S 24	S 19	S 25	S 30
T 24 N									
R 25 E	R 26 E								
S 24	S 19								
S 25	S 30								
	2002								
	Deposit a magnet in a white plastic case at the base of the stainless steel post.								

**Survey of the West Boundary,
T. 24 N., R. 26 E., Gila and Salt River Meridian, Arizona**

CHAINS	
	<p>Land, rolling and broken. Soil, sandy and sandy clay. Timber, piñon and juniper; undergrowth, sagebrush, rabbit brush cacti and native grasses.</p> <hr/> <p>North, bet. secs. 19 and 24.</p> <p>Over rolling land.</p>
40.00	<p>Point for the 1/4 sec. cor. of secs. 19 and 24.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;"> T 24 N R 25 E R 26 E 1/4 S 24 S 19 2002 </p> <p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p>
80.00	<p>Point for the cor. of secs. 13, 18, 19 and 24.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;"> T 24 N R 25 E R 26 E S 13 S 18 <hr style="width: 50%; margin: 0 auto;"/> S 24 S 19 2002 </p> <p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p>
	<p>Land, rolling. Soil, sandy and sandy clay. Timber, piñon and juniper; undergrowth, sagebrush, rabbit brush cacti and native grasses.</p> <hr/> <p>North, bet. secs. 13 and 18.</p> <p>Over rolling land.</p>
40.00	<p>Point for the 1/4 sec. cor. of secs. 13 and 18.</p>

**Survey of the West Boundary,
T. 24 N., R. 26 E., Gila and Salt River Meridian, Arizona**

CHAINS	
	<p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T 24 N R 25 E R 26 E 1/4 S 13 S 18</p> <p style="text-align: center;">2002</p> <p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p>
80.00	<p>Point for the cor. of secs. 7, 12, 13 and 18.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T 24 N R 25 E R 26 E S 12 S 7 <hr style="width: 50%; margin: auto;"/>S 13 S 18</p> <p style="text-align: center;">2002</p> <p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p> <p>Land, rolling. Soil, sandy and sandy clay. Timber, piñon and juniper; undergrowth, sagebrush, rabbit brush cacti and native grasses.</p> <hr style="width: 80%; margin: 10px auto;"/> <p>North, bet. secs. 7 and 12.</p> <p>Over rolling land.</p>
7.00	<p>Navajo Route 9606, a graded road, 20 ft. wide, bears ENE and WSW.</p>
38.73	<p>Barbed wire fence, 5 strands, bears ENE and WSW.</p>
40.00	<p>Point for the 1/4 sec. cor. of secs. 7 and 12.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p>

**Survey of the West Boundary,
T. 24 N., R. 26 E., Gila and Salt River Meridian, Arizona**

CHAINS	
	T 24 N R 25 E R 26 E 1/4 S 12 S 7 2002
	Deposit a magnet in a white plastic case at the base of the stainless steel post.
80.00	Point for the cor. of secs. 1, 6, 7 and 12. Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.
	T 24 N R 25 E R 26 E S 1 S 6 ----- S 12 S 7 2002
	Deposit a magnet in a white plastic case at the base of the stainless steel post.
	Land, rolling. Soil, sandy and sandy clay. Timber, piñon and juniper; undergrowth, sagebrush, rabbit brush cacti and native grasses.
	<hr/> North, bet. secs. 1 and 6. Over rolling land.
5.10	Underground gas pipeline, bears ENE and WSW.
6.00	Underground gas pipeline, bears ENE and WSW.
8.00	Navajo Route 28, a graded road, 25 ft. wide, bears SE and NW.
40.00	Point for the 1/4 sec. cor. of secs. 1 and 6. Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.
	T 24 N R 25 E R 26 E 1/4 S 1 S 6 2002

**Survey of the West Boundary,
T. 24 N., R. 26 E., Gila and Salt River Meridian, Arizona**

CHAINS	<p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p>																												
71.08	<p>Point for the closing cor. of Tps. 24 N., Rs. 25 and 26 E., at the intersection with Sixth Standard Parallel North, on the N. bdy. of the Tp.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center; margin: 10px 0;"> <table style="margin: auto; border-collapse: collapse;"> <tr> <td colspan="2">T 25 N</td> <td colspan="2">R 25 E</td> </tr> <tr> <td colspan="4">S 35</td> </tr> <tr> <td colspan="2" style="border-top: 1px solid black;">S 1</td> <td colspan="2" style="border-top: 1px solid black;">S 6</td> </tr> <tr> <td style="border-right: 1px solid black;">R 25 E</td> <td style="border-right: 1px solid black;"></td> <td style="border-right: 1px solid black;">R 26 E</td> <td></td> </tr> <tr> <td colspan="4">T 24 N</td> </tr> <tr> <td colspan="4">CC</td> </tr> <tr> <td colspan="4">2002</td> </tr> </table> </div> <p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p> <p>From this cor. point, the stan. cor. of secs. 35 and 36, T. 25 N., R. 25 E., bears S. 89°51' E., 2.20 chs. dist., monumented with a stainless steel post, 2 1/2 ins. diam., with brass cap, set and mkd. as described in the field notes of the dependent resurvey of a portion of the Sixth Standard Parallel North (south boundary), T. 25 N., R. 25 E., executed concurrently under this same group.</p> <p>From this same cor. point, the stan. 1/4 sec. cor. of sec. 35, T. 25 N., R. 25 E., bears N. 89°51' W., 37.89 chs. dist., monumented with a stainless steel post, 2 1/2 ins. diam., with brass cap, set, mkd. and witnessed as described in the field notes of the dependent resurvey of a portion of the Sixth Standard Parallel North (south boundary), T. 25 N., R. 25 E., executed concurrently under this same group.</p> <p>Closing cor. is located 85 lks. N. of a wash, 15 ft. wide, 10 ft. deep, drains W.</p> <p>Land, rolling. Soil, sandy and sandy clay. Timber, piñon and juniper; undergrowth, sagebrush, rabbit brush cacti and native grasses.</p> <hr style="width: 60%; margin-left: 0;"/>	T 25 N		R 25 E		S 35				S 1		S 6		R 25 E		R 26 E		T 24 N				CC				2002			
T 25 N		R 25 E																											
S 35																													
S 1		S 6																											
R 25 E		R 26 E																											
T 24 N																													
CC																													
2002																													

**Survey of the Subdivisional Lines,
T. 24 N., R. 26 E., Gila and Salt River Meridian, Arizona**

CHAINS	<p>From the cor. of secs. 1, 2, 35 and 36, on the S. bdy. of the Tp., monumented with a stainless steel post, 2 1/2 ins. diam., with brass cap, set and mkd., as described in the field notes of the dependent resurvey of the north boundary, T. 23 N., R. 26 E., executed concurrently under this same group.</p> <p>N. 0°01' W., bet. secs. 35 and 36.</p> <p>Over rolling land.</p>						
40.00	<p>Point for the 1/4 sec. cor. of secs. 35 and 36.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center; margin: 10px 0;"> <table style="margin: auto; border-collapse: collapse;"> <tr><td>T 24 N</td><td>R 26 E</td></tr> <tr><td></td><td>1/4</td></tr> <tr><td>S 35</td><td> S 36</td></tr> </table> <p>2002</p> </div> <p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p>	T 24 N	R 26 E		1/4	S 35	S 36
T 24 N	R 26 E						
	1/4						
S 35	S 36						
76.50	<p>Apache County Road C424, a graded road, 25 ft. wide, bears ENE and WSW.</p>						
80.00	<p>Point for the cor. of secs. 25, 26, 35 and 36.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center; margin: 10px 0;"> <table style="margin: auto; border-collapse: collapse;"> <tr><td>T 24 N</td><td>R 26 E</td></tr> <tr><td>S 26</td><td> S 25</td></tr> <tr><td>S 35</td><td> S 36</td></tr> </table> <p>2002</p> </div> <p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p> <p>Cor. is located 65 lks. S. of a trail road, bears ESE and WNW.</p> <p>Land, rolling. Soil, sandy and sandy clay. Timber, piñon and juniper; undergrowth, sagebrush, rabbit brush cacti and native grasses.</p> <hr style="width: 50%; margin: 10px auto;"/> <p>From the cor. of secs. 25 and 36 only, on the E. bdy. of the Tp., hereinbefore described.</p> <p>West, bet. secs. 25 and 36.</p>	T 24 N	R 26 E	S 26	S 25	S 35	S 36
T 24 N	R 26 E						
S 26	S 25						
S 35	S 36						

**Survey of the Subdivisional Lines,
T. 24 N., R. 26 E., Gila and Salt River Meridian, Arizona**

CHAINS	
	Over rolling land.
39.93	<p>Point for the 1/4 sec. cor. of secs. 25 and 36.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center; margin: 10px 0;"> T 24 N R 26 E S 25 1/4 ——— S 36 </div> <p style="text-align: center; margin: 10px 0;">2002</p> <p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p>
74.20	<p>Apache County Road C424, a graded road, 25 ft. wide, bears ENE and WSW.</p>
79.86	<p>The cor. of secs. 25, 26, 35 and 36.</p> <p>Land, rolling. Soil, sandy and sandy clay. Timber, piñon and juniper; undergrowth, sagebrush, rabbit brush cacti and native grasses.</p> <hr style="border: 0.5px solid black; margin: 10px 0;"/> <p>N. 0°01' W., bet. secs. 25 and 26.</p> <p>Over rolling land.</p>
40.00	<p>Point for the 1/4 sec. cor. of secs. 25 and 26.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center; margin: 10px 0;"> T 24 N R 26 E 1/4 S 26 S 25 </div> <p style="text-align: center; margin: 10px 0;">2002</p> <p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p>
80.00	<p>Point for the cor. of secs. 23, 24, 25 and 26.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p>

**Survey of the Subdivisional Lines,
T. 24 N., R. 26 E., Gila and Salt River Meridian, Arizona**

CHAINS	<table style="margin: auto; border-collapse: collapse;"> <tr> <td style="padding: 0 10px;">T 24 N</td> <td style="padding: 0 10px;">R 26 E</td> </tr> <tr> <td style="padding: 0 10px; border-right: 1px solid black;">S 23</td> <td style="padding: 0 10px;">S 24</td> </tr> <tr> <td style="padding: 0 10px; border-right: 1px solid black;">S 26</td> <td style="padding: 0 10px;">S 25</td> </tr> </table>	T 24 N	R 26 E	S 23	S 24	S 26	S 25
T 24 N	R 26 E						
S 23	S 24						
S 26	S 25						
	2002						
	Deposit a magnet in a white plastic case at the base of the stainless steel post. Land, rolling. Soil, sandy and sandy clay. Timber, piñon and juniper; undergrowth, sagebrush, rabbit brush cacti and native grasses.						
	<hr/> From the cor. of secs. 24 and 25 only, on the E. bdy. of the Tp., hereinbefore described. West, bet. secs. 24 and 25. Over rolling and broken land.						
37.38	Power line, bears NNE and SSW.						
39.94	Point for the 1/4 sec. cor. of secs. 24 and 25. Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.						
	<table style="margin: auto; border-collapse: collapse;"> <tr> <td style="padding: 0 10px;">T 24 N</td> <td style="padding: 0 10px;">R 26 E</td> </tr> <tr> <td></td> <td style="padding: 0 10px;">S 24</td> </tr> <tr> <td style="padding: 0 10px;">1/4</td> <td style="padding: 0 10px; border-top: 1px solid black;">S 25</td> </tr> </table>	T 24 N	R 26 E		S 24	1/4	S 25
T 24 N	R 26 E						
	S 24						
1/4	S 25						
	2002						
	Deposit a magnet in a white plastic case at the base of the stainless steel post.						
79.88	The cor. of secs. 23, 24, 25 and 26. Land, rolling and broken. Soil, sandy and sandy clay. Timber, piñon and juniper; undergrowth, sagebrush, rabbit brush and native grasses.						
	<hr/> N. 0°01' W., bet. secs. 23 and 24. Over rolling and broken land.						
40.00	Point for the 1/4 sec. cor. of secs. 23 and 24.						

**Survey of the Subdivisional Lines,
T. 24 N., R. 26 E., Gila and Salt River Meridian, Arizona**

CHAINS	
	<p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T 24 N R 26 E 1/4 S 23 S 24</p> <p style="text-align: center;">2002</p> <p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p>
41.10	Wash, 20 ft. wide, 10 ft. deep, drains SE.
80.00	Point for the cor. of secs. 13, 14, 23 and 24.
	<p>Set a magnet in a white plastic case, 24 ins. below the surface of the ground.</p> <p>from which</p> <p style="padding-left: 40px;">A stainless steel post, 28 ins. long, 2 1/2 ins. diam., set 24 ins. in the ground for a reference monument, bears S. 45°00' E., 30.00 ft. dist. with brass cap mkd. T24N R26E S24 RM 30.0 FT. TO COR. 2002 and an arrow pointing to the corner. Deposit a magnet in a white plastic case at the base of the stainless steel post.</p> <p style="padding-left: 40px;">A stainless steel post, 28 ins. long, 2 1/2 ins. diam., set 24 ins. in the ground for a reference monument, bears N. 45°00' W., 30.00 ft. dist. with brass cap mkd. T24N R26E S14 RM 30.0 FT. TO COR. 2002 and an arrow pointing to the corner. Deposit a magnet in a white plastic case at the base of the stainless steel post.</p> <p>Cor. is located on the E. bank of a wash, 10 lks. E. of the center, 10 ft. wide, 4 ft. deep, drains SSW.</p> <p>Land, rolling. Soil, sandy and sandy clay. Timber, piñon and juniper; undergrowth, sagebrush, rabbit brush cacti and native grasses.</p> <hr/> <p>From the cor. of secs. 13 and 24 only, on the E. bdy. of the Tp., hereinbefore described.</p> <p>West, bet. secs. 13 and 24.</p> <p>Over rolling and broken land.</p>
14.17	E. right-of-way fence of U. S. Highway 191, barbed wire, 4 strands, parallels highway.

**Survey of the Subdivisional Lines,
T. 24 N., R. 26 E., Gila and Salt River Meridian, Arizona**

CHAINS	
15.71	U. S. Highway 191, asphalt pavement, 30 ft. wide, bears N. and S.
17.22	W. right-of-way fence of U. S. Highway 191, barbed wire, 4 strands, parallels highway.
39.95	Point for the 1/4 sec. cor. of secs. 13 and 24. Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd. <div style="text-align: center;"> T 24 N R 26 E S 13 1/4 ——— S 24 2002 </div>
79.90	Deposit a magnet in a white plastic case at the base of the stainless steel post. The cor. of secs. 13, 14, 23 and 24. Land, rolling and broken. Soil, sandy and sandy clay. Timber, piñon and juniper; undergrowth, sagebrush, rabbit brush cacti and native grasses. <hr/>
40.00	N. 0°01' W., bet. secs. 13 and 14. Over rolling and broken land. Point for the 1/4 sec. cor. of secs. 13 and 14. Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd. <div style="text-align: center;"> T 24 N R 26 E 1/4 S 14 S 13 2002 </div>
80.00	Deposit a magnet in a white plastic case at the base of the stainless steel post. Point for the cor. of secs. 11, 12, 13 and 14. Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.

**Survey of the Subdivisional Lines,
T. 24 N., R. 26 E., Gila and Salt River Meridian, Arizona**

CHAINS									
	<table border="1"> <tr> <td>T 24 N</td> <td>R 26 E</td> </tr> <tr> <td>S 11</td> <td>S 12</td> </tr> <tr> <td>S 14</td> <td>S 13</td> </tr> </table>	T 24 N	R 26 E	S 11	S 12	S 14	S 13		
T 24 N	R 26 E								
S 11	S 12								
S 14	S 13								
	2002								
	<p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p> <p>Land, rolling and broken. Soil, sandy and sandy clay. Timber, piñon and juniper; undergrowth, sagebrush, rabbit brush cacti and native grasses.</p> <hr/> <p>From the cor. of secs. 12 and 13 only, on the E. bdy. of the Tp., hereinbefore described.</p> <p>West, bet. secs. 12 and 13.</p> <p>Over rolling land.</p>								
10.50	E. right-of-way fence of U. S. Highway 191, barbed wire, 4 strands, parallels highway.								
12.04	U. S. Highway 191, asphalt pavement, 30 ft. wide, bears N. and S.								
13.54	W. right-of-way fence of U. S. Highway 191, barbed wire, 4 strands, parallels highway.								
28.10	Apache County Road C421, a graded road, 20 ft. wide, bears SE and NW.								
39.96	Point for the 1/4 sec. cor. of secs. 12 and 13.								
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.								
	<table border="1"> <tr> <td>T 24 N</td> <td>R 26 E</td> </tr> <tr> <td></td> <td>S 12</td> </tr> <tr> <td>1/4</td> <td>—</td> </tr> <tr> <td></td> <td>S 13</td> </tr> </table>	T 24 N	R 26 E		S 12	1/4	—		S 13
T 24 N	R 26 E								
	S 12								
1/4	—								
	S 13								
	2002								
	<p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p>								
79.92	The cor. of secs. 11, 12, 13 and 14.								

**Survey of the Subdivisional Lines,
T. 24 N., R. 26 E., Gila and Salt River Meridian, Arizona**

CHAINS	
	<p>Land, rolling. Soil, sandy and sandy clay. Timber, piñon and juniper; undergrowth, sagebrush, rabbit brush cacti and native grasses.</p> <hr/> <p>N. 0°01' W., bet. secs. 11 and 12.</p> <p>Over rolling land.</p>
20.70	Apache County Road C421, a graded road, 20 ft. wide, bears ESE and WNW.
40.00	<p>Point for the 1/4 sec. cor. of secs. 11 and 12.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T 24 N R 26 E 1/4 S 11 S 12 2002</p> <p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p>
62.50	Navajo Route 28, a graded road, 20 ft. wide, bears E. and W.
80.00	<p>Point for the cor. of secs. 1, 2, 11 and 12.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T 24 N R 26 E S 2 S 1 <hr/>S 11 S 12 2002</p> <p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p> <p>Land, rolling. Soil, sandy and sandy clay. Timber, piñon and juniper; undergrowth, sagebrush, rabbit brush cacti and native grasses.</p> <hr/> <p>From the cor. of secs. 1 and 12 only, on the E. bdy. of the Tp., hereinbefore described.</p> <p>West, bet. secs. 1 and 12.</p>

**Survey of the Subdivisional Lines,
T. 24 N., R. 26 E., Gila and Salt River Meridian, Arizona**

CHAINS	
	Over rolling land.
6.64	E. right-of-way fence of U. S. Highway 191, barbed wire, 4 strands, parallels highway.
8.16	U. S. Highway 191, asphalt pavement, 30 ft. wide, bears N. and S.
9.65	W. right-of-way fence of U. S. Highway 191, barbed wire, 5 strands, parallels highway.
39.35	Trail road, bears SE and NW.
39.96	Point for the 1/4 sec. cor. of secs. 1 and 12. Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd. <div style="text-align: center;"> T 24 N R 26 E S 1 1/4 ——— S 12 2002 </div> Deposit a magnet in a white plastic case at the base of the stainless steel post. Cor. is located 15 lks. E. of a trail road, bears N. and S.
79.92	The cor. of secs. 1, 2, 11 and 12. Land, rolling. Soil, sandy and sandy clay. Timber, piñon and juniper; undergrowth, sagebrush, rabbit brush cacti and native grasses. <hr/> N. 0°01' W., bet. secs. 1 and 2. Over rolling land.
40.00	Point for the 1/4 sec. cor. of secs. 1 and 2. Set a magnet in a white plastic case, 24 ins. below the surface of the ground.

**Survey of the Subdivisional Lines,
T. 24 N., R. 26 E., Gila and Salt River Meridian, Arizona**

CHAINS

from which

A stainless steel post, 28 ins. long, 2 1/2 ins. diam., set 24 ins. in the ground for a reference monument, bears N. 20°00' E., 40.00 ft. dist. with brass cap mkd. T24N R26E 1/4 S1 RM 40.0 FT. TO COR. 2002 and an arrow pointing to the corner. Deposit a magnet in a white plastic case at the base of the stainless steel post.

A stainless steel post, 28 ins. long, 2 1/2 ins. diam., set 24 ins. in the ground for a reference monument, bears S. 20°00' W., 50.00 ft. dist. with brass cap mkd. T24N R26E 1/4 S2 RM 50.0 FT. TO COR. 2002 and an arrow pointing to the corner. Deposit a magnet in a white plastic case at the base of the stainless steel post.

Cor. is located in a wash, 20 ft. wide, 4 ft. deep, drains NW.

70.38

Point for the closing cor. of secs. 1 and 2, at the intersection with the Sixth Standard Parallel North, on the N. bdy. of the Tp.

Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.

T 25 N	R 26 E
S 34	

S 2	S 1
T 24 N	R 26 E
CC	

2002

Deposit a magnet in a white plastic case at the base of the stainless steel post.

From this cor. point, the stan. cor. of secs. 34 and 35, T. 25 N., R. 26 E., bears N. 89°53' E., 5.61 chs. dist., monumented with a stainless steel post, 2 1/2 ins. diam., with brass cap, set and mkd. as described in the field notes of the dependent resurvey of the Sixth Standard Parallel North (south boundary), T. 25 N., R. 26 E., executed concurrently under this same group.

From this same cor. point, the stan. 1/4 sec. cor. of sec. 34, T. 25 N., R. 26 E., bears S. 89°53' W., 34.35 chs. dist., monumented with a stainless steel post, 2 1/2 ins. diam., with brass cap, set, mkd. and witnessed as described in the field notes of the dependent resurvey of the Sixth Standard Parallel North (south boundary), T. 25 N., R. 26 E., executed concurrently under this same group.

**Survey of the Subdivisional Lines,
T. 24 N., R. 26 E., Gila and Salt River Meridian, Arizona**

CHAINS	
	<p>Land, rolling. Soil, sandy and sandy clay. Timber, piñon and juniper; undergrowth, sagebrush, rabbit brush cacti and native grasses.</p> <hr/> <p>Point for the 1/4 sec. cor. of sec. 1 only, T. 24 N., R. 26 E., at midpoint on the N. bdy. of sec. 1.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T 25 N R 26 E ----- 1/4 S 1 T 24 N R 26 E</p> <p style="text-align: center;">2002</p> <p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p> <p>From this cor. point, the stan. 1/4 sec. cor. sec. 35, T. 25 N., R. 26 E., bears N. 89°53' E., 5.605 chs. dist., hereinbefore described.</p> <p>From this same cor. point, the stan. cor. of secs. 34 and 35, T. 25 N., R. 26 E., bears S. 89°53' W., 34.355 chs. dist.</p> <hr/> <p>From the cor. of secs. 2, 3, 34 and 35, on the S. bdy. of the Tp., monumented with a stainless steel post, 2 1/2 ins. diam., with brass cap, set and mkd., as described in the field notes of the dependent resurvey of the north boundary, T. 23 N., R. 26 E., executed concurrently under this same group.</p> <p>N. 0°01' W., bet. secs. 34 and 35.</p> <p>Over rolling and broken land.</p>
16.10	Apache County Road C281, a graded road, 16 ft. wide, bears NE and SW.
26.70	Apache County Road C424, a graded road, 20 ft. wide, bears NE and SW.
40.00	<p>Point for the 1/4 sec. cor. of secs. 34 and 35.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p>

**Survey of the Subdivisional Lines,
T. 24 N., R. 26 E., Gila and Salt River Meridian, Arizona**

CHAINS	
	T 24 N R 26 E 1/4 S 34 S 35 2002 Deposit a magnet in a white plastic case at the base of the stainless steel post.
80.00	Point for the cor. of secs. 26, 27, 34 and 35. Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.
	T 24 N R 26 E S 27 S 26 S 34 S 35 2002 Deposit a magnet in a white plastic case at the base of the stainless steel post.
	Land, rolling and broken. Soil, sandy and sandy clay. Timber, piñon and juniper; undergrowth, sagebrush, rabbit brush cacti and native grasses.
	<hr/> From the cor. of secs. 25, 26, 35 and 36. West, bet. secs. 26 and 35. Over rolling and broken land.
39.92	Point for the 1/4 sec. cor. of secs. 26 and 35. Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.
	T 24 N R 26 E S 26 1/4 ——— S 35 2002 Deposit a magnet in a white plastic case at the base of the stainless steel post.
79.84	The cor. of secs. 26, 27, 34 and 35.

**Survey of the Subdivisional Lines,
T. 24 N., R. 26 E., Gila and Salt River Meridian, Arizona**

CHAINS	
	<p>Land, rolling and broken. Soil, sandy and sandy clay. Timber, piñon and juniper; undergrowth, sagebrush, rabbit brush cacti and native grasses.</p> <hr/> <p>N. 0°01' W., bet. secs. 26 and 27.</p> <p>Over rolling and broken land.</p>
40.00	<p>Point for the 1/4 sec. cor. of secs. 26 and 27.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T 24 N R 26 E 1/4 S 27 S 26</p> <p style="text-align: center;">2002</p> <p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p>
80.00	<p>Point for the cor. of secs. 22, 23, 26 and 27.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T 24 N R 26 E S 22 S 23 S 27 S 26</p> <p style="text-align: center;">2002</p> <p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p> <p>Land, rolling and broken. Soil, sandy and sandy clay. Timber, piñon and juniper; undergrowth, sagebrush, rabbit brush cacti and native grasses.</p> <hr/> <p>From the cor. of secs. 23, 24, 25 and 26.</p> <p>West, bet. secs. 23 and 26.</p> <p>Over rolling and broken land.</p>
39.91	<p>Point for the 1/4 sec. cor. of secs. 23 and 26.</p>

**Survey of the Subdivisional Lines,
T. 24 N., R. 26 E., Gila and Salt River Meridian, Arizona**

CHAINS	
	<p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T 24 N R 26 E S 23 1/4 ——— S 26</p> <p style="text-align: center;">2002</p> <p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p>
79.82	<p>The cor. of secs. 22, 23, 26 and 27.</p> <p>Land, rolling and broken. Soil, sandy and sandy clay. Timber, piñon and juniper; undergrowth, sagebrush, rabbit brush cacti and native grasses.</p> <hr/> <p>N. 0°01' W., bet. secs. 22 and 23.</p> <p>Over rolling and broken land.</p>
40.00	<p>Point for the 1/4 sec. cor. of secs. 22 and 23.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T 24 N R 26 E 1/4 S 22 S 23</p> <p style="text-align: center;">2002</p> <p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p>
41.20	<p>Trail road, bears NE and SW.</p>
80.00	<p>Point for the cor. of secs. 14, 15, 22 and 23.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T 24 N R 26 E S 15 S 14 S 22 S 23</p> <p style="text-align: center;">2002</p>

**Survey of the Subdivisional Lines,
T. 24 N., R. 26 E., Gila and Salt River Meridian, Arizona**

CHAINS	
	<p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p> <p>Land, rolling and broken. Soil, sandy and sandy clay. Timber, piñon and juniper; undergrowth, sagebrush, rabbit brush cacti and native grasses.</p> <hr/> <p>From the cor. of secs. 13, 14, 23 and 24.</p> <p>West, bet. secs. 14 and 23.</p> <p>Over rolling and broken land.</p>
39.90	<p>Point for the 1/4 sec. cor. of secs. 14 and 23.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T 24 N R 26 E S 14 1/4 ——— S 23</p> <p style="text-align: center;">2002</p>
79.80	<p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p> <p>The cor. of secs. 14, 15, 22 and 23.</p> <p>Land, rolling and broken. Soil, sandy and sandy clay. Timber, piñon and juniper; undergrowth, sagebrush, rabbit brush cacti and native grasses.</p> <hr/> <p>N. 0°01' W., bet. secs. 14 and 15.</p> <p>Over rolling land.</p>
40.00	<p>Point for the 1/4 sec. cor. of secs. 14 and 15.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T 24 N R 26 E 1/4 S 15 S 14</p> <p style="text-align: center;">2002</p>

**Survey of the Subdivisional Lines,
T. 24 N., R. 26 E., Gila and Salt River Meridian, Arizona**

CHAINS									
	Deposit a magnet in a white plastic case at the base of the stainless steel post.								
80.00	Point for the cor. of secs. 10, 11, 14 and 15. Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd. <div style="text-align: center;"> <table style="margin: auto;"> <tr><td>T 24 N</td><td>R 26 E</td></tr> <tr><td>S 10</td><td>S 11</td></tr> <tr><td>S 15</td><td>S 14</td></tr> </table> <p>2002</p> </div>	T 24 N	R 26 E	S 10	S 11	S 15	S 14		
T 24 N	R 26 E								
S 10	S 11								
S 15	S 14								
	Deposit a magnet in a white plastic case at the base of the stainless steel post. Cor. is located 60 lks. S. of a trail road, bears E. and W. Land, rolling. Soil, sandy and sandy clay. Timber, piñon and juniper; undergrowth, sagebrush, rabbit brush and native grasses.								
	From the cor. of secs. 11, 12, 13 and 14. West, bet. secs. 11 and 14. Over rolling land.								
39.90	Point for the 1/4 sec. cor. of secs. 11 and 14. Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd. <div style="text-align: center;"> <table style="margin: auto;"> <tr><td>T 24 N</td><td>R 26 E</td></tr> <tr><td>S 11</td><td></td></tr> <tr><td>1/4</td><td>—</td></tr> <tr><td>S 14</td><td></td></tr> </table> <p>2002</p> </div>	T 24 N	R 26 E	S 11		1/4	—	S 14	
T 24 N	R 26 E								
S 11									
1/4	—								
S 14									
79.80	Deposit a magnet in a white plastic case at the base of the stainless steel post. The cor. of secs. 10, 11, 14 and 15.								

**Survey of the Subdivisional Lines,
T. 24 N., R. 26 E., Gila and Salt River Meridian, Arizona**

CHAINS	
	<p>Land, rolling. Soil, sandy and sandy clay. Timber, piñon and juniper; undergrowth, sagebrush, rabbit brush, cacti and native grasses.</p> <hr/> <p>N. 0°01' W., bet. secs. 10 and 11.</p> <p>Over rolling land.</p>
40.00	<p>Point for the 1/4 sec. cor. of secs. 10 and 11.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T 24 N R 26 E 1/4 S 10 S 11 2002</p> <p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p>
50.80	<p>Navajo Route 28, a graded road, 25 ft. wide, bears E. and W.</p>
80.00	<p>Point for the cor. of secs. 2, 3, 10 and 11.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T 24 N R 26 E S 3 S 2 ----- S 10 S 11 2002</p> <p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p>
	<p>Land, rolling. Soil, sandy and sandy clay. Timber, piñon and juniper; undergrowth, sagebrush, rabbit brush and native grasses.</p> <hr/> <p>From the cor. of secs. 1, 2, 11 and 12.</p> <p>West, bet. secs. 2 and 11.</p> <p>Over rolling land.</p>
39.89	<p>Point for the 1/4 sec. cor. of secs. 2 and 11.</p>

**Survey of the Subdivisional Lines,
T. 24 N., R. 26 E., Gila and Salt River Meridian, Arizona**

CHAINS	
	<p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T 24 N R 26 E S 2 1/4 ——— S 11</p> <p style="text-align: center;">2002</p>
79.78	<p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p> <p>The cor. of secs. 2, 3, 10 and 11.</p> <p>Land, rolling. Soil, sandy and sandy clay. Timber, piñon and juniper; undergrowth, sagebrush, rabbit brush and native grasses.</p> <hr/> <p>N. 0°01' W., bet. secs. 2 and 3.</p> <p>Over rolling land.</p>
40.00	<p>Point for the 1/4 sec. cor. of secs. 2 and 3.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T 24 N R 26 E 1/4 S 3 S 2</p> <p style="text-align: center;">2002</p>
70.56	<p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p> <p>Point for the closing cor. of secs. 2 and 3, at the intersection with the Sixth Standard Parallel North, on the N. bdy. of the Tp.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T 25 N R 26 E S 33 ————— S 3 S 2 T 24 N R 26 E CC</p> <p style="text-align: center;">2002</p>

**Survey of the Subdivisional Lines,
T. 24 N., R. 26 E., Gila and Salt River Meridian, Arizona**

CHAINS

Deposit a magnet in a white plastic case at the base of the stainless steel post.

From this cor. point, the stan. cor. of secs. 33 and 34, T. 25 N., R. 26 E., bears S. 89°58' E., 5.04 chs. dist., monumented with a stainless steel post, 2 1/2 ins. diam., with brass cap, set, mkd. and witnessed as described in the field notes of the dependent resurvey of the Sixth Standard Parallel North (south boundary), T. 25 N., R. 26 E., executed concurrently under this same group.

From this same cor. point, the stan. 1/4 sec. cor. of sec. 33, T. 25 N., R. 26 E., bears N. 89°58' W., 34.78 chs. dist., monumented with a stainless steel post, 2 1/2 ins. diam., with brass cap, set and mkd. as described in the field notes of the dependent resurvey of the Sixth Standard Parallel North (south boundary), T. 25 N., R. 26 E., executed concurrently under this same group.

Cor. is located 1.10 chs. E. of a trail road, bears SSE and NNW.

Land, rolling.

Soil, sandy and sandy clay.

Timber, piñon and juniper; undergrowth, sagebrush, rabbit brush and native grasses.

Point for the 1/4 sec. cor. of sec. 2 only, T. 24 N., R. 26 E., at midpoint on the N. bdy. of sec. 2.

Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.

T 25 N R 26 E

1/4 S 2

T 24 N R 26 E

2002

Deposit a magnet in a white plastic case at the base of the stainless steel post.

From this cor. point, the stan. 1/4 sec. cor. of sec. 34, T. 25 N., R. 26 E., bears S. 89°40' E., 5.535 chs. dist.

**Survey of the Subdivisional Lines,
T. 24 N., R. 26 E., Gila and Salt River Meridian, Arizona**

CHAINS

From this same cor. point, the stan. cor. of secs. 34 and 35, T. 25 N., R. 26 E., ., bears N. 89°40' W., 34.845 chs. dist.

From the cor. of secs. 3, 4, 33 and 34, on the S. bdy. of the Tp., monumented with a stainless steel post, 2 1/2 ins. diam., with brass cap, set and mkd., as described in the field notes of the dependent resurvey of the north boundary, T. 23 N., R. 26 E., executed concurrently under this same group.

N. 0°02' W., bet. secs. 33 and 34.

Over rolling and broken land.

40.00

Point for the 1/4 sec. cor. of secs. 33 and 34.

Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.

T 24 N R 26 E
1/4
S 33 | S 34

2002

Deposit a magnet in a white plastic case at the base of the stainless steel post.

80.00

Point for the cor. of secs. 27, 28, 33 and 34.

Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.

T 24 N R 26 E
S 28 | S 27
S 33 | S 34

2002

Deposit a magnet in a white plastic case at the base of the stainless steel post.

Land, rolling and broken.

Soil, sandy and sandy clay.

Timber, piñon and juniper; undergrowth, sagebrush, rabbit brush, cacti and native grasses.

From the cor. of secs. 26, 27, 34 and 35.

West, bet. secs. 27 and 34.

Over rolling and broken land.

**Survey of the Subdivisional Lines,
T. 24 N., R. 26 E., Gila and Salt River Meridian, Arizona**

CHAINS	
39.93	<p>Point for the 1/4 sec. cor. of secs. 27 and 34.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center;"> <p>T 24 N R 26 E</p> <p>S 27</p> <p>1/4 ———</p> <p>S 34</p> <p>2002</p> </div> <p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p>
79.86	<p>The cor. of secs. 27, 28, 33 and 34.</p> <p>Land, rolling and broken. Soil, sandy and sandy clay. Timber, piñon and juniper; undergrowth, sagebrush, rabbit brush, cacti and native grasses.</p> <hr/> <p>N. 0°02' W., bet. secs. 27 and 28.</p> <p>Over rolling and broken land.</p>
40.00	<p>Point for the 1/4 sec. cor. of secs. 27 and 28.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center;"> <p>T 24 N R 26 E</p> <p>1/4</p> <p>S 28 S 27</p> <p>2002</p> </div> <p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p>
78.30	<p>Trail road, bears NE and SW.</p>
80.00	<p>Point for the cor. of secs. 21, 22, 27 and 28.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center;"> <p>T 24 N R 26 E</p> <p>S 21 S 22</p> <p>S 28 S 27</p> <p>2002</p> </div>

**Survey of the Subdivisional Lines,
T. 24 N., R. 26 E., Gila and Salt River Meridian, Arizona**

CHAINS	
	<p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p> <p>Land, rolling and broken. Soil, sandy and sandy clay. Timber, piñon and juniper; undergrowth, sagebrush, rabbit brush, cacti and native grasses.</p> <hr/> <p>From the cor. of secs. 22, 23, 26 and 27.</p> <p>West, bet. secs. 22 and 27.</p> <p>Over rolling land.</p>
39.93	<p>Point for the 1/4 sec. cor. of secs. 22 and 27.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T 24 N R 26 E S 22 1/4 ——— S 27</p> <p style="text-align: center;">2002</p>
	<p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p>
79.86	<p>The cor. of secs. 21, 22, 27 and 28.</p> <p>Land, rolling. Soil, sandy and sandy clay. Timber, piñon and juniper; undergrowth, sagebrush, rabbit brush, cacti and native grasses.</p> <hr/> <p>N. 0°02' W., bet. secs. 21 and 22.</p> <p>Over rolling and broken land.</p>
40.00	<p>Point for the 1/4 sec. cor. of secs. 21 and 22.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T 24 N R 26 E 1/4 S 21 S 22</p> <p style="text-align: center;">2002</p>

**Survey of the Subdivisional Lines,
T. 24 N., R. 26 E., Gila and Salt River Meridian, Arizona**

CHAINS									
80.00	<p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p> <p>Point for the cor. of secs. 15, 16, 21 and 22.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center;"> <table style="margin: auto;"> <tr> <td>T 24 N</td> <td>R 26 E</td> </tr> <tr> <td>S 16</td> <td>S 15</td> </tr> <tr> <td>S 21</td> <td>S 22</td> </tr> </table> <p>2002</p> </div> <p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p> <p>Cor. is located on the N. slope of a spur ridge, 50 ft. high, bears E. and W.</p> <p>Land, rolling and broken. Soil, sandy and sandy clay. Timber, piñon and juniper; undergrowth, sagebrush, rabbit brush, cacti and native grasses.</p> <hr/> <p>From the cor. of secs. 14, 15, 22 and 23.</p> <p>West, bet. secs. 15 and 22.</p> <p>Over rolling and broken land.</p>	T 24 N	R 26 E	S 16	S 15	S 21	S 22		
T 24 N	R 26 E								
S 16	S 15								
S 21	S 22								
39.93	<p>Point for the 1/4 sec. cor. of secs. 15 and 22.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center;"> <table style="margin: auto;"> <tr> <td>T 24 N</td> <td>R 26 E</td> </tr> <tr> <td></td> <td>S 15</td> </tr> <tr> <td>1/4</td> <td>_____</td> </tr> <tr> <td></td> <td>S 22</td> </tr> </table> <p>2002</p> </div> <p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p>	T 24 N	R 26 E		S 15	1/4	_____		S 22
T 24 N	R 26 E								
	S 15								
1/4	_____								
	S 22								
79.86	<p>The cor. of secs. 15, 16, 21 and 22.</p>								

**Survey of the Subdivisional Lines,
T. 24 N., R. 26 E., Gila and Salt River Meridian, Arizona**

CHAINS	
	<p>Land, rolling and broken. Soil, sandy and sandy clay. Timber, piñon and juniper; undergrowth, sagebrush, rabbit brush, cacti and native grasses.</p> <hr/> <p>N. 0°02' W., bet. secs. 15 and 16.</p> <p>Over rolling and broken land.</p>
40.00	<p>Point for the 1/4 sec. cor. of secs. 15 and 16.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T 24 N R 26 E 1/4 S 16 S 15 2002</p> <p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p>
77.15	<p>Trail road, bears NE and SW.</p>
80.00	<p>Point for the cor. of secs. 9, 10, 15 and 16.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T 24 N R 26 E S 9 S 10 S 16 S 15 2002</p> <p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p> <p>Land, rolling and broken. Soil, sandy and sandy clay. Timber, piñon and juniper; undergrowth, sagebrush, rabbit brush and native grasses.</p> <hr/> <p>From the cor. of secs. 10, 11, 14 and 15.</p> <p>West, bet. secs. 10 and 15.</p> <p>Over rolling land.</p>
39.93	<p>Point for the 1/4 sec. cor. of secs. 10 and 15.</p>

**Survey of the Subdivisional Lines,
T. 24 N., R. 26 E., Gila and Salt River Meridian, Arizona**

CHAINS	
	<p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T 24 N R 26 E S 10 1/4 ——— S 15</p> <p style="text-align: center;">2002</p> <p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p>
79.86	<p>The cor. of secs. 9, 10, 15 and 16.</p> <p>Land, rolling. Soil, sandy and sandy clay. Timber, piñon and juniper; undergrowth, sagebrush, rabbit brush and native grasses.</p> <hr/> <p>N. 0°02' W., bet. secs. 9 and 10.</p> <p>Over rolling land.</p>
15.80	Navajo Route 28, a graded road, 25 ft. wide, bears E. and W.
40.00	<p>Point for the 1/4 sec. cor. of secs. 9 and 10.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T 24 N R 26 E 1/4 S 9 S 10</p> <p style="text-align: center;">2002</p> <p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p>
80.00	<p>Point for the cor. of secs. 3, 4, 9 and 10.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T 24 N R 26 E S 4 S 3 S 9 S 10</p> <p style="text-align: center;">2002</p>

**Survey of the Subdivisional Lines,
T. 24 N., R. 26 E., Gila and Salt River Meridian, Arizona**

CHAINS	
	<p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p> <p>Land, rolling. Soil, sandy and sandy clay. Timber, piñon and juniper; undergrowth, sagebrush, rabbit brush and native grasses.</p> <hr/> <p>From the cor. of secs. 2, 3, 10 and 11.</p> <p>West, bet. secs. 3 and 10.</p> <p>Over rolling land.</p>
39.93	<p>Point for the 1/4 sec. cor. of secs. 3 and 10.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T 24 N R 26 E S 3 1/4 ——— S 10</p> <p style="text-align: center;">2002</p>
79.86	<p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p> <p>The cor. of secs. 3, 4, 9 and 10.</p> <p>Land, rolling. Soil, sandy and sandy clay. Timber, piñon and juniper; undergrowth, sagebrush, rabbit brush and native grasses.</p> <hr/> <p>N. 0°02' W., bet. secs. 3 and 4.</p> <p>Over rolling land.</p>
40.00	<p>Point for the 1/4 sec. cor. of secs. 3 and 4.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T 24 N R 26 E 1/4 S 4 S 3</p> <p style="text-align: center;">2002</p>

**Survey of the Subdivisional Lines,
T. 24 N., R. 26 E., Gila and Salt River Meridian, Arizona**

CHAINS	<p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p>												
70.61	<p>Point for the closing cor. of secs. 3 and 4, at the intersection with the Sixth Standard Parallel North, on the N. bdy. of the Tp.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center; margin: 10px 0;"> <table style="margin: auto; border-collapse: collapse;"> <tr> <td style="padding: 0 5px;">T 25 N</td> <td style="padding: 0 5px;">R 26 E</td> <td></td> </tr> <tr> <td style="padding: 0 5px;">S 32</td> <td style="border-top: 1px solid black; padding: 0 5px;"></td> <td></td> </tr> <tr> <td style="padding: 0 5px;">S 4</td> <td style="border-left: 1px solid black; border-right: 1px solid black; padding: 0 5px;">S 3</td> <td style="padding: 0 5px;">T 24 N R 26 E</td> </tr> <tr> <td></td> <td style="padding: 0 5px;">CC</td> <td></td> </tr> </table> </div> <p style="text-align: center; margin: 10px 0;">2002</p> <p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p> <p>From this cor. point, the stan. cor. of secs. 32 and 33, T. 25 N., R. 26 E., bears S. 89°54' E., 5.24 chs. dist., monumented with a stainless steel post, 2 1/2 ins. diam., with brass cap, set, mkd and witnessed as described in the field notes of the dependent resurvey of the Sixth Standard Parallel North (south boundary), T. 25 N., R. 26 E., executed concurrently under this same group.</p> <p>From this same cor. point, the stan. 1/4 sec. cor. of sec. 32, T. 25 N., R. 26 E., bears N. 89°54' W., 34.78 chs. dist., monumented with a stainless steel post, 2 1/2 ins. diam., with brass cap, set and mkd. as described in the field notes of the dependent resurvey of the Sixth Standard Parallel North (south boundary), T. 25 N., R. 26 E., executed concurrently under this same group.</p> <p>Land, rolling. Soil, sandy and sandy clay. Timber, piñon and juniper; undergrowth, sagebrush, rabbit brush and native grasses.</p> <hr style="width: 50%; margin: 20px auto;"/> <p>Point for the 1/4 sec. cor. of sec. 3 only, T. 24 N., R. 26 E., at midpoint on the N. bdy. of sec. 3.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p>	T 25 N	R 26 E		S 32			S 4	S 3	T 24 N R 26 E		CC	
T 25 N	R 26 E												
S 32													
S 4	S 3	T 24 N R 26 E											
	CC												

**Survey of the Subdivisional Lines,
T. 24 N., R. 26 E., Gila and Salt River Meridian, Arizona**

CHAINS	
	<p>T 25 N R 26 E</p> <hr style="width: 10%; margin: auto;"/> <p>1/4 S 3</p> <p>T 24 N R 26 E</p> <p>2002</p>
	<p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p> <p>From this cor. point, the stan. 1/4 sec. cor. sec. 33, T. 25 N., R. 26 E., bears S. 89°58' E., 5.14 chs. dist.</p> <p>From this same cor. point, the stan. cor. of secs. 32 and 33, T. 25 N., R. 26 E., bears N. 89°58' W., 34.68 chs. dist.</p> <hr/> <p>From the cor. of secs. 4, 5, 32 and 33, on the S. bdy. of the Tp., monumented with a stainless steel post, 2 1/2 ins. diam., with brass cap, set and mkd., as described in the field notes of the dependent resurvey of the north boundary, T. 23 N., R. 26 E., executed concurrently under this same group.</p> <p>N. 0°03' W., bet. secs. 32 and 33.</p> <p>Over rolling land.</p>
40.00	<p>Point for the 1/4 sec. cor. of secs. 32 and 33.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T 24 N R 26 E 1/4 S 32 S 33</p> <p style="text-align: center;">2002</p> <p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p> <p>Cor. is located 80 lks. N. and 90 lks. S. of trail roads, both bear ENE and WSW.</p>
61.10	<p>Barbed wire fence, 3 strands, bears ENE and WSW.</p>
80.00	<p>Point for the cor. of secs. 28, 29, 32 and 33.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p>

**Survey of the Subdivisional Lines,
T. 24 N., R. 26 E., Gila and Salt River Meridian, Arizona**

CHAINS									
	<table border="1"> <tr> <td>T 24 N</td> <td>R 26 E</td> </tr> <tr> <td>S 29</td> <td>S 28</td> </tr> <tr> <td>S 32</td> <td>S 33</td> </tr> </table>	T 24 N	R 26 E	S 29	S 28	S 32	S 33		
T 24 N	R 26 E								
S 29	S 28								
S 32	S 33								
	2002								
	Deposit a magnet in a white plastic case at the base of the stainless steel post.								
	Land, rolling. Soil, sandy and sandy clay. Timber, piñon and juniper; undergrowth, sagebrush, rabbit brush, cacti and native grasses.								
	<hr/>								
	From the cor. of secs. 27, 28, 33 and 34.								
	West, bet. secs. 28 and 33.								
	Over rolling land.								
39.93	Point for the 1/4 sec. cor. of secs. 28 and 33.								
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.								
	<table border="1"> <tr> <td>T 24 N</td> <td>R 26 E</td> </tr> <tr> <td></td> <td>S 28</td> </tr> <tr> <td>1/4</td> <td>—</td> </tr> <tr> <td></td> <td>S 33</td> </tr> </table>	T 24 N	R 26 E		S 28	1/4	—		S 33
T 24 N	R 26 E								
	S 28								
1/4	—								
	S 33								
	2002								
	Deposit a magnet in a white plastic case at the base of the stainless steel post.								
79.86	The cor. of secs. 28, 29, 32 and 33.								
	Land, rolling. Soil, sandy and sandy clay. Timber, piñon and juniper; undergrowth, sagebrush, rabbit brush, cacti and native grasses.								
	<hr/>								
	N. 0°03' W., bet. secs. 28 and 29.								
	Over rolling and broken land.								
40.00	Point for the 1/4 sec. cor. of secs. 28 and 29.								
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.								

**Survey of the Subdivisional Lines,
T. 24 N., R. 26 E., Gila and Salt River Meridian, Arizona**

CHAINS	
	T 24 N R 26 E 1/4 S 29 S 28 2002
80.00	Deposit a magnet in a white plastic case at the base of the stainless steel post. Point for the cor. of secs. 20, 21, 28 and 29. Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.
	T 24 N R 26 E S 20 S 21 S 29 S 28 2002
	Deposit a magnet in a white plastic case at the base of the stainless steel post. Land, rolling and broken. Soil, sandy and sandy clay. Timber, piñon and juniper; undergrowth, sagebrush, rabbit brush, cacti and native grasses.
	<hr/> From the cor. of secs. 21, 22, 27 and 28. West, bet. secs. 21 and 28. Over rolling and broken land.
39.93	Point for the 1/4 sec. cor. of secs. 21 and 28. Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.
	T 24 N R 26 E S 21 1/4 ——— S 28 2002
79.86	Deposit a magnet in a white plastic case at the base of the stainless steel post. The cor. of secs. 20, 21, 28 and 29.

Survey of the Subdivisional Lines,
T. 24 N., R. 26 E., Gila and Salt River Meridian, Arizona

CHAINS	
	<p>Land, rolling and broken. Soil, sandy and sandy clay. Timber, piñon and juniper; undergrowth, sagebrush, rabbit brush, cacti and native grasses.</p> <hr/> <p>N. 0°03' W., bet. secs. 20 and 21.</p> <p>Over rolling and broken land.</p>
40.00	<p>Point for the 1/4 sec. cor. of secs. 20 and 21.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T 24 N R 26 E 1/4 S 20 S 21</p> <p style="text-align: center;">2002</p> <p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p>
51.30	<p>N. rim of a mesa, bears ENE and WSW.</p>
80.00	<p>Point for the cor. of secs. 16, 17, 20 and 21.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T 24 N R 26 E S 17 S 16 S 20 S 21</p> <p style="text-align: center;">2002</p> <p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p> <p>Land, rolling and broken. Soil, sandy and sandy clay. Timber, piñon and juniper; undergrowth, sagebrush, rabbit brush, cacti and native grasses.</p> <hr/> <p>From the cor. of secs. 15, 16, 21 and 22.</p> <p>West, bet. secs. 16 and 21.</p> <p>Over rolling and broken land.</p>
39.93	<p>Point for the 1/4 sec. cor. of secs. 16 and 21.</p>

**Survey of the Subdivisional Lines,
T. 24 N., R. 26 E., Gila and Salt River Meridian, Arizona**

CHAINS	
	<p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T 24 N R 26 E S 16 1/4 ——— S 21</p> <p style="text-align: center;">2002</p> <p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p>
79.86	<p>The cor. of secs. 16, 17, 20 and 21.</p> <p>Land, rolling and broken. Soil, sandy and sandy clay. Timber, piñon and juniper; undergrowth, sagebrush, rabbit brush, cacti and native grasses.</p> <hr/> <p>N. 0°03' W., bet. secs. 16 and 17.</p> <p>Over rolling land.</p>
40.00	<p>Point for the 1/4 sec. cor. of secs. 16 and 17.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T 24 N R 26 E 1/4 S 17 S 16</p> <p style="text-align: center;">2002</p> <p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p>
80.00	<p>Point for the cor. of secs. 8, 9, 16 and 17.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T 24 N R 26 E S 8 S 9 S 17 S 16</p> <p style="text-align: center;">2002</p> <p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p>

Survey of the Subdivisional Lines,
T. 24 N., R. 26 E., Gila and Salt River Meridian, Arizona

CHAINS	
	<p>Land, rolling. Soil, sandy and sandy clay. Timber, piñon and juniper; undergrowth, sagebrush, rabbit brush and native grasses.</p> <hr/> <p>From the cor. of secs. 9, 10, 15 and 16. West, bet. secs. 9 and 16. Over rolling land.</p>
39.93	<p>Point for the 1/4 sec. cor. of secs. 9 and 16. Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T 24 N R 26 E S 9 1/4 ——— S 16</p> <p style="text-align: center;">2002</p> <p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p>
79.86	<p>The cor. of secs. 8, 9, 16 and 17. Land, rolling. Soil, sandy and sandy clay. Timber, piñon and juniper; undergrowth, sagebrush, rabbit brush and native grasses.</p> <hr/> <p>N. 0°03' W., bet. secs. 8 and 9. Over rolling land.</p>
36.30	<p>Navajo Route 28, a graded road, 25 ft. wide, bears ESE and WNW.</p>
40.00	<p>Point for the 1/4 sec. cor. of secs. 8 and 9. Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T 24 N R 26 E 1/4 S 8 S 9</p> <p style="text-align: center;">2002</p> <p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p>

**Survey of the Subdivisional Lines,
T. 24 N., R. 26 E., Gila and Salt River Meridian, Arizona**

CHAINS									
80.00	<p>Point for the cor. of secs. 4, 5, 8 and 9.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center;"> <table border="1"> <tr><td>T 24 N</td><td>R 26 E</td></tr> <tr><td>S 5</td><td>S 4</td></tr> <tr><td>S 8</td><td>S 9</td></tr> </table> <p>2002</p> </div> <p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p> <p>Land, rolling. Soil, sandy and sandy clay. Timber, piñon and juniper; undergrowth, sagebrush, rabbit brush and native grasses.</p> <hr/> <p>From the cor. of secs. 3, 4, 9 and 10.</p> <p>West, bet. secs. 4 and 9.</p> <p>Over rolling land.</p>	T 24 N	R 26 E	S 5	S 4	S 8	S 9		
T 24 N	R 26 E								
S 5	S 4								
S 8	S 9								
39.93	<p>Point for the 1/4 sec. cor. of secs. 4 and 9.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center;"> <table border="1"> <tr><td>T 24 N</td><td>R 26 E</td></tr> <tr><td>S 4</td><td></td></tr> <tr><td>1/4</td><td>—</td></tr> <tr><td>S 9</td><td></td></tr> </table> <p>2002</p> </div> <p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p>	T 24 N	R 26 E	S 4		1/4	—	S 9	
T 24 N	R 26 E								
S 4									
1/4	—								
S 9									
79.86	<p>The cor. of secs. 4, 5, 8 and 9.</p> <p>Land, rolling. Soil, sandy and sandy clay. Timber, piñon and juniper; undergrowth, sagebrush, rabbit brush, cacti and native grasses.</p> <hr/> <p>N. 0°03' W., bet. secs. 4 and 5.</p> <p>Over rolling land.</p>								

**Survey of the Subdivisional Lines,
T. 24 N., R. 26 E., Gila and Salt River Meridian, Arizona**

CHAINS	
40.00	<p>Point for the 1/4 sec. cor. of secs. 4 and 5.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T 24 N R 26 E 1/4 S 5 S 4</p> <p style="text-align: center;">2002</p> <p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p>
54.90	Underground gas pipeline, bears ENE and WSW.
55.80	Underground gas pipeline, bears ENE and WSW.
70.75	<p>Point for the closing cor. of secs. 4 and 5, at the intersection with the Sixth Standard Parallel North, on the N. bdy. of the Tp.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T 25 N R 26 E S 31 ----- S 5 S 4 T 24 N R 26 E CC</p> <p style="text-align: center;">2002</p> <p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p> <p>From this cor. point, the stan. cor. of secs. 31 and 32, T. 25 N., R. 26 E., bears S. 89°54' E., 5.06 chs. dist., monumented with a stainless steel post, 2 1/2 ins. diam., with brass cap, set and mkd. as described in the field notes of the dependent resurvey of the Sixth Standard Parallel North (south boundary), T. 25 N., R. 26 E., executed concurrently under this same group.</p> <p>From this same cor. point, the stan. 1/4 sec. cor. of sec. 31, T. 25 N., R. 26 E., bears N. 89°54' W., 34.96 chs. dist., monumented with a stainless steel post, 2 1/2 ins. diam., with brass cap, set and mkd. as described in the field notes of the dependent resurvey of the Sixth Standard Parallel North (south boundary), T. 25 N., R. 26 E., executed concurrently under this same group.</p>

**Survey of the Subdivisional Lines,
T. 24 N., R. 26 E., Gila and Salt River Meridian, Arizona**

CHAINS	
	<p>Land, rolling. Soil, sandy and sandy clay. Timber, piñon and juniper; undergrowth, sagebrush, rabbit brush and native grasses.</p> <hr/> <p>Point for the 1/4 sec. cor. of sec. 4 only, T. 24 N., R. 26 E., at midpoint on the N. bdy. of sec. 4.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T 25 N R 26 E ----- 1/4 S 4 T 24 N R 26 E</p> <p style="text-align: center;">2002</p> <p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p> <p>From this cor. point, the stan. 1/4 sec. cor. sec. 32, T. 25 N., R. 26 E., bears S. 89°54' E., 5.15 chs. dist.</p> <p>From this same cor. point, the stan. cor. of secs. 31 and 32, T. 25 N., R. 26 E., bears N. 89°54' W., 34.87 chs. dist.</p> <hr/> <p>From the cor. of secs. 5, 6, 31 and 32, on the S. bdy. of the Tp., monumented with a stainless steel post, 2 1/2 ins. diam., with brass cap, set and mkd., as described in the field notes of the dependent resurvey of the north boundary, T. 23 N., R. 26 E., executed concurrently under this same group.</p> <p>N. 0°03' W., bet. secs. 31 and 32.</p> <p>Over rolling land.</p>
40.00	<p>Point for the 1/4 sec. cor. of secs. 31 and 32.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T 24 N R 26 E 1/4 S 31 S 32</p> <p style="text-align: center;">2002</p> <p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p> <p>Cor. is located 35 lks. N. of a trail road, bears NNE and SSW.</p>

**Survey of the Subdivisional Lines,
T. 24 N., R. 26 E., Gila and Salt River Meridian, Arizona**

CHAINS 80.00	<p>Point for the cor. of secs. 29, 30, 31 and 32.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <table style="margin-left: auto; margin-right: auto; border-collapse: collapse;"> <tr> <td style="padding: 0 5px;">T 24 N</td> <td style="padding: 0 5px;">R 26 E</td> </tr> <tr> <td style="padding: 0 5px; border-right: 1px solid black;">S 30</td> <td style="padding: 0 5px;">S 29</td> </tr> <tr> <td style="padding: 0 5px; border-right: 1px solid black;">S 31</td> <td style="padding: 0 5px;">S 32</td> </tr> </table> <p style="text-align: center;">2002</p> <p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p> <p>Land, rolling. Soil, sandy and sandy clay. Timber, piñon and juniper; undergrowth, greasewood, rabbit brush and native grasses.</p> <hr/> <p>From the cor. of secs. 28, 29, 32 and 33.</p> <p>West, bet. secs. 29 and 32.</p> <p>Over rolling land.</p>	T 24 N	R 26 E	S 30	S 29	S 31	S 32
T 24 N	R 26 E						
S 30	S 29						
S 31	S 32						
39.93	<p>Point for the 1/4 sec. cor. of secs. 29 and 32.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <table style="margin-left: auto; margin-right: auto; border-collapse: collapse;"> <tr> <td style="padding: 0 5px;">T 24 N</td> <td style="padding: 0 5px;">R 26 E</td> </tr> <tr> <td style="padding: 0 5px;"></td> <td style="padding: 0 5px;">S 29</td> </tr> <tr> <td style="padding: 0 5px;">1/4</td> <td style="padding: 0 5px; border-top: 1px solid black;">S 32</td> </tr> </table> <p style="text-align: center;">2002</p> <p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p> <p>Cor. is located 1.65 chs. S. of a trail road, bears ENE and WSW.</p>	T 24 N	R 26 E		S 29	1/4	S 32
T 24 N	R 26 E						
	S 29						
1/4	S 32						
79.86	<p>The cor. of secs. 29, 30, 31 and 32.</p> <p>Land, rolling. Soil, sandy and sandy clay. Timber, piñon and juniper; undergrowth, sagebrush, rabbit brush and native grasses.</p> <hr/> <p>West, bet. secs. 30 and 31.</p>						

**Survey of the Subdivisional Lines,
T. 24 N., R. 26 E., Gila and Salt River Meridian, Arizona**

CHAINS	
	Over rolling land.
40.00	Point for the 1/4 sec. cor. of secs. 30 and 31. Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd. <div style="text-align: center;"> T 24 N R 26 E S 30 1/4 ——— S 31 2002 </div>
78.02	Deposit a magnet in a white plastic case at the base of the stainless steel post. The cor. of secs. 25, 30, 31 and 36, on the W. bdy. of the Tp., hereinbefore described. Land, rolling. Soil, sandy and sandy clay. Timber, piñon and juniper; undergrowth, greasewood, rabbit brush and native grasses.
	From the cor. of secs. 29, 30, 31 and 32. N. 0°03' W., bet. secs. 29 and 30. Over rolling and broken land.
40.00	Point for the 1/4 sec. cor. of secs. 29 and 30. Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd. <div style="text-align: center;"> T 24 N R 26 E 1/4 S 30 S 29 2002 </div>
74.60	Deposit a magnet in a white plastic case at the base of the stainless steel post. N. rim of mesa, bears E. and W.
80.00	Point for the cor. of secs. 19, 20, 29 and 30. Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.

**Survey of the Subdivisional Lines,
T. 24 N., R. 26 E., Gila and Salt River Meridian, Arizona**

CHAINS									
	<table border="0"> <tr> <td>T 24 N</td> <td>R 26 E</td> </tr> <tr> <td>S 19</td> <td>S 20</td> </tr> <tr> <td>S 30</td> <td>S 29</td> </tr> </table>	T 24 N	R 26 E	S 19	S 20	S 30	S 29		
T 24 N	R 26 E								
S 19	S 20								
S 30	S 29								
	2002								
	Deposit a magnet in a white plastic case at the base of the stainless steel post.								
	Land, rolling and broken. Soil, sandy and sandy clay. Timber, piñon and juniper; undergrowth, sagebrush, greasewood, rabbit brush and native grasses.								
	<hr/>								
	From the cor. of secs. 20, 21, 28 and 29.								
	West, bet. secs. 20 and 29.								
	Over rolling and broken land.								
39.93	Point for the 1/4 sec. cor. of secs. 20 and 29.								
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.								
	<table border="0"> <tr> <td>T 24 N</td> <td>R 26 E</td> </tr> <tr> <td></td> <td>S 20</td> </tr> <tr> <td>1/4</td> <td>—</td> </tr> <tr> <td></td> <td>S 29</td> </tr> </table>	T 24 N	R 26 E		S 20	1/4	—		S 29
T 24 N	R 26 E								
	S 20								
1/4	—								
	S 29								
	2002								
	Deposit a magnet in a white plastic case at the base of the stainless steel post.								
73.00	Top of mesa, bears NNE and SSW.								
79.86	The cor. of secs. 19, 20, 29 and 30.								
	Land, rolling. Soil, sandy and sandy clay. Timber, piñon and juniper; undergrowth, sagebrush, rabbit brush and native grasses.								
	<hr/>								
	West, bet. secs. 19 and 30.								
	Over rolling land.								
40.00	Point for the 1/4 sec. cor. of secs. 19 and 20.								

**Survey of the Subdivisional Lines,
T. 24 N., R. 26 E., Gila and Salt River Meridian, Arizona**

CHAINS	
	<p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T 24 N R 26 E S 19 1/4 ——— S 30</p> <p style="text-align: center;">2002</p> <p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p>
77.93	<p>The cor. of secs. 19, 24, 25 and 30, on the W. bdy. of the Tp., hereinbefore described.</p> <p>Land, rolling. Soil, sandy and sandy clay. Timber, piñon and juniper; undergrowth, sagebrush, rabbit brush and native grasses.</p> <hr/> <p>From the cor. of secs. 19, 20, 29 and 30.</p> <p>N. 0°03' W., bet. secs. 19 and 20.</p> <p>Over rolling land.</p>
40.00	<p>Point for the 1/4 sec. cor. of secs. 19 and 20.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T 24 N R 26 E 1/4 S 19 S 20</p> <p style="text-align: center;">2002</p> <p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p> <p>Cor. is located 25 lks. S. of a trail road, bears E. and W.</p>
80.00	<p>Point for the cor. of secs. 17, 18, 19 and 20.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p>

**Survey of the Subdivisional Lines,
T. 24 N., R. 26 E., Gila and Salt River Meridian, Arizona**

CHAINS	
	T 24 N R 26 E S 18 S 17 S 19 S 20
	2002
	Deposit a magnet in a white plastic case at the base of the stainless steel post. Land, rolling. Soil, sandy and sandy clay. Timber, piñon and juniper; undergrowth, sagebrush, rabbit brush and native grasses.
	<hr/> From the cor. of secs. 16, 17, 20 and 21. West, bet. secs. 17 and 20. Over rolling land.
39.93	Point for the 1/4 sec. cor. of secs. 17 and 20. Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.
	T 24 N R 26 E S 17 1/4 ——— S 20
	2002
	Deposit a magnet in a white plastic case at the base of the stainless steel post.
79.86	The cor. of secs. 17, 18, 19 and 20. Land, rolling. Soil, sandy and sandy clay. Timber, piñon and juniper; undergrowth, sagebrush, rabbit brush and native grasses.
	<hr/> West, bet. secs. 18 and 19. Over rolling land.
40.00	Point for the 1/4 sec. cor. of secs. 18 and 19. Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.

**Survey of the Subdivisional Lines,
T. 24 N., R. 26 E., Gila and Salt River Meridian, Arizona**

CHAINS	
	T 24 N R 26 E S 18 1/4 ——— S 19 2002
	Deposit a magnet in a white plastic case at the base of the stainless steel post.
77.84	The cor. of secs. 13, 18, 19 and 24, on the W. bdy. of the Tp., hereinbefore described. Land, rolling. Soil, sandy and sandy clay. Timber, piñon and juniper; undergrowth, sagebrush, rabbit brush and native grasses.
	<hr/> From the cor. of secs. 17, 18, 19 and 20. N. 0°03' W., bet. secs. 17 and 18. Over rolling land.
40.00	Point for the 1/4 sec. cor. of secs. 17 and 18. Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.
	T 24 N R 26 E 1/4 S 18 S 17 2002
	Deposit a magnet in a white plastic case at the base of the stainless steel post.
80.00	Point for the cor. of secs. 7, 8, 17 and 18. Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.
	T 24 N R 26 E S 7 S 8 ——— S 18 S 17 2002
	Deposit a magnet in a white plastic case at the base of the stainless steel post.

Survey of the Subdivisional Lines,
T. 24 N., R. 26 E., Gila and Salt River Meridian, Arizona

CHAINS	
	<p>Land, rolling. Soil, sandy and sandy clay. Timber, piñon and juniper; undergrowth, sagebrush, rabbit brush and native grasses.</p> <hr/> <p>From the cor. of secs. 8, 9, 16 and 17.</p> <p>West, bet. secs. 8 and 17.</p> <p>Over rolling land.</p>
39.93	<p>Point for the 1/4 sec. cor. of secs. 8 and 17.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T 24 N R 26 E S 8 1/4 ——— S 17</p> <p style="text-align: center;">2002</p> <p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p>
79.86	<p>The cor. of secs. 7, 8, 17 and 18.</p> <p>Land, rolling. Soil, sandy and sandy clay. Timber, piñon and juniper; undergrowth, sagebrush, rabbit brush and native grasses.</p> <hr/> <p>West, bet. secs. 7 and 18.</p> <p>Over rolling land.</p>
40.00	<p>Point for the 1/4 sec. cor. of secs. 7 and 18.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T 24 N R 26 E S 7 1/4 ——— S 18</p> <p style="text-align: center;">2002</p> <p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p>

Survey of the Subdivisional Lines,
T. 24 N., R. 26 E., Gila and Salt River Meridian, Arizona

CHAINS	
77.75	<p>The cor. of secs. 7, 12, 13 and 18, on the W. bdy. of the Tp., hereinbefore described.</p> <p>Land, rolling. Soil, sandy and sandy clay. Timber, piñon and juniper; undergrowth, sagebrush, rabbit brush and native grasses.</p> <hr/> <p>From the cor. of secs. 7, 8, 17 and 18.</p> <p>N. 0°03' W., bet. secs. 7 and 8.</p> <p>Over rolling land.</p>
40.00	<p>Point for the 1/4 sec. cor. of secs. 7 and 8.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T 24 N R 26 E 1/4 S 7 S 8 2002</p> <p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p>
63.30	Navajo Route 9606, a graded road, 20 ft. wide, bears E. and W.
63.80	Navajo Route 28, a graded road, 20 ft. wide, bears ESE and WNW.
80.00	<p>Point for the cor. of secs. 5, 6, 7 and 8.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T 24 N R 26 E S 6 S 5 S 7 S 8 2002</p> <p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p>

Survey of the Subdivisional Lines,
T. 24 N., R. 26 E., Gila and Salt River Meridian, Arizona

CHAINS	
	<p>Land, rolling. Soil, sandy and sandy clay. Timber, piñon and juniper; undergrowth, sagebrush, rabbit brush and native grasses.</p> <hr/> <p>From the cor. of secs. 4, 5, 8 and 9.</p> <p>West, bet. secs. 5 and 8.</p> <p>Over rolling land.</p>
39.93	<p>Point for the 1/4 sec. cor. of secs. 5 and 8.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T 24 N R 26 E S 5 1/4 ——— S 8</p> <p style="text-align: center;">2002</p> <p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p>
79.86	<p>The cor. of secs. 5, 6, 7 and 8.</p> <p>Land, rolling. Soil, sandy and sandy clay. Timber, piñon and juniper; undergrowth, sagebrush, rabbit brush and native grasses.</p> <hr/> <p>West, bet. secs. 6 and 7.</p> <p>Over rolling land.</p>
40.00	<p>Point for the 1/4 sec. cor. of secs. 6 and 7.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T 24 N R 26 E S 6 1/4 ——— S 7</p> <p style="text-align: center;">2002</p> <p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p>

**Survey of the Subdivisional Lines,
T. 24 N., R. 26 E., Gila and Salt River Meridian, Arizona**

CHAINS	
62.75	Navajo Route 28, a graded road, 20 ft. wide, bears ESE and WNW.
77.67	The cor. of secs. 1, 6, 7 and 12, on the W. bdy. of the Tp.. hereinbefore described. Land, rolling. Soil, sandy and sandy clay. Timber, piñon and juniper; undergrowth, sagebrush, rabbit brush and native grasses. <hr/>
	From the cor. of secs. 5, 6, 7 and 8. N. 0°03' W., bet. secs. 5 and 6. Over rolling land.
29.60	Underground gas pipeline, bears ENE and WSW.
30.30	Underground gas pipeline, bears ENE and WSW.
40.00	Point for the 1/4 sec. cor. of secs. 5 and 6. Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd. <div style="text-align: center;"> T 24 N R 26 E 1/4 S 6 S 5 2002 </div>
	Deposit a magnet in a white plastic case at the base of the stainless steel post.
70.89	Point for the closing cor. of secs. 5 and 6, at the intersection with the Sixth Standard Parallel North, on the N. bdy. of the Tp. Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd. <div style="text-align: center;"> T 25 N R 25 E S 36 <hr style="width: 10%; margin: 0 auto;"/> S 6 S 5 T 24 N R 26 E CC 2002 </div>
	Deposit a magnet in a white plastic case at the base of the stainless steel post.

**Survey of the Subdivisional Lines,
T. 24 N., R. 26 E., Gila and Salt River Meridian, Arizona**

CHAINS

From this cor. point, the stan. cor. of Tps. 25 N., Rs. 25 and 26 E., bears S. 89°53' E., 4.88 chs. dist., monumented with a stainless steel post, 2 1/2 ins. diam., with brass cap, set, mkd. and witnessed as described in the field notes of the dependent resurvey of a portion of the Sixth Standard Parallel North (south boundary), T. 25 N., R. 25 E., executed concurrently under this same group.

From this same cor. point, the stan. 1/4 sec. cor. of sec. 36, T. 25 N., R. 25 E., bears N. 89°53' W., 35.30 chs. dist., monumented with a stainless steel post, 2 1/2 ins. diam., with brass cap set, mkd. and witnessed as described in the field notes of the dependent resurvey of a portion of the Sixth Standard Parallel North (south boundary), T. 25 N., R. 25 E., executed concurrently under this same group.

Land, rolling.

Soil, sandy and sandy clay.

Timber, piñon and juniper; undergrowth, sagebrush, rabbit brush and native grasses.

Point for the 1/4 sec. cor. of sec. 5 only, T. 24 N., R. 26 E., at midpoint on the N. bdy. of sec. 5.

Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.

T 25 N R 26 E

1/4 S 5

T 24 N R 26 E

2002

Deposit a magnet in a white plastic case at the base of the stainless steel post.

From this cor. point, the stan. 1/4 sec. cor. sec. 31, T. 25 N., R. 26 E., bears S. 89°54' E., 4.97 chs. dist.

From this same cor. point, the stan. cor. of Tps. 25 N., Rs. 25 and 26 E., bears N. 89°54' W., 35.05 chs. dist.

Point for the 1/4 sec. cor. of secs. 6 only, T. 24 N., R. 26 E., at 40 chs. westing from the closing cor. of secs. 5 and 6, on the N. bdy. of sec. 6.

Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.

**Survey of the Subdivisional Lines,
T. 24 N., R. 26 E., Gila and Salt River Meridian, Arizona**

CHAINS	<p>T 25 N R 25 E</p> <hr style="width: 10%; margin: auto;"/> <p>1/4 S 6</p> <p>T 24 N R 26 E</p> <p>2002</p> <p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p> <p>From this cor. point, the stan. 1/4 sec. cor. of sec. 36, T. 25 N., R. 25 E., bears S. 89°51' E., 4.70 chs. dist.</p> <p>From this same cor. point, the stan. cor. of secs. 35 and 36, T. 25 N., R. 25 E., bears N. 89°51' W., 35.39 chs. dist., hereinbefore described.</p> <hr/> <p style="text-align: center;">GENERAL DESCRIPTION</p> <hr/> <p>The area surveyed is within the Navajo Indian Reservation, in the vicinity of Klagetoh, Arizona. The terrain is mostly rolling land with some areas of rugged and broken land in the central and southwestern portion of the township. The drainage is to the south.</p> <p>The elevation varies from 6200 to 6800 feet above sea level. The soil is sand and sandy clay. The timber consist of piñon and juniper. Undergrowth principally consists of sagebrush, rabbit brush, greasewood, cacti and native grasses.</p> <p>Principal access to the township is provided by U. S. Highway 191, which runs north and south in the eastern portion of the township. There are several graded roads and numerous trail roads through out the township. Much of this area is used for grazing livestock. There are numerous residences through out the township with no mining activity in this township.</p> <p>The mean magnetic declination of 11 1/2° E. was derived from the computer program GEOMAGIX, utilizing the World Magnetic Model for Epoch 2000 for the dates of survey.</p> <hr/>
--------	--

**UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT**

FIELD ASSISTANTS

NAMES	CAPACITY
William F. Olver	Cadastral Surveyor
Daniel Bryan	Engineering Technician
Wilfred Chee	Engineering Technician
Edward Clarke	Engineering Technician
Reuben Mason	Engineering Technician
Barney Woodie	Engineering Technician

CERTIFICATE OF SURVEY

I, Jones Curtiss, Cadastral Surveyor, HEREBY CERTIFY upon honor, that in pursuance of special instructions bearing date of the 1st day of May, 2002, and supplemental special instructions bearing date of the 23rd day of September, 2002, I have surveyed the east and west boundaries, and the subdivisional lines, T. 24 N., R. 26 E., of the Gila and Salt River Meridian, in the State of Arizona, which are represented in the foregoing field notes as having been executed by me and under my direction. Said survey has been made in strict conformity with said special instructions, supplemental special instructions, the Manual of Instructions for the Survey of the Public Lands of the United States, 1973, and in specific manner described in the foregoing field notes.

May 16, 2005
(Date)

Jones Curtiss
(Cadastral Surveyor)

CERTIFICATE OF APPROVAL

BUREAU OF LAND MANAGEMENT
Phoenix, Arizona

The foregoing field notes of the survey of the east and west boundaries, and the subdivisional lines, T. 24 N., R. 26 E., Gila and Salt River Meridian, in the State of Arizona, executed by Jones Curtiss, Cadastral Surveyor, having been critically examined and found correct, are hereby approved.

June 2, 2005
(Date)

Stephen K. Hansen
(Acting Chief Cadastral Surveyor of Arizona)

~~CERTIFICATE OF TRANSCRIPT~~

~~I CERTIFY That the foregoing transcript of the field notes of the above described surveys in T. 24 N., R. 26 E., Gila and Salt River Meridian, Arizona, is a true copy of the original field notes.~~

~~_____
(Date)~~

~~_____
(Acting Chief Cadastral Surveyor of Arizona)~~