

ORIGINAL

**UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT**

FIELD NOTES

OF THE

SURVEY OF THE SEVENTH STANDARD PARALLEL NORTH (SOUTH BOUNDARY),

THE EAST AND NORTH BOUNDARIES,

AND

THE SUBDIVISIONAL LINES

OF

TOWNSHIP 29 NORTH, RANGE 27 EAST,

OF THE GILA AND SALT RIVER MERIDIAN,

IN THE STATE OF ARIZONA

EXECUTED BY

Leonard R. Sandoval, Cadastral Surveyor

Under Special Instructions dated May 6, 2003, approved May 6, 2003, which provided for the surveys included under Group No. 902, and assignment instructions dated May 6, 2003.

Survey commenced June 3, 2003

Survey completed July 21, 2003

INDEX DIAGRAM

TOWNSHIP 29 NORTH RANGE 27 EAST
 GILA AND SALT RIVER MERIDIAN, ARIZONA

19	19	18	17	16	15
6	67 5	55 4	45 3	36 2	28 1 14
66	65	54	44	35	27
7	64 8	53 9	43 10	35 11	26 12 13
64	63	52	43	34	26
18	62 17	51 16	42 15	33 14	25 13 12
61	60	50	41	33	24
19	60 20	49 21	40 22	31 23	23 24 11
59	58	48	39	31	23
30	57 29	47 28	38 27	30 26	22 25 10
57	56	46	38	29	21
31	55 32	45 33	37 34	28 35	21 36 9
8	7	6	5	4	4

T. 29 N., R. 27 E., Gila and Salt River Meridian, Arizona

CHAINS

The following field notes describe the survey of the Seventh Standard Parallel North (south boundary), the east and north boundaries, and the subdivisional lines of Township 29 North, Range 27 East, Gila and Salt River Meridian, Arizona.

The history of surveys pertaining to this survey is as follows:

Steve D. Cully and William F. Olver surveyed the Seventh Standard Parallel North (south boundary) and the east boundary of Township 29 North, Range 26 East, in 1990-91.

The survey was executed in accordance with the specifications as set forth in the Manual of Instructions for the Survey of the Public Lands of the United States, 1973, and the Special Instructions dated May 6, 2003, for Group No. 902, Arizona.

The true meridian direction and length of all lines were determined by real time kinematic global positioning system observations using Trimble Navigation 5700 model receivers.

Preliminary to the survey, the lines of the prior surveys were retraced and search was made for all corners and other calls of record. Identified corners were remonumented in their original positions. The retracement data were thoroughly verified and only the true line field notes are given herein.

Geodetic control was derived from Global Positioning System (GPS) static observations post processed by National Geodetic Survey, Online Positioning User Service (OPUS), utilizing Continuously Operating Reference Stations (CORS) "FLAGSTAFF1", "AZTEC", and "PIE_TOWN". The NAD 83(CORS96) (EPOCH:2002), geographic position of the standard corner of Township 29 North, Ranges 27 and 28 East, is as follows:

Latitude: 35°52'02.99" N. Longitude: 109°23'14.92" W.

The mean magnetic declination is 11 1/4° E.

**Survey of the Seventh Standard Parallel North (South Boundary),
T. 29 N., R. 27 E., Gila and Salt River Meridian, Arizona**

CHAINS	
	<p>Beginning at the stan. Tp. cor. of Tps. 29 N., Rs. 27 and 28 E., monumented with a stainless steel post, 2 1/2 ins. diam., firmly set, projecting 4 ins. above ground, with brass cap mkd. as described in the field notes of the survey of the Seventh Parallel North(south boundary) of T. 29 N., R. 28 E., executed concurrently under this same group.</p> <p>West, on the S. bdy. of sec. 36.</p> <p>Over low rolling land.</p>
34.10	Navajo Route 26, a graded road, 25 ft. wide, bears ENE and WSW.
40.00	<p>Point for the stan. 1/4 sec. cor. of sec. 36.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p>
	<p align="center">SC T 29 N R 27 E 1/4 S 36 ----- 2003</p> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p> <p>Cor. is located at 1.10 chs. N. of Navajo Route 26, a graded road, 25 ft. wide, bears ENE and WSW.</p>
80.00	<p>Point for the stan. cor. of secs. 35 and 36.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p>
	<p align="center">SC T 29 N R 27 E S 35 S 36 ----- 2003</p> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p> <p>Land, gently rolling. Soil, sandy and gravelly clay. Timber, piñon and juniper; undergrowth, brush and native grasses.</p> <hr/> <p>West, on the S. bdy. of sec. 35.</p>

**Survey of the Seventh Standard Parallel North (South Boundary),
T. 29 N., R. 27 E., Gila and Salt River Meridian, Arizona**

CHAINS	
	Over rolling and broken land.
38.10	Rocky wash, 20 ft. wide, 6 ft. deep, drains NW.
40.00	Point for the stan. 1/4 sec. cor. of sec. 35.
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.
	<p align="center">SC T 29 N R 27 E 1/4 S 35</p> <hr/>
	2003
	Deposit a magnet, in a white plastic case, at the base of the stainless steel post.
66.08	E. right-of-way fence of Navajo Route 27, barbed wire, 5 strand, parallels the highway.
68.34	Navajo Route 27, asphalt pavement, 32 ft. wide, bears SE and NW.
71.54	W. right-of-way fence of Navajo Route 27, barbed wire, 5 strand, parallels the highway.
74.63	Underground gas pipeline, bears SE and NW.
74.75	Power line, bears SE and NW.
80.00	Point for the stan. cor. of secs. 34 and 35.
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.
	<p align="center">SC T 29 N R 27 E S 34 S 35</p> <hr/>
	2003
	Deposit a magnet, in a white plastic case, at the base of the stainless steel post.
	<p>Land, rolling and broken. Soil, sandy and gravelly clay. Timber, piñon and juniper; undergrowth, brush and native grasses.</p> <hr/>
	West, on the S. bdy. of sec. 34.

**Survey of the Seventh Standard Parallel North (South Boundary),
T. 29 N., R. 27 E., Gila and Salt River Meridian, Arizona**

CHAINS	
	Over rolling and broken land; ascend the east slope of mesa.
5.20	NE rim of Red Mesa, top of sandstone ledge, bears NNE and SSW, thence over nearly level land.
40.00	Point for the stan. 1/4 sec. cor. of sec. 34. Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.
	<p align="center">SC T 29 N R 27 E 1/4 S 34 -----</p>
	2003
	Deposit a magnet, in a white plastic case, at the base of the stainless steel post.
59.70	NW rim of Red Mesa, top of sandstone ledge, bears N. and S., thence descend over rugged and broken NW slope.
80.00	Point for the stan. cor. of secs. 33 and 34. Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.
	<p align="center">SC T 29 N R 27 E S 33 S 34 -----</p>
	2003
	Deposit a magnet, in a white plastic case, at the base of the stainless steel post.
	Land, nearly level to rugged and broken. Soil, sandy and gravelly clay. Timber, piñon and juniper; undergrowth, brush and native grasses.
	----- West, on the S. bdy. of sec. 33.
	Over rugged and broken land; descend the NW slope of Red Mesa.
37.65	Wash, 50 ft. wide, 25 ft. deep, drains WNW.
40.00	Point for the stan. 1/4 sec. cor. of sec. 33.

**Survey of the Seventh Standard Parallel North (South Boundary),
T. 29 N., R. 27 E., Gila and Salt River Meridian, Arizona**

CHAINS	
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.
	<p align="center">SC T 29 N R 27 E 1/4 S 33 _____</p>
	2003
	Deposit a magnet, in a white plastic case, at the base of the stainless steel post.
	Cor. is located N. of sandstone ledge, 9 ft. high.
80.00	Point for the stan. cor. of secs. 32 and 33.
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.
	<p align="center">SC T 29 N R 27 E S 32 S 33 _____</p>
	2003
	Deposit a magnet, in a white plastic case, at the base of the stainless steel post.
	<p>Land, rugged and broken. Soil, sandy and rocky clay. Timber, piñon and juniper; undergrowth and native grasses.</p> <hr/>
	West, on the S. bdy. of sec. 32.
	Over rugged and broken land; descend the NW slope of Red Mesa.
39.55	Wash, 12 ft. wide, 3 ft. deep, drains NW.
40.00	Point for the stan. 1/4 sec. cor. of sec. 32.
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 20 ins. in sandstone bedrock, in a mound of stone, 3 ft. base, to top, with brass cap mkd.
	<p align="center">SC T 29 N R 27 E 1/4 S 32 _____</p>
	2003

**Survey of the Seventh Standard Parallel North (South Boundary),
T. 29 N., R. 27 E., Gila and Salt River Meridian, Arizona**

CHAINS	
	Deposit a magnet, in a white plastic case, at the base of the stainless steel post.
72.19	Barbed wire fence, 5 strands, bears ENE and WNW.
77.85	Trail road, bears SE and NW.
80.00	Point for the stan. cor. of secs. 31 and 32.
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 20 ins. in sandstone bedrock, in a mound of stone, 3 ft. base, to top, with brass cap mkd.
	<p align="center">SC T 29 N R 27 E <u>S 31 S 32</u></p>
	2003
	Deposit a magnet, in a white plastic case, at the base of the stainless steel post.
	<p>Land, rugged and broken. Soil, sandy and rocky clay. Timber, piñon and juniper; undergrowth, brush and native grasses.</p>
	West, on the S. bdy. of sec. 31.
	Over rolling and broken land; gradual descent of the NW slope of Red Mesa.
40.00	Point for the stan. 1/4 sec. cor. of sec. 31.
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.
	<p align="center">SC T 29 N R 27 E <u>1/4 S 31</u></p>
	2003
	Deposit a magnet, in a white plastic case, at the base of the stainless steel post.
	Cor. is located at the base of descent of the NW slope of Red Mesa, thence over rolling land.
43.45	Wash, 70 ft. wide, 6 ft. deep, drains NW.

**Survey of the Seventh Standard Parallel North (South Boundary),
T. 29 N., R. 27 E., Gila and Salt River Meridian, Arizona**

CHAINS	
54.55	Trail road, bears ESE and WNW.
79.56	<p>The stan. Tp. cor. of Tps. 29 N., Rs. 26 and 27 E., monumented with a stainless steel post, 2 1/2 ins. diam., firmly set, projecting 11 ins. above ground, with brass cap mkd. SC T29N R26E R27E S36 S31 1990.</p> <p>Add the marks 2003 to the brass cap.</p> <p>from which new accessories</p> <p>A stainless steel post, 28 ins. long, 2 1/2 ins. diam., set 24 ins. in ground for a reference monument, bears N. 45°00' E., 125 ft. dist., with brass cap mkd. RM T29N R27E SC S31 125 FT TO COR 2003 and an arrow pointing to the cor. Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p> <p>A stainless steel post, 28 ins. long, 2 1/2 ins. diam., set 24 ins. in ground for a reference monument, bears N. 45°00' W., 210 ft. dist., with brass cap mkd. RM T29N R26E SC S36 210 FT TO COR 2003 and an arrow pointing to the cor. Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p> <p>The stan. Tp. cor. is located in eroding badlands.</p> <p>Land, rugged and broken to rolling. Soil, sandy and rocky clay. Timber, scattered piñon and juniper; undergrowth, brush and native grasses.</p>
<hr/> <p>Survey of the East Boundary, T. 29 N., R. 27 E., Gila and Salt River Meridian, Arizona</p> <hr/>	
	<p>From the stan. Tp. cor. of Tps. 29 N., Rs. 27 and 28 E., hereinbefore described.</p>
	<p>North, bet. secs. 31 and 36.</p>
	<p>Over gently rolling land.</p>
6.15	<p>Navajo Route 26, a graded road, 25 ft. wide, bears ENE and WSW.</p>
40.00	<p>Point for the 1/4 sec. cor. of secs. 31 and 36.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 20 ins. in sandstone bedrock, in a mound of stone, 3 ft. base, to top, with brass cap mkd.</p>

**Survey of the East Boundary,
T. 29 N., R. 27 E., Gila and Salt River Meridian, Arizona**

CHAINS	
	T 29 N 1/4 R 27 E R 28 E S 36 S 31 2003
	Deposit a magnet, in a white plastic case, at the base of the stainless steel post.
55.10	S. rim of a canyon, top of sandstone ledge, bears ENE and WSW, thence descend into the canyon.
80.00	Point for the cor. of secs. 25, 30, 31, and 36. Set a brass tablet, 3 1/4 ins. diam., 2 1/2 ins. stem, cemented in a drill hole, in sandstone outcrop, with top mkd.
	T 29 N R 27 E R 28 E S 25 S 30 <hr style="width: 50%; margin: 0 auto;"/> S 36 S 31 2003
	Deposit a magnet, in a white plastic case, at the base of the brass tablet. Land, gently rolling to rugged and broken. Soil, sandy and rocky clay. Timber, piñon and juniper; undergrowth, brush and native grasses.
	<hr/> North, bet. secs. 25 and 30. Over rugged and broken land; ascend out of the canyon.
13.60	N. rim of the canyon, top of sandstone ledge, bears NE and SW, thence over rolling land.
40.00	Point for the 1/4 sec. cor. of secs. 25 and 30. Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.
	T 29 N 1/4 R 27 E R 28 E S 25 S 30 2003

**Survey of the East Boundary,
T. 29 N., R. 27 E., Gila and Salt River Meridian, Arizona**

CHAINS									
	Deposit a magnet, in a white plastic case, at the base of the stainless steel post.								
80.00	Point for the cor. of secs. 19, 24, 25, and 30. Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.								
	<table style="margin-left: auto; margin-right: auto;"> <tr><td colspan="2">T 29 N</td></tr> <tr><td>R 27 E</td><td>R 28 E</td></tr> <tr><td>S 24</td><td>S 19</td></tr> <tr><td style="border-top: 1px solid black;">S 25</td><td style="border-top: 1px solid black;">S 30</td></tr> </table>	T 29 N		R 27 E	R 28 E	S 24	S 19	S 25	S 30
T 29 N									
R 27 E	R 28 E								
S 24	S 19								
S 25	S 30								
	2003								
	Deposit a magnet, in a white plastic case, at the base of the stainless steel post.								
	Land, rugged and broken to rolling. Soil, sandy and rocky clay, with sandstone outcrops. Timber, piñon and juniper; undergrowth, brush and native grasses.								
	North, bet. secs. 19 and 24.								
	Over rolling land.								
23.80	S. rim of a narrow canyon, top of sandstone ledge, bears SE and NW, thence across the canyon.								
36.85	N. rim of the same canyon, top of sandstone ledge, bears SE and NW.								
40.00	Point for the 1/4 sec. cor. of secs. 19 and 24. Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.								
	<table style="margin-left: auto; margin-right: auto;"> <tr><td colspan="2">T 29 N</td></tr> <tr><td colspan="2">1/4</td></tr> <tr><td>R 27 E</td><td>R 28 E</td></tr> <tr><td>S 24</td><td>S 19</td></tr> </table>	T 29 N		1/4		R 27 E	R 28 E	S 24	S 19
T 29 N									
1/4									
R 27 E	R 28 E								
S 24	S 19								
	2003								
	Deposit a magnet, in a white plastic case, at the base of the stainless steel post.								
41.20	S. rim of mesa, top of sandstone ledge, bears ENE and WSW; thence descend over rugged and broken N. slope.								

**Survey of the East Boundary,
T. 29 N., R. 27 E., Gila and Salt River Meridian, Arizona**

CHAINS											
75.85	Wash, 12 ft. wide, 4 ft. deep, drains W.										
80.00	Point for the cor. of secs. 13, 18, 19, and 24. Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd. <div style="text-align: center;"> <table style="margin: auto;"> <tr><td colspan="2">T 29 N</td></tr> <tr><td>R 27 E</td><td> R 28 E</td></tr> <tr><td>S 13</td><td> S 18</td></tr> <tr><td colspan="2"><hr style="width: 50%; margin: 0 auto;"/></td></tr> <tr><td>S 24</td><td> S 19</td></tr> </table> <p>2003</p> </div> Deposit a magnet, in a white plastic case, at the base of the stainless steel post. Land, rolling to rugged and broken. Soil, sandy and rocky clay with sandstone outcrops. Timber, piñon, juniper, and Gambel oak; undergrowth, brush and native grasses.	T 29 N		R 27 E	R 28 E	S 13	S 18	<hr style="width: 50%; margin: 0 auto;"/>		S 24	S 19
T 29 N											
R 27 E	R 28 E										
S 13	S 18										
<hr style="width: 50%; margin: 0 auto;"/>											
S 24	S 19										
	<hr/> North, bet. secs. 13 and 18. Over rugged and broken land; descend the N. slope of mesa.										
40.00	Point for the 1/4 sec. cor. of secs. 13 and 18. Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd. <div style="text-align: center;"> <table style="margin: auto;"> <tr><td colspan="2">T 29 N</td></tr> <tr><td colspan="2">1/4</td></tr> <tr><td>R 27 E</td><td> R 28 E</td></tr> <tr><td>S 13</td><td> S 18</td></tr> </table> <p>2003</p> </div> Deposit a magnet, in a white plastic case, at the base of the stainless steel post.	T 29 N		1/4		R 27 E	R 28 E	S 13	S 18		
T 29 N											
1/4											
R 27 E	R 28 E										
S 13	S 18										
40.90	S. rim of the Nazlini Creek Canyon, top of sandstone ledge, bears ENE and WSW; thence descend abruptly into the canyon.										
55.25	Nazlini Creek, 70 ft. wide, 25 ft. deep, drains WNW, at bottom of the canyon; thence ascend out of the canyon.										
79.45	N. rim of the Nazlini Creek Canyon, top of sandstone ledge, bears E. and W.										
80.00	Point for the cor. of secs. 7, 12, 13, and 18.										

**Survey of the East Boundary,
T. 29 N., R. 27 E., Gila and Salt River Meridian, Arizona**

CHAINS									
	<p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 19 ins. in sandstone bedrock, in a mound of stone, 3 ft. base, to top, with brass cap mkd.</p> <div style="text-align: center;"> <table style="margin: auto;"> <tr><td colspan="2">T 29 N</td></tr> <tr><td>R 27 E</td><td>R 28 E</td></tr> <tr><td>S 12</td><td>S 7</td></tr> <tr style="border-top: 1px solid black;"><td>S 13</td><td>S 18</td></tr> </table> <p>2003</p> </div> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p> <p>Land, rugged and broken. Soil, sandy and rocky clay with sandstone outcrops. Timber, piñon and juniper; undergrowth, brush and native grasses.</p> <hr/> <p>North, bet. secs. 7 and 12.</p> <p>Over rolling land.</p>	T 29 N		R 27 E	R 28 E	S 12	S 7	S 13	S 18
T 29 N									
R 27 E	R 28 E								
S 12	S 7								
S 13	S 18								
40.00	<p>Point for the 1/4 sec. cor. of secs. 7 and 12.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center;"> <table style="margin: auto;"> <tr><td colspan="2">T 29 N</td></tr> <tr><td colspan="2">1/4</td></tr> <tr><td>R 27 E</td><td>R 28 E</td></tr> <tr><td>S 12</td><td>S 7</td></tr> </table> <p>2003</p> </div> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p>	T 29 N		1/4		R 27 E	R 28 E	S 12	S 7
T 29 N									
1/4									
R 27 E	R 28 E								
S 12	S 7								
80.00	<p>Point for the cor. of secs. 1, 6, 7, and 12.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center;"> <table style="margin: auto;"> <tr><td colspan="2">T 29 N</td></tr> <tr><td>R 27 E</td><td>R 28 E</td></tr> <tr><td>S 1</td><td>S 6</td></tr> <tr style="border-top: 1px solid black;"><td>S 12</td><td>S 7</td></tr> </table> <p>2003</p> </div>	T 29 N		R 27 E	R 28 E	S 1	S 6	S 12	S 7
T 29 N									
R 27 E	R 28 E								
S 1	S 6								
S 12	S 7								

**Survey of the East Boundary,
T. 29 N., R. 27 E., Gila and Salt River Meridian, Arizona**

CHAINS	
	<p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p> <p>Land, rolling. Soil, sandy and rocky clay. Timber, piñon and juniper; undergrowth, brush and native grasses.</p> <hr/> <p>North, bet. secs. 1 and 6.</p> <p>Over rolling land; ascend the S. slope of Rock Mesa.</p>
38.65	S. rim of Rock Mesa, top of sandstone ledge, bears E. and W.
40.00	Point for the 1/4 sec. cor. of secs. 1 and 6.
	<p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 20 ins. in the ground, in a mound of stone, 3 ft. base, to top, with brass cap mkd.</p> <div style="text-align: center;"> <p>T 29 N 1/4 R 27 E R 28 E S 1 S 6</p> <p>2003</p> </div>
41.30	<p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p> <p>N. rim of Rock Mesa, top of sandstone ledge, bears SE and NW; thence descend over rugged and broken N. slope.</p>
80.00	<p>Point for the cor. of Tps. 29 and 30 N., Rs. 27 and 28 E.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center;"> <p>T 30 N R 27 E R 28 E S 36 S 31 S 1 S 6 T 29 N</p> <p>2003</p> </div>
	<p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p> <p>Cor. is located 45 lks. SE of a wash, 10 ft. wide, 5 ft. deep, drains SW.</p>

**Survey of the East Boundary,
T. 29 N., R. 27 E., Gila and Salt River Meridian, Arizona**

CHAINS	<p>Land, rolling to rugged and broken. Soil, sandy and rocky clay. Timber, piñon and juniper; undergrowth, brush and native grasses.</p> <hr/> <p align="center">Survey of the North Boundary, T. 29 N., R. 27 E., Gila and Salt River Meridian</p> <hr/> <p>From the cor. of Tps. 29 and 30 N., Rs. 27 and 28 E., hereinbefore described.</p> <p>West, bet. secs. 1 and 36.</p> <p>Over rolling and broken land.</p>
40.00	<p>Point for the 1/4 sec. cor. of secs. 1 and 36.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p align="center"> T 30 N R 27 E S 36 1/4 ——— S 1 T 29 N 2003 </p> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p>
45.95	<p>Trail road, bears NNE and SSW.</p>
80.00	<p>Point for the cor. of secs. 1, 2, 35, and 36.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p align="center"> T 30 N R 27 E S 35 S 36 ——— ——— S 2 S 1 T 29 N 2003 </p> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p>

**Survey of the North Boundary,
T. 29 N., R. 27 E., Gila and Salt River Meridian, Arizona**

CHAINS	
	<p>Land, rolling and broken. Soil, sandy and gravelly clay. Timber, piñon and juniper; undergrowth, brush and native grasses.</p> <hr/> <p>West, bet. secs. 2 and 35.</p> <p>Over rolling land.</p>
28.85	Trail road, bears SE and NW.
40.00	<p>Point for the 1/4 sec. cor. of secs. 2 and 35.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T 30 N R 27 E S 35 1/4 ——— S 2 T 29 N</p> <p style="text-align: center;">2003</p> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p>
47.95	Trail road, bears SE and NW.
75.95	W. rim of mesa, top of sandstone ledge, bears N. and S.; thence descend over rugged and broken W. slope.
80.00	<p>Point for the cor. of secs. 2, 3, 34, and 35.</p> <p>Set a brass tablet, 3 1/4 ins. diam., 2 1/2 ins. stem, cemented in a drill hole, in sandstone outcrop, with top mkd.</p> <p style="text-align: center;">T 30 N R 27 E S 34 S 35 S 3 S 2 T 29 N</p> <p style="text-align: center;">2003</p> <p>Deposit a magnet, in a white plastic case, at the base of the brass tablet.</p>

**Survey of the North Boundary,
T. 29 N., R. 27 E., Gila and Salt River Meridian, Arizona**

CHAINS	
	<p>Land, rolling to rugged and broken. Soil, sandy and rocky clay with sandstone outcrops. Timber, piñon and juniper; undergrowth, brush and native grasses.</p> <hr/> <p>West, bet. secs. 3 and 34.</p> <p>Over rugged and broken land; descend over W. slope of mesa.</p>
40.00	<p>Point for the 1/4 sec. cor. of secs. 3 and 34.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T 30 N R 27 E S 34 1/4 ——— S 3 T 29 N</p> <p style="text-align: center;">2003</p> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p> <p>Cor. is located W. of the base of the W. slope of mesa, thence over rolling land.</p>
45.80	<p>Trail road, bears NE and SW.</p>
80.00	<p>Point for the cor. of secs. 3, 4, 33, and 34.</p> <p>Set a brass tablet, 3 1/4 ins. diam., 2 1/2 ins. stem, cemented in a drill hole, in sandstone bedrock, with top mkd.</p> <p style="text-align: center;">T 30 N R 27 E S 33 S 34 S 4 S 3 T 29 N</p> <p style="text-align: center;">2003</p> <p>Deposit a magnet, in a white plastic case, at the base of the brass tablet.</p> <p>Cor. is located on E. rim of sandstone cove, 30 ft. high, bears N. and S.</p>

**Survey of the North Boundary,
T. 29 N., R. 27 E., Gila and Salt River Meridian, Arizona**

CHAINS	
	<p>Land, rugged and broken to rolling. Soil, sandy and rocky clay with sandstone outcrops. Timber, scattered piñon and juniper; undergrowth, brush and native grasses.</p> <hr/> <p>West, bet. secs. 4 and 33.</p> <p>Over rolling and broken land.</p>
3.90	W. rim of sandstone cove, 30 ft. high, bears N. and S.
38.15	Wash, 20 ft. wide, 7 ft. deep, drains WSW.
40.00	Point for the 1/4 sec. cor. of secs. 4 and 33.
	<p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;"> T 30 N R 27 E S 33 1/4 ——— S 4 T 29 N 2003 </p> <p>from which</p> <p style="text-align: center;"> The SW cor. of a L-shaped stucco house, bears N. 0° 30' E., 1.37 chs. dist.; sides bear N 32° E and N 58° W. </p> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p> <p>Cor. is located 20 lks. SE of a trail road, bears NNE and SSW.</p>
57.00	Navajo Route 8015, a graded road, 20 ft. wide, bears SSE and NNW.
80.00	Point for the cor. of secs. 4, 5, 32, and 33.
	<p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;"> T 30 N R 27 E S 32 S 33 S 5 S 4 T 29 N 2003 </p>

**Survey of the North Boundary,
T. 29 N., R. 27 E., Gila and Salt River Meridian, Arizona**

CHAINS	
	<p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p> <p>Land, rolling and broken. Soil, sandy and gravelly clay. Timber, scattered piñon and juniper; undergrowth, brush and native grasses.</p> <hr/> <p>West, bet. secs. 5 and 32.</p> <p>Over rolling land.</p>
40.00	<p>Point for the 1/4 sec. cor. of secs. 5 and 32.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T 30 N R 27 E S 32 1/4 ——— S 5 T 29 N</p> <p style="text-align: center;">2003</p> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p>
80.00	<p>Point for the cor. of secs. 5, 6, 31, and 32.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T 30 N R 27 E S 31 S 32 S 6 S 5 T 29 N</p> <p style="text-align: center;">2003</p> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p> <p>Land, rolling. Soil, sandy and gravelly clay. Timber, scattered piñon and juniper; undergrowth, brush and native grasses.</p> <hr/> <p>West, bet. secs. 6 and 31.</p>

**Survey of the North Boundary,
T. 29 N., R. 27 E., Gila and Salt River Meridian, Arizona**

CHAINS	<p>Over rolling land.</p>
40.00	<p>Point for the 1/4 sec. cor. of secs. 6 and 31.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 20 ins. in the ground, in a mound of stone, 3 ft. base, to top, with brass cap mkd.</p> <p style="text-align: center;">T 30 N R 27 E S 31 1/4 ——— S 6 T 29 N</p> <p style="text-align: center;">2003</p>
79.00	<p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p> <p>True point for the cor. of Tps. 29 and 30 N., Rs. 26 and 27 E., is determined at record bearing and dist., from a witness cor.</p> <p style="padding-left: 40px;">A stainless steel post, 2 1/2 ins. diam., firmly set, projecting 4 ins. above ground, bears South, 3.00 chs. dist., with brass cap mkd. WC T30N R26E R27E S36 S31 S1 S6 T29N 1991 and an arrow pointing to the Tp. cor.</p> <p style="padding-left: 40px;">Add the marks 2003 to the brass cap.</p> <p style="padding-left: 40px;">Witness cor. is located 30 lks. S. of S. rim of Nazlini Creek Canyon, bears ENE and WSW.</p> <p>True point falls on vertical sandstone cliff, the N. wall of Nazlini Creek Canyon, bears ENE and WSW.</p> <p>From the true point of Tp. cor., the 1/4 sec. cor. of secs. 1 and 36, Tps. 29 and 30 N., R. 26 E., bears West, 40.00 chs. dist., monumented with a stainless steel post, 2 1/2 ins. diam., firmly set, projecting 5 ins. above ground, with brass cap mkd. T30N R26E S36 S1 T29N 1991.</p> <p>From the true point of Tp. cor., the 1/4 sec. cor. of secs. 31 and 36, Tps. 30 N., Rs. 26 and 27 E., bears North, 40.00 chs. dist., monumented with a stainless steel post, 2 1/2 ins. diam., firmly set, projecting 10 ins. above ground, with brass cap mkd. T30N R26E R27E S36 S31 1991.</p> <p>Land, rolling. Soil, sandy and gravelly clay. Timber, scattered piñon and juniper; undergrowth, brush and native grasses.</p> <hr style="width: 60%; margin-left: 0;"/>

**Survey of the Subdivisional Lines,
T. 29 N., R. 27 E., Gila and Salt River Meridian, Arizona**

CHAINS	<p>From the stan. cor. of secs. 35 and 36, on the S. bdy. of the Tp., hereinbefore described.</p> <p>N. 0°01' W., bet. secs. 35 and 36.</p> <p>Over rolling land.</p>
40.00	<p>Point for the 1/4 sec. cor. of secs. 35 and 36.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p align="center">T 29 N R 27 E 1/4 S 35 S 36</p> <p align="center">2003</p> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p>
68.60	<p>N. rim of mesa, top of sandstone ledge, bears ENE and WSW; thence descend over rugged and broken N. slope.</p>
80.00	<p>Point for the cor. of secs. 25, 26, 35, and 36.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p align="center">T 29 N R 27 E S 26 S 25 S 35 S 36</p> <p align="center">2003</p> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p> <p>Land, rolling to rugged and broken. Soil, sandy and rocky clay. Timber, piñon and juniper; undergrowth, brush and native grasses.</p> <hr/> <p>From the cor. of secs. 25, 30, 31, and 36, on the E. bdy. of the Tp., hereinbefore described.</p> <p>West, bet. secs. 25 and 36.</p> <p>Over rugged and broken land.</p>
40.00	<p>Point for the 1/4 sec. cor. of secs. 25 and 36.</p>

**Survey of the Subdivisional Lines,
T. 29 N., R. 27 E., Gila and Salt River Meridian, Arizona**

CHAINS	
	<p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T 29 N R 27 E S 25 1/4 ——— S 36</p> <p style="text-align: center;">2003</p> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p>
80.00	<p>The cor. of secs. 25, 26, 35, and 36.</p> <p>Land, rolling and broken. Soil, sandy and rocky clay. Timber, piñon and juniper; undergrowth, brush and native grasses.</p> <hr/> <p>N. 0°01' W., bet. secs. 25 and 26.</p> <p>Over rolling and broken land.</p>
25.45	S. rim of a rocky draw, top of sandstone ledge, bears ENE and WSW.
28.95	N. rim of the same rocky draw, top of sandstone ledge, bears E. and W.
40.00	<p>Point for the 1/4 sec. cor. of secs. 25 and 26.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T 29 N R 27 E 1/4 S 26 S 25</p> <p style="text-align: center;">2003</p> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p>
80.00	<p>Point for the cor. of secs. 23, 24, 25, and 26.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p>

**Survey of the Subdivisional Lines,
T. 29 N., R. 27 E., Gila and Salt River Meridian, Arizona**

CHAINS	
	T 29 N R 27 E S 23 S 24 S 26 S 25 2003
	Deposit a magnet, in a white plastic case, at the base of the stainless steel post. Land, rolling and broken. Soil, sandy and rocky clay. Timber, scattered piñon and juniper; undergrowth, brush and native grasses.
	<hr/> From the cor. of secs. 19, 24, 25, and 30, on the E. bdy. of the Tp., hereinbefore described. West, bet. secs. 24 and 25. Over rolling land.
40.00	Point for the 1/4 sec. cor. of secs. 24 and 25. Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.
	T 29 N R 27 E S 24 1/4 ——— S 25 2003
68.10	Deposit a magnet, in a white plastic case, at the base of the stainless steel post. W. rim of mesa, top of sandstone ledge, bears ENE and WSW; thence descend over W. slope of mesa.
80.00	The cor. of secs. 23, 24, 25, and 26. Land, rolling to rugged and broken. Soil, sandy and rocky clay. Timber, piñon and juniper; undergrowth, brush and native grasses.
	<hr/> N. 0°01' W., bet. secs. 23 and 24. Over rolling and broken land.

**Survey of the Subdivisional Lines,
T. 29 N., R. 27 E., Gila and Salt River Meridian, Arizona**

CHAINS	
40.00	<p>Point for the 1/4 sec. cor. of secs. 23 and 24.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T 29 N R 27 E 1/4 S 23 S 24</p> <p style="text-align: center;">2003</p> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p>
80.00	<p>Point for the cor. of secs. 13, 14, 23, and 24.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T 29 N R 27 E S 14 S 13 S 23 S 24</p> <p style="text-align: center;">2003</p> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p> <p>Land, rolling. Soil, sandy and gravelly clay. Timber, piñon and juniper; undergrowth, brush and native grasses.</p> <hr/> <p>From the cor of secs. 13, 18, 19, and 24, on the E. bdy of the Tp., hereinbefore described.</p> <p>West, bet. secs. 13 and 24.</p> <p>Over rolling and broken land.</p>
4.25	<p>Wash, 12 ft. wide, 4 ft. deep, drains NW.</p>
40.00	<p>Point for the 1/4 sec. cor. of secs. 13 and 24.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p>

**Survey of the Subdivisional Lines,
T. 29 N., R. 27 E., Gila and Salt River Meridian, Arizona**

CHAINS	
	T 29 N R 27 E S 13 1/4 ——— S 24 2003
	Deposit a magnet, in a white plastic case, at the base of the stainless steel post.
80.00	The cor. of secs. 13, 14, 23, and 24. Land, rolling and broken. Soil, sandy and rocky clay. Timber, piñon and juniper; undergrowth, brush and native grasses.
	N. 0°01' W., bet. secs. 13 and 14.
	Over rolling and broken land.
5.40	S. rim of Nazlini Creek Canyon, top of sandstone ledge, bears ESE and WNW, thence across the canyon.
31.40	N. rim of Nazlini Creek Canyon, top of sandstone ledge, bears ESE and WNW.
40.00	Point for the 1/4 sec. cor. of secs. 13 and 14. Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.
	T 29 N R 27 E 1/4 S 14 S 13 2003
	Deposit a magnet, in a white plastic case, at the base of the stainless steel post.
80.00	Point for the cor. of secs. 11, 12, 13, and 14. Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.
	T 29 N R 27 E S 11 S 12 S 14 S 13 2003

**Survey of the Subdivisional Lines,
T. 29 N., R. 27 E., Gila and Salt River Meridian, Arizona**

CHAINS	
	<p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p> <p>Land, rolling and broken. Soil, sandy and rocky clay. Timber, piñon and juniper; undergrowth, brush and native grasses.</p> <hr/> <p>From the cor. of secs. 7, 12, 13, and 18, on the E. bdy. of the Tp., hereinbefore described.</p> <p>West, bet. secs. 12 and 13.</p> <p>Over rolling land.</p>
40.00	<p>Point for the 1/4 sec. cor. of secs. 12 and 13.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T 29 N R 27 E S 12 1/4 ——— S 13 2003</p>
80.00	<p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p> <p>The cor. of secs. 11, 12, 13, and 14.</p> <p>Land, rolling. Soil, sandy and rocky clay. Timber, piñon and juniper; undergrowth, brush and native grasses.</p> <hr/> <p>N. 0°01' W., bet. secs. 11 and 12.</p> <p>Over rolling land.</p>
40.00	<p>Point for the 1/4 sec. cor. of secs. 11 and 12.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T 29 N R 27 E 1/4 S 11 S 12 2003</p>

**Survey of the Subdivisional Lines,
T. 29 N., R. 27 E., Gila and Salt River Meridian, Arizona**

CHAINS	<p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p>																
80.00	<p>Point for the cor. of secs. 1, 2, 11, and 12.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center; margin: 10px 0;"> <table style="margin: auto; border-collapse: collapse;"> <tr> <td colspan="2">T 29 N</td> <td colspan="2">R 27 E</td> </tr> <tr> <td style="border-right: 1px solid black; padding: 0 5px;">S 2</td> <td style="padding: 0 5px;"> </td> <td style="padding: 0 5px;">S 1</td> <td></td> </tr> <tr> <td style="border-right: 1px solid black; padding: 0 5px;">S 11</td> <td style="padding: 0 5px;"> </td> <td style="padding: 0 5px;">S 12</td> <td></td> </tr> </table> </div> <p align="center">2003</p> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p> <p>Land, rolling. Soil, sandy clay. Timber, piñon and juniper; undergrowth, brush and native grasses.</p> <hr style="width: 80%; margin: 10px auto;"/> <p>From the cor. of secs. 1, 6, 7, and 12, on the E. bdy. of the Tp., hereinbefore described.</p> <p>West, bet. secs. 1 and 12.</p>	T 29 N		R 27 E		S 2		S 1		S 11		S 12					
T 29 N		R 27 E															
S 2		S 1															
S 11		S 12															
31.10	<p>Top of Pillow Mountain ridge, bears N. and S.</p>																
40.00	<p>Point for the 1/4 sec. cor. of secs. 1 and 12.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center; margin: 10px 0;"> <table style="margin: auto; border-collapse: collapse;"> <tr> <td colspan="2">T 29 N</td> <td colspan="2">R 27 E</td> </tr> <tr> <td colspan="2"></td> <td colspan="2">S 1</td> </tr> <tr> <td colspan="2"></td> <td colspan="2">1/4 ———</td> </tr> <tr> <td colspan="2"></td> <td colspan="2">S 12</td> </tr> </table> </div> <p align="center">2003</p> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p>	T 29 N		R 27 E				S 1				1/4 ———				S 12	
T 29 N		R 27 E															
		S 1															
		1/4 ———															
		S 12															
80.00	<p>The cor. of secs. 1, 2, 11, and 12.</p> <p>Land, rolling. Soil, sandy and rocky clay. Timber, piñon and juniper; undergrowth, brush and native grasses.</p> <hr style="width: 80%; margin: 10px auto;"/>																

**Survey of the Subdivisional Lines,
T. 29 N., R. 27 E., Gila and Salt River Meridian, Arizona**

CHAINS	
	N. 0°01' W., bet. secs. 1 and 2. Over rolling land.
40.00	Point for the 1/4 sec. cor. of secs. 1 and 2. Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd. <div style="text-align: center;"> T 29 N R 27 E 1/4 S 2 S 1 2003 </div>
	Deposit a magnet, in a white plastic case, at the base of the stainless steel post.
52.15	Trail road, bears ENE and WSW.
63.95	Trail road, bears ESE and WNW.
80.00	The cor. of secs. 1, 2, 35, and 36, on the N. bdy. of the Tp., hereinbefore described. Land, rolling. Soil, sandy and gravelly clay. Timber, piñon and juniper; undergrowth and native grasses.
	From the stan. cor. of secs. 34 and 35, on the S. bdy. of the Tp., hereinbefore described. N. 0°01' W., bet. secs. 34 and 35. Over rolling and broken land.
3.81	Barbed wire fence, 5 strand, bears SE and NW.
3.96	Power line, bears SE and NW.
4.70	Underground gas pipeline, bears SE and NW.
8.65	S. right-of-way fence of Navajo Route 27, barbed wire, 5 strand, parallels the highway.
10.95	Navajo Route 27, asphalt pavement, 32 ft. wide, bears SE and NW.
13.40	N. right-of-way fence of Navajo Route 27, barbed wire, 5 strand, parallels the highway.
22.75	N. rim of mesa, top of sandstone ledge, bears ESE and WNW; thence descend over N. slope of mesa.

**Survey of the Subdivisional Lines,
T. 29 N., R. 27 E., Gila and Salt River Meridian, Arizona**

CHAINS	
40.00	<p>Point for the 1/4 sec. cor. of secs. 34 and 35.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T 29 N R 27 E 1/4 S 34 S 35</p> <p style="text-align: center;">2003</p> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p>
75.25	<p>Wash, 35 ft. wide, 3 ft. deep, drains NW.</p>
80.00	<p>Point for the cor. of secs. 26, 27, 34, and 35.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T 29 N R 27 E S 27 S 26 S 34 S 35</p> <p style="text-align: center;">2003</p> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p> <p>Land, rolling to rugged and broken. Soil, sandy and rocky clay. Timber, piñon and juniper; undergrowth, brush and native grasses.</p> <hr/> <p>From the cor. of secs. 25, 26, 35, and 36.</p> <p>West, bet. secs. 26 and 35.</p> <p>Over rugged and broken land.</p>
40.00	<p>Point for the 1/4 sec. cor. of secs. 26 and 35.</p> <p>Set a brass tablet, 3 1/4 ins. diam., 2 1/2 ins. stem, cemented in a drill hole, in sandstone outcrop, with top mkd.</p>


**Survey of the Subdivisional Lines,
T. 29 N., R. 27 E., Gila and Salt River Meridian, Arizona**

CHAINS	
	T 29 N R 27 E S 26 1/4 ——— S 35 2003
	Deposit a magnet, in a white plastic case, at the base of the brass tablet.
80.00	The cor. of secs. 26, 27, 34, and 35. Land, rugged and broken. Soil, sandy and rocky clay. Timber, piñon and juniper; undergrowth, brush and native grasses.
	<hr/> N. 0°01' W., bet. secs. 26 and 27. Over rolling and broken land.
40.00	Point for the 1/4 sec. cor. of secs. 26 and 27. Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 18 ins. in sandstone bedrock, in a mound of stone, 3 ft. base, to top, with brass cap mkd.
	T 29 N R 27 E 1/4 S 27 S 26 2003
	Deposit a magnet, in a white plastic case, at the base of the stainless steel post.
80.00	True point for the cor. of secs. 22, 23, 26, and 27; falls on inaccessible sandstone cliff, 40 ft. high, where it is impracticable to establish a permanent monument. From this true point, the point selected for a witness cor. to the cor. of secs. 22, 23, 26, and 27, bears N. 45°00' W., 1.00 ch. dist. Set a brass tablet, 3 1/4 ins. diam., 2 1/2 ins. stem, cemented in a drill hole, in sandstone bedrock, with top mkd.

**Survey of the Subdivisional Lines,
T. 29 N., R. 27 E., Gila and Salt River Meridian, Arizona**

CHAINS	
	WC T 29 N R 27 E S 22 S 23 S 27 S 26 2003 ↘
	Deposit a magnet, in a white plastic case, at the base of the brass tablet.
	Land, rugged and broken. Soil, sandy and rocky clay with sandstone outcrops. Timber, piñon and juniper; undergrowth, brush and native grasses.
	<hr/> From the cor. of secs. 23, 24, 25, and 26. West, bet. secs. 23 and 26. Over rolling land.
40.00	Point for the 1/4 sec. cor. of secs. 23 and 26. Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 18 ins. in sandstone bedrock, in a mound of stone, 3 ft. base, to top, with brass cap mkd.
	T 29 N R 27 E S 23 1/4 ——— S 26 2003
	Deposit a magnet, in a white plastic case, at the base of the stainless steel post.
80.00	The cor. of secs. 22, 23, 26, and 27. Land, rolling and broken. Soil, sandy and rocky clay with sandstone outcrops. Timber, piñon and juniper; undergrowth, brush and native grasses.
	<hr/> N. 0°01' W., bet. secs. 22 and 23. Over rugged and broken land.
26.00	S. rim of Nazlini Creek Canyon, top of sandstone ledge, bears NE and SW; thence descend abruptly into the canyon.

Survey of the Subdivisional Lines,
T. 29 N., R. 27 E., Gila and Salt River Meridian, Arizona

CHAINS	
30.25	Trail road, bears ENE and WSW, at the base of the S. slope of canyon.
31.45	Nazlini Creek, 40 ft. wide, 3 ft. deep, drains W.
37.15	Base of the N. slope of the Nazlini Creek Canyon, bears ENE and WSW; thence ascend abruptly out of the canyon.
40.00	<p>True point for the 1/4 sec. cor. of secs. 22 and 23; falls on inaccessible sandstone cliff, 40 ft. high, where it is impracticable to establish a permanent monument.</p> <p>From this true point, the point selected for a witness cor. to the 1/4 sec. cor. of secs. 22 and 23, bears S. 20°00' W., 1.50 chs. dist.</p> <p>Set a brass tablet, 3 1/4 ins. diam., 2 1/2 ins. stem, cemented in a drill hole, in sandstone bedrock, with top mkd.</p> <div style="text-align: center;">  <p>T 29 N R 27 E 1/4 S 22 S 23</p> </div> <p style="text-align: center;">2003</p> <p>Deposit a magnet, in a white plastic case, at the base of the brass tablet.</p>
47.50	N. rim of Nazlini Creek Canyon, top of sandstone ledge, bears E. and W., thence over rolling land.
80.00	<p>Point for the cor. of secs. 14, 15, 22, and 23.</p> <p>Set a brass tablet, 3 1/4 ins. diam., 2 1/2 ins. stem, cemented in a drill hole, in sandstone outcrop, with top mkd.</p> <div style="text-align: center;"> <p>T 29 N R 27 E S 15 S 14 S 22 S 23</p> </div> <p style="text-align: center;">2003</p> <p>Deposit a magnet, in a white plastic case, at the base of the brass tablet.</p> <p>Land, rugged and broken to rolling. Soil, sandy and rocky clay with sandstone outcrops. Timber, scattered piñon and juniper; undergrowth, brush and native grasses.</p> <hr style="width: 50%; margin-left: 0;"/>

**Survey of the Subdivisional Lines,
T. 29 N., R. 27 E., Gila and Salt River Meridian, Arizona**

CHAINS	
	<p>From the cor. of secs. 13, 14, 23, and 24.</p> <p>West, bet. secs. 14 and 23.</p> <p>Over rugged and broken land.</p>
2.60	S. rim of Nazlini Creek Canyon, top of sandstone ledge, bears NNE and SSW, thence across the canyon.
32.00	N. rim of Nazlini Creek Canyon, top of sandstone ledge, bears ENE and WSW.
40.00	<p>Point for the 1/4 sec. cor. of secs. 14 and 23.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 19 ins. in sandstone bedrock, in a mound of stone, 3 ft. base, to top, with brass cap mkd.</p> <div style="text-align: center;"> <p>T 29 N R 27 E</p> <p>S 14</p> <p>1/4 ———</p> <p>S 23</p> <p>2003</p> </div> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p>
80.00	<p>The cor. of secs. 14, 15, 22, and 23.</p> <p>Land, rugged and broken to rolling.</p> <p>Soil, sandy and rocky clay with sandstone outcrops.</p> <p>Timber, scattered piñon and juniper; undergrowth, brush and native grasses.</p> <hr/> <p>N. 0°01' W., bet. secs. 14 and 15.</p> <p>Over rolling land.</p>
40.00	<p>Point for the 1/4 sec. cor. of secs. 14 and 15.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center;"> <p>T 29 N R 27 E</p> <p>1/4</p> <p>S 15 S 14</p> <p>2003</p> </div> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p>

**Survey of the Subdivisional Lines,
T. 29 N., R. 27 E., Gila and Salt River Meridian, Arizona**

CHAINS							
80.00	<p>Point for the cor. of secs. 10, 11, 14, and 15.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <table style="margin-left: auto; margin-right: auto; border-collapse: collapse;"> <tr> <td style="padding: 0 10px;">T 29 N</td> <td style="padding: 0 10px;">R 27 E</td> </tr> <tr> <td style="border-right: 1px solid black; padding: 0 5px;">S 10</td> <td style="padding: 0 5px;">S 11</td> </tr> <tr> <td style="border-right: 1px solid black; padding: 0 5px;">S 15</td> <td style="padding: 0 5px;">S 14</td> </tr> </table> <p style="text-align: center;">2003</p> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p> <p>Cor. is located on N. side of a sandstone ledge, 3 ft. high, bears ENE and WSW.</p> <p>Land, rolling. Soil, sandy and rocky clay, with sandstone outcrops. Timber, piñon and juniper; undergrowth, brush and native grasses.</p> <hr style="width: 50%; margin-left: 0;"/> <p>From the cor. of secs. 11, 12, 13, and 14.</p> <p>West, bet. secs. 11 and 14.</p> <p>Over rolling land.</p>	T 29 N	R 27 E	S 10	S 11	S 15	S 14
T 29 N	R 27 E						
S 10	S 11						
S 15	S 14						
37.65	Trail road, bears NNE and SSW.						
40.00	<p>Point for the 1/4 sec. cor. of secs. 11 and 14.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <table style="margin-left: auto; margin-right: auto; border-collapse: collapse;"> <tr> <td style="padding: 0 10px;">T 29 N</td> <td style="padding: 0 10px;">R 27 E</td> </tr> <tr> <td></td> <td style="padding: 0 10px;">S 11</td> </tr> <tr> <td style="padding: 0 10px;">1/4</td> <td style="border-top: 1px solid black; padding: 0 10px;">S 14</td> </tr> </table> <p style="text-align: center;">2003</p> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p>	T 29 N	R 27 E		S 11	1/4	S 14
T 29 N	R 27 E						
	S 11						
1/4	S 14						
80.00	The cor. of secs. 10, 11, 14, and 15.						

**Survey of the Subdivisional Lines,
T. 29 N., R. 27 E., Gila and Salt River Meridian, Arizona**

CHAINS	
	<p>Land, rolling. Soil, sandy and rocky clay. Timber, piñon and juniper; undergrowth, brush and native grasses.</p> <hr/> <p>N. 0°01' W., bet. secs. 10 and 11.</p> <p>Over rugged and broken land.</p>
30.70	S. rim of a canyon, bears NE and SW, thence across the canyon.
39.00	N. rim of the same canyon, bears NE and SW.
40.00	Point for the 1/4 sec. cor. of secs. 10 and 11.
	<p>Set a brass tablet, 3 1/4 ins. diam., 2 1/2 ins. stem, cemented in a drill hole, in sandstone bedrock, with top mkd.</p> <p style="text-align: center;">T 29 N R 27 E 1/4 S 10 S 11 2003</p>
	<p>Deposit a magnet, in a white plastic case, at the base of the brass tablet.</p>
80.00	Point for the cor. of secs. 2, 3, 10, and 11.
	<p>Set a brass tablet, 3 1/4 ins. diam., 2 1/2 ins. stem, cemented in a drill hole, in sandstone outcrop, with top mkd.</p> <p style="text-align: center;">T 29 N R 27 E S 3 S 2 S 10 S 11 2003</p>
	<p>Deposit a magnet, in a white plastic case, at the base of the brass tablet.</p>
	<p>Land, rugged and broken. Soil, sandy and rocky clay with sandstone outcrops. Timber, piñon and juniper; undergrowth, brush and native grasses.</p> <hr/> <p>From the cor. of secs. 1, 2, 11, and 12.</p> <p>West, bet. secs. 2 and 11.</p>

**Survey of the Subdivisional Lines,
T. 29 N., R. 27 E., Gila and Salt River Meridian, Arizona**

CHAINS	
	Over rolling land.
15.45	Trail road, bears N. and S.
40.00	Point for the 1/4 sec. cor. of secs. 2 and 11. Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.
	T 29 N R 27 E S 2 1/4 ——— S 11 2003
	Deposit a magnet, in a white plastic case, at the base of the stainless steel post.
60.30	W. rim of mesa, top of sandstone ledge, bears SSE and NNW; thence descend over rugged and broken W. slope of mesa.
80.00	The cor. of secs. 2, 3, 10, and 11. Land, rolling to rugged and broken. Soil, sandy and rocky clay with sandstone outcrops. Timber, piñon and juniper; undergrowth, brush and native grasses.
	————— N. 0°01' W., bet. secs. 2 and 3.
	Over rugged and broken land.
31.85	S. rim of a canyon, top of sandstone cliff, bears SE and NW, thence across the canyon.
40.00	Point for the 1/4 sec. cor. of secs. 2 and 3. Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 22 ins. in the ground, to sandstone bedrock, with brass cap mkd.
	T 29 N R 27 E 1/4 S 3 S 2 2003
	Deposit a magnet, in a white plastic case, at the base of the stainless steel post.
40.75	N. rim of the same canyon, top of sandstone ledge, bears E. and W.

**Survey of the Subdivisional Lines,
T. 29 N., R. 27 E., Gila and Salt River Meridian, Arizona**

CHAINS	
80.00	<p>The cor. of secs. 2, 3, 34, and 35, on the N. bdy. of the Tp., hereinbefore described.</p> <p>Land, rugged and broken. Soil, sandy and rocky clay with sandstone outcrops. Timber, piñon and juniper; undergrowth, brush and native grasses.</p> <hr/> <p>From the stan. cor. of secs. 33 and 34, on the S. bdy. of the Tp., hereinbefore described.</p> <p>N. 0°02' W., bet. secs. 33 and 34.</p> <p>Over rugged and broken land; descend the NW slope of mesa.</p>
40.00	<p>Point for the 1/4 sec. cor. of secs. 33 and 34.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T 29 N R 27 E 1/4 S 33 S 34 2003</p> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p>
40.13	<p>S. right-of-way fence of Navajo Route 27, barbed wire, 5 strand, parallels the highway.</p>
41.88	<p>Navajo Route 27, asphalt pavement, 32 ft. wide, bears ENE and WSW.</p>
43.65	<p>N. right-of-way fence of Navajo Route 27, barbed wire, 5 strand, parallels the highway.</p>
80.00	<p>Point for the cor. of secs. 27, 28, 33, and 34.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T 29 N R 27 E S 28 S 27 S 33 S 34 2003</p> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p>

**Survey of the Subdivisional Lines,
T. 29 N., R. 27 E., Gila and Salt River Meridian, Arizona**

CHAINS	
	<p>Land, rugged and broken. Soil, sandy and rocky clay. Timber, piñon and juniper; undergrowth, brush and native grasses.</p> <hr/> <p>From the cor. of secs. 26, 27, 34, and 35.</p> <p>West, bet. secs. 27 and 34.</p> <p>Over rugged and broken land.</p>
3.75	Wash, 35 ft. wide, 3 ft. deep, drains NNW; thence ascend over the N. slope of mesa.
39.75	E. rim of a mesa, top of sandstone ledge, bears SSE and NNW.
40.00	Point for the 1/4 sec. cor. of secs. 27 and 34.
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 23 ins. in sandstone bedrock, with brass cap mkd.
	<p>T 29 N R 27 E S 27 1/4 ——— S 34</p> <p>2003</p>
	Deposit a magnet, in a white plastic case, at the base of the stainless steel post.
51.00	W. rim of the same mesa, top of sandstone ledge, bears NE and SW; thence descend over NW slope of mesa.
69.81	Power line, bears SE and NW.
71.08	Underground gas pipeline, bears SE and NW.
80.00	The cor. of secs. 27, 28, 33, and 34.
	<p>Land, rugged and broken. Soil, sandy and rocky clay with sandstone outcrops. Timber, piñon and juniper; undergrowth, brush and native grasses.</p> <hr/> <p>N. 0°02' W., bet. secs. 27 and 28.</p> <p>Over rugged and broken land; continuing descent over N. slope of mesa.</p>
31.21	Underground gas pipeline, bears SSE and NNW.

**Survey of the Subdivisional Lines,
T. 29 N., R. 27 E., Gila and Salt River Meridian, Arizona**

CHAINS	
32.09	Power line, bears SSE and NNW.
35.05	Wash, 20 ft. wide, 3 ft. deep, drains NNW.
40.00	Point for the 1/4 sec. cor. of secs. 27 and 28. Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd. <div style="text-align: center;"> T 29 N R 27 E 1/4 S 28 S 27 2003 </div> Deposit a magnet, in a white plastic case, at the base of the stainless steel post. Cor. is located at base of the N. slope of mesa.
41.75	Wash, 15 ft. wide, 3 ft. deep, drains SSW.
61.40	Graded road, 15 ft. wide, bears ENE and WSW.
80.00	Point for the cor. of secs. 21, 22, 27, and 28. Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 20 ins. in the ground, to sandstone bedrock, in a mound of stone, 3 ft. base, to top, with brass cap mkd. <div style="text-align: center;"> T 29 N R 27 E S 21 S 22 S 28 S 27 2003 </div> Deposit a magnet, in a white plastic case, at the base of the stainless steel post. Land, rugged and broken. Soil, sandy and rocky clay. Timber, scattered piñon and juniper; undergrowth, brush and native grasses.
	<hr/> From the true point of the cor. of secs. 22, 23, 26, and 27. West, bet. secs. 22 and 27. Over rugged and broken land.

**Survey of the Subdivisional Lines,
T. 29 N., R. 27 E., Gila and Salt River Meridian, Arizona**

CHAINS	
34.95	S. rim of Nazlini Creek Canyon, top of sandstone cliff, bears NNE and SSW, thence descend into the canyon.
35.80	E. bank of Nazlini Creek, 6 ft. high, bears NNE and SSW.
36.95	Nazlini Creek, 40 ft. wide, 3 ft. deep, on a curve, drains W.
39.65	W. bank of Nazlini Creek, 4 ft. high, bears ESE and WNW.
40.00	Point for the 1/4 sec. cor. of secs. 22 and 27. Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd. <div style="text-align: center;"> T 29 N R 27 E S 22 1/4 ——— S 27 2003 </div> from which <div style="text-align: center;"> The marks, X BO, chiseled on the N. face of a sandstone cliff, 20 ft. high, bears S. 30° W., 1.375 chs. dist. </div> Deposit a magnet, in a white plastic case, at the base of the stainless steel post.
43.50	SW rim of Nazlini Creek Canyon, top of sandstone ledge, bears N. and S., thence over rolling land.
80.00	The cor. of secs. 21, 22, 27, and 28. Land, rugged and broken to rolling. Soil, sandy and rocky clay with sandstone outcrops. Timber, scattered piñon and juniper; undergrowth, brush and native grasses. <hr/> N. 0°02' W., bet. secs. 21 and 22. Over rolling and broken land.
12.20	S. rim of the Nazlini Creek Canyon, top of sandstone cliff, bears E. and W.
14.20	Nazlini Creek, 20 ft. wide, 2 ft. deep, drains WNW.
25.50	N. rim of the Nazlini Creek Canyon, top of sandstone cliff, bears SSE and NNW, thence over rolling land.
40.00	Point for the 1/4 sec. cor. of secs. 21 and 22.

**Survey of the Subdivisional Lines,
T. 29 N., R. 27 E., Gila and Salt River Meridian, Arizona**

CHAINS	
	<p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 23 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T 29 N R 27 E 1/4 S 21 S 22</p> <p style="text-align: center;">2003</p> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p>
41.50	E. rim of Nazlini Creek Canyon, top of sandstone cliff, bears NNE and SSW.
80.00	<p>Point for the cor. of secs. 15, 16, 21, and 22.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T 29 N R 27 E S 16 S 15 S 21 S 22</p> <p style="text-align: center;">2003</p> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p> <p>Land, rolling and broken. Soil, sandy and gravelly clay with sandstone outcrops. Timber, scattered piñon and juniper; undergrowth, brush and native grasses.</p> <hr/> <p>From the cor. of secs. 14, 15, 22, and 23.</p> <p>West, bet. secs. 15 and 22.</p> <p>Over rugged and broken land; descend the W. slope of mesa.</p>
40.00	<p>Point for the 1/4 sec. cor. of secs. 15 and 22.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T 29 N R 27 E S 15 1/4 ——— S 22</p> <p style="text-align: center;">2003</p>

**Survey of the Subdivisional Lines,
T. 29 N., R. 27 E., Gila and Salt River Meridian, Arizona**

CHAINS	
	Deposit a magnet, in a white plastic case, at the base of the stainless steel post.
80.00	The cor. of secs. 15, 16, 21, and 22. Land, rugged and broken. Soil, sandy and rocky clay with sandstone outcrops. Timber, piñon and juniper; undergrowth, brush and native grasses.
	N. 0°02' W., bet. secs. 15 and 16. Over rolling land.
40.00	Point for the 1/4 sec. cor. of secs. 15 and 16. Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd. <div style="text-align: center;"> T 29 N R 27 E 1/4 S 16 S 15 2003 </div>
	Deposit a magnet, in a white plastic case, at the base of the stainless steel post.
47.05	S. rim of a canyon, top of sandstone ledge, bears ESE and WNW, thence across the canyon.
76.65	N. rim of the same canyon, top of sandstone ledge, bears ENE and WSW, thence over rolling land.
80.00	Point for the cor. of secs. 9, 10, 15, and 16. Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd. <div style="text-align: center;"> T 29 N R 27 E S 9 S 10 S 16 S 15 2003 </div>
	Deposit a magnet, in a white plastic case, at the base of the stainless steel post.

**Survey of the Subdivisional Lines,
T. 29 N., R. 27 E., Gila and Salt River Meridian, Arizona**

CHAINS	
	<p>Land, rolling and broken. Soil, sandy and rocky clay with sandstone outcrops. Timber, scattered piñon and juniper; undergrowth, brush and native grasses.</p> <hr/> <p>From the cor. of secs. 10, 11, 14, and 15.</p> <p>West, bet. secs. 10 and 15.</p> <p>Over rugged and broken land; descend the W. slope of mesa.</p>
36.70	Wash, 20 ft. wide, 4 ft. deep, drains S., at the base of the W. slope of mesa, thence over rolling land.
40.00	Point for the 1/4 sec. cor. of secs. 10 and 15.
	<p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T 29 N R 27 E S 10 1/4 ——— S 15</p> <p style="text-align: center;">2003</p>
	<p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p>
80.00	<p>The cor. of secs. 9, 10, 15, and 16.</p> <p>Land, rugged and broken to rolling. Soil, sandy and rocky clay with sandstone outcrops. Timber, scattered piñon and juniper; undergrowth, brush and native grasses.</p> <hr/> <p>N. 0°02' W., bet. secs. 9 and 10.</p> <p>Over rolling land.</p>
36.70	S. rim of a canyon, top of sandstone ledge, bears E. and W., thence descend into the canyon.
40.00	Point for the 1/4 sec. cor. of secs. 9 and 10.
	<p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 16 ins. in the ground, to sandstone bedrock, in a mound of stone, 3 ft. base, to top, with brass cap mkd.</p>

**Survey of the Subdivisional Lines,
T. 29 N., R. 27 E., Gila and Salt River Meridian, Arizona**

CHAINS	
	T 29 N R 27 E 1/4 S 9 S 10 2003 Deposit a magnet, in a white plastic case, at the base of the stainless steel post.
40.50	Wash, 20 ft. wide, 9 ft. deep, drains W.
80.00	Point for the cor. of secs. 3, 4, 9, and 10. Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 22 ins. in the ground, with brass cap mkd.
	T 29 N R 27 E S 4 S 3 ———— S 9 S 10 2003 Deposit a magnet, in a white plastic case, at the base of the stainless steel post.
	<hr/> From the cor. of secs. 2, 3, 10, and 11. West, bet. secs. 3 and 10. Over rugged and broken land; descend the W. slope of mesa.
35.60	Base of the W. slope, bears N. and S., thence over rolling land.
40.00	Point for the 1/4 sec. cor. of secs. 3 and 10. Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.
	T 29 N R 27 E S 3 1/4 ———— S 10 2003 Deposit a magnet, in a white plastic case, at the base of the stainless steel post.
80.00	The cor. of secs. 3, 4, 9, and 10.

**Survey of the Subdivisional Lines,
T. 29 N., R. 27 E., Gila and Salt River Meridian, Arizona**

CHAINS	
	<p>Land, rugged and broken to rolling. Soil, sandy and rocky clay with sandstone outcrops. Timber, piñon and juniper; undergrowth, brush and native grasses.</p> <hr/> <p>N. 0°02' W., bet. secs. 3 and 4.</p> <p>Over rolling land.</p>
40.00	<p>Point for the 1/4 sec. cor. of secs. 3 and 4.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T 29 N R 27 E 1/4 S 4 S 3</p> <p style="text-align: center;">2003</p>
79.99	<p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p> <p>The cor. of secs. 3, 4, 33, and 34, on the N. bdy. of the Tp., hereinbefore described.</p> <p>Land, rolling. Soil, sandy and rocky clay. Timber, scattered piñon and juniper; undergrowth, brush and native grasses.</p> <hr/> <p>From the stan. cor. of secs. 32 and 33, on the S. bdy. of the Tp., hereinbefore described.</p> <p>N. 0°03' W., bet. secs. 32 and 33.</p> <p>Over rugged and broken land; descend the NW slope of mesa.</p>
40.00	<p>Point for the 1/4 sec. cor. of secs. 32 and 33.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in sandstone bedrock, with brass cap mkd.</p> <p style="text-align: center;">T 29 N R 27 E 1/4 S 32 S 33</p> <p style="text-align: center;">2003</p> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p>

**Survey of the Subdivisional Lines,
T. 29 N., R. 27 E., Gila and Salt River Meridian, Arizona**

CHAINS							
80.00	<p>Point for the cor. of secs. 28, 29, 32, 33.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center;"> <table style="margin: auto;"> <tr> <td>T 29 N</td> <td>R 27 E</td> </tr> <tr> <td>S 29</td> <td>S 28</td> </tr> <tr> <td>S 32</td> <td>S 33</td> </tr> </table> <p>2003</p> </div> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p> <p>Land, rugged and broken to rolling. Soil, sandy and gravelly clay. Timber, scattered piñon and juniper; undergrowth, brush and native grasses.</p> <hr/> <p>From the cor. of secs. 27, 28, 33, and 34.</p> <p>West, bet. secs. 28 and 33.</p> <p>Over rugged and broken land; descend the NW slope of mesa.</p>	T 29 N	R 27 E	S 29	S 28	S 32	S 33
T 29 N	R 27 E						
S 29	S 28						
S 32	S 33						
22.69	E. right-of-way fence of Navajo Route 27, barbed wire, 5 strand, parallels the highway.						
22.79	A brass tablet, 3 ins. diam., set flush in conc. collar, 8 ins. diam., set flush with surface of the ground, bears South, 45.5 lks. dist., with top mkd. B.I.A. ROADS 19.						
24.25	Navajo Route 27, asphalt pavement, 40 ft. wide, bears NNE and SSW.						
26.32	A brass tablet, 3 ins. diam., set flush in conc. collar, 12 ins. diam., set flush with surface of the ground, bears North, 43.5 lks. dist., with top mkd. B.I.A. ROADS 19, witnessed by an angle iron, firmly set, projecting 3 ft. above ground, with side mkd. P.O.T 51+00.00.						
26.44	W. right-of-way fence of Navajo Route 27, barbed wire, 5 strand, parallels the highway.						
40.00	<p>Point for the 1/4 sec. cor. of secs. 28 and 33.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p>						

**Survey of the Subdivisional Lines,
T. 29 N., R. 27 E., Gila and Salt River Meridian, Arizona**

CHAINS	
	T 29 N R 27 E S 28 1/4 ——— S 33 2003
	Deposit a magnet, in a white plastic case, at the base of the stainless steel post.
80.00	The cor. of secs. 28, 29, 32, and 33. Land, rugged and broken. Soil, sandy and gravelly clay, with sandstone outcrops. Timber, piñon and juniper; undergrowth, brush and native grasses.

	N. 0°03' W., bet. secs. 28 and 29.
	Over rolling land.
40.00	Point for the 1/4 sec. cor. of secs. 28 and 29. Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.
	T 29 N R 27 E 1/4 S 29 S 28 2003
	Deposit a magnet, in a white plastic case, at the base of the stainless steel post.
73.50	Navajo Route 271, a graded road, 25 ft. wide, bears ENE and WSW.
80.00	Point for the cor. of secs. 20, 21, 28, and 29. Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.
	T 29 N R 27 E S 20 S 21 ——— S 29 S 28 2003
	Deposit a magnet, in a white plastic case, at the base of the stainless steel post.

**Survey of the Subdivisional Lines,
T. 29 N., R. 27 E., Gila and Salt River Meridian, Arizona**

CHAINS	
	<p>Land, rolling. Soil, sandy and gravelly clay. Timber, scattered juniper; undergrowth, brush and native grasses.</p> <hr/> <p>From the cor. of secs. 21, 22, 27, and 28.</p> <p>West, bet. secs. 21 and 28.</p> <p>Over rolling land.</p>
14.44	Power line, bears SE and NW.
14.96	E. right-of-way fence of Navajo Route 27, barbed wire, 5 strand, parallels the highway.
15.53	A brass tablet, 3 ins. diam., set flush in conc. collar, 6 ins. diam., set flush with surface of the ground, bears North, 1.04 chs. dist., with top mkd. B.I.A. ROADS 19 and witnessed by an angle iron, firmly set, projecting 2 ft. above ground, with side mkd. P.O.T. 1055+52.02.
15.78	Underground gas pipeline, bears SSE and NNW.
16.69	Navajo Route 27, asphalt pavement, 32 ft. wide, bears SSE and NNW.
18.17	A brass tablet, 3 ins. diam., set flush in conc. collar, 6 ins. diam., set flush with surface of the ground, bears South, 45.5 lks. dist., with top mkd. B.I.A. ROADS 19 and witnessed by an angle iron, firmly set, projecting 2 ft. above ground, with side mkd. P.O.T. 1055+52.02.
18.40	W. right-of-way fence of Navajo Route 27, barbed wire fence, 5 strand, parallels the highway.
37.20	Graded road, 30 ft. wide, bears SE and NW.
37.97	Intersect the E. side of Nazlini Trading Post, a stucco house, 33 x 22 ft.; the SE cor. bears S. 43° E., 48 lks. dist.
40.00	Point for the 1/4 sec. cor. of secs. 21 and 28.
	<p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T 29 N R 27 E S 21 1/4 ——— S 28</p> <p style="text-align: center;">2003</p>

**Survey of the Subdivisional Lines,
T. 29 N., R. 27 E., Gila and Salt River Meridian, Arizona**

CHAINS	
	Deposit a magnet, in a white plastic case, at the base of the stainless steel post.
	Cor. is located along a woven fence, 5 ft. high, bears SSE and NNW, the east fence of a school compound.
41.52	Intersect the E. side of a stucco building, 64 x 23 ft.; the SE cor. of the long side bears S. 9 1/2° W., 31.5 lks. dist.
48.41	The NE cor. of the north extension of a school building, bears South, 49 lks dist.
52.71	Chain link fence, 4 ft. high, bears N. and S., leaving the school compound.
56.60	Navajo Route 271, a graded road, 25 ft. wide, bears ENE and WSW.
77.08	Chain link fence, 6 ft. high, bears ESE and WNW, the south fence of sewage pond.
80.00	The cor. of secs. 20, 21, 28, and 29. Land, rolling. Soil, sandy and gravelly clay. Timber, scattered juniper; undergrowth, brush and native grasses.
	<hr/>
	N. 0°03' W., bet. secs. 20 and 21. Over rolling land.
39.22	The NW cor. of a stucco house, 20 x 18 ft., bears East, 1.40 chs. dist., the long side bears S.
40.00	Point for the 1/4 sec. cor. of secs. 20 and 21. Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.
	T 29 N R 27 E 1/4 S 20 S 21 2003
	Deposit a magnet, in a white plastic case, at the base of the stainless steel post.
42.20	Trail road, bears SE and NW.
43.59	Power line, bears ENE and WSW.

**Survey of the Subdivisional Lines,
T. 29 N., R. 27 E., Gila and Salt River Meridian, Arizona**

CHAINS							
49.80	Trail road, bears ESE and WNW.						
66.62	S. right-of-way fence of Navajo Route 27, barbed wire, 5 strand, parallels the highway.						
68.09	Navajo Route 27, asphalt pavement, 30 ft. wide, bears E. and W.						
69.57	N. right-of-way fence of Navajo Route 27, barbed wire, 5 strand, parallels the highway.						
80.00	Point for the cor. of secs. 16, 17, 20, and 21. Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.						
	<table style="margin-left: auto; margin-right: auto;"> <tr> <td>T 29 N</td> <td>R 27 E</td> </tr> <tr> <td>S 17</td> <td>S 16</td> </tr> <tr> <td>S 20</td> <td>S 21</td> </tr> </table>	T 29 N	R 27 E	S 17	S 16	S 20	S 21
T 29 N	R 27 E						
S 17	S 16						
S 20	S 21						
	2003						
	Deposit a magnet, in a white plastic case, at the base of the stainless steel post.						
	Land, rolling. Soil, sandy and gravelly clay. Timber, scattered juniper; undergrowth, brush and native grasses.						
	<hr/>						
	From the cor. of secs. 15, 16, 21, and 22.						
	West, bet. secs. 16 and 21.						
	Over rolling and broken land.						
11.15	E. rim of Nazlini Creek Canyon, top of sandstone cliff, bears NE and SW.						
15.80	Nazlini Creek, 25 ft. wide, 4 ft. deep, drains N.						
16.40	W. rim of Nazlini Creek Canyon, top of sandstone cliff, bears NE and SW, thence over rolling land.						
40.00	Point for the 1/4 sec. cor. of secs. 16 and 21. Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.						

**Survey of the Subdivisional Lines,
T. 29 N., R. 27 E., Gila and Salt River Meridian, Arizona**

CHAINS	
	T 29 N R 27 E S 16 1/4 ——— S 21 2003
	Deposit a magnet, in a white plastic case, at the base of the stainless steel post.
65.00	Underground gas pipeline, bears ESE and WNW.
65.32	Power line, bears ESE and WNW.
80.00	The cor. of secs. 16, 17, 20, and 21. Land, rolling and broken. Soil, sandy and gravelly clay, with sandstone outcrops. Timber, scattered juniper; undergrowth, brush and native grasses.
	<hr/> N. 0°03' W., bet. secs. 16 and 17. Over rolling land.
9.35	Power line, bears ESE and WNW.
9.54	Underground gas pipeline, bears ESE and WNW.
18.64	The SE cor. of a two story L-shaped house, log with wood frame, 48 x 35 ft., bears W., 28 lks. dist., the long side bears N. 4 1/2° E.
21.07	The front NE cor. of a stucco octagonal hogan, bears W., 28.5 lks. dist., with 9 ft. sides.
30.70	Trail road, bears NE and SW.
34.87	Barbed wire fence, 5 strand, bears ESE and WNW, the south fence of a cultivated field.
40.00	Point for the 1/4 sec. cor. of secs. 16 and 17. Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. below the surface of the ground, with brass cap mkd.
	T 29 N R 27 E 1/4 S 17 S 16 2003

Survey of the Subdivisional Lines,
T. 29 N., R. 27 E., Gila and Salt River Meridian, Arizona

CHAINS

from which

A stainless steel post, 28 ins. long, 2 1/2 ins. diam., set 24 ins. in the ground for a reference monument, bears S. 70°00' E., 325 ft. dist., with brass cap mkd. RM T29N R27E 1/4 S16 325 FT TO COR 2003 and an arrow pointing to the cor. Deposit a magnet, in a white plastic case, beneath the stainless steel post.

A stainless steel post, 28 ins. long, 2 1/2 ins. diam., set 24 ins. in the ground for a reference monument, bears N. 70°00' W., 212 ft. dist., with brass cap mkd. RM T29N R27E 1/4 S17 212 FT TO COR 2003 and an arrow pointing to the cor. Deposit a magnet, in a white plastic case, beneath the stainless steel post.

Deposit a magnet, in a white plastic case, at the base of the stainless steel post.

47.49 Barbed wire fence, 5 strand, bears ESE and WNW, the north fence of the cultivated field.

80.00 Point for the cor. of secs. 8, 9, 16, and 17.

Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.

T 29 N	R 27 E
S 8	S 9
S 17	S 16

2003

Deposit a magnet, in a white plastic case, at the base of the stainless steel post.

Land, rolling.

Soil, sandy clay.

Timber, scattered juniper; undergrowth, brush and native grasses.

From the cor. of secs. 9, 10, 15, and 16.

West, bet. secs. 9 and 16.

Over rolling land.

40.00 Point for the 1/4 sec. cor. of secs. 9 and 16.

**Survey of the Subdivisional Lines,
T. 29 N., R. 27 E., Gila and Salt River Meridian, Arizona**

CHAINS	
	<p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 20 ins. in the ground, to sandstone bedrock, in a mound of stone, 3 ft. base, to top, with brass cap mkd.</p> <p style="text-align: center;">T 29 N R 27 E S 9 1/4 ——— S 16</p> <p style="text-align: center;">2003</p> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p>
56.60	E. rim of Nazlini Creek Canyon, top of sandstone cliff, bears ESE and WNW.
64.90	Nazlini Creek, 50 ft. wide, 4 ft. deep, drains WNW.
73.30	W. rim of Nazlini Creek Canyon, top of sandstone ledges, bears ESE and WNW.
80.00	The cor. of secs. 8, 9, 16, and 17.
	<p>Land, rolling and broken. Soil, sandy and gravelly clay with sandstone outcrops. Timber, scattered juniper; undergrowth, brush and native grasses.</p> <hr/> <p>N. 0°03' W., bet. secs. 8 and 9.</p> <p>Over rolling and broken land.</p>
2.90	S. rim of Nazlini Creek Canyon, top of sandstone ledges, bears SSE and NNW.
13.80	Nazlini Creek, 50 ft. wide, 5 ft. deep, drains WNW.
26.20	N. rim of Nazlini Creek Canyon, top of sandstone cliff, bears SSE and NNW, thence over rolling land.
40.00	Point for the 1/4 sec. cor. of secs. 8 and 9.
	<p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T 29 N R 27 E 1/4 S 8 S 9</p> <p style="text-align: center;">2003</p>

**Survey of the Subdivisional Lines,
T. 29 N., R. 27 E., Gila and Salt River Meridian, Arizona**

CHAINS									
	Deposit a magnet, in a white plastic case, at the base of the stainless steel post.								
76.10	Navajo Route 8015, a graded road, 25 ft. wide, bears ENE and WSW.								
77.90	Trail road, bears NE and SW.								
80.00	Point for the cor. of secs. 4, 5, 8, and 9. Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.								
	<table style="margin: auto;"> <tr> <td>T 29 N</td> <td>R 27 E</td> </tr> <tr> <td>S 5</td> <td>S 4</td> </tr> <tr> <td style="border-top: 1px solid black;">S 8</td> <td style="border-top: 1px solid black;">S 9</td> </tr> </table>	T 29 N	R 27 E	S 5	S 4	S 8	S 9		
T 29 N	R 27 E								
S 5	S 4								
S 8	S 9								
	2003								
	Deposit a magnet, in a white plastic case, at the base of the stainless steel post.								
	Land, rolling and broken. Soil, sandy and gravelly clay. Timber, scattered juniper; undergrowth, brush and native grasses.								
	From the cor. of secs. 3, 4, 9, and 10.								
	West, bet. secs. 4 and 9.								
	Over rolling land.								
40.00	Point for the 1/4 sec. cor. of secs. 4 and 9. Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.								
	<table style="margin: auto;"> <tr> <td>T 29 N</td> <td>R 27 E</td> </tr> <tr> <td></td> <td>S 4</td> </tr> <tr> <td>1/4</td> <td style="border-top: 1px solid black;">_____</td> </tr> <tr> <td></td> <td>S 9</td> </tr> </table>	T 29 N	R 27 E		S 4	1/4	_____		S 9
T 29 N	R 27 E								
	S 4								
1/4	_____								
	S 9								
	2003								
	Deposit a magnet, in a white plastic case, at the base of the stainless steel post.								
70.90	Navajo Route 8015, a graded road, 25 ft. wide, bears ENE and WSW.								

**Survey of the Subdivisional Lines,
T. 29 N., R. 27 E., Gila and Salt River Meridian, Arizona**

CHAINS	
77.95	Trail road, bears NE and SW.
80.00	The cor. of secs. 4, 5, 8, and 9. Land, rolling. Soil, sandy and gravelly clay. Timber, scattered juniper; undergrowth, brush and native grasses.
	N. 0°03' W., bet. secs. 4 and 5. Over rolling land.
37.80	Trail road, bears NNE and SSW.
40.00	Point for the 1/4 sec. cor. of secs. 4 and 5. Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.
	T 29 N R 27 E 1/4 S 5 S 4 2003
	Deposit a magnet, in a white plastic case, at the base of the stainless steel post.
79.99	The cor. of secs. 4, 5, 32, and 33, on the N. bdy. of the Tp., hereinbefore described. Land, rolling. Soil, sandy and gravelly clay. Timber, scattered juniper; undergrowth, brush and native grasses.
	From the stan. cor. of secs. 31 and 32, on the S. bdy. of Tp., hereinbefore described. N. 0°03' W., bet. secs. 31 and 32. Over rolling land.
40.00	Point for the 1/4 sec. cor. of secs. 31 and 32. Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.

**Survey of the Subdivisional Lines,
T. 29 N., R. 27 E., Gila and Salt River Meridian, Arizona**

CHAINS	<p align="center">T 29 N R 27 E 1/4 S 31 S 32</p> <p align="center">2003</p> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p> <p>56.95 Wash, 45 ft. wide, 4 ft. deep, drains WNW.</p> <p>80.00 Point for the cor. of secs. 29, 30, 31, and 32.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p align="center">T 29 N R 27 E S 30 S 29 ----- S 31 S 32</p> <p align="center">2003</p> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p> <p>Land, rolling. Soil, sandy and gravelly clay. Timber, scattered juniper; undergrowth, brush and native grasses.</p> <hr/> <p>From the cor. of secs. 28, 29, 32, and 33.</p> <p>West, bet. secs. 29 and 32.</p> <p>Over rolling land.</p> <p>40.00 Point for the 1/4 sec. cor. of secs. 29 and 32.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p align="center">T 29 N R 27 E S 29 1/4 ——— S 32</p> <p align="center">2003</p> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p>
--------	-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------

**Survey of the Subdivisional Lines,
T. 29 N., R. 27 E., Gila and Salt River Meridian, Arizona**

CHAINS	
80.00	<p>The cor. of secs. 29, 30, 31, and 32.</p> <p>Land, rolling. Soil, sandy and gravelly clay. Timber, scattered juniper; undergrowth, brush and native grasses.</p> <hr/> <p>West, bet. secs. 30 and 31.</p> <p>Over rolling land.</p>
2.80	Trail road, bears NNE and SSW.
5.64	Power line, bears NNE and SSW.
26.50	Wash, 25 ft. wide, 3 ft. deep, drains NW.
37.10	Navajo Route 271, a graded road, 25 ft. wide, bears NE and SW.
40.00	<p>Point for the 1/4 sec. cor. of secs. 30 and 31.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center;"> <p>T 29 N R 27 E S 30 1/4 ——— S 31</p> <p>2003</p> </div> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p>
55.40	Apache County Road C309, a graded road, 15 ft. wide, bears SE and NW.
79.48	<p>The cor. of secs. 25, 30, 31, and 36, on the W. bdy. of Tp., monumented with a stainless steel post, 2 1/2 ins. diam., firmly set, projecting 4 ins. above ground, with brass cap mkd. T29N R26E R27E S25 S30 S36 S31 1991.</p> <p>Add the marks 2003 to the brass cap.</p> <p>Land, rolling. Soil, sandy and gravelly clay. No timber, scattered brush and native grasses.</p> <hr/> <p>From the cor. of secs. 29, 30, 31, and 32.</p> <p>N. 0°03' W., bet. secs. 29 and 30.</p>

**Survey of the Subdivisional Lines,
T. 29 N., R. 27 E., Gila and Salt River Meridian, Arizona**

CHAINS	
	Over rolling land.
5.00	Trail road, bears NE and SW.
27.16	Power line, bears NNE and SSW.
30.23	The NE cor. of a wood frame house, 36 x 24 ft., bears W., 13.5 lks. dist., the long side bears S.
40.00	Point for the 1/4 sec. cor. of secs. 31 and 32. Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd. <div style="text-align: center;"> T 29 N R 27 E 1/4 S 30 S 29 2003 </div>
	Deposit a magnet, in a white plastic case, at the base of the stainless steel post.
41.65	Trail road, bears SSE and NNW.
44.24	Power line, bears ENE and WSW.
45.65	Navajo Route 271, a graded road, 25 ft. wide, bears NE and SW.
80.00	Point for the cor. of secs. 19, 20, 29, and 30. Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd. <div style="text-align: center;"> T 29 N R 27 E S 19 S 20 S 30 S 29 2003 </div>
	Deposit a magnet, in a white plastic case, at the base of the stainless steel post.
	Land, rolling. Soil, sandy and gravelly clay. No timber; scattered brush and native grasses.
	From the cor. of secs. 20, 21, 28, and 29.
	West, bet. secs. 20 and 29.

**Survey of the Subdivisional Lines,
T. 29 N., R. 27 E., Gila and Salt River Meridian, Arizona**

CHAINS	
	Over rolling land.
39.10	Trail road, bears NE and SW.
40.00	Point for the 1/4 sec. cor. of secs. 20 and 29. Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd. <div style="text-align: center;"> T 29 N R 27 E S 20 1/4 ——— S 29 2003 </div>
	Deposit a magnet, in a white plastic case, at the base of the stainless steel post.
70.10	Tah-atih-cheed Wash, 50 ft. wide, 5 ft. deep, drains NNW.
80.00	The cor. of secs. 19, 20, 29, and 30. Land, rolling. Soil, sandy and gravelly clay. No timber; scattered brush and native grasses.
	West, bet. secs. 19 and 30.
	Over rolling land.
40.00	Point for the 1/4 sec. cor. of secs. 19 and 30. Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd. <div style="text-align: center;"> T 29 N R 27 E S 19 1/4 ——— S 30 2003 </div>
	Deposit a magnet, in a white plastic case, at the base of the stainless steel post.
79.41	The cor. of secs. 19, 24, 25, and 30, on the W. bdy. of the Tp., monumented with a stainless steel post, 2 1/2 ins. diam., firmly set, projecting 6 ins. above ground, with brass cap mkd. T29N R26E R27E S24 S19 S25 S30 1991. Add the marks 2003 to the brass cap.

**Survey of the Subdivisional Lines,
T. 29 N., R. 27 E., Gila and Salt River Meridian, Arizona**

CHAINS	
	<p>Land, rolling. Soil, sandy and gravelly clay. No timber; scattered brush and native grasses.</p> <hr/> <p>From the cor. of secs. 19, 20, 29, and 30. N. 0°03' W., bet. secs. 19 and 20. Over rolling land.</p>
12.50	Tah-atih-cheed Wash, 30 ft. wide, 4 ft. deep, drains WSW.
38.60	Trail road, bears E. and W.
40.00	<p>Point for the 1/4 sec. cor. of secs. 19 and 20.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T 29 N R 27 E 1/4 S 19 S 20</p> <p style="text-align: center;">2003</p> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p>
80.00	<p>Point for the cor. of secs. 17, 18, 19, and 20.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T 29 N R 27 E S 18 S 17 S 19 S 20</p> <p style="text-align: center;">2003</p> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p> <p>Land, rolling. Soil, sandy and gravelly clay. No timber; scattered brush and native grasses.</p> <hr/> <p>From the cor. of secs. 16, 17, 20, and 21. West, bet. secs. 17 and 20.</p>

**Survey of the Subdivisional Lines,
T. 29 N., R. 27 E., Gila and Salt River Meridian, Arizona**

CHAINS	
	Over rolling land.
18.12	E. right-of-way fence of Navajo Route 27, barbed wire, 5 strand, parallels the highway.
20.10	Navajo Route 27, asphalt pavement, 30 ft. wide, bears SE and NW.
22.08	W. right-of-way fence of Navajo Route 27, barbed wire, 5 strand, parallels the highway.
29.80	Trail road, bears NE and SW.
40.00	Point for the 1/4 sec. cor. of secs. 17 and 20. Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd. <div style="text-align: center;"> T 29 N R 27 E S 17 1/4 ——— S 20 2003 </div>
	Deposit a magnet, in a white plastic case, at the base of the stainless steel post.
80.00	The cor. of secs. 17, 18, 19, and 20. Land, rolling. Soil, sandy and gravelly clay. No timber; scattered brush and native grasses. <hr/>
	West, bet. secs. 18 and 19.
	Over rolling land.
40.00	Point for the 1/4 sec. cor. of secs. 18 and 19. Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd. <div style="text-align: center;"> T 29 N R 27 E S 18 1/4 ——— S 19 2003 </div>
	Deposit a magnet, in a white plastic case, at the base of the stainless steel post.

**Survey of the Subdivisional Lines,
T. 29 N., R. 27 E., Gila and Salt River Meridian, Arizona**

CHAINS	
79.31	<p>The cor. of secs. 13, 18, 19, and 24, on the W. bdy. of the Tp., monumented with a stainless steel post, 2 1/2 ins. diam., firmly set, projecting 4 ins. above ground, with brass cap mkd. T29N R26E R27E S13 S18 S24 S19 1991.</p> <p>Add the marks the 2003 to the brass cap.</p> <p>Land, rolling. Soil, sandy and gravelly clay. No timber; scattered brush and native grasses.</p> <hr/> <p>From the cor. of secs. 17, 18, 19, and 20. N. 0°03' W., bet. secs. 17 and 18. Over rolling land.</p>
39.35	Trail road, bears E. and W.
40.00	<p>Point for the 1/4 sec. cor. of secs. 17 and 18.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T 29 N R 27 E 1/4 S 18 S 17</p> <p style="text-align: center;">2003</p> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p>
47.63	A brass tablet, 3 ins. diam., set flush in conc. collar, 18 ins. square, firmly set, projecting 3 ins. above ground, bears E., 1.33 chs. dist., with top mkd. B.I.A. ROADS 19, witnessed by an angle iron, firmly set, projecting 2 ft. above ground, with side mkd. PT 32+071.755.
49.23	W. right-of-way fence of Navajo Route 27, barbed wire, 5 strand, parallels the highway.
51.54	Navajo Route 27, asphalt pavement, 35 ft. wide, bears SE and NW.
53.81	E. right-of-way fence of Navajo Route 27, barbed wire, 5 strand, parallels the highway.
55.34	Power line, bears SE and NW.
72.70	Underground gas pipeline, bears SE and NW.
80.00	Point for the cor. of secs. 7, 8, 17, and 18.

**Survey of the Subdivisional Lines,
T. 29 N., R. 27 E., Gila and Salt River Meridian, Arizona**

CHAINS									
	<p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <table style="margin-left: auto; margin-right: auto;"> <tr> <td>T 29 N</td> <td>R 27 E</td> </tr> <tr> <td>S 7</td> <td>S 8</td> </tr> <tr> <td>S 18</td> <td>S 17</td> </tr> </table> <p style="text-align: center;">2003</p> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p> <p>Cor. is located at 1.40 chs. E. of a trail road, bears NE and SW.</p> <p>Land, rolling. Soil, sandy and gravelly clay. No timber; scattered brush and native grasses.</p> <hr/> <p>From the cor. of secs. 8, 9, 16, and 17.</p> <p>West, bet. secs. 8 and 17.</p> <p>Over rolling land.</p>	T 29 N	R 27 E	S 7	S 8	S 18	S 17		
T 29 N	R 27 E								
S 7	S 8								
S 18	S 17								
33.10	Navajo Route 8015, a graded road, 15 ft. wide, bears N. and S.								
40.00	<p>Point for the 1/4 sec. cor. of secs. 8 and 17.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <table style="margin-left: auto; margin-right: auto;"> <tr> <td>T 29 N</td> <td>R 27 E</td> </tr> <tr> <td></td> <td>S 8</td> </tr> <tr> <td>1/4</td> <td>—</td> </tr> <tr> <td></td> <td>S 17</td> </tr> </table> <p style="text-align: center;">2003</p> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p> <p>Cor. is located 6 lks. N. and 35 lks. E. of an underground waterline, bears ESE and WNW.</p>	T 29 N	R 27 E		S 8	1/4	—		S 17
T 29 N	R 27 E								
	S 8								
1/4	—								
	S 17								
43.12	The NE cor. of a stucco house, 59 x 25 ft., bears S., 1.32 chs. dist., the long side, bears S 12° E.								
80.00	The cor. of secs. 7, 8, 17, and 18.								

**Survey of the Subdivisional Lines,
T. 29 N., R. 27 E., Gila and Salt River Meridian, Arizona**

CHAINS	
	<p>Land, rolling. Soil, sandy and gravelly clay. No timber; scattered brush and grasses.</p> <hr/> <p>West, bet. secs. 7 and 18.</p> <p>Over rolling land.</p>
7.95	Underground gas pipeline, bears SE and NW.
20.98	Power line, bears SE and NW.
22.00	E. right-of-way fence of Navajo Route 27, barbed wire, 5 strand, parallels the highway.
23.92	Navajo Route 27, asphalt pavement, 35 ft. wide, bears SE and NW.
25.86	W. right-of-way fence of Navajo Route 27, barbed wire, 5 strand, parallels the highway.
40.00	<p>Point for the 1/4 sec. cor. of secs. 7 and 18.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center;"> <p>T 29 N R 27 E S 7 1/4 ——— S 18</p> <p>2003</p> </div> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p>
79.21	<p>The cor. of secs. 7, 12, 13, and 18, on the W. bdy. of the Tp., monumented with a stainless steel post, 2 1/2 ins. diam., firmly set, projecting 8 ins. above ground, with brass cap mkd. T29N R26E R27E S12 S7 S13 S18 1991.</p> <p>Add the marks 2003 to the brass cap.</p> <p>Land, rolling. Soil, sandy and gravelly clay. No timber; scattered brush and native grasses.</p> <hr/> <p>From the cor. of secs. 7, 8, 17, and 18.</p> <p>N. 0°03' W., bet. secs. 7 and 8.</p> <p>Over rolling land.</p>

**Survey of the Subdivisional Lines,
T. 29 N., R. 27 E., Gila and Salt River Meridian, Arizona**

CHAINS	
40.00	<p>Point for the 1/4 sec. cor. of secs. 7 and 8.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T 29 N R 27 E 1/4 S 7 S 8</p> <p style="text-align: center;">2003</p> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p>
78.90	Nazlini Creek, 40 ft. wide, 4 ft. deep, drains WNW.
80.00	<p>Point for the cor. of secs. 5, 6, 7, and 8.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T 29 N R 27 E S 6 S 5 S 7 S 8</p> <p style="text-align: center;">2003</p> <p>from which</p> <p style="padding-left: 40px;">The marks, X BO, chiseled on a sandstone boulder, 10 x 6 x 3 ft. high, bears S. 49 1/4° W., 1.465 chs. dist.</p> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p> <p>Land, rolling. Soil, sandy and gravelly clay. No timber; scattered brush and native grasses.</p> <hr/> <p>From the cor. of secs. 4, 5, 8, and 9.</p> <p>West, bet. secs. 5 and 8.</p> <p>Over rolling land.</p>
39.70	Ravine, 5 ft. wide, 30 ft. deep, drains SSW.
40.00	Point for the 1/4 sec. cor. of secs. 5 and 8.

**Survey of the Subdivisional Lines,
T. 29 N., R. 27 E., Gila and Salt River Meridian, Arizona**

CHAINS	
	<p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T 29 N R 27 E S 5 1/4 ——— S 8</p> <p style="text-align: center;">2003</p> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p>
80.00	<p>The cor. of secs. 5, 6, 7, and 8.</p> <p>Land, rolling. Soil, sandy and gravelly clay. Timber, scattered juniper; undergrowth, brush and native grasses.</p> <hr/> <p>West, bet. secs. 6 and 7.</p> <p>Over rolling land; ascend out of Nazlini Creek Canyon.</p>
2.25	Nazlini Creek, 40 ft. wide, 4 ft. deep, drains NW.
40.00	<p>Point for the 1/4 sec. cor. of secs. 6 and 7.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T 29 N R 27 E S 6 1/4 ——— S 7</p> <p style="text-align: center;">2003</p> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p>
79.11	<p>The cor. of secs. 1, 6, 7, and 12, on the W. bdy. of the Tp., monumented with a stainless steel post, 2 1/2 ins. diam., firmly set, projecting 4 ins. above ground, with brass cap mkd. T29N R26E R27E S1 S6 S12 S7 1991.</p> <p>from which the 1991 bearing tree</p> <p style="text-align: center;">A piñon, 8 ins. diam., bears N. 59 1/4° W., 54 lks. dist., mkd. T29N R26E S1 BT visible on open blaze. (Record: N. 57 3/4° W.)</p>

**Survey of the Subdivisional Lines,
T. 29 N., R. 27 E., Gila and Salt River Meridian, Arizona**

CHAINS	
	<p>Add the marks 2003 to the brass cap.</p> <p>Land, rolling. Soil, sandy and gravelly clay. Timber, scattered juniper; undergrowth, brush and native grasses.</p> <hr/> <p>From the cor. of secs. 5, 6, 7, and 8.</p> <p>N. 0°03' W., bet. secs. 5 and 6.</p> <p>Over rolling and broken land, along the Nazlini Creek Canyon.</p>
5.65	Nazlini Creek, 40 ft. wide, 4 ft. deep, drains NE.
12.90	Nazlini Creek, 50 ft. wide, 4 ft. deep, drains NW; thence ascend out of the canyon.
40.00	<p>Point for the 1/4 sec. cor. of secs. 5 and 6.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T 29 N R 27 E 1/4 S 6 S 5 2003</p>
	<p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p>
79.99	<p>The cor. of secs. 5, 6, 31, and 32, on the N. bdy. of the Tp., hereinbefore described.</p> <p>Land, rolling and broken. Soil, sandy and gravelly clay with sandstone outcrops. Timber, scattered juniper; undergrowth, brush and native grasses.</p> <hr/>

T. 29 N., R. 27 E., Gila and Salt River Meridian, Arizona

CHAINS

GENERAL DESCRIPTION

The area surveyed is around the community of Nazlini, Arizona, on the Navajo Indian Reservation. The land is mostly rugged and broken with rock canyons on the eastern portion of township and rolling and broken on the western portion. The main drainage is Nazlini Creek Canyon which enters the township in section 13 and curves southwesterly through the township and exits in section 6.

The elevation varies from 5900 to 7100 feet above sea level. The soil is mostly sandy and gravelly clay with sandstone ledges and outcrops. The timber consists primarily of piñon and juniper. Undergrowth consists of various brush and native grasses.

The main access to the area is provided by Navajo Route 27, a new highway which enters the township in section 35 and exits in section 7. From this, Navajo Route 8015, a graded road, branches off in section 17 and exits the township in section 4. From these main routes, there are numerous trail roads throughout the township. There are several scattered pastures for grazing livestock. There is no evidence of any current mining activity.

The mean magnetic declination of $11 \frac{1}{4}^{\circ}$ E. was derived from the computer program GEOMAGIX utilizing the Regional Magnetic Field Model for Epoch 2000 for the dates of survey.

CERTIFICATE OF SURVEY

I, Leonard R. Sandoval, Cadastral Surveyor, HEREBY CERTIFY upon honor, that in pursuance of special instructions bearing date of the 6th day of May, 2003, I have surveyed the Seventh Standard Parallel North (south boundary), the east and north boundaries, and the subdivisional lines, T. 29 N., R. 27 E., of the Gila and Salt River Meridian, in the State of Arizona, which are represented in the foregoing field notes as having been executed by me and under my direction. Said survey has been made in strict conformity with said special instructions, the Manual of Instructions for the Survey of the Public Lands of the United States, 1973, and in specific manner described in the foregoing field notes.

5-12-05

(Date)

Leonard R. Sandoval
(Cadastral Surveyor)

CERTIFICATE OF APPROVAL

BUREAU OF LAND MANAGEMENT
Phoenix, Arizona

The foregoing field notes of the Survey of the Seventh Standard Parallel North (south boundary), the east and north boundaries, and the subdivisional lines, T. 29 N., R. 27 E., Gila and Salt River Meridian, in the State of Arizona, executed by Leonard R. Sandoval, Cadastral Surveyor, having been critically examined and found correct, are hereby approved.

6-02-05

(Date)

Stephen K. Hansen
(Acting Chief Cadastral Surveyor of Arizona)

~~CERTIFICATE OF TRANSCRIPT~~

~~I CERTIFY That the foregoing transcript of the field notes of the above described surveys in T. 29 N., R. 27 E., Gila and Salt River Meridian, Arizona, is a true copy of the original field notes.~~

~~(Date)~~

~~(Acting Chief Cadastral Surveyor of Arizona)~~