

ORIGINAL

**UNITED STATES  
DEPARTMENT OF THE INTERIOR  
BUREAU OF LAND MANAGEMENT**

FIELD NOTES  
OF  
THE SURVEY OF THE EAST BOUNDARY,  
THE SECTIONAL CORRECTION LINE  
AND  
THE SUBDIVISIONAL LINES,  
TOWNSHIP 24 NORTH, RANGE 27 EAST,  
OF THE GILA AND SALT RIVER MERIDIAN,  
IN THE STATE OF ARIZONA

**EXECUTED BY**

**Jones Curtiss, Cadastral Surveyor**

Under Special Instructions dated and approved May 1, 2002, which provided for the surveys included under Group No. 886, and assignment instructions dated May 1, 2003.

**Survey commenced January 13, 2003**

**Survey completed March 11, 2003**

## INDEX DIAGRAM

TOWNSHIP 24 NORTH                  RANGE 27 EAST  
GILA & SALT RIVER MERIDIAN, ARIZONA

63	62	47	39	31	23
61 6	61 5	46 4	38 3	30 2	22 1 8
59	58	45	37	29	21
60 7	58 8	44 9	37 10	28 11	20 12 7
56	55	44	36	28	20
57 18	54 17	43 16	35 15	27 14	19 13 6
53	52	42	35	26	18
54 19	51 20	42 21	34 22	25 23	18 24 5
49	49	41	33	25	17
51 30	48 29	40 28	32 27	24 26	16 25 4
13	13	12	11	10	9
15 31	47 32	40 33	32 34	23 35	15 36 4

## T. 24 N., R. 27 E., Gila and Salt River Meridian, Arizona

CHAINS

The following field notes describes the survey of the east boundary, the sectional correction line and the subdivisional lines, Township 24 North, Range 27 East, Gila and Salt River Meridian, Arizona.

The history of surveys pertaining to this survey is as follows:

Frank Follman surveyed the north boundary, Township 23 North, Range 27 East in 1882 and the Sixth Standard Parallel North (south boundary), Townships 25 North, Ranges 26 and 27 East in 1883. Loyd E. Sechrist dependently resurveyed the Sixth Standard Parallel North thru Range 27 East in 1920. Jones Curtiss dependently resurveyed a portion of the Sixth Standard Parallel North (south boundary), Township 25 North, Range 26 East in 2002 and the Sixth Standard Parallel North (south boundary), Township 25 North, Range 27 East in 2003, both concurrently under this same group. Jones Curtiss surveyed the east boundary, Township 24 North, Range 26 East in 2002 and dependently resurveyed the east and north boundaries, Township 23 North, Range 27 East in 2002-03, both concurrently under this same group.

The survey was executed in accordance with the specifications as set forth in the Manual of Instructions for the Survey of the Public Lands of the United States, 1973, and the Special Instructions dated May 1, 2002 for Group No. 886, Arizona.

The true meridian direction and length of all lines were determined by real time kinematic global positioning system observations using Trimble Navigation Model 5700 receivers.

Geodetic control was derived from Global Positioning System (GPS) static observations post processed by National Geodetic Survey's, Online Positioning User Service (OPUS), utilizing Continuously Operating Reference Stations (CORS) FERNO MESA ARP, FLAGSTAFF 1 ARP, AND PIE TOWN ARP VLBA. The NAD83 (CORS96) (EPOCH:2003) geographic position of the southeast corner of the township is as follows:

Latitude: 35°25'50.96" N.                      Longitude: 109°25'13.34" W.

The mean magnetic declination is 11 1/2° E.

---

**Survey of the East Boundary,  
T. 24 N., R. 27 E., Gila and Salt River Meridian, Arizona**

CHAINS													
	<p>Beginning at the cor. of Tps. 23 and 24 N., Rs. 27 E. only, monumented with a stainless steel post, 2 1/2 ins. diam., with brass cap, set and mkd. as described in the field notes of the dependent resurvey of the E. bdy., T. 23 N., R. 27 E., executed concurrently under this same group.</p> <p>North, on the E. bdy. of sec. 36.</p> <p>Over rolling and broken land.</p>												
40.00	<p>Point for the 1/4 sec. cor. of sec. 36 only.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center;"> <table style="margin-left: auto; margin-right: auto;"> <tr><td>T 24 N</td><td></td></tr> <tr><td>R 27 E</td><td>R 28 E</td></tr> <tr><td>1/4</td><td> </td></tr> <tr><td>S 36</td><td> </td></tr> </table> <p>2003</p> </div> <p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p>	T 24 N		R 27 E	R 28 E	1/4		S 36					
T 24 N													
R 27 E	R 28 E												
1/4													
S 36													
80.00	<p>Point for the cor. of secs. 25 and 36 only.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center;"> <table style="margin-left: auto; margin-right: auto;"> <tr><td>T 24 N</td><td> </td><td>T 24 N</td></tr> <tr><td>S 25</td><td> </td><td>R 28 E</td></tr> <tr><td>S 36</td><td> </td><td>S 30</td></tr> <tr><td>R 27 E</td><td> </td><td></td></tr> </table> <p>2003</p> </div> <p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p> <p>Land, rolling and broken. Soil, sandy clay and rocky with sandstone outcrops. Timber, piñon and juniper; undergrowth, sagebrush, scrub oak and native grasses.</p> <hr/> <p>North, on the E. bdy. of sec. 25.</p> <p>Over rolling and broken land.</p>	T 24 N		T 24 N	S 25		R 28 E	S 36		S 30	R 27 E		
T 24 N		T 24 N											
S 25		R 28 E											
S 36		S 30											
R 27 E													
40.00	<p>Point for the 1/4 sec. cor. of sec. 25 only.</p>												

**Survey of the East Boundary,  
T. 24 N., R. 27 E., Gila and Salt River Meridian, Arizona**

CHAINS	
	<p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 19 ins. in the ground, to sandstone bedrock, in a mound of stone, 3 ft. base to top, with brass cap mkd.</p> <p style="text-align: center;">T 24 N R 27 E    R 28 E 1/4      S 25     </p> <p style="text-align: center;">2003</p> <p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p>
80.00	<p>Point for the cor. of secs. 24 and 25 only.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T 24 N         T 24 N S 24         R 28 E ----- S 25         S 19 R 27 E     </p> <p style="text-align: center;">2003</p> <p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p> <p>Land, rolling and broken. Soil, sand and sandy clay. Timber, piñon and juniper; undergrowth, sagebrush, scrub oak and native grasses.</p> <hr/> <p>North, on the E. bdy. of sec. 24.</p> <p>Over rolling and broken land.</p>
32.30	<p>Navajo Route 9355, a graded road, 25 ft. wide, bears N. 30° E. and S. 30° W.</p>
34.40	<p>Oak Ridge Wash, 12 ft. wide, 6 ft. deep, drains S. 80° W.</p>
40.00	<p>Point for the 1/4 sec. cor. of sec. 24 only.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p>

**Survey of the East Boundary,  
T. 24 N., R. 27 E., Gila and Salt River Meridian, Arizona**

CHAINS									
	T 24 N R 27 E    R 28 E 1/4   S 24    2003								
	Deposit a magnet in a white plastic case at the base of the stainless steel post.								
80.00	Point for the cor. of secs. 13 and 24 only.  Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.								
	<table style="margin-left: auto; margin-right: auto;"> <tr> <td style="border-right: 1px solid black; padding: 0 5px;">T 24 N</td> <td style="padding: 0 5px;">T 24 N</td> </tr> <tr> <td style="border-right: 1px solid black; padding: 0 5px;">S 13</td> <td style="padding: 0 5px;">R 28 E</td> </tr> <tr> <td style="border-right: 1px solid black; padding: 0 5px;">S 24</td> <td style="padding: 0 5px;">S 18</td> </tr> <tr> <td style="border-right: 1px solid black; padding: 0 5px;">R 27 E</td> <td style="padding: 0 5px;"></td> </tr> </table> 2003	T 24 N	T 24 N	S 13	R 28 E	S 24	S 18	R 27 E	
T 24 N	T 24 N								
S 13	R 28 E								
S 24	S 18								
R 27 E									
	Deposit a magnet in a white plastic case at the base of the stainless steel post.								
	Land, rolling and broken. Soil, sand clay and rocky. Timber, ponderosa pine, piñon and juniper; undergrowth, scrub oak, sagebrush and native grasses.								
	North, on the E. bdy. of sec. 13.  Over rolling and broken land.								
40.00	Point for the 1/4 sec. cor. of sec. 13 only.  Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.								
	T 24 N R 27 E    R 28 E 1/4   S 13    2003								
	Deposit a magnet in a white plastic case at the base of the stainless steel post.								
80.00	Point for the cor. of secs. 12 and 13 only.								

**Survey of the East Boundary,  
T. 24 N., R. 27 E., Gila and Salt River Meridian, Arizona**

CHAINS									
	<p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, in an embedded collar of stone, 2 ft. base, with brass cap mkd.</p> <table style="margin-left: auto; margin-right: auto;"> <tr> <td style="border-right: 1px solid black; padding: 2px;">T 24 N</td> <td style="padding: 2px;">T 24 N</td> </tr> <tr> <td style="border-right: 1px solid black; padding: 2px;">S 12</td> <td style="padding: 2px;">R 28 E</td> </tr> <tr> <td style="border-right: 1px solid black; padding: 2px;">S 13</td> <td style="padding: 2px;">S 7</td> </tr> <tr> <td style="border-right: 1px solid black; padding: 2px;">R 27 E</td> <td style="padding: 2px;"></td> </tr> </table> <p style="text-align: center;">2003</p> <p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p> <p>Land, rolling and broken. Soil, sandy clay and rocky. Timber, ponderosa pine, piñon and juniper; undergrowth, scrub oak, sagebrush and native grasses.</p> <hr style="width: 50%; margin: 10px auto;"/> <p>North, on the E. bdy. of sec. 12.</p> <p>Over rolling and broken land.</p>	T 24 N	T 24 N	S 12	R 28 E	S 13	S 7	R 27 E	
T 24 N	T 24 N								
S 12	R 28 E								
S 13	S 7								
R 27 E									
40.00	<p>Point for the 1/4 sec. cor. of sec. 12 only.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <table style="margin-left: auto; margin-right: auto;"> <tr> <td style="padding: 2px;">T 24 N</td> <td style="padding: 2px;"></td> </tr> <tr> <td style="padding: 2px;">R 27 E</td> <td style="padding: 2px;">R 28 E</td> </tr> <tr> <td style="padding: 2px;">1/4</td> <td style="padding: 2px;"> </td> </tr> <tr> <td style="padding: 2px;">S 12</td> <td style="padding: 2px;"> </td> </tr> </table> <p style="text-align: center;">2003</p> <p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p>	T 24 N		R 27 E	R 28 E	1/4		S 12	
T 24 N									
R 27 E	R 28 E								
1/4									
S 12									
80.00	<p>Point for the cor. of secs. 1 and 12 only.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 16 ins. in the ground, to sandstone bedrock, in a mound of stone, 3 ft. base to top, with brass cap mkd.</p> <table style="margin-left: auto; margin-right: auto;"> <tr> <td style="border-right: 1px solid black; padding: 2px;">T 24 N</td> <td style="padding: 2px;">T 24 N</td> </tr> <tr> <td style="border-right: 1px solid black; padding: 2px;">S 1</td> <td style="padding: 2px;">R 28 E</td> </tr> <tr> <td style="border-right: 1px solid black; padding: 2px;">S 12</td> <td style="padding: 2px;">S 6</td> </tr> <tr> <td style="border-right: 1px solid black; padding: 2px;">R 27 E</td> <td style="padding: 2px;"></td> </tr> </table> <p style="text-align: center;">2003</p>	T 24 N	T 24 N	S 1	R 28 E	S 12	S 6	R 27 E	
T 24 N	T 24 N								
S 1	R 28 E								
S 12	S 6								
R 27 E									

**Survey of the East Boundary,  
T. 24 N., R. 27 E., Gila and Salt River Meridian, Arizona**

CHAINS	
	<p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p> <p>Land, rolling and broken. Soil, sandy clay and rocky. Timber, ponderosa pine, piñon and juniper; undergrowth, scrub oak, sagebrush and native grasses.</p> <hr/> <p>North, on the E. bdy. of sec. 1. Over rolling and broken land.</p>
40.00	<p>Point for the 1/4 sec. cor. of sec. 1 only.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center;"> <p>T 24 N R 27 E    R 28 E 1/4   S 1  </p> <p>2003</p> </div>
78.86	<p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p> <p>Point for the closing cor. of Tps. 24 N., Rs. 27 and 28 E., at the intersection with the Sixth Standard Parallel North, on the N. bdy. of the Tp.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center;"> <p>T 25 N    R 27 E S 35 ----- S 1      S 6 R 27 E      R 28 E T 24 N CC</p> <p>2003</p> </div> <p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p>



**Survey of the East Boundary,  
T. 24 N., R. 27 E., Gila and Salt River Meridian, Arizona**

CHAINS

From this cor. point, the stan. cor. of secs. 35 and 36, T. 25 N., R. 27 E., bears S. 89°59' E., 8.24 chs. dist., monumented with a stainless steel post, 2 1/2 ins. diam., with brass cap, set, mkd. and witnessed as described in the field notes of the dependent resurvey of the Sixth Standard Parallel North (south boundary), T. 25 N., R. 27 E., executed concurrently under this same group.

From this same cor. point, the stan. 1/4 sec. cor. of sec. 35, T. 25 N., R. 27 E., bears N. 89°59' W., 31.80 chs. dist., monumented with an iron post, 1 in. diam., with brass cap, set, mkd. and witnessed as described in the field notes of the dependent resurvey of the Sixth Standard Parallel North (south boundary), T. 25 N., R. 27 E., executed concurrently under this same group.

Land, rolling and broken.

Soil, sand and sandy clay.

Timber, ponderosa pine, piñon and juniper; undergrowth, scrub oak, sagebrush and native grasses.

---

**Survey of the Sectional Correction Line,  
T. 24 N., R. 27 E., Gila and Salt River Meridian, Arizona**

---

Note: The results of the dependent resurvey of the N. bdy., T. 23 N., R. 27 E., exceed the specified rectangular limits for alinement to control the subdivision of this township. This necessitates the need for the establishment of a sectional correction line.

From the cor. of secs. 25 and 36 only, on the E. bdy. of the Tp., hereinbefore described.

West, bet. secs. 25 and 36.

Over rolling and broken land.

40.00

Point for the 1/4 sec. cor. of secs. 25 and 36.

Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.

T 24 N R 27 E  
S 25  
1/4 ———  
S 36

2003

Deposit a magnet in a white plastic case at the base of the stainless steel post.

Survey of the Sectional Correction Line,  
T. 24 N., R. 27 E., Gila and Salt River Meridian, Arizona

CHAINS	<p>80.00 Point for the cor. of secs. 25, 26, 35 and 36.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. below the surface of the ground, with brass cap mkd.</p> <table style="margin-left: auto; margin-right: auto; border-collapse: collapse;"> <tr> <td colspan="2" style="text-align: center;">T 24 N R 27 E</td> </tr> <tr> <td style="text-align: center; border-right: 1px solid black;">S 26</td> <td style="text-align: center;">S 25</td> </tr> <tr> <td style="text-align: center; border-right: 1px solid black;">S 35</td> <td style="text-align: center;">S 36</td> </tr> </table> <p style="text-align: center;">2003</p> <p>from which</p> <p style="padding-left: 40px;">A stainless steel post, 28 ins. long, 2 1/2 ins. diam., set 24 ins. in the ground for a reference monument, bears S. 60°00' E., 60.00 ft. dist., with brass cap mkd. RM T24N R27E S36 60.0 FT. TO COR 2003 and an arrow pointing to the corner. Deposit a magnet in a white plastic case at the base of the stainless steel post.</p> <p style="padding-left: 40px;">A stainless steel post, 28 ins. long, 2 1/2 ins. diam., set 24 ins. in the ground for a reference monument, bears N. 60°00' W., 60.00 ft. dist., with brass cap mkd. RM T24N R27E S26 60.0 FT. TO COR 2003 and an arrow pointing to the corner. Deposit a magnet in a white plastic case at the base of the stainless steel post.</p> <p>Deposit a magnet in a white plastic case at the base of the stainless steel post at the sec. cor.</p> <p>Cor. is located 24 lks. S. of the center of Navajo Route 9355, a graded road, 15 ft. wide, bears N. 30° E. and S. 30° W.</p> <p>Land, rolling and broken. Soil, sand and sandy clay. Timber, light ponderosa pine, piñon and juniper; undergrowth, sagebrush, scrub oak and native grasses.</p> <hr style="width: 50%; margin-left: 0;"/> <p>West, bet. secs. 26 and 35.</p> <p>Over rolling and broken land.</p>	T 24 N R 27 E		S 26	S 25	S 35	S 36
T 24 N R 27 E							
S 26	S 25						
S 35	S 36						
33.50	<p>Navajo Route 9352, a graded road, 20 ft. wide, bears S. 5° E. and N. 5° W.</p>						
40.00	<p>Point for the 1/4 sec. cor. of secs. 26 and 35.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p>						

Survey of the Sectional Correction Line,  
T. 24 N., R. 27 E., Gila and Salt River Meridian, Arizona

CHAINS	
	<p style="text-align: center;">T 24 N R 27 E S 26 1/4 ——— S 35</p> <p style="text-align: center;">2003</p>
80.00	<p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p> <p>Point for the cor. of secs. 26, 27, 34 and 35.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T 24 N R 27 E S 27   S 26 —————  S 34   S 35</p> <p style="text-align: center;">2003</p> <p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p> <p>Land, rolling and broken. Soil, sand and sandy clay. Timber, piñon and juniper; undergrowth, sagebrush, scrub oak and native grasses.</p>
	<hr/> <p>West, bet. secs. 27 and 34.</p> <p>Over rolling and broken land.</p>
40.00	<p>Point for the 1/4 sec. cor. of secs. 27 and 34.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p>
	<p style="text-align: center;">T 24 N R 27 E S 27 1/4 ——— S 34</p> <p style="text-align: center;">2003</p> <p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p>
80.00	<p>Point for the cor. of secs. 27, 28, 33 and 34.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p>

**Survey of the Sectional Correction Line,  
T. 24 N., R. 27 E., Gila and Salt River Meridian, Arizona**

CHAINS									
	<table border="0"> <tr> <td>T 24 N</td> <td>R 27 E</td> </tr> <tr> <td>S 28</td> <td>S 27</td> </tr> <tr> <td>S 33</td> <td>S 34</td> </tr> </table>	T 24 N	R 27 E	S 28	S 27	S 33	S 34		
T 24 N	R 27 E								
S 28	S 27								
S 33	S 34								
	2003								
	Deposit a magnet in a white plastic case at the base of the stainless steel post.								
	Cor. is located 2.65 chs. E. of Oak Ridge Wash, 30 ft. wide, 3 ft. deep, drains S. 45° W.								
	Land, rolling and broken. Soil, sand and sandy clay. Timber, piñon and juniper; undergrowth, sagebrush, scrub oak and native grasses.								
	<hr/>								
	West, bet. secs. 28 and 33.								
	Over rolling and broken land.								
40.00	Point for the 1/4 sec. cor. of secs. 28 and 33.								
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.								
	<table border="0"> <tr> <td>T 24 N</td> <td>R 27 E</td> </tr> <tr> <td>S 28</td> <td></td> </tr> <tr> <td>1/4</td> <td>—</td> </tr> <tr> <td>S 33</td> <td></td> </tr> </table>	T 24 N	R 27 E	S 28		1/4	—	S 33	
T 24 N	R 27 E								
S 28									
1/4	—								
S 33									
	2003								
	Deposit a magnet in a white plastic case at the base of the stainless steel post.								
80.00	Point for the cor. of secs. 28, 29, 32 and 33.								
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.								
	<table border="0"> <tr> <td>T 24 N</td> <td>R 27 E</td> </tr> <tr> <td>S 29</td> <td>S 28</td> </tr> <tr> <td>S 32</td> <td>S 33</td> </tr> </table>	T 24 N	R 27 E	S 29	S 28	S 32	S 33		
T 24 N	R 27 E								
S 29	S 28								
S 32	S 33								
	2003								
	Deposit a magnet in a white plastic case at the base of the stainless steel post.								

**Survey of the Sectional Correction Line,  
T. 24 N., R. 27 E., Gila and Salt River Meridian, Arizona**

CHAINS	
	<p>Land, rolling and broken. Soil, sand and sandy clay. Timber, piñon and juniper; undergrowth, sagebrush, scrub oak and native grasses.</p> <hr/> <p>West, bet. secs. 29 and 32.</p> <p>Over rolling and broken land.</p>
40.00	<p>Point for the 1/4 sec. cor. of secs. 29 and 32.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center;"> <p>T 24 N R 27 E S 29 1/4 ——— S 32</p> <p>2003</p> </div> <p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p>
64.50	<p>Wide Ruin Wash, 30 ft. wide, 8 ft. deep, drains S. 35° E.</p>
80.00	<p>Point for the cor. of secs. 29, 30, 31 and 32.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center;"> <p>T 24 N R 27 E S 30   S 29 S 31   S 32</p> <p>2003</p> </div> <p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p>
	<p>Land, rolling and broken. Soil, sand and sandy clay. Timber, piñon and juniper; undergrowth, sagebrush, scrub oak and native grasses.</p> <hr/> <p>West, bet. secs. 30 and 31.</p> <p>Over rolling and broken land.</p>
40.00	<p>Point for the 1/4 sec. cor. of secs. 30 and 31.</p>

Survey of the Sectional Correction Line,  
T. 24 N., R. 27 E., Gila and Salt River Meridian, Arizona

CHAINS	<p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T 24 N R 27 E S 30 1/4 ——— S 31</p> <p style="text-align: center;">2003</p> <p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p> <p>57.36 A brass tablet, 3 ins. diam., set flush in a concrete collar, 6 ins. diam., firmly set, projecting 8 ins. above ground, bears North, 1.63 chs. dist., with top mkd. BIA ROADS 19, and witnessed by an angle iron, to the N., firmly set, projecting 24 above ground with side mkd. PT 973+46.07.</p> <p>57.49 E. right-of-way fence of U. S. Highway 191, barbed wire, 4 strands, parallels highway.</p> <p>59.03 U. S. Highway No. 191, asphalt pavement, 28 ft. wide, bears N. 5° E. and S. 5° W.</p> <p>60.38 A brass tablet, 3 ins. diam., set flush in a concrete collar, 6 ins. diam., firmly set, projecting 4 ins. above ground, bears North, 1.90 chs. dist., with top mkd. BIA ROADS 19, and witness by an angle iron, to the N., firmly set projecting 24 ins. above ground with side mkd. PT 973+46.07.</p> <p>60.56 W. right-of-way fence of U. S. Highway 191, barbed wire, 4 strands, parallels highway.</p> <p>77.54 Point for the closing cor. of secs. 30 and 31, at the intersection with the E. bdy. of T. 24 N., R. 26 E.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T 24 N   T 24 N R 26 E   S 30 —————CC S 36   S 31   R 27 E</p> <p style="text-align: center;">2003</p> <p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p>
--------	--

**Survey of the Sectional Correction Line,  
T. 24 N., R. 27 E., Gila and Salt River Meridian, Arizona**

CHAINS

From this cor. point, the cor. of secs. 25 and 36 only, T. 24 N., R. 26 E., bears North, 8.35 chs. dist., monumented with a stainless steel post, 2 1/2 ins. diam., with brass cap, set and mkd. as described in the field notes of the survey of the E. bdy., T. 24 N., R. 26 E., executed concurrently under this same group.

From this same cor. point, the 1/4 sec. cor. of sec. 36 only, T. 24 N., R. 26 E., bears South, 31.65 chs. dist., monumented with a stainless steel post, 2 1/2 ins. diam., with brass cap, set and mkd. as described in the field notes of the survey of the E. bdy., T. 24 N., R. 26 E., executed concurrently under this same group.

Land, rolling and broken.  
Soil, sand and sandy clay.  
Timber, piñon and juniper; undergrowth, sagebrush, rabbit brush and native grasses.

---

Point for the 1/4 sec. cor. of secs. 31 only, T. 24 N., R. 27 E., at 40 chs. dist. in southing from the closing cor. of secs. 30 and 31, on the W. bdy. of sec. 31.

Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.

T 24 N  
R 26 E    R 27 E  
          |  
          1/4 S 31  
          2003

Deposit a magnet in a white plastic case at the base of the stainless steel post.

From this cor. point, the 1/4 sec. cor. of sec. 36 only, T. 24 N., R. 26 E., bears North, 8.35 chs. dist.

From this same cor. point, the cor. of Tps. 23 and 24 N., Rs. 26 and 27 E., bears South, 31.65 chs. dist., monumented with a stainless steel post, 2 1/2 ins. diam., with brass cap, set and mkd. as described in the field notes of the dependent resurvey of the E. bdy., T. 23 N., R. 26 E., executed concurrently under this same group.

---

**Survey of the Subdivisional Lines,  
T.24.N., R.27.E., Gila and Salt River Meridian, Arizona**

---

From the cor. of secs. 25, 26, 35 and 36, on the Sectional Correction Line, hereinbefore described.

Survey of the Subdivisional Lines,  
T. 24 N., R. 27 E., Gila and Salt River Meridian, Arizona

CHAINS	
	<p>S. 0°01' E., bet. secs. 35 and 36.</p> <p>Over rolling land.</p>
40.00	<p>Point for the 1/4 sec. cor. of secs. 35 and 36.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T 24 N R 27 E 1/4 S 35   S 36</p> <p style="text-align: center;">2003</p> <p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p>
78.60	<p>The cor. of secs. 1, 2, 35 and 36, on the S. bdy. of the Tp., monumented with a stainless steel post, 2 1/2 ins. diam., with brass cap, set and mkd. as described in the field notes of the dependent resurvey of the N. bdy., T. 23 N., R. 27 E., executed concurrently under this same group.</p> <p>Land, rolling and broken. Soil, sand and rocky clay. Timber, piñon and juniper; undergrowth, sagebrush, scrub oak and native grasses.</p> <hr/> <p>From the cor. of secs. 25, 26, 35 and 36, on the Sectional Correction Line, hereinbefore described.</p> <p>N. 0°01' W., bet. secs. 25 and 26.</p> <p>Over rolling land.</p>
40.00	<p>Point for the 1/4 sec. cor. of secs. 25 and 26.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T 24 N R 27 E 1/4 S 26   S 25</p> <p style="text-align: center;">2003</p> <p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p>
54.10	<p>Apache County Road C422, a graded road, 16 ft. wide, bears S. 80° E. and N. 80° W.</p>



**Survey of the Subdivisional Lines,  
T. 24 N., R. 27 E., Gila and Salt River Meridian, Arizona**

CHAINS									
80.00	<p>Point for the cor. of secs. 23, 24, 25 and 26.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center;"> <table style="margin: auto;"> <tr> <td>T 24 N</td> <td>R 27 E</td> </tr> <tr> <td style="border-right: 1px solid black;">S 23</td> <td>S 24</td> </tr> <tr> <td style="border-right: 1px solid black;">S 26</td> <td>S 25</td> </tr> </table> <p>2003</p> </div> <p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p> <p>Land, rolling. Soil, sand and sandy clay. Timber, ponderosa pine, piñon and juniper; undergrowth, sagebrush, scrub oak and native grasses.</p> <hr/> <p>From the cor. of secs. 24 and 25 only, on the E. bdy. of the Tp. hereinbefore described.</p> <p>West, bet. secs. 24 and 25.</p> <p>Over rolling and broken land.</p>	T 24 N	R 27 E	S 23	S 24	S 26	S 25		
T 24 N	R 27 E								
S 23	S 24								
S 26	S 25								
30.10	<p>Navajo Route 9355, a graded road, 25 ft. wide, bears N. 70° E. and S. 70° W.</p>								
40.00	<p>Point for the 1/4 sec. cor. of secs. 24 and 25.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center;"> <table style="margin: auto;"> <tr> <td>T 24 N</td> <td>R 27 E</td> </tr> <tr> <td></td> <td>S 24</td> </tr> <tr> <td>1/4</td> <td style="border-top: 1px solid black;">———</td> </tr> <tr> <td></td> <td>S 25</td> </tr> </table> <p>2003</p> </div> <p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p>	T 24 N	R 27 E		S 24	1/4	———		S 25
T 24 N	R 27 E								
	S 24								
1/4	———								
	S 25								
80.00	<p>The cor. of secs. 23, 24, 25 and 26.</p>								

**Survey of the Subdivisional Lines,  
T. 24 N., R. 27 E., Gila and Salt River Meridian, Arizona**

CHAINS	<p>Land, rolling and broken. Soil, sandy clay and rocky. Timber, light ponderosa pine, piñon and juniper; undergrowth, sagebrush, scrub oak and native grasses.</p> <hr/> <p>N. 0°01' W., bet. secs. 23 and 24.</p> <p>Over rolling and broken land.</p> <p>17.30 Oak Ridge Wash, 30 ft. wide, 5 ft. deep, drains N. 30° W.</p> <p>40.00 Point for the 1/4 sec. cor. of secs. 23 and 24.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p align="center">T 24 N R 27 E 1/4 S 23   S 24</p> <p align="center">2003</p> <p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p> <p>80.00 Point for the cor. of secs. 13, 14, 23 and 24.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p align="center">T 24 N R 27 E S 14   S 13 ----- S 23   S 24</p> <p align="center">2003</p> <p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p> <p>Cor. is located 60 lks. S. of a wash, 12 ft. wide, 1 ft. deep, drains S. 45° E.</p> <p>Land, rolling and broken. Soil, sand clay and rocky. Timber, ponderosa pine, piñon and juniper; undergrowth, sagebrush, scrub oak and native grasses.</p> <hr/> <p>From the cor. of secs. 13 and 24 only, on the E. bdy. of the Tp., hereinbefore described.</p> <p>West, bet. secs. 13 and 24.</p>
--------	--

**Survey of the Subdivisional Lines,  
T. 24 N., R. 27 E., Gila and Salt River Meridian, Arizona**

CHAINS	
40.00	<p>Over rolling and broken land.</p> <p>Point for the 1/4 sec. cor. of secs. 13 and 24.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T 24 N R 27 E S 13 1/4 ——— S 24</p> <p style="text-align: center;">2003</p> <p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p>
80.00	<p>The cor. of secs. 13, 14, 23 and 24.</p> <p>Land, rolling and broken. Soil, sand clay and rocky. Timber, ponderosa pine, piñon and juniper; undergrowth, sagebrush scrub oak and native grasses.</p> <hr/> <p>N. 0°01' W., bet. secs. 13 and 14.</p> <p>Over rolling and broken land.</p>
40.00	<p>Point for the 1/4 sec. cor. of secs. 13 and 14.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T 24 N R 27 E 1/4 S 14   S 13</p> <p style="text-align: center;">2003</p> <p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p>
80.00	<p>Point for the cor. of secs. 11, 12, 13 and 14.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p>

**Survey of the Subdivisional Lines,  
T. 24 N., R. 27 E., Gila and Salt River Meridian, Arizona**

CHAINS							
	<table style="margin: auto; border-collapse: collapse;"> <tr> <td style="padding: 0 10px;">T 24 N</td> <td style="padding: 0 10px;">R 27 E</td> </tr> <tr> <td style="padding: 0 10px; border-right: 1px solid black;">S 11</td> <td style="padding: 0 10px;">S 12</td> </tr> <tr> <td style="padding: 0 10px; border-right: 1px solid black;">S 14</td> <td style="padding: 0 10px;">S 13</td> </tr> </table>	T 24 N	R 27 E	S 11	S 12	S 14	S 13
T 24 N	R 27 E						
S 11	S 12						
S 14	S 13						
	2003						
	<p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p> <p>Land, rolling and broken. Soil, sand and sandy clay. Timber, ponderosa pine, piñon and juniper; undergrowth, sagebrush scrub oak and native grasses.</p> <hr/> <p>From the cor. of secs. 12 and 13 only, on the E. bdy. of the Tp., hereinbefore described.</p> <p>West, bet. secs. 12 and 13.</p> <p>Over rolling and broken land.</p>						
40.00	<p>Point for the 1/4 sec. cor. of secs. 12 and 13.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p>						
	<table style="margin: auto; border-collapse: collapse;"> <tr> <td style="padding: 0 10px;">T 24 N</td> <td style="padding: 0 10px;">R 27 E</td> </tr> <tr> <td style="padding: 0 10px;"></td> <td style="padding: 0 10px;">S 12</td> </tr> <tr> <td style="padding: 0 10px;">1/4</td> <td style="padding: 0 10px; border-top: 1px solid black;">S 13</td> </tr> </table>	T 24 N	R 27 E		S 12	1/4	S 13
T 24 N	R 27 E						
	S 12						
1/4	S 13						
	2003						
80.00	<p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p> <p>The cor. of secs. 11, 12, 13 and 14.</p> <p>Land, rolling and broken. Soil, sand clay and rocky. Timber, ponderosa pine, piñon and juniper; undergrowth sagebrush, scrub oak and native grasses.</p> <hr/> <p>N. 0°01' W., bet. secs. 11 and 12.</p> <p>Over rolling land.</p>						
40.00	<p>Point for the 1/4 sec. cor. of secs. 11 and 12.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p>						

**Survey of the Subdivisional Lines,  
T. 24 N., R. 27 E., Gila and Salt River Meridian, Arizona**

CHAINS	
	T 24 N R 27 E 1/4 S 11   S 12  2003
	Deposit a magnet in a white plastic case at the base of the stainless steel post.
80.00	Point for the cor. of secs. 1, 2, 11 and 12.
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 23 ins. in the ground, to sandstone bedrock, with brass cap mkd.
	T 24 N R 27 E S 2   S 1 S 11   S 12  2003
	Deposit a magnet in a white plastic case at the base of the stainless steel post.
	Land, rolling. Soil, sand and sand clay. Timber, piñon and juniper; undergrowth, sagebrush, rabbit brush and native grasses.
	From the cor. of secs. 1 and 12 only, on the E. bdy. of the Tp., hereinbefore described.
	West, bet. secs. 1 and 12.
	Over rolling and broken land.
40.00	Point for the 1/4 sec. cor. of secs. 1 and 12.
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.
	T 24 N R 27 E S 1 1/4 ——— S 12  2003
	Deposit a magnet in a white plastic case at the base of the stainless steel post.
80.00	The cor. of secs. 1, 2, 11 and 12.

**Survey of the Subdivisional Lines,  
T. 24 N., R. 27 E., Gila and Salt River Meridian, Arizona**

CHAINS	
	<p>Land, rolling and broken. Soil, sandy clay and rocky. Timber, ponderosa pine, piñon and juniper; undergrowth, sagebrush, scrub oak and native grasses.</p> <hr/> <p>N. 0°01' W., bet. secs. 1 and 2.</p> <p>Over rolling and broken land.</p>
40.00	<p>Point for the 1/4 sec. cor. of secs. 1 and 2.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T 24 N R 27 E 1/4 S 2   S 1  2003</p> <p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p>
74.60	<p>Navajo Route 28, a graded road, 25 ft. wide, bears N. 85° E. and S. 85° W.</p>
78.87	<p>Point for the closing cor. of secs. 1 and 2, at the intersection with Sixth Standard Parallel North, on the N. bdy. of the Tp.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T 25 N R 27 E S 34 ----- S 2   S 1 T 24 N R 27 E CC  2003</p> <p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p> <p>From this cor. point, the stan. cor. of secs. 34 and 35, T. 25 N., R. 27 E., bears East, 8.19 chs. dist., monumented with a stainless steel post, 2 1/2 ins. diam., with brass cap, set mkd. and witnessed as described in the field notes of the dependent resurvey of the Sixth Standard Parallel North (south boundary), T. 25 E., R. 27 E., executed concurrently under this same group.</p>

**Survey of the Subdivisional Lines,  
T. 24 N., R. 27 E., Gila and Salt River Meridian, Arizona**

CHAINS	<p>From this same cor. point, the stan. 1/4 sec. cor. of sec. 34, T. 25 N., R. 27 E., bears West, 31.82 chs. dist., monumented with an iron post, 1 in. diam., with brass cap, set and mkd. as described in the field notes of the dependent resurvey of the Sixth Standard Parallel North (south boundary), T. 25 N., R. 27 E., executed concurrently under this same group.</p> <p>Land, rolling. Soil, sand clay and rocky. Timber, ponderosa pine, piñon and juniper; undergrowth, sagebrush, scrub oak and native grasses.</p> <hr/> <p>Point for the 1/4 sec. cor. of sec. 1 only, T. 24 N., R. 27 E., at midpoint on the N. bdy. of sec. 1.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T 25 N R 27 E ----- 1/4 S 1 T 24 N R 27 E</p> <p style="text-align: center;">2003</p> <p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p> <p>From this cor. point, the stan. 1/4 sec. cor. of sec. 35, T 25 N., R. 27 E., bears East, 8.20 chs. dist., hereinbefore described.</p> <p>From this same cor. point, the stan. cor. of secs. 34 and 35, bears West, 31.81 chs. dist.</p> <hr/> <p>From the cor. of secs. 26, 27, 34 and 35, on the Sectional Correction Line, hereinbefore described.</p> <p>S. 0°01' E., bet. secs. 34 and 35.</p> <p>Over rolling and broken land.</p>
40.00	<p>Point for the 1/4 sec. cor. of secs. 34 and 35.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p>

**Survey of the Subdivisional Lines,  
T. 24 N., R. 27 E., Gila and Salt River Meridian, Arizona**

CHAINS	
	T 24 N R 27 E 1/4 S 34   S 35  2003  Deposit a magnet in a white plastic case at the base of the stainless steel post.
77.20	The cor. of secs. 2, 3, 34 and 35, on the S. bdy. of the Tp., monumented with a stainless steel post, 2 1/2 ins. diam., with brass cap, set and mkd. as described in the field notes of the dependent resurvey of the N. bdy., T. 23 N., R. 27 E., executed concurrently under this same group.  Land, rolling and broken. Soil, sand and sandy clay. Timber, piñon and juniper; undergrowth, sagebrush, scrub oak and native grasses.
	<hr/> From the cor. of secs. 26, 27, 34 and 35, on the Sectional Correction Line, hereinbefore described.  N. 0°01' W., bet. secs. 26 and 27.  Over rolling and broken land.
40.00	Point for the 1/4 sec. cor. of secs. 26 and 27.  Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.
	T 24 N R 27 E 1/4 S 27   S 26  2003  Deposit a magnet in a white plastic case at the base of the stainless steel post.
67.50	Oak Ridge Wash, 40 ft. wide, 4 ft. deep, drains S. 85° W.
80.00	Point for the cor. of secs. 22, 23, 26 and 27.  Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.



Survey of the Subdivisional Lines,  
T. 24 N., R. 27 E., Gila and Salt River Meridian, Arizona

CHAINS									
	<table style="margin-left: auto; margin-right: auto;"> <tr> <td>T 24 N</td> <td>R 27 E</td> </tr> <tr> <td style="border-right: 1px solid black;">S 22</td> <td>S 23</td> </tr> <tr> <td style="border-right: 1px solid black;">S 27</td> <td>S 26</td> </tr> </table>	T 24 N	R 27 E	S 22	S 23	S 27	S 26		
T 24 N	R 27 E								
S 22	S 23								
S 27	S 26								
	2003								
	Deposit a magnet in a white plastic case at the base of the stainless steel post.								
	Land, rolling. Soil, sand and sandy clay. Timber, piñon and juniper; undergrowth, sagebrush scrub oak and native grasses.								
	-----								
	From the cor. of secs. 23, 24, 25 and 26.								
	West, bet. secs. 23 and 26.								
	Over rolling and broken land.								
34.30	Navajo Route 9352, a graded road, 20 ft. wide, bears S. 5° E. and N. 5° W.								
35.50	Oak Ridge Wash, 40 ft. wide, 2 ft. deep, drains S. 55° W.								
40.00	Point for the 1/4 sec. cor. of secs. 23 and 26.								
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.								
	<table style="margin-left: auto; margin-right: auto;"> <tr> <td>T 24 N</td> <td>R 27 E</td> </tr> <tr> <td></td> <td>S 23</td> </tr> <tr> <td></td> <td>1/4 -----</td> </tr> <tr> <td></td> <td>S 26</td> </tr> </table>	T 24 N	R 27 E		S 23		1/4 -----		S 26
T 24 N	R 27 E								
	S 23								
	1/4 -----								
	S 26								
	2003								
	Deposit a magnet in a white plastic case at the base of the stainless steel post.								
	Cor. is located 1.65 chs. N. of Oak Ridge Wash, 30 ft. wide, 3 ft. deep, drains N. 80° W.								
80.00	The cor. of secs. 22, 23, 26 and 27.								
	Land, rolling and broken. Soil, sand and sandy clay. Timber, ponderosa pine, piñon and juniper; undergrowth, sagebrush, scrub oak and native grasses.								
	-----								
	N. 0°01' W., bet. secs. 22 and 23.								

Survey of the Subdivisional Lines,  
T. 24 N., R. 27 E., Gila and Salt River Meridian, Arizona

CHAINS	
	Over rolling and broken land.
40.00	Point for the 1/4 sec. cor. of secs. 22 and 23.  Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.  <div style="text-align: center;">           T 24 N R 27 E                  1/4            S 22   S 23              2003         </div>
	Deposit a magnet in a white plastic case at the base of the stainless steel post.
80.00	Point for the cor. of secs. 14, 15, 22 and 23.  Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 14 ins. in the ground, to sandstone bedrock, in a mound of stone, 3 ft. base to top, with brass cap mkd.  <div style="text-align: center;">           T 24 N R 27 E            S 15   S 14            S 22   S 23              2003         </div>
	Deposit a magnet in a white plastic case at the base of the stainless steel post.
	Cor. is located 1.25 chs. E. of a trail road, bears N. 20° E. and S. 20° W.
	Land, rolling and broken. Soil, sand and sandy clay. Timber, piñon and juniper; undergrowth, sagebrush, scrub oak and native grasses.
	From the cor. of secs. 13, 14, 23 and 24.
	West, bet. secs. 14 and 23.
	Over rolling and broken land.
40.00	Point for the 1/4 sec. cor. of secs. 14 and 23.  Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.

Survey of the Subdivisional Lines,  
T. 24 N., R. 27 E., Gila and Salt River Meridian, Arizona

CHAINS	
	T 24 N R 27 E S 14 1/4 ——— S 23  2003
	Deposit a magnet in a white plastic case at the base of the stainless steel post.
41.30	Power line, bears S. 5° E. and N. 5° W.
42.40	Navajo Route 9352, a graded road, 20 ft. wide, bears S. 5° E. and N. 5° W.
80.00	The cor. of secs. 14, 15, 22 and 23.  Land, rolling and broken. Soil, sand and sandy clay. Timber, ponderosa pine, piñon and juniper; undergrowth, sagebrush, scrub oak and native grasses.
	—————
	N. 0°01' W., bet. secs. 14 and 15.  Over rolling land.
40.00	Point for the 1/4 sec. cor. of secs. 14 and 15.  Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.
	T 24 N R 27 E 1/4 S 15   S 14  2003
	Deposit a magnet in a white plastic case at the base of the stainless steel post.
	Cor. is located 1.15 chs. SE of a curve to left, in a trail road, bears N. 50° E. and S. 80° W.
78.50	Trail road, bears S. 65° E. and N. 65° W.
80.00	Point for the cor. of secs. 10, 11, 14 and 15.  Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.

**Survey of the Subdivisional Lines,  
T. 24 N., R. 27 E., Gila and Salt River Meridian, Arizona**

CHAINS							
	<table style="margin: auto; border-collapse: collapse;"> <tr> <td style="padding: 0 10px;">T 24 N</td> <td style="padding: 0 10px;">R 27 E</td> </tr> <tr> <td style="padding: 0 10px; border-right: 1px solid black;">S 10</td> <td style="padding: 0 10px;">S 11</td> </tr> <tr> <td style="padding: 0 10px; border-right: 1px solid black;">S 15</td> <td style="padding: 0 10px;">S 14</td> </tr> </table>	T 24 N	R 27 E	S 10	S 11	S 15	S 14
T 24 N	R 27 E						
S 10	S 11						
S 15	S 14						
	2003						
	Deposit a magnet in a white plastic case at the base of the stainless steel post.						
	Land, rolling. Soil, sand and sandy clay. Timber, piñon and juniper; undergrowth, sagebrush, scrub oak and native grasses.						
	From the cor. of secs. 11, 12, 13 and 14.						
	West, bet. secs. 11 and 14.						
	Over rolling and broken land.						
40.00	Point for the 1/4 sec. cor. of secs. 11 and 14.						
	Set a stainless steel post, 28 ins. long, 2 1/4 ins. diam., 24 ins. in the ground, with brass cap mkd.						
	<table style="margin: auto; border-collapse: collapse;"> <tr> <td style="padding: 0 10px;">T 24 N</td> <td style="padding: 0 10px;">R 27 E</td> </tr> <tr> <td></td> <td style="padding: 0 10px;">S 11</td> </tr> <tr> <td style="padding: 0 10px;">1/4</td> <td style="padding: 0 10px; border-top: 1px solid black;">S 14</td> </tr> </table>	T 24 N	R 27 E		S 11	1/4	S 14
T 24 N	R 27 E						
	S 11						
1/4	S 14						
	2003						
	Deposit a magnet in a white plastic case at the base of the stainless steel post.						
44.90	Navajo Route 9352, a graded road, 25 ft. wide, bears North and South.						
80.00	The cor. of secs. 10, 11, 14 and 15.						
	Land, rolling. Soil, sand and sandy clay. Timber, piñon and juniper; undergrowth, sagebrush and native grasses.						
	N. 0°01' W., bet. secs. 10 and 11.						
	Over rolling land.						
40.00	Point for the 1/4 sec. cor. of secs. 10 and 11.						

Survey of the Subdivisional Lines,  
T. 24 N., R. 27 E., Gila and Salt River Meridian, Arizona

CHAINS	
	<p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T 24 N R 27 E 1/4 S 10   S 11</p> <p style="text-align: center;">2003</p> <p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p> <p>Cor. is located 65 lks. N. of a wash, 3 ft. wide, 1 ft. deep, drains N. 70° W.</p>
80.00	<p>Point for the cor. of secs. 2, 3, 10 and 11.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T 24 N R 27 E S 3   S 2 S 10   S 11</p> <p style="text-align: center;">2003</p> <p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p> <p>Land, rolling. Soil, sand and sandy clay. Timber, piñon and juniper; undergrowth, sagebrush and native grasses.</p> <hr/> <p>From the cor. of secs. 1, 2, 11 and 12.</p> <p>West, bet. secs. 2 and 11.</p> <p>Over rolling land.</p>
40.00	<p>Point for the 1/4 sec. cor. of secs. 2 and 11.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T 24 N R 27 E S 2 1/4 ——— S 11</p> <p style="text-align: center;">2003</p>

**Survey of the Subdivisional Lines,  
T. 24 N., R. 27 E., Gila and Salt River Meridian, Arizona**

CHAINS	
	<p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p> <p>Cor. is located 40 lks. S. of a trail road, bears S. 30° E. and N. 30° W.</p>
52.10	Navajo Route 9352, a graded road, 25 ft. wide, bears S. 15° E. and N. 15° W.
80.00	The cor. of secs. 2, 3, 10 and 11.
	<p>Land, rolling Soil, sand and sandy clay. Timber, piñon and juniper; undergrowth, sagebrush and native grasses.</p> <hr/> <p>N. 0°01' W., bet. secs. 2 and 3.</p> <p>Over rolling and broken land.</p>
40.00	<p>Point for the 1/4 sec. cor. of secs. 2 and 3.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T 24 N R 27 E 1/4 S 3   S 2  2003</p>
	<p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p>
44.60	Navajo Route 9352, a graded road, 20 ft. wide, bears S. 55° E. and N. 55° W.
69.20	Navajo Route 28, a graded road, 25 ft. wide, bears N. 85° E. and S. 85° W.
78.90	<p>Point for the closing cor. of secs. 2 and 3, at the intersection with the Sixth Standard Parallel North, on the N. bdy. of the Tp.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p>

**Survey of the Subdivisional Lines,  
T. 24 N., R. 27 E., Gila and Salt River Meridian, Arizona**

CHAINS

T 25 N R 27 E  
S 33  
-----  
S 3 | S 2  
T 24 N R 27 E  
CC

2003

Deposit a magnet in a white plastic case at the base of the stainless steel post.

From this cor. point, the stan. cor. of secs. 33 and 34, T. 25 N., R. 27 E., bears S. 89°59' E., 8.19 chs. dist., monumented with a iron post, 2 ins. diam., with brass cap, set and mkd. as described in the field notes of the dependent resurvey of the Sixth Standard Parallel North (south boundary), T. 25 N., R. 27 E., executed concurrently under this same group.

From this same cor. point, the stan. 1/4 sec. cor. of sec. 33, T. 25 N., R. 27 E., bears N. 89°59' W., 31.87 chs. dist., monumented with a stainless steel post, 2 1/2 ins. diam., with brass cap, set and mkd. as described in the field notes of the dependent resurvey of the Sixth Standard Parallel North (south boundary), T. 25 N., R. 27 E., executed concurrently under this same group.

Land, rolling.

Soil, sand and sandy clay.

Timber, piñon and juniper; undergrowth, sagebrush scrub oak and native grasses.

---

Point for the 1/4 sec. cor. of sec. 2 only, T. 24 N, R. 27 E., at midpoint on the N. bdy. of sec. 2.

Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.

T 25 N R 27 E  
-----  
1/4 S 2  
T 24 N R 27 E

2003

Deposit a magnet in a white plastic case at the base of the stainless steel post.

**Survey of the Subdivisional Lines,  
T. 24 N., R. 27 E., Gila and Salt River Meridian, Arizona**

CHAINS	
	<p>From this cor. point, the stan. 1/4 sec. cor. of sec. 34, T. 25 N., R. 27 E., bears S. 89°58' E., 8.185 chs. dist.</p> <p>From this same cor. point, the stan. cor. of secs. 33 and 34, T. 25 N., R. 27 E., bears N. 89°58' W., 31.815 chs. dist.,</p> <hr/> <p>From the cor. of secs. 27, 28, 33 and 34, on the Sectional Correction Line, hereinbefore described.</p> <p>S. 0°02' E., bet. secs. 33 and 34.</p> <p>Over rolling and broken land.</p>
40.00	<p>Point for the 1/4 sec. cor. of secs. 33 and 34.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T 24 N R 27 E 1/4 S 33   S 34</p> <p style="text-align: center;">2003</p> <p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p>
45.90	<p>The SE rim of a mesa, bears N. 25° E. and S. 25° W, descend into valley.</p>
64.00	<p>Enter Oak Ridge Wash, 60 ft. wide, 2 ft. deep, drains S., thence through the wash.</p>
68.00	<p>Leave Oak Ridge Wash, 30 ft. wide, 1 ft. deep, drains S. 30° W, ascend out of valley.</p>
72.20	<p>N. rim of a mesa, bears S. 85° E. and N. 85° W.</p>
75.80	<p>The cor. of secs. 3, 4, 33 and 34, on the S. bdy. of the Tp., monumented with a stainless steel post, 2 1/2 ins. diam., with brass cap, set and mkd. as described in the field notes of the dependent resurvey of the N. bdy., T. 23 N., R. 25 E., executed concurrently under this same group.</p> <p>Land, rolling and broken. Soil, sand and sandy clay. Timber, piñon and juniper; undergrowth, sagebrush. scrub oak and native grasses.</p> <hr/> <p>From the cor. of secs. 27, 28, 33 and 34, on the Sectional Correction Line, hereinbefore described.</p>



**Survey of the Subdivisional Lines,  
T. 24 N., R. 27 E., Gila and Salt River Meridian, Arizona**

CHAINS	<p>N. 0°02' W., bet. secs. 27 and 28.</p> <p>Over rolling and broken land.</p> <p>7.50 Oak Ridge Wash, 30 ft. wide, 2 ft. deep, drains S. 40° W.</p> <p>40.00 Point for the 1/4 sec. cor. of secs. 27 and 28.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p align="center">T 24 N R 27 E 1/4 S 28   S 27</p> <p align="center">2003</p> <p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p> <p>80.00 Point for the cor. of secs. 21, 22, 27 and 28.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p align="center">T 24 N R 27 E S 21   S 22 ----- S 28   S 27</p> <p align="center">2003</p> <p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p> <p>Land, rolling and broken. Soil, sand and rocky clay. Timber, piñon and juniper; undergrowth, sagebrush, scrub oak and native grasses.</p> <hr/> <p>From the cor. of secs. 22, 23, 26 and 27</p> <p>West, bet. secs. 22 and 27.</p> <p>Over rolling and broken land.</p> <p>40.00 Point for the 1/4 sec. cor. of secs. 22 and 27.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p>
--------	---

Survey of the Subdivisional Lines,  
T. 24 N., R. 27 E., Gila and Salt River Meridian, Arizona

CHAINS	
	T 24 N R 27 E S 22 1/4 ——— S 27  2003
	from which  The NE cor. of an L-shaped wood frame house, 40 x 36 ft., bears S. 81 1/2° W., 2.33 chs. dist., long side bears S. 40° W.
80.00	Deposit a magnet in a white plastic case at the base of the stainless steel post.  The cor. of secs. 21, 22, 27 and 28.  Land, rolling and broken. Soil, sand and sandy clay. Timber, piñon and juniper; undergrowth, sagebrush, scrub oak and native grasses.
	<hr/> N. 0°02' W., bet. secs. 21 and 22.  Over rolling land.
40.00	Point for the 1/4 sec. cor. of secs. 21 and 22.  Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.
	T 24 N R 27 E 1/4 S 21   S 22  2003
	Deposit a magnet in a white plastic case at the base of the stainless steel post.
41.25	Trail road, bears S. 70° E. and N. 70° W.
80.00	Point for the cor. of secs. 15, 16, 21 and 22.  Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.

Survey of the Subdivisional Lines,  
T. 24 N., R. 27 E., Gila and Salt River Meridian, Arizona

CHAINS									
	<table style="margin: auto;"> <tr> <td>T 24 N</td> <td>R 27 E</td> </tr> <tr> <td>S 16</td> <td>S 15</td> </tr> <tr> <td>S 21</td> <td>S 22</td> </tr> </table>	T 24 N	R 27 E	S 16	S 15	S 21	S 22		
T 24 N	R 27 E								
S 16	S 15								
S 21	S 22								
	2003								
	Deposit a magnet in a white plastic case at the base of the stainless steel post.								
	Land, rolling and broken. Soil, sand and sandy clay. Timber, piñon and juniper; undergrowth, sagebrush scrub oak and native grasses.								
	_____								
	From the cor. of secs. 14, 15, 22 and 23.								
	West, bet. secs. 15 and 22.								
	Over rolling and broken land.								
40.00	Point for the 1/4 sec. cor. of secs. 15 and 22.								
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.								
	<table style="margin: auto;"> <tr> <td>T 24 N</td> <td>R 27 E</td> </tr> <tr> <td></td> <td>S 15</td> </tr> <tr> <td>1/4</td> <td>_____</td> </tr> <tr> <td></td> <td>S 22</td> </tr> </table>	T 24 N	R 27 E		S 15	1/4	_____		S 22
T 24 N	R 27 E								
	S 15								
1/4	_____								
	S 22								
	2003								
	Deposit a magnet in a white plastic case at the base of the stainless steel post.								
80.00	The cor. of secs. 15, 16, 21 and 22.								
	Land, rolling and broken. Soil, sand and sandy clay. Timber, piñon and juniper; undergrowth, sagebrush, scrub oak and native grasses.								
	_____								
	N. 0°02' W., bet. secs. 15 and 16.								
	Over rolling and broken land.								
40.00	Point for the 1/4 sec. cor. of secs. 15 and 16.								
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.								

Survey of the Subdivisional Lines,  
T. 24 N., R. 27 E., Gila and Salt River Meridian, Arizona

CHAINS	
	T 24 N R 27 E 1/4 S 16   S 15  2003
80.00	Deposit a magnet in a white plastic case at the base of the stainless steel post.  Point for the cor. of secs. 9, 10, 15 and 16.  Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.
	T 24 N R 27 E S 9   S 10 S 16   S 15  2003
	Deposit a magnet in a white plastic case at the base of the stainless steel post.  Land, rolling and broken. Soil, sand and sandy clay. Timber, piñon and juniper; undergrowth, sagebrush and native grasses.
	<hr/> From the cor. of secs. 10, 11, 14 and 15.  West, bet. secs. 10 and 15.  Over rolling land.
40.00	Point for the 1/4 sec. cor. of secs. 10 and 15.  Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.
	T 24 N R 27 E S 10 1/4 ——— S 15  2003
80.00	Deposit a magnet in a white plastic case at the base of the stainless steel post.  The cor. of secs. 9, 10, 15 and 16.

**Survey of the Subdivisional Lines,  
T. 24 N., R. 27 E., Gila and Salt River Meridian, Arizona**

CHAINS	
	<p>Land, rolling. Soil, sand and sandy clay. Timber, piñon and juniper; undergrowth, sagebrush and native grasses.</p> <hr/> <p>N. 0°02' W., bet. secs. 9 and 10.</p> <p>Over rolling land.</p>
40.00	<p>Point for the 1/4 sec. cor. of secs. 9 and 10.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T 24 N R 27 E 1/4 S 9   S 10  2003</p> <p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p>
80.00	<p>Point for the cor. of secs. 3, 4, 9 and 10.</p> <p>Set a brass tablet, 3 1/4 ins. diam., 2 1/2 ins. stem., cemented in place, in a drill hole in sandstone bedrock, with top mkd.</p> <p style="text-align: center;">T 24 N R 27 E S 4   S 3 <hr/>S 9   S 10  2003</p> <p>Deposit a magnet in a white plastic case at the base of the brass tablet.</p>
	<p>Land, rolling. Soil, sandy and sandy clay. Timber, piñon and juniper; undergrowth, sagebrush and native grasses.</p> <hr/> <p>From the cor. of secs. 2, 3, 10 and 11.</p> <p>West, bet. secs. 3 and 10.</p> <p>Over rolling land.</p>
40.00	<p>Point for the 1/4 sec. cor. of secs. 3 and 10.</p>

**Survey of the Subdivisional Lines,  
T. 24 N., R. 27 E., Gila and Salt River Meridian, Arizona**

CHAINS	
	<p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T 24 N R 27 E S 3 1/4 ——— S 10</p> <p style="text-align: center;">2003</p> <p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p>
80.00	<p>Point for the cor. of secs. 3, 4, 9 and 10.</p> <p>Land, rolling and broken. Soil, sand and sandy clay. Timber, piñon and juniper; undergrowth, sagebrush and native grasses.</p> <hr/> <p>N. 0°02' W., bet. secs. 3 and 4.</p> <p>Over rolling and broken land.</p>
40.00	<p>Point for the 1/4 sec. cor. of secs. 3 and 4.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T 24 N R 27 E 1/4 S 4   S 3</p> <p style="text-align: center;">2003</p> <p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p>
56.80	<p>Navajo Route 28, a graded road, 25 ft. wide, bears East and West.</p>
78.91	<p>Point for the closing cor. of secs. 3 and 4, at the intersection with the Sixth Standard Parallel North, on the N. bdy. of the Tp.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p>

**Survey of the Subdivisional Lines,  
T. 24 N., R. 27 E., Gila and Salt River Meridian, Arizona**

CHAINS

T 25 N R 27 E  
                   S 32  


---

 S 4 | S 3  
 T 24 N R 27 E  
 CC

2003

Deposit a magnet in a white plastic case at the base of the stainless steel post.

From this cor. point, the stan. cor. of secs. 32 and 33, T. 25 N., R. 27 E., bears S. 89° 59' E., 8.08 chs. dist., monumented with an iron post, 2 ins. diam., with brass cap, set and mkd. as described in the field notes of the dependent resurvey of the Sixth Standard Parallel North (south boundary), T. 25 N., R. 27 E., executed concurrently under this same group.

From this same cor. point, the stan. 1/4 sec. cor. of sec. 32, T. 25 N. R. 27 E., bears N. 89° 59' W. 31.91 chs. dist., monumented with a stainless steel post, 2 1/2 ins. diam., with brass cap, set, mkd. and witnessed as described in the field notes of the dependent resurvey of the Sixth Standard Parallel North (south boundary), T. 25 N., R. 27 E., executed concurrently under this same group.

Land, rolling and broken.

Soil, sand and sandy clay.

Timber, piñon and juniper,,; undergrowth, sagebrush, scrub oak and native grasses.

---

Point for the 1/4 sec. cor. of sec. 3 only, T. 24 N., R. 27 E., at midpoint on the N. bdy. of sec. 3.

Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.

T 25 N R 27 E  


---

 1/4 S 3  
 T 24 N R 27 E

2003

Deposit a magnet in a white plastic case at the base of the stainless steel post.

From this cor. point, the stan. 1/4 sec. cor. of sec. 33, T. 25 N., R. 27 E., bears S. 89°59' E., 8.135 chs. dist.

**Survey of the Subdivisional Lines,  
T. 24 N., R. 27 E., Gila and Salt River Meridian, Arizona**

CHAINS	
	<p>From this same cor. point, the stan. cor. of secs. 32 and 33, T. 25 N., R. 27 E., bears N. 89° 59' W., 31.925 chs. dist.</p> <hr/> <p>From the cor. of secs. 28, 29, 32 and 33, on the Sectional Correction Line, hereinbefore described.</p> <p>S. 0°03' E., bet. secs. 32 and 33.</p> <p>Over rolling and broken land.</p>
40.00	<p>Point for the 1/4 sec. cor. of secs. 32 and 33.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T 24 N R 27 E 1/4 S 32   S 33  2003</p> <p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p>
74.41	<p>The cor. of secs. 4, 5, 32 and 33, on the S. bdy. of the Tp., monumented with a stainless steel post, 2 1/2 ins. diam., with brass cap, set and mkd. as described in the field notes of the dependent resurvey of the N. bdy., T. 23 N., R. 27 E., executed concurrently under this same group.</p> <p>Land, rolling and broken. Soil, sand and sandy clay. Timber, piñon and juniper; undergrowth, sagebrush, rabbit brush, scrub oak and native grasses.</p> <hr/> <p>From the cor. of secs. 28, 29, 32 and 33, on the Sectional Correction Line, hereinbefore described.</p> <p>N. 0°03' W., bet. secs. 28 and 29.</p> <p>Over rolling and broken land</p>
40.00	<p>Point for the 1/4 sec. cor. of secs. 28 and 29.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p>



**Survey of the Subdivisional Lines,  
T. 24 N., R. 27 E., Gila and Salt River Meridian, Arizona**

CHAINS	
	T 24 N R 27 E 1/4 S 29   S 28  2003
	Deposit a magnet in a white plastic case at the base of the stainless steel post.
80.00	Point for the cor. of secs. 20, 21, 28 and 29.  Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.
	T 24 N R 27 E S 20   S 21 S 29   S 28  2003
	Deposit a magnet in a white plastic case at the base of the stainless steel post.
	Land, rolling and broken. Soil, sand and sandy clay. Timber, piñon and juniper; undergrowth, sagebrush, rabbit brush, scrub oak and native grasses.
	From the cor. of secs. 21, 22, 27 and 28.  West, bet. secs. 21 and 28.  Over rolling and broken land.
40.00	Point for the 1/4 sec. cor. of secs. 21 and 28.  Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.
	T 24 N R 27 E S 21 1/4 ——— S 28  2003
	Deposit a magnet in a white plastic case at the base of the stainless steel post.
80.00	The cor. of secs. 20, 21, 28 and 29.

**Survey of the Subdivisional Lines,  
T. 24 N., R. 27 E., Gila and Salt River Meridian, Arizona**

CHAINS	
	<p>Land, rolling and broken. Soil, sand and sandy clay. Timber, piñon and juniper; undergrowth, sagebrush and native grasses.</p> <hr/> <p>N. 0°03' W., bet. secs. 20 and 21.</p> <p>Over rolling and broken land.</p>
40.00	<p>Point for the 1/4 sec. cor. of secs. 20 and 21.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T 24 N R 27 E 1/4 S 20   S 21</p> <p style="text-align: center;">2003</p> <p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p>
80.00	<p>Point for the cor. of secs. 16, 17, 20 and 21.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T 24 N R 27 E S 17   S 16 S 20   S 21</p> <p style="text-align: center;">2003</p> <p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p> <p>Cor. is located 2.50 chs. S. of a wash, 50 ft. wide, 12 ft. deep, drains S. 80° W.</p> <p>Land, rolling and broken. Soil, sand and sandy clay. Timber, piñon and juniper; undergrowth, sagebrush and native grasses.</p> <hr/> <p>From the cor. of secs. 15, 16, 21 and 22.</p> <p>West, bet. secs. 16 and 21.</p> <p>Over rolling and broken land.</p>

**Survey of the Subdivisional Lines,  
T. 24 N., R. 27 E., Gila and Salt River Meridian, Arizona**

CHAINS	
40.00	<p>Point for the 1/4 sec. cor. of secs. 16 and 21.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T 24 N R 27 E S 16 1/4 ——— S 21</p> <p style="text-align: center;">2003</p> <p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p>
80.00	<p>The cor. of sec. 16, 17, 20 and 21.</p> <p>Land, rolling and broken. Soil, sand and sandy clay. Timber, piñon and juniper; undergrowth, sagebrush, scrub oak and native grasses.</p> <hr/> <p>N. 0°03' W., bet. secs. 16 and 17.</p> <p>Over rolling and broken land.</p>
40.00	<p>Point for the 1/4 sec. cor. of secs. 16 and 17.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T 24 N R 27 E 1/4 S 17   S 16</p> <p style="text-align: center;">2003</p> <p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p> <p>Cor. is located 25 lks. S. of a trail road, bears N. 75° E. and S. 75° W.</p>
80.00	<p>Point for the cor. of secs. 8, 9, 16 and 17.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p>

Survey of the Subdivisional Lines,  
T. 24 N., R. 27 E., Gila and Salt River Meridian, Arizona

CHAINS	
	<p style="text-align: center;">T 24 N R 27 E S 8   S 9 S 17   S 16</p> <p style="text-align: center;">2003</p> <p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p> <p>Land, rolling and broken. Soil, sand and sandy clay. Timber, piñon and juniper; undergrowth, sagebrush, scrub oak and native grasses.</p> <hr/> <p>From the cor. of secs. 9, 10, 15 and 16.</p> <p>West, bet. secs. 9 and 16.</p> <p>Over rolling land.</p>
40.00	<p>Point for the 1/4 sec. cor. of secs. 9 and 16.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p>
	<p style="text-align: center;">T 24 N R 27 E S 9 1/4 ——— S 16</p> <p style="text-align: center;">2003</p> <p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p>
80.00	<p>The cor. of secs. 8, 9, 16 and 17.</p> <p>Land, rolling. Soil, sand and rocky clay. Timber, piñon and juniper; undergrowth, sagebrush and native grasses.</p> <hr/> <p>N. 0°03' W., bet. secs. 8 and 9.</p> <p>Over rolling and broken land.</p>
38.55	<p>A rocky draw, 135 ft. wide, 15 ft. deep, bears N. 80° E. and S. 80° W.</p>
40.00	<p>Point for the 1/4 sec. cor. of secs. 8 and 9.</p>

**Survey of the Subdivisional Lines,  
T. 24 N., R. 27 E., Gila and Salt River Meridian, Arizona**

CHAINS	<p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p align="center">T 24 N R 27 E 1/4 S 8   S 9</p> <p align="center">2003</p> <p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p> <p>Cor. is located 30 lks. N. of a trail road, bears N. 85° E. and S. 85° W.</p>
80.00	<p>Point for the cor. of secs. 4, 5, 8 and 9.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p align="center">T 24 N R 27 E S 5   S 4 ----- S 8   S 9</p> <p align="center">2003</p> <p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p> <p>Land, rolling and broken. Soil, sand and sandy clay. Timber, piñon and juniper; undergrowth, sagebrush, scrub oak and native grasses.</p> <hr/> <p>From the cor. of secs. 3, 4, 9 and 10.</p> <p>West, bet. secs. 4 and 9.</p> <p>Over rolling and broken land.</p>
40.00	<p>Point for the 1/4 sec. cor. of secs. 4 and 9.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p align="center">T 24 N R 27 E S 4 1/4 ----- S 9</p> <p align="center">2003</p>

Survey of the Subdivisional Lines,  
T. 24 N., R. 27 E., Gila and Salt River Meridian, Arizona

CHAINS	
	Deposit a magnet in a white plastic case at the base of the stainless steel post.
80.00	The cor. of secs. 4, 5, 8 and 9.  Land, rolling and broken. Soil, sand and sandy clay. Timber, piñon and juniper; undergrowth, sagebrush, scrub oak and native grasses.
	N. 0°03' W., bet. secs. 4 and 5.  Over rolling and broken land.
30.70	Navajo Route 28, a graded road, 22 ft. wide, bears N. 80° E. and S. 80° W.
40.00	Point for the 1/4 sec. cor. of secs. 4 and 5.  Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.
	T 24 N R 27 E 1/4 S 5   S 4  2003
	Deposit a magnet in a white plastic case at the base of the stainless steel post.
78.92	Point for the closing cor. of secs. 4 and 5, at the intersection with the Sixth Standard Parallel North, on the N. bdy. of the Tp.  Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.
	T 25 N R 27 E S 31 ----- S 5   S 4 T 24 N R 27 E CC  2003
	Deposit a magnet in a white plastic case at the base of the stainless steel post.

**Survey of the Subdivisional Lines,  
T. 24 N., R. 27 E., Gila and Salt River Meridian, Arizona**

CHAINS	<p>From this cor. point, the stan. cor. of secs. 31 and 32, T. 25 N., R. 27 E. bears S. 89°59' E., 8.10 chs. dist., monumented with an iron post, 2 ins. diam., with brass cap, set, mkd. and witnessed as described in the field notes of the dependent resurvey of the Sixth Standard Parallel North (south boundary), T. 25 N., R. 27 E., executed concurrently under this same group.</p> <p>From this same cor. point, the stan. 1/4 sec. cor. of sec. 31, T. 25 N., R 27 E., bears. N. 89°59' W., 31.84 chs., monumented with an iron post, 1 in. diam., with brass cap, set, mkd. and witnessed as described in the field notes of the dependent resurvey of the Sixth Standard Parallel North (south boundary), T. 25 N., R. 27 E., executed concurrently under this same group.</p> <p>Land, rolling. Soil, sandy and sandy clay. Timber, piñon and juniper; undergrowth, sagebrush and native grasses.</p> <hr/> <p>Point for the 1/4 sec. cor. of sec. 4 only, T. 24 N., R. 27 E., at midpoint on the N. bdy. of sec. 4.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T 25 N R 27 E ----- 1/4 S 4 T 24 N R 27 E</p> <p style="text-align: center;">2003</p> <p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p> <p>From this cor. point, the stan. 1/4 sec. cor. of sec. 32, T. 25 N., R. 27 E., bears S. 89°59' E., 8.09 chs. dist.</p> <p>From this same cor. point, the stan. cor. of secs. 31 and 32, T. 25 N., R. 27 E., bears N. 89°59' W., 31.90 chs. dist.</p> <hr/> <p>From the cor. of secs. 29, 30, 31 and 32, on the Sectional Correction Line, hereinbefore described.</p> <p>S. 0°03' E., bet. secs. 31 and 32.</p> <p>Over rolling and broken land.</p> <p>40.00 Point for the 1/4 sec. cor. of secs. 31 and 32.</p>
--------	---

**Survey of the Subdivisional Lines,  
T. 24 N., R. 27 E., Gila and Salt River Meridian, Arizona**

CHAINS	
	<p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T 24 N R 27 E 1/4 S 31   S 32</p> <p style="text-align: center;">2003</p> <p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p>
73.01	<p>The cor. of secs. 5, 6, 31 and 32, on the S. bdy. of the Tp., monumented with a stainless steel post, 2 1/2 ins. diam., with brass cap, set and mkd. as described in the field notes of the dependent resurvey of the N. bdy., T. 23 N., R. 27 E., executed concurrently under this same group.</p> <p>Land, rolling. Soil, sandy and sandy clay. Timber, piñon and juniper; undergrowth, sagebrush and native grasses.</p> <hr/> <p>From the cor. of secs. 29, 30, 31 and 32, on the Sectional Correction Line, hereinbefore described.</p> <p>N. 0°03' W., bet. secs. 29 and 30.</p> <p>Over rolling and broken land.</p>
40.00	<p>Point for the 1/4 sec. cor. of secs. 29 and 30.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T 24 N R 27 E 1/4 S 30   S 29</p> <p style="text-align: center;">2003</p> <p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p>
80.00	<p>Point for the cor. of secs. 19, 20, 29 and 30.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p>



Survey of the Subdivisional Lines,  
T. 24 N., R. 27 E., Gila and Salt River Meridian, Arizona

CHAINS	
	<p style="text-align: center;">T 24 N R 27 E S 19   S 20 ----- S 30   S 29</p> <p style="text-align: center;">2003</p> <p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p> <p>Land, rolling and broken. Soil, sand and sandy clay. Timber, piñon and juniper; undergrowth, sagebrush and native grasses.</p> <hr/> <p>From the cor. of secs. 20, 21, 28 and 29.</p> <p>West, bet. secs. 20 and 29.</p> <p>Over rolling and broken land.</p>
40.00	<p>Point for the 1/4 sec. cor. of secs. 20 and 29.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p>
	<p style="text-align: center;">T 24 N R 27 E S 20 1/4 ——— S 29</p> <p style="text-align: center;">2003</p> <p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p> <p>Cor. is located 65 lks. S. of a trail road, bears East and West, and 15 lks. N. of a wash, 12 ft. wide, 4 ft. deep, drains N. 50° W.</p>
66.20	<p>Wide Ruin Wash, 240 ft. wide, 8 ft. deep, drains S. 70° W.</p>
80.00	<p>The cor. of secs. 19, 20, 29 and 30.</p> <p>Land, rolling and broken. Soil, sand and sandy clay. Timber, piñon and juniper; undergrowth, sagebrush, rabbit brush, scrub oak and native grasses.</p> <hr/> <p>West, bet. secs. 19 and 30.</p> <p>Over broken land.</p>

**Survey of the Subdivisional Lines,  
T. 24 N., R. 27 E., Gila and Salt River Meridian, Arizona**

CHAINS																	
40.00	<p>Point for the 1/4 sec. cor. of secs. 19 and 30.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center;"> <p>T 24 N R 27 E S 19 1/4 ——— S 30</p> <p>2003</p> </div> <p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p> <p>Cor. is located 1.25 chs. S. of a graded road, 15 ft. wide, bears S. 80° E. and N. 80° W.</p>																
60.89	E. right-of-way fence of U. S. Highway 191, barbed wire, 4 strands, parallels highway.																
62.60	U. S. Highway No. 191, asphalt pavement, 28 ft. wide, bears S. 25° E. and N. 30° W., curves left.																
64.34	W. right-of-way fence of U. S. Highway 191, barbed wire, 4 strands, parallels highway.																
70.20	Apache County Road C424, a graded road, 20 ft. wide, bears N. 20° E. and S. 20° W.																
77.45	<p>Point for the closing cor. of secs. 19 and 30, at the intersection with the E. bdy. of T. 24 N., R. 26 E.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd</p> <div style="text-align: center;"> <table style="border-collapse: collapse; margin: auto;"> <tr> <td style="border-right: 1px solid black; padding: 0 5px;">T 24 E</td> <td style="padding: 0 5px;"> </td> <td style="padding: 0 5px;">T 24 N</td> <td></td> </tr> <tr> <td style="border-right: 1px solid black; padding: 0 5px;">R 26 E</td> <td style="padding: 0 5px;"> </td> <td style="padding: 0 5px;">S 19</td> <td></td> </tr> <tr> <td style="border-right: 1px solid black; padding: 0 5px;">S 25</td> <td style="padding: 0 5px;"> </td> <td style="padding: 0 5px;">S 30</td> <td style="padding: 0 5px;">—CC</td> </tr> <tr> <td style="border-right: 1px solid black; padding: 0 5px;"></td> <td style="padding: 0 5px;"> </td> <td style="padding: 0 5px;">R 27 E</td> <td></td> </tr> </table> <p>2003</p> <p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p> <p>From this cor. point, the cor. of secs. 24 and 25 only, T. 24 N., R. 26 E., bears North, 8.35 chs. dist., monumented with a stainless steel post, 2 1/2 ins. diam., with brass cap, set and mkd. as described in the field notes of the survey of the E. bdy., T. 24 N., R. 26 E., executed concurrently under this same group.</p> </div>	T 24 E		T 24 N		R 26 E		S 19		S 25		S 30	—CC			R 27 E	
T 24 E		T 24 N															
R 26 E		S 19															
S 25		S 30	—CC														
		R 27 E															

**Survey of the Subdivisional Lines,  
T. 24 N., R. 27 E., Gila and Salt River Meridian, Arizona**

CHAINS	<p>From this same cor. point, the 1/4 sec. cor. of sec. 25 only, T. 24 N., R. 26 E., bears South, 31.65 chs. dist., monumented with a stainless steel post, 2 1/2 ins. diam., with brass cap, set and mkd. as described in the field notes of the survey of the E. bdy., T. 24 N., R. 26 E., executed concurrently under this same group.</p> <p>Cor. is located 75 lks. E. of the E. bank of a wash, 15 ft. high, bears N. 20° E. and S. 20° W.</p> <p>Land, broken. Soil, sand and sandy clay. Timber, piñon and juniper; undergrowth, sagebrush, rabbit brush and native grasses.</p> <hr/> <p>Point for the 1/4 sec. cor. of sec. 30 only, T. 24 N., R. 27 E., at midpoint on the W. bdy. of sec. 30.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center;"> <p>T 24 N R 26 E R 27 E   1/4 S 30 2003</p> </div> <p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p> <p>From this cor. point, the 1/4 sec. cor. of sec. 25 only, T. 24 N., R. 26 E., bears North, 8.35 chs. dist.</p> <p>From this same cor. point, the cor. of secs. 25 and 36 only, T. 24 N., R. 26 E., bears South, 31.65 chs. dist., hereinbefore described.</p> <hr/> <p>From the cor. of secs. 19, 20, 29 and 30.</p> <p>N. 0°03' W., bet. secs. 19 and 20.</p> <p>Over rolling land.</p>
40.00	<p>Point for the 1/4 sec. cor. of secs. 19 and 20.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p>

Survey of the Subdivisional Lines,  
T. 24 N., R. 27 E., Gila and Salt River Meridian, Arizona

CHAINS	
	T 24 N R 27 E 1/4 S 19   S 20  2003
	Deposit a magnet in a white plastic case at the base of the stainless steel post.  Cor. is located 95 lks. N. of a trail road, paralleled by two barbed wire fences, one on each side, 5 and 3 strands, bears N. 85° E. and S. 85° W.
70.70	The middle of the flood plain of Wide Ruin Wash, 7 chs. wide, with undefined banks, drains S. 65° E.
80.00	Point for the cor. of secs. 17, 18, 19 and 20.  Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.
	T 24 N R 27 E S 18   S 17 ———— S 19   S 20  2003
	Deposit a magnet in a white plastic case at the base of the stainless steel post.  Land, rolling. Soil, sand and sandy clay. Timber, piñon and juniper; undergrowth, sagebrush, rabbit brush and native grasses.
	<hr/> From the cor. of secs. 16, 17, 20 and 21.  West, bet. secs. 17 and 20.  Over broken land.
40.00	Point for the 1/4 sec. cor. of secs. 17 and 20.  Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.
	T 24 N R 27 E S 17 1/4 ——— S 20  2003

**Survey of the Subdivisional Lines,  
T. 24 N., R. 27 E., Gila and Salt River Meridian, Arizona**

CHAINS																					
	Deposit a magnet in a white plastic case at the base of the stainless steel post.																				
80.00	The cor. of secs. 17, 18, 19 and 20.  Land, broken. Soil, sand and sandy clay. Timber, piñon and juniper; undergrowth, sagebrush, rabbit brush and native grasses.																				
	-----																				
	West, bet. secs. 18 and 19.  Over rolling land.																				
24.00	The middle of the flood plain of Wide Ruin Wash, 18 chs. wide, with undefined banks, drains S. 15° E.																				
34.40	Navajo Route 9353, a graded road, 25 ft. wide, bears N. 20° E. and S. 20° W.																				
40.00	Point for the 1/4 sec. cor. of secs. 18 and 19.  Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.																				
	T 24 N R 27 E S 18 1/4 ——— S 19  2003																				
	Deposit a magnet in a white plastic case at the base of the stainless steel post.  Cor. is located on the E. edge of a trail road, bears S. 20° E. and N. 20° W.																				
77.36	Point for the closing cor. of secs. 18 and 19, at the intersection with the E. bdy. of T. 24 N., R. 26 E.  Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.																				
	<table border="0"> <tr> <td>T 24 N</td> <td> </td> <td>T 24 N</td> <td></td> </tr> <tr> <td>R 26 E</td> <td> </td> <td>S 18</td> <td></td> </tr> <tr> <td></td> <td> </td> <td>-----</td> <td>CC</td> </tr> <tr> <td>S 24</td> <td> </td> <td>S 19</td> <td></td> </tr> <tr> <td></td> <td> </td> <td>R 27 E</td> <td></td> </tr> </table> 2003	T 24 N		T 24 N		R 26 E		S 18				-----	CC	S 24		S 19				R 27 E	
T 24 N		T 24 N																			
R 26 E		S 18																			
		-----	CC																		
S 24		S 19																			
		R 27 E																			

**Survey of the Subdivisional Lines,  
T. 24 N., R. 27 E., Gila and Salt River Meridian, Arizona**

CHAINS	<p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p> <p>From this cor. point, the cor. of secs. 13 and 24 only, T. 24 N., R. 26 E., bears North, 8.35 chs. dist., monumented with a stainless steel post, 2 1/2 ins. diam., with brass cap, set and mkd. as described in the field notes of the survey of the E. bdy., T. 24 N., R. 26 E., executed concurrently under this same group.</p> <p>From this same cor. point, the 1/4 sec. cor. of sec. 24 only, T. 24 N., R. 26 E., bears South, 31.65 chs. dist., monumented with a stainless steel post, 2 1/2 ins. diam., with brass cap, set and mkd. as described in the field notes of the survey of the E. bdy., T. 24 N., R. 26 E., executed concurrently under this same group.</p> <p>Land, rolling. Soil, sand and sandy clay. Timber, piñon and juniper; undergrowth, sagebrush, rabbit brush and native grasses.</p> <hr/> <p>Point for the 1/4 sec. cor. of sec. 19 only, T. 24 N., R. 27 E., at midpoint on the W. bdy. of sec. 19.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center; margin: 10px 0;"> <p>T 24 N R 26 E R 27 E   1/4 S 19  2003</p> </div> <p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p> <p>From this cor. point, the 1/4 sec. cor. of sec. 24 only, T. 24 N., R. 26 E., bears North, 8.35 chs. dist.</p> <p>From this same cor. point, the cor. of secs. 24 and 25 only, T. 24 N., R. 26 E., bears South, 31.65 chs. dist.</p> <hr/> <p>From the cor. of secs. 17, 18, 19 and 20.</p> <p>N. 0°03' W., bet. secs. 17 and 18.</p> <p>Over rolling land.</p>
40.00	Point for the 1/4 sec. cor. of secs. 17 and 18.

**Survey of the Subdivisional Lines,  
T. 24 N., R. 27 E., Gila and Salt River Meridian, Arizona**

CHAINS	
80.00	<p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T 24 N R 27 E 1/4 S 18   S 17</p> <p style="text-align: center;">2003</p> <p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p> <p>Cor. is located 20 lks. N. of the N. bank of a wash, 4 ft. high, bears N. 80° E. and S. 80° W.</p> <p>Point for the cor. of secs. 7, 8, 17 and 18.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T 24 N R 27 E S 7   S 8 ----- S 18   S 17</p> <p style="text-align: center;">2003</p> <p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p> <p>Land, rolling. Soil, sand and sandy clay. Timber, piñon and juniper; undergrowth, sagebrush, rabbit brush and native grasses.</p> <hr/> <p>From the cor. of secs. 8, 9, 16 and 17.</p> <p>West, bet. secs. 8 and 17.</p> <p>Over broken land.</p>
40.00	<p>Point for the 1/4 sec. cor. of secs. 8 and 17.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T 24 N R 27 E S 8 1/4 ——— S 17</p> <p style="text-align: center;">2003</p>

Survey of the Subdivisional Lines,  
T. 24 N., R. 27 E., Gila and Salt River Meridian, Arizona

CHAINS	<p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p> <p>80.00 The cor. of secs. 7, 8, 17 and 18.</p> <p>Land, rolling and broken. Soil, sand and sandy clay. Timber, piñon and juniper; undergrowth, sagebrush, scrub oak and native grasses.</p> <hr/> <p>West, bet. secs. 7 and 18.</p> <p>Over rolling land.</p> <p>19.90 The middle of the flood plain of Wide Ruin Wash, 13 1/2 chs. wide, with undefined banks, drains S. 10° E.</p> <p>37.29 Barbed wire fence, 4 strands, bears S. 10° E. and N. 10° W.</p> <p>40.00 Point for the 1/4 sec. cor. of secs. 7 and 18.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 20 ins. below the surface of the ground, with brass cap mkd.</p> <div style="text-align: center; margin: 10px 0;"> <p>T 24 N R 27 E</p> <p>S 7</p> <p>1/4 ———</p> <p>S 18</p> <p>2003</p> </div> <p>from which</p> <p style="margin-left: 40px;">A stainless steel post, 28 ins. long, 2 1/2 ins. diam., set 24 ins. in the ground for a reference monument, bears N. 45°00' E., 50.00 ft. dist., with brass cap mkd. RM T24N R27E 1/4 S7 50.0 FT. TO COR 2003 and an arrow pointing to the corner. Deposit a magnet in a white plastic case at the base of the stainless steel post.</p> <p style="margin-left: 40px;">A stainless steel post, 28 ins. long, 2 1/2 ins. diam., set 24 ins. in the ground for a reference monument, bears S. 45°00' W., 50.00 ft. dist., with brass cap mkd. RM T24N R27E 1/4 S18 50.0 FT. TO COR 2003 and an arrow pointing to the corner. Deposit a magnet in a white plastic case at the base of the stainless steel post.</p> <p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p> <p>Cor. is located 15 lks. E. of the center of Navajo Route 9353, a graded road, 22 ft. wide, bears S. 30° E. and N. 30° W.</p>
--------	---



Survey of the Subdivisional Lines,  
T. 24 N., R. 27 E., Gila and Salt River Meridian, Arizona

CHAINS

77.27

Point for the closing cor. of secs. 7 and 18, at the intersection with the E. bdy. of T. 24 N., R. 26 E.

Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ns. in the ground, with brass cap mkd.

T 24 N	T 24 N	
R 26 E	S 7	
	S 18	CC
S 13	R 27 E	

2003

Deposit a magnet in a white plastic case at the base of the stainless steel post.

From this cor. point, the cor. of secs. 12 and 13 only, T. 24 N., R. 26 E., bears North, 8.35 chs. dist., monumented with a stainless steel post, 2 1/2 ins. diam., with brass cap, set and mkd. as described in the field notes of the survey of the E. bdy., T. 24 N., R. 26 E., executed concurrently under this same group.

From this same cor. point, the 1/4 sec. cor. of sec. 13 only, T. 24 N., R. 26 E., bears South, 31.65 chs. dist., monumented with a stainless steel post, 2 1/2 ins. diam., with brass cap, set and mkd. as described in the field notes of the survey of the E. bdy., T. 24 N., R. 26 E., executed concurrently under this same group.

Land, rolling.

Soil, sand and sandy clay.

Timber, piñon and juniper; undergrowth, sagebrush, rabbit brush and native grasses.

Point for the 1/4 sec. cor. of sec. 18 only, T. 24 N., R. 27 E., at midpoint on the W. bdy. of sec. 18.

Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.

	T 24 N	
R 26 E	R 27 E	
	1/4	S 18

2003

Deposit a magnet in a white plastic case at the base of the stainless steel post.

**Survey of the Subdivisional Lines,  
T. 24 N., R. 27 E., Gila and Salt River Meridian, Arizona**

CHAINS	
	<p>From this cor. point, the 1/4 sec. cor. of sec. 13 only, T. 24 N., R. 26 E., bears North, 8.35 chs. dist.</p> <p>From this same cor. point, the cor. of secs. 13 and 24 only, T. 24 N., R. 26 E., bears South, 31.65 chs. dist.</p> <hr/> <p>From the cor. of secs. 7, 8, 17 and 18.</p> <p>N. 0°03' W., bet. secs. 7 and 8.</p> <p>Over rolling land.</p>
36.90	Wash, 15 ft. wide, 5 ft. deep, drains S. 70° W.
40.00	<p>Point for the 1/4 sec. cor. of secs. 7 and 8.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center;"> <p>T 24 N R 27 E 1/4 S 7   S 8</p> <p>2003</p> </div> <p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p>
80.00	<p>Point for the cor. of secs. 5, 6, 7 and 8.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center;"> <p>T 24 N R 27 E S 6   S 5 S 7   S 8</p> <p>2003</p> </div> <p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p> <p>Land, rolling. Soil, sand and sandy clay. Timber, piñon and juniper; undergrowth, sagebrush, rabbit brush and native grasses.</p> <hr/> <p>From the cor. of secs. 4, 5, 8 and 9.</p> <p>West, bet. secs. 5 and 8.</p>

**Survey of the Subdivisional Lines,  
T. 24 N., R. 27 E., Gila and Salt River Meridian, Arizona**

CHAINS	
	Over broken land.
40.00	Point for the 1/4 sec. cor. of secs. 5 and 8.  Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.  <div style="text-align: center;">           T 24 N R 27 E                      S 5            1/4 ———                      S 8             2003         </div>
80.00	Deposit a magnet in a white plastic case at the base of the stainless steel post.  The cor. of secs. 5, 6, 7 and 8.  Land, broken. Soil, sand and sandy clay. Timber, piñon and juniper; undergrowth, sagebrush, scrub oak and native grasses. <hr/>
	West, bet. secs. 6 and 7.  Over rolling land.
7.40	Wide Ruin Wash, 60 ft. wide, 8 ft. deep, drains S. 30° W.
40.00	Point for the 1/4 sec. cor. of secs. 6 and 7.  Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.  <div style="text-align: center;">           T 24 N R 27 E                      S 6            1/4 ———                      S 7             2003         </div>
	Deposit a magnet in a white plastic case at the base of the stainless steel post.  Cor. is located 1.64 chs. S. of a woven wire and 1 strand barbed wire fence, bears East and West.
77.18	Point for the closing cor. of secs. 6 and 7, at the intersection with the E. bdy. of T. 24 N., R. 26 E.

**Survey of the Subdivisional Lines,  
T. 24 N., R. 27 E., Gila and Salt River Meridian, Arizona**

CHAINS

Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.

T 24 N	T 24 N	
R 26 E	S 6	
	S 7	CC
S 12	R 27 E	

2003

Deposit a magnet in a white plastic case at the base of the stainless steel post.

From this cor. point, the cor. of secs. 1 and 12 only, T. 24 N., R. 26 E., bears North, 8.35 chs. dist., monumented with a stainless steel post, 2 1/2 ins. diam., with brass cap, set and mkd. as described in the field notes of the survey of the E. bdy., T. 24 N., R. 26 E., executed concurrently under this same group.

From this same cor. point, the 1/4 sec. cor. of sec. 12 only, T. 24 N., R. 26 E., bears South, 31.65 chs. dist., monumented with a stainless steel post, 2 1/2 ins. diam., with brass cap, set, mkd. and witnessed as described in the field notes of the survey of the E. bdy., T. 24 N., R. 26 E., executed concurrently under this same group.

Land, rolling.

Soil, sand and sandy clay.

Timber, piñon and juniper; undergrowth, sagebrush, rabbit brush and native grasses.

Point for the 1/4 sec. cor. of sec. 7 only, T. 24 N., R. 27 E., at midpoint on the W. bdy. of sec. 7.

Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.

	T 24 N	
R 26 E	R 27 E	
	1/4	S 7

2003

Deposit a magnet in a white plastic case at the base of the stainless steel post.

From this cor. point, the 1/4 sec. cor. of sec. 12 only, T. 24 N., R. 26 E., bears North, 8.35 chs. dist.

**Survey of the Subdivisional Lines,  
T. 24 N., R. 27 E., Gila and Salt River Meridian, Arizona**

CHAINS	
	<p>From this same cor. point, the cor. of secs. 12 and 13 only, T. 24 N., R. 26 E., bears South, 31.65 chs. dist.</p> <hr/> <p>Point for the 1/4 sec. cor. of sec. 6 only, T. 24 N., R. 27 E., at 40 chs. dist. in northing from the closing cor. of secs. 6 and 7, on the W. bdy. of sec. 6.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center;"> <p>T 24 N R 26 E    R 27 E</p> <p style="margin-left: 100px;"> </p> <p style="margin-left: 100px;">1/4 S 6</p> <p>2003</p> </div> <p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p> <p>From this cor. point, the 1/4 sec. cor. of sec. 1 only, T. 24 N., R. 26 E., bears North, 8.35 chs. dist., monumented with a stainless steel post, 2 1/2 ins. diam., with brass cap, set and mkd., as described in the field notes of the survey of the E. bdy., T. 24 N., R. 26 E., executed concurrently under this same group.</p> <p>From this same cor. point, the cor. of secs. 1 and 12 only, T. 24 N., R. 26 E., bears South, 31.65 chs. dist.</p> <hr/> <p>From the cor. of secs. 5, 6, 7 and 8.</p> <p>N. 0°03' W., bet. secs. 5 and 6.</p> <p>Over rolling land.</p>
26.20	Navajo Route 28, a graded road, 22 ft. wide, bears S. 80° E. and N. 80° W.
40.00	<p>Point for the 1/4 sec. cor. of secs. 5 and 6.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center;"> <p>T 24 N    R 27 E</p> <p style="margin-left: 100px;">1/4</p> <p style="margin-left: 100px;">S 6   S 5</p> <p>2003</p> </div>

**Survey of the Subdivisional Lines,  
T. 24 N., R. 27 E., Gila and Salt River Meridian, Arizona**

CHAINS	<p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p>										
78.94	<p>Point for the closing cor. of secs. 5 and 6, at the intersection with the Sixth Standard Parallel North, on the N. bdy. of the Tp.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center; margin: 10px 0;"> <table style="margin: auto; border-collapse: collapse;"> <tr> <td style="padding: 0 10px;">T 25 N</td> <td style="padding: 0 10px;">R 26 E</td> </tr> <tr> <td colspan="2" style="text-align: center; padding: 0 10px;">S 36</td> </tr> <tr> <td style="border-right: 1px solid black; padding: 0 5px;">S 6</td> <td style="padding: 0 5px;">S 5</td> </tr> <tr> <td colspan="2" style="text-align: center; padding: 0 10px;">T 24 N R 27 E</td> </tr> <tr> <td colspan="2" style="text-align: center; padding: 0 10px;">CC</td> </tr> </table> </div> <p style="text-align: center; margin: 10px 0;">2003</p> <p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p> <p>From this cor. point, the stan. cor. of Tps. 25 N., Rs. 26 and 27 E., bears N. 89°56' E., 8.12 chs. dist., monumented with a stainless steel post, 2 1/2 ins. diam., with brass cap, set, mkd. and witnessed as described in the field notes of the dependent resurvey of the Sixth Standard Parallel North (south boundary), T. 25 N., R. 26 E., executed concurrently under this same group.</p> <p>From this same point, the stan. 1/4 sec. cor. of sec. 36, T. 25 E., R 26 E., bears S. 89°56' W., 31.74 chs. dist., monumented with a stainless steel post, 2 1/2 ins. diam., with brass cap, set and mkd. as described in the field notes of the dependent resurvey of the Sixth Standard Parallel North (south boundary), T. 25 N., R. 26 E., executed concurrently under this same group.</p> <p>Cor. is located 50 lks. N. of a trail road, bears East and West.</p> <p>Land, rolling. Soil, sand and sandy clay. Timber, piñon and juniper; undergrowth, sagebrush, rabbit brush and native grasses.</p> <hr style="width: 50%; margin: 20px auto;"/> <p>Point for the 1/4 sec. cor. of sec. 5 only, T. 24 N., R. 27 E., at midpoint on the N. bdy. of sec. 5.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p>	T 25 N	R 26 E	S 36		S 6	S 5	T 24 N R 27 E		CC	
T 25 N	R 26 E										
S 36											
S 6	S 5										
T 24 N R 27 E											
CC											

**Survey of the Subdivisional Lines,  
T. 24 N., R. 27 E., Gila and Salt River Meridian, Arizona**

CHAINS

T 25 N R 27 E

1/4 S 5

T 24 N R 27 E

2003

Deposit a magnet in a white plastic case at the base of the stainless steel post.

From this cor. point, the stan. 1/4 sec. cor. of sec. 31, T. 25 N., R. 27 E., bears S. 89°58' E., 8.16 chs. dist.

From this same cor. point, the stan. cor. of Tps. 25 N., R. 26 and 27 E., bears N. 89°58' W., 31.88 chs. dist.

Point for the 1/4 sec. cor. of sec. 6 only, T. 24 N., R. 27 E., at 40 chs. dist. in westing from the closing cor. of secs. 5 and 6, on the N. bdy. of sec. 6.

Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.

T 25 N R 26 E

1/4 S 6

T 24 N R 27 E

2003

Deposit a magnet in a white plastic case at the base of the stainless steel post.

From this cor. point, the stan. 1/4 sec. cor. of sec. 36, T. 25 N., R. 26 E., bears N. 89°56' E., 8.26 chs. dist.

From this same point, the stan. cor. of secs. 35 and 36, T. 25 E., R. 26 E., bears S. 89°56' W., 31.60 chs. dist., monumented with a stainless steel post, 2 1/2 ins. diam., with brass cap, set and mkd. as described in the field notes of the dependent resurvey of the Sixth Standard Parallel North (south boundary), T. 25 N., R. 26 E., executed concurrently under this same group.

## T. 24 N., R. 27 E., Gila and Salt River Meridian, Arizona

CHAINS

## GENERAL DESCRIPTION

---

The area surveyed is within the Navajo Indian Reservation, in the vicinity of the communities of Klagetoh and Wide Ruins, Arizona. The terrain is rolling and broken land. The drainage is southwesterly to two main washes, Wide Ruin Wash and Oak Ridge Wash.

The elevation varies from 6200 to 7200 feet above sea level. The soil is sand clay and rocky. The timber is piñon and juniper with some scattered ponderosa pine in the eastern portion of the township. Undergrowth principally consists of sagebrush, rabbit brush, greasewood, cacti, scrub oak and native grasses.

Principal access to the township is provided by U. S. Highway 191, which enters the township in section 31, extends north-northwesterly and exits in section 19. There are four major Navajo Routes and one Apache County Road, all graded, with numerous trail roads through out the township. Much of this area is used for grazing livestock. There are several residences through out the township. There is no mining activity in the township.

The mean magnetic declination of  $11\ 1/2^\circ$  E. was derived from the computer program GEOMAGIX, utilizing the World Magnetic Model for Epoch 2000 for the dates of survey.

---



**UNITED STATES  
DEPARTMENT OF THE INTERIOR  
BUREAU OF LAND MANAGEMENT**

**FIELD ASSISTANTS**

NAMES	CAPACITY
William F. Olver	Cadastral Surveyor
Daniel Bryan	Engineering Technician
Wilfred Chee	Engineering Technician
Edward Clarke	Engineering Technician
Reuben Mason	Engineering Technician
Barney Woodie	Engineering Technician

CERTIFICATE OF SURVEY

I, Jones Curtiss, Cadastral Surveyor, HEREBY CERTIFY upon honor, that in pursuance of special instructions bearing date of the 1st day of May, 2002, I have surveyed the east boundary, the sectional correction line and the subdivisional lines, T. 24 N., R. 27 E., of the Gila and Salt River Meridian, in the State of Arizona, which are represented in the foregoing field notes as having been executed by me and under my direction. Said survey has been made in strict conformity with said special instructions, the Manual of Instructions for the Survey of the Public Lands of the United States, 1973, and in specific manner described in the foregoing field notes.

June 21, 2005  
(Date)

Jones Curtiss  
(Cadastral Surveyor)

CERTIFICATE OF APPROVAL

BUREAU OF LAND MANAGEMENT  
Phoenix, Arizona

The foregoing field notes of the survey of the east boundary, the sectional correction line and the subdivisional lines, T. 24 N., R. 27 E., Gila and Salt River Meridian, in the State of Arizona, executed by Jones Curtiss, Cadastral Surveyor, having been critically examined and found correct, are hereby approved.

June 27, 2005  
(Date)

Stephen K. Hansen  
(Acting Chief Cadastral Surveyor of Arizona)

~~CERTIFICATE OF TRANSCRIPT~~

~~I CERTIFY That the foregoing transcript of the field notes of the above described surveys in T. 24 N., R. 27 E., Gila and Salt River Meridian, Arizona, is a true copy of the original field notes.~~

~~\_\_\_\_\_  
(Date)~~

~~\_\_\_\_\_  
(Acting Chief Cadastral Surveyor of Arizona)~~