

ORIGINAL

**UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT**

FIELD NOTES
OF THE
SURVEY
OF
THE SOUTH AND NORTH BOUNDARIES
AND
THE SUBDIVISIONAL LINES,
TOWNSHIP 27 NORTH, RANGE 24 EAST,
OF THE GILA AND SALT RIVER MERIDIAN,
IN THE STATE OF ARIZONA

EXECUTED BY

Jones Curtiss, Cadastral Surveyor

Under Special Instructions dated and approved December 17, 2003, which provided for the surveys included under Group No. 924, and assignment instructions dated January 8, 2004.

Survey commenced January 8, 2004

Survey completed February 18, 2004

INDEX DIAGRAM

TOWNSHIP 27 NORTH RANGE 24 EAST
 GILA AND SALT RIVER MERIDIAN, ARIZONA

13	13	12	11	10	9
6	59 5	47 4	39 3	31 2	22 1
58	58	46	38	30	21
7	57 8	45 9	37 10	29 11	21 12
56	55	44	37	28	20
18	54 17	44 16	36 15	27 14	19 13
53	53	43	35	27	18
19	52 20	42 21	35 22	26 23	17 24
51	51	42	34	25	17
30	50 29	41 28	33 27	25 26	16 25
49	49	40	32	24	15
31	48 32	39 33	31 34	23 35	14 36
8	7	6	5	4	4

T. 27 N., R. 24 E., Gila and Salt River Meridian, Arizona

CHAINS

The following field notes describe the survey of the south and north boundaries and the subdivisional lines, Township 27 North, Range 24 East, Gila and Salt River Meridian, Arizona.

The history of surveys pertaining to this survey is as follows:

The west boundary, identical with the Sixth Guide Meridian East, Township 27 North, Range 25 East, was surveyed by William F. Olver, Leonard R. Sandoval and Olian T. Shockley in 1989-90. The east boundary, Township 27 North, Range 23 East, was surveyed by Leonard R. Sandoval in 2002.

The survey was executed in accordance with the specifications as set forth in the Manual of Instructions for the Survey of the Public Lands of the United States, 1973, and the Special Instructions dated December 17, 2004, for Group No. 924, Arizona.

The true meridian direction and length of all lines were determined by real time kinematic global positioning system observations using Trimble Navigation Model 5700 receivers.

Geodetic control was derived from Global Positioning System (GPS) static observations post processed by National Geodetic Survey's Online Positioning User Service (OPUS), utilizing Continuously Operating Reference Stations (CORS) FERNO MESA CORS ARP, FLAGSTAFF 1 CORS and AZTEZ COES ARP. The NAD83 (CORS96) (EPOCH:2002) geographic position of the southeast corner of the township is as follows:

Latitude: 35°41'30.43" N. Longitude: 109°43'11.83" W.

The mean magnetic declination is 11 1/2° E.

**Survey of the South Boundary,
T. 27 N., R. 24 E., Gila and Salt River Meridian, Arizona**

CHAINS					
	<p>Beginning at the cor. of Tps. 26 and 27 N., Rs. 24 and 25 E., monumented with an iron post, 3 ins. diam., firmly set, projecting 6 ins. above ground, with brass cap mkd. T27N R24E R25E S36 S31 S1 S6 T26N 1990 1915.</p> <p>Add the marks 2004 to the brass cap.</p> <p>N. 89°56' W., bet. secs. 1 and 36.</p> <p>Over rolling land.</p>				
3.70	<p>Navajo Route 9057, a graded road, 20 ft. wide, bears NNE and SSW.</p>				
40.00	<p>Point for the 1/4 sec. cor. of secs. 1 and 36.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center;"> <p>T 27 N R 24 E</p> <p>S 36</p> <p>1/4 ———</p> <p>S 1</p> <p>T 26 N</p> <p>2004</p> </div> <p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p>				
80.00	<p>Point for the cor. of secs. 1, 2, 35 and 36.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center;"> <p>T 27 N R 24 E</p> <table style="margin: auto; border-collapse: collapse;"> <tr> <td style="border-right: 1px solid black; padding: 0 5px;">S 35</td> <td style="padding: 0 5px;">S 36</td> </tr> <tr> <td style="border-right: 1px solid black; padding: 0 5px;">S 2</td> <td style="padding: 0 5px;">S 1</td> </tr> </table> <p>T 26 N</p> <p>2004</p> </div> <p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p> <p>Land, rolling. Soil, sand and sandy clay. Timber, scattered piñon and juniper; undergrowth, sagebrush and native grasses.</p> <hr style="width: 80%; margin-left: 0;"/> <p>N. 89°56' W., bet. secs. 2 and 35.</p>	S 35	S 36	S 2	S 1
S 35	S 36				
S 2	S 1				

**Survey of the South Boundary,
T. 27 N., R. 24 E., Gila and Salt River Meridian, Arizona**

CHAINS	
	Over rolling land.
40.00	Point for the 1/4 sec. cor. of secs. 2 and 35. Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd. <div style="text-align: center;"> T 27 N R 24 E S 35 1/4 ——— S 2 T 26 N 2004 </div>
	Deposit a magnet in a white plastic case at the base of the stainless steel post.
78.50	Trail road, bears N. and S.
80.00	Point for the cor. of secs. 2, 3, 34 and 35. Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd. <div style="text-align: center;"> T 27 N R 24 E S 34 S 35 ——— ——— S 3 S 2 T 26 N 2004 </div>
	Deposit a magnet in a white plastic case at the base of the stainless steel post.
	Land, rolling. Soil, sand and sandy clay. Timber, scattered piñon and juniper; undergrowth, sagebrush and native grasses.

	N. 89°56' W., bet. secs. 3 and 34.
	Over rolling land.
26.80	Sand Dunes Wash, with undefined banks, drains SW.
40.00	Point for the 1/4 sec. cor. of sec. 3 and 34. Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.

**Survey of the South Boundary,
T. 27 N., R. 24 E., Gila and Salt River Meridian, Arizona**

CHAINS

T 27 N R 24 E
S 34
1/4 ———
S 3
T 26 N

2004

Deposit a magnet in a white plastic case at the base of the stainless steel post.

51.20 Trail road, bears N. and S.

80.00 Point for the cor. of secs. 3, 4, 33 and 34.

Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.

T 27 N R 24 E
S 33 | S 34
———
S 4 | S 3
T 26 N

2004

Deposit a magnet in a white plastic case at the base of the stainless steel post.

Land, rolling.

Soil, sand and sandy clay.

Timber, scattered piñon and juniper; undergrowth, sagebrush and native grasses.

N. 89°56' W., bet. secs. 4 and 33.

Over rolling land.

40.00 Point for the 1/4 sec. cor. of secs. 4 and 33.

Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.

T 27 N R 24 E
S 33
1/4 ———
S 4
T 26 N

2004

**Survey of the South Boundary,
T. 27 N., R. 24 E., Gila and Salt River Meridian, Arizona**

CHAINS											
	<p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p>										
80.00	<p>Point for the cor. of secs. 4, 5, 32 and 33.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center;"> <table style="margin: auto;"> <tr><td>T 27 N</td><td>R 24 E</td></tr> <tr><td>S 32</td><td>S 33</td></tr> <tr><td>S 5</td><td>S 4</td></tr> <tr><td colspan="2">T 26 N</td></tr> </table> <p>2004</p> </div> <p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p> <p>Land, rolling. Soil, sand and sandy clay. Timber, scattered piñon and juniper; undergrowth, sagebrush and native grasses.</p> <hr/> <p>N. 89°56' W., bet. secs. 5 and 32.</p> <p>Over rolling land.</p>	T 27 N	R 24 E	S 32	S 33	S 5	S 4	T 26 N			
T 27 N	R 24 E										
S 32	S 33										
S 5	S 4										
T 26 N											
10.70	<p>Apache County Road C429, a graded road, 20 ft. wide, bears SE and NW.</p>										
40.00	<p>Point for the 1/4 sec. cor. of secs. 2 and 35.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center;"> <table style="margin: auto;"> <tr><td>T 27 N</td><td>R 24 E</td></tr> <tr><td>S 32</td><td></td></tr> <tr><td>1/4</td><td>—</td></tr> <tr><td>S 5</td><td></td></tr> <tr><td colspan="2">T 26 N</td></tr> </table> <p>2004</p> </div>	T 27 N	R 24 E	S 32		1/4	—	S 5		T 26 N	
T 27 N	R 24 E										
S 32											
1/4	—										
S 5											
T 26 N											
80.00	<p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p> <p>Point for the cor. of secs. 5, 6, 31 and 32.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p>										

**Survey of the South Boundary,
T. 27 N., R. 24 E., Gila and Salt River Meridian, Arizona**

CHAINS											
	<table style="margin: auto;"> <tr><td>T 27 N</td><td>R 24 E</td></tr> <tr><td>S 31</td><td>S 32</td></tr> <tr><td>S 6</td><td>S 5</td></tr> <tr><td colspan="2">T 26 N</td></tr> </table> <p style="text-align: center;">2004</p> <p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p> <p>Land, rolling. Soil, sand and sandy clay. Timber, scattered piñon and juniper; undergrowth, sagebrush and native grasses.</p> <hr/> <p>N. 89°56' W., bet. secs. 6 and 31.</p> <p>Over rolling land.</p>	T 27 N	R 24 E	S 31	S 32	S 6	S 5	T 26 N			
T 27 N	R 24 E										
S 31	S 32										
S 6	S 5										
T 26 N											
40.00	<p>Point for the 1/4 sec. cor. of secs. 6 and 31.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;"> <table style="margin: auto;"> <tr><td>T 27 N</td><td>R 24 E</td></tr> <tr><td>S 31</td><td></td></tr> <tr><td>1/4</td><td>—</td></tr> <tr><td>S 6</td><td></td></tr> <tr><td colspan="2">T 26 N</td></tr> </table> <p style="text-align: center;">2004</p> <p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p> </p>	T 27 N	R 24 E	S 31		1/4	—	S 6		T 26 N	
T 27 N	R 24 E										
S 31											
1/4	—										
S 6											
T 26 N											
81.65	<p>The cor. of Tps. 26 and 27 N., Rs. 23 and 24 E., monumented with a stainless steel post, 2 1/2 ins. diam., firmly set, projecting 4 ins. above ground, with brass cap mkd. T27N R23E R24E S36 S31 S1 S6 T26N 2002.</p> <p>Add the marks 2004 to the brass cap.</p> <p>Land, rolling. Soil, sand and sandy clay. Timber, scattered piñon and juniper; undergrowth, sagebrush and native grasses.</p> <hr/>										

**Survey of the North Boundary,
T. 27 N., R. 24 E., Gila and Salt River Meridian, Arizona**

CHAINS	
	<p>From the cor. of Tps. 27 and 28 N., Rs. 24 and 25 E., monumented with a stainless steel post, 2 1/2 ins. diam., firmly set, projecting 4 ins. above ground, with brass cap mkd. T28N R24E R25E S36 S31 S1 S6 T27N 1989.</p> <p>Add the marks 2004 to the brass cap.</p> <p>N. 89°56' W., bet. secs. 1 and 36.</p> <p>Over rolling land.</p>
35.08	S. right-of-way fence of Arizona State Highway 264, barbed wire, 5 strands, parallels highway.
37.80	Arizona State Highway 264, asphalt pavement, 26 ft. wide, bears NE and SW.
40.00	<p>Point for the 1/4 sec. cor. of secs. 1 and 36.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., flush with surface of the ground, with brass cap mkd.</p> <div style="text-align: center;"> <p>T 28 N R 24 E</p> <p>S 36</p> <p>1/4 ———</p> <p>S 1</p> <p>T 27 N</p> <p>2004</p> </div> <p>from which</p> <p>A stainless steel post, 28 ins. long, 2 1/2 ins. diam., set 24 ins. in the ground for a reference monument, bears S. 20°00' E., 190.00 ft. dist., with brass cap mkd. RM T27N R24E 1/4 S1 190.0 FT. TO COR. 2004 and an arrow pointing to the corner. Deposit a magnet in a white plastic case at the base of the stainless steel post.</p> <p>A stainless steel post, 28 ins. long, 2 1/2 ins. diam., set 24 ins. in the ground for a reference monument, bears N. 20°00' W., 19.00 ft. dist., with brass cap mkd. RM T28N R24E 1/4 S36 19.0 FT. TO COR. 2004 and an arrow pointing to the corner. Deposit a magnet in a white plastic case at the base of the stainless steel post.</p> <p>Deposit a magnet in a white plastic case at the base of the stainless steel post at the 1/4 sec. cor.</p> <p>Cor. is located 47 lks. E. of the N. right-of-way fence of Arizona State Highway 264, barbed wire, 5 strands, parallels highway.</p>

**Survey of the North Boundary,
T. 27 N., R. 24 E., Gila and Salt River Meridian, Arizona**

CHAINS											
80.00	<p>Point for the cor. of secs. 1, 2, 35 and 36.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center;"> <table border="1"> <tr> <td>T 28 N</td> <td>R 24 E</td> </tr> <tr> <td>S 35</td> <td>S 36</td> </tr> <tr> <td>S 2</td> <td>S 1</td> </tr> <tr> <td colspan="2">T 27 N</td> </tr> </table> <p>2004</p> </div> <p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p> <p>Cor. is located 90 lks. S. of a trail road, bears NE and SW.</p> <p>Land, rolling. Soil, sand and sandy clay. Timber, scattered piñon and juniper; undergrowth, sage brush and native grasses.</p> <hr/>	T 28 N	R 24 E	S 35	S 36	S 2	S 1	T 27 N			
T 28 N	R 24 E										
S 35	S 36										
S 2	S 1										
T 27 N											
40.00	<p>N. 89°56' W., bet. secs. 2 and 35.</p> <p>Over rolling land.</p> <p>Point for the 1/4 sec. cor. of secs. 2 and 35.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center;"> <table border="1"> <tr> <td>T 28 N</td> <td>R 24 E</td> </tr> <tr> <td>S 35</td> <td></td> </tr> <tr> <td>1/4</td> <td>—</td> </tr> <tr> <td>S 2</td> <td></td> </tr> <tr> <td colspan="2">T 27 N</td> </tr> </table> <p>2004</p> </div> <p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p> <p>Cor. is located 11 lks. N. of the N. edge of a trail road, bears ENE and WSW.</p>	T 28 N	R 24 E	S 35		1/4	—	S 2		T 27 N	
T 28 N	R 24 E										
S 35											
1/4	—										
S 2											
T 27 N											
45.30	<p>Navajo Route 9053, a graded road, 20 ft. wide, bears NNE and SSW.</p>										
80.00	<p>Point for the cor. of secs. 2, 3, 34 and 35.</p>										

**Survey of the North Boundary,
T. 27 N., R. 24 E., Gila and Salt River Meridian, Arizona**

CHAINS	
	<p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;"> T 28 N R 24 E S 34 S 35 S 3 S 2 T 27 N </p> <p style="text-align: center;">2004</p> <p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p> <p>Land, rolling. Soil, sand and sandy clay. Timber, scattered piñon and juniper; undergrowth, sagebrush and native grasses.</p> <hr/> <p>N. 89°56' W., bet. secs. 3 and 34.</p> <p>Over rolling and broken land.</p>
40.00	<p>Point for the 1/4 sec. cor. of secs. 3 and 34.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;"> T 28 N R 24 E S 34 1/4 ——— S 3 T 27 N </p> <p style="text-align: center;">2004</p> <p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p>
45.40	<p>Wash, 50 ft. wide, 15 ft. deep, drains NE.</p>
80.00	<p>Point for the cor. of secs. 3, 4, 33 and 34.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;"> T 28 N R 24 E S 33 S 34 S 4 S 3 T 27 N </p> <p style="text-align: center;">2004</p>

**Survey of the North Boundary,
T. 27 N., R. 24 E., Gila and Salt River Meridian, Arizona**

CHAINS	<p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p> <p>Land, rolling and broken. Soil, sand and sandy clay. Timber, piñon and juniper; undergrowth, sagebrush and native grasses.</p> <hr/> <p>N. 89°56' W., bet. secs. 4 and 33.</p> <p>Over rolling and broken land.</p>
40.00	<p>Point for the 1/4 sec. cor. of secs. 4 and 33.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p align="center"> T 28 N R 24 E S 33 1/4 ——— S 4 T 27 N 2004 </p>
80.00	<p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p> <p>Cor. is located 1.55 chs. W. of the E. rim of a mesa, bears SSE and NNW.</p> <p>Point for the cor. of secs. 4, 5, 32 and 33.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p align="center"> T 28 N R 24 E S 32 S 33 ———— S 5 S 4 T 27 N 2004 </p> <p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p>

**Survey of the North Boundary,
T. 27 N., R. 24 E., Gila and Salt River Meridian, Arizona**

CHAINS	
	<p>Land, rolling and broken. Soil, sand and sandy clay. Timber, piñon and juniper; undergrowth, sagebrush and native grasses.</p> <hr/> <p>N. 89°56' W., bet. secs. 5 and 32.</p> <p>Over rolling and broken land.</p>
19.50	<p>Apache County Road C429, a graded road, 30 ft. wide, bears SSE and NNW.</p>
40.00	<p>Point for the 1/4 sec. cor. of secs. 5 and 32.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center;"> <p>T 28 N R 24 E S 32 1/4 ——— S 5 T 27 N</p> <p>2004</p> </div> <p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p>
80.00	<p>Point for the cor. of secs. 5, 6, 31 and 32.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center;"> <p>T 28 N R 24 E S 31 S 32 S 6 S 5 T 27 N</p> <p>2004</p> </div> <p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p> <p>Land, rolling and broken. Soil, sand and sandy clay. Timber, piñon and juniper; undergrowth, sagebrush and native grasses.</p> <hr/> <p>N. 89°56' W., bet. secs. 6 and 31.</p>

**Survey of the North Boundary,
T. 27 N., R. 24 E., Gila and Salt River Meridian, Arizona**

CHAINS	<p>Over rolling and broken land.</p>
40.00	<p>Point for the 1/4 sec. cor. of secs. 6 and 31.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p align="center">T 28 N R 24 E S 31 1/4 ——— S 6 T 27 N</p> <p align="center">2004</p> <p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p>
81.11	<p>The cor. of Tps. 27 and 28 N., Rs. 23 and 24 E., monumented with a stainless steel post, 2 1/2 ins. diam., firmly set, projecting 4 ins. above ground, with brass cap mkd. T28N R23E R24E S36 S31 S1 S6 T27N 2002.</p> <p>Add the marks 2004 to the brass cap.</p> <p>Cor. is located 1.20 chs. E. and 50 lks. S. of the rim of a mesa, bears N. and S.</p> <p>Land, rolling and broken. Soil, sand and sandy clay. Timber, piñon and juniper; undergrowth, sagebrush and native grasses.</p> <hr/> <p align="center">Survey of the Subdivisional Lines, T. 25 N., R. 24 E., Gila and Salt River Meridian, Arizona</p> <hr/> <p>From the cor. of secs. 1, 2, 35 and 36, on the S. bdy. of the Tp., hereinbefore described.</p> <p>N. 0°01' W., bet. secs. 35 and 36.</p> <p>Over rolling land.</p>
40.00	<p>Point for the 1/4 sec. cor. of secs. 35 and 36.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p>

**Survey of the Subdivisional Lines,
T. 27 N., R. 24 E., Gila and Salt River Meridian, Arizona**

CHAINS	<p align="center">T 27 N R 24 E 1/4 S 35 S 36</p> <p align="center">2004</p> <p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p>
80.00	<p>Point for the cor. of secs. 25, 26, 35 and 36.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p align="center">T 27 N R 24 E S 26 S 25 S 35 S 36</p> <p align="center">2004</p> <p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p> <p>Land, rolling. Soil, sand and sandy clay. Timber, scattered piñon and juniper; undergrowth, greasewood, sagebrush and native grasses.</p> <hr/> <p>From the cor. of secs. 25, 30, 31 and 36, on the E. bdy. of the Tp., monumented with a stainless steel post, 2 1/2 ins. diam., firmly set, projecting 5 ins. above ground, with brass cap mkd. T27N R24E R25E S25 S30 S36 S31 1989.</p> <p>Add the marks 2004 to the brass cap.</p> <p>N. 89°56' W., bet. secs. 25 and 36.</p> <p>Over rolling land.</p>
40.00	<p>Point for the 1/4 sec. cor. of secs. 25 and 36.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p align="center">T 27 N R 24 E S 25 1/4 ——— S 36</p> <p align="center">2004</p>

**Survey of the Subdivisional Lines,
T. 27 N., R. 24 E., Gila and Salt River Meridian, Arizona**

CHAINS									
	Deposit a magnet in a white plastic case at the base of the stainless steel post.								
80.00	The cor. of secs. 25, 26, 35 and 36. Land, rolling. Soil, sand and sandy clay. Timber, scattered piñon and juniper; undergrowth, sagebrush and native grasses.								
	<hr/>								
	N. 0°01' W., bet. secs. 25 and 26. Over rolling land.								
1.90	Apache County Road C430, a graded road, 22 ft. wide, bears NE and SW.								
40.00	Point for the 1/4 sec. cor. of secs. 25 and 26. Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.								
	<table border="0"> <tr><td>T 27 N</td><td>R 24 E</td></tr> <tr><td>1/4</td><td></td></tr> <tr><td>S 26</td><td> S 25</td></tr> <tr><td colspan="2">2004</td></tr> </table>	T 27 N	R 24 E	1/4		S 26	S 25	2004	
T 27 N	R 24 E								
1/4									
S 26	S 25								
2004									
	Deposit a magnet in a white plastic case at the base of the stainless steel post.								
80.00	Point for the cor. of secs. 23, 24, 25 and 26. Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.								
	<table border="0"> <tr><td>T 27 N</td><td>R 24 E</td></tr> <tr><td>S 23</td><td> S 24</td></tr> <tr><td>S 26</td><td> S 25</td></tr> <tr><td colspan="2">2004</td></tr> </table>	T 27 N	R 24 E	S 23	S 24	S 26	S 25	2004	
T 27 N	R 24 E								
S 23	S 24								
S 26	S 25								
2004									
	Deposit a magnet in a white plastic case at the base of the stainless steel post.								

**Survey of the Subdivisional Lines,
T. 27 N., R. 24 E., Gila and Salt River Meridian, Arizona**

CHAINS	
	<p>Land, rolling. Soil, sand and sandy clay. Timber, scattered piñon and juniper; undergrowth, sagebrush and native grasses.</p> <hr/> <p>From the cor. of secs. 19, 24, 25 and 30, on the E. bdy. of the Tp., monumented with a stainless steel post, 2 1/2 ins. diam., firmly set, projecting 4 ins. above ground, with brass cap mkd. T27N R24E R25E S24 S19 S25 S30 1989.</p> <p>Add the marks 2004 to the brass cap.</p> <p>N. 89°57' W., bet. secs. 24 and 25.</p> <p>Over rolling land.</p>
20.00	Apache County Road C430, a graded road, 22 ft. wide, bears N. and S.
40.01	<p>Point for the 1/4 sec. cor. of secs. 24 and 25.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center;"> <p>T 27 N R 24 E S 24 1/4 ——— S 25</p> <p>2004</p> </div> <p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p>
80.02	<p>The cor. of secs. 23, 24, 25 and 26.</p> <p>Land, rolling. Soil, sand and sandy clay. Timber, scattered piñon and juniper; undergrowth, sagebrush and native grasses.</p> <hr/> <p>N. 0°01' W., bet. secs. 23 and 24.</p> <p>Over rolling land.</p>
40.00	<p>Point for the 1/4 sec. cor. of secs. 23 and 24.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p>

**Survey of the Subdivisional Lines,
T. 27 N., R. 24 E., Gila and Salt River Meridian, Arizona**

CHAINS	<div style="text-align: center; margin-bottom: 20px;"> <p>T 27 N R 24 E 1/4 S 23 S 24</p> <p>2004</p> </div> <p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p> <p>80.00 Point for the cor. of secs. 13, 14, 23 and 24.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center; margin-bottom: 20px;"> <p>T 27 N R 24 E S 14 S 13 S 23 S 24</p> <p>2004</p> </div> <p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p> <p>Land, rolling. Soil, sand and sandy clay. Timber, scattered piñon and juniper; undergrowth, sagebrush and native grasses.</p> <hr/> <p>From the cor. of secs. 13, 18, 19 and 24, on the E. bdy. of the Tp., monumented with a stainless steel post, 2 1/2 ins. diam., firmly set, projecting 6 ins. above ground, with brass cap mkd. T27N R24E R25E S13 S18 S24 S19 1989.</p> <p>Add the marks 2004 to the brass cap.</p> <p>N. 89°57' W., bet. secs. 13 and 24.</p> <p>Over rolling land.</p> <p>40.00 Point for the 1/4 sec. cor. of secs. 13 and 24.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center; margin-top: 20px;"> <p>T 27 N R 24 E S 13 1/4 ——— S 24</p> <p>2004</p> </div>
--------	---

**Survey of the Subdivisional Lines,
T. 27 N., R. 24 E., Gila and Salt River Meridian, Arizona**

CHAINS	<p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p>
80.00	<p>The cor. of secs. 13, 14, 23 and 24.</p> <p>Land, rolling. Soil, sand and sandy clay. Timber, scattered piñon and juniper; undergrowth, sagebrush and native grasses.</p> <hr/> <p>N. 0°01' W., bet. secs. 13 and 14.</p> <p>Over rolling land.</p>
40.00	<p>Point for the 1/4 sec. cor. of secs. 13 and 14.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p align="center"> T 27 N R 24 E 1/4 S 14 S 13 2004 </p>
80.00	<p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p> <p>Point for the cor. of secs. 11, 12, 13 and 14.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p align="center"> T 27 N R 24 E S 11 S 12 <hr style="width: 50%; margin: 0 auto;"/> S 14 S 13 2004 </p> <p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p>

**Survey of the Subdivisional Lines,
T. 27 N., R. 24 E., Gila and Salt River Meridian, Arizona**

CHAINS	<p>Land, rolling. Soil, sand and sandy clay. Timber, piñon and juniper; undergrowth, sagebrush, cacti and native grasses.</p> <hr/> <p>From the cor. of secs. 7, 12, 13 and 18, on the E. bdy. of the Tp., monumented with a stainless steel post, 2 1/2 ins. diam., firmly set, projecting 4 ins. above ground, with brass cap mkd. T27N R24E R25E S12 S7 S13 S18 1989, from which the original bearing trees</p> <p style="padding-left: 40px;">A piñon, 10 ins. diam., bears N. 51 3/4° E., 87 lks. dist., mkd. T27N R25E S7 BT on open blaze.</p> <p style="padding-left: 40px;">A piñon, 9 ins. diam., bears S. 44 1/4° W., 74 lks. dist., mkd. T27N R24E S13 BT on open blaze.</p> <p style="padding-left: 40px;">A piñon, 10 ins. diam., bears N. 75 1/2° W., 90 1/2 lks. dist., mkd. T27N R24E S12 BT on open blaze. (Record: 89 lks.)</p> <p>Add the marks 2004 to the brass cap.</p> <p>N. 89°57' W., bet. secs. 12 and 13.</p> <p>Over rolling land.</p> <p>3.40 Apache County Road C430, a graded road, 22 ft. wide, bears SSE and NNW.</p> <p>38.65 Wash, 26 ft. wide, 4 ft. deep, drains WSW.</p> <p>40.00 Point for the 1/4 sec. cor. of secs. 12 and 13.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center; padding: 10px 0;"> <p>T 27 N R 24 E</p> <p style="padding-left: 40px;">S 12</p> <p style="padding-left: 40px;">1/4 ———</p> <p style="padding-left: 40px;">S 13</p> <p style="padding-left: 40px;">2004</p> </div> <p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p> <p>80.00 The cor. of secs. 11, 12, 13 and 14.</p>
--------	---

**Survey of the Subdivisional Lines,
T. 27 N., R. 24 E., Gila and Salt River Meridian, Arizona**

CHAINS	
	<p>Land, rolling. Soil, sand and sandy clay. Timber, piñon and juniper; undergrowth, sagebrush, cacti and native grasses.</p> <hr/>
	<p>N. 0°01' W., bet. secs. 11 and 12.</p> <p>Over rolling and broken land.</p>
27.30	<p>Apache County Road C430, a graded road, 22 ft. wide, bears E. and W.</p>
40.00	<p>Point for the 1/4 sec. cor. of secs. 11 and 12.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T 27 N R 24 E 1/4 S 11 S 12</p> <p style="text-align: center;">2004</p> <p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p>
80.00	<p>Point for the cor. of secs. 1, 2, 11 and 12.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T 27 N R 24 E S 2 S 1 S 11 S 12</p> <p style="text-align: center;">2004</p> <p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p> <p>Land, rolling and broken. Soil, sand and sandy clay. Timber, piñon and juniper; undergrowth, sagebrush, cacti and native grasses.</p> <hr/> <p>From the cor. of secs. 1, 6, 7 and 12, on the E. bdy. of the Tp., monumented with a stainless steel post, 2 1/2 ins. diam., firmly set, projecting 6 ins. above ground, with brass cap mkd. T27N R24E R25E S1 S6 S12 S7 1989.</p>

**Survey of the Subdivisional Lines,
T. 27 N., R. 24 E., Gila and Salt River Meridian, Arizona**

CHAINS	
	<p>Add the marks 2004 to the brass cap.</p> <p>N. 89°58' W., bet. secs. 1 and 12.</p> <p>Over rolling and broken land.</p>
40.00	<p>Point for the 1/4 sec. cor. of secs. 1 and 12.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T 27 N R 24 E S 1 1/4 ——— S 12</p> <p style="text-align: center;">2004</p>
80.00	<p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p> <p>The cor. of secs. 1, 2, 11 and 12.</p> <p>Land, rolling and broken. Soil, sand and sandy clay. Timber, piñon and juniper; undergrowth, sagebrush, cacti and native grasses.</p> <hr/> <p>N. 0°01' W., bet. secs. 1 and 2.</p> <p>Over rolling and broken land.</p>
12.10	<p>N. rim of a mesa, bears NE and SW, thence descend into rolling land.</p>
40.00	<p>Point for the 1/4 sec. cor. of secs. 1 and 2.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T 27 N R 24 E 1/4 S 2 S 1</p> <p style="text-align: center;">2004</p>
44.22	<p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p> <p>S. right-of-way fence of Arizona State Highway 264, barbed wire, 5 strands, parallels highway.</p>

**Survey of the Subdivisional Lines,
T. 27 N., R. 24 E., Gila and Salt River Meridian, Arizona**

CHAINS	
45.03	A brass tablet, 3 ins. diam., firmly set flush in a concrete collar, 6 ins. diam., firmly set, projecting 3 ins. above ground, bears East, 99 lks. dist., witnessed by an angle iron, to the W., firmly set, projecting 21 ins. above ground, mkd. POT Sta. 2155+00 on the side.
46.16	Arizona State Highway 264, asphalt pavement, 30 ft. wide, bears NE and SW.
47.37	A brass tablet, 3 ins. diam., firmly set flush in a concrete collar, 6 ins. diam., firmly set, projecting 4 ins. above ground, bears West, 93 lks. dist., witnessed by an angle iron to the E., firmly set, projecting 22 ins. above ground, mkd. POT STA. 2155+00 on the side.
48.14	N. right-of-way fence of Arizona State Highway 264, barbed wire, 5 strands, parallels highway.
80.03	The cor. of secs. 1, 2, 35 and 36, on the N. bdy. of the Tp., hereinbefore described. Land, rolling and broken. Soil, sand and sandy clay. Timber, piñon and juniper; undergrowth, sagebrush, cacti and native grasses.
	From the cor. of secs. 2, 3, 34 and 35, on the S. bdy. the Tp., hereinbefore described. N. 0°01' W., bet. secs. 34 and 35. Over rolling land.
39.00	Trail road, bears NNE and SSW.
40.00	Point for the 1/4 sec. cor. of secs. 34 and 35. Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd. T 27 N R 24 E 1/4 S 34 S 35 2004
	Deposit a magnet in a white plastic case at the base of the stainless steel post.
80.00	Point for the cor. of secs. 26, 27, 34 and 35.

**Survey of the Subdivisional Lines,
T. 27 N., R. 24 E., Gila and Salt River Meridian, Arizona**

CHAINS									
	<p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p align="center"> <table border="0"> <tr> <td>T 27 N</td> <td>R 24 E</td> </tr> <tr> <td>S 27</td> <td>S 26</td> </tr> <tr> <td>S 34</td> <td>S 35</td> </tr> </table> </p> <p align="center">2004</p> <p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p> <p>Land, rolling. Soil, sand and sandy clay. No timber; greasewood, cacti, rabbit brush and native grasses.</p> <hr/> <p>From the cor. of secs. 25, 26, 35 and 36.</p> <p>N. 89°56' W., bet. secs. 26 and 35.</p> <p>Over rolling land.</p>	T 27 N	R 24 E	S 27	S 26	S 34	S 35		
T 27 N	R 24 E								
S 27	S 26								
S 34	S 35								
2.30	Apache County Road C430, a graded road, 22 ft. wide, bears NE and SW.								
38.35	Apache County Road C430, a graded road, 22 ft. wide, bears NE and SW.								
40.00	<p>Point for the 1/4 sec. cor. of secs. 26 and 35.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p align="center"> <table border="0"> <tr> <td>T 27 N</td> <td>R 24 E</td> </tr> <tr> <td></td> <td>S 26</td> </tr> <tr> <td>1/4</td> <td>—</td> </tr> <tr> <td></td> <td>S 35</td> </tr> </table> </p> <p align="center">2004</p> <p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p>	T 27 N	R 24 E		S 26	1/4	—		S 35
T 27 N	R 24 E								
	S 26								
1/4	—								
	S 35								
80.00	The cor. of secs. 26, 27, 34 and 35.								

**Survey of the Subdivisional Lines,
T. 27 N., R. 24 E., Gila and Salt River Meridian, Arizona**

CHAINS	
	<p>Land, rolling. Soil, sand and sandy clay. Timber, scattered piñon and juniper; undergrowth, sagebrush, greasewood, cacti and native grasses.</p> <hr/>
	<p>N. 0°01' W., bet. secs. 26 and 27.</p>
	<p>Over rolling land.</p>
40.00	<p>Point for the 1/4 sec. cor. of secs. 26 and 27.</p>
	<p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p>
	<p align="center">T 27 N R 24 E 1/4 S 27 S 26</p>
	<p align="center">2004</p>
	<p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p>
68.80	<p>Apache County Road C430, a graded road, 15 ft. wide, bears SSE and NNW.</p>
80.00	<p>Point for the cor. of secs. 22, 23, 26 and 27.</p>
	<p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p>
	<p align="center">T 27 N R 24 E S 22 S 23 S 27 S 26</p>
	<p align="center">2004</p>
	<p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p>
	<p>Land, rolling. Soil, sand and sandy clay. No timber; sagebrush, greasewood, cacti and native grasses.</p> <hr/>
	<p>From the cor. of secs. 23, 24, 25 and 26.</p>
	<p>N. 89°56' W., bet. secs. 23 and 26.</p>
	<p>Over rolling land.</p>

**Survey of the Subdivisional Lines,
T. 27 N., R. 24 E., Gila and Salt River Meridian, Arizona**

CHAINS	
40.00	<p>Point for the 1/4 sec. cor. of secs. 23 and 26.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T 27 N R 24 E S 23 1/4 ——— S 26</p> <p style="text-align: center;">2004</p> <p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p>
80.00	<p>The cor. of secs. 22, 23, 26 and 27.</p> <p>Land, rolling. Soil, sand and sandy clay. Timber, scattered piñon and juniper; undergrowth, greasewood, sagebrush, cacti and native grasses.</p> <hr/> <p>N. 0°01' W., bet. secs. 22 and 23.</p> <p>Over rolling land.</p>
40.00	<p>Point for the 1/4 sec. cor. of secs. 22 and 23.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T 27 N R 24 E 1/4 S 22 S 23</p> <p style="text-align: center;">2004</p> <p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p>
80.00	<p>Point for the cor. of secs. 14, 15, 22 and 23.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T 27 N R 24 E S 15 S 14 S 22 S 23</p> <p style="text-align: center;">2004</p>

**Survey of the Subdivisional Lines,
T. 27 N., R. 24 E., Gila and Salt River Meridian, Arizona**

CHAINS	
	<p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p> <p>Land, rolling. Soil, sand and sandy clay. Timber, scattered piñon and juniper; undergrowth, sagebrush, cacti and native grasses.</p> <hr/> <p>From the cor. of secs. 13, 14, 23 and 24.</p> <p>N. 89°56' W., bet. secs. 14 and 23.</p> <p>Over rolling land.</p>
40.00	<p>Point for the 1/4 sec. cor. of secs. 14 and 23.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T 27 N R 24 E S 14 1/4 ——— S 23</p> <p style="text-align: center;">2004</p>
	<p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p>
80.00	<p>The cor. of secs. 14, 15, 22 and 23.</p> <p>Land, rolling. Soil, sand and sandy clay. Timber, piñon and juniper; undergrowth, sagebrush, cacti and native grasses.</p> <hr/> <p>N. 0°01' W., bet. secs. 14 and 15.</p> <p>Over rolling land.</p>
40.00	<p>Point for the 1/4 sec. cor. of secs. 14 and 15.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T 27 N R 24 E 1/4 S 15 S 14</p> <p style="text-align: center;">2004</p>

**Survey of the Subdivisional Lines,
T. 27 N., R. 24 E., Gila and Salt River Meridian, Arizona**

CHAINS	<p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p>								
80.00	<p>Point for the cor. of secs. 10, 11, 14 and 15.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center; margin: 10px 0;"> <table style="margin: auto; border-collapse: collapse;"> <tr> <td style="padding: 0 10px;">T 27 N</td> <td style="padding: 0 10px;">R 24 E</td> </tr> <tr> <td style="border-right: 1px solid black; padding: 0 5px;">S 10</td> <td style="padding: 0 5px;">S 11</td> </tr> <tr> <td style="border-right: 1px solid black; padding: 0 5px;">S 15</td> <td style="padding: 0 5px;">S 14</td> </tr> </table> </div> <p align="center">2004</p> <p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p> <p>Land, rolling. Soil, sand and sandy clay. Timber, piñon and juniper; undergrowth, sagebrush, cacti and native grasses.</p> <hr style="width: 50%; margin: 10px auto;"/> <p>From the cor. of secs. 11, 12, 13 and 14.</p> <p>N. 89°56' W., bet. secs. 11 and 14.</p>	T 27 N	R 24 E	S 10	S 11	S 15	S 14		
T 27 N	R 24 E								
S 10	S 11								
S 15	S 14								
40.00	<p>Point for the 1/4 sec. cor. of secs. 11 and 14.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center; margin: 10px 0;"> <table style="margin: auto; border-collapse: collapse;"> <tr> <td style="padding: 0 10px;">T 27 N</td> <td style="padding: 0 10px;">R 24 E</td> </tr> <tr> <td style="padding: 0 10px;"></td> <td style="padding: 0 10px;">S 11</td> </tr> <tr> <td style="padding: 0 10px;">1/4</td> <td style="border-top: 1px solid black; padding: 0 10px;"></td> </tr> <tr> <td style="padding: 0 10px;"></td> <td style="padding: 0 10px;">S 14</td> </tr> </table> </div> <p align="center">2004</p> <p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p>	T 27 N	R 24 E		S 11	1/4			S 14
T 27 N	R 24 E								
	S 11								
1/4									
	S 14								
74.10	<p>Trail road, bears SE and NW.</p>								
80.00	<p>The cor. of secs. 10, 11, 14 and 15.</p>								

**Survey of the Subdivisional Lines,
T. 27 N., R. 24 E., Gila and Salt River Meridian, Arizona**

CHAINS	
	<p>Land, rolling. Soil, sand and sandy clay. Timber, piñon and juniper; undergrowth, sagebrush, cacti and native grasses.</p> <hr/> <p>N. 0°01' W., bet. secs. 10 and 11.</p> <p>Over rolling land.</p>
6.00	Trail road, bears SE and NW.
16.80	Apache County Road C430, a graded road, 15 ft. wide, bears ESE and WNW.
40.00	<p>Point for the 1/4 sec. cor. of secs. 10 and 11.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p align="center"> T 27 N R 24 E 1/4 S 10 S 11 2004 </p> <p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p>
60.09	S. right-of-way fence of Arizona State Highway 264, barbed wire, 5 strands, parallels highway.
61.70	Arizona State Highway 264, asphalt pavement, 28 ft. wide, bears ENE and WSW.
63.34	N. right-of-way fence of Arizona State Highway 264, barbed wire, 5 strands, parallels highway.
80.00	<p>Point for the cor. of secs. 2, 3, 10 and 11.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. below the surface of the ground, with brass cap mkd.</p> <p align="center"> T 27 N R 24 E S 3 S 2 <hr style="width: 50%; margin: 0 auto;"/> S 10 S 11 2004 </p>

**Survey of the Subdivisional Lines,
T. 27 N., R. 24 E., Gila and Salt River Meridian, Arizona**

CHAINS

from which

A stainless steel post, 28 ins. long, 2 1/2 ins. diam., set 24 ins. in the ground for a reference monument, bears S. 20°00' E., 65.00 ft. dist., with brass cap mkd. RM T27N R24E S11 65.0 FT. TO COR. 2004 and an arrow pointing to the corner. Deposit a magnet in a white plastic case at the base of the stainless steel post.

A stainless steel post, 28 ins. long, 2 1/2 ins. diam., set 24 ins. in the ground for a reference monument, bears N. 20°00' W., 31.00 ft. dist., with brass cap mkd. RM T27N R24E S3 31.0 FT. TO COR. 2004 and an arrow pointing to the corner. Deposit a magnet in a white plastic case at the base of the stainless steel post.

Deposit a magnet in a white plastic case at the base of the stainless steel post at the sec. cor.

Cor. is located 27 lks. N. and 17 lks. W. of the center of Navajo Route 9053, a graded road, 20 ft. wide, bears NNE and SSW.

Land, rolling.

Soil, sand and sandy clay.

Timber, piñon and juniper; undergrowth, sagebrush, cacti and native grasses.

From the cor. of secs. 1, 2, 11 and 12.

N. 89°56' W., bet. secs. 2 and 11.

Over rolling and broken land.

40.00 Point for the 1/4 sec. cor. of secs. 2 and 11.

Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.

T 27 N R 24 E
S 2
1/4 ———
S 11

2004

from which

The NE cor. of a hexagonal wood frame hogan, bears S. 16° W., 2.49 chs. dist., with 8 ft. sides, bears SSE and NW.

**Survey of the Subdivisional Lines,
T. 27 N., R. 24 E., Gila and Salt River Meridian, Arizona**

CHAINS	
	Deposit a magnet in a white plastic case at the base of the stainless steel post.
53.52	S. right-of-way fence of Arizona State Highway 264, barbed wire, 5 strands, parallels highway.
55.89	Arizona State Highway 264, asphalt surface, 28 ft. wide, bears NE and SW.
58.27	N. right-of-way fence of Arizona State Highway 264, barbed wire, 5 strands, parallels highway.
80.00	The cor. of secs. 2, 3, 10 and 11. Land, rolling and broken. Soil, sand and sandy clay. Timber, piñon and juniper; undergrowth, sagebrush, cacti and native grasses.
	<hr/>
	N. 0°01' W., bet. secs. 2 and 3. Over rolling land.
40.00	Point for the 1/4 sec. cor. of secs. 2 and 3. Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd. T 27 N R 24 E 1/4 S 3 S 2 2004
	Deposit a magnet in a white plastic case at the base of the stainless steel post.
80.02	The cor. of secs. 2, 3, 34 and 35, on the N. bdy. of the Tp., hereinbefore described. Land, rolling. Soil, sand and sandy clay. Timber, piñon and juniper; undergrowth, sagebrush, cacti and native grasses.
	<hr/>
	From the cor. of secs. 3, 4, 33 and 34, on the S. bdy. of the Tp., hereinbefore described. N. 0°02' W., bet. secs. 33 and 34. Over rolling land.

**Survey of the Subdivisional Lines,
T. 27 N., R. 24 E., Gila and Salt River Meridian, Arizona**

CHAINS	
40.00	<p>Point for the 1/4 sec. cor. of secs. 33 and 34.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T 27 N R 24 E 1/4 S 33 S 34</p> <p style="text-align: center;">2004</p> <p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p>
80.00	<p>Point for the cor. of secs. 27, 28, 33 and 34.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T 27 N R 24 E S 28 S 27 S 33 S 34</p> <p style="text-align: center;">2004</p> <p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p> <p>Cor. is located 95 lks. W. of a trail road, bears SSE and WNW.</p> <p>Land, rolling. Soil, sand and sandy clay. Timber, scattered piñon and juniper; undergrowth, sagebrush, cacti and native grasses.</p> <hr/> <p>From the cor. of secs. 26, 27, 34 and 35.</p> <p>N. 89°56' W., bet. secs. 27 and 34.</p> <p>Over rolling land.</p>
14.40	<p>Sand Dunes Wash, 60 ft. wide, 6 ft. deep, drains SSW.</p>
40.00	<p>Point for the 1/4 sec. cor. of secs. 27 and 34.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p>

**Survey of the Subdivisional Lines,
T. 27 N., R. 24 E., Gila and Salt River Meridian, Arizona**

CHAINS	
	T 27 N R 24 E S 27 1/4 ——— S 34 2004
	Deposit a magnet in a white plastic case at the base of the stainless steel post.
54.80	Trail road, bears N. and S.
80.00	The cor. of secs. 27, 28, 33 and 34. Land, rolling. Soil, sand and sandy clay. Timber, scattered piñon and juniper; undergrowth, sagebrush, cacti and native grasses.

	N. 0°02' W., bet. secs. 27 and 28. Over rolling land.
2.55	Trail road, bears SSE and NNW.
40.00	Point for the 1/4 sec. cor. of secs. 27 and 28. Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.
	T 27 N R 24 E 1/4 S 28 S 27 2004
	Deposit a magnet in a white plastic case at the base of the stainless steel post.
80.00	Point for the cor. of secs. 21, 22, 27 and 28. Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.
	T 27 N R 24 E S 21 S 22 ———— S 28 S 27 2004

**Survey of the Subdivisional Lines,
T. 27 N., R. 24 E., Gila and Salt River Meridian, Arizona**

CHAINS	
	<p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p> <p>Cor. is located 1.75 chs. S. of a trail road, bears ENE and WSW.</p> <p>Land, rolling. Soil, sand and sandy clay. Timber, scattered piñon and juniper; undergrowth, sagebrush, cacti and native grasses.</p> <hr/> <p>From the cor. of secs. 22, 23, 26 and 27.</p> <p>N. 89°56' W., bet. secs. 22 and 27.</p> <p>Over rolling land.</p>
7.80	Apache County Road C430, a graded road, 15 ft. wide, bears SE and NW.
11.60	Sand Dunes Wash, 15 ft. wide, 10 ft. deep, drains SSE.
40.00	<p>Point for the 1/4 sec. cor. of secs. 22 and 27.</p> <p>Set a magnet in a white plastic case, 24 ins. below the surface of the ground.</p> <p>from which</p> <p style="padding-left: 40px;">A stainless steel post, 28 ins. long, 2 1/2 ins. diam., set 24 ins. in the ground for a reference monument, bears N. 50°00' E., 40.00 ft. dist., with brass cap mkd. RM T27N R24E 1/4 S22 40.0 FT. TO COR. 2004 and an arrow pointing to the corner. Deposit a magnet in a white plastic case at the base of the stainless steel post.</p> <p style="padding-left: 40px;">A stainless steel post, 28 ins. long, 2 1/2 ins. diam., set 24 ins. in the ground for a reference monument, bears S. 50°00' W., 70.00 ft. dist., with brass cap mkd. RM T27N R24E 1/4 S27 70.0 FT. TO COR. 2004 and an arrow pointing to the corner. Deposit a magnet in a white plastic case at the base of the stainless steel post.</p> <p>Cor. is located in a wash, 12 ft. wide, 5 ft. deep, drains N.</p>
52.80	Trail road, bears SSE and NNW.
80.00	The cor. of secs. 21, 22, 27 and 28.

**Survey of the Subdivisional Lines,
T. 27 N., R. 24 E., Gila and Salt River Meridian, Arizona**

CHAINS	
	<p>Land, rolling. Soil, sand and sandy clay. No timber; sagebrush, greasewood, cacti and native grasses.</p> <hr/> <p>N. 0°02' W., bet. secs. 21 and 22.</p> <p>Over rolling land.</p>
21.00	Sand Dunes Wash, 40 ft. wide, 20 ft. deep, drains NE.
40.00	<p>Point for the 1/4 sec. cor. of secs. 21 and 22.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T 27 N R 24 E 1/4 S 21 S 22</p> <p style="text-align: center;">2004</p> <p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p>
80.00	<p>Point for the cor. of secs. 15, 16, 21 and 22.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T 27 N R 24 E S 16 S 15 S 21 S 22</p> <p style="text-align: center;">2004</p> <p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p> <p>Land, rolling. Soil, sand and sandy clay. Timber, scattered piñon and juniper; undergrowth, sagebrush, cacti and native grasses.</p> <hr/> <p>From the cor. of secs. 14, 15, 22 and 23.</p> <p>N. 89°56' W., bet. secs. 15 and 22.</p> <p>Over rolling land.</p>

**Survey of the Subdivisional Lines,
T. 27 N., R. 24 E., Gila and Salt River Meridian, Arizona**

CHAINS	
30.00	Apache County Road C430, a graded road, 20 ft. wide, bears NNE and SSW.
40.00	Point for the 1/4 sec. cor. of secs. 15 and 22. Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd. <div style="text-align: center;"> T 27 N R 24 E S 15 1/4 ——— S 22 2004 </div>
80.00	Deposit a magnet in a white plastic case at the base of the stainless steel post. The cor. of secs. 15, 16, 21 and 22. Land, rolling. Soil, sand and sandy clay. Timber, piñon and juniper; undergrowth, sagebrush, cacti and native grasses. ————— N. 0°02' W., bet. secs. 15 and 16. Over rolling land.
40.00	Point for the 1/4 sec. cor. of secs. 15 and 16. Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd. <div style="text-align: center;"> T 27 N R 24 E 1/4 S 16 S 15 2004 </div>
80.00	Deposit a magnet in a white plastic case at the base of the stainless steel post. Point for the cor. of secs. 9, 10, 15 and 16. Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.

**Survey of the Subdivisional Lines,
T. 27 N., R. 24 E., Gila and Salt River Meridian, Arizona**

CHAINS									
	<table border="1"> <tr> <td>T 27 N</td> <td>R 24 E</td> </tr> <tr> <td>S 9</td> <td>S 10</td> </tr> <tr> <td>S 16</td> <td>S 15</td> </tr> </table>	T 27 N	R 24 E	S 9	S 10	S 16	S 15		
T 27 N	R 24 E								
S 9	S 10								
S 16	S 15								
	2004								
	Deposit a magnet in a white plastic case at the base of the stainless steel post.								
	Land, rolling. Soil, sand and sandy clay. Timber, scattered piñon and juniper; undergrowth, sagebrush, cacti and native grasses.								
	<hr/>								
	From the cor. of secs. 10, 11, 14 and 15.								
	N. 89°56' W., bet. secs. 10 and 15.								
	Over rolling land.								
23.10	Apache County Road C430, a graded road, 20 ft. wide, bears N. and S.								
40.00	Point for the 1/4 sec. cor. of secs. 10 and 15.								
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.								
	<table border="1"> <tr> <td>T 27 N</td> <td>R 24 E</td> </tr> <tr> <td>S 10</td> <td></td> </tr> <tr> <td>1/4</td> <td>—</td> </tr> <tr> <td>S 15</td> <td></td> </tr> </table>	T 27 N	R 24 E	S 10		1/4	—	S 15	
T 27 N	R 24 E								
S 10									
1/4	—								
S 15									
	2004								
	Deposit a magnet in a white plastic case at the base of the stainless steel post.								
80.00	The cor. of secs. 9, 10, 15 and 16.								
	Land, rolling. Soil, sand and sandy clay. Timber, scattered piñon and juniper; undergrowth, sagebrush, cacti and native grasses.								
	<hr/>								
	N. 0°02' W., bet. secs. 9 and 10.								
	Over rolling land.								

**Survey of the Subdivisional Lines,
T. 27 N., R. 24 E., Gila and Salt River Meridian, Arizona**

CHAINS									
32.50	Apache County Road C316, a graded road, 20 ft. wide, bears NE and SW.								
40.00	Point for the 1/4 sec. cor. of secs. 9 and 10. Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd. <div style="text-align: center;"> <table style="margin: auto;"> <tr><td>T 27 N</td><td>R 24 E</td></tr> <tr><td colspan="2" style="text-align: center;">1/4</td></tr> <tr><td>S 9</td><td>S 10</td></tr> </table> <p>2004</p> </div>	T 27 N	R 24 E	1/4		S 9	S 10		
T 27 N	R 24 E								
1/4									
S 9	S 10								
	Deposit a magnet in a white plastic case at the base of the stainless steel post.								
57.98	S. right-of-way fence of Arizona State Highway 264, barbed wire, 5 strands, parallels highway.								
58.72	Arizona State Highway 264, asphalt pavement, 25 ft. wide, bears E. and W.								
60.25	N. right-of-way fence of Arizona State Highway 264, barbed wire, 5 strands, parallels highway.								
80.00	Point for the cor. of secs. 3, 4, 9 and 10. Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd. <div style="text-align: center;"> <table style="margin: auto;"> <tr><td>T 27 N</td><td>R 24 E</td></tr> <tr><td>S 4</td><td>S 3</td></tr> <tr><td colspan="2" style="text-align: center;">-----</td></tr> <tr><td>S 9</td><td>S 10</td></tr> </table> <p>2004</p> </div>	T 27 N	R 24 E	S 4	S 3	-----		S 9	S 10
T 27 N	R 24 E								
S 4	S 3								

S 9	S 10								
	Deposit a magnet in a white plastic case at the base of the stainless steel post.								
	Land, rolling. Soil, sand and sandy clay. Timber, scattered piñon and juniper; undergrowth, sagebrush, cacti and native grasses.								

	From the cor. of secs. 2, 3, 10 and 11.								
	N. 89°56' W., bet. secs. 3 and 10.								
	Over rolling land.								

**Survey of the Subdivisional Lines,
T. 27 N., R. 24 E., Gila and Salt River Meridian, Arizona**

CHAINS	
40.00	<p>Point for the 1/4 sec. cor. of secs. 3 and 10.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T 27 N R 24 E S 3 1/4 ——— S 10</p> <p style="text-align: center;">2004</p> <p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p>
80.00	<p>The cor. of secs. 3, 4, 9 and 10.</p> <p>Land, rolling. Soil, sand and sandy clay. Timber, scattered piñon and juniper; undergrowth, sagebrush, cacti and native grasses.</p> <hr/> <p>N. 0°02' W., bet. secs. 3 and 4.</p> <p>Over rolling and broken land.</p>
40.00	<p>Point for the 1/4 sec. cor. of secs. 3 and 4.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T 27 N R 24 E 1/4 S 4 S 3</p> <p style="text-align: center;">2004</p> <p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p>
80.02	<p>The cor. of secs. 3, 4, 33 and 34, on the N. bdy. of the Tp., hereinbefore described.</p> <p>Land, rolling and broken. Soil, sand and sandy clay. Timber, piñon and juniper; undergrowth, sagebrush, cacti and native grasses.</p> <hr/> <p>From the cor. of secs. 4, 5, 32 and 33, on the S. bdy. of the Tp., hereinbefore described.</p>

**Survey of the Subdivisional Lines,
T. 27 N., R. 24 E., Gila and Salt River Meridian, Arizona**

CHAINS	
	N. 0°03' W., bet. secs. 32 and 33.
40.00	Point for the 1/4 sec. cor. of secs. 32 and 33. Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd. <div style="text-align: center;"> T 27 N R 24 E 1/4 S 32 S 33 2004 </div> Deposit a magnet in a white plastic case at the base of the stainless steel post.
80.00	Point for the cor. of secs. 28, 29, 32 and 33. Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd. <div style="text-align: center;"> T 27 N R 24 E S 29 S 28 ----- S 32 S 33 2004 </div> Deposit a magnet in a white plastic case at the base of the stainless steel post. Land, rolling and broken. Soil, sand and sandy clay. Timber, piñon and juniper; undergrowth, sagebrush, cacti and native grasses. <hr/>
	From the cor. of secs. 27, 28, 33 and 34. N. 89°56' W., bet. secs. 28 and 33. Over rolling land.
40.00	Point for the 1/4 sec. cor. of secs. 28 and 33. Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.

**Survey of the Subdivisional Lines,
T. 27 N., R. 24 E., Gila and Salt River Meridian, Arizona**

CHAINS	<p align="center">T 27 N R 24 E S 28 1/4 ——— S 33</p> <p align="center">2004</p> <p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p> <p>80.00 The cor. of secs. 28, 29, 32 and 33.</p> <p>Land, rolling. Soil, sand and sandy clay. Timber, piñon and juniper; undergrowth, sagebrush, cacti and native grasses.</p> <hr/> <p>N. 0°03' W., bet. secs. 28 and 29.</p> <p>Over rolling land.</p> <p>40.00 Point for the 1/4 sec. cor. of secs. 28 and 29.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p align="center">T 27 N R 24 E 1/4 S 29 S 28</p> <p align="center">2004</p> <p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p> <p>80.00 Point for the cor. of secs. 20, 21, 28 and 29.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p align="center">T 27 N R 24 E S 20 S 21 ——— S 29 S 28</p> <p align="center">2004</p> <p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p>
--------	--

**Survey of the Subdivisional Lines,
T. 27 N., R. 24 E., Gila and Salt River Meridian, Arizona**

CHAINS	
	<p>Land, rolling. Soil, sand and sandy clay. Timber, scattered piñon and juniper; undergrowth, sagebrush, cacti and native grasses.</p> <hr/> <p>From the cor. of secs. 21, 22, 27 and 28. N. 89°56' W., bet. secs. 21 and 28. Over rolling land.</p>
2.95	Trail road, bears ENE and WSW.
40.00	<p>Point for the 1/4 sec. cor. of secs. 21 and 28. Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T 27 N R 24 E S 21 1/4 ——— S 28</p> <p style="text-align: center;">2004</p>
80.00	<p>Deposit a magnet in a white plastic case at the base of the stainless steel post. The cor. of secs. 20, 21, 28 and 29.</p> <p>Land, rolling. Soil, sand and sandy clay. Timber, scattered piñon and juniper; undergrowth, sagebrush, cacti and native grasses.</p> <hr/> <p>N. 0°03' W., bet. secs. 20 and 21. Over rolling land.</p>
40.00	<p>Point for the 1/4 sec. cor. of secs. 20 and 21. Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T 27 N R 24 E 1/4 S 20 S 21</p> <p style="text-align: center;">2004</p>

**Survey of the Subdivisional Lines,
T. 27 N., R. 24 E., Gila and Salt River Meridian, Arizona**

CHAINS									
	Deposit a magnet in a white plastic case at the base of the stainless steel post.								
54.00	S. bank of the flood plain of Sand Dunes Wash, 20 ft. high, bears ESE and WNW.								
55.10	Sand Dunes Wash, 40 ft. wide, 20 ft. deep, drains WSW.								
55.40	N. bank of the flood plain of Sand Dunes Wash, 20 ft. high, bears ESE and WNW.								
80.00	Point for the cor. of secs. 16, 17, 20 and 21.								
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.								
	<table style="margin: auto;"> <tr> <td>T 27 N</td> <td>R 24 E</td> </tr> <tr> <td>S 17</td> <td>S 16</td> </tr> <tr> <td>S 20</td> <td>S 21</td> </tr> </table>	T 27 N	R 24 E	S 17	S 16	S 20	S 21		
T 27 N	R 24 E								
S 17	S 16								
S 20	S 21								
	2004								
	Deposit a magnet in a white plastic case at the base of the stainless steel post.								
	Land, rolling. Soil, sand and sandy clay. Timber, scattered piñon and juniper; undergrowth, sagebrush, cacti and native grasses.								
	From the cor. of secs. 15, 16, 21 and 22.								
	N. 89°56' W., bet. secs. 16 and 21.								
	Over rolling land.								
40.00	Point for the 1/4 sec. cor. of secs. 16 and 21.								
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.								
	<table style="margin: auto;"> <tr> <td>T 27 N</td> <td>R 24 E</td> </tr> <tr> <td></td> <td>S 16</td> </tr> <tr> <td>1/4</td> <td>_____</td> </tr> <tr> <td></td> <td>S 21</td> </tr> </table>	T 27 N	R 24 E		S 16	1/4	_____		S 21
T 27 N	R 24 E								
	S 16								
1/4	_____								
	S 21								
	2004								
	Deposit a magnet in a white plastic case at the base of the stainless steel post.								

**Survey of the Subdivisional Lines,
T. 27 N., R. 24 E., Gila and Salt River Meridian, Arizona**

CHAINS	
80.00	<p>The cor. of secs. 16, 17, 20 and 21.</p> <p>Land, rolling. Soil, sand and sandy clay. Timber, scattered piñon and juniper; undergrowth, sagebrush, cacti and native grasses.</p> <hr/> <p>N. 0°03' W., bet. secs. 16 and 17.</p> <p>Over rolling land.</p>
38.50	Underground water pipeline, bears E. and W.
39.40	Apache County Road C316, a graded road, 20 ft. wide, bears E. and W.
40.00	<p>Point for the 1/4 sec. cor. of secs. 16 and 17.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center;"> <p>T 27 N R 24 E 1/4 S 17 S 16</p> <p>2004</p> </div> <p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p>
80.00	<p>Point for the cor. of secs. 8, 9, 16 and 17.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center;"> <p>T 27 N R 24 E S 8 S 9 S 17 S 16</p> <p>2004</p> </div> <p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p> <p>Land, rolling. Soil, sand and sandy clay. Timber, scattered piñon and juniper; undergrowth, sagebrush, cacti and native grasses.</p> <hr/> <p>From the cor. of secs. 9, 10, 15 and 16.</p>

**Survey of the Subdivisional Lines,
T. 27 N., R. 24 E., Gila and Salt River Meridian, Arizona**

CHAINS	
	N. 89°56' W., bet. secs. 9 and 16. Over rolling land.
27.00	Apache County Road C316, a graded road, 20 ft. wide, bears NE and SW.
40.00	Point for the 1/4 sec. cor. of secs. 9 and 16. Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd. <div style="text-align: center;"> T 27 N R 24 E S 9 1/4 ——— S 16 2004 </div>
80.00	Deposit a magnet in a white plastic case at the base of the stainless steel post. The cor. of secs. 8, 9, 16 and 17. Land, rolling. Soil, sand and sandy clay. Timber, scattered piñon and juniper; undergrowth, sagebrush, cacti and native grasses.
	N. 0°03' W., bet. secs. 8 and 9. Over rolling land.
40.00	Point for the 1/4 sec. cor. of secs. 8 and 9. Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd. <div style="text-align: center;"> T 27 N R 24 E 1/4 S 8 S 9 2004 </div>
80.00	Deposit a magnet in a white plastic case at the base of the stainless steel post. Cor. is located 25 lks. W. of a trail road, bears NNE and S. Point for the cor. of secs. 4, 5, 8 and 9.

**Survey of the Subdivisional Lines,
T. 27 N., R. 24 E., Gila and Salt River Meridian, Arizona**

CHAINS

Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam.,
24 ins. in the ground, with brass cap mkd.

T 27 N	R 24 E
S 5	S 4
S 8	S 9

2004

from which

The NE cor. of a wood frame, L-shaped house, 30 x 20 ft.,
bears N. 87 1/2° W., 2.85 chs. dist., the long side bears
WNW.

Deposit a magnet in a white plastic case at the base of the
stainless steel post.

Cor. is located 75 lks. W. and 1.25 chs. N. of Apache County
Road C429, a graded road, 20 ft. wide, bears NE and SW.

Land, rolling.

Soil, sand and sandy clay.

Timber, piñon and juniper; undergrowth, sagebrush, cacti and
native grasses.

From the cor. of secs. 3, 4, 9 and 10.

N. 89°56' W., bet. secs. 4 and 9.

Over rolling land.

40.00

Point for the 1/4 sec. cor. of secs. 4 and 9.

Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam.,
24 ins. in the ground, with brass cap mkd.

T 27 N	R 24 E
S 4	
1/4	_____
S 9	

2004

from which

The NE cor. of wood frame, brick sided house, 61 x 28 ft.,
bears S. 27 1/4° W., 1.72 chs. dist., the long side bears
WNW.

**Survey of the Subdivisional Lines,
T. 27 N., R. 24 E., Gila and Salt River Meridian, Arizona**

CHAINS	
	Deposit a magnet in a white plastic case at the base of the stainless steel post.
61.78	N. right-of-way fence of Arizona State Highway 264, barbed wire, 5 strands, parallels highway.
64.20	Arizona State Highway 264, asphalt pavement, 26 ft. wide, bears SE and NW.
66.79	S. right-of-way fence of Arizona State Highway 264, barbed wire, 5 strands, parallels highway.
80.00	The cor. of secs. 4, 5, 8 and 9. Land, rolling. Soil, sand and sandy clay. Timber, scattered piñon and juniper; undergrowth, sagebrush, cacti and native grasses.
	<hr/>
	N. 0°03' W., bet. secs. 4 and 5. Over rolling and broken land.
9.75	S. right-of-way fence of Arizona State Highway 264, barbed wire, 5 strands, parallels highway.
11.53	Arizona State Highway 264, asphalt pavement, 26 ft. wide, bears SE and NW.
13.28	N. right-of-way fence of Arizona State Highway 264, barbed wire, 5 strands, parallels highway.
40.00	Point for the 1/4 sec. cor. of secs. 4 and 5. Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.
	T 27 N R 24 E 1/4 S 5 S 4 2004
	Deposit a magnet in a white plastic case at the base of the stainless steel post.
50.20	Apache County Road C429, a graded road, 20 ft. wide, bears SSE and NNW.
80.01	The cor. of secs. 4, 5, 32 and 33, on the N. bdy. of the Tp., hereinbefore described.

**Survey of the Subdivisional Lines,
T. 27 N., R. 24 E., Gila and Salt River Meridian, Arizona**

CHAINS	
	<p>Land, rolling and broken. Soil, sand and sandy clay. Timber, piñon and juniper; undergrowth, sagebrush, cacti and native grasses.</p> <hr/> <p>From the cor. of secs. 5, 6, 31 and 32, on the S. bdy. of the Tp., hereinbefore described.</p> <p>N. 0°03' W., bet. secs. 31 and 32.</p> <p>Over rolling land.</p>
40.00	<p>Point for the 1/4 sec. cor. of secs. 31 and 32.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center;"> <p>T 27 N R 24 E 1/4 S 31 S 32</p> <p>2004</p> </div> <p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p>
78.95	<p>Apache County Road C429, a graded road, 26 ft. wide, bears SSE and NNW.</p>
80.00	<p>Point for the cor. of secs. 29, 30, 31 and 32.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 18 ins. below the surface of the ground, with brass cap mkd.</p> <div style="text-align: center;"> <p>T 27 N R 24 E S 30 S 29 S 31 S 32</p> <p>2004</p> </div> <p>from which</p> <p style="margin-left: 40px;">A stainless steel post, 28 ins. long, 2 1/2 ins. diam., set 24 ins. in the ground for a reference monument, bears N. 45°00' E., 20.00 ft. dist., with brass cap mkd. RM T27N R24E S29 20.0 FT. TO COR. 2004 and an arrow pointing to the corner. Deposit a magnet in a white plastic case at the base of the stainless steel post.</p>

**Survey of the Subdivisional Lines,
T. 27 N., R. 24 E., Gila and Salt River Meridian, Arizona**

CHAINS	
	<p>A stainless steel post, 28 ins. long, 2 1/2 ins. diam., set 24 ins. in the ground for a reference monument, bears S. 45°00' W., 65.00 ft. dist., with brass cap mkd. RM T27N R24E S31 65.0 FT. TO COR. 2004 and an arrow pointing to the corner. Deposit a magnet in a white plastic case at the base of the stainless steel post.</p> <p>Deposit a magnet in a white plastic case at the base of the stainless steel post at the sec. cor.</p> <p>Cor. is located 3 lks. E. of the E. edge of Apache County Road C429, a graded road, 26 ft. wide, bears SSE and NNW.</p> <p>Land, rolling. Soil, sand and sandy clay. Timber, scattered piñon and juniper; undergrowth, sagebrush, cacti and native grasses.</p>
40.00	<p>From the cor. of secs. 28, 29, 32 and 33.</p> <p>N. 89°56' W., bet. secs. 29 and 32.</p> <p>Over rolling land.</p> <p>Point for the 1/4 sec. cor. of secs. 29 and 32.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p align="center">T 27 N R 24 E S 29 1/4 ——— S 32</p> <p align="center">2004</p>
80.00	<p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p> <p>The cor. of secs. 29, 30, 31 and 32.</p> <p>Land, rolling. Soil, sand and sandy clay. Timber, scattered piñon and juniper; undergrowth, sagebrush, cacti and native grasses.</p>
40.00	<p>N. 89°56' W., bet. secs. 30 and 31.</p> <p>Over rolling land.</p> <p>Point for the 1/4 sec. cor. of secs. 30 and 31.</p>

**Survey of the Subdivisional Lines,
T. 27 N., R. 24 E., Gila and Salt River Meridian, Arizona**

CHAINS	
	<p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T 27 N R 24 E S 30 1/4 ——— S 31</p> <p style="text-align: center;">2004</p> <p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p>
81.56	<p>The cor. of secs. 25, 30, 31 and 36, on the W. bdy. of the Tp., monumented with a stainless steel post, 2 1/2 ins. diam., firmly set, projecting 4 ins. above ground, with brass cap mkd. T27N R23E R24E S25 S30 S36 S31 2002.</p> <p>Add the marks 2004 to the brass cap.</p> <p>Land, rolling. Soil, sand and sandy clay. Timber, scattered piñon and juniper; undergrowth, sagebrush, cacti and native grasses.</p> <hr/> <p>From the cor. of secs. 29, 30, 31 and 32.</p> <p>N. 0°03' W., bet. secs. 29 and 30.</p> <p>Over rolling land.</p>
40.00	<p>Point for the 1/4 sec. cor. of secs. 29 and 30.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T 27 N R 24 E 1/4 S 30 S 29</p> <p style="text-align: center;">2004</p> <p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p>
80.00	<p>Point for the cor. of secs. 19, 20, 29 and 30.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p>

**Survey of the Subdivisional Lines,
T. 27 N., R. 24 E., Gila and Salt River Meridian, Arizona**

CHAINS									
	<table border="1"> <tr> <td>T 27 N</td> <td>R 24 E</td> </tr> <tr> <td>S 19</td> <td>S 20</td> </tr> <tr> <td>S 30</td> <td>S 29</td> </tr> </table>	T 27 N	R 24 E	S 19	S 20	S 30	S 29		
T 27 N	R 24 E								
S 19	S 20								
S 30	S 29								
	2004								
	Deposit a magnet in a white plastic case at the base of the stainless steel post.								
	Land, rolling. Soil, sand and sandy clay. Timber, scattered piñon and juniper; undergrowth, sagebrush, cacti and native grasses.								
	<hr/>								
	From the cor. of secs. 20, 21, 28 and 29.								
	N. 89°56' W., bet. secs. 20 and 29.								
	Over rolling land.								
40.00	Point for the 1/4 sec. cor. of secs. 20 and 29.								
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.								
	<table border="1"> <tr> <td>T 27 N</td> <td>R 24 E</td> </tr> <tr> <td>S 20</td> <td></td> </tr> <tr> <td>1/4</td> <td>—</td> </tr> <tr> <td>S 29</td> <td></td> </tr> </table>	T 27 N	R 24 E	S 20		1/4	—	S 29	
T 27 N	R 24 E								
S 20									
1/4	—								
S 29									
	2004								
	Deposit a magnet in a white plastic case at the base of the stainless steel post.								
80.00	The cor. of secs. 19, 20, 29 and 30.								
	Land, rolling. Soil, sand and sandy clay. Timber, scattered piñon and juniper; undergrowth, sagebrush, cacti and native grasses.								
	<hr/>								
	N. 89°56' W., bet. secs. 19 and 30.								
	Over rolling land.								
31.30	Apache County Road C429, a graded road, 25 ft. wide, bears SE and NW.								
40.00	Point for the 1/4 sec. cor. of secs. 19 and 30.								

**Survey of the Subdivisional Lines,
T. 27 N., R. 24 E., Gila and Salt River Meridian, Arizona**

CHAINS	
	<p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T 27 N R 24 E S 19 1/4 ——— S 30</p> <p style="text-align: center;">2004</p> <p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p>
81.46	<p>The cor. of secs. 19, 24, 25 and 30, on the W. bdy. of the Tp., monumented with a stainless steel post, 2 1/2 ins. diam., firmly set, projecting 4 ins. above ground, with brass cap mkd. T27N R23E R24E S24 S19 S25 S30 2002.</p> <p>Add the marks 2004 to the brass cap.</p> <p>Cor. is located 75 lks. S. of a trail road, bears NNE and SSW.</p> <p>Land, rolling. Soil, sand and sandy clay. Timber, scattered piñon and juniper; undergrowth, sagebrush, cacti and native grasses.</p> <hr/> <p>From the cor. of secs. 19, 20, 29 and 30.</p> <p>N. 0°03' W., bet. secs. 19 and 20.</p> <p>Over rolling land.</p>
40.00	<p>Point for the 1/4 sec. cor. of secs. 19 and 20.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T 27 N R 24 E 1/4 S 19 S 20</p> <p style="text-align: center;">2004</p> <p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p>
80.00	<p>Point for the cor. of secs. 17, 18, 19 and 20.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p>

**Survey of the Subdivisional Lines,
T. 27 N., R. 24 E., Gila and Salt River Meridian, Arizona**

CHAINS	
	T 27 N R 24 E S 18 S 17 S 19 S 20 2004
	Deposit a magnet in a white plastic case at the base of the stainless steel post. Cor. is located 5 lks. W. of a trail road, bears SSE and NNW. Land, rolling. Soil, sand and sandy clay. Timber, scattered piñon and juniper; undergrowth, sagebrush, cacti and native grasses.
	<hr/> From the cor. of secs. 16, 17, 20 and 21. N. 89°56' W., bet. secs. 17 and 20. Over rolling land.
37.35	E. bank of Sand Dunes Wash, 15 ft. high, bears SE and NW.
40.00	Point for the 1/4 sec. cor. of secs. 17 and 20. Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.
	T 27 N R 24 E S 17 1/4 ——— S 20 2004
	Deposit a magnet in a white plastic case at the base of the stainless steel post. Cor. is located 1.80 chs. W. of the W. bank of Sand Dunes Wash, 15 ft. high, bears SSE and NN.
80.00	The cor. of secs. 17, 18, 19 and 20. Land, rolling. Soil, sand and sandy clay. Timber, scattered piñon and juniper; undergrowth, sagebrush, cacti and native grasses.
	<hr/> N. 89°56' W., bet. secs. 18 and 19.

**Survey of the Subdivisional Lines,
T. 27 N., R. 24 E., Gila and Salt River Meridian, Arizona**

CHAINS	
	Over rolling land.
40.00	Point for the 1/4 sec. cor. of secs. 18 and 19. Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd. <div style="text-align: center;"> T 27 N R 24 E S 18 1/4 ——— S 19 2004 </div>
	Deposit a magnet in a white plastic case at the base of the stainless steel post.
52.10	Apache County Road C429, a graded road, 25 ft. wide, bears N. and S.
81.38	The cor. of secs. 13, 18, 19 and 24, on the W. bdy. of the Tp., monumented with a stainless steel post, 2 1/2 ins. diam., firmly set, projecting 5 ins. above ground, with brass cap mkd. T27N R23E R24E S13 S18 S24 S19 2002. Add the marks 2004 to the brass cap. Land, rolling. Soil, sand and sandy clay. Timber, scattered piñon and juniper; undergrowth, sagebrush, cacti and native grasses.

	N. 0°03' W., bet. secs. 17 and 18.
	Over rolling land.
23.30	S. bank of Sand Dunes Wash, 15 ft. high, bears E. and W.
24.30	N. bank of Sand Dunes Wash, 15 ft. high, bears E. and W.
40.00	True point for the 1/4 sec. cor. of secs. 17 and 18, falls in a wash, 21 ft. wide, 20 ft. deep, where it is impracticable to establish a permanent monument. From this true point, the point selected for the witness cor. to 1/4 sec cor. of secs. 17 and 18, bears S. 40°00' E., 1.00 ch. dist. Set a brass tablet, 3 1/4 ins. diam., 2 1/2 ins. stem, cemented in place, in a drill hole, in sandstone bedrock, with top mkd.

**Survey of the Subdivisional Lines,
T. 27 N., R. 24 E., Gila and Salt River Meridian, Arizona**

CHAINS	
	W C T 27 N R 24 E ↙ 1/4 S 18 S 17 2004
80.00	Deposit a magnet in a white plastic case at the base of the brass tablet. Point for the cor. of secs. 7, 8, 17 and 18. Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd. T 27 N R 24 E S 7 S 8 S 18 S 17 2004 Deposit a magnet in a white plastic case at the base of the stainless steel post. Land, rolling. Soil, sand and sandy clay. Timber, piñon and juniper; undergrowth, sagebrush, cacti and native grasses.
40.00	<hr/> From the cor. of secs. 8, 9, 16 and 17. N. 89°56' W., bet. secs. 8 and 17. Over rolling land. Point for the 1/4 sec. cor. of secs. 8 and 17. Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd. T 27 N R 24 E S 8 1/4 ——— S 17 2004 Deposit a magnet in a white plastic case at the base of the stainless steel post.

**Survey of the Subdivisional Lines,
T. 27 N., R. 24 E., Gila and Salt River Meridian, Arizona**

CHAINS	
61.40	Apache County Road C316, a graded road, 20 ft. wide, bears NNE and SSW.
80.00	The cor. of secs. 7, 8, 17 and 18. Land, rolling. Soil, sand and sandy clay. Timber, piñon and juniper; undergrowth, sagebrush, cacti and native grasses.
	N. 89°56' W., bet. secs. 7 and 18. Over rolling and broken land.
8.60	Apache County Road C429, a graded road, 25 ft. wide, bears NE and SW.
40.00	Point for the 1/4 sec. cor. of secs. 7 and 18. Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.
	T 27 N R 24 E S 7 1/4 ——— S 18 2004
	from which <div style="margin-left: 40px;">A metal water tank, 25 ft. diam., 7 ft. high, bears N. 76 1/2° E., 1.25 chs. dist.</div> Deposit a magnet in a white plastic case at the base of the stainless steel post.
42.70	E. rim of Steamboat Canyon, bears ENE and WSW.
81.28	The cor. of secs. 7, 12, 13 and 18, on the W. bdy. of the Tp., monumented with a stainless steel post, 2 1/2 ins. diam., firmly set, projecting 4 ins. above ground, with brass cap mkd. T27N R23E R24E S12 S7 S13 S18 2002. Add the marks 2004 to the brass cap.

**Survey of the Subdivisional Lines,
T. 27 N., R. 24 E., Gila and Salt River Meridian, Arizona**

CHAINS	
	<p>Land, rolling and broken. Soil, sand and sandy clay. Timber, piñon and juniper; undergrowth, sagebrush, cacti and native grasses.</p> <hr/> <p>From the cor. of secs. 7, 8, 17 and 18. N. 0°03' W., bet. secs. 7 and 8. Over rolling and broken land.</p>
8.10	Apache County Road C429, a graded road, 25 ft. wide, bears NE and SW.
40.00	<p>Point for the 1/4 sec. cor. of secs. 7 and 8. Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T 27 N R 24 E 1/4 S 7 S 8 2004</p> <p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p>
64.33	S. right-of-way fence of Arizona State Highway 264, barbed wire, 5 strands, parallels highway.
66.00	Arizona State Highway 264, asphalt pavement, 26 ft. wide, bears ENE and WSW.
67.47	N. right-of-way fence of Arizona State Highway 264, barbed wire, 5 strands, parallels highway.
80.00	<p>Point for the cor. of secs. 5, 6, 7 and 8. Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T 27 N R 24 E S 6 S 5 S 7 S 8 2004</p> <p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p>

**Survey of the Subdivisional Lines,
T. 27 N., R. 24 E., Gila and Salt River Meridian, Arizona**

CHAINS	
	<p>Land, rolling and broken. Soil, sand and sandy clay. Timber, piñon and juniper; undergrowth, sagebrush, cacti and native grasses.</p> <hr/> <p>From the cor. of secs. 4, 5, 8 and 9. N. 89°56' W., bet. secs. 5 and 8. Over rolling and broken land.</p>
40.00	<p>Point for the 1/4 sec. cor. of secs. 5 and 8. Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center;"> <p>T 27 N R 24 E S 5 1/4 ——— S 8</p> <p>2004</p> </div> <p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p>
58.07	S. right-of-way fence of Arizona State Highway 264, barbed wire, 5 strands, parallels highway.
60.53	Arizona State Highway 264, asphalt surface, 25 ft. wide, bears NE and SW.
62.89	N. right-of-way fence of Arizona State Highway 264, barbed wire, 5 strands, parallels highway.
80.00	<p>The cor. of secs. 5, 6, 7 and 8. Land, rolling and broken. Soil, sand and sandy clay. Timber, piñon and juniper; undergrowth, sagebrush, cacti and native grasses.</p> <hr/> <p>N. 89°56' W., bet. secs. 6 and 7. Over rolling and broken land.</p>
40.00	<p>Point for the 1/4 sec. cor. of secs. 6 and 7. Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p>

**Survey of the Subdivisional Lines,
T. 27 N., R. 24 E., Gila and Salt River Meridian, Arizona**

CHAINS	
81.19	<p align="center">T 27 N R 24 E S 6 1/4 — S 7</p> <p align="center">2004</p> <p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p> <p>The cor. of secs. 1, 6, 7 and 12, on the W. bdy. of the Tp., monumented with a stainless steel post, 2 1/2 ins. diam., firmly set, projecting 4 ins. above ground, with brass cap mkd. T27N R23E R24E S1 S6 S12 S7 2002.</p> <p>Add the marks 2004 to the brass cap.</p> <p>Land, rolling and broken. Soil, sand and sandy clay. Timber, piñon and juniper; undergrowth, sagebrush, cacti and native grasses.</p> <hr/>
40.00	<p>N. 0°03' W., bet. secs. 5 and 6.</p> <p>Over rolling and broken land.</p> <p>Point for the 1/4 sec. cor. of secs. 5 and 6.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p>
80.01	<p align="center">T 27 N R 24 E 1/4 S 6 S 5</p> <p align="center">2004</p> <p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p> <p>The cor. of secs. 5, 6, 31 and 32, on the N. bdy. of the Tp., hereinbefore described.</p> <p>Land, rolling and broken. Soil, sand and sandy clay. Timber, piñon and juniper; undergrowth, sagebrush, cacti and native grasses.</p> <hr/>

T. 27 N., R. 24 E., Gila and Salt River Meridian, Arizona

CHAINS

GENERAL DESCRIPTION

The area surveyed is within the Navajo Indian Reservation and approximately three miles E. of the community of Steamboat, Arizona. The terrain is mostly rolling with an area of broken land in the northwestern portion of the township, where Steamboat Canyon originates and drains southwest. Most of the drainage is southerly through the central portion of the township with Sand Dunes Wash being the main drainage. The most northern portion of the township drains northerly into Steamboat Canyon.

The elevations varies from 6400 to 6800 feet above sea level. The soil is sand and sandy clay, with sandstone outcrops and ledges along the slopes of the mesas and canyons. The timber consists of piñon and juniper in the northwestern portion of the township with a sparse growth in the central portion of the township where it is mostly rolling hills. Undergrowth consists of greasewood and rabbit brush in the valleys and cacti and dense areas of sagebrush at the higher elevations.

Principal access to the township is provided by Arizona State Highway 264. The highway enters the township in section 1 and extends westerly where it exits in section 7. There are Apache County Roads branching off this major highway with numerous trail roads throughout the township. Much of this area is used for grazing of livestock. There are numerous permanent residences throughout the entire township. There is no mining activity in the township.

The mean magnetic declination of $11\ 1/2^\circ$ E. was derived from the computer program GEOMAGIX, utilizing the World Magnetic Model for Epoch 2000 for the dates of survey.

CERTIFICATE OF SURVEY

I, Jones Curtiss, Cadastral Surveyor, HEREBY CERTIFY upon honor, that in pursuance of special instructions bearing date of the 17th day of December, 2003, I have surveyed the south and north boundaries and the subdivisional lines, T. 27 N., R. 24 E., of the Gila and Salt River Meridian, in the State of Arizona, which are represented in the foregoing field notes as having been executed by me and under my direction. Said survey has been made in strict conformity with said special instructions, the Manual of Instructions for the Survey of the Public Lands of the United States, 1973, and in specific manner described in the foregoing field notes.

July 12, 2005
(Date)

Jones Curtiss
(Cadastral Surveyor)

CERTIFICATE OF APPROVAL

BUREAU OF LAND MANAGEMENT
Phoenix, Arizona

The foregoing field notes of the survey of the south and north boundaries and the subdivisional lines, T. 27 N., R. 24 E., Gila and Salt River Meridian, in the State of Arizona, executed by Jones Curtiss, Cadastral Surveyor, having been critically examined and found correct, are hereby approved.

July 19, 2005
(Date)

Stephen K. Hansen
(Acting Chief Cadastral Surveyor of Arizona)

~~CERTIFICATE OF TRANSCRIPT~~

~~I CERTIFY That the foregoing transcript of the field notes of the above described surveys in T. 27 N., R. 24 E., Gila and Salt River Meridian, Arizona, is a true copy of the original field notes.~~

~~_____~~
~~(Date)~~

~~_____~~
~~(Acting Chief Cadastral Surveyor of Arizona)~~