

ORIGINAL

**UNITED STATES  
DEPARTMENT OF THE INTERIOR  
BUREAU OF LAND MANAGEMENT**

FIELD NOTES  
OF THE  
SURVEY OF THE SOUTH, EAST AND NORTH BOUNDARIES,  
AND  
THE SUBDIVISIONAL LINES  
OF  
TOWNSHIP 27 NORTH, RANGE 27 EAST,  
OF THE GILA AND SALT RIVER MERIDIAN,  
IN THE STATE OF ARIZONA

**EXECUTED BY**

**Leonard R. Sandoval, Cadastral Surveyor**

Under Special Instructions dated May 6, 2003, approved May 6, 2003, which provided for the surveys included under Group No. 902, and assignment instructions dated May 6, 2003.

**Survey commenced July 22, 2003**

**Survey completed August 27, 2003**

**INDEX DIAGRAM**

TOWNSHIP 27 NORTH                      RANGE 27 EAST  
 GILA AND SALT RIVER MERIDIAN, ARIZONA

23	22	21	20	19	18
79 <b>6</b>	80 <b>5</b>	59 <b>4</b>	50 <b>3</b>	42 <b>2</b>	33 <b>1</b> 17
77	76	58	50	41	32
79 <b>7</b>	76 <b>8</b>	57 <b>9</b>	49 <b>10</b>	40 <b>11</b>	31 <b>12</b> 16
73	72	57	48	40	31
74 <b>18</b>	71 <b>17</b>	56 <b>16</b>	47 <b>15</b>	38 <b>14</b>	30 <b>13</b> 15
69	68	55	46	38	29
70 <b>19</b>	67 <b>20</b>	54 <b>21</b>	46 <b>22</b>	37 <b>23</b>	28 <b>24</b> 14
65	64	54	45	36	27
66 <b>30</b>	63 <b>29</b>	53 <b>28</b>	44 <b>27</b>	35 <b>26</b>	26 <b>25</b> 13
61	60	52	43	35	26
62 <b>31</b>	59 <b>32</b>	51 <b>33</b>	42 <b>34</b>	34 <b>35</b>	25 <b>36</b> 12
11	10	8	7	6	4

**T. 27 N., R. 27 E., Gila and Salt River Meridian, Arizona**

FEET

The following field notes describe the survey of the south, east and north boundaries, and the subdivisional lines of Township 27 North, Range 27 East, Gila and Salt River Meridian, Arizona.

The history of surveys pertaining to this survey is as follows:

Survey of the north boundary of Township 26 North, Range 28 East was done by Frank Follman in 1883. Survey of the south boundary and a portion of the west boundary was done by Samuel E. Day in 1904. Resurvey of a portion of the west boundary was done by Frederick C. Miller in 1915. Dependent resurvey and completion of the west boundary was done by Leonard R. Sandoval in 1990.

The survey was executed in accordance with the specifications as set forth in the Manual of Instructions for the Survey of the Public Lands of the United States, 1973, and the Special Instructions dated May 6, 2003, for Group No. 902, Arizona.

The true meridian direction and length of all lines were determined by real time kinematic global positioning system observations using Trimble Navigation 5700 model receivers.

Preliminary to the survey, the lines of the prior surveys were retraced and search was made for all corners and other calls of record. Identified corners were remonumented in their original positions. The retracement data were thoroughly verified and only the true line field notes are given herein.

Geodetic control was derived from Global Positioning System (GPS) static observations post processed by National Geodetic Survey, Online Positioning User Service (OPUS), utilizing Continuously Operating Reference Stations (CORS) "FLAGSTAFF1", "AZTEC", and "PIE\_TOWN". The NAD 83(CORS96) CEPOCH:2002), geographic position of the southeast township cor., is as follows:

Latitude: 35°41'33.71" N.                      Longitude: 109°24'09.19" W.

The mean magnetic declination is 11 1/4° E.

---

**Survey of the South Boundary,  
T. 27 N., R. 27 E., Gila and Salt River Meridian, Arizona**

FEET

Superseding the survey executed by  
Samuel E. Day, in 1904

---


NOTE: During the 1915 original survey of T. 26 N., R. 26 E., a new township corner of Tps. 26 and 27 N., Rs. 26 and 27 E., was established in order to avoid complications in later surveys. The 1915 survey did not utilize the 1904 Tp. cor. because it was not within limits during the survey of the E. bdy. of T. 26 N., R. 26 E. Utilizing this new township corner during this survey would yield the south boundary to be out of rectangular limits for alinement to use for the subdivision of this township. The 1904 survey was superseded by the 1915 survey thus rendering the 1904 survey of this boundary of no consideration.

Beginning at the cor. of Tps. 26 and 27 N., Rs. 27 and 28 E., determined at record bearing and distance from the remains of the 1883 bearing tree recovered in 1904

A badly decayed piñon stump, 15 ins. diam., projecting 5 ft. above ground, bears S. 42° E., 1.07 chs. dist., with scribe marks 26N R28E S6 BT visible on open blaze.

At the cor. point

Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.



2003

Deposit a magnet, in a white plastic case, at the base of the stainless steel post.

West, bet. secs. 1 and 36.

Over rolling land.

38.38 Graded road, 15 ft. wide, bears NNE and SSW.

40.00 Point for the 1/4 sec. cor. of secs. 1 and 36.

Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.

**Survey of the South Boundary,  
T. 27 N., R. 27 E., Gila and Salt River Meridian, Arizona**

FEET	<p style="text-align: center;">T 27 N R 27 E S 36 1/4 ——— S 1 T 26 N</p> <p style="text-align: center;">2003</p> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p> <p>From this cor. point, the bearing trees of the abandoned 1904 survey</p> <p style="padding-left: 40px;">A piñon, 12 ins. diam., bears N. 47° E., 91 lks. dist., with scribe marks 1/4 S36 BT visible on open blaze. Defaced the scribe marks.</p> <p style="padding-left: 40px;">A piñon, 9 ins. diam., bears N. 36 3/4° W., 38 lks. dist., with scribe marks 1/4 S1 BT visible on open blaze. Defaced the scribe marks.</p> <p>There is no remaining evidence of the abandoned 1904 piñon post 1/4 sec. cor.</p>
80.00	<p>Point for the cor. of secs. 1, 2, 35, and 36.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T 27 N R 27 E S 35   S 36 —   — S 2   S 1 T 26 N</p> <p style="text-align: center;">2003</p> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p> <p>From this cor. point, the remains of bearing trees of the abandoned 1904 survey</p> <p style="padding-left: 40px;">A root hole, bears N. 50 1/2° E., 1.575 chs. dist., with a fallen, badly decayed piñon, 8 ins. diam., alongside, with no scribe marks on open blaze.</p> <p style="padding-left: 40px;">A root hole, bears N. 87° E., 82 lks. dist., with remains of fallen, badly decayed piñon, nearby, with scribe marks T26N R27E S1 BT visible on open blaze. Defaced the scribe marks.</p>

**Survey of the South Boundary,  
T. 27 N., R. 27 E., Gila and Salt River Meridian, Arizona**

FEET	
	<p>A root hole, bears S. 73 1/2° E., 63 lks. dist., with a fallen, badly decayed piñon, 6 ins. diam., alongside, with scribe marks T26N R27E S2 BT visible on open blaze. Defaced the scribe marks.</p> <p>There is no remaining evidence of the abandoned 1904 piñon post sec. cor.</p> <p>Land, rolling. Soil, sandy and rocky clay. Timber, ponderosa pine, piñon, juniper, and Gambel oak; undergrowth, brush and native grasses.</p> <hr/> <p>West, bet. secs. 2 and 35.</p> <p>Over rolling land.</p>
40.00	<p>Point for the 1/4 sec. cor. of secs. 2 and 35.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T 27 N R 27 E S 35 1/4 ——— S 2 T 26 N</p> <p style="text-align: center;">2003</p> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p> <p>From this cor. point, the bearing trees of the abandoned 1904 survey</p> <p style="padding-left: 40px;">A dead forked piñon, 18 ins. diam., bears N. 11 1/2° E., 33 lks. dist., with scribe marks 1/4 S2 BT visible on partially healed blaze. Defaced the scribe marks.</p> <p style="padding-left: 40px;">A dead piñon, 11 ins. diam., bears N. 29° E., 1.58 chs. dist., with scribe marks 1/4 S35 BT visible on open blaze. Defaced the scribe marks.</p> <p>The remains of the abandoned 1904 1/4 sec. cor., a badly decayed piñon post, 17 x 4 x 2 ins., lying loose on the ground, mkd. S 4. Destroyed the old post.</p>
80.00	<p>Point for the cor. of secs. 2, 3, 34, and 35.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p>

**Survey of the South Boundary,  
T. 27 N., R. 27 E., Gila and Salt River Meridian, Arizona**

FEET	
	T 27 N R 27 E S 34   S 35 S 3   S 2 T 26 N  2003
	Deposit a magnet, in a white plastic case, at the base of the stainless steel post.  From this cor. point, the sec. cor. of the abandoned 1904 survey, bears N. 58°16' E., 82 lks. dist., monumented with a sandstone, 8 x 4 ins., firmly set, flush with the surface of the ground, with top broken and lying loose on the ground, 12 x 11 x 4 ins., mkd. with 4 and 2 grooves on opposite faces. Destroyed the sandstone and bury in place.  Land, rolling. Soil, sandy and rocky clay. Timber, scattered ponderosa pine, piñon, juniper, and Gambel oak; undergrowth, brush and native grasses.
	<hr/> West, bet. secs. 3 and 34.  Over rolling land.
4.65	Graded road, 15 ft. wide, bears SSE and NNW.
5.05	Trail road, bears SE and NW.
32.05	Fish Wash, 50 ft. wide, 5 ft. deep, drains NW.
40.00	Point for the 1/4 sec. cor. of secs. 3 and 34.
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.
	T 27 N R 27 E S 34 1/4 ——— S 3 T 26 N  2003
	Deposit a magnet, in a white plastic case, at the base of the stainless steel post.  The 1/4 sec. cor. of the abandoned 1904 survey, a sandstone, 20 x 11 x 4 ins., lying loose on the ground, mkd. 1/4 on wide face. Destroyed the sandstone. There is no remaining evidence of the 1904 bearing trees.

**Survey of the South Boundary,  
T. 27 N., R. 27 E., Gila and Salt River Meridian, Arizona**

FEET									
52.70	Apache County Road C450, a graded road, 20 ft. wide, bears N. and S.								
70.45	Trail road, bears SE and NW.								
71.70	Trail road, bears NNE and SSW.								
80.00	Point for the cor. of secs. 3, 4, 33, and 34.  Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.  <div style="text-align: center;"> <table border="1"> <tr> <td>T 27 N</td> <td>R 27 E</td> </tr> <tr> <td>S 33</td> <td>S 34</td> </tr> <tr> <td>S 4</td> <td>S 3</td> </tr> <tr> <td colspan="2">T 26 N</td> </tr> </table> <p>2003</p> </div> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p> <p>From this cor. point, the remaining bearing trees of the abandoned 1904 survey</p> <p style="padding-left: 40px;">A root hole, bears N. 48 1/2° E., 3.25 chs. dist., with a fallen badly decayed piñon, 12 ins. diam., 4 1/2 ft. long, alongside, with scribe marks BT visible on open blaze. Defaced the scribe marks.</p> <p style="padding-left: 40px;">A piñon, 12 ins. diam., bears S. 34° E., 1.40 chs. dist., with illegible scribe marks on healed blaze. Defaced the scribe marks.</p> <p style="padding-left: 40px;">A root hole, bears S. 79 1/4° W., 1.89 chs. dist., with remains of a fallen badly decayed piñon, 8 ins. diam., 3 1/2 ft. long, alongside, with scribe marks T26N R27E S4 BT visible on open blaze. Defaced the scribe marks.</p> <p>There is no remaining evidence of the abandoned 1904 piñon post sec. cor.</p> <p>Land, rolling. Soil, sandy and rocky clay. Timber, scattered piñon, juniper, and Gambel oak; undergrowth, brush and native grasses.</p> <hr/> <p>West, bet. secs. 4 and 33.</p> <p>Over rolling land.</p>	T 27 N	R 27 E	S 33	S 34	S 4	S 3	T 26 N	
T 27 N	R 27 E								
S 33	S 34								
S 4	S 3								
T 26 N									
40.00	Point for the 1/4 sec. cor. of secs. 4 and 33.								



**Survey of the South Boundary,  
T. 27 N., R. 27 E., Gila and Salt River Meridian, Arizona**

FEET	
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.
	T 27 N R 27 E S 33 1/4 ——— S 4 T 26 N  2003
	Deposit a magnet, in a white plastic case, at the base of the stainless steel post.
	There is no remaining evidence of the abandoned 1904 piñon post 1/4 sec. cor. or bearing trees.
50.00	Trail road, bears N. and S.
54.60	Trail road, bears ENE and WSW.
56.70	Trail road, bears SE and NW.
72.40	Graded road, 15 ft. wide, bears N and S.
74.80	Haakai Daachaahi Wash, 25 ft. wide, 5 ft. deep, drains N.
80.00	Point for the cor. of secs. 4, 5, 32, and 33.
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.
	T 27 N R 27 E S 32   S 33 ———   ——— S 5   S 4 T 26 N  2003
	Deposit a magnet, in a white plastic case, at the base of the stainless steel post.
	From this cor. point, the remaining bearing trees of the abandoned 1904 survey
	A burnt root hole, bears N. 24 1/4° E., 5.21 chs. dist., with a fallen, badly charred forked juniper, alongside.
	A root hole, bears S. 71 1/2° W., 3.55 chs. dist., with a fallen, dead forked piñon, 16 ins. diam., alongside, with scribe marks T26N R27E S4, visible on partially healed blaze. Defaced the scribe marks.

**Survey of the South Boundary,  
T. 27 N., R. 27 E., Gila and Salt River Meridian, Arizona**

FEET	
	<p>There is no remaining evidence of the abandoned 1904 piñon post sec. cor.</p> <p>Land, rolling. Soil, sandy and rocky clay. Timber, scattered piñon and juniper; undergrowth, brush and native grasses.</p> <hr/> <p>West, bet. secs. 5 and 32.</p> <p>Over rolling land.</p>
10.10	Underground waterline, bears NNE and SSW.
40.00	<p>Point for the 1/4 sec. cor. of secs. 5 and 32.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center;"> <p>T 27 N R 27 E S 32 1/4 ——— S 5 T 26 N</p> <p>2003</p> </div> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p> <p>There is no remaining evidence of the abandoned 1904 piñon post 1/4 sec. cor or bearing trees.</p>
57.13	High voltage transmission line, bears NE and SW.
80.00	<p>Point for the cor. of secs. 5, 6, 31, and 32.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center;"> <p>T 27 N R 27 E S 31   S 32 S 6   S 5 T 26 N</p> <p>2003</p> </div> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p> <p>From this cor. point, the bearing trees of the abandoned 1904 survey</p>

**Survey of the South Boundary,  
T. 27 N., R. 27 E., Gila and Salt River Meridian, Arizona**

FEET	
	<p>A forked piñon, 15 ins. diam., bears N. 41 1/4° E., 1.18 chs. dist., with scribe marks BT visible on partially healed blaze. Defaced the scribe marks.</p> <p>A forked piñon, 15 ins. diam., bears N. 85° E., 99 lks. dist., with healed blaze.</p> <p>A piñon, 13 ins. diam., bears S. 51° W., 1.23 chs. dist., with healed blaze.</p> <p>A piñon, 9 ins. diam., bears N. 65 1/4° W., 4.43 chs. dist., with healed blaze.</p> <p>There is no remaining evidence of the abandoned 1904 piñon post sec. cor.</p> <p>Land, rolling. Soil, sandy and rocky clay. Timber, scattered piñon and juniper; undergrowth, brush and native grasses.</p> <hr/> <p>West, bet. secs. 6 and 31.</p> <p>Over rolling land.</p>
40.00	<p>Point for the 1/4 sec. cor. of secs. 6 and 31.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p align="center">T 27 N R 27 E S 31 1/4 ——— S 6 T 26 N</p> <p align="center">2003</p> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p> <p>There is no remaining evidence of the abandoned 1904 piñon post 1/4 sec. cor.</p>
46.85	Wash, 50 ft. wide, 7 ft. deep, drains N.
56.15	Trail road, bears SE and NW.
56.95	High voltage transmission line, bears NE and SW.
70.55	Point for the closing cor. of Tps. 26 and 27 N., R. 27 E., only, at intersection with the E. bdy. of T. 27 N., R. 26 E.

**Survey of the South Boundary,  
T. 27 N., R. 27 E., Gila and Salt River Meridian, Arizona**

FEET

Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.

T 27 N	T 27 N
R 26 E	R 27 E
	S 31
S 36	CC
	S 6
	T 26 N

2003

Deposit a magnet, in a white plastic case, at the base of the stainless steel post.

From this cor. point, the bearing trees of the abandoned 1904 survey

A piñon, 10 ins. diam., bears S. 79 1/2° W., 8.01 chs. dist., with healed blaze.

A dead piñon, 16 ins. diam., bears N. 83 1/2° W., 9.07 chs. dist., with scribe marks T27N R26E S36 BT visible on open blaze. Defaced the scribe marks.

A forked piñon, 15 ins. diam. at base, bears N. 59 1/2° W., 7.14 chs. dist., with illegible scribe marks on partially healed blaze. Defaced the scribe marks.

From this same cor. point, the Tp. cor. of Tps. 26 and 27 N., R. 26 E. only, bears S. 0°05' W., 6.375 chs. dist., monumented with an iron post, 3 ins. diam., firmly set, projecting 9 ins. above ground, with brass cap mkd. T27N T26N R26E R27E S36 S1 S6 T26N 1990 2002 1915. Add the marks 2003 to the brass cap.

From this same cor. point, the 1/4 sec. cor. of secs. 31 and 36. T. 27 N., Rs. 26 and 27 E., bears N. 0°05'E, 33.62 chs. dist., hereinafter described.

Land, rolling.

Soil, sandy and gravelly clay.

Timber, scattered piñon and juniper; undergrowth, brush and native grasses.

---

**Survey of the East Boundary,  
T. 27 N., R. 27 E., Gila and Salt River Meridian, Arizona**

---

From the cor. of Tps. 26 and 27 N., Rs. 27 and 28 E., hereinbefore described.

North, bet. secs. 31 and 36.

**Survey of the East Boundary,  
T. 27 N., R. 27 E., Gila and Salt River Meridian, Arizona**

FEET	
	Over rolling land.
40.00	Point for the 1/4 sec. cor. of secs. 31 and 36.  Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 25 ins. in the ground, with brass cap mkd.  <div style="text-align: center;">           T 27 N            R 27 E    R 28 E                  1/4            S 36   S 31             2003         </div>
46.10	Deposit a magnet, in a white plastic case, at the base of the stainless steel post.  Graded road, 20 ft. wide, bears NNE and SSW.
80.00	Point for the cor. of secs. 25, 30, 31, and 36.  Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.  <div style="text-align: center;">           T 27 N            R 27 E   R 28 E            S 25   S 30            -----            S 36   S 31             2003         </div>
	Deposit a magnet, in a white plastic case, at the base of the stainless steel post.  Land, rolling. Soil, sandy and rocky clay. Timber, ponderosa pine, piñon, juniper, and Gambel oak; undergrowth, brush and native grasses.
	----- North, bet. secs. 25 and 30.
40.00	Over rolling land.  Point for the 1/4 sec. cor. of secs. 25 and 30.  Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.

**Survey of the East Boundary,  
T. 27 N., R. 27 E., Gila and Salt River Meridian, Arizona**

FEET	
	T 27 N R 27 E    R 28 E 1/4 S 25   S 30  2003
	Deposit a magnet, in a white plastic case, at the base of the stainless steel post.
56.03	S. right-of-way fence of Arizona State Highway 264, barbed wire, 5 strand, parallels the highway.
57.53	Arizona State Highway 264, asphalt pavement, 28 ft. wide, bears E. and W.
59.05	N. right-of-way fence of Arizona State Highway 264, barbed wire, 5 strand, parallels the highway.
66.05	Navajo Route 203, a graded road, 25 ft. wide, bears NNE and SSW.
72.00	Navajo Route 203, a graded road, 25 ft. wide, bears SE and NW.
80.00	Point for the cor. of secs. 19, 24, 25, and 30.  Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.
	T 27 N R 27 E   R 28 E S 24   S 19 S 25   S 30  2003
	Deposit a magnet, in a white plastic case, at the base of the stainless steel post.
	Land, rolling. Soil, sandy and rocky clay. Timber, scattered ponderosa pine, piñon, juniper, and Gambel oak; undergrowth, brush and native grasses.
	North, bet. secs. 19 and 24.  Over gently rolling land.
40.00	Point for the 1/4 sec. cor. of secs. 19 and 24.  Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.

**Survey of the East Boundary,  
T. 27 N., R. 27 E., Gila and Salt River Meridian, Arizona**

FEET	
	T 27 N R 27 E    R 28 E 1/4 S 24   S 19  2003
	Deposit a magnet, in a white plastic case, at the base of the stainless steel post.
75.30	Trail road, bears ESE and WNW.
80.00	Point for the cor. of secs. 13, 18, 19, and 24.
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.
	T 27 N R 27 E   R 28 E S 13   S 18 S 24   S 19  2003
	Deposit a magnet, in a white plastic case, at the base of the stainless steel post.
	Land, gently rolling. Soil, sandy and rocky clay. Timber, scattered piñon, juniper, and Gambel oak; undergrowth, brush and native grasses.
	North, bet. secs. 13 and 18.
	Over rolling and broken land.
38.40	S. rim of Kinlichee Creek Canyon, top of sandstone ledge, bears ESE and WNW; thence descend abruptly into the canyon.
40.00	Point for the 1/4 sec. cor. of secs. 13 and 18.
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.
	T 27 N R 27 E    R 28 E 1/4 S 13   S 18  2003

**Survey of the East Boundary,  
T. 27 N., R. 27 E., Gila and Salt River Meridian, Arizona**

FEET									
	<p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p> <p>Cor. is located 30 lks. S. of Kinlichee Creek, a wash, 12 ft. wide, 2 ft. deep, drains NW.</p>								
42.70	N. rim of Kinlichee Creek Canyon, top of sandstone ledge, bears ENE and WSW; thence over rolling land.								
80.00	<p>Point for the cor. of secs. 7, 12, 13, and 18.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center; margin: 10px 0;"> <table style="border-collapse: collapse; margin: auto;"> <tr><td colspan="2">T 27 N</td></tr> <tr><td style="border-right: 1px solid black; padding: 0 5px;">R 27 E</td><td style="padding: 0 5px;">R 28 E</td></tr> <tr><td style="border-right: 1px solid black; padding: 0 5px;">S 12</td><td style="padding: 0 5px;">S 7</td></tr> <tr><td style="border-right: 1px solid black; padding: 0 5px;">S 13</td><td style="padding: 0 5px;">S 18</td></tr> </table> <p>2003</p> </div> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p> <p>Land, rolling and broken. Soil, sandy and rocky clay with sandstone outcrops. Timber, scattered ponderosa pine, piñon, juniper, and Gambel oak; undergrowth, brush and native grasses.</p> <hr style="width: 50%; margin: 10px auto;"/> <p>North, bet. secs. 7 and 12.</p> <p>Over rolling land.</p>	T 27 N		R 27 E	R 28 E	S 12	S 7	S 13	S 18
T 27 N									
R 27 E	R 28 E								
S 12	S 7								
S 13	S 18								
38.90	Woven wire fence with barbed wire, 2 strand, bears NNE and SSW; enter a cultivated field.								
40.00	<p>Point for the 1/4 sec. cor. of secs. 7 and 12.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center; margin: 10px 0;"> <table style="border-collapse: collapse; margin: auto;"> <tr><td colspan="2">T 27 N</td></tr> <tr><td style="border-right: 1px solid black; padding: 0 5px;">R 27 E</td><td style="padding: 0 5px;">R 28 E</td></tr> <tr><td colspan="2" style="text-align: center; padding: 0 5px;">1/4</td></tr> <tr><td style="border-right: 1px solid black; padding: 0 5px;">S 12</td><td style="padding: 0 5px;">S 7</td></tr> </table> <p>2003</p> </div> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p>	T 27 N		R 27 E	R 28 E	1/4		S 12	S 7
T 27 N									
R 27 E	R 28 E								
1/4									
S 12	S 7								



**Survey of the East Boundary,  
T. 27 N., R. 27 E., Gila and Salt River Meridian, Arizona**

FEET													
	Cor. is located on N. edge of cultivated field.												
40.38	Woven wire fence with barbed wire, 2 strand, bears ESE and WNW; the N. fence of cultivated field.												
79.05	Navajo Route 203, a graded road, 23 ft. wide, bears ENE and WSW.												
80.00	Point for the cor. of secs. 1, 6, 7, and 12.  Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.												
	<table border="0"> <tr><td></td><td align="center">T 27 N</td><td></td></tr> <tr><td></td><td align="center">R 27 E   R 28 E</td><td></td></tr> <tr><td></td><td align="center">S 1   S 6</td><td></td></tr> <tr><td></td><td align="center">S 12   S 7</td><td></td></tr> </table>		T 27 N			R 27 E   R 28 E			S 1   S 6			S 12   S 7	
	T 27 N												
	R 27 E   R 28 E												
	S 1   S 6												
	S 12   S 7												
	2003												
	Deposit a magnet, in a white plastic case, at the base of the stainless steel post.												
	Land, rolling. Soil, sandy and rocky clay with sandstone outcrops. Timber, ponderosa pine, piñon, juniper, and Gambel oak; undergrowth, brush and native grasses.												
	<hr/>												
	North, bet. secs. 1 and 6.												
	Over rolling and broken land.												
8.88	High voltage transmission line, bears NE and SW.												
11.53	High voltage transmission line, bears NE and SW.												
23.70	Apache County Road C423, a graded road, 20 ft. wide, bears NE and SW.												
39.15	Trail road, bears ENE and WSW.												
40.00	Point for the 1/4 sec. cor. of secs. 1 and 6.  Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.												
	<table border="0"> <tr><td></td><td align="center">T 27 N</td><td></td></tr> <tr><td></td><td align="center">R 27 E   R 28 E</td><td></td></tr> <tr><td></td><td align="center">1/4</td><td></td></tr> <tr><td></td><td align="center">S 1   S 6</td><td></td></tr> </table>		T 27 N			R 27 E   R 28 E			1/4			S 1   S 6	
	T 27 N												
	R 27 E   R 28 E												
	1/4												
	S 1   S 6												
	2003												

**Survey of the East Boundary,  
T. 27 N., R. 27 E., Gila and Salt River Meridian, Arizona**

FEET	<p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p>										
80.00	<p>Point for the cor. of Tps. 27 and 28 N., Rs. 27 and 28 E.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center;"> <table style="border-collapse: collapse; margin: auto;"> <tr><td colspan="2">T 28 N</td></tr> <tr><td style="border-right: 1px solid black; padding: 0 5px;">R 27 E</td><td style="padding: 0 5px;">R 28 E</td></tr> <tr><td style="border-right: 1px solid black; padding: 0 5px;">S 36</td><td style="padding: 0 5px;">S 31</td></tr> <tr><td style="border-right: 1px solid black; padding: 0 5px;">S 1</td><td style="padding: 0 5px;">S 6</td></tr> <tr><td colspan="2">T 27 N</td></tr> </table> <p>2003</p> </div> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p> <p>Cor. is located 24 lks. S. and 86 lks. E. of a trail road, bears ENE and WSW.</p> <p>Land, rolling. Soil, sandy and rocky clay with sandstone outcrops. Timber, ponderosa pine, piñon, juniper, and Gambel oak; undergrowth, brush and native grasses.</p> <hr/> <p style="text-align: center;"><b>Survey of the North Boundary, T. 27 N., R. 27 E., Gila and Salt River Meridian, Arizona</b></p> <hr/> <p>From the cor. of Tps. 27 and 28 N., Rs. 27 and 28 E., hereinbefore described.</p> <p>West, bet. secs. 1 and 36.</p> <p>Over rolling and broken land.</p>	T 28 N		R 27 E	R 28 E	S 36	S 31	S 1	S 6	T 27 N	
T 28 N											
R 27 E	R 28 E										
S 36	S 31										
S 1	S 6										
T 27 N											
11.30	Sage House Wash, 50 ft. wide, 15 ft. deep, drains SSW.										
35.80	E. rim of a narrow mesa, top of sandstone ledge, bears NE and SW.										
40.00	<p>Point for the 1/4 sec. cor. of secs. 1 and 36.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 22 ins. in the ground to sandstone bedrock, with brass cap mkd.</p>										

**Survey of the North Boundary,  
T. 27 N., R. 27 E., Gila and Salt River Meridian, Arizona**

FEET	
	T 28 N R 27 E S 36 1/4 ——— S 1 T 27 N  2003
	Deposit a magnet, in a white plastic case, at the base of the stainless steel post.
41.30	W. rim of narrow mesa, top of sandstone ledge, bears NNE and SSW.
52.70	Left bank of Red Clay Wash, 4 ft. high, bears NE and SW.
53.40	Red Clay Wash, 26 ft. wide, 4 ft. deep, drains SW.
53.70	Right bank of Red Clay Wash, 4 ft. high, bears NE and SW.
76.30	Trail road, bears ENE and WSW.
80.00	Point for the cor. of secs. 1, 2, 35, and 36.  Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.
	T 28 N R 27 E S 35   S 36 S 2    S 1 T 27 N  2003
	Deposit a magnet, in a white plastic case, at the base of the stainless steel post.
	Land, rolling and broken. Soil, sandy and rocky clay with sandstone outcrops. Timber, scattered ponderosa pine, piñon, juniper, and Gambel oak; undergrowth, brush and native grasses.
	West, bet. secs. 2 and 35.
	Over rolling land.
40.00	Point for the 1/4 sec. cor. of secs. 2 and 35.  Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.

**Survey of the North Boundary,  
T. 27 N., R. 27 E., Gila and Salt River Meridian, Arizona**

FEET	
	T 28 N R 27 E S 35 1/4 ——— S 2 T 27 N  2003
	Deposit a magnet, in a white plastic case, at the base of the stainless steel post.
57.45	Apache County Road C305, a graded road, 20 ft. wide, bears SE and NW.
80.00	Point for the cor. of secs. 2, 3, 34, and 35.  Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.
	T 28 N R 27 E S 34   S 35 S 3    S 2 T 27 N  2003
	Deposit a magnet, in a white plastic case, at the base of the stainless steel post.
	Land, rolling. Soil, sandy and rocky clay. Timber, piñon and juniper; undergrowth, brush and native grasses.
	West, bet. secs. 3 and 34.  Over rolling land.
40.00	Point for the 1/4 sec. cor. of secs. 3 and 34.  Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.
	T 28 N R 27 E S 34 1/4 ——— S 3 T 27 N  2003

**Survey of the North Boundary,  
T. 27 N., R. 27 E., Gila and Salt River Meridian, Arizona**

FEET											
	Deposit a magnet, in a white plastic case, at the base of the stainless steel post.										
79.34	Barbed wire fence, 4 strand, bears NNE and SSW.										
80.00	Point for the cor. of secs. 3, 4, 33, and 34.  Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.										
	<table style="margin: auto;"> <tr><td>T 28 N</td><td>R 27 E</td></tr> <tr><td>S 33</td><td>S 34</td></tr> <tr><td>S 4</td><td>S 3</td></tr> <tr><td colspan="2">T 27 N</td></tr> </table>	T 28 N	R 27 E	S 33	S 34	S 4	S 3	T 27 N			
T 28 N	R 27 E										
S 33	S 34										
S 4	S 3										
T 27 N											
	2003										
	Deposit a magnet, in a white plastic case, at the base of the stainless steel post.										
	Land, rolling. Soil, sandy and rocky clay. Timber, piñon and juniper; undergrowth, brush and native grasses.										
	West, bet. secs. 4 and 33.										
	Over rolling land.										
34.07	Barbed wire fence, 3 strand, bears SE and NW.										
40.00	Point for the 1/4 sec. cor. of secs. 4 and 33.  Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.										
	<table style="margin: auto;"> <tr><td>T 28 N</td><td>R 27 E</td></tr> <tr><td colspan="2">S 33</td></tr> <tr><td colspan="2">1/4 ———</td></tr> <tr><td colspan="2">S 4</td></tr> <tr><td colspan="2">T 27 N</td></tr> </table>	T 28 N	R 27 E	S 33		1/4 ———		S 4		T 27 N	
T 28 N	R 27 E										
S 33											
1/4 ———											
S 4											
T 27 N											
	2003										
	Deposit a magnet, in a white plastic case, at the base of the stainless steel post.										
41.15	Apache County Route C423, a graded road, 22 ft. wide, bears SE and NW.										
43.06	Barbed wire fence, 5 strand, bears SE and NW.										

**Survey of the North Boundary,  
T. 27 N., R. 27 E., Gila and Salt River Meridian, Arizona**

FEET											
80.00	<p>Point for the cor. of secs. 4, 5, 32, and 33.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center;"> <table style="border-collapse: collapse; margin: auto;"> <tr> <td style="padding: 0 5px;">T 28 N</td> <td style="padding: 0 5px;">R 27 E</td> </tr> <tr> <td style="padding: 0 5px; border-right: 1px solid black;">S 32</td> <td style="padding: 0 5px;">S 33</td> </tr> <tr> <td style="padding: 0 5px; border-right: 1px solid black;">S 5</td> <td style="padding: 0 5px;">S 4</td> </tr> <tr> <td colspan="2" style="padding: 0 5px;">T 27 N</td> </tr> </table> <p>2003</p> </div> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p> <p>Land, rolling. Soil, sandy and rocky clay. Timber, piñon and juniper; undergrowth, brush and native grasses.</p> <hr style="width: 60%; margin: 10px auto;"/> <p>West, bet. secs. 5 and 32.</p> <p>Over rolling land.</p>	T 28 N	R 27 E	S 32	S 33	S 5	S 4	T 27 N			
T 28 N	R 27 E										
S 32	S 33										
S 5	S 4										
T 27 N											
40.00	<p>Point for the 1/4 sec. cor. of secs. 5 and 32.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center;"> <table style="border-collapse: collapse; margin: auto;"> <tr> <td style="padding: 0 5px;">T 28 N</td> <td style="padding: 0 5px;">R 27 E</td> </tr> <tr> <td style="padding: 0 5px;"></td> <td style="padding: 0 5px;">S 32</td> </tr> <tr> <td style="padding: 0 5px;">1/4</td> <td style="padding: 0 5px;">—</td> </tr> <tr> <td style="padding: 0 5px;"></td> <td style="padding: 0 5px;">S 5</td> </tr> <tr> <td colspan="2" style="padding: 0 5px;">T 27 N</td> </tr> </table> <p>2003</p> </div> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p>	T 28 N	R 27 E		S 32	1/4	—		S 5	T 27 N	
T 28 N	R 27 E										
	S 32										
1/4	—										
	S 5										
T 27 N											
70.20	Lone Tule Wash, 30 ft. wide, 3 ft. deep, drains W.										
73.72	Barbed wire fence, 8 strand, bears NE and SW.										
80.00	<p>Point for the cor. of secs. 5, 6, 31, and 32.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p>										

**Survey of the North Boundary,  
T. 27 N., R. 27 E., Gila and Salt River Meridian, Arizona**

FEET									
	<table style="margin: auto;"> <tr> <td>T 28 N</td> <td>R 27 E</td> </tr> <tr> <td>S 31</td> <td>S 32</td> </tr> <tr> <td>S 6</td> <td>S 5</td> </tr> <tr> <td colspan="2" style="text-align: center;">T 27 N</td> </tr> </table>	T 28 N	R 27 E	S 31	S 32	S 6	S 5	T 27 N	
T 28 N	R 27 E								
S 31	S 32								
S 6	S 5								
T 27 N									
	2003								
	Deposit a magnet, in a white plastic case, at the base of the stainless steel post.								
	Land, rolling. Soil, sandy and rocky clay. Timber, piñon and juniper; undergrowth, brush and native grasses.								
	West, bet. secs. 6 and 31.								
	Over rolling land.								
5.52	Power line, bears NE and SW.								
9.69	Barbed wire fence, 8 strand, bears ESE and WNW.								
25.98	A brass tablet, 3 ins. diam., firmly set flush in concrete collar, 8 ins. diam., projecting 6 ins. above ground, bears North, 91 lks. dist., with top mkd. B.I.A. ROADS 19, witnessed by an angle iron, firmly set, projecting 31 ins. above ground, with side mkd. P.O.T. 299+36.30.								
26.31	E. right-of-way fence of Navajo Route 27, barbed wire, 4 strand, parallels the highway.								
27.92	Navajo Route 27, asphalt pavement, 34 ft. wide, bears NNE and SSW.								
28.84	A brass tablet, 3 ins. diam., firmly set flush in concrete collar, 8 ins. diam., projecting 3 ins. above ground, bears North, 1.935 chs. dist., with top mkd. B.I.A. ROADS 19.								
29.53	W. right-of-way fence of Navajo Route 27, barbed wire, 4 strand, parallels the highway.								
29.92	Underground gas pipeline, bears NNE and SSW.								
40.00	Point for the 1/4 sec. cor. of secs. 6 and 31.  Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.								

**Survey of the North Boundary,  
T. 27 N., R. 27 E., Gila and Salt River Meridian, Arizona**

FEET																
	T 28 N R 27 E S 31 1/4 ——— S 6 T 27 N  2003															
	Deposit a magnet, in a white plastic case, at the base of the stainless steel post.															
69.94	Point for the closing cor. of Tps. 27 and 28 N., R. 27 E., only, at intersection of the E. bdy. of T. 28 N., R. 26 E.  Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.															
	<table style="border-collapse: collapse; margin: auto;"> <tr> <td style="padding-right: 10px;">T 28 N</td> <td style="border-left: 1px solid black; padding-left: 10px;">T 28 N</td> <td></td> </tr> <tr> <td style="padding-right: 10px;">R 26 E</td> <td style="border-left: 1px solid black; padding-left: 10px;">R 27 E</td> <td></td> </tr> <tr> <td></td> <td style="border-left: 1px solid black; padding-left: 10px;">S 31</td> <td></td> </tr> <tr> <td style="padding-right: 10px;">S 36</td> <td style="border-left: 1px solid black; padding-left: 10px;">S 6</td> <td style="padding-left: 10px;">CC</td> </tr> <tr> <td></td> <td style="border-left: 1px solid black; padding-left: 10px;">T 27 N</td> <td></td> </tr> </table>	T 28 N	T 28 N		R 26 E	R 27 E			S 31		S 36	S 6	CC		T 27 N	
T 28 N	T 28 N															
R 26 E	R 27 E															
	S 31															
S 36	S 6	CC														
	T 27 N															
	Deposit a magnet, in a white plastic case, at the base of the stainless steel post.															
	From this cor. point, the Tp. cor. of Tps. 27 and 28 N., Rs. 26 and 27 E., bears South, 6.545 chs. dist., monumented with a stainless steel post, 2 1/2 ins. diam., firmly set, projecting 4 ins. above ground with brass cap mkd. T28N R26E R27E S36 S31 S1 S6 T27N 1990. This Tp. cor. now becomes Tp. cor. of Tps. 27 and 28 N., R. 26 E., only. Remark the brass cap to read															
	<table style="border-collapse: collapse; margin: auto;"> <tr> <td style="padding-right: 10px;">T 28 N</td> <td></td> <td style="padding-right: 10px;">T 27 N</td> </tr> <tr> <td style="padding-right: 10px;">R 26 E</td> <td style="border-left: 1px solid black; padding-left: 10px;"></td> <td style="padding-right: 10px;">R 27 E</td> </tr> <tr> <td style="padding-right: 10px;">S 36</td> <td style="border-left: 1px solid black; padding-left: 10px;"></td> <td style="padding-right: 10px;">S 6</td> </tr> <tr> <td style="padding-right: 10px;">S 1</td> <td style="border-left: 1px solid black; padding-left: 10px;"></td> <td></td> </tr> <tr> <td style="padding-right: 10px;">T 27 N</td> <td style="border-left: 1px solid black; padding-left: 10px;"></td> <td></td> </tr> </table>	T 28 N		T 27 N	R 26 E		R 27 E	S 36		S 6	S 1			T 27 N		
T 28 N		T 27 N														
R 26 E		R 27 E														
S 36		S 6														
S 1																
T 27 N																
	2003 1990															
	From this same cor. point, the 1/4 sec. cor. of secs. 31 and 36, T. 28 N., Rs. 26 and 27 E., bears North, 33.455 chs. dist., monumented with a stainless steel post, loosely set, projecting 11 ins. above a scattered mound of stone, with brass cap mkd. T28N R26E R27E S36 S31 1990. This cor. now becomes the 1/4 sec. cor. of sec. 36 only, T. 28 N., R. 26 E.															



**Survey of the North Boundary,  
T. 27 N., R. 27 E., Gila and Salt River Meridian, Arizona**

FEET

from which the 1990 bearing trees

A juniper, 15 ins. diam., bears S. 34 1/4° E., 56 lks. dist., with scribe marks 1/4 S31 BT visible on open blaze. Defaced the scribe marks.

A piñon, 7 ins. diam., bears S. 65 3/4° W., 49 lks. dist., with scribe marks 1/4 S36 BT visible on open blaze.

Reset the stainless steel post, 28 ins. long, 24 ins. in the ground and sandstone bedrock. Remark the brass cap to read

T 28 N  
R 26 E    R 27 E  
1/4  
S 36 |  
2003  
1990

Deposit a magnet, in a white plastic case, at the base of the stainless steel post.

Land, rolling.

Soil, sandy and rocky clay.

Timber, scattered piñon and juniper; undergrowth, brush and native grasses.

---

**Survey of the Subdivisional Lines,  
T. 27 N., R. 27 E., Gila and Salt River Meridian, Arizona**

---

From the cor. of secs. 1, 2, 35, and 36, on the S. bdy. of the Tp., hereinbefore described.

N. 0°01' W., bet. secs. 35 and 36.

Over rolling land.

40.00

Point for the 1/4 sec. cor. of secs. 35 and 36.

Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.

T 27 N    R 27 E  
1/4  
S 35 | S 36  
2003

Deposit a magnet, in a white plastic case, at the base of the stainless steel post.

**Survey of the Subdivisional Lines,  
T. 27 N., R. 27 E., Gila and Salt River Meridian, Arizona**

FEET									
80.00	<p>Point for the cor. of secs. 25, 26, 35, and 36.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center;"> <table border="1"> <tr> <td>T 27 N</td> <td>R 27 E</td> </tr> <tr> <td>S 26</td> <td>S 25</td> </tr> <tr> <td>S 35</td> <td>S 36</td> </tr> </table> <p>2003</p> </div> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p> <p>Land, rolling. Soil, sandy and rocky clay. Timber, scattered ponderosa pine, piñon, juniper, and Gambel oak; undergrowth, brush and native grasses.</p> <hr/> <p>From the cor. of secs. 25, 30, 31, and 36, on the E. bdy. of the Tp., hereinbefore described.</p> <p>West, bet. secs. 25 and 36.</p> <p>Over rolling land.</p>	T 27 N	R 27 E	S 26	S 25	S 35	S 36		
T 27 N	R 27 E								
S 26	S 25								
S 35	S 36								
40.00	<p>Point for the 1/4 sec. cor. of secs. 25 and 36.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center;"> <table border="1"> <tr> <td>T 27 N</td> <td>R 27 E</td> </tr> <tr> <td></td> <td>S 25</td> </tr> <tr> <td>1/4</td> <td>—</td> </tr> <tr> <td></td> <td>S 36</td> </tr> </table> <p>2003</p> </div> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p>	T 27 N	R 27 E		S 25	1/4	—		S 36
T 27 N	R 27 E								
	S 25								
1/4	—								
	S 36								
80.00	<p>The cor. of secs. 25, 26, 35, and 36.</p> <p>Land, rolling. Soil, sandy and rocky clay. Timber, scattered ponderosa pine, piñon, juniper, and Gambel oak; undergrowth, brush and native grasses.</p> <hr/> <p>N. 0°01' W., bet. secs. 25 and 26.</p>								

**Survey of the Subdivisional Lines,  
T. 27 N., R. 27 E., Gila and Salt River Meridian, Arizona**

FEET	
	Over rolling land.
40.00	Point for the 1/4 sec. cor. of secs. 25 and 26.  Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.  <div style="text-align: center;">           T 27 N R 27 E                1/4            S 26   S 25             2003         </div>
	Deposit a magnet, in a white plastic case, at the base of the stainless steel post.
49.99	S. right-of-way fence of Arizona State Highway 264, barbed wire, 5 strand, parallels the highway.
51.53	Arizona State Highway 264, asphalt pavement, 25 ft. wide, bears E. and W.
53.03	N. right-of-way fence of Arizona State Highway 264, barbed wire, 5 strand, parallels the highway.
80.00	Point for the cor. of secs. 23, 24, 25, and 26.  Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.  <div style="text-align: center;">           T 27 N R 27 E            S 23   S 24            S 26   S 25             2003         </div>
	Deposit a magnet, in a white plastic case, at the base of the stainless steel post.
	Land, rolling. Soil, sandy and rocky clay. Timber, scattered piñon and juniper; undergrowth, brush and native grasses.
	From the cor. of secs. 19, 24, 25, and 30, on the E. bdy. of the Tp., hereinbefore described.
	West, bet. secs. 24 and 25.
	Over rolling land.

**Survey of the Subdivisional Lines,  
T. 27 N., R. 27 E., Gila and Salt River Meridian, Arizona**

FEET	
7.47	Navajo Route 203, a graded road, 26 ft. wide, bears SE and NW.
40.00	Point for the 1/4 sec. cor. of secs. 24 and 25.  Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.  <div style="text-align: center;">           T 27 N    R 27 E                      S 24                  1/4 ———                      S 25             2003         </div>
80.00	Deposit a magnet, in a white plastic case, at the base of the stainless steel post.  The cor. of secs. 23, 24, 25, and 26.  Land, rolling. Soil, sandy and rocky clay. Timber, scattered piñon and juniper; undergrowth, brush and native grasses.
	N. 0°01' W., bet. secs. 23 and 24.  Over rolling land.
40.00	Point for the 1/4 sec. cor. of secs. 23 and 24.  Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.  <div style="text-align: center;">           T 27 N    R 27 E                      1/4                  S 23   S 24             2003         </div>
	Deposit a magnet, in a white plastic case, at the base of the stainless steel post.
61.25	Navajo Route 39, a graded road, 25 ft. wide, bears ESE and WNW.
62.62	Barbed wire fence, 4 strand, bears ESE and WNW.
68.46	Chainlink fence, 8 ft. high, bears ESE and WNW, entering sewage lagoon.
72.66	Chainlink fence, 8 ft. high, bears ESE and WNW, leaving the sewage lagoon.

**Survey of the Subdivisional Lines,  
T. 27 N., R. 27 E., Gila and Salt River Meridian, Arizona**

FEET									
75.21	Barbed wire fence, 4 strand, bears ESE and WNW.								
80.00	Point for the cor. of secs. 13, 14, 23, and 24.  Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.  <div style="text-align: center;"> <table style="margin: auto;"> <tr><td>T 27 N</td><td>R 27 E</td></tr> <tr><td>S 14</td><td>S 13</td></tr> <tr><td>S 23</td><td>S 24</td></tr> </table> <p>2003</p> </div>	T 27 N	R 27 E	S 14	S 13	S 23	S 24		
T 27 N	R 27 E								
S 14	S 13								
S 23	S 24								
	Deposit a magnet, in a white plastic case, at the base of the stainless steel post.  Land, rolling. Soil, sandy and rocky clay. Timber, scattered piñon and juniper; undergrowth, brush and native grasses.								
	From the cor. of secs. 13, 18, 19, and 24, on the E. bdy. of the Tp., hereinbefore described.  West, bet. secs. 13 and 24.  Over rolling land.								
40.00	Point for the 1/4 sec. cor. of secs. 13 and 24.  Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.  <div style="text-align: center;"> <table style="margin: auto;"> <tr><td>T 27 N</td><td>R 27 E</td></tr> <tr><td></td><td>S 13</td></tr> <tr><td>1/4</td><td>—</td></tr> <tr><td></td><td>S 24</td></tr> </table> <p>2003</p> </div>	T 27 N	R 27 E		S 13	1/4	—		S 24
T 27 N	R 27 E								
	S 13								
1/4	—								
	S 24								
	Deposit a magnet, in a white plastic case, at the base of the stainless steel post.								
62.65	Navajo Route 203, a graded road, 23 ft. wide, bears SSE and NNW.								
80.00	The cor. of secs. 13, 14, 23, and 24.  Land, rolling. Soil, sandy and rocky clay. Timber, scattered piñon and juniper; undergrowth, brush and native grasses.								

**Survey of the Subdivisional Lines,  
T. 27 N., R. 27 E., Gila and Salt River Meridian, Arizona**

FEET	
	N. 0°01' W., bet. secs. 13 and 14.
	Over rolling land.
38.75	Power line, bears NE and SW.
40.00	Point for the 1/4 sec. cor. of secs. 13 and 14.
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in sandstone bedrock, with brass cap mkd.
	T 27 N R 27 E 1/4 S 14   S 13  2003
	Deposit a magnet, in a white plastic case, at the base of the stainless steel post.
47.90	Navajo Route 203, a graded road, 25 ft. wide, bears SE and NW.
70.69	Barbed wire fence, 4 strand, bears E. and W.; south fence of enclosed area of ruins.
78.91	Barbed wire fence, 3 strand, bears ENE and WSW.
80.00	Point for the cor. of secs. 11, 12, 13, and 14.
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.
	T 27 N R 27 E S 11   S 12 S 14   S 13  2003
	Deposit a magnet, in a white plastic case, at the base of the stainless steel post.
	Cor. is located 93 lks. E. of a barbed wire fence, 4 strand, bears SE and NW.
	Land, rolling. Soil, sandy and rocky clay. Timber, scattered piñon and juniper; undergrowth, brush and native grasses.

**Survey of the Subdivisional Lines,  
T. 27 N., R. 27 E., Gila and Salt River Meridian, Arizona**

FEET	
	From the cor. of secs. 7, 12, 13, and 18, on the E. bdy. of the Tp., hereinbefore described.
	West, bet. secs. 12 and 13.
	Over rolling and broken land; descend into Kinlichee Creek Canyon.
40.00	Point for the 1/4 sec. cor. of secs. 12 and 13.
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.
	T 27 N R 27 E S 12 1/4 ——— S 13  2003
	Deposit a magnet, in a white plastic case, at the base of the stainless steel post.
	Cor. is located 55 lks. S. and 91 lks. E. of a wash, 10 ft. wide, with undefined banks against sandstone cliffs.
56.96	Kinlichee Creek, a wash, 20 ft. wide, 5 ft. deep, drains NW.
72.45	Kinlichee Creek, a wash, 10 ft. wide, 6 ft. deep, drains SW.
76.60	W. rim of Kinlichee Creek Canyon, top of sandstone ledge, the W. bank of Kinlichee Creek, a wash, 20 ft. wide, 10 ft. deep, drains N.
77.85	Barbed wire fence, 2 strand, bears ENE and WSW; east fence of a ruins.
80.00	The cor. of secs. 11, 12, 13, and 14.
	Land, rolling and broken. Soil, sandy and rocky clay with sandstone outcrops. Timber, scattered piñon and juniper; undergrowth, brush and native grasses.
	_____
	N. 0°01' W., bet. secs. 11 and 12.
	Over broken land, across the Kinlichee Creek Canyon.
2.16	High voltage transmission line, bears NE and SW.
4.65	Kinlichee Creek, a wash, 60 ft. wide, 12 ft. deep, drains NW.

**Survey of the Subdivisional Lines,  
T. 27 N., R. 27 E., Gila and Salt River Meridian, Arizona**

FEET	
4.86	High voltage transmission line, bears NE and SW.
38.70	Power line, bears ENE and WSW.
40.00	Point for the 1/4 sec. cor. of secs. 11 and 12.  Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in sandstone bedrock, with brass cap mkd.  <div style="text-align: center;">           T 27 N R 27 E                  1/4            S 11   S 12             2003         </div>
	Deposit a magnet, in a white plastic case, at the base of the stainless steel post.
49.75	Navajo Route 203, a graded road, 26 ft. wide, bears ENE and WSW.
51.70	Apache County Road C305, a graded road, 22 ft. wide, bears NNE and SSW.
80.00	Point for the cor. of secs. 1, 2, 11, and 12.  Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.  <div style="text-align: center;">           T 27 N R 27 E            S 2   S 1            S 11   S 12             2003         </div>
	Deposit a magnet, in a white plastic case, at the base of the stainless steel post.
	Land, rolling and broken. Soil, sandy and rocky clay with sandstone outcrops. Timber, piñon, juniper, and Gambel oak; undergrowth, brush and native grasses.
	From the cor. of secs. 1, 6, 7, and 12.
	West, bet. secs. 1 and 12.
	Over rolling land.
2.22	Navajo Route 203, a graded road, 23 ft. wide, bears ENE and WSW.
8.14	High voltage transmission line, bears NE and SW.



**Survey of the Subdivisional Lines,  
T. 27 N., R. 27 E., Gila and Salt River Meridian, Arizona**

FEET	
10.62	High voltage transmission line, bears NE and SW.
19.60	Apache County Road C423, a graded road, 22 ft. wide, bears NE and SW.
40.00	Point for the 1/4 sec. cor. of secs. 1 and 12.  Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.  <div style="text-align: center;">           T 27 N R 27 E                      S 1                  1/4 ———                      S 12             2003         </div>
	Deposit a magnet, in a white plastic case, at the base of the stainless steel post.
74.95	Apache County Road C305, a graded road, 22 ft. wide, bears N. and S.
80.00	The cor. of secs. 1, 2, 11, and 12.  Land, rolling. Soil, sandy and rocky clay with sandstone outcrops. Timber, piñon, juniper, and Gambel oak; undergrowth, brush and native grasses.
	————— N. 0°01' W., bet. secs. 1 and 2.  Over rolling land.
21.65	Apache County Road C305, a graded road, 22 ft. wide, bears ESE and WNW.
35.35	Sage House Wash, 60 ft. wide, 12 ft. deep, drains SW.
38.95	Red Clay Wash, 30 ft. wide, 10 ft. deep, drains SW.
40.00	Point for the 1/4 sec. cor. of secs. 1 and 2.  Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.  <div style="text-align: center;">           T 27 N R 27 E                      1/4                  S 2   S 1             2003         </div>

**Survey of the Subdivisional Lines,  
T. 27 N., R. 27 E., Gila and Salt River Meridian, Arizona**

FEET	
	Deposit a magnet, in a white plastic case, at the base of the stainless steel post.
78.20	Trail road, bears ENE and WSW.
80.00	The cor. of secs. 1, 2, 35, and 36, on the N. bdy. of the Tp., hereinbefore described.  Land, rolling and broken. Soil, sandy and rocky clay. Timber, scattered piñon and juniper; undergrowth, brush and native grasses.
	----- From the cor. of secs. 2, 3, 34, and 35, on the S. bdy. of the Tp., hereinbefore described.  N. 0°01' W., bet. secs. 34 and 35.  Over gently rolling land.
38.20	Underground waterline, bears ESE and WNW.
39.00	Trail road, bears SE and NW.
40.00	Point for the 1/4 sec. cor. of secs. 34 and 35.  Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.  <div style="text-align: center;">                     T 27 N R 27 E                            1/4                      S 34   S 35                        2003                 </div>
80.00	Deposit a magnet, in a white plastic case, at the base of the stainless steel post.  Point for the cor. of secs. 26, 27, 34, and 35.  Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.  <div style="text-align: center;">                     T 27 N R 27 E                      S 27   S 26                      S 34   S 35                        2003                 </div>
	Deposit a magnet, in a white plastic case, at the base of the stainless steel post.

**Survey of the Subdivisional Lines,  
T. 27 N., R. 27 E., Gila and Salt River Meridian, Arizona**

FEET	
	<p>Land, gently rolling. Soil, sandy and rocky clay. Timber, scattered piñon and juniper; undergrowth, brush and native grasses.</p> <hr/> <p>From the cor. of secs. 25, 26, 35, and 36.</p> <p>West, bet. secs. 26 and 35.</p> <p>Over gently rolling land.</p>
40.00	<p>Point for the 1/4 sec. cor. of secs. 26 and 35.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p align="center">                     T 27 N R 27 E                                S 26                      1/4 ———                                S 35                        2003                 </p> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p>
80.00	<p>The cor. of secs. 26, 27, 34, and 35.</p> <p>Land, gently rolling. Soil, sandy clay. Timber, scattered piñon and juniper; undergrowth, brush and native grasses.</p> <hr/> <p>N. 0°01' W., bet. secs. 26 and 27.</p> <p>Over gently rolling land.</p>
40.00	<p>Point for the 1/4 sec. cor. of secs. 26 and 27.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p align="center">                     T 27 N R 27 E                                1/4                      S 27   S 26                        2003                 </p> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p>

**Survey of the Subdivisional Lines,  
T. 27 N., R. 27 E., Gila and Salt River Meridian, Arizona**

FEET							
43.92	S. right-of-way fence of Arizona State Highway 264, barbed wire, 5 strand, parallels the highway.						
43.97	A brass tablet, 3 ins. diam., firmly set flush in concrete collar, 6 ins. diam., projecting 4 ins. above ground, bears East, 64 lks. dist., with top unmarked, witnessed by an angle iron to the west, with side mkd. P.O.T. 1228.00.						
45.44	Arizona State Highway 264, asphalt pavement, 27 ft. wide, bears E. and W.						
46.96	N. right-of-way fence of Arizona State Highway 264, barbed wire, 5 strand, parallels the highway.						
46.99	A brass tablet, 3 ins. diam., firmly set flush in concrete collar, 6 ins. diam., projecting 4 ins. above ground, bears East, 41 lks. dist., with top unmarked, witnessed by an angle iron, firmly set, projecting 2 ft. above ground, to the west, with side mkd. P.O.T. 1228.00.						
80.00	Point for the cor. of secs. 22, 23, 26, and 27.  Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.						
	<table style="margin-left: auto; margin-right: auto;"> <tr> <td>T 27 N</td> <td>R 27 E</td> </tr> <tr> <td>S 22</td> <td>S 23</td> </tr> <tr> <td>S 27</td> <td>S 26</td> </tr> </table>	T 27 N	R 27 E	S 22	S 23	S 27	S 26
T 27 N	R 27 E						
S 22	S 23						
S 27	S 26						
	2003						
	Deposit a magnet, in a white plastic case, at the base of the stainless steel post.						
	Land, gently rolling. Soil, sandy clay. Timber, scattered piñon and juniper; undergrowth, brush and native grasses.						
	<hr/>						
	From the cor. of secs. 23, 24, 25, and 26.						
	West, bet. secs. 23 and 26.						
	Over gently rolling land.						
40.00	Point for the 1/4 sec. cor. of secs. 23 and 26.  Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.						

**Survey of the Subdivisional Lines,  
T. 27 N., R. 27 E., Gila and Salt River Meridian, Arizona**

FEET	
	T 27 N R 27 E S 23 1/4 ——— S 26  2003
	Deposit a magnet, in a white plastic case, at the base of the stainless steel post.
80.00	The cor. of secs. 22, 23, 26, and 27.  Land, gently rolling. Soil, sandy clay. Timber, scattered piñon and juniper; undergrowth, brush and native grasses.
	_____
	N. 0°01' W., bet. secs. 22 and 23.  Over gently rolling land.
40.00	Point for the 1/4 sec. cor. of secs. 22 and 23.  Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.
	T 27 N R 27 E 1/4 S 22   S 23  2003
	Deposit a magnet, in a white plastic case, at the base of the stainless steel post.
75.44	High voltage transmission line, bears NE and SW.
78.12	High voltage transmission line, bears NE and SW.
80.00	Point for the cor. of secs. 14, 15, 22, and 23.  Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.
	T 27 N R 27 E S 15   S 14 ——— S 22   S 23  2003

**Survey of the Subdivisional Lines,  
T. 27 N., R. 27 E., Gila and Salt River Meridian, Arizona**

FEET	
	<p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p> <p>Land, gently rolling. Soil, sandy clay. Timber, scattered piñon and juniper; undergrowth, brush and native grasses.</p> <hr/> <p>From the cor. of secs. 13, 14, 23, and 24.</p> <p>West, bet. secs. 14 and 23.</p> <p>Over rolling land.</p>
39.15	Navajo Route 39, a graded road, 28 ft. wide, bears ESE and WNW.
40.00	Point for the 1/4 sec. cor. of secs. 14 and 23.
	<p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T 27 N R 27 E S 14 1/4 ——— S 23</p> <p style="text-align: center;">2003</p>
	<p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p> <p>Set a steel fence post nearby.</p>
75.80	High voltage transmission line, bears NE and SW.
78.26	High voltage transmission line, bears NE and SW.
80.00	The cor. of secs. 14, 15, 22, and 23.
	<p>Land, rolling. Soil, sandy clay. Timber, scattered piñon and juniper; undergrowth, brush and native grasses.</p> <hr/> <p>N. 0°01' W., bet. secs. 14 and 15.</p> <p>Over rolling land.</p>
18.93	Navajo Route 39, asphalt pavement, 38 ft. wide, bears NE and SW.

**Survey of the Subdivisional Lines,  
T. 27 N., R. 27 E., Gila and Salt River Meridian, Arizona**

FEET	
21.40	A brass tablet, 3 ins. diam., set flush in concrete collar, 6 ins. diam., flush with the surface of the ground, bears East, 1.70 chs. dist., with top mkd. B.I.A. ROADS 19, witnessed by an angle iron, firmly set, projecting 2 ft. above ground to the south, with side mkd. 105+85.94.
29.29	A brass tablet, 3 ins. diam., set flush in concrete collar, 6 ins. diam., flush with the surface of the ground, bears East, 24.5 lks. dist., with top mkd. B.I.A. ROADS 19, witnessed by an angle iron, firmly set, projecting 2 ft. above ground, with side mkd. PC 113+21.13.
31.23	Navajo Route 39, asphalt pavement, 38 ft. wide, bears SE and NW.
34.12	Power line, bears ESE and WNW.
40.00	Point for the 1/4 sec. cor. of secs. 14 and 15.  Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in sandstone bedrock, with brass cap mkd.  <div style="text-align: center;">           T 27 N R 27 E                  1/4            S 15   S 14             2003         </div> Deposit a magnet, in a white plastic case, at the base of the stainless steel post.
58.70	Kinlichee Creek, a wash, 150 ft. wide, 22 ft. deep, drains SSW.
80.00	Point for the cor. of secs. 10, 11, 14, and 15.  Set a brass tablet, 3 1/4 ins. diam., 2 1/2 ins. stem, cemented in a drill hole, in sandstone boulder, 8 x 4 x 3 ft. high, with top mkd.  <div style="text-align: center;">           T 27 N R 27 E            S 10   S 11            S 15   S 14             2003         </div> Deposit a magnet, in a white plastic case, at the base of the brass tablet.  Land, rolling and broken. Soil, sandy and rocky clay with sandstone outcrops. Timber, scattered piñon and juniper; undergrowth, brush and native grasses.

**Survey of the Subdivisional Lines,  
T. 27 N., R. 27 E., Gila and Salt River Meridian, Arizona**

FEET	
	From the cor. of secs. 11, 12, 13, and 14. West, bet. secs. 11 and 14. Over rolling and broken land.
1.98	High voltage transmission line, bears NE and SW.
4.47	High voltage transmission line, bears NE and SW.
8.75	Navajo Route 203, a graded road, 20 ft. wide, bears N. and S.
40.00	Point for the 1/4 sec. cor. of secs. 11 and 14.  Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.  <div style="text-align: center;">           T 27 N   R 27 E                      S 11                  1/4 ———                      S 14             2003         </div>
	Deposit a magnet, in a white plastic case, at the base of the stainless steel post.
42.50	W. rim of mesa, bears ENE and WSW; thence descend into Kinlichee Creek valley.
53.66	Kinlichee Creek, a wash, 150 ft. wide, 20 ft. deep, drains SW.
80.00	The cor. of secs. 10, 11, 14, and 15.  Land, rolling and broken. Soil, sandy and rocky clay with sandstone outcrops. Timber, scattered piñon and juniper; undergrowth, brush and native grasses.
	----- N. 0°01' W., bet. secs. 10 and 11.  Over rolling land.
40.00	Point for the 1/4 sec. cor. of secs. 10 and 11.  Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.



**Survey of the Subdivisional Lines,  
T. 27 N., R. 27 E., Gila and Salt River Meridian, Arizona**

FEET	
	T 27 N R 27 E 1/4 S 10   S 11  2003  Deposit a magnet, in a white plastic case, at the base of the stainless steel post.
80.00	Point for the cor. of secs. 2, 3, 10, and 11.  Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.  <div style="text-align: center;">             T 27 N R 27 E              S 3   S 2              S 10   S 11               2003           </div> Deposit a magnet, in a white plastic case, at the base of the stainless steel post.  Land, rolling. Soil, sandy clay. Timber, scattered piñon and juniper; undergrowth, brush and native grasses.
	From the cor. of secs. 1, 2, 11, and 12.  West, bet. secs. 2 and 11.  Over rolling land.
16.80	Red Clay Wash, 30 ft. wide, 12 ft. deep, drains S.
40.00	Point for the 1/4 sec. cor. of secs. 2 and 11.  Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.  <div style="text-align: center;">             T 27 N R 27 E                    S 2              1/4 ———                    S 11               2003           </div> Deposit a magnet, in a white plastic case, at the base of the stainless steel post.

**Survey of the Subdivisional Lines,  
T. 27 N., R. 27 E., Gila and Salt River Meridian, Arizona**

FEET	
80.00	<p>The cor. of secs. 2, 3, 10, and 11.</p> <p>Land, rolling. Soil, sandy clay. Timber, scattered piñon and juniper; undergrowth, brush and native grasses.</p> <hr/> <p>N. 0°01' W., bet. secs. 2 and 3.</p> <p>Over rolling land.</p>
40.00	<p>Point for the 1/4 sec. cor. of secs. 2 and 3.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T 27 N R 27 E 1/4 S 3   S 2  2003</p> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p>
41.70	<p>Wash, 12 ft. wide, 13 ft. deep, drains SSW.</p>
80.00	<p>The cor. of secs. 2, 3, 34, and 35, on the N. bdy. of the Tp., hereinbefore described.</p> <p>Land, rolling. Soil, sandy clay. Timber, scattered piñon and juniper; undergrowth, brush and native grasses.</p> <hr/> <p>From the cor. of secs. 3, 4, 33, and 34, on the S. bdy. of the Tp., hereinbefore described.</p> <p>N. 0°02' W., bet. secs. 33 and 34.</p> <p>Over gently rolling land.</p>
40.00	<p>Point for the 1/4 sec. cor. of secs. 33 and 34.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p>

**Survey of the Subdivisional Lines,  
T. 27 N., R. 27 E., Gila and Salt River Meridian, Arizona**

FEET	
	T 27 N R 27 E 1/4 S 33   S 34  2003
	Deposit a magnet, in a white plastic case, at the base of the stainless steel post.
66.50	Fish Wash, 25 ft. wide, 12 ft. deep, drains NW.
80.00	Point for the cor. of secs. 27, 28, 33, and 34.
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.
	T 27 N R 27 E S 28   S 27 S 33   S 34  2003
	Deposit a magnet, in a white plastic case, at the base of the stainless steel post.
	Land, gently rolling. Soil, sandy clay. Timber, scattered piñon and juniper; undergrowth, brush and native grasses.
	From the cor. of secs. 26, 27, 34, and 35.
	West, bet. secs. 27 and 34.
	Over gently rolling land.
26.30	Apache County Road C450, a graded road, 20 ft. wide, bears N. and S.
40.00	Point for the 1/4 sec. cor. of secs. 27 and 34.
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.
	T 27 N R 27 E S 27 1/4 ——— S 34  2003

**Survey of the Subdivisional Lines,  
T. 27 N., R. 27 E., Gila and Salt River Meridian, Arizona**

FEET	
	Deposit a magnet, in a white plastic case, at the base of the stainless steel post.
78.35	Trail road, bears SSE and NNW.
80.00	The cor. of secs. 27, 28, 33, and 34.  Land, gently rolling. Soil, sandy clay. Timber, scattered piñon and juniper; undergrowth, brush and native grasses.
	N. 0°02' W., bet. secs. 27 and 28.  Over gently rolling land.
2.90	Trail road, bears SSE and NNW.
40.00	Point for the 1/4 sec. cor. of secs. 27 and 28.  Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.
	T 27 N R 27 E 1/4 S 28   S 27  2003
	Deposit a magnet, in a white plastic case, at the base of the stainless steel post.  Cor. is located 25 lks. S. of trail road, bears E. and W.
51.66	S. right-of-way fence of Arizona State Highway 264, barbed wire, 5 strand, parallels the highway.
53.20	Arizona State Highway 264, asphalt pavement, 26 ft. wide, bears E. and W.
54.73	N. right-of-way fence of Arizona State Highway 264, barbed wire, 5 strand, parallels the highway.
55.65	Underground gas pipeline, bears E. and W.
68.66	High voltage transmission line, bears NE and SW.
77.83	High voltage transmission line, bears NE and SW.
79.05	Trail road, bears ESE and WNW.
80.00	Point for the cor. of secs. 21, 22, 27, and 28.

**Survey of the Subdivisional Lines,  
T. 27 N., R. 27 E., Gila and Salt River Meridian, Arizona**

FEET									
	<p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p align="center"> <table border="1"> <tr> <td>T 27 N</td> <td>R 27 E</td> </tr> <tr> <td>S 21</td> <td>S 22</td> </tr> <tr> <td>S 28</td> <td>S 27</td> </tr> </table> </p> <p align="center">2003</p> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p> <p>Land, gently rolling. Soil, sandy clay. Timber, scattered piñon and juniper; undergrowth, brush and native grasses.</p> <hr/> <p>From the cor. of secs. 22, 23, 26, and 27.</p> <p>West, bet. secs. 22 and 27.</p> <p>Over gently rolling land.</p>	T 27 N	R 27 E	S 21	S 22	S 28	S 27		
T 27 N	R 27 E								
S 21	S 22								
S 28	S 27								
40.00	<p>Point for the 1/4 sec. cor. of secs. 22 and 27.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p align="center"> <table border="1"> <tr> <td>T 27 N</td> <td>R 27 E</td> </tr> <tr> <td></td> <td>S 22</td> </tr> <tr> <td>1/4</td> <td>_____</td> </tr> <tr> <td></td> <td>S 27</td> </tr> </table> </p> <p align="center">2003</p> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p> <p>Cor. is located 1.95 chs. S. of a graded road, 22 ft. wide, bears E. and W.</p>	T 27 N	R 27 E		S 22	1/4	_____		S 27
T 27 N	R 27 E								
	S 22								
1/4	_____								
	S 27								
53.75	<p>Graded road, 22 ft. wide, bears ENE and WSW.</p>								
60.07	<p>Navajo Route 39, asphalt pavement, 37 ft. wide, bears N. and S.</p>								
61.10	<p>Underground gas pipeline, bears N. and S.</p>								
69.58	<p>High voltage transmission line, bears NE and SW.</p>								
77.03	<p>High voltage transmission line, bears NE and SW.</p>								

**Survey of the Subdivisional Lines,  
T. 27 N., R. 27 E., Gila and Salt River Meridian, Arizona**

FEET	
80.00	<p>The cor. of secs. 21, 22, 27, and 28.</p> <p>Land, gently rolling. Soil, sandy clay. Timber, scattered piñon and juniper; undergrowth, brush and native grasses.</p> <hr/> <p>N. 0°02' W., bet. secs. 21 and 22.</p> <p>Over rolling land.</p>
40.00	<p>Point for the 1/4 sec. cor. of secs. 21 and 22.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T 27 N R 27 E 1/4 S 21   S 22</p> <p style="text-align: center;">2003</p> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p>
80.00	<p>Point for the cor. of secs. 15, 16, 21, and 22.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T 27 N R 27 E S 16   S 15 S 21   S 22</p> <p style="text-align: center;">2003</p> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p> <p>Land, rolling. Soil, sandy clay. Timber, scattered piñon and juniper; undergrowth, brush and native grasses.</p> <hr/> <p>From the cor. of secs. 14, 15, 22, and 23.</p> <p>West, bet. secs. 15 and 22.</p> <p>Over gently rolling land.</p>

**Survey of the Subdivisional Lines,  
T. 27 N., R. 27 E., Gila and Salt River Meridian, Arizona**

FEET	
28.95	Navajo Route 39, asphalt pavement, 37 ft. wide, bears NE and SW.
30.44	Underground gas pipeline, bears NE and SW.
36.76	Asphalt pavement road to Kinlichee Chapter House, 32 ft. wide, bears SSE and NNW.
37.50	Underground gas pipeline, bears SSE and NNW.
40.00	Point for the 1/4 sec. cor. of secs. 15 and 22.  Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.  <div style="text-align: center;">           T 27 N R 27 E                      S 15                  1/4 ———                      S 22             2003         </div>
	Deposit a magnet, in a white plastic case, at the base of the stainless steel post.
41.22	Power line, bears SSE and NNW.
80.00	The cor. of secs. 15, 16, 21, and 22.  Land, rolling. Soil, sandy clay. Timber, scattered piñon and juniper; undergrowth, brush and native grasses.
	————— N. 0°02' W., bet. secs. 15 and 16.  Over rolling and broken land.
40.00	Point for the 1/4 sec. cor. of secs. 15 and 16.  Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.  <div style="text-align: center;">           T 27 N R 27 E                      1/4                  S 16   S 15             2003         </div>
	Deposit a magnet, in a white plastic case, at the base of the stainless steel post.

**Survey of the Subdivisional Lines,  
T. 27 N., R. 27 E., Gila and Salt River Meridian, Arizona**

FEET									
48.80	S. rim of Kinlichee Creek Canyon, bears NE and SW; thence descend into the canyon.								
50.45	Kinlichee Creek, a wash, 60 ft. wide, 4 ft. deep, drains WSW; thence ascend out of the canyon.								
80.00	Point for the cor. of secs. 9, 10, 15, and 16.  Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.  <div style="text-align: center;"> <table style="margin: auto;"> <tr><td>T 27 N</td><td>R 27 E</td></tr> <tr><td>S 9</td><td>S 10</td></tr> <tr><td>S 16</td><td>S 15</td></tr> </table> <p>2003</p> </div> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p> <p>Land, rolling and broken. Soil, sandy and rocky clay with sandstone outcrops. Timber, scattered piñon and juniper; undergrowth, brush and native grasses.</p> <hr/> <p>From the cor. of secs. 10, 11, 14, and 15.  West, bet. secs. 10 and 15.  Over rolling and broken land.</p>	T 27 N	R 27 E	S 9	S 10	S 16	S 15		
T 27 N	R 27 E								
S 9	S 10								
S 16	S 15								
38.58	Apache County Road C423, a graded road, 22 ft. wide, bears ESE and WNW.								
40.00	Point for the 1/4 sec. cor. of secs. 10 and 15.  Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 12 ins. below the surface of graded road, with brass cap mkd.  <div style="text-align: center;"> <table style="margin: auto;"> <tr><td>T 27 N</td><td>R 27 E</td></tr> <tr><td>S 10</td><td></td></tr> <tr><td>1/4</td><td>—</td></tr> <tr><td>S 15</td><td></td></tr> </table> <p>2003</p> </div>	T 27 N	R 27 E	S 10		1/4	—	S 15	
T 27 N	R 27 E								
S 10									
1/4	—								
S 15									



**Survey of the Subdivisional Lines,  
T. 27 N., R. 27 E., Gila and Salt River Meridian, Arizona**

FEET	
	<p>from which</p> <p>A stainless steel post, 28 ins. long, 2 1/2 ins. diam., set 24 ins. in ground for a reference monument, bears N. 45°00' E., 150.0 ft. dist., with brass cap mkd. RM T27N R27E 1/4 S10 150.0 FT TO COR 2003, and an arrow pointing to the cor. Deposit a magnet, in a white plastic case, at the base of the stainless steel post. Set a steel fence post nearby.</p> <p>A stainless steel post, 28 ins. long, 2 1/2 ins. diam., set 24 ins. in ground for a reference monument, bears S. 45°00' E., 50.0 ft. dist., with brass cap mkd. RM T27N R27E 1/4 S15 50.0 FT TO COR 2003, and an arrow pointing to the cor. Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post at the 1/4 sec. cor.</p> <p>Cor. is located 12 lks., S. of Apache County Road C423, a graded road, 22 ft. wide, bears E. and W.</p>
80.00	<p>The cor. of secs. 9, 10, 15, and 16.</p> <p>Land, rolling. Soil, sandy and rocky clay. Timber, scattered piñon and juniper; undergrowth, brush and native grasses.</p> <hr/> <p>N. 0°02' W., bet. secs. 9 and 10.</p> <p>Over rolling land.</p>
40.00	<p>Point for the 1/4 sec. cor. of secs. 9 and 10.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p align="center">T 27 N R 27 E 1/4 S 9   S 10  2003</p> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p>
80.00	<p>Point for the cor. of secs. 3, 4, 9, and 10.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p>

**Survey of the Subdivisional Lines,  
T. 27 N., R. 27 E., Gila and Salt River Meridian, Arizona**

FEET									
	<table style="margin-left: auto; margin-right: auto;"> <tr> <td>T 27 N</td> <td>R 27 E</td> </tr> <tr> <td style="border-right: 1px solid black;">S 4</td> <td>S 3</td> </tr> <tr> <td style="border-right: 1px solid black;">S 9</td> <td>S 10</td> </tr> </table>	T 27 N	R 27 E	S 4	S 3	S 9	S 10		
T 27 N	R 27 E								
S 4	S 3								
S 9	S 10								
	2003								
	Deposit a magnet, in a white plastic case, at the base of the stainless steel post.								
	Land, rolling. Soil, sandy clay. Timber, scattered piñon and juniper; undergrowth, brush and native grasses.								
	From the cor. of secs. 2, 3, 10, and 11. West, bet. secs. 3 and 10. Over rolling land.								
40.00	Point for the 1/4 sec. cor. of secs. 3 and 10. Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.								
	<table style="margin-left: auto; margin-right: auto;"> <tr> <td>T 27 N</td> <td>R 27 E</td> </tr> <tr> <td></td> <td>S 3</td> </tr> <tr> <td>1/4</td> <td style="border-top: 1px solid black;">_____</td> </tr> <tr> <td></td> <td>S 10</td> </tr> </table>	T 27 N	R 27 E		S 3	1/4	_____		S 10
T 27 N	R 27 E								
	S 3								
1/4	_____								
	S 10								
	2003								
	Deposit a magnet, in a white plastic case, at the base of the stainless steel post.								
77.05	Apache County Road C423, a graded road, 22 ft. wide, bears SSE and NNW.								
80.00	The cor. of secs. 3, 4, 9, and 10. Land, rolling. Soil, sandy clay. Timber, piñon and juniper; undergrowth, brush and native grasses.								
	N. 0°02' W., bet. secs. 3 and 4. Over rolling land.								

**Survey of the Subdivisional Lines,  
T. 27 N., R. 27 E., Gila and Salt River Meridian, Arizona**

FEET	
13.25	Apache County Road C423, a graded road, 22 ft. wide, bears SSE and NNW.
40.00	Point for the 1/4 sec. cor. of secs. 3 and 4.  Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.  <div style="text-align: center;">           T 27 N R 27 E                  1/4            S 4   S 3             2003         </div>
	Deposit a magnet, in a white plastic case, at the base of the stainless steel post.
78.80	Barbed wire fence, 4 strand, bears NE and SW.
80.00	The cor. of secs. 3, 4, 33, and 34, on the N. bdy. of the Tp., hereinbefore described.  Land, rolling. Soil, sandy clay. Timber, piñon and juniper; undergrowth, brush and native grasses.
	<hr/> From the cor. of secs. 4, 5, 32, and 33, on the S. bdy. of the Tp., hereinbefore described.  N. 0°03' W., bet. secs. 32 and 33.  Over rolling land.
27.40	Haakai Daachaahi Wash, 30 ft. wide, 10 ft. deep, drains NW.
40.00	Point for the 1/4 sec. cor. of secs. 32 and 33.  Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.  <div style="text-align: center;">           T 27 N R 27 E                  1/4            S 32   S 33             2003         </div>
	Deposit a magnet, in a white plastic case, at the base of the stainless steel post.
55.05	Apache County Road C308, a graded road, 22 ft. wide, bears SSE and NNW.

**Survey of the Subdivisional Lines,  
T. 27 N., R. 27 E., Gila and Salt River Meridian, Arizona**

FEET									
61.93	High voltage transmission line, bears NE and SW.								
72.80	Trail road, bears SE and NW.								
80.00	Point for the cor. of secs. 28, 29, 32, and 33.  Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.								
	<table border="1"> <tr> <td>T 27 N</td> <td>R 27 E</td> </tr> <tr> <td>S 29</td> <td>S 28</td> </tr> <tr> <td>S 32</td> <td>S 33</td> </tr> </table>	T 27 N	R 27 E	S 29	S 28	S 32	S 33		
T 27 N	R 27 E								
S 29	S 28								
S 32	S 33								
	2003								
	Deposit a magnet, in a white plastic case, at the base of the stainless steel post.								
	Land, rolling and broken. Soil, sandy and rocky clay. Timber, scattered piñon and juniper; undergrowth, brush and native grasses.								
	<hr/>								
	From the cor. of secs. 27, 28, 33, and 34.								
	West, bet. secs. 28 and 33.								
	Over rolling land.								
10.95	Fish Wash, 30 ft. wide, 13 ft. deep, drains N.								
40.00	Point for the 1/4 sec. cor. of secs. 28 and 33.  Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.								
	<table border="1"> <tr> <td>T 27 N</td> <td>R 27 E</td> </tr> <tr> <td></td> <td>S 28</td> </tr> <tr> <td>1/4</td> <td>_____</td> </tr> <tr> <td></td> <td>S 33</td> </tr> </table>	T 27 N	R 27 E		S 28	1/4	_____		S 33
T 27 N	R 27 E								
	S 28								
1/4	_____								
	S 33								
	2003								
	Deposit a magnet, in a white plastic case, at the base of the stainless steel post.								
63.33	High voltage transmission line, bears NE and SW.								
80.00	The cor. of secs. 28, 29, 32, and 33.								

**Survey of the Subdivisional Lines,  
T. 27 N., R. 27 E., Gila and Salt River Meridian, Arizona**

FEET	
	<p>Land, rolling and broken. Soil, sandy and rocky clay. Timber, scattered piñon and juniper; undergrowth, brush and native grasses.</p> <hr/> <p>N. 0°03' W., bet. secs. 28 and 29.</p> <p>Over rolling land.</p>
19.67	High voltage transmission line, bears NE and SW.
40.00	Point for the 1/4 sec. cor. of secs. 28 and 29.
	<p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p align="center">                     T 27 N R 27 E                            1/4                      S 29   S 28                        2003                 </p> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p>
62.41	S. right-of-way fence of Arizona State Highway 264, barbed wire, 5 strand, parallels the highway.
63.92	Arizona State Highway 264, asphalt pavement, 26 ft. wide, bears E. and W.
65.46	N. right-of-way fence of Arizona State Highway 264, barbed wire, 5 strand, parallels the highway.
70.15	Underground gas pipeline, bears E. and W.
80.00	Point for the cor. of secs. 20, 21, 28, and 29.
	<p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p align="center">                     T 27 N R 27 E                      S 20   S 21  <hr style="width: 50%; margin: auto;"/>                     S 29   S 28                        2003                 </p> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p>

**Survey of the Subdivisional Lines,  
T. 27 N., R. 27 E., Gila and Salt River Meridian, Arizona**

FEET	
	<p>Land, rolling. Soil, sandy clay. Timber, scattered piñon and juniper; undergrowth, brush and native grasses.</p> <hr/> <p>From the cor. of secs. 21, 22, 27, and 28. West, bet. secs. 21 and 28. Over rolling and broken land.</p>
2.70	Trail road, bears ESE and WNW.
39.45	Fish Wash, 36 ft. wide, 25 ft. deep, drains NNW.
40.00	Point for the 1/4 sec. cor. of secs. 21 and 28.  Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 25 ins. in the ground, with brass cap mkd.
	<p>T 27 N R 27 E S 21 1/4 ——— S 28  2003</p>
	<p>from which</p> <p align="center">An X BO, chiseled on sandstone ledge, bears N. 83 1/2° W., 93 lks. dist.</p> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p> <p>Cor. is located 9 lks. W. of the west edge of Fish Wash, 36 ft. wide, 25 ft. deep, drains NNW.</p>
80.00	The cor. of secs. 20, 21, 28, and 29.  Land, rolling and broken. Soil, sandy and rocky clay with sandstone outcrops. Timber, scattered piñon and juniper; undergrowth, brush and native grasses.
	<hr/> <p>N. 0°03' W., bet. secs. 20 and 21. Over rolling and broken land.</p>
40.00	Point for the 1/4 sec. cor. of secs. 20 and 21.

**Survey of the Subdivisional Lines,  
T. 27 N., R. 27 E., Gila and Salt River Meridian, Arizona**

FEET	
	<p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T 27 N R 27 E 1/4 S 20   S 21</p> <p style="text-align: center;">2003</p> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p> <p>Cor. is located 67 lks. S. of a trail road, bears SE and NW.</p>
80.00	<p>Point for the cor. of secs. 16, 17, 20, and 21.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T 27 N R 27 E S 17   S 16 S 20   S 21</p> <p style="text-align: center;">2003</p> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p> <p>Land, rolling. Soil, sandy clay. Timber, scattered piñon and juniper; undergrowth, brush and native grasses.</p> <hr/> <p>From the cor. of secs. 15, 16, 21, and 22.</p> <p>West, bet. secs. 16 and 21.</p> <p>Over rolling land.</p>
40.00	<p>Point for the 1/4 sec. cor. of secs. 16 and 21.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T 27 N R 27 E S 16 1/4 ——— S 21</p> <p style="text-align: center;">2003</p>

**Survey of the Subdivisional Lines,  
T. 27 N., R. 27 E., Gila and Salt River Meridian, Arizona**

FEET	
	Deposit a magnet, in a white plastic case, at the base of the stainless steel post.
64.70	E. rim of Fish Wash canyon, top of sandstone ledge, bears NNE and SSW.
68.95	W. rim of the same canyon, top of sandstone ledge, bears NNE and SSW.
80.00	The cor. of secs. 16, 17, 20, and 21.  Land, rolling and broken. Soil, sandy and rocky clay with sandstone outcrops. Timber, scattered piñon and juniper; undergrowth, brush and native grasses.
	<hr/>
	N. 0°03' W., bet. secs. 16 and 17.  Over rolling and broken land.
14.20	S. rim of the Kinlichee Creek Canyon, top of sandstone ledge, bears ESE and WNW.
21.80	N. rim of the same canyon, top of sandstone ledge, bears NE and SW.
40.00	Point for the 1/4 sec. cor. of secs. 16 and 17.  Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.  <div style="text-align: center;">           T 27 N R 27 E                  1/4            S 17   S 16              2003         </div>
	Deposit a magnet, in a white plastic case, at the base of the stainless steel post.
80.00	Point for the cor. of secs. 8, 9, 16, and 17.  Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.  <div style="text-align: center;">           T 27 N R 27 E            S 8   S 9  <hr style="width: 50%; margin: 0 auto;"/>           S 17   S 16              2003         </div>



**Survey of the Subdivisional Lines,  
T. 27 N., R. 27 E., Gila and Salt River Meridian, Arizona**

FEET	
	<p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p> <p>Land, rolling and broken. Soil, sandy and rocky clay with sandstone outcrops. Timber, scattered piñon and juniper; undergrowth, brush and native grasses.</p> <hr/> <p>From the cor. of secs. 9, 10, 15, and 16.</p> <p>West, bet. secs. 9 and 16.</p> <p>Over rolling land.</p>
40.00	<p>Point for the 1/4 sec. cor. of secs. 9 and 16.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p align="center">T 27 N R 27 E S 9 1/4 ——— S 16</p> <p align="center">2003</p>
80.00	<p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p> <p>The cor. of secs. 8, 9, 16, and 17.</p> <p>Land, rolling. Soil, sandy clay. Timber, scattered piñon and juniper; undergrowth, brush and native grasses.</p> <hr/> <p>N. 0°03' W., bet. secs. 8 and 9.</p> <p>Over rolling land.</p>
1.79	Trail road, bears NE and SW.
38.50	Barbed wire fence, 4 strand, bears ESE and WNW.
40.00	<p>Point for the 1/4 sec. cor. of secs. 8 and 9.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p>

**Survey of the Subdivisional Lines,  
T. 27 N., R. 27 E., Gila and Salt River Meridian, Arizona**

FEET	
	T 27 N R 27 E 1/4 S 8   S 9  2003
	Deposit a magnet, in a white plastic case, at the base of the stainless steel post.
41.84	Barbed wire fence, 3 strand, bears NNE and SSW.
80.00	Point for the cor. of secs. 4, 5, 8, and 9.
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.
	T 27 N R 27 E S 5   S 4 S 8   S 9  2003
	Deposit a magnet, in a white plastic case, at the base of the stainless steel post.
	Land, rolling. Soil, sandy clay. Timber, piñon and juniper; undergrowth, brush and native grasses.
	From the cor. of secs. 3, 4, 9, and 10.
	West, bet. secs. 4 and 9.
39.85	Trail road, bears SE and NW.
40.00	Point for the 1/4 sec. cor. of secs. 4 and 9.
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., flush with the surface of the ground, with brass cap mkd.
	T 27 N R 27 E S 4 1/4 ——— S 9  2003
	Deposit a magnet, in a white plastic case, at the base of the stainless steel post.

**Survey of the Subdivisional Lines,  
T. 27 N., R. 27 E., Gila and Salt River Meridian, Arizona**

FEET	
45.03	Barbed wire fence, 3 strand, bears NNE and SSW.
80.00	The cor. of secs. 4, 5, 8, and 9.  Land, rolling. Soil, sandy clay. Timber, piñon and juniper; undergrowth, brush and native grasses.
	N. 0°03' W., bet. secs. 4 and 5.  Over rolling land.
40.00	Point for the 1/4 sec. cor. of secs. 4 and 5.  Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.  T 27 N R 27 E 1/4 S 5   S 4  2003  Deposit a magnet, in a white plastic case, at the base of the stainless steel post.
55.15	Barbed wire fence, 4 strand, bears NE and SW.
80.00	The cor. of secs. 4, 5, 32, and 33, on the N. bdy. of the Tp., hereinbefore described.  Land, rolling. Soil, sandy clay. Timber, piñon and juniper; undergrowth, brush and native grasses.
	From the cor. of secs. 5, 6, 31, and 32, on the S. bdy. of the Tp., hereinbefore described.  N. 0°03' W., bet. secs. 31 and 32.  Over rolling land.
40.00	Point for the 1/4 sec. cor. of secs. 31 and 32.  Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.

**Survey of the Subdivisional Lines,  
T. 27 N., R. 27 E., Gila and Salt River Meridian, Arizona**

FEET	
	T 27 N R 27 E 1/4 S 31   S 32  2003
	Deposit a magnet, in a white plastic case, at the base of the stainless steel post.
41.45	High voltage transmission line, bears NE and SW.
80.00	Point for the cor. of secs. 29, 30, 31, and 32.
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.
	T 27 N R 27 E S 30   S 29 S 31   S 32  2003
	Deposit a magnet, in a white plastic case, at the base of the stainless steel post.
	Land, rolling. Soil, sandy clay. Timber, scattered piñon and juniper; undergrowth, brush and native grasses.
	From the cor. of secs. 28, 29, 32, and 33.
	West, bet. secs. 29 and 32.
	Over rolling land.
6.35	Trail road, bears SSE and NNW.
7.15	Apache County Road C308, a graded road, 22 ft. wide, bears SSE and NNW.
27.01	High voltage transmission line, bears NE and SW.
35.90	Haakai Daachaahi Wash, 30 ft. wide, 10 ft. deep, drains WNW; thence along the S. bank of the wash.
40.00	Point for the 1/4 sec. cor. of secs. 29 and 32.
	Set a magnet, in a white plastic case, 24 ins. below the surface of the ground.

**Survey of the Subdivisional Lines,  
T. 27 N., R. 27 E., Gila and Salt River Meridian, Arizona**

FEET	
	<p>from which</p> <p>A stainless steel post, 28 ins. long, 2 1/2 ins. diam., set 24 ins. in ground for a reference monument, bears N. 45°00' E., 150.0 ft. dist., with brass cap mkd. RM T27N R27E 1/4 S29 150.0 FT. TO COR. 2003, and an arrow pointing to the cor. Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p> <p>A stainless steel post, 28 ins. long, 2 1/2 ins. diam., set 24 ins. in ground for a reference monument, bears S. 45°00' W., 100.0 ft. dist., with brass cap mkd. RM T27N R27E 1/4 S32 100.0 FT. TO COR. 2003, and an arrow pointing to the cor. Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p> <p>Cor. is located on S. edge of Haakai Daachaahi Wash, 30 ft. wide, 10 ft. deep, drains WNW.</p>
80.00	<p>The cor. of secs. 29, 30, 31, and 32.</p> <p>Land, rolling and broken. Soil, sandy and rocky clay. Timber, scattered piñon and juniper; undergrowth, brush and native grasses.</p> <hr/> <p>West, bet. secs. 30 and 31.</p> <p>Over rolling land.</p>
38.75	<p>Wash, 50 ft. wide, 4 ft. deep, drains NW.</p>
40.00	<p>Point for the 1/4 sec. cor. of secs. 30 and 31.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T 27 N R 27 E S 30 1/4 ——— S 31</p> <p style="text-align: center;">2003</p> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p>
65.64	<p>Power line, bears NNE and SSW.</p>
68.35	<p>Trail road, bears SSE and NNW.</p>

**Survey of the Subdivisional Lines,  
T. 27 N., R. 27 E., Gila and Salt River Meridian, Arizona**

FEET																									
70.35	<p>Point for the closing cor. of secs. 30 and 31, at intersection with the E. bdy. of T. 27 N., R. 26 E.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center;"> <table style="border-collapse: collapse; margin: auto;"> <tr> <td style="padding-right: 10px;">T 27 N</td> <td style="border-left: 1px solid black; padding-left: 10px;">T 27 N</td> <td></td> </tr> <tr> <td style="padding-right: 10px;">R 26 E</td> <td style="border-left: 1px solid black; padding-left: 10px;">R 27 E</td> <td></td> </tr> <tr> <td></td> <td style="border-left: 1px solid black; padding-left: 10px;">S 30</td> <td></td> </tr> <tr> <td style="padding-right: 10px;">S 25</td> <td style="border-left: 1px solid black; padding-left: 10px;">S 31</td> <td style="padding-left: 10px;">CC</td> </tr> </table> </div> <p style="text-align: center;">2003</p> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p> <p>Cor. is located 92 lks. S. of a trail road, bears NE and SW.</p> <p>From this cor. point, the cor. of secs. 25, 30, 31, and 36, on the E. bdy. of T. 27 N., Rs. 26 and 27 E., bears S. 0°05' W., 6.385 chs. dist., monumented with a stainless steel post, 2 1/2 ins. diam., firmly set flush with the surface of the ground, with brass cap mkd. T27N R26E R27E S25 S30 S36 S31 1990. This cor. now becomes sec. cor. of secs. 25 and 36 only, T. 27 N., R. 26 E. Remark the brass cap to read</p> <div style="text-align: center;"> <table style="border-collapse: collapse; margin: auto;"> <tr> <td style="padding-right: 10px;">T 27 N</td> <td style="border-left: 1px solid black; padding-left: 10px;">T 27 N</td> <td></td> </tr> <tr> <td style="padding-right: 10px;">R 26 E</td> <td style="border-left: 1px solid black; padding-left: 10px;">R 27 E</td> <td></td> </tr> <tr> <td style="padding-right: 10px;">S 25</td> <td style="border-left: 1px solid black; padding-left: 10px;">S 31</td> <td></td> </tr> <tr> <td style="padding-right: 10px;">S 36</td> <td style="border-left: 1px solid black; padding-left: 10px;"></td> <td></td> </tr> </table> </div> <p style="text-align: center;">2003 1990</p> <p>Land, rolling. Soil, sandy clay. Timber, scattered piñon and juniper; undergrowth, brush and native grasses.</p> <hr style="width: 50%; margin-left: auto; margin-right: auto;"/> <p>Point for the 1/4 sec. cor. of sec. 31 only, T. 27 N., R. 27 E., at midpoint on the W. bdy. of sec. 31, on the E. bdy. of T. 27 N., R. 26 E.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p>	T 27 N	T 27 N		R 26 E	R 27 E			S 30		S 25	S 31	CC	T 27 N	T 27 N		R 26 E	R 27 E		S 25	S 31		S 36		
T 27 N	T 27 N																								
R 26 E	R 27 E																								
	S 30																								
S 25	S 31	CC																							
T 27 N	T 27 N																								
R 26 E	R 27 E																								
S 25	S 31																								
S 36																									

**Survey of the Subdivisional Lines,  
T. 27 N., R. 27 E., Gila and Salt River Meridian, Arizona**

FEET	
	T 27 N R 26 E    R 27 E   1/4   S 31  2003
	Deposit a magnet, in a white plastic case, at the base of the stainless steel post.
	From this cor. point, the 1/4 sec. cor. of secs. 31 and 36, T. 27 N., Rs. 26 and 27 E., bears S. 0°05' W., 6.38 chs. dist., monumented with a stainless steel post, 2 1/2 ins. diam., firmly set, projecting 6 ins. above ground, with brass cap mkd. T27N R26E R27E 1/4 S36 S31 1990. This cor. now becomes the 1/4 sec. cor. of sec. 36 only, T. 27 N., R. 26 E. Remark the brass cap to read
	T 27 N R 26 E    R 27 E 1/4   S 36   2003 1990
	<hr/> From the cor. of secs. 29, 30, 31, and 32.  N. 0°03' W., bet. secs. 29 and 30.  Over rolling and broken land.
6.30	Haakai Daachaahi Wash, 22 ft. wide, 8 ft. deep, drains WSW.
28.48	S. right-of-way fence of Arizona State Highway 264, barbed wire, 5 strand, parallels the highway.
29.96	Arizona State Highway 264, asphalt pavement, 26 ft. wide, bears ENE and WSW.
31.59	N. right-of-way fence of Arizona State Highway 264, barbed wire, 5 strand, parallels the highway.
32.70	Underground gas pipeline, bears ENE and WSW.
40.00	Point for the 1/4 sec. cor. of secs. 29 and 30.  Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.

**Survey of the Subdivisional Lines,  
T. 27 N., R. 27 E., Gila and Salt River Meridian, Arizona**

FEET	
	T 27 N R 27 E 1/4 S 30   S 29  2003
	Deposit a magnet, in a white plastic case, at the base of the stainless steel post.
41.40	Graded road, 20 ft. wide, bears NNE and SSW.
43.79	Power line, bears ENE and WSW.
80.00	Point for the cor. of secs. 19, 20, 29, and 30.
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.
	T 27 N R 27 E S 19   S 20 S 30   S 29  2003
	Deposit a magnet, in a white plastic case, at the base of the stainless steel post.
	Cor. is located 91 lks. S. of a trail road, bears ESE and WNW.
	Land, rolling and broken. Soil, sandy and gravelly clay. Timber, scattered piñon and juniper; undergrowth, brush and native grasses.
	From the cor. of secs. 20, 21, 28, and 29.
	West, bet. secs. 20 and 29.
	Over rolling land.
39.15	Apache County Road C457, a graded road, 20 ft. wide, bears SE and NW.
40.00	Point for the 1/4 sec. cor. of secs. 20 and 29.
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.



**Survey of the Subdivisional Lines,  
T. 27 N., R. 27 E., Gila and Salt River Meridian, Arizona**

FEET	
	T 27 N R 27 E S 20 1/4 ——— S 29  2003
	Deposit a magnet, in a white plastic case, at the base of the stainless steel post.
78.60	Trail road, bears ESE and WNW.
80.00	The cor. of secs. 19, 20, 29, and 30.
	Land, rolling. Soil, sandy and gravelly clay. Timber, scattered piñon and juniper; undergrowth, brush and native grasses.
	West, bet. secs. 19 and 30.
	Over rolling and broken land.
40.00	Point for the 1/4 sec. cor. of secs. 19 and 30.
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.
	T 27 N R 27 E S 19 1/4 ——— S 30  2003
	Deposit a magnet, in a white plastic case, at the base of the stainless steel post.
60.35	Haakai Daachaahi Wash, 42 ft. wide, 5 ft. deep, drains NNW.
70.22	Point for the closing cor. of secs. 19 and 30, at intersection with the E. bdy. of T. 27 N., R. 26 E.
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.

**Survey of the Subdivisional Lines,  
T. 27 N., R. 27 E., Gila and Salt River Meridian, Arizona**

FEET

T 27 N	T 27 N	
R 26 E	R 27 E	
	S 19	
S 24	S 30	CC

2003

Deposit a magnet, in a white plastic case, at the base of the stainless steel post.

From this cor. point, the cor. of secs. 19, 24, 25, and 30, on the E. bdy. of T. 27 N., R. 26 E., bears S. 0°02' E., 6.415 chs. dist., monumented with an iron post, 3 ins. diam., firmly set, projecting 7 ins. above ground, with brass cap mkd. T27N R26E R27E S24 S19 S25 S30 1990 1915. This cor. now becomes sec. cor. of secs. 24 and 25 only, T. 27 N., R. 26 E. Remark the brass cap to read

T 27 N	T 27 N	
R 26 E	R 27 E	
	S 24	
S 25	S 30	

2003

1990

1915

from which the 1915 bearing trees

A piñon stump, 15 ins. diam., bears N. 73° E., 94 lks. dist., projecting 14 ins. high, with no scribe marks. (Record: 24 ins. diam.)

A piñon, 12 ins. diam., bears S. 37 1/2° W., 1.29 chs. dist., with scribe marks T27N R26E S25 BT visible on partially healed blaze. (Record: 20 ins. diam.)

A piñon stump, 30 ins. diam., bears N. 46° W., 84 lks. dist., with scribe marks 27N 26E S24 BT visible on open blaze.

Land, rolling.

Soil, sandy and gravelly clay.

Timber, scattered piñon and juniper; undergrowth, brush and native grasses.

---

Point for the 1/4 sec. cor. of sec. 30 only, T. 27 N., R. 27 E., at midpoint on the W. bdy. of sec. 30, on the E. bdy. of T. 27 N., R. 26 E.

**Survey of the Subdivisional Lines,  
T. 27 N., R. 27 E., Gila and Salt River Meridian, Arizona**

FEET	
	<p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p align="center">T 27 N R 26 E R 27 E   1/4   S 30</p> <p align="center">2003</p> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p> <p>From this cor. point, the 1/4 sec. cor. of secs. 25 and 30, T. 27 N., Rs. 26 and 27 E., bears South, 6.395 chs. dist., monumented with a stainless steel post, 2 1/2 ins. diam., firmly set, projecting 6 ins. above ground, with brass cap mkd. T27N R26E R27E 1/4 S25 S30 1990. This cor. now becomes the 1/4 sec. cor. of sec. 25 only, T. 27 N., R. 26 E. Remark the brass cap to read.</p> <p align="center">T 27 N R 26 E R 27 E 1/4   S 25   2003 1990</p> <p>from which the remaining 1915 bearing tree</p> <p align="center">A piñon, 20 ins. diam., bears N. 74 1/2° E., 1.30 chs. dist., with scribe marks BT visible on open blaze. Defaced the scribe marks.</p>
40.00	<hr/> <p>From the cor. of secs. 19, 20, 29, and 30.</p> <p>N. 0°03' W., bet. secs. 19 and 20.</p> <p>Over rolling and broken land.</p> <p>Point for the 1/4 sec. cor. of secs. 19 and 20.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p align="center">T 27 N R 27 E 1/4 S 19   S 20</p> <p align="center">2003</p>

**Survey of the Subdivisional Lines,  
T. 27 N., R. 27 E., Gila and Salt River Meridian, Arizona**

FEET							
	Deposit a magnet, in a white plastic case, at the base of the stainless steel post.						
60.19	Power line, bears E. and W.						
80.00	Point for the cor. of secs. 17, 18, 19, and 20.  Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 17 ins. below the surface of the ground, with brass cap mkd.						
	<table style="margin-left: auto; margin-right: auto;"> <tr> <td>T 27 N</td> <td>R 27 E</td> </tr> <tr> <td>S 18</td> <td>S 17</td> </tr> <tr> <td>S 19</td> <td>S 20</td> </tr> </table>	T 27 N	R 27 E	S 18	S 17	S 19	S 20
T 27 N	R 27 E						
S 18	S 17						
S 19	S 20						
	2003						
	from which						
	<p>A stainless steel post, 28 ins. long, 2 1/2 ins. diam., set 24 ins. in ground for a reference monument, bears N. 45°00' E., 200.0 ft. dist., with brass cap mkd. RM T27N R27E S17 RM 200.0 FT TO COR 2003, and an arrow pointing to the cor. Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p> <p>A stainless steel post, 28 ins. long, 2 1/2 ins. diam., set 24 ins. in ground for a reference monument, bears S. 45°00' E., 200.0 ft. dist., with brass cap mkd. RM T27N R27E S20 RM 200.0 FT TO COR 2003, and an arrow pointing to the cor. Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p>						
	Deposit a magnet, in a white plastic case, at the base of the stainless steel post at the sec. cor.						
	Cor. is located in cultivated field, enclosed with woven wire fence.						
	Land, rolling. Soil, sandy and gravelly clay. Timber, scattered piñon and juniper; undergrowth, brush and native grasses.						
	From the cor. of secs. 16, 17, 20, and 21.						
	West, bet. secs. 17 and 20.						
	Over rolling land.						
40.00	Point for the 1/4 sec. cor. of secs. 17 and 20.						

**Survey of the Subdivisional Lines,  
T. 27 N., R. 27 E., Gila and Salt River Meridian, Arizona**

FEET	
	<p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T 27 N R 27 E S 17 1/4 ——— S 20</p> <p style="text-align: center;">2003</p> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p>
76.45	Trail road, bears NE and SW.
80.00	The cor. of secs. 17, 18, 19, and 20.
	<p>Land, rolling and broken. Soil, sandy and gravelly clay. Timber, piñon and juniper; undergrowth, brush and native grasses.</p> <hr/> <p>West, bet. secs. 18 and 19.</p> <p>Over rolling and broken land.</p>
18.80	Pueblo Colorado Wash, 100 ft. wide, 10 ft. deep, drains SW.
33.80	Pueblo Colorado Wash, 60 ft. wide, 4 ft. deep, drains NNW.
40.00	Point for the 1/4 sec. cor. of secs. 18 and 19.
	<p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T 27 N R 27 E S 18 1/4 ——— S 19</p> <p style="text-align: center;">2003</p> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p>
49.15	Pueblo Colorado Wash, 60 ft. wide, 6 ft. deep, drains SSW.
70.19	Point for the closing cor. of secs. 18 and 19, at intersection with the E. bdy. of T. 27 N., R. 26 E.
	<p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p>

**Survey of the Subdivisional Lines,  
T. 27 N., R. 27 E., Gila and Salt River Meridian, Arizona**

FEET

T 27 N	T 27 N
R 26 E	R 27 E
	S 18
S 13	CC
	S 19

2003

Deposit a magnet, in a white plastic case, at the base of the stainless steel post.

From this cor. point, the cor. of secs. 13, 18, 19, and 24, on the E. bdy. of T. 27 N., R. 26 E., bears South, 6.545 chs. dist., monumented with an iron post, 3 ins. diam., firmly set, projecting 12 ins. above ground, with brass cap mkd. T27N R26E R27E S13 S18 S24 S19 1990 1915. This cor. now becomes sec. cor. of secs. 13 and 24 only, T. 27 N., R. 26 E. Remark the brass cap to read

T 27 N	T 27 N
R 26 E	R 27 E
S 13	S 19
S 24	

2003

1990

1915

Land, rolling.

Soil, sandy clay.

Timber, scattered piñon and juniper; undergrowth, brush and native grasses.

---

Point for the 1/4 sec. cor. of sec. 19 only, T. 27 N., R. 27 E., at midpoint on the W. bdy. of sec. 19, on the E. bdy. of T. 27 N., R. 26 E.

Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 25 ins. in the ground, with brass cap mkd.

T 27 N	T 27 N
R 26 E	R 27 E
	1/4
	S 19

2003

Deposit a magnet, in a white plastic case, at the base of the stainless steel post.

**Survey of the Subdivisional Lines,  
T. 27 N., R. 27 E., Gila and Salt River Meridian, Arizona**

FEET	
	<p>From this cor. point, the 1/4 sec. cor. of secs. 19 and 24, T. 27 N., Rs. 26 and 27 E., bears S. 0°02' E., 6.48 chs. dist., monumented with a stainless steel post, 2 1/2 ins. diam., firmly set, projecting 3 ins. above ground, with brass cap mkd. T27N R26E R27E 1/4 S24 S19 1990. This cor. now becomes the 1/4 sec. cor. of sec. 24 only, T. 27 N., R. 26 E. Remark the brass cap to read</p>
	<pre> T 27 N R 26 E R 27 E   1/4   S 24                 2003       1990           </pre>
	<p>from which</p> <p style="padding-left: 40px;">A brass tablet, 3 1/4 ins. diam., set flush with sandstone bedrock, cemented in place, for a reference monument, bears S. 30°00' E., 120.0 ft. dist., with top mkd. RM T27N R27E 1/4 S19 120.0 FT TO COR 1990, and an arrow pointing to the cor. Remove the 1/4 mark and add the marks 2003 to the brass cap.</p> <p style="padding-left: 40px;">A stainless steel post, 2 1/2 ins. diam., firmly set, projecting 4 ins. above ground for a reference monument, bears S. 60°00' W., 220.0 ft. dist., with brass cap mkd. RM T27N R26E 1/4 S24 220.0 FT TO COR 1990, and an arrow pointing to the cor. Add the marks 2003 to the brass cap.</p>
	<hr/> <p>From the cor. of secs. 17, 18, 19, and 20.</p> <p>N. 0°03' W., bet. secs. 17 and 18.</p> <p>Over rolling and broken land.</p>
19.15	Kinlichee Creek, a wash, 100 ft. wide, 14 ft. deep, drains WSW.
40.00	<p>Point for the 1/4 sec. cor. of secs. 17 and 18.</p> <p>Set a brass tablet, 3 1/4 ins. diam., 2 1/2 ins. stem, cemented in a drill hole, on sandstone outcrop, with top mkd.</p>
	<pre> T 27 N R 27 E   1/4 S 18   S 17               2003           </pre>
	<p>Deposit a magnet, in a white plastic case, at the base of the brass tablet.</p>

**Survey of the Subdivisional Lines,  
T. 27 N., R. 27 E., Gila and Salt River Meridian, Arizona**

FEET									
	Cor. is located on E. bank of a spillway for a earthen dam, 45 ft. wide, 5 ft. deep, drains SSE; thence enter the flood plains and pasture areas.								
55.97	Barbed wire fence, 4 strand, bears ESE and WNW.								
80.00	Point for the cor. of secs. 7, 8, 17, and 18.  Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a steel fence post, 6 ft. long, with brass cap mkd.								
	<table style="margin-left: auto; margin-right: auto;"> <tr> <td>T 27 N</td> <td>R 27 E</td> </tr> <tr> <td>S 7</td> <td>S 8</td> </tr> <tr> <td>S 18</td> <td>S 17</td> </tr> </table>	T 27 N	R 27 E	S 7	S 8	S 18	S 17		
T 27 N	R 27 E								
S 7	S 8								
S 18	S 17								
	2003								
	Deposit a magnet, in a white plastic case, at the base of the stainless steel post, alongside the steel fence post.								
	Land, rolling and broken to nearly level. Soil, sandy and gravelly clay. Timber, scattered piñon and juniper; undergrowth, brush and native grasses.								
	From the cor. of secs. 8, 9, 16, and 17.  West, bet. secs. 8 and 17.  Over rolling land.								
1.93	Trail road, bears NE and SW.								
40.00	Point for the 1/4 sec. cor. of secs. 8 and 17.  Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.								
	<table style="margin-left: auto; margin-right: auto;"> <tr> <td>T 27 N</td> <td>R 27 E</td> </tr> <tr> <td></td> <td>S 8</td> </tr> <tr> <td></td> <td>1/4 ———</td> </tr> <tr> <td></td> <td>S 17</td> </tr> </table>	T 27 N	R 27 E		S 8		1/4 ———		S 17
T 27 N	R 27 E								
	S 8								
	1/4 ———								
	S 17								
	2003								
	Deposit a magnet, in a white plastic case, at the base of the stainless steel post.								
64.44	Barbed wire fence, 5 strand, bears N. and S.; thence enter the flood plains of Lone Tule Wash.								



**Survey of the Subdivisional Lines,  
T. 27 N., R. 27 E., Gila and Salt River Meridian, Arizona**

FEET	
80.00	<p>The cor. of secs. 7, 8, 17, and 18.</p> <p>Land, rolling to nearly level. Soil, sandy and gravelly clay. Timber, scattered piñon and juniper; undergrowth, brush and native grasses.</p> <hr/> <p>West, bet. secs. 7 and 18.</p> <p>Over nearly level land.</p>
27.81	Barbed wire fence, 5 strand, bears N. and S.; thence over rolling land.
40.00	<p>Point for the 1/4 sec. cor. of secs. 7 and 18.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center;"> <p>T 27 N R 27 E S 7 1/4 ——— S 18</p> <p>2003</p> </div> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p>
50.00	E. right-of-way fence of Navajo Route 27, barbed wire, 5 strand, parallels the highway.
51.56	Navajo Route 27, asphalt pavement, 32 ft. wide, bears NNE and SSW.
53.14	W. right-of-way fence of Navajo Route 27, barbed wire, 5 strand, parallels the highway.
60.15	Underground gas pipeline, bears N. and S.
70.11	<p>Point for the closing cor. of secs. 7 and 18, at intersection with the E. bdy. of T. 27 N., R. 26 E.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p>

**Survey of the Subdivisional Lines,  
T. 27 N., R. 27 E., Gila and Salt River Meridian, Arizona**

FEET

T 27 N	T 27 N
R 26 E	R 27 E
	S 7
S 12	CC
	S 18

2003

Deposit a magnet, in a white plastic case, at the base of the stainless steel post.

From this cor. point, the cor. of secs. 7, 12, 13, and 18, on the E. bdy. of T. 27 N., R. 26 E., bears South, 6.545 chs. dist., monumented with a stainless steel post, 2 1/2 ins. diam., firmly set, projecting 4 ins. above ground, with brass cap mkd. T27N R26E R27E S12 S7 S13 S18 1990. This cor. now becomes sec. cor. of secs. 12 and 13 only, T. 27 N., R. 26 E. Remark the brass cap to read

T 27 N	T 27 N
R 26 E	R 27 E
S 12	
S 13	S 18

2003  
1990

Land, rolling.  
Soil, sandy and gravelly clay.  
Timber, scattered piñon and juniper; undergrowth, brush and native grasses.

---

Point for the 1/4 sec. cor. of sec. 18 only, T. 27 N., R. 27 E., at midpoint on the W. bdy. of sec. 18, on the E. bdy. of T. 27 N., R. 26 E.

Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., flush with the ground, with brass cap mkd.

T 27 N	
R 26 E	R 27 E
	1/4
	S 18

2003

Survey of the Subdivisional Lines,  
T. 27 N., R. 27 E., Gila and Salt River Meridian, Arizona

FEET

from which

A stainless steel post, 28 ins. long, 2 1/2 ins. diam., set 24 ins. in the ground for a reference monument, bears N. 65°00' E., 227.0 ft. dist., with brass cap mkd. RM T27N R27E 1/4 S18 227.0 FT TO COR 2003, and an arrow pointing to the cor. Deposit a magnet, in a white plastic case, at the base of the stainless steel post. Located along the E. right-of-way fence of Navajo Route 27, barbed wire, 5 strand, parallels the highway.

A stainless steel post, 28 ins. long, 2 1/2 ins. diam., set 24 ins. in the ground for a reference monument, bears S. 25°00' E., 166.0 ft. dist., with brass cap mkd. RM T27N R27E 1/4 S18 166.0 FT TO COR 2003, and an arrow pointing to the cor. Deposit a magnet, in a white plastic case, at the base of the stainless steel post. Located along the E. right-of-way fence of Navajo Route 27, barbed wire, 5 strand, parallels the highway.

Deposit a magnet, in a white plastic case, at the base of the stainless steel post.

Cor. is located 1.06 chs. N. of Navajo Route 27, asphalt pavement, 32 ft. wide, bears NNE and SSW.

From this cor. point, the 1/4 sec. cor. of secs. 13 and 18, T. 27 N., Rs. 26 and 27 E., bears South, 6.545 chs. dist., monumented with a stainless steel post, 2 1/2 ins. diam., firmly set, projecting 4 ins. above ground, with brass cap mkd. T27N R26E R27E 1/4 S13 S18 1990. This cor. now becomes the 1/4 sec. cor. of sec. 13 only, T. 27 N., R. 26 E. Remark the brass cap to read

T 27 N  
R 26 E R 27 E  
1/4 |  
S 13 |  
2003  
1990

from which

A brass tablet, 3 ins. diam., set flush in concrete collar, 8 ins. diam., firmly set, projecting 9 ins. above ground, bears N. 71 1/4° W., 1.16 chs. dist., with top mkd. B.I.A ROADS 19, and witnessed by an angle iron, firmly set, projecting 16 ins. above ground, mkd. +43.23 on the side.

---

From the cor. of secs. 7, 8, 17, and 18.

**Survey of the Subdivisional Lines,  
T. 27 N., R. 27 E., Gila and Salt River Meridian, Arizona**

FEET	
	N. 0°03' W., bet. secs. 7 and 8.
	Over nearly level land, the flood plains of Lone Tule Wash.
40.00	Point for the 1/4 sec. cor. of secs. 7 and 8.
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.
	T 27 N R 27 E 1/4 S 7   S 8  2003
	Deposit a magnet, in a white plastic case, at the base of the stainless steel post.
80.00	Point for the cor. of secs. 5, 6, 7, and 8.
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a steel fence post, 6 ft. long, with brass cap mkd.
	T 27 N R 27 E S 6   S 5 --- S 7   S 8  2003
	Deposit a magnet, in a white plastic case, at the base of the stainless steel post, alongside the steel fence post.
	Land, nearly level.
	Soil, sandy clay.
	No timber, scattered brush and native grasses.
	<hr/>
	From the cor. of secs. 4, 5, 8, and 9.
	West, bet. secs. 5 and 8.
	Over rolling land.
40.00	Point for the 1/4 sec. cor. of secs. 5 and 8.
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.

**Survey of the Subdivisional Lines,  
T. 27 N., R. 27 E., Gila and Salt River Meridian, Arizona**

FEET	
	T 27 N R 27 E S 5 1/4 ——— S 8  2003
	Deposit a magnet, in a white plastic case, at the base of the stainless steel post.
54.37	Barbed wire fence, 4 strand, bears NE and SW.
60.29	Power line, bears ESE and WNW.
76.95	Lone Tule Wash, 40 ft. wide, 1 ft. deep, turns into flood plains, drains S.
80.00	The cor. of secs. 5, 6, 7, and 8.  Land, rolling to nearly level. Soil, sandy and gravelly clay. Timber, scattered piñon and juniper; undergrowth, brush and native grasses.
	—————
	West, bet. secs. 6 and 7.  Over nearly level land.
22.73	Woven wire fence with barbed wire, 3 strand, bears N. and S.; thence leave the pasture area into rolling land.
23.85	Trail road, bears NNE and SSW.
25.96	Power line, bears NNE and SSW.
26.88	Intersect E. wall of a sandstone masonry house, 33 x 13 ft.; the NE cor. bears N. 37 1/2° E., 7 1/2 lks dist., the long side bears SW.
40.00	Point for the 1/4 sec. cor. of secs. 6 and 7.  Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.
	T 27 N R 27 E S 6 1/4 ——— S 7  2003

**Survey of the Subdivisional Lines,  
T. 27 N., R. 27 E., Gila and Salt River Meridian, Arizona**

FEET											
	Deposit a magnet, in a white plastic case, at the base of the stainless steel post.										
42.83	E. right-of-way fence of Navajo Route 27, barbed wire, 5 strand, parallels the highway.										
44.33	Navajo Route 27, asphalt pavement, 32 ft. wide, bears N. and S.										
45.87	W. right-of-way fence of Navajo Route 27, barbed wire, 5 strand, parallels the highway.										
50.85	Underground gas pipeline, bears N. and S.										
70.04	Point for the closing cor. of secs. 6 and 7, at intersection with the E. bdy. of T. 27 N., R. 26 E.										
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 20 ins. in the ground, to sandstone bedrock, in a mound of stone, 3 ft. base, to top, with brass cap mkd.										
	<table style="margin-left: auto; margin-right: auto;"> <tr> <td style="padding-right: 10px;">T 27 N</td> <td style="border-left: 1px solid black; padding-left: 10px;">T 27 N</td> </tr> <tr> <td style="padding-right: 10px;">R 26 E</td> <td style="border-left: 1px solid black; padding-left: 10px;">R 27 E</td> </tr> <tr> <td></td> <td style="border-left: 1px solid black; padding-left: 10px;">S 6</td> </tr> <tr> <td style="padding-right: 10px;">S 1</td> <td style="border-left: 1px solid black; padding-left: 10px;">----- CC</td> </tr> <tr> <td></td> <td style="border-left: 1px solid black; padding-left: 10px;">S 7</td> </tr> </table>	T 27 N	T 27 N	R 26 E	R 27 E		S 6	S 1	----- CC		S 7
T 27 N	T 27 N										
R 26 E	R 27 E										
	S 6										
S 1	----- CC										
	S 7										
	2003										
	Deposit a magnet, in a white plastic case, at the base of the stainless steel post.										
	From this cor. point, the cor. of secs. 1, 6, 7, and 12, on the E. bdy. of T. 27 N., R. 26 E., bears South, 6.555 chs. dist., monumented with a stainless steel post, 2 1/2 ins. diam., firmly set, projecting 7 ins. above ground, with brass cap mkd. T27N R26E R27E S1 S6 S12 S7 1990. This cor. now becomes sec. cor. of secs. 1 and 12 only, T. 27 N., R. 26 E. Remark the brass cap to read										
	<table style="margin-left: auto; margin-right: auto;"> <tr> <td style="padding-right: 10px;">T 27 N</td> <td style="border-left: 1px solid black; padding-left: 10px;">T 27 N</td> </tr> <tr> <td style="padding-right: 10px;">R 26 E</td> <td style="border-left: 1px solid black; padding-left: 10px;">R 27 E</td> </tr> <tr> <td style="padding-right: 10px;">S 1</td> <td style="border-left: 1px solid black; padding-left: 10px;">S 7</td> </tr> <tr> <td style="padding-right: 10px;">-----</td> <td style="border-left: 1px solid black; padding-left: 10px;"></td> </tr> <tr> <td style="padding-right: 10px;">S 12</td> <td style="border-left: 1px solid black; padding-left: 10px;"></td> </tr> </table>	T 27 N	T 27 N	R 26 E	R 27 E	S 1	S 7	-----		S 12	
T 27 N	T 27 N										
R 26 E	R 27 E										
S 1	S 7										
-----											
S 12											
	2003 1990										
	Land, nearly level to rolling. Soil, sandy and rocky clay. Timber, scattered piñon and juniper; undergrowth, brush and native grasses.										

**Survey of the Subdivisional Lines,  
T. 27 N., R. 27 E., Gila and Salt River Meridian, Arizona**

FEET

Point for the 1/4 sec. cor. of sec. 7 only, T. 27 N., R. 27 E., at midpoint on the W. bdy. of sec. 7, on the E. bdy. of T. 27 N., R. 26 E.

Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.

T 27 N  
R 26 E R 27 E  
| 1/4  
| S 7

2003

Deposit a magnet, in a white plastic case, at the base of the stainless steel post.

From this cor. point, the 1/4 sec. cor. of secs. 7 and 12, T. 27 N., Rs. 26 and 27 E., bears South, 6.55 chs. dist., monumented with a stainless steel post, 2 1/2 ins. diam., firmly set, projecting 4 ins. above ground, in a collar of stone, with brass cap mkd. T27N R26E R27E 1/4 S12 S7 1990. This cor. now becomes the 1/4 sec. cor. of sec. 12 only, T. 27 N., R. 26 E. Remark the brass cap to read

T 27 N  
R 26 E R 27 E  
1/4 |  
S 12 |  
2003  
1990

Point for the 1/4 sec. cor. of sec. 6 only, T. 27 N., R. 27 E., at midpoint on the W. bdy. of sec. 6, on the E. bdy. of T. 27 N., R. 26 E.

Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.

T 27 N  
R 26 E R 27 E  
| 1/4  
| S 6

2003

Deposit a magnet, in a white plastic case, at the base of the stainless steel post.

**Survey of the Subdivisional Lines,  
T. 27 N., R. 27 E., Gila and Salt River Meridian, Arizona**

FEET	
	<p>From this cor. point, the 1/4 sec. cor. of secs. 1 and 6, T. 27 N., Rs. 26 and 27 E., bears South, 6.555 chs. dist., monumented with a stainless steel post, 2 1/2 ins. diam., firmly set, projecting 6 ins. above ground, with brass cap mkd. T27N R26E R27E 1/4 S1 S6 1990. This cor. now becomes the 1/4 sec. cor. of sec. 1 only, T. 27 N., R. 26 E. Remark the brass cap to read</p>
	<p>T 27 N R 26 E R 27 E 1/4   S 1   2003 1990</p>
	<p>From the cor. of secs. 5, 6, 7, and 8. N. 0°03' W., bet. secs. 5 and 6. Over nearly level land.</p>
4.90	Trail road, bears SE and NW.
5.51	Power line, bears E. and W.
22.20	Trail road, bears ENE and WSW.
27.90	Lone Tule Wash, 30 ft. wide, 3 ft. deep, drains SE.
40.00	Point for the 1/4 sec. cor. of secs. 5 and 6.  Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.
	<p>T 27 N R 27 E 1/4 S 6   S 5 2003</p>
	<p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.  Cor. is located 20 lks. E. of the E. bank of Lone Tule Wash, 35 ft. wide, 3 ft. deep, drains S.</p>
52.75	Trail road, bears SE and NW.
71.60	Lone Tule Wash, 30 ft. wide, 3 ft. deep, drains WSW.
73.95	The same wash, drains SSE.



**Survey of the Subdivisional Lines,  
T. 27 N., R. 27 E., Gila and Salt River Meridian, Arizona**

FEET	
74.85	The same wash, drains SW.
76.76	Barbed wire fence, 8 strand, bears ESE and WNW.
79.99	The cor. of secs. 5, 6, 31, and 32, on the N. bdy. of the Tp., hereinbefore described.
	Land, nearly level. Soil, sandy clay. Timber, scattered piñon and juniper; undergrowth, brush and native grasses.
<hr/> GENERAL DESCRIPTION <hr/>	
	The area surveyed is located around the community of Kinlichee, Arizona, within the Navajo Indian Reservation. The terrain is rolling land. The drainage is to the west, with Kinlichee Creek being the main drainage and Lone Tule Wash entering the township at the northwest part.
	The elevation varies from 6400 to 7000 feet above sea level. The soil is sandy, rocky, and gravelly clay with some sandstone outcrops along the Kinlichee Creek Canyon. The timber is primarily piñon, juniper, and Gambel oak with some scattered ponderosa pine on the southeastern portion of the township. The undergrowth are various brushes and native grasses throughout the township.
	Principal access is Arizona State Highway 264, going from east to west through the township. From this main highway, Navajo Route 39, a highway, goes to the Kinlichee Community. Apache County Roads, C457, C423, C305, and Navajo Route 203, are graded roads branching throughout from these two main highways. Most of the area are occupied by permanent residents with few pasture areas for livestock. There is no evidence of any current mining activity.
	The mean magnetic declination of 11 1/4° E. was derived from the computer program GEOMAGIX utilizing the World Magnetic Model for Epoch 2000 for the dates of survey.



## CERTIFICATE OF SURVEY

I, Leonard R. Sandoval, Cadastral Surveyor, HEREBY CERTIFY upon honor, that in pursuance of special instructions bearing date of the 6th day of May, 2003, I have surveyed the south, east and north boundaries, and the subdivisional lines, T. 27 N., R. 27 E., of the Gila and Salt River Meridian, in the State of Arizona, which are represented in the foregoing field notes as having been executed by me and under my direction. Said survey has been made in strict conformity with said special instructions, the Manual of Instructions for the Survey of the Public Lands of the United States, 1973, and in specific manner described in the foregoing field notes.

7-11-05

(Date)

Leonard R. Sandoval

(Cadastral Surveyor)

## CERTIFICATE OF APPROVAL

BUREAU OF LAND MANAGEMENT  
Phoenix, Arizona

The foregoing field notes of the survey of the south, east and north boundaries, and the subdivisional lines, T. 27 N., R. 27 E., Gila and Salt River Meridian, in the State of Arizona, executed by Leonard R. Sandoval, Cadastral Surveyor, having been critically examined and found correct, are hereby approved.

8/17/05

(Date)

Stephen K. Hansen

(Acting Chief Cadastral Surveyor of Arizona)

~~CERTIFICATE OF TRANSCRIPT~~

~~I CERTIFY That the foregoing transcript of the field notes of the above described surveys in T. 27 N., R. 27 E., Gila and Salt River Meridian, Arizona, is a true copy of the original field notes.~~

~~(Date)~~

~~(Acting Chief Cadastral Surveyor of Arizona)~~