

ORIGINAL

**UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT**

FIELD NOTES
OF THE
DEPENDENT RESURVEY OF THE NORTH BOUNDARY,
TOWNSHIP 26 NORTH, RANGE 28 EAST,
AND THE SURVEY OF
THE SEVENTH GUIDE MERIDIAN EAST (EAST BOUNDARY),
THE NORTH BOUNDARY,
THE LATITUDINAL GOVERNING SECTION LINE
AND
THE SUBDIVISIONAL LINES,
TOWNSHIP 27 NORTH, RANGE 28 EAST,
OF THE GILA AND SALT RIVER MERIDIAN,
IN THE STATE OF ARIZONA

EXECUTED BY

Leonard R. Sandoval, Cadastral Surveyor

Under Special Instructions dated and approved May 6, 2003, which provided for the surveys included under Group No. 902, and assignment instructions dated May 6, 2003.

Survey commenced October 10, 2003

Survey completed January 10, 2004

INDEX DIAGRAM

TOWNSHIP 27 NORTH RANGE 28 EAST
 GILA AND SALT RIVER MERIDIAN, ARIZONA

| | | | | | |
|-------------------|-------------------|-------------------|-------------------|-------------------|-------------------|
| 20 6 68 | 19 5 57 | 18 4 49 | 17 3 41 | 17 2 33 | 16 1 15 |
| 67 7 66 | 66 8 55 | 56 9 47 | 48 10 40 | 40 11 32 | 33 12 14 |
| 65 18 63 | 64 17 54 | 54 16 46 | 47 15 38 | 39 14 31 | 31 13 13 |
| 63 19 61 | 62 20 52 | 53 21 44 | 45 22 37 | 38 23 29 | 30 24 12 |
| 61 30 59 | 60 29 50 | 52 28 43 | 44 27 35 | 36 26 28 | 29 25 11 |
| 26 31 57 59 | 25 32 49 58 | 24 33 42 50 | 23 34 34 42 | 22 35 26 35 | 21 36 10 27 |
| 10 6 | 9 5 | 8 4 | 6 3 | 5 2 | 4 1 |

TOWNSHIP 26 NORTH RANGE 28 EAST
 GILA AND SALT RIVER MERIDIAN, ARIZONA

Tps. 26 and 27 N., R. 28 E., Gila and Salt River Meridian, Arizona

FEET

The following field notes describe the dependent resurvey of the north boundary, Township 26 North, Range 28 East, and the survey of the Seventh Guide Meridian East (east boundary), the north boundary, the latitudinal governing section line and the subdivisional lines, Township 27 North, Range 28 East, Gila and Salt River Meridian, Arizona.

Frank Follman surveyed the north boundary, Township 26 North, Range 28 East, in 1883. Jack A. Salvan dependently resurveyed the west and north boundaries, Township 26 North, Range 29 East, in 1984. Leonard R. Sandoval surveyed the south and east boundaries, Township 27 North, Range 27 East, in 2003, concurrently under this same group.

The survey was executed in accordance with the specifications as set forth in the Manual of Instructions for the Survey of the Public Lands of the United States, 1973, the Special Instructions dated May 6, 2003, for Group No. 902, Arizona.

Preliminary to the survey, the lines of the original survey were retraced and search was made for all corners and other calls of the record. Identified corners were remonumented in their original positions; lost corners were restored and monumented at proportionate positions based on the original record. The retracement data were thoroughly verified and only the true line field notes are given herein.

The true meridian direction and length of all lines were determined by real time kinematic global positioning system observations using Trimble Navigation Model 5700 receivers.

Geodetic control was derived from Global Positioning System (GPS) static observations post processed by National Geodetic Survey's, Online Positioning User Service (OPUS), utilizing Continuously Operating Reference Stations (CORS) FLAGSTAFF, AZTEC, and PIE TOWN VLBA. The NAD83(CORS96) (EPOCH:2002) geographic position of the southeast corner of the township is as follows:

Latitude: 35°41'33.82" N. Longitude: 109°17'45.49" W.

The mean magnetic declination is 11 1/2° E.

**Dependent Resurvey of the North Boundary,
T. 26 N., R. 28 E., Gila and Salt River Meridian, Arizona**

| FEET | |
|--------|---|
| | <p>Restoring the survey executed by Frank Follman, in 1883</p> <hr/> |
| | <p>Beginning at the cor. of Tps. 26 and 27 N., Rs. 28 and 29 E., monumented with a stainless post, 2 1/2 ins. diam., firmly set, projecting 4 ins. above ground with brass cap mkd. T27N R28E R29E S36 S31 S1 S6 T26N 1984.</p> |
| | <p>from which the remains of 1883 bearing trees</p> |
| | <p style="padding-left: 40px;">A ponderosa pine stump, 20 ins. diam., bears N. 65° E., 97 lks. dist., projecting 12 ins. above ground, with no visible mks.</p> |
| | <p style="padding-left: 40px;">A rotting ponderosa pine stump, 28 ins. diam., bears S. 19 3/4° W., 1.99 chs. dist., projecting 18 ins. above ground, with no visible mks.</p> |
| | <p>and from which the 1984 bearing trees</p> |
| | <p style="padding-left: 40px;">A piñon, 10 ins. diam., bears N. 42 1/2° E., 14 lks. dist., mkd. T27N R29E S31 BT on open blaze.</p> |
| | <p style="padding-left: 40px;">A piñon, 8 ins. diam., bears S. 9 1/4° E., 44 lks. dist., mkd. T26N R29E S6 BT on open blaze.</p> |
| | <p style="padding-left: 40px;">A piñon, 6 ins. diam., bears S. 29 3/4° W., 29 lks. dist., mkd. T26N R28E S1 BT on open blaze.</p> |
| | <p style="padding-left: 40px;">A ponderosa pine, 21 ins. diam., bears N. 9 1/4° W., 96 lks. dist., mkd. T27N R28E S36 BT on open blaze.</p> |
| | <p>Add the marks 2003 to the brass cap</p> |
| | <p>S. 89°56' W., on the N. bdy. of sec. 1.</p> |
| | <p>Over rolling land.</p> |
| 40.745 | <p>Point for the 1/4 sec. cor. of secs. 1 and 36, at proportionate dist.; there is no remaining evidence of the original cor.</p> |
| | <p>This cor. now functions as the 1/4 sec. cor. of sec. 1 only.</p> |
| | <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> |
| | <p>T 27 N R 28 E</p> <hr style="width: 20%; margin: auto;"/> <p>1/4 S 1</p> <p>T 26 N R 28 E</p> |
| | <p>2003</p> |

**Dependent Resurvey of the North Boundary,
T. 26 N., R. 28 E., Gila and Salt River Meridian, Arizona**

| FEET | | | | | | | | | | | |
|--------|---|--------|--------|------|--|-------|--|-----|-----|--------|--------|
| | Deposit a magnet in a white plastic case at the base of the stainless steel post. | | | | | | | | | | |
| 55.35 | Apache County Road C324, a graded road, 20 ft. wide, bears NNE and SSW. | | | | | | | | | | |
| 81.49 | The cor. of secs. 1, 2, 35 and 36, determined from the remaining original bearing tree A piñon, 18 ins. diam., bears S. 28° W., 1.52 chs. dist., mkd. T2 on partially healed blaze. This cor. now functions as the cor. of secs. 1 and 2 only. At the corner point Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd. <div style="text-align: center;"> <table style="margin: auto;"> <tr><td>T 27 N</td><td>R 28 E</td></tr> <tr><td colspan="2" style="text-align: center;">S 35</td></tr> <tr><td colspan="2" style="text-align: center;">-----</td></tr> <tr><td>S 2</td><td>S 1</td></tr> <tr><td>T 26 N</td><td>R 28 E</td></tr> </table> <p>2003</p> </div> | T 27 N | R 28 E | S 35 | | ----- | | S 2 | S 1 | T 26 N | R 28 E |
| T 27 N | R 28 E | | | | | | | | | | |
| S 35 | | | | | | | | | | | |
| ----- | | | | | | | | | | | |
| S 2 | S 1 | | | | | | | | | | |
| T 26 N | R 28 E | | | | | | | | | | |
| | Deposit a magnet in a white plastic case at the base of the stainless steel post. | | | | | | | | | | |
| | <hr/> | | | | | | | | | | |
| | S. 89°53' W., on the N. bdy. of sec. 2. Over rolling land. | | | | | | | | | | |
| 38.79 | The 1/4 sec. cor. of secs. 2 and 35, determined from the original bearing tree A piñon, 16 ins. diam., S. 15° E., 78 lks. dist., with illegible scribe mks. on open blaze. This cor. now functions as the 1/4 sec. cor. of sec. 2 only. At the corner point Set a brass tablet, 3 1/4 ins. diam., 2 1/2 ins. stem, in a drill hole, cemented in place in a sandstone outcrop, with top mkd. | | | | | | | | | | |

**Dependent Resurvey of the North Boundary,
T. 26 N., R. 28 E., Gila and Salt River Meridian, Arizona**

| FEET | |
|-------|--|
| | T 27 N R 28 E <hr style="width: 10%; margin: auto;"/> 1/4 S 2 T 26 N R 28 E 2003 |
| | Deposit a magnet in a white plastic case at the base of the brass tablet. <hr style="width: 30%; margin: auto;"/> S. 89°12' W., beginning new measurement. Over rolling and broken land. |
| 27.65 | Apache County Road C324, a graded road, 20 ft. wide, bears SSE and NNW. |
| 29.90 | Trail road, bears NE and SW. |
| 40.57 | The cor. of secs. 2, 3, 34 and 35, determined from the remaining original bearing trees A piñon, 17 ins. diam., bears N. 79 1/4° E., 18 lks. dist., with healed blaze. (Record: 20 ins., N. 12 1/2° E.) A piñon, 14 ins. diam., bears S. 54° E., 17 lks. dist., with illegible scribe mks. on open blaze. (Record: 20 ins., S. 10° E.) A piñon, 11 ins. diam., bears S. 56 1/2° W., 32 lks. dist., mkd. T26N R28E S3 BT on open blaze. (Record: 18 ins., S. 20° W.) This cor. now functions as the cor. of secs. 2 and 3 only. At the corner point Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd. |
| | T 27 N R 28 E <hr style="width: 10%; margin: auto;"/> S 34 <hr style="width: 10%; margin: auto;"/> S 3 S 2 T 26 N R 28 E 2003 |
| | Deposit a magnet in a white plastic case at the base of the stainless steel post. <hr style="width: 30%; margin: auto;"/> N. 89°40' W., on the N. bdy. of sec. 3. |

**Dependent Resurvey of the North Boundary,
T. 26 N., R. 28 E., Gila and Salt River Meridian, Arizona**

| FEET | |
|-------|--|
| | Over rolling and broken land. |
| 39.79 | The 1/4 sec. cor. of secs. 3 and 34, determined from the remains of the original bearing tree A root hole, bears N. 20° W., 55 lks. dist., with a fallen ponderosa pine, 16 ins. diam., alongside, mkd. BT on open blaze. (Record: 20 ins.) This cor. now functions as the 1/4 sec. cor. of sec. 3 only. At the corner point Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd. T 27 N R 28 E <hr style="width: 10%; margin: auto;"/> 1/4 S 3 T 26 N R 28 E 2003 Deposit a magnet in a white plastic case at the base of the stainless steel post. <hr style="width: 30%; margin: auto;"/> S. 89°48' W., beginning new measurement. Over rolling and broken land. |
| 21.00 | Trail road, bears N. and S. |
| 39.38 | The cor. of secs. 3, 4, 33 and 34, determined from the original bearing trees A piñon, 12 ins. diam., bears N. 62° E., 19 lks. dist., mkd. T27N R28E S34 BT on partially healed blaze. (Record: N. 12 1/2° E.) A piñon, 14 ins. diam., bears S. 64 1/2° W., 37 lks. dist., mkd. T26N R28E S BT on open blaze. (Record: 18 ins., S. 15° W.) At the corner point Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd. |

**Dependent Resurvey of the North Boundary,
T. 26 N., R. 28 E., Gila and Salt River Meridian, Arizona**

| FEET | |
|-------|--|
| | T 27 N R 28 E S 33 S 34 S 4 S 3 T 26 N 2003 |
| | Deposit a magnet in a white plastic case at the base of the stainless steel post. |
| | <hr/> S. 89°43' W., on the N. bdy. of sec. 4. Over rolling and broken land. |
| 39.42 | Point for the 1/4 sec. cor. of secs. 4 and 33, at proportionate dist.; there is no remaining evidence of the original cor. This cor. now functions as the 1/4 sec. cor. of sec. 4 only. Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd. |
| | T 27 N R 28 E <hr style="width: 10%; margin: auto;"/> 1/4 S 4 T 26 N R 28 E 2003 |
| | Deposit a magnet in a white plastic case at the base of the stainless steel post. |
| 64.10 | Apache County Road C324, a graded road, 20 ft. wide, bears NE and SW. |
| 69.45 | Apache County Road C324, a graded road, 20 ft. wide, bears N. and S. |
| 78.84 | The cor. of secs. 4, 5, 32 and 33, determined from the remaining original bearing tree A piñon, 16 ins. diam., bears N. 10 1/2° E., 90 lks. dist., mkd. 27N 28E S33 BTW on open blaze. This cor. now functions as the cor. of secs. 4 and 5 only. At the corner point Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd. |

**Dependent Resurvey of the North Boundary,
T. 26 N., R. 28 E., Gila and Salt River Meridian, Arizona**

| FEET | |
|-------|--|
| | T 27 N R 28 E S 33 <hr style="width: 50%; margin: auto;"/> S 5 S 4 T 26 N R 28 E 2003 |
| | Deposit a magnet in a white plastic case at the base of the stainless steel post. |
| | <hr/> N. 89°41' W., on the N. bdy. of sec. 5. Over rolling and broken land. |
| 37.90 | Burnt Piñon Wash, 26 ft. wide, 4 ft. deep, drains WNW. |
| 40.49 | Point for the 1/4 sec. cor. of secs. 5 and 32, at proportionate dist.; there is no remaining evidence of the original cor. This cor. now functions as the 1/4 sec. cor. of sec. 5 only. Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd. |
| | T 27 N R 28 E <hr style="width: 50%; margin: auto;"/> 1/4 S 5 T 26 N R 28 E 2003 |
| | Deposit a magnet in a white plastic case at the base of the stainless steel post. |
| 80.98 | Point for the cor. of secs. 5, 6, 31 and 32, at proportionate dist.; there is no remaining evidence of the original cor. This cor. now functions as the cor. of secs. 5 and 6 only. Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd. |
| | T 27 N R 28 E S 32 <hr style="width: 50%; margin: auto;"/> S 6 S 5 T 26 N R 28 E 2003 |

**Dependent Resurvey of the North Boundary,
T. 26 N., R. 28 E., Gila and Salt River Meridian, Arizona**

| FEET | |
|-------|--|
| | <p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p> <hr/> <p>N. 89°41' W., on the N. bdy. of sec. 6.</p> <p>Over rolling and broken land.</p> |
| 8.60 | Burnt Piñon Wash, 40 ft. wide, 4 ft. deep, drains SSW. |
| 27.95 | Navajo Route 203, a graded road, 25 ft. wide, bears SSE and NNW. |
| 40.49 | <p>Point for the 1/4 sec. cor. of secs. 6 and 31, at proportionate dist.; there is no remaining evidence of the original cor.</p> <p>This cor. now functions as the 1/4 sec. cor. of sec. 6 only.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T 27 N R 28 E ----- 1/4 S 6 T 26 N R 28 E</p> <p style="text-align: center;">2003</p> |
| | <p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p> |
| 79.87 | <p>The cor. of Tps. 26 and 27 N., Rs. 27 and 28 E., monumented with a stainless steel post, 2 1/2 ins. diam., with brass cap, set, mkd and witnessed as described in the field notes of survey of the S. bdy., T. 27 N., R. 27 E., executed concurrently under this same group.</p> <hr/> <p style="text-align: center;">Survey of the Seventh Guide Meridian East (East Boundary), T. 27 N., R. 28 E., Gila and Salt River Meridian, Arizona</p> <hr/> <p>From the cor. of Tps. 26 and 27 N., Rs. 28 and 29 E., hereinbefore described.</p> <p>North, bet. secs. 31 and 36.</p> <p>Over rolling land.</p> |
| 39.00 | Trail road,, bears ESE and WNW. |
| 40.00 | Point for the 1/4 sec. cor. of secs. 31 and 36. |

**Survey of the Seventh Guide Meridian East (East Boundary),
T. 27 N., R. 28 E., Gila and Salt River Meridian, Arizona**

| FEET | |
|-------|---|
| | <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T 27 N R 28 E R 29 E 1/4 S 36 S 31</p> <p style="text-align: center;">2003</p> <p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p> |
| 48.39 | S. right-of-way fence of Arizona State Highway 264, barbed wire, 5 strands, parallels highway. |
| 50.00 | Arizona State Highway 264, asphalt pavement, 30 ft. wide, bears ESE and WNW. |
| 51.60 | N. right-of-way fence of Arizona State Highway 264, barbed wire, 5 strands, parallels highway. |
| 74.45 | S. rim of Kinlichee Creek canyon, a sandstone ledge, bears SE and NW, thence descend into the canyon. |
| 80.00 | <p>Point for the cor. of secs. 25, 30, 31 and 36.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T 27 N R 28 E R 29 E S 25 S 30 ----- S 36 S 31</p> <p style="text-align: center;">2003</p> <p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p> <p>Land, rolling to rugged and broken. Soil, sandy and rocky clay with sandstone outcrops. Timber, ponderosa pine, piñon, juniper and Gambel's oak; undergrowth, brush and native grasses.</p> <hr/> <p>North, bet. secs. 25 and 30.</p> <p>Over nearly level land, across the canyon floor.</p> |
| 10.80 | Kinlichee Creek, a wash, 60 ft. wide, 2 ft. deep, drains W., thence ascend out of the canyon. |

**Survey of the Seventh Guide Meridian East (East Boundary),
T. 27 N., R. 28 E., Gila and Salt River Meridian, Arizona**

| FEET | |
|-------|--|
| 12.35 | N. rim of Kinlichee Creek canyon, a sandstone cliff, 120 ft. high, bears ENE and WNW, thence over rolling and broken land. |
| 16.45 | Trail road, bears E. and W. |
| 40.00 | <p>Point for the 1/4 sec. cor. of secs. 25 and 30.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center;"> <p>T 27 N R 28 E R 29 E 1/4 S 25 S 30</p> <p>2003</p> </div> <p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p> |
| 80.00 | <p>Point for the cor. of secs. 19, 24, 25 and 30.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center;"> <p>T 27 N R 28 E R 29 E S 24 S 19 S 25 S 30</p> <p>2003</p> </div> <p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p> <p>Land, rugged and broken to rolling. Soil, sandy and rocky clay with sandstone outcrops. Timber, ponderosa pine, piñon, juniper and Gambel's oak; undergrowth, brush and native grasses.</p> <hr/> <p>North, bet. secs. 19 and 24.</p> <p>Over rolling land.</p> |
| 40.00 | <p>Point for the 1/4 sec. cor. of secs. 19 and 24.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> |

**Survey of the Seventh Guide Meridian East (East Boundary),
T. 27 N., R. 28 E., Gila and Salt River Meridian, Arizona**

| FEET | |
|-------|--|
| | <p align="center">T 27 N R 28 E R 29 E 1/4 S 24 S 19</p> <p align="center">2003</p> |
| 50.70 | <p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p> <p>Trail road, bears E. and W.</p> |
| 80.00 | <p>Point for the cor. of secs. 13, 18, 19 and 24.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> |
| | <p align="center">T 27 N R 28 E R 29 E S 13 S 18 ----- S 24 S 19</p> <p align="center">2003</p> <p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p> <p>Land, rolling. Soil, sandy and rocky clay with sandstone outcrops. Timber, ponderosa pine, piñon, juniper and Gambel's oak; undergrowth, brush and native grasses.</p> <hr/> <p>North, bet. secs. 13 and 18.</p> <p>Over rolling land.</p> |
| 40.00 | <p>Point for the 1/4 sec. cor. of secs. 13 and 18.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., flush with surface of the ground, with brass cap mkd.</p> |
| | <p align="center">T 27 N R 28 E R 29 E 1/4 S 13 S 18</p> <p align="center">2003</p> <p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p> <p>Cor. is located 5 lks. S. of a trail road, bears E. and W.</p> |

**Survey of the Seventh Guide Meridian East (East Boundary),
T. 27 N., R. 28 E., Gila and Salt River Meridian, Arizona**

| FEET | | | | | | | | | |
|--------|--|--------|--|--------|--------|------|-----|------|------|
| 80.00 | <p>Point for the cor. of secs. 7, 12, 13 and 18.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <table border="1" data-bbox="808 451 1047 583"> <tr><td colspan="2" style="text-align:center">T 27 N</td></tr> <tr><td style="text-align:center">R 28 E</td><td style="text-align:center">R 29 E</td></tr> <tr><td style="text-align:center">S 12</td><td style="text-align:center">S 7</td></tr> <tr><td style="text-align:center">S 13</td><td style="text-align:center">S 18</td></tr> </table> <p style="text-align:center">2003</p> <p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p> <p>Land, rolling. Soil, sandy and rocky clay with sandstone outcrops. Timber, ponderosa pine, piñon, juniper and Gambel's oak; undergrowth, brush and native grasses.</p> | T 27 N | | R 28 E | R 29 E | S 12 | S 7 | S 13 | S 18 |
| T 27 N | | | | | | | | | |
| R 28 E | R 29 E | | | | | | | | |
| S 12 | S 7 | | | | | | | | |
| S 13 | S 18 | | | | | | | | |
| | <p>North, bet. secs. 7 and 12.</p> | | | | | | | | |
| | <p>Over rolling and broken land.</p> | | | | | | | | |
| 40.00 | <p>Point for the 1/4 sec. cor. of secs. 7 and 12.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <table border="1" data-bbox="797 1213 1055 1333"> <tr><td colspan="2" style="text-align:center">T 27 N</td></tr> <tr><td style="text-align:center">R 28 E</td><td style="text-align:center">R 29 E</td></tr> <tr><td colspan="2" style="text-align:center">1/4</td></tr> <tr><td style="text-align:center">S 12</td><td style="text-align:center">S 7</td></tr> </table> <p style="text-align:center">2003</p> <p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p> | T 27 N | | R 28 E | R 29 E | 1/4 | | S 12 | S 7 |
| T 27 N | | | | | | | | | |
| R 28 E | R 29 E | | | | | | | | |
| 1/4 | | | | | | | | | |
| S 12 | S 7 | | | | | | | | |
| 62.80 | <p>S. rim of Scattered Willow Wash canyon, a sandstone ledge, bears ESE and WNW.</p> | | | | | | | | |
| 76.50 | <p>N. rim of Scattered Willow Wash canyon, a sandstone ledge, bears ENE and WSW.</p> | | | | | | | | |
| 80.00 | <p>Point for the cor. of secs. 1, 6, 7 and 12.</p> <p>Set a brass tablet, 3 1/4 ins. diam., 2 1/2 ins. stem, in a drill hole, in sandstone bedrock atop a sandstone ledge, bears SE and NW, with top mkd.</p> | | | | | | | | |

Survey of the Seventh Guide Meridian East (East Boundary),
T. 27 N., R. 28 E., Gila and Salt River Meridian, Arizona

| | | | | | | | | | | | |
|--------|--|--------|--|--------|--------|------|------|------|-----|--------|--|
| FEET | <table style="margin: auto; border-collapse: collapse;"> <tr><td colspan="2">T 27 N</td></tr> <tr><td style="border-right: 1px solid black; padding: 0 5px;">R 28 E</td><td style="padding: 0 5px;">R 29 E</td></tr> <tr><td style="border-right: 1px solid black; padding: 0 5px;">S 1</td><td style="padding: 0 5px;">S 6</td></tr> <tr style="border-top: 1px solid black;"><td style="border-right: 1px solid black; padding: 0 5px;">S 12</td><td style="padding: 0 5px;">S 7</td></tr> </table> <p style="text-align: center; margin-top: 10px;">2003</p> <p>Deposit a magnet in a white plastic case at the base of the brass tablet.</p> <p>Land, rolling and broken. Soil, sandy and rocky clay with sandstone outcrops. Timber, ponderosa pine, piñon, juniper and Gambel's oak; undergrowth, brush and native grasses.</p> <hr style="width: 80%; margin: 20px auto;"/> <p>North, bet. secs. 1 and 6.</p> <p>Over rugged and broken land.</p> <p>40.00 Point for the 1/4 sec. cor. of secs. 1 and 6.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 19 ins. in the ground, in a mound of stone, 3 ft. base, to top, with brass cap mkd.</p> | T 27 N | | R 28 E | R 29 E | S 1 | S 6 | S 12 | S 7 | | |
| T 27 N | | | | | | | | | | | |
| R 28 E | R 29 E | | | | | | | | | | |
| S 1 | S 6 | | | | | | | | | | |
| S 12 | S 7 | | | | | | | | | | |
| 80.00 | <table style="margin: auto; border-collapse: collapse;"> <tr><td colspan="2">T 27 N</td></tr> <tr><td style="border-right: 1px solid black; padding: 0 5px;">R 28 E</td><td style="padding: 0 5px;">R 29 E</td></tr> <tr><td colspan="2" style="text-align: center; padding: 0 5px;">1/4</td></tr> <tr><td style="border-right: 1px solid black; padding: 0 5px;">S 1</td><td style="padding: 0 5px;">S 6</td></tr> </table> <p style="text-align: center; margin-top: 10px;">2003</p> <p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p> <p>Point for the cor. of Tps. 27 and 28 N., Rs. 28 and 29 E.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> | T 27 N | | R 28 E | R 29 E | 1/4 | | S 1 | S 6 | | |
| T 27 N | | | | | | | | | | | |
| R 28 E | R 29 E | | | | | | | | | | |
| 1/4 | | | | | | | | | | | |
| S 1 | S 6 | | | | | | | | | | |
| | <table style="margin: auto; border-collapse: collapse;"> <tr><td colspan="2">T 28 N</td></tr> <tr><td style="border-right: 1px solid black; padding: 0 5px;">R 28 E</td><td style="padding: 0 5px;">R 29 E</td></tr> <tr><td style="border-right: 1px solid black; padding: 0 5px;">S 36</td><td style="padding: 0 5px;">S 31</td></tr> <tr style="border-top: 1px solid black;"><td style="border-right: 1px solid black; padding: 0 5px;">S 1</td><td style="padding: 0 5px;">S 6</td></tr> <tr><td colspan="2">T 27 N</td></tr> </table> <p style="text-align: center; margin-top: 10px;">2003</p> <p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p> | T 28 N | | R 28 E | R 29 E | S 36 | S 31 | S 1 | S 6 | T 27 N | |
| T 28 N | | | | | | | | | | | |
| R 28 E | R 29 E | | | | | | | | | | |
| S 36 | S 31 | | | | | | | | | | |
| S 1 | S 6 | | | | | | | | | | |
| T 27 N | | | | | | | | | | | |

**Survey of the Seventh Guide Meridian East (East Boundary),
T. 27 N., R. 28 E., Gila and Salt River Meridian, Arizona**

| FEET | |
|-------|---|
| | <p>Land, rolling and broken. Soil, sandy and rocky clay with sandstone outcrops. Timber, ponderosa pine, piñon, juniper and Gambel's oak; undergrowth, brush and native grasses.</p> <hr/> <p align="center">Survey of the North Boundary, T. 27 N., R. 28 E., Gila and Salt River Meridian, Arizona</p> <hr/> <p>From the cor. of Tps. 27 and 28 N., Rs. 28 and 29 E., hereinbefore described.</p> <p>S. 89°59' W., bet. secs. 1 and 36.</p> <p>Over rolling land.</p> |
| 40.00 | <p>Point for the 1/4 sec. cor. of secs. 1 and 36.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p align="center">T 28 N R 28 E S 36 1/4 ——— S 1 T 27 N</p> <p align="center">2003</p> |
| 51.95 | <p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p> <p>Trail road, bears ENE and WSW.</p> |
| 80.00 | <p>Point for the cor. of secs. 1, 2, 35 and 36.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p align="center">T 28 N R 28 E S 35 S 36 S 2 S 1 T 27 N</p> <p align="center">2003</p> <p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p> |

**Survey of the North Boundary,
T. 27 N., R. 28 E., Gila and Salt River Meridian, Arizona**

| FEET | |
|-------|--|
| | <p>Land, rolling. Soil, sandy and rocky clay. Timber, ponderosa pine, piñon, juniper and Gambel's oak; undergrowth, brush and native grasses.</p> <hr/> <p>S. 89°59' W., bet. secs. 2 and 35.</p> <p>Over rolling and broken land.</p> |
| 40.00 | <p>Point for the 1/4 sec. cor. of secs. 2 and 35.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center; margin: 10px 0;"> <p>T 28 N R 28 E S 35 1/4 ——— S 2 T 27 N</p> <p>2003</p> </div> <p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p> |
| 43.50 | <p>Black Soil Wash, 10 ft. wide, 2 ft. deep, drains SW.</p> |
| 80.00 | <p>Point for the cor. of secs. 2, 3, 34 and 35.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center; margin: 10px 0;"> <p>T 28 N R 28 E S 34 S 35 S 3 S 2 T 27 N</p> <p>2003</p> </div> <p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p> <p>Land, rolling. Soil, sandy and rocky clay. Timber, ponderosa pine, piñon, juniper and Gambel's oak; undergrowth, brush and native grasses.</p> <hr/> <p>S. 89°59' W., bet. secs. 3 and 34.</p> <p>Over rolling and broken land.</p> |

**Survey of the North Boundary,
T. 27 N., R. 28 E., Gila and Salt River Meridian, Arizona**

| FEET | | | | | |
|-------|---|------|------|-----|-----|
| 14.80 | Navajo Route 203, a graded road, 20 ft. wide, bears NE and SW. | | | | |
| 40.00 | <p>Point for the 1/4 sec. cor. of secs. 3 and 34.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center; margin: 10px 0;"> <p>T 28 N R 28 E</p> <p style="margin-left: 100px;">S 34</p> <p style="margin-left: 100px;">1/4 ———</p> <p style="margin-left: 100px;">S 3</p> <p>T 27 N</p> <p style="margin-top: 10px;">2003</p> </div> <p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p> | | | | |
| 80.00 | <p>Point for the cor. of secs. 3, 4, 33 and 34.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center; margin: 10px 0;"> <p>T 28 N R 28 E</p> <table style="margin-left: auto; margin-right: auto; border-collapse: collapse;"> <tr> <td style="border-right: 1px solid black; padding: 0 5px;">S 33</td> <td style="padding: 0 5px;">S 34</td> </tr> <tr> <td style="border-right: 1px solid black; padding: 0 5px;">S 4</td> <td style="padding: 0 5px;">S 3</td> </tr> </table> <p>T 27 N</p> <p style="margin-top: 10px;">2003</p> </div> <p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p> <p>Land, rolling. Soil, sandy and rocky clay. Timber, ponderosa pine, piñon, juniper and Gambel's oak; undergrowth, brush and native grasses.</p> <hr style="width: 80%; margin: 10px auto;"/> <p>S. 89°59' W., bet. secs. 4 and 33.</p> <p>Over rolling and broken land.</p> | S 33 | S 34 | S 4 | S 3 |
| S 33 | S 34 | | | | |
| S 4 | S 3 | | | | |
| 40.00 | <p>Point for the 1/4 sec. cor. of secs. 4 and 33.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> | | | | |

**Survey of the North Boundary,
T. 27 N., R. 28 E., Gila and Salt River Meridian, Arizona**

| FEET | |
|-------|--|
| | T 28 N R 28 E S 33 1/4 ——— S 4 T 27 N 2003 |
| | Deposit a magnet in a white plastic case at the base of the stainless steel post. |
| 48.40 | E. rim of Ruin Wash canyon, a sandstone cliff, 100 ft. high, bears NE and SW. |
| 54.75 | Ruin Wash, 20 ft. wide, 10 ft. deep, drains SW. |
| 59.70 | W. rim of Ruin Wash canyon, a sandstone cliff, 40 ft. high, bears NNE and SSW. |
| 80.00 | Point for the cor. of secs. 4, 5, 32 and 33. Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd. |
| | T 28 N R 28 E S 32 S 33 ——— ——— S 5 S 4 T 27 N 2003 |
| | Deposit a magnet in a white plastic case at the base of the stainless steel post. |
| | Land, rolling and broken. Soil, sandy and rocky clay. Timber, ponderosa pine, piñon, juniper and Gambel's oak; undergrowth, brush and native grasses. |
| | ————— S. 89°59' W., bet. secs. 5 and 32. |
| | Over rolling land. |
| 40.00 | Point for the 1/4 sec. cor. of secs. 5 and 32. Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd. |

Survey of the North Boundary,
T. 27 N., R. 28 E., Gila and Salt River Meridian, Arizona

| FEET | |
|-------|---|
| | T 28 N R 28 E S 32 1/4 ——— S 5 T 27 N 2003 |
| | Deposit a magnet in a white plastic case at the base of the stainless steel post. |
| 48.60 | Apache County Road C423, a graded road, 20 ft. wide, bears NE and SW. |
| 80.00 | Point for the cor. of secs. 5, 6, 31 and 32. |
| | Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd. |
| | T 28 N R 28 E S 31 S 32 ——— ——— S 6 S 5 T 27 N 2003 |
| | Deposit a magnet in a white plastic case at the base of the stainless steel post. |
| | Land, rolling. Soil, sandy and rocky clay. Timber, ponderosa pine, piñon, juniper and Gambel's oak; undergrowth, brush and native grasses. |
| | _____ |
| | S. 89°59' W., bet. secs. 6 and 31. |
| | Over rolling and broken land. |
| 13.47 | High voltage transmission line, bears NE and SW. |
| 15.95 | High voltage transmission line, bears NE and SW. |
| 40.00 | Point for the 1/4 sec. cor. of secs. 6 and 31. |
| | Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd. |

**Survey of the North Boundary,
T. 27 N., R. 28 E., Gila and Salt River Meridian, Arizona**

| FEET | |
|-------|--|
| | T 28 N R 28 E S 31 1/4 ——— S 6 T 27 N 2003 |
| | Deposit a magnet in a white plastic case at the base of the stainless steel post. |
| 41.20 | Wash, 12 ft. wide, 4 ft. deep, drains NW. |
| 79.20 | <p>The cor. of Tps. 27 and 28 N., Rs. 27 and 28 E., monumented with a stainless steel post, 2 1/2 ins. diam., with brass cap, set and mkd., as described in the field notes of the survey of the E. bdy., T. 27 N., R. 27 E., executed concurrently under this same group.</p> <p>Cor. is located 25 lks. S. and 85 lks. E. of a trail road, bears ENE and WSW.</p> <p>Land, rolling and broken. Soil, sandy and rocky clay. Timber, ponderosa pine, piñon, juniper and Gambel's oak; undergrowth, brush and native grasses.</p> <hr/> <p style="text-align: center;">Survey of the Latitudinal Governing Section Line, T. 27 N., R. 28 E., Gila and Salt River Meridian, Arizona</p> <hr/> <p>NOTE: The results of the dependent resurvey of the N. bdy., T. 26 N., R. 28 E., exceed the specified rectangular limits for alinement to control the subdivision of this township. This necessitates the need for the establishment of a latitudinal governing section line.</p> <p>From the cor. of secs. 25, 30, 31 and 36, on the E. bdy. of the Tp., hereinbefore described.</p> <p>S. 89°59' W., bet. secs. 25 and 36.</p> <p>Over rugged and broken land, ascend out of Kinlichee Creek canyon.</p> |
| 1.90 | S. rim of Kinlichee Creek canyon, a sandstone ledge, bears N. and S., thence over rolling land. |
| 40.00 | <p>Point for the 1/4 sec. cor. of secs. 25 and 36.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> |

Survey of the Latitudinal Governing Section Line,
T. 27 N., R. 28 E., Gila and Salt River Meridian, Arizona

| | |
|-------|--|
| FEET | <p style="text-align: center;">T 27 N R 28 E S 25 1/4 ——— S 36</p> <p style="text-align: center;">2003</p> <p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p> |
| 80.00 | <p>Point for the cor. of secs. 25, 26, 35 and 36.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T 27 N R 28 E S 26 S 25 ——— ——— S 35 S 36</p> <p style="text-align: center;">2003</p> <p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p> <p>Cor. is located 26 lks. N. and 65 lks. E. of the N. right-of-way fence of Arizona State Highway 264, barbed wire, 5 strands, bears ESE and WNW.</p> <p>Land, rolling, rugged and broken. Soil, sandy and rocky clay with sandstone outcrops. Timber, ponderosa pine, piñon, juniper and Gambel's oak; undergrowth, brush and native grasses.</p> <hr/> <p>S. 89°59' W., bet. secs. 26 and 35.</p> <p>Over rolling land.</p> |
| 4.67 | <p>Arizona State Highway 264, asphalt pavement, 28 ft. wide, bears ESE and WNW.</p> |
| 8.89 | <p>S. right-of-way fence of Arizona State Highway 264, barbed wire, 5 strands, parallels highway.</p> |
| 40.00 | <p>Point for the 1/4 sec. cor. of secs. 25 and 36.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> |

Survey of the Latitudinal Governing Section Line,
T. 27 N., R. 28 E., Gila and Salt River Meridian, Arizona

| FEET | |
|-------|---|
| | T 27 N R 28 E S 26 1/4 ——— S 35 2003 |
| | Deposit a magnet in a white plastic case at the base of the stainless steel post. |
| 80.00 | Point for the cor. of secs. 26, 27, 34 and 35. Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd. |
| | T 27 N R 28 E S 27 S 26 ——— ——— S 34 S 35 2003 |
| | Deposit a magnet in a white plastic case at the base of the stainless steel post. |
| | Land, rolling. Soil, sandy and rocky clay. Timber, ponderosa pine, piñon, juniper and Gambel's oak; undergrowth, brush and native grasses. |
| | _____ |
| | S. 89°59' W., bet. secs. 27 and 34. |
| | Over rolling land. |
| 40.00 | Point for the 1/4 sec. cor. of secs. 27 and 34. Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd. |
| | T 27 N R 28 E S 27 1/4 ——— S 34 2003 |
| | Deposit a magnet in a white plastic case at the base of the stainless steel post. |
| 80.00 | Point for the cor. of secs. 27, 28, 33 and 34. Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd. |

Survey of the Latitudinal Governing Section Line,
T. 27 N., R. 28 E., Gila and Salt River Meridian, Arizona

| FEET | | | | | | | | | |
|--------|---|--------|--------|------|------|------|------|--|------|
| | <table style="margin-left: auto; margin-right: auto;"> <tr> <td>T 27 N</td> <td>R 28 E</td> </tr> <tr> <td>S 28</td> <td>S 27</td> </tr> <tr> <td>S 33</td> <td>S 34</td> </tr> </table> | T 27 N | R 28 E | S 28 | S 27 | S 33 | S 34 | | |
| T 27 N | R 28 E | | | | | | | | |
| S 28 | S 27 | | | | | | | | |
| S 33 | S 34 | | | | | | | | |
| | 2003 | | | | | | | | |
| | Deposit a magnet in a white plastic case at the base of the stainless steel post. | | | | | | | | |
| | Land, rolling. Soil, sandy and rocky clay. Timber, ponderosa pine, piñon, juniper and Gambel's oak; undergrowth, brush and native grasses. | | | | | | | | |
| | S. 89°59' W., bet. secs. 28 and 33. | | | | | | | | |
| | Over rolling land. | | | | | | | | |
| 20.55 | Apache County Road C324, a graded road, 20 ft. wide, bears N. and S. | | | | | | | | |
| 40.00 | Point for the 1/4 sec. cor. of secs. 28 and 33. Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd. | | | | | | | | |
| | <table style="margin-left: auto; margin-right: auto;"> <tr> <td>T 27 N</td> <td>R 28 E</td> </tr> <tr> <td></td> <td>S 28</td> </tr> <tr> <td>1/4</td> <td>—</td> </tr> <tr> <td></td> <td>S 33</td> </tr> </table> | T 27 N | R 28 E | | S 28 | 1/4 | — | | S 33 |
| T 27 N | R 28 E | | | | | | | | |
| | S 28 | | | | | | | | |
| 1/4 | — | | | | | | | | |
| | S 33 | | | | | | | | |
| | 2003 | | | | | | | | |
| | Deposit a magnet in a white plastic case at the base of the stainless steel post. | | | | | | | | |
| 80.00 | Point for the cor. of secs. 28, 29, 32 and 33. Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd. | | | | | | | | |
| | <table style="margin-left: auto; margin-right: auto;"> <tr> <td>T 27 N</td> <td>R 28 E</td> </tr> <tr> <td>S 29</td> <td>S 28</td> </tr> <tr> <td>S 32</td> <td>S 33</td> </tr> </table> | T 27 N | R 28 E | S 29 | S 28 | S 32 | S 33 | | |
| T 27 N | R 28 E | | | | | | | | |
| S 29 | S 28 | | | | | | | | |
| S 32 | S 33 | | | | | | | | |
| | 2003 | | | | | | | | |
| | Deposit a magnet in a white plastic case at the base of the stainless steel post. | | | | | | | | |

**Survey of the Latitudinal Governing Section Line,
T. 27 N., R. 28 E., Gila and Salt River Meridian, Arizona**

| FEET | |
|-------|--|
| | <p>Land, rolling. Soil, sandy. Timber, scattered ponderosa pine, piñon, juniper and Gambel's oak; undergrowth, brush and native grasses.</p> <hr/> <p>S. 89°59' W., bet. secs. 29 and 32.</p> <p>Over rolling land.</p> |
| 35.10 | Apache County Road C324, a graded road, 20 ft. wide, bears SE and NW. |
| 40.00 | <p>Point for the 1/4 sec. cor. of secs. 29 and 32.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p align="center"> T 27 N R 28 E S 29 1/4 ——— S 32 2003 </p> <p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p> |
| 41.50 | Trail road, bears NNE and SSW. |
| 80.00 | <p>Point for the cor. of secs. 29, 30, 31 and 32.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p align="center"> T 27 N R 28 E S 30 S 29 S 31 S 32 2003 </p> <p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p> <p>From this cor. point, third order U. S. Geological Survey triangulation station, "CHOYOJ DO LID", bears N. 76°09' W., 10.405 chs. dist., monumented with a standard brass tablet, 3 3/4 ins. diam., firmly set, cemented in a sandstone outcrop, 12 x 6 ins., projecting 3 ins. above ground, with top mkd. CHOYOJ DO LID 1955 and a triangle.</p> |

**Survey of the Latitudinal Governing Section Line,
T. 27 N., R. 28 E., Gila and Salt River Meridian, Arizona**

| FEET | |
|-------|---|
| | <p>Land, rolling. Soil, sandy clay. Timber, scattered ponderosa pine, piñon, juniper and Gambel's oak; undergrowth, brush and native grasses.</p> <hr/> <p>S. 89°59' W., bet. secs. 30 and 31.</p> <p>Over rolling land.</p> |
| 40.00 | <p>Point for the 1/4 sec. cor. of secs. 30 and 31.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T 27 N R 28 E S 30 1/4 ——— S 31</p> <p style="text-align: center;">2003</p> <p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p> |
| 58.55 | <p>Navajo Route 203, a graded road, 20 ft. wide, bears SSE and NNW.</p> |
| 79.63 | <p>The cor. of secs. 25, 30, 31 and 36, on the W. bdy. of the Tp., monumented with a stainless steel post, 2 1/2 ins. diam., with brass cap, set and mkd., as described in the field notes of the survey of the E. bdy., T. 27 N., R. 27 E., executed concurrently under this same group.</p> <p>Land, rolling. Soil, sandy clay. Timber, scattered ponderosa pine, piñon, juniper and Gambel's oak; undergrowth, brush and native grasses.</p> <hr/> <p style="text-align: center;">Survey of the Subdivisional Lines, T. 27 N., R. 28 E., Gila and Salt River Meridian, Arizona</p> <hr/> <p>From the cor. of secs. 25, 26, 35 and 36, on the latitudinal governing section line, hereinbefore described.</p> <p>S. 0°01' E., bet. secs. 35 and 36.</p> <p>Over rolling land.</p> |
| 1.88 | <p>Arizona State Highway 264, asphalt pavement, 28 ft. wide, bears ESE and WNW.</p> |

**Survey of the Subdivisional Lines,
T. 27 N., R. 28 E., Gila and Salt River Meridian, Arizona**

| FEET | |
|-------|---|
| 3.89 | S. right-of-way fence of Arizona State Highway 264, barbed wire, 5 strands, parallels highway. |
| 40.00 | <p>Point for the 1/4 sec. cor. of secs. 35 and 36.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T 27 N R 28 E 1/4 S 35 S 36</p> <p style="text-align: center;">2003</p> <p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p> |
| 80.07 | <p>Point for the closing cor. of secs. 35 and 36, at intersection with the N. bdy. of T. 26 N., R. 28 E.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T 27 N R 28 E CC S 35 S 36</p> <p style="text-align: center;">S 1 T 26 N R 28 E</p> <p style="text-align: center;">2003</p> <p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p> <p>From this cor. point, the cor. of secs. 1 and 2 only, T. 26 N., R. 28 E., bears S. 89°56' W., 1.49 chs. dist., hereinbefore described.</p> <p>Land, rolling. Soil, sandy clay. Timber, ponderosa pine, piñon, juniper and Gambel's oak; undergrowth, brush and native grasses.</p> <hr/> <p>Point for the 1/4 sec. cor. of sec. 36 only, T. 27 N., R. 28 E., at midpoint on the S. bdy. of sec. 36.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> |

**Survey of the Subdivisional Lines,
T. 27 N., R. 28 E., Gila and Salt River Meridian, Arizona**

| FEET | |
|-------|---|
| | T 27 N R 28 E 1/4 S 36 <hr style="width: 10%; margin: auto;"/> T 26 N R 28 E 2003 |
| | Deposit a magnet in a white plastic case at the base of the stainless steel post. From this cor. point, the 1/4 sec. cor. of sec. 1 only, T. 26 N., R. 28 E., bears S. 89°56' W., 74.5 lks. dist., hereinbefore described. |
| | <hr/> From the cor. of secs. 25, 26, 35 and 36, on the latitudinal governing section line, hereinbefore described. N. 0°01' W., bet. secs. 25 and 26. Over rolling and broken land. |
| 28.50 | S. rim of Kinlichee Creek canyon, a sandstone ledge, bears NE and SW, thence across the canyon. |
| 31.90 | Kinlichee Creek, a wash, 35 ft. wide, 40 ft. deep, drains NW, thence ascend out of the canyon. |
| 40.00 | Point for the 1/4 sec. cor. of secs. 25 and 26. Set a brass tablet, 3 1/4 ins. diam., 2 1/2 ins. stem, in a drill hole, cemented in place in a sandstone boulder, 7 x 7 x 1 ft., with top mkd. |
| | T 27 N R 28 E 1/4 S 26 S 25 2003 |
| | Deposit a magnet in a white plastic case at the base of the brass tablet. Cor. is located 8 lks. N. of the N. rim of the Kinlichee Creek canyon, a sandstone ledge, bears SE and NW. |
| 80.00 | Point for the cor. of secs. 23, 24, 25 and 26. Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd. |

**Survey of the Subdivisional Lines,
T. 27 N., R. 28 E., Gila and Salt River Meridian, Arizona**

| FEET | | | | | | | | | |
|--------|---|--------|--------|------|------|------|-------|--|------|
| | <table border="1"> <tr> <td>T 27 N</td> <td>R 28 E</td> </tr> <tr> <td>S 23</td> <td>S 24</td> </tr> <tr> <td>S 26</td> <td>S 25</td> </tr> </table> | T 27 N | R 28 E | S 23 | S 24 | S 26 | S 25 | | |
| T 27 N | R 28 E | | | | | | | | |
| S 23 | S 24 | | | | | | | | |
| S 26 | S 25 | | | | | | | | |
| | 2003 | | | | | | | | |
| | Deposit a magnet in a white plastic case at the base of the stainless steel post. | | | | | | | | |
| | Land, rolling and broken. Soil, sandy and rocky clay with sandstone outcrops. Timber, ponderosa pine, piñon, juniper and Gambel's oak; undergrowth, brush and native grasses. | | | | | | | | |
| | <hr/> | | | | | | | | |
| | From the cor. of secs. 19, 24, 25 and 30, on the E. bdy. of the Tp., hereinbefore described. | | | | | | | | |
| | S. 89°59' W., bet. secs. 24 and 25. | | | | | | | | |
| | Over rolling land. | | | | | | | | |
| 40.00 | Point for the 1/4 sec. cor. of secs. 24 and 25. | | | | | | | | |
| | Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd. | | | | | | | | |
| | <table border="1"> <tr> <td>T 27 N</td> <td>R 28 E</td> </tr> <tr> <td></td> <td>S 24</td> </tr> <tr> <td>1/4</td> <td>_____</td> </tr> <tr> <td></td> <td>S 25</td> </tr> </table> | T 27 N | R 28 E | | S 24 | 1/4 | _____ | | S 25 |
| T 27 N | R 28 E | | | | | | | | |
| | S 24 | | | | | | | | |
| 1/4 | _____ | | | | | | | | |
| | S 25 | | | | | | | | |
| | 2003 | | | | | | | | |
| | Deposit a magnet in a white plastic case at the base of the stainless steel post. | | | | | | | | |
| 80.00 | The cor. of secs. 23, 24, 25 and 26. | | | | | | | | |
| | Land, rolling. Soil, sandy and rocky clay with sandstone outcrops. Timber, ponderosa pine, piñon, juniper and Gambel's oak; undergrowth, brush and native grasses. | | | | | | | | |
| | <hr/> | | | | | | | | |
| | N. 0°01' W., bet. secs. 23 and 24. | | | | | | | | |
| | Over rolling land. | | | | | | | | |
| 40.00 | Point for the 1/4 sec. cor. of secs. 23 and 24. | | | | | | | | |
| | Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd. | | | | | | | | |

**Survey of the Subdivisional Lines,
T. 27 N., R. 28 E., Gila and Salt River Meridian, Arizona**

| FEET | |
|-------|---|
| | T 27 N R 28 E 1/4 S 23 S 24 2003 |
| 80.00 | Deposit a magnet in a white plastic case at the base of the stainless steel post. Point for the cor. of secs. 13, 14, 23 and 24. Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd. |
| | T 27 N R 28 E S 14 S 13 S 23 S 24 2003 |
| | Deposit a magnet in a white plastic case at the base of the stainless steel post. Land, rolling. Soil, sandy and rocky clay with sandstone outcrops. Timber, ponderosa pine, piñon, juniper and Gambel's oak; undergrowth, brush and native grasses. |
| | <hr/> From the cor. of secs. 13, 18, 19 and 24, on the E. bdy. of the Tp., hereinbefore described. S. 89°59' W., bet. secs. 13 and 24. Over rolling land. |
| 40.00 | Point for the 1/4 sec. cor. of secs. 13 and 24. Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd. |
| | T 27 N R 28 E S 13 1/4 ——— S 24 2003 |
| 80.00 | Deposit a magnet in a white plastic case at the base of the stainless steel post. The cor. of secs. 13, 14, 23 and 24. |

**Survey of the Subdivisional Lines,
T. 27 N., R. 28 E., Gila and Salt River Meridian, Arizona**

| FEET | |
|-------|---|
| | <p>Land, rolling. Soil, sandy and rocky clay with sandstone outcrops. Timber, ponderosa pine, piñon, juniper and Gambel's oak; undergrowth, brush and native grasses.</p> <hr/> <p>N. 0°01' W., bet. secs. 13 and 14.</p> <p>Over rolling land.</p> |
| 40.00 | <p>Point for the 1/4 sec. cor. of secs. 13 and 14.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T 27 N R 28 E 1/4 S 14 S 13</p> <p style="text-align: center;">2003</p> <p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p> |
| 80.00 | <p>Point for the cor. of secs. 11, 12, 13 and 14.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T 27 N R 28 E S 11 S 12 S 14 S 13</p> <p style="text-align: center;">2003</p> <p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p> <p>Land, rolling. Soil, sandy and rocky clay with sandstone outcrops. Timber, ponderosa pine, piñon, juniper and Gambel's oak; undergrowth, brush and native grasses.</p> <hr/> <p>From the cor. of secs. 7, 12, 13 and 18, on the E. bdy. of the Tp., hereinbefore described.</p> <p>S. 89°59' W., bet. secs. 12 and 13.</p> <p>Over rolling land.</p> |
| 40.00 | <p>Point for the 1/4 sec. cor. of secs. 12 and 13.</p> |

**Survey of the Subdivisional Lines,
T. 27 N., R. 28 E., Gila and Salt River Meridian, Arizona**

| FEET | |
|-------|---|
| | <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T 27 N R 28 E S 12 1/4 ——— S 13</p> <p style="text-align: center;">2003</p> <p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p> |
| 80.00 | <p>The cor. of secs. 11, 12, 13 and 14.</p> <p>Land, rolling. Soil, sandy and rocky clay with sandstone outcrops. Timber, ponderosa pine, piñon, juniper and Gambel's oak; undergrowth, brush and native grasses.</p> <hr/> <p>N. 0°01' W., bet. secs. 11 and 12.</p> <p>Over rolling and broken land.</p> |
| 38.70 | <p>N. rim of Scattered Willow Wash canyon, a sandstone ledge, bears ENE and WSW.</p> |
| 40.00 | <p>Point for the 1/4 sec. cor. of secs. 11 and 12.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 20 ins. in the ground, in a mound of stone, 3 ft. base, to top, with brass cap mkd.</p> <p style="text-align: center;">T 27 N R 28 E 1/4 S 11 S 12</p> <p style="text-align: center;">2003</p> <p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p> |
| 80.00 | <p>Point for the cor. of secs. 1, 2, 11 and 12.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> |

Survey of the Subdivisional Lines,
T. 27 N., R. 28 E., Gila and Salt River Meridian, Arizona

| FEET | | | | | | | | | |
|--------|---|--------|--------|-----|-----|------|------|--|------|
| | <table style="margin-left: auto; margin-right: auto;"> <tr><td>T 27 N</td><td>R 28 E</td></tr> <tr><td style="border-right: 1px solid black;">S 2</td><td>S 1</td></tr> <tr><td style="border-right: 1px solid black;">S 11</td><td>S 12</td></tr> </table> <p style="text-align: center;">2003</p> <p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p> <p>Land, rolling, rugged and broken. Soil, sandy and rocky clay with sandstone outcrops. Timber, ponderosa pine, piñon, juniper and Gambel's oak; undergrowth, brush and native grasses.</p> <hr/> <p>From the cor. of secs. 1, 6, 7 and 12, on the E. bdy. of the Tp., hereinbefore described.</p> <p>S. 89°59' W., bet. secs. 1 and 12.</p> <p>Over rolling and broken land.</p> | T 27 N | R 28 E | S 2 | S 1 | S 11 | S 12 | | |
| T 27 N | R 28 E | | | | | | | | |
| S 2 | S 1 | | | | | | | | |
| S 11 | S 12 | | | | | | | | |
| 40.00 | <p>Point for the 1/4 sec. cor. of secs. 1 and 12.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;"> <table style="margin-left: auto; margin-right: auto;"> <tr><td>T 27 N</td><td>R 28 E</td></tr> <tr><td></td><td>S 1</td></tr> <tr><td>1/4</td><td>—</td></tr> <tr><td></td><td>S 12</td></tr> </table> <p style="text-align: center;">2003</p> <p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p> </p> | T 27 N | R 28 E | | S 1 | 1/4 | — | | S 12 |
| T 27 N | R 28 E | | | | | | | | |
| | S 1 | | | | | | | | |
| 1/4 | — | | | | | | | | |
| | S 12 | | | | | | | | |
| 80.00 | <p>The cor. of secs. 1, 2, 11 and 12.</p> <p>Land, rolling, rugged and broken. Soil, sandy and rocky clay with sandstone outcrops. Timber, ponderosa pine, piñon, juniper and Gambel's oak; undergrowth, brush and native grasses.</p> <hr/> <p>N. 0°01' W., bet. secs. 1 and 2.</p> <p>Over rugged and broken land.</p> | | | | | | | | |
| 40.00 | <p>Point for the 1/4 sec. cor. of secs. 1 and 2.</p> | | | | | | | | |

**Survey of the Subdivisional Lines,
T. 27 N., R. 28 E., Gila and Salt River Meridian, Arizona**

| FEET | |
|-------|---|
| | <p>Set a brass tablet, 3 1/4 ins. diam., 2 1/2 ins. stem, in a drill hole, cemented in place in a sandstone outcrop, with top mkd.</p> <p style="text-align: center;">T 27 N R 28 E 1/4 S 2 S 1</p> <p style="text-align: center;">2003</p> <p>Deposit a magnet in a white plastic case at the base of the brass tablet.</p> |
| 80.00 | <p>The cor. of secs. 1, 2, 35 and 36, on the N. bdy. of the Tp., hereinbefore described.</p> <p>Land, rolling, rugged and broken. Soil, sandy and rocky clay with sandstone outcrops. Timber, ponderosa pine, piñon, juniper and Gambel's oak; undergrowth, brush and native grasses.</p> <hr/> <p>From the cor. of secs. 26, 27, 34 and 35, on the latitudinal governing section line, hereinbefore described.</p> <p>S. 0°01' E., bet. secs. 34 and 35.</p> <p>Over rolling land.</p> |
| 40.00 | <p>Point for the 1/4 sec. cor. of secs. 34 and 35.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T 27 N R 28 E 1/4 S 34 S 35</p> <p style="text-align: center;">2003</p> <p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p> |
| 80.68 | <p>Point for the closing cor. of secs. 34 and 35, at intersection with the N. bdy. of T. 26 N., R. 28 E.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> |

**Survey of the Subdivisional Lines,
T. 27 N., R. 28 E., Gila and Salt River Meridian, Arizona**

FEET

T 27 N R 28 E
CC
S 34 | S 35
S 2
T 26 N R 28 E

2003

Deposit a magnet in a white plastic case at the base of the stainless steel post.

From this cor. point, the cor. of secs. 2 and 3 only, T. 26 N., R. 28 E., bears S. 89°12' W., 85 lks. dist., hereinbefore described.

Land, rolling.

Soil, sandy clay.

Timber, ponderosa pine, piñon, juniper and Gambel's oak; undergrowth, brush and native grasses.

Point for the 1/4 sec. cor. of sec. 35 only, T. 27 N., R. 28 E., at midpoint on the S. bdy. of sec. 35.

Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 18 ins. in sandstone bedrock, in a mound of stone, 2 ft. base, to top, with brass cap mkd.

T 27 N R 28 E
1/4 S 35
T 26 N R 28 E

2003

Deposit a magnet in a white plastic case at the base of the stainless steel post.

From this cor. point, the 1/4 sec. cor. of sec. 2 only, T. 26 N., R. 28 E., bears S. 89°53' W., 28 lks. dist., hereinbefore described.

From the cor. of secs. 26, 27, 34 and 35, on the latitudinal governing section line, hereinbefore described.

N. 0°01' W., bet. secs. 26 and 27.

Over rolling and broken land.

28.07

S. right-of-way fence of Arizona State Highway 264, barbed wire, 5 strands, parallels highway.

**Survey of the Subdivisional Lines,
T. 27 N., R. 28 E., Gila and Salt River Meridian, Arizona**

| FEET | |
|-------|--|
| 29.69 | Arizona State Highway 264, asphalt pavement, 28 ft. wide, bears ESE and WNW. |
| 31.30 | N. right-of-way fence of Arizona State Highway 264, barbed wire, 5 strands, parallels highway. |
| 40.00 | Point for the 1/4 sec. cor. of secs. 26 and 27. Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd. <div style="text-align: center;"> T 27 N R 28 E 1/4 S 27 S 26 2003 </div> |
| 80.00 | Deposit a magnet in a white plastic case at the base of the stainless steel post. Point for the cor. of secs. 22, 23, 26 and 27. Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd. <div style="text-align: center;"> T 27 N R 28 E S 22 S 23 <hr style="width: 50%; margin: 0 auto;"/> S 27 S 26 2003 </div> |
| | Deposit a magnet in a white plastic case at the base of the stainless steel post. Land, rolling. Soil, sandy clay. Timber, ponderosa pine, piñon, juniper and Gambel's oak; undergrowth, brush and native grasses. |
| | From the cor. of secs. 23, 24, 25 and 26. S. 89°59' W., bet. secs. 23 and 26. Over rolling, rugged and broken land, across Kinlichee Creek canyon. |
| 33.75 | W. rim of Kinlichee Creek canyon, a sandstone ledge, bears SSE and NNW. |
| 40.00 | Point for the 1/4 sec. cor. of secs. 23 and 26. |

**Survey of the Subdivisional Lines,
T. 27 N., R. 28 E., Gila and Salt River Meridian, Arizona**

| FEET | |
|-------|--|
| | <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p align="center">T 27 N R 28 E S 23 1/4 ——— S 26</p> <p align="center">2003</p> <p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p> |
| 80.00 | <p>The cor. of secs. 22, 23, 26 and 27.</p> <p>Land, rolling, rugged and broken. Soil, sandy and rocky clay with sandstone outcrops. Timber, ponderosa pine, piñon, juniper and Gambel's oak; undergrowth, brush and native grasses.</p> <hr/> <p>N. 0°01' W., bet. secs. 22 and 23.</p> <p>Over rolling land.</p> |
| 40.00 | <p>Point for the 1/4 sec. cor. of secs. 22 and 23.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p align="center">T 27 N R 28 E 1/4 S 22 S 23</p> <p align="center">2003</p> <p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p> |
| 80.00 | <p>Point for the cor. of secs. 14, 15, 22 and 23.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in sandstone bedrock, with brass cap mkd.</p> <p align="center">T 27 N R 28 E S 15 S 14 S 22 S 23</p> <p align="center">2003</p> <p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p> |

**Survey of the Subdivisional Lines,
T. 27 N., R. 28 E., Gila and Salt River Meridian, Arizona**

| FEET | |
|-------|---|
| | <p>Cor. is located 1.25 chs. S. and 1.95 chs. W. of the S. rim of Kinlichee Creek canyon, a sandstone ledge, bears SE and NW.</p> <p>Land, rolling. Soil, sandy clay. Timber, ponderosa pine, piñon, juniper and Gambel's oak; undergrowth, brush and native grasses.</p> <hr/> <p>From the cor. of secs. 13, 14, 23 and 24.</p> <p>S. 89°59' W., bet. secs. 14 and 23.</p> <p>Over rolling land.</p> |
| 40.00 | <p>Point for the 1/4 sec. cor. of secs. 14 and 23.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T 27 N R 28 E S 14 1/4 ——— S 23 2003</p> |
| 80.00 | <p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p> <p>The cor. of secs. 14, 15, 22 and 23.</p> <p>Land, rolling, rugged and broken. Soil, sandy and rocky clay with sandstone outcrops. Timber, ponderosa pine, piñon, juniper and Gambel's oak; undergrowth, brush and native grasses.</p> <hr/> <p>N. 0°01' W., bet. secs. 14 and 15.</p> <p>Over rugged and broken land, thence across Kinlichee Creek canyon.</p> |
| 36.45 | <p>N. rim of Kinlichee Creek canyon, a sandstone ledge, bears SSE and NNW.</p> |
| 40.00 | <p>Point for the 1/4 sec. cor. of secs. 14 and 15.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 22 ins. in the ground, in a mound of stone, 3 ft. base, to top, with brass cap mkd.</p> |

Survey of the Subdivisional Lines,
T. 27 N., R. 28 E., Gila and Salt River Meridian, Arizona

| FEET | |
|-------|--|
| | T 27 N R 28 E 1/4 S 15 S 14 2003 |
| | Deposit a magnet in a white plastic case at the base of the stainless steel post. |
| 80.00 | Point for the cor. of secs. 10, 11, 14 and 15. |
| | Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd. |
| | T 27 N R 28 E S 10 S 11 S 15 S 14 2003 |
| | Deposit a magnet in a white plastic case at the base of the stainless steel post. |
| | Land, rugged and broken. Soil, sandy and rocky clay with sandstone outcrops. Timber, ponderosa pine, piñon, juniper and Gambel's oak; undergrowth, brush and native grasses. |
| | From the cor. of secs. 11, 12, 13 and 14. |
| | S. 89°59' W., bet. secs. 11 and 14. |
| | Over rolling land. |
| 40.00 | Point for the 1/4 sec. cor. of secs. 11 and 14. |
| | Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd. |
| | T 27 N R 28 E S 11 1/4 ——— S 14 2003 |
| | Deposit a magnet in a white plastic case at the base of the stainless steel post. |
| 80.00 | The cor. of secs. 10, 11, 14 and 15. |

**Survey of the Subdivisional Lines,
T. 27 N., R. 28 E., Gila and Salt River Meridian, Arizona**

| FEET | |
|-------|---|
| | <p>Land, rolling. Soil, sandy and rocky clay. Timber, ponderosa pine, piñon, juniper and Gambel's oak; undergrowth, brush and native grasses.</p> <hr/> <p>N. 0°01' W., bet. secs. 10 and 11.</p> <p>Over rugged and broken land, thence across Scattered Willow Wash canyon.</p> |
| 19.05 | N. rim of Scattered Willow Wash canyon, a sandstone ledge, bears SE and NW. |
| 40.00 | <p>Point for the 1/4 sec. cor. of secs. 10 and 11.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T 27 N R 28 E 1/4 S 10 S 11</p> <p style="text-align: center;">2003</p> <p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p> |
| 80.00 | <p>Point for the cor. of secs. 2, 3, 10 and 11.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T 27 N R 28 E S 3 S 2 S 10 S 11</p> <p style="text-align: center;">2003</p> <p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p> <p>Land, rugged, broken and rolling. Soil, sandy and rocky clay with sandstone outcrops. Timber, ponderosa pine, piñon, juniper and Gambel's oak; undergrowth, brush and native grasses.</p> <hr/> <p>From the cor. of secs. 1, 2, 11 and 12.</p> <p>S. 89°59' W., bet. secs. 2 and 11.</p> <p>Over rolling land.</p> |

**Survey of the Subdivisional Lines,
T. 27 N., R. 28 E., Gila and Salt River Meridian, Arizona**

| FEET | |
|-------|--|
| 40.00 | <p>Point for the 1/4 sec. cor. of secs. 2 and 11.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T 27 N R 28 E S 2 1/4 ——— S 11</p> <p style="text-align: center;">2003</p> <p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p> |
| 80.00 | <p>The cor. of secs. 2, 3, 10 and 11.</p> <p>Land, rolling. Soil, sandy and rocky clay. Timber, ponderosa pine, piñon, juniper and Gambel's oak; undergrowth, brush and native grasses.</p> <hr/> <p>N. 0°01' W., bet. secs. 2 and 3.</p> <p>Over rugged and broken land.</p> |
| 40.00 | <p>Point for the 1/4 sec. cor. of secs. 2 and 3.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 18 ins. in sandstone bedrock, in a mound of stone, 3 ft. base, to top, with brass cap mkd.</p> <p style="text-align: center;">T 27 N R 28 E 1/4 S 3 S 2</p> <p style="text-align: center;">2003</p> <p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p> |
| 41.70 | <p>Black Soil Wash, 10 ft. wide, 2 ft. deep, drains WSW.</p> |
| 80.00 | <p>The cor. of secs. 2, 3, 34 and 35, on the N. bdy. of the Tp., hereinbefore described.</p> |

**Survey of the Subdivisional Lines,
T. 27 N., R. 28 E., Gila and Salt River Meridian, Arizona**

| FEET | |
|-------|---|
| | <p>Land, rolling, rugged and broken. Soil, sandy and rocky clay with sandstone outcrops. Timber, ponderosa pine, piñon, juniper and Gambel's oak; undergrowth, brush and native grasses.</p> <hr/> <p>From the cor. of secs. 27, 28, 33 and 34, on the latitudinal governing section line, hereinbefore described.</p> <p>S. 0°01' E., bet. sec. 33 and 34.</p> <p>Over rolling land.</p> |
| 40.00 | <p>Point for the 1/4 sec. cor. of secs. 33 and 34.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T 27 N R 28 E 1/4 S 33 S 34</p> <p style="text-align: center;">2003</p> <p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p> |
| 41.10 | <p>Trail road, bears ESE and WNW.</p> |
| 80.57 | <p>The cor. of secs. 3, 4, 33 and 34, on the S. bdy. of the Tp., hereinbefore described.</p> <p>Land, rolling. Soil, sandy clay. Timber, ponderosa pine, piñon, juniper and Gambel's oak; undergrowth, brush and native grasses.</p> <hr/> <p>Point for the 1/4 sec. cor. of sec. 34 only, T. 27 N., R. 28 E., at midpoint on the S. bdy. of sec. 34.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T 27 N R 28 E 1/4 S 34</p> <hr/> <p style="text-align: center;">T 26 N R 28 E</p> <p style="text-align: center;">2003</p> <p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p> |

**Survey of the Subdivisional Lines,
T. 27 N., R. 28 E., Gila and Salt River Meridian, Arizona**

| FEET | |
|-------|--|
| | <p>From this cor. point, the 1/4 sec. cor. of sec. 3 only, T. 26 N., R. 28 E., bears N. 89°40' W., 63 lks. dist., hereinbefore described.</p> <hr/> <p>From the cor. of secs. 27, 28, 33 and 34, on the latitudinal governing section line, hereinbefore described.</p> <p>N. 0°02' W., bet. secs. 27 and 28.</p> <p>Over rolling land.</p> |
| 40.00 | <p>Point for the 1/4 sec. cor. of secs. 27 and 28.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center;"> <p>T 27 N R 28 E 1/4 S 28 S 27</p> <p>2003</p> </div> <p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p> |
| 41.30 | <p>Apache County Road C423, a graded road, 20 ft. wide, bears ENE and WSW.</p> |
| 51.42 | <p>S. right-of-way fence of Arizona State Highway 264, barbed wire, 5 strands, bears ESE and WSW.</p> |
| 52.97 | <p>Arizona State Highway 264, asphalt pavement, 30 ft. wide, bears ESE and WNW.</p> |
| 54.50 | <p>N. right-of-way fence of Arizona State Highway 264, barbed wire, 5 strands, bears ESE and WSW.</p> |
| 59.85 | <p>Graded road, 20 ft. wide, bears NE and SW.</p> |
| 80.00 | <p>Point for the cor. of secs. 21, 22, 27 and 28.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center;"> <p>T 27 N R 28 E S 21 S 22 S 28 S 27</p> <p>2003</p> </div> <p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p> |

**Survey of the Subdivisional Lines,
T. 27 N., R. 28 E., Gila and Salt River Meridian, Arizona**

| FEET | |
|-------|---|
| | <p>Cor. is located 73 lks. S. of a woven wire fence, 4 ft. high, bears ESE and WNW.</p> <p>Land, rolling. Soil, sandy clay. Timber, ponderosa pine, piñon, juniper and Gambel's oak; undergrowth, brush and native grasses.</p> <hr/> <p>From the cor. of secs. 22, 23, 27 and 28.</p> <p>S. 89°59' W., bet. secs. 22 and 27.</p> <p>Over rolling land.</p> |
| 40.00 | <p>Point for the 1/4 sec. cor. of secs. 22 and 27.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center; margin: 10px 0;"> <p>T 27 N R 28 E S 22 1/4 ——— S 27</p> <p>2003</p> </div> <p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p> |
| 62.25 | <p>Graded road, 20 ft. wide, bears NE and SW.</p> |
| 75.25 | <p>Trail road, bears NNE and SSW.</p> |
| 77.31 | <p>Woven wire fence, 4 ft. high, bears ESE and WNW.</p> |
| 80.00 | <p>The cor. of secs. 21, 22, 27 and 28.</p> <p>Land, rolling. Soil, sandy clay. Timber, ponderosa pine, piñon, juniper and Gambel's oak; undergrowth, brush and native grasses.</p> <hr/> <p>N. 0°02' W., bet. secs. 21 and 22.</p> <p>Over rolling land.</p> |
| 1.95 | <p>Trail road, bears NNE and SSW.</p> |
| 40.00 | <p>Point for the 1/4 sec. cor. of secs. 21 and 22.</p> |

**Survey of the Subdivisional Lines,
T. 27 N., R. 28 E., Gila and Salt River Meridian, Arizona**

| FEET | |
|-------|---|
| 80.00 | <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T 27 N R 28 E 1/4 S 21 S 22</p> <p style="text-align: center;">2003</p> <p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p> <p>Point for the cor. of secs. 15, 16, 21 and 22.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T 27 N R 28 E S 16 S 15 ----- S 21 S 22</p> <p style="text-align: center;">2003</p> <p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p> <p>Land, rolling. Soil, sandy clay. Timber, ponderosa pine, piñon, juniper and Gambel's oak; undergrowth, brush and native grasses.</p> <hr/> <p>From the cor. of secs. 14, 15, 22 and 23.</p> <p>S. 89°59' W., bet. secs. 15 and 22.</p> <p>Over rolling land.</p> |
| 40.00 | <p>Point for the 1/4 sec. cor. of secs. 15 and 22.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T 27 N R 28 E S 15 1/4 ——— S 22</p> <p style="text-align: center;">2003</p> <p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p> |

Survey of the Subdivisional Lines,
T. 27 N., R. 28 E., Gila and Salt River Meridian, Arizona

| FEET | |
|-------|--|
| 80.00 | <p>The cor. of secs. 15, 16, 21 and 22.</p> <p>Land, rolling. Soil, sandy clay. Timber, ponderosa pine, piñon, juniper and Gambel's oak; undergrowth, brush and native grasses.</p> <hr/> <p>N. 0°02' W., bet. secs. 15 and 16.</p> <p>Over rolling land.</p> |
| 40.00 | <p>Point for the 1/4 sec. cor. of secs. 15 and 16.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T 27 N R 28 E 1/4 S 16 S 15</p> <p style="text-align: center;">2003</p> <p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p> |
| 75.40 | <p>S. rim of Kinlichee Creek canyon, a sandstone ledge, bears NE and SW, thence descend into the canyon.</p> |
| 80.00 | <p>True point for the cor. of secs. 9, 10, 15 and 16, falls on a vertical sandstone cliff, 10 ft. high, bears E. and W.; where it is impracticable to establish a monument.</p> <p>From this true point, the point selected for the witness cor. to the cor. of secs. 9, 10, 15 and 16, bears S. 71°12' E., 81.5 lks. dist.</p> <p>Set a brass tablet, 3 1/4 ins. diam., 2 1/2 ins. stem, in a drill hole, cemented in place in sandstone bedrock, with top mkd.</p> <p style="text-align: center;">WC ← T 27 N R 28 E S 9 S 10 S 16 S 15</p> <p style="text-align: center;">2003</p> <p>Deposit a magnet in a white plastic case at the base of the brass tablet.</p> |

**Survey of the Subdivisional Lines,
T. 27 N., R. 28 E., Gila and Salt River Meridian, Arizona**

| FEET | |
|-------|---|
| | <p>Land, rolling to broken. Soil, sandy clay. Timber, ponderosa pine, piñon, juniper and Gambel's oak; undergrowth, brush and native grasses.</p> <hr/> <p>From the cor. of secs. 10, 11, 14 and 15. S. 89°59' W., bet. secs. 10 and 15. Over rugged and broken land.</p> |
| 26.50 | E. rim of Scattered Willow Wash canyon, a sandstone ledge, bears NNE and SSW. |
| 37.30 | W. rim of Scattered Willow Wash canyon, a sandstone ledge, bears NE and SW, thence over rolling land. |
| 40.00 | <p>Point for the 1/4 sec. cor. of secs. 10 and 15. Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center;"> <p>T 27 N R 28 E S 10 1/4 ——— S 15</p> <p>2003</p> </div> <p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p> |
| 60.55 | N. rim of Kinlichee Creek canyon, a sandstone ledge, bears SSE and NNW, thence descend into the canyon. |
| 80.00 | <p>The true point for the cor. of secs. 9, 10, 15 and 16. Land, rolling, rugged and broken. Soil, sandy and rocky clay with sandstone outcrops. Timber, ponderosa pine, piñon, juniper and Gambel's oak; undergrowth, brush and native grasses.</p> <hr/> <p>N. 0°02' W., bet. secs. 9 and 10. Over rugged and broken land, ascend out of Kinlichee Creek canyon.</p> |
| 2.40 | Kinlichee Creek, a wash, 50 ft. wide, 3 ft. deep, drains W., thence ascend out of the canyon. |

**Survey of the Subdivisional Lines,
T. 27 N., R. 28 E., Gila and Salt River Meridian, Arizona**

| FEET | |
|-------|---|
| 9.55 | N. rim of Kinlichee Creek canyon, a sandstone ledge, bears NE and SW, thence over rolling land. |
| 40.00 | Point for the 1/4 sec. cor. of secs. 9 and 10. Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd. <div style="text-align: center;"> T 27 N R 28 E 1/4 S 9 S 10 2003 </div> Deposit a magnet in a white plastic case at the base of the stainless steel post. |
| 64.85 | N. rim of Black Soil Wash canyon, a sandstone ledge, bears E. and W. |
| 80.00 | Point for the cor. of secs. 3, 4, 9 and 10. Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd. <div style="text-align: center;"> T 27 N R 28 E S 4 S 3 --- S 9 S 10 2003 </div> Deposit a magnet in a white plastic case at the base of the stainless steel post. Land, rolling, rugged and broken. Soil, sandy and rocky clay with sandstone outcrops. Timber, ponderosa pine, piñon, juniper and Gambel's oak; undergrowth, brush and native grasses. |
| | <hr/> From the cor. of secs. 2, 3, 10 and 11. S. 89°59' W., bet. secs. 3 and 10. Over rolling and broken land. |
| 29.40 | W. rim of Black Soil Wash canyon, a sandstone ledge, bears NE and SW. |
| 40.00 | Point for the 1/4 sec. cor. of secs. 3 and 10. Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd. |

**Survey of the Subdivisional Lines,
T. 27 N., R. 28 E., Gila and Salt River Meridian, Arizona**

| FEET | |
|-------|--|
| | T 27 N R 28 E S 3 1/4 ——— S 10 2003 |
| | Deposit a magnet in a white plastic case at the base of the stainless steel post. |
| 80.00 | The cor. of secs. 3, 4, 9 and 10. Land, rolling, rugged and broken. Soil, sandy and rocky clay with sandstone outcrops. Timber, ponderosa pine, piñon, juniper and Gambel's oak; undergrowth, brush and native grasses. |
| | <hr/> N. 0°02' W., bet. secs. 3 and 4. Over rolling land. |
| 28.35 | Navajo Route 203, a graded road, 20 ft. wide, bears ENE and WSW. |
| 40.00 | Point for the 1/4 sec. cor. of secs. 3 and 4. Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd. |
| | T 27 N R 28 E 1/4 S 4 S 3 2003 |
| | Deposit a magnet in a white plastic case at the base of the stainless steel post. |
| 80.00 | The cor. of secs. 3, 4, 33 and 34, on the N. bdy. of the Tp., hereinbefore described. Land, rolling. Soil, sandy and rocky clay. Timber, scattered ponderosa, piñon, juniper and Gambel's oak; undergrowth, brush and native grasses. |
| | <hr/> From the cor. of secs. 28, 29, 32 and 33, on the latitudinal governing section line, hereinbefore described. S. 0°03' E., bet. secs. 32 and 33. Over rolling land. |

**Survey of the Subdivisional Lines,
T. 27 N., R. 28 E., Gila and Salt River Meridian, Arizona**

| FEET | |
|-------|--|
| 40.00 | <p>Point for the 1/4 sec. cor. of secs. 32 and 33.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T 27 N R 28 E 1/4 S 32 S 33</p> <p style="text-align: center;">2003</p> <p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p> |
| 59.15 | <p>Apache County Road C324, a graded road, 20 ft. wide, bears SSE and NNW.</p> |
| 80.94 | <p>Point for the closing cor. of secs. 32 and 33, at intersection with the S. bdy. of the Tp.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T 27 N R 28 E CC S 32 S 33</p> <p style="text-align: center;">S 5 T 26 N R 28 E</p> <p style="text-align: center;">2003</p> <p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p> <p>From this cor. point, the cor. of secs. 4 and 5 only, T. 26 N., R. 28 E., bears S. 89°41' E., 1.14 chs. dist., hereinbefore described.</p> <p>Land, rolling. Soil, sandy clay. Timber, piñon, juniper and Gambel's oak; undergrowth, brush and native grasses.</p> <hr/> <p>Point for the 1/4 sec. cor. of sec. 33 only, T. 27 N., R. 28 E., at midpoint on the S. bdy. of sec. 33.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> |

**Survey of the Subdivisional Lines,
T. 27 N., R. 28 E., Gila and Salt River Meridian, Arizona**

| FEET | |
|-------|--|
| | <p>T 27 N R 28 E 1/4 S 33</p> <hr style="width: 20%; margin: auto;"/> <p>T 26 N R 28 E</p> <p>2003</p> |
| | <p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p> <p>From this cor. point, the 1/4 sec. cor. of sec. 4 only, T. 26 N., R. 28 E., bears N. 89°43' E., 57 lks. dist., hereinbefore described.</p> <hr style="width: 80%; margin-left: 0;"/> <p>From the cor. of secs. 28, 29, 32 and 33, on the latitudinal governing section line, hereinbefore described.</p> <p>N. 0°03' W., bet. secs. 28 and 29.</p> <p>Over rolling land.</p> |
| 40.00 | <p>Point for the 1/4 sec. cor. of secs. 28 and 29.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> |
| | <p>T 27 N R 28 E 1/4 S 29 S 28</p> <p>2003</p> |
| | <p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p> |
| 65.84 | <p>S. right-of-way fence of Arizona State Highway 264, barbed wire, 5 strands, parallels highway.</p> |
| 67.36 | <p>Arizona State Highway 264, asphalt pavement, 26 ft. wide, bears ESE and WNW.</p> |
| 68.89 | <p>N. right-of-way fence of Arizona State Highway 264, barbed wire, 5 strands, parallels highway.</p> |
| 80.00 | <p>Point for the cor. of secs. 20, 21, 28 and 29.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> |

**Survey of the Subdivisional Lines,
T. 27 N., R. 28 E., Gila and Salt River Meridian, Arizona**

| FEET | | | | | | | | | |
|--------|---|--------|--------|------|------|------|------|--|------|
| | <table border="0"> <tr> <td>T 27 N</td> <td>R 28 E</td> </tr> <tr> <td>S 20</td> <td>S 21</td> </tr> <tr> <td>S 29</td> <td>S 28</td> </tr> </table> | T 27 N | R 28 E | S 20 | S 21 | S 29 | S 28 | | |
| T 27 N | R 28 E | | | | | | | | |
| S 20 | S 21 | | | | | | | | |
| S 29 | S 28 | | | | | | | | |
| | 2003 | | | | | | | | |
| | Deposit a magnet in a white plastic case at the base of the stainless steel post. | | | | | | | | |
| | Land, rolling. Soil, sandy clay. Timber, piñon, juniper and Gambel's oak; undergrowth, brush and native grasses. | | | | | | | | |
| | <hr/> | | | | | | | | |
| | From the cor. of secs. 21, 22, 27 and 28. | | | | | | | | |
| | S. 89°59' W., bet. secs. 21 and 28. | | | | | | | | |
| | Over rolling land. | | | | | | | | |
| 1.10 | Trail road, bears NNE and SSW. | | | | | | | | |
| 40.00 | Point for the 1/4 sec. cor. of secs. 21 and 28. | | | | | | | | |
| | Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd. | | | | | | | | |
| | <table border="0"> <tr> <td>T 27 N</td> <td>R 28 E</td> </tr> <tr> <td></td> <td>S 21</td> </tr> <tr> <td>1/4</td> <td>—</td> </tr> <tr> <td></td> <td>S 28</td> </tr> </table> | T 27 N | R 28 E | | S 21 | 1/4 | — | | S 28 |
| T 27 N | R 28 E | | | | | | | | |
| | S 21 | | | | | | | | |
| 1/4 | — | | | | | | | | |
| | S 28 | | | | | | | | |
| | 2003 | | | | | | | | |
| | Deposit a magnet in a white plastic case at the base of the stainless steel post. | | | | | | | | |
| 80.00 | The cor. of secs. 20, 21, 28 and 29. | | | | | | | | |
| | Land, rolling. Soil, sandy clay. Timber, piñon, juniper and Gambel's oak; undergrowth, brush and native grasses. | | | | | | | | |
| | <hr/> | | | | | | | | |
| | N. 0°03' W., bet. secs. 20 and 21. | | | | | | | | |
| | Over rolling land. | | | | | | | | |
| 40.00 | Point for the 1/4 sec. cor. of secs. 20 and 21. | | | | | | | | |

**Survey of the Subdivisional Lines,
T. 27 N., R. 28 E., Gila and Salt River Meridian, Arizona**

| FEET | |
|-------|---|
| | <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T 27 N R 28 E 1/4 S 20 S 21</p> <p style="text-align: center;">2003</p> <p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p> |
| 80.00 | <p>Point for the cor. of secs. 16, 17, 20 and 21.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T 27 N R 28 E S 17 S 16 ----- S 20 S 21</p> <p style="text-align: center;">2003</p> <p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p> <p>Land, rolling. Soil, sandy clay. Timber, scattered ponderosa pine, piñon, juniper and Gambel's oak; undergrowth, brush and native grasses.</p> <hr/> <p>From the cor. of secs. 15, 16, 21 and 22.</p> <p>S. 89°59' W., bet. secs. 16 and 21.</p> <p>Over rolling land.</p> |
| 40.00 | <p>Point for the 1/4 sec. cor. of secs. 16 and 21.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T 27 N R 28 E S 16 1/4 ----- S 21</p> <p style="text-align: center;">2003</p> <p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p> |

**Survey of the Subdivisional Lines,
T. 27 N., R. 28 E., Gila and Salt River Meridian, Arizona**

| FEET | |
|-------|--|
| 80.00 | <p>The cor. of secs. 16, 17, 20 and 21.</p> <p>Land, rolling. Soil, sandy clay. Timber, scattered ponderosa pine, piñon, juniper and Gambel's oak; undergrowth, brush and native grasses.</p> <hr/> <p>N. 0°03' W., bet. secs. 16 and 17.</p> <p>Over rolling land.</p> |
| 40.00 | <p>Point for the 1/4 sec. cor. of secs. 16 and 17.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center;"> <p>T 27 N R 28 E 1/4 S 17 S 16</p> <p>2003</p> </div> <p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p> |
| 68.50 | <p>S. rim of Kinlichee Creek canyon, a sandstone ledge, bears ENE and WSW, thence across the canyon.</p> |
| 78.50 | <p>N. rim of Kinlichee Creek canyon, a sandstone ledge, bears ENE and WSW.</p> |
| 80.00 | <p>Point for the cor. of secs. 8, 9, 16 and 17.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center;"> <p>T 27 N R 28 E S 8 S 9 S 17 S 16</p> <p>2003</p> </div> <p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p> <p>Land, rolling and broken. Soil, sandy and rocky clay with sandstone outcrops. Timber, ponderosa pine, piñon, juniper and Gambel's oak; undergrowth, brush and native grasses.</p> <hr/> <p>From the true point for the cor. of secs. 9, 10, 15 and 16.</p> |

**Survey of the Subdivisional Lines,
T. 27 N., R. 28 E., Gila and Salt River Meridian, Arizona**

| FEET | |
|-------|---|
| | S. 89°59' W., bet. secs. 9 and 16. Over rugged and broken canyon land. |
| 33.70 | S. rim of Kinlichee Creek canyon, a sandstone ledge, bears N. and S., thence over rolling land. |
| 40.00 | Point for the 1/4 sec. cor. of secs. 9 and 16. Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd. |
| | T 27 N R 28 E S 9 1/4 ——— S 16 2003 |
| | Deposit a magnet in a white plastic case at the base of the stainless steel post. |
| 51.05 | S. rim of Kinlichee Creek canyon, a sandstone ledge, bears NE and SW, thence across the canyon. |
| 66.90 | N. rim of Kinlichee Creek canyon, a sandstone ledge, bears NE and SW. |
| 80.00 | The cor. of secs. 8, 9, 16 and 17. Land, rugged, broken and rolling. Soil, sandy and rocky clay with sandstone outcrops. Timber, scattered ponderosa pine, piñon, juniper and Gambel's oak; undergrowth, brush and native grasses. |
| | N. 0°03' W., bet. secs. 8 and 9. Over rolling land. |
| 40.00 | Point for the 1/4 sec. cor. of secs. 8 and 9. Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd. |
| | T 27 N R 28 E 1/4 S 8 S 9 2003 |
| | Deposit a magnet in a white plastic case at the base of the stainless steel post. |

**Survey of the Subdivisional Lines,
T. 27 N., R. 28 E., Gila and Salt River Meridian, Arizona**

| FEET | | | | | | | | | |
|--------|--|--------|--------|-----|-----|-----|-----|-----|--|
| 71.85 | Navajo Route 203, a graded road, 20 ft. wide, bears E. and W. | | | | | | | | |
| 80.00 | Point for the cor. of secs. 4, 5, 8 and 9. Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd. <div style="text-align: center;"> <table style="margin: auto;"> <tr><td>T 27 N</td><td>R 28 E</td></tr> <tr><td>S 5</td><td>S 4</td></tr> <tr><td>S 8</td><td>S 9</td></tr> </table> <p>2003</p> </div> | T 27 N | R 28 E | S 5 | S 4 | S 8 | S 9 | | |
| T 27 N | R 28 E | | | | | | | | |
| S 5 | S 4 | | | | | | | | |
| S 8 | S 9 | | | | | | | | |
| | Deposit a magnet in a white plastic case at the base of the stainless steel post. Land, rolling. Soil, sandy and rocky clay. Timber, scattered ponderosa pine, piñon, juniper and Gambel's oak; undergrowth, brush and native grasses. | | | | | | | | |
| | From the cor. of secs. 3, 4, 9 and 10. S. 89°59' W., bet. secs. 4 and 9. Over rolling land. | | | | | | | | |
| 40.00 | Point for the 1/4 sec. cor. of secs. 4 and 9. Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd. <div style="text-align: center;"> <table style="margin: auto;"> <tr><td>T 27 N</td><td>R 28 E</td></tr> <tr><td>S 4</td><td></td></tr> <tr><td>1/4</td><td>—</td></tr> <tr><td>S 9</td><td></td></tr> </table> <p>2003</p> </div> | T 27 N | R 28 E | S 4 | | 1/4 | — | S 9 | |
| T 27 N | R 28 E | | | | | | | | |
| S 4 | | | | | | | | | |
| 1/4 | — | | | | | | | | |
| S 9 | | | | | | | | | |
| | Deposit a magnet in a white plastic case at the base of the stainless steel post. | | | | | | | | |
| 63.40 | Navajo Route 203, a graded road, 20 ft. wide, bears ENE and WSW. | | | | | | | | |
| 80.00 | The cor. of secs. 4, 5, 8 and 9. | | | | | | | | |

**Survey of the Subdivisional Lines,
T. 27 N., R. 28 E., Gila and Salt River Meridian, Arizona**

| FEET | |
|-------|--|
| | <p>Land, rolling. Soil, sandy and rocky clay. Timber, piñon, juniper and Gambel's oak; undergrowth, brush and native grasses.</p> <hr/> <p>N. 0°03' W., bet. secs. 4 and 5.</p> <p>Over rolling and broken land.</p> |
| 40.00 | <p>Point for the 1/4 sec. cor. of secs. 4 and 5.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T 27 N R 28 E 1/4 S 5 S 4 2003</p> |
| 41.40 | <p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p> <p>Ruin Wash, 30 ft. wide, 10 ft. deep, drains SW.</p> |
| 80.00 | <p>The cor. of secs. 4, 5, 32 and 33, on the N. bdy. of the Tp., hereinbefore described.</p> <p>Land, rolling. Soil, sandy and rocky clay. Timber, piñon, juniper and Gambel's oak; undergrowth, brush and native grasses.</p> <hr/> <p>From the cor. of secs. 29, 30, 31 and 32, on the latitudinal governing section line, hereinbefore described.</p> <p>S. 0°03' E., bet. secs. 31 and 32.</p> <p>Over rolling land.</p> |
| 40.00 | <p>Point for the 1/4 sec. cor. of secs. 31 and 32.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T 27 N R 28 E 1/4 S 31 S 32 2003</p> |

**Survey of the Subdivisional Lines,
T. 27 N., R. 28 E., Gila and Salt River Meridian, Arizona**

| FEET | |
|-------|--|
| | Deposit a magnet in a white plastic case at the base of the stainless steel post. |
| 77.20 | Burnt Piñon Wash, 40 ft. wide, 4 ft. deep, drains NW. |
| 80.47 | Point for the closing cor. of secs. 31 and 32, at intersection with the S. bdy. of the Tp. |
| | Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd. |
| | T 27 N R 28 E CC <u>S 31 S 32</u> S 6 T 26 N R 28 E 2003 |
| | Deposit a magnet in a white plastic case at the base of the stainless steel post. |
| | From this cor. point, the cor. of secs. 5 and 6 only, T. 26 N., R. 28 E., bears S. 89°41' E., 15 lks. dist., hereinbefore described. |
| | Land, rolling. Soil, sandy clay. Timber, piñon, juniper and Gambel's oak; undergrowth, brush and native grasses. |
| | <hr/> |
| | Point for the 1/4 sec. cor. of sec. 32 only, T. 27 N., R. 28 E., at midpoint on the S. bdy. of sec. 32. |
| | Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd. |
| | T 27 N R 28 E <u>1/4 S 32</u> T 26 N R 28 E 2003 |
| | Deposit a magnet in a white plastic case at the base of the stainless steel post. |

**Survey of the Subdivisional Lines,
T. 27 N., R. 28 E., Gila and Salt River Meridian, Arizona**

| FEET | |
|-------|---|
| | <p>From this cor. point, the 1/4 sec. cor. of sec. 5 only, T. 26 N., R. 28 E., bears S. 89°41' E., 64.5 lks. dist., hereinbefore described.</p> <hr/> <p>Point for the 1/4 sec. cor. of sec. 31 only, T. 27 N., R. 28 E., at 40.00 chs. in westing from the closing cor. of secs. 31 and 32, on S. bdy. of sec. 31.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T 27 N R 28 E 1/4 S 31 <hr/>T 26 N R 28 E</p> <p style="text-align: center;">2003</p> <p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p> <p>From this cor. point, the 1/4 sec. cor. of sec. 6 only, T. 26 N., R. 28 E., bears N. 89°41' W., 34 lks. dist., hereinbefore described.</p> <hr/> <p>From the cor. of secs. 29, 30, 31 and 32, on the latitudinal governing section line, hereinbefore described.</p> <p>N. 0°03' W., bet. secs. 29 and 30.</p> <p>Over rolling land.</p> |
| 40.00 | <p>Point for the 1/4 sec. cor. of secs. 29 and 30.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T 27 N R 28 E 1/4 S 30 S 29</p> <p style="text-align: center;">2003</p> <p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p> |
| 45.75 | <p>Trail road, bears SE and NW.</p> |
| 61.92 | <p>S. right-of-way fence of Arizona State Highway 264, barbed wire, 4 strands, parallels highway.</p> |

**Survey of the Subdivisional Lines,
T. 27 N., R. 28 E., Gila and Salt River Meridian, Arizona**

| FEET | | | | | | | |
|--------|---|--------|--------|------|-------|------|------|
| 63.44 | Arizona State Highway 264, asphalt pavement, 28 ft. wide, bears E. and W. | | | | | | |
| 64.95 | N. right-of-way fence of Arizona State Highway 264, barbed wire, 5 strands, parallels highway. | | | | | | |
| 80.00 | Point for the cor. of secs. 19, 20, 29 and 30. Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd. <div style="text-align: center;"> <table border="1"> <tr> <td>T 27 N</td> <td>R 28 E</td> </tr> <tr> <td>S 19</td> <td>S 20</td> </tr> <tr> <td>S 30</td> <td>S 29</td> </tr> </table> <p>2003</p> </div> <p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p> <p>Cor. is located 15 lks. E. and 35 lks. S. of a trail road, bears NNE and SSW.</p> <p>Land, rolling. Soil, sandy clay. Timber, piñon, juniper and Gambel's oak; undergrowth, brush and native grasses.</p> <hr/> <p>From the cor. of secs. 20, 21, 28 and 29. S. 89°59' W., bet. secs. 20 and 29. Over rolling land.</p> | T 27 N | R 28 E | S 19 | S 20 | S 30 | S 29 |
| T 27 N | R 28 E | | | | | | |
| S 19 | S 20 | | | | | | |
| S 30 | S 29 | | | | | | |
| 40.00 | Point for the 1/4 sec. cor. of secs. 20 and 29. Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd. <div style="text-align: center;"> <table border="1"> <tr> <td>T 27 N</td> <td>R 28 E</td> </tr> <tr> <td>S 20</td> <td>1/4 —</td> </tr> <tr> <td>S 29</td> <td></td> </tr> </table> <p>2003</p> </div> <p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p> | T 27 N | R 28 E | S 20 | 1/4 — | S 29 | |
| T 27 N | R 28 E | | | | | | |
| S 20 | 1/4 — | | | | | | |
| S 29 | | | | | | | |
| 80.00 | The cor. of secs. 19, 20, 29 and 30. | | | | | | |

Survey of the Subdivisional Lines,
T. 27 N., R. 28 E., Gila and Salt River Meridian, Arizona

| FEET | |
|-------|---|
| | <p>Land, rolling. Soil, sandy clay. Timber, piñon, juniper and Gambel's oak; undergrowth, brush and native grasses.</p> <hr/> <p>S. 89°59' W., bet. secs. 19 and 30.</p> <p>Over rolling land.</p> |
| 40.00 | <p>Point for the 1/4 sec. cor. of secs. 19 and 30.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center;"> <p>T 27 N R 28 E S 19 1/4 — S 30</p> <p>2003</p> </div> <p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p> |
| 79.54 | <p>The cor. of secs. 19, 24, 25 and 30, on the W. bdy. of the Tp., monumented with a stainless steel post, 2 1/2 ins. diam., with brass cap, set and mkd. as described in the field notes of the survey of the E. bdy., T. 27 N., R. 27 E., executed concurrently under this same group.</p> <p>Land, rolling. Soil, sandy clay. Timber, piñon, juniper and Gambel's oak; undergrowth, brush and native grasses.</p> <hr/> <p>From the cor. of secs. 19, 20, 29 and 30.</p> <p>N. 0°03' W., bet. secs. 19 and 20.</p> <p>Over rolling land.</p> |
| 40.00 | <p>Point for the 1/4 sec. cor. of secs. 19 and 20.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center;"> <p>T 27 N R 28 E 1/4 S 19 S 20</p> <p>2003</p> </div> |

**Survey of the Subdivisional Lines,
T. 27 N., R. 28 E., Gila and Salt River Meridian, Arizona**

| FEET | | | | | | | | | |
|--------|--|--------|--------|------|------|------|---------|--|------|
| | Deposit a magnet in a white plastic case at the base of the stainless steel post. | | | | | | | | |
| 80.00 | Point for the cor. of secs. 17, 18, 19 and 20. Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd. | | | | | | | | |
| | <table style="margin-left: auto; margin-right: auto;"> <tr> <td>T 27 N</td> <td>R 28 E</td> </tr> <tr> <td>S 18</td> <td>S 17</td> </tr> <tr> <td style="border-top: 1px solid black;">S 19</td> <td style="border-top: 1px solid black;">S 20</td> </tr> </table> | T 27 N | R 28 E | S 18 | S 17 | S 19 | S 20 | | |
| T 27 N | R 28 E | | | | | | | | |
| S 18 | S 17 | | | | | | | | |
| S 19 | S 20 | | | | | | | | |
| | 2003 | | | | | | | | |
| | Deposit a magnet in a white plastic case at the base of the stainless steel post. | | | | | | | | |
| | Land, rolling. Soil, sandy clay. Timber, piñon and juniper; undergrowth, brush and native grasses. | | | | | | | | |
| | <hr/> | | | | | | | | |
| | From the cor. of secs. 16, 17, 20 and 21. | | | | | | | | |
| | S. 89°59' W., bet. secs. 17 and 20. | | | | | | | | |
| | Over rolling land. | | | | | | | | |
| 37.10 | Trail road, bears NNE and SSW. | | | | | | | | |
| 40.00 | Point for the 1/4 sec. cor. of secs. 17 and 20. Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd. | | | | | | | | |
| | <table style="margin-left: auto; margin-right: auto;"> <tr> <td>T 27 N</td> <td>R 28 E</td> </tr> <tr> <td></td> <td>S 17</td> </tr> <tr> <td></td> <td>1/4 ———</td> </tr> <tr> <td></td> <td>S 20</td> </tr> </table> | T 27 N | R 28 E | | S 17 | | 1/4 ——— | | S 20 |
| T 27 N | R 28 E | | | | | | | | |
| | S 17 | | | | | | | | |
| | 1/4 ——— | | | | | | | | |
| | S 20 | | | | | | | | |
| | 2003 | | | | | | | | |
| | Deposit a magnet in a white plastic case at the base of the stainless steel post. | | | | | | | | |
| 80.00 | The cor. of secs. 17, 18, 19 and 20. | | | | | | | | |

**Survey of the Subdivisional Lines,
T. 27 N., R. 28 E., Gila and Salt River Meridian, Arizona**

| FEET | |
|-------|--|
| | <p>Land, rolling. Soil, sandy clay. Timber, scattered ponderosa pine, piñon, juniper and Gambel's oak; undergrowth, brush and native grasses.</p> <hr/> <p>S. 89°59' W., bet. secs. 18 and 19.</p> <p>Over rolling land.</p> |
| 40.00 | <p>Point for the 1/4 sec. cor. of secs. 18 and 19.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T 27 N R 28 E S 18 1/4 ——— S 19</p> <p style="text-align: center;">2003</p> <p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p> |
| 79.46 | <p>The cor. of secs. 13, 18, 19 and 24, on the W. bdy. of the Tp., monumented with a stainless steel post, 2 1/2 ins. diam., with brass cap, set and mkd., as described in the field notes of the survey of the E. bdy., T. 27 N., R. 27 E., executed concurrently under this same group.</p> <p>Land, rolling. Soil, sandy clay. Timber, piñon and juniper; undergrowth, brush and native grasses.</p> <hr/> <p>From the cor. of secs. 17, 18, 19 and 20.</p> <p>N. 0°03' W., bet. secs. 17 and 18.</p> <p>Over rolling land.</p> |
| 40.00 | <p>Point for the 1/4 sec. cor. of secs. 17 and 18.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T 27 N R 28 E 1/4 S 18 S 17</p> <p style="text-align: center;">2003</p> |

**Survey of the Subdivisional Lines,
T. 27 N., R. 28 E., Gila and Salt River Meridian, Arizona**

| FEET | | | | | | | |
|--------|--|--------|--------|-----|-----|------|------|
| | Deposit a magnet in a white plastic case at the base of the stainless steel post. | | | | | | |
| 53.00 | S. rim of Kinlichee Creek canyon, a sandstone ledge, bears NE and SW, thence across the canyon. | | | | | | |
| 61.00 | N. rim of Kinlichee Creek canyon, a sandstone cliff, 200 ft. high, bears NE and SW, thence ascend the N. slope. | | | | | | |
| 65.25 | Top of the N. slope of Kinlichee Creek canyon, a sandstone ledge, bears NE and SW. | | | | | | |
| 80.00 | Point for the cor. of secs. 7, 8, 17 and 18. | | | | | | |
| | Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd. | | | | | | |
| | <table style="margin-left: auto; margin-right: auto;"> <tr> <td>T 27 N</td> <td>R 28 E</td> </tr> <tr> <td>S 7</td> <td>S 8</td> </tr> <tr> <td>S 18</td> <td>S 17</td> </tr> </table> | T 27 N | R 28 E | S 7 | S 8 | S 18 | S 17 |
| T 27 N | R 28 E | | | | | | |
| S 7 | S 8 | | | | | | |
| S 18 | S 17 | | | | | | |
| | 2003 | | | | | | |
| | Deposit a magnet in a white plastic case at the base of the stainless steel post. | | | | | | |
| | Land, rolling, rugged and broken. Soil, sandy and rocky clay. Timber, piñon and juniper; undergrowth, brush and native grasses. | | | | | | |
| | From the cor. of secs. 8, 9, 16 and 17. | | | | | | |
| | S. 89°59' W., bet. secs. 8 and 17. | | | | | | |
| | Over rugged and broken land, along the N. rim of Kinlichee Creek canyon. | | | | | | |
| 4.10 | N. rim of Kinlichee Creek canyon, a sandstone ledge, bears SE and NW, thence descend into the canyon. | | | | | | |
| 27.90 | N. rim of Kinlichee Creek canyon, a sandstone ledge, bears NE and SW. | | | | | | |
| 40.00 | Point for the 1/4 sec. cor. of secs. 8 and 17. | | | | | | |
| | Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd. | | | | | | |

**Survey of the Subdivisional Lines,
T. 27 N., R. 28 E., Gila and Salt River Meridian, Arizona**

| FEET | |
|-------|---|
| | T 27 N R 28 E S 8 1/4 ——— S 17 2003 |
| | Deposit a magnet in a white plastic case at the base of the stainless steel post. |
| 55.80 | E. rim of Ruin Wash canyon, a sandstone ledge, bears SSE and NNW, thence across the canyon. |
| 69.60 | W. rim of Ruin Wash canyon, a sandstone ledge, bears SE and NW, thence over rolling land. |
| 80.00 | The cor. of secs. 7, 8, 17 and 18. Land, rugged and broken to rolling. Soil, sandy and rocky clay with sandstone outcrops. Timber, scattered ponderosa pine, piñon, juniper and Gambel's oak; undergrowth, brush and native grasses. |
| | _____ |
| | S. 89°59' W., bet. secs. 7 and 18. |
| | Over rolling land. |
| 40.00 | Point for the 1/4 sec. cor. of secs. 7 and 18. Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd. |
| | T 27 N R 28 E S 7 1/4 ——— S 18 2003 |
| | Deposit a magnet in a white plastic case at the base of the stainless steel post. |
| 79.37 | The cor. of secs. 7, 12, 13 and 18, on the W. bdy. of the Tp., monumented with a stainless steel post, 2 1/2 ins. diam., with brass cap, set and mkd., as described in the field notes of the survey of the E. bdy., T. 27 N., R. 27 E., executed concurrently under this same group. |

Survey of the Subdivisional Lines,
T. 27 N., R. 28 E., Gila and Salt River Meridian, Arizona

| FEET | |
|-------|---|
| | <p>Land, rolling. Soil, sandy clay. Timber, piñon and juniper; undergrowth, brush and native grasses.</p> <hr/> <p>From the cor. of secs. 7, 8, 17 and 18. N. 0°03' W., bet. secs. 7 and 8. Over rolling land.</p> |
| 40.00 | <p>Point for the 1/4 sec. cor. of secs. 7 and 8. Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T 27 N R 28 E 1/4 S 7 S 8 2003</p> <p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p> |
| 73.60 | <p>Navajo Route 203, a graded road, 20 ft. wide, bears ESE and WNW.</p> |
| 80.00 | <p>Point for the cor. of secs. 5, 6, 7 and 8. Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T 27 N R 28 E S 6 S 5 S 7 S 8 2003</p> <p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p> <p>Land, rolling. Soil, sandy clay. Timber, piñon and juniper; undergrowth, brush and native grasses.</p> <hr/> <p>From the cor. of secs. 4, 5, 8 and 9. S. 89°59' W., bet. secs. 5 and 8. Over rolling and broken land.</p> |

**Survey of the Subdivisional Lines,
T. 27 N., R. 28 E., Gila and Salt River Meridian, Arizona**

| FEET | |
|-------|--|
| 34.60 | E. bank of Ruin Wash, 10 ft. high, bears NE and SW. |
| 36.40 | W. bank of Ruin Wash, 15 ft. high, bears NNE and SSW. |
| 37.25 | Navajo Route 203, a graded road, 20 ft. wide, bears NNE and SSW. |
| 38.85 | Navajo Route 203, a graded road, 20 ft. wide, bears NE and SW. |
| 40.00 | Point for the 1/4 sec. cor. of secs. 5 and 8. Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 20 ins. in the ground, in a mound of stone, 2 ft. base, to top, with brass cap mkd. <div style="text-align: center;"> T 27 N R 28 E S 5 1/4 ——— S 8 2003 </div> |
| 80.00 | Deposit a magnet in a white plastic case at the base of the stainless steel post. The cor. of secs. 5, 6, 7 and 8. Land, rolling and broken. Soil, sandy and rocky clay with sandstone outcrops. Timber, piñon and juniper; undergrowth, brush and native grasses. <hr/> S. 89°59' W., bet. secs. 6 and 7. Over rolling land. |
| 30.50 | Navajo Route 203, a graded road, 20 ft. wide, bears ESE and WNW. |
| 40.00 | Point for the 1/4 sec. cor. of secs. 6 and 7. Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd. <div style="text-align: center;"> T 27 N R 28 E S 6 1/4 ——— S 7 2003 </div> |
| | Deposit a magnet in a white plastic case at the base of the stainless steel post. |

Survey of the Subdivisional Lines,
T. 27 N., R. 28 E., Gila and Salt River Meridian, Arizona

| FEET | |
|-------|---|
| 79.28 | <p>The cor. of secs. 1, 6, 7 and 12, on the W. bdy. of the Tp., monumented with a stainless steel post, 2 1/2 ins. diam., with brass cap, set and mkd., as described in the field notes of the survey of the E. bdy., T. 27 N., R. 27 E., executed concurrently under this same group.</p> <p>Land, rolling. Soil, sandy clay. Timber, piñon and juniper; undergrowth, brush and native grasses.</p> <hr/> <p>From the cor. of secs. 5, 6, 7 and 8.</p> <p>N. 0°03' W., bet. secs. 5 and 6.</p> <p>Over rolling land.</p> |
| 39.50 | Trail road, bears NNE and SSW. |
| 40.00 | <p>Point for the 1/4 sec. cor. of secs. 5 and 6.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T 27 N R 28 E 1/4 S 6 S 5 2003</p> <p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p> |
| 74.60 | Apache County Road C423, a graded road, 20 ft. wide, bears ENE and WSW. |
| 80.00 | <p>The cor. of secs. 5, 6, 31 and 32, on the N. bdy. of the Tp., hereinbefore described.</p> <p>Land, rolling. Soil, sandy clay. Timber, piñon and juniper; undergrowth, brush and native grasses.</p> <hr/> |

Tps. 26 and 27 N., R. 28 E., Gila and Salt River Meridian, Arizona

FEET

GENERAL DESCRIPTION

The area surveyed is about 3 miles E. of Kinlichee, Arizona, within the Navajo Indian Reservation. The terrain is mostly rolling with rocky canyons. The main drainage is Kinlichee Creek, which drains westerly through the south and central portions of the township.

The elevation varies from 6800 to 7500 feet above sea level. The soil is mostly sandy and rocky clay with sandstone ledges and outcrops. The timber consists of ponderosa pine, piñon, juniper and Gambel's oak. The undergrowth consists of sagebrush, cacti, greasewood and native grasses.

Principal access to the area is Arizona State Highway 264, which enters the township in section 36 and exists in section 30. From this highway, Apache County Road C324 and Navajo Route 203, graded roads, branch off providing access to the southerly portion of the township. Apache County Road C423 and Navajo Route 203, graded roads, provide access to the northwest portion of the township. Much of the area is utilized for grazing livestock. There is no mining activity in the township.

The mean magnetic declination of $11\ 1/2^\circ$ E. was derived from the computer program GEOMAGIX utilizing the World Magnetic Model for Epoch 2000 for the dates of survey.

CERTIFICATE OF SURVEY

I, Leonard R. Sandoval, Cadastral Surveyor, HEREBY CERTIFY upon honor, that in pursuance of special instructions bearing date of the 6th day of May, 2003, I have dependently resurveyed the north boundary, T. 26 N., R. 28 E., and surveyed the Seventh Guide Meridian East (east boundary), the north boundary, the latitudinal governing section line and the subdivisional lines, T. 27 N., R. 28 E., of the Gila and Salt River Meridian, in the State of Arizona, which are represented in the foregoing field notes as having been executed by me and under my direction. Said survey has been made in strict conformity with said special instructions, the Manual of Instructions for the Survey of the Public Lands of the United States, 1973 and in specific manner described in the foregoing field notes.

7-18-05

(Date)

Leonard R. Sandoval
(Cadastral Surveyor)

CERTIFICATE OF APPROVAL

BUREAU OF LAND MANAGEMENT
Phoenix, Arizona

The foregoing field notes of the dependent resurvey of the north boundary, T. 26 N., R. 28 E., and the survey of the Seventh Guide Meridian East (east boundary), the north boundary, the latitudinal governing section line and the subdivisional lines, T. 27 N., R. 28 E., Gila and Salt River Meridian, in the State of Arizona, executed by Leonard R. Sandoval, Cadastral Surveyor, having been critically examined and found correct, are hereby approved.

8/17/05

(Date)

Stephen K. Hansen
(Acting Chief Cadastral Surveyor of Arizona)

~~CERTIFICATE OF TRANSCRIPT~~

~~I CERTIFY That the foregoing transcript of the field notes of the above described surveys in Tps. 26 and 27 N., R. 28 E., Gila and Salt River Meridian, Arizona, is a true copy of the original field notes.~~

~~(Date)~~

~~(Acting Chief Cadastral Surveyor of Arizona)~~