

ORIGINAL

**UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT**

FIELD NOTES
OF THE
SURVEY OF
THE SIXTH GUIDE MERIDIAN EAST (EAST BOUNDARY),
THE SOUTH AND WEST BOUNDARIES
AND
THE SUBDIVISIONAL LINES,
TOWNSHIP 24 NORTH, RANGE 24 EAST,
OF THE GILA AND SALT RIVER MERIDIAN,
IN THE STATE OF ARIZONA

EXECUTED BY

Leonard R. Sandoval, Cadastral Surveyor

Under Special Instructions dated and approved May 24, 2004, which provided for the surveys included under Group No. 925, and assignment instructions dated May 24, 2004.

Survey commenced October 18, 2004

Survey completed January 12, 2005

INDEX DIAGRAM

TOWNSHIP 24 NORTH RANGE 24 EAST
 GILA & SALT RIVER MERIDIAN, ARIZONA

72 22 6	71 69 5	58 57 4	50 48 3	41 40 2	32 31 1 9
69 21 7	68 67 8	57 56 9	48 47 10	39 38 11	31 30 12 9
67 20 18	66 65 17	55 54 16	46 46 15	38 37 14	29 28 13 8
65 19 19	64 63 20	54 53 21	45 44 22	37 36 23	28 27 24 7
63 18 30	62 61 29	52 51 28	44 43 27	35 34 26	26 25 25 6
61 17 31 15	60 59 32 14	51 50 33 13	42 41 34 13	34 33 35 12	24 24 36 4 11

T. 24 N., R. 24 E., Gila and Salt River Meridian, Arizona

CHAINS

The following field notes describe the survey of the Sixth Guide Meridian East (east boundary), the south and west boundaries and the subdivisional lines, Township 24 North, Range 24 East, Gila and Salt River Meridian, Arizona.

The history of surveys pertaining to this survey is as follows:

Frank Follman in 1882 surveyed the Sixth Auxiliary Meridian through Township 22 North, and the north boundary of Township 22 North, Range 24 East. In 1883 Follman surveyed the Sixth Standard Parallel North through Ranges 23 and 24 East. Jones Curtiss dependently resurveyed the Sixth Standard Parallel North for the south boundary of Townships 25 North, Ranges 23 and 24 East in 2001-02.

The survey was executed in accordance with the specifications as set forth in the Manual of Instructions for the Survey of the Public Lands of the United States, 1973, and the Special Instructions dated May 24, 2004, for Group No. 925, Arizona.

The true meridian direction and length of all lines were determined by real time kinematic global positioning system observations using Trimble Navigation 5700 model receivers.

Preliminary to the resurvey, the lines of the prior surveys were retraced and search was made for all corners and other calls of record. Identified corners were remonumented in their original positions. Lost corners were reestablished and remonumented at proportionate positions based on the official record. The retracement data were thoroughly verified and only the true line field notes are given herein.

Geodetic control was derived from Global Positioning System (GPS) static observations post processed by National Geodetic Survey, Online Positioning User Service (OPUS), utilizing Continuously Operating Reference Stations (CORS) FERNO MESA CORS ARP, GILA COUNTY CORPS ARP, FLAGSTAFF 1 CORS ARP and AZTEC CORS ARP. The NAD 83 (CORS96) (EPOCH: 2002) geographic position of the southeast corner of township, is as follows:

Latitude: 35°25'52.52" N. Longitude: 109°44'17.05" W.

The mean magnetic declination is 11 1/2° E.

**Survey of the Sixth Guide Meridian East (East Boundary),
T. 24 N., R. 24 E., Gila and Salt River Meridian, Arizona**

CHAINS

Beginning at the cor. of Tps. 23 and 24 N., Rs. 24 and 25 E., established at a point on the Sixth Guide Meridian East geodetically determined to be North, 480.00 chs. dist. from the cor. of Tps. 22 and 23 N., Rs. 24 and 25 E.

Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.

T 24 N	
R 24 E	R 25 E
S 36	S 31
S 1	S 6
T 23 N	

2004

Deposit a magnet in a white plastic case at the base of the stainless steel post.

From this cor. point, the cor. of Tps. 22 and 23 N., Rs. 24 and 25 E., bears South, 480.00 chs. dist., determined at proportionate dist. longitudinal and record dist. latitudinal; there is no remaining evidence of the original cor.

Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.

T 23 N	
R 24 E	R 25 E
S 36	S 31
S 1	S 6
T 22 N	

2004

Deposit a magnet in a white plastic case at the base of the stainless steel post.

From this cor. of Tps. 22 and 23 N., Rs. 24 and 25 E., the cor. of Tps. 22 and 23 N., Rs. 25 and 26 E., bears N. 89°17' E., 479.92 chs. dist., monumented with a stainless steel post, 2 1/2 ins. diam., firmly set, projecting 4 ins. above ground, in collar of stone, with brass cap mkd. T23N R25E R26E S36 S31 S1 S6 T22N 2002. Add the marks 2004 to the brass cap.

**Survey of the Sixth Guide Meridian East (East Boundary),
T. 24 N., R. 24 E., Gila and Salt River Meridian, Arizona**

CHAINS	
	<p>From this same cor. of Tps. 22 and 23 N., Rs. 24 and 25 E., the stan. cor. of T. 21 N., Rs. 24 and 25 E., bears S. 0°12' W., 960.00 chs. dist., monumented with an iron post, 3 ins. diam., firmly set, projecting 9 ins. above ground, witnessed by a mound of stone, 3 ft. base, 6 ins. high to the N., with brass cap mkd. SC T21N R24E R25E S36 S31 T20N R24E S1 PFM 1938.</p> <p>From this same cor. of Tps. 22 and 23 N., Rs. 24 and 25 E., the cor. of Tps. 22 and 23 N., Rs. 21 and 22 E., bears S. 89°56' W., 1432.29 chs. dist., monumented with a stainless steel post, 2 1/2 ins. diam., firmly set, projecting 2 ins. above ground, witnessed by a mound of stone, 3 ft. base, 1 1/2 ft. high, to the S., with brass cap mkd. T23N R21E R22E S36 S31 S1 S6 T22N 2004.</p> <p>These control lines were fully retraced and careful search was made for evidence of intervening cors., none of which was recovered.</p> <p>North, bet. secs. 31 and 36.</p> <p>Over rolling and broken land.</p>
6.00	Trail road, bears S. 80° W. and N. 80° E.
14.70	Wash, 30 ft. wide, 6 ft. deep, drains N. 30° W.
40.00	Point for the 1/4 sec. cor. of secs. 31 and 36.
	<p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;"> T 24 N 1/4 R 24 E R 25 E S 36 S 31 2004 </p> <p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p>
80.00	<p>Point for the cor. of secs. 25, 30, 31, and 36.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p>

**Survey of the Sixth Guide Meridian East (East Boundary),
T. 24 N., R. 24 E., Gila and Salt River Meridian, Arizona**

CHAINS

T 24 N	
R 24 E	R 25 E
S 25	S 30
S 36	S 31

2004

Deposit a magnet in a white plastic case at the base of the stainless steel post.

Land, rolling and broken.

Soil, rocky and sandy clay.

Timber, scattered juniper; undergrowth, greasewood, scattered brush and native grasses.

North, bet. secs. 25 and 30.

Over rolling and broken land.

- 3.05 Top of a ridge, bears N. 80° E. and S. 80° W.
- 38.55 Trail road, bears N. 40° E. and S. 40° W.
- 40.00 Point for the 1/4 sec. cor. of secs. 25 and 30.
- Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.

T 24 N	
1/4	
R 24 E	R 25 E
S 25	S 30

2004

Deposit a magnet in a white plastic case at the base of the stainless steel post.

- 55.60 Navajo Route 9606, a graded road, 36 ft. wide, bears S. 75° E. and N. 75° W.
- 80.00 Point for the cor. of secs. 19, 24, 25, and 30.

Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.

**Survey of the Sixth Guide Meridian East (East Boundary),
T. 24 N., R. 24 E., Gila and Salt River Meridian, Arizona**

CHAINS									
	<table border="1"> <tr><td align="center" colspan="2">T 24 N</td></tr> <tr><td align="center">R 24 E</td><td align="center">R 25 E</td></tr> <tr><td align="center">S 24</td><td align="center">S 19</td></tr> <tr><td align="center">S 25</td><td align="center">S 30</td></tr> </table>	T 24 N		R 24 E	R 25 E	S 24	S 19	S 25	S 30
T 24 N									
R 24 E	R 25 E								
S 24	S 19								
S 25	S 30								
	2004								
	Deposit a magnet in a white plastic case at the base of the stainless steel post.								
	Land, rolling and broken. Soil, rocky and sandy clay. Timber, scattered juniper; undergrowth, greasewood, scattered brush and native grasses.								

	North, bet. secs. 19 and 24.								
	Over rolling land.								
40.00	Point for the 1/4 sec. cor. of secs. 19 and 24.								
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.								
	<table border="1"> <tr><td align="center" colspan="2">T 24 N</td></tr> <tr><td align="center" colspan="2">1/4</td></tr> <tr><td align="center">R 24 E</td><td align="center">R 25 E</td></tr> <tr><td align="center">S 24</td><td align="center">S 19</td></tr> </table>	T 24 N		1/4		R 24 E	R 25 E	S 24	S 19
T 24 N									
1/4									
R 24 E	R 25 E								
S 24	S 19								
	2004								
	Deposit a magnet in a white plastic case at the base of the stainless steel post.								
41.05	Trail road, bears N. 55° E. and S. 55° W.								
49.00	High Voltage transmission line, bears N. 40° E. and S. 40° W.								
80.00	Point for the cor. of secs. 13, 18, 19, and 24.								
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.								
	<table border="1"> <tr><td align="center" colspan="2">T 24 N</td></tr> <tr><td align="center">R 24 E</td><td align="center">R 25 E</td></tr> <tr><td align="center">S 13</td><td align="center">S 18</td></tr> <tr><td align="center">S 24</td><td align="center">S 19</td></tr> </table>	T 24 N		R 24 E	R 25 E	S 13	S 18	S 24	S 19
T 24 N									
R 24 E	R 25 E								
S 13	S 18								
S 24	S 19								
	2004								

**Survey of the Sixth Guide Meridian East (East Boundary),
T. 24 N., R. 24 E., Gila and Salt River Meridian, Arizona**

CHAINS	
	<p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p> <p>Land, rolling. Soil, rocky and sandy clay. Timber, scattered juniper; undergrowth, greasewood, scattered brush and native grasses.</p> <hr/> <p>North, bet. secs. 13 and 18.</p> <p>Over rolling and broken land.</p>
11.00	Underground gas pipeline, bears N. 70° E. and S. 70° W.
11.80	Underground gas pipeline, bears N. 70° E. and S. 70° W.
40.00	<p>Point for the 1/4 sec. cor. of secs. 13 and 18.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center;"> <p>T 24 N 1/4 R 24 E R 25 E S 13 S 18</p> <p>2004</p> </div> <p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p>
80.00	<p>Point for the cor. of secs. 7, 12, 13, and 18.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center;"> <p>T 24 N R 24 E R 25 E S 12 S 7 <hr/>S 13 S 18</p> <p>2004</p> </div> <p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p> <p>Cor. is located 14 1/2 lks. S. of barbed wired fence, 4 strands, bears S. 50° E. and N. 50° W.</p>

**Survey of the Sixth Guide Meridian East (East Boundary),
T. 24 N., R. 24 E., Gila and Salt River Meridian, Arizona**

CHAINS											
	<p>Land, rolling. Soil, rocky and sandy clay. Timber, scattered juniper; undergrowth, greasewood, scattered brush and native grasses.</p> <hr/> <p>North, bet. secs. 7 and 12.</p> <p>Over rolling and broken land.</p>										
24.51	Barb wire fence, 5 strands, bears N. 40° E. and S. 40° W.										
37.50	Wash, 12 ft. wide, 6 ft. deep, drains N. 75° W.										
40.00	Point for the 1/4 sec. cor. of secs. 7 and 12.										
	<p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center;"> <table style="margin: auto;"> <tr><td colspan="2">T 24 N</td></tr> <tr><td colspan="2">1/4</td></tr> <tr><td>R 24 E</td><td> R 25 E</td></tr> <tr><td>S 12</td><td> S 7</td></tr> </table> <p>2004</p> </div> <p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p>	T 24 N		1/4		R 24 E	R 25 E	S 12	S 7		
T 24 N											
1/4											
R 24 E	R 25 E										
S 12	S 7										
80.00	Point for the cor. of secs. 1, 6, 7, and 12.										
	<p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center;"> <table style="margin: auto;"> <tr><td colspan="2">T 24 N</td></tr> <tr><td>R 24 E</td><td> R 25 E</td></tr> <tr><td>S 1</td><td> S 6</td></tr> <tr><td colspan="2"><hr/></td></tr> <tr><td>S 12</td><td> S 7</td></tr> </table> <p>2004</p> </div> <p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p> <p>Land, rolling and broken. Soil, rocky and sandy clay. Timber, juniper; undergrowth, greasewood, scattered brush and native grasses.</p> <hr/> <p>North, bet. secs. 1 and 6.</p>	T 24 N		R 24 E	R 25 E	S 1	S 6	<hr/>		S 12	S 7
T 24 N											
R 24 E	R 25 E										
S 1	S 6										
<hr/>											
S 12	S 7										

**Survey of the Sixth Guide Meridian East (East Boundary),
T. 24 N., R. 24 E., Gila and Salt River Meridian, Arizona**

CHAINS	
	Over rolling and broken land.
40.00	Point for the 1/4 sec. cor. of secs. 1 and 6.
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.
	<p align="center">T 24 N 1/4 R 24 E R 25 E S 1 S 6</p>
	<p align="center">2004</p>
	Deposit a magnet in a white plastic case at the base of the stainless steel post.
66.35	Navajo Route 28, a graded road, 30 ft. wide, bears N. 85° E. and S. 85° W.
77.30	Point for the closing cor. of T. 24 N., Rs. 24 and 25 E., at intersection with the Sixth Standard Parallel North, on the N. bdy. of the Tp.
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.
	<p align="center">T 25 N R 24 E S 35 ----- S 1 S 6 R 24 E R 25 E C C T 24 N</p>
	<p align="center">2004</p>
	Deposit a magnet in a white plastic case at the base of the stainless steel post.
	From this cor. point, the stan. cor. of secs. 35 and 36, T. 25 N., R. 24 E., bears S. 89°55' E., 72 lks. dist., monumented with a stainless steel post, 2 1/2 ins. diam., firmly set, projecting 4 ins. above ground with brass cap mkd. SC T25N R24E S35 S36 2001.
	From this same cor. point, the stan. 1/4 sec. cor. of sec. 35, T. 25 N., R. 24 E., bears N. 89°55' W., 39.45 chs. dist., monumented with a stainless steel post, 2 1/2 ins. diam., firmly set, projecting 4 ins. above ground with brass cap mkd. SC T25N R24E 1/4 S35 2001.

**Survey of the Sixth Guide Meridian East (East Boundary),
T. 24 N., R. 24 E., Gila and Salt River Meridian, Arizona**

CHAINS	
	<p>Land, rolling and broken. Soil, rocky and sandy clay. Timber, juniper; undergrowth, greasewood, scattered brush and native grasses.</p> <hr/> <p style="text-align: center;">Survey of the South Boundary, T. 24 N., R. 24 E., Gila and Salt River Meridian, Arizona</p> <hr/> <p>From the cor. of Tps. 23 and 24 N., Rs. 24 and 25 E., hereinbefore described.</p> <p>N. 89°58' W., bet. secs. 1 and 36.</p> <p>Over rolling and broken land.</p>
6.60	Trail road, bears S. 5° E. and N. 5° W.
34.50	Wash, 40 ft. wide, 10 ft. deep, drains S. 15° W.
40.00	Point for the 1/4 sec. cor. of secs. 1 and 36.
	<p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center;"> <p>T 24 N R 24 E S 36 1/4 ——— S 1 T 23 N</p> <p>2004</p> </div> <p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p>
78.80	Top of ridge, bears N. 10° E. and S. 10° W.
80.00	Point for the cor. of secs. 1, 2, 35, and 36.
	<p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center;"> <p>T 24 N R 24 E S 35 S 36 S 2 S 1 T 23 N</p> <p>2004</p> </div>

**Survey of the South Boundary,
T. 24 N., R. 24 E., Gila and Salt River Meridian, Arizona**

CHAINS					
	<p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p> <p>Land, rolling and broken. Soil, rocky and sandy clay. Timber, scattered juniper; undergrowth, greasewood, scattered brush and native grasses.</p> <hr/> <p>N. 89°58' W., bet. secs. 2 and 35.</p> <p>Over rolling and broken land.</p>				
33.90	E. rim of mesa, bears S. 30° E. and N. 30° W.				
40.00	<p>Point for the 1/4 sec. cor. of secs. 2 and 35.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center; padding: 10px 0;"> <p>T 24 N R 24 E</p> <p>S 35</p> <p>1/4 ———</p> <p>S 2</p> <p>T 23 N</p> <p>2004</p> </div>				
	<p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p>				
45.05	Trail road, bears S. 20° E. and N. 20° W.				
58.25	Trail road, bears N. 50° E. and S. 50° W.				
69.30	Rim of mesa, bears N. 70° E. and S. 70° W.				
80.00	<p>Point for the cor. of secs. 2, 3, 34, and 35.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center; padding: 10px 0;"> <p>T 24 N R 24 E</p> <table style="margin: auto; border-collapse: collapse;"> <tr> <td style="border-right: 1px solid black; padding: 0 5px;">S 34</td> <td style="padding: 0 5px;">S 35</td> </tr> <tr> <td style="border-right: 1px solid black; padding: 0 5px;">S 3</td> <td style="padding: 0 5px;">S 2</td> </tr> </table> <p>T 23 N</p> <p>2004</p> </div>	S 34	S 35	S 3	S 2
S 34	S 35				
S 3	S 2				
	<p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p>				

**Survey of the South Boundary,
T. 24 N., R. 24 E., Gila and Salt River Meridian, Arizona**

CHAINS											
	<p>Land, rolling and broken. Soil, rocky and sandy clay. Timber, scattered juniper; undergrowth, greasewood, scattered brush and native grasses.</p> <hr/> <p>N. 89°58' W., bet. secs. 3 and 34.</p> <p>Over rolling and broken land.</p>										
31.72	High Voltage transmission line, bears N. 40° E. and S. 40° W.										
40.00	<p>Point for the 1/4 sec. cor. of secs. 3 and 34.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center; margin: 10px 0;"> <table style="margin: auto;"> <tr><td>T 24 N</td><td>R 24 E</td></tr> <tr><td></td><td>S 34</td></tr> <tr><td>1/4</td><td>—</td></tr> <tr><td></td><td>S 3</td></tr> <tr><td>T 23 N</td><td></td></tr> </table> <p>2004</p> </div> <p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p>	T 24 N	R 24 E		S 34	1/4	—		S 3	T 23 N	
T 24 N	R 24 E										
	S 34										
1/4	—										
	S 3										
T 23 N											
80.00	<p>Point for the cor. of secs. 3, 4, 33, and 34.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center; margin: 10px 0;"> <table style="margin: auto;"> <tr><td>T 24 N</td><td>R 24 E</td></tr> <tr><td>S 33</td><td>S 34</td></tr> <tr><td>S 4</td><td>S 3</td></tr> <tr><td>T 23 N</td><td></td></tr> </table> <p>2004</p> </div> <p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p> <p>Land, rolling and broken. Soil, rocky and sandy clay. Timber, scattered juniper; undergrowth, greasewood, scattered brush and native grasses.</p> <hr/> <p>N. 89°58' W., bet. secs. 4 and 33.</p> <p>Over rolling and broken land.</p>	T 24 N	R 24 E	S 33	S 34	S 4	S 3	T 23 N			
T 24 N	R 24 E										
S 33	S 34										
S 4	S 3										
T 23 N											

**Survey of the South Boundary,
T. 24 N., R. 24 E., Gila and Salt River Meridian, Arizona**

CHAINS	
36.85	Wash, 20 ft. wide, 3 ft. deep, drains S. 60° W.
40.00	Point for the 1/4 sec. cor. of secs. 4 and 33. Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd. <div style="text-align: center;"> T 24 N R 24 E S 33 1/4 ——— S 4 T 23 N 2004 </div> Deposit a magnet in a white plastic case at the base of the stainless steel post.
80.00	Point for the cor. of secs. 4, 5, 32, and 33. Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd. <div style="text-align: center;"> T 24 N R 24 E S 32 S 33 S 5 S 4 T 23 N 2004 </div> Deposit a magnet in a white plastic case at the base of the stainless steel post. Land, rolling and broken. Soil, rocky and sandy clay. No timber; undergrowth, greasewood, scattered brush and native grasses.
40.00	<hr/> N. 89°58' W., bet. secs. 5 and 32. Over rolling and broken land. Point for the 1/4 sec. cor. of secs. 5 and 32. Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.

**Survey of the South Boundary,
T. 24 N., R. 24 E., Gila and Salt River Meridian, Arizona**

CHAINS	
	T 24 N R 24 E S 32 1/4 ——— S 5 T 23 N 2004
	Deposit a magnet in a white plastic case at the base of the stainless steel post.
71.20	Navajo Route 9003, a graded road, 19 ft. wide, bears S. 40° E. and N. 40° W.
80.00	Point for the cor. of secs. 5, 6, 31, and 32.
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.
	T 24 N R 24 E S 31 S 32 ——— ——— S 6 S 5 T 23 N 2004
	Deposit a magnet in a white plastic case at the base of the stainless steel post.
	Land, rolling and broken. Soil, rocky and sandy clay. No timber; undergrowth, greasewood, scattered brush and native grasses.

	N. 89°58' W., bet. secs. 6 and 31.
	Over rolling and broken land.
9.73	High voltage transmission line, bears N. 30° E. and S. 30° W.
12.16	Barbed wire fence, 5 strands, bears N. 30° E. and S. 30° W.
40.00	Point for the 1/4 sec. cor. of secs. 6 and 31.
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.

**Survey of the South Boundary,
T. 24 N., R. 24 E., Gila and Salt River Meridian, Arizona**

CHAINS

T 24 N R 24 E
S 31
1/4 ———
S 6
T 23 N

2004

Deposit a magnet in a white plastic case at the base of the stainless steel post.

76.36

Point for the cor. of Tps. 23 and 24 N., Rs. 23 and 24 E., determined geodetically North, 480.00 chs. from the cor. of Tps. 22 and 23 N., Rs. 23 and 24 E.

Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.

T 24 N
R 23 E | R 24 E
S 36 | S 31
S 1 | S 6
T 23 N

2004

Deposit a magnet in a white plastic case at the base of the stainless steel post.

From this cor. point, the cor. of Tps. 22 and 23 N., Rs. 23 and 24 E., bears South, 480.00 chs. dist., determined at proportionate dist. longitudinal and record dist. latitudinal; there is no remaining evidence of the original cor.

Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.

T 23 N
R 23 E | R 24 E
S 36 | S 31
S 1 | S 6
T 22 N

2004

Deposit a magnet in a white plastic case at the base of the stainless steel post.

From this cor. of Tps. 22 and 23 N., Rs. 23 and 24 E., the cor. of Tps. 22 and 23 N., Rs. 24 and 25 E., bears S. 89°58' E., 476.87 chs. dist., hereinbefore described.

**Survey of the South Boundary,
T. 24 N., R. 24 E., Gila and Salt River Meridian, Arizona**

CHAINS

From this same cor. of Tps. 22 and 23 N., Rs. 23 and 24 E., the stan. cor. of T. 21 N., Rs. 23 and 24 E., bears S. 0°03' W., 960.00 chs. dist., monumented with an iron post, 3 ins. diam., firmly set, projecting 9 ins. above ground with brass cap mkd. SC T21N R23E R24E S36 S31 T20N R23E S1 PFM 1938.

From this same cor. of Tps. 22 and 23 N., Rs. 23 and 24 E., the cor. of Tps. 22 and 23 N., Rs. 21 and 22 E., bears S. 89°53' W., 955.43 chs. dist., monumented with a stainless steel post, 2 1/2 ins. diam., firmly set, projecting 2 ins. above ground, witnessed by a mound of stone, 3 ft. base, 1 1/2 ft. high, to the S., with brass cap mkd. T23N R21E R22E S36 S31 S1 S6 T22N 2004.

These control lines were fully retraced and careful search was made for evidence of intervening cors., none of which was recovered.

Land, rolling and broken.
Soil, rocky and sandy clay.
No timber; undergrowth, greasewood, scattered brush and native grasses.

**Survey of the West Boundary,
T. 24 N., R. 24 E., Gila and Salt River Meridian, Arizona**

From the cor. of Tps. 23 and 24 N., Rs. 23 and 24 E., hereinbefore described.

North, bet. secs. 31 and 36.

Over rolling land.

40.00 Point for the 1/4 sec. cor. of secs. 31 and 36.

Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.

T 24 N
1/4
R 23 E | R 24 E
S 36 | S 31

2004

Deposit a magnet in a white plastic case at the base of the stainless steel post.

62.23 Barbed wire fence, 5 strands, bears S. 45° E. and N. 45° W.

**Survey of the West Boundary,
T. 24 N., R. 24 E., Gila and Salt River Meridian, Arizona**

CHAINS									
63.40	Trail road, bears N. 25° E. and S. 25° W.								
80.00	Point for the cor. of secs. 25, 30, 31, and 36. Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd. <div style="text-align: center;"> <table border="1"> <tr><td colspan="2">T 24 N</td></tr> <tr><td>R 23 E</td><td>R 24 E</td></tr> <tr><td>S 25</td><td>S 30</td></tr> <tr><td>S 36</td><td>S 31</td></tr> </table> <p>2004</p> </div> <p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p> <p>Land, rolling. Soil, sandy clay. No timber; undergrowth, greasewood, scattered brush and native grasses.</p> <hr/> <p>North, bet. secs. 25 and 30.</p> <p>Over rolling land.</p>	T 24 N		R 23 E	R 24 E	S 25	S 30	S 36	S 31
T 24 N									
R 23 E	R 24 E								
S 25	S 30								
S 36	S 31								
40.00	Point for the 1/4 sec. cor. of secs. 25 and 30. Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd. <div style="text-align: center;"> <table border="1"> <tr><td colspan="2">T 24 N</td></tr> <tr><td colspan="2">1/4</td></tr> <tr><td>R 23 E</td><td>R 24 E</td></tr> <tr><td>S 25</td><td>S 30</td></tr> </table> <p>2004</p> </div> <p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p>	T 24 N		1/4		R 23 E	R 24 E	S 25	S 30
T 24 N									
1/4									
R 23 E	R 24 E								
S 25	S 30								
80.00	Point for the cor. of secs. 19, 24, 25, and 30. Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.								

**Survey of the West Boundary,
T. 24 N., R. 24 E., Gila and Salt River Meridian, Arizona**

CHAINS									
	<table style="margin: auto;"> <tr><td colspan="2" style="text-align: center;">T 24 N</td></tr> <tr><td style="text-align: center;">R 23 E</td><td style="text-align: center;">R 24 E</td></tr> <tr><td style="text-align: center;">S 24</td><td style="text-align: center;">S 19</td></tr> <tr><td style="text-align: center;">S 25</td><td style="text-align: center;">S 30</td></tr> </table>	T 24 N		R 23 E	R 24 E	S 24	S 19	S 25	S 30
T 24 N									
R 23 E	R 24 E								
S 24	S 19								
S 25	S 30								
	2004								
	Deposit a magnet in a white plastic case at the base of the stainless steel post.								
	Land, rolling. Soil, sandy clay. No timber; undergrowth, greasewood, scattered brush and native grasses.								
	North, bet. secs. 19 and 24.								
	Over rolling land.								
40.00	Point for the 1/4 sec. cor. of secs. 19 and 24.								
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.								
	<table style="margin: auto;"> <tr><td colspan="2" style="text-align: center;">T 24 N</td></tr> <tr><td colspan="2" style="text-align: center;">1/4</td></tr> <tr><td style="text-align: center;">R 23 E</td><td style="text-align: center;">R 24 E</td></tr> <tr><td style="text-align: center;">S 24</td><td style="text-align: center;">S 19</td></tr> </table>	T 24 N		1/4		R 23 E	R 24 E	S 24	S 19
T 24 N									
1/4									
R 23 E	R 24 E								
S 24	S 19								
	2004								
	Deposit a magnet in a white plastic case at the base of the stainless steel post.								
42.95	Underground gas pipeline, bears E. and W.								
43.70	Underground gas pipeline, bears E. and W.								
80.00	Point for the cor. of secs. 13, 18, 19, and 24.								
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 16 ins. below the surface of the ground, with brass cap mkd.								
	<table style="margin: auto;"> <tr><td colspan="2" style="text-align: center;">T 24 N</td></tr> <tr><td style="text-align: center;">R 23 E</td><td style="text-align: center;">R 24 E</td></tr> <tr><td style="text-align: center;">S 13</td><td style="text-align: center;">S 18</td></tr> <tr><td style="text-align: center;">S 24</td><td style="text-align: center;">S 19</td></tr> </table>	T 24 N		R 23 E	R 24 E	S 13	S 18	S 24	S 19
T 24 N									
R 23 E	R 24 E								
S 13	S 18								
S 24	S 19								
	2004								
	from which								

**Survey of the West Boundary,
T. 24 N., R. 24 E., Gila and Salt River Meridian, Arizona**

CHAINS	
	<p>A stainless steel post, 28 ins. long, 2 1/2 ins. diam., set 24 ins. in the ground for a reference monument, bears N. 60°00' E., 100.0 ft. dist., with brass cap mkd. RM T24N R24E S18 RM 100.0 FT. TO COR. 2004 and an arrow pointing to the cor. Deposit a magnet in a white plastic case at the base of the stainless steel post. Set a steel fence post nearby.</p> <p>A stainless steel post, 28 ins. long, 2 1/2 ins. diam., set 24 ins. in the ground for a reference monument, bears S. 60°00' W., 100.0 ft. dist., with brass cap mkd. RM T24N R24E S24 100.0 FT. TO COR. 2004 and an arrow pointing to the cor. Deposit a magnet in a white plastic case at the base of the stainless steel post. Set a steel fence post nearby.</p> <p>Deposit a magnet in a white plastic case at the base of the stainless steel post at the sec. cor.</p> <p>Cor. is located in Navajo Route 9606, a graded road, 30 ft. wide, bears S. 33° E. and N. 33° W.</p> <p>Land, rolling. Soil, sandy clay. No timber; undergrowth, greasewood, scattered brush and native grasses.</p> <hr/> <p>North, bet. secs. 13 and 18.</p> <p>Over rolling land.</p>
40.00	<p>Point for the 1/4 sec. cor. of secs. 13 and 18.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center;"> <p>T 24 N 1/4 R 23 E R 24 E S 13 S 18</p> <p>2004</p> </div> <p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p>
80.00	<p>Point for the cor. of secs. 7, 12, 13, and 18.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p>

**Survey of the West Boundary,
T. 24 N., R. 24 E., Gila and Salt River Meridian, Arizona**

CHAINS									
	<table style="margin: auto; border-collapse: collapse;"> <tr><td colspan="2" style="text-align: center;">T 24 N</td></tr> <tr><td style="text-align: center;">R 23 E</td><td style="text-align: center;">R 24 E</td></tr> <tr><td style="text-align: center;">S 12</td><td style="text-align: center;">S 7</td></tr> <tr style="border-top: 1px solid black;"><td style="text-align: center;">S 13</td><td style="text-align: center;">S 18</td></tr> </table>	T 24 N		R 23 E	R 24 E	S 12	S 7	S 13	S 18
T 24 N									
R 23 E	R 24 E								
S 12	S 7								
S 13	S 18								
	2004								
	Deposit a magnet in a white plastic case at the base of the stainless steel post.								
	Land, rolling. Soil, sandy clay. No timber; undergrowth, greasewood, scattered brush and native grasses.								
	North, bet. secs. 7 and 12.								
	Over rolling and broken land.								
40.00	Point for the 1/4 sec. cor. of secs. 7 and 12.								
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.								
	<table style="margin: auto; border-collapse: collapse;"> <tr><td colspan="2" style="text-align: center;">T 24 N</td></tr> <tr><td colspan="2" style="text-align: center;">1/4</td></tr> <tr><td style="text-align: center;">R 23 E</td><td style="text-align: center;">R 24 E</td></tr> <tr><td style="text-align: center;">S 12</td><td style="text-align: center;">S 7</td></tr> </table>	T 24 N		1/4		R 23 E	R 24 E	S 12	S 7
T 24 N									
1/4									
R 23 E	R 24 E								
S 12	S 7								
	2004								
	Deposit a magnet in a white plastic case at the base of the stainless steel post.								
80.00	Point for the cor. of secs. 1, 6, 7, and 12.								
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.								
	<table style="margin: auto; border-collapse: collapse;"> <tr><td colspan="2" style="text-align: center;">T 24 N</td></tr> <tr><td style="text-align: center;">R 23 E</td><td style="text-align: center;">R 24 E</td></tr> <tr><td style="text-align: center;">S 1</td><td style="text-align: center;">S 6</td></tr> <tr style="border-top: 1px solid black;"><td style="text-align: center;">S 12</td><td style="text-align: center;">S 7</td></tr> </table>	T 24 N		R 23 E	R 24 E	S 1	S 6	S 12	S 7
T 24 N									
R 23 E	R 24 E								
S 1	S 6								
S 12	S 7								
	2004								
	Deposit a magnet in a white plastic case at the base of the stainless steel post.								

**Survey of the West Boundary,
T. 24 N., R. 24 E., Gila and Salt River Meridian, Arizona**

CHAINS	
	<p>Land, rolling and broken. Soil, sandy clay. No timber; undergrowth, greasewood, scattered brush and native grasses.</p> <hr/> <p>North, bet. secs. 1 and 6.</p> <p>Over rolling land.</p>
5.15	Intersect the southwest side of a wood frame house, 32 x 42 ft., SE cor., bears S. 67° E., 4 1/2 lks. dist., with longside bears N. 23° E.
10.00	Navajo Route 9606, a graded road, 20 ft. wide, bears N. 30° E. and S. 30° W.
11.55	Power line, bears N. 30° E. and S. 30° W.
23.63	Intersect the south side of stucco house, 28 x 34 ft., SW cor., bears N. 73° W., 13 1/2 lks. dist., with long side bears S. 73° E.
40.00	<p>Point for the 1/4 sec. cor. of secs. 1 and 6.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center;"> <p>T 24 N 1/4 R 23 E R 24 E S 1 S 6</p> <p>2004</p> </div> <p>from which</p> <p style="margin-left: 40px;">NW cor. of a sandstone masonry house, 14 x 28 ft., bears S. 31 1/2° E., 1.87 chs. dist., with long side bears S. 29° W.</p> <p style="margin-left: 40px;">SE cor. of a brick house, 24 x 40 ft., bears N. 18 1/2° W., 1.50 chs. dist., with long side bears N. 22 1/2° E.</p> <p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p>
43.38	Intersect S. cor. of an octagonal shaped log hogan, 9 ft. side, bears E. and W.
46.95	Apache County Road C459, a graded road, 25 ft. wide, bears S. 70° E. and N. 70° W.

**Survey of the West Boundary,
T. 24 N., R. 24 E., Gila and Salt River Meridian, Arizona**

CHAINS

77.73

Point for the closing cor. of Tps. 24 N., Rs. 23 and 24 E., at intersection with the Sixth Standard Parallel North, on the N. bdy. of the Tp.

Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.

T 25 N	R 23 E
S 36	
S 1	S 6
R 23 E	R 24 E
C C	
T 24 N	

2004

Deposit a magnet in a white plastic case at the base of the stainless steel post.

From this cor. point, the stan. 1/4 sec. cor. of sec. 36, T. 25 N., R. 23 E., bears S. 89°55' E., 34.71 chs. dist., monumented with a stainless steel post, 2 1/2 ins. diam., firmly set, projecting 4 ins. above ground with brass cap mkd. SC T25N R23E 1/4 S36 2002.

From this same cor. point, a rebar, 5/8 in. diam., firmly set, projecting 2 ins. above ground, bears S. 9°08' E., 7.78 chs. dist., with a yellow plastic cap mkd. NAVAJO COUNTY, witnessed by a galvanized steel fence post with a tag mkd. SURVEY MARKER 520-524-4100. This cor. was established by Navajo County Engineering Office, only to determine an election line between Navajo and Apache counties.

From this same cor. point, the stan. cor. of secs. 35 and 36, T. 25 N., R. 23 E., bears N. 89°55' W., 5.46 chs. dist., monumented with a stainless steel post, 2 1/2 ins. diam., firmly set, projecting 4 ins. above ground with brass cap mkd. SC T25N R23E S35 S36 2002.

Land, rolling.

Soil, sandy clay.

No timber; undergrowth, greasewood, scattered brush and native grasses.

**Survey of the Subdivisional Lines,
T. 24 N., R. 24 E., Gila and Salt River Meridian, Arizona**

CHAINS	
	<p>From the cor. of secs. 1, 2, 35 and 36, on the S. bdy. of the Tp., hereinbefore described.</p> <p>N. 0°01' W., bet. secs. 35 and 36.</p> <p>Over rolling and broken land.</p>
39.00	Top of a ridge, bears N. 85° E. and S. 85° W.
40.00	<p>Point for the 1/4 sec. cor. of secs. 35 and 36.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T 24 N R 24 E 1/4 S 35 S 36</p> <p style="text-align: center;">2005</p> <p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p>
80.00	<p>Point for the cor. of secs. 25, 26, 35, and 36.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T 24 N R 24 E S 26 S 25 S 35 S 36</p> <p style="text-align: center;">2005</p> <p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p> <p>Cor. is located 54 lks. E., of a trail road, bears N. 20° E. and S. 20° W.</p> <p>Land, rolling and broken. Soil, rocky and sandy clay. Timber, scattered juniper; undergrowth, greasewood, scattered brush and native grasses.</p> <hr/> <p>From the cor. of secs. 25, 30, 31, and 36, on the E. bdy. of the Tp., hereinbefore described.</p> <p>N. 89°58' W., bet. secs. 25 and 36.</p> <p>Over rolling and broken land.</p>

**Survey of the Subdivisional Lines,
T. 24 N., R. 24 E., Gila and Salt River Meridian, Arizona**

CHAINS	
40.00	<p>Point for the 1/4 sec. cor. of secs. 25 and 36.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center;"> <p>T 24 N R 24 E S 25 1/4 ——— S 36</p> <p>2005</p> </div> <p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p>
80.00	<p>The cor. of secs. 25, 26, 35, and 36.</p> <p>Land, rolling and broken. Soil, rocky and sandy clay. Timber, scattered juniper; undergrowth, greasewood, scattered brush and native grasses.</p> <hr/> <p>N. 0°01' W., bet. secs. 25 and 26.</p> <p>Over rolling land.</p>
1.30	Trail road, bears N. 25° E. and S. 25° W.
20.65	Trail road, bears N. 25° E. and S. 25° W.
40.00	<p>Point for the 1/4 sec. cor. of secs. 25 and 26.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center;"> <p>T 24 N R 24 E 1/4 S 26 S 25</p> <p>2005</p> </div> <p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p>
41.78	High voltage transmission line, bears N. 45° E. and S. 45° W.
67.00	Navajo Route 9606, a graded road, 36 ft. wide, bears S. 85° E. and N. 85° W.
80.00	Point for the cor. of secs. 23, 24, 25, and 26.

**Survey of the Subdivisional Lines,
T. 24 N., R. 24 E., Gila and Salt River Meridian, Arizona**

CHAINS	<p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p align="center"> <table style="margin-left: auto; margin-right: auto; border-collapse: collapse;"> <tr> <td style="padding: 0 10px;">T 24 N</td> <td style="padding: 0 10px;">R 24 E</td> </tr> <tr> <td style="padding: 0 10px; border-right: 1px solid black;">S 23</td> <td style="padding: 0 10px;">S 24</td> </tr> <tr> <td style="padding: 0 10px; border-right: 1px solid black;">S 26</td> <td style="padding: 0 10px;">S 25</td> </tr> </table> </p> <p align="center">2005</p> <p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p> <p>Cor. is located 1.30 chs. E., of a trail road, bears N. 50° E. and S. 50° W.</p> <p>Land, rolling. Soil, sandy clay. Timber, scattered juniper; undergrowth, greasewood, scattered brush and native grasses.</p> <hr/> <p>From the cor. of secs. 19, 24, 25, and 30, on the E. bdy. of the Tp., hereinbefore described.</p> <p>N. 89°58' W., bet. secs. 24 and 25.</p> <p>Over rolling land.</p>	T 24 N	R 24 E	S 23	S 24	S 26	S 25		
T 24 N	R 24 E								
S 23	S 24								
S 26	S 25								
40.00	<p>Point for the 1/4 sec. cor. of secs. 24 and 25.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p align="center"> <table style="margin-left: auto; margin-right: auto; border-collapse: collapse;"> <tr> <td style="padding: 0 10px;">T 24 N</td> <td style="padding: 0 10px;">R 24 E</td> </tr> <tr> <td style="padding: 0 10px;"></td> <td style="padding: 0 10px;">S 24</td> </tr> <tr> <td style="padding: 0 10px;">1/4</td> <td style="padding: 0 10px; border-top: 1px solid black;">———</td> </tr> <tr> <td style="padding: 0 10px;"></td> <td style="padding: 0 10px;">S 25</td> </tr> </table> </p> <p align="center">2005</p> <p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p>	T 24 N	R 24 E		S 24	1/4	———		S 25
T 24 N	R 24 E								
	S 24								
1/4	———								
	S 25								
44.96	<p>High voltage transmission line, bears N. 45° E. and S. 45° W.</p>								
46.75	<p>Trail road, bears N. 20° E. and S. 20° W.</p>								
80.00	<p>The cor. of secs. 23, 24, 25, and 26.</p>								

**Survey of the Subdivisional Lines,
T. 24 N., R. 24 E., Gila and Salt River Meridian, Arizona**

CHAINS	
	<p>Land, rolling. Soil, sandy clay. Timber, scattered juniper; undergrowth, greasewood, scattered brush and native grasses.</p> <hr/>
	<p>N. 0°01' W., bet. secs. 23 and 24.</p> <p>Over rolling land.</p>
1.20	Trail road, bears N. 50° E. and S. 50° W.
40.00	<p>Point for the 1/4 sec. cor. of secs. 23 and 24.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center;"> <p>T 24 N R 24 E 1/4 S 23 S 24</p> <p>2005</p> </div> <p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p>
65.45	Underground gas pipeline, bears N. 70° E. and S. 70° W.
66.30	Underground gas pipeline, bears N. 70° E. and S. 70° W.
80.00	<p>Point for the cor. of secs. 13, 14, 23, and 24.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center;"> <p>T 24 N R 24 E S 14 S 13 S 23 S 24</p> <p>2005</p> </div> <p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p> <p>Land, rolling. Soil, rocky and sandy clay. Timber, scattered juniper; undergrowth, greasewood, scattered brush and native grasses.</p> <hr/>
	<p>From the cor. of secs. 13, 18, 19, and 24, on the E. bdy. of the Tp., hereinbefore described.</p>

**Survey of the Subdivisional Lines,
T. 24 N., R. 24 E., Gila and Salt River Meridian, Arizona**

CHAINS	
	N. 89°58' W., bet. secs. 13 and 24. Over rolling land.
34.55	Underground gas pipeline, bears N. 70° E. and S. 70° W.
36.30	Trail road, bears S. 10° E. and N. 10° W.
37.10	Underground gas pipeline, bears N. 70° E. and S. 70° W.
40.00	Point for the 1/4 sec. cor. of secs. 13 and 24. Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd. <div style="text-align: center;"> T 24 N R 24 E S 13 1/4 ——— S 24 2005 </div>
80.00	Deposit a magnet in a white plastic case at the base of the stainless steel post. The cor. of secs. 13, 14, 23, and 24. Land, rolling. Soil, sandy clay. Timber, juniper; undergrowth, greasewood, scattered brush and native grasses. <hr/>
40.00	N. 0°01' W., bet. secs. 13 and 14. Over rolling and broken land. Point for the 1/4 sec. cor. of secs. 13 and 14. Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd. <div style="text-align: center;"> T 24 N R 24 E 1/4 S 14 S 13 2005 </div>
50.50	Deposit a magnet in a white plastic case at the base of the stainless steel post. Wash, 100 ft. wide, 25 ft. deep, drains N. 80° W.

**Survey of the Subdivisional Lines,
T. 24 N., R. 24 E., Gila and Salt River Meridian, Arizona**

CHAINS									
80.00	<p>Point for the cor. of secs. 11, 12, 13, and 14.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center;"> <table style="margin: auto;"> <tr> <td>T 24 N</td> <td>R 24 E</td> </tr> <tr> <td>S 11</td> <td>S 12</td> </tr> <tr> <td>S 14</td> <td>S 13</td> </tr> </table> <p>2005</p> </div> <p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p> <p>Land, rolling and broken. Soil, rocky and sandy clay. Timber, juniper; undergrowth, greasewood, scattered brush and native grasses.</p> <hr/> <p>From the cor. of secs. 7, 12, 13, and 18, on the E. bdy. of the Tp., hereinbefore described.</p> <p>N. 89°58' W., bet. secs. 12 and 13.</p> <p>Over rolling and broken land.</p>	T 24 N	R 24 E	S 11	S 12	S 14	S 13		
T 24 N	R 24 E								
S 11	S 12								
S 14	S 13								
40.00	<p>Point for the 1/4 sec. cor. of secs. 12 and 13.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center;"> <table style="margin: auto;"> <tr> <td>T 24 N</td> <td>R 24 E</td> </tr> <tr> <td></td> <td>S 12</td> </tr> <tr> <td>1/4</td> <td>—</td> </tr> <tr> <td></td> <td>S 13</td> </tr> </table> <p>2005</p> </div> <p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p>	T 24 N	R 24 E		S 12	1/4	—		S 13
T 24 N	R 24 E								
	S 12								
1/4	—								
	S 13								
40.30	Wash, 16 ft. wide, 10 ft. deep, drains N. 80° W.								
48.85	Trail road, bears N. 15° E. and S. 15° W.								
80.00	The cor. of secs. 11, 12, 13, and 14.								

**Survey of the Subdivisional Lines,
T. 24 N., R. 24 E., Gila and Salt River Meridian, Arizona**

CHAINS	
	<p>Land, rolling and broken. Soil, rocky and sandy clay. Timber, juniper; undergrowth, greasewood, scattered brush and native grasses.</p> <hr/>
	<p>N. 0°01' W., bet. secs. 11 and 12.</p>
	<p>Over rolling and broken land.</p>
40.00	<p>Point for the 1/4 sec. cor. of secs. 11 and 12.</p>
	<p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 18 ins. in the ground, in a mound of stone, 2 ft. base, to top, with brass cap mkd.</p>
	<p align="center">T 24 N R 24 E 1/4 S 11 S 12 2005</p>
	<p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p>
40.25	<p>Trail road, bears S. 50° E. and N. 50° W.</p>
80.00	<p>Point for the cor. of secs. 1, 2, 11, and 12.</p>
	<p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p>
	<p align="center">T 24 N R 24 E S 2 S 1 S 11 S 12 2005</p>
	<p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p>
	<p>Cor. is located 1.60 chs. N., of a rim of mesa, bears E. and W.</p>
	<p>Land, rolling and broken. Soil, rocky and sandy clay. Timber, juniper; undergrowth, greasewood, scattered brush and native grasses.</p> <hr/>
	<p>From the cor. of secs. 1, 6, 7, and 12, on the E. bdy. of the Tp., hereinbefore described.</p>

**Survey of the Subdivisional Lines,
T. 24 N., R. 24 E., Gila and Salt River Meridian, Arizona**

CHAINS	
	N. 89°58' W., bet. secs. 1 and 12. Over rolling and broken land.
33.80	Trail road, bears N. 30° E. and S. 30° W.
40.00	Point for the 1/4 sec. cor. of secs. 1 and 12. Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.
	T 24 N R 24 E S 1 1/4 ——— S 12 2005
	Deposit a magnet in a white plastic case at the base of the stainless steel post.
62.30	Trail road, bears S. 25° E. and N. 25° W.
80.00	The cor. of secs. 1, 2, 11, and 12. Land, rolling and broken. Soil, rocky and sandy clay. Timber, juniper; undergrowth, greasewood, scattered brush and native grasses.
	N. 0°01' W., bet. secs. 1 and 2. Over rolling and broken land.
35.70	Trail road, bears S. 30° E. and N. 30° W.
40.00	Point for the 1/4 sec. cor. of secs. 1 and 2. Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.
	T 24 N R 24 E 1/4 S 2 S 1 2004
	Deposit a magnet in a white plastic case at the base of the stainless steel post.
61.15	Navajo Route 28, a graded road, 26 ft. wide, bears E. and W.

**Survey of the Subdivisional Lines,
T. 24 N., R. 24 E., Gila and Salt River Meridian, Arizona**

CHAINS

77.37

Point for the closing cor. of secs. 1 and 2, at intersection with the Sixth Standard Parallel North, on the N. bdy. of the Tp.

Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.

T 25 N	R 24 E
S 34	
S 2	S 1
T 24 N	R 24 E
C C	

2004

Deposit a magnet in a white plastic case at the base of the stainless steel post.

From this cor. point, the stan. cor. of secs. 34 and 35, T. 25 N., R. 24 E., bears S. 89°55' E., 38 lks. dist., monumented with a stainless steel post, 2 1/2 ins. diam., firmly set, projecting 4 ins. above ground with brass cap mkd. SC T25N R24E S34 S35 2001.

From this same cor. point, the stan. 1/4 sec. cor. of sec. 34, T. 25 N., R. 24 E., bears N. 89°55' W., 39.79 chs. dist., monumented with a stainless steel post, 2 1/2 ins. diam., firmly set, projecting 4 ins. above ground with brass cap mkd. SC T25N R24E 1/4 S34 2001.

Land, rolling and broken.

Soil, rocky and sandy clay.

Timber, juniper; undergrowth, greasewood, scattered brush and native grasses.

Point for the 1/4 sec. cor. of sec. 1 only, T. 24 N., R. 24 E., at midpoint on the N. bdy. of sec. 1.

Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.

T 25 N	R 24 E
1/4 S 1	
T 24 N	R 24 E

2004

Deposit a magnet in a white plastic case at the base of the stainless steel post.

**Survey of the Subdivisional Lines,
T. 24 N., R. 24 E., Gila and Salt River Meridian, Arizona**

CHAINS	<p>From this cor. point, the stan. 1/4 sec. cor. of sec. 35, T. 25 N., R. 24 E., bears S. 89°55' E., 55 lks. dist., monumented with a stainless steel post, 2 1/2 ins. diam., firmly set, projecting 4 ins. above ground with brass cap mkd. SC T25N R24E 1/4 S35 2001.</p> <p>From this same cor. point, the stan. cor. of secs. 34 and 35, T. 25 N., R. 24 E., bears N. 89°55' W., 39.62 chs. dist., hereinbefore described.</p> <hr/> <p>From the cor. of secs. 2, 3, 34 and 35, on the S. bdy. of the Tp., hereinbefore described.</p> <p>N. 0°01' W., bet. secs. 34 and 35.</p> <p>Over rolling and broken land.</p> <p>34.58 High voltage transmission line, bears N. 45° E. and S. 45° W.</p> <p>40.00 Point for the 1/4 sec. cor. of secs. 34 and 35.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p align="center">T 24 N R 24 E 1/4 S 34 S 35 2005</p> <p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p> <p>80.00 Point for the cor. of secs. 26, 27, 34, and 35.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p align="center">T 24 N R 24 E S 27 S 26 S 34 S 35 2005</p> <p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p>
--------	--

**Survey of the Subdivisional Lines,
T. 24 N., R. 24 E., Gila and Salt River Meridian, Arizona**

CHAINS	
	<p>Land, rolling and broken. Soil, rocky and sandy clay. Timber, scattered juniper; undergrowth, greasewood, scattered brush and native grasses.</p> <hr/> <p>From the cor. of secs. 25, 26, 35, and 36. N. 89°58' W., bet. secs. 26 and 35. Over rolling and broken land.</p>
38.35	High voltage transmission line, bears N. 45° E. and S. 45° W.
40.00	Point for the 1/4 sec. cor. of secs. 26 and 35. Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.
	<p>T 24 N R 24 E S 26 1/4 ——— S 35 2005</p>
	Deposit a magnet in a white plastic case at the base of the stainless steel post.
80.00	The cor. of secs. 26, 27, 34, and 35. Land, rolling and broken. Soil, rocky and sandy clay. Timber, scattered juniper; undergrowth, greasewood, scattered brush and native grasses.
	<hr/> <p>N. 0°01' W., bet. secs. 26 and 27. Over rolling and broken land.</p>
34.60	Ridge, bears N. 45° E. and S. 45° W.
40.00	Point for the 1/4 sec. cor. of secs. 26 and 27. Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.

**Survey of the Subdivisional Lines,
T. 24 N., R. 24 E., Gila and Salt River Meridian, Arizona**

CHAINS	
	T 24 N R 24 E 1/4 S 27 S 26 2005 Deposit a magnet in a white plastic case at the base of the stainless steel post.
70.60	Navajo Route 9606, a graded road, 36 ft. wide, bears E. and W.
80.00	Point for the cor. of secs. 22, 23, 26, and 27. Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.
	T 24 N R 24 E S 22 S 23 S 27 S 26 2005 Deposit a magnet in a white plastic case at the base of the stainless steel post.
	Land, rolling and broken. Soil, rocky and sandy clay. Timber, scattered juniper; undergrowth, greasewood, scattered brush and native grasses.
	<hr/> From the cor. of secs. 23, 24, 25, and 26. N. 89°58' W., bet. secs. 23 and 26. Over rolling land.
40.00	Point for the 1/4 sec. cor. of secs. 23 and 26. Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.
	T 24 N R 24 E S 23 1/4 ——— S 26 2005 Deposit a magnet in a white plastic case at the base of the stainless steel post.

**Survey of the Subdivisional Lines,
T. 24 N., R. 24 E., Gila and Salt River Meridian, Arizona**

CHAINS	
80.00	<p>The cor. of secs. 22, 23, 26, and 27.</p> <p>Land, rolling. Soil, rocky and sandy clay. No timber; undergrowth, greasewood, scattered brush and native grasses.</p> <hr/> <p>N. 0°01' W., bet. secs. 22 and 23.</p> <p>Over rolling land.</p>
37.55	Underground gas pipeline, bears N. 75° E. and S. 75° W.
38.35	Underground gas pipeline, bears N. 75° E. and S. 75° W.
40.00	<p>Point for the 1/4 sec. cor. of secs. 22 and 23.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T 24 N R 24 E 1/4 S 22 S 23</p> <p style="text-align: center;">2005</p> <p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p>
80.00	<p>Point for the cor. of secs. 14, 15, 22, and 23.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T 24 N R 24 E S 15 S 14 S 22 S 23</p> <p style="text-align: center;">2005</p> <p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p> <p>Cor. is located 80 lks. N. and 29 lks. W., of a ridge line, bears N. 70° E. and S. 70° W.</p> <p>Land, rolling and broken. Soil, rocky and sandy clay. Timber, scattered juniper; undergrowth, greasewood, scattered brush and native grasses.</p> <hr/>

**Survey of the Subdivisional Lines,
T. 24 N., R. 24 E., Gila and Salt River Meridian, Arizona**

CHAINS	
	<p>From the cor. of secs. 13, 14, 23, and 24.</p> <p>N. 89°58' W., bet. secs. 14 and 23.</p> <p>Over rolling land.</p>
40.00	<p>Point for the 1/4 sec. cor. of secs. 14 and 23.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T 24 N R 24 E S 14 1/4 ——— S 23</p> <p style="text-align: center;">2005</p>
	<p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p>
80.00	<p>The cor. of secs. 14, 15, 22, and 23.</p> <p>Land, rolling. Soil, sandy clay. Timber, scattered juniper; undergrowth, greasewood, scattered brush and native grasses.</p> <hr/> <p>N. 0°01' W., bet. secs. 14 and 15.</p> <p>Over rolling and broken land.</p>
21.50	<p>Ridge, bears S. 80° E. and N. 80° W.</p>
40.00	<p>Point for the 1/4 sec. cor. of secs. 14 and 15.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T 24 N R 24 E 1/4 S 15 S 14</p> <p style="text-align: center;">2005</p>
	<p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p>
80.00	<p>Point for the cor. of secs. 10, 11, 14, and 15.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p>

**Survey of the Subdivisional Lines,
T. 24 N., R. 24 E., Gila and Salt River Meridian, Arizona**

CHAINS									
	<table border="0"> <tr> <td>T 24 N</td> <td>R 24 E</td> </tr> <tr> <td>S 10</td> <td>S 11</td> </tr> <tr> <td>S 15</td> <td>S 14</td> </tr> </table> <p>2005</p> <p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p> <p>Land, rolling and broken. Soil, rocky and sandy clay. Timber, scattered juniper; undergrowth, greasewood, scattered brush and native grasses.</p> <hr/> <p>From the cor. of secs. 11, 12, 13, and 14.</p> <p>N. 89°58' W., bet. secs. 11 and 14.</p> <p>Over rolling and broken land.</p>	T 24 N	R 24 E	S 10	S 11	S 15	S 14		
T 24 N	R 24 E								
S 10	S 11								
S 15	S 14								
40.00	<p>Point for the 1/4 sec. cor. of secs. 11 and 14.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p>								
	<table border="0"> <tr> <td>T 24 N</td> <td>R 24 E</td> </tr> <tr> <td></td> <td>S 11</td> </tr> <tr> <td>1/4</td> <td>—</td> </tr> <tr> <td></td> <td>S 14</td> </tr> </table> <p>2005</p> <p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p>	T 24 N	R 24 E		S 11	1/4	—		S 14
T 24 N	R 24 E								
	S 11								
1/4	—								
	S 14								
80.00	<p>The cor. of secs. 10, 11, 14, and 15.</p> <p>Land, rolling and broken. Soil, rocky and sandy clay. Timber, scattered juniper; undergrowth, greasewood, scattered brush and native grasses.</p> <hr/> <p>N. 0°01' W., bet. secs. 10 and 11.</p> <p>Over rolling land.</p>								
40.00	<p>Point for the 1/4 sec. cor. of secs. 10 and 11.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p>								

**Survey of the Subdivisional Lines,
T. 24 N., R. 24 E., Gila and Salt River Meridian, Arizona**

CHAINS	
	T 24 N R 24 E 1/4 S 10 S 11 2005 Deposit a magnet in a white plastic case at the base of the stainless steel post.
64.65	High voltage transmission line, bears N. 35° E. and S. 35° W.
80.00	Point for the cor. of secs. 2, 3, 10, and 11. Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.
	T 24 N R 24 E S 3 S 2 S 10 S 11 2005 Deposit a magnet in a white plastic case at the base of the stainless steel post.
	Land, rolling. Soil, rocky and sandy clay. Timber, scattered juniper; undergrowth, greasewood, scattered brush and native grasses.
	<hr/> From the cor. of secs. 1, 2, 11, and 12. N. 89°58' W., bet. secs. 2 and 11. Over rolling and broken land.
40.00	Point for the 1/4 sec. cor. of secs. 2 and 11. Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.
	T 24 N R 24 E S 2 1/4 ——— S 11 2005 Deposit a magnet in a white plastic case at the base of the stainless steel post.

**Survey of the Subdivisional Lines,
T. 24 N., R. 24 E., Gila and Salt River Meridian, Arizona**

CHAINS	
69.95	High voltage transmission line, bears N. 35° E. and S. 35° W.
80.00	The cor. of secs. 2, 3, 10, and 11. Land, rolling and broken. Soil, rocky and sandy clay. No timber; undergrowth, greasewood, scattered brush and native grasses.

	N. 0°01' W., bet. secs. 2 and 3. Over rolling and broken land.
40.00	Point for the 1/4 sec. cor. of secs. 2 and 3. Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd. <div style="text-align: center;"> T 24 N R 24 E 1/4 S 3 S 2 2005 </div>
	Deposit a magnet in a white plastic case at the base of the stainless steel post.
77.44	Point for the closing cor. of secs. 2 and 3, at intersection with the Sixth Standard Parallel North, on the N. bdy. of the Tp. Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd. <div style="text-align: center;"> T 25 N R 24 E S 33 ----- S 3 S 2 T 24 N R 24 E C C 2005 </div>
	Deposit a magnet in a white plastic case at the base of the stainless steel post.
	From this cor. point, the stan. cor. of secs. 33 and 34, T. 25 N., R. 24 E., bears S. 89°55' E., 5 lks. dist., monumented with a stainless steel post, 2 1/2 ins. diam., firmly set, projecting 4 ins. above ground with brass cap mkd. SC T25N R24E S33 S34 2001.

**Survey of the Subdivisional Lines,
T. 24 N., R. 24 E., Gila and Salt River Meridian, Arizona**

CHAINS

From this same cor. point, the stan. 1/4 sec. cor. of sec. 33, T. 25 N., R. 24 E., bears N. 89°55' W., 40.12 chs. dist., monumented with a stainless steel post, 2 1/2 ins. diam., firmly set, projecting 4 ins. above ground with brass cap mkd. SC T25N R24E 1/4 S33 2001.

Land, rolling and broken.
Soil, rocky and sandy clay.
Timber, juniper; undergrowth, greasewood, scattered brush and native grasses.

Point for the 1/4 sec. cor. of sec. 2 only, T. 24 N., R. 24 E., at midpoint on the N. bdy. of sec. 2.

Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.

T 25 N R 24 E

1/4 S 2

T 24 N R 24 E

2005

Deposit a magnet in a white plastic case at the base of the stainless steel post.

From this cor. point, the stan. 1/4 sec. cor. of sec. 34, T. 25 N., R. 24 E., bears S. 89°55' E., 21.5 lks. dist., monumented with a stainless steel post, 2 1/2 ins. diam., firmly set, projecting 4 ins. above ground with brass cap mkd. SC T25N R24E 1/4 S34 2001.

From this same cor. point, the stan. cor. of secs. 33 and 34, T. 25 N., R. 24 E., bears N. 89°55' W., 39.955 chs. dist., hereinbefore described.

From the cor. of secs. 3, 4, 33 and 34, on the S. bdy. of the Tp., hereinbefore described.

N. 0°02' W., bet. secs. 33 and 34.

Over rolling and broken land.

40.00

Point for the 1/4 sec. cor. of secs. 33 and 34.

Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.

**Survey of the Subdivisional Lines,
T. 24 N., R. 24 E., Gila and Salt River Meridian, Arizona**

CHAINS	
	T 24 N R 24 E 1/4 S 33 S 34 2004
	Deposit a magnet in a white plastic case at the base of the stainless steel post.
74.80	Rim of mesa, bears N. 35° E. and S. 35° W.
80.00	Point for the cor. of secs. 27, 28, 33, and 34.
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.
	T 24 N R 24 E S 28 S 27 S 33 S 34 2004
	Deposit a magnet in a white plastic case at the base of the stainless steel post.
	Land, rolling and broken. Soil, rocky and sandy clay. Timber, scattered juniper; undergrowth, greasewood, scattered brush and native grasses.
	From the cor. of secs. 26, 27, 34, and 35.
	N. 89°58' W., bet. secs. 27 and 34.
	Over rolling land.
40.00	Point for the 1/4 sec. cor. of secs. 27 and 34.
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.
	T 24 N R 24 E S 27 1/4 ——— S 34 2004
	Deposit a magnet in a white plastic case at the base of the stainless steel post.

**Survey of the Subdivisional Lines,
T. 24 N., R. 24 E., Gila and Salt River Meridian, Arizona**

CHAINS	
80.00	<p>The cor. of secs. 27, 28, 33, and 34.</p> <p>Land, rolling. Soil, rocky and sandy clay. Timber, scattered juniper; undergrowth, greasewood, scattered brush and native grasses.</p> <hr/> <p>N. 0°02' W., bet. secs. 27 and 28.</p> <p>Over rolling land.</p>
40.00	<p>Point for the 1/4 sec. cor. of secs. 27 and 28.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T 24 N R 24 E 1/4 S 28 S 27</p> <p style="text-align: center;">2004</p> <p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p>
70.00	<p>Navajo Route 9606, a graded road, 36 ft. wide, bears N. 85° E. and S. 85° W.</p>
76.75	<p>Rim of mesa, bears S. 70° E. and N. 70° W.</p>
80.00	<p>Point for the cor. of secs. 21, 22, 27, and 28.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T 24 N R 24 E S 21 S 22 S 28 S 27</p> <p style="text-align: center;">2004</p> <p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p> <p>Land, rolling and broken. Soil, rocky and sandy clay. Timber, scattered juniper; undergrowth, greasewood, scattered brush and native grasses.</p> <hr/> <p>From the cor. of secs. 22, 23, 26, and 27.</p>

**Survey of the Subdivisional Lines,
T. 24 N., R. 24 E., Gila and Salt River Meridian, Arizona**

CHAINS	
	N. 89°58' W., bet. secs. 22 and 27. Over rolling land.
40.00	Point for the 1/4 sec. cor. of secs. 22 and 27. Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd. <div style="text-align: center;"> T 24 N R 24 E S 22 1/4 ——— S 27 2004 </div>
73.70	Deposit a magnet in a white plastic case at the base of the stainless steel post. Rim of mesa, bears S. 10° E. and N. 10° W.
80.00	The cor. of secs. 21, 22, 27, and 28. Land, rolling and broken. Soil, rocky and sandy clay. Timber, scattered juniper; undergrowth, greasewood, scattered brush and native grasses.
	<hr/>
	N. 0°02' W., bet. secs. 21 and 22. Over rolling and broken land.
32.80	Underground gas pipeline, bears S. 85° E. and N. 85° W.
33.55	Underground gas pipeline, bears S. 85° E. and N. 85° W.
40.00	Point for the 1/4 sec. cor. of secs. 21 and 22. Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd. <div style="text-align: center;"> T 24 N R 24 E 1/4 S 21 S 22 2004 </div>
	Deposit a magnet in a white plastic case at the base of the stainless steel post.
44.90	Wash, 25 ft. wide, 6 ft. deep, drains S. 60° W.

**Survey of the Subdivisional Lines,
T. 24 N., R. 24 E., Gila and Salt River Meridian, Arizona**

CHAINS									
46.65	Trail road, bears N. 45° E. and S. 45° W.								
80.00	Point for the cor. of secs. 15, 16, 21, and 22. Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd. <div style="text-align: center;"> <table style="margin: auto;"> <tr><td>T 24 N</td><td>R 24 E</td></tr> <tr><td>S 16</td><td>S 15</td></tr> <tr><td>S 21</td><td>S 22</td></tr> </table> <p>2004</p> </div> <p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p> <p>Land, rolling and broken. Soil, rocky and sandy clay. Timber, scattered juniper; undergrowth, greasewood, scattered brush and native grasses.</p> <hr/> <p>From the cor. of secs. 14, 15, 22, and 23. N. 89°58' W., bet. secs. 15 and 22. Over rolling and broken land.</p>	T 24 N	R 24 E	S 16	S 15	S 21	S 22		
T 24 N	R 24 E								
S 16	S 15								
S 21	S 22								
33.65	E. rim of a draw, bears N. 70° E. and S. 70° W.								
40.00	Point for the 1/4 sec. cor. of secs. 15 and 22. Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd. <div style="text-align: center;"> <table style="margin: auto;"> <tr><td>T 24 N</td><td>R 24 E</td></tr> <tr><td>S 15</td><td></td></tr> <tr><td>1/4</td><td>_____</td></tr> <tr><td>S 22</td><td></td></tr> </table> <p>2004</p> </div> <p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p>	T 24 N	R 24 E	S 15		1/4	_____	S 22	
T 24 N	R 24 E								
S 15									
1/4	_____								
S 22									
40.25	W. rim of the same draw, bears N. 25° E. and S. 25° W.								
80.00	The cor. of secs. 15, 16, 21, and 22.								

**Survey of the Subdivisional Lines,
T. 24 N., R. 24 E., Gila and Salt River Meridian, Arizona**

CHAINS	
	<p>Land, rolling and broken. Soil, rocky and sandy clay. Timber, scattered juniper; undergrowth, greasewood, scattered brush and native grasses.</p> <hr/>
	<p>N. 0°02' W., bet. secs. 15 and 16.</p> <p>Over rolling and broken land.</p>
21.38	High voltage transmission line, bears N. 35° E. and S. 35° W.
40.00	<p>Point for the 1/4 sec. cor. of secs. 15 and 16.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T 24 N R 24 E 1/4 S 16 S 15</p> <p style="text-align: center;">2005</p>
80.00	<p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p> <p>Point for the cor. of secs. 9, 10, 15, and 16.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T 24 N R 24 E S 9 S 10 S 16 S 15</p> <p style="text-align: center;">2005</p> <p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p>
	<p>Land, rolling and broken. Soil, rocky and sandy clay. Timber, scattered juniper; undergrowth, greasewood, scattered brush and native grasses.</p> <hr/>
	<p>From the cor. of secs. 10, 11, 14, and 15.</p> <p>N. 89°58' W., bet. secs. 10 and 15.</p> <p>Over rolling and broken land.</p>

**Survey of the Subdivisional Lines,
T. 24 N., R. 24 E., Gila and Salt River Meridian, Arizona**

CHAINS	
40.00	<p>Point for the 1/4 sec. cor. of secs. 10 and 15.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T 24 N R 24 E S 10 1/4 ——— S 15</p> <p style="text-align: center;">2004</p> <p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p>
41.91	High Voltage transmission line, bears N. 35° E. and S. 35° W.
80.00	<p>The cor. of secs. 9, 10, 15, and 16.</p> <p>Land, rolling and broken. Soil, rocky and sandy clay. Timber, scattered juniper; undergrowth, greasewood, scattered brush and native grasses.</p> <hr/> <p>N. 0°02' W., bet. secs. 9 and 10.</p> <p>Over rolling and broken land.</p>
40.00	<p>Point for the 1/4 sec. cor. of secs. 9 and 10.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T 24 N R 24 E 1/4 S 9 S 10</p> <p style="text-align: center;">2005</p> <p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p>
80.00	<p>Point for the cor. of secs. 3, 4, 9, and 10.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p>

**Survey of the Subdivisional Lines,
T. 24 N., R. 24 E., Gila and Salt River Meridian, Arizona**

CHAINS									
	<table border="0"> <tr> <td>T 24 N</td> <td>R 24 E</td> </tr> <tr> <td>S 4</td> <td>S 3</td> </tr> <tr> <td colspan="2"><hr/></td> </tr> <tr> <td>S 9</td> <td>S 10</td> </tr> </table> <p>2005</p> <p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p> <p>Land, rolling and broken. Soil, rocky and sandy clay. Timber, scattered juniper; undergrowth, greasewood, scattered brush and native grasses.</p> <hr/> <p>From the cor. of secs. 2, 3, 10, and 11.</p> <p>N. 89°58' W., bet. secs. 3 and 10.</p> <p>Over rolling and broken land.</p>	T 24 N	R 24 E	S 4	S 3	<hr/>		S 9	S 10
T 24 N	R 24 E								
S 4	S 3								
<hr/>									
S 9	S 10								
39.30	Wash, 5 ft. wide, 3 ft. deep, drains S. 45° W.								
40.00	Point for the 1/4 sec. cor. of secs. 3 and 10.								
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.								
	<table border="0"> <tr> <td>T 24 N</td> <td>R 24 E</td> </tr> <tr> <td></td> <td>S 3</td> </tr> <tr> <td>1/4</td> <td><hr/></td> </tr> <tr> <td></td> <td>S 10</td> </tr> </table> <p>2005</p> <p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p>	T 24 N	R 24 E		S 3	1/4	<hr/>		S 10
T 24 N	R 24 E								
	S 3								
1/4	<hr/>								
	S 10								
80.00	The cor. of secs. 3, 4, 9, and 10.								
	Land, rolling and broken. Soil, rocky and sandy clay. Timber, scattered juniper; undergrowth, greasewood, scattered brush and native grasses.								
	<hr/>								
	N. 0°02' W., bet. secs. 3 and 4.								
	Over rolling and broken land.								
17.40	Trail road, bears N. 50° E. and S. 50° W.								

**Survey of the Subdivisional Lines,
T. 24 N., R. 24 E., Gila and Salt River Meridian, Arizona**

CHAINS	
19.90	S. rim of a canyon, bears N. 75° E. and S. 75° W.
27.50	N. rim of the same canyon, bears N. 25° E. and S. 25° W.
38.15	Trail road, bears N. 80° E. and S. 80° W.
40.00	Point for the 1/4 sec. cor. of secs. 3 and 4. Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd. <div style="text-align: center;"> T 24 N R 24 E 1/4 S 4 S 3 2005 </div> Deposit a magnet in a white plastic case at the base of the stainless steel post.
60.30	Rim of mesa, bears N. 80° E. and S. 80° W.
77.52	Point for the closing cor. of secs. 3 and 4, at intersection with the Sixth Standard Parallel North, on the N. bdy. of the Tp. Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd. <div style="text-align: center;"> T 25 N R 24 E S 33 ----- S 4 S 3 T 24 N R 24 E C C 2004 </div> Deposit a magnet in a white plastic case at the base of the stainless steel post. From this cor. point, the stan. 1/4 sec. cor. of sec. 33, T. 25 N., R. 24 E., bears S. 89°55' E., 39.88 chs. dist., monumented with a stainless steel post, 2 1/2 ins. diam., firmly set, projecting 4 ins. above ground with brass cap mkd. SC T25N R24E 1/4 S33 2001. From this same cor. point, the stan. cor. of secs. 32 and 33, T. 25 N., R. 24 E., bears N. 89°55' W., 29 lks. dist., monumented with a stainless steel post, 2 1/2 ins. diam., firmly set, projecting 4 ins. above ground with brass cap mkd. SC T25N R24E S32 S33 2001.

**Survey of the Subdivisional Lines,
T. 24 N., R. 24 E., Gila and Salt River Meridian, Arizona**

CHAINS	
	<p>Land, rolling and broken. Soil, rocky and sandy clay. Timber, juniper; undergrowth, greasewood, scattered brush and native grasses.</p> <hr/> <p>Point for the 1/4 sec. cor. of sec. 3 only, T. 24 N., R. 24 E., at midpoint on the N. bdy. of sec. 3.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T 25 N R 24 E ----- 1/4 S 3 T 24 N R 24 E</p> <p style="text-align: center;">2005</p> <p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p> <p>From this cor. point, the stan. cor. of secs. 33 and 34, T. 25 N., R. 24 E., bears S. 89°55' E., 40.05 chs. dist., hereinbefore described.</p> <p>From this same cor. point, the stan. 1/4 sec. cor. of sec. 33, T. 25 N., R. 24 E., bears N. 89°55' W., 12 lks. dist., hereinbefore described.</p> <hr/> <p>From the cor. of secs. 4, 5, 32 and 33, on the S. bdy. of the Tp., hereinbefore described.</p> <p>N. 0°03' W., bet. secs. 32 and 33.</p> <p>Over rolling and broken land.</p>
40.00	<p>Point for the 1/4 sec. cor. of secs. 32 and 33.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T 24 N R 24 E 1/4 S 32 S 33</p> <p style="text-align: center;">2004</p> <p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p>
80.00	<p>Point for the cor. of secs. 28, 29, 32, and 33.</p>

**Survey of the Subdivisional Lines,
T. 24 N., R. 24 E., Gila and Salt River Meridian, Arizona**

CHAINS	
	<p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T 24 N R 24 E S 29 S 28 ----- S 32 S 33</p> <p style="text-align: center;">2004</p> <p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p> <p>Land, rolling and broken. Soil, rocky and sandy clay. No timber; undergrowth, greasewood, scattered brush and native grasses.</p> <hr/> <p>From the cor. of secs. 27, 28, 33, and 34. N. 89°58' W., bet. secs. 28 and 33. Over rolling land.</p>
40.00	<p>Point for the 1/4 sec. cor. of secs. 28 and 33.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T 24 N R 24 E S 28 1/4 ----- S 33</p> <p style="text-align: center;">2004</p> <p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p>
80.00	<p>The cor. of secs. 28, 29, 32, and 33.</p> <p>Land, rolling. Soil, rocky and sandy clay. No timber; undergrowth, greasewood, scattered brush and native grasses.</p> <hr/> <p>N. 0°03' W., bet. secs. 28 and 29. Over rolling and broken land.</p>
1.34	<p>Trail road, bears N. 60° E. and S. 70° W.</p>

**Survey of the Subdivisional Lines,
T. 24 N., R. 24 E., Gila and Salt River Meridian, Arizona**

CHAINS	
40.00	<p>Point for the 1/4 sec. cor. of secs. 28 and 29.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T 24 N R 24 E 1/4 S 29 S 28</p> <p style="text-align: center;">2004</p> <p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p>
58.16	High voltage transmission line, bears N. 35° E. and S. 35° W.
80.00	<p>Point for the cor. of secs. 20, 21, 28, and 29.</p> <p>Set a magnet in a white plastic case, 24 ins. below the surface of the ground.</p> <p>from which</p> <p style="padding-left: 40px;">A stainless steel post, 28 ins. long, 2 1/2 ins. diam., set 24 ins. in the ground for a reference monument, bears S. 45°00' E., 75.0 ft. dist., with brass cap mkd. RM T24N R24E S28 75.0 FT. TO COR. 2004 and an arrow pointing to the cor. Deposit a magnet in a white plastic case at the base of the stainless steel post.</p> <p style="padding-left: 40px;">A stainless steel post, 28 ins. long, 2 1/2 ins. diam., set 24 ins. in the ground for a reference monument, bears N. 45°00' W., 75.0 ft. dist., with brass cap mkd. RM T24N R24E S20 RM 75.0 FT. TO COR. 2004 and an arrow pointing to the cor. Deposit a magnet in a white plastic case at the base of the stainless steel post.</p> <p>Cor. is located in a wash, 60 ft. wide, 4 ft. deep, drains S. 35° W.</p> <p>Land, rolling and broken. Soil, rocky and sandy clay. Timber, scattered juniper; undergrowth, greasewood, scattered brush and native grasses.</p> <hr/> <p>From the cor. of secs. 21, 22, 27, and 28.</p> <p>N. 89°58' W., bet. secs. 21 and 28.</p> <p>Over rolling land.</p>
40.00	Point for the 1/4 sec. cor. of secs. 21 and 28.

**Survey of the Subdivisional Lines,
T. 24 N., R. 24 E., Gila and Salt River Meridian, Arizona**

CHAINS	
	<p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T 24 N R 24 E S 21 1/4 ——— S 28</p> <p style="text-align: center;">2004</p> <p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p>
65.80	High voltage transmission line, bears N. 35° E. and S. 35° W.
77.60	Navajo Route 9606, a graded road, 28 ft. wide, bears S. 45° E. and N. 45° W.
80.00	The cor. of secs. 20, 21, 28, and 29.
	<p>Land, rolling and broken. Soil, rocky and sandy clay. Timber, scattered juniper; undergrowth, greasewood, scattered brush and native grasses.</p> <hr/> <p>N. 0°03' W., bet. secs. 20 and 21.</p> <p>Over rolling and broken land.</p>
2.45	Navajo Route 9606, a graded road, 28 ft. wide, bears S. 45° E. and N. 45° W.
37.68	Underground gas pipeline, bears E. and W.
38.58	Underground gas pipeline, bears E. and W.
40.00	Point for the 1/4 sec. cor. of secs. 20 and 21.
	<p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T 24 N R 24 E 1/4 S 20 S 21</p> <p style="text-align: center;">2005</p> <p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p>
80.00	Point for the cor. of secs. 16, 17, 20, and 21.

**Survey of the Subdivisional Lines,
T. 24 N., R. 24 E., Gila and Salt River Meridian, Arizona**

CHAINS	
	<p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T 24 N R 24 E S 17 S 16 S 20 S 21</p> <p style="text-align: center;">2005</p> <p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p> <p>Land, rolling and broken. Soil, rocky and sandy clay. Timber, scattered juniper; undergrowth, greasewood, scattered brush and native grasses.</p> <hr/> <p>From the cor. of secs. 15, 16, 21, and 22. N. 89°58' W., bet. secs. 16 and 21. Over rolling and broken land.</p>
10.30	Wash, 30 ft. wide, 12 ft. deep, drains S. 40° W.
13.90	High voltage transmission line, bears N. 35° E. and S. 35° W.
40.00	Point for the 1/4 sec. cor. of secs. 16 and 21. Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.
	<p style="text-align: center;">T 24 N R 24 E S 16 1/4 ——— S 21</p> <p style="text-align: center;">2005</p> <p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p>
80.00	<p>The cor. of secs. 16, 17, 20, and 21.</p> <p>Land, rolling and broken. Soil, rocky and sandy clay. Timber, scattered juniper; undergrowth, greasewood, scattered brush and native grasses.</p> <hr/> <p>N. 0°03' W., bet. secs. 16 and 17.</p>

**Survey of the Subdivisional Lines,
T. 24 N., R. 24 E., Gila and Salt River Meridian, Arizona**

CHAINS	
	Over rolling and broken land.
40.00	Point for the 1/4 sec. cor. of secs. 16 and 17. Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd. <div style="text-align: center;"> T 24 N R 24 E 1/4 S 17 S 16 2005 </div>
	Deposit a magnet in a white plastic case at the base of the stainless steel post.
47.40	Rim of mesa, bears N. 25° E. and S. 25° W.
80.00	Point for the cor. of secs. 8, 9, 16, and 17. Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd. <div style="text-align: center;"> T 24 N R 24 E S 8 S 9 S 17 S 16 2005 </div>
	Deposit a magnet in a white plastic case at the base of the stainless steel post.
	Land, rolling and broken. Soil, rocky and sandy clay. Timber, scattered juniper; undergrowth, greasewood, scattered brush and native grasses.
	From the cor. of secs. 9, 10, 15, and 16. N. 89°58' W., bet. secs. 9 and 16. Over rolling and broken land.
8.10	Rim of mesa, bears S. 20° E. and N. 20° W.
40.00	Point for the 1/4 sec. cor. of secs. 9 and 16. Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.

**Survey of the Subdivisional Lines,
T. 24 N., R. 24 E., Gila and Salt River Meridian, Arizona**

CHAINS	
	T 24 N R 24 E S 9 1/4 ——— S 16 2005 Deposit a magnet in a white plastic case at the base of the stainless steel post.
80.00	The cor. of secs. 8, 9, 16, and 17. Land, rolling and broken. Soil, rocky and sandy clay. Timber, scattered juniper; undergrowth, greasewood, scattered brush and native grasses.
	N. 0°03' W., bet. secs. 8 and 9. Over rolling and broken land.
11.10	Rim of mesa, bears N. 60° E. and S. 60° W.
40.00	Point for the 1/4 sec. cor. of secs. 8 and 9. Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.
	T 24 N R 24 E 1/4 S 8 S 9 2004
80.00	Deposit a magnet in a white plastic case at the base of the stainless steel post. Point for the cor. of secs. 4, 5, 8, and 9. Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.
	T 24 N R 24 E S 5 S 4 ——— S 8 S 9 2005
	Deposit a magnet in a white plastic case at the base of the stainless steel post.

**Survey of the Subdivisional Lines,
T. 24 N., R. 24 E., Gila and Salt River Meridian, Arizona**

CHAINS	
	<p>Land, rolling and broken. Soil, rocky and sandy clay. Timber, scattered juniper; undergrowth, greasewood, scattered brush and native grasses.</p> <hr/> <p>From the cor. of secs. 3, 4, 9, and 10. N. 89°58' W., bet. secs. 4 and 9. Over rolling and broken land.</p>
10.60	Trail road, bears N. 25° E. and S. 25° W.
23.55	Rim of mesa, bears N. 50° E. and S. 50° W.
40.00	Point for the 1/4 sec. cor. of secs. 4 and 9. Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.
	<p>T 24 N R 24 E S 4 1/4 ——— S 9</p> <p>2005</p>
	Deposit a magnet in a white plastic case at the base of the stainless steel post.
80.00	The cor. of secs. 4, 5, 8, and 9. Land, rolling and broken. Soil, rocky and sandy clay. Timber, scattered juniper; undergrowth, greasewood, scattered brush and native grasses.
	<hr/> <p>N. 0°03' W., bet. secs. 4 and 5. Over rolling and broken land.</p>
40.00	Point for the 1/4 sec. cor. of secs. 4 and 5. Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.

**Survey of the Subdivisional Lines,
T. 24 N., R. 24 E., Gila and Salt River Meridian, Arizona**

CHAINS

T 24 N R 24 E
1/4
S 5 | S 4

2005

Deposit a magnet in a white plastic case at the base of the stainless steel post.

77.59

Point for the closing cor. of secs. 4 and 5, at intersection with the Sixth Standard Parallel North, on the N. bdy. of the Tp.

Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.

T 25 N R 24 E
S 32

S 5 | S 4
T 24 N | R 24 E
C C

2004

Deposit a magnet in a white plastic case at the base of the stainless steel post.

From this cor. point, the stan. 1/4 sec. cor. of sec. 32, T. 25 N., R. 24 E., bears S. 89°55' E., 39.55 chs. dist., monumented with a stainless steel post, 2 1/2 ins. diam., firmly set, projecting 4 ins. above ground with brass cap mkd. SC T25N R24E 1/4 S32 2001.

From this same cor. point, the stan. cor. of secs. 31 and 32, T. 25 N., R. 24 E., bears N. 89°55' W., 62 lks. dist., monumented with a stainless steel post, 2 1/2 ins. diam., firmly set, projecting 4 ins. above ground with brass cap mkd. SC T25N R24E S31 S32 2001.

Land, rolling and broken.

Soil, rocky and sandy clay.

Timber, juniper; undergrowth, greasewood, scattered brush and native grasses.

Point for the 1/4 sec. cor. of sec. 4 only, T. 24 N., R. 24 E., at midpoint on the N. bdy. of sec. 4.

Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.

**Survey of the Subdivisional Lines,
T. 24 N., R. 24 E., Gila and Salt River Meridian, Arizona**

CHAINS	
	T 25 N R 24 E <hr style="width: 10%; margin: auto;"/> 1/4 S 4 T 24 N R 24 E 2005
	Deposit a magnet in a white plastic case at the base of the stainless steel post. From this cor. point, the stan. cor. of secs. 32 and 33, T. 25 N., R. 24 E., bears S. 89°55' E., 39.71 chs. dist., hereinbefore described. From this same cor. point, the stan. 1/4 sec. cor. of sec. 32, T. 25 N., R. 24 E., bears N. 89°55' W., 46 lks. dist., hereinbefore described.
	<hr/> From the cor. of secs. 5, 6, 31 and 32, on the S. bdy. of the Tp., hereinbefore described. N. 0°03' W., bet. secs. 31 and 32. Over rolling and broken land.
12.70	Navajo Route 9003, a graded road, 15 ft. wide, bears S. 40° E. and N. 40° W.
15.07	High Voltage transmission line, bears N. 35° E. and S. 35° W.
40.00	Point for the 1/4 sec. cor. of secs. 31 and 32. Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.
	T 24 N R 24 E 1/4 S 31 S 32 2004
	Deposit a magnet in a white plastic case at the base of the stainless steel post.
65.30	Flood plains, 150 ft. wide, drains S. 30° W.
80.00	Point for the cor. of secs. 29, 30, 31, and 32. Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.

**Survey of the Subdivisional Lines,
T. 24 N., R. 24 E., Gila and Salt River Meridian, Arizona**

CHAINS	
	T 24 N R 24 E S 30 S 29 S 31 S 32 2004
	Deposit a magnet in a white plastic case at the base of the stainless steel post. Land, rolling and broken. Soil, rocky and sandy clay. No timber; undergrowth, greasewood, scattered brush and native grasses.
	<hr/> From the cor. of secs. 28, 29, 32, and 33. N. 89°58' W., bet. secs. 29 and 32. Over rolling and broken land.
3.70	Trail road, bears N. 70° E. and S. 70° W.
37.77	High Voltage transmission line, bears N. 35° E. and S. 35° W.
40.00	Point for the 1/4 sec. cor. of secs. 29 and 32. Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.
	T 24 N R 24 E S 29 1/4 ——— S 32 2004
	Deposit a magnet in a white plastic case at the base of the stainless steel post.
63.00	Earthen dike, 5 ft. wide, 6 ft. high, bears S. 35° E. and N. 35° W.
76.50	Earthen dike, 5 ft. wide, 6 ft. high, bears S. 65° E. and N. 65° W.
80.00	The cor. of secs. 29, 30, 31, and 32.

**Survey of the Subdivisional Lines,
T. 24 N., R. 24 E., Gila and Salt River Meridian, Arizona**

CHAINS	
	<p>Land, rolling and broken. Soil, rocky and sandy clay. No timber; undergrowth, greasewood, scattered brush and native grasses.</p> <hr/> <p>N. 89°58' W., bet. secs. 30 and 31.</p> <p>Over rolling land.</p>
25.58	Navajo Route 9003, a graded road, 16 ft. wide, bears S. 15° E. and N. 15° W.
40.00	<p>Point for the 1/4 sec. cor. of secs. 30 and 31.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center;"> <p>T 24 N R 24 E S 30 1/4 ——— S 31</p> <p>2004</p> </div>
	<p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p>
76.27	<p>The cor. of secs. 25, 30, 31, and 36 on the W. bdy. of the Tp., hereinbefore described.</p> <p>Land, rolling. Soil, sandy clay. No timber; undergrowth, greasewood, scattered brush and native grasses.</p> <hr/>
	<p>From the cor. of secs. 29, 30, 31, and 32.</p> <p>N. 0°03' W., bet. secs. 29 and 30.</p> <p>Over rolling land.</p>
40.00	<p>Point for the 1/4 sec. cor. of secs. 29 and 30.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p>

**Survey of the Subdivisional Lines,
T. 24 N., R. 24 E., Gila and Salt River Meridian, Arizona**

CHAINS	
	T 24 N R 24 E 1/4 S 30 S 29 2004
	Deposit a magnet in a white plastic case at the base of the stainless steel post.
80.00	Point for the cor. of secs. 19, 20, 29, and 30.
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.
	T 24 N R 24 E S 19 S 20 S 30 S 29 2004
	Deposit a magnet in a white plastic case at the base of the stainless steel post.
	Land, rolling. Soil, sandy clay. No timber; undergrowth, greasewood, scattered brush and native grasses.
	From the cor. of secs. 20, 21, 28, and 29.
	N. 89°58' W., bet. secs. 20 and 29.
	Over rolling land.
16.25	Wash, 30 ft. wide, 12 ft. deep, drains S. 10° W.
40.00	Point for the 1/4 sec. cor. of secs. 20 and 29.
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.
	T 24 N R 24 E S 20 1/4 ——— S 29 2004
	Deposit a magnet in a white plastic case at the base of the stainless steel post.

**Survey of the Subdivisional Lines,
T. 24 N., R. 24 E., Gila and Salt River Meridian, Arizona**

CHAINS	
80.00	<p>The cor. of secs. 19, 20, 29, and 30.</p> <p>Land, rolling and broken. Soil, rocky and sandy clay. No timber; undergrowth, greasewood, scattered brush and native grasses.</p> <hr/> <p>N. 89°58' W., bet. secs. 19 and 30.</p> <p>Over rolling land.</p>
40.00	<p>Point for the 1/4 sec. cor. of secs. 19 and 30.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T 24 N R 24 E S 19 1/4 ——— S 30</p> <p style="text-align: center;">2004</p> <p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p>
44.35	<p>Navajo Route 9003, a graded road, 20 ft. wide, bears S. 5° E. and N. 5° W.</p>
76.19	<p>The cor. of secs. 19, 24, 25, and 30 on the W. bdy. of the Tp., hereinbefore described.</p> <p>Land, rolling. Soil, sandy clay. No timber; undergrowth, greasewood, scattered brush and native grasses.</p> <hr/> <p>From the cor. of secs. 19, 20, 29, and 30.</p> <p>N. 0°03' W., bet. secs. 19 and 20.</p> <p>Over rolling and broken land.</p>
21.30	<p>Earthen dike, 30 ft. wide at base, 5 ft. high, bears S. 85° E. and N. 85° W.</p>
32.35	<p>Navajo Route 9606, a graded road, 20 ft. wide, bears S. 75° E. and N. 75° W.</p>
40.00	<p>Point for the 1/4 sec. cor. of secs. 19 and 20.</p>

**Survey of the Subdivisional Lines,
T. 24 N., R. 24 E., Gila and Salt River Meridian, Arizona**

CHAINS	
	<p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T 24 N R 24 E 1/4 S 19 S 20</p> <p style="text-align: center;">2004</p> <p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p>
41.08	Underground gas pipeline, bears E. and W.
41.80	Underground gas pipeline, bears E. and W.
80.00	Point for the cor. of secs. 17, 18, 19, and 20.
	<p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T 24 N R 24 E S 18 S 17 S 19 S 20</p> <p style="text-align: center;">2004</p> <p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p> <p>Land, rolling and broken. Soil, rocky and sandy clay. No timber; undergrowth, greasewood, scattered brush and native grasses.</p> <hr/> <p>From the cor. of secs. 16, 17, 20, and 21.</p> <p>N. 89°58' W., bet. secs. 17 and 20.</p> <p>Over rolling and broken land.</p>
40.00	Point for the 1/4 sec. cor. of secs. 17 and 20.
	<p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p>

**Survey of the Subdivisional Lines,
T. 24 N., R. 24 E., Gila and Salt River Meridian, Arizona**

CHAINS	
	<p align="center">T 24 N R 24 E S 17 1/4 ——— S 20</p> <p align="center">2004</p>
80.00	<p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p> <p>The cor. of secs. 17, 18, 19, and 20.</p> <p>Land, rolling and broken. Soil, rocky and sandy clay. No timber; undergrowth, greasewood, scattered brush and native grasses.</p> <hr/>
40.00	<p>N. 89°58' W., bet. secs. 18 and 19.</p> <p>Over rolling and broken land.</p> <p>Point for the 1/4 sec. cor. of secs. 18 and 19.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p>
76.10	<p align="center">T 24 N R 24 E S 18 1/4 ——— S 19</p> <p align="center">2004</p> <p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p> <p>The cor. of secs. 13, 18, 19, and 24 on the W. bdy. of the Tp., hereinbefore described.</p> <p>Land, rolling and broken. Soil, sandy clay. No timber; undergrowth, greasewood, scattered brush and native grasses.</p> <hr/>
40.00	<p>From the cor. of secs. 17, 18, 19, and 20.</p> <p>N. 0°03' W., bet. secs. 17 and 18.</p> <p>Over rolling and broken land.</p> <p>Point for the 1/4 sec. cor. of secs. 17 and 18.</p>

**Survey of the Subdivisional Lines,
T. 24 N., R. 24 E., Gila and Salt River Meridian, Arizona**

CHAINS	
	<p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T 24 N R 24 E 1/4 S 18 S 17</p> <p style="text-align: center;">2004</p> <p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p>
80.00	<p>Point for the cor. of secs. 7, 8, 17, and 18.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T 24 N R 24 E S 7 S 8 ----- S 18 S 17 2004</p> <p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p> <p>Land, rolling and broken. Soil, rocky and sandy clay. No timber; undergrowth, greasewood, scattered brush and native grasses.</p> <hr/> <p>From the cor. of secs. 8, 9, 16, and 17.</p> <p>N. 89°58' W., bet. secs. 8 and 17.</p> <p>Over rolling and broken land.</p>
16.85	Rim of mesa, bears N. and S.
40.00	<p>Point for the 1/4 sec. cor. of secs. 8 and 17.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in ground, with brass cap mkd.</p> <p style="text-align: center;">T 24 N R 24 E S 8 1/4 ----- S 17</p> <p style="text-align: center;">2004</p>

**Survey of the Subdivisional Lines,
T. 24 N., R. 24 E., Gila and Salt River Meridian, Arizona**

CHAINS	<p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p>
80.00	<p>The cor. of secs. 7, 8, 17, and 18.</p> <p>Land, rolling and broken. Soil, rocky and sandy clay. No timber; undergrowth, greasewood, scattered brush and native grasses.</p> <hr/> <p>N. 89°58' W., bet. secs. 7 and 18.</p> <p>Over rolling land.</p>
40.00	<p>Point for the 1/4 sec. cor. of secs. 7 and 18.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center; margin: 10px 0;"> <p>T 24 N R 24 E S 7 1/4 ——— S 18</p> <p>2004</p> </div>
76.01	<p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p> <p>The cor. of secs. 7, 12, 13, and 18 on the W. bdy. of the Tp., hereinbefore described.</p> <p>Land, rolling. Soil, sandy clay. No timber; undergrowth, greasewood, scattered brush and native grasses.</p> <hr/> <p>From the cor. of secs. 7, 8, 17, and 18.</p> <p>N. 0°03' W., bet. secs. 7 and 8.</p> <p>Over rolling land.</p>
40.00	<p>Point for the 1/4 sec. cor. of secs. 7 and 8.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p>

**Survey of the Subdivisional Lines,
T. 24 N., R. 24 E., Gila and Salt River Meridian, Arizona**

CHAINS	
	T 24 N R 24 E 1/4 S 7 S 8 2004
	Deposit a magnet in a white plastic case at the base of the stainless steel post.
80.00	Point for the cor. of secs. 5, 6, 7, and 8. Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.
	T 24 N R 24 E S 6 S 5 --- S 7 S 8 2004
	Deposit a magnet in a white plastic case at the base of the stainless steel post.
	Land, rolling. Soil, sandy clay. No timber; undergrowth, greasewood, scattered brush and native grasses.
	From the cor. of secs. 4, 5, 8, and 9. N. 89°58' W., bet. secs. 5 and 8. Over rolling and broken land.
40.00	Point for the 1/4 sec. cor. of secs. 5 and 8. Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.
	T 24 N R 24 E S 5 1/4 ——— S 8 2004
	Deposit a magnet in a white plastic case at the base of the stainless steel post.
80.00	The cor. of secs. 5, 6, 7, and 8.

**Survey of the Subdivisional Lines,
T. 24 N., R. 24 E., Gila and Salt River Meridian, Arizona**

CHAINS	
	<p>Land, rolling and broken. Soil, rocky and sandy clay. Timber, scattered juniper; undergrowth, greasewood, scattered brush and native grasses.</p> <hr/> <p>N. 89°58' W., bet. secs. 6 and 7.</p> <p>Over rolling land.</p>
40.00	<p>Point for the 1/4 sec. cor. of secs. 6 and 7.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center;"> <p>T 24 N R 24 E S 6 1/4 ——— S 7</p> <p>2004</p> </div> <p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p>
75.93	<p>The cor. of secs. 1, 6, 7, and 12 on the W. bdy. of the Tp., hereinbefore described.</p> <p>Land, rolling. Soil, rocky and sandy clay. No timber; undergrowth, greasewood, scattered brush and native grasses.</p> <hr/> <p>From the cor. of secs. 5, 6, 7, and 8.</p> <p>N. 0°03' W., bet. secs. 5 and 6.</p> <p>Over rolling and broken land.</p>
40.00	<p>Point for the 1/4 sec. cor. of secs. 5 and 6.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center;"> <p>T 24 N R 24 E 1/4 S 6 S 5</p> <p>2004</p> </div> <p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p>

**Survey of the Subdivisional Lines,
T. 24 N., R. 24 E., Gila and Salt River Meridian, Arizona**

CHAINS

77.67

Point for the closing cor. of secs. 5 and 6, at intersection with the Sixth Standard Parallel North, on the N. bdy. of the Tp.

Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 20 ins. below the surface of the ground, with brass cap mkd.

T 25 N R 24 E	
S 31	
S 6	S 5
T 24 N	R 24 E
C C	

2004

from which

A stainless steel post, 28 ins. long, 2 1/2 ins. diam., set 24 ins. in the ground for a reference monument, bears S. 79°48' E., 100.00 ft. dist., with brass cap mkd. RM T24N R24E S5 100.0 FT. TO COR. 2004 and an arrow pointing to the cor. Deposit a magnet in a white plastic case at the base of the stainless steel post. Set a steel fence post nearby.

A stainless steel post, 28 ins. long, 2 1/2 ins. diam., set 24 ins. in the ground for a reference monument, bears S. 10°12' W., 150.0 ft. dist., with brass cap mkd. RM T24N R24E S6 150.0 FT. TO COR. 2004 and an arrow pointing to the cor. Deposit a magnet in a white plastic case at the base of the stainless steel post. Set a steel fence post nearby.

Deposit a magnet in a white plastic case at the base of the stainless steel post at the closing cor.

Cor. is located on the E. edge of the Navajo Route 6322, a graded road, 18 ft. wide, bears NE and SW.

From this cor. point, the stan. 1/4 sec. cor. of sec. 31, T. 25 N., R. 24 E., bears S. 89°55' E., 39.21 chs. dist., monumented with a stainless steel post, 2 1/2 ins. diam., firmly set, projecting 4 ins. above ground with brass cap mkd. SC T25N R24E 1/4 S31 2001.

**Survey of the Subdivisional Lines,
T. 24 N., R. 24 E., Gila and Salt River Meridian, Arizona**

CHAINS

From this same cor. point, a sandstone, 9 x 3 ins., firmly set, projecting 16 ins. above ground, bears S. 1°21' E., 6.10 chs. dist., with no marks visible, witnessed by a mound of stone, 3 ft. base, 1 ft. high, to the N., and a galvanized steel fence post with a tag mkd. County Surveyors Office. This corner was recovered by Jones Curtiss in 2002, and described in the field notes of dependent resurvey of the Sixth Standard Parallel North(south boundary), T. 25 N., R. 23 E.

From this same cor. point, the stan. cor. of T. 25 N., Rs. 23 and 24 E., bears N. 89°55' W., 96 lks. dist., monumented with a stainless steel post, 2 1/2 ins. diam., firmly set, 4 ins. below the surface of the ground with brass cap mkd. SC T25N R23E R24E S36 S31 2002.

from which the 2002 reference monuments

A stainless steel post, 2 1/2 ins. diam., bears N. 30°00' E., 100.0 ft. dist., firmly set, projecting 4 ins. above ground, with brass cap mkd. RM SC T25N R24E S31 100.0 FT. TO COR 2002, and an arrow pointing toward the cor., witnessed by a steel fence post nearby.

A stainless steel post, 2 1/2 ins. diam., bears N. 60°00' W., 50.0 ft. dist., firmly set, projecting 4 ins. above ground, with brass cap mkd. RM SC T25N R23E S36 50.0 FT. TO COR 2002, and an arrow pointing toward the cor., witnessed by a steel fence post nearby.

Land, rolling and broken.

Soil, rocky and sandy clay.

No timber; undergrowth, greasewood, scattered brush and native grasses.

Point for the 1/4 sec. cor. of sec. 5 only, T. 24 N., R. 24 E., at midpoint on the N. bdy. of sec. 5.

Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.

T 25 N R 24 E

1/4 S 5

T 24 N R 24 E

2004

Deposit a magnet in a white plastic case at the base of the stainless steel post.

**Survey of the Subdivisional Lines,
T. 24 N., R. 24 E., Gila and Salt River Meridian, Arizona**

CHAINS

From this cor. point, the stan. cor. of secs. 31 and 32, T. 25 N., R. 24 E., bears S. 89°55' E., 39.38 chs. dist., hereinbefore described.

From this same cor. point, the stan. 1/4 sec. cor. of sec. 31, T. 25 N., R. 24 E., bears N. 89°55' W., 79 lks. dist., hereinbefore described.

Point for the 1/4 sec. cor. of sec. 6 only, T. 24 N., R. 24 E., at 40.00 chs. westerly from the closing cor. of secs. 5 and 6, on the N. bdy. of sec. 6.

Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.

T 25 N R 24 E

1/4 S 6

T 24 N R 24 E

2004

Deposit a magnet in a white plastic case at the base of the stainless steel post.

From this cor. point, the stan. cor. of T. 25 N., Rs. 23 and 24 E., bears S. 89°55' E., 39.04 chs. dist., hereinbefore described.

From this same cor. point, the stan. 1/4 sec. cor. of sec. 36, T. 25 N., R. 23 E., bears N. 89°55' W., 1.13 chs. dist., hereinbefore described.

T. 24 N., R. 24 E., Gila and Salt River Meridian, Arizona

CHAINS

GENERAL DESCRIPTION

The area surveyed is within the Navajo Indian Reservation, approximately 5 miles east southeast of Greasewood, Arizona. The terrain is mostly rolling land with areas of broken badlands atop of mesa. Drainage is to the southwest.

The elevation varies from 5800 to 6800 feet above sea level. The soil is sandy and some areas of gravelly rocky clay. Timber consist of scattered juniper. Undergrowth principally consists of scattered brush, cacti, greasewood, and native grasses.

Principal access to the township is provided by Navajo Route 28, a graded road, which enters the township in section 2 and exits in section 1. The other graded road, Navajo Route 9606, which enters the township in section 19 and exits in section 25, from these two main roads there are numerous trail roads through out the township to residential areas. Much of the area is used for grazing livestock. There is no mining activity in the township.

The mean magnetic declination of $11\ 1/2^\circ$ E. was derived from the computer program GEOMAGIX, utilizing the World Magnetic Model for Epoch 2005 for the dates of survey.

CERTIFICATE OF SURVEY

I, Leonard R. Sandoval, Cadastral Surveyor, HEREBY CERTIFY upon honor, that in pursuance of special instructions bearing date of the 24th day of May, 2004, I have surveyed the Sixth Guide Meridian East (east boundary), the south and west boundaries and the subdivisional lines, T. 24 N., R. 24 E., of the Gila and Salt River Meridian, in the State of Arizona, which are represented in the foregoing field notes as having been executed by me and under my direction. Said survey has been made in strict conformity with said special instructions, the Manual of Instructions for the Survey of the Public Lands of the United States, 1973, and in specific manner described in the foregoing field notes.

8-25-05
(Date)

Leonard R. Sandoval
(Cadastral Surveyor)

CERTIFICATE OF APPROVAL

BUREAU OF LAND MANAGEMENT
Phoenix, Arizona

The foregoing field notes of the survey of the Sixth Guide Meridian East (east boundary), the south and west boundaries and the subdivisional lines, T. 24 N., R. 24 E., Gila and Salt River Meridian, in the State of Arizona, executed by Leonard R. Sandoval, Cadastral Surveyor, having been critically examined and found correct, are hereby approved.

1-9-2006
(Date)

Stephen K. Hansen
~~Acting~~(Chief Cadastral Surveyor of Arizona)

~~CERTIFICATE OF TRANSCRIPT~~

I CERTIFY That the foregoing transcript of the field notes of the above described surveys in T. 24 N., R. 24 E., Gila and Salt River Meridian, Arizona, is a true copy of the original field notes.

~~_____~~
(Date)

~~_____~~
~~Acting~~(Chief Cadastral Surveyor of Arizona)

