

**ORIGINAL**

**UNITED STATES  
DEPARTMENT OF THE INTERIOR  
BUREAU OF LAND MANAGEMENT**

FIELD NOTES

OF THE DEPENDENT RESURVEY OF  
A PORTION OF THE TENTH STANDARD PARALLEL NORTH (NORTH BOUNDARY)

AND

THE SURVEY OF A PORTION OF THE SUBDIVISIONAL LINES

**TOWNSHIP 40 NORTH, RANGE 3 WEST,**

OF THE GILA AND SALT RIVER MERIDIAN,

IN THE STATE OF ARIZONA.

**EXECUTED BY**

**Adrien J. Rodriguez, Cadastral Surveyor**

Under Special Instructions dated July 21, 2004, approved July 21, 2004, which provided for the surveys included under Group No. 940, and assignment instructions dated July 21, 2004.

**Survey commenced July 27, 2004**

**Survey completed August 25, 2004**

## INDEX DIAGRAM

TOWNSHIP 40 NORTH                  RANGE 3 WEST  
GILA AND SALT RIVER MERIDIAN

<b>7</b>	<b>6</b>	<b>6</b>	<b>5</b>	<b>5</b>	<b>4</b>
<b>6</b>	<b>49 5</b>	<b>39 4</b>	<b>31 3</b>	<b>23 2</b>	<b>15 1</b>
<b>49</b>	<b>48</b>	<b>38</b>	<b>31</b>	<b>23</b>	<b>14</b>
<b>7</b>	<b>47 8</b>	<b>37 9</b>	<b>30 10</b>	<b>22 11</b>	<b>14 12</b>
<b>46</b>	<b>46</b>	<b>37</b>	<b>29</b>	<b>21</b>	<b>13</b>
<b>18</b>	<b>45 17</b>	<b>36 16</b>	<b>29 15</b>	<b>21 14</b>	<b>12 13</b>
<b>44</b>	<b>44</b>	<b>35</b>	<b>28</b>	<b>20</b>	<b>11</b>
<b>19</b>	<b>43 20</b>	<b>35 21</b>	<b>27 22</b>	<b>19 23</b>	<b>11 24</b>
<b>42</b>	<b>42</b>	<b>34</b>	<b>27</b>	<b>19</b>	<b>10</b>
<b>30</b>	<b>41 29</b>	<b>33 28</b>	<b>26 27</b>	<b>18 26</b>	<b>9 25</b>
<b>40</b>		<b>33</b>			
<b>31</b>	<b>32</b>	<b>33</b>	<b>25 34</b>	<b>16 35</b>	<b>8 36</b>

## T. 40 N., R. 3 W., Gila and Salt River Meridian, Arizona

## CHAINS

The following field notes describe the dependent resurvey of a portion of the Tenth Standard Parallel North (North Boundary) and the survey of a portion of the subdivisional lines, Township 40 North, Range 3 West, Gila and Salt River Meridian, Arizona.

The history of surveys pertaining to this survey is as follows:

J. C. Thoma, U.S. Surveyor, surveyed a portion of the Tenth Standard Parallel North (North Boundary) and surveyed the south and west boundaries, in 1914. Donald E. Harding, Cadastral Engineer, surveyed the east boundary and a portion of the subdivisional lines in 1955. W. William Foster, Cadastral Surveyor, dependently resurveyed a portion of the west boundary in 2003. Geoffrey A. Graham, Cadastral Surveyor, dependently resurveyed the east boundary in 2004.

The survey was executed in accordance with the specifications as set forth in the Manual of Instructions for the Survey of the Public Lands of the United States, 1973, and the Special Instructions dated July 21, 2004, for Group Number 940, Arizona.

The true meridian direction and length of all lines were determined by real time kinematic global positioning system observations using Trimble Navigation 5800 model receivers.

Preliminary to the resurvey, the lines of the prior surveys were retraced and search was made for all corners and other calls of record. Identified corners were remonumented in their original positions. Lost corners were reestablished and remonumented at proportionate positions based on the official record. The retracement data were thoroughly verified and only the true line field notes are given herein.

Geodetic control was derived from Global Positioning System (GPS) static post observations processed by National Geodetic Survey, Online Positioning User Service (OPUS), utilizing Continuously Operating Reference Stations (CORS) ECHO CANYON S.P. CORS ARP, FREDONIA CORS ARP, FERNO MESA CORS ARP. The NAD 83 (CORS96) (EPOCH: 2002.000), geographic position of the corner of sections 25 and 36, on the east boundary of the township, is as follows:

Latitude: 36°49'54.90" N.                      Longitude: 112°33'26.68" W.

The mean magnetic declination is 12 1/2° E.

**Dependent Resurvey of a Portion of the  
Tenth Standard Parallel North (North Boundary),  
T. 40 N., R. 3 W., Gila and Salt River Meridian, Arizona**

CHAINS


Restoring the survey executed by  
J. C. Thoma, in 1914

---

Beginning at the true point for the stan. cor. of Tps. 41 N., Rs. 2 and 3 W., determined at proportionate dist., there is no remaining evidence of the original cor., falls in Kanab Creek, 300 ft. wide, 25 ft. deep, course S. 35° W., where it is impracticable to establish a permanent monument.

From this true point, the point selected for a witness cor. to the stan. cor. of Tps. 41 N., Rs. 2 and 3 W., bears S. 45°00' E., 5.00 chs. dist.

Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd..



2004

Deposit a magnet, in a white plastic case, at the base of the stainless steel post.

From this same true point, the stan. 1/4 sec. cor. of sec. 31, T. 41 N., R. 2 W., bears East, 40.02 chs. dist., monumented with an iron post, 1 in. diam., firmly set, projecting 9 ins. above ground, with brass cap mkd. SC T41N R2W 1/4 S31 2004 1911.

Cor. is located alongside a barbed wire fence, bears E. and W.

From this same true point, the closing cor. of Tps. 40 N., Rs. 2 and 3 W., bears East, 5.28 chs. dist., monumented with an iron post, 2 1/2 ins. diam., firmly set, projecting 4 ins. above ground, with brass cap mkd. T41N R2W S31 S1 S6 R3W R2W CC T40N 1954 2004.

Cor. is located alongside a barbed wire fence, bears E. and W.

West, on the S. bdy. of sec. 36, T. 41 N., R. 3 W.

Over rolling terrain covered with sage and scattered grasses.

40.02

Point for the stan. 1/4 sec. cor. of sec. 36, T. 41 N., R. 3 W., at proportionate dist., there is no evidence of the position of the orig. cor., the original iron post, 1 in. diam., with brass cap mkd. S36 1914, was found nearby laying loose on the ground.

**Dependent Resurvey of a Portion of the  
Tenth Standard Parallel North (North Boundary),  
T. 40 N., R. 3 W., Gila and Salt River Meridian, Arizona**

CHAINS	
	<p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">SC T 41 N R 3 W 1/4 S 36</p> <hr style="width: 10%; margin: auto;"/> <p style="text-align: center;">2004</p> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p> <p>Bury the original iron post alongside the stainless steel post.</p>
80.04	<p>The stan. cor. of secs. 35 and 36, T. 41 N., R. 3 W., monumented with an iron post, 3 ins. diam., firmly set, projecting 13 ins. above ground, with brass cap mkd. T41N R3W S35 S36 1914.</p> <p>Add the marks SC 2004 to the brass cap.</p> <hr/> <p>West, on the S. bdy. of sec. 35, T. 41 N., R. 3 W.</p> <p>Over rolling terrain covered with sage and scattered grasses.</p>
39.99	<p>The stan. 1/4 sec. cor. of sec. 35, T. 41 N., R. 3 W., monumented with an iron post, 1 in. diam., firmly set, projecting 10 ins. above ground, with brass cap mkd. S35 1914.</p> <p>Add the marks SC T41N R3W 1/4 2004 to the brass cap.</p> <hr/> <p>West, beginning new measurement.</p>
40.04	<p>The stan. cor. of secs. 34 and 35, T. 41 N., R. 3 W., monumented with an iron post, 3 ins. diam., firmly set, projecting 12 ins. above ground, with brass cap mkd. T41N R3W S34 S35 1914.</p> <p>Add the marks SC 2004 to the brass cap.</p> <hr/> <p>West, on the S. bdy. of sec. 34, T. 41 N., R. 3 W.</p> <p>Over rolling terrain covered with sage and scattered grasses.</p>
6.90	<p>Arizona State Highway No. 389, asphalt surfaced, 35 ft. wide, bears N. 45° E. and S. 45° W.</p>
40.08	<p>The stan. 1/4 sec. cor. of sec. 34, T. 41 N., R. 3 W., monumented with an iron post, 1 in. diam., firmly set, flush with the ground, badly rusted, with brass cap mkd. S34 1914.</p>

**Dependent Resurvey of a Portion of the  
Tenth Standard Parallel North (North Boundary),  
T. 40 N., R. 3 W., Gila and Salt River Meridian, Arizona**

CHAINS	
	<p>At the corner point</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">SC T 41 N R 3 W 1/4 S 34</p> <hr style="width: 10%; margin: auto;"/> <p style="text-align: center;">2004</p> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p> <p>Bury the original iron post alongside the stainless steel post.</p> <hr style="width: 20%; margin: auto;"/> <p>West, beginning new measurement.</p>
40.02	<p>The stan. cor. of secs. 33 and 34, T. 41 N., R. 3 W., monumented with an iron post, 3 ins. diam., firmly set, flush with the ground, with brass cap mkd. T41N R3W S33 S34 1914.</p> <p>Add the marks SC 2004 to the brass cap.</p> <hr style="width: 50%; margin: auto;"/> <p>West, on the S. bdy. of sec. 33, T. 41 N., R. 3 W.</p> <p>Over rolling terrain covered with sage and scattered grasses.</p>
40.02	<p>The stan. 1/4 sec. cor. of sec. 33, T. 41 N., R. 3 W., monumented with an iron post, 1 in. diam., firmly set, projecting 10 ins. above ground, with brass cap mkd. S33 1914.</p> <p>Add the marks SC T41N R3W 1/4 2004 to the brass cap.</p> <hr style="width: 50%; margin: auto;"/> <p>N. 89°59' W., beginning new measurement.</p>
40.02	<p>The stan. cor. of secs. 32 and 33, T. 41 N., R. 3 W., monumented with an iron post, 3 ins. diam., firmly set, projecting 14 ins. above ground, with brass cap mkd. T41N R3W S32 S33 1914.</p> <p>Add the marks SC and 2004 to the brass cap.</p> <hr style="width: 50%; margin: auto;"/> <p>West, on the S. bdy. of sec. 32, T. 41 N., R. 3 W.</p> <p>Over rolling and broken terrain covered with sage, scattered juniper and grasses.</p>

**Dependent Resurvey of a Portion of the  
Tenth Standard Parallel North (North Boundary),  
T. 40 N., R. 3 W., Gila and Salt River Meridian, Arizona**

CHAINS	
39.99	<p>The stan. 1/4 sec. cor. of sec. 32, T. 41 N., R. 3 W., monumented with an iron post, 1 in. diam., firmly set, projecting 12 ins. above ground, with brass cap mkd. S32 1914.</p> <p>Add the marks SC T41N R3W 1/4 2004 to the brass cap.</p> <hr style="width: 20%; margin: 10px auto;"/> <p>S. 89°58' W., beginning new measurement.</p>
40.05	<p>The stan. cor. of secs. 31 and 32, monumented with an iron post, 3 ins. diam., firmly set, projecting 15 ins. above ground, with the brass cap mkd. T41N R3W S31 S32 2003 1914.</p> <p>Add the marks SC 2004 to the brass cap.</p> <hr style="width: 20%; margin: 10px auto;"/> <p>West, on the S. bdy. of sec. 31, T. 41 N., R. 3 W.</p> <p>Over rolling terrain covered with sage, scattered juniper and sage.</p>
40.03	<p>The stan. 1/4 sec. cor. of sec. 31, monumented with an iron post, 1 in. diam., firmly set, projecting 13 ins. above ground, with brass cap mkd. SC T41N R3W 1/4 S31 2003 1914.</p> <p>Add the marks 2004 to the brass cap.</p> <hr style="width: 20%; margin: 10px auto;"/> <p>S. 89°59' W., beginning new measurement.</p>
33.10	<p>The closing cor. of Tps. 40 N., Rs. 3 and 4 W., monumented with an iron post, 3 ins. diam., firmly set, projecting 11 ins. above ground, with the brass cap mkd. T41N R4W R3W S36 S31 CC S1 S6 R4W R3W T40N 2003 1914</p> <p>Add the marks 2004 to the brass cap.</p>
40.03	<p>The stan. cor. of Tps. 41 N., Rs. 3 and 4 W., monumented with an iron post, 3 ins. diam., firmly set, projecting 9 ins. above ground, with the brass cap mkd. T41N R4W S36 S31 R3W 2003 1914.</p> <p>Add the marks SC 2004 to the brass cap.</p> <hr style="width: 20%; margin: 10px auto;"/> <p style="text-align: center;"><b>Survey of a Portion of the Subdivisional Lines, T. 40 N., R. 3 W., Gila and Salt River Meridian, Arizona</b></p> <hr style="width: 20%; margin: 10px auto;"/> <p>From the cor. of secs. 1, 2, 35 and 36, on the S. bdy. of the Tp., monumented with an iron post, 3 ins. diam., firmly set, projecting 30 ins. above ground, in a supporting mound of stone, 4 ft. base, 2 ft. high, with the brass cap mkd. T40N S35 S36 R3W S2 S1 T39N 1914.</p>

**Survey of the Subdivisional Lines,  
T. 40 N., R. 3 W., Gila and Salt River Meridian, Arizona**

CHAINS							
	Add the marks 2004 to the brass cap.						
	N. 0°04' E., bet. secs. 35 and 36.						
	Over rolling terrain covered with sage, scattered juniper and grasses.						
40.00	Point for the 1/4 sec. cor. of secs. 35 and 36, not monumented.						
44.75	Trail road, bears N. 55° E. and S. 55° W.						
46.25	High voltage transmission line, bears N. 65° E. and S. 65° W.						
80.00	Point for the cor. of secs. 25, 26, 35 and 36.						
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 11 ins. in the ground, to bedrock, in a supporting mound of stone, 5 ft. base, to top, with brass cap mkd.						
	<table style="margin-left: auto; margin-right: auto;"> <tr> <td>T 40 N</td> <td>R 3 W</td> </tr> <tr> <td>S 26</td> <td>S 25</td> </tr> <tr> <td>S 35</td> <td>S 36</td> </tr> </table>	T 40 N	R 3 W	S 26	S 25	S 35	S 36
T 40 N	R 3 W						
S 26	S 25						
S 35	S 36						
	2004						
	Deposit a magnet, in a white plastic case, at the base of the stainless steel post.						
	Land, rolling.						
	Soil, sandy.						
	Undergrowth, sage and native grasses.						
	<hr/>						
	From the cor. of secs. 25 and 36, on the E. bdy. of the Tp., monumented with a stainless steel post, 2 1/2 ins. diam., firmly set, projecting 9 ins. above ground, in a mound of stone, 3 1/2 ft. base, 6 ins. high, with the brass cap mkd. T40N S25 S36 R3W T40N R2W S30 2004.						
	Cor. is located 7 lks. N. of a barbed wire fence, bears E. and W.						
	N. 89°57' W., bet. secs. 25 and 36.						
	Over rolling terrain covered with sage and scattered grasses.						
13.30	High voltage transmission line, bears N. 65° E. and S. 65° W.						
15.15	Trail road, bears N. 25° E. and S. 20° W.						
24.45	Trail road, bears S. 10° E. and N. 10° W.						



**Survey of the Subdivisional Lines,  
T. 40 N., R. 3 W., Gila and Salt River Meridian, Arizona**

CHAINS	
40.02	<p>Point for the 1/4 sec. cor. of secs. 25 and 36.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 9 ins. in the ground, to bedrock, in a supporting mound of stone, 4 ft. base, to top, with brass cap mkd.</p> <p style="text-align: center;">T 40 N R 3 W S 25 1/4 ——— S 36</p> <p style="text-align: center;">2004</p> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p> <p>Cor. is located 5 lks. N. of a barbed wire fence, bears E. and W.</p>
80.04	<p>The cor. of secs. 25, 26, 35 and 36.</p> <p>Land, rolling. Soil, sandy. Undergrowth, sage and native grasses.</p> <hr/> <p>N. 0°04' E., bet. secs. 25 and 26.</p> <p>Over rolling terrain covered with sage and scattered grasses.</p>
0.05	Barbed wire fence, bears E. and W.
40.00	<p>Point for the 1/4 sec. cor. of secs. 25 and 26.</p> <p>Set a brass tablet, 3 1/4 ins. diam., 3 1/2 ins. stem, cemented in a drill hole in solid rock, with top mkd.</p> <p style="text-align: center;">T 40 N R 3 W 1/4 S 26   S 25</p> <p style="text-align: center;">2004</p> <p>Deposit a magnet at the base of the brass tablet.</p> <p>Raise a mound of stone, 2 ft. base, 2 1/2 ft. high, W. of cor.</p>
45.25	Wash, 25 ft. wide, 25 ft. deep, drains S. 55° W.
80.00	Point for the cor. of secs. 23, 24, 25 and 26.

Survey of the Subdivisional Lines,  
T. 40 N., R. 3 W., Gila and Salt River Meridian, Arizona

CHAINS	<p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 10 ins. in the ground, to bedrock, in a supporting mound of stone, 5 ft. base, to top, with brass cap mkd.</p> <p style="text-align: center;">             T 40 N R 3 W              S 23   S 24              S 26   S 25           </p> <p style="text-align: center;">2004</p> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p> <p>Land, rolling. Soil, sandy. Undergrowth, sage and native grasses.</p> <hr/> <p>From the cor. of secs. 24 and 25, on the E. bdy. of the Tp., monumented with an iron post, 2 1/2 ins. diam., firmly set, projecting 11 ins. above ground, with an accessory mound of stone, 2 ft. base, 1 ft. high, to the W., with brass cap mkd. T40N R3W S24 S25 R2W S19 2004 1954.</p> <p>N. 89°57' W., bet. secs. 24 and 25.</p> <p>Over rolling terrain covered with sage and scattered grasses.</p>
40.02	<p>True point for the 1/4 sec. cor. of secs. 24 and 25, falls in the center of a dirt stock water tank, 400 x 600 ft., where it is impracticable to establish a permanent monument.</p> <p>From this true point, the point selected for a witness cor. to the 1/4 sec. cor. of secs. 24 and 25, bears S. 45°00' W., 4.37 chs. dist.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 28 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">             WC              T 40 N R 3 W              S 24              1/4 ———              S 25           </p> <p style="text-align: center;">2004</p> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p> <p>Witness cor. is located on a earthen dam, 9 ft. wide, 5 ft. high, bears S. 20° E. and N. 20° W.</p>

**Survey of the Subdivisional Lines,  
T. 40 N., R. 3 W., Gila and Salt River Meridian, Arizona**

CHAINS							
51.35	Trail road, bears S. 30° E. and N. 25° W.						
80.04	The cor. of secs. 23, 24, 25 and 26.						
	Land, rolling. Soil, sandy. Undergrowth, sage and native grasses.						
	<hr/> N. 0°04' E., bet. secs. 23 and 24.						
	Over rolling terrain covered with sage and scattered grasses.						
40.00	Point for the 1/4 sec. cor. of secs. 23 and 24.						
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 25 ins. in the ground, to bedrock, with brass cap mkd.						
	<table border="0" style="margin-left: auto; margin-right: auto;"> <tr> <td>T 40 N</td> <td>R 3 W</td> </tr> <tr> <td></td> <td>1/4</td> </tr> <tr> <td>S 23</td> <td>  S 24</td> </tr> </table>	T 40 N	R 3 W		1/4	S 23	S 24
T 40 N	R 3 W						
	1/4						
S 23	S 24						
	2004						
	Deposit a magnet, in a white plastic case, at the base of the stainless steel post.						
80.00	Point for the cor. of secs. 13, 14, 23 and 24.						
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 23 ins. in the ground, in a collar of stone, with brass cap mkd.						
	<table border="0" style="margin-left: auto; margin-right: auto;"> <tr> <td>T 40 N</td> <td>R 3 W</td> </tr> <tr> <td>S 14</td> <td>  S 13</td> </tr> <tr> <td>S 23</td> <td>  S 24</td> </tr> </table>	T 40 N	R 3 W	S 14	S 13	S 23	S 24
T 40 N	R 3 W						
S 14	S 13						
S 23	S 24						
	2004						
	Deposit a magnet, in a white plastic case, at the base of the stainless steel post.						
	Land, rolling. Soil, sandy. Undergrowth, sage and native grasses.						
	<hr/> From the cor. of secs. 13 and 24, on the E. bdy. of the Tp., monumented with an iron post, 2 1/2 ins. diam., firmly set, projecting 15 ins. above ground, with brass cap mkd. T40N R3W S13 S24 R2W S18 2004 1954.						
	N. 89°57' W., bet. secs. 13 and 24.						

**Survey of the Subdivisional Lines,  
T. 40 N., R. 3 W., Gila and Salt River Meridian, Arizona**

CHAINS	
	Over rolling terrain covered with sage and scattered grasses.
40.02	Point for the 1/4 sec. cor. of secs. 13 and 24.  Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.  <div style="text-align: center;">                     T 40 N R 3 W                            S 13                      1/4 ———                            S 24                       2004                 </div>
	Deposit a magnet, in a white plastic case, at the base of the stainless steel post.
79.05	Graded road, 10 ft. wide, bears S. 20° E. and N. 35° W.
80.04	The cor. of secs. 13, 14, 23 and 24.  Land, rolling. Soil, sandy with broken sandstone. Undergrowth, sage and native grasses.
	----- N. 0°04' E., bet. secs. 13 and 14.
	Over rolling terrain covered with sage and scattered grasses.
1.60	Graded road, 12 ft. wide, bears S. 40° E. and N. 15° W.
40.00	Point for the 1/4 sec. cor. of secs. 13 and 14.  Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 23 ins. in the ground, with brass cap mkd.  <div style="text-align: center;">                     T 40 N R 3 W                            1/4                      S 14   S 13                       2004                 </div>
	Deposit a magnet, in a white plastic case, at the base of the stainless steel post.
80.00	Point for the cor. of secs. 11, 12, 13 and 14.  Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 27 ins. in the ground, with brass cap mkd.

Survey of the Subdivisional Lines,  
T. 40 N., R. 3 W., Gila and Salt River Meridian, Arizona

CHAINS											
	<div style="text-align: center;"> <table border="1"> <tr> <td>T 40 N</td> <td>R 3 W</td> </tr> <tr> <td>S 11</td> <td>S 12</td> </tr> <tr> <td>S 14</td> <td>S 13</td> </tr> </table> <p>2004</p> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p> <p>Land, rolling to flood plain. Soil, sandy and clay. Timber, tamarisk and scattered cottonwood; undergrowth, sage, native grasses and willow.</p> <hr/> <p>From the cor. of secs. 12 and 13, on the E. bdy. of the Tp., monumented with an iron post, 2 1/2 ins. diam., firmly set, projecting 10 ins. above ground, with an accessory mound of stone, 2 ft. base, 1 ft. high, to the W., with brass cap mkd. T40N R3W S12 S13 R2W S7 2004 1954.</p> <p>A steel fence post is located alongside the iron post.</p> <p>N. 89°57' W., bet. secs. 12 and 13.</p> <p>Over rolling terrain covered with sage and scattered grasses.</p> </div>	T 40 N	R 3 W	S 11	S 12	S 14	S 13				
T 40 N	R 3 W										
S 11	S 12										
S 14	S 13										
40.01	<p>Point for the 1/4 sec. cor. of secs. 12 and 13; falls in the center of a wash, 50 ft. wide, 8 ft. deep, drains S. 15° W., where it is impracticable to establish a permanent monument.</p> <p>From this point, the point selected for a witness cor. to the cor. of secs. 11, 12, 13 and 14, bears S. 45°00' W., 3.00 chs. dist.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 25 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center;"> <table border="1"> <tr> <td colspan="2">WC</td> </tr> <tr> <td>T 40 N</td> <td>R 3 W</td> </tr> <tr> <td colspan="2">S 12</td> </tr> <tr> <td>1/4</td> <td>_____</td> </tr> <tr> <td colspan="2">S 13</td> </tr> </table> <p>2004</p> </div> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p>	WC		T 40 N	R 3 W	S 12		1/4	_____	S 13	
WC											
T 40 N	R 3 W										
S 12											
1/4	_____										
S 13											
80.02	<p>The cor. of secs. 11, 12, 13 and 14.</p>										

Survey of the Subdivisional Lines,  
T. 40 N., R. 3 W., Gila and Salt River Meridian, Arizona

CHAINS	<p>Land, low level flood plain. Soil, sandy and clay. Undergrowth, sage.</p> <hr/> <p>N. 0°04' E., bet. secs. 11 and 12.</p> <p>Over rolling terrain covered with sage and scattered grasses.</p> <p>40.00 Point for the 1/4 sec. cor. of secs. 11 and 12.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 25 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T 40 N R 3 W 1/4 S 11   S 12 2004</p> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p> <p>80.00 Point for the cor. of secs. 1, 2, 11 and 12.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 25 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T 40 N R 3 W S 2   S 1 S 11   S 12 2004</p> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p> <p>Land, rolling. Soil, sandy. Undergrowth, sage and native grasses.</p> <hr/> <p>From the cor. of secs. 1 and 12, on the E. bdy. of the Tp., monumented with an iron post, 2 1/2 ins. diam., firmly set, projecting 13 ins. above ground, with brass cap mkd. T40N R3W S1 S12 R2W S6 2004 1954.</p> <p>N. 89°57' W., bet. secs. 1 and 12.</p> <p>Over rolling and hilly terrain covered with sage and scattered grasses.</p>
--------	--

**Survey of the Subdivisional Lines,  
T. 40 N., R. 3 W., Gila and Salt River Meridian, Arizona**

CHAINS	
40.02	<p>Point for the 1/4 sec. cor. of secs. 1 and 12.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 23 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T 40 N R 3 W S 1 1/4 ——— S 12</p> <p style="text-align: center;">2004</p> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p>
80.04	<p>The cor. of secs. 1, 2, 11 and 12.</p> <p>Land, low and rolling. Soil, sandy. Undergrowth, sage and native grasses.</p> <hr/> <p>N. 0°04' E., bet. secs. 1 and 2.</p> <p>Over rolling terrain covered with sage and scattered grasses.</p>
40.00	<p>Point for the 1/4 sec. cor. of secs. 1 and 2.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 25 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T 40 N R 3 W 1/4 S 2   S 1</p> <p style="text-align: center;">2004</p> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p>
74.19	<p>Point for the closing cor. of secs. 1 and 2, on the N. bdy. of the Tp.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 23 ins. in the ground, with brass cap mkd.</p>

Survey of the Subdivisional Lines,  
T. 40 N., R. 3 W., Gila and Salt River Meridian, Arizona

CHAINS	<div style="text-align: center;"> <p>T 41 N R 3 W S 36</p> <hr style="width: 50%; margin: auto;"/> <p>S 2   S 1 T 40 N R 3 W CC</p> <p>2004</p> </div> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p> <p>From this point the stan. cor. of secs. 35 and 36, T. 41 N., R. 3 W., bears West, 5.28 chs. dist., hereinbefore described.</p> <p>Land, rolling. Soil, sandy. Undergrowth, sage and native grasses.</p> <hr/> <p>The point for the 1/4 sec. cor. of sec. 1 only, T. 40 N., R. 3 W., is at midpoint on the N. bdy. of sec. 1.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center;"> <p>T 41 N R 3 W</p> <hr style="width: 50%; margin: auto;"/> <p>1/4 S 1 T 40 N R 3 W</p> <p>2004</p> </div> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p> <p>From this point the stan. 1/4 sec. cor. of sec. 36, T. 41 N., R. 3 W., bears West, 5.28 chs. dist., hereinbefore described.</p> <p>Land, rolling. Soil, sandy. Undergrowth, sage and native grasses.</p> <hr/> <p>From the cor. of secs. 2, 3, 34 and 35, on the S. bdy. of the Tp., monumented with an iron post, 3 ins. diam., firmly set, projecting 16 ins. above ground, with an accessory mound of stone, 3 ft. base, 1 ft. high, to the W., with brass cap mkd. T40N S34 S35 R3W S3 S2 T39N 1914.</p> <p>Add the marks 2004 to the brass cap.</p> <p>N. 0°03' E., bet. secs. 34 and 35.</p>
--------	---



Survey of the Subdivisional Lines,  
T. 40 N., R. 3 W., Gila and Salt River Meridian, Arizona

CHAINS									
	<p>Over rolling and mountainous terrain covered with sage and scattered grasses.</p>								
4.90	<p>Trail road, bears N. 60° E. and S. 60° W.</p>								
6.40	<p>High voltage transmission line, bears N. 80° E. and S. 80° W.</p>								
40.00	<p>Point for the 1/4 sec. cor. of secs. 34 and 35, not monumented.</p>								
80.00	<p>Point for the cor. of secs. 26, 27, 34 and 35.</p>								
	<p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 15 ins. in the ground, to bedrock, in a supporting mound of stone, 3 ft. base, to top, with brass cap mkd.</p>								
	<table border="0" style="margin-left: auto; margin-right: auto;"> <tr> <td>T 40 N</td> <td>R 3 W</td> </tr> <tr> <td>S 27</td> <td>S 26</td> </tr> <tr> <td>S 34</td> <td>S 35</td> </tr> </table>	T 40 N	R 3 W	S 27	S 26	S 34	S 35		
T 40 N	R 3 W								
S 27	S 26								
S 34	S 35								
	<p style="text-align: center;">2004</p>								
	<p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p>								
	<p>Land, rolling and mountainous. Soil, sandy and broken sandstone. Undergrowth, sage and native grasses.</p>								
	<hr/> <p>From the cor. of secs. 25, 26, 35 and 36.</p>								
	<p>N. 89°59' W., bet. secs. 26 and 35.</p>								
	<p>Over rolling and mountainous terrain covered with sage and scattered grasses.</p>								
40.04	<p>Point for the 1/4 sec. cor. of secs. 26 and 35.</p>								
	<p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 2 ins. in the ground, to bedrock, in a supporting mound of stone, 5 ft. base, to top, with brass cap mkd.</p>								
	<table border="0" style="margin-left: auto; margin-right: auto;"> <tr> <td>T 40 N</td> <td>R 3 W</td> </tr> <tr> <td>S 26</td> <td></td> </tr> <tr> <td>1/4</td> <td>—</td> </tr> <tr> <td>S 35</td> <td></td> </tr> </table>	T 40 N	R 3 W	S 26		1/4	—	S 35	
T 40 N	R 3 W								
S 26									
1/4	—								
S 35									
	<p style="text-align: center;">2004</p>								
	<p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p>								

**Survey of the Subdivisional Lines,  
T. 40 N., R. 3 W., Gila and Salt River Meridian, Arizona**

CHAINS	
	Cor. is located 14 lks. S. of a barbed wire fence, bears E. and W.
46.50	Wash, 70 ft. wide, 8 ft. deep, drains S. 25° W.
80.08	The cor. of secs. 26, 27, 34 and 35.  Land, rolling and mountainous. Soil, sandy and broken sandstone. Undergrowth, sage and native grasses.
	N. 0°03' E., bet. secs. 26 and 27.  Over mountainous and rolling terrain covered with sage and scattered grasses.
0.14	Barbed wire fence, bears E. and W.
40.00	Point for the 1/4 sec. cor. of secs. 26 and 27.  Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with brass cap mkd.
	T 40 N R 3 W 1/4 S 27   S 26  2004
	Deposit a magnet, in a white plastic case, at the base of the stainless steel post.  Raise a mound of stone, 3 ft. base, 3 1/2 ft. high, W. of cor.
80.00	Point for the cor. of secs. 22, 23, 26 and 27.  Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 25 ins. in the ground, with brass cap mkd.
	T 40 N R 3 W S 22   S 23 S 27   S 26  2004
	Deposit a magnet, in a white plastic case, at the base of the stainless steel post.

Survey of the Subdivisional Lines,  
T. 40 N., R. 3 W., Gila and Salt River Meridian, Arizona

CHAINS	
	<p>Land, rolling and mountainous. Soil, sandy broken sandstone. Undergrowth, sage and native grasses.</p> <hr/> <p>From the cor. of secs. 23, 24, 25 and 26.</p> <p>N. 89°59' W., bet. secs. 23 and 26.</p> <p>Over rolling and broken terrain covered with sage and scattered grasses.</p>
40.04	<p>Point for the 1/4 sec. cor. of secs. 23 and 26.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 13 ins. in the ground, to bedrock, in a supporting mound of stone, 5 ft. base, to top, with brass cap mkd.</p> <p style="text-align: center;">T 40 N R 3 W S 23 1/4 ——— S 26</p> <p style="text-align: center;">2004</p> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p> <p>Cor. is located 80 lks. N. of a wash, 45 ft. wide, 8 ft. deep, drains S. 70° W.</p>
80.08	<p>The cor. of secs. 22, 23, 26 and 27.</p> <p>Land, rolling and broken. Soil, sandy. Undergrowth, sage and native grasses.</p> <hr/> <p>N. 0°03' E., bet. secs. 22 and 23.</p> <p>Over rolling terrain covered with sage and scattered grasses.</p>
40.00	<p>Point for the 1/4 sec. cor. of secs. 22 and 23.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 22 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T 40 N R 3 W 1/4 S 22   S 23</p> <p style="text-align: center;">2004</p>

**Survey of the Subdivisional Lines,  
T. 40 N., R. 3 W., Gila and Salt River Meridian, Arizona**

CHAINS	<p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p>						
80.00	<p>Point for the cor. of secs. 14, 15, 22 and 23.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 23 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center; margin: 10px 0;"> <table style="margin: auto; border-collapse: collapse;"> <tr> <td style="padding: 0 5px;">T 40 N</td> <td style="padding: 0 5px;">R 3 W</td> </tr> <tr> <td style="padding: 0 5px; border-right: 1px solid black;">S 15</td> <td style="padding: 0 5px;">S 14</td> </tr> <tr> <td style="padding: 0 5px; border-right: 1px solid black;">S 22</td> <td style="padding: 0 5px;">S 23</td> </tr> </table> <p style="margin: 5px 0;">2004</p> </div> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p> <p>Land, rolling. Soil, sandy. Undergrowth, sage and native grasses.</p> <hr style="width: 80%; margin: 10px auto;"/> <p>From the cor. of secs. 13, 14, 23 and 24.</p> <p>N. 89°59' W., bet. secs. 14 and 23.</p> <p>Over rolling terrain covered with sage and scattered grasses.</p>	T 40 N	R 3 W	S 15	S 14	S 22	S 23
T 40 N	R 3 W						
S 15	S 14						
S 22	S 23						
40.04	<p>True point for the 1/4 sec. cor. of secs. 14 and 23; falls in Kanab Creek, 500 ft. wide, 30 ft. deep, course S. 50° W., where it is impracticable to establish a permanent monument.</p> <p>From this true point, the point selected for a witness cor. to the 1/4 sec. cor. of secs. 14 and 23, bears N. 45°00' W., 4.00 chs. dist.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 23 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center; margin: 10px 0;"> <table style="margin: auto; border-collapse: collapse;"> <tr> <td style="padding: 0 5px;">WC</td> </tr> <tr> <td style="padding: 0 5px;">T 40 N R 3 W</td> </tr> <tr> <td style="padding: 0 5px;">S 14</td> </tr> <tr> <td style="padding: 0 5px;">1/4 <span style="border-top: 1px solid black; display: inline-block; width: 50px;"></span></td> </tr> <tr> <td style="padding: 0 5px;">S 23</td> </tr> </table> <p style="margin: 5px 0;">2004</p> </div> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p>	WC	T 40 N R 3 W	S 14	1/4 <span style="border-top: 1px solid black; display: inline-block; width: 50px;"></span>	S 23	
WC							
T 40 N R 3 W							
S 14							
1/4 <span style="border-top: 1px solid black; display: inline-block; width: 50px;"></span>							
S 23							
80.08	<p>The cor. of secs. 14, 15, 22 and 23.</p>						

**Survey of the Subdivisional Lines,  
T. 40 N., R. 3 W., Gila and Salt River Meridian, Arizona**

CHAINS	
	<p>Land, rolling. Soil, sandy. Undergrowth, sage and native grasses.</p> <hr/> <p>N. 0°03' E., bet. secs. 14 and 15.</p> <p>Over rolling terrain covered with sage and scattered grasses.</p>
40.00	<p>Point for the 1/4 sec. cor. of secs. 14 and 15.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 19 ins. in the ground, to bedrock, in a mound of stone, 2 1/2 ft. base, to top, with brass cap mkd.</p> <p style="text-align: center;">T 40 N R 3 W 1/4 S 15   S 14</p> <p style="text-align: center;">2004</p> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p>
80.00	<p>Point for the cor. of secs. 10, 11, 14 and 15.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 22 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T 40 N R 3 W S 10   S 11 S 15   S 14</p> <p style="text-align: center;">2004</p> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p> <p>Land, rolling. Soil, sandy. Undergrowth, sage and native grasses.</p> <hr/> <p>From the cor. of secs. 11, 12, 13 and 14.</p> <p>N. 89°59' W., bet. secs. 11 and 14.</p> <p>Over rolling terrain covered with sage and scattered grasses.</p>
40.04	<p>Point for the 1/4 sec. cor. of secs. 11 and 14.</p>

**Survey of the Subdivisional Lines,  
T. 40 N., R. 3 W., Gila and Salt River Meridian, Arizona**

CHAINS	
	<p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p align="center">T 40 N R 3 W S 11 1/4 ——— S 14</p> <p align="center">2004</p> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p>
56.65	Graded road, 14 ft. wide, bears S. 30° E. and N. 30° W.
80.08	<p>The cor. of secs. 10, 11, 14 and 15.</p> <p>Land, rolling. Soil, sandy. Undergrowth, sage and native grasses.</p> <hr/> <p>N. 0°03' E., bet. secs. 10 and 11.</p> <p>Over rolling terrain covered with sage and scattered grasses.</p>
4.20	Barbed wire fence, bears N. 40° E. and S. 40° W.
40.00	<p>Point for the 1/4 sec. cor. of secs. 10 and 11.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p align="center">T 40 N R 3 W 1/4 S 10   S 11</p> <p align="center">2004</p> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p>
51.40	Graded road, 14 ft. wide, bears S. 40° E. and N. 40° W.
76.20	Trail road, bears S. 75° E. and N. 75° W.
80.00	<p>Point for the cor. of secs. 2, 3, 10 and 11.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 23 ins. in the ground, with brass cap mkd.</p>

**Survey of the Subdivisional Lines,  
T. 40 N., R. 3 W., Gila and Salt River Meridian, Arizona**

CHAINS	
	<p align="center">T 40 N R 3 W S 3   S 2 <hr/>S 10   S 11</p> <p align="center">2004</p> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p> <p>Land, rolling. Soil, sandy. Undergrowth, sage and native grasses.</p> <hr/> <p>From the cor. of secs. 1, 2, 11 and 12.</p> <p>N. 89°58' W., bet. secs. 2 and 11.</p> <p>Over rolling terrain covered with sage and scattered grasses.</p>
40.04	<p>Point for the 1/4 sec. cor. of secs. 2 and 11.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p>
80.08	<p align="center">T 40 N R 3 W S 2 1/4 <hr/>S 11</p> <p align="center">2004</p> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p> <p>The cor. of secs. 2, 3, 10 and 11.</p> <p>Land, rolling. Soil, sandy. Undergrowth, sage and native grasses.</p> <hr/> <p>N. 0°03' E., bet. secs. 2 and 3.</p> <p>Over rolling terrain covered with sage and scattered grasses.</p>
40.00	<p>Point for the 1/4 sec. cor. of secs. 2 and 3.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 23 ins. in the ground, with brass cap mkd.</p>

Survey of the Subdivisional Lines,  
T. 40 N., R. 3 W., Gila and Salt River Meridian, Arizona

<p>CHAINS</p>	<p style="text-align: center;">T 40 N R 3 W 1/4 S 3   S 2</p> <p style="text-align: center;">2004</p> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p> <p>63.90 Trail road, bears N. 35° E. and S. 35° W.</p> <p>74.15 Point for the closing cor. of secs. 2 and 3, on the N. bdy. of the Tp.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 23 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T 41 N R 3 W S 35 ----- S 3   S 2 T 40 N R 3 W CC</p> <p style="text-align: center;">2004</p> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p> <p>From this point the stan. cor. of secs. 34 and 35, T. 41 N., R. 3 W., bears West, 5.24 chs. dist., hereinbefore described.</p> <p>Land, rolling. Soil, sandy. Undergrowth, sage and native grasses.</p> <hr/> <p>The point for the 1/4 sec. cor. of sec. 2 only, T. 40 N., R. 3 W., is at midpoint on the N. bdy. of sec. 2.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T 41 N R 3 W ----- 1/4 S 2 T 40 N R 3 W</p> <p style="text-align: center;">2004</p> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p>
---------------	---



**Survey of the Subdivisional Lines,  
T. 40 N., R. 3 W., Gila and Salt River Meridian, Arizona**

CHAINS									
	<p>From this point the stan. 1/4 sec. cor. of sec. 35, T. 41 N., R. 3 W., bears West, 5.235 chs. dist., hereinbefore described.</p> <p>Land, rolling. Soil, sandy. Undergrowth, sage and native grasses.</p> <hr/> <p>From the cor. of secs. 3, 4, 33 and 34, on the S. bdy. of the Tp., monumented with an iron post, 3 ins. diam., firmly set, projecting 17 ins. above ground, with an accessory mound of stone, 3 ft. base, 1 ft. high to the W., with brass cap mkd. T40N S33 S34 R3W S4 S3 T39N 1914.</p> <p>Add the marks 2004 to the brass cap.</p> <p>N. 0°02' E., bet. secs. 33 and 34.</p> <p>Over rolling terrain covered with sage and scattered grasses.</p>								
40.00	Point for the 1/4 sec. cor. of secs. 33 and 34, not monumented.								
80.00	<p>True point for the cor. of secs. 27, 28, 33 and 34, falls in the center of a wash, 30 ft. wide, 1 ft. deep, drains N. 10° E., where it is impracticable to establish a permanent monument.</p> <p>From this true point, the point selected for a witness cor. to the cor. of secs. 27, 28, 33 and 34, bears N. 45°00' W., 1.00 ch. dist.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 14 ins. in the ground, to bedrock, in a supporting mound of stone, 4 ft. base, to top, with brass cap mkd.</p> <div style="text-align: center; margin: 10px 0;"> <table style="margin: 0 auto;"> <tr><td colspan="2">WC</td></tr> <tr><td>T 40 N</td><td>R 3 W</td></tr> <tr><td style="border-right: 1px solid black;">S 28</td><td>S 27</td></tr> <tr><td style="border-right: 1px solid black;">S 33</td><td>S 34</td></tr> </table> <p style="margin-top: 5px;">2004 </p> </div> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p> <p>Land, rolling. Soil, sandy. Undergrowth, sage and native grasses.</p> <hr/> <p>From the cor. of secs. 26, 27, 34 and 35.</p> <p>N. 89°58' W., bet. secs. 27 and 34.</p>	WC		T 40 N	R 3 W	S 28	S 27	S 33	S 34
WC									
T 40 N	R 3 W								
S 28	S 27								
S 33	S 34								

**Survey of the Subdivisional Lines,  
T. 40 N., R. 3 W., Gila and Salt River Meridian, Arizona**

CHAINS	
	Over mountainous and rolling terrain covered with sage and scattered grasses.
40.04	Point for the 1/4 sec. cor. of secs. 27 and 34.  Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 11 ins. in the ground, to bedrock, in a supporting mound of stone, 5 ft. base, to top, with brass cap mkd.  <div style="text-align: center;">           T 40 N R 3 W                  S 27            1/4 ———                  S 34             2004         </div>
	Deposit a magnet, in a white plastic case, at the base of the stainless steel post.
	Cor. is located 15 lks. S. of a barbed wire fence, bears E. and W.
80.08	The cor. of secs. 27, 28, 33 and 34.  Land, mountainous and rolling. Soil, sandy and broken sandstone. Undergrowth, sage and native grasses.
	-----
	N. 0°02' E., bet. secs. 27 and 28.
	Over rolling terrain covered with sage and scattered grasses.
0.20	Barbed wire fence, bears E. and W.
40.00	Point for the 1/4 sec. cor. of secs. 27 and 28.  Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 25 ins. in the ground, with brass cap mkd.  <div style="text-align: center;">           T 40 N R 3 W                  1/4            S 28   S 27             2004         </div>
	Deposit a magnet, in a white plastic case, at the base of the stainless steel post.
49.65	Trail road, bears N. 30° E. and S. 35° W.
80.00	Point for the cor. of secs. 21, 22, 27 and 28.

**Survey of the Subdivisional Lines,  
T. 40 N., R. 3 W., Gila and Salt River Meridian, Arizona**

CHAINS									
	<p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 25 ins. in the ground, with brass cap mkd.</p> <p align="center"> <table border="1"> <tr> <td>T 40 N</td> <td>R 3 W</td> </tr> <tr> <td>S 21</td> <td>S 22</td> </tr> <tr> <td>S 28</td> <td>S 27</td> </tr> </table> </p> <p align="center">2004</p> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p> <p>Land, rolling. Soil, sandy. Undergrowth, sage and native grasses.</p> <hr/>	T 40 N	R 3 W	S 21	S 22	S 28	S 27		
T 40 N	R 3 W								
S 21	S 22								
S 28	S 27								
	<p>From the cor. of secs. 22, 23, 26 and 27.</p> <p>N. 89°58' W., bet. secs. 22 and 27.</p> <p>Over rolling terrain covered with sage and scattered grasses.</p>								
<p>40.04</p>	<p>Point for the 1/4 sec. cor. of secs. 22 and 27.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 12 ins. in the ground, to bedrock, in a supporting mound of stone, 5 ft. base, to top, with brass cap mkd.</p> <p align="center"> <table border="1"> <tr> <td>T 40 N</td> <td>R 3 W</td> </tr> <tr> <td>S 22</td> <td></td> </tr> <tr> <td>1/4</td> <td>—</td> </tr> <tr> <td>S 27</td> <td></td> </tr> </table> </p> <p align="center">2004</p> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p>	T 40 N	R 3 W	S 22		1/4	—	S 27	
T 40 N	R 3 W								
S 22									
1/4	—								
S 27									
<p>60.30</p>	<p>Trail road, bears N. 30° E. and S. 25° W.</p>								
<p>80.08</p>	<p>The cor. of secs. 21, 22, 27 and 28.</p> <p>Land, rolling. Soil, sandy and broken sandstone. Undergrowth, sage and native grasses.</p> <hr/> <p>N. 0°02' E., bet. secs. 21 and 22.</p> <p>Over rolling terrain covered with sage and scattered grasses.</p>								

**Survey of the Subdivisional Lines,  
T. 40 N., R. 3 W., Gila and Salt River Meridian, Arizona**

CHAINS	
40.00	<p>Point for the 1/4 sec. cor. of secs. 21 and 22.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T 40 N R 3 W 1/4 S 21   S 22</p> <p style="text-align: center;">2004</p> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p>
80.00	<p>Point for the cor. of secs. 15, 16, 21 and 22.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T 40 N R 3 W S 16   S 15 S 21   S 22</p> <p style="text-align: center;">2004</p> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p> <p>Land, rolling. Soil, sandy. Undergrowth, sage and native grasses.</p> <hr/> <p>From the cor. of secs. 14, 15, 22 and 23.</p> <p>N. 89°58' W., bet. secs. 15 and 22.</p> <p>Over rolling terrain covered with sage and scattered grasses.</p>
40.04	<p>Point for the 1/4 sec. cor. of secs. 15 and 22.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T 40 N R 3 W S 15 1/4 ——— S 22</p> <p style="text-align: center;">2004</p>

**Survey of the Subdivisional Lines,  
T. 40 N., R. 3 W., Gila and Salt River Meridian, Arizona**

CHAINS	
	Deposit a magnet, in a white plastic case, at the base of the stainless steel post.
80.08	The cor. of secs. 15, 16, 21 and 22.  Land, rolling. Soil, sandy. Undergrowth, sage and native grasses.
	<hr/>
	N. 0°02' E., bet. secs. 15 and 16.  Over rolling terrain covered with sage and scattered grasses.
0.55	Barbed wire fence, bears N. 50° E. and S. 50° W.
40.00	Point for the 1/4 sec. cor. of secs. 15 and 16.  Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 25 ins. in the ground, with brass cap mkd.
	T 40 N R 3 W 1/4 S 16   S 15  2004
	Deposit a magnet, in a white plastic case, at the base of the stainless steel post.
80.00	Point for the cor. of secs. 9, 10, 15 and 16.  Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.
	T 40 N R 3 W S 9   S 10 S 16   S 15  2004
	Deposit a magnet, in a white plastic case, at the base of the stainless steel post.  Land, rolling. Soil, sandy. Undergrowth, sage and native grasses.
	<hr/>
	From the cor. of secs. 10, 11, 14 and 15.  N. 89°58' W., bet. secs. 10 and 15.

**Survey of the Subdivisional Lines,  
T. 40 N., R. 3 W., Gila and Salt River Meridian, Arizona**

CHAINS	<p>Over rolling terrain covered with sage and scattered grasses.</p>
40.04	<p>Point for the 1/4 sec. cor. of secs. 10 and 15.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p align="center">                     T 40 N R 3 W                                S 10                      1/4 ———                                S 15                 </p> <p align="center">2004</p> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p>
80.08	<p>The cor. of secs. 9, 10, 15 and 16.</p> <p>Land, rolling. Soil, sandy. Undergrowth, sage and native grasses.</p> <hr/> <p>N. 0°02' E., bet. secs. 9 and 10.</p> <p>Over rolling terrain covered with sage and scattered grasses.</p>
40.00	<p>Point for the 1/4 sec. cor. of secs. 9 and 10.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 25 ins. in the ground, with brass cap mkd.</p> <p align="center">                     T 40 N R 3 W                                1/4                      S 9   S 10                 </p> <p align="center">2004</p> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p>
80.00	<p>Point for the cor. of secs. 3, 4, 9 and 10.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with brass cap mkd.</p> <p align="center">                     T 40 N R 3 W                      S 4   S 3                      ———                      S 9   S 10                 </p> <p align="center">2004</p>

**Survey of the Subdivisional Lines,  
T. 40 N., R. 3 W., Gila and Salt River Meridian, Arizona**

CHAINS	
	<p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p> <p>Land, rolling. Soil, sandy. Undergrowth, sage and native grasses.</p> <hr/> <p>From the cor. of secs. 2, 3, 10 and 11.</p> <p>N. 89°58' W., bet. secs. 3 and 10.</p> <p>Over rolling terrain covered with sage and scattered grasses.</p>
40.04	<p>Point for the 1/4 sec. cor. of secs. 3 and 10.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 25 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T 40 N R 3 W S 3 1/4 ——— S 10  2004</p>
80.08	<p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p> <p>The cor. of secs. 3, 4, 9 and 10.</p> <p>Land, rolling. Soil, sandy. Undergrowth, sage and native grasses.</p> <hr/> <p>N. 0°02' E., bet. secs. 3 and 4.</p> <p>Over rolling terrain covered with sage and scattered grasses.</p>
15.60	Trail road, bears N. 60° E. and S. 60° W.
27.45	Arizona State Highway No. 389, asphalt surfaced, 35 ft. wide, bears N. 60° E. and S. 60° W.
40.00	<p>Point for the 1/4 sec. cor. of secs. 3 and 4.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p>

Survey of the Subdivisional Lines,  
T. 40 N., R. 3 W., Gila and Salt River Meridian, Arizona

CHAINS	
74.11	<p style="text-align: center;">T 40 N R 3 W 1/4 S 4   S 3  2004</p> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p> <p>Point for the closing cor. of secs. 3 and 4, on the N. bdy. of the Tp.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T 41 N R 3 W S 34 ----- S 4   S 3 T 40 N   R 3 W C   C  2004</p> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p> <p>From this point the stan. cor. of secs. 33 and 34, T. 41 N., R. 3 W., bears West, 5.25 chs. dist., hereinbefore described.</p> <p>Land, rolling. Soil, sandy and clay. Undergrowth, sage and native grasses.</p> <hr/> <p>The point for the 1/4 sec. cor. of sec. 3 only, T. 40 N., R. 3 W., is at midpoint on the N. bdy. of sec. 3.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 23 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T 41 N R 3 W ----- 1/4 S 3 T 40 N R 3 W  2004</p> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p> <p>From this point the stan. 1/4 sec. cor. of sec. 34, T. 41 N., R. 3 W., bears West, 5.28 chs. dist., hereinbefore described.</p>



**Survey of the Subdivisional Lines,  
T. 40 N., R. 3 W., Gila and Salt River Meridian, Arizona**

CHAINS	
	<p>Land, rolling. Soil, sandy. Undergrowth, sage and native grasses.</p> <hr/> <p>From the true point for the cor. of secs. 27, 28, 33 and 34. N. 89°59' W., bet. secs. 28 and 33. Over rolling terrain covered with sage and scattered grasses.</p> <p>40.07 Point for the 1/4 sec. cor. of secs. 28 and 33. Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 25 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T 40 N R 3 W S 28 1/4 ——— S 33</p> <p style="text-align: center;">2004</p> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p> <p>Cor. is located 25 lks. S. of a barbed wire fence, bears E. and W.</p>
80.14	<p>The cor. of secs. 28, 29, 32 and 33, monumented with an iron post, 2 1/2 ins. diam., firmly set, projecting 8 ins. above ground, with an accessory mound of stone, 3 ft. base, 1 ft. high to the W., with brass cap mkd. T40N R3W S29 S28 S32 S33 1954.</p> <p>Add the marks 2004 to the brass cap.</p> <p>Land, rolling. Soil, sandy. Undergrowth, sage and native grasses.</p> <hr/>
	<p>N. 0°02' E., bet. secs. 28 and 29. Over rolling terrain covered with sage and scattered grasses.</p>
0.30	<p>Barbed wire fence, bears E. and W.</p>
0.55	<p>Trail road, bears E. and W.</p>
40.00	<p>Point for the 1/4 sec. cor. of secs. 28 and 29. Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p>

**Survey of the Subdivisional Lines,  
T. 40 N., R. 3 W., Gila and Salt River Meridian, Arizona**

CHAINS	
	T 40 N R 3 W 1/4 S 29   S 28  2004
	Deposit a magnet, in a white plastic case, at the base of the stainless steel post.
80.00	Point for the cor. of secs. 20, 21, 28 and 29.
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.
	T 40 N R 3 W S 20   S 21 S 29   S 28  2004
	Deposit a magnet, in a white plastic case, at the base of the stainless steel post.
	Land, rolling. Soil, sandy. Undergrowth, sage and native grasses.
	From the cor. of secs. 21, 22, 27 and 28.
	N. 89°59' W., bet. secs. 21 and 28.
	Over rolling terrain covered with sage and scattered grasses.
35.60	Barbed wire fence, bears S. 25° E. and N. 25° W.
40.07	Point for the 1/4 sec. cor. of secs. 21 and 28.
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with brass cap mkd.
	T 40 N R 3 W S 21 1/4 ——— S 28  2004
	Deposit a magnet, in a white plastic case, at the base of the stainless steel post.
80.14	The cor. of secs. 20, 21, 28 and 29.

**Survey of the Subdivisional Lines,  
T. 40 N., R. 3 W., Gila and Salt River Meridian, Arizona**

CHAINS	
	<p>Land, rolling. Soil, sandy. Undergrowth, sage and native grasses.</p> <hr/> <p>N. 0°02' E., bet. secs. 20 and 21.</p> <p>Over rolling terrain covered with sage and scattered grasses.</p>
40.00	<p>Point for the 1/4 sec. cor. of secs. 20 and 21.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T 40 N R 3 W 1/4 S 20   S 21</p> <p style="text-align: center;">2004</p> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p>
80.00	<p>Point for the cor. of secs. 16, 17, 20 and 21.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 25 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T 40 N R 3 W S 17   S 16 S 20   S 21</p> <p style="text-align: center;">2004</p> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p>
	<p>Land, rolling. Soil, sandy. Undergrowth, sage and native grasses.</p> <hr/> <p>From the cor. of secs. 15, 16, 21 and 22.</p> <p>N. 89°59' W., bet. secs. 16 and 21.</p> <p>Over rolling terrain covered with sage and scattered grasses.</p>
0.70	<p>Barbed wire fence, bears N. 50° E. and S. 50° W.</p>
40.07	<p>Point for the 1/4 sec. cor. of secs. 16 and 21.</p>

**Survey of the Subdivisional Lines,  
T. 40 N., R. 3 W., Gila and Salt River Meridian, Arizona**

CHAINS	
	<p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T 40 N R 3 W S 16 1/4 ——— S 21</p> <p style="text-align: center;">2004</p> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p>
80.14	<p>The cor. of secs. 16, 17, 20 and 21.</p> <p>Land, rolling. Soil, sandy. Undergrowth, sage and native grasses.</p> <hr/> <p>N. 0°02' E., bet. secs. 16 and 17.</p> <p>Over rolling terrain covered with sage and scattered grasses.</p>
40.00	<p>Point for the 1/4 sec. cor. of secs. 16 and 17.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T 40 N R 3 W 1/4 S 17   S 16</p> <p style="text-align: center;">2004</p> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p>
80.00	<p>Cor. is located 2.35 chs. E. of a barbed wire fence, bears S. 30° E. and N. 30° W.</p> <p>Point for the cor. of secs. 8, 9, 16 and 17.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T 40 N R 3 W S 8   S 9 S 17   S 16</p> <p style="text-align: center;">2004</p>

**Survey of the Subdivisional Lines,  
T. 40 N., R. 3 W., Gila and Salt River Meridian, Arizona**

CHAINS	
	<p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p> <p>Land, rolling. Soil, sandy. Undergrowth, sage and native grasses.</p> <hr/> <p>From the cor. of secs. 9, 10, 15 and 16.</p> <p>N. 89°59' W., bet. secs. 9 and 16.</p> <p>Over rolling terrain covered with sage and scattered grasses.</p>
40.07	<p>Point for the 1/4 sec. cor. of secs. 9 and 16.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p align="center">T 40 N R 3 W S 9 1/4 ——— S 16  2004</p>
80.14	<p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p> <p>The cor. of secs. 8, 9, 16 and 17.</p> <p>Land, rolling. Soil, sandy. Undergrowth, sage and native grasses.</p> <hr/> <p>N. 0°02' E., bet. secs. 8 and 9.</p> <p>Over rolling terrain covered with sage and scattered grasses.</p>
40.00	<p>Point for the 1/4 sec. cor. of secs. 8 and 9.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p align="center">T 40 N R 3 W 1/4 S 8   S 9  2004</p> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p>

**Survey of the Subdivisional Lines,  
T. 40 N., R. 3 W., Gila and Salt River Meridian, Arizona**

CHAINS									
51.90	Trail road, bears N. 55° E. and S. 55° W.								
61.50	Arizona State Highway No. 389, asphalt surfaced, 35 ft. wide, bears N. 60° E. and S. 60° W.								
80.00	Point for the cor. of secs. 4, 5, 8 and 9.  Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 25 ins. in the ground, with brass cap mkd.  <div style="text-align: center;"> <table border="1"> <tr><td>T 40 N</td><td>R 3 W</td></tr> <tr><td>S 5</td><td>S 4</td></tr> <tr><td>S 8</td><td>S 9</td></tr> </table> <p>2004</p> </div> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p> <p>Land, rolling. Soil, sandy. Undergrowth, sage and native grasses.</p> <hr/> <p>From the cor. of secs. 3, 4, 9 and 10. N. 89°59' W., bet. secs. 4 and 9. Over rolling terrain covered with sage and scattered grasses.</p>	T 40 N	R 3 W	S 5	S 4	S 8	S 9		
T 40 N	R 3 W								
S 5	S 4								
S 8	S 9								
28.60	Trail road, bears N. 60° E. and S. 60° W.								
40.07	Point for the 1/4 sec. cor. of secs. 4 and 9.  Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 25 ins. in the ground, with brass cap mkd.  <div style="text-align: center;"> <table border="1"> <tr><td>T 40 N</td><td>R 3 W</td></tr> <tr><td>S 4</td><td></td></tr> <tr><td>1/4</td><td>—</td></tr> <tr><td>S 9</td><td></td></tr> </table> <p>2004</p> </div> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p> <p>Cor. is located 2.65 chs. S. of a barbed wire fence, bears N. 60° E. and S. 60° W.</p>	T 40 N	R 3 W	S 4		1/4	—	S 9	
T 40 N	R 3 W								
S 4									
1/4	—								
S 9									
47.90	Arizona State Highway No. 389, asphalt surfaced, 35 ft. wide, bears N. 60° E. and S. 60° W.								

Survey of the Subdivisional Lines,  
T. 40 N., R. 3 W., Gila and Salt River Meridian, Arizona

CHAINS	
80.14	<p>The cor. of secs. 4, 5, 8 and 9.</p> <p>Land, rolling. Soil, sandy. Undergrowth, sage and native grasses.</p> <hr/>
40.00	<p>N. 0°02' E., bet. secs. 4 and 5.</p> <p>Over rolling terrain covered with sage and scattered grasses.</p> <p>Point for the 1/4 sec. cor. of secs. 4 and 5.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 25 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T 40 N R 3 W 1/4 S 5   S 4</p> <p style="text-align: center;">2004</p>
74.10	<p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p> <p>Point for the closing cor. of secs. 4 and 5, on the N. bdy. of the Tp.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T 41 N R 3 W S 33 S 5   S 4 T 40 N   R 3 W C   C</p> <p style="text-align: center;">2004</p> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p> <p>From this point the stan. cor. of secs. 32 and 33, T. 41 N., R. 3 W., bears N. 89°59' W., 5.16 chs. dist., hereinbefore described.</p> <p>Land, rolling. Soil, sandy and clay. Undergrowth, sage and native grasses.</p> <hr/>

**Survey of the Subdivisional Lines,  
T. 40 N., R. 3 W., Gila and Salt River Meridian, Arizona**

CHAINS	
	<p>The point for the 1/4 sec. cor. of sec. 4 only, T. 40 N., R. 3 W., is at midpoint on the N. bdy. of sec. 4.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 23 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T 41 N R 3 W ----- 1/4 S 4 T 40 N R 3 W</p> <p style="text-align: center;">2004</p> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p> <p>From this point the stan. 1/4 sec. cor. of sec. 33, T. 41 N., R. 3 W., bears West, 5.21 chs. dist., hereinbefore described.</p> <p>Land, rolling. Soil, sandy. Undergrowth, sage and native grasses.</p> <hr/> <p>From the cor. of secs. 29, 30, 31 and 32, monumented with an iron post, 2 1/2 ins. diam., firmly set, projecting 10 ins. above ground, with an accessory mound of stone, 3 ft. base, 1 ft. high to the W., with brass cap mkd. T40N R3W S30 S29 S31 S32 1954.</p> <p>Add the marks 2004 to the brass cap.</p> <p>N. 89°54' W., bet. secs. 30 and 31.</p> <p>Over rolling terrain covered with sage and scattered grasses.</p>
40.00	<p>Point for the 1/4 sec. cor. of secs. 30 and 31.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T 40 N R 3 W S 30 1/4 ----- S 31</p> <p style="text-align: center;">2004</p> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p> <p>Cor. is located 20 lks. S. of a barbed wire fence, bears E. and W.</p>



**Survey of the Subdivisional Lines,  
T. 40 N., R. 3 W., Gila and Salt River Meridian, Arizona**

CHAINS	
78.29	<p>The cor. of secs. 25, 30, 31 and 36, on the W. bdy. of the Tp., monumented with an iron post, 3 ins. diam., firmly set, projecting 10 ins. above ground, with brass cap mkd. T40N R4W R3W S25 S30 S36 S31 2003 1914.</p> <p>Add the marks 2004 to the brass cap.</p> <p>Cor. is located at the intersection of fences, extending E., S. and W.</p> <p>Land, rolling. Soil, sandy. Undergrowth, sage and native grasses.</p> <hr/>
	<p>From the cor. of secs. 29, 30, 31 and 32.</p> <p>N. 0°01' E., bet. secs. 29 and 30.</p> <p>Over rolling and broken terrain covered with sage and scattered grasses.</p>
0.30	Barbed wire fence, bears E. and W.
10.40	Trail road, bears S. 70° E. and N. 70° W.
40.00	<p>Point for the 1/4 sec. cor. of secs. 29 and 30.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p align="center">T 40 N R 3 W 1/4 S 30   S 29  2004</p> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p>
80.00	<p>Point for the cor. of secs. 19, 20, 29 and 30.</p> <p>Set a stainless steel post, 28 ins. long, 2½ ins. diam., 9 ins. in the ground, to bedrock, in a supporting mound of stone, 4 ft. base, to top, with brass cap mkd.</p> <p align="center">T 40 N R 3 W S 19   S 20 ----- S 30   S 29  2004</p>

**Survey of the Subdivisional Lines,  
T. 40 N., R. 3 W., Gila and Salt River Meridian, Arizona**

CHAINS	
	<p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p> <p>Land, rolling and broken. Soil, sandy and broken sandstone. Undergrowth, sage and native grasses.</p> <hr/> <p>From the cor. of secs. 20, 21, 28 and 29.</p> <p>S. 89°59' W., bet. secs. 20 and 29.</p> <p>Over rolling terrain covered with sage and scattered grasses.</p>
40.04	<p>Point for the 1/4 sec. cor. of secs. 20 and 29.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 25 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T 40 N R 3 W S 20 1/4 ——— S 29</p> <p style="text-align: center;">2004</p>
80.08	<p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p> <p>The cor. of secs. 19, 20, 29 and 30.</p> <p>Land, rolling. Soil, sandy. Undergrowth, sage and native grasses.</p> <hr/> <p>N. 89°52' W., bet. secs. 19 and 30.</p> <p>Over rolling and broken terrain covered with sage and scattered grasses.</p>
21.05	<p>Trail road, bears N. 15° E. and S. 20° W., at intersection of a wash, 15 ft. wide, 5 ft. deep, drains S. 45° W.</p>
40.00	<p>Point for the 1/4 sec. cor. of secs. 19 and 30.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p>

**Survey of the Subdivisional Lines,  
T. 40 N., R. 3 W., Gila and Salt River Meridian, Arizona**

CHAINS	
	T 40 N R 3 W S 19 1/4 ——— S 30  2004
	Deposit a magnet, in a white plastic case, at the base of the stainless steel post.
66.30	Graded road, 22 ft. wide, bears N. 20° E. and S. 20° W., at intersection with a wash, 30 ft. wide, 10 ft. deep, drains S. 80° E.
78.30	The cor. of secs. 19, 24, 25 and 30, on the W. bdy. of the Tp., monumented with an iron post, 3 ins. diam., firmly set, projecting 14 ins. above ground, with brass cap mkd. T40N R4W R3W S24 S19 S25 S30 2003 1914.  Add the marks 2004 to the brass cap.  Land, rolling and broken. Soil, sandy. Undergrowth, sage and native grasses.
	—————
	From the cor. of secs. 19, 20, 29 and 30.  N. 0°01' E., bet. secs. 19 and 20.  Over rolling terrain covered with sage and scattered grasses.
40.00	Point for the 1/4 sec. cor. of secs. 19 and 20.  Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 25 ins. in the ground, with brass cap mkd.
	T 40 N R 3 W 1/4 S 19   S 20  2004
	Deposit a magnet, in a white plastic case, at the base of the stainless steel post.
80.00	Point for the cor. of secs. 17, 18, 19 and 20.  Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.

**Survey of the Subdivisional Lines,  
T. 40 N., R. 3 W., Gila and Salt River Meridian, Arizona**

CHAINS							
	<table style="margin: auto; border-collapse: collapse;"> <tr> <td style="padding: 0 10px;">T 40 N</td> <td style="padding: 0 10px;">R 3 W</td> </tr> <tr> <td style="border-right: 1px solid black; padding: 0 5px;">S 18</td> <td style="padding: 0 5px;">S 17</td> </tr> <tr> <td style="border-right: 1px solid black; padding: 0 5px;">S 19</td> <td style="padding: 0 5px;">S 20</td> </tr> </table>	T 40 N	R 3 W	S 18	S 17	S 19	S 20
T 40 N	R 3 W						
S 18	S 17						
S 19	S 20						
	2004						
	Deposit a magnet, in a white plastic case, at the base of the stainless steel post.						
	Land, rolling. Soil, sandy. Undergrowth, sage and native grasses.						
	<hr/>						
	From the cor. of secs. 16, 17, 20 and 21.						
	S. 89°59' W., bet. secs. 17 and 20.						
	Over rolling terrain covered with sage and scattered grasses.						
40.04	Point for the 1/4 sec. cor. of secs. 17 and 20.						
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.						
	<table style="margin: auto; border-collapse: collapse;"> <tr> <td style="padding: 0 10px;">T 40 N</td> <td style="padding: 0 10px;">R 3 W</td> </tr> <tr> <td style="padding: 0 10px;"></td> <td style="padding: 0 10px;">S 17</td> </tr> <tr> <td style="padding: 0 10px;">1/4</td> <td style="border-top: 1px solid black; padding: 0 10px;">S 20</td> </tr> </table>	T 40 N	R 3 W		S 17	1/4	S 20
T 40 N	R 3 W						
	S 17						
1/4	S 20						
	2004						
	Deposit a magnet, in a white plastic case, at the base of the stainless steel post.						
80.08	The cor. of secs. 17, 18, 19 and 20.						
	Land, rolling. Soil, sandy. Undergrowth, sage and native grasses.						
	<hr/>						
	N. 89°50' W., bet. secs. 18 and 19.						
	Over rolling terrain covered with sage and scattered grasses.						
11.60	Graded road, 33 ft. wide, bears N. 40° E. and S. 40° W.						
40.00	Point for the 1/4 sec. cor. of secs. 18 and 19.						
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 25 ins. in the ground, with brass cap mkd.						

**Survey of the Subdivisional Lines,  
T. 40 N., R. 3 W., Gila and Salt River Meridian, Arizona**

CHAINS	
	T 40 N R 3 W S 18 1/4 ——— S 19  2004
	Deposit a magnet, in a white plastic case, at the base of the stainless steel post.
78.27	The cor. of secs. 13, 18, 19 and 24, on the W. bdy. of the Tp., monumented with an iron post, 3 ins. diam., firmly set, projecting 9 ins. above ground, with brass cap mkd. T40N R4W R3W S13 S18 S24 S19 2003 1914.  Add the marks 2004 to the brass cap.  Land, rolling. Soil, sandy. Undergrowth, sage and native grasses.
	<hr/> From the cor. of secs. 17, 18, 19 and 20.  N. 0°01' E., bet. secs. 17 and 18.  Over rolling terrain covered with sage and scattered grasses.
11.15	Graded road, 26 ft. wide, bears N. 35° E. and S. 40° W.
40.00	Point for the 1/4 sec. cor. of secs. 17 and 18.  Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.
	T 40 N R 3 W 1/4 S 18   S 17  2004
	Deposit a magnet, in a white plastic case, at the base of the stainless steel post.
80.00	Point for the cor. of secs. 7, 8, 17 and 18.  Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with brass cap mkd.

**Survey of the Subdivisional Lines,  
T. 40 N., R. 3 W., Gila and Salt River Meridian, Arizona**

CHAINS									
	<table border="1"> <tr> <td>T 40 N</td> <td>R 3 W</td> </tr> <tr> <td>S 7</td> <td>S 8</td> </tr> <tr> <td>S 18</td> <td>S 17</td> </tr> </table> <p>2004</p> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p> <p>From this cor. point, U.S.G.S. triangulation station EASY, bears S. 61°21' E., 11.99 chs. dist., monumented with a brass disk, 3 1/2 ins. diam., firmly set in a concrete base, 10 ins. diam., projecting 8 ins. above ground, mkd. EASY 1953 and a triangle.</p> <p>Land, rolling. Soil, sandy. Undergrowth, sage and native grasses.</p> <hr/> <p>From the cor. of secs. 8, 9, 16 and 17.</p> <p>S. 89°59' W., bet. secs. 8 and 17.</p> <p>Over rolling terrain covered with sage and scattered grasses.</p>	T 40 N	R 3 W	S 7	S 8	S 18	S 17		
T 40 N	R 3 W								
S 7	S 8								
S 18	S 17								
40.04	<p>Point for the 1/4 sec. cor. of secs. 8 and 17.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with brass cap mkd.</p> <p align="center"> <table border="1"> <tr> <td>T 40 N</td> <td>R 3 W</td> </tr> <tr> <td>S 8</td> <td></td> </tr> <tr> <td>1/4</td> <td>—</td> </tr> <tr> <td>S 17</td> <td></td> </tr> </table> <p>2004</p> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p> </p>	T 40 N	R 3 W	S 8		1/4	—	S 17	
T 40 N	R 3 W								
S 8									
1/4	—								
S 17									
73.10	Graded road, 30 ft. wide, bears S. 20° E. and N. 20° W.								
78.45	Barbed wire fence, bears S. 15° E. and N. 15° W.								
80.08	<p>The cor. of secs. 7, 8, 17 and 18.</p> <p>Land, rolling. Soil, sandy. Undergrowth, sage and native grasses.</p> <hr/> <p>N. 89°47' W., bet. secs. 7 and 18.</p>								

**Survey of the Subdivisional Lines,  
T. 40 N., R. 3 W., Gila and Salt River Meridian, Arizona**

CHAINS	
	Over rolling terrain covered with sage and scattered grasses.
40.00	Point for the 1/4 sec. cor. of secs. 7 and 18.  Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 23 ins. in the ground, with brass cap mkd.  <div style="text-align: center;">           T 40 N R 3 W                      S 7            1/4 ———                      S 18             2004         </div>
	Deposit a magnet, in a white plastic case, at the base of the stainless steel post.
64.90	Arizona State Highway No. 389, asphalt surfaced, 35 ft. wide, bears N. 70° E. and S. 70° W.
78.27	The cor. of secs. 7, 12, 13 and 18, on the W. bdy. of the Tp., monumented with an iron post, 3 ins. diam., firmly set, projecting 8 ins. above ground, with brass cap mkd. T40N R4W R3W S12 S7 S13 S18 2003 1914.  Add the marks 2004 to the brass cap.  Land, rolling. Soil, sandy. Undergrowth, sage and native grasses.
	From the cor. of secs. 7, 8, 17 and 18.  N. 0°01' E., bet. secs. 7 and 8.  Over rolling terrain covered with sage and scattered grasses.
11.30	Trail road, bears N. 70° E. and S. 70° W.
13.80	Graded road, 30 ft. wide, bears S. 30° E. and N. 20° W.
20.60	Arizona State Highway No. 389, asphalt surfaced, 35 ft. wide, bears N. 70° E. and S. 70° W.
40.00	Point for the 1/4 sec. cor. of secs. 7 and 8.  Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.

Survey of the Subdivisional Lines,  
T. 40 N., R. 3 W., Gila and Salt River Meridian, Arizona


CHAINS	
	<p style="text-align: center;">T 40 N R 3 W 1/4 S 7   S 8</p> <p style="text-align: center;">2004</p> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p>
80.00	<p>Point for the cor. of secs. 5, 6, 7 and 8.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 4 ins. in the ground, to bedrock, in a supporting mound of stone, 4 ft. base, to top, with brass cap mkd.</p> <p style="text-align: center;">T 40 N R 3 W S 6   S 5 S 7   S 8</p> <p style="text-align: center;">2004</p> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p> <p>Land, rolling. Soil, sandy and broken sandstone. Undergrowth, sage and native grasses.</p> <hr/> <p>From the cor. of secs. 4, 5, 8 and 9.</p> <p>S. 89°59' W., bet. secs. 5 and 8.</p> <p>Over rolling and broken terrain covered with sage and scattered grasses.</p>
40.04	<p>Point for the 1/4 sec. cor. of secs. 5 and 8.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T 40 N R 3 W S 5 1/4 ——— S 8</p> <p style="text-align: center;">2004</p>
78.10	<p>Barbed wire fence, bears S. 25° E. and N. 25° W.</p>
80.08	<p>The cor. of secs. 5, 6, 7 and 8.</p>



**Survey of the Subdivisional Lines,  
T. 40 N., R. 3 W., Gila and Salt River Meridian, Arizona**

CHAINS	
	<p>Land, rolling and broken. Soil, sandy. Undergrowth, sage and native grasses.</p> <hr/> <p>N. 89°46' W., bet. secs. 6 and 7.</p> <p>Over rolling and broken terrain covered with sage and scattered grasses.</p>
32.70	Trail road, bears S. 20° E. and N. 5° W.
40.00	<p>Point for the 1/4 sec. cor. of secs. 6 and 7.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center; margin: 10px 0;"> <p>T 40 N R 3 W</p> <p style="margin-left: 100px;">S 6</p> <p style="margin-left: 100px;">1/4 ———</p> <p style="margin-left: 100px;">S 7</p> <p style="margin-left: 100px;">2004</p> </div> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p> <p>Cor. is located 30 lks. E. of a drain, 3 ft. wide, 7 ft. deep, drains S. 25° E.</p>
78.24	<p>The cor. of secs. 1, 6, 7 and 12, on the W. bdy. of the Tp., monumented with an iron post, 3 ins. diam., firmly set, projecting 6 ins. above ground, with brass cap mkd. T40N R4W R3W S1 S6 S12 S7 2003 1914.</p> <p>Add the marks 2004 to the brass cap.</p> <p>Land, rolling and broken. Soil, sandy. Undergrowth, sage and native grasses.</p> <hr/> <p>From the cor. of secs. 5, 6, 7 and 8.</p> <p>N. 0°01' E., bet. secs. 5 and 6.</p> <p>Over rolling and broken land covered with sage, scattered juniper and grasses.</p>
5.70	Barbed wire fence, bears S. 25° E. and N. 25° W.
40.00	Point for the 1/4 sec. cor. of secs. 5 and 6.

Survey of the Subdivisional Lines,  
T. 40 N., R. 3 W., Gila and Salt River Meridian, Arizona

CHAINS	<p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T 40 N R 3 W 1/4 S 6   S 5</p> <p style="text-align: center;">2004</p> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p>
74.12	<p>True point for the closing cor. of secs. 5 and 6, on the N. bdy. of the Tp., falls on a steep and eroding slope, where it is impracticable to establish a permanent monument.</p> <p>From this true point, the point selected for a witness cor. to the closing cor. of secs. 5 and 6, on the N. bdy. of the Tp., bears S. 10°51' E., 27 lks. dist.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, in a collar of stone, with brass cap mkd.</p> <div style="text-align: center;">  <p style="margin-left: 100px;">WC</p> <p style="margin-left: 100px;">T 41 N R 3 W</p> <p style="margin-left: 100px;">S 32</p> <hr style="width: 100%; margin: 0;"/> <p style="margin-left: 100px;">S 6   S 5</p> <p style="margin-left: 100px;">T 40 N R 3 W</p> <p style="margin-left: 100px;">C C</p> </div> <p style="text-align: center;">2004</p> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p> <p>From this same true point the stan. cor. of secs. 31 and 32, T. 41 N., R. 3 W., bears S. 89°58' W., 5.12 chs. dist., hereinbefore described.</p> <p>Land, rolling. Soil, sandy and clay. Undergrowth, sage and native grasses.</p> <hr style="width: 80%; margin: 10px auto;"/> <p>The point for the 1/4 sec. cor. of sec. 5 only, T. 40 N., R. 3 W., is at midpoint on the N. bdy. of sec. 5.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with brass cap mkd.</p>

**Survey of the Subdivisional Lines,  
T. 40 N., R. 3 W., Gila and Salt River Meridian, Arizona**

CHAINS

T 41 N R 3 W

1/4 S 5

T 40 N R 3 W

2004

Deposit a magnet, in a white plastic case, at the base of the stainless steel post.

From this point the stan. 1/4 sec. cor. of sec. 32, T. 41 N., R. 3 W., bears West, 5.11 chs. dist., hereinbefore described.

Land, rolling and broken.  
Soil, sandy.  
Undergrowth, sage and native grasses.

---

The point for the 1/4 sec. cor. of sec. 6 only, T. 40 N., R. 3 W., is at midpoint on the N. bdy. of sec. 6.

Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.

T 41 N R 3 W

1/4 S 6

T 40 N R 3 W

2004

Deposit a magnet, in a white plastic case, at the base of the stainless steel post.

From this point the stan. 1/4 sec. cor. of sec. 31, T. 41 N., R. 3 W., bears West, 5.15 chs. dist., hereinbefore described.

Land, rolling and broken.  
Soil, sandy.  
Undergrowth, sage and native grasses.

---

GENERAL DESCRIPTION

The survey is located about 9 miles southwest of Fredonia, Arizona. The main access to the area is Arizona State Highway 389. Further access to the township is provided by numerous secondary and desert trail roads.

The terrain is mostly rolling throughout the township except in the SE and NW where it is rolling and broken. The elevation varies from 4500 to 5000 feet above sea level.

**T. 41 N., R. 4 W., Gila and Salt River Meridian, Arizona**

CHAINS

Kanab Creek runs through the northeasterly portion of the township and drains to the southeast.

The soil varies from mostly sandy to broken sandstone. No mineral deposits or mining activity was noted during the course of the survey.

The mean magnetic declination of  $12\ 1/2^\circ$  E. was derived from the computer program GEOMAGIX, utilizing the World Magnetic Model for Epoch WMM-2000 for the dates of survey.

---



CERTIFICATE OF SURVEY

I, Adrien J. Rodriguez, Cadastral Surveyor, HEREBY CERTIFY upon honor, that in pursuance of special instructions bearing date of the 21st day of July, 2004, I have dependently resurveyed a portion of the Tenth Standard Parallel North (North Boundary) and surveyed a portion of the subdivisional lines, T. 40 N., R. 3 W., of the Gila and Salt River Meridian, in the State of Arizona, which are represented in the foregoing field notes as having been executed by me and under my direction. Said survey has been made in strict conformity with said special instructions, the Manual of Instructions for the Survey of the Public Lands of the United States, and in specific manner described in the foregoing field notes.

August 9, 2005  
(Date)

Adrien J. Rodriguez  
(Cadastral Surveyor)

CERTIFICATE OF APPROVAL

BUREAU OF LAND MANAGEMENT  
Phoenix, Arizona

The foregoing field notes of the dependant resurvey of a portion of the Tenth Standard Parallel North (North Boundary) and the survey of a portion of the subdivisional lines, T. 40 N., R. 3 W., Gila and Salt River Meridian, in the State of Arizona, executed by Adrien J. Rodriguez, Cadastral Surveyor, having been critically examined and found correct, are hereby approved.

March 27, 2006  
(Date)

Stephen K. Hansen  
(Acting Chief Cadastral Surveyor of Arizona)

~~CERTIFICATE OF TRANSCRIPT~~

~~I CERTIFY That the foregoing transcript of the field notes of the above described surveys in T. 40 N., R. 3 W., Gila and Salt River Meridian, Arizona, is a true copy of the original field notes.~~

~~\_\_\_\_\_  
(Date)~~

~~\_\_\_\_\_  
(Acting Chief Cadastral Surveyor of Arizona)~~