

ORIGINAL

**UNITED STATES  
DEPARTMENT OF THE INTERIOR  
BUREAU OF LAND MANAGEMENT**

FIELD NOTES  
OF THE  
DEPENDENT RESURVEY  
OF  
THE SUBDIVISIONAL LINES  
TOWNSHIP 22 NORTH, RANGE 27 EAST  
OF THE GILA AND SALT RIVER MERIDIAN  
IN THE STATE OF ARIZONA

**EXECUTED BY**

**Leonard R. Sandoval, Cadastral Surveyor**

Under Special Instructions dated December 29, 2004, approved December 29, 2004, which provided for the surveys included under Group No. 947, and assignment instructions dated December 29, 2004.

**Survey commenced January 12, 2005**

**Survey completed February 24, 2005**

## INDEX DIAGRAM

TOWNSHIP 22 NORTH                  RANGE 27 EAST  
GILA AND SALT RIVER MERIDIAN, ARIIZONA

6	44    5	34    4	26    3	19    2	11    1
44	43	33	26	19	11
7	42    8	32    9	25    10	18    11	10    12
42	41	32	25	17	9
18	40    17	31    16	24    15	17    14	8    13
40	39	31	23	16	8
19	38    20	30    21	22    22	15    23	7    24
38	37	29	22	15	6
30	36    29	29    28	21    27	14    26	5    25
36	35	28	21	13	5
31	34    32	27    33	20    34	12    35	4    36

**T. 22 N., R. 27 E., Gila and Salt River Meridian, Arizona**

## CHAINS

The following field notes describe the dependent resurvey of the subdivisional lines, Township 22 North, Range 27 East, Gila and Salt River Meridian, Arizona.

The history of surveys pertaining to this survey is as follows:

The exterior boundaries and subdivisional lines of Township 22 North, Range 27 East were originally surveyed by Frank Follman in 1882-83. The north boundary of Township 21 North, Range 27 East, was resurveyed by Ty White in 1947, and by William P. Carpender and Darren R. Breckenridge in 1988-94. The east, west and north boundaries were resurveyed by Jones Curtiss, in 2002-03, executed concurrently under Group No. 886, Arizona.

The survey was executed in accordance with the specifications as set forth in the Manual of Instructions for the Survey of the Public Lands of the United States, 1973, and the Special Instructions dated December 29, 2004, for Group No. 947, Arizona.

The true meridian direction and length of all lines were determined by real time kinematic global positioning system observations using Trimble Navigation 5700 model receivers.

Preliminary to the resurvey, the lines of the prior surveys were retraced and search was made for all corners and other calls of record. Identified corners were remonumented in their original positions. Lost corners were reestablished and remonumented at proportionate positions based on the official record. The retracement data were thoroughly verified and only the true line field notes are given herein.

Geodetic control was derived from Global Positioning System (GPS) static observations post processed by National Geodetic Survey, Online Positioning User Service (OPUS), utilizing Continuously Operating Reference Stations (CORS), FLAGSTAFF, FERNO MESA AND PIE TOWN VLBA. The NAD 83 (CORS96) (EPOCH 2002) geographic position of the southeast corner of the township, is as follows:

Latitude: 35°15'24.51" N.                      Longitude: 109°25'16.04" W.

The mean magnetic declination is 11 1/4° E.

---

**Dependent Resurvey of the Subdivisional Lines,  
T. 22 N., R. 27 E., Gila and Salt River Meridian, Arizona**

CHAINS	<p style="text-align: center;">Restoring the survey executed by Frank Folman, in 1883</p> <hr/> <p>Beginning at the cor. of secs. 1, 2, 35 and 36, on the S. bdy., of the Tp., monumented with an iron post, 2 ins. diam., firmly set, projecting 10 ins. above ground, with brass cap mkd. T22N R27E S35 S36 S2 S1 T21N 1994 1947.</p> <p>from which the remains of the 1947 bearing trees</p> <p style="padding-left: 40px;">A juniper, 8 ins. diam., bears N. 15 1/2° E., 4.46 chs. dist., mkd. T22N R27E S36 BT on open blaze.</p> <p style="padding-left: 40px;">A root hole, bears S. 49 1/2° E., 3.54 chs. dist., with a dead and down juniper, 8 ins. diam., mkd. T21N R27E S1 BT on open blaze, lying nearby. (Record: 2.36 chs. dist.)</p> <p style="padding-left: 40px;">A juniper, 14 ins. diam., bears N. 4 1/2° W., 3.17 chs. dist., mkd. BT on partially healed blaze.</p> <p>Add the marks 2005 to the brass cap.</p> <p>Cor. is located 3 lks. N. of a barbed wire fence, 5 strands, bears East and West.</p> <p>N. 1°14' E., bet. sec. 35 and 36.</p> <p>Over rolling land.</p> <p>40.005 Point for the 1/4 sec. cor. of secs. 35 and 36, at proportionate dist.; there is no remaining evidence of the original cor.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T 22 N R 27 E 1/4 S 35   S 36 2005</p> <p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p> <p>42.54 W. right-of-way fence of U. S. Highway 191, barbed wire, 4 strands, parallels highway.</p> <p>48.65 U. S. Highway 191, asphalt pavement, 37 ft. wide, bears S. 15° E. and N. 15° W.</p> <p>54.83 E. right-of-way fence of U. S. Highway 191, barbed wire, 4 strands, parallels highway.</p>
--------	---

Dependent Resurvey of the Subdivisional Lines,  
T. 22 N., R. 27 E., Gila and Salt River Meridian, Arizona

CHAINS									
80.01	<p>Point for the cor. of secs. 25, 26, 35 and 36, at proportionate dist.; there is no remaining evidence of the original cor.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <table border="1" data-bbox="808 464 1036 562"> <tr> <td>T 22 N</td> <td>R 27 E</td> </tr> <tr> <td>S 26</td> <td>S 25</td> </tr> <tr> <td>S 35</td> <td>S 36</td> </tr> </table> <p>2005</p> <p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p>	T 22 N	R 27 E	S 26	S 25	S 35	S 36		
T 22 N	R 27 E								
S 26	S 25								
S 35	S 36								
40.175	<p>From the cor. of secs. 25, 30, 31 and 36, on the E. bdy. of the Tp., monumented with a stainless steel post, 2 1/2 ins. diam., firmly set, projecting 4 ins. above ground, with brass cap mkd. T22N R27E R28E S25 S30 S36 S31 2003.</p> <p>N. 89°20' W., bet. secs. 25 and 36.</p> <p>Over rolling land.</p> <p>Point for the 1/4 sec. cor. of secs. 25 and 36, at proportionate dist.; there is no remaining evidence of the original cor.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <table border="1" data-bbox="808 1220 1036 1339"> <tr> <td>T 22 N</td> <td>R 27 E</td> </tr> <tr> <td></td> <td>S 25</td> </tr> <tr> <td>1/4</td> <td>—</td> </tr> <tr> <td></td> <td>S 36</td> </tr> </table> <p>2005</p> <p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p>	T 22 N	R 27 E		S 25	1/4	—		S 36
T 22 N	R 27 E								
	S 25								
1/4	—								
	S 36								
80.35	<p>The cor. of secs. 25, 26, 35 and 36.</p> <hr/> <p>North, bet. secs. 25 and 26.</p> <p>Over rolling land.</p>								
39.995	<p>Point for the 1/4 sec. cor. of secs. 25 and 26, at proportionate dist.; there no remaining evidence of the original cor.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p>								

**Dependent Resurvey of the Subdivisional Lines,  
T. 22 N., R. 27 E., Gila and Salt River Meridian, Arizona**

CHAINS	
79.99	<p style="text-align: center;">T 22 N R 27 E 1/4 S 26   S 25</p> <p style="text-align: center;">2005</p> <p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p> <p>Point for the cor. of secs. 23, 24, 25 and 26, at proportionate dist.; there is no remaining evidence of the original cor.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T 22 N R 27 E S 23   S 24 S 26   S 25</p> <p style="text-align: center;">2005</p> <p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p> <p>Cor. is located 1.48 chs. E. of the E. right-of-way fence of U. S. Highway 191, barbed wire, 4 strands, bears N. 10° E. and S. 10° W.</p>
40.27	<hr/> <p>From the cor. of secs. 19, 24, 25 and 30, on the E. bdy. of the Tp., monumented with a stainless steel post, 2 1/2 ins. diam., firmly set, projecting 4 ins. above ground, with brass cap mkd. T22N R27E R28E S24 S19 S25 S30 2003.</p> <p>N. 89°20' W., bet. secs. 24 and 25.</p> <p>Over rolling land.</p> <p>Point for the 1/4 sec. cor. of secs. 24 and 25, at proportionate dist.; there is no remaining evidence of the original cor.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T 22 N R 27 E S 24 1/4 ——— S 25</p> <p style="text-align: center;">2005</p> <p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p>

**Dependent Resurvey of the Subdivisional Lines,  
T. 22 N., R. 27 E., Gila and Salt River Meridian, Arizona**

CHAINS	
42.30	Graded road, 30 ft. wide, bears S. 60° E. and N. 60° W.
80.54	The cor. of secs. 23, 24, 25 and 26
	<hr/> <p>N. 0°37' E., bet. secs. 23 and 24.</p> <p>Over rolling land.</p>
7.37	W. right-of-way fence of U. S. Highway 191, barbed wire, 4 strands, parallels highway.
14.85	U. S. Highway 191, asphalt pavement, 37 ft. wide, bears N. 10° E. and S. 10° W.
22.55	E. right-of-way fence of U. S. Highway 191, barbed wire, 4 strands, parallels highway.
39.995	Point for the 1/4 sec. cor. of secs. 23 and 24, at proportionate dist.; there is no remaining evidence of the original cor.
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.
	<p>T 22 N R 27 E</p> <p style="margin-left: 100px;">1/4</p> <p style="margin-left: 80px;">S 23   S 24</p> <p>2005</p>
	Deposit a magnet in a white plastic case at the base of the stainless steel post.
45.95	Apache County Road C272, a graded road, 25 ft. wide, bears N. 80° E. and S. 80° W.
46.85	Barbed wire fence, 5 strands, bears N. 80° E. and S. 80° W.
79.99	Point for the cor. of secs. 13, 14, 23 and 24, at proportionate dist.; there is no remaining evidence of the original cor.
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.
	<p>T 22 N R 27 E</p> <p style="margin-left: 100px;">S 14   S 13</p> <p style="margin-left: 80px;">S 23   S 24</p> <p>2005</p>
	Deposit a magnet in a white plastic case at the base of the stainless steel post.
	<hr/>

**Dependent Resurvey of the Subdivisional Lines,  
T. 22 N., R. 27 E., Gila and Salt River Meridian, Arizona**

CHAINS	
	<p>From the cor. of secs. 13, 18, 19 and 24, on the E. bdy. of the Tp., monumented with a stainless steel post, 2 1/2 ins. diam., firmly set, projecting 4 ins. above ground, with brass cap mkd. T22N R27E R28E S13 S18 S24 S19 2003.</p> <p>N. 89°20' W., bet. secs. 13 and 24.</p> <p>Over rolling land.</p>
39.935	<p>Point for the 1/4 sec. cor. of secs. 13 and 24, at proportionate dist.; there is no remaining evidence of the original cor.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T 22 N R 27 E S 13 1/4 ——— S 24</p> <p style="text-align: center;">2005</p> <p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p>
65.43	<p>E. right-of-way fence of U. S. Highway 191, barbed wire, 4 strands, parallels highway.</p>
67.00	<p>U. S. Highway 191, asphalt pavement, 37 ft. wide, bears N. 10° E. and S. 10° W.</p>
68.52	<p>W. right-of-way fence of U. S. Highway 191, barbed wire, 4 strands, parallels highway.</p>
79.87	<p>The cor. of secs. 13, 14, 23 and 24.</p> <hr/>
	<p>N. 0°20' E., bet. secs. 13 and 14.</p> <p>Over rolling land.</p>
39.995	<p>Point for the 1/4 sec. cor. of secs. 13 and 14, at proportionate dist.; there is no remaining evidence of the original cor.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T 22 N R 27 E 1/4 S 14   S 13</p> <p style="text-align: center;">2005</p>



**Dependent Resurvey of the Subdivisional Lines,  
T. 22 N., R. 27 E., Gila and Salt River Meridian, Arizona**

CHAINS									
	Deposit a magnet in a white plastic case at the base of the stainless steel post.								
79.99	<p>Point for the cor. of secs. 11, 12, 13 and 14, at proportionate dist.; there is no remaining evidence of the original cor.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center;"> <table style="margin: auto;"> <tr> <td>T 22 N</td> <td>R 27 E</td> </tr> <tr> <td>S 11</td> <td>S 12</td> </tr> <tr> <td>S 14</td> <td>S 13</td> </tr> </table> <p>2005</p> </div> <p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p> <hr/> <p>From the cor. of secs. 7, 12, 13 and 18, on the E. bdy. of the Tp., monumented with a stainless steel post, 2 1/2 ins. diam., firmly set, projecting 4 ins. above ground, with brass cap mkd. T22N R27E R28E S12 S7 S13 S18 2003.</p> <p>N. 89°21' W., bet. secs. 12 and 13.</p> <p>Over rolling land.</p>	T 22 N	R 27 E	S 11	S 12	S 14	S 13		
T 22 N	R 27 E								
S 11	S 12								
S 14	S 13								
39.805	<p>Point for the 1/4 sec. cor. of secs. 12 and 13, at proportionate dist.; there is no remaining evidence of the original cor.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center;"> <table style="margin: auto;"> <tr> <td>T 22 N</td> <td>R 27 E</td> </tr> <tr> <td>S 12</td> <td></td> </tr> <tr> <td>1/4</td> <td>—</td> </tr> <tr> <td>S 13</td> <td></td> </tr> </table> <p>2005</p> </div> <p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p>	T 22 N	R 27 E	S 12		1/4	—	S 13	
T 22 N	R 27 E								
S 12									
1/4	—								
S 13									
49.09	E. right-of-way fence of U. S. Highway 191, barbed wire, 4 strands, parallels highway.								
50.65	U. S. Highway 191, asphalt pavement, 37 ft. wide, bears N. 5° E. and S. 5° W.								
52.09	W. right-of-way fence of U. S. Highway 191, barbed wire, 4 strands, parallels highway.								

Dependent Resurvey of the Subdivisional Lines,  
T. 22 N., R. 27 E., Gila and Salt River Meridian, Arizona

CHAINS							
79.61	The cor. of secs. 11, 12, 13 and 14.						
	N. 0°08' E., bet. secs. 11 and 12.						
	Over rolling land.						
39.995	Point for the 1/4 sec. cor. of secs. 11 and 12, at proportionate dist.; there is no remaining evidence of the original cor.						
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.						
	<table style="margin-left: auto; margin-right: auto;"> <tr> <td>T 22 N</td> <td>R 27 E</td> </tr> <tr> <td colspan="2" style="text-align: center;">1/4</td> </tr> <tr> <td>S 11</td> <td>  S 12</td> </tr> </table>	T 22 N	R 27 E	1/4		S 11	S 12
T 22 N	R 27 E						
1/4							
S 11	S 12						
	2005						
	Deposit a magnet in a white plastic case at the base of the stainless steel post.						
78.35	W. right-of-way fence of U. S. Highway 191, barbed wire, 4 strands, bears S. 35° E. and N. 35° W.						
79.99	Point for the cor. of secs. 1, 2, 11 and 12, at proportionate dist.; there is no remaining evidence of the original cor.						
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 16 ins. below the surface of the ground, with brass cap mkd.						
	<table style="margin-left: auto; margin-right: auto;"> <tr> <td>T 22 N</td> <td>R 27 E</td> </tr> <tr> <td>S 2</td> <td>  S 1</td> </tr> <tr> <td>S 11</td> <td>  S 12</td> </tr> </table>	T 22 N	R 27 E	S 2	S 1	S 11	S 12
T 22 N	R 27 E						
S 2	S 1						
S 11	S 12						
	2005						
	from which						
	<p>A stainless steel post, 28 ins., 2 1/2 ins. diam., set 24 ins. in the ground for a reference monument, bears N. 45°00' E., 139.00 ft. dist., with brass cap mkd. T22N R27E S1 RM 139.0 FT. TO COR. 2005 and an arrow pointing to the cor. Deposit a magnet in a white plastic case at the base of the stainless post.</p>						
	<p>A stainless steel post, 28 ins., 2 1/2 ins. diam., set 24 ins. in the ground for a reference monument, bears S. 45°00' W., 66.0 ft. dist., with brass cap mkd. T22N R27E S11 RM 66.0 FT. TO COR. 2005 and an arrow pointing to the cor. Deposit a magnet in a white plastic case at the base of the stainless post.</p>						

**Dependent Resurvey of the Subdivisional Lines,  
T. 22 N., R. 27 E., Gila and Salt River Meridian, Arizona**

CHAINS	
	<p>Cor. is located 1 ch. S. and 67 lks. W. of the center of U. S. Highway 191, asphalt pavement, 34 ft. wide, bears S. 35° E. and N. 35° W.</p> <hr/> <p>From the cor. of secs. 1, 6, 7 and 12, on the E. bdy. of the Tp., monumented with a stainless steel post, 2 1/2 ins. diam., firmly set, projecting 4 ins. above ground, with brass cap mkd. T22N R27E R28E S1 S6 S12 S7 2003.</p> <p>N. 89°21' W., bet. secs. 1 and 12.</p> <p>Over rolling land.</p>
27.80	Apache County Road C322, a graded road, N. 50° E. and S. 50° W.
37.55	Trail road, bears N. 5° E. and S. 5° W.
39.81	<p>Point for the 1/4 sec. cor. of secs. 1 and 12, at proportionate dist.; there is no remaining evidence of the original cor.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center;"> <p>T 22 N R 27 E</p> <p>S 1</p> <p>1/4 ———</p> <p>S 12</p> <p>2005</p> </div> <p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p>
75.65	Trail road, bears N. 60° E. and S. 60° W.
77.08	E. right-of-way fence of U. S. Highway 191, barbed wire, 4 strands, bears S. 35° E. and N. 35° W.
79.62	The cor. of secs. 1, 2, 11 and 12.
	<hr/> <p>N. 0°02' E., bet. secs. 1 and 2.</p> <p>Over rolling land.</p>
3.62	E. right-of-way fence of U. S. Highway 191, barbed wire, 4 strands, bears S. 35° E. and N. 35° W.
21.25	Trail road, bears S. 75° E. and N. 75° W.
39.995	Point for the 1/4 sec. cor. of secs. 1 and 2, at proportionate dist.; there is no remaining evidence of the original cor.

**Dependent Resurvey of the Subdivisional Lines,  
T. 22 N., R. 27 E., Gila and Salt River Meridian, Arizona**

CHAINS	
	<p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p align="center">T 22 N R 27 E 1/4 S 2   S 1  2005</p> <p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p>
80.33	<p>The cor. of secs. 1, 2, 35 and 36, on the N. bdy. of the Tp., monumented with a stainless steel post, 2 1/2 ins. diam., firmly set, projecting 4 ins. above ground, with brass cap mkd. T23N R27E S35 S36 S2 S1 T22N 2003.</p> <hr/> <p>From the cor. of secs. 2, 3, 34 and 35, on the S. bdy. of the Tp., monumented with an iron post, 2 ins. diam., firmly set, projecting 7 ins. above ground, with brass cap mkd. T22N R27E S34 S35 S3 S2 T21N 1994 1947.</p> <p>from which the remains of the 1947 bearing trees</p> <p align="center">A forked juniper, 10 ins. diam., bears N. 1° E., 1.28 chs. dist., mkd. T22N R27E S35 BT on open blaze. (Record: 1.26 chs. dist.)</p> <p align="center">A juniper stump, 14 ins. diam. at base, 18 ins. high, bears N. 45 1/2° W., 1.20 chs. dist., mkd. R27E S34 BT on open blaze.</p> <p>Add the marks 2005 to the brass cap.</p> <p>Cor. is located 1.5 lks. N. of a barbed wire fence, 5 strands, bears East and West.</p> <p>N. 1°15' E., bet. secs. 34 and 35.</p> <p>Over rolling land.</p>
36.70	<p>Graded road, 25 ft. wide, bears N. 50° E. and S. 50° W.</p>
40.075	<p>Point for the 1/4 sec. cor. of secs. 34 and 35, at proportionate dist.; there is no remaining evidence of the original cor.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p>

**Dependent Resurvey of the Subdivisional Lines,  
T. 22 N., R. 27 E., Gila and Salt River Meridian, Arizona**

CHAINS	
	T 22 N R 27 E 1/4 S 34   S 35  2005  Deposit a magnet in a white plastic case at the base of the stainless steel post.
80.15	Point for the cor. of secs. 26, 27, 34 and 35, at proportionate dist.; there is no remaining evidence of the original cor.  Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.  T 22 N R 27 E S 27   S 26 S 34   S 35  2005  Deposit a magnet in a white plastic case at the base of the stainless steel post.
	<hr/> From the cor. of secs. 25, 26, 35 and 36.  N. 89°31' W., bet. secs. 26 and 35.  Over rolling land.
6.40	E. right-of-way fence of U. S. Highway 191, barbed wire, 4 strands, parallels highway.
7.95	U. S. Highway 191, asphalt pavement, 37 ft. wide, bears S. 15° E. and N. 15° W.
9.51	W. right-of-way fence of U. S. Highway 191, barbed wire, 4 strands, parallels highway.
10.80	Graded road, 20 ft. wide, bears S. 10° E. and N. 10° W.
30.25	Trail road, bears N. 50° E. and S. 50° W.
37.85	Trail road, bears E. 5° E. and N. 5° W.
39.93	Point for the 1/4 sec. cor. of secs. 26 and 35, at proportionate dist.; there is no remaining evidence of the original cor.  Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.

**Dependent Resurvey of the Subdivisional Lines,  
T. 22 N., R. 27 E., Gila and Salt River Meridian, Arizona**

CHAINS	
	T 22 N R 27 E S 26 1/4 ——— S 35  2005
	Deposit a magnet in a white plastic case at the base of the stainless steel post.
79.86	The cor. of secs. 26, 27, 34 and 35.
	<hr/> N. 0°14' E., bet. secs. 26 and 27.  Over rolling land.
6.45	Trail road, bears N. 75° E. and S. 75° W.
40.065	Point for the 1/4 sec. cor. of secs. 26 and 27, at proportionate dist.; there is no remaining evidence of the original cor.
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.
	T 22 N R 27 E 1/4 S 27   S 26  2005
	Deposit a magnet in a white plastic case at the base of the stainless steel post.
40.65	Trail road, bears N. 55° E. and S. 55° W.
67.40	Trail road, bears N. 70° E. and S. 70° W.
69.60	Trail road, bears N. 50° E. and S. 50° W.
80.13	Point for the cor. of secs. 22, 23, 26 and 27, at proportionate dist.; there is no remaining evidence of the original cor.
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.
	T 22 N R 27 E S 22   S 23 ——— S 27   S 26  2005

**Dependent Resurvey of the Subdivisional Lines,  
T. 22 N., R. 27 E., Gila and Salt River Meridian, Arizona**

CHAINS	
	<p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p> <hr/> <p>From the cor. of secs. 23, 24, 25 and 26.</p> <p>N. 89°25' W., bet. secs. 23 and 26.</p> <p>Over rolling land.</p>
1.48	E. right-of-way fence of U. S. Highway 191, barbed wire, 4 strands, parallels highway.
3.00	U. S. Highway 191, asphalt pavement, 33 ft. wide, bears N. 10° E. and S. 10° W.
4.57	W. right-of-way fence of U. S. Highway 191, barbed wire, 4 strands, parallels highway.
29.05	Trail road, bears S. 5° E. and N. 5° W.
39.76	<p>Point for the 1/4 cor. of secs. 23 and 26, at proportionate dist.; there is no remaining evidence of the original cor.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p align="center">T 22 N R 27 E S 23 1/4 ——— S 26</p> <p align="center">2005</p>
	<p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p>
49.30	Trail road, bears N. 70° E. and S. 70° W.
79.52	The cor. of secs. 22, 23, 26 and 27.
	<hr/> <p>N. 0°27' E., bet. secs. 22 and 23.</p> <p>Over rolling land.</p>
40.07	<p>Point for the 1/4 sec. cor. of secs. 22 and 23, at proportionate dist.; there is no remaining evidence of the original cor.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p>

**Dependent Resurvey of the Subdivisional Lines,  
T. 22 N., R. 27 E., Gila and Salt River Meridian, Arizona**

CHAINS	
	<p style="text-align: center;">T 22 N R 27 E 1/4 S 22   S 23</p> <p style="text-align: center;">2005</p> <p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p>
47.15	Apache County Road C272, a graded road, 25 ft. wide, bears N. 80° E. and S. 80° W.
51.55	Trail road, bears S. 70° E. and N. 70° W.
80.14	<p>Point for the cor. of secs. 14, 15, 22 and 23, at proportionate dist.; there is no remaining evidence of the original cor.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p>
	<p style="text-align: center;">T 22 N R 27 E S 15   S 14 S 22   S 23</p> <p style="text-align: center;">2005</p> <p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p> <hr/> <p>From the cor. of secs. 13, 14, 23 and 24.</p> <p>N. 89°19' W., bet. secs. 14 and 23.</p> <p>Over rolling land.</p>
37.65	Trail road, bears S. 15° E. and N. 15° W.
39.88	<p>Point for the 1/4 sec. cor. of secs. 14 and 23, at proportionate dist.; there is no remaining evidence of the original cor.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p>
	<p style="text-align: center;">T 22 N R 27 E S 14 1/4 ——— S 23</p> <p style="text-align: center;">2005</p> <p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p>



**Dependent Resurvey of the Subdivisional Lines,  
T. 22 N., R. 27 E., Gila and Salt River Meridian, Arizona**

CHAINS	
79.76	<p>The cor. of secs. 14, 15, 22 and 23.</p> <hr/> <p>N. 0°03' E., bet. secs. 14 and 15.</p> <p>Over rolling land.</p>
40.065	<p>Point for the 1/4 sec. cor. of secs. 14 and 15, at proportionate dist.; there is no remaining evidence of the original cor.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T 22 N R 27 E 1/4 S 15   S 14</p> <p style="text-align: center;">2005</p> <p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p>
67.00	<p>Graded road, 20 ft. wide, bears S. 80° E. and N. 80° W.</p>
80.13	<p>Point for the cor. of secs. 10, 11, 14 and 15, at proportionate dist.; there is no remaining evidence of the original cor.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T 22 N R 27 E S 10   S 11 S 15   S 14</p> <p style="text-align: center;">2005</p> <p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p> <hr/> <p>From the cor. of secs. 11, 12, 13 and 14.</p> <p>N. 89°13' W., bet. secs. 11 and 14.</p> <p>Over rolling land.</p>
33.05	<p>Trail road, bears S. 35° E. and N. 35° W.</p>
40.07	<p>Point for the 1/4 sec. cor. of secs. 11 and 14, at proportionate dist.; there is no remaining evidence of the original cor.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p>

**Dependent Resurvey of the Subdivisional Lines,  
T. 22 N., R. 27 E., Gila and Salt River Meridian, Arizona**

CHAINS	
	T 22 N R 27 E S 11 1/4 ——— S 14  2005
	Deposit a magnet in a white plastic case at the base of the stainless steel post.
46.60	Graded road, 20 ft. wide, bears S. 30° E. and N. 30° W.
77.86	Barbed wire fence, 5 strands, bears S. 35° E. and N. 35° W.
80.14	The cor. of secs. 10, 11, 14 and 15.
	<hr/> N. 0°23' E., bet. secs. 10 and 11.  Over rolling land.
38.30	Trail road, bears S. 70° E. and N. 70° W.
40.07	Point for the 1/4 sec. cor. of secs. 10 and 11, at proportionate dist.; there is no remaining evidence of the original cor.
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., flush with the surface of the ground, with brass cap mkd.
	T 22 N R 27 E 1/4 S 10   S 11  2005
	Deposit a magnet in a white plastic case at the base of the stainless steel post.
	Set a steel fence post nearby.
80.14	Point for the cor. of secs. 2, 3, 10 and 11, at proportionate dist.; there is no remaining evidence of the original cor.
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.
	T 22 N R 27 E S 3   S 2 ———— S 10   S 11  2005

**Dependent Resurvey of the Subdivisional Lines,  
T. 22 N., R. 27 E., Gila and Salt River Meridian, Arizona**

CHAINS	
	<p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p> <hr/> <p>From the cor. of secs. 1, 2, 11 and 12.</p> <p>N. 89°06' W., bet. secs. 2 and 11.</p> <p>Over rolling land.</p>
1.19	W. right-of-way fence of U. S. Highway 191, barbed wire, 4 strands, bears S. 35° E. and N. 35° W.
39.89	<p>Point for the 1/4 sec. cor. of secs. 2 and 11, at proportionate dist.; there is no remaining evidence of the original cor.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T 22 N R 27 E S 2 1/4 ——— S 11</p> <p style="text-align: center;">2005</p>
	<p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p>
49.00	Trail road, bears N. 15° E. and S. 15° W.
72.15	Trail road, bears S. 5° E and N. 5° W.
79.78	The cor. of secs. 2, 3, 10 and 11.
	<hr/> <p>N. 0°03' E., bet. secs. 2 and 3.</p> <p>Over rolling land.</p>
2.09	Barbed wire fence, 5 strands, bears S. 70° E and N. 70° W.
40.07	<p>Point for the 1/4 sec. cor. of secs. 2 and 3, at proportionate dist.; there is no remaining evidence of the original cor.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T 22 N R 27 E 1/4 S 3   S 2</p> <p style="text-align: center;">2005</p>

**Dependent Resurvey of the Subdivisional Lines,  
T. 22 N., R. 27 E., Gila and Salt River Meridian, Arizona**

CHAINS	
	Deposit a magnet in a white plastic case at the base of the stainless steel post.
63.30	Trail road, bears S. 70° E and N. 70° W.
80.30	The cor. of secs. 2, 3, 34 and 35, on the N. bdy. of the Tp., monumented with a stainless steel post, 2 1/2 ins. diam., firmly set, projecting 4 ins. above ground, with brass cap mkd. T23N R27E S34 S35 S3 S2 T22N 2003.
	<hr/> <p>From the cor. of secs. 3, 4, 33 and 34, on the S. bdy. of the Tp., monumented with an iron post, 2 ins. diam., firmly set, 25 ins. below the surface of the ground, with brass cap mkd. T22N R27E S33 S34 S4 S3 T21N 1994 1947.</p> <p>At the cor. point</p> <p>Reset the iron post, 36 ins. long, 30 ins. in the ground.</p> <p>Deposit a magnet in a white plastic case at the base of the iron post.</p> <p>Add the marks 2005 to the brass cap and set a steel fence post nearby.</p> <p>Cor. is located 4 lks. N. of a barbed wire fence, 5 strands, bears East and West.</p> <p>N. 1°04' E., bet. secs. 33 and 34.</p> <p>Over rolling land.</p>
40.15	<p>Point for the 1/4 sec. cor. of secs. 33 and 34, at proportionate dist.; there is no remaining evidence of the original cor.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p align="center">T 22 N R 27 E 1/4 S 33   S 34  2005</p>
80.30	<p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p> <p>Point for the cor. of secs. 27, 28, 33 and 34, at proportionate dist.; there is no remaining evidence of the original cor.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p>

**Dependent Resurvey of the Subdivisional Lines,  
T. 22 N., R. 27 E., Gila and Salt River Meridian, Arizona**

CHAINS	
	T 22 N R 27 E S 28   S 27 S 33   S 34  2005
	Deposit a magnet in a white plastic case at the base of the stainless steel post.
	<hr/> From the cor. of secs. 26, 27, 34 and 35. N. 89°30' W., bet. secs. 27 and 34. Over rolling land.
9.35	Trail road, bears N. 5° E. and S. 5° W.
40.045	Point for the 1/4 sec. cor. of secs. 27 and 34, at proportionate dist.; there is no remaining evidence of the original cor. Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.
	T 22 N R 27 E S 27 1/4 ——— S 34  2005
	Deposit a magnet in a white plastic case at the base of the stainless steel post.
80.09	The cor. of secs. 27, 28, 33 and 34. <hr/> N. 0°22' E., bet. secs. 27 and 28. Over rolling land.
25.60	Trail road, bears East and West.
40.145	Point for the 1/4 sec. cor. of secs. 27 and 28, at proportionate dist.; there is no remaining evidence of the original cor. Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.

**Dependent Resurvey of the Subdivisional Lines,  
T. 22 N., R. 27 E., Gila and Salt River Meridian, Arizona**

CHAINS	
	<p style="text-align: center;">T 22 N R 27 E 1/4 S 28   S 27</p> <p style="text-align: center;">2005</p>
	<p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p>
65.30	<p>Trail road, bears S. 60° E. and N. 60°W.</p>
80.29	<p>Point for the cor. of secs. 21, 22, 27 and 28, at proportionate dist.; there is no remaining evidence of the original cor.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p>
	<p style="text-align: center;">T 22 N R 27 E S 21   S 22 S 28   S 27</p> <p style="text-align: center;">2005</p>
	<p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p>
	<hr/> <p>From the cor. of secs. 22, 23, 26 and 27.</p> <p>N. 89°23' W., bet. secs. 22 and 27.</p> <p>Over rolling land.</p>
39.945	<p>Point for the 1/4 sec. cor. of secs. 22 and 27, at proportionate dist.; there is no remaining evidence of the original cor.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p>
	<p style="text-align: center;">T 22 N R 27 E S 22 1/4 ——— S 27</p> <p style="text-align: center;">2005</p>
	<p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p>
79.89	<p>The cor. of secs. 21, 22, 27 and 28.</p> <hr/> <p>N. 0°20' E., bet. secs. 21 and 22.</p>

**Dependent Resurvey of the Subdivisional Lines,  
T. 22 N., R. 27 E., Gila and Salt River Meridian, Arizona**

CHAINS	
	Over rolling land.
5.15	Trail road, bears N. 60° E. and S. 60° W.
40.145	Point for the 1/4 sec. cor. of secs. 21 and 22, at proportionate dist.; there is no remaining evidence of the original cor.
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.
	<p align="center">T 22 N R 27 E                    1/4                    S 21   S 22                      2005</p>
	Deposit a magnet in a white plastic case at the base of the stainless steel post.
52.20	Apache County Road C272, a graded road, 25 ft. wide, bears S. 80° E. and N. 80° W.
80.29	Point for the cor. of secs. 15, 16, 21 and 22, at proportionate dist.; there is no remaining evidence of the original cor.
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.
	<p align="center">T 22 N R 27 E            S 16   S 15            S 21   S 22                      2005</p>
	Deposit a magnet in a white plastic case at the base of the stainless steel post.
	<hr/> <p>From the cor. of secs. 14, 15, 22 and 23.  N. 89°17' W., bet. secs. 15 and 22.  Over rolling land.</p>
40.02	Point for the 1/4 sec. cor. of secs. 15 and 22, at proportionate dist.; there is no remaining evidence of the original cor.  Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.

**Dependent Resurvey of the Subdivisional Lines,  
T. 22 N., R. 27 E., Gila and Salt River Meridian, Arizona**

CHAINS	
	<p style="text-align: center;">T 22 N R 27 E S 15 1/4 _____ S 22  2005</p>
80.04	<p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p> <p>The cor. of secs. 15, 16, 21 and 22.</p> <hr/>
	<p>N. 0°02' E., bet. secs. 15 and 16.</p> <p>Over rolling land.</p>
38.10	<p>Trail road, bears N. 65° E. and S. 65° W.</p>
40.145	<p>Point for the 1/4 sec. cor. of secs. 15 and 16, at proportionate dist.; there is no remaining evidence of the original cor.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p>
	<p style="text-align: center;">T 22 N R 27 E 1/4 S 16   S 15  2005</p> <p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p>
68.75	<p>Trail road, bears N. 75° E. and S. 75° W.</p>
80.29	<p>Point for the cor. of secs. 9, 10, 15 and 16, at proportionate dist.; there is no remaining evidence of the original cor.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p>
	<p style="text-align: center;">T 22 N R 27 E S 9   S 10 ----- S 16   S 15  2005</p> <p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p>



**Dependent Resurvey of the Subdivisional Lines,  
T. 22 N., R. 27 E., Gila and Salt River Meridian, Arizona**

CHAINS	
	Cor. is located 85 lks. W. of a trail road, bears North and South.
	_____
	From the cor. of secs. 10, 11, 14 and 15.
	N. 89°10' W., bet. secs. 10 and 15.
	Over rolling land.
3.85	Barbed wire fence, 4 strands, bears S. 30° E. and N. 30° W.
38.05	Trail road, bears N. 85° E. and S. 85° W.
40.03	Point for the 1/4 sec. cor. of secs. 10 and 15, at proportionate dist.; there is no remaining evidence of the original cor.
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.
	T 22 N R 27 E S 10 1/4 ——— S 15  2005
	Deposit a magnet in a white plastic case at the base of the stainless steel post.
	Cor. is located 55 lks. N. of a trail road, bears N. 70° E. and S. 70° W.
55.15	Trail road, bears N. 40° E. and S. 40° W.
79.20	Trail road, bears North and South.
80.06	The cor. of secs. 9, 10, 15 and 16.
	_____
	N. 0°37' E., bet. secs. 9 and 10.
	Over rolling land.
40.15	Point for the 1/4 sec. cor. of secs. 9 and 10, at proportionate dist.; there is no remaining evidence of the original cor.
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.

**Dependent Resurvey of the Subdivisional Lines,  
T. 22 N., R. 27 E., Gila and Salt River Meridian, Arizona**

CHAINS	
	<p style="text-align: center;">T 22 N R 27 E 1/4 S 9   S 10  2005</p>
80.30	<p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p> <p>Point for the cor. of secs. 3, 4, 9 and 10, at proportionate dist.; there is no remaining evidence of the original cor.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p>
	<p style="text-align: center;">T 22 N R 27 E S 4   S 3 ----- S 9   S 10  2005</p>
	<p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p> <hr/> <p>From the cor. of secs. 2, 3, 10 and 11.</p> <p>N. 89°03' W., bet. secs. 3 and 10.</p> <p>Over rolling land.</p>
39.865	<p>Point for the 1/4 sec. cor. of secs. 3 and 10, at proportionate dist.; there is no remaining evidence of the original cor.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p>
	<p style="text-align: center;">T 22 N R 27 E S 3 1/4 ----- S 10  2005</p>
57.45	<p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p> <p>Trail road, bears North and South.</p>
79.73	<p>The cor. of secs. 3, 4, 9 and 10.</p> <hr/> <p>North, bet. secs. 3 and 4.</p>

**Dependent Resurvey of the Subdivisional Lines,  
T. 22 N., R. 27 E., Gila and Salt River Meridian, Arizona**

CHAINS	
	Over rolling land.
25.15	Trail road, bears East and West.
40.15	Point for the 1/4 sec. cor. of secs. 3 and 4, at proportionate dist.; there is no remaining evidence of the original cor.
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.
	<p align="center">T 22 N R 27 E 1/4 S 4   S 3</p>
	2005
	Deposit a magnet in a white plastic case at the base of the stainless steel post.
47.32	Barbed wire fence, 5 strands, bears S. 40° E. and N. 40° W.
80.20	The cor. of secs. 3, 4, 33 and 34, on the N. bdy. of the Tp., monumented with a stainless steel post, 2 1/2 ins. diam., firmly set, projecting 4 ins. above ground, with brass cap mkd. T23N R27E S33 S34 S4 S3 T22N 2003.
	<hr/> <p>From the cor. of secs. 4, 5, 32 and 33, on the S. bdy. of the Tp., monumented with an iron post, 2 ins. diam., firmly set flush with the surface of the ground, with brass cap mkd. T22N R27E S32 S33 S5 S4 T21N 1994 1947.</p>
	from which the remains of the 1947 bearing trees
	<p>A juniper, 12 ins. diam., bears N. 38° E., 57 lks. dist., mkd. T22N R27E S33 BT on open blaze. (Record: N. 32 3/4° E.)</p>
	A root hole, bears S. 86 1/4° E., 1.31 chs. dist., with remains of juniper branches lying nearby, trunk missing.
	A juniper, 18 ins. diam., bears S. 44 1/2° W., 154 lks. dist., mkd. T22N R27E S5 BT on open blaze.
	A juniper, 16 ins. diam., bears N. 46 1/2° W., 60 lks. dist., no mks. on open blaze.
	Add the marks 2005 to the brass cap.
	Cor. is located 2 lks. N. of a barbed wire fence, 5 strands, bears East and West.
	N. 0°44' E., bet. secs. 32 and 33.

**Dependent Resurvey of the Subdivisional Lines,  
T. 22 N., R. 27 E., Gila and Salt River Meridian, Arizona**

CHAINS							
	Over rolling land.						
40.21	Point for the 1/4 sec. cor. of secs. 32 and 33, at proportionate dist.; there is no remaining evidence of the original cor.						
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.						
	<table style="margin-left: auto; margin-right: auto;"> <tr><td>T 22 N</td><td>R 27 E</td></tr> <tr><td>1/4</td><td></td></tr> <tr><td>S 32</td><td>  S 33</td></tr> </table>	T 22 N	R 27 E	1/4		S 32	S 33
T 22 N	R 27 E						
1/4							
S 32	S 33						
	2005						
	Deposit a magnet in a white plastic case at the base of the stainless steel post.						
80.42	Point for the cor. of secs. 28, 29, 32 and 33, at proportionate dist.; there is no remaining evidence of the original cor.						
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.						
	<table style="margin-left: auto; margin-right: auto;"> <tr><td>T 22 N</td><td>R 27 E</td></tr> <tr><td>S 29</td><td>  S 28</td></tr> <tr><td>S 32</td><td>  S 33</td></tr> </table>	T 22 N	R 27 E	S 29	S 28	S 32	S 33
T 22 N	R 27 E						
S 29	S 28						
S 32	S 33						
	2005						
	Deposit a magnet in a white plastic case at the base of the stainless steel post.						
	<hr/>						
	From the cor. of secs. 27, 28, 33 and 34.						
	N. 89°32' W., bet. secs. 28 and 33.						
	Over rolling land.						
9.35	Trail road, bears N. 5° E. and S. 5° W.						
40.125	Point for the 1/4 sec. cor. of secs. 28 and 33, at proportionate dist.; there is no remaining evidence of the original cor.						
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 12 ins. in the ground to sandstone bedrock, in a mound of stone, 2 1/2 ft. base, 1 ft. high, with brass cap mkd.						

Dependent Resurvey of the Subdivisional Lines,  
T. 22 N., R. 27 E., Gila and Salt River Meridian, Arizona

CHAINS	
	<p style="text-align: center;">T 22 N R 27 E S 28 1/4 ——— S 33</p> <p style="text-align: center;">2005</p>
	<p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p>
80.25	<p>The cor. of secs. 28, 29, 32 and 33.</p> <hr/>
	<p>N. 0°28' E., bet. secs. 28 and 29.</p>
	<p>Over rolling land.</p>
35.89	<p>Barbed wire fence, 5 strands, bears S. 35° E. and N. 35° W.</p>
40.21	<p>Point for the 1/4 sec. cor. of secs. 28 and 29, at proportionate dist.; there is no remaining evidence of the original cor.</p>
	<p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p>
	<p style="text-align: center;">T 22 N R 27 E 1/4 S 29   S 28</p>
	<p style="text-align: center;">2005</p>
	<p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p>
78.80	<p>Trail road, bears N. 80° E. and S. 80° W.</p>
80.42	<p>Point for the cor. of secs. 20, 21, 28 and 29, at proportionate dist.; there is no remaining evidence of the original cor.</p>
	<p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p>
	<p style="text-align: center;">T 22 N R 27 E S 20   S 21 S 29   S 28</p>
	<p style="text-align: center;">2005</p>
	<p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p> <hr/>
	<p>From the cor. of secs. 21, 22, 27 and 28.</p>

**Dependent Resurvey of the Subdivisional Lines,  
T. 22 N., R. 27 E., Gila and Salt River Meridian, Arizona**

CHAINS	
	N. 89°27' W., bet. secs. 21 and 28. Over rolling land.
2.65	Trail road, bears S. 10° E. and N. 10° W.
33.05	Trail road, bears S. 15° E. and N. 15° W.
40.05	Point for the 1/4 sec. cor. of secs. 21 and 28, at proportionate dist.; there is no remaining evidence of the original cor.  Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.  <div style="text-align: center;">                     T 22 N R 27 E                                S 21                      1/4 ———                                S 28                       2005                 </div>
	Deposit a magnet in a white plastic case at the base of the stainless steel post.
75.80	Wash, 15 ft. wide, 2 ft. deep, drains S. 30° W.
80.10	The cor. of secs. 20, 21, 28 and 29.
<hr/>	
	N. 0°31' E., bet. secs. 20 and 21. Over rolling land.
40.21	Point for the 1/4 sec. cor. of secs. 20 and 21, at proportionate dist.; there is no remaining evidence of the original cor.  Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.  <div style="text-align: center;">                     T 22 N R 27 E                                1/4                      S 20   S 21                       2005                 </div>
	Deposit a magnet in a white plastic case at the base of the stainless steel post.
78.30	Apache County Road C272, a graded road, 25 ft. wide, bears S. 45° E. and N. 45° W.
80.42	Point for the cor. of secs. 16, 17, 20 and 21, at proportionate dist.; there is no remaining evidence of the original cor.

**Dependent Resurvey of the Subdivisional Lines,  
T. 22 N., R. 27 E., Gila and Salt River Meridian, Arizona**

CHAINS	
	<p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p align="center">T 22 N R 27 E S 17   S 16 S 20   S 21</p> <p align="center">2005</p> <p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p> <hr/>
	<p>From the cor. of secs. 15, 16, 21 and 22.</p> <p>N. 89°22' W., bet. secs. 16 and 21.</p> <p>Over rolling land.</p>
39.92	<p>Point for the 1/4 sec. cor. of secs. 16 and 21, at proportionate dist.; there is no remaining evidence of the original cor.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p align="center">T 22 N R 27 E S 16 1/4 ——— S 21</p> <p align="center">2005</p> <p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p>
79.84	<p>The cor. of secs. 16, 17, 20 and 21.</p> <hr/> <p>N. 0°03' E., bet. secs. 16 and 17.</p> <p>Over rolling land.</p>
40.21	<p>Point for the 1/4 sec. cor. of secs. 16 and 17, at proportionate dist.; there is no remaining evidence of the original cor.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p align="center">T 22 N R 27 E 1/4 S 17   S 16</p> <p align="center">2005</p>

**Dependent Resurvey of the Subdivisional Lines,  
T. 22 N., R. 27 E., Gila and Salt River Meridian, Arizona**

CHAINS									
	<p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p>								
76.40	<p>N. rim of Padres Mesa, bears N. 85° E. and S. 85° W.</p>								
80.42	<p>Point for the cor. of secs. 8, 9, 16 and 17, at proportionate dist.; there is no remaining evidence of the original cor.</p>								
	<p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p>								
	<table style="margin-left: auto; margin-right: auto;"> <tr> <td>T 22 N</td> <td>R 27 E</td> </tr> <tr> <td>S 8</td> <td>S 9</td> </tr> <tr> <td>S 17</td> <td>S 16</td> </tr> </table>	T 22 N	R 27 E	S 8	S 9	S 17	S 16		
T 22 N	R 27 E								
S 8	S 9								
S 17	S 16								
	<p style="text-align: center;">2005</p>								
	<p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p>								
	<hr/> <p>From the cor. of secs. 9, 10, 15 and 16.</p>								
	<p>N. 89°16' W., bet. secs. 9 and 16.</p>								
	<p>Over rolling land.</p>								
39.895	<p>Point for the 1/4 sec. cor. of secs. 9 and 16, at proportionate dist.; there is no remaining evidence of the original cor.</p>								
	<p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p>								
	<table style="margin-left: auto; margin-right: auto;"> <tr> <td>T 22 N</td> <td>R 27 E</td> </tr> <tr> <td>S 9</td> <td></td> </tr> <tr> <td>1/4</td> <td>—</td> </tr> <tr> <td>S 16</td> <td></td> </tr> </table>	T 22 N	R 27 E	S 9		1/4	—	S 16	
T 22 N	R 27 E								
S 9									
1/4	—								
S 16									
	<p style="text-align: center;">2005</p>								
	<p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p>								
64.50	<p>N. rim of Padres Mesa, bears N. 60° E. and S. 60° W.</p>								
79.79	<p>The cor. of secs. 8, 9, 16 and 17.</p>								
	<hr/> <p>N. 0°24' E., bet. secs. 8 and 9.</p>								
	<p>Over rolling land.</p>								



**Dependent Resurvey of the Subdivisional Lines,  
T. 22 N., R. 27 E., Gila and Salt River Meridian, Arizona**

CHAINS	
40.21	<p>Point for the 1/4 sec. cor. of secs. 8 and 9, at proportionate dist.; there is no remaining evidence of the original cor.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T 22 N R 27 E 1/4 S 8   S 9 2005</p> <p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p>
75.75	<p>Navajo Route 9410, a graded road, 20 ft. wide, bears N. 50° E. and S. 50° W.</p>
80.42	<p>Point for the cor. of secs. 4, 5, 8 and 9, at proportionate dist.; there is no remaining evidence of the original cor.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T 22 N R 27 E S 5   S 4 S 8   S 9 2005</p> <p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p> <hr/> <p>From the cor. of secs. 3, 4, 9 and 10.</p> <p>N. 89°11' W., bet. secs. 4 and 9.</p> <p>Over rolling land.</p>
37.40	<p>N. rim of Padres Mesa, bears N. 50° W. and S. 50° E.</p>
40.04	<p>Point for the 1/4 sec. cor. of secs. 4 and 9, at proportionate dist.; there is no remaining evidence of the original cor.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p>

**Dependent Resurvey of the Subdivisional Lines,  
T. 22 N., R. 27 E., Gila and Salt River Meridian, Arizona**

CHAINS	
	T 22 N R 27 E S 4 1/4 ——— S 9  2005
	Deposit a magnet in a white plastic case at the base of the stainless steel post.
75.55	Navajo Route 9410, a graded road, 25 ft. wide, bears N. 30° E. and S. 30° W.
80.08	The cor. of secs. 4, 5, 8 and 9.
	<hr/> N. 0° 13' E., bet. secs. 4 and 5.  Over rolling land.
8.10	Trail road, bears N. 60° E. and S. 60° W.
40.21	Point for the 1/4 sec. cor. of secs. 4 and 5, at proportionate dist.; there is no remaining evidence of the original cor.
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.
	T 22 N R 27 E 1/4 S 5   S 4  2005
	Deposit a magnet in a white plastic case at the base of the stainless steel post.
80.28	The cor. of secs. 4, 5, 32 and 33, on the N. bdy. of the Tp., monumented with a stainless steel post, 2 1/2 ins. diam., firmly set, projecting 4 ins. above ground, with brass cap mkd. T23N R27E S32 S33 S5 S4 T22N 2003.
	<hr/> From the cor. of secs. 5, 6, 31 and 32, on the S. bdy. of the Tp., monumented with iron post, 2 ins. diam., firmly set flush with the surface of the ground, with brass cap mkd. T22N R27E S31 S32 S6 S5 T21N 1994 1947.  from which the remains of the 1947 bearing trees  A charred juniper stump, 14 ins. diam. at base, bears N. 16 1/2° E., 1.26 chs. dist., with a portion of the burned trunk, 13 ins. diam., lying alongside, mkd. T22N R27E on open blaze.

**Dependent Resurvey of the Subdivisional Lines,  
T. 22 N., R. 27 E., Gila and Salt River Meridian, Arizona**

CHAINS

A juniper, 12 ins. diam., bears S. 51 1/2° E., 1.23 chs. dist., with healed blaze.

A juniper, 18 ins. diam., bears S. 8 1/4° W., 1.56 chs. dist., mkd. T22N R27E S6 BT on open blaze.

A juniper, 16 ins. diam., bears N. 24 1/4° W., 1.56 chs. dist., mkd. T22N R27E S31 BT on open blaze.

Add the marks 2005 to the brass cap.

Cor. is located 5 lks. N. of a barbed wire fence, 5 strands, bears East and West.

N. 0°35' E., bet. secs. 31 and 32.

Over rolling land.

40.35 Point for the 1/4 sec. cor. of secs. 31 and 32, at proportionate dist.; there is no remaining evidence of the original cor.

Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.

T 22 N R 27 E  
1/4  
S 31 | S 32  
2005

Deposit a magnet in a white plastic case at the base of the stainless steel post.

80.70 Point for the cor. of secs. 29, 30, 31 and 32, at proportionate dist.; there is no remaining evidence of the original cor.

Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.

T 22 N R 27 E  
S 30 | S 29  
S 31 | S 32  
2005

Deposit a magnet in a white plastic case at the base of the stainless steel post.

---

From the cor. of secs. 28, 29, 32 and 33.

S. 89°41' W., bet. secs. 29 and 32.

**Dependent Resurvey of the Subdivisional Lines,  
T. 22 N., R. 27 E., Gila and Salt River Meridian, Arizona**

CHAINS	
40.075	<p>Over rolling land.</p> <p>Point for the 1/4 sec. cor. of secs. 29 and 32, at proportionate dist.; there is no remaining evidence of the original cor.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p align="center">T 22 N R 27 E S 29 1/4 ——— S 32</p> <p align="center">2005</p> <p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p>
80.15	<p>The cor. of secs. 29, 30, 31 and 32.</p> <hr/> <p>S. 89°42' W., bet. secs. 30 and 31.</p> <p>Over rolling land.</p>
40.11	<p>Point for the 1/4 sec. cor. of secs. 30 and 31, at proportionate dist.; there is no remaining evidence of the original cor.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p align="center">T 22 N R 27 E S 30 1/4 ——— S 31</p> <p align="center">2005</p> <p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p>
40.80	<p>Top of ridge, bears N. 40° E. and S. 40° W.</p>
69.40	<p>Trail road, bears N. 40° E. and S. 40° W.</p>
78.79	<p>The cor. of secs. 25, 30, 31 and 36, on the W. bdy. of the Tp., monumented with stainless steel post, firmly set, projecting 4 ins. above ground, with brass cap mkd. T22N R26E R27E S25 S30 S36 S31 2003.</p> <hr/> <p>From the cor. of secs. 29, 30, 31 and 32.</p> <p>N. 0°18' E., bet. secs. 29 and 30.</p>

**Dependent Resurvey of the Subdivisional Lines,  
T. 22 N., R. 27 E., Gila and Salt River Meridian, Arizona**

CHAINS	
40.35	<p>Over rolling land.</p> <p>Point for the 1/4 sec. cor. of secs. 29 and 30, at proportionate dist.; there is no remaining evidence of the original cor.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T 22 N R 27 E 1/4 S 30   S 29</p> <p style="text-align: center;">2005</p> <p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p>
80.70	<p>Point for the cor. of secs. 19, 20, 29 and 30, at proportionate dist.; there is no remaining evidence of the original cor.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T 22 N R 27 E S 19   S 20 S 30   S 29</p> <p style="text-align: center;">2005</p> <p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p> <hr/> <p>From the cor. of secs. 20, 21, 28 and 29.</p> <p>S. 89°54' W., bet. secs. 20 and 29.</p> <p>Over rolling land.</p>
40.18	<p>Point for the 1/4 sec. cor. of secs. 20 and 29, at proportionate dist.; there is no remaining evidence of the original cor.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T 22 N R 27 E S 20 1/4 ——— S 29</p> <p style="text-align: center;">2005</p>

**Dependent Resurvey of the Subdivisional Lines,  
T. 22 N., R. 27 E., Gila and Salt River Meridian, Arizona**

CHAINS	
	Deposit a magnet in a white plastic case at the base of the stainless steel post.
80.36	The cor. of secs. 19, 20, 29 and 30.
	<hr/> S. 89°57' W., bet. secs. 19 and 30.  Over rolling land.
8.90	Top of ridge, bears S. 65° E. and N. 65° W.
21.75	Trail road, bears N. 10° E. and S. 10° W.
40.07	Point for the 1/4 sec. cor. of secs. 19 and 30, at proportionate dist.; there is no remaining evidence of the original cor.
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.
	<div style="text-align: center;">             T 22 N R 27 E              S 19              1/4 ———              S 30               2005           </div>
	Deposit a magnet in a white plastic case at the base of the stainless steel post.
45.00	Trail road, bears S. 20° E. and N. 20° W.
78.48	The cor. of secs. 19, 24, 25 and 30, on the W. bdy. of the Tp., monumented with stainless steel post, firmly set, projecting 4 ins. above ground, with brass cap mkd. T22N R26E R27E S24 S19 S25 S30 2003.
	<hr/> From the cor. of secs. 19, 20, 29 and 30.  N. 0°29' E., bet. secs. 19 and 20.  Over rolling land.
28.25	Trail road, bears N. 40° E. and S. 40° W.
40.35	Point for the 1/4 sec. cor. of secs. 19 and 20, at proportionate dist.; there is no remaining evidence of the original cor.
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.

**Dependent Resurvey of the Subdivisional Lines,  
T. 22 N., R. 27 E., Gila and Salt River Meridian, Arizona**

CHAINS	
	T 22 N R 27 E 1/4 S 19   S 20  2005
	Deposit a magnet in a white plastic case at the base of the stainless steel post.
67.20	Graded road, 15 ft. wide, bears N. 85° E. and S. 85° W.
68.67	Barbed wire fence, 4 strands, bears N. 75° E. and S. 75° W.
80.70	Point for the cor. of secs. 17, 18, 19 and 20, at proportionate dist.; there is no remaining evidence of the original cor.
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.
	T 22 N R 27 E S 18   S 17 <hr style="width: 10%; margin: 0 auto;"/> S 19   S 20  2005
	Deposit a magnet in a white plastic case at the base of the stainless steel post.
	<hr/> From the cor. of secs. 16, 17, 20 and 21.  N. 89°55' W., bet. secs. 17 and 20.  Over rolling land.
2.15	Apache County Road C272, a graded road, 25 ft. wide, bears S. 45° E. and N. 45° W.
34.45	Graded road, 15 ft. wide, bears N. 50° E. and S. 50° W.
35.72	Barbed wire fence, 4 strands, bears N. 50° E. and S. 50° W.
40.19	Point for the 1/4 sec. cor. of secs. 17 and 20, at proportionate dist.; there is no remaining evidence of the original cor.
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.

Dependent Resurvey of the Subdivisional Lines,  
T. 22 N., R. 27 E., Gila and Salt River Meridian, Arizona

CHAINS	<p style="text-align: center;">T 22 N R 27 E S 17 1/4 ——— S 20</p> <p style="text-align: center;">2005</p> <p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p> <p>80.38 The cor. of secs. 17, 18, 19 and 20.</p> <hr/> <p>N. 89°48' W., bet. secs. 18 and 19.</p> <p>Over rolling land.</p> <p>39.95 Point for the 1/4 sec. cor. of secs. 18 and 19, at proportionate dist.; there is no remaining evidence of the original cor.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T 22 N R 27 E S 18 1/4 ——— S 19</p> <p style="text-align: center;">2005</p> <p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p> <p>78.43 The cor. of secs. 13, 18, 19 and 24, on the W. bdy. of the Tp., monumented with stainless steel post, firmly set, projecting 4 ins. above ground, with brass cap mkd. T22N R26E R27E S13 S18 S24 S19 2003.</p> <hr/> <p>From the cor. of secs. 17, 18, 19 and 20.</p> <p>N. 0°23' E., bet. secs. 17 and 18.</p> <p>Over rolling land.</p> <p>29.86 Power line, bears N. 50° E. and S. 50° W.</p> <p>40.35 Point for the 1/4 sec. cor. of secs. 17 and 18, at proportionate dist.; there is no remaining evidence of the original cor.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p>
--------	--



**Dependent Resurvey of the Subdivisional Lines,  
T. 22 N., R. 27 E., Gila and Salt River Meridian, Arizona**

CHAINS	
	<p style="text-align: center;">T 22 N R 27 E 1/4 S 18   S 17</p> <p style="text-align: center;">2005</p>
	<p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p>
	<p>Cor. is located near the rim of Padres Mesa, bears N. 25° E. and S. 25° W.</p>
57.70	<p>Power line, bears S. 20° E. and N. 20° W.</p>
80.70	<p>Point for the cor. of secs. 7, 8, 17 and 18, at proportionate dist.; there is no remaining evidence of the original cor.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p>
	<p style="text-align: center;">T 22 N R 27 E S 7   S 8 ----- S 18   S 17</p> <p style="text-align: center;">2005</p> <p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p> <hr/> <p>From the cor. of secs. 8, 9, 16 and 17.</p> <p>N. 89°42' W., bet. secs. 8 and 17.</p> <p>Over rolling land.</p>
39.95	<p>Point for the 1/4 sec. cor. of secs. 8 and 17, at proportionate dist.; there is no remaining evidence of the original cor.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p>
	<p style="text-align: center;">T 22 N R 27 E S 8 1/4 ----- S 17</p> <p style="text-align: center;">2005</p> <p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p>

**Dependent Resurvey of the Subdivisional Lines,  
T. 22 N., R. 27 E., Gila and Salt River Meridian, Arizona**

CHAINS	
	<p>From this cor. point, a brass tablet, 3 ins. diam., cemented on concrete post, 7 ins. square, firmly set flush with the surface of the ground, bears S. 4°52' W., 27.79 chs. dist., the remaining reference monument to second order U. S. Geological Survey triangulation station "WIDE RUIN 1972", which has been destroyed, with top mkd. WIDE RUIN NO. 2 1972 and an arrow.</p>
79.90	<p>The cor. of secs. 7, 8, 17 and 18.</p> <hr/> <p>N. 89°32' W., bet. secs. 7 and 18.</p> <p>Over rolling land.</p>
39.09	<p>Barbed wire fence, 5 strands, bears N. 25° E. and S. 25° W.</p>
39.99	<p>Point for the 1/4 sec. cor. of secs. 7 and 18, at proportionate dist.; there is no remaining evidence of the original cor.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center;"> <p>T 22 N R 27 E</p> <p>S 7</p> <p>1/4 ———</p> <p>S 18</p> <p>2005</p> </div> <p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p>
78.23	<p>The cor. of secs. 7, 12, 13 and 18, on the W. bdy. of the Tp., monumented with stainless steel post, firmly set, projecting 4 ins. above ground, with brass cap mkd. T22N R26E R27E S12 S7 S13 S18 2003.</p> <hr/> <p>From the cor. of secs. 7, 8, 17 and 18.</p> <p>N. 0°21' E., bet. secs. 7 and 8.</p> <p>Over rolling land.</p>
23.15	<p>Navajo Route 9410, a graded road, 25 ft. wide, bears N. 60° E. and S. 60° W.</p>
40.35	<p>Point for the 1/4 sec. cor. of secs. 7 and 8, at proportionate dist.; there is no remaining evidence of the original cor.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p>

**Dependent Resurvey of the Subdivisional Lines,  
T. 22 N., R. 27 E., Gila and Salt River Meridian, Arizona**

CHAINS	
	<p style="text-align: center;">T 22 N R 27 E 1/4 S 7   S 8  2005</p> <p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p>
77.25	Trail road, bears S. 50° E. and N. 50° W.
80.70	<p>Point for the cor. of secs. 5, 6, 7 and 8, at proportionate dist.; there is no remaining evidence of the original cor.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T 22 N R 27 E S 6   S 5 ----- S 7   S 8  2005</p> <p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p> <hr/> <p>From the cor. of secs. 4, 5, 8 and 9.</p> <p>N. 89°30' W., bet. secs. 5 and 8.</p> <p>Over rolling land.</p>
39.98	<p>Point for the 1/4 sec. cor. of secs. 5 and 8, at proportionate dist.; there is no remaining evidence of the original cor.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T 22 N R 27 E S 5 1/4 ----- S 8  2005</p> <p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p>
47.79	Barbed wire fence, 5 strands, bears N. 85° E. and S. 85° W.
44.60	Trail road, bears N. 80° E. and S. 80° W.

**Dependent Resurvey of the Subdivisional Lines,  
T. 22 N., R. 27 E., Gila and Salt River Meridian, Arizona**

CHAINS	
79.96	<p>The cor. of secs. 5, 6, 7 and 8.</p> <hr/> <p>N. 89°17' W., bet. secs. 6 and 7.</p> <p>Over rolling land.</p> <p>3.90 Trail road, bears S. 50° E. and N. 50° W.</p> <p>16.83 Power line, bears S. 65° E. and N. 65° W.</p> <p>35.60 Trail road, bears S. 35° E. and N. 35° W.</p> <p>39.92 Point for the 1/4 sec. cor. of secs. 6 and 7, at proportionate dist.; there is no remaining evidence of the original cor.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p>
	<p style="text-align: center;">T 22 N R 27 E           S 6           1/4 ———           S 7</p> <p style="text-align: center;">2005</p>
78.00	<p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p> <p>The cor. of secs. 1, 6, 7 and 12, on the W. bdy. of the Tp., monumented with stainless steel post, firmly set, projecting 4 ins. above ground, with brass cap mkd. T22N R26E R27E S1 S6 S12 S7 2003.</p>
	<hr/> <p>From the cor. of secs. 5, 6, 7 and 8.</p> <p>N. 0°21' E., bet. secs. 5 and 6.</p> <p>Over rolling land.</p> <p>8.60 Power line, bears N. 65° E. and S. 65° W.</p> <p>40.35 Point for the 1/4 sec. cor. of secs. 5 and 6, at proportionate dist.; there is no remaining evidence of the original cor.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p>
	<p style="text-align: center;">T 22 N R 27 E           1/4           S 6   S 5</p> <p style="text-align: center;">2005</p>





## CERTIFICATE OF SURVEY

I, Leonard Sandoval, Cadastral Surveyor, HEREBY CERTIFY upon honor, that in pursuance of special instructions bearing date of the 29th day of December, 2004, I have dependently resurveyed the subdivisional lines, T. 22 N., R. 27 E., of the Gila and Salt River Meridian, in the State of Arizona, which are represented in the foregoing field notes as having been executed by me and under my direction. Said survey has been made in strict conformity with said special instructions, the Manual of Instructions for the Survey of the Public Lands of the United States, 1973, and in specific manner described in the foregoing field notes.

2-21-06

(Date)

Leonard R. Sandoval  
(Cadastral Surveyor)

## CERTIFICATE OF APPROVAL

BUREAU OF LAND MANAGEMENT  
Phoenix, Arizona

The foregoing field notes of the dependent resurvey of the subdivisional lines, T. 22 N., R. 27 E., Gila and Salt River Meridian, in the State of Arizona, executed by Leonard Sandoval, Cadastral Surveyor, having been critically examined and found correct, are hereby approved.

4/06/06

(Date)

Stephen K. Hansen  
(Chief Cadastral Surveyor of Arizona)

~~CERTIFICATE OF TRANSCRIPT~~

~~I CERTIFY That the foregoing transcript of the field notes of the above described surveys in T. 22 N., R. 27 E., Gila and Salt River Meridian, Arizona, is a true copy of the original field notes.~~

~~(Date)~~

~~(Chief Cadastral Surveyor of Arizona)~~

