

ORIGINAL

**UNITED STATES  
DEPARTMENT OF THE INTERIOR  
BUREAU OF LAND MANAGEMENT**

FIELD NOTES  
OF THE  
DEPENDENT RESURVEY OF  
A PORTION OF THE FIFTH GUIDE MERIDIAN WEST (EAST BOUNDARY),  
A PORTION OF THE SOUTH BOUNDARY,  
A PORTION OF THE SUBDIVISIONAL LINES,  
AND  
THE METES-AND-BOUNDS SURVEY OF THE WARM SPRINGS WILDERNESS  
AREA BOUNDARY THROUGH SECTIONS 20, 22, 23, 26 AND 35,  
**TOWNSHIP 19 NORTH, RANGE 19 WEST,**  
OF THE GILA AND SALT RIVER MERIDIAN,  
IN THE STATE OF ARIZONA.

**EXECUTED BY**

**W. William Foster, Cadastral Surveyor**

Under Special Instructions dated February 17, 2004, approved February 17, 2004, which provided for the surveys included under Group No. 928, and assignment instructions dated February 17, 2004.

**Survey commenced March 1, 2004**

**Survey completed April 14, 2004**

**INDEX DIAGRAM**

TOWNSHIP 19 NORTH                      RANGE 19 WEST  
 GILA AND SALT RIVER MERIDIAN, ARIZONA

6	5	4	3	2	1
7	8	9	10	11	12
18 19	17 19	16	15 16	14	13 4 8
19	20 18	21 14 17	22 13	23 6 12	24
30	29	28	27 11	26 10	25
31	32	33	34	35 6	36

Metes-and-Bounds Survey of the Warm Springs Wilderness Area  
 Boundary Through Sections 20, 22, 23, 26 and 35 . Pages 20-64

**T. 19 N., R. 19 W., Gila and Salt River Meridian, Arizona**

CHAINS

The following field notes describe the dependent resurvey of a portion of the Fifth Guide Meridian West (east boundary), a portion of the south boundary, and a portion of the subdivisional lines, and the metes-and-bounds survey of the Warm Springs Wilderness Area Boundary through sections 20, 22, 23, 26 and 35, Township 19 North, Range 19 West, Gila and Salt River Meridian, Arizona.

The history of surveys pertaining to this survey is as follows:

William B. Alexander surveyed the south and west boundaries, and a portion of the subdivision lines, in 1910-12. Harry K. Smith resurveyed a portion of the 5th Guide Meridian West (east boundary), in 1977. Dennis K. McKay resurveyed a portion of the 5th Guide Meridian West (east boundary), south, west and north boundaries, and a portion of the subdivisional lines, in 1984-90. Olian T. Shockley resurveyed a portion of subdivisional lines, in 1992.

The survey was executed in accordance with the specifications as set forth in the Manual of Instructions for the Survey of the Public Lands of the United States, 1973, and the Special Instructions dated February 17, 2004, for Group No. 928, Arizona.

The true meridian direction and length of all lines were determined by real time kinematic global positioning system observations using Topcon Hyper Plus model receivers.

Preliminary to the resurvey, the lines of the prior surveys were retraced and search was made for all corners and other calls of record. Identified corners were remonumented in their original positions. Lost corners were reestablished and remonumented at proportionate positions based on the official record. The retracement data were thoroughly verified and only the true line field notes are given herein.

Geodetic control was derived from second order U. S. Coast and Geodetic Survey triangulation station "Fig Spring 1948," as published by the National Geodetic Survey, NAD 83 (1992). The geographic position of the corner of sections 13, 18, 19 and 24, Township 19 North, Ranges 18 and 19 West, is as follows:

Latitude: 35°01'31.35" N.                      Longitude: 114°14'43.95" W.

The mean magnetic declination is 12 3/4° E.

---

**Dependent Resurvey of a Portion of the  
Fifth Guide Meridian West (East Boundary),  
T. 19 N., R. 19 W., Gila and Salt River Meridian, Arizona**

CHAINS	
	Restoring the resurvey executed by Harry K. Smith, in 1977
	Beginning at the cor. of secs. 13, 18, 19 and 24 on the E. bdy. of the Tp., monumented with an iron post, 2 1/2 ins. diam., firmly set, projecting 11 ins. above a supporting mound of stone, 3 ft. base, with brass cap mkd. T19N R19W R18W S13 S18 S24 S19 1977. A mound of stone, 3 ft. base, 2 ft. high, is W. of cor.
	Add the marks 2004 to the brass cap.
	N. 0°02' W., bet. secs. 13 and 18, on the E. bdy.
	Over level to rolling land, through creosote, yucca and sage brush.
14.18	Point for a witness point on line bet. secs. 13 and 18.  Set an aluminum drive rod, 42 ins. long, 3/4 in. diam., 36 ins. in the ground, with aluminum cap mkd.
	WP T 19 N R 19 W   R 18 W S 13   S 18 WSWA 2004
26.71	Point for a witness point on line bet. secs. 13 and 18.  Set an aluminum drive rod, 42 ins. long, 3/4 in. diam., 34 ins. in the ground, with aluminum cap mkd.
	WP T 19 N R 19 W   R 18 W S 13   S 18 WSWA 2004
39.70	The 1/4 sec. cor. of secs. 13 and 18, monumented with an iron post, 2 1/2 ins. diam., firmly set, projecting 6 ins. above the ground, with brass cap mkd. T19N 1/4 R19W R18W S13 S18 1977. A mound of stone, 3 ft. base, 2 ft. high is W. of cor.  Add the marks 2004 to the brass cap.
	WP T 19 N R 19 W   R 18 W S 13   S 18 WSWA 2004
	N. 0°04' W., beginning new measurement.
13.43	Point for a witness point on line bet. secs. 13 and 18.

**Dependent Resurvey of a Portion of the  
Fifth Guide Meridian West (East Boundary),  
T. 19 N., R. 19 W., Gila and Salt River Meridian, Arizona**

CHAINS	
	<p>Set an aluminum drive rod, 27 ins. long, 3/4 in. diam., 20 ins. in the ground, with aluminum cap mkd.</p> <p style="text-align: center;">WP T 19 N R 19 W   R 18 W S 13   S 18 WSWA</p> <p style="text-align: center;">2004</p>
19.69	Point on line, a 5/8 in. iron rod, firmly set, projecting 5 ins. above the ground, with aluminum cap mkd. RLS 25401.
27.50	<p>Point for a witness point on line bet. secs. 13 and 18.</p> <p>Set an aluminum drive rod, 42 ins. long, 3/4 in. diam., 35 ins. in the ground, with aluminum cap mkd.</p> <p style="text-align: center;">WP T 19 N R 19 W   R 18 W S 13   S 18 WSWA</p> <p style="text-align: center;">2004</p>
40.02	<p>The cor. of secs. 7, 12, 13 and 18, monumented with an iron post, 2 1/2 ins. diam., firmly set, projecting 6 ins. above the ground, with brass cap mkd. T19N R19W R18W S12 S7 S13 S18 1977. A mound of stone, 4 ft. base, 3 ft. high, is W. of cor.</p> <p>Add the marks 2004 to the brass cap.</p> <p>From this cor. point, U.S.C. &amp; G.S. triangulation station "FIG SPRING 1948" bears N. 16°41' E., 91.49 chs. dist., a bronze disc, 3 ins. diam., set in a concrete collar, 12 ins. diam., projecting 2 1/2 ins. above the ground, with top mkd. FIG SPRING 1948.</p> <hr/>

**Dependent Resurvey of a Portion of the South Boundary,  
T. 19 N., R. 19 W., Gila and Salt River Meridian, Arizona**

CHAINS	
	<p>Restoring the survey executed by Dennis K. Mckay, in 1984-1990</p> <hr/>
	<p>From the cor. of secs. 1, 2, 35 and 36, on the S. bdy. of the Tp., monumented with an aluminum post, 1 in. diam., firmly set projecting 4 ins. above the ground with aluminum cap mkd. T19NR19W S35 S36 S2 S1 T18N 1984.</p> <p>Add the marks 2004 to the aluminum cap.</p> <p>N. 89°58' W., bet. secs. 2 and 35, on the S. bdy. of the Tp.</p> <p>Over rolling, rocky land, through creosote and scrub brush.</p>
23.31	Point for AP 15, sec. 35, hereinafter described.
24.22	Point for AP 16, sec. 35, hereinafter described.
39.99	<p>The 1/4 sec. cor. of secs. 2 and 35, monumented with an aluminum post, 1 in. diam., firmly set, projecting 10 ins. above the ground, in a collar of stone, with aluminum cap mkd. T19NR19W 1/4 S35 S2 T18N 1984. A mound of stone, 3 ft. base, 1 1/2 ft. high, is N. of cor.</p> <p>Add the marks 2004 to the aluminum cap.</p> <hr/>
	<p><b>Dependent Resurvey of a Portion of the Subdivisional Lines, T. 19 N., R. 19 W., Gila and Salt River Meridian, Arizona</b></p> <hr/>
	<p>Restoring the surveys executed by William B. Alexander, in 1910-12 and Dennis K. Mckay, in 1984-90</p> <hr/>
	<p>From the cor. of secs. 23, 24, 25 and 26, monumented with an iron post, 2 1/2 ins. diam., firmly set in a supporting mound of stone, 4 ft. base, 2 ft. high, with brass cap mkd. T19NR19W S23 S24 S26 S25 1984. A mound of stone, 3 ft. base, 1 1/2 ft. high, is W. of cor. and a steel fence post is set alongside the iron post.</p> <p>Add the marks 2004 to the brass cap.</p> <p>Cor. is located SE of a bladed road bears N. and W.</p> <p>N. 0°05' W., bet. secs. 23 and 24.</p> <p>Over rolling rocky land, through creosote, yucca and scrub brush.</p>
15.77	Point for a witness point on line bet. secs. 23 and 24.

**Dependent Resurvey of a Portion of the Subdivisional Lines,  
T. 19 N., R. 19 W., Gila and Salt River Meridian, Arizona**

CHAINS	
	<p>Set an aluminum drive rod, 42 ins. long, 3/4 in. diam., 18 ins. in the ground to bedrock, in a supporting mound of stone, 4 ft. base to top, with aluminum cap mkd.</p> <p style="text-align: center;">                     WP                      T 19 N R 19 W                      S 23   S 24                              WSWA                      2004                 </p>
<p>27.82</p>	<p>Point for a witness point on line bet. secs. 23 and 24.</p> <p>Set an aluminum drive rod, 42 ins. long, 3/4 in. diam., 30 ins. in the ground, in a collar of stone, with aluminum cap mkd.</p> <p style="text-align: center;">                     WP                      T 19 N R 19 W                      S 23   S 24                              WSWA                      2004                 </p>
<p>40.15</p>	<p>The 1/4 sec. cor. of secs. 23 and 24, monumented with a stainless steel post, 2 1/2 ins. diam., firmly set in a supporting mound of stone, 3 ft. base, 1 1/2 ft. high, with brass cap mkd. T19NR19W 1/4 S23 S24 1984. A steel fence post is W. of cor.</p> <p>Add the marks 2004 to the brass cap.</p> <p>Cor. is located 19 lks. E. of a bladed road, 15 ft. wide, bears N. and S.</p> <hr style="width: 20%; margin: 10px auto;"/> <p>N. 0°03' W., beginning new measurement.</p>
<p>15.56</p>	<p>Point for a witness point on line bet. secs. 23 and 24.</p> <p>Set an aluminum drive rod, 42 ins. long, 3/4 in. diam., 32 ins. in the ground, in a collar of stone, with aluminum cap mkd.</p> <p style="text-align: center;">                     WP                      T 19 N R 19 W                      S 23   S 24                              WSWA                      2004                 </p> <p>Cor. is located on the E. edge of a bladed road, 12 ft. wide, bears N. and S.</p>

**Dependent Resurvey of a Portion of the Subdivisional Lines,  
T. 19 N., R. 19 W., Gila and Salt River Meridian, Arizona**

CHAINS					
27.45	<p>Point for a witness point on line bet. secs. 23 and 24.</p> <p>Set an aluminum drive rod, 42 ins. long, 3/4 in. diam., 19 ins. in the ground to bedrock, in a supporting mound of stone, 4 ft. base to top, with aluminum cap mkd.</p> <div style="text-align: center;"> <p>WP</p> <p>T 19 N R 19 W</p> <table style="margin: auto; border-collapse: collapse;"> <tr> <td style="border-right: 1px solid black; padding: 0 5px;">S 23</td> <td style="padding: 0 5px;">S 24</td> </tr> <tr> <td style="border-right: 1px solid black; padding: 0 5px;"></td> <td style="padding: 0 5px;">WSWA</td> </tr> </table> <p>2004</p> </div> <p>Cor. is located on the E. edge of a bladed road, 12 ft. wide, bears N. and S.</p>	S 23	S 24		WSWA
S 23	S 24				
	WSWA				
40.00	<p>The cor. of secs. 13, 14, 23 and 24, monumented with an aluminum post, 1 in. diam., firmly set, projecting 11 ins. above the ground in a supporting mound of stone, 3 ft. base, to top, with aluminum cap mkd. T19NR19W S14 S13 S23 S24 1984. A steel fence post is W. of cor.</p> <p>Add the marks 2004 to the aluminum cap.</p> <hr/> <p>From the cor. of secs. 13, 18, 19 and 24, on the E. bdy. of the Tp., hereinbefore described.</p> <p>N. 89°52' W., bet. secs. 13 and 24.</p> <p>Over rolling, rocky land, through creosote, yucca and scrub brush.</p>				
13.29	<p>Point for a witness point on line bet. secs. 13 and 24.</p> <p>Set an aluminum drive rod, 30 ins. long, 3/4 in. diam., 24 ins. in the ground, with aluminum cap mkd.</p> <div style="text-align: center;"> <p>WP</p> <p>T 19 N R 19 W</p> <p>S 13</p> <hr style="width: 10%; margin: 0 auto;"/> <p>S 24</p> <p>WSWA</p> <p>2004</p> </div>				
28.44	<p>Point for a witness point on line bet. secs. 13 and 24.</p>				



**Dependent Resurvey of a Portion of the Subdivisional Lines,  
T. 19 N., R. 19 W., Gila and Salt River Meridian, Arizona**

CHAINS	
	<p>Set an aluminum drive rod, 42 ins. long, 3/4 in. diam., 36 ins. in the ground, with aluminum cap mkd.</p> <p align="center">WP T 19 N R 19 W S 13 ----- S 24. WSWA  2004</p>
39.97	<p>The 1/4 sec. cor. of secs. 13 and 24, monumented with an aluminum post, 1 in. diam., firmly set, projecting 5 ins. above the ground, with brass cap mkd. T19NR19W 1/4 S13 S24 1984. A mound of stone, 3 ft. base, 2 ft. high, is N. of cor. A steel fence post is N. of cor.</p> <p>Add the marks 2004 to the aluminum cap.</p> <p align="center">-----</p> <p>N. 89°53' W., beginning new measurement.</p>
12.83	<p>Point for a witness point on line bet. secs. 13 and 24.</p> <p>Set an aluminum drive rod, 42 ins. long, 3/4 in. diam., 29 ins. in the ground, with aluminum cap mkd.</p> <p align="center">WP T 19 N R 19 W S 13 ----- S 24 WSWA  2004</p>
23.89	<p>Point for a witness point on line bet. secs. 13 and 24.</p> <p>Set an aluminum drive rod, 32 ins. long, 3/4 in. diam., 26 ins. in the ground, with aluminum cap mkd.</p>

**Dependent Resurvey of a Portion of the Subdivisional Lines,  
T. 19 N., R. 19 W., Gila and Salt River Meridian, Arizona**

CHAINS	
	<p align="center">WP T 19 N R 19 W S 13</p> <hr/> <p align="center">S 24 WSWA</p> <p align="center">2004</p>
39.93	<p>The cor. of secs. 13, 14, 23 and 24.</p> <hr/> <p>From the cor. of secs. 25, 26, 35 and 36, monumented with a Malapais stone, 18 X 12 X 10 ins., firmly set, projecting 6 ins. above the ground, with one notch on E. face and one notch on the S. face.</p> <p>At the corner point</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p align="center">T 19 N R 19 W S 26   S 25 S 35   S 36</p> <p align="center">2004</p> <p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p> <p>Bury the original stone alongside the post.</p> <p>A mound of stone, 3 ft. base, 1 1/2 ft. high, is W. of cor.</p> <p>N. 89°57' W., bet. secs. 26 and 35.</p> <p>Over rolling rocky land, through creosote, yucca and scrub brush.</p>
31.80	Point for AP 17, sec. 26, identical with AP 1, sec. 35, hereinafter described.
34.75	Point for AP 18, sec. 26, identical with AP 32, sec. 35, hereinafter described.
39.88	The 1/4 sec. cor. of secs. 26 and 35, monumented with a Malapais stone, 18 X 10 X 9 ins., firmly set, projecting 9 ins. above the ground, with 1/4 scribed on the N. face. A mound of stone, 3 ft. base, 2 ft. high, is N. of cor.

**Dependent Resurvey of a Portion of the Subdivisional Lines,  
T. 19 N., R. 19 W., Gila and Salt River Meridian, Arizona**

CHAINS	
	<p>At the corner point</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T 19 N R 19 W S 26 1/4 ——— S 35</p> <p style="text-align: center;">2004</p> <p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p> <p>Bury original stone alongside the post.</p> <hr/>
	<p>From the 1/4 sec. cor. of secs. 26 and 27, monumented with a stainless steel post, 2 1/2 ins. diam., firmly set, projecting 4 ins. above a supporting mound of stone, 4 ft. base, 2 ft. high, with brass cap mkd. T19NR19W 1/4 S27 S26 1984. A steel fence post and a rebar, 3/8 in. diam., are W. of cor.</p> <p>Add the marks 2004 to the brass cap.</p> <p>N. 0°06' W., bet. secs. 26 and 27.</p> <p>Over rolling, rocky land, through creosote, yucca and scrub brushes.</p>
39.02	<p>The witness cor. of secs. 22, 23, 26 and 27, monumented with an aluminum post, 1 in. diam., firmly set in a supporting mound of stone, 3 ft. base, 1 1/2 ft. high, with aluminum cap mkd. WC T19NR19W S22 S23 S27 S26 1984 and an arrow pointing to the true point.</p> <p>Add the marks 2004 to the aluminum cap.</p> <hr/>
1.00	<p>N. 0°06' W., beginning new measurement.</p> <p>True point for the cor. of secs. 22, 23, 26 and 27.</p> <p>The true point falls in a dry sandy wash, 70 ft. wide, 10 ft. deep, drains S. 50° E., where it is impracticable to establish a permanent monument.</p> <hr/> <p>From the cor. of secs. 23, 24, 25 and 26.</p>

Dependent Resurvey of a Portion of the Subdivisional Lines,  
T. 19 N., R. 19 W., Gila and Salt River Meridian, Arizona

CHAINS	
12.62	<p>N. 89°52' W., bet. secs. 23 and 26.</p> <p>Over rolling rocky land, through creosote, yucca and scrub brush.</p> <p>Point for a witness point on line bet. secs. 23 and 26.</p> <p>Set an aluminum drive rod, 42 ins. long, 3/4 in. diam., 24 ins. in the ground to bedrock, in a supporting mound of stone, 3 ft. base to top, with aluminum cap mkd.</p>
	<p style="text-align: center;">WP T 19 N R 19 W S 23 ----- S 26 WSWA 2004</p>
23.94	<p>Cor. is in the middle of a graded road, 12 ft. wide, bears E. and W.</p> <p>Point for a witness point on line bet. secs. 23 and 26.</p> <p>Set an aluminum drive rod, 42 ins. long, 3/4 in. diam., 13 ins. in the ground to bedrock, in a supporting mound of stone, 3 ft. base to top, with aluminum cap mkd.</p>
	<p style="text-align: center;">WP T 19 N R 19 W S 23 ----- S 26 WSWA 2004</p>
39.93	<p>Cor. is in the middle of a graded road, 12 ft. wide, bears E. and W.</p> <p>The 1/4 sec. cor. of secs. 23 and 26, monumented with an iron post, 2 1/2 ins. diam., firmly set, projecting 5 ins. above a collar of stone, with brass cap mkd. T19NR19W 1/4 S23 S26 1984. An accessory mound of stone, 3 ft. base, 1 1/2 ft. high and a steel fence post are N. of cor.</p> <p>Add the marks 2004 to the brass cap.</p> <hr style="width: 20%; margin: 10px auto;"/> <p>S. 89°59' W., beginning new measurement.</p>

**Dependent Resurvey of a Portion of the Subdivisional Lines,  
T. 19 N., R. 19 W., Gila and Salt River Meridian, Arizona**

CHAINS	
12.65	<p>Point for a witness point on line bet. secs. 23 and 26.</p> <p>Set an aluminum drive rod, 23 ins. long, 3/4 in. diam., 17 ins. in the ground, with aluminum cap mkd.</p>
	<p align="center">WP T 19 N R 19 W S 23 <hr/>S 26  WSWA 2004</p>
20.11	<p>A rebar, 1/2 in. diam., firmly set, projecting 11 ins. above the ground, bears N., 5 lks. dist.</p>
27.06	<p>Point for a witness point on line bet. secs. 23 and 26.</p> <p>Set an aluminum drive rod, 42 ins. long, 3/4 in. diam., 36 ins. in the ground, with aluminum cap mkd.</p>
	<p align="center">WP T 19 N R 19 W S 23 <hr/>S 26  WSWA 2004</p>
34.60	<p>Point for AP 1, sec. 26, hereinafter described.</p>
35.82	<p>Point for AP 34, sec. 26, identical to AP 1, sec. 23, hereinafter described.</p>
40.03	<p>The true point for the cor. of secs. 22, 23, 26 and 27.</p> <hr/> <p>N. 0°16' W., bet. secs. 22 and 23.</p> <p>Over rolling, rocky land, through creosote, yucca and scrub brush.</p>
0.15	<p>Dry sandy wash, 70 ft. wide, 10 ft. deep, drains S. 50° E.</p>
5.62	<p>The point for AP 1, sec. 22, identical with AP 2, sec. 23, hereinafter described.</p>

**Dependent Resurvey of a Portion of the Subdivisional Lines,  
T. 19 N., R. 19 W., Gila and Salt River Meridian, Arizona**

CHAINS	
40.04	<p>The 1/4 sec. cor. of secs. 22 and 23, monumented with an iron post, 2 1/2 ins. diam., firmly set in a supporting mound of stone, 4 ft. base, 2 ft. high, with brass cap mkd. T19NR19W 1/4 S22 S23 1984.</p> <p>Add the marks 2004 to the brass cap.</p> <p>Cor. is located on W. edge of a bladed road, 20 ft. wide, bears N., E. and S.</p> <hr style="width: 20%; margin: 20px auto;"/> <p>N. 0°05' W., beginning new measurement.</p>
40.07	<p>The cor. of secs. 14, 15, 22 and 23, monumented with an iron post, 2 1/2 ins. diam., firmly set, projecting 6 ins. above a supporting mound of stone, 4 ft. base, 2 ft. high, with brass cap mkd. T19NR19W S15 S14 S22 S23 1984. A steel fence post is S. of cor.</p> <p>Add the marks 2004 to the brass cap.</p> <p>Cor. is located on N. edge of a bladed road, 20 ft. wide, bears E. and S.</p> <hr style="width: 20%; margin: 20px auto;"/> <p>From the cor. of secs. 21, 22, 27 and 28, monumented with a stainless steel post, 2 1/2 ins. diam., firmly set, projecting 2 ins. above a supporting mound of stone, 4 ft. base, 1 1/2 ft. high, with brass cap mkd. T19NR19W S21 S22 S28 S27 1984. A steel fence post is N. of cor.</p> <p>Add the marks 2004 to the brass cap.</p> <p>N. 0°05' W., bet. secs. 21 and 22.</p> <p>Over broken rocky land, through scattered creosote, yucca, ocotillo and scrub brush.</p>
14.88	<p>Point for a witness point on line bet. secs. 21 and 22.</p> <p>Set an aluminum drive rod, 42 ins. long, 3/4 in. diam., 15 ins. in the ground to bedrock, in a supporting mound of stone, 4 ft. base to top, with aluminum cap mkd.</p>

Dependent Resurvey of a Portion of the Subdivisional Lines,  
T. 19 N., R. 19 W., Gila and Salt River Meridian, Arizona

CHAINS	
27.55	<p style="text-align: center;">WP T 19 N R 19 W</p> <p style="text-align: center;">S 21   S 22             WSWA</p> <p style="text-align: center;">2004</p> <p>Point for a witness point on line bet. secs. 21 and 22.</p> <p>Set an aluminum drive rod, 42 ins. long, 3/4 in. diam., 23 ins. in the ground to bedrock, in a supporting mound of stone, 3 ft. base to top, with aluminum cap mkd.</p>
40.03	<p style="text-align: center;">WP T 19 N R 19 W</p> <p style="text-align: center;">S 21   S 22             WSWA</p> <p style="text-align: center;">2004</p> <p>The 1/4 sec. cor. of secs. 21 and 22, monumented with a stainless steel post, 2 1/2 ins. diam., firmly set in a supporting mound of stone, 4 ft. base, 2 ft. high, with brass cap mkd. T19NR19W 1/4 S21 S22 1984. A steel fence post is N. of cor.</p> <p>Add the marks 2004 to the brass cap.</p> <hr style="width: 20%; margin: 10px auto;"/> <p>N. 0°06' W., beginning new measurement.</p>
11.90	<p>Point for a witness point on line bet. secs. 21 and 22.</p> <p>Set an aluminum drive rod, 42 ins. long, 3/4 in. diam., 10 ins. in the ground to bedrock, in a supporting mound of stone, 4 ft. base to top, with aluminum cap mkd.</p>
35.36	<p style="text-align: center;">WP T 19 N R 19 W</p> <p style="text-align: center;">S 21   S 22             WSWA</p> <p style="text-align: center;">2004</p> <p>Point for a witness point on line bet. secs. 21 and 22.</p> <p>Set an aluminum drive rod, 26 ins. long, 3/4 in. diam., 20 ins. in the ground, with aluminum cap mkd.</p>

**Dependent Resurvey of a Portion of the Subdivisional Lines,  
T. 19 N., R. 19 W., Gila and Salt River Meridian, Arizona**

CHAINS	
	<p style="text-align: center;">WP T 19 N R 19 W S 21   S 22             WSWA 2004 .</p>
40.02	<p>The cor. of secs. 15, 16, 21 and 22, monumented with an aluminum post, 1 in. diam., firmly set in a supporting mound of stone, 3 ft. base, 1 ft. high, with aluminum cap mkd. T19NR19W S16 S15 S21 S22 1984 1992.</p> <p>Add the marks 2004 to the aluminum cap.</p> <hr/>
	<p>From the cor. of secs. 14, 15, 22 and 23.</p> <p>N. 89°54' W., bet. secs. 15 and 22.</p> <p>Over level rocky land, through creosote, yucca and scrub brush.</p>
32.40	<p>Bladed road, 20 ft. wide, bears S. 30° E. and N. 30° W.</p>
32.86	<p>Point for AP 13, sec. 22, hereinafter described.</p>
39.99	<p>The 1/4 sec. cor. of secs. 15 and 22, monumented with an aluminum post, 1 in. diam., firmly set, projecting 6 ins. above the ground, with aluminum cap mkd. T19NR19W 1/4 S15 S22 1984. A mound of stone, 4 ft. base, 2 1/2 ft. high, is N. of the cor.</p> <p>Add the marks 2004 to the aluminum cap.</p> <hr/>
	<p>N. 89°55' W., beginning new measurement.</p>
14.47	<p>Point for a witness point on line bet. secs. 15 and 22.</p> <p>Set an aluminum drive rod, 32 ins. long, 3/4 in. diam., 26 ins. in the ground, with aluminum cap mkd.</p>



Dependent Resurvey of a Portion of the Subdivisional Lines,  
T. 19 N., R. 19 W., Gila and Salt River Meridian, Arizona

CHAINS	
26.85	<p style="text-align: center;">WP T 19 N R 19 W S 15</p> <hr style="width: 10%; margin: auto;"/> <p style="text-align: center;">S 22 WSWA</p> <p style="text-align: center;">2004</p> <p>Point for a witness point on line bet. secs. 15 and 22.</p> <p>Set an aluminum drive rod, 42 ins. long, 3/4 in. diam., 31 ins. in the ground in a collar of stone, with aluminum cap mkd.</p>
39.98	<p style="text-align: center;">WP T 19 N R 19 W S 15</p> <hr style="width: 10%; margin: auto;"/> <p style="text-align: center;">S 22 WSWA</p> <p style="text-align: center;">2004</p> <p>The cor. of secs. 15, 16, 21 and 22.</p>
17.41	<hr style="width: 80%; margin-left: 0;"/> <p>From the cor. of secs. 21, 22, 27 and 28.</p> <p>S. 89°56' W., bet. secs. 21 and 28.</p> <p>Over broken, rocky land, through creosote, yucca and scrub brush.</p> <p>Point for a witness point on line bet. secs. 21 and 28.</p> <p>Set an aluminum drive rod, 42 ins. long, 3/4 in. diam., 32 ins. in the ground, with aluminum cap mkd.</p>
	<p style="text-align: center;">WP T 19 N R 19 W S 21</p> <hr style="width: 10%; margin: auto;"/> <p style="text-align: center;">S 28 WSWA</p> <p style="text-align: center;">2004</p>

**Dependent Resurvey of a Portion of the Subdivisional Lines,  
T. 19 N., R. 19 W., Gila and Salt River Meridian, Arizona**

CHAINS	
40.56	<p>The 1/4 sec. cor. of secs. 21 and 28, monumented with a stainless steel post, 2 1/2 ins. diam., firmly set in a supporting mound of stone, 4 ft. base, 2 1/2 ft. high, with brass cap mkd. T19NR19W 1/4 S21 S28 1984.</p> <p>Add the marks 2004 to the brass cap.</p> <hr/> <p>S. 89°54' W., beginning new measurement.</p>
15.90	<p>Point for a witness point on line bet. secs. 21 and 28.</p> <p>Set an aluminum drive rod, 42 ins. long, 3/4 in. diam., 23 ins. in the ground to bedrock, in a supporting mound of stone, 3 ft. base, to top, with aluminum cap mkd.</p> <p align="center">           WP            T 19 N R 19 W            S 21  <hr/>           S 28            WSWA              2004         </p>
40.05	<p>The cor. of secs. 20, 21, 28 and 29, monumented with an iron post, 2 1/2 ins. diam., firmly set, projecting 3 ins. above a supporting mound of stone, 3 ft. base, 1 ft. high, with brass cap mkd. T19NR19W S20 S21 S29 S28 1984. A mound of stone, 3 ft. base, 1 1/2 ft. high and a steel fence post are W. of cor.</p> <p>Add the marks 2004 to the brass cap.</p> <hr/> <p>N. 0°03' E., bet. secs. 20 and 21.</p> <p>Over steep mountainous land, through creosote, yucca, ocotillo and scrub brush.</p>
23.77	<p>Point for AP 1, sec. 20, begin cherry stem for graded road, bears S. 82° W., hereinafter described.</p>
24.68	<p>Point for AP 18, sec. 20, end of cherry stem, hereinafter described.</p>
28.60	<p>Creek, 10 ft. wide, 6 ins. deep, drains S. 80° E.</p>

**Dependent Resurvey of a Portion of the Subdivisional Lines,  
T. 19 N., R. 19 W., Gila and Salt River Meridian, Arizona**


CHAINS	
40.01	<p>The 1/4 sec. cor. of secs. 20 and 21, monumented with an aluminum rock tablet, set in the original boulder, 3 X 2 X 1 1/2 ft., with 1/4 scribed on W. face, with top mkd. T19NR19W 1/4 S20 S21 1984. A steel fence post is NW. of cor. and a mound of stone, 4 ft. base, 2 ft. high, is W. of cor.</p>
	<p>Add the marks 2004 to the aluminum cap.</p> <hr/>
	<p>From the 1/4 sec. cor. of secs. 17 and 20, monumented with an aluminum rock tablet, set in the original boulder, 4 X 3 X 3 ft., with top mkd. T19NR19W 1/4 S17 S20 1984. A mound of stone, 2 ft. base, 1 ft. high and a steel fence post is N. of cor.</p>
	<p>Add the marks 2004 to the aluminum cap.</p>
	<p>from which</p>
	<p style="padding-left: 40px;">A rock outcropping, 15 X 6 X 4 ft., bears S. 26 1/2° W., 25.5 lks. dist., mkd. X BO (Record: S. 29° W.).</p>
	<p>S. 89°55' W., bet. secs. 17 and 20.</p>
	<p>Over steep mountainous rocky land, through scattered creosote, yucca, ocotillo and various cacti.</p>
39.85	<p>The cor. of secs. 17, 18, 19 and 20, monumented with an aluminum rock tablet, set in the original rock boulder, 3 X 3 X 1 ft., mkd. with 5 notches on the E. face, with top mkd. T19NR19W S18 S17 S19 S20 1984. A steel fence post is N. of cor.</p>
	<p>Add the marks 2004 to the aluminum cap.</p>
	<p>from which</p>
	<p style="padding-left: 40px;">A malapais boulder, 4 X 3 X 1 ft., bears S. 82 3/4° E., 20 lks. dist., mkd. X BO (Record S. 79° E., 21.5 lks. dist.).</p> <hr/>
	<p>N. 89°32' W., bet. secs. 18 and 19.</p>
	<p>Over mountainous broken land, through scattered ocotillo, yucca, and various cacti.</p>
39.97	<p>The true point for the 1/4 sec. cor. of secs. 18 and 19, falls on steep rock face and is impractical to monument.</p>

**Dependent Resurvey of a Portion of the Subdivisional Lines,  
T. 19 N., R. 19 W., Gila and Salt River Meridian, Arizona**

CHAINS	
	<p>From this true point, the witness cor. for the 1/4 sec. cor. of secs. 18 and 19, bears North, 9 lks. dist., monumented with an aluminum post, 1 in. diam., firmly set, projecting 10 ins. above the ground, with aluminum cap mkd. WC T19NR19W 1/4 S18 S19 1984 and an arrow pointing to the true point. A mound of stone, 3 ft. base, 2 ft. high, is N. of cor.</p> <p>Add the marks 2004 to the aluminum cap.</p> <hr/> <p>N. 89°32' W., beginning new measurement.</p>
13.705	<p>Point for a witness point on line bet. secs. 21 and 28.</p> <p>Set an aluminum drive rod, 42 ins. long, 3/4 in. diam., 40 ins. in the ground, with aluminum cap mkd.</p> <p style="text-align: center;">             WP              T 19 N R 19 W              S 18  <hr style="width: 10%; margin: auto;"/>             S 19              WSWA              2004         </p>
38.65	<p>The cor. of secs. 13, 18, 19 and 24, on the W. bdy. of the Tp., monumented with an aluminum post, 1 in. diam., firmly set, projecting 10 ins. above the ground, with aluminum cap mkd. T19N R20W R19W S13 S18 S24 S19 1984. A mound of stone, 4 ft. base, 2 ft. high, is W. of cor.</p> <p>Add the marks 2004 to the aluminum cap.</p> <hr/> <p style="text-align: center;"><b>Metes-and-Bounds Survey of the Warm Springs Wilderness Area Boundary, through secs. 20, 22, 23, 26 and 35, T. 19 N., R. 19 W., Gila and Salt River Meridian, Arizona</b></p> <hr/> <p style="text-align: center;">In section 26</p> <hr/> <p>From the point for AP 1, sec. 26, determined on the line bet. secs. 23 and 26, 30 ft. easterly of an old bladed road.</p> <p>Set an aluminum drive rod, 42 ins. long, 3/4 in. diam., 38 ins. in the ground, with aluminum cap mkd.</p>

Metes-and-Bounds Survey of the Warm Springs  
Wilderness Area Boundary, through secs. 20, 22, 23, 26 and 35,  
T. 19 N., R. 19 W., Gila and Salt River Meridian, Arizona

CHAINS



From this cor. point, the 1/4 sec. cor. of secs. 23 and 26, bears N. 89°59' E., 34.60 chs. dist., hereinbefore described.


Cor. is located 30 ft. easterly of a bladed road.

S. 31°28' E., on line 1-2, sec. 26, along the Warm Springs Wilderness Area Bdy.

Over level rocky land, through scattered creosote, yucca and scrub brush.

2.66 Point for AP 2, sec. 26.

Set an aluminum drive rod, 30 ins. long, 3/4 in. diam., 23 ins. in the ground, with aluminum cap mkd.



Cor. is located 30 ft. easterly of a bladed road.

S. 41°57' E., on line 2-3, sec. 26.

Over level rocky land, through scattered creosote, yucca and scrub brush.


3.59 Point for AP 3, sec. 26.

Set an aluminum drive rod, 42 ins. long, 3/4 in. diam., 34 ins. in the ground, with aluminum cap mkd.

**Metes-and-Bounds Survey of the Warm Springs  
Wilderness Area Boundary, through secs. 20, 22, 23, 26 and 35,  
T. 19 N., R. 19 W., Gila and Salt River Meridian, Arizona**

CHAINS

T 19 N R 19 W



Cor. is located 30 ft. easterly of a bladed road.

---


S. 35°14' E., on line 3-4, sec. 26.

Over level rocky land, through scattered creosote, yucca and scrub brush.

6.07 Point for AP 4, sec. 26.

Set an aluminum drive rod, 28 ins. long, 3/4 in. diam., 21 ins. in the ground, with aluminum cap mkd.

T 19 N R 19 W



Cor. is located 30 ft. easterly of a bladed road.

---


S. 43°12' E., on line 4-5, sec. 26.

Over level rocky land, through scattered creosote, yucca and scrub brush.

8.61 Point for AP 5, sec. 26.



Set an aluminum drive rod, 29 ins. long, 3/4 in. diam., 23 ins. in the ground, with aluminum cap mkd.

T 19 N R 19 W



Cor. is located 30 ft. easterly of a bladed road.

**Metes-and-Bounds Survey of the Warm Springs  
Wilderness Area Boundary, through secs. 20, 22, 23, 26 and 35,  
T. 19 N., R. 19 W., Gila and Salt River Meridian, Arizona**

CHAINS	
11.80	<hr/> <p>S. 38°13' E., on line 5-6, sec. 26.</p> <p>Over level rocky land, through scattered creosote, yucca and scrub brush.</p> <p>Point for AP 6, sec. 26.</p> <p>Set an aluminum drive rod, 24 ins. long, 3/4 in. diam., 18 ins. in the ground, with aluminum cap mkd.</p> <div style="text-align: center;"> <p>T 19 N R 19 W</p>  </div> <p>Cor. is located 30 ft. easterly of a bladed road.</p> <hr/>
2.73	<p>S. 37°56' E., on line 6-7, sec. 26.</p> <p>Over level rocky land, through scattered creosote, yucca and scrub brush.</p> <p>Point for AP 7, sec. 26.</p> <p>Set an aluminum drive rod, 42 ins. long, 3/4 in. diam., 35 ins. in the ground, with aluminum cap mkd.</p> <div style="text-align: center;"> <p>T 19 N R 19 W</p>  </div> <p>Cor. is located 30 ft. easterly of a bladed road.</p> <hr/>
	<p>S. 16°26' E., on line 7-8, sec. 26.</p> <p>Over level rocky land, through scattered creosote, yucca and scrub brush.</p>

**Metes-and-Bounds Survey of the Warm Springs  
Wilderness Area Boundary, through secs. 20, 22, 23, 26 and 35,  
T. 19 N., R. 19 W., Gila and Salt River Meridian, Arizona**

CHAINS	
3.56	<p>Point for AP 8, sec. 26.</p> <p>Set an aluminum drive rod, 32 ins. long, 3/4 in. diam., 26 ins. in the ground, with aluminum cap mkd.</p> <div data-bbox="803 499 1031 703" style="text-align: center;"> <p>T 19 N R 19 W</p> <p>S 26 WSWA AP8</p> <p>2004</p> </div> <p>Cor. is located 30 ft. easterly of a bladed road.</p> <hr style="width: 20%; margin: 10px auto;"/> <p>S. 59°42' E., on line 8-9, sec. 26.</p> <p>Over level rocky land, through scattered creosote, yucca and scrub brush.</p>
6.75	<p>Point for AP 9, sec. 26.</p> <p>Set an aluminum drive rod, 42 ins. long, 3/4 in. diam., 38 ins. in the ground, with aluminum cap mkd.</p> <div data-bbox="803 1186 1031 1396" style="text-align: center;"> <p>T 19 N R 19 W</p> <p>S 26 WSWA AP9</p> <p>2004</p> </div> <p>Cor. is located 30 ft. easterly of a bladed road.</p> <hr style="width: 20%; margin: 10px auto;"/> <p>S. 44°59' E., on line 9-10, sec. 26.</p> <p>Over level rocky land, through scattered creosote, yucca and scrub brush.</p>
5.40	<p>Point for AP 10, sec. 26.</p> <p>Set an aluminum drive rod, 42 ins. long, 3/4 in. diam., 34 ins. in the ground, with aluminum cap mkd.</p>





Metes-and-Bounds Survey of the Warm Springs  
Wilderness Area Boundary, through secs. 20, 22, 23, 26 and 35,  
T. 19 N., R. 19 W., Gila and Salt River Meridian, Arizona

CHAINS	
	<div data-bbox="803 317 1031 527" data-label="Diagram"> <p>T 19 N R 19 W</p> <p>WSWA S 26 AP10</p> <p>2004</p> </div> <p data-bbox="396 556 1170 590">Cor. is located 30 ft. easterly of a bladed road.</p> <hr data-bbox="651 640 1175 651"/> <p data-bbox="396 676 980 709">S. 18°21' E., on line 10-11, sec. 26.</p> <p data-bbox="396 737 1425 793">Over level rocky land, through scattered creosote, yucca and scrub brush.</p> <p data-bbox="245 827 789 856">12.92 Point for AP 11, sec. 26.</p> <p data-bbox="396 888 1419 947">Set an aluminum drive rod, 42 ins. long, 3/4 in. diam., 35 ins. in the ground, with aluminum cap mkd.</p>
	<div data-bbox="792 1012 1019 1222" data-label="Diagram"> <p>T 19 N R 19 W</p> <p>WSWA S 26 AP11</p> <p>2004</p> </div> <p data-bbox="386 1247 1166 1281">Cor. is located 30 ft. easterly of a bladed road.</p> <hr data-bbox="643 1331 1170 1341"/> <p data-bbox="386 1365 974 1398">S. 12°05' E., on line 11-12, sec. 26.</p> <p data-bbox="386 1428 1419 1484">Over level rocky land, through scattered creosote, yucca and scrub brush.</p> <p data-bbox="253 1516 781 1545">7.46 Point for AP 12, sec. 26.</p> <p data-bbox="386 1577 1414 1635">Set an aluminum drive rod, 36 ins. long, 3/4 in. diam., 27 ins. in the ground, with aluminum cap mkd.</p>
	<div data-bbox="784 1701 1011 1911" data-label="Diagram"> <p>T 19 N R 19 W</p> <p>WSWA S 26 AP12</p> <p>2004</p> </div>

**Metes-and-Bounds Survey of the Warm Springs  
Wilderness Area Boundary, through secs. 20, 22, 23, 26 and 35,  
T. 19 N., R. 19 W., Gila and Salt River Meridian, Arizona**

CHAINS	
6.99	<p>Cor. is located 30 ft. easterly of a bladed road.</p> <hr style="width: 20%; margin: auto;"/> <p>S. 20°58' E., on line 12-13, sec. 26.</p> <p>Over level rocky land, through scattered creosote, yucca and scrub brush.</p> <p>Point for AP 13, sec. 26.</p> <p>Set an aluminum drive rod, 42 ins. long, 3/4 in. diam., 35 ins. in the ground, with aluminum cap mkd.</p> <div style="text-align: center; margin: 10px 0;"> <p>T 19 N R 19 W</p> <p>WSWA S 26 AP13 2004</p> </div> <p>Cor. is located 30 ft. easterly of a bladed road.</p> <hr style="width: 20%; margin: auto;"/> <p>S. 6°43' E., on line 13-14, sec. 26.</p> <p>Over level rocky land, through scattered creosote, yucca and scrub brush.</p> <p>Point for AP 14, sec. 26.</p> <p>Set an aluminum drive rod, 42 ins. long, 3/4 in. diam., 36 ins. in the ground, with aluminum cap mkd.</p> <div style="text-align: center; margin: 10px 0;"> <p>T 19 N R 19 W</p> <p>WSWA S 26 AP14 2004</p> </div> <p>Cor. is located 30 ft. easterly of a bladed road.</p> <hr style="width: 20%; margin: auto;"/> <p>S. 55°52' E., on line 14-15, sec. 26.</p> <p>Over level rocky land, through scattered creosote, yucca and scrub brush.</p>


**Metes-and-Bounds Survey of the Warm Springs  
Wilderness Area Boundary, through secs. 20, 22, 23, 26 and 35,  
T. 19 N., R. 19 W., Gila and Salt River Meridian, Arizona**

CHAINS	
0.95	<p>Point for AP 15, sec. 26.</p> <p>Set an aluminum drive rod, 42 ins. long, 3/4 in. diam., 33 ins. in the ground, with aluminum cap mkd.</p> <div style="text-align: center;"> <p>T 19 N R 19 W</p>  </div> <p>From this cor. point, the NE cor. of an old corral, bears S. 14°01' W., 1.17 chs. dist.</p> <p>Cor. is located 30 ft. easterly of a bladed road.</p> <hr style="width: 20%; margin: 10px auto;"/> <p>S. 15°57' E., on line 15-16, sec. 26.</p> <p>Over level rocky land, through scattered creosote, yucca and scrub brush.</p>
6.60	<p>Point for AP 16, sec. 26</p> <p>Set an aluminum drive rod, 42 ins. long, 3/4 in. diam., 33 ins. in the ground, with aluminum cap mkd.</p> <div style="text-align: center;"> <p>T 19 N R 19 W</p>  </div> <p>From this cor. point, the SE cor. of an old corral, bears N. 61°40' W., 53 lks. dist.</p> <p>Cor. is located 30 ft. easterly of a bladed road.</p> <hr style="width: 20%; margin: 10px auto;"/> <p>S. 49°03' W., on line 16-17, sec. 26.</p> <p>Over level rocky land, through scattered creosote, yucca and scrub brush.</p>
2.16	<p>Point for AP 17, sec. 26, identical with AP 1, sec. 35, on the line bet. secs. 26 and 35.</p>

**Metes-and-Bounds Survey of the Warm Springs  
Wilderness Area Boundary, through secs. 20, 22, 23, 26 and 35,  
T. 19 N., R. 19 W., Gila and Salt River Meridian, Arizona**

CHAINS

Set an aluminum drive rod, 42 ins. long, 3/4 in. diam., 33 ins. in the ground, with aluminum cap mkd.



2004


From this cor. point, the cor. of secs. 25, 26, 35 and 36, bears S. 89°57' E., 31.80 chs. dist., hereinbefore described.

Cor. is located 30 ft. easterly of a bladed road.

---

From the point for AP 18, sec. 26, identical with AP 32, sec. 35, on the line bet. secs. 26 and 35.

Set an aluminum drive rod, 42 ins. long, 3/4 in. diam., 33 ins. in the ground, with aluminum cap mkd.



2004

From this cor. point, the 1/4 sec. cor. of secs. 26 and 35, bears N. 89°57' W., 5.13 chs. dist., hereinbefore described.

From this same cor. point, the SW cor. of an old corral, bears N. 64°54' E., 1.56 chs. dist.

Cor. is located 30 ft. westerly of a bladed road.

---

N. 7°28' E., on line 18-19, sec. 26.




**Metes-and-Bounds Survey of the Warm Springs  
Wilderness Area Boundary, through secs. 20, 22, 23, 26 and 35,  
T. 19 N., R. 19 W., Gila and Salt River Meridian, Arizona**

CHAINS	
4.07	<p>Over level rocky land, through scattered creosote, yucca and scrub brush.</p> <p>Point for AP 19, sec. 26.</p> <p>Set an aluminum drive rod, 42 ins. long, 3/4 in. diam., 30 ins. in the ground, with aluminum cap mkd.</p>
	<p style="text-align: center;">T 19 N    R 19 W</p> <p style="text-align: center;">WSWA AP19    }    S 26</p> <p style="text-align: center;">2004</p>
	<p>Cor. is located 30 ft. westerly of a bladed road.</p> <hr style="width: 20%; margin: 10px auto;"/>
	<p>N. 10°13' W., on line 19-20, sec. 26.</p>
2.85	<p>Over level rocky land, through scattered creosote, yucca and scrub brush.</p> <p>Point for AP 20, sec. 26.</p> <p>Set an aluminum drive rod, 42 ins. long, 3/4 in. diam., 12 ins. in the ground to bedrock, in a supporting mound of stone, 3 ft. base, to top, with aluminum cap mkd.</p>
	<p style="text-align: center;">T 19 N    R 19 W</p> <p style="text-align: center;">WSWA AP20    }    S 26</p> <p style="text-align: center;">2004</p>
	<p>From this cor. point, the NW cor. of an old corral, bears S. 72°45' E., 1.07 chs. dist.</p>
	<p>Cor. is located 30 ft. westerly of a bladed road.</p> <hr style="width: 20%; margin: 10px auto;"/>
	<p>N. 29°33' E., on line 20-21, sec. 26.</p>
1.76	<p>Over level rocky land, through scattered creosote, yucca and scrub brush.</p> <p>Point for AP 21, sec. 26.</p>

**Metes-and-Bounds Survey of the Warm Springs  
Wilderness Area Boundary, through secs. 20, 22, 23, 26 and 35,  
T. 19 N., R. 19 W., Gila and Salt River Meridian, Arizona**

CHAINS	
	<p>Set an aluminum drive rod, 42 ins. long, 3/4 in. diam., 38 ins. in the ground, with aluminum cap mkd.</p> <div data-bbox="797 468 1024 674" style="text-align: center;"> <p>T 19 N R 19 W</p> <p>WSWA AP21 } S 26</p> <p>2004</p> </div> <p>Cor. is located 30 ft. westerly of a bladed road.</p> <hr style="width: 20%; margin: 10px auto;"/> <p>N. 6°08' W., on line 21-22, sec. 26.</p> <p>Over level rocky land, through scattered creosote, yucca and scrub brush.</p>
7.26	<p>Point for AP 22, sec. 26.</p> <p>Set an aluminum drive rod, 42 ins. long, 3/4 in. diam., 30 ins. in the ground, with aluminum cap mkd.</p> <div data-bbox="797 1157 1024 1362" style="text-align: center;"> <p>T 19 N R 19 W</p> <p>WSWA AP22 } S 26</p> <p>2004</p> </div> <p>Cor. is located 30 ft. westerly of a bladed road.</p> <hr style="width: 20%; margin: 10px auto;"/> <p>N. 20°14' W., on line 22-23, sec. 26.</p> <p>Over level rocky land, through scattered creosote, yucca and scrub brush.</p>
7.00	<p>Point for AP 23, sec. 26.</p> <p>Set an aluminum drive rod, 42 ins. long, 3/4 in. diam., 35 ins. in the ground, with aluminum cap mkd.</p>

**Metes-and-Bounds Survey of the Warm Springs  
Wilderness Area Boundary, through secs. 20, 22, 23, 26 and 35,  
T. 19 N., R. 19 W., Gila and Salt River Meridian, Arizona**



CHAINS	
	<p style="text-align: center;">T 19 N R 19 W</p>  <p style="text-align: center;">WSWA AP23 S 26 2004</p>
7.59	<p>Cor. is located 30 ft. westerly of a bladed road.</p> <hr style="width: 20%; margin: 10px auto;"/> <p>N. 11°55' W., on line 23-24, sec. 26.</p> <p>Over level rocky land, through scattered creosote, yucca and scrub brush.</p> <p>Point for AP 24, sec. 26.</p> <p>Set an aluminum drive rod, 42 ins. long, 3/4 in. diam., 36 ins. in the ground, with aluminum cap mkd.</p>
12.49	<p style="text-align: center;">T 19 N R 19 W</p>  <p style="text-align: center;">WSWA AP24 S 26 2004</p> <p>Cor. is located 30 ft. westerly of a bladed road.</p> <hr style="width: 20%; margin: 10px auto;"/> <p>N. 19°06' W., on line 24-25, sec. 26.</p> <p>Over level rocky land, through scattered creosote, yucca and scrub brush.</p> <p>Point for AP 25, sec. 26.</p> <p>Set an aluminum drive rod, 42 ins. long, 3/4 in. diam., 34 ins. in the ground, with aluminum cap mkd.</p>
	<p style="text-align: center;">T 19 N R 19 W</p>  <p style="text-align: center;">AP25 WSWA S 26 2004</p>

**Metes-and-Bounds Survey of the Warm Springs  
Wilderness Area Boundary, through secs. 20, 22, 23, 26 and 35,  
T. 19 N., R. 19 W., Gila and Salt River Meridian, Arizona**



CHAINS	
<p>4.89</p>	<p>Cor. is located 30 ft. westerly of a bladed road.</p> <hr/> <p>N. 42°36' W., on line 25-26, sec. 26.</p> <p>Over level rocky land, through scattered creosote, yucca and scrub brush.</p> <p>Point for AP 26, sec. 26.</p> <p>Set an aluminum drive rod, 42 ins. long, 3/4 in. diam., 35 ins. in the ground, with aluminum cap mkd.</p> <div data-bbox="787 766 1023 976" style="text-align: center;"> <p>T 19 N R 19 W</p> <p>AP26 WSWA</p> <p>S 26</p> <p>2004</p> </div> <p>Cor. is located 30 ft. westerly of a bladed road.</p> <hr/>
<p>7.29</p>	<p>N. 65°29' W., on line 26-27, sec. 26.</p> <p>Over level rocky land, through scattered creosote, yucca and scrub brush.</p> <p>Point for AP 27, sec. 26.</p> <p>Set an aluminum drive rod, 42 ins. long, 3/4 in. diam., 38 ins. in the ground, with aluminum cap mkd.</p> <div data-bbox="787 1459 1023 1669" style="text-align: center;"> <p>T 19 N R 19 W</p> <p>WSWA AP27</p> <p>S 26</p> <p>2004</p> </div> <p>Cor. is located 30 ft. westerly of a bladed road.</p> <hr/> <p>N. 11°41' W., on line 27-28, sec. 26.</p> <p>Over level rocky land, through scattered creosote, yucca and scrub brush.</p>



**Metes-and-Bounds Survey of the Warm Springs  
Wilderness Area Boundary, through secs. 20, 22, 23, 26 and 35,  
T. 19 N., R. 19 W., Gila and Salt River Meridian, Arizona**

CHAINS	
3.96	<p>Point for AP 28, sec. 26.</p> <p>Set an aluminum drive rod, 42 ins. long, 3/4 in. diam., 38 ins. in the ground, with aluminum cap mkd.</p> <div style="text-align: center;"> <p>T 19 N R 19 W</p>  </div> <p>Cor. is located 30 ft. westerly of a bladed road.</p> <hr style="width: 20%; margin: 10px auto;"/> <p>N. 37°18' W., on line 28-29, sec. 26.</p> <p>Over level rocky land, through scattered creosote, yucca and scrub brush.</p>
2.69	<p>Point for AP 29, sec. 26.</p> <p>Set an aluminum drive rod, 42 ins. long, 3/4 in. diam., 35 ins. in the ground, with aluminum cap mkd.</p> <div style="text-align: center;"> <p>T 19 N R 19 W</p>  </div> <p>Cor. is located 30 ft. westerly of a bladed road.</p> <hr style="width: 20%; margin: 10px auto;"/> <p>N. 37°21' W., on line 29-30, sec. 26.</p> <p>Over level rocky land, through scattered creosote, yucca and scrub brush.</p>
11.78	<p>Point for AP 30, sec. 26.</p> <p>Set an aluminum drive rod, 31 ins. long, 3/4 in. diam., 25 ins. in the ground, with aluminum cap mkd.</p>

Metes-and-Bounds Survey of the Warm Springs  
Wilderness Area Boundary, through secs. 20, 22, 23, 26 and 35,  
T. 19 N., R. 19 W., Gila and Salt River Meridian, Arizona

CHAINS	
	<p style="text-align: center;">T 19 N R 19 W</p>  <p style="text-align: center;">2004</p> <p>Cor. is located 30 ft. westerly of a bladed road.</p> <hr style="width: 30%; margin: 10px auto;"/> <p>N. 43°22' W., on line 30-31, sec. 26.</p> <p>Over level rocky land, through scattered creosote, yucca and scrub brush.</p> <p>8.72 Point for AP 31, sec. 26.</p> <p>Set an aluminum drive rod, 42 ins. long, 3/4 in. diam., 24 ins. in the ground to bedrock in a supporting mound of stone, 3 ft. base, to top, with aluminum cap mkd.</p>
	<p style="text-align: center;">T 19 N R 19 W</p>  <p style="text-align: center;">2004</p> <p>Cor. is located 30 ft. westerly of a bladed road.</p> <hr style="width: 30%; margin: 10px auto;"/> <p>N. 35°35' W., on line 31-32, sec. 26.</p> <p>Over level rocky land, through scattered creosote, yucca and scrub brush.</p> <p>6.27 Point for AP 32, sec. 26.</p> <p>Set an aluminum drive rod, 42 ins. long, 3/4 in. diam., 12 ins. in the ground to bedrock, in a supporting mound of stone, 4 ft. base, to top, with aluminum cap mkd.</p>

Metes-and-Bounds Survey of the Warm Springs  
Wilderness Area Boundary, through secs. 20, 22, 23, 26 and 35,  
T. 19 N., R. 19 W., Gila and Salt River Meridian, Arizona

CHAINS

T 19 N R 19 W

WSWA  
AP32 S 26

2004

Cor. is located 30 ft. westerly of a bladed road.

---

N. 39°48' W., on line 32-33, sec. 26.

Over level rocky land, through scattered creosote, yucca and scrub brush.

3.40 Point for AP 33, sec. 26.

Set an aluminum drive rod, 23 ins. long, 3/4 in. diam., 15 ins. in the ground, with aluminum cap mkd.

T 19 N R 19 W

WSWA  
AP33 S 26

2004

Cor. is located 30 ft. westerly of a bladed road.

---

N. 33°04' W., on line 33-34, sec. 26.

Over level rocky land, through scattered creosote, yucca and scrub brush.

3.25 Point for AP 34, sec. 26, identical with AP 1, sec. 23, on the line bet. secs. 23 and 26.

Set an aluminum drive rod, 42 ins. long, 3/4 in. diam., 37 ins. in the ground, with aluminum cap mkd.

T 19 N R 19 W

W  
S AP1 S 23  
W  
A AP34 S 26

2004

**Metes-and-Bounds Survey of the Warm Springs  
Wilderness Area Boundary, through secs. 20, 22, 23, 26 and 35,  
T. 19 N., R. 19 W., Gila and Salt River Meridian, Arizona**

CHAINS	
	<p>From this cor. point, the true point for the cor. of secs. 22, 23, 26 and 27, bears S. 89°59' W., 4.21 chs. dist., hereinbefore described.</p>
	<p>Cor. is located 30 ft. westerly of a bladed road.</p>
	<p style="text-align: center;">In section 35</p>
	<p>From AP 17, sec. 26, identical with AP 1, sec. 35, hereinbefore described.</p>
	<p>S. 25°45' E., on line 1-2, sec. 35, along the Warm Springs Wilderness Area Bdy.</p>
	<p>Over level rocky land, through scattered creosote, yucca and scrub brush.</p>
<p>11.14</p>	<p>Point for AP 2, sec. 35.</p>
	<p>Set an aluminum drive rod, 42 ins. long, 3/4 in. diam., 39 ins. in the ground, with aluminum cap mkd.</p>
	<div style="text-align: center;"> <p>T 19 N R 19 W</p> </div>
	<p>Cor. is located 30 ft. easterly of a bladed road.</p>
	<p>S. 7°34' E., on line 2-3, sec. 35.</p>
	<p>Over level rocky land, through scattered creosote, yucca and scrub brush.</p>
<p>6.36</p>	<p>Point for AP 3, sec. 35.</p>
	<p>Set an aluminum drive rod, 42 ins. long, 3/4 in. diam., 36 ins. in the ground, with aluminum cap mkd.</p>

**Metes-and-Bounds Survey of the Warm Springs  
Wilderness Area Boundary, through secs. 20, 22, 23, 26 and 35,  
T. 19 N., R. 19 W., Gila and Salt River Meridian, Arizona**

CHAINS	
<p>8.34</p>	<div data-bbox="795 321 1024 527" data-label="Diagram"> <p>T 19 N R 19 W</p> <p>S 35 AP3 WSWA</p> <p>2004</p> </div> <p>Cor. is located 30 ft. easterly of a bladed road.</p> <hr/> <p>S. 13°10' E., on line 3-4, sec. 35.</p> <p>Over level rocky land, through scattered creosote, yucca and scrub brush.</p> <p>Point for AP 4, sec. 35.</p> <p>Set an aluminum drive rod, 42 ins. long, 3/4 in. diam., 33 ins. in the ground, with aluminum cap mkd.</p>
<p>6.03</p>	<div data-bbox="787 1012 1016 1218" data-label="Diagram"> <p>T 19 N R 19 W</p> <p>S 35 AP4 WSWA</p> <p>2004</p> </div> <p>Cor. is located 30 ft. easterly of a bladed road.</p> <hr/> <p>S. 1°34' W., on line 4-5, sec. 35.</p> <p>Over level rocky land, through scattered creosote, yucca and scrub brush.</p> <p>Point for AP 5, sec. 35.</p> <p>Set an aluminum drive rod, 42 ins. long, 3/4 in. diam., 37 ins. in the ground, with aluminum cap mkd.</p>
	<div data-bbox="779 1701 1013 1906" data-label="Diagram"> <p>T 19 N R 19 W</p> <p>S 35 AP5 WSWA</p> <p>2004</p> </div>

**Metes-and-Bounds Survey of the Warm Springs  
Wilderness Area Boundary, through secs. 20, 22, 23, 26 and 35,  
T. 19 N., R. 19 W., Gila and Salt River Meridian, Arizona**

CHAINS

Cor. is located 30 ft. easterly of a bladed road.


---

S. 21°27' E., on line 5-6, sec. 35.

Over level rocky land, through scattered creosote, yucca and scrub brush.

5.61 Point for AP 6, sec. 35.

Set an aluminum drive rod, 34 ins. long, 3/4 in. diam., 28 ins. in the ground, with aluminum cap mkd.



Cor. is located 30 ft. easterly of a bladed road.


---

S. 8°14' E., on line 6-7, sec. 35.

Over level rocky land, through scattered creosote, yucca and scrub brush.

7.52 Point for AP 7, sec. 35.

Set an aluminum drive rod, 42 ins. long, 3/4 in. diam., 37 ins. in the ground, with aluminum cap mkd.



Cor. is located 30 ft. easterly of a bladed road.

---

S. 17°24' E., on line 7-8, sec. 35.


Over level rocky land, through scattered creosote, yucca and scrub brush.

**Metes-and-Bounds Survey of the Warm Springs  
Wilderness Area Boundary, through secs. 20, 22, 23, 26 and 35,  
T. 19 N., R. 19 W., Gila and Salt River Meridian, Arizona**

CHAINS	
5.78	<p>Point for AP 8, sec. 35.</p> <p>Set an aluminum drive rod, 29 ins. long, 3/4 in. diam., 23 ins. in the ground, with aluminum cap mkd.</p>
	<p style="text-align: center;">T 19 N R 19 W</p> <p style="text-align: center;">S 35 AP 8 WSWA</p> <p style="text-align: center;">2004</p>
	<p>Cor. is located 30 ft. easterly of a bladed road.</p> <hr style="width: 20%; margin: 10px auto;"/>
	<p>S. 28°49' W., on line 8-9, sec. 35.</p>
	<p>Over level rocky land, through scattered creosote, yucca and scrub brush.</p>
3.09	<p>Point for AP 9, sec. 35.</p> <p>Set an aluminum drive rod, 42 ins. long, 3/4 in. diam., 30 ins. in the ground, with aluminum cap mkd.</p>
	<p style="text-align: center;">T 19 N R 19 W</p> <p style="text-align: center;">S 35 AP 9 WSWA</p> <p style="text-align: center;">2004</p>
	<p>Cor. is located 30 ft. easterly of a bladed road.</p> <hr style="width: 20%; margin: 10px auto;"/>
	<p>S. 18°48' W., on line 9-10, sec. 35.</p>
	<p>Over level rocky land, through scattered creosote, yucca and scrub brush.</p>
7.03	<p>Point for AP 10, sec. 35.</p> <p>Set an aluminum drive rod, 42 ins. long, 3/4 in. diam., 34 ins. in the ground, with aluminum cap mkd.</p>

Metes-and-Bounds Survey of the Warm Springs  
Wilderness Area Boundary, through secs. 20, 22, 23, 26 and 35,  
T. 19 N., R. 19 W., Gila and Salt River Meridian, Arizona

CHAINS



Cor. is located 30 ft. easterly of a bladed road.


---

S.  $5^{\circ}17'$  W., on line 10-11, sec. 35.

Over level rocky land, through scattered creosote, yucca and scrub brush.

3.79 Point for AP 11, sec. 35.

Set an aluminum drive rod, 42 ins. long,  $3/4$  in. diam., 38 ins. in the ground, with aluminum cap mkd.



Cor. is located 30 ft. easterly of a bladed road.


---

S.  $10^{\circ}06'$  W., on line 11-12, sec. 35.

Over level rocky land, through scattered creosote, yucca and scrub brush.

4.77 Point for AP 12, sec. 35.

Set an aluminum drive rod, 42 ins. long,  $3/4$  in. diam., 36 ins. in the ground, with aluminum cap mkd.





**Metes-and-Bounds Survey of the Warm Springs  
Wilderness Area Boundary, through secs. 20, 22, 23, 26 and 35,  
T. 19 N., R. 19 W., Gila and Salt River Meridian, Arizona**

CHAINS	
6.93	<p>Cor. is located 30 ft. easterly of a bladed road.</p> <hr/> <p>S. 8°56' W., on line 12-13, sec. 35.</p> <p>Over level rocky land, through scattered creosote, yucca and scrub brush.</p> <p>Point for AP 13, sec. 35.</p> <p>Set an aluminum drive rod, 42 ins. long, 3/4 in. diam., 38 ins. in the ground, with aluminum cap mkd.</p> <div data-bbox="792 772 1019 982" style="text-align: center;"> <p>T 19 N R 19 W</p> </div>
3.16	<p>Cor. is located 30 ft. easterly of a bladed road.</p> <hr/> <p>S. 30°13' E., on line 13-14, sec. 35.</p> <p>Over level rocky land, through scattered creosote, yucca and scrub brush.</p> <p>Point for AP 14, sec. 35.</p> <p>Set an aluminum drive rod, 34 ins. long, 3/4 in. diam., 27 ins. in the ground, with aluminum cap mkd.</p> <div data-bbox="792 1465 1019 1675" style="text-align: center;"> <p>T 19 N R 19 W</p> </div>
	<p>Cor. is located 30 ft. easterly of a bladed road.</p> <hr/> <p>S. 9°33' E., on line 14-15, sec. 35.</p> <p>Over level rocky land, through scattered creosote, yucca and scrub brush.</p>


**Metes-and-Bounds Survey of the Warm Springs  
Wilderness Area Boundary, through secs. 20, 22, 23, 26 and 35,  
T. 19 N., R. 19 W., Gila and Salt River Meridian, Arizona**

## CHAINS

4.01

Point for AP 15, sec. 35, at intersection with the S. bdy. of the Tp., bet. secs. 2 and 35.

Set an aluminum drive rod, 42 ins. long, 3/4 in. diam., 34 ins. in the ground, with aluminum cap mkd.



2004


From this cor. point, the cor. of secs. 1, 2, 35 and 36, bears S. 89°58' E., 23.31 chs. dist., hereinbefore described.

Cor. is located 30 ft. easterly of a bladed road.

---

From the point for AP 16, sec. 35, at intersection with the S. bdy. of the Tp., bet. secs. 2 and 35.

Set an aluminum drive rod, 42 ins. long, 3/4 in. diam., 34 ins. in the ground, with aluminum cap mkd.



2004

From this cor. point, the 1/4 sec. cor. of secs. 2 and 35, bears N. 89°58' W., 15.77 chs. dist., hereinbefore described.

Cor. is located 30 ft. westerly of a bladed road.

---

N. 10°26' W., on line 16-17, sec. 35.

**Metes-and-Bounds Survey of the Warm Springs  
Wilderness Area Boundary, through secs. 20, 22, 23, 26 and 35,  
T. 19 N., R. 19 W., Gila and Salt River Meridian, Arizona**

CHAINS	
3.70	<p>Over level rocky land, through scattered creosote, yucca and scrub brush.</p> <p>Point for AP 17, sec. 35.</p> <p>Set an aluminum drive rod, 42 ins. long, 3/4 in. diam., 38 ins. in the ground, with aluminum cap mkd.</p> <div style="text-align: center;"> <p>T 19 N R 19 W</p> <p>WSWA AP17      S 35</p> <p>2004</p> </div> <p>Cor. is located 30 ft. westerly of a bladed road.</p> <hr style="width: 20%; margin: 10px auto;"/> <p>N. 28°54' W., on line 17-18, sec. 35.</p> <p>Over level rocky land, through scattered creosote, yucca and scrub brush.</p>
3.45	<p>Point for AP 18, sec. 35.</p> <p>Set an aluminum drive rod, 42 ins. long, 3/4 in. diam., 38 ins. in the ground, with aluminum cap mkd.</p> <div style="text-align: center;"> <p>T 19 N R 19 W</p> <p>WSWA AP18      S 35</p> <p>2004</p> </div> <p>Cor. is located 30 ft. westerly of a bladed road.</p> <hr style="width: 20%; margin: 10px auto;"/> <p>N. 8°41' E., on line 18-19, sec. 35.</p> <p>Over level rocky land, through scattered creosote, yucca and scrub brush.</p>
6.89	<p>Point for AP 19, sec. 35.</p> <p>Set an aluminum drive rod, 42 ins. long, 3/4 in. diam., 37 ins. in the ground, with aluminum cap mkd.</p>

Metes-and-Bounds Survey of the Warm Springs  
Wilderness Area Boundary, through secs. 20, 22, 23, 26 and 35,  
T. 19 N., R. 19 W., Gila and Salt River Meridian, Arizona

CHAINS	
	<p style="text-align: center;">T 19 N R 19 W</p> <p style="text-align: center;">WSWA AP19 / S 35</p> <p style="text-align: center;">2004</p> <p>Cor. is located 30 ft. westerly of a bladed road.</p> <hr style="width: 20%; margin: 10px auto;"/> <p>N. 9°33' E., on line 19-20, sec. 35.</p> <p>Over level rocky land, through scattered creosote, yucca and scrub brush.</p>
<p>5.09</p>	<p>Point for AP 20, sec. 35.</p> <p>Set an aluminum drive rod, 42 ins. long, 3/4 in. diam., 37 ins. in the ground, with aluminum cap mkd.</p> <p style="text-align: center;">T 19 N R 19 W</p> <p style="text-align: center;">WSWA AP20 / S 35</p> <p style="text-align: center;">2004</p> <p>Cor. is located 30 ft. westerly of a bladed road.</p> <hr style="width: 20%; margin: 10px auto;"/> <p>N. 5°34' E., on line 20-21, sec. 35.</p> <p>Over level rocky land, through scattered creosote, yucca and scrub brush.</p>
<p>3.48</p>	<p>Point for AP 21, sec. 35.</p> <p>Set an aluminum drive rod, 42 ins. long, 3/4 in. diam., 33 ins. in the ground, with aluminum cap mkd.</p>

Metes-and-Bounds Survey of the Warm Springs  
Wilderness Area Boundary, through secs. 20, 22, 23, 26 and 35,  
T. 19 N., R. 19 W., Gila and Salt River Meridian, Arizona

CHAINS

T 19 N R 19 W

WSWA  
AP21 S 35

2004

Cor. is located 30 ft. westerly of a bladed road.

---

N. 18°18' E., on line 21-22, sec. 35.

Over level rocky land, through scattered creosote, yucca and scrub brush.

7.44 Point for AP 22, sec. 35.

Set an aluminum drive rod, 42 ins. long, 3/4 in. diam., 37 ins. in the ground, with aluminum cap mkd.

T 19 N R 19 W

WSWA  
AP22 S 35

2004

Cor. is located 30 ft. westerly of a bladed road.

---

N. 30°51' E., on line 22-23, sec. 35.

Over level rocky land, through scattered creosote, yucca and scrub brush.

2.83 Point for AP 23, sec. 35.

Set an aluminum drive rod, 32 ins. long, 3/4 in. diam., 25 ins. in the ground, with aluminum cap mkd.

T 19 N R 19 W

WSWA  
AP23 S 35

2004




**Metes-and-Bounds Survey of the Warm Springs  
Wilderness Area Boundary, through secs. 20, 22, 23, 26 and 35,  
T. 19 N., R. 19 W., Gila and Salt River Meridian, Arizona**

CHAINS	
5.41	<p>Cor. is located 30 ft. westerly of a bladed road.</p> <hr/> <p>N. 17°57' W., on line 23-24, sec. 35.</p> <p>Over level rocky land, through scattered creosote, yucca and scrub brush.</p> <p>Point for AP 24, sec. 35.</p> <p>Set an aluminum drive rod, 42 ins. long, 3/4 in. diam., 38 ins. in the ground, with aluminum cap mkd.</p>
	<p style="text-align: center;">T 19 N R 19 W</p> <div style="text-align: center;"> </div>
7.37	<p>Cor. is located 30 ft. westerly of a bladed road.</p> <hr/> <p>N. 9°03' W., on line 24-25, sec. 35.</p> <p>Over level rocky land, through scattered creosote, yucca and scrub brush.</p> <p>Point for AP 25, sec. 35.</p> <p>Set an aluminum drive rod, 33 ins. long, 3/4 in. diam., 27 ins. in the ground, with aluminum cap mkd.</p>
	<p style="text-align: center;">T 19 N R 19 W</p> <div style="text-align: center;"> </div>
	<p>Cor. is located 30 ft. westerly of a bladed road.</p> <hr/> <p>N. 19°33' W., on line 25-26, sec. 35.</p> <p>Over level rocky land, through scattered creosote, yucca and scrub brush.</p>

**Metes-and-Bounds Survey of the Warm Springs  
Wilderness Area Boundary, through secs. 20, 22, 23, 26 and 35,  
T. 19 N., R. 19 W., Gila and Salt River Meridian, Arizona**


CHAINS	
5.89	<p>Point for AP 26, sec. 35.</p> <p>Set an aluminum drive rod, 42 ins. long, 3/4 in. diam., 35 ins. in the ground, with aluminum cap mkd.</p> <div style="text-align: center;"> <p>T 19 N R 19 W</p> <p>WSWA AP26</p> <p style="margin-left: 100px;">S 35</p> <p style="margin-left: 100px;">2004</p> </div> <p>Cor. is located 30 ft. westerly of a bladed road.</p> <hr style="width: 20%; margin: 10px auto;"/> <p>N. 0°42' E., on line 26-27, sec. 35.</p> <p>Over level rocky land, through scattered creosote, yucca and scrub brush.</p>
5.58	<p>Point for AP 27, sec. 35.</p> <p>Set an aluminum drive rod, 42 ins. long, 3/4 in. diam., 37 ins. in the ground, with aluminum cap mkd.</p> <div style="text-align: center;"> <p>T 19 N R 19 W</p> <p>WSWA AP27</p> <p style="margin-left: 100px;">S 35</p> <p style="margin-left: 100px;">2004</p> </div> <p>Cor. is located 30 ft. westerly of a bladed road.</p> <hr style="width: 20%; margin: 10px auto;"/> <p>N. 12°08' W., on line 27-28, sec. 35.</p> <p>Over level rocky land, through scattered creosote, yucca and scrub brush.</p>
8.58	<p>Point for AP 28, sec. 35.</p> <p>Set an aluminum drive rod, 42 ins. long, 3/4 in. diam., 31 ins. in the ground, with aluminum cap mkd.</p>

Metes-and-Bounds Survey of the Warm Springs  
Wilderness Area Boundary, through secs. 20, 22, 23, 26 and 35,  
T. 19 N., R. 19 W., Gila and Salt River Meridian, Arizona

CHAINS	
	<div style="text-align: center;"> <p>T 19 N R 19 W</p>  </div> <p>Cor. is located 30 ft. westerly of a bladed road.</p> <hr style="width: 30%; margin: 10px auto;"/>
<p>6.73</p>	<p>N. 8°25' W., on line 28-29, sec. 35.</p> <p>Over level rocky land, through scattered creosote, yucca and scrub brush.</p> <p>Point for AP 29, sec. 35.</p> <p>Set an aluminum drive rod, 42 ins. long, 3/4 in. diam., 37 ins. in the ground, with aluminum cap mkd.</p>
	<div style="text-align: center;"> <p>T 19 N R 19 W</p>  </div> <p>Cor. is located 30 ft. westerly of a bladed road.</p> <hr style="width: 30%; margin: 10px auto;"/>
<p>10.14</p>	<p>N. 25°27' W., on line 29-30, sec. 35.</p> <p>Over level rocky land, through scattered creosote, yucca and scrub brush.</p> <p>Point for AP 30, sec. 35.</p> <p>Set an aluminum drive rod, 42 ins. long, 3/4 in. diam., 36 ins. in the ground, with aluminum cap mkd.</p>
	<div style="text-align: center;"> <p>T 19 N R 19 W</p>  </div>




**Metes-and-Bounds Survey of the Warm Springs  
Wilderness Area Boundary, through secs. 20, 22, 23, 26 and 35,  
T. 19 N., R. 19 W., Gila and Salt River Meridian, Arizona**

CHAINS	
1.62	<p>Cor. is located 30 ft. westerly of a bladed road.</p> <hr/> <p>N. 89°29' W., on line 30-31, sec. 35.</p> <p>Over level rocky land, through scattered creosote, yucca and scrub brush.</p> <p>Point for AP 31, sec. 35.</p> <p>Set an aluminum drive rod, 42 ins. long, 3/4 in. diam., 29 ins. in the ground, in a collar of stone, with aluminum cap mkd.</p> <div style="text-align: center;"> <p>T 19 N R 19 W</p>  </div> <p>Cor. is located 30 ft. westerly of a bladed road.</p> <hr/>
1.09	<p>N. 41°04' W., on line 31-32, sec. 35.</p> <p>Over level rocky land, through scattered creosote, yucca and scrub brush.</p> <p>AP 32, sec. 35, identical with AP 18, sec. 26, on the line bet. secs. 26 and 35, hereinbefore described.</p> <hr/>
7.04	<p style="text-align: center;">In section 23</p> <hr/> <p>From AP 1, sec. 23, identical with AP 34, sec. 26, on the line bet. secs. 23 and 26, hereinbefore described.</p> <p>N. 37°01' W., on line 1-2, sec. 23.</p> <p>Over level rocky land, through scattered creosote, yucca and scrub brush.</p> <p>Point for AP 2, sec. 23, identical with AP 1, sec. 22, on the line bet secs. 22 and 23.</p> <p>Set an aluminum drive rod, 24 ins. long, 3/4 in. diam., 18 ins. in the ground, with aluminum cap mkd.</p>

**Metes-and-Bounds Survey of the Warm Springs  
Wilderness Area Boundary, through secs. 20, 22, 23, 26 and 35,  
T. 19 N., R. 19 W., Gila and Salt River Meridian, Arizona**

CHAINS

T 19 N R 19 W



2004

From this cor. point, the true point for the cor. of secs. 22, 23, 26 and 27, bears S. 0°16' E., 5.62 chs. dist., hereinbefore described.

Cor. is located 30 ft. westerly of a bladed road.

In Section 22

From AP 1, sec. 22, identical with AP 2, sec. 23 on line bet secs. 22 and 23, hereinbefore described.


N. 20°46' W., on line 1-2, sec. 22.

Over level rocky land, through scattered creosote, yucca and scrub brush.

2.16 Point for AP 2, sec. 22.

Set an aluminum drive rod, 30 ins. long, 3/4 in. diam., 24 ins. in the ground, with aluminum cap mkd.

T 19 N R 19 W



2004

Cor. is located 30 ft. westerly of a bladed road.

N. 11°55' W., on line 2-3, sec. 22.


Over level rocky land, through scattered creosote, yucca and scrub brush.

9.61 Point for AP 3, sec. 22.

**Metes-and-Bounds Survey of the Warm Springs  
Wilderness Area Boundary, through secs. 20, 22, 23, 26 and 35,  
T. 19 N., R. 19 W., Gila and Salt River Meridian, Arizona**

CHAINS

Set an aluminum drive rod, 30 ins. long, 3/4 in. diam., 24 ins. in the ground, with aluminum cap mkd.



Cor. is located 30 ft. westerly of a bladed road.


---

N. 22°56' W., on line 3-4, sec. 22.

Over level rocky land, through scattered creosote, yucca and scrub brush.

7.21 Point for AP 4, sec. 22.

Set an aluminum drive rod, 26 ins. long, 3/4 in. diam., 18 ins. in the ground, with aluminum cap mkd.



Cor. is located 30 ft. westerly of a bladed road.

---

N. 40°45' W., on line 4-5, sec. 22.

Over level rocky land, through scattered creosote, yucca and scrub brush.

4.71 Point for AP 5, sec. 22.

Set an aluminum drive rod, 42 ins. long, 3/4 in. diam., 35 ins. in the ground, with aluminum cap mkd.

Metes-and-Bounds Survey of the Warm Springs  
Wilderness Area Boundary, through secs. 20, 22, 23, 26 and 35,  
T. 19 N., R. 19 W., Gila and Salt River Meridian, Arizona

CHAINS

T 19 N R 19 W



WSWA  
AP5 S 22

2004

Cor. is located 30 ft. westerly of a bladed road.

---


N.  $36^{\circ}57'$  W., on line 5-6, sec. 22.

Over level rocky land, through scattered creosote, yucca and scrub brush.

5.09 Point for AP 6, sec. 22.

Set an aluminum drive rod, 42 ins. long,  $3/4$  in. diam., 34 ins. in the ground, with aluminum cap mkd.

T 19 N R 19 W



WSWA  
AP6 S 22

2004

Cor. is located 30 ft. westerly of a bladed road.

---


N.  $24^{\circ}34'$  W., on line 6-7, sec. 22.

Over level rocky land, through scattered creosote, yucca and scrub brush.

6.74 Point for AP 7, sec. 22.

Set an aluminum drive rod, 27 ins. long,  $3/4$  in. diam., 20 ins. in the ground, with aluminum cap mkd.

T 19 N R 19 W



WSWA  
AP7 S 22

2004

**Metes-and-Bounds Survey of the Warm Springs  
Wilderness Area Boundary, through secs. 20, 22, 23, 26 and 35,  
T. 19 N., R. 19 W., Gila and Salt River Meridian, Arizona**

CHAINS	
10.62	<p>Cor. is located 30 ft. westerly of a bladed road.</p> <hr style="width: 20%; margin: 0 auto;"/> <p>N. 28°41' W., on line 7-8, sec. 22.</p> <p>Over level rocky land, through scattered creosote, yucca and scrub brush.</p> <p>Point for AP 8, sec. 22.</p> <p>Set an aluminum drive rod, 22 ins. long, 3/4 in. diam., 16 ins. in the ground, with aluminum cap mkd.</p> <div style="text-align: center; margin: 10px 0;"> <p>T 19 N R 19 W</p> <p>WSWA AP8    S 22</p> <p>2004</p> </div> <p>Cor. is located 30 ft. westerly of a bladed road.</p> <hr style="width: 20%; margin: 0 auto;"/> <p>N. 17°27' W., on line 8-9, sec. 22.</p> <p>Over level rocky land, through scattered creosote, yucca and scrub brush.</p> <p>Point for AP 9, sec. 22.</p> <p>Set an aluminum drive rod, 42 ins. long, 3/4 in. diam., 36 ins. in the ground, with aluminum cap mkd.</p> <div style="text-align: center; margin: 10px 0;"> <p>T 19 N R 19 W</p> <p>WSWA AP9    S 22</p> <p>2004</p> </div> <p>Cor. is located 30 ft. westerly of a bladed road.</p> <hr style="width: 20%; margin: 0 auto;"/> <p>N. 9°52' E., on line 9-10, sec. 22.</p> <p>Over level rocky land, through scattered creosote, yucca and scrub brush.</p>

**Metes-and-Bounds Survey of the Warm Springs  
Wilderness Area Boundary, through secs. 20, 22, 23, 26 and 35,  
T. 19 N., R. 19 W., Gila and Salt River Meridian, Arizona**

CHAINS	
4.15	<p>Point for AP 10, sec. 22.</p> <p>Set an aluminum drive rod, 24 ins. long, 3/4 in. diam., 20 ins. in the ground, with aluminum cap mkd.</p> <div style="text-align: center;"> <p>T 19 N R 19 W</p> <p>WSWA AP10 } S 22</p> <p>2004</p> </div> <p>Cor. is located 30 ft. westerly of a bladed road.</p> <hr style="width: 20%; margin: 10px auto;"/> <p>N. 12°06' W., on line 10-11, sec. 22.</p> <p>Over level rocky land, through scattered creosote, yucca and scrub brush.</p>
2.26	<p>Point for AP 11, sec. 22.</p> <p>Set an aluminum drive rod, 6 ins. long, 3/4 in. diam., 6 ins. in the ground, with aluminum cap mkd.</p> <div style="text-align: center;"> <p>T 19 N R 19 W</p> <p>WSWA AP11 } S 22</p> <p>2004</p> </div> <p>Cor. is located 30 ft. westerly of a bladed road.</p> <hr style="width: 20%; margin: 10px auto;"/> <p>N. 35°25' W., on line 11-12, sec. 22.</p> <p>Over level rocky land, through scattered creosote, yucca and scrub brush.</p>
9.37	<p>Point for AP 12, sec. 22.</p> <p>Set an aluminum drive rod, 42 ins. long, 3/4 in. diam., 15 ins. in the ground, to bedrock, in a supporting mound of stone, 3 ft. base, to top, with aluminum cap mkd.</p>

Metes-and-Bounds Survey of the Warm Springs  
Wilderness Area Boundary, through secs. 20, 22, 23, 26 and 35,  
T. 19 N., R. 19 W., Gila and Salt River Meridian, Arizona

CHAINS

T 19 N R 19 W

WSWA  
AP12 / S 22

2004

Cor. is located 30 ft. westerly of a bladed road.

---

N. 32°16' W., on line 12-13, sec. 22.

Over level rocky land, through scattered creosote, yucca and scrub brush.

8.12 Point for AP 13, sec. 22, at intersection with the line bet. secs. 15 and 22, hereinbefore described.

Set an aluminum drive rod, 24 ins. long, 3/4 in. diam., 18 ins. in the ground, with aluminum cap mkd.

T 19 N R 19 W

S 15  
AP13 / S 22  
WSWA

2004

From this cor. point, the 1/4 sec. cor. of secs. 15 and 22, bears N. 89°54' W., 7.13 chs. dist., hereinbefore described.

Cor. is located 30 ft. westerly of a bladed road.




---

In Section 20

From the point for AP1, sec. 20, bet. secs. 20 and 21, hereinbefore described.

Set an aluminum drive rod, 42 ins. long, 3/4 in. diam., 38 ins. in the ground, with aluminum cap mkd.

Metes-and-Bounds Survey of the Warm Springs  
Wilderness Area Boundary, through secs. 20, 22, 23, 26 and 35,  
T. 19 N., R. 19 W., Gila and Salt River Meridian, Arizona

CHAINS	
3.09	<p style="text-align: center;">T 19 N R 19 W</p> <div style="text-align: center;">  </div> <p style="text-align: center;">2004</p> <p>Cor. is located 30 ft. S. of a graded road.</p> <p>S. 81°48' W., on line 1-2, sec. 20.</p> <p>Over level rocky land, through scattered creosote, yucca and scrub brush.</p> <p>Point for AP 2, sec. 20.</p> <p>Set an aluminum drive rod, 42 ins. long, 3/4 in. diam., 38 ins. in the ground, with aluminum cap mkd.</p>
3.26	<p style="text-align: center;">T 19 N R 19 W</p> <div style="text-align: center;">  </div> <p style="text-align: center;">2004</p> <p>Cor. is located 30 ft. S. of a graded road.</p> <hr style="width: 20%; margin: 10px auto;"/> <p>S. 85°56' W., on line 2-3, sec. 20.</p> <p>Over level rocky land, through scattered creosote, yucca and scrub brush.</p> <p>Point for AP 3, sec. 20.</p> <p>Set an aluminum drive rod, 42 ins. long, 3/4 in. diam., 36 ins. in the ground, with aluminum cap mkd.</p>
	<p style="text-align: center;">T 19 N R 19 W</p> <div style="text-align: center;">  </div> <p style="text-align: center;">2004</p>



**Metes-and-Bounds Survey of the Warm Springs  
Wilderness Area Boundary, through secs. 20, 22, 23, 26 and 35,  
T. 19 N., R. 19 W., Gila and Salt River Meridian, Arizona**

CHAINS	
4.32	<p>Cor. is located 30 ft. S. of a graded road.</p> <hr style="width: 20%; margin: 0 auto;"/> <p>S. 64°07' W., on line 3-4, sec. 20.</p> <p>Over level rocky land, through scattered creosote, yucca and scrub brush.</p> <p>Point for AP 4, sec. 20.</p> <p>Set an aluminum drive rod, 42 ins. long, 3/4 in. diam., 30 ins. in the ground, with aluminum cap mkd.</p> <div style="text-align: center; margin: 20px 0;"> <p>T 19 N R 19 W</p> <p>S 20</p> <p>AP4</p> <p>WSWA</p> <p>2004</p> </div> <p>Cor. is located 30 ft. S. of a graded road.</p> <hr style="width: 20%; margin: 0 auto;"/> <p>N. 71°31' W., on line 4-5, sec. 20.</p> <p>Over level rocky land, through scattered creosote, yucca and scrub brush.</p> <p>Point for AP 5, sec. 20.</p> <p>Set an aluminum drive rod, 36 ins. long, 3/4 in. diam., 28 ins. in the ground, with aluminum cap mkd.</p> <div style="text-align: center; margin: 20px 0;"> <p>T 19 N R 19 W</p> <p>S 20</p> <p>AP5</p> <p>WSWA</p> <p>2004</p> </div> <p>Cor. is located 30 ft. S. of a graded road.</p> <hr style="width: 20%; margin: 0 auto;"/> <p>N. 85°27' W., on line 5-6, sec. 20.</p>

**Metes-and-Bounds Survey of the Warm Springs  
Wilderness Area Boundary, through secs. 20, 22, 23, 26 and 35,  
T. 19 N., R. 19 W., Gila and Salt River Meridian, Arizona**

CHAINS	
1.43	<p>Over level rocky land, through scattered creosote, yucca and scrub brush.</p> <p>Point for AP 6, sec. 20.</p> <p>Set an aluminum drive rod, 42 ins. long, 3/4 in. diam., 30 ins. in the ground, with aluminum cap mkd.</p> <p style="text-align: center;">T 19 N R 19 W</p> <p style="text-align: center;">S 20</p> <p style="text-align: center;">—————</p> <p style="text-align: center;">AP6 WSWA</p> <p style="text-align: center;">2004</p> <p>Cor. is located 30 ft. S. of a graded road.</p> <p style="text-align: center;">—————</p> <p>S. 84°24' W., on line 6-7, sec. 20.</p> <p>Over level rocky land, through scattered creosote, yucca and scrub brush.</p>
1.95	<p>Point for AP 7, sec. 20.</p> <p>Set an aluminum drive rod, 42 ins. long, 3/4 in. diam., 36 ins. in the ground, with aluminum cap mkd.</p> <p style="text-align: center;">T 19 N R 19 W</p> <p style="text-align: center;">S 20</p> <p style="text-align: center;">—————</p> <p style="text-align: center;">AP7 WSWA</p> <p style="text-align: center;">2004</p> <p>Cor. is located 30 ft. S. of a graded road.</p> <p style="text-align: center;">—————</p> <p>S. 43°47' W., on line 7-8, sec. 20.</p> <p>Over level rocky land, through scattered creosote, yucca and scrub brush.</p>
0.96	<p>Point for AP 8, sec. 20.</p>



**Metes-and-Bounds Survey of the Warm Springs  
Wilderness Area Boundary, through secs. 20, 22, 23, 26 and 35,  
T. 19 N., R. 19 W., Gila and Salt River Meridian, Arizona**

CHAINS	
	<p>Set an aluminum drive rod, 42 ins. long, 3/4 in. diam., 34 ins. in the ground, with aluminum cap mkd.</p> <p style="text-align: center;">T 19 N R 19 W</p> <p style="text-align: center;">S 20</p> <p style="text-align: center;">AP8 WSWA</p> <p style="text-align: center;">2004</p> <p>Cor. is located 30 ft. S. of a graded road.</p> <hr style="width: 20%; margin: 10px auto;"/> <p>S. 69°30' W., on line 8-9, sec. 20.</p> <p>Over level rocky land, through scattered creosote, yucca and scrub brush.</p>
0.98	<p>Point for AP 9, sec. 20.</p> <p>Set an aluminum drive rod, 42 ins. long, 3/4 in. diam., 35 ins. in the ground, with aluminum cap mkd.</p> <p style="text-align: center;">T 19 N R 19 W</p> <p style="text-align: center;">S 20</p> <p style="text-align: center;">AP9 WSWA</p> <p style="text-align: center;">2004</p> <p>Cor. is located 30 ft. S. of a graded road.</p> <hr style="width: 20%; margin: 10px auto;"/> <p>N. 0°13' E., on line 9-10, sec. 20.</p> <p>Over level rocky land, through scattered creosote, yucca and scrub brush.</p>
1.13	<p>Point for AP 10, sec. 20.</p> <p>Set an aluminum drive rod, 42 ins. long, 3/4 in. diam., 33 ins. in the ground, with aluminum cap mkd.</p>



Metes-and-Bounds Survey of the Warm Springs  
Wilderness Area Boundary, through secs. 20, 22, 23, 26 and 35,  
T. 19 N., R. 19 W., Gila and Salt River Meridian, Arizona

CHAINS	
	<div data-bbox="803 317 1031 556" data-label="Diagram"> </div> <p data-bbox="397 588 1079 619">Cor. is located 30 ft. W. of a graded road.</p> <hr data-bbox="657 667 1177 676"/> <p data-bbox="397 703 982 735">N. 37°12' E., on line 10-11, sec. 20.</p> <p data-bbox="397 766 1429 829">Over level rocky land, through scattered creosote, yucca and scrub brush.</p>
<p data-bbox="267 856 332 882">0.63</p>	<p data-bbox="397 856 787 888">Point for AP 11, sec. 20.</p> <p data-bbox="397 919 1421 982">Set an aluminum drive rod, 42 ins. long, 3/4 in. diam., 34 ins. in the ground, with aluminum cap mkd.</p> <div data-bbox="795 1039 1023 1270" data-label="Diagram"> </div> <p data-bbox="389 1302 1071 1333">Cor. is located 30 ft. NW of a graded road.</p> <hr data-bbox="649 1386 1169 1394"/> <p data-bbox="389 1423 974 1455">N. 75°48' E., on line 11-12, sec. 20.</p> <p data-bbox="389 1486 1421 1549">Over level rocky land, through scattered creosote, yucca and scrub brush.</p>
<p data-bbox="259 1575 324 1600">1.10</p>	<p data-bbox="389 1575 779 1606">Point for AP 12, sec. 20.</p> <p data-bbox="389 1638 1412 1701">Set an aluminum drive rod, 42 ins. long, 3/4 in. diam., 36 ins. in the ground, with aluminum cap mkd.</p>



**Metes-and-Bounds Survey of the Warm Springs  
Wilderness Area Boundary, through secs. 20, 22, 23, 26 and 35,  
T. 19 N., R. 19 W., Gila and Salt River Meridian, Arizona**

CHAINS	
	<p>T 19 N R 19 W</p> <p>WSWA AP12</p>  <p>S 20</p> <p>2004</p> <p>Cor. is located 30 ft. N. of a graded road.</p> <hr style="width: 20%; margin: 10px auto;"/>
1.96	<p>N. 82°11' E., on line 12-13, sec. 20.</p> <p>Over level rocky land, through scattered creosote, yucca and scrub brush.</p> <p>Point for AP 13, sec. 20.</p> <p>Set an aluminum drive rod, 35 ins. long, 3/4 in. diam., 28 ins. in the ground, with aluminum cap mkd.</p>
	<p>T 19 N R 19 W</p> <p>WSWA AP13</p>  <p>S 20</p> <p>2004</p> <p>Cor. is located 30 ft. N. of a graded road.</p> <hr style="width: 20%; margin: 10px auto;"/>
1.65	<p>S. 87°40' E., on line 13-14, sec. 20.</p> <p>Over level rocky land, through scattered creosote, yucca and scrub brush.</p> <p>Point for AP 14, sec. 20.</p> <p>Set an aluminum drive rod, 42 ins. long, 3/4 in. diam., 18 ins. in the ground to bedrock, in a supporting mound of stone, 3 ft. base, to top, with aluminum cap mkd.</p>

Metes-and-Bounds Survey of the Warm Springs  
 Wilderness Area Boundary, through secs. 20, 22, 23, 26 and 35,  
 T. 19 N., R. 19 W., Gila and Salt River Meridian, Arizona

CHAINS	
<p>6.97</p>	<p style="text-align: center;">T 19 N R 19 W</p> <p style="text-align: center;">WSWA AP14</p>  <p style="text-align: center;">S 20</p> <p style="text-align: center;">2004</p> <p>Cor. is located 30 ft. N. of a graded road.</p> <hr style="width: 30%; margin: 10px auto;"/> <p>S. 71°48' E., on line 14-15, sec. 20.</p> <p>Over level rocky land, through scattered creosote, yucca and scrub brush.</p> <p>Point for AP 15, sec. 20.</p> <p>Set an aluminum drive rod, 42 ins. long, 3/4 in. diam., 33 ins. in the ground, with aluminum cap mkd.</p>
<p>4.18</p>	<p style="text-align: center;">T 19 N R 19 W</p> <p style="text-align: center;">WSWA AP15</p>  <p style="text-align: center;">S 20</p> <p style="text-align: center;">2004</p> <p>Cor. is located 30 ft. N. of a graded road.</p> <hr style="width: 30%; margin: 10px auto;"/> <p>N. 65°57' E., on line 15-16, sec. 20.</p> <p>Over level rocky land, through scattered creosote, yucca and scrub brush.</p> <p>Point for AP 16, sec. 20.</p> <p>Set an aluminum drive rod, 42 ins. long, 3/4 in. diam., 33 ins. in the ground, with aluminum cap mkd.</p>

**Metes-and-Bounds Survey of the Warm Springs  
Wilderness Area Boundary, through secs. 20, 22, 23, 26 and 35,  
T. 19 N., R. 19 W., Gila and Salt River Meridian, Arizona**

CHAINS	
	<p>T 19 N R 19 W</p> <p>WSWA AP16</p>  <p>S 20</p> <p>2004</p>
	<p>Cor. is located 30 ft. N. of a graded road.</p> <hr style="width: 30%; margin: 10px auto;"/>
	<p>N. 85°00' E., on line 16-17, sec. 20.</p> <p>Over level rocky land, through scattered creosote, yucca and scrub brush.</p>
3.60	<p>Point for AP 17, sec. 20.</p> <p>Set an aluminum drive rod, 42 ins. long, 3/4 in. diam., 37 ins. in the ground, with aluminum cap mkd.</p>
	<p>T 19 N R 19 W</p> <p>WSWA AP17</p>  <p>S 20</p> <p>2004</p>
	<p>Cor. is located 30 ft. N. of a graded road.</p> <hr style="width: 30%; margin: 10px auto;"/>
	<p>N. 83°08' E., on line 17-18, sec. 20.</p> <p>Over level rocky land, through scattered creosote, yucca and scrub brush.</p>
2.92	<p>Point for AP 18, sec. 20, at intersection with the line bet. secs. 20 and 21, hereinbefore described.</p> <p>Set an aluminum drive rod, 42 ins. long, 3/4 in. diam., 33 ins. in the ground, with aluminum cap mkd.</p>

**Metes-and-Bounds Survey of the Warm Springs  
Wilderness Area Boundary, through secs. 20, 22, 23, 26 and 35,  
T. 19 N., R. 19 W., Gila and Salt River Meridian, Arizona**

CHAINS

T 19 N R 19 W

WSWA  
AP18

S 20

2004

Cor. is located 30 ft. N. of a graded road.

---

GENERAL DESCRIPTION

---

The Warm Springs Wilderness Area is located approximately 25 miles southwesterly of Kingman Az. Access is by way of I-40 to old highway U.S. 66.

The terrain varies from level and rolling in sections 13, 21, 22, 23, 24, 25, 26 and 35 to steep and mountainous in sections 17, 18, 19 and 20. The vegetation consists mostly of creosote and yucca bush, various cacti and native grasses.

The area is used for cattle grazing. There are several wild burros roaming in the area. Cold Spring is located in the NW 1/4 of the SE 1/4 of section 20.

The mean magnetic declination of  $12\frac{3}{4}^{\circ}$  E. was derived from the United States Geological Survey computer program GEOMAG, utilizing the World Magnetic Model for Epoch 2000 for the dates of survey.

---

**Description of the Warm Springs Wilderness Area Boundary,  
T. 19 N., R. 19 W., Gila and Salt River Meridian, Arizona**

---

The following is for informational purposes only

---

Beginning at the cor. of secs. 7, 12, 13 and 18, on the E. bdy. of the Tp.

thence S.  $0^{\circ}04'$  E., 12.52 chs. dist. to WP 1, on the line bet. secs. 13 and 18, T. 19 N., Rgs. 18 and 19 W.

thence S.  $0^{\circ}04'$  E., 14.07 chs. dist. to WP 2, on the line bet. secs. 13 and 18, T. 19 N., Rgs. 18 and 19 W.

thence S.  $0^{\circ}04'$  E., 13.43 chs. dist., on the line bet. secs. 13 and 18, to the 1/4 sec. cor. of secs. 13 and 18, T. 19 N., Rgs. 18 and 19 W.



**Description of the Warm Springs Wilderness Area Boundary,  
T. 19 N., R. 19 W., Gila and Salt River Meridian, Arizona**

CHAINS	
	thence S. 0°02' E., 12.99 chs. dist. to WP 3, on the line bet. secs. 13 and 18, T. 19 N., Rgs. 18 and 19 W.
	thence S. 0°02' E., 12.53 chs. dist. to WP 4, on the line bet. secs. 13 and 18, T. 19 N., Rgs. 18 and 19 W.
	thence S. 0°02' E., 14.18 chs. dist., on the line bet. secs. 13 and 18, to the cor. of secs. 13, 18, 19 and 24, T. 19 N., Rgs. 18 and 19 W.
	thence N. 89°52' W., 13.29 chs. dist. to WP 5, on line bet. secs. 13 and 24.
	thence N. 89°52' W., 15.15 chs. dist. to WP 6, on line bet. secs. 13 and 24.
	thence N. 89°52' W., 11.53 chs. dist., on line bet. secs. 13 and 24, to the 1/4 sec. cor. of secs. 13 and 24.
	thence N. 89°53' W., 12.83 chs. dist. to WP 7, on line bet. secs. 13 and 24.
	thence N. 89°53' W., 11.06 chs. dist. to WP 8, on line bet. secs. 13 and 24.
	thence N. 89°53' W., 16.04 chs. dist., on line bet. secs. 13 and 24, to the cor. of secs. 13, 14, 23 and 24.
	thence S. 0°03' E., 12.55 chs. dist. to WP 9, on line bet. secs. 23 and 24.
	thence S. 0°03' E., 11.89 chs. dist. to WP 10, on line bet. secs. 23 and 24.
	thence S. 0°03' E., 15.56 chs. dist., on line bet. secs. 23 and 24, to the 1/4 sec. cor. of secs. 23 and 24.
	thence S. 0°05' E., 12.33 chs. dist. to WP 11, on line bet. secs. 23 and 24.
	thence S. 0°05' E., 12.05 chs. dist. to WP 12, on line bet. secs. 23 and 24.
	thence S. 0°05' E., 15.77 chs. dist., on line bet. secs. 23 and 24, to the cor. of secs. 23, 24, 25 and 26.
	thence N. 89°52' W., 12.62 chs. dist. to WP 13, on line bet. secs. 23 and 26.
	thence N. 89°52' W., 11.32 chs. dist. to WP 14, on line bet. secs. 23 and 26.
	thence N. 89°52' W., 15.99 chs. dist., on line bet. secs. 23 and 26, to the 1/4 sec. cor. of secs. 23 and 26.
	thence S. 89°59' W., 12.65 chs. dist. to WP 15, on line bet. secs. 23 and 26.
	thence S. 89°59' W., 14.41 chs. dist. to WP 16, on line bet. secs. 23 and 26.
	thence S. 89°59' W., 7.54 chs. dist. to Angle Point 1, sec. 26, on the line bet. secs. 23 and 26.
	thence S. 31°28' E., 2.66 chs. dist. to Angle Point 2, sec. 26;
	thence S. 41°57' E., 3.59 chs. dist. to Angle Point 3, sec. 26;
	thence S. 35°14' E., 6.07 chs. dist. to Angle Point 4, sec. 26;
	thence S. 43°12' E., 8.61 chs. dist. to Angle Point 5, sec. 26;
	thence S. 38°13' E., 11.80 chs. dist. to Angle Point 6, sec. 26;

**Description of the Warm Springs Wilderness Area Boundary,  
T. 19 N., R. 19 W., Gila and Salt River Meridian, Arizona**

CHAINS	
	thence S. 37°56' E., 2.73 chs. dist. to Angle Point 7, sec. 26;
	thence S. 16°26' E., 3.56 chs. dist. to Angle Point 8, sec. 26;
	thence S. 59°42' E., 6.75 chs. dist. to Angle Point 9, sec. 26;
	thence S. 44°59' E., 5.40 chs. dist. to Angle Point 10, sec. 26;
	thence S. 18°21' E., 12.92 chs. dist. to Angle Point 11, sec. 26;
	thence S. 12°05' E., 7.46 chs. dist. to Angle Point 12, sec. 26;
	thence S. 20°58' E., 6.99 chs. dist. to Angle Point 13, sec. 26;
	thence S. 6°43' E., 7.62 chs. dist. to Angle Point 14, sec. 26;
	thence S. 55°52' E., 0.95 chs. dist. to Angle Point 15, sec. 26;
	thence S. 15°57' E., 6.60 chs. dist. to Angle Point 16, sec. 26;
	thence S. 49°03' W., 2.16 chs. dist. to Angle Point 17, sec. 26, identical with Angle Point 1, sec. 35, on the line bet. secs. 26 and 35.
	thence S. 25°45' E., 11.14 chs. dist. to Angle Point 2, sec. 35;
	thence S. 7°34' E., 6.36 chs. dist. to Angle Point 3, sec. 35;
	thence S. 13°10' E., 8.34 chs. dist. to Angle point 4, sec. 35;
	thence S. 1°34' W., 6.03 chs. dist. to Angle Point 5, sec. 35;
	thence S. 21°27' E., 5.61 chs. dist. to Angle Point 6, sec. 35;
	thence S. 8°14' E., 7.52 chs. dist. to Angle Point 7, sec. 35;
	thence S. 17°24' E., 5.78 chs. dist. to Angle point 8, sec. 35;
	thence S. 28°49' W., 3.09 chs. dist. to Angle Point 9, sec. 35;
	thence S. 18°48' W., 7.03 chs. dist. to Angle Point 10, sec. 35;
	thence S. 5°17' W., 3.79 chs. dist. to Angle Point 11, sec. 35;
	thence S. 10°06' W., 4.77 chs. dist. to Angle Point 12, sec. 35;
	thence S. 8°56' W., 6.93 chs. dist. to Angle Point 13, sec. 35;
	thence S. 30°13' E., 3.16 chs. dist. to Angle Point 14, sec. 35;
	thence S. 9°33' E., 4.01 chs. dist. to Angle Point 15, sec. 35, at intersection with the Tp. line bet. Tps. 18 and 19 N., R. 19 W., on line bet. secs. 2 and 35.

**Description of the Warm Springs Wilderness Area Boundary,  
T. 19 N., R. 19 W., Gila and Salt River Meridian, Arizona**

CHAINS	
	thence N. 89°58' W., 0.91 chs. dist., bet. secs 2 and 35, to Angle Point 16, sec. 35, on the Tp. line bet. Tps. 18 and 19 N., R. 19 W.
	thence N. 10°26' W., 3.70 chs. dist. to Angle Point 17, sec. 35;
	thence N. 28°54' W., 3.45 chs. dist. to Angle Point 18, sec. 35;
	thence N. 8°41' E., 6.89 chs. dist. to Angle Point 19, sec. 35;
	thence N. 9°33' E., 5.09 chs. dist. to Angle Point 20, sec. 35;
	thence N. 5°34' E., 3.48 chs. dist. to Angle Point 21, sec. 35;
	thence N. 18°18' E., 7.44 chs. dist. to Angle Point 22, sec. 35;
	thence N. 30°51' E., 2.83 chs. dist. to Angle Point 23, sec. 35;
	thence N. 17°57' W., 5.41 chs. dist. to Angle Point 24, sec. 35;
	thence N. 9°03' W., 7.37 chs. dist. to Angle Point 25, sec. 35;
	thence N. 19°33' W., 5.89 chs. dist. to Angle Point 26, sec. 35;
	thence N. 0°42' E., 5.58 chs. dist. to Angle Point 27, sec. 35;
	thence N. 12°08' W., 8.58 chs. dist. to Angle Point 28, sec. 35;
	thence N. 8°25' W., 6.73 chs. dist. to Angle Point 29, sec. 35;
	thence N. 25°27' W., 10.14 chs. dist. to Angle Point 30, sec. 35;
	thence N. 89°29' W., 1.62 chs. dist. to Angle Point 31, sec. 35;
	thence N. 41°04' W., 1.09 chs. dist. to Angle Point 32, sec. 35, identical with Angle Point 18, sec. 26, on line bet. secs. 26 and 35;
	thence N. 7°28' E., 4.07 chs. dist. to Angle Point 19, sec. 26;
	thence N. 10°13' W., 2.85 chs. dist. to Angle Point 20, sec. 26;
	thence N. 29°33' E., 1.76 chs. dist. to Angle Point 21, sec. 26;
	thence N. 6°08' W., 7.26 chs. dist. to Angle Point 22, sec. 26;
	thence N. 20°14' W., 7.00 chs. dist. to Angle Point 23, sec. 26;
	thence N. 11°55' W., 7.59 chs. dist. to Angle Point 24, sec. 26;
	thence N. 19°06' W., 12.49 chs. dist. to Angle Point 25, sec. 26;
	thence N. 42°36' W., 4.89 chs. dist. to Angle Point 26, sec. 26;
	thence N. 65°29' W., 7.29 chs. dist. to Angle Point 27, sec. 26;

**Description of the Warm Springs Wilderness Area Boundary,  
T. 19 N., R. 19 W., Gila and Salt River Meridian, Arizona**

CHAINS	
	thence N. 11°41' W., 3.96 chs. dist. to Angle Point 28, sec. 26;
	thence N. 37°18' W., 2.69 chs. dist. to Angle Point 29, sec. 26;
	thence N. 37°21' W., 11.78 chs. dist. to Angle Point 30, sec. 26;
	thence N. 43°22' W., 8.72 chs. dist. to Angle Point 31, sec. 26;
	thence N. 35°35' W., 6.27 chs. dist. to Angle Point 32, sec. 26;
	thence N. 39°48' W., 3.40 chs. dist. to Angle Point 33, sec. 26;
	thence N. 33°04' W., 3.25 chs. dist. to Angle Point 34, sec. 26, identical with Angle Point 1, sec. 23, on line bet. secs. 23 and 26.
	thence N. 37°01' W., 7.04 chs. dist. to Angle Point 2, sec. 23, identical with Angle Point 1, sec. 22, on line bet. secs. 22 and 23.
	thence N. 20°46' W., 2.16 chs. dist. to Angle Point 2, sec. 22;
	thence N. 11°55' W., 9.61 chs. dist. to Angle Point 3, sec. 22;
	thence N. 22°56' W., 7.21 chs. dist. to Angle Point 4, sec. 22;
	thence N. 40°45' W., 4.71 chs. dist. to Angle Point 5, sec. 22;
	thence N. 36°57' W., 5.09 chs. dist. to Angle Point 6, sec. 22;
	thence N. 24°34' W., 6.74 chs. dist. to Angle Point 7, sec. 22;
	thence N. 28°41' W., 10.62 chs. dist. to Angle Point 8, sec. 22;
	thence N. 17°27' W., 13.20 chs. dist. to Angle Point 9, sec. 22;
	thence N. 9°52' E., 4.15 chs. dist. to Angle Point 10, sec. 22;
	thence N. 12°06' W., 2.26 chs. dist. to Angle Point 11, sec. 22;
	thence N. 35°25' W., 9.37 chs. dist. to Angle Point 12, sec. 22;
	thence N. 32°16' W., 8.12 chs. dist. to Angle Point 13, sec. 22, intersecting the sec. line bet. secs. 15 and 22.
	thence N. 89°54' W., 7.13 chs. dist. on line bet. secs. 15 and 22, to the 1/4 sec. cor. of secs. 15 and 22.
	thence N. 89°55' W., 14.47 chs. dist. to WP 17, on line bet. secs. 15 and 22.
	thence N. 89°55' W., 12.38 chs. dist. to WP 18, on line bet. secs. 15 and 22.
	thence N. 89°55' W., 13.13 chs. dist. on line bet. secs. 15 and 22, to the cor. of secs. 15, 16, 21 and 22.
	thence S. 0°06' E., 4.66 chs. dist. to WP 19, on line bet. secs. 21 and 22.
	thence S. 0°06' E., 23.46 chs. dist. WP 20, on line bet. secs 21 and 22.

**Description of the Warm Springs Wilderness Area Boundary,  
T. 19 N., R. 19 W., Gila and Salt River Meridian, Arizona**

## CHAINS

thence S. 0°06' E., 11.90 chs. dist. on line bet. secs. 21 and 22, to the 1/4 sec. cor. of secs. 21 and 22.

thence S. 0°05' E., 12.48 chs. dist. to WP 21, on line bet. secs. 21 and 22.

thence S. 0°05' E., 12.67 chs. dist. to WP 22, on line bet. secs. 21 and 22.

thence S. 0°05' E., 14.88 chs. dist. on line bet. secs. 21 and 22, to the cor. of secs. 21, 22, 27 and 28.

thence S. 89°56' W., 17.41 chs. dist. to WP 23, on line bet. secs. 21 and 28.

thence S. 89°56' W., 23.15 chs. dist. on line bet. secs. 21 and 28, to the 1/4 sec. cor. of secs. 21 and 28.

thence S. 89°54' W., 15.90 chs. dist. to WP 24, on line bet. secs. 21 and 28.

thence S. 89°54' W., 24.15 chs. dist. on line bet. secs. 21 and 28, to the cor. of secs. 20, 21, 28 and 29.

thence N. 0°03' E., 23.77 chs. dist. to Angle Point 1, sec. 20, on line bet. secs. 20 and 21.

thence S. 81°48' W., 3.09 chs. dist. to Angle Point 2, sec. 20;

thence S. 85°56' W., 3.26 chs. dist. to Angle Point 3, sec. 20;

thence S. 64°07' W., 4.32 chs. dist. to Angle Point 4, sec. 20;

thence N. 71°31' W., 7.20 chs. dist. to Angle Point 5, sec. 20;

thence N. 85°27' W., 1.43 chs. dist. to Angle Point 6, sec. 20;

thence S. 84°24' W., 1.95 chs. dist. to Angle Point 7, sec. 20;

thence S. 43°47' W., 0.96 chs. dist. to Angle Point 8, sec. 20;

thence S. 69°30' W., 0.98 chs. dist. to Angle Point 9, sec. 20;

thence N. 0°13' E., 1.13 chs. dist. to Angle Point 10, sec. 20;

thence N. 37°12' E., 0.63 chs. dist. to Angle Point 11, sec. 20;

thence N. 75°48' E., 1.10 chs. dist. to Angle Point 12, sec. 20;

thence N. 82°11' E., 1.96 chs. dist. to Angle Point 13, sec. 20;

thence S. 87°40' E., 1.65 chs. dist. to Angle Point 14, sec. 20;

thence S. 71°48' E., 6.97 chs. dist. to Angle Point 15, sec. 20;

thence N. 65°57' E., 4.18 chs. dist. to Angle Point 16, sec. 20;

thence N. 85°00' E., 3.60 chs. dist. to Angle Point 17, sec. 20;

thence N. 83°08' E., 2.92 chs. dist. to Angle Point 18, sec. 20;

thence N. 0°03' E., 15.33 chs. dist. on line bet. secs. 20 and 21, to the 1/4 sec. cor. of secs. 20 and 21.

thence N. 0°10' W., 40.00 chs. dist. on line bet. secs. 20 and 21, to the cor. of secs. 16, 17, 20 and 21.

thence S. 89°53' W., 39.87 chs. dist. on line bet. secs. 17 and 20, to the 1/4 sec. cor. of secs. 17 and 20.

thence S. 89°55' W., 39.85 chs. dist. on line bet. secs. 17 and 20, to the cor. of secs. 17, 18, 19 and 20.

thence N. 89°32' W., 39.97 chs. dist. on line bet. secs. 18 and 19, to the true point for the 1/4 sec. cor. of secs. 18 and 19.

thence N. 89°32' W., 13.705 chs. dist. to WP on line bet. secs. 18 and 19.

thence N. 89°32' W., 24.945 chs. dist. on line bet. secs. 18 and 19, to the cor. of secs. 13, 18, 19 and 24, on the W. bdy. of the Tp.



CERTIFICATE OF SURVEY

I, W. William Foster, Cadastral Surveyor, HEREBY CERTIFY upon honor, that in pursuance of special instructions bearing date of the 17th day of February, 2004, I have dependently resurveyed a portion of the Fifth Guide Meridian West (east boundary), a portion of the south boundary and a portion of the subdivisional lines, and the metes-and-bounds survey of the Warm Springs Wilderness Area Boundary through sections 20, 22, 23, 26 and 35, T. 19 N., R. 19 W., of the Gila and Salt River Meridian, in the State of Arizona, which are represented in the foregoing field notes as having been executed by me and under my direction. Said survey has been made in strict conformity with said special instructions, the Manual of Instructions for the Survey of the Public Lands of the United States, and in specific manner described in the foregoing field notes.

2/02/06  
(Date)

W. William Foster  
(Cadastral Surveyor)

CERTIFICATE OF APPROVAL

BUREAU OF LAND MANAGEMENT  
Phoenix, Arizona

The foregoing field notes of the dependent resurvey of a portion of the Fifth Guide Meridian West (east boundary), a portion of the south boundary and a portion of the subdivisional lines, and the metes-and-bounds survey of the Warm Springs Wilderness Area Boundary through sections 20, 22, 23, 26 and 35, T. 19 N., R. 19 W., Gila and Salt River Meridian, in the State of Arizona, executed by W. William Foster, Cadastral Surveyor, having been critically examined and found correct, are hereby approved.

6/05/06  
(Date)

Stephen H. Hansen  
(Chief Cadastral Surveyor of Arizona)

~~CERTIFICATE OF TRANSCRIPT~~

~~I CERTIFY That the foregoing transcript of the field notes of the above described surveys in T. 19 N., R. 19 W., Gila and Salt River Meridian, Arizona, is a true copy of the original field notes.~~

~~\_\_\_\_\_~~  
(Date)

~~\_\_\_\_\_~~  
(Chief Cadastral Surveyor of Arizona)

