

ORIGINAL

**UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT**

FIELD NOTES
OF
THE
DEPENDENT RESURVEY
OF
THE
SUBDIVISIONAL LINES,
TOWNSHIP 22 NORTH, RANGE 28 EAST,
OF THE GILA AND SALT RIVER MERIDIAN,
IN THE STATE OF ARIZONA
EXECUTED BY
Jones Curtiss, Cadastral Surveyor

Under Special Instructions dated and approved April 13, 2005, which provided for the surveys included under Group No. 956, and assignment instructions dated April 13, 2005.

Survey commenced April 18, 2005

Survey completed June 16, 2005

INDEX DIAGRAM

TOWNSHIP 22 NORTH RANGE 28 EAST
GILA AND SALT RIVER MERIDIAN, ARIZONA

6	43 5	33 4	27 3	20 2	12 1
43	42	33	26	19	11
7	42 8	32 9	25 10	18 11	11 12
41	41	32	25	18	10
18	40 17	31 16	24 15	17 14	9 13
39	39	31	24	16	8
19	38 20	30 21	23 22	16 23	8 24
37	37	29	22	15	7
30	36 29	29 28	22 27	14 26	6 25
36	35	28	21	14	5
31	34 32	27 33	20 34	12 35	4 36

T. 22 N., R. 28 E., Gila and Salt River Meridian, Arizona

CHAINS

The following field notes describe the dependent resurvey of the subdivisional lines, Township 22 North, Range 28 East, Gila and Salt River Meridian, Arizona.

The history of surveys pertaining to this survey is as follows:

W. R. Fitzgerald surveyed the Seventh Auxiliary Guide Meridian East (east boundary) and the south boundary in 1882. Frank Follman surveyed the west and north boundaries and the subdivisional lines in 1882-83. Sidney E. Blout retraced a portion of the north boundary in 1920. William P. Carpenter, Stephen J. Malloy and Kenneth W. Bays dependently resurveyed the Seventh Auxiliary Guide Meridian East (west boundary), Township 21 North, Range 29 East, in 1987-93. Joe R. Salazar dependently resurveyed a portion of the Seventh Auxiliary Guide Meridian East (west boundary), Township 22 North, Range 29 East, in 1993. William P. Carpenter and Stephen J. Malloy dependently resurveyed the north boundary, Township 21 North, Range 28 East, in 1987-94. Jones Curtiss dependently resurveyed the north and west boundaries in 2002-03. Adrien J. Rodriguez dependently resurveyed a portion of the Seventh Auxiliary Guide Meridian East (west boundary), Township 22 North, Range 29 East in 2004-05.

The survey was executed in accordance with the specifications as set forth in the Manual of Instructions for the Survey of the Public Lands of the United States, 1973, and the Special Instructions dated April 13, 2005, for Group No. 956, Arizona.

The true meridian direction and length of all lines were determined by real time kinematic global positioning system observations using Trimble Navigation 5700 model receivers.

Preliminary to the resurvey, the lines of the prior surveys were retraced and search was made for all corners and other calls of record. Identified corners were remonumented in their original positions. Lost corners were reestablished and remonumented at proportionate positions based on the official record. The retracement data were thoroughly verified and only the true line field notes are given herein.

During the course of this survey, the southeast and northeast township corners were occupied by global positioning system receivers. The following geographic position of the southeast corner of the township was a result of their observations.

T. 22 N., R. 28 E., Gila and Salt River Meridian, Arizona

CHAINS

Geodetic control was derived from Global Positioning System (GPS) static observations post processed by National Geodetic Survey's Online Positioning User Service (OPUS), utilizing Continuously Operating Reference Stations (CORS) Ferno Mesa, Flagstaff, Pie Town VLBA. The NAD83 (CORS96) (EPOCH:2002) geographic position of the southeast corner of the township is as follows:

Latitude: 35°15'15.26" N. Longitude: 109°18'53.25" W.

The mean magnetic declination is 11° E.

**Dependent Resurvey of the Subdivisional Lines,
T. 22 N., R. 28 E., Gila and Salt River Meridian, Arizona**

Restoring the survey executed by
Frank Follman, in 1883

From the cor. of secs. 1, 2, 35 and 36, on the S. bdy. of the Tp., monumented with a stainless steel post, 2 1/2 ins. diam., firmly set, projecting 1 in. above ground, with brass cap mkd. T22N R28E S35 S36 S2 S1 T21N 1992, from which the 1992 bearing trees

A juniper, 6 ins. diam., bears N. 58 1/2° E., 84 lks. dist., mkd. T22N R28E S36 BT on partially healed blaze.

A juniper, 10 ins. diam., bears S. 80 1/2° E., 1.24 chs. dist., mkd. T21N R28E S1 BT on partially healed blaze.

A juniper, 11 ins. diam., bears S. 8 1/4° W., 42 lks. dist., mkd. T21N R28E S2 BT on partially healed blaze.

A juniper, 6 ins. diam., bears N. 31 1/2° W., 49 lks. dist., mkd. X BT on open blaze.

Add the marks 2005 to the brass cap.

N. 0°18' E., bet. secs. 35 and 36.

Over rolling land.

39.98

Point for the 1/4 sec. cor. of secs. 35 and 36, at proportionate dist.; there is no remaining evidence of the original cor.

Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.

**Dependent Resurvey of the Subdivisional Lines,
T. 22 N., R. 28 E., Gila and Salt River Meridian, Arizona**

CHAINS	
	T 22 N R 28 E 1/4 S 35 S 36 2005
79.96	<p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p> <p>Point for the cor. of secs. 25, 26, 35 and 36, at proportionate dist.; there is no remaining evidence of the original cor.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p>
	T 22 N R 28 E S 26 S 25 S 35 S 36 2005
40.03	<p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p> <p>From this cor. point, second order U. S. Coast and Geodetic Survey triangulation station "LOST", bears N. 56° 58' W., 34.65 chs. dist., monumented with a standard brass tablet, 3 1/2 ins. diam., firmly set flush in concrete collar, 10 ins. square, projecting 10 ins. above ground., with top mkd. LOST 1959 and a triangle.</p> <hr/> <p>From the cor. of secs. 25, 30, 31 and 36, on the E. bdy. of the Tp., monumented with a stainless steel post, 2 1/2 ins. diam., firmly set, projecting 4 ins. above ground, with brass cap mkd. T22N R28E R29E S25 S30 S36 S31 2004, with a steel fence post set nearby.</p> <p>Add the marks 2005 to the brass cap.</p> <p>N. 87°38' W., bet. secs. 25 and 36.</p> <p>Over rolling land.</p> <p>Point for the 1/4 sec. cor. of secs. 25 and 36, at proportionate dist.; there is no remaining evidence of the original cor.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p>

Dependent Resurvey of the Subdivisional Lines,
T. 22 N., R. 28 E., Gila and Salt River Meridian, Arizona

CHAINS	
	<p style="text-align: center;">T 22 N R 28 E S 25 1/4 ——— S 36</p> <p style="text-align: center;">2005</p>
80.06	<p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p> <p>The cor. of secs. 25, 26, 35 and 36.</p> <hr/>
	<p>N. 0°12' W., bet. secs. 25 and 26.</p> <p>Over rolling land.</p>
39.98	<p>Point for the 1/4 sec. cor. of secs. 25 and 26, at proportionate dist.; there is no remaining evidence of the original cor.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p>
	<p style="text-align: center;">T 22 N R 28 E 1/4 S 26 S 25</p> <p style="text-align: center;">2005</p>
	<p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p>
79.96	<p>Point for the cor. of secs. 23, 24, 25 and 26, at proportionate dist.; there is no remaining evidence of the original cor.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p>
	<p style="text-align: center;">T 22 N R 28 E S 23 S 24 — — S 26 S 25</p> <p style="text-align: center;">2005</p>

**Dependent Resurvey of the Subdivisional Lines,
T. 22 N., R. 28 E., Gila and Salt River Meridian, Arizona**

CHAINS

Deposit a magnet, in a white plastic case, at the base of the stainless steel post.

From the cor. of secs. 19, 24, 25 and 30, on the E. bdy. of the Tp., monumented with a stainless steel post, 2 1/2 ins. diam., firmly set, projecting 4 ins. above ground, with brass cap mkd. T22N R28E R29E S24 S19 S25 S30 1992 2004, with a steel fence post set nearby, from which the 1992 bearing trees

A forked juniper, 12 ins. diam. at base, bears N. 36° E., 2.14 chs. dist., mkd. T22N R29E S19 BT, on partially healed blaze.

A juniper, 7 ins. diam., bears S. 47 1/4° E., 1.70 chs. dist., mkd. T22N R29E S30 BT on partially healed blaze.

A juniper, 10 ins. diam., bears S. 4 1/2 ° W., 2.38 chs. dist., mkd. T22N R28E S25 BT on partially healed blaze.

A juniper stump, 17 ins. diam. at base, projecting 2 1/2 ft. high, bears N. 60 1/4° W., 1.115 chs. dist., mkd. 2N R28E S24 BT on partially healed blaze.

Add the marks 2005 to the brass cap.

Cor. is located at the intersection of barbed wire fences, extending North, East and South.

N. 88°28' W., bet. secs. 24 and 25.

Over rolling land.

40.14

Point for the 1/4 sec. cor. of secs. 24 and 25, at proportionate dist.; there is no remaining evidence of the original cor.

Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.

T 22 N R 28 E
S 24
1/4 ———
S 25

2005

Deposit a magnet, in a white plastic case, at the base of the stainless steel post.

Cor. is located 66 lks. W. of W. edge of a wash, 5 ft. wide, 6 ft. deep, drains S. 5° E.

Dependent Resurvey of the Subdivisional Lines,
T. 22 N., R. 28 E., Gila and Salt River Meridian, Arizona

CHAINS	
80.28	<p>The cor. of secs. 23, 24, 25 and 26.</p> <hr/> <p>N. 1°06' W., bet. secs. 23 and 24.</p> <p>Over rolling and broken land.</p>
18.20	E. rim of a mesa, 100 ft. high, bears N. 25° E. and S. 25° W.
39.99	<p>Point for the 1/4 sec. cor. of secs. 23 and 24, at proportionate dist.; there is no remaining evidence of the original cor.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center;"> <p>T 22 N R 28 E 1/4 S 23 S 24</p> <p>2005</p> </div> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p>
79.98	<p>Point for the cor. of secs. 13, 14, 23 and 24, at proportionate dist.; there is no remaining evidence of the original cor.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center;"> <p>T 22 N R 28 E S 14 S 13 S 23 S 24</p> <p>2005</p> </div> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p> <hr/> <p>From the cor. of secs. 13, 18, 19 and 24, on the E. bdy. of the Tp., monumented with a stainless steel post, 2 1/2 ins. diam., firmly set, projecting 2 ins. above ground, with brass cap mkd. T22N R28E R29E S13 S18 S24 S19 1993 2004, with a steel fence post set nearby, from which the 1993 bearing tree</p> <p style="padding-left: 40px;">A forked juniper, 14 ins. diam. at base, bears N. 24 1/4° W., 62 lks. dist., mkd. T22N R28E S13 BT on partially healed blaze.</p> <p>Add the marks 2005 to the brass cap.</p>

**Dependent Resurvey of the Subdivisional Lines,
T. 22 N., R. 28 E., Gila and Salt River Meridian, Arizona**

CHAINS	
	<p>Cor. is located 3 lks. W. of the intersection of barbed wire fences, extending North and East.</p> <p>N. 88°52' W., bet. secs. 13 and 24.</p> <p>Over rolling land.</p>
17.30	<p>Apache County Road C301, a graded road, 20 ft. wide, bears N. 5° E. and S. 5° W.</p>
39.82	<p>Point for the 1/4 sec. cor. of secs. 13 and 24, at proportionate dist.; there is no remaining evidence of the original cor.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center;"> <p>T 22 N R 28 E</p> <p>S 13</p> <p>1/4 ———</p> <p>S 24</p> <p>2005</p> </div> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p>
52.10	<p>E. rim of a mesa, 60 ft. high, bears N. 20° E. and S. 20° W.</p>
79.64	<p>The cor. of secs. 13, 14, 23 and 24.</p> <hr/>
	<p>N. 0°09' W., bet. secs. 13 and 14.</p> <p>Over rolling land.</p>
39.98	<p>Point for the 1/4 sec. cor. of secs. 13 and 14, at proportionate dist.; there is no remaining evidence of the original cor.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center;"> <p>T 22 N R 28 E</p> <p>1/4</p> <p>S 14 S 13</p> <p>2005</p> </div> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p>
44.00	<p>Apache County Road C409, a graded road, 20 ft. wide, bears N. 80° E. and S. 80° W.</p>

**Dependent Resurvey of the Subdivisional Lines,
T. 22 N., R. 28 E., Gila and Salt River Meridian, Arizona**

CHAINS									
44.40	Barbed wire fence, 4 strands, bears N. 80° E. and S. 80° W.								
79.96	<p>Point for the cor. of secs. 11, 12, 13 and 14, at proportionate dist.; there is no remaining evidence of the original cor.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center;"> <table border="1"> <tr> <td>T 22 N</td> <td>R 28 E</td> </tr> <tr> <td>S 11</td> <td>S 12</td> </tr> <tr> <td>S 14</td> <td>S 13</td> </tr> </table> <p>2005</p> </div> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p> <hr/> <p>From the cor. of secs. 7, 12, 13 and 18, on the E. bdy. of the Tp., monumented with a stainless steel post, 2 1/2 ins. diam., firmly set, projecting 6 ins. above ground, with brass cap mkd. T22N R28E R29E S12 S7 S13 S18 1993 2004, from which the 1993 bearing tree</p> <p style="padding-left: 40px;">A forked juniper, 12 ins. diam. at base, bears N. 0 1/2° E., 45.5 lks. dist., mkd. T22N R29E S7 BT on partially healed blaze.</p> <p>Add the marks 2005 to the brass cap.</p> <p>Cor. is located 60 lks. E. of Apache County Road C409, a graded road, 25 ft. wide, bears N. 35° E. and S. 35° W.</p> <p>N. 88°30' W., bet. secs. 12 and 13.</p> <p>Over rolling land.</p>	T 22 N	R 28 E	S 11	S 12	S 14	S 13		
T 22 N	R 28 E								
S 11	S 12								
S 14	S 13								
40.01	<p>Point for the 1/4 sec. cor. of secs. 12 and 13, at proportionate dist.; there is no remaining evidence of the original cor.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center;"> <table border="1"> <tr> <td>T 22 N</td> <td>R 28 E</td> </tr> <tr> <td></td> <td>S 12</td> </tr> <tr> <td>1/4</td> <td>———</td> </tr> <tr> <td></td> <td>S 13</td> </tr> </table> <p>2005</p> </div> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p>	T 22 N	R 28 E		S 12	1/4	———		S 13
T 22 N	R 28 E								
	S 12								
1/4	———								
	S 13								

**Dependent Resurvey of the Subdivisional Lines,
T. 22 N., R. 28 E., Gila and Salt River Meridian, Arizona**

CHAINS	
	<p>Cor. is located 22 lks. E. of a abandoned trail road, bears S. 10° E. and N. 10° W.</p>
80.02	<p>The cor. of secs. 11, 12, 13 and 14.</p> <hr/> <p>N. 0°08' E., bet. secs. 11 and 12.</p> <p>Over rolling land.</p>
39.98	<p>Point for the 1/4 sec. cor. of secs. 11 and 12, at proportionate dist.; there is no remaining evidence of the original cor.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center;"> <p>T 22 N R 28 E 1/4 S 11 S 12</p> <p>2005</p> </div> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p>
79.96	<p>Point for the cor. of secs. 1, 2, 11 and 12, at proportionate dist.; there is no remaining evidence of the original cor.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center;"> <p>T 22 N R 28 E S 2 S 1 S 11 S 12</p> <p>2005</p> </div> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p> <hr/> <p>From the cor. of secs. 1, 6, 7 and 12, on the E. bdy. of the Tp., monumented with a stainless steel post, 2 1/2 ins. diam., firmly set, projecting 3 ins. above ground, with brass cap mkd. T22N R28E R29E S1 S6 S12 S7 2004.</p> <p>Add the marks 2005 to the brass cap.</p> <p>N. 88°07' W., bet. secs. 1 and 12.</p> <p>Over rolling land.</p>

**Dependent Resurvey of the Subdivisional Lines,
T. 22 N., R. 28 E., Gila and Salt River Meridian, Arizona**

CHAINS	
40.00	<p>Point for the 1/4 sec. cor. of secs. 1 and 12, at proportionate dist.; there is no remaining evidence of the original cor.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T 22 N R 28 E S 1 1/4 ——— S 12</p> <p style="text-align: center;">2005</p> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p>
63.90	Graded road, 15 ft. wide, bears S. 25° E. and N. 25° W.
80.00	The cor. of secs. 1, 2, 11 and 12.
	<hr/> <p>N. 0°15' E., bet. secs. 1 and 2.</p> <p>Over rolling land.</p>
33.50	Graded road, 15 ft. wide, bears S. 55° E. and N. 55° W.
39.98	<p>Point for the 1/4 sec. cor. of secs. 1 and 2, at proportionate dist.; there is no remaining evidence of the original cor.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T 22 N R 28 E 1/4 S 2 S 1</p> <p style="text-align: center;">2005</p> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p>
79.53	<p>The cor. of secs. 1, 2, 35 and 36, on the N. bdy. of the Tp., monumented with a stainless steel post, 2 1/2 ins. diam., firmly set, projecting 4 ins. above ground, with brass cap mkd. T23N R28E S35 S36 S2 S1 T22N 2003.</p> <hr/> <p>From the cor. of secs. 2, 3, 34 and 35, on the S. bdy. of the Tp., monumented with a magnet, in a white plastic case, set 24 ins. below the surface of the ground.</p> <p>At the corner point</p>

**Dependent Resurvey of the Subdivisional Lines,
T. 22 N., R. 28 E., Gila and Salt River Meridian, Arizona**

CHAINS

Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam.,
24 ins. in the ground, with brass cap mkd.

T 22 N	R 28 E
S 34	S 35
S 3	S 2
T 21 N	

2005

from which the 1991 bearing trees

A forked juniper, 18 ins. diam. at base, bears
N. 33 1/2° E., 14 lks. dist., mkd. T22N R28E S35 BT on
partially healed blaze.

A juniper, 6 ins. diam., bears S. 41° E., 1.235 chs.
dist., mkd. X BT on open blaze.

A forked juniper, 24 ins. diam. at base, bears S. 56° W.,
51 lks. dist., mkd. T21N R28E S3 BT on partially healed
blaze.

A juniper, 5 ins. diam., bears N. 22 3/4° W., 1.90 chs.
dist., mkd. X BT on open blaze.

North, bet. secs. 34 and 35.

Over rolling land.

- 2.50 Barbed wire fence, 5 strands, bears N. 35° E. and S. 35° W.
11.40 Barbed wire fence, 3 strands, bears N. 60° E. and S. 60° W.
20.90 Barbed wire fence, 4 strands, bears N. 80° E. and S. 80° W.
40.02 Point for the 1/4 sec. cor. of secs. 34 and 35, at proportionate
dist.; there is no remaining evidence of the original cor.

Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam.,
24 ins. in the ground, with brass cap mkd.

T 22 N	R 28 E
1/4	
S 34	S 35

2005

Deposit a magnet, in a white plastic case, at the base of the
stainless steel post.

Cor. is located 34 lks. N. of a trail road, bears N. 80° E. and
S. 80° W.

**Dependent Resurvey of the Subdivisional Lines,
T. 22 N., R. 28 E., Gila and Salt River Meridian, Arizona**

CHAINS									
80.04	<p>Point for the cor. of secs. 26, 27, 34 and 35, at proportionate dist.; there is no remaining evidence of the original cor.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center;"> <table style="margin: auto;"> <tr> <td>T 22 N</td> <td>R 28 E</td> </tr> <tr> <td>S 27</td> <td>S 26</td> </tr> <tr> <td>S 34</td> <td>S 35</td> </tr> </table> <p>2005</p> </div> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p> <hr/> <p>From the cor. of secs. 25, 26, 35 and 36.</p> <p>N. 88°34' W., bet. secs. 26 and 35.</p> <p>Over broken land.</p>	T 22 N	R 28 E	S 27	S 26	S 34	S 35		
T 22 N	R 28 E								
S 27	S 26								
S 34	S 35								
40.36	<p>Point for the 1/4 sec. cor. of secs. 26 and 35, at proportionate dist.; there is no remaining evidence of the original cor.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center;"> <table style="margin: auto;"> <tr> <td>T 22 N</td> <td>R 28 E</td> </tr> <tr> <td></td> <td>S 26</td> </tr> <tr> <td>1/4</td> <td>—</td> </tr> <tr> <td></td> <td>S 35</td> </tr> </table> <p>2005</p> </div> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p> <p>Cor. is located 1.34 chs. S. of a trail road, bears N. 70° E. and S. 70° W.</p>	T 22 N	R 28 E		S 26	1/4	—		S 35
T 22 N	R 28 E								
	S 26								
1/4	—								
	S 35								
70.70	<p>Apache County Road C409, a graded road, 20 ft. wide, bears N. 25° E. and S. 25° W.</p>								
73.20	<p>Graded road, 20 ft. wide, bears S. 45° E. and N. 45° W.</p>								
80.72	<p>The cor. of secs. 26, 27, 34 and 35.</p> <hr/> <p>N. 0°04' W., bet. secs. 26 and 27.</p> <p>Over rolling land.</p>								

**Dependent Resurvey of the Subdivisional Lines,
T. 22 N., R. 28 E., Gila and Salt River Meridian, Arizona**

CHAINS	
6.70	Graded road, 20 ft. wide, bears S. 50° E. and N. 50° W.
40.02	Point for the 1/4 sec. cor. of secs. 26 and 27, at proportionate dist.; there is no remaining evidence of the original cor. Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd. <div style="text-align: center;"> T 22 N R 28 E 1/4 S 27 S 26 2005 </div> Deposit a magnet, in a white plastic case, at the base of the stainless steel post.
80.04	Point for the cor. of secs. 22, 23, 26 and 27, at proportionate dist.; there is no remaining evidence of the original cor. Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd. <div style="text-align: center;"> T 22 N R 28 E S 22 S 23 S 27 S 26 2005 </div> Deposit a magnet, in a white plastic case, at the base of the stainless steel post.
	<hr/> From the cor. of secs. 23, 24, 25 and 26. N. 88°30' W., bet. secs. 23 and 26. Over broken land.
5.50	E. rim of a mesa, 60 ft. high, bears N. 25° E. and S. 25° W.
34.90	Apache County Road C409, a graded road, 30 ft. wide, bears N. 20° E. and S. 20° W.
37.76	Barbed wire fence, 5 strands, bears N. 25° E. and S. 25° W.
40.26	Point for the 1/4 sec. cor. of secs. 23 and 26, at proportionate dist.; there is no remaining evidence of the original cor. Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.

Dependent Resurvey of the Subdivisional Lines,
T. 22 N., R. 28 E., Gila and Salt River Meridian, Arizona

CHAINS	
	<p style="text-align: center;">T 22 N R 28 E S 23 1/4 ——— S 26</p> <p style="text-align: center;">2005</p>
	<p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p>
50.12	<p>Barbed wire fence, 4 strands, bears S. 65° E. and N. 65° W.</p>
80.52	<p>The cor. of secs. 22, 23, 26 and 27.</p> <hr/>
	<p>N. 0°34' W., bet. secs. 22 and 23.</p> <p>Over rolling land.</p>
40.02	<p>Point for the 1/4 sec. cor. of secs. 22 and 23, at proportionate dist.; there is no remaining evidence of the original cor.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p>
	<p style="text-align: center;">T 22 N R 28 E 1/4 S 22 S 23</p> <p style="text-align: center;">2005</p>
	<p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p>
80.04	<p>Point for the cor. of secs. 14, 15, 22 and 23, at proportionate dist.; there is no remaining evidence of the original cor.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p>
	<p style="text-align: center;">T 22 N R 28 E S 15 S 14 S 22 S 23</p> <p style="text-align: center;">2005</p>
	<p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p> <hr/>
	<p>From the cor. of secs. 13, 14, 23 and 24.</p> <p>N. 88°26' W., bet. secs. 14 and 23.</p>

**Dependent Resurvey of the Subdivisional Lines,
T. 22 N., R. 28 E., Gila and Salt River Meridian, Arizona**

CHAINS	
	Over broken land.
24.30	Apache County Road C409, a graded road, 30 ft. wide, bears N. 15° E. and S. 15° W.
39.89	Point for the 1/4 sec. cor. of secs. 14 and 23, at proportionate dist.; there is no remaining evidence of the original cor. Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd. <div style="text-align: center;"> T 22 N R 28 E S 14 1/4 ——— S 23 2005 </div>
	Deposit a magnet, in a white plastic case, at the base of the stainless steel post.
79.78	The cor. of secs. 14, 15, 22 and 23. <hr/>
	N. 0°01' W., bet. secs. 14 and 15. Over rolling land.
31.50	Apache County Road C411, a graded road, 30 ft. wide, bears N. 85° E. and S. 85° W.
40.02	Point for the 1/4 sec. cor. of secs. 14 and 15, at proportionate dist.; there is no remaining evidence of the original cor. Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd. <div style="text-align: center;"> T 22 N R 28 E 1/4 S 15 S 14 2005 </div>
	Deposit a magnet, in a white plastic case, at the base of the stainless steel post.
80.04	Point for the cor. of secs. 10, 11, 14 and 15, at proportionate dist.; there is no remaining evidence of the original cor. Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.

Dependent Resurvey of the Subdivisional Lines,
T. 22 N., R. 28 E., Gila and Salt River Meridian, Arizona

CHAINS									
	<div style="text-align: center;"> <table border="1"> <tr> <td>T 22 N</td> <td>R 28 E</td> </tr> <tr> <td>S 10</td> <td>S 11</td> </tr> <tr> <td>S 15</td> <td>S 14</td> </tr> </table> <p>2005</p> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p> <p>Cor. is located 2.34 chs. S. of a trail road, bears N. 55° E. and S. 55° W.</p> <hr/> <p>From the cor. of secs. 11, 12, 13 and 14.</p> <p>N. 88°22' W., bet. secs. 11 and 14.</p> <p>Over rolling land.</p> </div>	T 22 N	R 28 E	S 10	S 11	S 15	S 14		
T 22 N	R 28 E								
S 10	S 11								
S 15	S 14								
39.78	<p>Point for the 1/4 sec. cor. of secs. 11 and 14, at proportionate dist.; there is no remaining evidence of the original cor.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center;"> <table border="1"> <tr> <td>T 22 N</td> <td>R 28 E</td> </tr> <tr> <td></td> <td>S 11</td> </tr> <tr> <td>1/4</td> <td>——</td> </tr> <tr> <td></td> <td>S 14</td> </tr> </table> <p>2005</p> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p> <p>Cor. is located 1.35 chs. S. of a trail road, bears N. 70° E. and S. 70° W.</p> </div>	T 22 N	R 28 E		S 11	1/4	——		S 14
T 22 N	R 28 E								
	S 11								
1/4	——								
	S 14								
79.56	<p>The cor. of secs. 10, 11, 14 and 15.</p> <hr/> <p>N. 0°13' E., bet. secs. 10 and 11.</p> <p>Over rolling land.</p>								
40.02	<p>Point for the 1/4 sec. cor. of secs. 10 and 11, at proportionate dist.; there is no remaining evidence of the original cor.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p>								

Dependent Resurvey of the Subdivisional Lines,
T. 22 N., R. 28 E., Gila and Salt River Meridian, Arizona

CHAINS	
80.04	<p style="text-align: center;">T 22 N R 28 E 1/4 S 10 S 11</p> <p style="text-align: center;">2005</p> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p> <p>Point for the cor. of secs. 2, 3, 10 and 11, at proportionate dist.; there is no remaining evidence of the original cor.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T 22 N R 28 E S 3 S 2 S 10 S 11</p> <p style="text-align: center;">2005</p> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p> <p>Cor. is located 1.00 ch. S. of a wash, 20 ft. wide, 3 ft. deep, drains S. 65° W.</p>
39.72	<hr/> <p>From the cor. of secs. 1, 2, 11 and 12.</p> <p>N. 88°18' W., bet. secs. 2 and 11.</p> <p>Over rolling land.</p> <p>Point for the 1/4 sec. cor. of secs. 2 and 11, at proportionate dist.; there is no remaining evidence of the original cor.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T 22 N R 28 E S 2 1/4 ——— S 11</p> <p style="text-align: center;">2005</p> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p> <p>Cor. is located 65 lks. E. of a barbed wire fence, 4 strands, bears S. 35° E. and N. 35° W.</p>

**Dependent Resurvey of the Subdivisional Lines,
T. 22 N., R. 28 E., Gila and Salt River Meridian, Arizona**

CHAINS	
52.49	Barbed wire fence, 4 strands, bears N. 35° E. and S. 35° W.
54.40	Trail road, bears N. 30° E. and S. 30° W.
79.44	The cor. of secs. 2, 3, 10 and 11.
	N. 0°01' W., bet. secs. 2 and 3.
	Over broken land.
40.02	Point for the 1/4 sec. cor. of secs. 2 and 3, at proportionate dist.; there is no remaining evidence of the original cor.
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.
	T 22 N R 28 E 1/4 S 3 S 2 2005
	Deposit a magnet, in a white plastic case, at the base of the stainless steel post.
79.90	The cor. of secs. 2, 3, 34 and 35, on the N. bdy. of the Tp., monumented with a stainless steel post, 2 1/2 ins. diam., firmly set, projecting 4 ins. above ground, with brass cap mkd. T23N R28E S34 S35 S3 S2 T22N 2002.
	From the cor. of secs. 3, 4, 33 and 34, on the S. bdy. of the Tp., monumented with a stainless steel post, 2 1/2 ins. diam., firmly set, projecting 3 ins. above ground, with brass cap mkd. T22N R28E S33 S34 S4 S3 T21N 1991, from which the 1991 bearing trees
	A forked juniper, 20 ins. diam. at base, bears N. 38 1/4° E., 2.70 chs. dist., mkd. T22N R28E S34 BT on partially healed blaze.
	A juniper, 16 ins. diam., bears S. 34 1/2° E., 2.49 chs. dist., mkd. T21N R28E S3 BT on partially healed blaze.
	A juniper, 10 ins. diam., bears S. 5 3/4° W., 1.215 chs. dist., mkd. T21N R28E S4 BT on partially healed blaze.
	A forked juniper, 13 ins. diam. at base, bears N. 44 1/4° W., 1.335 chs. dist., mkd T22N R28E S33 BT on partially healed blaze.
	Add the marks 2005 to the brass cap.

**Dependent Resurvey of the Subdivisional Lines,
T. 22 N., R. 28 E., Gila and Salt River Meridian, Arizona**

CHAINS	
	<p>N. 0°07' W., bet. secs. 33 and 34.</p> <p>Over rolling land.</p>
39.99	<p>Point for the 1/4 sec. cor. of secs. 33 and 34, at proportionate dist.; there is no remaining evidence of the original cor.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T 22 N R 28 E 1/4 S 33 S 34</p> <p style="text-align: center;">2005</p> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p>
79.98	<p>Point for the cor. of secs. 27, 28, 33 and 34, at proportionate dist.; there is no remaining evidence of the original cor.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T 22 N R 28 E S 28 S 27 S 33 S 34</p> <p style="text-align: center;">2005</p> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p> <hr/> <p>From the cor. of secs. 26, 27, 34 and 35.</p> <p>N. 88°02' W., bet. secs. 27 and 34.</p> <p>Over rolling land.</p>
40.18	<p>Point for the 1/4 sec. cor. of secs. 27 and 34, at proportionate dist.; there is no remaining evidence of the original cor.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p>

Dependent Resurvey of the Subdivisional Lines,
T. 22 N., R. 28 E., Gila and Salt River Meridian, Arizona

CHAINS	
	<p style="text-align: center;">T 22 N R 28 E S 27 1/4 ——— S 34</p> <p style="text-align: center;">2005</p>
80.36	<p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p> <p>The cor. of secs. 27, 28, 33 and 34.</p> <hr/>
	<p>N. 0°09' W., bet. secs. 27 and 28.</p> <p>Over rolling land.</p>
39.99	<p>Point for the 1/4 sec. cor. of secs. 27 and 28, at proportionate dist.; there is no remaining evidence of the original cor.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., flush with surface of the ground, with brass cap mkd.</p>
	<p style="text-align: center;">T 22 N R 28 E 1/4 S 28 S 27</p> <p style="text-align: center;">2005</p> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p> <p>Cor. is located in an abandoned trail road, bears East and West.</p>
79.98	<p>Point for the cor. of secs. 21, 22, 27 and 28, at proportionate dist.; there is no remaining evidence of the original cor.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p>
	<p style="text-align: center;">T 22 N R 28 E S 21 S 22 S 28 S 27</p> <p style="text-align: center;">2005</p> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p> <hr/>
	<p>From the cor. of secs. 22, 23, 26 and 27.</p> <p>N. 88°05' W., bet. secs. 22 and 27.</p>

**Dependent Resurvey of the Subdivisional Lines,
T. 22 N., R. 28 E., Gila and Salt River Meridian, Arizona**

CHAINS	
	Over rolling land.
40.23	Point for the 1/4 sec. cor. of secs. 22 and 27, at proportionate dist.; there is no remaining evidence of the original cor. Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd. <div style="text-align: center;"> T 22 N R 28 E S 22 1/4 ——— S 27 2005 </div>
	Deposit a magnet, in a white plastic case, at the base of the stainless steel post.
73.70	Graded road, 26 ft. wide, bears S. 65° E. and N. 65° W.
76.54	Barbed wire fence, 3 strands, bears S. 55° E. and N. 55° W.
80.46	The cor. of secs. 21, 22, 27 and 28. <hr style="width: 60%; margin-left: 0;"/> N. 0°32' W., bet. secs. 21 and 22. Over rolling land.
2.05	Barbed wire fence, 3 strands, bears S. 65° E. and N. 65° W.
2.90	Graded road, 26 ft. wide, bears S. 55° E. and N. 55° W.
39.99	Point for the 1/4 sec. cor. of secs. 21 and 22, at proportionate dist.; there is no remaining evidence of the original cor. Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd. <div style="text-align: center;"> T 22 N R 28 E 1/4 S 21 S 22 2005 </div>
	Deposit a magnet, in a white plastic case, at the base of the stainless steel post.
79.98	Point for the cor. of secs. 15, 16, 21 and 22, at proportionate dist.; there is no remaining evidence of the original cor. Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.

**Dependent Resurvey of the Subdivisional Lines,
T. 22 N., R. 28 E., Gila and Salt River Meridian, Arizona**

CHAINS	
	T 22 N R 28 E S 16 S 15 S 21 S 22 2005
	Deposit a magnet, in a white plastic case, at the base of the stainless steel post.
	<hr/> From the cor. of secs. 14, 15, 22 and 23. N. 88°08' W., bet. secs. 15 and 22. Over rolling land.
40.20	Point for the 1/4 sec. cor. of secs. 15 and 22, at proportionate dist.; there is no remaining evidence of the original cor. Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.
	T 22 N R 28 E S 15 1/4 ——— S 22 2005
	Deposit a magnet, in a white plastic case, at the base of the stainless steel post.
80.40	The cor. of secs. 15, 16, 21 and 22.
	<hr/> N. 0°26' E., bet. secs. 15 and 16. Over rolling land.
18.30	Apache County Road C411, a graded road, 26 ft. wide, N. 80° E. and N. 80° W.
39.99	Point for the 1/4 sec. cor. of secs. 15 and 16, at proportionate dist.; there is no remaining evidence of the original cor. Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.
	T 22 N R 28 E 1/4 S 16 S 15 2005

**Dependent Resurvey of the Subdivisional Lines,
T. 22 N., R. 28 E., Gila and Salt River Meridian, Arizona**

<p>CHAINS</p>	<p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p> <p>79.98 Point for the cor. of secs. 9, 10, 15 and 16, at proportionate dist.; there is no remaining evidence of the original cor.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <table style="margin-left: auto; margin-right: auto;"> <tr> <td>T 22 N</td> <td>R 28 E</td> </tr> <tr> <td>S 9</td> <td>S 10</td> </tr> <tr> <td>S 16</td> <td>S 15</td> </tr> </table> <p style="text-align: center;">2005</p> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p> <hr/> <p>From the cor. of secs. 10, 11, 14 and 15.</p> <p>N. 88°10' W., bet. secs. 10 and 15.</p> <p>Over rolling land.</p> <p>39.87 Point for the 1/4 sec. cor. of sec. 10 and 15, at proportionate dist.; there is no remaining evidence of the original cor.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <table style="margin-left: auto; margin-right: auto;"> <tr> <td>T 22 N</td> <td>R 28 E</td> </tr> <tr> <td></td> <td>S 10</td> </tr> <tr> <td>1/4</td> <td>_____</td> </tr> <tr> <td></td> <td>S 15</td> </tr> </table> <p style="text-align: center;">2005</p> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p> <p>Cor. is located 1.14 chs. E. of a trail road, bears N. 30° E. and S. 30° W.</p> <p>79.74 The cor. of secs. 9, 10, 15 and 16.</p> <hr/> <p>N. 0°12' E., bet. secs. 9 and 10.</p> <p>Over rolling land.</p> <p>10.70 Trail road, bears S. 45° E. and N. 45° W.</p>	T 22 N	R 28 E	S 9	S 10	S 16	S 15	T 22 N	R 28 E		S 10	1/4	_____		S 15
T 22 N	R 28 E														
S 9	S 10														
S 16	S 15														
T 22 N	R 28 E														
	S 10														
1/4	_____														
	S 15														

**Dependent Resurvey of the Subdivisional Lines,
T. 22 N., R. 28 E., Gila and Salt River Meridian, Arizona**

CHAINS	
39.99	<p>Point for the 1/4 sec. cor. of secs. 9 and 10, at proportionate dist.; there is no remaining evidence of the original cor.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T 22 N R 28 E 1/4 S 9 S 10</p> <p style="text-align: center;">2005</p> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p>
79.98	<p>Point for the cor. of secs. 3, 4, 9 and 10, at proportionate dist.; there is no remaining evidence of the original cor.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T 22 N R 28 E S 4 S 3 ----- S 9 S 10</p> <p style="text-align: center;">2005</p> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p> <hr/> <p>From the cor. of secs. 2, 3, 10 and 11.</p> <p>N. 88°13' W., bet. secs. 3 and 10.</p> <p>Over rolling land.</p>
39.87	<p>Point for the 1/4 sec. cor. of secs. 3 and 10, at proportionate dist.; there is no remaining evidence of the original cor.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T 22 N R 28 E S 3 1/4 ——— S 10</p> <p style="text-align: center;">2005</p> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p>

**Dependent Resurvey of the Subdivisional Lines,
T. 22 N., R. 28 E., Gila and Salt River Meridian, Arizona**

CHAINS	
79.74	<p>The cor. of secs. 3, 4, 9 and 10.</p> <hr/> <p>N. 0°04' W., bet. secs. 3 and 4.</p> <p>Over rolling land.</p>
39.99	<p>Point for the 1/4 sec. cor. of secs. 3 and 4, at proportionate dist.; there is no remaining evidence of the original cor.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T 22 N R 28 E 1/4 S 4 S 3 2005</p> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p>
80.14	<p>The cor. of secs. 3, 4, 33 and 34, on the N. bdy. of the Tp., monumented with a stainless steel post, 2 1/2 ins. diam., firmly set, projecting 4 ins. above ground, with brass cap mkd. T23N R28E S33 S34 S4 S3 T22N 2003.</p> <hr/> <p>From the cor. of secs. 4, 5, 32 and 33, on the S. bdy. of the Tp., monumented with a stainless steel post, 2 1/2 ins. diam., firmly set, projecting 1 in. above ground, with brass cap mkd. T22N R28E S32 S33 S5 S4 T21N 1991, from which the 1991 bearing trees</p> <p style="padding-left: 40px;">A forked juniper, 26 ins. diam. at base, bears N. 87° E., 79 lks. dist., mkd. T22N R28E S33 BT on partially healed blaze.</p> <p style="padding-left: 40px;">A forked juniper, 16 ins. diam. at base, bears S. 58 1/2° E., 1.07 chs. dist., mkd. T21N R28E S4 BT on partially healed blaze.</p> <p style="padding-left: 40px;">A forked juniper, 24 ins. diam. at base, bears S. 33° W., 49 1/2 lks. dist., mkd. T21N R28E S5 BT on partially healed blaze.</p> <p style="padding-left: 40px;">A juniper, 10 ins. diam., bears N. 42 1/4° W., 1.515 chs. dist., mkd. T22N R28E S32 BT on partially healed blaze.</p> <p>Add the marks 2005 to the brass cap.</p> <p>N. 0°14' W., bet. secs. 32 and 33.</p>

**Dependent Resurvey of the Subdivisional Lines,
T. 22 N., R. 28 E., Gila and Salt River Meridian, Arizona**

CHAINS	
	Over rolling land.
39.97	<p>Point for the 1/4 sec. cor. of secs. 32 and 33, at proportionate dist.; there is no remaining evidence of the original cor.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T 22 N R 28 E 1/4 S 32 S 33</p> <p style="text-align: center;">2005</p> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p>
79.94	<p>Point for the cor. of secs. 28, 29, 32 and 33, at proportionate dist.; there is no remaining evidence of the original cor.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T 22 N R 28 E S 29 S 28 S 32 S 33</p> <p style="text-align: center;">2005</p> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p> <hr/> <p>From the cor. of secs. 27, 28, 33 and 34.</p> <p>N. 88°01' W., bet. secs. 28 and 33.</p> <p>Over rolling land.</p>
40.30	<p>Point for the 1/4 sec. cor. of secs. 28 and 33, at proportionate dist.; there is no remaining evidence of the original cor.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T 22 N R 28 E S 28 1/4 ——— S 33</p> <p style="text-align: center;">2005</p>

**Dependent Resurvey of the Subdivisional Lines,
T. 22 N., R. 28 E., Gila and Salt River Meridian, Arizona**

CHAINS	
	<p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p> <p>Cor. is located 1.45 chs. E. of a trail road, bears S. 35° E. and N. 35° W.</p>
80.60	<p>The cor. of secs. 28, 29, 32 and 33.</p> <hr/> <p>N. 0°05' E., bet. secs. 28 and 29.</p> <p>Over rolling land.</p>
39.97	<p>Point for the 1/4 sec. cor. of secs. 28 and 29, at proportionate dist.; there is no remaining evidence of the original cor.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center;"> <p>T 22 N R 28 E 1/4 S 29 S 28</p> <p>2005</p> </div> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p>
79.94	<p>Point for the cor. of secs. 20, 21, 28 and 29, at proportionate dist.; there is no remaining evidence of the original cor.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center;"> <p>T 22 N R 28 E S 20 S 21 S 29 S 28</p> <p>2005</p> </div> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p> <hr/> <p>From the cor. of secs. 21, 22, 27 and 28.</p> <p>N. 88°02' W., bet. secs. 21 and 28.</p> <p>Over rolling land.</p>
33.99	<p>Barbed wire fence, 3 strands, bears N. 50° E. and S. 50° W.</p>
34.30	<p>Trail road, bears N. 50° E. and S. 50° W.</p>

**Dependent Resurvey of the Subdivisional Lines,
T. 22 N., R. 28 E., Gila and Salt River Meridian, Arizona**

CHAINS	
40.13	<p>Point for the 1/4 sec. cor. of secs. 21 and 28, at proportionate dist.; there is no remaining evidence of the original cor.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center;"> <p>T 22 N R 28 E</p> <p>S 21</p> <p>1/4 ———</p> <p>S 28</p> <p>2005</p> </div> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p>
80.26	<p>The cor. of secs. 20, 21, 28 and 29.</p> <hr/> <p>N. 0°03' E., bet. secs. 20 and 21.</p> <p>Over rolling land.</p>
39.97	<p>Point for the 1/4 sec. cor. of secs. 20 and 21, at proportionate dist.; there is no remaining evidence of the original cor.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center;"> <p>T 22 N R 28 E</p> <p>1/4</p> <p>S 20 S 21</p> <p>2005</p> </div> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p>
58.50	<p>Graded road, 26 ft. wide, bears S. 60° E. and N. 60° W.</p>
79.94	<p>Point for the cor. of secs. 16, 17, 20 and 21, at proportionate dist.; there is no remaining evidence of the original cor.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center;"> <p>T 22 N R 28 E</p> <p>S 17 S 16</p> <p>—————</p> <p>S 20 S 21</p> <p>2005</p> </div>

**Dependent Resurvey of the Subdivisional Lines,
T. 22 N., R. 28 E., Gila and Salt River Meridian, Arizona**

CHAINS	
	<p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p> <hr/> <p>From the cor. of secs. 15, 16, 21 and 22.</p> <p>N. 88°02' W., bet. secs. 16 and 21.</p> <p>Over rolling land.</p>
39.71	<p>Point for the 1/4 sec. cor. of secs. 16 and 21, at proportionate dist.; there is no remaining evidence of the original cor.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T 22 N R 28 E S 16 1/4 ——— S 21</p> <p style="text-align: center;">2005</p> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p> <p>Cor. is located 56 lks. W. of a trail road, bears N. 40° E. and S. 40° W.</p>
79.42	<p>The cor. of secs. 16, 17, 20 and 21.</p> <hr/> <p>N. 0°18' E., bet. secs. 16 and 17.</p> <p>Over rolling land.</p>
4.90	<p>Apache County Road C411, a graded road, 26 ft. wide, bears N. 80° E. and S. 80° E.</p>
39.97	<p>Point for the 1/4 sec. cor. of secs. 16 and 17, at proportionate dist.; there is no remaining evidence of the original cor.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T 22 N R 28 E 1/4 S 17 S 16</p> <p style="text-align: center;">2005</p> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p>

**Dependent Resurvey of the Subdivisional Lines,
T. 22 N., R. 28 E., Gila and Salt River Meridian, Arizona**

CHAINS									
79.94	<p>Point for the cor. of secs. 8, 9, 16 and 17, at proportionate dist.; there is no remaining evidence of the original cor.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center;"> <table style="margin: auto;"> <tr> <td>T 22 N</td> <td>R 28 E</td> </tr> <tr> <td>S 8</td> <td>S 9</td> </tr> <tr> <td>S 17</td> <td>S 16</td> </tr> </table> <p>2005</p> </div> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p> <hr/> <p>From the cor. of secs. 9, 10, 15 and 16.</p> <p>N. 88°04' W., bet. secs. 9 and 16.</p> <p>Over rolling land.</p>	T 22 N	R 28 E	S 8	S 9	S 17	S 16		
T 22 N	R 28 E								
S 8	S 9								
S 17	S 16								
39.80	<p>Point for the 1/4 sec. cor. of secs. 9 and 16, at proportionate dist.; there is no remaining evidence of the original cor.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center;"> <table style="margin: auto;"> <tr> <td>T 22 N</td> <td>R 28 E</td> </tr> <tr> <td>S 9</td> <td></td> </tr> <tr> <td>1/4</td> <td>—</td> </tr> <tr> <td>S 16</td> <td></td> </tr> </table> <p>2005</p> </div> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p>	T 22 N	R 28 E	S 9		1/4	—	S 16	
T 22 N	R 28 E								
S 9									
1/4	—								
S 16									
79.60	<p>The cor. of secs. 8, 9, 16 and 17.</p> <hr/> <p>N. 0°09' W., bet. secs. 8 and 9.</p> <p>Over rolling land.</p>								
39.97	<p>Point for the 1/4 sec. cor. of secs. 8 and 9, at proportionate dist.; there is no remaining evidence of the original cor.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p>								

Dependent Resurvey of the Subdivisional Lines,
T. 22 N., R. 28 E., Gila and Salt River Meridian, Arizona

CHAINS	
	<p style="text-align: center;">T 22 N R 28 E 1/4 S 8 S 9 2005</p>
79.94	<p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p> <p>Point for the cor. of secs. 4, 5, 8 and 9, at proportionate dist.; there is no remaining evidence of the original cor.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T 22 N R 28 E S 5 S 4 S 8 S 9 2005</p> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p>
	<hr/> <p>From the cor. of secs. 3, 4, 9 and 10.</p> <p>N. 88°06' W., bet. secs. 4 and 9. Over rolling land.</p>
40.04	<p>Point for the 1/4 sec. cor. of secs. 4 and 9, at proportionate dist.; there is no remaining evidence of the original cor.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T 22 N R 28 E S 4 1/4 ——— S 9 2005</p>
53.95	<p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p> <p>Trail road, bears S. 30° E. and N. 30° W.</p>
80.08	<p>The cor. of secs. 4, 5, 8 and 9.</p> <hr/> <p>N. 0°08' E., bet. secs. 4 and 5.</p>

**Dependent Resurvey of the Subdivisional Lines,
T. 22 N., R. 28 E., Gila and Salt River Meridian, Arizona**

CHAINS	
39.97	<p>Over rolling land.</p> <p>Point for the 1/4 sec. cor. of secs. 4 and 5, at proportionate dist.; there is no remaining evidence of the original cor.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center;"> <p>T 22 N R 28 E</p> <p>1/4</p> <p>S 5 S 4</p> <p>2005</p> </div> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p>
80.21	<p>The cor. of secs. 4, 5, 32 and 33, on the N. bdy. of the Tp., monumented with a stainless steel post, 2 1/2 ins. diam., firmly set, projecting 4 ins. above ground, with brass cap mkd. T23N R28E S32 S33 S5 S4 T22N 2003.</p> <hr/> <p>From the cor. of secs. 5, 6, 31 and 32, on the S. bdy. of the Tp., monumented with a magnet, in a white plastic case, set 24 ins. below the surface of the ground.</p> <p>At the corner point</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center;"> <p>T 22 N R 28 E</p> <p>S 31 S 32</p> <hr style="width: 50%; margin: 0 auto;"/> <p>S 6 S 5</p> <p>T 21 N</p> <p>2005</p> </div> <p>from which the remaining 1991 bearing trees</p> <p style="margin-left: 40px;">A juniper, 14 ins. diam., bears N. 58° E., 2.795 chs. dist., mkd. T22N R28E S32 BT on partially healed blaze.</p> <p style="margin-left: 40px;">A juniper, 6 ins. diam., bears S. 59 1/4° E., 2.09 chs. dist., mkd. T21N R28E S5 BT on partially healed blaze.</p> <p style="margin-left: 40px;">A juniper, 21 ins. diam., bears N. 21° W., 4.88 chs. dist., mkd. T22N R28E S31 BT on partially healed blaze.</p> <p>N. 0°11' E., bet. secs. 31 and 32.</p>

**Dependent Resurvey of the Subdivisional Lines,
T. 22 N., R. 28 E., Gila and Salt River Meridian, Arizona**

CHAINS	
	Over rolling land.
39.93	Point for the 1/4 sec. cor. of secs. 31 and 32, at proportionate dist.; there is no remaining evidence of the original cor. Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd. <div style="text-align: center;"> T 22 N R 28 E 1/4 S 31 S 32 2005 </div>
79.86	Deposit a magnet, in a white plastic case, at the base of the stainless steel post. Point for the cor. of secs. 29, 30, 31 and 32, at proportionate dist.; there is no remaining evidence of the original cor. Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd. <div style="text-align: center;"> T 22 N R 28 E S 30 S 29 S 31 S 32 2005 </div>
	Deposit a magnet, in a white plastic case, at the base of the stainless steel post.
	From the cor. of secs. 28, 29, 32 and 33. N. 87°38' W., bet. secs. 29 and 32. Over rolling land.
29.70	Trail road, bears S. 65° E. and N. 65° W.
40.12	Point for the 1/4 sec. cor. of secs. 29 and 32, at proportionate dist.; there is no remaining evidence of the original cor. Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd. <div style="text-align: center;"> T 22 N R 28 E S 29 1/4 ——— S 32 2005 </div>

**Dependent Resurvey of the Subdivisional Lines,
T. 22 N., R. 28 E., Gila and Salt River Meridian, Arizona**

CHAINS	
	<p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p> <p>Cor. is located 1.23 chs. W. of a trail road, bears N. 50° E. and S. 50° W.</p>
80.24	<p>The cor. of secs. 29, 30, 31 and 32.</p> <hr/> <p>N. 88°28' W., bet. secs. 30 and 31.</p> <p>Over rolling land.</p>
31.06	<p>Woven wire fence with 1 strand barbed wire, bears S. 25° E. and N. 25° W.</p>
40.20	<p>Point for the 1/4 sec. cor. of secs. 30 and 31, at proportionate dist.; there is no remaining evidence of the original cor.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center;"> <p>T 22 N R 28 E</p> <p>S 30</p> <p>1/4 ———</p> <p>S 31</p> <p>2005</p> </div>
	<p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p> <p>Cor. is located 24 lks. E. of a trail road, bears N. 55° E. and S. 55° W. and 90 lks. W. of woven wire fence with 1 strand barbed wire, bears S. 15° E. and N. 15° W.</p>
79.21	<p>The cor. of secs. 25, 30, 31 and 36, on the W. bdy. of the Tp., monumented with a stainless steel post, 2 1/2 ins. diam., firmly set, projecting 4 ins. above ground, with brass cap mkd. T22N R27E R28E S25 S30 S36 S31 2003.</p> <hr/> <p>From the cor. of secs. 29, 30, 31 and 32.</p> <p>North, bet. secs. 29 and 30.</p> <p>Over rolling land.</p>
39.93	<p>Point for the 1/4 sec. cor. of secs. 29 and 30, at proportionate dist.; there is no remaining evidence of the original cor.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p>

**Dependent Resurvey of the Subdivisional Lines,
T. 22 N., R. 28 E., Gila and Salt River Meridian, Arizona**

CHAINS	
	T 22 N R 28 E 1/4 S 30 S 29 2005
	Deposit a magnet, in a white plastic case, at the base of the stainless steel post.
79.86	Point for the cor. of secs. 19, 20, 29 and 30, at proportionate dist.; there is no remaining evidence of the original cor. Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.
	T 22 N R 28 E S 19 S 20 S 30 S 29 2005
	Deposit a magnet, in a white plastic case, at the base of the stainless steel post.
	<hr/> From the cor. of secs. 20, 21, 28 and 29. N. 87°42' W., bet. secs. 20 and 29. Over rolling land.
40.16	Point for the 1/4 sec. cor. of secs. 20 and 29, at proportionate dist.; there is no remaining evidence of the original cor. Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.
	T 22 N R 28 E S 20 1/4 ——— S 29 2005
	Deposit a magnet, in a white plastic case, at the base of the stainless steel post.
80.32	The cor. of secs. 19, 20, 29 and 30.
	<hr/> N. 88°22' W., bet. secs. 19 and 30. Over rolling land.

**Dependent Resurvey of the Subdivisional Lines,
T. 22 N., R. 28 E., Gila and Salt River Meridian, Arizona**

CHAINS	
40.18	<p>Point for the 1/4 sec. cor. of secs. 19 and 30, at proportionate dist.; there is no remaining evidence of the original cor.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T 22 N R 28 E S 19 1/4 ——— S 30</p> <p style="text-align: center;">2005</p> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p> <p>Cor. is located 28 lks. W. of a trail road, bears N. 5° E. and S. 5° W.</p>
79.00	<p>The cor. of secs. 19, 24, 25 and 30, on the W. bdy. of the Tp., monumented with a stainless steel post, 2 1/2 ins. diam., firmly set, projecting 4 ins. above ground, with brass cap mkd. T22N R27E R28E S24 S19 S25 S30 2003.</p> <hr/> <p>From the cor. of secs. 19, 20, 29 and 30.</p> <p>N. 0°13' E., bet. secs. 19 and 20.</p> <p>Over rolling land.</p>
39.93	<p>Point for the 1/4 sec. cor. of secs. 19 and 20, at proportionate dist.; there is no remaining evidence of the original cor.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T 22 N R 28 E 1/4 S 19 S 20</p> <p style="text-align: center;">2005</p> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p>
70.50	<p>Apache County Road C411, a graded road, 20 ft. wide, bears N. 80° E. and N. 80° W.</p>
79.86	<p>Point for the cor. of secs. 17, 18, 19 and 20, at proportionate dist.; there is no remaining evidence of the original cor.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p>

**Dependent Resurvey of the Subdivisional Lines,
T. 22 N., R. 28 E., Gila and Salt River Meridian, Arizona**

CHAINS	
	T 22 N R 28 E S 18 S 17 S 19 S 20 2005
	Deposit a magnet, in a white plastic case, at the base of the stainless steel post.
	<hr/> From the cor. of secs. 16, 17, 20 and 21. N. 87°45' W., bet. secs. 17 and 20. Over rolling land.
27.80	Apache County Road C411, a graded road, 26 ft. wide, bears N. 80° E. and S. 80° W.
40.04	Point for the 1/4 sec. cor. of secs. 17 and 20, at proportionate dist.; there is no remaining evidence of the original cor. Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.
	T 22 N R 28 E S 17 1/4 ——— S 20 2005
	Deposit a magnet, in a white plastic case, at the base of the stainless steel post.
44.20	Graded road, 26 ft. wide, bears S. 65° E. and N. 65° W.
80.08	The cor. of secs. 17, 18, 19 and 20.
	<hr/> N. 88°16' W., bet. secs. 18 and 19. Over rolling land.
30.50	Trail road, bears N. 5° E. and S. 5° W.
39.96	Point for the 1/4 sec. cor. of secs. 18 and 19, at proportionate dist.; there is no remaining evidence of the original cor. Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.

Dependent Resurvey of the Subdivisional Lines,
T. 22 N., R. 28 E., Gila and Salt River Meridian, Arizona

CHAINS	
	<p style="text-align: center;">T 22 N R 28 E S 18 1/4 ——— S 19</p> <p style="text-align: center;">2005</p>
79.08	<p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p> <p>The cor. of secs. 13, 18, 19 and 24, on the W. bdy. of the Tp., monumented with a stainless steel post, 2 1/2 ins. diam., firmly set, projecting 4 ins. above ground, with brass cap mkd. T22N R27E R28E S13 S18 S24 S19 2003.</p>
	<p>From the cor. of secs. 17, 18, 19 and 20.</p> <p>N. 0°14' E., bet. secs. 17 and 18.</p> <p>Over rolling land.</p>
19.50	<p>Graded road, 20 ft. wide, bears S. 60° E. and N. 60° W.</p>
39.93	<p>Point for the 1/4 sec. cor. of secs. 17 and 18, at proportionate dist.; there is no remaining evidence of the original cor.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p>
	<p style="text-align: center;">T 22 N R 28 E 1/4 S 18 S 17</p> <p style="text-align: center;">2005</p> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p>
79.86	<p>Point for the cor. of secs. 7, 8, 17 and 18, at proportionate dist.; there is no remaining evidence of the original cor.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p>
	<p style="text-align: center;">T 22 N R 28 E S 7 S 8 S 18 S 17</p> <p style="text-align: center;">2005</p>

**Dependent Resurvey of the Subdivisional Lines,
T. 22 N., R. 28 E., Gila and Salt River Meridian, Arizona**

CHAINS	
	<p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p> <hr/> <p>From the cor. of secs. 8, 9, 16 and 17.</p> <p>N. 87°48' W., bet. secs. 8 and 17.</p> <p>Over rolling land.</p>
40.08	<p>Point for the 1/4 sec. cor. of secs. 8 and 17, at proportionate dist.; there is no remaining evidence of the original cor.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center;"> <p>T 22 N R 28 E</p> <p>S 8</p> <p>1/4 ———</p> <p>S 17</p> <p>2005</p> </div> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p>
80.16	<p>The cor. of secs. 7, 8, 17 and 18.</p> <hr/> <p>N. 88°10' W., bet. secs. 7 and 18.</p> <p>Over rolling land.</p>
39.89	<p>Point for the 1/4 sec. cor. of secs. 7 and 18, at proportionate dist.; there is no remaining evidence of the original cor.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center;"> <p>T 22 N R 28 E</p> <p>S 7</p> <p>1/4 ———</p> <p>S 18</p> <p>2005</p> </div> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p>
49.80	<p>Trail road, bears S. 40° E. and N. 40° W.</p>

**Dependent Resurvey of the Subdivisional Lines,
T. 22 N., R. 28 E., Gila and Salt River Meridian, Arizona**

CHAINS	
79.19	<p>The cor. of secs. 7, 12, 13 and 18, on the W. bdy. of the Tp., monumented with a stainless steel post, 2 1/2 ins. diam., firmly set, projecting 4 ins. above ground, with brass cap mkd. T22N R27E R28E S12 S7 S13 S18 2003.</p> <hr/> <p>From the cor. of secs. 7, 8, 17 and 18.</p> <p>N. 0°09' E., bet. secs. 7 and 8.</p> <p>Over rolling land.</p>
39.93	<p>Point for the 1/4 sec. cor. of secs. 7 and 8, at proportionate dist.; there is no remaining evidence of the original cor.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T 22 N R 28 E 1/4 S 7 S 8 2005</p> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p>
71.78	<p>Barbed wire fence, 5 strands, bears N. 15° E. and S. 15° W.</p>
79.86	<p>Point for the cor. of secs. 5, 6, 7 and 8, at proportionate dist.; there is no remaining evidence of the original cor.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T 22 N R 28 E S 6 S 5 S 7 S 8 2005</p> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p> <hr/> <p>From the cor. of secs. 4, 5, 8 and 9.</p> <p>N. 87°51' W., bet. secs. 5 and 8.</p> <p>Over rolling land.</p>
39.86	<p>Point for the 1/4 sec. cor. of secs. 5 and 8, at proportionate dist.; there is on remaining evidence of the original cor.</p>

**Dependent Resurvey of the Subdivisional Lines,
T. 22 N., R. 28 E., Gila and Salt River Meridian, Arizona**

CHAINS	
	<p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T 22 N R 28 E S 5 1/4 ——— S 8</p> <p style="text-align: center;">2005</p> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p>
79.72	<p>The cor. of secs. 5, 6, 7 and 8.</p> <hr/> <p>N. 88°05' W., bet. secs. 6 and 7.</p> <p>Over rolling land.</p>
27.64	<p>Woven wire fence with 1 strand barbed wire, bears S. 75° E. and N. 75° W.</p>
39.93	<p>Point for the 1/4 sec. cor. of secs. 6 and 7, at proportionate dist.; there is no remaining evidence of the original cor.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., flush with surface of the ground, with brass cap mkd.</p> <p style="text-align: center;">T 22 N R 28 E S 6 1/4 ——— S 7</p> <p style="text-align: center;">2005</p> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p> <p>Cor. is located on the SE edge of a trail road, bears N. 30° E. and S. 30° W.</p>
79.16	<p>The cor. of secs. 1, 6, 7 and 12, on the W. bdy. of the Tp., monumented with a stainless steel post, 2 1/2 ins. diam., firmly set, projecting 4 ins. above ground, with brass cap mkd. T22N R27E R28E S1 S6 S12 S7 2003.</p> <hr/> <p>From the cor. of secs. 5, 6, 7 and 8.</p> <p>N. 0°04' E., bet. secs. 5 and 6.</p> <p>Over rolling land.</p>

**Dependent Resurvey of the Subdivisional Lines,
T. 22 N., R. 28 E., Gila and Salt River Meridian, Arizona**

CHAINS	
39.93	<p>Point for the 1/4 sec. cor. of secs. 5 and 6, at proportionate dist.; there is no remaining evidence of the original cor.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T 22 N R 28 E 1/4 S 6 S 5</p> <p style="text-align: center;">2005</p> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p>
73.11	Barbed wire fence, 5 strands, bears N. 75° E. and S. 75° W.
75.20	Apache County Road C322, a graded road, 15 ft. wide, bears N. 85° E. and S. 85° W.
79.96	<p>The cor. of secs, 5, 6, 31 and 32, on the N. bdy. of the Tp., monumented with a stainless steel post, 2 1/2 ins. diam., firmly set, projecting 4 ins. above ground, with brass cap mkd. T23N R28E S31 S32 S6 S5 T22N 2003.</p> <hr/>

T. 22 N., R. 28 E., Gila and Salt River Meridian, Arizona

CHAINS

GENERAL DESCRIPTION

The area resurveyed is within the Navajo Indian Reservation, approximately 3 miles north of Sanders, Arizona. The terrain is rolling in the western portion of the township with the eastern portion being rolling with broken badlands along the slope of a mesa. The drainage is to the southeast, with Burntwater Wash, outside the township and paralleling the east boundary, being the principal drainage.

The elevation varies from 6000 to 6800 feet above sea level. The soil is sand and sandy clay. The vegetation principally consists of rabbit brush, cacti, sagebrush and native grasses. The timber consist of piñon and juniper, ranging from sparse to moderate.

Principal access to the township is provided by U. S. Highway 191, which runs north and south, outside the township and paralleling the west boundary. From this highway there are two Apache County roads, branching off into the township with several other graded roads and numerous trail roads throughout the township. Much of the area is used for grazing livestock. There are numerous permanent residential homes throughout the township. There is no mining activity in the area.

The mean magnetic declination of 11° E. was derived from the computer program GEOMAGIX, utilizing the World Magnetic Model for Epoch 2005 for the dates of survey.

CERTIFICATE OF SURVEY

I, Jones Curtiss, Cadastral Surveyor, HEREBY CERTIFY upon honor, that in pursuance of special instructions bearing date of the 13th day of April, 2005, I have dependently resurveyed the subdivisonal lines of T. 22 N., R. 28 E., of the Gila and Salt River Meridian, in the State of Arizona, which are represented in the foregoing field notes as having been executed by me and under my direction. Said survey has been made in strict conformity with said special instructions, the Manual of Instructions for the Survey of the Public Lands of the United States, 1973, and in specific manner described in the foregoing field notes.

July 7, 2006
(Date)

Jones Curtiss
(Cadastral Surveyor)

CERTIFICATE OF APPROVAL

BUREAU OF LAND MANAGEMENT
Phoenix, Arizona

The foregoing field notes of the dependent resurvey of the subdivisonal lines, T. 22 N., R. 28 E., Gila and Salt River Meridian, in the State of Arizona, executed by Jones Curtiss, Cadastral Surveyor, having been critically examined and found correct, are hereby approved.

October 2, 2006
(Date)

Stephen K. Hansen
(Chief Cadastral Surveyor of Arizona)

~~CERTIFICATE OF TRANSCRIPT~~

~~I CERTIFY That the foregoing transcript of the field notes of the above described surveys in T. 22 N., R. 28 E., Gila and Salt River Meridian, Arizona, is a true copy of the original field notes.~~

~~_____~~
~~(Date)~~

~~_____~~
~~(Chief Cadastral Surveyor of Arizona)~~