

ORIGINAL

**UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT**

FIELD NOTES
OF THE
DEPENDENT RESURVEY OF THE
EIGHTH STANDARD PARALLEL NORTH (NORTH BOUNDARY),
A PORTION OF THE SOUTH BOUNDARY, THE WEST BOUNDARY
AND THE SUBDIVISIONAL LINES
AND THE SUBDIVISION OF CERTAIN SECTIONS,
TOWNSHIP 32 NORTH, RANGE 10 EAST,
OF THE GILA AND SALT RIVER MERIDIAN,
IN THE STATE OF ARIZONA

EXECUTED BY

W. William Foster, Cadastral Surveyor

Under Special Instructions dated December 15, 2005, approved December 15, 2005, which provided for the surveys included under Group No. 975, and assignment instructions dated December 15, 2005.

Survey commenced February 21, 2006

Survey completed May 10, 2006

INDEX DIAGRAM

TOWNSHIP 32 NORTH RANGE 10 EAST
 GILA AND SALT RIVER MERIDIAN, ARIZONA

EIGHTH STANDARD PARALLEL NORTH

8	7	6	6	4	4
18 6 66	5 54	4 44	3 36	2 27	1
65	65	53	44	36	27
17 7 64	8 52	9 43	10 35	11 26	12
63	63	51	43	34	26
16 18 62	17 50	16 42	15 33	14 25	13
61	61	50	41	33	24
15 19 60	20 49	21 41	22 32	23 23	24
59	59	48	40	31	23
14 30 58	29 48	28 39	27 30	26 22	25
57	56	47	39	30	21
13 31 55	32 46	33 38	34 29	35 20	36
12	11	10	10		

Subdivision of Sections 1 thru 4.....Pages 68-72

Subdivision of Sections 7 thru 12.....Pages 72-77

Subdivision of Sections 13 thru 15.....Pages 77-79

Subdivision of Sections 23 thru 24.....Pages 79-81

Subdivision of Sections 29 thru 30.....Pages 81-82

Subdivision of Sections 31 thru 34.....Pages 82-85

T. 32 N., R. 10 E., Gila and Salt River Meridian, Arizona

CHAINS

The following field notes describe the dependent resurvey of the Eighth Standard Parallel North (north boundary), a portion of the south boundary, the west boundary and the subdivisional lines and the subdivision of certain sections, Township 32 North, Range 10 East, Gila and Salt River Meridian, Arizona.

The history of surveys pertaining to this survey is as follows:

Philip Contzen surveyed the Eighth Standard Parallel North (south boundary), Townships 33 North, Ranges 9, 10 and 11 East, the west boundary, Township 32 North, Range 11 East and the south and west boundaries and the subdivisional lines, Township 32 North, Range 10 East, in 1905. L. W. Murphy dependently resurveyed a portion of the west boundary, Township 32 North, Range 11 East, in 1962. Daniel N. Patterson dependently resurveyed a portion of the north boundary, Township 31 North, Range 10 East, in 1988. William F. Olver and Daniel N. Patterson dependently resurveyed a portion of the west boundary, Township 32 North, Range 11 East, in 1988-90. Robin T. Mathews remonumented the southeast township corner, Township 32 North, Range 9 East, in 1990. Stephen K. Hansen dependently resurveyed a portion of the subdivisional lines, Township 31 North, Range 10 East, in 1997. W. William Foster dependently resurveyed the Eighth Standard Parallel North (north boundary) and a portion of the west boundary, Township 32 North, Range 11 East, concurrently under Group No. 969, Arizona.

Note: The sections that were not subdivided are for the most part or entirely within the Bennett Freeze Area, ongoing litigation at the time of this resurvey.

The survey was executed in accordance with the specifications as set forth in the Manual of Instructions for the Survey of the Public Lands of the United States, 1973, and the Special Instructions dated December 15th, 2005, for Group No. 975, Arizona.

The true meridian direction and length of all lines were determined by real time kinematic global positioning system observations using Trimble Navigation 5700 model receivers.

Preliminary to the resurvey, the lines of the prior surveys were retraced and search was made for all corners and other calls of record. Identified corners were remonumented in their original positions. Lost corners were reestablished and remonumented at proportionate positions based on the official record. The retracement data were thoroughly verified and only the true line field notes are given herein.

Geodetic control was derived from first order National Geodetic Survey triangulation station "T32N R11E 1/4 SECS. 28 33", as published by the National Geodetic Survey. The NAD 83 (1992) geographic position of the corner of sections 19, 24, 25 and 30, Townships 32 North, Ranges 10 and 11 East, is as follows:

T. 32 N., R. 10 E., Gila and Salt River Meridian, Arizona

CHAINS	
	<p>Latitude: 36°07'59.14" N. Longitude: 111°15'55.59" W.</p> <p>The mean magnetic declination is 11 3/4°.</p> <hr/> <p>Dependent Resurvey of the Eighth Standard Parallel North (N. Bdy.), T. 32 N., R. 10 E., Gila and Salt River Meridian, Arizona</p> <hr/> <p>Restoring the survey executed by Philip Contzen, in 1905</p> <hr/> <p>Beginning at the stan. 1/4 sec. cor. of sec. 36, T. 33 N., R. 10 E., monumented with a brass tablet, 3 1/4 ins. diam., cemented in solid rock, with top mkd. SC T33N R10E 1/4 S36 2006.</p> <p>N. 89°56' W., on the S. bdy. of sec. 36, T. 33 N., R. 10 E.</p> <p>Over rolling, sandy terrain, through scattered native grasses and cacti.</p>
14.33	Trail road, bears N. 35° E. and S. 35° W.
39.96	<p>Point for the stan. cor. of secs. 35 and 36, at proportionate dist., there is no remaining evidence of the orig. cor.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 25 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">SC T 33 N R 10 E S 35 S 36</p> <p style="text-align: center;">2006</p> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p> <hr/> <p>N. 89°56' W., on the S. bdy. of sec. 35, T. 33 N., R. 10 E.</p> <p>Over rolling, sandy terrain, through scattered native grasses and cacti.</p>
21.02	<p>The closing cor. of secs. 1 and 2, T. 32 N., R. 10 E., monumented with a limestone, 16 x 6 x 2 ins., firmly set, 12 ins. below the surface of the ground, mkd. CC on the S. face, 1 groove on the E. face and 5 grooves on the W. face.</p> <p>At the corner point</p>

Dependent Resurvey of the Eighth Standard Parallel North (N. Bdy.),
T. 32 N., R. 10 E., Gila and Salt River Meridian, Arizona

CHAINS	
	<p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T 33 N R 10 E S 35 ----- S 2 S 1 T 32 N R 10 E CC</p> <p style="text-align: center;">2006</p> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p> <p>Deposit the mkd. stone alongside the stainless steel post.</p>
39.96	<p>Point for the stan. 1/4 sec. cor. of sec. 35, at proportionate dist., there is no remaining evidence of the orig. cor.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 25 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">SC T 33 N R 10 E 1/4 S 35 -----</p> <p style="text-align: center;">2006</p> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p>
60.44	<p>Trail road, bears N. 15° E. and S. 15° W.</p>
79.92	<p>Point for the stan. cor. of secs. 34 and 35, at proportionate dist., there is no remaining evidence of the orig. cor.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 25 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">SC T 33 N R 10 E S 34 S 35 -----</p> <p style="text-align: center;">2006</p>

**Dependent Resurvey of the Eighth Standard Parallel North (N. Bdy.),
T. 32 N., R. 10 E., Gila and Salt River Meridian, Arizona**

CHAINS	
	<p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p> <hr/>
	<p>N. 89°56' W., on the S. bdy. of sec. 34, T. 33 N., R. 10 E.</p> <p>Over rolling, sandy terrain, through scattered native grasses and cacti.</p>
39.96	<p>The stan. 1/4 sec. cor. of sec. 34, monumented with a stainless steel post, 2 1/2 ins. diam., firmly set, projecting 8 ins. above the ground, encircled with a collar of stone, with brass cap mkd. SC T33N R10E 1/4 S34 2006.</p> <hr/>
	<p>N. 89°55' W., beginning new measurement.</p> <p>Over rolling, sandy terrain, through scattered native grasses and cacti.</p>
40.07	<p>Point for the stan. cor. of secs. 33 and 34, at proportionate dist., there is no remaining evidence of the orig. cor.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p>
	<p align="center">SC T 33 N R 10 E S 33 S 34 ----- 2006</p> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p> <hr/>
	<p>N. 89°55' W., on the S. bdy. of sec. 33, T. 33 N., R. 10 E.</p> <p>Over rolling, sandy terrain, through scattered native grasses and cacti.</p>
40.07	<p>Point for the stan. 1/4 sec. cor. of sec. 33, at proportionate dist., there is no remaining evidence of the orig. cor.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 25 ins. in the ground, with brass cap mkd.</p>
	<p align="center">SC T 33 N R 10 E 1/4 S 33 ----- 2006</p>

Dependent Resurvey of the Eighth Standard Parallel North (N. Bdy.),
T. 32 N., R. 10 E., Gila and Salt River Meridian, Arizona

CHAINS	
80.14	<p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p> <p>Point for the stan. cor. of secs. 32 and 33, at proportionate dist., there is no remaining evidence of the orig. cor.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 25 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">SC T 33 N R 10 E <u>S 32 S 33</u></p> <p style="text-align: center;">2006</p> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p> <hr/>
40.07	<p>N. 89°55' W., on the S. bdy. of sec. 32, T. 33 N., R. 10 E.</p> <p>Over rolling, sandy terrain, through scattered native grasses and cacti.</p> <p>The stan. 1/4 sec. cor. of sec. 32, monumented with a sandstone, 14 x 9 x 4 ins., loosely set, 2 ins. in the ground, mkd. SC 1/4 32 on a face.</p> <p>At the corner point</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 22 ins. in the ground, encircled with a collar of stone, with brass cap mkd.</p> <p style="text-align: center;">SC T 33 N R 10 E <u>1/4 S 32</u></p> <p style="text-align: center;">2006</p> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p> <p>from which</p> <p style="padding-left: 40px;">A sandstone outcropping, 6 x 4 ft., bears N. 38 1/4° W., 82 lks. dist., with XBO chiseled on the S. edge.</p> <p>Deposit the mkd. stone in the collar of stone.</p> <hr/> <p>West, beginning new measurement.</p>

Dependent Resurvey of the Eighth Standard Parallel North (N. Bdy.),
T. 32 N., R. 10 E., Gila and Salt River Meridian, Arizona

CHAINS	
	<p>Over gradually ascending terrain.</p> <p>39.98 The stan. cor. of secs. 31 and 32, monumented with a limestone, 19 x 7 x 5 ins., firmly set, 7 ins. in the ground, mkd. SC on the N. face, 5 notches on the E. edge and 1 notch on the W. edge, with a mound of stone, 2 ft. base, 2 ft. high, N. of the cor.</p> <p>At the corner point</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 17 ins. in the ground, to bedrock, in a supporting mound of stone, 3 ft. base, to top, with brass cap mkd.</p> <p style="text-align: center;">SC T 33 N R 10 E <u>S 31 S 32</u></p> <p style="text-align: center;">2006</p> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p> <p>Deposit the mkd. stone alongside the stainless steel post.</p> <p>Rebuild the mound of stone, 3 ft. base, 2 ft. high, N. of the cor.</p> <hr/> <p>West, on the S. bdy. of sec. 31, T. 33 N., R. 10 E.</p> <p>Over gradually descending, sandy terrain, through scattered juniper and sagebrush.</p>
39.99	<p>The stan. 1/4 sec. cor. of sec. 31, monumented with a limestone, 19 x 7 x 4 ins., loosely set, 2 ins. in the ground, mkd. SC 1/4 on a face, with a sandstone, 21 x 7 x 4 ins., mkd. SC 1/4 on a face, lying nearby.</p> <p>At the corner point</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 23 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">SC T 33 N R 10 E <u>1/4 S 31</u></p> <p style="text-align: center;">2006</p> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p>

Dependent Resurvey of the Eighth Standard Parallel North (N. Bdy.),
T. 32 N., R. 10 E., Gila and Salt River Meridian, Arizona

CHAINS	
	<p>Deposit the mkd. stones alongside the stainless steel post.</p> <hr/> <p>N. 89°58' W., beginning new measurement.</p> <p>Over rolling, sandy terrain, through scattered native grasses.</p> <p>40.05 The stan. cor. of Tps. 33 N., Rs. 9 and 10 E., monumented with an X chiseled in exposed sandstone bedrock, with the additional chisel marks SC T33N and 6 grooves to the W., 6 grooves to the N. and R10E and 6 grooves to the E., with a sandstone, 13 x 7 x 4 ins., mkd. SC on a face, 6 grooves on a face and 6 grooves on a face, lying in a scattered mound of stone, N. of the cor.</p> <p>At the corner point</p> <p>Set a brass tablet, 3 1/4 ins. diam., 3 1/2 ins. stem, cemented in a drill hole, in solid rock, with top mkd.</p> <p style="text-align: center;">SC T 33 N R 9 E R 10 E S 36 S 31</p> <hr/> <p style="text-align: center;">2006</p> <p>Deposit a magnet, in the drill hole, beneath the brass tablet.</p> <p>Rebuild the mound of stone, 3 ft. base, 2 ft. high, N. of the cor. and deposit the mkd. stone in the mound of stone.</p> <hr/>
40.05	<p>N. 89°47' W., on the S. bdy. of sec. 36, T. 33 N., R. 9 E.</p> <p>Over rolling, sandy terrain, through native grasses and sagebrush.</p> <p>The stan. 1/4 sec. cor. of sec. 36, T. 33 N., R. 9 E., monumented with a limestone, 18 x 8 x 4 ins., loosely set, 2 ins. in the ground, mkd. SC 1/4 on a face.</p> <p>At the corner point</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 25 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">SC T 33 N R 9 E 1/4 S 36</p> <hr/> <p style="text-align: center;">2006</p>

**Dependent Resurvey of the Eighth Standard Parallel North (N. Bdy.),
T. 32 N., R. 10 E., Gila and Salt River Meridian, Arizona**

CHAINS

Deposit a magnet, in a white plastic case, at the base of the stainless steel post.

Deposit the mkd. stone alongside the stainless steel post.

**Dependent Resurvey of a Portion of the South Boundary,
T. 32 N., R. 10 E., Gila and Salt River Meridian, Arizona**

Restoring the survey executed by
Philip Contzen, in 1905

From the 1/4 sec. cor. of secs. 3 and 34, monumented with a stainless steel post, 2 1/2 ins. diam., firmly set, projecting 3 ins. above a sandstone outcropping, with brass cap mkd. T32N R10E 1/4 S34 S3 T31N 1988, with a limestone, 18 x 7 x 7 ins., mkd. 3 on a face and 34 on a face, lying nearby.

Add the marks 2006 to the brass cap.

N. 89°57' W., bet. secs. 3 and 34, on the S. bdy. of the Tp.

Over rocky, wind eroded terrain.

40.26 Point for the cor. of secs. 3, 4, 33 and 34, at proportionate dist., there is no remaining evidence of the orig. cor.

Set a brass tablet, 3 1/4 ins. diam., 3 1/2 ins. stem, cemented in a drill hole, in solid rock, with top mkd.

T 32 N	R 10 E
S 33	S 34
S 4	S 3
T 31 N	

2006

Deposit a magnet, in the drill hole, beneath the brass tablet.

N. 89°57' W., bet. secs. 4 and 33, on the S. bdy. of the Tp.

Over rocky, wind eroded terrain.

40.26 The 1/4 sec. cor. of secs. 4 and 33, monumented with a limestone, 18 x 8 x 5 ins., loosely set, 3 ins. in the ground, mkd. 1/4 33 on a face and 4 on a face.

At the corner point

**Dependent Resurvey of a Portion of the South Boundary,
T. 32 N., R. 10 E., Gila and Salt River Meridian, Arizona**

CHAINS	
	<p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 25 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T 32 N R 10 E S 33 1/4 ——— S 4 T 31 N</p> <p style="text-align: center;">2006</p> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p> <p>Deposit the mkd. stone alongside the stainless steel post.</p> <hr style="width: 20%; margin: auto;"/> <p>N. 89°59' W., beginning new measurement.</p> <p>Over rocky, barren terrain.</p>
40.39	<p>Point for the cor. of secs. 4, 5, 32 and 33, at proportionate dist., there is no remaining evidence of the orig. cor.</p> <p>Set a brass tablet, 3 1/4 ins. diam., 3 1/2 ins. stem, cemented in a drill hole, in solid rock, with top mkd.</p> <p style="text-align: center;">T 32 N R 10 E S 32 S 33 S 5 S 4 T 31 N</p> <p style="text-align: center;">2006</p> <p>Deposit a magnet, in the drill hole, beneath the brass tablet.</p> <hr style="width: 20%; margin: auto;"/> <p>N. 89°59' W., bet. secs. 5 and 32, on the S. bdy. of the Tp.</p> <p>Over rocky, barren terrain.</p>
40.39	<p>The 1/4 sec. cor. of secs. 5 and 32, monumented with a limestone, 15 x 7 x 6 ins., firmly set, 3 ins. in the ground, mkd. 1/4 32 on the N. face and 5 on the S. face, with a mound of stone, 2 ft. base, 2 ft. high, N. of the cor.</p> <p>At the corner point</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 16 ins. in the ground, to bedrock, in a supporting mound of stone, 4 ft. base, to top, with brass cap mkd.</p>

Dependent Resurvey of a Portion of the South Boundary,
T. 32 N., R. 10 E., Gila and Salt River Meridian, Arizona

CHAINS

T 32 N R 10 E
S 32
1/4 ———
S 5
T 31 N

2006

Deposit a magnet, in a white plastic case, at the base of the stainless steel post.

Utilize the mound of stone and deposit the mkd. stone in the supporting mound of stone.

N. 89°47' W., beginning new measurement.


Over rough, rocky terrain.

39.99

The true point for the cor. of secs. 5, 6, 31 and 32, at proportionate dist., there is no remaining evidence of the orig. cor.; falls in a wash where it is impracticable to establish a permanent monument.

From the true point, the point selected for a witness cor. to the cor. of secs. 5, 6, 31 and 32, bears S. 16°55' W., 90 lks. dist.

Set a brass tablet, 3 1/4 ins. diam., 3 1/2 ins. stem, cemented in a drill hole, in solid rock, with top mkd.

WC 

T 32 N R 10 E
S 31 | S 32
S 6 | S 5
T 31 N

2006

Deposit a magnet, in the drill hole, beneath the brass tablet.

N. 89°47' W., bet. secs. 6 and 31, on the S. bdy. of the Tp.

Over rocky, barren terrain.

39.99

The 1/4 sec. cor. of secs. 6 and 31, monumented with a limestone, 20 x 6 x 6 ins., loosely set, 3 ins. in the ground, mkd. 1/4 31 on a face and 6 on a face.

At the corner point

**Dependent Resurvey of a Portion of the South Boundary,
T. 32 N., R. 10 E., Gila and Salt River Meridian, Arizona**

<p>CHAINS</p>	<p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 25 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T 32 N R 10 E S 31 1/4 ——— S 6 T 31 N</p> <p style="text-align: center;">2006</p> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p> <p>Deposit the mkd. stone alongside the stainless steel post.</p> <hr style="width: 20%; margin: auto;"/> <p>N. 89°58' W., beginning new measurement.</p>
<p>38.48</p>	<p>The cor. of Tps. 31 and 32 N., Rs. 9 and 10 E., monumented with a stainless steel post, 2 1/2 ins. diam., firmly set, projecting 3 ins. above the ground, with brass cap mkd. T32N R9E R10E S36 S31 S1 S6 T31N 1990, with a mound of stone, 3 ft. base, 2 ft. high, W. of the cor.</p> <p>Add the marks 2006 to the brass cap.</p>
	<hr/> <p style="text-align: center;">Dependent Resurvey of the West Boundary, T. 32 N., R. 10 E., Gila and Salt River Meridian, Arizona</p> <hr/> <p style="text-align: center;">Restoring the survey executed by Philip Contzen, in 1905</p> <hr/> <p>From the cor. of Tps. 31 and 32 N., Rs. 9 and 10 E., hereinbefore described.</p> <p>N. 0°32' E., bet. secs. 31 and 36, on the W. bdy. of the Tp.</p> <p>Over rolling, rocky terrain.</p> <p>40.05 The 1/4 sec. cor. of secs. 31 and 36, monumented with a limestone, 20 x 8 x 6 ins., loosely set, 3 ins. in the ground, mkd. 1/4 36 on a face and 31 on a face.</p> <p>At the corner point</p> <p>Set a stainless steel post, 12 ins. long, 2 1/2 ins. diam., flush with the surface of the ground, in a concrete collar, with brass cap mkd.</p>

**Dependent Resurvey of the West Boundary,
T. 32 N., R. 10 E., Gila and Salt River Meridian, Arizona**

CHAINS

T 32 N	
1/4	
R 9 E	R 10 E
S 36	S 31

2006

Deposit a magnet, in a white plastic case, at the base of the stainless steel post.

Deposit the mkd. stone alongside the stainless steel post.

N. 0°29' E., beginning new measurement.

39.52

The cor. of secs. 25, 30, 31 and 36, monumented with a limestone, 14 x 10 x 6 ins., loosely set, 3 ins. in the ground, mkd. T32N on a face, 9E on a face and 5 notches on an edge.

At the corner point

Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 15 ins. in the ground, to bedrock, in a supporting mound of stone, 3 ft. base, to top, with brass cap mkd.

T 32 N	
R 9 E	R 10 E
S 25	S 30
S 36	S 31

2006

Deposit a magnet, in a white plastic case, at the base of the stainless steel post.

Deposit the mkd. stone in the supporting mound of stone.

N. 0°03' W., bet. secs. 25 and 30, on the W. bdy. of the Tp.

Over rocky, sandstone terrain.

39.99

The 1/4 sec. cor. of secs 25 and 30, monumented with a limestone, 17 x 8 x 5 ins., firmly set, 11 ins. in the ground, mkd. 1/4 25 on the W. face and 30 on the E. face.

At the corner point

Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 22 ins. in the ground, with brass cap mkd.

**Dependent Resurvey of the West Boundary,
T. 32 N., R. 10 E., Gila and Salt River Meridian, Arizona**

CHAINS	
	T 32 N 1/4 R 9 E R 10 E S 25 S 30 2006
	Deposit a magnet, in a white plastic case, at the base of the stainless steel post. Deposit the mkd. stone alongside the stainless steel post. <hr style="width: 20%; margin: auto;"/> N. 0°03' E., beginning new measurement.
40.38	The cor. of secs. 19, 24, 25 and 30, monumented with a sandstone, 19 x 9 x 4 ins., loosely set, 2 ins. in the ground, mkd. 4 grooves on a face, with a mound of stone, 2 ft. base, 1/2 ft. high, W. of the cor. At the corner point Set a brass tablet, 3 1/4 ins. diam., 3 1/2 ins. stem, cemented in a drill hole, in solid rock, with top mkd.
	T 32 N R 9 E R 10 E S 24 S 19 <hr style="width: 20%; margin: auto;"/> S 25 S 30 2006
	Deposit a magnet, in the drill hole, beneath the brass tablet. Rebuild the mound of stone 3 ft. base, 2 ft. high, W. of the cor. and deposit the mkd. stone in the mound of stone. <hr style="width: 20%; margin: auto;"/> N. 0°04' E., bet. secs. 19 and 24, on the W. bdy. of the Tp. Over rolling, rocky terrain.
38.14	Wash, 50 ft. wide, 2 ft. deep, drains S. 80° E.
40.03	Point for the 1/4 sec. cor. of secs. 19 and 24, at proportionate dist., there is no remaining evidence of the orig. cor. Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 23 ins. in the ground, with brass cap mkd.

**Dependent Resurvey of the West Boundary,
T. 32 N., R. 10 E., Gila and Salt River Meridian, Arizona**

CHAINS	
	T 32 N 1/4 R 9 E R 10 E S 24 S 19 2006
	Deposit a magnet, in a white plastic case, at the base of the stainless steel post.
80.06	The cor. of secs. 13, 18, 19 and 24, monumented with a sandstone, 16 x 8 x 4 ins., loosely set, 2 ins. in the ground, mkd. 3 grooves on a face, 3 grooves on a face and an X on an end, with a mound of stone, 3 ft. base, 1/2 ft. high, W. of the cor. At the corner point Set a brass tablet, 3 1/4 ins. diam., 3 1/2 ins. stem, cemented in a drill hole, in solid rock, with top mkd.
	T 32 N R 9 E R 10 E S 13 S 18 S 24 S 19 2006
	Deposit a magnet, in the drill hole, beneath the brass tablet. Rebuild the mound of stone, 3 ft. base, 2 1/2 ft. high, W. of the cor. and deposit the mkd. stone in the mound of stone.
	<hr/> N. 0°26' W., bet. secs. 13 and 18, on the W. bdy. of the Tp. Over rough, rocky terrain, through scattered native grasses.
39.66	The 1/4 sec. cor. of secs. 13 and 18, monumented with a limestone, 17 x 6 x 6 ins., loosely set, 3 ins. in the ground, mkd. 1/4 13 on a face, 18 on a face and an X on an end. At the corner point Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 25 ins. in the ground, with brass cap mkd.
	T 32 N 1/4 R 9 E R 10 E S 13 S 18 2006

**Dependent Resurvey of the West Boundary,
T. 32 N., R. 10 E., Gila and Salt River Meridian, Arizona**

CHAINS																										
40.24	<p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p> <p>Deposit the mkd. stone alongside the stainless steel post.</p> <p>Cor. is located in a drainage, 10 ft. wide, 6 ins. deep, drains S. 25° W.</p> <hr style="width: 20%; margin: 10px auto;"/> <p>N. 0°42' E., beginning new measurement.</p> <p>The true point for the cor. of secs. 7, 12, 13 and 18, at proportionate dist., there is no remaining evidence of the orig. cor.; falls in a water filled drainage, 13 ft. wide, 1 ft. deep, drains N. 78° W., where it is impracticable to monument.</p> <p>From the true point, the point selected for a witness cor. to the cor. of secs. 7, 12, 13 and 18, bears N. 23°25' E., 1.37 chs. dist.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 23 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center; margin: 10px 0;"> <table style="border-collapse: collapse; margin: 0 auto;"> <tr><td></td><td></td><td style="text-align: center;">WC</td><td></td><td></td></tr> <tr><td></td><td></td><td style="text-align: center;">T 32 N</td><td></td><td></td></tr> <tr><td style="text-align: center;">R 9 E</td><td style="border-left: 1px solid black; border-right: 1px solid black;"></td><td style="border-left: 1px solid black; border-right: 1px solid black;"></td><td style="border-left: 1px solid black; border-right: 1px solid black;"></td><td style="text-align: center;">R 10 E</td></tr> <tr><td style="text-align: center;">S 12</td><td style="border-left: 1px solid black; border-right: 1px solid black;"></td><td style="border-left: 1px solid black; border-right: 1px solid black;"></td><td style="border-left: 1px solid black; border-right: 1px solid black;"></td><td style="text-align: center;">S 7</td></tr> <tr><td style="text-align: center;">S 13</td><td style="border-left: 1px solid black; border-right: 1px solid black;"></td><td style="border-left: 1px solid black; border-right: 1px solid black;"></td><td style="border-left: 1px solid black; border-right: 1px solid black;"></td><td style="text-align: center;">S 18</td></tr> </table> <p style="margin-top: 5px;">↓ 2006</p> </div> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p> <hr style="width: 20%; margin: 10px auto;"/> <p>N. 0°42' E., bet. secs. 7 and 12, on the W. bdy. of the Tp.</p> <p>Over rocky terrain.</p> <p>The 1/4 sec. cor. of secs. 7 and 12, monumented with a sandstone, 17 x 6 x 5 ins., loosely set, 3 ins. in the ground, mkd. 1/4 12 on a face and S7 on a face, with a scattered mound of stone, W. of the cor.</p> <p>At the corner point</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 17 ins. in the ground, to bedrock, in a supporting mound of stone, 3 ft. base, to top, with brass cap mkd.</p>			WC					T 32 N			R 9 E				R 10 E	S 12				S 7	S 13				S 18
		WC																								
		T 32 N																								
R 9 E				R 10 E																						
S 12				S 7																						
S 13				S 18																						
40.24	<p>The 1/4 sec. cor. of secs. 7 and 12, monumented with a sandstone, 17 x 6 x 5 ins., loosely set, 3 ins. in the ground, mkd. 1/4 12 on a face and S7 on a face, with a scattered mound of stone, W. of the cor.</p> <p>At the corner point</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 17 ins. in the ground, to bedrock, in a supporting mound of stone, 3 ft. base, to top, with brass cap mkd.</p>																									

**Dependent Resurvey of the West Boundary,
T. 32 N., R. 10 E., Gila and Salt River Meridian, Arizona**

CHAINS

T 32 N	
1/4	
R 9 E	R 10 E
S 12	S 7

2006

Deposit a magnet, in a white plastic case, at the base of the stainless steel post.

Utilize the scattered mound of stone and deposit the mkd. stone in the supporting mound of stone.

N. 0°46' W., beginning new measurement.

41.02 The true point for the cor. of secs. 1, 6, 7 and 12, monumented with a limestone, 17 x 6 x 5 ins., loosely set, 3 ins. in the ground, on exposed sandstone bedrock, mkd. 32N on a face, 10E on a face, 9E on a face, 1 notch on an edge and 5 notches on an edge; where it is impracticable to remonument.

From the true point, the point selected for a witness cor. to the cor. of secs. 7, 12, 13 and 18, bears N. 60°01' E., 24 lks. dist.

Set a brass tablet, 3 1/4 ins. diam., 3 1/2 ins. stem, cemented in a drill hole, in solid rock, with top mkd.

WC	
T 32 N	
R 9 E	R 10 E
S 1	S 6
S 12	S 7

↙ 2006

Deposit a magnet, in the drill hole, beneath the brass tablet.

Remove the mkd. stone from the area.

N. 0°52' E., bet. secs. 1 and 6, on the W. bdy. of the Tp.

Over rocky terrain.

39.06 The 1/4 sec. cor. of secs. 1 and 6, determined at the E. edge of a mound of stone, 2 ft. base, 1 ft. high; and is accepted as the best available evidence of the position of the original corner, with a sandstone, 21 x 7 x 7 ins., mkd. 1/4 on a face and S6 on a face, lying nearby.

At the corner point

**Dependent Resurvey of the West Boundary,
T. 32 N., R. 10 E., Gila and Salt River Meridian, Arizona**

CHAINS	
	<p>Set a brass tablet, 3 1/4 ins. diam., 3 1/2 ins. stem, cemented in a drill hole, in solid rock, with top mkd.</p> <p style="text-align: center;">T 32 N 1/4 R 9 E R 10 E S 1 S 6</p> <p style="text-align: center;">2006</p> <p>Deposit a magnet, in the drill hole, beneath the brass tablet.</p> <p>Rebuild the mound of stone, 3 ft. base, 2 ft. high, W. of the cor. and deposit the mkd. stone in the mound of stone.</p> <hr style="width: 20%; margin: 10px auto;"/> <p>N. 1°00' E., beginning new measurement.</p>
39.85	<p>The closing cor. of secs. 1 and 6, Tps. 32 N., Rs. 9 and 10 E., monumented with a limestone, 14 x 6 x 4 ins., loosely set, 2 ins. in the ground, mkd. 32N and 6 grooves on a face, 6 grooves on a face, 6 grooves on a face and CC on an end. Add the marks AM, unable to bury the stone in place.</p>
40.06	<p>Point for the closing cor. of secs. 1 and 6, Tps. 32 N., Rs. 9 and 10 E., at intersection with the Eighth Standard Parallel North.</p> <p>Set a brass tablet, 3 1/4 ins. diam., 3 1/2 ins. stem, cemented in a drill hole, in solid rock, with top mkd.</p> <p style="text-align: center;">T 33 N R 9 E S 36 S 1 S 6 R 9 E R 10 E T 32 N CC</p> <p style="text-align: center;">2006</p> <p>Deposit a magnet, in the drill hole, beneath the brass tablet.</p> <p>Raise a mound of stone, 3 ft. base, 2 1/2 ft. high, S. of the cor. and deposit the mkd. stone in the mound of stone.</p> <p>Cor. is located on a area of exposed sandstone bedrock.</p> <p>From this cor. point, the stan. cor. of Tps. 33 N., Rs. 9 and 10 E., bears S. 89°47' E., 18.45 chs. dist., hereinbefore described.</p>

**Dependent Resurvey of the West Boundary,
T. 32 N., R. 10 E., Gila and Salt River Meridian, Arizona**

CHAINS

From this same cor. point, the stan. 1/4 sec. cor. of sec. 36, T. 33 N., R. 9 E., bears N. 89°47' W., 21.60 chs. dist., hereinbefore described.

**Dependent Resurvey of the Subdivisional Lines,
T. 32 N., R. 10 E., Gila and Salt River Meridian, Arizona**

Restoring the survey executed by
Philip Contzen, in 1905

From the cor. of secs. 1, 2, 35 and 36, on the S. bdy. of the Tp., monumented with a stainless steel post, 2 1/2 ins. diam., firmly set, projecting 12 ins. above the ground, in a mound of stone, 3 ft. base, 1/2 ft. high, with brass cap mkd. T32N R10E S35 S36 S2 S1 T31N 1988 1997.

Add the marks 2006 to the brass cap.

N. 0°37' W., bet. secs. 35 and 36.

Over broken terrain.

39.73

The 1/4 sec. cor. of secs. 35 and 36, determined at the E. edge of a mound of stone, 2 ft. base, 1 ft. high; and is accepted as the best available evidence of the position of the original corner.

At the corner point

Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 20 ins. in the ground, encircled with a collar of stone, with brass cap mkd.

T 32 N R 10 E

1/4

S 35 | S 36

2006

Deposit a magnet, in a white plastic case, at the base of the stainless steel post.

N. 0°02' E., beginning new measurement.

38.43

The witness cor. to the cor. of secs. 25, 26, 35 and 36, determined at the E. edge of a mound of stone, 2 ft. base, 1 ft. high; and is accepted as the best available evidence of the position of the original corner.

**Dependent Resurvey of the Subdivisional Lines,
T. 32 N., R. 10 E., Gila and Salt River Meridian, Arizona**

CHAINS	
	<p>At the corner point</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 23 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center;"> <p>WC ↑ T 32 N R 10 E S 26 S 25 — — S 35 S 36</p> <p>2006</p> </div> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p>
39.93	<p>The true point for the cor. of secs. 25, 26, 35 and 36, falls on the edge of a sandstone cliff where it is impracticable to monument.</p> <hr/> <p>From the cor. of secs. 25, 30, 31 and 36, on the E. bdy. of the Tp., monumented with a stainless steel post, 2 1/2 ins. diam., firmly set, projecting 4 ins. above the ground, with brass cap mkd. T32N R10E R11E S25 S30 S36 S31 1988.</p> <p>Add the marks 2006 to the brass cap.</p> <p>N. 89°10' W., bet. secs. 25 and 36.</p> <p>Over rolling, sandy terrain, through native grasses.</p>
40.35	<p>Trail road, bears N. 40° E. and S. 40° W.</p>
40.62	<p>The 1/4 sec. cor. of secs. 25 and 36, monumented with a limestone, 14 x 7 x 5 ins., loosely set, 3 ins. in the ground, mkd. 1/4 25 on a face and 36 on a face.</p> <p>At the corner point</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 25 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center;"> <p>T 32 N R 10 E S 25 1/4 — S 36</p> <p>2006</p> </div> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p>

**Dependent Resurvey of the Subdivisional Lines,
T. 32 N., R. 10 E., Gila and Salt River Meridian, Arizona**

CHAINS	
	<p>Deposit the mkd. stone alongside the stainless steel post.</p> <p>Cor. is located under an overhead power line, bears S. 70° E. and N. 70° W.</p> <hr style="width: 20%; margin: 10px auto;"/> <p>S. 88°49' W., beginning new measurement.</p>
39.67	<p>The true point for the cor. of secs. 25, 26, 35 and 36.</p> <hr style="width: 60%; margin: 10px auto;"/> <p>N. 0°12' E., bet. secs. 25 and 26.</p> <p>Over rolling, sandy terrain, through native grasses.</p>
40.13	<p>Point for the 1/4 sec. cor. of secs. 25 and 26, at proportionate dist., there is no remaining evidence of the orig. cor.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T 32 N R 10 E 1/4 S 26 S 25 2006</p> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p> <p>From this cor. point, a steel pipe, 1 3/4 in. diam., firmly set, projecting 9 ins. above a concrete cylinder, bears N. 45 3/4° E., 16.5 lks. dist.</p>
56.83	<p>Graded road, 55 ft. wide, bears N. 80° E. and S. 80° W.</p>
80.26	<p>The cor. of secs. 23, 24, 25 and 26, monumented with a sandstone, 18 x 6 x 5 ins., loosely set, 3 ins. in the ground, mkd. 2 notches on an edge, with an iron post, 2 ins. diam., 4 ft. long, with iron cap mkd. 23 24 25 26 PC1, lying nearby.</p> <p>At the corner point</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 25 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T 32 N R 10 E S 23 S 24 S 26 S 25 2006</p>

**Dependent Resurvey of the Subdivisional Lines,
T. 32 N., R. 10 E., Gila and Salt River Meridian, Arizona**

CHAINS	
	<p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p> <p>Deposit the mkd. stone alongside the stainless steel post.</p> <p>Remove the iron post from the area.</p> <hr/> <p>From the cor. of secs. 19, 24, 25 and 30, on the E. bdy. of the Tp., monumented with an iron post, 2 1/2 ins. diam., firmly set, 10 ins. below the surface of the ground, with brass cap mkd. T32N R10E R11E S24 S19 S25 S30 1962 2005.</p> <p>Add the marks 2006 to the brass cap.</p> <p>N. 89°55' W., bet. secs. 24 and 25.</p> <p>Over rolling sand dunes and sandstone outcroppings.</p>
40.04	<p>The 1/4 sec. cor. of secs. 24 and 25, determined at the S. edge of a mound of stone, 2 ft. base, 1 ft. high; and is accepted as the best available evidence of the position of the original corner.</p> <p>At the corner point</p> <p>Set a brass tablet, 3 1/4 ins. diam., 3 1/2 ins. stem, cemented in a drill hole, in solid rock, with top mkd.</p> <div style="text-align: center;"> <p>T 32 N R 10 E</p> <p>S 24</p> <p>1/4 ———</p> <p>S 25</p> <p>2006</p> </div> <p>Deposit a magnet, in the drill hole, beneath the brass tablet.</p> <hr/> <p>N. 89°53' W., beginning new measurement.</p>
40.05	<p>The cor. of secs. 23, 24, 25 and 26.</p> <hr/> <p>N. 0°07' W., bet. secs. 23 and 24.</p> <p>Over rolling, sandy terrain, through native grasses and scattered sagebrush.</p>
40.04	<p>Point for the 1/4 sec. cor. of secs 23 and 24, at proportionate dist., there is no remaining evidence of the orig. cor.</p>

Dependent Resurvey of the Subdivisional Lines,
T. 32 N., R. 10 E., Gila and Salt River Meridian, Arizona

CHAINS	
	<p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T 32 N R 10 E 1/4 S 23 S 24</p> <p style="text-align: center;">2006</p> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p>
79.85	Trail road, 10 ft. wide, bears S. 50° E. and N. 60° W.
80.08	<p>Point for the cor. of secs. 13, 14, 23 and 24, at proportionate dist., there is no remaining evidence of the orig. cor.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 27 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T 32 N R 10 E S 14 S 13 S 23 S 24</p> <p style="text-align: center;">2006</p> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p> <hr/> <p>From the cor. of secs. 13, 18, 19 and 24, on the E. bdy. of the Tp., monumented with a stainless steel post, 2 1/2 ins. diam., firmly set, 4 ins. below the surface of the ground, with brass cap mkd. T32N R10E R11E S13 S18 S24 S19 2006.</p> <p>N. 89°56' W., bet. secs. 13 and 24.</p> <p>Over rolling, sandy terrain.</p>
40.17	<p>Point for the 1/4 sec. cor. of secs. 13 and 24, at proportionate dist., there is no remaining evidence of the orig. cor.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T 32 N R 10 E S 13 1/4 ——— S 24</p> <p style="text-align: center;">2006</p>

Dependent Resurvey of the Subdivisional Lines,
T. 32 N., R. 10 E., Gila and Salt River Meridian, Arizona

CHAINS	
	Deposit a magnet, in a white plastic case, at the base of the stainless steel post.
80.34	The cor. of secs. 13, 14, 23 and 24.
	N. 0°27' E., bet. secs. 13 and 14.
	Over rolling, sandy terrain, through native grasses.
38.85	Trail road, 8 ft. wide, bears S. 25° E. and N. 20° W.
40.04	The 1/4 sec. cor. of secs. 13 and 14, monumented with a limestone, 16 x 6 x 5 ins., firmly set, 13 ins. in the ground, mkd. 1/4 14 on the W. face and S13 on the E. face.
	At the corner point
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 25 ins. in the ground, with brass cap mkd.
	<p style="text-align: center;">T 32 N R 10 E 1/4 S 14 S 13</p>
	2006
	Deposit a magnet, in a white plastic case, at the base of the stainless steel post.
	Deposit the mkd. stone alongside the stainless steel post.
	N. 0°02' E., beginning new measurement.
40.07	Point for the cor. of secs. 11, 12, 13 and 14, at proportionate dist., there is no remaining evidence of the orig. cor.
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.
	<p style="text-align: center;">T 32 N R 10 E S 11 S 12 S 14 S 13</p>
	2006

**Dependent Resurvey of the Subdivisional Lines,
T. 32 N., R. 10 E., Gila and Salt River Meridian, Arizona**

CHAINS	
	<p>Deposit a magnet, in a white plastic case at the base of the stainless steel post.</p> <hr/> <p>From the cor. of secs. 7, 12, 13 and 18, on the E. bdy of the Tp., monumented with a stainless steel post, 2 1/2 ins. diam., firmly set, projecting 18 ins. above the ground, in a supporting mound of stone, 3 ft. base, to top, with brass cap mkd. T32N R10E R11E S12 S7 S13 S18 2005.</p> <p>N. 89°54' W., bet. secs. 12 and 13.</p> <p>Over rolling, sandy terrain, through native grasses.</p>
40.05	<p>Point for the 1/4 sec. cor. of secs. 12 and 13, at proportionate dist., there is no remaining evidence of the orig. cor.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T 32 N R 10 E S 12 1/4 ——— S 13</p> <p style="text-align: center;">2006</p> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p> <p>From this cor. point, the pump pipe at Natanabah Well, set in a concrete slab, 10 x 10 x 3 1/2 ft., bears S. 31°05' W., 9.77 chs. dist.</p>
80.10	<p>The cor. of secs. 11, 12, 13 and 14.</p> <hr/> <p>N. 0°16' E., bet. secs. 11 and 12.</p> <p>Over rolling, sandy terrain, through native grasses.</p>
40.07	<p>Point for the 1/4 sec. cor. of secs. 11 and 12, at proportionate dist., there is no remaining evidence of the orig. cor.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T 32 N R 10 E 1/4 S 11 S 12</p> <p style="text-align: center;">2006</p>

**Dependent Resurvey of the Subdivisional Lines,
T. 32 N., R. 10 E., Gila and Salt River Meridian, Arizona**

CHAINS									
	<p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p>								
80.14	<p>Point for the cor. of secs. 1, 2, 11 and 12, at proportionate dist., there is no remaining evidence of the orig. cor.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center;"> <table style="margin: auto;"> <tr><td>T 32 N</td><td>R 10 E</td></tr> <tr><td>S 2</td><td>S 1</td></tr> <tr><td>S 11</td><td>S 12</td></tr> </table> <p>2006</p> </div> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p> <hr/> <p>From the cor. of secs. 1, 6, 7 and 12, on the E. bdy. of the Tp., monumented with a stainless steel post, 2 1/2 ins. diam., firmly set, projecting 7 ins. above the ground, encircled with collar of stone, with brass cap mkd. T32N R10E R11E S1 S6 S7 S12 2005.</p> <p>N. 89°50' W., bet. secs. 1 and 12.</p> <p>Over rolling, sandy terrain.</p>	T 32 N	R 10 E	S 2	S 1	S 11	S 12		
T 32 N	R 10 E								
S 2	S 1								
S 11	S 12								
40.01	<p>Point for the 1/4 sec. cor. of secs. 1 and 12, at proportionate dist., there is no remaining evidence of the orig. cor.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center;"> <table style="margin: auto;"> <tr><td>T 32 N</td><td>R 10 E</td></tr> <tr><td>S 1</td><td></td></tr> <tr><td>1/4</td><td>—</td></tr> <tr><td>S 12</td><td></td></tr> </table> <p>2006</p> </div> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p>	T 32 N	R 10 E	S 1		1/4	—	S 12	
T 32 N	R 10 E								
S 1									
1/4	—								
S 12									
66.42	<p>Graded road, 30 ft. wide, bears S. 30° E. and N. 30° W.</p>								
80.02	<p>The cor. of secs. 1, 2, 11 and 12.</p> <hr/> <p>N. 0°05' E., bet. secs. 1 and 2.</p> <p>Over rolling, sandy terrain, through native grasses.</p>								

**Dependent Resurvey of the Subdivisional Lines,
T. 32 N., R. 10 E., Gila and Salt River Meridian, Arizona**

CHAINS	
40.07	<p>Point for the 1/4 sec. cor. of secs. 1 and 2, at proportionate dist., there is no remaining evidence of the orig. cor.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T 32 N R 10 E 1/4 S 2 S 1 2006</p> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p>
80.10	<p>The closing cor. of secs. 1 and 2, hereinbefore described.</p> <hr/> <p>Point for the 1/4 sec. cor. of sec. 1 only, T. 32 N., R. 10 E., is at midpoint on the N. bdy. of sec. 1, on the Eighth Standard Parallel North.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T 33 N R 10 E 1/4 S 1 T 32 N R 10 E 2006</p> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p> <p>From this cor. point, the stan. cor. of secs. 35 and 36, T. 33 N., R. 10 E., bears N. 89°56' W., 18.92 chs. dist., hereinbefore described.</p> <p>From this same cor. point, the stan. 1/4 sec. cor. of sec. 36, T. 33 N., R. 10 E., bears S. 89°56' E., 21.04 chs. dist., hereinbefore described.</p>

Dependent Resurvey of the Subdivisional Lines,
T. 32 N., R. 10 E., Gila and Salt River Meridian, Arizona

CHAINS	
	<p>From this same cor. point, the closing cor. of Tps. 32 N., Rs. 10 and 11 E., bears S. 89°56' E., 39.94 chs. dist., monumented with a brass tablet, 3 1/4 ins. diam., cemented in solid rock, with top mkd. T33N R10E S36 S1 S6 R10E R11E T32N CC 2005.</p>
	<p>From the cor. of secs. 2, 3, 34 and 35, on the S. bdy. of the Tp., monumented with a stainless steel post, 2 1/2 ins. diam., firmly set, projecting 12 ins. above the ground, in a supporting mound of stone, 2 1/2 ft. base, to top, with brass cap mkd. T32N R10E S34 S35 S3 S2 T31N 1988.</p>
	<p>Add the marks 2006 to the brass cap.</p>
	<p>From this cor. point, a power pole, bears N. 82° E., 5.24 chs. dist.</p>
	<p>N. 0°32' W., bet. secs. 34 and 35.</p>
	<p>Over rocky, broken terrain, through scattered native grasses.</p>
<p>39.92</p>	<p>Point for the 1/4 sec. cor. of secs. 34 and 35, at proportionate dist., there is no remaining evidence of the orig. cor.</p> <p>Set a brass tablet, 3 1/4 ins. diam., 3 1/2 ins. stem, cemented in a drill hole, in solid rock, with top mkd.</p>
	<p style="text-align: center;">T 32 N R 10 E 1/4 S 34 S 35 2006</p>
	<p>Deposit a magnet, in the drill hole, beneath the brass tablet.</p>
<p>79.84</p>	<p>The cor. of secs. 26, 27, 34 and 35, monumented with a limestone, 14 x 7 x 6 ins., loosely set, 3 ins. in the ground, mkd. 32N on a face, 10E on a face, 2 notches on an edge and 1 notch on an edge., with a mound of stone, 2 ft. base, 1 ft. high, W. of the cor.</p>
	<p>At the corner point</p>
	<p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 25 ins. in the ground, with brass cap mkd.</p>
	<p style="text-align: center;">T 32 N R 10 E S 27 S 26 S 34 S 35 2006</p>

**Dependent Resurvey of the Subdivisional Lines,
T. 32 N., R. 10 E., Gila and Salt River Meridian, Arizona**

CHAINS	
	<p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p> <p>Deposit the mkd. stone alongside the stainless steel post.</p> <p>Rebuild the mound of stone, 3 ft. base, 2 ft. high, W. of the cor.</p> <hr/> <p>From the true point for cor. of secs. 25, 26, 35 and 36.</p> <p>N. 89°50' W., bet. secs. 26 and 35.</p> <p>Over rolling, broken sandy and rocky terrain, through native grasses.</p>
40.13	<p>Point for the 1/4 sec. cor. of secs. 26 and 25, at proportionate dist., there is no remaining evidence of the orig. cor.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 23 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center;"> <p>T 32 N R 10 E</p> <p>S 26</p> <p>1/4 ———</p> <p>S 35</p> <p>2006</p> </div>
80.26	<p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p> <p>The cor. of secs. 26, 27, 34 and 35.</p> <hr/> <p>N. 0°30' E., bet. secs. 26 and 27.</p> <p>Over rolling, broken sandy and rocky terrain, through native grasses.</p>
36.44	<p>Base of a mesa, bears S. 80° E. and N. 40° W.</p>
40.20	<p>The 1/4 sec. cor. of secs. 26 and 27, monumented with a limestone, 16 x 6 x 5 ins., loosely set, 2 ins. in the ground, mkd. 1/4 27 on a face, with an imbedded mound of stone, W. of the cor.</p> <p>At the corner point</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 25 ins. in the ground, with brass cap mkd.</p>

Dependent Resurvey of the Subdivisional Lines,
T. 32 N., R. 10 E., Gila and Salt River Meridian, Arizona

CHAINS	
	<p style="text-align: center;">T 32 N R 10 E 1/4 S 27 S 26</p> <p style="text-align: center;">2006</p> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p> <p>Rebuild the mound of stone, 2 ft. base, 2 ft. high, W. of the cor. and deposit the mkd. stone in the mound of stone.</p> <hr/> <p>N. 0°22' E., beginning new measurement.</p>
39.55	<p>The cor. of secs. 22, 23, 26 and 27, monumented with a limestone, 16 x 8 x 4 ins., loosely set, 2 ins. in the ground, mkd. 32N on a face, 10E on a face, 2 notches on an edge and 2 notches on an edge.</p> <p>At the corner point</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 25 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T 32 N R 10 E S 22 S 23 S 27 S 26</p> <p style="text-align: center;">2006</p> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p> <p>Deposit the mkd. stone alongside the stainless steel post.</p> <hr/> <p>From the cor. of secs. 23, 24, 25 and 26.</p> <p>N. 89°52' W., bet. secs. 23 and 26.</p> <p>Over level to rolling, sandy terrain, through medium growth sagebrush and canatilla.</p>
40.22	<p>The 1/4 sec. cor. of secs. 23 and 26, monumented with a limestone, 12 x 9 x 4 ins., loosely set, 2 ins. in the ground, mkd. 1/4 23 on a face and S26 on a face.</p> <p>At the corner point</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 25 ins. in the ground, with brass cap mkd.</p>

Dependent Resurvey of the Subdivisional Lines,
T. 32 N., R. 10 E., Gila and Salt River Meridian, Arizona

CHAINS	
	<p style="text-align: center;">T 32 N R 10 E S 23 1/4 ——— S 26</p> <p style="text-align: center;">2006</p> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p> <p>Deposit the mkd. stone alongside the stainless steel post.</p> <hr style="width: 20%; margin: auto;"/> <p>S. 89°28' W., beginning new measurement.</p>
39.72	<p>The cor. of secs. 22, 23, 26 and 27.</p> <hr style="width: 60%; margin: auto;"/> <p>N. 0°13' W., bet. secs. 22 and 23.</p> <p>Over level to rolling, sandy terrain, through medium growth sagebrush and canatilla.</p>
40.17	<p>Point for the 1/4 sec. cor. of secs. 22 and 23, at proportionate dist., there is no remaining evidence of the orig. cor.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p>
	<p style="text-align: center;">T 32 N R 10 E 1/4 S 22 S 23</p> <p style="text-align: center;">2006</p> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p>
80.34	<p>Point for the cor. of secs. 14, 15, 22 and 23, at proportionate dist., there is no remaining evidence of the orig. cor.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p>
	<p style="text-align: center;">T 32 N R 10 E S 15 S 14 S 22 S 23</p> <p style="text-align: center;">2006</p>

**Dependent Resurvey of the Subdivisional Lines,
T. 32 N., R. 10 E., Gila and Salt River Meridian, Arizona**

CHAINS	
	<p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p> <hr/> <p>From the cor. of secs. 13, 14, 23 and 24.</p> <p>N. 88°38' W., bet. secs. 14 and 23.</p> <p>Over level to rolling, sandy terrain, through medium growth sagebrush and canatilla.</p>
40.12	<p>The 1/4 sec. cor. of secs. 14 and 23, monumented with a limestone, 16 x 10 x 4 ins., loosely set, 2 ins. in the ground, mkd. 1/4 14 on a face and 23 on a face.</p> <p>At the corner point</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 25 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center;"> <p>T 32 N R 10 E</p> <p>S 14</p> <p>1/4 ———</p> <p>S 23</p> <p>2006</p> </div> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p> <p>Deposit the mkd. stone alongside the stainless steel post.</p> <hr/> <p>S. 88°36' W., beginning new measurement.</p>
39.98	<p>The cor. of secs. 14, 15, 22 and 23.</p> <hr/> <p>N. 0°16' E., bet. secs. 14 and 15.</p> <p>Over rolling, sandy terrain, through medium growth sagebrush and native grasses.</p>
40.17	<p>The 1/4 sec. cor. of secs. 14 and 15, monumented with a limestone, 12 x 7 x 6 ins., loosely set, 3 ins. in the ground, mkd. 1/4 15 on a face and S14 on a face.</p> <p>At the corner point</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 25 ins. in the ground, with brass cap mkd.</p>

Dependent Resurvey of the Subdivisional Lines,
T. 32 N., R. 10 E., Gila and Salt River Meridian, Arizona

CHAINS

T 32 N R 10 E
1/4
S 15 | S 14

2006

Deposit a magnet, in a white plastic case, at the base of the stainless steel post.

Deposit the mkd. stone alongside the stainless steel post.

N. 0°11' E., beginning new measurement.

40.22 The cor. of secs. 10, 11, 14 and 15, monumented with a limestone, 18 x 6 x 5 ins., firmly set, 12 ins. in the ground, mkd. 32N on the N. face, 2 notches on N. edge and 4 notches on the S. edge.

At the corner point

Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 25 ins. in the ground, with brass cap mkd.

T 32 N R 10 E
S 10 | S 11
S 15 | S 14

2006

Deposit a magnet, in a white plastic case, at the base of the stainless steel post.

Deposit the mkd. stone alongside the stainless steel post.

Raise a mound of stone, 2 ft. base, 1 1/2 ft. high, W. of the cor.

From the cor. of secs. 11, 12, 13 and 14.

N. 89°49' W., bet. secs. 11 and 14.

Over rolling, sandy terrain, through medium growth sagebrush and native grasses.

40.04 Point for the 1/4 sec. cor. of secs. 11 and 14, at proportionate dist., there is no remaining evidence of the orig. cor.

Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.

Dependent Resurvey of the Subdivisional Lines,
T. 32 N., R. 10 E., Gila and Salt River Meridian, Arizona

CHAINS	
	<p style="text-align: center;">T 32 N R 10 E S 11 1/4 <u> </u> S 14</p> <p style="text-align: center;">2006</p>
80.08	<p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p> <p>The cor. of secs. 10, 11, 14 and 15.</p> <hr/>
	<p>N. 0°19' E., bet. secs. 10 and 11.</p> <p>Over rolling, sandy terrain, through medium growth sagebrush and native grasses.</p>
40.01	<p>Point for the 1/4 sec. cor. of secs. 10 and 11, at proportionate dist., there is no remaining evidence of the orig. cor.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p>
	<p style="text-align: center;">T 32 N R 10 E 1/4 S 10 S 11</p> <p style="text-align: center;">2006</p> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p>
80.02	<p>The cor. of secs. 2, 3, 10 and 11, determined at the E. edge of a scattered mound of stone; and is accepted as the best available evidence of the position of the original corner.</p> <p>At the corner point</p> <p>Set a brass tablet, 3 1/4 ins. diam., 3 1/2 ins. stem, cemented in a drill hole, in solid rock, with top mkd.</p>
	<p style="text-align: center;">T 32 N R 10 E S 3 S 2 <u> </u> S 10 S 11</p> <p style="text-align: center;">2006</p> <p>Deposit a magnet, in the drill hole, beneath the brass tablet.</p>

**Dependent Resurvey of the Subdivisional Lines,
T. 32 N., R. 10 E., Gila and Salt River Meridian, Arizona**

CHAINS	
40.01	<p>Rebuild the mound of stone, 2 ft. base, 1 1/2 ft. high, W. of the cor.</p> <hr/> <p>From the cor. of 1, 2, 11 and 12.</p> <p>N. 89°53' W., bet. secs. 2 and 11.</p> <p>Over rolling, sandy terrain, through medium growth sagebrush and native grasses.</p> <p>Point for the 1/4 sec. cor. of secs. 2 and 11, at proportionate dist., there is no remaining evidence of the orig. cor.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center;"> <p>T 32 N R 10 E</p> <p>S 2</p> <p>1/4 ———</p> <p>S 11</p> <p>2006</p> </div> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p>
80.02	<p>The cor. of secs. 2, 3, 10 and 11.</p> <hr/> <p>N. 0°30' E., bet. secs. 2 and 3.</p> <p>Over rolling, sandy terrain and sandstone outcrops.</p>
39.81	<p>The 1/4 sec. cor. of secs. 2 and 3, monumented with a limestone, 18 x 7 x 5 ins., loosely set, 3 ins. in the ground, mkd. 1/4 3 on a face.</p> <p>At the corner point</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 23 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center;"> <p>T 32 N R 10 E</p> <p>1/4</p> <p>S 3 S 2</p> <p>2006</p> </div> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p>

**Dependent Resurvey of the Subdivisional Lines,
T. 32 N., R. 10 E., Gila and Salt River Meridian, Arizona**

CHAINS	<p>Deposit the mkd. stone alongside the stainless steel post.</p> <hr style="width: 20%; margin: 10px auto;"/> <p>N. 0°09' W., beginning new measurement.</p>																
40.23	<p>Point for the closing cor. of secs. 2 and 3, T. 32 N., R. 10 E., at proportionate dist., on the Eighth Standard Parallel North, there is no remaining evidence of the orig. cor.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center; margin: 10px 0;"> <table style="margin: auto; border-collapse: collapse;"> <tr><td>T 33 N</td><td>R 10 E</td></tr> <tr><td colspan="2" style="border-top: 1px solid black;">S 34</td></tr> <tr><td>S 3</td><td>S 2</td></tr> <tr><td>T 32 N</td><td>R 10 E</td></tr> <tr><td colspan="2" style="text-align: center;">CC</td></tr> </table> <p>2006</p> </div> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p> <p>From this cor. point, the stan. 1/4 sec. cor. of sec. 34, T. 33 N., R. 10 E., bears N. 89°56' W., 18.98 chs. dist., hereinbefore described.</p> <p>From this same cor. point, the stan. cor. of secs. 34 and 35, T. 33 N., R. 10 E., bears S. 89°56' E., 20.98 chs. dist., hereinbefore described.</p> <hr style="width: 20%; margin: 10px auto;"/> <p>Point for the 1/4 sec. cor. of sec. 2 only, T. 32 N., R. 10 E., is at midpoint on the N. bdy. of sec. 2, on the Eighth Standard Parallel North.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center; margin: 10px 0;"> <table style="margin: auto; border-collapse: collapse;"> <tr><td>T 33 N</td><td>R 10 E</td></tr> <tr><td colspan="2" style="border-top: 1px solid black;">1/4 S 2</td></tr> <tr><td>T 32 N</td><td>R 10 E</td></tr> </table> <p>2006</p> </div> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p> <p>From this cor. point, the stan. cor. of secs. 34 and 35, T. 33 N., R. 10 E., bears N. 89°56' W., 18.96 chs. dist., hereinbefore described.</p>	T 33 N	R 10 E	S 34		S 3	S 2	T 32 N	R 10 E	CC		T 33 N	R 10 E	1/4 S 2		T 32 N	R 10 E
T 33 N	R 10 E																
S 34																	
S 3	S 2																
T 32 N	R 10 E																
CC																	
T 33 N	R 10 E																
1/4 S 2																	
T 32 N	R 10 E																

**Dependent Resurvey of the Subdivisional Lines,
T. 32 N., R. 10 E., Gila and Salt River Meridian, Arizona**

CHAINS	
	<p>From this same cor. point, the stan. 1/4 sec. cor. of sec. 35, T. 33 N., R. 10 E., bears S. 89°56' E., 21.00 chs. dist., hereinbefore described.</p> <hr/> <p>From the cor. of secs. 3, 4, 33 and 34, on the S. bdy. of the Tp., hereinbefore described.</p> <p>N. 0°39' W., bet. secs. 33 and 34.</p> <p>Over rolling, rocky terrain.</p>
39.61	<p>The 1/4 sec. cor. of secs. 33 and 34, monumented with a limestone, 13 x 7 x 7 ins., loosely set, 3 ins. in the ground, mkd. 1/4 33 on a face and 34 on a face.</p> <p>At the corner point</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 21 ins. in the ground, encircled with a collar of stone, with brass cap mkd.</p> <div style="text-align: center;"> <p>T 32 N R 10 E</p> <p>1/4</p> <p>S 33 S 34</p> <p>2006</p> </div> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p> <p>Deposit the mkd. stone in the collar of stone.</p> <hr/> <p>North, beginning new measurement.</p> <p>Over rolling, broken sandy and rocky terrain, through native grasses.</p>
40.09	<p>Point for the cor. of secs. 27, 28, 33 and 34, at proportionate dist., there is no remaining evidence of the orig. cor.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center;"> <p>T 32 N R 10 E</p> <p>S 28 S 27</p> <hr style="width: 50%; margin: 0 auto;"/> <p>S 33 S 34</p> <p>2006</p> </div>

**Dependent Resurvey of the Subdivisional Lines,
T. 32 N., R. 10 E., Gila and Salt River Meridian, Arizona**

CHAINS	
	<p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p> <hr/> <p>From the cor. of secs. 26, 27, 34 and 35.</p> <p>N. 89°58' W., bet. secs. 27 and 34.</p> <p>Over rolling, sandy terrain, through native grasses.</p>
39.98	<p>The 1/4 sec. cor. of secs. 27 and 34, monumented with a limestone, 14 x 6 x 5 ins., loosely set, 3 ins. in the ground, mkd. 1/4 27 on a face and 34 on a face.</p> <p>At the corner point</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 25 ins. in the ground, with brass cap mkd.</p> <p align="center">T 32 N R 10 E S 27 1/4 ——— S 34</p> <p align="center">2006</p>
	<p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p> <p>Deposit the mkd. stone alongside the stainless steel post.</p> <hr/> <p>S. 89°50' W., beginning new measurement.</p>
39.98	<p>The cor. of secs. 27, 28, 33 and 34.</p> <hr/> <p>N. 0°17' E., bet. secs. 27 and 28.</p> <p>Over level to rolling, sandy terrain, through medium growth sagebrush and canatilla.</p>
40.09	<p>Point for the 1/4 sec. cor. of secs. 27 and 28, at proportionate dist., there is no remaining evidence of the orig. cor.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p align="center">T 32 N R 10 E 1/4 S 28 S 27</p> <p align="center">2006</p>

**Dependent Resurvey of the Subdivisional Lines,
T. 32 N., R. 10 E., Gila and Salt River Meridian, Arizona**

CHAINS							
	Deposit a magnet, in a white plastic case, at the base of the stainless steel post.						
80.18	Point for the cor. of secs. 21, 22, 27 and 28, at proportionate dist., there is no remaining evidence of the orig. cor. Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.						
	<table style="margin-left: auto; margin-right: auto;"> <tr> <td colspan="2">T 32 N R 10 E</td> </tr> <tr> <td style="border-right: 1px solid black; text-align: center;">S 21</td> <td style="text-align: center;">S 22</td> </tr> <tr> <td style="border-right: 1px solid black; text-align: center;">S 28</td> <td style="text-align: center;">S 27</td> </tr> </table>	T 32 N R 10 E		S 21	S 22	S 28	S 27
T 32 N R 10 E							
S 21	S 22						
S 28	S 27						
	2006						
	Deposit a magnet, in a white plastic case, at the base of the stainless steel post.						
	From the cor. of secs. 22, 23, 26 and 27. N. 89°45' W., bet. secs. 22 and 27. Over rolling, sandy terrain, through native grasses.						
38.08	Power line, bears N. 5° E. and S. 5° W.						
40.08	Point for the 1/4 sec. cor. of secs. 22 and 27, at proportionate dist., there is no remaining evidence of the orig. cor. Set a nail, 6 ins. long, 1 in. below the surface of the ground, to bedrock. from which A stainless steel post, 28 ins. long, 2 1/2 ins. diam., set 24 ins. in the ground, for a reference monument, bears S. 44° E., 74.3 ft. dist., with brass cap mkd. RM T32N R10E 1/4 S27 74.3 FT TO COR 2006, and an arrow pointing to the cor. Deposit a magnet, in a white plastic case, at the base of the stainless steel post. A stainless steel post, 28 ins. long, 2 1/2 ins. diam., set 24 ins. in the ground, for a reference monument, bears N. 44° W., 52.5 ft. dist., with brass cap mkd. RM T32N R10E 1/4 S22 52.5 FT TO COR 2006, and an arrow pointing to the cor. Deposit a magnet, in a white plastic case, at the base of the stainless steel post. Cor. is located in a graded road, 55 lks. wide, 18 lks. W. of the center, bears North and South.						

**Dependent Resurvey of the Subdivisional Lines,
T. 32 N., R. 10 E., Gila and Salt River Meridian, Arizona**

CHAINS	
80.16	<p>The cor. of secs. 21, 22, 27 and 28.</p> <hr/> <p>N. 0°08' W., bet. secs. 21 and 22.</p> <p>Over rolling, sandy terrain, through native grasses.</p>
40.09	<p>Point for the 1/4 sec. cor. of secs. 27 and 28, at proportionate dist., there is no remaining evidence of the orig. cor.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, in a supporting mound of stone on the downhill side, 3 ft. base, to top, with brass cap mkd.</p> <p style="text-align: center;">T 32 N R 10 E 1/4 S 21 S 22</p> <p style="text-align: center;">2006</p> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p> <p>Cor. is located on a rocky shelf, 50 ft. high, on a W. facing sandstone cliff, 100 ft. high, bears North and South.</p>
80.18	<p>Point for the cor. of secs. 15, 16, 21 and 22, at proportionate dist., there is no remaining evidence of the orig. cor.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T 32 N R 10 E S 16 S 15 S 21 S 22</p> <p style="text-align: center;">2006</p> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p> <hr/> <p>From the cor. of secs. 14, 15, 22 and 23.</p> <p>N. 89°53' W., bet. secs. 15 and 22.</p> <p>Over rolling, sandy terrain, through native grasses.</p>
40.01	<p>Point for the 1/4 sec. cor. of secs. 15 and 22, at proportionate dist., there is no remaining evidence of the orig. cor.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p>

Dependent Resurvey of the Subdivisional Lines,
T. 32 N., R. 10 E., Gila and Salt River Meridian, Arizona

CHAINS	
	<p style="text-align: center;">T 32 N R 10 E S 15 1/4 ——— S 22</p> <p style="text-align: center;">2006</p>
80.02	<p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p> <p>The cor. of secs. 15, 16, 21 and 22.</p> <hr/>
	<p>N. 0°22' E., bet. secs. 15 and 16.</p> <p>Over rolling, sandy terrain, through native grasses.</p>
40.09	<p>The 1/4 sec. cor. of secs. 15 and 16, monumented with a sandstone, 12 x 9 x 4 ins., loosely set, 2 ins. in the ground, mkd. 1/4 1 on a face.</p> <p>At the corner point</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 25 ins. in the ground, with brass cap mkd.</p>
	<p style="text-align: center;">T 32 N R 10 E 1/4 S 16 S 15</p> <p style="text-align: center;">2006</p> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p> <p>Deposit the mkd. stone alongside the stainless steel post.</p> <hr/>
40.07	<p>N. 0°16' W., beginning new measurement.</p> <p>Over rolling, sandy terrain, through native grasses.</p> <p>Point for the cor. of secs. 9, 10, 15 and 16, at proportionate dist., there is no remaining evidence of the orig. cor.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p>
	<p style="text-align: center;">T 32 N R 10 E S 9 S 10 S 16 S 15</p> <p style="text-align: center;">2006</p>

**Dependent Resurvey of the Subdivisional Lines,
T. 32 N., R. 10 E., Gila and Salt River Meridian, Arizona**

CHAINS	
	<p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p> <hr/> <p>From the cor. of secs. 10, 11, 14 and 15.</p> <p>S. 89°57' W., bet. secs. 10 and 15.</p> <p>Over rolling, sandy terrain, through native grasses.</p>
40.12	<p>Point for the 1/4 sec. cor. of secs. 10 and 15, at proportionate dist., there is no remaining evidence of the orig. cor.</p> <p>Set a brass tablet, 3 1/4 ins. diam., 3 1/2 ins. stem, cemented in a drill hole, in solid rock, with top mkd.</p> <p style="text-align: center;">T 32 N R 10 E S 10 1/4 ——— S 15</p> <p style="text-align: center;">2006</p> <p>Deposit a magnet, in the drill hole, beneath the brass tablet.</p> <p>Cor. is located on the SE edge of a sandstone outcropping.</p>
80.24	<p>The cor. of secs. 9, 10, 15 and 16.</p> <hr/> <p>N. 0°22' E., bet. secs. 9 and 10.</p> <p>Over rolling, sandy terrain, through native grasses.</p>
40.07	<p>Point for the 1/4 sec. cor. of secs. 9 and 10, at proportionate dist., there is no remaining evidence of the orig. cor.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T 32 N R 10 E 1/4 S 9 S 10</p> <p style="text-align: center;">2006</p> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p> <p>From this cor. point, the pump pipe at Charlie Secody Well, set in a concrete slab, 5 ft. x 5 ft. x 4.5 ft., bears N. 20°22' E., 12.20 chs. dist.</p>

**Dependent Resurvey of the Subdivisional Lines,
T. 32 N., R. 10 E., Gila and Salt River Meridian, Arizona**

CHAINS									
77.12	Trail road, 12 ft. wide, bears S. 20° E. and N. 20° W.								
80.14	Point for the cor. of secs. 3, 4, 9 and 10, at proportionate dist., there is no remaining evidence of the orig. cor. Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd. <div style="text-align: center;"> <table style="margin: auto;"> <tr><td>T 32 N</td><td>R 10 E</td></tr> <tr><td>S 4</td><td>S 3</td></tr> <tr><td>S 9</td><td>S 10</td></tr> </table> <p>2006</p> </div> Deposit a magnet, in a white plastic case, at the base of the stainless steel post. <hr/>	T 32 N	R 10 E	S 4	S 3	S 9	S 10		
T 32 N	R 10 E								
S 4	S 3								
S 9	S 10								
	From the cor. of secs. 2, 3, 10 and 11. N. 89°58' W., bet. secs. 3 and 10. Over rolling, sandy terrain, through native grasses.								
40.08	Point for the 1/4 sec. cor. of secs. 3 and 10, at proportionate dist., there is no remaining evidence of the orig. cor. Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd. <div style="text-align: center;"> <table style="margin: auto;"> <tr><td>T 32 N</td><td>R 10 E</td></tr> <tr><td>S 3</td><td></td></tr> <tr><td>1/4</td><td>—</td></tr> <tr><td>S 10</td><td></td></tr> </table> <p>2006</p> </div> Deposit a magnet, in a white plastic case, at the base of the stainless steel post.	T 32 N	R 10 E	S 3		1/4	—	S 10	
T 32 N	R 10 E								
S 3									
1/4	—								
S 10									
80.16	The cor. of secs. 3, 4, 9 and 10. <hr/>								
	N. 0°11' E., bet. secs. 3 and 4. Over rolling, sandy terrain, through native grasses.								
40.07	Point for the 1/4 sec. cor. of secs. 3 and 4, at proportionate dist., there is no remaining evidence of the orig. cor. Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 12 ins. in the ground, to bedrock, in a supporting mound of stone, 3 ft. base, to top, with brass cap mkd.								

Dependent Resurvey of the Subdivisional Lines,
T. 32 N., R. 10 E., Gila and Salt River Meridian, Arizona

CHAINS	
80.10	<p style="text-align: center;">T 32 N R 10 E 1/4 S 4 S 3</p> <p style="text-align: center;">2006</p> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p> <p>Point for the closing cor. of secs. 3 and 4, at proportionate dist., on the Eighth Standard Parallel North, there is no remaining evidence of the orig. cor.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 25 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T 33 N R 10 E S 33 ----- S 4 S 3 T 32 N R 10 E CC</p> <p style="text-align: center;">2006</p> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p> <p>From this cor. point, the stan. 1/4 sec. cor. of sec. 33, T. 33 N., R. 10 E., bears N. 89°55' W., 18.99 chs. dist., hereinbefore described.</p> <p>From this same cor. point, the stan. cor. of secs. 33 and 34, T. 33 N., R. 10 E., bears S. 89°55' E., 21.08 chs. dist., hereinbefore described.</p> <hr/> <p>Point for the 1/4 sec. cor. of sec. 3 only, T. 32 N., R. 10 E., is at midpoint on the N. bdy. of sec. 3, on the Eighth Standard Parallel North.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T 33 N R 10 E ----- 1/4 S 3 T 32 N R 10 E</p> <p style="text-align: center;">2006</p> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p>

**Dependent Resurvey of the Subdivisional Lines,
T. 32 N., R. 10 E., Gila and Salt River Meridian, Arizona**

CHAINS

From this cor. point, the stan. cor. of secs. 33 and 34, T. 33 N., R. 10 E., bears N. 89°55' W., 18.99 chs. dist., hereinbefore described.

From this same cor. point, the stan. 1/4 sec. cor. of sec. 34, T. 33 N., R. 10 E., bears S. 89°55' E., 21.08 chs. dist., hereinbefore described.

From the cor. of secs. 4, 5, 32 and 33, on the S. bdy. of the Tp., hereinbefore described.

N. 0°28' E., bet. secs. 32 and 33.

Over broken, sandy and rocky terrain, through scattered native grasses.

40.04

The 1/4 sec. cor. of secs. 32 and 33, monumented with a limestone, 19 x 7 x 5 ins., loosely set, 3 ins. in the ground, mkd. 33 on a E. face, with a scattered mound of stone, W. of the cor.

At the corner point

Set a brass tablet, 3 1/4 ins. diam., 3 1/2 ins. stem, cemented in a drill hole, in solid rock, with top mkd.

T 32 N R 10 E
1/4
S 32 | S 33

2006

Deposit a magnet, in the drill hole, beneath the brass tablet.

from which

An exposed sandstone bedrock, bears S. 60 1/2°E., 63 lks. dist., with XBO chiseled on top face.

Rebuild the mound of stone, 2 ft. base, 1 1/2 ft. high, W. of the cor.

Remove the mkd. stone from the area.

Cor. is located 68 lks. N. of an edge of a drainage, 20 ft. wide, 3 ins. deep, drains S. 36° E.

N. 1°50' W., beginning new measurement.

Dependent Resurvey of the Subdivisional Lines,
T. 32 N., R. 10 E., Gila and Salt River Meridian, Arizona

CHAINS									
40.78	<p>The cor. of secs. 28, 29, 32 and 33, monumented with a limestone, 20 x 7 x 5 ins., loosely set, 3 ins. in the ground, mkd. 32N on a face, 10E on a face, 4 notches on an edge and 1 notch on an edge.</p> <p>At the corner point</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 23 ins. in the ground, with brass cap mkd.</p> <table border="1" data-bbox="787 619 1015 724"> <tr> <td colspan="2">T 32 N R 10 E</td> </tr> <tr> <td>S 29</td> <td>S 28</td> </tr> <tr> <td>S 32</td> <td>S 33</td> </tr> </table> <p>2006</p> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p> <p>Deposit the mkd. stone alongside the stainless steel post.</p> <hr/> <p>From the cor. of secs. 27, 28, 33 and 34.</p> <p>N. 89°20' W., bet. secs. 28 and 33.</p> <p>Over rolling, broken sandy and rocky terrain, through native grasses.</p>	T 32 N R 10 E		S 29	S 28	S 32	S 33		
T 32 N R 10 E									
S 29	S 28								
S 32	S 33								
39.98	<p>The 1/4 sec. cor. of secs. 28 and 33, monumented with a sandstone, 18 x 10 x 3 ins., loosely set, 2 ins. in the ground, mkd. 1/4 28 on a face and an X on an end, with a mound of stone, 3 ft. base, 2 ft. high, N. of the cor.</p> <p>At the corner point</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 25 ins. in the ground, with brass cap mkd.</p> <table border="1" data-bbox="787 1501 1015 1627"> <tr> <td colspan="2">T 32 N R 10 E</td> </tr> <tr> <td></td> <td>S 28</td> </tr> <tr> <td>1/4</td> <td>—</td> </tr> <tr> <td></td> <td>S 33</td> </tr> </table> <p>2006</p> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p> <p>Deposit the mkd. stone in the mound of stone.</p> <hr/> <p>N. 89°03' W., beginning new measurement.</p>	T 32 N R 10 E			S 28	1/4	—		S 33
T 32 N R 10 E									
	S 28								
1/4	—								
	S 33								

**Dependent Resurvey of the Subdivisional Lines,
T. 32 N., R. 10 E., Gila and Salt River Meridian, Arizona**

CHAINS	
23.72	Graded road, 25 ft. wide, bears S. 25° E. and N. 25° W.
41.20	The cor. of secs. 28, 29, 32 and 33. <hr/>
	N. 0°58' E., bet. secs. 28 and 29. Over rolling, broken sandy and rocky terrain, through native grasses.
39.79	Point for the 1/4 sec. cor. of secs. 28 and 29, at proportionate dist., there is no remaining evidence of the orig. cor. Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd. <div style="text-align: center;"> T 32 N R 10 E 1/4 S 29 S 28 2006 </div> Deposit a magnet, in a white plastic case, at the base of the stainless steel post.
79.58	Point for the cor. of secs. 20, 21, 28 and 29, at proportionate dist., there is no remaining evidence of the orig. cor. Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd. <div style="text-align: center;"> T 32 N R 10 E S 20 S 21 S 29 S 28 2006 </div> Deposit a magnet, in a white plastic case, at the base of the stainless steel post. Cor. is located in a old cultivated field. Set a steel fence post nearby. <hr/>
	From the cor. of secs. 21, 22, 27 and 28. N. 89°36' W., bet. secs. 21 and 28. Over rolling, sandy terrain, through medium growth sagebrush and native grasses.

**Dependent Resurvey of the Subdivisional Lines,
T. 32 N., R. 10 E., Gila and Salt River Meridian, Arizona**

CHAINS	
40.11	<p>Point for the 1/4 sec. cor. of secs. 21 and 28, at proportionate dist., there is no remaining evidence of the orig. cor.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T 32 N R 10 E S 21 1/4 ——— S 28</p> <p style="text-align: center;">2006</p> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p>
80.22	<p>The cor. of secs. 20, 21, 28 and 29.</p> <hr/> <p>N. 0°02' W., bet. secs. 20 and 21.</p> <p>Over rolling, sandy terrain, through medium growth sagebrush and native grasses.</p>
28.83	Barbed wire fence, bears S. 75° E. and N. 75° W.
29.17	Graded road, 30 ft. wide, bears S. 75° E. and N. 75° W.
29.35	Barbed wire fence, bears S. 75° E. and N. 75° W.
39.79	<p>Point for the 1/4 sec. cor. of secs. 20 and 21, at proportionate dist., there is no remaining evidence of the orig. cor.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T 32 N R 10 E 1/4 S 20 S 21</p> <p style="text-align: center;">2006</p> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p> <p>Cor. is located in a cultivated field.</p> <p>Set a steel fence post nearby.</p>
79.58	<p>The cor. of secs. 16, 17, 20 and 21, monumented with a limestone, 14 x 6 x 5 ins., loosely set, 3 ins. in the ground, mkd. 32N on a face, 10E on a face, 4 notches on an edge and 3 notches on an edge.</p>

**Dependent Resurvey of the Subdivisional Lines,
T. 32 N., R. 10 E., Gila and Salt River Meridian, Arizona**

CHAINS									
	<p>At the corner point</p> <p>Set a brass tablet, 3 1/4 ins. diam., 3 1/2 ins. stem, cemented in a drill hole, in solid rock, with top mkd.</p> <table border="1" data-bbox="795 462 1023 567"> <tr> <td>T 32 N</td> <td>R 10 E</td> </tr> <tr> <td>S 17</td> <td>S 16</td> </tr> <tr> <td>S 20</td> <td>S 21</td> </tr> </table> <p align="center">2006</p> <p>Deposit a magnet, in the drill hole, beneath the brass tablet.</p> <p>Remove the mkd. stone from the area.</p> <p>Cor. is located on the S. edge of a small mesa.</p> <hr/> <p>From the cor. of secs. 15, 16, 21 and 22.</p> <p>S. 89°58' W., bet. secs. 16 and 21.</p> <p>Over level to rolling, sandy terrain, through medium growth sagebrush and canatilla.</p>	T 32 N	R 10 E	S 17	S 16	S 20	S 21		
T 32 N	R 10 E								
S 17	S 16								
S 20	S 21								
40.03	<p>Point for the 1/4 sec. cor. of secs. 16 and 21, at proportionate dist., there is no remaining evidence of the orig. cor.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <table border="1" data-bbox="779 1260 1023 1375"> <tr> <td>T 32 N</td> <td>R 10 E</td> </tr> <tr> <td></td> <td>S 16</td> </tr> <tr> <td></td> <td>1/4 ———</td> </tr> <tr> <td></td> <td>S 21</td> </tr> </table> <p align="center">2006</p> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p>	T 32 N	R 10 E		S 16		1/4 ———		S 21
T 32 N	R 10 E								
	S 16								
	1/4 ———								
	S 21								
80.06	<p>The cor. of secs. 16, 17, 20 and 21.</p> <hr/> <p>N. 0°06' E., bet. secs. 16 and 17.</p> <p>Over level to rolling, sandy terrain, through native grasses and canatilla.</p>								

**Dependent Resurvey of the Subdivisional Lines,
T. 32 N., R. 10 E., Gila and Salt River Meridian, Arizona**

CHAINS	
39.96	<p>The 1/4 sec. cor. of secs. 16 and 17, monumented with a limestone, 15 x 6 x 4 ins., loosely set, 2 ins. in the ground, mkd. 1/4 17 on a face, 16 on a face and an X on an end, with a sandstone, 13 x 10 x 5 ins, mkd. 1/4 17, lying nearby, with a mound of stone, 2 ft. base, 1/2 ft. high, W. of the cor.</p> <p>At the corner point</p> <p>Set a brass tablet, 3 1/4 ins. diam., 3 1/2 ins. stem, cemented in a drill hole, in solid rock, with top mkd.</p> <p style="text-align: center;">T 32 N R 10 E 1/4 S 17 S 16</p> <p style="text-align: center;">2006</p> <p>Deposit a magnet, in the drill hole, beneath the brass tablet.</p> <p>Rebuild the mound of stone, 2 ft. base, 1 1/2 ft. high, W. of the cor. and deposit the mkd. stones in the mound of stone.</p> <hr style="width: 20%; margin: 10px auto;"/> <p>N. 0° 19' E., beginning new measurement.</p>
40.09	<p>The cor. of secs. 8, 9, 16 and 17, monumented with a limestone, 18 x 6 x 5 ins., loosely set, 3 ins. in the ground, mkd. 32N on a face, 10E on a face, 4 notches on an edge and 4 notches on an edge.</p> <p>At the corner point</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 25 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T 32 N R 10 E S 8 S 9 S 17 S 16</p> <p style="text-align: center;">2006</p> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p> <p>Deposit the mkd. stone alongside the stainless steel post.</p> <hr style="width: 20%; margin: 10px auto;"/> <p>From the cor. of secs. 9, 10, 15 and 16.</p> <p>S. 89°36' W., bet. secs. 9 and 16.</p> <p>Over rolling, sandy terrain, through native grasses and scattered cacti.</p>

**Dependent Resurvey of the Subdivisional Lines,
T. 32 N., R. 10 E., Gila and Salt River Meridian, Arizona**

CHAINS	
40.11	<p>The 1/4 sec. cor. of secs. 9 and 16, monumented with a limestone, 18 x 7 x 5 ins., loosely set, 3 ins. in the ground, mkd. 1/4 9 on a face and 16 on a face.</p> <p>At the corner point</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 25 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T 32 N R 10 E S 9 1/4 ——— S 16</p> <p style="text-align: center;">2006</p> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p> <p>Deposit the mkd. stone alongside the stainless steel post.</p> <hr style="width: 20%; margin: 10px auto;"/> <p>N. 89°49' W., beginning new measurement.</p>
39.70	<p>The cor. of secs. 8, 9, 16 and 17.</p> <hr style="width: 80%; margin: 10px auto;"/> <p>N. 0°03' W., bet. secs. 8 and 9.</p> <p>Over rolling, sandy terrain, through native grasses and scattered cacti.</p>
40.09	<p>The 1/4 sec. cor. of secs. 8 and 9, monumented with a limestone, 16 x 6 x 6 ins., firmly set, 14 ins. in the ground, mkd. 8 on the W. face and 9 on the E. face.</p> <p>At the corner point</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 25 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T 32 N R 10 E 1/4 S 8 S 9</p> <p style="text-align: center;">2006</p> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p>

**Dependent Resurvey of the Subdivisional Lines,
T. 32 N., R. 10 E., Gila and Salt River Meridian, Arizona**

CHAINS

Deposit the mkd. stone alongside the stainless steel post.

N. 0°11' E., beginning new measurement.

40.03

The cor. of secs. 4, 5, 8 and 9, monumented with a limestone, 14 x 9 x 8 ins., loosely set, 4 ins. in the ground, mkd. 32N on a face, 10E on a face, 4 notches on an edge and 5 notches on an edge, with a sandstone, 9 x 8 x 4 ins, mkd. 10E and 4 faint grooves on a face, lying nearby.

At the corner point

Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 25 ins. in the ground, with brass cap mkd.

T 32 N	R 10 E
S 5	S 4
S 8	S 9

2006

Deposit a magnet, in a white plastic case, at the base of the stainless steel post.

Deposit the mkd. stones alongside the stainless steel post.

From the cor. of secs. 3, 4, 9 and 10.

S. 89°53' W., bet. secs. 4 and 9.

Over rolling, sandy terrain, through native grasses and scattered cacti.

40.11

Point for the 1/4 sec. cor. of secs. 4 and 9, at proportionate dist., there is no remaining evidence of the orig. cor.

Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.

T 32 N	R 10 E
	S 4
1/4	—
	S 9

2006

Deposit a magnet, in a white plastic case, at the base of the stainless steel post.

**Dependent Resurvey of the Subdivisional Lines,
T. 32 N., R. 10 E., Gila and Salt River Meridian, Arizona**

CHAINS	
80.22	<p>The cor. of secs. 4, 5, 8 and 9.</p> <hr/> <p>N. 0°13' E., bet. secs. 4 and 5.</p> <p>Over rolling, sandy terrain, through scattered juniper and native grasses.</p>
40.06	<p>The 1/4 sec. cor. of secs. 4 and 5, monumented with a limestone, 16 x 11 x 4 ins., loosely set, 2 ins. in the ground, mkd. 1/4 5 on a face and S4 on a face, with a sandstone, 15 x 8 x 6 ins., mkd. 1/4 5 on a face and S4 on a face, lying nearby.</p> <p>At the corner point</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center;"> <p>T 32 N R 10 E</p> <p>1/4</p> <p>S 5 S 4</p> <p>2006</p> </div> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p> <p>Deposit the mkd. stones alongside the stainless steel post.</p> <hr/> <p>N. 0°19' E., beginning new measurement.</p> <p>Over rolling, sandy terrain, across sandstone surfaces and sandstone outcrops.</p>
40.28	<p>The closing cor. of secs. 4 and 5, monumented with a limestone, 14 x 7 x 6 ins., loosely set, 3 ins. in the ground, mkd. CC on a face, 2 notches on an edge and 4 notches on an edge. Add the marks AM and bury the stone in place.</p>
40.32	<p>Point for the closing cor. of secs. 4 and 5, at intersection with the Eighth Standard Parallel North.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 25 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center;"> <p>T 33 N R 10 E</p> <p>S 32</p> <hr/> <p>S 5 S 4</p> <p>T 32 N R 10 E</p> <p>CC</p> <p>2006</p> </div>

**Dependent Resurvey of the Subdivisional Lines,
T. 32 N., R. 10 E., Gila and Salt River Meridian, Arizona**

CHAINS

Deposit a magnet, in a white plastic case, at the base of the stainless steel post.

From this cor. point, the stan. 1/4 sec. cor. of sec. 32, T. 33 N., R. 10 E., bears N. 89°55' W., 19.05 chs. dist., hereinbefore described.

From this same cor. point, the stan. cor. of secs. 32 and 33, T. 33 N., R. 10 E., bears S. 89°55' E., 21.02 chs. dist., hereinbefore described.

Point for the 1/4 sec. cor. of sec. 4 only, T. 32 N., R. 10 E., is at midpoint on the N. bdy. of sec. 4, on the Eighth Standard Parallel North.

Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 25 ins. in the ground, with brass cap mkd.

T 33 N R 10 E

1/4 S 4

T 32 N R 10 E

2006

Deposit a magnet, in a white plastic case, at the base of the stainless steel post.

From this cor. point, the stan. cor. of secs. 32 and 33, T. 33 N., R. 10 E., bears N. 89°55' W., 19.025 chs. dist., hereinbefore described.

From this same cor. point, the stan. 1/4 sec. cor. of sec. 33, T. 33 N., R. 10 E., bears S. 89°55' E., 21.045 chs. dist., hereinbefore described.

From the true point for the cor. of secs. 5, 6, 31 and 32, on the S. bdy. of the Tp., hereinbefore described.

N. 0°24' E., bet. secs. 31 and 32.

Over rough, rocky terrain.

40.02

The 1/4 sec. cor. of secs. 31 and 32, determined at the E. edge of a mound of stone, 2 ft. base, 1 1/2 ft. high; and is accepted as the best available evidence of the position of the original corner.

At the corner point

**Dependent Resurvey of the Subdivisional Lines,
T. 32 N., R. 10 E., Gila and Salt River Meridian, Arizona**

CHAINS	
	<p>Set a brass tablet, 3 1/4 ins. diam., 3 1/2 ins. stem, cemented in a drill hole, in solid rock, with top mkd.</p> <p style="text-align: center;">T 32 N R 10 E 1/4 S 31 S 32</p> <p style="text-align: center;">2006</p> <p>Deposit a magnet, in the drill hole, beneath the brass tablet.</p> <hr style="width: 20%; margin: auto;"/> <p>N. 0°19' E., beginning new measurement.</p>
39.96	<p>The cor. of secs. 29, 30, 31 and 32, monumented with a limestone, 18 x 6 x 5 ins., loosely set, 3 ins. in the ground, mkd. 32N on a face and 10E on a face, with a sandstone, 17 x 4 x 4 ins., mkd. 32N on a face, 10E on a face, 1 notch on an edge and 5 notches on an edge, lying nearby.</p> <p>At the corner point</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 20 ins. in the ground, encircled with a collar of stone, with brass cap mkd.</p> <p style="text-align: center;">T 32 N R 10 E S 30 S 29 S 31 S 32</p> <p style="text-align: center;">2006</p> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p> <p>Deposit the mkd. stones alongside the stainless steel post.</p> <hr style="width: 20%; margin: auto;"/> <p>From the cor. of secs. 28, 29, 32 and 33.</p> <p>S. 88°45' W., bet. secs. 29 and 32.</p> <p>Over broken sandstone outcroppings.</p>
38.81	<p>The 1/4 sec. cor. of secs. 29 and 32, monumented with a limestone, 14 x 9 x 4 ins., firmly set, 8 ins. in the ground, mkd. 1/4 29 on the N. face and 32 on the S. face, with a mound of stone, 2 ft. base, 1 ft. high, N. of the cor.</p> <p>At the corner point</p>

Dependent Resurvey of the Subdivisional Lines,
T. 32 N., R. 10 E., Gila and Salt River Meridian, Arizona

CHAINS	
	<p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 7 ins. in the ground, to bedrock, in a supporting mound of stone, 5 ft. base, to top, with brass cap mkd.</p> <p style="text-align: center;">T 32 N R 10 E S 29 1/4 ——— S 32</p> <p style="text-align: center;">2006</p> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p> <p>Utilize the mound of stone and deposit the mkd. stone in the supporting mound of stone.</p> <hr style="width: 20%; margin: 10px auto;"/> <p>N. 89°43' W., beginning new measurement.</p>
40.10	<p>The cor. of secs. 29, 30, 31 and 32.</p> <hr style="width: 80%; margin: 10px auto;"/>
	<p>N. 89°58' W., bet. secs. 30 and 31.</p> <p>Over rolling, rocky terrain.</p>
39.87	<p>The 1/4 sec. cor. of secs. 30 and 31, monumented with a limestone, 20 x 6 x 6 ins., loosely set, 3 ins. in the ground, mkd. 1/4 30 on a face and 31 on a face, with a scattered mound of stone, N. of the cor.</p> <p>At the corner point</p> <p>Set a brass tablet, 3 1/4 ins. diam., 3 1/2 ins. stem, cemented in a concrete collar, with top mkd.</p> <p style="text-align: center;">T 32 N R 10 E S 30 1/4 ——— S 31</p> <p style="text-align: center;">2006</p> <p>Deposit a magnet, in the concrete collar, beneath the brass tablet.</p> <p>Rebuild the mound of stone, 3 ft. base, 2 ft. high, N. of the cor. and deposit the mkd. stone in the mound of stone.</p> <hr style="width: 20%; margin: 10px auto;"/> <p>S. 89°37' W., beginning new measurement.</p>

**Dependent Resurvey of the Subdivisional Lines,
T. 32 N., R. 10 E., Gila and Salt River Meridian, Arizona**

CHAINS	
38.38	<p>The cor. of secs. 25, 30, 31 and 36, on the W. bdy. of the Tp., hereinbefore described.</p> <hr/> <p>From the cor. of secs. 29, 30, 31 and 32.</p> <p>N. 0°15' E., bet. secs. 29 and 30.</p> <p>Over rolling, rocky terrain and sandstone outcroppings.</p>
40.11	<p>The 1/4 sec. cor. of secs. 29 and 30, monumented with a limestone, 16 x 6 x 4 ins., loosely set, 2 ins. in the ground, mkd. 1/4 30 on a face and 29 on a face.</p> <p>At the corner point</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 16 ins. in the ground, to bedrock, in a supporting mound of stone, 3 ft. base, to top, with brass cap mkd.</p> <div style="text-align: center;"> <p>T 32 N R 10 E 1/4 S 30 S 29</p> <p>2006</p> </div> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p> <p>Deposit the mkd. stone in the supporting mound of stone.</p> <hr/> <p>N. 0°16' W., beginning new measurement.</p>
39.89	<p>The cor. of secs. 19, 20, 29 and 30, monumented with a limestone, 13 x 7 x 6 ins., loosely set, 3 ins. in the ground, mkd. 32N on a face, 10E on a face, 5 notches on an edge and 2 notches on an edge, with a mound of stone, 3 ft. base, 2 ft. high, W. of the cor.</p> <p>At the corner point</p> <p>Set a brass tablet, 3 1/4 ins. diam., 3 1/2 ins. stem, cemented in a concrete collar, with top mkd.</p> <div style="text-align: center;"> <p>T 32 N R 10 E S 19 S 20 S 30 S 29</p> <p>2006</p> </div> <p>Deposit a magnet, in the concrete collar, beneath the brass tablet.</p>

Dependent Resurvey of the Subdivisional Lines,
T. 32 N., R. 10 E., Gila and Salt River Meridian, Arizona

CHAINS	
40.11	<p>Deposit the mkd. stone in the mound of stone.</p> <hr/> <p>From the cor. of secs. 20, 21, 28 and 29.</p> <p>S. 89°50' W., bet. secs. 20 and 29.</p> <p>Over rolling, broken sandy and rocky terrain, through native grasses.</p> <p>Point for the 1/4 sec. cor. of secs 20 and 29, at proportionate dist., there is no remaining evidence of the orig. cor.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T 32 N R 10 E S 20 1/4 ——— S 29</p> <p style="text-align: center;">2006</p> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p>
80.22	<p>The cor. of secs. 19, 20, 29 and 30.</p> <hr/> <p>N. 89°52' W., bet. secs. 19 and 30.</p> <p>Over rolling, broken sandy and rocky terrain, through native grasses.</p>
40.04	<p>The 1/4 sec. cor. of secs. 19 and 30, determined at the S. edge of a mound of stone, 2 ft. base, 1/2 ft. high; and is accepted as the best available evidence of the position of the original corner, with a limestone, 16 x 7 x 4 ins., mkd. 1/4 19 on a face and 30 on a face, lying nearby.</p> <p>At the corner point</p> <p>Set a brass tablet, 3 1/4 ins. diam., 3 1/2 ins. stem, cemented in a drill hole, in solid rock, with top mkd.</p> <p style="text-align: center;">T 32 N R 10 E S 19 1/4 ——— S 30</p> <p style="text-align: center;">2006</p> <p>Deposit a magnet, in the drill hole, beneath the brass tablet.</p>

**Dependent Resurvey of the Subdivisional Lines,
T. 32 N., R. 10 E., Gila and Salt River Meridian, Arizona**

CHAINS	
	<p>Rebuild the mound of stone, 2 ft. base, 1 1/2 ft. high and deposit the mkd. stone in the mound of stone.</p> <hr style="width: 20%; margin: auto;"/> <p>N. 89°56' W., beginning new measurement.</p>
38.19	<p>The cor. of secs. 19, 24, 25 and 30, on the W. bdy. of the Tp., hereinbefore described.</p> <hr style="width: 20%; margin: auto;"/> <p>From the cor. of secs. 19, 20, 29 and 30.</p> <p>N. 0°07' E., bet. secs. 19 and 20.</p> <p>Over rolling, rocky terrain.</p>
40.05	<p>The 1/4 sec. cor. of secs. 19 and 20, monumented with a limestone, 16 x 6 x 6 ins., firmly set, 10 ins. in the ground, mkd. 1/4 19 on the W. face and 20 on the E. face.</p> <p>At the corner point</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 23 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center;"> <p>T 32 N R 10 E 1/4 S 19 S 20</p> <p>2006</p> </div> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p> <p>Deposit the mkd. stone alongside the stainless steel post.</p> <hr style="width: 20%; margin: auto;"/> <p>N. 0°03' E., beginning new measurement.</p>
40.02	<p>Point for the cor. of secs. 17, 18, 19 and 20, at proportionate dist., there is no remaining evidence of the orig. cor.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center;"> <p>T 32 N R 10 E S 18 S 17 S 19 S 20</p> <p>2006</p> </div>

**Dependent Resurvey of the Subdivisional Lines,
T. 32 N., R. 10 E., Gila and Salt River Meridian, Arizona**

CHAINS	
	<p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p> <hr/> <p>From the cor. of secs. 16, 17, 20 and 21.</p> <p>N. 89°55' W., bet. secs. 17 and 20.</p> <p>Over rolling, sandy terrain and sandstone outcrops.</p>
40.04	<p>The 1/4 sec. cor. of secs. 17 and 20, monumented with a limestone, 16 x 6 x 6 ins., loosely set, 3 ins. in the ground, mkd. 1/4 17 on a face and 20 on a face, with a mound of stone, 2 ft. base, 1 ft. high, N. of the cor.</p> <p>At the corner point</p> <p>Set a brass tablet, 3 1/4 ins. diam., 3 1/2 ins. stem, cemented in a drill hole, in solid rock, with top mkd.</p> <div style="text-align: center;"> <p>T 32 N R 10 E</p> <p>S 17</p> <p>1/4 <u> </u></p> <p>S 20</p> <p>2006</p> </div> <p>Deposit a magnet, in the drill hole, beneath the brass tablet.</p> <p>Rebuild the mound of stone, 3 ft. base, 2 1/2 ft. high and deposit the mkd. stone in the mound of stone.</p> <hr/> <p>N. 89°42' W., beginning new measurement.</p>
40.01	<p>The cor. of secs. 17, 18, 19 and 20.</p> <hr/> <p>N. 89°54' W., bet. secs. 18 and 19.</p> <p>Over rocky, sandstone terrain.</p>
39.99	<p>Point for the 1/4 sec. cor. of secs. 18 and 19, at proportionate dist., there is no remaining evidence of the orig. cor.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p>

Dependent Resurvey of the Subdivisional Lines,
T. 32 N., R. 10 E., Gila and Salt River Meridian, Arizona

CHAINS	
	<p style="text-align: center;">T 32 N R 10 E S 18 1/4 ——— S 19</p> <p style="text-align: center;">2006</p>
78.23	<p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p> <p>The cor. of secs. 13, 18, 19 and 24, on the W. bdy. of the Tp., hereinbefore described.</p> <hr/>
	<p>From the cor. of secs. 17, 18, 19 and 20.</p> <p>N. 0°30' E., bet. secs. 17 and 18.</p> <p>Over level, sandy terrain, through heavy growth sagebrush.</p>
35.46	<p>Top edge of a mesa, 300 ft. high, bears S. 46° E. and N. 33° W.</p>
40.02	<p>Point for the 1/4 sec. cor. of secs. 17 and 18, at proportionate dist., there is no remaining evidence of the orig. cor.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p>
	<p style="text-align: center;">T 32 N R 10 E 1/4 S 18 S 17</p> <p style="text-align: center;">2006</p>
80.04	<p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p> <p>The cor. of secs. 7, 8, 17 and 18, monumented with a sandstone, 16 x 5 x 4 ins., loosely set, 2 ins. in the ground, mkd. 4 notches on an edge and 2 notches on an edge.</p> <p>At the corner point</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T 32 N R 10 E S 7 S 8 S 18 S 17</p> <p style="text-align: center;">2006</p>

**Dependent Resurvey of the Subdivisional Lines,
T. 32 N., R. 10 E., Gila and Salt River Meridian, Arizona**

CHAINS	
39.60	<p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p> <p>Deposit the mkd. stone alongside the stainless steel post.</p> <hr/> <p>From the cor. of secs. 8, 9, 16 and 17.</p> <p>N. 89°51' W., bet. secs. 8 and 17.</p> <p>Over level to rolling, sandy terrain, through medium growth sagebrush and native grasses.</p> <p>The 1/4 sec. cor. of secs. 8 and 17, monumented with a limestone, 16 x 7 x 4 ins., loosely set, 2 ins. in the ground, mkd. 1/4 8 on a face and 17 on a face.</p> <p>At the corner point</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 25 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center;"> <p>T 32 N R 10 E</p> <p>S 8</p> <p>1/4 ———</p> <p>S 17</p> <p>2006</p> </div> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p> <p>Deposit the mkd. stone alongside the stainless steel post.</p> <hr/> <p>N. 89°46' W., beginning new measurement.</p>
40.03	<p>The cor. of secs. 7, 8, 17 and 18.</p> <hr/> <p>N. 89°52' W., bet. secs. 7 and 18.</p> <p>Over broken terrain, through sandstone outcroppings.</p>
40.05	<p>The 1/4 sec. cor. of secs. 7 and 18, monumented with a limestone, 18 x 5 x 5 ins., firmly set, 10 ins. in the ground, mkd. 1/4 7 on the N. face and 18 on the S. face, with a mound of stone, 2 ft. base, 1/2 ft. high, N. of the cor.</p> <p>At the corner point</p>

**Dependent Resurvey of the Subdivisional Lines,
T. 32 N., R. 10 E., Gila and Salt River Meridian, Arizona**

CHAINS	
	<p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 12 ins. in the ground, to bedrock, in a supporting mound of stone, 5 ft. base, to top, with brass cap mkd.</p> <p style="text-align: center;">T 32 N R 10 E S 7 1/4 ——— S 18</p> <p style="text-align: center;">2006</p> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p> <p>Utilize the mound of stone and deposit the mkd. stone in the supporting mound of stone.</p> <hr style="width: 20%; margin: auto;"/> <p>S. 89°51' W., beginning new measurement.</p>
38.68	<p>The true point for the cor. of secs. 7, 12, 13 and 18, on the W. bdy. of the Tp., hereinbefore described.</p> <hr style="width: 80%; margin: auto;"/> <p>From the cor. of secs. 7, 8, 17 and 18.</p> <p>N. 0°04' E., bet. secs. 7 and 8.</p> <p>Over rolling, sandy terrain, through medium growth sagebrush, native grasses and cacti.</p>
40.04	<p>The 1/4 sec. cor. of secs. 7 and 8, determined at the E. edge of a mound of stone, 2 ft. base, 1 ft. high; and is accepted as the best available evidence of the position of the original corner.</p> <p>At the corner point</p> <p>Set a brass tablet, 3 1/4 ins. diam., 3 1/2 ins. stem, cemented in a drill hole, in solid rock, with top mkd.</p> <p style="text-align: center;">T 32 N R 10 E 1/4 S 7 S 8</p> <p style="text-align: center;">2006</p> <p>Deposit a magnet, in the drill hole, beneath the brass tablet.</p> <p>Rebuild the mound of stone, 2 ft. base, 2 ft. high, W. of the cor.</p> <hr style="width: 20%; margin: auto;"/> <p>N. 0°05' E., beginning new measurement.</p>

**Dependent Resurvey of the Subdivisional Lines,
T. 32 N., R. 10 E., Gila and Salt River Meridian, Arizona**

CHAINS									
40.01	<p>The cor. of secs. 5, 6, 7 and 8, monumented with a sandstone, 15 x 10 x 5 ins., loosely set, 3 ins. in the ground, mkd. 5 grooves on a face and 5 grooves and 3 on a face, with a malpais stone, 13 x 7 x 7 ins., mkd. 32N on a face, 10E on a face, 5 notches on a edge and 5 notches on a edge, lying nearby.</p> <p>At the corner point</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 25 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center;"> <table style="margin-left: auto; margin-right: auto;"> <tr><td>T 32 N</td><td>R 10 E</td></tr> <tr><td>S 6</td><td>S 5</td></tr> <tr><td>S 7</td><td>S 8</td></tr> </table> <p>2006</p> </div> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p> <p>Deposit the mkd. stones alongside the stainless steel post.</p> <hr/> <p>From the cor. of secs. 4, 5, 8 and 9.</p> <p>N. 89°52' W., bet. secs. 5 and 8.</p> <p>Over rolling, sandy terrain, through medium growth sagebrush and native grasses.</p>	T 32 N	R 10 E	S 6	S 5	S 7	S 8		
T 32 N	R 10 E								
S 6	S 5								
S 7	S 8								
39.80	<p>Point for the 1/4 sec. cor. of secs 5 and 8, at proportionate dist., there is no remaining evidence of the orig. cor.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 25 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center;"> <table style="margin-left: auto; margin-right: auto;"> <tr><td>T 32 N</td><td>R 10 E</td></tr> <tr><td>S 5</td><td></td></tr> <tr><td>1/4</td><td>—</td></tr> <tr><td>S 8</td><td></td></tr> </table> <p>2006</p> </div> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p>	T 32 N	R 10 E	S 5		1/4	—	S 8	
T 32 N	R 10 E								
S 5									
1/4	—								
S 8									
79.60	<p>The cor. of secs. 5, 6, 7 and 8.</p> <hr/> <p>N. 89°56' W., bet. secs. 6 and 7.</p> <p>Over broken terrain, through sandstone outcroppings.</p>								

**Dependent Resurvey of the Subdivisional Lines,
T. 32 N., R. 10 E., Gila and Salt River Meridian, Arizona**

CHAINS	
40.06	<p>The 1/4 sec. cor. of secs. 6 and 7, monumented with a limestone, 15 x 5 x 4 ins., loosely set, 2 ins. in the ground, mkd. 1/4 6 on a face and 7 on a face, with a mound of stone, 1 ft. base, 1/2 ft. high, N. of the cor.</p> <p>At the corner point</p> <p>Set a brass tablet, 3 1/4 ins. diam., 3 1/2 ins. stem, cemented in a drill hole, in solid rock, with top mkd.</p> <div style="text-align: center;"> <p>T 32 N R 10 E</p> <p>S 6</p> <p>1/4 ———</p> <p>S 7</p> <p>2006</p> </div> <p>Deposit a magnet, in the drill hole, beneath the brass tablet.</p> <p>Remove the mkd. stone from the area.</p> <hr style="width: 20%; margin: 10px auto;"/> <p>N. 88°18' W., beginning new measurement.</p>
38.83	<p>The true point for the cor. of secs. 1, 6, 7 and 12, on the W. bdy. of the Tp., hereinbefore described.</p> <hr style="width: 60%; margin: 10px auto;"/> <p>From the cor. of secs. 5, 6, 7, and 8.</p> <p>N. 0°02' E., bet. secs. 5 and 6.</p> <p>Over rolling, sandy terrain, through medium growth sagebrush and native grasses.</p>
40.07	<p>The 1/4 sec. cor. of secs 5 and 6, monumented with a limestone, 19 x 8 x 6 ins., loosely set, 3 ins. in the ground, mkd. 1/4 6 on a face and 5 on a face.</p> <p>At the corner point</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 25 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center;"> <p>T 32 N R 10 E</p> <p>1/4</p> <p>S 6 S 5</p> <p>2006</p> </div> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p>

**Dependent Resurvey of the Subdivisional Lines,
T. 32 N., R. 10 E., Gila and Salt River Meridian, Arizona**

CHAINS

Deposit the mkd. stone alongside the stainless steel post.

Cor. is located 10 lks. E. of a sandstone spur ridge, bears N. 5° E. and S. 5° W.

N. 0°12' W., beginning new measurement.

40.14

Point for the closing cor. of secs. 5 and 6, T. 32 N., R. 10 E., is at intersection with the Eighth Standard Parallel North.

Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 17 ins. in the ground, to bedrock, in a supporting mound of stone, 3 ft. base, to top, with brass cap mkd.

T 33 N	R 10 E
S 31	
S 6	S 5
T 32 N R 10 E	
CC	

2006

Deposit a magnet, in a white plastic case, at the base of the stainless steel post.

From this cor. point, the closing cor. of sec. 5 and 6, monumented with a basalt stone, 15 x 8 x 5 1/2 ins., firmly set, 8 ins. in the ground, mkd. CC on the S. face, 5 notches on the E. edge and 1 notch on the W. edge, bears N. 0°12' W., 3 lks. dist. Add the marks AM and bury the stone in place.

From this same cor. point, the stan. 1/4 sec. cor. of sec. 31, T. 33 N., R. 10 E., bears West, 18.94 chs. dist., hereinbefore described.

From this same cor. point, the stan. cor. of secs. 31 and 32, T. 33 N., R. 10 E. bears East, 21.05 chs. dist., hereinbefore described.

Point for the 1/4 sec. cor. of sec. 5 only, T. 32 N., R. 10 E., is at midpoint on the N. bdy. of sec. 5, on the Eighth Standard Parallel North.

Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 16 ins. in the ground, to bedrock, in a supporting mound of stone, 4 ft. base, to top, with brass cap mkd.

**Dependent Resurvey of the Subdivisional Lines,
T. 32 N., R. 10 E., Gila and Salt River Meridian, Arizona**

CHAINS

T 33 N R 10 E

1/4 S 5

T 32 N R 10 E

2006

Deposit a magnet, in a white plastic case, at the base of the stainless steel post.

From this cor. point, the stan. cor. of secs. 31 and 32, T. 33 N., R. 10 E., bears West, 18.99 chs. dist., hereinbefore described.

From this same cor. point, the stan. 1/4 sec. cor. of sec. 32, T. 33 N., R. 10 E., bears East, 20.99 chs. dist., hereinbefore described.

Point for the 1/4 sec. cor. of sec. 6 only, T. 32 N., R. 10 E., at proportionate dist. on the N. bdy. of sec. 6, on the Eighth Standard Parallel North.

Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.

T 33 N R 10 E

1/4 S 6

T 32 N R 10 E

2006

Deposit a magnet, in a white plastic case, at the base of the stainless steel post.

From this cor. point, the stan. cor. of Tps. 33 N., Rs. 9 and 10 E., bears N. 89°58' W., 19.24 chs. dist., hereinbefore described.

From this same cor. point, the stan. 1/4 sec. cor. of sec. 31, T. 33 N., R. 10 E., bears S. 89°58' E., 20.81 chs. dist., hereinbefore described.

**Subdivision of Section 1,
T. 32 N., R. 10 E., Gila and Salt River Meridian, Arizona**

From the 1/4 sec. cor. of secs. 1 and 12.

N. 0°03' E., on the N. and S. center line of sec. 1.

**Subdivision of Section 1,
T. 32 N., R. 10 E., Gila and Salt River Meridian, Arizona**

CHAINS	
	Over sandy, broken terrain, through sandstone outcroppings.
40.09	Point for the center 1/4 sec. cor. of sec. 1, at intersection with the E. and W. center line. Set a brass tablet, 3 1/4 ins. diam., 3 1/2 ins. stem, cemented in a drill hole, in solid rock, with top mkd. T 32 N R 10 E C 1/4 S 1 2006 Deposit a magnet, in the drill hole, beneath the brass tablet.
80.16	The 1/4 sec. cor. of sec. 1 only, on the Eighth Standard Parallel North. <hr/>
	From the 1/4 sec. cor. of secs. 1 and 6, on the E. bdy. of the Tp., monumented with a brass tablet, 3 1/4 ins. diam., cemented in solid rock, with top mkd. T32N 1/4 R10E R11E S1 S6 2005. N. 89°52' W., on the E. and W. center line of sec. 1. Over sandy, broken terrain, through sandstone outcroppings.
39.97	The center 1/4 sec. cor. of sec. 1.
74.51	Trail road, 10 ft. wide, bears N. 30° E. and S. 30° W.
79.94	The 1/4 sec. cor. of secs. 1 and 2. <hr/>
	Subdivision of Section 2, T. 32 N., R. 10 E., Gila and Salt River Meridian, Arizona
	From the 1/4 sec. cor. of secs. 2 and 11. N. 0°08' E., on the N. and S. center line of sec. 2. Over rolling, sandy terrain, through medium growth sagebrush and native grasses.
39.94	Point for the center 1/4 sec. cor. of sec. 2, at intersection with the E. and W. center line. Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.

**Subdivision of Section 2,
T. 32 N., R. 10 E., Gila and Salt River Meridian, Arizona**

CHAINS	
	<p>T 32 N R 10 E C 1/4 S 2</p> <p>2006</p>
	<p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p> <p>Set a steel fence post nearby.</p>
80.07	<p>The 1/4 sec. cor. of sec. 2 only, on the Eighth Standard Parallel North.</p> <hr/> <p>From the 1/4 sec. cor. of secs. 1 and 2.</p> <p>S. 89°56' W., on the E. and W. center line of sec. 2.</p> <p>Over rolling, sandy terrain, through medium growth sagebrush and native grasses.</p>
9.78	Trail road, 10 ft. wide, bears S. 5° E. and N. 5° W.
23.47	Graded road, 20 ft. wide, bears S. 65° E. and N. 65 W.
39.97	The center 1/4 sec. cor. of sec. 2.
79.72	The 1/4 sec. cor. of secs. 2 and 3.
	<p>Subdivision of Section 3, T. 32 N., R. 10 E., Gila and Salt River Meridian, Arizona</p> <hr/>
	<p>From the 1/4 sec. cor. of secs. 3 and 10.</p> <p>N. 0°11' E., on the N. and S. center line of sec. 3.</p> <p>Over rolling, sandy terrain, through medium growth sagebrush and native grasses.</p>
3.99	Trail road, 10 ft. wide, bears S. 75° E. and S. 85° W.
39.94	<p>Point for the center 1/4 sec. cor. of sec. 3, at intersection with the E. and W. center line.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p>
	<p>T 32 N R 10 E C 1/4 S 3</p> <p>2006</p>

**Subdivision of Section 3,
T. 32 N., R. 10 E., Gila and Salt River Meridian, Arizona**

CHAINS	<p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p> <p>Set a steel fence post nearby.</p>
80.07	<p>The 1/4 sec. cor. of sec. 3 only, on the Eighth Standard Parallel North.</p> <hr/> <p>From the 1/4 sec. cor. of secs. 2 and 3.</p> <p>N. 89°47' W., on the E. and W. center line of sec. 3.</p> <p>Over rolling, sandy terrain, through medium growth sagebrush and native grasses.</p>
40.30	<p>The center 1/4 sec. cor. of sec. 3.</p>
80.37	<p>The 1/4 sec. cor. of secs. 3 and 4.</p> <hr/> <p style="text-align: center;">Subdivision of Section 4, T. 32 N., R. 10 E., Gila and Salt River Meridian, Arizona</p> <hr/> <p>From the 1/4 sec. cor. of secs. 4 and 9.</p> <p>N. 0°14' E., on the N. and S. center line of sec. 4.</p> <p>Over rolling, sandy terrain, through medium growth sagebrush and scattered juniper.</p>
40.07	<p>Point for the center 1/4 sec. cor. of sec. 4, at intersection with the E. and W. center line.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T 32 N R 10 E C 1/4 S 4</p> <p style="text-align: center;">2006</p>
80.24	<p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p> <p>Set a steel fence post nearby.</p> <p>The 1/4 sec. cor. of sec. 4 only, on the Eighth Standard Parallel North.</p> <hr/> <p>From the 1/4 sec. cor. of secs. 3 and 4.</p>

**Subdivision of Section 4,
T. 32 N., R. 10 E., Gila and Salt River Meridian, Arizona**

CHAINS	<p>S. 89°52' W., on the E. and W. center line of sec. 4.</p> <p>Over rolling, sandy terrain, through medium growth sagebrush and scattered juniper.</p>
40.07	The center 1/4 sec. cor. of sec. 4.
80.18	The 1/4 sec. cor. of secs. 4 and 5.
<hr/> <p>Subdivision of Section 7, T. 32 N., R. 10 E., Gila and Salt River Meridian, Arizona</p> <hr/>	
	<p>From the 1/4 sec. cor. of secs. 7 and 18.</p> <p>N. 0°04' E., on the N. and S. center line of sec. 7.</p> <p>Over rolling, sandy terrain and sandstone outcroppings, through medium growth sagebrush and native grasses.</p>
40.04	<p>The true point for the center 1/4 sec. cor. of sec. 7, at intersection with the E. and W. center line, falls on the sheer edge of a sandstone outcropping where it is impracticable to monument.</p> <p>From the true point, the point selected for a witness cor. to the center 1/4 sec. cor. of sec. 7, bears N. 38°58' W., 1.20 chs. dist.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">WC T 32 N R 10 E C 1/4 S 7</p> <p style="text-align: center;">2006 ↘</p> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p> <p>Set a steel fence post nearby.</p>
80.00	<p>The 1/4 sec. cor. of secs. 6 and 7.</p> <hr/> <p>From the 1/4 sec. cor. of secs. 7 and 8.</p> <p>N. 89°51' W., on the E. and W. center line of sec. 7.</p> <p>Over rolling, sandy terrain and sandstone outcroppings, through medium growth sagebrush and native grasses.</p>

**Subdivision of Section 7,
T. 32 N., R. 10 E., Gila and Salt River Meridian, Arizona**

CHAINS	
40.04	The true point for the center 1/4 sec. cor. of sec. 7.
78.27	The 1/4 sec. cor. of secs. 7 and 12, on the W. bdy. of the Tp.
<hr/> <p>Subdivision of Section 8, T. 32 N., R. 10 E., Gila and Salt River Meridian, Arizona</p> <hr/>	
	From the 1/4 sec. cor. of secs. 8 and 17.
	N. 0°05' W., on the N. and S. center line of sec. 8.
	Over rolling, sandy terrain, through medium growth sagebrush.
40.09	Point for the center 1/4 sec. cor. of sec. 8, at intersection with the E. and W. center line.
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.
	T 32 N R 10 E C 1/4 S 8
	2006
	Deposit a magnet, in a white plastic case, at the base of the stainless steel post.
	Set a steel fence post nearby.
80.11	The 1/4 sec. cor. of secs. 5 and 8.
<hr/>	
	From the 1/4 sec. cor. of secs. 8 and 9.
	N. 89°51' W., on the E. and W. center line of sec. 8.
	Over rolling, sandy terrain, through medium growth sagebrush.
39.62	The center 1/4 sec. cor. of sec. 8.
79.55	The 1/4 sec. cor. of secs. 7 and 8.
<hr/> <p>Subdivision of Section 9, T. 32 N., R. 10 E., Gila and Salt River Meridian, Arizona</p> <hr/>	
	From the 1/4 sec. cor. of secs. 9 and 16.
	N. 0°22' E., on the N. and S. center line of sec. 9.

**Subdivision of Section 9,
T. 32 N., R. 10 E., Gila and Salt River Meridian, Arizona**

CHAINS	
	Over rolling, sandy terrain, through medium growth sagebrush.
40.28	Point for the center 1/4 sec. cor. of sec. 9, at intersection with the E. and W. center line. Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd. T 32 N R 10 E C 1/4 S 9 2006 Deposit a magnet, in a white plastic case, at the base of the stainless steel post. Set a steel fence post nearby.
80.33	The 1/4 sec. cor. of secs. 4 and 9. <hr/>
	From the 1/4 sec. cor. of secs. 9 and 10. S. 89°54' W., on the E. and W. center line of sec. 9. Over rolling, sandy terrain, through medium growth sagebrush.
40.11	The center 1/4 sec. cor. of sec. 9.
80.10	The 1/4 sec. cor. of secs. 8 and 9. <hr/>
	Subdivision of Section 10, T. 32 N., R. 10 E., Gila and Salt River Meridian, Arizona
	From the 1/4 sec. cor. of secs. 10 and 15. N. 0°20' E., on the N. and S. center line of sec. 10. Over rolling, sandy terrain, through medium growth sagebrush.
40.04	Point for the center 1/4 sec. cor. of sec. 10, at intersection with the E. and W. center line. Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd. T 32 N R 10 E C 1/4 S 10 2006

**Subdivision of Section 10,
T. 32 N., R. 10 E., Gila and Salt River Meridian, Arizona**

CHAINS	
	<p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p> <p>Set a steel fence post nearby.</p>
80.08	<p>The 1/4 sec. cor. of secs. 3 and 10.</p> <hr/> <p>From the 1/4 sec. cor. of secs. 10 and 11.</p> <p>West, on the E. and W. center line of sec. 10.</p> <p>Over rolling, sandy terrain, through medium growth sagebrush.</p>
40.10	<p>The center 1/4 sec. cor. of sec. 10.</p>
80.20	<p>The 1/4 sec. cor. of secs. 9 and 10.</p> <hr/> <p style="text-align: center;">Subdivision of Section 11, T. 32 N., R. 10 E., Gila and Salt River Meridian, Arizona</p> <hr/> <p>From the 1/4 sec. cor. of secs. 11 and 14.</p> <p>N. 0°18' E., on the N. and S. center line of sec. 11.</p> <p>Over rolling, sandy terrain, through medium growth sagebrush.</p>
40.04	<p>Point for the center 1/4 sec. cor. of sec. 10, at intersection with the E. and W. center line.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T 32 N R 10 E C 1/4 S 11</p> <p style="text-align: center;">2006</p>
80.08	<p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p> <p>Set a steel fence post nearby.</p> <p>The 1/4 sec. cor. of secs. 2 and 11.</p> <hr/> <p>From the 1/4 sec. cor. of secs. 11 and 12.</p> <p>N. 89°51' W., on the E. and W. center line of sec. 11.</p> <p>Over rolling, sandy terrain, through medium growth sagebrush.</p>

**Subdivision of Section 11,
T. 32 N., R. 10 E., Gila and Salt River Meridian, Arizona**

CHAINS	
40.02	The center 1/4 sec. cor. of sec. 11.
80.04	The 1/4 sec. cor. of secs. 10 and 11.
<hr/> <p>Subdivision of Section 12, T. 32 N., R. 10 E., Gila and Salt River Meridian, Arizona</p> <hr/>	
	From the 1/4 sec. cor. of secs. 12 and 13.
	N. 0°15' E., on the N. and S. center line of sec. 12.
	Over rolling, sandy terrain, through medium growth sagebrush.
26.09	Graded road, 30 ft. wide, bears S. 25° E. and N. 10° W.
40.09	Point for the center 1/4 sec. cor. of sec. 12, at intersection with the E. and W. center line.
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.
	T 32 N R 10 E C 1/4 S 12 2006
	Deposit a magnet, in a white plastic case, at the base of the stainless steel post.
	Set a steel fence post nearby.
80.08	The 1/4 sec. cor. of secs. 1 and 12.
	<hr/> From the 1/4 sec. cor. of secs. 7 and 12, on the E. bdy. of the Tp., monumented with a stainless steel post, 2 1/2 ins. diam., firmly set, projecting 4 ins. above the ground, with brass cap mkd. T32N 1/4 R10E R11E S12 S7 2005.
	N. 89°56' W., on the E. and W. center line of sec. 12.
	Over rolling, sandy terrain, through medium growth sagebrush.
40.07	The center 1/4 sec. cor. of sec. 12.
47.40	Graded road, 30 ft. wide, bears S. 30° E. and N. 30° W.

**Subdivision of Section 12,
T. 32 N., R. 10 E., Gila and Salt River Meridian, Arizona**

CHAINS	
80.10	The 1/4 sec. cor. of secs. 11 and 12.
	<hr/> <p>Subdivision of Section 13, T. 32 N., R. 10 E., Gila and Salt River Meridian, Arizona</p> <hr/>
	From the 1/4 sec. cor. of secs. 13 and 24.
	N. 0°10' E., on the N. and S. center line of sec. 13.
	Over rolling, sandy terrain, through medium growth sagebrush.
40.05	Point for the center 1/4 sec. cor. of sec. 12, at intersection with the E. and W. center line.
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.
	<p>T 32 N R 10 E C 1/4 S 13</p> <p>2006</p>
	Deposit a magnet, in a white plastic case, at the base of the stainless steel post.
	Set a steel fence post nearby.
80.09	The 1/4 sec. cor. of secs. 12 and 13.
	<hr/>
	From the 1/4 sec. cor. of secs. 13 and 18, on the E. bdy. of the Tp., monumented with a brass tablet, 3 1/4 ins. diam., cemented in solid rock, with top mkd. T32N 1/4 R10E R11E S13 S18 2005.
	N. 89°57' W., on the E. and W. center line of sec. 13.
	Over rolling, sandy terrain, through medium growth sagebrush.
40.12	The center 1/4 sec. cor. of sec. 13.
80.08	The 1/4 sec. cor. of secs. 13 and 14.
	<hr/> <p>Subdivision of Section 14, T. 32 N., R. 10 E., Gila and Salt River Meridian, Arizona</p> <hr/>
	From the 1/4 sec. cor. of secs. 14 and 23.
	N. 0°17' E., on the N. and S. center line of sec. 14.

**Subdivision of Section 14,
T. 32 N., R. 10 E., Gila and Salt River Meridian, Arizona**

CHAINS	
	Over rolling, sandy terrain, through medium growth sagebrush.
38.39	Trail road, 8 ft. wide, bears N. 80° E. and N. 85° W.
39.14	Point for the center 1/4 sec. cor. of sec. 14, at intersection with the E. and W. center line.
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.
	T 32 N R 10 E C 1/4 S 14
	2006
	Deposit a magnet, in a white plastic case, at the base of the stainless steel post.
	Set a steel fence post nearby.
79.28	The 1/4 sec. cor. of secs. 11 and 14.

	From the 1/4 sec. cor. of secs. 13 and 14.
	N. 89°55' W., on the E. and W. center line of sec. 14.
	Over rolling, sandy terrain, through medium growth sagebrush.
31.59	Trail road, 8 ft. wide, bears N. 45° E. and S. 75° W.
40.22	The center 1/4 sec. cor. of sec. 14.
44.99	Trail road, 8 ft. wide, bears S. 80° E. and N. 70° W.
80.19	The 1/4 sec. cor. of secs. 14 and 15.

	Subdivision of Section 15, T. 32 N., R. 10 E., Gila and Salt River Meridian, Arizona

	From the 1/4 sec. cor. of secs. 15 and 22.
	N. 0°08' E., on the N. and S. center line of sec. 15.
	Over rolling, sandy terrain, through medium growth sagebrush.
40.13	Point for the center 1/4 sec. cor. of sec. 15, at intersection with the E. and W. center line.
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.

**Subdivision of Section 15,
T. 32 N., R. 10 E., Gila and Salt River Meridian, Arizona**

CHAINS	
	<p>T 32 N R 10 E C 1/4 S 15</p> <p>2006</p>
	<p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p> <p>Set a steel fence post nearby.</p>
80.27	<p>The 1/4 sec. cor. of secs. 10 and 15.</p> <hr/> <p>From the 1/4 sec. cor. of secs. 14 and 15.</p> <p>N. 89°56' W., on the E. and W. center line of sec. 15.</p> <p>Over rolling sandy terrain, through medium growth sagebrush.</p>
40.09	<p>The center 1/4 sec. cor. of sec. 15.</p>
79.93	<p>The 1/4 sec. cor. of secs. 15 and 16.</p> <hr/> <p style="text-align: center;">Subdivision of Section 23, T. 32 N., R. 10 E., Gila and Salt River Meridian, Arizona</p> <hr/> <p>From the 1/4 sec. cor. of secs. 23 and 26.</p> <p>N. 0°02' W., on the N. and S. center line of sec. 23.</p> <p>Over rolling, sandy terrain, through medium growth sagebrush.</p>
38.83	<p>Trail road, 10 ft. wide, bears N. 25° E. and S. 25° W.</p>
39.88	<p>Point for the center 1/4 sec. cor. of sec. 23, at intersection with the E. and W. center line.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T 32 N R 10 E C 1/4 S 23</p> <p style="text-align: center;">2006</p> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p> <p>Set a steel fence post nearby.</p>

**Subdivision of Section 23,
T. 32 N., R. 10 E., Gila and Salt River Meridian, Arizona**

CHAINS	
80.95	<p>The 1/4 sec. cor. of secs. 14 and 23.</p> <hr/> <p>From the 1/4 sec. cor. of secs. 23 and 24.</p> <p>S. 89°54' W., on the E. and W. center line of sec. 23.</p> <p>Over rolling, sandy terrain, through medium growth sagebrush.</p>
39.48	Trail road, 10 ft. wide, bears N. 25° E. and S. 30° W.
40.17	The center 1/4 sec. cor. of sec. 23.
80.01	<p>The 1/4 sec. cor. of secs. 22 and 23.</p> <hr/> <p style="text-align: center;">Subdivision of Section 24, T. 32 N., R. 10 E., Gila and Salt River Meridian, Arizona</p> <hr/> <p>From the 1/4 sec. cor. of secs. 24 and 25.</p> <p>N. 0°02' W., on the N. and S. center line of sec. 24.</p> <p>Over rolling, sandy terrain, through medium growth sagebrush.</p>
40.06	<p>Point for the center 1/4 sec. cor. of sec. 24, at intersection with the E. and W. center line.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T 32 N R 10 E C 1/4 S 24</p> <p style="text-align: center;">2006</p> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p> <p>Set a steel fence post nearby.</p>
80.12	<p>The 1/4 sec. cor. of secs. 13 and 24.</p> <hr/> <p>From the 1/4 sec. cor. of secs. 19 and 24, on the E. bdy. of the Tp., monumented with a stainless steel post, 2 1/2 ins. diam., firmly set, projecting 6 ins. above the ground, with brass cap mkd. T32N R10E R11E S24 S19 1988 2005.</p> <p>N. 89°55' W., on the E. and W. center line of sec. 24.</p> <p>Over rolling, sandy terrain, through medium growth sagebrush.</p>

**Subdivision of Section 24,
T. 32 N., R. 10 E., Gila and Salt River Meridian, Arizona**

CHAINS

40.11 The center 1/4 sec. cor. of sec. 24.

80.22 The 1/4 sec. cor. of secs. 23 and 24.

**Subdivision of Section 29,
T. 32 N., R. 10 E., Gila and Salt River Meridian, Arizona**

From the 1/4 sec. cor. of secs. 29 and 32.

N. 0°01' E., on the N. and S. center line of sec. 29.

Over rolling, sandy terrain and sandstone outcroppings.

40.47 Point for the center 1/4 sec. cor. of sec. 29, at intersection with the E. and W. center line.

Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.

T 32 N R 10 E
C 1/4 S 29

2006

Deposit a magnet, in a white plastic case, at the base of the stainless steel post.

Set a steel fence post nearby.

80.31 The 1/4 sec. cor. of secs. 20 and 29.

From the 1/4 sec. cor. of secs. 28 and 29.

S. 89°46' W., on the E. and W. center line of sec. 29.

Over rolling, sandy terrain and sandstone outcroppings.

39.45 The center 1/4 sec. cor. of sec. 29.

79.37 The 1/4 sec. cor. of secs. 29 and 30.

**Subdivision of Section 30,
T. 32 N., R. 10 E., Gila and Salt River Meridian, Arizona**

From the 1/4 sec. cor. of secs. 30 and 31.

N. 0°08' W., on the N. and S. center line of sec. 30.

**Subdivision of Section 30,
T. 32 N., R. 10 E., Gila and Salt River Meridian, Arizona**

CHAINS	
	Over rolling, sandy terrain and sandstone outcroppings.
39.91	Point for the center 1/4 sec. cor. of sec. 30, at intersection with the E. and W. center line. Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 15 ins. in the ground, to bedrock, in a supporting mound of stone, 3 ft. base, to top, with brass cap mkd. T 32 N R 10 E C 1/4 S 30 2006 Deposit a magnet, in a white plastic case, at the base of the stainless steel post. Set a steel fence post nearby.
80.07	The 1/4 sec. cor. of secs. 19 and 30. <hr/>
	From the 1/4 sec. cor. of secs. 29 and 30. S. 89°45' W., on the E. and W. center line of sec. 30. Over rolling, sandy terrain and sandstone outcroppings.
40.13	The center 1/4 sec. cor. of sec. 30.
78.45	The 1/4 sec. cor. of secs. 25 and 30, on the W. bdy. of the Tp. <hr/>
	Subdivision of Section 31, T. 32 N., R. 11 E., Gila and Salt River Meridian, Arizona
	From the 1/4 sec. cor. of secs. 6 and 31, on the S. bdy of the Tp. N. 0°27' E., on the N. and S. center line of sec. 31. Over rolling, sandy terrain and sandstone outcroppings.
39.97	Point for the center 1/4 sec. cor. of sec. 31, at intersection with the E. and W. center line. Set a limestone boulder, 3 x 2 x 2 ft., 12 ins. in the ground to bedrock, with a brass tablet, 3 1/4 ins. diam., 3 1/2 ins. stem, cemented in a drill hole, in the top of the boulder, with top mkd.

**Subdivision of Section 31,
T. 32 N., R. 10 E., Gila and Salt River Meridian, Arizona**

CHAINS	
	<p>T 32 N R 10 E C 1/4 S 31</p> <p>2006</p>
79.85	<p>Deposit a magnet, in the drill hole, beneath the brass tablet.</p> <p>The 1/4 sec. cor. of secs. 30 and 31.</p> <hr/>
39.95	<p>From the 1/4 sec. cor. of secs. 31 and 32.</p> <p>N. 89°51' W., on the E. and W. center line of sec. 31.</p> <p>Over rolling, sandy terrain and sandstone outcroppings.</p> <p>The center 1/4 sec. cor. of sec. 31.</p>
78.36	<p>The 1/4 sec. cor. of secs. 31 and 36, on the W. bdy. of the Tp.</p> <hr/> <p style="text-align: center;">Subdivision of Section 32, T. 32 N., R. 10 E., Gila and Salt River Meridian, Arizona</p> <hr/>
40.10	<p>From the 1/4 sec. cor. of secs. 5 and 32, on the S. bdy. of the Tp.</p> <p>N. 0°26' E., on the N. and S. center line of sec. 32.</p> <p>Over broken, sandy terrain and sandstone outcroppings.</p> <p>Point for the center 1/4 sec. cor. of sec. 32, at intersection with the E. and W. center line.</p> <p>Set a brass tablet, 3 1/4 ins. diam., 3 1/2 ins. stem, cemented in a drill hole, in solid rock, with top mkd.</p>
79.94	<p>T 32 N R 10 E C 1/4 S 32</p> <p>2006</p>
	<p>Deposit a magnet, in the drill hole, beneath the brass tablet.</p> <p>Raise a mound of stone, 3 ft. base, 2 ft. high, W. of the cor.</p> <p>Cor. is located on a sandstone outcrop.</p> <p>The 1/4 sec. cor. of secs. 29 and 32.</p> <hr/> <p>From the 1/4 sec. cor. of secs. 32 and 33.</p>

**Subdivision of Section 32,
T. 32 N., R. 10 E., Gila and Salt River Meridian, Arizona**

CHAINS	<p>N. 89°54' W., on the E. and W. center line of sec. 32. Over broken, sandy terrain and sandstone outcroppings.</p>
40.41	The center 1/4 sec. cor. of sec. 32.
80.43	The 1/4 sec. cor. of secs. 31 and 32.
<hr/> <p>Subdivision of Section 33, T. 32 N., R. 10 E., Gila and Salt River Meridian, Arizona</p> <hr/>	
	<p>From the 1/4 sec. cor. of secs. 4 and 33, on the S. bdy. of the Tp. N. 0°07' W., on the N. and S. center line of sec. 33. Over broken, sandy terrain and sandstone outcroppings.</p>
39.81	<p>Point for the center 1/4 sec. cor. of sec. 33, at intersection with the E. and W. center line. Set a stainless steel post, 12 ins. long, 2 1/2 ins. diam., 11 ins. in a concrete cylinder, 2 ft. diam., 12 ins. in the ground, with brass cap mkd.</p>
	<p>T 32 N R 10 E C 1/4 S 33 2006</p>
	<p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post. Set a steel fence post nearby.</p>
42.96	Graded road, 35 ft. wide, bears S. 35° E. and N. 35° W.
80.12	The 1/4 sec. cor. of secs. 28 and 33.
	<hr/> <p>From the 1/4 sec. cor. of secs. 33 and 34. N. 89°39' W., on the E. and W. center line of sec. 33. Over broken, sandy terrain and sandstone outcroppings.</p>
37.82	Graded road, 35 ft. wide, bears S. 35° E. and N. 35° W.
39.90	The center 1/4 sec. cor. of sec. 33.

Subdivision of Section 33,
T. 32 N., R. 10 E., Gila and Salt River Meridian, Arizona

CHAINS	
79.88	<p>The 1/4 sec. cor. of secs. 32 and 33.</p> <hr/> <p style="text-align: center;">Subdivision of Section 34, T. 32 N., R. 10 E., Gila and Salt River Meridian, Arizona</p> <hr/> <p>From the 1/4 sec. cor. of secs. 3 and 34, on the S. bdy. of the Tp.</p> <p>N. 0°32' W., on the N. and S. center line of sec. 34.</p> <p>Over broken, sandy terrain and sandstone outcroppings.</p>
39.78	<p>Point for the center 1/4 sec. cor. of sec. 34, at intersection with the E. and W. center line.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T 32 N R 10 E C 1/4 S 34</p> <p style="text-align: center;">2006</p> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p> <p>Set a steel fence post nearby.</p>
79.85	<p>The 1/4 sec. cor. of secs. 27 and 34.</p> <hr/> <p>From the 1/4 sec. cor. of secs. 34 and 35.</p> <p>S. 89°49' W., on the E. and W. center line of sec. 34.</p> <p>Over broken, sandy terrain and sandstone outcroppings.</p>
39.97	<p>The center 1/4 sec. cor. of sec. 34.</p>
80.32	<p>The 1/4 sec. cor. of secs. 33 and 34.</p> <hr/>

T. 32 N., R. 11 E., Gila and Salt River Meridian, Arizona

CHAINS

GENERAL DESCRIPTION

The area surveyed is located approximately one mile west of Tuba City, Arizona. The terrain varies from gently rolling to broken land, with scattered mesas, washes, sand dunes and sandstone outcroppings.

The elevation ranges from 4,600 ft. to 5,700 ft. above sea level. The soil is generally sandy loam, with large sand dunes and exposed bedrock throughout the township. The vegetation consists of native grasses and sagebrush. The drainage is generally southwesterly.

Access to the area is provided by U.S. Highway No. 160 in the southeast corner of the township with trail roads throughout the remainder of the township.

There is no evidence of active mining at the present time.

The mean magnetic declination of $11\ 3/4^\circ$ E. was derived from the computer program GEOMAGIX utilizing the World Magnetic Model for Epoch 2005 for the dates of survey.

CERTIFICATE OF SURVEY

I, W. William Foster, Cadastral Surveyor, HEREBY CERTIFY upon honor, that in pursuance of special instructions bearing date of the 15th day of December, 2005, I have dependently resurveyed the Eighth Standard Parallel North (north boundary), a portion of the south boundary, the west boundary and the subdivisional lines and subdivided certain sections, Township 32 North, Range 10 East, Gila and Salt River Meridian, Arizona, which are represented in the foregoing field notes as having been executed by me and under my direction. Said survey has been made in strict conformity with said special instructions, the Manual of Instructions for the Survey of the Public Lands of the United States, 1973, and in specific manner described in the foregoing field notes.

W. William Foster is no longer assigned to this office
and is unavailable for signature.

(Date)

(Cadastral Surveyor)

CERTIFICATE OF APPROVAL

BUREAU OF LAND MANAGEMENT
Phoenix, Arizona

The foregoing field notes of the dependent resurvey of the Eighth Standard Parallel North (north boundary), a portion of the south boundary, the west boundary and the subdivisional lines and the subdivision of certain sections, Township 32 North, Range 10 East, Gila and Salt River Meridian, Arizona, executed by W. William Foster, Cadastral Surveyor, having been critically examined and found correct, are hereby approved.

Mar. 26, 2007
(Date)

Stephen K. Hansen
(Chief Cadastral Surveyor of Arizona)

CERTIFICATE OF TRANSCRIPT

I CERTIFY That the foregoing transcript of the field notes of the above described surveys in T. 32 N., R. 10 E., Gila and Salt River Meridian, Arizona, is a true copy of the original field notes.

(Date)

(Chief Cadastral Surveyor of Arizona)