

ORIGINAL

**UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT**

FIELD NOTES
OF
THE
DEPENDENT RESURVEY
OF
THE
SUBDIVISIONAL LINES,
TOWNSHIP 23 NORTH, RANGE 27 EAST,
OF THE GILA AND SALT RIVER MERIDIAN,
IN THE STATE OF ARIZONA.

EXECUTED BY

Jones Curtiss, Cadastral Surveyor

Under Special Instructions dated and approved May 1, 2002 and Supplemental Special Instructions dated and approved September 23, 2002, which provided for the surveys included under Group No. 886 and assignment instructions dated January 8, 2007.

Survey commenced January 10, 2007

Survey completed February 23, 2007

INDEX DIAGRAM

TOWNSHIP 23 NORTH RANGE 27 EAST
 GILA AND SALT RIVER MERIDIAN, ARIIZONA

6	47 5	34 4	26 3	18 2	11 1
46	45	34	26	18	10
7	44 8	33 9	25 10	17 11	9 12
44	43	32	25	17	9
18	42 17	31 16	24 15	16 14	8 13
41	40	31	23	15	7
19	39 20	30 21	22 22	14 23	6 24
39	38	29	22	14	6
30	37 29	28 28	21 27	13 26	5 25
36	36	28	20	13	5
31	35 32	27 33	19 34	11 35	4 36

T. 23 N., R. 27 E., Gila and Salt River Meridian, Arizona

CHAINS

The following field notes describe the dependent resurvey of the subdivisional lines of Township 23 North, Range 27 East, Gila and Salt River Meridian, Arizona.

The history of surveys pertaining to this survey is as follows:

Frank Follman surveyed the south, east, west and north boundaries in 1882 and surveyed the subdivisional lines in 1883. Jones Curtiss and Leonard R. Sandoval dependently resurveyed the west boundary in 2003. Jones Curtiss dependently resurveyed the south, east and north boundaries in 2002-03.

The survey was executed in accordance with the specifications as set forth in the Manual of Instructions for the Survey of the Public Lands of the United States, 1973, and the Special Instructions dated and approved May 01, 2002 and the supplemental Special Instructions dated and approved September 23, 2002, for Group No. 886, Arizona.

The true meridian direction and length of all lines were determined by real time kinematic global positioning system observations using Trimble Navigation 5700 model receivers.

Preliminary to the resurvey, the lines of the prior surveys were retraced and search was made for all corners and other calls of record. Identified corners were remonumented in their original positions. Lost corners were reestablished and remonumented at proportionate positions based on the official record. The retracement data were thoroughly verified and only the true line field notes are given herein.

Geodetic control was derived from Global Positioning System (GPS) static observations post processed by National Geodetic Survey's Online Positioning User Service (OPUS), utilizing Continuously Operating Reference Stations (CORS) AZTEC CORS ARP, Flagstaff 1 CORS ARP and GILA COUNTY CORS ARP. The NAD83 (CORS96) (EPOCH:2002), geographic position of the southeast corner of the township is as follows:

Latitude: 35°20'37.74" N. Longitude: 109°25'15.01" W.

The mean magnetic declination is 10 3/4° E.

**Dependent Resurvey of the Subdivisional Lines,
T. 23 N., R. 27 E., Gila and Salt River Meridian, Arizona**

CHAINS	
	<p>Restoring the survey executed by Frank Follman, in 1883</p> <hr/>
	<p>From the cor. of secs. 1, 2, 35 and 36, on the S. bdy. of the Tp., monumented with a stainless steel post, 2 1/2 ins. diam., firmly set, projecting 4 ins. above ground, with brass cap mkd. T23N R27E S35 S36 S2 S1 T22N 2003.</p> <p>Add the marks 2007 to the brass cap.</p> <p>Cor. is located 34 lks. S. of a trail road, bears N. 55° E. and S. 55° W.</p> <p>N. 0°24' E., bet. secs. 35 and 36.</p> <p>Over rolling and broken land.</p>
39.98	<p>Point for the 1/4 sec cor. of secs. 35 and 36, at proportionate dist., there is no remaining evidence of the orig. cor.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center;"> <p>T 23 N R 27 E 1/4 S 35 S 36</p> <p>2007</p> </div> <p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p>
79.96	<p>Point for the cor. of secs. 25, 26, 35 and 36, at proportionate dist., there is no remaining evidence of the orig. cor.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center;"> <p>T 23 N R 27 E S 26 S 25 S 35 S 36</p> <p>2007</p> </div> <p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p> <hr/>

**Dependent Resurvey of the Subdivisional Lines,
T. 23 N., R. 27 E., Gila and Salt River Meridian, Arizona**

CHAINS	
	<p>From the cor. of secs. 25 and 36 only, on the E. bdy. of the Tp., monumented with an stainless steel post, 2 1/2 ins. diam., firmly set, projecting 4 ins. above ground, with brass cap mkd. T23N S25 S36 R27E on the west half, T23N R28E S30 on the east half and 2003.</p> <p>Add the marks 2007 to the brass cap.</p> <p>N. 89°09' W., bet. secs. 25 and 36.</p> <p>Over rolling and broken land.</p>
39.775	<p>Point for the 1/4 sec. cor. of secs. 25 and 36, at proportionate dist., there is no remaining evidence of the orig. cor.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T 23 N R 27 E S 25 1/4 ——— S 36</p> <p style="text-align: center;">2007</p> <p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p>
79.55	<p>The cor. of secs. 25, 26, 35 and 36.</p> <hr/> <p>N. 0°02' W., bet. secs. 25 and 26.</p> <p>Over rolling land.</p>
39.98	<p>Point for the 1/4 sec. cor. of secs. 25 and 26, at proportionate dist., there is no remaining evidence of the orig. cor.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T 23 N R 27 E 1/4 S 26 S 25</p> <p style="text-align: center;">2007</p> <p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p>
79.96	<p>Point for the cor. of secs. 23, 24, 25 and 26, at proportionate dist., there is no remaining evidence of the orig. cor.</p>

**Dependent Resurvey of the Subdivisional Lines,
T. 23 N., R. 27 E., Gila and Salt River Meridian, Arizona**

CHAINS	
	<p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T 23 N R 27 E S 23 S 24 S 26 S 25</p> <p style="text-align: center;">2007</p> <p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p> <hr/> <p>From the cor. of secs. 24 and 25 only, on the E. bdy. of the Tp., monumented with an stainless steel post, 2 1/2 ins. diam., firmly set, projecting 4 ins. above ground, with brass cap mkd. T23N S24 S25 R27E on the west half, T23N R28E S19 on the east half and 2003.</p> <p>Add the marks 2007 to the brass cap.</p> <p>N. 89°11' W., bet. secs. 24 and 25.</p> <p>Over rolling land.</p>
39.96	<p>Point for the 1/4 sec. cor. of secs. 24 and 25, at proportionate dist., there is no remaining evidence of the orig. cor.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T 23 N R 27 E S 24 1/4 ——— S 25</p> <p style="text-align: center;">2007</p> <p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p>
79.92	<p>The cor. of secs. 23, 24, 25 and 26.</p> <hr/> <p>N. 0°21' E., bet. secs. 23 and 24.</p> <p>Over rolling land.</p>
37.25	<p>Trail road, bears S. 75° E. and N. 75° W.</p>
39.98	<p>Point for the 1/4 sec. cor. of secs. 23 and 34, at proportionate dist., there is no remaining evidence of the orig. cor.</p>

**Dependent Resurvey of the Subdivisional Lines,
T. 23 N., R. 27 E., Gila and Salt River Meridian, Arizona**

CHAINS	
	<p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T 23 N R 27 E 1/4 S 23 S 24</p> <p style="text-align: center;">2007</p> <p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p> <p>Cor. is located 3 lks. W. of a trail road, bears S. 35° E. and N. 35° W.</p> <p>Set a steel fence post nearby.</p>
61.30	Wash, 20 ft. wide, 2 ft. deep, drains N. 85° W.
79.96	<p>Point for the cor. of secs. 13, 14, 23 and 24, at proportionate dist., there is no remaining evidence of the orig. cor.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T 23 N R 27 E S 14 S 13 S 23 S 24</p> <p style="text-align: center;">2007</p> <p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p> <hr/> <p>From the cor. of secs. 13 and 24 only, on the E. bdy. of the Tp., monumented with an stainless steel post, 2 1/2 ins. diam., firmly set, projecting 4 ins. above ground, with brass cap mkd. T23N on top, R27E S13 S24 on the west half, R28E S18 on the east half and 2003.</p> <p>Add the marks 2007 to the brass cap.</p> <p>N. 89°12' W., bet. secs. 13 and 24.</p> <p>Over rolling land.</p>
39.885	<p>Point for the 1/4 sec. cor. of secs. 13 and 24, at proportionate dist., there is no remaining evidence of the orig. cor.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p>

**Dependent Resurvey of the Subdivisional Lines,
T. 23 N., R. 27 E., Gila and Salt River Meridian, Arizona**

CHAINS	
	T 23 N R 27 E S 13 1/4 ——— S 24 2007
	Deposit a magnet in a white plastic case at the base of the stainless steel post.
79.77	The cor. of secs. 13, 14, 23 and 24. <hr/>
	N. 0°01' E., bet. secs. 13 and 14. Over rolling and broken land.
39.98	Point for the 1/4 sec. cor. of secs. 13 and 14, at proportionate dist., there is no remaining evidence of the orig. cor. Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 22 ins. in the ground to bedrock, with brass cap mkd.
	T 23 N R 27 E 1/4 S 14 S 13 2007
	Deposit a magnet in a white plastic case at the base of the stainless steel post.
	Cor. is located 1.64 chs. S. of a trail road, bears E. and W.
58.70	Bent Knee wash, 30 ft. wide, 15 ft. deep, drains S. 80° W.
79.96	Point for the cor. of secs. 11, 12, 13 and 14, at proportionate dist., there is no remaining evidence of the orig. cor. Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.
	T 23 N R 27 E S 11 S 12 S 14 S 13 2007
	Deposit a magnet in a white plastic case at the base of the stainless steel post. <hr/>

**Dependent Resurvey of the Subdivisional Lines,
T. 23 N., R. 27 E., Gila and Salt River Meridian, Arizona**

CHAINS	
	<p>From the cor. of secs. 12 and 13 only, on the E. bdy. of the Tp., monumented with an stainless steel post, 2 1/2 ins. diam., firmly set, projecting 4 ins. above ground, with brass cap mkd. T23N on top, R27E S12 S13 on the west half, R28E S7 on the east half and 2003.</p> <p>Add the marks 2007 to the brass cap.</p> <p>N. 89°14' W., bet. secs. 12 and 13.</p> <p>Over rolling and broken land.</p>
40.045	<p>Point for the 1/4 sec. cor. of secs. 12 and 13, at proportionate dist., there is no remaining evidence of the orig. cor.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground to bedrock, with brass cap mkd.</p> <div style="text-align: center;"> <p>T 23 N R 27 E S 12 1/4 ——— S 13</p> <p>2007</p> </div> <p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p> <p>Cor. is located 26 lks. S. of a trail road, bears N. 65° E. and S. 65° W.</p>
65.80	<p>Bent Knee wash, 20 ft. wide, 2 ft. deep, with 15 ft. high stone wall on N. bank, drains S. 55° W.</p>
80.09	<p>The cor. of secs. 11, 12, 13 and 14.</p> <hr/> <p>N. 0°04' E., bet. secs. 11 and 12.</p> <p>Over broken land.</p>
39.98	<p>Point for the 1/4 sec. cor. of secs. 11 and 12, at proportionate dist., there is no remaining evidence of the orig. cor.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center;"> <p>T 23 N R 27 E 1/4 S 11 S 12</p> <p>2007</p> </div>

Dependent Resurvey of the Subdivisional Lines,
T. 23 N., R. 27 E., Gila and Salt River Meridian, Arizona

CHAINS	<p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p>								
79.96	<p>Point for the cor. of secs. 1, 2, 11 and 12, at proportionate dist., there is no remaining evidence of the orig. cor.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center; margin: 10px 0;"> <table style="margin: auto; border-collapse: collapse;"> <tr> <td style="padding: 0 10px;">T 23 N</td> <td style="padding: 0 10px;">R 27 E</td> </tr> <tr> <td style="padding: 0 10px; border-right: 1px solid black;">S 2</td> <td style="padding: 0 10px;">S 1</td> </tr> <tr> <td style="padding: 0 10px; border-right: 1px solid black;">S 11</td> <td style="padding: 0 10px;">S 12</td> </tr> </table> <p style="margin: 5px 0;">2007</p> </div> <p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p> <hr style="width: 50%; margin: 10px auto;"/> <p>From the cor. of secs. 1 and 12 only, on the E. bdy. of the Tp., monumented with an stainless steel post, 2 1/2 ins. diam., firmly set, projecting 4 ins. above ground, with brass cap mkd. T23N on top, R27E S1 S12 on the west half, R28E S6 on the east half and 2003.</p> <p>Add the marks 2007 to the brass cap.</p> <p>N. 89°16' W., bet. secs. 1 and 12.</p> <p>Over broken land.</p>	T 23 N	R 27 E	S 2	S 1	S 11	S 12		
T 23 N	R 27 E								
S 2	S 1								
S 11	S 12								
6.60	<p>Bent Knee wash, 50 ft. wide, 5 ft. deep, drains S. 40° E.</p>								
40.17	<p>Point for the 1/4 sec. cor. of secs. 1 and 12, at proportionate dist., there is no remaining evidence of the orig. cor.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center; margin: 10px 0;"> <table style="margin: auto; border-collapse: collapse;"> <tr> <td style="padding: 0 10px;">T 23 N</td> <td style="padding: 0 10px;">R 27 E</td> </tr> <tr> <td style="padding: 0 10px;"></td> <td style="padding: 0 10px;">S 1</td> </tr> <tr> <td style="padding: 0 10px;">1/4</td> <td style="padding: 0 10px; border-top: 1px solid black;">—</td> </tr> <tr> <td style="padding: 0 10px;"></td> <td style="padding: 0 10px;">S 12</td> </tr> </table> <p style="margin: 5px 0;">2007</p> </div> <p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p> <p>Cor. is located 1.56 chs. E. of a trail road, bears S. 35° E. and N. 35° W.</p>	T 23 N	R 27 E		S 1	1/4	—		S 12
T 23 N	R 27 E								
	S 1								
1/4	—								
	S 12								

**Dependent Resurvey of the Subdivisional Lines,
T. 23 N., R. 27 E., Gila and Salt River Meridian, Arizona**

CHAINS	
80.34	<p>The cor. of secs. 1, 2, 11 and 12.</p> <hr/> <p>N. 0°29' E., bet. secs. 1 and 2.</p> <p>Over rolling land.</p>
39.98	<p>Point for the 1/4 sec. cor. of secs. 1 and 2, at proportionate dist., there is no remaining evidence of the orig. cor.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T 23 N R 27 E 1/4 S 2 S 1</p> <p style="text-align: center;">2007</p> <p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p>
65.00	<p>Trail road, bears N. 70° E. and S. 70° W.</p>
80.36	<p>The cor. of secs. 1, 2, 35 and 36, on the N. bdy. of the Tp., monumented with a stainless steel post, 2 1/2 ins. diam., firmly set, projecting 4 ins. above ground, with brass cap mkd. T24N R27E S35 S36 S2 S1 T23N 2003.</p> <p>Add the marks 2007 to the brass cap.</p> <hr/> <p>From the cor. of secs. 2, 3, 34 and 35, on the S. bdy. of the Tp., monumented with a stainless steel post, 2 1/2 ins. diam., firmly set, projecting 4 ins. above ground, with brass cap mkd. T23N R27E S34 S35 S3 S2 T22N 2003.</p> <p>Add the marks 2007 to the brass cap.</p> <p>Cor. is located 70 lks. S. of a trail road, bears N. 25° E. and S. 25° W.</p> <p>N. 0°21' E., bet. secs. 34 and 35.</p> <p>Over rolling and broken land.</p>
21.22	<p>From this point, a highway right-of-way marker, bears East, 6.38 chs. dist., monumented with a brass disk, 3 ins. diam. set in the center of a 6 ins. diam. concrete collar, firmly set, flush with the ground, mkd. BIA ROADS 19.</p>

**Dependent Resurvey of the Subdivisional Lines,
T. 23 N., R. 27 E., Gila and Salt River Meridian, Arizona**

CHAINS	
22.96	From this point, a highway right-of-way marker, bears East, 8.85 chs. dist., monumented with a brass disk, 3 ins. diam., set in the center of a 6 ins. diam. concrete collar, projecting 6 ins. above the surface of the ground, mkd. BIA ROADS 19, witnessed by a 4 x 4 ins. L shaped angle iron, 3 ft. W., projecting 21 ins. above ground, mkd. 1379+96.30.
27.60	Power line, bears S. 35° E. and N. 35° W.
30.23	S. right-of-way fence, barbed wire, 4 strand, parallels highway.
32.88	State Highway 191, asphalt surfaced, 28 ft. wide, bears S. 35° E. and N. 35° W.
35.48	N. right-of-way fence, barbed wire, 4 strand, parallels highway.
40.025	Point for the 1/4 sec. cor. of secs. 34 and 35, at proportionate dist., there is no remaining evidence of the orig. cor. Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd. <div style="text-align: center;"> T 23 N R 27 E 1/4 S 34 S 35 2007 </div>
	Deposit a magnet in a white plastic case at the base of the stainless steel post.
41.64	From this point, a highway right-of-way marker, bears West, 8.06 chs. dist., monumented with a brass disk, 3 ins. diam., set in the center of 6 ins. diam. concrete collar, firmly set, projecting 10 ins. above the ground, mkd. BIA ROADS, witnessed by a 4 x 4 ins. L shaped angle iron, 3 ft. W., projecting 24 ins. above ground, mkd. 1381+50.10.
43.38	From this point, a highway right-of-way marker, bears West, 5.59 chs. dist., monumented with a brass disk, 3 ins. diam., set in the center of 6 ins. diam. concrete collar, firmly set, flush with the surface of the ground, mkd. BIA ROADS 19, witnessed by a 4 x 4 ins. L shape angle iron, 3 ft. W., projecting 21 ins. above ground, mkd. 1381+50.10.
80.05	Point for the cor. of secs. 26, 27, 34 and 35, at proportionate dist., there is no remaining evidence of the orig. cor. Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.

**Dependent Resurvey of the Subdivisional Lines,
T. 23 N., R. 27 E., Gila and Salt River Meridian, Arizona**

CHAINS	
	T 23 N R 27 E S 27 S 26 S 34 S 35 2007 Deposit a magnet in a white plastic case at the base of the stainless steel post. <hr/> From the cor. of secs. 25, 26, 35 and 36. N. 89°04' W., bet. secs. 26 and 35. Over broken land.
39.90	Point for the 1/4 sec. cor. of secs. 26 and 35, at proportionate dist., there is no remaining evidence of the orig. cor. Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd. <div style="text-align: center;"> T 23 N R 27 E S 26 1/4 ——— S 35 </div> 2007 Deposit a magnet in a white plastic case at the base of the stainless steel post.
79.80	The cor. of secs. 26, 27, 34 and 35. <hr/> N. 0°15' W., bet. secs. 26 and 27. Over broken land.
40.02	Point for the 1/4 sec. cor. of secs. 26 and 27, at proportionate dist., there is no remaining evidence of the orig. cor. Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd. <div style="text-align: center;"> T 23 N R 27 E 1/4 S 27 S 26 </div> 2007 Deposit a magnet in a white plastic case at the base of the stainless steel post.

Dependent Resurvey of the Subdivisional Lines,
T. 23 N., R. 27 E., Gila and Salt River Meridian, Arizona

CHAINS									
71.60	Trail road, bears S. 35° E. and N. 35° W.								
80.04	<p>Point for the cor. of secs. 22, 23, 26 and 27, at proportionate dist., there is no remaining evidence of the orig. cor.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center;"> <table border="1"> <tr> <td>T 23 N</td> <td>R 27 E</td> </tr> <tr> <td>S 22</td> <td>S 23</td> </tr> <tr> <td>S 27</td> <td>S 26</td> </tr> </table> <p>2007</p> </div> <p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p> <p>Cor. is located 1.33 chs. E. of a trail road, bears N. 10° E. and S. 10° W.</p> <hr/>	T 23 N	R 27 E	S 22	S 23	S 27	S 26		
T 23 N	R 27 E								
S 22	S 23								
S 27	S 26								
	<p>From the cor. of secs. 23, 24, 25 and 26.</p> <p>N. 89°00' W., bet. secs. 23 and 26.</p> <p>Over rolling land.</p>								
27.20	Trail road, bears N. 15° E. and S. 15° W.								
40.045	<p>Point for the 1/4 sec. cor. of secs. 23 and 26, at proportionate dist., there is no remaining evidence of the orig. cor.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center;"> <table border="1"> <tr> <td>T 23 N</td> <td>R 27 E</td> </tr> <tr> <td>S 23</td> <td></td> </tr> <tr> <td>1/4</td> <td>—</td> </tr> <tr> <td>S 26</td> <td></td> </tr> </table> <p>2007</p> </div> <p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p>	T 23 N	R 27 E	S 23		1/4	—	S 26	
T 23 N	R 27 E								
S 23									
1/4	—								
S 26									
80.09	<p>The cor. of secs. 22, 23, 26 and 27.</p> <hr/> <p>N. 0°09' E., bet. secs. 22 and 23.</p> <p>Over rolling land.</p>								
19.70	Trail road, bears S. 85° E. and N. 85° W.								

**Dependent Resurvey of the Subdivisional Lines,
T. 23 N., R. 27 E., Gila and Salt River Meridian, Arizona**

CHAINS	
40.02	<p>Point for the 1/4 sec. cor. of secs. 22 and 23, at proportionate dist., there is no remaining evidence of the orig. cor.</p> <p>Set a brass tablet, 3 1/4 ins. diam., 2 1/2 ins. stem. cemented in place, in a drill hole, in sandstone bedrock, with top mkd.</p> <div style="text-align: center;"> <p>T 23 N R 27 E 1/4 S 22 S 23</p> <p>2007</p> </div> <p>Deposit a magnet in a white plastic case, beneath the brass tablet.</p>
48.40	Wash, 30 ft. wide, 4 ft. deep, drains W.
61.40	S. bank of Bent Knee wash, 5 ft. high, bears N. 75° E. and S. 75° W.
62.80	N. bank of Bent Knee wash, 5 ft. high, bears N. 70° E. and S. 70° W.
80.04	<p>The cor. of secs. 14, 15, 22 and 23, at proportionate dist., there is no remaining evidence of the orig. cor.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center;"> <p>T 23 N R 27 E S 15 S 14 S 22 S 23</p> <p>2007</p> </div> <p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p> <hr/> <p>From the cor. of secs. 13, 14, 23 and 24.</p> <p>N. 88°57' W., bet. secs. 14 and 23.</p> <p>Over rolling land.</p>
40.18	<p>Point for the 1/4 sec. cor. of secs. 14 and 23, at proportionate dist., there is no remaining evidence of the orig. cor.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p>

**Dependent Resurvey of the Subdivisional Lines,
T. 23 N., R. 27 E., Gila and Salt River Meridian, Arizona**

CHAINS	
	T 23 N R 27 E S 14 1/4 ——— S 23 2007
	Deposit a magnet in a white plastic case at the base of the stainless steel post.
43.60	Bent Knee wash, 60 ft. wide, 2 ft. deep, drains S. 55° W.
80.36	The cor. of secs. 14, 15, 22 and 23.
	<hr/> N. 0°18' E., bet. secs. 14 and 15. Over rolling land.
40.02	Point for the 1/4 sec. cor. of secs. 14 and 15, at proportionate dist., there is no remaining evidence of the orig. cor. Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.
	T 23 N R 27 E 1/4 S 15 S 14 2007
	Deposit a magnet in a white plastic case at the base of the stainless steel post.
69.60	Trail road, bears S. 75° E. and N. 75° W.
80.04	Point for the cor. of secs. 10, 11, 14 and 15, at proportionate dist., there is no remaining evidence of the orig. cor. Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.
	T 23 N R 27 E S 10 S 11 S 15 S 14 2007
	Deposit a magnet in a white plastic case at the base of the stainless steel post.
	<hr/>

**Dependent Resurvey of the Subdivisional Lines,
T. 23 N., R. 27 E., Gila and Salt River Meridian, Arizona**

CHAINS	
	<p>From the cor. of secs. 11, 12, 13 and 14.</p> <p>N. 88°53' W., bet. secs. 11 and 14.</p> <p>Over broken land.</p>
39.97	<p>Point for the 1/4 sec. cor. of secs. 11 and 14, at proportionate dist., there is no remaining evidence of the orig. cor.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T 23 N R 27 E S 11 1/4 ——— S 14</p> <p style="text-align: center;">2007</p> <p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p> <p>Cor. is located 53 lks. E. of a trail road, bears N. 5° E. and S. 5° W.</p>
79.94	<p>The cor. of secs. 10, 11, 14 and 15.</p> <hr/> <p>North, bet. secs. 10 and 11.</p> <p>Over rolling and broken land.</p>
40.025	<p>Point for the 1/4 sec. cor. of secs. 10 and 11, at proportionate dist., there is no remaining evidence of the orig. cor.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T 23 N R 27 E 1/4 S 10 S 11</p> <p style="text-align: center;">2007</p> <p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p> <p>Cor. is located 14 lks. W. of a faint wood road, bears N. 35° E. and S. 35° W.</p>
80.05	<p>Point for the cor. of secs. 2, 3, 10 and 11, at proportionate dist., there is no remaining evidence of the orig. cor.</p>

**Dependent Resurvey of the Subdivisional Lines,
T. 23 N., R. 27 E., Gila and Salt River Meridian, Arizona**

CHAINS	
	<p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p align="center"> T 23 N R 27 E S 3 S 2 ----- S 10 S 11 </p> <p align="center">2007</p> <p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p> <hr/>
	<p>From the cor. of secs. 1, 2, 11 and 12.</p> <p>N. 88°50' W., bet. secs. 2 and 11.</p> <p>Over rolling land.</p>
40.00	<p>Point for the 1/4 sec. cor. of secs. 2 and 11, at proportionate dist., there is no remaining evidence of the orig. cor.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p align="center"> T 23 N R 27 E S 2 1/4 ——— S 11 </p> <p align="center">2007</p> <p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p>
80.00	<p>The cor. of secs. 2, 3, 10 and 11.</p> <hr/> <p>N. 0°28' E., bet. secs. 2 and 3.</p> <p>Over rolling and broken land.</p>
28.00	<p>Banana Wash road, Navajo Rt. 9352, a graded road, 24 ft. wide, bears N. 55° E. and S. 55° W.</p>
40.03	<p>Point for the 1/4 sec. cor. of secs. 2 and 3, at proportionate dist., there is no remaining evidence of the orig. cor.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p>

**Dependent Resurvey of the Subdivisional Lines,
T. 23 N., R. 27 E., Gila and Salt River Meridian, Arizona**

CHAINS	
	T 23 N R 27 E 1/4 S 3 S 2 2007
	Deposit a magnet in a white plastic case at the base of the stainless steel post.
80.13	The cor. of secs. 2, 3, 34 and 35, on the N. bdy. of the Tp., monumented with a stainless steel post, 2 1/2 ins. diam., firmly set, projecting 3 ins. above ground, with brass cap mkd. T24N R27E S34 S35 S3 S2 T23N 2003. Add the marks 2007 to the brass cap.
	<hr/> From the cor. of secs. 3, 4, 33 and 34, on the S. bdy. of the Tp., monumented with a stainless steel post, 2 1/2 ins. diam., firmly set, projecting 4 ins. above ground, with brass cap mkd. T23N R27E S33 S34 S4 S3 T22N 2003. Add the marks 2007 to the brass cap.
	N. 0°03' E., bet. secs. 33 and 34. Over rolling land.
3.00	Fence, barbed wire, 5 strand, bears S. 55° E. and N. 55° W.
40.015	Point for the 1/4 sec. cor. of secs. 33 and 34, at proportionate dist., there is no remaining evidence of the orig. cor. Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ns. in the ground, with brass cap mkd.
	T 23 N R 27 E 1/4 S 33 S 34 2007
	Deposit a magnet in a white plastic case at the base of the stainless steel post. Cor. is located 1.63 chs. S. of a fence line, barbed wire, 4 strand, bears N. 55° E. and S. 55° W.
60.00	Navajo Rt. 9411, graded road, 20 ft. wide, bears N. 45° E. and S. 45° W.
64.70	Power line, bears N. 45° E. and S. 45° W.

**Dependent Resurvey of the Subdivisional Lines,
T. 23 N., R. 27 E., Gila and Salt River Meridian, Arizona**

CHAINS									
64.10	Trail road, bears E. and W.								
71.99	Barbed wire fence, 4 strands, bears N. 60° E. and S. 60° W.								
80.03	Point for the cor. of secs. 27, 28, 33 and 34, at proportionate dist., there is no remaining evidence of the orig. cor. Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd. <div style="text-align: center;"> <table style="margin: auto;"> <tr><td>T 23 N</td><td>R 27 E</td></tr> <tr><td>S 28</td><td>S 27</td></tr> <tr><td>S 33</td><td>S 34</td></tr> </table> <p>2007</p> </div> <p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p> <hr/> <p>From the cor. of secs. 26, 27, 34 and 35. N. 89°08' W., bet. secs. 27 and 34. Over rolling land.</p>	T 23 N	R 27 E	S 28	S 27	S 33	S 34		
T 23 N	R 27 E								
S 28	S 27								
S 33	S 34								
32.85	E. right-of-way fence, barbed wire, 4 strand, parallels highway.								
34.82	State Highway 191, asphalt surface, 28 ft. wide, bears S. 40° E. and N. 40° W.								
36.90	W. right-of-way fence, barbed wire, 4 strand, parallels highway.								
40.09	Point for the 1/4 sec. cor. of secs. 27 and 34, at proportionate dist., there is no remaining evidence of the orig. cor. Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd. <div style="text-align: center;"> <table style="margin: auto;"> <tr><td>T 23 N</td><td>R 27 E</td></tr> <tr><td>S 27</td><td></td></tr> <tr><td>1/4</td><td>—</td></tr> <tr><td>S 34</td><td></td></tr> </table> <p>2007</p> </div> <p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p>	T 23 N	R 27 E	S 27		1/4	—	S 34	
T 23 N	R 27 E								
S 27									
1/4	—								
S 34									
58.30	Navajo Rt. 9411, graded road, 20 ft. wide, bears N. 10° E. and S. 35° W.								
62.40	Power line, bears S. 45° E. and N. 45° W.								

**Dependent Resurvey of the Subdivisional Lines,
T. 23 N., R. 27 E., Gila and Salt River Meridian, Arizona**

CHAINS							
65.10	Power line, bears N. 45° E. and S. 45° W.						
69.31	Barbed wire fence, 4 strand, bears N. 35° E. and S. 35° W.						
80.18	The cor. of secs. 27, 28, 33 and 34.						
	N. 0°06' W., bet. secs. 27 and 28.						
	Over rolling land.						
38.18	S. right-of-way fence, barbed wire, 4 strand, parallels highway.						
40.015	Point for the 1/4 sec. cor. of secs. 27 and 28, at proportionate dist., there is no remaining evidence of the orig. cor.						
	Set a PK nail in the pavement of State Highway 191, 5 ft. from W. edge of pavement.						
	from which						
	A stainless steel post, 28 ins. long, 2 1/2 ins. diam., set 24 ins. in the ground for a reference monument, bears N. 40°00' E., 110.0 ft. dist. with brass cap mkd. RM T23N R27E S27 1/4 110.00 FT. TO COR 2007 and an arrow pointing to the corner. Deposit a magnet in a white plastic case at the base of the stainless steel post.						
	A stainless steel post, 28 ins. long, 2 1/2 ins. diam., set 24 ins. in the ground for a reference monument, bears S. 40°00' W., 94.0 ft. dist., with brass cap mkd. RM T23N R27E S28 1/4 94.00 FT. TO COR 2007 and an arrow pointing to the corner. Deposit a magnet in a white plastic case at the base of the stainless steel post.						
	Cor. is located in the pavement of State Highway 191, 15 lks. S. of the center of highway, asphalt surface, 28 ft. wide, bears S. 50° E. and N. 50° W.						
42.18	N. right-of-way fence, barbed wire, 4 strand, parallels highway.						
80.03	Point for the cor. of secs. 21, 22, 27 and 28, at proportionate dist., there is no remaining evidence of the orig. cor.						
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.						
	<table style="margin-left: auto; margin-right: auto;"> <tr> <td>T 23 N</td> <td>R 27 E</td> </tr> <tr> <td style="border-right: 1px solid black;">S 21</td> <td>S 22</td> </tr> <tr> <td style="border-right: 1px solid black;">S 28</td> <td>S 27</td> </tr> </table>	T 23 N	R 27 E	S 21	S 22	S 28	S 27
T 23 N	R 27 E						
S 21	S 22						
S 28	S 27						
	2007						

**Dependent Resurvey of the Subdivisional Lines,
T. 23 N., R. 27 E., Gila and Salt River Meridian, Arizona**

CHAINS	
	<p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p> <hr/> <p>From the cor. of secs. 22, 23, 26 and 27.</p> <p>N. 89°09' W., bet. secs. 22 and 27.</p> <p>Over broken land.</p>
39.985	<p>Point for the 1/4 sec. cor. of secs. 22 and 27, at proportionate dist., there is no remaining evidence of the orig. cor.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T 23 N R 27 E S 22 1/4 <u> </u> S 27</p> <p style="text-align: center;">2007</p> <p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p>
52.60	Trail road, bears N. 25° E. and S. 25° W.
73.60	Trail road, bears S. 15° E. and N. 15° W.
74.30	Trail road, bears S. 50° E. and N. 50° W.
79.97	The cor. of secs. 21, 22, 27 and 28.
	<hr/> <p>N. 0°19' E., bet. secs. 21 and 22.</p> <p>Over rolling land.</p>
5.10	Trail road, bears S. 60° E. and N. 60° W.
5.29	Fence, barbed wire, 4 strand, bears S. 65° E. and N. 65° W.
26.40	Power line, bears N. 45° E. and S. 45° W.
26.60	Power line, bears S. 50° E. and N. 50° W.
27.96	Fence, 1 strand barbed wire with 3 strands of 1/4 ins. diam. cable, bears S. 80° E. and N. 80° W.
40.015	Point for the 1/4 sec. cor. of secs. 21 and 22, at proportionate dist., there is no remaining evidence of the orig. cor.

**Dependent Resurvey of the Subdivisional Lines,
T. 23 N., R. 27 E., Gila and Salt River Meridian, Arizona**

CHAINS	
	<p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T 23 N R 27 E 1/4 S 21 S 22</p> <p style="text-align: center;">2007</p> <p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p> <p>Set steel fence post alongside.</p> <p>Cor. is located 1.14 chs. N. of a trail road, bears N. 75° E. and S. 75° W. and 1.44 chs. N. of a barbed wire fence, 5 strand, bears N. 75° E. and S. 75° W. and 2.50 chs. S. of Bent Knee wash, 170 ft. wide, 4 ft. deep, drains S. 80° W.</p>
80.03	<p>Point for the cor. of secs. 15, 16, 21 and 22, at proportionate dist., there is no remaining evidence of the orig. cor.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T 23 N R 27 E S 16 S 15 S 21 S 22</p> <p style="text-align: center;">2007</p> <p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p> <hr/> <p>From the cor. of secs. 14, 15, 22 and 23.</p> <p>N. 89°10' W., bet. secs. 15 and 22.</p> <p>Over rolling land.</p>
39.855	<p>Point for the 1/4 sec. cor. of secs. 15 and 22, at proportionate dist., there is no remaining evidence of the orig. cor.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T 23 N R 27 E S 15 1/4 ——— S 22</p> <p style="text-align: center;">2007</p>

Dependent Resurvey of the Subdivisional Lines,
T. 23 N., R. 27 E., Gila and Salt River Meridian, Arizona

CHAINS	<p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p>
48.50	Trail road, bears N. 60° E. and S. 60° W.
79.71	The cor. of secs. 15, 16, 21 and 22.
<p>N. 0°04' W., bet. secs. 15 and 16.</p> <p>Over rolling land.</p>	
28.66	Fence, barbed wire, 3 strand, bears N. 55° E. and S. 55° W.
40.015	<p>Point for the 1/4 sec. cor. of secs. 15 and 16, at proportionate dist., there is no remaining evidence of the orig. cor.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p>
<p>T 23 N R 27 E 1/4 S 16 S 15</p> <p>2007</p>	
<p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p> <p>From this cor. point, the most NE corner of an octagon hogan, bears S. 69°22' W., 1.62 chs. dist., 9.6 ft. per side.</p>	
48.34	Barbed wire fence, 4 strand, bears N. 55° E. and S. 55° W.
75.40	Trail road, bears N. 80° E. and S. 80° W.
80.03	<p>Point for the cor. of secs. 9, 10, 15 and 16, at proportionate dist., there is no remaining evidence of the orig. cor.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p>
<p>T 23 N R 27 E S 9 S 10 S 16 S 15</p> <p>2007</p>	
<p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p>	
<p>From the cor. of secs. 10, 11, 14 and 15.</p>	

**Dependent Resurvey of the Subdivisional Lines,
T. 23 N., R. 27 E., Gila and Salt River Meridian, Arizona**

CHAINS	
	N. 89°11' W., bet. secs. 10 and 15. Over rolling land.
40.11	Point for the 1/4 sec. cor. of secs. 10 and 15, at proportionate dist., there is no remaining evidence of the orig. cor. Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., flush with the surface of the ground, with brass cap mkd. <div style="text-align: center;"> T 23 N R 27 E S 10 1/4 ——— S 15 2007 </div> Deposit a magnet in a white plastic case at the base of the stainless steel post. Cor. is located 6 lks. S. of a trail road, bears S. 85° E. and N. 85° W. Set a steel fence post nearby.
46.20	Trail road, bears N. 85° E. and S. 85° W.
80.22	The cor. of secs. 9, 10, 15 and 16. <hr/>
	N. 0°03' E., bet. secs. 9 and 10. Over rolling land.
31.80	Trail road, bears N. 65° E. and S. 65° W.
40.015	Point for the 1/4 sec. cor. of secs. 9 and 10, at proportionate dist., there is no remaining evidence of the orig. cor. Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd. <div style="text-align: center;"> T 23 N R 27 E 1/4 S 9 S 10 2007 </div> Deposit a magnet in a white plastic case at the base of the stainless steel post.
58.00	Power line, bears N. 60° E. and S. 60° W.

**Dependent Resurvey of the Subdivisional Lines,
T. 23 N., R. 27 E., Gila and Salt River Meridian, Arizona**

CHAINS									
59.70	Banana Wash road, Navajo Rt. 9352, a graded road, 30 ft. wide, bears N. 65° E. and S. 65° W.								
80.03	<p>Point for the cor. of secs. 3, 4, 9 and 10, at proportionate dist., there is no remaining evidence of the orig. cor.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center;"> <table style="margin: auto;"> <tr><td>T 23 N</td><td>R 27 E</td></tr> <tr><td>S 4</td><td>S 3</td></tr> <tr><td>S 9</td><td>S 10</td></tr> </table> <p>2007</p> </div> <p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p> <hr/> <p>From the cor. of secs. 2, 3, 10 and 11.</p> <p>N. 89°11' W., bet. secs. 3 and 10.</p> <p>Over rolling land.</p>	T 23 N	R 27 E	S 4	S 3	S 9	S 10		
T 23 N	R 27 E								
S 4	S 3								
S 9	S 10								
40.08	<p>Point for the 1/4 sec. cor. of secs. 3 and 10, at proportionate dist., there is no remaining evidence of the orig. cor.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center;"> <table style="margin: auto;"> <tr><td>T 23 N</td><td>R 27 E</td></tr> <tr><td>S 3</td><td></td></tr> <tr><td>1/4</td><td>—</td></tr> <tr><td>S 10</td><td></td></tr> </table> <p>2007</p> </div> <p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p>	T 23 N	R 27 E	S 3		1/4	—	S 10	
T 23 N	R 27 E								
S 3									
1/4	—								
S 10									
42.00	Power line, bears N. 60° E. and S. 60° W.								
43.90	Banana Wash road, Navajo Rt. 9352, a graded road, 30 ft. wide, bears N. 60° E. and S. 60° W.								
80.16	<p>The cor. of secs. 3, 4, 9 and 10.</p> <hr/> <p>N. 0°33' E., bet. secs. 3 and 4.</p> <p>Over rolling and broken land.</p>								

**Dependent Resurvey of the Subdivisional Lines,
T. 23 N., R. 27 E., Gila and Salt River Meridian, Arizona**

CHAINS	
40.01	<p>Point for the 1/4 sec. cor. of secs. 3 and 4, at proportionate dist., there is no remaining evidence of the orig. cor.</p> <p>Set a brass tablet, 3 1/4 ins. diam., 2 1/2 ins. stem. cemented in place, in a drill hole, in sandstone bedrock, with top mkd.</p> <p style="text-align: center;">T 23 N R 27 E 1/4 S 4 S 3</p> <p style="text-align: center;">2007</p> <p>Deposit a magnet in a white plastic case, beneath the brass tablet.</p> <p>Cor. falls on N. edge of wash, 30 ft. wide, on a sandstone outcropping, 2 x 4 x 4 ft.</p>
80.39	<p>The cor. of secs. 3, 4, 33 and 34, on the N. bdy. of the Tp., monumented with a stainless steel post, 2 1/2 ins. diam., firmly set, projecting 4 ins. above ground, with brass cap mkd. T24N R27E S33 S34 S4 S3 T23N 2003.</p> <p>Add the marks 2007 to the brass cap.</p> <hr/> <p>From the cor. of secs. 4, 5, 32 and 33, on the S. bdy. of the Tp., monumented with a stainless steel post, 2 1/2 ins. diam., firmly set, projecting 4 ins. above ground, with brass cap mkd. T23N R27E S32 S33 S5 S4 T22N 2003.</p> <p>Add the marks 2007 to the brass cap.</p> <p>N. 0°01' W., bet. secs. 32 and 33.</p> <p>Over rolling land.</p>
40.085	<p>Point for the 1/4 sec. cor. of secs. 32 and 33, at proportionate dist., there is no remaining evidence of the orig. cor.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T 23 N R 27 E 1/4 S 32 S 33</p> <p style="text-align: center;">2007</p> <p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p>
52.40	<p>Trail road, bears N. 75° E. and S. 75° W.</p>

**Dependent Resurvey of the Subdivisional Lines,
T. 23 N., R. 27 E., Gila and Salt River Meridian, Arizona**

CHAINS									
80.17	<p>Point for the cor. of secs. 28, 29, 32 and 33, at proportionate dist., there is no remaining evidence of the orig. cor.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center;"> <table border="1"> <tr> <td>T 23 N</td> <td>R 27 E</td> </tr> <tr> <td>S 29</td> <td>S 28</td> </tr> <tr> <td>S 32</td> <td>S 33</td> </tr> </table> <p>2007</p> </div> <p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p> <hr/>	T 23 N	R 27 E	S 29	S 28	S 32	S 33		
T 23 N	R 27 E								
S 29	S 28								
S 32	S 33								
	<p>From the cor. of secs. 27, 28, 33 and 34.</p> <p>N. 89°01' W., bet. secs. 28 and 33.</p> <p>Over rolling land.</p>								
39.92	<p>Point for the 1/4 sec. cor. of secs. 28 and 33, at proportionate dist., there is no remaining evidence of the orig. cor.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center;"> <table border="1"> <tr> <td>T 23 N</td> <td>R 27 E</td> </tr> <tr> <td>S 28</td> <td></td> </tr> <tr> <td>1/4</td> <td>—</td> </tr> <tr> <td>S 33</td> <td></td> </tr> </table> <p>2007</p> </div> <p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p>	T 23 N	R 27 E	S 28		1/4	—	S 33	
T 23 N	R 27 E								
S 28									
1/4	—								
S 33									
79.84	<p>The cor. of secs. 28, 29, 32 and 33.</p> <hr/> <p>N. 0°25' W., bet. secs. 28 and 29.</p> <p>Over rolling land.</p>								
36.70	<p>Trail road, bears N. 45° E. and S. 45° W.</p>								
40.085	<p>Point for the 1/4 sec. cor. of secs. 28 and 29, at proportionate dist., there is no remaining evidence of the orig. cor.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p>								

**Dependent Resurvey of the Subdivisional Lines,
T. 23 N., R. 27 E., Gila and Salt River Meridian, Arizona**

CHAINS	
	<p align="center">T 23 N R 27 E 1/4 S 29 S 28 2007</p>
80.17	<p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p> <p>Point for the cor. of secs. 20, 21, 28 and 29, at proportionate dist., there is no remaining evidence of the orig. cor.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p align="center">T 23 N R 27 E S 20 S 21 S 29 S 28 2007</p>
	<p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p> <p>Cor. is located 1.16 chs. N. of a trail road, bears S. 70° E. and N. 70° W.</p> <hr/> <p>From the cor. of secs. 21, 22, 27 and 28.</p> <p>N. 88°56' W., bet. secs. 21 and 28.</p> <p>Over rolling land.</p>
40.13	<p>Point for the 1/4 sec. cor. of secs. 21 and 28, at proportionate dist., there is no remaining evidence of the orig. cor.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p align="center">T 23 N R 27 E S 21 1/4 ——— S 28 2007</p>
46.13	<p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p> <p>N. right-of-way fence, barbed wire, 5 strand, parallels highway.</p>

**Dependent Resurvey of the Subdivisional Lines,
T. 23 N., R. 27 E., Gila and Salt River Meridian, Arizona**

CHAINS	
48.55	State Highway 191, asphalt surfaced, 27 ft. wide, bears S. 50° E. and N. 50° W.
50.97	S. right-of-way fence, barbed wire, 5 strand, parallels highway.
80.26	The cor. of secs. 20, 21, 28 and 29.
	N. 0°34' E., bet. secs. 20 and 21.
	Over rolling and broken land.
23.78	S. right-of-way fence, barbed wire, 5 strand, parallels highway.
25.83	State Highway 191, asphalt surfaced, 27 ft. wide, bears S. 50° E. and N. 50° W.
27.88	N. Right-of-way fence, barbed wire, 5 strand, parallels highway.
40.085	Point for the 1/4 sec. cor. of secs. 20 and 21, at proportionate dist., there is no remaining evidence of the orig. cor.
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.
	T 23 N R 27 E 1/4 S 20 S 21 2007
	Deposit a magnet in a white plastic case at the base of the stainless steel post.
54.45	Barbed wire fence, 2 strand, bears E. and W.
54.70	Trail road, bears E. and W.
54.95	Barbed wire fence, 5 strand, bears E. and W., thence entering cultivated field.
61.02	Barbed wire fence in a cultivated field, 5 strand, bears N. 30° E. and S. 30° W.
65.55	Barbed wire fence, 4 strand, bears S. 60° E. and N. 60° W., thence leaving cultivated field.
66.20	Bent Knee wash, 40 ft. wide, 3 ft. deep, drains N. 60° W.
74.00	Barbed wire fence, 4 strands, bears S. 80° E. and N. 80° W.
80.17	Point for the cor. of secs. 16, 17, 20 and 21, at proportionate dist., there is no remaining evidence of the orig. cor.

**Dependent Resurvey of the Subdivisional Lines,
T. 23 N., R. 27 E., Gila and Salt River Meridian, Arizona**

CHAINS	
	<p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T 23 N R 27 E S 17 S 16 S 20 S 21</p> <p style="text-align: center;">2007</p> <p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p> <p>Cor. is located 19 lks. N. of a wash, 6 ft. wide, 1 ft. deep, drains S. 70° W.</p> <hr/> <p>From the cor. of secs. 15, 16, 21 and 22.</p> <p>N. 88°49' W., bet. secs. 16 and 21.</p> <p>Over rolling land.</p>
39.955	<p>Point for the 1/4 sec. cor. of secs. 16 and 21, at proportionate dist., there is no remaining evidence of the orig. cor.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T 23 N R 27 E S 16 1/4 ——— S 21</p> <p style="text-align: center;">2007</p> <p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p>
79.91	<p>The cor. of secs. 16, 17, 20 and 21.</p> <hr/> <p>N. 0°09' W., bet. secs. 16 and 17.</p> <p>Over broken land.</p>
40.085	<p>Point for the 1/4 sec. cor. of secs. 16 and 17, at proportionate dist., there is no remaining evidence of the orig. cor.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p>

**Dependent Resurvey of the Subdivisional Lines,
T. 23 N., R. 27 E., Gila and Salt River Meridian, Arizona**

CHAINS	
80.17	<p align="center">T 23 N R 27 E 1/4 S 17 S 16</p> <p align="center">2007</p> <p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p> <p>Point for the cor. of secs. 8, 9, 16 and 17, at proportionate dist., there is no remaining evidence of the orig. cor.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 8 ins. below the surface of the ground, with brass cap mkd.</p> <p align="center">T 23 N R 27 E S 8 S 9 ----- S 17 S 16</p> <p align="center">2007</p> <p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p> <p>Cor. is located in portable livestock coral, adjacent to an L-shape storage shack, 74 x 49 ft. long, 56 lks. to the NE corner and 58 lks. to the SE corner of the shack.</p> <hr/>
40.005	<p>From the cor. of secs. 9, 10, 15 and 16.</p> <p>N. 88°43' W., bet. secs. 9 and 16.</p> <p>Over rolling land.</p> <p>Point for the 1/4 sec. cor. of secs. 9 and 16, at proportionate dist., there is no remaining evidence of the orig. cor.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p align="center">T 23 N R 27 E S 9 1/4 ——— S 16</p> <p align="center">2007</p> <p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p>
80.01	<p>The cor. of secs. 8, 9, 16 and 17.</p> <hr/>

**Dependent Resurvey of the Subdivisional Lines,
T. 23 N., R. 27 E., Gila and Salt River Meridian, Arizona**

CHAINS	
	N. 0°05' E., bet. secs. 8 and 9. Over broken land.
36.50	Banana Wash road, Navajo Rt. 9352, a graded road, 21 ft. wide, bears N. 55° E. and S. 55° W.
40.085	Point for the 1/4 sec. cor. of secs. 8 and 9, at proportionate dist., there is no remaining evidence of the orig. cor. Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd. <div style="text-align: center;"> T 23 N R 27 E 1/4 S 8 S 9 2007 </div> Deposit a magnet in a white plastic case at the base of the stainless steel post.
68.50	Wide Ruins loop road, a graded road, 25 ft. wide, bears N. 15° E. and S. 15° W.
80.17	Point for the cor. of secs. 4, 5, 8 and 9, at proportionate dist., there is no remaining evidence of the orig. cor. Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. below the surface of a graded road, with brass cap mkd. <div style="text-align: center;"> T 23 N R 27 E S 5 S 4 S 8 S 9 2007 </div> from which A stainless steel post, 28 ins. long, 2 1/2 ins. diam., set 24 ins. in the ground for a reference monument, bears N. 20°00' E., 75.0 ft. dist., with brass cap mkd. RM T23N R27E S4 75.0 FT. TO COR 2007 and an arrow pointing to the corner. Deposit a magnet in a white plastic case at the base of the stainless steel post. Set a steel fence post nearby.

**Dependent Resurvey of the Subdivisional Lines,
T. 23 N., R. 27 E., Gila and Salt River Meridian, Arizona**

CHAINS	
	<p>A stainless steel post, 28 ins. long, 2 1/2 ins. diam., set 24 ins. in the ground for a reference monument, bears N. 70°00' W., 100.0 ft. dist., with brass cap mkd. RM T23N R27E S5 100.0 FT. TO COR 2007 and an arrow pointing to the corner. Deposit a magnet in a white plastic case at the base of the stainless steel post. Set a steel fence post nearby.</p> <p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p> <p>Cor. is located in the center of Wide Ruins loop road, a graded road, 24 ft. wide, bears S. 30° E. and N. 30° W., 36 lks. S. of the end of asphalt pavement.</p> <hr/> <p>From the cor. of secs. 3, 4, 9 and 10.</p> <p>N. 88°37' W., bet. secs. 4 and 9.</p> <p>Over rolling land.</p>
39.975	<p>Point for the 1/4 sec. cor. of secs. 4 and 9, at proportionate dist., there is no remaining evidence of the orig. cor.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center;"> <p>T 23 N R 27 E</p> <p>S 4</p> <p>1/4 ———</p> <p>S 9</p> <p>2007</p> </div> <p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p>
79.95	<p>The cor. of secs. 4, 5, 8 and 9.</p> <hr/> <p>N. 0°30' E., bet. secs. 4 and 5.</p> <p>Over broken land.</p>
40.09	<p>Point for the 1/4 sec. cor. of secs. 4 and 5, at proportionate dist., there is no remaining evidence of the orig. cor.</p> <p>Set a magnet in a white plastic case, 24 ins. in the ground.</p> <p>from which</p>

**Dependent Resurvey of the Subdivisional Lines,
T. 23 N., R. 27 E., Gila and Salt River Meridian, Arizona**

CHAINS	
	<p>A stainless steel post, 28 ins. long, 2 1/2 ins. diam., set 24 ins. in the ground for a reference monument, bears N. 50°00' E., 140.0 ft. dist. with brass cap mkd. RM T23N R27E S4 1/4 140.0 FT. TO COR 2007 and an arrow pointing to the corner. Deposit a magnet in a white plastic case at the base of the stainless steel post. Set a steel fence post nearby.</p> <p>A stainless steel post, 28 ins. long, 2 1/2 ins. diam., set 24 ins. in the ground for a reference monument, bears S. 50°00' W., 50.0 ft. dist., with brass cap mkd. RM T23N R27E S5 1/4 50.0 FT. TO COR 2007 and an arrow pointing to the corner. Deposit a magnet in a white plastic case at the base of the stainless steel post. Set a steel fence post nearby.</p> <p>Cor. is located in the center of Oak Ridge wash, 21 ft. wide, 4 ft. deep, drains N. 35° W.</p>
79.87	<p>The cor. of secs. 4, 5, 32 and 33, on the N. bdy. of the Tp., monumented with a stainless steel post, 2 1/2 ins. diam., firmly set, projecting 4 ins. above ground, with brass cap mkd. T24N R27E S32 S33 S5 S4 T23N 2003.</p> <p>Add the marks 2007 to the brass cap.</p>
	<p>From the cor. of secs. 5, 6, 31 and 32, on the S. bdy. of the Tp., monumented with a stainless steel post, 2 1/2 ins. diam., firmly set, projecting 4 ins. above ground, with brass cap mkd. T23N R27E S31 S32 S6 S5 T22N 2003.</p> <p>Add the marks 2007 to the brass cap.</p> <p>N. 0°04' E., bet. secs. 31 and 32.</p> <p>Over rolling land.</p>
21.40	<p>Trail road, bears E. and W.</p>
40.115	<p>Point for the 1/4 sec. cor. of secs. 31 and 32, at proportionate dist., there is no remaining evidence of the orig. cor.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p align="center">T 23 N R 27 E 1/4 S 31 S 32 2007</p>

**Dependent Resurvey of the Subdivisional Lines,
T. 23 N., R. 27 E., Gila and Salt River Meridian, Arizona**

CHAINS									
	<p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p>								
80.23	<p>Point for the cor. of secs. 29, 30, 31 and 32, at proportionate dist., there is no remaining evidence of the orig. cor.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center;"> <table style="margin: auto;"> <tr><td>T 23 N</td><td>R 27 E</td></tr> <tr><td>S 30</td><td>S 29</td></tr> <tr><td>S 31</td><td>S 32</td></tr> </table> <p>2007</p> </div> <p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p> <p>Cor. is located 2.44 chs. W. of a trail road, bears S. 70° E. and N. 70° W.</p> <hr/> <p>From the cor. of secs. 28, 29, 32 and 33.</p> <p>N. 89°05' W., bet. secs. 29 and 32.</p> <p>Over rolling land.</p>	T 23 N	R 27 E	S 30	S 29	S 31	S 32		
T 23 N	R 27 E								
S 30	S 29								
S 31	S 32								
39.815	<p>Point for the 1/4 sec. cor. of secs. 29 and 32, at proportionate dist., there is no remaining evidence of the orig. cor.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center;"> <table style="margin: auto;"> <tr><td>T 23 N</td><td>R 27 E</td></tr> <tr><td>S 29</td><td></td></tr> <tr><td>1/4</td><td>—</td></tr> <tr><td>S 32</td><td></td></tr> </table> <p>2007</p> </div> <p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p> <p>Cor. is located 1.53 chs. W. of a trail road, bears N. and S.</p>	T 23 N	R 27 E	S 29		1/4	—	S 32	
T 23 N	R 27 E								
S 29									
1/4	—								
S 32									
63.20	<p>Power line, bears N. 15° E. and S. 15° W.</p>								
79.63	<p>The cor. of secs. 29, 30, 31 and 32.</p> <hr/> <p>N. 88°32' W., bet. secs. 30 and 31.</p>								

**Dependent Resurvey of the Subdivisional Lines,
T. 23 N., R. 27 E., Gila and Salt River Meridian, Arizona**

CHAINS	
	Over rolling land.
39.97	Point for the 1/4 sec. cor. of secs. 30 and 31, at proportionate dist., there is no remaining evidence of the orig. cor. Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd. <div style="text-align: center;"> T 23 N R 27 E S 30 1/4 ——— S 31 2007 </div>
	Deposit a magnet in a white plastic case at the base of the stainless steel post.
77.88	The cor. of secs. 25, 30, 31 and 36, on the W. bdy. of the Tp., monumented with a stainless steel post, 2 1/2 ins. diam., firmly set, projecting 4 ins. above ground, with brass cap mkd. T23N R26E R27E S25 S30 S31 S36 2003. Add the marks 2007 to the brass cap.
	From the cor. of secs. 29, 30, 31 and 32. N. 0°13' W., bet. secs. 29 and 30. Over rolling land.
36.50	Power line, bears E. and W.
40.115	Point for the 1/4 sec. cor. of secs. 29 and 30, at proportionate dist., there is no remaining evidence of the orig. cor. Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd. <div style="text-align: center;"> T 23 N R 27 E 1/4 S 30 S 29 2007 </div>
	Deposit a magnet in a white plastic case at the base of the stainless steel post.
48.70	Trail road, bears S. 85° E. and N. 85° W.
57.10	Graded road, 20 ft. wide, bears N. 50° E. and S. 50° W.

**Dependent Resurvey of the Subdivisional Lines,
T. 23 N., R. 27 E., Gila and Salt River Meridian, Arizona**

CHAINS									
57.42	Barbed wire fence, 6 strands, bears N. 50° E. and S. 50° W.								
80.23	Point for the cor. of secs. 19, 20, 29 and 30, at proportionate dist., there is no remaining evidence of the orig. cor.								
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.								
	<table border="0" style="margin-left: auto; margin-right: auto;"> <tr> <td>T 23 N</td> <td>R 27 E</td> </tr> <tr> <td>S 19</td> <td>S 20</td> </tr> <tr> <td>S 30</td> <td>S 29</td> </tr> </table>	T 23 N	R 27 E	S 19	S 20	S 30	S 29		
T 23 N	R 27 E								
S 19	S 20								
S 30	S 29								
	2007								
	Deposit a magnet in a white plastic case at the base of the stainless steel post.								
	<hr/> From the cor. of secs. 20, 21, 28 and 29.								
	N. 89°02' W., bet. secs. 20 and 29.								
	Over rolling land.								
37.60	Power line, bears N. 5° E. and S. 5° W.								
39.67	Point for the 1/4 sec. cor. of secs. 20 and 29, at proportionate dist., there is no remaining evidence of the orig. cor.								
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.								
	<table border="0" style="margin-left: auto; margin-right: auto;"> <tr> <td>T 23 N</td> <td>R 27 E</td> </tr> <tr> <td>S 20</td> <td></td> </tr> <tr> <td>1/4</td> <td>_____</td> </tr> <tr> <td>S 29</td> <td></td> </tr> </table>	T 23 N	R 27 E	S 20		1/4	_____	S 29	
T 23 N	R 27 E								
S 20									
1/4	_____								
S 29									
	2007								
	Deposit a magnet in a white plastic case at the base of the stainless steel post.								
	Cor. is located 73 lks. E. of a trail road, bears N. 15° E. and S. 15° W.								
54.30	Graded road, 22 ft. wide, bears N. 55° E. and S. 55° W.								
62.65	Barbed wire fence, 4 strand with one strand of 1/4 in. diam. cable, bears S. 5° E. and N. 5° W.								
79.34	The cor. of secs. 19, 20, 29 and 30.								
	<hr/>								

**Dependent Resurvey of the Subdivisional Lines,
T. 23 N., R. 27 E., Gila and Salt River Meridian, Arizona**

CHAINS	
	N. 87°55' W., bet. secs. 19 and 30. Over rolling land.
20.35	Barbed wire fence, 5 strands, bears S. 10° E. and N. 10° W.
39.99	Point for the 1/4 sec. cor. of secs. 19 and 30, at proportionate dist., there is no remaining evidence of the orig. cor. Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.
	T 23 N R 27 E S 19 1/4 ——— S 30 2007
	Deposit a magnet in a white plastic case at the base of the stainless steel post.
66.03	Barbed wire fence, 5 strand, bears N. 45° E. and S. 45° W.
77.58	The cor. of secs. 19, 24, 25 and 30, on the W. bdy. of the Tp., monumented with a stainless steel post, 2 1/2 ins. diam., firmly set, projecting 4 ins. above ground, with brass cap mkd. T23N R26E R27E S24 S19 S25 S30 2003. Add the marks 2007 to the brass cap.
	From the cor. of secs. 19, 20, 29 and 30. N. 0°16' E., bet. secs. 19 and 20. Over rolling land.
17.01	Barbed wire fence, 4 strand, bears S. 85° E. and N. 85° W.
17.56	Barbed wire fence, 5 strand, bears S. 85° E. and N. 85° W.
35.60	Barbed wire fence, 4 strand, bears N. 15° E. and S. 15° W.
40.115	Point for the 1/4 sec. cor. of secs. 19 and 20, at proportionate dist., there is no remaining evidence of the orig. cor. Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.

**Dependent Resurvey of the Subdivisional Lines,
T. 23 N., R. 27 E., Gila and Salt River Meridian, Arizona**

CHAINS	
	T 23 N R 27 E 1/4 S 19 S 20 2007
	Deposit a magnet in a white plastic case at the base of the stainless steel post.
48.02	Barbed wire fence, 5 strand, bears N. 60° E. and S. 60° W.
62.05	Barbed wire fence, 4 strand, bears S. 80° E. and N. 80° W.
71.71	Barbed wire fence, 5 strand, bears N. 20° E. and S. 20° W.
77.08	Barbed wire fence, 5 strand, bears S. 80° E. and N. 80° W.
80.23	Point for the cor. of secs. 17, 18, 19 and 20, at proportionate dist., there is no remaining evidence of the orig. cor.
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ns. in the ground, with brass cap mkd.
	T 23 N R 27 E S 18 S 17 S 19 S 20 2007
	Deposit a magnet in a white plastic case at the base of the stainless steel post.
	Set a steel fence post nearby.
	Cor. is located 1.56 chs. W. of a fence line, barbed wire, 4 strand, bears N. 5° E. and S. 5° W.
	<hr/> From the cor. of secs. 16, 17, 20 and 21. N. 88°59' W., bet. secs. 17 and 20. Over rolling land.
6.48	Barbed wire fence, 4 strands, bears S. 40° E. and N. 40° W.
21.50	Bent Knee wash, 80 ft. wide, 3 ft. deep, drains N. 30° E.
28.05	E. right-of-way fence, barbed wire, 4 strand, parallels highway.
29.62	State Highway 191, asphalt surfaced, 28 ft. wide, bears S. 15° E. and N. 15° W.

**Dependent Resurvey of the Subdivisional Lines,
T. 23 N., R. 27 E., Gila and Salt River Meridian, Arizona**

CHAINS	
31.19	W. right-of-way fence, barbed wire, 4 strand, parallels highway.
39.865	Point for the 1/4 sec. cor. of secs. 17 and 20, at proportionate dist., there is no remaining evidence of the orig. cor. Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd. <div style="text-align: center;"> T 23 N R 27 E S 17 1/4 ——— S 20 2007 </div>
	Deposit a magnet in a white plastic case at the base of the stainless steel post. Set a steel fence post nearby.
46.31	Barbed wire fence, 4 strand, bears N. 55° E. and S. 55° W.
48.10	Bent Knee wash, 80 ft. wide, 5 ft. deep, drains S. 65° W.
52.10	Power line, bears S. 40° E. and N. 40° W.
69.40	Wide Ruins wash, 30 ft. wide, 12 ft. deep, drains S. 15° E.
73.42	Barbed wire fence, 5 strand, bears N. 55° E. and S. 55° W.
79.73	The cor. of secs. 17, 18, 19 and 20. <hr/>
	N. 88°21' W., bet. secs. 18 and 19. Over rolling land.
39.98	Point for the 1/4 sec. cor. of secs. 18 and 19, at proportionate dist., there is no remaining evidence of the orig. cor. Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd. <div style="text-align: center;"> T 23 N R 27 E S 18 1/4 ——— S 19 2007 </div>
	Deposit a magnet in a white plastic case at the base of the stainless steel post.

**Dependent Resurvey of the Subdivisional Lines,
T. 23 N., R. 27 E., Gila and Salt River Meridian, Arizona**

CHAINS	
	Cor. is located 23 lks. S. of a barbed wire fence, 3 strand, bears E. and W.
77.77	The cor. of secs. 13, 18, 19 and 24, on the W. bdy. of the Tp., monumented with a stainless steel post, 2 1/2 ins. diam., firmly set, projecting 4 ins. above ground, with brass cap mkd. T23N R26E R27E S13 S18 S19 S24 2003. Add the marks 2007 to the brass cap.
	From the cor. of secs. 17, 18, 19 and 20. N. 0°04' W., bet. secs. 17 and 18. Over rolling land.
15.80	Wide Ruins wash, 30 ft. wide, 12 ft. deep, drains E.
24.40	Wide Ruins wash, 30 ft. wide, 5 ft. deep, drains S. 5 E., thence meanders back across the sec. line to the west.
35.87	Barbed wire fence, 4 strand, bears N. 15° E. and S. 15° W. to a fence corner, thence bears S. 80° E. back across the sec. line.
40.115	Point for the 1/4 sec. cor. of secs. 17 and 18, at proportionate dist., there is no remaining evidence of the orig. cor. Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd. <div style="text-align: center;"> T 23 N R 27 E 1/4 S 18 S 17 2007 </div>
	Deposit a magnet in a white plastic case at the base of the stainless steel post.
43.30	Wide Ruins wash, 50 ft. wide, 15 ft. deep, drains S. 35° W.
45.61	Barbed wire fence, 3 strand, bears N. 25° E. and S. 25° W.
57.63	Barbed wire fence, 3 strand, bears S. 75° E. and N. 75° W.
58.21	Barbed wire fence, 3 strand, bears S. 75° E. and N. 75° W.
80.23	Point for the cor. of secs. 7, 8, 17 and 18, at proportionate dist., there is no remaining evidence of the orig. cor. Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.

**Dependent Resurvey of the Subdivisional Lines,
T. 23 N., R. 27 E., Gila and Salt River Meridian, Arizona**

CHAINS									
	<table border="0"> <tr><td>T 23 N</td><td>R 27 E</td></tr> <tr><td>S 7</td><td>S 8</td></tr> <tr><td>S 18</td><td>S 17</td></tr> </table> <p>2007</p> <p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p> <p>Set a steel fence post nearby.</p> <p>Cor. is located 1.81 chs. N. of a power line, bears E. and W. and 2.44 chs. N. of a barbed wire fence, 3 strand, bears S. 70° E. and N. 70° W.</p> <hr/> <p>From the cor. of secs. 8, 9, 16 and 17.</p> <p>N. 88°57' W., bet. secs. 8 and 17.</p> <p>Over rolling land.</p>	T 23 N	R 27 E	S 7	S 8	S 18	S 17		
T 23 N	R 27 E								
S 7	S 8								
S 18	S 17								
31.60	Wide Ruins loop road, a graded road, 30 ft. wide, bears N. 25° E. and S. 25° W.								
39.805	Point for the 1/4 sec. cor. of secs. 8 and 17, at proportionate dist., there is no remaining evidence of the orig. cor.								
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.								
	<table border="0"> <tr><td>T 23 N</td><td>R 27 E</td></tr> <tr><td>S 8</td><td></td></tr> <tr><td>1/4</td><td>—</td></tr> <tr><td>S 17</td><td></td></tr> </table> <p>2007</p> <p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p>	T 23 N	R 27 E	S 8		1/4	—	S 17	
T 23 N	R 27 E								
S 8									
1/4	—								
S 17									
64.59	E. right-of-way fence, barbed wire, 4 strand, bears S. 75° E. and N. 75° W.								
65.50	State Highway 191, asphalt surfaced, 28 ft. wide, bears S. 30° E. and N. 30° W.								
65.97	W. right-of-way fence, barbed wire, 4 strand, bears N. 2° W. and S. 2° E.								
66.60	Wide Ruins wash, 80 ft. wide, 15 ft. deep, drains S. 55° W.								

**Dependent Resurvey of the Subdivisional Lines,
T. 23 N., R. 27 E., Gila and Salt River Meridian, Arizona**

CHAINS	
79.61	<p>The cor. of secs. 7, 8, 17 and 18.</p> <hr/> <p>N. 88°46' W., bet. secs. 7 and 18.</p> <p>Over rolling land.</p>
29.60	Tanner Springs road, Navajo Rt. 9401, a graded road, 20 ft. wide, bears N. 30° E. and S. 30° W.
39.99	<p>Point for the 1/4 sec. cor. of secs. 7 and 18, at proportionate dist., there is no remaining evidence of the orig. cor.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center;"> <p>T 23 N R 27 E</p> <p>S 7</p> <p>1/4 ———</p> <p>S 18</p> <p>2007</p> </div> <p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p>
77.47	<p>The cor. of secs. 7, 12, 13 and 18, on the W. bdy. of the Tp., monumented with a stainless steel post, 2 1/2 ins. diam., firmly set, projecting 3 ins. above ground, with brass cap mkd. T23N R26E R27E S12 S7 S13 S18 2003.</p> <p>Add the marks 2007 to the brass cap.</p> <hr/> <p>From the cor. of secs. 7, 8, 17 and 18.</p> <p>N. 0°05' E., bet. secs. 7 and 8.</p> <p>Over rolling land.</p>
22.83	S. right-of-way fence, barbed wire, 4 strand, parallels highway.
26.11	State Highway 191, asphalt surfaced, 28 ft. wide, bears S. 30° E. and N. 30° W.
27.63	From this point, a highway right-of-way marker, bears West, 2.56 chs. dist., monumented with a brass disk, 3 ins. diam., set in the center of 6 ins. diam. concrete collar, firmly set, projecting 4 ins. above ground, mkd. BIA ROADS 19, witnessed by a 4 x 4 ins. L shaped angle iron, 3 ft. N., projecting 2 ft. above ground mkd. 1119+02.05.

**Dependent Resurvey of the Subdivisional Lines,
T. 23 N., R. 27 E., Gila and Salt River Meridian, Arizona**

CHAINS	
29.06	From this point, a highway right-of-way marker, bears East, 11 lks. dist., monumented with a brass disk, 3 ins. diam., set in the center of 6 ins. diam. concrete collar, firmly set, projecting 4 ins. above ground, mkd. BIA ROADS 19, witnessed by a 4 x 4 ins. L shaped angle iron, 3.5 ft. N., projecting 19 ins. above ground mkd. 1119+02.05.
29.33	N. right-of-way fence, barbed wire, 4 strand, parallels highway.
40.115	Point for the 1/4 sec. cor. of secs. 7 and 8, at proportionate dist., there is no remaining evidence of the orig. cor. Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd. <div style="text-align: center;"> T 23 N R 27 E 1/4 S 7 S 8 2007 </div> Deposit a magnet in a white plastic case at the base of the stainless steel post.
80.23	Point for the cor. of secs. 5, 6, 7 and 8, at proportionate dist., there is no remaining evidence of the orig. cor. Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd. <div style="text-align: center;"> T 23 N R 27 E S 6 S 5 S 7 S 8 2007 </div> Deposit a magnet in a white plastic case at the base of the stainless steel post.
	<hr/> From the cor. of secs. 4, 5, 8 and 9. N. 88°54' W., bet. secs. 5 and 8. Over rolling land.
28.50	Chain link fence, 6 ft. high, bears N. 45° E. and S. 45° W.
37.96	Chain link fence, 6 ft. high, bears N. 20° E. and S. 20° W.
39.80	Point for the 1/4 sec. cor. of secs. 5 and 8, at proportionate dist., there is no remaining evidence of the orig. cor.

**Dependent Resurvey of the Subdivisional Lines,
T. 23 N., R. 27 E., Gila and Salt River Meridian, Arizona**

CHAINS	
	<p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ns. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T 23 N R 27 E S 5 1/4 ——— S 8</p> <p style="text-align: center;">2007</p> <p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p> <p>Set a steel fence post nearby.</p>
65.20	Wide Ruins wash, 30 ft. wide, 2 ft. deep, drains S. 30° W.
79.60	The cor. of secs. 5, 6, 7 and 8.
	<hr/> <p>N. 89°11' W., bet. secs. 6 and 7.</p> <p>Over rolling land.</p>
16.78	Wide Ruins loop highway, asphalt surfaced, 24 ft. wide, bears N. 75° E. and S. 75° W.
19.97	<p>From this point, a highway right-of-way marker, bears South, 2.32 chs. dist., , monumented with a brass disk, 3 ins. diam., set in the center of 10 ins. diam. concrete collar, firmly set, flush with the surface of the ground, mkd. BIA ROADS 2002, witnessed by a 4 x 4 ins. L shape angle iron, 3.4 ft. S., projecting 27 ins. above ground, mkd. POT 33+092.16.</p> <p>From this right-of-way marker, a highway right-of-way marker, bears N. 79°30' E., 28.19 ft. dist., monumented with a brass disk, 3 ins. diam., set in the center of 10 ins. diam. concrete collar, firmly set, flush with the surface of the ground, mkd. BIA ROADS 2002, witnessed by a 4 x 4 ins. L shaped angle iron, 3.4 ft. W., projecting 27 ins. above ground, mkd. PT 4+671.03.</p>
20.37	E. right-of-way fence, barbed wire, 5 strand, parallels highway.
20.52	From this point, a highway right-of-way marker, bears North, 60 lks., monumented with a brass disk, 3 ins. diam., set in the center of 10 ins. diam. concrete collar, firmly set, flush with the surface of the ground, mkd. BIA ROADS 2002, witnessed by a 4 x 4 ins. L shaped angle iron, 3 ft. S., projecting 27 ins. above ground, mkd. POT 32+895.30.

**Dependent Resurvey of the Subdivisional Lines,
T. 23 N., R. 27 E., Gila and Salt River Meridian, Arizona**

CHAINS	
	<p>From this right-of-way marker, a highway right-of-way marker, bears N. 79°39' E., 28.14 ft. dist., monumented with a brass disk, 3 ins. diam., set in the center of 10 ins. diam. concrete collar, firmly set, flush with the surface of the ground, mkd. BIA ROADS 2002, witnessed by a 4 x 4 ins. L shaped angle iron, 3 ft. E., projecting 27 ins. above ground mkd. PT 4+671.03.</p>
21.96	State Highway 191, asphalt surfaced, 40 ft. wide, bears S. 10° E. and N. 10° W.
23.51	W. right-of-way fence, barbed wire, 5 strand, parallels highway.
40.04	<p>Point for the 1/4 sec. cor. of secs. 6 and 7, at proportionate dist., there is no remaining evidence of the orig. cor.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T 23 N R 27 E S 6 1/4 ——— S 7</p> <p style="text-align: center;">2007</p> <p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p>
77.38	<p>The cor. of secs. 1, 6, 7 and 12, on the W. bdy. of the Tp., monumented with a stainless steel post, 2 1/2 ins. diam., firmly set, flush with the surface of the ground, with brass cap mkd. T23N R26E R27E S1 S6 S12 S7 2003.</p> <p>Add the marks 2007 to the brass cap.</p> <hr/> <p>From the cor. of secs. 5, 6, 7 and 8.</p> <p>N. 0°11' E., bet. secs. 5 and 6.</p> <p>Over rolling land.</p>
8.50	From this point, a highway right-of-way marker, bears West, 8 lks. dist., monumented with a brass disk, 3 ins. diam., set in the center of 12 ins. diam. concrete collar, firmly set, flush with the surface of the ground, mkd. BIA ROADS 2003, witnessed by a 4 x 4 ins. L shaped angle iron, 3.3 ft. W., projecting 27 ins. above ground, mkd. PT 4+234.33.
10.35	Wide Ruins loop highway, asphalt surfaced, 24 ft. wide, bears N. 60° E. and S. 55° W.

**Dependent Resurvey of the Subdivisional Lines,
T. 23 N., R. 27 E., Gila and Salt River Meridian, Arizona**

CHAINS	
30.30	Graded road, 18 ft. wide, bears S. 50° E. and N. 50° W.
40.11	<p>Point for the 1/4 sec. cor. of secs. 5 and 6, at proportionate dist., there is no remaining evidence of the orig. cor.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T 23 N R 27 E 1/4 S 6 S 5</p> <p style="text-align: center;">2007</p> <p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p>
79.74	<p>The cor. of secs. 5, 6, 31 and 32, on the N. bdy. of the Tp., monumented with a stainless steel post, 2 1/2 ins. diam., firmly set, projecting 4 ins. above ground, with brass cap mkd. T24N R27E S30 S31 S6 S5 T23N 2003.</p> <p>Add the marks 2007 to the brass cap.</p> <hr/>

T. 23 N., R. 27 E., Gila and Salt River Meridian, Arizona

CHAINS

GENERAL DESCRIPTION

The area surveyed is within the Navajo Indian Reservation and around the community of Wide Ruins, Arizona. The terrain is mostly rolling except along the north boundary, there are some areas of broken land. The drainage is south and southwesterly in the west portion of the township, with Wide Ruins Wash being the principal drainage. The main drainage in the east is Bent Knee Wash; which drains into Wide Ruins wash in the central portion of the township.

The elevation varies from 6000 to 6900 feet above sea level. The soil is sandy and sandy clay. There is a medium stand of juniper and piñon along the mesa within the township. Undergrowth principally consists of sagebrush, cacti, greasewood, scrub oak and native grasses.

The principal access to the township is provided by U.S. Highway 191, which enters the township in section 35, runs northwesterly and exits in section 6. There are some major graded roads and numerous trail roads through the township. There are numerous permanent residential homes throughout the township. Wide Ruins Elementary School, a boarding school is located in the southeast quarter of section 5. Much of this area is used for grazing livestock. There is no mining activity in this township.

The mean magnetic declination of $10 \frac{3}{4}^{\circ}$ E. was derived from the computer program GEOMAGIX, utilizing the World Magnetic Model for Epoch 2005 for the dates of survey.

CERTIFICATE OF SURVEY

I, Jones Curtiss, Cadastral Surveyor, HEREBY CERTIFY upon honor, that in pursuance of special instructions bearing date of the 1st day of May, 2002 and the Supplemental Special Instructions dated and approved September 23, 2002, I have dependently resurveyed the subdivisional lines of T. 23 N., R. 27 E., of the Gila and Salt River Meridian, in the State of Arizona, which are represented in the foregoing field notes as having been executed by me and under my direction. Said survey has been made in strict conformity with said special instructions, the Manual of Instructions for the Survey of the Public Lands of the United States, 1973, and in specific manner described in the foregoing field notes.

October 30, 2007
(Date)

Jones Curtiss
(Cadastral Surveyor)

CERTIFICATE OF APPROVAL

BUREAU OF LAND MANAGEMENT
Phoenix, Arizona

The foregoing field notes of the dependent resurvey of the subdivisional lines, T. 23 N., R. 27 E., Gila and Salt River Meridian, in the State of Arizona, executed by Jones Curtiss, Cadastral Surveyor, having been critically examined and found correct, are hereby approved.

Jan. 11, 2009
(Date)

Stephen K. Hansen
(Chief Cadastral Surveyor of Arizona)

~~CERTIFICATE OF TRANSCRIPT~~

~~I CERTIFY That the foregoing transcript of the field notes of the above described surveys in T. 23 N., R. 27 E., Gila and Salt River Meridian, Arizona, is a true copy of the original field notes.~~

~~_____~~
~~(Date)~~

~~_____~~
~~(Chief Cadastral Surveyor of Arizona)~~