

ORIGINAL

**UNITED STATES  
DEPARTMENT OF THE INTERIOR  
BUREAU OF LAND MANAGEMENT**

FIELD NOTES  
OF THE  
DEPENDENT RESURVEY OF THE SOUTH,  
WEST AND NORTH BOUNDARIES,  
AND THE SUBDIVISIONAL LINES,  
AND THE SUBDIVISION OF ALL SECTIONS,  
**TOWNSHIP 23 NORTH, RANGE 18 EAST,**  
OF THE GILA AND SALT RIVER MERIDIAN,  
IN THE STATE OF ARIZONA.

**EXECUTED BY**

**Gordon R. Bubel and Joel A. Emert, Cadastral Surveyors**

Under Special Instructions dated December 15, 2006, approved December 15, 2006, which provided for the surveys included under Group No. 1015, and assignment instructions dated December 15, 2006.

**Survey commenced December 18, 2006**

**Survey completed May 2, 2007**

**INDEX DIAGRAM**

TOWNSHIP 23 NORTH                      RANGE 18 EAST  
 GILA AND SALT RIVER MERIDIAN, ARIZONA

14	19 6 63	19 5 52	18 4 44	17 3 37	16 2 28	15 1
13	63 7 61	62 8 50	51 9 43	43 10 35	36 11 27	28 12
12	61 18 59	60 17 49	50 16 41	42 15 33	35 14 25	26 13
12	59 19 57	58 20 47	48 21 40	41 22 32	33 23 23	25 24
11	56 30 54	56 29 46	47 28 38	39 27 30	31 26 22	23 25
10	54 31 52	53 32 45	45 33 37	38 34 29	30 35 20	21 36
	8	7	7	6	5	4

## T. 23 N., R. 18 E., Gila and Salt River Meridian, Arizona

## CHAINS

The following field notes describe the dependent resurvey of the south, west and north boundaries, the subdivisional lines, and the subdivision of all sections, Township 23 North, Range 18 East, Gila and Salt River Meridian, Arizona.

The history of surveys pertaining to this survey is as follows:

O. D. Wheeler surveyed the west boundary in 1882. A.P. Johnson surveyed the south, east, north and subdivisional lines in 1883. Geoffrey A. Graham resurveyed the east boundary in 2004.

The survey was executed in accordance with the specifications as set forth in the Manual of Instructions for the Survey of the Public Lands of the United States, 1973, and the Special Instructions dated December 15, 2006, for Group No. 1015, Arizona.

The true meridian direction and length of all lines were determined by real time kinematic global positioning system observations using Trimble Navigation 5700 model receivers.

Preliminary to the resurvey, the lines of the prior surveys were retraced and search was made for all corners and other calls of record. Identified corners were remonumented in their original positions. Lost corners were reestablished and remonumented at proportionate positions based on the official record. The retracement data were thoroughly verified and only the true line field notes are given herein.

Geodetic control was derived from Global Positioning System (GPS) static observations post processed by National Geodetic Survey, Online Positioning User Service (OPUS), utilizing Continuously Operating Reference Stations (CORS) FLAGSTAFF 1, DUECECLUBSAZ2005 AND SPIDERROCKAZ2005. The NAD 83 (CORS96) (EPOCH:2002), geographic position of the southeast township corner, is as follows:

Latitude: 35°20'39.79" N.                      Longitude: 110°22'16.04" W.

The mean magnetic declination is 11 1/4° E.

---

**Dependent Resurvey of the South Boundary,  
T. 23 N., R. 18 E., Gila and Salt River Meridian, Arizona**

CHAINS

Restoring the survey executed by  
A. P. Johnson, in 1883

---

Beginning at the cor. of Tps. 22 and 23 N., Rs. 18 and 19 E., monumented with a stainless steel post, 2 1/2 ins. diam., firmly set, projecting 6 ins. above the ground, in a mound of stone, 3 ft. base, to top, with brass cap mkd.

	T 23 N	
R 18 E		R 19 E
S 36		S 31
S 1		S 6
	T 22 N	

2004

Add the marks 2007 to the brass cap.

A steel fence post is set alongside and E. of the cor.

---

S. 89°56' W., bet. secs. 1 and 36.

Over rolling land through bunchgrass.

39.43 Point for the 1/4 sec. cor. of secs. 1 and 36, at proportionate dist., there is no remaining evidence of the orig. cor.

Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, in a collar of stone, with brass cap mkd.

T 23 N	R 18 E
S 36	—
1/4	—
S 1	—
T 22 N	

2007

Deposit a magnet, in a white plastic case, at the base of the stainless steel post.

Set steel fence post alongside and N. of the cor.

78.86 Point for the cor. of secs. 1, 2, 35 and 36, at proportionate dist., there is no remaining evidence of the orig. cor.

Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.

**Dependent Resurvey of the South Boundary,  
T. 23 N., R. 18 E., Gila and Salt River Meridian, Arizona**

CHAINS											
	<table style="margin: auto;"> <tr><td>T 23 N</td><td>R 18 E</td></tr> <tr><td>S 35</td><td>S 36</td></tr> <tr><td>S 2</td><td>S 1</td></tr> <tr><td colspan="2">T 22 N</td></tr> </table> <p style="text-align: center;">2007</p> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p> <p>Set a steel fence post alongside and N. of the cor.</p> <hr/> <p>S. 89°56' W., bet. secs. 2 and 35.</p> <p>Over broken land, through bunchgrass.</p>	T 23 N	R 18 E	S 35	S 36	S 2	S 1	T 22 N			
T 23 N	R 18 E										
S 35	S 36										
S 2	S 1										
T 22 N											
39.43	<p>Point for the 1/4 sec. cor. of secs. 2 and 35, at proportionate dist., there is no remaining evidence of the orig. cor.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 22 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;"> <table style="margin: auto;"> <tr><td>T 23 N</td><td>R 18 E</td></tr> <tr><td colspan="2">S 35</td></tr> <tr><td>1/4</td><td>—</td></tr> <tr><td colspan="2">S 2</td></tr> <tr><td colspan="2">T 22 N</td></tr> </table> <p style="text-align: center;">2007</p> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p> <p>Set a steel fence post alongside and N. of the cor.</p> </p>	T 23 N	R 18 E	S 35		1/4	—	S 2		T 22 N	
T 23 N	R 18 E										
S 35											
1/4	—										
S 2											
T 22 N											
78.86	<p>Point for the cor. of secs. 2, 3, 34 and 35, at proportionate dist., there is no remaining evidence of the orig. cor.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 17 ins. in the ground, in a mound of stone, 3 ft. base, to top, with brass cap mkd.</p> <p style="text-align: center;"> <table style="margin: auto;"> <tr><td>T 23 N</td><td>R 18 E</td></tr> <tr><td>S 34</td><td>S 35</td></tr> <tr><td>S 3</td><td>S 2</td></tr> <tr><td colspan="2">T 22 N</td></tr> </table> <p style="text-align: center;">2007</p> </p>	T 23 N	R 18 E	S 34	S 35	S 3	S 2	T 22 N			
T 23 N	R 18 E										
S 34	S 35										
S 3	S 2										
T 22 N											

**Dependent Resurvey of the South Boundary,  
T. 23 N., R. 18 E., Gila and Salt River Meridian, Arizona**

CHAINS	
39.43	<p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p> <hr/> <p>S. 89°56' W., bet. secs. 3 and 34.</p> <p>The 1/4 sec. cor. of secs. 3 and 34, determined from the remains of the orig. accessory, a mound of stone, 3 ft. diam., 1/2 ft. high.</p> <p>At the corner point</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 12 ins. in the ground, in a supporting mound of stone, 4 ft. base to top, with brass cap mkd.</p> <div style="text-align: center;"> <p>T 23 N R 18 E S 34 1/4 ——— S 3 T 22 N</p> <p>2007</p> </div> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p> <p>Incorporate the accessory mound of stone into the supporting mound of stone.</p> <hr/> <p>N. 89°38' W., beginning new measurement.</p> <p>Over sloping terrain through bunchgrass.</p>
40.00	<p>Point for the cor. of secs. 3, 4, 33 and 34, at proportionate dist., there is no remaining evidence of the orig. cor.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 diam., 24 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center;"> <p>T 23 N R 18 E S 33   S 34 S 4   S 3 T 22 N</p> <p>2007</p> </div> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p> <p>Set a steel fence post alongside and N. of the cor.</p> <hr/>

**Dependent Resurvey of the South Boundary,  
T. 23 N., R. 18 E., Gila and Salt River Meridian, Arizona**

CHAINS	
	N. 89°38' W., bet. secs. 4 and 33.  Over rolling land through grass and sage.
1.96	Center of pavement, Arizona State Highway No. 87, asphalt surfaced, 28 ft. wide, bears S. 1°47' E. and N. 1°47' W.
40.00	Point for the 1/4 sec. cor. of secs. 4 and 33, at proportionate dist., there is no remaining evidence of the orig. cor.  Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 22 ins. in the ground, with brass cap mkd.  <div style="text-align: center;">           T 23 N R 18 E                  S 33              1/4 ———                  S 4              T 22 N             2007         </div> Deposit a magnet, in a white plastic case, at the base of the stainless steel post.  Set a steel fence post alongside and N. of the cor.  Cor. is located 1.14 chs. N. of a track road, bears S. 60° E. and N. 60° W.
80.00	Point for the cor. of secs. 4, 5, 32 and 33, at proportionate dist., there is no remaining evidence of the orig. cor.  Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.  <div style="text-align: center;">           T 23 N R 18 E            S 32   S 33            ———   ———            S 5   S 4            T 22 N             2007         </div> Deposit a magnet, in a white plastic case, at the base of the stainless steel post.  Cor. is located 80 lks. S. of the left cut bank of Coyote Wash, 10 ft. high, bears N. 60° E. and S. 60° W.  Set a steel fence post alongside and N. of the cor.  <hr style="width: 50%; margin-left: 0;"/> N. 89°38' W., bet. secs. 5 and 32.

**Dependent Resurvey of the South Boundary,  
T. 23 N., R. 18 E., Gila and Salt River Meridian, Arizona**

CHAINS	
	Over rolling and broken land.
16.07	Midpoint bet. two, El Paso Natural Gas Co., underground gas lines, bears S. 13°16' E. and N. 13°16' W.
40.00	Point for the 1/4 sec. cor. of secs. 5 and 32, at proportionate dist., there is no remaining evidence of the orig. cor.  Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.  <div style="text-align: center;">           T 23 N R 18 E                      S 32            1/4 ———                      S 5            T 22 N             2007         </div>
	Deposit a magnet, in a white plastic case, at the base of the stainless steel post.
	Set a steel fence post alongside and N. of the cor.
80.00	Point for the cor. of secs. 5, 6, 31 and 32, at proportionate dist., there is no remaining evidence of the orig. cor.  Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 21 ins. in the ground, in a collar of stone, with brass cap mkd.  <div style="text-align: center;">           T 23 N R 18 E            S 31   S 32            ———   ———            S 6   S 5            T 22 N             2007         </div>
	Deposit a magnet, in a white plastic case, at the base of the stainless steel post.
	Set a steel fence post alongside and N. of the cor.
	_____
	N. 89°38' W., bet. secs. 6 and 31.
	Over rolling land through grass and sage.
40.00	Point for the 1/4 sec. cor. of secs. 6 and 31, at proportionate dist., there is no remaining evidence of the orig. cor.  Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, in a collar of stone, with brass cap mkd.



**Dependent Resurvey of the South Boundary,  
T. 23 N., R. 18 E., Gila and Salt River Meridian, Arizona**

CHAINS	
	T 23 N R 18 E S 31 1/4 ——— S 6 T 22 N  2007
	Deposit a magnet, in a white plastic case, at the base of the stainless steel post.
	Set a steel fence post alongside and N. of the cor.
	From this cor. point, the well head at Coyote Spring bears, S. 53°09' E., 8.63 chs. dist., an iron pipe, 8 1/2 ins. diam., projecting 15 ins. above the ground.
74.80	Graded road, 25 ft. wide, bears N. 11° E. and S. 11° W.
77.00	The cor. of Tps. 22 and 23 N., Rs. 17 and 18 E., monumented with a basalt stone, 16 X 9 X 6 ins., firmly set, projecting 10 ins. above ground, in a scattered mound of stone, mkd. with 6 grooves on N., E., S. and W. faces. Found set alongside the mkd. stone, a basalt stone, (12 X 11 X 4 ins., mkd. A 6 on the W. face), and a rebar, 18 ins. long, 5/8 in. diam., set 17 ins. in the ground.
	At the corner point
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 22 ins. in the ground, in a collar of stone, with brass cap mkd.
	T 23 N R 17 E   R 18 E S 36   S 31 ———— S 1   S 6 T 22 N
	2006
	Deposit a magnet, in a white plastic case, at the base, and the rebar inside, and the mkd. stones alongside of the stainless steel post.
	Set a steel fence post alongside and W. of the cor.

Dependent Resurvey of the West Boundary,  
T. 23 N., R. 18 E., Gila and Salt River Meridian, Arizona

CHAINS									
	Restoring the survey executed by O. D. Wheeler, in 1882 <hr/>								
	From the cor. of Tps. 22 and 23 N., Rs. 17 and 18 E., hereinbefore described.  N. 0°02' E., bet. secs. 31 and 36, on the W. bdy. of the Tp.  Over rolling land through bunchgrass and sage.								
21.63	Center of pavement, BIA Route N15, asphalt surfaced, 25 ft. wide, bears N. 80°25' E. and S. 80°25' W.								
39.95	Point for the 1/4 sec. cor. of secs. 31 and 36, at proportionate dist., there is no remaining evidence of the orig. cor.  Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 22 ins. in the ground, with brass cap mkd.								
	<table border="0"> <tr><td colspan="2">T 23 N</td></tr> <tr><td colspan="2">1/4</td></tr> <tr><td>R 17 E</td><td>  R 18 E</td></tr> <tr><td>S 36</td><td>  S 31</td></tr> </table>	T 23 N		1/4		R 17 E	R 18 E	S 36	S 31
T 23 N									
1/4									
R 17 E	R 18 E								
S 36	S 31								
	2007								
	Deposit a magnet, in a white plastic case, at the base of the stainless steel post.  Set a steel fence post alongside and W. of the cor.								
46.35	Midpoint bet. two, Transwestern Pipeline Co., underground gas lines, bears N. 76°31' E. and S. 76°31' W.								
59.94	Midpoint bet. four, El Paso Natural Gas Co., underground gas lines, bears N. 76°15' E. and S. 76°15' W.								
79.90	Point for the cor. of secs. 25, 30, 31 and 36, at proportionate dist., there is no remaining evidence of the orig. cor.  Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 20 ins. in the ground, in a mound of stone, 3 ft. base, to top, with brass cap mkd.								
	<table border="0"> <tr><td colspan="2">T 23 N</td></tr> <tr><td>R 17 E</td><td>  R 18 E</td></tr> <tr><td>S 25</td><td>  S 30</td></tr> <tr><td>S 36</td><td>  S 31</td></tr> </table>	T 23 N		R 17 E	R 18 E	S 25	S 30	S 36	S 31
T 23 N									
R 17 E	R 18 E								
S 25	S 30								
S 36	S 31								
	2007								

**Dependent Resurvey of the West Boundary,  
T. 23 N., R. 18 E., Gila and Salt River Meridian, Arizona**

CHAINS	
	<p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p> <hr/> <p>N. 0°02' E., bet. secs. 25 and 30.</p> <p>Over rolling land through bunchgrass and sage along the westerly slope of Pyramid Butte.</p>
39.95	<p>Point for the 1/4 sec. cor. of secs. 25 and 30, at proportionate dist., there is no remaining evidence of the orig. cor.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 20 ins. in the ground, in a mound of stone, 3 ft. base, to top, with brass cap mkd.</p> <div style="text-align: center;"> <p>T 23 N 1/4 R 17 E   R 18 E S 25   S 30</p> <p>2007</p> </div> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p>
59.925	<p>Point for the N. 1/16 sec. cor. of secs. 25 and 30.</p> <p>Not monumented.</p>
79.90	<p>Point for the cor. of secs. 19, 24, 25 and 30, at proportionate dist., there is no remaining evidence of the orig. cor.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 23 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center;"> <p>T 23 N R 17 E   R 18 E S 24   S 19 <hr/>S 25   S 30</p> <p>2007</p> </div> <p>from which</p> <p style="text-align: center;">The most northeasterly cor. of a cinder block Hogan, bears S. 26 1/2° W., 85 lks. dist.</p> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p> <p>Set a steel fence post alongside and W. of the cor.</p> <hr/>

Dependent Resurvey of the West Boundary,  
T. 23 N., R. 18 E., Gila and Salt River Meridian, Arizona

CHAINS	
	N. 0°02' E., bet. secs. 19 and 24.
	Over rolling and broken land.
5.20	Graded dirt road, 25 ft. wide, bears S. 60° E. and N. 60° W.
20.32	From this point, the top of a well head, 7 ins. diam., projecting 18 ins. above the ground, at Chandler Springs, bears E., 1.98 chs. dist.
39.95	Point for the 1/4 sec. cor. of secs. 19 and 24, at proportionate dist., there is no remaining evidence of the orig. cor.
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 25 ins. in the ground, with brass cap mkd.
	<div style="text-align: center;"> <p>T 23 N 1/4 R 17 E   R 18 E S 24   S 19</p> </div>
	2007
	Deposit a magnet, in a white plastic case, at the base of the stainless steel post.
	Raise a mound of stone, 3 1/2 ft. base, 1 1/2 ft. high, W. of cor.
79.90	Point for the cor. of secs. 13, 18, 19 and 24, at proportionate dist., there is no remaining evidence of the orig. cor.
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with brass cap mkd.
	<div style="text-align: center;"> <p>T 23 N R 17 E   R 18 E S 13   S 18 S 24   S 19</p> </div>
	2007
	Deposit a magnet, in a white plastic case, at the base of the stainless steel post.
	Set a steel fence post alongside and W. of the cor.
	<hr/> <p>N. 0°02' E., bet. secs. 13 and 18.</p>
	Over nearly level land, through bunchgrass and sage.

**Dependent Resurvey of the West Boundary,  
T. 23 N., R. 18 E., Gila and Salt River Meridian, Arizona**

CHAINS	
39.95	<p>Point for the 1/4 sec. cor. of secs. 13 and 18, at proportionate dist., there is no remaining evidence of the orig. cor.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center;"> <p>T 23 N 1/4 R 17 E   R 18 E S 13   S 18</p> <p>2007</p> </div> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p> <p>Set a steel fence post alongside and W. of the cor.</p>
76.60	Graded road, 25 ft. wide, bears N. 60° E. and S. 60° W.
79.85	Natural water line, bears N. 66°10' E. and S. 66°10' W.
79.90	<p>Point for the cor. of secs. 7, 12, 13 and 18, at proportionate dist., there is no remaining evidence of the orig. cor.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center;"> <p>T 23 N R 17 E   R 18 E S 12   S 7 S 13   S 18</p> <p>2007</p> </div> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p> <p>Set a steel fence post alongside and W. of the cor.</p> <hr/> <p>N. 0°02' E., bet. secs. 7 and 12.</p> <p>Over broken level land, through bunchgrass and sage.</p>
39.95	<p>Point for the 1/4 sec. cor. of secs. 7 and 12, at proportionate dist., there is no remaining evidence of the orig. cor.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 21 ins. in the ground, in a mound of stone, 3 1/2 ft. base, to top, with brass cap mkd.</p>

**Dependent Resurvey of the West Boundary,  
T. 23 N., R. 18 E., Gila and Salt River Meridian, Arizona**

CHAINS	
79.90	<p style="text-align: center;">T 23 N 1/4 R 17 E   R 18 E S 12   S 7</p> <p style="text-align: center;">2007</p> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p> <p>The cor. of secs. 1, 6, 7 and 12, monumented with a basalt stone, 15 x 14 x 8 ins., mkd. with 5 grooves on a face, laying loose in an embedded accessory mound of stone, 4 ft. base, 1 ft. high.</p> <p>At the corner point</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p>
40.05	<p style="text-align: center;">T 23 N R 17 E   R 18 E S 1   S 6 <hr style="width: 50%; margin: auto;"/>S 12   S 7</p> <p style="text-align: center;">2007</p> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p> <p>Rebuild the accessory mound of stone, 4 ft. base, 2 ft. high, W. of the cor., and incorporate the mkd. stone into the accessory mound.</p> <hr style="width: 80%; margin: 10px auto;"/> <p>N. 0°10' E., bet. secs. 1 and 6.</p> <p>Over rolling and broken land.</p> <p>Point for the 1/4 sec. cor. of secs. 1 and 6, at proportionate dist., there is no remaining evidence of the orig. cor.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, in a collar of stone, with brass cap mkd.</p>
	<p style="text-align: center;">T 23 N 1/4 R 17 E   R 18 E S 1   S 6</p> <p style="text-align: center;">2007</p>

**Dependent Resurvey of the West Boundary,  
T. 23 N., R. 18 E., Gila and Salt River Meridian, Arizona**

CHAINS	
80.10	<p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p> <p>The cor. of Tps. 23 and 24 N., Rs. 17 and 18 E., monumented with a stainless steel post, 2 1/2 ins. diam., firmly set, projecting 3 ins. above ground, with a mound of stone, 3 1/2 ft. base, 1 1/2 ft. high, to the S., with brass cap mkd. T24N R18E R18E S36 S31 S1 S6 T23N 2004.</p> <p>Add the marks 2007 to the brass cap.</p> <p>This cor. was remonumented in 2004 by Geoffery A. Graham, Cadastral Surveyor, during the dependent resurvey of T. 23 N., R. 19 E.</p> <hr/> <p style="text-align: center;"><b>Dependent Resurvey of the North Boundary, T. 23 N., R. 18 E., Gila and Salt River Meridian, Arizona</b></p> <hr/> <p style="text-align: center;">Restoring the survey executed by A. P. Johnson, in 1883</p> <hr/> <p>From the cor. of Tps. 23 and 24 N., Rs 18 and 19 E., monumented with a stainless steel post, 2 1/2 ins. diam., firmly set, projecting 4 ins. above ground, in a collar of stone, with a steel fence post set N. of cor., with brass cap mkd. T24N R18E R19E S36 S31 S1 S6 T23N 2004.</p> <p>Add the marks 2007 to the brass cap.</p> <p>N. 89°49' W., bet. secs. 1 and 36, on the N. bdy. of the Tp.</p> <p>Ascending over the northerly foothills of Shonto Butte.</p>
39.35	<p>Point for the 1/4 sec. cor. of secs. 1 and 36, at proportionate dist., there is no remaining evidence of the orig. cor.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 20 ins. in the ground, in a mound of stone, 3 ft. base, to top, with brass cap mkd.</p> <p style="text-align: center;">T 24 N R 18 E S 36 1/4 ——— S 1 T 23 N</p> <p style="text-align: center;">2007</p> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p>

**Dependent Resurvey of the North Boundary,  
T. 23 N., R. 18 E., Gila and Salt River Meridian, Arizona**

CHAINS	
78.70	<p>The cor. of secs. 1, 2, 35 and 36, remonumented in 2004 by Geoffery A. Graham, Cadastral surveyor, during the dependent resurvey of T. 23 N., R. 19 E., monumented with a stainless steel post, 2 1/2 ins. diam., firmly set, projecting 5 ins. above ground, in a mound of stone, 3 ft. base, to top, with brass cap mkd. T24N R18E S35 S36 S2 S1 T23N 2004.</p> <p>Add the marks 2007 to the brass cap and set a steel fence post alongside and W. of the cor.</p> <hr/> <p>S. 89°10' W., bet. secs. 2 and 35.</p> <p>Over foothills of Shonto Butte, through bunchgrass and juniper timber.</p>
39.64	<p>The 1/4 sec. cor. of secs. 2 and 35, determined from the remains of the orig. accessory, a mound of stone, 4 ft. diam., 1/2 ft. high, with a basalt stone, 15 x 10 x 6 ins., set 1 in. in the ground, mkd. 1/4 A on E. face, set alongside and to the E.</p> <p>At the corner point</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 14 ins. in the ground, to bedrock, in a mound of stone, 3 ft. base, to top, with brass cap mkd.</p> <div style="text-align: center;"> <p>T 24 N R 18 E S 35 1/4 ——— S 2 T 23 N</p> <p>2007</p> </div> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post, and the mkd. stone alongside.</p> <p>Set a steel fence post alongside and N. of the cor.</p> <p>Orig. accessory mound of stone incorporated into the mound of stone around stainless steel post.</p> <hr/> <p>N. 89°50' W., beginning new measurement.</p>
40.82	<p>Point for the cor. of secs. 2, 3, 34 and 35, at proportionate dist., there is no remaining evidence of the orig. cor.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 20 ins. in the ground, in a mound of stone, 3 1/2 ft. base, to top, with brass cap mkd.</p>



**Dependent Resurvey of the North Boundary,  
T. 23 N., R. 18 E., Gila and Salt River Meridian, Arizona**

CHAINS									
	<table style="margin: auto;"> <tr> <td>T 24 N</td> <td>R 18 E</td> </tr> <tr> <td>S 34</td> <td>S 35</td> </tr> <tr> <td>S 3</td> <td>S 2</td> </tr> <tr> <td colspan="2" style="text-align: center;">T 23 N</td> </tr> </table>	T 24 N	R 18 E	S 34	S 35	S 3	S 2	T 23 N	
T 24 N	R 18 E								
S 34	S 35								
S 3	S 2								
T 23 N									
	2007								
	Deposit a magnet, in a white plastic case, at the base of the stainless steel post.								
	Set a steel fence post alongside and W. of the cor.								
	<hr/>								
	N. 89°50' W., bet. secs. 3 and 34.								
	Over nearly level land, through bunchgrass and sage.								
7.85	Barbed wire fence, bears N. and S.								
17.85	Barbed wire fence, bears N. and S.								
40.82	Point for the 1/4 sec. cor. of secs. 3 and 34, at proportionate dist., there is no remaining evidence of the orig. cor.								
	Set a railroad spike, flush with the surface of a graded road.								
	from which								
	A stainless steel post, 28 ins. long, 2 1/2 ins. diam., set 26 ins. in the ground for a reference monument, bears S. 20°00' E., 33.0 ft. dist. with brass cap mkd. RM T23N R18E 1/4 S3 33.0 FT TO COR. 2007 and an arrow pointing to the cor. Deposit a magnet, in a white plastic case, at the base of the stainless steel post.								
	A stainless steel post, 28 ins. long, 2 1/2 ins. diam., set 27 ins. in the ground for a reference monument, bears S. 70°00' W., 33.0 ft. dist. with brass cap mkd. RM T23N R18E 1/4 S3 33.0 FT TO COR. 2007 and an arrow pointing to the cor. Deposit a magnet, in a white plastic case, at the base of the stainless steel post.								
	Cor. is located in a graded road, 8 ft. wide, bears S. 50° E. and N. 50° W.								
41.84	Underground waterline, bears S. 1°46' E. and N. 1°46' W.								
81.64	Point for the cor. of secs. 3, 4, 33 and 34, at proportionate dist., there is no remaining evidence of the orig. cor.								
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 20 ins. in the ground, in a mound of stone, 3 ft. base, to top, with brass cap mkd.								

Dependent Resurvey of the North Boundary,  
T. 23 N., R. 18 E., Gila and Salt River Meridian, Arizona

CHAINS	
	<p style="text-align: center;">T 24 N R 18 E S 33   S 34 S 4   S 3 T 23 N</p> <p style="text-align: center;">2007</p> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p> <hr/> <p>N. 89°50' W., bet. secs. 4 and 33.</p> <p>Over nearly level land</p>
6.45	Graded dirt road, 20 ft. wide, bears N. 60° E. and S. 60° W.
13.44	Center of pavement, Arizona State Highway No. 87, asphalt surfaced, 28 ft. wide, bears N. 4° 46' E. and S. 4° 46' W.
40.82	Point for the 1/4 sec. cor. of secs. 4 and 33, at proportionate dist., there is no remaining evidence of the orig. cor.
	<p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 22 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T 24 N R 18 E S 33 1/4 ——— S 4 T 23 N</p> <p style="text-align: center;">2007</p> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p> <p>Set a steel fence post westerly of the cor.</p>
81.64	Point for the cor. of secs. 4, 5, 32 and 33, at proportionate dist., there is no remaining evidence of the orig. cor.
	<p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 21 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T 24 N R 18 E S 32   S 33 S 5   S 4 T 23 N</p> <p style="text-align: center;">2007</p>

**Dependent Resurvey of the North Boundary,  
T. 23 N., R. 18 E., Gila and Salt River Meridian, Arizona**

CHAINS	
	<p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p> <p>Drive an aluminum rod, guard post, 36 ins. long, 3/4 in. diam., 18 ins. in the ground, W. of the cor.</p> <hr/> <p>N. 89°50' W., bet. secs. 5 and 32.</p> <p>Over gently rolling land, through sage and bunchgrass.</p>
40.82	<p>Point for the 1/4 sec. cor. of secs. 5 and 32, at proportionate dist., there is no remaining evidence of the orig. cor.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 20 ins. in the ground, in a mound of stone, 3 ft. base, to top, with brass cap mkd.</p> <div style="text-align: center;"> <p>T 24 N R 18 E S 32 1/4 ——— S 5 T 23 N</p> <p>2007</p> </div>
	<p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p>
81.64	<p>Point for the cor. of secs. 5, 6, 31 and 32, at proportionate dist., there is no remaining evidence of the orig. cor.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 23 ins. in the ground, in a collar of stone, with brass cap mkd.</p> <div style="text-align: center;"> <p>T 24 N R 18 E S 31   S 32 S 6   S 5 T 23 N</p> <p>2007</p> </div>
	<p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p> <hr/> <p>N. 89°50' W., bet. secs. 6 and 31.</p> <p>Ascending over broken and rolling land, through bunchgrass.</p>
40.82	<p>Point for the 1/4 sec. cor. of secs. 6 and 31, at proportionate dist., there is no remaining evidence of the orig. cor.</p>

**Dependent Resurvey of the North Boundary,  
T. 23 N., R. 18 E., Gila and Salt River Meridian, Arizona**

CHAINS	
	<p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 22 ins. in the ground, in a collar of stone, with brass cap mkd.</p> <p style="text-align: center;">T 24 N R 18 E S 31 1/4 ——— S 6 T 23 N</p> <p style="text-align: center;">2007</p> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p>
78.12	<p>The cor. of Tps. 23 and 24 N., Rs. 17 and 18 E., hereinbefore described.</p> <hr/> <p style="text-align: center;"><b>Dependent Resurvey of the Subdivisional Lines, T. 23 N., R. 18 E., Gila and Salt River Meridian, Arizona</b></p> <hr/> <p style="text-align: center;">Restoring the survey executed by A. P. Johnson, in 1883</p> <hr/> <p>From the cor. of secs. 1, 2, 35 and 36, on the S. bdy. of the Tp., hereinbefore described.</p> <p>N. 0°02' E., bet. secs. 35 and 36.</p> <p>Descending over broken land.</p>
40.04	<p>Point for the 1/4 sec. cor. of secs. 35 and 36, at proportionate dist., there is no remaining evidence of the orig. cor.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T 23 N R 18 E 1/4 S 35   S 36</p> <p style="text-align: center;">2007</p> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p> <p>Raise a mound of stone, 2 ft. base, 1 1/2 ft. high, W. of cor.</p> <p>Set a steel fence post, alongside and N. of the cor.</p>

**Dependent Resurvey of the Subdivisional Lines,  
T. 23 N., R. 18 E., Gila and Salt River Meridian, Arizona**

CHAINS									
80.08	<p>Cor. is located 22 lks. S. of a dry wash, 3 ft. wide, 1/2 ft. deep, drains N. 50° E.</p> <p>True point for the cor. of secs. 25, 26, 35 and 36; at proportionate dist., there is no remaining evidence of the orig. cor., falls in the bed of a wash, (130 ft. wide, 2 ft. deep, drains S. 80° W.), where it is impracticable to establish a permanent monument.</p> <p>From this true point, the point selected for a witness cor. to the cor. of secs. 25, 26, 35 and 36, bears N. 45°00' W., 2.00 chs. dist.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 25 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center;"> <p>WC</p> <table style="margin: auto;"> <tr> <td>T 23 N</td> <td>R 18 E</td> </tr> <tr> <td>S 26</td> <td>S 25</td> </tr> <tr> <td>S 35</td> <td>S 36</td> </tr> </table> <p style="text-align: center;">↙</p> <p>2007</p> </div> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p> <p>Set a steel fence post, alongside and N. of cor.</p> <hr/> <p>From the cor. of secs. 25, 30, 31 and 36, on the E. bdy. of the Tp., monumented with a stainless steel post, 2 1/2 ins. diam., firmly set, projecting 4 ins. above ground, with brass cap mkd. T23N R18E R19E S25 S30 S36 S31 2004. Add the marks 2007 to the brass cap.</p> <p>A steel fence post, is set nearby and N. of the cor.</p> <p>N. 89°58' W., bet. secs. 25 and 36.</p> <p>Over rolling land through grass and sage.</p>	T 23 N	R 18 E	S 26	S 25	S 35	S 36		
T 23 N	R 18 E								
S 26	S 25								
S 35	S 36								
39.54	<p>Point for the 1/4 sec. cor. of secs. 25 and 36, at proportionate dist., there is no remaining evidence of the orig. cor.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center;"> <table style="margin: auto;"> <tr> <td>T 23 N</td> <td>R 18 E</td> </tr> <tr> <td></td> <td>S 25</td> </tr> <tr> <td>1/4</td> <td>—</td> </tr> <tr> <td></td> <td>S 36</td> </tr> </table> <p>2007</p> </div>	T 23 N	R 18 E		S 25	1/4	—		S 36
T 23 N	R 18 E								
	S 25								
1/4	—								
	S 36								

**Dependent Resurvey of the Subdivisional Lines,  
T. 23 N., R. 18 E., Gila and Salt River Meridian, Arizona**

CHAINS	
79.09	<p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p> <p>Set a steel fence post, alongside and N. of the cor.</p> <p>The true point for the cor. of secs. 25, 26, 35 and 36.</p> <hr/> <p>N. 0°13' E., bet. secs. 25 and 26.</p> <p>Over rolling land through sage and grass.</p>
40.04	<p>Point for the 1/4 sec. cor. of secs. 25 and 26, at proportionate dist., there is no remaining evidence of the orig. cor.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 27 ins. in the ground, over a steel fence post, (72 ins. long, driven 72 ins. in the ground), with brass cap mkd.</p> <p style="text-align: center;">T 23 N R 18 E 1/4 S 26   S 25</p> <p style="text-align: center;">2007</p>
80.08	<p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p> <p>Set a steel fence post, alongside and N. of the cor.</p> <p>Cor. is located 20 lks. N. of the right bank of Coyote Wash, 100 ft. wide, 3 ft. deep, drains N. 65° W.</p> <p>Point for the cor. of secs. 23, 24, 25 and 26, at proportionate dist., there is no remaining evidence of the orig. cor.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 25 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T 23 N R 18 E S 23   S 24 S 26   S 25</p> <p style="text-align: center;">2007</p> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p> <hr/>

**Dependent Resurvey of the Subdivisional Lines,  
T. 23 N., R. 18 E., Gila and Salt River Meridian, Arizona**

CHAINS	
	<p>From the cor. of secs. 19, 24, 25 and 30, on the E. bdy. of the Tp., monumented with a stainless steel post, 2 1/2 ins. diam., firmly set, projecting 3 ins. above ground, with brass cap mkd. T23N R18E R19E S24 S19 S25 S30 2004, with a mound of stone, 2 1/2 ft. base, 1 1/2 ft. high to the W. Add the marks 2007 to the brass cap.</p> <p>A steel fence post, is set nearby and N. of the cor.</p> <p>S. 89°57' W., bet. secs. 24 and 25.</p> <p>Over rolling land through grass and sage.</p>
39.55	<p>Point for the 1/4 sec. cor. of secs. 24 and 25, at proportionate dist., there is no remaining evidence of the orig. cor.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 25 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center;"> <p>T 23 N R 18 E S 24 1/4 ——— S 25</p> <p>2007</p> </div> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p> <p>Raise a mound of stone, 1 1/2 ft. base, 1 1/2 ft. high, N. of cor.</p> <p>Cor. is located 1.12 chs. S. of a wash, 17 ft. wide, 2 ft. deep, drains N. 65° W.</p> <p>Cor. is located 1.36 chs. E. of this same wash, drains S. 50° W.</p>
79.10	<p>The cor. of secs. 23, 24, 25 and 26.</p> <hr/> <p>N. 0°28' E., bet. secs. 23 and 24.</p> <p>Over nearly level land, through grass and sage.</p>
17.41	<p>Midpoint bet. two, Transwestern Pipeline Co., underground gas lines, bears N. 70°13' E. and S. 70°13' W.</p>
40.04	<p>Point for the 1/4 sec. cor. of secs. 23 and 24, at proportionate dist., there is no remaining evidence of the orig. cor.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 28 ins. in the ground, with brass cap mkd.</p>

**Dependent Resurvey of the Subdivisional Lines,  
T. 23 N., R. 18 E., Gila and Salt River Meridian, Arizona**

CHAINS	
	T 23 N R 18 E 1/4 S 23   S 24  2007
	Deposit a magnet, in a white plastic case, at the base of the stainless steel post.  Cor. is located in S. drainage ditch of BIA Route N15.
40.83	Center line of BIA Route N15, a paved two lane road, 28 ft. wide, on the arc of a circular curve to the right, having a central angle of 2°57' and a radius of 22,853.6 ft.  From this point, the calculated P.O.T., bears N. 71°09' E., 17.12 chs. dist.  From this same point, the calculated P.O.C., bears S. 69°49' W., 0.685 chs. dist.
44.59	Midpoint bet. four, El Paso Natural Gas Co., underground gas lines, bears N. 69°36' E. and S. 69°36' W.
80.08	Point for the cor. of secs. 13, 14, 23 and 24, at proportionate dist., there is no remaining evidence of the orig. cor.  Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with brass cap mkd.  <div style="text-align: center;">             T 23 N R 18 E              S 14   S 13              ---              S 23   S 24               2007           </div> Deposit a magnet, in a white plastic case, at the base of the stainless steel post.  Set a steel fence post, alongside and W. of the cor.  From this cor. point, a sandstone, 10 x 6 x 3 ins., lying loose, in a mound of stone, (3 ft. base, 1 ft. high), mkd. S14A on a face, bears N. 9°22' W., 1.81 chs. dist. This monument is irreconcilable with found orig. cors., and is not utilized in the course of this resurvey.



**Dependent Resurvey of the Subdivisional Lines,  
T. 23 N., R. 18 E., Gila and Salt River Meridian, Arizona**

CHAINS	
	<p>From the cor. of secs. 13, 18, 19 and 24, on the E. bdy. of the Tp., monumented with a stainless steel post, 2 1/2 ins. diam., firmly set, projecting 5 ins. above ground, with brass cap mkd. T23N R18E R19E S13 S18 S24 S19 2004. Add the marks 2007 to the brass cap.</p> <p>A steel fence post, is set nearby and N. of the cor.</p> <p>S. 89°34' W., bet. secs. 13 and 24.</p> <p>Over nearly level land and grass.</p>
39.82	<p>Point for the 1/4 sec. cor. of secs. 13 and 24, at proportionate dist., there is no remaining evidence of the orig. cor.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 27 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T 23 N R 18 E S 13 1/4 ——— S 24</p> <p style="text-align: center;">2007</p> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p>
79.65	<p>The cor. of secs. 13, 14, 23 and 24.</p> <hr style="width: 50%; margin-left: 0;"/> <p>N. 1°36' E., bet. secs. 13 and 14.</p> <p>Ascend over gentle S. facing slope.</p>
40.06	<p>Point for the 1/4 sec. cor. of secs. 13 and 14, at proportionate dist., there is no remaining evidence of the orig. cor.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T 23 N R 18 E 1/4 S 14   S 13</p> <p style="text-align: center;">2007</p> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p> <p>Set a steel fence post, alongside and W. of the cor.</p>
59.39	<p>Underground water line, bears S. 74°55' E. and N. 74°55' W.</p>

Dependent Resurvey of the Subdivisional Lines,  
T. 23 N., R. 18 E., Gila and Salt River Meridian, Arizona

<p>CHAINS</p>	<p>80.12 Point for the cor. of secs. 11, 12, 13 and 14, at proportionate dist., there is no remaining evidence of the orig. cor.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, in a collar of stone, with brass cap mkd.</p> <table style="margin-left: auto; margin-right: auto;"> <tr> <td>T 23 N</td> <td>R 18 E</td> </tr> <tr> <td>S 11</td> <td>S 12</td> </tr> <tr> <td>S 14</td> <td>S 13</td> </tr> </table> <p style="text-align: center;">2007</p> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p> <p>Set a steel fence post, alongside and N. of the cor.</p> <hr/> <p>From the cor. of secs. 7, 12, 13 and 18, on the E. bdy. of the Tp., monumented with a stainless steel post, 2 1/2 ins. diam., firmly set, projecting 4 ins. above ground, with brass cap mkd. T23N R18E R19E S12 S7 S13 S18 2004, with a mound of stone, 3 ft. base, 2 ft. high to the W. Add the marks 2007 to the brass cap.</p> <p>A steel fence post, is set nearby and N. of the cor.</p> <p>S. 89°39' W., bet. secs. 12 and 13.</p> <p>Across S. facing toe slopes of Shonto Butte.</p> <p>38.76 Point for the 1/4 sec. cor. of secs. 12 and 13, at proportionate dist., there is no remaining evidence of the orig. cor.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, in a collar of stone, with brass cap mkd.</p> <table style="margin-left: auto; margin-right: auto;"> <tr> <td>T 23 N</td> <td>R 18 E</td> </tr> <tr> <td></td> <td>S 12</td> </tr> <tr> <td>1/4</td> <td>—</td> </tr> <tr> <td></td> <td>S 13</td> </tr> </table> <p style="text-align: center;">2007</p> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p> <p>Set a steel fence post, alongside and N. of the cor.</p>	T 23 N	R 18 E	S 11	S 12	S 14	S 13	T 23 N	R 18 E		S 12	1/4	—		S 13
T 23 N	R 18 E														
S 11	S 12														
S 14	S 13														
T 23 N	R 18 E														
	S 12														
1/4	—														
	S 13														

**Dependent Resurvey of the Subdivisional Lines,  
T. 23 N., R. 18 E., Gila and Salt River Meridian, Arizona**

CHAINS	
	<p>From this cor. point, a basalt stone, 14 X 9 X 6 ins., loosely set 4 ins. in the ground, mkd. 1/4 on E. face and A on top face, bears N. 74°26' W., 1.36 chs. dist. This monument is irreconcilable with found orig. cors., and is not utilized in the course of this resurvey.</p>
77.52	<p>The cor. of secs. 11, 12, 13 and 14.</p> <hr/> <p>N. 0°14' E., bet. secs. 11 and 12.</p> <p>Ascend S. slope of Shonto Butte.</p>
40.04	<p>Point for the 1/4 sec. cor. of secs. 11 and 12, at proportionate dist., there is no remaining evidence of the orig. cor.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 4 ins. in the ground to bedrock, in a supporting mound of stone, 5 ft. base, to top, with brass cap mkd.</p> <p style="text-align: center;">T 23 N R 18 E 1/4 S 11   S 12</p> <p style="text-align: center;">2007</p> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p> <p>Set a steel fence post, alongside and W. of the cor.</p> <p>Cor. is located on a bench in the southerly foothills of Shonto Butte.</p> <p>From this cor. point, the well head at Coyote Springs, bears N. 46°49' W., 23.73 chs. dist., an iron pipe, 24 ins. diam., set on concrete pedestal.</p>
80.08	<p>Point for the cor. of secs. 1, 2, 11 and 12, at proportionate dist., there is no remaining evidence of the orig. cor.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 23 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T 23 N R 18 E S 2   S 1 S 11   S 12</p> <p style="text-align: center;">2007</p> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p>

**Dependent Resurvey of the Subdivisional Lines,  
T. 23 N., R. 18 E., Gila and Salt River Meridian, Arizona**

CHAINS	
	<p>Set a steel fence post, alongside and N. of the cor.</p> <p>Cor. is located on top of Shonto Butte, about 15 chs. N. of the S. edge of the butte.</p> <p>From this cor. point, a basalt stone, 11 x 9 ins., firmly set, projecting 13 ins. above ground, in a collar of stone, mkd. S12A on S. face, bears N. 89°21' E., 5.63 chs. dist. This monument is irreconcilable with found orig. cors., and is not utilized in the course of this resurvey.</p> <hr/> <p>From the cor. of secs. 1, 6, 7 and 12, on the E. bdy. of the Tp., monumented with a stainless steel post, 2 1/2 ins. diam., firmly set, projecting 10 ins. above ground, in a mound of stone, 5 ft. base, to top, with brass cap mkd. T23N R18E R19E S1 S6 S12 S7 2004. Add the marks 2007 to the brass cap.</p> <p>A steel fence post, is set nearby and N. of the cor.</p> <p>N. 89°37' W., bet. secs. 1 and 12.</p> <p>Ascend over the easterly foothills of Shonto Butte.</p>
39.35	<p>Point for the 1/4 sec. cor. of secs. 1 and 12, at proportionate dist., there is no remaining evidence of the orig. cor.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 20 ins. in the ground, in a mound of stone, 3 ft. base, to top, with brass cap mkd.</p> <div style="text-align: center;"> <p>T 23 N R 18 E</p> <p>S 1</p> <p>1/4 ———</p> <p>S 12</p> <p>2007</p> </div> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p> <p>Set a steel fence post, alongside and N. of the cor.</p>
78.71	<p>The cor. of secs. 1, 2, 11 and 12.</p> <hr/> <p>N. 3°55' E., bet. secs. 1 and 2.</p> <p>Over nearly level grass land, atop Shonto Butte</p>
40.14	<p>Point for the 1/4 sec. cor. of secs. 1 and 2, at proportionate dist., there is no remaining evidence of the orig. cor.</p>

**Dependent Resurvey of the Subdivisional Lines,  
T. 23 N., R. 18 E., Gila and Salt River Meridian, Arizona**

CHAINS	
80.58	<p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 20 ins. in the ground, in a mound of stone, 2 1/2 ft. base, to top, with brass cap mkd.</p> <p align="center">T 23 N R 18 E 1/4 S 2   S 1</p> <p align="center">2007</p> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p> <p>Set a steel fence post, alongside and W. of the cor.</p> <p>Cor. is located on a bench, within the N. facing slopes of Shonto Butte.</p> <p>The cor. of secs. 1, 2, 35 and 36, on the N. bdy. of the Tp., hereinbefore described.</p>
39.23	<hr/> <p>From the cor. of secs. 2, 3, 34 and 35, on the S. bdy. of the Tp., hereinbefore described.</p> <p>N. 0°07' E., bet. secs. 34 and 35.</p> <p>Descending over broken and rolling land.</p> <p>Point for the 1/4 sec. cor. of secs. 34 and 35, at proportionate dist., there is no remaining evidence of the orig. cor.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 15 ins. in the ground to bedrock, in a mound of stone, 3 ft. base, to top, with brass cap mkd.</p> <p align="center">T 23 N R 18 E 1/4 S 34   S 35</p> <p align="center">2007</p>
78.46	<p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p> <p>Cor. is located 33 lks. E. of a wash, 5 ft. wide at bottom, drains NW.</p> <p>Point for the cor. of secs. 26, 27, 34 and 35, at proportionate dist., there is no remaining evidence of the orig. cor.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 22 ins. in the ground, with brass cap mkd.</p>

**Dependent Resurvey of the Subdivisional Lines,  
T. 23 N., R. 18 E., Gila and Salt River Meridian, Arizona**

CHAINS									
	<table style="margin: auto;"> <tr><td>T 23 N</td><td>R 18 E</td></tr> <tr><td>S 27</td><td>S 26</td></tr> <tr><td>S 34</td><td>S 35</td></tr> </table>	T 23 N	R 18 E	S 27	S 26	S 34	S 35		
T 23 N	R 18 E								
S 27	S 26								
S 34	S 35								
	2007								
	Deposit a magnet, in a white plastic case, at the base of the stainless steel post.								
	Set a steel fence post, alongside and N. of the cor.								
	<hr/>								
	From the true point for the cor. of secs. 25, 26, 35 and 36.								
	S. 88°45' W., bet. secs. 26 and 35.								
	Over broken and rolling land.								
39.37	Point for the 1/4 sec. cor. of secs. 26 and 35, at proportionate dist., there is no remaining evidence of the orig. cor.								
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 25 ins. in the ground, with brass cap mkd.								
	<table style="margin: auto;"> <tr><td>T 23 N</td><td>R 18 E</td></tr> <tr><td>S 26</td><td></td></tr> <tr><td>1/4</td><td>—</td></tr> <tr><td>S 35</td><td></td></tr> </table>	T 23 N	R 18 E	S 26		1/4	—	S 35	
T 23 N	R 18 E								
S 26									
1/4	—								
S 35									
	2007								
	Deposit a magnet, in a white plastic case, at the base of the stainless steel post.								
	Set a steel fence post, alongside and N. of the cor.								
78.74	The cor. of secs. 26, 27, 34 and 35.								
	<hr/>								
	N. 0°05' E., bet. secs. 26 and 27.								
	Descending, over broken land.								
32.23	Point selected for a witness cor. to the 1/4 sec. cor. of secs. 26 and 27.								
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 22 ins. in the ground, over a steel fence post, (72 ins. long, driven 66 ins. in the ground), with brass cap mkd.								

Dependent Resurvey of the Subdivisional Lines,  
T. 23 N., R. 18 E., Gila and Salt River Meridian, Arizona

CHAINS	
	<p style="text-align: center;">WC T 23 N R 18 E 1/4 S 27 ↑ S 26 2007</p>
	<p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p> <p>Set a steel fence post, alongside and W. of the cor.</p>
	<p>Cor. is located on a bluff at the S. side of Coyote Wash, about 50 lks. above the bottom.</p>
39.23	<p>True point for the 1/4 sec. cor. of secs. 26 and 27, at proportionate dist., falls in Coyote Wash, where it is impracticable to establish a permanent monument, there is no remaining evidence of the orig. cor.</p>
47.25	<p>Right high bank of Coyote Wash, bears S. 40° E. and S. 70° W., thence ascend.</p>
76.53	<p>Midpoint bet. two, Transwestern Pipeline Co., underground gas lines, bears N. 77°13' E. and S. 77°13' W.</p>
78.46	<p>Point for the cor. of secs. 22, 23, 26 and 27, at proportionate dist., there is no remaining evidence of the orig. cor.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p>
	<p style="text-align: center;">T 23 N R 18 E S 22   S 23 S 27   S 26 2007</p> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p> <p>Set a steel fence post, alongside and W. of the cor.</p> <hr/> <p>From the cor. of secs. 23, 24, 25 and 26.</p> <p>S. 87°34' W., bet. secs. 23 and 26.</p> <p>Over broken and rolling land, through sage and bunch grass.</p>
39.49	<p>Point for the 1/4 sec. cor. of secs. 23 and 26, at proportionate dist., there is no remaining evidence of the orig. cor.</p>

**Dependent Resurvey of the Subdivisional Lines,  
T. 23 N., R. 18 E., Gila and Salt River Meridian, Arizona**

CHAINS	
	<p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 22 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T 23 N R 18 E S 23 1/4 ——— S 26</p> <p style="text-align: center;">2007</p> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p> <p>Set a steel fence post, alongside and N. of the cor.</p>
68.53	Midpoint bet. two, Transwestern Pipeline Co., underground gas lines, bears N. 77°13' E. and S. 77°13' W.
78.98	The cor. of secs. 22, 23, 26 and 27.
	<hr/> <p>N. 0°02' W., bet. secs. 22 and 23.</p> <p>Over nearly level land.</p>
14.74	Center line of BIA Route N15, a paved two lane road, 25 ft. wide, bears N. 69°37' E. and S. 69°37' W.
18.46	Midpoint bet. four, El Paso Natural Gas Co., underground gas lines, bears N. 69°36' E. and S. 69°36' W.
39.23	Point for the 1/4 sec. cor. of secs. 22 and 23, at proportionate dist., there is no remaining evidence of the orig. cor.
	<p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 25 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T 23 N R 18 E 1/4 S 22   S 23</p> <p style="text-align: center;">2007</p> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p>
78.46	Point for the cor. of secs. 14, 15, 22 and 23, at proportionate dist., there is no remaining evidence of the orig. cor.
	<p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 25 ins. in the ground, with brass cap mkd.</p>



**Dependent Resurvey of the Subdivisional Lines,  
T. 23 N., R. 18 E., Gila and Salt River Meridian, Arizona**

CHAINS	
	T 23 N R 18 E S 15   S 14 S 22   S 23  2007
	Deposit a magnet, in a white plastic case, at the base of the stainless steel post.  Set a steel fence post, alongside and W. of the cor.  From this cor. point, a basalt stone, 10 x 8 x 6 ins., lying loose in a mound of stone, mkd. S14 on a face and A on opposite face, bears N. 8°52' W., 5.90 chs. dist. A rebar, 3/4 in. diam., firmly set, projecting 1 in. above ground, is set in the center of the mound of stone. Theses monuments are irreconcilable with found orig. cors., and are not utilized in the course of this resurvey.
	<hr/> From the cor. of secs. 13, 14, 23 and 24.  S. 86°25' W., bet. secs. 14 and 23.  Over nearly level land.
39.87	Point for the 1/4 sec. cor. of secs. 14 and 23, at proportionate dist., there is no remaining evidence of the orig. cor.  Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with brass cap mkd.
	T 23 N R 18 E S 14 1/4 ——— S 23  2007
	Deposit a magnet, in a white plastic case, at the base of the stainless steel post.  Set a steel fence post, alongside and N. of the cor.  From this cor. point, a basalt stone, 6 x 4 x 2 ins., lying loose, mkd. 1/4 on exposed face, bears N. 13°16' W., 3.37 chs. dist. This monument is irreconcilable with found orig. cors., and is not utilized in the course of this resurvey.
79.73	The cor. of secs. 14, 15, 22 and 23.  <hr/> N. 2°40' E., bet. secs. 14 and 15.

**Dependent Resurvey of the Subdivisional Lines,  
T. 23 N., R. 18 E., Gila and Salt River Meridian, Arizona**

CHAINS	
39.27	<p>Ascending over rolling land.</p> <p>Point for the 1/4 sec. cor. of secs. 14 and 15, at proportionate dist., there is no remaining evidence of the orig. cor.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 25 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T 23 N R 18 E 1/4 S 15   S 14</p> <p style="text-align: center;">2007</p> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p> <p>Set a steel fence post, alongside and W. of the cor.</p> <p>From this cor. point, a basalt stone, 8 x 5 x 3 ins., lying loose, in an embedded mound of stone, mkd. 1/4 A on a face, bears N. 22°09' W., 7.02 chs. dist. This monument is irreconcilable with found orig. cors., and is not utilized in the course of this resurvey.</p>
78.54	<p>The cor. of secs. 10, 11, 14 and 15, monumented with a basalt stone, 13 x 11 x 8 ins., firmly set, projecting 9 ins. above ground, mkd. with 2 grooves on E. face and 4 grooves on S. face.</p> <p>At the corner point</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 25 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T 23 N R 18 E S 10   S 11 S 15   S 14</p> <p style="text-align: center;">2007</p> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p> <p>Raise a mound of stone, 3 ft. base, 1 1/2 ft. high, W. of cor.</p> <p>Incorporate the mkd. stone within the accessory mound of stone.</p> <p>From this cor. point, a mound of stone, 2 ft. base, 1 ft. high, bears N. 31°16' W., 8.43 chs. dist. This monument is irreconcilable with found orig. cors., and is not utilized in the course of this resurvey.</p> <hr/>

**Dependent Resurvey of the Subdivisional Lines,  
T. 23 N., R. 18 E., Gila and Salt River Meridian, Arizona**

CHAINS	
	<p>From the cor. of secs. 11, 12, 13 and 14.</p> <p>S. 85°10' W., bet. secs. 11 and 14.</p> <p>Across S. facing toe slopes of Shonto Butte.</p>
39.22	<p>Point for the 1/4 sec. cor. of secs. 11 and 14, at proportionate dist., there is no remaining evidence of the orig. cor.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T 23 N R 18 E S 11 1/4 ——— S 14</p> <p style="text-align: center;">2007</p> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p> <p>Set a steel fence post, alongside and N. of the cor.</p> <p>From this cor. point, a mound of stone, 3 ft. base, 1 ft. high, bears N. 41°48' W., 5.24 chs. dist. This monument is irreconcilable with found orig. cors., and is not utilized in the course of this resurvey.</p>
59.17	Underground water line, bears S. 74°49' E. and N. 74°49' W.
78.44	<p>The cor. of secs. 10, 11, 14 and 15.</p> <hr/> <p>N. 0°16' W., bet. secs. 10 and 11.</p> <p>Ascending over foothills of Shonto Butte.</p>
6.84	Underground water line, bears S. 74°49' E. and N. 74°49' W.
40.24	<p>Point for the 1/4 sec. cor. of secs. 10 and 11, at proportionate dist., there is no remaining evidence of the orig. cor.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T 23 N R 18 E 1/4 S 10   S 11</p> <p style="text-align: center;">2007</p>

**Dependent Resurvey of the Subdivisional Lines,  
T. 23 N., R. 18 E., Gila and Salt River Meridian, Arizona**

CHAINS									
80.48	<p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p> <p>Set a steel fence post, alongside and W. of the cor.</p> <p>The cor. of secs. 2, 3, 10 and 11, monumented with a basalt stone, 15 x 12 x 10 ins., firmly set, projecting 12 ins. above ground, mkd. with 5 grooves on S. face, and 2 grooves on E. face, with a mound of stone, 3 ft. base, 1 ft. high to the W.</p> <p>At the corner point</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 25 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center;"> <table style="margin: auto;"> <tr><td>T 23 N</td><td>R 18 E</td></tr> <tr><td>S 3</td><td>S 2</td></tr> <tr><td>S 10</td><td>S 11</td></tr> </table> <p>2007</p> </div> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p> <p>Rebuild accessory mound of stone, to 3 ft. base, 2 ft. high, incorporate mkd. stone within.</p> <hr/> <p>From the cor. of secs. 1, 2, 11 and 12.</p> <p>S. 85°30' W., bet. secs. 2 and 11.</p> <p>Across S. face of Shonto Butte.</p>	T 23 N	R 18 E	S 3	S 2	S 10	S 11		
T 23 N	R 18 E								
S 3	S 2								
S 10	S 11								
39.54	<p>Point for the 1/4 sec. cor. of secs. 2 and 11, at proportionate dist., there is no remaining evidence of the orig. cor.</p> <p>Set a brass tablet, 3 1/4 ins. diam., 3 1/2 ins. stem, in a concrete form, (8 x 8 x 7 ins.), atop rock outcropping, with top mkd.</p> <div style="text-align: center;"> <table style="margin: auto;"> <tr><td>T 23 N</td><td>R 18 E</td></tr> <tr><td>S 2</td><td></td></tr> <tr><td>1/4</td><td>—</td></tr> <tr><td>S 11</td><td></td></tr> </table> <p>2007</p> </div> <p>Raise a mound of stone, 3 ft. base, 2 ft. high, N. of the cor.</p> <p>Set a steel fence post within the accessory mound.</p>	T 23 N	R 18 E	S 2		1/4	—	S 11	
T 23 N	R 18 E								
S 2									
1/4	—								
S 11									

**Dependent Resurvey of the Subdivisional Lines,  
T. 23 N., R. 18 E., Gila and Salt River Meridian, Arizona**

CHAINS	
	Cor. is located 1.30 chs. E. of and 45 lks. above, the center of a wash, 7 ft. wide, drains S. 15° W.
79.09	The cor. of secs. 2, 3, 10 and 11. <hr/>
	N. 2°35' E., bet. secs. 2 and 3.  Along western flank of Shonto Butte.
43.17	True point for the 1/4 sec. cor. of secs. 2 and 3, at proportionate dist., falls on the face of a near vertical cliff, where is impracticable to establish a permanent monument, there is no remaining evidence of the orig. cor.
48.17	Point selected for a witness cor. to the 1/4 sec. cor. of secs. 2 and 3.  Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 18 ins. in the ground, in a mound of stone, 3 ft. base, to top, with brass cap mkd.  <div style="text-align: center;">           WC            T 23 N R 18 E            1/4            S 3 ↓ S 2            2007         </div>
	Deposit a magnet, in a white plastic case, at the base of the stainless steel post.  Set a steel fence post, alongside and W. of the cor.  Cor. is located on a bench, within the north slopes of Shonto Butte.
86.22	The cor. of secs. 2, 3, 34 and 35, on the N. bdy. of the Tp., hereinbefore described. <hr/>
	From the cor. of secs. 3, 4, 33 and 34, on the S. bdy. of the Tp., hereinbefore described.  N. 0°32' E., bet. secs. 33 and 34.  Descending over broken and rolling land.
39.22	Point for the 1/4 sec. cor. of secs. 33 and 34, at proportionate dist., there is no remaining evidence of the orig. cor.  Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 22 ins. in the ground, in a collar of stone, with brass cap mkd.

Dependent Resurvey of the Subdivisional Lines,  
T. 23 N., R. 18 E., Gila and Salt River Meridian, Arizona

CHAINS	
78.44	<p style="text-align: center;">T 23 N R 18 E 1/4 S 33   S 34</p> <p style="text-align: center;">2007</p> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p> <p>Point for the cor. of secs. 27, 28, 33 and 34, at proportionate dist., there is no remaining evidence of the orig. cor.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 22 ins. in the ground, over a steel fence post, (72 ins. long, driven 66 ins. in the ground), with brass cap mkd.</p> <p style="text-align: center;">T 23 N R 18 E S 28   S 27 S 33   S 34</p> <p style="text-align: center;">2007</p> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p>
39.42	<hr/> <p>From the cor. of secs. 26, 27, 34 and 35.</p> <p>N. 89°51' W., bet. secs. 27 and 34.</p> <p>Over broken and rolling land.</p> <p>Point for the 1/4 sec. cor. of secs. 27 and 34, at proportionate dist., there is no remaining evidence of the orig. cor.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, in a collar of stone, with brass cap mkd.</p> <p style="text-align: center;">T 23 N R 18 E S 27 1/4 ——— S 34</p> <p style="text-align: center;">2007</p> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p>
78.84	<hr/> <p>The cor. of secs. 27, 28, 33 and 34.</p> <hr/> <p>N. 0°02' W., bet. secs. 27 and 28.</p>

**Dependent Resurvey of the Subdivisional Lines,  
T. 23 N., R. 18 E., Gila and Salt River Meridian, Arizona**

CHAINS	
	Over gently rolling land.
39.22	Point for the 1/4 sec. cor. of secs. 27 and 28, at proportionate dist., there is no remaining evidence of the orig. cor.  Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with brass cap mkd.  <div style="text-align: center;">           T 23 N R 18 E                  1/4            S 28   S 27             2007         </div>
	Deposit a magnet, in a white plastic case, at the base of the stainless steel post.  Set a steel fence post, alongside and W. of the cor.
54.05	Midpoint bet. two, Transwestern Pipeline Co., underground gas lines, bears N. 69°19' E. and S. 69°19' W.
63.66	Center of pavement, BIA Route N15, asphalt surfaced, 25 ft. wide, bears N. 69°37' E. and S. 69°37' W.
67.33	Midpoint bet. four, El Paso Natural Gas Co., underground gas lines, bears N. 70°03' E. and S. 70°02' W.
78.44	Point for the cor. of secs. 21, 22, 27 and 28, at proportionate dist., there is no remaining evidence of the orig. cor.  Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 20 ins. in the ground, in a mound of stone, 3 ft. base, to top, with brass cap mkd.  <div style="text-align: center;">           T 23 N R 18 E            S 21   S 22            --- ---            S 28   S 27             2007         </div>
	Deposit a magnet, in a white plastic case, at the base of the stainless steel post.  Set a steel fence post, alongside and W. of the cor.
	From the cor. of secs. 22, 23, 26 and 27.  N. 89°52' W., bet. secs. 22 and 27.  Over broken and rolling land.

**Dependent Resurvey of the Subdivisional Lines,  
T. 23 N., R. 18 E., Gila and Salt River Meridian, Arizona**

CHAINS	
39.43	Center of pavement, BIA Route N15, asphalt surfaced, 25 ft. wide, bears N. 69°37' E. and S. 69°37' W.
39.49	Point for the 1/4 sec. cor. of secs. 22 and 27, at proportionate dist., falls in the west bound lane of BIA Route N15, asphalt surfaced, 25 ft. wide, bears N. 69°37' E. and S. 69°37' W., there is no remaining evidence of the orig. cor.  Set a railroad spike, flush with the surface of asphalt.  from which  A stainless steel post, 28 ins. long, 2 1/2 ins. diam., set 21 ins. in the ground, for a reference monument, bears N. 25°00' E., 137.0 ft. dist., with brass cap mkd. RM T23N R18E 1/4 S22 137.0 FT. TO COR., and an arrow pointing to the cor. Deposit a magnet, in a white plastic case, at the base of the stainless steel post.  A stainless steel post, 28 ins. long, 2 1/2 ins. diam., set 25 ins. in the ground, for a reference monument, bears S 65°00' E., 138.0 ft. dist., with brass cap mkd. RM T23N R18E 1/4 S27 138.0 FT. TO COR., and an arrow pointing to the cor. Deposit a magnet, in a white plastic case, at the base of the stainless steel post.
49.20	Midpoint bet. four, El Paso Natural Gas Co., underground gas lines, bears N. 69°36' E. and S. 69°37' W.
78.98	The cor. of secs. 21, 22, 27 and 28. <hr/>
	N. 0°52' W., bet. secs. 21 and 22.  Over broken and rolling land.
39.23	Point for the 1/4 sec. cor. of secs. 21 and 22, at proportionate dist., there is no remaining evidence of the orig. cor.  Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 20 ins. in the ground, in a mound of stone, 3 ft. base, to top, with brass cap mkd.  T 23 N R 18 E 1/4 S 21   S 22  2007  Deposit a magnet, in a white plastic case, at the base of the stainless steel post.



**Dependent Resurvey of the Subdivisional Lines,  
T. 23 N., R. 18 E., Gila and Salt River Meridian, Arizona**

CHAINS									
78.46	<p>Point for the cor. of secs. 15, 16, 21 and 22, at proportionate dist., there is no remaining evidence of the orig. cor.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center;"> <table border="0"> <tr> <td>T 23 N</td> <td>R 18 E</td> </tr> <tr> <td>S 16</td> <td>S 15</td> </tr> <tr> <td>S 21</td> <td>S 22</td> </tr> </table> <p>2007</p> </div> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p> <p>Set a steel fence post, alongside and W. of the cor.</p> <hr/>	T 23 N	R 18 E	S 16	S 15	S 21	S 22		
T 23 N	R 18 E								
S 16	S 15								
S 21	S 22								
	<p>From the cor. of secs. 14, 15, 22 and 23.</p> <p>N. 89°53' W., bet. secs. 15 and 22.</p> <p>Over broken and rolling land.</p>								
40.06	<p>Point for the 1/4 sec. cor. of secs. 15 and 22, at proportionate dist., there is no remaining evidence of the orig. cor.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, in a collar of stone, with brass cap mkd.</p> <div style="text-align: center;"> <table border="0"> <tr> <td>T 23 N</td> <td>R 18 E</td> </tr> <tr> <td>S 15</td> <td></td> </tr> <tr> <td>1/4</td> <td>—</td> </tr> <tr> <td>S 22</td> <td></td> </tr> </table> <p>2007</p> </div> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p>	T 23 N	R 18 E	S 15		1/4	—	S 22	
T 23 N	R 18 E								
S 15									
1/4	—								
S 22									
80.12	<p>The cor. of secs. 15, 16, 21 and 22.</p> <hr/> <p>N. 2°36' E., bet. secs. 15 and 16.</p> <p>Over broken and rolling land.</p>								
39.26	<p>Point for the 1/4 sec. cor. of secs. 15 and 16, at proportionate dist., there is no remaining evidence of the orig. cor.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p>								

**Dependent Resurvey of the Subdivisional Lines,  
T. 23 N., R. 18 E., Gila and Salt River Meridian, Arizona**

CHAINS	
78.52	<p style="text-align: center;">T 23 N R 18 E 1/4 S 16   S 15</p> <p style="text-align: center;">2007</p> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p> <p>Set a steel fence post, alongside and W. of the cor.</p> <p>The cor. of secs. 9, 10, 15 and 16, monumented with a basalt stone, 18 x 11 x 5 ins., lying loose, mkd. with 4 grooves on a face, and 3 grooves on an adjacent face.</p> <p>At the corner point</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 25 ins. in the ground, with brass cap mkd.</p>
40.09	<p style="text-align: center;">T 23 N R 18 E S 9   S 10 S 16   S 15</p> <p style="text-align: center;">2007</p> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post, and the orig. stone alongside.</p> <p>Set a steel fence post, alongside and W. of the cor.</p> <hr/> <p>From the cor. of secs. 10, 11, 14 and 15.</p> <p>N. 89°53' W., bet. secs. 10 and 15.</p> <p>Over broken and rolling land.</p> <p>Point for the 1/4 sec. cor. of secs. 10 and 15, at proportionate dist., there is no remaining evidence of the orig. cor.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 25 ins. in the ground, with brass cap mkd.</p>
	<p style="text-align: center;">T 23 N R 18 E S 10 1/4 ——— S 15</p> <p style="text-align: center;">2007</p> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p>

**Dependent Resurvey of the Subdivisional Lines,  
T. 23 N., R. 18 E., Gila and Salt River Meridian, Arizona**

CHAINS	
80.19	<p>Set a steel fence post, alongside and N. of the cor.</p> <p>The cor. of secs. 9, 10, 15 and 16.</p> <hr/> <p>N. 0°02' E., bet. secs. 9 and 10.</p> <p>Ascending over broken and rolling land.</p>
41.84	<p>Point for the 1/4 sec. cor. of secs. 9 and 10, at proportionate dist., there is no remaining evidence of the orig. cor.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 18 ins. in the ground, in a mound of stone, 2 1/2 ft. base, to top, with brass cap mkd.</p> <p style="text-align: center;">T 23 N R 18 E 1/4 S 9   S 10  2007</p> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p>
83.68	<p>The cor. of secs. 3, 4, 9 and 10, monumented with a basalt stone, 15 x 8 x 7 ins., firmly set, projecting 11 ins. above ground, mkd. with 3 grooves on E. face and 5 grooves on S. face, located in an embedded mound of stone.</p> <p>At the corner point</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 18 ins. in the ground, in a mound of stone, 2 1/2 ft. base, to top, with brass cap mkd.</p> <p style="text-align: center;">T 23 N R 18 E S 4   S 3 <hr/>S 9   S 10  2007</p> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p> <p>Incorporate the mkd. stone within the mound of stone.</p> <hr/> <p>From the cor. of secs. 2, 3, 10 and 11.</p> <p>N. 88°46' W., bet. secs. 3 and 10.</p>

**Dependent Resurvey of the Subdivisional Lines,  
T. 23 N., R. 18 E., Gila and Salt River Meridian, Arizona**

CHAINS	
	Descending over SW facing toe slopes of Shonto Butte.
35.97	Underground water line, bears N. 1°26' E. and S. 1°26' W.
39.99	The 1/4 sec. cor. of secs. 3 and 10, monumented with a basalt stone, 12 x 8 x 4 ins., lying loose, mkd. 1/4 on exposed face, with an embedded mound of stone, 3 ft. base to W.
	At the corner point
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.
	T 23 N R 18 E S 3 1/4 ——— S 10  2007
	Deposit a magnet, in a white plastic case, at the base of the stainless steel post.
	Disassemble embedded mound of stone, and raise a mound of stone, 2 1/2 ft. base, 2 ft. high, N. of cor.
	Incorporate the mkd. stone, within the mound of stone.
	—————
	N. 86°24' W., beginning new measurement.
39.85	The cor. of secs. 3, 4, 9 and 10.
	—————
	N. 1°23' E., bet. secs. 3 and 4.
	Over rolling and broken land.
41.69	Point for the 1/4 sec. cor. of secs. 3 and 4, at proportionate dist., there is no remaining evidence of the orig. cor.
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 20 ins. in the ground, in a mound of stone, 2 ft. base, to top, with brass cap mkd.
	T 23 N R 18 E 1/4 S 4   S 3  2007
	Deposit a magnet, in a white plastic case, at the base of the stainless steel post.

**Dependent Resurvey of the Subdivisional Lines,  
T. 23 N., R. 18 E., Gila and Salt River Meridian, Arizona**

CHAINS	
83.03	<p>The cor. of secs. 3, 4, 33 and 34, on the N. bdy. of the Tp., hereinbefore described.</p> <hr/> <p>From the cor. of secs. 4, 5, 32 and 33, on the S. bdy. of the Tp., hereinbefore described.</p> <p>N. 1°27' E., bet. secs. 32 and 33.</p> <p>Over rolling and broken land.</p>
40.05	<p>Point for the 1/4 sec. cor. of secs. 32 and 33, at proportionate dist., there is no remaining evidence of the orig. cor.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center;"> <p>T 23 N R 18 E 1/4 S 32   S 33</p> <p>2007</p> </div> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p> <p>Set a steel fence post, alongside and W. of the cor.</p>
80.10	<p>Point for the cor. of secs. 28, 29, 32 and 33, at proportionate dist., there is no remaining evidence of the orig. cor.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center;"> <p>T 23 N R 18 E S 29   S 28 S 32   S 33</p> <p>2007</p> </div> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p> <p>Set a steel fence post, alongside and W. of the cor.</p> <p>Cor. is located 20 lks. S. of a track road, bears NE and SW.</p> <hr/> <p>From the cor. of secs. 27, 28, 33 and 34.</p> <p>N. 88°26' W., bet. secs. 28 and 33.</p>

**Dependent Resurvey of the Subdivisional Lines,  
T. 23 N., R. 18 E., Gila and Salt River Meridian, Arizona**

CHAINS	
	Over gently rolling land.
5.14	Center of pavement, Arizona State Highway No. 87, asphalt surfaced, 28 ft. wide, bears S. 1°47' E. and N. 1°47' W.
39.35	Point for the 1/4 sec. cor. of secs. 28 and 33, at proportionate dist., there is no remaining evidence of the orig. cor.  Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.  <div style="text-align: center;">           T 23 N R 18 E                      S 28                  1/4 ———                      S 33             2007         </div>
	Deposit a magnet, in a white plastic case, at the base of the stainless steel post.  Set a steel fence post, alongside and N. of the cor.
78.70	The cor. of secs. 28, 29, 32 and 33. <hr/>
	N. 0°23' W., bet. secs. 28 and 29.  Over gently rolling land.
21.98	Midpoint bet. two, Transwestern Pipeline Co., underground gas lines, bears N. 69°10' E. and S. 69°10' W.
32.21	Center of pavement, BIA Route N15, asphalt surfaced, 24 ft. wide, bears N. 69°36' E. and S. 69°36' W.
35.78	Midpoint bet. four, El Paso Natural Gas Co., underground gas lines, bears N. 69°33' E. and S. 69°33' W.
40.04	Point for the 1/4 sec. cor. of secs. 28 and 29, at proportionate dist., there is no remaining evidence of the orig. cor.  Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 25 ins. in the ground, with brass cap mkd.  <div style="text-align: center;">           T 23 N R 18 E                      1/4                  S 29   S 28             2007         </div>
	Deposit a magnet, in a white plastic case, at the base of the stainless steel post.

**Dependent Resurvey of the Subdivisional Lines,  
T. 23 N., R. 18 E., Gila and Salt River Meridian, Arizona**

CHAINS									
80.08	<p>Set a steel fence post, alongside and W. of the cor.</p> <p>Point for the cor. of secs. 20, 21, 28 and 29, at proportionate dist., there is no remaining evidence of the orig. cor.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center;"> <table style="margin: auto;"> <tr><td>T 23 N</td><td>R 18 E</td></tr> <tr><td>S 20</td><td>S 21</td></tr> <tr><td>S 29</td><td>S 28</td></tr> </table> <p>2007</p> </div> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p> <p>Set a steel fence post, alongside and W. of the cor.</p> <hr/> <p>From the cor. of secs. 21, 22, 27 and 28.</p> <p>N. 87°16' W., bet. secs. 21 and 28.</p> <p>Over gently sloping land.</p>	T 23 N	R 18 E	S 20	S 21	S 29	S 28		
T 23 N	R 18 E								
S 20	S 21								
S 29	S 28								
7.56	<p>Center of pavement, Arizona State Highway No. 87, asphalt surfaced, 28 ft. wide, bears S. 1°47' E. and N. 1°47' W.</p>								
39.62	<p>Point for the 1/4 sec. cor. of secs. 21 and 28, at proportionate dist., there is no remaining evidence of the orig. cor.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 25 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center;"> <table style="margin: auto;"> <tr><td>T 23 N</td><td>R 18 E</td></tr> <tr><td>S 21</td><td></td></tr> <tr><td>1/4</td><td>—</td></tr> <tr><td>S 28</td><td></td></tr> </table> <p>2007</p> </div> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p> <p>Set a steel fence post, alongside and N. of the cor.</p>	T 23 N	R 18 E	S 21		1/4	—	S 28	
T 23 N	R 18 E								
S 21									
1/4	—								
S 28									
79.24	<p>The cor. of secs. 20, 21, 28 and 29.</p> <hr/> <p>N. 1°30' W., bet. secs. 20 and 21.</p>								

**Dependent Resurvey of the Subdivisional Lines,  
T. 23 N., R. 18 E., Gila and Salt River Meridian, Arizona**

CHAINS	
	Ascending over broken and rolling land.
40.05	Point for the 1/4 sec. cor. of secs. 20 and 21, at proportionate dist., there is no remaining evidence of the orig. cor.  Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.  <div style="text-align: center;">           T 23 N R 18 E                  1/4            S 20   S 21             2007         </div> Deposit a magnet, in a white plastic case, at the base of the stainless steel post.  Set a steel fence post, alongside and W. of the cor.
80.10	Point for the cor. of secs. 16, 17, 20 and 21, at proportionate dist., there is no remaining evidence of the orig. cor.  Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.  <div style="text-align: center;">           T 23 N R 18 E            S 17   S 16            S 20   S 21             2007         </div> Deposit a magnet, in a white plastic case, at the base of the stainless steel post.  Set a steel fence post, alongside and W. of the cor.  From this cor. point, a pumice stone, 7 x 6 x 3 ins., lying loose in an embedded mound of stone, mkd S20 on a face and A on an adjacent face, bears N. 72°57' E., 3.44 chs. dist. This monument is irreconcilable with found orig. cors., and is not utilized in the course of this resurvey.  <hr/> From the cor. of secs. 15, 16, 21 and 22.  N. 86°08' W., bet. secs. 16 and 21.  Over nearly level land.
8.85	Center of pavement, Arizona State Highway No. 87, asphalt surfaced, 28 ft. wide, bears S. 1°47' E. and N. 1°47' W.



**Dependent Resurvey of the Subdivisional Lines,  
T. 23 N., R. 18 E., Gila and Salt River Meridian, Arizona**

CHAINS	
40.12	<p>Point for the 1/4 sec. cor. of secs. 16 and 21, at proportionate dist., there is no remaining evidence of the orig. cor.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 25 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center;">           T 23 N R 18 E                      S 16                  1/4 ———                      S 21             2007         </div> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p>
80.24	<p>The cor. of secs. 16, 17, 20 and 21.</p> <hr/> <p>N. 1°53' E., bet. secs. 16 and 17.</p> <p>Over nearly level land.</p>
40.06	<p>Point for the 1/4 sec. cor. of secs. 16 and 17, at proportionate dist., there is no remaining evidence of the orig. cor.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 23 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center;">           T 23 N R 18 E                      1/4                  S 17   S 16             2007         </div> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p> <p>Set a steel fence post, alongside and W. of the cor.</p>
80.12	<p>Point for the cor. of secs. 8, 9, 16 and 17, at proportionate dist., there is no remaining evidence of the orig. cor.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center;">           T 23 N R 18 E                  S 8   S 9                  — —                  S 17   S 16             2007         </div>

**Dependent Resurvey of the Subdivisional Lines,  
T. 23 N., R. 18 E., Gila and Salt River Meridian, Arizona**

CHAINS	
	<p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p> <hr/> <p>From the cor. of secs. 9, 10, 15 and 16.</p> <p>N. 85°02' W., bet. secs. 9 and 16.</p> <p>Over rolling land.</p>
14.92	Center of pavement, Arizona State Highway No. 87, asphalt surfaced, 28 ft. wide, bears S. 1°47' E. and N. 1°47' W.
40.64	<p>Point for the 1/4 sec. cor. of secs. 9 and 16, at proportionate dist., there is no remaining evidence of the orig. cor.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center;"> <p>T 23 N R 18 E</p> <p>S 9</p> <p>1/4 ———</p> <p>S 16</p> <p>2007</p> </div> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p> <p>Set a steel fence post, alongside and N. of the cor.</p>
81.28	<p>The cor. of secs. 8, 9, 16 and 17.</p> <hr/> <p>N. 0°04' E., bet. secs. 8 and 9.</p> <p>Over rolling and broken land.</p>
40.04	<p>Point for the 1/4 sec. cor. of secs. 8 and 9, at proportionate dist., there is no remaining evidence of the orig. cor.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 25 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center;"> <p>T 23 N R 18 E</p> <p>1/4</p> <p>S 8   S 9</p> <p>2007</p> </div> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p>

**Dependent Resurvey of the Subdivisional Lines,  
T. 23 N., R. 18 E., Gila and Salt River Meridian, Arizona**

CHAINS									
80.08	<p>Point for the cor. of secs. 4, 5, 8 and 9, at proportionate dist., there is no remaining evidence of the orig. cor.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center;"> <table style="margin-left: auto; margin-right: auto;"> <tr><td>T 23 N</td><td>R 18 E</td></tr> <tr><td>S 5</td><td>S 4</td></tr> <tr><td>S 8</td><td>S 9</td></tr> </table> <p>2007</p> </div> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p> <p>Set a steel fence post, alongside and W. of the cor.</p> <hr/> <p>From the cor. of secs. 3, 4, 9 and 10.</p> <p>N. 87°34' W., bet. secs. 4 and 9.</p> <p>Over rolling land.</p>	T 23 N	R 18 E	S 5	S 4	S 8	S 9		
T 23 N	R 18 E								
S 5	S 4								
S 8	S 9								
17.42	<p>Center of pavement, Arizona State Highway No. 87, asphalt surfaced, 28 ft. wide, on the arc of a circular curve to the right, having a central angle of 6°33'30" and a radius of 11,503.3 ft.</p> <p>From this point, the calculated P.O.T., bears N. 1°45' E., 17.055 chs. dist.</p> <p>From this same point, the calculated P.O.C., bears S. 0°03' E., 2.892 chs. dist.</p>								
40.48	<p>Point for the 1/4 sec. cor. of secs. 4 and 9, at proportionate dist., there is no remaining evidence of the orig. cor.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 20 ins. in the ground, in a mound of stone, 2 1/2 ft. base, to top, with brass cap mkd.</p> <div style="text-align: center;"> <table style="margin-left: auto; margin-right: auto;"> <tr><td>T 23 N</td><td>R 18 E</td></tr> <tr><td>S 4</td><td></td></tr> <tr><td>1/4</td><td>—</td></tr> <tr><td>S 9</td><td></td></tr> </table> <p>2007</p> </div> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p>	T 23 N	R 18 E	S 4		1/4	—	S 9	
T 23 N	R 18 E								
S 4									
1/4	—								
S 9									

**Dependent Resurvey of the Subdivisional Lines,  
T. 23 N., R. 18 E., Gila and Salt River Meridian, Arizona**

CHAINS	
80.96	<p>The cor. of secs. 4, 5, 8 and 9.</p> <hr/> <p>N. 0°53' E., bet. secs. 4 and 5.</p> <p>Ascending over rolling land.</p>
40.04	<p>Point for the 1/4 sec. cor. of secs. 4 and 5, at proportionate dist., there is no remaining evidence of the orig. cor.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T 23 N R 18 E 1/4 S 5   S 4  2007</p> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p> <p>Set a steel fence post, alongside and W. of the cor.</p>
46.60	<p>Graded road, 25 ft. wide, bears N. 55° E. and S. 55° W.</p>
79.80	<p>The cor. of secs. 4, 5, 32 and 33, on the N. bdy. of the Tp., hereinbefore described.</p> <hr/> <p>From the cor. of secs. 5, 6, 31 and 32, on the S. bdy. of the Tp., hereinbefore described.</p> <p>N. 1°56' E., bet. secs. 31 and 32.</p> <p>Over gently rolling land.</p>
39.99	<p>Point for the 1/4 sec. cor. of secs. 31 and 32, at proportionate dist., there is no remaining evidence of the orig. cor.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 27 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T 23 N R 18 E 1/4 S 31   S 32  2007</p> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p>

**Dependent Resurvey of the Subdivisional Lines,  
T. 23 N., R. 18 E., Gila and Salt River Meridian, Arizona**

CHAINS									
61.81	Center of pavement, BIA Route N15, asphalt surfaced, 24 ft. wide, bears N. 49°29' E. and S. 49°29' W.								
71.33	Midpoint bet. two, Transwestern Pipeline Co., underground gas lines, bears N. 69°11' E. and S. 69°11' W.								
79.98	Point for the cor. of secs. 29, 30, 31 and 32, at proportionate dist., there is no remaining evidence of the orig. cor.  Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 25 ins. in the ground, with brass cap mkd.  <div style="text-align: center;"> <table style="margin: auto;"> <tr><td>T 23 N</td><td>R 18 E</td></tr> <tr><td>S 30</td><td>S 29</td></tr> <tr><td>S 31</td><td>S 32</td></tr> </table> <p>2007</p> </div> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p> <p>Set a steel fence post, alongside and W. of the cor.</p> <hr/> <p>From the cor. of secs. 28, 29, 32 and 33.</p> <p>N. 89°43' W., bet. secs. 29 and 32.</p> <p>Over nearly level land.</p>	T 23 N	R 18 E	S 30	S 29	S 31	S 32		
T 23 N	R 18 E								
S 30	S 29								
S 31	S 32								
39.66	Point for the 1/4 sec. cor. of secs. 29 and 32, at proportionate dist., there is no remaining evidence of the orig. cor.  Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 22 ins. in the ground, with brass cap mkd.  <div style="text-align: center;"> <table style="margin: auto;"> <tr><td>T 23 N</td><td>R 18 E</td></tr> <tr><td>S 29</td><td></td></tr> <tr><td>1/4</td><td>—</td></tr> <tr><td>S 32</td><td></td></tr> </table> <p>2007</p> </div> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p> <p>Set a steel fence post, alongside and W. of the cor.</p>	T 23 N	R 18 E	S 29		1/4	—	S 32	
T 23 N	R 18 E								
S 29									
1/4	—								
S 32									
46.13	Midpoint bet. two, El Paso Natural Gas Co., underground gas lines, bears S. 20°25' E. and N 20°25' W.								
57.16	Midpoint bet. two, Transwestern Pipeline Co., underground gas lines, bears N. 69°09' E. and S. 69°09' W.								

**Dependent Resurvey of the Subdivisional Lines,  
T. 23 N., R. 18 E., Gila and Salt River Meridian, Arizona**

CHAINS	
58.80	Center of pavement, BIA Route N15, asphalt surfaced, 24 ft. wide, bears N. 49°29' E. and S. 49°29' W.
79.33	The cor. of secs. 29, 30, 31 and 32. <hr/>
	N. 88°37' W., bet. secs. 30 and 31.  Ascending over S. facing slopes of Pyramid Butte.
17.08	Midpoint bet. four, El Paso Natural Gas Co., underground gas lines, bears N. 71°09' E. and S. 71°09' W.
39.49	The 1/4 sec. cor. of secs. 30 and 31, monumented with a basalt stone, 11 x 6 x 6 ins., lying loose, mkd. 1/4 on exposed face, with a mound of stone, 1 ft. base, 1/2 ft. high to N.  At the corner point  Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 17 ins. in the ground, in a mound of stone, 4 ft. base, to top, with brass cap mkd.  T 23 N R 18 E S 30 1/4 ——— S 31  2007  Deposit a magnet, in a white plastic case, at the base of the stainless steel post, and destroy the accessory mound of stone.  A basalt stone, 10 x 10 x 9 ins., mkd. 1/4 on an exposed face was found lying loose nearby.  Bury both stones alongside the stainless steel post.  Cor. is located on S. facing slope of pyramid Butte. <hr/>
40.15	S. 89°18' W., beginning new measurement.  The cor. of secs. 25, 30, 31 and 36, on the W. bdy. of the Tp., hereinbefore described. <hr/>
	From the cor. of secs. 29, 30, 31 and 32.  N. 0°57' W., bet. secs. 29 and 30.  Over gently rolling land.

**Dependent Resurvey of the Subdivisional Lines,  
T. 23 N., R. 18 E., Gila and Salt River Meridian, Arizona**

CHAINS	
6.20	Midpoint bet. four, El Paso Natural Gas Co., underground gas lines, bears N. 71°09' E. and S. 71°09' W.
39.98	<p>Point for the 1/4 sec. cor. of secs. 29 and 30, at proportionate dist., there is no remaining evidence of the orig. cor.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 25 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T 23 N R 18 E 1/4 S 30   S 29</p> <p style="text-align: center;">2007</p> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p> <p>Set a steel fence post, alongside and W. of the cor.</p> <p>From this cor. point, a wood post, 3 ins. sq., firmly set, projecting 12 ins. above ground, mkd. 4A on the W. face, bears N. 32°52' E., 1.54 chs. dist. This monument is irreconcilable with found orig. cors., and is not utilized in the course of this resurvey.</p>
58.90	Graded road, 25 ft. wide, bears S. 50° E. and N. 50° W.
59.97	<p>Point for the N. 1/16 sec. cor. of secs. 29 and 30.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T 23 N R 18 E N 1/16 S 30   S 29</p> <p style="text-align: center;">2007</p> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p> <p>Set a steel fence post, alongside and W. of the cor.</p>
79.96	<p>Point for the cor. of secs. 19, 20, 29 and 30, at proportionate dist., there is no remaining evidence of the orig. cor.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 25 ins. in the ground, with brass cap mkd.</p>

**Dependent Resurvey of the Subdivisional Lines,  
T. 23 N., R. 18 E., Gila and Salt River Meridian, Arizona**

CHAINS	
	T 23 N R 18 E S 19   S 20 S 30   S 29  2007
	Deposit a magnet, in a white plastic case, at the base of the stainless steel post.  Set a steel fence post, alongside and W. of the cor.
	<hr/> From the cor. of secs. 20, 21, 28 and 29.  S. 88°57' W., bet. secs. 20 and 29.  Over rolling land.
39.52	The 1/4 sec. cor. of secs. 20 and 29, monumented with a fractured basalt stone, 8 x 8 x 8 ins., loosely set, projecting 6 ins. above ground, mkd. 1/4 on the N. face, set in an embedded mound of stone.  At the corner point  Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 20 ins. in the ground, in a mound of stone, 3 1/2 ft. base, to top, with brass cap mkd.
	T 23 N R 18 E S 20 1/4 ——— S 29  2007
	Deposit a magnet, in a white plastic case, at the base of the stainless steel post.  Incorporate the marked stone, within the mound of stone.
	<hr/> N. 88°38' W., beginning new measurement.
40.58	The cor. of secs. 19, 20, 29 and 30.
	<hr/> N. 89°42' W., bet. secs. 19 and 30.  Over broken and rolling land.
7.76	From this point, Chandler Springs(1), bears N., 4.25 chs. dist., located in the middle of a dirt stock tank, 47 ft. x 38 ft.



**Dependent Resurvey of the Subdivisional Lines,  
T. 23 N., R. 18 E., Gila and Salt River Meridian, Arizona**

CHAINS	
20.275	<p>Point for the E. 1/16 sec. cor. of secs. 19 and 30.</p> <p>Not monumented.</p>
40.55	<p>Point for the 1/4 sec. cor. of secs. 19 and 30, at proportionate dist., there is no remaining evidence of the orig. cor.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 20 ins. in the ground, in a mound of stone, 2 1/2 ft. base, to top, with brass cap mkd.</p> <div style="text-align: center;"> <p>T 23 N R 18 E</p> <p>S 19</p> <p>1/4 ———</p> <p>S 30</p> <p>2007</p> </div> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p> <p>Set a steel fence post, alongside and N. of the cor.</p>
52.73	<p>From this point, Chandler Springs(2), bears S., 3.90 chs. dist., encased in a concrete box, 7 1/2 x 7 1/2 x 4 1/2 ft. high.</p>
60.825	<p>Point for the W. 1/16 sec. cor. of secs. 19 and 30.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center;"> <p>T 23 N R 18 E</p> <p>S 19</p> <p>W 1/16 ———</p> <p>S 30</p> <p>2007</p> </div> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p> <p>Set a steel fence post, alongside and N. of the cor.</p>
69.70	<p>Graded road, 25 ft. wide, bears N. 55° W. and S. 55° E.</p>
78.26	<p>The cor. of secs. 19, 24, 25 and 30, on the W. bdy. of the Tp., hereinbefore described.</p> <hr/> <p>From the cor. of secs. 19, 20, 29 and 30.</p> <p>N. 0°59' W., bet. secs. 19 and 20.</p>

**Dependent Resurvey of the Subdivisional Lines,  
T. 23 N., R. 18 E., Gila and Salt River Meridian, Arizona**

CHAINS							
39.98	<p>Over rolling and broken land.</p> <p>Point for the 1/4 sec. cor. of secs. 19 and 20, at proportionate dist., there is no remaining evidence of the orig. cor.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 25 ins. in the ground, in a collar of stone, with brass cap mkd.</p> <div style="text-align: center; margin: 10px 0;"> <table style="margin: auto; border-collapse: collapse;"> <tr><td>T 23 N</td><td>R 18 E</td></tr> <tr><td colspan="2" style="text-align: center;">1/4</td></tr> <tr><td>S 19</td><td style="border-left: 1px solid black; border-right: 1px solid black;">S 20</td></tr> </table> <p>2007</p> </div> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p>	T 23 N	R 18 E	1/4		S 19	S 20
T 23 N	R 18 E						
1/4							
S 19	S 20						
79.96	<p>Point for the cor. of secs. 17, 18, 19 and 20, at proportionate dist., there is no remaining evidence of the orig. cor.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 20 ins. in the ground, in a mound of stone, 2 1/2 ft. base, to top, with brass cap mkd.</p> <div style="text-align: center; margin: 10px 0;"> <table style="margin: auto; border-collapse: collapse;"> <tr><td>T 23 N</td><td>R 18 E</td></tr> <tr><td>S 18</td><td style="border-left: 1px solid black; border-right: 1px solid black;">S 17</td></tr> <tr><td>S 19</td><td style="border-left: 1px solid black; border-right: 1px solid black;">S 20</td></tr> </table> <p>2007</p> </div> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p> <p>Set a steel fence post, alongside and W. of the cor.</p> <hr style="width: 50%; margin: 10px auto;"/> <p>From the cor. of secs. 16, 17, 20 and 21.</p> <p>N. 89°55' W., bet. secs. 17 and 20.</p> <p>Over gently rolling land.</p>	T 23 N	R 18 E	S 18	S 17	S 19	S 20
T 23 N	R 18 E						
S 18	S 17						
S 19	S 20						
39.67	<p>Point for the 1/4 sec. cor. of secs. 17 and 20, at proportionate dist., there is no remaining evidence of the orig. cor.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 22 ins. in the ground, with brass cap mkd.</p>						

**Dependent Resurvey of the Subdivisional Lines,  
T. 23 N., R. 18 E., Gila and Salt River Meridian, Arizona**

CHAINS	
	T 23 N R 18 E S 17 1/4 ——— S 20  2007
	Deposit a magnet, in a white plastic case, at the base of the stainless steel post.
	Set a steel fence post, alongside and N. of the cor.
79.34	The cor. of secs. 17, 18, 19 and 20.  <hr/> N. 89°43' W., bet. secs. 18 and 19.  Over broken and rolling land.
39.88	Point for the 1/4 sec. cor. of secs. 18 and 19, at proportionate dist., there is no remaining evidence of the orig. cor.  Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.
	T 23 N R 18 E S 18 1/4 ——— S 19  2007
	Deposit a magnet, in a white plastic case, at the base of the stainless steel post.
	Set a steel fence post, alongside and N. of the cor.
76.84	The cor. of secs. 13, 18, 19 and 24, on the W. bdy. of the Tp., hereinbefore described.  <hr/> From the cor. of secs. 17, 18, 19 and 20.  N. 0°46' E., bet. secs. 17 and 18.  Over broken and rolling land.
39.97	Point for the 1/4 sec. cor. of secs. 17 and 18, at proportionate dist., there is no remaining evidence of the orig. cor.  Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 27 ins. in the ground, with brass cap mkd.

**Dependent Resurvey of the Subdivisional Lines,  
T. 23 N., R. 18 E., Gila and Salt River Meridian, Arizona**

CHAINS	
	T 23 N R 18 E 1/4 S 18   S 17  2007
	Deposit a magnet, in a white plastic case, at the base of the stainless steel post.
	Set a steel fence post, alongside and W. of the cor.
79.94	Point for the cor. of secs. 7, 8, 17 and 18, at proportionate dist., there is no remaining evidence of the orig. cor.
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.
	T 23 N R 18 E S 7   S 8 S 18   S 17  2007
	Deposit a magnet, in a white plastic case, at the base of the stainless steel post.
	Set a steel fence post, alongside and W. of the cor.
	From this cor. point, the NE cor. of a wood house, (40 x 28 ft.), bears S. 81°37' W., 14.26 chs. dist., the long side bears S. 10° W.
	From this same cor. point, the most NE cor. of a wood Hogan, (15 ft. across), bears N. 85°31' W., 14.25 chs. dist.
	<hr/> From the cor. of secs. 8, 9, 16 and 17.
	S. 89°59' W., bet. secs. 8 and 17.
	Over gently rolling land.
40.44	Point for the 1/4 sec. cor. of secs. 8 and 17, at proportionate dist., there is no remaining evidence of the orig. cor.
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.

**Dependent Resurvey of the Subdivisional Lines,  
T. 23 N., R. 18 E., Gila and Salt River Meridian, Arizona**

CHAINS	
	T 23 N R 18 E S 8 1/4 ——— S 17  2007
	Deposit a magnet, in a white plastic case, at the base of the stainless steel post.
	Set a steel fence post, alongside and N. of the cor.
80.88	The cor. of secs. 7, 8, 17 and 18. <hr/> N. 89°45' W., bet. secs. 7 and 18.  Over broken and rolling land.
40.50	Point for the 1/4 sec. cor. of secs. 7 and 18, at proportionate dist., there is no remaining evidence of the orig. cor.  Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.
	T 23 N R 18 E S 7 1/4 ——— S 18  2007
	Deposit a magnet, in a white plastic case, at the base of the stainless steel post.
	Set a steel fence post, alongside and N. of the cor.
71.60	Graded road, 25 ft. wide, bears N. 60° E. and S. 60° W.
77.75	Underground water line, bears N. 65° E. and S. 65° W.
77.87	The cor. of secs. 7, 12, 13 and 18, on the W. bdy. of the Tp., hereinbefore described. <hr/> From the cor. of secs. 7, 8, 17 and 18.  North, bet. secs. 7 and 8.  Over broken and rolling land.
39.97	Point for the 1/4 sec. cor. of secs. 7 and 8, at proportionate dist., there is no remaining evidence of the orig. cor.

**Dependent Resurvey of the Subdivisional Lines,  
T. 23 N., R. 18 E., Gila and Salt River Meridian, Arizona**

CHAINS	
	<p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 25 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T 23 N R 18 E 1/4 S 7   S 8</p> <p style="text-align: center;">2007</p> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p> <p>Set a steel fence post, alongside and W. of the cor.</p>
49.85	Graded road, 25 ft. wide, bears N. 45° E. and S. 45° W.
79.94	<p>Point for the cor. of secs. 5, 6, 7 and 8, at proportionate dist., there is no remaining evidence of the orig. cor.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T 23 N R 18 E S 6   S 5 S 7   S 8</p> <p style="text-align: center;">2007</p> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p> <p>Set a steel fence post, alongside and W. of the cor.</p> <hr/> <p>From the cor. of secs. 4, 5, 8 and 9.</p> <p>S. 89°54' W., bet. secs. 5 and 8.</p> <p>Over rolling land.</p>
40.48	<p>Point for the 1/4 sec. cor. of secs. 5 and 8, at proportionate dist., there is no remaining evidence of the orig. cor.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T 23 N R 18 E S 5 1/4 ——— S 8</p> <p style="text-align: center;">2007</p>

**Dependent Resurvey of the Subdivisional Lines,  
T. 23 N., R. 18 E., Gila and Salt River Meridian, Arizona**

CHAINS	
	<p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p> <p>Set a steel fence post, alongside and N. of the cor.</p>
52.40	Graded road, 25 ft. wide, bears N. 45° E. and S. 45° W.
80.96	The cor. of secs. 5, 6, 7 and 8.
	<hr/> <p>N. 89°47' W., bet. secs. 6 and 7.</p> <p>Over rolling land.</p>
13.85	Underground water line, bears N. 25° E. and S. 25° W.
40.57	Point for the 1/4 sec. cor. of secs. 6 and 7, at proportionate dist., there is no remaining evidence of the orig. cor.
	<p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 23 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T 23 N R 18 E S 6 1/4 ——— S 7</p> <p style="text-align: center;">2007</p>
	<p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p> <p>Set a steel fence post, alongside and N. of the cor.</p>
77.82	The cor. of secs. 1, 6, 7 and 12, on the W. bdy. of the Tp., hereinbefore described.
	<hr/> <p>From the cor. of secs. 5, 6, 7 and 8.</p> <p>N. 0°23' E., bet. secs. 5 and 6.</p> <p>Over gently rolling land.</p>
31.50	Underground water line, bears N. 25° E. and S. 25° W.
39.97	Point for the 1/4 sec. cor. of secs. 5 and 6, at proportionate dist., there is no remaining evidence of the orig. cor.
	<p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with brass cap mkd.</p>

**Dependent Resurvey of the Subdivisional Lines,  
T. 23 N., R. 18 E., Gila and Salt River Meridian, Arizona**

CHAINS	
	<p align="center">T 23 N R 18 E 1/4 S 6   S 5  2007</p>
80.18	<p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p> <p>The cor. of secs. 5, 6, 31 and 32, on the N. bdy. of the Tp., hereinbefore described.</p>
	<hr/> <p align="center"><b>Subdivision of Section 1, T. 23 N., R. 18 E., Gila and Salt River Meridian, Arizona</b></p> <hr/> <p>From the 1/4 sec. cor. of secs. 1 and 12.</p> <p>N. 3°55' E., on the N. and S. center line of sec. 1.</p> <p>Ascending, over easterly slopes of Shonto Butte.</p>
40.28	<p>Point for the center 1/4 sec. cor. of sec. 1, at intersection with the E. and W. center line.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 15 ins. in the ground, in a mound of stone, 4 ft. base, to top, with brass cap mkd.</p>
	<p align="center">T 23 N R 18 E C 1/4 S 1  2007</p> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p> <p>Cor. is located on a N. facing slope of Shonto Butte.</p>
80.71	<p>The 1/4 sec. cor. of secs. 1 and 36.</p> <hr/> <p>From the 1/4 sec. cor. of secs. 1 and 6, monumented with a stainless steel post, 2 1/2 ins. diam., firmly set, projecting 10 ins. above ground, in a mound of stone, 5 ft. base, to top, with brass cap mkd. T23N R18E R19E 1/4 S1 S6 2004. Add the marks 2007 to the brass cap.</p>



**Subdivision of Section 1,  
T. 23 N., R. 18 E., Gila and Salt River Meridian, Arizona**

CHAINS	
	N. 89°50' W., on the E. and W. center line of sec. 1.
39.35	The center 1/4 sec. cor. of sec. 1.
78.71	The 1/4 sec. cor. of secs. 1 and 2.
<hr/> <p><b>Subdivision of Section 2, T. 23 N., R. 18 E., Gila and Salt River Meridian, Arizona</b></p> <hr/>	
	From the 1/4 sec. cor. of secs. 2 and 11.
	N. 3°39' E., on the N. and S. center line of sec. 2.
	Ascending, over Shonto Butte.
41.68	Point for the center 1/4 sec. cor. of sec. 2, at intersection with the E. and W. center line.
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 20 ins. in the ground, in a mound of stone, 4 ft. base, to top, with brass cap mkd.
	T 23 N R 18 E C 1/4 S 2  2007
	Deposit a magnet, in a white plastic case, at the base of the stainless steel post.
	Set a steel fence post, alongside and W. of the cor.
	Cor. is located on a NW facing slope, within the N. slopes of Shonto Butte.
83.08	The 1/4 sec. cor. of secs. 2 and 35.
	From the 1/4 sec. cor. of secs. 1 and 2.
	S. 87°45' W., on the E. and W. center line of sec. 2.
	Over north facing slopes of Shonto Butte.

**Subdivision of Section 2,  
T. 23 N., R. 18 E., Gila and Salt River Meridian, Arizona**

CHAINS	
39.54	The center 1/4 sec. cor. of sec. 2.
79.70	The true point for the 1/4 sec. cor. of secs. 2 and 3.
<hr/> <p><b>Subdivision of Section 3, T. 23 N., R. 18 E., Gila and Salt River Meridian, Arizona</b></p> <hr/>	
	From the 1/4 sec. cor. of secs. 3 and 10.
	N. 2°03' E., on the N. and S. center line of sec. 3.
	Over the westerly foothills of Shonto Butte.
43.25	Point for the center 1/4 sec. cor. of sec. 3, at intersection with the E. and W. center line.
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 25 ins. in the ground, with brass cap mkd.
	T 23 N R 18 E C 1/4 S 3
	2007
	Deposit a magnet, in a white plastic case, at the base of the stainless steel post.
	Set a steel fence post, alongside and W. of the cor.
85.44	The 1/4 sec. cor. of secs. 3 and 34.
	From the true point for the 1/4 sec. cor. of secs. 2 and 3.
	N. 88°38' W., on the E. and W. center line of sec. 3.
38.60	Underground water line, bears S. 2° E. and N. 2° W.
40.40	The center 1/4 sec. cor. of sec. 3.
80.72	The 1/4 sec. cor. of secs. 3 and 4.
<hr/> <p><b>Subdivision of Section 4, T. 23 N., R. 18 E., Gila and Salt River Meridian, Arizona</b></p> <hr/>	
	From the 1/4 sec. cor. of secs. 4 and 9.
	N. 1°08' E., on the N. and S. center line of sec. 4.

**Subdivision of Section 4,  
T. 23 N., R. 18 E., Gila and Salt River Meridian, Arizona**

CHAINS	
	Over gently rolling land.
40.87	Point for the center 1/4 sec. cor. of sec. 4, at intersection with the E. and W. center line.  Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.  T 23 N R 18 E C 1/4 S 4  2007  Deposit a magnet, in a white plastic case, at the base of the stainless steel post.  Set a steel fence post, alongside and W. of the cor.
81.41	The 1/4 sec. cor. of secs. 4 and 33. <hr/> From the 1/4 sec. cor. of secs. 3 and 4. N. 88°44' W., on the E. and W. center line of sec. 4.
15.87	Center of pavement, Arizona State Highway No. 87, asphalt surfaced, 28 ft. wide, bears N. 4°46' E. and S. 4°46' W.
40.64	The center 1/4 sec. cor. of sec. 4.
81.29	The 1/4 sec. cor. of secs. 4 and 5. <hr/>
	<b>Subdivision of Section 5, T. 23 N., R. 18 E., Gila and Salt River Meridian, Arizona</b>
	From the 1/4 sec. cor. of secs. 5 and 8. N. 0°38' E., on the N. and S. center line of sec. 5.  Over nearly level land.
11.65	Graded road, 25 ft. wide, bears N. 45° E. and S. 45° W.
40.01	Point for the center 1/4 sec. cor. of sec. 5, at intersection with the E. and W. center line.  Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.

**Subdivision of Section 5,  
T. 23 N., R. 18 E., Gila and Salt River Meridian, Arizona**

CHAINS	
	T 23 N R 18 E C 1/4 S 5  2007
	Deposit a magnet, in a white plastic case, at the base of the stainless steel post.
	Set a steel fence post, alongside and W. of the cor.
79.99	The 1/4 sec. cor. of secs. 5 and 32. <hr/>
	From the 1/4 sec. cor. of secs. 4 and 5.
	S. 89°51' W., on the E. and W. center line of sec. 5.
8.90	Graded road, 25 ft. wide, bears N. 55° E. and S. 55° W.
40.65	The center 1/4 sec. cor. of sec. 5.
81.30	The 1/4 sec. cor. of secs. 5 and 6. <hr/>
	<b>Subdivision of Section 6, T. 23 N., R. 18 E., Gila and Salt River Meridian, Arizona</b> <hr/>
	From the 1/4 sec. cor. of secs. 6 and 7.
	N. 0°12' E., on the N. and S. center line of sec. 6.
	Over gently rolling land.
40.02	Point for the center 1/4 sec. cor. of sec. 6, at intersection with the E. and W. center line.
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.
	T 23 N R 18 E C 1/4 S 6  2007
	Deposit a magnet, in a white plastic case, at the base of the stainless steel post.
	Set a steel fence post, alongside and W. of the cor.
80.15	The 1/4 sec. cor. of secs. 6 and 31. <hr/>

**Subdivision of Section 6,  
T. 23 N., R. 18 E., Gila and Salt River Meridian, Arizona**

CHAINS	
	From the 1/4 sec. cor. of secs. 5 and 6.
	N. 89°43' W., on the E. and W. center line of sec. 6.
40.69	The center 1/4 sec. cor. of sec. 6.
77.97	The 1/4 sec. cor. of secs. 1 and 6.
<hr/>	
<b>Subdivision of Section 7, T. 23 N., R. 18 E., Gila and Salt River Meridian, Arizona</b>	
<hr/>	
	From the 1/4 sec. cor. of secs. 7 and 18.
	N. 0°03' W., on the N. and S. center line of sec. 7.
	Over rolling and broken land.
16.55	Graded road, 25 ft. wide, bears N. 55° E. and S. 60° W.
20.50	Underground waterline, bears N. 25° E. and S. 25° W.
39.96	Point for the center 1/4 sec. cor. of sec. 7, at intersection with the E. and W. center line.
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.
	T 23 N R 18 E C 1/4 S 7
	2007
	Deposit a magnet, in a white plastic case, at the base of the stainless steel post.
	Set a steel fence post, alongside and W. of the cor.
79.92	The 1/4 sec. cor. of secs. 6 and 7.
<hr/>	
	From the 1/4 sec. cor. of secs. 7 and 8.
	N. 89°46' W., on the E. and W. center line of sec. 7.
9.60	Graded road, 25 ft. wide, bears N. 45° E. and S. 45° W.
31.75	Underground waterline, bears N. 25° E. and S. 25° W.
40.54	The center 1/4 sec. cor. of sec. 7.

**Subdivision of Section 7,  
T. 23 N., R. 18 E., Gila and Salt River Meridian, Arizona**

CHAINS	
77.85	The 1/4 sec. cor. of secs. 7 and 12.
	<hr/> <b>Subdivision of Section 8, T. 23 N., R. 18 E., Gila and Salt River Meridian, Arizona</b> <hr/>
	From the 1/4 sec. cor. of secs. 8 and 17.
	N. 0°02' E., on the N. and S. center line of sec. 8.
	Over rolling and broken land.
40.00	Point for the center 1/4 sec. cor. of sec. 8, at intersection with the E. and W. center line.
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 27 ins. in the ground, with brass cap mkd.
	T 23 N R 18 E C 1/4 S 8  2007
	Deposit a magnet, in a white plastic case, at the base of the stainless steel post.
	Set a steel fence post, alongside and W. of the cor.
80.01	The 1/4 sec. cor. of secs. 5 and 8.
	<hr/>
	From the 1/4 sec. cor. of secs. 8 and 9.
	S. 89°56' W., on the E. and W. center line of sec. 8.
40.46	The center 1/4 sec. cor. of sec. 8.
80.91	The 1/4 sec. cor. of secs. 7 and 8.
	<hr/> <b>Subdivision of Section 9, T. 23 N., R. 18 E., Gila and Salt River Meridian, Arizona</b> <hr/>
	From the 1/4 sec. cor. of secs. 9 and 16.
	N. 0°03' E., on the N. and S. center line of sec. 9.
	Over rolling and broken land.
40.94	Point for the center 1/4 sec. cor. of sec. 9, at intersection with the E. and W. center line.

**Subdivision of Section 9,  
T. 23 N., R. 18 E., Gila and Salt River Meridian, Arizona**

CHAINS	
	<p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T 23 N R 18 E C 1/4 S 9</p> <p style="text-align: center;">2007</p> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p> <p>Set a steel fence post, alongside and W. of the cor.</p>
81.88	<p>The 1/4 sec. cor. of secs. 4 and 9.</p> <hr/> <p>From the 1/4 sec. cor. of secs. 9 and 10.</p> <p>N. 86°18' W., on the E. and W. center line of sec. 9.</p>
16.21	<p>Center of pavement, Arizona State Highway No. 87, asphalt surfaced, 28 ft. wide, bears S. 1°47' E. and N. 1°47' W.</p>
40.55	<p>The center 1/4 sec. cor. of sec. 9.</p>
81.10	<p>The 1/4 sec. cor. of secs. 8 and 9.</p> <hr/> <p style="text-align: center;"><b>Subdivision of Section 10, T. 23 N., R. 18 E., Gila and Salt River Meridian, Arizona</b></p> <hr/> <p>From the 1/4 sec. cor. of secs. 10 and 15.</p> <p>N. 0°12' W., on the N. and S. center line of sec. 10.</p> <p>Over broken and rolling land.</p>
41.04	<p>Point for the center 1/4 sec. cor. of sec. 10, at intersection with the E. and W. center line.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 25 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T 23 N R 18 E C 1/4 S 10</p> <p style="text-align: center;">2007</p> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p>

**Subdivision of Section 10,  
T. 23 N., R. 18 E., Gila and Salt River Meridian, Arizona**

CHAINS	
81.26	<p>Set a steel fence post, alongside and W. of the cor. The 1/4 sec. cor. of secs. 3 and 10.</p> <hr/>
21.35	<p>From the 1/4 sec. cor. of secs. 10 and 11. N. 88°44' W., on the E. and W. center line of sec. 10. Underground water line, bears S. 30° E. and N. 30° W.</p>
40.05	<p>The center 1/4 sec. cor. of sec. 10.</p>
79.99	<p>The 1/4 sec. cor. of secs. 9 and 10.</p> <hr/>
<p><b>Subdivision of Section 11, T. 23 N., R. 18 E., Gila and Salt River Meridian, Arizona</b></p> <hr/>	
40.14	<p>From the 1/4 sec. cor. of secs. 11 and 14. N. 0°01' W., on the N. and S. center line of sec. 11. Ascending over SW facing slopes of Shonto Butte. Point for the center 1/4 sec. cor. of sec. 11, at intersection with the E. and W. center line. Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 23 ins. in the ground, in a collar of stone, with brass cap mkd.</p> <p style="text-align: center;">T 23 N R 18 E C 1/4 S 11</p> <p style="text-align: center;">2007</p> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p>
80.28	<p>Set a steel fence post, alongside and W. of the cor. The 1/4 sec. cor. of secs. 2 and 11.</p> <hr/>
39.38	<p>From the 1/4 sec. cor. of secs. 11 and 12. S. 85°20' W., on the E. and W. center line of sec. 11. The center 1/4 sec. cor. of sec. 11.</p>



**Subdivision of Section 11,  
T. 23 N., R. 18 E., Gila and Salt River Meridian, Arizona**

CHAINS	
78.76	<p>The 1/4 sec. cor. of secs. 10 and 11.</p> <hr/> <p style="text-align: center;"><b>Subdivision of Section 12, T. 23 N., R. 18 E., Gila and Salt River Meridian, Arizona</b></p> <hr/> <p>From the 1/4 sec. cor. of secs. 12 and 13.</p> <p>N. 0°40' E., on the N. and S. center line of sec. 12.</p> <p>Ascending over SW facing slopes of Shonto Butte.</p>
39.80	<p>Point for the center 1/4 sec. cor. of sec. 12, at intersection with the E. and W. center line.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 23 ins. in the ground, in a collar of stone, with brass cap mkd.</p> <p style="text-align: center;">T 23 N R 18 E C 1/4 S 12</p> <p style="text-align: center;">2007</p> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p> <p>Set a steel fence post, alongside and W. of the cor.</p> <p>From this cor. point, Shonto Springs bears N. 40°02' W., 11.02 chs. dist., a 3 x 3 ft., concrete slab, enclosing well head.</p>
79.60	<p>The 1/4 sec. cor. of secs. 1 and 12.</p> <hr/> <p>From the 1/4 sec. cor. of secs. 7 and 12, monumented with a stainless steel post, 2 1/2 ins. diam., firmly set, projecting 12 ins. above ground, in a mound of stone, 4 ft. base, to top, with brass cap mkd. T23N R18E R19E 1/4 S12 S7 2004. Add the marks 2007 to the brass cap.</p> <p>N. 89°59' W., on the E. and W. center line of sec. 12.</p>
39.06	<p>The center 1/4 sec. cor. of sec. 12.</p>
78.12	<p>The 1/4 sec. cor. of secs. 11 and 12.</p> <hr/> <p style="text-align: center;"><b>Subdivision of Section 13, T. 23 N., R. 18 E., Gila and Salt River Meridian, Arizona</b></p> <hr/>

**Subdivision of Section 13,  
T. 23 N., R. 18 E., Gila and Salt River Meridian, Arizona**

CHAINS	
	<p>From the 1/4 sec. cor. of secs. 13 and 24.</p> <p>N. 0°51' E., on the N. and S. center line of sec. 13.</p> <p>Over broken and rolling land.</p>
40.02	<p>Point for the center 1/4 sec. cor. of sec. 13, at intersection with the E. and W. center line.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 20 ins. in the ground, in a mound of stone, 3 ft. base, to top, with brass cap mkd.</p> <p style="text-align: center;">T 23 N R 18 E C 1/4 S 13</p> <p style="text-align: center;">2007</p> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p>
48.60	Underground water line, bears S. 75° E. and N. 75° W.
80.03	<p>The 1/4 sec. cor. of secs. 12 and 13.</p> <hr/> <p>From the 1/4 sec. cor. of secs. 13 and 18, monumented with a stainless steel post, 2 1/2 ins. diam., firmly set, projecting 3 ins. above ground, with brass cap mkd. T23N R18E R19E 1/4 S13 S18 2004, and witnessed by a steel fence post, set nearby and N. of the cor. Add the marks 2007 to the brass cap.</p> <p>S. 89°37' W., on the E. and W. center line of sec. 13.</p>
11.75	Underground water line, bears S. 25° E. and N. 25° W.
39.29	The center 1/4 sec. cor. of sec. 13.
78.58	The 1/4 sec. cor. of secs. 13 and 14.
<p><b>Subdivision of Section 14, T. 23 N., R. 18 E., Gila and Salt River Meridian, Arizona</b></p> <hr/>	
	<p>From the 1/4 sec. cor. of secs. 14 and 23.</p> <p>N. 2°08' E., on the N. and S. center line of sec. 14.</p> <p>Over broken and rolling land.</p>
39.66	Point for the center 1/4 sec. cor. of sec. 14, at intersection with the E. and W. center line.

**Subdivision of Section 14,  
T. 23 N., R. 18 E., Gila and Salt River Meridian, Arizona**

CHAINS	
	<p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 22 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T 23 N R 18 E C 1/4 S 14</p> <p style="text-align: center;">2007</p> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p> <p>Set a steel fence post, alongside and W. of the cor.</p>
72.30	Underground water line, bears S. 75° E. and N. 75° W.
79.33	The 1/4 sec. cor. of secs. 11 and 14.
	<hr/> <p>From the 1/4 sec. cor. of secs. 13 and 14.</p> <p>S. 85°48' W., on the E. and W. center line of sec. 14.</p>
39.54	The center 1/4 sec. cor. of sec. 14.
79.08	The 1/4 sec. cor. of secs. 14 and 15.
	<hr/> <p style="text-align: center;"><b>Subdivision of Section 15, T. 23 N., R. 18 E., Gila and Salt River Meridian, Arizona</b></p> <hr/>
	<p>From the 1/4 sec. cor. of secs. 15 and 22.</p> <p>N. 2°38' E., on the N. and S. center line of sec. 15.</p> <p>Over gently rolling land.</p>
39.27	<p>Point for the center 1/4 sec. cor. of sec. 15, at intersection with the E. and W. center line.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 21 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T 23 N R 18 E C 1/4 S 15</p> <p style="text-align: center;">2007</p> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p> <p>Set a steel fence post, alongside and W. of the cor.</p>

**Subdivision of Section 15,  
T. 23 N., R. 18 E., Gila and Salt River Meridian, Arizona**

CHAINS	
78.54	<p>The 1/4 sec. cor. of secs. 10 and 15.</p> <hr/> <p>From the 1/4 sec. cor. of secs. 14 and 15. N. 89°53' W., on the E. and W. center line of sec. 15.</p>
40.07	The center 1/4 sec. cor. of sec. 15.
80.15	The 1/4 sec. cor. of secs. 15 and 16.
<p><b>Subdivision of Section 16, T. 23 N., R. 18 E., Gila and Salt River Meridian, Arizona</b></p> <hr/>	
	<p>From the 1/4 sec. cor. of secs. 16 and 21. N. 2°14' E., on the N. and S. center line of sec. 16. Over gently rolling land.</p>
39.66	<p>Point for the center 1/4 sec. cor. of sec. 16, at intersection with the E. and W. center line.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 25 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T 23 N R 18 E C 1/4 S 16</p> <p style="text-align: center;">2007</p> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p> <p>Set a steel fence post, alongside and W. of the cor.</p>
79.32	<p>The 1/4 sec. cor. of secs. 9 and 16.</p> <hr/> <p>From the 1/4 sec. cor. of secs. 15 and 16. N. 85°35' W., on the E. and W. center line of sec. 16.</p>
11.88	Center of pavement, Arizona State Highway No. 87, asphalt surfaced, 28 ft. wide, bears S. 1°47' E. and N. 1°47' W.
40.38	The center 1/4 sec. cor. of sec. 16.

**Subdivision of Section 16,  
T. 23 N., R. 18 E., Gila and Salt River Meridian, Arizona**

CHAINS	
80.75	The 1/4 sec. cor. of secs. 16 and 17.
<hr/> <p><b>Subdivision of Section 17, T. 23 N., R. 18 E., Gila and Salt River Meridian, Arizona</b></p> <hr/>	
	From the 1/4 sec. cor. of secs. 17 and 20.
	N. 1°20' E., on the N. and S. center line of sec. 17.
	Over gently rolling land.
40.02	Point for the center 1/4 sec. cor. of sec. 17, at intersection with the E. and W. center line.
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 22 ins. in the ground, with brass cap mkd.
	T 23 N R 18 E C 1/4 S 17
	2007
	Deposit a magnet, in a white plastic case, at the base of the stainless steel post.
	Set a steel fence post, alongside and W. of the cor.
80.03	The 1/4 sec. cor. of secs. 8 and 17.
<hr/>	
	From the 1/4 sec. cor. of secs. 16 and 17.
	N. 89°58' W., on the E. and W. center line of sec. 17.
40.05	The center 1/4 sec. cor. of sec. 17.
80.10	The 1/4 sec. cor. of secs. 17 and 18.
<hr/> <p><b>Subdivision of Section 18, T. 23 N., R. 18 E., Gila and Salt River Meridian, Arizona</b></p> <hr/>	
	From the 1/4 sec. cor. of secs. 18 and 19.
	N. 0°19' E., on the N. and S. center line of sec. 18.
	Over rolling and broken land.
39.96	Point for the center 1/4 sec. cor. of sec. 18, at intersection with the E. and W. center line.

**Subdivision of Section 18,  
T. 23 N., R. 18 E., Gila and Salt River Meridian, Arizona**

CHAINS	
	<p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T 23 N R 18 E C 1/4 S 18</p> <p style="text-align: center;">2007</p> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p> <p>Set a steel fence post, alongside and W. of the cor.</p>
79.92	<p>The 1/4 sec. cor. of secs. 7 and 18.</p> <hr/> <p>From the 1/4 sec. cor. of secs. 17 and 18.</p> <p>N. 89°44' W., on the E. and W. center line of sec. 18.</p>
40.19	<p>The center 1/4 sec. cor. of sec. 18.</p>
77.36	<p>The 1/4 sec. cor. of secs. 13 and 18.</p> <hr/> <p style="text-align: center;"><b>Subdivision of Section 19, T. 23 N., R. 18 E., Gila and Salt River Meridian, Arizona</b></p> <hr/> <p>From the 1/4 sec. cor. of secs. 19 and 30.</p> <p>N. 0°30' W., on the N. and S. center line of sec. 19.</p> <p>Over rolling and broken land.</p>
39.96	<p>Point for the center 1/4 sec. cor. of sec. 19, at intersection with the E. and W. center line.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 20 ins. in the ground, in a mound of stone, 2 1/2 ft. base, to top, with brass cap mkd.</p> <p style="text-align: center;">T 23 N R 18 E C 1/4 S 19</p> <p style="text-align: center;">2007</p> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p>
79.92	<p>The 1/4 sec. cor. of secs. 18 and 19.</p> <hr/>

**Subdivision of Section 19,  
T. 23 N., R. 18 E., Gila and Salt River Meridian, Arizona**

CHAINS	
	From the 1/4 sec. cor. of secs. 19 and 20. N. 89°43' W., on the E. and W. center line of sec. 19.
40.21	The center 1/4 sec. cor. of sec. 19.
77.55	The 1/4 sec. cor. of secs. 19 and 24.
<hr/> <b>Subdivision of Section 20, T. 23 N., R. 18 E., Gila and Salt River Meridian, Arizona</b> <hr/>	
	From the 1/4 sec. cor. of secs. 20 and 29. N. 1°36' W., on the N. and S. center line of sec. 20. Over gently rolling land.
40.87	Point for the center 1/4 sec. cor. of sec. 20, at intersection with the E. and W. center line.  Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 22 ins. in the ground, with brass cap mkd.  T 23 N R 18 E C 1/4 S 20  2007
80.89	Deposit a magnet, in a white plastic case, at the base of the stainless steel post.  The 1/4 sec. cor. of secs. 17 and 20.
	From the 1/4 sec. cor. of secs. 20 and 21. N. 89°52' W., on the E. and W. center line of sec. 20.
39.60	The center 1/4 sec. cor. of sec. 20.
79.71	The 1/4 sec. cor. of secs. 19 and 20.
<hr/> <b>Subdivision of Section 21, T. 23 N., R. 18 E., Gila and Salt River Meridian, Arizona</b> <hr/>	
	From the 1/4 sec. cor. of secs. 21 and 28. N. 1°11' W., on the N. and S. center line of sec. 21.

**Subdivision of Section 21,  
T. 23 N., R. 18 E., Gila and Salt River Meridian, Arizona**

CHAINS	
	Over gently rolling land.
39.64	Point for the center 1/4 sec. cor. of sec. 21, at intersection with the E. and W. center line.  Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 21 ins. in the ground, in a mound of stone, 2 1/2 ft. base, to top, with brass cap mkd.  T 23 N R 18 E C 1/4 S 21  2007  Deposit a magnet, in a white plastic case, at the base of the stainless steel post.
79.28	The 1/4 sec. cor. of secs. 16 and 21. <hr/> From the 1/4 sec. cor. of secs. 21 and 22. N. 86°42' W., on the E. and W. center line of sec. 21.
8.20	Center of pavement, Arizona State Highway No. 87, asphalt surfaced, 28 ft. wide, bears S. 1°47' E. and N. 1°47' W.
39.87	The center 1/4 sec. cor. of sec. 21.
79.74	The 1/4 sec. cor. of secs. 20 and 21. <hr/>
<b>Subdivision of Section 22, T. 23 N., R. 18 E., Gila and Salt River Meridian, Arizona</b>	
	From the 1/4 sec. cor. of secs. 22 and 27. N. 0°27' W., on the N. and S. center line of sec. 22.  Over gently rolling land.
3.62	Midpoint bet. four, El Paso Natural Gas Co., underground gas lines, bears N. 69°36' E. and S. 69°36' W.
39.23	Point for the center 1/4 sec. cor. of sec. 22, at intersection with the E. and W. center line.  Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.



**Subdivision of Section 22,  
T. 23 N., R. 18 E., Gila and Salt River Meridian, Arizona**

CHAINS	
	<p>T 23 N R 18 E C 1/4 S 22</p> <p>2007</p>
	<p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p> <p>Cor. is located 2.10 chs. S. of a wash, 65 ft. wide, 8 ft. deep, drains S. 50° W.</p>
78.45	<p>The 1/4 sec. cor. of secs. 15 and 22.</p> <hr/> <p>From the 1/4 sec. cor. of secs. 22 and 23.</p> <p>N. 89°52' W., on the E. and W. center line of sec. 22.</p>
39.77	<p>The center 1/4 sec. cor. of sec. 22.</p>
79.54	<p>The 1/4 sec. cor. of secs. 21 and 22.</p> <hr/> <p style="text-align: center;"><b>Subdivision of Section 23, T. 23 N., R. 18 E., Gila and Salt River Meridian, Arizona</b></p> <hr/> <p>From the 1/4 sec. cor. of secs. 23 and 26.</p> <p>N. 0°13' E., on the N. and S. center line of sec. 23.</p> <p>Over gently rolling land.</p>
5.40	<p>Midpoint bet. two, Transwestern Pipeline Co., underground gas lines, bears N. 77°03' E. and S. 77°03' W.</p>
27.76	<p>Center of pavement, BIA Route N15, asphalt surfaced, 25 ft. wide, bears N. 69°37' E. and S. 69°37' W.</p>
31.50	<p>Midpoint bet. four, El Paso Natural Gas Co., underground gas lines, bears N. 69°36' E. and S. 69°36' W.</p>
39.64	<p>Point for the center 1/4 sec. cor. of sec. 23, at intersection with the E. and W. center line.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;"> T 23 N R 18 E  C 1/4 S 23  2007 </p>

**Subdivision of Section 23,  
T. 23 N., R. 18 E., Gila and Salt River Meridian, Arizona**

CHAINS	
	Deposit a magnet, in a white plastic case, at the base of the stainless steel post.
	Set a steel fence post, alongside and W. of the cor.
79.27	The 1/4 sec. cor. of secs. 14 and 23.
	From the 1/4 sec. cor. of secs. 23 and 24.
	S. 87°00' W., on the E. and W. center line of sec. 23.
2.47	Center of pavement, BIA Route N15, asphalt surfaced, 25 ft. wide, bears N. 69°37' E. and S. 69°37' W.
14.22	Midpoint bet. four, El Paso Natural Gas Co., underground gas lines, bears N. 69°36' E. and S. 69°36' W.
39.68	The center 1/4 sec. cor. of sec. 23.
79.36	The 1/4 sec. cor. of secs. 22 and 23.
	<b>Subdivision of Section 24, T. 23 N., R. 18 E., Gila and Salt River Meridian, Arizona</b>
	From the 1/4 sec. cor. of secs. 24 and 25.
	N. 0°40' E., on the N. and S. center line of sec. 24.
	Over gently rolling land.
39.48	Midpoint bet. two, Transwestern Pipeline Co., underground gas lines, bears N. 63°08' E. and S. 63°08' W.
40.18	Point for the center 1/4 sec. cor. of sec. 24, at intersection with the E. and W. center line.
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 25 ins. in the ground, with brass cap mkd.
	T 23 N R 18 E C 1/4 S 24
	2007
	Deposit a magnet, in a white plastic case, at the base of the stainless steel post.
53.74	Center of pavement, BIA Route N15, asphalt surfaced, 25 ft. wide, bears N. 72°35' E. and S. 72°35' W.

**Subdivision of Section 24,  
T. 23 N., R. 18 E., Gila and Salt River Meridian, Arizona**

CHAINS	
57.64	Midpoint bet. four, El Paso Natural Gas Co., underground gas lines, bears N. 72°09' E. and S. 72°09' W.
80.35	The 1/4 sec. cor. of secs. 13 and 24. <hr/>
	From the 1/4 sec. cor. of secs. 19 and 24, monumented with a stainless steel post, 2 1/2 ins. diam., firmly set, projecting 5 ins. above ground, with brass cap mkd. T23N R18E R19E 1/4 S24 S19 2004. Add the marks 2007 to the brass cap, and set a steel fence post, nearby and W. of the cor.  S. 89°46' W., on the E. and W. center line of sec. 24.
38.29	Midpoint bet. two, Transwestern Pipeline Co., underground gas lines, bears N. 63°08' E. and S. 63°08' W.
39.68	The center 1/4 sec. cor. of sec. 24.
79.37	The 1/4 sec. cor. of secs. 23 and 24. <hr/>
	<b>Subdivision of Section 25, T. 23 N., R. 18 E., Gila and Salt River Meridian, Arizona</b> <hr/>
	From the 1/4 sec. cor. of secs. 25 and 36.  N. 0°13' E., on the N. and S. center line of sec. 25.  Over broken and rolling land.
40.03	Point for the center 1/4 sec. cor. of sec. 25, at intersection with the E. and W. center line.  Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 25 ins. in the ground, with brass cap mkd.  T 23 N R 18 E C 1/4 S 25  2007
	Deposit a magnet, in a white plastic case, at the base of the stainless steel post.  Cor. is located 30 lks. S. of left bank of Coyote Wash, bears N. 60° E. and S. 55° W.
80.14	The 1/4 sec. cor. of secs. 24 and 25. <hr/>

**Subdivision of Section 25,  
T. 23 N., R. 18 E., Gila and Salt River Meridian, Arizona**

CHAINS	
	<p>From the 1/4 sec. cor. of secs. 25 and 30, monumented with a stainless steel post, 2 1/2 ins. diam., firmly set, projecting 3 ins. above ground, with brass cap mkd. T23N R18E R19E 1/4 S25 S30 2004, and witnessed by a steel fence post, set nearby and N. of the cor. Add the marks 2007 to the brass cap.</p> <p>N. 89°57' W., on the E. and W. center line of sec. 25.</p>
39.41	The center 1/4 sec. cor. of sec. 25.
78.96	The 1/4 sec. cor. of secs. 25 and 26.
<hr/> <p><b>Subdivision of Section 26, T. 23 N., R. 18 E., Gila and Salt River Meridian, Arizona</b></p> <hr/>	
	<p>From the 1/4 sec. cor. of secs. 26 and 35.</p> <p>N. 0°09' E., on the N. and S. center line of sec. 26.</p> <p>Over broken and rolling land.</p>
39.64	<p>Point for the center 1/4 sec. cor. of sec. 26, at intersection with the E. and W. center line.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T 23 N R 18 E C 1/4 S 26</p> <p style="text-align: center;">2007</p> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p> <p>Raise a mound of stone, 3 ft. base, 2 ft. high W. of cor.</p> <p>Set a steel fence post, alongside and N. of the cor.</p>
79.27	The 1/4 sec. cor. of secs. 23 and 26.
	<hr/> <p>From the 1/4 sec. cor. of secs. 25 and 26.</p> <p>S. 88°10' W., on the E. and W. center line of sec. 26.</p>
39.43	The center 1/4 sec. cor. of sec. 26.

**Subdivision of Section 26,  
T. 23 N., R. 18 E., Gila and Salt River Meridian, Arizona**

CHAINS	
78.86	<p>The true point for the 1/4 sec. cor. of secs. 26 and 27.</p> <hr/> <p style="text-align: center;"><b>Subdivision of Section 27, T. 23 N., R. 18 E., Gila and Salt River Meridian, Arizona</b></p> <hr/> <p>From the 1/4 sec. cor. of secs. 27 and 34.</p> <p>N. 0°01' E., on the N. and S. center line of sec. 27.</p> <p>Over broken and rolling land.</p>
39.23	<p>Point for the center 1/4 sec. cor. of sec. 27, at intersection with the E. and W. center line.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 25 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T 23 N R 18 E C 1/4 S 27</p> <p style="text-align: center;">2007</p> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p> <p>Set a steel fence post, alongside and W. of the cor.</p>
67.48	<p>Midpoint bet. two, Transwestern Pipeline Co., underground gas lines, bears N. 77°14' E. and S. 77°14' W.</p>
78.45	<p>The 1/4 sec. cor. of secs. 22 and 27.</p> <hr/> <p>From the true point for the 1/4 sec. cor. of secs. 26 and 27.</p> <p>N. 89°52' W., on the E. and W. center line of sec. 27.</p>
39.46	<p>The center 1/4 sec. cor. of sec. 27.</p>
78.91	<p>The 1/4 sec. cor. of secs. 27 and 28.</p> <hr/> <p style="text-align: center;"><b>Subdivision of Section 28, T. 23 N., R. 18 E., Gila and Salt River Meridian, Arizona</b></p> <hr/> <p>From the 1/4 sec. cor. of secs. 28 and 33.</p> <p>N. 0°13' W., on the N. and S. center line of sec. 28.</p> <p>Over rolling land.</p>

**Subdivision of Section 28,  
T. 23 N., R. 18 E., Gila and Salt River Meridian, Arizona**

CHAINS	
38.02	Midpoint bet. two, Transwestern Pipeline Co., underground gas lines, bears N. 69°10' E. and S. 69°10' W.
39.63	Point for the center 1/4 sec. cor. of sec. 28, at intersection with the E. and W. center line.  Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.  T 23 N R 18 E C 1/4 S 28  2007  Deposit a magnet, in a white plastic case, at the base of the stainless steel post.  Set a steel fence post, alongside and W. of the cor.  From this cor. point, the SW cor. of a wood framed house, 42 x 32 ft., bears N. 16°54' E., 26.30 chs. dist., the long side bears N. 10° E.  From this same cor. point, the SE cor. of a wood framed house, 50 x 32 ft., bears N. 38°57' W., 22.10 chs. dist., the long side bears N. 50° E.
47.92	Center of pavement, BIA Route N15, asphalt surfaced, 25 ft. wide, bears N. 69°36' E. and S. 69°36' W.
51.79	Midpoint bet. four, El Paso Natural Gas Co., underground gas lines, bears N. 69°10' E. and S. 69°10' W.
79.26	The 1/4 sec. cor. of secs. 21 and 28. <hr/>
	From the 1/4 sec. cor. of secs. 27 and 28.  N. 87°51' W., on the E. and W. center line of sec. 28.
6.35	Center of pavement, Arizona State Highway No. 87, asphalt surfaced, 28 ft. wide, bears S. 1°47' E. and N. 1°47' W.
35.61	Midpoint bet. two, Transwestern Pipeline Co., underground gas lines, bears N. 69°10' E. and S. 69°10' W.
39.48	The center 1/4 sec. cor. of sec. 28.
59.77	Center of pavement, BIA Route N15, asphalt surfaced, 25 ft. wide, bears N. 69°36' E. and S. 69°36' W.

**Subdivision of Section 28,  
T. 23 N., R. 18 E., Gila and Salt River Meridian, Arizona**

CHAINS	
68.63	Midpoint bet. four, El Paso Natural Gas Co., underground gas lines, bears N. 69°10' E. and S. 69°10' W.
78.96	The 1/4 sec. cor. of secs. 28 and 29.
<hr/> <p><b>Subdivision of Section 29, T. 23 N., R. 18 E., Gila and Salt River Meridian, Arizona</b></p> <hr/>	
	From the 1/4 sec. cor. of secs. 29 and 32.
	N. 0°18' W., on the N. and S. center line of sec. 29.
	Over rolling land.
6.74	Midpoint bet. two, Transwestern Pipeline Co., underground gas lines, bears N. 69°09' E. and S. 69°09' W.
15.26	Center of pavement, BIA Route N15, asphalt surfaced, 25 ft. wide, on the arc of a circular curve to the right, having a central angle of 20°06' and a radius of 5730.7 ft.
	From this point, the calculated P.O.T., bears N. 63°33' E., 18.29 chs. dist.
	From this same point, the calculated P.O.C., bears S. 53°30' W., 12.13 chs. dist.
20.86	Midpoint bet. four, El Paso Natural Gas Co., underground gas lines, bears N. 69°35' E. and S. 69°35' W.
33.50	Graded road, 25 ft. wide, bears S. 70° E. and N. 70° W.
40.00	Point for the center 1/4 sec. cor. of sec. 29, at intersection with the E. and W. center line.
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 25 ins. in the ground, with brass cap mkd.
	<p>T 23 N R 18 E C 1/4 S 29</p> <p>2007</p>
	Deposit a magnet, in a white plastic case, at the base of the stainless steel post.
	Set a steel fence post, alongside and W. of the cor.
79.16	The 1/4 sec. cor. of secs. 20 and 29.

**Subdivision of Section 29,  
T. 23 N., R. 18 E., Gila and Salt River Meridian, Arizona**

CHAINS	
	From the 1/4 sec. cor. of secs. 28 and 29. N. 89°46' W., on the E. and W. center line of sec. 29.
39.59	The center 1/4 sec. cor. of sec. 29.
56.40	Graded road, 25 ft. wide, bears S. 50° E. and N. 50° W.
79.71	The 1/4 sec. cor. of secs. 29 and 30.
<hr/> <b>Subdivision of Section 30, T. 23 N., R. 18 E., Gila and Salt River Meridian, Arizona</b> <hr/>	
	From the 1/4 sec. cor. of secs. 30 and 31. N. 1°44' W., on the N. and S. center line of sec. 30. Over easterly flank of Pyramid Butte.
39.26	Point for the center 1/4 sec. cor. of sec. 30, at intersection with the E. and W. center line.  Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 20 ins. in the ground, in a mound of stone, 3 ft. base, to top, with brass cap mkd.  T 23 N R 18 E C 1/4 S 30  2007
	Deposit a magnet, in a white plastic case, at the base of the stainless steel post.  Set a steel fence post, alongside and W. of the cor.  Cor. is located in the NE facing toe slopes of Pyramid Butte.
59.25	Point for the center N. 1/16 sec. cor. of sec. 30.  Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.  T 23 N R 18 E C N 1/16   S 30 C  2007



**Subdivision of Section 30,  
T. 23 N., R. 18 E., Gila and Salt River Meridian, Arizona**

CHAINS	
	<p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p> <p>Set a steel fence post, alongside and W. of the cor.</p>
63.20	Graded road, 25 ft. wide, bears N. 80° E. and W.
79.24	The 1/4 sec. cor. of secs. 19 and 30.
	<hr/> <p>From the 1/4 sec. cor. of secs. 29 and 30.</p> <p>N. 89°41' W., on the E. and W. center line of sec. 30.</p>
20.00	<p>Point for the center E. 1/16 sec. cor. of sec. 30.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with brass cap mkd.</p>
	<p>T 23 N R 18 E E 1/16 C———C S 30</p> <p>2007</p>
	<p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p> <p>Set a steel fence post, alongside and N. of the cor.</p>
40.00	The center 1/4 sec. cor. of sec. 30.
60.85	<p>Point for the center W. 1/16 sec. cor. of sec. 30.</p> <p>Not monumented.</p>
78.95	The 1/4 sec. cor. of secs. 25 and 30.
	<hr/> <p>NE 1/4</p> <hr/>
	<p>From the center E. 1/16 sec. cor. of sec. 30.</p> <p>N. 1°20' W., on the N. and S. center line of the NE 1/4 of sec. 30.</p>
19.99	<p>Point for the NE 1/16 sec. cor. of sec. 30, at intersection with the E. and W. center line of the NE 1/4.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p>

**Subdivision of Section 30,  
T. 23 N., R. 18 E., Gila and Salt River Meridian, Arizona**

CHAINS	
	T 23 N R 18 E NE 1/16 S 30 2007
	Deposit a magnet, in a white plastic case, at the base of the stainless steel post.
	Set a steel fence post, alongside and W. of the cor.
36.19	Graded road, 25 ft. wide, bears S. 55° E. and N. 85° W.
39.98	The point for the E. 1/16 sec. cor. of secs. 19 and 30.
	_____
	From the N. 1/16 sec. cor. of secs. 29 and 30.
	N. 89°41' W., on the E. and W. center line of the NE 1/4 of sec. 30.
1.30	Graded road, 25 ft. wide, bears S. 50° E. and N. 50° W.
20.14	The NE 1/16 sec. cor. of sec. 30.
40.28	The center N. 1/16 sec. cor. of sec. 30.
	_____
	NW 1/4 _____
	From the point for the center W. 1/16 sec. cor. of sec. 30.
	N. 0°55' W., on the N. and S. center line of the NW 1/4 of sec. 30.
19.98	Point for the NW 1/16 sec. cor. of sec. 30, at intersection with the E. and W. center line of the NW 1/4.
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 25 ins. in the ground, with brass cap mkd.
	T 23 N R 18 E NW 1/16 S 30 2007
	Deposit a magnet, in a white plastic case, at the base of the stainless steel post.
	Set a steel fence post, alongside and W. of the cor.

**Subdivision of Section 30,  
T. 23 N., R. 18 E., Gila and Salt River Meridian, Arizona**

CHAINS	
34.55	Graded road, 25 ft. wide, bears S. 60° E. and N. 60° W.
39.96	The W. 1/16 sec. cor. of secs. 19 and 30.
<hr/>	
	From the center N. 1/16 sec. cor. of sec. 30.
	N. 89°41' W., on the E. and W. center line of the NW 1/4 of sec. 30.
20.56	The NW 1/16 sec. cor. of sec. 30.
38.33	The point for the N. 1/16 sec. cor. of secs. 25 and 30.
<hr/>	
<p><b>Subdivision of Section 31, T. 23 N., R. 18 E., Gila and Salt River Meridian, Arizona</b></p>	
<hr/>	
	From the 1/4 sec. cor. of secs. 6 and 31.
	N. 2°16' E., on the N. and S. center line of sec. 31.
	Over broken and rolling land.
29.43	Center of pavement, BIA Route N15, asphalt surfaced, 25 ft. wide, on the arc of a circular curve to the left, having a central angle of 30°55'45" and a radius of 2865.1 ft.
	From this point, the calculated P.O.T., bears N. 58°33' E., 13.68 chs. dist.
	From this same point, the calculated P.O.C., bears S. 74°02' W., 9.68 chs. dist.
39.99	Point for the center 1/4 sec. cor. of sec. 31, at intersection with the E. and W. center line.
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with brass cap mkd.
	<p>T 23 N R 18 E C 1/4 S 31</p>
	2007
	Deposit a magnet, in a white plastic case, at the base of the stainless steel post.
	Set a steel fence post, alongside and W. of the cor.

**Subdivision of Section 31,  
T. 23 N., R. 18 E., Gila and Salt River Meridian, Arizona**

CHAINS	
56.03	Midpoint bet. two, Transwestern Pipeline Co., underground gas lines, bears N. 76°31' E. and S. 76°31' W.
72.39	Midpoint bet. four, El Paso Natural Gas Co., underground gas lines, bears N. 71°09' E. and S. 71°09' W.
80.69	The 1/4 sec. cor. of secs. 30 and 31. <hr/>
	From the 1/4 sec. cor. of secs. 31 and 32. N. 89°39' W., on the E. and W. center line of sec. 31.
24.62	Center of pavement, BIA Route N15, asphalt surfaced, 25 ft. wide, bears N. 49°29' E. and S. 49°29' W.
39.76	The center 1/4 sec. cor. of sec. 31.
78.32	The 1/4 sec. cor. of secs. 31 and 36. <hr/>
	<b>Subdivision of Section 32, T. 23 N., R. 18 E., Gila and Salt River Meridian, Arizona</b>
	From the 1/4 sec. cor. of secs. 5 and 32. N. 1°42' E., on the N. and S. center line of sec. 32. Over rolling land.
40.02	Point for the center 1/4 sec. cor. of sec. 32, at intersection with the E. and W. center line.  Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.  T 23 N R 18 E C 1/4 S 32  2007  Deposit a magnet, in a white plastic case, at the base of the stainless steel post.  Set a steel fence post, alongside and W. of the cor.
63.95	Midpoint bet. two, El Paso Natural Gas Co., underground gas lines, bears S. 20°25' E. and N. 20°25' W.
80.04	The 1/4 sec. cor. of secs. 29 and 32. <hr/>

**Subdivision of Section 32,  
T. 23 N., R. 18 E., Gila and Salt River Meridian, Arizona**

CHAINS	
	From the 1/4 sec. cor. of secs. 32 and 33. N. 89°40' W., on the E. and W. center line of sec. 32.
30.32	Midpoint bet. two, El Paso Natural Gas Co., underground gas lines, bears S. 20°06' E. and N. 20°06' W.
39.83	The center 1/4 sec. cor. of sec. 32.
79.66	The 1/4 sec. cor. of secs. 31 and 32.
<hr/> <p><b>Subdivision of Section 33, T. 23 N., R. 18 E., Gila and Salt River Meridian, Arizona</b></p> <hr/>	
	From the 1/4 sec. cor. of secs. 4 and 33. N. 1°00' E., on the N. and S. center line of sec. 33. Over rolling land.
34.90	Left cut bank of Coyote Wash, 10 ft. high, bears N. 85° E. and S. 65° W.
39.64	True point for the center 1/4 sec. cor. of sec. 33, at intersection with the E. and W. center line; falls on the right cut bank of Coyote Wash, (10 ft. high, bears S. 55° E. and W.), where it is impracticable to establish a permanent monument.
41.64	Point selected for a witness cor. to the center 1/4 sec. cor. of sec. 33.  Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with brass cap mkd.  <div style="text-align: center;">           WC            T 23 N R 18 E            C 1/4 S 33            ↓            2007         </div>
	Deposit a magnet, in a white plastic case, at the base of the stainless steel post.  Set a steel fence post, alongside and W. of the cor.
79.27	The 1/4 sec. cor. of secs. 28 and 33.
	<hr/> From the 1/4 sec. cor. of secs. 33 and 34.

**Subdivision of Section 33,  
T. 23 N., R. 18 E., Gila and Salt River Meridian, Arizona**

CHAINS

N. 89°02' W., on the E. and W. center line of sec. 33.

- 3.55 Center of pavement, Arizona State Highway No. 87, asphalt surfaced, 28 ft. wide, bears S. 1°47' E. and N. 1°47' W.
- 39.67 The true point for the center 1/4 sec. cor. of sec. 33.
- 79.34 The 1/4 sec. cor. of secs. 32 and 33.

**Subdivision of Section 34,  
T. 23 N., R. 18 E., Gila and Salt River Meridian, Arizona**

From the 1/4 sec. cor. of secs. 3 and 34.

N. 0°07' E., on the N. and S. center line of sec. 34.

Over broken and rolling land.

- 39.38 Point for the center 1/4 sec. cor. of sec. 34, at intersection with the E. and W. center line.

Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 22 ins. in the ground, with brass cap mkd.

T 23 N R 18 E  
C 1/4 S 34

2007

Deposit a magnet, in a white plastic case, at the base of the stainless steel post.

Set a steel fence post, alongside and W. of the cor.

- 78.60 The 1/4 sec. cor. of secs. 27 and 34.

From the 1/4 sec. cor. of secs. 34 and 35.

N. 89°51' W., on the E. and W. center line of sec. 34.

- 39.43 The center 1/4 sec. cor. of sec. 34.
- 79.14 The 1/4 sec. cor. of secs. 33 and 34.

**Subdivision of Section 35,  
T. 23 N., R. 18 E., Gila and Salt River Meridian, Arizona**

From the 1/4 sec. cor. of secs. 2 and 35.

**Subdivision of Section 35,  
T. 23 N., R. 18 E., Gila and Salt River Meridian, Arizona**

CHAINS	
	N. 0°04' E., on the N. and S. center line of sec. 35. Descending, over broken and rolling land.
39.64	Point for the center 1/4 sec. cor. of sec. 35, at intersection with the E. and W. center line.  Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 25 ins. in the ground, with brass cap mkd.  T 23 N R 18 E C 1/4 S 35  2007
	Deposit a magnet, in a white plastic case, at the base of the stainless steel post.  Set a steel fence post, alongside and W. of the cor.
79.27	The 1/4 sec. cor. of secs. 26 and 35. <hr/>
	From the 1/4 sec. cor. of secs. 35 and 36.  S. 89°21' W., on the E. and W. center line of sec. 35.
39.40	The center 1/4 sec. cor. of sec. 35.
78.80	The 1/4 sec. cor. of secs. 34 and 35. <hr/>
	<b>Subdivision of Section 36, T. 23 N., R. 18 E., Gila and Salt River Meridian, Arizona</b>
	From the 1/4 sec. cor. of secs. 1 and 36.  N. 0°07' E., on the N. and S. center line of sec. 36. Descending, over broken and rolling land.
39.99	Point for the center 1/4 sec. cor. of sec. 36, at intersection with the E. and W. center line.  Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.  T 23 N R 18 E C 1/4 S 36  2007

**Subdivision of Section 36,  
T. 23 N., R. 18 E., Gila and Salt River Meridian, Arizona**

CHAINS	<p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p> <p>Set a steel fence post, alongside and N. of the cor.</p>
80.02	<p>The 1/4 sec. cor. of secs. 25 and 36.</p> <hr/> <p>From the 1/4 sec. cor. of secs. 31 and 36, monumented with a stainless steel post, 2 1/2 ins. diam., firmly set, projecting 3 ins. above ground, with brass cap mkd. T23N R18E R19E 1/4 S36 S31 2004, with a mound of stone, 3 ft. base, 2 ft. high W. of the cor. Add the marks 2007 to the brass cap.</p> <p>N. 89°59' W., on the E. and W. center line of sec. 36.</p>
39.60	<p>The center 1/4 sec. cor. of sec. 36.</p>
79.09	<p>The 1/4 sec. cor. of secs. 35 and 36.</p> <hr/> <p style="text-align: center;">GENERAL DESCRIPTION</p> <hr/> <p>The survey is located about 3 miles west of Dilkon Arizona, on the Navajo Indian Reservation. Access is by way of Arizona State Highway No. 87 and BIA Route N15.</p> <p>The terrain is gently rolling, with the exception of Shonto Butte, in sections 1, 2, 11 and 12 and Pyramid Butte in section 30. Vegetation is predominantly grass and sage, with some junipers within the previously mentioned buttes. Elevations vary from about 6700 ft. above sea level atop Shonto Butte, to about 5500 ft. above sea level in the section 31.</p> <p>Coyote Wash is the predominant water course, entering the township in section 25, traversing WSW through sections 26, 27, 28, 33 and exiting the township in section 32. Shonto Springs in section 12, Coyote Springs in section 11 and Chandler Springs in sections 19 and 30 are all developed and utilized.</p> <p>There are approximately forty dwelling, scattered throughout the township. The majority are on the water and electrical power grids, some with power or water only, and a few with neither.</p> <p>Transwestern Pipeline Co. and El Paso Natural Gas Co., have underground gas lines, in the township.</p>



**T. 23 N., R. 18 E., Gila and Salt River Meridian, Arizona**

CHAINS

Grazing of horses, sheep and cattle is the primary use of the land.

The mean magnetic declination of  $11\ 1/4^{\circ}$  E. was derived from the National Geophysical Data Center's magnetic declination calculator, GEOMAG v6.0, utilizing the International Geomagnetic Reference Field Model for years 2005 through 2010, for the dates of survey.

---

UNITED STATES  
DEPARTMENT OF THE INTERIOR  
BUREAU OF LAND MANAGEMENT

FIELD ASSISTANTS

NAMES	CAPACITY
Geoffrey A. Graham	Land Surveyor
Robert J. Lyle	Surveying Technician
Mark R. Searles	Surveying Technician

CERTIFICATE OF SURVEY

We, Gordon R. Bubel and Joel A. Emert, Cadastral Surveyors, HEREBY CERTIFY upon honor, that in pursuance of special instructions bearing date of the 15th day of December, 2006, We have dependently resurveyed the the south, west and north boundaries and the subdivisional lines and subdivided all sections, T. 23 N., R. 18 E., of the Gila and Salt River Meridian, in the State of Arizona, which are represented in the foregoing field notes as having been executed by us and under our direction. Said survey has been made in strict conformity with said special instructions, the Manual of Instructions for the Survey of the Public Lands of the United States, 1973, and in specific manner described in the foregoing field notes.

AUG. 13, 2007  
(Date)

*Gordon R. Bubel*  
(Cadastral Surveyor)

AUG 13, 2007  
(Date)

*Joel A. Emert*  
(Cadastral Surveyor)

CERTIFICATE OF APPROVAL

BUREAU OF LAND MANAGEMENT  
Phoenix, Arizona

The foregoing field notes of the dependent resurvey of the south, west and north boundaries and the subdivisional lines and the subdivision of all sections, T. 23 N., R. 18 E., Gila and Salt River Meridian, in the State of Arizona, executed by Gordon R. Bubel and Joel A. Emert, Cadastral Surveyors, having been critically examined and found correct, are hereby approved.

April 7, 2008  
(Date)

*Stephen K. Hansen*  
(Chief Cadastral Surveyor of Arizona)

~~CERTIFICATE OF TRANSCRIPT~~

~~I CERTIFY That the foregoing transcript of the field notes of the above described surveys in T. 23 N., R. 18 E., Gila and Salt River Meridian, Arizona, is a true copy of the orig. field notes.~~

~~\_\_\_\_\_~~  
~~(Date)~~

~~\_\_\_\_\_~~  
~~(Chief Cadastral Surveyor of Arizona)~~