

ORIGINAL

UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

FIELD NOTES

OF THE

DEPENDENT RESURVEY OF A PORTION OF THE SIXTH STANDARD PARALLEL NORTH
(SOUTH BOUNDARY), **TOWNSHIP 25 NORTH, RANGE 17 EAST,**
THE SIXTH STANDARD PARALLEL NORTH (SOUTH BOUNDARY), **TOWNSHIP 25 NORTH,**
RANGE 18 EAST, WHICH ARE IDENTICAL WITH PORTIONS OF THE HOPI-NAVAJO
PARTITION LINE, SEGMENT "A"

AND

THE DEPENDENT RESURVEY OF PORTIONS OF THE HOPI-NAVAJO PARTITION LINE,
SEGMENT "A", THE EAST AND WEST BOUNDARIES AND THE SUBDIVISIONAL LINES
AND THE SUBDIVISION OF CERTAIN SECTIONS AND METES-AND-BOUNDS SURVEYS,
TOWNSHIP 24 NORTH, RANGE 18 EAST,

OF THE GILA AND SALT RIVER MERIDIAN,

IN THE STATE OF ARIZONA

EXECUTED BY

Jones Curtiss, Cadastral Surveyor

Under Special Instructions dated and approved June 4, 2007, which provided for the surveys included under Group No. 1023, and assignment instructions dated June 4, 2007.

Survey commenced June 11, 2007

Survey completed September 18, 2007

INDEX DIAGRAM

TOWNSHIPS 25 NORTH, RANGES 17 AND 18 EAST
 AND
 TOWNSHIP 24 NORTH, RANGE 18 EAST
 GILA AND SALT RIVER MERIDIAN, ARIZONA

SIXTH STANDARD PARALLEL NORTH

36 4	31 5	32 6	33 8	34 9	35 10	36 11
83	82	70	58	49	39	
27 6	81 5	68 4	57 3	48 2	38 1	20
80	80	68	57	47	37	
26 7	79 8	66 9	56 10	46 11	36 12	19
78	78	65	55	45	35	
25 18	77 17	64 16	54 15	44 14	34 13	18
76	76	63	54	43	33	
24 19	75 20	62 21	53 22	43 23	32 24	16
74	74	62	52	42	32	
23 30	73 29	61 28	51 27	41 26	31 25	15
72	71	60	51	41	30	
22 31	70 32	59 33	50 34	40 35	29 36	14
13	12	11	11	10	9	

Portions of Hopi-Navajo Partition Line, Segment "A"...12-14
 Subdivision of Certain Sections.....84-100
 Metes-and-Bounds Surveys.....100-111

**Tps. 25 N., Rs. 17 and 18 E. and T. 24 N., R. 18 E.,
Gila and Salt River Meridian, Arizona**

CHAINS

The following field notes describe the dependent resurvey of a portion of the Sixth Standard Parallel North (south boundary), Township 25 North, Range 17 East, the Sixth Standard Parallel North (south boundary), Township 25 North, Range 18 East, which are identical with portions of the Hopi-Navajo Partition Line, Segment "A" and the dependent resurvey of portions of the Hopi-Navajo Partition Line, Segment "A", the east and west boundaries and the subdivisional lines and the subdivision of certain sections and metes-and-bounds surveys, Township 24 North, Range 18 East, Gila and Salt River Meridian, Arizona.

The history of surveys pertaining to this survey is as follows:

O.D. Wheeler surveyed the Sixth Standard Parallel North (south boundary), Township 25 North, Range 17 East and the east boundary, Township 24 North, Range 17 East in 1882. A.P. Johnson surveyed the Sixth Standard Parallel North (south boundary), Township 25 North, Range 18 East, and the south and east boundaries and subdivisional lines, Township 24 North, Range 18 East in 1883. Sidney E. Blout resurveyed the Sixth Standard Parallel North (south boundary), Townships 25 North, Ranges 17 and 18 East, and portions of the east and west boundaries, and the subdivisional lines, Township 24 North, Range 18 East in 1910. Leonard W. Murphy and Paul G. Bauer surveyed the south boundary of the Hopi Indian Reservation, Executive Order of December 16, 1882 in 1964. Shirley B. Hjellum, Kenneth A. Krenke and Marvin T. Koppang surveyed the Hopi-Navajo Partition Line, Segment "A" (resurveyed a portion of the Sixth Standard Parallel North, through Ranges 15, 16, 17, 18 and 19 East) in 1977-79. Geoffrey A. Graham dependently resurveyed the west and north boundaries of Township 23 North, Range 19 East in 2004-05. Joe R. Salazar, dependently resurveyed a portion of the Sixth Standard Parallel North, (south boundary), Township 25 North, Range 18 East in 2003-05. Gordon R. Bubel and Joel A. Emert, dependently resurveyed the west and north boundaries, Township 23 North, Range 18 East in 2006-07.

The survey was executed in accordance with the specifications as set forth in the Manual of Instructions for the Survey of the Public Lands of the United States, 1973, and the Special Instructions dated June 4, 2007, for Group Number 1023, Arizona.

The true meridian direction and length of all lines were determined by real time kinematic global positioning system observations using Trimble Navigation 5700 model receivers.

Preliminary to the resurvey, the lines of the prior surveys were retraced and a search was made for all corners and other calls of record. Identified corners were remonumented in their original positions. Lost corners were reestablished and remonumented at proportionate positions based on the official record. The retracement data were thoroughly verified and only the true line field notes are given herein.

**Tps. 25 N., Rs. 17 and 18 E. and T. 24 N., R. 18 E.,
Gila and Salt River Meridian, Arizona**

CHAINS	<p>Geodetic control was derived from Global Positioning System (GPS) static observations post processed by National Geodetic Survey's Online Positioning User Service (OPUS), utilizing Continuously Operating Reference Stations (CORS) FERNO MESA ARP, FLAGSTAFF 1 ARP AND SPIDERROCKAZ2005 ARP. The NAD83 (CORS96) (EPOCH:2002), geographic position of the southeast corner of the township is as follows:</p> <p>Latitude: 35°25'53.32" N. Longitude: 110°22'08.88" W.</p> <p>The mean magnetic declination is 11 1/4° E.</p> <hr/> <p style="text-align: center;">Dependent Resurvey of a Portion of the Sixth Standard Parallel North (South Boundary), Identical with a Portion of the Hopi-Navajo Partition Line, Segment "A", T. 25 N., R. 17 E., Gila and Salt River Meridian, Arizona</p> <hr/> <p style="text-align: center;">Restoring the dependent resurvey executed by Shirley P. Hjellum, Kenneth A. Krenke and Marvin T. Koppang, in 1977-79</p> <hr/> <p>Beginning at the stan. cor. of secs. 35 and 36, identical with Angle Point A-26, Hopi-Navajo Partition Line, Segment "A", monumented with an iron post, 3 ins. diam., firmly set, projecting 16 ins. above ground, with brass cap mkd. SC T25N R17E S35 S36 HOPI AP A-26 NAVAJO 77 1910.</p> <p>Add the marks 2007 to the brass cap.</p> <p>Cor. is located in a barbed wire fence, 5 strand, bears East and West.</p> <p>S. 89°53' E., on the S. bdy. of sec. 36, identical with a portion of the Hopi-Navajo Partition Line, Segment "A".</p> <p>Over rolling land, along a barbed wire fence.</p> <p>40.03 The stan. 1/4 sec. cor. of sec. 36, identical with Angle Point A-27, Hopi-Navajo Partition Line, Segment "A", monumented with an iron post, 2 1/2 ins. diam., set flush with the surface of the ground, with brass cap mkd. SC T25N R17E HOPI 1/4 S36 AP A-27 NAVAJO 1977.</p> <p>Add the marks 2007 to the brass cap.</p>
--------	--

**Dependent Resurvey of a Portion of the
Sixth Standard Parallel North (South Boundary),
Identical with a Portion of the Hopi-Navajo Partition Line, Segment "A",
T. 25 N., R. 17 E., Gila and Salt River Meridian, Arizona**

CHAINS	
	<p>Cor. is located in a barbed wire fence, 5 strand, bears East and West.</p> <hr style="width: 20%; margin: 10px auto;"/> <p>S. 89°53' E., beginning new measurement.</p>
40.03	<p>The stan. cor. of Tps. 25 N., Rs. 17 and 18 E., identical with Angle Point A-28, Hopi-Navajo Partition Line, Segment "A", monumented with an iron post, 3 ins. diam., projecting 3 ins. above a conical concrete base, 14 ins. diam. bottom, 8 ins. diam. top, firmly set, projecting 20 ins. above ground, with brass cap mkd. SC T25N R17E R18E S36 S31 HOPI AP A-28 NAVAJO 1910 1977 2003.</p> <p>Add the marks 2007 to the brass cap.</p> <p>Cor. is located in a barbed wire fence, 5 strand, bears East and West.</p> <hr style="width: 80%; margin: 10px auto;"/> <p style="text-align: center;">Dependent Resurvey of the Sixth Standard Parallel North (South Boundary), Identical with a Portion of the Hopi-Navajo Partition Line, Segment "A", T. 25 N., R. 18 E., Gila and Salt River Meridian, Arizona</p> <hr style="width: 80%; margin: 10px auto;"/> <p style="text-align: center;">Restoring the dependent resurvey executed by Joe R. Salazar, in 2003-05</p> <hr style="width: 20%; margin: 10px auto;"/> <p>From the stan. cor. of Tps. 25 N., Rs. 17 and 18 E., identical with Angle Point A-28, Hopi-Navajo Partition Line, Segment "A", hereinbefore described.</p> <p>N. 89°43' E., on the S. bdy. of sec. 31, identical with a portion of the Hopi-Navajo Partition Line, Segment "A".</p> <p>Over rolling land, along a barbed wire fence.</p>
9.83	<p>Angle Point A-28A, Hopi-Navajo Partition Line, Segment "A", monumented with an iron post, 2 1/2 ins. diam., firmly set, projecting 4 ins. above ground, with brass cap mkd. T25N R18E S31 AP A-28A HOPI S6 NAVAJO T24N 1979 2003.</p> <p>Add the marks 2007 to the brass cap.</p> <p>Cor. is located in the cor. of barbed wire fences, 6 strand, extending South and West.</p> <hr style="width: 20%; margin: 10px auto;"/> <p>N. 89°43' E., beginning new measurement.</p>

**Dependent Resurvey of the
Sixth Standard Parallel North (South Boundary),
Identical with a Portion of the Hopi-Navajo Partition Line, Segment "A",
T. 25 N., R. 18 E., Gila and Salt River Meridian, Arizona**

CHAINS	
2.05	<p>Angle Point A-28D, Hopi-Navajo Partition Line, Segment "A", monumented with an iron post, 2 1/2 ins. diam., firmly set, projecting 5 ins. above ground, with brass cap mkd. T25N R18E S31 AP A-28D S6 NAVAJO T24N 1979 2003.</p> <p>Add the marks 2007 to the brass cap.</p> <p>Cor. is located in the cor. of barbed wire fences, 6 strand, extending South and East.</p> <hr style="width: 20%; margin: 10px auto;"/> <p>N. 89°43' E., beginning new measurement.</p>
28.18	<p>The stan. 1/4 sec. cor. of sec. 31, identical with Angle Point A-29, Hopi-Navajo Partition Line, Segment "A", monumented with an iron post, 2 1/2 ins. diam., projecting 11 ins. above a conical concrete base, 12 ins. diam. bottom, 8 ins. diam. top, firmly set, projecting 11 ins. above ground, with brass cap mkd. SC T25N R18E 1/4 S31 HOPI AP A-29 NAVAJO 1910 77 2003.</p> <p>Add the marks 2007 to the brass cap.</p> <p>Cor. is located in a barbed wire fence, 5 strand, bears East and West.</p> <hr style="width: 20%; margin: 10px auto;"/> <p>N. 89°44' E., beginning new measurement.</p>
40.06	<p>The stan. cor. of secs. 31 and 32, identical with Angle Point A-30, Hopi-Navajo Partition Line, Segment "A", monumented with an iron post, 3 ins. diam., projecting 3 ins. above a conical concrete base, 12 ins. diam. bottom, 8 ins. diam. top, firmly set, projecting 15 ins. above ground, with brass cap mkd. SC T25N R18E HOPI S31 S32 AP A-30 NAVAJO 1910 77 2003.</p> <p>Add the marks 2007 to the brass cap.</p> <p>Cor. is located in a barbed wire fence, 6 strand, bears East and West.</p> <hr style="width: 20%; margin: 10px auto;"/> <p>S. 89°26' E., on the S. bdy. of sec. 32, identical with a portion of the Hopi-Navajo Partition Line, Segment "A".</p> <p>Over rolling land, along a barbed wire fence.</p>
18.93	<p>Angle Point A-30A, Hopi-Navajo Partition Line, Segment "A", monumented with an iron post, 2 1/2 ins. diam., set flush with the surface of the ground, with brass cap mkd. T25N R18E S32 HOPI AP A-30A NAVAJO S5 T24N 1979 2003.</p> <p>Add the marks 2007 to the brass cap.</p>

**Dependent Resurvey of the
Sixth Standard Parallel North (South Boundary),
Identical with a Portion of the Hopi-Navajo Partition Line, Segment "A",
T. 25 N., R. 18 E., Gila and Salt River Meridian, Arizona**

CHAINS	
	<p>Cor. is located in the cor. of barbed wire fences, 6 strand, extending South and West.</p> <hr style="width: 20%; margin: 10px auto;"/> <p>S. 89°26' E., beginning new measurement.</p>
2.31	<p>Angle Point A-30D, Hopi-Navajo Partition Line, Segment "A", monumented with an iron post, 2 1/2 ins. diam., set flush with the surface of the ground, with brass cap mkd. T25N R18E S32 HOPI AP A-30D NAVAJO S5 T24N 1979 2003.</p> <p>Add the marks 2007 to the brass cap.</p> <p>Cor. is located in the cor. of barbed wire fences, 6 strand, extending South and East.</p> <hr style="width: 20%; margin: 10px auto;"/> <p>S. 89°26' E., beginning new measurement.</p>
5.83	<p>W. right-of-way fence of Arizona State Highway 87, 5 strand barbed wire, parallels highway.</p>
7.40	<p>Arizona State Highway 87, asphalt surface, 28 ft. wide, bears S. 15° E. and N. 15° W.</p>
8.99	<p>E. right-of-way fence of Arizona State Highway 87, 5 strand barbed wire, parallels highway.</p>
18.66	<p>The stan. 1/4 sec. cor. of sec. 32, identical with Angle Point A-31, Hopi-Navajo Partition Line, Segment "A", monumented with an iron post, 2 1/2 ins. diam., projecting 4 ins. above a conical concrete base, 12 ins. diam. bottom, 8 ins. diam. top, firmly set, projecting 12 ins. above ground, with brass cap mkd. SC T25N R18E HOPI 1/4 S32 AP-A31 NAVAJO 1977 2003.</p> <p>Add the marks 2007 to the brass cap.</p> <p>Cor. is located in a barbed wire fence, 5 strand, bears East and West.</p> <hr style="width: 20%; margin: 10px auto;"/> <p>S. 89°25' E., beginning new measurement.</p>
39.89	<p>The stan. cor. of secs. 32 and 33, identical with Angle Point A-32, Hopi-Navajo Partition Line, Segment "A", monumented with an iron post, 3 ins. diam., projecting 4 ins. above a conical concrete base, 20 ins. diam. bottom, 9 ins. diam. top, firmly set, projecting 24 ins. above ground, with brass cap mkd. SC HOPI T25N R18E S32 S33 AP A-32 NAVAJO 1910 77 2003.</p> <p>Add the marks 2007 to the brass cap.</p>

**Dependent Resurvey of the
Sixth Standard Parallel North (South Boundary),
Identical with a Portion of the Hopi-Navajo Partition Line, Segment "A",
T. 25 N., R. 18 E., Gila and Salt River Meridian, Arizona**

CHAINS	
	<p>Cor. is located in a barbed wire fence, 5 strand, bears East and West.</p> <hr/> <p style="text-align: center;">Restoring the dependent resurvey executed by Shirley P. Hjellum, Kenneth A. Krenke and Marvin T. Koppang, in 1977-79</p> <hr/> <p>S. 89°52' E., on the S. bdy. of sec. 33, identical with a portion of the Hopi-Navajo Partition Line, Segment "A".</p> <p>Over rolling land, along a barbed wire fence.</p>
39.98	<p>The stan. 1/4 sec. cor. of sec. 33, identical with Angle Point A-33, Hopi-Navajo Partition Line, Segment "A", monumented with an iron post, 2 1/2 ins. diam., projecting 6 ins. above a conical concrete base, 13 ins. diam. bottom, 8 ins. diam. top, firmly set, projecting 12 ins. above ground, with brass cap mkd. SC T25N R18E HOPI 1/4 S33 AP A-33 NAVAJO 1977.</p> <p>Add the marks 2007 to the brass cap.</p> <p>Cor. is located in a barbed wire fence, 5 strand, bears East and West.</p> <hr/> <p>S. 89°52' E., beginning new measurement.</p>
6.19	<p>Angle Point A-33A, Hopi-Navajo Partition Line, Segment "A", monumented with an iron post, 2 1/2 ins. diam., set flush with the surface of the ground, with brass cap mkd. T25N R18E S33 HOPI AP A-33A NAVAJO S3 T24N 1979.</p> <p>Add the marks 2007 to the brass cap.</p> <p>Cor. is located in the cor. of barbed wire fences, 5 strand, extending South and West.</p> <hr/> <p>S. 89°52' E., beginning new measurement.</p>
4.15	<p>Point for Angle Point A-33D, Hopi-Navajo Partition Line, Segment "A", determined at the intersection of record distances from Angle Point A-33A and Angle Point A-33C, there is no remaining evidence of the 1979 cor.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p>

**Dependent Resurvey of the
Sixth Standard Parallel North (South Boundary),
Identical with a Portion of the Hopi-Navajo Partition Line, Segment "A",
T. 25 N., R. 18 E., Gila and Salt River Meridian, Arizona**

CHAINS

T 25 N R 18 E
S 33

HOPI | AP A-33D
 | NAVAJO
 | S 3
 | T 24 N

2007

Deposit a magnet, in a white plastic case, at the base of the stainless steel post.

Cor. is located in the cor. of barbed wire fences, 5 strand, extending South and East.

From this cor. point, Angle Point A-33C, Hopi-Navajo Partition Line, Segment "A", bears S. 0°02' E., 3.79 chs. dist., hereinafter described.

S. 89°52' E., beginning new measurement.

29.62 True point for the stan. cor. of secs. 33 and 34, identical with Angle Point A-34, Hopi-Navajo Partition Line, Segment "A", determined at record bearing and distance from the witness cor.; falls on the slope of a wash, where it is impracticable to establish a permanent monument.

S. 89°52' E., on the S. bdy. of sec. 34, identical with a portion of the Hopi-Navajo Partition Line, Segment "A".

Over rolling land, along a barbed wire fence.

.15 The witness cor. to the stan. cor. of secs. 33 and 34, identical with Angle Point A-34, Hopi-Navajo Partition Line, Segment "A", monumented with an iron post, 2 1/2 ins. diam., projecting 4 ins. above a conical concrete base, 16 ins. diam. bottom, 9 ins. diam. top, firmly set, projecting 18 ins. above ground, with brass cap mkd. WC SC T25N R18E HOPI S33 S34 AP A-34 NAVAJO 1977 2003 and arrow point to the true point.

Add the marks 2007 to the brass cap.

Cor. is located in a barbed wire fence, 5 strand, bears East and West.

S. 89°53' E., beginning new measurement.

**Dependent Resurvey of the
Sixth Standard Parallel North (South Boundary),
Identical with a Portion of the Hopi-Navajo Partition Line, Segment "A",
T. 25 N., R. 18 E., Gila and Salt River Meridian, Arizona**

CHAINS	
39.80	<p>The stan. 1/4 sec. cor. of sec. 34, identical with Angle Point A-35, Hopi-Navajo Partition Line, Segment "A", monumented with an iron post, 1 in. diam., projecting 3 ins. above a conical concrete base, 12 ins. diam. bottom, 4 ins. diam. top, firmly set, projecting 18 ins. above ground, with brass cap mkd. SC T25N R18E HOPI 1/4 S34 AP A-35 NAVAJO 1910 77.</p> <p>Add the marks 2007 to the brass cap.</p> <p>Cor. is located in a barbed wire fence, 5 strand, bears East and West.</p> <hr style="width: 20%; margin: 10px auto;"/> <p>S. 89°50' E., beginning new measurement.</p>
26.88	Barbed wire fence, 5 strand, bears N. 8° E. and S. 8° W.
28.40	Navajo Route 9757, a graded road, 25 ft. wide, bears N. 5° E. and S. 5° W.
39.96	<p>The stan. cor. of secs. 34 and 35, identical with Angle Point A-36, Hopi-Navajo Partition Line, Segment "A", monumented with an iron post, 2 1/2 ins. diam., projecting 2 ins. above a conical concrete base, 11 ins. diam. bottom, 9 ins. diam. top, firmly set, projecting 10 ins. above ground, with brass cap mkd. SC T25N R18E HOPI S34 S35 AP A-36 NAVAJO 1977 2003.</p> <p>Add the marks 2007 to the brass cap.</p> <p>Cor. is located in a barbed wire fence, 5 strand, bears East and West.</p> <hr style="width: 20%; margin: 10px auto;"/> <p>S. 89°37' E., on the S. bdy. of sec. 35, identical with a portion of the Hopi-Navajo Partition Line, Segment "A".</p> <p>Over rolling land, along a barbed wire fence.</p>
34.20	Wash, 12 ft. wide, 2 ft. deep, drains S. 80° W.
39.95	<p>The stan. 1/4 sec. cor. of sec. 35, identical with Angle Point A-37, Hopi-Navajo Partition Line, Segment "A", monumented with an iron post, 2 1/2 ins. diam., firmly set, projecting 4 ins. above a concrete collar, 9 ins. square, 10 ins. above ground, with brass cap mkd. SC T25N R18E HOPI 1/4 S35 AP A-37 NAVAJO 1977.</p> <p>Add the marks 2007 to the brass cap.</p>

**Dependent Resurvey of the
Sixth Standard Parallel North (South Boundary),
Identical with a Portion of the Hopi-Navajo Partition Line, Segment "A",
T. 25 N., R. 18 E., Gila and Salt River Meridian, Arizona**

CHAINS	
	<p>Cor. is located in a barbed wire fence, 5 strand, bears East and West.</p> <hr style="width: 20%; margin: 10px auto;"/> <p>S. 89°47' E., beginning new measurement.</p>
39.96	<p>The stan. cor. of secs. 35 and 36, identical with Angle Point A-38, Hopi-Navajo Partition Line, Segment "A", monumented with an iron post, 2 1/2 ins. diam., projecting 2 ins. above a conical concrete base, 12 ins. diam. bottom, 8 ins. diam. top, firmly set, projecting 12 ins. above ground, with brass cap mkd. SC T25N R18E HOPI S35 S36 AP A-38 NAVAJO 1977 2003, with a mound of stone, 3 ft. base, 1 ft. high, N. of cor., from which the remaining 1910 bearing tree</p> <p style="padding-left: 40px;">A juniper, 19 ins. diam., bears N. 17 1/4° E., 1.05 chs. dist., with scribe marks SCT25NR18ES36BT visible on partially open blaze. (Record: N. 18 3/4° E.)</p> <p>Add the marks 2007 to the brass cap.</p> <p>Cor. is located in a barbed wire fence, 5 strand, bears East and West.</p> <hr style="width: 20%; margin: 10px auto;"/> <p>S. 89°36' E., on the S. bdy. of sec. 36, identical with a portion of the Hopi-Navajo Partition Line, Segment "A".</p> <p>Over rolling land, along a barbed wire fence.</p>
17.30	<p>Navajo Route 9062, a graded road, 20 ft. wide, bears N. 55° E. and S. 55° W.</p>
39.95	<p>The stan. 1/4 sec. cor. of sec. 36, identical with Angle Point A-39, Hopi-Navajo Partition Line, Segment "A", monumented with an iron post, 1 in. diam., firmly set, projecting 5 ins. above a concrete collar, 12 ins. square, 13 ins. above ground, with brass cap mkd. SC T25N R18E S36 HOPI 1/4 AP A-39 NAVAJO 1910 77.</p> <p>Add the marks 2007 to the brass cap.</p> <p>Cor. is located in a barbed wire fence, 5 strand, bears East and West.</p> <hr style="width: 20%; margin: 10px auto;"/> <p>S. 89°33' E., beginning new measurement.</p>

**Dependent Resurvey of the
Sixth Standard Parallel North (South Boundary),
Identical with a Portion of the Hopi-Navajo Partition Line, Segment "A",
T. 25 N., R. 18 E., Gila and Salt River Meridian, Arizona**

CHAINS	
39.96	<p>The stan. cor. of Tps. 25 N., Rs. 18 and 19 E., identical with Angle Point A-40, Hopi-Navajo Partition Line, Segment "A", monumented with an iron post, 3 ins. diam., firmly set, projecting 20 ins. above ground, in a concrete collar, with brass cap mkd. SC T25N R18E R19E S36 S31 HOPI AP A-40 NAVAJO 1910 77 2003, with a mound of stone, 3 ft. base, 1 ft. high, N. of cor.</p> <p>Add the marks 2007 to the brass cap.</p> <p>Cor. is located in a barbed wire fence, 5 strand, bears East and West.</p> <hr/> <p style="text-align: center;">Dependent Resurvey of Portions of the Hopi-Navajo Partition Line, Segment "A", T. 24 N., R. 18 E., Gila and Salt River Meridian, Arizona</p> <hr/> <p>From Angle Point A-28A, Hopi-Navajo Partition Line, Segment "A", on the Sixth Standard Parallel North (south boundary), T. 25 N., R. 18 E., hereinbefore described.</p> <p>S. 0°14' W., on line A-28A - A-28B, Hopi-Navajo Partition Line, Segment "A".</p> <p>Over rolling land, along a barbed wire fence.</p>
1.51	<p>Angle Point A-28B, Hopi-Navajo Partition Line, Segment "A", monumented with an iron post, 2 1/2 ins. diam., firmly set, projecting 6 ins. above ground, with brass cap mkd. T24N R18E S6 AP A-28B HOPI NAVAJO 1979 2003.</p> <p>Add the marks 2007 to the brass cap.</p> <p>Cor. is located in the cor. of barbed wire fences, 6 strand, extending North and East.</p> <hr/> <p>N. 89°46' E., on line A-28B - A-28C, Hopi-Navajo Partition Line, Segment "A".</p> <p>Over rolling land, along a barbed wire fence.</p>
2.07	<p>Angle Point A-28C, Hopi-Navajo Partition Line, Segment "A", monumented with an iron post, 2 1/2 ins. diam., firmly set, projecting 3 ins. above ground, with brass cap mkd. T24N R18E S6 AP A-28C HOPI NAVAJO 1979 2003.</p> <p>Add the marks 2007 to the brass cap.</p>

**Dependent Resurvey of Portions
of the Hopi-Navajo Partition Line, Segment "A",
T. 24 N., R. 18 E., Gila and Salt River Meridian, Arizona**

CHAINS	
	<p>Cor. is located in the cor. of barbed wire fences, 6 strand, extending North and West.</p> <hr style="width: 20%; margin: 10px auto;"/> <p>N. 0°35' W., on line A-28C - A-28D, Hopi-Navajo Partition Line, Segment "A".</p> <p>Over rolling land, along a barbed wire fence.</p>
1.51	<p>Angle Point A-28D, Hopi-Navajo Partition Line, Segment "A", on the Sixth Standard Parallel North (south boundary), T. 25 N., R. 18 E., hereinbefore described.</p> <hr style="width: 20%; margin: 10px auto;"/> <p>From Angle Point A-30A, Hopi-Navajo Partition Line, Segment "A", on the Sixth Standard Parallel North (south boundary), T. 25 N., R. 18 E., hereinbefore described.</p> <p>S. 0°58' W., on line A-30A - A-30B, Hopi-Navajo Partition Line, Segment "A".</p> <p>Over rolling land, along a barbed wire fence.</p>
1.54	<p>Angle Point A-30B, Hopi-Navajo Partition Line, Segment "A", monumented with an iron post, 2 1/2 ins. diam., firmly set, projecting 4 ins. above ground, with brass cap mkd. T24N R18E S5 HOPI AP A-30B NAVAJO 1979 2003.</p> <p>Add the marks 2007 to the brass cap.</p> <p>Cor. is located in the cor. of barbed wire fences, 6 strand, extending North and East.</p> <hr style="width: 20%; margin: 10px auto;"/> <p>S. 89°33' E., on line A-30B - A-30C, Hopi-Navajo Partition Line, Segment "A".</p> <p>Over rolling land, along a barbed wire fence.</p>
2.33	<p>Angle Point A-30C, Hopi-Navajo Partition Line, Segment "A", monumented with an iron post, 2 1/2 ins. diam., firmly set, projecting 4 ins. above ground, with brass cap mkd. T24N R18E S5 AP A-30C HOPI NAVAJO 1979 2003.</p> <p>Add the marks 2007 to the brass cap.</p> <p>Cor. is located in the cor. of barbed wire fences, 6 strand, extending North and West.</p> <hr style="width: 20%; margin: 10px auto;"/> <p>N. 0°16' E., on line A-30C - A-30D, Hopi-Navajo Partition Line, Segment "A".</p> <p>Over rolling land, along a barbed wire fence.</p>

**Dependent Resurvey of Portions
of the Hopi-Navajo Partition Line, Segment "A",
T. 24 N., R. 18 E., Gila and Salt River Meridian, Arizona**

CHAINS	
1.53	<p>Angle Point A-30D, Hopi-Navajo Partition Line, Segment "A", on the Sixth Standard Parallel North (south boundary), T. 25 N., R. 18 E., hereinbefore described.</p> <hr/> <p>From Angle Point A-33A, Hopi-Navajo Partition Line, Segment "A", on the Sixth Standard Parallel North (south boundary), T. 25 N., R. 18 E., hereinbefore described.</p> <p>S. 0°25' W., on line A-33A - A-33B, Hopi-Navajo Partition Line, Segment "A".</p> <p>Over rolling land, along a barbed wire fence.</p>
3.79	<p>Angle Point A-33B, Hopi-Navajo Partition Line, Segment "A", monumented with an iron post, 2 1/2 ins. diam., firmly set, projecting 4 ins. above ground, with brass cap mkd. T24N R18E S3 HOPI AP A-33B NAVAJO 1979.</p> <p>Add the marks 2007 to the brass cap.</p> <p>Cor. is located in the cor. of barbed wire fences, 5 strand, extending North and East.</p> <hr/> <p>S. 89°55' E., on line A-33B - A-33C, Hopi-Navajo Partition Line, Segment "A".</p> <p>Over rolling land, along a barbed wire fence.</p>
4.18	<p>Angle Point A-33C, Hopi-Navajo Partition Line, Segment "A", monumented with an iron post, 2 1/2 ins. diam., firmly set, projecting 4 ins. above ground, with brass cap mkd. T24N R18E S3 HOPI AP A-33C NAVAJO 1979.</p> <p>Add the marks 2007 to the brass cap.</p> <p>Cor. is located in the cor. of barbed wire fences, 5 strand, extending North and West.</p> <hr/> <p>N. 0°02' W., on line A-33C - A-33D, Hopi-Navajo Partition Line, Segment "A".</p>
3.79	<p>Angle Point A-33D, Hopi-Navajo Partition Line, Segment "A", on the Sixth Standard Parallel North (south boundary), T. 25 N., R. 18 E., hereinbefore described.</p> <hr/> <p style="text-align: center;">Dependent Resurvey of the East Boundary, T. 24 N., R. 18 E., Gila and Salt River Meridian, Arizona</p> <hr/>

**Dependent Resurvey of the East Boundary,
T. 24 N., R. 18 E., Gila and Salt River Meridian, Arizona**

CHAINS									
	<p>Restoring the survey executed by A. P. Johnson, in 1883</p> <hr/>								
	<p>From the cor. of Tps. 23 and 24 N., Rs. 18 and 19 E., monumented with a stainless steel post, 2 1/2 ins. diam., firmly set, projecting 5 ins. above ground, encircled with a collar of stone, with brass cap mkd. T24N R18E R19E S36 S31 S1 S6 T23N 2004 with a steel fence post nearby.</p> <p>Add the marks 2007 to the brass cap.</p> <p>From this cor. point, U.S. Geological Survey triangulation station "DILKON", bears S. 69° 00' W., 144.81 chs. dist., monumented with a aluminum tablet, 4 ins. diam., cemented atop a basalt stone outcrop, with top mkd. DILKON 1966 and a triangle.</p> <p>N. 2°00' W., bet. secs. 31 and 36.</p> <p>Over broken and rugged land.</p>								
5.70	Navajo Route 60, asphalt surface, 24 ft. wide, bears S. 60° E. and N. 60° W.								
11.60	Power line, 2 strand, bears S. 60° E. and N. 60° W.								
40.35	<p>Point for the 1/4 sec. cor. of secs. 31 and 36, at proportionate dist., there is no remaining evidence of the orig. cor.</p> <p>Set a brass tablet, 3 1/4 ins. diam., 2 1/2 ins. stem, cemented in place, in a drill hole, in a basalt stone outcrop, with top mkd.</p> <div style="text-align: center; margin: 10px 0;"> <table style="margin: auto;"> <tr><td colspan="2">T 24 N</td></tr> <tr><td colspan="2">1/4</td></tr> <tr><td>R 18 E</td><td> R 19 E</td></tr> <tr><td>S 36</td><td> S 31</td></tr> </table> <p>2007</p> </div> <p>Deposit a magnet, in a white plastic case, in the drill hole, at the base of the brass tablet.</p>	T 24 N		1/4		R 18 E	R 19 E	S 36	S 31
T 24 N									
1/4									
R 18 E	R 19 E								
S 36	S 31								
80.70	<p>The cor. of secs. 25, 30, 31 and 36, monumented with a stainless steel post, 2 1/2 ins. diam., firmly set, projecting 13 ins. above the ground, in a mound of stone, 2 1/2 ft. base, 1 ft. high, with brass cap mkd. T24N R18E R19E S25 S30 S31 S36 2004.</p> <p>Add the marks 2007 to the brass cap.</p> <hr/> <p>N. 2°54' E., bet. secs. 25 and 30.</p> <p>Over broken land.</p>								

**Dependent Resurvey of the East Boundary,
T. 24 N., R. 18 E., Gila and Salt River Meridian, Arizona**

CHAINS	
16.10	Navajo Route 601, a graded road, 25 ft. wide, bears N. 80° E. and S. 80° W.
39.53	Point for the 1/4 sec. cor. of secs. 25 and 30, at proportionate dist., there is no remaining evidence of the orig. cor. Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd. <div style="text-align: center;"> T 24 N 1/4 R 18 E R 19 E S 25 S 30 2007 </div> Deposit a magnet, in a white plastic case, at the base of the stainless steel post.
49.50	Graded road, 25 ft. wide, bears S. 75° E. and N. 75° W.
53.70	Power line, 2 strand, bears S. 75° E. and N. 75° W.
79.06	The cor. of secs. 19, 24, 25 and 30, determined at the center of an embedded mound of stone, 3 ft. base, 1 ft. high. This is accepted as the best available evidence of the orig. cor. position. At the corner point Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, in an embedded mound of stone, with brass cap mkd. <div style="text-align: center;"> T 24 N R 18 E R 19 E S 24 S 19 S 25 S 30 2007 </div> Deposit a magnet, in a white plastic case, at the base of the stainless steel post. Set a steel fence post nearby. <hr style="width: 60%; margin: auto;"/> <div style="text-align: center;"> Restoring the resurvey executed by Sidney E. Blout, in 1910 <hr style="width: 30%; margin: auto;"/> </div> N. 0°13' E., bet. secs. 24 and 19.

**Dependent Resurvey of the East Boundary,
T. 24 N., R. 18 E., Gila and Salt River Meridian, Arizona**

CHAINS	
39.95	<p>Over broken and rugged land, ascend Lone Cottonwood Butte.</p> <p>The 1/4 sec. cor. of secs. 19 and 24, monumented with a basalt stone, 20 X 8 X 5 ins., firmly set, projecting 15 ins. above ground, mkd. 1/4 on W. face.</p> <p>At the corner point</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 10 ins. in the ground, in a supporting mound of stone, 3 ft. base, to top, with brass cap mkd.</p> <div style="text-align: center;"> <p>T 24 N 1/4 R 18 E R 19 E S 24 S 19</p> <p>2007</p> </div> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p> <p>Bury the 1910 stone alongside the stainless steel post.</p> <p>Set a steel fence post nearby.</p> <p>Cor. is located between basalt stone boulders, at the base of a rocky ledge, bears N. 55° E. and S. 55° W.</p> <hr style="width: 20%; margin: 10px auto;"/> <p>N. 0°15' W., beginning new measurement.</p> <p>Thence over broken land, descend N. slope of Lone Cottonwood Butte.</p>
19.89	<p>Point for the N. 1/16 sec. cor. of secs. 19 and 24.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center;"> <p>T24N N 1/16 R 18 E R 19 E S 24 S 19</p> <p>2007</p> </div> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p>

**Dependent Resurvey of the East Boundary,
T. 24 N., R. 18 E., Gila and Salt River Meridian, Arizona**

CHAINS

39.78

The cor. of secs. 13, 18, 19 and 24, determined at the center of a mound of stone, 3 ft. base, 1 ft. high, occupied by a rebar, 5/8 in. diam., with a basalt stone, 14 X 12 X 8 ins., mkd. 3 grooves on one side, lying loose nearby. This is accepted as the best available evidence of the orig. cor. position.

At the corner point

Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.

T 24 N	
R 18 E	R 19 E
S 13	S 18
S 24	S 19

2007

Deposit a magnet, in a white plastic case, at the base of the stainless steel post.

Bury the orig. stone alongside, and deposit the rebar, 13 ins. long, inside, the stainless steel post.

Raise a mound of stone, 3 ft. base, 1 ft. high, N. of cor.

Set a steel fence post nearby.

N. 0°04' E., bet. secs. 13 and 18.

Over rolling land.

40.04

The 1/4 sec. cor. of secs. 13 and 18, monumented with a basalt stone, 16 X 15 X 4 ins., firmly set, projecting 5 ins. above ground, mkd. 1/4 on W. face, with a rebar, 1/2 in. diam., firmly set, projecting 3 ins. above ground, alongside, with plastic cap mkd. NECA NMLS 13473.

At the corner point

Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.

T 24 N	
1/4	
R 18 E	R 19 E
S 13	S 18

2007

Deposit a magnet, in a white plastic case, at the base of the stainless steel post.

**Dependent Resurvey of the East Boundary,
T. 24 N., R. 18 E., Gila and Salt River Meridian, Arizona**

CHAINS									
	<p>Bury the 1910 stone alongside, and deposit the rebar, 13 ins. long, inside, the stainless steel post.</p> <p>From this cor. point, the SW corner of a wood framed house, 44 x 32 ft., bears N. 30° E., 53 lks. dist., the long side bears N. 10° E.</p> <hr style="width: 30%; margin: 10px auto;"/> <p>North, beginning new measurement.</p>								
20.70	Tees Toh Wash, 55 ft. wide, 2 ft. deep, drains N. 65° W.								
37.90	Power line, 2 strand, bears S. 80° E. and N. 80° W.								
38.90	Navajo Route 9065, a graded road, 23 ft. wide, bears S. 85° E. and N. 85° W.								
40.35	<p>Point for the cor. of secs. 7, 12, 13 and 18, at proportionate dist., by the method of irregular boundary adjustment, there is no remaining evidence of the 1910 cor.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center; margin: 10px 0;"> <table style="border-collapse: collapse; margin: 0 auto;"> <tr> <td colspan="2" style="padding: 0 10px;">T 24 N</td> </tr> <tr> <td style="border-right: 1px solid black; padding: 0 5px;">R 18 E</td> <td style="padding: 0 5px;">R 19 E</td> </tr> <tr> <td style="border-right: 1px solid black; padding: 0 5px;">S 12</td> <td style="padding: 0 5px;">S 7</td> </tr> <tr> <td style="border-right: 1px solid black; padding: 0 5px;">S 13</td> <td style="padding: 0 5px;">S 18</td> </tr> </table> <p style="margin: 5px 0;">2007</p> </div> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p> <p>Set a steel fence nearby.</p> <hr style="width: 30%; margin: 10px auto;"/> <p>N. 0°03' W., bet. secs. 7 and 12.</p> <p>Over rolling desert land.</p>	T 24 N		R 18 E	R 19 E	S 12	S 7	S 13	S 18
T 24 N									
R 18 E	R 19 E								
S 12	S 7								
S 13	S 18								
11.80	Power line, 2 strand, bears S. 10° E. and N. 10° W.								
18.94	Barbed wire fence, 4 strand, bears N. 30° E. and S. 30° W.								
40.39	<p>Point for the 1/4 sec. cor. of secs. 7 and 12, at proportionate dist., there is no remaining evidence of the 1910 cor.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p>								

**Dependent Resurvey of the East Boundary,
T. 24 N., R. 18 E., Gila and Salt River Meridian, Arizona**

CHAINS	
	T 24 N 1/4 R 18 E R 19 E S 12 S 7 2007
	Deposit a magnet, in a white plastic case, at the base of the stainless steel post.
58.39	Barbed wire fence, 5 strand, bears North and East. From this point, the 160 Mile Post of the S. bdy. of 1882 Executive Order Hopi Indian Reservation, bears West, 18.54 chs. dist., monumented with an iron post, 2 1/2 diam., set flush with the surface of the ground, with brass cap mkd. EO 1882 160M NAVAJO 1964. Add the marks 2007 to the brass cap. From this same point, the 160 1/2 Mile Post of the S. bdy. of 1882 Executive Order Hopi Indian Reservation, bears East, 21.47 chs. dist., monumented with an iron post, 2 1/2 diam., firmly set, projecting 4 ins. above ground, with brass cap mkd. EO 1882 160 1/2M NAVAJO 1964. Add the marks 2007 to the brass cap.
80.78	The cor. of secs. 1, 6, 7 and 12, determined at the cor. of barbed wire fences, 5 strand, extending South and West, with a basalt stone, 21 x 10 x 8 ins., mkd. 5 grooves on one side and 1 groove on the opposite side, laying loose alongside. This is accepted as the best available evidence of the orig. cor. position. At the corner point Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.
	T 24 N R 18 E R 19 E S 1 S 6 S 12 S 7 2007
	Deposit a magnet, in a white plastic case, at the base of the stainless steel post. Bury the 1910 stone alongside the stainless steel post.
	<hr/> N. 0°05' E., bet. secs. 1 and 6. Over rolling desert land.

**Dependent Resurvey of the East Boundary,
T. 24 N., R. 18 E., Gila and Salt River Meridian, Arizona**

CHAINS	
14.20	Lukai Wash, 40 ft. wide, 6 ft. deep, drains N. 30° W.
38.44	<p>The 1/4 sec. cor. of secs. 1 and 6, monumented with a basalt stone, 16 x 12 x 8 ins., firmly set, projecting 6 ins. above ground, mkd. 1/4 on E. face.</p> <p>At the corner point</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center;"> <p>T 24 N 1/4 R 18 E R 19 E S 1 S 6</p> <p>2007</p> </div> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p> <p>Bury the 1910 stone alongside the stainless steel post.</p> <hr style="width: 20%; margin: 10px auto;"/> <p>N. 0°05' E., beginning new measurement.</p>
43.52	<p>Point for the closing cor. of Tps. 24 N., Rs. 18 and 19 E., at the intersection with the Sixth Standard Parallel North, on the N. bdy. of the Tp., on the projection of the bearing from the cor. of secs. 1, 6, 7, and 12 through the 1/4 sec. cor. of secs. 1 and 6, there is no remaining evidence of the orig. cor.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center;"> <p>T 25 N R 18 E S 36 ----- S 1 S 6 R 18 E R 19 E T 24 N CC</p> <p>2007</p> </div> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p> <p>Cor. is located in a barbed wire fence, 5 strand, bears East and West.</p>

**Dependent Resurvey of the East Boundary,
T. 24 N., R. 18 E., Gila and Salt River Meridian, Arizona**

CHAINS

From this cor. point, the stan. 1/4 sec. cor. of sec. 36, T. 25 N., R. 18 E., identical with Angle Point A-39, Hopi-Navajo Partition Line, Segment "A", bears S. 89°36' E., 3.76 chs. dist., hereinbefore described.

From this same cor. point, the stan. cor. of secs. 35 and 36, T. 25 N., R. 18 E., identical with Angle Point A-38, Hopi-Navajo Partition Line, Segment "A", bears N. 89°36' W., 36.19 chs. dist., hereinbefore described.

**Dependent Resurvey of the West Boundary,
T. 24 N., R. 18 E., Gila and Salt River Meridian, Arizona**

Restoring the survey executed by
O. D. Wheeler, in 1882

From the cor. of Tps. 23 and 24 N., Rs. 17 and 18 E., monumented with a stainless steel post, 2 1/2 ins. diam., firmly set, projecting 3 ins. above ground, with brass cap mkd. T24N R17E R18E S36 S31 S1 S6 T23N 2004 2007, with a mound of stone, 3 ft. base, 2 ft. high, S. of cor.

N. 0°24' W., bet. secs. 31 and 36.

Over rolling land.

40.63

Point for the 1/4 sec. cor. of secs. 31 and 36, at proportionate dist., there is no remaining evidence of the orig. cor.

Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.

T 24 N
1/4
R 17 E | R 18 E
S 36 | S 31

2007

Deposit a magnet, in a white plastic case, at the base of the stainless steel post.

81.26

The cor. of secs. 25, 30, 31 and 36, determined at the center of an embedded mound of stone, 2 ft. base, occupied by a rebar, 5/8 in. diam., set flush with the surface of the ground. This is accepted as the best available evidence of the orig. corner position.

At the corner point

**Dependent Resurvey of the West Boundary,
T. 24 N., R. 18 E., Gila and Salt River Meridian, Arizona**

CHAINS									
	<p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, in a embedded mound of stone, with brass cap mkd.</p> <table style="margin-left: auto; margin-right: auto;"> <tr><td colspan="2" style="text-align: center;">T 24 N</td></tr> <tr><td style="text-align: center;">R 17 E</td><td style="text-align: center;">R 18 E</td></tr> <tr><td style="text-align: center;">S 25</td><td style="text-align: center;">S 30</td></tr> <tr><td style="text-align: center;">S 36</td><td style="text-align: center;">S 31</td></tr> </table> <p style="text-align: center;">2007</p> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p> <p>Bury the rebar, 18 ins. long, alongside the stainless steel post.</p> <hr/> <p>N. 0°11' W., bet. secs. 25 and 30.</p> <p>Over rolling land.</p>	T 24 N		R 17 E	R 18 E	S 25	S 30	S 36	S 31
T 24 N									
R 17 E	R 18 E								
S 25	S 30								
S 36	S 31								
28.70	Navajo Route 9844, a graded road, 26 ft. wide, bears S. 60° E. and N. 60° W.								
39.805	<p>Point for the 1/4 sec. cor. of secs. 25 and 30, at proportionate dist., there is no remaining evidence of the orig. cor.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with brass cap mkd.</p> <table style="margin-left: auto; margin-right: auto;"> <tr><td colspan="2" style="text-align: center;">T 24 N</td></tr> <tr><td colspan="2" style="text-align: center;">1/4</td></tr> <tr><td style="text-align: center;">R 17 E</td><td style="text-align: center;">R 18 E</td></tr> <tr><td style="text-align: center;">S 25</td><td style="text-align: center;">S 30</td></tr> </table> <p style="text-align: center;">2007</p> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p> <p>Cor. is located within a area enclosed by a fence surrounding a residential area, 2.78 chs. N. of a barbed wire fence, 4 strand, bears N. 25° E. and S. 25° W. and 16 lks. S. of the fence, bears S. 55° E. and N. 55° W. and 1.31 chs. S. of a power line, 2 strand, bears N. 65° E. and S. 65° W.</p>	T 24 N		1/4		R 17 E	R 18 E	S 25	S 30
T 24 N									
1/4									
R 17 E	R 18 E								
S 25	S 30								
72.30	Trail road, bears S. 75° E. and N. 75° W.								
79.61	<p>Point for the cor. of secs. 19, 24, 25 and 30, at proportionate dist., there is no remaining evidence of the orig. cor.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p>								

**Dependent Resurvey of the West Boundary,
T. 24 N., R. 18 E., Gila and Salt River Meridian, Arizona**

CHAINS									
	<table style="margin: auto;"> <tr><td colspan="2">T 24 N</td></tr> <tr><td>R 17 E</td><td>R 18 E</td></tr> <tr><td>S 24</td><td>S 19</td></tr> <tr><td>S 25</td><td>S 30</td></tr> </table> <p style="text-align: center;">2007</p> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p> <hr/> <p>N. 0°11' W., bet. secs. 19 and 24.</p> <p>Over rolling land.</p>	T 24 N		R 17 E	R 18 E	S 24	S 19	S 25	S 30
T 24 N									
R 17 E	R 18 E								
S 24	S 19								
S 25	S 30								
39.805	<p>The 1/4 sec. cor. of secs. 19 and 24, determined at the center of a mound of stone, 3 ft. base, 1 ft. high. This is accepted as the best available evidence of the orig. corner position.</p> <p>At the corner point</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center;"> <table style="margin: auto;"> <tr><td colspan="2">T 24 N</td></tr> <tr><td colspan="2">1/4</td></tr> <tr><td>R 17 E</td><td>R 18 E</td></tr> <tr><td>S 24</td><td>S 19</td></tr> </table> <p style="text-align: center;">2007</p> </div> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p> <p>Raise a mound of stone, 2 ft. base, 2 ft. high, W. of cor.</p> <hr/> <p>N. 2°19' E., beginning new measurement.</p>	T 24 N		1/4		R 17 E	R 18 E	S 24	S 19
T 24 N									
1/4									
R 17 E	R 18 E								
S 24	S 19								
39.78	<p>The cor. of secs. 13, 18, 19 and 24, determined at the projection of the bearing from the cor. of secs. 7, 12, 13, and 18 through the 1/4 sec. cor. of secs. 13 and 18, utilizing the resurvey distance, there is no remaining evidence of the orig. cor.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p>								

**Dependent Resurvey of the West Boundary,
T. 24 N., R. 18 E., Gila and Salt River Meridian, Arizona**

CHAINS	
	T 24 N R 17 E R 18 E S 13 S 18 S 24 S 19 2007
	Deposit a magnet, in a white plastic case, at the base of the stainless steel post.
	<hr/> Restoring the resurvey executed by Sidney E. Blout, in 1910 <hr/>
	N. 0°10' W., bet. secs. 13 and 18. Over rolling land.
7.30	Wash, 25 ft. wide, 4 ft. deep, drains N. 55° W.
24.10	Power line, 2 strand, bears N. 60° E. and S. 60° W.
28.10	Wash, 25 ft. wide, 20 ft. deep, drains N. 60° E.
40.09	The 1/4 sec. cor. of secs. 13 and 18, monumented with a basalt stone, 18 x 8 x 5 ins., firmly set, projecting 8 ins. above ground, mkd. 1/4 on W. face. At the corner point Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.
	T 24 N 1/4 R 17 E R 18 E S 13 S 18 2007
	Deposit a magnet, in a white plastic case, at the base of the stainless steel post.
	Bury the 1910 stone alongside the stainless steel post.
	<hr/> N. 0°10' W., beginning new measurement.
40.09	Point for the cor. of secs. 7, 12, 13 and 18, at proportionate dist., by the method of irregular boundary adjustment, there is no remaining evidence of the 1910 cor.

**Dependent Resurvey of the West Boundary,
T. 24 N., R. 18 E., Gila and Salt River Meridian, Arizona**

CHAINS									
	<p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <table style="margin-left: auto; margin-right: auto; border-collapse: collapse;"> <tr> <td colspan="2" style="text-align: center;">T 24 N</td> </tr> <tr> <td style="text-align: center; border-right: 1px solid black;">R 17 E</td> <td style="text-align: center;">R 18 E</td> </tr> <tr> <td style="text-align: center; border-right: 1px solid black;">S 12</td> <td style="text-align: center;">S 7</td> </tr> <tr> <td style="text-align: center; border-right: 1px solid black;">S 13</td> <td style="text-align: center;">S 18</td> </tr> </table> <p style="text-align: center;">2007</p> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p> <p>Cor. is located 25 lks. W. and 1.34 chs. S. of a wash, 6 ft. wide, 4 ft. deep, drains N. 85° W.</p> <hr/> <p>N. 0°01' E., bet. secs. 7 and 12.</p> <p>Over rolling land.</p>	T 24 N		R 17 E	R 18 E	S 12	S 7	S 13	S 18
T 24 N									
R 17 E	R 18 E								
S 12	S 7								
S 13	S 18								
39.98	<p>Point for the 1/4 sec. cor. of secs. 7 and 12, at proportionate dist., there is no remaining evidence of the 1910 cor.</p> <p>Set a magnet, in a white plastic case, 24 ins. in the ground.</p> <p>from which</p> <p style="padding-left: 40px;">A stainless steel post, 28 ins. long, 2 1/2 ins. diam., set 24 ins. in the ground, for a reference monument, bears S. 45°00' E., 85.0 ft. dist., with brass cap mkd. RM T24N R18E 1/4 S7 85.0 FT. TO COR 2007 and an arrow pointing to the corner. Deposit a magnet, in a white plastic case, at the base of the stainless steel post. Set a steel fence post nearby.</p> <p style="padding-left: 40px;">A stainless steel post, 28 ins. long, 2 1/2 ins. diam., set 24 ins. in the ground, for a reference monument, bears N. 45°00' W., 105.0 ft. dist., with brass cap mkd. RM T24N R17E 1/4 S12 105.0 FT. TO COR 2007 and an arrow pointing to the corner. Deposit a magnet, in a white plastic case, at the base of the stainless steel post. Set a steel fence post nearby.</p> <p>Cor. is located in Tees Toh Wash, 50 ft. wide, 5 ft. deep, drains S. 25° W.</p>								
56.90	<p>Barbed wire fence, 5 strand, bears East and West.</p>								

**Dependent Resurvey of the West Boundary,
T. 24 N., R. 18 E., Gila and Salt River Meridian, Arizona**

CHAINS											
	<p>From this point, the 154 1/2 Mile Post of the S. bdy. of 1882 Executive Order Hopi Indian Reservation, bears East, 23.83 chs. dist., monumented with an iron post, 2 1/2 diam., set 9 ins. below the surface of the ground, with brass cap mkd. EO 1882 154 1/2 M NAVAJO 1964. Add the marks 2007 to the brass cap.</p> <p>Cor. is located in a barbed wire fence, 5 strand, bears East and West.</p> <p>From this same point, the 154 Mile Post of the S. bdy. of 1882 Executive Order Hopi Indian Reservation, bears West, 16.19 chs. dist., monumented with an iron post, 2 1/2 diam., set flush with the surface of the ground, with brass cap mkd. EO 1882 154M NAVAJO 1964. Add the marks 2007 to the brass cap.</p> <p>Cor. is located in a barbed wire fence, 5 strand, bears East and West.</p>										
68.90	Navajo Route 9901, a graded road, 22 ft. wide, bears East and West.										
79.96	<p>The cor. of secs. 1, 6, 7 and 12, monumented with a lava stone, 8 x 7 x 7 ins., loosely set, projecting 6 ins. above ground, mkd. 5 grooves on N. side and 1 groove on S. side, with a rebar, 5/8 in. diam., firmly set, projecting 3 ins. above ground, alongside, with yellow plastic cap mkd. NECA.</p> <p>At the corner point</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center;"> <table style="margin: auto;"> <tr><td colspan="2">T 24 N</td></tr> <tr><td>R 17 E</td><td>R 18 E</td></tr> <tr><td>S 1</td><td>S 6</td></tr> <tr><td colspan="2"><hr/></td></tr> <tr><td>S 12</td><td>S 7</td></tr> </table> <p>2007</p> </div> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p> <p>Bury the 1910 stone alongside, and deposit the rebar, 13 ins. long, inside, the stainless steel post</p> <hr/> <p>N. 0°02' E., bet. secs. 1 and 6.</p> <p>Over rolling land.</p>	T 24 N		R 17 E	R 18 E	S 1	S 6	<hr/>		S 12	S 7
T 24 N											
R 17 E	R 18 E										
S 1	S 6										
<hr/>											
S 12	S 7										

**Dependent Resurvey of the West Boundary,
T. 24 N., R. 18 E., Gila and Salt River Meridian, Arizona**

CHAINS	
39.96	<p>The 1/4 sec. cor. of secs. 1 and 6, monumented with a sandstone, 16 x 12 x 4 ins., firmly set, projecting 5 ins. above ground, mkd. 1/4 on W. face, with a rebar, 5/8 ins. diam., firmly set, projecting 3 ins. above ground, alongside.</p> <p>At the corner point</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center;"> <p>T 24 N 1/4 R 17 E R 18 E S 1 S 6</p> <p>2007</p> </div> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p> <p>Bury the 1910 stone alongside, and deposit the rebar, 13 ins. long, inside, the stainless steel post.</p> <hr style="width: 20%; margin: 10px auto;"/> <p>N. 0°06' E., beginning new measurement.</p>
23.80	Graded road, 18 ft. wide, bears S. 65° E. and N. 65° W.
42.82	<p>The closing cor. of Tps. 24 N., Rs. 17 and 18 E., at intersection with the Sixth Standard Parallel North, on the N. bdy. of the Tp., monumented with a basalt stone, 16 x 8 x 4 ins., firmly set, projecting 9 ins. above ground, mkd. 6 grooves on S. and W. faces, with a rebar, 5/8 in. diam., firmly set, projecting 3 ins. above ground, alongside, with yellow plastic cap mkd. NECA.</p> <p>At the corner point</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center;"> <p>T 25 N R 17 E S 36</p> <hr style="width: 20%; margin: 0 auto;"/> <p>S 1 S 6 R 17 E R 18 E T 24 N CC</p> <p>2007</p> </div> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p>

**Dependent Resurvey of the West Boundary,
T. 24 N., R. 18 E., Gila and Salt River Meridian, Arizona**

CHAINS	<p>Bury the 1910 stone alongside, and deposit the rebar, 18 ins. long, inside, the stainless steel post</p> <p>Cor. is located in a barbed wire fence, 6 strand, bears East and West.</p> <p>From this cor. point, the stan. 1/4 sec. cor. of sec. 36, T. 25 N., R. 17 E., identical with Angle Point A-27, Hopi-Navajo Partition Line, Segment "A", bears N. 89°53' E., 6.48 chs. dist., hereinbefore described.</p> <p>From this same cor. point, the stan. cor. of secs. 35 and 36, T. 25 N., R. 17 E., identical with Angle Point A-26, Hopi-Navajo Partition Line, Segment "A", bears N. 89°53' W., 33.55 chs. dist., hereinbefore described.</p> <hr/> <p align="center">Dependent Resurvey of the Subdivisional Lines, T. 24 N., R. 18 E., Gila and Salt River Meridian, Arizona</p> <hr/> <p align="center">Restoring the survey executed by A. P. Johnson, in 1883</p> <hr/> <p>From the cor. of secs. 1, 2, 35 and 36, on the S. bdy. of the Tp., monumented with a stainless steel post, 2 1/2 ins. diam., firmly set, 4 ins. above ground, in an embedded mound of stone, 2 ft. base, with brass cap mkd. T24N R18E S35 S36 S2 S1 T23N 2004 2007, with a steel fence post nearby.</p> <p>N. 0°29' W., bet. secs. 35 and 36.</p> <p>Over rolling land.</p> <p>40.175 Point for the 1/4 sec. cor. of secs. 35 and 36, at proportionate dist., there is no remaining evidence of the orig. cor.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p align="center">T 24 N R 18 E 1/4 S 35 S 36</p> <p align="center">2007</p> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p> <p>Cor. is located 82 lks. N. of a trail road, bears N. 85° E. and S. 85° W. and 1.50 chs. N. of a barbed wire fence, 6 strand, bears East and West.</p>
--------	--

**Dependent Resurvey of the Subdivisional Lines,
T. 24 N., R. 18 E., Gila and Salt River Meridian, Arizona**

CHAINS							
49.60	Navajo Route 602, asphalt surface, 22 ft. wide, bears S. 65° E., and N. 65° W.						
55.20	Power line, 2 strand, bears S. 60° E. and N. 60° W.						
80.35	<p>The cor. of secs. 25, 26, 35 and 36, determined at the cor. of the remains of old wire fences, with wood posts extending North and West. This is accepted as the best available evidence of the orig. cor. position.</p> <p>At the corner point</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <table style="margin-left: auto; margin-right: auto; border-collapse: collapse;"> <tr> <td style="padding: 0 10px;">T 24 N</td> <td style="padding: 0 10px;">R 18 E</td> </tr> <tr> <td style="border-right: 1px solid black; padding: 0 5px;">S 26</td> <td style="padding: 0 5px;">S 25</td> </tr> <tr> <td style="border-right: 1px solid black; padding: 0 5px;">S 35</td> <td style="padding: 0 5px;">S 36</td> </tr> </table> <p style="text-align: center;">2007</p> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p> <hr style="width: 50%; margin: 10px auto;"/> <p>From the cor. of secs. 25, 30, 31 and 36, on the E. bdy. of the Tp.</p> <p>S. 89°56' W., bet. secs. 25 and 36.</p> <p>Over broken land.</p>	T 24 N	R 18 E	S 26	S 25	S 35	S 36
T 24 N	R 18 E						
S 26	S 25						
S 35	S 36						
38.27	<p>Point for the 1/4 sec. cor. of secs. 25 and 36, at proportionate dist., there is no remaining evidence of the orig. cor.</p> <p>Set a PK nail in the asphalt surface of Navajo Route 60, 24 ft. wide, bears S. 5° E. and N. 5° W.</p> <p>from which</p> <p style="padding-left: 40px;">A stainless steel post, 28 ins. long, 2 1/2 ins. diam., set 24 ins. in the ground, for a reference monument, bears N. 49°28' E., 70.60 ft. dist., with brass cap mkd. RM T24N R18E 1/4 S25 70.6 FT. TO COR 2007, and an arrow pointing to the corner. Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p>						

**Dependent Resurvey of the Subdivisional Lines,
T. 24 N., R. 18 E., Gila and Salt River Meridian, Arizona**

CHAINS	
	<p>A stainless steel post, 28 ins. long, 2 1/2 ins. diam., set 24 ins. in the ground, for a reference monument, bears S. 50°20' W., 104.40 ft. dist., with brass cap mkd. RM T24N R18E 1/4 S36 104.4 FT. TO COR 2007, and an arrow pointing to the corner. Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p> <p>Cor. is located 6 lks. E. of the center of Navajo Route 60, and 2.28 chs. W. of a power line, 4 strand, bears North and South.</p> <p>From this cor. point, a brass disk, 3 ins. diam., set in a concrete collar, 6 ins. diam., firmly set, projecting 8 ins. above ground, mkd. BIA ROADS 19, bears N. 36°57' E., 1.29 chs. dist.</p> <p>From this same cor. point, a brass disk, 3 ins. diam., set in a concrete collar, 6 ins. diam., firmly set, projecting 10 ins. above ground, mkd. BIA ROADS 19, bears N. 32°56' W., 1.35 chs. dist.</p>
72.30	Trail road, bears North and South.
76.54	The cor. of secs. 25, 26, 35 and 36.
	<hr/> <p>N. 0°12' E., bet. secs. 25 and 26.</p> <p>Over broken land, ascend Hopi Buttes.</p>
40.08	<p>Point for the 1/4 sec. cor. of secs. 25 and 26, at proportionate dist., there is no remaining evidence of the orig. cor.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T 24 N R 18 E 1/4 S 26 S 25 2007</p> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p> <p>From this cor. point, a juniper post, 4 ins. diam., firmly set, projecting 12 ins. above ground, mkd. 1/4 A on W. face, bears N. 49°00' W., 3.13 chs. dist.</p>
80.16	<p>Point for the cor. of secs. 23, 24, 25 and 26, at proportionate dist., there is no remaining evidence of the orig. cor.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p>

**Dependent Resurvey of the Subdivisional Lines,
T. 24 N., R. 18 E., Gila and Salt River Meridian, Arizona**

CHAINS	
	T 24 N R 18 E S 23 S 24 S 26 S 25 2007
	Deposit a magnet, in a white plastic case, at the base of the stainless steel post.
	<hr/> From the cor. of secs. 19, 24, 25 and 30. N. 89°12' W., bet. secs. 24 and 25. Over broken land.
37.80	Power line, 4 strand, bears S. 15° E. and N. 15° W.
38.74	Navajo Route 60, asphalt surface, 22 ft. wide, bears S. 10° E. and N. 10° W.
40.135	Point for the 1/4 sec. cor. of secs. 24 and 25, at proportionate dist., there is no remaining evidence of the orig. cor. Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.
	T 24 N R 18 E S 24 1/4 ——— S 25 2007
	Deposit a magnet, in a white plastic case, at the base of the stainless steel post. Set a steel fence post nearby. From this cor. point, a brass disk, 3 ins. diam., set in a concrete collar, 6 ins. diam., firmly set, projecting 9 ins. above ground, mkd. BIA ROADS 19, bears S. 84°44' E., 66 lks. dist.
80.27	The cor. of secs. 23, 24, 25 and 26. <hr/> N. 0°11' E., bet. secs. 23 and 24. Over broken land, descend N. slope of Hopi Buttes.
40.08	Point for the 1/4 sec. cor. of secs. 23 and 24, at proportionate dist., there is no remaining evidence of the orig. cor.

Dependent Resurvey of the Subdivisional Lines,
T. 24 N., R. 18 E., Gila and Salt River Meridian, Arizona

CHAINS	
80.16	<p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T 24 N R 18 E 1/4 S 23 S 24</p> <p style="text-align: center;">2007</p> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p> <p>Set a steel fence post nearby.</p> <p>Point for the cor. of secs. 13, 14, 23 and 24, at proportionate dist., there is no remaining evidence of the orig. cor.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T 24 N R 18 E S 14 S 13 S 23 S 24</p> <p style="text-align: center;">2007</p> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p> <p>From this cor. point, a rebar, 5/8 in. diam., firmly set in an iron pipe, 1 in. diam., firmly set, projecting 2 ins. above ground, bears N. 1°05' W., 1.46 chs. dist., with a steel fence post nearby.</p> <hr/> <p>From the cor. of secs. 13, 18, 19 and 24, on the E. bdy. of the Tp.</p> <p>N. 88°54' W., bet. secs. 13 and 24.</p> <p>Over rolling and broken land.</p>
20.00	<p>Point for the E. 1/16 sec. cor. of secs. 13 and 24.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p>

**Dependent Resurvey of the Subdivisional Lines,
T. 24 N., R. 18 E., Gila and Salt River Meridian, Arizona**

CHAINS	
	T 24 N R 18 E S 13 E 1/16 ——— S 24 2007
	Deposit a magnet, in a white plastic case, at the base of the stainless steel post. Set a steel fence post nearby.
40.00	Point for the 1/4 sec. cor. of secs. 13 and 24, at proportionate dist., there is no remaining evidence of the orig. cor. Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd. <div style="text-align: center;"> T 24 N R 18 E S 13 1/4 ——— S 24 2007 </div> Deposit a magnet, in a white plastic case, at the base of the stainless steel post. Set a steel fence post nearby. From this cor. point, a rebar, 5/8 in. diam., firmly set in an iron pipe, 2 ins. diam., firmly set, projecting 2 ins. above ground, bears S. 1°00' W., 73 lks. dist., with a steel fence post nearby.
55.96	From this point, a brass disk, 3 ins. diam., set in a concrete collar, 6 ins. diam., firmly set, projecting 10 ins. above ground, mkd. BIA ROADS 19, bears South, 1.10 chs. dist.
56.00	Power line, 4 strand, bears S. 15° E. and N. 15° W.
57.04	Navajo Route 60, asphalt surface, 21 ft. wide, bears S. 15° E. and N. 15° W.
57.43	From this point, a brass disk, 3 ins. diam., set in a concrete collar, 6 ins. diam., firmly set, projecting 9 ins. above ground, mkd. BIA ROADS 19, bears South, 1.46 chs. dist.
79.99	The cor. of secs. 13, 14, 23 and 24. <hr/> N. 0°04' W., bet. secs. 13 and 14. Over rolling land.

**Dependent Resurvey of the Subdivisional Lines,
T. 24 N., R. 18 E., Gila and Salt River Meridian, Arizona**

CHAINS	
33.11	Navajo Route 60, asphalt surface, 21 ft. wide, bears S. 35° E. and N. 35° W.
34.60	Power line, 4 strand, bears S. 35° E. and N. 35° W.
40.08	Point for the 1/4 sec. cor. of secs. 13 and 14, at proportionate dist., there is no remaining evidence of the orig. cor. Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd. <div style="text-align: center;"> T 24 N R 18 E 1/4 S 14 S 13 2007 </div> Deposit a magnet, in a white plastic case, at the base of the stainless steel post. Set a steel fence post nearby. Cor. is located 95 lks. N. of a power line, 2 strand, bears N. 60° E. and S. 60° W.
80.16	Point for the cor. of secs. 11, 12, 13 and 14, at proportionate dist., there is no remaining evidence of the orig. cor. Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd. <div style="text-align: center;"> T 24 N R 18 E S 11 S 12 S 14 S 13 2007 </div> Deposit a magnet, in a white plastic case, at the base of the stainless steel post. Set a steel fence post nearby. <hr/> From the cor. of sec. 7, 12, 13, and 18, on the E. bdy. of the Tp. N. 89°04' W., bet. secs. 12 and 13. Over rolling land.
10.50	Navajo Route 9065, a graded road, 25 ft. wide, bears S. 75° E. and N. 75° W.,

**Dependent Resurvey of the Subdivisional Lines,
T. 24 N., R. 18 E., Gila and Salt River Meridian, Arizona**

CHAINS	
40.06	<p>Point for the 1/4 sec. cor. of secs. 12 and 13, at proportionate dist., there is no remaining evidence of the orig. cor.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T 24 N R 18 E S 12 1/4 ——— S 13</p> <p style="text-align: center;">2007</p> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p> <p>Set a steel fence post nearby.</p>
71.00	Tees Toh Wash, 30 ft. wide, 2 ft. deep, drains N. 15° W.
80.11	The cor. of secs. 11, 12, 13 and 14.
	<hr/> <p>N. 0°17' E., bet. secs. 11 and 12.</p> <p>Over rolling land.</p>
9.60	Tees Toh Wash, 30 ft. wide, 2 ft. deep, drains N. 75° W.
24.10	Navajo Route 9065, a graded road, 20 ft. wide, bears S. 75° E. and N. 75° W.
40.08	<p>Point for the 1/4 sec. cor. of secs. 11 and 12, at proportionate dist., there is no remaining evidence of the orig. cor.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T 24 N R 18 E 1/4 S 11 S 12</p> <p style="text-align: center;">2007</p> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p> <p>Set a steel fence post nearby.</p>
57.09	Barbed wire fence, 5 strand, bears East and West.

**Dependent Resurvey of the Subdivisional Lines,
T. 24 N., R. 18 E., Gila and Salt River Meridian, Arizona**

CHAINS	<p>From this point, the 159 1/2 Mile Post of the S. bdy. of 1882 Executive Order Hopi Indian Reservation, bears East, 21.18 chs. dist., monumented with an iron post, 2 1/2 diam., firmly set, projecting 4 ins. above ground, with brass cap mkd. EO 1882 159 1/2M NAVAJO 1964. Add the marks 2007 to the brass cap.</p> <p>Cor. is located in a barbed wire fence, 5 strand, bears East and West.</p> <p>From this same point, the 159 Mile Post of the S. bdy. of 1882 Executive Order Hopi Indian Reservation, bears West, 18.83 chs. dist., monumented with an iron post, 2 1/2 diam., set 16 ins. below the surface of the ground, with brass cap mkd. EO 1882 159M NAVAJO 1964. Add the marks 2007 to the brass cap.</p> <p>Cor. is located in a barbed wire fence, 5 strand, bears East and West.</p>								
80.16	<p>The cor. of secs. 1, 2, 11 and 12, determined at the center of a mound of stone, 2 ft. base and 1 ft. high. This is accepted as the best available evidence of the orig. cor. position.</p> <p>At the corner point</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, in an embedded mound of stone, with brass cap mkd.</p> <table border="0" style="margin-left: auto; margin-right: auto;"> <tr> <td colspan="2">T 24 N</td> <td colspan="2">R 18 E</td> </tr> <tr> <td style="border-right: 1px solid black; padding: 0 5px;">S 2</td> <td style="padding: 0 5px;">S 1</td> <td style="border-right: 1px solid black; padding: 0 5px;">S 11</td> <td style="padding: 0 5px;">S 12</td> </tr> </table> <p align="center">2007</p> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p> <p>Set a steel fence post nearby.</p> <hr/> <p align="center">Restoring the resurvey executed by Sidney E. Blout, in 1910</p> <hr/> <p>From the cor. of secs. 1, 6, 7 and 12, on the E. bdy. of the Tp., hereinbefore described.</p> <p>N. 89°31' W., bet. secs. 1 and 12.</p> <p>Over rolling desert land.</p>	T 24 N		R 18 E		S 2	S 1	S 11	S 12
T 24 N		R 18 E							
S 2	S 1	S 11	S 12						
39.80	<p>Point for the 1/4 sec. cor. of secs. 1 and 12, at proportionate dist., there is no remaining evidence of the 1910 cor.</p>								

**Dependent Resurvey of the Subdivisional Lines,
T. 24 N., R. 18 E., Gila and Salt River Meridian, Arizona**

CHAINS	
	<p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T 24 N R 18 E S 1 1/4 ——— S 12</p> <p style="text-align: center;">2007</p> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p> <p>From this cor. point, the cor. of barbed wire fences, 5 strand, extending South and East, bears South, 7 lks. dist.</p>
79.60	<p>The cor. of secs. 1, 2, 11 and 12.</p> <hr/> <p>N. 0°07' E., bet. secs. 1 and 2.</p> <p>Over rolling land.</p>
11.40	Lukai Wash, 15 ft. wide, 3 ft. deep, drains S. 50° W.
39.98	<p>Point for the 1/4 sec. cor. of secs. 1 and 2, at proportionate dist., there is no remaining evidence of the 1910 cor.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T 24 N R 18 E 1/4 S 2 S 1</p> <p style="text-align: center;">2007</p> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p>
45.90	Trail road, bears S. 10° E. and N. 10° W.
50.00	Power line, 2 strand, bears S. 85° E. and N. 85° W.
58.00	Navajo Route 9062, a graded road, 30 ft. wide, bears N. 60° E. and S. 60° W.
81.70	Point for the closing cor. of secs. 1 and 2, at the intersection with the Sixth Standard Parallel North, on the N. bdy. of the Tp. and at 1910 record distance from the stan. 1/4 sec. cor. of sec. 35, T. 25 N., R. 18 E., there is no remaining evidence of the 1910 cor.

**Dependent Resurvey of the Subdivisional Lines,
T. 24 N., R. 18 E., Gila and Salt River Meridian, Arizona**

CHAINS

Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, in an embedded mound of stone, 3 ft. base to top, with brass cap mkd.

T 25 N R 18 E
S 35

S 2 | S 1
T 24 N R 18 E
CC

2007

Deposit a magnet, in a white plastic case, at the base of the stainless steel post.

Cor. is located in a barbed wire fence, 5 strand, bears East and West and 50 lks. S. of a wash, 12 ft. wide, 2 ft. deep, drains S. 80° W.

From this cor. point, the stan. 1/4 sec. cor. of sec. 35, T. 25 N., R. 18 E., identical with Angle Point A-37, Hopi-Navajo Partition Line, Segment "A", bears S. 89°37' E., 3.39 chs. dist., hereinbefore described.

From this same cor. point, the stan. cor. of secs. 34 and 35, T. 25 N., R. 18 E., identical with Angle Point A-36, Hopi-Navajo Partition Line, Segment "A", bears N. 89°37' W., 36.56 chs. dist., hereinbefore described.

Point for the 1/4 sec. cor. of sec. 1 only, T. 24 N., R. 18 E., at midpoint on the N. bdy. of sec. 1.

Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.

T 25 N R 18 E

1/4 S 1
T 24 N R 18 E

2007

Deposit a magnet, in a white plastic case, at the base of the stainless steel post.

Cor. is located in a barbed wire fence, 5 strand, bears East and West.

From this cor. point, the stan. cor. of secs. 35 and 36, T. 25 N., R. 18 E., identical with Angle Point A-38, Hopi-Navajo Partition Line, Segment "A", bears S. 89°47' E., 3.58 chs. dist., hereinbefore described.

**Dependent Resurvey of the Subdivisional Lines,
T. 24 N., R. 18 E., Gila and Salt River Meridian, Arizona**

CHAINS	
	<p>From this same cor. point, the stan. 1/4 sec. cor. sec. 35, T. 25 N., R. 18 E., identical with Angle Point A-37, Hopi-Navajo Partition Line, Segment "A", bears N. 89°47' W., 36.38 chs. dist., hereinbefore described.</p> <hr/> <p style="text-align: center;">Restoring the survey executed by A. P. Johnson, in 1883</p> <hr/> <p>From the cor. of secs. 2, 3, 34 and 35, on the S. bdy. of the Tp., monumented with a stainless steel post, 2 1/2 ins. diam., firmly set, projecting 18 ins. above the ground, in a mound of stone, 3 ft. base, 1 ft. high, with a steel fence post nearby, with brass cap mkd., T24N R18E S34 S35 S3 S2 T23N 2007.</p> <p>N. 1°17' E., bet. secs. 34 and 35.</p> <p>Over rolling land.</p>
39.82	<p>The 1/4 sec. cor. of secs. 34 and 35, determined at the center of an embedded mound of stone, 2 ft. base, with a basalt stone, 10 X 10 X 6 ins., mkd. with illegible marks on down face, lying loose nearby. This is accepted as the best available evidence of the orig. cor. position.</p> <p>At the corner point</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, in an embedded mound of stone, with brass cap mkd.</p> <p style="text-align: center;">T 24 N R 18 E 1/4 S 34 S 35 2007</p> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p> <p>Bury the marked stone alongside the stainless steel post.</p> <hr/> <p>N. 3°44' W., beginning new measurement.</p>
40.40	<p>Point for the cor. of secs. 26, 27, 34 and 35, at proportionate dist., there is no remaining evidence of the orig. cor.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p>

Dependent Resurvey of the Subdivisional Lines,
T. 24 N., R. 18 E., Gila and Salt River Meridian, Arizona

CHAINS	
	T 24 N R 18 E S 27 S 26 S 34 S 35 2007 Deposit a magnet, in a white plastic case, at the base of the stainless steel post. <hr/> From the cor. of secs. 25, 26, 35 and 36. S. 89°31' W., bet. secs. 26 and 35. Over rolling land.
40.75	Point for the 1/4 sec. cor. of secs. 26 and 35, at proportionate dist., there is no remaining evidence of the orig. cor. Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.
	T 24 N R 18 E S 26 1/4 ——— S 35 2007 Deposit a magnet, in a white plastic case, at the base of the stainless steel post.
45.10	Underground waterline, bears S. 65° E. and N. 65° W.
47.00	Power line, 2 strand, bears S. 60° E. and N. 60° W.
59.76	Navajo Route 602, asphalt surface, 24 ft. wide, bears S. 65° E. and N. 65° W.
77.60	Trail road, bears S. 10° E. and N. 10° W.
81.50	The cor. of secs. 26, 27, 34 and 35. <hr/> N. 1°07' E., bet. secs. 26 and 27. Over rolling land.
11.01	Navajo Route 602, asphalt surface, 24 ft. wide, bears S. 65° E. and N. 65° W.
18.20	Power line, 2 strand, bears S. 65° E. and N. 65° W.

**Dependent Resurvey of the Subdivisional Lines,
T. 24 N., R. 18 E., Gila and Salt River Meridian, Arizona**

CHAINS	
19.20	Underground water line, bears S. 60° E. and N. 60° W.
35.40	Wash, 60 ft. wide, 8 ft. deep, drains N. 85° W.
40.32	<p>Point for the 1/4 sec. cor. of secs. 26 and 27, at proportionate dist., there is no remaining evidence of the orig. cor.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T 24 N R 18 E 1/4 S 27 S 26</p> <p style="text-align: center;">2007</p> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p>
80.64	<p>The cor. of secs. 22, 23, 26 and 27, determined at the center of an embedded mound of stone, 2 ft. base, occupied by the remains of an old corner of fences with wood post extending South and East. This is accepted as the best available evidence of the orig. cor. position.</p> <p>At the corner point</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, in an embedded mound of stone, with brass cap mkd.</p> <p style="text-align: center;">T 24 N R 18 E S 22 S 23 S 27 S 26</p> <p style="text-align: center;">2007</p> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p> <hr/> <p>From the cor. of secs. 23, 24, 25 and 26.</p> <p>S. 89°51' W., bet. secs. 23 and 26.</p> <p>Over broken land, descend W. slope of Hopi Buttes.</p>
40.10	<p>Point for the 1/4 sec. cor. of secs. 23 and 26, at proportionate dist., there is no remaining evidence of the orig. cor.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p>

Dependent Resurvey of the Subdivisional Lines,
T. 24 N., R. 18 E., Gila and Salt River Meridian, Arizona

CHAINS	
	<p style="text-align: center;">T 24 N R 18 E S 23 1/4 ——— S 26</p> <p style="text-align: center;">2007</p>
80.20	<p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p> <p>The cor. of secs. 22, 23, 26 and 27.</p> <hr/>
	<p>N. 0°32' E., bet. secs. 22 and 23.</p> <p>Over broken land, ascend Bobcat Butte.</p>
39.26	<p>Point for the 1/4 sec. cor. of secs. 22 and 23, at proportionate dist., there is no remaining evidence of the orig. cor.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p>
	<p style="text-align: center;">T 24 N R 18 E 1/4 S 22 S 23</p> <p style="text-align: center;">2007</p>
78.52	<p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p>
	<p>The cor. of secs. 14, 15, 22 and 23, determined at the center of a mound of stone, 3 ft. base, 1 ft. high. This is accepted as the best available evidence of the orig. cor. position.</p> <p>At the corner point</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 22 ins. in the ground, in an embedded mound of stone, with brass cap mkd.</p>
	<p style="text-align: center;">T 24 N R 18 E S 15 S 14 S 22 S 23</p> <p style="text-align: center;">2007</p>
	<p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p> <hr/> <p>From the cor. of secs. 13, 14, 23 and 24.</p>

**Dependent Resurvey of the Subdivisional Lines,
T. 24 N., R. 18 E., Gila and Salt River Meridian, Arizona**

CHAINS	
	S. 88°40' W., bet. secs. 14 and 23. Over rolling land.
39.86	Point for the 1/4 sec. cor. of secs. 14 and 23, at proportionate dist., there is no remaining evidence of the orig. cor. Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, in an embedded mound of stone, 2 ft. base, with brass cap mkd. <div style="text-align: center;"> T 24 N R 18 E S 14 1/4 ——— S 23 2007 </div>
79.72	Deposit a magnet, in a white plastic case, at the base of the stainless steel post. The cor. of secs. 14, 15, 22 and 23. <hr/>
	N. 0°08' E., bet. secs. 14 and 15. Over broken and rugged land, descend N. slope of Bobcat Butte and ascend Saddle Butte.
19.40	Underground water line, bears N. 50° E. and S. 50° W.
22.40	Trail road, bears East and West.
40.855	Point for the 1/4 sec. cor. of secs. 14 and 15, at proportionate dist., there is no remaining evidence of the orig. cor. Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd. <div style="text-align: center;"> T 24 N R 18 E 1/4 S 15 S 14 2007 </div>
81.71	Deposit a magnet, in a white plastic case, at the base of the stainless steel post. The cor. of secs. 10, 11, 14 and 15, monumented with a basalt stone, 20 x 15 x 12 ins., firmly set, projecting 16 ins. above ground, mkd. 4 grooves on S. face and 2 grooves on E. face. At the corner point

**Dependent Resurvey of the Subdivisional Lines,
T. 24 N., R. 18 E., Gila and Salt River Meridian, Arizona**

CHAINS	
	<p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T 24 N R 18 E S 10 S 11 S 15 S 14</p> <p style="text-align: center;">2007</p> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p> <p>Bury the orig. stone alongside the stainless steel post.</p> <p>Raise a mound of stone, 4 ft. base, 2 ft. high, W. of cor.</p> <hr/> <p>From the cor. of secs. 11, 12, 13 and 14.</p> <p>S. 89°47' W., bet. secs. 11 and 14.</p> <p>Over rolling land.</p>
33.30	Power line, 4 strand, bears S. 35° E. and N. 35° W.
35.11	Navajo Route 60, asphalt surface, 20 ft. wide, bears S. 45° E. and N. 45° W.
39.72	<p>Point for the 1/4 sec. cor. of secs. 11 and 14, at proportionate dist., there is no remaining evidence of the orig. cor.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T 24 N R 18 E S 11 1/4 ——— S 14</p> <p style="text-align: center;">2007</p> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p> <p>Set a steel fence post nearby.</p> <p>Cor. is located 93 lks. N. of a wash, 30 ft. wide, 2 ft. deep, drains N. 55° W.</p>

**Dependent Resurvey of the Subdivisional Lines,
T. 24 N., R. 18 E., Gila and Salt River Meridian, Arizona**

CHAINS	
79.44	<p>The cor. of secs. 10, 11, 14 and 15.</p> <hr/> <p style="text-align: center;">Restoring the resurvey executed by Sidney E. Blout, in 1910</p> <hr/> <p>N. 0°06' W., bet. secs. 10 and 11.</p> <p>Over broken land.</p>
28.23	Navajo Route 60, asphalt surface, 20 ft. wide, bears S. 60° E. and N. 60° W.
29.30	Power line, 2 strand, bears S. 60° E. and N. 60° W.
30.52	From this point, a rebar, 5/8 in. diam., with yellow plastic cap mkd. NHA 1, bears West, 5.22 chs. dist.
39.98	<p>Point for the 1/4 sec. cor. of secs. 10 and 11, at proportionate dist., there is no remaining evidence of the 1910 cor.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T 24 N R 18 E 1/4 S 10 S 11</p> <p style="text-align: center;">2007</p> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p> <p>From this cor. point, the NE corner of Tees Toh Chapter House, 83 x 64 ft., bears S. 22°27' E., 4.73 chs. dist., the long side bears S. 45° E.</p>
50.20	Navajo Route 9065, a graded road, 25 ft. wide, bears S. 65° E and N. 65° W.
57.38	<p>Barbed wire fence, 5 strand, bears East and West.</p> <p>From this point, the 158 1/2 Mile Post of the S. bdy. of 1882 Executive Order Hopi Indian Reservation, bears East, 20.95 chs. dist., monumented with an iron post, 2 1/2 diam., firmly set, projecting 6 ins. above ground, with brass cap mkd. EO 1882 158 1/2 M NAVAJO 1964. Add the marks 2007 to the brass cap.</p> <p>Cor. is located in a barbed wire fence, 5 strand, bears East and West.</p>

**Dependent Resurvey of the Subdivisional Lines,
T. 24 N., R. 18 E., Gila and Salt River Meridian, Arizona**

CHAINS									
	<p>From this same point, the 158 Mile Post of the S. bdy. of 1882 Executive Order Hopi Indian Reservation, bears West, 19.04 chs. dist., monumented with an iron post, 2 1/2 diam., firmly set, projecting 2 ins. above ground, with brass cap mkd. EO 1882 158M NAVAJO 1964. Add the marks 2007 to the brass cap.</p> <p>Cor. is located in a barbed wire fence, 5 strand, bears East and West.</p>								
58.10	Tees Toh Wash, 60 ft. wide, 2 ft. deep, drains N. 75° W.								
79.96	<p>Point for the cor. of secs. 2, 3, 10 and 11, at proportionate dist., there is no remaining evidence of the 1910 cor.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., flush with the surface of the ground, with brass cap mkd.</p> <div style="text-align: center;"> <table style="margin: auto;"> <tr><td>T 24 N</td><td>R 18 E</td></tr> <tr><td>S 3</td><td>S 2</td></tr> <tr><td>S 10</td><td>S 11</td></tr> </table> <p>2007</p> </div> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p> <p>Cor. is located in a residential area with a mobile home and livestock corrals nearby.</p> <hr/> <p>From the cor. of secs. 1, 2, 11 and 12.</p> <p>S. 89°22' W., bet. secs. 2 and 11.</p> <p>Over rolling land.</p>	T 24 N	R 18 E	S 3	S 2	S 10	S 11		
T 24 N	R 18 E								
S 3	S 2								
S 10	S 11								
23.60	Lukai Wash, 30 ft. wide, 2 ft. deep, drains N. 55° W.								
39.95	<p>The 1/4 sec. cor. of secs. 2 and 11, monumented with a sandstone 18 x 9 x 8 ins., firmly set, projecting 7 ins. above ground, mkd. 1/4 on N. face.</p> <p>At the corner point</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center;"> <table style="margin: auto;"> <tr><td>T 24 N</td><td>R 18 E</td></tr> <tr><td>S 2</td><td></td></tr> <tr><td>1/4</td><td>—</td></tr> <tr><td>S 11</td><td></td></tr> </table> <p>2007</p> </div>	T 24 N	R 18 E	S 2		1/4	—	S 11	
T 24 N	R 18 E								
S 2									
1/4	—								
S 11									

**Dependent Resurvey of the Subdivisional Lines,
T. 24 N., R. 18 E., Gila and Salt River Meridian, Arizona**

CHAINS	
	<p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p> <p>Bury the 1910 stone alongside the stainless steel post.</p> <hr style="width: 20%; margin: 10px auto;"/> <p>S. 89°55' W., beginning new measurement.</p>
40.00	<p>The cor. of secs. 2, 3, 10 and 11.</p> <hr style="width: 80%; margin: 10px auto;"/> <p>N. 0°04' E., bet. secs. 2 and 3.</p> <p>Over rolling desert land.</p>
25.20	<p>Navajo Route 9757, a graded road, 25 ft. wide, bears N. 15° E. and S. 15° W.</p>
39.93	<p>Point for the 1/4 sec. cor. of secs. 2 and 3, at proportionate dist., there is no remaining evidence of the 1910 cor.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T 24 N R 18 E 1/4 S 3 S 2</p> <p style="text-align: center;">2007</p> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p> <p>From this cor. point, the NE cor. of a stucco house, 65 x 32 ft., bears N. 84°00' W., 1.09 chs. dist., the long side bears N. 80° W.</p>
82.56	<p>Point for the closing cor. of secs. 2 and 3, at the intersection with the Sixth Standard Parallel North, on the N. bdy. of the Tp. and at 1910 record distance from the stan. 1/4 sec. cor. of sec. 34, T. 25 N., R. 18 E., there is no remaining evidence of the 1910 cor.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p>

**Dependent Resurvey of the Subdivisional Lines,
T. 24 N., R. 18 E., Gila and Salt River Meridian, Arizona**

CHAINS

T 25 N R 18 E
S 34
 S 3 | S 2
 T 24 N R 18 E
 CC

2007

Deposit a magnet, in a white plastic case, at the base of the stainless steel post.

Cor. is located in a barbed wire fence, 5 strand, bears East and West.

From this cor. point, the stan. 1/4 sec. cor. of sec. 34, T. 25 N., R. 18 E., identical with Angle Point A-35, Hopi-Navajo Partition Line, Segment "A", bears S. 89°53' E., 3.48 chs. dist., hereinbefore described.

From this same cor. point, a juniper post, 3 ins. diam., of unknown origin, firmly set, projecting 10 ins. above ground, no marks visible, bears S. 42°56' W., 1.46 chs. dist. Bury the juniper post, 24 ins. long, in place.

From this same cor. point, the witness corner to the stan. cor. of secs. 33 and 34, T. 25 N., R. 18 E., identical with Angle Point A-34, Hopi-Navajo Partition Line, Segment "A", bears N. 89°53' W., 36.32 chs. dist., hereinbefore described.

Point for the 1/4 sec. cor. of sec. 2 only, T. 24 N., R. 18 E., at midpoint on the N. bdy. of sec. 2.

Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ns. in the ground, with brass cap mkd.

T 25 N R 18 E
1/4 S 2
 T 24 N R 18 E

2007

Deposit a magnet, in a white plastic case, at the base of the stainless steel post.

Cor. is located in a barbed wire fence, 5 strand, bears East and West.

From this cor. point, the stan. cor. of secs. 34 and 35, T. 25 N., R. 18 E., identical with Angle Point A-36, Hopi-Navajo Partition Line, Segment "A", bears S. 89°50' E., 3.44 chs. dist., hereinbefore described.

**Dependent Resurvey of the Subdivisional Lines,
T. 24 N., R. 18 E., Gila and Salt River Meridian, Arizona**

CHAINS	
	<p>From this same cor. point, the stan. 1/4 sec. cor. sec. 34, T. 25 N., R. 18 E., identical with Angle Point A-35, Hopi-Navajo Partition Line, Segment "A", bears N. 89°50' W., 36.52 chs. dist., hereinbefore described.</p> <hr/> <p style="text-align: center;">Restoring the survey executed by A. P. Johnson, in 1883</p> <hr/> <p>From the cor. of secs. 3, 4, 33 and 34, on the S. bdy. of the Tp., monumented with a stainless steel post, 2 1/2 ins. diam., firmly set, projecting 6 ins. above ground, in an embedded mound of stone, with brass cap mkd., T24N R18E S33 S34 S4 S3 T23N 2007.</p> <p>N. 1°14 W., bet. secs. 33 and 34.</p> <p>Over rolling land.</p>
2.80	Graded road, 22 ft. wide, bears N. 70° E. and S. 70° W.
40.03	<p>Point for the 1/4 sec. cor. of secs. 33 and 34, at proportionate dist., there is no remaining evidence of the orig. cor.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T 24 N R 18 E 1/4 S 33 S 34 2007</p> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p>
80.06	<p>Point for the cor. of secs. 27, 28, 33 and 34, at proportionate dist., there is no remaining evidence of the orig. cor.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T 24 N R 18 E S 28 S 27 S 33 S 34 2007</p>

**Dependent Resurvey of the Subdivisional Lines,
T. 24 N., R. 18 E., Gila and Salt River Meridian, Arizona**

CHAINS	
	<p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p> <hr/> <p>From the cor. of secs. 26, 27, 34 and 35.</p> <p>N. 89°53' W., bet. secs. 27 and 34.</p> <p>Over rolling land.</p>
40.80	<p>Point for the 1/4 sec. cor. of secs. 27 and 34, at proportionate dist., there is no remaining evidence of the orig. cor.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center;"> <p>T 24 N R 18 E</p> <p>S 27</p> <p>1/4 ———</p> <p>S 34</p> <p>2007</p> </div> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p>
42.60	Underground water line, bears North and South.
81.59	<p>The cor. of secs. 27, 28, 33 and 34.</p> <hr/> <p>N. 1°07' E., bet. secs. 27 and 28.</p> <p>Over rolling land.</p>
10.90	Underground water line, bears N. 85° E. and S. 85° W.
13.15	Navajo Route 602, asphalt surface, 22 ft. wide, bears N. 85° E. and S. 85° W.
14.30	Woven wire fence, bears N. 85° E. and S. 85° W.
20.20	Woven wire fence, bears N. 85° E. and S. 85° W.
40.03	<p>Point for the 1/4 sec. cor. of secs. 27 and 28, at proportionate dist., there is no remaining evidence of the orig. cor.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p>

Dependent Resurvey of the Subdivisional Lines,
T. 24 N., R. 18 E., Gila and Salt River Meridian, Arizona

CHAINS	
	T 24 N R 18 E
	1/4
	S 28 S 27
	2007
	<p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p>
	<p>Cor. is located 93 lks. E. of the E. right-of-way fence of Arizona State Highway 87, 5 strand, barbed wire, parallels highway.</p>
54.73	<p>E. right-of-way fence of Arizona State Highway 87, 5 strand barbed wire, parallels highway.</p>
80.06	<p>Point for the cor. of secs. 21, 22, 27 and 28, at proportionate dist., there is no remaining evidence of the orig. cor.</p>
	<p>Set a PK nail, 2 1/2 ins. long, flush in the asphalt surface of Arizona State Highway 87.</p>
	<p>from which</p>
	<p style="padding-left: 40px;">A stainless steel post, 28 ins. long, 2 1/2 ins. diam., set 24 ins. in the ground, for a reference monument, bears N. 80°00' E., 111.00 ft. dist., with brass cap mkd. RM T24N R18E S22 111.0 FT. TO COR 2007 and an arrow pointing to the corner. Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p>
	<p style="padding-left: 40px;">Reference monument is located in the E. right-of-way fence of Arizona State Highway 87, barbed wire, 5 strand, parallels highway.</p>
	<p style="padding-left: 40px;">A stainless steel post, 28 ins. long, 2 1/2 ins. diam., set 24 ins. in the ground, for a reference monument, bears S. 80°00' W., 99.00 ft. dist., with brass cap mkd. RM T24N R18E S28 99.0 FT. TO COR 2007 and an arrow pointing to the corner. Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p>
	<p style="padding-left: 40px;">Reference monument is located in the W. right-of-way fence of Arizona State Highway 87, barbed wire, 5 strand, parallels highway.</p>
	<p>Cor. is located 4.5 lks. W. of the center of Arizona State Highway 87, asphalt surface, 30 ft. wide, bears N. 5° E. and S. 5° W.</p>
	<hr/> <p>From the cor. of secs. 22, 23, 26 and 27.</p>
	<p>S. 89°43' W., bet. secs. 22 and 27.</p>

**Dependent Resurvey of the Subdivisional Lines,
T. 24 N., R. 18 E., Gila and Salt River Meridian, Arizona**

CHAINS	
	Over rolling land.
36.80	Power line, 2 strand, bears S. 35° E. and N. 35° W.
40.79	Point for the 1/4 sec. cor. of secs. 22 and 27, at proportionate dist., there is no remaining evidence of the orig. cor. Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd. <div style="text-align: center;"> T 24 N R 18 E S 22 1/4 ——— S 27 2007 </div>
	Deposit a magnet, in a white plastic case, at the base of the stainless steel post.
43.70	Trail road, bears S. 5° E. and N. 5° W.
81.58	The cor. of secs. 21, 22, 27 and 28. <hr/>
	N. 1°34' E., bet. secs. 21 and 22. Over rolling land.
14.25	Arizona State Highway 87, asphalt surface, 26 ft. wide, bears North and South.
30.30	E. right-of-way fence of Arizona State Highway 87, 5 strand barbed wire, parallels highway.
40.04	Point for the 1/4 sec. cor. of secs. 21 and 22, at proportionate dist., there is no remaining evidence of the orig. cor. Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd. <div style="text-align: center;"> T 24 N R 18 E 1/4 S 21 S 22 2007 </div>
	Deposit a magnet, in a white plastic case, at the base of the stainless steel post.
80.08	True point for the cor. of secs. 15, 16, 21 and 22, at proportionate dist., there is no remaining evidence of the orig. cor.; falls within the foundation of a house under construction.

**Dependent Resurvey of the Subdivisional Lines,
T. 24 N., R. 18 E., Gila and Salt River Meridian, Arizona**

CHAINS									
	<p>From this true point, the point selected for the witness cor. to the cor. of secs. 15, 16, 21 and 22, bears N. 80°00' W., 2.50 chs. dist.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center;"> <p>WC</p> <table style="margin: auto;"> <tr> <td>T 24 N</td> <td>R 18 E</td> </tr> <tr> <td>S 16</td> <td>S 15</td> </tr> <tr> <td>S 21</td> <td>S 22</td> </tr> </table> <p style="text-align: center;">2007</p> </div> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p> <p>Set a steel fence post nearby.</p> <p>From the true point, the SW corner of the house, 62 x 40 ft., bears S. 74°00' W., 32 lks. dist., the long side bears N. 5° W.</p> <hr/> <p>From the cor. of secs. 14, 15, 22 and 23.</p> <p>N. 89°12' W., bet. secs. 15 and 22.</p> <p>Over rolling land.</p>	T 24 N	R 18 E	S 16	S 15	S 21	S 22		
T 24 N	R 18 E								
S 16	S 15								
S 21	S 22								
40.05	<p>Point for the 1/4 sec. cor. of secs. 15 and 22, at proportionate dist., there is no remaining evidence of the orig. cor.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center;"> <table style="margin: auto;"> <tr> <td>T 24 N</td> <td>R 18 E</td> </tr> <tr> <td></td> <td>S 15</td> </tr> <tr> <td>1/4</td> <td>—</td> </tr> <tr> <td></td> <td>S 22</td> </tr> </table> <p style="text-align: center;">2007</p> </div> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p>	T 24 N	R 18 E		S 15	1/4	—		S 22
T 24 N	R 18 E								
	S 15								
1/4	—								
	S 22								
48.20	<p>Trail road, bears N. 5° E. and S. 5° W.</p>								
80.10	<p>True point for the cor. of secs. 15, 16, 21 and 22.</p> <hr/> <p>N. 0°33' E., bet. secs. 15 and 16.</p> <p>Over rolling land.</p>								

**Dependent Resurvey of the Subdivisional Lines,
T. 24 N., R. 18 E., Gila and Salt River Meridian, Arizona**

CHAINS	
40.03	<p>Point for the 1/4 sec. cor. of secs. 15 and 16, at proportionate dist., there is no remaining evidence of the orig. cor.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T 24 N R 18 E 1/4 S 16 S 15</p> <p style="text-align: center;">2007</p> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p>
80.06	<p>Point for the cor. of secs. 9, 10, 15 and 16, at proportionate dist., there is no remaining evidence of the orig. cor.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T 24 N R 18 E S 9 S 10 S 16 S 15</p> <p style="text-align: center;">2007</p> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p> <hr/> <p>From the cor. of secs. 10, 11, 14 and 15.</p> <p>S. 89°37' W., bet. secs. 10 and 15.</p> <p>Over rolling land.</p>
39.75	<p>Point for the 1/4 sec. cor. of secs. 10 and 15, at proportionate dist., there is no remaining evidence of the orig. cor.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T 24 N R 18 E S 10 1/4 ——— S 15</p> <p style="text-align: center;">2007</p> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p>

**Dependent Resurvey of the Subdivisional Lines,
T. 24 N., R. 18 E., Gila and Salt River Meridian, Arizona**

CHAINS	
	Cor. is located 2.80 chs. E. of a trail road, bears N. 35° E. and S. 35° W.
79.50	The cor. of secs. 9, 10, 15 and 16. <hr/>
	N. 0°32' E., bet. secs. 9 and 10. Over rolling land.
29.87	Navajo Route 60, asphalt surface, 22 ft. wide, bears N. 80° E. and S. 80° W.
31.30	Power line, 4 strand, bears N. 80° E. and S. 80° W.
40.03	Point for the 1/4 sec. cor. of secs. 9 and 10, at proportionate dist., there is no remaining evidence of the orig. cor. Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd. <div style="text-align: center;"> T 24 N R 18 E 1/4 S 9 S 10 2007 </div>
	Deposit a magnet, in a white plastic case, at the base of the stainless steel post.
57.92	Barbed wire fence, 5 strand, bears East and West.
77.40	Tees Toh Wash, 80 ft. wide, 3 ft. deep, drains S. 40° W.
80.06	The cor. of secs. 3, 4, 9 and 10, at single proportionate dist., based on the 1910 resurvey record, there is no remaining evidence of the orig. cor. Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, encircled with an embedded collar of stone, with brass cap mkd. <div style="text-align: center;"> T 24 N R 18 E S 4 S 3 <hr style="width: 50%; margin: 0 auto;"/> S 9 S 10 2007 </div>
	Deposit a magnet, in a white plastic case, at the base of the stainless steel post.

**Dependent Resurvey of the Subdivisional Lines,
T. 24 N., R. 18 E., Gila and Salt River Meridian, Arizona**

CHAINS	
	<p>Cor. is located 2.30 chs. W. of Tees Toh Wash, 80 ft. wide, 3 ft. deep, drains S. 40° W.</p> <hr/> <p style="text-align: center;">Restoring the resurvey executed by Sidney E. Blout, in 1910</p> <hr/> <p>From the cor. of secs. 2, 3, 10 and 11.</p> <p>S. 89°25' W., bet. secs. 3 and 10.</p> <p>Over rolling desert land.</p>
6.90	Navajo Route 9757, a graded road, 25 ft. wide, bears N. 15° E. and S. 15° W.
39.30	<p>The 1/4 sec. cor. of secs. 3 and 10, monumented with a basalt stone, 14 x 6 x 5 ins., firmly set, projecting 5 ins. above ground, mkd. 1/4 on N. face.</p> <p>At the corner point</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center;"> <p>T 24 N R 18 E</p> <p>S 3</p> <p>1/4 ———</p> <p>S 10</p> <p>2007</p> </div> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p> <p>Bury the 1910 stone alongside the stainless steel post.</p> <hr/> <p>S. 89°56' W., beginning new measurement.</p>
27.80	Tees Toh Wash, 40 ft. wide, 5 ft. deep, drains N. 40° W.
39.31	<p>The cor. of secs. 3, 4, 9 and 10.</p> <hr/> <p>N. 0°05' E., bet. secs. 3 and 4.</p> <p>Over rolling desert land.</p>
40.00	Point for the 1/4 sec. cor. of secs. 3 and 4, at proportionate dist., there is no remaining evidence of the 1910 cor.

**Dependent Resurvey of the Subdivisional Lines,
T. 24 N., R. 18 E., Gila and Salt River Meridian, Arizona**

CHAINS	<p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T 24 N R 18 E 1/4 S 4 S 3</p> <p style="text-align: center;">2007</p> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p>
83.19	<p>Point for the closing cor. of secs. 3 and 4, at the intersection with the Sixth Standard Parallel North, on the N. bdy. of the Tp. and at 1910 record distance from the stan. 1/4 sec. cor. of sec. 33, T. 25 N., R. 18 E., there is no remaining evidence of the 1910 cor.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T 25 N R 18 E S 33 ----- S 4 S 3 T 24 N R 18 E CC</p> <p style="text-align: center;">2007</p> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p> <p>Cor. is located in a barbed wire fence, 5 strand, bears East and West.</p> <p>From this cor. point, the stan. 1/4 sec. cor. of sec. 33, T. 25 N., R. 18 E., identical with Angle Point A-33, Hopi-Navajo Partition Line, Segment "A", bears S. 89°52' E., 2.13 chs. dist., hereinbefore described.</p> <p>From this same cor. point, the stan. cor. of secs. 32 and 33, T. 25 N., R. 18 E., identical with Angle Point A-32, Hopi-Navajo Partition Line, Segment "A", bears N. 89°52' W., 37.85 chs. dist., hereinbefore described.</p> <hr style="width: 50%; margin: 10px auto;"/> <p>Point for the 1/4 sec. cor. of sec. 3 only, T. 24 N., R. 18 E., at midpoint on the N. bdy. of sec. 3.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p>

Dependent Resurvey of the Subdivisional Lines,
T. 24 N., R. 18 E., Gila and Salt River Meridian, Arizona

CHAINS	
	<p style="text-align: center;">T 25 N R 18 E</p> <hr style="width: 10%; margin: auto;"/> <p style="text-align: center;">1/4 S 3</p> <p style="text-align: center;">T 24 N R 18 E</p> <p style="text-align: center;">2007</p> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p> <p>Cor. is located in a barbed wire fence, 5 strand, bears East and West.</p> <p>From this cor. point, the true point for the stan. cor. of secs. 33 and 34, T. 25 N., R. 18 E., identical with Angle Point A-34, Hopi-Navajo Partition Line, Segment "A", bears S. 89°52' E., 2.81 chs. dist., hereinbefore described.</p> <p>From this same cor. point, Angle Point A-33D, Hopi-Navajo Partition Line, Segment "A", on the Sixth Standard Parallel North (south boundary), T. 25 N., R. 18 E., bears N. 89°52' W., 26.81 chs. dist., hereinbefore described.</p> <hr/> <p style="text-align: center;">Restoring the survey executed by A. P. Johnson, in 1883</p> <hr/> <p>From the cor. of secs. 4, 5, 32 and 33, on the S. bdy. of the Tp., monumented with a stainless steel post, 2 1/2 ins. diam., firmly set, projecting 7 ins. above ground, with brass cap mkd. T24N R18E S32 S33 S5 S4 T23N 2007.</p> <p>N. 0°55 W., bet. secs. 32 and 33.</p> <p>Over rolling land.</p>
37.30	Trail road, bears S. 40° E. and N. 40° W.
40.09	<p>Point for the 1/4 sec. cor. of secs. 32 and 33, at proportionate dist., there is no remaining evidence of the orig. cor.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., flush with the surface of the ground, with brass cap mkd.</p> <p style="text-align: center;">T 24 N R 18 E</p> <p style="text-align: center;">1/4</p> <p style="text-align: center;">S 32 S 33</p> <p style="text-align: center;">2007</p> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p>

**Dependent Resurvey of the Subdivisional Lines,
T. 24 N., R. 18 E., Gila and Salt River Meridian, Arizona**

CHAINS							
	Set a steel fence post nearby.						
	Cor. is located 12 lks. N. of a trail road, bears East and West.						
76.60	Trail road, bears N. 30° E. and S. 30° W.						
80.18	Point for the cor. of secs. 28, 29, 32 and 33, at proportionate dist., there is no remaining evidence of the orig. cor.						
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.						
	<table style="margin: auto;"> <tr> <td colspan="2">T 24 N R 18 E</td> </tr> <tr> <td style="border-right: 1px solid black; text-align: center;">S 29</td> <td style="text-align: center;">S 28</td> </tr> <tr> <td style="border-right: 1px solid black; text-align: center;">S 32</td> <td style="text-align: center;">S 33</td> </tr> </table>	T 24 N R 18 E		S 29	S 28	S 32	S 33
T 24 N R 18 E							
S 29	S 28						
S 32	S 33						
	2007						
	Deposit a magnet, in a white plastic case, at the base of the stainless steel post.						
	Set a steel fence post nearby.						
	Cor. is located 53 lks. E. of a trail road, bears N. 50° E. and S. 50° W.						
	<hr/>						
	From the cor. of secs. 27, 28, 33 and 34.						
	N. 89°45' W., bet. secs. 28 and 33.						
	Over rolling land.						
3.49	E. right-of-way fence of Arizona State Highway 87, 5 strand barbed wire, parallels highway.						
5.04	Arizona State Highway 87, asphalt surface, 30 ft. wide, bears N. 5° E. and S. 5° W.						
6.54	W. right-of-way fence of Arizona State Highway 87, 5 strand barbed wire, parallels highway.						
40.60	Point for the 1/4 sec. cor. of secs. 28 and 33, at proportionate dist., there is no remaining evidence of the orig. cor.						
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.						

**Dependent Resurvey of the Subdivisional Lines,
T. 24 N., R. 18 E., Gila and Salt River Meridian, Arizona**

CHAINS	
	T 24 N R 18 E S 28 1/4 ——— S 33 2007
	Deposit a magnet, in a white plastic case, at the base of the stainless steel post.
77.20	Trail road, bears S. 10° E. and N. 10° W.
78.60	Trail road, bears N. 30° E. and S. 30° W.
81.20	The cor. of secs. 28, 29, 32 and 33.
	<hr/> N. 0°59' E., bet. secs. 28 and 29. Over rolling land.
2.70	Underground pipe line, bears N. 85° E. and S. 85° W.
3.90	Navajo Route 9844, a graded road, 30 ft. wide, bears N. 85° E. and S. 85° W.
36.80	Trail road, bears S. 70° E. and N. 70° W.
40.09	Point for the 1/4 sec. cor. of secs. 28 and 29, at proportionate dist., there is no remaining evidence of the orig. cor.
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.
	T 24 N R 18 E 1/4 S 29 S 28 2007
	Deposit a magnet, in a white plastic case, at the base of the stainless steel post.
53.30	Trail road, bears N. 70° E. and S. 70° W.
56.80	Power line, 2 strand, bears S. 85° E. and N. 85° W.
80.18	Point for the cor. of secs. 20, 21, 28 and 29, at proportionate dist., there is no remaining evidence of the orig. cor.
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.

**Dependent Resurvey of the Subdivisional Lines,
T. 24 N., R. 18 E., Gila and Salt River Meridian, Arizona**

CHAINS	
	T 24 N R 18 E S 20 S 21 S 29 S 28 2007
	Deposit a magnet, in a white plastic case, at the base of the stainless steel post.
	<hr/> From the cor. of secs. 21, 22, 27 and 28. N. 89°40' W., bet. secs. 21 and 28. Over rolling land.
32.00	Trail road, bears S. 65° E. and N. 65° W.
40.69	Point for the 1/4 sec. cor. of secs. 21 and 28, at proportionate dist., there is no remaining evidence of the orig. cor. Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.
	T 24 N R 18 E S 21 1/4 ——— S 28 2007
	Deposit a magnet, in a white plastic case, at the base of the stainless steel post.
64.20	Trail road, bears S. 25° E. and N. 25° W.
81.38	The cor. of secs. 20, 21, 28 and 29. <hr/> N. 2°46' E., bet. secs. 20 and 21. Over rolling land.
11.30	Trail road, bears S. 65° E. and N. 65° W.
40.13	Point for the 1/4 sec. cor. of secs. 20 and 21, at proportionate dist., there is no remaining evidence of the orig. cor. Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.

**Dependent Resurvey of the Subdivisional Lines,
T. 24 N., R. 18 E., Gila and Salt River Meridian, Arizona**

CHAINS	
	T 24 N R 18 E 1/4 S 20 S 21 2007
	Deposit a magnet, in a white plastic case, at the base of the stainless steel post.
	Cor. located 66 lks. N. of a power line, 2 strand, bears N. 60° E. and S. 60° W.
49.80	Trail road, bears N. 70° E. and S. 70° W.
68.60	Navajo Route 9845, a graded road, 20 ft. wide, bears N. 35° E. and S. 35° W.
80.26	Point for the cor. of secs. 16, 17, 20 and 21, at proportionate dist., there is no remaining evidence of the orig. cor.
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.
	T 24 N R 18 E S 17 S 16 S 20 S 21 2007
	Deposit a magnet, in a white plastic case, at the base of the stainless steel post.
	Raise a mound of stone, 2 ft. base, 1 ft. high, W. of cor.
	<hr/> From the true point for the cor. of secs. 15, 16, 21 and 22. N. 89°34' W., bet. secs. 16 and 21. Over rolling land.
3.40	Power line, 2 strand, bears S. 5° E. and N. 5° W.
13.22	E. right-of-way fence of Arizona State Highway 87, 5 strand barbed wire, parallels highway.
14.80	Arizona State Highway 87, asphalt surface, 30 ft. wide, bears S. 15° E. and N. 15° W.
16.40	W. right-of-way fence of Arizona State Highway 87, 5 strand barbed wire, parallels highway.
38.20	Wash, 40 ft. wide, 6 ft. deep, drains N.

**Dependent Resurvey of the Subdivisional Lines,
T. 24 N., R. 18 E., Gila and Salt River Meridian, Arizona**

CHAINS	
39.84	<p>Point for the 1/4 sec. cor. of secs. 16 and 21, at proportionate dist., there is no remaining evidence of the orig. cor.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center;"> <p>T 24 N R 18 E S 16 1/4 ——— S 21</p> <p>2007</p> </div> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p>
72.70	<p>Navajo Route 9845, a graded road, 20 ft. wide, bears N. 30° E. and S. 30° W.</p>
79.68	<p>The cor. of secs. 16, 17, 20 and 21.</p> <hr/> <p>N. 0°23' E., bet. secs. 16 and 17.</p> <p>Over rolling land, E. slope of Bad Medicine Butte.</p>
40.09	<p>Point for the 1/4 sec. cor. of secs. 16 and 17, at proportionate dist., there is no remaining evidence of the orig. cor.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center;"> <p>T 24 N R 18 E 1/4 S 17 S 16</p> <p>2007</p> </div> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p>
80.18	<p>The cor. of secs. 8, 9, 16 and 17, monumented with a basalt stone, 15 x 12 x 10 ins., firmly set, projecting 1 in. above ground, mkd. 4 grooves on S. and E. sides.</p> <p>At the corner point</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p>

Dependent Resurvey of the Subdivisional Lines,
T. 24 N., R. 18 E., Gila and Salt River Meridian, Arizona

CHAINS	
	<p style="text-align: center;">T 24 N R 18 E S 8 S 9 ----- S 17 S 16</p> <p style="text-align: center;">2007</p> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p> <p>Bury the orig. stone alongside the stainless steel post.</p> <p>Raise a mound of stone, 4 ft. base, 1 ft. high, W. of cor.</p> <hr/> <p>From the cor. of secs. 9, 10, 15 and 16.</p> <p>N. 89°29' W., bet. secs. 9 and 16.</p> <p>Over rolling land.</p>
37.90	E. right-of-way fence of Arizona State Highway 87, 5 strand barbed wire, parallels highway.
39.955	<p>Point for the 1/4 sec. cor. of secs. 9 and 16, at proportionate dist., there is no remaining evidence of the orig. cor.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., flush with the surface of the ground, with brass cap mkd.</p>
	<p style="text-align: center;">T 24 N R 18 E S 9 1/4 ----- S 16</p> <p style="text-align: center;">2007</p> <p>from which</p> <p style="padding-left: 40px;">A stainless steel post, 28 ins. long, 2 1/2 ins. diam., set 24 ins. in the ground, for a reference monument, bears N. 70°00' E., 130.00 ft. dist., with brass cap mkd. RM T24N R18E 1/4 S9 130.0 FT. TO COR 2007 and an arrow pointing to the cor. Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p> <p style="padding-left: 40px;">Reference monument is located in the E. right-of-way fence of Arizona State Highway 87, barbed wire, 5 strand, parallels highway.</p>

**Dependent Resurvey of the Subdivisional Lines,
T. 24 N., R. 18 E., Gila and Salt River Meridian, Arizona**

CHAINS	
	<p>A stainless steel post, 28 ins. long, 2 1/2 ins. diam., set 24 ins. in the ground, for a reference monument, bears S. 70°00' W., 70.00 ft. dist., with brass cap mkd. RM T24N R18E 1/4 S16 70.0 FT. TO COR 2007 and an arrow pointing to the cor. Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p> <p>Reference monument is located in the W. right-of-way fence of Arizona State Highway 87, barbed wire, 5 strand, parallels highway.</p> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post at the 1/4 sec. cor.</p> <p>Cor. is located 46 lks. W. of the center of Arizona State Highway 87, asphalt surface, 28 ft. wide, bears S. 15° E. and N. 15° W. and 1.09 chs. E. of the W. right-of-way fence of Arizona State Highway 87, 5 strand barbed wire, parallels highway.</p>
60.30	Wash, 20 ft. wide, 2 ft. deep, drains N. 50° W.
69.90	Navajo Route 9845, a graded road, 18 ft. wide, bears N. 30° E. and S. 30° W.
79.905	The cor. of secs. 8, 9, 16 and 17.
<hr/> <p>Restoring the resurvey executed by Sidney E. Blout, in 1910</p> <hr/>	
	N. 0°01' W., bet. secs. 8 and 9.
	Over rolling land.
10.80	Navajo Route 9845, a graded road, 20 ft. wide, bears S. 50° E. and N. 50° W.
19.80	Trail road, bears N. 70° E. and S. 70° W.
22.80	Wash, 20 ft. wide, 5 ft. deep, drains N. 80° W.
25.50	Power line, 2 strand, bears N. 20° E. and S. 20° W.
31.46	From this point, a brass disk, 3 ins. diam., set in a concrete collar, 6 ins. diam., firmly set, projecting 10 ins. above ground, mkd. BIA ROAD 19, bears East, 33 lks. dist.
32.53	Navajo Route 60, asphalt surface, 22 ft. wide, bears S. 60° W. and N. 60° W.
40.03	Point for the 1/4 sec. cor. of secs. 8 and 9, at proportionate dist., there is no remaining evidence of the 1910 cor.

**Dependent Resurvey of the Subdivisional Lines,
T. 24 N., R. 18 E., Gila and Salt River Meridian, Arizona**

CHAINS	
	<p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T 24 N R 18 E 1/4 S 8 S 9</p> <p style="text-align: center;">2007</p> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p> <p>Set a steel fence post nearby.</p> <p>Cor. is located 63 lks. S. of a power line, 2 strand, bears S. 75° E. and N. 75° W.</p>
57.22	<p>Barbed wire fence, 5 strand, bears East and West.</p> <p>From this point, the 156 1/2 Mile Post of the S. bdy. of 1882 Executive Order Hopi Indian Reservation, bears East, 20.22 chs. dist., monumented with an iron post, 2 1/2 diam., firmly set, projecting 6 ins. above ground, with brass cap mkd. EO 1882 156 1/2 M NAVAJO 1964. Add the marks 2007 to the brass cap.</p> <p>Cor. is located in a barbed wire fence, 5 strand, bears East and West.</p> <p>From this same point, the 156 Mile Post of the S. bdy. of 1882 Executive Order Hopi Indian Reservation, bears West, 19.79 chs. dist., monumented with an iron post, 2 1/2 diam., set flush with the surface of the ground, with brass cap mkd. EO 1882 156 M NAVAJO 1964. Add the marks 2007 to the brass cap.</p> <p>Cor. is located 4.5 lks. S. of a barbed wire fence, 5 strand, bears East and West.</p>
64.30	<p>Tees Toh Wash, 75 ft. wide, 10 ft. deep, drains N. 70° W.</p>
80.06	<p>Point for the cor. of secs. 4, 5, 8 and 9, at proportionate dist., there is no remaining evidence of the 1910 cor.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T 24 N R 18 E S 5 S 4 S 8 S 9</p> <p style="text-align: center;">2007</p> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p>

**Dependent Resurvey of the Subdivisional Lines,
T. 24 N., R. 18 E., Gila and Salt River Meridian, Arizona**

CHAINS	
	<p>Set a steel fence post nearby.</p> <hr/> <p>From the cor. of 3, 4, 9 and 10.</p> <p>N. 89°27' W., bet. secs. 4 and 9.</p> <p>Over rolling desert land.</p>
40.35	<p>The 1/4 sec. cor. of secs. 4 and 9, determined 6 ins. S. of the S. edge. of a mound of stone, 2 ft. base, 1 ft. high. This is accepted as the best available evidence of the 1910 cor. position.</p> <p>At the corner point</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, in an embedded mound of stone, with brass cap mkd.</p> <div style="text-align: center; margin: 10px 0;"> <p>T 24 N R 18 E</p> <p style="margin-left: 100px;">S 4</p> <p style="margin-left: 100px;">1/4 ———</p> <p style="margin-left: 100px;">S 9</p> <p style="margin-left: 100px;">2007</p> </div> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p> <hr/> <p>N. 89°30' W., beginning new measurement.</p>
21.70	Power line, 2 strand, bears S. 15° E. and N. 15° W.
22.19	E. right-of-way fence of Arizona State Highway 87, 5 strand barbed wire, parallels highway.
23.78	Arizona State Highway 87, asphalt surface, 38 ft. wide, bears S. 5° E. and N. 5° W.
25.34	W. right-of-way fence of Arizona State Highway 87, 5 strand barbed wire, parallels highway.
40.31	<p>The cor. of secs. 4, 5, 8 and 9.</p> <hr/> <p>N. 0°09' E., bet. secs. 4 and 5.</p> <p>Over rolling desert land.</p>
39.99	The 1/4 sec. cor. of secs. 4 and 5, monumented with a sandstone, 12 x 8 x 8 ins., firmly set, projecting 2 ins. above ground, mkd. 1/4 on W. face.

**Dependent Resurvey of the Subdivisional Lines,
T. 24 N., R. 18 E., Gila and Salt River Meridian, Arizona**

CHAINS	
	At the corner point
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.
	T 24 N R 18 E 1/4 S 5 S 4 2007
	Deposit a magnet, in a white plastic case, at the base of the stainless steel post.
	Bury the 1910 stone alongside the stainless steel post.

	N. 0°08' E., beginning new measurement.
5.30	Power line, 2 strand, bears S. 85° E. and N. 85° W.
9.68	W. right-of-way fence of Arizona State Highway 87, 5 strand barbed wire, parallels highway.
14.95	Arizona State Highway 87, asphalt surface, 30 ft. wide, bears S. 15° E. and N. 15° W.
20.20	E. right-of-way fence of Arizona State Highway 87, 5 strand barbed wire, parallels highway.
42.99	Point for the closing cor. of secs. 4 and 5, at the intersection with the Sixth Standard Parallel North, on the N. bdy. of the Tp. and at 1910 record distance from the stan. 1/4 sec. cor. of sec. 32, T. 25 N., R. 18 E., there is no remaining evidence of the 1910 cor.
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.
	T 25 N R 18 E S 32 S 5 S 4 T 24 N R 18 E CC 2007
	Deposit a magnet, in a white plastic case, at the base of the stainless steel post.
	Cor. is located in a barbed wire fence, 5 strand, bears East and West.

**Dependent Resurvey of the Subdivisional Lines,
T. 24 N., R. 18 E., Gila and Salt River Meridian, Arizona**

CHAINS

From this cor. point, the stan. 1/4 sec. cor. of sec. 32, T. 25 N., R. 18 E., identical with Angle Point A-31, Hopi-Navajo Partition Line, Segment "A", bears S. 89°26' E., 2.82 chs. dist., hereinbefore described.

From this same cor. point, Angle Point A-30D, Hopi-Navajo Partition Line, Segment "A", on the Sixth Standard Parallel North (south boundary), T. 25 N., R. 18 E., bears N. 89°26' W., 15.84 chs. dist., hereinbefore described.

Point for the 1/4 sec. cor. of sec. 4 only, T. 24 N., R. 18 E., at midpoint on the N. bdy. of sec. 4.

Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.

T 25 N R 18 E

1/4 S 4

T 24 N R 18 E

2007

Deposit a magnet, in a white plastic case, at the base of the stainless steel post.

Cor. is located in a barbed wire fence, 5 strand, bears East and West.

From this cor. point, the stan. cor. of secs. 32 and 33, T. 25 N., R. 18 E., identical with Angle Point A-32, Hopi-Navajo Partition Line, Segment "A", bears S. 89°25' E., 2.43 chs. dist., hereinbefore described.

From this same cor. point, the stan. 1/4 sec. cor. of sec. 32, T. 25 N., R. 18 E., identical with Angle Point A-31, Hopi-Navajo Partition Line, Segment "A", bears N. 89°25' W., 37.46 chs. dist., hereinbefore described.

Restoring the survey executed by
A. P. Johnson, in 1883

From the cor. of secs. 5, 6, 31 and 32, on the S. bdy. of the Tp., monumented with a stainless steel post, 2 1/2 ins. diam., firmly set, projecting 4 ins. above ground, encircled with an embedded collar of stone, with brass cap mkd. T24N R18E S31 S32 S6 S5 T23N 2007.

N. 0°42 W., bet. secs. 31 and 32.

Over rolling land.

**Dependent Resurvey of the Subdivisional Lines,
T. 24 N., R. 18 E., Gila and Salt River Meridian, Arizona**

CHAINS	
10.60	Underground water line, bears N. 15° E. and S. 15° W.
12.90	Power line, 2 strand, bears N. 25° E. and S. 25° W.
40.13	Point for the 1/4 sec. cor. of secs. 31 and 32, at proportionate dist., there is no remaining evidence of the orig. cor. Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd. <div style="text-align: center;"> T 24 N R 18 E 1/4 S 31 S 32 2007 </div> Deposit a magnet, in a white plastic case, at the base of the stainless steel post.
75.60	Power line, bears S. 85° E. and N. 85° W.
77.30	Navajo Route 9844, a graded road, 24 ft. wide, bears S. 85° E. and N. 85° W.
80.26	Point for the cor. of secs. 29, 30, 31 and 32, at proportionate dist., there is no remaining evidence of the orig. cor. Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd. <div style="text-align: center;"> T 24 N R 18 E S 30 S 29 S 31 S 32 2007 </div> Deposit a magnet, in a white plastic case, at the base of the stainless steel post.
<hr/>	
	From the cor. of secs. 28, 29, 32 and 33. N. 89°47' W., bet. secs. 29 and 32. Over rolling land.
21.90	Trail road, bears N. 60° E. and S. 60° W.
26.90	Underground water line, bears N. 85° E. and S. 85° W.
36.60	Power line, 2 strand, bears N. 35° E. and S. 35° W.

**Dependent Resurvey of the Subdivisional Lines,
T. 24 N., R. 18 E., Gila and Salt River Meridian, Arizona**

CHAINS	
40.66	<p>Point for the 1/4 sec. cor. of secs. 29 and 32, at proportionate dist., there is no remaining evidence of the orig. cor.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. below the surface of a graded road, with brass cap mkd.</p> <div style="text-align: center;"> <p>T 24 N R 18 E</p> <p>S 29</p> <p>1/4 ———</p> <p>S 32</p> <p>2007</p> </div> <p>from which</p> <p style="padding-left: 40px;">A stainless steel post, 28 ins. long, 2 1/2 ins. diam., set 24 ins. in the ground, for a reference monument, bears North, 60.00 ft. dist., with brass cap mkd. RM T24N R18E 1/4 S29 60.0 FT. TO COR 2007 and an arrow pointing to the corner. Deposit a magnet, in a white plastic case, at the base of the stainless steel post. Set a steel fence post nearby.</p> <p style="padding-left: 40px;">A stainless steel post, 28 ins. long, 2 1/2 ins. diam., set 24 ins. in the ground, for a reference monument, bears South, 60.00 ft. dist., with brass cap mkd. RM T24N R18E 1/4 S32 60.0 FT. TO COR 2007 and an arrow pointing to the corner. Deposit a magnet, in a white plastic case, at the base of the stainless steel post. Set a steel fence post nearby.</p> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post at the 1/4 sec. cor.</p> <p>Cor. is located 65 lks. W. of the center of Navajo Route 9844, a graded road, 20 ft. wide, bears N. 85° E. and S. 85° W.</p>
81.31	<p>The cor. of secs. 29, 30, 31 and 32.</p> <hr/> <p>N. 89°05' W., bet. secs. 30 and 31.</p> <p>Over rolling land.</p>
21.10	<p>Navajo Route 9844, a graded road, 20 ft. wide, bears S. 80° E. and N. 80° W.</p>
40.67	<p>Point for the 1/4 sec. cor. of secs. 30 and 31, at proportionate dist., there is no remaining evidence of the orig. cor.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p>

**Dependent Resurvey of the Subdivisional Lines,
T. 24 N., R. 18 E., Gila and Salt River Meridian, Arizona**

CHAINS	
	T 24 N R 18 E S 30 1/4 ——— S 31 2007
	Deposit a magnet, in a white plastic case, at the base of the stainless steel post.
	Cor. is located 1.04 chs. N. of an underground water line, bears S. 80° W. and N. 80° W.
77.70	The cor. of secs. 25, 30, 31 and 36, on the W. bdy. of the Tp., hereinbefore described.
	<hr/> From the cor. of secs. 29, 30, 31 and 32. N. 0°24' E., bet. secs. 29 and 30. Over rolling land, W. slope of Window Rock Butte.
40.13	Point for the 1/4 sec. cor. of secs. 29 and 30, at proportionate dist., there is no remaining evidence of the orig. cor. Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.
	T 24 N R 18 E 1/4 S 30 S 29 2007
	Deposit a magnet, in a white plastic case, at the base of the stainless steel post.
	Cor. is located 2.56 chs. W. of a barbed wire fence, 5 strand, bears S. 35° E. and N. 35° W.
60.68	Barbed wire fence, 5 strand, bears S. 30° E. and N. 30° W.
75.80	Trail road, bears N. 65° E. and S. 65° W.
77.00	Power line, 2 strand, bears N. 65° E. and S. 65° W.
80.26	Point for the cor. of secs. 19, 20, 29 and 30, at proportionate dist., there is no remaining evidence of the orig. cor. Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.

**Dependent Resurvey of the Subdivisional Lines,
T. 24 N., R. 18 E., Gila and Salt River Meridian, Arizona**

CHAINS	T 24 N R 18 E S 19 S 20 S 30 S 29 2007 Deposit a magnet, in a white plastic case, at the base of the stainless steel post. Cor. is located 2.88 chs. N. of a barbed wire fence, 5 strand, bears S. 30° E. and N. 30° W. <hr/> From the cor. of secs. 20, 21, 28 and 29. N. 89°44' W., bet. secs. 20 and 29. Over rolling land.
23.70	Navajo Route 9845, a graded road, 20 ft. wide, bears N. 10° E. and S. 10° W.
32.93	From this point, the S. cor. of a hexagonal hogan, bears North, 24 lks. dist., one side bears N. 70° E. for 11 ft. and the another side bears N. 65° W. for 9 ft.
35.20	Power line, 2 strand, bears S. 10° E. and N. 10° W.
41.05	Point for the 1/4 sec. cor. of secs. 20 and 29, at proportionate dist., there is no remaining evidence of the orig. cor. Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd. <div style="text-align: center;"> T 24 N R 18 E S 20 1/4 ——— S 29 2007 </div> Deposit a magnet, in a white plastic case, at the base of the stainless steel post.
74.00	Trail road, bears N. 65° E. and S. 65° W.
74.90	Power line, 2 strand, bears S. 65° E. and N. 65° W.
82.10	The cor. of secs. 19, 20, 29 and 30. <hr/> N. 89°34' W., bet. secs. 19 and 30.

**Dependent Resurvey of the Subdivisional Lines,
T. 24 N., R. 18 E., Gila and Salt River Meridian, Arizona**

CHAINS	
	Over rolling land.
11.99	Barbed wire fence, 5 strand, bears S. 30° E. and N. 30° W.
40.87	Point for the 1/4 sec. cor. of secs. 19 and 30, at proportionate dist., there is no remaining evidence of the orig. cor. Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd. <div style="text-align: center;"> T 24 N R 18 E S 19 1/4 ——— S 30 2007 </div>
	Deposit a magnet, in a white plastic case, at the base of the stainless steel post.
78.49	The cor. of secs. 19, 24, 25 and 30, on the W. bdy. of the Tp., hereinbefore described. <hr/> From the cor. of secs. 19, 20, 29 and 30. N. 4°17' E., bet. secs. 19 and 20. Over rolling land.
35.10	Wash, 15 ft. wide, 5 ft. deep, drains N. 50° W.
40.24	Point for the 1/4 sec. cor. of secs. 19 and 20, at proportionate dist., there is no remaining evidence of the orig. cor. Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd. <div style="text-align: center;"> T 24 N R 18 E 1/4 S 19 S 20 2007 </div>
	Deposit a magnet, in a white plastic case, at the base of the stainless steel post.
80.48	The cor. of secs. 17, 18, 19 and 20, monumented with a basalt stone, 9 x 7 x 6 ins., loosely set in a mound of stone, 3 ft. base, 1 ft. high, mkd. 5 grooves on one side and 3 notches on one end. At the corner point

**Dependent Resurvey of the Subdivisional Lines,
T. 24 N., R. 18 E., Gila and Salt River Meridian, Arizona**

CHAINS	
	<p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, in a embedded mound of stone, 3 ft. base, with brass cap mkd.</p> <p style="text-align: center;">T 24 N R 18 E S 18 S 17 S 19 S 20</p> <p style="text-align: center;">2007</p> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p> <hr/> <p>From the cor. of secs. 16, 17, 20 and 21.</p> <p>N. 89°40' W., bet. secs. 17 and 20.</p> <p>Over rolling and broken land, S. slope of Bad Medicine Butte.</p>
39.98	<p>Point for the 1/4 sec. cor. of secs. 17 and 20, at proportionate dist., there is no remaining evidence of the orig. cor.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 20 ins. in the ground, in a mound of stone, 3 ft. base, to top, with brass cap mkd.</p> <p style="text-align: center;">T 24 N R 18 E S 17 1/4 ——— S 20</p> <p style="text-align: center;">2007</p> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p> <p>Cor. is located on the rocky S. slope of Bad Medicine Butte.</p>
79.96	<p>The cor. of secs. 17, 18, 19 and 20.</p> <hr/> <p>S. 89°56' W., bet. secs. 18 and 19.</p> <p>Over rolling land.</p>
43.03	<p>Point for the 1/4 sec. cor. of secs. 18 and 19, at proportionate dist., there is no remaining evidence of the orig. cor.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, in an embedded mound of stone, 3 ft. base, with brass cap mkd.</p>

**Dependent Resurvey of the Subdivisional Lines,
T. 24 N., R. 18 E., Gila and Salt River Meridian, Arizona**

CHAINS	
	T 24 N R 18 E S 18 1/4 ——— S 19 2007
82.99	Deposit a magnet, in a white plastic case, at the base of the stainless steel post. The cor. of secs. 13, 18, 19 and 24, on the W. bdy. of the Tp., hereinbefore described. <hr/> From the cor. of secs. 17, 18, 19 and 20. N. 0°26' E., bet. secs. 17 and 18. Over rolling and broken land, W. slope of Bad Medicine Butte.
40.08	Point for the 1/4 sec. cor. of secs. 17 and 18, at proportionate dist., there is no remaining evidence of the orig. cor. Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.
	T 24 N R 18 E 1/4 S 18 S 17 2007
80.16	Deposit a magnet, in a white plastic case, at the base of the stainless steel post. Raise a mound of stone, 2 ft. base, 1 ft. high, W. of cor. The cor. of secs. 7, 8, 17 and 18, monumented with a basalt stone, 11 x 7 x 6 ins., firmly set, projecting 7 ins. above ground, mkd. 3 grooves on S. side and with a piece of the top missing, with a mound of stone, 3 ft. base and 1 ft. high, W. of cor. At the corner point Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, encircled with a collar of stone, with brass cap mkd.

**Dependent Resurvey of the Subdivisional Lines,
T. 24 N., R. 18 E., Gila and Salt River Meridian, Arizona**

CHAINS	
	T 24 N R 18 E S 7 S 8 S 18 S 17 2007
	Deposit a magnet, in a white plastic case, at the base of the stainless steel post. Bury the orig. stone alongside the stainless steel post. Cor. is located 1.35 chs. E. of a wash, 10 ft. wide, 6 ft. deep, drains N. 30° E. and 2.23 chs. E. of a trail road, bears N. 30° E. and S. 30° W.
	<hr/> Restoring the resurvey executed by Sidney E. Blout, in 1910 <hr/>
	From the cor. of secs. 8, 9, 16 and 17. N. 89°41' W., bet. secs. 8 and 17. Over broken land, N. slope of Bad Medicine Butte.
39.945	Point for the 1/4 sec. cor. of secs. 8 and 17, at proportionate dist., there is no remaining evidence of the orig. cor. Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.
	T 24 N R 18 E S 8 1/4 ——— S 17 2007
	Deposit a magnet, in a white plastic case, at the base of the stainless steel post.
79.885	The cor. of secs. 7, 8, 17 and 18. <hr/> S. 89°57' W., bet. secs. 7 and 18. Over rolling land.
43.22	Point for the 1/4 sec. cor. of secs. 7 and 18, at proportionate dist., there is no remaining evidence of the orig. cor.

**Dependent Resurvey of the Subdivisional Lines,
T. 24 N., R. 18 E., Gila and Salt River Meridian, Arizona**

CHAINS	
	<p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T 24 N R 18 E S 7 1/4 ——— S 18</p> <p style="text-align: center;">2007</p> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p>
51.30	Trail road, bears S. 5° E. and N. 5° W.
83.82	The cor. of secs. 7 12, 13 and 18, on the W. bdy. of the Tp., hereinbefore described.
	<hr/> <p>From the cor. of secs. 7, 8, 17 and 18.</p> <p>N. 0°20' E., bet. secs. 7 and 8.</p> <p>Over rolling land.</p>
3.90	Trail road, bears N. 60° E. and S. 60° W.
33.80	Trail road, bears N. 30° E. and S. 30° W.
40.44	Point for the 1/4 sec. cor. of secs. 7 and 8, at proportionate dist., by the method of irregular boundary adjustment, there is no remaining evidence of the orig. cor.
	<p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T 24 N R 18 E 1/4 S 7 S 8</p> <p style="text-align: center;">2007</p> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p> <hr/> <p>N. 0°16' W., beginning new measurement.</p>
16.35	Barbed wire fence, 5 strand, bears East and West.
24.20	Tees Toh Wash, 175 ft. wide, 10 ft. deep, drains S. 55° W.
40.00	Point for the cor. of secs. 5, 6, 7 and 8, at proportionate dist., there is no remaining evidence of the 1910 cor.

**Dependent Resurvey of the Subdivisional Lines,
T. 24 N., R. 18 E., Gila and Salt River Meridian, Arizona**

CHAINS							
	<p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a steel fence post, 5 ft. long, with brass cap mkd.</p> <div style="text-align: center;"> <table style="border-collapse: collapse; margin: auto;"> <tr> <td style="padding: 0 10px;">T 24 N</td> <td style="padding: 0 10px;">R 18 E</td> </tr> <tr> <td style="border-right: 1px solid black; padding: 0 5px;">S 6</td> <td style="padding: 0 5px;">S 5</td> </tr> <tr> <td style="border-right: 1px solid black; padding: 0 5px;">S 7</td> <td style="padding: 0 5px;">S 8</td> </tr> </table> <p>2007</p> </div> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p> <p>Set a steel fence post nearby.</p> <p>Cor. is located in a sand dune.</p> <hr/> <p>From the cor. of secs. 4, 5, 8 and 9.</p> <p>N. 89°24' W., bet. secs. 5 and 8.</p> <p>Over rolling land.</p>	T 24 N	R 18 E	S 6	S 5	S 7	S 8
T 24 N	R 18 E						
S 6	S 5						
S 7	S 8						
25.01	From this point, the SE corner of a stucco house, 54 x 28 ft., bears North, 23 lks. dist., the long side bears N. 20° E.						
39.90	<p>Point for the 1/4 sec. cor. of secs. 5 and 8, at proportionate dist., there is no remaining evidence of the 1910 cor.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center;"> <table style="border-collapse: collapse; margin: auto;"> <tr> <td style="padding: 0 10px;">T 24 N</td> <td style="padding: 0 10px;">R 18 E</td> </tr> <tr> <td style="padding: 0 10px;">S 5</td> <td style="padding: 0 10px;">S 8</td> </tr> <tr> <td style="padding: 0 10px;">1/4</td> <td style="border-top: 1px solid black; padding: 0 10px;">S 8</td> </tr> </table> <p>2007</p> </div> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p>	T 24 N	R 18 E	S 5	S 8	1/4	S 8
T 24 N	R 18 E						
S 5	S 8						
1/4	S 8						
52.80	Navajo Route 9901, a graded road, 30 ft. wide, bears S. 70° E. and N. 70° W.						
79.80	<p>The cor. of secs 5, 6, 7 and 8.</p> <hr/> <p>S. 89°38' W., bet. secs. 6 and 7.</p> <p>Over rolling land.</p>						

**Dependent Resurvey of the Subdivisional Lines,
T. 24 N., R. 18 E., Gila and Salt River Meridian, Arizona**

CHAINS	
40.02	<p>Point for the 1/4 sec. cor. of secs. 6 and 7, at proportionate dist., there is no remaining evidence of the 1910 cor.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T 24 N R 18 E S 6 1/4 ——— S 7</p> <p style="text-align: center;">2007</p> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p> <p>Set a steel fence post nearby.</p>
42.60	<p>Navajo Route 9901, a graded road, 30 ft. wide, bears N. 70° E. and S. 65° W. in curve to the left.</p>
83.84	<p>The cor. of secs. 1, 6, 7 and 12, on the W. bdy. of the Tp., hereinbefore described.</p> <hr/> <p>N. 0°04' E., bet. secs. 5 and 6.</p> <p>Over rolling land.</p>
3.10	<p>Navajo Route 9901, a graded road, 30 ft. wide, bears N. 85° E. and S. 85° W.</p>
40.06	<p>The 1/4 sec. cor. of secs. 5 and 6, monumented with a sandstone, 14 x 8 x 4 ins., firmly set, projecting 3 ins. above ground, mkd. 1/4 on W. face, with a rebar, 5/8 ins. diam., firmly set, projecting 3 ins. above ground, alongside, with yellow plastic cap mkd. NECA.</p> <p>At the corner point</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T 24 N R 18 E 1/4 S 6 S 5</p> <p style="text-align: center;">2007</p> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p> <p>Bury the 1910 stone alongside, and deposit the rebar, 18 ins. long, inside, the stainless steel post.</p>

**Dependent Resurvey of the Subdivisional Lines,
T. 24 N., R. 18 E., Gila and Salt River Meridian, Arizona**

CHAINS													
	Cor. is located 88 lks. N. of a trail road, bears S. 40° E. and N. 40° W.												

	N. 0°04' W., beginning new measurement.												
11.60	Power line, 2 strand, bears S. 85° E. and N. 85° W.												
14.80	Graded road, 20 ft. wide, bears S. 75° E. and N. 75° W.												
41.96	The closing cor. of secs. 5 and 6, monumented with a sandstone, 18 x 17 x 2 ins., firmly set, projecting 9 ins. above ground, mkd. 5 grooves on E. side and 1 groove on W. side and a hole in the center. Bury the 1910 cor. in place.												
42.27	Point for the closing cor. of secs. 5 and 6, at intersection with the Sixth Standard Parallel North, on the N. bdy. of the Tp.												
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.												
	<table style="margin: auto;"> <tr><td>T 25 N</td><td>R 18 E</td></tr> <tr><td>S 31</td><td></td></tr> <tr><td colspan="2" style="border-top: 1px solid black;"></td></tr> <tr><td>S 6</td><td>S 5</td></tr> <tr><td>T 24 N</td><td>R 18 E</td></tr> <tr><td colspan="2" style="text-align: center;">CC</td></tr> </table>	T 25 N	R 18 E	S 31				S 6	S 5	T 24 N	R 18 E	CC	
T 25 N	R 18 E												
S 31													
S 6	S 5												
T 24 N	R 18 E												
CC													
	2007												
	Deposit a magnet, in a white plastic case, at the base of the stainless steel post.												
	Cor. is located in a barbed wire fence, 5 strand, bears East and West.												
	From this cor. point, the stan. 1/4 sec. cor. of sec. 31, T 25 N., R. 18 E., identical with Angle Point A-29, Hopi-Navajo Partition Line, Segment "A", bears N. 89°43' E., 2.84 chs. dist., hereinbefore described.												
	From this same cor. point, Angle Point A-28D, Hopi-Navajo Partition Line, Segment "A", on the Sixth Standard Parallel North (south boundary), T. 25 N., R. 18 E., bears N. 89°43' W., 25.34 chs. dist., hereinbefore described.												

	Point for the 1/4 sec. cor. of sec. 5 only, T. 24 N., R. 18 E., at midpoint on the N. bdy. of sec. 5.												
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.												

**Dependent Resurvey of the Subdivisional Lines,
T. 24 N., R. 18 E., Gila and Salt River Meridian, Arizona**

CHAINS	
	<p>T 25 N R 18 E</p> <hr style="width: 10%; margin: auto;"/> <p>1/4 S 5</p> <p>T 24 N R 18 E</p> <p>2007</p>
	<p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p> <p>Cor. is located in a barbed wire fence, 5 strand, bears East and West.</p> <p>From this cor. point, the stan. cor. of secs. 31 and 32, T. 25 N., R. 18 E., identical with Angle Point A-30, Hopi-Navajo Partition Line, Segment "A", bears N. 89°44' E., 2.91 chs. dist., hereinbefore described.</p> <p>From this same cor. point, the stan. 1/4 sec. cor. of sec. 31, T. 25 N., R. 18 E., identical with Angle Point A-29, Hopi-Navajo Partition Line, Segment "A", bears S. 89°44' W., 37.15 chs. dist., hereinbefore described.</p> <hr style="width: 50%; margin-left: 0;"/> <p>Point for the 1/4 sec. cor. of sec. 6 only, T. 24 N., R. 18 E., at 40.00 chs. dist. in westing from the closing cor. of secs. 5 and 6.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p>
	<p>T 25 N R 17 E</p> <hr style="width: 10%; margin: auto;"/> <p>1/4 S 6</p> <p>T 24 N R 18 E</p> <p>2007</p>
	<p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p> <p>Cor. is located in a barbed wire fence, 5 strand, bears East and West.</p> <p>From this cor. point, the stan. cor. of Tps. 25 N., Rs. 17 and 18 E., identical with Angle Point A-28, Hopi-Navajo Partition Line, Segment "A", bears S. 89°53' E., 2.79 chs. dist., hereinbefore described.</p>

**Dependent Resurvey of the Subdivisional Lines,
T. 24 N., R. 18 E., Gila and Salt River Meridian, Arizona**

CHAINS	
	<p>From this same cor. point, the stan. 1/4 sec. cor. of sec. 36, T. 25 N., R. 17 E., identical with Angle Point A-27, Hopi-Navajo Partition Line, Segment "A", bears N. 89°53' W., 37.24 chs. dist., hereinbefore described.</p> <hr/> <p style="text-align: center;">Subdivision of Section 1, T. 24 N., R. 18 E., Gila and Salt River Meridian, Arizona</p> <hr/> <p>From the 1/4 sec. cor. of secs. 1 and 12.</p> <p>N. 0°06' E., on the N. and S. center line of sec. 1.</p> <p>Over rolling land.</p> <p>14.40 Lukai Wash, 60 ft. wide, 15 ft. deep, drains N. 80° W.</p> <p>39.21 Point for the center 1/4 sec. cor. of sec. 1, at intersection with the E. and W. center line.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T 24 N R 18 E C 1/4 S 1</p> <p style="text-align: center;">2007</p> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p> <p>Set a steel fence post nearby.</p> <p>62.10 Power line, 2 strand, bears N. 30° E. and S. 30° W.</p> <p>73.10 Navajo Route 9062, a graded road, 25 ft. wide, bears N. 80° E. and S. 80° W.</p> <p>80.30 Wash, 85 ft. wide, 4 ft. deep, drains N. 85° W.</p> <p>81.88 The 1/4 sec. cor. of sec. 1 only, on the N. bdy. of the Tp.</p> <hr/> <p>From the 1/4 sec. cor. of secs. 1 and 6, on the E. bdy. of the Tp.</p> <p>N. 88°24' W., on the E. and W. center line of sec. 1.</p> <p>Over rolling land.</p> <p>39.80 The center 1/4 sec. cor. of sec. 1.</p> <p>79.60 The 1/4 sec. cor. of secs. 1 and 2.</p>

**Subdivision of Certain Sections,
T. 24 N., R. 18 E., Gila and Salt River Meridian, Arizona**

CHAINS	
	<hr/> <p>Subdivision of Section 2, T. 24 N., R. 18 E., Gila and Salt River Meridian, Arizona</p> <hr/>
	<p>From the 1/4 sec. cor. of secs. 2 and 11. N. 0°05' E., on the N. and S. center line of sec. 2. Over rolling land.</p>
40.15	<p>Point for the center 1/4 sec. cor. of sec. 2, at intersection with the E. and W. center line. Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T 24 N R 18 E C 1/4 S 2</p> <p style="text-align: center;">2007</p> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post. Set a steel fence post nearby.</p>
52.50	<p>Navajo Route 9062, a graded road, 25 ft. wide, bears S. 85° E. and N. 85° W.</p>
82.39	<p>The 1/4 sec. cor. of sec. 2 only, on the N. bdy. of the Tp.</p> <hr/> <p>From the 1/4 sec. cor. of secs. 1 and 2. S. 89°37' W., on the E. and W. center line of sec. 2. Over rolling land.</p>
39.97	<p>The center 1/4 sec. cor. of sec. 2.</p>
50.40	<p>Power line, 2 strand, bears N. 30° E. and S. 30° W.</p>
73.70	<p>Navajo Route 9757, a graded road, 20 ft. wide, bears N. 40° E. and S. 40° W.</p>
79.98	<p>The 1/4 sec. cor. of secs. 2 and 3.</p> <hr/> <p style="text-align: center;">Subdivision of Section 3, T. 24 N., R. 18 E., Gila and Salt River Meridian, Arizona</p> <hr/>

**Subdivision of Certain Sections,
T. 24 N., R. 18 E., Gila and Salt River Meridian, Arizona**

CHAINS	
	From the 1/4 sec. cor. of secs. 3 and 10. N. 0°04' E., on the N. and S. center line of sec. 3. Over rolling land.
26.10	Trail road, bears East and West.
40.14	Point for the center 1/4 sec. cor. of sec. 3, at intersection with the E. and W. center line. Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd. T 24 N R 18 E C 1/4 S 3 2007
	Deposit a magnet, in a white plastic case, at the base of the stainless steel post. Set a steel fence post nearby.
83.04	The 1/4 sec. cor. of sec. 3 only, on the N. bdy. of the Tp. <hr/>
	From the 1/4 sec. cor. of secs. 2 and 3. S. 89°43' W., on the E. and W. center line of sec. 3. Over rolling land.
39.29	The center 1/4 sec. cor. of sec. 3.
78.59	The 1/4 sec. cor. of secs. 3 and 4. <hr/>
	Subdivision of Section 4, T. 24 N., R. 18 E., Gila and Salt River Meridian, Arizona
	From the 1/4 sec. cor. of secs. 4 and 9. N. 0°08' E., on the N. and S. center line of sec. 4. Over rolling land.
21.20	Trail road, bears N. 85° E. and S. 85° W.
39.98	Point for the center 1/4 sec. cor. of sec. 4, at intersection with the E. and W. center line.

**Subdivision of Certain Sections,
T. 24 N., R. 18 E., Gila and Salt River Meridian, Arizona**

CHAINS	
	<p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T 24 N R 18 E C 1/4 S 4</p> <p style="text-align: center;">2007</p> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p> <p>Set a steel fence post nearby.</p>
82.92	<p>The 1/4 sec. cor. of sec. 4 only, on the N. bdy. of the Tp.</p> <hr/> <p>From the 1/4 sec. cor. of secs. 3 and 4.</p> <p>N. 89°29' W., on the E. and W. center line of sec. 4.</p> <p>Over rolling land.</p>
40.32	The center 1/4 sec. cor. of sec. 4.
73.70	Power line, 2 strand, bears S. 15° E. and N. 15° W.
74.54	E. right-of-way fence of Arizona State Highway 87, 5 strand barbed wire, parallels highway.
76.10	Arizona State Highway 87, asphalt surface, 28 ft. wide, bears S. 15° E. and N. 15° W.
77.69	W. right-of-way fence of Arizona State Highway 87, 5 strand barbed wire, parallels highway.
80.60	The 1/4 sec. cor. of secs. 4 and 5.
	<p>Subdivision of Section 5, T. 24 N., R. 18 E., Gila and Salt River Meridian, Arizona</p> <hr/>
	<p>From the 1/4 sec. cor. of secs. 5 and 8.</p> <p>N. 0°04' E., on the N. and S. center line of sec. 5.</p> <p>Over rolling land.</p>
3.30	Graded road, 20 ft. wide, bears N. 80° E. and S. 80° W.
40.03	Point for the center 1/4 sec. cor. of sec. 5, at intersection with the E. and W. center line.

**Subdivision of Certain Sections,
T. 24 N., R. 18 E., Gila and Salt River Meridian, Arizona**

CHAINS	
	<p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T 24 N R 18 E C 1/4 S 5</p> <p style="text-align: center;">2007</p> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p> <p>Set a steel fence post nearby.</p>
41.20	Graded road, 18 ft. wide, bears S. 70° E. and N. 70° W.
48.50	Power line, 2 strand, bears S. 85° E. and N. 85° W.
82.92	The 1/4 sec. cor. of sec. 5 only, on the N. bdy. of the Tp.
	<hr/> <p>From the 1/4 sec. cor. of secs. 4 and 5.</p> <p>N. 89°22' W., on the E. and W. center line of sec. 5.</p> <p>Over rolling land.</p>
39.95	The center 1/4 sec. cor. of sec. 5.
79.85	The 1/4 sec. cor. of secs. 5 and 6.
	<hr/> <p style="text-align: center;">Subdivision of Section 6, T. 24 N., R. 18 E., Gila and Salt River Meridian, Arizona</p> <hr/>
	<p>From the 1/4 sec. cor. of secs. 6 and 7.</p> <p>North, on the N. and S. center line of sec. 6.</p> <p>Over rolling land.</p>
.90	Navajo Route 9901, a graded road, 30 ft. wide, bears N. 85° E. and S. 75° W., on a curve.
40.01	Point for the center 1/4 sec. cor. of sec. 6, at intersection with the E. and W. center line.
	<p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T 24 N R 18 E C 1/4 S 6</p> <p style="text-align: center;">2007</p>

**Subdivision of Certain Sections,
T. 24 N., R. 18 E., Gila and Salt River Meridian, Arizona**

CHAINS	
	Deposit a magnet, in a white plastic case, at the base of the stainless steel post.
	Set a steel fence post nearby.
55.50	Power line, 2 strand, bears S. 85° E. and N. 85° W.
69.30	Graded road, 18 ft. wide, bears S. 80° E. and N. 80° W.
82.40	The 1/4 sec. cor. of sec. 6 only, on the N. bdy. of the Tp.
<hr/>	
	From the 1/4 sec. cor. of secs. 5 and 6.
	S. 89°34' W., on the E. and W. center line of sec. 6.
	Over rolling land.
40.05	The center 1/4 sec. cor. of sec. 6.
83.85	The 1/4 sec. cor. of secs. 1 and 6, on the W. bdy. of the Tp., hereinbefore described.
<hr/>	
<p>Subdivision of Section 9, T. 24 N., R. 18 E., Gila and Salt River Meridian, Arizona</p>	
<hr/>	
	From the 1/4 sec. cor. of secs. 9 and 16.
	N. 0°14' E., on the N. and S. center line of sec. 9.
	Over rolling land.
1.53	Arizona State Highway 87, asphalt surface, 28 ft. wide, bears S. 15° E. and N. 15° W.
6.92	E. right-of-way fence of Arizona State Highway 87, barbed wire, 5 strand, parallels highway.
26.70	Navajo Route 60, asphalt surface, 22 ft. wide, bears S. 85° E. and N. 85° W.
31.50	Power line, 4 strand, bears S. 75° E. and N. 75° W.
40.03	Point for the center 1/4 sec. cor. of sec. 9, at intersection with the E. and W. center line.
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.

**Subdivision of Certain Sections,
T. 24 N., R. 18 E., Gila and Salt River Meridian, Arizona**

CHAINS	
	T 24 N R 18 E C 1/4 S 9
	2007
	Deposit a magnet, in a white plastic case, at the base of the stainless steel post.
	Set a steel fence post nearby.
	Cor. is located 60 lks. E. and 55 lks. S. of a trail road, bears N. 50° E. and S. 50° W.
57.57	Barbed wire fence, 5 strand, bears East and West.
77.00	Tees Toh Wash, 60 ft. wide, 5 ft. deep, drains S. 55° W
80.08	The 1/4 sec. cor. of secs. 4 and 9.
	<hr/>
	From the 1/4 sec. cor. of secs. 9 and 10.
	N. 89°29' W., on the E. and W. center line of sec. 9.
	Over rolling land.
40.15	The center 1/4 sec. cor. of sec. 9.
50.22	E. right-of-way fence of Arizona State Highway 87, 5 strand barbed wire, parallels highway.
51.80	Arizona State Highway 87, asphalt surface, 28 ft. wide, bears S. 15° E. and N. 15° W.
53.37	W. right-of-way fence of Arizona State Highway 87, 5 strand barbed wire, parallels highway.
80.28	The 1/4 sec. cor. of secs. 8 and 9.
	<hr/>
	Subdivision of Section 12, T. 24 N., R. 18 E., Gila and Salt River Meridian, Arizona
	<hr/>
	From the 1/4 sec. cor. of secs. 12 and 13.
	N. 0°07' E., on the N. and S. center line of sec. 12.
	Over rolling land.
11.80	Navajo Route 9065, a graded road, 20 ft. wide, bears S. 65° E. and N. 65° W.

**Subdivision of Certain Sections,
T. 24 N., R. 18 E., Gila and Salt River Meridian, Arizona**

CHAINS	
40.23	<p>Point for the center 1/4 sec. cor. of sec. 12, at intersection with the E. and W. center line.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T 24 N R 18 E C 1/4 S 12</p> <p style="text-align: center;">2007</p> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p> <p>Set a steel fence post nearby.</p>
57.70	Barbed wire fence, 5 strand, bears East and West.
80.47	The 1/4 sec. cor. of secs. 1 and 12.
	<hr/> <p>From the 1/4 sec. cor. of secs. 7 and 12, on the E. bdy. of the Tp.</p> <p>N. 89°17' W., on the E. and W. center line of sec. 12.</p> <p>Over rolling land.</p>
39.93	The center 1/4 sec. cor. of sec. 12.
79.86	The 1/4 sec. cor. of secs. 11 and 12.
	<hr/> <p style="text-align: center;">Subdivision of Section 14, T. 24 N., R. 18 E., Gila and Salt River Meridian, Arizona</p> <hr/> <p>From the 1/4 sec. cor. of secs. 14 and 23.</p> <p>N. 0°02' E., on the N. and S. center line of sec. 14.</p> <p>Over rolling land.</p>
3.60	Trail road, bears S. 45° E. and N. 45° W.
40.47	<p>Point for the center 1/4 sec. cor. of sec. 14, at intersection with the E. and W. center line.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p>

**Subdivision of Certain Sections,
T. 24 N., R. 18 E., Gila and Salt River Meridian, Arizona**

CHAINS	
	T 24 N R 18 E C 1/4 S 14 2007
	Deposit a magnet, in a white plastic case, at the base of the stainless steel post.
	Set a steel fence post nearby.
	Cor. is located 1.76 chs. S. of a trail road, bears N. 80° E. and S. 80° W.
80.93	The 1/4 sec. cor. of secs. 11 and 14. <hr/>
	From the 1/4 sec. cor. of secs. 13 and 14. S. 89°13' W., on the E. and W. center line of sec. 14. Over rolling land.
3.90	Power line, 4 strand, bears S. 35° E. and N. 35° W.
5.07	Navajo Route 60, asphalt surface, 21 ft. wide, bears S. 35° E. and N. 35° W.
39.79	The center 1/4 sec. cor. of sec. 14.
79.57	The 1/4 sec. cor. of secs. 14 and 15. <hr/>
	Subdivision of Section 16, T. 24 N., R. 18 E., Gila and Salt River Meridian, Arizona <hr/>
	From the 1/4 sec. cor. of secs. 16 and 21. N. 0°28' E., on the N. and S. center line of sec. 16. Over rolling land.
40.06	Point for the center 1/4 sec. cor. of sec. 16, at intersection with the E. and W. center line. Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.
	T 24 N R 18 E C 1/4 S 16 2007

**Subdivision of Certain Sections,
T. 24 N., R. 18 E., Gila and Salt River Meridian, Arizona**

CHAINS	
	Deposit a magnet, in a white plastic case, at the base of the stainless steel post.
80.11	The 1/4 sec. cor. of secs. 9 and 16. <hr/>
	From the 1/4 sec. cor. of secs. 15 and 16. N. 89°32' W., on the E and W. center of sec. 16. Over rolling land.
25.56	E. right-of-way fence of Arizona State Highway 87, 5 strand barbed wire, parallels highway.
27.15	Arizona State Highway 87, asphalt surface, 28 ft. wide, bears S. 15° E. and N. 15° W.
28.71	W. right-of-way fence of Arizona State Highway 87, 5 strand barbed wire, parallels highway.
39.90	The center 1/4 sec. cor. of sec. 16.
48.80	Wash, 20 ft. wide, 6 ft. deep, drains N. 50° W.
59.60	Navajo Route 9845, a graded road, 18 ft. wide, bears N. 5° E. and S. 5° W.
79.79	The 1/4 sec. cor. of secs. 16 and 17. <hr/>
	Subdivision of Section 21, T. 24 N., R. 18 E., Gila and Salt River Meridian, Arizona <hr/>
	From the 1/4 sec. cor. of secs. 21 and 28. N. 2°10' E., on the N. and S. center line of sec. 21. Over rolling land.
3.60	Trail road, bears S. 70° E. and N. 70° W.
40.09	Point for the center 1/4 sec. cor. of sec. 21, at intersection with the E. and W. center line. Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.
	T 24 N R 18 E C 1/4 S 21 2007

**Subdivision of Certain Sections,
T. 24 N., R. 18 E., Gila and Salt River Meridian, Arizona**

CHAINS	
	<p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p> <p>Set a steel fence post nearby.</p> <p>Cor. is located 1.42 chs. E. of a trail road, bears N. 10° E. and S. 10° W.</p>
60.90	Power line, 2 strand, bears N. 80° E. and S. 80° W.
80.17	The 1/4 sec. cor. of secs. 16 and 21.
	<hr/> <p>From the 1/4 sec. cor. of secs. 15 and 16.</p> <p>N. 89°37' W., on the E. and W. center line of sec. 21.</p> <p>Over rolling land.</p>
1.61	E. right-of-way fence of Arizona State Highway 87, 5 strand barbed wire, parallels highway.
3.11	Arizona State Highway 87, asphalt surface, 25 ft. wide, bears S. 10° E. and N. 10° W.
4.62	W. right-of-way fence of Arizona State Highway 87, 5 strand barbed wire, parallels highway.
13.70	Wash, 40 ft. wide, 5 ft. deep, drains N. 25° W.
17.50	Trail road, bears S. 45° E. and N. 45° W.
40.26	The center 1/4 sec. cor. of sec. 21.
80.53	The 1/4 sec. cor. of secs. 20 and 21.
	<hr/> <p style="text-align: center;">Subdivision of Section 24, T. 24 N., R. 18 E., Gila and Salt River Meridian, Arizona</p> <hr/> <p>From the 1/4 sec. cor. of secs. 24 and 25.</p> <p>N. 0°05' E., on the N. and S. center line of sec. 24.</p> <p>Over broken land.</p>
40.02	<p>Point for the center 1/4 sec. cor. of sec. 24, at intersection with the E. and W. center line.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p>

**Subdivision of Certain Sections,
T. 24 N., R. 18 E., Gila and Salt River Meridian, Arizona**

CHAINS	
	T 24 N R 18 E C 1/4 S 24 2007
	Deposit a magnet, in a white plastic case, at the base of the stainless steel post. Set a steel fence post nearby. From this cor. point, a rebar, 5/8 in. diam., firmly set in a iron pipe, 3 ins. diam., set flush with the surface of ground, bears S. 0°41' E., 80 lks. dist., with a steel fence post nearby.
59.98	Point for the C-N 1/16 sec. cor. of sec. 24. Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.
	T 24 N R 18 E C N 1/16 S 24 C
	2007
	Deposit a magnet, in a white plastic case, at the base of the stainless steel post. Set a steel fence post nearby.
63.90	Power line, 2 strand, bears N. 85° E. and S. 85° W.
79.94	The 1/4 sec. cor. of secs. 13 and 24.
	<hr/> From the 1/4 sec. cor. of secs. 19 and 24, on the E. bdy. of the Tp. N. 89°07' W., on the E. and W. center line of sec. 24. Over broken land.
20.11	Point for the C-E 1/16 sec. cor. of sec. 24. Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ns. in the ground, with brass cap mkd.

**Subdivision of Certain Sections,
T. 24 N., R. 18 E., Gila and Salt River Meridian, Arizona**

CHAINS	
	T 24 N R 18 E E 1/16 C———C S 24 2007
	Deposit a magnet, in a white plastic case, at the base of the stainless steel post. Set a steel fence post nearby.
40.22	The center 1/4 sec. cor. of sec. 24.
47.10	Power line, 4 strand, bears S. 15° E. and N. 15° W.
48.00	Navajo Route 60, asphalt surface, 21 ft. wide, bears S. 15° E. and N. 15° W.
80.29	The 1/4 sec. cor. of secs. 23 and 24.
	<hr/> NE 1/4 Section 24 <hr/>
	From the C-E 1/16 sec. cor. of sec. 24. N. 0°05' W., on the N. and S. center line of the NE 1/4 of sec. 24. Over broken land.
19.93	Point for the NE 1/16 sec. cor. of sec. 24, at intersection with the E. and W. center line of the NE 1/4, sec. 24. Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.
	T 24 N R 18 E NE 1/16 S 24 2007
	Deposit a magnet, in a white plastic case, at the base of the stainless steel post. Set a steel fence post nearby.
25.30	Power line, 2 strand, bears N. 85° E. and S. 85° W.
27.60	Trail road, bears S. 80° E. and N. 80° W.

**Subdivision of Certain Sections,
T. 24 N., R. 18 E., Gila and Salt River Meridian, Arizona**

CHAINS	
39.86	<p>The E 1/16 sec. cor. of secs. 13 and 24.</p> <hr/> <p>From the N 1/16 sec. cor. of secs. 19 and 24, on the E. bdy. of the Tp.</p> <p>N. 89°00' W., on the E. and W. center line of the NE 1/4 of sec. 24.</p> <p>Over broken land.</p>
20.055	The NE 1/16 sec. cor. of sec. 24.
40.11	The C-N 1/16 sec. cor. of sec. 24.
<hr/> <p>Subdivision of Section 27, T. 24 N., R. 18 E., Gila and Salt River Meridian, Arizona</p> <hr/>	
	<p>From the 1/4 sec. cor. of secs. 27 and 34.</p> <p>N. 1°07' E., on the N. and S. center line of sec. 27.</p> <p>Over rolling land.</p>
16.40	Navajo Route 602, asphalt surface, 22 ft. wide, bears N. 85° E. and S. 85° W.
19.60	Power line, 2 strand, bears East and West.
40.18	<p>Point for the center 1/4 sec. cor. of sec. 27, at intersection with the E. and W. center line.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T 24 N R 18 E C 1/4 S 27</p> <p style="text-align: center;">2007</p> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p> <p>Set a steel fence post nearby.</p>
44.20	Trail road, bears S. 60° E. and N. 60° W.
46.10	S. edge of an abandoned sand and gravel pit, approximately 300 ft. by 200 ft.
53.10	Wash, 100 ft. wide, 6 ft. deep, drains N. 45° W.

**Subdivision of Certain Sections,
T. 24 N., R. 18 E., Gila and Salt River Meridian, Arizona**

CHAINS	
65.00	Trail road, bears S. 65° E. and N. 65° W.
80.35	The 1/4 sec. cor. of secs. 22 and 27.

	From the 1/4 sec. cor. of secs. 26 and 27.
	S. 89°55' W., on the E. and W. center line of sec. 27.
	Over rolling land.
15.50	Graded road, 15 ft. wide, bears N. 45° E. and S. 45° W.
17.20	Power line, 2 strand, bears North and South.
26.10	Wash, 60 ft. wide, 8 ft. deep, drains N. 40° W.
33.90	Trail road, bears S. 60° E. and N. 60° W.
40.79	The center 1/4 sec. cor. of sec. 27.
43.90	Underground water line, bears North and South.
81.58	The 1/4 sec. cor. of secs. 27 and 28.

	Subdivision of Section 28, T. 24 N., R. 18 E., Gila and Salt River Meridian, Arizona

	From the 1/4 sec. cor. of secs. 28 and 33.
	N. 1°03' E., on the N. and S. center line of sec. 28.
	Over rolling land.
6.90	Underground water line, bears N. 85° E. and S. 85° W.
7.80	Navajo Route 9844, a graded road, 25 ft. wide, bears N. 85° E. and S. 85° W.
24.40	Trail road, bears S. 75° E. and N. 75° W.
40.06	Point for the center 1/4 sec. cor. of sec. 28, at intersection with the E. and W. center line.
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.
	T 24 N R 18 E C 1/4 S 28
	2007



**Subdivision of Certain Sections,
T. 24 N., R. 18 E., Gila and Salt River Meridian, Arizona**

CHAINS	
	Deposit a magnet, in a white plastic case, at the base of the stainless steel post.
	Set a steel fence post nearby.
74.30	Trail road, bears N. 80° E. and S. 80° W.
80.12	The 1/4 sec. cor. of secs. 28 and 29.
<hr/>	
	From the 1/4 sec. cor. of secs. 27 and 28.
	N. 89°42' W., on the E. and W. center line of sec. 28.
	Over rolling land.
0.93	E. right-of-way fence of Arizona State Highway 87, 5 strand barbed wire, parallels highway.
2.48	Arizona State Highway 87, asphalt surface, 25 ft. wide, bears N. 5° E. and S. 5° W.
3.98	W. right-of-way fence of Arizona State Highway 87, 5 strand barbed wire, parallels highway.
40.64	The center 1/4 sec. cor. of sec. 28.
81.28	The 1/4 sec. cor. of secs. 28 and 29.
<hr/>	
<p>Subdivision of Section 33, T. 24 N., R. 18 E., Gila and Salt River Meridian, Arizona</p>	
<hr/>	
	From the 1/4 sec. cor. of secs. 4 and 33, on the S. bdy. of the Tp., monumented with a stainless steel post, 2 1/2 ins. diam., firmly set, projecting 6 ins. above ground, with brass cap mkd. T24N R18E 1/4 S33 S4 T23N 2007, with a steel fence post nearby.
	N. 1°04' W., on the N. and S. center line of sec. 33.
	Over rolling land.
19.90	Trail road, bears S. 35° E. and N. 35° W.
40.06	Point for the center 1/4 sec. cor. of sec. 33, at intersection with the E. and W. centerline.
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.


**Subdivision of Certain Sections,
T. 24 N., R. 18 E., Gila and Salt River Meridian, Arizona**

CHAINS	
	T 24 N R 18 E C 1/4 S 33
	2007
	Deposit a magnet, in a white plastic case, at the base of the stainless steel post.
80.12	The 1/4 sec. cor. of secs. 28 and 33. <hr/>
	From the 1/4 sec. cor. of secs. 33 and 34. N. 89°48' W., on the E. and W. center line of sec. 33. Over rolling land.
7.70	E. right-of-way fence of Arizona State Highway 87, 5 strand barbed wire, parallels highway.
9.24	Arizona State Highway 87, asphalt surfaced, 25 ft. wide, bears N. 5° E. and S. 5° W.
10.74	W. right-of-way fence of Arizona State Highway 87, 5 strand barbed wire, parallels highway.
40.71	The center 1/4 sec. cor. of sec. 33.
57.30	Trail road, bears S. 35° E. and N. 35° W.
81.42	The 1/4 sec. cor. of secs. 32 and 33. <hr/>
	Metes-and-Bounds Surveys, T. 24 N., R. 18 E., Gila and Salt River Meridian, Arizona <hr/>
	Note: The following metes-and-bounds surveys in sections 5 and 8 pertain to the Bureau of Indian Affairs Seba Dalkai School Property, Parcels A, B and C, as shown on a property plot plan, dated June 24, 1986, Branch of Facilities Management, surveyed by Tommy R. Conley, Arizona Registered Land Surveyor No. 7687.
	PARCEL A <hr/>
	From Angle Point 1, sec. 8, identical with Property Corner No. 1, Parcel A, Seba Dalkai School Property, monumented with a rebar, 5/8 in. diam., set 10 ins. below the surface of the ground. Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.



**Metes-and-Bounds Surveys,
T. 24 N., R. 18 E., Gila and Salt River Meridian, Arizona**

CHAINS	
	<p>T 24 N R 18 E AP 1</p>  <p>S8</p>
	2007
	<p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p> <p>Deposit the rebar, 18 ins. long, inside the stainless steel post.</p> <p>Set a steel fence post nearby.</p> <p>From this cor. point, the 156 Mile Post of the S. bdy. of 1882 Executive Order Hopi Indian Reservation, bears S. 82°19' E., 49 lks. dist., hereinbefore described.</p> <p>From this same cor. point, the 1/4 sec. cor. of secs. 8 and 9, bears S. 49°37' E., 26.62 chs. dist., hereinbefore described.</p> <p>From this same cor. point, the cor. of chain link fences, which surrounds the school property, 6 ft. high, bears S. 21° W. and N. 76° W., bears S 83°57' W., 14 lks. dist.</p> <p>S. 20°26' W., on line 1-2.</p> <p>Over rolling land.</p>
16.51	<p>Point for Angle Point 2, sec. 8, identical with Property Corner No. 2, Parcel A, Seba Dalkai School Property, determined at the intersection of record distances from Property Corners No. 1 and No. 3.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p>
	<p>T 24 N R 18 E</p>  <p>S 8 AP 2</p>
	2007
	<p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p>



**Metes-and-Bounds Surveys,
T. 24 N., R. 18 E., Gila and Salt River Meridian, Arizona**

CHAINS	
	<p>From this cor. point, the cor. of chain link fences, which surrounds the school property, 6 ft. high, bears S. 21° W. and N. 70° W., bears N 3°10' E., 57 lks. dist.</p> <p>From this same cor. point, a brass disk, 3 ins. diam., set in a concrete collar, 6 ins. diam., firmly set, projecting 19 ins. above ground, mkd. BIA 19, bears N. 87°20' E., 7.65 chs. dist.</p> <hr/> <p>N. 68°30' W., on line 2-3.</p>
9.05	<p>Angle Point 3, sec. 8, identical with Property Corner No. 3, Parcel A, Seba Dalkai School Property, monumented with a rebar, 5/8 in. diam., set 8 ins. below the surface of the ground.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T 24 N R 18 E</p> <div style="text-align: center;">  </div> <p style="text-align: center;">2007</p> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p> <p>Deposit the rebar, 18 ins. long, inside the stainless steel post.</p> <p>Set a steel fence post nearby.</p> <p>From this cor. point, the cor. of chain link fences, which surrounds the school property, 6 ft. high, bears S. 70° E. and N. 57° W., bears N 20°09' E., 37 lks. dist.</p> <hr/> <p>N. 55°41' W., on line 3-4.</p>
14.265	<p>Angle Point 4, sec. 8, identical with Property Corner No. 4, Parcel A, Seba Dalkai School Property, determined at the intersection of record distances from Property Corners No. 3 and No. 5.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p>


**Metes-and-Bounds Surveys,
T. 24 N., R. 18 E., Gila and Salt River Meridian, Arizona**

CHAINS	
	<p>T 24 N R 18 E</p>  <p>AP 4</p> <p style="margin-left: 100px;">S 8</p> <p>2007</p>
	<p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p> <p>Set a steel fence post nearby.</p> <hr/> <p>N. 7°16' E., on line 4-5.</p>
.63	Chain link fence, 6 ft. high, bears S. 46° E. and N. 46° W.
6.39	<p>Angle Point 5, sec. 8, identical with Property Corner No. 5, Parcel A, Seba Dalkai School Property, monumented with a rebar, 5/8 in. diam., firmly set, projecting 5 ins. above ground.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p>
	<p>T 24 N R 18 E</p>  <p>AP 5</p> <p style="margin-left: 100px;">S 8</p> <p>2007</p>
	<p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p> <p>Deposit the rebar, 18 ins. long, inside the stainless steel post.</p> <p>Set a steel fence post nearby.</p> <p>Cor. is located in the chain link fence, which surrounds the school property, 6 ft. high, bears N. 78° E. and S. 78° W.</p>


**Metes-and-Bounds Surveys,
T. 24 N., R. 18 E., Gila and Salt River Meridian, Arizona**

CHAINS	
	<p>From this cor. point, the cor. of chain link fences, which surrounds the school property, 6 ft. high, bears N. 78° E. and S. 6° W., bears S 77°46' W., 20 lks. dist.</p> <hr/> <p>N. 77°05' E., on line 5-6.</p>
7.095	<p>Point for Angle Point 6, sec. 8, identical with Property Corner No. 6, Parcel A, Seba Dalkai School Property, at proportionate dist., by the method of Grant boundary adjustment, there is no remaining evidence of the private survey cor.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center;"> <p>T 24 N R 18 E S 8 AP 6</p>  <p>2007</p> </div> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p> <p>Set a steel fence post nearby.</p> <p>From this cor. point, the cor. of chain link fences, which surrounds the school property, 6 ft. high, bears S. 89° E. and N. 78° W., bears N 86°02' E., 1.30 chs. dist.</p> <p>From this same cor. point, a water valve on a pipe, 4 ins. diam., projecting 24 ins. above the floor, inside a octagonal shaped concrete shed, 10 ft. diam., mkd. 407, bears N. 72°18' W., 2.91 chs. dist.</p> <hr/> <p>N. 86°15' E., on line 6-7.</p>
5.39	<p>Point for Angle Point 7, sec. 8, identical with Property Corner No. 7, Parcel A, Seba Dalkai School Property, at proportionate dist., by the method of Grant boundary adjustment, with a rebar, 5/8 in. diam., 18 ins. long, laying loose nearby.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center;"> <p>T 24 N R 18 E AP 7</p>  <p>S 8</p> <p>2007</p> </div>

**Metes-and-Bounds Surveys,
T. 24 N., R. 18 E., Gila and Salt River Meridian, Arizona**

CHAINS	
	<p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p> <p>Deposit the rebar, 18 ins. long, inside the stainless steel post.</p> <p>Set a steel fence post nearby.</p> <p>From this cor. point, the cor. of chain link fences, which surrounds the school property, 6 ft. high, bears S. 58° E. and N. 89° W., bears S 72°17' W., 60 lks. dist.</p> <hr/> <p>S. 44°02' E., on line 7-8.</p>
1.67	Chain link fence, 6 ft. high, bears S. 75° E. and N. 75° W.
5.78	<p>Point for Angle Point 8, sec. 8, identical with Property Corner No. 8, Parcel A, Seba Dalkai School Property, at proportionate dist., by the method of Grant boundary adjustment, there is no remaining evidence of the private survey cor.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center;"> <p>T 24 N R 18 E</p> <p>S 8</p> <p>AP 8</p>  </div> <p>2007</p>
	<p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p> <p>From this cor. point, a water valve on a pipe, 2 ins. diam., projecting 24 ins. above the floor, inside a 9 ft. square concrete structure, mkd. 424, surrounded by a chain link fence, 6 ft. high, 20 ft. square, bears N. 8°50' W., 4.37 chs. dist.</p> <hr/> <p>S. 89°58' E., on line 8-1.</p>
8.64	Chain link fence, 6 ft. high, bears S. 75° E. and N. 75° W.


**Metes-and-Bounds Surveys,
T. 24 N., R. 18 E., Gila and Salt River Meridian, Arizona**

CHAINS 8.835	<p>Angle Point 1, sec. 8, identical with Property Corner No. 1, Parcel A, Seba Dalkai School Property.</p> <hr/> <p style="text-align: center;">PARCEL B</p> <hr/> <p>From Angle Point 9, sec. 8, identical with the NE cor., Parcel B, Seba Dalkai School Property, monumented with a rebar, 1/4 in. diam., set flush with the surface of the ground.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center;"> <p>T 24 N R 18 E S 8</p>  <p>2007</p> </div> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p> <p>Deposit the rebar, 18 ins. long, inside the stainless steel post.</p> <p>Set a steel fence post nearby.</p> <p>From this cor. point, the cor. of chain link fences, which surrounds a sewer lagoon, 6 ft. high, bears S. 11° W. and N. 75° W., bears S 67°07' W., 65 lks. dist.</p> <p>From this cor. point, Angle Point 4, sec. 8, identical with Property Corner No. 4, Parcel A, Seba Dalkai School Property, bears S 71°47' E., 21.32 chs. dist., hereinbefore described.</p> <p>From this same cor. point, the cor. of secs. 5, 6, 7 and 8, bears N 32°18' W., 24.92 chs. dist., hereinbefore described.</p> <p>S. 14°53' W., on line 9-10.</p> <p>Over rolling land.</p>
2.68	Barbed wire fence, 5 strand, bears East and West.
3.15	Angle Point 10, sec. 8, identical with the SE cor., Parcel B, Seba Dalkai School Property, monumented with a rebar, 1/4 in. diam., set flush with the surface of the ground.

**Metes-and-Bounds Surveys,
T. 24 N., R. 18 E., Gila and Salt River Meridian, Arizona**

CHAINS

Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.



Deposit a magnet, in a white plastic case, at the base of the stainless steel post.

Deposit the rebar, 18 ins. long, inside the stainless steel post.

Set a steel fence post nearby.


From this cor. point, the cor. of chain link fences, which surrounds a sewer lagoon, 6 ft. high, bears N. 11° E. and N. 76° W., bears N 21°24' W., 60 lks. dist.

N. 75°06' W., on line 10-11.

1.74 Barbed wire fence, 5 strand, bears East and West.

5.465 Angle Point 11, sec. 8, identical with the SW cor., Parcel B, Seba Dalkai School Property, monumented with a rebar, 1/4 in. diam., firmly set, projecting 2 ins. above ground.

Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.




Deposit a magnet, in a white plastic case, at the base of the stainless steel post.



Deposit the rebar, 18 ins. long, inside the stainless steel post.

Set a steel fence post nearby.



**Metes-and-Bounds Surveys,
T. 24 N., R. 18 E., Gila and Salt River Meridian, Arizona**

CHAINS	
	<p>From this cor. point, the cor. of chain link fences, which surrounds a sewer lagoon, 6 ft. high, bears N. 17° E. and S. 76° E., bears N 65°54' E., 62 lks. dist.</p> <hr/> <p>N. 14°55' E., on line 11-12.</p>
3.15	<p>Angle Point 12, sec. 8, identical with the NW cor., Parcel B, Seba Dalkai School Property, monumented with a 60D nail, set flush with the surface of the ground.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., flush with the surface of the ground, with brass cap mkd.</p> <div style="text-align: center;"> <p>T 24 N R 18 E S 8</p>  <p>2007</p> </div> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p> <p>Deposit the 60D nail inside the stainless steel post.</p> <p>Set a steel fence post nearby.</p> <p>From this cor. point, the cor. of chain link fences, which surrounds a sewer lagoon, 6 ft. high, bears S. 75° E. and S. 17° W., bears S 38°08' E., 71 lks. dist.</p> <hr/> <p>S. 74°58' E., on line 12-9.</p>
5.465	<p>Angle Point 9, sec. 8, identical with the NE cor., Parcel B, Seba Dalkai School Property, hereinbefore described.</p> <hr/> <p style="text-align: center;">PARCEL C</p> <hr/> <p>From the point for Angle Point 13, sec. 5, identical to the NE cor., Parcel C, Seba Dalkai School Property, determined at the intersection of record distances from the SE cor., Parcel C, and Angle Point 5, identical with Property Corner No. 5, Parcel A, Seba Dalkai School Property.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p>

**Metes-and-Bounds Surveys,
T. 24 N., R. 18 E., Gila and Salt River Meridian, Arizona**

CHAINS	
	<p>T 24 N R 18 E S 5</p>  <p>2007</p>
	<p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p> <p>Set a steel fence post nearby.</p> <p>From this cor. point, Angle Point 5, sec. 8, identical with Property Corner No. 5, Parcel A, Seba Dalkai School Property, bears S 37°49' E., 27.345 chs. dist., hereinbefore described.</p> <p>From this same cor. point, the cor. of secs. 5, 6, 7 and 8, bears S. 89°17' W., 17.61 chs. dist., hereinbefore described.</p> <p>S. 32°52' W., on line 13-14.</p> <p>Over rolling land.</p>
.48	<p>Intersect the line bet. secs. 5 and 8. Point not monumented.</p> <p>From this point, the cor. of secs. 4, 5, 8 and 9, bears S. 89°25' E., 62.45 chs. dist., hereinbefore described.</p>
4.47	<p>Angle Point 14, sec. 8, identical with the SE cor., Parcel C, Seba Dalkai School Property, monumented with a rebar, 5/8 in. diam., set 30 ins. below the surface of the ground.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., over a steel fence post, 5 ft. long, 24 ins. in the ground, with brass cap mkd.</p>
	<p>T 24 N R 18 E S 8</p>  <p>2007</p>
	<p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p> <p>Bury the rebar, 18 ins. long, alongside the stainless steel post.</p>

**Metes-and-Bounds Surveys,
T. 24 N., R. 18 E., Gila and Salt River Meridian, Arizona**

CHAINS	
	<p>Set a steel fence post nearby.</p> <hr/> <p>N. 57°07' W., on line 14-15.</p>
4.47	<p>Angle Point 15, sec. 8, identical with the SW cor., Parcel C, Seba Dalkai School Property, monumented with a rebar, 5/8 in. diam., set 10 ins. below the surface of the ground.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ns. in the ground, with brass cap mkd.</p> <div style="text-align: center;"> <p>T 24 N R 18 E</p> <p>S 8</p>  <p>AP 15</p> <p>2007</p> </div> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p> <p>Bury the rebar, 18 ins. long, alongside the stainless steel post.</p> <p>Set a steel fence post nearby.</p> <hr/> <p>N. 32°53' E., on line 15-16.</p>
1.17	<p>Intersect the line bet. secs. 5 and 8. Point not monumented.</p> <p>From this point, the cor. of secs. 5, 6, 7 and 8, bears N. 89°24' W., 12.06 chs. dist., hereinbefore described.</p>
4.47	<p>Point for Angle Point 16, sec. 5, identical with the NW cor., Parcel C, Seba Dalkai School Property, determined at the intersection of record distances from Angle Point 13, identical to the NE cor., and Angle Point 15, identical with the SE cor., Parcel C, Seba Dalkai School Property.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center;"> <p>T 24 N R 18 E</p> <p>S 5</p> <p>AP 16</p>  <p>2007</p> </div>

Metes-and-Bounds Surveys,
T. 24 N., R. 18 E., Gila and Salt River Meridian, Arizona

CHAINS	<p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p> <p>Set a steel fence post nearby.</p> <hr/> <p>S. 57°08' E., on line 16-13.</p> <p>4.47 Angle Point 13, sec. 5, identical to the NE cor., Parcel C, Seba Dalkai School Property.</p> <hr/>
--------	---

**Tps. 25 N., Rs. 17 and 18 E. and T. 24 N., R. 18 E.,
Gila and Salt River Meridian, Arizona**

CHAINS

GENERAL DESCRIPTION

The area surveyed is within the Navajo Indian Reservation and encompasses the communities of Seba Dalkai and Teesto, Arizona. The Hopi-Navajo Indian Reservation Boundary is partially adjacent to and is the north boundary of the township. The area is mostly rolling, desert land. Several rocky buttes are in the area where, along the slopes, the land is broken and rugged. The drainage is southwesterly in the southern portion and westerly, by Tees Toh Wash, in the northern portion.

The elevation varies from 5400 in the rolling desert to nearly 6700 feet at the top of the buttes. The soil is sandy and sandy clay. There is a medium stand of juniper along the slope of the buttes. Undergrowth principally consists of sagebrush, cacti, greasewood, yucca and native grasses.

The principal access to the township is provided by Arizona State Highway 87, which enters the township in section 33, extends northerly and exits in section 5. There are Navajo Routes 60 and 602, asphalt surfaced highways, and several major graded roads and numerous trail roads through the township. There are numerous residential homes throughout the township. Seba Dalkai School is located in section 8. Much of this area is used for grazing livestock. There is no mining activity in this township.

The mean magnetic declination of $11 \frac{1}{4}^{\circ}$ E. was derived from the computer program GEOMAGIX, utilizing the World Magnetic Model for Epoch 2005 for the dates of survey.

CERTIFICATE OF SURVEY

I, Jones Curtiss, Cadastral Surveyor, HEREBY CERTIFY upon honor, that in pursuance of special instructions bearing date of the 4th day of June, 2007, I have dependently resurveyed a portion of the Sixth Standard Parallel North (south boundary), Township 25 North, Range 17 East, the Sixth Standard Parallel North (south boundary), Township 25 North, Range 18 East, which are identical with portions of the Hopi-Navajo Partition Line, Segment "A" and dependently resurveyed portions of the Hopi-Navajo Partition Line, Segment "A", the east and west boundaries and the subdivisional lines and the subdivision of certain sections and metes-and-bounds surveys, Township 24 North, Range 18 East, of the Gila and Salt River Meridian, in the State of Arizona, which are represented in the foregoing field notes as having been executed by me and under my direction. Said survey has been made in strict conformity with said special instructions, the Manual of Instructions for the Survey of the Public Lands of the United States, 1973, and in specific manner described in the foregoing field notes.

August 25, 2008
(Date)

Jones Curtiss
(Cadastral Surveyor)

CERTIFICATE OF APPROVAL

BUREAU OF LAND MANAGEMENT
Phoenix, Arizona

The foregoing field notes of the dependent resurvey of a portion of the Sixth Standard Parallel North (south boundary), Township 25 North, Range 17 East, the Sixth Standard Parallel North (south boundary), Township 25 North, Range 18 East, which are identical with portions of the Hopi-Navajo Partition Line, Segment "A" and the dependent resurvey of portions of the Hopi-Navajo Partition Line, Segment "A", the east and west boundaries and the subdivisional lines and the subdivision of certain sections and metes-and-bounds surveys, Township 24 North, Range 18 East, Gila and Salt River Meridian, in the State of Arizona, executed by Jones Curtiss, Cadastral Surveyor, having been critically examined and found correct, are hereby approved.

Sept 2, 2008
(Date)

Stephen H. Hansen
(Chief Cadastral Surveyor of Arizona)

 CERTIFICATE OF TRANSCRIPT

I CERTIFY That the foregoing transcript of the field notes of the above described surveys in Tps. 25 N., Rs. 17 and 18 E. and T. 24 N., R. 18 E., Gila and Salt River Meridian, Arizona, is a true copy of the original field notes.

(Date)

(Chief Cadastral Surveyor of Arizona)
