

ORIGINAL

**UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT**

FIELD NOTES

OF THE

SURVEY OF THE SIXTH GUIDE MERIDIAN EAST (EAST BOUNDARY),

TOWNSHIP 23 NORTH, RANGE 24 EAST,

THE

DEPENDENT RESURVEY OF THE NORTH BOUNDARY,

TOWNSHIP 22 NORTH, RANGE 25 EAST

AND

THE SURVEY OF THE NORTH BOUNDARY,

A SECTIONAL CORRECTION LINE

AND THE SUBDIVISIONAL LINES,

TOWNSHIP 23 NORTH, RANGE 25 EAST,

OF THE GILA AND SALT RIVER MERIDIAN,

IN THE STATE OF ARIZONA

EXECUTED BY

Alvina A. Begaye, Cadastral Surveyor

Under Special Instructions dated and approved January 31, 2008, which provided for the surveys included under Group No. 1039 and assignment instructions dated January 31, 2008.

Survey commenced February 1, 2008

Survey completed April 10, 2008

INDEX DIAGRAM

TOWNSHIP 23 NORTH RANGE 25 EAST
 GILA AND SALT RIVER MERIDIAN, ARIZONA

8	18 6	17 70 5	16 55 4	16 47 3	15 39 2	14 32 1
7	68 7	67 66 8	54 53 9	46 46 10	39 38 11	32 31 12
6	65 18	64 63 17	53 52 16	45 44 15	37 36 14	30 29 13
5	62 19	61 60 20	51 51 21	44 43 22	36 35 23	29 28 24
4	59 30	58 57 29	50 49 28	42 42 27	34 34 26	27 26 25
4	24 31 13	23 55 32 12	23 48 33 12	22 40 34 11	21 33 35 10	20 26 36 9

Tps. 22 and 23 N., Rs. 24 and 25 E., Gila and Salt River Meridian, Arizona

CHAINS

The following field notes describe the survey of the Sixth Guide Meridian East (east boundary), Township 23 North, Range 24 East, the dependent resurvey of the north boundary, Township 22 North, Range 25 East and the survey of the north boundary, a sectional correctional line and the subdivisional lines, Township 23 North, Range 25 East, Gila and Salt River Meridian, Arizona.

The history of surveys pertaining to this survey is as follows:

Frank Follman surveyed the north boundary of Township 22 North, Range 25 East in 1882. Jones Curtiss dependently resurveyed the west boundary of Township 22 North, Range 27 East in 2002-03. Jones Curtiss and Leonard R. Sandoval dependently resurveyed the south and west boundaries of Township 23 North, Range 26 East, in 2003. Leonard R. Sandoval reestablished the corner of Townships 22 and 23 North, Ranges 23 and 24 East and surveyed the Sixth Guide Meridian East (east boundary), Township 24 North, Range 24 East in 2004-05.

The survey was executed in accordance with the specifications as set forth in the Manual of Instructions for the Survey of the Public Lands of the United States, 1973 and the Special Instructions dated January 31, 2008, for Group 1039, Arizona.

The true meridian directions and length of all lines were determined by real time kinematic global positioning system observations using Trimble Navigation 5700 model receivers.

Preliminary to the resurvey, the lines of the prior surveys were retraced and search was made for all corners and other calls of record. Identified corners were remonumented in their original positions. Lost corners were reestablished and remonumented at proportionate positions based on the official record. The retracement data were thoroughly verified and only the true line field notes are given herein.

Geodetic control was derived from Global Positioning Systems (GPS) static observations post processed by National Geodetic Survey, Online Positioning User Service (OPUS), utilizing Continuously Operating Reference Stations (CORS) FLAGSTAFF 1 CORS ARP, PIETOWN CORS ARP and AZTEC CORS ARP. The NAD 83 (CORS96) (EPOCH:2002) geographic position of the southeast corner of township is as follows:

Latitude: 35°20'43.22" N. Longitude: 109°37'54.84" W.

The mean magnetic declination is 10 3/4° E.

**Survey of the Sixth Guide Meridian East (East Boundary),
T. 23 N., R. 24 E., Gila and Salt River Meridian, Arizona**

CHAINS													
	<p>Beginning at the cor. of Tps. 22 and 23 N., Rs. 24 and 25 E., monumented with a stainless steel post, 2 1/2 ins. diam., firmly set, projecting 4 ins. above ground, with brass cap mkd. T23N R24E R25E S36 S31 S1 S6 T22N 2004.</p>												
	<p>Add the marks 2008 to the brass cap.</p>												
	<p>North, on the E. bdy. of sec. 36.</p>												
	<p>Over nearly level land.</p>												
40.00	<p>Point for the 1/4 sec. cor. of sec. 36 only.</p>												
	<p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p>												
	<table style="margin-left: auto; margin-right: auto;"> <tr> <td style="text-align: center;">T 23 N</td> <td style="border-left: 1px solid black; padding-left: 5px;"></td> <td style="text-align: center;">R 25 E</td> </tr> <tr> <td style="text-align: center;">R 24 E</td> <td style="border-left: 1px solid black; padding-left: 5px;"></td> <td></td> </tr> <tr> <td style="text-align: center;">1/4 S 36</td> <td style="border-left: 1px solid black; padding-left: 5px;"></td> <td></td> </tr> </table>	T 23 N		R 25 E	R 24 E			1/4 S 36					
T 23 N		R 25 E											
R 24 E													
1/4 S 36													
	<p style="text-align: center;">2008</p>												
	<p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p>												
80.00	<p>Point for the cor. of secs. 25 and 36 only.</p>												
	<p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p>												
	<table style="margin-left: auto; margin-right: auto;"> <tr> <td style="text-align: center;">T 23 N</td> <td style="border-left: 1px solid black; padding-left: 5px;"></td> <td style="text-align: center;">T 23 N</td> </tr> <tr> <td style="text-align: center;">S 25</td> <td style="border-left: 1px solid black; padding-left: 5px;"></td> <td style="text-align: center;">R 25 E</td> </tr> <tr> <td style="text-align: center;">S 36</td> <td style="border-left: 1px solid black; padding-left: 5px;"></td> <td style="text-align: center;">S 31</td> </tr> <tr> <td style="text-align: center;">R 24 E</td> <td style="border-left: 1px solid black; padding-left: 5px;"></td> <td></td> </tr> </table>	T 23 N		T 23 N	S 25		R 25 E	S 36		S 31	R 24 E		
T 23 N		T 23 N											
S 25		R 25 E											
S 36		S 31											
R 24 E													
	<p style="text-align: center;">2008</p>												
	<p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p>												
	<p>Land, nearly level.</p>												
	<p>Soil, sandy clay.</p>												
	<p>Timber, scattered piñon and juniper; undergrowth, greasewood and native grasses.</p>												
	<hr/>												
	<p>North, on the E. bdy. of sec. 25.</p>												
	<p>Over nearly level land.</p>												
18.50	<p>Top of ridge, bears. N. 60° E. and S. 60° W.</p>												

**Survey of the Sixth Guide Meridian East (East Boundary),
T. 23 N., R. 24 E., Gila and Salt River Meridian, Arizona**

CHAINS													
40.00	<p>Point for the 1/4 sec. cor. of sec. 25 only.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center;"> <table border="0"> <tr><td></td><td>T 23 N</td><td></td></tr> <tr><td></td><td>R 24 E</td><td>R 25 E</td></tr> <tr><td></td><td>1/4 S 25</td><td> </td></tr> </table> <p>2008</p> </div> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p>		T 23 N			R 24 E	R 25 E		1/4 S 25				
	T 23 N												
	R 24 E	R 25 E											
	1/4 S 25												
79.60	Trail road, bears N. 40° E. and S. 40° W.												
80.00	<p>Point for the cor. of secs. 24 and 25 only.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center;"> <table border="0"> <tr><td></td><td>T 23 N</td><td>T 23 N</td></tr> <tr><td></td><td>S 24</td><td>R 25 E</td></tr> <tr><td></td><td>S 25</td><td>S 30</td></tr> <tr><td></td><td>R 24 E</td><td> </td></tr> </table> <p>2008</p> </div> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p> <p>Land, nearly level. Soil, sandy clay. Timber, scattered piñon and juniper; undergrowth, greasewood and native grasses.</p> <hr/> <p>North, on the E. bdy. of sec. 24.</p> <p>Over nearly level land.</p>		T 23 N	T 23 N		S 24	R 25 E		S 25	S 30		R 24 E	
	T 23 N	T 23 N											
	S 24	R 25 E											
	S 25	S 30											
	R 24 E												
7.20	Trail road, bears N. 50° E. and S. 50° W.												
40.00	<p>Point for the 1/4 sec. cor. of sec. 24 only.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p>												

**Survey of the Sixth Guide Meridian East (East Boundary),
T. 23 N., R. 24 E., Gila and Salt River Meridian, Arizona**

CHAINS													
	<table border="0"> <tr><td></td><td align="center">T 23 N</td><td></td></tr> <tr><td></td><td align="center">R 24 E</td><td align="center">R 25 E</td></tr> <tr><td></td><td align="center">1/4 S 24</td><td></td></tr> </table>		T 23 N			R 24 E	R 25 E		1/4 S 24				
	T 23 N												
	R 24 E	R 25 E											
	1/4 S 24												
	2008												
	Deposit a magnet, in a white plastic case, at the base of the stainless steel post.												
66.20	Trail road, bears S. 70° W. and N. 70° E.												
73.20	Trail road, bears S. 60° W. and N. 60° E.												
80.00	Point for the cor. of secs. 13 and 24 only.												
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.												
	<table border="0"> <tr><td></td><td align="center">T 23 N</td><td align="center">T 23 N</td></tr> <tr><td></td><td align="center">S 13</td><td align="center">R 25 E</td></tr> <tr><td></td><td align="center">S 24</td><td align="center">S 19</td></tr> <tr><td></td><td align="center">R 24 E</td><td></td></tr> </table>		T 23 N	T 23 N		S 13	R 25 E		S 24	S 19		R 24 E	
	T 23 N	T 23 N											
	S 13	R 25 E											
	S 24	S 19											
	R 24 E												
	2008												
	Deposit a magnet, in a white plastic case, at the base of the stainless steel post.												
	Land, nearly level. Soil, sandy clay. Timber, scattered piñon and juniper; undergrowth, greasewood and native grasses.												
	<hr/>												
	North, on the E. bdy. of sec. 13.												
	Over nearly level to rugged land.												
40.00	Point for the 1/4 sec. cor. of sec. 13 only.												
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.												
	<table border="0"> <tr><td></td><td align="center">T 23 N</td><td></td></tr> <tr><td></td><td align="center">R 24 E</td><td align="center">R 25 E</td></tr> <tr><td></td><td align="center">1/4 S 13</td><td></td></tr> </table>		T 23 N			R 24 E	R 25 E		1/4 S 13				
	T 23 N												
	R 24 E	R 25 E											
	1/4 S 13												
	2008												
	Deposit a magnet, in a white plastic case, at the base of the stainless steel post.												

**Survey of the Sixth Guide Meridian East (East Boundary),
T. 23 N., R. 24 E., Gila and Salt River Meridian, Arizona**

CHAINS									
43.40	Top of ridge, bears N. 85° E. and S. 85° W.								
78.20	Top of ridge, bears S. 40° E. and N. 40° W.								
80.00	Point for the cor. of secs. 12 and 13 only.								
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.								
	<table border="0" style="margin-left: auto; margin-right: auto;"> <tr> <td style="border-right: 1px solid black; padding: 0 5px;">T 23 N</td> <td style="padding: 0 5px;">T 23 N</td> </tr> <tr> <td style="border-right: 1px solid black; padding: 0 5px;">S 12</td> <td style="padding: 0 5px;">R 25 E</td> </tr> <tr> <td style="border-right: 1px solid black; padding: 0 5px;">S 13</td> <td style="padding: 0 5px;">S 18</td> </tr> <tr> <td style="border-right: 1px solid black; padding: 0 5px;">R 24 E</td> <td></td> </tr> </table>	T 23 N	T 23 N	S 12	R 25 E	S 13	S 18	R 24 E	
T 23 N	T 23 N								
S 12	R 25 E								
S 13	S 18								
R 24 E									
	2008								
	Deposit a magnet, in a white plastic case, at the base of the stainless steel post.								
	Land, nearly level to rugged. Soil, sandy clay, rocky with sandstone outcrops. Timber, scattered piñon and juniper; undergrowth, greasewood and native grass.								
	North, on the E. bdy. of sec. 12.								
	Over rugged and broken land.								
40.00	Point for the 1/4 sec. cor. of sec. 12 only.								
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.								
	<table border="0" style="margin-left: auto; margin-right: auto;"> <tr> <td style="border-right: 1px solid black; padding: 0 5px;">R 24 E</td> <td style="padding: 0 5px;">T 23 N</td> </tr> <tr> <td style="border-right: 1px solid black; padding: 0 5px;">1/4 S 12</td> <td style="padding: 0 5px;">R 25 E</td> </tr> </table>	R 24 E	T 23 N	1/4 S 12	R 25 E				
R 24 E	T 23 N								
1/4 S 12	R 25 E								
	2008								
	Deposit a magnet, in a white plastic case, at the base of the stainless steel post.								
80.00	Point for the cor. of secs. 1 and 12 only.								
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.								

**Survey of the Sixth Guide Meridian East (East Boundary),
T. 23 N., R. 24 E., Gila and Salt River Meridian, Arizona**

CHAINS											
	<table border="0" style="margin-left: auto; margin-right: auto;"> <tr> <td style="padding-right: 10px;">T 23 N</td> <td style="border-left: 1px solid black; padding-left: 10px;">T 23 N</td> </tr> <tr> <td></td> <td style="border-left: 1px solid black; padding-left: 10px;">R 25 E</td> </tr> <tr> <td style="border-bottom: 1px solid black; padding-bottom: 5px;">S 1</td> <td style="border-left: 1px solid black; padding-left: 10px; border-bottom: 1px solid black;">S 7</td> </tr> <tr> <td style="padding-top: 5px;">S 12</td> <td style="border-left: 1px solid black; padding-left: 10px; padding-top: 5px;"></td> </tr> <tr> <td style="padding-top: 5px;">R 24 E</td> <td style="border-left: 1px solid black; padding-left: 10px; padding-top: 5px;"></td> </tr> </table>	T 23 N	T 23 N		R 25 E	S 1	S 7	S 12		R 24 E	
T 23 N	T 23 N										
	R 25 E										
S 1	S 7										
S 12											
R 24 E											
	<p align="center">2008</p> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p> <p>Land, rugged and broken. Soil, sandy clay and rocky sandstone outcrops. Timber, scattered piñon and juniper; undergrowth, greasewood, native grasses.</p> <hr/>										
	<p>North, on the E. bdy. of sec. 1.</p> <p>Over rugged to nearly level land.</p>										
40.00	<p>Point for the 1/4 sec. cor. of sec. 1 only.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p>										
	<table border="0" style="margin-left: auto; margin-right: auto;"> <tr> <td></td> <td style="padding-right: 10px;">T 23 N</td> <td></td> </tr> <tr> <td style="padding-right: 10px;">R 24 E</td> <td style="border-left: 1px solid black; padding-left: 10px;"></td> <td style="padding-left: 10px;">R 25 E</td> </tr> <tr> <td style="border-bottom: 1px solid black; padding-bottom: 5px;">1/4 S 1</td> <td style="border-left: 1px solid black; padding-left: 10px; border-bottom: 1px solid black;"></td> <td style="padding-left: 10px;"></td> </tr> </table> <p align="center">2008</p> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p>		T 23 N		R 24 E		R 25 E	1/4 S 1			
	T 23 N										
R 24 E		R 25 E									
1/4 S 1											
72.70	<p>Trail road, bears S. 80° E. and N. 80° W.</p>										
80.00	<p>The cor. of Tps. 23 and 24 N., R. 24 E., monumented with a stainless steel post, 2 1/2 ins. diam., firmly set, projecting 4 ins. above ground, with brass cap mkd. T24N T23N R24E R25E S36 S31 S1 S6 2004.</p> <p>This cor. now functions as the cor. of Tps. 23 and 24 N., R. 24 E. only.</p> <p>Remark the brass cap to read</p>										

**Survey of the Sixth Guide Meridian East (East Boundary),
T. 23 N., R. 24 E., Gila and Salt River Meridian, Arizona**

CHAINS																					
	<table border="1" style="margin-left: auto; margin-right: auto;"> <tr> <td>T 24 N</td> <td>T 23 N</td> </tr> <tr> <td>R 24 E</td> <td>R 25 E</td> </tr> <tr> <td>S 36</td> <td>S 6</td> </tr> <tr> <td>S 1</td> <td></td> </tr> <tr> <td>T 23 N</td> <td></td> </tr> </table> <p style="text-align: center;">2004 2008</p> <p>Land, rugged to nearly level. Soil, sandy clay. Timber, scattered piñon and juniper; undergrowth, greasewood and native grasses.</p> <hr/> <p align="center">Dependent Resurvey of the North Boundary, T. 22 N., R. 25 E., Gila and Salt River Meridian, Arizona</p> <hr/> <p align="center">Restoring the survey executed by Frank Follman, in 1882</p> <hr/> <p>From the cor. of Tps. 22 and 23 N., Rs. 25 and 26 E., monumented with a stainless post 2 1/2 ins. diam., firmly set, projecting 4 ins. above an embedded mound of stone, with brass mkd. T23N R25E R26E S36 S31 S1 S6 T22N 2003 2004.</p> <p>Add the marks 2008 to the brass cap.</p> <p>S. 89°17' W., bet. secs. 1 and 36.</p> <p>Over nearly level land.</p> <p>40.09 Point for the 1/4 sec. cor. of secs. 1 and 36, at proportionate dist.; there is no remaining evidence of the orig. cor.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <table border="1" style="margin-left: auto; margin-right: auto;"> <tr> <td>T 23 N</td> <td>R 25 E</td> </tr> <tr> <td></td> <td>S 36</td> </tr> <tr> <td>1/4</td> <td>—</td> </tr> <tr> <td></td> <td>S 1</td> </tr> <tr> <td>T 22 N</td> <td></td> </tr> </table> <p style="text-align: center;">2008</p> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p> <p>80.18 Point for the cor. of secs. 1, 2, 35 and 36, at proportionate dist.; there is no remaining evidence of the orig. cor.</p>	T 24 N	T 23 N	R 24 E	R 25 E	S 36	S 6	S 1		T 23 N		T 23 N	R 25 E		S 36	1/4	—		S 1	T 22 N	
T 24 N	T 23 N																				
R 24 E	R 25 E																				
S 36	S 6																				
S 1																					
T 23 N																					
T 23 N	R 25 E																				
	S 36																				
1/4	—																				
	S 1																				
T 22 N																					

**Dependent Resurvey of the North Boundary,
T. 22 N., R. 25 E., Gila and Salt River Meridian, Arizona**

CHAINS	
	<p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T 23 N R 25 E S 35 S 36 S 2 S 1 T 22 N</p> <p style="text-align: center;">2008</p> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p> <hr/> <p>S. 89°17 W., bet. secs. 2 and 35.</p> <p>Over nearly level land.</p>
20.55	Trail road, bears N. 35° E. and S. 35° W.
40.09	<p>Point for the 1/4 sec. cor. of secs. 2 and 35, at proportionate dist., there is no remaining evidence of the orig. cor.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T 23 N R 25 E S 35 1/4 ——— S 2 T 22 N</p> <p style="text-align: center;">2008</p> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p>
49.90	Trail road, bears N. 50° E. and S. 50° W.
68.55	Trail road, bears N. 25° E. and S. 25° W.
80.18	<p>Point for the cor. of secs. 2, 3, 34 and 35, at proportionate dist.; there is no remaining evidence of the orig. cor.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p>

**Dependent Resurvey of the North Boundary,
T. 22 N., R. 25 E., Gila and Salt River Meridian, Arizona**

CHAINS									
	<table style="margin-left: auto; margin-right: auto;"> <tr><td>T 23 N</td><td>R 25 E</td></tr> <tr><td>S 34</td><td>S 35</td></tr> <tr><td>S 3</td><td>S 2</td></tr> <tr><td colspan="2">T 22 N</td></tr> </table> <p style="text-align: center;">2008</p> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p> <hr/> <p>S. 89°17' W., on the N. bdy. of sec. 3.</p> <p>Over rugged to rolling land.</p>	T 23 N	R 25 E	S 34	S 35	S 3	S 2	T 22 N	
T 23 N	R 25 E								
S 34	S 35								
S 3	S 2								
T 22 N									
25.30	Top of ridge, bears N. 40° E. and S. 40° W.								
40.09	Point for the 1/4 sec. cor. of secs. 3 and 34, at proportionate dist., there is no remaining evidence of the orig. cor.								
	This cor. now functions as the 1/4 sec. cor. of sec. 3 only.								
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.								
	<table style="margin-left: auto; margin-right: auto;"> <tr><td>T 23 N</td><td>R 25 E</td></tr> <tr><td colspan="2"><hr/></td></tr> <tr><td colspan="2">1/4 S 3</td></tr> <tr><td>T 22 N</td><td>R 25 E</td></tr> </table> <p style="text-align: center;">2008</p> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p>	T 23 N	R 25 E	<hr/>		1/4 S 3		T 22 N	R 25 E
T 23 N	R 25 E								
<hr/>									
1/4 S 3									
T 22 N	R 25 E								
80.18	Point for the cor. of secs. 3, 4, 33 and 34, at proportionate dist., there was no remaining evidence of the orig. cor.								
	This cor. now functions as the cor. of secs. 3 and 4 only.								
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.								
	<table style="margin-left: auto; margin-right: auto;"> <tr><td>T 23 N</td><td>R 25 E</td></tr> <tr><td>S</td><td>33</td></tr> <tr><td>S 4</td><td>S 3</td></tr> <tr><td>T 22 N</td><td>R 25 E</td></tr> </table> <p style="text-align: center;">2008</p>	T 23 N	R 25 E	S	33	S 4	S 3	T 22 N	R 25 E
T 23 N	R 25 E								
S	33								
S 4	S 3								
T 22 N	R 25 E								

**Dependent Resurvey of the North Boundary,
T. 22 N., R. 25 E., Gila and Salt River Meridian, Arizona**

CHAINS	
	<p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p> <hr/> <p>S. 89°17' W., on the N. bdy. of sec. 4.</p> <p>Over rugged to rolling land.</p>
40.09	<p>Point for the 1/4 sec. cor. of secs. 4 and 33, at proportionate dist., there is no remaining evidence of the orig. cor.</p> <p>This cor. now functions as the 1/4 sec. cor. of sec. 4 only.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center;"> <p>T 23 N R 25 E</p> <hr style="width: 50px; margin: 0 auto;"/> <p>1/4 S 4</p> <p>T 22 N R 25 E</p> <p>2008</p> </div> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p>
80.18	<p>Point for the cor. of secs. 4, 5, 32 and 33 at proportionate dist., there is no remaining evidence of the orig. cor.</p> <p>This cor. now functions as the cor. of secs. 4 and 5 only.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center;"> <p>T 23 N R 25 E</p> <p style="margin-left: 100px;">S 32</p> <hr style="width: 100px; margin: 0 auto;"/> <p style="margin-left: 50px;">S 5 S 4</p> <p>T 22 N R 25 E</p> <p>2008</p> </div> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p> <hr/> <p>S. 89°17' W., on the N. bdy. of sec. 5.</p> <p>Over nearly level land.</p>
40.09	<p>Point for the 1/4 sec. cor. of secs. 5 and 32, at proportionate dist., there is no remaining evidence of the orig. cor.</p> <p>This cor. now functions as the 1/4 sec. cor. of sec. 5 only.</p>

**Dependent Resurvey of the North Boundary,
T. 22 N., R. 25 E., Gila and Salt River Meridian, Arizona**

CHAINS	
80.18	<p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T 23 N R 25 E ----- 1/4 S 5 T 22 N R 25 E</p> <p style="text-align: center;">2008</p> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p> <p>Point for the cor. of secs. 5, 6, 31 and 32, at proportionate dist., there was no remaining evidence of the orig. cor.</p> <p>This cor. now functions as the cor. of secs. 5 and 6 only.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T 23 N R 25 E S 31 ----- S 6 S 5 T 22 N R 25 E</p> <p style="text-align: center;">2008</p> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p> <hr/> <p>S. 89°17' W., on the N. bdy. of sec. 6.</p> <p>Over nearly level land.</p>
40.09	<p>Point for the 1/4 sec. cor. of secs. 6 and 31, at proportionate dist., there is no remaining evidence of the orig. cor.</p> <p>This cor. now functions as the 1/4 sec. cor. of sec. 6 only.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T 23 N R 25 E ----- 1/4 S 6 T 22 N R 25 E</p> <p style="text-align: center;">2008</p>

**Dependent Resurvey of the North Boundary,
T. 22 N., R. 25 E., Gila and Salt River Meridian, Arizona**

CHAINS	<p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p>
42.40	<p>Sabito Wash, 15 ft. wide, 10 ft. deep, drains S. 35° W.</p>
78.98	<p>The cor. of Tps. 22 and 23 N., Rs. 24 and 25 E., hereinbefore described.</p> <hr/> <p align="center">Survey of the North Boundary, T. 23 N., R. 25 E., Gila and Salt River Meridian, Arizona</p> <hr/> <p>From the cor. of Tps. 23 and 24 N., R. 25 and 26 E. monumented with a stainless steel post, 2 1/2 ins. diam., firmly set, projecting 4 ins. above ground, brass cap mkd. T24N R25E R26E S36 S31 S1 S6 T23N 2002.</p> <p>Add the marks 2008 to the brass cap.</p> <p>West, bet. secs. 1 and 36.</p> <p>Over rolling to rugged land.</p>
40.00	<p>Point for the 1/4 sec. cor. of secs. 1 and 36.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p align="center"> T 24 N R 25 E S 36 1/4 ——— S 1 T 23 N 2008 </p> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p>
61.90	<p>Apache County Road C323, a graded road, 21 ft. wide, bears S. 25° E. and N. 25° W.</p>
80.00	<p>Point for the cor. of secs. 1, 2, 35 and 36.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p>

**Survey of the North Boundary,
T. 23 N., R. 25 E., Gila and Salt River Meridian, Arizona**

CHAINS											
	<table style="margin-left: auto; margin-right: auto;"> <tr><td>T 24 N</td><td>R 25 E</td></tr> <tr><td>S 35</td><td>S 36</td></tr> <tr><td>S 2</td><td>S 1</td></tr> <tr><td colspan="2">T 23 N</td></tr> </table> <p style="text-align: center;">2008</p>	T 24 N	R 25 E	S 35	S 36	S 2	S 1	T 23 N			
T 24 N	R 25 E										
S 35	S 36										
S 2	S 1										
T 23 N											
	<p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p> <p>Land, rolling to rugged. Soil, sandy clay. Timber, scattered piñon and juniper; undergrowth, greasewood and native grasses.</p> <hr/> <p>West, bet. secs. 2 and 35.</p> <p>Over rolling to rugged land.</p>										
40.00	<p>Point for the 1/4 sec. cor. of secs. 2 and 35.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p>										
	<table style="margin-left: auto; margin-right: auto;"> <tr><td>T 24 N</td><td>R 25 E</td></tr> <tr><td>S 35</td><td></td></tr> <tr><td>1/4</td><td>—</td></tr> <tr><td>S 2</td><td></td></tr> <tr><td colspan="2">T 23 N</td></tr> </table> <p style="text-align: center;">2008</p>	T 24 N	R 25 E	S 35		1/4	—	S 2		T 23 N	
T 24 N	R 25 E										
S 35											
1/4	—										
S 2											
T 23 N											
53.10	<p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p> <p>Trail road, bears S. 20° E. and N. 20° W.</p>										
80.00	<p>Point for the cor. of secs. 2, 3, 34 and 35.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p>										
	<table style="margin-left: auto; margin-right: auto;"> <tr><td>T 24 N</td><td>R 25 E</td></tr> <tr><td>S 34</td><td>S 35</td></tr> <tr><td>S 3</td><td>S 2</td></tr> <tr><td colspan="2">T 23 N</td></tr> </table> <p style="text-align: center;">2008</p>	T 24 N	R 25 E	S 34	S 35	S 3	S 2	T 23 N			
T 24 N	R 25 E										
S 34	S 35										
S 3	S 2										
T 23 N											
	<p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p>										

**Survey of the North Boundary,
T. 23 N., R. 25 E., Gila and Salt River Meridian, Arizona**

CHAINS	
	<p>Land, rolling to rugged. Soil, sandy clay. Timber, scattered piñon and juniper; undergrowth, greasewood and native grasses.</p> <hr/> <p>West, bet. secs. 3 and 34.</p> <p>Over rolling to rugged land.</p>
26.90	Trail road, bears N. 65° E. and S. 65° W.
40.00	<p>Point for the 1/4 sec. cor. of secs. 3 and 34.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center;"> <p>T 24 N R 25 E S 34 1/4 ——— S 3 T 23 N</p> <p>2008</p> </div> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p>
80.00	<p>Point for the cor. of secs. 3, 4, 33 and 34.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center;"> <p>T 24 N R 25 E S 33 S 34 S 4 S 3 T 23 N</p> <p>2008</p> </div> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p> <p>Land, rolling to rugged. Soil, sandy clay. Timber, scattered piñon and juniper; undergrowth, greasewood and native grasses.</p> <hr/> <p>West, bet. secs. 4 and 33.</p> <p>Over rolling to rugged land.</p>

**Survey of the North Boundary,
T. 23 N., R. 25 E., Gila and Salt River Meridian, Arizona**

CHAINS	
40.00	<p>Point for the 1/4 sec. cor. of secs. 4 and 33.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center;"> <p>T 24 N R 25 E S 33 1/4 ——— S 4 T 23 N</p> <p>2008</p> </div> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p>
80.00	<p>Point for the cor. of secs. 4, 5, 32 and 33.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center;"> <p>T 24 N R 25 E S 32 S 33 S 5 S 4 T 23 N</p> <p>2008</p> </div> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p> <p>Land, rolling to rugged. Soil, sandy clay. Timber, scattered piñon and juniper; undergrowth, greasewood and native grasses.</p> <hr/> <p>West bet. secs. 5 and 32.</p> <p>Over rolling to rugged land.</p>
40.00	<p>Point for the 1/4 sec. cor. of secs. 5 and 32.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p>

**Survey of the North Boundary,
T. 23 N., R. 25 E., Gila and Salt River Meridian, Arizona**

CHAINS	
	T 24 N R 25 E S 32 1/4 ——— S 5 T 23 N 2008
	Deposit a magnet, in a white plastic case, at the base of the stainless steel post.
80.00	Point for the cor. of secs. 5, 6, 31 and 32. Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.
	T 24 N R 25 E S 31 S 32 ——— ——— S 6 S 5 T 23 N 2008
	Deposit a magnet, in a white plastic case, at the base of the stainless steel post.
	Land, rolling to rugged. Soil, sandy clay. Timber, scattered piñon and juniper; undergrowth, greasewood and native grasses.
	<hr/> West, bet. secs. 6 and 31. Over rolling to rugged land.
36.60	Wash, 80 ft. wide, 20 ft. deep, drains S. 5° E.
37.95	Trail road, bears S. 15° E. and N. 15° W.
40.00	Point for the 1/4 sec. cor. of secs. 6 and 31. Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.
	T 24 N R 25 E S 31 1/4 ——— S 6 T 23 N 2008

**Survey of the North Boundary,
T. 23 N., R. 25 E., Gila and Salt River Meridian, Arizona**

CHAINS	<p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p>																	
79.51	<p>Point for the closing cor. of Tps. 23 and 24 N., R. 25 E., at intersection with the Sixth Guide Meridian East (east boundary), T. 24 N., R. 24 E.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., flush with the surface of the ground, with brass cap mkd.</p> <div style="text-align: center; margin: 10px 0;"> <table style="border-collapse: collapse; margin: auto;"> <tr> <td style="border-right: 1px solid black; padding: 0 5px;">T 24 N</td> <td style="padding: 0 5px;">T 24 N</td> </tr> <tr> <td style="border-right: 1px solid black; padding: 0 5px;">R 24 E</td> <td style="padding: 0 5px;">R 25 E</td> </tr> <tr> <td style="border-right: 1px solid black; padding: 0 5px;">S 36</td> <td style="padding: 0 5px;">S 31</td> </tr> <tr> <td style="border-right: 1px solid black; padding: 0 5px;"></td> <td style="padding: 0 5px;">CC</td> </tr> <tr> <td style="border-right: 1px solid black; padding: 0 5px;"></td> <td style="padding: 0 5px;">S 6</td> </tr> <tr> <td style="border-right: 1px solid black; padding: 0 5px;"></td> <td style="padding: 0 5px;">T 23 N</td> </tr> </table> </div> <p style="text-align: center; margin: 10px 0;">2008</p> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p> <p>Cor. is located on the S. edge of a trail road, bears N. 75° E. and S. 75° W.</p> <p>From this cor. point, the 1/4 sec. cor. of secs. 31 and 36, Tps. 24 N., Rs. 24 and 25 E., bears North, 34.04 chs. dist., monumented with a stainless steel post, 2 1/2 ins. diam., firmly set, projecting 4 ins. above ground, with brass cap mkd. T24N R24E R25E 1/4 S36 S31 2004.</p> <p>This cor. now functions as the 1/4 sec. cor. of sec. 36 only.</p> <p>Remark the brass cap to read</p> <div style="text-align: center; margin: 10px 0;"> <table style="border-collapse: collapse; margin: auto;"> <tr> <td style="padding: 0 5px;">T 24 N</td> </tr> <tr> <td style="border-right: 1px solid black; padding: 0 5px;">R 24 E</td> <td style="padding: 0 5px;">R 25 E</td> </tr> <tr> <td style="border-right: 1px solid black; padding: 0 5px;">1/4 S 36</td> <td style="padding: 0 5px;"></td> </tr> </table> </div> <p style="text-align: center; margin: 10px 0;">2008 2004</p> <p>From this same cor. point, the cor. of Tps. 23 and 24 N., R. 24 E., bears South, 5.96 chs. dist., hereinbefore described.</p>	T 24 N	T 24 N	R 24 E	R 25 E	S 36	S 31		CC		S 6		T 23 N	T 24 N	R 24 E	R 25 E	1/4 S 36	
T 24 N	T 24 N																	
R 24 E	R 25 E																	
S 36	S 31																	
	CC																	
	S 6																	
	T 23 N																	
T 24 N																		
R 24 E	R 25 E																	
1/4 S 36																		

**Survey of the North Boundary,
T. 23 N., R. 25 E., Gila and Salt River Meridian, Arizona**

CHAINS	<p>Land, rolling to rugged. Soil, sandy clay. Timber, scattered piñon and juniper; undergrowth, greasewood and native grasses.</p> <hr/> <p align="center">Survey of a Sectional Correction Line, T. 23 N., R. 25 E., Gila and Salt River Meridian, Arizona</p> <hr/> <p>Note: The results of the dependent resurvey of the N. bdy., T. 22 N., R. 25 E., exceeds the specified rectangular limits for alinement to control the subdivision of this township. This necessitates the need for the establishment of a sectional correction line.</p> <p>From the cor. of secs. 25, 30, 31 and 36, on the E. bdy. of the Tp., monumented with stainless steel post, 2 1/2 ins. diam., firmly set, projecting 4 ins. above ground, with brass cap mkd. T23N R25E R26E S25 S30 S36 S31 2003.</p> <p>Add the marks 2008 to brass cap.</p> <p>West, bet. secs. 25 and 36.</p> <p>Over nearly level to rugged land.</p> <p>24.25 Trail road, bears N. 55° E. and S. 55° W.</p> <p>40.00 Point for the 1/4 sec. cor. of secs. 25 and 36.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p align="center">T 23 N R 25 E S 25 1/4 ——— S 36</p> <p align="center">2008</p> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p> <p>80.00 Point for the cor. of secs. 25, 26, 35 and 36.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p>
--------	---

**Survey of a Sectional Correction Line,
T. 23 N., R. 25 E., Gila and Salt River Meridian, Arizona**

CHAINS	
	T 23 N R 25 E S 26 S 25 S 35 S 36 2008
	Deposit a magnet, in a white plastic case, at the base of the stainless steel post. Land, nearly level to rugged. Soil, sandy clay. Timber, scattered piñon and juniper; undergrowth, greasewood and native grasses.
	West, bet. secs. 26 and 35. Over nearly level to rugged land.
40.00	Point for the 1/4 sec. cor. of secs. 26 and 35. Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.
	T 23 N R 25 E S 26 1/4 ——— S 35 2008
	Deposit a magnet, in a white plastic case, at the base of the stainless steel post.
69.30	Trail road, bears N. 15° E. and S. 15° W.
76.25	East bank of a wash, 40 ft. high, bears N. 5° E. and S. 5° W.
80.00	Point for the cor. of secs. 26, 27, 34 and 35. Set a magnet, in a white plastic case, 24 ins. below the surface of the ground. from which A stainless steel post, 28 ins. long, 2 1/2 ins. diam., set 24 ins. in the ground, for a reference monument, bears S. 45 00' E., 210.00 ft. dist., with brass cap mkd. RM T23N R25E S35 210.0 FT. TO COR. 2008 and an arrow pointing to the cor. Deposit a magnet, in a white plastic case, at the base of the stainless steel post.

**Survey of a Sectional Correction Line,
T. 23 N., R. 25 E., Gila and Salt River Meridian, Arizona**

CHAINS					
	<p>A stainless steel post, 28 ins. long, 2 1/2 ins. diam., set 24 ins. in the ground, for a reference monument, bears S. 45°00' W., 60.00 ft. dist., with brass cap mkd. RM T23N R25E S34 60.0 FT. TO COR. 2008 and an arrow pointing to the cor. Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p> <p>Cor. is located at the base of the W. bank of a wash, 285 ft. wide, 40 ft. deep, drains S 20° W.</p> <p>Land, nearly level to rugged. Soil, sandy clay. Timber, scattered piñon and juniper; undergrowth, greasewood and native grasses.</p> <hr/> <p>West, bet. secs. 27 and 34.</p> <p>Over rugged land.</p>				
40.00	<p>Point for the 1/4 sec. cor. of secs. 27 and 34.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center;"> <p>T 23 N R 25 E</p> <p>S 27</p> <p>1/4 ———</p> <p>S 34</p> <p>2008</p> </div> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p>				
80.00	<p>Point for the cor. of secs. 28, 27, 33 and 34.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center;"> <p>T 23 N R 25 E</p> <table style="margin: auto; border-collapse: collapse;"> <tr> <td style="border-right: 1px solid black; padding: 0 5px;">S 28</td> <td style="padding: 0 5px;">S 27</td> </tr> <tr> <td style="border-right: 1px solid black; padding: 0 5px;">S 33</td> <td style="padding: 0 5px;">S 34</td> </tr> </table> <p>2008</p> </div> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p>	S 28	S 27	S 33	S 34
S 28	S 27				
S 33	S 34				

**Survey of a Sectional Correction Line,
T. 23 N., R. 25 E., Gila and Salt River Meridian, Arizona**

CHAINS									
	<p>Land, rugged. Soil, sandy clay. Timber, scattered piñon and juniper; undergrowth, greasewood and native grasses.</p> <hr/> <p>West, bet. secs. 28 and 33.</p> <p>Over rugged land.</p>								
40.00	<p>Point for the 1/4 sec. cor. of secs. 28 and 33.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center;"> <table style="margin: auto;"> <tr><td>T 23 N</td><td>R 25 E</td></tr> <tr><td></td><td>S 28</td></tr> <tr><td>1/4</td><td>—</td></tr> <tr><td></td><td>S 33</td></tr> </table> <p>2008</p> </div> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p>	T 23 N	R 25 E		S 28	1/4	—		S 33
T 23 N	R 25 E								
	S 28								
1/4	—								
	S 33								
80.00	<p>Point for the cor. of secs. 29, 28, 32 and 33.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center;"> <table style="margin: auto;"> <tr><td>T 23 N</td><td>R 25 E</td></tr> <tr><td>S 29</td><td>S 28</td></tr> <tr><td>S 32</td><td>S 33</td></tr> </table> <p>2008</p> </div> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p>	T 23 N	R 25 E	S 29	S 28	S 32	S 33		
T 23 N	R 25 E								
S 29	S 28								
S 32	S 33								
	<p>Land, rugged. Soil, sandy clay. Timber, scattered piñon and juniper; undergrowth, greasewood and native grasses.</p> <hr/> <p>West, bet. secs. 29 and 32.</p> <p>Over rugged to nearly level land.</p>								
40.00	<p>Point for the 1/4 sec. cor. of secs. 29 and 32.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p>								

**Survey of a Sectional Correction Line,
T. 23 N., R. 25 E., Gila and Salt River Meridian, Arizona**

CHAINS	
	T 23 N R 25 E S 29 1/4 ——— S 32 2008
	Deposit a magnet, in a white plastic case, at the base of the stainless steel post.
70.85	Sabito Wash, 36 ft. wide, 12 ft. deep, drains S. 10° W.
80.00	Point for the cor. of secs. 29, 30, 31 and 32. Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.
	T 23 N R 25 E S 30 S 29 ——— ——— S 31 S 32 2008
	Deposit a magnet, in a white plastic case, at the base of the stainless steel post.
	Land, rugged to nearly level. Soil, sandy clay. Timber, scattered piñon and juniper; undergrowth, greasewood and native grasses.
	West, bet. secs. 30 and 31. Over nearly level land.
40.00	Point for the 1/4 sec. cor. of secs. 30 and 31. Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.
	T 23 N R 25 E S 30 1/4 ——— S 31 2008
	Deposit a magnet, in a white plastic case, at the base of the stainless steel post.

**Survey of a Sectional Correction Line,
T. 23 N., R. 25 E., Gila and Salt River Meridian, Arizona**

CHAINS

79.86

Point for the closing cor. of secs. 30 and 31, at intersection with the Sixth Guide Meridian East (east boundary), T. 23 N., R. 24 E.

Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.

T 23 N	T 23 N
R 24 E	R 25 E
	S 30
S 25	S 31
	CC

2008

Deposit a magnet, in a white plastic case, at the base of the stainless steel post.

From this cor. point, the cor. of secs. 25 and 36 only, T. 23 N., R. 24 E., bears South, 5.99 chs. dist., hereinbefore described.

From this same cor. point, the 1/4 sec. cor. of sec. 25 only, T. 23 N., R. 24 E., bears North, 34.01 chs. dist., hereinbefore described.

Land, nearly level.

Soil, sandy clay.

Timber, scattered piñon and juniper; undergrowth, greasewood and native grasses.

Point for the 1/4 sec. cor. of sec. 31 only, T. 23 N., R. 25 E., at 40.00 chs. dist. in southing from the closing cor. of secs. 30 and 31, on the W. bdy. of sec. 31.

Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.

	T 23 N	
R 24 E	R 25 E	
	1/4 S 31	

2008

Deposit a magnet, in a white plastic case, at the base of the stainless steel post.

From this cor. point, the 1/4 cor. sec. of sec. 36 only, T. 23 N., R. 24 E., bears South, 5.99 chs. dist., hereinbefore described.

**Survey of a Sectional Correction Line,
T. 23 N., R. 25 E., Gila and Salt River Meridian, Arizona**

CHAINS

From this same cor. point, the cor. of secs. 25 and 36 only, T. 23 N., R. 24 E., bears North, 34.01 chs. dist., hereinbefore described.

**Survey of the Subdivisional Lines,
T. 23 N., R. 25 E., Gila and Salt River Meridian, Arizona**

From the cor. of secs. 25, 26, 35 and 36, on the sectional correction line, hereinbefore described.

S. 0°10' W., bet. secs. 35 and 36.

Over nearly level land.

- 4.35 Barbed wire fence, bears N. 40° W. and S. 40° E.
39.23 Barbed wire fence, bears S. 50° W. and N. 50° E.
40.00 Point for 1/4 sec. cor. of secs. 35 and 36.

Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.

T 23 N R 25 E
1/4
S 35 | S 36

2008

Deposit a magnet, in a white plastic case, at the base of the stainless steel post.

- 41.20 Trail road, bears S. 50° W. and N. 50° E.
52.35 Trail road, bears S. 35° W. and N. 35° E.
80.97 The cor. of secs. 1, 2, 35 and 36, on the S. bdy. of the Tp., hereinbefore described.

Land, nearly level.

Soil, sandy clay.

Timber, scattered piñon and juniper; undergrowth, greasewood and native grasses.

From the cor. of secs. 25, 26, 35 and 36, on the sectional correction line, hereinbefore described.

North, bet. secs. 25 and 26.

Over nearly level land.

**Survey of the Subdivisional Lines,
T. 23 N., R. 25 E., Gila and Salt River Meridian, Arizona**

CHAINS	
40.00	<p>Point for 1/4 sec. cor. of secs. 25 and 26.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T 23 N R 25 E 1/4 S 26 S 25</p> <p style="text-align: center;">2008</p> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p>
80.00	<p>Point for the cor. of secs. 23, 24, 25 and 26.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T 23 N R 25 E S 23 S 24 S 26 S 25</p> <p style="text-align: center;">2008</p> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p> <p>Land, nearly level. Soil, sandy clay. Timber, scattered piñon and juniper; undergrowth, greasewood and native grasses.</p> <hr/> <p>From the cor. of secs. 19, 24, 25 and 30, on the E. bdy. of the Tp., monumented with a stainless steel post, 2 1/2 ins. diam., firmly set, projecting 4 ins. above ground, with brass cap mkd. T23N R25E R26E S24 S19 S25 S30 2002.</p> <p>Add the marks 2008 to brass cap.</p> <p>N. 89°59' W., bet. secs. 24 and 25.</p> <p>Over nearly level land.</p>
31.85	Trail road, bears S. 30° E. and N. 30° W.
40.02	<p>Point for the 1/4 sec. cor. of secs. 24 and 25.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p>

**Survey of the Subdivisional Lines,
T. 23 N., R. 25 E., Gila and Salt River Meridian, Arizona**

CHAINS	
	T 23 N R 25 E S 24 1/4 ——— S 25 2008
	Deposit a magnet, in a white plastic case, at the base of the stainless steel post.
80.04	The cor. of secs. 23, 24, 25 and 26. Land, nearly level. Soil, sandy clay. Timber, scattered piñon and juniper; undergrowth, greasewood and native grasses.
	<hr/> North, bet. secs. 23 and 24. Over nearly level land.
13.15	Graded road, 20 ft. wide, bears N. 75° E. and S. 75° W.
40.00	Point of the 1/4 sec. cor. of secs. 23 and 24. Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.
	T 23 N R 25 E 1/4 S 23 S 24 2008
	Deposit a magnet, in a white plastic case, at the base of the stainless steel post.
80.00	Point for the cor. of secs. 13, 14, 23 and 24. Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.
	T 23 N R 25 E S 14 S 13 ———— S 23 S 24 2008
	Deposit a magnet, in a white plastic case, at the base of the stainless steel post.

**Survey of the Subdivisional Lines,
T. 23 N., R. 25 E., Gila and Salt River Meridian, Arizona**

CHAINS	
	<p>Land, nearly level. Soil, sandy clay. Timber, scattered piñon and juniper; undergrowth, greasewood and native grasses.</p> <hr/> <p>From the cor. of secs. 13, 18, 19 and 24, on the E. bdy. of the Tp., monumented with a stainless steel post, 2 1/2 ins. diam., firmly set, projecting 4 ins. above ground, with brass cap mkd. T23N R25E R26E S13 S18 S24 S19 2002.</p> <p>Add the marks 2008 to the brass cap.</p> <p>N. 89°59' W., bet. secs. 13 and 24.</p> <p>Over nearly level to rolling land.</p>
40.01	<p>Point for the 1/4 sec. cor. of secs. 13 and 24.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center;"> <p>T 23 N R 25 E S 13 1/4 ——— S 24</p> <p>2008</p> </div> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p>
72.30	Rim of a mesa, 50 ft. high, bears North and South.
75.35	Apache County Road C323, a graded road, 20 ft. wide, bears S. 10° E. and N. 10° W.
80.02	<p>The cor. of secs. 13, 14, 23 and 24.</p> <p>Land, nearly level to rolling. Soil, sandy clay. Timber, scattered piñon and juniper; undergrowth, greasewood and native grasses.</p> <hr/> <p>North, bet. secs. 13 and 14.</p> <p>Over rolling to nearly level land.</p>
40.00	<p>Point for 1/4 sec. cor. of secs. 13 and 14.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p>

**Survey of the Subdivisional Lines,
T. 23 N., R. 25 E., Gila and Salt River Meridian, Arizona**

CHAINS	
	T 23 N R 25 E 1/4 S 14 S 13 2008
	Deposit a magnet, in a white plastic case, at the base of the stainless steel post.
80.00	Point for the cor. of secs. 11, 12, 13 and 14.
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.
	T 23 N R 25 E S 11 S 12 S 14 S 13 2008
	Deposit a magnet, in a white plastic case, at the base of the stainless steel post.
	Land, rolling to nearly level. Soil, sandy clay. Timber, scattered piñon and juniper; undergrowth, greasewood and native grasses.
	<hr/> From the cor. of secs. 7, 12, 13 and 18, on the E. bdy. of the Tp., monumented with a stainless steel post, 2 1/2 ins. diam., firmly set, projecting 4 ins. above ground, with brass cap mkd. T23N R25E R26E S12 S7 S13 S18 2002.
	Add the marks 2008 to the brass cap.
	N. 89°59' W., bet. secs. 12 and 13.
	Over rugged to nearly level land.
35.00	Rim of mesa, bears S. 10° E. and N. 10° W.
40.00	Point for the 1/4 sec. cor. of secs. 12 and 13.
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.

**Survey of the Subdivisional Lines,
T. 23 N., R. 25 E., Gila and Salt River Meridian, Arizona**

CHAINS	
	T 23 N R 25 E S 12 1/4 ——— S 13 2008
	Deposit a magnet, in a white plastic case, at the base of the stainless steel post.
70.00	Apache County Road C323, a graded road, 24 ft. wide, bears N. 20° E. and S. 20° W.
80.00	The cor. of secs. 11, 12, 13 and 14. Land, rugged to nearly level. Soil, sandy clay. Timber, scattered piñon and juniper; undergrowth, greasewood and native grasses.
	North, bet. secs. 11 and 12. Over rugged land.
40.00	Point for the 1/4 sec. cor. of secs. 11 and 12. Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.
	T 23 N R 25 E 1/4 S 11 S 12 2008
	Deposit a magnet, in a white plastic case, at the base of the stainless steel post.
80.00	Point for the cor. of secs. 1, 2, 11 and 12. Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.
	T 23 N R 25 E S 2 S 1 ———— S 11 S 12 2008
	Deposit a magnet, in a white plastic case, at the base of the stainless steel post.

**Survey of the Subdivisional Lines,
T. 23 N., R. 25 E., Gila and Salt River Meridian, Arizona**

CHAINS	
	<p>Land, rugged. Soil, sandy clay. Timber, scattered piñon and juniper; undergrowth, greasewood and native grasses.</p> <hr/> <p>From the cor. of secs. 1, 6, 7 and 12, on the E. bdy. of the Tp., monumented with a stainless steel post, 2 1/2 ins. diam., firmly set, projecting 4 ins. above ground, with brass cap mkd. T23N R25E R26E S1 S6 S12 S7 2002.</p> <p>Add the marks 2008 to the brass cap.</p> <p>N. 89°59' W., bet. secs. 1 and 12.</p> <p>Over rugged to rolling land.</p>
34.45	Trail road, bears S. 45° E. and N. 45° W.
39.99	Point for the 1/4 sec. cor. of secs. 1 and 12.
	<p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T 23 N R 25 E S 1 1/4 ——— S 12</p> <p style="text-align: center;">2008</p> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p>
65.60	Apache County Road C323, a graded road, 24 ft. wide, bears N. 5° E. and S. 5° W.
67.02	From this point, the pump shaft of windmill No. 17-T552, bears South, 2.18 chs. dist.
79.98	The cor. of secs. 1, 2, 11 and 12.
	<p>Land, rugged to rolling. Soil, sandy clay. Timber, scattered piñon and juniper; undergrowth, greasewood and native grasses.</p> <hr/> <p>N. 0°01' W., bet. secs. 1 and 2.</p> <p>Over nearly level to rolling land.</p>
31.10	Trail road, bears S. 25° E. and N. 25° W.

**Survey of the Subdivisional Lines,
T. 23 N., R. 25 E., Gila and Salt River Meridian, Arizona**

CHAINS	
40.00	<p>Point for the 1/4 sec. cor. of secs. 1 and 2.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T 23 N R 25 E 1/4 S 2 S 1</p> <p style="text-align: center;">2008</p> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p>
46.10	Trail road, bears N. 60° E. and S. 60° W.
79.97	<p>The cor. of secs. 1, 2, 35 and 36, on the N. bdy. of the Tp., hereinbefore described.</p> <p>Land, nearly level to rolling. Soil, sandy clay. Timber, scattered piñon and juniper; undergrowth, greasewood and native grasses.</p> <hr/> <p>From the cor. of secs. 26, 27, 34 and 35, on the sectional correction line, hereinbefore described.</p> <p>S. 0°17' W., bet. secs. 34 and 35.</p> <p>Over nearly level land.</p>
2.85	Wash, 20 ft. wide, 30 ft. deep, drains S. 50° E.
40.00	<p>Point for the 1/4 sec. cor. of secs. 34 and 35.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T 23 N R 25 E 1/4 S 34 S 35</p> <p style="text-align: center;">2008</p> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p>
81.98	The cor. of secs. 2, 3, 34 and 35, on the S. bdy. of the Tp., hereinbefore described.

**Survey of the Subdivisional Lines,
T. 23 N., R. 25 E., Gila and Salt River Meridian, Arizona**

CHAINS	
	<p>Land, nearly level. Soil, sandy clay. Timber, scattered piñon and juniper; undergrowth, greasewood and native grasses.</p> <hr/> <p>From the cor. of secs. 26, 27, 34 and 35, on the sectional correctional line, hereinbefore described.</p> <p>North, bet. secs. 26 and 27.</p> <p>Over rugged to rolling land.</p>
40.00	<p>Point of the 1/4 sec. cor. of secs. 26 and 27.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T 23 N R 25 E 1/4 S 27 S 26</p> <p style="text-align: center;">2008</p> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p>
80.00	<p>Point for the cor. of secs. 22, 23, 26 and 27.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T 23 N R 25 E S 22 S 23 S 27 S 26</p> <p style="text-align: center;">2008</p> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p> <p>Land, rugged to rolling. Soil, sandy clay. Timber, scattered piñon and juniper; undergrowth, greasewood and native grasses.</p> <hr/> <p>From the cor. of secs. 23, 24, 25 and 26.</p> <p>West, bet. secs. 23 and 26.</p> <p>Over rugged land.</p>

**Survey of the Subdivisional Lines,
T. 23 N., R. 25 E., Gila and Salt River Meridian, Arizona**

CHAINS	
40.00	<p>Point for the 1/4 sec. cor. of secs. 23 and 26.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T 23 N R 25 E S 23 1/4 ——— S 26</p> <p style="text-align: center;">2008</p> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p>
63.75	Trail road, bears N. 20° E. and S. 20° W.
80.00	<p>The cor. of secs. 22, 23, 26 and 27.</p> <p>Land, rugged. Soil, sandy clay. Timber, scattered piñon and juniper; undergrowth, greasewood and native grasses.</p> <hr/> <p>North, bet. secs. 22 and 23.</p> <p>Over rolling to nearly level land.</p> <p>North, bet. secs. 22 and 23.</p>
40.00	<p>Point of the 1/4 sec. cor. of secs. 22 and 23.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T 23 N R 25 E 1/4 S 22 S 23</p> <p style="text-align: center;">2008</p> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p>
80.00	<p>Point for the cor. of secs. 14, 15, 22 and 23.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p>

**Survey of the Subdivisional Lines,
T. 23 N., R. 25 E., Gila and Salt River Meridian, Arizona**

CHAINS	
	T 23 N R 25 E S 15 S 14 S 22 S 23 2008
	Deposit a magnet, in a white plastic case, at the base of the stainless steel post. Land, rolling to nearly level. Soil, sandy clay. Timber, scattered piñon and juniper; undergrowth, greasewood and native grasses.
	<hr/> From the cor. of secs. 13, 14, 23 and 24. West, bet. secs. 14 and 23. Over nearly level to rugged land.
4.10	Trail road, bears N. 30° E. and S. 30° W.
36.10	Trail road, bears N. 45° E. and S. 45° W.
40.00	Point for the 1/4 secs. cor. of secs. 14 and 23. Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.
	T 23 N R 25 E S 14 1/4 ——— S 23 2008
80.00	Deposit a magnet, in a white plastic case, at the base of the stainless steel post. The cor. of secs, 14, 15, 22 and 23. Land, nearly level to rugged. Soil, sandy clay. Timber, scatted piñon and juniper; undergrowth, greasewood and native grasses.
	<hr/> North, bet. secs. 14 and 15. Over rugged land.
40.00	Point for the 1/4 sec. cor. of secs. 14 and 15.

**Survey of the Subdivisional Lines,
T. 23 N., R. 25 E., Gila and Salt River Meridian, Arizona**

CHAINS	
	<p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T 23 N R 25 E 1/4 S 15 S 14</p> <p style="text-align: center;">2008</p> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p>
80.00	<p>Point for the cor. of secs. 10, 11, 14 and 15.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T 23 N R 25 E S 10 S 11 S 15 S 14</p> <p style="text-align: center;">2008</p> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p> <p>Land, rugged. Soil, sandy clay. Timber, scatted piñon and juniper; undergrowth, greasewood and native grasses.</p> <hr/> <p>From the cor. of secs. 11, 12, 13 and 14.</p> <p>West, bet. secs. 11 and 14.</p> <p>Over rugged land.</p>
2.65	<p>Trail road, bears S. 5° W. and N. 5° E.</p>
40.00	<p>Point for the 1/4 sec. cor. of secs. 11 and 14.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p>

Survey of the Subdivisional Lines,
T. 23 N., R. 25 E., Gila and Salt River Meridian, Arizona

CHAINS	
	T 23 N R 25 E S 11 1/4 ——— S 14 2008
	Deposit a magnet, in a white plastic case, at the base of the stainless steel post.
80.00	The cor. of secs. 10, 11, 14 and 15. Land, rugged. Soil, sandy clay. Timber, scatted piñon and juniper; undergrowth, greasewood and native grasses.
	<hr/> North, bet. secs. 10 and 11. Over rugged land.
36.70	Wash, 20 ft. wide, 15 ft. deep, drains S. 45° W.
40.00	Point for the 1/4 sec. cor. of secs. 10 and 11. Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.
	T 23 N R 25 E 1/4 S 10 S 11 2008
	Deposit a magnet, in a white plastic case, at the base of the stainless steel post.
80.00	True point for the cor. of secs. 2, 3, 10 and 11, falls on a steep slope, on the E. bank of Sabito Wash; where it is impracticable to establish a permanent monument. From this true point, the point selected for the witness cor. to the cor. of secs. 2, 3, 10 and 11, bears N. 35°00' E., 1.50 chs. dist. Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.

**Survey of the Subdivisional Lines,
T. 23 N., R. 25 E., Gila and Salt River Meridian, Arizona**

CHAINS	
	WC T 23 N R 25 E S 3 S 2 S 10 S 11 ↙ 2008
	Deposit a magnet, in a white plastic case, at the base of the stainless steel post. Land, rugged. Soil, sandy clay. Timber, scattered piñon and juniper; undergrowth, greasewood and native grasses.
	<hr/> From the cor. of secs. 1, 2, 11 and 12. West, bet. secs. 2 and 11. Over rugged land.
40.00	Point for the 1/4 sec. cor. of secs. 2 and 11. Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.
	T 23 N R 25 E S 2 1/4 ——— S 11 2008
80.00	Deposit a magnet, in a white plastic case, at the base of the stainless steel post. True point for the cor. of secs. 2, 3, 10 and 11. Land, rugged. Soil, sandy clay. Timber, scattered piñon and juniper; undergrowth, greasewood and native grasses.
	<hr/> N. 0°02' W., bet. secs. 2 and 3. Over rugged land.
6.00	South bank of Sabito Wash, 30 ft. high, bears N. 30° E. and S. 30° W.

**Survey of the Subdivisional Lines,
T. 23 N., R. 25 E., Gila and Salt River Meridian, Arizona**

CHAINS	
11.40	Northwest bank of Sabito Wash, 30 ft. high, bears N. 30° E. and S. 30° W.
39.36	Wash, 7 ft. wide, 6 ft. deep, drains S. 65° W.
40.00	Point for the 1/4 sec. cor. of secs. 2 and 3. Set a magnet, in a white plastic case, 24 ins. below the surface of the ground. from which A stainless steel post, 28 ins. long, 2 1/2 ins. diam., set 24 ins. in the ground, for a reference monument, bears N. 30°00' E., 60.00 ft. dist., with brass cap mkd. RM T23N R25E 1/4 S2 60.0 FT. TO COR 2008 and an arrow pointing to the cor. Deposit a magnet, in a white plastic case, at the base of the stainless steel post. A stainless steel post, 28 ins. long, 2 1/2 ins. diam., set 24 ins. in the ground, for a reference monument, bears N. 60°00' W., 60.00 ft. dist., with brass cap mkd. RM T23N R25E 1/4 S3 60.00 FT. TO COR 2008 and an arrow pointing to the cor. Deposit a magnet, in a white plastic case, at the base of the stainless steel post. Cor. is located on the N. edge of a wash, 60 ft. wide, 6 ft. deep, drains S 60° W.
79.97	The cor. of secs. 2, 3, 34 and 35, on the N. bdy. of Tp., hereinbefore described. Land, rugged. Soil, sandy clay. Timber, scattered piñon and juniper; undergrowth, greasewood and native grasses. <hr/> From the cor. of secs. 27, 28, 33 and 34, on the sectional correctional line, hereinbefore described. S. 0°01' E., bet. secs. 33 and 34. Over rolling to rugged land.
40.00	Point for the 1/4 sec. cor. of secs. 33 and 34. Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.

**Survey of the Subdivisional Lines,
T. 23 N., R. 25 E., Gila and Salt River Meridian, Arizona**

CHAINS	
82.98	<p style="text-align: center;">T 23 N R 25 E 1/4 S 33 S 34</p> <p style="text-align: center;">2008</p> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p> <p>Point for the closing cor. of secs. 33 and 34, at intersection with the N. bdy. of sec. 3, T. 22 N., R. 25 E.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T 23 N R 25 E CC S 33 S 34 S 3 T 22 N R 25 E</p> <p style="text-align: center;">2008</p> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p> <p>From this cor. point, the 1/4 sec. cor. of sec. 3 only, T. 22 N., R. 25 E., bears N. 89°17' E., 39.50 chs. dist., hereinbefore described.</p> <p>From this same cor. point, the cor. of secs. 3 and 4 only, T. 22 N., R. 25 E., bears S. 89°17' W., 0.59 chs. dist., hereinbefore described.</p> <p>Land, rolling to rugged. Soil, sandy clay. Timber, scattered piñon and juniper; undergrowth, greasewood and native grasses.</p> <hr/> <p>Point for the 1/4 sec. cor. of sec. 34 only, T. 23 N., R. 25 E., at midpoint on the S. bdy. of sec. 34.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T 23 N R 25 E 1/4 S 34 T 22 N R 25 E</p> <p style="text-align: center;">2008</p>

**Survey of the Subdivisional Lines,
T. 23 N., R. 25 E., Gila and Salt River Meridian, Arizona**

CHAINS	
	<p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p> <p>From this cor. point, the cor. of secs. 2, 3, 34 and 35, bears N. 89°17' E., 39.795 chs. dist., hereinbefore described.</p> <p>From this same cor. point, the 1/4 sec. cor. of sec. 3 only, T. 22 N., R. 25 E., bears S. 89°17' W., 0.295 chs. dist., hereinbefore described.</p> <hr/> <p>From the cor. of secs. 27, 28, 33 and 34, on the sectional correctional line, hereinbefore described.</p> <p>N. 0°01' W., bet. secs. 27 and 28.</p> <p>Over rugged land.</p>
40.00	<p>Point for the 1/4 sec. cor. of secs. 27 and 28.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T 23 N R 25 E 1/4 S 28 S 27 2008</p>
80.00	<p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p> <p>Point for the cor. of secs. 21, 22, 27 and 28.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T 23 N R 25 E S 21 S 22 S 28 S 27 2008</p> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p> <p>Land, rugged. Soil, sandy clay. Timber, scattered piñon and juniper; undergrowth, greasewood and native grasses.</p> <hr/> <p>From the cor. of secs. 22, 23, 26 and 27.</p>

**Survey of the Subdivisional Lines,
T. 23 N., R. 25 E., Gila and Salt River Meridian, Arizona**

CHAINS	
	West, bet. secs. 22 and 27. Over rugged land.
40.00	Point for the 1/4 sec. cor. of secs. 22 and 27. Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd. <div style="text-align: center;"> T 23 N R 25 E S 22 1/4 ——— S 27 2008 </div>
80.00	Deposit a magnet, in a white plastic case, at the base of the stainless steel post. The cor. of secs. 21, 22, 27 and 28. Land, rugged. Soil, sandy clay. Timber, scattered piñon and juniper; undergrowth, greasewood and native grasses.

	N. 0°01' W., bet. secs. 21 and 22. Over rugged land.
40.00	Point for the 1/4 sec. cor. of secs. 21 and 22. Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd. <div style="text-align: center;"> T 23 N R 25 E 1/4 S 21 S 22 2008 </div>
80.00	Deposit a magnet, in a white plastic case, at the base of the stainless steel post. Point for the cor. of secs. 15, 16, 21 and 22. Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.

**Survey of the Subdivisional Lines,
T. 23 N., R. 25 E., Gila and Salt River Meridian, Arizona**

CHAINS	
	T 23 N R 25 E S 16 S 15 S 21 S 22 2008
	Deposit a magnet, in a white plastic case, at the base of the stainless steel post. Land, rugged. Soil, sandy clay. Timber, scattered piñon and juniper; undergrowth, greasewood and native grasses.
	<hr/> From the cor. of secs. 14, 15, 22 and 23. West, bet. secs. 15 and 22. Over rugged land.
40.00	Point for the 1/4 sec. cor. of secs. 15 and 22. Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.
	T 23 N R 25 E S 15 1/4 ——— S 22 2008
80.00	Deposit a magnet, in a white plastic case, at the base of the stainless steel post. The cor. of secs. 15, 16, 21 and 22. Land, rugged. Soil, sandy clay. Timber, scattered piñon and juniper; undergrowth, greasewood and native grasses.
	<hr/> N. 0°01' W., bet. secs. 15 and 16. Over rugged land.
40.00	Point for the 1/4 sec. cor. of secs. 15 and 16. Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.

**Survey of the Subdivisional Lines,
T. 23 N., R. 25 E., Gila and Salt River Meridian, Arizona**

CHAINS	
	T 23 N R 25 E 1/4 S 16 S 15 2008
	Deposit a magnet, in a white plastic case, at the base of the stainless steel post.
45.10	Wash, 50 ft. wide, 12 ft. deep, drains S. 40° E.
80.00	Point for the cor. of secs. 9, 10, 15 and 16.
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.
	T 23 N R 25 E S 9 S 10 S 16 S 15 2008
	Deposit a magnet, in a white plastic case, at the base of the stainless steel post.
	Land, rugged. Soil, sandy clay. Timber, scattered piñon and juniper; undergrowth, greasewood and native grasses.
	From the cor. of secs. 10, 11, 14 and 15.
	West, bet. secs. 10 and 15.
	Over rugged land.
40.00	Point for the 1/4 sec. cor. of secs. 10 and 15.
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.
	T 23 N R 25 E S 10 1/4 ——— S 15 2008
	Deposit a magnet, in a white plastic case, at the base of the stainless steel post.
80.00	The cor. of secs. 9, 10, 15 and 16.

**Survey of the Subdivisional Lines,
T. 23 N., R. 25 E., Gila and Salt River Meridian, Arizona**

CHAINS	
	<p>Land, rugged. Soil, sandy clay. Timber, scattered piñon and juniper; undergrowth, greasewood and native grasses.</p> <hr/> <p>N. 0°01' W., bet. secs. 9 and 10.</p> <p>Over rugged land.</p>
36.55	<p>Sabito Wash, 83 ft. wide, 8 ft. deep, drains N. 65° W.</p>
40.00	<p>Point for the 1/4 sec. cor. of secs. 9 and 10.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center; margin: 10px 0;"> <p>T 23 N R 25 E 1/4 S 9 S 10</p> <p>2008</p> </div> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p>
80.00	<p>Point for the cor. of secs. 3, 4, 9 and 10.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center; margin: 10px 0;"> <p>T 23 N R 25 E S 4 S 3 ----- S 9 S 10</p> <p>2008</p> </div> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p> <p>Land, rugged. Soil, sandy clay. Timber, scattered piñon and juniper; undergrowth, greasewood and native grasses.</p> <hr/> <p>From the true point for the cor. of secs. 2, 3, 10 and 11.</p> <p>West, bet. secs. 3 and 10.</p> <p>Over rugged land.</p>
2.70	<p>Sabito Wash, 130 ft. wide, 30 ft. deep, drains S. 40 E.</p>

**Survey of the Subdivisional Lines,
T. 23 N., R. 25 E., Gila and Salt River Meridian, Arizona**

CHAINS	
40.00	<p>Point for the 1/4 sec. cor. of secs. 3 and 10.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T 23 N R 25 E S 3 1/4 ——— S 10</p> <p style="text-align: center;">2008</p> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p>
62.45	Wash, 60 ft. wide, 12 ft. deep, drains N. 35° E.
80.00	<p>The cor. of secs. 3, 4, 9 and 10.</p> <p>Land, rugged. Soil, sandy clay. Timber, scattered piñon and juniper; undergrowth, greasewood and native grasses.</p> <hr/> <p>N. 0°02' W., bet. secs. 3 and 4.</p> <p>Over rugged to rolling land.</p>
40.00	<p>Point for the 1/4 sec. cor. of secs. 3 and 4.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., flush with the surface of the ground, with brass cap mkd.</p> <p style="text-align: center;">T 23 N R 25 E 1/4 S 4 S 3</p> <p style="text-align: center;">2008</p> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p>
40.05	Trail road, bears and N. 70° E. and S. 70° W.
79.97	The cor. of secs. 3, 4, 33 and 34, on the N. bdy. of the Tp., hereinbefore described.

**Survey of the Subdivisional Lines,
T. 23 N., R. 25 E., Gila and Salt River Meridian, Arizona**

CHAINS	
	<p>Land, rugged to rolling. Soil, sandy clay. Timber, scattered piñon and juniper; undergrowth, greasewood and native grasses.</p> <hr/> <p>From the cor. of secs. 28, 29, 32 and 33, on the sectional correctional line, hereinbefore described.</p> <p>S. 0°02' E., bet. secs. 32 and 33.</p> <p>Over nearly level land.</p>
40.00	<p>Point for the 1/4 sec. cor. of secs. 32 and 33.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center;"> <p>T 23 N R 25 E 1/4 S 32 S 33</p> <p>2008</p> </div> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p>
83.98	<p>Point for the closing cor. of secs. 32 and 33, at intersection with the N. bdy. of sec. 4, T. 22 N., R. 25 E.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center;"> <p>T 23 N R 25 E CC S 32 S 33 S 4 T 22 N R 25 E</p> <p>2008</p> </div> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p> <p>From this cor. point, the 1/4 sec. cor. of sec. 4 only, T. 22 N., R. 25 E., bears N. 89°17' E., 39.32 chs. dist., hereinbefore described.</p> <p>From this same cor. point, the cor. of secs. 4 and 5 only, T. 22 N., R. 25 E., bears S. 89°17' W., 0.77 chs. dist., hereinbefore described.</p>

**Survey of the Subdivisional Lines,
T. 23 N., R. 25 E., Gila and Salt River Meridian, Arizona**

CHAINS

Land, nearly level.
Soil, sandy clay.
Timber, scattered piñon and juniper; undergrowth, greasewood and native grasses.

Point for the 1/4 sec. cor. of sec. 33 only, T. 23 N., R. 25 E., at midpoint on the S. bdy. of sec. 33.

Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.

T 23 N R 25 E
1/4 S 33

T 22 N R 25 E

2008

Deposit a magnet, in a white plastic case, at the base of the stainless steel post.

From this cor. point, the cor. of secs. 3 and 4 only, T. 22 N., R. 25 E., bears N. 89°17' E., 39.41 chs. dist., hereinbefore described.

From this same cor. point, the 1/4 sec. cor. of sec. 4 only, T. 22 N., R. 25 E., bears S. 89°17' W., 0.68 chs. dist., hereinbefore described.

From the cor. of secs. 28, 29, 32 and 33, on the sectional correctional line, hereinbefore described.

N. 0°02' W., bet. secs. 28 and 29.

Over rolling to broken land.

40.00

Point for the 1/4 sec. cor. of secs. 28 and 29.

Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.

T 23 N R 25 E
1/4
S 29 | S 28

2008

Deposit a magnet, in a white plastic case, at the base of the stainless steel post.

**Survey of the Subdivisional Lines,
T. 23 N., R. 25 E., Gila and Salt River Meridian, Arizona**

CHAINS									
78.80	Wash, 10 ft. wide, 16 ft. deep, drains S. 20° E.								
80.00	Point for the cor. of secs. 20, 21, 28 and 29. Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd. <div style="text-align: center;"> <table style="margin: auto;"> <tr><td>T 23 N</td><td>R 25 E</td></tr> <tr><td>S 20</td><td>S 21</td></tr> <tr><td>S 29</td><td>S 28</td></tr> </table> <p>2008</p> </div> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p> <p>Land, rolling to broken. Soil, sandy clay. Timber, scattered piñon and juniper; undergrowth, greasewood and native grasses.</p> <hr/> <p>From the cor. of secs. 21, 22, 27 and 28.</p> <p>West, bet. secs. 21 and 28.</p> <p>Over rolling to rugged land.</p>	T 23 N	R 25 E	S 20	S 21	S 29	S 28		
T 23 N	R 25 E								
S 20	S 21								
S 29	S 28								
39.60	Wash, 15 ft. wide, 18 ft. deep, drains South.								
40.00	True point for the 1/4 sec. cor. of secs. 21 and 28, falls on the eroding SW slope of a wash; where it is impracticable to establish a permanent monument. From this true point, the point selected for the witness cor. to the 1/4 sec. cor. of secs. 21 and 28, bears N. 15°00' E., 1.00 ch. dist. Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd. <div style="text-align: center;"> <p>WC</p> <table style="margin: auto;"> <tr><td>T 23 N</td><td>R 25 E</td></tr> <tr><td>S 21</td><td></td></tr> <tr><td>1/4</td><td>—</td></tr> <tr><td>S 28</td><td></td></tr> </table> <p>↙ 2008</p> </div> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p>	T 23 N	R 25 E	S 21		1/4	—	S 28	
T 23 N	R 25 E								
S 21									
1/4	—								
S 28									
80.00	The cor. of secs. 20, 21, 28 and 29.								

**Survey of the Subdivisional Lines,
T. 23 N., R. 25 E., Gila and Salt River Meridian, Arizona**

CHAINS	
	<p>Land, rolling to rugged. Soil, sandy clay. Timber, scattered piñon and juniper; undergrowth, greasewood and native grasses.</p> <hr/> <p>N. 0°02' W., bet. secs. 20 and 21.</p> <p>Over rolling to rugged land.</p>
40.00	<p>Point for the 1/4 sec. cor. of secs. 20 and 21.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center;"> <p>T 23 N R 25 E 1/4 S 20 S 21</p> <p>2008</p> </div> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p>
80.00	<p>Point for the cor. of secs. 16, 17, 20, and 21.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center;"> <p>T 23 N R 25 E S 17 S 16 S 20 S 21</p> <p>2008</p> </div> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p> <p>Land, rolling to rugged. Soil, sandy clay. Timber, scattered piñon and juniper; undergrowth, greasewood and native grasses.</p> <hr/> <p>From the cor. of secs. 15, 16, 21 and 22.</p> <p>West, bet. secs. 16 and 21.</p> <p>Over rugged land.</p>
40.00	<p>Point for the 1/4 sec. cor. of secs. 16 and 21.</p>

Survey of the Subdivisional Lines,
T. 23 N., R. 25 E., Gila and Salt River Meridian, Arizona

CHAINS	
	<p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T 23 N R 25 E S 16 1/4 ——— S 21</p> <p style="text-align: center;">2008</p> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p>
80.00	<p>The cor. of secs. 16, 17, 20 and 21.</p> <p>Land, rugged. Soil, sandy clay. Timber, scattered piñon and juniper; undergrowth, greasewood and native grasses.</p> <hr/> <p>N. 0°02' W., bet. secs. 16 and 17.</p> <p>Over rugged land.</p>
7.35	<p>Sabito Wash, 15 ft. wide, 25 ft. deep, drains S. 85° W.</p>
40.00	<p>Point for the 1/4 sec. cor. of secs. 16 and 17.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T 23 N R 25 E 1/4 S 17 S 16</p> <p style="text-align: center;">2008</p> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p>
80.00	<p>Point for the cor. of secs. 8, 9, 16 and 17.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T 23 N R 25 E S 8 S 9 ——— S 17 S 16</p> <p style="text-align: center;">2008</p>

**Survey of the Subdivisional Lines,
T. 23 N., R. 25 E., Gila and Salt River Meridian, Arizona**

CHAINS	
	<p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p> <p>Land, rugged. Soil, sandy clay. Timber, scattered piñon and juniper; undergrowth, greasewood and native grasses.</p> <hr/> <p>From the cor. of secs. 9, 10, 15 and 16.</p> <p>West, bet. secs. 9 and 16.</p> <p>Over rugged land.</p>
33.20	Sabito Wash, 100 ft. wide, 20 ft. deep, drains S. 80° W.
40.00	<p>Point for the 1/4 sec. cor. of secs. 9 and 16.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T 23 N R 25 E S 9 1/4 ——— S 16</p> <p style="text-align: center;">2008</p>
80.00	<p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p> <p>The cor. of secs. 8, 9, 16 and 17.</p> <p>Land, rugged. Soil, sandy clay. Timber, scattered piñon and juniper; undergrowth, greasewood and native grasses.</p> <hr/> <p>N. 0°02' W., bet. secs. 8 and 9.</p> <p>Over rugged land.</p>
40.00	<p>Point for the 1/4 sec. cor. of secs. 8 and 9.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p>

Survey of the Subdivisional Lines,
T. 23 N., R. 25 E., Gila and Salt River Meridian, Arizona

CHAINS	
	T 23 N R 25 E 1/4 S 8 S 9 2008
	Deposit a magnet, in a white plastic case, at the base of the stainless steel post.
80.00	Point for the cor. of secs. 4, 5, 8 and 9. Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.
	T 23 N R 25 E S 5 S 4 --- S 8 S 9 2008
	Deposit a magnet, in a white plastic case, at the base of the stainless steel post.
	Land, rugged. Soil, sandy clay. Timber, scattered piñon and juniper; undergrowth, greasewood and native grasses.
	From the cor. of secs, 3, 4, 9 and 10. West, bet. secs. 4 and 9. Over rugged land.
40.00	Point of the 1/4 sec. cor. of secs. 4 and 9. Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.
	T 23 N R 25 E S 4 1/4 ——— S 9 2008
	Deposit a magnet, in a white plastic case, at the base of the stainless steel post.
80.00	The cor. of secs. 4, 5, 8 and 9.

Survey of the Subdivisional Lines,
T. 23 N., R. 25 E., Gila and Salt River Meridian, Arizona

CHAINS	
	<p>Land, rugged. Soil, sandy clay. Timber, scattered piñon and juniper; undergrowth, greasewood and native grasses.</p> <hr/> <p>N. 0°03' W., bet. secs. 4 and 5.</p> <p>Over rugged land.</p>
40.00	<p>Point for the 1/4 sec. cor. of secs. 4 and 5.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center;"> <p>T 23 N R 25 E 1/4 S 5 S 4 2008</p> </div> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p>
79.97	<p>The cor. of secs. 4, 5, 32 and 33, on the N. bdy. of the Tp., hereinbefore described.</p> <p>Land, rugged. Soil, sandy clay. Timber, scattered piñon and juniper; undergrowth, greasewood and native grasses.</p> <hr/> <p>From the cor. of secs. 29, 30, 31 and 32, on the sectional correction line, hereinbefore described.</p> <p>S. 0°02' E., bet. secs. 31 and 32.</p> <p>Over nearly level land.</p>
9.80	Sabito Wash, 36 ft. wide, 12 ft. deep, drains S. 60° W.
16.80	Sabito Wash, 40 ft. wide, 14 ft. deep, drains S. 20° E.
18.80	Sabito Wash, 40 ft. wide, 14 ft. deep, drains S. 30° W.
40.00	<p>Point for the 1/4 sec. cor. of secs. 31 and 32.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p>

Survey of the Subdivisional Lines,
T. 23 N., R. 25 E., Gila and Salt River Meridian, Arizona

CHAINS	
	T 23 N R 25 E 1/4 S 31 S 32 2008
	Deposit a magnet, in a white plastic case, at the base of the stainless steel post.
84.98	Point for the closing cor. of secs. 31 and 32, at intersection with the N. bdy. of sec. 5, T. 22 N., R. 25 E. Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.
	T 23 N R 25 E CC S 31 S 32 ----- S 5 T 22 N R 25 E 2008
	Deposit a magnet, in a white plastic case, at the base of the stainless steel post.
	From this cor. point, the 1/4 sec. cor. of sec. 5 only, T. 22 N., R. 25 E., bears N. 89°17' E., 39.13 chs. dist., hereinbefore described.
	From this same cor. point, the cor. of secs. 5 and 6 only, T. 22 N., R. 25 E., bears S. 89°17' W., 0.96 chs. dist., hereinbefore described.
	Land, nearly level. Soil, sandy clay. Timber, scattered piñon and juniper; undergrowth, greasewood and native grasses.
	<hr/> Point for the 1/4 sec. cor. of sec. 32 only, T. 23 N., R. 25 E., at midpoint on the S. bdy. of sec. 32.
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.

**Survey of the Subdivisional Lines,
T. 23 N., R. 25 E., Gila and Salt River Meridian, Arizona**

CHAINS	
	T 23 N R 25 E 1/4 S 32 <hr style="width: 10%; margin: auto;"/> T 22 N R 25 E 2008
	<p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p> <p>From this cor. point, the cor. of secs. 4 and 5 only, T. 22 N., R. 25 E., bears N. 89°17' E., 39.225 chs. dist., hereinbefore described.</p> <p>From this same cor. point, the 1/4 sec. cor. of sec. 5 only, T. 22 N., R. 25 E., bears S. 89°17' W., 0.865 chs. dist., hereinbefore described.</p> <hr/> <p>Point for the 1/4 sec. cor. of sec. 31 only, T. 23 N., R. 25 E., at 40.00 chs. dist. in westing from the closing cor. of secs. 31 and 32, on the S. bdy. of sec. 31.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p>
	T 23 N R 25 E 1/4 S 31 <hr style="width: 10%; margin: auto;"/> T 22 N R 25 E 2008
	<p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p> <p>From this cor. point, the cor. of secs. 5 and 6 only, T. 22 N., R. 25 E., bears N. 89°17' E., 39.04 chs. dist., hereinbefore described.</p> <p>From this same cor. point, the 1/4 sec. cor. of sec. 6 only, T. 22 N., R. 25 E., bears S. 89°17' W., 1.05 chs. dist., hereinbefore described.</p> <hr/> <p>From the cor. of secs. 29, 30, 31 and 32, on the sectional correctional line, hereinbefore described.</p> <p>N. 0°02' W., bet. secs. 29 and 30.</p> <p>Over nearly level land.</p>
40.00	Point for the 1/4 sec. cor. of secs. 29 and 30.

**Survey of the Subdivisional Lines,
T. 23 N., R. 25 E., Gila and Salt River Meridian, Arizona**

CHAINS	
	<p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T 23 N R 25 E 1/4 S 30 S 29</p> <p style="text-align: center;">2008</p> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p>
80.00	<p>Point for the cor. of secs. 19, 20, 29 and 30.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T 23 N R 25 E S 19 S 20 S 30 S 29</p> <p style="text-align: center;">2008</p> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p> <p>Land, nearly level. Soil, sandy clay. Timber, scattered piñon and juniper; undergrowth, greasewood and native grasses.</p> <hr/> <p>From the cor. of secs. 20, 21, 28 and 29.</p> <p>West, bet. secs. 20 and 29.</p> <p>Over nearly level land.</p>
.35	Wash, 10 ft. wide, 16 ft. deep, drains S. 15° E.
1.75	Same wash, 20 ft. wide, 16 ft. deep, drains West.
40.00	<p>Point for the 1/4 sec. cor. of secs. 20 and 29.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p>

**Survey of the Subdivisional Lines,
T. 23 N., R. 25 E., Gila and Salt River Meridian, Arizona**

CHAINS	
	T 23 N R 25 E S 20 1/4 ——— S 29 2008
	Deposit a magnet, in a white plastic case, at the base of the stainless steel post.
45.40	Sabito Wash, 50 ft. wide, 15 ft. deep, drains S. 30° E.
80.00	The cor. of secs. 19, 20, 29 and 30.
	Land, nearly level. Soil, sandy clay. Timber, scattered piñon and juniper; undergrowth, greasewood and native grasses.
	West, bet. secs. 19 and 30.
	Over rolling to rugged land.
36.55	Rim of mesa, bears N. 40° E. and S. 40° W.
40.00	Point for the 1/4 sec. cor. of secs. 19 and 30.
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.
	T 23 N R 25 E S 19 1/4 ——— S 30 2008
	Deposit a magnet, in a white plastic case, at the base of the stainless steel post.
79.80	Point for the closing cor. of secs. 19 and 30, at intersection with the Sixth Guide Meridian East (east boundary), T. 23 N., R. 24 E.
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.

Survey of the Subdivisional Lines,
T. 23 N., R. 25 E., Gila and Salt River Meridian, Arizona

CHAINS

T 23 N	T 23 N
R 24 E	R 25 E
	S 19
S 24	S 30
	CC

2008

Deposit a magnet, in a white plastic case, at the base of the stainless steel post.

From this cor. point, the cor. of secs. 24 and 25 only, T. 23 N., R. 24 E., bears South, 5.99 chs. dist., hereinbefore described.

From this same cor. point, the 1/4 sec. cor. of sec. 24 only, T. 23 N., R. 24 E., bears North, 34.01 chs. dist., hereinbefore described.

Land, rolling to rugged.

Soil, sandy clay.

Timber, scattered piñon and juniper; undergrowth, greasewood and native grasses.

Point for the 1/4 sec. cor. of sec. 30 only, T. 23 N., R. 25 E., at midpoint on the W. bdy. of sec. 30.

Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.

	T 23 N	
R 24 E	R 25 E	
	1/4 S 30	

2008

Deposit a magnet, in a white plastic case, at the base of the stainless steel post.

From this cor. point, the 1/4 sec. cor. of sec. 25 only, T. 23 N., R. 24 E., bears South, 5.99 chs. dist., hereinbefore described.

From this same cor. point, the cor. of secs. 25 and 36 only, T. 23 N., R. 24 E., bears North, 34.01 chs. dist., hereinbefore described.

From the cor. of secs. 19, 20, 29 and 30.

N. 0°02' W., bet. secs. 19 and 20.

Over rolling to broken land.

**Survey of the Subdivisional Lines,
T. 23 N., R. 25 E., Gila and Salt River Meridian, Arizona**

CHAINS	
40.00	<p>Point for the 1/4 sec. cor. of secs. 19 and 20.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T 23 N R 25 E 1/4 S 19 S 20</p> <p style="text-align: center;">2008</p> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p>
80.00	<p>Point for the cor. of secs. 17, 18, 19 and 20.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T 23 N R 25 E S 18 S 17 S 19 S 20</p> <p style="text-align: center;">2008</p> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p> <p>Land, rolling to broken. Soil, sandy clay. Timber, scattered piñon and juniper; undergrowth, greasewood and native grasses.</p> <hr/> <p>From the cor. of secs. 16, 17, 20 and 21.</p> <p>West, bet. secs. 17 and 20.</p> <p>Over rugged land.</p>
4.75	<p>Sabito Wash, 25 ft. wide, 20 ft. deep, drains S. 65° W.</p>
40.00	<p>Point for the 1/4 sec. cor. of secs. 17 and 20.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p>

Survey of the Subdivisional Lines,
T. 23 N., R. 25 E., Gila and Salt River Meridian, Arizona

CHAINS													
	T 23 N R 25 E S 17 1/4 ——— S 20 2008												
	Deposit a magnet, in a white plastic case, at the base of the stainless steel post.												
80.00	The cor. of secs. 17, 18, 19 and 20. Land, rugged. Soil, sandy clay. Timber, scattered piñon and juniper; undergrowth, greasewood and native grasses.												
	West, bet. secs. 18 and 19. Over nearly level land.												
40.00	Point for the 1/4 sec. cor. of secs. 18 and 19. Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.												
	T 23 N R 25 E S 18 1/4 ——— S 19 2008												
	Deposit a magnet, in a white plastic case, at the base of the stainless steel post.												
56.90	Rim of mesa, bears N. 20° E. and S. 20° W.												
79.74	Point for the closing cor. of secs. 18 and 19, at intersection with the Sixth Guide Meridian (east boundary), T. 23 N., R. 24 E. Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.												
	<table style="margin: auto; border-collapse: collapse;"> <tr> <td style="padding: 0 5px;">T 23 N</td> <td style="border-left: 1px solid black; padding: 0 5px;">T 23 N</td> <td style="padding: 0 5px;"></td> </tr> <tr> <td style="padding: 0 5px;">R 24 E</td> <td style="border-left: 1px solid black; padding: 0 5px;">R 25 E</td> <td style="padding: 0 5px;"></td> </tr> <tr> <td style="padding: 0 5px;"></td> <td style="border-left: 1px solid black; padding: 0 5px;">S 18</td> <td style="padding: 0 5px;">CC</td> </tr> <tr> <td style="padding: 0 5px;">S 13</td> <td style="border-left: 1px solid black; padding: 0 5px;">S 19</td> <td style="padding: 0 5px;"></td> </tr> </table> 2008	T 23 N	T 23 N		R 24 E	R 25 E			S 18	CC	S 13	S 19	
T 23 N	T 23 N												
R 24 E	R 25 E												
	S 18	CC											
S 13	S 19												

**Survey of the Subdivisional Lines,
T. 23 N., R. 25 E., Gila and Salt River Meridian, Arizona**

CHAINS	<p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p> <p>From this cor. point, the cor. of secs. 13 and 24 only, T. 23 N., R. 24 E., bears South, 5.99 chs. dist., hereinbefore described.</p> <p>From this same cor. point, the 1/4 sec. cor. of sec. 13 only, T. 23 N., R. 24 E., bears North, 34.01 chs. dist., hereinbefore described.</p> <p>Land, nearly level. Soil, sandy clay. Timber, scattered piñon and juniper; undergrowth, greasewood and native grasses.</p> <hr/> <p>Point for the 1/4 sec. cor. of sec. 19 only, T. 23 N., R. 25 E., at midpoint on the W. bdy. of sec. 19.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center; margin: 10px 0;"> <table style="border: none; margin: auto;"> <tr> <td></td> <td style="text-align: center;">T 23 N</td> <td></td> </tr> <tr> <td style="text-align: center;">R 24 E</td> <td style="text-align: center;"> </td> <td style="text-align: center;">R 25 E</td> </tr> <tr> <td></td> <td style="text-align: center;"> </td> <td style="text-align: center;">1/4 S 19</td> </tr> </table> </div> <p style="text-align: center;">2008</p> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p> <p>From this cor. point, the 1/4 sec. cor. of sec. 24 only, T. 23 N., R. 24 E., bears South, 5.99 chs. dist., hereinbefore described.</p> <p>From this same cor. point, the cor. of secs. 13 and 24 only, T. 23 N., R. 24 E., bears North, 34.01 chs. dist., hereinbefore described.</p> <hr/> <p>From the cor. of secs. 17, 18, 19 and 20.</p> <p>N. 0°02' W., bet. secs. 17 and 18.</p> <p>Over nearly level land.</p>		T 23 N		R 24 E		R 25 E			1/4 S 19
	T 23 N									
R 24 E		R 25 E								
		1/4 S 19								
40.00	<p>Point for the 1/4 sec. cor. of secs. 17 and 18.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p>									

Survey of the Subdivisional Lines,
T. 23 N., R. 25 E., Gila and Salt River Meridian, Arizona

CHAINS	
	T 23 N R 25 E 1/4 S 18 S 17 2008 Deposit a magnet, in a white plastic case, at the base of the stainless steel post.
80.00	Point for the cor. of secs. 7, 8, 17 and 18. Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.
	T 23 N R 25 E S 7 S 8 S 18 S 17 2008 Deposit a magnet, in a white plastic case, at the base of the stainless steel post. Land, nearly level. Soil, sandy clay. Timber, scattered piñon and juniper; undergrowth, greasewood and native grasses.
	<hr/> From the cor. of secs. 8, 9, 16 and 17. West, bet. secs. 8 and 17. Over rugged land.
40.00	Point for the 1/4 sec. cor. of secs. 8 and 17. Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.
	T 23 N R 25 E S 8 1/4 ——— S 17 2008 Deposit a magnet, in a white plastic case, at the base of the stainless steel post.
80.00	The cor. of secs. 7, 8, 17 and 18.

**Survey of the Subdivisional Lines,
T. 23 N., R. 25 E., Gila and Salt River Meridian, Arizona**

CHAINS																
	<p>Land, rugged. Soil, sandy clay. Timber, scattered piñon and juniper; undergrowth, greasewood and native grasses.</p> <hr/> <p>West, bet. secs. 7 and 18.</p> <p>Over nearly level to rugged land.</p>															
8.35	Trail road, bears N. 50° E. and S. 50° W.															
40.00	<p>Point for the 1/4 sec. cor. of secs. 7 and 18.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center; margin: 10px 0;"> <table style="margin: auto;"> <tr><td>T 23 N</td><td>R 25 E</td></tr> <tr><td></td><td>S 7</td></tr> <tr><td>1/4</td><td>—</td></tr> <tr><td></td><td>S 18</td></tr> </table> <p>2008</p> </div> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p>	T 23 N	R 25 E		S 7	1/4	—		S 18							
T 23 N	R 25 E															
	S 7															
1/4	—															
	S 18															
79.67	<p>Point for the closing cor. of secs. 7 and 18, at intersection with the Sixth Guide Meridian East (east boundary), T. 23 N., R. 24 E.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center; margin: 10px 0;"> <table style="margin: auto;"> <tr><td>T 23 N</td><td> </td><td>T 23 N</td></tr> <tr><td>R 24 E</td><td> </td><td>R 25 E</td></tr> <tr><td></td><td> </td><td>S 7</td></tr> <tr><td>S 12</td><td> </td><td>—CC</td></tr> <tr><td></td><td> </td><td>S 18</td></tr> </table> <p>2008</p> </div> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p> <p>From this cor. point, the cor. of secs. 12 and 13 only, T. 23 N., R. 24 E., bears South, 5.99 chs. dist., hereinbefore described.</p> <p>From this same cor. point, the 1/4 sec. cor. of sec. 12 only, T. 23 N., R. 24 E., bears North, 34.01 chs. dist., hereinbefore described.</p>	T 23 N		T 23 N	R 24 E		R 25 E			S 7	S 12		—CC			S 18
T 23 N		T 23 N														
R 24 E		R 25 E														
		S 7														
S 12		—CC														
		S 18														

**Survey of the Subdivisional Lines,
T. 23 N., R. 25 E., Gila and Salt River Meridian, Arizona**

CHAINS	
	<p>Land, nearly level to rugged. Soil, sandy clay. Timber, scattered piñon and juniper; undergrowth, greasewood and native grasses.</p> <hr/> <p>True point for the 1/4 sec. cor. of sec. 18 only, T. 23 N., R. 25 E., at midpoint on the W. bdy. of sec. 18, falls on an eroding steep slope of a mesa; where it is impracticable to establish a permanent monument.</p> <p>From this true point, the point selected for the witness cor. to the 1/4 cor. of sec. 18 only, bears S. 69°44' E., 3.00 chs. dist.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center;"> <p style="margin: 0;">WC ↖ T 23 N R 24 E R 25 E 1/4 S 18</p> </div> <p style="text-align: center;">2008</p> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p> <p>From this same true point, the 1/4 sec. cor. of sec. 13 only, T. 23 N., R. 24 E., bears South, 5.99 chs. dist., hereinbefore described.</p> <p>From this same true point, the cor. of secs. 12 and 13 only, T. 23 N., R. 24 E., bears North, 34.01 chs. dist., hereinbefore described.</p> <hr/> <p>From the cor. of secs. 7, 8, 17 and 18. N. 0°02' W., bet. secs. 7 and 8. Over rugged land.</p>
40.00	<p>Point for the 1/4 sec. cor. of secs. 7 and 8.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p>

**Survey of the Subdivisional Lines,
T. 23 N., R. 25 E., Gila and Salt River Meridian, Arizona**

CHAINS	
	T 23 N R 25 E 1/4 S 7 S 8 2008
	Deposit a magnet, in a white plastic case, at the base of the stainless steel post.
80.00	Point for the cor. of secs. 5, 6, 7 and 8. Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.
	T 23 N R 25 E S 6 S 5 S 7 S 8 2008
	Deposit a magnet, in a white plastic case, at the base of the stainless steel post.
	Land, rugged. Soil, sandy clay. Timber, scattered piñon and juniper; undergrowth, greasewood and native grasses.
	<hr/> From the cor. of secs. 4, 5, 8 and 9. West, bet. secs. 5 and 8. Over rugged land.
40.00	Point for the 1/4 sec. cor. of secs. 5 and 8. Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.
	T 23 N R 25 E S 5 1/4 ——— S 8 2008
	Deposit a magnet, in a white plastic case, at the base of the stainless steel post.
80.00	The cor. of secs. 5, 6, 7 and 8.

**Survey of the Subdivisional Lines,
T. 23 N., R. 25 E., Gila and Salt River Meridian, Arizona**

CHAINS									
	<p>Land, rugged. Soil, sandy clay. Timber, scattered piñon and juniper; undergrowth, greasewood and native grasses.</p> <hr/> <p>West, bet. secs. 6 and 7.</p> <p>Over rugged to nearly level land.</p>								
37.70	Trail road, bears S. 10° E. and N. 10° W.								
40.00	<p>Point for the 1/4 sec. cor. of secs. 6 and 7.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center;"> <p>T 23 N R 25 E S 6 1/4 ——— S 7</p> <p>2008</p> </div> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p>								
79.60	<p>Point for the closing cor. of secs. 6 and 7, at intersection with the Sixth Guide Meridian East (east boundary), T. 23 N., R. 24 E.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center;"> <table style="border-collapse: collapse; margin: auto;"> <tr> <td style="border-right: 1px solid black; padding: 0 5px;">T 23 N</td> <td style="padding: 0 5px;">T 23 N</td> </tr> <tr> <td style="border-right: 1px solid black; padding: 0 5px;">R 24 E</td> <td style="padding: 0 5px;">R 25 E</td> </tr> <tr> <td style="border-right: 1px solid black; padding: 0 5px;">S 1</td> <td style="padding: 0 5px;">S 6 ————— S 7</td> </tr> <tr> <td></td> <td style="text-align: right; padding: 0 5px;">CC</td> </tr> </table> <p>2008</p> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p> <p>From this cor. point, the cor. of secs. 1 and 12 only, T. 23 N., R. 24 E., bears South, 5.99 chs. dist., hereinbefore described.</p> <p>From this same cor. point, the 1/4 sec. cor. of sec. 1 only, T. 23 N., R. 24 E., bears North, 34.01 chs. dist., hereinbefore described.</p> </div>	T 23 N	T 23 N	R 24 E	R 25 E	S 1	S 6 ————— S 7		CC
T 23 N	T 23 N								
R 24 E	R 25 E								
S 1	S 6 ————— S 7								
	CC								

**Survey of the Subdivisional Lines,
T. 23 N., R. 25 E., Gila and Salt River Meridian, Arizona**

CHAINS

Land, rugged to nearly level.
Soil, sandy clay.
Timber, scattered piñon and juniper; undergrowth, greasewood and native grasses.

Point for the 1/4 sec. cor. of sec. 7 only, T. 23 N., R. 25 E., at midpoint on the W. bdy. of sec. 7.

Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.

T 23 N	
R 24 E	R 25 E
	1/4 S 7

2008

Deposit a magnet, in a white plastic case, at the base of the stainless steel post.

From this cor. point, the 1/4 sec. cor. of sec. 12 only, T. 23 N., R. 24 E., bears South, 5.99 chs. dist., hereinbefore described.

From this same cor. point, the cor. of secs. 1 and 12 only, T. 23 N., R. 24 E., bears North, 34.01 chs. dist., hereinbefore described.

Point for the 1/4 sec. cor. of sec. 6 only, T. 23 N., R. 25 E., at 40.00 chs. dist. in northing from the closing cor. of secs. 6 and 7, on the W. bdy. of sec. 6.

Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.

T 23 N	
R 24 E	R 25 E
	1/4 S 6

2008

Deposit a magnet, in a white plastic case, at the base of the stainless steel post.

From this cor. point, the 1/4 sec. cor. of sec. 1 only, T. 23 N., R. 24 E., bears South, 5.99 chs. dist., hereinbefore described.

**Survey of the Subdivisional Lines,
T. 23 N., R. 25 E., Gila and Salt River Meridian, Arizona**

CHAINS	
	<p>From this same cor. point, the cor. of Tps. 23 and 24 N., R. 24 E., bears North, 34.01 chs. dist., hereinbefore described.</p> <hr/> <p>From the cor. of secs, 5, 6, 7 and 8.</p> <p>N.0°03' W., bet. secs. 5 and 6.</p> <p>Over nearly level land.</p>
40.00	<p>Point for the 1/4 sec. cor. of secs. 5 and 6.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T 23 N R 25 E 1/4 S 6 S 5 2008</p>
79.97	<p>The cor. of secs. 5, 6, 31 and 32, on the N. bdy. of the Tp., hereinbefore described.</p> <p>Land, nearly level. Soil, sandy clay. Timber, scattered piñon and juniper; undergrowth, greasewood and native grasses.</p> <hr/>

Tps. 22 and 23 N., Rs. 24 and 25 E., Gila and Salt River Meridian, Arizona

CHAINS

GENERAL DESCRIPTION

The area surveyed is within the Navajo Indian Reservation, approximately 8 miles southwest of Klagetoh, Arizona. The terrain is nearly level to rugged. Sabito Wash is the main wash draining southwesterly.

The elevation varies from 6000 to 6500 feet above sea level. The soil is sandy clay and rocky. The timber consist of piñon and juniper scattered through out the township. Undergrowth principally consists of sagebrush, rabbit brush, greasewood, scrub oak and native grasses.

Principal access to the township is provided by Apache County Road C323, which enters the township in section 24 and extends northerly and exits in section 1.

The mean magnetic declination of $10\ 3/4^{\circ}$ E. was derived from the United States Geological Survey computer program GEOMAG, utilizing the World Magnetic Model for Epoch 2005 for the dates of this survey.

CERTIFICATE OF SURVEY

I, Alvina A. Begaye, Cadastral Surveyor, HEREBY CERTIFY upon honor, that in pursuance of special instructions bearing date of the 31st day of January, 2008, I have surveyed the Sixth Guide Meridian East (east boundary), T. 23 N., R. 24 E., dependently resurveyed the north boundary, T. 22 N., R. 25 E. and surveyed the north boundary, a sectional correction line and the subdivisional lines, T. 23 N., R. 25 E., of the Gila and Salt River Meridian, in the State of Arizona, which are represented in the foregoing field notes as having been executed by me and under my direction. Said survey has been made in strict conformity with said special instructions, the Manual of Instructions for the Survey of the Public Lands of the United States, 1973 and in specific manner described in the foregoing field notes.

11/19/2008

(Date)

Alvina A. Begaye

(Cadastral Surveyor)

CERTIFICATE OF APPROVAL

BUREAU OF LAND MANAGEMENT
Phoenix, Arizona

The foregoing field notes of the survey of the Sixth Guide Meridian East (east boundary), T. 23 N., R. 24 E., the dependent resurvey of the north boundary, T. 22 N., R. 25 E. and the survey of the north boundary, a sectional correction line and the subdivisional lines, T. 23 N., R. 25 E., Gila and Salt River Meridian, in the State of Arizona, executed by Alvina A. Begaye, Cadastral Surveyor, having been critically examined and found correct, are hereby approved.

01/29/2009

(Date)

Stephen K. Hansen

(Chief Cadastral Surveyor of Arizona)

~~CERTIFICATE OF TRANSCRIPT~~

~~I CERTIFY That the foregoing transcript of the field notes of the above described surveys in Tps. 22 and 23 N., Rs. 24 and 25 E., Gila and Salt River Meridian, Arizona, is a true copy of the original field notes.~~

~~(Date)~~

~~(Chief Cadastral Surveyor of Arizona)~~