

ORIGINAL

**UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT**

FIELD NOTES
OF THE
DEPENDENT RESURVEY OF
THE SEVENTH GUIDE MERIDIAN EAST (EAST BOUNDARY)
THE WEST AND NORTH BOUNDARIES
AND
THE SURVEY OF
THE SUBDIVISIONAL LINES
THE SUBDIVISION OF CERTAIN SECTIONS
TRACTS 37 AND 38
AND INFORMATIVE TRAVERSES
TOWNSHIP 41 NORTH, RANGE 28 EAST,
OF THE GILA AND SALT RIVER MERIDIAN,
IN THE STATE OF ARIZONA.

EXECUTED BY

Craig S. Dukart, Cadastral Surveyor

Under Special Instructions dated May 1, 2008, approved May 1, 2008, and Supplemental Special Instructions dated June 3, 2008, which provided for the surveys included under Group No. 1045, and assignment instructions dated May 1, 2008.

Survey commenced May 15, 2008

Survey completed July 15, 2008

INDEX DIAGRAM

TOWNSHIP 41 NORTH RANGE 28 EAST
 GILA AND SALT RIVER MERIDIAN, ARIZONA

14	19 6 69	18 5 57	17 4 47	16 3 37	16 2 28	15 1 9
13	68 7 66	67 8 55	56 9 45	46 10 35	36 11 26	27 12 8
12	65 18 64	65 17 53	54 16 43	44 15 33	34 14 24	25 13 7
11	63 19 62	62 20 51	52 21 41	42 22 31	32 23 22	24 24 6
11	61 30 59	60 29 49	50 28 40	41 27 30	31 26 21	22 25 5
9	59 31 57	58 32 48	49 33 38	39 34 28	29 35 20	21 36 4

Subdivision of Secs. 5,8,9,13,14,15,16,17,18 & 24 .. Pages 69-80
 Survey of Tracts 37 & 38 Pages 80-87
 Informative Traverses Pages 87-92

T. 41 N., R. 28 E., Gila and Salt River Meridian, Arizona

CHAINS

The following field notes describe the dependent resurvey of the Seventh Guide Meridian East (east boundary), the west and north boundaries, and the survey of the subdivisional lines, the subdivision of certain sections, tracts 37 and 38, and informative traverses, Township 41 North, Range 28 East, Gila and Salt River Meridian, Arizona.

The history of surveys pertaining to this survey is as follows:

Mineral Survey No. 3861, was surveyed by Allsion L. Kroeger, Mineral Surveyor, in 1922, and was cancelled on April 12, 2006.

The Tenth Standard Parallel North along the south boundary, the west and north boundaries of Township 41 North, Range 28 East, Gila and Salt River Meridian, were surveyed by Horace G. Parker, Cartographer Cadastral, in 1953.

The Tenth Standard Parallel North along the south boundary, the west and north boundaries of Township 41 North, Range 29 East, Gila and Salt River Meridian, were surveyed by Horace G. Parker, Cartographer Cadastral, in 1953.

The Tenth Standard Parallel North along the south boundary, Township 41 North, Range 28 East, and the south boundary, the Seventh Guide Meridian East (east boundary) and subdivision lines, T. 40 N., R. 28 E., Gila and Salt River Meridian, were surveyed by Leonard R. Sandoval, Cadastral Surveyor, in 2006.

The survey was executed in accordance with the specifications as set forth in the Manual of Instructions for the Survey of the Public Lands of the United States, 1973, and the Special Instructions dated May 1, 2008, and Supplemental Special Instructions dated June 3, 2008, for Group No. 1045, Arizona.

The true meridian direction and length of all lines were determined by real time kinematic global positioning system observations using Trimble Navigation 5800 model receivers.

Preliminary to the resurvey, the lines of the prior surveys were retraced and search was made for all corners and other calls of record. Identified corners were remonumented in their original positions. Lost corners were reestablished and remonumented at proportionate positions based on the official record. The retracement data were thoroughly verified and only the true line field notes are given herein.

T. 41 N., R. 28 E., Gila and Salt River Meridian, Arizona

CHAINS

Geodetic control was derived from Global Positioning System (GPS) static observations post processed by National Geodetic Survey, Online Positioning User Service (OPUS), utilizing Continuously Operating Reference Stations (CORS) FST5 FLAGSTAFF 5 CORS ARP, NMGR GRANTS NMDOT CORS ARP, AZCN AZTEC CORS ARP, P011 SPIDERROCKAZ2005 CORS ARP and P028 CHACOCNHP_NM2005 CORS ARP. The NAD 83 (CORS96)(EPOCH:2002), geographic position of the southeast corner of the township, is as follows:

Latitude: 36°54'31.53" N. Longitude: 109°16'58.50" W.

The mean magnetic declination is 11° E.

**Dependent Resurvey of the Seventh Guide Mer. East (E. Bdy.),
T. 41 N., R. 28 E., Gila and Salt River Meridian, Arizona**

Restoring the survey executed by
Horace G. Parker, in 1953

Beginning at the stan. cor. of Tps. 41 N., Rs. 28 and 29 E., monumented with a stainless steel post, 2 1/2 ins. diam., firmly set, projecting 4 ins. above ground, with brass cap mkd. SC T41N R28E R29E S36 S31 2006, from which the 2006 bearing object and survey tie

A metal cover for water meter, 9 ins. diam., bears N. 29° W., 1.32 chs. dist., set on concrete slab, 2 ft. square, firmly set flush with the surface of the ground, with top mkd. WATER, with 3 blue steel fence posts nearby.

From this cor. point, an open-end iron pipe, 1 in. diam., bears S. 89°36' W., 2.80 chs. dist., firmly set, projecting 6 ins. above the ground, with no marks.

A steel "T-Post" fence post is set nearby stainless steel post.

N. 0°02' E., bet. secs. 31 and 36.

Over nearly level terrain.

3.80 Power line, 2 wire, bears E. and W.

40.00 The 1/4 sec. cor. of secs. 31 and 36, monumented with an iron post, 2 1/2 ins. diam., firmly set, projecting 1 in. above the ground, with brass cap mkd. 1/4 S36 S31 1953, with no evidence of the orig. mound of stone to the W.

Remark the brass cap to read

Dependent Resurvey of the Seventh Guide Mer. East (E. Bdy.),
T. 41 N., R. 28 E., Gila and Salt River Meridian, Arizona

CHAINS	
	<p style="text-align: center;">T 41 N R 28 E 1/4 R 29 E</p> <p style="text-align: center;">S 36 S 31</p> <p style="text-align: center;">2008 1953</p> <p>This cor. falls 17 lks. east of a trail road, 8 ft. wide, bears N. 5° E. and S. 5° W.</p> <p>This cor. falls 44 lks. west of a drainage, 4 ft. wide, drains N.</p> <hr style="width: 30%; margin: 10px auto;"/> <p>North, beginning new measurement.</p> <p>Over nearly level terrain.</p> <p>4.40 Dirt road, 10 ft. wide, bears N. 35° E. and S. 35° W.</p> <p>40.015 The cor. of secs. 25, 30, 31 and 36, monumented with an iron post, 2 1/2 ins. diam., firmly set, projecting 4 ins. above the ground, with brass cap mkd. T41N R28E R29E S25 S30 S36 S31 1953, with a mound of stone, 2 ft. base, 1 ft. high, W. of cor.</p> <p>Add the marks 2008 to the brass cap.</p> <hr style="width: 60%; margin: 10px auto;"/> <p>North, bet. secs. 25 and 30.</p> <p>Over nearly level terrain.</p> <p>40.015 The 1/4 sec. cor. of secs. 25 and 30, monumented with an iron post, 2 1/2 ins. diam., firmly set, projecting 7 ins. above the ground, encircled by a rock collar, with brass cap mkd. 1/4 S25 S30 1953, with no evidence of the orig. mound of stone to the W.</p> <p>Remark the brass cap to read</p> <p style="text-align: center;">T 41 N R 28 E 1/4 R 29 E</p> <p style="text-align: center;">S 25 S 30</p> <p style="text-align: center;">1953 2008</p> <hr style="width: 30%; margin: 10px auto;"/> <p>North, beginning new measurement.</p>

Dependent Resurvey of the Seventh Guide Mer. East (E. Bdy.),
T. 41 N., R. 28 E., Gila and Salt River Meridian, Arizona

CHAINS	
	Over nearly level terrain.
40.02	<p>The cor. of secs. 19, 24, 25 and 30, monumented with an iron post, 2 1/2 ins. diam., firmly set, projecting 5 ins. above the ground, with brass cap mkd. T41N R28E R29E S24 S19 S25 S30 1953, with remnants of a mound of stone, 2 1/2 ft. base, 1/2 ft. high, W. of the cor.</p> <p>Add the marks 2008 to the brass cap.</p> <hr/> <p>N. 0°01' W., bet. secs. 19 and 24.</p> <p>Over nearly level terrain.</p>
23.10	Dirt road, 10 ft. wide, bears N. 30° E. and S. 30° W.
30.00	High voltage transmission line, 5 wire, bears S. 77° E. and N. 77° W.
40.015	<p>The 1/4 sec. cor. of secs. 19 and 24, monumented with an iron post, 2 1/2 ins. diam., firmly set, projecting 10 ins. above the ground, with brass cap mkd. 1/4 S24 S19 1953, with the orig. mound of stone, 2 ft. base, 1/2 ft. high, to the W. of the cor.</p> <p>Remark the brass cap to read</p> <div style="text-align: center; margin: 10px 0;"> <p>T 41 N</p> <p>R 28 E 1/4 R 29 E</p> <p style="margin-left: 100px;"> </p> <p>S 24 S 19</p> <p style="margin-left: 100px;">2008</p> <p style="margin-left: 100px;">1953</p> </div> <p>Cor. falls 12 lks. E. of a trail road, 8 ft. wide, bears N. and S.</p> <hr/> <p>N. 0°01' W., beginning new measurement.</p> <p>Over nearly level terrain.</p>
2.25	Barbed wire fence, 3 strand, bears S. 70° E. and N. 70° W.
3.10	Barbed wire fence, 3 strand, bears N. 30° E. and S. 30° W.
28.60	South right-of-way fence, barbed wire, 5 strand, bears S. 69° E. and N. 69° W.
30.25	Interstate Highway No. 160, asphalt surfaced, 30 ft. wide, bears S. 69° E. and N. 69° W.

Dependent Resurvey of the Seventh Guide Mer. East (E. Bdy.),
T. 41 N., R. 28 E., Gila and Salt River Meridian, Arizona

CHAINS									
33.50	North right-of-way fence, barbed wire, 5 strand, bears S. 69° E. and N. 69° W.								
40.015	<p>The point accepted for the cor. of secs. 13, 18, 19 and 24, occupied with an iron rebar, 5/8 in. diam., firmly set, projecting 4 ins. above the ground, in a mound of stone, 2 ft. base, 1/2 ft. high, with alum. cap mkd. BALLEW & ASSOC 13 18 24 19. This position is accepted as the best available evidence of the orig. cor. position.</p> <p>At the corner point</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with brass cap mkd.</p> <table style="margin-left: auto; margin-right: auto;"> <tr> <td colspan="2" style="text-align: center;">T 41 N</td> </tr> <tr> <td style="text-align: center;">R 28 E</td> <td style="text-align: center;">R 29 E</td> </tr> <tr> <td style="text-align: center;">S 13</td> <td style="text-align: center;">S 18</td> </tr> <tr> <td style="text-align: center;">S 24</td> <td style="text-align: center;">S 19</td> </tr> </table> <p style="text-align: center;">2008</p> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p> <p>Deposit the iron rebar, 5/8 in. diam., with alum. cap, inside the stainless steel post.</p> <p>Raise a mound of stone, 4 ft. base, 1 1/2 ft. high, W. of cor.</p> <p>Set a steel "T-Post" fence post near cor.</p> <hr/> <p>N. 0°01' W., bet. secs. 13 and 18.</p> <p>Over gently rolling terrain.</p>	T 41 N		R 28 E	R 29 E	S 13	S 18	S 24	S 19
T 41 N									
R 28 E	R 29 E								
S 13	S 18								
S 24	S 19								
0.60	Dirt road, 10 ft. wide, bears S. 50° E. and N. 50° W.								
20.20	Underground petroleum pipeline, bears S. 70° E. and N. 70° W.								
22.65	Dirt road, 8 ft. wide, bears N. 85° E. and S. 85° W.								
40.01	<p>The 1/4 sec. cor. of secs. 13 and 18, monumented with an iron post, 2 1/2 ins. diam., firmly set, flush with the ground, with brass cap mkd. 1/4 S13 S18 1953, encircled with stones.</p> <p>Remark the brass cap to read</p>								

Dependent Resurvey of the Seventh Guide Mer. East (E. Bdy.),
T. 41 N., R. 28 E., Gila and Salt River Meridian, Arizona

CHAINS	
	<p style="text-align: center;">T 41 N R 28 E 1/4 R 29 E S 13 S 18 2008 1953</p> <hr/>
	<p>North, beginning new measurement.</p> <p>Over nearly level terrain.</p>
40.03	<p>The cor. of secs. 7, 12, 13 and 18, monumented with an iron post, 2 1/2 ins. diam., firmly set, projecting 8 ins. above the ground, with brass cap mkd. T41N R28E R29E S12 S7 S13 S18 1953, encircled with stones.</p> <p>Add the marks 2008 to the brass cap.</p> <hr/>
	<p>N. 0°01' W., bet. secs. 7 and 12.</p> <p>Over gently rolling terrain.</p>
39.995	<p>The 1/4 sec. cor. of secs. 7 and 12, monumented with an iron post, 2 1/2 ins. diam., firmly set, 5 ins. below the ground, with brass cap mkd. 1/4 S12 S7 1953.</p> <p>Remark the brass cap to read</p>
	<p style="text-align: center;">T 41 N R 28 E 1/4 R 29 E S 12 S 7 2008 1953</p> <hr/> <p>Drive a "T-post" fence post near the cor.</p> <hr/>
	<p>N. 0°01' W., beginning new measurement.</p> <p>Over gently rolling terrain.</p>
17.95	<p>Dirt road, 15 ft. wide, bears N. 85° E. and S. 85° W.</p>
40.02	<p>The cor. of secs. 1, 6, 7 and 12, monumented with an iron post, 2 1/2 ins. diam., firmly set, projecting 15 ins. above the ground, in a mound of stone, 5 ft. base, 1 1/2 ft. high, with brass cap mkd. T41N R28E R29E S1 S6 S12 S7 1953.</p>

**Dependent Resurvey of the Seventh Guide Mer. East (E. Bdy.),
T. 41 N., R. 28 E., Gila and Salt River Meridian, Arizona**

CHAINS	
	<p>Add the marks 2008 to the brass cap.</p> <p>Rebuild the supporting mound of stone, 5 ft. base, to cap.</p> <hr/> <p>N. 0°01' W., bet. secs. 1 and 6.</p> <p>Over gently rolling terrain.</p> <p>40.02 The 1/4 sec. cor. of secs. 1 and 6, monumented with an iron post, 2 1/2 ins. diam., firmly set, 5 ins. below the ground, with brass cap mkd. 1/4 S1 S6 1953.</p> <p>Remark the brass cap to read</p> <div style="text-align: center;"> <p>T 41 N</p> <p>R 28 E 1/4 R 29 E</p> <p>S 1 S 6</p> <p>2008</p> <p>1953</p> </div> <p>Drive a "T-post" fence post near the cor.</p> <hr/> <p>N. 0°01' W., beginning new measurement.</p> <p>Over gently rolling terrain.</p>
40.015	<p>The cor. of Tps. 41 and 42 N., Rs. 28 and 29 E., monumented with an iron post, 2 1/2 ins. diam., firmly set, flush with the ground, with brass cap mkd. T42N R28E R29E S36 S31 S1 S6 T41N 1953.</p> <p>Add the marks 2008 to the brass cap.</p> <p>Drive a "T-post" fence post near the cor.</p> <hr/> <p style="text-align: center;">Dependent Resurvey of the West Boundary, T. 41 N., R. 28 E., Gila and Salt River Meridian, Arizona</p> <hr/> <p style="text-align: center;">Restoring the survey executed by Horace G. Parker, in 1953</p> <hr/> <p>From the stan. cor. of Tps. 41 N., Rs. 27 and 28 E., monumented with a stainless steel post, 2 1/2 ins. diam., firmly set, projecting 12 ins. above ground, in a mound of stone, 4 ft. base, to brass cap mkd. SC T41N R27E R28E S36 S31 2006 2000, from which the orig. 1953 bearing trees</p>

Dependent Resurvey of the West Boundary,
T. 41 N., R. 28 E., Gila and Salt River Meridian, Arizona

CHAINS							
	<p>A forked piñon pine, 12 ins. diam. at base, bears N. 69° E., 1.05 chs. dist., with scribe marks T41N R28E S31 SC BT visible on partially open blaze.</p>						
	<p>A dead forked piñon pine, 12 ins. diam. at base, bears N. 38° W., 27 1/2 lks. dist., with scribe marks T41N R27E S36 SC BT visible on partially open blaze.</p>						
	<p>North, bet. secs. 31 and 36.</p>						
	<p>Across top of Toh Atin Mesa.</p>						
2.70	<p>North edge of Toh Atin Mesa, bears N. 55° E. and S. 75° W.; descend steep N. slope and continue over rugged terrain.</p>						
40.00	<p>The 1/4 sec. cor. of secs. 31 and 36, monumented with an iron post, 2 1/2 ins. diam., firmly set, projecting 5 ins. above the ground, with brass cap mkd. 1/4 S36 S31 1953, with the orig. mound of stone, 2 ft. base, 1/2 ft. high, to the NE. of the cor.</p> <p>Remark the brass cap to read</p> <div style="text-align: center;"> <p>T 41 N R 27 E 1/4 R 28 E</p> <table style="margin: auto;"> <tr> <td style="border-right: 1px solid black; padding: 0 5px;">S 36</td> <td style="padding: 0 5px;">S 31</td> </tr> <tr> <td colspan="2" style="text-align: center; padding: 5px 0;">2008</td> </tr> <tr> <td colspan="2" style="text-align: center; padding: 5px 0;">1953</td> </tr> </table> <hr style="width: 30%; margin: 10px auto;"/> </div>	S 36	S 31	2008		1953	
S 36	S 31						
2008							
1953							
	<p>N. 0°01' E., beginning new measurement.</p>						
	<p>Over rugged terrain.</p>						
40.005	<p>Point for the cor. of secs. 25, 30, 31 and 36, at proportionate dist.; the orig. iron post is laying loose, out of position.</p> <p>Set the orig. iron post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, underpinned with a steel "T-Post" fence post, 4 ft. long, with brass cap mkd.</p> <div style="text-align: center;"> <p>T 41 N</p> <table style="margin: auto;"> <tr> <td style="border-right: 1px solid black; padding: 0 5px;">R 27 E</td> <td style="padding: 0 5px;">R 28 E</td> </tr> <tr> <td style="border-right: 1px solid black; padding: 0 5px;">S 25</td> <td style="padding: 0 5px;">S 30</td> </tr> <tr> <td style="border-right: 1px solid black; padding: 0 5px;">S 36</td> <td style="padding: 0 5px;">S 31</td> </tr> </table> <p style="text-align: center; padding: 5px 0;">2008</p> <p style="text-align: center; padding: 5px 0;">1953</p> </div>	R 27 E	R 28 E	S 25	S 30	S 36	S 31
R 27 E	R 28 E						
S 25	S 30						
S 36	S 31						
	<p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p>						

**Dependent Resurvey of the West Boundary,
T. 41 N., R. 28 E., Gila and Salt River Meridian, Arizona**

CHAINS	
40.005	<p>Set a steel "T-Post" fence post near cor. Cor. is located in deep blow sand.</p> <hr/> <p>N. 0°01' E., bet. secs. 25 and 30. Over gently rolling terrain.</p> <p>The 1/4 sec. cor. of secs. 25 and 30, monumented with an iron post, 2 1/2 ins. diam., firmly set, projecting 2 ins. above the ground, with brass cap mkd. 1/4 S25 S30 1953, with remnants of the orig. mound of stone, 2 ft. base, flush with the sand, W. of cor.</p> <p>Remark the brass cap to read</p> <div style="text-align: center;"> <p>T 41 N R 27 E 1/4 R 28 E S 25 S 30 2008 1953</p> </div> <p>Rebuild mound of stone, 2 ft. base, 1 ft. high.</p> <hr/> <p>North, beginning new measurement. Over gently rolling terrain.</p>
40.045	<p>Point for the cor. of secs. 19, 24, 25 and 30, at proportionate dist.; there is no remaining evidence of the orig. cor.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 25 ins. in the ground, underpinned with a steel "T-Post" fence post, 4 ft. long, with brass cap mkd.</p> <div style="text-align: center;"> <p>T 41 N R 27 E R 28 E S 24 S 19 S 25 S 30 2008</p> </div> <p>Set a steel "T-Post" fence post near cor.</p> <hr/> <p>North, bet. secs. 19 and 24. Over nearly level terrain.</p>

**Dependent Resurvey of the West Boundary,
T. 41 N., R. 28 E., Gila and Salt River Meridian, Arizona**

CHAINS	
40.045	<p>The 1/4 sec. cor. of secs. 19 and 24, monumented with an iron post, 2 1/2 ins. diam., firmly set, projecting 12 ins. above the ground, in scattered remains of mound of stone, with brass cap mkd. 1/4 S24 S19 1953.</p> <p>Remark the brass cap to read</p> <div style="text-align: center;"> <p>T 41 N R 27 E 1/4 R 28 E</p> <p>S 24 S 19</p> <p>2008 1953</p> </div> <p>Rebuild rock collar, 3 1/2 ft. base.</p> <hr style="width: 30%; margin: auto;"/> <p>N. 0°02' E., beginning new measurement.</p> <p>Over nearly level terrain.</p>
17.80	Power line, 2 wire, bears N. 50° E. and S. 50° W.
39.955	<p>The cor. of secs. 13, 18, 19 and 24, monumented with an iron post, 2 1/2 ins. diam., firmly set, projecting 2 ins. above the ground, with brass cap mkd. T41N R27E R28E S13 S18 S24 S19 1953.</p> <p>Add the marks 2008 to the brass cap.</p> <p>Set a steel "T-Post" fence post near cor.</p> <hr style="width: 60%; margin: auto;"/> <p>North, bet. secs. 13 and 18.</p> <p>Over nearly level terrain.</p>
21.05	High voltage transmission line, 5 wire, bears S. 86° E. and N. 86° W.
40.02	<p>The 1/4 sec. cor. of secs. 13 and 18, monumented with an iron post, 2 1/2 ins. diam., firmly set, projecting 5 ins. above the ground, with brass cap mkd. 1/4 S13 S18 1953.</p> <p>Remark the brass cap to read</p>

**Dependent Resurvey of the West Boundary,
T. 41 N., R. 28 E., Gila and Salt River Meridian, Arizona**

CHAINS	
	T 41 N R 27 E 1/4 R 28 E S 13 S 18 2008 1953
	Set a steel "T-Post" fence post near cor.

	North, beginning new measurement.
	Over nearly level terrain.
7.35	South right-of-way fence, barbed wire, 5 strand, bears S. 88° E. and N. 88° W.
8.85	Interstate Highway No. 160, asphalt surfaced, 30 ft. wide, bears S. 88° E. and N. 88° W.
11.90	North right-of-way fence, barbed wire, 5 strand, bears S. 88° E. and N. 88° W.
40.00	The cor. of secs. 7, 12, 13 and 18, monumented with a concrete filled iron post, 2 ins. diam., firmly set, projecting 7 ins. above the ground, with brass cap mkd. R41N 2007 T27E T28E S12 S7 S13 S18 LS15083. This position is accepted as a careful and faithful perpetuation of the orig. cor. position. The Arizona Land Survey Corner Record(2 pages) for this corner was recorded at the Apache County Recorders Office on July 6th, 2007, as 2007-006446.

	North, bet. secs. 7 and 12.
	Over nearly level terrain.
40.005	The 1/4 sec. cor. of secs. 7 and 12, monumented with an iron post, 2 1/2 ins. diam., firmly set, projecting 8 ins. above the ground, in scattered remains of mound of stone, with brass cap mkd. 1/4 S12 S7 1953.
	Remark the brass cap to read
	T 41 N R 27 E 1/4 R 28 E S 12 S 7 2008 1953

Dependent Resurvey of the West Boundary,
T. 41 N., R. 28 E., Gila and Salt River Meridian, Arizona

CHAINS									
	<p>Set a steel "T-Post" fence post near cor.</p> <hr/> <p>North, beginning new measurement.</p> <p>Over nearly level terrain.</p>								
39.85	Dirt road, 10 ft. wide, bears N. 60° E. and S. 60° W.								
40.005	<p>Point for the cor. of secs. 1, 6, 7 and 12, at proportionate dist.; the orig. iron post is laying loose, out of position.</p> <p>Set the orig. iron post, 30 ins. long, 2 1/2 ins. diam., 27 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center;"> <table border="1"> <tr><td colspan="2">T 41 N</td></tr> <tr><td>R 27 E</td><td>R 28 E</td></tr> <tr><td>S 1</td><td>S 6</td></tr> <tr><td>S 12</td><td>S 7</td></tr> </table> <p>2008 1953</p> </div> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p> <p>Set a steel "T-Post" fence post near cor.</p> <hr/> <p>North, bet. secs. 1 and 6.</p> <p>Over nearly level terrain.</p>	T 41 N		R 27 E	R 28 E	S 1	S 6	S 12	S 7
T 41 N									
R 27 E	R 28 E								
S 1	S 6								
S 12	S 7								
2.95	Power line, 3 wire, bears N. 75° E. and S. 75° W.								
40.005	<p>The 1/4 sec. cor. of secs. 1 and 6, monumented with an iron post, 2 1/2 ins. diam., firmly set, projecting 7 ins. above the ground, with brass cap mkd. 1/4 S1 S6 1953.</p> <p>Remark the brass cap to read</p> <div style="text-align: center;"> <table border="1"> <tr><td colspan="2">T 41 N</td></tr> <tr><td>R 27 E</td><td>1/4 R 28 E</td></tr> <tr><td>S 1</td><td>S 6</td></tr> <tr><td colspan="2">2008 1953</td></tr> </table> </div> <p>Set a steel "T-Post" fence post near cor.</p> <hr/> <p>N. 0°02' W., beginning new measurement.</p>	T 41 N		R 27 E	1/4 R 28 E	S 1	S 6	2008 1953	
T 41 N									
R 27 E	1/4 R 28 E								
S 1	S 6								
2008 1953									

**Dependent Resurvey of the West Boundary,
T. 41 N., R. 28 E., Gila and Salt River Meridian, Arizona**

CHAINS	
	Over nearly level terrain.
10.85	Power line, 5 wire, bears S. 15° E. and N. 15° W., with a dirt road, 8 ft. wide, running parallel, west of it.
40.00	The cor. of Tps. 41 and 42 N., Rs. 27 and 28 E., monumented with an iron post, 2 1/2 ins. diam., firmly set, 12 ins. below the ground, with brass cap mkd. T42N R27E R28E S36 S31 S1 S6 T41N 1953. Add the marks 2008 to the brass cap.
<hr/> <p>Dependent Resurvey of the North Boundary, T. 41 N., R. 28 E., Gila and Salt River Meridian, Arizona</p> <hr/>	
<p>Restoring the survey executed by Horace G. Parker, in 1953</p> <hr/>	
	From the cor. of Tps. 41 and 42 N., Rs. 28 and 29 E., hereinbefore described. N. 89°57' W., bet. secs. 1 and 36. Over gently rolling terrain.
39.975	The 1/4 sec. cor. of secs. 1 and 36, monumented with an iron post, 2 1/2 ins. diam., firmly set, projecting 14 ins. above the ground, with brass cap mkd. 1/4 S36 S1 1953, with broken glass buried alongside. Reference the iron post and reset it 25 ins. in the ground, and remark the brass cap to read
	<p>T 42 N R 28 E S 36 1/4 ——— S 1 T 41 N</p> <p>2008 1953</p>
	Set a steel "T-Post" fence post near cor.
	<hr/>
	S. 89°57' W., beginning new measurement. Over gently rolling terrain.

**Dependent Resurvey of the North Boundary,
T. 41 N., R. 28 E., Gila and Salt River Meridian, Arizona**

CHAINS	
40.015	<p>The cor. of secs. 1, 2, 35 and 36, monumented with an iron post, 2 1/2 ins. diam., firmly set, projecting 18 ins. above the ground, in a mound of stone, 2 1/2 ft. base, 1 ft. high, with brass cap mkd. T42N R28E S35 S36 S2 S1 T41N 1953.</p> <p>Add the marks 2008 to the brass cap.</p> <hr style="width: 80%; margin: 10px auto;"/> <p>West, bet. secs. 2 and 35.</p> <p>Over gently rolling terrain.</p>
40.035	<p>The 1/4 sec. cor. of secs. 2 and 35, monumented with an iron post, 2 1/2 ins. diam., firmly set, projecting 8 ins. above the ground, with brass cap mkd. 1/4 S35 S2 1953, with a small pile of stone to the N.</p> <p>Use the accessory mound of stone to build a mound of stone around the iron post, 2 ft. base, to brass cap, and remark the brass cap to read</p> <div style="text-align: center; margin: 10px 0;"> <p>T 42 N R 28 E</p> <p style="margin-left: 40px;">S 35</p> <p style="margin-left: 30px;">1/4 ———</p> <p style="margin-left: 40px;">S 2</p> <p style="margin-left: 40px;">T 41 N</p> <p style="margin-left: 40px;">2008</p> <p style="margin-left: 40px;">1953</p> </div> <hr style="width: 80%; margin: 10px auto;"/> <p>S. 89°59' W., beginning new measurement.</p> <p>Over gently rolling terrain.</p>
40.005	<p>The cor. of secs. 2, 3, 34 and 35, monumented with an iron post, 2 1/2 ins. diam., firmly set, projecting 8 ins. above the ground, in a mound of stone, 2 ft. base, to brass cap mkd. T42N R28E S34 S35 S3 S2 T41N 1953, with a small pile of stones to the W.</p> <p>Use the accessory mound of stone to build a mound of stone around the iron post, 2 ft. base, to brass cap, and add the marks 2008 to the brass cap.</p> <hr style="width: 80%; margin: 10px auto;"/> <p>West, bet. secs. 3 and 34.</p> <p>Over nearly level terrain.</p>
35.60	<p>Dirt road, 12 ft. wide, bears N. 30° E. and S. 30° W.</p>

**Dependent Resurvey of the North Boundary,
T. 41 N., R. 28 E., Gila and Salt River Meridian, Arizona**

CHAINS	
40.015	<p>The 1/4 sec. cor. of secs. 3 and 34, monumented with an iron post, 2 1/2 ins. diam., firmly set, projecting 4 ins. above the ground, with brass cap mkd. 1/4 S34 S3 1953, with the remnants of a mound of stone, 2 1/2 ft. base, 1/2 ft. high, to the W.</p> <p>Remark the brass cap to read</p> <div style="text-align: center;"> <p>T 42 N R 28 E S 34 1/4 ——— S 3 T 41 N</p> <p>2008 1953</p> <hr style="width: 30%; margin: 0 auto;"/> </div> <p>S. 89°55' W., beginning new measurement.</p> <p>Over nearly level terrain.</p>
39.985	<p>The cor. of secs. 3, 4, 33 and 34, monumented with an iron post, 2 1/2 ins. diam., firmly set, projecting 28 ins. above the ground, in a mound of stone, 4 ft. base, 19 ins. high, with brass cap mkd. T42N R28E S33 S34 S4 S3 T41N 1953.</p> <p>Rebuild the supporting mound of stone, 4 1/2 ft. base, to brass cap, and add the marks 2008 to the brass cap.</p> <p>Cor. falls in dry wash, 15 ft. wide, drains N. 45° E.</p> <hr style="width: 60%; margin: 10px auto;"/> <p>S. 89°58' W., bet. secs. 4 and 33.</p> <p>Over broken terrain; begin ascent of east side of Red Mesa.</p>
39.975	<p>The 1/4 sec. cor. of secs. 4 and 33, monumented with an iron post, 2 1/2 ins. diam., firmly set, projecting 23 ins. above the ground, in a mound of stone, 3 ft. base, 1 ft. high, with brass cap mkd. 1/4 S33 S4 1953.</p> <p>Rebuild the mound of stone, 3 ft. base, to brass cap, and remark the brass cap to read</p> <div style="text-align: center;"> <p>T 42 N R 28 E S 33 1/4 ——— S 4 T 41 N</p> <p>2008 1953</p> </div>

**Dependent Resurvey of the North Boundary,
T. 41 N., R. 28 E., Gila and Salt River Meridian, Arizona**

CHAINS	
	<p>Cor. falls on top of Red Mesa.</p> <hr style="width: 30%; margin: 10px auto;"/> <p>N. 89°54' W., beginning new measurement.</p> <p>Across the top of Red Mesa, transitioning into the descent of Red Mesa, then rolling terrain.</p>
39.985	<p>The cor. of secs. 4, 5, 32 and 33, monumented with an iron post, 2 1/2 ins. diam., firmly set, projecting 10 ins. above the ground, with brass cap mkd. T42N R28E S32 S33 S5 S4 T41N 1953.</p> <p>Add the marks 2008 to the brass cap.</p> <p>Set a steel "T-Post" fence post near cor.</p> <hr style="width: 30%; margin: 10px auto;"/>
	<p>S. 89°59' W., bet. secs. 5 and 32.</p> <p>Over gently rolling terrain.</p>
30.23	<p>East right-of-way fence, barbed wire, 5 strand, bears N. 4° E. and S. 4° W.</p>
31.75	<p>Navajo Route 35, asphalt surfaced, 38 ft. wide, bears N. 4° E. and S. 4° W.</p>
33.23	<p>West right-of-way fence, barbed wire, 5 strand, bears N. 4° E. and S. 4° W.</p>
39.985	<p>The 1/4 sec. cor. of secs. 5 and 32, monumented with an iron post, 2 1/2 ins. diam., firmly set, projecting 3 ins. above the ground, with brass cap mkd. 1/4 S32 S5 1953.</p> <p>Remark the brass cap to read</p> <div style="text-align: center; margin-left: 100px;"> <p>T 42 N R 28 E</p> <p style="margin-left: 40px;">S 32</p> <p style="margin-left: 40px;">1/4 ———</p> <p style="margin-left: 60px;">S 5</p> <p style="margin-left: 60px;">T 41 N</p> <p style="margin-left: 60px;">2008</p> <p style="margin-left: 60px;">1953</p> </div> <hr style="width: 30%; margin: 10px auto;"/>
	<p>West, beginning new measurement.</p> <p>Over gently rolling terrain.</p>
2.95	<p>Graded road, 20 ft. wide, bears N. 60° E. and S. 60° W.</p>

**Dependent Resurvey of the North Boundary,
T. 41 N., R. 28 E., Gila and Salt River Meridian, Arizona**

CHAINS											
15.45	Graded road, 20 ft. wide, bears S. 45° E. and N. 45° W.										
40.05	<p>Point for the cor. of secs. 5, 6, 31 and 32, at proportionate dist.; there is no remaining evidence of the orig. cor.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 25 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center;"> <table style="margin: auto;"> <tr><td>T 42 N</td><td>R 28 E</td></tr> <tr><td>S 31</td><td>S 32</td></tr> <tr><td>S 6</td><td>S 5</td></tr> <tr><td>T 41 N</td><td>R 28 E</td></tr> </table> <p>2008</p> </div> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p> <p>Raise a mound of stone, 2 1/2 ft. base, 1 ft. high, N. of cor.</p> <p>Set a steel "T-Post" fence post near cor.</p> <hr/> <p>West, bet. secs. 6 and 31.</p> <p>Over gently rolling terrain.</p>	T 42 N	R 28 E	S 31	S 32	S 6	S 5	T 41 N	R 28 E		
T 42 N	R 28 E										
S 31	S 32										
S 6	S 5										
T 41 N	R 28 E										
40.05	<p>Point for the 1/4 sec. cor. of secs. 6 and 31, at proportionate dist.; there is no remaining evidence of the orig. cor.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 25 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center;"> <table style="margin: auto;"> <tr><td>T 42 N</td><td>R 28 E</td></tr> <tr><td>S 31</td><td></td></tr> <tr><td>1/4</td><td>———</td></tr> <tr><td>S 6</td><td></td></tr> <tr><td>T 41 N</td><td>R 28 E</td></tr> </table> <p>2008</p> </div> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p>	T 42 N	R 28 E	S 31		1/4	———	S 6		T 41 N	R 28 E
T 42 N	R 28 E										
S 31											
1/4	———										
S 6											
T 41 N	R 28 E										
40.40	Underground petroleum pipe line, bears S. 50° E. and N. 50° W.										
68.05	Underground water line, bears N. and S.										

**Dependent Resurvey of the North Boundary,
T. 41 N., R. 28 E., Gila and Salt River Meridian, Arizona**

CHAINS	<p>79.52 The cor. of Tps. 41 and 42 N., Rs. 27 and 28 E., hereinbefore described.</p> <hr/> <p align="center">Survey of the Subdivisional Lines, T. 41 N., R. 28 E., Gila and Salt River Meridian, Arizona</p> <hr/> <p>From the stan. cor. of secs. 35 and 36, on the S. bdy. of the Tp., monumented with an iron post, 2 1/2 ins. diam., firmly set, projecting 26 ins. above the ground, in a mound of stone, 4 ft. base, to brass cap mkd. SC T41N R28E S35 S36 2006 1953.</p> <p>N. 0°01' W., bet. secs. 35 and 36.</p> <p>Over rolling terrain, transitioning to nearly level terrain.</p>
7.35	Dirt road, 20 ft. wide, bears E. and S. 80° W.
15.10	Power line, 2 wire, bears S. 70° E. and N. 70° W.
40.00	<p>Point for the 1/4 sec. cor. of secs. 35 and 36.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with brass cap mkd.</p> <p align="center">T 41 N R 28 E 1/4 S 35 S 36 2008</p> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p> <p>Set a steel "T-Post" fence post near cor.</p>
80.00	<p>Point for the cor. of secs. 25, 26, 35 and 36.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p align="center">T 41 N R 28 E S 26 S 25 S 35 S 36 2008</p> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p> <p>Set a steel "T-Post" fence post near cor.</p>

**Survey of the Subdivisional Lines,
T. 41 N., R. 28 E., Gila and Salt River Meridian, Arizona**

CHAINS	
	<p>Land, rolling to nearly level. Soil, fine sand. No timber; scattered native grasses.</p> <hr/> <p>From the cor. of secs. 25, 30, 31 and 36, on the E. bdy. of the Tp., hereinbefore described.</p> <p>West, bet. secs. 25 and 36.</p> <p>Over nearly level terrain.</p>
40.035	<p>Point for the 1/4 sec. cor. of secs. 25 and 36.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T 41 N R 28 E S 25 1/4 ——— S 36</p> <p style="text-align: center;">2008</p> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p> <p>Set a steel "T-Post" fence post near cor.</p>
80.07	<p>The cor. of secs. 25, 26, 35 and 36.</p> <p>Land, rolling to nearly level. Soil, fine sand. No timber; scattered native grasses.</p> <hr/> <p>N. 0°01' W., bet. secs. 25 and 26.</p> <p>Over nearly level terrain.</p>
40.00	<p>Point for the 1/4 sec. cor. of secs. 25 and 26.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 25 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T 41 N R 28 E 1/4 S 26 S 25</p> <p style="text-align: center;">2008</p> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p>

**Survey of the Subdivisional Lines,
T. 41 N., R. 28 E., Gila and Salt River Meridian, Arizona**

CHAINS									
80.00	<p>Set a steel "T-Post" fence post near cor.</p> <p>Point for the cor. of secs. 23, 24, 25 and 26.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center;"> <table style="margin: auto;"> <tr><td>T 41 N</td><td>R 28 E</td></tr> <tr><td>S 23</td><td>S 24</td></tr> <tr><td>S 26</td><td>S 25</td></tr> </table> <p>2008</p> </div> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p> <p>Land, rolling to nearly level. Soil, fine sand. No timber; scattered native grasses.</p> <hr/> <p>From the cor. of secs. 19, 24, 25 and 30, on the E. bdy. of the Tp., hereinbefore described.</p> <p>S. 89°59' W., bet. secs. 24 and 25.</p> <p>Over nearly level terrain.</p>	T 41 N	R 28 E	S 23	S 24	S 26	S 25		
T 41 N	R 28 E								
S 23	S 24								
S 26	S 25								
40.035	<p>Point for the 1/4 sec. cor. of secs. 24 and 25.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center;"> <table style="margin: auto;"> <tr><td>T 41 N</td><td>R 28 E</td></tr> <tr><td>S 24</td><td></td></tr> <tr><td>1/4</td><td>—</td></tr> <tr><td>S 25</td><td></td></tr> </table> <p>2008</p> </div> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p>	T 41 N	R 28 E	S 24		1/4	—	S 25	
T 41 N	R 28 E								
S 24									
1/4	—								
S 25									
80.07	<p>The cor. of secs. 23, 24, 25 and 26.</p> <p>Land, nearly level. Soil, sandstone and fine sand. No timber; scattered native grasses.</p> <hr/> <p>N. 0°01' W., bet. secs. 23 and 24.</p>								

**Survey of the Subdivisional Lines,
T. 41 N., R. 28 E., Gila and Salt River Meridian, Arizona**

CHAINS	
	Over nearly level terrain.
36.45	Dirt road, 15 ft. wide, bears N. 40° E. and S. 40° W.
40.00	Point for the 1/4 sec. cor. of secs. 23 and 24. Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with brass cap mkd. <div style="text-align: center;"> T 41 N R 28 E 1/4 S 23 S 24 2008 </div>
	Deposit a magnet, in a white plastic case, at the base of the stainless steel post. Set a steel "T-Post" fence post near cor. Cor. falls near northerly edge of an area of sand dunes, bears N. 45° E. and S. 45° W.
48.30	High voltage transmission line, 5 wire, bears S. 77° E. and N. 77° W.
80.00	Point for the cor. of secs. 13, 14, 23 and 24. Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with brass cap mkd. <div style="text-align: center;"> T 41 N R 28 E S 14 S 13 S 23 S 24 2008 </div>
	Deposit a magnet, in a white plastic case, at the base of the stainless steel post. Set a steel "T-Post" fence post near cor. From this cor. point, a cor. set by persons unknown, bears N. 70°47' E., 9 lks. dist., monumented with an open ended iron pipe, 2 ins. diam., firmly set, projecting 24 ins. above the ground, with marks T41N 14 13 23 24 R28E on its side. Land, rolling to nearly level. Soil, fine sand. No timber; scattered native grasses.

**Survey of the Subdivisional Lines,
T. 41 N., R. 28 E., Gila and Salt River Meridian, Arizona**

CHAINS	
	<p>From the cor. of secs. 13, 18, 19 and 24, on the E. bdy. of the Tp., hereinbefore described.</p> <p>S. 89°57' W., bet. secs. 13 and 24.</p> <p>Over gently rolling terrain.</p>
16.67	Northeast right-of-way fence, barbed wire, 5 strand, bears S. 69° E. and N. 69° W.
24.90	Interstate Highway No. 160, asphalt surfaced, 34 ft. wide, bears S. 69° E. and N. 69° W.
29.16	Southwest right-of-way fence, barbed wire, 2 strand, and pig wire, bears S. 69° E. and N. 69° W.
40.035	<p>Point for the 1/4 sec. cor. of secs. 13 and 24.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 27 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T 41 N R 28 E S 13 1/4 ——— S 24</p> <p style="text-align: center;">2008</p> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p> <p>Set a steel "T-Post" fence post near cor.</p> <p>From this cor. point, a cor. set by persons unknown, bears N. 65°35' E., 5 lks. dist., monumented with an open ended iron pipe, 2 1/2 ins. diam., firmly set, projecting 15 ins. above the ground, with marks 13 24 on its northerly side.</p>
42.05	Dirt road, 12 ft. wide, bears N. 45° E. and S. 45° W.
80.07	<p>The cor. of secs. 13, 14, 23 and 24.</p> <p>Land, nearly level. Soil, sandstone and fine sand. No timber; scattered native grasses.</p> <hr/> <p>N. 0°01' W., bet. secs. 13 and 14.</p> <p>Over gently rolling terrain.</p>
19.97	South right-of-way fence, barbed wire, 5 strand, bears S. 69° E. and N. 69° W.

**Survey of the Subdivisional Lines,
T. 41 N., R. 28 E., Gila and Salt River Meridian, Arizona**

CHAINS	
21.55	Interstate Highway No. 160, asphalt surfaced, 30 ft. wide, bears S. 69° E. and N. 69° W.
24.80	North right-of-way fence, barbed wire, 5 strand, bears S. 69° E. and N. 69° W.
40.00	Point for the 1/4 sec. cor. of secs. 13 and 14. Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 25 ins. in the ground, with brass cap mkd. <div style="text-align: center;"> T 41 N R 28 E 1/4 S 14 S 13 2008 </div> Deposit a magnet, in a white plastic case, at the base of the stainless steel post. Set a steel "T-Post" fence post near cor.
50.40	Underground petroleum pipe line, bears S. 70° E. and N. 70° W.
53.25	Dirt Road, 15 ft. wide, bears N. 35° E. and S. 35° W.
55.90	Power Line, 3 wire, bears N. 60° E. and S. 60° W.
80.00	Point for the cor. of secs. 11, 12, 13 and 14. Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd. <div style="text-align: center;"> T 41 N R 28 E S 11 S 12 S 14 S 13 2008 </div> Deposit a magnet, in a white plastic case, at the base of the stainless steel post. Set a steel "T-Post" fence post near cor. Land, rolling to nearly level. Soil, fine sand. No timber; scattered native grasses.
	<hr/> From the cor. of secs. 7, 12, 13 and 18, on the E. bdy. of the Tp., hereinbefore described.

**Survey of the Subdivisional Lines,
T. 41 N., R. 28 E., Gila and Salt River Meridian, Arizona**

CHAINS	
	<p>S. 89°56' W., bet. secs. 12 and 13.</p> <p>Over gently rolling terrain.</p>
40.035	<p>Point for the 1/4 sec. cor. of secs. 12 and 13.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 27 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T 41 N R 28 E S 12 1/4 ——— S 13</p> <p style="text-align: center;">2008</p> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p> <p>Set a steel "T-Post" fence post near cor.</p>
60.45	Dirt Road, 15 ft. wide, bears N. 35° E. and S. 35° W.
80.07	<p>The cor. of secs. 11, 12, 13 and 14.</p> <p>Land, nearly level. Soil, sandstone and fine sand. No timber; scattered native grasses.</p> <hr/> <p>N. 0°01' W., bet. secs. 11 and 12.</p> <p>Over gently rolling terrain.</p>
2.10	Underground water line, bears S. 60° E. and N. 60° W.
40.00	<p>Point for the 1/4 sec. cor. of secs. 11 and 12.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T 41 N R 28 E 1/4 S 11 S 12</p> <p style="text-align: center;">2008</p> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p> <p>Set a steel "T-Post" fence post near cor.</p>

**Survey of the Subdivisional Lines,
T. 41 N., R. 28 E., Gila and Salt River Meridian, Arizona**

CHAINS									
77.45	Top of cliff face at S. edge of mesa, bears N. 50° E. and S. 50° W.								
80.00	<p>Point for the cor. of secs. 1, 2, 11 and 12.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 19 ins. in the ground, encircled by a supporting mound of stone, 5 ft. base, to top of brass cap mkd.</p> <div style="text-align: center; margin: 10px 0;"> <table style="margin: auto; border-collapse: collapse;"> <tr> <td style="padding: 0 10px;">T 41 N</td> <td style="padding: 0 10px;">R 28 E</td> </tr> <tr> <td style="border-right: 1px solid black; padding: 0 5px;">S 2</td> <td style="padding: 0 5px;">S 1</td> </tr> <tr> <td style="border-right: 1px solid black; padding: 0 5px;">S 11</td> <td style="padding: 0 5px;">S 12</td> </tr> </table> <p style="margin: 5px 0;">2008</p> </div> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p> <p>Set a steel "T-Post" fence post near cor.</p> <p>An iron pipe, 2 ins. diam., 28 ins. long, disturbed and laying loose, with marks T41N 2 1 11 12 R28E on it's side, was found nearby, next to a mound of stone. Dismantled the mound of stone.</p> <p>Land, rolling and broken. Soil, fine sand. Timber, occasional juniper; scattered native grasses.</p> <hr style="width: 80%; margin: 10px auto;"/> <p>From the cor. of secs. 1, 6, 7 and 12, on the E. bdy. of the Tp., hereinbefore described.</p> <p>S. 89°55' W., bet. secs. 1 and 12.</p> <p>Over gently rolling terrain, transitioning to a mesa.</p>	T 41 N	R 28 E	S 2	S 1	S 11	S 12		
T 41 N	R 28 E								
S 2	S 1								
S 11	S 12								
40.03	<p>Point for the 1/4 sec. cor. of secs. 1 and 12.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 27 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center; margin: 10px 0;"> <table style="margin: auto; border-collapse: collapse;"> <tr> <td style="padding: 0 10px;">T 41 N</td> <td style="padding: 0 10px;">R 28 E</td> </tr> <tr> <td style="padding: 0 10px;"></td> <td style="padding: 0 10px;">S 1</td> </tr> <tr> <td style="padding: 0 10px;">1/4</td> <td style="border-top: 1px solid black; padding: 0 10px;"></td> </tr> <tr> <td style="padding: 0 10px;"></td> <td style="padding: 0 10px;">S 12</td> </tr> </table> <p style="margin: 5px 0;">2008</p> </div> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p> <p>Raise a mound of stone, 3 ft. base, 1 1/2 ft. high, N. of cor.</p>	T 41 N	R 28 E		S 1	1/4			S 12
T 41 N	R 28 E								
	S 1								
1/4									
	S 12								

**Survey of the Subdivisional Lines,
T. 41 N., R. 28 E., Gila and Salt River Meridian, Arizona**

CHAINS	
	<p>Set a steel "T-Post" fence post near cor.</p> <p>From this cor. point, a cor. set by persons unknown, bears N. 58°57' E., 9 lks. dist., monumented with an open ended iron pipe, 2 ins. diam., loosely set, projecting 18 ins. above the ground, with marks 1 12 on its southerly side.</p>
80.06	<p>The cor. of secs. 1, 2, 11 and 12.</p> <p>Land, rolling and broken. Soil, sandstone and fine sand. Timber, occasional juniper; scattered native grasses.</p> <hr/> <p>N. 0°01' E., bet. secs. 1 and 2.</p> <p>Over rolling and broken mesa top.</p>
40.00	<p>Point for the 1/4 sec. cor. of secs. 1 and 2.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T 41 N R 28 E 1/4 S 2 S 1 2008</p> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p> <p>Raise a mound of stone, 4 ft. base, 2 ft. high, S. of cor.</p>
45.25	<p>Top of cliff face at N. edge of mesa, bears N. 55° E. and S. 55° W.</p>
80.15	<p>The cor. of secs. 1, 2, 35 and 36, hereinbefore described.</p> <p>Land, rolling and broken. Soil, sandstone and fine sand. No timber; scattered native grasses.</p> <hr/> <p>From the stan. cor. of secs. 34 and 35, on the S. bdy. of the Tp., monumented with an iron post, 2 1/2 ins. diam., firmly set, projecting 2 ins. above the ground, with brass cap mkd. SC T41N R28E S34 S35 2006 1953.</p> <p>N. 0°02' W., bet. secs. 34 and 35.</p> <p>Over rolling terrain, transitioning to nearly level terrain.</p>

**Survey of the Subdivisional Lines,
T. 41 N., R. 28 E., Gila and Salt River Meridian, Arizona**

CHAINS	
30.30	Dirt road, 12 ft. wide, bears S. 75° E. and N. 75° W.
39.65	Power line, 2 wire, bears S. 70° E. and N. 70° W.
40.00	Point for the 1/4 sec. cor. of secs. 34 and 35. Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with brass cap mkd. <div style="text-align: center;"> T 41 N R 28 E 1/4 S 34 S 35 2008 </div> from which <div style="text-align: center;"> A power pole (BB-21), 10 ins. diam., bears S. 55 1/4° W., 34 lks. dist., mkd. by a 60 D nail driven into it 13 ins. above the ground. </div> Deposit a magnet, in a white plastic case, at the base of the stainless steel post. Set a steel "T-Post" fence post near cor.
80.00	Point for the cor. of secs. 26, 27, 34 and 35. Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 27 ins. in the ground, with brass cap mkd. <div style="text-align: center;"> T 41 N R 28 E S 27 S 26 S 34 S 35 2008 </div> Deposit a magnet, in a white plastic case, at the base of the stainless steel post. Set a steel "T-Post" fence post near cor. Land, gently rolling to nearly level. Soil, fine sand. No timber; scattered native grasses. <hr/> From the cor. of secs. 25, 26, 35 and 36. N. 89°59' W., bet. secs. 26 and 35. Over gently rolling to nearly level terrain.

**Survey of the Subdivisional Lines,
T. 41 N., R. 28 E., Gila and Salt River Meridian, Arizona**

CHAINS	
3.60	Dirt road, 8 ft. wide, bears S. 40° E. and N. 40° W.
40.025	Point for the 1/4 sec. cor. of secs. 26 and 35. Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 27 ins. in the ground, with brass cap mkd. <div style="text-align: center;"> T 41 N R 28 E S 26 1/4 ——— S 35 2008 </div> Deposit a magnet, in a white plastic case, at the base of the stainless steel post. Set a steel "T-Post" fence post near cor.
80.05	The cor. of secs. 26, 27, 34 and 35. Land, rolling to nearly level. Soil, fine sand. No timber; scattered native grasses. <hr/>
	N. 0°02' W., bet. secs. 26 and 27. Over gently rolling to nearly level terrain.
23.95	Dirt road, 12 ft. wide, bears N. 45° E. and S. 45° W.
40.00	Point for the 1/4 sec. cor. of secs. 26 and 27. Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 25 ins. in the ground, with brass cap mkd. <div style="text-align: center;"> T 41 N R 28 E 1/4 S 27 S 26 2008 </div> Deposit a magnet, in a white plastic case, at the base of the stainless steel post. Set a steel "T-Post" fence post near cor.
80.00	Point for the cor. of secs. 22, 23, 26 and 27. Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 27 ins. in the ground, with brass cap mkd.

**Survey of the Subdivisional Lines,
T. 41 N., R. 28 E., Gila and Salt River Meridian, Arizona**

CHAINS									
	<table style="margin-left: auto; margin-right: auto;"> <tr> <td>T 41 N</td> <td>R 28 E</td> </tr> <tr> <td>S 22</td> <td>S 23</td> </tr> <tr> <td>S 27</td> <td>S 26</td> </tr> </table>	T 41 N	R 28 E	S 22	S 23	S 27	S 26		
T 41 N	R 28 E								
S 22	S 23								
S 27	S 26								
	2008								
	Deposit a magnet, in a white plastic case, at the base of the stainless steel post.								
	Set a steel "T-Post" fence post near cor.								
	Land, gently rolling to nearly level. Soil, fine sand. No timber; scattered native grasses.								
	<hr/>								
	From the cor. of secs. 23, 24, 25 and 26.								
	N. 89°59' W., bet. secs. 23 and 26.								
	Over gently rolling to nearly level terrain.								
31.35	Dirt road, 8 ft. wide, bears N. 50° E. and S. 50° W.								
40.025	Point for the 1/4 sec. cor. of secs. 23 and 26.								
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 27 ins. in the ground, with brass cap mkd.								
	<table style="margin-left: auto; margin-right: auto;"> <tr> <td>T 41 N</td> <td>R 28 E</td> </tr> <tr> <td>S 23</td> <td></td> </tr> <tr> <td>1/4</td> <td>—</td> </tr> <tr> <td>S 26</td> <td></td> </tr> </table>	T 41 N	R 28 E	S 23		1/4	—	S 26	
T 41 N	R 28 E								
S 23									
1/4	—								
S 26									
	2008								
	Deposit a magnet, in a white plastic case, at the base of the stainless steel post.								
	Set a steel "T-Post" fence post near cor.								
80.05	The cor. of secs. 22, 23, 26 and 27.								
	Land, rolling to nearly level. Soil, fine sand. No timber; scattered native grasses.								
	<hr/>								
	N. 0°02' W., bet. secs. 22 and 23.								
	Over gently rolling to nearly level terrain.								

**Survey of the Subdivisional Lines,
T. 41 N., R. 28 E., Gila and Salt River Meridian, Arizona**

CHAINS	
7.35	Dirt road, 12 ft. wide, bears N. 60° E. and S. 60° W.
7.65	Power line, 2 wire, bears N. 55° E. and S. 55° W.
19.90	Dirt road, 10 ft. wide, bears S. 50° E. and N. 50° W.
40.00	Point for the 1/4 sec. cor. of secs. 22 and 23. Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 25 ins. in the ground, with brass cap mkd. <div style="text-align: center;"> T 41 N R 28 E 1/4 S 22 S 23 2008 </div> Deposit a magnet, in a white plastic case, at the base of the stainless steel post. Set a steel "T-Post" fence post near cor. From this cor. point, the pump shaft of a windmill, set on a concrete slab, 9 ft. x 9 ft., bears N. 45°15' W., 19.32 chs. dist., with a water tank, approximately 30 ft. diam., nearby.
66.60	High voltage transmission line, 5 wire, bears S. 77° E. and N. 77° W.
80.00	Point for the cor. of secs. 14, 15, 22 and 23. Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 25 ins. in the ground, with brass cap mkd. <div style="text-align: center;"> T 41 N R 28 E S 15 S 14 S 22 S 23 2008 </div> Deposit a magnet, in a white plastic case, at the base of the stainless steel post. Set a steel "T-Post" fence post near cor. Land, gently rolling to nearly level. Soil, fine sand. No timber; scattered native grasses.
	<hr/> From the cor. of secs. 13, 14, 23 and 24. N. 89°59' W., bet. secs. 14 and 23.

**Survey of the Subdivisional Lines,
T. 41 N., R. 28 E., Gila and Salt River Meridian, Arizona**

CHAINS	
	Over gently rolling to nearly level terrain.
40.025	Point for the 1/4 sec. cor. of secs. 14 and 23. Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 27 ins. in the ground, with brass cap mkd. <div style="text-align: center;"> T 41 N R 28 E S 14 1/4 ——— S 23 2008 </div>
	Deposit a magnet, in a white plastic case, at the base of the stainless steel post.
	Set a steel "T-Post" fence post near cor.
	From this cor. point, a cor. set by persons unknown, bears northeasterly, 10 1/2 lks. dist., monumented with an open ended iron pipe, 2 ins. diam., firmly set, projecting 20 ins. above the ground, in supporting mound of stone, 2 ft. base, 1 ft. high, with marks 14 23 on its southerly side.
80.05	The cor. of secs. 14, 15, 22 and 23. Land, rolling to nearly level. Soil, fine sand. No timber; scattered native grasses.

	N. 0°02' W., bet. secs. 14 and 15.
	Over gently rolling to nearly level terrain.
34.10	South right-of-way fence, barbed wire, 5 strand, bears S. 85° E. and N. 85° W.
35.60	Interstate Highway No. 160, asphalt surfaced, 34 ft. wide, bears S. 85° E. and N. 85° W.
38.65	North right-of-way fence, barbed wire, 5 strand, bears S. 85° E. and N. 85° W.
38.95	Power line, 4 wire, bears S. 85° E. and N. 85° W.
40.00	Point for the 1/4 sec. cor. of secs. 14 and 15. Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 25 ins. in the ground, with brass cap mkd.

**Survey of the Subdivisional Lines,
T. 41 N., R. 28 E., Gila and Salt River Meridian, Arizona**

CHAINS	
	T 41 N R 28 E 1/4 S 15 S 14 2008
	Deposit a magnet, in a white plastic case, at the base of the stainless steel post. Set a steel "T-Post" fence post near cor. From this cor. point, a cor. set by persons unknown, bears N. 23°34' E., 9 lks. dist., monumented with an open ended iron pipe, 1 in. diam., firmly set, projecting 8 ins. and bent to ground, with marks 1/4 14 15 on side. From this same cor. point, a Department of Transportation (DOT) monument, bears S. 13°42' W., 1.385 chs. dist., monumented with a brass tablet, 3 ins. diam., set in a concrete cylinder, 6 ins. diam., firmly set, projecting 12 ins. above the ground, mkd. ELEV + STA 19.
80.00	Point for the cor. of secs. 10, 11, 14 and 15. Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 27 ins. in the ground, with brass cap mkd. T 41 N R 28 E S 10 S 11 S 15 S 14 2008 Deposit a magnet, in a white plastic case, at the base of the stainless steel post. Set a steel "T-Post" fence post near cor. From this cor. point, a cor. set by persons unknown, bears N. 31°12' E., 7 lks. dist., monumented with an open ended iron pipe, 1 in. diam., firmly set, projecting 12 ins. above ground, with marks T41N 10 11 15 14 R28E on its northerly side. Land, gently rolling to nearly level. Soil, fine sand. No timber; scattered native grasses.
	From the cor. of secs. 11, 12, 13 and 14. N. 89°59' W., bet. secs. 11 and 14. Over gently rolling to nearly level terrain.

**Survey of the Subdivisional Lines,
T. 41 N., R. 28 E., Gila and Salt River Meridian, Arizona**

CHAINS	
40.025	<p>Point for the 1/4 sec. cor. of secs. 11 and 14.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T 41 N R 28 E S 11 1/4 ——— S 14</p> <p style="text-align: center;">2008</p> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p> <p>Set a steel "T-Post" fence post near cor.</p>
53.25	Graded road, 24 ft. wide, bears S. 20° E. and N. 20° W.
77.00	Underground petroleum pipe line, bears S. 60° E. and N. 60° W.
80.05	<p>The cor. of secs. 10, 11, 14 and 15.</p> <p>Land, rolling to nearly level. Soil, fine sand. No timber; scattered native grasses.</p> <hr/> <p>N. 0°02' W., bet. secs. 10 and 11.</p> <p>Over gently rolling to nearly level terrain.</p>
1.55	Underground petroleum pipe line, bears S. 60° E. and N. 60° W.
37.50	Underground waterline, bears N. 75° E. and S. 75° W.
40.00	<p>Point for the 1/4 sec. cor. of secs. 10 and 11.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 27 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T 41 N R 28 E 1/4 S 10 S 11</p> <p style="text-align: center;">2008</p> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p> <p>Set a steel "T-Post" fence post near cor.</p>

**Survey of the Subdivisional Lines,
T. 41 N., R. 28 E., Gila and Salt River Meridian, Arizona**

CHAINS							
	<p>From this cor. point, a drill hole casing, an iron post, 5 ins. diam., bears N. 31°49' E., 13.25 chs. dist., firmly set, projecting 4 ft. above ground, mkd. MERRIO-BAYLESS NAVAJO 2-11 N.W. SEC.11 T.41N. R.28E. APACHE ARIZ. LEASE 14-20-603-227.</p> <p>From this same cor. point, a concrete water well cistern, bears N. 75°52' E., 25.25 chs. dist., 5 x 5 x 3 ft. high, with an iron hand pump.</p> <p>From this same cor. point, a drill hole casing, an iron post, 5 ins. diam., bears S. 71°41' E., 31.61 chs. dist., firmly set, projecting 5 ft. above ground, mkd. MERRIO-BAYLESS NAVAJO 23-11 S.W. SEC.11 T.41N. R.28E. APACHE ARIZ. LEASE 1-20-603-227.</p> <p>From this same cor. point, a drill hole casing, an iron post, 5 ins. diam., bears N. 78°04' W., 30.34 chs. dist., firmly set, projecting 6 1/2 ft. above ground, mkd. NAVAJO E WELL #1 SEC 10 T41N R28E APACHE ARIZONA MERRION OIL & GAS CORPORATION.</p>						
47.35	Graded road, 15 ft. wide, bears S. 75° E. and N. 80° W.						
48.15	Graded road, 15 ft. wide, bears S. 45° E. and N. 45° W.						
67.10	Graded road, 10 ft. wide, bears N. 35° E. and S. 35° W.						
80.00	Point for the cor. of secs. 2, 3, 10 and 11.						
	<p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center;"> <table border="1"> <tr> <td colspan="2">T 41 N R 28 E</td> </tr> <tr> <td>S 3</td> <td>S 2</td> </tr> <tr> <td>S 10</td> <td>S 11</td> </tr> </table> <p>2008</p> </div> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p> <p>Set a steel "T-Post" fence post near cor.</p> <p>Land, gently rolling to nearly level. Soil, fine sand. No timber; scattered native grasses.</p> <hr/> <p>From the cor. of secs. 1, 2, 11 and 12.</p> <p>N. 89°59' W., bet. secs. 2 and 11.</p> <p>Over rolling and broken mesa top, transitioning into rolling terrain.</p>	T 41 N R 28 E		S 3	S 2	S 10	S 11
T 41 N R 28 E							
S 3	S 2						
S 10	S 11						

**Survey of the Subdivisional Lines,
T. 41 N., R. 28 E., Gila and Salt River Meridian, Arizona**

CHAINS	
40.025	<p>Point for the 1/4 sec. cor. of secs. 2 and 11.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 23 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T 41 N R 28 E S 2 1/4 ——— S 11</p> <p style="text-align: center;">2008</p> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p> <p>Set a steel "T-Post" fence post near cor.</p> <p>From this cor. point, a cor. set by persons unknown, bears N. 63°36' E., 13 lks. dist., monumented with an open ended iron pipe, 2 ins. diam., firmly set, projecting 12 ins. above ground, in a supporting mound of stone, 4 ft. base, to top, with marks 2 11 on its southerly side.</p> <p>Cor. falls on E. edge of sandstone boulder in place, 5 x 3 ft.</p>
72.50	Graded road, 10 ft. wide, bears N. 30° E. and S. 30° W.
80.05	<p>The cor. of secs. 2, 3, 10 and 11.</p> <p>Land, rolling to nearly level. Soil, fine sand. No timber; scattered native grasses.</p> <hr/> <p>N. 0°01' E., bet. secs. 2 and 3.</p> <p>Over gently rolling to nearly level terrain.</p>
15.05	Dirt road, 8 ft. wide, bears E. and W.
40.00	<p>Point for the 1/4 sec. cor. of secs. 2 and 3.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 25 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T 41 N R 28 E 1/4 S 3 S 2</p> <p style="text-align: center;">2008</p> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p>

**Survey of the Subdivisional Lines,
T. 41 N., R. 28 E., Gila and Salt River Meridian, Arizona**

CHAINS	
80.13	<p>Set a steel "T-Post" fence post near cor.</p> <p>The cor. of secs. 2, 3, 34 and 35, hereinbefore described.</p> <p>Land, rolling and broken. Soil, fine sand. No timber; scattered native grasses.</p> <hr/> <p>From the stan. cor. of secs. 33 and 34, on the S. bdy. of the Tp., monumented with an iron post, 2 1/2 ins. diam., firmly set, projecting 4 ins. above the ground, with brass cap mkd. SC T41N R28E S33 S34 2006, with a mound of stone, 3 ft. base, 2 ft. high, N. of cor., from which the bearing tree mkd. in 1953</p> <p style="padding-left: 40px;">A juniper, 15 ins. diam., bears N. 51°24' E., 97 lks. dist., with a healed blaze.</p> <p>N. 0°02' W., bet. secs. 33 and 34.</p> <p>Over broken and rolling terrain.</p>
34.95	<p>Navajo Route 35, a graded road, 30 ft. wide, bears N. 80° E. and S. 80° W.</p>
40.00	<p>Point for the 1/4 sec. cor. of secs. 33 and 34.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T 41 N R 28 E 1/4 S 33 S 34 2008</p> <p>from which</p> <p style="padding-left: 40px;">A sandstone outcrop, 9 x 5 x 2 ft. above ground, bears S. 9 1/4° E., 93 lks. dist., mkd. with an X over BO.</p> <p style="padding-left: 40px;">A sandstone rock in place, 5 x 3 x 3 ft. above ground, bears S. 72° W., 1.18 chs. dist., mkd. X BO, with the B above and the O below the X.</p> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p> <p>Set a steel "T-Post" fence post near cor.</p>
56.00	<p>Power line, 2 wire, bears S. 80° E. and N. 80° W.</p>

**Survey of the Subdivisional Lines,
T. 41 N., R. 28 E., Gila and Salt River Meridian, Arizona**

CHAINS									
62.25	Dirt road, 10 ft. wide, bears E. and W.								
80.00	Point for the cor. of secs. 27, 28, 33 and 34. Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 25 ins. in the ground, with brass cap mkd. <div style="text-align: center;"> <table border="0"> <tr> <td>T 41 N</td> <td>R 28 E</td> </tr> <tr> <td>S 28</td> <td>S 27</td> </tr> <tr> <td>S 33</td> <td>S 34</td> </tr> </table> <p>2008</p> </div> Deposit a magnet, in a white plastic case, at the base of the stainless steel post. Set a steel "T-Post" fence post near cor. Land, gently rolling to nearly level. Soil, fine sand. No timber; scattered native grasses. <hr/> From the cor. of secs. 26, 27, 34 and 35. N. 89°58' W., bet. secs. 27 and 34. Over gently rolling to nearly level terrain.	T 41 N	R 28 E	S 28	S 27	S 33	S 34		
T 41 N	R 28 E								
S 28	S 27								
S 33	S 34								
20.50	Dirt road, 10 ft. wide, bears N. 50° E. and S. 50° W.								
40.06	Point for the 1/4 sec. cor. of secs. 27 and 34. Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with brass cap mkd. <div style="text-align: center;"> <table border="0"> <tr> <td>T 41 N</td> <td>R 28 E</td> </tr> <tr> <td></td> <td>S 27</td> </tr> <tr> <td>1/4</td> <td>_____</td> </tr> <tr> <td></td> <td>S 34</td> </tr> </table> <p>2008</p> </div> Deposit a magnet, in a white plastic case, at the base of the stainless steel post. Set a steel "T-Post" fence post near cor.	T 41 N	R 28 E		S 27	1/4	_____		S 34
T 41 N	R 28 E								
	S 27								
1/4	_____								
	S 34								
56.05	Navajo Route 35, a graded road, 30 ft. wide, bears S. 25° E. and N. 25° W.								
80.12	The cor. of secs. 27, 28, 33 and 34.								

**Survey of the Subdivisional Lines,
T. 41 N., R. 28 E., Gila and Salt River Meridian, Arizona**

CHAINS	
	<p>Land, rolling to nearly level. Soil, fine sand. No timber; scattered native grasses.</p> <hr/> <p>N. 0°02' W., bet. secs. 27 and 28.</p> <p>Over gently rolling terrain.</p>
40.00	<p>Point for the 1/4 sec. cor. of secs. 27 and 28.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center;"> <p>T 41 N R 28 E 1/4 S 28 S 27</p> <p>2008</p> </div> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p> <p>Set a steel "T-Post" fence post near cor.</p> <p>From this cor. point, a Department of Transportation (DOT) monument, bears N. 81°19' E., 74 1/2 lks. dist., monumented with a brass tablet, 3 ins. diam., set in a concrete cylinder, 6 ins. diam., firmly set, projecting 5 ins. above the ground, mkd. B.I.A. NAVAJO ROADS BM 129 5525.89 1973.</p>
48.35	<p>Navajo Route 35, a graded road, 35 ft. wide, bears S. 25° E. and N. 25° W.</p>
54.10	<p>Power line, 2 wire, bears N. 75° E. and S. 75° W.</p>
63.10	<p>Dirt road, 15 ft. wide, bears N. 45° E. and S. 45° W.</p>
80.00	<p>Point for the cor. of secs. 21, 22, 27 and 28.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center;"> <p>T 41 N R 28 E S 21 S 22 <hr/>S 28 S 27</p> <p>2008</p> </div> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p> <p>Set a steel "T-Post" fence post near cor.</p>

Survey of the Subdivisional Lines,
T. 41 N., R. 28 E., Gila and Salt River Meridian, Arizona

CHAINS	
	<p>Land, gently rolling. Soil, fine sand. No timber; scattered native grasses.</p> <hr/> <p>From the cor. of secs. 22, 23, 26 and 27. N. 89°58' W., bet. secs. 22 and 27. Over gently rolling to nearly level terrain.</p>
40.06	<p>Point for the 1/4 sec. cor. of secs. 22 and 27. Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T 41 N R 28 E S 22 1/4 ——— S 27</p> <p style="text-align: center;">2008</p> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p> <p>Set a steel "T-Post" fence post near cor.</p>
58.65	Dirt road, 10 ft. wide, bears S. 50° E. and N. 50° W.
63.95	Dirt road, 10 ft. wide, bears N. 70° E. and S. 45° W.
80.12	The cor. of secs. 21, 22, 27 and 28.
	<p>Land, gently rolling. Soil, fine sand. No timber; scattered native grasses.</p> <hr/> <p>N. 0°02' W., bet. secs. 21 and 22. Over gently rolling to nearly level terrain.</p>
40.00	<p>Point for the 1/4 sec. cor. of secs. 21 and 22. Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 25 ins. in the ground, with brass cap mkd.</p>

**Survey of the Subdivisional Lines,
T. 41 N., R. 28 E., Gila and Salt River Meridian, Arizona**

CHAINS	
	T 41 N R 28 E 1/4 S 21 S 22 2008
	Deposit a magnet, in a white plastic case, at the base of the stainless steel post.
	Set a steel "T-Post" fence post near cor.
48.45	Dirt road, 10 ft. wide, bears N. 60° E. and S. 60° W.
68.55	Dirt road, 8 ft. wide, bears S. 40° E. and S. 70° W.
80.00	Point for the cor. of secs. 15, 16, 21 and 22.
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with brass cap mkd.
	T 41 N R 28 E S 16 S 15 S 21 S 22 2008
	Deposit a magnet, in a white plastic case, at the base of the stainless steel post.
	Set a steel "T-Post" fence post near cor.
	Land, gently rolling to nearly level. Soil, fine sand. No timber; scattered native grasses.
	<hr/> From the cor. of secs. 14, 15, 22 and 23.
	N. 89°58' W., bet. secs. 15 and 22.
	Over gently rolling to nearly level terrain.
40.06	Point for the 1/4 sec. cor. of secs. 15 and 22.
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with brass cap mkd.

Survey of the Subdivisional Lines,
T. 41 N., R. 28 E., Gila and Salt River Meridian, Arizona

CHAINS	
	T 41 N R 28 E S 15 1/4 ——— S 22 2008
	Deposit a magnet, in a white plastic case, at the base of the stainless steel post.
	Set a steel "T-Post" fence post near cor.
56.75	Dirt road, 10 ft. wide, bears S. 40° E. and N. 40° W.
57.40	Dirt road, 10 ft. wide, bears S. 50° E. and N. 50° W.
58.85	High voltage transmission line, 5 wire, bears S. 77° E. and N. 77° W.
60.75	Dirt road, 8 ft. wide, bears N. 45° E. and S. 45° W.
80.12	The cor. of secs. 15, 16, 21 and 22. Land, rolling to nearly level. Soil, fine sand. No timber; scattered native grasses.
	N. 0°02' W., bet. secs. 15 and 16. Over gently rolling to nearly level terrain.
4.85	High voltage transmission line, 5 wire, bears S. 77° E. and N. 77° W.
23.60	Dirt road, 10 ft. wide, bears S. 45° E. and N. 45° W.
23.90	Dirt road, 10 ft. wide, bears S. 45° E. and N. 45° W.
37.40	South right-of-way fence, barbed wire, 5 strand, bears S. 88° E. and N. 88° W.
38.90	Interstate Highway No. 160, asphalt surfaced, 30 ft. wide, bears S. 88° E. and N. 88° W.
40.00	Point for the 1/4 sec. cor. of secs. 15 and 16. Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 25 ins. in the ground, with brass cap mkd.

**Survey of the Subdivisional Lines,
T. 41 N., R. 28 E., Gila and Salt River Meridian, Arizona**

CHAINS	
	T 41 N R 28 E 1/4 S 16 S 15 2008
	Deposit a magnet, in a white plastic case, at the base of the stainless steel post. Set a steel "T-Post" fence post near cor.
41.95	Intersect line 3-4, Tract 37, not monumented; also North right-of-way fence, barbed wire, 5 strand, bears S. 88° E. and N. 88° W.
42.15	South storage pond fence, rabbit wire, bears S. 88° E. and N. 88° W.
42.25	Power line, 4 wire, bears S. 88° E. and N. 88° W.
44.05	West storage pond fence, rabbit wire, bears N. 2° E. and S. 2° W.
47.67	Intersect line 2-3, Tract 37, not monumented.
80.00	Point for the cor. of secs. 9, 10, 15 and 16. Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.
	T 41 N R 28 E S 9 S 10 S 16 S 15 2008
	Deposit a magnet, in a white plastic case, at the base of the stainless steel post. Set a steel "T-Post" fence post near cor. Land, gently rolling to nearly level. Soil, fine sand. No timber; scattered native grasses.
	<hr/> From the cor. of secs. 10, 11, 14 and 15. N. 89°58' W., bet. secs. 10 and 15. Over gently rolling to nearly level terrain.
19.40	Dirt road, 8 ft. wide, bears S. 50° E. and N. 50° W.

**Survey of the Subdivisional Lines,
T. 41 N., R. 28 E., Gila and Salt River Meridian, Arizona**

CHAINS	
40.06	<p>Point for the 1/4 sec. cor. of secs. 10 and 15.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 25 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T 41 N R 28 E S 10 1/4 ——— S 15</p> <p style="text-align: center;">2008</p> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p> <p>Set a steel "T-Post" fence post near cor.</p>
80.12	<p>The cor. of secs. 9, 10, 15 and 16.</p> <p>Land, rolling to nearly level. Soil, fine sand. No timber; scattered native grasses.</p> <hr/> <p>N. 0°02' W., bet. secs. 9 and 10.</p> <p>Over gently rolling to nearly level terrain.</p>
1.60	Dirt road, 8 ft. wide, bears E. and W.
19.50	Graded road, 20 ft. wide, bears N. 40° E. and S. 40° W.
40.00	<p>Point for the 1/4 sec. cor. of secs. 9 and 10.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 27 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T 41 N R 28 E 1/4 S 9 S 10</p> <p style="text-align: center;">2008</p> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p> <p>Set a steel "T-Post" fence post near cor.</p>
40.15	Underground petroleum pipe line, bears S. 70° E. and N. 70° W.
41.80	Graded road, 12 ft. wide, bears E. and W.

**Survey of the Subdivisional Lines,
T. 41 N., R. 28 E., Gila and Salt River Meridian, Arizona**

CHAINS									
49.10	Top of bluff, bears S. 65° E. and N. 40° W.								
80.00	Point for the cor. of secs. 3, 4, 9 and 10. Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 25 ins. in the ground, with brass cap mkd. <div style="text-align: center;"> <table style="margin: auto;"> <tr><td>T 41 N</td><td>R 28 E</td></tr> <tr><td>S 4</td><td>S 3</td></tr> <tr><td colspan="2"><hr style="width: 50%; margin: 0 auto;"/></td></tr> <tr><td>S 9</td><td>S 10</td></tr> </table> <p>2008</p> </div> Deposit a magnet, in a white plastic case, at the base of the stainless steel post. Set a steel "T-Post" fence post near cor. From this cor. point, a drill hole casing, an iron pipe, 5 ins. diam., bears N. 60°13' E., 9.46 chs. dist., firmly set, projecting 5 1/2 ft. above ground, mkd. MERRION OIL-GAS CO NAVAJO 3-3 M. SW/SW SEC 3 T41N R28E APACHE CO AZ BIA-#14-20-603-226 on the side. Land, gently rolling to nearly level. Soil, fine sand. No timber; scattered native grasses. <hr style="width: 50%; margin: 10px auto 10px auto;"/>	T 41 N	R 28 E	S 4	S 3	<hr style="width: 50%; margin: 0 auto;"/>		S 9	S 10
T 41 N	R 28 E								
S 4	S 3								
<hr style="width: 50%; margin: 0 auto;"/>									
S 9	S 10								
	From the cor. of secs. 2, 3, 10 and 11. N. 89°58' W., bet. secs. 3 and 10. Over rolling and broken terrain.								
6.65	Graded road, 12 ft. wide, bears S. 30° E. and N. 20° W.								
40.06	Point for the 1/4 sec. cor. of secs. 3 and 10. Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 25 ins. in the ground, with brass cap mkd. <div style="text-align: center;"> <table style="margin: auto;"> <tr><td>T 41 N</td><td>R 28 E</td></tr> <tr><td></td><td>S 3</td></tr> <tr><td>1/4</td><td><hr style="width: 50%; margin: 0 auto;"/></td></tr> <tr><td></td><td>S 10</td></tr> </table> <p>2008</p> </div> Deposit a magnet, in a white plastic case, at the base of the stainless steel post. Set a steel "T-Post" fence post near cor.	T 41 N	R 28 E		S 3	1/4	<hr style="width: 50%; margin: 0 auto;"/>		S 10
T 41 N	R 28 E								
	S 3								
1/4	<hr style="width: 50%; margin: 0 auto;"/>								
	S 10								

**Survey of the Subdivisional Lines,
T. 41 N., R. 28 E., Gila and Salt River Meridian, Arizona**

CHAINS	
80.12	<p>The cor. of secs. 3, 4, 9 and 10.</p> <p>Land, rolling to nearly level. Soil, fine sand. No timber; scattered native grasses.</p> <hr/> <p>N. 0°05' E., bet. secs. 3 and 4.</p> <p>Over rolling and broken terrain.</p>
20.40	Dirt road, 15 ft. wide, bears N. 80° E. and S. 80° W.
40.00	<p>Point for the 1/4 sec. cor. of secs. 3 and 4.</p> <p>Set a brass tablet, 3 1/4 ins. diam., 3 1/2 ins. stem, cemented in a drill hole in sandstone outcrop, with top mkd.</p> <p style="text-align: center;">T 41 N R 28 E 1/4 S 4 S 3</p> <p style="text-align: center;">2008</p> <p>Deposit a magnet, in a white plastic case, in bottom of drill hole.</p> <p>From this cor. point, the main pump shaft of an active oil well, bears N. 71°31' E., 31.76 chs. dist., with tanks nearby and sign mkd. ELM RIDGE EXPLORATION, LLC NAVAJO #2 LEASE #: NOOC 14-20-603-226 API: 02-001-05020 SEC.: 3-T41N-R28E 1980' FNL x 1980' FWL APACHE COUNTY, AZ EMERG. CONTACT: 505-632-3476.</p> <p>From this same cor. point, the main pump shaft of an active oil well, bears S. 75°41' E., 33.13 chs. dist., with tanks nearby and sign mkd. CENTRAL RESOURCES, INC NAVAJO WELL NO. 3-11 NAVAJO TRIBAL NE/4 SW/4 SEC. 3, T41N R23E LEASE NO. NOO-C-14-20-603-226 APACHE COUNTY, ARIZONA.</p> <p>From this same cor. point, the pump shaft of a windmill, set on a concrete slab, 10 ft. x 10 ft., bears S. 23°23' W., 18.24 chs. dist., with a water tank, approximately 30 ft. diam., nearby.</p> <p>From this same cor. point, the main pump shaft of an active oil well, bears S. 55°49' W., 17.88 chs. dist., with tanks nearby and sign mkd. ELM RIDGE EXPLORATION, LLC NAVAJO #1 LEASE #: NOOC 14-20-603-413 API: 02-001-05199 SEC.: 4-T41N-R28E 1980' FSL x 990' FEL APACHE COUNTY, AZ EMERG. CONTACT: 505-632-3476.</p>
80.04	The cor. of secs. 3, 4, 33 and 34, hereinbefore described.

**Survey of the Subdivisional Lines,
T. 41 N., R. 28 E., Gila and Salt River Meridian, Arizona**

CHAINS	
	<p>Land, rolling and broken. Soil, fine sand. No timber; scattered native grasses.</p> <hr/> <p>From the stan. cor. of secs. 32 and 33, on the S. bdy. of the Tp., monumented with a stainless steel post, 2 1/2 ins. diam., firmly set, projecting 2 ins. above the ground, with brass cap mkd. SC T41N R28E S32 S33 2006, from which the remaining bearing tree mkd. in 1953</p> <p style="padding-left: 40px;">A dead piñon, 10 ins. diam., bears N. 55°16' E., 1.11 chs. dist., with remaining scribe marks BT visible on a badly decayed open blaze.</p> <p>From this cor. point, a rebar, 1/4 in. diam., bears N. 11° W., 3 lks. dist., firmly set, projecting 2 ins. above ground, with no cap, of unknown origin.</p> <p>N. 0°03' W., bet. secs. 32 and 33.</p> <p>Over broken and rolling terrain.</p>
39.05	Dirt road, 8 ft. wide, bears N. 30° E. and S. 30° W.
40.00	<p>Point for the 1/4 sec. cor. of secs. 32 and 33.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 27 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T 41 N R 28 E 1/4 S 32 S 33 2008</p> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p> <p>Set a steel "T-Post" fence post near cor.</p>
80.00	<p>Point for the cor. of secs. 28, 29, 32 and 33.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T 41 N R 28 E S 29 S 28 S 32 S 33 2008</p>

**Survey of the Subdivisional Lines,
T. 41 N., R. 28 E., Gila and Salt River Meridian, Arizona**

CHAINS	
	<p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p> <p>Set a steel "T-Post" fence post near cor.</p> <p>Land, gently rolling. Soil, fine sand. No timber; scattered native grasses.</p> <hr/> <p>From the cor. of secs. 27, 28, 33 and 34.</p> <p>S. 89°57' W., bet. secs. 28 and 33.</p> <p>Over rolling terrain.</p>
35.20	Power line, 2 wire, bears S. 10° E. and N. 10° W.
39.98	<p>Point for the 1/4 sec. cor. of secs. 28 and 33.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center;"> <p>T 41 N R 28 E</p> <p>S 28</p> <p>1/4 ———</p> <p>S 33</p> <p>2008</p> </div>
	<p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p> <p>Set a steel "T-Post" fence post near cor.</p>
79.96	<p>The cor. of secs. 28, 29, 32 and 33.</p> <p>Land, rolling to nearly level. Soil, fine sand. No timber; scattered native grasses.</p> <hr/> <p>N. 0°03' W., bet. secs. 28 and 29.</p> <p>Over gently rolling terrain.</p>
0.10	Dirt road, 8 ft. wide, bears E. and W.
4.45	Power line, 2 wire, bears N. 70° E. and S. 70° W.
40.00	Point for the 1/4 sec. cor. of secs. 28 and 29.

**Survey of the Subdivisional Lines,
T. 41 N., R. 28 E., Gila and Salt River Meridian, Arizona**

CHAINS	
	<p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T 41 N R 28 E 1/4 S 29 S 28</p> <p style="text-align: center;">2008</p> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p> <p>Set a steel "T-Post" fence post near cor.</p>
80.00	<p>Point for the cor. of secs. 20, 21, 28 and 29.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 27 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T 41 N R 28 E S 20 S 21 S 29 S 28</p> <p style="text-align: center;">2008</p> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p> <p>Set a steel "T-Post" fence post near cor.</p> <p>Land, gently rolling. Soil, fine sand. No timber; scattered native grasses.</p> <hr/> <p>From the cor. of secs. 21, 22, 27 and 28.</p> <p>S. 89°57' W., bet. secs. 21 and 28.</p> <p>Over gently rolling terrain.</p>
15.00	<p>Navajo Route 35, a graded road, 30 ft. wide, bears S. 25° E. and N. 25° W.</p>
39.98	<p>Point for the 1/4 sec. cor. of secs. 21 and 28.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 25 ins. in the ground, with brass cap mkd.</p>

**Survey of the Subdivisional Lines,
T. 41 N., R. 28 E., Gila and Salt River Meridian, Arizona**

CHAINS	
	T 41 N R 28 E S 21 1/4 ——— S 28 2008
	Deposit a magnet, in a white plastic case, at the base of the stainless steel post. Set a steel "T-Post" fence post near cor.
51.30	Dirt road, 8 ft. wide, bears N. 45° E. and S. 45° W.
51.55	Power line, 2 wire, bears S. 10° E. and N. 10° W.
79.96	The cor. of secs. 20, 21, 28 and 29. Land, gently rolling. Soil, fine sand. No timber; scattered native grasses.
	N. 0°03' W., bet. secs. 20 and 21. Over gently rolling terrain.
40.00	Point for the 1/4 sec. cor. of secs. 20 and 21. Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 25 ins. in the ground, with brass cap mkd.
	T 41 N R 28 E 1/4 S 20 S 21 2008
	Deposit a magnet, in a white plastic case, at the base of the stainless steel post. Set a steel "T-Post" fence post near cor.
46.75	Graded road, 12 ft. wide, bears N. 40° E. and S. 30° W.
80.00	Point for the cor. of secs. 16, 17, 20 and 21. Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with brass cap mkd.

**Survey of the Subdivisional Lines,
T. 41 N., R. 28 E., Gila and Salt River Meridian, Arizona**

CHAINS	
	T 41 N R 28 E S 17 S 16 S 20 S 21 2008
	Deposit a magnet, in a white plastic case, at the base of the stainless steel post. Set a steel "T-Post" fence post near cor. From this cor. point, a cor. set by persons unknown, bears N. 49°27' E., 20 1/2 lks. dist., monumented with an open ended iron pipe, 1 in. diam., firmly set, projecting 15 ins. above ground, with marks T41N 17 16 20 21 R28E on its southerly side. Land, gently rolling. Soil, fine sand. No timber; scattered native grasses.
	<hr/> From the cor. of secs. 15, 16, 21 and 22. S. 89°57' W., bet. secs. 16 and 21. Over gently rolling terrain.
39.98	Point for the 1/4 sec. cor. of secs. 16 and 21. Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with brass cap mkd. T 41 N R 28 E S 16 1/4 ——— S 21 2008
	Deposit a magnet, in a white plastic case, at the base of the stainless steel post. Set a steel "T-Post" fence post near cor. From this cor. point, a cor. set by persons unknown, bears N. 58°20' E., 19 lks. dist., monumented with an open ended iron pipe, 1 in. diam., firmly set, projecting 10 ins. above ground, with marks 1/4 16 21 on its southerly side.
55.55	Navajo Route 35, a graded road, 30 ft. wide, bears S. 30° E. and N. 30° W.
67.90	Power line, 2 wire, bears S. 10° E. and N. 10° W.

**Survey of the Subdivisional Lines,
T. 41 N., R. 28 E., Gila and Salt River Meridian, Arizona**

CHAINS	
68.75	Underground waterline, bears N. 10° E. and S. 10° W.
79.96	The cor. of secs. 16, 17, 20 and 21. Land, gently rolling. Soil, fine sand. No timber; scattered native grasses.
	N. 0°03' W., bet. secs. 16 and 17. Over gently rolling terrain.
1.55	Power line, 2 wire, bears N. 75° E. and S. 75° W.
10.95	High voltage transmission line, 5 wire, bears S. 86° E. and N. 86° W.
40.00	Point for the 1/4 sec. cor. of secs. 16 and 17. Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with brass cap mkd. <div style="text-align: center;"> T 41 N R 28 E 1/4 S 17 S 16 2008 </div> Deposit a magnet, in a white plastic case, at the base of the stainless steel post. Set a steel "T-Post" fence post near cor.
40.80	South right-of-way fence, barbed wire, 5 strand, bears S. 88° E. and N. 88° W.
42.30	Interstate Highway No. 160, asphalt surfaced, 36 ft. wide, bears S. 88° E. and N. 88° W.
45.35	North right-of-way fence, barbed wire, 5 strand, bears S. 88° E. and N. 88° W.
51.25	Power line, 4 wire, bears S. 88° E. and N. 88° W.
53.40	Dirt road, 15 ft. wide, bears N. 75° E. and S. 75° W.
80.00	Point for the cor. of secs. 8, 9, 16 and 17. Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with brass cap mkd.

Survey of the Subdivisional Lines,
T. 41 N., R. 28 E., Gila and Salt River Meridian, Arizona

CHAINS									
	<table style="margin-left: auto; margin-right: auto;"> <tr> <td>T 41 N</td> <td>R 28 E</td> </tr> <tr> <td style="border-right: 1px solid black;">S 8</td> <td>S 9</td> </tr> <tr> <td style="border-right: 1px solid black;">S 17</td> <td>S 16</td> </tr> </table>	T 41 N	R 28 E	S 8	S 9	S 17	S 16		
T 41 N	R 28 E								
S 8	S 9								
S 17	S 16								
	2008								
	<p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p> <p>Set a steel "T-Post" fence post near cor.</p> <p>From this cor. point, an iron rebar, 5/8 in. diam., bears N. 51°43' E., 22 1/2 lks. dist., firmly set, projecting 5 ins. above ground, with no cap, of unknown origin.</p> <p>Land, gently rolling. Soil, fine sand. No timber; scattered native grasses.</p>								
	<hr/> <p>From the cor. of secs. 9, 10, 15 and 16.</p> <p>S. 89°57' W., bet. secs. 9 and 16.</p> <p>Over gently rolling terrain.</p>								
30.45	Dirt road, 20 ft. wide, bears N. 40° E. and S. 40° W.								
39.98	<p>Point for the 1/4 sec. cor. of secs. 9 and 16.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with brass cap mkd.</p>								
	<table style="margin-left: auto; margin-right: auto;"> <tr> <td>T 41 N</td> <td>R 28 E</td> </tr> <tr> <td></td> <td style="border-right: 1px solid black;">S 9</td> </tr> <tr> <td></td> <td style="border-right: 1px solid black;">1/4 ———</td> </tr> <tr> <td></td> <td style="border-right: 1px solid black;">S 16</td> </tr> </table>	T 41 N	R 28 E		S 9		1/4 ———		S 16
T 41 N	R 28 E								
	S 9								
	1/4 ———								
	S 16								
	2008								
	<p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p> <p>Set a steel "T-Post" fence post near cor.</p>								
54.45	Dirt road, 10 ft. wide, bears S. 40° E. and N. 40° W.								
70.30	East right-of-way fence, barbed wire, 5 strand, bears S. 20° E. and N. 20° W.								
71.90	Navajo Route 35, asphalt surfaced, 36 ft. wide, bears S. 20° E. and N. 20° W.								

**Survey of the Subdivisional Lines,
T. 41 N., R. 28 E., Gila and Salt River Meridian, Arizona**

CHAINS	
73.53	West right-of-way fence, barbed wire, 5 strand, bears S. 20° E. and N. 20° W.
73.80	Underground fiber optic line, bears S. 20° E. and N. 20° W.
79.96	The cor. of secs. 8, 9, 16 and 17. Land, gently rolling. Soil, fine sand. No timber; scattered native grasses.
	N. 0°03' W., bet. secs. 8 and 9. Over gently rolling terrain.
17.80	Underground fiber optic line, bears S. 20° E. and N. 20° W.
18.40	Southwest right-of-way fence, barbed wire, 5 strand, bears S. 20° E. and N. 20° W.
22.90	Navajo Route 35, asphalt surfaced, 36 ft. wide, bears S. 20° E. and N. 20° W.
27.63	Northeast right-of-way fence, barbed wire, 5 strand, bears S. 20° E. and N. 20° W.
40.00	Point for the 1/4 sec. cor. of secs. 8 and 9. Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 27 ins. in the ground, with brass cap mkd. <div style="text-align: center;"> T 41 N R 28 E 1/4 S 8 S 9 2008 </div> Deposit a magnet, in a white plastic case, at the base of the stainless steel post. Set a steel "T-Post" fence post near cor.
76.85	Graded road, 22 ft. wide, bears S. 70° E. and N. 70° W.
80.00	Point for the cor. of secs. 4, 5, 8 and 9. Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with brass cap mkd.

Survey of the Subdivisional Lines,
T. 41 N., R. 28 E., Gila and Salt River Meridian, Arizona

CHAINS	
	T 41 N R 28 E S 5 S 4 ———— S 8 S 9 2008
	Deposit a magnet, in a white plastic case, at the base of the stainless steel post. Set a steel "T-Post" fence post near cor. Land, gently rolling. Soil, fine sand. No timber; scattered native grasses.
	<hr/> From the cor. of secs. 3, 4, 9 and 10. S. 89°57' W., bet. secs. 4 and 9. Over gently rolling terrain.
30.25	Dirt road, 10 ft. wide, bears N. 60° E. and S. 60° W.
39.98	Point for the 1/4 sec. cor. of secs. 4 and 9. Set a brass tablet, 3 1/4 ins. diam., 3 1/2 ins. stem, cemented in a drill hole in solid rock, with top mkd.
	T 41 N R 28 E S 4 1/4 ——— S 9 2008
	From this cor. point, a drill hole casing, an iron pipe, 5 ins. diam., bears S. 48°15' W., 8.61 chs. dist., firmly set, projecting 4 ft. above ground, mkd. ARI-MEX. OIL & EXPLORATION INC NAVAJO E4 420 FNL 2310 FW SEC 9 T41N R28E APACHE CO ARIZONA. Cor. falls on south edge of a sandstone boulder, 6 x 4 x 4 ft. high.
46.30	Top of Bluff, bears N. 45° E. and S. 30° E.
79.96	The cor. of secs. 4, 5, 8 and 9. Land, gently rolling. Soil, fine sand. No timber; scattered native grasses.

**Survey of the Subdivisional Lines,
T. 41 N., R. 28 E., Gila and Salt River Meridian, Arizona**

CHAINS	
	N. 0°05' E., bet. secs. 4 and 5. Over rolling and broken terrain.
3.70	Underground petroleum pipe line, bears S. 60° E. and N. 60° W.
40.00	Point for the 1/4 sec. cor. of secs. 4 and 5. Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with brass cap mkd.
	T 41 N R 28 E 1/4 S 5 S 4 2008
	Deposit a magnet, in a white plastic case, at the base of the stainless steel post. Set a steel "T-Post" fence post near cor. Cor. falls SW of a stock pond.
80.14	The cor. of secs. 4, 5, 32 and 33, hereinbefore described. Land, rolling and broken. Soil, fine sand. No timber; scattered native grasses.
	From the stan. cor. of secs. 31 and 32, on the S. bdy. of the Tp., monumented with an iron post, 2 1/2 ins. diam., firmly set, projecting 1 in. above the ground, with mound of stone, 3 1/2 ft. base, 2 ft. high, N. of cor., with brass cap mkd. SC T41N R28E S31 S32 2006 1953, with no search made for the orig. bearing trees.
	N. 0°04' W., bet. secs. 31 and 32. Over broken and rolling terrain.
40.00	Point for the 1/4 sec. cor. of secs. 31 and 32. Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 25 ins. in the ground, with brass cap mkd.

**Survey of the Subdivisional Lines,
T. 41 N., R. 28 E., Gila and Salt River Meridian, Arizona**

CHAINS	
	T 41 N R 28 E 1/4 S 31 S 32 2008
	Deposit a magnet, in a white plastic case, at the base of the stainless steel post.
	Set a steel "T-Post" fence post near cor.
80.00	Point for the cor. of secs. 29, 30, 31 and 32. Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with brass cap mkd.
	T 41 N R 28 E S 30 S 29 S 31 S 32 2008
	Deposit a magnet, in a white plastic case, at the base of the stainless steel post.
	Set a steel "T-Post" fence post near cor.
	Land, rolling. Soil, fine sand. No timber; scattered native grasses.
	<hr/> From the cor. of secs. 28, 29, 32 and 33. N. 89°59' W., bet. secs. 29 and 32. Over gently rolling terrain.
37.25	Dirt road, 8 ft. wide, bears N. 25° E. and S. 25° W.
40.025	Point for the 1/4 sec. cor. of secs. 29 and 32. Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 25 ins. in the ground, with brass cap mkd.
	T 41 N R 28 E S 29 1/4 ——— S 32 2008

**Survey of the Subdivisional Lines,
T. 41 N., R. 28 E., Gila and Salt River Meridian, Arizona**

CHAINS	
	<p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p> <p>Set a steel "T-Post" fence post near cor.</p> <p>From this cor. point, a rebar, 5/8 in. diam., bears S. 82°12' E., 53 1/2 lks. dist., firmly set, projecting 2 ins. above ground, with no cap, of unknown origin.</p>
43.70	Dirt road, 8 ft. wide, bears S. 10° E. and N. 10° W.
80.05	<p>The cor. of secs. 29, 30, 31 and 32.</p> <p>Land, gently rolling. Soil, fine sand. No timber; scattered native grasses.</p> <hr/> <p>N. 89°59' W., bet. secs. 30 and 31.</p> <p>Over gently rolling terrain.</p>
40.00	<p>Point for the 1/4 sec. cor. of secs. 30 and 31.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 25 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center;"> <p>T 41 N R 28 E</p> <p>S 30</p> <p>1/4 ———</p> <p>S 31</p> <p>2008</p> </div> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p> <p>Set a steel "T-Post" fence post near cor.</p> <p>This cor. falls in a small drainage, 4 ft. wide, drains N. 20° E.</p>
79.86	<p>The cor. of secs. 25, 30, 31 and 36, on the W. bdy. of the Tp., hereinbefore described.</p> <p>Land, gently rolling. Soil, fine sand. Timber, scattered juniper; scattered native grasses.</p> <hr/> <p>From the cor. of secs. 29, 30, 31 and 32.</p> <p>N. 0°04' W., bet. secs. 29 and 30.</p>

**Survey of the Subdivisional Lines,
T. 41 N., R. 28 E., Gila and Salt River Meridian, Arizona**

CHAINS	
	Over gently rolling terrain.
32.85	Dirt road, 8 ft. wide, bears S. 55° E. and N. 55° W.
40.00	Point for the 1/4 sec. cor. of secs. 29 and 30. Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 25 ins. in the ground, with brass cap mkd. <div style="text-align: center;"> T 41 N R 28 E 1/4 S 30 S 29 2008 </div>
	Deposit a magnet, in a white plastic case, at the base of the stainless steel post.
	Set a steel "T-Post" fence post near cor.
80.00	Point for the cor. of secs. 19, 20, 29 and 30. Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 25 ins. in the ground, with brass cap mkd. <div style="text-align: center;"> T 41 N R 28 E S 19 S 20 S 30 S 29 2008 </div>
	Deposit a magnet, in a white plastic case, at the base of the stainless steel post.
	Set a steel "T-Post" fence post near cor.
	Land, gently rolling. Soil, fine sand. No timber; scattered native grasses.
	From the cor. of secs. 20, 21, 28 and 29. N. 89°59' W., bet. secs. 20 and 29. Over gently rolling terrain.
29.35	Dirt road, 12 ft. wide, bears N. 40° E. and S. 40° W.
40.025	Point for the 1/4 sec. cor. of secs. 20 and 29.

**Survey of the Subdivisional Lines,
T. 41 N., R. 28 E., Gila and Salt River Meridian, Arizona**

CHAINS	
	<p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T 41 N R 28 E S 20 1/4 ——— S 29</p> <p style="text-align: center;">2008</p> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p> <p>Set a steel "T-Post" fence post near cor.</p>
80.05	<p>The cor. of secs. 19, 20, 29 and 30.</p> <p>Land, gently rolling. Soil, fine sand. No timber; scattered native grasses.</p> <hr/> <p>N. 89°57' W., bet. secs. 19 and 30.</p> <p>Over gently rolling terrain.</p>
40.00	<p>Point for the 1/4 sec. cor. of secs. 19 and 30.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 25 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T 41 N R 28 E S 19 1/4 ——— S 30</p> <p style="text-align: center;">2008</p> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p> <p>Set a steel "T-Post" fence post near cor.</p>
51.95	<p>Dirt road, 8 ft. wide, bears N. 10° E. and S. 10° W.</p>
79.74	<p>The cor. of secs. 19, 24, 25 and 30, on the W. bdy. of the Tp., hereinbefore described.</p> <p>Land, gently rolling. Soil, fine sand. Timber, scattered juniper; scattered native grasses.</p> <hr/>

**Survey of the Subdivisional Lines,
T. 41 N., R. 28 E., Gila and Salt River Meridian, Arizona**

CHAINS	
	<p>From the cor. of secs. 19, 20, 29 and 30.</p> <p>N. 0°04' W., bet. secs. 19 and 20.</p> <p>Over gently rolling terrain.</p>
40.00	<p>Point for the 1/4 sec. cor. of secs. 19 and 20.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 27 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T 41 N R 28 E 1/4 S 19 S 20</p> <p style="text-align: center;">2008</p> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p> <p>Set a steel "T-Post" fence post near cor.</p>
64.70	<p>Dirt road, 8 ft. wide, bears S. 80° E. and N. 80° W.</p>
80.00	<p>Point for the cor. of secs. 17, 18, 19 and 20.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 27 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T 41 N R 28 E S 18 S 17 S 19 S 20</p> <p style="text-align: center;">2008</p> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p> <p>Set a steel "T-Post" fence post near cor.</p> <p>Land, gently rolling. Soil, fine sand. No timber; scattered native grasses.</p> <hr/> <p>From the cor. of secs. 16, 17, 20 and 21.</p> <p>N. 89°59' W., bet. secs. 17 and 20.</p> <p>Over gently rolling terrain.</p>
40.025	<p>Point for the 1/4 sec. cor. of secs. 17 and 20.</p>

**Survey of the Subdivisional Lines,
T. 41 N., R. 28 E., Gila and Salt River Meridian, Arizona**

CHAINS	
	<p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T 41 N R 28 E S 17 1/4 ——— S 20</p> <p style="text-align: center;">2008</p> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p> <p>Set a steel "T-Post" fence post near cor.</p>
53.75	Graded road, 20 ft. wide, bears N. 45° E. and S. 45° W.
80.05	The cor. of secs. 17, 18, 19 and 20.
	<p>Land, gently rolling. Soil, fine sand. No timber; scattered native grasses.</p> <hr/> <p>N. 89°57' W., bet. secs. 18 and 19.</p> <p>Over gently rolling terrain.</p>
22.50	Dirt road, 8 ft. wide, bears N. 40° E. and S. 40° W.
40.00	Point for the 1/4 sec. cor. of secs. 18 and 19.
	<p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T 41 N R 28 E S 18 1/4 ——— S 19</p> <p style="text-align: center;">2008</p> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p> <p>Set a steel "T-Post" fence post near cor.</p> <p>From this cor. point, a cor. set by persons unknown, bears N. 76°46' E., 25 lks. dist., monumented with an open ended iron pipe, 1 in. diam., firmly set, projecting 2 ins. above ground, with the marks 1/4 on its side.</p>

**Survey of the Subdivisional Lines,
T. 41 N., R. 28 E., Gila and Salt River Meridian, Arizona**

CHAINS	
79.62	<p>The cor. of secs. 13, 18, 19 and 24, on the W. bdy. of the Tp., hereinbefore described.</p> <p>Land, gently rolling. Soil, fine sand. No timber; scattered native grasses.</p> <hr/> <p>From the cor. of secs. 17, 18, 19 and 20. N. 0°04' W., bet. secs. 17 and 18. Over gently rolling terrain.</p>
16.05	High voltage transmission line, 5 wire, bears S. 86° E. and N. 86° W.
40.00	<p>Point for the 1/4 sec. cor. of secs. 17 and 18.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 25 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T 41 N R 28 E 1/4 S 18 S 17 2008</p> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p> <p>Set a steel "T-Post" fence post near cor.</p> <p>From this cor. point, a Department of Transportation (DOT) monument, bears N. 30°36' E., 4.665 chs. dist., monumented with a brass tablet, 3 ins. diam., set in a concrete cylinder, 6 ins. diam., firmly set, projecting 9 ins. above the ground, mkd. ARIZONA HIGHWAY DEPT 448.8 1961.</p>
44.12	South right-of-way fence, barbed wire, 5 strand, bears S. 88° E. and N. 88° W.
45.65	Interstate Highway No. 160, asphalt surfaced, 36 ft. wide, bears S. 88° E. and N. 88° W.
48.67	North right-of-way fence, barbed wire, 5 strand, bears S. 88° E. and N. 88° W.
65.10	Power line, 4 wire, bears S. 80° E. and N. 80° W.
67.40	Underground waterline, bears S. 65° E. and N. 65° W.
80.00	Point for the cor. of secs. 7, 8, 17 and 18.

Survey of the Subdivisional Lines,
T. 41 N., R. 28 E., Gila and Salt River Meridian, Arizona

CHAINS	
	<p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 25 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T 41 N R 28 E S 7 S 8 S 18 S 17</p> <p style="text-align: center;">2008</p> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p> <p>Set a steel "T-Post" fence post near cor.</p> <p>Land, gently rolling. Soil, fine sand. No timber; scattered native grasses.</p> <hr/> <p>From the cor. of secs. 8, 9, 16 and 17.</p> <p>N. 89°59' W., bet. secs. 8 and 17.</p> <p>Over gently rolling terrain.</p>
40.025	<p>Point for the 1/4 sec. cor. of secs. 8 and 17.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T 41 N R 28 E S 8 1/4 ——— S 17</p> <p style="text-align: center;">2008</p> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p> <p>Set a steel "T-Post" fence post near cor.</p>
80.05	<p>The cor. of secs. 7, 8, 17 and 18.</p> <p>Land, gently rolling. Soil, fine sand. No timber; scattered native grasses.</p> <hr/> <p>N. 89°56' W., bet. secs. 7 and 18.</p> <p>Over gently rolling terrain.</p>

**Survey of the Subdivisional Lines,
T. 41 N., R. 28 E., Gila and Salt River Meridian, Arizona**

CHAINS	
40.00	<p>Point for the 1/4 sec. cor. of secs. 7 and 18.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 25 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T 41 N R 28 E S 7 1/4 ——— S 18</p> <p style="text-align: center;">2008</p> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p> <p>Set a steel "T-Post" fence post near cor.</p>
47.15	Power line, 4 wire, bears S. 10° E. and N. 10° W.
48.30	Dirt road, 10 ft. wide, bears N. 20° E. and S. 20° W.
79.50	<p>The cor. of secs. 7, 12, 13 and 18, on the W. bdy. of the Tp., hereinbefore described.</p> <p>Land, gently rolling. Soil, fine sand. No timber; scattered native grasses.</p> <hr/> <p>From the cor. of secs. 7, 8, 17 and 18.</p> <p>N. 0°04' W., bet. secs. 7 and 8.</p> <p>Over gently rolling terrain.</p>
40.00	<p>Point for the 1/4 sec. cor. of secs. 7 and 8.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 27 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T 41 N R 28 E 1/4 S 7 S 8</p> <p style="text-align: center;">2008</p> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p> <p>Set a steel "T-Post" fence post near cor.</p>
80.00	Point for the cor. of secs. 5, 6, 7 and 8.

**Survey of the Subdivisional Lines,
T. 41 N., R. 28 E., Gila and Salt River Meridian, Arizona**

CHAINS							
	<p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 25 ins. in the ground, with brass cap mkd.</p>						
	<table style="margin: auto;"> <tr> <td>T 41 N</td> <td>R 28 E</td> </tr> <tr> <td style="border-right: 1px solid black;">S 6</td> <td>S 5</td> </tr> <tr> <td style="border-right: 1px solid black;">S 7</td> <td>S 8</td> </tr> </table>	T 41 N	R 28 E	S 6	S 5	S 7	S 8
T 41 N	R 28 E						
S 6	S 5						
S 7	S 8						
	2008						
	<p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p> <p>Set a steel "T-Post" fence post near cor.</p> <p>From this cor. point, a cor. set by persons unknown, bears N. 70°12' E., 31 lks. dist., monumented with an open ended iron pipe, 1 in. diam., firmly set, projecting 11 ins. above ground, with marks T41N 6 5 7 8 R28E on its northerly side and HO&R on its southerly side.</p> <p>Land, gently rolling. Soil, fine sand. No timber; scattered native grasses.</p> <hr/>						
	<p>From the cor. of secs. 4, 5, 8 and 9.</p> <p>N. 89°59' W., bet. secs. 5 and 8.</p> <p>Over gently rolling terrain.</p>						
11.20	Graded road, 20 ft. wide, bears S. 70° E. and N. 70° W.						
18.30	Northeast right-of-way fence, barbed wire, 5 strand, bears S. 20° E. and N. 20° W.						
19.90	Navajo Route 35, asphalt surfaced, 38 ft. wide, bears S. 20° E. and N. 20° W.						
21.50	Southwest right-of-way fence, barbed wire, 5 strand, bears S. 20° E. and N. 20° W.						
21.75	Underground fiber optic line, bears S. 20° E. and N. 20° W.						
40.025	Point for the 1/4 sec. cor. of secs. 5 and 8.						
	<p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 27 ins. in the ground, with brass cap mkd.</p>						

Survey of the Subdivisional Lines,
T. 41 N., R. 28 E., Gila and Salt River Meridian, Arizona

CHAINS	
	T 41 N R 28 E S 5 1/4 ——— S 8 2008
	Deposit a magnet, in a white plastic case, at the base of the stainless steel post. Set a steel "T-Post" fence post near cor.
80.05	The cor. of secs. 5, 6, 7 and 8. Land, gently rolling. Soil, fine sand. No timber; scattered native grasses.
	N. 89°56' W., bet. secs. 6 and 7. Over gently rolling terrain.
10.70	Dirt road, 8 ft. wide, bears S. 5° E. and N. 5° W.
22.05	Dirt road, 8 ft. wide, bears N. 30° E. and S. 30° W.
40.00	Point for the 1/4 sec. cor. of secs. 6 and 7. Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 27 ins. in the ground, with brass cap mkd.
	T 41 N R 28 E S 6 1/4 ——— S 7 2008
	Deposit a magnet, in a white plastic case, at the base of the stainless steel post. Set a steel "T-Post" fence post near cor.
66.85	Power line, 4 wire, bears S. 10° E. and N. 10° W.
67.00	Dirt road, 8 ft. wide, bears S. 10° E. and N. 10° W.
79.41	The cor. of secs. 1, 6, 7 and 12, on the W. bdy. of the Tp., hereinbefore described.

**Survey of the Subdivisional Lines,
T. 41 N., R. 28 E., Gila and Salt River Meridian, Arizona**

CHAINS	
	<p>Land, gently rolling. Soil, fine sand. No timber; scattered native grasses.</p> <hr/> <p>N. 0°05' E., bet. secs. 5 and 6.</p> <p>Over gently rolling terrain.</p>
26.00	Dirt road, 8 ft. wide, bears S. 60° E. and N. 80° W.
40.00	Point for the 1/4 sec. cor. of secs. 5 and 6.
	<p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 25 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T 41 N R 28 E 1/4 S 6 S 5 2008</p> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p> <p>Set a steel "T-Post" fence post near cor.</p>
54.50	Underground petroleum pipe line, bears S. 50° E. and N. 50° W.
66.45	Power line, 2 wire, bears N. 75° E. and S. 75° W.
68.50	Graded road, 15 ft. wide, bears N. 40° E. and S. 40° W.
80.12	The cor. of secs. 5, 6, 31 and 32, hereinbefore described.
	<p>Land, rolling and broken. Soil, fine sand. No timber; scattered native grasses.</p> <hr/> <p style="text-align: center;">Subdivision of Section 5, T. 41 N., R. 28 E., Gila and Salt River Meridian, Arizona</p> <hr/> <p>From the 1/4 sec. cor. of secs. 5 and 8.</p> <p>N. 0°06' E., on the N. and S. center line of sec. 5.</p>
10.90	Underground waterline, bears S. 70° E. and N. 70° W.
17.80	Dirt road, 20 ft. wide, bears E. and W.

**Subdivision of Section 5,
T. 41 N., R. 28 E., Gila and Salt River Meridian, Arizona**

CHAINS	
29.10	Underground petroleum pipe line, bears S. 55° E. and N. 55° W.
40.00	Point for the center 1/4 sec. cor. of sec. 5, at intersection with the E. and W. center line. Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 25 ins. in the ground, with brass cap mkd. T 41 N R 28 E C 1/4 S 5 2008 Deposit a magnet, in a white plastic case, at the base of the stainless steel post. Set a steel "T-Post" fence post near cor.
41.40	Power line, 2 wire, bears S. 35° E. and N. 35° W.
80.12	The 1/4 sec. cor. of secs. 5 and 32. <hr/>
	From the 1/4 sec. cor. of secs. 4 and 5. N. 89°59' W., on the E. and W. center line of sec. 5.
30.31	Northeast right-of-way fence, barbed wire, 5 strand, bears S. 10° E. and N. 10° W.
31.82	Navajo Route 35, asphalt surfaced, 36 ft. wide, bears S. 10° E. and N. 10° W.
32.85	Southwest right-of-way fence, barbed wire, 5 strand, bears N. 40° W. from intersection with a culvert.
39.10	Power line, 2 wire, bears S. 35° E. and N. 35° W.
40.005	The center 1/4 sec. cor. of sec. 5.
57.15	Underground petroleum pipe line, bears S. 55° E. and N. 55° W.
80.045	The 1/4 sec. cor. of secs. 5 and 6. <hr/>
	Subdivision of Section 8, T. 41 N., R. 28 E., Gila and Salt River Meridian, Arizona
	From the 1/4 sec. cor. of secs. 8 and 17. N. 0°03' W., on the N. and S. center line of sec. 8.

**Subdivision of Section 8,
T. 41 N., R. 28 E., Gila and Salt River Meridian, Arizona**

CHAINS	
40.00	<p>Point for the center 1/4 sec. cor. of sec. 8, at intersection with the E. and W. center line.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 25 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T 41 N R 28 E C 1/4 S 8</p> <p style="text-align: center;">2008</p> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p> <p>Set a steel "T-Post" fence post near cor.</p>
80.00	<p>The 1/4 sec. cor. of secs. 5 and 8.</p> <hr/> <p>From the 1/4 sec. cor. of secs. 8 and 9.</p> <p>N. 89°59' W., on the E. and W. center line of sec. 8.</p>
4.34	Northeast right-of-way fence, barbed wire, 5 strand, bears S. 20° E. and N. 20° W.
5.93	Navajo Route 35, asphalt surfaced, 36 ft. wide, bears S. 20° E. and N. 20° W.
7.53	Southwest right-of-way fence, barbed wire, 5 strand, bears S. 20° E. and N. 20° W.
7.75	Underground fiber optic line, bears S. 20° E. and N. 20° W.
40.025	The center 1/4 sec. cor. of sec. 8.
80.05	The 1/4 sec. cor. of secs. 7 and 8.
<p>Subdivision of Section 9, T. 41 N., R. 28 E., Gila and Salt River Meridian, Arizona</p> <hr/>	
40.00	<p>From the 1/4 sec. cor. of secs. 9 and 16.</p> <p>N. 0°03' W., on the N. and S. center line of sec. 9.</p> <p>Point for the center 1/4 sec. cor. of sec. 9, at intersection with the E. and W. center line.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 25 ins. in the ground, with brass cap mkd.</p>

**Subdivision of Section 9,
T. 41 N., R. 28 E., Gila and Salt River Meridian, Arizona**

CHAINS	
	T 41 N R 28 E C 1/4 S 9 2008
	Deposit a magnet, in a white plastic case, at the base of the stainless steel post.
	Set a steel "T-Post" fence post near cor.
	From this cor. point, a drill hole casing, an iron pipe, 5 ins. diam., bears N. 44°36' E., 14.11 chs. dist., firmly set, projecting 6 ft. above ground, mkd. MERRION OIL-GAS CORP NAVAJO E2 APACHE CO AZ 1980 FNL X 1980 FEL SEC 9 T41N R28E.
59.00	Graded road, 20 ft. wide, bears S. 65° E. and N. 65° W.
59.35	Underground petroleum pipe line, bears S. 65° E. and N. 65° W.
65.50	Top of Bluff, bears S. 70° E. and N. 40° W.
80.00	The 1/4 sec. cor. of secs. 4 and 9.
	<hr/>
	From the 1/4 sec. cor. of secs. 9 and 10.
	S. 89°57' W., on the E. and W. center line of sec. 9.
39.98	The center 1/4 sec. cor. of sec. 9.
79.96	The 1/4 sec. cor. of secs. 8 and 9.
	<hr/>
	Subdivision of Section 13, T. 41 N., R. 28 E., Gila and Salt River Meridian, Arizona
	From the 1/4 sec. cor. of secs. 13 and 24.
	N. 0°01' W., on the N. and S. center line of sec. 13.
2.65	Graded road, 12 ft. wide, bears N. 30° E. and S. 30° W.
4.26	South right-of-way fence, barbed wire, 5 strand, bears S. 69° E. and N. 69° W.
5.90	Interstate Highway No. 160, asphalt surfaced, 34 ft. wide, bears S. 69° E. and N. 69° W.
9.14	North right-of-way fence, barbed wire, 5 strand, bears S. 69° E. and N. 69° W.
23.30	Dirt road, 8 ft. wide, bears S. 55° E. and N. 55° W.

**Subdivision of Section 13,
T. 41 N., R. 28 E., Gila and Salt River Meridian, Arizona**

CHAINS	
35.40	Underground petroleum pipe line, bears S. 70° E. and N. 70° W.
40.01	Point for the center 1/4 sec. cor. of sec. 13, at intersection with the E. and W. center line. Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 25 ins. in the ground, with brass cap mkd. T 41 N R 28 E C 1/4 S 13 2008 Deposit a magnet, in a white plastic case, at the base of the stainless steel post. Set a steel "T-Post" fence post near cor.
80.02	The 1/4 sec. cor. of secs. 12 and 13. <hr/>
	From the 1/4 sec. cor. of secs. 13 and 18. S. 89°57' W., on the E. and W. center line of sec. 13.
40.035	The center 1/4 sec. cor. of sec. 13.
52.30	Underground petroleum pipe line, bears S. 70° E. and N. 70° W.
80.065	The 1/4 sec. cor. of secs. 13 and 14. <hr/>
	Subdivision of Section 14, T. 41 N., R. 28 E., Gila and Salt River Meridian, Arizona
	From the 1/4 sec. cor. of secs. 14 and 23. N. 0°02' W., on the N. and S. center line of sec. 14.
32.26	South right-of-way fence, barbed wire, 5 strand, bears S. 88° E. and N. 88° W.
33.80	Interstate Highway No. 160, asphalt surfaced, 34 ft. wide, bears S. 88° E. and N. 88° W.
36.83	North right-of-way fence, barbed wire, 5 strand, bears S. 88° E. and N. 88° W.
37.30	Power line, 4 wire, bears S. 85° E. and N. 85° W.

**Subdivision of Section 14,
T. 41 N., R. 28 E., Gila and Salt River Meridian, Arizona**

CHAINS	
40.00	Point for the center 1/4 sec. cor. of sec. 14, at intersection with the E. and W. center line. Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with brass cap mkd. T 41 N R 28 E C 1/4 S 14 2008 Deposit a magnet, in a white plastic case, at the base of the stainless steel post. Set a steel "T-Post" fence post near cor.
44.20	Graded road, 20 ft. wide, bears S. 20° E. and N. 20° W.
65.40	Underground petroleum pipe line, bears S. 75° E. and N. 75° W.
80.00	The 1/4 sec. cor. of secs. 11 and 14. <hr/>
	From the 1/4 sec. cor. of secs. 13 and 14. N. 89°59' W., on the E. and W. center line of sec. 14.
14.25	Dirt road, 10 ft. wide, bears N. 80° E. and S. 80° W.
27.35	Power line, 4 wire, bears N. 60° E. and S. 60° W.
31.30	Dirt road, 10 ft. wide, bears N. 45° E. and S. 45° W.
37.05	Graded road, 20 ft. wide, bears S. 40° E. and N. 40° W.
40.025	The center 1/4 sec. cor. of sec. 14.
80.05	The 1/4 sec. cor. of secs. 14 and 15. <hr/>
	Subdivision of Section 15, T. 41 N., R. 28 E., Gila and Salt River Meridian, Arizona
	From the 1/4 sec. cor. of secs. 15 and 22. N. 0°02' W., on the N. and S. center line of sec. 15.
35.74	South right-of-way fence, barbed wire, 5 strand, bears S. 88° E. and N. 88° W.
37.25	Interstate Highway No. 160, asphalt surfaced, 34 ft. wide, bears S. 88° E. and N. 88° W.

**Subdivision of Section 15,
T. 41 N., R. 28 E., Gila and Salt River Meridian, Arizona**

CHAINS	
40.27	North right-of-way fence, barbed wire, 5 strand, bears S. 88° E. and N. 88° W.
40.00	Point for the center 1/4 sec. cor. of sec. 15, at intersection with the E. and W. center line. Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with brass cap mkd. T 41 N R 28 E C 1/4 S 15 2008 Deposit a magnet, in a white plastic case, at the base of the stainless steel post. Set a steel "T-Post" fence post near cor.
40.60	Power line, 4 wire, bears S. 85° E. and N. 85° W.
80.00	The 1/4 sec. cor. of secs. 10 and 15. <hr/>
	From the 1/4 sec. cor. of secs. 14 and 15. N. 89°58' W., on the E. and W. center line of sec. 15.
25.35	Power line, 4 wire, bears S. 85° E. and N. 85° W.
33.55	North right-of-way fence, barbed wire, 5 strand, bears S. 88° E. and N. 88° W.
40.06	The center 1/4 sec. cor. of sec. 15.
80.12	The 1/4 sec. cor. of secs. 15 and 16. <hr/>
	Subdivision of Section 16, T. 41 N., R. 28 E., Gila and Salt River Meridian, Arizona
	From the 1/4 sec. cor. of secs. 16 and 21. N. 0°03' W., on the N. and S. center line of sec. 16.
8.35	High voltage transmission line, 5 wire, bears S. 85° E. and N. 85° W.
25.80	Dirt road, 10 ft. wide, bears S. 80° E. and N. 80° W.

**Subdivision of Section 16,
T. 41 N., R. 28 E., Gila and Salt River Meridian, Arizona**

CHAINS	
39.10	South right-of-way fence, barbed wire, 5 strand, bears S. 88° E. and N. 88° W.
40.00	Point for the center 1/4 sec. cor. of sec. 16, at intersection with the E. and W. center line. Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with brass cap mkd. T 41 N R 28 E C 1/4 S 16 2008 Deposit a magnet, in a white plastic case, at the base of the stainless steel post.
40.65	Interstate Highway No. 160, asphalt surfaced, 34 ft. wide, bears S. 88° E. and N. 88° W.
43.65	North right-of-way fence, barbed wire, 5 strand, bears S. 88° E. and N. 88° W.
46.055	Intersect line 1-2, Tract 38, not monumented. Cor. No. 1 bears S. 47°25' W., 3.42 chs. dist., hereinafter described.
67.845	Intersect line 3-4, Tract 38, not monumented. Cor. No. 3 bears N. 47°25' E., 6.795 chs. dist., hereinafter described.
69.30	Graded road, 20 ft. wide, bears N. 45° E. and S. 45° W.
80.00	The 1/4 sec. cor. of secs. 9 and 16. <hr/>
	From the 1/4 sec. cor. of secs. 15 and 16. S. 89°57' W., on the E. and W. center line of sec. 16.
25.25	Interstate Highway No. 160, asphalt surfaced, 34 ft. wide, bears S. 88° E. and N. 88° W.
39.98	The center 1/4 sec. cor. of sec. 16.
61.23	Southwest right-of-way fence, barbed wire, 5 strand, bears S. 88° E. and N. 88° W.
64.00	Navajo Route 35, asphalt surfaced, 24 ft. wide, bears S. 10° E. and N. 10° W.

**Subdivision of Section 16,
T. 41 N., R. 28 E., Gila and Salt River Meridian, Arizona**

CHAINS	
79.96	The 1/4 sec. cor. of secs. 16 and 17.
<hr/> <p>Subdivision of Section 17, T. 41 N., R. 28 E., Gila and Salt River Meridian, Arizona</p> <hr/>	
	From the 1/4 sec. cor. of secs. 17 and 20.
	N. 0°03' W., on the N. and S. center line of sec. 17.
13.50	High voltage transmission line, 5 wire, bears S. 85° E. and N. 85° W.
20.15	Dirt road, 22 ft. wide, bears N. 30° E. and S. 30° W.
40.00	Point for the center 1/4 sec. cor. of sec. 17, at intersection with the E. and W. center line.
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with brass cap mkd.
	T 41 N R 28 E C 1/4 S 17 2008
	Deposit a magnet, in a white plastic case, at the base of the stainless steel post.
	Set a steel "T-Post" fence post near cor.
42.46	South right-of-way fence, barbed wire, 5 strand, bears S. 88° E. and N. 88° W.
44.00	Interstate Highway No. 160, asphalt surfaced, 34 ft. wide, bears S. 88° E. and N. 88° W.
47.00	North right-of-way fence, barbed wire, 5 strand, bears S. 88° E. and N. 88° W.
58.20	Power line, 4 wire, bears S. 80° E. and N. 80° W.
80.00	The 1/4 sec. cor. of secs. 8 and 17.
<hr/>	
	From the 1/4 sec. cor. of secs. 16 and 17.
	N. 89°59' W., on the E. and W. center line of sec. 17.
27.55	Dirt road, 20 ft. wide, bears N. 40° E. and S. 40° W.
40.025	The center 1/4 sec. cor. of sec. 17.

**Subdivision of Section 17,
T. 41 N., R. 28 E., Gila and Salt River Meridian, Arizona**

CHAINS	
80.05	The 1/4 sec. cor. of secs. 17 and 18.
<hr/> <p>Subdivision of Section 18, T. 41 N., R. 28 E., Gila and Salt River Meridian, Arizona</p> <hr/>	
	From the 1/4 sec. cor. of secs. 18 and 19.
	N. 0°04' W., on the N. and S. center line of sec. 18.
18.55	High voltage transmission line, 5 wire, bears S. 85° E. and N. 85° W.
40.01	Point for the center 1/4 sec. cor. of sec. 18, at intersection with the E. and W. center line.
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with brass cap mkd.
	T 41 N R 28 E C 1/4 S 18
	2008
	Deposit a magnet, in a white plastic case, at the base of the stainless steel post.
	Set a steel "T-Post" fence post near cor.
45.74	South right-of-way fence, barbed wire, 5 strand, bears S. 88° E. and N. 88° W.
47.30	Interstate Highway No. 160, asphalt surfaced, 34 ft. wide, bears S. 88° E. and N. 88° W.
50.30	North right-of-way fence, chain link, 7 ft. high, bears S. 88° E. and N. 88° W.
66.15	Power line, 4 wire, bears S. 80° E. and N. 80° W.
71.95	Power line, 4 wire, bears S. 80° E. and N. 80° W.
80.01	The 1/4 sec. cor. of secs. 7 and 18.
	From the 1/4 sec. cor. of secs. 17 and 18.
	N. 89°56' W., on the E. and W. center line of sec. 18.
40.00	The center 1/4 sec. cor. of sec. 18.

**Subdivision of Section 18,
T. 41 N., R. 28 E., Gila and Salt River Meridian, Arizona**

CHAINS	
79.56	The 1/4 sec. cor. of secs. 13 and 18.
<hr/> <p>Subdivision of Section 24, T. 41 N., R. 28 E., Gila and Salt River Meridian, Arizona</p> <hr/>	
	From the 1/4 sec. cor. of secs. 24 and 25.
	N. 0°01' W., on the N. and S. center line of sec. 24.
39.15	High voltage transmission line, 5 wire, bears S. 75° E. and N. 75° W.
40.01	Point for the center 1/4 sec. cor. of sec. 24, at intersection with the E. and W. center line.
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with brass cap mkd.
	T 41 N R 28 E C 1/4 S 24 2008
	Deposit a magnet, in a white plastic case, at the base of the stainless steel post.
	Set a steel "T-Post" fence post near cor.
80.02	The 1/4 sec. cor. of secs. 13 and 24.
<hr/>	
	From the 1/4 sec. cor. of secs. 19 and 24.
	S. 89°58' W., on the E. and W. center line of sec. 24.
40.035	The center 1/4 sec. cor. of sec. 24.
43.80	High voltage transmission line, 5 wire, bears S. 75° E. and N. 75° W.
77.00	Dirt road, 10 ft. wide, bears N. 45° E. and S. 45° W.

**Subdivision of Section 24,
T. 41 N., R. 28 E., Gila and Salt River Meridian, Arizona**

CHAINS							
80.07	<p>The 1/4 sec. cor. of secs. 23 and 24.</p> <hr/> <p style="text-align: center;">Survey of Tract 37, T. 41 N., R. 28 E., Gila and Salt River Meridian, Arizona</p> <hr/> <p>Note: A survey depicting this tract of land entitled "Proposed Red Mesa Montezuma Creek Health Center and Staff Quarters", was surveyed by Robert Jack Smith, Arizona Registered Land Surveyor, RLS-5439, for Surveying Control, Inc., in 1999.</p> <p>From Angle Point No. 1, Tract 37, monumented with an iron rebar, 5/8 in. diam., firmly set, flush with the ground, with alum. cap mkd. AZ 5439.</p> <p>At the angle point</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 27 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T 41 N R 28 E</p> <div style="text-align: center;"> <table style="margin-left: auto; margin-right: auto;"> <tr> <td></td> <td style="text-align: right;">S 15</td> </tr> <tr> <td style="border-right: 1px solid black; padding-right: 5px;">AP 1</td> <td></td> </tr> <tr> <td style="border-right: 1px solid black; padding-right: 5px;">TR 37</td> <td></td> </tr> </table> </div> <p style="text-align: center;">2008</p> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p> <p>Deposit the iron rebar, 5/8 in. diam., 18 ins. long, with alum. cap, inside the stainless steel post.</p> <p>Set a steel "T-Post" fence post near the angle point.</p> <p>N. 87°37' W., on line 1-2, Tract 37.</p> <p>Over nearly level terrain.</p>		S 15	AP 1		TR 37	
	S 15						
AP 1							
TR 37							
16.49	<p>Angle Point No. 2, Tract 37, monumented with an iron rebar, 5/8 in. diam., firmly set, 2 ins. below the ground, with alum. cap mkd. AZ 5439, and with a "T-post" fence post nearby.</p> <p>At the angle point</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 28 ins. in the ground, with brass cap mkd.</p>						

**Survey of Tract 37,
T. 41 N., R. 28 E., Gila and Salt River Meridian, Arizona**

CHAINS			
	<p>T 41 N R 28 E</p> <p>S 15</p> <table border="1" style="margin-left: auto; margin-right: auto;"> <tr><td>AP 2</td></tr> <tr><td>TR 37</td></tr> </table> <p>2008</p> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p> <p>Deposit the iron rebar, 5/8 in. diam., 18 ins. long, with alum. cap, inside the stainless steel post.</p> <hr style="width: 20%; margin: 10px auto;"/> <p>S. 2°22' W., on line 2-3, Tract 37.</p> <p>Over nearly level terrain.</p>	AP 2	TR 37
AP 2			
TR 37			
3.375	Intersect the line bet. secs. 15 and 16.		
9.095	<p>Angle Point No. 3, Tract 37, monumented with an iron rebar, 5/8 in. diam., firmly set, projecting 1 in. above the ground, with alum. cap mkd. AZ 5439.</p> <p>At the angle point</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 25 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T 41 N R 28 E</p> <table border="1" style="margin-left: auto; margin-right: auto;"> <tr><td>TR 37</td></tr> <tr><td>AP 3</td></tr> </table> <p style="text-align: center;">S 16</p> <p style="text-align: center;">2008</p> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p> <p>Deposit the iron rebar, 5/8 in. diam., 18 ins. long, with alum. cap, inside the stainless steel post.</p> <p>Set a steel "T-Post" fence post near the angle point.</p> <p>From this angle point, the 1/4 sec. cor. of secs. 15 and 16, bears S. 7°03' E., 1.97 chs. dist., hereinbefore described.</p> <hr style="width: 20%; margin: 10px auto;"/> <p>S. 87°36' E., on line 3-4, Tract 37.</p> <p>Over nearly level terrain.</p>	TR 37	AP 3
TR 37			
AP 3			

**Survey of Tract 37,
T. 41 N., R. 28 E., Gila and Salt River Meridian, Arizona**

CHAINS					
0.24	Intersect the line bet. secs. 15 and 16.				
16.495	<p>Angle Point No. 4, Tract 37, monumented with an iron rebar, 5/8 in. diam., firmly set, flush with the ground, with alum. cap mkd. AZ 5439.</p> <p>At the angle point</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 27 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center;"> <p>T 41 N R 28 E</p> <table border="1" style="margin: auto;"> <tr> <td style="padding: 2px;">TR 37</td> <td style="padding: 2px;"> </td> </tr> <tr> <td style="padding: 2px;">AP 4</td> <td style="padding: 2px;"> </td> </tr> </table> <p style="margin-top: 10px;">S 15 2008</p> </div> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p> <p>Deposit the iron rebar, 5/8 in. diam., 18 ins. long, with alum. cap, inside the stainless steel post.</p> <p>Set a steel "T-Post" fence post near the angle point.</p> <hr style="width: 20%; margin: 10px auto;"/> <p>N. 2°22' E., on line 4-1, Tract 37.</p> <p>Over nearly level terrain.</p>	TR 37		AP 4	
TR 37					
AP 4					
0.53	A cor. of the Red Mesa Unified School District No. 27 Proposed High School Site, monumented with an iron rebar, 5/8 in. diam., firmly set, projecting 1 in. above the ground, with a yellow plastic cap mkd. S. TOLER AZ 38746.				
9.905	Angle Point No. 1, and point of beginning.				
	<hr/> <p>Survey of Tract 38, T. 41 N., R. 28 E., Gila and Salt River Meridian, Arizona</p> <hr/>				
	<p>Note: The following entitled surveys depict this tract of land:</p> <p style="padding-left: 40px;">"Tract Survey for Montezuma Health Facility", was surveyed by Harold Baldwin, Arizona Registered Land Surveyor, RLS-19810, for San Juan Engineers, in 1990.</p>				

**Survey of Tract 38,
T. 41 N., R. 28 E., Gila and Salt River Meridian, Arizona**

CHAINS	
	<p>"Proposed Red Mesa Montezuma Creek Health Center and Staff Quarters", was surveyed by Robert Jack Smith, Arizona Registered Land Surveyor, RLS-5439, for Surveying Control, Inc., in 1999.</p> <p>"Plat of Survey of Red Mesa Montezuma Creek Staff Quarters Site", was surveyed by Stephen J. Toler, Arizona Registered Land Surveyor, RLS-38746, for Surveying Control, Inc., in 2003.</p> <p>From Angle Point No. 1, Tract 38, monumented with an iron rebar, 1/2 in. diam., firmly set, 3 ins. below ground, with a yellow plastic cap, not mkd.</p> <p>At the angle point</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 25 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center;"> <p>T 41 N R 28 E</p> <p>TR 38 /</p> <p>AP 1 /</p> <hr style="width: 10%; margin: 0 auto;"/> <p>S 16</p> <p>2008</p> </div> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p> <p>Deposit the iron rebar, 1/2 in. diam., 18 ins. long, with alum. cap, inside the stainless steel post.</p> <p>Angle point falls in the North right-of-way fence line of Highway No. 160, and easterly of an intersecting fence line that encompasses the staff quarters site for the health clinic.</p> <p>From this angle point, the center 1/4 sec. cor. of sec. 16, bears S. 33°58' E., 4.515 chs. dist., hereinbefore described.</p> <p>N. 47°25' E., on line 1-2, Tract 38.</p> <p>Over fairly level terrain, along a fence line.</p> <p>3.42 Intersect the N. and S. center line of sec. 16.</p> <p>24.94 Angle Point No. 2, Tract 38, monumented with an iron rebar, 5/8 in. diam., firmly set, flush with the ground, with alum. cap mkd. AZ 5439.</p> <p>At the angle point</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 27 ins. in the ground, with brass cap mkd.</p>

**Survey of Tract 38,
T. 41 N., R. 28 E., Gila and Salt River Meridian, Arizona**

CHAINS

T 41 N R 28 E
 AP 2 S 16
 TR 38

2008

Deposit a magnet, in a white plastic case, at the base of the stainless steel post.

Deposit the iron rebar, 5/8 in. diam., 18 ins. long, with alum. cap, inside the stainless steel post.

Angle point falls near a cor. of fences encompassing the staff quarters site for the health clinic.

From this angle point, angle point No. 2, Tract 37, bears S. 68°32' E., 26.08 chs. dist., hereinbefore described.

N. 42°34' W., on line 2-3, Tract 38.

Over nearly level terrain, along a fence line.

16.055

Angle Point No. 3, Tract 38, monumented with an iron rebar, 5/8 in. diam., firmly set, flush with the ground, with alum. cap mkd. AZ 5439.

At the angle point

Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with brass cap mkd.

T 41 N R 28 E
 S 16
 AP 3
 TR 38

2008

Deposit a magnet, in a white plastic case, at the base of the stainless steel post.

Deposit the iron rebar, 5/8 in. diam., 18 ins. long, with alum. cap, inside the stainless steel post.

Angle point falls near a cor. of fences encompassing the staff quarters site for the health clinic.

**Survey of Tract 38,
T. 41 N., R. 28 E., Gila and Salt River Meridian, Arizona**

CHAINS	
	<p>S. 47°25' W., on line 3-4, Tract 38.</p> <p>Over nearly level terrain, along a fence line.</p>
6.795	Intersect the N. and S. center line of sec. 16.
19.565	<p>Point for Angle Point No. 4, Tract 38, at proportionate position between the northwest cor. of the Health Center Site (Angle Point No. 5), and the point for the northeast cor. of the Health Center Site. This point falls in a cattle guard, where it is impracticable to establish a permanent monument.</p> <p>From this true point, the point selected for an off line witness cor. bears S. 44°36' E., 50 lks. dist.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center;"> <p>WC T 41 N R 28 E S 16 AP 4 TR 38</p> <p>2008</p> </div> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p> <p>Set a steel "T-Post" fence post near the witness cor.</p> <p>From this true point, the point for the northeast cor. of the Health Center Site, determined by Grant Boundary Method, bears S. 87°35' E., 7.555 chs. dist., not monumented. The cor. of a house falls on this position.</p> <hr style="width: 30%; margin: 10px auto;"/>
	<p>N. 87°35' W., on line 4-5, Tract 38.</p> <p>Over nearly level terrain, along a fence line.</p>
12.235	<p>Angle Point No. 5, Tract 38, monumented with an iron rebar, 5/8 in. diam., firmly set, flush with the ground, with alum. cap mkd. 2000 NMPS 11599.</p> <p>At the angle point</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with brass cap mkd.</p>

**Survey of Tract 38,
T. 41 N., R. 28 E., Gila and Salt River Meridian, Arizona**

CHAINS					
	T 41 N R 28 E S 16 <table style="margin-left: auto; margin-right: auto; border-collapse: collapse;"> <tr> <td style="border-right: 1px solid black; border-bottom: 1px solid black; padding: 2px 5px;">AP 5</td> <td style="border-bottom: 1px solid black; padding: 2px 5px;"></td> </tr> <tr> <td style="border-right: 1px solid black; padding: 2px 5px;">TR 38</td> <td style="padding: 2px 5px;"></td> </tr> </table>	AP 5		TR 38	
AP 5					
TR 38					
	2008				
	<p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p> <p>Deposit the iron rebar, 5/8 in. diam., 18 ins. long, with alum. cap, inside the stainless steel post.</p> <p>Angle point falls 2 1/2 lks. westerly of a steel water cap, 9 ins. diam., in a concrete base, 2 x 2 ft., projecting 2 ins. above ground.</p> <p>From this angle point, the northwest cor. of the Access Withdrawal, bears N. 87°39' W., 1.85 chs. dist., monumented with an iron rebar, 5/8 in. diam., firmly set, flush with the ground, with no cap.</p> <hr style="width: 30%; margin: 10px auto;"/> <p>S. 2°28' W., on line 5-6, Tract 38.</p> <p>Over nearly level terrain, along a fence line.</p>				
12.80	<p>B.I.A. Roads, PT STA. 145+19.05, monumented with a brass tablet, 3 ins. diam., set in a concrete cylinder, 6 ins. diam., firmly set, projecting 2 ins. above the ground, mkd. B.I.A. ROADS 19. This point is designated as Angle Point No. 6, Tract 38.</p> <hr style="width: 30%; margin: 10px auto;"/> <p>S. 2°30' W., on line 6-7, Tract 38, identical with a portion of the easterly right-of-way of Navajo Route 35.</p> <p>Over nearly level terrain, along a fence line.</p>				
2.355	<p>B.I.A. Roads, PI STA. 146+70.71, monumented with a brass tablet, 3 ins. diam., set in a concrete cylinder, 6 ins. diam., firmly set, projecting 6 ins. above the ground, mkd. B.I.A. ROADS 449.95 19. This point is designated as Angle Point No. 7, Tract 38.</p> <hr style="width: 30%; margin: 10px auto;"/> <p>S. 87°35' E., on line 7-1, Tract 38, identical with a portion of the north right-of-way of Highway 160.</p> <p>Over nearly level terrain, along a fence line.</p>				

**Survey of Tract 38,
T. 41 N., R. 28 E., Gila and Salt River Meridian, Arizona**

CHAINS	
19.80	<p>Angle Point No. 1, Tract 38, and point of beginning.</p> <hr/> <p style="text-align: center;">Informational Traverse of the Red Mesa Trading Post, in Section 17, T. 41 N., R. 28 E., Gila and Salt River Meridian, Arizona</p> <hr/> <p>Note: A survey depicting this tract of land entitled "4 Acre Tract Survey for Bradley Blair" (Red Mesa Trading Post), was surveyed by James P. Leese, Arizona Registered Land Surveyor, RLS-1849, in 1961.</p> <p>From the southeast cor. of the Red Mesa Trading Post, monumented with an iron rebar, 1/2 in. diam., firmly set, flush with the ground, with a red plastic cap.</p> <p>From this cor. point, the 1/4 sec. cor. of secs. 16 and 17, bears S. 33°48' E., 6.62 chs. dist., hereinbefore described.</p> <p>N. 87°37' W., on the south boundary.</p> <p>Over nearly level terrain.</p>
6.325	<p>Southwest cor. of the Red Mesa Trading Post, monumented with an iron rebar, 1/2 in. diam., firmly set, projecting 1 in. above the ground, with a red plastic cap.</p> <p>This cor. falls near the cor. of barbed wire fences, extending N. 2° E. and S. 88° E.</p> <hr/> <p>N. 2°25' E., on the west boundary.</p> <p>Over nearly level terrain, along a fence line.</p>
6.33	<p>Northwest cor. of the Red Mesa Trading Post, monumented with an open ended iron pipe, 1 in. diam., firmly set, projecting 7 ins. above the ground.</p> <p>This cor. falls alongside a wood post cor. of fences, extending S. 88 E. and S. 2° W.</p> <hr/> <p>S. 87°33' E., on the north boundary.</p> <p>Over nearly level terrain.</p>
6.32	<p>Northeast cor. of the Red Mesa Trading Post, monumented with an iron rebar, 1/2 in. diam., firmly set, 1 in. below the ground, with a red plastic cap mkd. NMLS 12163 AZLS 29894.</p>

**Informational Traverse of the
Red Mesa Trading Post, in Section 17,
T. 41 N., R. 28 E., Gila and Salt River Meridian, Arizona**

CHAINS	
6.32	<p>This cor. falls near a wood post cor. of fences, extending S. 2° W. and N. 88° W.</p> <hr style="width: 20%; margin: auto;"/> <p>S. 2°21' W., on the east boundary.</p> <p>Over nearly level terrain.</p> <p>Southeast cor. of the Red Mesa Trading Post, and point of beginning.</p> <hr style="width: 20%; margin: auto;"/> <p>There is a structure within these boundaries that is a small general store and gas station.</p> <hr style="width: 20%; margin: auto;"/> <p style="text-align: center;">Informational Traverse of the Red Mesa Trading Post Addition, in Section 16, T. 41 N., R. 28 E., Gila and Salt River Meridian, Arizona</p> <hr style="width: 20%; margin: auto;"/> <p>Note: A survey depicting this tract of land entitled "Boundary Survey - Red Mesa 501-SE", was surveyed by Michael Daly, Arizona Registered Land Surveyor, RLS-15083, for Arrow Engineers, in 2007, and was recorded at the Apache County Records Office, Book No. 17LS, Page 40 (1 of 2), in 2007.</p> <p>From the northwest cor. of the Red Mesa Post Addition, at the intersection of the south right-of-way of Highway 160 with the east right-of-way of Navajo Route 35, monumented with a concrete filled iron pipe, 2 1/2 ins. diam., firmly set, projecting 5 ins. above the ground, with a brass tag mkd. LS 15083 set in the concrete.</p> <p>From this cor. point, the 1/4 sec. cor. of secs. 16 and 17, bears S. 89°46' W., 17.435 chs. dist., hereinbefore described.</p> <p>From this same cor. point, a B.I.A. Shiprock Roads point, bears S. 87°06' E., 74 1/2 lks. dist. monumented with an iron rebar, 5/8 in. diam., firmly set, 5 ins. below the ground, with an alum. cap mkd. B.I.A. SHIPROCK ROADS.</p> <p>S. 87°37' E., on the north boundary.</p> <p>Over nearly level terrain, along the south right-of-way fence of Highway 160.</p>
7.27	<p>Northeast cor. of the Red Mesa Trading Post Addition, monumented with a concrete filled iron pipe, 2 1/2 ins. diam., firmly set, projecting 4 ins. above the ground, with a brass tag mkd. LS 15083 set in the concrete.</p> <p>There is a "T-post" fence post near the cor.</p>

**Informational Traverse of the
Red Mesa Trading Post Addition, in Section 16,
T. 41 N., R. 28 E., Gila and Salt River Meridian, Arizona**

CHAINS	
	<p>This cor. falls in the south right-of-way fence line of Highway 160.</p> <hr style="width: 20%; margin: auto;"/> <p>S. 2°23' W., on the east boundary.</p> <p>Over nearly level terrain.</p>
4.85	<p>Southeast cor. of the Red Mesa Trading Post Addition, monumented with a concrete filled iron pipe, 2 1/2 ins. diam., firmly set, projecting 6 ins. above the ground, with a brass tag mkd. LS 15083 set in the concrete.</p> <p>There is a "T-post" fence post near the cor.</p> <hr style="width: 20%; margin: auto;"/> <p>N. 87°37' W., on the south boundary.</p> <p>Over nearly level terrain.</p>
6.80	<p>Southwest cor. of the Red Mesa Trading Post Addition, monumented with a concrete filled iron pipe, 2 1/2 ins. diam., firmly set, projecting 1 in. above the ground, with a brass tag mkd. LS 15083 set in the concrete.</p> <p>From this cor. point, a B.I.A. Shiprock Roads point, bears S. 27°32' E., 2.85 chs. dist., monumented with an iron rebar, 5/8 in. diam., firmly set, projecting 2 ins. above the ground, with an alum. cap mkd. B.I.A. SHIPROCK ROADS.</p> <p>There is a "T-post" fence post near the cor.</p> <hr style="width: 20%; margin: auto;"/> <p>The west boundary of this parcel was not resurveyed. There are no structures on this parcel.</p> <hr style="width: 20%; margin: auto;"/> <p style="text-align: center;">Informational Traverse of the Sewer Lagoon Extension, in Section 17, T. 41 N., R. 28 E., Gila and Salt River Meridian, Arizona</p> <hr style="width: 20%; margin: auto;"/> <p>Note: A survey depicting this tract of land entitled "Tract Survey for Montezuma Health Facility", was surveyed by Harold Baldwin, Arizona Registered Land Surveyor, RLS-19810, for San Juan Engineers, in 1990.</p> <p>From the northeast cor. of the Sewer Lagoon Extension, monumented with an angle iron fence cor., 6 ft. high, at the southeast cor. of existing sewer lagoons.</p>

**Informational Traverse of the
Sewer Lagoon Extension, in Section 17,
T. 41 N., R. 28 E., Gila and Salt River Meridian, Arizona**

CHAINS	
	<p>From this cor. point, the 1/4 sec. cor. of secs. 16 and 17, bears N. 47°54' E., 12.72 chs. dist., hereinbefore described.</p> <p>S. 3°16' W., on the east boundary.</p> <p>Over nearly level terrain.</p>
3.79	<p>Southeast cor. of the Sewer Lagoon Extension, monumented with an iron rebar, 1/2 in. diam., firmly set, projecting 1 in. above the ground, with a plastic cap.</p> <hr style="width: 20%; margin: 10px auto;"/> <p>N. 87°19' W., on the south boundary.</p> <p>Over nearly level terrain.</p>
6.885	<p>Southwest cor. of the Sewer Lagoon Extension, monumented with an iron rebar, 1/2 in. diam., firmly set, projecting 1 in. above the ground, with a plastic cap.</p> <hr style="width: 20%; margin: 10px auto;"/> <p>N. 2°09' E., on the west boundary.</p> <p>Over nearly level terrain.</p>
3.79	<p>Northwest cor. of the Sewer Lagoon Extension, monumented with an angle iron fence cor., 6 ft. high, at the southwest cor. of existing sewer lagoons.</p> <hr style="width: 20%; margin: 10px auto;"/> <p>S. 87°19' E., on the north boundary, along existing sewer lagoons.</p> <p>Over nearly level terrain.</p>
6.96	<p>The northeast cor. of the Sewer Lagoon Extension, and point of beginning.</p> <hr style="width: 20%; margin: 10px auto;"/> <p style="text-align: center;">Informational Traverse of the Red Mesa Unified School District No. 27 Proposed High School Site, in Section 15, T. 41 N., R. 28 E., Gila and Salt River Meridian, Arizona</p> <hr style="width: 20%; margin: 10px auto;"/> <p>Note: A survey depicting this tract of land entitled "Red Mesa Unified School District No. 27 Proposed High School Site", was surveyed by Stephen J. Toler, Arizona Registered Land Surveyor, RLS-38746, for Surveying Control, Inc., in 2008.</p> <p>From Angle Point No. 2, Tract 37, hereinbefore described, which is identical with a cor. of the Red Mesa Unified School District No. 27 Proposed High School Site.</p>

**Informational Traverse of the Red Mesa Unified School
District No. 27 Proposed High School Site, in Section 15,
T. 41 N., R. 28 E., Gila and Salt River Meridian, Arizona**

CHAINS	
	<p>N. 2°24' E., on the west boundary.</p> <p>Over nearly level to gently rolling terrain.</p>
42.90	<p>Northwesterly cor. of the Red Mesa Unified School District No. 27 Proposed High School Site, monumented with an iron rebar, 5/8 in. diam., firmly set, projecting 1 in. above the ground, with a yellow plastic cap mkd. S. TOLER AZ 38746.</p> <hr/>
	<p>N. 62°49' E., on the north boundary.</p> <p>Over nearly level to gently rolling terrain.</p>
17.145	<p>Most northerly cor. of the Red Mesa Unified School District No. 27 Proposed High School Site, monumented with an iron rebar, 5/8 in. diam., firmly set, projecting 1 in. above the ground, with a yellow plastic cap mkd. S. TOLER AZ 38746.</p> <hr/>
	<p>S. 64°16' E., on the north boundary.</p> <p>Over nearly level to gently rolling terrain.</p>
26.065	<p>Northeast cor. of the Red Mesa Unified School District No 27 Proposed High School Site, monumented with an iron rebar, 5/8 in. diam., firmly set, projecting 1 in. above the ground, with a yellow plastic cap mkd. S. TOLER AZ 38746.</p> <hr/>
	<p>S. 2°24' W., on the east boundary.</p> <p>Over nearly level to gently rolling terrain.</p>
49.60	<p>Southeast cor. of the Red Mesa Unified School District No. 27 Proposed High School Site, monumented with an iron rebar, 5/8 in. diam., firmly set, projecting 1 in. above the ground, with a yellow plastic cap mkd. S. TOLER AZ 38746.</p> <hr/>
	<p>N. 87°36' W., on the south boundary.</p> <p>Over nearly level to gently rolling terrain.</p>

**Informational Traverse of the Red Mesa Unified School
District No. 27 Proposed High School Site, in Section 15,
T. 41 N., R. 28 E., Gila and Salt River Meridian, Arizona**

CHAINS	
22.35	<p>A cor. of the Red Mesa Unified School District No. 27 Proposed High School Site, on line 4-1, Tract 37, hereinbefore described.</p> <hr/> <p align="center">Informational Traverse of the Red Mesa School, in Section 18, T. 41 N., R. 28 E., Gila and Salt River Meridian, Arizona</p> <hr/> <p>From the southwest cor. of the school property, marked with a fence cor. of a cyclone fence, 6 ft. high. There is no evidence of any monumentation at this point.</p> <p>From this cor. point, the center 1/4 sec. cor. of sec. 18, bears S. 44°27' E., 15.02 chs. dist.</p> <p>N. 2°10' E., on the west boundary.</p> <p>Over nearly level to gently rolling terrain.</p>
15.13	<p>Northwest cor. of the school property, marked with a fence cor. of a cyclone fence, 6 ft. high. There is no evidence of any monumentation at this point.</p> <hr/> <p>S. 87°40' E., on the north boundary.</p> <p>Over nearly level to gently rolling terrain.</p>
33.09	<p>Northeast cor. of the school property, marked with a fence cor. of a wire fence, 5 ft. high. There is no evidence of any monumentation at this point.</p> <hr/> <p>S. 2°25' W., on the east boundary.</p> <p>Over nearly level to gently rolling terrain.</p>
15.145	<p>Southeast cor. of the school property, marked with a fence cor. of a wire fence, 5 ft. high. There is no evidence of any monumentation at this point.</p> <hr/> <p>N. 87°39' W., on the south boundary.</p> <p>Over nearly level to gently rolling terrain.</p>
33.025	<p>Southwest cor. of the school property and point of beginning.</p> <hr/> <p>This area encompasses the current Red Mesa school.</p> <hr/>

T. 41 N., R. 28 E., Gila and Salt River Meridian, Arizona

CHAINS

GENERAL DESCRIPTION

The terrain is mostly level to gently rolling desert, with broken and rugged land toward the northern and southern portions of the township. A portion of Toh Atin Mesa is located in the southwest cor. of the township, and a portion of Red Mesa is located in the middle of the northern part of the township. There is an unnamed mesa in the northeast corner of the township.

The elevation varies from 5,300 to 6,300 feet above sea level. The soil is mostly fine sand with areas of sandstone outcrops and ledges. There is scattered juniper at the higher elevations, with sagebrush, cacti, greasewood and native grasses undergrowth throughout the township.

Highway 160 runs easterly and westerly through the township, and Navajo Route 35 runs northerly and southerly. There are multiple graded and dirt roads throughout the township.

The mean magnetic declination of 11° E. was derived from the United States Geological Survey computer program GEOMAG, utilizing the World Magnetic Model for Epoch 2005 for the dates of survey.

CERTIFICATE OF SURVEY

I, Craig S. Dukart, Cadastral Surveyor, HEREBY CERTIFY upon honor, that in pursuance of special instructions bearing date of the 1st day of May, 2008, and supplemental special instructions bearing the date of the 3rd day of June, 2008, I have dependently resurveyed the Seventh Guide Meridian East (east boundary), the west and north boundaries, and the survey of the subdivisional lines, the subdivision of certain sections, tracts 37 and 38, and informative traverses, T. 41 N., R. 28 E., of the Gila and Salt River Meridian, in the State of Arizona, which are represented in the foregoing field notes as having been executed by me and under my direction. Said survey has been made in strict conformity with said special instructions, the Manual of Instructions for the Survey of the Public Lands of the United States, 1973, and in specific manner described in the foregoing field notes.

02/26/09

(Date)



(Cadastral Surveyor)


CERTIFICATE OF APPROVAL

BUREAU OF LAND MANAGEMENT
Phoenix, Arizona

The foregoing field notes of the dependent resurvey of the Seventh Guide Meridian East (east boundary), the west and north boundaries, and the survey of the subdivisional lines, the subdivision of certain sections, tracts 37 and 38, and informative traverses, T. 41 N., R. 28 E., Gila and Salt River Meridian, in the State of Arizona, executed by Craig S. Dukart, Cadastral Surveyor, having been critically examined and found correct, are hereby approved.

6/3/2009

(Date)



(Chief Cadastral Surveyor of Arizona)

 CERTIFICATE OF TRANSCRIPT

I CERTIFY That the foregoing transcript of the field notes of the above described surveys in T. 41 N., R. 28 E., Gila and Salt River Meridian, Arizona, is a true copy of the original field notes.

 (Date)

 (Chief Cadastral Surveyor of Arizona)