

ORIGINAL

**UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT**

FIELD NOTES

OF THE

DEPENDENT RESURVEY OF A PORTION OF THE
THIRD STANDARD PARALLEL NORTH (SOUTH BOUNDARY),

A PORTION OF THE SUBDIVISIONAL LINES,

A PORTION OF THE FORT WHIPPLE TIMBER RESERVE,

AND PATENTED MINING CLAIMS, MINERAL SURVEY NOS. 2129 and 4226,

AND

THE SUBDIVISION OF SECTIONS 27, 28, 34 AND 35

OF

TOWNSHIP 13 NORTH, RANGE 2 WEST,

OF THE GILA AND SALT RIVER MERIDIAN,

IN THE STATE OF ARIZONA.

EXECUTED BY

Craig S. Dukart, Cadastral Surveyor

Under Special Instructions dated July 11, 2007, approved July 11, 2007, which provided for the surveys included under Group No. 1022, and assignment instructions dated September 10, 2007.

Survey commenced September 17, 2007

Survey completed January 24, 2008

INDEX DIAGRAM

TOWNSHIP 13 NORTH RANGE 2 WEST
 GILA AND SALT RIVER MERIDIAN, ARIZONA

6	5	4	3	2	1
7	8	9	10	11	12
18	17	16	15	14	13
19	20	21 22	22 19	23	24
30	29 21	28 17	27 12 15	26	25
31	32	33	34 8 6	11 35 4	36

Dep. Res. Por. of Subdivision of Secs. 34 & 35 Pages 23-28
 Dep. Res. of Mineral Survey No. 2129 Pages 28-31
 Dep. Res. Por. of Mineral Survey No. 4226 Pages 31-34
 Subdivision of Secs. 27, 28, 34 & 35 Pages 34-56

T. 13 N., R. 2 W., Gila and Salt River Meridian, Arizona

CHAINS

The following field notes describe the dependent resurvey of a portion of the Third Standard Parallel North (south boundary), a portion of the subdivisional lines, a portion of the Fort Whipple Timber Reserve and patented mining claims, Mineral Survey Nos. 2129 and 4226, and the subdivision of sections 27, 28, 34 and 35, Township 13 North, Range 2 West, Gila and Salt River Meridian, Arizona.

The history of surveys pertaining to this survey is as follows:

The east, south and west boundaries of Township 13 North, Range 2 West, Gila and Salt River Meridian, were surveyed by Omar H. Case, U. S. Deputy Surveyor, in 1871.

The subdivisional lines of Township 13 North, Range 2 West, Gila and Salt River Meridian, were surveyed by Omar H. Case, U. S. Deputy Surveyor, in 1871.

Mineral Survey No. 2129, within sections 34 and 35, Township 13 North, Range 2 West, Gila and Salt River Meridian, was surveyed by John J. Fisher, U. S. Deputy Mineral Surveyor, in 1905.

The dependent resurvey of a portion of the Third Parallel North, Mineral Survey No. 2129, part of the subdivisional lines, and the survey of the boundary of Fort Whipple Timber Reserve in sections 33, 34 and 35, Township 13 North, Range 2 West, Gila and Salt River Meridian, were surveyed by David W. Eaton, U. S. Transitman, in 1918.

The dependent resurvey of a portion of the 3rd Standard Parallel North, east, west and north boundaries, and part of the subdivisional lines of Township 13 North, Range 2 West, Gila and Salt River Meridian, were surveyed by Benjamin J. Kinsey, U. S. Surveyor, in 1930.

Mineral Survey No. 4226, within section 34, Township 13 North, Range 2 West, Gila and Salt River Meridian, was surveyed by Richard L. Merritt, G. L. O. Mineral Surveyor, in 1940.

The retracement of the Third Standard Parallel North, Township 13 North, Range 2 West, and the survey of the subdivisional lines of fractional Township 12 1/2 North, Range 2 West, Gila and Salt River Meridian, were surveyed by Paul G. Bauer, Cadastral Surveyor, in 1964.

The dependent resurvey of the south boundary and the retacement of the south 1/2 of the west boundary and survey of a partial subdivision of section 29, Township 13 North, Range 2 West, Gila and Salt River Meridian, were surveyed by Gary T. Oviatt and Louis D. Gilbert, Cadastral Surveyors, in 1967.

T. 13 N., R. 2 W., Gila and Salt River Meridian, Arizona

CHAINS

The survey was executed in accordance with the specifications as set forth in the Manual of Instructions for the Survey of the Public Lands of the United States, 1973, and the Special Instructions dated July 11, 2007, for Group Number 1022, Arizona.

The true meridian direction and length of all lines were determined by real time kinematic global positioning system observations using Trimble Navigation 5800 model receivers.

Geodetic control was derived from Global Positioning System (GPS) static observations post processed by National Geodetic Survey, Online Positioning User Service (OPUS), utilizing Continuously Operating Reference Stations (CORS) FERN FERNO MESA CORS ARP, FST1 FLAGSTAFF 1 CORS ARP, AND AZAH ASHLER HILLS CORS ARP. The geographic position of the standard 1/4 section corner of section 35 is as follows:

Latitude: 34°27'11.15" N. Longitude: 112°26'12.10" W.

The mean magnetic declination is 11 3/4° E.

**Dependent Resurvey of a Portion of the Third
Standard Parallel North (South Boundary),
T. 13 N., R. 2 W., Gila and Salt River Meridian, Arizona**


Restoring the dependent resurveys executed by
David W. Eaton, in 1918, Benjamin J. Kinsey, in 1930
and Paul G. Bauer, in 1964

Beginning at the stan. 1/4 sec. cor. of sec. 35, monumented with an oak tree, 8 1/2 ins. diam., with a healed blaze/scar, 14 ins. long, beginning 2 ft. above the ground, on the easterly side of the tree, and a healed blaze/scar, 6 ins. long, beginning 1 1/2 ft. above the ground on the westerly side of the tree. The tree is encircled with stones.

From this cor. point, an iron post, 1 in. diam., loosely set, projecting 24 ins. above ground, in a mound of stone, 2 1/2 ft. base, 1 ft. high, with a brass cap mkd. 1/4 SC S35 1964 1918, oriented towards the south, bears West, 3 lks. dist. A steel fence post is set alongside the iron post, with a "Land Survey Monument" sign attached. Note: This iron post will now function as a reference monument.

Replace the iron post with a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with brass cap mkd.

**Dependent Resurvey of a Portion of the Third
Standard Parallel North (South Boundary),
T. 13 N., R. 2 W., Gila and Salt River Meridian, Arizona**

CHAINS	
	RM T 13 N R 2 W SC 1/4 S35 1.5 FT.  TO COR. 2007
	Deposit a magnet, in a white plastic case, at the base of the stainless steel post.
	Bury the iron post horizontally alongside the stainless steel post.
	Build a semi circle collar of stone around the oak corner tree.
	S. 89°09' W., along the S. bdy. of sec. 35.
	Over rolling terrain, through pine timber and scrub oak.
14.45	Senator Highway, a dirt road, 24 ft. wide, bears S. 20° E. and N. 20° W.
20.60	The stan. W. 1/16 sec. cor. of sec. 35, identical with Cor. No. 6 of the Fort Whipple Timber Reserve, monumented with an iron post, 2 ins. diam., firmly set, projecting 17 ins. above the ground, with a brass cap mkd. T13N R2W SC FWTR NO 6 W 1/16 S35 1964 1918, from which the only remaining bearing tree mkd. in 1918
	A pine, 20 ins. diam., bears N. 14° W., 47 lks. dist., with healed blaze.
	A steel fence post is set alongside the iron post, with a "Land Survey Monument" sign attached.
	Add the marks 2007 to the brass cap.
	From this cor. point, cor. No. 6, Black Horse lode, Mineral Survey No. 914, bears S. 25°18' W., 2.552 chs. dist., monumented with a stone, 14 x 9 ins., projecting 10 ins. above the ground, with chiseled marks BH No 6 on the NW face and a chiseled X on top. A pile of stones lies to the NW of this cor., with a rebar in the middle of it.
	<hr style="width: 20%; margin: 0 auto;"/>
	S. 89°16' W., beginning new measurement, continuing along the S. bdy. of sec. 35, now identical with a portion of line 5-6, Fort Whipple Timber Reserve.

**Dependent Resurvey of a Portion of the Third
Standard Parallel North (South Boundary),
T. 13 N., R. 2 W., Gila and Salt River Meridian, Arizona**

CHAINS	
20.62	<p>The stan. sec. cor. of secs. 34 and 35, identical with an angle point on line 5-6, Fort Whipple Timber Reserve, monumented with an iron post, 3 ins. diam., leaning heavily in a small mound of stone, with a brass cap mkd. T13N R2W FWTR SC AP S34 S35 1964 1918, with no evidence of the orig. stone monument found, from which the remaining bearing trees mkd. in 1918</p> <p style="padding-left: 40px;">An oak, 9 ins. diam., bears N. 52 1/4° E., 52 lks. dist., with healed blaze. (Record: N. 51° E., 55 lks.)</p> <p style="padding-left: 40px;">A pine, 33 ins. diam., bears S. 10 1/4° E., 30 lks. dist., with healed blaze. (Record: S. 12° E., 27 lks.)</p> <p>A steel fence post is set alongside the iron post, with a "Land Survey Monument" sign attached.</p> <p>At the corner point</p> <p>Reset the iron post, 36 ins. long, 3 ins. diam., 25 ins. in the ground, and in a mound of stone, 3 ft. base, to brass cap, and add the marks 2007 to the brass cap, and new accessories</p> <p style="padding-left: 40px;">The marks X BO on a granite outcrop, 3 1/2 x 3 x 1 1/2 ft., bears N. 38° E., 76 1/2 lks. dist.</p> <p style="padding-left: 40px;">A drill hole, 3/4 in. diam., 1 in. deep and marks BO on a granite outcrop, 3 x 2 1/2 x 1 1/2 ft., bears S. 69 1/2° E., 2.344 chs. dist.</p> <p style="padding-left: 40px;">The marks X BO on a granite outcrop, 7 x 3 1/2 x 1 ft., bears S. 8° W., 2.543 chs. dist.</p> <p>Land, rolling. Soil, decomposed granite. Timber, pine and oak.</p> <hr/> <p>N. 88°47' W., along the S. bdy. of sec. 34, identical with a portion of line 5-6, Fort Whipple Timber Reserve.</p> <p>Over rolling terrain, through pine timber and scrub oak.</p>
13.145	<p>From this point, the closing cor. of secs. 22 and 23, T. 12 1/2 N., R. 2 W., bears S., 4 1/2 lks. dist. monumented with an iron post, 2 1/2 ins. diam., firmly set, projecting 12 ins. above the ground, in a mound of stone, 3 ft. base to brass cap mkd. T13N R2W S34 T12 1/2 N R2W S22 S23 CC 1964, from which the 1964 bearing trees</p> <p style="padding-left: 40px;">A pine, 16 ins. diam., bears S. 68 1/2° E., 34 lks. dist., with a portion of scribe marks 23 BT visible on a partially healed blaze. (Record: S. 66° E.)</p>

**Dependent Resurvey of a Portion of the Third
Standard Parallel North (South Boundary),
T. 13 N., R. 2 W., Gila and Salt River Meridian, Arizona**

CHAINS	<p style="text-align: center;">An oak, 13 ins. diam., bears S. 69° W., 75 1/2 lks. dist., with a healed blaze. (Record: 78 lks.)</p>
19.595	<p>Point for the stan. E. 1/16 sec. cor. of sec. 34.</p> <p>Set an alum. post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with alum. cap mkd.</p> <p style="text-align: center;">SC T 13 N R 2 W</p> <p style="text-align: center;"><u>E 1/16 S34</u></p> <p style="text-align: center;">2007</p> <p>from which</p> <p style="text-align: center;">A pine, 10 ins. diam., bears N. 48 3/4° E., 64 1/2 lks. dist., mkd. X BT.</p> <p style="text-align: center;">The marks X B0 on a granite boulder, 6 x 4 1/2 x 5 ft., bears N. 52 1/4° W., 86 1/2 lks. dist. The X is 3 1/2 ft. above the ground.</p> <p>Deposit a magnet, in a white plastic case, at the base of the alum. post.</p> <p>Set a steel fence post nearby, with a "Land Survey Monument" sign attached to it.</p>
39.19	<p>The stan. 1/4 sec. cor. of sec. 34, monumented with a stone, 14 x 8 ins., projecting 14 ins. above the ground, mkd. 1/4 S on S. face, from which the remains of the bearing trees mkd. in 1918</p> <p style="text-align: center;">A rotted stump, bears N. 6 1/2° E., 27 1/2 lks. dist., with no evidence of a blaze or scribing. (Record: N. 6° E., 26 lks.)</p> <p style="text-align: center;">A cut stump, bears S. 27 1/2° W., 80 lks. dist., with no evidence of a blaze or scribing.</p> <p>A steel fence post is set alongside the iron post, with a "Land Survey Monument" sign attached.</p> <p>At the corner point</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 27 ins. in the ground, with alum. cap mkd.</p>

**Dependent Resurvey of a Portion of the Third
Standard Parallel North (South Boundary),
T. 13 N., R. 2 W., Gila and Salt River Meridian, Arizona**

CHAINS	<p style="text-align: center;">SC T 13 N R 2 W <u>1/4 S 34</u></p> <p style="text-align: center;">2007</p> <p>and new accessories</p> <p style="padding-left: 40px;">The marks X BO on a granite outcrop, 5 x 4 x 2 ft., bears S. 48 1/2° W., 79 lks. dist.</p> <p style="padding-left: 40px;">The marks X BO on a granite boulder, 4 1/2 x 3 x 2 1/2 ft., bears N. 48 1/2° W., 86 lks. dist.</p> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p> <p>Bury the orig. stone monument alongside the stainless steel post.</p> <p>There was no evidence of the iron post set in the 1918 survey and recovered in the 1964 survey.</p> <p>Land, rolling. Soil, decomposed granite. Timber, pine and oak.</p> <hr/> <p style="text-align: center;">Dependent Resurvey of a Portion of the Subdivisional Lines, T. 13 N., R. 2 W., Gila and Salt River Meridian, Arizona</p> <hr/> <p style="text-align: center;">Restoring the dependent resurveys executed by David W. Eaton, in 1918 and Benjamin J. Kinsey, in 1930</p> <hr/> <p>From the stan. cor. of secs. 34 and 35, on the S. bdy. of the Tp., hereinbefore described.</p> <p>N. 1°30' E., bet. secs. 34 and 35.</p> <p>Over rolling terrain, through pine timber and scrub oak.</p> <p>20.515 Point for the S. 1/16 sec. cor. of secs. 34 and 35.</p> <p>Set an alum. post, 28 ins. long, 2 1/2 ins. diam., 27 ins. in the ground, with alum. cap mkd.</p>
--------	---

**Dependent Resurvey of a Portion of the Subdivisional Lines,
T. 13 N., R. 2 W., Gila and Salt River Meridian, Arizona**

CHAINS	
	<p align="center">T 13 N R 2 W S 1/16 S 34 S 35 2007</p>
	<p>from which</p>
	<p>A pine, 11 ins. diam., bears S. 23 1/4° E., 39 lks. dist., mkd. S1/16 S35 BT.</p>
	<p>The marks X BO on a granite slab, 3 1/2 x 8 x 5 1/2 ft., bears S. 84 3/4° W., 84 lks. dist. The X is 4.3 ft. above the ground. This slab is alongside and southerly of another granite slab, 3 x 6 x 7 ft.</p>
	<p>Deposit a magnet, in a white plastic case, at the base of the alum. post.</p>
	<p>Set a steel fence post nearby, with "Land Survey Monument" and "Property Boundary" signs attached to it.</p>
22.55	<p>Wolf Creek road, a dirt road, 14 ft. wide, bears N. 70° E. and S. 60° W.</p>
30.49	<p>Intersect line 3-4, Lost Chance lode, M.S. No. 2129, at a point from which cor. No. 3 bears S. 35°19' E., 11.05 chs. dist., hereinafter described, not monumented.</p>
41.03	<p>The 1/4 sec. cor. of secs. 34 and 35, determined at record bearing and distance from the only remaining bearing tree mkd. in 1918</p>
	<p>A pine, 20 ins. diam., bears S. 74° W., 71 lks. dist., with a scribed 4 clearly visible in a "popped" portion of the completely healed blaze.</p>
	<p>At the corner point</p>
	<p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 31 ins. in the ground, with brass cap mkd.</p>
	<p align="center">T 13 N R 2 W 1/4 S 34 S 35 2007</p>
	<p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p>

**Dependent Resurvey of a Portion of the Subdivisional Lines,
T. 13 N., R. 2 W., Gila and Salt River Meridian, Arizona**

CHAINS	
	<p>This cor. falls in a well trafficked area of the Sky-Y camp. The popped open blaze of the bearing tree was covered with a piece of plexi glass by the camp handy man.</p> <hr style="width: 20%; margin: 10px auto;"/>
	<p>N. 1°36' E., beginning new measurement.</p>
4.04	<p>Intersect line 4-1, Lost Chance lode, M.S. No. 2129, at a point from which cor. No. 1 bears N. 54°02' E., 0.31 chs. dist., hereinafter described, not monumented.</p>
10.24	<p>Point for the S-N 1/64 sec. cor. of secs. 34 and 35.</p>
	<p>Set an alum. post, 28 ins. long, 2 1/2 ins. diam., 27 ins. in the ground, with alum. cap mkd.</p>
	<p style="text-align: center;">T 13 N R 2 W S-N 1/64 S 34 S 35 2007</p>
	<p>Deposit a magnet, in a white plastic case, at the base of the alum. post.</p>
	<p>Set a steel fence post nearby, with "Land Survey Monument" and "Property Boundary" signs attached to it.</p>
20.48	<p>Point for the N. 1/16 sec. cor. of secs. 34 and 35.</p>
	<p>Set an alum. post, 28 ins. long, 2 1/2 ins. diam., 30 ins. in the ground, with alum. cap mkd.</p>
	<p style="text-align: center;">T 13 N R 2 W N 1/16 S 34 S 35 2007</p>
	<p>from which</p>
	<p>A pine, 20 ins. diam., bears N. 83 1/2° E., 47 lks. dist., mkd. N1/16 S35 BT.</p>
	<p>The marks X B0 on a granite boulder, 8 x 4 x 2 1/2 ft., bears N. 25 1/2° W., 38 1/2 lks. dist.</p>

**Dependent Resurvey of a Portion of the Subdivisional Lines,
T. 13 N., R. 2 W., Gila and Salt River Meridian, Arizona**

CHAINS	<p>Deposit a magnet, in a white plastic case, at the base of the alum. post.</p> <p>This cor. falls in the vicinity of camp site No. 36, of the Groom Creek Horse Camp, a Forest Service Campground.</p>
40.96	<p>The cor. of secs. 26, 27, 34 and 35, identical with an angle point on line 1-2, Fort Whipple Timber Reserve, monumented with an iron post, 2 ins. diam., firmly set, projecting 18 ins. above the ground, with a brass cap mkd. T13N R2W S27 S26 S34 S35 AP WTR 1918, from which there is no remaining evidence of the orig. bearing trees or the bearing trees mkd. in 1918.</p> <p>A steel fence post is set alongside the iron post, with a "Land Survey Monument" sign attached.</p> <p>At the corner point</p> <p>Rebuild the supporting mound of stone, 4 ft. base to cap, and add the marks 2007 to brass cap, and new accessories</p> <p style="padding-left: 40px;">The marks X BO on a granite outcrop, 75 ft. long, and 15 ft. high, bears N. $4\frac{1}{4}^{\circ}$ E., 1.04 chs. dist. The X is 2 ft. above the ground.</p> <p style="padding-left: 40px;">The marks X BO on a granite rock, 5 x 5 x 2 $\frac{1}{2}$ ft., bears S. $74\frac{3}{4}^{\circ}$ E., 92 $\frac{1}{2}$ lks. dist. The X is 2 ft. above the ground.</p> <p>The 1918 field notes for this cor. say that they set the iron post alongside the orig. stone monument. We found the remains of a panel point underneath the mound of stone, indicating that the mound of stone, and possibly the orig. stone, had been disturbed. We were unable to find the orig. stone monument.</p> <p>Land, rolling. Soil, decomposed granite. Timber, pine and oak.</p> <hr/> <p>From the $\frac{1}{4}$ sec. cor. of secs. 26 and 35, monumented with an iron post, 1 in. diam., firmly set in concrete, projecting 28 ins. above the ground, with brass cap mkd. $\frac{1}{4}$ S26 S35 1918, with no evidence of the orig. stone monument, the orig. bearing trees or of the bearing trees mkd. in 1918.</p> <p>A steel fence post is set alongside the iron post, with a "Land Survey Monument" sign attached.</p> <p>At the corner point</p> <p>Build a supporting mound of stone, 3 ft. base, to cap, and add the marks T13N R2W and 2007 to the brass cap, and new accessories</p>

**Dependent Resurvey of a Portion of the Subdivisional Lines,
T. 13 N., R. 2 W., Gila and Salt River Meridian, Arizona**

CHAINS	
	<p>The marks X BO on a granite outcrop, 60 x 30 ft., 15 ft. high, bears N. 60 3/4° E., 57 1/2 lks. dist. The X is 2 ft. below top of outcrop.</p> <p>The marks X BO on a granite boulder, 5 x 5 x 3 ft., bears S. 5° E., 31 1/2 lks. dist. The X is on top of the boulder.</p> <p>N. 89°22' W., bet. secs. 26 and 35.</p> <p>Over rolling terrain, through pine timber and scrub oak.</p>
11.70	<p>Senator Highway, asphalt surfaced, 24 ft. wide, bears N. 30° E. and S. 30° W.</p>
19.30	<p>The W. 1/16 sec. cor. of secs. 26 and 35, identical with cor. No. 1, Fort Whipple Timber Reserve, monumented with an iron post, 2 ins. diam., firmly set, projecting 19 ins. above the ground, with a brass cap mkd. T13N R2W W1/16 S26 S35 AP FWTR 1918. No evidence of the mound of stone was found.</p> <p>A steel fence post is set alongside the iron post, with a "Land Survey Monument" sign attached.</p> <p>At the corner point</p> <p>Build a supporting mound of stone, 3 ft. base to cap, and add the marks 2007 to brass cap.</p> <hr/> <p>N. 88°33' W., beginning new measurement, continuing bet. secs. 26 and 35, identical with a portion of line 1-6, Fort Whipple Timber Reserve.</p>
19.36	<p>The cor. of secs. 26, 27, 34 and 35, identical with an angle point on line 1-2, Fort Whipple Timber Reserve.</p> <p>Land, rolling. Soil, decomposed granite. Timber, pine and oak.</p> <hr/> <p>N. 0°33' E., bet. secs. 26 and 27.</p> <p>Over rolling terrain, through pine timber and scrub oak.</p>

**Dependent Resurvey of a Portion of the Subdivisional Lines,
T. 13 N., R. 2 W., Gila and Salt River Meridian, Arizona**

CHAINS	
20.62	<p>The S. 1/16 sec. cor. of secs. 26 and 27, established by William J. Cheek, Registered Civil Engineer, in 1972, according to Plat 16-94 (Pine Hills), filed at the Yavapai County Courthouse, dated September 18, 1972, and accepted as the true cor. by Linda S. Smith, Arizona R.L.S. No. 18554, in 1986, according to Arizona Land Survey Monument Record, Instrument No. 11617, Book 1807, Page 417, filed at the Yavapai County Courthouse, dated April 2, 1986, monumented with an alum. post, 2 1/2 ins. diam., firmly set, projecting 14 ins. above the ground, with alum. cap mkd. T13N R2W S1/16 S27 S26 18554 1986. This is accepted as a careful and faithful establishment of the cor. position, from which the bearing trees mkd. in 1986</p> <p style="padding-left: 40px;">A pine, 19 ins. diam., bears S. 63° W., 32 1/2 lks. dist., with scribe marks S1/16 S26/S27 BT visible on a partially healed blaze.</p> <p style="padding-left: 40px;">A pine, 15 ins. diam., bears N. 36 1/2° W., 27 1/2 lks. dist., with scribe marks X BT visible on a partially healed low blaze.</p> <p>Add the marks 2007 to the alum. cap.</p> <hr style="width: 20%; margin: 10px auto;"/> <p>N. 0°25' E., beginning new measurement.</p>
4.31	<p>Cor. of lots 11 and 12, Pine Hills, monumented with an iron rebar, 1/2 in. diam., firmly set, projecting 2 ins. above the ground, with a plastic cap mkd. LS 15331.</p> <p>A steel fence post is set alongside the iron rebar, with a "Property Boundary" sign attached.</p>
5.92	<p>Cor. of lots 7 and 11, Pine Hills Subdivision, monumented with an iron rebar, 1/2 in. diam., firmly set, projecting 1 in. above the ground, with a plastic cap mkd. LS 15331.</p> <p>A steel fence post is set alongside the iron rebar, with a "Property Boundary" sign attached.</p>
11.225	<p>Cor. of lots 6 and 7, Pine Hills Subdivision, monumented with an iron rebar, 1/2 in. diam., firmly set, projecting 11 ins. above the ground, with a slight lean.</p> <p>A steel fence post is set alongside the iron rebar, with a "Property Boundary" sign attached.</p>
11.68	<p>An iron rebar, 1/2 in. diam., firmly set, projecting 11 ins. above the ground, set by persons unknown.</p> <p>A steel fence post is set alongside the iron rebar, with a "Property Boundary" sign attached.</p>

**Dependent Resurvey of a Portion of the Subdivisional Lines,
T. 13 N., R. 2 W., Gila and Salt River Meridian, Arizona**

CHAINS	
12.88	<p>Point for a 1/1024 sec. cor. of secs. 26 and 27.</p> <p>Set an alum. post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with alum. cap mkd.</p> <p align="center">T 13 N R 2 W</p> <p align="center">1/1024</p> <p align="center">2007</p> <p>Deposit a magnet, in a white plastic case, at the base of the alum. post.</p> <p>Set a steel fence post nearby, with "Property Boundary" sign attached to it.</p>
13.91	<p>An iron rebar, 1/2 in. diam., firmly set, projecting 12 ins. above the ground, set by persons unknown.</p>
14.15	<p>Friendly Pines road, a dirt road, 16 ft. wide, bears N. 45° E. and S. 60° W.</p>
14.68	<p>Northerly right-of-way of Friendly Pines Road, identical with the northwesterly cor. of Pine Hills, monumented with an iron rebar, 1/2 in. diam., firmly set, 2 ins. below the ground.</p> <p>A steel fence post is set alongside the iron rebar, with a "Property Boundary" sign attached.</p>
17.80	<p>Intersect southerly side of garage, 20 x 14 ft., attached to house, at a point S. 73° E., 2.2 lks. dist., from the SW cor., long side bears N. 17° E.</p>
17.87	<p>Intersect westerly side of same garage at a point S. 17° W., 23.3 lks. dist. from the NW cor.</p>
18.12	<p>Intersect southerly side of an irregularly shaped house, approximately 40 x 28 ft., at a point S. 73° E., 9.4 lks. dist. from a southerly cor.</p>
18.58	<p>Intersect westerly side of same house, at a point S. 17° W., 6 lks. dist. of a northwesterly cor., long side bears S. 17° W.</p>
20.61	<p>The 1/4 sec. cor. of secs. 26 and 27, monumented with an iron post, 1 in. diam., loosely set, projecting 22 ins. above the ground, with a brass cap mkd. 1/4 S27 S26 1930, from which the only remaining bearing tree mkd. in 1930</p> <p align="center">An oak, 21 ins. diam., bears N. 78 1/2° E., 27 lks. dist., with a completely healed blaze.</p>

Dependent Resurvey of a Portion of the Subdivisional Lines,
T. 13 N., R. 2 W., Gila and Salt River Meridian, Arizona

CHAINS	
	<p>A steel fence post is set alongside the iron post, with a "Land Survey Monument" sign attached.</p>
	<p>We found no evidence of the orig. corner stone.</p>
	<p>At the corner point</p>
	<p>Reset the 1930 iron post, 1 in. diam., 36 ins. long, 30 ins. in the ground, and add the marks T13N R2W and 2007 to the brass cap.</p>
	<p>Deposit a magnet, in a white plastic case, at the base of the iron post.</p>
	<p>Land, rolling. Soil, decomposed granite. Timber, pine and oak.</p>
	<hr/> <p>From the cor. of secs. 26, 27, 34 and 35, identical with an angle point on line 1-2, Fort Whipple Timber Reserve.</p>
	<p>N. 88°38' W., bet. secs. 27 and 34.</p>
	<p>Over rolling terrain, through pine timber and scrub oak.</p>
19.895	<p>Point for the E. 1/16 sec. cor. of secs. 27 and 34.</p>
	<p>Set an alum. post, 28 ins. long, 2 1/2 ins. diam., 16 ins. in the ground, in a mound of stone, 3 1/2 ft. base, to top, with alum. cap mkd.</p>
	<p style="text-align: center;">T 13 N R 2 W</p>
	<p style="text-align: center;">S 27</p>
	<p style="text-align: center;">E 1/16 —————</p>
	<p style="text-align: center;">S 34</p>
	<p style="text-align: center;">2007</p>
	<p>from which</p>
	<p style="padding-left: 40px;">A pine, 13 ins. diam., bears N. 69 1/4° E., 1.06 chs. dist., mkd. X BT.</p>
	<p style="padding-left: 40px;">A pine, 20 ins. diam., bears N. 38 1/2° W., 34 lks. dist., mkd. E1/16 S27 BT.</p>
	<p>Deposit a magnet, in a white plastic case, at the base of the alum. post.</p>

**Dependent Resurvey of a Portion of the Subdivisional Lines,
T. 13 N., R. 2 W., Gila and Salt River Meridian, Arizona**

CHAINS	
	Set a steel fence post nearby, with "Attention" sign attached to it.
39.79	The 1/4 sec. cor. of secs. 27 and 34, identical with cor. No. 2, Fort Whipple Timber Reserve, monumented with an iron post, 1 in. diam., firmly set, projecting 18 ins. above the ground, with a brass cap mkd. 1/4 S27 S34 AP FWTR 1918, from which the bearing trees mkd. in 1918
	A pine, 20 ins. diam., bears N. 51° E., 20 lks. dist., with a completely healed blaze. (Record: 16 lks.)
	A pine, 20 ins. diam., bears S. 19° W., 37 lks. dist., with a completely healed blaze.
	A steel fence post is set alongside the iron post, with a "Land Survey Monument" sign attached.
	Add the marks T13N R2W and 2007 to the brass cap
	N. 89°24' W., beginning new measurement.
39.91	The cor. of secs. 27, 28, 33 and 34, monumented with an iron post, 2 ins. diam., firmly set, projecting 17 ins. above the ground and leaning, with a brass cap mkd. T13N R2W S28 S27 S33 S34 1918, from which the bearing trees mkd. in 1918
	A pine, 20 ins. diam., bears N. 32 3/4° E., 74 lks. dist., with a completely healed blaze. (Record: N. 32° E.)
	A pine, 32 ins. diam., bears S. 31 3/4° E., 24 lks. dist., with a completely healed blaze. (Record: S. 34° E., 23 lks.)
	An oak, 12 ins. diam., bears S. 18 1/4° W., 36 1/2 lks. dist., with a completely healed blaze. (Record: Pine, S. 15° W., 37 lks.)
	A pine, 18 ins. diam., bears N. 34° W., 59 lks. dist., with a completely healed blaze.
	Each of the bearing trees had a Forest Service bearing tree tag dated 1965 nailed to them.
	A steel fence post is set alongside the iron post, with a "Land Survey Monument" sign attached.
	At the corner point
	Plumb the iron post and build a supporting mound of stone, 3 ft. base, to cap, and add the marks 2007 to the brass cap.

Dependent Resurvey of a Portion of the Subdivisional Lines,
T. 13 N., R. 2 W., Gila and Salt River Meridian, Arizona

CHAINS	
	<p>Land, rolling. Soil, decomposed granite. Timber, pine and oak.</p> <hr/>
15.16	<p>N. 1°18' E., bet. secs. 27 and 28.</p> <p>Over rolling terrain, through pine timber and scrub oak.</p> <p>Point for the N-S-S 1/256 sec. cor. of secs. 27 and 28.</p> <p>Set an alum. post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with alum. cap mkd.</p> <div style="text-align: center;"> <p>T 13 N R 2 W N-S-S 1/256 S 28 S 27 2007</p> </div> <p>Deposit a magnet, in a white plastic case, at the base of the alum. post.</p> <p>Set a steel fence post nearby, with "Land Survey Monument" and "Property Boundary" signs attached to it.</p>
20.21	<p>The S. 1/16 sec. cor. of secs. 27 and 28, assumed established by Cecil Overstreet, according to an unrecorded survey dated February 1948, and accepted as the true cor. by Linda S. Smith, Arizona R.L.S. No. 18554, in 1985, according to Arizona Land Survey Monument Record, Instrument No. 6123, Book 1795, Page 860, filed at the Yavapai County Courthouse, dated February 20, 1986, monumented with an alum. rod, 3/4 in. diam., firmly set, projecting 2 ins. above the ground, with an alum. cap mkd. S1/16 S28 S27 LS18554 1985. This is accepted as a careful and faithful establishment of the cor. position, from which the bearing trees mkd. in 1985</p> <p style="padding-left: 40px;">A pine (dead), 16 ins. diam., bears S. 64° E., 35 lks. dist., with fragmentary scribe marks visible on a partially healed, pitch covered blaze.</p> <p style="padding-left: 40px;">A pine, 12 ins. diam., bears S. 42° W., 61 lks. dist., with fragmentary scribe marks 1/16 S28 BT legible on a partially healed, pitch covered blaze. (Record: S. 34° W.)</p> <p>An alum. sign post is set alongside the iron post, with "Land Survey Monument" and "Property Boundary" signs attached.</p>

**Dependent Resurvey of a Portion of the Subdivisional Lines,
T. 13 N., R. 2 W., Gila and Salt River Meridian, Arizona**

CHAINS	
	<p>Add the marks 2007 to the brass cap.</p> <hr/> <p>N. 1°13' E., beginning new measurement.</p>
20.22	<p>The 1/4 sec. cor. of secs. 27 and 28, monumented with an iron post, 1 in. diam., firmly set, projecting 8 ins. above the ground, in a mound of stone, 2 ft. base to brass cap mkd. 1/4 S28 S27 1930, from which the bearing trees mkd. in 1930</p> <p style="padding-left: 40px;">A pine, 14 ins. diam., bears S. 53° E., 37 lks. dist., with a completely healed blaze. (Record: 36 lks.)</p> <p style="padding-left: 40px;">A pine, 23 ins. diam., bears S. 72 1/2° W., 26 1/2 lks. dist., with a completely healed blaze. (Record: 28 lks.)</p> <p>A steel fence post is set alongside the iron post, with "Land Survey Monument" and "Property Boundary" signs attached.</p> <p>This cor. falls on the west edge of a wash, 7 ft. wide, drains S. 15° E., and just north of a 4 strand wire fence.</p> <p>Add the marks T13N R2W and 2007 to the brass cap.</p> <hr/> <p>N. 0°52' E., beginning new measurement.</p>
40.47	<p>The cor. of secs. 21, 22, 27 and 28, monumented with an iron post, 2 ins. diam., firmly set, projecting 12 ins. above the ground and leaning, in a mound of stone, 2 ft. base to brass cap mkd. T13N R2W S21 S22 S28 S27 1930, from which the bearing trees mkd. in 1930</p> <p style="padding-left: 40px;">A pine snag, 19 ins. diam., bears N. 15° E., 2.00 chs. dist., with scribe marks visible but not legible on a partially healed blaze.</p> <p style="padding-left: 40px;">A nearly rotted away stump, 5 ins. diam., bears S. 85 1/2° E., 36 lks. dist., with a Forest Service bearing tree tag nailed to it.</p> <p style="padding-left: 40px;">A juniper (dead), 19 ins. diam., bears S. 21 1/2° W., 1.35 chs. dist., with fragmentary scribe marks visible and partially legible on a partially healed blaze. (Record: 1.33 chs.)</p> <p style="padding-left: 40px;">A juniper, 25 ins. diam., bears N. 87° W., 39 lks. dist., with faint scribe marks visible on a partially healed blaze on the main trunk, and with fragmentary scribe marks visible on a partially healed blaze on a branch, 18 ins. diam.</p> <p>At the corner point</p>

**Dependent Resurvey of a Portion of the Subdivisional Lines,
T. 13 N., R. 2 W., Gila and Salt River Meridian, Arizona**

CHAINS	
40.36	<p>Plumb up the iron post and build a supporting mound of stone, 3 ft. base, to cap, and add the marks 2007 to the brass cap.</p> <p>The orig. stone monument, 14 x 10 x 8 ins., properly marked, was found disturbed, laying nearby, and was placed in the supporting mound of stone.</p> <p>Land, rolling. Soil, decomposed granite. Timber, pine and oak.</p> <hr/> <p>From the 1/4 sec. cor. of secs. 22 and 27, monumented with an iron post, 1 in. diam., firmly set, projecting 14 ins. above the ground and leaning, in a mound of stone, 2 ft. base, 1 ft. high, with a brass cap mkd. 1/4 S22 S27 1930, from which bearing trees mkd. by persons unknown in 2007</p> <p style="padding-left: 40px;">A pine, 14 ins. diam., bears S. 41 3/4° W., 52 1/2 lks. dist., with scribe marks 1/4 S27 BT visible on an open blaze. There is a Forest Service bearing tree tag mkd. by G.L.B., dated 2007 giving a bearing and dist. of N. 41° E., 34.5 ft.</p> <p style="padding-left: 40px;">A pine, 14 ins. diam., bears N. 53 1/4° W., 34 lks. dist., with scribe marks 1/4 S22 BT visible on an open blaze. There is a Forest Service bearing tree tag mkd. by G.L.B., dated 2007 giving a bearing and dist. of S. 52° E., 22.6 ft.</p> <p>A steel fence post is set alongside the iron post, with "Land Survey Monument" and "Property Boundary" signs attached.</p> <p>At the corner point</p> <p>Plumb the iron post and build a supporting mound of stone, 3 ft. base, to cap, and add the marks T13N R2W and 2007 to the brass cap.</p> <p>N. 89°19' W., bet. secs. 22 and 27.</p> <p>Over rolling terrain, through pine timber and scrub oak.</p> <p>The cor. of secs. 21, 22, 27 and 28.</p> <p>Land, rolling. Soil, decomposed granite. Timber, pine and oak.</p> <hr/> <p>From the cor. of secs. 27, 28, 33 and 34.</p>

**Dependent Resurvey of a Portion of the Subdivisional Lines,
T. 13 N., R. 2 W., Gila and Salt River Meridian, Arizona**

CHAINS	
19.875	<p>S. 89°55' W., bet. secs. 28 and 33.</p> <p>Over rolling terrain, through pine timber and scrub oak.</p> <p>Point for the E. 1/16 sec. cor. of secs. 28 and 33.</p> <p>Set an alum. post, 28 ins. long, 2 1/2 ins. diam., 25 ins. in the ground, with alum. cap mkd.</p>
	<p align="center">T 13 N R 2 W</p> <p align="center">S 28</p> <p align="center">E 1/16 —————</p> <p align="center">S 33</p> <p align="center">2007</p>
	<p>from which</p> <p>The marks X BO on a granite rock in place, 4 x 4 ft., 3 ft. high, bears S. 19 1/2° E., 31 1/2 lks. dist. The X is 2 1/2 ft. above the ground.</p> <p>A pine, 12 ins. diam., bears S. 64 1/2° W., 39 lks. dist., mkd. E1/16 S33 BT.</p> <p>Deposit a magnet, in a white plastic case, at the base of the alum. post.</p> <p>Set a steel fence post nearby, with a "Land Survey Monument" sign attached to it.</p>
39.75	<p>The 1/4 sec. cor. of secs. 28 and 33, monumented with a stone, 10 x 6 ins., firmly set, in a mound of stone, projecting 12 ins. above the ground, with no definitive marks found, from which the bearing trees mkd. in 1918</p> <p>An oak, 16 ins. diam., bears North, 7 lks. dist., with a completely healed blaze.</p> <p>A pine, 13 ins. diam., bears S. 38° E., 8 lks. dist., with a completely healed blaze. (Record: South)</p> <p>An iron post, 1 in. diam., firmly set, projecting 10 ins. above the ground, with a brass cap mkd. 1/4 S28 S33 1930, is set alongside the stone monument.</p> <p>A steel fence post is set alongside the stone monument, with a "Land Survey Monument" sign attached.</p> <p>At the corner point</p>

**Dependent Resurvey of a Portion of the Subdivisional Lines,
T. 13 N., R. 2 W., Gila and Salt River Meridian, Arizona**

CHAINS	
	<p>Reset the 1930 iron post, 36 ins. long, 1 in. diam., 26 ins. in the ground, encircle by a collar of stone, 3 ft. diam., and add the marks T13N R2W and 2007 to the brass cap.</p> <p>Deposit a magnet, in a white plastic case, at the base of the iron post, and bury the orig. stone alongside.</p> <p>This cor. is located on the S. bank of Groom Creek about 30 ft. above bottom of creek.</p> <p>Land, rolling. Soil, dirt and rock. Timber, pine and oak.</p> <hr/> <p>From the 1/4 sec. cor. of secs. 28 and 29, monumented with an iron post, 1 in. diam., firmly set, projecting 15 ins. above the ground, in a mound of stone, 3 1/2 ft. base, to brass cap mkd. 1/4 S29 S28 1930, from which the remains of a bearing tree mkd. in 1930</p> <p style="padding-left: 40px;">A pine (dead), 22 ins. diam., bears S. 42° E., 46 lks. dist., with a healed blaze. (Record: 55 lks.)</p> <p>Set a steel fence post nearby, with a "Land Survey Monument" sign attached to it.</p> <p>N. 2°02' W., bet. secs. 28 and 29.</p> <p>Over rolling terrain, through pine timber and scrub oak.</p>
40.85	<p>The cor. of secs. 20, 21, 28 and 29, monumented with an iron post, 2 ins. diam., firmly set, projecting 8 ins. above a mound of stone, 2 ft. diam., 1 ft. high, with brass cap mkd. T13N R2W S20 S21 S29 S28 1930, from which the remains of one of the bearing trees mkd. in 1871</p> <p style="padding-left: 40px;">An oak, 11 ins. diam., bears S. 23° E., 44 lks. dist., with scribe marks visible but not legible on a partially healed blaze. (1871 Record: S. 28 1/2° E., 46 lks.) (1930 Record: S. 22 3/4° E., 46 lks.)</p> <p>and the bearing trees mkd. in 1918</p> <p style="padding-left: 40px;">A cut stump, 9 ins. diam., bears S. 56 1/4° E., 47 lks. dist., with a partial BT visible on portion of the remaining blaze. (Record: S. 55° E., 48 lks.)</p> <p style="padding-left: 40px;">A pine, 19 ins. diam., bears S. 31 1/2° W., 42 lks. dist., with a completely healed blaze. (Record: S. 30 1/2° W., 43 lks.)</p> <p>Add the marks 2007 to the brass cap.</p>

**Dependent Resurvey of a Portion of the Subdivisional Lines,
T. 13 N., R. 2 W., Gila and Salt River Meridian, Arizona**

CHAINS	
	<p>The orig. stone was found, disturbed, to the N. alongside the iron pipe.</p> <p>Land, rolling. Soil, decomposed granite. Timber, pine and oak.</p> <hr/> <p>From the cor. of secs. 21, 22, 27 and 28.</p> <p>S. 87°30' W., bet. secs. 21 and 28.</p> <p>Over rolling terrain, through pine timber and scrub oak.</p>
45.66	<p>The 1/4 sec. cor. of secs. 21 and 28, monumented with an iron post, 1 in. diam., firmly set, projecting 24 ins. above the ground, in a mound of stone, 4 ft. base to brass cap mkd. 1/4 S21 S28 1930, from which the remains of the bearing trees mkd. in 1930</p> <p style="padding-left: 40px;">A rotted stump, diam. not measured, bears S. 28° W., 19 lks. dist., with the broken off tree laying alongside with scribe marks BT visible on a low blaze and a completely healed higher blaze. (Record: 20 lks.)</p> <p style="padding-left: 40px;">A rotted stump, diam. not measured, bears N. 36 1/2° W., 37 lks. dist., with the broken off tree laying alongside with scribe marks visible but not legible on a rotting low blaze. (Record: 38 lks.)</p> <p>A steel fence post is set alongside the iron post, with "Land Survey Monument" sign attached.</p> <p>Add the marks T13N R2W and 2007 to the brass cap.</p> <hr/> <p>S. 87°36' W., beginning new measurement.</p>
45.18	<p>The sec. cor. of secs. 20, 21, 28 and 29.</p>

**Dependent Resurvey of a Portion of the Subdivisional Lines,
T. 13 N., R. 2 W., Gila and Salt River Meridian, Arizona**

CHAINS	
	<p>Land, rolling. Soil, decomposed granite. Timber, pine and oak.</p> <hr/> <p style="text-align: center;">Dependent Resurvey of a portion of the Subdivision of Sections 34 and 35, T. 13 N., R. 2 W., Gila and Salt River Meridian, Arizona</p> <hr/> <p style="text-align: center;">Restoring a portion of the survey executed by David W. Eaton, in 1918 and the resurvey executed by Benjamin J. Kinsey, in 1930</p> <hr/> <p>From the stan. 1/4 sec. cor. of sec. 34, on the S. bdy. of the Tp.</p> <p>N. 1°08' E., on the N. and S. center line of sec. 34, identical in part with line 3-2 of the Fort Whipple Forest Reserve.</p> <p>0.40 Wolf Creek, 4 ft. wide, course S. 70° W.</p> <p>2.80 Wolf Creek road, a dirt road, 16 ft. wide, bears S. 85° E. and W.</p> <p>20.535 Point for the center S. 1/16 sec. cor. of sec. 34.</p> <p>Set an alum. post, 28 ins. long, 2 1/2 ins. diam., 22 ins. in the ground, in a collar of stone, with alum. cap mkd.</p> <div style="text-align: center;"> <p>T 13 N R 2 W</p> <p style="margin-left: 100px;">C</p> <p style="margin-left: 100px;"> </p> <p style="margin-left: 100px;">S1/16 S 34</p> <p style="margin-left: 100px;">C</p> <p>2007</p> </div> <p>from which</p> <p>The marks X BO on a granite boulder, 10 x 8 x 8 ft., bears N. 73 1/2° E., 1.116 chs. dist. The X is 3 1/2 ft. above the ground.</p> <p>A pine, 16 ins. diam., bears S. 33 1/2° W., 76 lks. dist., mkd. CS1/16 S34 BT.</p> <p>Deposit a magnet, in a white plastic case, at the base of the alum. post.</p>

Dependent Resurvey of a Portion of the Subdivision of Sections 34 and 35
T. 13 N., R. 2 W., Gila and Salt River Meridian, Arizona

CHAINS	
41.07	<p>Set a steel fence post nearby, with an "Attention" sign attached to it.</p> <p>Point for the center 1/4 sec. cor. of sec. 34, at intersection with the E. and W. center line, identical with cor. No. 3, Fort Whipple Timber Reserve.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, in a collar of stone, with brass cap mkd.</p> <p style="text-align: center;">T 13 N R 2 W C 1/4 S 34</p> <p style="text-align: center;">2008</p> <p>from which</p> <p style="padding-left: 40px;">A pine, 18 ins. diam., bears S. 84° E., 10 1/2 lks. dist., mkd. S34 C1/4 BT.</p> <p style="padding-left: 40px;">A pine, 17 ins. diam., bears N. 15 1/4° W., 41 1/2 lks. dist., mkd. C1/4 S34 BT.</p> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p> <p>From this point, the center 1/4 sec. cor. of sec. 34, identical with cor. No. 3, Fort Whipple Timber Reserve, set in 1918, monumented with an iron post, 2 ins. diam., firmly set, projecting 19 ins. above the ground, with brass cap erroneously mkd. C1/4 S33 FWTR 1918, and orientated to the south, bears N. 66°10' W., 56 1/2 lks. dist., with no evidence of the orig. mound of stone. The monument was amended as follows: Add the marks AM T13N R2W 2007 to the brass cap, change S33 to S34, and leave the iron post in place.</p>
61.58	<p>Point for the center N. 1/16 sec. cor. of sec. 34.</p> <p>Set an alum. post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with an alum. cap mkd.</p> <p style="text-align: center;">T 13 N R 2 W C N1/16 S 34 C</p> <p style="text-align: center;">2007</p> <p>from which</p>

**Dependent Resurvey of a Portion of the Subdivision of Sections 34 and 35
T. 13 N., R. 2 W., Gila and Salt River Meridian, Arizona**

CHAINS	
	<p>A pine, 18 ins. diam., bears N. 1 3/4° E., 1.149 chs. dist., mkd. CN1/16 S34 BT.</p>
	<p>A pine, 16 ins. diam., bears N. 76° W., 51 lks. dist., mkd. X BT.</p>
	<p>Deposit a magnet, in a white plastic case, at the base of the alum. post.</p>
	<p>Set a steel fence post nearby, with an "Attention" sign attached to it.</p>
	<p>Cor. falls 67 lks. E. of a dirt road, 14 ft. wide, bears N. 10° E. and S. 10° W.</p>
82.09	<p>The 1/4 sec. cor. of secs. 27 and 34, identical with cor. No. 2, Fort Whipple Timber Reserve.</p> <hr/>
	<p>From the 1/4 sec. cor. of secs. 34 and 35.</p>
	<p>N. 88°43' W., on the E. and W. center line of sec. 34, identical in part with a portion of line 3-4, Fort Whipple Timber Reserve.</p>
5.30	<p>Intersect line 4-1, Lost Chance lode, M.S. No. 2129, at a point from which cor. No. 4 bears S. 54°02' W., 2.06 chs. dist., not monumented.</p>
29.59	<p>Point for the center W-E 1/64 sec. cor. of sec. 34.</p>
	<p>Set an alum. post, 28 ins. long, 2 1/2 ins. diam., 25 ins. in the ground, with alum. cap mkd.</p>
	<p align="center">T 13 N R 2 W S34 C-W-E 1/64</p>
	<p align="center">2007</p>
	<p>Deposit a magnet, in a white plastic case, at the base of the alum. post.</p>
	<p>Set a steel fence post nearby, with "Land Survey Monument" and "Property Boundary" signs attached to it.</p>
31.80	<p>Dirt road, 12 ft. wide, bears N. 45° E. and S. 55° W.</p>
39.45	<p>The center 1/4 sec. cor. of sec. 34, identical with cor. No. 3, Fort Whipple Timber Reserve.</p>

Dependent Resurvey of a Portion of the Subdivision of Sections 34 and 35
T. 13 N., R. 2 W., Gila and Salt River Meridian, Arizona

CHAINS	
79.355	<p>The 1/4 sec. cor. of secs. 33 and 34, monumented with an iron post, 1 in. diam., loosely set, projecting 14 ins. above the ground, with brass cap mkd. 1/4 S33 S34 FWTR 1918, from which an original bearing tree</p> <p style="padding-left: 40px;">An alligator juniper, 53 ins. diam., bears N. 12° E., 84 lks. dist., with scribe marks 1/4 S33 visible on partially open blaze. (Record: 82 lks.)</p> <p>Remnants of the mound of stone are to the W. of the cor.</p> <p>A steel fence post is set alongside the iron post, with a "Land Survey Monument" sign attached.</p> <p>At the corner point</p> <p>Reset the iron post, 36 ins. long, 1 in. diam., 33 ins. in the ground, and in a rock collar, and add the marks T13N R2W 2008 to the brass cap.</p>
	<p>From the stan. W. 1/16 sec. cor. of sec. 35, identical with cor. No. 6, Fort Whipple Timber Reserve.</p> <p>N. 0°40' E., on the N. and S. center line of the SW 1/4 of sec. 35, on line 6-1 of the Fort Whipple Timber Reserve.</p> <p>Over rolling terrain, through pine timber and scrub oak.</p>
4.75	<p>Senator Highway, a dirt road, 16 ft. wide, bears S. 30° E. and N. 30° W.</p>
20.57	<p>Point for the SW 1/16 sec. cor. of sec. 35.</p> <p>Set an alum. post, 28 ins. long, 2 1/2 ins. diam., 23 ins. in the ground, with alum. cap mkd.</p>
	<p style="text-align: center;">T 13 N R 2 W</p> <p style="text-align: center;">SW 1/16 S35</p> <p style="text-align: center;">2007</p>
	<p>from which</p> <p style="padding-left: 40px;">The marks X BO on a granite boulder, 3 x 2 x 3 ft., bears N. 28 1/4° E., 68 lks. dist. The X is 1 1/2 ft. above the ground.</p> <p style="padding-left: 40px;">A pine, 13 ins. diam., bears N. 45° W., 72 lks. dist., mkd. SW1/16 S35 BT.</p>

Dependent Resurvey of a Portion of the Subdivision of Sections 34 and 35
T. 13 N., R. 2 W., Gila and Salt River Meridian, Arizona

CHAINS	
	<p>Deposit a magnet, in a white plastic case, at the base of the alum. post.</p> <p>Set a steel fence post nearby, with an "Attention" sign attached to it.</p>
41.12	<p>Point for the center W. 1/16 sec. cor. of sec. 35.</p> <p>Set an alum. post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with alum. cap mkd.</p> <p style="text-align: center;">T 13 N R 2 W</p> <p style="text-align: center;">W 1/16</p> <p style="text-align: center;">C ————— C</p> <p style="text-align: center;">S 35</p> <p style="text-align: center;">2007</p> <p>from which</p> <p style="padding-left: 40px;">The marks X BO on a granite boulder, 6 x 4 x 3 1/2 ft., bears N. 7 1/4° E., 1.25 chs. dist. The X is 2 1/2 ft. above the ground.</p> <p style="padding-left: 40px;">A pine, 14 ins. diam., bears S. 74° E., 65 lks. dist., mkd. CW1/16 S35 BT.</p>
	<p>Deposit a magnet, in a white plastic case, at the base of the alum. post.</p> <p>Set a steel fence post nearby, with an "Attention" sign attached to it.</p> <hr/>
	<p>N. 0°40' E., on the N. and S. center line of the NW 1/4 of sec. 35, continuing on line 6-1 of the Fort Whipple Timber Reserve.</p> <p>Over rolling terrain, through pine timber and scrub oak.</p>
19.10	<p>Trail, 6 ft. wide, bears N. 60° E. and S. 60° W.</p>
20.12	<p>Point for the NW 1/16 sec. cor. of sec. 35.</p> <p>Set an alum. post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with alum. cap mkd.</p>

**Dependent Resurvey of a Portion of the Subdivision of Sections 34 and 35
T. 13 N., R. 2 W., Gila and Salt River Meridian, Arizona**

CHAINS	
	<p style="text-align: center;">T 13 N R 2 W</p> <p style="text-align: center;">NW 1/16 S35</p> <p style="text-align: center;">2007</p> <p>from which</p> <p style="padding-left: 40px;">A pine, 10 ins. diam., bears N. 42° E., 37 lks. dist., mkd. X BT.</p> <p style="padding-left: 40px;">A pine, 15 ins. diam., bears S. 42° E., 49 1/2 lks. dist., mkd. NW1/16 S35 BT.</p> <p>Deposit a magnet, in a white plastic case, at the base of the alum. post.</p> <p>Set a steel fence post nearby, with an "Attention" sign attached to it.</p>
21.30	Gravel drive entering into trail head parking lot, 20 ft. wide, bears N. 65° E. and S. 80° W.
24.25	Senator Highway, asphalt surfaced, 24 ft. wide, bears N. 45° E. and S. 45° W.
40.10	The W. 1/16 sec. cor. of secs. 26 and 35, identical with cor. No. 1, Fort Whipple Timber Reserve.
	<p>Land, rolling.</p> <p>Soil, decomposed granite.</p> <p>Timber, pine and oak.</p>
	<hr/> <p>Dependent Resurvey of Mineral Survey No. 2129, T. 13 N., R. 2 W., Gila and Salt River Meridian, Arizona</p> <hr/>
	<p>Restoring the survey executed by J.J. Fisher, in 1905</p> <hr/>
	<p>From cor. No. 1, Lost Chance lode, M.S. No. 2129, perpetuated by Gary B. Collins, Arizona R.L.S. No. 7335, in 1999, according to Plat No. LS50-159, Book 50 of Land Surveys, Page 59, filed at the Yavapai County Courthouse, dated Octoer 26, 1999, and Arizona Land Survey Corner Record, 3196292, Book 3703, Page 417, filed at the Yavapai County Courthouse, dated October 15, 1999, monumented with an alum. post, 2 1/2 ins. diam., firmly set, projecting 1 in. above the ground, in a collar of stone, with alum. cap mkd. P.N.F. 1 L.C. M.S.2129 R.L.S.7335 1999. This is</p>

**Dependent Resurvey of Mineral Survey No. 2129,
T. 13 N., R. 2 W., Gila and Salt River Meridian, Arizona**

CHAINS	
	<p>accepted as a careful and faithful perpetuation of the orig. cor. position, from which one of the bearing trees mkd. in 1905</p> <p style="padding-left: 40px;">An oak, 13 ins. diam., bears N. 82 1/2° W., 10 1/2 lks. dist., with completely healed blaze.</p> <p>and the bearing tree mkd. in 1999</p> <p style="padding-left: 40px;">A pine, 20 ins. diam., bears N. 14° E., 94 1/2 lks. dist., with a plastic LS tag spiked to the tree.</p> <p>A steel fence post is set alongside the iron post, with "Land Survey Monument" and "Property Boundary" signs attached.</p> <p>S. 35°18' E., on line 1-2, Lost Chance lode, M.S. No. 2129.</p> <p>Over rolling terrain.</p>
5.10	Intersect E. and W. center line of sec. 35, hereinafter described, not monumented.
15.95	Senator Highway, asphalt surfaced, 24 ft. wide, bears N. and S. 5° W.
22.72	<p>Cor. No. 2, Lost Chance lode, M.S. No. 2129, reestablished by Gary B. Collins, Arizona R.L.S. No. 7335, in 1999, according to Plat No. LS50-159, Book 50 of Land Surveys, Page 59, filed at the Yavapai County Courthouse, dated Octoer 26, 1999, and Arizona Land Survey Corner Record, 3196293, Book 3703, Page 418, filed at the Yavapai County Courthouse, dated October 15, 1999, monumented with an alum. post, 2 1/2 ins. diam., firmly set, encircled with large stones, projecting 2 ins. above the ground, with alum. cap mkd. M.S.2129 L.C.2 P.N.F. R.L.S.7335 1999. This is accepted as a careful and faithful reestablishment of the cor. position, from which the bearing trees mkd. in 1999</p> <p style="padding-left: 40px;">A pine, 22 ins. diam., bears N. 15° E., 17 lks. dist., with plastic LS tag spiked to the tree.</p> <p style="padding-left: 40px;">A pine stump, 5 1/2 ft. high, 13 ins. diam., bears S. 77° E., 31 lks. dist., with a plastic LS tag spiked to the tree.</p> <p>A steel fence post is set alongside the iron post, with "Land Survey Monument" and "Property Boundary" signs attached.</p> <hr style="width: 20%; margin: 10px auto;"/> <p>S. 54°39' W., on line 2-3, Lost Chance lode, M.S. No. 2129.</p> <p>Over rolling terrain.</p>
6.15	Senator Highway, a dirt road, 20 ft. wide, bears S. 20° E. and N. 10° W.

**Dependent Resurvey of Mineral Survey No. 2129,
T. 13 N., R. 2 W., Gila and Salt River Meridian, Arizona**

CHAINS	
9.04	<p>Cor. No. 3, Lost Chance lode, M.S. No. 2129, monumented with a stone, 13 x 12 ins., firmly set, projecting 7 ins. above the ground, in a collar of stone, mkd. LC3 2129 on NE face, from which one of the bearing trees mkd. in 1905</p> <p style="padding-left: 40px;">An oak, 22 ins. diam., bears North, 6 1/2 lks. dist., with completely healed blaze.</p> <p>and the bearing trees mkd. by Gary B. Collins, Arizona R.L.S. No. 7335, in 1999</p> <p style="padding-left: 40px;">A pine stump, 6 ft. high, 14 ins. diam., bears S. 48° W., 18 1/2 lks. dist.</p> <p style="padding-left: 40px;">A pine, 11 ins. diam., bears N. 32° W., 37 1/2 lks. dist.</p> <p>A steel fence post is set alongside the iron post, with "Land Survey Monument" and "Property Boundary" signs attached.</p> <hr style="width: 20%; margin: 10px auto;"/> <p>N. 35°19' W., on line 3-4, Lost Chance lode, M.S. No. 2129.</p> <p>Over rolling terrain.</p>
11.05	Intersect the line bet. secs. 34 and 35, not monumented.
22.62	<p>Cor. No. 4, Lost Chance lode, M.S. No. 2129, monumented with a stone, 12 x 10 ins., firmly set, projecting 8 ins. above the ground, mkd. with an X on top and LC4 2129 on NE face, from which the bearing trees mkd. by Gary B. Collins, Arizona R.L.S. No. 7335, in 1999</p> <p style="padding-left: 40px;">A pine, 13 ins. diam., bears N. 66° E., 9 1/2 lks. dist., with a plastic LS tag mkd. RLS 7335 spiked to the tree.</p> <p style="padding-left: 40px;">A pine, 10 ins. diam., bears S. 29° E., 12 1/2 lks. dist., with a plastic LS tag mkd. RLS 7335 spiked to the tree.</p> <p>A steel fence post is set alongside the iron post, with "Land Survey Monument" and "Property Boundary" signs attached.</p> <hr style="width: 20%; margin: 10px auto;"/> <p>N. 54°02' E., on line 4-1, Lost Chance lode, M.S. No. 2129.</p> <p>Over rolling terrain.</p>
2.06	Intersect the E. and W. center line of sec. 34, hereinafter described, not monumented.
8.745	Intersect the line bet. secs. 34 and 35, hereinbefore described.

**Dependent Resurvey of Mineral Survey No. 2129,
T. 13 N., R. 2 W., Gila and Salt River Meridian, Arizona**

CHAINS	<p>9.055 Cor. No. 1, Lost Chance lode, M.S. No. 2129, and point of beginning.</p> <hr/> <p style="text-align: center;">Dependent Resurvey of a Portion of Mineral Survey No. 4226, T. 13 N., R. 2 W., Gila and Salt River Meridian, Arizona</p> <hr/> <p style="text-align: center;">Restoring the survey executed by Richard L. Merrit, in 1940</p> <hr/> <p>From cor. No. 1, Emporia lode, M.S. No. 4226, monumented with a stone, 12 x 7 ins., firmly set, projecting 11 ins. above the ground, in a collar of stone, mkd. with an X on top and E1 4226 on W. face, from which one of the bearing trees mkd. in 1940</p> <p style="padding-left: 40px;">A pine, 18 ins. diam., bears S. 64 1/2° W., 56 1/2 lks. dist., with scribe marks 1 and 22 visible on a partially healed blaze. (Record: S. 31°53' E.)</p> <p>and the bearing trees mkd. by Gary B. Collins, Arizona R.L.S. No. 7335, in 1999</p> <p style="padding-left: 40px;">A pine, 19 ins. diam., bears S. 70° E., 12 lks. dist., with a plastic LS tag spiked to the tree.</p> <p style="padding-left: 40px;">A pine, 21 ins. diam., bears N. 15° W., 24 lks. dist., with a plastic LS tag spiked to the tree.</p> <p>A steel fence post is set alongside the iron post, with "Land Survey Monument" and "Property Boundary" signs attached.</p> <p>From this cor. point, cor. No. 1, Lost Chance lode, M.S. No. 2129, bears S. 34°37' E., 1.46 chs. dist., hereinbefore described.</p> <p>From this same cor. point, a local cor., bears N. 34°35' W., 1.515 chs. dist., monumented with an iron rebar, 5/8 in. diam., firmly set, flush with the ground, with plastic cap mkd. RLS 33872.</p> <hr/> <p>S. 57°24' W., on line 1-2, Emporia lode, M.S. No. 4226.</p> <p>Over rolling terrain.</p>
9.09	<p>Cor. No. 2, Emporia lode, M.S. No. 4226, monumented with a stone, 14 x 6 ins., firmly set, projecting 10 ins. above the ground, mkd. with an X on top and E2 4226 on NE face, from which the accessories mkd. in 1940</p>

**Dependent Resurvey of Mineral Survey No. 4226,
T. 13 N., R. 2 W., Gila and Salt River Meridian, Arizona**

CHAINS	
	<p>A granite rock in place, 6 x 2 ft., 2 ft. above ground, bears N. 53° E., 82 1/2 lks. dist., mkd. X BR E2 4226.</p> <p>An oak, 9 ins. diam., bears N. 33° W., 50 1/2 lks. dist., with the scribe mark 2 visible on a mostly healed blaze.</p> <p>A steel fence post is set alongside the iron post, with "Land Survey Monument" and "Property Boundary" signs attached.</p> <hr style="width: 20%; margin: 10px auto;"/> <p>N. 32°48' W., on a line 2-3, Emporia lode, M.S. No. 4226.</p> <p>Over rolling terrain.</p>
5.025	<p>From this point, Cor. No. 3, Manhattan lode (cancelled), M.S. No. 4226, bears S. 57°12' W., 9 1/2 lks. dist., determined at record bearing and distance from the bearing trees mkd. in 1940</p> <p>A pine, 31 ins. diam., bears S. 65 1/2° E., 61 1/2 lks. dist., with scribe marks BT M clearly visible in a "popped" portion of the completely healed blaze. (Record dist. was to face of tree, this is to center.)</p> <p>An oak, 17 ins. diam., bears N. 61 3/4° W., 15 lks. dist., with healed blaze. (Record dist. was to face of tree, this is to center.)</p>
14.11	<p>From this point, Cor. No. 2, Manhattan lode (cancelled), M.S. No. 4226, bears S. 57°12' W., 7 lks. dist., monumented with a granite stone, 9 x 6 ins., firmly set, projecting 12 ins. above the ground, mkd. with an X on top and M2 4226 on SW face, from which the accessories mkd. in 1940</p> <p>A pine, 16 ins. diam., bears N. 49° E., 24 lks. dist., with scribe marks M and 22 visible on a partially healed blaze.</p> <p>A granite rock in place, 6 x 4 ft., 3 ft. above ground, bears S. 15 3/4° W., 50 lks. dist., mkd. X on top and BR E2 4226 on NE face.</p>
22.435	<p>Cor. No. 3, Emporia lode, identical with cor. No. 4, Poco lode (cancelled), M.S. No. 4226, monumented with a granite stone, 12 x 8 ins., firmly set, projecting 14 ins. above the ground, mkd. with an X on top, E3 4226 on southerly face, and P4 on northerly face, and witnessed by a mound of stone, 2 ft. base, 1 1/2 ft. high, to the NW, from which the accessories mkd. in 1940</p> <p>An oak, 11 ins. diam., bears N. 35 1/2° E., 52 1/2 lks. dist., with a healed blaze.</p>

**Dependent Resurvey of Mineral Survey No. 4226,
T. 13 N., R. 2 W., Gila and Salt River Meridian, Arizona**

CHAINS	
	<p style="text-align: center;">A granite rock in place, 6 x 7 ft., 7 ft. above ground, bears S. 52° E., 65 lks. dist., mkd. X BR E3 P4 4226.</p> <p>A steel fence post is set alongside the iron post, with "Land Survey Monument" and "Property Boundary" signs attached.</p> <hr style="width: 20%; margin: auto;"/> <p>N. 57°25' E., on line 3-4, Emporia lode, identical with line 4-3, Poco lode (cancelled), M.S. No. 4226.</p> <p>Over rolling terrain.</p>
2.81	Point for the closing cor. on the E. and W. center line of the NE 1/4 sec. 34, hereinafter described.
9.09	<p>Cor. No. 4, Emporia lode, identical with cor. No. 3, Poco lode (cancelled), M.S. No. 4226, monumented with a granite stone, 10 x 8 ins., firmly set, projecting 8 ins. above the ground, mkd. with an X on top, E4 4226 on southerly face, and P3 on northerly face, and witnessed by a mound of stone, 2 1/2 ft. base, 2 ft. high, to the E., from which the accessories mkd. in 1940</p> <p style="text-align: center;">A pine, 18 ins. diam., bears S. 43° E., 21 1/2 lks. dist., with scribe marks E and P visible on a partially healed blaze.</p> <p style="text-align: center;">A granite rock in place, 8 x 6 ft., 4 ft. above ground, bears N. 9 3/4° W., 77 lks. dist., mkd. X BR E4 P3 4226 on upper right portion of southerly face.</p> <p>A steel fence post is set alongside the iron post, with "Land Survey Monument" and "Property Boundary" signs attached.</p> <hr style="width: 20%; margin: auto;"/> <p>S. 32°48' E., on line 4-1, Emporia lode, M.S. No. 4226.</p> <p>Over rolling terrain.</p>
12.015	<p>From this point, Cor. No. 2, El Lobo lode (cancelled), M.S. No. 4226, bears N. 57°12' E., 4 lks. dist., monumented with a stone, 14 x 12 ins., firmly set, projecting 10 ins. above the ground, mkd. with an X on top, EL2 4226 on NE face, and witnessed by a mound of stone, 3 ft. base, 2 ft. high, to the SW, from which the accessories mkd. in 1940</p> <p style="text-align: center;">A granite rock in place, 4 x 2 ft., 1 ft. above ground, bears N. 18 3/4° W., 66 1/2 lks. dist., mkd. X EL2 4226.</p> <p style="text-align: center;">An oak, 10 ins. diam., bears N. 64 1/4° W., 69 1/2 lks. dist., with a healed blaze.</p>

**Dependent Resurvey of Mineral Survey No. 4226,
T. 13 N., R. 2 W., Gila and Salt River Meridian, Arizona**

CHAINS	
16.605	Point for the closing cor. on the E. and W. center line of the SE 1/4 of the NE 1/4 of sec. 34, hereinafter described.
22.435	Cor. No. 1, Emporia lode, M.S. No. 4226, and point of beginning.
<hr/> <p>Survey of Partial Subdivision of Section 27, T. 13 N., R. 2 W., Gila and Salt River Meridian, Arizona</p> <hr/>	
	From the 1/4 sec. cor. of secs. 27 and 34.
	N. 1°23' E., on a portion of the N. and S. center line of sec. 27.
	Over rolling terrain, through pine timber and scrub oak.
19.95	Dirt road, 20 ft. wide, bears N. 85° E. and S. 85° W.
20.29	Point for the center S. 1/16 sec. cor. of sec. 27.
	Set an alum. post, 28 ins. long, 2 1/2 ins. diam., 28 ins. in the ground, with alum. cap mkd.
	<pre> T 13 N R 2 W C S1/16 S 27 C 2007 </pre>
	from which
	A pine, 19 ins. diam., bears N. 9° E., 94 1/2 lks. dist., mkd. CS 1/16 S27 BT.
	A pine, 9 ins. diam., bears N. 87 1/4° E., 31 lks. dist., mkd. X BT.
	Deposit a magnet, in a white plastic case, at the base of the alum. post.
	Set a steel fence post nearby.
21.60	Trail, 8 ft. wide, bears S. 25° E. and N. 25° W.

**Survey of Partial Subdivision of Section 27,
T. 13 N., R. 2 W., Gila and Salt River Meridian, Arizona**

CHAINS	
40.58	<p>The center 1/4 sec. cor. of sec. 27, established by Linda S. Smith, Arizona R.L.S. No. 18554, in 1986, according to Plat LS06-008, Book 6 of Land Surveys, Page 8, filed at the Yavapai County Courthouse, dated July 21, 1986, and Arizona Land Survey Monument Record, Instrument No. 11619, Book 1807, Page 419, filed at the Yavapai County Courthouse, dated April 2, 1986, monumented with an alum. rod, 3/4 in. diam., firmly set, projecting 2 ins. above the ground, with an alum. cap mkd. T13N R2W C1/4 S27 18554 1986. This is accepted as a careful and faithful establishment of the cor. position, from which one of the bearing trees mkd. in 1986</p> <p style="padding-left: 40px;">A pine, 14 ins. diam., bears S. 31° E., 24 1/2 lks. dist., with scribe marks X BT visible on a partially healed blaze.</p> <p>An alum. sign post is set alongside the iron post, with "Land Survey Monument" and "Property Boundary" signs attached.</p> <p>Add the marks 2007 to the alum. cap.</p> <p>From this cor. point, the 1/4 sec. cor. of secs. 22 and 27, bears N. 1°24' E., 40.27 chs. dist., hereinbefore described.</p> <p>From this same cor. point, the 1/4 sec. cor. of secs. 27 and 28, bears N. 89°37' W., 39.99 chs. dist., hereinbefore described.</p> <p>Land, rolling. Soil, decomposed granite. Timber, pine and oak.</p> <hr/> <p>From the 1/4 sec. cor. of secs. 26 and 27.</p> <p>N. 89°35' W., on a portion of the E. and W. center line of sec. 27.</p> <p>Over rolling terrain, through pine timber and scrub oak.</p>
2.73	<p>SW cor. of Assessor's Parcel 104-20-015, established by Robert L. Weaver, Arizona R.L.S. No. 22287, in 1998, according to Plat LS44-074, Book 44 of Land Surveys, Page 74, filed at the Yavapai County Courthouse, dated October 2, 1998, monumented with an iron rebar, 1/2 in. diam., firmly set, projecting 1 in. above the ground, with plastic cap mkd. ORION LS 22287.</p> <p>From this cor. point, a cor. set by persons unknown, bears S. 5°40' E., 9 lks. dist., monumented with an iron rebar, 1/2 in. diam., firmly set, projecting 2 ins. above the ground.</p>
8.15	<p>Dirt road, 20 ft. wide, bears N. 5° E. and S. 5° W.</p>

**Survey of Partial Subdivision of Section 27,
T. 13 N., R. 2 W., Gila and Salt River Meridian, Arizona**

CHAINS	
9.52	Intersect easterly side of a wood storage shed, 10 x 8 ft., at a point S. 15° W., 0.3 lks. dist. from the NE cor., the long side bears S. 15° W.
9.65	Intersect westerly side of same wood storage shed, at a point S. 15° W., 3.5 lks. dist. from the NW cor.
9.81	From this point, a cor. set by persons unknown, bears S., 0.9 lks. dist., monumented with an iron rebar, 1/2 in. diam., firmly set, projecting 2 ins. above the ground.
9.96	From this point, a cor. set by persons unknown, bears S., 0.8 lks. dist., monumented with an iron pipe, 1 in. diam., firmly set, projecting 9 ins. above ground.
11.94	Coral rails, 6 rails high, bears N. 25° E. and S. 25° W.
13.92	Intersect northerly side of stable/storage, 62 x 16 ft., at a point S. 70° E., 23.4 lks. dist. from the NW cor., the long side bears S. 70° E.
14.16	Intersect westerly side of same stable/storage, at a point S. 20° W., 8.3 lks. dist. from NW cor.
14.25	Wire fence with wood slats, bears N. 10° E. and S. 10° W.
15.16	Intersect northerly side of a log cabin, 24 x 20 ft., named "B bar B", at a point S. 70° E., 3 lks. dist. of the NW cor., the long side bears S. 70° E.
15.19	Intersect westerly side of the same log cabin, at a point S. 20° W., 1 lk. dist. from the NW cor.
16.51	Backstop, made out of wood pole supports and expanded metal, bears S. 45° E. and N. 45° W.
16.84	Intersect easterly side of wood framed cabin, 20 x 16 ft., named "Paiute", at a point N. 7° W., 3 lks. dist. from the SE cor., the long side bears N. 7° W.
17.09	Intersect westerly side of same wood framed cabin, at a point N. 7° W., 6.4 lks. from the SW cor.
17.28	Intersect easterly side of wood framed cabin, 24 x 16 ft., named "Papago", at a point N. 10° E., 19.5 lks. dist. from the SE cor., the long side bears N. 10° E.
17.53	Intersect westerly side of same wood framed cabin, at a point N. 10° E., 15.3 lks. dist. from the SW cor.
19.57	Point for the center E. 1/16 sec. cor. of sec. 27, falls in creek bottom, 8 ft. wide, course N. 85° W.

**Survey of Partial Subdivision of Section 27,
T. 13 N., R. 2 W., Gila and Salt River Meridian, Arizona**

CHAINS	
	<p>Set a 60 penny nail at the true point and reference with a steel post, with a "Property Boundary" sign attached, set alongside.</p> <p>from which</p> <p style="padding-left: 40px;">An alum. post, 28 ins. long, 2 1/2 ins. diam., set 26 ins. in the ground, for a reference monument, bears S. 60°00' E., 90.9 lks. dist., with alum. cap mkd. RM1 T13N R2W C-E 1/16 S27 60.00 ft. TO COR 2007 and an arrow pointing to the cor. Deposit a magnet in a white plastic case, at the base of the alum. post, and set a steel fence post nearby.</p> <p style="padding-left: 40px;">An alum. post, 28 ins. long, 2 1/2 ins. diam., set 26 ins. in the ground, for a reference monument, bears S. 30°00' W., 75.8 lks. dist., with alum. cap mkd. RM2 T13N R2W C-E 1/16 S27 50.00 ft. TO COR 2007 and an arrow pointing to the cor. Deposit a magnet in a white plastic case, at the base of the alum. post, and set a steel fence post nearby.</p>
26.85	From this point, a cor. set by persons unknown, bears S., 3 lks. dist., monumented with an iron rebar, 1/2 in. diam., firmly set, projecting 1 in. above ground.
35.48	From this point, a cor. set by persons unknown, bears S., 3.2 lks. dist., monumented with an iron rebar, 1/2 in. diam., firmly set, projecting 2 ins. above ground.
38.43	From this point, a cor. set by persons unknown, bears S., 3.2 lks. dist., monumented with an iron rebar, 1/2 in. diam., firmly set, projecting 3 ins. above ground.
39.14	<p>The center 1/4 sec. cor. of sec. 27.</p> <p>Land, rolling. Soil, decomposed granite. Timber, pine and oak.</p> <hr/> <p>From the E. 1/16 sec. cor. of secs. 27 and 34.</p> <p>N. 0°56' E., on the N. and S. center line of the SE 1/4 of sec. 27.</p> <p>Over rolling terrain, through pine timber and scrub oak.</p>
20.455	<p>Point for the SE 1/16 sec. cor. of sec. 27.</p> <p>Set an alum. post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with alum. cap mkd.</p>

**Survey of Partial Subdivision of Section 27,
T. 13 N., R. 2 W., Gila and Salt River Meridian, Arizona**

CHAINS	
	T 13 N R 2 W
	SE1/16 S 27
	2007
	from which
	A pine, 10 ins. diam., bears N. 66 1/4° E., 61 lks. dist., mkd. X BT.
	The marks X BO on a granite boulder, 20 x 12 x 15 ft., bears S. 40 1/4° E., 1.457 chs. dist. The X is 4 1/2 ft. above the ground.
	Deposit a magnet, in a white plastic case, at the base of the alum. post.
	Set a steel fence post nearby.
33.235	Point for a 1/1024 sec. cor. of sec. 27.
	Set an alum. post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with alum. cap mkd.
	T 13 N R 2 W
	1/1024
	2007
	Deposit a magnet, in a white plastic case, at the base of the alum. post.
	Set a steel fence post nearby, with a "Property Boundary" sign attached to it.
34.85	Coral rail, 3 rails high, bears E. and W.
39.00	Intersect south side of a shed, 30 x 16 ft., at a point N. 83° W., 9.7 lks. dist. from the SE cor., the long side bears N. 7° E.
39.50	Intersect north side of same shed, at a point N. 83° W., 12.3 lks. from the NE cor.
39.80	Fence line, bears N. 85° E. and S. 85° W.

**Survey of Partial Subdivision of Section 27,
T. 13 N., R. 2 W., Gila and Salt River Meridian, Arizona**

CHAINS	
40.90	<p>The center E. 1/16 sec. cor. of sec. 27.</p> <p>Land, rolling. Soil, decomposed granite. Timber, pine and oak.</p> <hr/> <p>From the S. 1/16 sec. cor. of secs. 26 and 27.</p> <p>N. 89°07' W., on the E. and W. center line of the SE 1/4 of sec. 27.</p> <p>Over rolling terrain, through pine timber and scrub oak.</p>
19.755	The SE 1/16 sec. cor. of sec. 27.
38.60	Dirt road, 20 ft. wide, bears N. 60° E. and S. 60° W.
39.49	<p>The center S. 1/16 sec. cor. of sec. 27.</p> <p>Land, rolling. Soil, decomposed granite. Timber, pine and oak.</p> <hr/> <p>From the 1/1024 sec. cor. on the line bet. secs. 26 and 27.</p> <p>N. 89°24' W., on the E. and W. center line of the S. 1/2 of the N. 1/2, of the NE 1/4, of the SE 1/4 of sec. 27.</p> <p>Over rolling terrain, through pine timber and scrub oak.</p>
18.60	Dirt road, 8 ft. wide, bears N. 35° E. and S. 35° W.
19.64	<p>The 1/1024 sec. cor. on the N. and S. center line of the SE 1/4 of sec. 27.</p> <p>Land, rolling. Soil, decomposed granite. Timber, pine and oak.</p> <hr/> <p style="text-align: center;">Survey of Partial Subdivision of Section 28, T. 13 N., R. 2 W., Gila and Salt River Meridian, Arizona</p> <hr/> <p>From the 1/4 sec. cor. of secs. 28 and 33.</p> <p>N. 3°10' W., on the N. and S. center line of sec. 28.</p> <p>Over rolling terrain, through pine timber and scrub oak.</p>

**Survey of Partial Subdivision of Section 28,
T. 13 N., R. 2 W., Gila and Salt River Meridian, Arizona**

CHAINS	
19.245	<p>Point for the center S. 1/16 sec. cor. of sec. 28.</p> <p>Set an alum. post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, encircled with a collar of stone, with alum. cap mkd.</p> <div style="text-align: center; margin: 10px 0;"> <p>T 13 N R 2 W</p> <p style="margin: 0 10px;">C</p> <p style="margin: 0 10px;">S 1/16 S 28</p> <p style="margin: 0 10px;">C</p> <p>2007</p> </div> <p>from which</p> <p style="margin-left: 40px;">The marks X BO on a granite outcrop, 4 x 7 x 4 1/2 ft., bears S. 57 1/4° W., 1.242 chs. dist. The X is 3 1/2 ft. above the ground.</p> <p style="margin-left: 40px;">A pine, 20 ins. diam., bears N. 11° W., 53 lks. dist., mkd. CS 1/16 S28 BT.</p> <p>Deposit a magnet, in a white plastic case, at the base of the alum. post.</p> <p>Set a steel fence post nearby, with a "Land Survey Monument" sign attached to it.</p> <p>Cor. falls 22 lks. W. of a creek bed, 2 ft. wide, course S. 40° E.</p>
38.49	<p>Point for the center 1/4 sec. cor. of sec. 28, at intersection with the E. and W. center line.</p> <p>Set an stainless steel post, 28 ins. long, 2 1/2 ins. diam., 23 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center; margin: 10px 0;"> <p>T 13 N R 2 W</p> <p style="margin: 0 10px;">C 1/4 S28</p> <p>2007</p> </div> <p>from which</p> <p style="margin-left: 40px;">The marks X BO on a granite outcrop, 5 x 5 x 3 ft., bears S. 77 3/4° E., 17 lks. dist. The X is 1 ft. above the ground.</p>

**Survey of Partial Subdivision of Section 28,
T. 13 N., R. 2 W., Gila and Salt River Meridian, Arizona**

CHAINS	
	<p align="center">A pine, 14 ins. diam., bears S. 21 1/2° W., 48 lks. dist., mkd. C 1/4 S28 BT.</p> <p>Raise a mound of stone, 3 ft. base, 3 ft. high, W. of cor.</p> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p> <p>Set a steel fence post nearby, with a "Land Survey Monument" sign attached to it.</p>
79.07	<p>The 1/4 sec. cor. of secs. 21 and 28.</p> <p>Land, rolling. Soil, decomposed granite. Timber, pine and oak.</p> <hr/>
	<p>From the 1/4 sec. cor. of secs. 27 and 28.</p> <p>S. 87°15' W., on the E. and W. center line of sec. 28.</p> <p>Over rolling terrain, through pine timber and scrub oak.</p>
21.41	<p>The center E. 1/16 sec. cor. of sec. 28, established by Linda S. Smith, Arizona R.L.S. No. 18554, in 1985, according to Plat LS05-052, Book 5 of Land Surveys, Page 52, filed at the Yavapai County Courthouse, dated February 20 1986, and Arizona Land Survey Monument Record, Instrument No. 6125, Book 1795, Page 862, filed at the Yavapai County Courthouse, dated February 20, 1986, monumented with an alum. rod, 3/4 in. diam., firmly set, projecting 4 ins. above the ground, with an alum. cap mkd. C E 1/16 C S28 LS18554 1985. This is accepted as a careful and faithful establishment of the cor. position, from which the bearing trees mkd. in 1985</p> <p align="center">A pine, 11 ins. diam., bears N. 23 1/2° E., 21 lks. dist., with fragments of scribe marks 1/16 S28 BT visible on a partially healed blaze. (Record: N. 20° E.)</p> <p align="center">A pine, 12 ins. diam., bears N. 89° W., 48 1/2 lks. dist., with fragmentary scribe marks visible on a partially healed blaze.</p> <p>An alum. sign post is set alongside the iron post, with "Land Survey Monument" and "Property Boundary" signs attached.</p> <p>Add the marks 2007 to the alum. cap.</p> <hr/> <p>S. 87°16' W., beginning new measurement.</p>
21.41	<p>The center 1/4 sec. cor. of sec. 28.</p>

**Survey of Partial Subdivision of Section 28,
T. 13 N., R. 2 W., Gila and Salt River Meridian, Arizona**

CHAINS	
67.40	<p>The 1/4 sec. cor. of secs. 28 and 29.</p> <p>Land, rolling. Soil, decomposed granite. Timber, pine and oak.</p> <hr/> <p>From the E. 1/16 sec. cor. of secs. 28 and 33.</p> <p>N. 0°53' W., on the N. and S. center line of the SE 1/4 of sec. 28.</p> <p>Over rolling terrain, through pine timber and scrub oak.</p>
12.325	<p>Point for a 1/1024 sec. cor. of sec. 28.</p> <p>Set an alum. post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with alum. cap mkd.</p> <p style="text-align: center;">T 13 N R 2 W</p> <p style="text-align: center;">1/1024</p> <p style="text-align: center;">2007</p> <p>Deposit a magnet, in a white plastic case, at the base of the alum. post.</p> <p>Set a steel fence post nearby, with "Land Survey Monument" and "Property Boundary" signs attached to it.</p>
14.79	<p>Point for the center N-S-SE 1/256 sec. cor. of sec. 28.</p> <p>Set an alum. post, 28 ins. long, 2 1/2 ins. diam., 23 ins. in the ground, encircled by a collar of stone, with alum. cap mkd.</p> <p style="text-align: center;">T 13 N R 2 W</p> <p style="text-align: center;">S28</p> <p style="text-align: center;">C-N-S-SE</p> <p style="text-align: center;">1/256</p> <p style="text-align: center;">2007</p> <p>Deposit a magnet, in a white plastic case, at the base of the alum. post.</p> <p>Set a steel fence post nearby, with "Land Survey Monument" and "Property Boundary" signs attached to it.</p>

**Survey of Partial Subdivision of Section 28,
T. 13 N., R. 2 W., Gila and Salt River Meridian, Arizona**

CHAINS	
	Cor. falls in easterly edge of an old baseball field.
18.45	Groom Creek, 5 ft. wide, course S. 30° W.
19.72	<p>The SE 1/16 sec. cor. of sec. 28, established by Linda S. Smith, Arizona R.L.S. No. 18554, in 1985, according to Plat LS05-052, Book 5 of Land Surveys, Page 52, filed at the Yavapai County Courthouse, dated February 20 1986, and Arizona Land Survey Monument Record, Instrument No. 6124, Book 1795, Page 861, filed at the Yavapai County Courthouse, dated February 20, 1986, monumented with an alum. rod, 3/4 in. diam., firmly set, projecting 1 in. above the ground, with an alum. cap mkd. SE 1/16 S28 LS18554 1985. This is accepted as a careful and faithful establishment of the cor. position, from which the bearing trees mkd. in 1985</p> <p style="padding-left: 40px;">A pine, 10 ins. diam., bears S. 30° E., 21 lks. dist., with fragmentary scribe marks visible on a partially healed blaze.</p> <p style="padding-left: 40px;">A pine, 14 ins. diam., bears S. 75° W., 9 lks. dist., with fragmentary scribe marks visible on a partially healed blaze.</p> <p>An alum. sign post is set alongside the iron post, with "Land Survey Monument" and "Property Boundary" signs attached.</p> <p>Add the marks 2007 to the alum. cap.</p> <hr style="width: 20%; margin: 10px auto;"/> <p>N. 0°54' W., beginning new measurement.</p>
0.40	Dirt road, 12 ft. wide, bears N. 75° E. and S. 85° W.
2.46	<p>Point for a 1/1024 sec. cor. of sec. 28.</p> <p>Set an alum. post, 28 ins. long, 2 1/2 ins. diam., 23 ins. in the ground, with alum. cap mkd.</p> <p style="text-align: center;">T 13 N R 2 W</p> <p style="text-align: center;">1/1024</p> <p style="text-align: center;">2007</p> <p>Deposit a magnet, in a white plastic case, at the base of the alum. post.</p> <p>Cor. falls in a barbed wire fence, 4 strand, bears N. and S.</p>
19.71	The center E. 1/16 sec. cor. of sec. 28.

**Survey of Partial Subdivision of Section 28,
T. 13 N., R. 2 W., Gila and Salt River Meridian, Arizona**

CHAINS	
	<p>Land, rolling. Soil, decomposed granite. Timber, pine and oak.</p> <hr/> <p>From the S. 1/16 sec. cor. of secs. 27 and 28.</p> <p>S. 88°34' W., on the E. and W. center line of the SE 1/4 of sec. 28.</p> <p>Over rolling terrain, through pine timber and scrub oak.</p>
20.65	<p>The SE 1/16 sec. cor. of sec. 28.</p> <hr/> <p>S. 88°32' W., beginning new measurement.</p>
10.32	<p>Point for the center W-SE 1/64 sec. cor. of sec. 28.</p> <p>Set an alum. post, 28 ins. long, 2 1/2 ins. diam., 23 ins. in the ground, with alum. cap mkd.</p> <p style="text-align: center;">T 13 N R 2 W S28 C-W-SE 1/64</p> <p style="text-align: center;">2007</p> <p>Deposit a magnet, in a white plastic case, at the base of the alum. post.</p> <p>Set a steel fence post nearby, with "Land Survey Monument" and "Property Boundary" signs attached to it.</p>
20.64	<p>The center S. 1/16 sec. cor. of sec. 28.</p> <p>Land, rolling. Soil, decomposed granite. Timber, pine and oak.</p> <hr/> <p>From the N-S-S 1/256 sec. cor. of secs. 27 and 28.</p> <p>S. 88°53' W., on the E. and W. center line of the N. 1/2 of the SE 1/4 of sec. 28.</p> <p>Over rolling terrain, through pine timber and scrub oak.</p>
20.455	<p>The center N-S-SE 1/256 sec. cor. of sec. 28.</p>

**Survey of Partial Subdivision of Section 28,
T. 13 N., R. 2 W., Gila and Salt River Meridian, Arizona**

CHAINS	
	<p>Land, rolling. Soil, decomposed granite. Timber, pine and oak.</p> <hr/> <p>From the point for a 1/1024 sec. cor. of sec. 28, on the N. and S. center line of the SW 1/4 of the SE 1/4 of sec. 28.</p> <p>Set an alum. post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, in a mound of stone, 4 ft. base, to top, with alum. cap mkd.</p> <p align="center">T 13 N R 2 W</p> <p align="center">1/1024</p> <p align="center">2007</p> <p>Deposit a magnet, in a white plastic case, at the base of the alum. post.</p> <p>Set a steel fence post nearby, with "Land Survey Monument" and "Property Boundary" signs attached to it.</p> <p>Cor. falls near the top of a northerly slope.</p> <p>N. 2°01' W., on the N. and S. center line of the SW 1/4 of the SE 1/4 of sec. 28.</p> <p>Over rolling terrain, through pine timber and scrub oak.</p>
7.305	<p>The center W-SE 1/64 sec. cor. of sec. 28.</p> <p>Land, rolling. Soil, decomposed granite. Timber, pine and oak.</p> <hr/>
10.175	<p>From the 1/1024 sec. cor. of sec. 28, on the N. and S. center line of the SE 1/4 of sec. 28.</p> <p>S. 89°03' W., on the E. and W. center line of the S. 1/2 of the NE 1/4 of the SW 1/4 of the SE 1/4 of sec. 28.</p> <p>Over rolling terrain, through pine timber and scrub oak.</p> <p>The 1/1024 sec. cor. of sec. 28, on the N. and S. center line of SW 1/4 of the SE 1/4 of sec. 28.</p>

**Survey of Partial Subdivision of Section 28,
T. 13 N., R. 2 W., Gila and Salt River Meridian, Arizona**

CHAINS	
	<p>Land, rolling. Soil, boulders and dirt. Timber, pine and oak.</p> <hr/> <p>From the center W-SE 1/64 sec. cor. of sec. 28.</p> <p>N. 2°02' W., on the N. and S. center line of the NW 1/4 of the SE 1/4 of sec. 28.</p> <p>Over rolling terrain, through pine timber and scrub oak.</p>
0.70	Dirt road, 10 ft. wide, bears N. 75° E. and S. 75° W.
2.43	<p>Point for a 1/1024 sec. cor. of sec. 28.</p> <p>Set an alum. post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with alum. cap mkd.</p> <p style="text-align: center;">T 13 N R 2 W</p> <p style="text-align: center;">1/1024</p> <p style="text-align: center;">2007</p> <p>Deposit a magnet, in a white plastic case, at the base of the alum. post.</p> <p>Set a steel fence post nearby, with "Land Survey Monument" and "Property Boundary" signs attached to it.</p> <p>Land, rolling. Soil, decomposed granite. Timber, pine and oak.</p> <hr/> <p>From a 1/1024 sec. cor. of sec. 28, on the N. and S. center line of the SE 1/4 of sec. 28.</p> <p>S. 88°23' W., on the E. and W. center line of the S. 1/2 of the SE 1/4 of the NW 1/4 of the SE 1/4 of sec. 28.</p> <p>Over rolling terrain, through pine timber and scrub oak.</p>
10.365	The 1/1024 sec. cor. of sec. 28, on the N. and S. center line of the NW 1/4 of the SE 1/4 of sec. 28.

**Survey of Partial Subdivision of Section 28,
T. 13 N., R. 2 W., Gila and Salt River Meridian, Arizona**

CHAINS

**Survey of Partial Subdivision of Section 34,
T. 13 N., R. 2 W., Gila and Salt River Meridian, Arizona**

From the center N. 1/16 sec. cor. of sec. 34.

S. 88°41' E., on the E. and W. center line of the NE 1/4 of sec. 34.

Over rolling terrain, through pine timber and scrub oak.

9.905 Point for the center W-NE 1/64 sec. cor. of sec. 34.

Set a brass tablet, 3 1/4 ins. diam., 3 1/2 in. stem, in drill hole in granite bedrock, 3 ins. below top of outcrop, with top mkd.

T 13 N R 2 W
S34
C-W-NE
1/64

2007

Deposit broken pieces of a magnet, at base of stem in drill hole.

Raise a mound of stone, 3 ft. base, 3 ft. high, N. of cor.

21.135 Intersect line 3-4, Emporia lode, M.S. No. 4226, point for a closing cor.

Set an alum. post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with alum. cap mkd.

T 13 N R 2 W

CC
N ————— N
S34 MS4226

2007

Deposit a magnet, in a white plastic case, at the base of the alum. post.

Set a steel fence post nearby, with "Attention" and "Property Boundary" signs attached to it.

**Survey of Partial Subdivision of Section 34,
T. 13 N., R. 2 W., Gila and Salt River Meridian, Arizona**

CHAINS	
3.91	<p>From this cor. point, the N. 1/16 sec. cor. of secs. 34 and 35, bears S. 88°41' E., 18.485 chs. dist.</p> <p>Land, rolling. Soil, decomposed granite. Timber, pine and oak.</p> <hr/> <p>From the S-N 1/64 sec. cor. of secs. 34 and 35.</p> <p>N. 88°42' W., on the E. and W. center line of the SE 1/4 of the NE 1/4 of sec. 34.</p> <p>Over rolling terrain, through pine timber and scrub oak.</p> <p>Intesect line 4-1, Emporia lode, M.S. No. 4226, point for a closing cor.</p> <p>Set an alum. post, 28 ins. long, 2 1/2 ins. diam., 25 ins. in the ground, with alum. cap mkd.</p> <div style="text-align: center;"> <p>T 13 N R 2 W</p> </div> <p>Deposit a magnet, in a white plastic case, at the base of the alum. post.</p> <p>Set a steel fence post nearby, with "Attention" and "Property Boundary" signs attached to it.</p> <p>Land, rolling. Soil, decomposed granite. Timber, pine and oak.</p> <hr/> <p>From the center W-E 1/64 sec. cor. of sec. 34.</p> <p>N. 1°15' E., on the N. and S. center line of the SW 1/4 of the NE 1/4 of sec. 34.</p> <p>Over rolling terrain, through pine timber and scrub oak.</p>
20.505	<p>The center W-NE 1/64 sec. cor. of sec. 34.</p> <p>Land, rolling. Soil, decomposed granite. Timber, pine and oak.</p>

**Survey of Partial Subdivision of Section 34,
T. 13 N., R. 2 W., Gila and Salt River Meridian, Arizona**

CHAINS	
	<hr/> <p>From the S. 1/16 sec. cor. of secs. 34 and 35.</p> <p>N. 88°45' W., on the E. and W. center line of the SE 1/4 of sec. 34.</p> <p>Over rolling terrain, through pine timber and scrub oak.</p>
3.70	<p>Wolf Creek road, a dirt road, 18 ft. wide, bears N. 65° E. and S. 65° W.</p>
29.49	<p>Point for the center W-SE 1/64 sec. cor. of sec. 34.</p> <p>Set an alum. post, 28 ins. long, 2 1/2 ins. diam., 25 ins. in the ground, with alum. cap mkd.</p> <p style="text-align: center;">T 13 N R 2 W S34 C-W-SE 1/64</p> <p style="text-align: center;">2007</p> <p>Deposit a magnet, in a white plastic case, at the base of the alum. post.</p> <p>Set a steel fence post nearby, with "Land Survey Monument" and "Property Boundary" signs attached to it.</p>
30.70	<p>Dirt road, 12 ft. wide, bears S. 65° E. and N. 65° W.</p>
39.32	<p>The center S. 1/16 sec. cor. of sec. 34.</p> <p>Land, rolling. Soil, decomposed granite. Timber, pine and oak.</p> <hr/>
	<p>From the center W-SE 1/64 sec. cor. of sec. 34.</p> <p>N. 1°13' E., on a the N. and S. center line of the NW 1/4 of the SE 1/4 of sec. 34.</p> <p>Over rolling terrain, through pine timber and scrub oak.</p>
20.53	<p>The center W-E 1/64 sec. cor. of sec. 34.</p>

**Survey of Partial Subdivision of Section 34,
T. 13 N., R. 2 W., Gila and Salt River Meridian, Arizona**

CHAINS	<p>Land, rolling. Soil, decomposed granite. Timber, pine and oak.</p> <hr/> <p style="text-align: center;">Survey of Partial Subdivision of Section 35, T. 13 N., R. 2 W., Gila and Salt River Meridian, Arizona</p> <hr/> <p>From the stand. 1/4 sec. cor. of sec. 35, on the S. bdy. of the Tp.</p> <p>N. 0°15' W., on the N. and S. center line of sec. 35.</p> <p>Over rolling terrain, through pine timber and scrub oak.</p> <p>20.585 Point for the center S. 1/16 sec. cor. of sec. 35.</p> <p>Set an alum. post, 28 ins. long, 2 1/2 ins. diam., 27 ins. in the ground, with alum. cap mkd.</p> <div style="text-align: center; margin: 20px 0;"> <p>T 13 N R 2 W</p> <p style="margin-left: 100px;">C</p> <p style="margin-left: 100px;"> </p> <p style="margin-left: 100px;">S 1/16 S 35</p> <p style="margin-left: 100px;"> </p> <p style="margin-left: 100px;">C</p> <p style="margin-left: 100px;">2007</p> </div> <p>from which</p> <p style="margin-left: 40px;">The marks X B0 on a granite boulder, 6 1/2 x 3 1/2 x 4 1/2 ft., bears N. 67 1/2° E., 47 lks. dist. The X is 3 1/2 ft. above the ground.</p> <p style="margin-left: 40px;">A pine, 9 ins. diam., bears N. 42 1/4° W., 70 lks. dist., mkd. X BT.</p> <p>Deposit a magnet, in a white plastic case, at the base of the alum. post.</p> <p>Set a steel fence post nearby, with a "Land Survey Monument" sign attached to it.</p> <p>41.05 Trail, 4 ft. wide, bears N. 70° E. and S. 70° W.</p> <p>41.17 Point for the center 1/4 sec. cor. of sec. 35, at intersection with the E. and W. center line.</p> <p>Set an stainless steel post, 28 ins. long, 2 1/2 ins. diam., 27 ins. in the ground, with brass cap mkd.</p>
--------	--


**Survey of Partial Subdivision of Section 35,
T. 13 N., R. 2 W., Gila and Salt River Meridian, Arizona**

CHAINS	
	<p>T 13 N R 2 W</p> <p>C 1/4 S35</p> <p>2007</p>
	<p>from which</p> <p style="padding-left: 40px;">The marks X BO on a granite boulder, 8 x 5 x 6 ft., bears N. 21 1/4° E., 37 lks. dist. The X is 4 1/2 ft. above the ground.</p> <p style="padding-left: 40px;">A pine, 15 ins. diam., bears S. 52° E., 38 lks. dist., mkd. C1/4 S35 BT.</p> <p>Deposit a magnet, in a white plastic case, at the base of the alum. post.</p> <p>Set a steel fence post nearby, with a "Land Survey Monument" sign attached to it.</p>
41.30	Drainage, 2 ft. wide, drains N. 80° W.
60.935	<p>Point for the center N. 1/16 sec. cor. of sec. 35.</p> <p>Set an alum. post, 28 ins. long, 2 1/2 ins. diam., 27 ins. in the ground, with alum. cap mkd.</p>
	<p>T 13 N R 2 W</p> <p style="margin-left: 100px;">C</p> <p style="margin-left: 100px;"> </p> <p style="margin-left: 100px;">N1/16 S 35</p> <p style="margin-left: 100px;"> </p> <p style="margin-left: 100px;">C</p> <p>2007</p>
	<p>from which</p> <p style="padding-left: 40px;">A pine, 11 ins. diam., bears S. 85° E., 57 1/2 lks. dist., mkd. CN1/16 S35 BT.</p> <p style="padding-left: 40px;">The marks X BO on a granite boulder, 6 x 6 x 7 1/2 ft., bears N. 11 3/4° W., 39 lks. dist. The X is 4 1/2 ft. above the ground.</p> <p>Deposit a magnet, in a white plastic case, at the base of the alum. post.</p> <p>Set a steel fence post nearby, with a "Land Survey Monument" sign attached to it.</p>

**Survey of Partial Subdivision of Section 35,
T. 13 N., R. 2 W., Gila and Salt River Meridian, Arizona**

CHAINS	
80.70	<p>The 1/4 sec. cor. of secs. 26 and 35.</p> <p>Land, rolling. Soil, decomposed granite. Timber, pine and oak.</p> <hr/> <p>From the 1/4 sec. cor. of secs. 35 and 36, monumented with an iron post, 1 in. diam., firmly set, projecting 18 ins. above the ground, in a mound of stone, 2 ft. base, 1 ft. high, with brass cap mkd. 1/4 S35 S36 1930, from which the bearing trees mkd. in 1930</p> <p style="padding-left: 40px;">An oak, 25 ins. diam., bears N. 35 3/4° E., 4 lks. dist., with a healed blaze. (Record: N. 20° E.)</p> <p style="padding-left: 40px;">A pine (dead), 24 ins. diam., bears N. 15° W., 31 lks. dist., with scribe marks 1/4 legible on a deteriorating blaze.</p> <p>At the corner point</p> <p>Rebuild the supporting mound of stone, 3 ft. base, to cap, and add marks 2007 to cap, from which new bearing trees</p> <p style="padding-left: 40px;">A pine, 9 ins. diam., bears S. 75°1/4 E., 80 lks. dist., mkd. 1/4 S36 BT.</p> <p style="padding-left: 40px;">An alligator juniper, 7 ins. diam., bears S. 67 3/4° W., 1.056 chs. dist., mkd. 1/4 S35 BT.</p> <p>S. 88°58' W., on the E. and W. center line of sec. 35.</p> <p>Over rolling terrain, through pine timber and scrub oak.</p>
42.40	The center 1/4 sec. cor. of sec. 35.
62.34	The center W. 1/16 sec. cor. of sec. 35, hereinbefore described.
67.35	<p>Point for the center E-W-W 1/256 sec. cor. of sec. 35.</p> <p>Set an alum. post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with alum. cap mkd.</p> <p style="text-align: center;">T 13 N R 2 W S35 C-E-W-W 1/256 2007</p>

**Survey of Partial Subdivision of Section 35,
T. 13 N., R. 2 W., Gila and Salt River Meridian, Arizona**

CHAINS	
	<p>Deposit a magnet, in a white plastic case, at the base of the alum. post.</p> <p>Set a steel fence post nearby, with "Land Survey Monument" and "Property Boundary" signs attached to it.</p>
79.06	Intersect line 1-2, Lost Chance lode, M.S. No. 2129, at a point from which cor. No. 1, bears N. 35°18' W., 5.10 chs. dist., not monumented.
82.37	<p>The 1/4 sec. cor. of secs. 34 and 35.</p> <p>Land, rolling. Soil, decomposed granite. Timber, pine and oak.</p> <hr/> <p>From the center S. 1/16 sec. cor. of sec. 35.</p> <p>S. 89°05' W., on the E. and W. center line of the SW 1/4 of sec. 35.</p> <p>Over rolling terrain, through pine timber and scrub oak.</p>
20.27	The SW 1/16 sec. cor. of sec. 35, hereinbefore described.
24.15	Senator Highway, dirt road at this point, 25 ft. wide, bears S. 5° E. and N. 60° W.
25.20	Wolf Creek, 6 ft. wide, course S.
25.35	<p>True point for the center E-W-SW 1/256 sec. cor. of sec. 35, falls on steep bank of creek where it is impracticable to establish a permanent monument. Set a steel fence post with a "Property Boundary" sign at this point.</p> <p>From the true point, a point selected for a witness cor., bears N. 49°27' W., 20 lks. dist.</p> <p>Set an alum. post, 28 ins. long, 2 1/2 ins. diam., 27 ins. in the ground, with alum. cap mkd.</p> <p style="text-align: center;">T 13 N R 2 W WC S35 C-E-W-SW  1/256 2007</p>

**Survey of Partial Subdivision of Section 35,
T. 13 N., R. 2 W., Gila and Salt River Meridian, Arizona**

CHAINS	
	Deposit a magnet, in a white plastic case, at the base of the alum. post.
	Set a steel fence post nearby, with a "Land Survey Monument" sign attached to it.
29.80	Wolf Creek road, a dirt road, 26 ft. wide, bears N. 15° E. and S. 35° W.
33.85	Wolf Creek road, a dirt road, 15 ft. wide, bears S. 60° E. and N. 60° W.
40.595	The S. 1/16 sec. cor. of secs. 34 and 35. Land, rolling. Soil, decomposed granite. Timber, pine and oak.
	From the true point for the center E-W-SW 1/256 sec. cor. of sec. 35. N. 0°53' E., on the N. and S. center line of the E. 1/2 of the NW 1/4 of the SW 1/4 of sec. 35. Over rolling terrain, through pine timber and scrub oak.
0.75	Senator Highway, dirt road at this point, 25 ft. wide, bears S. 70° E. and N. 80° W.
19.35	Dirt road, 10 ft. wide, bears E. and W.
20.54	The center E-W-W 1/256 sec. cor. of sec. 35. Land, rolling. Soil, decomposed granite. Timber, pine and oak.
	From the center N. 1/16 sec. cor. of sec. 35. S. 89°59' W., on the E. and W. center line of the NW 1/4 of sec. 35. Over rolling terrain, through pine timber and scrub oak.
18.40	Trail, 6 ft. wide, bears N. 45° E. and S. 45° W.
19.62	The NW 1/16 sec. cor. of sec. 35, hereinbefore described.
23.45	Senator Highway, asphalt surfaced, 24 ft. wide, bears N. 50° E. and S. 50° W.

**Survey of Partial Subdivision of Section 35,
T. 13 N., R. 2 W., Gila and Salt River Meridian, Arizona**

CHAINS	
39.31	<p>The N. 1/16 sec. cor. of secs. 34 and 35.</p> <p>Land, rolling. Soil, decomposed granite. Timber, pine and oak.</p> <hr/> <p>From the point for the center E-SW-NW 1/256 sec. cor. of sec. 35.</p> <p>Set an alum. post, 28 ins. long, 2 1/2 ins. diam., 27 ins. in the ground, with alum. cap mkd.</p> <p style="text-align: center;">T 13 N R 2 W S35 C-E-SW-NW 1/256 2007</p> <p>Deposit a magnet, in a white plastic case, at the base of the alum. post.</p> <p>Set a steel fence post nearby, with "Land Survey Monument" and "Property Boundary" signs attached to it.</p> <p>S. 89°28' W., on a portion of the E. and W. center line of the SW 1/4 of the NW 1/4 of sec. 35.</p> <p>Over rolling terrain, through pine timber and scrub oak.</p>
7.50	<p>Senator Highway, asphalt surfaced, 24 ft. wide, bears N. 5° E. and S.</p>
14.895	<p>The S-N 1/64 sec. cor. of secs. 34 and 35.</p> <p>Land, rolling. Soil, decomposed granite. Timber, pine and oak.</p> <hr/> <p>From the center E-W-W 1/256 sec. cor. of sec. 35.</p> <p>N. 0°54' E., on the N. and S. center line of the SE 1/4 of the SW 1/4 of the NW 1/4 of sec. 35.</p> <p>Over rolling terrain, through pine timber and scrub oak.</p>
1.25	<p>Utility line, 4 wire, bears E. and W.</p>
10.105	<p>The center E-SW-NW 1/256 sec. cor. of sec. 35.</p>

**Survey of Partial Subdivision of Section 35,
T. 13 N., R. 2 W., Gila and Salt River Meridian, Arizona**

CHAINS	<p>Land, rolling. Soil, decomposed granite. Timber, pine and oak.</p> <hr/> <p align="center">GENERAL DESCRIPTION</p> <hr/> <p>This survey is concerned with the subdivision of sections 27, 28, 34 and 35, in order to define lands near local "Camps". These lands are to be a part of the Yavapai Ranch land exchange.</p> <p>Primary access to this survey was the Senator Highway, which traverses northerly and southerly through the southerly portion of this township. The Senator Highway is a paved road until near line 1-2 of the Lost Chance lode, where it become a dirt road. Section 27 was accessed by Friendly Pines road, which is paved until the section line between sections 26 and 27, then is dirt. Section 28 was accessed by Maripai road, which is paved part of the way and dirt the rest. There are various Forest Service dirt roads that were also used to access different parts of this survey.</p> <p>The terrain is mountainous and rolling with areas of large granite outcrops and granite boulders. There are numerous creeks and drainages in the area. Groom Creek and Wolf Creek are the two named creeks that cut through the surveyed lands. Pine is the main timber in the area with smaller amounts of oak and juniper.</p> <p>The elevation ranges from 5,800 ft. to 6,800 ft.</p> <p>The mean magnetic declination of $11 \frac{3}{4}^{\circ}$ E. was derived from the United States Geological Survey computer program GEOMAG, utilizing the World Magnetic Model for Epoch 2005 for the dates of survey.</p> <hr/>
--------	--

CERTIFICATE OF SURVEY

I, Craig S. Dukart, Cadastral Surveyor, HEREBY CERTIFY upon honor, that in pursuance of special instructions bearing date of the 11th day of July, 2007, I have dependently resurveyed a portion of the Third Standard Parallel North (south boundary), a portion of the subdivisional lines, a portion of the Fort Whipple Timber Reserve and Patented Mining Claims, Mineral Survey Nos. 2129 and 4226, and surveyed the subdivision of secs. 27, 28, 34 and 35, T. 13 N., R. 2 W., Gila and Salt River Meridian, in the State of Arizona, which are represented in the foregoing field notes as having been executed by me and under my direction. Said survey has been made in strict conformity with said special instructions, the Manual of Instructions for the Survey of the Public Lands of the United States, 1973 and in specific manner described in the foregoing field notes.

Nov. 17, 2008
(Date)

Craig S. Dukart
(Cadastral Surveyor)

CERTIFICATE OF APPROVAL

BUREAU OF LAND MANAGEMENT
Phoenix, Arizona

The foregoing field notes of the dependent resurvey of a portion of the Third Standard Parallel North (south boundary), a portion of the subdivisional lines, a portion of the Fort Whipple Timber Reserve and Patented Mining Claims, Mineral Survey Nos. 2129 and 4226 and the subdivision of secs. 27, 28, 34 and 35, T. 13 N., R. 2 W., Gila and Salt River Meridian, in the State of Arizona, executed by Craig S. Dukart, Cadastral Surveyor, having been critically examined and found correct, are hereby approved.

6/8/2009
(Date)

Stephen K. Hansen
(Chief Cadastral Surveyor of Arizona)

~~CERTIFICATE OF TRANSCRIPT~~

~~I CERTIFY That the foregoing transcript of the field notes of the above described surveys in T. 13 N., R. 2 W., Gila and Salt River Meridian, Arizona, is a true copy of the original field notes.~~

~~_____
(Date)~~

~~_____
(Chief Cadastral Surveyor of Arizona)~~