

ORIGINAL

**UNITED STATES  
DEPARTMENT OF THE INTERIOR  
BUREAU OF LAND MANAGEMENT**

FIELD NOTES  
OF THE  
DEPENDENT RESURVEY OF A PORTION  
OF THE SECOND GUIDE MERIDIAN EAST(WEST BOUNDARY) ,  
A PORTION OF THE NORTH BOUNDARY,  
A PORTION OF THE SECTIONAL CORRECTION LINE,  
A PORTION OF THE SUBDIVISIONAL LINES  
AND THE  
SUBDIVISION OF SECTION 9  
**TOWNSHIP 14 SOUTH, RANGE 11 EAST,**  
OF THE GILA AND SALT RIVER MERIDIAN,  
IN THE STATE OF ARIZONA.

**EXECUTED BY**

**Joe R. Salazar, Cadastral Surveyor**

Under Special Instructions dated October 20, 2008, approved October 20, 2008, which provided for the surveys included under Group No. 1056, and assignment instructions dated October 20, 2008.

**Survey commenced December 8, 2008**

**Survey completed May 5, 2009**

**INDEX DIAGRAM**

TOWNSHIP 14 SOUTH                      RANGE 11 EAST  
 GILA AND SALT RIVER MERIDIAN, ARIZONA

7	7	6			
6	5	4	3	2	1
		21			
7	8	20 9	15 10	11	12
26	26	20			
6 18	25 17	19 16	13 15	14	13
25	25	19			
5 19	24 20	18 21	11 22	23	24
23	22	17			
4 30	22 29	17 28	10 27	26	25
9	9	8			
4 31	32	33	34	35	36

**T. 14 S., R. 11 E., Gila and Salt River Meridian, Arizona**

## CHAINS

The following field notes describe the dependent resurvey of the Second Guide Meridian East (west boundary), a portion of the north boundary, a portion of the sectional correction line, a portion of the subdivisional lines and a survey of the subdivision of section 9, Township 14 South, Range 11 East, Gila and Salt River Meridian, Arizona.

The history of surveys pertaining to this survey is as follows:

Philip Contzen resurveyed the Second Guide Meridian East (west boundary) in 1895. Philip Contzen surveyed the north and east boundaries, resurveyed the south boundary and surveyed the subdivisional lines in 1903. William H. Thorn and Otis O. Gould resurveyed the east boundary in 1925-26. William E. Heister resurveyed a portion of the north boundary in 1932. Joe R. Salazar resurveyed a portion of the Second Guide Meridian East (west boundary) and a portion of the subdivisional lines and surveyed the subdivision of section 7 in 2003. Joe R. Salazar resurveyed a portion of the south and west boundaries and a portion of the subdivisional lines and surveyed the subdivision of sections 6, 17 and 20 in Township 13 South, Range 10 East in 2001-02.

The survey was executed in accordance with the specifications as set forth in the Manual of Instructions for the Survey of the Public Lands of the United States, 1973, and the Special Instructions dated October 20, 2008, for Group Number 1056, Arizona.

The true meridian direction and length of all lines were determined by real time kinematic global positioning system observations using Trimble Navigation 5700 model receivers.

Preliminary to the resurvey, the lines of the prior surveys were retraced and search was made for all corners and other calls of record. Identified corners were remonumented in their original positions. Lost corners were reestablished and remonumented at proportionate positions based on the official record. The retracement data were thoroughly verified and only the true line field notes are given herein.

Geodetic control was derived from Global Positioning System (GPS) static observations post processed by National Geodetic Survey, Online Positioning User Service (OPUS), utilizing Continuously Operating Reference Stations (CORS) AZCL COOLIDGE, AZKR KEARNY and COT2 CITY OF TUCSON 2. The NAD 83 (CORS96) (EPOCH: 2002.0000) (EPOCH: 2008.8248) geographic position of the corner of Townships 14 and 15 South, Ranges 10 and 11 East is as follows:

Latitude: 32°09'39.72" N.

Longitude: 111°16'11.60" W.

**T. 14 S., R. 11 E., Gila and Salt River Meridian, Arizona**

CHAINS

The mean magnetic declination is  $10 \frac{3}{4}^{\circ}$  E.

---

**Dependent Resurvey of a Portion of the  
Second Guide Meridian East (West Boundary),  
T. 14 S., R. 11 E., Gila and Salt River Meridian, Arizona**

---

Restoring the survey executed by  
Philip Contzen, in 1895

---

Beginning at the cor. of Tps. 14 and 15 S., Rgs. 10 and 11 E., monumented with a malpais stone, 10 X 8 ins., 18 ins. below the surface of the ground, clearly mkd. with 4 grooves on E. face, 1 groove on S. face, 4 grooves on W. face and 2 grooves on N. face.

At the corner point

Set a stainless steel post, 28 ins. long,  $2 \frac{1}{2}$  ins. diam., 18 ins. in the ground, over orig. stone, in a mound of hardened concrete blocks, 3 ft. base, to top, with brass cap mkd.

T 14 S	
R 10 E	R 11 E
S 36	S 31
S 1	S 6
T 15 S	

2009

Deposit a magnet, in a white plastic case, at the base of the stainless steel post.

N.  $0^{\circ}03'$  W., bet. secs. 31 and 36, on the W. bdy. of the Tp.

Over nearly level terrain, through scattered mesquite bushes and cactus.

39.965 Point for the  $\frac{1}{4}$  sec. cor. of secs. 31 and 36, at proportionate dist; there is no remaining evidence of the orig. cor.

Cor. not monumented.

79.93 Point for the cor. of secs. 25, 30, 31 and 36, at proportionate dist.; there is no remaining evidence of the orig. cor.

Cor. not monumented.

---

N.  $0^{\circ}03'$  W., bet. secs. 25 and 30.

**Dependent Resurvey of a Portion of the  
Second Guide Meridian East (West Boundary),  
T. 14 S., R. 11 E., Gila and Salt River Meridian, Arizona**

CHAINS									
	Over nearly level terrain, through scattered mesquite bushes and cactus.								
39.965	Point for the 1/4 sec. cor. of secs. 25 and 30, at proportionate dist.; there is no remaining evidence of the orig. cor.  Cor. not monumented.								
79.93	Point for the cor. of secs. 19, 24, 25 and 30, at proportionate dist.; there is no remaining evidence of the orig. cor.  Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.  <div style="text-align: center;"> <table style="margin: auto;"> <tr><td colspan="2">T 14 S</td></tr> <tr><td>R 10 E</td><td>R 11 E</td></tr> <tr><td>S 24</td><td>S 19</td></tr> <tr><td>S 25</td><td>S 30</td></tr> </table> <p>2009</p> </div> Deposit a magnet, in a white plastic case, at the base of the stainless steel post.  From this cor. point, a local monument set by Robert Douglas Miller, Arizona Registered Land Surveyor No. 13564 and recorded in the Pima County Department of Transportation, Section Corner Reference Sheet, bears N. 59°05' E., 40 lks. dist., monumented with an iron pipe, 1 in. diam., firmly set, projecting 3 ins. above the ground, with aluminum cap mkd. T14S R11E R10E 24 19 25 30 14 10 RLS 13564. This monument is not utilized in the course of this survey.  <hr/> N. 0°03' W., bet. secs. 19 and 24, enter Tohono O'Odham Indian Reservation.  Over nearly level terrain, through scattered mesquite bushes and cactus.	T 14 S		R 10 E	R 11 E	S 24	S 19	S 25	S 30
T 14 S									
R 10 E	R 11 E								
S 24	S 19								
S 25	S 30								
0.62	Barbed wire fence, 4 strand, bears E. and W., thence over nearly level terrain, through cleared land.								
4.70	Center of paved road, 25 ft. wide, bears E. and W.								
4.90	Enter cultivated fields.								
39.965	Point for the 1/4 sec. cor. of secs. 19 and 24, at proportionate dist.; there is no remaining evidence of the orig. cor.  Cor. not monumented.								

**Dependent Resurvey of a Portion of the  
Second Guide Meridian East (West Boundary),  
T. 14 S., R. 11 E., Gila and Salt River Meridian, Arizona**

CHAINS	
79.93	<p>Point for the cor. of secs. 13, 18, 19 and 24, at proportionate dist.; there is no remaining evidence of the orig. cor.</p> <p>Cor. not monumented.</p> <hr/> <p>N. 0°03' W., bet. secs. 13 and 18.</p> <p>Over nearly level terrain, through cultivated fields.</p>
27.50	Leave cultivated fields.
27.70	Center of graded road, bears E. and W.
27.90	Enter nearly level terrain, through scattered mesquite bushes and cactus.
39.965	<p>Point for the 1/4 sec. cor. of secs. 13 and 18, at proportionate dist.; there is no remaining evidence of the orig. cor.</p> <p>Cor. not monumented.</p>
79.93	<p>The cor. of secs. 7, 12, 13 and 18, monumented with a stainless steel post, 2 1/2 ins. diam., firmly set, projecting 4 ins. above the ground, with brass cap mkd. T14S R10E R11E S12 S7 S13 S18 2003.</p> <p>Add the marks 2008 to the brass cap.</p> <hr/> <p style="text-align: center;"><b>Dependent Resurvey of a Portion of the North Boundary, T. 14 S., R. 11 E., Gila and Salt River Meridian, Arizona</b></p> <hr/> <p style="text-align: center;">Restoring the survey executed by Philip Contzen, in 1903</p> <hr/> <p>From the cor. of secs. 3, 4, 33 and 34, on the N. bdy. of the Tp., determined from the remaining 1932 bearing tree</p> <p style="padding-left: 40px;">A dead and standing ironwood, 9 ins. diam., bears N. 22° E., 2.65 chs. dist., clearly mkd. T13N R11E S34 BT on an open blaze.</p> <p>Cor. not monumented.</p> <p>Cor. point is located in Mile Wide Road.</p> <p>S. 89°55' W., bet. secs. 4 and 33.</p> <p>Along Mile Wide Road.</p>

**Dependent Resurvey of a Portion of the North Boundary,  
T. 14 S., R. 11 E., Gila and Salt River Meridian, Arizona**

CHAINS	
40.19	<p>Point for the 1/4 sec. cor. of secs. 4 and 33, at proportionate dist.; there is no remaining evidence of the orig. cor.</p> <p>Cor. not monumented.</p> <p>Cor. point is located in Mile Wide Road.</p>
80.38	<p>Point for the cor. of secs. 4, 5, 32 and 33, at proportionate dist.; there is no remaining evidence of the orig. cor.</p> <p>Cor. not monumented.</p> <p>Cor. point is located in Mile Wide Road.</p> <hr/>
	<p>S. 89°55' W., bet. secs. 5 and 32.</p> <p>Along Mile Wide Road.</p>
40.19	<p>Point for the 1/4 sec. cor. of secs. 5 and 32, at proportionate dist.; there is no remaining evidence of the orig. cor.</p> <p>Cor. not monumented.</p> <p>Cor. point is located in Mile Wide Road.</p>
80.38	<p>Point for the cor. of secs. 5, 6, 31 and 32, at proportionate dist.; there is no remaining evidence of the orig. cor.</p> <p>Cor. not monumented.</p> <p>Cor. point is located in Mile Wide Road.</p> <hr/>
	<p>S. 89°55' W., bet. secs. 6 and 31.</p> <p>Along Mile Wide Road.</p>
40.19	<p>The 1/4 sec. cor. of secs. 6 and 31, monumented by person(s) unknown and recorded in the Pima County Recorders Office on an Arizona Land Survey Monument Reference Record, with a rebar, 3/8 in. diam., firmly set, flush with pavement, at intersection with Mile Wide Road, bears E. and W. and a graded road, bears N.</p> <hr/>
	<p>N. 89°53' W., beginning new measurement.</p>
42.41	<p>The cor. of Tps. 13 and 14 S., Rgs. 10 and 11 E., monumented with a stainless steel post, 2 1/2 ins. diam., firmly set, projecting 4 ins. above the ground, with brass cap mkd. T13S R10E R11E S36 S31 S1 S6 T14S 2002.</p>

**Dependent Resurvey of a Portion of the North Boundary,  
T. 14 S., R. 11 E., Gila and Salt River Meridian, Arizona**

CHAINS

Add the marks 2009 to the brass cap.

---

**Dependent Resurvey of a Portion of the  
Sectional Correction Line,  
T. 14 S., R. 11 E., Gila and Salt River Meridian, Arizona**

---

Restoring the survey executed by  
Philip Contzen, in 1903

---

From the point for the cor. of secs. 27, 28, 33 and 34, on the sectional correction line, at proportionate dist.; there is no remaining evidence of the orig. cor.

Cor. point falls in Sandario Road, not monumented.

From this cor. point, the cor. of secs. 25 and 36 only, on the E. bdy. of the Tp., bears N. 89°57' E., 240.57 chs. dist., monumented with an iron post, 2 1/2 ins. diam., firmly set, 8 ins. below the surface of the ground, with brass cap mkd. T14S S25 S31 S36 R11E R12E 1925. Add the marks 2009 to the brass cap.

This control line was fully retraced and a careful search was made for evidence of intervening cors., none of which were recovered.

From this same cor. point, the 1/4 sec. cor. of secs. 33 and 34, perpetuated by person(s) unknown and recorded in the Pima County Recorders Office on an Arizona Land Survey Monument Reference Record, bears S. 0°23' E., 39.14 chs. dist., determined from ties recorded in the Pima County Department of Transportation, Section Corner Reference Sheet, falls in Sandario Road.

from which local reference monuments

An aluminum cap, 3 ins. diam., incased in concrete, 24 ins. diam., projecting 1 in. above the ground, bears N. 35°53' E., 1.72 chs. dist., with aluminum cap mkd. PIMA COUNTY NN-37 1991 SURVEY POINT DEPT OF TRANSPORTATION FLOOD CONTROL DISTRICT.

A stainless steel washer, 2 ins. diam., nailed to a utility pole, 14 ins. from bottom, bears S. 7°37' E., 2.48 chs. dist.

A rebar, 1/2 in. diam., firmly set, projecting 1 in. above the ground, bears S. 35°53' W., 1.61 chs. dist. with attached washer, 2 ins. diam., mkd. PC DOT 22 REF.

S. 89°57' W., bet. secs. 28 and 33.



**Dependent Resurvey of a Portion of the Sectional Correction Line,  
T. 14 S., R. 11 E., Gila and Salt River Meridian, Arizona**

CHAINS	
	Over nearly level terrain.
1.30	Right-of-way fence, bears N. and S., thence along scattered mesquite and cactus.
40.095	Point for the 1/4 sec. cor. of secs. 28 and 33, at proportionate dist.; there is no remaining evidence of the orig. cor.  Cor. not monumented.
80.19	Point for the cor. of secs. 28, 29, 32 and 33, at proportionate dist.; there is no remaining evidence of the orig. cor.  Cor. not monumented.
	From this cor. point, a local monument, set by person(s) unknown and recorded in the Pima County Recorders Office on an Arizona Land Survey Monument Reference Record, bears N. 8°11' W., 12 lks. dist., monumented with an iron post, 2 1/2 ins. diam., firmly set, projecting 8 ins. above the ground, with lead cap mkd., T14S R11E 29 28 32 33. This monument is not utilized in the course of this survey.
	S. 89°57' W., bet. secs. 29 and 32.
	Over nearly level terrain, through scattered mesquite bushes and cactus.
40.095	Point for the 1/4 sec. cor. of secs. 29 and 32, at proportionate dist.; there is no remaining evidence of the orig. cor.  Cor. not monumented.
80.19	Point for the cor. of secs. 29, 30, 31 and 32, at proportionate dist.; there is no remaining evidence of the orig. cor.  Cor. not monumented.
	From this cor. point, a local monument, set by person(s) unknown and recorded in the Pima County Recorders Office on an Arizona Land Survey Monument Reference Record, bears N. 79°18' E., 0.67 chs. dist., monumented with an iron post, 2 1/2 ins. diam., firmly set, projecting 3 ins. above the ground, with brass cap mkd. T14S R11E 30 29 31 32. This monument is not utilized in the course of this survey.
	S. 89°57' W., bet. secs. 30 and 31.
	Enter nearly level terrain, through scattered mesquite bushes and cactus.

**Dependent Resurvey of a Portion of the Sectional Correction Line,  
T. 14 S., R. 11 E., Gila and Salt River Meridian, Arizona**

CHAINS	
40.095	<p>Point for the 1/4 sec. cor. of secs. 30 and 31, at proportionate dist.; there is no remaining evidence of the orig. cor.</p> <p>Cor. not monumented.</p>
83.12	<p>The point for the cor. of secs. 25, 30, 31 and 36, on the W. bdy. of the Tp., hereinbefore described.</p>
<hr/> <p><b>Dependent Resurvey of a Portion of the Subdivisional Lines, T. 14 S., R. 11 E., Gila and Salt River Meridian, Arizona</b></p> <hr/>	
<p>Restoring the survey executed by Philip Contzen, in 1903</p> <hr/>	
<p>From the point for the cor. of secs. 27, 28, 33 and 34, hereinbefore described.</p>	
<p>N. 0°02' W., bet. secs. 27 and 28.</p>	
<p>Along Sandario Road, a paved road, 25 ft. wide.</p>	
40.07	<p>Point for the 1/4 sec. cor. of secs. 27 and 28, at proportionate dist.; there is no remaining evidence of the orig. cor.</p> <p>Cor. not monumented.</p>
<p>From this cor. point, a local monument, set by person(s) unknown and recorded in the Pima County Department of Transportation, Section Corner Reference Sheet, bears N. 12°09' E., 14 lks. dist., monumented with and iron post, 2 ins. diam., firmly set, 6 ins. below the surface of Sandario Road. This monument is not utilized in the course of this survey.</p>	
80.14	<p>Point for the cor. of secs. 21, 22, 27 and 28, at proportionate dist.; there is no remaining evidence of the orig. cor.</p> <p>Set a PK nail in Sandario Road.</p>
<p>from which</p>	
<p style="padding-left: 40px;">A stainless steel post, 28 ins. long, 2 1/2 ins. diam., set 24 ins. in the ground for a reference monument, bears S. 50°15' W., 49.0 ft. dist. with brass cap mkd. RM T14S R11E 49.0 FT TO COR S28 2009 and an arrow pointing to the cor. Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p>	

**Dependent Resurvey of a Portion of the Subdivisional Lines,  
T. 14 S., R. 11 E., Gila and Salt River Meridian, Arizona**

CHAINS	
	<p>A stainless steel post, 28 ins. long, 2 1/2 ins. diam., set 24 ins. in the ground for a reference monument, bears N. 54°00' W., 47.0 ft. dist. with brass cap mkd. RM T14S R11E 47.0 FT TO COR S21 2009 and an arrow pointing to the cor. Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p> <p>Reference monuments are located in the westerly right-of-way fence, bears N. and S.</p> <p>From this cor. point, the 1/4 sec. cor. of secs. 24 and 25, bears N. 89°56' E., 200.33 chs. dist., perpetuated by the U. S. Dept. of Interior, Bureau of Reclamation and recorded in the Pima County Department of Transportation, Section Corner Reference Sheet, monumented with an aluminum post, 2 1/2 ins. diam., firmly set, projecting 4 ins. above the ground, with aluminum cap mkd. U S DEPT. OF INTERIOR T14S R11E 1/4 S24 S25 1985 CADASTRAL SURVEY BUREAU OF RECLAMATION. This position is accepted as a true and faithful perpetuation of the orig. cor.</p> <p>from which the remaining orig. bearing tree</p> <p>A dead mesquite stump, 12 ins. diam., bears N. 16° W., 1.76 chs. dist., mkd. 24 and other illegible marks on an open blaze.</p> <p>This control line was fully retraced and a careful search was made for evidence of intervening cors., none of which were recovered.</p> <p>From this same cor. point, a local monument, set by person(s) unknown and recorded in the Pima County Recorders Office on an Arizona Land Survey Monument Reference Record, bears S. 56°06' E., 77 lks. dist., monumented with a rebar, 1/2 in. diam., firmly set, 7 ins. below the surface of the ground. This monument is not utilized in the course of this survey.</p> <p>From this same cor. point, a local monument, set by person(s) unknown and recorded in the Pima County Recorders Office on an Arizona Land Survey Monument Reference Record, bears N. 36°28' W., 97 lks. dist., monumented with a rebar, 3/8 in. diam., firmly set, 4 ins. below the surface of the ground. This monument is not utilized in the course of this survey.</p> <hr/> <p>N. 0°14' W., bet. secs. 21 and 22, identical with the Tohono O'Odham Indian Reservation boundary.</p> <p>Along Sandario Road.</p>
40.07	Point for the 1/4 sec. cor. of secs. 21 and 22, at proportionate dist.; there is no remaining evidence of the orig. cor.

**Dependent Resurvey of a Portion of the Subdivisional Lines,  
T. 14 S., R. 11 E., Gila and Salt River Meridian, Arizona**

CHAINS

Set a PK nail in Sandario Road.

from which

A stainless steel post, 28 ins. long, 2 1/2 ins. diam., set 24 ins. in the ground for a reference monument, bears S. 52°33' W., 41.0 ft. dist., with brass cap mkd. RM T14S R11E 41.0 FT TO COR 1/4 S21 2009 and an arrow pointing to the cor. Deposit a magnet, in a white plastic case, at the base of the stainless steel post.

A stainless steel post, 28 ins. long, 2 1/2 ins. diam., set 24 ins. in the ground for a reference monument, bears N. 47°26' W., 44.0 ft. dist., with brass cap mkd. RM T14S R11E 44.0 FT TO COR 1/4 S21 2009 and an arrow pointing to the cor. Deposit a magnet, in a white plastic case, at the base of the stainless steel post.

Reference monuments are located in westerly right-of-way fence, bears N. and S.

80.14 Point for the cor. of secs. 15, 16, 21 and 22, at proportionate dist.; there is no remaining evidence of the orig. cor.

Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 6 ins. below the surface of the ground, with brass cap mkd.

T 14 S	R 11 E
S 16	S 15
S 21	S 22

2009

Deposit a magnet, in a white plastic case, at the base of the stainless steel post.

Cor. is located 5 lks. W. of the W. edge of Sandario Road.

From this cor. point, the 1/4 sec. cor. of secs. 14 and 23, bears N. 89°56' E., 119.89 chs. dist., perpetuated by the U. S. Dept. of Interior, Bureau of Reclamation and recorded in the Pima County Department of Transportation, Section Corner Reference Sheet, monumented with an aluminum post, 2 1/2 ins. diam., firmly set, flush with the ground, with aluminum cap mkd. U S DEPT. OF INTERIOR T14S R11E 1/4 S14 S23 1985 CADASTRAL SURVEY BUREAU OF RECLAMATION. This position is accepted as a true and faithful perpetuation of the orig. cor.

from which the remaining orig. bearing tree

**Dependent Resurvey of a Portion of the Subdivisional Lines,  
T. 14 S., R. 11 E., Gila and Salt River Meridian, Arizona**

CHAINS

A mesquite bush, 10 ins. diam., bears S. 34° E., 2.73 chs. dist., with illegible marks visible on a partially healed blaze.

This control line was fully retraced and a careful search was made for evidence of intervening cors., none of which were recovered.

From this same cor. point, a local monument, set by person(s) unknown and recorded in the Pima County Recorders Office on an Arizona Land Survey Monument Reference Record, bears S. 74°59' E., 1.44 chs. dist., monumented with a rebar, 5/8 in. diam., firmly set, projecting 4 ins. above the ground, with aluminum cap mkd. USBR ROW 75.00 R-5. This monument is not utilized in the course of this survey.

From this same cor. point, a local monument, set by person(s) unknown and recorded in the Pima County Recorders Office on an Arizona Land Survey Monument Reference Record, bears S. 43°19' W., 52 lks. dist., monumented with a rebar, 1/2 in. diam., firmly set, flush with the ground, with aluminum cap mkd. RLS 19316 ROW. This monument is not utilized in the course of this survey.

From this same cor. point, a local monument, set by person(s) unknown and recorded in the Pima County Recorders Office on an Arizona Land Survey Monument Reference Record, bears N. 56°45' W., 43 lks. dist., monumented with a rebar, 1/2 in. diam., firmly set, flush with the ground. This monument is not utilized in the course of this survey.

---

N. 0°06' E., bet. secs. 15 and 16, identical with the Tohono O'Odham Indian Reservation boundary.

Along Sandario Road.

40.07

Point for the 1/4 sec. cor. of secs. 15 and 16, at proportionate dist.; there is no remaining evidence of the orig. cor.

Set a PK nail in Sandario Road.

from which

A stainless steel post, 28 ins. long, 2 1/2 ins. diam., set 24 ins. in the ground for a reference monument, bears S. 44°25' W., 47.5 ft. dist. with brass cap mkd. RM T14S R11E 47.5 FT TO COR 1/4 S16 2009 and an arrow pointing to the cor. Deposit a magnet, in a white plastic case, at the base of the stainless steel post.

**Dependent Resurvey of a Portion of the Subdivisional Lines,  
T. 14 S., R. 11 E., Gila and Salt River Meridian, Arizona**

CHAINS

A stainless steel post, 28 ins. long, 2 1/2 ins. diam., set 24 ins. in the ground for a reference monument, bears N. 47°24' W., 45.0 ft. dist. with brass cap mkd. RM T14S R11E 45.0 FT TO COR 1/4 S16 2009 and an arrow pointing to the cor. Deposit a magnet, in a white plastic case, at the base of the stainless steel post.

Reference monuments are located in the westerly right-of-way fence, bears N. and S.

From this cor. point, a local monument, set by person(s) unknown and recorded in the Pima County Recorders Office on an Arizona Land Survey Monument Reference Record, bears S. 54°47' W., 62 lks. dist., monumented with a rebar, 1/2 in. diam., firmly set, flush with the ground and a second rebar, 1/2 in. diam., firmly set, flush with the ground, alongside, with aluminum cap mkd. ROW RLS 19316, lying loose alongside. This monument is not utilized in the course of this survey.

From this same cor. point, a local monument, set by person(s) unknown and recorded in the Pima County Recorders Office on an Arizona Land Survey Monument Reference Record, bears N. 64°14' W., 56.5 lks. dist., monumented with a rebar, 1/2 in. diam., firmly set, projecting 2 ins. above the ground. This monument is not utilized in the course of this survey.

80.14

Point for the cor. of secs. 9, 10, 15 and 16, at proportionate dist.; there is no remaining evidence of the orig. cor.

Set a PK nail in Sandario Road.

from which

A stainless steel post, 28 ins. long, 2 1/2 ins. diam., set 24 ins. in the ground for a reference monument, bears S. 38°23' W., 62.4 ft. dist., with brass cap mkd. RM T14S R11E 62.4 FT TO COR S16 2009 and an arrow pointing to the cor. Deposit a magnet, in a white plastic case, at the base of the stainless steel post.

A stainless steel post, 28 ins. long, 2 1/2 ins. diam., set 24 ins. in the ground for a reference monument, bears N. 33°43' W., 70.9 ft. dist., with brass cap mkd. RM T14S R11E 70.9 FT TO COR S9 2009 and an arrow pointing to the cor. Deposit a magnet, in a white plastic case, at the base of the stainless steel post.

Reference monuments are located in westerly right-of-way fence, bears N. and S.

**Dependent Resurvey of a Portion of the Subdivisional Lines,  
T. 14 S., R. 11 E., Gila and Salt River Meridian, Arizona**

CHAINS	
	<p>From this cor. point, the 1/4 sec. cor. of secs. 10 and 15, bears N. 89°48' E., 40.09 chs. dist., perpetuated by the U. S. Dept. of Interior, Bureau of Reclamation and recorded in the Pima County Department of Transportation, Section Corner Reference Sheet, monumented with an aluminum post, 2 1/2 ins. diam., firmly set, projecting 4 ins. above the ground, with aluminum cap mkd. U S DEPT. OF INTERIOR T14S R11E 1/4 S10 S15 1987 CADASTRAL SURVEY BUREAU OF RECLAMATION. This position is accepted as a true and faithful perpetuation of the orig. cor.</p> <p>from which the remaining orig. bearing trees</p> <p style="padding-left: 40px;">A mesquite bush, 10 ins. diam., bears N. 34 3/4° E., 1.85 chs. dist., with illegible marks visible on a partially healed blaze.</p> <p style="padding-left: 40px;">A mesquite bush, 9 ins. diam., bears S. 36 1/2° W., 1.83 chs. dist., with illegible marks visible on a partially healed blaze. (Record: S. 37° W., 1.85 chs.)</p> <p>From this same cor. point, a local monument, set by person(s) unknown and recorded in the Pima County Recorders Office on an Arizona Land Survey Monument Reference Record, bears N. 28°15' E., 3 lks. dist., monumented with an aluminum cap, 3 ins. diam., 5 ins. below Sandario Road, mkd. T14S R11E S9 S10 and other illegible marks. This monument is not utilized in the course of this survey.</p> <hr/> <p>N. 0°24' W., bet. secs. 9 and 10, identical with the Tohono O'Odham Indian Reservation boundary.</p> <p>Along Sandario Road.</p> <p>40.07 Point for the 1/4 sec. cor. of secs. 9 and 10, at proportionate dist.; there is no remaining evidence of the orig. cor.</p> <p>Set a PK nail in Sandario Road.</p> <p>from which</p> <p style="padding-left: 40px;">A stainless steel post, 28 ins. long, 2 1/2 ins. diam., set 24 ins. in the ground for a reference monument, bears S. 41°50' W., 58.6 ft. dist., with brass cap mkd. RM T14S R11E 58.6 FT TO COR 1/4 S9 2009 and an arrow pointing to the cor. Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p>





**Dependent Resurvey of a Portion of the Subdivisional Lines,  
T. 14 S., R. 11 E., Gila and Salt River Meridian, Arizona**

CHAINS							
	<p>From this cor. point, the cor. of secs. 3, 4, 33 and 34, on the N. bdy. of the Tp., hereinbefore described, bears N. 0°03' W., 79.93 chs. dist.</p>						
	<p>From the point for the cor. of secs. 28, 29, 32 and 33, hereinbefore described.</p> <p>N. 0°06' W., bet. secs. 28 and 29.</p>						
	<p>Over nearly level terrain, through scattered mesquite bushes and cactus.</p>						
<p>40.065</p>	<p>Point for the 1/4 sec. cor. of secs. 28 and 29, at proportionate dist.; there is no remaining evidence of the orig. cor.</p> <p>Cor. not monumented.</p>						
<p>80.13</p>	<p>Point for the cor. of secs. 20, 21, 28 and 29, on the Tohono O'odham Indian Reservation boundary, at proportionate dist.; there is no remaining evidence of the orig. cor.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p>						
	<table style="margin-left: auto; margin-right: auto;"> <tr> <td>T 14 S</td> <td>R 11 E</td> </tr> <tr> <td>S 20</td> <td>S 21</td> </tr> <tr> <td>S 29</td> <td>S 28</td> </tr> </table>	T 14 S	R 11 E	S 20	S 21	S 29	S 28
T 14 S	R 11 E						
S 20	S 21						
S 29	S 28						
	<p style="text-align: center;">2009</p>						
	<p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p>						
	<p>From this cor. point, a local monument set by Robert Douglas Miller, Arizona Registered Land Surveyor No. 13564 and recorded in the Pima County Department of Transportation, Section Corner Reference Sheet, bears N. 43°11' E., 19 lks. dist., monumented with an iron post, 1 in. diam., firmly set, projecting 4 ins. above the ground, with aluminum cap mkd. T14S R11E 20 21 29 28 RLS 13564. This monument is not utilized in the course of this survey.</p>						
	<p>From the cor. of secs. 21, 22, 27 and 28.</p>						
	<p>S. 89°56' W., bet. secs. 21 and 28, identical with the Tohono O'odham Indian Reservation boundary.</p>						
	<p>Over nearly level terrain, through cleared terrain.</p>						
<p>0.55</p>	<p>Westerly right-of-way fence, bears N. and S.</p>						

**Dependent Resurvey of a Portion of the Subdivisional Lines,  
T. 14 S., R. 11 E., Gila and Salt River Meridian, Arizona**

CHAINS	
	Thence over nearly level terrain, through scattered mesquite bushes and cactus.
40.135	Point for the 1/4 sec. cor. of secs. 21 and 28, at proportionate dist.; there is no remaining evidence of the orig. cor.
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.
	<p style="text-align: center;">T 14 S R 11 E S 21 1/4 ——— S 28</p>
	2009
	Deposit a magnet, in a white plastic case, at the base of the stainless steel post.
	Cor. is located E., 4 lks. dist., from a 5 strand barbed wire fence, bears N. and S.
	From this cor. point, a local monument, set by Robert Douglas Miller, Arizona Registered Land Surveyor No. 13564 and recorded in the Pima County Department of Transportation, Section Corner Reference Sheet, bears N. 25°56' E., 18 lks. dist., monumented with an iron post, 1 in. diam., firmly set, projecting 3 ins. above the ground, with aluminum cap mkd. T14S 21 28 1/4 R11E LS 13564. This monument is not utilized in the course of this survey.
	From this same cor. point, an intersection of fences, bears N. 5°58' W., 31 lks. dist., fences bear E., S. and W.
79.95	Fence, 4 strand barbed wire, bears N. and S.
80.27	The cor. of secs. 20, 21, 28 and 29.
	<hr/> <p>N. 0°08' W., bet. secs. 20 and 21.</p>
	Over nearly level terrain, through scattered mesquite bushes and cactus.
0.45	Fence, 5 strand barbed wire, extending E. and W.
4.65	Center of paved road, 25 ft. wide, bears E. and W.
5.40	Fence, chain link, 8 ft. high, bears E. and W.
	Enter Schuk Toak Farms maintenance yard and office complex.

**Dependent Resurvey of a Portion of the Subdivisional Lines,  
T. 14 S., R. 11 E., Gila and Salt River Meridian, Arizona**

CHAINS	
12.75	<p>Fence, chain link, 8 ft. high, extending E. and W.</p> <p>Leave Schuk Toak Farms maintenance yard and office complex, enter cultivated field.</p>
40.065	<p>Point for the 1/4 sec. cor. of secs. 20 and 21, at proportionate dist.; there is no remaining evidence of the orig. cor.</p> <p>Cor. not monumented.</p>
80.13	<p>Point for the cor. of secs. 16, 17, 20 and 21, at proportionate dist.; there is no remaining evidence of the orig. cor.</p> <p>Cor. not monumented.</p>
<hr/>	
	<p>From the cor. of secs. 15, 16, 21 and 22.</p> <p>S. 89°56' W., bet. secs. 16 and 21.</p> <p>over nearly level terrain, through cleared terrain.</p>
0.35	<p>Westerly right-of-way fence, bears N. and S.</p> <p>Thence over nearly level terrain, through scattered mesquite bushes and cactus.</p>
25.85	<p>Graveled road, 18 ft. wide, bears N. and S.</p>
26.00	<p>Enter cultivated field.</p>
40.06	<p>Point for the 1/4 sec. cor. of secs. 16 and 21, at proportionate dist.; there is no remaining evidence of the orig. cor.</p> <p>Cor. not monumented.</p>
80.12	<p>The point for the cor. of secs. 16, 17, 20 and 21.</p>
<hr/>	
	<p>N. 0°03' W., bet. secs. 16 and 17.</p> <p>Over nearly level terrain, through cultivated field.</p>
27.00	<p>Leave cultivated field.</p>
27.25	<p>Graded road, 32 ft. wide, bears E. and W.</p>
27.50	<p>Enter, nearly level terrain, through scattered mesquite bushes and cactus.</p>
40.065	<p>Point for the 1/4 sec. cor. of secs. 16 and 17, at proportionate dist.; there is no remaining evidence of the orig. cor.</p>

**Dependent Resurvey of a Portion of the Subdivisional Lines,  
T. 14 S., R. 11 E., Gila and Salt River Meridian, Arizona**

CHAINS							
	Cor. not monumented.						
80.13	Point for the cor. of secs. 8, 9, 16 and 17, at proportionate dist.; there is no remaining evidence of the orig. cor.						
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.						
	<table border="0" style="margin-left: auto; margin-right: auto;"> <tr> <td>T 14 S</td> <td>R 11 E</td> </tr> <tr> <td style="border-right: 1px solid black;">S 8</td> <td>S 9</td> </tr> <tr> <td style="border-right: 1px solid black;">S 17</td> <td>S 16</td> </tr> </table>	T 14 S	R 11 E	S 8	S 9	S 17	S 16
T 14 S	R 11 E						
S 8	S 9						
S 17	S 16						
	2009						
	Deposit a magnet, in a white plastic case, at the base of the stainless steel post						
	From this cor. point, a local monument, set by person(s) unknown and recorded in the Pima County Recorders Office on an Arizona Land Survey Monument Reference Record, bears N. 43°03' E., 23.5 lks. dist., monumented with an open ended iron pipe, 1 in. diam., firmly set, bent over, 2 ins. below the surface of the ground. Iron pipe is located 1 1/2 lks. N. of the intersection of fences, fences bear N., E. and W. This monument is not utilized in the course of this survey.						
	From the cor. of secs. 9, 10, 15 and 16.						
	S. 89°55' W., bet. secs. 9 and 16.						
	Over nearly level terrain, through cleared terrain.						
0.59	Westerly right-of-way fence, bears N. and S.						
	Thence over nearly level terrain, through scattered mesquite bushes and cactus.						
40.16	Point for the 1/4 sec. cor. of secs. 9 and 16, at proportionate dist.; there is no remaining evidence of the orig. cor.						
	Cor. not monumented.						
80.32	The cor. of secs. 8, 9, 16 and 17.						
	N. 0°21' W., bet. secs. 8 and 9, identical with the Tohono O'Odham Indian Reservation boundary.						
	Over nearly level terrain, through scattered mesquite bushes and cactus.						

**Dependent Resurvey of a Portion of the Subdivisional Lines,  
T. 14 S., R. 11 E., Gila and Salt River Meridian, Arizona**

CHAINS	
40.065	<p>True point for the 1/4 sec. cor. of secs. 8 and 9, at proportionate dist.; there is no remaining evidence of the orig. cor., falls in a wash, 5 ft. deep, 15 ft. wide, drains S., where it is impracticable to establish a permanent monument.</p> <p>From this true point, the point selected for a witness cor. to the 1/4 sec. cor. of secs. 8 and 9, bears S. 81°29' E., 9 lks. dist.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center;"> <p>WC</p> <p>T 14 S R 11 E</p> <p>← 1/4</p> <p>S 8   S 9</p> <p>2009</p> </div> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p> <p>Leave, Tohono O'Odham Indian Reservation boundary.</p>
80.13	<p>Point for the cor. of secs. 4, 5, 8 and 9, at proportionate dist.; there is no remaining evidence of the orig. cor.</p> <p>Cor. not monumented.</p> <p>From this cor. point, the cor. of secs. 4, 5, 32 and 33, on the N. bdy. of the Tp., hereinbefore described, bears N. 0°10' W., 79.95 chs. dist.</p> <p>From this same cor. point, the cor. of secs. 5, 6, 7 and 8, bears N. 89°59' W., 80.18 chs. dist., monumented with a stainless steel post, 2 1/2 ins. diam., firmly set, projecting 4 ins. above the ground, with brass cap mkd. T14S R11E S6 S5 S7 S8 2003.</p> <p>These control lines were fully retraced and a careful search was made for evidence of intervening cors., none of which were recovered.</p> <hr/> <p>From the cor. of secs. 3, 4, 9 and 10.</p> <p>S. 89°54' W., bet. secs. 4 and 9.</p> <p>Over nearly level terrain, through cleared terrain.</p>
1.10	<p>Westerly right-of-way fence, bears N. and S.</p>

**Dependent Resurvey of a Portion of the Subdivisional Lines,  
T. 14 S., R. 11 E., Gila and Salt River Meridian, Arizona**

CHAINS							
	Thence over nearly level terrain, through scattered mesquite bushes and cactus.						
40.11	Point for the 1/4 sec. cor. of secs. 4 and 9, at proportionate dist.; there is no remaining evidence of the orig. cor.  Cor. not monumented.						
80.22	The point for the cor. of secs. 4, 5, 8 and 9.						
	From the point for the cor. of secs. 29, 30, 31 and 32.  N. 0°08' W., bet. secs. 29 and 30.						
	Over nearly level terrain, through scattered mesquite bushes and cactus.						
40.08	Point for the 1/4 sec. cor. of secs. 29 and 30, at proportionate dist.; there is no remaining evidence of the orig. cor.  Cor. not monumented.						
80.16	Point for the cor. of secs. 19, 20, 29 and 30, at proportionate dist.; there is no remaining evidence of the orig. cor.  Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.						
	<table style="margin-left: auto; margin-right: auto; border-collapse: collapse;"> <tr> <td style="padding: 0 10px;">T 14 S</td> <td style="padding: 0 10px;">R 11 E</td> </tr> <tr> <td style="padding: 0 10px; border-right: 1px solid black;">S 19</td> <td style="padding: 0 10px;">S 20</td> </tr> <tr> <td style="padding: 0 10px; border-right: 1px solid black;">S 30</td> <td style="padding: 0 10px;">S 29</td> </tr> </table>	T 14 S	R 11 E	S 19	S 20	S 30	S 29
T 14 S	R 11 E						
S 19	S 20						
S 30	S 29						
	2009						
	Deposit a magnet, in a white plastic case, at the base of the stainless steel post.						
	From this cor. point, a local monument, set by Robert Douglas Miller, Arizona Registered Land Surveyor No. 13564 and recorded in the Pima County Department of Transportation, Section Corner Reference Sheet, bears N. 72°27' E., 24 lks. dist., monumented with an iron post, 1 in. diam., firmly set, projecting 5 ins. above the ground, with aluminum cap mkd. T14S 19 20 30 29 R11E RLS 13564. This monument is not utilized in the course of this survey.						
	From this same cor. point, a local monument, set by person(s) unknown and recorded in the Pima County Recorders Office on an Arizona Land Survey Monument Reference Record, bears N. 77°21' E., 1.84 chs., monumented with a 1 in. iron post, firmly set, projecting 2 ins. above the ground. This monument is not utilized in the course of this survey.						

**Dependent Resurvey of a Portion of the Subdivisional Lines,  
T. 14 S., R. 11 E., Gila and Salt River Meridian, Arizona**

CHAINS	
	<hr/> <p>From the cor. of secs. 20, 21, 28 and 29.</p>
	<p>S. 89°58' W., bet. secs. 20 and 29, along the Tohono O'Odham Indian Reservation boundary.</p>
	<p>Over nearly level terrain, through scattered mesquite bushes and cactus.</p>
40.105	<p>Point for the 1/4 sec. cor. of secs. 20 and 29, at proportionate dist.; there is no remaining evidence of the orig. cor.</p>
	<p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p>
	<p style="text-align: center;">T 14 S R 11 E S 20 1/4 ——— S 29</p>
	<p style="text-align: center;">2009</p>
	<p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p>
	<p>Cor. is located S., 30 lks. dist. from a 5 strand barbed wire fence, bears E. and W.</p>
	<p>From this cor. point, a local monument, set by Robert Douglas Miller, Arizona Registered Land Surveyor No. 13564 and recorded in the Pima County Department of Transportation, Section Corner Reference Sheet, bears N. 58°45' E., 21 lks. dist., monumented with an iron post, 1 in. diam., firmly set, projecting 14 ins. above the ground, with aluminum cap mkd. T14S 20 29 1/4 R11E LS 13564. This monument is not utilized in the course of this survey.</p>
40.25	<p>Fence, 5 strand barbed wire, bears N. and S.</p>
80.21	<p>The cor. of secs. 19, 20, 29 and 30.</p> <hr/>
	<p>S. 89°47' W., bet. secs. 19 and 30, along the Tohono O'Odham Indian Reservation boundary.</p>
	<p>Over nearly level terrain, through scattered mesquite bushes and cactus.</p>
40.09	<p>Point for the 1/4 sec. cor. of secs. 19 and 30, at proportionate dist.; there is no remaining evidence of the orig. cor.</p>

**Dependent Resurvey of a Portion of the Subdivisional Lines,  
T. 14 S., R. 11 E., Gila and Salt River Meridian, Arizona**

CHAINS	
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.
	<p style="text-align: center;">T 14 S R 11 E S 19 1/4 ——— S 30</p>
	2009
	Deposit a magnet, in a white plastic case, at the base of the stainless steel post.
	Cor. is located 62 lks. S. of a fence, bears E. and W.
	From this cor. point, a local monument, set by Robert Douglas Miller, Arizona Registered Land Surveyor No. 13564 and recorded in the Pima County Department of Transportation, Section Corner Reference Sheet, bears N. 83°27' W., 1.14 chs. dist., monumented with an iron post, 1 in. diam., firmly set, projecting 2 ins. above the ground, with aluminum cap mkd. T14S 19 30 1/4 R11E LS 13564. This monument is not utilized in the course of this survey.
83.02	The cor. of secs. 19, 24, 25 and 30, on the W. bdy. of the Tp., hereinbefore described.
	<hr/> From the cor. of secs. 19, 20, 29 and 30.
	N. 0°14' W., bet. secs. 19 and 20.
	Over nearly level terrain, through scattered mesquite bushes and cactus.
0.39	Fence, 4 strand barbed wire, bears E. and W.
4.65	Center of paved road, 25 ft. wide, bears E. and W.
4.90	Enter cultivated field.
40.08	Point for the 1/4 sec. cor. of secs. 19 and 20, at proportionate dist.; there is no remaining evidence of the orig. cor.
	Cor. not monumented.
80.16	Point for the cor. of secs. 17, 18, 19 and 20, at proportionate dist.; there is no remaining evidence of the orig. cor.
	Cor. not monumented.
	<hr/> From the point for the cor. of secs. 16, 17, 20 and 21.



**Dependent Resurvey of a Portion of the Subdivisional Lines,  
T. 14 S., R. 11 E., Gila and Salt River Meridian, Arizona**

CHAINS	
	S. 89°59' W., bet. secs. 17 and 20.
	Over nearly level terrain, through cultivated fields.
40.165	Point for the 1/4 sec. cor. of secs. 17 and 20, at proportionate dist.; there is no remaining evidence of the orig. cor.
	Cor. not monumented.
80.33	The point for the cor. of secs. 17, 18, 19 and 20.
	S. 89°38' W., bet. secs. 18 and 19.
	Over nearly level terrain, through cultivated fields.
40.04	Point for the 1/4 sec. cor. of secs. 18 and 19, at proportionate dist.; there is no remaining evidence of the orig. cor.
	Cor. not monumented.
82.74	The point for the cor. of secs. 13, 18, 19 and 24, on the W. bdy. of the Tp., hereinbefore described.
	From the point for the cor. of secs. 17, 18, 19 and 20.
	N. 0°02' W., bet. secs. 17 and 18.
	Over nearly level terrain, through cultivated fields.
34.80	Leave cultivated field.
35.00	Graded road, 32 ft. wide, bears S. 70° E. and N. 70° W.
35.20	Enter, nearly level terrain, through scattered mesquite bushes and cactus.
40.08	Point for the 1/4 sec. cor. of secs. 17 and 18, at proportionate dist.; there is no remaining evidence of the orig. cor.
	Cor. not monumented.
	From this cor. point, a local monument, set by person(s) unknown, bears N. 89°04' E., 18 lks. dist., monumented with an iron post, 1 in. diam., firmly set, projecting 6 ins. above the ground, with aluminum cap mkd. T14S 1/4 18 17 R11E. This monument is not utilized in the course of this survey.
80.16	The cor. of secs. 7, 8, 17 and 18, monumented with a stainless steel post, firmly set, projecting 4 ins. above the ground, with brass cap mkd. T14S R11E S7 S8 S18 S17 2003.

Dependent Resurvey of a Portion of the Subdivisional Lines,  
T. 14 S., R. 11 E., Gila and Salt River Meridian, Arizona

CHAINS	
	<p>Add the marks 2008 to the brass cap.</p> <p>Cor. is located at the intersection of fences, fences bear N., E. and W.</p> <hr/>
	<p>From the cor. of secs. 8, 9, 16 and 17.</p> <p>S. 89°59' W., bet. secs. 8 and 17, identical with the Tohono O'Odham Indian Reservation boundary.</p> <p>Over nearly level terrain, through cultivated fields.</p>
40.15	<p>Point for the 1/4 sec. cor. of secs. 8 and 17, at proportionate dist.; there is no remaining evidence of the orig. cor.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p>
	<p style="text-align: center;">T 14 S R 11 E S 8 1/4 ——— S 17</p> <p style="text-align: center;">2009</p>
	<p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p> <p>Cor. is located 8 lks. S. of a fence, bears E. and W.</p> <p>From this cor. point, a local monument, set by Robert Douglas Miller, Arizona Registered Land Surveyor No. 13564 and recorded in the Pima County Department of Transportation, Section Corner Reference Sheet, bears N. 67°02' E., 22 lks. dist., monumented with an iron post, 1 in. diam., firmly set, projecting 3 ins. above the ground, with aluminum cap mkd. T14S 8 17 1/4 R11E LS 13564. This monument is not utilized in the course of this survey.</p>
80.30	<p>The cor. of secs. 7, 8, 17 and 18.</p> <hr/> <p>S. 89°29' W., bet. secs. 7 and 18, identical with the Tohono O'Odham Indian Reservation boundary.</p> <p>Over nearly level terrain, through cultivated fields.</p>
40.03	<p>The 1/4 sec. cor. of secs. 7 and 18, monumented with a stainless steel post, firmly set, projecting 4 ins. above the ground, with brass cap mkd. T14S R11E 1/4 S7 S18 2003.</p>

**Dependent Resurvey of a Portion of the Subdivisional Lines,  
T. 14 S., R. 11 E., Gila and Salt River Meridian, Arizona**

CHAINS	<p>Add the marks 2009 to the brass cap.</p> <hr/>
42.72	<p>S. 89°29' W., beginning new measurement.</p> <p>The cor. of secs. 7, 12, 13 and 18, on the W. bdy. of the Tp., hereinbefore described.</p> <hr/>
	<p align="center"><b>Subdivision of Section 9, T. 14 S., R. 11 E., Gila and Salt River Meridian, Arizona</b></p> <hr/>
	<p>From the 1/4 sec. cor. of secs. 9 and 10.</p> <p>S. 89°55' W., on the E. and W. center line of sec. 9, identical with the Tohono O'Odham Indian Reservation boundary.</p> <p>Over nearly level terrain, through scattered mesquite bushes and cactus.</p>
39.99	<p>From this point, a local monument, set by person(s) unknown and recorded in the Pima County Recorders Office on an Arizona Land Survey Monument Reference Record, bears N., 7 lks. dist., monumented with an iron post, 1 in. diam., firmly set, projecting 5 ins. above the ground, with lead cap mkd. 1052 C 1.4 SEC 9 3.60. This monument is not utilized in the course of this survey.</p>
80.27	<p>The true point for the 1/4 sec. cor. of secs. 8 and 9.</p> <hr/>
	<p align="center">GENERAL DESCRIPTION</p> <hr/>
	<p>The area embraced by this survey is approximately 9 miles west of the town of Marana, Arizona, situated adjacent to Interstate Highway 10.</p>
	<p>The terrain is mostly flat desert. The Tohono O'Odham Indian Reservation has a substantial farming operation in secs. 16, 17, 18, 19, 20 and 21, with the Schuk Toak Farms maintenance yard and office complex situated in secs. 20 and 21. All other vegetation consists mainly of mesquite, creosote and palo verde, with sparse native grasses and cacti.</p>
	<p>The elevation is approximately 2000 ft. above sea level.</p>
	<p>The mean magnetic declination of 10 3/4° E. was derived from the United States Geological Survey computer program GEOMAG, utilizing the World Magnetic Model for Epoch 2005 for the dates of survey.</p> <hr/>



## CERTIFICATE OF SURVEY

I, Joe R. Salazar, Cadastral Surveyor, HEREBY CERTIFY upon honor, that in pursuance of special instructions bearing date of the 20th day of October, 2008, I have dependently resurveyed a portion of the Second Guide Meridian East (west boundary), a portion of the north boundary, a portion of the sectional correction line, a portion of the subdivisional lines and the subdivision of section 9, T. 14 S., R. 11 E., of the Gila and Salt River Meridian, in the State of Arizona, which are represented in the foregoing field notes as having been executed by me and under my direction. Said survey has been made in strict conformity with said special instructions, the Manual of Instructions for the Survey of the Public Lands of the United States, 1973, and in specific manner described in the foregoing field notes.

5/28/2009

(Date)

Joe R. Salazar  
(Cadastral Surveyor)

## CERTIFICATE OF APPROVAL

BUREAU OF LAND MANAGEMENT  
Phoenix, Arizona

The foregoing field notes of the dependent resurvey of a portion of the Second Guide Meridian East (west boundary), a portion of the north boundary, a portion of the sectional correction line, a portion of the subdivisional lines and the subdivision of section 9, T. 14 S., R. 11 E., Gila and Salt River Meridian, in the State of Arizona, executed by Joe R. Salazar, Cadastral Surveyor, having been critically examined and found correct, are hereby approved.

6/24/2009

(Date)

Stephen K. Hansen  
(Chief Cadastral Surveyor of Arizona)

~~CERTIFICATE OF TRANSCRIPT~~

~~I CERTIFY That the foregoing transcript of the field notes of the above described surveys in T. 14 S., R. 11 E., Gila and Salt River Meridian, Arizona, is a true copy of the orig. field notes.~~

~~(Date)~~

~~(Chief Cadastral Surveyor of Arizona)~~