

ORIGINAL

**UNITED STATES  
DEPARTMENT OF THE INTERIOR  
BUREAU OF LAND MANAGEMENT**

FIELD NOTES  
OF THE  
SURVEY OF  
THE SOUTH, EAST  
AND  
WEST BOUNDARIES,  
AND  
THE SUBDIVISIONAL LINES,  
**TOWNSHIP 39 NORTH, RANGE 27 EAST,**  
OF THE GILA AND SALT RIVER MERIDIAN,  
IN THE STATE OF ARIZONA

**EXECUTED BY**

**Alvina A. Begaye, Cadastral Surveyor**

Under Special Instructions dated and approved July 14, 2008, which provided for the surveys included under Group No. 1046, and assignment instructions dated July 14, 2008.

**Survey commenced July 21, 2008**

**Survey completed October 9, 2008**

## INDEX DIAGRAM

TOWNSHIP 39 NORTH                  RANGE 27 EAST  
GILA AND SALT RIVER MERIDIAN, ARIZONA

20	69 6	68	69 5	56	57 4	47	48 3	38	39 2	29	30 1	14
	67		67		56		46		37		29	
19	7	66	8	55	9	45	10	36	11	28	12	14
	65		65		54		44		36		27	
18	18	64	17	53	16	44	15	35	14	26	13	13
	63		63		52		43		34		25	
18	19	62	20	52	21	42	22	34	23	25	24	12
	61		61		51		42		33		24	
17	30	60	29	50	28	41	27	32	26	23	25	11
	59		59		50		40		32		22	
16	31	58	32	49	33	40	34	31	35	21	36	10
	9		8		7		6		5		4	

**T. 39 N., R. 27 E., Gila and Salt River Meridian, Arizona**

## CHAINS

The following field notes describe the survey of the south, east and west boundaries, and the subdivisional lines, Township 39 North, Range 27 East, Gila and Salt River Meridian, Arizona.

The history of surveys pertaining to this survey is as follows:

The survey of the Ninth Standard Parallel North (south boundaries), Townships 37 North, Ranges 26 and 27 East, were surveyed by Leonard R. Sandoval in 1999. The south boundary of Township 40 North, Ranges 27 East, was surveyed by Leonard R. Sandoval in 2000. The south boundary of Township 40 North, Ranges 28 East, was surveyed by Leonard R. Sandoval in 2006.

The survey was executed in accordance with the specifications as set forth in the Manual of Instructions for the Survey of the Public Lands of the United States, 1973, and the special instructions dated July 14, 2008, for Group Number 1046, Arizona.

The true meridian direction and length of all lines were determined by real time kinematic global positioning system observations using Trimble Navigation 5700 model receivers.

Geodetic control was derived from Global Positioning Systems (GPS) static observations post processed by National Geodetic Survey, Online Positioning User Service (OPUS), utilizing Continuously Operating Reference Stations (CORS) SPIDERROCKAZ2005 CORS ARP, MONTICELLOUT2006 CORS ARP, and AZTEC CORS ARP. The NAD 83 (CORS96) (EPOCH:2002) geographic position of the southeast corner of the township is as follows:

Latitude: 36°44'15.16" N.                      Longitude: 109°22'23.46" W.

The mean magnetic declination is 11° E.

---

**Survey of the South Boundary,  
T. 39 N., R. 27 E., Gila and Salt River Meridian, Arizona**

CHAINS

Beginning at the point for the cor. of Tps. 38 and 39 N., Rs. 26 and 27 E., established North, 960.00 chs. dist., from the stan. cor. of Tps. 37 N., Rs. 26 and 27 E., monumented with a stainless steel post, 2 1/2 ins. diam., firmly set, projecting 4 ins. above ground, with brass cap mkd. SC T37N R26E R27E S36 S31 1999.

Add the marks 2008 to the brass cap.

Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.

T 39 N	
R 26 E	R 27 E
S 36	S 31
S 1	S 6
T 38 N	

2008

Deposit a magnet, in a white plastic case, at the base of the stainless steel post.

From this cor. point, third order National Geodetic Survey triangulation station "WALKER RESET 1968", bears N. 12°09' W., 184.71 chs. dist., monumented with a copper rod, 1/2 in. diam., firmly set, projecting 1 in. above a sandstone outcrop, cemented in place, with unmarked yellow plastic cap.

From the point for the cor. of Tps. 38 and 39 N., Rs. 27 and 28 E., established North, 960.00 chs. dist., from the stan. cor. of Tps. 37 N., Rs. 27 and 28 E., monumented with a stainless steel post, 2 1/2 ins. diam., firmly set, projecting 6 ins. above ground, with brass cap mkd. SC T37N R27E R28E S36 S31 1999.

Add the marks 2008 to the brass cap.

Set a brass tablet, 3 1/4 ins. diam., 2 1/2 ins. stem, cemented in place, in a drill hole, in sandstone bedrock, with top mkd.

T 39 N	
R 27 E	R 28 E
S 36	S 31
S 1	S 6
T 38 N	

2008

Deposit a magnet, in a white plastic case, in the drill hole, beneath the brass tablet.

West, bet. secs. 1 and 36.

**Survey of the South Boundary,  
T. 39 N., R. 27 E., Gila and Salt River Meridian, Arizona**

CHAINS	
	Over broken land, ascend out of Alcove Canyon.
40.00	Point for the 1/4 sec. cor. of secs. 1 and 36.  Set a brass tablet, 3 1/4 ins. diam., 2 1/2 ins. stem, cemented in place, in a drill hole, in sandstone bedrock, with top mkd.  <div style="text-align: center;">           T 39 N R 27 E                      S 36                  1/4 ———                      S 1            T 38 N             2008         </div>
80.00	Point for the cor. of secs. 1, 2, 35 and 36.  Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.  <div style="text-align: center;">           T 39 N R 27 E            S 35   S 36            S 2   S 1            T 38 N             2008         </div>
	Deposit a magnet, in a white plastic case, in the drill hole, beneath the brass tablet.
	Deposit a magnet, in a white plastic case, at the base of the stainless steel post.
	Land, broken. Soil, sandy clay with sandstone outcrops. Timber, scattered juniper; undergrowth, scattered brush and native grasses.
	West, bet. secs. 2 and 35.
	Over rolling and broken land.
38.50	E. rim of a narrow canyon, bears North and South.
40.00	True point for the 1/4 sec. cor. of secs. 2 and 35, falls on the steep E. slope of a canyon, where it is impracticable to establish a permanent monument.  From this true point, the point selected for a witness cor. to the 1/4 sec. cor. of secs. 2 and 35, bears N. 40°00' E., 1.00 ch. dist.

**Survey of the South Boundary,  
T. 39 N., R. 27 E., Gila and Salt River Meridian, Arizona**

CHAINS	
	<p>Set a brass tablet, 3 1/4 ins. diam., 2 1/2 ins. stem, cemented in place, in a drill hole, in sandstone bedrock, with top mkd.</p> <div style="text-align: center;"> <p>WC T 39 N R 27 E S 35 1/4 ——— S 2 ↙ T 38 N</p> <p>2008</p> </div> <p>Deposit a magnet, in a white plastic case, in the drill hole, beneath the brass tablet.</p>
51.90	W. rim of a canyon, bears N. 15° E. and S. 15° W.
80.00	<p>True point for the cor. of secs. 2, 3, 34 and 35, falls on the NE face of a sandstone cliff, where it is impracticable to establish a permanent monument.</p> <p>From this true point, the point selected for a witness cor. to the cor. of secs. 2, 3, 34 and 35, bears N. 73°00' E., 1.00 ch. dist.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 20 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center;"> <p>WC T 39 N R 27 E S 34   S 35 S 3   S 2 ↙ T 38 N</p> <p>2008</p> </div> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p> <p>Land, rolling and broken. Soil, sandy clay with sandstone outcrops. Timber, scattered juniper; undergrowth, scattered brush and native grasses.</p> <hr/> <p>West, bet. secs. 3 and 34.</p> <p>Over rugged and broken land, along the slope of a mesa.</p>
24.60	NE rim of a mesa, bears S. 35° E. and N. 35° W., thence over rolling land.
40.00	Point for the 1/4 sec. cor. of secs. 3 and 34.

**Survey of the South Boundary,  
T. 39 N., R. 27 E., Gila and Salt River Meridian, Arizona**

CHAINS	
	<p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T 39 N R 27 E S 34 1/4 ——— S 3 T 38 N</p> <p style="text-align: center;">2008</p> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p>
80.00	<p>Point for the cor. of secs. 3, 4, 33 and 34.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T 39 N R 27 E S 33   S 34 S 4   S 3 T 38 N</p> <p style="text-align: center;">2008</p> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post</p> <p>Cor. is located .80 chs. E. of Navajo Route 5040, a graded road, 25 ft. wide, bears S. 35° E. and N. 35° W.</p> <p>Land, rugged and broken. Soil, sandy clay with sandstone outcrops. Timber, scattered juniper; undergrowth, scattered brush and native grasses.</p> <hr/> <p>West, bet. secs. 4 and 33.</p> <p>Over rolling land.</p>
1.85	Trail road, bears S. 10° W.
11.25	Trail road, bears S. 20° E. and N. 20° W.
40.00	<p>Point for the 1/4 sec. cor. of secs. 4 and 33.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p>

**Survey of the South Boundary,  
T. 39 N., R. 27 E., Gila and Salt River Meridian, Arizona**

CHAINS	
	T 39 N R 27 E S 33 1/4 ——— S 4 T 38 N  2008
80.00	Deposit a magnet, in a white plastic case, at the base of the stainless steel post.  Point for the cor. of secs. 4, 5, 32 and 33.  Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.  <div style="text-align: center;">             T 39 N R 27 E              S 32   S 33              S 5   S 4              T 38 N           </div> 2008  Deposit a magnet, in a white plastic case, at the base of the stainless steel post.  From this cor. point, a concrete filled iron pipe, 2 1/2 ins. diam., firmly set, projecting 12 ins. above ground, established by Ernest V. Echohawk, R.L.S. No. 2311, Az., bears N. 72°31' E., 2.63 chs. dist., with flat steel cap mkd. T39N R27E S32 S33 S5 S4 T38N E.V.E  Land, rolling. Soil, sandy clay with sandstone outcrops. Timber, scattered juniper; undergrowth, scattered brush and native grasses.
40.00	<hr/> West, bet. secs. 5 and 32.  Over rolling land.  Point for the 1/4 sec. cor. of secs. 5 and 32.  Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.



Survey of the South Boundary,  
T. 39 N., R. 27 E., Gila and Salt River Meridian, Arizona

CHAINS	
	<p style="text-align: center;">T 39 N R 27 E S 32 1/4 ——— S 5 T 38 N</p> <p style="text-align: center;">2008</p> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p>
80.00	<p>Point for the cor. of secs. 5, 6, 31 and 32.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T 39 N R 27 E S 31   S 32 S 6   S 5 T 38 N</p> <p style="text-align: center;">2008</p> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p> <p>Land, rolling. Soil, sandy clay with sandstone outcrops. Timber, scattered juniper; undergrowth, scattered brush and native grasses.</p>
	<hr/> <p>West, bet. secs. 6 and 31.</p> <p>Over rolling land.</p>
40.00	<p>Point for the 1/4 sec. cor. of secs. 6 and 31.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T 39 N R 27 E S 31 1/4 ——— S 6 T 38 N</p> <p style="text-align: center;">2008</p>
78.93	<p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p> <p>The cor. of Tps. 38 and 39 N., Rs. 26 and 27 E.</p>

**Survey of the South Boundary,  
T. 39 N., R. 27 E., Gila and Salt River Meridian, Arizona**

CHAINS	
	<p>Land, rolling. Soil, sandy clay with sandstone outcrops. Timber, scattered juniper; undergrowth, scattered brush and native grasses.</p> <hr/> <p style="text-align: center;"><b>Survey of the East Boundary, T. 39 N., R. 27 E., Gila and Salt River Meridian, Arizona</b></p> <hr/> <p>From the cor. of Tps. 39 N., Rs. 27 and 28 E., hereinbefore described.</p> <p>North, bet. secs. 31 and 36.</p> <p>Over rugged and broken land, along Alcove Canyon wash.</p>
8.30	Wash, 35 ft. wide, 8 ft. deep, drains N. 35° E.
14.90	Alcove Canyon wash, 200 ft. wide, 100 ft. deep, drains N. 85° W.
27.30	Alcove Canyon wash, 250 ft. wide, 100 ft. deep, drains N. 55° E.
40.00	Point for the 1/4 sec. cor. of secs. 31 and 36.
	<p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center;"> <p>T 39 N 1/4 R 27 E   R 28 E S 36   S 31</p> <p>2008</p> </div> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p>
44.75	Alcove Canyon wash, 100 ft. wide, 5 ft. deep, drains, N. 40° W.
80.00	Point for the cor. of secs. 25, 30, 31 and 36.
	<p>Set a brass tablet, 3 1/4 ins. diam., 2 1/2 ins. stem, cemented in place, in a drill hole, in sandstone bedrock, with top mkd.</p> <div style="text-align: center;"> <p>T 39 N R 27 E   R 28 E S 25   S 30 S 36   S 31</p> <p>2008</p> </div>

**Survey of the East Boundary,  
T. 39 N., R. 27 E., Gila and Salt River Meridian, Arizona**

CHAINS	
	<p>Deposit a magnet, in a white plastic case, in the drill hole, beneath the brass tablet.</p> <p>Land, rugged and broken. Soil, sandy clay with sandstone outcrops. Timber, scattered salt cedar and Russian olive along the wash; undergrowth, scattered brush and greasewood.</p> <hr/>
	<p>North, bet. secs. 25 and 30.</p> <p>Over rolling land.</p>
40.00	<p>Point for the 1/4 sec. cor. of secs. 25 and 30.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p align="center">             T 39 N              1/4              R 27 E   R 28 E              S 25   S 30                2008           </p>
75.90	<p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p>
	<p>Navajo Route 5037, a graded road, 30 ft. wide, bears S. 50° E. and N. 50° W.</p>
80.00	<p>Point for the cor. of secs. 24, 19, 25 and 30.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p align="center">             T 39 N              R 27 E   R 28 E              S 24   S 19              S 25   S 30                2008           </p>
	<p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p>

**Survey of the East Boundary,  
T. 39 N., R. 27 E., Gila and Salt River Meridian, Arizona**

CHAINS	
	<p>Land, rolling. Soil, sandy clay with sandstone outcrops. Timber, scattered juniper; undergrowth, scattered brush, greasewood, and native grasses.</p> <hr/> <p>North, bet secs. 19 and 24.</p> <p>Over rolling land.</p>
5.69	Power line, bears S. 45° E. and N. 45° W.
15.38	Power line, bears S. 80° E. and N. 80° W.
22.30	Trail road, bears N. 60° E. and S. 60° W.
40.00	<p>Point for the 1/4 sec. cor. of secs. 19 and 24.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center;"> <p>T 39 N 1/4 R 27 E   R 28 E S 24   S 19</p> <p>2008</p> </div> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p>
80.00	<p>Point for the cor. of secs. 13, 18, 19 and 24.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center;"> <p>T 39 N R 27 E   R 28 E S 13   S 18 <hr/>S 24   S 19</p> <p>2008</p> </div> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p>

**Survey of the East Boundary,  
T. 39 N., R. 27 E., Gila and Salt River Meridian, Arizona**

CHAINS	
	<p>Land, rolling. Soil, sandy clay with sandstone outcrops. Timber, scattered juniper; undergrowth, scattered brush, greasewood and native grasses.</p> <hr/> <p>North, bet. secs. 13 and 18.</p> <p>Over rolling and broken land.</p>
2.60	Seklagaldesa Canyon wash, 30 ft. wide, 70 ft. deep, drains S. 80° W.
14.65	Trail road, bears West and ascend S. slope of a mesa.
38.30	S. rim of a mesa, bears N. 80° E. and S. 80° W.
40.00	Point for the 1/4 sec. cor. of secs. 13 and 18.
	<p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 17 ins. in the ground, in a mound of stone, 3 ft. base, to top, with brass cap mkd.</p> <p style="text-align: center;">T 39 N 1/4 R 27 E   R 28 E S 13   S 18</p> <p style="text-align: center;">2008</p> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p>
55.90	NW rim of a mesa, bears N. 30° E. and S. 30° W.
78.60	SW rim of a mesa, bears S. 70° E. and N. 70° W.
80.00	Point for the cor. of secs. 7, 12, 13 and 18.
	<p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 23 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T 39 N R 27 E   R 28 E S 12   S 7 S 13   S 18</p> <p style="text-align: center;">2008</p> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p>

**Survey of the East Boundary,  
T. 39 N., R. 27 E., Gila and Salt River Meridian, Arizona**

CHAINS	
	<p>Land, rolling and broken. Soil, sandy clay with sandstone outcrops. Timber, scattered juniper; undergrowth, scattered brush and greasewood, and native grasses.</p> <hr/> <p>North, bet. secs. 7 and 12.</p> <p>Over rolling land.</p>
40.00	<p>Point for the 1/4 sec. cor. of secs. 7 and 12.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center;"> <p>T 39 N 1/4 R 27 E   R 28 E S 12   S 7</p> </div> <p style="text-align: center;">2008</p> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p>
59.20	<p>Toh Chin Lini Canyon wash, 70 ft. wide, 5 ft. deep, drains S. 40° W.</p>
80.00	<p>Point for the cor. of secs. 1, 6, 7 and 12.</p> <p>Set a brass tablet, 3 1/4 ins. diam., 2 1/2 ins. stem, cemented in place, in a drill hole, in sandstone bedrock, with top mkd.</p> <div style="text-align: center;"> <p>T 39 N R 27 E   R 28 E S 1   S 6 <hr/>S 12   S 7</p> </div> <p style="text-align: center;">2008</p> <p>Deposit a magnet, in a white plastic case, in the drill hole, beneath the brass tablet.</p> <p>Land, rolling. Soil, sandy clay with sandstone outcrops. Timber, scattered juniper; undergrowth, scattered brush, and native grasses.</p> <hr/> <p>North, bet. secs. 1 and 6.</p> <p>Over rolling land.</p>

**Survey of the East Boundary,  
T. 39 N., R. 27 E., Gila and Salt River Meridian, Arizona**

CHAINS	
30.05	Power line, 2 strand, bears N. 40 E. and S. 40 W.
31.35	Trail road, bears N. 40° E. and S. 40 W.
36.47	Power line, 2 strand, bears S. 80° E. and N. 80 W.
40.00	Point for the 1/4 sec. cor. of secs. 1 and 6.  Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.  <div style="text-align: center;">           T 39 N            1/4            R 27 E   R 28 E            S 1   S 6              2008         </div> Deposit a magnet, in a white plastic case, at the base of the stainless steel post.
46.75	Apache County Road C480, a graded road, 30 ft. wide, bears S. 40° E. and N. 40° W.
73.60	Navajo Route 354, a graded road, 30 ft. wide, bears N. 45° E. and S. 45° W.
77.84	Point for the closing cor. of Tps. 39 N., Rs. 27 and 28 E., at intersection with the S. bdy. of sec. 32, T. 40 N., R 28 E.  Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.  <div style="text-align: center;">           T 40 N R 28 E            S 32  <hr style="width: 50%; margin: auto;"/>           S 1   S 6            R 27 E R 28 E            T 39 N            CC              2008         </div> Deposit a magnet, in a white plastic case, at the base of the stainless steel post.  From this cor. point, the 1/4 sec. cor. of sec. 32 only, T. 40 N., R. 28 E., bears East, 37.86 chs. dist., monumented with a stainless steel post, 2 1/2 ins. diam., firmly set, projecting 4 ins. above ground, with brass cap mkd. T40N R28E 1/4 S32 2006.  Add the marks T39N R28E 2008 to the brass cap.

**Survey of the East Boundary,  
T. 39 N., R. 27 E., Gila and Salt River Meridian, Arizona**

CHAINS	
	<p>From this same cor. point, the cor. of secs. 31 and 32 only, T. 40 N., R. 28 E., bears West, 2.14 chs. dist., monumented with a stainless steel post, 2 1/2 ins. diam., firmly set, projecting 4 ins. above ground, with brass cap mkd. T40N R28E S31 S32 2006.</p> <p>Add the marks S1 T39N R27E 2008 to the brass cap.</p> <p>Land, rolling. Soil, sandy clay and sandstone outcrops. Timber, scattered juniper; undergrowth, greasewood, scattered brush and native grasses.</p> <hr/> <p style="text-align: center;"><b>Survey of the West Boundary, T. 39 N., R. 27 E., Gila and Salt River Meridian, Arizona</b></p> <hr/> <p>From the cor. of Tps. 38 and 39 N., Rs. 26 and 27 E., hereinbefore described.</p> <p>North, bet. secs. 31 and 36.</p> <p>Over rolling and broken land.</p>
40.00	<p>Point for the 1/4 sec. cor. of secs. 31 and 36.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center;"> <p>T 39 N 1/4 R 26 E   R 27 E S 36   S 31</p> <p>2008</p> </div>
42.40	<p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p> <p>Navajo Route 5040, a graded road, 25 ft. wide, bears S. 55° E. and N. 55° W.</p>
77.70	<p>N. rim of a mesa, bears N. 20° E. and S. 20° W.</p>
80.00	<p>Point for the cor. of secs. 25, 30, 31 and 36.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p>



**Survey of the West Boundary,  
T. 39 N., R. 27 E., Gila and Salt River Meridian, Arizona**

CHAINS									
	<table style="margin: auto; border-collapse: collapse;"> <tr><td colspan="2" style="text-align: center;">T 39 N</td></tr> <tr><td style="text-align: center;">R 26 E</td><td style="text-align: center;">R 27 E</td></tr> <tr><td style="text-align: center;">S 25</td><td style="text-align: center;">S 30</td></tr> <tr><td style="text-align: center;">S 36</td><td style="text-align: center;">S 31</td></tr> </table> <p style="text-align: center;">2008</p> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p> <p>Land, rolling and broken. Soil, sandy clay with sandstone outcrops. Timber, scattered juniper; undergrowth, scattered brush and native grasses.</p> <hr/> <p>North, bet. secs. 25 and 30.</p> <p>Over rugged and broken land, along the E. rim of a mesa.</p> <p>27.80 SE rim of a mesa, bears N. 60° E. and W. 60° W.</p> <p>29.70 N. rim of a mesa, bears S. 85° E. and N. 85° W., thence descend over the N. slope of a mesa.</p> <p>40.00 Point for the 1/4 sec. cor. of secs. 25 and 30.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p>	T 39 N		R 26 E	R 27 E	S 25	S 30	S 36	S 31
T 39 N									
R 26 E	R 27 E								
S 25	S 30								
S 36	S 31								
	<table style="margin: auto; border-collapse: collapse;"> <tr><td colspan="2" style="text-align: center;">T 39 N</td></tr> <tr><td colspan="2" style="text-align: center;">1/4</td></tr> <tr><td style="text-align: center;">R 26 E</td><td style="text-align: center;">R 27 E</td></tr> <tr><td style="text-align: center;">S 25</td><td style="text-align: center;">S 30</td></tr> </table> <p style="text-align: center;">2008</p> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p> <p>80.00 Point for the cor. of secs. 19, 24, 25 and 30.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p>	T 39 N		1/4		R 26 E	R 27 E	S 25	S 30
T 39 N									
1/4									
R 26 E	R 27 E								
S 25	S 30								
	<table style="margin: auto; border-collapse: collapse;"> <tr><td colspan="2" style="text-align: center;">T 39 N</td></tr> <tr><td style="text-align: center;">R 26 E</td><td style="text-align: center;">R 27 E</td></tr> <tr><td style="text-align: center;">S 24</td><td style="text-align: center;">S 19</td></tr> <tr><td style="text-align: center;">S 25</td><td style="text-align: center;">S 30</td></tr> </table> <p style="text-align: center;">2008</p>	T 39 N		R 26 E	R 27 E	S 24	S 19	S 25	S 30
T 39 N									
R 26 E	R 27 E								
S 24	S 19								
S 25	S 30								

**Survey of the West Boundary,  
T. 39 N., R. 27 E., Gila and Salt River Meridian, Arizona**

CHAINS									
	<p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p> <p>Land, rugged and broken. Soil, sandy clay with sandstone outcrops. Timber, scattered juniper; undergrowth, scattered brush and native grasses.</p> <hr/> <p>North, bet. secs. 19 and 24.</p> <p>Over rolling land.</p>								
26.40	Wash, 15 ft. wide, 2 ft. deep, drains N. 65° E.								
40.00	<p>Point for the 1/4 sec. cor. of secs. 19 and 24.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center;"> <table style="margin: auto;"> <tr><td colspan="2">T 39 N</td></tr> <tr><td colspan="2">1/4</td></tr> <tr><td>R 26 E</td><td>R 27 E</td></tr> <tr><td>S 24</td><td>S 19</td></tr> </table> <p>2008</p> </div>	T 39 N		1/4		R 26 E	R 27 E	S 24	S 19
T 39 N									
1/4									
R 26 E	R 27 E								
S 24	S 19								
80.00	<p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p> <p>Point for the cor. of secs. 13, 18, 19 and 24.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center;"> <table style="margin: auto;"> <tr><td colspan="2">T 39 N</td></tr> <tr><td>R 26 E</td><td>R 27 E</td></tr> <tr><td>S 13</td><td>S 18</td></tr> <tr><td>S 24</td><td>S 19</td></tr> </table> <p>2008</p> </div> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p> <p>Land, rolling. Soil, sandy clay. Timber, scattered juniper; undergrowth, greasewood, scattered brush, and native grasses.</p> <hr/> <p>North, bet. secs. 13 and 18.</p>	T 39 N		R 26 E	R 27 E	S 13	S 18	S 24	S 19
T 39 N									
R 26 E	R 27 E								
S 13	S 18								
S 24	S 19								

**Survey of the West Boundary,  
T. 39 N., R. 27 E., Gila and Salt River Meridian, Arizona**

CHAINS	
	Over rolling land.
40.00	Point for the 1/4 sec. cor. of secs. 13 and 18.  Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.  <div style="text-align: center;">           T 39 N            1/4            R 26 E   R 27 E            S 13   S 18              2008         </div>
80.00	Point for the cor. of secs. 7, 12, 13 and 18.  Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.  <div style="text-align: center;">           T 39 N            R 26 E   R 27 E            S 12   S 7            S 13   S 18              2008         </div>
	Deposit a magnet, in a white plastic case, at the base of the stainless steel post.
	Land, rolling. Soil, sandy clay. Timber, scattered juniper; undergrowth, greasewood, scattered brush and native grasses.
	North, bet. secs. 7 and 12.
	Over rolling land.
40.00	Point for the 1/4 sec. cor. of secs. 7 and 12.  Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.  <div style="text-align: center;">           T 39 N            1/4            R 26 E   R 27 E            S 12   S 7              2008         </div>

**Survey of the West Boundary,  
T. 39 N., R. 27 E., Gila and Salt River Meridian, Arizona**

CHAINS									
	Deposit a magnet, in a white plastic case, at the base of the stainless steel post.								
68.40	Trail road, bears S. 25° E. and N. 25° W.								
80.00	Point for the cor. of secs. 1, 6, 7 and 12.  Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.								
	<table style="margin-left: auto; margin-right: auto;"> <tr><td colspan="2" style="text-align: center;">T 39 N</td></tr> <tr><td style="text-align: center;">R 26 E</td><td style="text-align: center;">R 27 E</td></tr> <tr><td style="text-align: center;">S 1</td><td style="text-align: center;">S 6</td></tr> <tr><td style="text-align: center;">S 12</td><td style="text-align: center;">S 7</td></tr> </table>	T 39 N		R 26 E	R 27 E	S 1	S 6	S 12	S 7
T 39 N									
R 26 E	R 27 E								
S 1	S 6								
S 12	S 7								
	2008								
	Deposit a magnet, in a white plastic case, at the base of the stainless steel post.								
	Land, rolling. Soil, sandy clay. Timber, scattered juniper; undergrowth, scattered brush, and native grasses.								
	North, bet. secs. 1 and 6.								
	Over rolling land.								
40.00	Point for the 1/4 sec. cor. of secs. 1 and 6.  Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.								
	<table style="margin-left: auto; margin-right: auto;"> <tr><td colspan="2" style="text-align: center;">T 39 N</td></tr> <tr><td colspan="2" style="text-align: center;">1/4</td></tr> <tr><td style="text-align: center;">R 26 E</td><td style="text-align: center;">R 27 E</td></tr> <tr><td style="text-align: center;">S 1</td><td style="text-align: center;">S 6</td></tr> </table>	T 39 N		1/4		R 26 E	R 27 E	S 1	S 6
T 39 N									
1/4									
R 26 E	R 27 E								
S 1	S 6								
	2008								
	Deposit a magnet, in a white plastic case, at the base of the stainless steel post.								
77.83	Point for the closing cor. of secs. 1 and 6, at intersection with the S. bdy. of sec. 32, T. 40 N., R. 27 E.  Set a brass tablet, 3 1/4 ins. diam., 2 1/2 ins. stem, cemented in place, in a drill hole, in sandstone bedrock, with top mkd.								

**Survey of the West Boundary,  
T. 39 N., R. 27 E., Gila and Salt River Meridian, Arizona**

CHAINS	<div style="text-align: center;"> <p>T 40 N R 27 E S 32</p> <hr style="width: 10%; margin: auto;"/> <p>S 1   S 6 R 26 E   R 27 E T 39 N CC</p> <p>2008</p> </div> <p>Deposit a magnet, in a white plastic case, in the drill hole, beneath the brass tablet.</p> <p>From this cor. point, the 1/4 sec. cor. of sec. 32 only, T. 40 N., R. 27 E., bears East, 37.86 chs. dist., monumented with a stainless steel post, 2 1/2 ins. diam., firmly set, projecting 4 ins. above ground, with brass cap mkd. T40N R27E 1/4 S32 2000.</p> <p>Add the marks T39N R27E 2008 to the brass cap.</p> <p>From this same cor. point, the cor. of secs. 31 and 32 only, T. 40 N., R. 27 E., bears West, 2.14 chs. dist., monumented with a stainless steel post, 2 1/2 ins. diam., firmly set, projecting 3 ins. above ground, with brass cap mkd. T40N R27E S31 S32 2000.</p> <p>Add the marks S1 T39N R26E 2008 to the brass cap.</p> <p>Land, rolling. Soil, sandy clay with sandstone outcrops. Timber, scattered juniper; undergrowth, scattered brush, greasewood, sagebrush and native grasses.</p> <hr/> <p style="text-align: center;"><b>Survey of the Subdivisional Lines, T. 39 N., R. 27 E., Gila and Salt River Meridian, Arizona</b></p> <hr/> <p>From the cor. of secs. 1, 2, 35 and 36, on the S. bdy. of the Tp., hereinbefore described.</p> <p>N. 0°01' W., bet. secs. 35 and 36.</p> <p>Over rugged and broken land.</p> <p>40.00 Point for the 1/4 sec. cor. of secs. 35 and 36.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p>
--------	-----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------

**Survey of the Subdivisional Lines,  
T. 39 N., R. 27 E., Gila and Salt River Meridian, Arizona**

CHAINS	
	T 39 N R 27 E 1/4 S 35   S 36  2008
	Deposit a magnet, in a white plastic case, at the base of the stainless steel post.
80.00	Point for the cor. of secs. 25, 26, 35 and 36.  Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.
	T 39 N R 27 E S 26   S 25 S 35   S 36  2008
	Deposit a magnet, in a white plastic case, at the base of the stainless steel post.  Land, rugged and broken. Soil, sandy clay with sandstone outcrops. Timber, scattered juniper; undergrowth, scattered brush, and native grasses.
	<hr/> From the cor. of secs. 25, 30, 31 and 36, on the E. bdy. of the Tp., hereinbefore described.  West, bet. secs. 25 and 36.  Over rugged and broken land.
17.30	Alcove Canyon wash, 200 ft. wide, 80 ft. deep, drains N. 15° W.
40.00	Point for the 1/4 sec. cor. of secs. 25 and 36.  Set a brass tablet, 3 1/4 ins. diam., 2 1/2 ins. stem, cemented in place, in a drill hole, in sandstone bedrock, with top mkd.
	T 39 N R 27 E S 25 1/4 ——— S 36  2008
	Deposit a magnet, in a white plastic case, in the drill hole, beneath the brass tablet.

**Survey of the Subdivisional Lines,  
T. 39 N., R. 27 E., Gila and Salt River Meridian, Arizona**

CHAINS							
80.00	<p>The cor. of secs. 25, 26, 35 and 36.</p> <p>Land, rugged and broken. Soil, sandy clay with sandstone outcrops. Timber, salt cedar and Russian olive along the wash, and scattered juniper; undergrowth, scattered brush, and native grasses.</p> <hr/> <p>N. 0°01' W., bet. secs. 25 and 26.</p> <p>Over rugged and broken land.</p>						
40.00	<p>Point for the 1/4 sec. cor. of secs. 25 and 26.</p> <p>Set a magnet, in a white plastic case, 24 ins. below the surface of the ground.</p> <p>from which</p> <p style="padding-left: 40px;">A brass tablet, 3 1/4 ins. diam., 2 1/2 ins. stem, cemented in place, in a drill hole, in a sandstone boulder, for a reference monument, bears S. 45°00' W., 370.0 ft. dist., with top mkd. RM T39N R27E 1/4 S26 370.00 FT TO COR. 2008 and an arrow pointing to the cor. Deposit a magnet, in a white plastic case, in the drill hole, beneath the brass tablet.</p> <p style="padding-left: 40px;">A brass tablet, 3 1/4 ins. diam., 2 1/2 ins. stem, cemented in place, in a drill hole, in exposed sandstone bedrock, flush with the surface of the ground, for a reference monument, bears N. 45°00' W., 77.0 ft. dist., with brass cap mkd. RM T39N R27E 1/4 S26 77.00 FT TO COR. 2008 and an arrow pointing to the cor. Deposit a magnet, in a white plastic case, in the drill hole, beneath the brass tablet.</p> <p>The 1/4 sec. cor. is located in Alcove Canyon wash, 150 ft. wide, 50 ft. deep, drains S. 70° W.</p>						
80.00	<p>Point for the cor. of secs. 23, 24, 25 and 26.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <table style="margin-left: auto; margin-right: auto; border-collapse: collapse;"> <tr> <td style="padding: 0 10px;">T 39 N</td> <td style="padding: 0 10px;">R 27 E</td> </tr> <tr> <td style="padding: 0 10px; border-right: 1px solid black;">S 23</td> <td style="padding: 0 10px;">S 24</td> </tr> <tr> <td style="padding: 0 10px; border-right: 1px solid black;">S 26</td> <td style="padding: 0 10px;">S 25</td> </tr> </table> <p style="text-align: center; margin-top: 10px;">2008</p> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p>	T 39 N	R 27 E	S 23	S 24	S 26	S 25
T 39 N	R 27 E						
S 23	S 24						
S 26	S 25						

**Survey of the Subdivisional Lines,  
T. 39 N., R. 27 E., Gila and Salt River Meridian, Arizona**

CHAINS	
	<p>Land, rugged and broken. Soil, sandy clay with sandstone outcrops. Timber, salt cedar and Russian olive along the wash and scattered juniper; undergrowth, scattered brush and native grasses.</p> <hr/> <p>From the cor. of secs. 19, 24, 25 and 30, on the E. bdy. of the Tp., hereinbefore described.</p> <p>West, bet. secs. 24 and 25.</p> <p>Over rolling land.</p>
4.80	Navajo Route 5037, a graded road, 30 ft. wide, bears S. 60° E. and N. 60° W.
22.10	From this point, the pump shaft of a windmill, bears North, 3.25 chs. dist.
27.75	Trail road, bears N. 70° E. and S. 70° W.
29.70	Trail road, bears North and South.
38.12	Power line, bears N. 40° E. and S. 40° W.
40.00	<p>Point for the 1/4 sec. cor. of secs. 24 and 25.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T 39 N R 27 E S 24 1/4 ——— S 25</p> <p style="text-align: center;">2008</p> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p>
62.55	Trail road, bears North and South.
80.00	The cor. of secs. 23, 24, 25 and 26.



**Survey of the Subdivisional Lines,  
T. 39 N., R. 27 E., Gila and Salt River Meridian, Arizona**

CHAINS	
	<p>Land, rolling. Soil, sandy clay with sandstone outcrops. Timber, scattered juniper; undergrowth, scattered brush, and native grasses.</p> <hr/>
	<p>N. 0°01' W., bet. secs. 23 and 24.</p> <p>Over rolling and broken land.</p>
20.20	Trail road, bears N. 85° E. and S. 85° W.
26.20	Power line, bears N. 55° E. and S. 55° W.
40.00	Point for the 1/4 sec. cor. of secs. 23 and 24.
	<p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T 39 N R 27 E 1/4 S 23   S 24</p> <p style="text-align: center;">2008</p> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p>
40.60	Seklagaldesa Canyon wash, 30 ft. wide, 75 ft. deep, drains S. 70° W.
80.00	Point for the cor. of secs. 13, 14, 23 and 24.
	<p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T 39 N R 27 E S 14   S 13 S 23   S 24</p> <p style="text-align: center;">2008</p> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p> <p>Land, rolling and broken. Soil, sandy clay with sandstone outcrops. Timber, scattered juniper; undergrowth, scattered brush and native grasses.</p> <hr/>
	<p>From the cor. of secs. 13, 18, 19, and 24, on the E. bdy. of the Tp., hereinbefore described.</p>

**Survey of the Subdivisional Lines,  
T. 39 N., R. 27 E., Gila and Salt River Meridian, Arizona**

CHAINS	
	West, bet. secs. 13 and 24.  Over rolling and broken land.
4.30	Seklagaldesa Canyon wash, 60 ft. wide, 75 ft. deep, drains S. 65° W.
40.00	Point for the 1/4 sec. cor. of secs. 13 and 24.  Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.  <div style="text-align: center;">           T 39 N R 27 E                  S 13                  1/4 ———                  S 24             2008         </div> Deposit a magnet, in a white plastic case, at the base of the stainless steel post.
53.20	Navajo Route 5037, a graded road, 25 ft. wide, bears S. 65° E. and N. 65° W.
55.60	Power line, bears North and South.
80.00	The cor. of secs. 13, 14, 23 and 24.  Land, rolling and broken. Soil, sandy clay with sandstone outcrops. Timber, scattered juniper; undergrowth, scattered brush, greasewood, and native grasses.
	<hr/> N. 0°01' W., bet. secs. 13 and 14.  Over rolling land.
40.00	Point for the 1/4 sec. cor. of secs. 13 and 14.  Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.  <div style="text-align: center;">           T 39 N R 27 E                  1/4                  S 14   S 13             2008         </div> Deposit a magnet, in a white plastic case, at the base of the stainless steel post.
44.23	Power line, bears S. 25° E. and N. 25° W.

**Survey of the Subdivisional Lines,  
T. 39 N., R. 27 E., Gila and Salt River Meridian, Arizona**

CHAINS									
68.80	Toh Chin Lini Canyon wash, 60 ft. wide, 4 ft. deep, drains N. 65° W.								
76.00	Navajo Route 5037, a graded road, 30 ft. wide, bears S. 20° E. and N. 20° W.								
80.00	Point for the cor. of secs. 11, 12, 13 and 14.  Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.  <div style="text-align: center;"> <table border="0"> <tr> <td>T 39 N</td> <td>R 27 E</td> </tr> <tr> <td>S 11</td> <td>S 12</td> </tr> <tr> <td>S 14</td> <td>S 13</td> </tr> </table> <p>2008</p> </div> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p> <p>Land, rolling. Soil, sandy clay and sandstone outcrops. Timber, scattered juniper; undergrowth, scattered brush, greasewood, and native grasses.</p> <hr/> <p>From the cor. of secs. 7, 12, 13 and 18, on the E. bdy. of the Tp., hereinbefore described.</p> <p>West, bet. secs. 12 and 13.</p> <p>Over rolling and broken land.</p>	T 39 N	R 27 E	S 11	S 12	S 14	S 13		
T 39 N	R 27 E								
S 11	S 12								
S 14	S 13								
4.60	SW rim of a mesa, bears S. 20° E. and N. 20° W., thence descending into rolling land.								
40.00	Point for the 1/4 sec. cor. of secs. 12 and 13.  Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.  <div style="text-align: center;"> <table border="0"> <tr> <td>T 39 N</td> <td>R 27 E</td> </tr> <tr> <td></td> <td>S 12</td> </tr> <tr> <td>1/4</td> <td>—</td> </tr> <tr> <td></td> <td>S 13</td> </tr> </table> <p>2008</p> </div> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p>	T 39 N	R 27 E		S 12	1/4	—		S 13
T 39 N	R 27 E								
	S 12								
1/4	—								
	S 13								
66.10	Toh Chin Lini Canyon wash, 25 ft. wide, 10 ft. deep, drains S. 40° W.								

**Survey of the Subdivisional Lines,  
T. 39 N., R. 27 E., Gila and Salt River Meridian, Arizona**

CHAINS	
80.00	<p>The cor. of secs. 11, 12, 13 and 14.</p> <p>Land, rolling and broken. Soil, sandy clay with sandstone outcrops. Timber, scattered juniper; undergrowth, greasewood, scattered brush, and native grasses.</p> <hr/> <p>N. 0°01' W., bet. secs. 11 and 12.</p> <p>Over rolling land.</p>
40.00	<p>Point for the 1/4 sec. cor. of secs. 11 and 12.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T 39 N R 27 E 1/4 S 11   S 12</p> <p style="text-align: center;">2008</p> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p>
41.50	<p>Wash, 30 ft. wide, 12 ft. deep, drains N. 75° W.</p>
54.40	<p>Navajo Route 5043, a graded road, 30 ft. wide, bears N. 50° E. and S. 50° W.</p>
66.37	<p>Power line, bears N. 50° E. and S. 50° W.</p>
80.00	<p>Point for the cor. of secs. 1, 2, 11 and 12.</p> <p>Set a brass tablet, 3 1/4 ins. diam., 2 1/2 ins. stem, cemented in place, in a drill hole, in sandstone bedrock, with top mkd.</p> <p style="text-align: center;">T 39 N R 27 E S 2   S 1 S 11   S 12</p> <p style="text-align: center;">2008</p> <p>Deposit a magnet, in a white plastic case, in the drill hole, beneath the brass tablet.</p>

**Survey of the Subdivisional Lines,  
T. 39 N., R. 27 E., Gila and Salt River Meridian, Arizona**

CHAINS	
	<p>Land, rolling. Soil, sandy clay with sandstone outcrops. Timber, scattered juniper; undergrowth, greasewood, scattered brush, and native grasses.</p> <hr/> <p>From the cor. of secs. 1, 6, 7 and 12, on the E. bdy. of the Tp., hereinbefore described.</p> <p>West, bet. secs. 1 and 12.</p> <p>Over rolling land.</p>
40.00	<p>Point for the 1/4 sec. cor. of secs. 1 and 12.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T 39 N R 27 E S 1 1/4 ——— S 12</p> <p style="text-align: center;">2008</p> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p>
41.70	Wash, 30 ft. wide, 12 ft. deep, drains South.
59.10	Navajo Route 5043, a graded road, 30 ft. wide, bears N. 35° E. and S. 35° W.
62.86	Power line, bears N. 50° E. and S. 50° W.
80.00	<p>The cor. of secs. 1, 2, 11 and 12.</p> <p>Land, rolling. Soil, sandy clay with sandstone outcrops. Timber, scattered juniper; undergrowth, scattered brush, greasewood, and native grasses.</p> <hr/> <p>N. 0°01' W., bet. secs. 1 and 2.</p> <p>Over rolling land.</p>
40.00	<p>Point for the 1/4 sec. cor. of secs. 1 and 2.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p>

**Survey of the Subdivisional Lines,  
T. 39 N., R. 27 E., Gila and Salt River Meridian, Arizona**

CHAINS	<p style="text-align: center;">T 39 N R 27 E 1/4 S 2   S 1  2008</p> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p>
77.84	<p>Point for the closing cor. of secs. 1 and 2, at intersection with the S. bdy. of sec. 31, T. 40 N., R. 28 E.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T 40 N R 28 E S 31 ----- S 2   S 1 T 39 N R 27 E CC 2008</p> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p> <p>From this cor. point, the 1/4 sec. cor. of sec. 31 only, T. 40 N., R. 28 E., bears East, 37.86 chs. dist., monumented with a stainless steel post, 2 1/2 ins. diam., firmly set, projecting 4 ins. above ground, with brass cap mkd. T40N R28E 1/4 S31 2006.</p> <p>Add the marks T39N R27E 2008 to the brass cap.</p> <p>From this same cor. point, the cor. of Tps. 40 N., Rs. 27 and 28 E., bears West, 0.52 chs. dist., monumented with a stainless steel post, 2 1/2 ins. diam., firmly set flush with surface of the ground, with brass cap mkd. T40N R27E R28E S36 S31 2006.</p> <p>Add the marks S2 T39N R27E 2008 to the brass cap.</p> <p>Land, rolling. Soil, sandy clay with sandstone outcrops. Timber, scattered juniper; undergrowth, scattered brush, greasewood, and native grasses.</p> <hr/> <p>Point for the 1/4 sec. cor. of sec. 1 only, at midpoint on the N. bdy. of sec. 1.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p>

**Survey of the Subdivisional Lines,  
T. 39 N., R. 27 E., Gila and Salt River Meridian, Arizona**

CHAINS	
	<p>T 40 N R 28 E</p> <hr style="width: 10%; margin: auto;"/> <p>1/4 S 1 T 39 N R 27 E</p> <p>2008</p>
	<p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p> <p>From this cor. point, the cor. of secs. 31 and 32 only, T. 40 N., R. 28 E., bears East, 37.86 chs. dist., hereinbefore described.</p> <p>From this same cor. point, the 1/4 sec. cor. of sec. 31 only, T. 40 N., R. 28 E., bears West, 2.14 chs. dist.</p> <hr/> <p>From the true point for the cor. of secs. 2, 3, 34 and 35, on the S. bdy. of the Tp., hereinbefore described.</p> <p>N. 0°01' W., bet. secs. 34 and 35.</p> <p>Over broken land, descend into a valley.</p>
40.00	<p>Point for the 1/4 sec. cor. of secs. 34 and 35.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 22 ins. in the ground, encircled with a collar of stone, with brass cap mkd.</p>
	<p>T 39 N R 27 E 1/4 S 34   S 35</p> <p>2008</p>
80.00	<p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p> <p>Point for the cor. of secs. 26, 27, 34 and 35.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 22 ins. in the ground, encircled with a collar of stone, with brass cap mkd.</p>
	<p>T 39 N R 27 E S 27   S 26 S 34   S 35</p> <p>2008</p>

**Survey of the Subdivisional Lines,  
T. 39 N., R. 27 E., Gila and Salt River Meridian, Arizona**

CHAINS	
	<p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p> <p>Land, broken. Soil, sandy clay with sandstone outcrops. Timber, scattered juniper; undergrowth, scattered brush, and native grasses.</p> <hr/> <p>From the cor. of secs. 25, 26, 35 and 36.</p> <p>West, bet. secs. 26 and 35.</p> <p>Over rolling and broken land.</p>
39.60	Wash, 30 ft. wide, 50 ft. deep, drains N. 30° W.
40.00	<p>Point for the 1/4 sec. cor. of secs. 26 and 35.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center;"> <p>T 39 N R 27 E</p> <p>S 26</p> <p>1/4 ———</p> <p>S 35</p> <p>2008</p> </div>
80.00	<p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p> <p>The cor. of secs. 26, 27, 34 and 35.</p> <p>Land, rolling and broken. Soil, sandy clay with sandstone outcrops. Timber, scattered salt cedar and Russian olive along the wash; undergrowth, scattered brush and native grasses.</p> <hr/> <p>N. 0°01' W., bet. secs. 26 and 27.</p> <p>Over broken land.</p>
40.00	<p>Point for the 1/4 sec. cor. of secs. 26 and 27.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 22 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center;"> <p>T 39 N R 27 E</p> <p>1/4</p> <p>S 27   S 26</p> <p>2008</p> </div>



**Survey of the Subdivisional Lines,  
T. 39 N., R. 27 E., Gila and Salt River Meridian, Arizona**

CHAINS									
	Deposit a magnet, in a white plastic case, at the base of the stainless steel post.								
69.00	Wash, 20 ft. wide, 40 ft. deep, drains N. 40° E.								
80.00	Point for the cor. of secs. 22, 23, 26 and 27.								
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.								
	<table style="margin: auto;"> <tr> <td>T 39 N</td> <td>R 27 E</td> </tr> <tr> <td>S 22</td> <td>S 23</td> </tr> <tr> <td>S 27</td> <td>S 26</td> </tr> </table>	T 39 N	R 27 E	S 22	S 23	S 27	S 26		
T 39 N	R 27 E								
S 22	S 23								
S 27	S 26								
	2008								
	Deposit a magnet, in a white plastic case, at the base of the stainless steel post.								
	Land, broken.								
	Soil, sandy clay with sandstone outcrops.								
	Timber, scattered juniper; undergrowth, scattered brush, and native grasses.								
	<hr/>								
	From the cor. of secs. 23, 24, 25 and 26.								
	West, bet. secs. 23 and 26.								
	Over broken land.								
31.10	Alcove Canyon wash, 200 ft. wide, 20 ft. deep, drains N. 20° W.								
40.00	Point for the 1/4 sec. cor. of secs. 23 and 26.								
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.								
	<table style="margin: auto;"> <tr> <td>T 39 N</td> <td>R 27 E</td> </tr> <tr> <td></td> <td>S 23</td> </tr> <tr> <td>1/4</td> <td>—</td> </tr> <tr> <td></td> <td>S 26</td> </tr> </table>	T 39 N	R 27 E		S 23	1/4	—		S 26
T 39 N	R 27 E								
	S 23								
1/4	—								
	S 26								
	2008								
	Deposit a magnet, in a white plastic case, at the base of the stainless steel post.								
75.70	Wash, 10 ft. wide, 20 ft. deep, drains N. 35° E.								
80.00	The cor. of secs. 22, 23, 26 and 27.								

**Survey of the Subdivisional Lines,  
T. 39 N., R. 27 E., Gila and Salt River Meridian, Arizona**

CHAINS	
	<p>Land, broken. Soil, sandy clay with sandstone outcrops. Timber, scattered juniper; undergrowth, scattered brush, and native grasses.</p> <hr/> <p>N. 0°01' W., bet. secs. 22 and 23.</p> <p>Over rolling and broken.</p>
27.40	Alcove Canyon wash, 100 ft. wide, 25 ft. deep, drains West.
40.00	<p>Point for the 1/4 sec. cor. of secs. 22 and 23.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center;"> <p>T 39 N R 27 E 1/4 S 22   S 23</p> <p>2008</p> </div> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p>
80.00	<p>Point for the cor. of secs. 14, 15, 22 and 23.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center;"> <p>T 39 N R 27 E S 15   S 14 S 22   S 23</p> <p>2008</p> </div> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p> <p>Land, rolling and broken. Soil, sandy clay with sandstone outcrops. Timber, salt cedar and Russian olive along the wash, and scattered juniper; undergrowth, scattered brush, and native grasses.</p> <hr/> <p>From the cor. of secs. 13, 14, 23, and 24.</p> <p>West, bet secs. 14 and 23.</p> <p>Over rolling land.</p>

**Survey of the Subdivisional Lines,  
T. 39 N., R. 27 E., Gila and Salt River Meridian, Arizona**

CHAINS	
40.00	<p>Point for the 1/4 sec. cor. of secs. 14 and 23.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T 39 N R 27 E S 14 1/4 ——— S 23</p> <p style="text-align: center;">2008</p> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p>
80.00	<p>The cor. of secs. 14, 15, 22 and 23.</p> <p>Land, rolling. Soil, sandy clay and sandstone outcrops. Timber, scattered juniper; undergrowth, scattered brush, greasewood, and native grasses.</p> <hr/> <p>N. 0°01' W., bet. secs. 14 and 15.</p> <p>Over rolling and broken land.</p>
40.00	<p>Point for the 1/4 sec. cor. of secs. 14 and 15.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T 39 N R 27 E 1/4 S 15   S 14</p> <p style="text-align: center;">2008</p> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p>
65.90	<p>Toh Chin Lini Canyon wash, 10 ft. wide, 30 ft. deep, drains S. 45° W.</p>
80.00	<p>Point for the cor. of secs. 10, 11, 14 and 15.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p>

**Survey of the Subdivisional Lines,  
T. 39 N., R. 27 E., Gila and Salt River Meridian, Arizona**

CHAINS	
	T 39 N R 27 E S 10   S 11 S 15   S 14
	2008
	Deposit a magnet, in a white plastic case, at the base of the stainless steel post.
	Land, rolling and broken. Soil, sandy clay with sandstone outcrops. Timber, scattered juniper; scattered brush, greasewood, sagebrush, and native grasses.
	From the cor. of secs. 11, 12, 13, and 14.
	West, bet. secs. 11 and 14.
	Over nearly level and rolling land.
1.50	Navajo Route 5037, a graded road, 30 ft. wide, bears S. 20° E. and N. 20° W.
15.70	Trail road, bears N. 45° E. and S. 45° W.
17.08	Power line, bears S. 25° E. and N. 25° W.
40.00	Point for the 1/4 sec. cor. of secs. 11 and 14.
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.
	T 39 N R 27 E S 11 1/4 ——— S 14
	2008
	Deposit a magnet, in a white plastic case, at the base of the stainless steel post.
80.00	The cor. of secs. 10, 11, 14 and 15.
	Land, nearly level and rolling. Soil, sandy clay with sandstone outcrops. Timber, scattered juniper; undergrowth, scattered brush, greasewood, and native grasses.
	N. 0°01' W., bet. secs. 10 and 11.

**Survey of the Subdivisional Lines,  
T. 39 N., R. 27 E., Gila and Salt River Meridian, Arizona**

CHAINS	
	Over rolling land.
5.45	Power line, bears N. 55° E. and S. 55° W.
21.05	Trail road, bears S. 65° E. and N. 65° W.
33.55	Apache County Road C537, a graded road, 20 ft. wide, bears N. 35° E. and S. 35° W. to termination at residential area.
40.00	Point for the 1/4 sec. cor. of secs. 10 and 11.  Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.  <div style="text-align: center;">           T 39 N R 27 E                  1/4            S 10   S 11             2008         </div> Deposit a magnet, in a white plastic case, at the base of the stainless steel post.
60.10	Navajo Route 5043, a graded road, 30 ft. wide, bears S. 60° E. and N. 60° W.
75.20	Wash, 30 ft. wide, 5 ft. deep, drains S. 25° W.
80.00	Point for the cor. of secs. 2, 3, 10 and 11.  Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.  <div style="text-align: center;">           T 39 N R 27 E            S 3   S 2            S 10   S 11             2008         </div> Deposit a magnet, in a white plastic case, at the base of the stainless steel post.  Land, rolling. Soil, sandy clay with sandstone outcrops. Timber, scattered juniper; scattered brush, greasewood, sagebrush and native grasses.
	From the cor. of secs. 1, 2, 11, and 12.
	West, bet. secs. 2 and 11.
	Over rolling land.

**Survey of the Subdivisional Lines,  
T. 39 N., R. 27 E., Gila and Salt River Meridian, Arizona**

CHAINS	
40.00	<p>Point for the 1/4 sec. cor. of secs. 2 and 11.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T 39 N R 27 E S 2 1/4 ——— S 11</p> <p style="text-align: center;">2008</p> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p>
45.80	W. rim of a mesa, bears N. 20° E. and S. 20° W.
77.50	Wash, 45 ft. wide, 5 ft. deep, drains S. 30° W.
80.00	<p>The cor. of secs. 2, 3, 10 and 11.</p> <p>Land, rolling. Soil, sandy clay with sandstone outcrops. Timber, scattered juniper; undergrowth, scattered brush, greasewood, sagebrush and native grasses.</p> <hr/> <p>N. 0°01' W., bet. secs. 2 and 3.</p> <p>Over rolling land.</p>
40.00	<p>Point for the 1/4 sec. cor. of secs. 2 and 3.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 22 ins. in the ground, in a mound of stone, 3 ft. base, to top, with brass cap mkd.</p> <p style="text-align: center;">T 39 N R 27 E 1/4 S 3   S 2</p> <p style="text-align: center;">2008</p> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p>
77.83	<p>Point for the closing cor. of secs. 2 and 3, at intersection with the S. bdy. of sec. 36, T. 40 N., R. 27 E.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p>

**Survey of the Subdivisional Lines,  
T. 39 N., R. 27 E., Gila and Salt River Meridian, Arizona**

CHAINS

T 40 N R 27 E  
S 36  
-----  
S 3 | S 2  
T 39 N R 27 E  
CC  
2008

Deposit a magnet, in a white plastic case, at the base of the stainless steel post.

From this cor. point, the 1/4 sec. cor. of sec. 36 only, T. 40 N., R. 27 E., bears East, 39.48 chs. dist., monumented with a stainless steel post, 2 1/2 ins. diam., firmly set, projecting 6 ins. above ground, with brass cap mkd. T40N R27E 1/4 S36 2000.

Add the marks T39N R27E 2008 to the brass cap.

From this same cor. point, an iron pipe, 2 1/2 ins. diam., firmly set, projecting 7 ins. above ground, established by Ernest V. Echohawk, R.L.S. No. 2311, Az., in 1958, bears S. 75°40' W., 1.31 chs. dist., mkd. T40N R27E 35 36 1 2 T39N on the side.

From this same cor. point, the cor. of secs. 35 and 36 only, T. 40 N., R. 27 E., bears West, 0.52 chs. dist., monumented with a stainless steel post, 2 1/2 ins. diam., firmly set, projecting 5 ins. above ground, with brass cap mkd. T40N R27E S35 S36 2000.

Add the marks S3 T39N R27E 2008 to the brass cap.

Land, rolling.

Soil, sandy clay with sandstone outcrops.

Timber, scattered juniper; undergrowth, scattered brush, greasewood, sagebrush and native grasses.

---

Point for the 1/4 cor. sec. of sec. 2 only, at midpoint on the N. bdy. of sec. 2.

Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.

T 40 N R 27 E  
-----  
1/4 S 2  
T 39 N R 27 E  
2008

Deposit a magnet, in a white plastic case, at the base of the stainless steel post.

**Survey of the Subdivisional Lines,  
T. 39 N., R. 27 E., Gila and Salt River Meridian, Arizona**

CHAINS	
	<p>From this cor. point, the cor. of Tps. 40 N., Rs. 27 and 28 E., bears East, 39.48 chs. dist.</p> <p>From this same cor. point, the 1/4 sec. cor. of sec. 36 only, bears West, 0.52 chs. dist.</p> <hr/> <p>From the cor. of secs. 3, 4, 33 and 34, on the S. bdy. of the Tp., hereinbefore described.</p> <p>N. 0°02' W., bet. secs. 33 and 34.</p> <p>Over rolling and broken land.</p>
40.00	<p>Point for the 1/4 sec. cor. of secs. 33 and 34.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center;"> <p>T 39 N R 27 E 1/4 S 33   S 34</p> <p>2008</p> </div> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p>
47.70	<p>N. rim of a mesa, bears N. 85° E. and S. 85° W, thence descend into a valley.</p>
80.00	<p>Point for the cor. of secs. 27, 28, 33, and 34.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center;"> <p>T 39 N R 27 E S 28   S 27 S 33   S 34</p> <p>2008</p> </div> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p> <p>Land, rolling and broken. Soil, sandy clay with sandstone outcrops. Timber, scattered juniper; undergrowth, greasewood, scattered brush, and native grasses.</p> <hr/> <p>From the cor. of secs. 26, 27, 34 and 35.</p>



**Survey of the Subdivisional Lines,  
T. 39 N., R. 27 E., Gila and Salt River Meridian, Arizona**

CHAINS	
	West, bet. secs. 27 and 34.  Over broken land.
39.10	Base of a sandstone ridge, bears North and South, thence ascend the rock ridge.
40.00	Point for the 1/4 sec. cor. of secs. 27 and 34.  Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.
	T 39 N R 27 E S 27 1/4 ——— S 34  2008
	Deposit a magnet, in a white plastic case, at the base of the stainless steel post.
80.00	The cor. of secs. 27, 28, 33 and 34.  Land, broken. Soil, sandy clay with sandstone outcrops. Timber, scattered juniper; undergrowth, scattered brush, greasewood, and native grasses.
	_____
	N. 0°02' W., bet. secs. 27 and 28.  Over rolling land.
38.10	Wash, 20 ft. wide, 4 ft. deep, drains N. 85° E.
40.00	Point for the 1/4 sec. cor. of secs. 27 and 28.  Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.
	T 39 N R 27 E 1/4 S 28   S 27  2008
	Deposit a magnet, in a white plastic case, at the base of the stainless steel post.
80.00	Point for the cor. of secs. 21, 22, 27 and 28.  Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.

**Survey of the Subdivisional Lines,  
T. 39 N., R. 27 E., Gila and Salt River Meridian, Arizona**

CHAINS	<div style="text-align: center; margin-bottom: 10px;"> <table style="margin: auto; border-collapse: collapse;"> <tr> <td style="padding: 0 10px;">T 39 N</td> <td style="padding: 0 10px;">R 27 E</td> </tr> <tr> <td style="padding: 0 10px; border-right: 1px solid black;">S 21</td> <td style="padding: 0 10px;">S 22</td> </tr> <tr> <td style="padding: 0 10px; border-right: 1px solid black;">S 28</td> <td style="padding: 0 10px;">S 27</td> </tr> </table> </div> <div style="text-align: center; margin-bottom: 10px;">2008</div> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p> <p>Land, rolling. Soil, sandy clay with sandstone outcrops. Timber, scattered juniper; undergrowth, scattered brush, yucca, and native grasses.</p> <hr style="width: 80%; margin: 10px auto;"/> <p>From the cor. of secs. 22, 23, 26 and 27.</p> <p>West, bet. secs. 22 and 27.</p> <p>Over rolling and broken land.</p> <p>40.00 Point for the 1/4 sec. cor. of secs. 22 and 27.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center; margin-bottom: 10px;"> <table style="margin: auto; border-collapse: collapse;"> <tr> <td style="padding: 0 10px;">T 39 N</td> <td style="padding: 0 10px;">R 27 E</td> </tr> <tr> <td></td> <td style="padding: 0 10px;">S 22</td> </tr> <tr> <td></td> <td style="padding: 0 10px;">1/4 ———</td> </tr> <tr> <td></td> <td style="padding: 0 10px;">S 27</td> </tr> </table> </div> <div style="text-align: center; margin-bottom: 10px;">2008</div> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p> <p>80.00 The cor. of secs. 21, 22, 27 and 28.</p> <p>Land, rolling and broken. Soil, sandy clay with sandstone outcrops. Timber, scattered juniper; undergrowth, scattered brush, and native grasses.</p> <hr style="width: 80%; margin: 10px auto;"/> <p>N. 0°02' W., bet. secs. 21 and 22.</p> <p>Over rolling land.</p> <p>40.00 Point for the 1/4 sec. cor. of secs. 21 and 22.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p>	T 39 N	R 27 E	S 21	S 22	S 28	S 27	T 39 N	R 27 E		S 22		1/4 ———		S 27
T 39 N	R 27 E														
S 21	S 22														
S 28	S 27														
T 39 N	R 27 E														
	S 22														
	1/4 ———														
	S 27														

**Survey of the Subdivisional Lines,  
T. 39 N., R. 27 E., Gila and Salt River Meridian, Arizona**

CHAINS	
	T 39 N R 27 E 1/4 S 21   S 22  2008
80.00	Deposit a magnet, in a white plastic case, at the base of the stainless steel post.  Point of the cor. of secs. 15, 16, 21 and 22.  Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.
	T 39 N R 127 E S 16   S 15 S 21   S 22  2008
	Deposit a magnet, in a white plastic case, at the base of the stainless steel post.  Land, rolling. Soil, sandy clay with sandstone outcrops. Timber, scattered juniper; undergrowth, greasewood, scattered brush, and native grasses.
	From the cor. of secs. 14, 15, 22 and 23.  West, bet. secs. 15 and 22.  Over rolling land.
37.60	Alcove Canyon wash, 100 ft. wide, 5 ft. deep, drains N. 15° W.
40.00	Point for the 1/4 sec. cor. of secs. 15 and 22.  Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.
	T 39 N R 27 E S 15 1/4 ——— S 22  2008
80.00	Deposit a magnet, in a white plastic case, at the base of the stainless steel post.  The cor. of secs. 15, 16, 21 and 22.

**Survey of the Subdivisional Lines,  
T. 39 N., R. 27 E., Gila and Salt River Meridian, Arizona**

CHAINS	
	<p>Land, rolling. Soil, sandy clay and sandstone outcrops. Timber, salt cedar along the wash, scattered juniper; undergrowth, scattered brush, greasewood, sagebrush and native grasses.</p> <hr/> <p>N. 0°02' W., bet. secs. 15 and 16.</p> <p>Over rolling and broken land.</p>
40.00	<p>Point for the 1/4 sec. cor. of secs. 15 and 16.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T 39 N R 27 E 1/4 S 16   S 15</p> <p style="text-align: center;">2008</p> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p>
70.70	Walker Creek wash, 50 ft. wide, 5 ft. deep, drains N. 70° W.
78.30	Navajo Route 5043, a graded road, 15 ft. wide, bears N. 75° E. and S. 75° W.
80.00	<p>Point for the cor. of secs. 9, 10, 15 and 16.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T 39 N R 27 E S 9   S 10 ----- S 16   S 15</p> <p style="text-align: center;">2008</p> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p> <p>Land, rolling and broken. Soil, sandy clay with sandstone outcrops. Timber, scattered salt cedar along the wash; undergrowth, scattered brush, sagebrush, and native grasses.</p> <hr/> <p>From the cor. of secs. 10, 11, 14 and 15.</p> <p>West, bet. secs. 10 and 15.</p>

**Survey of the Subdivisional Lines,  
T. 39 N., R. 27 E., Gila and Salt River Meridian, Arizona**

CHAINS	
	Over rolling land.
34.44	Power line, bears S. 45° E. and N. 45° W.
35.70	Trail road, bears N. 65° E. and S. 65° W.
40.00	Point for the 1/4 sec. cor. of secs. 10 and 15.  Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.  <div style="text-align: center;">           T 39 N R 27 E                      S 10                  1/4 ———                      S 15             2008         </div> Deposit a magnet, in a white plastic case, at the base of the stainless steel post.
74.10	Navajo Route 5043, a graded road, 15 ft. wide, bears N. 60° E. and S. 60° W.
75.22	Power line, bears N. 35° E. and S. 35° W.
80.00	The cor. of secs. 9, 10, 15 and 16.  Land, rolling. Soil, sandy clay, with sandstone outcrops. Timber, scattered juniper; undergrowth, scattered brush, sagebrush, greasewood and native grasses. <hr/>
	N. 0°02' W., bet. secs. 9 and 10.  Over rolling land.
40.00	Point for the 1/4 sec. cor. of secs. 9 and 10.  Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.  <div style="text-align: center;">           T 39 N R 27 E                      1/4                  S 9   S 10             2008         </div> Deposit a magnet, in a white plastic case, at the base of the stainless steel post.
80.00	Point for the cor. of secs. 3, 4, 9 and 10.

**Survey of the Subdivisional Lines,  
T. 39 N., R. 27 E., Gila and Salt River Meridian, Arizona**

CHAINS	<p>Set a brass tablet, 3 1/4 ins. diam., 2 1/2 ins. stem, cemented in place, in a drill hole, in sandstone bedrock, with top mkd.</p> <p align="center">                     T 39 N R 27 E                      S 4   S 3  <hr style="width: 50%; margin: auto;"/>                     S 9   S 10                 </p> <p align="center">2008</p> <p>Deposit a magnet, in a white plastic case, in the drill hole, beneath the brass tablet.</p> <p>Cor. is located at the base of a mesa, bears N. 65°E. and S. 65°W.</p> <p>Land, rolling. Soil, sandy clay with sandstone outcrops. Timber, scattered juniper; undergrowth, scattered brush, sagebrush, greasewood, and native grasses.</p> <hr/> <p>From the cor. of secs. 2, 3, 10 and 11.</p> <p>West, bet. secs. 3 and 10.</p> <p>Over rolling and broken land, ascend the E. slope of a mesa.</p> <p>40.00 Point for the 1/4 sec. cor. of secs. 3 and 10.</p> <p>Set a brass tablet, 3 1/4 ins. diam., 2 1/2 ins. stem, cemented in place, in a drill hole, in sandstone bedrock, with top mkd.</p> <p align="center">                     T 39 N R 27 E                      S 3                      1/4 ———                      S 10                 </p> <p align="center">2008</p> <p>Deposit a magnet, in a white plastic case, in the drill hole, beneath the brass tablet.</p> <p>40.70 E. rim of a mesa, bears N. 45° E. and S. 50° W.</p> <p>80.00 The cor. of secs. 3, 4, 9 and 10.</p>
--------	-----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------

**Survey of the Subdivisional Lines,  
T. 39 N., R. 27 E., Gila and Salt River Meridian, Arizona**

CHAINS	
	<p>Land, rolling and broken. Soil, sandy clay with sandstone outcrops. Timber, scattered juniper; undergrowth, scattered brush, sagebrush, yucca, and native grasses.</p> <hr/> <p>N. 0°02' W., bet. secs. 3 and 4.</p> <p>Over rolling land, ascend the S. slope of a mesa.</p>
1.00	S. rim of a mesa, bears N. 65° E. and S. 65° W, thence over rolling land.
19.10	Trail road, bears N. 55° E. and S. 55° W.
40.00	<p>Point for the 1/4 sec. cor. of secs. 3 and 4.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center;"> <p>T 39 N R 27 E 1/4 S 4   S 3</p> <p>2008</p> </div> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p>
77.84	<p>Point for the closing cor. of secs. 3 and 4, at intersection with the S. bdy. of sec. 35, T. 40 N., R. 27 E.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center;"> <p>T 40 N R 27 E S 35</p> <hr style="width: 10%; margin: 0 auto;"/> <p>S 4   S 3 T 39 N R 27 E CC 2008</p> </div> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p> <p>From this cor. point, the 1/4 sec. cor. of sec. 35 only, T. 40 N., R. 27 E., bears East, 39.47 chs. dist., monumented with only a memorial; a magnet, in a white plastic case, set 24 ins. below the surface of the ground.</p> <p>There is no remaining evidence of the orig. stainless steel post.</p>

**Survey of the Subdivisional Lines,  
T. 39 N., R. 27 E., Gila and Salt River Meridian, Arizona**

CHAINS

At the corner point

Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam.,  
24 ins. in the ground, with brass cap mkd.

T 40 N R 27 E  
1/4 S 35  
—

T 39 N R 27 E

2008

Redeposit the magnet, in a white plastic case, at the base of  
the stainless steel post.

From this same cor. point, a concrete filled iron pipe,  
2 1/2 ins. diam., firmly set, projecting 5 ins. above ground,  
established by Ernest V. Echohawk, R.L.S. No. 2311, Az., in  
1958, bears S. 77°21' W., 1.18 chs. dist., mkd. T40N R27E 34 35  
2 3 T39N on the side.

From this same cor. point, the cor. of secs. 34 and 35 only,  
T. 40 N., R. 27 E., bears West, .53 chs. dist., monumented with  
only a memorial; a magnet, in a white plastic case, set 24 ins.  
below ground.

There is no remaining evidence of the orig. stainless steel  
post.

At the corner point

Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam.,  
24 ins. in the ground, with brass cap mkd.

T 40 N R 27 E  
S 34 | S 35  
—

S 4

T 39 N R 27 E

2008

Redeposit the magnet, in a white plastic case, at the base of  
the stainless steel post.

Land, rolling.

Soil, sandy clay with sandstone outcrops.

Timber, scattered juniper; undergrowth, scattered brush, yucca,  
greasewood and native grasses.

---

Point for the 1/4 sec. cor. of sec. 3 only, at midpoint on the  
N. bdy. of sec. 3.



**Survey of the Subdivisional Lines,  
T. 39 N., R. 27 E., Gila and Salt River Meridian, Arizona**

CHAINS	
	<p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T 40 N R 27 E</p> <p style="text-align: center;">——— 1/4 S 3 T 39 N R 27 E</p> <p style="text-align: center;">2008</p> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p> <p>From this cor. point, the cor. of secs. 35 and 36 only, T. 40 N., R. 27 E., bears East, 39.475 chs. dist.</p> <p>From this same cor. point, the 1/4 sec. cor. of sec. 35 only, T. 40 N., R. 27 E., bears West, 0.525 chs. dist.</p> <hr/> <p>From the cor. of secs. 4, 5, 32 and 33, on the S. bdy of Tp., hereinbefore described.</p> <p>N. 0°03' W., bet. secs. 32 and 33.</p> <p>Over rolling land.</p>
37.30	Navajo Route 5040, a graded road, 30 ft. wide, bears S. 85° E. and N. 85° W.
40.00	<p>Point for the 1/4 sec. cor. of secs. 32 and 33.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T 39 N R 27 E 1/4 S 32   S 33</p> <p style="text-align: center;">2008</p> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p>
80.00	<p>Point for the cor. of secs. 28, 29, 32 and 33.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p>

**Survey of the Subdivisional Lines,  
T. 39 N., R. 27 E., Gila and Salt River Meridian, Arizona**

CHAINS									
	<table border="1"> <tr> <td>T 39 N</td> <td>R 27 E</td> </tr> <tr> <td>S 29</td> <td>S 28</td> </tr> <tr> <td>S 32</td> <td>S 33</td> </tr> </table>	T 39 N	R 27 E	S 29	S 28	S 32	S 33		
T 39 N	R 27 E								
S 29	S 28								
S 32	S 33								
	2008								
	Deposit a magnet, in a white plastic case, at the base of the stainless steel post.								
	Land, rolling. Soil, sandy clay with sandstone outcrops. Timber, scattered juniper; undergrowth, scattered brush, greasewood, and native grasses.								
	-----								
	From the cor. of secs. 27, 28, 33 and 34.								
	West, bet. secs. 28 and 33.								
	Over rolling and broken land, along the N. slope of a mesa.								
40.00	Point for the 1/4 sec. cor. of secs. 28 and 33.								
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.								
	<table border="1"> <tr> <td>T 39 N</td> <td>R 27 E</td> </tr> <tr> <td></td> <td>S 28</td> </tr> <tr> <td>1/4</td> <td>-----</td> </tr> <tr> <td></td> <td>S 33</td> </tr> </table>	T 39 N	R 27 E		S 28	1/4	-----		S 33
T 39 N	R 27 E								
	S 28								
1/4	-----								
	S 33								
	2008								
	Deposit a magnet, in a white plastic case, at the base of the stainless steel post.								
61.03	NE rim of a mesa, bears S. 5° E. and N. 5° W.								
80.00	The cor. of secs. 28, 29, 32 and 33.								
	Land, rolling and broken. Soil, sandy clay with sandstone outcrops. Timber, scattered juniper; undergrowth, scattered brush, greasewood, and native grasses.								
	-----								
	N. 0°03' W., bet. secs. 28 and 29.								
	Over rolling and broken land.								
24.50	N. rim of a mesa, bears N. 45° E. and S. 45° W, thence descend into a valley.								
40.00	Point for the 1/4 sec. cor. of secs. 28 and 29.								

**Survey of the Subdivisional Lines,  
T. 39 N., R. 27 E., Gila and Salt River Meridian, Arizona**

CHAINS	
	<p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T 39 N R 27 E 1/4 S 29   S 28</p> <p style="text-align: center;">2008</p> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p>
80.00	<p>Point for the cor. of secs. 20, 21, 28 and 29.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T 39 N R 27 E S 20   S 21 S 29   S 28</p> <p style="text-align: center;">2008</p> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p> <p>Land, rolling and broken. Soil, sandy clay with sandstone outcrops. Timber, scattered juniper; undergrowth, scattered brush, greasewood, and native grasses.</p> <hr/> <p>From the cor. of secs. 21, 22, 27 and 28.</p> <p>West, bet. secs. 21 and 28.</p> <p>Over rolling land.</p>
40.00	<p>Point for the 1/4 sec. cor. of secs. 21 and 28.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T 39 N R 27 E S 21 1/4 ——— S 28</p> <p style="text-align: center;">2008</p> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p>

**Survey of the Subdivisional Lines,  
T. 39 N., R. 27 E., Gila and Salt River Meridian, Arizona**

CHAINS	
80.00	<p>The cor. of secs. 20, 21, 28 and 29.</p> <p>Land, rolling. Soil, sandy clay with sandstone outcrops. Timber, scattered juniper; undergrowth, scattered brush, greasewood, and native grasses.</p> <hr/> <p>N. 0°03' W., bet. secs. 20 and 21.</p> <p>Over rolling land.</p>
40.00	<p>Point for the 1/4 sec. cor. of secs. 20 and 21.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T 39 N R 27 E 1/4 S 20   S 21</p> <p style="text-align: center;">2008</p> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p>
47.60	<p>Navajo Route 5043, a graded road, 20 ft. wide, bears N. 30° E. and S. 30° W.</p>
61.04	<p>Power line, bears N. 65° E. and S. 65° W.</p>
80.00	<p>Point for the cor. of secs. 16, 17, 20 and 21.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T 39 N R 27 E S 17   S 16 S 20   S 21</p> <p style="text-align: center;">2008</p> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p> <p>Land, rolling. Soil, sandy clay with sandstone outcrops. Timber, scattered juniper; undergrowth, scattered brush, greasewood and native grasses.</p> <hr/> <p>From the cor. of secs. 15, 16, 21 and 22.</p>

**Survey of the Subdivisional Lines,  
T. 39 N., R. 27 E., Gila and Salt River Meridian, Arizona**

CHAINS	
	West, bet. secs. 16 and 21. Over rolling land.
40.00	Point for the 1/4 sec. cor. of secs. 16 and 21. Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.  <div style="text-align: center;">           T 39 N R 27 E                      S 16            1/4 ———                      S 21             2008         </div>
53.00	Deposit a magnet, in a white plastic case, at the base of the stainless steel post.
53.00	Navajo Route 5043, a graded road, 20 ft. wide, bears N. 30° E. and S. 30° W.
54.67	Power line, bears N. 35° E. and S. 35° W.
80.00	The cor. of secs. 16, 17, 20 and 21. Land, rolling. Soil, sandy clay and sandstone outcrops. Timber, scattered juniper; undergrowth, scattered brush, greasewood, and native grasses.
	-----
	N. 0°03' W., bet. secs. 16 and 17. Over rolling land.
40.00	Point for the 1/4 sec. cor. of secs. 16 and 17. Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.  <div style="text-align: center;">           T 39 N R 27 E                      1/4            S 17   S 16             2008         </div>
	Deposit a magnet, in a white plastic case, at the base of the stainless steel post.
58.35	Trail road, bears S. 70° E. and N. 70° W.
69.95	Power line, bears S. 45° E. and N. 45° W.

**Survey of the Subdivisional Lines,  
T. 39 N., R. 27 E., Gila and Salt River Meridian, Arizona**

CHAINS																	
70.70	Underground water line, bears S. 45° E. and N. 45° W.																
79.80	Trail road, bears S. 70° E. and N. 70° W.																
80.00	Point for the cor. of secs. 8, 9, 16 and 17.  Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.																
	<table style="margin: auto;"> <tr> <td colspan="2">T 39 N</td> <td colspan="2">R 27 E</td> </tr> <tr> <td style="border-right: 1px solid black;">S 8</td> <td style="border-right: 1px solid black;"></td> <td style="border-right: 1px solid black;">S 9</td> <td></td> </tr> <tr> <td style="border-right: 1px solid black;">S 17</td> <td style="border-right: 1px solid black;"></td> <td style="border-right: 1px solid black;">S 16</td> <td></td> </tr> </table>	T 39 N		R 27 E		S 8		S 9		S 17		S 16					
T 39 N		R 27 E															
S 8		S 9															
S 17		S 16															
	2008																
	Deposit a magnet, in a white plastic case, at the base of the stainless steel post.																
	Land, rolling. Soil, sandy clay with sandstone outcrops. Timber, scattered juniper; undergrowth, scattered brush, greasewood and native grasses.																
	From the cor. of secs. 9, 10, 15 and 16.																
	West, bet. secs. 9 and 16.																
	Over rolling and broken land.																
40.00	Point for the 1/4 sec. cor. of secs. 9 and 16.  Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.																
	<table style="margin: auto;"> <tr> <td colspan="2">T 39 N</td> <td colspan="2">R 27 E</td> </tr> <tr> <td colspan="2"></td> <td colspan="2" style="text-align: center;">S 9</td> </tr> <tr> <td colspan="2"></td> <td colspan="2" style="text-align: center;">1/4 ———</td> </tr> <tr> <td colspan="2"></td> <td colspan="2" style="text-align: center;">S 16</td> </tr> </table>	T 39 N		R 27 E				S 9				1/4 ———				S 16	
T 39 N		R 27 E															
		S 9															
		1/4 ———															
		S 16															
	2008																
	Deposit a magnet, in a white plastic case, at the base of the stainless steel post.																
40.99	Barbed wire fence, 4 strand, bears N. 60° E. and S. 60° W.																
45.60	N. bank of Walker Creek wash, 8 ft. high, bears S. 50° E and N. 50° W.																
50.10	Walker Creek wash, 40 ft. wide, 5 ft. deep, drains North.																
80.00	The cor. of secs. 8, 9, 16 and 17.																

**Survey of the Subdivisional Lines,  
T. 39 N., R. 27 E., Gila and Salt River Meridian, Arizona**

CHAINS	
	<p>Land, rolling and broken. Soil, sandy clay and sandstone outcrops. Timber, scattered salt cedar and cottonwood, along the wash; undergrowth, scattered brush, and native grasses.</p> <hr/> <p>N. 0°03' W., bet. secs. 8 and 9.</p> <p>Over rolling and broken land.</p>
15.50	S. rim of Walker Creek canyon, 150 ft. high, bears S. 35° E. and N. 35° W.
35.10	N. rim of Walker Creek canyon, 150 ft. high, bears S. 75° E. and N. 75° W.
40.00	<p>Point for the 1/4 sec. cor. of secs. 8 and 9.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center;"> <p>T 39 N R 27 E 1/4 S 8   S 9</p> <p>2008</p> </div> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p>
43.55	Trail road, bears S. 60° E. and N. 60° W.
80.00	<p>Point for the cor. of secs. 4, 5, 8 and 9.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center;"> <p>T 39 N R 27 E S 5   S 4 S 8   S 9</p> <p>2008</p> </div> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p>

**Survey of the Subdivisional Lines,  
T. 39 N., R. 27 E., Gila and Salt River Meridian, Arizona**

CHAINS	
	<p>Land, rolling and broken. Soil, sandy clay with sandstone outcrops. Timber, scattered juniper; undergrowth, scattered brush, greasewood and native grasses.</p> <hr/> <p>From the cor. of secs. 3, 4, 9 and 10.</p> <p>West, bet. secs. 4 and 9.</p> <p>Over rugged and broken land, ascend the SE slope of a mesa.</p>
0.70	SE rim of a mesa, bears N. 15° E. and S. 15° W., thence over rolling land.
28.40	W. rim of a mesa, bears N. 25° E. and S. 25° W., thence descend into a valley.
40.00	<p>Point for the 1/4 sec. cor. of secs. 4 and 9.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center;"> <p>T 39 N R 27 E</p> <p>S 4</p> <p>1/4 ———</p> <p>S 9</p> <p>2008</p> </div> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p>
80.00	<p>The cor. of secs. 4, 5, 8 and 9.</p> <p>Land, rugged and broken. Soil, sandy clay with sandstone outcrops. Timber, scattered juniper; undergrowth, scattered brush, greasewood and native grasses.</p> <hr/> <p>N. 0°03' W., bet. secs. 4 and 5.</p> <p>Over rolling and broken land.</p>
39.00	Wash, 50 ft. wide, 10 ft. deep, drains S. 60° W.
40.00	<p>Point for the 1/4 sec. cor. of secs. 4 and 5.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p>



**Survey of the Subdivisional Lines,  
T. 39 N., R. 27 E., Gila and Salt River Meridian, Arizona**

CHAINS

T 39 N R 27 E  
1/4  
S 5 | S 4

2008

Deposit a magnet, in a white plastic case, at the base of the stainless steel post.

58.30 S. rim of a mesa, bears N. 55° E. and S. 55° W., thence ascend the S. slope of the mesa.

76.00 S. rim of a mesa, bears N. 45° E. and S. 45° W.

77.83 Point for the closing cor. of secs. 4 and 5, at the intersection with the S. bdy. of sec. 34, T. 40 N., R. 27 E.

Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.

T 40 N R 27 E  
S 34

S 5 | S 4  
T 39 N R 27 E  
CC  
2008

Deposit a magnet, in a white plastic case, at the base of the stainless steel post.

From this cor. point, the 1/4 sec. cor. of sec. 34 only, T. 40 N., R. 27 E., bears East, 39.47 chs. dist., monumented with a stainless steel post, 2 1/2 ins. diam., firmly set, projecting 4 ins. above ground, with brass cap mkd. T40N R27E 1/4 S34 2000.

Add the marks T39N R27E 2008 to the brass cap.

From this same cor. point, the cor. of secs. 33 and 34 only, T. 40 N., R. 27 E., bears West, 0.53 chs. dist., monumented with a stainless steel post, 2 1/2 ins. diam., firmly set, projecting 4 ins. above ground, with brass cap mkd. T40N R27E S33 S34 2000.

Add the marks S4 T39N R27E 2008 to the brass cap.

Land, rolling and broken.

Soil, sandy clay with sandstone outcrops.

Timber, scattered juniper; undergrowth, scattered brush, greasewood, and native grasses.

---

Point for the 1/4 sec. cor. of sec. 4 only, at midpoint on the N. bdy. of sec. 4.

**Survey of the Subdivisional Lines,  
T. 39 N., R. 27 E., Gila and Salt River Meridian, Arizona**

CHAINS	
	<p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T 40 N R 27 E</p> <p style="text-align: center;">——— 1/4 S 4 T 39 N R 27 E</p> <p style="text-align: center;">2008</p> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p> <p>From this cor. point, the cor. of secs. 34 and 35 only, T. 40 N., R. 27 E., bears East, 39.47 chs. dist.</p> <p>From this same cor. point, the 1/4 sec. cor. of sec. 34 only, T. 40 N., R. 27 E., bears West, 0.53 chs. dist.</p> <hr/> <p>From the cor. of secs. 5, 6, 31 and 32, on the S. bdy. of the Tp., hereinbefore described.</p> <p>N. 0°03' W., bet. secs. 31 and 32.</p> <p>Over rolling land.</p>
21.60	Navajo Route 5040, a graded road, 45 ft. wide, bears S. 85° E. and N. 85° W.
40.00	<p>Point for the 1/4 sec. cor. of secs. 31 and 32.</p> <p>Set a brass tablet, 3 1/4 ins. diam., 2 1/2 ins. stem, cemented in place, in a drill hole, in sandstone bedrock, with top mkd.</p> <p style="text-align: center;">T 39 N R 27 E 1/4 S 31   S 32</p> <p style="text-align: center;">2008</p> <p>Deposit a magnet, in a white plastic case, in the drill hole, beneath the brass tablet.</p>
80.00	<p>Point for the cor. of secs. 29, 30, 31 and 32.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p>

**Survey of the Subdivisional Lines,  
T. 39 N., R. 27 E., Gila and Salt River Meridian, Arizona**

CHAINS	T 39 N R 27 E S 30   S 29 S 31   S 32
	2008
	Deposit a magnet, in a white plastic case, at the base of the stainless steel post.
	Land, rolling. Soil, sandy clay with sandstone outcrops. Timber, scattered juniper; undergrowth, scattered brush, greasewood and native grasses.
	From the cor. of secs. 28, 29, 32 and 33.
	West, bet. secs. 29 and 32.
	Over rolling and broken land.
40.00	Point for the 1/4 sec. cor. of secs. 29 and 32.
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.
	T 39 N R 27 E S 29 1/4 ——— S 32
	2008
	Deposit a magnet, in a white plastic case, at the base of the stainless steel post.
46.30	W. rim of a mesa, bears S. 5° E. and N. 5° W., thence descend into a valley.
68.60	Navajo Route 5043, a graded road, 30 ft. wide, bears N. 20° E. and S. 20° W.
80.00	The cor. of secs. 29, 30, 31 and 32.
	Land, rolling and broken. Soil, sandy clay and sandstone outcrops. Timber, scattered juniper; undergrowth, scattered brush, greasewood and native grasses.
	West, bet. secs. 30 and 31.
	Over rolling land.

**Survey of the Subdivisional Lines,  
T. 39 N., R. 27 E., Gila and Salt River Meridian, Arizona**

CHAINS	
40.00	<p>Point for the 1/4 sec. cor. of secs. 30 and 31.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T 39 N R 27 E S 30 1/4 ——— S 31</p> <p style="text-align: center;">2008</p> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p>
78.84	<p>The cor. of secs. 25, 30, 31 and 36, on the W. bdy. of the Tp., hereinbefore described.</p> <p>Land, rolling. Soil, sandy clay with sandstone outcrops. Timber, scattered juniper; undergrowth, scattered brush, and native grasses.</p> <hr/> <p>From the cor. of secs. 29, 30, 31 and 32.</p> <p>N. 0°03' W., bet. secs. 29 and 30.</p> <p>Over rolling land.</p>
40.00	<p>Point for the 1/4 sec. cor. of secs. 29 and 30.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 20 ins. in sandstone bedrock, in a mound of stone, 4 ft. base, to top, with brass cap mkd.</p> <p style="text-align: center;">T 39 N R 27 E 1/4 S 30   S 29</p> <p style="text-align: center;">2008</p> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p>
75.10	S. rim of a canyon, 100 ft. high, bears N. 75° E. and S. 75° W.
75.80	Wash, 200 ft. wide, 100 ft. deep, drains S. 60° W.
78.80	N. rim of a canyon, 100 ft. high, bears N. 60° E. and S. 60° W.
80.00	Point for the cor. of secs. 19, 20, 29 and 30.

**Survey of the Subdivisional Lines,  
T. 39 N., R. 27 E., Gila and Salt River Meridian, Arizona**

CHAINS	
	<p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 18 ins. in sandstone bedrock, in a mound of stone, 4 ft. base, to top, with brass cap mkd.</p> <p style="text-align: center;">T 39 N   R 27 E S 19       S 20 ----- S 30       S 29</p> <p style="text-align: center;">2008</p> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p> <p>Land, rolling. Soil, sandy clay with sandstone outcrops. Timber, scattered juniper; undergrowth, scattered brush, and native grasses.</p> <hr/> <p>From the cor. of secs. 20, 21, 28 and 29.</p> <p>West, bet. secs. 20 and 29.</p> <p>Over rolling land.</p>
37.25	<p>Navajo Route 5043, a graded road, 30 ft. wide, bears N. 15° E. and S. 15° W.</p>
40.00	<p>Point for the 1/4 sec. cor. of secs. 20 and 29.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T 39 N   R 27 E           S 20           1/4 ———           S 29</p> <p style="text-align: center;">2008</p> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p>
80.00	<p>The cor. of secs. 19, 20, 29 and 30.</p> <p>Land, rolling. Soil, sandy clay with sandstone outcrops. Timber, scattered juniper; undergrowth, scattered brush, and native grasses.</p> <hr/> <p>West, bet. secs. 19 and 30.</p>

**Survey of the Subdivisional Lines,  
T. 39 N., R. 27 E., Gila and Salt River Meridian, Arizona**

CHAINS	
	Over rolling land.
40.00	Point for the 1/4 sec. cor. of secs. 19 and 30.  Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.  <div style="text-align: center;">           T 39 N R 27 E                      S 19                  1/4 ———                      S 30             2008         </div>
	Deposit a magnet, in a white plastic case, at the base of the stainless steel post.
40.50	Wash, 4 ft. wide, 3 ft. deep, drains N. 10° E.
78.75	The cor. of secs. 19, 24, 25 and 30, on the W. bdy. of the Tp., hereinbefore described.  Land, rolling. Soil, sandy clay with sandstone outcrops. Timber, scattered juniper; undergrowth, scattered brush, and native grasses.
	From the cor. of secs. 19, 20, 29 and 30.  N. 0°03' W., bet. secs. 19 and 20.  Over rolling land.
40.00	Point for the 1/4 sec. cor. of secs. 19 and 20.  Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.  <div style="text-align: center;">           T 39 N R 27 E                      1/4                  S 19   S 20             2008         </div>
	Deposit a magnet, in a white plastic case, at the base of the stainless steel post.
80.00	Point for the cor. of secs. 17, 18, 19 and 20.  Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.

**Survey of the Subdivisional Lines,  
T. 39 N., R. 27 E., Gila and Salt River Meridian, Arizona**

CHAINS									
	<table border="1"> <tr> <td>T 39 N</td> <td>R 27 E</td> </tr> <tr> <td>S 18</td> <td>S 17</td> </tr> <tr> <td>S 19</td> <td>S 20</td> </tr> </table>	T 39 N	R 27 E	S 18	S 17	S 19	S 20		
T 39 N	R 27 E								
S 18	S 17								
S 19	S 20								
	2008								
	Deposit a magnet, in a white plastic case, at the base of the stainless steel post.								
	Land, rolling. Soil, sandy clay with sandstone outcrops. Timber, scattered juniper; undergrowth, scattered brush, and native grasses.								
	<hr/>								
	From the cor. of secs. 16, 17, 20 and 21.								
	West, bet. secs. 17 and 20.								
	Over rolling land.								
38.10	Canyon, 400 ft. wide, 150 ft. deep, wash in the bottom drains N. 20° E.								
40.00	Point for the 1/4 sec. cor. of secs. 17 and 20.								
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.								
	<table border="1"> <tr> <td>T 39 N</td> <td>R 27 E</td> </tr> <tr> <td></td> <td>S 17</td> </tr> <tr> <td>1/4</td> <td>—</td> </tr> <tr> <td></td> <td>S 20</td> </tr> </table>	T 39 N	R 27 E		S 17	1/4	—		S 20
T 39 N	R 27 E								
	S 17								
1/4	—								
	S 20								
	2008								
	Deposit a magnet, in a white plastic case, at the base of the stainless steel post.								
80.00	The cor. of secs. 17, 18, 19 and 20.								
	Land, rolling. Soil, sandy clay with sandstone outcrops. Timber, scattered juniper; undergrowth, scattered brush, and native grasses.								
	<hr/>								
	West, bet. secs. 18 and 19.								
	Over rolling land.								
40.00	Point for the 1/4 sec. cor. of secs. 18 and 19.								

**Survey of the Subdivisional Lines,  
T. 39 N., R. 27 E., Gila and Salt River Meridian, Arizona**

CHAINS	
	<p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T 39 N R 27 E S 18 1/4 ——— S 19</p> <p style="text-align: center;">2008</p> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p>
78.66	<p>The cor. of secs. 13, 18, 19 and 24, on the W. bdy. of the Tp., hereinbefore described.</p> <p>Land, rolling. Soil, sandy clay with sandstone outcrops. Timber, scattered juniper; undergrowth, scattered brush, greasewood and native grasses.</p> <hr/> <p>From the cor. of secs. 17, 18, 19 and 20. N. 0°03' W., bet secs. 17 and 18. Over rolling land.</p>
40.00	<p>Point for the 1/4 sec. cor. of secs. 17 and 18.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T 39 N R 27 E 1/4 S 18   S 17</p> <p style="text-align: center;">2008</p> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p>
80.00	<p>Point for the cor. of secs. 7, 8, 17 and 18.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T 39 N R 27 E S 7   S 8 S 18   S 17</p> <p style="text-align: center;">2008</p>



**Survey of the Subdivisional Lines,  
T. 39 N., R. 27 E., Gila and Salt River Meridian, Arizona**

CHAINS	
	<p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p> <p>Land, rolling. Soil, sandy clay with sandstone outcrops. Timber, scattered juniper; undergrowth, scattered brush, greasewood, and native grasses.</p> <hr/> <p>From the cor. of secs. 8, 9, 16 and 17.</p> <p>West, bet. secs. 8 and 17.</p> <p>Over rolling land.</p>
9.15	Trail road, bears S. 45° E. and N. 45° W.
9.46	Power line, bears S. 45° E. and N. 45° W.
23.15	Trail road, bears S. 20° E. and N. 20° W.
34.50	Wash, 40 ft. wide, 20 ft. deep, drains N. 15° W.
40.00	Point for the 1/4 sec. cor. of secs. 8 and 17.
	<p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T 39 N R 27 E S 8 1/4 ——— S 17</p> <p style="text-align: center;">2008</p>
80.00	<p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p> <p>The cor. of secs. 7, 8, 17 and 18.</p> <p>Land, rolling. Soil, sandy clay with sandstone outcrops. Timber, scattered juniper; undergrowth, scattered brush, greasewood, and native grasses.</p> <hr/> <p>West, bet. secs. 7 and 18.</p> <p>Over rolling land.</p>
40.00	<p>Point for the 1/4 sec. cor. of secs. 7 and 18.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p>

**Survey of the Subdivisional Lines,  
T. 39 N., R. 27 E., Gila and Salt River Meridian, Arizona**

CHAINS	
	T 39 N R 27 E S 7 1/4 ——— S 18  2008
	Deposit a magnet, in a white plastic case, at the base of the stainless steel post.
78.57	The cor. of secs. 7, 12, 13 and 18, on the W. bdy. of the Tp., hereinbefore described.  Land, rolling. Soil, sandy clay with sandstone outcrops. Timber, scattered juniper; undergrowth, scattered brush, and native grasses.
	<hr/> From the cor. of secs. 7, 8, 17 and 18.  N. 0°03' W., bet. secs. 7 and 8.  Over rolling land.
16.45	Trail road, bears S. 60° E. and N. 60° W.
40.00	Point for the 1/4 sec. cor. of secs. 7 and 8.  Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.
	T 39 N R 27 E 1/4 S 7   S 8  2008
	Deposit a magnet, in a white plastic case, at the base of the stainless steel post.
49.90	Walker Creek wash, 40 ft. wide, 8 ft. deep, drains N. 55° W.
80.00	Point for the cor. of secs. 5, 6, 7 and 8.  Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.
	T 39 N R 27 E S 6   S 5 S 7   S 8  2008

**Survey of the Subdivisional Lines,  
T. 39 N., R. 27 E., Gila and Salt River Meridian, Arizona**

CHAINS	
	<p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p> <p>Land, rolling. Soil, sandy clay with sandstone outcrops. Timber, scattered juniper; undergrowth, scattered brush, greasewood, and native grasses.</p> <hr/> <p>From the cor. of secs. 4, 5, 8 and 9.</p> <p>West, bet. secs. 5 and 8.</p> <p>Over rolling land.</p>
40.00	<p>Point for the 1/4 sec. cor. of secs. 5 and 8.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center;"> <p>T 39 N R 27 E</p> <p>S 5</p> <p>1/4 ———</p> <p>S 8</p> <p>2008</p> </div>
80.00	<p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p> <p>The cor. of secs. 5, 6, 7 and 8.</p> <p>Land, rolling. Soil, sandy clay with sandstone outcrops. Timber, scattered juniper; undergrowth, scattered brush, greasewood and native grasses.</p> <hr/> <p>West, bet. secs. 6 and 7.</p> <p>Over rolling land.</p>
24.90	<p>Walker Creek wash, 50 ft. wide, 10 ft. deep, drains N. 25° W.</p>
40.00	<p>Point for the 1/4 sec. cor. of secs. 6 and 7.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p>

**Survey of the Subdivisional Lines,  
T. 39 N., R. 27 E., Gila and Salt River Meridian, Arizona**

CHAINS	
78.48	<p style="text-align: center;">T 39 N R 27 E S 6 1/4 ——— S 7</p> <p style="text-align: center;">2008</p> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p> <p>The cor. of secs. 1, 6, 7 and 12, on the W. bdy. of the Tp., hereinbefore described.</p> <p>Land, rolling. Soil, sandy clay with sandstone outcrops. Timber, scattered juniper; undergrowth, scattered brush, greasewood, and native grasses.</p> <hr/> <p>From the cor. of secs. 5, 6, 7 and 8.</p> <p>N. 0°03' W., bet. secs. 5 and 6.</p> <p>Over rolling land.</p>
40.00	<p>Point for the 1/4 sec. cor. of secs. 5 and 6.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T 39 N R 27 E 1/4 S 6   S 5</p> <p style="text-align: center;">2008</p> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p>
77.83	<p>Point for the closing cor. of secs. 5 and 6, at intersection with the S. bdy. of sec. 33, T. 40 N., R. 27 E.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T 40 N R 27 E S 33 ————— S 6   S 5 T 39 N R 27 E CC 2008</p>

**Survey of the Subdivisional Lines,  
T. 39 N., R. 27 E., Gila and Salt River Meridian, Arizona**

CHAINS

Deposit a magnet, in a white plastic case, at the base of the stainless steel post.

From this cor. point, the 1/4 sec. cor. of sec. 33 only, T. 40 N., R. 27 E., bears East, 39.46 chs. dist., monumented with a stainless steel post, 2 1/2 ins. diam., firmly set, projecting 4 ins. above ground, with brass cap mkd. T40N R27E 1/4 S33 2000.

Add the marks T39N R27E 2008 to the brass cap.

From this same cor. point, the cor. of secs. 32 and 33 only, T. 40 N., R. 27 E., bears West, 0.54 chs. dist., monumented with a stainless steel post, 2 1/2 ins. diam., firmly set, projecting 4 ins. above ground, with brass cap mkd. T40N R27E S32 S33 2000.

Add the marks S6 T39N R27E 2008 to the brass cap.

Land, rolling.

Soil, sandy clay with sandstone outcrops.

Timber, scattered juniper; undergrowth, scattered brush, greasewood, and native grasses.

Point for the 1/4 sec. cor. of sec. 5 only, at midpoint on the N. bdy. of sec. 5.

Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.

T 40 N R 27 E

—  
1/4 S 5

T 39 N R 27 E

2008

Deposit a magnet, in a white plastic case, at the base of the stainless steel post.

From this cor. point, the cor. of secs. 33 and 34 only, T. 40 N., R. 27 E., bears East, 39.465 chs. dist.

From this same cor. point, the 1/4 sec. cor. of sec. 33 only, T. 40 N., R. 27 E., bears West, 0.535 chs. dist.

Point for the 1/4 sec. cor. of sec. 6 only, T. 39 N., R. 27 E., at 40.00 chs. in westing from the closing cor. of secs. 5 and 6, on the N. bdy. of sec. 6.

Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.

**Survey of the Subdivisional Lines,  
T. 39 N., R. 27 E., Gila and Salt River Meridian, Arizona**

CHAINS

T 40 N R 27 E

---

1/4 S 6

T 39 N R 27 E

2008

Deposit a magnet, in a white plastic case, at the base of the stainless steel post.

From this cor. point, the cor. of secs. 32 and 33 only, T. 40 N., R. 27 E., bears East, 39.46 chs. dist.

From this same cor. point, the 1/4 sec. cor. of sec. 32 only, T. 40 N., R. 27 E., bears West, 0.54 chs. dist., hereinbefore described.

---

**T. 39 N., R. 27 E., Gila and Salt River Meridian, Arizona**

CHAINS

## GENERAL DESCRIPTION

---

The area surveyed is within the Navajo Indian Reservation, near the communities of Totacon and Rock Point, Arizona. The terrain varies from rolling throughout most of the township to broken in the SW portion. The drainage is NW with Alcove Canyon wash and Toh Chin Lini Canyon wash converging into Walker Creek wash; the principal drainage.

The elevation varies from 5200 to 6200 feet above sea level. The soil is mostly sandy clay with some gravelly areas and sandstone outcrops. The timber consists of scattered juniper and scattered salt cedar and Russian olive along the washes. Other vegetation principally consists of scattered brush, greasewood and native grasses.

Principal access to the township is provided by Navajo Route 5043, a graded road, which enters the township in section 1 and ends in section 32. Navajo Routes 5040 and 5037 and Apache County Road C537, all graded roads, provide additional access. There are trail roads scattered throughout most of the township. Much of the area is used for grazing livestock. There is no current mining activity in the township.

The mean magnetic declination of 11° E. was derived from the United States Geological Survey computer program GEOMAG, utilizing the World Magnetic Model for Epoch 2005 for the dates of survey.

---





## CERTIFICATE OF SURVEY

I, Alvina A. Begaye, Cadastral Surveyor, HEREBY CERTIFY upon honor, that in pursuance of special instructions bearing date of the 14th day of July, 2008, I have surveyed the south, east and west boundaries, and the subdivisional lines, T. 39 N., R. 27 E., of the Gila and Salt River Meridian, in the State of Arizona, which are represented in the foregoing field notes as having been executed by me and under my direction. Said survey has been made in strict conformity with said special instructions, the Manual of Instructions for the Survey of the Public Lands of the United States, 1973, and in specific manner described in the foregoing field notes.

July 27, 2009  
(Date)

Alvina A. Begaye  
(Cadastral Surveyor)

## CERTIFICATE OF APPROVAL

BUREAU OF LAND MANAGEMENT  
Phoenix, Arizona

The foregoing field notes of the survey of the south, east and west boundaries, and the subdivisional lines, T. 39 N., R. 27 E., Gila and Salt River Meridian, in the State of Arizona, executed by Alvina A. Begaye, Cadastral Surveyor, having been critically examined and found correct, are hereby approved.

8/6/2009  
(Date)

Stephen K. Hansen  
(Chief Cadastral Surveyor of Arizona)

~~CERTIFICATE OF TRANSCRIPT~~

~~I CERTIFY That the foregoing transcript of the field notes of the above described surveys in T. 39 N., R. 27 E., Gila and Salt River Meridian, Arizona, is a true copy of the original field notes.~~

~~\_\_\_\_\_  
(Date)~~

~~\_\_\_\_\_  
(Chief Cadastral Surveyor of Arizona)~~