

ORIGINAL

**UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT**

FIELD NOTES
OF THE
DEPENDENT RESURVEY OF
A PORTION OF THE WEST BOUNDARY OF THE SAN CARLOS INDIAN RESERVATION
A PORTION OF THE GILA AND SALT RIVER BASE LINE
THROUGH RANGE 16 EAST (NORTH BOUNDARY)
A PORTION OF THE SOUTH BOUNDARY
AND
THE SURVEY OF
THE SOUTH AND EAST BOUNDARIES;
AND SUBDIVISIONAL LINES (WITHIN THE SAN CARLOS INDIAN RESERVATION)
TOWNSHIP 1 SOUTH, RANGE 16 EAST,
OF THE GILA AND SALT RIVER MERIDIAN,
IN THE STATE OF ARIZONA.

EXECUTED BY

W. William Foster, Cadastral Surveyor

Under Special Instructions dated May 21, 2001, approved May 21, 2001, which provided for the surveys included under Group No. 873, and assignment instructions dated May 21, 2001.

Survey commenced May 21, 2001

Survey completed July 31, 2001

INDEX DIAGRAM

TOWNSHIP 1 SOUTH RANGE 16 EAST
 GILA AND SALT RIVER MERIDIAN

		11		13		14		15		
6	5	4	60	61	3	50	2	39	40	28
7	8	9	58	59	10	48	11	37	38	27
18	17	16	56	57	15	46	14	35	36	26
19	20	21	55	55	22	44	23	33	34	25
30	29	28	53	54	27	42	26	31	32	24
31	32	33	51	52	34	40	35	30	31	22
	16	21	19	18	17					

Dependent Resurvey of a Portion of the W. Bdy. of the
 San Carlos Indian Reservation Pgs. 5-11

T. 1 S., R. 16 E., Gila and Salt River Meridian, Arizona

CHAINS

The following field notes describe the dependent resurvey of a portion of the west boundary of the San Carlos Indian Reservation, a portion of the Gila and Salt River Base Line through Range 16 East (north boundary) and a portion of the south boundary and the survey of the south and east boundaries and subdivisional lines (within the San Carlos Indian Reservation), Township 1 South, Range 16 East, Gila and Salt River Meridian, Arizona.

The history of surveys pertaining to this survey is as follows:

John C. Smith, U.S. Deputy Surveyor, surveyed the west boundary of the White Mountain Indian Reservation (San Carlos Indian Reservation), in 1890.

Roscoe C. Ham, U.S. Deputy Surveyor, surveyed the Gila and Salt River Base Line through Townships 1 North, Ranges 15 1/2 and 16 East, and established the closing corner on the west boundary of the White Mountain Indian Reservation (San Carlos Indian Reservation), in 1910.

Sydney E. Blout, U.S. Surveyor, established the closing corner of Townships 1 South, Ranges 15 and 16 East, on the Base Line, in the course of his survey of the east boundary of Township 1 South, Range 15 East, in 1914.

Walter G. Turley, Forest Service Surveyor, retraced a portion of the west boundary of the White Mountain Indian Reservation (San Carlos Indian Reservation) from the 68 mile corner to the 69 mile corner, while surveying Homestead Entry Survey No. 118, in 1914.

H.L. Baldwin, Topographer, surveyed the Gila and Salt River Base Line through Ranges 16, 17 and 18 East, within the White Mountain Indian Reservation (San Carlos Indian Reservation), in 1915.

William B. Kimmel, U.S. Cadastral Engineer, and Roger F. Wilson, U.S. Transitman, surveyed a portion of the south boundary of Township 1 South, Range 16 East, and retraced a portion of the west boundary of the White Mountain Indian Reservation (San Carlos Indian Reservation) from the 70 1/2 mile corner to the 76 1/2 mile corner, in 1923.

Thomas F. Myers, Chief Surveyor, U.S. Forest Service, retraced a portion of the west boundary of the White Mountain Indian Reservation (San Carlos Indian Reservation) from the standard closing corner on the Gila and Salt River Base Line to the 65 mile corner, while surveying Exchange Survey No. 653, in 1927.

T. 1 S., R. 16 E., Gila and Salt River Meridian, Arizona

CHAINS

Paul L. Reeves, Cadastral Surveyor, dependently resurveyed the west boundary of the San Carlos Indian Reservation, between the 64 mile corner and the 67 mile corner and conducted a metes-and-bounds survey of Tract 38, adjacent to and west of the reservation boundary, in unsurveyed Township 1 South, Range 16 East, in 1982.

H.L. Baldwin, Topographer, established the corner of Townships 2 and 3 South, Ranges 17 and 18 East, in the course of his survey of the west and north boundaries of Township 3 South, Range 18 East, in 1915.

Roger F. Wilson, U.S. Transitman, established the closing corner of sections 13 and 18, Townships 3 South, Ranges 16 and 17 East, in the course of his survey of a portion of the west boundary of Township 3 South, Range 17 East, in 1924.

The survey was executed in accordance with the specifications as set forth in the Manual of Instructions for the Survey of the Public Lands of the United States, 1973, and the Special Instructions dated May 21, 2001, for Group Number 873, Arizona.

The true meridian direction and length of all lines were determined by real time kinematic global positioning system observations using Trimble Navigation 4700 model receivers.

Preliminary to the resurvey and survey, the lines of the prior surveys were retraced and search was made for all corners and other calls of record. Identified corners were remonumented in their original positions. Lost corners were reestablished and remonumented at proportionate positions based on the official record. The retracement data were thoroughly verified and only the true line field notes are given herein.

Geodetic control was derived from first order United States Coast and Geodetic Survey triangulation station CUTTER RESET 1973, as published by the National Geodetic Survey, NAD 83 (1992). The geographic position of the corner of Townships 1 and 2 South, Ranges 16 and 17 East, is as follows:


Latitude: 33°17'42.00" N. Longitude: 110°39'20.85" W.

The mean magnetic declination is 11 1/2° E.

**Dependent Resurvey of a Portion of the West Boundary
of the San Carlos Indian Reservation,
T. 1 S., R. 16 E., Gila and Salt River Meridian, Arizona**

CHAINS	
	<p>Restoring the survey executed by Paul L. Reeves, in 1982</p> <hr/>
	<p>Beginning at the 64 1/2 mile cor., monumented with an aluminum rod, 3/4 in. diam., firmly set, projecting 4 ins. above the ground, with aluminum cap mkd. T1N SCIR R16E 64 1/2 M S31 1982.</p> <p>Cor. is located 10 lks. E. of a barbed wire fence, bears N. 8 1/4° E. and S. 8 1/4° W.</p> <p>Add the marks 2001 to the aluminum cap.</p> <p>From this cor. point, the 64 mile cor., bears N. 8°22' E., 39.95 chs. dist., monumented with an aluminum rod, 3/4 in. diam., firmly set, projecting 4 ins. above the ground, with aluminum cap mkd. T1N SCIR R16E 64M S31 1982. Cor. is located in a barbed wire fence, bears N. 8 1/4° E. and S. 8 1/4° W. Add the marks 2001 to the aluminum cap.</p> <p>S. 8°22' W., on the 65th mile of the San Carlos Indian Reservation.</p> <p>Over rolling land, through medium oak brush, crucifixion thorn, mesquite, yucca, cacti, and scattered juniper.</p>
2.48	Point for the closing cor. of sec. 31, on the Gila and Salt River Base Line at intersection with the W. bdy. of the San Carlos Indian Reservation, hereinafter described.
39.95	<p>The 65 mile cor., monumented with a stainless steel post, 2 1/2 ins. diam., firmly set, projecting 13 ins. above the ground, with brass cap mkd. PL SCIR 65M 1982.</p> <p>Add the marks 2001 to the brass cap.</p> <hr/> <p>S. 8°24' W., on the 66th mile of the San Carlos Indian Reservation.</p> <p>Over rolling land, through medium oak brush, crucifixion thorn, mesquite, yucca, cacti, and scattered juniper.</p>
24.02	Center of railroad tracks, bears S. 35° E. and N. 35° W., tracks begin curving to NW.
24.28	Point for the closing cor. of secs. 4 and 9, hereinafter described.
28.93	N. edge of pavement of U.S. Highway No. 70, bears S. 70° E. and N. 70° W.



**Dependent Resurvey of a Portion of the West Boundary
of the San Carlos Indian Reservation,
T. 1 S., R. 16 E., Gila and Salt River Meridian, Arizona**

CHAINS	
29.51	S. edge of pavement of U.S. Highway No. 70, bears S. 70° E. and N. 70° W.
30.73	S. right-of-way fence of U.S. Highway No. 70, bears S. 70° E. and N. 70° W.
30.805	<p>Point for Cor. 1, Tract 38, at proportionate dist., falls in the remains of a mound of stone, there is no remaining evidence of the aluminum rod.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 25 ins. in the ground, in a collar of stone, with brass cap mkd.</p> <p style="text-align: center;">T 1 S R 16 E</p>  <p style="text-align: center;">2001</p> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p>
40.12	True point for the 65 1/2 mile cor., at proportionate dist., falls in a wash where it is impracticable to establish a permanent monument.
41.625	<p>The witness cor. to the 65 1/2 mile cor., monumented with an iron post, 2 1/2 ins. diam., firmly set, projecting 6 ins. above the ground, with brass cap mkd. WC SCIR 65 1/2 M 1982.</p> <p>A mound of stone, 2 ft. base, 1 ft. high, is E. of cor.</p> <p>Add the marks 2001 to the brass cap.</p> <hr style="width: 20%; margin: 10px auto;"/> <p>S. 8°17' W., beginning new measurement.</p> <p>Over rolling land, through medium oak brush, crucifixion thorn, mesquite, yucca, cacti, and scattered juniper.</p>
38.72	<p>The 66 mile cor., monumented with an aluminum rod, 3/4 in. diam., firmly set, projecting 6 ins. above the ground, in a mound of stone, 3 1/2 ft. base, to top of aluminum cap mkd. SCIR 66M 1982.</p> <p>Add the marks 2001 to the aluminum cap.</p> <p>Cor. is located on the S. edge of a small wash, 3 ft. wide, drains northeasterly.</p> <hr style="width: 20%; margin: 10px auto;"/>

**Dependent Resurvey of a Portion of the West Boundary
of the San Carlos Indian Reservation,
T. 1 S., R. 16 E., Gila and Salt River Meridian, Arizona**

CHAINS	
	<p>S. 8°16' W., on the 67th mile of the San Carlos Indian Reservation.</p> <p>Over rolling land, through medium oak brush, crucifixion thorn, mesquite, yucca, cacti, and scattered juniper.</p>
24.735	Point for the closing cor. of secs. 9 and 16, hereinafter described.
27.735	<p>Cor. No. 3, Tract 38, monumented with an aluminum rod, 3/4 in. diam., firmly set, projecting 3 ins. above the ground, with aluminum cap mkd. T1S R16E SCIR COR3 TR38 1982.</p> <p>Add the marks 2001 to the aluminum cap.</p> <p>Cor. is located 12 lks. E. of a barbed wire fence, bears N. 8 1/4° E. and S. 8 1/4° W.</p> <hr style="width: 20%; margin: 10px auto;"/>
	S. 8°16' W., beginning new measurement.
12.485	<p>The 66 1/2 mile cor., monumented with an iron post, 2 1/2 ins. diam., firmly set, projecting 8 ins. above the ground, with brass cap mkd. PL SCIR 66 1/2 M 1982.</p> <p>Add the marks 2001 to the aluminum cap.</p> <hr style="width: 20%; margin: 10px auto;"/>
	S. 8°16' W., beginning new measurement.
40.225	<p>The 67 mile cor., monumented with an iron post, 2 1/2 ins. diam., firmly set, projecting 5 ins. above the ground, with brass cap mkd. PL SCIR 67M 1982.</p> <p>Add the marks 2001 to the aluminum cap.</p> <p>A mound of stone, 2 ft. base, 1 ft. high, is E. of cor.</p> <hr style="width: 20%; margin: 10px auto;"/> <p style="text-align: center;">Restoring the survey executed by John C. Smith, in 1890</p> <hr style="width: 20%; margin: 10px auto;"/>
	<p>S. 8°19' W., on the 68th mile of the San Carlos Indian Reservation.</p> <p>Over rolling land, through medium oak brush, crucifixion thorn, mesquite, yucca, cacti, and scattered juniper.</p>
25.08	Point for the closing cor. of secs. 16 and 21, hereinafter described.

**Dependent Resurvey of a Portion of the West Boundary
of the San Carlos Indian Reservation,
T. 1 S., R. 16 E., Gila and Salt River Meridian, Arizona**

CHAINS	
37.50	Wash, 20 ft. wide, 1 ft. deep, drains S. 75° E.
40.095	<p>Point for the 67 1/2 mile cor., at proportionate dist., there is no remaining evidence of the orig. cor.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 22 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T 1 S R 16 E</p> <div style="text-align: center;">  </div> <p style="text-align: center;">2001</p> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p> <p>Cor. is located 11 lks. E. of a barbed wire fence, bears N. 8 1/4° E. and S. 8 1/4° W., on nearly level land, in the flood plain between washes N. and S. of cor.</p>
44.50	Wash, 5 ft. wide, 2 ft. deep, drains N. 65° E.
80.19	<p>Point for the 68 mile cor., at proportionate dist., the orig. granite stone, 14 x 10 x 8 ins., mkd. WMIR 68M WB, was found hanging as a deadman in a nearby fence.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T 1 S R 16 E</p> <div style="text-align: center;">  </div> <p style="text-align: center;">2001</p> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p> <p>Bury stone alongside stainless steel post.</p> <hr style="width: 20%; margin: 10px auto;"/> <p>S. 8°19' W., on the 69th mile of the San Carlos Indian Reservation.</p> <p>Over rolling land, through medium oak brush, crucifixion thorn, mesquite, yucca, cacti, and scattered juniper.</p>

**Dependent Resurvey of a Portion of the West Boundary
of the San Carlos Indian Reservation,
T. 1 S., R. 16 E., Gila and Salt River Meridian, Arizona**

CHAINS	
10.16	Point for the closing cor. of secs. 20 and 21, hereinafter described.
25.685	Point for the closing cor. of secs. 20 and 29, hereinafter described.
40.095	<p>Point for the 68 1/2 mile cor., at proportionate dist., there is no remaining evidence of the orig. cor., falls in a washed out area, where it is impracticable to establish a permanent monument.</p> <p>from which</p> <p style="padding-left: 40px;">A stainless steel post, 28 ins. long, 2 1/2 ins. diam., set 24 ins. in the ground for a reference monument, bears N. 49°25' E., 63.7 ft. dist. with brass cap mkd. RM T1S R16E SCIR 68 1/2 M 63.7 FT TO COR 2001 and an arrow pointing to the cor. Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p> <p style="padding-left: 40px;">A stainless steel post, 28 ins. long, 2 1/2 ins. diam., set 24 ins. in the ground for a reference monument, bears S. 45°27' E., 47.1 ft. dist. with brass cap mkd. RM T1S R16E SCIR 68 1/2 M 47.1 FT TO COR 2001 and an arrow pointing to the cor. Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p>
80.19	<p>The 69 mile cor., monumented with a granite stone, 17 x 14 x 4 ins., loosely set, projecting 4 ins. above the ground, mkd. WMIR WB 69M on E. face.</p> <p>At the corner point</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 16 ins. in the ground to bedrock, in a mound of stone, 3 ft. base, to top, with brass cap mkd.</p> <div style="text-align: center; margin: 20px 0;"> <p>T 1 S R 16 E</p> <p style="margin-left: 100px;">/</p> <p style="margin-left: 100px;">SCIR</p> <p style="margin-left: 100px;">69 M</p> <p style="margin-left: 100px;"> </p> <p style="margin-left: 100px;">2001</p> </div> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p> <p>Bury stone alongside stainless steel post.</p> <hr style="width: 30%; margin-left: auto; margin-right: auto;"/>


**Dependent Resurvey of a Portion of the West Boundary
of the San Carlos Indian Reservation,
T. 1 S., R. 16 E., Gila and Salt River Meridian, Arizona**

CHAINS	
	<p>S. 8°20' W., on the 70th mile of the San Carlos Indian Reservation.</p> <p>Over rolling land, through medium oak brush, crucifixion thorn, mesquite, yucca, cacti, and scattered juniper.</p>
26.29	Point for the closing cor. of secs. 29 and 32, hereinafter described.
39.98	<p>Point for the 69 1/2 mile cor., at proportionate dist., there is no remaining evidence of the orig. cor.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 22 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center;"> <p>T 1 S R 16 E</p> <p>PL / SCIR</p> <p>69 1/2 M</p> <p>S 32</p> <p>2001</p> </div> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p> <p>Cor. is located in dense manzanita and creosote bush.</p> <p>Build a mound of stone E. of cor.</p>
79.96	<p>Point for the 70 mile cor., at proportionate dist., there is no remaining evidence of the orig. cor., falls in a washed out area, where it is impracticable to establish a permanent monument.</p> <p>from which</p> <p style="padding-left: 40px;">A granite boulder, 3 x 2 x 1 ft. above the ground, bears N. 74°54' E., 39 lks. dist., mkd. X BO on the SW face.</p> <p style="padding-left: 40px;">A stainless steel post, 28 ins. long, 2 1/2 ins. diam., set 18 ins. in the ground, in a mound of stone, 4 ft., base, to top, for a reference monument, bears N. 39°14' W., 34.2 ft. dist. with brass cap mkd. RM T1S R16E S32 34.2 FT TO COR 2001 and an arrow pointing to the cor. Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p> <hr style="width: 20%; margin: 20px auto;"/> <p>S. 8°20' W., on the 71st mile of the San Carlos Indian Reservation.</p>

**Dependent Resurvey of a Portion of the West Boundary
of the San Carlos Indian Reservation,
T. 1 S., R. 16 E., Gila and Salt River Meridian, Arizona**

CHAINS	
	Over rolling land, through medium oak brush, crucifixion thorn, mesquite, yucca, cacti, and scattered juniper.
27.13	Point for the closing cor. of secs. 5 and 32, Tps. 1 and 2 S., R. 16 E., hereinafter described.
39.98	The 70 1/2 mile cor., monumented with a sandstone, 14 x 12 ins., firmly set, projecting 8 ins. above the ground, mkd. WMIR 70 1/2 M on E. face. Cor. is located 4 lks. W. of a barbed wire fence, bears N. 8 1/4° E. and S. 8 1/4° W. From this cor. point, the 71 mile cor., bears S. 8°15' W., 39.37 chs. dist., monumented with a sandstone, 14 x 10 ins., firmly set, projecting 11 ins. above the ground, mkd. WMIR WB 71 M. A scattered mound of stone is located W. of the cor. Cor. is located 3 lks. W. of a barbed wire fence, bears N. 8 1/4° E. and S. 8 1/4° W.
<hr/> <p>Dependent Resurvey of a Portion of the Gila and Salt River Base Line Through Range 16 East (North Boundary), T. 1 S., R. 16 E., Gila and Salt River Meridian, Arizona</p> <hr/>	
<p>Restoring the survey executed by Roscoe C. Ham, in 1910</p> <hr/>	
	From the Stan. cor. of Tps. 1 N., Rs. 15 1/2 and 16 E., monumented with a granite stone, 8 x 5 ins., firmly set, projecting 10 ins. above the ground, mkd. SC1N with 6 grooves on N. face, 16 E with 6 grooves on E. face and 15 1/2 E with 6 grooves on W. face.
	Not remonumented.
	East, on the Gila and Salt River Base Line.
	Over rolling land through scrub brush and scattered Palo Verde trees.
28.16	The 1910 closing cor. of sec. 31, a stone, 7 x 6 ins., firmly set, projecting 4 ins. above the ground, mkd. T1N on N. face, WMIR WB on the E. face and CCR16E on the W. face. From this cor. point, an iron post, 3 ins. diam., firmly set, projecting 16 ins. above the ground, in a collar of stone, with brass cap mkd. SC T1N R16E R16E CC S31 S34 PL WMIR WB 1982 1915, bears North, 1 lk. dist.

Dependent Resurvey of a Portion of the Gila and Salt River
Base Line Through Range 16 East (North Boundary),
T. 1 S., R. 16 E., Gila and Salt River Meridian, Arizona

CHAINS	
	<p>Add the marks AM to the 1910 stone and 1915 iron post and bury both in place.</p> <p>28.21 Point for the closing cor. of sec. 31, on the Gila and Salt River Base Line at intersection with the W. bdy. of the San Carlos Indian Reservation.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T 1 N R 16 E</p> <div style="text-align: center;">  </div> <p style="text-align: center;">2001</p> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p> <p>From this cor. point, the 64 1/2 mile cor. on the W. bdy. of the San Carlos Indian Reservation, bears N. 8°22' E., 2.48 chs. dist., hereinbefore described.</p> <p>From this same cor. point, a rebar, firmly set, projecting 3 ins. above the ground, with a washer attached and stamped LS 14169, bears N. 13° E., 1 lk. dist.</p> <p>Cor. is located 9 lks. E. of a barbed fence, bears N. 8 1/4° E. and S. 8 1/4° W.</p> <p style="text-align: center;"> <hr/> Restoring the survey executed by H. L. Baldwin, in 1915 <hr/> </p> <p>S. 89°57' E., beginning new measurement.</p>
11.76	<p>The stan. 1/4 sec. cor. of sec. 31, T. 1 N., R. 16 E., monumented with a rusted iron post, 1 in. diam., broken off flush with the ground, with the top portion lying alongside, with brass cap mkd. SC 1/4 S31 1915. A mound of stone is N. of cor.</p> <p>At the corner point</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p>

Dependent Resurvey of a Portion of the Gila and Salt River
Base Line Through Range 16 East (North Boundary),
T. 1 S., R. 16 E., Gila and Salt River Meridian, Arizona

CHAINS	
	SC T 1 N R 16 E 1/4 S 31 <hr style="width: 10%; margin: auto;"/> 2001
	Deposit a magnet, in a white plastic case, at the base of the stainless steel post. Bury iron post alongside stainless steel post. Rebuild mound of stone, 3 ft. base, 1 1/2 ft. high, N. of cor. <hr style="width: 20%; margin: auto;"/> N. 89°58' E., beginning new measurement.
26.25	Point for the closing cor. of secs. 3 and 4, hereinafter described.
40.00	The stan. cor. of secs. 31 and 32, monumented with an iron post, 3 ins. diam., firmly set, 4 ins. below the surface of the ground, with brass cap mkd. SC T1N R16E S31 S32 1915. Add the marks 2001 to the brass cap. <hr style="width: 60%; margin: auto;"/> N. 89°58' E., on the Gila and Salt River Base Line. Over rolling land through scrub brush and scattered Palo Verde trees.
26.28	Point for the 1/4 sec. cor. of sec. 3 only, hereinafter described.
40.03	The stan. 1/4 sec. cor. of sec. 32, T. 1 N., R. 16 E., monumented with a iron post, 1 in. diam., firmly set, 4 ins. below the surface of the ground, with brass cap mkd. SC 1/4 S32 1915, from which the remains of the orig. bearing trees A palo verde stump, 12 ins. diam., 2 ft. high, bears N. 39 3/4° E., 1.54 chs. dist., with scribe marks 1/4 S32 visible on partially open blaze. <hr style="width: 20%; margin: auto;"/> N. 89°58' E., beginning new measurement.
24.60	Wash, 35 ft. wide, 2 ft. deep, drains S. 5° E.
26.28	Point for the closing cor. of secs. 2 and 3, hereinafter described.

**Dependent Resurvey of a Portion of the Gila and Salt River
Base Line Through Range 16 East (North Boundary),
T. 1 S., R. 16 E., Gila and Salt River Meridian, Arizona**

CHAINS	
26.70	Wash, 15 ft. wide, 1 ft. deep, drains S. 20° W.
40.05	The stan. cor. of secs. 32 and 33, monumented with an iron post, 3 ins. diam., firmly set, 12 ins. below the surface of the ground, with brass cap mkd. SC T1N R16E S32 S33 1915.
	Add the marks 2001 to the brass cap.
	<hr/> East, on the Gila and Salt River Base Line.
	Over rolling land through scrub brush and scattered Palo Verde trees.
5.55	Graded road, 12 ft. wide, bears S. 25° E. and N. 25° W.
24.20	Wash, 4 ft. wide, 1/2 ft. deep, drains S. 15° W.
26.19	Point for the 1/4 sec. cor. of sec. 2 only, hereinafter described.
26.60	Ridge, bears N. 15° E. and S. 40° W.
40.04	The stan. 1/4 sec. cor. of sec. 33, T. 1 N., R. 16 E., monumented with a iron post, 1 in. diam., firmly set, projecting 12 ins. above the ground, with brass cap mkd. SC 1/4 S33 1915.
	Add the marks T1N R16E T1S 2001 to the brass cap.
	<hr/> N. 89°56' E., beginning new measurement.
26.11	Point for the closing cor. of secs. 1 and 2, hereinafter described.
40.045	Point for the stan. cor. of secs. 33 and 34, at proportionate dist., the 1915 iron post, 36 ins. long, 3 ins. diam., with brass cap mkd. SC T1N R16E S33 S34 1915 was found lying on the ground nearby and there is no remaining evidence of the mound of stone set N. of the cor.
	At the corner point
	Reset the 1915 iron post, 36 ins. long, 3 ins. diam., 24 ins. in the ground, in a mound of stone, 3 ft. base, to top, with brass cap mkd.

Dependent Resurvey of a Portion of the Gila and Salt River
Base Line Through Range 16 East (North Boundary),
T. 1 S., R. 16 E., Gila and Salt River Meridian, Arizona

CHAINS	
	SC T 1 N R 16 E S 33 S 34 <hr style="width: 10%; margin: auto;"/> 2001 1915 <hr style="width: 80%; margin: 10px auto;"/>
	N. 89°56' E., on the Gila and Salt River Base Line.
	Over rolling land through scrub brush and scattered Palo Verde trees.
26.095	Point for the 1/4 sec. cor. of sec. 1 only, hereinafter described.
40.045	The stan. 1/4 sec. cor. of sec. 34, T. 1 N., R. 16 E., monumented with a iron post, 1 in. diam., firmly set, projecting 16 ins. above the ground, in a mound of stone, 3 ft. base, to top, with brass cap mkd. SC 1/4 S34 1915.
	Add the marks 2001 to the brass cap.
	S. 89°55' E., beginning new measurement.
26.08	Point for the closing cor. of secs. 1 and 6, on the E. bdy. of the Tp., hereinafter described.
40.045	The stan. cor. of secs. 34 and 35, monumented with an iron post, 3 ins. diam., firmly set, projecting 16 ins. above the ground, with brass cap mkd. SC T1N R16E S34 S35 1915, from which the remains of the orig. bearing trees
	A palo verde, 11 ins. diam., bears N. 20° E., 20 lks. dist., with scribe marks BT and other illegible marks visible on partially open blaze.
	A stump hole, bears N. 75 3/4° W., 28 lks. dist., with a dead and downed palo verde alongside, 12 ins. diam., with scribe marks BT and other illegible marks visible on partially open blaze.

**Dependent Resurvey of a Portion of the Gila and Salt River
Base Line Through Range 16 East (North Boundary),
T. 1 S., R. 16 E., Gila and Salt River Meridian, Arizona**

CHAINS

Add the marks 2001 to the brass cap.

**Dependent Resurvey of a Portion of the South Boundary,
T. 1 S., R. 16 E., Gila and Salt River Meridian, Arizona**

Restoring the survey executed by
William B. Kimmel and Roger F. Wilson, in 1923

From the 1/4 sec. cor. of secs. 5 and 32, on the S. bdy. of the Tp., monumented with an iron post, 1 in. diam., firmly set, projecting 19 ins. above the ground, with brass cap mkd. 1/4 S32 S5 1923.

S. 89°48' E., bet. secs. 5 and 32.

5.415 Point for the closing cor. of secs. 5 and 32, on the S. bdy. of the Tp., at intersection with the W. bdy. of the San Carlos Indian Reservation.

Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 16 ins. in the ground to bedrock, in a mound of stone, 2 1/2 ft. base, to top, with brass cap mkd.

T 1 S R 16 E
C S 32 / SCIR
C S 5 / T 2 S

2001

Deposit a magnet, in a white plastic case, at the base of the stainless steel post.

From this cor. point, the 1923 closing cor., bears S. 89°48' E., 2 1/2 lks. dist., monumented with an iron post, 3 ins. diam., firmly set, projecting 12 ins. above the ground, with brass cap mkd. T1S R16E S32 WMIR CC S5 T2S 1923, with a mound of stone to the W. of cor. Add the marks AM to the brass cap and bury iron post in place and incorporate the mound of stone around the stainless steel post.

From this same cor. point, the 70 1/2 mile cor. on the W. bdy. of the San Carlos Indian Reservation, bears S. 8°20' W., 12.85 chs. dist., hereinbefore described.

**Dependent Resurvey of a Portion of the South Boundary,
T. 1 S., R. 16 E., Gila and Salt River Meridian, Arizona**

CHAINS

Cor. is located 1 1/2 lks. E. of a barbed fence, bears N. 8 1/4° E. and S. 8 1/4° W.

**Survey of the South Boundary
(Within the San Carlos Indian Reservation),
T. 1 S., R. 16 E., Gila and Salt River Meridian, Arizona**

From the point for the cor. of Tps. 1 and 2 S., Rs. 16 and 17 E., determined at a point geodetically north of the closing cor. of secs. 13 and 18, T. 3 S., Rs. 16 and 17 E., on the S. bdy. of the San Carlos Indian Reservation; and at protracted dist. (720 chs. dist.) from the cor. of secs. 13, 18, 19 and 24, T. 3 S., Rgs. 16 and 17 E.

Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 16 ins. in the ground, in a mound of stone, 2 1/2 ft. base, to top, with brass cap mkd.

	T 1 S	
R 16 E		R 17 E
S 36		S 31
S 1		S 6
	T 2 S	

2001

Deposit a magnet, in a white plastic case, at the base of the stainless steel post.

From this cor. point, the closing cor. of secs. 13 and 18, T. 3 S., Rs. 16 and 17 E., on the S. bdy. of the San Carlos Indian Reservation, bears South, 690.38 chs. dist., monumented with an iron post, 3 ins. diam., firmly set, projecting 6 ins. above a mound of stone, 3 ft. base, 1 ft. high, with brass cap mkd. WMIRASB S13 S18 R16E R17E T3S CC 1924.

From this same cor. point, the cor. of secs. 13, 18, 19 and 24, T. 3 S., Rgs. 16 and 17 E., bears South, 720.00 chs. dist., monumented with an iron post, 2 ins. diam., firmly set, projecting 24 ins. above the ground, in a supporting mound of stone, 3 ft. base, 1 1/2 ft. high, with brass cap mkd. T3S R16E R17E S13 S18 S24 S19 1924.

N. 89°45' W., bet. secs. 1 and 36.

Over rolling land through scrub brush and scattered timber.

40.00

Point for the 1/4 sec. cor. of secs. 1 and 36.

**Survey of the South Boundary
(Within the San Carlos Indian Reservation),
T. 1 S., R. 16 E., Gila and Salt River Meridian, Arizona**

CHAINS	
	<p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T 1 S R 16 E S 36 1/4 ——— S 1 T 2 S</p> <p style="text-align: center;">2001</p> <p>from which</p> <p style="padding-left: 40px;">A pine, 11 ins. diam., bears S. 54 1/2° E., 68 lks. dist., mkd. 1/4 S1 BT.</p> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p> <p>Cor. is located on steep N. facing slope.</p>
78.90	Wash, 10 ft. wide, 1 ft. deep, drains S. 52° W.
80.00	Point for the cor. of secs. 1, 2, 35 and 36.
	<p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 12 ins. in the ground to bedrock, in a mound of stone, 3 ft. base, to top, with brass cap mkd.</p> <p style="text-align: center;">T 1 S R 16 E S 35 S 36 S 2 S 1 T 2 S</p> <p style="text-align: center;">2001</p> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p> <p>Cor. is located on a gradual S. facing slope.</p> <p>Land, rolling. Soil, sandy loam. Timber, scattered; undergrowth, scrub brush.</p> <hr style="width: 60%; margin-left: 0;"/> <p>N. 89°45' W., bet. secs. 2 and 35.</p> <p>Over gradual descent through scrub brush and timber.</p>
21.70	Wash, 15 ft. wide, 1 ft. deep, drains N. 40° W.

**Survey of the South Boundary
(Within the San Carlos Indian Reservation),
T. 1 S., R. 16 E., Gila and Salt River Meridian, Arizona**

CHAINS							
40.00	<p>Point for the 1/4 sec. cor. of secs. 2 and 35.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 14 ins. in the ground, in a mound of stone, 3 ft. base, to top, with brass cap mkd.</p> <div style="text-align: center;"> <p>T 1 S R 16 E</p> <p>S 35</p> <p>1/4 ———</p> <p>S 2</p> <p>T 2 S</p> <p>2001</p> </div> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p> <p>Cor. is located on a steep W. facing slope.</p>						
44.30	Wash, 145 ft. wide, 1 1/2 ft. deep, drains N.						
72.95	Graded road on top of a ridge, 15 ft. wide, bears N. 45° E. and S. 45° W.						
80.00	<p>Point for the cor. of secs. 2, 3, 34 and 35.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 18 ins. in the ground to bedrock, in a mound of stone, 2 1/2 ft. base, to top, with brass cap mkd.</p> <div style="text-align: center;"> <p>T 1 S R 16 E</p> <table style="margin: auto; border-collapse: collapse;"> <tr> <td style="border-right: 1px solid black; padding: 0 5px;">S 34</td> <td style="padding: 0 5px;">S 35</td> </tr> <tr> <td style="border-right: 1px solid black; padding: 0 5px;">S 3</td> <td style="padding: 0 5px;">S 2</td> </tr> <tr> <td colspan="2" style="text-align: center;">T 2 S</td> </tr> </table> <p>2001</p> </div> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p> <p>Cor. is located on a steep W. facing slope.</p> <p>Land, rolling. Soil, sandy loam. Timber, scattered; undergrowth, scrub brush.</p> <hr style="width: 60%; margin-left: 0;"/> <p>N. 89°45' W., bet. secs. 3 and 34.</p>	S 34	S 35	S 3	S 2	T 2 S	
S 34	S 35						
S 3	S 2						
T 2 S							

Survey of the South Boundary
 (Within the San Carlos Indian Reservation),
 T. 1 S., R. 16 E., Gila and Salt River Meridian, Arizona

CHAINS					
40.00	<p>Along steep N. facing slope through scrub brush and scattered timber.</p> <p>Point for the 1/4 sec. cor. of secs. 3 and 34.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 10 ins. in the ground to bedrock, in a supporting mound of stone, 3 ft. base, to top, with brass cap mkd.</p> <div style="text-align: center; margin: 10px 0;"> <p>T 1 S R 16 E</p> <p>S 34</p> <p>1/4 ———</p> <p>S 3</p> <p>T 2 S</p> <p>2001</p> </div> <p>from which</p> <p style="margin-left: 40px;">A pine, 17 ins. diam., bears S. 12 1/2° E., 56 lks. dist., mkd. 1/4 S3 BT.</p> <p style="margin-left: 40px;">A pine, 11 ins. diam., bears N. 40° W., 8.5 lks. dist., mkd. 1/4 S34 BT.</p> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p> <p>Cor. is located on a steep N. facing slope.</p>				
80.00	<p>Point for the cor. of secs. 3, 4, 33 and 34.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 18 ins. in the ground to bedrock, in a mound of stone, 3 ft. base, to top, with brass cap mkd.</p> <div style="text-align: center; margin: 10px 0;"> <p>T 1 S R 16 E</p> <table style="margin: auto; border-collapse: collapse;"> <tr> <td style="border-right: 1px solid black; padding: 0 5px;">S 33</td> <td style="padding: 0 5px;">S 34</td> </tr> <tr> <td style="border-right: 1px solid black; padding: 0 5px;">S 4</td> <td style="padding: 0 5px;">S 3</td> </tr> </table> <p>T 2 S</p> <p>2001</p> </div> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p> <p>Cor. is located on a steep N. facing slope.</p>	S 33	S 34	S 4	S 3
S 33	S 34				
S 4	S 3				

Survey of the South Boundary
(Within the San Carlos Indian Reservation),
T. 1 S., R. 16 E., Gila and Salt River Meridian, Arizona

CHAINS	
	<p>Land, rolling. Soil, sandy loam. Timber, scattered; undergrowth, scrub brush.</p> <hr/> <p>N. 89°45' W., bet. secs. 4 and 33.</p> <p>Descend to wash then ascend NE facing slope through scrub brush and scattered timber.</p>
2.00	Wash, 5 ft. wide, 1/2 ft. deep, drains N. 70° E.
15.10	Ridge, bears N. 25° E. and S. 25° W.
29.30	Wash, 12 ft. wide, 1 ft. deep, drains N.
30.25	Graded road, 15 ft. wide, bears N. 20° E. and S. 10° E.
30.50	Barbed wire fence, bears N. and S.
40.00	Point for the 1/4 sec. cor. of secs. 3 and 34, falls on rock surface.
	<p>Set a brass tablet, 3 1/4 ins. diam., 3 1/2 ins. stem, cemented in a drill hole in solid rock, with top mkd.</p> <p style="text-align: center;">T 1 S R 16 E S 33 1/4 ——— S 4 T 2 S</p> <p style="text-align: center;">2001</p> <p>from which</p> <p style="text-align: center;">A boulder, 4 1/2 x 3 1/2 x 3 ft., bears N. 32 1/2° E., 34 lks. dist., mkd. X BO.</p> <p>Deposit a magnet, 1 in. diam., in drill hole beneath brass tablet.</p> <p>Raise a mound of stone, 3 ft. base, 2 ft. high, N. of cor.</p>
80.00	Point for the cor. of secs. 4, 5, 32 and 33.
	<p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 16 ins. in the ground to bedrock, in a mound of stone, 2 1/2 ft. base, to top, with brass cap mkd.</p>

**Survey of the South Boundary
(Within the San Carlos Indian Reservation),
T. 1 S., R. 16 E., Gila and Salt River Meridian, Arizona**

CHAINS									
	<table border="0"> <tr> <td>T 1 S</td> <td>R 16 E</td> </tr> <tr> <td>S 32</td> <td>S 33</td> </tr> <tr> <td>S 5</td> <td>S 4</td> </tr> <tr> <td>T 2 S</td> <td></td> </tr> </table>	T 1 S	R 16 E	S 32	S 33	S 5	S 4	T 2 S	
T 1 S	R 16 E								
S 32	S 33								
S 5	S 4								
T 2 S									
	2001								
	Deposit a magnet, in a white plastic case, at the base of the stainless steel post.								
	Cor. is located on a steep S. facing slope.								
	Land, rolling. Soil, sandy loam. Timber, scattered; undergrowth, scrub brush.								

	N. 89°45' W., bet. secs. 5 and 32.								
	Along S. facing slope through scrub brush and scattered timber.								
25.755	The closing cor. of secs. 5 and 32, on the S. bdy. of the Tp., at intersection with the W. bdy. of the San Carlos Indian Reservation, hereinbefore described.								
	Land, rolling. Soil, sandy loam. Timber, scattered; undergrowth, scrub brush.								

	<p>Survey of the East Boundary, T. 1 S., R. 16 E., Gila and Salt River Meridian, Arizona</p>								
	From the cor. of Tps. 1 and 2 S., Rs. 16 and 17 E., hereinbefore described.								
	North, bet. secs. 31 and 36, on the E. bdy. of the Tp.								
	Over rolling terrain through medium scrub brush, creosote bush and scattered palo verde.								
3.10	Spur, slopes W.								
5.40	Spur, slopes W.								
14.60	Ridge, bears S. 80° E. and N. 80° W.								
31.60	Wash, 100 ft. wide, 1 ft. deep, drains N. 50° W.								
38.60	Wash, 5 ft. wide, 1 ft. deep, drains S. 60° W.								
40.00	Point for the 1/4 sec. cor. of secs. 31 and 36.								

**Survey of the East Boundary,
T. 1 S., R. 16 E., Gila and Salt River Meridian, Arizona**

CHAINS									
	<p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 18 ins. in the ground, in a mound of stone, 2 1/2 ft. base, to top, with brass cap mkd.</p>								
	<table style="margin: auto;"> <tr><td colspan="2">T 1 S</td></tr> <tr><td colspan="2">1/4</td></tr> <tr><td>R 16 E</td><td>R 17 E</td></tr> <tr><td>S 36</td><td>S 31</td></tr> </table>	T 1 S		1/4		R 16 E	R 17 E	S 36	S 31
T 1 S									
1/4									
R 16 E	R 17 E								
S 36	S 31								
	2001								
	from which								
	A pine, 5 ins. diam., bears S. 80 1/2° E., 44 lks. dist., mkd. X at breast height and BT at base.								
	Deposit a magnet, in a white plastic case, at the base of the stainless steel post.								
	Cor. is located 4 1/2 lks. N. of a wash, 1 1/2 ft. wide, 1 ft. deep, drains W.								
50.00	Spur, slopes W.								
67.10	Wash, 10 ft. wide, 1/2 ft. deep, drains W.								
79.40	Ridge, bears S. 60° E. and N. 60° W.								
80.00	Point for the cor. of secs. 25, 30, 31 and 36.								
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.								
	<table style="margin: auto;"> <tr><td colspan="2">T 1 S</td></tr> <tr><td>R 16 E</td><td>R 17 E</td></tr> <tr><td>S 25</td><td>S 30</td></tr> <tr><td>S 36</td><td>S 31</td></tr> </table>	T 1 S		R 16 E	R 17 E	S 25	S 30	S 36	S 31
T 1 S									
R 16 E	R 17 E								
S 25	S 30								
S 36	S 31								
	2001								
	Deposit a magnet, in a white plastic case, at the base of the stainless steel post.								
	Cor. is located on N. face of ridge, bears S. 60° E. and N. 60° W.								
	Land, rolling.								
	Soil, sandy loam.								
	Timber, palo verde; undergrowth, scrub brush and creosote bush.								

Survey of the East Boundary,
T. 1 S., R. 16 E., Gila and Salt River Meridian, Arizona

CHAINS									
	North, bet. secs. 25 and 30.								
	Over rolling terrain through medium scrub brush, creosote bush and scattered palo verde.								
11.20	Wash, 5 ft. wide, 1/2 ft. deep, drains W.								
26.30	Spur, slopes N. 60° W.								
33.70	Wash, 100 ft. wide, 1/2 ft. deep, drains N. 60° W.								
40.00	Point for the 1/4 sec. cor. of secs. 25 and 30.								
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 17 ins. in the ground to bedrock, in a mound of stone, 2 1/2 ft. base, to top, with brass cap mkd.								
	<table style="margin: auto;"> <tr><td colspan="2">T 1 S</td></tr> <tr><td colspan="2">1/4</td></tr> <tr><td>R 16 E</td><td> R 17 E</td></tr> <tr><td>S 25</td><td> S 30</td></tr> </table>	T 1 S		1/4		R 16 E	R 17 E	S 25	S 30
T 1 S									
1/4									
R 16 E	R 17 E								
S 25	S 30								
	2001								
	Deposit a magnet, in a white plastic case, at the base of the stainless steel post.								
40.30	Ridge, bears S. 60° E. and N. 60° W.								
47.40	Wash, 35 ft. wide, 1/2 ft. deep, drains N. 60° W.								
62.90	Ridge, bears S. 60° E. and N. 60° W.								
80.00	Point for the cor. of secs. 19, 24, 25 and 30.								
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, in a collar of stone, with brass cap mkd.								
	<table style="margin: auto;"> <tr><td colspan="2">T 1 S</td></tr> <tr><td>R 16 E</td><td> R 17 E</td></tr> <tr><td>S 24</td><td> S 19</td></tr> <tr><td>S 25</td><td> S 30</td></tr> </table>	T 1 S		R 16 E	R 17 E	S 24	S 19	S 25	S 30
T 1 S									
R 16 E	R 17 E								
S 24	S 19								
S 25	S 30								
	2001								
	Deposit a magnet, in a white plastic case, at the base of the stainless steel post.								

**Survey of the East Boundary,
T. 1 S., R. 16 E., Gila and Salt River Meridian, Arizona**

CHAINS	
	<p>Land, rolling. Soil, sandy loam. Timber, palo verde; undergrowth, scrub brush and creosote bush.</p> <hr/> <p>North, bet. secs. 19 and 24.</p> <p>Across level ground through medium underbrush and scrub mesquite trees.</p>
36.80	Ridge, bears S. 45° E. and N. 45° W.
40.00	<p>Point for the 1/4 sec. cor. of secs. 19 and 24.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 20 ins. in the ground to bedrock, in a mound of stone, 3 ft. base, to top, with brass cap mkd.</p> <div style="text-align: center;"> <p>T 1 S 1/4 R 16 E R 17 E S 24 S 19</p> <p>2001</p> </div> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p>
40.30	Wash, 20 ft. wide, 1/2 ft. deep, drains N. 45° W.
46.50	Ridge, bears S. 45° E. and N. 45° W.
65.10	Wash, 150 ft. wide, 1 ft. deep, drains N. 45° W.
72.20	Ridge, bears S. 45° E. and N. 45° W.
80.00	<p>Point for the cor. of secs. 13, 18, 19 and 24.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center;"> <p>T 1 S R 16 E R 17 E S 13 S 18 <hr/>S 24 S 19</p> <p>2001</p> </div> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p>

**Survey of the East Boundary,
T. 1 S., R. 16 E., Gila and Salt River Meridian, Arizona**

CHAINS	
	<p>Cor. is located on nearly level land with thick mesquite.</p> <p>Land, rolling to level. Soil, sandy loam. Timber, mesquite; undergrowth, scrub brush.</p> <hr/> <p>North, bet. secs. 13 and 18.</p> <p>Over level ground through thick mesquite.</p>
35.80	Right bank of wash, 330 ft. wide, 2 ft. deep, drains N. 50° E.
40.00	Point for the 1/4 sec. cor. of secs. 13 and 18, falls in a wash, 330 ft. wide, where it is impracticable to establish a permanent monument.
	<p>from which</p> <p style="padding-left: 40px;">A stainless steel post, 28 ins. long, 2 1/2 ins. diam., set 24 ins. in the ground for a reference monument, bears S. 72°46' E., 237.2 ft. dist. with brass cap mkd. RM T1S R17E 237.2 FT TO COR S18 2001 and an arrow pointing to the cor. Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p> <p style="padding-left: 40px;">A stainless steel post, 28 ins. long, 2 1/2 ins. diam., set 24 ins. in the ground for a reference monument, bears N. 52°15' W., 144.3 ft. dist. with brass cap mkd. RM T1S R16E 144.3 FT TO COR S13 2001 and an arrow pointing to the cor. Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p>
45.40	Graded road, 15 ft. wide, bears N. 30° E. and S. 30° W.
45.80	Left bank of same wash, 330 ft. wide, 2 ft. deep, drains N. 50° E.
45.79	Barbed wire fence, bears N. 30° E. and S. 30° W.
63.22	Chain link fence, 6 ft. high, along S. side of Globe Municipal Airport, bears S. 80° E. and N. 80° W.
78.88	Chain link fence, 6 ft. high, along N. side of Globe Municipal Airport, bears S. 80° E. and N. 80° W.
78.96	S. right-of-way fence of U.S. Highway No. 70, barbed wire, bears S. 80° E. and N. 80° W.
80.00	<p>Point for the cor. of secs. 7, 12, 13 and 18.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 2 ins. below the surface of the ground, with brass cap mkd.</p>

**Survey of the East Boundary,
T. 1 S., R. 16 E., Gila and Salt River Meridian, Arizona**

CHAINS													
	<table style="margin: auto; border-collapse: collapse;"> <tr> <td></td> <td style="text-align: center;">T 1 S</td> <td></td> </tr> <tr> <td style="text-align: center;">R 16 E</td> <td style="border-left: 1px solid black; border-right: 1px solid black; text-align: center;"> </td> <td style="text-align: center;">R 17 E</td> </tr> <tr> <td style="text-align: center;">S 12</td> <td style="border-left: 1px solid black; border-right: 1px solid black; text-align: center;"> </td> <td style="text-align: center;">S 7</td> </tr> <tr> <td style="text-align: center;">S 13</td> <td style="border-left: 1px solid black; border-right: 1px solid black; text-align: center;"> </td> <td style="text-align: center;">S 18</td> </tr> </table>		T 1 S		R 16 E		R 17 E	S 12		S 7	S 13		S 18
	T 1 S												
R 16 E		R 17 E											
S 12		S 7											
S 13		S 18											
	2001												
	from which												
	A highway right-of-way marker, a piece of railroad track, firmly set, projecting 24 ins. above the ground, bears S. 50°55' W., 1.295 chs. dist., mkd. X.												
	Deposit a magnet, in a white plastic case, at the base of the stainless steel post.												
	Cor. is located on the S. berm of U.S. Highway No. 70.												
	From this cor. point, U.S.C. and G.S. triangulation station CUTTER RESET 1973, bears S. 63°21' E., 4.985 chs. dist., monumented with a concrete monument, 12 ins. sq., firmly set, flush with ground, with brass tablet, 3 ins. diam., mkd. CUTTER 1945 1973.												
	Land, level. Soil, sandy loam. Timber, mesquite; undergrowth, scrub brush.												
	North, bet. secs. 7 and 12.												
	Over broken terrain through dense palo verde and mesquite.												
0.23	S. edge of pavement of U.S. Highway No. 70, bears S. 80° E. and N. 80° W.												
0.79	N. edge of pavement of U.S. Highway No. 70, bears S. 80° E. and N. 80° W.												
2.05	N. right-of-way fence of U.S. Highway No. 70, barbed wire, bears S. 80° E. and N. 80° W.												
8.50	Barbed wire fence, bears S. 80° E. and N. 80° W.												
8.98	Center of railroad tracks, bears S. 80° E. and N. 80° W.												
11.00	Gas pipeline, bears S. 80° E. and N. 80° W.												
19.30	Wash, 60 ft. wide, 1 ft. deep, drains N. 75° E.												
21.00	Graded road, 20 ft. wide, bears S. 80° E. and N. 80° W.												

Survey of the East Boundary,
T. 1 S., R. 16 E., Gila and Salt River Meridian, Arizona

CHAINS	
26.15	Cor. of chain link fences, on top of ridge, bears N. 62° E. and N. 10° W.
31.31	Chain link fence, 5 ft. high, bears N. 60° E. and S. 60° W.
36.50	N. edge of ridge, bears E. and W.
40.00	<p>Point for the 1/4 sec. cor. of secs. 7 and 12.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p>
	<div style="text-align: center;"> <p>T 1 S 1/4 R 16 E R 17 E S 12 S 7</p> <p>2001</p> </div> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p> <p>Cor. is located 40 lks. N. of the top of a ridge, bears E. and W.</p>
43.50	Wash, 320 ft. wide, 1 ft. deep, drains E.
80.00	<p>Point for the cor. of secs. 1, 6, 7 and 12.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 20 ins. in the ground, in a mound of stone, 3 ft. base, to top, with brass cap mkd.</p>
	<div style="text-align: center;"> <p>T 1 S R 16 E R 17 E S 1 S 6 <hr/>S 12 S 7</p> <p>2001</p> </div> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p> <p>Land, level to broken. Soil, sandy loam. Timber, palo verde and mesquite; undergrowth, scrub brush.</p> <hr/> <p>North, bet. secs. 1 and 6.</p>

**Survey of the East Boundary,
T. 1 S., R. 16 E., Gila and Salt River Meridian, Arizona**

CHAINS	
	Over broken terrain through dense palo verde and mesquite.
24.70	Ridge, bears S. 40° E. and N. 40° W.
36.20	Wash, drains S. 40° E.
40.00	Point for the 1/4 sec. cor. of secs. 1 and 6. Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 20 ins. in the ground, in a mound of stone, 3 ft. base, to top, with brass cap mkd.
	T 1 S 1/4 R 16 E R 17 E S 1 S 6 2001
	Deposit a magnet, in a white plastic case, at the base of the stainless steel post.
	Cor. is located on S. slope of a ridge, bears S. 35° E. and N. 35° W.
43.90	Ridge, bears S. 35° E. and N. 35° W.
53.40	Ridge, bears S. 60° E. and N. 60° W.
62.51	Point for the closing cor. of secs. 1 and 6, at intersection with the Gila and Salt River Base Line. Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.
	T 1 N R 16 E C C S 1 S 6 R 16 E R 17 E T 1 S 2001
	Deposit a magnet, in a white plastic case, at the base of the stainless steel post.
	Cor. is located on N. slope of a ridge, bears E. and W.

**Survey of the East Boundary,
T. 1 S., R. 16 E., Gila and Salt River Meridian, Arizona**

CHAINS	
	<p>From this cor. point, the stan. cor. of secs. 34 and 35, T. 1 N., R. 16 E., bears S. 89°55' E., 13.965 chs. dist., hereinbefore described.</p> <p>Land, broken. Soil, sandy loam. Timber, palo verde and mesquite; undergrowth, scrub brush.</p> <hr/> <p align="center">Survey of the Subdivisional Lines, T. 1 S., R. 16 E., Gila and Salt River Meridian, Arizona</p> <hr/> <p>From the cor. of secs. 1, 2, 35 and 36, on the S. bdy. of the Tp. N. 0°01' W., bet. secs. 35 and 36. Over mountainous terrain to rolling and broken.</p>
40.00	<p>Point for the 1/4 sec. cor. of secs. 35 and 36.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 16 ins. in the ground, in a mound of stone, 3 ft. base, to top, with brass cap mkd.</p> <p align="center">T 1 S R 16 E 1/4 S 35 S 36 2001</p>
	<p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p> <p>Cor. is located on a steep N. facing slope.</p>
64.20	<p>Graded road, No. 703, 15 ft. wide, bears E. and W.</p>
80.00	<p>Point for the cor. of secs. 25, 26, 35 and 36.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, in a collar of stone, with brass cap mkd.</p> <p align="center">T 1 S R 16 E S 26 S 25 S 35 S 36 2001</p>

**Survey of the Subdivisional Lines,
T. 1 S., R. 16 E., Gila and Salt River Meridian, Arizona**

CHAINS	
	<p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p> <p>Land, mountainous to rolling. Soil, sandy loam. Timber, scattered; undergrowth, scrub brush.</p> <hr/> <p>From the cor. of secs. 25, 30, 31 and 36, on the E. bdy. of the Tp.</p> <p>N. 89°44' W., bet. secs. 25 and 36.</p> <p>Over broken terrain through scrub oak and mesquite.</p>
35.30	Ridge, bears S. 30° E. and N. 50° W.
38.40	Wash, 10 ft. wide, 1 1/2 ft. deep, drains N. 75° W.
40.00	Point for the 1/4 sec. cor. of secs. 25 and 36.
	<p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p align="center">T 1 S R 16 E S 25 1/4 ——— S 36</p> <p align="center">2001</p>
	<p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p> <p>Cor. is located 25 lks. S. of a wash, 10 ft. wide, 1 1/2 ft. deep, drains N. 75° W.</p>
55.90	Wash, 15 ft. wide, 1/2 ft. deep, drains N. 45° W.
62.00	Ridge, bears S. 45° E. and N. 80° W.
80.00	The cor. of secs. 25, 26, 35 and 36.
	<p>Land, broken. Soil, sandy loam. Timber, scrub oak and mesquite; undergrowth, scrub brush.</p> <hr/> <p>N. 0°01' W., bet. secs. 25 and 26.</p> <p>Over broken to level terrain through scrub oak and mesquite.</p>

**Survey of the Subdivisional Lines,
T. 1 S., R. 16 E., Gila and Salt River Meridian, Arizona**

CHAINS	
0.80	Spur, slopes N. 60° W.
32.30	Wash, 130 ft. wide, 1 ft. deep, drains N. 28° E.
40.00	Point for the 1/4 sec. cor. of secs. 25 and 26. Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd. <div style="text-align: center;"> T 1 S R 16 E 1/4 S 26 S 25 2001 </div> Deposit a magnet, in a white plastic case, at the base of the stainless steel post.
50.53	From this point, a windmill located at Martin Well, 8 ft. sq. base on concrete slab, 30 ft. high, bears East, 2.13 chs. dist.
80.00	Point for the cor. of secs. 23, 24, 25 and 26. Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 25 ins. in the ground, with brass cap mkd. <div style="text-align: center;"> T 1 S R 16 E S 23 S 24 S 26 S 25 2001 </div> Deposit a magnet, in a white plastic case, at the base of the stainless steel post. Cor. is located 70 lks. E. and 1.65 chs. S. of a graded road, 15 ft. wide, bears N. 25° E. and S. 25° W. Land, broken to level. Soil, sandy loam. Timber, scrub oak and mesquite; undergrowth, scrub brush. <hr/>
31.40	From the cor. of secs. 19, 24, 25 and 30, on the E. bdy. of the Tp. N. 89°44' W., bet. secs. 24 and 25. Over broken to level terrain through mesquite. Ridge, bears S. 25° E. and N. 15° W.

**Survey of the Subdivisional Lines,
T. 1 S., R. 16 E., Gila and Salt River Meridian, Arizona**

CHAINS	
40.01	<p>Point for the 1/4 sec. cor. of secs. 24 and 25.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 16 ins. in the ground to bedrock, in a mound of stone, 2 1/2 ft. base, to top, with brass cap mkd.</p> <div style="text-align: center; margin: 10px 0;"> <p>T 1 S R 16 E</p> <p> S 24</p> <p> 1/4 ———</p> <p> S 25</p> </div> <p style="text-align: center; margin: 10px 0;">2001</p> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p> <p>Cor. is located on a steep E. facing slope.</p>
46.30	Ridge, bears S. 10° E. and N. 35° W.
56.90	Wash, 65 ft. wide, 1/2 ft. deep, drains N. 30° W.
63.30	Wash, 130 ft. wide, 1 ft. deep, drains N. 10° E.
80.02	<p>The cor. of secs. 23, 24, 25 and 26.</p> <p>Land, broken to level. Soil, sandy loam. Timber, mesquite; undergrowth, scrub brush.</p> <hr style="border: 0.5px solid black; margin: 10px 0;"/> <p>N. 0°01' W., bet. secs. 23 and 24.</p> <p>Over level terrain through scrub mesquite.</p>
1.65	Graded road, 15 ft. wide, bears N. 25° E. and S. 25° W.
39.65	Graded road, 15 ft. wide, bears E. and W.
40.00	<p>Point for the 1/4 sec. cor. of secs. 23 and 24.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 25 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center; margin: 10px 0;"> <p>T 1 S R 16 E</p> <p> 1/4</p> <p> S 23 S 24</p> </div> <p style="text-align: center; margin: 10px 0;">2001</p>

**Survey of the Subdivisional Lines,
T. 1 S., R. 16 E., Gila and Salt River Meridian, Arizona**

CHAINS									
80.00	<p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p> <p>Cor. is located 4 lks. S. of a barbed wire fence, bears E. and W.</p> <p>Point for the cor. of secs. 13, 14, 23 and 24.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 22 ins. in the ground, in a mound of stone, 2 1/2 ft. base, to top, with brass cap mkd.</p> <div style="text-align: center; margin: 10px 0;"> <table style="margin: auto; border-collapse: collapse;"> <tr> <td colspan="2">T 1 S R 16 E</td> </tr> <tr> <td style="border-right: 1px solid black; padding: 2px 5px;">S 14</td> <td style="padding: 2px 5px;">S 13</td> </tr> <tr> <td style="border-right: 1px solid black; padding: 2px 5px;">S 23</td> <td style="padding: 2px 5px;">S 24</td> </tr> </table> <p>2001</p> </div> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p> <p>Cor. is located on a steep S. facing slope.</p> <p>Land, level. Soil, sandy loam. Timber, mesquite; undergrowth, scrub brush.</p> <hr style="width: 80%; margin: 10px auto;"/> <p>From the cor. of secs. 13, 18, 19 and 24, on the E. bdy. of the Tp.</p> <p>N. 89°44' W., bet. secs. 13 and 24.</p> <p>Over level to broken terrain through scrub mesquite.</p>	T 1 S R 16 E		S 14	S 13	S 23	S 24		
T 1 S R 16 E									
S 14	S 13								
S 23	S 24								
27.70	<p>Wash, 330 ft. wide, 4 ft. deep, drains N. 35° E.</p>								
36.05	<p>Graded road, 20 ft. wide, bears N. 20° E. and S. 20° W.</p>								
40.015	<p>Point for the 1/4 sec. cor. of secs. 13 and 24.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center; margin: 10px 0;"> <table style="margin: auto; border-collapse: collapse;"> <tr> <td colspan="2">T 1 S R 16 E</td> </tr> <tr> <td colspan="2" style="text-align: center;">S 13</td> </tr> <tr> <td style="text-align: center;">1/4</td> <td style="border-top: 1px solid black; width: 50px;"></td> </tr> <tr> <td colspan="2" style="text-align: center;">S 24</td> </tr> </table> <p>2001</p> </div>	T 1 S R 16 E		S 13		1/4		S 24	
T 1 S R 16 E									
S 13									
1/4									
S 24									

**Survey of the Subdivisional Lines,
T. 1 S., R. 16 E., Gila and Salt River Meridian, Arizona**

CHAINS	
	<p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p> <p>Raise a mound of stone, 3 ft. base, 2 ft. high, N. of cor.</p> <p>Cor. is located on level ground in scrub mesquite.</p>
40.85	Barbed wire fence, bears N. 30° E. and S. 30° W.
80.03	<p>The cor. of secs. 13, 14, 23 and 24.</p> <p>Land, broken to level. Soil, sandy loam. Timber, mesquite; undergrowth, scrub brush.</p> <hr/> <p>N. 0°01' W., bet. secs. 13 and 14.</p> <p>Over broken terrain.</p>
0.40	Ridge, bears S. 80° E. and N. 70° W.
6.80	Wash, 30 ft. wide, 1/2 ft. deep, drains S. 60° E.
33.00	Ridge, bears N. 80° E. and W.
38.70	Wash, 5 ft. wide, 1/2 ft. deep, drains N. 70° W.
40.00	<p>Point for the 1/4 sec. cor. of secs. 13 and 14.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 25 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center; margin: 10px 0;"> <p>T 1 S R 16 E</p> <p>1/4</p> <p>S 14 S 13</p> <p>2001</p> </div> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p> <p>Cor. is located on S. facing slope.</p>
40.40	Ridge, bears N. 50° E. and S. 50° W.
78.10	Chain link fence, 6 ft. high, along S. side of Globe Municipal Airport, bears S. 80° E. and N. 80° W.
80.00	Point for the cor. of secs. 11, 12, 13 and 14, falls in a wash, 100 ft. wide, 1 ft. deep, drains SE, where it is impracticable to establish a permanent monument.

**Survey of the Subdivisional Lines,
T. 1 S., R. 16 E., Gila and Salt River Meridian, Arizona**

CHAINS	
	<p>from which</p> <p>A stainless steel post, 28 ins. long, 2 1/2 ins. diam., set 24 ins. in the ground for a reference monument, bears S. 28°18' E., 113.1 ft. dist. with brass cap mkd. RM T1S R16E S13 113.1 FT TO COR 2001 and an arrow pointing to the cor. Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p> <p>A stainless steel post, 28 ins. long, 2 1/2 ins. diam., set 24 ins. in the ground for a reference monument, bears S. 88°37' W., 49.0 ft. dist. with brass cap mkd. RM T1S R16E S14 49.0 FT TO COR 2001 and an arrow pointing to the cor. Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p> <p>Land, broken. Soil, sandy loam. Undergrowth, scrub brush.</p> <hr/> <p>From the cor. of secs. 7, 12, 13 and 18, on the E. bdy. of the Tp. N. 89°44' W., bet. secs. 12 and 13. Over level terrain.</p>
5.14	Chain link fence, 6 ft. high, along N. side of Globe Municipal Airport, bears S. 80° E. and N. 80° W.
22.18	Southeast cor. of asphalt airplane tie down area.
29.07	Airport taxiway, asphalt surface, 32 ft. wide, bears S. 70° E. and N. 70° W.
40.02	Point for the 1/4 sec. cor. of secs. 12 and 13. Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 25 ins. in the ground, with brass cap mkd.
	<p>T 1 S R 16 E S 12 1/4 ——— S 13</p> <p>2001</p>
	Deposit a magnet, in a white plastic case, at the base of the stainless steel post.

**Survey of the Subdivisional Lines,
T. 1 S., R. 16 E., Gila and Salt River Meridian, Arizona**

CHAINS	
	Cor. is located bet. the Globe Municipal Airport runway and taxiway.
51.61	Center line of airport runway, asphalt surface, 100 ft. wide, bears S. 80° E. and N. 80° W.
79.00	Wash, 100 ft. wide, 1 ft. deep, drains S. 55° E.
80.04	The cor. of secs. 11, 12, 13 and 14. Land, level. Soil, sandy loam. Undergrowth, scrub brush.

	N. 0°01' W., bet. secs. 11 and 12. Over level terrain.
0.80	Wash, 100 ft. wide, 1 ft. deep, drains S. 55° E.
5.83	Center line of airport runway, asphalt surface, 100 ft. wide, bears S. 80° E. and N. 80° W.
10.47	Airport taxiway, asphalt surface, 32 ft. wide, bears S. 70° E. and N. 70° W.
16.45	Chain link fence, 6 ft. high, along N. side of Globe Municipal Airport, bears S. 80° E. and N. 80° W.
16.70	Gas pipeline, bears E. and W.
17.20	S. right-of-way fence of U.S. Highway No. 70, barbed wire, bears S. 78° E. and N. 78° W.
18.29	S. edge of pavement of U.S. Highway No. 70, bears S. 78° E. and N. 78° W.
18.84	N. edge of pavement of U.S. Highway No. 70, bears S. 78° E. and N. 78° W.
19.29	N. right-of-way fence of U.S. Highway No. 70, barbed wire, bears S. 83° E. and N. 83° W.
20.07	Center of railroad tracks, bears S. 81° E. and N. 81° W.
22.44	Gas line, bears E. and W., thence enter golf course on S. edge of driving range and across fairway of 18th hole.
40.00	Point for the 1/4 sec. cor. of secs. 11 and 12. Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., flush with the surface of the ground, with brass cap mkd.

Survey of the Subdivisional Lines,
T. 1 S., R. 16 E., Gila and Salt River Meridian, Arizona

CHAINS	
	<p style="text-align: center;">T 1 S R 16 E 1/4 S 11 S 12 2001</p> <p>from which</p> <p style="padding-left: 40px;">A concrete slab, bears N. 79 1/2° E., 68 lks. dist., mkd. with a chiseled X.</p> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p> <p>Cor. is located on the N. edge of the 18th fairway of a golf course.</p>
51.95	S. edge of putting green for the 16th hole of a golf course.
77.10	N. edge of the 8th fairway of a golf course, bears S. 40° E. and N. 80° W.
80.00	Point for the cor. of secs. 1, 2, 11 and 12.
	<p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 23 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T 1 S R 16 E S 2 S 1 S 11 S 12 2001</p> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p> <p>Land, level. Soil, sandy loam. Undergrowth, scrub brush.</p> <hr/> <p>From the cor. of secs. 1, 6, 7 and 12, on the E. bdy. of the Tp. N. 89°44' W., bet. secs. 1 and 12.</p> <p>Over broken terrain through scrub mesquite.</p>
39.30	Wash, 7 ft. wide, 1 ft. deep, drains S.
40.02	Point for the 1/4 sec. cor. of secs. 1 and 12.

**Survey of the Subdivisional Lines,
T. 1 S., R. 16 E., Gila and Salt River Meridian, Arizona**

CHAINS	
	<p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T 1 S R 16 E S 1 1/4 ——— S 12</p> <p style="text-align: center;">2001</p> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p>
50.15	Chain link fence, bears S. 7° E. and N. 33° W.
80.04	<p>The cor. of secs. 1, 2, 11 and 12.</p> <p>Land, broken. Soil, sandy loam. Timber, mesquite; undergrowth, scrub brush.</p> <hr/> <p>N. 0°01' W., bet. secs. 1 and 2.</p> <p>Across golf course fairway and over broken to level terrain through creosote.</p>
35.94	Chain link fence, 5 ft. high, bears S. 71° E. and N. 71° W.
40.00	<p>Point for the 1/4 sec. cor. of secs. 1 and 2.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T 1 S R 16 E 1/4 S 2 S 1</p> <p style="text-align: center;">2001</p> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p> <p>Cor. is located on flat terrain in creosote.</p>
62.11	Point for the closing cor. of secs. 1 and 2, at intersection with the Gila and Salt River Base Line.

**Survey of the Subdivisional Lines,
T. 1 S., R. 16 E., Gila and Salt River Meridian, Arizona**

CHAINS

Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam.,
24 ins. in the ground, with brass cap mkd.

T 1 N R 16 E
S 33

S 2 | S 1
T 1 S R 16 E
CC

2001

Deposit a magnet, in a white plastic case, at the base of the
stainless steel post.

Cor. is located on top of a spur, slopes S.

From this cor. point, the stan. cor. of secs. 33 and 34,
T. 1 N., R. 16 E., bears N. 89°56' E., 13.935 chs. dist.,
hereinbefore described.

Land, broken to level.

Soil, sandy loam.

Undergrowth, creosote and scrub brush.

Point for the 1/4 sec. cor. of sec. 1 only, T. 1 S., R. 16 E.,
is at midpoint on the N. bdy. of sec. 1.

Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam.,
24 ins. in the ground, with brass cap mkd.

T 1 N R 16 E

1/4 S 1
T 1 S R 16 E

2001

Deposit a magnet, in a white plastic case, at the base of the
stainless steel post.

Cor. is located on flat terrain in creosote.

From this cor. point, the stan. 1/4 sec. cor. of sec. 34,
T. 1 N., R. 16 E., bears N. 89°56' E., 13.95 chs. dist.,
hereinbefore described.

From the cor. of secs. 2, 3, 34 and 35, on the S. bdy. of the
Tp.

**Survey of the Subdivisional Lines,
T. 1 S., R. 16 E., Gila and Salt River Meridian, Arizona**

CHAINS	
	N. 0°01' W., bet. secs. 34 and 35.
	Over rolling land, through scrub brush and scattered timber.
23.80	Wash, 100 ft. wide, 1/2 ft. deep, drains N. 78° E.
30.40	Ridge, bears N. 85° E. and S. 80° W.
33.40	Wash, 7 ft. wide, 1 ft. deep, drains N. 70° E.
39.50	Wash, 3 ft. wide, 1/2 ft. deep, drains S. 25° E.
40.00	Point for the 1/4 sec. cor. of secs. 34 and 35.
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 22 ins. in the ground, in a collar of stone, with brass cap mkd.
	T 1 S R 16 E 1/4 S 34 S 35 2001
	Deposit a magnet, in a white plastic case, at the base of the stainless steel post.
46.20	Ridge, bears S. 70° E. and N. 50° W.
76.40	Wash, 8 ft. wide, 1 ft. deep, drains S. 60° E.
80.00	Point for the cor. of secs. 26, 27, 34 and 35.
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.
	T 1 S R 16 E S 27 S 26 S 34 S 35 2001
	Deposit a magnet, in a white plastic case, at the base of the stainless steel post.
	Cor. is located on top of a spur, slopes S.
	Land, rolling.
	Soil, sandy loam.
	Timber, scattered; undergrowth, scrub brush.

**Survey of the Subdivisional Lines,
T. 1 S., R. 16 E., Gila and Salt River Meridian, Arizona**

CHAINS	
	<p>From the cor. of secs. 25, 26, 35 and 36.</p> <p>N. 89°44' W., bet. secs. 26 and 35.</p> <p>Over rolling land, through scrub brush and scattered timber.</p>
23.30	Graded road, No. 700, 12 ft. wide, bears N. 46° E. and S. 58° W.
27.70	Wash, 200 ft. wide, 1 ft. deep, drains E.
39.99	<p>Point for the 1/4 sec. cor. of secs. 26 and 35.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 22 ins. in the ground, with brass cap mkd.</p>
	<p>T 1 S R 16 E</p> <p>S 26</p> <p>1/4 ———</p> <p>S 35</p> <p>2001</p>
	<p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p>
40.60	Ridge, bears N. 60° E. and S. 70° W.
79.98	<p>The cor. of secs. 26, 27, 34 and 35.</p> <p>Land, rolling.</p> <p>Soil, sandy loam.</p> <p>Timber, scattered; undergrowth, scrub brush.</p> <hr/>
	<p>N. 0°01' W., bet. secs. 26 and 27.</p> <p>Over rolling land, through scrub brush and scattered timber.</p>
7.70	Graded road on top of a ridge, 15 ft. wide, bears S. 75° E. and N. 60° W.
40.00	<p>Point for the 1/4 sec. cor. of secs. 26 and 27.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 16 ins. in the ground, in a mound of stone, 3 ft. base, to top, with brass cap mkd.</p>

**Survey of the Subdivisional Lines,
T. 1 S., R. 16 E., Gila and Salt River Meridian, Arizona**

CHAINS	
	T 1 S R 16 E 1/4 S 27 S 26 2001
	Deposit a magnet, in a white plastic case, at the base of the stainless steel post. Cor. is located on a steep N. facing slope.
41.70	Wash, 4 ft. wide, 2 ft. deep, drains N. 80° E.
45.40	Ridge, bears E. and S. 75° W.
51.60	Ridge, bears E. and W.
55.70	Wash, 6 ft. wide, 1 ft. deep, drains E.
59.90	Ridge, bears S. 75° E. and N. 75° W.
66.30	Wash, 6 ft. wide, 1 ft. deep, drains S. 70° W.
70.10	Ridge, bears N. 75° E. and S. 80° W.
74.40	Wash, 7 ft. wide, 1 ft. deep, drains N. 75° E.
80.00	Point for the cor. of secs. 22, 23, 26 and 27.
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 17 ins. in the ground, in a mound of stone, 3 ft. base, to top, with brass cap mkd.
	T 1 S R 16 E S 22 S 23 S 27 S 26 2001
	Deposit a magnet, in a white plastic case, at the base of the stainless steel post. Cor. is located on a steep E. facing slope. Land, rolling. Soil, sandy loam. Timber, scattered; undergrowth, scrub brush.
	<hr/> From the cor. of secs. 23, 24, 25 and 26. N. 89°44' W., bet. secs. 23 and 26.

**Survey of the Subdivisional Lines,
T. 1 S., R. 16 E., Gila and Salt River Meridian, Arizona**

CHAINS	
	Over rolling land, through scrub brush and scattered timber.
0.70	Graded road, 15 ft. wide, bears N. 25° E. and S. 25° W.
37.20	Ridge, bears N. 35° E. and S. 35° W.
39.99	Point for the 1/4 sec. cor. of secs. 23 and 26. Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.
	T 1 S R 16 E S 23 1/4 ——— S 26 2001
	Deposit a magnet, in a white plastic case, at the base of the stainless steel post.
53.10	Wash, 30 ft. wide, 1 ft. deep, drains N. 30° E.
79.98	The cor. of secs. 22, 23, 26 and 27. Land, rolling. Soil, sandy loam. Timber, scattered; undergrowth, scrub brush.
	----- N. 0°01' W., bet. secs. 22 and 23.
	Over rolling land, through scrub brush and scattered timber.
4.20	Ridge, bears E. and S. 35° W.
17.70	Wash, 9 ft. wide, 1 ft. deep, drains N. 25° E.
22.30	Graded road, 10 ft. wide, bears N. 85° E. and S. 60° W.
22.78	Barbed wire fence, 4 strand, bears N. 57° E. and S. 57° W.
29.90	Wash, 200 ft. wide, 1 1/2 ft. deep, drains N. 85° E.
35.60	Ridge, bears E. and N. 70° W.
40.00	Point for the 1/4 sec. cor. of secs. 22 and 23. Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 23 ins. in the ground, with brass cap mkd.

**Survey of the Subdivisional Lines,
T. 1 S., R. 16 E., Gila and Salt River Meridian, Arizona**

CHAINS	
	T 1 S R 16 E 1/4 S 22 S 23 2001
	Deposit a magnet, in a white plastic case, at the base of the stainless steel post. Cor. is located at the foot of a steep N. facing slope in creosote.
40.80	Wash, 6 ft. wide, 1/2 ft. deep, drains S. 85° E.
49.40	Ridge, bears N. 50° E. and W.
80.00	Point for the cor. of secs. 14, 15, 22 and 23. Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 22 ins. in the ground, with brass cap mkd.
	T 1 S R 16 E S 15 S 14 S 22 S 23 2001
	Deposit a magnet, in a white plastic case, at the base of the stainless steel post. Cor. is located in scrub mesquite. Land, rolling. Soil, sandy loam. Timber, scattered; undergrowth, scrub brush.
	<hr/> From the cor. of secs. 13, 14, 23 and 24. N. 89°44' W., bet. secs. 14 and 23. Over rolling land, through scrub brush.
39.98	Point for the 1/4 sec. cor. of secs. 14 and 23. Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 16 ins. in the ground, in a mound of stone, 3 ft. base, to top, with brass cap mkd.

**Survey of the Subdivisional Lines,
T. 1 S., R. 16 E., Gila and Salt River Meridian, Arizona**

CHAINS	
	T 1 S R 16 E S 14 1/4 ——— S 23 2001
	Deposit a magnet, in a white plastic case, at the base of the stainless steel post.
40.30	Wash, 3 ft. wide, 1/2 ft. deep, drains S. 20° E.
43.50	Ridge, bears S. 10° E. and N. 10° W.
79.96	The cor. of secs. 14, 15, 22 and 23.
	Land, rolling. Soil, sandy loam. Undergrowth, scrub brush.
	N. 0°01' W., bet. secs. 14 and 15.
	Over rolling to level land.
40.00	Point for the 1/4 sec. cor. of secs. 14 and 15.
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.
	T 1 S R 16 E 1/4 S 15 S 14 2001
	Deposit a magnet, in a white plastic case, at the base of the stainless steel post.
	Raise a mound of stone, 3 ft. base, 2 ft. high, W. of cor.
77.19	Barbed wire fence, 4 strand, bears S. 15° E. and N. 15° W.
77.83	Barbed wire fence, 4 strand, bears S. 85° E. and N. 85° W. From this point, an intersection of fences bears N. 85° W., 19 lks. dist., fences bear S. 15° E. and N. 15° W.; and S. 85° E. and N. 85° W.
80.00	Point for the cor. of secs. 10, 11, 14 and 15.
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 22 ins. in the ground, with brass cap mkd.

**Survey of the Subdivisional Lines,
T. 1 S., R. 16 E., Gila and Salt River Meridian, Arizona**

CHAINS	
	<p>T 1 S R 16 E S 10 S 11 S 15 S 14</p> <p>2001</p> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p> <p>Cor. is located on level ground.</p> <p>Land, rolling to level. Soil, sandy loam. Undergrowth, scrub brush.</p> <hr/> <p>From the cor. of secs. 11, 12, 13 and 14.</p> <p>N. 89°45' W., bet. secs. 11 and 14.</p> <p>Over nearly level land.</p>
16.07	Chain link fence, 6 ft. high, along W. side of Globe Municipal Airport, bears N. 10° E. and S. 10° W.
39.97	Point for the 1/4 sec. cor. of secs. 11 and 14.
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.
	<p>T 1 S R 16 E S 11 1/4 ——— S 14</p> <p>2001</p> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p>
76.31	From this point, the NW cor. of a trailer house, 60 x 12 ft., bears S., 28 lks. dist.; long side bears E.
79.94	The cor. of secs. 10, 11, 14 and 15.
	Land, level. Soil, sandy loam. Undergrowth, scrub brush.

**Survey of the Subdivisional Lines,
T. 1 S., R. 16 E., Gila and Salt River Meridian, Arizona**

CHAINS	
	N. 0°01' W., bet. secs. 10 and 11. Over nearly level land.
2.97	Barbed wire fence, 4 strand, bears N. 80° E. and S. 80° W.
3.25	Graded road, 15 ft. wide, bears S. 33° E. and N. 43° W.
4.15	Graded road, 18 ft. wide, bears S. 75° E. and N. 73° W.
5.80	Power line, 2 strand, bears S. 73° E. and N. 73° W.
25.40	Power line, 4 strand, bears S. 80° E. and N. 80° W.
26.60	Two track road, 10 ft. wide, bears S. 75° E. and N. 80° W.
28.05	S. right-of-way fence of U.S. Highway No. 70, 4 strand barbed wire, bears S. 80° E. and N. 80° W.
29.31	S. edge of pavement of U.S. Highway No. 70, 33 ft. wide, bears S. 80° E. and N. 80° W.
29.88	N. edge of pavement of U.S. Highway No. 70, bears S. 80° E. and N. 80° W.
30.34	N. right-of-way fence of U.S. Highway No. 70, 4 strand barbed wire, bears S. 80° E. and N. 80° W.
31.12	Center of railroad tracks, bears S. 80° E. and N. 80° W.
33.25	Two track road, 12 ft. wide, bears S. 65° E. and N. 65° W. in a curve.
40.00	Point for the 1/4 sec. cor. of secs. 10 and 11. Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd. <div style="text-align: center;"> <p>T 1 S R 16 E 1/4 S 10 S 11</p> <p>2001</p> </div> Deposit a magnet, in a white plastic case, at the base of the stainless steel post. Cor. is located in mesquite bush.
80.00	Point for the cor. of secs. 2, 3, 10 and 11.

**Survey of the Subdivisional Lines,
T. 1 S., R. 16 E., Gila and Salt River Meridian, Arizona**

CHAINS	
	<p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;"> T 1 S R 16 E S 3 S 2 S 10 S 11 2001 </p> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p> <p>Land, level. Soil, sandy loam. Timber, mesquite; Undergrowth, scrub brush.</p> <hr/> <p>From the cor. of secs. 1, 2, 11 and 12.</p> <p>N. 89°44' W., bet. secs. 2 and 11.</p> <p>Over nearly level land.</p>
39.30	Graded road, 12 ft. wide, bears N. 10° E. and S. 10° W.
39.74	Chain link fence, with 2 strand barbed wire, bears N. 38° E. and S. 38° W.
39.97	Point for the 1/4 sec. cor. of secs. 2 and 11.
	<p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 22 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;"> T 1 S R 16 E S 2 1/4 ——— S 11 2001 </p> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p>
42.10	Wash, 20 ft. wide, 1 ft. deep, drains S. 65° E.
79.94	<p>The cor. of secs. 2, 3, 10 and 11.</p> <p>Land, level. Soil, sandy loam. Undergrowth, scrub brush.</p> <hr/>

**Survey of the Subdivisional Lines,
T. 1 S., R. 16 E., Gila and Salt River Meridian, Arizona**

CHAINS	
	N. 0°01' W., bet. secs. 2 and 3. Over nearly level land.
38.70	Graded road, 12 ft. wide, bears S. 75° E. and N. 75° W.
40.00	Point for the 1/4 sec. cor. of secs. 2 and 3. Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.
	T 1 S R 16 E 1/4 S 3 S 2 2001
	Deposit a magnet, in a white plastic case, at the base of the stainless steel post.
61.72	Point for the closing cor. of secs. 2 and 3, at intersection with the Gila and Salt River Base Line. Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 23 ins. in the ground, with brass cap mkd.
	T 1 N R 16 E S 32 ----- S 3 S 2 T 1 S R 16 E CC 2001
	Deposit a magnet, in a white plastic case, at the base of the stainless steel post. Cor. is located on level ground. From this cor. point, the stan. cor. of secs. 32 and 33, T. 1 N., R. 16 E., bears N. 89°58' E., 13.77 chs. dist., hereinbefore described. Land, level. Soil, sandy loam. Undergrowth, scrub brush.
	Point for the 1/4 sec. cor. of sec. 2 only, T. 1 S., R. 16 E., is at midpoint on the N. bdy. of sec. 2.

**Survey of the Subdivisional Lines,
T. 1 S., R. 16 E., Gila and Salt River Meridian, Arizona**

CHAINS	
	<p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 25 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T 1 N R 16 E ----- 1/4 S 2 T 1 S R 16 E</p> <p style="text-align: center;">2001</p> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p> <p>Cor. is located on W. face of a ridge, bears N. 15° E. and S. 40° W.</p> <p>From this cor. point, the stan. 1/4 sec. cor. of sec. 33, T. 1 N., R. 16 E., bears East, 13.85 chs. dist., hereinbefore described.</p> <hr/> <p>From the cor. of secs. 3, 4, 33 and 34, on the S. bdy. of the Tp.</p> <p>N. 0°02' W., bet. secs. 33 and 34.</p> <p>Over rolling land, through scrub brush and scattered timber.</p>
40.00	<p>Point for the 1/4 sec. cor. of secs. 33 and 34.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 23 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T 1 S R 16 E 1/4 S 33 S 34</p> <p style="text-align: center;">2001</p> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p>
45.80	<p>Graded road on top of a ridge, 16 ft. wide, bears N. 84° E. and S. 68° W.</p>
64.90	<p>Wash, 30 ft. wide, 1/2 ft. deep, drains N. 70° E.</p>
80.00	<p>Point for the cor. of secs. 27, 28, 33 and 34.</p>

**Survey of the Subdivisional Lines,
T. 1 S., R. 16 E., Gila and Salt River Meridian, Arizona**

CHAINS	
	<p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 22 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;"> T 1 S R 16 E S 28 S 27 S 33 S 34 </p> <p style="text-align: center;">2001</p> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p> <p>Cor. is located on top of a spur, slopes N. 56° E.</p> <p>Land, rolling. Soil, sandy loam. Timber, scattered; undergrowth, scrub brush.</p> <hr/> <p>From the cor. of secs. 26, 27, 34 and 35.</p> <p>N. 89°45' W., bet. secs. 27 and 34.</p> <p>Over rolling land, through scrub brush and scattered timber.</p>
34.70	Wash, 5 ft. wide, 1/2 ft. deep, drains S. 70° E.
40.00	Point for the 1/4 sec. cor. of secs. 27 and 34.
	<p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 23 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;"> T 1 S R 16 E S 27 1/4 ——— S 34 </p> <p style="text-align: center;">2001</p> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p> <p>Raise a mound of stone, 3 ft. base, 2 ft. high, N. of the cor.</p>
42.90	Graded road, 15 ft. wide, bears N. 12° E. and S. 12° W.
80.00	The cor. of secs. 27, 28, 33 and 34.

**Survey of the Subdivisional Lines,
T. 1 S., R. 16 E., Gila and Salt River Meridian, Arizona**

CHAINS	
	Land, rolling. Soil, sandy loam. Timber, scattered; undergrowth, scrub brush.
	<hr/>
	N. 0°02' W., bet. secs. 27 and 28.
	Over rolling land, through scrub brush and scattered timber.
5.20	Wash, 7 ft. wide, 1/2 ft. deep, drains N. 60° E.
11.40	Ridge, bears N. 40° E. and N. 79° W.
21.30	Wash, 90 ft. wide, 1/2 ft. deep, drains N. 82° E.
33.50	Spur, slopes N. 75° E.
40.00	Point for the 1/4 sec. cor. of secs. 27 and 28. Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 22 ins. in the ground, with brass cap mkd.
	T 1 S R 16 E 1/4 S 28 S 27 2001
	Deposit a magnet, in a white plastic case, at the base of the stainless steel post.
	Cor. is located on a steep N. facing slope.
43.10	Wash, 7 ft. wide, 1/2 ft. deep, drains N. 60° E.
49.10	Ridge, bears S. 70° E. and N. 55° W.
57.66	Barbed wire fence, 4 strand, bears N. 56° E. and S. 56° W.
63.10	Wash, 7 ft. wide, 1 ft. deep, drains N. 10° E. for 5 ft. dist. then drains N. 70° W.
64.00	Wash, 10 ft. wide, 1 1/2 ft. deep, drains N. 60° E.
66.10	Wash, 7 ft. wide, 1 1/2 ft. deep, drains N. 80° E.
68.60	Spur, slopes N. 60° E.
73.00	Wash, 5 ft. wide, 2 ft. deep, drains N. 64° E.
80.00	Point for the cor. of secs. 21, 22, 27 and 28.

**Survey of the Subdivisional Lines,
T. 1 S., R. 16 E., Gila and Salt River Meridian, Arizona**

CHAINS									
	<p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 23 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center;"> <table style="margin: auto;"> <tr> <td>T 1 S</td> <td>R 16 E</td> </tr> <tr> <td style="border-right: 1px solid black;">S 21</td> <td>S 22</td> </tr> <tr> <td style="border-right: 1px solid black;">S 28</td> <td>S 27</td> </tr> </table> <p>2001</p> </div> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p> <p>Cor. is located on a steep S. facing slope.</p> <p>Land, rolling. Soil, sandy loam. Timber, scattered; undergrowth, scrub brush.</p> <hr/> <p>From the cor. of secs. 22, 23, 26 and 27.</p> <p>N. 89°45' W., bet. secs. 22 and 27.</p> <p>Over rolling land, through scrub brush and scattered timber.</p>	T 1 S	R 16 E	S 21	S 22	S 28	S 27		
T 1 S	R 16 E								
S 21	S 22								
S 28	S 27								
40.01	<p>Point for the 1/4 sec. cor. of secs. 22 and 27.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 23 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center;"> <table style="margin: auto;"> <tr> <td>T 1 S</td> <td>R 16 E</td> </tr> <tr> <td></td> <td>S 22</td> </tr> <tr> <td>1/4</td> <td style="border-top: 1px solid black;">———</td> </tr> <tr> <td></td> <td>S 27</td> </tr> </table> <p>2001</p> </div> <p>Deposit nine(9) 40d nails, wrapped in flagging, as a memorial at the base of the stainless steel post.</p> <p>Cor. is located on top of a ridge, bears N. 45° E. and S. 45° W.</p>	T 1 S	R 16 E		S 22	1/4	———		S 27
T 1 S	R 16 E								
	S 22								
1/4	———								
	S 27								
46.70	<p>Wash, 30 ft. wide, 1 ft. deep, drains N. 45° E.</p>								
78.10	<p>Ridge, bears N. 65° E. and S. 65° W.</p>								
80.02	<p>The cor. of secs. 21, 22, 27 and 28.</p>								

**Survey of the Subdivisional Lines,
T. 1 S., R. 16 E., Gila and Salt River Meridian, Arizona**

CHAINS	
	<p>Land, rolling. Soil, sandy loam. Timber, scattered; undergrowth, scrub brush.</p> <hr/> <p>N. 0°02' W., bet. secs. 21 and 22.</p> <p>Over rolling to level land, through mesquite.</p>
40.00	<p>Point for the 1/4 sec. cor. of secs. 21 and 22.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T 1 S R 16 E 1/4 S 21 S 22</p> <p style="text-align: center;">2001</p> <p>Deposit ten(10) 40d nails, wrapped in flagging, as a memorial at the base of the stainless steel post.</p>
46.38	<p>From this point, the well head at Nig Well No. 2, bears East, 6.43 chs. dist.</p>
80.00	<p>Point for the cor. of secs. 15, 16, 21 and 22.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 27 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T 1 S R 16 E S 16 S 15 S 21 S 22</p> <p style="text-align: center;">2001</p> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p> <p>Cor. is located 10 lks. S. of a wash, 5 ft. wide, 1 ft. deep, drains S. 70° E.</p> <p>Land, rolling to level. Soil, sandy loam. Timber, mesquite; undergrowth, scrub brush.</p> <hr/> <p>From the cor. of secs. 14, 15, 22 and 23.</p> <p>N. 89°45' W., bet. secs. 15 and 22.</p>

**Survey of the Subdivisional Lines,
T. 1 S., R. 16 E., Gila and Salt River Meridian, Arizona**

CHAINS	
	Over gently rolling land, through mesquite.
33.60	Two track road, No. 711, 9 ft. wide, bears N. 30° E. and S. 20° W.
40.015	Point for the 1/4 sec. cor. of secs. 15 and 22. Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 23 ins. in the ground, with brass cap mkd.
	T 1 S R 16 E S 15 1/4 ——— S 22 2001
	Deposit a magnet, in a white plastic case, at the base of the stainless steel post.
	Cor. is located on near level ground in medium mesquite timber.
59.85	Graded road, No. 710, 22 ft. wide, bears S. 3° W. and N. 3° W. in a curve.
71.10	Wash, 22 ft. wide, 1/2 ft. deep, drains N. 35° E.
80.03	The cor. of secs. 15, 16, 21 and 22. Land, gently rolling. Soil, sandy loam. Timber, mesquite; undergrowth, scrub brush.
	————— N. 0°02' W., bet. secs. 15 and 16. Over rolling land.
17.00	Enter building site, edge bears N. 70° E. and S. 70° W.
19.80	Leave building site, edge bears N. 80° E. and S. 80° W.
40.00	Point for the 1/4 sec. cor. of secs. 15 and 16. Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.

**Survey of the Subdivisional Lines,
T. 1 S., R. 16 E., Gila and Salt River Meridian, Arizona**

CHAINS	
	T 1 S R 16 E 1/4 S 16 S 15 2001
	Deposit a magnet, in a white plastic case, at the base of the stainless steel post.
41.10	Wash, 10 ft. wide, 1 ft. deep, drains S. 75° E.
43.05	Graded road, 18 ft. wide, bears N. 45° E. and S. 45° W., curving westerly.
78.40	Power line, 2 strand, bears S. 45° E. and N. 45° W.
80.00	Point for the cor. of secs. 9, 10, 15 and 16.
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 23 ins. in the ground, in a collar of stone, with brass cap mkd.
	T 1 S R 16 E S 9 S 10 S 16 S 15 2001
	Deposit a magnet, in a white plastic case, at the base of the stainless steel post.
	Cor. is located on level ground.
	Land, rolling to level. Soil, sandy loam. Undergrowth, scrub brush.
	From the cor. of secs. 10, 11, 14 and 15.
	N. 89°45' W., bet. secs. 10 and 15.
	Over level ground.
0.81	Barbed wire fence, 4 strand, bears S. 15° E. and N. 15° W.
40.02	Point for the 1/4 sec. cor. of secs. 10 and 15.
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 25 ins. in the ground, with brass cap mkd.

**Survey of the Subdivisional Lines,
T. 1 S., R. 16 E., Gila and Salt River Meridian, Arizona**

CHAINS	
	T 1 S R 16 E S 10 1/4 ——— S 15 2001
	Deposit a magnet, in a white plastic case, at the base of the stainless steel post.
40.20	Wash, 2 ft. wide, 1/2 ft. deep, drains N. 24° E.
48.90	Power line, bears N. 18° E. and S. 18° W.
50.30	Graded road, No. 710, 10 ft. wide, bears N. 18° E. and S. 18° W.
80.04	The cor. of secs. 9, 10, 15 and 16. Land, level. Soil, sandy loam. Undergrowth, scrub brush.
	N. 0°02' W., bet. secs. 9 and 10.
	Over rolling to level land, through scattered creosote and mesquite.
38.00	Graded road, 16 ft. wide, bears SW and NE.
40.00	Point for the 1/4 sec. cor. of secs. 9 and 10. Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 25 ins. in the ground, with brass cap mkd.
	T 1 S R 16 E 1/4 S 9 S 10 2001
	Deposit a magnet, in a white plastic case, at the base of the stainless steel post.
	Cor. is located on nearly level ground in scattered mesquite.
50.07	Gas line, power line and graded road, 16 ft. wide, bears S. 65° E. and N. 65° W.
51.04	S. right-of-way fence of U.S. Highway No. 70, 4 strand barbed wire, bears S. 65° E. and N. 65° W.

**Survey of the Subdivisional Lines,
T. 1 S., R. 16 E., Gila and Salt River Meridian, Arizona**

CHAINS									
52.41	S. edge of pavement of U.S. Highway No. 70, 33 ft. wide, bears S. 65° E. and N. 65° W.								
53.02	N. edge of pavement of U.S. Highway No. 70, bears S. 65° E. and N. 65° W.								
53.71	N. right-of-way fence of U.S. Highway No. 70, 4 strand barbed wire, bears S. 65° E. and N. 65° W.								
54.54	Center of railroad tracks, bears S. 65° E. and N. 65° W.								
55.40	Two track road, 12 ft. wide, bears S. 65° E. and N. 65° W.								
80.00	Point for the cor. of secs. 3, 4, 9 and 10. Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.								
	<table border="0"> <tr> <td>T 1 S</td> <td>R 16 E</td> </tr> <tr> <td>S 4</td> <td>S 3</td> </tr> <tr> <td>S 9</td> <td>S 10</td> </tr> </table>	T 1 S	R 16 E	S 4	S 3	S 9	S 10		
T 1 S	R 16 E								
S 4	S 3								
S 9	S 10								
	2001								
	Deposit a magnet, in a white plastic case, at the base of the stainless steel post.								
	Cor. is located on rolling terrain in scattered creosote.								
	Land, rolling to level. Soil, sandy loam. Timber, mesquite; undergrowth, creosote and scrub brush.								
	<hr/>								
	From the cor. of secs. 2, 3, 10 and 11.								
	N. 89°45' W., bet. secs. 3 and 10.								
	Over rolling to broken land.								
40.025	Point for the 1/4 sec. cor. of secs. 3 and 10. Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 25 ins. in the ground, with brass cap mkd.								
	<table border="0"> <tr> <td>T 1 S</td> <td>R 16 E</td> </tr> <tr> <td></td> <td>S 3</td> </tr> <tr> <td>1/4</td> <td>—</td> </tr> <tr> <td></td> <td>S 10</td> </tr> </table>	T 1 S	R 16 E		S 3	1/4	—		S 10
T 1 S	R 16 E								
	S 3								
1/4	—								
	S 10								
	2001								

**Survey of the Subdivisional Lines,
T. 1 S., R. 16 E., Gila and Salt River Meridian, Arizona**

CHAINS	
	Deposit a magnet, in a white plastic case, at the base of the stainless steel post.
80.05	The cor. of secs. 3, 4, 9 and 10. Land, rolling to broken. Soil, sandy loam. Timber, mesquite; undergrowth, creosote and scrub brush.

	N. 0°02' W., bet. secs. 3 and 4. Over rolling to broken land.
17.60	Graded road, No. 803, 20 ft. wide, bears ENE and WSW.
37.20	Spur, slopes ESE.
39.80	Wash, 3 ft. wide, 1/2 ft. deep, drains ESE.
40.00	Point for the 1/4 sec. cor. of secs. 3 and 4. Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.
	T 1 S R 16 E 1/4 S 4 S 3 2001
	Deposit a magnet, in a white plastic case, at the base of the stainless steel post. Cor. is located on a S. facing slope.
42.40	Ridge, bears E. and W.
61.31	Point for the closing cor. of secs. 3 and 4, at intersection with the Gila and Salt River Base Line. Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.

**Survey of the Subdivisional Lines,
T. 1 S., R. 16 E., Gila and Salt River Meridian, Arizona**

CHAINS

T 1 N R 16 E
 S 31

 S 4 | S 3
 T 1 S R 16 E
 CC

2001

Deposit a magnet, in a white plastic case, at the base of the stainless steel post.

Cor. is located on a ridge, bears E. and W.

From this cor. point, the stan. cor. of secs. 31 and 32, T. 1 N., R. 16 E., bears N. 89°58' E., 13.75 chs. dist., hereinbefore described.

Land, rolling to broken.

Soil, sandy loam.

Timber, mesquite; undergrowth, creosote and scrub brush.

Point for the 1/4 sec. cor. of sec. 3 only, T. 1 S., R. 16 E., is at midpoint on the N. bdy. of sec. 3.

Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.

T 1 N R 16 E

 1/4 S 3
 T 1 S R 16 E

2001

Deposit a magnet, in a white plastic case, at the base of the stainless steel post.

Cor. is located on a spur, slopes NNE.

From this cor. point, the stan. 1/4 sec. cor. of sec. 32, T. 1 N., R. 16 E., bears N. 89°58' E., 13.75 chs. dist., hereinbefore described.

From the cor. of secs. 4, 5, 32 and 33, on the S. bdy. of the Tp.

N. 0°02' W., bet. secs. 32 and 33.

Over rolling land.

**Survey of the Subdivisional Lines,
T. 1 S., R. 16 E., Gila and Salt River Meridian, Arizona**

CHAINS	
12.50	Two track road on the top of a ridge, 10 ft. wide, bears N. 61° E. and S. 79° W.
23.11	Barbed wire fence, 6 strand, bears S. 65° E. and N. 65° W.
24.70	Wash, 11 ft. wide, 1/2 ft. deep, drains N. 65° E.
36.80	Ridge, bears N. 45° E. and S. 75° W.
40.00	Point for the 1/4 sec. cor. of secs. 32 and 33. Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 21 ins. in the ground, in a collar of stone, with brass cap mkd. <div style="text-align: center;"> T 1 S R 16 E 1/4 S 32 S 33 2001 </div>
80.00	Deposit a magnet, in a white plastic case, at the base of the stainless steel post. Point for the cor. of secs. 28, 29, 32 and 33. Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 21 ins. in the ground, in a collar of stone, with brass cap mkd. <div style="text-align: center;"> T 1 S R 16 E S 29 S 28 S 32 S 33 2001 </div>
39.99	Deposit a magnet, in a white plastic case, at the base of the stainless steel post. Cor. is located on a steep S. facing slope. Land, rolling. Soil, sandy loam. Timber, scattered; undergrowth, scrub brush. <hr/> From the cor. of secs. 27, 28, 33 and 34. N. 89°45' W., bet. secs. 28 and 33. Over rolling and broken land. Point for the 1/4 sec. cor. of secs. 28 and 33.

**Survey of the Subdivisional Lines,
T. 1 S., R. 16 E., Gila and Salt River Meridian, Arizona**

CHAINS	
	<p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 22 ins. in the ground, in a collar of stone, with brass cap mkd.</p> <p style="text-align: center;">T 1 S R 16 E S 28 1/4 ——— S 33</p> <p style="text-align: center;">2001</p> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p> <p>Cor. is located on a steep S. facing slope.</p>
79.98	<p>The cor. of secs. 28, 29, 32 and 33.</p> <p>Land, rolling to broken. Soil, sandy loam. Timber, scattered; undergrowth, scrub brush.</p> <hr/> <p>N. 0°02' W., bet. secs. 28 and 29.</p> <p>Over rolling and broken land.</p>
40.00	<p>Point for the 1/4 sec. cor. of secs. 28 and 29.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 19 ins. in the ground to bedrock, in a mound of stone, 3 ft. base, to top, with brass cap mkd.</p> <p style="text-align: center;">T 1 S R 16 E 1/4 S 29 S 28</p> <p style="text-align: center;">2001</p> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p> <p>Cor. is located on a steep N. facing slope.</p>
80.00	<p>Point for the cor. of secs. 20, 21, 28 and 29.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 17 ins. in the ground to bedrock, in a mound of stone, 2 1/2 ft. base, to top, with brass cap mkd.</p>

**Survey of the Subdivisional Lines,
T. 1 S., R. 16 E., Gila and Salt River Meridian, Arizona**

CHAINS	
	T 1 S R 16 E S 20 S 21 S 29 S 28 2001
	Deposit a magnet, in a white plastic case, at the base of the stainless steel post. Land, rolling to broken. Soil, sandy loam. Timber, scattered; undergrowth, scrub brush.
	<hr/> From the cor. of secs. 21, 22, 27 and 28. N. 89°45' W., bet. secs. 21 and 28. Over rolling land.
39.98	Point for the 1/4 sec. cor. of secs. 21 and 28. Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 25 ins. in the ground, with brass cap mkd.
	T 1 S R 16 E S 21 1/4 ——— S 28 2001
	Deposit a magnet, in a white plastic case, at the base of the stainless steel post. Cor. is located on nearly level ground in moderate mesquite and scattered oak.
44.40	Wash, 22 ft. wide, 3 ft. deep, drains N. 45° E.
52.90	Two track road, No. 710, 9 ft. wide, located on top of a ridge, bears N. 60° E. and S. 70° W.
79.96	The cor. of secs. 20, 21, 28 and 29. Land, rolling. Soil, sandy loam. Undergrowth, scrub brush.
	<hr/> N. 0°04' W., bet. secs. 20 and 21.

**Survey of the Subdivisional Lines,
T. 1 S., R. 16 E., Gila and Salt River Meridian, Arizona**

CHAINS	<p>Over rolling land.</p>
15.37	<p>Point for the closing cor. of secs. 20 and 21, at intersection with the W. bdy. of the San Carlos Indian Reservation.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center; margin: 10px 0;"> <p>T 1 S R 16 E</p> <p>S 20 S 21</p> <p>CC</p> </div> <p>2001</p> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p> <p>From this cor. point, the 68 mile cor., on the W. bdy. of the San Carlos Indian Reservation, bears N. 8°19' E., 10.16 chs. dist., hereinbefore described.</p> <p>Land, rolling. Soil, sandy loam. Undergrowth, scrub brush.</p> <hr style="width: 60%; margin: 10px auto;"/> <p>From the cor. of secs. 15, 16, 21 and 22.</p> <p>N. 89°45' W., bet. secs. 16 and 21.</p> <p>Over rolling land.</p>
40.00	<p>Point for the 1/4 sec. cor. of secs. 16 and 21.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 22 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center; margin: 10px 0;"> <p>T 1 S R 16 E</p> <p>S 16</p> <p>1/4 ———</p> <p>S 21</p> </div> <p>2001</p> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p>

**Survey of the Subdivisional Lines,
T. 1 S., R. 16 E., Gila and Salt River Meridian, Arizona**

CHAINS	<p>Cor. is located on a moderate S. facing slope, 50 lks. below top of ridge, bears E. and W.</p>
70.47	<p>Point for the closing cor. of secs. 16 and 21, at intersection with the W. bdy. of the San Carlos Indian Reservation.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 22 ins. in the ground, in a collar of stone, with brass cap mkd.</p> <div style="text-align: center; margin: 10px 0;"> <p>T 1 S R 16 E R I S 16 C S 21 S</p> </div> <p align="center">2001</p> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p> <p>Cor. is located 9 1/2 lks. E. of a barbed wire fence, 11 strand, bears N. 8° E. and S. 8° W.</p> <p>From this cor. point, the 67 1/2 mile cor., on the W. bdy. of the San Carlos Indian Reservation, bears S. 8°19' W., 15.015 chs. dist., hereinbefore described.</p> <p>Land, rolling. Soil, sandy loam. Undergrowth, scrub brush.</p> <hr style="width: 60%; margin: 10px auto;"/> <p>From the cor. of secs. 9, 10, 15 and 16.</p> <p>N. 89°45' W., bet. secs. 9 and 16.</p> <p>Over rolling land.</p>
39.90	<p>Intersect the southeasterly side of a manufactured home, 60 1/2 x 27 1/2 ft., long side bears N. 58° W. From this point, the NE cor. bears N. 32° E., 7.5 lks. dist.</p>
40.00	<p>True point for the 1/4 sec. cor. of secs. 9 and 16, falls in the manufactured home, where it is impracticable to establish a permanent monument.</p> <p>From this true point, the point selected for the witness cor. to the 1/4 sec. cor. of secs. 9 and 16, bears S. 16°45' E., 87.5 lks. dist.</p>

**Survey of the Subdivisional Lines,
T. 1 S., R. 16 E., Gila and Salt River Meridian, Arizona**

CHAINS

Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 27 ins. in the ground, with brass cap mkd.

WC
T 1 S R 16 E
 ↑ S 9
 1/4 ———
 S 16

2001

Deposit a magnet, in a white plastic case, at the base of the stainless steel post.

40.56 Intersect the southwesterly side of the same manufactured home. From this point, the SE cor. bears S. 58° E., 56 lks. dist.

58.78 Point for the closing cor. of secs. 9 and 16, at intersection with the W. bdy. of the San Carlos Indian Reservation.

Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 22 ins. in the ground, in a collar of stone, with brass cap mkd.

T 1 S R 16 E
 / R
 I S 9
 ——— CC
 C S 16
 /S

2001

Deposit a magnet, in a white plastic case, at the base of the stainless steel post.

Cor. is located 13 lks. E. of an old wooden post barbed wire fence, 5 strand, intermingled with a newer iron post barbed wire fence, 5 strand, bears N. 8° E. and S. 8° W.

From this cor. point, the 66 mile cor., on the W. bdy. of the San Carlos Indian Reservation, bears N. 8°16' E., 24.735 chs. dist., hereinbefore described.

Land, rolling.
Soil, sandy loam.
Undergrowth, scrub brush.

From the cor. of secs. 3, 4, 9 and 10.

**Survey of the Subdivisional Lines,
T. 1 S., R. 16 E., Gila and Salt River Meridian, Arizona**

CHAINS	<p>N. 89°45' W., bet. secs. 4 and 9.</p> <p>Over rolling land.</p> <p>36.55 Graded road, No. 803, 20 ft. wide, bears N. 55° E. and S. 25° W., in a curve.</p> <p>40.00 Point for the 1/4 sec. cor. of secs. 4 and 9.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 25 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center; margin: 10px 0;"> <p>T 1 S R 16 E</p> <p> S 4</p> <p> 1/4 ———</p> <p> S 9</p> <p>2001</p> </div> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p> <p>Cor. is located on a gentle S. facing slope.</p> <p>45.61 Railroad right-of-way fence, bears S. 35° E. and N. 35° W.</p> <p>46.42 Barbed wire fence, 5 strand, bears N. 8° E. and S. 8° W.</p> <p>46.74 Center of railroad tracks, bears S. 35° E. and N. 35° W., tracks begin curving to NW.</p> <p>47.05 Point for the closing cor. of secs. 4 and 9, at intersection with the W. bdy. of the San Carlos Indian Reservation.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 14 ins. in the ground, in a mound of stone, 3 ft. base, to top, with brass cap mkd.</p> <div style="text-align: center; margin: 10px 0;"> <p>T 1 S R 16 E</p> <p> / R</p> <p> / I S 4</p> <p> / ————— CC</p> <p> / C S 9</p> <p> / S</p> <p>2001</p> </div> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p>
--------	---

**Survey of the Subdivisional Lines,
T. 1 S., R. 16 E., Gila and Salt River Meridian, Arizona**

CHAINS

Cor. is located on the S. side of the railroad tracks embankment.

From this cor. point, the 65 mile cor., on the W. bdy. of the San Carlos Indian Reservation, bears N. 8°24' E., 24.28 chs. dist., hereinbefore described.

Land, rolling.
Soil, sandy loam.
Undergrowth, scrub brush.


From the cor. of secs. 28, 29, 32 and 33.

N. 89°45' W., bet. secs. 29 and 32.

Over rolling land.

14.01 Point for the closing cor. of secs. 29 and 32, at intersection with the W. bdy. of the San Carlos Indian Reservation.

Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 19 ins. in the ground, in a mound of stone, 3 ft. base, to top, with brass cap mkd.



2001

Deposit a magnet, in a white plastic case, at the base of the stainless steel post.

From this cor. point, the 69 1/2 mile cor., on the W. bdy. of the San Carlos Indian Reservation, bears S. 8°20' W., 13.69 chs. dist., hereinbefore described.

Land, rolling.
Soil, sandy loam.
Undergrowth, scrub brush.

From the cor. of secs. 20, 21, 28 and 29.

N. 89°45' W., bet. secs. 20 and 29.

Over rolling land.


**Survey of the Subdivisional Lines,
T. 1 S., R. 16 E., Gila and Salt River Meridian, Arizona**

CHAINS

2.26

Point for the closing cor. of secs. 20 and 29, at intersection with the W. bdy. of the San Carlos Indian Reservation.

Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 23 ins. in the ground, with brass cap mkd.



2001

Deposit a magnet, in a white plastic case, at the base of the stainless steel post.

Raise a mound of stone, 3 ft. base, 1 1/2 ft. high, E. of the cor.

Cor. is located 6 lks. W. of a barbed wire fence, 8 strand, bears N. 8° E. and S. 8° W.

From this cor. point, the point for the 68 1/2 mile cor., on the W. bdy. of the San Carlos Indian Reservation, bears S. 8°19' W., 14.41 chs. dist., hereinbefore described.

Land, rolling.
Soil, sandy loam.
Undergrowth, scrub brush.

GENERAL DESCRIPTION

This survey is located approximately 6 miles east of Globe, Arizona, on the San Carlos Indian Reservation. Access is provided by U.S. Highway No. 70 which crosses easterly and westerly through the upper portion of the township and by a few graded roads. Globe Municipal Airport is located in sections 12 and 13.

The elevation ranges from 3100 to 4100 feet above sea level. The terrain varies from rolling and broken land to nearly level. Vegetation consists of scrub oak, mesquite, and creosote. The soil is mostly sandy loam.

The mean magnetic declination of 11 1/2° E. was derived from the National Geophysical Data Center's (NGDC) on-line declination calculator, utilizing the latest International Geomagnetic Reference Field (IGRF) model for the dates of survey.

**UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT**

FIELD ASSISTANTS

NAMES	CAPACITY
Gordon R. Bubel	Land Surveyor
Joe R. Salazar	Land Surveyor
John D. Knudson	Surveying Technician
Robert J. Lyle	Surveying Technician
Mark R. Searles	Surveying Technician
Marvin P. Murphy	Surveying Technician
Rudy Keedah	Surveyor in Training

CERTIFICATE OF SURVEY

I, W. William Foster, Cadastral Surveyor, HEREBY CERTIFY upon honor, that in pursuance of special instructions bearing date of the 21st day of May, 2001, I have dependently resurveyed a portion of the west boundary of the San Carlos Indian Reservation, a portion of the Gila and Salt River Base Line through range 16 east (north boundary), a portion of the south boundary and surveyed the south and east boundaries and the subdivisional lines (within the San Carlos Indian Reservation), T. 1 S., R. 16 E., of the Gila and Salt River Meridian, in the State of Arizona, which are represented in the foregoing field notes as having been executed by me and under my direction. Said survey has been made in strict conformity with said special instructions, the Manual of Instructions for the Survey of the Public Lands of the United States, 1973, and in specific manner described in the foregoing field notes.

W. William Foster is no longer assigned to this office and is unavailable for signature.

(Date)

(Cadastral Surveyor)

CERTIFICATE OF APPROVAL

BUREAU OF LAND MANAGEMENT
Phoenix, Arizona

The foregoing field notes of the dependent resurvey of a portion of the west boundary of the San Carlos Indian Reservation, a portion of the Gila and Salt River Base Line through range 16 east (north boundary), a portion of the south boundary and the survey of the south and east boundaries and subdivisional lines (within the San Carlos Indian Reservation), T. 1 S., R. 16 E., Gila and Salt River Meridian, in the State of Arizona, executed by W. William Foster, Cadastral Surveyor, having been critically examined and found correct, are hereby approved.

8/12/2009
(Date)

Stephen K. Hansen
(Chief Cadastral Surveyor of Arizona)

~~CERTIFICATE OF TRANSCRIPT~~

~~I CERTIFY That the foregoing transcript of the field notes of the above described surveys in T. 1 S., R. 16 E., Gila and Salt River Meridian, Arizona, is a true copy of the original field notes.~~

~~_____
(Date)~~

~~_____
(Chief Cadastral Surveyor of Arizona)~~