

ORIGINAL

**UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT**

FIELD NOTES

OF THE

DEPENDENT RESURVEY OF PORTIONS OF THE SIXTH STANDARD PARALLEL NORTH

(SOUTH BOUNDARY), TOWNSHIPS 25 NORTH, RANGES 28 AND 29 EAST

AND

THE DEPENDENT RESURVEY OF THE SOUTH BOUNDARY,

AND THE SURVEY OF THE SEVENTH GUIDE MERIDIAN EAST (WEST BOUNDARY)

AND

THE SUBDIVISIONAL LINES,

TOWNSHIP 24 NORTH, RANGE 29 EAST,

OF THE GILA AND SALT RIVER MERIDIAN,

IN THE STATE OF ARIZONA

EXECUTED BY

Jones Curtiss, Cadastral Surveyor

Under Special Instructions dated and approved July 30, 2008, which provided for the surveys included under Group No. 1049, and assignment instructions dated July 30, 2008.

Survey commenced August 7, 2008

Survey completed December 10, 2008

INDEX DIAGRAM

TOWNSHIPS 25 NORTH, RANGES 28 AND 29 EAST
AND
TOWNSHIP 24 NORTH, RANGE 29 EAST
GILA AND SALT RIVER MERIDIAN, ARIZONA

SIXTH STANDARD PARALLEL NORTH

35 4	36 5	31 6	32 7	33 7	34 8	35 9					
	72	72	60	51	42	33					
22	6	70	5	58	4	50	3	41	2	32	1
	70	69	58	49	40	31					
21	7	68	8	57	9	48	10	39	11	30	12
	68	67	56	48	39	29					
20	18	66	17	56	16	47	15	38	14	28	13
	66	65	55	46	37	28					
19	19	64	20	54	21	45	22	36	23	27	24
	64	63	54	45	36	26					
18	30	62	29	53	28	44	27	35	26	25	25
	62	61	52	44	34	24					
17	31	60	32	51	33	42	34	34	35	23	36
	10	12	13	14	15	16					

**Tps. 25 N., Rs. 28 and 29 E. and
T. 24 N., R. 29 E., Gila and Salt River Meridian, Arizona**

CHAINS

The following field notes describe the dependent resurvey of portions of the Sixth Standard Parallel North (south boundary), Townships 25 North, Ranges 28 and 29 East and the dependent resurvey of the south boundary, and the survey of the Seventh Guide Meridian East (west boundary) and the subdivisional lines, Township 24 North, Range 29 East, Gila and Salt River Meridian, Arizona.

The history of surveys pertaining to this survey is as follows:

Frank Follman surveyed the Sixth Standard Parallel North (south boundary), Townships 25 North, Ranges 28 and 29 East, in 1883. Sidney E. Blout surveyed the east, west and north boundaries, Township 23 North, Range 29 East, in 1920. Loyd E. Sechrist and William D. Wilson surveyed the north boundary, Township 23 North, Range 30 East, in 1920. Loyd E. Sechrist and Sidney E. Blout resurveyed the Sixth Standard Parallel North (south boundary), Township 25 North, Range 28 East, in 1920-27. Sidney E. Blout resurveyed the Sixth Standard Parallel North (south boundary), Township 25 North, Range 29 East, in 1927. Kevin R. DeRossett dependently resurveyed the Sixth Standard Parallel North (south boundary), Township 25 North, Range 29 East, in 1985-86. Jones Curtiss dependently resurveyed a portion of the Sixth Standard Parallel North (south boundary), Township 25 North, Range 29 East, in 2001. Jones Curtiss and Leonard R. Sandoval surveyed the west boundary, Township 24 North, Range 30 East, in 2001.

The survey was executed in accordance with the specifications as set forth in the Manual of Instructions for the Survey of the Public Lands of the United States, 1973, and the Special Instructions dated July 30, 2008, for Group Number 1049, Arizona.

The true meridian direction and length of all lines were determined by real time kinematic global positioning system observations using Trimble Navigation 5700 model receivers.

Preliminary to the resurvey, the lines of the prior surveys were retraced and a search was made for all corners and other calls of record. Identified corners were remonumented in their original positions. Lost corners were reestablished and remonumented at proportionate positions based on the official record. The retracement data were thoroughly verified and only the true line field notes are given herein.

Geodetic control was derived from Global Positioning System (GPS) static observations post processed by National Geodetic Survey, Online Positioning User Service (OPUS), utilizing Continuously Operating Reference Stations (CORS) GRANTS NMDOT CORS ARP, SPIDERROCKAZ2005 CORS ARP and GRANTS_NM2006 CORS ARP. The NAD 83(CORS96)(EPOCH: 2002.0000)(EPOCH:2008.5211) geographic position of the southeast corner of the township is as follows:

**Tps. 25 N., Rs. 28 and 29 E. and
T. 24 N., R. 29 E., Gila and Salt River Meridian, Arizona**

CHAINS

Latitude: 35°25'40.79" N. Longitude: 109°12'34.60" W.

The mean magnetic declination is 10 1/2° E.

**Dependent Resurvey of a Portion of the
Sixth Standard Parallel North (South Boundary),
T. 25 N., R. 28 E., Gila and Salt River Meridian, Arizona**

Restoring the resurvey executed by
Lloyd E. Sechrist and Sidney E. Blout, in 1920-27

Beginning at the stan. cor. of secs. 34 and 35, monumented with an iron post, 2 ins. diam., firmly set, projecting 20 ins. above ground, in a scattered mound of stone, 3 ft. base, with brass cap mkd. SC T25N R28E S34 S35 1920.

from which the 1920 bearing trees

A ponderosa pine, 39 ins. diam., bears N. 79 1/2° E., 1.27 chs. dist., illegibly mkd. on a partially healed blaze.

A dead piñon, 13 ins. diam., bears N. 79 3/4° W., 93 lks. dist., mkd. SC BT on a partially healed blaze.

At the corner point

Reset the iron post, 36 ins. long, 24 ins. in ground, in a mound stone, 2 ft. base, to top.

Deposit a magnet, in a white plastic case, at the base of the iron post.

Add the marks 2008 to the brass cap.

N. 89°59' E., on the S. bdy. of sec. 35.

Over rolling land.

40.02

Point for the stan. 1/4 sec. cor. of sec. 35, at proportionate dist.; there is no remaining evidence of the 1920 cor.

Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.

**Dependent Resurvey of a Portion of the
Sixth Standard Parallel North (South Boundary),
T. 25 N., R. 28 E., Gila and Salt River Meridian, Arizona**

CHAINS	
	SC T 25 N R 28 E 1/4 S 35 <hr style="width: 10%; margin: auto;"/> 2008
	Deposit a magnet, in a white plastic case, at the base of the stainless steel post.
80.04	The stan. cor. of secs. 35 and 36, monumented with an iron post, 2 ins. diam., firmly set, projecting 12 ins. above ground, with brass cap mkd. SC T25N R28E S35 S36 1920. Add the marks 2008 to the brass cap. <hr style="width: 80%; margin: 10px auto;"/>
	S. 89°56' E., on the S. bdy. of sec. 36. Over rolling land.
6.10	Navajo Route 2010, a graded road, 18 ft. wide, bears S. 25° E. and N. 25° W.
40.01	Point for the stan. 1/4 sec. cor. of sec. 36, at proportionate dist.; there is no remaining evidence of the 1920 cor. Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.
	SC T 25 N R 28 E 1/4 S 36 <hr style="width: 10%; margin: auto;"/> 2008
	Deposit a magnet, in a white plastic case, at the base of the stainless steel post.
80.02	The stan. cor. of Tps. 25 N., Rs. 28 and 29 E., monumented with an iron post, 3 ins. diam., firmly set, projecting 15 ins. above ground, in a mound of stone, 4 ft. base, 1 ft. high, with brass cap mkd. SC T25N R28E R29E S36 S31 1920 1985. from which the remains of the 1920 bearing trees The root hole of a dead ponderosa pine, lying alongside, 20 ins. diam. at base, bears N. 27° E., 1.21 chs. dist., mkd. T25N R29E S SC BT on an open blaze.

**Dependent Resurvey of a Portion of the
Sixth Standard Parallel North (South Boundary),
T. 25 N., R. 28 E., Gila and Salt River Meridian, Arizona**

CHAINS

A piñon, 10 ins. diam., bears N. 56 3/4° W., 27 lks. dist., mkd. T25N R28E S36 SC BT on an open blaze.

and the 1985 bearing tree

A piñon, 9 ins. diam., bears N. 12 3/4° W., 45.5 lks. dist., mkd. X BT at the base on an open blaze.

Add the marks 2008 to the brass cap.

**Dependent Resurvey of a Portion of the
Sixth Standard Parallel North (South Boundary),
T. 25 N., R. 29 E., Gila and Salt River Meridian, Arizona**

Restoring the dependent resurvey executed by
Kevin R. DeRossett, in 1985-86

N. 89°57' E., on the S. bdy. of sec. 31.

Over rolling land through dense piñon and juniper.

39.99 The stan. 1/4 sec. cor. of sec. 31, monumented with a stainless steel post, 2 1/2 ins. diam., firmly set, projecting 11 ins. above ground, with brass cap mkd. SC T25N R29E 1/4 S31 1985.

from which the remaining 1927 bearing tree

A piñon, 12 ins. diam., bears N. 7 3/4° E., 1.61 chs. dist., mkd. 1/4 S31 SC BT on an open blaze.

At the corner point

Reset the stainless steel post, 28 ins. long, 21 ins. in the ground, in a mound of stone, 4 ft. base, to top.

Add the marks 2008 to the brass cap.

S. 89°59' E., beginning new measurement.

39.99 The stan. cor. of secs. 31 and 32, monumented with a stainless steel post, 2 1/2 ins. diam., firmly set, encircled with an embedded collar of stone, 3 ft. base, to top, with brass cap mkd. SC T25N R29E S31 S32 1985.

from which the 1985 bearing trees

An oak, 11 ins. diam. at base, bears N. 42 3/4° E., 1.115 chs. dist., mkd. T25N R29E S32 SC BT on an open blaze.

**Dependent Resurvey of a Portion of the
Sixth Standard Parallel North (South Boundary),
T. 25 N., R. 29 E., Gila and Salt River Meridian, Arizona**

CHAINS	
	<p>A dead ponderosa pine, 40 ins. diam., bears N. 10 1/2° W., 2.95 chs. dist., mkd. T25N R29E S31 SC BT on an open blaze.</p> <p>Add the marks 2008 to the brass cap.</p> <hr/> <p>East, on the S. bdy. of sec. 32.</p> <p>Over rolling land through dense piñon and juniper and scattered ponderosa pine.</p>
39.98	<p>The stan. 1/4 sec. cor. of sec. 32, monumented with iron post, 1 in. diam., firmly set, projecting 18 ins. above ground, in a mound of stone, 2 1/2 ft. base, 1 ft. high, with brass cap mkd. SC T25N R29E 1/4 S32 1927 1985.</p> <p>from which the 1927 bearing trees</p> <p>A piñon, 11 ins. diam., bears N. 6 1/2° E., 85 lks. dist., mkd. 1/4 S32 SC BT on a partially healed blaze.</p> <p>A piñon, 11 ins. diam. at base, bears N. 56° W., 1.355 chs. dist., with a healed blaze.</p> <p>Add the marks 2008 to the brass cap.</p> <hr/> <p>N. 89°59' E., beginning new measurement.</p>
39.98	<p>The stan. cor. of secs. 32 and 33, monumented with a stainless steel post, 2 1/2 ins. diam., firmly set, projecting 16 ins. above ground, in a mound of stone, 3 ft. base, to top, with brass cap mkd. SC T25N R29E S32 S33 1985.</p> <p>from which the 1927 bearing trees</p> <p>A ponderosa pine, 25 ins. diam., bears N. 3 1/2° E., 66 lks. dist., mkd. 25 29 S3 SC BT on a partially healed blaze.</p> <p>A piñon, 20 ins. diam., bears N. 46 1/4° W., 1.42 chs. dist., with a partially healed blaze.</p> <p>Add the marks 2008 to the brass cap.</p> <hr/> <p>N. 89°57' E., on the S. bdy. of sec. 33.</p> <p>Over rolling land through dense piñon and juniper and scattered ponderosa pine.</p>

**Dependent Resurvey of a Portion of the
Sixth Standard Parallel North (South Boundary),
T. 25 N., R. 29 E., Gila and Salt River Meridian, Arizona**

CHAINS	
40.01	<p>The stan. 1/4 sec. cor. of sec. 33, monumented with iron post, 1 in. diam., firmly set, projecting 10 ins. above ground, encircled with an embedded collar stone, 2 1/2 ft. base, with brass cap mkd. SC T25N R29E 1/4 S33 1927 1985.</p> <p>from which the 1927 bearing trees</p> <p style="padding-left: 40px;">A piñon, 14 ins. diam., bears N. 40° E., 29 lks. dist., with a healed blaze.</p> <p style="padding-left: 40px;">A piñon, 12 ins. diam., bears N. 78 3/4° W., 31 lks. dist., with a healed blaze.</p> <p>Add the marks 2008 to the brass cap.</p> <hr style="width: 20%; margin: 10px auto;"/> <p>N. 89°59' E., beginning new measurement.</p>
40.00	<p>The stan. cor. of secs. 33 and 34, monumented with a stainless steel post, 2 1/2 ins. diam., firmly set, projecting 24 ins. above ground, in a mound of stone, 4 ft. base, to top, with brass cap mkd. SC T25N R29E S33 S34 1985.</p> <p>from which the 1985 bearing tree</p> <p style="padding-left: 40px;">A ponderosa pine, 12 ins. diam., bears N. 10 1/2° W., 2.475 chs. dist., mkd. N R29E S33 SC BT on a partially healed blaze.</p> <p>Add the marks 2008 to the brass cap.</p> <hr style="width: 20%; margin: 10px auto;"/> <p>N. 89°59' E., on the S. bdy. of sec. 34.</p> <p>Over rolling land through dense piñon and juniper.</p>
39.97	<p>The stan. 1/4 sec. cor. of sec. 34, monumented with iron post, 1 in. diam., firmly set, projecting 6 ins. above ground, encircled with an embedded collar stone, with brass cap mkd. SC T25N R29E 1/4 S34 1927 1985.</p> <p>from which the 1927 bearing trees</p> <p style="padding-left: 40px;">A piñon, 12 ins. diam., bears N. 14 1/2° E., 78.5 lks. dist., with a healed blaze.</p> <p style="padding-left: 40px;">A forked piñon, 17 ins. diam. at base, bears N. 7° W., 80 lks. dist., with a healed blaze.</p>

**Dependent Resurvey of a Portion of the
Sixth Standard Parallel North (South Boundary),
T. 25 N., R. 29 E., Gila and Salt River Meridian, Arizona**

CHAINS	
	<p>Add the marks 2008 to the brass cap.</p> <hr style="width: 20%; margin: 10px auto;"/> <p>N. 89°59' E., beginning new measurement.</p>
40.00	<p>The stan. cor. of secs. 34 and 35, monumented with an iron post, 2 ins. diam., firmly set, projecting 18 ins. above ground, in a mound of stone, 3 ft. base, to top, with brass cap mkd. SC T25N R29E S34 S35 1927 1985.</p> <p>from which the remaining 1927 bearing tree</p> <p style="padding-left: 40px;">A ponderosa pine, 34 ins. diam., bears N. 74 1/4° W., 1.45 chs. dist., with a healed blaze.</p> <p>and the 1985 bearing tree</p> <p style="padding-left: 40px;">A ponderosa pine, 16 ins. diam., bears N. 36 3/4° W., 1.275 chs. dist., with a healed blaze.</p> <p>Add the marks 2008 to the brass cap.</p> <hr style="width: 20%; margin: 10px auto;"/> <p>S. 89°59' E., on the S. bdy. of sec. 35.</p> <p>Over rolling land through dense piñon and juniper and scattered ponderosa pine.</p>
39.97	<p>The stan. 1/4 sec. cor. of sec. 35, monumented with a stainless steel post, 2 1/2 ins. diam., firmly set, projecting 16 ins. above ground, in a mound of stone, 4 ft. base, 1 ft. high, with brass cap mkd. SC T25N R29E 1/4 S35 1985 2001.</p> <p>from which the 1927 bearing trees</p> <p style="padding-left: 40px;">A dead ponderosa pine, 17 ins. diam., bears N. 31 1/2° E., 69 lks. dist., mkd. 1/4 S35 SC BT on an open blaze.</p> <p style="padding-left: 40px;">A ponderosa pine, 28 ins. diam., bears N. 66 3/4° W., 60 lks. dist., with a healed blaze.</p> <p>and the 1985 bearing tree</p> <p style="padding-left: 40px;">A ponderosa pine, 15 ins. diam., bears N. 70 1/4° E., 95.5 lks. dist., with a healed blaze.</p> <p>Add the marks 2008 to the brass cap.</p>

**Dependent Resurvey of a Portion of the
Sixth Standard Parallel North (South Boundary),
T. 25 N., R. 29 E., Gila and Salt River Meridian, Arizona**

CHAINS

From this cor. point, the closing cor. of Tps. 24 N., Rs. 29 and 30 E., bears N. 89°59' E., 22.05 chs. dist., monumented with a stainless steel post, 2 1/2 ins. diam., firmly set, projecting 4 ins. above ground, with brass cap mkd. T25N R29E S35 S1 S6 R29E R30E T24N CC 2001.

**Dependent Resurvey of the South Boundary,
T. 24 N., R. 29 E., Gila and Salt River Meridian, Arizona**

Restoring the survey executed by
Sidney E. Blout, in 1920

From the cor. of Tps. 23 and 24 N., Rs. 28 and 29 E., monumented with an iron post, 3 ins. diam., firmly set, projecting 12 ins. above ground, with brass cap mkd. T24N R28E R29E S36 S31 S1 S6 T23N 1920.

from which the remains of the orig. bearing trees

A forked piñon, 19 ins. diam., bears N. 49 1/2° E., 43 lks. dist., mkd. T24N R29E S31 BT on an open blaze.

A dead piñon, 14 ins. diam., bears S. 69° E., 94 lks. dist., mkd. T23N R29E S6 BT on an open blaze.

A piñon stump, 14 ins. diam., 10 ins. high, bears S. 24 1/2° W., 60 lks. dist.

The root hole of a decaying piñon, lying alongside, 15 ins. diam., bears N. 75 1/4° W., 99 lks. dist., mkd. T24N R28E S36 BT.

Add the marks 2008 to the brass cap.

S. 89°55' E., bet. secs. 6 and 31.

Over rolling land through dense piñon and juniper.

36.83

The 1/4 sec. cor. of secs. 6 and 31, determined at record distances from the orig. bearing trees

A piñon, 12 ins. diam., bears N. 48 1/4° E., 32 lks. dist., mkd. 1/4 S31 BT on an open blaze.
(Record: N. 50° E.)

A piñon, 12 ins. diam., bears S. 38 1/2° E., 79 lks. dist., mkd. 1/4 S6 BT on an open blaze.
(Record: S. 37 1/4° E.)

**Dependent Resurvey of the South Boundary,
T. 24 N., R. 29 E., Gila and Salt River Meridian, Arizona**

CHAINS

At the corner point

Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam.,
24 ins. in the ground, with brass cap mkd.

T 24 N R 29 E
S 31
1/4 ———
S 6
T 23 N

2008

Deposit a magnet, in a white plastic case, at the base of the
stainless steel post.

N. 89°59' E., beginning new measurement.

- 6.50 Underground water line, bears S. 40° E. and N. 40° W.
- 7.30 Power line, 2 strand, bears S. 45° E. and N. 45° W.
- 8.10 Graded road, 20 ft. wide, bears S. 40° E. and N. 40° W.
- 39.98 The cor. of secs. 5, 6, 31 and 32, determined at record
distances from the remains of three orig. bearing trees
- A dead piñon, 12 ins. diam., bears N. 69 1/4° E., 25 lks.
dist., mkd. T24N R29E S32 BT on an open blaze.
(Record: N. 68 1/2° E.)
- A forked piñon, 18 ins. diam., bears S. 15 1/2° E.,
32 lks. dist., mkd. T23N R29E S5 BT on an open blaze.
- A juniper, 12 ins. diam., bears S. 58° W., 93.5 lks.
dist., mkd. 23N R29E S6 on a partially healed blaze.
(Record: 54 lks.)
- The root hole of a piñon, lying alongside, 7 ins. diam.,
bears N. 53° W., 74 lks. dist., mkd. T24N R29E S31 BT on
an open blaze.

At the corner point

Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam.,
24 ins. in the ground, with brass cap mkd.

Dependent Resurvey of the South Boundary,
T. 24 N., R. 29 E., Gila and Salt River Meridian, Arizona

CHAINS

T 24 N	R 29 E
S 31	S 32
S 6	S 5
T 23 N	

2008

Deposit a magnet, in a white plastic case, at the base of the stainless steel post.

N. 89°53' E., bet. secs. 5 and 32.

Over rolling land through dense piñon and juniper.

40.00

The 1/4 sec. cor. of secs. 5 and 32, determined at record distances from the orig. bearing trees

A piñon, 10 ins. diam., bears N. 12 1/4° E., 32 lks. dist., mkd. 1/4 S32 BT on an open blaze.
(Record: N. 11 3/4° E.)

A piñon, 17 ins. diam., bears S. 67 1/2° E., 56 lks. dist., mkd. 1/4 S5 BT on an open blaze.
(Record: S. 68 1/2° E.)

At the corner point

Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.

T 24 N	R 29 E
	S 32
1/4	—
	S 5
T 23 N	

2008

Deposit a magnet, in a white plastic case, at the base of the stainless steel post.

From this cor. point, a rebar, 5/8 in. diam., firmly set, projecting 4 ins. above ground, in a scattered mound of stone, bears N. 86° E., 2 lks. dist., with aluminum cap mkd. ASCG 3/06 APOTTS.

N. 89°56' E., beginning new measurement.

27.00

Navajo Route 2010, a graded road, 30 ft. wide, bears North and S.

**Dependent Resurvey of the South Boundary,
T. 24 N., R. 29 E., Gila and Salt River Meridian, Arizona**

CHAINS	
39.98	<p>The cor. of secs. 4, 5, 32 and 33, monumented with an iron post, 2 ins. diam., firmly set, projecting 13 ins. above ground, with a scattered mound of stone W., with brass cap mkd. T24N R29E S32 S33 S5 S4 T23N 1920.</p> <p>Add the marks 2008 to the brass cap.</p> <p>Rebuild the mound of stone, 2 ft. base, 1 ft. high, W. of cor.</p> <p>Cor. is located 53 lks. S. of a barded wire fence, 5 strand, bears N. 80° E. and S. 80° W., and 35 lks. N. of a trail road, bears East and West.</p> <hr/> <p>N. 89°46' E., bet. secs. 4 and 33.</p> <p>Over rolling land through dense piñon and juniper.</p>
39.98	<p>The 1/4 sec. cor. of secs. 4 and 33, determined at record distances from the orig. bearing trees</p> <p style="padding-left: 40px;">A piñon, 11 ins. diam., bears S. 43° W., 36 lks. dist., mkd. 1/4 S4 BT on an open blaze.</p> <p style="padding-left: 40px;">A dead piñon, 9 ins. diam., bears N. 54° W., 45 lks. dist., mkd. 1/4 S33 BT on an open blaze.</p> <p>At the corner point</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center; padding: 10px 0;"> <p>T 24 N R 29 E</p> <p style="padding-left: 40px;">S 33</p> <p style="padding-left: 20px;">1/4 ———</p> <p style="padding-left: 40px;">S 4</p> <p>T 23 N</p> <p style="padding-left: 40px;">2008</p> </div> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p> <hr/> <p>N. 89°45' E., beginning new measurement.</p>
20.90	<p>Power line, 2 strand, bears N. 25° E. and S. 25° W.</p>
23.00	<p>Navajo Route 25, a graded road, 25 ft. wide, bears N. 45° E. and S. 45° W.</p>

**Dependent Resurvey of the South Boundary,
T. 24 N., R. 29 E., Gila and Salt River Meridian, Arizona**

CHAINS	
40.00	<p>The cor. of secs. 3, 4, 33 and 34, monumented with an iron post, 2 ins. diam., firmly set, projecting 5 ins. above ground, with brass cap mkd. T24N R29E S33 S34 S4 S3 T23N and 1920.</p> <p>from which the orig. bearing trees</p> <p style="padding-left: 40px;">A piñon, 11 ins. diam., bears N. 33 3/4° E., 57 lks. dist., illegibly mkd. on a partially healed blaze.</p> <p style="padding-left: 40px;">A piñon, 7 ins. diam., bears S. 10 1/2° E., 29.5 lks. dist., with a healed blaze. (Record: S. 7 1/2° E., 46 lks.)</p> <p style="padding-left: 40px;">A piñon, 12 ins. diam., bears S. 40 1/2° W., 46 lks. dist., with a healed blaze. (Record: S. 39 3/4° W., 47 lks.)</p> <p style="padding-left: 40px;">A piñon, 9 ins. diam., bears N. 35 3/4° W., 55 lks. dist., mkd. T24N R29E S33 BT on an open blaze. (Record: N. 36 1/4° W.)</p> <p>Add the marks 2008 to the brass cap.</p> <hr/> <p>N. 89°42' E., bet. secs. 3 and 34.</p> <p>Over rolling land through dense piñon and juniper.</p>
40.01	<p>The 1/4 sec. cor. of secs. 3 and 34, monumented with an iron post, 1 in. diam., firmly set, projecting 28 ins. above ground, in a mound of stone, 4 ft. base, 1 1/2 ft. high, with brass cap mkd. 1/4 S34 S3 1920.</p> <p>from which the remains of the orig. bearing trees</p> <p style="padding-left: 40px;">A piñon, 10 ins. diam., bears N. 13 1/2° E., 1.055 chs. dist., mkd. 1/4 S34 B on an open blaze. (Record: N. 14° E., 1.05 chs.)</p> <p style="padding-left: 40px;">The root hole of a piñon, lying alongside, 10 ins. diam., bears S. 66 3/4° E., 64 lks. dist., mkd. 1/4 S3 BT on an open blaze. (Record: S. 65 1/2° E.)</p> <p>Add the marks T24N R29E T23N 2008 to the brass cap.</p> <hr/> <p>S. 89°58' E., beginning new measurement.</p>
39.93	<p>The cor. of secs. 2, 3, 34 and 35, determined at record distances from the remains of three orig. bearing trees</p>

**Dependent Resurvey of the South Boundary,
T. 24 N., R. 29 E., Gila and Salt River Meridian, Arizona**

CHAINS

A juniper, 8 ins. diam., bears N. 51 1/4° E., 29.5 lks. dist., mkd. T24N R29E S35 BT on an open blaze. (Record: N. 49° E., 25 lks.)

A juniper stump, 18 ins. diam. at top, 5 ft. high, bears S. 31 1/2° E., 68 lks. dist., mkd. S2 BT on an open blaze.

A juniper, 10 ins. diam., bears S. 40 1/2° W., 1.50 chs. dist., mkd. T23N R29E S3 BT on an open blaze.

A piñon, 14 ins. diam., bears N. 69 1/2° W., 72 lks. dist., illegibly mkd. on a partially healed blaze.

At the corner point

Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 20 ins. in the ground, to bedrock, in a mound of stone, 3 ft. base, to top, with brass cap mkd.

T 24 N	R 29 E
S 34	S 35
S 3	S 2
T 23 N	

2008

Deposit a magnet, in a white plastic case, at the base of the stainless steel post.

N. 89°55' E., bet. secs. 2 and 35.

Over broken land through dense piñon and juniper.

40.02

The 1/4 sec. cor. of secs. 2 and 35, monumented with an iron post, 1 in. diam., firmly set, projecting 20 ins. above ground, in a scattered mound of stone, with brass cap mkd. 1/4 S35 S2 1920.

from which the orig. bearing trees

A piñon, 9 ins. diam., bears N. 1° W., 42 lks. dist., mkd. 1/4 S35 BT on an open blaze.

A piñon, 10 ins. diam., bears S. 22° W., 41 lks. dist., mkd. 1/4 S2 BT on an open blaze. (Record: 40 lks.)

**Dependent Resurvey of the South Boundary,
T. 24 N., R. 29 E., Gila and Salt River Meridian, Arizona**

CHAINS	
	Add the marks T24N R29E T23N 2008 to the brass cap.

	N. 89°52' E., beginning new measurement.
9.20	W. rim of canyon, 200 ft. high, bears S. 50° E. and N. 50° W.
16.90	E. rim of canyon, 200 ft. high, bears S. 50° E. and N. 50° W.
39.94	The cor. of secs. 1, 2, 35 and 36, monumented with an iron post, 2 ins. diam., firmly set, projecting 36 ins. above ground, in a mound of stone, 4 ft. base, to top, with brass cap mkd. T24N R29E S35 S36 S2 S1 T23N 1920.
	from which the orig. bearing trees
	A juniper, 17 ins. diam., bears N. 75 3/4° E., 91 lks. dist., mkd. T24N R29E S36 BT on an open blaze.
	A piñon, 11 ins. diam., bears S. 41 1/2° E., 72.5 lks. dist., mkd. T23N R29E S1 BT on an open blaze. (Record: 71 lks.)
	A forked juniper, 13 ins. diam., bears S. 31° W., 54 lks. dist., mkd. T23N R29E S2 BT on an open blaze. (Record: S. 32° W., 53 lks.)
	A juniper, 12 ins. diam., bears N. 72° W., 1.10 chs. dist., mkd. T24N R29E on a partially healed blaze. (Record: N. 72 3/4° E., 1.19 chs.)
	Add the marks 2008 to the brass cap.
	Cor. is located 2.30 chs. W. of the W. rim of a canyon, bears N. 20° E. and S. 20° W.

	N. 89°51' E., bet. secs. 1 and 36.
	Over broken and rugged land, thence across West Fork Black Creek canyon.
28.40	E. rim of West Fork Black Creek canyon, bears N. 10° E. and S. 10° W.
40.00	The 1/4 sec. cor. of secs. 1 and 36, monumented with an iron post, 1 in. diam., firmly set, projecting 20 ins. above ground, with brass cap mkd. 1/4 S36 S1 1920.

**Dependent Resurvey of the South Boundary,
T. 24 N., R. 29 E., Gila and Salt River Meridian, Arizona**

CHAINS	
	<p>from which the remains of the orig. bearing trees</p> <p>The root hole of a decayed piñon, lying alongside, 10 ins. diam. at the blaze, bears S. 22 3/4° W., 5 lks. dist., mkd. 1/4 S1 BT on an open blaze. (Record: S. 10 1/4° E.)</p> <p>The root hole of a decayed piñon, lying alongside, in pieces, bears N. 17° W., 36 lks. dist., with reassembled pieces mkd. 1/4 S36. (Record: N. 8 1/4° W.)</p> <p>Add the marks T24N R29E T23N 2008 to the brass cap.</p> <hr/> <p>N. 89°49' E., beginning new measurement.</p>
32.60	Trail road, bears N. 35° E. and S. 35° W.
39.92	<p>The cor. of Tps 23 and 24 N., R. 29 E. only, monumented with an iron post, 3 ins. diam., firmly set, projecting 12 ins. above ground, with brass cap mkd. T24N T23N R29E R30E S36 S1 S6 T23N 1920 2001.</p> <p>from which the orig. bearing trees</p> <p>A dead piñon, 9 ins. diam., bears S. 48 W., 1.41 chs. dist., mkd. T23N R29E S1 BT on an open blaze.</p> <p>A piñon, 10 ins. diam., bears N. 70 1/2° W., 1.21 chs. dist., mkd. T24N R29E S36 BT on an open blaze. (Record: N. 70° W. (2001), 1.20 chs. (2001), 1.26 chs. (1920))</p> <p>Add the marks 2008 to the brass cap.</p> <hr/> <p align="center">Survey of the Seventh Guide Meridian East (West Boundary), T. 24 N., R. 29 E., Gila and Salt River Meridian, Arizona</p> <hr/> <p>From the cor. of Tps. 23 and 24 N., Rs. 28 and 29 E., hereinbefore described.</p> <p>North, bet. secs. 31 and 36.</p> <p>Over rolling land through dense piñon and juniper.</p>
40.00	<p>Point for the 1/4 sec. cor. of secs. 31 and 36.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p>

**Survey of the Seventh Guide Meridian East (West Boundary),
T. 24 N., R. 29 E., Gila and Salt River Meridian, Arizona**

CHAINS	
	T 24 N 1/4 R 28 E R 29 E S 36 S 31 2008 Deposit a magnet, in a white plastic case, at the base of the stainless steel post.
42.30	Underground water line, bears S. 45° E. and N. 45° W.
43.10	Power line, 2 strand, bears S. 45° E. and N. 45° W.
51.90	Trail road, bears S. 45° E. and N. 45° W.
68.30	Underground water line, bears N. 60° E. and S. 60° W.
80.00	Point for the cor. of secs. 25, 30, 31 and 36. Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 21 ins. in the ground, to bedrock, with brass cap mkd.
	T 24 N R 28 E R 29 E S 25 S 30 S 36 S 31 2008 Deposit a magnet, in a white plastic case, at the base of the stainless steel post. Land, rolling. Soil, sand and sandy clay. Timber, ponderosa pine, piñon, juniper; undergrowth, scrub oak, sagebrush and native grasses.
	North, bet. secs. 25 and 30. Over rolling land through dense piñon and juniper.
34.40	Underground water line, bears N. 75° E. and S. 75° W.
34.90	Trail road, bears N. 75° E. and S. 75° W.
40.00	Point for the 1/4 sec. cor. of secs. 25 and 30. Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.

**Survey of the Seventh Guide Meridian East (West Boundary),
T. 24 N., R. 29 E., Gila and Salt River Meridian, Arizona**

CHAINS	
	<p align="center">T 24 N 1/4 R 28 E R 29 E S 25 S 30</p> <p align="center">2008</p> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p> <p>From this cor. point, the SE cor. of a stucco house, 36.5 x 24 ft., bears S. 87°10' W., 78.5 lks. dist., with a 6 x 12 ft. addition to the NE, long side bears S. 84° W.</p>
80.00	<p>Point for the cor. of secs. 19, 24, 25 and 30.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 22 ins. in the ground, with brass cap mkd.</p>
	<p align="center">T 24 N R 28 E R 29 E S 24 S 19 S 25 S 30</p> <p align="center">2008</p> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p> <p>Cor. is located 1.50 chs. S. of a wash, 10 ft. wide, 1 ft. deep, drains N. 75° W.</p> <p>Land, rolling. Soil, sand and sandy clay. Timber, ponderosa pine, piñon, juniper; undergrowth, scrub oak, sagebrush and native grasses.</p>
	<p>North, bet. secs. 19 and 24.</p> <p>Over rolling and broken land through dense piñon and juniper.</p>
19.54	<p>Barbed wire fence, 5 strand, bears N. 55° E. and S. 55° W.</p>
40.00	<p>Point for the 1/4 sec. cor. of secs. 19 and 24.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 18 ins. in the ground, to bedrock, in a mound of stone, 4 ft. base, to top, with brass cap mkd.</p>

**Survey of the Seventh Guide Meridian East (West Boundary),
T. 24 N., R. 29 E., Gila and Salt River Meridian, Arizona**

CHAINS	
	<p align="center">T 24 N 1/4 R 28 E R 29 E S 24 S 19</p> <p align="center">2008</p> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p>
80.00	<p>Point for the cor. of secs. 13, 18, 19 and 24.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p align="center">T 24 N R 28 E R 29 E S 13 S 18 S 24 S 19</p> <p align="center">2008</p> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p> <p>Land, rolling and broken. Soil, sand and sandy clay. Timber, ponderosa pine, piñon, juniper; undergrowth, scrub oak, sagebrush and native grasses.</p> <hr/> <p>North, bet. secs. 13 and 18.</p> <p>Over rolling and broken land through dense piñon and juniper.</p>
40.00	<p>Point for the 1/4 sec. cor. of secs. 13 and 18.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p align="center">T 24 N 1/4 R 28 E R 29 E S 13 S 18</p> <p align="center">2008</p> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p> <p>Cor. is located 2.42 chs. W. of a barbed wire fence, 5 strand, bears S. 25° E. and N. 25° W.</p>

**Survey of the Seventh Guide Meridian East (West Boundary),
T. 24 N., R. 29 E., Gila and Salt River Meridian, Arizona**

CHAINS									
80.00	<p>Point for the cor. of secs. 7, 12, 13 and 18.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 21 ins. in the ground, encircled with a collar of stone, with brass cap mkd.</p> <table border="1" data-bbox="792 478 1036 613"> <tr><td colspan="2" style="text-align:center">T 24 N</td></tr> <tr><td style="text-align:center">R 28 E</td><td style="text-align:center">R 29 E</td></tr> <tr><td style="text-align:center">S 12</td><td style="text-align:center">S 7</td></tr> <tr><td style="text-align:center">S 13</td><td style="text-align:center">S 18</td></tr> </table> <p style="text-align:center">2008</p> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p> <p>Land, rolling and broken. Soil, sand and sandy clay. Timber, ponderosa pine, piñon, juniper; undergrowth, scrub oak, sagebrush, cacti, and native grasses.</p>	T 24 N		R 28 E	R 29 E	S 12	S 7	S 13	S 18
T 24 N									
R 28 E	R 29 E								
S 12	S 7								
S 13	S 18								
	<p>North, bet. secs. 7 and 12.</p> <p>Over rolling land through dense piñon and juniper and scattered ponderosa pine.</p>								
40.00	<p>Point for the 1/4 sec. cor. of secs. 7 and 12.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 18 ins. in the ground, in a mound of stone, 4 ft. base, to top, with brass cap mkd.</p> <table border="1" data-bbox="792 1318 1036 1432"> <tr><td colspan="2" style="text-align:center">T 24 N</td></tr> <tr><td colspan="2" style="text-align:center">1/4</td></tr> <tr><td style="text-align:center">R 28 E</td><td style="text-align:center">R 29 E</td></tr> <tr><td style="text-align:center">S 12</td><td style="text-align:center">S 7</td></tr> </table> <p style="text-align:center">2008</p> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p>	T 24 N		1/4		R 28 E	R 29 E	S 12	S 7
T 24 N									
1/4									
R 28 E	R 29 E								
S 12	S 7								
80.00	<p>Point for the cor. of secs. 1, 6, 7 and 12.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 22 ins. in the ground, encircled with a collar of stone, with brass cap mkd.</p>								

**Survey of the Seventh Guide Meridian East (West Boundary),
T. 24 N., R. 29 E., Gila and Salt River Meridian, Arizona**

CHAINS	
	<p align="center">T 24 N R 28 E R 29 E S 1 S 6 ----- S 12 S 7</p> <p align="center">2008</p> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p> <p>Land, rolling. Soil, sand and sandy clay. Timber, ponderosa pine, piñon, juniper; undergrowth, scrub oak, sagebrush, cacti, and native grasses.</p> <hr/> <p>North, bet. secs. 1 and 6.</p> <p>Over rolling land.</p>
40.00	<p>Point for the 1/4 sec. cor. of secs. 1 and 6.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 20 ins. in the ground, in a mound of stone, 4 ft. base, to top, with brass cap mkd.</p> <p align="center">T 24 N 1/4 R 28 E R 29 E S 1 S 6</p> <p align="center">2008</p> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p>
48.77	<p>Barbed wire fence, 5 strand, bears N. 75° E. and S. 75° W.</p>
80.00	<p>Point for the 80 1/16 sec. cor. of secs. 1 and 6.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 22 ins. in the ground, encircled with a collar of stone, with brass cap mkd.</p> <p align="center">T 24 N 1/16 R 28 E R 29 E S 1 S 6 80</p> <p align="center">2008</p>

**Survey of the Seventh Guide Meridian East (West Boundary),
T. 24 N., R. 29 E., Gila and Salt River Meridian, Arizona**

CHAINS

Deposit a magnet, in a white plastic case, at the base of the stainless steel post.

95.32

Point for the closing cor. of Tps. 24 N., Rs. 28 and 29 E., at intersection with the Sixth Standard Parallel North, on the N. bdy. of the Tp.

Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 20 ins. in the ground, in a mound of stone, 3 ft. base, to top, with brass cap mkd.

T 25 N	R 28 E
S 35	
S 1	S 6
R 28 E	R 29 E
T 24 N	
CC	

2008

Deposit a magnet, in a white plastic case, at the base of the stainless steel post.

Cor. is located 1.00 ch. S. of a trail road, bears N. 60° E. and S. 60° W.

From this cor. point, the stan. cor. of secs. 35 and 36, T. 25 N., R. 28 E., bears N. 89°59' E., 14.12 chs. dist., hereinbefore described.

From this same cor. point, the stan. 1/4 sec. cor. of sec. 35, T. 25 N., R. 28 E., bears S. 89°59' W., 25.90 chs. dist., hereinbefore described.

Land, rolling.

Soil, sandy clay and rocky.

Timber, ponderosa pine, piñon, juniper; undergrowth, scrub oak, sagebrush, cacti, and native grasses.

**Survey of the Subdivisional Lines,
T. 24 N., R. 29 E., Gila and Salt River Meridian, Arizona**

From the cor. of secs. 1, 2, 35 and 36, on the S. bdy. of the Tp., hereinbefore described.

N. 0°01' W., bet. secs. 35 and 36.

Over broken and rugged land, thence across canyons.

40.00

Point for the 1/4 sec. cor. of secs. 35 and 36.

**Survey of the Subdivisional Lines,
T. 24 N., R. 29 E., Gila and Salt River Meridian, Arizona**

CHAINS	
	<p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 22 ins. in the ground, encircled with a collar of stone, with brass cap mkd.</p> <p style="text-align: center;">T 24 N R 29 E 1/4 S 35 S 36</p> <p style="text-align: center;">2008</p> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p> <p>Cor. is located 1.30 chs. N. of the rim of a canyon, 200 ft. high, bears S. 70° E. and N. 70° W.</p>
68.00	Trail road, bears S. 45° E. and N. 45° W.
80.00	Point for the cor. of secs. 25, 26, 35 and 36.
	<p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T 24 N R 29 E S 26 S 25 S 35 S 36</p> <p style="text-align: center;">2008</p> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p> <p>Land, broken and rugged. Soil, sandy clay and rocky. Timber, ponderosa pine, piñon, juniper; undergrowth, scrub oak, sagebrush, cacti, and native grasses.</p> <hr/> <p>From the cor. of secs. 25 and 36 only, T. 24 N., R. 29 E., on the E. bdy. of the Tp., monumented with a stainless steel post, 2 1/2 ins. diam., firmly set, projecting 6 ins. above ground, with brass cap mkd. T24N S25 S36 R29E on the W. half and T24N R30E S31 on the E. half 2001.</p> <p>Add the marks 2008 to the brass cap.</p> <p>S. 89°50' W., bet. secs. 25 and 36.</p> <p>Over rolling land, thence across West Fork Black Creek canyon.</p>
1.40	Trail road, bears N. 10° E. and S. 10° W.

**Survey of the Subdivisional Lines,
T. 24 N., R. 29 E., Gila and Salt River Meridian, Arizona**

CHAINS	
25.80	E. rim of West Fork Black Creek canyon, 250 ft. high, bears S. 55° E. and N. 55° W.
39.96	Point for the 1/4 sec. cor. of secs. 25 and 36. Set a brass tablet, 3 1/4 ins. diam., 3 1/2 ins. stem, cemented in a drill hole in exposed bedrock, with top mkd. <div style="text-align: center;"> T 24 N R 29 E S 25 1/4 ——— S 36 2008 </div> Deposit a magnet, in a white plastic case, in the drill hole, beneath the brass tablet. Cor. is located 60 lks. W. of the W. rim of West Fork Black Creek canyon, 250 ft. high, bears S. 35° E. and N. 35° W.
79.92	The cor. of secs. 25, 26, 35 and 36. Land, rolling and broken. Soil, sandy clay and rocky. Timber, ponderosa pine, piñon, juniper; undergrowth, scrub oak, sagebrush, cacti, and native grasses. <hr/>
	N. 0°01' W., bet. secs. 25 and 26. Over rolling land through dense piñon and juniper.
40.00	Point for the 1/4 sec. cor. of secs. 25 and 26. Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd. <div style="text-align: center;"> T 24 N R 29 E 1/4 S 26 S 25 2008 </div> Deposit a magnet, in a white plastic case, at the base of the stainless steel post.
80.00	Point for the cor. of secs. 23, 24, 25 and 26. Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 22 ins. in the ground, encircled with a collar of stone, with brass cap mkd.

**Survey of the Subdivisional Lines,
T. 24 N., R. 29 E., Gila and Salt River Meridian, Arizona**

CHAINS									
	<table style="margin: auto;"> <tr><td>T 24 N</td><td>R 29 E</td></tr> <tr><td>S 23</td><td>S 24</td></tr> <tr><td>S 26</td><td>S 25</td></tr> </table>	T 24 N	R 29 E	S 23	S 24	S 26	S 25		
T 24 N	R 29 E								
S 23	S 24								
S 26	S 25								
	2008								
	Deposit a magnet, in a white plastic case, at the base of the stainless steel post.								
	Land, rolling. Soil, sand and sandy clay. Timber, piñon, juniper; undergrowth, sagebrush, cacti, and native grasses.								
	From the cor. of secs. 24 and 25 only, T. 24 N., R. 29 E., on the E. bdy. of the Tp., monumented with a stainless steel post, 2 1/2 ins. diam., firmly set, projecting 6 ins. above ground, with brass cap mkd. T24N S24 S25 R29E on the W. half and T24N R30E S30 on the E. half 2001.								
	Add the marks 2008 to the brass cap.								
	S. 89°50' W., bet. secs. 24 and 25.								
	Over broken land, thence across East Fork Black Creek canyon.								
4.90	N. rim of West Fork Black Creek canyon, 300 ft. high, bears S. 65° E. and N. 65° W.								
19.20	N. rim of West Fork Black Creek canyon, 300 ft. high, bears N. 40° E. and S. 40° W.								
39.96	Point for the 1/4 sec. cor. of secs. 24 and 25. Set a brass tablet, 3 1/4 ins. diam., 3 1/2 ins. stem, cemented in a drill hole in exposed bedrock, with top mkd.								
	<table style="margin: auto;"> <tr><td>T 24 N</td><td>R 29 E</td></tr> <tr><td>S 24</td><td></td></tr> <tr><td>1/4</td><td>—</td></tr> <tr><td>S 25</td><td></td></tr> </table>	T 24 N	R 29 E	S 24		1/4	—	S 25	
T 24 N	R 29 E								
S 24									
1/4	—								
S 25									
	2008								
	Deposit a magnet, in a white plastic case, in the drill hole, beneath the brass tablet.								
	Cor. is located 2.15 chs. W. of a trail road, bears S. 40° E. and N. 40° W.								
79.92	The cor. of secs. 23, 24, 25 and 26.								

**Survey of the Subdivisional Lines,
T. 24 N., R. 29 E., Gila and Salt River Meridian, Arizona**

CHAINS	
	<p>Land, rolling and broken. Soil, sandy clay and rocky. Timber, ponderosa pine, piñon, juniper; undergrowth, sagebrush, scrub oak, cacti and native grasses.</p> <hr/> <p>N. 0°01' W., bet. secs. 23 and 24.</p> <p>Over rolling land through dense piñon and juniper.</p>
40.00	<p>Point for the 1/4 sec. cor. of secs. 23 and 24.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 23 ins. in the ground, encircled with a collar of stone, with brass cap mkd.</p> <div style="text-align: center;"> <p>T 24 N R 29 E 1/4 S 23 S 24</p> <p>2008</p> </div> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p> <p>Cor. is located 1.60 chs. E. of a trail road, bears North and South, and 3.31 chs. E. of a barbed wire fence, 5 strand, bears N. 25° E. and S. 25° W.</p>
80.00	<p>Point for the cor. of secs. 13, 14, 23 and 24.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 22 ins. in the ground, encircled with a collar of stone, with brass cap mkd.</p> <div style="text-align: center;"> <p>T 24 N R 29 E S 14 S 13 S 23 S 24</p> <p>2008</p> </div> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p>

**Survey of the Subdivisional Lines,
T. 24 N., R. 29 E., Gila and Salt River Meridian, Arizona**

CHAINS	
	<p>Land, rolling. Soil, sand and sandy clay. Timber, piñon, juniper; undergrowth, sagebrush, cacti, and native grasses.</p> <hr/> <p>From the cor. of secs. 13 and 24 only, T. 24 N., R. 29 E., on the E. bdy. of the Tp., monumented with a stainless steel post, 2 1/2 ins. diam., firmly set, projecting 4 ins. above ground, with brass cap mkd. T24N S13 S24 R29E on the W. half and T24N R30E S19 on the E. half 2001.</p> <p>Add the marks 2008 to the brass cap.</p> <p>Cor. is located 70 lks. N. of the N. rim of West Fork Black Creek, bears S. 40° E. and N. 40° W.</p> <p>S. 89°50' W., bet. secs. 13 and 24.</p> <p>Over broken land, thence across West Fork Black Creek canyon.</p>
6.30	W. rim of West Fork Black Creek canyon, 150 ft. high, bears S. 60° E. and N. 60° W.
39.96	<p>Point for the 1/4 sec. cor. of secs. 13 and 24.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 22 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center;"> <p>T 24 N R 29 E</p> <p>S 13</p> <p>1/4 ———</p> <p>S 24</p> <p>2008</p> </div> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p>
55.66	Barbed wire fence, 5 strand, bears N. 30° E. and S. 30° W.
64.20	Trail road, bears S. 30° E. and N. 30° W.
79.92	<p>The cor. of secs. 13, 14, 23 and 24.</p> <p>Land, broken. Soil, sandy clay and rocky. Timber, ponderosa pine, piñon, juniper; undergrowth, sagebrush, scrub oak, cacti and native grasses.</p> <hr/> <p>N. 0°01' W., bet. secs. 13 and 14.</p>

**Survey of the Subdivisional Lines,
T. 24 N., R. 29 E., Gila and Salt River Meridian, Arizona**

CHAINS	
	Over rolling land.
34.00	Power line, 2 strand, bears S. 30° E. and N. 30° W.
36.50	Navajo Route 25, a graded road, 22 ft. wide, bears N. 65° E. and S. 65° W.
40.00	Point for the 1/4 sec. cor. of sec. 13 and 14. Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 18 ins. in the ground, encircled with a collar of stone, with brass cap mkd. <div style="text-align: center;"> T 24 N R 29 E 1/4 S 14 S 13 2008 </div>
	Deposit a magnet, in a white plastic case, at the base of the stainless steel post.
	Cor. is located 65 lks. N. of a trail road, bears S. 45° E. and N. 45° W.
80.00	Point for the cor. of secs. 11, 12, 13 and 14. Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd. <div style="text-align: center;"> T 24 N R 29 E S 11 S 12 S 14 S 13 2008 </div>
	Deposit a magnet, in a white plastic case, at the base of the stainless steel post.
	Cor. is located 1.00 ch. E. of a trail road, bears N. 15° E. and S. 15° W.
	Land, rolling. Soil, sand and sandy. Timber, ponderosa pine, piñon, juniper; undergrowth, sagebrush, scrub oak, cacti and native grasses.
	From the cor. of secs. 12 and 13 only, T. 24 N., R. 29 E., on the E. bdy. of the Tp., monumented with a stainless steel post, 2 1/2 ins. diam., firmly set, projecting 4 ins. above ground, with brass cap mkd. T24N S12 S13 R29E on the W. half and T24N R30E S18 on the E. half 2001.

**Survey of the Subdivisional Lines,
T. 24 N., R. 29 E., Gila and Salt River Meridian, Arizona**

CHAINS	
	<p>Add the marks 2008 to the brass cap.</p> <p>S. 89°50' W., bet. secs. 12 and 13.</p> <p>Over rolling and broken land through dense piñon and juniper, thence across canyon.</p>
24.30	E. rim of West Fork Black Creek canyon, 100 ft. high, bears N. 5° E. and S. 5° W.
28.20	W. rim of West Fork Black Creek canyon, 60 ft. high, bears S. 5° E. and N. 5° W.
39.96	<p>Point for the 1/4 sec. cor. of secs. 12 and 13.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 22 ins. in the ground, encircled with a collar of stone, with brass cap mkd.</p> <div style="text-align: center;"> <p>T 24 N R 29 E</p> <p>S 12</p> <p>1/4 ———</p> <p>S 13</p> <p>2008</p> </div> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p>
79.92	<p>The cor. of secs. 11, 12, 13 and 14.</p> <p>Land, rolling and broken.</p> <p>Soil, sandy clay and rocky.</p> <p>Timber, ponderosa pine, piñon, juniper; undergrowth, sagebrush, scrub oak, cacti and native grasses.</p> <hr/> <p>N. 0°01' W., bet. secs. 11 and 12.</p> <p>Over rolling land.</p>
35.00	Trail road, bears S. 85° E. and N. 85° W.
40.00	<p>Point for the 1/4 sec. cor. of secs. 11 and 12.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 14 ins. in the ground, to bedrock, in a mound of stone, 4 ft. base, to top, with brass cap mkd.</p>

**Survey of the Subdivisional Lines,
T. 24 N., R. 29 E., Gila and Salt River Meridian, Arizona**

CHAINS	
	T 24 N R 29 E 1/4 S 11 S 12 2008
	Deposit a magnet, in a white plastic case, at the base of the stainless steel post.
80.00	Point for the cor. of secs. 1, 2, 11 and 12. Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.
	T 24 N R 29 E S 2 S 1 S 11 S 12 2008
	Deposit a magnet, in a white plastic case, at the base of the stainless steel post.
	Land, rolling. Soil, sandy clay and rocky. Timber, ponderosa pine, piñon, juniper; undergrowth, sagebrush, scrub oak, cacti and native grasses.
	<hr/> From the cor. of secs. 1 and 12 only, T. 24 N., R. 29 E., on the E. bdy. of the Tp., monumented with a stainless steel post, 2 1/2 ins. diam., firmly set, projecting 15 ins. above ground, in a mound of stone, 3 ft. base, to top, with brass cap mkd. T24N S1 S12 R29E on the W. half and T24N R30E S7 on the E. half 2001.
	Add the marks 2008 to the brass cap.
	S. 89°50' W., bet. secs. 1 and 12.
	Over rolling land through dense piñon and juniper.
39.96	Point for the 1/4 sec. cor. of secs. 1 and 12. Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.
	T 24 N R 29 E S 1 1/4 ——— S 12 2008

**Survey of the Subdivisional Lines,
T. 24 N., R. 29 E., Gila and Salt River Meridian, Arizona**

CHAINS	
	Deposit a magnet, in a white plastic case, at the base of the stainless steel post.
54.30	Trail road, bears N. 55° E. and S. 55° W.
79.92	The cor. of secs. 1, 2, 11 and 12. Land, rolling. Soil, sand and sandy clay. Timber, ponderosa pine, piñon, juniper; undergrowth, sagebrush, scrub oak, cacti and native grasses.
	N. 0°01' W., bet. secs. 1 and 2.
	Over rolling and broken land through scattered piñon, juniper and ponderosa pine.
40.00	Point for the 1/4 sec. cor. of secs. 1 and 2. Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.
	T 24 N R 29 E 1/4 S 2 S 1 2008
	Deposit a magnet, in a white plastic case, at the base of the stainless steel post.
64.20	Trail road, bears S. 60° E. and N. 60° W.
68.20	S. bank of wash, 35 ft. high, bears N. 85° E. and S. 85° W.
68.90	Wash, 25 ft. wide, 35 ft. deep, drains N. 80° E.
80.00	Point for the 80 1/16 sec. cor. of secs. 1 and 2. Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 13 ins. in the ground, in a mound of stone, 3 ft. base, to top, with brass cap mkd.
	T 24 N R 29 E 1/16 S 2 S 1 80 2008
	Deposit a magnet, in a white plastic case, at the base of the stainless steel post.

**Survey of the Subdivisional Lines,
T. 24 N., R. 29 E., Gila and Salt River Meridian, Arizona**

CHAINS

94.58

Point for the closing cor. of secs. 1 and 2, at intersection with the Sixth Standard Parallel North, on the N. bdy. of the Tp.

Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.

T 25 N	R 29 E
S 34	
S 2	S 1
T 24 N	R 29 E
CC	

2008

Deposit a magnet, in a white plastic case, at the base of the stainless steel post.

From this cor. point, the stan. cor. of secs. 34 and 35, T. 25 N., R. 29 E., bears N. 89°59' E., 17.91 chs. dist., hereinbefore described.

From this same cor. point, the stan. 1/4 sec. cor. of sec. 34, T. 25 N., R. 29 E., bears S. 89°59' W., 22.09 chs. dist., hereinbefore described.

Land, rolling and broken.

Soil, sandy clay and rocky.

Timber, ponderosa pine, piñon, juniper; undergrowth, scrub oak, sagebrush, cacti, and native grasses.

Point for the 1/4 sec. cor of sec. 1 only, T. 24 N., R. 29 E., at midpoint on the N. bdy. of sec. 1.

Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 18 ins. in the ground, in a mound of stone, 3 ft. base, to top, with brass cap mkd.

T 25 N	R 29 E
1/4 S 1	
T 24 N	R 29 E

2008

Deposit a magnet, in a white plastic case, at the base of the stainless steel post.

From this cor. point, the stan. 1/4 sec. cor. of sec. 35, T. 25 N., R. 29 E., bears S. 89°59' E., 17.915 chs. dist., hereinbefore described.

**Survey of the Subdivisional Lines,
T. 24 N., R. 29 E., Gila and Salt River Meridian, Arizona**

CHAINS

From this same cor. point, the stan. cor. of secs. 34 and 35, T. 25 N., R. 29 E., bears N. 89°59' W., 22.055 chs. dist., hereinbefore described.

From the cor. of secs. 2, 3, 34 and 35, on the S. bdy. of the Tp., hereinbefore described.

N. 0°01' W., bet. secs. 34 and 35.

Over rolling land through dense piñon and juniper.

40.00 Point for the 1/4 sec. cor. of secs. 34 and 35.

Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.

T 24 N R 29 E
1/4
S 34 | S 35

2008

Deposit a magnet, in a white plastic case, at the base of the stainless steel post.

80.00 Point for the cor. of secs. 26, 27, 34 and 35.

Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 18 ins. in the ground, to bedrock, in a mound of stone, 3 ft. base, to top, with brass cap mkd.

T 24 N R 29 E
S 27 | S 26
S 34 | S 35

2008

Deposit a magnet, in a white plastic case, at the base of the stainless steel post.

Land, rolling.

Soil, sand and sandy clay.

Timber, ponderosa pine, piñon, juniper; undergrowth, scrub oak, sagebrush, cacti, and native grasses.

From the cor. of secs. 25, 26, 35 and 36.

S. 89°53' W., bet. secs. 26 and 35.

Over rolling land through dense piñon and juniper.

**Survey of the Subdivisional Lines,
T. 24 N., R. 29 E., Gila and Salt River Meridian, Arizona**

CHAINS	
10.30	Trail road, bears S. 50° E. and N. 50° W.
23.09	Barbed wire fence, 5 strand, bears S. 40° E. and N. 40° W.
39.98	Point for the 1/4 sec. cor. of secs. 26 and 35. Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 23 ins. in the ground, to bedrock, encircled with a collar of stone, with brass cap mkd. <div style="text-align: center;"> T 24 N R 29 E S 26 1/4 ——— S 35 2008 </div>
79.96	Deposit a magnet, in a white plastic case, at the base of the stainless steel post. The cor. of secs. 26, 27, 34 and 35. Land, rolling. Soil, sand and sandy clay. Timber, ponderosa pine, piñon, juniper; undergrowth, scrub oak, sagebrush, cacti, and native grasses. <hr/> N. 0°01' W., bet. secs. 26 and 27. Over rolling land through dense piñon and juniper.
40.00	Point for the 1/4 sec. cor. of secs. 26 and 27. Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd. <div style="text-align: center;"> T 24 N R 29 E 1/4 S 27 S 26 2008 </div>
80.00	Deposit a magnet, in a white plastic case, at the base of the stainless steel post. Cor. is located 2.40 chs. S. of a trail road, bears S. 55° E. and N. 55° W. Point for the cor. of secs. 22, 23, 26 and 27. Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 23 ins. in the ground, with brass cap mkd.

**Survey of the Subdivisional Lines,
T. 24 N., R. 29 E., Gila and Salt River Meridian, Arizona**

CHAINS									
	<table border="0"> <tr> <td>T 24 N</td> <td>R 29 E</td> </tr> <tr> <td>S 22</td> <td>S 23</td> </tr> <tr> <td>S 27</td> <td>S 26</td> </tr> </table>	T 24 N	R 29 E	S 22	S 23	S 27	S 26		
T 24 N	R 29 E								
S 22	S 23								
S 27	S 26								
	2008								
	Deposit a magnet, in a white plastic case, at the base of the stainless steel post.								
	Land, rolling. Soil, sand and sandy clay. Timber, ponderosa pine, piñon, juniper; undergrowth, scrub oak, sagebrush, cacti, and native grasses.								
	<hr/>								
	From the cor. of secs. 23, 24, 25 and 26.								
	S. 89°53' W., bet. secs. 23 and 26.								
	Over rolling land through dense piñon and juniper.								
36.95	Barbed wire fence, 5 strand, bears N. 25° E. and S. 25° W.								
39.98	Point for the 1/4 sec. cor. of secs. 23 and 26.								
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 23 ins. in the ground, to bedrock, encircled with a collar of stone, with brass cap mkd.								
	<table border="0"> <tr> <td>T 24 N</td> <td>R 29 E</td> </tr> <tr> <td></td> <td>S 23</td> </tr> <tr> <td>1/4</td> <td>—</td> </tr> <tr> <td></td> <td>S 26</td> </tr> </table>	T 24 N	R 29 E		S 23	1/4	—		S 26
T 24 N	R 29 E								
	S 23								
1/4	—								
	S 26								
	2008								
	Deposit a magnet, in a white plastic case, at the base of the stainless steel post.								
79.96	The cor. of secs. 22, 23, 26 and 27.								
	Land, rolling. Soil, sand and sandy clay. Timber, ponderosa pine, piñon, juniper; undergrowth, scrub oak, sagebrush, cacti, and native grasses.								
	<hr/>								
	N. 0°01' W., bet. secs. 22 and 23.								
	Over rolling and broken land through dense piñon and juniper and scattered ponderosa pine.								
40.00	Point for the 1/4 sec. cor. of secs. 22 and 23.								

**Survey of the Subdivisional Lines,
T. 24 N., R. 29 E., Gila and Salt River Meridian, Arizona**

CHAINS	
	<p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T 24 N R 29 E 1/4 S 22 S 23</p> <p style="text-align: center;">2008</p> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p>
80.00	<p>Point for the cor. of secs. 14, 15, 22 and 23.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 18 ins. in the ground, in a mound of stone, 4 ft. base, to top, with brass cap mkd.</p> <p style="text-align: center;">T 24 N R 29 E S 15 S 14 S 22 S 23</p> <p style="text-align: center;">2008</p> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p> <p>Land, rolling and broken. Soil, sand and sandy clay. Timber, ponderosa pine, piñon, juniper; undergrowth, scrub oak, sagebrush, cacti, and native grasses.</p> <hr/> <p>From the cor. of secs. 13, 14, 23 and 24.</p> <p>S. 89°53' W., bet. secs. 14 and 23.</p> <p>Over broken land through scattered piñon, juniper and ponderosa pine.</p>
39.98	<p>Point for the 1/4 sec. cor. of secs. 14 and 23.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, encircled with a collar of stone, with brass cap mkd.</p> <p style="text-align: center;">T 24 N R 29 E S 14 1/4 ——— S 23</p> <p style="text-align: center;">2008</p>

**Survey of the Subdivisional Lines,
T. 24 N., R. 29 E., Gila and Salt River Meridian, Arizona**

CHAINS	
	Deposit a magnet, in a white plastic case, at the base of the stainless steel post.
79.96	The cor. of secs. 14, 15, 22 and 23. Land, broken. Soil, sand and sandy clay. Timber, ponderosa pine, piñon, juniper; undergrowth, scrub oak, sagebrush, cacti, and native grasses.
	N. 0°01' W., bet. secs. 14 and 15. Over rolling land.
13.50	Navajo Route 25, a graded road, 21 ft. wide, bears N. 65° E. and S. 65° W.
15.60	Power line, 2 strand, bears N. 65° E. and S. 65° W.
36.29	Barbed wire fence, 3 strand, bears S. 35° E. and N. 35° W., thence enter cultivated field.
40.00	Point for the 1/4 sec. cor. of secs. 14 and 15. Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd. <div style="text-align: center;"> T 24 N R 29 E 1/4 S 15 S 14 2008 </div>
	Deposit a magnet, in a white plastic case, at the base of the stainless steel post. Cor. is located 84 lks. N. of a barbed wire, 3 strand, enclosing a cultivated field, bears N. 60° E. and S. 60° W.
66.80	Trail road, bears S. 55° E. and N. 55° W.
80.00	Point for the cor. of secs. 10, 11, 14 and 15. Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd. <div style="text-align: center;"> T 24 N R 29 E S 10 S 11 S 15 S 14 2008 </div>

**Survey of the Subdivisional Lines,
T. 24 N., R. 29 E., Gila and Salt River Meridian, Arizona**

CHAINS	
	<p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p> <p>Land, rolling. Soil, sand and sandy clay. Timber, ponderosa pine, piñon, juniper; undergrowth, scrub oak, sagebrush, cacti, and native grasses.</p> <hr/> <p>From the cor. of secs. 11, 12, 13 and 14.</p> <p>S. 89°53' W., bet. secs. 11 and 14.</p> <p>Over rolling land.</p>
39.98	<p>Point for the 1/4 sec. cor. of secs. 11 and 14.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 20 ins. in the ground, to bedrock, encircled with a collar of stone, with brass cap mkd.</p> <div style="text-align: center;"> <p>T 24 N R 29 E</p> <p>S 11</p> <p>1/4 ———</p> <p>S 14</p> <p>2008</p> </div> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p> <p>Cor. is located 80 lks. N. of trail road, bears N. 50° E. and S. 50° W.</p>
79.96	<p>The cor. of secs. 10, 11, 14 and 15.</p> <p>Land, rolling. Soil, sand and sandy clay. Timber, ponderosa pine, piñon, juniper; undergrowth, scrub oak, sagebrush, cacti, and native grasses.</p> <hr/> <p>N. 0°01' W., bet. secs. 10 and 11.</p> <p>Over rolling land through dense piñon and juniper and scattered ponderosa pine.</p>
40.00	<p>Point for the 1/4 secs. cor. of secs. 10 and 11.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p>

**Survey of the Subdivisional Lines,
T. 24 N., R. 29 E., Gila and Salt River Meridian, Arizona**

CHAINS	
	T 24 N R 29 E 1/4 S 10 S 11 2008
	Deposit a magnet, in a white plastic case, at the base of the stainless steel post.
80.00	Point for the cor. of secs. 2, 3, 10 and 11. Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 21 ins. in the ground, to bedrock, encircled with a collar of stone, with brass cap mkd.
	T 24 N R 29 E S 3 S 2 S 10 S 11 2008
	Deposit a magnet, in a white plastic case, at the base of the stainless steel post.
	Land, rolling. Soil, sand and sandy clay. Timber, ponderosa pine, piñon, juniper; undergrowth, scrub oak, sagebrush, cacti, and native grasses.
	<hr/> From the cor. of secs. 1, 2, 11 and 12. S. 89°53' W., bet. secs. 2 and 11.
39.98	Point for the 1/4 sec. cor. of secs. 2 and 11. Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 22 ins. in the ground, to bedrock, in a mound of stone, 3 ft. base, to top, with brass cap mkd.
	T 24 N R 29 E S 2 1/4 ——— S 11 2008
	Deposit a magnet, in a white plastic case, at the base of the stainless steel post.
71.10	Trail road, bears S. 55° E. and N. 55° W.
79.96	The cor. of secs. 2, 3, 10 and 11.

**Survey of the Subdivisional Lines,
T. 24 N., R. 29 E., Gila and Salt River Meridian, Arizona**

CHAINS	
	<p>Land, rolling. Soil, sand and sandy clay. Timber, ponderosa pine, piñon, juniper; undergrowth, scrub oak, sagebrush, cacti, and native grasses.</p> <hr/> <p>N. 0°01' W., bet. secs. 2 and 3.</p> <p>Over rolling land through scattered piñon, juniper and ponderosa pine.</p>
7.50	Trail road, bears S. 55° E. and N. 55° W.
40.00	<p>Point for the 1/4 sec. cor. of secs. 2 and 3.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T 24 N R 29 E 1/4 S 3 S 2 2008</p> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p> <p>Cor. is located 60 lks. S. of a trail road, bears S. 85° E. and N. 85° W.</p>
80.00	<p>Point for the 80 1/16 sec. cor. of secs. 2 and 3.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 21 ins. in the ground, to bedrock, encircled with a collar of stone, with brass cap mkd.</p> <p style="text-align: center;">T 24 N R 29 E 1/16 S 3 S 2 80 2008</p> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p>
94.72	<p>Point for the closing cor. of secs. 2 and 3, at intersection with the Sixth Standard Parallel North, on the N. bdy. of the Tp.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p>

**Survey of the Subdivisional Lines,
T. 24 N., R. 29 E., Gila and Salt River Meridian, Arizona**

CHAINS

T 25 N R 29 E
 S 33
 —————
 S 3 | S 2
 T 24 N R 29 E
 CC

2008

Deposit a magnet, in a white plastic case, at the base of the stainless steel post.

From this cor. point, the stan. cor. of secs. 33 and 34, T. 25 N., R. 29 E., bears N. 89°59' E., 17.90 chs. dist., hereinbefore described.

From this same cor. point, the stan. 1/4 sec. cor. of sec. 33, T. 25 N., R. 29 E., bears S. 89°59' W., 22.10 chs. dist., hereinbefore described.

Land, rolling.

Soil, sandy clay and rocky.

Timber, ponderosa pine, piñon, juniper; undergrowth, scrub oak, sagebrush, cacti, and native grasses.

Point for the 1/4 sec. cor of sec. 2 only, T. 24 N., R. 29 E., at midpoint on the N. bdy. of sec. 2.

Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.

T 25 N R 29 E
 —————
 1/4 S 2
 T 24 N R 29 E

2008

Deposit a magnet, in a white plastic case, at the base of the stainless steel post.

From this cor. point, the stan. 1/4 sec. cor. of sec. 34, T. 25 N., R. 29 E., bears N. 89°59' E., 17.89 chs. dist., hereinbefore described.

From this same cor. point, the stan. cor. of secs. 33 and 34, T. 25 N., R. 29 E., bears S. 89°59' W., 22.08 chs. dist., hereinbefore described.

From the cor. of secs. 3, 4, 33 and 34, on the S. bdy. of the Tp., hereinbefore described.

N. 0°02' W., bet. secs. 33 and 34.

**Survey of the Subdivisional Lines,
T. 24 N., R. 29 E., Gila and Salt River Meridian, Arizona**

CHAINS	<p>Over rolling land through dense piñon and juniper.</p>						
40.00	<p>Point for the 1/4 sec. cor. of secs. 33 and 34.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center; margin: 10px 0;"> <table style="margin: auto; border-collapse: collapse;"> <tr><td style="padding: 0 10px;">T 24 N</td><td style="padding: 0 10px;">R 29 E</td></tr> <tr><td style="padding: 0 10px;"></td><td style="padding: 0 10px;">1/4</td></tr> <tr><td style="padding: 0 10px;">S 33</td><td style="padding: 0 10px;"> S 34</td></tr> </table> </div> <p style="text-align: center; margin: 10px 0;">2008</p> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p>	T 24 N	R 29 E		1/4	S 33	S 34
T 24 N	R 29 E						
	1/4						
S 33	S 34						
80.00	<p>Point for the cor. of secs. 27, 28, 33 and 34.</p> <p>Set a brass tablet, 3 1/4 ins. diam., 3 1/2 ins. stem, cemented in a drill hole in exposed bedrock, with top mkd.</p> <div style="text-align: center; margin: 10px 0;"> <table style="margin: auto; border-collapse: collapse;"> <tr><td style="padding: 0 10px;">T 24 N</td><td style="padding: 0 10px;">R 29 E</td></tr> <tr><td style="padding: 0 10px;">S 28</td><td style="padding: 0 10px;"> S 27</td></tr> <tr><td style="padding: 0 10px;">S 33</td><td style="padding: 0 10px;"> S 34</td></tr> </table> </div> <p style="text-align: center; margin: 10px 0;">2008</p> <p>from which</p> <p style="margin-left: 40px;">A stainless steel post, 28 ins. long, 2 1/2 ins. diam., set 24 ins. in the ground, for a reference monument, bears N. 80°00' E., 60.00 ft. dist. with brass cap mkd. RM T24N R29E S27 60.0 FT. TO COR 2008 and an arrow pointing to the corner. Deposit a magnet, in a white plastic case, at the base of the stainless steel post. Set a steel fence post nearby.</p> <p style="margin-left: 40px;">A stainless steel post, 28 ins. long, 2 1/2 ins. diam., set 22 ins. in the ground, for a reference monument, bears N. 50°00' W., 45.00 ft. dist. with brass cap mkd. RM T24N R29E S28 45.0 FT. TO COR 2008 and an arrow pointing to the corner. Deposit a magnet, in a white plastic case, at the base of the stainless steel post. Set a steel fence post nearby.</p> <p>Deposit a magnet, in a white plastic case, in the drill hole, beneath the brass tablet.</p> <p>Cor. is located 25 lks. W. of the center, on the W. cut bank, of Navajo Route 25, a graded road, 24 ft. wide, bears N. 30° E. and S. 30° W.</p>	T 24 N	R 29 E	S 28	S 27	S 33	S 34
T 24 N	R 29 E						
S 28	S 27						
S 33	S 34						

**Survey of the Subdivisional Lines,
T. 24 N., R. 29 E., Gila and Salt River Meridian, Arizona**

CHAINS	
	<p>Land, rolling. Soil, sand and sandy clay. Timber, ponderosa pine, piñon, juniper; undergrowth, scrub oak, sagebrush, cacti, and native grasses.</p> <hr/> <p>From the cor. of secs. 26, 27, 34 and 35. S. 89°52' W., bet. secs. 27 and 34. Over rolling land through dense piñon and juniper.</p>
39.97	<p>Point for the 1/4 sec. cor. of secs. 27 and 34. Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 20 ins. in the ground, to bedrock, in a mound of stone, 4 ft. base, to top, with brass cap mkd.</p> <p style="text-align: center;">T 24 N R 29 E S 27 1/4 ——— S 34</p> <p style="text-align: center;">2008</p> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p>
79.94	<p>The cor. of secs. 27, 28, 33 and 34. Land, rolling. Soil, sand and sandy clay. Timber, ponderosa pine, piñon, juniper; undergrowth, scrub oak, sagebrush, cacti, and native grasses.</p> <hr/> <p>N. 0°02' W., bet. secs. 27 and 28.</p>
36.70	<p>Trail road, bears N. 80° E. and S. 80° W.</p>
40.00	<p>Point for the 1/4 sec. cor. of secs. 27 and 28. Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T 24 N R 29 E 1/4 S 28 S 27</p> <p style="text-align: center;">2008</p> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p>

**Survey of the Subdivisional Lines,
T. 24 N., R. 29 E., Gila and Salt River Meridian, Arizona**

CHAINS									
80.00	<p>Point for the cor. of secs. 21, 22, 27 and 28.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <table border="1" data-bbox="803 441 1031 556" style="margin-left: auto; margin-right: auto;"> <tr> <td>T 24 N</td> <td>R 29 E</td> </tr> <tr> <td>S 21</td> <td>S 22</td> </tr> <tr> <td>S 28</td> <td>S 27</td> </tr> </table> <p align="center">2008</p> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p> <p>Land, rolling. Soil, sand and sandy clay. Timber, ponderosa pine, piñon, juniper; undergrowth, scrub oak, sagebrush, cacti, and native grasses.</p>	T 24 N	R 29 E	S 21	S 22	S 28	S 27		
T 24 N	R 29 E								
S 21	S 22								
S 28	S 27								
	<hr/> <p>From the cor. of secs. 22, 23, 26 and 27.</p> <p>S. 89°52' W., bet. secs. 22 and 27.</p> <p>Over rolling land through dense piñon and juniper.</p>								
39.97	<p>Point for the 1/4 sec. cor. of secs. 22 and 27.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <table border="1" data-bbox="803 1249 1031 1375" style="margin-left: auto; margin-right: auto;"> <tr> <td>T 24 N</td> <td>R 29 E</td> </tr> <tr> <td></td> <td>S 22</td> </tr> <tr> <td>1/4</td> <td>—</td> </tr> <tr> <td></td> <td>S 27</td> </tr> </table> <p align="center">2008</p> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p>	T 24 N	R 29 E		S 22	1/4	—		S 27
T 24 N	R 29 E								
	S 22								
1/4	—								
	S 27								
45.20	<p>Navajo Route 25, a graded road, 24 ft. wide, bears N. 10° E. and S. 10° W.</p>								
79.94	<p>The cor. of secs. 21, 22, 27 and 28.</p> <p>Land, rolling. Soil, sand and sandy clay. Timber, ponderosa pine, piñon, juniper; undergrowth, scrub oak, sagebrush, cacti, and native grasses.</p> <hr/> <p>N. 0°02' W., bet. secs. 21 and 22.</p>								

**Survey of the Subdivisional Lines,
T. 24 N., R. 29 E., Gila and Salt River Meridian, Arizona**

CHAINS	
	Over rolling land through dense piñon and juniper.
40.00	Point for the 1/4 sec. cor. of secs. 21 and 22. Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd. <div style="text-align: center;"> T 24 N R 29 E 1/4 S 21 S 22 2008 </div>
	Deposit a magnet, in a white plastic case, at the base of the stainless steel post.
80.00	Point for the cor. of secs. 15, 16, 21 and 22. Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 18 ins. in the ground, to bedrock, in a mound of stone, 3 ft. base, to top, with brass cap mkd. <div style="text-align: center;"> T 24 N R 29 E S 16 S 15 S 21 S 22 2008 </div>
	Deposit a magnet, in a white plastic case, at the base of the stainless steel post.
	Land, rolling. Soil, sand and sandy clay. Timber, ponderosa pine, piñon, juniper; undergrowth, scrub oak, sagebrush, cacti, and native grasses.
	From the cor. of secs. 14, 15, 22 and 23. S. 89°52' W., bet. secs. 15 and 22.
	Over rolling land through dense piñon and juniper.
13.60	Navajo Route 25, a graded road, 21 ft. wide, bears N. 40° E. and S. 40° W.
14.40	Power line, 2 strand, bears N. 35° E. and S. 35° W.
39.97	Point for the 1/4 sec. cor. of secs. 15 and 22. Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.

**Survey of the Subdivisional Lines,
T. 24 N., R. 29 E., Gila and Salt River Meridian, Arizona**

CHAINS	
	<p align="center">T 24 N R 29 E S 15 1/4 ——— S 22</p> <p align="center">2008</p>
79.94	<p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p> <p>The cor. of secs. 15, 16, 21 and 22.</p> <p>Land, rolling. Soil, sand and sandy clay. Timber, ponderosa pine, piñon, juniper; undergrowth, scrub oak, sagebrush, cacti, and native grasses.</p> <hr/>
	<p>N. 0°02' W., bet. secs. 15 and 16.</p>
	<p>Over rolling land through dense piñon and juniper and scattered ponderosa pine.</p>
11.10	<p>Power line, 2 strand, bears N. 80° E. and S. 80° W.</p>
40.00	<p>Point for the 1/4 sec. cor. of secs. 15 and 16.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p>
	<p align="center">T 24 N R 29 E 1/4 S 16 S 15</p> <p align="center">2008</p>
	<p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p>
80.00	<p>Point for the cor. of secs. 9, 10, 15 and 16.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p>
	<p align="center">T 24 N R 29 E S 9 S 10 S 16 S 15</p> <p align="center">2008</p>
	<p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p>

**Survey of the Subdivisional Lines,
T. 24 N., R. 29 E., Gila and Salt River Meridian, Arizona**

CHAINS	
	<p>Land, rolling. Soil, sand and sandy clay. Timber, ponderosa pine, piñon, juniper; undergrowth, scrub oak, sagebrush, cacti, and native grasses.</p> <hr/> <p>From the cor. of secs. 10, 11, 14 and 15. S. 89°52' W., bet. secs. 10 and 15. Over rolling land through dense piñon and juniper.</p>
16.70	Trail road, bears S. 50° E. and N. 50° W.
39.97	<p>Point for the 1/4 sec. cor. of secs. 10 and 15.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 18 ins. in the ground, to bedrock, in a mound of stone, 3 ft. base, to top, with brass cap mkd.</p> <div style="text-align: center;"> <p>T 24 N R 29 E S 10 1/4 ——— S 15</p> <p>2008</p> </div> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p>
79.94	<p>The cor. of secs. 9, 10, 15 and 16.</p> <p>Land, rolling. Soil, sand and sandy clay. Timber, ponderosa pine, piñon, juniper; undergrowth, scrub oak, sagebrush, cacti, and native grasses.</p> <hr/> <p>N. 0°02' W., bet. secs. 9 and 10. Over rolling land.</p>
36.70	Trail road, bears S. 65° E. and N. 65° W.
40.00	<p>Point for the 1/4 sec. cor. of secs. 9 and 10.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p>

**Survey of the Subdivisional Lines,
T. 24 N., R. 29 E., Gila and Salt River Meridian, Arizona**

CHAINS	
	<p align="center">T 24 N R 29 E 1/4 S 9 S 10</p> <p align="center">2008</p> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p>
80.00	<p>Point for the cor. of secs. 3, 4, 9 and 10.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 22 ins. in the ground, with brass cap mkd.</p> <p align="center">T 24 N R 29 E S 4 S 3 ----- S 9 S 10</p> <p align="center">2008</p> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p> <p>Land, rolling. Soil, sand and sandy clay. Timber, ponderosa pine, piñon, juniper; undergrowth, scrub oak, sagebrush, cacti, and native grasses.</p> <hr/>
	<p>From the cor. of secs. 2, 3, 10 and 11.</p> <p>S. 89°52' W., bet. secs. 3 and 10.</p> <p>Over rolling land.</p>
30.50	<p>Trail road, bears S. 20° E. and N. 20° W.</p>
39.97	<p>Point for the 1/4 sec. cor. of secs. 3 and 10.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p align="center">T 24 N R 29 E S 3 1/4 ——— S 10</p> <p align="center">2008</p>
79.94	<p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p> <p>The cor. of secs. 3, 4, 9 and 10.</p>

**Survey of the Subdivisional Lines,
T. 24 N., R. 29 E., Gila and Salt River Meridian, Arizona**

CHAINS	
	<p>Land, rolling. Soil, sand and sandy clay. Timber, ponderosa pine, piñon, juniper; undergrowth, scrub oak, sagebrush, cacti, and native grasses.</p> <hr/> <p>N. 0°02' W., bet. secs. 3 and 4.</p> <p>Over rolling land through dense piñon and juniper and scattered ponderosa pine.</p>
40.00	<p>Point for the 1/4 sec. cor. of secs. 3 and 4.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 18 ins. in the ground, to bedrock, in a mound of stone, 4 ft. base, to top, with brass cap mkd.</p> <p style="text-align: center;">T 24 N R 29 E 1/4 S 4 S 3 2008</p> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p>
80.00	<p>Point for the 80 1/16 sec. cor. of secs. 3 and 4.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T 24 N R 29 E 1/16 S 4 S 3 80 2008</p> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p>
94.84	<p>Point for the closing cor. of secs. 3 and 4, at intersection with the Sixth Standard Parallel North, on the N. bdy. of the Tp.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p>

**Survey of the Subdivisional Lines,
T. 24 N., R. 29 E., Gila and Salt River Meridian, Arizona**

CHAINS

T 25 N R 29 E
 S 32
 S 4 | S 3
 T 24 N R 29 E
 CC

2008

Deposit a magnet, in a white plastic case, at the base of the stainless steel post.

From this cor. point, the stan. cor. of secs. 32 and 33, T. 25 N., R. 29 E., bears N. 89°59' E., 17.83 chs. dist., hereinbefore described.

From this same cor. point, the stan. 1/4 sec. cor. of sec. 32, T. 25 N., R. 29 E., bears S. 89°59' W., 22.15 chs. dist., hereinbefore described.

Land, rolling.

Soil, sand and sandy clay.

Timber, ponderosa pine, piñon, juniper; undergrowth, scrub oak, sagebrush, cacti, and native grasses.

Point for the 1/4 sec. cor of sec. 3 only, T. 24 N., R. 29 E., at midpoint on the N. bdy. of sec. 3.

Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 20 ins. in the ground, to bedrock, in a mound of stone, 3 ft. base, to top, with brass cap mkd.

T 25 N R 29 E
 1/4 S 3
 T 24 N R 29 E

2008

Deposit a magnet, in a white plastic case, at the base of the stainless steel post.

From this cor. point, the stan. 1/4 sec. cor. of sec. 33, T. 25 N., R. 29 E., bears N. 89°57' E., 17.87 chs. dist., hereinbefore described.

From this same cor. point, the stan. cor. of secs. 32 and 33, T. 25 N., R. 29 E., bears S. 89°57' W., 22.14 chs. dist., hereinbefore described.

From the cor. of secs. 4, 5, 32 and 33, on the S. bdy. of the Tp., hereinbefore described.

**Survey of the Subdivisional Lines,
T. 24 N., R. 29 E., Gila and Salt River Meridian, Arizona**

CHAINS									
	N. 0°03' W., bet. secs. 32 and 33.								
	Over rolling land through dense piñon and juniper.								
35.10	Trail road, bears S. 55° E. and N. 55° W.								
40.00	Point for the 1/4 sec. cor. of secs. 32 and 33.								
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 18 ins. in the ground, to bedrock, in a mound of stone, 4 ft. base, to top, with brass cap mkd.								
	<table style="margin-left: auto; margin-right: auto;"> <tr><td>T 24 N</td><td>R 29 E</td></tr> <tr><td colspan="2" style="text-align: center;">1/4</td></tr> <tr><td>S 32</td><td> S 33</td></tr> </table>	T 24 N	R 29 E	1/4		S 32	S 33		
T 24 N	R 29 E								
1/4									
S 32	S 33								
	2008								
	Deposit a magnet, in a white plastic case, at the base of the stainless steel post.								
48.10	Trail road, bears S. 35° E. and N. 35° W.								
80.00	Point for the cor. of secs. 28, 29, 32 and 33.								
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.								
	<table style="margin-left: auto; margin-right: auto;"> <tr><td>T 24 N</td><td>R 29 E</td></tr> <tr><td>S 29</td><td> S 28</td></tr> <tr><td colspan="2" style="text-align: center;">-----</td></tr> <tr><td>S 32</td><td> S 33</td></tr> </table>	T 24 N	R 29 E	S 29	S 28	-----		S 32	S 33
T 24 N	R 29 E								
S 29	S 28								

S 32	S 33								
	2008								
	Deposit a magnet, in a white plastic case, at the base of the stainless steel post.								
	From this cor. point, the NW cor. of a stucco house, 24 x 34 ft., bears S. 16°31' E., 1.43 chs. dist., with a porch, 14 x 8 ft, on the S., long side bears N. 70° E.								
	Land, rolling.								
	Soil, sand and sandy clay.								
	Timber, ponderosa pine, piñon, juniper; undergrowth, scrub oak, sagebrush, cacti, and native grasses.								

	From the cor. of secs. 27, 28, 33 and 34.								
	S. 89°45' W., bet. secs. 28 and 33.								
	Over rolling land through dense piñon and juniper.								

**Survey of the Subdivisional Lines,
T. 24 N., R. 29 E., Gila and Salt River Meridian, Arizona**

CHAINS	
39.99	<p>Point for the 1/4 sec. cor. of secs. 28 and 33.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center;"> <p>T 24 N R 29 E S 28 1/4 ——— S 33</p> <p>2008</p> </div> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p> <p>Cor. is located 25 lks. S. of a trail road, bears N. 80° E. and S. 80° W.</p>
79.98	<p>The cor. of secs. 28, 29, 32 and 33.</p> <p>Land, rolling. Soil, sand and sandy clay. Timber, ponderosa pine, piñon, juniper; undergrowth, scrub oak, sagebrush, cacti, and native grasses.</p> <hr/> <p>N. 0°03' W., bet. secs. 28 and 29.</p> <p>Over rolling land through dense piñon and juniper.</p>
40.00	<p>Point for the 1/4 sec. cor. of secs. 28 and 29.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center;"> <p>T 24 N R 29 E 1/4 S 29 S 28</p> <p>2008</p> </div> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p>
80.00	<p>Point for the cor. of secs. 20, 21, 28 and 29.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 22 ins. in the ground, to bedrock, with brass cap mkd.</p>

**Survey of the Subdivisional Lines,
T. 24 N., R. 29 E., Gila and Salt River Meridian, Arizona**

CHAINS	
	<p align="center">T 24 N R 29 E S 20 S 21 S 29 S 28</p> <p align="center">2008</p> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p> <p>Land, rolling. Soil, sand and sandy clay. Timber, ponderosa pine, piñon, juniper; undergrowth, scrub oak, sagebrush, cacti, and native grasses.</p> <hr/> <p>From the cor. of secs. 21, 22, 27 and 28.</p> <p>S. 89°45' W., bet. secs. 21 and 28.</p> <p>Over rolling land through dense piñon and juniper.</p>
39.99	<p>Point for the 1/4 sec. cor. of secs. 21 and 28.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p align="center">T 24 N R 29 E S 21 1/4 ——— S 28</p> <p align="center">2008</p> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p>
79.98	<p>The cor. of secs. 20, 21, 28 and 29.</p> <p>Land, rolling. Soil, sand and sandy clay. Timber, ponderosa pine, piñon, juniper; undergrowth, scrub oak, sagebrush, cacti, and native grasses.</p> <hr/> <p>N. 0°03' W., bet. secs. 20 and 21.</p> <p>Over rolling land through dense piñon and juniper.</p>
40.00	<p>Point for the 1/4 sec. cor. of secs. 20 and 21.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p>

**Survey of the Subdivisional Lines,
T. 24 N., R. 29 E., Gila and Salt River Meridian, Arizona**

CHAINS	<p align="center">T 24 N R 29 E 1/4 S 20 S 21</p> <p align="center">2008</p> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p> <p>Cor. is located 1.40 chs. W. of a trail road, bears N. 10° E. and S. 10° W.</p>
80.00	<p>Point for the cor. of secs. 16, 17, 20 and 21.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p align="center">T 24 N R 29 E S 17 S 16 ----- S 20 S 21</p> <p align="center">2008</p> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p> <p>Land, rolling. Soil, sand and sandy clay. Timber, ponderosa pine, piñon, juniper; undergrowth, scrub oak, sagebrush, cacti, and native grasses.</p> <hr/> <p>From the cor. of secs. 15, 16, 21 and 22.</p> <p>S. 89°45' W., bet. secs. 16 and 21.</p> <p>Over rolling land through dense piñon and juniper.</p>
39.99	<p>Point for the 1/4 sec. cor. of secs. 16 and 21.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 22 ins. in the ground, encircled with a collar of stone, with brass cap mkd.</p> <p align="center">T 24 N R 29 E S 16 1/4 ----- S 21</p> <p align="center">2008</p> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p>

**Survey of the Subdivisional Lines,
T. 24 N., R. 29 E., Gila and Salt River Meridian, Arizona**

CHAINS	
79.98	<p>The cor. of secs. 16, 17, 20 and 21.</p> <p>Land, rolling. Soil, sand and sandy clay. Timber, ponderosa pine, piñon, juniper; undergrowth, scrub oak, sagebrush, cacti, and native grasses.</p> <hr/> <p>N. 0°03' W., bet. secs. 16 and 17.</p> <p>Over rolling land through dense piñon and juniper.</p>
40.00	<p>Point for the 1/4 sec. cor. of secs. 16 and 17.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T 24 N R 29 E 1/4 S 17 S 16</p> <p style="text-align: center;">2008</p> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p>
80.00	<p>Point for the cor. of secs. 8, 9, 16 and 17.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T 24 N R 29 E S 8 S 9 S 17 S 16</p> <p style="text-align: center;">2008</p> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p> <p>Land, rolling. Soil, sand and sandy clay. Timber, ponderosa pine, piñon, juniper; undergrowth, scrub oak, sagebrush, cacti, and native grasses.</p> <hr/> <p>From the cor. of secs. 9, 10, 15 and 16.</p> <p>S. 89°45' W., bet. secs. 9 and 16.</p> <p>Over rolling land through dense piñon and juniper.</p>
39.99	<p>Point for the 1/4 sec. cor. of secs. 9 and 16.</p>

**Survey of the Subdivisional Lines,
T. 24 N., R. 29 E., Gila and Salt River Meridian, Arizona**

CHAINS	
	<p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T 24 N R 29 E S 9 1/4 ——— S 16</p> <p style="text-align: center;">2008</p> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p> <p>Cor. is located 1.90 chs. W. a trail road, bears N. 70° E. and S. 70° W.</p>
79.98	<p>The cor. of secs. 8, 9, 16 and 17.</p> <p>Land, rolling. Soil, sand and sandy clay. Timber, ponderosa pine, piñon, juniper; undergrowth, scrub oak, sagebrush, cacti, and native grasses.</p> <hr/> <p>N. 0°03' W., bet. secs. 8 and 9.</p> <p>Over rolling land.</p>
31.60	<p>Power line, 2 strand, bears S. 25° E. and N. 25° W.</p>
40.00	<p>Point for the 1/4 sec. cor. of secs. 8 and 9.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 22 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T 24 N R 29 E 1/4 S 8 S 9</p> <p style="text-align: center;">2008</p> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p>
70.80	<p>Trail road, bears S. 50° E. and N. 50° W.</p>
80.00	<p>Point for the cor. of secs. 4, 5, 8 and 9.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p>

**Survey of the Subdivisional Lines,
T. 24 N., R. 29 E., Gila and Salt River Meridian, Arizona**

CHAINS									
	<table border="0"> <tr> <td>T 24 N</td> <td>R 29 E</td> </tr> <tr> <td>S 5</td> <td>S 4</td> </tr> <tr> <td>S 8</td> <td>S 9</td> </tr> </table> <p>2008</p> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p> <p>Cor. is located 2.50 chs. E. of a trail road, bears North and South.</p> <p>Land, rolling. Soil, sand and sandy clay. Timber, ponderosa pine, piñon, juniper; undergrowth, scrub oak, sagebrush, cacti, and native grasses.</p> <hr/> <p>From the cor. of secs. 3, 4, 9 and 10.</p> <p>S. 89°45' W., bet. secs. 4 and 9.</p> <p>Over rolling land.</p>	T 24 N	R 29 E	S 5	S 4	S 8	S 9		
T 24 N	R 29 E								
S 5	S 4								
S 8	S 9								
39.99	<p>Point for the 1/4 sec. cor. of secs. 4 and 9.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p align="center"> <table border="0"> <tr> <td>T 24 N</td> <td>R 29 E</td> </tr> <tr> <td>S 4</td> <td></td> </tr> <tr> <td>1/4</td> <td>—</td> </tr> <tr> <td>S 9</td> <td></td> </tr> </table> </p> <p>2008</p> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p>	T 24 N	R 29 E	S 4		1/4	—	S 9	
T 24 N	R 29 E								
S 4									
1/4	—								
S 9									
79.98	<p>The cor. of secs. 4, 5, 8 and 9.</p> <p>Land, rolling. Soil, sand and sandy clay. Timber, ponderosa pine, piñon, juniper; undergrowth, scrub oak, sagebrush, cacti, and native grasses.</p> <hr/> <p>N. 0°03' W., bet. secs. 4 and 5.</p> <p>Over rolling land through dense piñon and juniper and scattered ponderosa pine.</p>								
40.00	<p>Point for the 1/4 sec. cor. of secs. 4 and 5.</p>								

**Survey of the Subdivisional Lines,
T. 24 N., R. 29 E., Gila and Salt River Meridian, Arizona**

CHAINS	
	<p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T 24 N R 29 E 1/4 S 5 S 4</p> <p style="text-align: center;">2008</p> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p> <p>Cor. is located 20 lks. E. of a trail road, bears N. 5° E. and S. 5° W.</p>
80.00	<p>Point for the 80 1/16 sec. cor. of secs. 4 and 5.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T 24 N R 29 E 1/16 S 5 S 4 80</p> <p style="text-align: center;">2008</p> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p>
95.17	<p>Point for the closing cor. of secs. 4 and 5, at intersection with the Sixth Standard Parallel North, on the N. bdy. of the Tp.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 20 ins. in the ground, to bedrock, in a mound of stone, 3 ft. base, to top, with brass cap mkd.</p> <p style="text-align: center;">T 25 N R 29 E S 31 ----- S 5 S 4 T 24 N R 29 E CC</p> <p style="text-align: center;">2008</p> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p> <p>From this cor. point, the stan. cor. of secs. 31 and 32, T. 25 N., R. 29 E., bears S. 89°59' E., 17.85 chs. dist., hereinbefore described.</p>

**Survey of the Subdivisional Lines,
T. 24 N., R. 29 E., Gila and Salt River Meridian, Arizona**

CHAINS	
	<p>From this same cor. point, the stan. 1/4 sec. cor. of sec. 31, T. 25 N., R. 29 E., bears N. 89°59' W., 22.14 chs. dist., hereinbefore described.</p> <p>Land, rolling. Soil, sand and sandy clay. Timber, ponderosa pine, piñon, juniper; undergrowth, scrub oak, sagebrush, cacti, and native grasses.</p> <hr/>
39.99	<p>Point for the 1/4 sec. cor of sec. 4 only, T. 24 N., R. 29 E., at midpoint on the N. bdy. of sec. 4.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T 25 N R 29 E ----- 1/4 S 4 T 24 N R 29 E</p> <p style="text-align: center;">2008</p> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p> <p>From this cor. point, the stan. 1/4 sec. cor. of sec. 32, T. 25 N., R. 29 E., bears East, 17.84 chs. dist., hereinbefore described.</p> <p>From this same cor. point, the stan. cor. of secs. 31 and 32, T. 25 N., R. 29 E., bears West, 22.14 chs. dist., hereinbefore described.</p> <hr/>
40.00	<p>From the cor. of secs. 5, 6, 31 and 32, on the S. bdy. of the Tp., hereinbefore described.</p> <p>N. 0°03' W., bet. secs. 31 and 32.</p> <p>Over rolling land through dense piñon and juniper.</p> <p>Point for the 1/4 sec. cor. of secs. 31 and 32.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T 24 N R 29 E 1/4 S 31 S 32</p> <p style="text-align: center;">2008</p>

**Survey of the Subdivisional Lines,
T. 24 N., R. 29 E., Gila and Salt River Meridian, Arizona**

CHAINS	<p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p>						
80.00	<p>Point for the cor. of secs. 29, 30, 31 and 32.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center; margin: 10px 0;"> <table style="margin: auto; border-collapse: collapse;"> <tr> <td style="padding: 0 10px;">T 24 N</td> <td style="padding: 0 10px;">R 29 E</td> </tr> <tr> <td style="border-right: 1px solid black; padding: 0 5px;">S 30</td> <td style="padding: 0 5px;">S 29</td> </tr> <tr> <td style="border-right: 1px solid black; padding: 0 5px;">S 31</td> <td style="padding: 0 5px;">S 32</td> </tr> </table> </div> <p style="text-align: center; margin: 10px 0;">2008</p> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p> <p>Land, rolling. Soil, sand and sandy clay. Timber, ponderosa pine, piñon, juniper; undergrowth, scrub oak, sagebrush, cacti, and native grasses.</p> <hr style="width: 50%; margin: 20px auto;"/> <p>From the cor. of secs. 28, 29, 32 and 33.</p> <p>S. 89°55' W., bet. secs. 29 and 32.</p> <p>Over rolling land through dense piñon and juniper.</p>	T 24 N	R 29 E	S 30	S 29	S 31	S 32
T 24 N	R 29 E						
S 30	S 29						
S 31	S 32						
15.10	<p>Navajo Route 2010, a graded road, 20 ft. wide, bears North and South.</p>						
40.00	<p>Point for the 1/4 sec. cor. of secs. 29 and 32.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center; margin: 10px 0;"> <table style="margin: auto; border-collapse: collapse;"> <tr> <td style="padding: 0 10px;">T 24 N</td> <td style="padding: 0 10px;">R 29 E</td> </tr> <tr> <td></td> <td style="padding: 0 5px;">S 29</td> </tr> <tr> <td style="padding: 0 5px;">1/4</td> <td style="border-top: 1px solid black; padding: 0 5px;">S 32</td> </tr> </table> </div> <p style="text-align: center; margin: 10px 0;">2008</p> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p>	T 24 N	R 29 E		S 29	1/4	S 32
T 24 N	R 29 E						
	S 29						
1/4	S 32						
80.00	<p>The cor. of secs. 29, 30, 31 and 32.</p>						

**Survey of the Subdivisional Lines,
T. 24 N., R. 29 E., Gila and Salt River Meridian, Arizona**

CHAINS	
	<p>Land, rolling. Soil, sand and sandy clay. Timber, ponderosa pine, piñon, juniper; undergrowth, scrub oak, sagebrush, cacti, and native grasses.</p> <hr/> <p>N. 89°58' W., bet. secs. 30 and 31.</p> <p>Over rolling land through dense piñon and juniper.</p>
40.00	<p>Point for the 1/4 sec. cor. of secs. 30 and 31.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center;"> <p>T 24 N R 29 E S 30 1/4 ——— S 31</p> <p>2008</p> </div> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p>
76.73	<p>The cor. of secs. 25, 30, 31 and 36, on the W. bdy. of the Tp., hereinbefore described.</p> <p>Land, rolling. Soil, sand and sandy clay. Timber, ponderosa pine, piñon, juniper; undergrowth, scrub oak, sagebrush, cacti, and native grasses.</p> <hr/> <p>From the cor. of secs. 29, 30, 31 and 32.</p> <p>N. 0°03' W., bet. secs. 29 and 30.</p> <p>Over rolling land through dense piñon and juniper.</p>
40.00	<p>Point for the 1/4 sec. cor. of secs. 29 and 30.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center;"> <p>T 24 N R 29 E 1/4 S 30 S 29</p> <p>2008</p> </div> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p>

**Survey of the Subdivisional Lines,
T. 24 N., R. 29 E., Gila and Salt River Meridian, Arizona**

CHAINS									
62.70	Trail road, bears N. 70° E. and S. 70° W.								
80.00	Point for the cor. of secs. 19, 20, 29 and 30. Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 20 ins. in the ground, to bedrock, in a mound of stone, 4 ft. base, to top, with brass cap mkd.								
	<table style="margin-left: auto; margin-right: auto;"> <tr> <td>T 24 N</td> <td>R 29 E</td> </tr> <tr> <td style="border-right: 1px solid black;">S 19</td> <td>S 20</td> </tr> <tr> <td style="border-right: 1px solid black;">S 30</td> <td>S 29</td> </tr> </table>	T 24 N	R 29 E	S 19	S 20	S 30	S 29		
T 24 N	R 29 E								
S 19	S 20								
S 30	S 29								
	2008								
	Deposit a magnet, in a white plastic case, at the base of the stainless steel post.								
	Land, rolling. Soil, sand and sandy clay. Timber, ponderosa pine, piñon, juniper; undergrowth, scrub oak, sagebrush, cacti, and native grasses.								
	From the cor. of secs. 20, 21, 28 and 29. S. 89°55' W., bet. secs. 20 and 29. Over rolling land through dense piñon and juniper.								
11.90	Navajo Route 2010, a graded road, 20 ft. wide, bears North and South.								
40.00	Point for the 1/4 sec. cor. of secs. 20 and 29. Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.								
	<table style="margin-left: auto; margin-right: auto;"> <tr> <td>T 24 N</td> <td>R 29 E</td> </tr> <tr> <td></td> <td>S 20</td> </tr> <tr> <td></td> <td>1/4 ———</td> </tr> <tr> <td></td> <td>S 29</td> </tr> </table>	T 24 N	R 29 E		S 20		1/4 ———		S 29
T 24 N	R 29 E								
	S 20								
	1/4 ———								
	S 29								
	2008								
	Deposit a magnet, in a white plastic case, at the base of the stainless steel post.								
46.70	Trail road, bears N. 60° E. and S. 60° W.								
80.00	The cor. of secs. 19, 20, 29 and 30.								

**Survey of the Subdivisional Lines,
T. 24 N., R. 29 E., Gila and Salt River Meridian, Arizona**

CHAINS	
	<p>Land, rolling. Soil, sand and sandy clay. Timber, ponderosa pine, piñon, juniper; undergrowth, scrub oak, sagebrush, cacti, and native grasses.</p> <hr/> <p>N. 89°58' W., bet. secs. 19 and 30.</p> <p>Over rolling land through dense piñon and juniper.</p>
40.00	<p>Point for the 1/4 sec. cor. of secs. 19 and 30.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T 24 N R 29 E S 19 1/4 ——— S 30</p> <p style="text-align: center;">2008</p>
76.64	<p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p> <p>The cor. of secs. 19, 24, 25 and 30, on the W. bdy. of the Tp., hereinbefore described.</p> <p>Land, rolling. Soil, sand and sandy clay. Timber, ponderosa pine, piñon, juniper; undergrowth, scrub oak, sagebrush, cacti, and native grasses.</p> <hr/> <p>From the cor. of secs. 19, 20, 29 and 30.</p> <p>N. 0°03' W., bet. secs. 19 and 20.</p> <p>Over rolling land through dense piñon and juniper.</p>
40.00	<p>Point for the 1/4 sec. cor. of secs. 19 and 20.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 20 ins. in the ground, to bedrock, in a mound of stone, 3 ft. base, to top, with brass cap mkd.</p> <p style="text-align: center;">T 24 N R 29 E 1/4 S 19 S 20</p> <p style="text-align: center;">2008</p>

**Survey of the Subdivisional Lines,
T. 24 N., R. 29 E., Gila and Salt River Meridian, Arizona**

CHAINS									
	<p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p> <p>Cor. is located in a faint trail road, bears S. 35° E. and N. 25° W.</p> <p>Set a steel fence post nearby.</p>								
80.00	<p>Point for the cor. of secs. 17, 18, 19 and 20.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 22 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center;"> <table style="margin: auto;"> <tr> <td>T 24 N</td> <td>R 29 E</td> </tr> <tr> <td>S 18</td> <td>S 17</td> </tr> <tr> <td>S 19</td> <td>S 20</td> </tr> </table> <p>2008</p> </div> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p> <p>Land, rolling. Soil, sand and sandy clay. Timber, ponderosa pine, piñon, juniper; undergrowth, scrub oak, sagebrush, cacti, and native grasses.</p> <hr/> <p>From the cor. of secs. 16, 17, 20 and 21.</p> <p>S. 89°55' W., bet. secs. 17 and 20.</p> <p>Over rolling land through dense piñon and juniper.</p>	T 24 N	R 29 E	S 18	S 17	S 19	S 20		
T 24 N	R 29 E								
S 18	S 17								
S 19	S 20								
29.50	<p>Navajo Route 2010, a graded road, 18 ft. wide, bears S. 45° E. and N. 45° W.</p>								
40.00	<p>Point for the 1/4 sec. cor. of secs. 17 and 20.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center;"> <table style="margin: auto;"> <tr> <td>T 24 N</td> <td>R 29 E</td> </tr> <tr> <td></td> <td>S 17</td> </tr> <tr> <td>1/4</td> <td>—</td> </tr> <tr> <td></td> <td>S 20</td> </tr> </table> <p>2008</p> </div> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p>	T 24 N	R 29 E		S 17	1/4	—		S 20
T 24 N	R 29 E								
	S 17								
1/4	—								
	S 20								

**Survey of the Subdivisional Lines,
T. 24 N., R. 29 E., Gila and Salt River Meridian, Arizona**

CHAINS	
	Cor. is located 35 lks. W. of a trail road, bears N. 15° E. and S. 15° W.
80.00	The cor. of secs. 17, 18, 19 and 20. Land, rolling. Soil, sand and sandy clay. Timber, ponderosa pine, piñon, juniper; undergrowth, scrub oak, sagebrush, cacti, and native grasses.
	<hr/>
	N. 89°58' W., bet. secs. 18 and 19. Over broken land.
40.00	Point for the 1/4 sec. cor. of secs. 18 and 19. Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 20 ins. in the ground, to bedrock, in a mound of stone, 3 ft. base, to top, with brass cap mkd. <div style="text-align: center;"> T 24 N R 29 E S 18 1/4 ——— S 19 2008 </div>
	Deposit a magnet, in a white plastic case, at the base of the stainless steel post.
53.50	Barbed wire fence, 5 strand, bears S. 30° E. and N. 30° W.
76.55	The cor. of secs. 13, 18, 19 and 24, on the W. bdy. of the Tp., hereinbefore described. Land, broken. Soil, sand and sandy clay. Timber, ponderosa pine, piñon, juniper; undergrowth, scrub oak, sagebrush, cacti, and native grasses.
	<hr/>
	From the cor. of secs. 17, 18, 19 and 20. N. 0°03' W., bet. secs. 17 and 18. Over rolling and broken land.
40.00	Point for the 1/4 sec. cor. of secs. 17 and 18. Set a brass tablet, 3 1/4 ins. diam., 3 1/2 ins. stem, cemented in a drill hole in exposed bedrock, with top mkd.

**Survey of the Subdivisional Lines,
T. 24 N., R. 29 E., Gila and Salt River Meridian, Arizona**

CHAINS	
	T 24 N R 29 E 1/4 S 18 S 17 2008
	Deposit a magnet, in a white plastic case, in the drill hole, beneath the brass tablet.
80.00	Point for the cor. of secs. 7, 8, 17 and 18. Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 21 ins. in the ground, with brass cap mkd.
	T 24 N R 29 E S 7 S 8 S 18 S 17 2008
	Deposit a magnet, in a white plastic case, at the base of the stainless steel post.
	Land, rolling and broken. Soil, sand and sandy clay. Timber, ponderosa pine, piñon, juniper; undergrowth, scrub oak, sagebrush, cacti, and native grasses.
	<hr/> From the cor. of secs. 8, 9, 16 and 17. S. 89°55' W., bet. secs. 8 and 17. Over rolling land through dense piñon and juniper.
14.90	Trail road, bears North and South.
40.00	Point for the 1/4 sec. cor. of secs. 8 and 17. Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.
	T 24 N R 29 E S 8 1/4 ——— S 17 2008
	Deposit a magnet, in a white plastic case, at the base of the stainless steel post.

**Survey of the Subdivisional Lines,
T. 24 N., R. 29 E., Gila and Salt River Meridian, Arizona**

CHAINS	
69.60	Navajo Route 2010, a graded road, 20 ft. wide, bears S. 15° E. and N. 15° W.
80.00	The cor. of secs. 7, 8, 17 and 18. Land, rolling. Soil, sand and sandy clay. Timber, ponderosa pine, piñon, juniper; undergrowth, scrub oak, sagebrush, cacti, and native grasses.
	N. 89°58' W., bet. secs. 7 and 18. Over rolling land through dense piñon and juniper.
40.00	Point for the 1/4 sec. cor. of secs. 7 and 18. Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 21 ins. in the ground, with brass cap mkd.
	T 24 N R 29 E S 7 1/4 ——— S 18 2008
	Deposit a magnet, in a white plastic case, at the base of the stainless steel post.
65.66	Barbed wire fence, 5 strand, bears N. 30° E. and S. 30° W.
76.46	The cor. of secs. 7, 12, 13 and 18, on the W. bdy. of the Tp., hereinbefore described. Land, rolling. Soil, sand and sandy clay. Timber, ponderosa pine, piñon, juniper; undergrowth, scrub oak, sagebrush, cacti, and native grasses.
	From the cor. of secs. 7, 8, 17 and 18. N. 0°03' W., bet. secs. 7 and 8. Over rolling land.
35.20	Navajo Route 2010, a graded road, 21 ft. wide, bears S. 20° E. and N. 20° W.
40.00	Point for the 1/4 sec. cor. of secs. 7 and 8.

**Survey of the Subdivisional Lines,
T. 24 N., R. 29 E., Gila and Salt River Meridian, Arizona**

CHAINS	
	<p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T 24 N R 29 E 1/4 S 7 S 8</p> <p style="text-align: center;">2008</p> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p> <p>Cor. is located 1.40 chs. E. of Navajo Route 2010, a graded road, 21 ft. wide, bears S. 15° E. and N. 15° W.</p>
75.80	Trail road, bears S. 65° E. and N. 65° W.
80.00	Point for the cor. of secs. 5, 6, 7 and 8.
	<p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T 24 N R 29 E S 6 S 5 S 7 S 8</p> <p style="text-align: center;">2008</p> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p> <p>Land, rolling. Soil, sand and sandy clay. Timber, ponderosa pine, piñon, juniper; undergrowth, scrub oak, sagebrush, cacti, and native grasses.</p> <hr/> <p>From the cor. of secs. 4, 5, 8 and 9.</p> <p>S. 89°55' W., bet. secs. 5 and 8.</p> <p>Over rolling land.</p>
6.20	Power line, 2 strand, bears North and South.
21.90	Graded road, 18 ft. wide, bears N. 40° E. and S. 40° W.
40.00	Point for the 1/4 sec. cor. of secs. 5 and 8.
	<p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p>

**Survey of the Subdivisional Lines,
T. 24 N., R. 29 E., Gila and Salt River Meridian, Arizona**

CHAINS	
	T 24 N R 29 E S 5 1/4 ——— S 8 2008
	Deposit a magnet, in a white plastic case, at the base of the stainless steel post.
80.00	The cor. of secs. 5, 6 7 and 8. Land, rolling. Soil, sand and sandy clay. Timber, ponderosa pine, piñon, juniper; undergrowth, scrub oak, sagebrush, cacti, and native grasses.
	N. 89°58' W., bet. secs. 6 and 7. Over rolling land.
15.60	Navajo Route 2010, a graded road, 18 ft. wide, bears S. 20° E. and N. 20° W.
40.00	Point for the 1/4 sec. cor. of secs. 6 and 7. Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.
	T 24 N R 29 E S 6 1/4 ——— S 7 2008
	Deposit a magnet, in a white plastic case, at the base of the stainless steel post.
46.06	Barbed wire fence, 5 strand, bears S. 5° E. and N. 5° W.
76.38	The cor. of secs. 1, 6, 7 and 12, on the W. bdy. of the Tp., hereinbefore described. Land, rolling. Soil, sandy clay and rocky. Timber, ponderosa pine, piñon, juniper; undergrowth, scrub oak, sagebrush, cacti, and native grasses.
	From the cor. of secs. 5, 6, 7 and 8.

**Survey of the Subdivisional Lines,
T. 24 N., R. 29 E., Gila and Salt River Meridian, Arizona**

CHAINS	
	N. 0°03' W., bet. secs. 5 and 6. Over rolling land.
40.00	Point for the 1/4 sec. cor. of secs. 5 and 6. Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 23 ins. in the ground, with brass cap mkd. <div style="text-align: center;"> T 24 N R 29 E 1/4 S 6 S 5 2008 </div>
	Deposit a magnet, in a white plastic case, at the base of the stainless steel post.
76.30	Trail road, bears S. 55° E. and N. 55° W.
80.00	Point for the 80 1/16 sec. cor. of secs. 5 and 6. Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd. <div style="text-align: center;"> T 24 N R 29 E 1/16 S 6 S 5 80 2008 </div>
	Deposit a magnet, in a white plastic case, at the base of the stainless steel post.
95.30	Point for the closing cor. of secs. 5 and 6, at intersection with the Sixth Standard Parallel North, on the N. bdy. of the Tp. Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd. <div style="text-align: center;"> T 25 N R 28 E S 36 ----- S 6 S 5 T 24 N R 29 E CC 2008 </div>
	Deposit a magnet, in a white plastic case, at the base of the stainless steel post.

**Survey of the Subdivisional Lines,
T. 24 N., R. 29 E., Gila and Salt River Meridian, Arizona**

CHAINS

From this cor. point, the stan. cor. of Tps. 25 N., Rs. 28 and 29 E., bears S. 89°56' E., 17.87 chs. dist., hereinbefore described.

From this same cor. point, the stan. 1/4 sec. cor. of sec. 36, T. 25 N., R. 28 E., bears N. 89°56' W., 22.14 chs. dist., hereinbefore described.

Land, rolling.

Soil, sandy clay and rocky.

Timber, ponderosa pine, piñon, juniper; undergrowth, scrub oak, sagebrush, cacti, and native grasses.

Point for the 1/4 sec. cor of sec. 5 only, T. 24 N., R. 29 E., at midpoint on the N. bdy. of sec. 5.

Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 22 ins. in the ground, to bedrock, in a mound of stone, 3 ft. base, to top, with brass cap mkd.

T 25 N R 29 E

1/4 S 5

T 24 N R 29 E

2008

Deposit a magnet, in a white plastic case, at the base of the stainless steel post.

From this cor. point, the stan. 1/4 sec. cor. of sec. 31, T. 25 N., R. 29 E., bears N. 89°57' E., 17.86 chs. dist., hereinbefore described.

From this same cor. point, the stan. cor. of Tps. 25 N., Rs. 28 and 29 E., bears S. 89°57' W., 22.13 chs. dist., hereinbefore described.

Point for the 1/4 sec. cor of sec. 6 only, T. 24 N., R. 29 E., at 40.00 chs. in westing from the closing cor. of secs. 5 and 6, on the N. bdy. of sec. 6.

Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 22 ins. in the ground, with brass cap mkd.

T 25 N R 28 E

1/4 S 6

T 24 N R 29 E

2008

**Survey of the Subdivisional Lines,
T. 24 N., R. 29 E., Gila and Salt River Meridian, Arizona**

CHAINS

Deposit a magnet, in a white plastic case, at the base of the stainless steel post.

From this cor. point, the stan. 1/4 sec. cor. of sec. 36, T. 25 N., R. 28 E., bears S. 89°56' E., 17.86 chs. dist., hereinbefore described.

From this same cor. point, the stan. cor. of secs. 35 and 36, T. 25 N., R. 28 E., bears N. 89°56' W., 22.15 chs. dist., hereinbefore described.

GENERAL DESCRIPTION

The area surveyed is within the Navajo Indian Reservation and approximately 2 miles north of the community of Pine Springs, Arizona. The terrain is mainly rolling and broken, with areas of rugged land. The eastern portion, along West Fork Black Creek wash, has steep rugged slopes and a canyon. The principal drainage is easterly draining into West Fork Black Creek wash in the eastern portion of the township. The western portion drains westerly.

The elevation varies from 6500 to 7500 feet above sea level. The soil is sandy clay and rocky. The eastern portion, along the West Fork Black Creek wash, is very rocky. There is a moderate stand of ponderosa pine with a dense growth of piñon and juniper. Undergrowth principally consists of sagebrush, rabbit brush, scrub oak, cacti, yucca and native grasses.

The principal access to the township is provided by two Navajo Routes, 2010 and 25. Both routes are major graded roads. Navajo Route 2010 extends northerly, entering the township in section 32 and exiting in section 6. Navajo Route 25 enters in section 33 and extends northeasterly to section 14, thence extends easterly and exits in section 13. There are other major graded roads and numerous trail roads through the township. There are numerous permanent residential homes throughout the township. Much of this area is used for grazing livestock. There is no mining activity in this township.

The mean magnetic declination of 10 1/2° E. was derived from the United States Geological Survey computer program GEOMAG, utilizing the World Magnetic Model for Epoch 2005-2010 for the dates of survey.

UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

FIELD ASSISTANTS

NAMES	CAPACITY
Leonard R. Sandoval	Cadastral Surveyor
Nelson Kinsel	Surveying Technician
Daniel Bryan	Engineering Technician
Nathan Henio	Engineering Technician
Barney Woodie	Engineering Technician

CERTIFICATE OF SURVEY

I, Jones Curtiss, Cadastral Surveyor, HEREBY CERTIFY upon honor, that in pursuance of special instructions bearing date of the 30th day of July, 2008, I have dependently resurveyed portions of the Sixth Standard Parallel North (south boundary), Tps. 25 N., Rs. 28 and 29 E. and dependently resurveyed the south boundary, and surveyed the Seventh Guide Meridian East (west boundary) and the subdivisional lines, T. 24 N., R. 29 E., of the Gila and Salt River Meridian, in the State of Arizona, which are represented in the foregoing field notes as having been executed by me and under my direction. Said survey has been made in strict conformity with said special instructions, the Manual of Instructions for the Survey of the Public Lands of the United States, 1973, and in specific manner described in the foregoing field notes.

August 19, 2009
(Date)

Jones Curtiss
(Cadastral Surveyor)

CERTIFICATE OF APPROVAL

BUREAU OF LAND MANAGEMENT
Phoenix, Arizona

The foregoing field notes of the dependent resurvey of portions of the Sixth Standard Parallel North (south boundary), Tps. 25 N., Rs. 28 and 29 E., and the dependent resurvey of the south boundary, and the survey of the Seventh Guide Meridian East (west boundary) and the subdivisional lines, T. 24 N., R. 29 E., Gila and Salt River Meridian, in the State of Arizona, executed by Jones Curtiss, Cadastral Surveyor, having been critically examined and found correct, are hereby approved.

10/13/2009
(Date)

Paul J. Moss
Acting (Chief Cadastral Surveyor of Arizona)

~~CERTIFICATE OF TRANSCRIPT~~

~~I CERTIFY That the foregoing transcript of the field notes of the above described surveys in Tps. 25 N., Rs. 28 and 29 E. and T. 24 N., R. 29 E., Gila and Salt River Meridian, Arizona, is a true copy of the original field notes.~~

~~_____
(Date)~~

~~_____
(Chief Cadastral Surveyor of Arizona)~~