

ORIGINAL

**UNITED STATES  
DEPARTMENT OF THE INTERIOR  
BUREAU OF LAND MANAGEMENT**

FIELD NOTES  
OF THE  
DEPENDENT RESURVEY OF THE SECTIONAL CORRECTION LINE  
AND A PORTION OF THE SUBDIVISIONAL LINES  
AND THE SUBDIVISION  
OF SECTIONS 23, 24 AND 26

**TOWNSHIP 14 SOUTH, RANGE 10 EAST,**  
OF THE GILA AND SALT RIVER MERIDIAN,  
IN THE STATE OF ARIZONA.

**EXECUTED BY**

**Geoffrey A. Graham, Cadastral Surveyor**

Under Special Instructions dated October 20, 2008, approved October 20, 2008, which provided for the surveys included under Group No. 1055, and assignment instructions dated October 20, 2008.

**Survey commenced December 16, 2008**

**Survey completed February 24, 2009**

**INDEX DIAGRAM**

TOWNSHIP 14 SOUTH                      RANGE 10 EAST  
 GILA AND SALT RIVER MERIDIAN, ARIZONA

6	5	4	3	2	1
7	8	9	10 25	11	12
30	28	27	25	24	16
18	17	16	15 23	14 14	13
19	20	21	22 20	23 12	24
30	29	28	19 27 17	18 26 11	11 25
9	9	8	6	5	4
31	32	33	34	35	36

Subdivision of Section 23 ..... Pages 31-33  
 Subdivision of Section 24 ..... Pages 33-34  
 Subdivision of Section 26 ..... Pages 34-36

**T. 14 S., R. 10 E., Gila and Salt River Meridian, Arizona**

CHAINS

The following field notes describe the dependent resurvey of the sectional correction line and a portion of the subdivisional lines and the subdivision of sections 23, 24 and 26., Township 14 South, Range 10 East, Gila and Salt River Meridian, Arizona.

The history of surveys pertaining to this survey is as follows:

S. W. Foreman surveyed the Second Guide Meridian East, the east boundary, in 1871. In 1895, Philip Contzen resurveyed the east boundary and returned in 1903 to survey the north boundary and portions of the west boundary and the subdivisional lines. In 1925, Charles E. Hunter resurveyed the west and portions of the south boundaries and the subdivisional lines and surveyed a portion of the subdivisional lines. In 2002, Joe R. Salazar resurveyed a portion of the east boundary.

The survey was executed in accordance with the specifications as set forth in the Manual of Instructions for the Survey of the Public Lands of the United States, 1973, and the Special Instructions dated October 20, 2008, for Group No. 1055, Arizona.

The true meridian direction and length of all lines were determined by real time kinematic global positioning system observations using Trimble Navigation 5700 and 5800 model receivers.

Preliminary to the resurvey, the lines of the prior surveys were retraced and search was made for all corners and other calls of record. Identified corners were remonumented in their original positions. Lost corners were reestablished and remonumented at proportionate positions based on the official record. The retracement data were thoroughly verified and only the true line field notes are given herein.

Geodetic control was derived from Global Positioning System (GPS) static observations post processed by National Geodetic Survey, Online Positioning User Service (OPUS), utilizing Continuously Operating Reference Stations (CORS) DH4132 AZCL COOLIDGE, AI3680 COT1 TUSCON and DH4134 AZKR KEARNY. The NAD 83 (1996), geographic position of the southeast corner of the township, is as follows:

Latitude: 32°09'39.72" N.

Longitude: 111°16'11.60" W.

**T. 14 S., R. 10 E., Gila and Salt River Meridian, Arizona**

CHAINS

The mean magnetic declination is 10 3/4° E.

---

**Dependent Resurvey of the Sectional Correction Line,  
T. 14 S., R. 10 E., Gila and Salt River Meridian, Arizona**

---

Restoring the survey executed by  
Philip Contzen, in 1903

---

Beginning at the point for the cor. of secs. 25, 30, 31 and 36, on the 2nd Guide Mer. E., the E. bdy. of the Tp., at proportionate dist.; there is no remaining evidence of the orig. cor. Position not monumented.

From this point, the cor. of Tps. 14 and 15 S., Rgs. 10 and 11 E., monumented with a stainless steel post, 2 1/2 ins. diam., firmly set, projecting 10 ins. above the ground, in a mound of concrete and earth, 2 1/2 ft. base to top, with brass cap mkd. T14S R10E R11E S36 S31 S1 S6 T15S 2009, bears S. 0°03' E., 79.93 chs. dist. This cor. was perpetuated by Joe. R. Salazar in a concurrent survey, under Arizona Group No. 1056.

From this same point, the cor. of secs. 19, 24, 25 and 30, on the 2nd Guide Mer. E., the E. bdy of the Tp., monumented with a stainless steel post, 2 1/2 ins. diam., firmly set, projecting 4 ins. above the ground, with brass cap mkd. T14S R10E R11E S24 S19 S25 S30 2009, bears N. 0°03' W., 79.93 chs. dist. This cor. was established by Joe R. Salazar in a concurrent survey under Group No. 1056.

S. 89°52' W., on the sectional correction line bet. secs. 25 and 36.

Over nearly level terrain.

40.05 Point for the 1/4 sec. cor. of secs. 25 and 36, at proportionate dist.; there is no remaining evidence of the orig. cor. Not monumented.

80.10 Point for the cor. of secs. 25, 26, 35 and 36, at proportionate dist.; there is no remaining evidence of the orig. cor.

Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, in a collar of stone, with brass cap mkd.

T 14 S	R 10 E
S 26	S 25
S 35	S 36

2009

**Dependent Resurvey of the Sectional Correction Line,  
T. 14 S., R. 10 E., Gila and Salt River Meridian, Arizona**

CHAINS	
	<p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p> <p>Set a steel sign post as a guard post.</p> <hr/> <p>S. 89°52' W., on the sectional correction line bet. secs. 26 and 35.</p> <p>Gently ascending over nearly level desert.</p>
0.70	Track road, 9 ft. wide, bears N. 20° E. and S.
0.75	Single pole utility line, bears N. and S.
20.025	<p>Point for the E. 1/16 sec. cor. of secs. 26 and 35.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 25 ins. in the ground, in a collar of stone, with brass cap mkd.</p> <div style="text-align: center;"> <p>T 14 S R 10 E S 26 E 1/16 ——— S 35</p> <p>2009</p> </div>
	<p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p> <p>Set a steel fence post as a guard post.</p> <p>Cor. is located on a diversion dam, 5 ft. above and S. of a track road, 10 ft. wide, bearing N. 60° E. and W.</p>
25.16	Fence, bears N. and S.
39.00	Track road, 12 ft. wide, bears E., S. and N. 10° W.
40.05	<p>Point for the 1/4 sec. cor. of secs. 26 and 35, at proportionate dist.; there is no remaining evidence of the orig. cor.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, in a collar of stone, with brass cap mkd.</p> <div style="text-align: center;"> <p>T 14 S R 10 E S 26 1/4 ——— S 35</p> <p>2009</p> </div>

**Dependent Resurvey of the Sectional Correction Line,  
T. 14 S., R. 10 E., Gila and Salt River Meridian, Arizona**

CHAINS							
	<p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p>						
	<p>Set a steel fence post as a guard post.</p>						
	<p>Cor. is located 15 lks. S. of a fence, bearing E. and W.</p>						
	<p>From this cor. point, a cor. of fences extending N., E. and W., bears N. 82° E., 1.18 chs. dist.</p>						
	<p>Also from this cor. point, an iron post, 1 in. diam., firmly set, 2 ins. below the ground, with an alum. cap mkd. T14SR10E 26 1/4 35 RLS 13564, set by Robert Douglas Miller, Arizona Registered Land Surveyor 13564, in an un-recorded survey, bears S. 88°53' E., 11 lks. dist. This monument was not utilized in the course of this survey.</p>						
78.20	<p>Double pole utility line, bears N. and S.</p>						
79.40	<p>Track road for utility line, 15 ft. wide, bears N. 30° E. and S. 30° E.</p>						
80.10	<p>The cor. of secs. 26, 27, 34 and 35, monumented with a granite stone, 17 X 9 X 6 ins., firmly set, 13 ins. in the ground, mkd. with 1 notch on the S. and 2 notches on the E. edges, with a scattered mound of stone N. of the cor.</p>						
	<p>At the corner point</p>						
	<p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, in a collar of stone, with brass cap mkd.</p>						
	<table border="0" style="margin-left: auto; margin-right: auto;"> <tr> <td>T 14 S</td> <td>R 10 E</td> </tr> <tr> <td>S 27</td> <td>S 26</td> </tr> <tr> <td>S 34</td> <td>S 35</td> </tr> </table>	T 14 S	R 10 E	S 27	S 26	S 34	S 35
T 14 S	R 10 E						
S 27	S 26						
S 34	S 35						
	<p align="center">2009</p>						
	<p>Deposit a magnet, in a white plastic case, at the base and the mkd. stone alongside of the stainless steel post.</p>						
	<p>Set a steel fence post as a guard post.</p>						
	<p>Cor. is located 11 lks. S. of a fence bearing E. and W.</p>						
	<hr/> <p>S. 89°52' W., on the sectional correction line bet. secs. 27 and 34.</p>						
	<p>Ascending over rocky terrain.</p>						

**Dependent Resurvey of the Sectional Correction Line,  
T. 14 S., R. 10 E., Gila and Salt River Meridian, Arizona**

CHAINS					
33.40	<p>Wash, 12 ft. wide, 3 ft. deep, drains N. 40° E., from S. 10° W. (Record: 34.10 chs.)</p>				
40.02	<p>The 1/4 sec. cor. of secs. 27 and 34, monumented with a granite stone, 14 X 11 X 7 ins., firmly set, 8 ins. the ground, mkd. 1/4 on N. face.</p> <p>At the corner point</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, in a collar of stone, with brass cap mkd.</p> <div style="text-align: center;"> <p>T 14 S R 10 E</p> <p>S 27</p> <p>1/4 ———</p> <p>S 34</p> <p>2009</p> </div> <p>Deposit a magnet, in a white plastic case, at the base and the mkd. stone alongside of the stainless steel post.</p> <p>Cor. is located 3 lks. S. of a fence bearing E. and W.</p> <hr style="width: 20%; margin: auto;"/> <p>S. 89°55' W., beginning new measurement.</p> <p>Ascending over increasingly steep terrain.</p>				
40.02	<p>The cor. of secs. 27, 28, 33 and 34, monumented with a granite stone, 19 X 9 X 9 ins., firmly set 11 ins. in the ground, mkd. with 1 notch on the S. and 3 notches on the E. edges, and a scattered mound of stone W. of the cor.</p> <p>from which the remains of the orig. bearing trees</p> <p style="padding-left: 40px;">A forked ironwood, with a 4 ins. diam. rotten trunk, bears S. 42 1/4° E., 93 lks. dist., with no marks.</p> <p style="padding-left: 40px;">An ironwood, 9 ins. diam., bears N. 39°50' W., 1.51 chs. dist., with no marks visible on a partially healed blaze.</p> <p>At the corner point</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, in a collar of stone, with brass cap mkd.</p> <div style="text-align: center;"> <p>T 14 S R 10 E</p> <table style="margin: auto; border-collapse: collapse;"> <tr> <td style="border-right: 1px solid black; padding: 0 10px;">S 28</td> <td style="padding: 0 10px;">S 27</td> </tr> <tr> <td style="border-right: 1px solid black; padding: 0 10px;">S 33</td> <td style="padding: 0 10px;">S 34</td> </tr> </table> <p>2009</p> </div>	S 28	S 27	S 33	S 34
S 28	S 27				
S 33	S 34				

**Dependent Resurvey of the Sectional Correction Line,  
T. 14 S., R. 10 E., Gila and Salt River Meridian, Arizona**

CHAINS	
	<p>Deposit a magnet, in a white plastic case, at the base and the mkd. stone alongside of the stainless steel post.</p> <p>Rebuild accessory mound of stone 3 ft. base, 2 ft. high W. of cor.</p> <p>Cor. is located 2 lks. S. of a fence bearing E. and W.</p>
	<p align="center">Restoring the survey executed by Charles E. Hunter, in 1925</p>
	<p>S. 89°59' W., on the sectional correction line bet. secs. 28 and 33.</p>
	<p>Ascending the foothills of the Roskruge Mountains.</p>
40.10	<p>The 1/4 sec. cor. of secs. 28 and 33, monumented with an iron post, 1 in. diam., firmly set, projecting 11 ins. above the ground, with brass cap mkd. S28 1/4 S33 1925.</p>
	<p>from which the remains of the orig. bearing trees</p>
	<p>A nail set at the rotten remains of a palo verde, of indeterminate diam., bears S. 39°32' E., 19.6 lks. dist., with no marks. (Record: S. 28 1/2° E., 21 lks.)</p>
	<p>A nail set at the rotten remains of a palo verde, of indeterminate diam., bears N. 75°23' W., 42.3 lks. dist., with no marks. (Record: N. 81 1/2° W., 41 lks.)</p>
	<p>Add the marks T14S R10E 2009 to the brass cap.</p>
	<p>Raise a mound of stone, 3 ft. base to top of iron post.</p>
	<p>Cor. is located 1 lk. S. of a fence bearing E. and W.</p>
	<p>West, beginning new measurement.</p>
	<p>Steeply ascending the foothills, into the Roskruge Mountains.</p>
40.13	<p>The cor. of secs. 28, 29, 32 and 33, monumented with an iron post, 2 ins. diam., firmly set, projecting 6 ins. above a supporting mound of stone, 3 ft. base, 1 1/2 ft. high, with brass cap mkd. T14S R10E S29 S28 S32 S33 1925.</p>
	<p>Add the marks 2009 to the brass cap.</p>

**Dependent Resurvey of the Sectional Correction Line,  
T. 14 S., R. 10 E., Gila and Salt River Meridian, Arizona**

CHAINS	
	<p>Cor. is located 2 lks. N. of a fence bearing E. and W. on the steep NE face of a ridge bearing SE and NW, approximately 25 ft. below the ridge top.</p> <hr/> <p>S. 89°57' W., on the sectional correction line bet. secs. 29 and 32.</p> <p>Descending over rocky terrain.</p>
39.95	<p>The 1/4 sec. cor. of secs. 29 and 32, monumented with an iron post, 1 in. diam., firmly set, projecting 7 ins. above a supporting mound of stone, 3 ft. base, 1 1/2 ft. high, with brass cap mkd. S29 1/4 S32 1925.</p> <p>Add the marks T14S R10E 2009 to the brass cap.</p> <p>Cor. is located 2 lks. N. of a fence bearing E. and W.</p> <hr/> <p>S. 89°59' W., beginning new measurement.</p> <p>Descending into valley in the Roskruge Mountains.</p>
34.40	<p>Track road, 9 ft. wide, bears N. 35° E. and S. 60° W.</p>
40.05	<p>The cor. of secs. 29, 30, 31 and 32, monumented with an iron post, 2 ins. diam., firmly set, projecting 8 ins. above a supporting mound of stone, 3 ft. base, 1 1/2 ft. high, with brass cap mkd. T14S R10E S30 S29 S31 S32 1925.</p> <p>from which the remains of the orig. bearing tree</p> <p style="padding-left: 40px;">A nail set at the rotten remains of a palo verde, of indeterminate diam., bears N. 28°02' E., 96.7 lks. dist., with no marks. (Record: N. 27° E., 96 lks.)</p> <p>Add the marks 2009 to the brass cap.</p> <p>Cor. is located in a fence bearing E. and W.</p> <hr/>
39.99	<p>S. 89°59' W., on the sectional correction line bet. secs. 30 and 31.</p> <p>Generally ascending over valley floor.</p> <p>The 1/4 sec. cor. of secs. 30 and 31, monumented with an iron post, 1 in. diam., firmly set, projecting 6 ins. above a mound of stone, 3 1/2 ft. base, 1 ft. high, with brass cap mkd. S30 1/4 S31 1925.</p> <p>Add the marks T14S R10E 2009 to the brass cap.</p>

**Dependent Resurvey of the Sectional Correction Line,  
T. 14 S., R. 10 E., Gila and Salt River Meridian, Arizona**

CHAINS

Cor. is located in a fence bearing E. and W.

N. 89°53' W., beginning new measurement.

Ascending over rocky terrain.

39.88

At proportionate position find the orig. cor. disturbed, with an iron post, 2 ins. diam., 36 ins. long, loosely wired to a cor. of fences extending E. and S., 15 lks., S. 56°47' E., of the cor. position, with marks 1925 visible on an otherwise illegible brass cap.

Reset the iron post, 18 ins. in the ground, in a supporting mound of stone, 4 ft. base, to top, with brass cap remarked

T 14 S		T 14 S	
R 9 E		S 30	
		-----	CC
S 25		S 31	
		R 10 E	

2009

Deposit a magnet, in a white plastic case, at the base of the iron post.

From this cor. point, the 1/4 sec. cor. of sec. 25 only, T. 14 S., R. 9 E., monumented with an iron post, 1 in. diam., firmly set, projecting 10 ins. above the ground, with brass cap mkd. 1/4 S25 1925, with a mound of stone 3 ft. base, 2 ft. high, W. of the cor., bears N. 0°09' W., 24.25 chs. dist. Add the marks T14S R9E R10E 2009 to the brass cap.

From this same cor. point, the cor. of secs. 25 and 36 only, T. 14 S., R. 9 E., monumented with an iron post, 2 ins. diam., firmly set, projecting 11 ins. above a supporting mound of stone, 4 ft. base, 2 ft. high, with brass cap mkd. T14S R9E S25 S36 1925, bears S. 0°09' E., 15.68 chs. dist. Add the marks T14S R10E S31 2009 to the brass cap. Cor. is located at cor. of fences extending N. and W.

**Dependent Resurvey of a Portion of the Subdivisional Lines,  
T. 14 S., R. 10 E., Gila and Salt River Meridian, Arizona**

Restoring the survey executed by  
Philip Contzen, in 1903

**Dependent Resurvey of a Portion of the Subdivisional Lines,  
T. 14 S., R. 10 E., Gila and Salt River Meridian, Arizona**

CHAINS	
	From the cor. of secs. 25, 26, 35 and 36.
	N. 0°08' W., bet. secs. 25 and 26.
	Over nearly level desert.
1.55	Single pole utility line, bears N. 30° E. and S. 30° W.
40.04	Point for the 1/4 sec. cor. of secs. 25 and 26, at proportionate dist.; there is no remaining evidence of the orig. cor.
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, in a collar of stone, with brass cap mkd.
	<p align="center">T 14 S R 10 E                    1/4                    S 26   S 25</p>
	2009
	Deposit a magnet, in a white plastic case, at the base of the stainless steel post.
40.32	Curved fence, bears S. 30° E. and N. 45° W.
77.90	Track road, 10 ft. wide, bears E. and N. 85° W.
80.08	Point for the cor. of secs. 23, 24, 25 and 26, at proportionate dist.; there is no remaining evidence of the orig. cor.
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 23 ins. in the ground, in a collar of stone, with brass cap mkd.
	<p align="center">T 14 S R 10 E            S 23   S 24            S 26   S 25</p>
	2009
	Deposit a magnet, in a white plastic case, at the base of the stainless steel post.
	<hr/> From the cor. of secs. 19, 24, 25 and 30, on the 2nd Guide Mer. E., the E. bdy of the Tp., hereinbefore described.
	S. 89°58' W., bet. secs. 24 and 25.
	Over nearly level terrain.
40.10	Point for the 1/4 sec. cor. of secs. 24 and 25, at proportionate dist.; there is no remaining evidence of the orig. cor.

**Dependent Resurvey of a Portion of the Subdivisional Lines,  
T. 14 S., R. 10 E., Gila and Salt River Meridian, Arizona**

CHAINS	
	<p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, in a collar of stone, with brass cap mkd.</p> <p align="center">T 14 S R 10 E S 24 1/4 ——— S 25</p> <p align="center">2009</p> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p> <p>From this cor. point, an iron post, 1 in. diam., firmly set, projecting 6 ins. above the ground, presumably set by Robert Douglas Miller, Arizona Registered Land Surveyor 13564, in an unrecorded survey, bears N. 69°49' E., 28 lks. dist. This monument was not utilized in the course of this survey.</p> <p>From this same cor. point, three rebar, 1/2 in. diam., with brass tags mkd. PC DOT 24 REF, are firmly set as follows: The first, projecting 4 ins. above the ground, bears N. 58°05' E., 84.9 lks. dist., the second, projecting 2 ins. above the ground, bears N. 85°06' E., 66.3 lks. dist., the third, projecting 3 ins. above the ground, bears N. 29°51' W., 52.9 lks. dist.</p> <p>Also from this same cor. point, a rebar, 1/2 in. diam., firmly set, projecting 1 in. above the ground, at center of aerial panel, bears N. 80°28' E., 76 lks. dist.</p> <p>Cor. is located 25 lks. S. of track road, 9 ft. wide, bearing E. and W.</p>
41.30	Single pole utility line, bears N. 30° E. and S. 30° W.
63.60	From this point, a brass disc, 3 ins. diam., set flush in a concrete cylinder, 12 ins. diam., projecting 2 ins. above the ground, mkd. BM 296 2316 FT, bears N., 38 lks. dist.
80.20	The cor. of secs. 23, 24, 25 and 26.
	<hr/> <p>N. 0°07' W., bet. secs. 23 and 24.</p> <p>Over nearly level desert.</p>
0.33	Fence bears E. and W.
39.99	Fence, bearing E. and W.
40.04	Point for the 1/4 sec. cor. of secs. 23 and 24, at proportionate dist.; there is no remaining evidence of the orig. cor.

**Dependent Resurvey of a Portion of the Subdivisional Lines,  
T. 14 S., R. 10 E., Gila and Salt River Meridian, Arizona**

<p>CHAINS</p>	<p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, in a collar of stone, with brass cap mkd.</p> <p align="center">T 14 S R 10 E 1/4 S 23   S 24</p> <p align="center">2009</p> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p> <p>From this cor. point, an iron post, 1 in. diam., firmly set, projecting 8 ins. above the ground, with an alum. cap mkd. T14S R10E, presumably set by Robert Douglas Miller, Arizona Registered Land Surveyor 13564, in an un-recorded survey, bears N. 86°09' E., 16 lks. dist. This monument was not utilized in the course of this survey.</p>
<p>80.08</p>	<p>Point for the cor. of secs. 13, 14, 23 and 24, at proportionate dist.; there is no remaining evidence of the orig. cor.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, in a collar of stone, with brass cap mkd.</p> <p align="center">T 14 S R 10 E S 14   S 13 S 23   S 24</p> <p align="center">2009</p> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p> <p>From this cor. point, an iron post, 1 in. diam., firmly set, projecting 8 ins. above the ground, with an alum. cap mkd. T14S R10E 14 13 23 24 RLS 13564, set by Robert Douglas Miller, Arizona Registered Land Surveyor 13564, in an un-recorded survey, bears N. 84°08' E., 12 lks. dist. This monument was not utilized in the course of this survey</p> <p>Cor. is located 1 1/2 lks. S. of fence bearing E. and W.</p> <hr/> <p>From the point for the cor. of secs. 13, 18, 19 and 24, on the 2nd Guide Mer. E., the E. bdy. of the Tp., at proportionate dist.; there is no remaining evidence of the orig. cor. Position falls in an irrigated field of Schuk Toak Farms, not monumented.</p> <p>From this point, the cor. of secs. 19, 24, 25 and 30, on the 2nd Guide Mer. E., the E. bdy. of the Tp., bears S. 0°03' E., 79.93 chs. dist.</p>

**Dependent Resurvey of a Portion of the Subdivisional Lines,  
T. 14 S., R. 10 E., Gila and Salt River Meridian, Arizona**

CHAINS	
	<p>From this same point, the cor. of secs. 7, 12, 13 and 18, monumented with a stainless steel post, 2 1/2 ins. diam., firmly set, projecting 6 ins. above the ground, in a collar of stone, with brass cap mkd. T14S R10E R11E S12 S7 S13 S18 2003 2008, bears N. 0°03' W., 79.93 chs. dist.</p>
	<p>N. 89°56' W., bet. secs. 13 and 24.</p>
	<p>Over irrigated field.</p>
36.90	<p>Bladed dirt road around farm fields, 20 ft. wide, bears S. 10° E. and N. 5° W.</p>
38.30	<p>Garcia Ranch Road, bladed dirt, 15 ft. wide, bears S. 45° E. and N. 52° W.</p>
40.14	<p>Point for the 1/4 sec. cor. of secs. 13 and 24, at proportionate dist.; there is no remaining evidence of the orig. cor.</p>
	<p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 25 ins. in the ground, in a collar of stone, with brass cap mkd.</p>
	<p align="center">T 14 S R 10 E S 13 1/4 ——— S 24</p>
	<p align="center">2009</p>
	<p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p>
	<p>From this cor. point, a cor. of fences extending N. 30° E. and S. 50° W., bears N. 53°13' E., 76 lks. dist.</p>
	<p>Also from this cor. point, a cor. of fences extending N. 50° E., S. 10° E. and S. 80° W., bears N. 45°55' W., 20 lks. dist.</p>
40.28	<p>Fence bearing S. 10° E. and N. 10° W.</p>
40.90	<p>Single pole utility line, bearing S. 20° E. and N. 20° W.</p>
43.80	<p>From this point, a well casing, 8 ins. diam., projecting 9 ins. above a square concrete pad, 6 X 6 ft., bears N., 44 lks. dist.</p>
44.21	<p>From this point, a rebar, 1 in. diam., firmly set, projecting 2 ins. above the ground, bears N., 38 lks. dist.</p>
80.28	<p>The cor. of secs. 13, 14, 23 and 24.</p>
	<hr/> <p>N. 0°07' W., bet. secs. 13 and 14.</p>

**Dependent Resurvey of a Portion of the Subdivisional Lines,  
T. 14 S., R. 10 E., Gila and Salt River Meridian, Arizona**

CHAINS	
	Over nearly level desert, broken by many small washes.
1.40	Garcia Ranch Road, bladed dirt, 20 ft. wide, bears N. 80° E. and S. 80° W.
40.04	Point for the 1/4 sec. cor. of secs. 13 and 14, at proportionate dist.; there is no remaining evidence of the orig. cor.
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 25 ins. in the ground, in a collar of stone, with brass cap mkd.
	<p align="center">T 14 S R 10 E  1/4  S 14   S 13  2009</p>
	Deposit a magnet, in a white plastic case, at the base of the stainless steel post.
	Set a steel fence post as a guard post.
	From this cor. point, an iron post, 1 in. diam., firmly set, flush with the ground, presumably set by Robert Douglas Miller, Arizona Registered Land Surveyor 13564, in an un-recorded survey, bears N. 58°52' E., 2 lks. dist. This monument was not utilized in the course of this survey.
80.08	The cor. of secs. 11, 12, 13 and 14, determined from the remains of the orig. bearing trees
	A mesquite, 5 ins. diam., bears N. 41 3/4° E., 1.13 chs. dist., with no marks.
	A mesquite stump, 16 ins. diam., with fork 12 ins. diam., bears S. 22 1/2° E., 5.71 chs. dist., with axe marks and faint BT on partial blaze. (Record: 5.36 chs.)
	A burned mesquite stump, 10 ins. diam., bears S. 75 3/4° W., 2.52 chs. dist., with no marks. (Record: S. 76 1/4° W.)
	A mesquite, 5 ins. diam., partially dead, bears N. 70 3/4° W., 6.00 chs. dist., with no marks.
	At the corner point
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., flush with the ground, with brass cap mkd.

Dependent Resurvey of a Portion of the Subdivisional Lines,  
T. 14 S., R. 10 E., Gila and Salt River Meridian, Arizona

CHAINS	<div style="text-align: center; margin-bottom: 10px;"> <table style="margin: auto; border-collapse: collapse;"> <tr> <td style="padding: 0 5px;">T 14 S</td> <td style="padding: 0 5px;">R 10 E</td> </tr> <tr> <td style="padding: 0 5px; border-right: 1px solid black;">S 11</td> <td style="padding: 0 5px;">S 12</td> </tr> <tr> <td style="padding: 0 5px; border-right: 1px solid black;">S 14</td> <td style="padding: 0 5px;">S 13</td> </tr> </table> </div> <div style="text-align: center; margin-bottom: 10px;">2009</div> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p> <p>From this cor. point, a rebar, 1/2 in. diam., firmly set flush with the ground, at center of aerial panel with no tag, bears S. 11°27' E., 3.6 lks. dist.</p> <p>From this same cor. point, a rebar, 1/2 in. diam., firmly set flush with the ground, at center of aerial panel with no tag, bears S. 41°29' W., 35 lks. dist., located in track road, 12 ft. wide, bearing N. 10° E. and S. 10° W.</p> <p>Cor. is located 1 lk. S. of a cor. of fences extending N., E. and W. and 15 lks. E., of track road, 12 ft. wide, bearing N. and S. 10° W.</p> <hr style="width: 50%; margin: 10px auto;"/> <p>From the cor. of secs. 7, 12, 13 and 18, on the 2nd Guide Mer. E., the E. bdy. of the Tp.</p> <p>N. 89°49' W., bet. secs. 12 and 13.</p> <p>Over level terrain, broken by small washes.</p> <p>40.18 Point for the 1/4 sec. cor. of secs. 12 and 13, at proportionate dist.; there is no remaining evidence of the orig. cor.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., flush with the ground, underpinned with a galvanized sign post, 5 ft. long, in a collar of stone, with brass cap mkd.</p> <div style="text-align: center; margin-bottom: 10px;"> <table style="margin: auto; border-collapse: collapse;"> <tr> <td style="padding: 0 5px;">T 14 S</td> <td style="padding: 0 5px;">R 10 E</td> </tr> <tr> <td></td> <td style="padding: 0 5px;">S 12</td> </tr> <tr> <td></td> <td style="padding: 0 5px;">1/4 ———</td> </tr> <tr> <td></td> <td style="padding: 0 5px;">S 13</td> </tr> </table> </div> <div style="text-align: center; margin-bottom: 10px;">2009</div> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p> <p>Set a steel fence post as a guard post.</p> <p>From this cor. point, an iron pipe, 2 1/2 ins. diam., with threaded pipe end cap, firmly set 3 ins. below ground, bears N. 11°41' W., 22 lks. dist.</p>	T 14 S	R 10 E	S 11	S 12	S 14	S 13	T 14 S	R 10 E		S 12		1/4 ———		S 13
T 14 S	R 10 E														
S 11	S 12														
S 14	S 13														
T 14 S	R 10 E														
	S 12														
	1/4 ———														
	S 13														

**Dependent Resurvey of a Portion of the Subdivisional Lines,  
T. 14 S., R. 10 E., Gila and Salt River Meridian, Arizona**

CHAINS	
	Cor. is located 20 lks. S. of fence bearing E. and W., in a small wash, 2 ft. deep, 7 ft. wide, drains N. 45° E., from S. 30° W.
40.85	Single pole utility line, bears N. and S.
41.45	Track road for utility line, 12 ft. wide, bears N. 30° E. and S.
80.36	The cor. of secs. 11, 12, 13 and 14. <hr/>
	From the cor. of secs. 26, 27, 34 and 35, on the sectional correction line.
	N. 0°03' W., bet. secs. 26 and 27.
	Gently descending through desert, broken by many small washes.
40.04	The 1/4 sec. cor. of secs. 26 and 27, monumented with the rotten remains of a mesquite post, 3 ins. below the ground. Two fragments of a mesquite post, 10 ins. long each, lay loose in a scattered mound of stone. An iron post, 1 in. diam., firmly set, projecting 1 in. above the ground, with alum. cap mkd. T14S R10E S27 S26 1/4 RLS 13564, set by Robert Douglas Miller, Arizona Registered Land Surveyor 13564, in an un-recorded survey, is alongside.
	At the corner point
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 23 ins. in the ground, in a collar of stone, with brass cap mkd.
	T 14 S R 10 E
	1/4
	S 27   S 26
	2009
	Deposit a magnet, in a white plastic case, at the base, and the 3 ft. long iron post alongside of the stainless steel post. Place the remains of the wood post on the collar of stone.
	Set a steel fence post as a guard post. <hr/>
	N. 0°08' W., beginning new measurement.
	Gently descending.
2.40	Small wash, 5 ft. wide, 1 ft. deep, drains N. 25° E., from S. 35° W. (Record: 2.30 chs.)

**Dependent Resurvey of a Portion of the Subdivisional Lines,  
T. 14 S., R. 10 E., Gila and Salt River Meridian, Arizona**

CHAINS	
40.05	<p>Point for the cor. of secs. 22, 23, 26 and 27, at proportionate dist.; there is no remaining evidence of the orig. cor.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., flush with the ground, with brass cap mkd.</p> <p align="center">           T 14 S   R 10 E            S 22   S 23            S 27   S 26            2009         </p> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p> <p>From this cor. point, an iron post, 1 in. diam., firmly set 3 ins. below the ground, with an alum. cap mkd. T14S R10E 22 23 27 26 RLS 13564, set by Robert Douglas Miller, Arizona Registered Land Surveyor 13564, in an un-recorded survey, bears S. 72°50' E., 7 lks. dist. This monument was not utilized in the course of this survey.</p>
	<p>From the cor. of secs. 23, 24, 25 and 26.</p> <p>S. 89°53' W., bet. secs. 23 and 26.</p> <p>Gently ascending over nearly level terrain.</p>
20.005	<p>Point for the E. 1/16 sec. cor. of secs. 23 and 26.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 25 ins. in the ground, in a collar of stone, with brass cap mkd.</p> <p align="center">           S 23            E 1/16 ———            S 26            2009         </p> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p> <p>Located 25 lks. N. of track road, 8 ft. wide, bearing E. and W.</p>
40.01	<p>Point for the 1/4 sec. cor. of secs. 23 and 26, at proportionate dist.; there is no remaining evidence of the orig. cor.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 25 ins. in the ground, with brass cap mkd.</p>

**Dependent Resurvey of a Portion of the Subdivisional Lines,  
T. 14 S., R. 10 E., Gila and Salt River Meridian, Arizona**

CHAINS	
	T 14 S R 10 E S 23 1/4 ——— S 26  2009
	Deposit a magnet, in a white plastic case, at the base of the stainless steel post.  Set a steel fence post as a guard post.  From this cor. point, an iron post, 1 in. diam., firmly set, projecting 2 ins. above the ground, with alum. cap mkd. T14S 23 1/4 26 R10E, presumably set by Robert Douglas Miller, Arizona Registered Land Surveyor 13564, in an un-recorded survey, bears S. 86°00' E., 14 lks. dist. This monument was not utilized in the course of this survey.
42.34	Fence bearing N. and S.
76.15	Two pole utility line, with track road, 10 ft. wide, both bear N. and S.
77.80	Confluence of two small washes, 3 ft. wide, 3 ft. deep, drains N. 18° E., from S. 8° E., and S. 48° W.
80.02	The cor. of secs. 22, 23, 26 and 27.
	<hr/> N. 89°59' W., bet. secs. 22 and 27.  Over nearly level desert.
40.05	The 1/4 sec. cor. of secs. 22 and 27, monumented with a granite stone, 19 X 12 X 5 ins., firmly set 10 ins. in the ground, mkd. 1/4 on N. face, and a scattered mound of stone N. of the cor.  from which the orig. bearing tree  A mesquite, 6 ins. diam., bears N. 2 1/2° E., 1.00 ch. dist., with no marks visible on extremely weathered blaze.  At the corner point  Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, in a collar of stone, with brass cap mkd.

**Dependent Resurvey of a Portion of the Subdivisional Lines,  
T. 14 S., R. 10 E., Gila and Salt River Meridian, Arizona**

CHAINS	
	T 14 S R 10 E S 22 1/4 ——— S 27  2009
	Deposit a magnet, in a white plastic case, at the base, and the mkd. stone alongside of the stainless steel post.  Set a steel fence post as guard post.  <hr/> From the cor. of secs. 22, 23, 26 and 27.  N. 0°14' W., bet. secs. 22 and 23.  Gently descending over nearly level terrain, with small washes.
0.18	From this point, a railroad tie post, the SW cor. of a cemetery, bears E., 5 lks. dist.
0.83	From this point, the SW cor. of the base of a marble headstone, 3.5 X 1.2 ft., with the names Richard and Alice Paul, bears E., 77 lks. dist.
1.16	The NW cor. of cemetery, a railroad tie post.
40.05	The 1/4 sec. cor. of secs. 22 and 23, determined from the remains of the orig. bearing trees  A rotten mesquite stump, 10 ins. diam., bears S. 27° E., 1.11 chs. dist., with no marks.  A mesquite stump, 13 ins. diam., with fork 6 ins. diam., bears S. 44° W., 77 lks. dist., with no marks.  At the corner point  Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.
	T 14 S R 10 E 1/4 S 22   S 23  2009
	Deposit a magnet, in a white plastic case, at the base of the stainless steel post.  Set a steel fence post as guard post.

**Dependent Resurvey of a Portion of the Subdivisional Lines,  
T. 14 S., R. 10 E., Gila and Salt River Meridian, Arizona**

CHAINS							
	<p>From this cor., an iron post, 1 in. diam., firmly set, flush with the ground, with alum. cap mkd. T14S R10E 1/4 22 23 RLS 13564, set by Robert Douglas Miller, Arizona Registered Land Surveyor 13564, in an un-recorded survey, bears S. 75°13' E., 11 lks. dist. This monument was not utilized in the course of this survey.</p> <hr/> <p>N. 0°08' W., beginning new measurement.</p> <p>Gently descending.</p>						
40.02	<p>Point for the cor. of secs. 14, 15, 22 and 23, at proportionate dist.; there is no remaining evidence of the orig. cor.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, in a collar of stone, with brass cap mkd.</p> <table border="1" data-bbox="792 842 1019 947" style="margin-left: auto; margin-right: auto;"> <tr> <td colspan="2" style="text-align: center;">T 14 S R 10 E</td> </tr> <tr> <td style="text-align: center;">S 15</td> <td style="text-align: center;">S 14</td> </tr> <tr> <td style="text-align: center;">S 22</td> <td style="text-align: center;">S 23</td> </tr> </table> <p style="text-align: center;">2009</p> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p> <p>Set a steel fence post as guard post.</p> <p>From this cor., an iron post, 1 in. diam., firmly set, flush with the ground, with alum. cap mkd. T14S S15 S14 S22 S23 RLS 13564, set by Robert Douglas Miller, Arizona Registered Land Surveyor 13564, in an un-recorded survey, bears S. 78°11' E., 8 lks. dist. This monument was not utilized in the course of this survey.</p> <hr/>	T 14 S R 10 E		S 15	S 14	S 22	S 23
T 14 S R 10 E							
S 15	S 14						
S 22	S 23						
40.055	<p>From the cor. of secs. 13, 14, 23 and 24.</p> <p>S. 89°52' W., bet. secs. 14 and 23.</p> <p>Over nearly level terrain.</p> <p>Point for the 1/4 sec. cor. of secs. 14 and 23, at proportionate dist.; there is no remaining evidence of the orig. cor.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 27 ins. in the ground, in a collar of stone, with brass cap mkd.</p>						

Dependent Resurvey of a Portion of the Subdivisional Lines,  
T. 14 S., R. 10 E., Gila and Salt River Meridian, Arizona

CHAINS	
	<p style="text-align: center;">T 14 S R 10 E S 14 1/4 ——— S 23  2009</p>
	<p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p>
	<p>Set a steel fence post as guard post.</p>
	<p>Cor. is located at projected fence cor. of fences extending E. and S.</p>
77.45	<p>Fence bearing N. and S.</p>
78.10	<p>Two pole utility line, with track road 10 ft. wide, bearing N. and S. 5° E.</p>
80.11	<p>The cor. of secs. 14, 15, 22 and 23.</p> <hr/>
	<p>S. 89°59' W., bet. secs. 15 and 22.</p> <p>Gently ascending over nearly level desert.</p>
40.05	<p>The 1/4 sec. cor. of secs. 15 and 22, monumented with a limestone, 12 X 12 X 10 ins., firmly set 6 ins. in the ground, mkd. 1/4 on N. face, with a scattered mound of stone N. of the cor.</p>
	<p>from which the remains of the orig. bearing trees</p>
	<p style="padding-left: 40px;">A rotten mesquite stump, 10 ins. diam., in a cluster of trunks, bears S. 29 1/2° E., 73 lks. dist., with no marks. (Record: S. 25 3/4° E.)</p>
	<p style="padding-left: 40px;">A palo verde stump, 12 ins. diam., bears N. 25° W., 1.95 chs. dist., with no marks. (Record: N. 26 1/4° W.)</p>
	<p>At the corner point</p>
	<p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 23 ins. in the ground, in a collar of stone, with brass cap mkd.</p>

**Dependent Resurvey of a Portion of the Subdivisional Lines,  
T. 14 S., R. 10 E., Gila and Salt River Meridian, Arizona**

CHAINS	
	<p align="center">T 14 S R 10 E S 15 1/4 ——— S 22  2009</p>
	<p>Deposit a magnet, in a white plastic case, at the base, and the mkd. stone alongside of the stainless steel post.</p> <p>Cor. is located 36 lks. S. of dirt road, 13 ft. wide, bearing S. 55° E. and N. 55° W.</p> <hr/>
	<p>From the cor. of secs. 14, 15, 22 and 23.</p>
	<p>N. 0°08' W., bet. secs. 14 and 15.</p>
	<p>Gently descending over desert broken by small washes.</p>
36.15	<p>Small wash, 5 ft. wide, 2 ft. deep, drains N. 20° E. from S. 30° W.</p>
37.50	<p>Small wash, 9 ft. wide, 3 ft. deep, drains N. 10° E. from S. 40° W.</p>
40.02	<p>Point for the 1/4 sec. cor. of secs. 14 and 15, at proportionate dist.; there is no remaining evidence of the orig. cor.</p>
	<p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., flush with the ground, in a collar of stone, with brass cap mkd.</p>
	<p align="center">T 14 S R 10 E 1/4 S 15   S 14  2009</p>
	<p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p>
	<p>Set a steel fence post as a guard post.</p>
	<p>From this cor. point, an iron post, 1 in. diam., firmly set, flush with the ground, with alum. cap mkd. T14S R10E 1/4 15 14 RLS 13564, set by Robert Douglas Miller, Arizona Registered Land Surveyor 13564, in an un-recorded survey, bears S. 79°22' W., 1 lk. dist. This monument was not utilized in the course of this survey.</p>
80.04	<p>Point for the cor. of secs. 10, 11, 14 and 15, at proportionate dist.; there is no remaining evidence of the orig. cor.</p>

**Dependent Resurvey of a Portion of the Subdivisional Lines,  
T. 14 S., R. 10 E., Gila and Salt River Meridian, Arizona**

CHAINS	<p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with brass cap mkd.</p> <p align="center"> T 14 S R 10 E  S 10   S 11  S 15   S 14  2009 </p> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p> <p>Set a steel fence post as guard post.</p> <p>Cor. is located 3 lks., S. of fence bearing E. and W.</p> <p>From this cor. point, an iron post, 1 in. diam., firmly set, projecting 3 ins. above the ground, with alum. cap mkd. T14S R10E + RLS 13564, set by Robert Douglas Miller, Arizona Registered Land Surveyor 13564, in an un-recorded survey, bears N. 84°53' W., 10 lks. dist. This monument was not utilized in the course of this survey.</p> <hr/> <p>From the cor. of secs. 11, 12, 13 and 14.</p> <p>S. 89°51' W., bet. secs. 11 and 14.</p> <p>Over nearly level desert.</p> <p>40.05 Point for the 1/4 sec. cor. of secs. 11 and 14, at proportionate dist.; there is no remaining evidence of the orig. cor.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 25 ins. in the ground, in a collar of stone, with brass cap mkd.</p> <p align="center"> T 14 S R 10 E  S 11  1/4 ———  S 14  2009 </p> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p> <p>From this cor. point, an iron post, 1 in. diam., firmly set, projecting 5 ins. above the ground, with alum. cap mkd. T14S R10E, presumably set by Robert Douglas Miller, Arizona Registered Land Surveyor 13564, in an un-recorded survey, bears N. 83°46' W., 8 lks. dist. This monument was not utilized in the course of this survey.</p>
--------	---

**Dependent Resurvey of a Portion of the Subdivisional Lines,  
T. 14 S., R. 10 E., Gila and Salt River Meridian, Arizona**

CHAINS	
80.10	<p>The cor. of secs. 10, 11, 14 and 15.</p> <hr/> <p>N. 0°04' E., bet. secs. 10 and 11.</p> <p>Over nearly level terrain.</p>
40.02	<p>The 1/4 sec. cor. of secs. 10 and 11, determined from the remains of the orig. bearing trees</p> <p style="padding-left: 40px;">A mesquite stump, 10 ins. diam., bears N. 43° E., 1.02 chs. dist., with no marks.</p> <p style="padding-left: 40px;">A rotten mesquite stump, 16 ins. diam., bears S. 32 1/2° W., 1.31 chs. dist., with no marks.</p> <p>At the corner point</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 23 ins. in the ground, in a collar of stone, with brass cap mkd.</p> <p style="text-align: center;">T 14 S R 10 E 1/4 S 10   S 11</p> <p style="text-align: center;">2009</p> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p> <hr/>
	<p>From the cor. of secs. 10, 11, 14 and 15.</p> <p>West, bet. secs. 10 and 15.</p> <p>Gently ascending over desert with small washes.</p>
39.75	<p>Cor. of fences extending E., S. and W.</p>
40.00	<p>The 1/4 sec. cor. of secs. 10 and 15, monumented with a limestone, 18 X 12 X 7 ins., firmly set, 16 ins. in the ground, mkd. 1/4 on N. face.</p> <p>from which the remains of the orig. bearing tree</p> <p style="padding-left: 40px;">A forked palo verde, with a 16 ins. diam. rotten trunk, bears N. 5 1/4° W., 61 lks. dist., with no marks.</p> <p>At the corner point</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, in a collar of stone, with brass cap mkd.</p>

**Dependent Resurvey of a Portion of the Subdivisional Lines,  
T. 14 S., R. 10 E., Gila and Salt River Meridian, Arizona**

CHAINS	<p align="center">T 14 S R 10 E S 10 1/4 ——— S 15</p> <p align="center">2009</p> <p>Deposit a magnet, in a white plastic case, at the base and the mkd. stone alongside of the stainless steel post.</p> <p>Cor. is located in a fence, bearing E. and W.</p> <hr/> <p>S. 89°50' W., beginning new measurement.</p> <p>Generally ascending over nearly level terrain.</p> <p>40.12 The cor. of secs. 9, 10, 15 and 16, monumented with a granite stone, 14 X 9 X 7 ins., firmly set 11 ins. in the ground, in a collar of stone, mkd. with 3 notches on the E. and 4 notches on the S. edges.</p> <p>from which the remains of the orig. bearing trees</p> <p>A forked palo verde, with a 8 ins. diam. trunk, bears N. 24° E., 53 lks. dist., with no marks visible on a partially closed rotten blaze.</p> <p>A nail set at the rotten remains of a palo verde, of indeterminate diam., bears S. 59°07' E., 2.30 chs. dist., with no marks. (Record: S. 59° E., 2.31 chs.)</p> <p>A standing dead ironwood, 4 ins. diam., bears S. 54 3/4° W., 52 lks. dist., with no marks visible on a rotten blaze.</p> <p>At the corner point</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, in a collar of stone, with brass cap mkd.</p> <p align="center">T 14 S R 10 E S 9   S 10 S 16   S 15</p> <p align="center">2009</p> <p>Deposit a magnet, in a white plastic case, at the base and the mkd. stone alongside of the stainless steel post.</p> <p>Raise an accessory mound of stone 1 1/2 ft. base, 1 1/2 ft. high W. of the cor.</p>
--------	---

**Dependent Resurvey of a Portion of the Subdivisional Lines,  
T. 14 S., R. 10 E., Gila and Salt River Meridian, Arizona**

CHAINS	
	Cor. is located 1 lk. N. of fence bearing E. and W.
	S. 89°39' W., bet. secs. 9 and 16.
	Gently ascending over desert with many washes.
37.60	Wash, 66 ft. wide, 2 ft. deep, drains N. 55° E., from S. 35° W. (Record: 37.55 chs.)
39.92	The 1/4 sec. cor. of secs. 9 and 16, monumented with a quartzite stone, 14 X 8 X 6 ins., firmly set with the ground, in a collar of stone, mkd. with 1/4 on the N. face.
	from which the remaining orig. bearing tree
	An ironwood, 12 ins. diam., bears S. 19 1/2° E., 1.45 chs. dist., with no marks visible on mostly healed blaze.
	At the corner point
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 23 ins. in the ground, with brass cap mkd.
	<p style="text-align: center;">T 14 S R 10 E S 9 1/4 ——— S 16</p>
	2009
	Deposit a magnet, in a white plastic case, at the base and the mkd. stone alongside of the stainless steel post.
	Raise a mound of stone, 2 ft. base, 1 1/2 ft. high, N. of the cor.
	Cor. is located 1 1/2 lks. N. of fence bearing E. and W.
	S. 89°56' W., beginning new measurement.
	Over nearly level desert.
2.30	Wash, 25 ft. wide, 2 ft. deep, drains N. 25° W., from S. 25° E. (Record: 2.17 chs.)
40.01	Cor. of fences extending N., E. and W.
40.10	The cor. of secs. 8, 9, 16 and 17, monumented with a granite stone, 15 X 12 X 10 ins., firmly set, 8 ins. in the ground, mkd. with 4 notches on the E. and 4 notches on the S. edges.

**Dependent Resurvey of a Portion of the Subdivisional Lines,  
T. 14 S., R. 10 E., Gila and Salt River Meridian, Arizona**

CHAINS							
	<p>from which the remains of the orig. bearing trees</p> <p>A nail set at approximate base of a palo verde, 6 ins. diam., bears N. 44°01' E., 1.19 chs. dist., with no marks visible on extremely weathered blaze. (Record: N. 44 1/4° E., 1.20 chs.)</p> <p>A standing dead ironwood, 7 ins. diam., bears S. 72° E., 1.51 chs. dist., with marks T14SR10ES16BT carved on a weathered blaze.</p> <p>A palo verde, 8 ins. diam., bears S. 32 1/4° W., 34 lks. dist., with no marks.</p> <p>At the corner point</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 23 ins. in the ground, in a collar of stone, with brass cap mkd.</p> <table border="1" data-bbox="792 865 1019 970"> <tr> <td colspan="2">T 14 S R 10 E</td> </tr> <tr> <td>S 8</td> <td>S 9</td> </tr> <tr> <td>S 17</td> <td>S 16</td> </tr> </table> <p align="center">2009</p> <p>Deposit a magnet, in a white plastic case, at the base and the mkd. stone alongside of the stainless steel post.</p> <p>Cor. is located in fence bearing E. and W.</p> <hr/> <p>N. 89°56' W., bet. secs. 8 and 17.</p> <p>Ascending over the S. foot of Cocoraque Butte.</p> <p>39.43 Wash, 18 ft. wide, 2 ft. deep, drains S. 50° W., from N. 50° E. (Record: 38.70)</p> <p>40.88 The 1/4 sec. cor. of secs. 8 and 17, monumented with a granite stone, 14 X 12 X 6 ins., firmly set 9 ins. in the ground, mkd. 1/4 on N. face.</p> <p>from which the remains of the orig. bearing trees</p> <p>A nail set at the rotten remains of a palo verde, of indeterminate diam., bears N. 4°17' W., 32 lks. dist., with no marks visible on an extremely weathered blaze. (Record: N. 13 1/4° E., 22 lks.)</p> <p>An ironwood with multiple trunks and a 24 ins. diam. root base, bears S. 58° E., 22 lks. dist., with no marks. (Record: 30 lks.)</p>	T 14 S R 10 E		S 8	S 9	S 17	S 16
T 14 S R 10 E							
S 8	S 9						
S 17	S 16						

**Dependent Resurvey of a Portion of the Subdivisional Lines,  
T. 14 S., R. 10 E., Gila and Salt River Meridian, Arizona**

CHAINS	
	<p>At the corner point</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 22 ins. in the ground, in a collar of stone, with brass cap mkd.</p> <p align="center">T 14 S R 10 E S 8 1/4 ——— S 17</p> <p align="center">2009</p> <p>Deposit a magnet, in a white plastic case, at the base and the mkd. stone alongside of the stainless steel post.</p> <p>Raise a mound of stone 3 ft. base, 2 ft. high N. of the cor.</p> <p>Cor. is located 10 lks. N. of fence bearing E. and W.</p> <hr/> <p>S. 89°38' W., beginning new measurement.</p> <p>Descending over rocky terrain.</p>
14.62	Projected cor. of fences extending N., E. and W.
14.85	Track road, 15 ft. wide, bears S. and N. 30° W.
36.97	Cor. of fences extending E., S. 55° E. and W.
37.38	Cor. of fences extending N., E. and W.
38.05	<p>The cor. of secs. 7, 8, 17 and 18, monumented with a granite stone, 20 X 7 X 6 ins., firmly set 10 ins. in the ground, in a collar of stone, mkd. with 4 notches on the S. and 5 notches on the E. edges.</p> <p>from which the remains of the orig. bearing trees</p> <p align="center">An ironwood, 6 ins. diam., bears N. 27 1/4° E., 1.45 chs. dist., with axe marks but no blaze.</p> <p align="center">A palo verde, 8 ins. diam., bears S. 22 1/2° E., 91 lks. dist., with no marks visible on a rotten blaze.</p> <p align="center">An ironwood, with multiple trunks and an 18 ins. diam. root cluster, bears S. 52 1/4° W., 1.36 chs. dist., with axe marks but no blaze.</p> <p align="center">An ironwood, 4 ins. diam., bears N. 47 1/2° W., 2.09 chs. dist., with faint marks visible on an extremely weathered blaze.</p>

**Dependent Resurvey of a Portion of the Subdivisional Lines,  
T. 14 S., R. 10 E., Gila and Salt River Meridian, Arizona**

CHAINS	
	At the corner point
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 20 ins. in the ground, in a mound of stone, 4 ft. base to top, with brass cap mkd.
	<p align="center">T 14 S R 10 E  S 7   S 8  S 18   S 17</p>
	2008
	Deposit a magnet, in a white plastic case, at the base and the mkd. stone alongside of the stainless steel post.
	Cor. is located 2 lks. S. of fence bearing E. and W.
	S. 89°00' W., bet. secs. 7 and 18.
	Ascending over rocky desert.
36.60	Wash, 30 ft. wide, 5 ft. deep, drains N. 10° W., from S. 15° E. (Record: 35.83 chs.)
40.38	The 1/4 sec. cor. of secs. 7 and 18, monumented with a quartzite stone, 18 X 13 X 8 ins., firmly set 12 ins. in the ground, mkd. 1/4 on N. face, an embedded mound of stone 2 ft. diam., W. of the cor.
	from which the remains of the orig. bearing tree
	<p align="center">A nail set at approximate base of a dead palo verde, 6 ins. diam., bears N. 2°52' E., 93 lks. dist., with the rotten remains of a healed blaze.  (Record: N. 7 1/2° E., 90 lks.)</p>
	At the corner point
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 23 ins. in the ground, in a mound of stone, 3 ft. base, to top, with brass cap mkd.
	<p align="center">T 14 S R 10 E  S 7  1/4 ———  S 18</p>
	2008
	Deposit a magnet, in a white plastic case, at the base and the mkd. stone alongside of the stainless steel post.



**Subdivision of Section 23,  
T. 14 S., R. 10 E., Gila and Salt River Meridian, Arizona**

CHAINS	
37.41	From this point, a cor. of fences extending N., E. and S. bears E., 38 lks. dist.
37.92	From this point, the projected cor. of fences extending N., S. and W., bears E., 36 lks. dist.
40.04	Point for the center 1/4 sec. cor. of sec. 23, at intersection with the E. and W. center line.  Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 27 ins. in the ground, in a collar of stone, with brass cap mkd.  T 14 S R 10 E C 1/4 S 23  2009  Deposit a magnet, in a white plastic case, at the base of the stainless steel post.
80.07	The 1/4 sec. cor. of secs. 14 and 23. <hr/> From the 1/4 sec. cor. of secs. 23 and 24.  S. 89°53' W., on the E. and W. center line.
20.015	Point for the center E. 1/16 sec. cor. of sec. 23.  Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, in a collar of stone, with brass cap mkd.  T 14 S R 10 E E 1/16 C ——— C S 23  2009  Deposit a magnet, in a white plastic case, at the base of the stainless steel post.  From this cor. point, an iron post, 1 in. diam., firmly set, flush with the ground, with alum. cap mkd. T14S R10E, presumably set by Robert Douglas Miller, Arizona Registered Land Surveyor 13564, in an un-recorded survey, bears N. 89°14' E., 13.8 lks. dist. This monument was not utilized in the course of this survey.
39.69	Fence, bears N. and S.
40.03	The center 1/4 sec. cor. of sec. 23.

**Subdivision of Section 23,  
T. 14 S., R. 10 E., Gila and Salt River Meridian, Arizona**

CHAINS	
80.10	<p>The 1/4 sec. cor. of secs. 22 and 23.</p> <hr/> <p style="text-align: center;">SE 1/4, Section 23</p> <hr/> <p>From the E. 1/16 sec. cor. of secs. 23 and 26.</p> <p>N. 0°08' W., on the N. and S. center line of the SE 1/4 of sec. 23.</p>
38.70	<p>Fence, bears E. and W., 3 lks. W. of cor. of fences extending E. S. and W.</p>
40.04	<p>The center E. 1/16 sec. cor. of sec. 23.</p> <hr/> <p style="text-align: center;"><b>Subdivision of Section 24, T. 14 S., R. 10 E., Gila and Salt River Meridian, Arizona</b></p> <hr/> <p>From the 1/4 sec. cor. of secs. 24 and 25.</p> <p>N. 0°05' W., on the N. and S. center line of sec. 24.</p>
40.00	<p>Point for the center 1/4 sec. cor. of sec. 24, at intersection with the E. and W. center line.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, in a collar of stone, with brass cap mkd.</p> <p style="text-align: center;">T 14 S R 10 E C 1/4 S 24</p> <p style="text-align: center;">2009</p> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p> <p>Set steel fence post as guard post.</p> <p>From this cor. point, an iron post, 1 in. diam., firmly set, projecting 1/2 in. above the ground, presumably set by Robert Douglas Miller, Arizona Registered Land Surveyor 13564, in an un-recorded survey, bears N. 57° E., 26 lks. dist. This monument was not utilized in the course of this survey.</p>

**Subdivision of Section 24,  
T. 14 S., R. 10 E., Gila and Salt River Meridian, Arizona**

CHAINS	
80.00	<p>The 1/4 sec. cor. of secs. 13 and 24.</p> <hr/> <p>From the point for the 1/4 sec. cor. of secs. 19 and 24 on the 2nd Guide Mer. E., the E. bdy. of the Tp., at proportionate dist.; there is no remaining evidence of the orig. cor. Position falls in an irrigated field of Schuk Toak Farms, not monumented.</p> <p>From this point, the cor. of secs. 19, 24, 25 and 30 on the E. bdy. of the Tp., bears S. 0°03' E., 39.965 chs. dist.</p> <p>From this same point, the cor. of secs. 7, 12, 13 and 18 on the E. bdy of the Tp., bears N. 0°03' W., 119.895 chs. dist.</p> <p>N. 89°59' W., on the E. and W. center line of sec. 24.</p>
40.115	The center 1/4 sec. cor. of sec. 24.
40.18	Cor. of fences extending N., S. and W.
80.23	<p>The 1/4 sec. cor. of secs. 23 and 24.</p> <hr/> <p style="text-align: center;"><b>Subdivision of Section 26, T. 14 S., R. 10 E., Gila and Salt River Meridian, Arizona</b></p> <hr/> <p>From the 1/4 sec. cor. of secs. 26 and 35.</p> <p>N. 0°06' W., on the N. and S. center line of sec. 26.</p>
39.97	Point in alignment with old fence, bearing E. and W.
40.04	<p>Point for the center 1/4 sec. cor. of sec. 26, at intersection with the E. and W. center line.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, in a collar of stone, with brass cap mkd.</p> <p style="text-align: center;">T 14 S R 10 E C 1/4 S 26</p> <p style="text-align: center;">2009</p> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p> <p>Set a steel fence post as a guard post.</p>

**Subdivision of Section 26,  
T. 14 S., R. 10 E., Gila and Salt River Meridian, Arizona**

CHAINS	
80.08	<p>The 1/4 sec. cor. of secs. 23 and 26.</p> <hr/> <p>From the 1/4 sec. cor. of secs. 25 and 26.</p> <p>S. 89°52' W., on the E. and W. center line of sec. 26.</p>
20.015	<p>Point for the center E. 1/16 sec. cor. of sec. 26.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 27 ins. in the ground, in a collar of stone, with brass cap mkd.</p> <p style="text-align: center;">T 14 S R 10 E E 1/16 C———C S 26</p> <p style="text-align: center;">2009</p> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p> <p>Set a steel fence post as a guard post.</p>
20.66	Terminus of old fence, extending W.
40.03	The center 1/4 sec. cor. of sec. 26.
40.54	Fence, bears N. and S.
80.04	<p>The 1/4 sec. cor. of secs. 26 and 27.</p> <hr/> <p style="text-align: center;">The NE 1/4, Section 26</p> <hr/> <p>From the center E. 1/16 sec. cor. of sec. 26.</p> <p>N. 0°07' W., on the N. and S. center line of the NE 1/4 of sec. 26.</p>
0.13	Fence, bears E. and W., 37 lks. E. of cor. of fences extending N., E. and S.
40.04	<p>The E. 1/16 sec. cor. of secs. 23 and 26.</p> <hr/> <p style="text-align: center;">The SE 1/4, Section 26</p> <hr/> <p>From the E. 1/16 sec. cor. of secs. 26 and 35.</p>

**Subdivision of Section 26,  
T. 14 S., R. 10 E., Gila and Salt River Meridian, Arizona**

CHAINS	<p>N. 0°07' W., on the N. and S. center line of the SE 1/4 of sec. 26.</p>
40.04	<p>The center E. 1/16 sec. cor. of sec. 26.</p> <hr/> <p style="text-align: center;">GENERAL DESCRIPTION</p> <hr/> <p>This survey is located 18 miles west of Tucson, Arizona. The primary access is 3 miles west of Sendario Road, through the Schuk Toak farms managed by the Tohono O'odham Nation, thence along the Garcia Ranch Road. There are several track roads and roads along utility lines that provide reasonable access to the project. The Garcia Ranch was quite active at one time, but much of the fences, corrals and water tanks are in disrepair.</p> <p>The southwest portion of this township is dominated by the Roskrige Mountains with elevations reaching 3180 ft. above sea level. The balance of the project descends gradually to floodplains in the northeast with elevations of 2260 ft. There are many small washes cutting this project, flowing northerly, away from the mountains.</p> <p>The flora and fauna are of the Arizona Upland Subdivision of the Sonoran Desertscrub. The area would be quite scenic if the refuse left by illegal immigrant traffic was not so prevalent. Even so, the vegetation appears healthy and many animals including mule deer, javelina, jack rabbits and eagles were evident.</p> <p>The mean magnetic declination of 10 3/4° E. was derived from the National Geophysical Data Center's (NGDC) on-line declination calculator, utilizing the latest International Geomagnetic Reference Field (IGRF) model for the dates of the survey.</p> <hr/>



CERTIFICATE OF SURVEY

I, Geoffrey A. Graham, Cadastral Surveyor, HEREBY CERTIFY upon honor, that in pursuance of special instructions bearing date of the 20th day of October, 2008, I have dependently resurveyed the sectional correction line and a portion of the subdivisional lines and subdivided sections 23, 24 and 26, T. 14 S., R. 10 E., of the Gila and Salt River Meridian, in the State of Arizona, which are represented in the foregoing field notes as having been executed by me and under my direction. Said survey has been made in strict conformity with said special instructions, the Manual of Instructions for the Survey of the Public Lands of the United States, 1973, and in specific manner described in the foregoing field notes.

8/26/2009  
(Date)

Geoffrey A. Graham  
(Cadastral Surveyor)

CERTIFICATE OF APPROVAL

BUREAU OF LAND MANAGEMENT  
Phoenix, Arizona

The foregoing field notes of the dependent resurvey of the sectional correction line and a portion of the subdivisional lines and subdivision of sections 23, 24 and 26, T. 14 S., R. 10 E., Gila and Salt River Meridian, in the State of Arizona, executed by Geoffrey A. Graham, Cadastral Surveyor, having been critically examined and found correct, are hereby approved.

3/17/2010  
(Date)

Stephen K. Hansen  
(Chief Cadastral Surveyor of Arizona)

~~CERTIFICATE OF TRANSCRIPT~~

~~I CERTIFY That the foregoing transcript of the field notes of the above described surveys in T. 14 S., R. 10 E., Gila and Salt River Meridian, Arizona, is a true copy of the original field notes.~~

~~(Date)~~

~~(Chief Cadastral Surveyor of Arizona)~~