

ORIGINAL

**UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT**

FIELD NOTES
OF THE DEPENDENT RESURVEY OF THE
SECOND GUIDE MERIDIAN EAST (EAST BOUNDARY)
AND THE SOUTH BOUNDARY AND THE SURVEY OF THE
WEST AND NORTH BOUNDARIES
AND THE
SUBDIVISIONAL LINES
TOWNSHIP 34 NORTH, RANGE 8 EAST,
OF THE GILA AND SALT RIVER MERIDIAN,
IN THE STATE OF ARIZONA

EXECUTED BY

Craig S. Dukart, Cadastral Surveyor

Under Special Instructions dated February 10, 2010, approved February 10, 2010, which provided for the surveys included under Group No. 1080, and assignment instructions dated February 10, 2010.

Survey commenced February 23, 2010

Survey completed April 6, 2010

INDEX DIAGRAM

TOWNSHIP 34 NORTH RANGE 8 EAST
GILA AND SALT RIVER MERIDIAN, ARIZONA

29 22 6 83	28 5 71	27 4 62	25 3 53	24 2 43	23 1 9
82 21 7 80	81 8 69	70 9 61	62 10 51	52 11 41	42 12 8
80 20 18 78	79 17 68	69 16 59	60 15 49	50 14 38	39 13 7
78 19 19 76	77 20 66	67 21 57	58 22 47	48 23 35	36 24 6
75 18 30 74	75 29 65	66 28 56	57 27 45	46 26 32	33 25 5
73 17 31 71 16	72 32 63 15	64 33 54 14	55 34 43 13	44 35 29 12	31 36 4 10

T. 34 N., R. 8 E., Gila and Salt River Meridian, Arizona

CHAINS

The following field notes describe the dependent resurvey of the Second Guide Meridian East (east boundary) and the south boundary and the survey of the west and north boundaries and the subdivisional lines, Township 34 North, Range 8 East, Gila and Salt River Meridian, Arizona.

The history of surveys pertaining to this survey is as follows:

Jones Curtiss established the northeast and northwest township corners, Township 33 North, Range 8 East, in 2009. Joe R. Salazar established the northwest township corner, Township 34 North, Range 9 East, in 2009.

The survey was executed in accordance with the specifications as set forth in the Manual of Instructions for the Survey of the Public Lands of the United States, 1973, and the Special Instructions dated February 10, 2010, for Group Number 1080, Arizona.

The true meridian direction and length of all lines were determined by real time kinematic global positioning system observations using Trimble Navigation 5700 model receivers.

Geodetic control was derived from Global Positioning System (GPS) static observations post processed by National Geodetic Survey, Online Positioning User Service (OPUS), utilizing Continuously Operating Reference Stations (CORS) AI8805 FRED FREDONIA CORS ARP, DJ8981 FST5 FLAGSTAFF 5 CORS ARP and DK8419 AZPG CITY OF PAGE CORS ARP. The NAD 83 (CORS96) (EPOCH: 2002), geographic position of the southeast township corner is as follows:

Latitude: 36°17'40.90" N. Longitude: 111°28'32.81" W.

The mean magnetic declination is 11 1/4° E.

**Dependent Resurvey of the Second Guide Meridian East
(East Boundary),
T. 34 N., R. 8 E., Gila and Salt River Meridian, Arizona**

CHAINS

Restoring the survey executed by
Joe R. Salazar, in 2009

Beginning at the cor. of Tps. 33 and 34 N., R. 8 E. and Tps. 33 1/2 and 34 N., R. 9 E., on the Second Guide Meridian East, monumented with a stainless steel post, 2 1/2 ins. diam., firmly set, projecting 2 ins. above ground, with brass cap mkd. T34N R8E R9E S36 S31 S1 S30 T33N R8E T33 1/2N R9E 2009, from which the reference monuments

A stainless steel post, 2 1/2 ins. diam., firmly set, projecting 2 ins. above ground, bears S. 39°44' W., 33.0 ft. dist., with brass cap mkd. RM T33N R8E S1 33.0 FT TO COR 2009 and an arrow pointing to the cor. Add the marks 2010 to the brass cap.

A stainless steel post, 2 1/2 ins. diam., firmly set, projecting 3 ins. above ground, encircled with a collar of stone, bears N. 54°59' W., 850.0 ft. dist., with brass cap mkd. RM T34N R8E S36 850.0 FT TO COR 2009 and an arrow pointing to the cor. Add the marks 2010 to the brass cap.

Add the marks 2010 to the brass cap.

North, bet. secs. 31 and 36.

Over broken and rolling terrain.

- | | |
|-------|---|
| 4.70 | Wash, 8 ft. wide, drains N. 75° E. |
| 11.60 | Trail road, bears S. 80° E. and N. 80° W. |
| 26.05 | Trail road, bears East and West. |
| 40.00 | Point for the 1/4 sec. cor. of secs. 31 and 36. |

Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 23 ins. in the ground, with brass cap mkd.

T 34 N
R 8 E R 9 E
 1/4
S 36 | S 31

2010

Deposit a magnet, in a white plastic case, at the base of the stainless steel post.

Set a T shaped steel fence post near the cor.

**Dependent Resurvey of the Second Guide Meridian East
(East Boundary),
T. 34 N., R. 8 E., Gila and Salt River Meridian, Arizona**

CHAINS									
41.10	Wash, 13 ft. wide, 3 ft. deep, drains N. 85° E.								
80.00	Point for the cor. of secs. 25, 30, 31 and 36. Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 22 ins. in the ground, with brass cap mkd.								
	<table style="margin: auto;"> <tr><td colspan="2">T 34 N</td></tr> <tr><td>R 8 E</td><td>R 9 E</td></tr> <tr><td>S 25</td><td>S 30</td></tr> <tr><td>S 36</td><td>S 31</td></tr> </table>	T 34 N		R 8 E	R 9 E	S 25	S 30	S 36	S 31
T 34 N									
R 8 E	R 9 E								
S 25	S 30								
S 36	S 31								
	2010								
	Deposit a magnet, in a white plastic case, at the base of the stainless steel post.								
	Set a T shaped steel fence post near the cor.								
	Terrain, broken and rolling. Soil, red clay. Timber, occasional small juniper; undergrowth, sage brush and rabbit brush.								

	North, bet. secs. 25 and 30.								
	Over broken and rolling terrain.								
1.15	Trail road, bears N. 50° E. and S. 50° W.								
34.65	B. I. A. Route 6130, a graded road, 18 ft. wide, bears S. 80° E. and N. 80° W.								
37.40	Utility line, 10 strand, bears S. 45° E. and N. 45° W.								
39.25	Underground water line, bears S. 45° E. and N. 45° W.								
39.65	Southwesterly right-of-way fence of U. S. Highway 89, barbed wire, 5 strand, bears S. 45° E. and N. 45° W.								
40.00	Point for the 1/4 sec. cor. of secs. 25 and 30. Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 27 ins. in the ground, with brass cap mkd.								
	<table style="margin: auto;"> <tr><td colspan="2">T 34 N</td></tr> <tr><td>R 8 E</td><td>R 9 E</td></tr> <tr><td colspan="2">1/4</td></tr> <tr><td>S 25</td><td>S 30</td></tr> </table>	T 34 N		R 8 E	R 9 E	1/4		S 25	S 30
T 34 N									
R 8 E	R 9 E								
1/4									
S 25	S 30								
	2010								

**Dependent Resurvey of the Second Guide Meridian East
(East Boundary),
T. 34 N., R. 8 E., Gila and Salt River Meridian, Arizona**

CHAINS

from which

An X chiseled on the steel ring, of a water valve access opening, 9 ins. diam., set in concrete, 2 ft. square, bears S. 27°44' W., 59 lks. dist.

Deposit a magnet, in a white plastic case, at the base of the stainless steel post.

Set a T shaped steel fence post near the cor.

From this cor. point, the SE cor. of a concrete housing, 5 1/2 ft. square, 3 ft. high, of BODAWAY WELL, sides bear S. 70° W. and N. 20° W., bears N. 27°02' W., 16.95 chs. dist.

41.25 Southwesterly edge of U. S. Highway 89, asphalt surface, 40 ft. wide, bears S. 45° E. and N. 45° W.

42.10 Northeasterly edge of U. S. Highway 89, bears S. 45° E. and N. 45° W.

43.70 Wash, 10 ft. wide, drains S. 55° E.

43.95 Northeasterly right-of-way fence of U. S. Highway 89, barbed wire, 5 strand, bears S. 45° E. and N. 45° W.

48.50 Hamblin Wash, 50 ft. wide, drains S. 55° E.

80.00 Point for the cor. of secs. 19, 24, 25 and 30.

Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, encircled with a collar of stone, with brass cap mkd.

T 34 N	
R 8 E	R 9 E
S 24	S 19
S 25	S 30

2010

Deposit a magnet, in a white plastic case, at the base of the stainless steel post.

Set a T shaped steel fence post near the cor.

Terrain, broken and rocky.

Soil, red clay.

Timber, occasional small juniper; undergrowth, sage brush and rabbit brush.

North, bet. secs. 19 and 24.

**Dependent Resurvey of the Second Guide Meridian East
(East Boundary),
T. 34 N., R. 8 E., Gila and Salt River Meridian, Arizona**

CHAINS	
	Over broken and rolling terrain.
1.60	Wash, 4 ft. wide, drains S. 70° W.
11.10	Base of a sandstone bench below Echo Cliffs, bears S. 60° E. and N. 60° W.; ascend a series of sandstone cliffs.
36.10	Top of Echo Cliffs, bears S. 75° E. and N. 75° W.; descend a steep, rocky slope.
40.00	Point for the 1/4 sec. cor. of secs. 19 and 24. Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 22 ins. in sandstone bedrock, with brass cap mkd. <div style="text-align: center;"> T 34 N R 8 E R 9 E 1/4 S 24 S 19 2010 </div>
	Deposit a magnet, in a white plastic case, at the base of the stainless steel post.
48.00	Bottom of a steep descent, bears S. 30° E. and N. 45° W.; thence across rolling and broken terrain.
80.00	Point for the cor. of secs. 13, 18, 19 and 24. Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 23 ins. in the ground, with brass cap mkd. <div style="text-align: center;"> T 34 N R 8 E R 9 E S 13 S 18 S 24 S 19 2010 </div>
	Deposit a magnet, in a white plastic case, at the base of the stainless steel post.
	Terrain, broken and rolling. Soil, sand and sandstone. Timber, occasional small juniper and piñon pine; undergrowth, sage brush, Mormon Tea, yucca and prickly pear cacti.
	----- North, bet. secs. 13 and 18.
	Over broken and rolling terrain.

**Dependent Resurvey of the Second Guide Meridian East
(East Boundary),
T. 34 N., R. 8 E., Gila and Salt River Meridian, Arizona**

CHAINS	
40.00	<p>Point for the 1/4 sec. cor. of secs. 13 and 18.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 23 ins. in sandstone bedrock, encircled with a collar of stone, with brass cap mkd.</p> <p style="text-align: center;">T 34 N R 8 E R 9 E 1/4 S 13 S 18</p> <p style="text-align: center;">2010</p> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p> <p>Cor. is located on the NE cor. of a crème colored sandstone shelf, 70 x 45 x 4 ft. high.</p>
78.50	Wash, 10 ft. wide, drains N. 40° E.
80.00	<p>Point for the cor. of secs. 7, 12, 13 and 18.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 23 ins. in the ground, encircled with a collar of stone, with brass cap mkd.</p> <p style="text-align: center;">T 34 N R 8 E R 9 E S 12 S 7 S 13 S 18</p> <p style="text-align: center;">2010</p> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p> <p>Terrain, broken and rolling. Soil, sand and sandstone outcrops. Timber, occasional small juniper and piñon pine; undergrowth, sage brush, Mormon Tea, yucca and prickly pear cacti.</p> <hr/> <p>North, bet. secs. 7 and 12.</p> <p>Over broken and rolling terrain.</p>
40.00	Point for the 1/4 sec. cor. of secs. 7 and 12.

**Dependent Resurvey of the Second Guide Meridian East
(East Boundary),
T. 34 N., R. 8 E., Gila and Salt River Meridian, Arizona**

CHAINS	
	<p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 25 ins. in the ground, underpinned with a U shaped steel fence post, 5 ft. long, with brass cap mkd.</p> <p style="text-align: center;">T 34 N R 8 E R 9 E 1/4 S 12 S 7</p> <p style="text-align: center;">2010</p> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p> <p>Set a T shaped steel fence post near the cor.</p>
80.00	<p>Point for the cor. of secs. 1, 6, 7 and 12.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, underpinned with a U shaped steel fence post, 5 ft. long, encircled with a collar of stone, with brass cap mkd.</p> <p style="text-align: center;">T 34 N R 8 E R 9 E S 1 S 6 S 12 S 7</p> <p style="text-align: center;">2010</p> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p> <p>Set a T shaped steel fence post near the cor.</p> <p>Terrain, broken and rolling. Soil, sand and sandstone outcrops. Timber, occasional small juniper and piñon pine; undergrowth, sage brush, Mormon Tea, yucca and prickly pear cacti.</p> <hr/> <p>North, bet. secs. 1 and 6.</p> <p>Over broken and rolling terrain.</p>
40.00	<p>Point for the 1/4 sec. cor. of secs. 1 and 6.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 25 ins. in the ground, encircled with a collar of stone, with brass cap mkd.</p>

**Dependent Resurvey of the Second Guide Meridian East
(East Boundary),
T. 34 N., R. 8 E., Gila and Salt River Meridian, Arizona**

CHAINS

T 34 N
R 8 E R 9 E
 1/4
S 1 | S 6

2010

Deposit a magnet, in a white plastic case, at the base of the stainless steel post.

Set a T shaped steel fence post near the cor.

80.00 The cor. of Tps. 34 and 35 N., Rs. 8 and 9 E., monumented with a stainless steel post, 2 1/2 ins. diam., firmly set, projecting 3 ins. above ground, with brass cap mkd. T35N R8E R9E S36 S31 S1 S6 T34N 2009, with a mound of stone, 2 ft. base, 1 1/2 ft. high, S. of cor., from which the reference monuments

A brass tablet, 3 1/4 ins. diam., cemented flush on a sandstone outcrop, bears S. 49°23' E., 950.0 ft. dist., with top mkd. RM T34N R9E S6 950.0 FT TO COR 2009 and an arrow pointing to the cor. Add the marks 2010 to the top.

A stainless steel post, 2 1/2 ins. diam., firmly set, projecting 2 ins. above ground, bears S. 46°10' W., 29.0 ft. dist., with brass cap mkd. RM T34N R8E S1 29.0 FT TO COR 2009 and an arrow pointing to the cor. Add the marks 2010 to the brass cap.

Add the marks 2010 to the brass cap.

Terrain, broken and rolling.

Soil, sand and sandstone outcrops.

Timber, occasional small juniper and piñon pine; undergrowth, sage brush, Mormon Tea, yucca and prickly pear cacti.

**Dependent Resurvey of the South Boundary,
T. 34 N., R. 8 E., Gila and Salt River Meridian, Arizona**

Restoring the survey executed by
Jones Curtiss, in 2009

From the cor. of Tps. 33 and 34 N., R. 8 E. and Tps. 33 1/2 and 34 N., R. 9 E., on the Second Guide Meridian East, hereinbefore described.

West, bet. secs. 1 and 36.

Over rolling terrain.

**Dependent Resurvey of the South Boundary,
T. 34 N., R. 8 E., Gila and Salt River Meridian, Arizona**

CHAINS	
7.70	Wash, 9 ft. wide, drains N. 20° E.
32.00	Point for the 80 1/16 sec. cor. of secs. 1 and 36. Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 22 ins. in the ground, encircled with a collar of stone, with brass cap mkd. <div style="text-align: center;"> T 34 N R 8 E S 36 80 ——— 1/16 S 1 T33N 2010 </div>
	Deposit a magnet, in a white plastic case, at the base of the stainless steel post. Set a T shaped steel fence post near the cor.
52.15	Trail road, bears N. 25° E. and S. 25° W.
67.90	Trail road, bears S. 25° E. and N. 25° W.
72.00	Point for the 1/4 sec. cor. of secs. 1 and 36. Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd. <div style="text-align: center;"> T 34 N R 8 E S 36 1/4 ——— S 1 T 33 N 2010 </div>
	Deposit a magnet, in a white plastic case, at the base of the stainless steel post. Set a T shaped steel fence post near the cor.
101.30	Trail road, bears S. 50° E. and N. 50° W.
112.00	Point for the cor. of secs. 1, 2, 35 and 36. Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.

**Dependent Resurvey of the South Boundary,
T. 34 N., R. 8 E., Gila and Salt River Meridian, Arizona**

CHAINS

T 34 N	R 8 E
S 35	S 36
S 2	S 1
T 33 N	

2010

Deposit a magnet, in a white plastic case, at the base of the stainless steel post.

Set a T shaped steel fence post near the cor.

Terrain, rolling.

Soil, sand and red sandy clay.

No timber; sage brush, Mormon Tea and various high desert grasses.

West, bet. secs. 2 and 35.

Over rolling terrain.

36.25 Trail road, bears S. 25° E. and N. 25° W.

40.00 Point for the 1/4 sec. cor. of secs. 2 and 35.

Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 25 ins. in the ground, with brass cap mkd.

T 34 N	R 8 E
S 35	S 36
1/4	—
S 2	S 1
T 33 N	

2010

Deposit a magnet, in a white plastic case, at the base of the stainless steel post.

Set a T shaped steel fence post near the cor.

42.55 Trail road, bears N. 15° E. and S. 15° W.

80.00 Point for the cor. of secs. 2, 3, 34 and 35.

Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with brass cap mkd.

Dependent Resurvey of the South Boundary,
T. 34 N., R. 8 E., Gila and Salt River Meridian, Arizona

CHAINS

T 34 N	R 8 E
S 34	S 35
S 3	S 2
T 33 N	

2010

Deposit a magnet, in a white plastic case, at the base of the stainless steel post.

Set a T shaped steel fence post near the cor.

Terrain, rolling hills.

Soil, sand and sandy clay.

Timber, scattered small juniper; undergrowth, sparse sage brush and Mormon Tea.

West, bet. secs. 3 and 34.

Over rolling terrain.

0.30 Wash, 8 ft. wide, drains N. 30° E.

40.00 Point for the 1/4 sec. cor. of secs. 3 and 34.

Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 25 ins. in the ground, with brass cap mkd.

T 34 N	R 8 E
S 34	
1/4	—
S 3	
T 33 N	

2010

Deposit a magnet, in a white plastic case, at the base of the stainless steel post.

Set a T shaped steel fence post near the cor.

80.00 Point for the cor. of secs. 3, 4, 33 and 34.

Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 25 ins. in the ground, with brass cap mkd.

**Dependent Resurvey of the South Boundary,
T. 34 N., R. 8 E., Gila and Salt River Meridian, Arizona**

CHAINS	
	T 34 N R 8 E S 33 S 34 S 4 S 3 T 33 N 2010
	Deposit a magnet, in a white plastic case, at the base of the stainless steel post. Set a T shaped steel fence post near the cor. Terrain, gently rolling hills. Soil, sandy clay. No timber; sparse sage brush and Mormon Tea.
	<hr/> West, bet. secs. 4 and 33. Over rolling terrain.
40.00	Point for the 1/4 sec. cor. of secs. 4 and 33. Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 13 ins. in the ground, to bedrock, in a mound of stone, 2 1/2 ft. base, to top, with brass cap mkd.
	T 34 N R 8 E S 33 1/4 ——— S 4 T 33 N 2010
	Deposit a magnet, in a white plastic case, at the base of the stainless steel post. Set a T shaped steel fence post near the cor.
67.50	B. I. A. Route 6130, a graded road, 40 ft. wide, bears N. 50° E. and S. 50° W.
78.60	Trail road, bears N. 50° E. and S. 50° W.
79.50	W. rim of a mesa, bears N. 40° E. and S. 50° W.; descend a NW facing slope.
80.00	Point for the cor. of secs. 4, 5, 32 and 33.

**Dependent Resurvey of the South Boundary,
T. 34 N., R. 8 E., Gila and Salt River Meridian, Arizona**

CHAINS

Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 14 ins. in the ground, to bedrock, in a mound of stone, 4 ft. base, to top, with brass cap mkd.

T 34 N	R 8 E
S 32	S 33
S 5	S 4
T 33 N	

2010

Deposit a magnet, in a white plastic case, at the base of the stainless steel post.

Set a T shaped steel fence post near the cor.

Terrain, broken and rolling.

Soil, limestone and sand.

No timber; sparse sage brush and Mormon Tea.

West, bet. secs. 5 and 32.

Over broken and rolling terrain.

40.00 Point for the 1/4 sec. cor. of secs. 5 and 32.

Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 25 ins. in the ground, with brass cap mkd.

T 34 N	R 8 E
	S 32
1/4	——
	S 5
T 33 N	

2010

Deposit a magnet, in a white plastic case, at the base of the stainless steel post.

Set a T shaped steel fence post near the cor.

Cor. is located 1.30 chs. NW from the intersection of trail roads, bearing N. 55° E. and S. 55° W., and S. 85° W.

80.00 Point for the cor. of secs. 5, 6, 31 and 32.

Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 25 ins. in the ground, with brass cap mkd.

**Dependent Resurvey of the South Boundary,
T. 34 N., R. 8 E., Gila and Salt River Meridian, Arizona**

CHAINS

T 34 N	R 8 E
S 31	S 32
S 6	S 5
T 33 N	

2010

Deposit a magnet, in a white plastic case, at the base of the stainless steel post.

Set a T shaped steel fence post near the cor.

Terrain, rolling.

Soil, sand.

No timber; sparse sage brush and Mormon Tea.

West, bet. secs. 6 and 31.

Over rolling terrain.

40.00

Point for the 1/4 sec. cor. of secs. 6 and 31.

Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 27 ins. in the ground, with brass cap mkd.

T 34 N	R 8 E
	S 31
1/4	—
	S 6
T 33 N	

2010

Deposit a magnet, in a white plastic case, at the base of the stainless steel post.

Raise a mound of stone, 4 ft. base, 3 1/2 ft. high, S. of cor.

Cor. is located on a steep, easterly facing slope, 75 lks. W. of a rocky gorge.

79.44

The cor. of Tps. 33 and 34 N., Rs. 7 and 8 E., monumented with a stainless steel post, 2 1/2 ins. diam., firmly set, projecting 4 ins. above ground, with brass cap mkd. T34N R7E R8E S36 S31 S1 S6 T33N 2009, from which the reference monuments

A stainless steel post, 2 1/2 ins. diam., firmly set, projecting 4 ins. above ground, bears N. 45°00' E., 200.0 ft. dist., with brass cap mkd. RM T34N R8E S31 200.0 FT TO COR 2009 and an arrow pointing to the cor. Add the marks 2010 to the brass cap.

**Dependent Resurvey of the South Boundary,
T. 34 N., R. 8 E., Gila and Salt River Meridian, Arizona**

CHAINS

A stainless steel post, 2 1/2 ins. diam., firmly set, projecting 5 ins. above ground, bears S. 45°00' W., 660.0 ft. dist., with brass cap mkd. RM T33N R7E S1 660.0 FT TO COR 2009 and an arrow pointing to the cor. Add the marks 2010 to the brass cap. Raise a mound of stone, 2 1/2 ft. base, 2 ft. high, W. of reference monument.

Add the marks 2010 to the brass cap.

Terrain, rolling.

Soil, sandy clay.

Timber, occasional small juniper and piñon pine; undergrowth, sage brush and Mormon Tea.

**Survey of the West Boundary,
T. 34 N., R. 8 E., Gila and Salt River Meridian, Arizona**

From the cor. of Tps. 33 and 34 N., Rs. 7 and 8 E., hereinbefore described.

North, bet. secs. 31 and 36.

Over rolling terrain.

40.00

Point for the 1/4 sec. cor. of secs. 31 and 36.

Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 27 ins. in the ground, encircled with an embedded collar of stone, with brass cap mkd.

T 34 N
R 7 E R 8 E
 1/4
S 36 | S 31

2010

Deposit a magnet, in a white plastic case, at the base of the stainless steel post.

Set a T shaped steel fence post near the cor.

80.00

Point for the cor. of secs. 25, 30, 31 and 36.

Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with brass cap mkd.

**Survey of the West Boundary,
T. 34 N., R. 8 E., Gila and Salt River Meridian, Arizona**

CHAINS	
	T 34 N R 7 E R 8 E S 25 S 30 S 36 S 31 2010
	Deposit a magnet, in a white plastic case, at the base of the stainless steel post. Set a T shaped steel fence post near the cor. Terrain, gently rolling. Soil, sandy clay. Timber, occasional small juniper and piñon pine; undergrowth, sage brush and Mormon Tea.
	<hr/> North, bet. secs. 25 and 30. Over gently rolling terrain.
40.00	Point for the 1/4 sec. cor. of secs. 25 and 30. Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with brass cap mkd.
	T 34 N R 7 E R 8 E 1/4 S 25 S 30 2010
62.45	Deposit a magnet, in a white plastic case, at the base of the stainless steel post. Set a T shaped steel fence post near the cor. Trail road, bears S. 25° E. and N. 25° W.
80.00	Point for the cor. of secs. 19, 24, 25 and 30. Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with brass cap mkd.

**Survey of the West Boundary,
T. 34 N., R. 8 E., Gila and Salt River Meridian, Arizona**

CHAINS	
	T 34 N R 7 E R 8 E S 24 S 19 S 25 S 30 2010
	Deposit a magnet, in a white plastic case, at the base of the stainless steel post. Set a T shaped steel fence post near the cor. Terrain, nearly level to gently rolling. Soil, sand and sandy clay. No timber; sparse Mormon Tea.
	<hr/> North, bet. secs. 19 and 24. Over gently rolling terrain.
21.90	Trail road, bears S. 80° E. and N. 80° W.
22.90	Earthen berm of a check dam, 5 ft. wide, 5 ft. high, bears S. 85° E. and N. 85° W.
40.00	Point for the 1/4 sec. cor. of secs. 19 and 24. Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 27 ins. in the ground, with brass cap mkd.
	T 34 N R 7 E R 8 E 1/4 S 24 S 19 2010
	Deposit a magnet, in a white plastic case, at the base of the stainless steel post. Set a T shaped steel fence post near the cor.
40.20	Wash, 15 ft. wide, 2 ft. deep, drains S. 40° E.
80.00	Point for the cor. of secs. 13, 18, 19 and 24. Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with brass cap mkd.

**Survey of the West Boundary,
T. 34 N., R. 8 E., Gila and Salt River Meridian, Arizona**

CHAINS									
	<table style="margin: auto;"> <tr><td colspan="2">T 34 N</td></tr> <tr><td>R 7 E</td><td>R 8 E</td></tr> <tr><td>S 13</td><td>S 18</td></tr> <tr><td>S 24</td><td>S 19</td></tr> </table>	T 34 N		R 7 E	R 8 E	S 13	S 18	S 24	S 19
T 34 N									
R 7 E	R 8 E								
S 13	S 18								
S 24	S 19								
	2010								
	Deposit a magnet, in a white plastic case, at the base of the stainless steel post.								
	Set a T shaped steel fence post near the cor.								
	Terrain, gently rolling.								
	Soil, sandy clay.								
	No timber; sparse sage brush and various high desert grasses.								
	<hr/>								
	North, bet. secs. 13 and 18.								
	Over gently rolling terrain.								
39.35	Trail road, bears East and West.								
40.00	Point for the 1/4 sec. cor. of secs. 13 and 18.								
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with brass cap mkd.								
	<table style="margin: auto;"> <tr><td colspan="2">T 34 N</td></tr> <tr><td>R 7 E</td><td>R 8 E</td></tr> <tr><td colspan="2">1/4</td></tr> <tr><td>S 13</td><td>S 18</td></tr> </table>	T 34 N		R 7 E	R 8 E	1/4		S 13	S 18
T 34 N									
R 7 E	R 8 E								
1/4									
S 13	S 18								
	2010								
	Deposit a magnet, in a white plastic case, at the base of the stainless steel post.								
47.20	Foot of Bodaway Mesa, bears N. 70° E. and S. 80° W.								
59.80	Top rim of Bodaway Mesa, bears N. 55° E. and S. 55° W.								
80.00	Point for the cor. of secs. 7, 12, 13 and 18.								
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with brass cap mkd.								

**Survey of the West Boundary,
T. 34 N., R. 8 E., Gila and Salt River Meridian, Arizona**

CHAINS											
	<table style="margin: auto;"> <tr><td colspan="2">T 34 N</td></tr> <tr><td>R 7 E</td><td>R 8 E</td></tr> <tr><td>S 12</td><td>S 7</td></tr> <tr><td colspan="2"><hr/></td></tr> <tr><td>S 13</td><td>S 18</td></tr> </table>	T 34 N		R 7 E	R 8 E	S 12	S 7	<hr/>		S 13	S 18
T 34 N											
R 7 E	R 8 E										
S 12	S 7										
<hr/>											
S 13	S 18										
	2010										
	Deposit a magnet, in a white plastic case, at the base of the stainless steel post.										
	Terrain, level mesa top. Soil, sandy clay with rocks. Timber, scattered juniper; undergrowth, various high desert grasses.										
	<hr/>										
	North, bet. secs. 7 and 12.										
	Over gently rolling terrain.										
4.15	Trail road, bears S. 60° E. and N. 60° W.										
24.40	Top rim of Bodaway Mesa, bears S. 70° E. and N. 70° W.										
32.10	Foot of Bodaway Mesa, bears N. 80° E. and S. 80° W.										
33.80	Trail road, bears S. 80° E. and N. 80° W.										
40.00	Point for the 1/4 sec. cor. of secs. 7 and 12.										
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with brass cap mkd.										
	<table style="margin: auto;"> <tr><td colspan="2">T 34 N</td></tr> <tr><td>R 7 E</td><td>R 8 E</td></tr> <tr><td colspan="2">1/4</td></tr> <tr><td>S 12</td><td>S 7</td></tr> </table>	T 34 N		R 7 E	R 8 E	1/4		S 12	S 7		
T 34 N											
R 7 E	R 8 E										
1/4											
S 12	S 7										
	2010										
	Deposit a magnet, in a white plastic case, at the base of the stainless steel post.										
	Set a T shaped steel fence post near the cor.										
41.05	Trail road, bears N. 80° E. and S. 80° W.										
59.65	Trail road, bears S. 75° E. and N. 75° W.										
73.00	Trail road, bears N. 50° E. and S. 50° W.										
80.00	Point for the cor. of secs. 1, 6, 7 and 12.										

**Survey of the West Boundary,
T. 34 N., R. 8 E., Gila and Salt River Meridian, Arizona**

CHAINS	
	<p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;"> T 34 N R 7 E R 8 E S 1 S 6 S 12 S 7 </p> <p style="text-align: center;">2010</p> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p> <p>Set a T shaped steel fence post near the cor.</p> <p>Terrain, gently rolling. Soil, sand and red clay. No timber; sparse various high desert grasses.</p> <hr/> <p>North, bet. secs. 1 and 6.</p> <p>Over gently rolling terrain.</p>
40.00	<p>Point for the 1/4 sec. cor. of secs. 1 and 6.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;"> T 34 N R 7 E R 8 E 1/4 S 1 S 6 </p> <p style="text-align: center;">2010</p> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p> <p>Set a T shaped steel fence post near the cor.</p>
53.25	<p>B. I. A. Route 6110, a graded road, 25 ft. wide, bears East and West.</p>
69.45	<p>Trail road, bears N. 35° E. and S. 35° W.</p>
80.00	<p>Point for the cor. of Tps. 34 and 35 N., Rs. 7 and 8 E.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with brass cap mkd.</p>

**Survey of the West Boundary,
T. 34 N., R. 8 E., Gila and Salt River Meridian, Arizona**

CHAINS

T 35 N	
R 7 E	R 8 E
S 36	S 31
S 1	S 6
T 34 N	

2010

Deposit a magnet, in a white plastic case, at the base of the stainless steel post.

Set a T shaped steel fence post near the cor.

Terrain, gently rolling.

Soil, sandy clay.

No timber; sparse various high desert grasses.

**Survey of the North Boundary,
T. 34 N., R. 8 E., Gila and Salt River Meridian, Arizona**

From the cor. of Tps. 34 and 35 N., Rs. 8 and 9 E., hereinbefore described.

West, bet. secs. 1 and 36.

Over rolling terrain.

32.00 Point for the 80 1/16 sec. cor. of secs. 1 and 36.

Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, underpinned with a U shaped steel fence post, 5 ft. long, with brass cap mkd.

T 35 N		R 8 E
S 36		
80	—	1/16
S 1		
T 34 N		

2010

Deposit a magnet, in a white plastic case, at the base of the stainless steel post.

Set a T shaped steel fence post near the cor.

72.00 Point for the 1/4 sec. cor. of secs. 1 and 36.

**Survey of the North Boundary,
T. 34 N., R. 8 E., Gila and Salt River Meridian, Arizona**

CHAINS	
	<p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, encircled with a collar of stone, with brass cap mkd.</p> <p style="text-align: center;">T 35 N R 8 E S 36 1/4 ——— S 1 T 34 N</p> <p style="text-align: center;">2010</p> <p>Deposit eight 60 penny nails at the base of the stainless steel post.</p> <p>Thence descend W. face of Echo Cliffs.</p>
110.90	Base of a steep descent; wash, 6 ft. wide, drains S. 15° W.
112.00	Point for the cor. of secs. 1, 2, 35 and 36.
	<p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 21 ins. in the ground, in a mound of stone, 3 ft. base, to top, with brass cap mkd.</p> <p style="text-align: center;">T 35 N R 8 E S 35 S 36 S 2 S 1 T 34 N</p> <p style="text-align: center;">2010</p> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p> <p>Set a T shaped steel fence post near the cor.</p> <p>Cor. is located on the left bank of a small mountain drainage, 2 ft. wide, 1 ft. deep, drains S. 20° E.</p> <p>Terrain, broken and rolling. Soil, sand and sandstone. Timber, juniper and piñon; undergrowth, sage brush, Mormon Tea, prickly pear and cholla cacti.</p> <hr/> <p>West, bet. secs. 2 and 35.</p> <p>Over broken and rolling terrain.</p>
40.00	Point for the 1/4 sec. cor. of secs. 2 and 35.

**Survey of the North Boundary,
T. 34 N., R. 8 E., Gila and Salt River Meridian, Arizona**

CHAINS	
	<p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 25 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T 35 N R 8 E S 35 1/4 ——— S 2 T 34 N</p> <p style="text-align: center;">2010</p> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p>
78.70	Trail road, bears S. 45° E. and N. 45° W.
79.90	Trail road, bears S. 20° E. and N. 20° W.
80.00	Point for the cor. of secs. 2, 3, 34 and 35.
	<p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T 35 N R 8 E S 34 S 35 S 3 S 2 T 34 N</p> <p style="text-align: center;">2010</p> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p> <p>Set a T shaped steel fence post near the cor.</p> <p>Cor. is located 3 lks. E. of a utility line, 2 strand, bears S. 25° E. and N. 25° W.</p> <p>Terrain, broken and rolling to level. Soil, sand. Timber, scattered juniper; undergrowth, sparse various high desert grasses.</p> <hr/> <p>West, bet. secs. 3 and 34.</p> <p>Over level to rolling terrain.</p>
1.85	Easterly right-of-way fence of U. S. Highway 89, barbed wire, 5 strand, bears S. 20° E. and N. 20° W.
3.15	Easterly edge of U. S. Highway 89, asphalt surface, 40 ft. wide, bears S. 20° E. and N. 20° W.

**Survey of the North Boundary,
T. 34 N., R. 8 E., Gila and Salt River Meridian, Arizona**

CHAINS	
3.80	Westerly edge of U. S. Highway 89, bears S. 20° E. and N. 20° W.
4.15	Driveway, asphalt surface, 15 ft. wide, bears N. 70° E. and S. 70° W.
5.10	Westerly right-of-way fence of U. S. Highway 89, barbed wire, 5 strand, bears S. 20° E. and N. 20° W.
9.50	Utility line, 10 strand, bears S. 20° E. and N. 20° W.
40.00	Point for the 1/4 sec. cor. of secs. 3 and 34. Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 14 ins. in the ground, to bedrock, in a mound of stone, 2 ft. base, to top, with brass cap mkd. <div style="text-align: center;"> T 35 N R 8 E S 34 1/4 ——— S 3 T 34 N 2010 </div> Deposit a magnet, in a white plastic case, at the base of the stainless steel post. Raise a mound of stone, 3 ft. base, 2 1/2 ft. high, N. of cor.
80.00	Point for the cor. of secs. 3, 4, 33 and 34. Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 14 ins. in the ground, to bedrock, in a mound of stone, 4 ft. base, to top, with brass cap mkd. <div style="text-align: center;"> T 35 N R 8 E S 33 S 34 S 4 S 3 T 34 N 2010 </div> Deposit a magnet, in a white plastic case, at the base of the stainless steel post.

**Survey of the North Boundary,
T. 34 N., R. 8 E., Gila and Salt River Meridian, Arizona**

CHAINS	
	<p>Terrain, rolling. Soil, sand to loam over bedrock. Timber, juniper; undergrowth, sparse various high desert grasses.</p> <hr/> <p>West, bet. secs. 4 and 33.</p> <p>Over rolling terrain.</p>
8.80	B. I. A. Route 6110, a graded road, 25 ft. wide, bears N. 80° E. and S. 80° W.
16.40	Utility line, 2 strand, bears N. 80° E. and S. 80° W.
40.00	<p>Point for the 1/4 sec. cor. of secs. 4 and 33.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 27 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center;"> <p>T 35 N R 8 E S 33 1/4 ——— S 4 T 34 N</p> <p>2010</p> </div> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p> <p>Set a T shaped steel fence post near the cor.</p>
73.45	Trail road, bears S. 20° E. and N. 20° W.
73.75	Trail road, bears S. 15° E. and N. 15° W.
80.00	<p>Point for the cor. of secs. 4, 5, 32 and 33.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 23 ins. in the ground, encircled with a collar of stone, with brass cap mkd.</p> <div style="text-align: center;"> <p>T 35 N R 8 E S 32 S 33 S 5 S 4 T 34 N</p> <p>2010</p> </div> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p>

**Survey of the North Boundary,
T. 34 N., R. 8 E., Gila and Salt River Meridian, Arizona**

CHAINS	
	<p>Set a T shaped steel fence post near the cor.</p> <p>Terrain, rolling. Soil, sand and sandstone. Timber, juniper; undergrowth, sage brush, Mormon Tea and yucca cactus.</p> <hr/> <p>West, bet. secs. 5 and 32.</p> <p>Over rolling terrain.</p>
35.80	Utility line, 2 strand, bears North and South.
40.00	<p>Point for the 1/4 sec. cor. of secs. 5 and 32.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T 35 N R 8 E S 32 1/4 ——— S 5 T 34 N</p> <p style="text-align: center;">2010</p> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p> <p>Set a T shaped steel fence post near the cor.</p> <p>Cor. is located 48 lks. N. of a trail road, bears S. 70° E. and N. 70° W.</p>
41.40	Trail road, bears S. 70° E. and N. 70° W.
80.00	<p>Point for the cor. of secs. 5, 6, 31 and 32.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., flush with the surface of the ground, with brass cap mkd.</p> <p style="text-align: center;">T 35 N R 8 E S 31 S 32 S 6 S 5 T 34 N</p> <p style="text-align: center;">2010</p> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p> <p>Set a T shaped steel fence post near the cor.</p>

**Survey of the North Boundary,
T. 34 N., R. 8 E., Gila and Salt River Meridian, Arizona**

CHAINS	
	<p>Cor. is located in a cleared and graveled parking area, S. of an animal corral.</p> <p>Terrain, rolling to level. Soil, sand. No timber; sparse various high desert grasses.</p> <hr/> <p>West, bet. secs. 6 and 31.</p> <p>Over level terrain.</p>
5.20	Trail road, bears North and South.
7.65	Utility line, 2 strand, bears North and South.
14.50	Intersection of trail roads, bearing North and South, and N. 25° E. and S. 25° W.
40.00	<p>Point for the 1/4 sec. cor. of secs. 6 and 31.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 27 ins. in the ground, with brass cap mkd.</p> <p align="center">T 35 N R 8 E S 31 1/4 ——— S 6 T 34 N</p> <p align="center">2010</p> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p> <p>Set a T shaped steel fence post near the cor.</p>
71.35	Trail road, bears N. 25° E. and S. 25° W.
78.88	<p>The cor. of Tps. 34 and 35 N., Rs. 7 and 8 E., hereinbefore described.</p> <p>Terrain, level. Soil, sand. No timber; sparse various high desert grasses.</p> <hr/> <p align="center">Survey of the Subdivisional Lines, T. 34 N., R. 8 E., Gila and Salt River Meridian, Arizona</p> <hr/> <p>From the cor. of secs. 1, 2, 35 and 36, on the S. bdy. of the Tp., hereinbefore described.</p>

**Survey of the Subdivisional Lines,
T. 34 N., R. 8 E., Gila and Salt River Meridian, Arizona**

CHAINS	
	N. 0°01' W., bet. secs. 35 and 36.
	Over rolling terrain.
9.75	Trail road, bears S. 55° E. and N. 55° W.
10.05	Trail road, bears S. 60° E. and N. 60° W.
40.00	Point for the 1/4 sec. cor. of secs. 35 and 36.
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.
	T 34 N R 8 E 1/4 S 35 S 36 2010
	Deposit a magnet, in a white plastic case, at the base of the stainless steel post.
	Set a T shaped steel fence post near the cor.
	From this cor. point, an iron pipe, the casing of a drill hole, 4 1/2 ins. diam., firmly set in a concrete base, 2 ft. diam., 6 ins. high, projecting 4 1/2 ft. above the concrete, mkd. COLLINS WELL 1XX-3 SE4 SE4-T34N-R8E, bears S. 84°33' W., 8.95 chs. dist.
	From this same cor. point, an iron pipe, the casing of a drill hole, 4 1/2 ins. diam., firmly set in a concrete base, 2 ft. diam., 6 ins. high, projecting 6 1/2 ft. above the concrete, mkd. COLLINS WELL 1X NW4 SE4 SEC22 T34 R8E, bears N. 74°32' W., 22.74 chs. dist.
52.45	Trail road, bears N. 85° E. and N. 85° W.
80.00	Point for the cor. of secs. 25, 26, 35 and 36.
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.
	T 34 N R 8 E S 26 S 25 S 35 S 36 2010
	Deposit a magnet, in a white plastic case, at the base of the stainless steel post.

**Survey of the Subdivisional Lines,
T. 34 N., R. 8 E., Gila and Salt River Meridian, Arizona**

CHAINS	
	<p>Set a T shaped steel fence post near the cor.</p> <p>Terrain, gently rolling. Soil, sand. No timber; sage brush, Mormon Tea and various high desert grasses.</p> <hr/> <p>From the cor. of secs. 25, 30, 31 and 36, on the E. bdy. of the Tp., hereinbefore described.</p> <p>West, bet. secs. 25 and 36.</p> <p>Over broken and rolling terrain.</p>
2.15	Trail road, bears N. 50° E. and S. 50° W.
30.55	Trail road, bears S. 55° E. and N. 55° W.
32.00	<p>Point for the 80 1/16 sec. cor. of secs. 25 and 36.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 23 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center;"> <p>T 34 N R 8 E</p> <p>S 25</p> <p>80 ——— 1/16</p> <p>S 36</p> <p>2010</p> </div> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p> <p>Set a T shaped steel fence post near the cor.</p>
39.05	Trail road, bears S. 50° E. and N. 50° W.
66.75	Wash, 8 ft. wide, drains S. 70° E.
67.75	Wash, 9 ft. wide, drains S. 50° E.
72.00	<p>Point for the 1/4 sec. cor. of secs. 25 and 36.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 23 ins. in the ground, encircled with a collar of stone, with brass cap mkd.</p>

**Survey of the Subdivisional Lines,
T. 34 N., R. 8 E., Gila and Salt River Meridian, Arizona**

CHAINS	
	T 34 N R 8 E S 25 1/4 ——— S 36 2010
	Deposit a magnet, in a white plastic case, at the base of the stainless steel post.
	Set a T shaped steel fence post near the cor.
112.00	The cor. of secs. 25, 26, 35 and 36. Terrain, broken and rolling. Soil, sand. No timber; sage brush, Mormon Tea and various high desert grasses.
	<hr/> N. 0°01' W., bet. secs. 25 and 26. Over broken and rolling terrain.
36.25	Trail road, bears N. 10° E. and S. 10° W.
39.90	S. bank of Hole Reservoir, bears S. 75° E. and N. 70° W.
40.00	Point for the 1/4 sec. cor. of secs. 25 and 26. Set a magnet, in a white plastic case, 15 ins. in the ground. from which <p style="margin-left: 40px;"> A stainless steel post, 28 ins. long, 2 1/2 ins. diam., set 24 ins. in the ground, for a reference monument, bears S. 24°59' E., 70.0 ft. dist., with brass cap mkd. RM T34N R8E S25 70.0 FT TO COR 2010 and an arrow pointing to the cor. Deposit a magnet, in a white plastic case, at the base of the stainless steel post. </p> <p style="margin-left: 40px;"> A stainless steel post, 28 ins. long, 2 1/2 ins. diam., set 24 ins. in the ground, for a reference monument, bears S. 65°02' W., 80.0 ft. dist., with brass cap mkd. RM T34N R8E S26 80.0 FT TO COR 2010 and an arrow pointing to the cor. Deposit a magnet, in a white plastic case, at the base of the stainless steel post. </p> Cor. is located below the high water mark of Hole Reservoir.
48.00	N. berm of Hole Reservoir, 8 ft. high, 3 ft. wide, bears S. 10° E. and N. 10° W.

**Survey of the Subdivisional Lines,
T. 34 N., R. 8 E., Gila and Salt River Meridian, Arizona**

CHAINS							
51.55	B. I. A. Route 6130, a graded road, 18 ft. wide, bears N. 70° E. and S. 70° W.						
60.80	Utility line, 2 strand, bears S. 85° E. and N. 85° W.						
62.30	Wash, 10 ft. wide, 3 ft. deep, drains N. 20° E.						
75.10	Wash, 6 ft. wide, 2 ft. deep, drains N. 50° E.						
80.00	Point for the cor. of secs. 23, 24, 25 and 26. Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd. <div style="text-align: center;"> <table style="margin: auto;"> <tr> <td>T 34 N</td> <td>R 8 E</td> </tr> <tr> <td style="border-right: 1px solid black;">S 23</td> <td>S 24</td> </tr> <tr> <td style="border-right: 1px solid black;">S 26</td> <td>S 25</td> </tr> </table> <p>2010</p> </div> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p> <p>Set a T shaped steel fence post near the cor.</p> <p>Terrain, broken and rolling. Soil, loam over sandstone. No timber; sage brush, Mormon Tea and various high desert grasses.</p> <hr/> <p>From the cor. of secs. 19, 24, 25 and 30, on the E. bdy. of the Tp., hereinbefore described.</p> <p>West, bet. secs. 24 and 25.</p> <p>Over broken and rolling terrain.</p>	T 34 N	R 8 E	S 23	S 24	S 26	S 25
T 34 N	R 8 E						
S 23	S 24						
S 26	S 25						
1.20	Wash, 6 ft. wide, 4 ft. deep, drains S. 10° W.						
5.60	Tributary channel of Hamblin Wash, 15 ft. wide, drains S. 5° E.						
10.60	Main channel of Hamblin Wash, 30 ft. wide, 2 ft. deep, drains S. 25° E.						
25.90	Abandoned road, asphalt surface, 18 ft. wide, bears S. 35° E. and N. 35° W.						
27.75	Easterly right-of-way fence of U. S. Highway 89, barbed wire, 5 strand, bears S. 35° E. and N. 35° W.						

**Survey of the Subdivisional Lines,
T. 34 N., R. 8 E., Gila and Salt River Meridian, Arizona**

CHAINS	
29.15	Easterly edge of U. S. Highway 89, asphalt surface, 40 ft. wide, bears S. 55° E. and N. 55° W.
29.95	Westerly edge of U. S. Highway 89, bears S. 55° E. and N. 55° W.
31.50	Westerly right-of-way fence of U. S. Highway 89, barbed wire, 5 strand, bears S. 45° E. and N. 45° W.
32.00	Point for the 80 1/16 sec. cor. of secs. 24 and 25. Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 23 ins. in the ground, with brass cap mkd. <div style="text-align: center;"> T 34 N R 8 E S 24 80 ——— 1/16 S 25 2010 </div> Deposit a magnet, in a white plastic case, at the base of the stainless steel post. Set a T shaped steel fence post near the cor. From this cor. point, an aluminum tablet, 3 ins. diam., set in the center of a concrete culvert, mkd. AHD 5427.00 1742+81 + STA 1959, bears N. 8°00' W., 4.80 chs. dist.
35.50	Utility line, 10 strand, bears S. 35° E. and N. 35° W.
72.00	Point for the 1/4 sec. cor. of secs. 24 and 25. Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, underpinned with an aluminum rod, 36 ins. long, 3/4 in. diam., with brass cap mkd. <div style="text-align: center;"> T 34 N R 8 E S 24 1/4 ——— S 25 2010 </div> Deposit a magnet, in a white plastic case, at the base of the stainless steel post. Cor. is located 20 lks. N. of the top of a steep NE slope, and is supported by a sandstone bench, 2 x 9 ft., on the downhill side. The sandstone bench is braced by 2 T shaped steel fence posts, 6 ft. long, driven 3 ft. into the ground.
72.70	Ridge, bears North and South.

**Survey of the Subdivisional Lines,
T. 34 N., R. 8 E., Gila and Salt River Meridian, Arizona**

CHAINS	
80.50	Wash, 15 ft. wide, 5 ft. deep, drains North.
82.70	Wash, 25 ft. wide, 3 ft. deep, drains East.
85.20	Wash, 45 ft. wide, 3 ft. deep, drains N. 65° E.
92.10	Wash, 18 ft. wide, 1 ft. deep, drains S. 10° E.
99.10	Wash, 20 ft. wide, 5 ft. deep, drains North.
100.10	Wash, 25 ft. wide, 3 ft. deep, drains S. 80° E.
105.60	Wash, 35 ft. wide, 6 ft. deep, drains N. 55° E.
106.20	Wash, 9 ft. wide, 4 ft. deep, drains S. 40° E.
112.00	The cor. of secs. 23, 24, 25 and 26. Terrain, broken and rolling. Soil, sand. Timber, juniper and piñon; undergrowth, sage brush, Mormon Tea and various high desert grasses.
	N. 0°01' W., bet. secs. 23 and 24. Over broken and rolling terrain.
2.40	Wash, 8 ft. wide, 6 ft. deep, drains S. 85° E.
34.85	Trail road, bears S. 80° E. and S. 80° W.
40.00	Point for the 1/4 sec. cor. of secs. 23 and 24. Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.
	T 34 N R 8 E 1/4 S 23 S 24 2010
	Deposit a magnet, in a white plastic case, at the base of the stainless steel post. Set a T shaped steel fence post near the cor.
62.90	Billy Goat Wash, 30 ft. wide, 2 ft. deep, drains S. 35° E.; wash falls in a ravine 140 ft. deep.
80.00	Point for the cor. of secs. 13, 14, 23 and 24.

Survey of the Subdivisional Lines,
T. 34 N., R. 8 E., Gila and Salt River Meridian, Arizona

CHAINS

Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.

T 34 N	R 8 E
S 14	S 13
S 23	S 24

2010

Deposit a magnet, in a white plastic case, at the base of the stainless steel post.

Set a T shaped steel fence post near the cor.

Terrain, broken and rolling.

Soil, clayish loam and sandstone.

Timber, sparse juniper and piñon; undergrowth, sage brush, Mormon Tea and various high desert grasses.

From the cor. of secs. 13, 18, 19 and 24, on the E. bdy. of the Tp., hereinbefore described.

West, bet. secs. 13 and 24.

Over broken and rolling terrain.

24.30 Top of Echo Cliffs, bears S. 20° E. and N. 20° W.

29.00 Base of a cliff, bears S. 25° E. and N. 25° W.

31.30 Top of a cliff, bears S. 25° E. and N. 25° W.

32.00 True point for the 80 1/16 sec. cor. of secs. 13 and 24; falls on the steep SW face of Echo Cliffs, where it is impracticable to establish a permanent monument.

From this true point, the point selected for a witness cor. to the 80 1/16 sec. cor. of secs. 13 and 24, bears N. 1°30' E., 1.30 chs. dist.

Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 25 ins. in the ground, with brass cap mkd.

**Survey of the Subdivisional Lines,
T. 34 N., R. 8 E., Gila and Salt River Meridian, Arizona**

CHAINS	
	WC T 34 N R 8 E S 13 80 ————— 1/16 S 24 ↓ 2010
	Deposit a magnet, in a white plastic case, at the base of the stainless steel post. Thence continue descent of cliff faces.
51.60	Toe of a sandstone bench below Echo Cliffs, bears S. 30° E. and N. 30° W.
62.60	Hamblin Wash, 50 ft. wide, 2 ft. deep, drains S. 15° E.
72.00	Point for the 1/4 sec. cor. of secs. 13 and 24. Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.
	T 34 N R 8 E S 13 1/4 ————— S 24 2010
	Deposit a magnet, in a white plastic case, at the base of the stainless steel post. Set a T shaped steel fence post near the cor. From this cor. point, the most southerly cor. of a concrete water well cistern for Curtis Well, 6 x 6 x 4 ft. high, sides extend N. 50° E. and N. 40° W., with an iron hand pump, bears S. 51°56' E., 22.71 chs. dist.
73.55	Road, asphalt surface, 12 ft. wide, bears S. 25° E. and N. 25° W.
87.45	Easterly right-of-way fence of U. S. Highway 89, barbed wire, 5 strand, bears S. 30° E. and N. 30° W.
88.85	Easterly edge of U. S. Highway 89, asphalt surface, 40 ft. wide, bears S. 30° E. and N. 30° W.
89.60	Westerly edge of U. S. Highway 89, bears S. 30° E. and N. 30° W.

**Survey of the Subdivisional Lines,
T. 34 N., R. 8 E., Gila and Salt River Meridian, Arizona**

CHAINS	
91.00	Westerly right-of-way fence of U. S. Highway 89, barbed wire, 5 strand, bears S. 30° E. and N. 30° W.
95.05	Utility line, 10 strand, bears S. 35° E. and N. 35° W.
112.00	The cor. of secs. 13, 14, 23 and 24. Terrain, broken and rolling. Soil, sand. No timber; sage brush, Mormon Tea and various high desert grasses.

	N. 0°01' W., bet. secs. 13 and 14. Over broken and rolling terrain.
25.05	Utility line, 10 strand, bears S. 35° E. and N. 35° W.
30.60	Southerly right-of-way fence of U. S. Highway 89, barbed wire, 5 strand, bears S. 45° E. and N. 45° W.
32.00	Southerly edge of U. S. Highway 89, asphalt surface, 40 ft. wide, bears S. 20° E. and N. 20° W.
32.90	Northerly edge of U. S. Highway 89, bears S. 20° E. and N. 20° W.
33.80	Northerly right-of-way fence of U. S. Highway 89, barbed wire, 5 strand, bears S. 75° E. and N. 75° W.
33.90	Wash, 6 ft. wide, 1 ft. deep, drains S. 85° E.
40.00	Point for the 1/4 sec. cor. of secs. 13 and 14. Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.
	T 34 N R 8 E 1/4 S 14 S 13 2010
	Deposit a magnet, in a white plastic case, at the base of the stainless steel post. Set a T shaped steel fence post near the cor.

**Survey of the Subdivisional Lines,
T. 34 N., R. 8 E., Gila and Salt River Meridian, Arizona**

CHAINS									
	<p>From this cor. point, an aluminum tablet, 3 ins. diam., set in the center of a concrete culvert, mkd. ELEV. 5605.15 + STA 1832.25 1956, bears S. 3°22' W., 6.10 chs. dist.</p>								
44.85	Wash, 18 ft. wide, 5 ft. deep, drains N. 65° E.								
80.00	<p>Point for the cor. of secs. 11, 12, 13 and 14.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 25 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center;"> <table style="margin: auto;"> <tr> <td>T 34 N</td> <td>R 8 E</td> </tr> <tr> <td>S 11</td> <td>S 12</td> </tr> <tr> <td>S 14</td> <td>S 13</td> </tr> </table> <p>2010</p> </div> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p> <p>Set a T shaped steel fence post near the cor.</p> <p>Cor. is located 20 lks. W. of the top of a ridge, bears S. 10° E. and N. 10° W. and alongside a sandstone ledge, 1 ft. high.</p> <p>Terrain, broken and rolling. Soil, loam. Timber, sparse juniper and piñon; undergrowth, sage brush, Mormon Tea and various high desert grasses.</p> <hr/> <p>From the cor. of secs. 7, 12, 13 and 18, on the E. bdy. of the Tp., hereinbefore described.</p> <p>West, bet. secs. 12 and 13.</p> <p>Over broken and rolling terrain.</p>	T 34 N	R 8 E	S 11	S 12	S 14	S 13		
T 34 N	R 8 E								
S 11	S 12								
S 14	S 13								
32.00	<p>Point for the 80 1/16 sec. cor. of secs. 12 and 13.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 25 ins. in the ground, underpinned with a U shaped steel fence post, 5 ft. long, with brass cap mkd.</p> <div style="text-align: center;"> <table style="margin: auto;"> <tr> <td>T 34 N</td> <td>R 8 E</td> </tr> <tr> <td>S 12</td> <td></td> </tr> <tr> <td>80</td> <td>1/16</td> </tr> <tr> <td>S 13</td> <td></td> </tr> </table> <p>2010</p> </div>	T 34 N	R 8 E	S 12		80	1/16	S 13	
T 34 N	R 8 E								
S 12									
80	1/16								
S 13									

**Survey of the Subdivisional Lines,
T. 34 N., R. 8 E., Gila and Salt River Meridian, Arizona**

CHAINS	
	<p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p> <p>Set a T shaped steel fence post near the cor.</p> <p>Thence across broken terrain, transitioning into the steep descent of Echo Cliffs.</p>
66.80	Bottom of Echo Cliffs, bears S. 10° E. and N. 10° W.
72.00	Point for the 1/4 sec. cor. of secs. 12 and 13.
	<p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 23 ins. in the ground, encircled with a collar of stone, with brass cap mkd.</p> <p style="text-align: center;">T 34 N R 8 E S 12 1/4 ——— S 13</p> <p style="text-align: center;">2010</p>
	<p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p> <p>Set a T shaped steel fence post near the cor.</p> <p>From this cor. point, a brass tablet, 3 1/2 ins. diam., established by U.S. Public Health Service, set in the top of the concrete water well cistern for Tsin-Besk-Skunk Well, 5 x 5 x 2 1/2 ft. high, sides extend S. 70° W. and N. 20° W., with an iron hand pump, bears S. 85°48' W., 21.20 chs. dist.</p>
79.70	Top of a sandstone bench below Echo Cliffs, 150 ft. high, bears South and N. 20° W.
82.40	Toe of a sandstone bench below Echo Cliffs, bears North and S. 20° E.
94.30	Hamblin Wash, 60 ft. wide, 2 ft. deep, drains South.
98.90	Trail road, old highway, bears S. 20° E. and N. 20° W.
112.00	The cor. of secs. 11, 12, 13 and 14.

**Survey of the Subdivisional Lines,
T. 34 N., R. 8 E., Gila and Salt River Meridian, Arizona**

CHAINS	
	<p>Terrain, broken and rolling. Soil, sand and sandstone Timber, sparse juniper and piñon; undergrowth, sage brush, Mormon Tea and various high desert grasses.</p> <hr/> <p>N. 0°01' W., bet. secs. 11 and 12.</p> <p>Over broken and rolling terrain.</p>
17.00	Trail road, old highway, bears S. 70° E. and N. 70° W.
40.00	Point for the 1/4 sec. cor. of secs. 11 and 12.
	<p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T 34 N R 8 E 1/4 S 11 S 12 2010</p> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p> <p>Set a T shaped steel fence post near the cor.</p>
76.90	Hamblin Wash, 10 ft. wide, 1 ft. deep, drains S. 35° E.
78.90	Hamblin Wash, 10 ft. wide, 1 ft. deep, drains S. 60° E.
80.00	Point for the cor. of secs. 1, 2, 11 and 12.
	<p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T 34 N R 8 E S 2 S 1 S 11 S 12 2010</p> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p> <p>Set a T shaped steel fence post near the cor.</p>

**Survey of the Subdivisional Lines,
T. 34 N., R. 8 E., Gila and Salt River Meridian, Arizona**

CHAINS	
	<p>Terrain, rolling. Soil, sand and sandstone. Timber, sparse juniper and piñon; undergrowth, sage brush, salt brush, prickly pear cactus and various high desert grasses.</p> <hr/> <p>From the cor. of secs. 1, 6, 7 and 12, on the E. bdy. of the Tp., hereinbefore described.</p> <p>West, bet. secs. 1 and 12.</p> <p>Over broken and rolling terrain.</p>
32.00	<p>Point for the 80 1/16 sec. cor. of secs. 1 and 12.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 22 ins. in sandstone bedrock, with brass cap mkd.</p> <div style="text-align: center; margin: 10px 0;"> <p>T 34 N R 8 E</p> <p>S 1</p> <p>80 ——— 1/16</p> <p>S 12</p> <p>2010</p> </div> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p> <p>Cor. is located on the steep easterly face of a sandstone outcrop, 10 ft. high, bears North and South.</p> <p>Thence continue over broken and rolling land, transitioning into the steep ascent of the backside of Echo Cliffs ridge.</p>
66.60	<p>Top of the backside of Echo Cliffs ridge, bears North and South; continue across the ridge of Echo Cliffs.</p>
72.00	<p>Point for the 1/4 sec. cor. of secs. 1 and 12.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 22 ins. in sandstone bedrock, with brass cap mkd.</p> <div style="text-align: center; margin: 10px 0;"> <p>T 34 N R 8 E</p> <p>S 1</p> <p>1/4 ———</p> <p>S 12</p> <p>2010</p> </div> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p>

**Survey of the Subdivisional Lines,
T. 34 N., R. 8 E., Gila and Salt River Meridian, Arizona**

CHAINS	
	Cor. is located at the base of a W. facing cliff, 8 ft. high, bears N. 20° E. and S. 20° W.
76.10	Top of Echo Cliffs, bears S. 5° E. and N. 5° W.; continue down the steep descent of Echo Cliffs, transitioning into broken and rolling terrain.
112.00	The cor. of secs. 1, 2, 11 and 12. Terrain, broken and rolling. Soil, sand and sandstone. Timber, sparse juniper and piñon; undergrowth, sage brush, Mormon Tea and various high desert grasses.
	<hr/>
	N. 0°01' W., bet. secs. 1 and 2. Over broken and rolling terrain.
40.00	Point for the 1/4 sec. cor. of secs. 1 and 2. Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 25 ins. in the ground, with brass cap mkd. <div style="text-align: center;"> T 34 N R 8 E 1/4 S 2 S 1 2010 </div>
	Deposit a magnet, in a white plastic case, at the base of the stainless steel post. Set a T shaped steel fence post near the cor.
	From this cor. point, the southwesterly cor. of a concrete water well cistern, 6 x 6 x 4 ft. high, sides extend N. 10° E. and S. 80° E., mkd. 3A-PHS 10, bears N. 80°51' W., 24.45 chs. dist.
80.00	The cor. secs. 1, 2, 35 and 36, on the N. bdy. of the Tp., hereinbefore described. Terrain, broken and rolling. Soil, sand and sandstone. Timber, sparse juniper and piñon; undergrowth, sage brush, Mormon Tea and various high desert grasses.
	<hr/>
	From the cor. of secs. 2, 3, 34 and 35, on the S. bdy. of the Tp., hereinbefore described. N. 0°02' W., bet. secs. 34 and 35.

Survey of the Subdivisional Lines,
T. 34 N., R. 8 E., Gila and Salt River Meridian, Arizona

CHAINS	
	Over rolling terrain.
40.00	Point for the 1/4 sec. cor. of secs. 34 and 35. Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 25 ins. in the ground, encircled with a collar of stone, with brass cap mkd. <div style="text-align: center;"> T 34 N R 8 E 1/4 S 34 S 35 2010 </div>
	Deposit a magnet, in a white plastic case, at the base of the stainless steel post.
	Set a T shaped steel fence post near the cor.
80.00	Point for the cor. of secs. 26, 27, 34 and 35. Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 25 ins. in the ground, with brass cap mkd. <div style="text-align: center;"> T 34 N R 8 E S 27 S 26 S 34 S 35 2010 </div>
	Deposit a magnet, in a white plastic case, at the base of the stainless steel post.
	Set a T shaped steel fence post near the cor.
	Terrain, rolling to level. Soil, sand and red clay. No timber; sage brush and various high desert grasses.
	<hr/>
	From the cor. of secs. 25, 26, 35 and 36.
	West, bet. secs. 26 and 35.
	Over rolling to level terrain.
9.15	Trail road, bears N. 25° E. and S. 25° W.
30.00	Trail road, bears N. 30° E. and S. 30° W.
40.00	Point for the 1/4 sec. cor. of secs. 26 and 35.

**Survey of the Subdivisional Lines,
T. 34 N., R. 8 E., Gila and Salt River Meridian, Arizona**

CHAINS	
	<p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T 34 N R 8 E S 26 1/4 ——— S 35</p> <p style="text-align: center;">2010</p> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p> <p>Set a T shaped steel fence post near the cor.</p>
41.40	Wash, 4 ft. wide, drains N. 30° E.
59.10	Trail road, bears N. 15° E. and S. 15° W.
59.85	Utility line, 2 strand, bears North and South.
80.00	The cor. of secs. 26, 27, 34 and 35.
	<p>Terrain, rolling to level. Soil, sand and red clay. No timber; sage brush and various high desert grasses.</p> <hr/> <p>N. 0°02' W., bet. secs. 26 and 27.</p> <p>Over rolling to level terrain.</p>
13.95	B. I. A. Route 6130, a graded road, 20 ft. wide, bears N. 70° E. and S. 70° W.
33.60	Wash, 4 ft. wide, 2 ft. deep, drains S. 45° W.
37.70	Wash, 4 ft. wide, 2 ft. deep, drains S. 35° E.
39.10	Wash, 4 ft. wide, 2 ft. deep, drains S. 50° E.
40.00	Point for the 1/4 sec. cor. of secs. 26 and 27.
	<p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 25 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T 34 N R 8 E 1/4 S 27 S 26</p> <p style="text-align: center;">2010</p>

**Survey of the Subdivisional Lines,
T. 34 N., R. 8 E., Gila and Salt River Meridian, Arizona**

CHAINS							
	<p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p> <p>Set a T shaped steel fence post near the cor.</p>						
54.55	Trail road, bears S. 80° E. and N. 80° W.; continue across level to gently rolling terrain, crossing numerous trail roads.						
69.30	Utility line, 2 strand, bears S. 80° E. and N. 80° W.						
74.55	Utility line, 2 strand, bears N. 20° E. and S. 20° W.						
74.80	Trail road, bears N. 80° E. and S. 80° W.						
75.70	S. wall of a shed, 14 x 18 ft., bears S. 85° E. and N. 85° W.						
75.97	N. wall of the same shed, bears S. 85° E. and N. 85° W.						
80.00	Point for the cor. of secs. 22, 23, 26 and 27.						
	<p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with brass cap mkd.</p> <table border="0" style="margin-left: auto; margin-right: auto;"> <tr> <td>T 34 N</td> <td>R 8 E</td> </tr> <tr> <td>S 22</td> <td>S 23</td> </tr> <tr> <td>S 27</td> <td>S 26</td> </tr> </table> <p align="center">2010</p>	T 34 N	R 8 E	S 22	S 23	S 27	S 26
T 34 N	R 8 E						
S 22	S 23						
S 27	S 26						
	<p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p> <p>Set a T shaped steel fence post near the cor.</p> <p>Terrain, level. Soil, sand and red clay. No timber; various high desert grasses.</p> <hr/> <p>From the cor. of secs. 23, 24, 25 and 26.</p> <p>West, bet. secs. 23 and 26.</p> <p>Over rolling to level terrain.</p>						
40.00	<p>Point for the 1/4 sec. cor. of secs. 23 and 26.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with brass cap mkd.</p>						

**Survey of the Subdivisional Lines,
T. 34 N., R. 8 E., Gila and Salt River Meridian, Arizona**

CHAINS	
	T 34 N R 8 E S 23 1/4 ——— S 26 2010
	Deposit a magnet, in a white plastic case, at the base of the stainless steel post. Set a T shaped steel fence post near the cor.
61.85	Trail road, bears S. 30° E. and N. 30° W.
76.20	Trail road, bears N. 10° E. and S. 10° W.
77.30	Trail road, bears S. 45° E. and N. 45° W.
80.00	The cor. of secs. 22, 23, 26 and 27.
	Terrain, level. Soil, sand and loam. No timber; various high desert grasses.
	N. 0°02' W., bet. secs. 22 and 23. Over level to rolling terrain.
0.75	Trail road, bears S. 85° E. and N. 85° W.
2.15	Trail road, bears N. 45° E. and S. 45° W.
14.10	Wash, at the base of a steep, N. facing slope, 6 ft. wide, drains North; continue N. along wash.
22.10	Leave wash, 10 ft. wide, drains N. 40° E.
38.80	Trail road, along ridgetop, bears East and West.
40.00	Point for the 1/4 sec. cor. of secs. 22 and 23.
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, encircled with a collar of stone, with brass cap mkd.
	T 34 N R 8 E 1/4 S 22 S 23 2010

**Survey of the Subdivisional Lines,
T. 34 N., R. 8 E., Gila and Salt River Meridian, Arizona**

CHAINS							
	<p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p> <p>Set a T shaped steel fence post near the cor.</p>						
43.10	Wash, 10 ft. wide, drains S. 65° E.						
54.45	Trail road, bears S. 85° E. and N. 85° W.						
80.00	<p>Point for the cor. of secs. 14, 15, 22 and 23.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 12 ins. in the ground, to bedrock, in a mound of stone, 3 1/2 ft. base, to top, with brass cap mkd.</p> <div style="text-align: center;"> <table border="1"> <tr> <td colspan="2">T 34 N R 8 E</td> </tr> <tr> <td>S 15</td> <td>S 14</td> </tr> <tr> <td>S 22</td> <td>S 23</td> </tr> </table> <p>2010</p> </div> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p> <p>Cor. is located near the top of a gentle southerly facing hill.</p> <p>Terrain, rolling. Soil, rocky over bedrock. No timber; various high desert grasses.</p> <hr/> <p>From the cor. of secs. 13, 14, 23 and 24.</p> <p>West, bet. secs. 14 and 23.</p> <p>Over rolling terrain.</p>	T 34 N R 8 E		S 15	S 14	S 22	S 23
T 34 N R 8 E							
S 15	S 14						
S 22	S 23						
40.00	<p>Point for the 1/4 sec. cor. of secs. 14 and 23.</p> <p>Set an aluminum rod, 36 ins. long, 3/4 in. diam., 24 ins. in the ground, with no cap.</p> <p>from which</p> <p style="padding-left: 40px;">A stainless steel post, 28 ins. long, 2 1/2 ins. diam., set 24 ins. in the ground, for a reference monument, bears S. 89°59' E., 99.0 ft. dist., with brass cap mkd. RM T34N R8E S14 99.0 FT TO COR 2010 and an arrow pointing to the cor. Deposit a magnet, in a white plastic case, at the base of the stainless steel post. Set a T shaped steel fence post near the reference monument.</p>						

**Survey of the Subdivisional Lines,
T. 34 N., R. 8 E., Gila and Salt River Meridian, Arizona**

CHAINS	
	<p>A stainless steel post, 28 ins. long, 2 1/2 ins. diam., set 26 ins. in the ground, for a reference monument, bears S. 0°02' E., 99.0 ft. dist., with brass cap mkd. RM T34N R8E S23 99.0 FT TO COR 2010 and an arrow pointing to the cor. Deposit a magnet, in a white plastic case, at the base of the stainless steel post. Set a T shaped steel fence post near the reference monument.</p> <p>Deposit a magnet, in a white plastic case, alongside the aluminum rod.</p> <p>Cor. is located in a wash, 3 ft. wide, 3 ft. deep, drains S. 80° W.</p>
80.00	<p>The cor. of secs. 14, 15, 22 and 23.</p> <p>Terrain, rolling. Soil, sand. Timber, scattered juniper; undergrowth, sage brush and various high desert grasses.</p> <hr/> <p>N. 0°02' W., bet. secs. 14 and 15.</p> <p>Over rolling terrain.</p>
6.75	Trail road, bears East and West.
10.40	Trail road, bears S. 80° E. and N. 80° W.
26.20	Trail road, bears N. 50° E. and S. 50° W.
37.30	Wash, 15 ft. wide, drains N. 55° E.
37.65	Trail, 8 ft. wide, bears N. 60° E. and S. 60° W.
40.00	<p>Point for the 1/4sec. cor. of secs. 14 and 15.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 10 ins. in the ground, to bedrock, in a mound of stone, 3 1/2 ft. base, to top, with brass cap mkd.</p> <p style="text-align: center;">T 34 N R 8 E 1/4 S 15 S 14</p> <p style="text-align: center;">2010</p> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p>

**Survey of the Subdivisional Lines,
T. 34 N., R. 8 E., Gila and Salt River Meridian, Arizona**

CHAINS							
79.80	Wash, 15 ft. wide, drains East.						
80.00	Point for the cor. of secs. 10, 11, 14 and 15. Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, encircled with a collar of stone, with brass cap mkd. <div style="text-align: center;"> <table style="margin: auto;"> <tr> <td>T 34 N</td> <td>R 8 E</td> </tr> <tr> <td style="border-right: 1px solid black;">S 10</td> <td>S 11</td> </tr> <tr> <td style="border-right: 1px solid black;">S 15</td> <td>S 14</td> </tr> </table> <p>2010</p> </div> Deposit a magnet, in a white plastic case, at the base of the stainless steel post. Set a T shaped steel fence post near the cor. Cor. is located on a flat bench, near the northerly bank of a wash, at the bottom of a drainage canyon. A small rock barrier was constructed between the cor. and the wash. Terrain, rolling. Soil, sand. Timber, scattered juniper; undergrowth, sage brush and various high desert grasses. <hr style="width: 50%; margin-left: 0;"/> From the cor. of secs. 11, 12, 13 and 14. West, bet. secs. 11 and 14. Over rolling terrain.	T 34 N	R 8 E	S 10	S 11	S 15	S 14
T 34 N	R 8 E						
S 10	S 11						
S 15	S 14						
20.65	Easterly right-of-way fence of U. S. Highway 89, barbed wire, 5 strand, bears S. 10° E. and N. 10° W.						
21.85	Easterly edge of U. S. Highway 89, asphalt surface, 38 ft. wide, bears S. 10° E. and N. 10° W.						
22.50	Westerly edge of U. S. Highway 89, bears S. 10° E. and N. 10° W.						
23.70	Westerly right-of-way fence of U. S. Highway 89, barbed wire, 5 strand, bears S. 10° E. and N. 10° W.						
27.50	Utility line, 10 strand, bears S. 10° E. and N. 10° W.						
40.00	Point for the 1/4 sec. cor. of secs. 11 and 14.						

**Survey of the Subdivisional Lines,
T. 34 N., R. 8 E., Gila and Salt River Meridian, Arizona**

CHAINS	
	<p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 12 ins. in the ground, to bedrock, in a mound of stone, 4 ft. base, to top, with brass cap mkd.</p> <p style="text-align: center;">T 34 N R 8 E S 11 1/4 ——— S 14</p> <p style="text-align: center;">2010</p> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p>
62.85	Trail road, bears S. 40° E. and N. 40° W.
80.00	<p>The cor. of secs. 10, 11, 14 and 15.</p> <p>Terrain, rolling. Soil, sand. Timber, scattered juniper; undergrowth, sage brush and various high desert grasses.</p> <hr/> <p>N. 0°02' W., bet. secs. 10 and 11.</p> <p>Over rolling terrain.</p>
34.70	Trail road, bears S. 10° E. and N. 10° W.
40.00	<p>Point for the 1/4 sec. cor. of secs. 10 and 11.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T 34 N R 8 E 1/4 S 10 S 11</p> <p style="text-align: center;">2010</p> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p> <p>Set a T shaped steel fence post near the cor.</p>
60.85	Trail road, bears N. 70° E. and S. 70° W.
80.00	Point for the cor. of secs. 2, 3, 10 and 11.

**Survey of the Subdivisional Lines,
T. 34 N., R. 8 E., Gila and Salt River Meridian, Arizona**

CHAINS

Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam.,
25 ins. in the ground, with brass cap mkd.

T 34 N	R 8 E
S 3	S 2
S 10	S 11

2010

Deposit a magnet, in a white plastic case, at the base of the
stainless steel post.

Raise a mound of stone, 3 1/2 ft. base, 2 ft. high, N. of cor.

Terrain, rolling.

Soil, sand.

Timber, scattered juniper; undergrowth, sage brush, prickly pear
cactus and various high desert grasses.

From the cor. of secs. 1, 2, 11 and 12.

West, bet. secs. 2 and 11.

Over rolling terrain.

1.60 Hamblin Wash, 15 ft. wide, 1 ft. deep, drains S. 15° E.

40.00 Point for the 1/4 sec. cor. of secs. 2 and 11.

Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam.,
25 ins. in the ground, with brass cap mkd.

T 34 N	R 8 E
	S 2
1/4	_____
	S 11

2010

Deposit a magnet, in a white plastic case, at the base of the
stainless steel post.

Set a T shaped steel fence post near the cor.

40.30 Wash, 5 ft. wide, drains S. 20° E.

46.95 Dirt road, old U. S. Highway 89, bears S. 25° E. and N. 25° W.

**Survey of the Subdivisional Lines,
T. 34 N., R. 8 E., Gila and Salt River Meridian, Arizona**

CHAINS	
47.75	Easterly right-of-way fence of U. S. Highway 89, barbed wire, 5 strand, bears S. 25° E. and N. 25° W.
50.75	Easterly edge of U. S. Highway 89, asphalt surface, 40 ft. wide, bears S. 25° E. and N. 25° W.
51.45	Westerly edge of U. S. Highway 89, bears S. 25° E. and N. 25° W.
52.75	Westerly right-of-way fence of U. S. Highway 89, barbed wire, 5 strand, bears S. 25° E. and N. 25° W.
55.35	Utility line, 10 strand, bears S. 25° E. and N. 25° W.
80.00	The cor. of secs. 2, 3, 10 and 11. Terrain, rolling. Soil, sand and rocky. Timber, scattered juniper; undergrowth, sage brush, prickly pear cactus and various high desert grasses.

	N. 0°02' W., bet. secs. 2 and 3. Over rolling terrain.
40.00	Point for the 1/4 sec. cor. of secs. 2 and 3. Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 25 ins. in the ground, with brass cap mkd. <div style="text-align: center;"> T 34 N R 8 E 1/4 S 3 S 2 2010 </div> Deposit a magnet, in a white plastic case, at the base of the stainless steel post. Set a T shaped steel fence post near the cor. From this cor. point, an aluminum tablet, 3 ins. diam., set in a concrete cylinder, 6 ins. diam., firmly set, mkd. ADOT HWY DIV. 19, with an angle iron nearby mkd. P.O.T. 1967+99.77 STA., bears N. 9°03' E., 19.515 chs. dist. From this same cor. point, an aluminum tablet, 3 ins. diam., set in a concrete cylinder, 6 ins. diam., firmly set, mkd. ADOT HWY DIV. 19, with an angle iron nearby mkd. P.O.T. 1967+99.77 STA., bears N. 16°07' E., 21.22 chs. dist.
56.65	Utility line, 10 strand, bears S. 15° E. and N. 15° W.

**Survey of the Subdivisional Lines,
T. 34 N., R. 8 E., Gila and Salt River Meridian, Arizona**

CHAINS	
63.10	Wash, 4 ft. wide, drains N. 70° E.
67.10	Southwesterly right-of-way fence of U. S. Highway 89, barbed wire, 5 strand, bears S. 15° E. and N. 15° W.
67.70	Asphalt surfaced portion of an access road, 15 ft. wide, bears N. 70° E. and S. 70° W.
70.40	Southwesterly edge of U. S. Highway 89, asphalt surface, 40 ft. wide, bears S. 20° E. and N. 20° W.
72.05	Northeasterly edge of U. S. Highway 89, bears S. 20° E. and N. 20° W.
75.30	Northeasterly right-of-way fence of U. S. Highway 89, barbed wire, 5 strand, bears S. 20° E. and N. 20° W.
77.00	Wash, 4 ft. wide, 3 ft. deep, drains S. 80° E.
80.00	The cor. of secs. 2, 3, 34 and 35, on the N. bdy. of the Tp., hereinbefore described.
	Terrain, rolling. Soil, sand and rocky. Timber, scattered juniper; undergrowth, sage brush, yucca cactus and various high desert grasses.
	From the cor. of secs. 3, 4, 33 and 34, on the S. bdy. of the Tp., hereinbefore described.
	N. 0°02' W., bet. secs. 33 and 34.
	Over level terrain.
10.45	Trail road, bears N. 10° E. and S. 10° W.
40.00	Point for the 1/4 sec. cor. of secs. 33 and 34.
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 22 ins. in the ground, encircled with a collar of stone, with brass cap mkd.
	T 34 N R 8 E 1/4 S 33 S 34 2010
	Deposit a magnet, in a white plastic case, at the base of the stainless steel post.

**Survey of the Subdivisional Lines,
T. 34 N., R. 8 E., Gila and Salt River Meridian, Arizona**

CHAINS									
	Set a T shaped steel fence post near the cor.								
57.10	B. I. A. Route 6130, a graded road, 20 ft. wide, bears N. 50° E. and S. 50° W.								
61.10	Trail road, bears N. 65° E. and S. 65° W.								
65.10	Trail road, bears N. 70° E. and S. 70° W.								
80.00	Point for the cor. of secs. 27, 28, 33 and 34.								
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 25 ins. in the ground, with brass cap mkd.								
	<table style="margin-left: auto; margin-right: auto;"> <tr> <td colspan="2">T 34 N R 8 E</td> </tr> <tr> <td style="border-right: 1px solid black; padding: 0 5px;">S 28</td> <td style="padding: 0 5px;">S 27</td> </tr> <tr> <td style="border-right: 1px solid black; padding: 0 5px;">S 33</td> <td style="padding: 0 5px;">S 34</td> </tr> </table>	T 34 N R 8 E		S 28	S 27	S 33	S 34		
T 34 N R 8 E									
S 28	S 27								
S 33	S 34								
	2010								
	Deposit a magnet, in a white plastic case, at the base of the stainless steel post.								
	Set a T shaped steel fence post near the cor.								
	Terrain, rolling.								
	Soil, sand and rocky.								
	Timber, scattered juniper; undergrowth, various high desert grasses.								
	<hr/>								
	From the cor. of secs. 26, 27, 34 and 35.								
	West, bet. secs. 27 and 34.								
	Over rolling terrain.								
39.30	B. I. A. Route 6130, a graded road, 20 ft. wide, bears N. 75° E. and S. 75° W.								
40.00	Point for the 1/4 sec. cor. of secs. 27 and 34.								
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 2 ins. below the surface of the ground, with brass cap mkd.								
	<table style="margin-left: auto; margin-right: auto;"> <tr> <td colspan="2">T 34 N R 8 E</td> </tr> <tr> <td colspan="2" style="text-align: center;">S 27</td> </tr> <tr> <td style="text-align: center;">1/4</td> <td style="border-top: 1px solid black; width: 50px;"></td> </tr> <tr> <td colspan="2" style="text-align: center;">S 34</td> </tr> </table>	T 34 N R 8 E		S 27		1/4		S 34	
T 34 N R 8 E									
S 27									
1/4									
S 34									
	2010								

**Survey of the Subdivisional Lines,
T. 34 N., R. 8 E., Gila and Salt River Meridian, Arizona**

CHAINS	
	<p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p> <p>Cor. is located near the W. edge of B. I. A. Route 6130.</p>
56.20	Trail road, bears N. 45° E. and S. 45° W.
57.15	Trail road, bears N. 45° E. and S. 45° W.
80.00	The cor. of secs. 27, 28, 33 and 34.
	<p>Terrain, rolling. Soil, sand and rocky. Timber, scattered juniper; undergrowth, various high desert grasses.</p> <hr/>
	N. 0°02' W., bet. secs. 27 and 28.
	Over rolling terrain.
14.30	Trail road, bears East and West.
40.00	Point for the 1/4 sec. cor. of secs. 27 and 28.
	<p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T 34 N R 8 E 1/4 S 28 S 27</p> <p style="text-align: center;">2010</p>
	<p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p> <p>Set a T shaped steel fence post near the cor.</p>
75.90	Trail road, bears N. 80° E. and S. 80° W.
79.90	Wash, 5 ft. wide, drains S. 50° W.
80.00	Point for the cor. of secs. 21, 22, 27 and 28.
	<p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 25 ins. in the ground, with brass cap mkd.</p>

Survey of the Subdivisional Lines,
T. 34 N., R. 8 E., Gila and Salt River Meridian, Arizona

CHAINS									
	<table border="0"> <tr> <td>T 34 N</td> <td>R 8 E</td> </tr> <tr> <td>S 21</td> <td>S 22</td> </tr> <tr> <td>S 28</td> <td>S 27</td> </tr> </table> <p>2010</p> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p> <p>Set a T shaped steel fence post near the cor.</p> <p>Terrain, rolling. Soil, rocky. Timber, scattered juniper; undergrowth, sage brush and various high desert grasses.</p> <hr/> <p>From the cor. of secs. 22, 23, 26 and 27.</p> <p>West, bet. secs. 22 and 27.</p> <p>Over rolling terrain.</p>	T 34 N	R 8 E	S 21	S 22	S 28	S 27		
T 34 N	R 8 E								
S 21	S 22								
S 28	S 27								
40.00	<p>Point for the 1/4 sec. cor. of secs. 22 and 27.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with brass cap mkd.</p>								
	<table border="0"> <tr> <td>T 34 N</td> <td>R 8 E</td> </tr> <tr> <td></td> <td>S 22</td> </tr> <tr> <td>1/4</td> <td>—</td> </tr> <tr> <td></td> <td>S 27</td> </tr> </table> <p>2010</p> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p> <p>Set a T shaped steel fence post near the cor.</p>	T 34 N	R 8 E		S 22	1/4	—		S 27
T 34 N	R 8 E								
	S 22								
1/4	—								
	S 27								
52.00	<p>Trail road, bears N. 85° E. and S. 85° W.</p>								
60.25	<p>Trail road, bears S. 30° E. and N. 30° W.</p>								
80.00	<p>The cor. of secs. 21, 22, 27 and 28.</p> <p>Terrain, rolling. Soil, rocky. Timber, scattered juniper; undergrowth, various high desert grasses.</p> <hr/> <p>N. 0°02' W., bet. secs. 21 and 22.</p>								

**Survey of the Subdivisional Lines,
T. 34 N., R. 8 E., Gila and Salt River Meridian, Arizona**

CHAINS	
	Over rolling terrain.
14.65	Trail road, bears S. 85° E. and N. 85° W.
24.25	Trail road, bears N. 55° E. and S. 55° W.
24.85	Trail road, bears N. 40° E. and S. 40° W.
40.00	Point for the 1/4 sec. cor. of secs. 21 and 22. Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 25 ins. in the ground, with brass cap mkd. <div style="text-align: center;"> T 34 N R 8 E 1/4 S 21 S 22 2010 </div> Deposit a magnet, in a white plastic case, at the base of the stainless steel post. Set a T shaped steel fence post near the cor.
80.00	Point for the cor. of secs. 15, 16, 21 and 22. Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 18 ins. in the ground, to bedrock, encircled with a collar of stone, with brass cap mkd. <div style="text-align: center;"> T 34 N R 8 E S 16 S 15 S 21 S 22 2010 </div> Deposit a magnet, in a white plastic case, at the base of the stainless steel post. Set a T shaped steel fence post near the cor. Terrain, rolling. Soil, rocky. No timber; prickly pear cactus, Mormon Tea and various high desert grasses.
	From the cor. of secs. 14, 15, 22 and 23. West, bet. secs. 15 and 22.
40.00	Point for the 1/4 sec. cor. of secs. 15 and 22.

**Survey of the Subdivisional Lines,
T. 34 N., R. 8 E., Gila and Salt River Meridian, Arizona**

CHAINS	
	<p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 25 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T 34 N R 8 E S 15 1/4 ——— S 22</p> <p style="text-align: center;">2010</p> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p> <p>Set a T shaped steel fence post near the cor.</p>
47.90	Wash, 6 ft. wide, drains S. 20° E.
50.70	Wash, 6 ft. wide, drains S. 40° E.
66.15	Trail road, bears N. 35° E. and S. 35° W.
80.00	The cor. of secs. 15, 16, 21 and 22.
	<p>Terrain, rolling. Soil, sand. Timber, scattered juniper; undergrowth, Mormon Tea and various high desert grasses.</p> <hr/> <p>N. 0°02' W., bet. secs. 15 and 16.</p> <p>Over rolling terrain.</p>
40.00	<p>Point for the 1/4 sec. cor. of secs. 15 and 16.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 27 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T 34 N R 8 E 1/4 S 16 S 15</p> <p style="text-align: center;">2010</p> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p> <p>Raise a mound of stone, 4 ft. base, 2 1/2 ft. high, near the cor.</p>
80.00	Point for the cor. of secs. 9, 10, 15 and 16.

**Survey of the Subdivisional Lines,
T. 34 N., R. 8 E., Gila and Salt River Meridian, Arizona**

CHAINS	
	<p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, encircled with a collar of stone, with brass cap mkd.</p> <p style="text-align: center;">T 34 N R 8 E S 9 S 10 S 16 S 15</p> <p style="text-align: center;">2010</p> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p> <p>Set a T shaped steel fence post near the cor.</p> <p>Terrain, rolling. Soil, red clay shale and sandstone. Timber, scattered juniper; undergrowth, sage brush.</p> <hr/> <p>From the cor. of secs. 10, 11, 14 and 15.</p> <p>West, bet. secs. 10 and 15.</p> <p>Over rolling terrain.</p>
40.00	<p>Point for the 1/4 sec. cor. of secs. 10 and 15.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 25 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T 34 N R 8 E S 10 1/4 ——— S 15</p> <p style="text-align: center;">2010</p> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p> <p>Set a T shaped steel fence post near the cor.</p> <p>Cor. is located 30 lks. S. of a wash, 3 ft. wide, drains East.</p>
76.20	<p>Trail road, bears S. 55° E. and N. 55° W.</p>
80.00	<p>The cor. of secs. 9, 10, 15 and 16.</p>

**Survey of the Subdivisional Lines,
T. 34 N., R. 8 E., Gila and Salt River Meridian, Arizona**

CHAINS	
	<p>Terrain, rolling. Soil, red clay shale and sandstone. Timber, scattered juniper; undergrowth, sage brush.</p> <hr/> <p>N. 0°02' W., bet. secs. 9 and 10.</p> <p>Over rolling terrain.</p>
2.40	Trail road, bears S. 70° E. and N. 70° W.
32.10	Trail road, bears N. 15° E. and S. 15° W.
40.00	Point for the 1/4 sec. cor. of secs. 9 and 10.
	<p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T 34 N R 8 E 1/4 S 9 S 10 2010</p> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p> <p>Set a T shaped steel fence post near the cor.</p>
80.00	Point for the cor. of secs. 3, 4, 9 and 10.
	<p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T 34 N R 8 E S 4 S 3 S 9 S 10 2010</p> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p> <p>Set a T shaped steel fence post near the cor.</p>

**Survey of the Subdivisional Lines,
T. 34 N., R. 8 E., Gila and Salt River Meridian, Arizona**

CHAINS	
	<p>Terrain, rolling to level. Soil, sandy loam. Timber, scattered juniper; undergrowth, sage brush, cholla cactus and various high desert grasses.</p> <hr/> <p>From the cor. of secs. 2, 3, 10 and 11.</p> <p>West, bet. secs. 3 and 10</p> <p>Over rolling terrain.</p>
40.00	<p>Point for the 1/4 sec. cor. of secs. 3 and 10.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T 34 N R 8 E S 3 1/4 ——— S 10</p> <p style="text-align: center;">2010</p> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p> <p>Set a T shaped steel fence post near the cor.</p>
60.50	Trail road, bears S. 45° E. and N. 45° W.
60.90	Trail road, bears North and South.
65.45	Trail road, bears S. 40° E. and N. 40° W.
79.50	Trail road, bears S. 10° E. and N. 10° W.
80.00	<p>The cor. of secs. 3, 4, 9 and 10.</p> <p>Terrain, rolling to level. Soil, sandy loam. Timber, scattered juniper; undergrowth, sage brush, cholla cactus and various high desert grasses.</p> <hr/> <p>N. 0°02' W., bet. secs. 3 and 4.</p> <p>Over rolling terrain.</p>
40.00	Point for the 1/4 sec. cor. of secs. 3 and 4.

**Survey of the Subdivisional Lines,
T. 34 N., R. 8 E., Gila and Salt River Meridian, Arizona**

CHAINS	
	<p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 27 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T 34 N R 8 E 1/4 S 4 S 3</p> <p style="text-align: center;">2010</p> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p> <p>Set a T shaped steel fence post near the cor.</p> <p>Cor. is located 70 lks. W. of a wash, 6 ft. wide, drains N. 20° E.</p>
80.00	<p>The cor. of secs. 3, 4, 33 and 34, on the N. bdy. of the Tp., hereinbefore described.</p> <p>Terrain, rolling. Soil, sand and rocky. Timber, scattered juniper; undergrowth, sage brush, yucca cactus and various high desert grasses.</p> <hr/> <p>From the cor. of secs. 4, 5, 32 and 33, on the S. bdy. of the Tp., hereinbefore described.</p> <p>N. 0°03' W., bet. secs. 32 and 33.</p> <p>Over level to broken and rolling terrain.</p>
40.00	<p>Point for the 1/4 sec. cor. of secs. 32 and 33.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 22 ins. in the ground, encircled with a collar of stone, with brass cap mkd.</p> <p style="text-align: center;">T 34 N R 8 E 1/4 S 32 S 33</p> <p style="text-align: center;">2010</p> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p> <p>Set a T shaped steel fence post near the cor.</p>
80.00	<p>Point for the cor. of secs. 28, 29, 32 and 33.</p>

**Survey of the Subdivisional Lines,
T. 34 N., R. 8 E., Gila and Salt River Meridian, Arizona**

CHAINS	
	<p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 23 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T 34 N R 8 E S 29 S 28 S 32 S 33</p> <p style="text-align: center;">2010</p> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p> <p>Set a T shaped steel fence post near the cor.</p> <p>Terrain, rolling. Soil, sand and sandstone. No timber; sage brush, Mormon Tea and various high desert grasses.</p> <hr/> <p>From the cor. of secs. 27, 28, 33 and 34.</p> <p>West, bet. sec. 28 and 33.</p> <p>Over rolling terrain.</p>
40.00	<p>Point for the 1/4 sec. cor. of secs. 28 and 33.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 20 ins. in the ground, to bedrock, in a mound of stone, 3 ft. base, to top, with brass cap mkd.</p> <p style="text-align: center;">T 34 N R 8 E S 28 1/4 ——— S 33</p> <p style="text-align: center;">2010</p> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p> <p>Set a T shaped steel fence post near the cor.</p>
80.00	<p>The cor. of secs. 28, 29, 32 and 33.</p>

**Survey of the Subdivisional Lines,
T. 34 N., R. 8 E., Gila and Salt River Meridian, Arizona**

CHAINS	
	<p>Terrain, rolling. Soil, sand and sandstone. No timber; sage brush, Mormon Tea and various high desert grasses.</p> <hr/> <p>N. 0°03' W., bet. secs. 28 and 29.</p> <p>Over rolling terrain.</p>
35.60	Left bank of a wash, 14 ft. high, bears N. 30° E. and S. 40° W.
37.50	Wash, 12 ft. wide, 2 ft. deep, drains S. 40° W.
39.20	Right bank of a wash, 15 ft. high, bears N. 15° E. and S. 20° W.
40.00	Point for the 1/4 sec. cor. of secs. 28 and 29.
	<p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 15 ins. in the ground, to bedrock, in a mound of stone, 3 ft. base, to top, with brass cap mkd.</p> <p style="text-align: center;">T 34 N R 8 E 1/4 S 29 S 28</p> <p style="text-align: center;">2010</p> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p>
80.00	Point for the cor. of secs. 20, 21, 28 and 29.
	<p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 15 ins. in the ground, to bedrock, in a mound of stone, 3 1/2 ft. base, to top, with brass cap mkd.</p> <p style="text-align: center;">T 34 N R 8 E S 20 S 21 S 29 S 28</p> <p style="text-align: center;">2010</p> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p> <p>Set a T shaped steel fence post near the cor.</p>

Survey of the Subdivisional Lines,
T. 34 N., R. 8 E., Gila and Salt River Meridian, Arizona

CHAINS	
	<p>Terrain, rolling. Soil, sand and sandstone. No timber; sage brush, Mormon Tea and various high desert grasses.</p> <hr/> <p>From the cor. of secs. 21, 22, 27 and 28.</p> <p>West, bet. secs. 21 and 28.</p>
40.00	<p>Point for the 1/4 sec. cor. of secs. 21 and 28.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 25 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T 34 N R 8 E S 21 1/4 ——— S 28</p> <p style="text-align: center;">2010</p> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p> <p>Set a T shaped steel fence post near the cor.</p>
80.00	<p>The cor. of secs. 20, 21, 28 and 29.</p> <p>Terrain, rolling. Soil, sand and sandstone. Timber, scattered juniper; undergrowth, sage brush, Mormon Tea and various high desert grasses.</p> <hr/> <p>N. 0°03' W., bet. secs. 20 and 21.</p> <p>Over rolling terrain.</p>
40.00	<p>Point for the 1/4 sec. cor. of secs. 20 and 21.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 19 ins. in the ground, to bedrock, in a mound of stone, 3 ft. base, to top, with brass cap mkd.</p> <p style="text-align: center;">T 34 N R 8 E 1/4 S 20 S 21</p> <p style="text-align: center;">2010</p> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p>

**Survey of the Subdivisional Lines,
T. 34 N., R. 8 E., Gila and Salt River Meridian, Arizona**

CHAINS									
	Set a T shaped steel fence post near the cor.								
53.45	Trail road, bears S. 55° E. and N. 55° W.								
80.00	Point for the cor. of secs. 16, 17, 20 and 21.								
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 25 ins. in the ground, with brass cap mkd.								
	<table style="margin-left: auto; margin-right: auto;"> <tr> <td>T 34 N</td> <td>R 8 E</td> </tr> <tr> <td>S 17</td> <td>S 16</td> </tr> <tr> <td>S 20</td> <td>S 21</td> </tr> </table>	T 34 N	R 8 E	S 17	S 16	S 20	S 21		
T 34 N	R 8 E								
S 17	S 16								
S 20	S 21								
	2010								
	Deposit a magnet, in a white plastic case, at the base of the stainless steel post.								
	Set a T shaped steel fence post near the cor.								
	Terrain, rolling. Soil, sandy clay and sandstone. Timber, scattered juniper; undergrowth, sage brush, Mormon Tea and various high desert grasses.								

	From the cor. of secs. 15, 16, 21 and 22.								
	West, bet. secs. 16 and 21.								
40.00	Point for the 1/4 sec. cor. of secs. 16 and 21.								
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 21 ins. in the ground, encircled with a collar of stone, with brass cap mkd.								
	<table style="margin-left: auto; margin-right: auto;"> <tr> <td>T 34 N</td> <td>R 8 E</td> </tr> <tr> <td></td> <td>S 16</td> </tr> <tr> <td>1/4</td> <td>_____</td> </tr> <tr> <td></td> <td>S 21</td> </tr> </table>	T 34 N	R 8 E		S 16	1/4	_____		S 21
T 34 N	R 8 E								
	S 16								
1/4	_____								
	S 21								
	2010								
	Deposit a magnet, in a white plastic case, at the base of the stainless steel post.								
	Set a T shaped steel fence post near the cor.								
80.00	The cor. of secs. 16, 17, 20 and 21.								

**Survey of the Subdivisional Lines,
T. 34 N., R. 8 E., Gila and Salt River Meridian, Arizona**

CHAINS	
	<p>Terrain, rolling. Soil, sandy clay and sandstone. Timber, scattered juniper; undergrowth, sage brush, Mormon Tea and various high desert grasses.</p> <hr/> <p>N. 0°03' W., bet. secs. 16 and 17.</p> <p>Over rolling terrain.</p>
36.90	S. rim of a mesa, bears S. 45° E. and S. 70° W.
40.00	<p>Point for the 1/4 sec. cor. of secs. 16 and 17.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 10 ins. in the ground, to bedrock, in a mound of stone, 5 ft. base, to top, with brass cap mkd.</p> <div style="text-align: center;"> <p>T 34 N R 8 E 1/4 S 17 S 16</p> <p>2010</p> </div> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p> <p>Set a T shaped steel fence post, in a supporting mound of stone, near the cor.</p>
54.30	Trail road, bears N. 45° E. and S. 45° W.
75.30	N. rim of a mesa, bears N. 50° E. and N. 80° W.
80.00	<p>Point for the cor. of secs. 8, 9, 16 and 17.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 15 ins. in the ground, to bedrock, in a mound of stone, 4 ft. base, to top, with brass cap mkd.</p> <div style="text-align: center;"> <p>T 34 N R 8 E S 8 S 9 S 17 S 16</p> <p>2010</p> </div> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p>

**Survey of the Subdivisional Lines,
T. 34 N., R. 8 E., Gila and Salt River Meridian, Arizona**

CHAINS	
	<p>Terrain, rolling. Soil, sand and sandstone. Timber, scattered juniper and piñon; undergrowth, sage brush, Mormon Tea and various high desert grasses.</p> <hr/> <p>From the cor. of secs. 9, 10, 15 and 16.</p> <p>West, bet. secs. 9 and 16.</p> <p>Over rolling terrain.</p>
40.00	<p>Point for the 1/4 sec. cor. of secs. 9 and 16.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 25 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T 34 N R 8 E S 9 1/4 ——— S 16</p> <p style="text-align: center;">2010</p> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p> <p>Set a T shaped steel fence post near the cor.</p>
80.00	<p>The cor. of secs. 8, 9, 16 and 17.</p> <p>Terrain, rolling. Soil, sandy clay and sandstone. Timber, scattered juniper; undergrowth, sage brush, Mormon Tea and various high desert grasses.</p> <hr/> <p>N. 0°03' W., bet. secs. 8 and 9.</p> <p>Over rolling terrain.</p>
40.00	<p>Point for the 1/4 sec. cor. of secs. 8 and 9.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T 34 N R 8 E 1/4 S 8 S 9</p> <p style="text-align: center;">2010</p>

**Survey of the Subdivisional Lines,
T. 34 N., R. 8 E., Gila and Salt River Meridian, Arizona**

CHAINS									
	<p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p> <p>Set a T shaped steel fence post near the cor.</p>								
41.30	Trail road, bears N. 20° E. and S. 20° W.								
80.00	<p>Point for the cor. of secs. 4, 5, 8 and 9.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center;"> <table style="margin: auto;"> <tr> <td>T 34 N</td> <td>R 8 E</td> </tr> <tr> <td style="border-right: 1px solid black;">S 5</td> <td>S 4</td> </tr> <tr> <td style="border-right: 1px solid black;">S 8</td> <td>S 9</td> </tr> </table> <p>2010</p> </div> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p> <p>Set a T shaped steel fence post near the cor.</p> <p>Terrain, rolling. Soil, sandy clay and sandstone. Timber, scattered juniper; undergrowth, sage brush, Mormon Tea and various high desert grasses.</p> <hr/> <p>From the cor. of secs. 3, 4, 9 and 10.</p> <p>West, bet. secs. 4 and 9.</p> <p>Over rolling terrain.</p>	T 34 N	R 8 E	S 5	S 4	S 8	S 9		
T 34 N	R 8 E								
S 5	S 4								
S 8	S 9								
40.00	<p>Point for the 1/4 sec. cor. of secs. 4 and 9.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 14 ins. in the ground, to bedrock, in a mound of stone, 4 ft. base, to top, with brass cap mkd.</p> <div style="text-align: center;"> <table style="margin: auto;"> <tr> <td>T 34 N</td> <td>R 8 E</td> </tr> <tr> <td></td> <td>S 4</td> </tr> <tr> <td>1/4</td> <td style="border-top: 1px solid black;">———</td> </tr> <tr> <td></td> <td>S 9</td> </tr> </table> <p>2010</p> </div> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p>	T 34 N	R 8 E		S 4	1/4	———		S 9
T 34 N	R 8 E								
	S 4								
1/4	———								
	S 9								

**Survey of the Subdivisional Lines,
T. 34 N., R. 8 E., Gila and Salt River Meridian, Arizona**

CHAINS	
71.25	Trail road, bears S. 45° E. and N. 45° W.
80.00	The cor. of secs. 4, 5, 8 and 9. Terrain, rolling. Soil, sand and sandstone. Timber, scattered juniper and piñon; undergrowth, sage brush, Mormon Tea and various high desert grasses.
	N. 0°03' W., bet. secs. 4 and 5. Over rolling terrain.
13.60	Trail road, bears S. 45° E. and N. 45° W.
40.00	Point for the 1/4 sec. cor. of secs. 4 and 5. Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 20 ins. in the ground, to bedrock, in a mound of stone, 4 ft. base, to top, with brass cap mkd.
	T 34 N R 8 E 1/4 S 5 S 4 2010
	Deposit a magnet, in a white plastic case, at the base of the stainless steel post. Set a T shaped steel fence post near the cor.
56.45	B. I. A. Route 6110, a graded road, 40 ft. wide, bears East and West.
58.10	Utility line, 2 strand, bears East and West.
62.65	Trail road, bears S. 60° E. and N. 60° W.
80.00	The cor. of secs. 4, 5, 32 and 33, on the N. bdy. of the Tp., hereinbefore described. Terrain, rolling. Soil, sand and rocky. Timber, scattered juniper; undergrowth, sage brush, Mormon Tea, yucca cactus and various high desert grasses.
	From the cor. of secs. 5, 6, 31 and 32, on the S. bdy. of the Tp., hereinbefore described. N. 0°03' W., bet. secs. 31 and 32.

**Survey of the Subdivisional Lines,
T. 34 N., R. 8 E., Gila and Salt River Meridian, Arizona**

CHAINS	
	Over rolling terrain.
2.00	Wash, 45 ft. wide, 3 ft. deep, drains N. 70° W.
40.00	Point for the 1/4 sec. cor. of secs. 31 and 32.
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 25 ins. in the ground, with brass cap mkd.
	T 34 N R 8 E 1/4 S 31 S 32 2010
	Deposit a magnet, in a white plastic case, at the base of the stainless steel post.
	Set a T shaped steel fence post near the cor.
40.60	Wash, 3 ft. wide, 3 ft. deep, drains S. 65° W.
73.80	Wash, 20 ft. wide, 4 ft. deep, drains S. 80° E.
80.00	Point for the cor. of secs. 29, 30, 31 and 32.
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 25 ins. in the ground, with brass cap mkd.
	T 34 N R 8 E S 30 S 29 S 31 S 32 2010
	Deposit a magnet, in a white plastic case, at the base of the stainless steel post.
	Set a T shaped steel fence post near the cor.
	Terrain, rolling. Soil, sandy clay and sandstone. No timber; scattered sage brush, Mormon Tea and various high desert grasses.
	From the cor. of secs. 28, 29, 32 and 33.
	West, bet. secs. 29 and 32.
	Over rolling terrain.
40.00	Point for the 1/4 sec. cor. of secs. 29 and 32.

**Survey of the Subdivisional Lines,
T. 34 N., R. 8 E., Gila and Salt River Meridian, Arizona**

CHAINS	
	<p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T 34 N R 8 E S 29 1/4 ——— S 32</p> <p style="text-align: center;">2010</p> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p> <p>Set a T shaped steel fence post near the cor.</p>
41.20	Wash, 2 ft. wide, 1 ft. deep, drains S. 55° W.
80.00	The cor. of secs. 29, 30, 31 and 32.
	<p>Terrain, rolling. Soil, sandy clay and sandstone. No timber; scattered sage brush, Mormon Tea and various high desert grasses.</p> <hr/> <p>West, bet. secs. 30 and 31.</p> <p>Over rolling terrain.</p>
2.20	Wash, 3 ft. wide, 3 ft. deep, drains South.
40.00	Point for the 1/4 sec. cor. of secs. 30 and 31.
	<p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 14 ins. in the ground, to bedrock, in a mound of stone, 3 1/2 ft. base, to top, with brass cap mkd.</p> <p style="text-align: center;">T 34 N R 8 E S 30 1/4 ——— S 31</p> <p style="text-align: center;">2010</p> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p>
68.60	Wash, 10 ft. wide, drains S. 30° W.
71.70	Trail road, bears S. 10° E. and N. 10° W.

**Survey of the Subdivisional Lines,
T. 34 N., R. 8 E., Gila and Salt River Meridian, Arizona**

CHAINS	
79.35	<p>The cor. of secs. 25, 30, 31 and 36, on the W. bdy. of the Tp., hereinbefore described.</p> <p>Terrain, rolling. Soil, sandy clay and sandstone. No timber; scattered sage brush, Mormon Tea and various high desert grasses.</p> <hr/> <p>From the cor. of secs. 29, 30, 31 and 32.</p> <p>N. 0°03' W., bet. secs. 29 and 30.</p> <p>Over rolling terrain.</p>
40.00	<p>Point for the 1/4 sec. cor. of secs. 29 and 30.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 19 ins. in the ground, to bedrock, in a mound of stone, 5 ft. base, to top, with brass cap mkd.</p> <p style="text-align: center;">T 34 N R 8 E 1/4 S 30 S 29</p> <p style="text-align: center;">2010</p> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p>
43.70	<p>Wash, halfway down a 10 ft. waterfall, 8 ft. wide, drains N. 60° E.</p>
80.00	<p>Point for the cor. of secs. 19, 20, 29 and 30.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 9 ins. in the ground, to bedrock, in a mound of stone, 5 ft. base, to top, with brass cap mkd.</p> <p style="text-align: center;">T 34 N R 8 E S 19 S 20 S 30 S 29</p> <p style="text-align: center;">2010</p> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p> <p>Cor. is located 11 lks. W. of the top of the W. bank of a canyon wall, 70 ft. high, bears N. 10° E. and S. 15° E.</p>

**Survey of the Subdivisional Lines,
T. 34 N., R. 8 E., Gila and Salt River Meridian, Arizona**

CHAINS	
	<p>Terrain, rolling to broken. Soil, sandy clay and sandstone. No timber; scattered sage brush, Mormon Tea and various high desert grasses.</p> <hr/> <p>From the cor. of secs. 20, 21, 28 and 29.</p> <p>West, bet. secs. 20 and 29.</p> <p>Over rolling terrain.</p>
36.80	Wash, 6 ft. wide, 1/2 ft. deep, drains S. 30° W.
40.00	Point for the 1/4 sec. cor. of secs. 20 and 29.
	<p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T 34 N R 8 E S 20 1/4 ——— S 29</p> <p style="text-align: center;">2010</p> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p> <p>Set a T shaped steel fence post near the cor.</p>
78.50	Wash, 45 ft. wide, 3 ft. deep, drains S. 5° E.
80.00	The cor. of secs. 19, 20, 29 and 30.
	<p>Terrain, rolling to broken. Soil, sandy clay and sandstone. No timber; scattered sage brush, Mormon Tea and various high desert grasses.</p> <hr/> <p>West, bet. secs. 19 and 30.</p> <p>Over broken and rolling terrain.</p>
40.00	Point for the 1/4 sec. cor. of secs. 19 and 30.
	<p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with brass cap mkd.</p>

**Survey of the Subdivisional Lines,
T. 34 N., R. 8 E., Gila and Salt River Meridian, Arizona**

CHAINS	
	T 34 N R 8 E S 19 1/4 ——— S 30 2010
	Deposit a magnet, in a white plastic case, at the base of the stainless steel post. Raise a mound of stone, 4 ft. base, 2 1/2 ft. high, S. of cor. Cor. is located 60 lks. N. of the intersection of two washes.
50.80	Wash, 20 ft. wide, drains S. 30° E.
64.10	Trail road, bears North and South.
79.25	The cor. of secs. 19, 24, 25 and 30, on the W. bdy. of the Tp., hereinbefore described. Terrain, rolling. Soil, sandy clay and sandstone. No timber; scattered sage brush, Mormon Tea and various high desert grasses.
	<hr/> From the cor. of secs. 19, 20, 29 and 30. N. 0°03' W., bet. secs. 19 and 20. Over rolling terrain.
3.50	Mountain drainage, 10 ft. wide, 2 ft. deep, drains S. 35° E.
40.00	Point for the 1/4 sec. cor. of secs. 19 and 20. Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 25 ins. in the ground, with brass cap mkd.
	T 34 N R 8 E 1/4 S 19 S 20 2010
	Deposit a magnet, in a white plastic case, at the base of the stainless steel post. Set a T shaped steel fence post near the cor.
80.00	Point for the cor. of secs. 17, 18, 19 and 20.

**Survey of the Subdivisional Lines,
T. 34 N., R. 8 E., Gila and Salt River Meridian, Arizona**

CHAINS	
	<p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T 34 N R 8 E S 18 S 17 S 19 S 20</p> <p style="text-align: center;">2010</p> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p> <p>Set a T shaped steel fence post near the cor.</p> <p>Terrain, rolling to broken. Soil, sand and rocky. No timber; scattered sage brush, Mormon Tea and various high desert grasses.</p> <hr/> <p>From the cor. of secs. 16, 17, 20 and 21.</p> <p>West, bet. secs. 17 and 20.</p> <p>Over rolling terrain.</p>
40.00	<p>Point for the 1/4 sec. cor. of secs. 17 and 20.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 23 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T 34 N R 8 E S 17 1/4 ——— S 20</p> <p style="text-align: center;">2010</p> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p> <p>Set a T shaped steel fence post near the cor.</p>
45.00	<p>Trail road, bears S. 15° E. and N. 15° W.</p>
48.10	<p>Wash, 12 ft. wide, 2 ft. deep, drains S. 10° W.</p>
80.00	<p>The cor. of secs. 17, 18, 19 and 20.</p>

**Survey of the Subdivisional Lines,
T. 34 N., R. 8 E., Gila and Salt River Meridian, Arizona**

CHAINS	
	<p>Terrain, rolling to broken. Soil, sand and rocky. No timber; scattered sage brush, Mormon Tea and various high desert grasses.</p> <hr/>
	<p>West, bet. secs. 18 and 19.</p> <p>Over broken terrain.</p>
40.00	<p>Point for the 1/4 sec. cor. of secs. 18 and 19.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 20 ins. in the ground, to bedrock, with brass cap mkd.</p> <p style="text-align: center;">T 34 N R 8 E S 18 1/4 ——— S 19</p> <p style="text-align: center;">2010</p> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p>
76.25	<p>Trail road, bears North and South.</p>
79.16	<p>The cor. of secs. 13, 18, 19 and 24, on the W. bdy. of the Tp., hereinbefore described.</p> <p>Terrain, rolling to broken. Soil, sand and rocky. No timber; scattered sage brush, Mormon Tea and various high desert grasses.</p> <hr/>
	<p>From the cor. of secs. 17, 18, 19 and 20.</p> <p>N. 0°03' W., bet. secs. 17 and 18.</p> <p>Over rolling terrain.</p>
34.20	<p>Wash, 6 ft. wide, drains S. 35° E.</p>
40.00	<p>Point for the 1/4 sec. cor. of secs. 17 and 18.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 23 ins. in the ground, with brass cap mkd.</p>

**Survey of the Subdivisional Lines,
T. 34 N., R. 8 E., Gila and Salt River Meridian, Arizona**

CHAINS	
	T 34 N R 8 E 1/4 S 18 S 17 2010
	Deposit a magnet, in a white plastic case, at the base of the stainless steel post.
42.90	Trail road, bears S. 85° E. and N. 85° W.
80.00	Point for the cor. of secs. 7, 8, 17 and 18.
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., flush with the surface of the ground, encircled with an embedded collar of stone, with brass cap mkd.
	T 34 N R 8 E S 7 S 8 ———— S 18 S 17 2010
	Deposit a magnet, in a white plastic case, at the base of the stainless steel post.
	Set a T shaped steel fence post near the cor.
	Terrain, rolling to broken.
	Soil, sandy clay and rocky.
	Timber, juniper; undergrowth, scattered sage brush, Mormon Tea and various high desert grasses.
	<hr/>
	From the cor. of secs. 8, 9, 16 and 17.
	West, bet. secs. 8 and 17.
	Over rolling to broken terrain.
40.00	Point for the 1/4 sec. cor. of secs. 8 and 17.
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., flush with the surface of the ground, with brass cap mkd.
	T 34 N R 8 E S 8 1/4 ———— S 17 2010

**Survey of the Subdivisional Lines,
T. 34 N., R. 8 E., Gila and Salt River Meridian, Arizona**

CHAINS	
80.00	<p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p> <p>Set a T shaped steel fence post near the cor.</p> <p>Cor. is located near the northerly end of Tolchaco Gap.</p> <p>The cor. of secs. 7, 8, 17 and 18.</p> <p>Terrain, rolling to broken. Soil, sandy clay and rocky. Timber, juniper; undergrowth, scattered sage brush, Mormon Tea and various high desert grasses.</p> <hr/>
40.00	<p>West, bet. secs. 7 and 18.</p> <p>Over rolling to broken terrain.</p> <p>Point for the 1/4 sec. cor. of secs. 7 and 18.</p> <p>Set a brass tablet, 3 1/2 ins. diam., attached to a stainless steel rod, 18 ins. long, 9/16 in. diam., cemented in a drill hole, 12 ins. deep, in solid rock, with top mkd.</p> <div style="text-align: center;"> <p>T 34 N R 8 E</p> <p>S 7</p> <p>1/4 ———</p> <p>S 18</p> <p>2010</p> </div>
66.40	<p>Deposit fragments of a magnet, in the drill hole, beneath the stainless steel rod.</p> <p>Raise a mound of stone, 3 ft. base, 2 ft. high, N. of cor.</p> <p>Cor. is located on level ground on the top of Bodaway Mesa.</p> <p>Trail road, bears S. 75° E. and N. 75° W.</p>
79.07	<p>The cor. of secs. 7, 12, 13 and 18, on the W. bdy. of the Tp., hereinbefore described.</p> <p>Terrain, rolling to broken. Soil, sandy clay and rocky. Timber, juniper; undergrowth, scattered sage brush, Mormon Tea and various high desert grasses.</p> <hr/> <p>From the cor. of secs. 7, 8, 17 and 18.</p> <p>N. 0°03' W., bet. secs. 7 and 8.</p>

**Survey of the Subdivisional Lines,
T. 34 N., R. 8 E., Gila and Salt River Meridian, Arizona**

CHAINS	
	Over rolling terrain.
8.50	Wash, 4 ft. wide, drains S. 60° E.
22.40	Wash, 6 ft. wide, drains S. 80° E.
33.00	Trail road, bears East and West.
34.45	Trail road, bears N. 30° E. and S. 30° W.
40.00	Point for the 1/4 sec. cor. of secs. 7 and 8.
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 25 ins. in the ground, with brass cap mkd.
	T 34 N R 8 E 1/4 S 7 S 8 2010
	Deposit a magnet, in a white plastic case, at the base of the stainless steel post.
	Set a T shaped steel fence post near the cor.
80.00	Point for the cor. of secs. 5, 6, 7 and 8.
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with brass cap mkd.
	T 34 N R 8 E S 6 S 5 S 7 S 8 2010
	Deposit a magnet, in a white plastic case, at the base of the stainless steel post.
	Set a T shaped steel fence post near the cor.
	Terrain, rolling. Soil, sandy loam. No timber; various high desert grasses.
	<hr/>
	From the cor. of secs. 4, 5, 8 and 9.
	West, bet. secs. 5 and 8.
	Over rolling terrain.

**Survey of the Subdivisional Lines,
T. 34 N., R. 8 E., Gila and Salt River Meridian, Arizona**

CHAINS	
40.00	<p>Point for the 1/4 sec. cor. of secs. 5 and 8.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 25 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T 34 N R 8 E S 5 1/4 ——— S 8</p> <p style="text-align: center;">2010</p> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p> <p>Set a T shaped steel fence post near the cor.</p>
65.50	Trail road, bears N. 15° E. and S. 15° W.
66.65	Trail road, bears S. 30° E. and N. 30° W.
80.00	<p>The cor. of secs. 5, 6, 7 and 8.</p> <p>Terrain, rolling. Soil, sandy loam. No timber; various high desert grasses.</p> <hr/> <p>West, bet. secs. 6 and 7.</p> <p>Over rolling terrain.</p>
3.00	Trail road, bears N. 25° E. and S. 25° W.
20.95	Trail road, bears N. 55° E. and S. 55° W.
21.65	Trail road, bears N. 20° E. and S. 20° W.
29.15	Trail road, bears North and South.
39.00	Trail road, bears North and South.
40.00	<p>Point for the 1/4 sec. cor. of secs. 6 and 7.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T 34 N R 8 E S 6 1/4 ——— S 7</p> <p style="text-align: center;">2010</p>

**Survey of the Subdivisional Lines,
T. 34 N., R. 8 E., Gila and Salt River Meridian, Arizona**

CHAINS	
	Deposit a magnet, in a white plastic case, at the base of the stainless steel post.
	Set a T shaped steel fence post near the cor.
59.65	Trail road, bears N. 10° E. and S. 10° W.
72.90	Wash, 4 ft. wide, drains N. 20° W.
78.98	The cor. of secs. 1, 6, 7 and 12, on the W. bdy. of the Tp., hereinbefore described.
	Terrain, rolling. Soil, sandy loam. No timber; various high desert grasses.
	From the cor. of secs. 5, 6, 7 and 8.
	N. 0°03' W., bet. secs. 5 and 6.
	Over rolling terrain.
19.35	Trail road, bears S. 50° E. and N. 50° W.
26.65	Trail road, bears N. 40° E. and S. 40° W.
40.00	Point for the 1/4 sec. cor. of secs. 5 and 6.
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.
	T 34 N R 8 E 1/4 S 6 S 5 2010
	Deposit a magnet, in a white plastic case, at the base of the stainless steel post.
43.45	Trail road, bears N. 80° E. and S. 80° W.
47.50	Trail road, bears East and West.
54.10	B. I. A. Route 6110, a graded road, 25 ft. wide, bears East and West.
80.00	The cor. of secs. 5, 6, 31 and 32, on the N. bdy. of the Tp., hereinbefore described.

**Survey of the Subdivisional Lines,
T. 34 N., R. 8 E., Gila and Salt River Meridian, Arizona**

CHAINS

Terrain, rolling.
Soil, sandy loam.
No timber; various high desert grasses.

GENERAL DESCRIPTION

This township is located approximately 1 1/4 miles northwesterly, along U. S. Highway 89, from the community of The Gap, and approximately 3/4 of a mile southeasterly, along U. S. Highway 89, from the community of Cedar Ridge, on the Navajo Indian Reservation. The terrain is rolling and broken, with mesas and ravines throughout. Echo Cliffs runs through sections 1, 12, 13 and 24, with Hamblin Wash draining southeasterly, in the same sections, at the base of Echo Cliffs.

The elevation W. of Echo Cliffs varies from 5,400 ft. along Hamblin Wash, to 6,300 ft. on top of Bodaway Mesa and varies from 5,700 ft. to 6,300 ft. E. of Echo Cliffs. The soil varies from blow sand and sandstone outcrops E. of Echo Cliffs to clayish sand, sandstone and limestone, W. of Echo Cliffs.

U. S. Highway 89 runs southeasterly and northwesterly thru the northeasterly portion of the township, somewhat parallel, and W. of Echo Cliffs. Access to the top side of Echo Cliffs is by way of Navajo Route 20, which intersects U. S. Highway 89 at The Gap. B. I. A. Route 6130 traverses through the southerly portion of the township and B. I. A. Route 6110 traverses through the northerly portion. There are multiple dirt roads crisscrossing the township.

The mean magnetic declination of 11 1/4° E. was derived from the National Geophysical Data Center's magnetic declination calculator, GEOMAG v6.0, utilizing the International Geomagnetic Reference Field Model for years 2005 through 2010, for the dates of the survey.

CERTIFICATE OF SURVEY

I, Craig S. Dukart, Cadastral Surveyor, HEREBY CERTIFY upon honor, that in pursuance of special instructions bearing date of the 10th day of February, 2010, I have dependently resurveyed the Second Guide Meridian East (east boundary) and the south boundary and surveyed the west and north boundaries and the subdivisional lines, T. 34 N., R. 8 E., of the Gila and Salt River Meridian, in the State of Arizona, which are represented in the foregoing field notes as having been executed by me and under my direction. Said survey has been made in strict conformity with said special instructions, the Manual of Instructions for the Survey of the Public Lands of the United States, 1973, and in specific manner described in the foregoing field notes.

12/06/10

(Date)

Craig S. Dukart

(Cadastral Surveyor)

CERTIFICATE OF APPROVAL

BUREAU OF LAND MANAGEMENT
Phoenix, Arizona

The foregoing field notes of the dependent resurvey of the Second Guide Meridian East (east boundary) and the south boundary and the survey of the west and north boundaries and the subdivisional lines, T. 34 N., R. 8 E., of the Gila and Salt River Meridian, in the State of Arizona, executed by Craig S. Dukart, Cadastral Surveyor, having been critically examined and found correct, are hereby approved.

2/23/2011

(Date)

Stephen K. Hamner

(Chief Cadastral Surveyor of Arizona)

~~CERTIFICATE OF TRANSCRIPT~~

~~I CERTIFY That the foregoing transcript of the field notes of the above described surveys in T. 34 N., R. 8 E., of the Gila and Salt River Meridian, in the State of Arizona, is a true copy of the original field notes.~~

~~(Date)~~

~~(Chief Cadastral Surveyor of Arizona)~~