

ORIGINAL

**UNITED STATES  
DEPARTMENT OF THE INTERIOR  
BUREAU OF LAND MANAGEMENT**

FIELD NOTES

OF THE

DEPENDENT RESURVEY OF A PORTION OF THE NORTH BOUNDARY,  
A PORTION OF THE SUBDIVISIONAL LINES, A PORTION OF THE SUBDIVISION OF  
SECTION 8 AND PORTIONS OF A METES-AND-BOUNDS SURVEY OF THE SOUTH BOUNDARY  
OF THE SALT RIVER PIMA-MARICOPA INDIAN COMMUNITY  
AND THE SUBDIVISION OF SECTION 3,  
**TOWNSHIP 1 NORTH, RANGE 5 EAST,**  
OF THE GILA AND SALT RIVER MERIDIAN,  
IN THE STATE OF ARIZONA.

**EXECUTED BY**

**Gordon R. Bubel, Cadastral Surveyor**

Under Special Instructions dated February 3, 2010, approved February 3, 2010, which provided for the surveys included under Group No. 1076, and assignment instructions dated February 3, 2010.

**Survey commenced February 10, 2010**

**Survey completed February 11, 2011**

**INDEX DIAGRAM**

**TOWNSHIP 1 NORTH                      RANGE 5 EAST  
GILA AND SALT RIVER MERIDIAN, ARIZONA**

			5	4	
<b>6</b>	<b>5</b> 14	<b>4</b> 10 11	<b>3</b>	<b>2</b>	<b>1</b>
<b>7</b> 18 16	20 <b>8</b> 8 15	<b>9</b>	<b>10</b>	<b>11</b>	<b>12</b>
<b>18</b>	<b>17</b>	<b>16</b>	<b>15</b>	<b>14</b>	<b>13</b>
<b>19</b>	<b>20</b>	<b>21</b>	<b>22</b>	<b>23</b>	<b>24</b>
<b>30</b>	<b>29</b>	<b>28</b>	<b>27</b>	<b>26</b>	<b>25</b>
<b>31</b>	<b>32</b>	<b>33</b>	<b>34</b>	<b>35</b>	<b>36</b>

Subdivision of Section 8 .....Pages 21-29  
 Subdivision of Section 3 .....Pages 29-34  
 Metes-and-Bounds Survey of S. bdy. of SRPMIC .....Pages 35-44

## T. 1 N., R. 5 E., Gila and Salt River Meridian, Arizona

## CHAINS

The following field notes describe the dependent resurvey of a portion of the north boundary, a portion of the subdivisional lines, a portion of the subdivision of section 8 and portions of a metes-and-bounds survey of the south boundary of the Salt River Pima-Maricopa Indian Community and the subdivision of section 3, Township 1 North, Range 5 East, Gila and Salt River Meridian, Arizona.

The history of surveys pertaining to this resurvey and survey is as follows: Wilfred F. Ingalls, surveyed the north and west boundaries and the subdivisional lines in 1868. In 1888 L.D. Chillson, resurveyed a portion of the north and west boundaries, a portion of the subdivisional lines, north of the right bank of the Salt River, and established the meander line of the right bank of the Salt River through the township. In 1910, Robert A. Farmer resurveyed the north boundary, a portion of the west boundary, a portion of the subdivisional lines, north of the right bank of the Salt River, subdivided the sections north of the right bank of the Salt River and established a meander line on the right bank of the Salt River independent, of the 1888 survey. In 1962, Boyd S. Owens and Paul G. Bauer, resurveyed a portion of the north and west boundaries, a portion of the subdivisional lines, retraced a portion of the subdivisional lines and subdivided sections 4, 7 and 8. An Executive Order, dated June 14, 1879, created the Salt River Indian Reservation within the township. It states in part, "Up the middle of the Salt River, both the Chillson 1888 survey and the Farmer 1910 recognize the lands north of their meander lines as being within the Salt River Indian Reservation, neither survey located the south boundary of the Salt River Indian Reservation. In 1972, Owens and Bauer surveyed the south boundary of the Salt River Indian Reservation, in compliance with a 1969 decision by the Secretary of the Interior and a 1971 determination by the Assistant Secretary, Public Land Management: *The south boundary of the Salt River Indian Reservation was in the south channel of the Salt River, as it existed in the 1965-1966 floods.* The 1972 survey declared the middle of the Salt River as ambulatory, subject to the natural movements of a river. Public Law 95-399, enacted on September 30, 1978, set the South Boundary of the Salt River Indian Reservation, (now referred to as the Salt River Pima-Maricopa Indian Reservation), *as fixed and not ambulatory*, the 1978 law also included provisions that accepted the 1972 survey in part as the south boundary of the Salt River Indian Reservation, where the 1972 survey infringed upon prior rights it was rejected.

The survey was executed in accordance with the specifications as set forth in the Manual of Surveying Instructions for the Survey of the Public Lands of the United States, 2009, and the Special Instructions dated February 3, 2010, for Group Number 1076, Arizona.

## T. 1 N., R. 5 E., Gila and Salt River Meridian, Arizona

## CHAINS

The true meridian direction and length of all lines were determined by real time kinematic global positioning system observations using Trimble Navigation 5700 model receivers.

Preliminary to the resurvey, the lines of the prior surveys were retraced and search was made for all corners and other calls of record. Identified corners were remonumented in their original positions. Lost corners were reestablished and remonumented at proportionate positions based on the official record. The retracement data were thoroughly verified and only the true line field notes are given herein.

Geodetic control was derived from Global Positioning System (GPS) static observations post processed by National Geodetic Survey, Online Positioning User Service (OPUS), utilizing Continuously Operating Reference Stations (CORS) AZTP TEMPE CORS ARP, AZSC CNTR FOR ARTS CORS ARP and COSA SCOTTSDALE CORS ARP.

The NAD 83 (CORS96) (EPOCH: 2002), geographic position of the center 1/4 section corner of section 3, is as follows:

Latitude: 33°27'31.37" N.                      Longitude: 111°49'51.68" W.

The mean magnetic declination is 11° E.

---

**Dependent Resurvey of a Portion of the North Boundary,  
T. 1 N., R. 5 E., Gila and Salt River Meridian, Arizona**

---

Restoring the resurvey executed by Robert A. Farmer,  
in 1910-1911 and Boyd S. Owens and Paul G. Bauer in 1962.

---

Beginning at the cor. of secs. 34 and 35, T. 2 N., R. 5 E., monumented with a brass disk, 3 ins. diam., set in concrete flush with the surface of ground, with brass disk mkd. MARICOPA COUNTY D.O.T. RLS. This is accepted as the best available evidence of the 1910 cor.

N. 89°51' W., on the N. bdy. of sec. 2.

1.43 The cor. of secs. 2 and 3 only, T. 2 N., R. 5 E., on the N. bdy. of the Tp., monumented with an unmarked brass disk, 3 ins. diam., seated in concrete, 4 ins. below the surface, set inside a survey well, 10 ins. diam. This is accepted as the best available evidence of the 1910 cor.

There is no remaining evidence of the accessories recorded in the 1910 and 1972 resurveys.

Dependent Resurvey of a Portion of the North Boundary,  
T. 1 N., R. 5 E., Gila and Salt River Meridian, Arizona

## CHAINS

Cor. is located on the S. edge of pavement of McDowell Rd. bearing E., and on the extension of the center of pavement of Mesa Dr. bearing S.

---


S. 88°18' W., beginning new measurement, on the N. bdy. of sec. 3.

Across overflow lands.

- 8.14 Point for the meander cor. of sec. 34, T. 2 N., R. 5 E., determined at proportionate dist., on the left bank of the Salt River in 1910. There is no remaining evidence of the orig. cor., not monumented.
- 18.57 The E. 1/16 sec. cor. of sec. 34, T. 2 N., R. 5 E., monumented with a rebar, 18 ins. long, 1/2 in. diam., set 18 ins. in the ground, with attached 1 in. diam., plastic cap, stamped GETTING RLS 27239. This is accepted as a careful and faithful perpetuation of the 1910 cor.
- 19.24 Angle Point No. 53, on the S. bdy. of the Salt River Indian Reservation, now known as the Salt River Pima Maricopa Indian Community and hereinafter cited as SRPMIC. Monumented with a rebar, 18 ins. in diam., firmly set, 24 ins. in the ground, with a plastic cap, 1 in. diam., stamped GETTINGS LS 27239. This is accepted as a careful and faithful perpetuation of the orig. cor.

At the corner point

Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 27 ins. in the ground, with brass cap mkd.



Deposit a magnet, in a white plastic case, at the base of the stainless steel post.

Deposit the rebar inside the stainless steel post.

---

S. 88°18' W., beginning new measurement, within the SRPMIC, across closed landfill.

Dependent Resurvey of a Portion of the North Boundary,  
T. 1 N., R. 5 E., Gila and Salt River Meridian, Arizona

CHAINS	
0.60	Point for the meander cor. of sec. 34, T. 2 N., R. 5 E., determined at proportionate dist., established on the E. shore of an island within the Salt River in the 1910 resurvey. There is no remaining evidence of the orig. cor., not monumented.
1.03	<p>The E. 1/16 sec. cor. of sec. 3, monumented with an iron post, 2 ins. diam., firmly set, in concrete, projecting 12 in. above ground, with a blank, 2 1/2 ins. diam., brass cap. Established by Mason L. Womble, Arizona R.L.S. No. 1757, as per an unrecorded <i>Result of Survey plat</i>, obtained from the SRPMIC Survey Dept. This is accepted as a careful and faithful reestablishment of the original corner.</p> <p>Mark the existing brass cap to read:</p> <div style="text-align: center;"> <p>T 2 N R 5 E</p> <hr style="width: 10%; margin: 0 auto;"/> <p>E 1/16 S3</p> <p>T 1 N R 5 E</p> <p>2010</p> <hr style="width: 20%; margin: 10px auto 0 auto;"/> </div> <p>S. 88°18' W., beginning new measurement.</p> <p>Continuing within the SRPMIC, across closed landfill.</p>
18.31	Point for the 1/4 sec. cor. of sec. 34, T. 2 N., R. 5 E., determined at proportionate dist., there is no remaining evidence of the 3 ins. diam. open end pipe accepted in the 1962 resurvey. Not monumented.
20.27	<p>The 1/4 sec. cor. of sec. 3 only, established by Martin T. Etcheverry, Arizona R.L.S. No. 33873, monumented with a rebar, 1/2 in. diam., firmly set, projecting 1 in. above ground, with 1 in. diam. plastic cap, marked SGS LS 33873. This is accepted as a careful and faithful determination of the cor.</p> <p>Cor. is located on the westerly toe slope of closed land fill, edge bears N. and S., and is not remonumented.</p> <hr style="width: 20%; margin: 10px auto 0 auto;"/> <p>S. 88°17' W., beginning new measurement.</p> <p>Over bed of Salt River, within the SRPMIC.</p>
20.27	Point for the W. 1/16 sec. cor. of sec. 3, at proportionate dist., falls in the bed of the Salt River, not monumented.
27.96	Point for the meander cor. of sec. 34, T. 2 N., R. 5 E., at proportionate dist., established on the W. shore of an island within the Salt River in the 1910 resurvey. There is no remaining evidence of the cor., not monumented.

**Dependent Resurvey of a Portion of the North Boundary,  
T. 1 N., R. 5 E., Gila and Salt River Meridian, Arizona**

CHAINS																									
38.01	Point for the cor. of secs. 33 and 34, T. 2 N., R. 5 E., at proportionate dist., there is no remaining evidence of the 3 ins. diam. open end pipe, accepted in the 1962 resurvey. Cor. falls in a canal which is part of a flood control project for State Route 87, not monumented.																								
39.93	Point for the meander cor. of sec. 33, T. 2 N., R. 5 E., at proportionate dist., on the right bank of the Salt River in 1910. There is no remaining evidence of the cor., not monumented.																								
40.54	The cor. of secs. 3 and 4, monumented with an iron post, 2 1/2 ins. diam., firmly set, 24 ins. below the surface, with brass cap mkd. T2N R5E S33 S4 S3 T1N R5E 1962.																								
	<p>At the corner point</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over the existing iron post, with brass cap mkd.</p>																								
	<table style="margin-left: auto; margin-right: auto;"> <tr> <td>T</td> <td>2</td> <td>N</td> <td>R</td> <td>5</td> <td>E</td> </tr> <tr> <td></td> <td></td> <td>S</td> <td>33</td> <td></td> <td></td> </tr> <tr> <td>S</td> <td>5</td> <td> </td> <td>S</td> <td>4</td> <td></td> </tr> <tr> <td>T</td> <td>1</td> <td>N</td> <td>R</td> <td>5</td> <td>E</td> </tr> </table>	T	2	N	R	5	E			S	33			S	5		S	4		T	1	N	R	5	E
T	2	N	R	5	E																				
		S	33																						
S	5		S	4																					
T	1	N	R	5	E																				
	2010																								
	Set a steel fence post, alongside and NE of the cor.																								
	Cor. is located within the existing bed of the Salt River.																								
	From this cor. point, an open end iron pipe, 1 in. diam., firmly set, 12 ins. below the surface bears E., 1 lk. dist.																								
	<hr/> <p style="text-align: center;"><b>Dependent Resurvey of a Portion of the Subdivisional Lines, T. 1 N., R. 5 E., Gila and Salt River Meridian, Arizona</b></p> <hr/>																								
	<p style="text-align: center;">Restoring the survey executed by W. F Ingalls in 1868 and the resurvey executed by B. Owens and P. Bauer in 1962</p> <hr/>																								
	<p>From the cor. of secs. 8, 9, 16 and 17, monumented with an unmarked brass disk, 3 ins. diam., seated in concrete, 6 ins. below the surface, set inside a 10 ins. diam., survey well. This is accepted as the best available evidence of the 1962 cor.</p>																								
	<p>Cor. is located at the intersection of Alma School Road, bearing N. and S., and Bass Pro Drive bearing W.</p>																								

Dependent Resurvey of a Portion of the Subdivisional Lines  
T. 1 N., R. 5 E., Gila and Salt River Meridian, Arizona

CHAINS							
	<p>N. 0°27' W., bet. secs. 8 and 9.</p> <p>Within Alma School Road, City of Mesa.</p>						
40.34	<p>Point for the 1/4 sec. cor. of secs. 8 and 9, at proportionate dist., by the method of irregular boundary adjustment, based upon a <i>Result of Survey</i>, executed by Daniel N. Miller, Arizona R.L.S. No. 25392, in 1995, filed with the Arizona Department of Transportation, Right of Way Plans Section, in Drawing No. D-7-T-887. There is no remaining evidence of the 1962 monument or accessories. Not monumented.</p> <hr/>						
	<p>N. 0°28' W., beginning new measurement.</p> <p>Across State Route No. 202.</p>						
20.15	<p>Manmade left bank of the Salt River, bears N. 65° E. and S. 65° W.</p>						
20.285	<p>Point for the N. 1/16 sec. cor. of secs. 8 and 9, at proportionate dist., there is no remaining evidence of the 1962 monument or accessories.</p> <p>Cor. is located on, entrance road from Alma School Road to sand and gravel mining operations within the bed of Salt River, not monumented.</p>						
24.03	<p>Point for the witness point, at intersection with the S. bdy. of the SRPMIC, at proportionate dist., there is no remaining evidence of the 1972 monument or accessories.</p> <p>Set a stainless steel rod, 12 ins. long, 1/2 in. diam., 15 ins. in the ground, cemented in place, with brass cap mkd.</p> <div data-bbox="776 1360 1003 1570" style="text-align: center;"> <p>WP</p> <table style="margin: auto;"> <tr> <td style="text-align: center;">T 1 N</td> <td style="border-left: 1px solid black; border-right: 1px solid black; padding: 0 5px;">R 5 E</td> </tr> <tr> <td style="text-align: center;">SRPMIC</td> <td style="border-left: 1px solid black; border-right: 1px solid black; padding: 0 5px;">S 9</td> </tr> <tr> <td style="text-align: center;">S 8</td> <td style="border-left: 1px solid black; border-right: 1px solid black; padding: 0 5px;">S 9</td> </tr> </table> <p>2010</p> </div> <p>Deposit a magnet, in a white plastic case, beneath the stainless steel rod.</p> <p>Cor. is located, within a sand and gravel operation, approximately 1.5 chs. E., of the east edge of the south Alma School Road bridge, over the Salt River.</p>	T 1 N	R 5 E	SRPMIC	S 9	S 8	S 9
T 1 N	R 5 E						
SRPMIC	S 9						
S 8	S 9						



Dependent Resurvey of a Portion of the Subdivisional Lines  
T. 1 N., R. 5 E., Gila and Salt River Meridian, Arizona

CHAINS																			
	<p>From this cor. point, the point accepted for Angle Point 24, of the resurvey of the 1972 metes-and-bounds survey of the S. bdy. of the SRPMIC, bears S. 74°47' W., 4.17 chs. dist., hereinafter described.</p> <p>Continuing measurement, identical with the S. bdy. of the SRPMIC.</p>																		
30.43	<p>The N-N 1/64 sec. cor. of secs. 8 and 9, monumented with an iron post, 2 1/2 ins. diam., firmly set, 13 ins. below the surface, with the marks N-N 1/64 1962, visible on a scuffed brass cap.</p> <p>from which</p> <p style="padding-left: 40px;">The SW cor. of a block building, bears S. 53°21' E., 92.5 lks. dist., the long side bears N. and S.</p> <p style="padding-left: 40px;">The NW cor. of same block building, bears N. 48°00' E., 99.5 lks. dist.</p> <p>Cor. is located, atop an island, between the N. and S. channels of the Salt River.</p> <hr style="width: 20%; margin: 10px auto;"/> <p>N. 0°19' W., beginning new measurement.</p> <p>Within a sand and gravel mining operation, identical with the S. bdy. of the SRPMIC.</p>																		
10.095	<p>Point accepted for the cor. of secs. 4, 5, 8 and 9, occupied with an iron pipe, 4 ins. diam., firmly set, 13 ins. below the surface. This is accepted as the best available evidence of the 1962 monument.</p> <p>At the corner point</p> <p>Set a stainless steel rod, 12 ins. long, 1/2 in. diam., inside the iron pipe, cemented in place, with brass cap mkd.</p> <table style="margin-left: auto; margin-right: auto; border-collapse: collapse;"> <tr> <td style="padding: 0 5px;">T</td> <td style="padding: 0 5px;">1</td> <td style="padding: 0 5px;">N</td> <td style="padding: 0 5px;">R</td> <td style="padding: 0 5px;">5</td> <td style="padding: 0 5px;">E</td> </tr> <tr> <td style="padding: 0 5px;">S</td> <td style="padding: 0 5px;">5</td> <td style="border-left: 1px solid black; padding: 0 5px;"></td> <td style="padding: 0 5px;">S</td> <td style="padding: 0 5px;">4</td> <td style="padding: 0 5px;"></td> </tr> <tr> <td style="padding: 0 5px;">S</td> <td style="padding: 0 5px;">8</td> <td style="border-left: 1px solid black; padding: 0 5px;"></td> <td style="padding: 0 5px;">S</td> <td style="padding: 0 5px;">9</td> <td style="padding: 0 5px;"></td> </tr> </table> <p style="text-align: center;">2010</p> <p>Set a steel fence post, NW of the cor.</p> <p>Cor. is located, within sand and gravel mining operation.</p>	T	1	N	R	5	E	S	5		S	4		S	8		S	9	
T	1	N	R	5	E														
S	5		S	4															
S	8		S	9															


Dependent Resurvey of a Portion of the Subdivisional Lines  
T. 1 N., R. 5 E., Gila and Salt River Meridian, Arizona

CHAINS	
	<p>From this cor. point, a damaged and unreadable brass disk, 3 ins. diam., seated in concrete, set 8 ins. below the surface of Alma School Road, within a 10 ins. diam. survey well, bears S. 89°47' W., 4.55 chs. dist.</p>
	<hr/> <p style="text-align: center;">Restoring the resurvey executed by Robert A. Farmer in 1910 and Boyd S. Owens and Paul G. Bauer in 1962</p> <hr/>
	<p>From the cor. of secs. 3 and 4, on the N. bdy. of the Tp., hereinbefore described.</p>
	<p>S. 0°19' W., bet. secs. 3 and 4.</p>
	<p>Over Salt River bottom, within the SRPMIC.</p>
1.395	<p>The meander corner of secs. 3 and 4, on the 1910 right bank of the Salt River, reestablished at record course and distance in the 1962/1972 resurvey, monumented with an iron post, 2 1/2 ins. diam., firmly set, 14 ins. below the surface, with brass cap mkd. T1N R5E S4 S3 MC 1962.</p>
	<p>Set a steel fence post, alongside and N. of the cor.</p>
	<hr/> <p style="text-align: center;">Restoring the survey executed by W. F Ingalls in 1868 and the resurvey executed by Owens and Bauer in 1962</p> <hr/>
	<p>From the meander cor. of secs. 3 and 4.</p>
	<p>S. 1°04' E., bet. secs. 3 and 4.</p>
	<p>Over Salt River bottom.</p>
19.495	<p>Point for the N. 1/16 sec. cor. of secs. 3 and 4, in the bed of the Salt River, not monumented.</p>
28.85	<p>The witness point at intersection with 1972 metes-and-bounds survey of the S. bdy. of the SRPMIC, reestablished by Mason Linsey Womble Jr., Arizona R.L.S. No. 17575, as per an unrecorded <i>Result of Survey</i> plat, obtained from the SRPMIC Survey Dept. Monumented with a rebar 1/2 in. diam., firmly set, projecting 1 in. above ground, with affixed plastic cap mkd. LS 17575. This is accepted as a careful and faithful reestablishment of the orig. cor.</p>
	<p>At the corner point</p>
	<p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 27 ins. in the ground, with brass cap mkd.</p>

Dependent Resurvey of a Portion of the Subdivisional Lines  
T. 1 N., R. 5 E., Gila and Salt River Meridian, Arizona

CHAINS	
	<p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p> <p>Deposit the rebar inside the stainless steel post.</p> <p>Set a steel fence post, alongside and N. of the cor.</p> <p>Cor. is located in bed of Salt River.</p> <hr/> <p>S. 1°04' E., beginning new measurement, exiting the SRPMIC.</p>
10.20	Woven wire fence, on manmade left bank of Salt River, bears N. 45° E. and S. 45° W., thence exit bed of Salt River.
11.06	<p>The 1/4 section cor. of secs. 3 and 4, perpetuated by Karl Lawrence Pearson, Arizona R.L.S. No. 35832, as per <i>Record of Survey</i>, recorded in the Maricopa County Recorder's Office in book 689, page 17, monumented with a 1/2 in. diam. aluminum rod, firmly set, 2 ins. below the surface, with affixed 3 ins. diam. brass cap mkd. MARICOPA COUNTY 1/4 S4 S3 2004 RLS 35832. This is accepted as a careful and faithful perpetuation of the orig. cor. position.</p> <p>Set a rebar 18 ins. long, 20 ins. in the ground, alongside and W. of the aluminum rod.</p> <p>Cor. is located 1 ch. W. of Country Club Drive bridge, over the Salt River.</p> <hr/> <p>S. 0°10' E., beginning new measurement.</p>
40.01	<p>The cor. of secs. 3, 4, 9 and 10 occupied with a brass disk, 3 ins. diam., seated in concrete, 7 ins. below the pavement, set inside a 10 ins. diam., survey well, with top mkd. CITY OF MESA. This is accepted as the best available evidence of the orig. cor.</p> <p>Cor. is located at the intersection of Country Club Drive bearing N. and S., and McKellips Road bearing E. and W., City of Mesa.</p> <hr/> <p>S. 89°13' W., bet. secs. 4 and 9, within McKellips road, City of Mesa.</p>

Dependent Resurvey of a Portion of the Subdivisional Lines  
T. 1 N., R. 5 E., Gila and Salt River Meridian, Arizona

CHAINS	
38.07	<p>Point for the 1/4 sec. cor. of secs. 4 and 9, at proportionate dist., by the method of irregular boundary adjustment, based upon a <i>Result of Survey</i>, executed by Daniel N. Miller, Arizona R.L.S. No. 25392, in 1995, filed with the Arizona Department of Transportation, Right of Way Plans Section, in Drawing No. D-7-T-887. There is no remaining evidence of the 1962 monument or accessories.</p> <p>The cor. point falls within the E. bound lanes of State Route No. 202, not monumented.</p> <hr style="width: 20%; margin: 10px auto;"/> <p>S. 89°50' W., beginning new measurement.</p> <p>Across a storage yard, for wooden wire spools.</p>
9.66	<p>Point for the E-W 1/64 sec. cor. of secs. 4 and 9, at proportionate dist., there is no remaining evidence of the 1962 monument or accessories.</p> <p>The cor. point falls on the westerly edge of a storage yard for wooden wire spools, identical with the left man made bank, of the south channel of the Salt River, bears N. 35° E. and S. 35° W., not monumented.</p>
10.30	<p>Point for the witness point, at intersection with the S. bdy. of the SRPMIC, determined at proportionate dist., during the course of the 1972 survey the cor. point was identified, however was not monumented.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, in a mound of stone, 3 ft. base, to top, with brass cap mkd.</p> <div style="text-align: center; margin: 10px 0;">  </div> <p>from which</p> <p style="text-align: center;">An X chiseled on the N. wing wall of concrete head wall, bears S. 3°57' W., 21.5 lks. dist.</p> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p> <p>Cor. is located on the side slope, of the man made left bank of the S. channel of the Salt River, bears N. 35° E. and S. 35° W.</p>

**Dependent Resurvey of a Portion of the Subdivisional Lines  
T. 1 N., R. 5 E., Gila and Salt River Meridian, Arizona**

CHAINS	<p>From this cor. point, Angle Point 30, of the resurvey of the 1972 metes-and-bounds survey of the S. bdy. of the SRPMIC, bears N. 63°36' E., 7.20 chs. dist., hereinafter described.</p> <p>Continuing measurement, identical with the S. bdy. of the SRPMIC, across the S. channel of the Salt River.</p>
19.32	<p>The W. 1/16 sec. cor. of secs. 4 and 9, reestablished by Gerald David Hughes, Arizona R.L.S. No. 15573, date unknown, monumented with a rebar, 1/2 in. diam., firmly set, 18 ins. below the surface, with affixed plastic cap mkd. RLS 15573. This is accepted as a careful and faithful reestablishment of the 1962 cor. position.</p> <p>At the corner point</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 27 ins. in the ground, over the rebar, with brass cap mkd.</p> <div style="text-align: center; margin: 10px 0;"> <p>T 1 N R 5 E</p> <p style="margin-left: 100px;">S 4</p> <p style="margin-left: 100px;">W 1/16 ———</p> <p style="margin-left: 100px;">S 9</p> <p style="margin-top: 10px;">2010</p> </div> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p> <p>Raise a mound of stone, 3 1/2 ft. base, 2 ft. high N. of cor.</p> <hr style="width: 20%; margin: 10px auto;"/> <p>S. 89°50' W., beginning new measurement.</p> <p>On the S. bdy. of the SRPMIC, across sand and gravel mining operation.</p>
9.66	<p>Point for the W-W 1/64 sec. cor. of secs. 4 and 9, at proportionate dist., there is no remaining evidence of the 1962 monument or accessories. Not monumented.</p> <p>Continuing measurement on the S. bdy. of the SRPMIC, across a sand and gravel mining operation.</p>
19.32	<p>The cor. of secs. 4, 5, 8 and 9.</p> <hr style="width: 60%; margin: 10px auto;"/>

Dependent Resurvey of a Portion of the Subdivisional Lines  
T. 1 N., R. 5 E., Gila and Salt River Meridian, Arizona

CHAINS	
	<p>Restoring the resurvey executed by Robert A. Farmer, in 1910 and Boyd S. Owens and Paul G. Bauer in 1962</p> <hr/>
	<p>From the cor. of secs. 4 and 5 on the N. bdy. of the Tp., occupied with a 10 ins. diam., survey well, no disk found. This is accepted as the best available evidence of the 1910 cor.</p>
	<p>Cor. is located, in the east bound lane of McDowell Road, about 2.5 chs. W. of the intersection with Alma School Road, bearing N. and S.</p>
	<p>S. 0°19' W., bet. secs. 4 and 5, within the SRPMIC.</p>
19.82	<p>Point for the N. 1/16 sec. cor. of secs. 4 and 5, at proportionate dist., there is no remaining evidence of the 1910 monument. Not monumented.</p>
39.67	<p>The 1/4 sec. cor. of secs. 4 and 5, monumented with a 3 ins. diam., brass disk, mkd. MARICOPA COUNTY D.O.T., seated in concrete, 5 ins. below the surface, set inside a 10 ins. diam., survey well. This is accepted as a careful and faithful reestablishment of the 1962 monument. Not monumented.</p>
	<p>Cor. is located at the intersection of Alma School Road, bearing N. and S. with Lehi Road, bearing W.</p> <hr/>
	<p>S. 0°19' W., beginning new measurement.</p>
	<p>Along Alma School Road, within the SRPMIC.</p>
20.04	<p>Point for the S. 1/16 sec. cor. of secs. 4 and 5, at proportionate dist., there is no remaining evidence of the 1962 monument or accessories. Not monumented.</p>
21.43	<p>Point for the meander cor. of secs. 4 and 5, at proportionate dist., by the method of irregular boundary adjustment, on the right bank of the Salt River in 1910, reestablished by one point control in 1962. There is no remaining evidence of the 1962 monument or accessories.</p> <p>Cor. point is located, within the pavement of Alma School Road, on the north end of the north Alma School Road bridge, over the Salt River. Not monumented.</p> <hr/>
	<p>Restoring the survey executed by W. F Ingalls in 1868 and the resurvey executed by B. Owens and P. Bauer in 1962</p> <hr/>
	<p>From the meander cor. of secs. 4 and 5.</p>

**Dependent Resurvey of a Portion of the Subdivisional Lines  
T. 1 N., R. 5 E., Gila and Salt River Meridian, Arizona**

CHAINS	
	S. 13°32' E., bet. secs. 4 and 5.
	Across the N. channel of the Salt River, within the SRPMIC.
8.835	Point for the S-S 1/64 sec. cor. of secs. 4 and 5, at proportionate dist., there is no remaining evidence of the 1962 monument or accessories. Not monumented.
13.93	The manmade left bank, of the N. channel of the Salt River, bears N. 80° E. and S. 80° W.; thence across sand and gravel mining operation.
19.105	The cor. of secs. 4, 5, 8 and 9.
	<hr/> From the cor. of secs. 8, 9, 16 and 17.
	N. 89°41' W., bet. secs. 8 and 17.
	Across Mesa River View Shopping complex.
41.40	Point for the 1/4 sec. cor. of secs. 8 and 17, at proportionate dist., by the method of irregular boundary adjustment, based upon a <i>Record of Survey</i> , executed by David Shane, Arizona R.L.S. No. 18222, in 1997, filed with the Arizona Department of Transportation, in Drawing No. D-7-T-860. There is no remaining evidence of the 1962 monument or accessories. Not monumented.
	<hr/> N. 89°42' W., beginning new measurement.
20.715	Point for the W. 1/16 sec. cor. of secs. 8 and 17, at proportionate dist., there is no remaining evidence of the 1962 monument or accessories.
	Cor. is located, in the pavement of Dobson Road, not monumented.
	Continuing measurement, across State Route No. 202.
41.43	Point accepted, for the cor. of secs. 7, 8, 17 and 18, monumented with an iron pin, 8 ins. long, 1/4 diam., set 8 ins. in the ground. This is accepted as the best available evidence of the 1972 monument.
	At the corner point
	Set a stainless steel rod, 12 ins. long, 1/2 in. diam., 13 ins. in the ground, cemented in place, with brass cap mkd.

Dependent Resurvey of a Portion of the Subdivisional Lines  
T. 1 N., R. 5 E., Gila and Salt River Meridian, Arizona

CHAINS

T 1 N		R 5 E
S 7		S 8
S 18		S 17

2010

The cor. was previously occupied with a 1/2 in. diam. rebar, the iron pin was perpetuated from measurement by the SRPMIC survey division.

Cor. is located atop, manmade left bank of the Salt River, 16 ft. wide, bears N. 65° E. and S. 65° W., 12 lks. N. of the N. retaining wall of State Route No. 202.

---

N. 89°56' W., bet. secs. 7 and 18.

Descending into bed of the channelized Salt River.

4.375 Point accepted for the witness point, of secs. 7 and 18, as established in the 1972 metes-and-bounds survey of the S. bdy. of the SRPMIC, monumented with an iron rod, 1 in. diam., firmly set, projecting 30 ins. above ground, encircled with a collar of stone. This is accepted as the best available evidence of the 1972 monument.

At the corner point

Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 27 ins. in the ground, with brass cap mkd.

	W P	
T 1 N		R 5 E
		SRPMIC
S 7		/
S 18		
		2011

Deposit a magnet, in a white plastic case, at the base of the stainless steel post.

Raise a mound of stone, 4 base, 2 1/2 ft. high, NNE of the cor.

Cor. is located on a trail road, within the channelized bed of the Salt River.

Note: The 1 in. iron rod, recovered in 2010, was not recovered in 2011, the corner point was reestablished using a 2010, 60D spike nail, set alongside the iron rod.

---



**Dependent Resurvey of a Portion of the Subdivisional Lines  
T. 1 N., R. 5 E., Gila and Salt River Meridian, Arizona**

CHAINS	
	<p>N. 89°56' W., beginning new measurement.</p>
	<p>Within the bed of the Salt River, identical with the S. bdy. of the SRPMIC.</p>
16.34	<p>Point for the E. 1/16 sec. cor. of secs. 7 and 18, at proportionate dist., there is no remaining evidence of the 1962 monument or accessories.</p>
	<p>Cor. is located, in the active channel of Salt River, not monumented.</p>
37.06	<p>Point accepted for the 1/4 sec. cor. of secs. 7 and 18, monumented with an iron pin, 6 ins. long, 1/4 in. diam., set 6 ins. in the ground, witnessed by a steel fence post, set alongside. This is accepted as the best available evidence of the 1962 monument.</p>
	<p>from which</p>
	<p>A rebar, 18 ins. long, 1/2 in. diam., set 17 ins. in the ground for a reference monument, bears S. 27°27' E., 170.2 ft. dist. with a 2 ins. diam. brass cap mkd. SRPMIC RM T1N R5E 170.2 FT TO COR. S18 2010 SURVEY DIVISION and an arrow pointing to the cor., located alongside a woven wire fence.</p>
	<p>A rebar, 18 ins. long, 1/2 in. diam., set 18 ins. in the ground for a reference monument, bears S. 29°39' W., 171.2 ft. dist. with a 2 ins. diam. brass cap mkd. SRPMIC T1N R5E 171.2 FT TO COR S18 2010 SURVEY DIVISION and an arrow pointing to the cor., located alongside a woven wire fence.</p>
	<p>Cor. is located, in active channel of the Salt River.</p>
	<p>N. 89°56' W., beginning new measurement, on the S. bdy. of the SRPMIC.</p>
10.36	<p>Point for the E-W 1/64 sec. cor. of secs. 7 and 18, at proportionate dist., there is no remaining evidence of the 1962 monument or accessories.</p>
	<p>Cor. is located, in the active channel of the Salt River, not monumented.</p>
20.72	<p>Point for the W. 1/16 sec. cor. of secs. 7 and 18, at proportionate dist., there is no remaining evidence of the 1962 monument or accessories.</p>
	<p>Cor. is located, in the active channel of Salt River, not monumented.</p>

**Dependent Resurvey of a Portion of the Subdivisional Lines  
T. 1 N., R. 5 E., Gila and Salt River Meridian, Arizona**

CHAINS	
31.08	<p>Point for the W-W 1/64 sec. cor. of secs. 7 and 18, at proportionate dist., there is no remaining evidence of the 1962 monument or accessories.</p> <p>Cor. is located, in the active channel of Salt River, not monumented.</p>
41.28	<p>Point for the cor. of secs. 7, 12, 13 and 18, on the W. bdy. of the Tp., determined at proportionate dist., by the method of irregular boundary adjustment, there is no remaining evidence of the 1962 monument or accessories. As described in the field notes of the dependent resurvey in T. 1 N., R. 4 E., executed concurrently under this same group.</p> <p>Cor. is located within the active channel of the Salt River, beneath the interchange of State Routes 101 and 202, not monumented.</p> <hr/> <p align="center">Restoring the resurvey executed by Robert A. Farmer, in 1910-1911 and Boyd S. Owens and Paul G. Bauer in 1962</p> <hr/> <p>From the cor. of secs. 5, 6, 7 and 8, monumented with a brass disk, 3 ins. diam., seated in concrete, 10 ins. below the pavement, set inside a 10 ins. diam., survey well, with top mkd. A.D.O.T. HIGHWAY DIV. 19 This is accepted as the best available evidence of the orig. cor.</p> <p>Cor. is located at the intersection of Alma School Road, bearing E. and W. and Dobson Road bearing N.</p> <p>S. 0°23' W., bet. secs. 7 and 8.</p> <p>Over nearly level land, within the SRPMIC.</p>
18.11	<p>Point for the witness cor. to the N. 1/16 sec. cor. of secs. 7 and 8, at proportionate dist., there is no remaining evidence of the 1910 cor.</p> <p>Cor. point falls in roadway of a sand and gravel mining operation, not monumented.</p>
20.01	<p>True point for the N. 1/16 sec. cor. of secs. 7 and 8, at proportionate dist., not monumented in 1910, 1962 or 2010.</p>
23.78	<p>Point for the meander cor. of secs. 7 and 8, at proportionate dist., by the method of irregular boundary adjustment, on the right bank of the Salt River in 1910 and reestablished at record dist., from the witness cor. to the N. 1/16 sec. cor. of secs. 7 and 8 in 1962. There is no remaining evidence of the 1962 monument or accessories.</p>

**Dependent Resurvey of a Portion of the Subdivisional Lines  
T. 1 N., R. 5 E., Gila and Salt River Meridian, Arizona**

CHAINS	
	Cor. point falls in a sand and gravel mining operation, not monumented.
	<hr/> <p align="center">Restoring the survey executed by W. F Ingalls in 1868 and the resurvey executed by B. Owens and P. Bauer in 1962</p> <hr/>
	S. 2°39' E., beginning new measurement.
	Over sand and gravel mining operation, within the SRPMIC.
6.28	Point for the S-N 1/64 sec. cor. of secs. 7 and 8, at proportionate dist., there is no remaining evidence of the 1962 monument or accessories, not monumented.
16.335	Point for the 1/4 sec. cor. of secs. 7 and 8, at proportionate dist., there is no remaining evidence of the 1962 monument or accessories, not monumented.
26.42	Point for the N-S 1/64 sec. cor. of secs. 7 and 8, at proportionate dist., there is no remaining evidence of the 1962 monument or accessories, not monumented.
36.21	Man made, left bank of the Salt River, 30 ft. wide, 30 ft. high, bears N. 65° E. and S. 65° W.
	Thence, descending into channelized bed of the Salt River.
36.505	Point for the S 1/16 sec. cor. of secs. 7 and 8, at proportionate dist., there is no remaining evidence of the 1962 monument or accessories, not monumented.
54.93	Point for the witness point, at intersection with the S. bdy. of the SRPMIC, there is no remaining evidence of the 1972 monument or accessories.
	Cor. point, falls in the active channel of the Salt River, not monumented.
	From this cor. point, the witness point, at intersection of the line bet. secs. 7 and 18, with the S. bdy. of the SRPMIC, bears S. 68°02' W., 4.63 chs. dist., hereinbefore described.
	Continuing measurement, leaving the SRPMIC.
56.67	The cor. of secs. 7, 8, 17 and 18.

Dependent Resurvey of a Portion of the Subdivisional Lines  
T. 1 N., R. 5 E., Gila and Salt River Meridian, Arizona

CHAINS	
	<p>Restoring the resurvey executed by Robert A. Farmer, in 1910-1911 and Boyd S. Owens and Paul G. Bauer in 1962/1972</p> <hr/> <p>From the cor. of secs. 5, 6, 7 and 8.</p> <p>N. 89°59' E., bet. secs. 5 and 8.</p> <p>Over nearly level land, within the SRPMIC.</p>
20.01	<p>The W. 1/16 sec. cor. of secs. 5 and 8, monumented with an iron post, 1 in. diam., firmly set, projecting 1 in. above ground, with brass cap mkd. No. 2 1/16 S5 S8 1910. Add the marks T1N R5E 2010 to the brass cap.</p> <p>A 4 x 4 ins. sq. post, projecting 32 ins. above ground, is set 2 lks. N. of the cor.</p> <hr/>
	<p>N. 89°59' E., beginning new measurement.</p>
18.30	<p>Mid-point bet. two parallel high voltage transmission lines, bears N. 60° E. and S. 60° W.</p>
20.02	<p>The 1/4 sec. cor. of secs. 5 and 8, monumented with an iron post, 2 1/2 ins. diam., set 33 ins. below the surface, the brass cap is scuffed and unreadable.</p> <p>At the corner point</p> <p>Set a rebar, 18 ins. long, 1/2 in. diam., 22 ins. in the ground, atop the iron post.</p> <p>Cor. is located on the extension of Longmore Road, bearing N.</p> <hr/>
	<p>S. 89°58' E., beginning new measurement.</p>
5.08	<p>A rebar 1/2 in. diam., firmly set, projecting 2 ins. above ground, with affixed 1 in. diam. plastic cap, mkd. SGS LS 33873.</p>
8.70	<p>Man made right bank of the Salt River, bears N. 30° E. and S. 30° W.</p>
19.015	<p>Point for the meander cor. of secs. 5 and 8, at proportionate dist., by the method of irregular boundary adjustment, on the right bank of the Salt River in 1910 and reestablished by one point control in 1962. Falls in the active N. channel of the Salt River, there is no remaining evidence of the 1962 monument or accessories. Not monumented.</p> <hr/>

**Dependent Resurvey of a Portion of the Subdivisional Lines  
T. 1 N., R. 5 E., Gila and Salt River Meridian, Arizona**

CHAINS	
	<p align="center">Restoring the survey executed by W. F Ingalls in 1868 and the resurvey executed by B. Owens and P. Bauer in 1962</p> <hr/> <p>N. 89°56' E., beginning new measurement.</p>
3.29	Point for the E. 1/16 sec. cor. of secs. 5 and 8, at proportionate dist., falls in the active N. channel of the Salt River, there is no remaining evidence of the 1962 monument or accessories. Not monumented.
14.445	Point for the E-E 1/64 sec. cor. of secs. 5 and 8, at proportionate dist., there is no remaining evidence of the 1962 monument or accessories. Not monumented.
25.60	The cor. of secs. 4, 5, 8 and 9.
	<p><b>Subdivision of Section 8, T. 1 N., R. 5 E., Gila and Salt River Meridian, Arizona</b></p> <hr/> <p>Restoring the survey executed by Robert A. Farmer, in 1910-1911 and the resurvey executed by Boyd S. Owens and Paul G. Bauer in 1962</p> <hr/> <p>From the 1/4 sec. cor. of secs. 5 and 8, hereinbefore described. S. 0°21' W., on the N. and S. center line of sec. 8. Over nearly level land, within the SRPMIC.</p>
1.15	Intersect a woven wire fence, bears NW for 55 lks., thence W. and E. for. 2.4 lks. to fence cor., with fence extending S.
10.07	Point for the C-N-N 1/64 sec. cor. of sec. 8, at proportionate dist., there is no remaining evidence of the 1962 monument or accessories. Not monumented.
11.40	Graded road, 35 ft. wide, bears N. 50° E. and S. 50° W.
13.355	The meander corner on the N. and S. center line of sec. 8, at intersection with 1910 right bank of the Salt River, reestablished at record course and distance in the 1962 resurvey, monumented with an iron post, 2 1/2 ins. diam., firmly set, projecting 4 ins. above ground, with brass cap mkd. T1N R5E S8 MC 1962.  Add the marks 2010 to the brass cap.  Cor. is located 2 lks. E. of a woven wire fence, bears N. and S.

Subdivision of Section 8,  
T. 1 N., R. 5 E., Gila and Salt River Meridian, Arizona

CHAINS	
	Restoring the survey executed by Boyd S. Owens and Paul G. Bauer in 1962
	S. 3°20' E., beginning new measurement, on the N. and S. center line of sec. 8.
	Within the SRPMIC.
1.65	Terminus of woven wire fence, bears N.
3.48	Point selected for a witness point.
	Set a brass tablet, 3 1/4 ins. diam., 3 1/2 ins. stem, cemented in a drill hole, flush with surface, with top mkd.
	WP T 1 N R 5 E C   S 8 C  2010
	Deposit a magnet, in a white plastic case, at the base of the stainless steel post.
	Cor. is locate atop the man made right bank of the Salt River, 20 ft. high, 15 ft. wide, bears N. 20° E. and S. 20° W.
	Continuing measurement, descending into active channel of the Salt River.
6.80	Point for the C-N 1/16 sec. cor. of sec. 8, at proportionate dist., there is no remaining evidence of the 1962 monument or accessories. Not monumented.
16.895	Point for the C-S-N 1/64 sec. cor. of sec. 8, at proportionate dist., there is no remaining evidence of the 1962 monument or accessories. Not monumented.
26.99	Point for the C 1/4 sec. cor. of sec. 8, at intersection with the E. and W. center line of sec. 8, there is no remaining evidence of the 1962 monument or accessories. Not monumented.
27.87	Intersect the S. bdy. of the SRPMIC.
	From this point, the calculated point for AP 18, on the S. bdy. of the SRPMIC, bears N. 41°44' E., 1.61 chs. dist., hereinafter described.
	Continuing measurement, leaving the SRPMIC.

Subdivision of Section 8,  
T. 1 N., R. 5 E., Gila and Salt River Meridian, Arizona

CHAINS	
37.085	Point for the C-N-S 1/64 sec. cor. of sec. 8, at proportionate dist., there is no remaining evidence of the 1962 monument or accessories. Not monumented.
40.43	<p>Point selected for a witness point.</p> <p>Set a brass tablet, 3 1/4 ins. diam., 3 1/2 ins. stem, cemented in a drill hole, flush with surface, with top mkd.</p>
	<p style="text-align: center;">WP T 1 N R 5 E C S 8   C</p> <p style="text-align: center;">2010</p>
	Deposit a magnet, in a white plastic case, at the base of the stainless steel post.
	Cor. is locate atop the man made left bank of the Salt River, 25 ft. high, 15 ft. wide, bears N. 35° E. and S. 35° W.
	Continuing measurement, across State Route No. 202.
47.18	<p>The center S. 1/16 sec. cor. of sec. 8, reestablished by Daniel N. Miller, Arizona R.L.S. No. 25392, in 1995, as filed with the Arizona Department of Transportation, Right of Way Plans Section, in Drawing No. D-7-T-887. Monumented with an aluminum disk, 3 ins. diam., set in concrete flush with the surface, with top mkd. A.D.O.T. HIGHWAY DIV. 438 + 01.17 189.88 FT. 1997. This is accepted as a careful and faithful reestablishment of the 1962 cor. position.</p>
	<hr style="width: 30%; margin-left: auto; margin-right: auto;"/> <p>S. 3°21' E., beginning new measurement.</p>
20.19	The point for, the 1/4 sec. cor. of secs. 8 and 17, hereinbefore described.
	<hr style="width: 60%; margin-left: auto; margin-right: auto;"/> <p>From the point for the 1/4 sec. cor. of secs. 7 and 8, hereinbefore described.</p>
	S. 89°44' E., on the E. and W. center line of sec. 8.
	Across, sand and gravel mining operation.
	Within the SRPMIC.
10.23	Point for the C-W-W 1/64 sec. cor. of sec. 8, falls within a mining operation, there is no remaining evidence of the 1962 monument or accessories. Not monumented.

Subdivision of Section 8,  
T. 1 N., R. 5 E., Gila and Salt River Meridian, Arizona

CHAINS	
20.46	Point for the C-W 1/16 sec. cor. of sec. 8, falls within a mining operation, there is no remaining evidence of the 1962 monument or accessories. Not monumented.
26.43	<p>Point selected for a witness point.</p> <p>Set a brass tablet, 3 1/4 ins. diam., 3 1/2 ins. stem, cemented in a drill hole, with brass cap mkd.</p> <p style="text-align: center;">W P T 1 N R 5 E S 8 C———C</p> <p style="text-align: center;">2010</p> <p>Deposit a magnet, in a white plastic case, at the base of the drill hole.</p> <p>Cor. is located on the manmade right bank of the Salt River, 25 ft. high, 15 ft. wide, bears NE and SW.</p>
30.70	Point for the C-E-W 1/64 sec. cor. of sec. 8, falls in the active channel of the Salt River, there is no remaining evidence of the 1962 monument or accessories. Not monumented.
40.93	Point for the C 1/4 sec. cor. of sec. 8.
41.76	<p>Intersect the S. bdy. of the SRPMIC.</p> <p>From this point, the calculated point for AP 18, on the S. bdy. of the SRPMIC, bears N. 41°44' W., 0.435 chs. dist., hereinafter described.</p> <p>Continuing measurement, leaving the SRPMIC.</p>
51.79	Point for the C-W-E 1/64 sec. cor. of sec. 8, falls within the bed of the Salt River, there is no remaining evidence of the 1962 monument or accessories. Not monumented.
54.00	<p>Point selected for a witness point.</p> <p>Set a brass tablet, 3 1/4 ins. diam., 3 1/2 ins. stem, cemented in a drill hole, with brass cap mkd.</p> <p style="text-align: center;">W P T 1 N R 5 E S 8 C———C</p> <p style="text-align: center;">2010</p>





Subdivision of Section 8,  
T. 1 N., R. 5 E., Gila and Salt River Meridian, Arizona

CHAINS	
	<p>Deposit a magnet, in a white plastic case, at the base of the drill hole.</p> <p>Cor. is located atop the manmade left bank of the Salt River, 25 ft. high, 15 ft. wide, bears NE and SW.</p> <p>Continuing measurement across State Route No. 202.</p>
62.65	<p>Point for the C-E 1/16 sec. cor. of sec. 8, falls on the S. slope of State Route No. 202, within the Arizona Dept. of Transportation right-of-way, there is no remaining evidence of the 1962 monument or accessories. Not monumented.</p>
84.36	<p>The point for the 1/4 sec. cor. of secs. 8 and 9, hereinbefore described.</p> <hr/> <p style="text-align: center;">NE 1/4</p> <hr/> <p>From the point for the E. 1/16 sec. cor. of secs. 5 and 8, hereinbefore described.</p> <p>S. 1°15' E., on the N. and S. center line of the NE 1/4 of sec. 8.</p> <p>Within the SRPMIC.</p> <p>Over the bed of the Salt River.</p>
10.09	<p>Point for the C-N-NE 1/64 sec. cor. of sec. 8, falls within the bed of the Salt River, there is no remaining evidence of the 1962 monument or accessories. Not monumented.</p>
20.18	<p>The NE 1/16 sec. cor. of sec. 8, on the S. bdy. of the SRPMIC, monumented with an iron post, 2 1/2 ins. diam., set 6 ins. below the surface of ground, with brass cap mkd. NE 1/16 S8 1962.</p> <p>Add the marks T1N R5E 2010 to the brass cap.</p> <p>A rebar, 18 ins. long, 1/2 in. diam., set 15 ins. in the ground, with attached brass wafer, stamped PLS 19809, is set alongside the iron post.</p> <p>Cor. is located on the W. side of an iron post fence corner, 6 ins. diam., extends E. for 7 ft. and S. for 7 ft.</p> <hr/> <p>S. 1°17' E., beginning new measurement.</p> <p>On the S. bdy. of the SRPMIC, over fill area within the bed of the Salt River.</p>

Subdivision of Section 8,  
T. 1 N., R. 5 E., Gila and Salt River Meridian, Arizona

CHAINS	
5.83	<p>Point for a witness point, at intersection with the 1972 survey of the S. bdy. of the SRPMIC.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 27 ins. in the ground, in a collar of stone, with brass cap mkd.</p> <div style="text-align: center;"> </div> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p> <p>Continuing measurement, departing from the SRPMIC.</p>
10.11	<p>Point for the C-S-NE 1/64 sec. cor. of sec. 8, falls on the W. facing slope of a fill area within the bed of the Salt River, there is no remaining evidence of the 1962 monument or accessories. Not monumented.</p>
15.20	<p>Man made, left bank of the Salt River, 20 ft. high, 20 ft. wide, bears N. 65° E. and S. 65° W.</p> <p>Continuing measurement, across State Route No. 202.</p>
20.22	<p>The point for the C-E 1/16 sec. cor. of sec. 8.</p> <hr/> <p>From the point for the center N. 1/16 sec. cor. of sec. 8.</p> <p>S. 89°54' E., on the E. and W. center line of the NE 1/4 of sec. 8.</p> <p>Over active channel of the Salt River.</p> <p>Within the SRPMIC.</p>
11.22	<p>Point for the C-W-NE 1/64 sec. cor. of sec. 8, falls within the bed of the Salt River, there is no remaining evidence of the 1962 monument or accessories. Not monumented.</p>
22.44	<p>The NE 1/16 sec. cor. of sec. 8.</p> <hr/> <p>S. 89°54' E., beginning new measurement.</p> <p>Within the bed of the Salt River, on the S. bdy. of the SRPMIC.</p>

Subdivision of Section 8,  
T. 1 N., R. 5 E., Gila and Salt River Meridian, Arizona

CHAINS	
11.00	<p>Point for the C-E-NE 1/64 sec. cor. of sec. 8, falls within the bed of the Salt River, there is no remaining evidence of the 1962 monument or accessories. Not monumented.</p>
12.315	<p>Point for a witness point, at intersection with the 1972 survey of the S. bdy. of the SRPMIC.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 27 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center; margin: 10px 0;"> <p>W P</p> <p>T 1 N R 5 E</p> <p>SRPMIC</p>  </div> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p> <p>Continuing measurement, outside the SRPMIC.</p>
22.00	<p>The point for the N. 1/16 sec. cor. of secs. 8 and 9, hereinbefore described.</p> <hr style="width: 80%; margin: 10px auto;"/> <p style="text-align: center;">SW 1/4</p> <hr style="width: 80%; margin: 10px auto;"/> <p>From the point for the center W. 1/16 sec. of sec. 8.</p> <p>S. 3°00' E., on the N. and S. center line of the SW 1/4 of sec. 8.</p> <p>Across, sand and gravel mining operation.</p> <p>Within the SRPMIC.</p>
5.68	<p>Point selected for a witness point.</p> <p>Set a brass tablet, 3 1/4 ins. diam., 3 1/2 ins. stem, cemented in a drill hole, flush with surface, with top mkd.</p> <div style="text-align: center; margin: 10px 0;"> <p>W P</p> <p>T 1 N R 5 E</p>  </div>

Subdivision of Section 8,  
T. 1 N., R. 5 E., Gila and Salt River Meridian, Arizona

CHAINS	
	<p>Deposit a magnet, in a white plastic case, at the base of the drill hole.</p> <p>Cor. is located on the manmade right bank of the Salt River, 25 ft. high, 15 ft. wide, bears NE and SW.</p> <p>Thence, descending into active channel of the Salt River.</p>
20.18	<p>Point for the SW 1/16 sec. cor. of sec. 8, at intersection with the E. and W. center line of sec. 8, falls in the active channel of the Salt River, there is no remaining evidence of the 1962 monument or accessories. Not monumented.</p>
20.76	<p>Intersect the S. bdy. of the SRPMIC, hereinafter described.</p> <p>Continuing measurement, leaving the SRPMIC.</p>
31.01	<p>Point selected for a witness point.</p> <p>Set a brass tablet, 3 1/4 ins. diam., 3 1/2 ins. stem, cemented in a drill hole, with brass cap mkd.</p> <div style="text-align: center;"> <p>W P</p> <p>T 1 N R 5 E</p> <p>W</p> <p> </p> <p>S 8</p> <p>W</p> <p>2010</p> </div> <p>Deposit a magnet, in a white plastic case, at the base of the drill hole.</p> <p>Cor. is located on the manmade left bank of the Salt River, 25 ft. high, 15 ft. wide, bears N. 60° E. and S. 60° W.</p> <p>Continuing measurement, across State Route No. 202.</p>
40.36	<p>The point for the W. 1/16 sec. cor. of secs. 8 and 17, hereinbefore described.</p> <hr/> <p>From the point for the S. 1/16 sec. cor. of secs. 7 and 8, hereinbefore described.</p> <p>S. 89°43' E., on the E. and W. center line of the SW 1/4 of sec. 8.</p> <p>Over bed of the Salt River, within the SRPMIC</p>
10.295	<p>Point for the C-W-SW 1/64 sec. cor. of sec. 8, falls in the active channel of the Salt River, there is no remaining evidence of the 1962 monument or accessories. Not monumented.</p>

**Subdivision of Section 8,  
T. 1 N., R. 5 E., Gila and Salt River Meridian, Arizona**

CHAINS	
20.59	The point for the SW 1/16 sec. cor. of sec. 8.
21.24	Intersect the S. bdy. of the SRPMIC, hereinafter described.  Continuing measurement, leaving the SRPMIC.
30.885	Point for the C-E-SW 1/64 sec. cor. of sec. 8, falls in the active channel of the Salt River, there is no remaining evidence of the 1962 monument or accessories. Not monumented.
34.69	Point selected for a witness point.  Set a brass tablet, 3 1/4 ins. diam., 3 1/2 ins. stem, cemented in a drill hole, flush with surface, with top mkd.  <div style="text-align: center;">           W P            T 1 N R 5 E            S 8            S ————— S            2010         </div> Deposit a magnet, in a white plastic case, at the base of the drill hole.  Cor. is located on the manmade left bank of the Salt River, 25 ft. high, 15 ft. wide, bears NE and SW.  Continuing measurement, across State Route No. 202.
41.18	The center S. 1/16 sec. cor. of sec. 8, hereinbefore described.  <hr/> <div style="text-align: center;"> <b>Subdivision of Section 3, T. 1 N., R. 5 E., Gila and Salt River Meridian, Arizona</b> </div> <hr/> From the 1/4 sec. cor. of secs. 3 and 10, occupied with a brass disk, 3 ins. diam., seated in concrete, 5 ins. below the surface, set inside a 10 ins. diam., survey well, with top mkd. CITY OF MESA 19. This is accepted as the best available evidence of the cor., as described in the 1962 dependent resurvey.  Cor. is located at the intersection of Center Street, bearing N. and S., and McKellips Road, bearing E. and W., City of Mesa.  N. 0°29' E., on the N. and S. center line of sec. 3, within Center Street, across State Route No. 202.


**Subdivision of Section 3,  
T. 1 N., R. 5 E., Gila and Salt River Meridian, Arizona**

CHAINS	
39.96	<p>Point accepted, for center 1/4 sec. cor. of sec. 3, occupied with a brass disk, 3 ins. diam., seated in concrete, 6 ins. below the surface, set inside a 10 ins. diam., survey well, with top mkd. CITY OF MESA 19352. This is accepted as a careful and faithful determination of the cor. point.</p> <hr style="width: 20%; margin: 10px auto;"/> <p>N. 0°29' E., beginning new measurement.</p>
21.08	<p>Point for the center N. 1/16 sec. cor. of sec. 3, on the SRPMIC bdy., determined at the intersection of the extension of the bearing from the 1/4 sec. cor. of secs. 3 and 10 thru the center 1/4 sec. cor. of sec. 3, with the extension of the bearing from the N 1/16 sec. cor. of secs. 2 and 3 thru a lot cor. on the E. and W. center line of the NE 1/4 of sec. 3.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 28 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T 1 N R 5 E</p> <p style="text-align: center;"> <math display="block">\begin{array}{c} C \\ N\ 1/16 \quad   \quad S\ 3 \\ C \end{array}</math> </p> <p style="text-align: center;">2011</p> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p> <p>from which</p> <p style="padding-left: 40px;">A wooden power pole bears N. 10°01' E., 2.05 chs. dist.</p> <p style="padding-left: 40px;">A steel well head, 12 ins. diam., projecting 30 ins. above ground, bears S. 56°22' W., 34 lks. dist.</p> <p>From this cor. point, a rebar, 1/2 in. diam., firmly set, projecting 1 in. above ground, with attached plastic cap stamped SGS LS 33873, bears N. 78°12' W., 78 lks. dist.</p> <p>Cor. is located at the SW cor. of a closed landfill and at the northerly extension of Center Street, City of Mesa.</p> <hr style="width: 20%; margin: 10px auto;"/> <p>N. 2°18' W., beginning new measurement.</p> <p>Across a closed landfill, within the bed of the Salt River.</p>
21.40	<p>The 1/4 sec. cor. of sec. 3 only, hereinbefore described.</p> <hr style="width: 60%; margin: 10px auto;"/> <p>From the center 1/4 sec. cor. of sec. 3.</p>

Subdivision of Section 3,  
T. 1 N., R. 5 E., Gila and Salt River Meridian, Arizona

CHAINS	
	<p>S. 89°56' W., on the W. 1/2 of the E. and W. center line of sec. 3.</p> <p>Along a woven wire fence.</p>
10.79	<p>An aluminum disk, 3 ins. diam., set in concrete, with top mkd. A.D.O.T. HIGHWAY DIV. STP-600-8(802) 557 2002 25396.</p>
15.00	<p>An aluminum disk, 3 ins. diam., set in concrete, with top mkd. A.D.O.T. HIGHWAY DIV. STP-600-8(802) 504 2002 25396.</p>
17.44	<p>Intersect the 1972 survey of the S. bdy of the SRPMIC, at a point from which the computed point for AP 43, bears S. 65°54' W., 0.83 chs. dist.</p>
20.235	<p>Point for the center W. 1/16 sec. cor. of sec. 3, on the SRPMIC bdy.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 27 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T 1 N R 5 E</p> <p style="text-align: center;">W 1/16</p> <p style="text-align: center;">C ——— C</p> <p style="text-align: center;">S 3</p> <p style="text-align: center;">2010</p> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p> <p>Set a steel fence post, alongside and W. of the cor.</p> <p>Cor. is located on the N. side of a woven wire fence.</p> <p>Continuing measurement on the S. bdy. of the SRPMIC.</p>
20.76	<p>Point for a witness point, at intersection with the 1972 survey of the S. bdy. of the SRPMIC.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 27 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">W P</p> <p style="text-align: center;">T 1 N R 5 E</p> <p style="text-align: center;">SRPMIC</p> <p style="text-align: center;">S 3</p> <p style="text-align: center;">2010</p> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p>

Subdivision of Section 3,  
T. 1 N., R. 5 E., Gila and Salt River Meridian, Arizona

CHAINS	<p>Set a steel fence post, alongside and E. of the cor.</p> <p>From this cor. point, the computed point for AP 42, bears S. 41°59' E., 0.325 chs. dist.</p> <p>Continuing measurement, departing from the S. bdy. of the SRPMIC.</p>
40.47	<p>The 1/4 sec. cor. of secs. 3 and 4, hereinbefore described.</p> <hr style="width: 80%; margin: 10px auto;"/> <p style="text-align: center;">NE 1/4</p> <hr style="width: 80%; margin: 10px auto;"/> <p>From the point accepted for the N. 1/16 sec. cor. of secs. 2 and 3, monumented with a rebar, 1/2 in. diam., set flush with the surface of ground, of unknown origin.</p> <p>N. 89°48' W., on the E. and W. center line of the NW 1/4 of sec. 3.</p> <p>Within the City of Mesa.</p>
7.75	<p>A rebar, 1/2 in. diam., firmly set, projecting 4 ins. above ground, with attached plastic cap, stamped AZTEC RLS 25396, established by Alan D. Reece, Arizona R.L.S. No. 25396, in 2003, as per <i>Supplemental Result of Survey</i>, recorded in the Maricopa County Recorder's Office in book 650, page 46.</p> <p>Continuing measurement, within the City of Mesa, across State Route No. 202.</p>
29.41	<p>Point for an angle point, at intersection with the 1972 survey of the S. bdy. of the SRPMIC.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 27 ins. in the ground, in a collar of stone, with brass cap mkd.</p> <div style="text-align: center; margin: 10px 0;"> <p>T 1 N R 5 E</p> <p>SRPMIC</p> <p>AP</p>  <p>2011</p> </div> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p> <p>From this cor. point, the point for AP 51, bears S. 18°48' W., 4.77 chs. dist., determined at proportionate dist., by the method of grant boundary adjustment</p>



Subdivision of Section 3,  
T. 1 N., R. 5 E., Gila and Salt River Meridian, Arizona

CHAINS	
	<p>From this same cor. point, an iron pipe, 2 ins. diam., set in concrete, projecting 16 ins. above ground, with blank 2 1/2 ins. diam., brass cap bears N. 18°39' E., 46.5 lks. dist.</p> <p>Cor. is located 5 ft. S., of a barbed wire fence, bearing E. and W. and at the base of fill pile, about 30 ft. high.</p> <p>Continuing measurement on the S. bdy. of the SRPMIC.</p>
35.55	<p>From this point, a rebar 1/2 in. diam., firmly set, projecting 1 in. above ground, with attached plastic cap stamped GETTINGS RLS 27239, bears N., 28.5 lks. dist.</p>
39.63	<p>The center N. 1/16 sec. cor.</p> <hr style="width: 80%; margin: 10px auto;"/> <p style="text-align: center;">NW 1/4</p> <hr style="width: 80%; margin: 10px auto;"/> <p>From the center W. 1/16 sec. cor.</p> <p>N. 0°29' E., on the N. and S. center line of the NW 1/4 of sec. 3, parallel to the S 1/2 of the N 1/2 of the N. and S. center line of sec. 3, on the S. bdy. of the SRPMIC.</p> <p>Along the W. side of City of Mesa ware yard and police gun range.</p>
0.30	<p>Center of pavement, private access road for Arizona Dept. of Transportation and Arizona Dept. of Safety, 28 ft. wide, bears E. and W.</p>
0.55	<p>Woven wire fence, bears E. and W.</p>
21.08	<p>Point for the NW 1/16 sec. cor. of sec. 3, at intersection with a line from the center N. 1/16 sec. cor. of sec. 3, parallel with the W 1/2 of the E. and W. center line of sec. 3.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 20 ins. in the ground, in a mound of stone, 4 ft. base, to top, with brass cap mkd.</p> <p style="text-align: center;">T 1 N R 5 E SRPMIC NW 1/16 S 3</p> <p style="text-align: center;">2011</p> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p>

Subdivision of Section 3,  
T. 1 N., R. 5 E., Gila and Salt River Meridian, Arizona

CHAINS	
	<p>From this cor. point, a rebar, 1/2 in. diam., firmly set, projecting 1 in. above ground, with attached plastic cap stamped SGS LS 33873, bears S. 47°47' W., 36.5 lks. dist.</p> <p>From this same cor. point, an iron pipe, 2 ins. diam., set in concrete, projecting 12 ins. above ground, with blank 2 1/2 ins. diam., brass cap bears S. 68°27' W., 69.5 lks. dist.</p> <p>Cor. is located in overflow lands of the Salt River.</p> <hr style="width: 20%; margin: auto;"/> <p>N. 2°26' W., beginning new measurement.</p> <p>Across bed of the Salt River.</p>
20.82	<p>The point for the W. 1/16 sec. cor. of sec. 3, on the N. bdy. of the Tp., hereinbefore described.</p> <hr style="width: 60%; margin: auto;"/> <p>From the center N. 1/16 sec. cor. of sec. 3.</p> <p>S. 89°56' W., on the E. and W. center line of the NW 1/4 of sec. 3, parallel to the E 1/2 of the W 1/2 of the E. and W. center line of sec. 3.</p> <p>Along the N. side of City of Mesa, police gun range.</p>
0.61	<p>From this point, a cor. of woven wire fences, enclosing the City of Mesa, police gun range, bears S., 10 lks. dist., with fences extending S. and S. 89° W.</p>
4.89	<p>Intersect a woven wire fence, the northerly cor. bears N. 45° W., 9 lks. dist., thence S. 89° W., the southerly cor. bears S. 45° E., 23 lks. dist., thence N. 89° E.</p>
9.10	<p>Intersect same woven wire fence, bears N. 89° E. and S. 89° W.</p>
12.30	<p>From this point, a cor. of woven wire fences, enclosing the City of Mesa, police gun range, bears S., 5 lks. dist., with fences extending N. 89° E. and S. 32° W.</p>
20.235	<p>The NW 1/16 sec. cor. of sec. 3.</p> <hr style="width: 60%; margin: auto;"/> <p>S. 88°05' W., beginning new measurement.</p> <p>Across bed of the Salt River.</p>
20.80	<p>Point for the N. 1/16 sec. cor. of secs. 3 and 4, hereinbefore described.</p> <hr style="width: 60%; margin: auto;"/>

**Metes-and-Bounds Survey of the South Boundary  
of the Salt River Pima-Maricopa Indian Community,  
T. 1 N., R. 5 E., Gila and Salt River Meridian, Arizona**

CHAINS

**Metes-and-Bounds Survey of the South Boundary  
of the Salt River Pima-Maricopa Indian Community  
T. 1 N., R. 5 E., Gila and Salt River Meridian, Arizona**

---

Note: The following metes-and-bounds survey, complies with Public Law 95-399, which declared the south boundary of the SRPMIC *fixed and permanent and not ambulatory*. P.L. 95-399 accepted in part the 1972 survey of the S. bdy. of the SRPMIC, certain portions North of the 1972 survey that crossed patented lands were acquired via purchase or condemnations, other portions of the 1972 survey that infringed upon prior rights were declared null and void.

---

Restoring portions of the survey executed by  
Boyd S. Owens and Paul G. Bauer, in 1972

---

In sec. 7

From the witness point on the line bet. secs. 7 and 18, hereinbefore described.

N. 68°02' E., on a portion of line 10-11.

Within the channelized bed of the Salt River.

4.63 Point for the witness point, at intersection with the line bet. secs. 7 and 8, hereinbefore described.

From this cor. point, the cor. of secs. 7, 8, 17 and 18, bears S. 2°39' E., 1.74 chs. dist. hereinbefore described.

---

In sec. 8

N. 68°02' E., beginning new measurement, on a portion of line 10-11.

Within the channelized bed of the Salt River.

2.61 Point accepted for AP 11, occupied with an iron pin, 13 ins. long, 1/4 diam., set flush with the bed of the Salt River, underwater, 2 ft. deep, origin unknown. This is accepted as the best available evidence of the 1972 cor.

---

N. 45°14' E., on line 11-12.



**Metes-and-Bounds Survey of the South Boundary  
of the Salt River Pima-Maricopa Indian Community,  
T. 1 N., R. 5 E., Gila and Salt River Meridian, Arizona**

CHAINS	
4.11	<p>Point for AP 12, at proportionate dist., by the method of grant boundary adjustment, there is no remaining evidence of the 1972 monument or accessories. Not monumented.</p> <hr style="width: 20%; margin: 10px auto;"/> <p>N. 50°00' E., on line 12-13.</p>
4.25	<p>Point accepted for AP 13, occupied with an iron pin, 13 ins. long, 1/4 diam., set 3 ins. below the bed of the Salt River, underwater, 1 ft. deep, origin unknown. This is accepted as the best available evidence of the 1972 cor. Not monumented.</p> <hr style="width: 20%; margin: 10px auto;"/> <p>N. 43°57' E., on line 13-14.</p>
9.98	<p>Point accepted for AP 14, occupied with an iron pin, 13 ins. long, 1/4 diam., set 3 ins. below the bed of the Salt River, underwater, 1 ft. deep, origin unknown. This is accepted as the best available evidence of the 1972 cor. Not monumented.</p> <hr style="width: 20%; margin: 10px auto;"/> <p>N. 47°07' E., on line 14-15.</p>
5.79	<p>Intersect the N-S center line of the SW 1/4 of sec. 8, from which the point for the SW 1/16 sec. cor. of sec. 8, bears N. 3°00' W., 0.58 chs. dist., hereinbefore described.</p>
6.64	<p>Intersect the E-W center line of the SW 1/4 of sec. 8, from which the point for the SW 1/16 sec. cor. of sec. 8, bears N. 89°43' W., 0.65 chs. dist., hereinbefore described.</p>
11.51	<p>Point for AP 15, determined at proportionate dist., by the method of grant boundary adjustment, there is no remaining evidence of the 1972 monument or accessories. Not monumented.</p> <hr style="width: 20%; margin: 10px auto;"/> <p>N. 43°51' E., on line 15-16.</p>
10.91	<p>Point accepted for AP 16, reestablished by Christopher Edward Aulerich, Arizona R.L.S. No. 19809, monumented with a rebar, 1/2 in. diam., firmly set, projecting 1 in. above ground, with attached 1 in. diam., plastic cap stamped PLS 19809. This is accepted as a careful and faithful reestablishment of the orig. cor.</p> <p>Cor. is located on a sand bar, within the bed of the Salt River.</p> <hr style="width: 20%; margin: 10px auto;"/> <p>N. 46°08' E., on line 16-17.</p>

**Metes-and-Bounds Survey of the South Boundary  
of the Salt River Pima-Maricopa Indian Community,  
T. 1 N., R. 5 E., Gila and Salt River Meridian, Arizona**

CHAINS	
5.36	<p>Point for AP 17, at proportionate dist., by the method of grant boundary adjustment, there is no remaining evidence of the 1972 monument or accessories. Not monumented.</p> <hr style="width: 20%; margin: 10px auto;"/> <p>N. 41°44' E., on line 17-18.</p>
5.73	<p>Intersect the N-S center line of sec. 8, from which the point for the center 1/4 sec. cor. of sec. 8, bears N. 3°20' W., 88 lks. dist., hereinbefore described.</p>
6.90	<p>Intersect the E-W center line of sec. 8, from which the point for the center 1/4 sec. cor. of sec. 8, bears N. 89°44' W., 83 lks. dist., hereinbefore described.</p>
7.34	<p>Point for AP 18, at proportionate dist., by the method of grant boundary adjustment, there is no remaining evidence of the 1972 monument or accessories. Not monumented.</p> <hr style="width: 20%; margin: 10px auto;"/> <p>N. 50°41' E., on line 18-19.</p>
8.02	<p>Point for AP 19, at proportionate dist., by the method of grant boundary adjustment, there is no remaining evidence of the 1972 monument or accessories. Not monumented.</p> <hr style="width: 20%; margin: 10px auto;"/> <p>N. 49°49' E., on line 19-20.</p>
7.66	<p>Point accepted for AP 20, occupied with a rebar, 1/2 diam., set flush with the bed of the Salt River, underwater, 1 ft. deep, with a steel fence post, set alongside, origin unknown. This is accepted as the best available evidence of the 1972 cor.</p> <hr style="width: 20%; margin: 10px auto;"/> <p>N. 64°20' E., on line 20-21.</p>
8.80	<p>Stone berm, 10 ft. high, 4 ft. wide, bears N. and S.</p>
9.11	<p>The witness point, at intersection with the N. and S. center line of the NE 1/4 of sec. 8, hereinbefore described.</p> <p>From this cor. point, the point for AP 21, bears N. 64°20' E., 1.22 chs. dist., determined at proportionate dist., by the method of grant boundary adjustment, there is no remaining evidence of the 1972 monument or accessories. Not monumented.</p> <hr style="width: 20%; margin: 10px auto;"/> <p>From the witness point, at intersection with the E. and W. center line of the NE 1/4 of sec. 8, hereinbefore described.</p>

**Metes-and-Bounds Survey of the South Boundary  
of the Salt River Pima-Maricopa Indian Community,  
T. 1 N., R. 5 E., Gila and Salt River Meridian, Arizona**

CHAINS	
	<p>From this cor. point, the point for AP 23, bears S. 64°57' W., 2.06 chs. dist., determined at proportionate dist., by the method of grant boundary adjustment, there is no remaining evidence of the 1972 monument or accessories. Not monumented.</p> <p>N. 64°57' E., on a portion of line 23-24, identical with the S. bdy. of the SRPMIC.</p>
6.22	<p>Point accepted for AP 24, occupied with a rebar, 17 ins. long, 1/2 diam., firmly set, 6 ins. in the dry bed of the Salt River, origin unknown. This is accepted as the best available evidence of the 1972 cor.</p> <p>At the corner point</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 25 ins. in the ground, in a collar of stone, with brass cap mkd.</p> <div style="text-align: center;"> <p>T 1 N R 5 E SRPMIC AP 24</p>  </div> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p> <p>Deposit the rebar inside the stainless steel post.</p> <hr style="width: 20%; margin: 10px auto;"/>
1.575	<p>N. 74°47' E., on a portion of line 24-25.</p> <p>Point selected for a witness point.</p> <p>Set a brass tablet, 3 1/4 ins. diam., 3 1/2 ins. stem, cemented in a drill hole, flush with surface of a concrete slab, with top mkd.</p> <div style="text-align: center;"> <p>W P T 1 N R 5 E SRPMIC</p>  </div> <p>Deposit a magnet, in a white plastic case, at the base of the drill hole.</p> <p>Continuing measurement, underneath the Alma School Road bridge.</p>
4.17	<p>The witness point on the line bet. secs. 8 and 9, hereinbefore described.</p> <hr style="width: 60%; margin: 10px auto;"/>

**Metes-and-Bounds Survey of the South Boundary  
of the Salt River Pima-Maricopa Indian Community,  
T. 1 N., R. 5 E., Gila and Salt River Meridian, Arizona**

CHAINS	
	<p>Note: AP 25, 26, 28 and 29 in the NW 1/4 of sec. 9, set in the 1972 survey of the S. bdy. of the SRPMIC, were searched for and not found.</p> <hr/> <p style="text-align: center;"><u>In sec. 4</u></p> <p>From the witness point, at intersection with the S. bdy. of the SRPMIC, as surveyed in 1972, and the line bet. secs. 4 and 9, hereinbefore described.</p> <p>N. 63°36' E., on a portion of line 29-30, identical with the S. bdy. of the SRPMIC.</p>
1.10	Intersect the westerly edge of storage yard, for wooden wire spools, the most northerly cor. bears N. 35° E., 4.70 chs. dist., thence within storage yard
6.40	Intersect the northerly edge of storage yard, for wooden wire spools, the most northerly cor. bears N. 54° W., 2.50 chs. dist., thence exit storage yard.
7.20	Point for AP 30, at proportionate dist., by the method of grant boundary adjustment, there is no remaining evidence of the 1972 monument or accessories.
	<p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 27 ins. in the ground, in a collar of stone, with brass cap mkd.</p> <div style="text-align: center;"> <p style="margin: 0;">T 1 N R 5 E</p> <p style="margin: 0;">SRPMIC</p> <p style="margin: 0;">AP 30</p> <p style="margin: 0;">S4</p> <p style="margin: 0;">2010</p> </div>
	<p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p> <p>Set a steel fence post, alongside and NW of the cor.</p> <p>Cor. is located on a fill area, within the bed of the Salt River.</p> <hr/> <p>N. 53°26' E., on line 30-31.</p>
1.95	Southwesterly edge of McKellips Rd, bears S. 50° E. and N. 50° W.
3.20	Northeasterly edge of McKellips Rd, bears S. 50° E. and N. 50° W.

**Metes-and-Bounds Survey of the South Boundary  
of the Salt River Pima-Maricopa Indian Community,  
T. 1 N., R. 5 E., Gila and Salt River Meridian, Arizona**

CHAINS	
5.90	<p>Point for AP 31, at proportionate dist., by the method of grant boundary adjustment, there is no remaining evidence of the 1972 monument or accessories.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 20 ins. in the ground, seated in concrete, in a mound of stone, 3 1/2 ft. base, to top, with brass cap mkd.</p> <div style="text-align: center;"> </div> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p> <p>Set a steel fence post, alongside and NW of the cor.</p> <p>Cor. is located on a fill area, within the bed of the Salt River.</p> <hr style="width: 20%; margin: 10px auto;"/> <p>N. 24°44' E., on line 31-32.</p>
8.00	<p>Point selected for a witness point.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 22 ins. in the ground, in a collar of stone, with brass cap mkd.</p> <div style="text-align: center;"> </div> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p>
9.00	<p>Left man made bank of the Salt River, 15 ft. high, bears N. 60° E. and S. 60° W.</p> <p>Thence, descending into natural bed of the Salt River.</p>
10.20	<p>Point for AP 32, at proportionate dist., by the method of grant boundary adjustment, there is no remaining evidence of the 1972 monument or accessories. Not monumented.</p> <hr style="width: 20%; margin: 10px auto;"/> <p>N. 42°32' E., on line 32-33.</p>



**Metes-and-Bounds Survey of the South Boundary  
of the Salt River Pima-Maricopa Indian Community,  
T. 1 N., R. 5 E., Gila and Salt River Meridian, Arizona**

CHAINS	
11.51	<p>Point accepted for AP 33, reestablished by Gerald David Hughes, Arizona R.L.S. No. 15573, monumented with a rebar, 1/2 in. diam., firmly set, projecting 4 in. above ground, with attached 1 in. diam., plastic cap stamped RLS 15573. This is accepted as a careful and faithful reestablishment of the original corner. Not monumented.</p> <hr style="width: 20%; margin: 10px auto;"/> <p>N. 48°45' E., on line 33-34.</p>
6.57	<p>Point for AP 34, at proportionate dist., by the method of grant boundary adjustment, there is no remaining evidence of the 1972 monument or accessories. Not monumented.</p> <hr style="width: 20%; margin: 10px auto;"/> <p>N. 43°17' E., on line 34-35.</p>
4.99	<p>Point accepted for AP 35, reestablished by Gerald David Hughes, Arizona R.L.S. No. 15573, monumented with a rebar, 1/2 in. diam., firmly set, projecting 4 in. above ground, with attached 1 in. diam., plastic cap stamped RLS 15573. This is accepted as a careful and faithful reestablishment of the original corner.</p> <hr style="width: 20%; margin: 10px auto;"/> <p>N. 24°05' E., on line 35-36.</p>
11.48	<p>Point for AP 36, at proportionate dist., by the method of grant boundary adjustment, there is no remaining evidence of the 1972 monument or accessories. Not monumented.</p> <p>Found lying loose nearby, a rebar 18 ins. long, 1/2 in. diam., with attached 1 in. diam., plastic cap stamped RLS 15573.</p> <hr style="width: 20%; margin: 10px auto;"/> <p>N. 45°13' E., on line 36-37.</p>
7.48	<p>From this point, a brass disk, 3 ins. diam., stamped A.D.O.T. HIGHWAY DIV., cemented flush with the sidewalk on the Country Club Rd. bridge, bears N. 44°47' W., 3 lks. dist.</p>
12.50	<p>Point for AP 37, at proportionate dist., by the method of grant boundary adjustment, there is no remaining evidence of the 1972 monument or accessories. Not monumented.</p> <hr style="width: 20%; margin: 10px auto;"/> <p>S. 88°16' E., on line 37-38.</p>
2.89	<p>The witness point, on the line bet. secs. 3 and 4, hereinbefore described.</p> <hr style="width: 20%; margin: 10px auto;"/>


**Metes-and-Bounds Survey of the South Boundary  
of the Salt River Pima-Maricopa Indian Community,  
T. 1 N., R. 5 E., Gila and Salt River Meridian, Arizona**

CHAINS	
	<u>In sec. 3</u>
	S. 88°16' E., beginning new measurement.
14.08	Point accepted for AP 38, monumented with an iron post, 2 ins. diam., firmly set, in concrete, projecting 14 in. above ground, with a blank, 2 1/2 ins. diam., brass cap. Established by Mason L. Womble, Arizona R.L.S. No. 1757, as per an unrecorded <i>Result of Survey</i> , obtained from the SRPMIC Survey Dept. This is accepted as a careful and faithful reestablishment of the original corner.
	Mark the brass cap to read:
	S. 43°40' E., on line 38-39.
1.20	Manmade left bank of the Salt River, 6 ft. high, bears S. 75° E. and N. 75° W.; thence over fill area.
4.85	Point for AP 39, at proportionate dist., by the method of irregular boundary adjustment, there is no remaining evidence of the 1972 monument or accessories.
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 27 ins. in the ground, with brass cap mkd.
	Deposit a magnet, in a white plastic case, at the base of the stainless steel post.
	Raise a mound of stone 3 1/2 ft. base, 1 1/2 ft. high, E. of the cor.
	Set a steel fence post, alongside and SSE of the cor.
	S. 16°48' E., on line 39-40.

**Metes-and-Bounds Survey of the South Boundary  
of the Salt River Pima-Maricopa Indian Community,  
T. 1 N., R. 5 E., Gila and Salt River Meridian, Arizona**

CHAINS	
<p>2.05</p>	<p>Point accepted for AP 41, monumented with an iron post, 2 ins. diam., severed flush with the ground, set, in concrete. Established by Mason L. Womble, Arizona R.L.S. No. 1757, as per an unrecorded <i>Result of Survey</i>, obtained from the SRPMIC Survey Dept. This is accepted as a careful and faithful reestablishment of the orig. cor.</p> <p>Drive a stainless steel rod, 12 ins. long, 1/2 in. diam., 12 ins. inside of the severed iron post, with brass cap mkd.</p> <div style="text-align: center;"> <p>T 1 N R 5 E SRPMIC S 3 AP 40 2010</p> </div> <p>Cor. is located N. 50° E., 5.5 lks. dist., from a fence corner, with woven wire fences (enclosing A.D.O.T., storage yard), bearing S. and W.</p> <hr style="width: 20%; margin: 10px auto;"/> <p>S. 2°47' E., on line 40-41.</p>
<p>3.18</p>	<p>Point accepted for AP 41, monumented with an iron post, 2 ins. diam., firmly set, in concrete, projecting 12 in. above ground, with a blank, 2 1/2 ins. diam., brass cap. Established by Mason L. Womble, Arizona R.L.S. No. 1757, as per an unrecorded <i>Result of Survey</i>, obtained from the SRPMIC Survey Dept. This is accepted as a careful and faithful reestablishment of the orig. cor.</p> <p>Mark the brass cap to read:</p> <div style="text-align: center;"> <p>T 1 N R 5 E SRPMIC S3 AP 41 2010</p> </div> <p>Cor. is located 4 lks. W., of a woven wire fence, bears N. and S.</p> <hr style="width: 20%; margin: 10px auto;"/> <p>S. 41°59' E., on a rotated bearing, holding as fixed, the record interior angle.</p>
<p>1.91</p>	<p>Woven wire fence, bears E. and W.</p>
<p>2.25</p>	<p>Center of pavement, private drive, bears E. and W.</p>
<p>2.625</p>	<p>Point for a witness point, at intersection with the E. and W. center line of sec. 3, hereinbefore described.</p>

**Metes-and-Bounds Survey of the South Boundary  
of the Salt River Pima-Maricopa Indian Community,  
T. 1 N., R. 5 E., Gila and Salt River Meridian, Arizona**

CHAINS	<p>Note: AP 42 to AP 51 on the S. bdy. of the SRPMIC in sec. 3, as surveyed in 1972 where searched for and not found.</p> <hr/> <p>From the angle point, on the E. and W. center line of the NE 1/4 of sec. 3, hereinbefore described.</p> <p>N. 18°48' E., identical with a portion of line 51-52 of the 1972 survey of the S. bdy. of the SRPMIC.</p> <p>Across closed Tri-City landfill.</p> <p>9.245 Point accepted for AP 52, monumented with an iron post, 2 ins. diam., firmly set, in concrete, projecting 16 in. above ground, with a blank, 2 1/2 ins. diam., brass cap. Established by Mason L. Womble, Arizona R.L.S. No. 1757, as per an unrecorded <i>Result of Survey</i>, obtained from the SRPMIC Survey Dept. This is accepted as a careful and faithful reestablishment of the orig. cor.</p> <p>Mark the brass cap to read:</p> <div style="text-align: center; margin: 10px 0;"> <p>T 1 N R 5 E</p>  </div> <hr/> <p>N. 28°31' E., on line 52-53.</p> <p>15.135 AP 53, on the N. bdy. of the Tp., hereinbefore described.</p> <hr/> <p style="text-align: center;">GENERAL DESCRIPTION</p> <hr/> <p>The area surveyed and resurveyed lies in and along the Salt River, adjacent to the City of Mesa. The south boundary of the SRPMIC is within the Salt River bed through the entire area surveyed. State Route No. 202, lies immediately south of the boundary,</p> <p>Sand and Gravel mining operations are located in the NW 1/4 of section 9, the NW 1/4 of section 8 and the SW 1/4 of the NE 1/4 of section 3. The mining operation in section 9 intrudes into the SW 1/4 of section 4, within the SRPMIC, occupying an area of approximately 15 acres.</p>
--------	---

**T. 1 N., R. 5 E., Gila and Salt River Meridian, Arizona**

CHAINS

The mean magnetic declination of 11° E. was derived from the United States Geological Survey computer program GEOMAG, utilizing the World Magnetic Model for Epoch 2005-2010 for the dates of survey.

---

**Description of the South Boundary  
of the Salt River Pima-Maricopa Indian Community  
T. 1 N., R. 5 E., Gila and Salt River Meridian, Arizona**

---

The following is for informational purposes only

---

Beginning at the point for the cor. of secs. 7, 12, 13 and 18, on the W. bdy. of the Tp.

thence S. 89°56' E., 41.28 chs. dist., on the line bet. secs. 7 and 18, to the 1/4 sec. cor. of secs. 7 and 18;

thence S. 89°56' E., 37.06 chs. dist., on the line bet. secs. 7 and 18, to the witness point on the line bet. secs. 7 and 18;

thence N. 68°02' E., 4.63 chs. dist., to the witness point on the line bet. secs. 7 and 8;

thence N. 68°02' E., 2.61 chs. dist., to Angle Point 11;  
thence N. 45°14' E., 4.11 chs. dist., to Angle Point 12;  
thence N. 50°00' E., 4.25 chs. dist., to Angle Point 13;  
thence N. 43°57' E., 9.98 chs. dist., to Angle Point 14;  
thence N. 47°07' E., 11.51 chs. dist., to Angle Point 15;  
thence N. 43°51' E., 10.91 chs. dist., to Angle Point 16;  
thence N. 46°08' E., 5.36 chs. dist., to Angle Point 17;  
thence N. 41°44' E., 7.34 chs. dist., to Angle Point 18;  
thence N. 50°41' E., 8.02 chs. dist., to Angle Point 19;  
thence N. 49°49' E., 7.66 chs. dist., to Angle Point 20;  
thence N. 64°20' E., 9.11 chs. dist., to the witness point on the North and South center line of the NE 1/4 of sec 8;

thence N. 1°17' W., 5.83 chs. dist., on the North and South center line of the NE 1/4 of sec. 8, to the NE 1/16 sec. cor. of sec. 8;

thence S. 89°54' E., 12.315 chs. dist., on the East and West center line of the NE 1/4 of sec 8, to the witness point on the East and West center line of the NE 1/4 of sec. 8

thence N. 64°57' E., 6.22 chs. dist., to Angle Point 24;  
thence N. 74°47' E., 4.17 chs. dist., to the witness point on the line bet. secs. 8 and 9;

## T. 1 N., R. 5 E., Gila and Salt River Meridian, Arizona

## CHAINS

thence N. 0°28' W., 6.40 chs. dist., on the line bet. secs. 8 and 9, to the N-N 1/64 sec. cor. of secs. 8 and 9;

thence N. 0°19' W., 10.095 chs. dist., on the line bet. secs. 8 and 9, to the cor. of secs. 4, 5, 8 and 9;

thence N. 89°50' E., 28.34 chs. dist., on the line bet. secs. 4 and 9, to the witness point on the line bet. secs. 4 and 9;

thence N. 63°36' E., 7.20 chs. dist., to Angle Point 30;  
 thence N. 53°26' E., 5.90 chs. dist., to Angle Point 31;  
 thence N. 24°44' E., 10.20 chs. dist., to Angle Point 32;  
 thence N. 42°32' E., 11.51 chs. dist., to Angle Point 33;  
 thence N. 48°45' E., 6.57 chs. dist., to Angle Point 34;  
 thence N. 43°17' E., 4.99 chs. dist., to Angle Point 35;  
 thence N. 24°05' E., 11.48 chs. dist., to Angle Point 36;  
 thence N. 45°13' E., 12.50 chs. dist., to Angle Point 37;  
 thence S. 88°16' E., 2.89 chs. dist., to the witness point on the line bet. secs. 3 and 4;

thence S. 88°16' E., 14.08 chs. dist., to Angle Point 38;  
 thence S. 43°40' E., 4.85 chs. dist., to Angle Point 39;  
 thence S. 16°48' E., 2.05 chs. dist., to Angle Point 40;  
 thence S. 2°47' E., 3.18 chs. dist., to Angle Point 41;  
 thence S. 41°59' E., 2.625 chs. dist., to the witness point on the East and West center line of sec. 3;

thence N. 89°56' E., 0.525 chs. dist., on the East and West centerline of sec. 3, to the center W. 1/16 sec. cor. of sec. 3;

thence N. 0°29' E., 21.08 chs. dist., on the North and South centerline of the NW 1/4 of sec. 3, to the NW 1/16 sec. cor. of sec. 3;

thence N. 89°56' E., 20.235 chs. dist., on the East and West centerline of NW 1/4 of sec. 3, to the center N. 1/16 sec. cor. of sec. 3;

thence S. 89°48' E., 10.22 chs. dist., on the East and West centerline of the NE 1/4 of sec. 3, to the witness point on the East and West centerline of the NE 1/4 of sec. 3;

thence N. 18°48' E., 9.245 chs. dist., to Angle Point 52;  
 thence N. 28°31' E., 15.135 chs. dist., to Angle Point 53, on the N. bdy. of the Tp.;

thence N. 88°18' E., 0.67 chs. dist., on the N. bdy. of the Tp., bet. sec. 3, T. 1 N., R. 5 E., sec. 34, T. 2 N., R. 5 E., to the E. 1/16 sec. cor. of sec. 34, T. 2 N., R. 5 E., only;



