

ORIGINAL

**UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT**

FIELD NOTES

OF THE

SURVEY OF THE SOUTH BOUNDARY,

THE EAST BOUNDARY

AND THE SUBDIVISIONAL LINES

TOWNSHIP 1 SOUTH, RANGE 18 EAST,

OF THE GILA AND SALT RIVER MERIDIAN,

IN THE STATE OF ARIZONA.

EXECUTED BY

Geoffrey A. Graham, Cadastral Surveyor

Under Special Instructions dated March 15, 2010, approved March 15, 2010, which provided for the surveys included under Group No. 1074, and assignment instructions dated March 15, 2010.

Survey commenced April 6, 2010

Survey completed June 7, 2010

INDEX DIAGRAM

TOWNSHIP 1 SOUTH RANGE 18 EAST
 GILA AND SALT RIVER MERIDIAN, ARIZONA

66 6 65 64	66 5 52 63	53 4 43 52	44 3 33 43	35 2 23 33	25 1 14 23
7 62 62	8 51 61	9 42 50	10 32 41	11 22 31	12 13 21
18 60 60	17 49 59	16 40 49	15 30 39	14 20 29	13 12 20
19 58 58	20 48 57	21 38 47	22 28 38	23 19 28	24 11 18
30 56 55	29 46 55	28 37 46	27 27 36	26 17 26	25 10 16
31 54 8	32 45 8	33 35 7	34 25 6	35 15 4	36 9 3

T. 1 S., R. 18 E., Gila and Salt River Meridian, Arizona

CHAINS

The following field notes describe the survey of the south boundary, the east boundary and the subdivisional lines, Township 1 South, Range 18 East, Gila and Salt River Meridian, Arizona.

The history of surveys pertaining to this survey is as follows:

Joe R. Salazar surveyed the west boundary, established the corner of Townships 1 South, 18 and 19 East, and the corner of Townships 1 and 2 South, Ranges 18 and 19 East, in 2001-2009. Geoffrey A. Graham resurveyed the baseline, concurrently under this same Group, in 2010.

The survey was executed in accordance with the specifications as set forth in the Manual of Surveying Instructions for the Survey of the Public Lands of the United States, 2009, and the Special Instructions dated March 15, 2010, for Group Number 1074, Arizona.

The true meridian direction and length of all lines were determined by real time kinematic global positioning system observations using Trimble Navigation 5700 and 5800 model receivers.

Geodetic control was derived from Electronic Control Corner Number 1, as recorded on Bureau of Land Management plat for this township dated October 29, 2009. The NAD 83 (CORS96) (EPOCH: 2009) geographic position of the southeast corner of the township, is as follows:

Latitude: 33°17'43.60" N. Longitude: 110°26'56.78" W.

The NAD 83 (CORS96) (EPOCH: 2009) geographic position of the Standard 1/4 section corner of section 34, Township 1 North, Range 17 East, is as follows:

Latitude: 33°22'44.10" N. Longitude: 110°33'27.41" W.

The mean magnetic declination is 10 1/2° E.

**Survey of the South Boundary,
T. 1 S., R. 18 E., Gila and Salt River Meridian, Arizona**

Beginning at the cor. of Tps. 1 and 2 S., Rs. 18 and 19 E., monumented with a stainless steel post, 2 1/2 ins. diam., firmly set, 1 in. below ground, with brass cap mkd. T1S R18E R19E S36 S31 S1 S6 T2S 2009. Add the marks 2010 to the brass cap.

S. 89°48' W., on the S. bdy. of the Tp., bet. secs. 1 and 36.

Over rolling to broken terrain.

Survey of the South Boundary,
T. 1 S., R. 18 E., Gila and Salt River Meridian, Arizona

CHAINS	
39.35	Dirt road, 24 ft. wide, bears N. 10° E. and S. 10° E.
40.00	Point for the 1/4 sec. cor. of secs. 1 and 36. Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., flush with the ground, underpinned with a steel fence post, 5 1/2 ft. long, with brass cap mkd. <div style="text-align: center;"> T 1 S R 18 E S 36 1/4 ——— S 1 T 2 S 2010 </div>
	Deposit a magnet, in a white plastic case, at the base of the stainless steel post.
	Cor. is located on the uphill side of a foot path bet. railroad and dirt road.
40.83	Center of Arizona Eastern railroad tracks, bears N. 20° E. and S. 20° W.
45.70	Indian Route 3, asphalt surfaced, 26 ft. wide, bears N. 10° E., curving E., and S. 10° W., curving E.
80.00	Point for the cor. of secs. 1, 2, 35 and 36. Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd. <div style="text-align: center;"> T 1 S R 18 E S 35 S 36 S 2 S 1 T 2 S 2010 </div>
	Deposit a magnet, in a white plastic case, at the base of the stainless steel post.
	Cor. is located on S. aspect of narrow ridge, bears S. 80° E. and N. 80° W.
	Land, broken desert. Soil, sandy loam. Timber, none; ; undergrowth, creosote, cats claw and Mormon Tea.
	----- S. 89°48' W., on the S. bdy., bet. secs. 2 and 35.

Survey of the South Boundary,
T. 1 S., R. 18 E., Gila and Salt River Meridian, Arizona

CHAINS	
	Over rolling to broken terrain.
40.00	Point for the 1/4 sec. cor. of secs. 2 and 35. Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 27 ins. in the ground, with brass cap mkd. <div style="text-align: center;"> T 1 S R 18 E S 35 1/4 ——— S 2 T 2 S 2010 </div>
	Deposit a magnet, in a white plastic case, at the base of the stainless steel post.
	Raise an accessory mound of stone 2 ft. base, 2 ft. high, N. of the cor.
56.00	Underground El Paso gas line with two track road alongside, bears S. 48° E. and N. 48° W.
74.15	Power line with newer wood posts, bears N. 20° E. and S. 20° W., approximately 30 lks. E. of abandoned power line of steel trellis posts.
75.20	Bladed road along power line, 12 ft. wide, bears N. 25° E. and S. 10° W.
80.00	Point for the cor. of secs. 2, 3, 34 and 35. Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd. <div style="text-align: center;"> T 1 S R 18 E S 34 S 35 S 3 S 2 T 2 S 2010 </div>
	Deposit a magnet, in a white plastic case, at the base of the stainless steel post.
	Raise an accessory mound of stone 2 ft. base, 2 ft. high, W. of the cor.

Survey of the South Boundary,
T. 1 S., R. 18 E., Gila and Salt River Meridian, Arizona

CHAINS	
	<p>Land, rolling desert. Soil, coarse sandy loam. Timber, scrub mesquite; undergrowth, creosote, cats claw, sotol and Mormon Tea.</p> <hr/> <p>S. 89°48' W., on the S. bdy., bet. secs. 3 and 34.</p> <p>Over rolling to broken terrain.</p>
40.00	<p>Point for the 1/4 sec. cor. of secs. 3 and 34.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 27 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center;"> <p>T 1 S R 18 E S 34 1/4 ——— S 3 T 2 S</p> <p>2010</p> </div> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p> <p>Raise an accessory mound of stone, 2 ft. base, 2 ft. high, N. of the cor.</p>
80.00	<p>Point for the cor. of secs. 3, 4, 33 and 34.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center;"> <p>T 1 S R 18 E S 33 S 34 ——— S 4 S 3 T 2 S</p> <p>2010</p> </div> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p> <p>Raise an accessory mound of stone, 2 ft. base, 2 ft. high, W. of the cor.</p> <p>Cor. is located on spur ridge, bears N. 30° E. and S. 30° W.</p>

Survey of the South Boundary,
T. 1 S., R. 18 E., Gila and Salt River Meridian, Arizona

CHAINS	
	<p>Land, rolling desert. Soil, coarse sandy loam. Timber, scrub mesquite and Palo Verde; undergrowth, creosote, cats claw, sotol and grasses.</p> <hr/> <p>S. 89°48' W., on the S. bdy., bet. secs. 4 and 33.</p> <p>Over rolling to broken terrain.</p>
40.00	<p>Point for the 1/4 sec. cor. of secs. 4 and 33.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 25 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center;"> <p>T 1 S R 18 E S 33 1/4 ——— S 4 T 2 S</p> <p>2010</p> </div> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p> <p>Raise an accessory mound of stone, 2 ft. base, 2 ft. high, N. of the cor.</p>
80.00	<p>Point for the cor. of secs. 4, 5, 32 and 33.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center;"> <p>T 1 S R 18 E S 32 S 33 S 5 S 4 T 2 S</p> <p>2010</p> </div> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p> <p>Raise an accessory mound of stone, 2 ft. base, 2 ft. high, W. of the cor.</p> <p>Land, rolling desert. Soil, coarse sandy loam. Timber, scrub mesquite; undergrowth, creosote, cats claw, sotol and Mormon Tea.</p> <hr/>

**Survey of the South Boundary,
T. 1 S., R. 18 E., Gila and Salt River Meridian, Arizona**

CHAINS	
	<p>S. 89°48' W., on the S. bdy., bet. secs. 5 and 32.</p> <p>Over rolling to broken terrain.</p>
40.00	<p>Point for the 1/4 sec. cor. of secs. 5 and 32.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T 1 S R 18 E S 32 1/4 ——— S 5 T 2 S</p> <p style="text-align: center;">2010</p> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p> <p>Raise an accessory mound of stone, 2 ft. base, 2 ft. high, N. of the cor.</p>
80.00	<p>Point for the cor. of secs. 5, 6, 31 and 32.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T 1 S R 18 E S 31 S 32 S 6 S 5 T 2 S</p> <p style="text-align: center;">2010</p> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p> <p>Raise an accessory mound of stone, 3 ft. base, 2 ft. high, W. of the cor.</p> <p>Cor. is located bet. courses of a shallow braided wash system, 5 chs. wide, generally drains S. 75° E.</p> <p>Land, rolling desert. Soil, coarse sandy loam. Timber, scrub mesquite; undergrowth, creosote, cats claw, sotol and Mormon Tea.</p> <hr/> <p>S. 89°48' W., on the S. bdy., bet. secs. 6 and 31.</p> <p>Over rolling to broken terrain.</p>


**Survey of the South Boundary,
T. 1 S., R. 18 E., Gila and Salt River Meridian, Arizona**

CHAINS	
40.00	<p>Point for the 1/4 sec. cor. of secs. 6 and 31.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 22 ins. in the ground, in a collar of stone, with brass cap mkd.</p> <p style="text-align: center;">T 1 S R 18 E S 31 1/4 ——— S 6 T 2 S</p> <p style="text-align: center;">2010</p> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p>
40.70	Trail road, 15 ft. wide, bears N. 35° E. and S. 35° W.
78.42	<p>The cor. of Tps. 1 and 2 S., Rs. 17 and 18 E., monumented with a stainless steel post, 2 1/2 ins. diam., firmly set, in a mound of stone 4 ft. base 1 1/2 high, with brass cap mkd. T1S R17E R18E S36 S31 S1 S6 T2S 2001. Add the marks 2010 to the brass cap.</p> <p>Land, rolling desert. Soil, coarse loam. Timber, scrub mesquite; undergrowth, creosote, cats claw, sotol and Mormon Tea.</p> <hr/> <p style="text-align: center;">Survey of the East Boundary, T. 1 S., R. 18 E., Gila and Salt River Meridian, Arizona</p> <hr/> <p>From the cor. of Tps. 1 and 2 S., Rs. 18 and 19 E., hereinbefore described.</p> <p>North, on the E. bdy., bet. secs. 31 and 36.</p> <p>Over the floodplain of the San Carlos River.</p>
2.05	U.S. Highway No. 70, asphalt surfaced, 34 ft. wide, bears S. 75° E. and N. 75° W.
40.00	<p>True point for the 1/4 sec. cor. of secs. 31 and 36; falls in the floodplain of the San Carlos River, where it is impracticable to establish a permanent monument.</p> <p>From this true point, the point selected for the witness cor. to the 1/4 sec. cor. of secs. 31 and 36, bears N. 53°27' W., 7.14 chs. dist.</p>

Survey of the East Boundary,
T. 1 S., R. 18 E., Gila and Salt River Meridian, Arizona

CHAINS

Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, in a collar of stone, with brass cap mkd.



Deposit a magnet, in a white plastic case, at the base of the stainless steel post.


Raise an accessory mound of stone 2 ft. base, 2 ft. high, W. of the cor.

Cor. is located bet. a fence, bears S. 20° E. and N. 20° W. and rip rap on the right bank of the San Carlos River, bears N 10° E. and S. 10° W.

80.00 True point for the cor. of secs. 25, 30, 31 and 36; falls in the San Carlos floodplain, where it is impracticable to establish a permanent monument.

From the true point, the point selected for a witness cor. to cor. of secs. 25, 30, 31, and 36, bears N. 59°38' W., 8.94 chs. dist.

Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.



Deposit a magnet, in a white plastic case, at the base of the stainless steel post.

Cor. is located 36 lks. W. of rip rap for the floodplain of the San Carlos River

Land, floodplain.

Soil, coarse sandy loam.


Timber, persimmon and cottonwood; undergrowth, grasses.

North, on the E. bdy., bet. secs. 25 and 30.

Survey of the East Boundary,
T. 1 S., R. 18 E., Gila and Salt River Meridian, Arizona

CHAINS	
	Over the floodplain of the San Carlos River.
40.00	Point for the 1/4 sec. cor. of secs. 25 and 30. Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, in a collar of stone, underpinned with a 5 1/2 ft. steel fence post, with brass cap mkd. <div style="text-align: center;"> T 1 S R 18 E R 19 E 1/4 S 25 S 30 2010 </div>
	Deposit a magnet, in a white plastic case, at the base of the stainless steel post.
80.00	Point for the cor. of secs. 19, 24, 25 and 30. Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 22 ins. in the ground, in a collar of stone, with brass cap mkd. <div style="text-align: center;"> T 1 S R 18 E R 19 E S 24 S 19 S 25 S 30 2010 </div>
	Deposit a magnet, in a white plastic case, at the base of the stainless steel post.
	Raise an accessory mound of stone 3 ft. base, 2 ft. high, N. of the cor.
	Land, floodplain. Soil, coarse sandy loam. Timber, persimmon and cottonwood; undergrowth, grasses.
	North, on the E. bdy., bet. secs. 19 and 24.
	Over the floodplain of the San Carlos River.
40.00	Point for the 1/4 sec. cor. of secs. 19 and 24. Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 27 ins. in the ground, with brass cap mkd.


Survey of the East Boundary,
T. 1 S., R. 18 E., Gila and Salt River Meridian, Arizona

CHAINS	
80.00	<div style="text-align: center; margin-bottom: 10px;"> T 1 S R 18 E R 19 E 1/4 S 24 S 19 </div> <p style="text-align: center;">2010</p> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p> <p>Raise an accessory mound of stone 3 ft. base, 2 ft. high, W. of the cor. and set a steel "T-post" fence post near the cor.</p> <p>True point for the cor. of secs. 13, 18, 19 and 24; falls in the San Carlos floodplain, where it is impracticable to establish a permanent monument.</p> <p>From the true point, the point selected for a witness cor. to cor. of secs. 13, 18, 19, and 24, bears S. 34°16' W., 4.03 chs. dist.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with brass cap mkd.</p>
40.00	<div style="text-align: center; margin-bottom: 10px;"> WC T 1 S R 18 E R 19 E S 13 S 18 S 24 S 19  </div> <p style="text-align: center;">2010</p> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p> <p>Land, floodplain. Soil, coarse sandy loam. Timber, persimmon and cottonwood; undergrowth, grasses.</p> <hr style="width: 80%; margin: 10px auto;"/> <p>North, on the E. bdy., bet. secs. 13 and 18.</p> <p>Over the floodplain of the San Carlos River.</p> <p>True point for the 1/4 sec. cor. of secs. 13 and 18; falls in the floodplain of the San Carlos River, where it is impracticable to establish a permanent monument.</p> <p>From this true point, the point selected for the witness cor. to the 1/4 sec. cor. of secs. 13 and 18, bears N. 78°37' W., 6.18 chs. dist.</p>

Survey of the East Boundary,
T. 1 S., R. 18 E., Gila and Salt River Meridian, Arizona

CHAINS	
	<p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 27 ins. in the ground, in a collar of stone, with brass cap mkd.</p> <div style="text-align: center;"> <p>WC T 1 S R 18 E R 19 E 1/4 S 13 S 18 ↘ 2010</p> </div> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p> <p>Cor. is located on private property, with consent of owner, Tom Kinney, W. of driveway.</p>
80.00	<p>Point for the cor. of secs. 7, 12, 13 and 18.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 27 ins. in the ground, in a collar of stone, with brass cap mkd.</p> <div style="text-align: center;"> <p>T 1 S R 18 E R 19 E S 12 S 7 S 13 S 18 2010</p> </div> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p> <p>Set a steel "T-post" fence post near the cor.</p> <p>Cor. is located on the W. side of a 16 ft. wide, dirt road, bears N 20° E and S. 20° W.</p> <p>Land, rolling. Soil, coarse sandy loam. Timber, persimmon and cottonwood; undergrowth, grasses.</p> <hr/> <p>North, on the E. bdy., bet. secs. 7 and 12.</p> <p>Over gently rolling terrain.</p>
40.00	<p>True point for the 1/4 sec. cor. of secs. 7 and 12; falls in the floodplain of the San Carlos River, where it is impracticable to establish a permanent monument.</p> <p>From this true point, the point selected for the witness cor. to the 1/4 sec. cor. of secs. 7 and 12, bears S. 59°45' W., 10.58 chs. dist.</p>

Survey of the East Boundary,
T. 1 S., R. 18 E., Gila and Salt River Meridian, Arizona


CHAINS									
	<p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, in a collar of stone, with brass cap mkd.</p> <div style="text-align: center; margin: 10px 0;"> <p>WC T 1 S R 18 E R 19 E 1/4 S 12 S 7</p>  <p>2010</p> </div> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p> <p>Raise an accessory mound of stone 2 ft. base, 1 ft. high, W. of the cor.</p>								
80.00	<p>Point for the cor. of secs. 1, 6, 7 and 12.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., flush with the ground, with brass cap mkd.</p> <div style="text-align: center; margin: 10px 0;"> <table style="margin: auto; border-collapse: collapse;"> <tr> <td colspan="2" style="text-align: center;">T 1 S</td> </tr> <tr> <td style="border-right: 1px solid black; padding: 0 5px;">R 18 E</td> <td style="padding: 0 5px;">R 19 E</td> </tr> <tr> <td style="border-right: 1px solid black; padding: 0 5px;">S 1</td> <td style="padding: 0 5px;">S 6</td> </tr> <tr> <td style="border-right: 1px solid black; padding: 0 5px;">S 12</td> <td style="padding: 0 5px;">S 7</td> </tr> </table> <p>2010</p> </div> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p> <p>Cor. is located in a small horse pasture, behind the Baily Family house.</p> <p>Land, floodplain. Soil, coarse sandy loam. Timber, persimmon and cottonwood; undergrowth, grasses.</p> <hr style="width: 60%; margin: 10px auto;"/> <p>North, on the E. bdy., bet. secs. 1 and 6.</p> <p>Over gently rolling terrain.</p>	T 1 S		R 18 E	R 19 E	S 1	S 6	S 12	S 7
T 1 S									
R 18 E	R 19 E								
S 1	S 6								
S 12	S 7								
36.70	<p>Right bank of the Seven Mile Wash, 5 ft. deep, bears S. 30° E. and N. 30° W.</p>								
40.00	<p>True point for the 1/4 sec. cor. of secs. 1 and 6; falls in the Seven Mile Wash, where it is impracticable to establish a permanent monument.</p>								

**Survey of the East Boundary,
T. 1 S., R. 18 E., Gila and Salt River Meridian, Arizona**

CHAINS

From this true point, the point selected for the witness cor. to the 1/4 sec. cor. of secs. 1 and 6, bears N. 54°03' W., 3.96 chs. dist.

Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 27 ins. in the ground, in a collar of stone, with brass cap mkd.



Deposit a magnet, in a white plastic case, at the base of the stainless steel post.

Set a steel "T-post" fence post near the cor.

47.75 Bridge over Seven Mile Wash, 40 ft. wide, bears N. 35° E. and S. 35° W.

48.85 Left bank of the Seven Mile Wash, 5 ft. deep, bears S. 30° E. and N. 30° W.

60.32 The closing cor. of Tps. 1 S., Rs. 18 and 19 E., monumented with a stainless steel post, 2 1/2 ins. diam., firmly set, projecting 4 ins. above the ground, with brass cap mkd. T1N R18E S34 S1 S6 R18E R19E CC 2009. Add the marks 2010 to the brass cap.

From this cor. the stan. cor. of secs. 34 and 35, T. 1 N., R. 18 E., bears S. 89°58' E., 18.12 chs. dist., monumented with an iron post, 3 ins. diam., projecting 14 ins. above the ground, in a supporting mound of stone, 4 ft. base, 1 ft. high, with brass cap mkd. SC T1N R18E S34 S35 1915 2010 2009.

From this same cor. the stan. 1/4 sec. cor. of sec. 34, T. 1 N., R. 18 E., bears N. 89°58' W., 21.89 chs. dist., monumented with stainless steel post, 2 1/2 ins. diam., set flush with the ground, in a collar of stone, with brass cap mkd. SC T1N R18E 1/4 S34 2010.

**Survey of the Subdivisional Lines,
T. 1 S., R. 18 E., Gila and Salt River Meridian, Arizona**

From the cor. of secs. 1, 2, 35 and 36, on the S. bdy. of the Tp., hereinbefore described.

N. 0°01' W., bet. secs. 35 and 36.

Over rolling to broken terrain.

Survey of the Subdivisional Lines,
T. 1 S., R. 18 E., Gila and Salt River Meridian, Arizona

CHAINS	
27.40	U.S. Highway No. 70, asphalt surfaced, 38 ft. wide, bears S. 75° E. and N. 75° W.
40.00	Point for the 1/4 sec. cor. of secs. 35 and 36. Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 27 ins. in the ground, with brass cap mkd. <div style="text-align: center;"> T 1 S R 18 E 1/4 S 35 S 36 2010 </div> Deposit a magnet, in a white plastic case, at the base of the stainless steel post. Raise an accessory mound of stone 2 ft. base, 2 ft. high, W. of the cor.
80.00	Point for the cor. of secs. 25, 26, 35 and 36. Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 20 ins. in the ground, in a supporting mound of stone, 4 ft. base, to top, with brass cap mkd. <div style="text-align: center;"> T 1 S R 18 E S 26 S 25 S 35 S 36 2010 </div> Deposit a magnet, in a white plastic case, at the base of the stainless steel post. Land, rolling to broken. Soil, clay loam and limestone. Timber, palo negro; undergrowth, creosote, Mormon Tea and sage.
	<hr/> From the true point for the cor. of secs. 25, 30, 31 and 36, on the E. bdy. of the Tp., hereinbefore described. S. 89° 48' W., bet. secs. 25 and 36. Over rolling terrain.
24.70	Center of Arizona Eastern railroad tracks, bears N. 2° E. and S. 2° W.
27.00	Indian Route No. 170, asphalt surfaced, 36 ft. wide, bears S. 5° E. and N. 5° W.

Survey of the Subdivisional Lines,
T. 1 S., R. 18 E., Gila and Salt River Meridian, Arizona

CHAINS	
40.00	<p>Point for the 1/4 sec. cor. of secs. 25 and 36.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, in a collar of stone, with brass cap mkd.</p> <div style="text-align: center; margin: 10px 0;"> T 1 S R 18 E S 25 1/4 ——— S 36 </div> <p style="text-align: center; margin: 10px 0;">2010</p> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p>
80.00	<p>The cor. of secs. 25, 26, 35 and 36.</p> <p>Land, rolling to broken. Soil, sandy loam. Timber, palo negro; undergrowth, creosote, Mormon Tea and sage.</p> <hr style="width: 80%; margin: 10px auto;"/> <p>N. 0°01' W., bet. secs. 25 and 26.</p> <p>Over rolling terrain.</p>
40.00	<p>True point for the 1/4 sec. cor. of secs. 25 and 26; falls in bed of meandering wash system, 130 ft. wide, drains S. from N. 50° W., where it is impracticable to establish a permanent monument.</p> <p>From this true point, the point selected for the witness cor. to the 1/4 sec. cor. of secs. 25 and 26, bears N. 53°58' W., 2.18 chs. dist.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 16 ins. in the ground, in a mound of stone, 3 ft. base, to top, with brass cap mkd.</p> <div style="text-align: center; margin: 10px 0;"> WC T 1 S R 18 E 1/4 S 26 S 25 ↘ 2010 </div> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p> <p>Witness cor. is located on a flat spur, bears E. and W.</p>
80.00	<p>Point for the cor. of secs. 23, 24, 25 and 26.</p>

Survey of the Subdivisional Lines,
T. 1 S., R. 18 E., Gila and Salt River Meridian, Arizona

CHAINS									
	<p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center;"> <table style="margin: auto;"> <tr> <td colspan="2">T 1 S R 18 E</td> </tr> <tr> <td style="border-right: 1px solid black; padding: 0 5px;">S 23</td> <td style="padding: 0 5px;">S 24</td> </tr> <tr> <td style="border-right: 1px solid black; padding: 0 5px;">S 26</td> <td style="padding: 0 5px;">S 25</td> </tr> </table> <p>2010</p> </div> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p> <p>Raise an accessory mound of stone 3 ft. base, 2 ft. high, W. of the cor.</p> <p>Land, rolling to broken. Soil, loam. Timber, mesquite and palo negro; undergrowth, creosote, Mormon Tea and sage.</p> <hr style="width: 50%; margin: 10px auto;"/> <p>From the cor. of secs. 19, 24, 25 and 30, on the E. bdy. of the Tp., hereinbefore described.</p> <p>S. 89°48' W., bet. secs. 24 and 25.</p> <p>Over rolling to broken terrain.</p>	T 1 S R 18 E		S 23	S 24	S 26	S 25		
T 1 S R 18 E									
S 23	S 24								
S 26	S 25								
5.75	Center of Arizona Eastern railroad tracks, bears N. 2° E. and S. 2° W.								
7.90	Indian Route No. 170, asphalt surfaced, 48 ft. wide, bears S. 20° E. and N. 20° W.								
40.00	<p>Point for the 1/4 sec. cor. of secs. 24 and 25.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 14 ins. in the ground, in a supporting mound of stone, 3 ft. base, to top, with brass cap mkd.</p> <div style="text-align: center;"> <table style="margin: auto;"> <tr> <td colspan="2">T 1 S R 18 E</td> </tr> <tr> <td colspan="2">S 24</td> </tr> <tr> <td style="padding-right: 10px;">1/4</td> <td style="border-top: 1px solid black; width: 50px;"></td> </tr> <tr> <td colspan="2">S 25</td> </tr> </table> <p>2010</p> </div> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p>	T 1 S R 18 E		S 24		1/4		S 25	
T 1 S R 18 E									
S 24									
1/4									
S 25									
80.00	The cor. of secs. 23, 24, 25 and 26.								

Survey of the Subdivisional Lines,
T. 1 S., R. 18 E., Gila and Salt River Meridian, Arizona

CHAINS	
	<p>Land, rolling to broken. Soil, rocky loam. Timber, mesquite; undergrowth, creosote, Mormon Tea and sage.</p> <hr/> <p>N. 0°01' W., bet. secs. 23 and 24.</p> <p>Over rolling to broken terrain.</p>
0.35	Trail road to Telephone Tank, bears S. 70° E. and N. 60° W.
39.20	High voltage transmission line, poles transition from single pole to 3 pole over canyon, bears N. 20° E. and S. 20° W.; A dirt road, 10 ft. wide, runs parallel on the west side of transmission line.
40.00	<p>Point for the 1/4 sec. cor. of secs. 23 and 24.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 20 ins. in the ground, in a mound of stone, 3 ft. base, to top, with brass cap mkd.</p> <div style="text-align: center;"> <p>T 1 S R 18 E 1/4 S 23 S 24</p> <p>2010</p> </div> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p> <p>Raise an accessory mound of stone 3 ft. base, 2 ft. high, W. of the cor.</p>
80.00	<p>Point for the cor. of secs. 13, 14, 23 and 24.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 23 ins. in the ground, in a collar of stone, with brass cap mkd.</p> <div style="text-align: center;"> <p>T 1 S R 18 E S 14 S 13 S 23 S 24</p> <p>2010</p> </div> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p> <p>Raise an accessory mound of stone 2 ft. base, 2 ft. high, W. of the cor.</p>

Survey of the Subdivisional Lines,
T. 1 S., R. 18 E., Gila and Salt River Meridian, Arizona

CHAINS	
	<p>Land, rolling to broken. Soil, clay loam. Timber, mesquite; undergrowth, creosote.</p> <hr/> <p>From the true point for the cor. of secs. 13, 18, 19 and 24, on the E. bdy. of the Tp., hereinbefore described.</p> <p>S. 89°48' W., bet. secs. 13 and 24.</p> <p>Over rolling terrain.</p>
5.10	Center of Arizona Eastern railroad tracks, bears N. 5° E. and S. 5° W.
10.10	Indian Route No. 170, asphalt surfaced, 34 ft. wide, bears N. 40° E. and S. 40° W.
40.00	<p>Point for the 1/4 sec. cor. of secs. 13 and 24.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 23 ins. in the ground, in a collar of stone, with brass cap mkd.</p> <div style="text-align: center;"> <p>T 1 S R 18 E</p> <p>S 13</p> <p>1/4 ———</p> <p>S 24</p> <p>2010</p> </div> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p> <p>Raise an accessory mound of stone 2 ft. base, 2 ft. high, N. of the cor.</p>
64.20	Graded road, 10 ft. wide, bears N. 20° E. and S. 20° W.
64.65	High voltage transmission line, bears N. 20° E. and S. 20° W.
80.00	The cor. of secs. 13, 14, 23 and 24.
	<p>Land, rolling to broken. Soil, clay loam. Timber, mesquite; undergrowth, creosote.</p> <hr/> <p>N. 0°01' W., bet. secs. 13 and 14.</p> <p>Over rolling terrain.</p>
40.00	Point for the 1/4 sec. cor. of secs. 13 and 14.

Survey of the Subdivisional Lines,
T. 1 S., R. 18 E., Gila and Salt River Meridian, Arizona

CHAINS	
	<p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 25 ins. in the ground, in a collar of stone, with brass cap mkd.</p> <p style="text-align: center;">T 1 S R 18 E 1/4 S 14 S 13</p> <p style="text-align: center;">2010</p> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p> <p>Raise an accessory mound of stone 2 ft. base, 2 ft. high, W. of the cor.</p>
64.35	Center of Arizona Eastern railroad tracks, bears S. 64° E. and N. 64° W.
80.00	<p>Point for the cor. of secs. 11, 12, 13 and 14.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, in a collar of stone, with brass cap mkd.</p> <p style="text-align: center;">T 1 S R 18 E S 11 S 12 S 14 S 13</p> <p style="text-align: center;">2010</p> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p> <p>Land, rolling to broken. Soil, loam. Timber, mesquite; undergrowth, creosote.</p> <hr/> <p>From the cor. of secs. 7, 12, 13 and 18, on the E. bdy. of the Tp., hereinbefore described.</p> <p>S. 89°48' W., bet. secs. 12 and 13.</p> <p>Over rolling to broken terrain.</p>
35.00	Enter cemetery.
40.00	<p>True point for the 1/4 sec. cor. of secs. 12 and 13; falls in an unmarked grave, where it is disrespectful to establish a permanent monument.</p> <p>From this true point, the point selected for the witness cor. to the 1/4 sec. cor. of secs. 12 and 13, bears S. 67°30' W., 2.62 chs. dist.</p>

Survey of the Subdivisional Lines,
T. 1 S., R. 18 E., Gila and Salt River Meridian, Arizona

CHAINS	
	<p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">WC T 1 S R 18 E S 12 1/4 ———→ S 13</p> <p style="text-align: center;">2010</p> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p> <p>From the true point for the 1/4 sec. cor. of secs. 12 and 13, a brass tablet, in concrete, mkd. SAN CARLOS 2688.42, bears S. 74°39' E., 5.43 chs. dist.</p>
47.60	Leave cemetery.
76.90	Indian Route No. 6, asphalt surfaced, 26 ft. wide, bears S. 60° E. and N. 60° W.
80.00	The cor. of secs. 11, 12, 13 and 14. Land, rolling to broken. Soil, loam. Timber, mesquite and palo negro; undergrowth, creosote.
	<hr/> <p>N. 0°01' W., bet. secs. 11 and 12.</p> <p>Over rolling terrain.</p>
1.85	Indian Route No. 6, asphalt surfaced, 26 ft. wide, bears S. 60° E. and N. 60° W.
40.00	<p>Point for the 1/4 sec. cor. of secs. 11 and 12.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 23 ins. in the ground, in a collar of stone, with brass cap mkd.</p> <p style="text-align: center;">T 1 S R 18 E 1/4 S 11 S 12</p> <p style="text-align: center;">2010</p> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p> <p>Raise an accessory mound of stone 3 ft. base, 1 ft. high, W. of the cor.</p>

Survey of the Subdivisional Lines,
T. 1 S., R. 18 E., Gila and Salt River Meridian, Arizona

CHAINS									
80.00	<p>Point for the cor. of secs. 1, 2, 11 and 12.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center;"> <table style="margin: auto;"> <tr><td>T 1 S</td><td>R 18 E</td></tr> <tr><td>S 2</td><td>S 1</td></tr> <tr><td>S 11</td><td>S 12</td></tr> </table> <p>2010</p> </div> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p> <p>Raise an accessory mound of stone 2 ft. base, 2 ft. high, N. of the cor.</p> <p>Land, rolling to broken. Soil, loam. Timber, mesquite; undergrowth, creosote.</p> <hr/> <p>From the cor. of secs. 1, 6, 7 and 12, on the E. bdy. of the Tp., hereinbefore described.</p> <p>S. 89°48' W., bet. secs. 1 and 12.</p> <p>Over rolling to broken terrain.</p>	T 1 S	R 18 E	S 2	S 1	S 11	S 12		
T 1 S	R 18 E								
S 2	S 1								
S 11	S 12								
40.00	<p>Point for the 1/4 sec. cor. of secs. 1 and 12.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 22 ins. in the ground, in a mound of stone, 3 ft. base, to top, with brass cap mkd.</p> <div style="text-align: center;"> <table style="margin: auto;"> <tr><td>T 1 S</td><td>R 18 E</td></tr> <tr><td>S 1</td><td></td></tr> <tr><td>1/4</td><td>—</td></tr> <tr><td>S 12</td><td></td></tr> </table> <p>2010</p> </div> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p>	T 1 S	R 18 E	S 1		1/4	—	S 12	
T 1 S	R 18 E								
S 1									
1/4	—								
S 12									
80.00	<p>The cor. of secs. 1, 2, 11 and 12.</p> <p>Terrain, rolling. Soil, sand. Timber, mesquite; undergrowth, creosote.</p> <hr/> <p>N. 0°01' W., bet. secs. 1 and 2.</p>								

Survey of the Subdivisional Lines,
T. 1 S., R. 18 E., Gila and Salt River Meridian, Arizona

CHAINS	
	Over rolling to broken terrain.
40.00	<p>Point for the 1/4 sec. cor. of secs. 1 and 2.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 27 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T 1 S R 18 E 1/4 S 2 S 1 2010</p> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p> <p>Raise an accessory mound of stone 2 ft. base, 1 1/2 ft. high, W. of the cor.</p>
60.64	<p>Point for the closing cor. of secs. 1 and 2, on the N. bdy. of the Tp., at intersection with the Gila and Salt River base line.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T 1 N R 18 E S 33 ----- S 2 S 1 CC T 1 S R 18 E 2010</p> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p> <p>Raise an accessory mound of stone 2 ft. base, 1 ft. high, N. of the cor.</p> <p>From this cor. point, the stand. cor. of secs. 33 and 34, T. 1 N., R. 18 E., bears S. 89°58' E., 18.105 chs. dist., monumented with an iron pipe, 3 ins. diam., firmly set, projecting 14 ins. above ground, with brass cap mkd. SC T1N R18E S33 S34 2009 2010 1915.</p> <p>From this same cor. point, the stand. 1/4 sec. cor. of sec. 33, T. 1 N., R. 18 E., bears N. 89°58' W., 21.905 chs. dist., monumented with an iron pipe, 1 in. diam., firmly set, flush with the ground, in a collar of stone, with brass cap mkd. SC T1N R18E 1/4 S33 2010 1915.</p>

Survey of the Subdivisional Lines,
T. 1 S., R. 18 E., Gila and Salt River Meridian, Arizona

CHAINS	
	<p>Land, rolling to broken. Soil, loam. Timber, mesquite and palo negro; undergrowth, creosote and sage.</p> <hr/> <p>Point for the 1/4 sec. cor. of sec. 1 only, at midpoint on the N. bdy. of sec. 1.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 22 ins. in the ground, in a collar of stone, with brass cap mkd.</p> <p style="text-align: center;">T 1 N R 18 E ----- 1/4 S 1 T 1 S R 18 E</p> <p style="text-align: center;">2010</p> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p> <p>Set a steel "T-post" fence post near the cor.</p> <p>From this cor. point, the stan. 1/4 sec. cor. of sec. 34 only, T. 1 N., R. 18 E., bears S. 89°58' E., 18.11 chs. dist., monumented with an stainless steel pipe, 2 1/2 ins. diam., firmly set, flush with the ground, in a collar of stone, with brass cap mkd. SC T1N R18E 1/4 S 34 2010.</p> <p>From this same cor. point, the stan. cor. of secs. 33 and 34, T. 1 N., R. 18 E., bears N. 89°58' W., 21.90 chs. dist., hereinbefore described.</p> <hr/> <p>From the cor. of secs. 2, 3, 34 and 35, on the S. bdy. of the Tp., hereinbefore described.</p> <p>N. 0°01' W., bet. secs. 34 and 35.</p> <p>Over rolling to broken terrain.</p>
19.20	Underground El Paso gas line with two track road alongside, bears S. 48° E. and N. 48° W.
40.00	<p>Point for the 1/4 sec. cor. of secs. 34 and 35.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with brass cap mkd.</p>

Survey of the Subdivisional Lines,
T. 1 S., R. 18 E., Gila and Salt River Meridian, Arizona

CHAINS	
	<p style="text-align: center;">T 1 S R 18 E 1/4 S 34 S 35</p> <p style="text-align: center;">2010</p> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p> <p>Cor. is located 75 lks. S. of northerly property fence for Gene Irvine's home site.</p>
52.70	<p>U.S. Highway No. 70, asphalt surfaced, 34 ft. wide, bears S. 70° E. and N. 70° W.</p>
80.00	<p>Point for the cor. of secs. 26, 27, 34 and 35.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 27 ins. in the ground, with brass cap mkd.</p>
	<p style="text-align: center;">T 1 S R 18 E S 27 S 26 S 34 S 35</p> <p style="text-align: center;">2010</p> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p> <p>Raise an accessory mound of stone 2 ft. base, 2 ft. high, W. of the cor.</p> <p>Land, rolling to broken. Soil, gravely sandy loam. Timber, none; undergrowth, creosote, Mormon Tea, cats claw and sotol.</p> <hr/> <p>From the cor. of secs. 25, 26, 35 and 36.</p> <p>S. 89°48' W., bet. secs. 26 and 35.</p> <p>Over rolling to broken terrain.</p>
40.00	<p>Point for the 1/4 sec. cor. of secs. 26 and 35</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 18 ins. in the ground, in a supporting mound of stone, 3 ft. base, to top, with brass cap mkd.</p>

Survey of the Subdivisional Lines,
T. 1 S., R. 18 E., Gila and Salt River Meridian, Arizona

CHAINS	
	T 1 S R 18 E S 26 1/4 ——— S 35 2010
	Deposit a magnet, in a white plastic case, at the base of the stainless steel post.
43.05	Graded road, 15 ft. wide, bears N. and S. 35° W.
44.75	High voltage transmission line, bears N. 20° E. and S. 25° W.
80.00	The cor. of secs. 26, 27, 34 and 35. Terrain, broken and rolling. Soil, gravely sandy loam. Timber, none; undergrowth, creosote and Mormon Tea.
	N. 0°01' W., bet. secs. 26 and 27. Over rolling to broken terrain.
40.00	Point for the 1/4 sec. cor. of secs. 26 and 27. Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with brass cap mkd.
	T 1 S R 18 E 1/4 S 27 S 26 2010
	Deposit a magnet, in a white plastic case, at the base of the stainless steel post.
	Raise an accessory mound of stone 3 ft. base, 2 ft. high, W. of the cor.
80.00	Point for the cor. of secs. 22, 23, 26 and 27. Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.
	T 1 S R 18 E S 22 S 23 S 27 S 26 2010

Survey of the Subdivisional Lines,
T. 1 S., R. 18 E., Gila and Salt River Meridian, Arizona

CHAINS	
	<p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p> <p>Raise an accessory mound of stone 2 ft. base, 2 ft. high, W. of the cor.</p> <p>Land, rolling to broken. Soil, loam. Timber, mesquite and palo negro; undergrowth, creosote, Mormon Tea and sage.</p> <hr style="width: 80%; margin: 10px auto;"/>
	<p>From the cor. of secs. 23, 24, 25 and 26.</p> <p>S. 89°48' W., bet. secs. 23 and 26.</p> <p>Over rolling terrain.</p>
14.50	Graded road, 10 ft. wide, bears N. 25° E. and S. 25° W.
14.70	High voltage transmission line, bears N. 25° E. and S. 25° W.
40.00	<p>Point for the 1/4 sec. cor. of secs. 23 and 26.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 12 ins. in the ground, in a mound of stone, 4 ft. base, to top, with brass cap mkd.</p> <div style="text-align: center; margin: 10px 0;"> <p>T 1 S R 18 E</p> <p style="margin-left: 100px;">S 23</p> <p style="margin-left: 100px;">1/4 ———</p> <p style="margin-left: 100px;">S 26</p> <p style="margin-left: 100px;">2010</p> </div>
80.00	<p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p> <p>Cor. is located on N. side of road, 15 ft. wide, bears S 55° E. from N. 60° W.</p> <p>The cor. of secs. 22, 23, 26 and 27.</p> <p>Land, rolling to broken. Soil, loam. Timber, mesquite and palo negro; undergrowth, creosote, Mormon Tea and sage.</p> <hr style="width: 80%; margin: 10px auto;"/> <p>N. 0°01' W., bet. secs. 22 and 23.</p> <p>Over broken and rolling terrain.</p>

Survey of the Subdivisional Lines,
T. 1 S., R. 18 E., Gila and Salt River Meridian, Arizona

CHAINS	
40.00	<p>Point for the 1/4 sec. cor. of secs. 22 and 23.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T 1 S R 18 E 1/4 S 22 S 23</p> <p style="text-align: center;">2010</p> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p> <p>Raise an accessory mound of stone 2 ft. base, 2 ft. high, W. of the cor.</p>
80.00	<p>Point for the cor. of secs. 14, 15, 22 and 23.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, in a collar of stone, with brass cap mkd.</p> <p style="text-align: center;">T 1 S R 18 E S 15 S 14 S 22 S 23</p> <p style="text-align: center;">2010</p> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p> <p>Raise an accessory mound of stone 3 ft. base, 2 ft. high, W. of the cor.</p> <p>Land, rolling to broken. Soil, loam. Timber, mesquite and palo negro; undergrowth, creosote, Mormon Tea and sage.</p> <hr/> <p>From the cor. of secs. 13, 14, 23 and 24.</p> <p>S. 89°48' W., bet. secs. 14 and 23.</p>
40.00	<p>Point for the 1/4 sec. cor. of secs. 14 and 23.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 21 ins. in the ground, in a supporting mound of stone, 3 ft. base, to top, with brass cap mkd.</p>

Survey of the Subdivisional Lines,
T. 1 S., R. 18 E., Gila and Salt River Meridian, Arizona

CHAINS	
	T 1 S R 18 E S 14 1/4 ——— S 23 2010
	Deposit a magnet, in a white plastic case, at the base of the stainless steel post. Set a steel "T-post" fence post near the cor. Cor. is located in tailings from Peridot pit mines - low if any mining activity.
80.00	The cor. of secs. 14, 15, 22 and 23. Land, rolling to broken. Soil, loam. Timber, mesquite and palo negro; undergrowth, creosote, Mormon Tea and sage.
	N. 0°01' W., bet. secs. 14 and 15. Over rolling terrain.
40.00	Point for the 1/4 sec. cor. of secs. 14 and 15. Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 27 ins. in the ground, in a collar of stone, with brass cap mkd.
	T 1 S R 18 E 1/4 S 15 S 14 2010
	Deposit a magnet, in a white plastic case, at the base of the stainless steel post. Raise an accessory mound of stone 2 ft. base, 1 ft. high, W. of the cor.
80.00	Point for the cor. of secs. 10, 11, 14 and 15. Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 27 ins. in the ground, in a collar of stone, with brass cap mkd.

Survey of the Subdivisional Lines,
T. 1 S., R. 18 E., Gila and Salt River Meridian, Arizona

CHAINS									
	<table style="margin: auto;"> <tr><td>T 1 S</td><td>R 18 E</td></tr> <tr><td>S 10</td><td>S 11</td></tr> <tr><td>S 15</td><td>S 14</td></tr> </table>	T 1 S	R 18 E	S 10	S 11	S 15	S 14		
T 1 S	R 18 E								
S 10	S 11								
S 15	S 14								
	2010								
	Deposit a magnet, in a white plastic case, at the base of the stainless steel post.								
	Raise an accessory mound of stone 2 ft. base, 2 ft. high, W. of the cor.								
	from which								
	A brass tablet set in 8 ins. well casing, projecting 6 ins. above the ground, filled with concrete, bears N. 31°14' E., 4.48 chs. dist., mkd. INDIAN HEALTH SERVICES SC CP ELEVATION 2920.13 028 20.								
	Land, rolling to broken. Soil, loam. Timber, mesquite and palo negro; undergrowth, creosote, Mormon Tea and sage.								
	From the cor. of secs. 11, 12, 13 and 14.								
	S. 89°48' W., bet. secs. 11 and 14.								
	Over rolling to broken terrain.								
33.70	Center of Arizona Eastern railroad tracks, bears S. 64° E. and N. 64° W.								
40.00	Point for the 1/4 sec. cor. of secs. 11 and 14.								
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 20 ins. in the ground, in a mound of stone, 3 ft. base, to top, with brass cap mkd.								
	<table style="margin: auto;"> <tr><td>T 1 S</td><td>R 18 E</td></tr> <tr><td>S 11</td><td></td></tr> <tr><td>1/4</td><td>—</td></tr> <tr><td>S 14</td><td></td></tr> </table>	T 1 S	R 18 E	S 11		1/4	—	S 14	
T 1 S	R 18 E								
S 11									
1/4	—								
S 14									
	2010								
	Deposit a magnet, in a white plastic case, at the base of the stainless steel post.								
	Cor. is located on right side of foot trail, bears N. 50° E. and S. 50° W.								

Survey of the Subdivisional Lines,
T. 1 S., R. 18 E., Gila and Salt River Meridian, Arizona

CHAINS	
73.50	Edge of Peridot Mesa, bears N. and S.
80.00	The cor. of secs. 10, 11, 14 and 15. Terrain, rolling to broken. Soil, loam. Timber, mesquite; undergrowth, creosote, cats claw, prickly pear and grasses.

	N. 0°01' W., bet. secs. 10 and 11. Over rolling to broken terrain.
3.40	Edge of Peridot Mesa, bears N. 60° E. and S. 60° W.
6.90	Center of Arizona Eastern railroad tracks, bears N. 72° E. and S. 50° W.
30.25	Indian Route No. 6, asphalt surfaced, 26 ft. wide, bears S. 84° E. and N. 84° W.
40.00	Point for the 1/4 sec. cor. of secs. 10 and 11. Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 28 ins. in the ground, in a collar of stone, with brass cap mkd.
	T 1 S R 18 E 1/4 S 10 S 11 2010
	Deposit a magnet, in a white plastic case, at the base of the stainless steel post. Set a steel "T-post" fence post near the cor. Cor. is located in the easterly track of a two track road, bears S. 10° E. and N. 10° W., on top of spur ridge with the same bearing.
80.00	Point for the cor. of secs. 2, 3, 10 and 11. Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 20 ins. in the ground, in a mound of stone, 3 ft. base, to top, with brass cap mkd.

Survey of the Subdivisional Lines,
T. 1 S., R. 18 E., Gila and Salt River Meridian, Arizona

CHAINS									
	<table style="margin-left: auto; margin-right: auto;"> <tr><td>T 1 S</td><td>R 18 E</td></tr> <tr><td>S 3</td><td>S 2</td></tr> <tr><td>S 10</td><td>S 11</td></tr> </table> <p style="text-align: center;">2010</p>	T 1 S	R 18 E	S 3	S 2	S 10	S 11		
T 1 S	R 18 E								
S 3	S 2								
S 10	S 11								
	<p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p> <p>Cor. is located in small ravine, drains N. 15° E.</p> <p>Terrain, rolling. Soil, rocky loam and sandstone. Timber, palo negro; undergrowth, creosote, cats claw and Mormon Tea.</p> <hr/> <p>From the cor. of secs. 1, 2, 11 and 12.</p> <p>S. 89°48' W., bet. secs. 2 and 11.</p> <p>Over rolling terrain.</p>								
40.00	<p>Point for the 1/4 sec. cor. of secs. 2 and 11.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 25 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;"> <table style="margin-left: auto; margin-right: auto;"> <tr><td>T 1 S</td><td>R 18 E</td></tr> <tr><td>S 2</td><td></td></tr> <tr><td>1/4</td><td>—</td></tr> <tr><td>S 11</td><td></td></tr> </table> <p style="text-align: center;">2010</p> </p>	T 1 S	R 18 E	S 2		1/4	—	S 11	
T 1 S	R 18 E								
S 2									
1/4	—								
S 11									
80.00	<p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p> <p>Raise an accessory mound of stone 3 ft. base, 1 ft. high, W. of the cor.</p> <p>Cor. is located on small hill, bears S. 30° E. and N. 30° W.</p> <p>The cor. of secs. 2, 3, 10 and 11.</p> <p>Terrain, rolling. Soil, silted loam. Timber, mesquite; undergrowth, creosote, cats claw and cholla.</p> <hr/> <p>N. 0°01' W., bet. secs. 2 and 3.</p> <p>Over rolling terrain.</p>								

Survey of the Subdivisional Lines,
T. 1 S., R. 18 E., Gila and Salt River Meridian, Arizona

CHAINS	
40.00	<p>Point for the 1/4 sec. cor. of secs. 2 and 3.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, in a collar of stone, with brass cap mkd.</p> <p style="text-align: center;">T 1 S R 18 E 1/4 S 3 S 2</p> <p style="text-align: center;">2010</p> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p> <p>Set a steel "T-post" fence post near the cor.</p> <p>Cor. is located in the extreme limits of Tufa Stone Stock Tank, possibly could be under water part of the year.</p>
60.91	<p>Point for the closing cor. of secs. 2 and 3, on the N. bdy. of the Tp., at intersection with the Gila and Salt River base line.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T 1 N R 18 E S 32 ----- S 3 S 2 T 1 S R 18 E CC</p> <p style="text-align: center;">2010</p> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p> <p>Raise an accessory mound of stone 2 ft. base, 2 ft. high, N. of the cor.</p> <p>From this cor. point, the stan. sec. cor. of secs. 32 and 33, T. 1 N., R. 18 E., bears N. 89°58' E., 18.085 chs. dist., monumented with an iron pipe, 3 ins. diam., firmly set, projecting 14 ins. above ground, with brass cap mkd. SC T1N R18E S32 S33 2010 1915.</p> <p>From this same cor. point, the stan. 1/4 sec. cor. to 32 only, T. 1 N., R. 18 E., bears S. 89°58' W., 21.915 chs. dist., monumented with an iron pipe, 1 in. diam., firmly set, projecting 11 ins. above ground, with brass cap mkd. SC T1N R18E 1/4 S32 2010 1915.</p>

Survey of the Subdivisional Lines,
T. 1 S., R. 18 E., Gila and Salt River Meridian, Arizona

CHAINS	
	<p>Terrain, rolling. Soil, loam. Timber, mesquite; undergrowth, creosote and grasses.</p> <hr/> <p>Point for the 1/4 sec. cor. of sec. 2 only, at midpoint on the N. bdy. of sec. 2.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 27 ins. in the ground, underpinned by 5 1/2 ft. steel "T-post" fence post, with brass cap mkd.</p> <p style="text-align: center;">T 1 N R 18 E <hr style="width: 10%; margin: auto;"/>1/4 S 2 T 1 S R 18 E</p> <p style="text-align: center;">2010</p> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p> <p>Raise an accessory mound of stone 2 ft. base, 2 ft. high, N. of the cor.</p> <p>From this cor. point, the stan. 1/4 sec. cor. of sec. 33 only, T. 1 N., R. 18 E., bears N. 89°59' E., 18.095 chs. dist., hereinbefore described.</p> <p>From this same cor. point, the stan. cor. of secs. 32 and 33, T. 1 N., R. 18 E., bears S. 89°59' W., 21.915 chs. dist., hereinbefore described.</p> <hr/> <p>From the cor. of secs. 3, 4, 33 and 34, on the S. bdy. of the Tp., hereinbefore described.</p> <p>N. 0°02' W., bet. secs. 33 and 34.</p> <p>Over rolling terrain.</p>
40.00	<p>Point for the 1/4 sec. cor. of secs. 33 and 34.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T 1 S R 18 E 1/4 S 33 S 34</p> <p style="text-align: center;">2010</p>

Survey of the Subdivisional Lines,
T. 1 S., R. 18 E., Gila and Salt River Meridian, Arizona

CHAINS							
	<p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p> <p>Raise an accessory mound of stone 2 ft. base, 2 ft. high, W. of the cor.</p>						
76.40	<p>Underground El Paso gas line with two track road alongside, bears S. 55° E. and N. 55° W., at the gate for the right-of-way to State Route 70, right-of-way fence bears S. 62° E. and N 62° W.</p>						
78.00	<p>U.S. Highway No. 70, asphalt surfaced, 34 ft. wide, bears S. 71° E. and N. 71° W.</p>						
80.00	<p>Point for the cor. of secs. 27, 28, 33 and 34.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center;"> <table style="margin: auto;"> <tr><td>T 1 S</td><td>R 18 E</td></tr> <tr><td>S 28</td><td> S 27</td></tr> <tr><td>S 33</td><td> S 34</td></tr> </table> <p>2010</p> </div> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p> <p>Raise an accessory mound of stone 2 ft. base, 2 ft. high, W. of the cor.</p> <p>Cor. is located 36 lks. N. of fiber optic line road, 9 ft. wide, parallels right-of-way fence, 48 lks. from cor., bears S. 70° E. and N. 70° W.</p> <p>Land, rolling. Soil, coarse loam. Timber, mesquite; undergrowth, creosote, cats claw and Mormon Tea.</p> <hr/> <p>From the cor. of secs. 26, 27, 34 and 35.</p> <p>S. 89°48' W., bet. secs. 27 and 34.</p> <p>Over rolling terrain.</p>	T 1 S	R 18 E	S 28	S 27	S 33	S 34
T 1 S	R 18 E						
S 28	S 27						
S 33	S 34						
40.00	<p>Point for the 1/4 sec. cor. of secs. 27 and 34.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with brass cap mkd.</p>						

Survey of the Subdivisional Lines,
T. 1 S., R. 18 E., Gila and Salt River Meridian, Arizona

CHAINS	
	T 1 S R 18 E S 27 1/4 ——— S 34 2010
	Deposit a magnet, in a white plastic case, at the base of the stainless steel post.
	Raise an accessory mound of stone 2 ft. base, 2 ft. high, N. of the cor.
80.00	The cor. of secs. 27, 28, 33 and 34. Terrain, rolling to broken. Soil, loam. Timber, mesquite and palo negro; undergrowth, creosote, Mormon Tea, prickly pear, yucca and barrel cactus.
	N. 0°02' W., bet. secs. 27 and 28. Over rolling terrain.
40.00	Point for the 1/4 sec. cor. of secs. 27 and 28. Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 25 ins. in the ground, with brass cap mkd.
	T 1 S R 18 E 1/4 S 28 S 27 2010
	Deposit a magnet, in a white plastic case, at the base of the stainless steel post.
	Raise an accessory mound of stone 2 ft. base, 2 ft. high, W. of the cor.
80.00	Point for the cor. of secs. 21, 22, 27 and 28. Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 5 ins. in the ground, in a supporting mound of stone, 4 ft. base, to top, with brass cap mkd.
	T 1 S R 18 E S 21 S 22 S 28 S 27 2010

Survey of the Subdivisional Lines,
T. 1 S., R. 18 E., Gila and Salt River Meridian, Arizona

CHAINS	
	<p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p> <p>Cor. is located on the E. aspect of S. spur of Peridot Mesa.</p> <p>Terrain, rolling. Soil, rocky loam. Timber, mesquite and palo negro; undergrowth, creosote.</p> <hr/> <p>From the cor. of secs. 22, 23, 26 and 27.</p> <p>S. 89°48' W., bet. secs. 22 and 27.</p> <p>Over rolling and broken terrain.</p>
40.00	<p>Point for the 1/4 sec. cor. of secs. 22 and 27.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 14 ins. in the ground, in a supporting mound of stone, 3 ft. base, to top, with brass cap mkd.</p> <div style="text-align: center;"> <p>T 1 S R 18 E</p> <p>S 22</p> <p>1/4 ———</p> <p>S 27</p> <p>2010</p> </div>
80.00	<p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p> <p>The cor. of secs. 21, 22, 27 and 28.</p> <p>Terrain, rolling. Soil, rocky loam. Timber, mesquite and palo verde; undergrowth, creosote, cats claw and grasses.</p> <hr/> <p>N. 0°02' W., bet. secs. 21 and 22.</p> <p>Over rolling and broken terrain.</p>
40.00	<p>Point for the 1/4 sec. cor. of secs 21 and 22.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with brass cap mkd.</p>

Survey of the Subdivisional Lines,
T. 1 S., R. 18 E., Gila and Salt River Meridian, Arizona

CHAINS	
	T 1 S R 18 E 1/4 S 21 S 22 2010
	Deposit a magnet, in a white plastic case, at the base of the stainless steel post.
	Raise an accessory mound of stone 2 ft. base, 3 ft. high, W. of the cor.
80.00	Point for the cor. of secs. 15, 16, 21 and 22. Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 27 ins. in the ground, with brass cap mkd.
	T 1 S R 18 E S 16 S 15 S 21 S 22 2010
	Deposit a magnet, in a white plastic case, at the base of the stainless steel post.
	Cor. is located 75 lks. W. of dirt road, 21 ft., wide, bears N. and S. 20° E.
	Terrain, rolling. Soil, rocky clay loam. Timber, mesquite and palo verde; undergrowth, creosote, cats claw and grasses.
	<hr/> From the cor. of secs. 14, 15, 22 and 23. S. 89°48' W., bet. secs. 15 and 22. Over rolling and broken terrain.
40.00	Point for the 1/4 sec. cor. of secs. 15 and 22. Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.
	T 1 S R 18 E S 15 1/4 ——— S 22 2010

Survey of the Subdivisional Lines,
T. 1 S., R. 18 E., Gila and Salt River Meridian, Arizona

CHAINS	
	<p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p> <p>Raise an accessory mound of stone 2 1/2 ft. base, 2 1/2 ft. high, N. of the cor.</p> <p>Cor. is located in a fire road 15 ft. wide, bears N. 70° E. and S. 60° W.</p>
80.00	<p>The cor. of secs. 15, 16, 21 and 22.</p> <p>Terrain, rolling. Soil, rocky loam. Timber, mesquite and palo verde; undergrowth, creosote, cats claw and grasses.</p> <hr/> <p>N. 0°02' W., bet. secs. 15 and 16.</p> <p>Over broken terrain.</p>
40.00	<p>True point for the 1/4 sec. cor. of secs. 15 and 16; falls in bed of meandering wash, 60 ft. wide, 6 ft. deep, drains N. 3° E. from S. 5° W., where it is impracticable to establish a permanent monument.</p> <p>From this true point, the point selected for the witness cor. to the 1/4 sec. cor. of secs. 15 and 16, bears S. 58°15' W., 1.28 chs. dist.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, underpinned with a steel "T-post" fence post, 6 ft. long, with brass cap mkd.</p> <div style="text-align: center;"> <p>WC</p> <p>T 1 S R 18 E</p> <p>1/4</p> <p>S 16 S 15</p> <p>2010</p> </div> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p> <p>Raise an accessory mound of stone 2 ft. base, 2 ft. high, W. of the cor.</p>
78.52	<p>Center of Arizona Eastern railroad tracks, bears S. 82° E. and N. 82° W.</p>
80.00	<p>Point for the cor. of secs. 9, 10, 15 and 16.</p>

Survey of the Subdivisional Lines,
T. 1 S., R. 18 E., Gila and Salt River Meridian, Arizona

CHAINS									
	<p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 27 ins. in the ground, with brass cap mkd.</p>								
	<table style="margin-left: auto; margin-right: auto;"> <tr><td>T 1 S</td><td>R 18 E</td></tr> <tr><td>S 9</td><td>S 10</td></tr> <tr><td>S 16</td><td>S 15</td></tr> </table>	T 1 S	R 18 E	S 9	S 10	S 16	S 15		
T 1 S	R 18 E								
S 9	S 10								
S 16	S 15								
	2010								
	<p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p>								
	<p>Raise a mound of stone, 2 ft. base, 1 ft. high, W. of cor.</p>								
	<p>Terrain, rolling. Soil, rocky loam. Timber, mesquite and palo verde; undergrowth, creosote, cats claw and grasses</p>								
	<hr/>								
	<p>From the cor. of secs. 10, 11, 14 and 15.</p>								
	<p>S. 89°48' W., bet. secs 10 and 15.</p>								
	<p>Over rolling and broken terrain.</p>								
7.00	<p>Edge of Peridot Mesa, bears N. 45° E. and S. 45° W.</p>								
16.10	<p>Center of Arizona Eastern railroad tracks, bears N. 66° E. and S. 66° W.</p>								
40.00	<p>Point for the 1/4 sec. cor. of secs. 10 and 15.</p>								
	<p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 27 ins. in the ground, in a collar of stone, with brass cap mkd.</p>								
	<table style="margin-left: auto; margin-right: auto;"> <tr><td>T 1 S</td><td>R 18 E</td></tr> <tr><td>S 10</td><td></td></tr> <tr><td>1/4</td><td>—</td></tr> <tr><td>S 15</td><td></td></tr> </table>	T 1 S	R 18 E	S 10		1/4	—	S 15	
T 1 S	R 18 E								
S 10									
1/4	—								
S 15									
	2010								
	<p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p>								
	<p>Raise an accessory mound of stone 2 ft. base, 2 ft. high, N. of the cor.</p>								
80.00	<p>Point for the cor. of secs. 9, 10, 15 and 16.</p>								

Survey of the Subdivisional Lines,
T. 1 S., R. 18 E., Gila and Salt River Meridian, Arizona

CHAINS	
	<p>Terrain, rolling. Soil, rocky loam. Timber, mesquite and palo verde; undergrowth, creosote, cats claw and grasses.</p> <hr/> <p>N. 0°02' W., bet. secs. 9 and 10.</p> <p>Over rolling and broken terrain.</p>
40.00	<p>Point for the 1/4 sec. cor. of secs. 9 and 10.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 23 ins. in the ground, underpinned with a steel "T-post" fence post, 5 ft. long, with brass cap mkd.</p> <div style="text-align: center;"> <p>T 1 S R 18 E 1/4 S 9 S 10</p> <p>2010</p> </div> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p> <p>Cor. is located 75 lks. N. of the left bank of a wash, 15 ft. deep, drains E.</p>
46.50	<p>Indian Route No. 6, asphalt surfaced, 26 ft. wide, bears S. 70° E. and N. 70° W.</p>
80.00	<p>Point for the cor. of secs. 3, 4, 9 and 10.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, in a collar of stone, with brass cap mkd.</p> <div style="text-align: center;"> <p>T 1 S R 18 E S 4 S 3 S 9 S 10</p> <p>2010</p> </div> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p> <p>Raise an accessory mound of stone 3 ft. base, 1 ft. high, N. of the cor.</p> <p>Land, rolling. Soil, rocky clay loam. Timber, mesquite; undergrowth, creosote, cats claw and Mormon Tea.</p> <hr/>

Survey of the Subdivisional Lines,
T. 1 S., R. 18 E., Gila and Salt River Meridian, Arizona

CHAINS	
	<p>From the cor. of secs. 2, 3, 10 and 11.</p> <p>S. 89°48' W., bet. secs. 3 and 10.</p>
40.00	<p>Point for the 1/4 sec. cor. of secs. 3 and 10.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T 1 S R 18 E S 3 1/4 ——— S 10</p> <p style="text-align: center;">2010</p> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p> <p>Raise an accessory mound of stone 2 ft. base, 1 ft. high, N. of the cor.</p>
80.00	<p>The cor. of secs. 3, 4, 9 and 10.</p> <p>Terrain, rolling. Soil, rocky loam. Timber, mesquite and palo verde; undergrowth, creosote, cats claw and grasses.</p> <hr/> <p>N. 0°02' W., bet. secs. 3 and 4.</p> <p>Over broken terrain.</p>
40.00	<p>Point for the 1/4 sec. cor. of secs. 3 and 4.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, in a collar of stone, with brass cap mkd.</p> <p style="text-align: center;">T 1 S R 18 E 1/4 S 4 S 3</p> <p style="text-align: center;">2010</p> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p> <p>Raise an accessory mound of stone 3 ft. base, 1 ft. high, W. of the cor.</p>
61.18	<p>Point for the closing cor. of secs. 3 and 4, on the N. bdy. of the Tp., at intersection with the Gila and Salt River base line.</p>

Survey of the Subdivisional Lines,
T. 1 S., R. 18 E., Gila and Salt River Meridian, Arizona

CHAINS

Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.

T 1 N R 18 E
 S 31

 S 4 | S 3
 C | C
 T 1 S R 18 E

2010

Deposit a magnet, in a white plastic case, at the base of the stainless steel post.

Raise an accessory mound of stone 2 ft. base, 2 ft. high, S. of the cor.

From this cor. point, the stan. cor. of secs. 31 and 32, T. 1 N., R. 18 E., bears East, 18.085 chs. dist., monumented with an iron pipe, 3 ins. diam., firmly set, projecting 12 ins. above ground, in a mound of stone, 4 ft. base, to top, with brass cap mkd. SC T1N R18E S31 S32 2010 1915.

From this same cor. point, the stan. 1/4 sec. cor. of sec. 31 only, T. 1 N., R. 18 E., bears West, 21.935 chs. dist., monumented with an iron pipe, 1 in. diam., firmly set, projecting 12 ins. above ground, in a mound of stone, 3 ft. base, to top, with brass cap mkd. SC T1N R18E 1/4 S31 2010 1915.

Terrain, rolling.

Soil, rocky loam.

Timber, mesquite and palo verde; undergrowth, creosote, cats claw and grasses.

Point for the 1/4 sec. cor. of sec. 3 only, at midpoint on the N. bdy. of sec. 3.

Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 25 ins. in the ground, in a collar of stone, with brass cap mkd.

T 1 N R 18 E

 1/4 S 3
 T 1 S R 18 E

2010

Deposit a magnet, in a white plastic case, at the base of the stainless steel post.

Raise an accessory mound of stone 3 ft. base, 3 ft. high, N. of the cor.

Survey of the Subdivisional Lines,
T. 1 S., R. 18 E., Gila and Salt River Meridian, Arizona

CHAINS	
	<p>From this cor. point, the stan. 1/4 sec. cor. of sec. 32 only, T. 1 N., R. 18 E., bears East, 18.085 chs. dist., hereinbefore described.</p> <p>From this same cor. point, the stan. sec. cor. of secs. 31 and 32, T. 1 N., R. 18 E., bears West, 21.915 chs. dist., hereinbefore described.</p> <hr/> <p>From the cor. of secs. 4, 5, 32 and 33, on the S. bdy. of the Tp., hereinbefore described.</p> <p>N. 0°02' W., bet. secs. 32 and 33.</p> <p>Over flat to rolling terrain.</p>
40.00	<p>Point for the 1/4 sec. cor. of secs. 32 and 33.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center;"> <p>T 1 S R 18 E</p> <p>1/4</p> <p>S 32 S 33</p> <p>2010</p> </div> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p> <p>Raise an accessory mound of stone 2 ft. base, 2 1/2 ft. high, W. of the cor.</p>
80.00	<p>Point for the cor. of secs. 28, 29, 32 and 33.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 25 ins. in the ground with brass cap mkd.</p> <div style="text-align: center;"> <p>T 1 S R 18 E</p> <p>S 29 S 28</p> <hr style="width: 50%; margin: 0 auto;"/> <p>S 32 S 33</p> <p>2010</p> </div> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p> <p>Raise an accessory mound of stone 1 1/2 ft. base, 1 1/2 ft. high, W. of the cor.</p> <p>Cor. is located 20 lks. N. of small drainage, between low ridges, bears E. from N. 60° W.</p>

Survey of the Subdivisional Lines,
T. 1 S., R. 18 E., Gila and Salt River Meridian, Arizona

CHAINS	
	<p>Land, rolling. Soil, coarse loam. Timber, mesquite; undergrowth, creosote, cats claw, sotol, and Mormon Tea..</p> <hr/> <p>From the cor. of secs. 27, 28, 33 and 34.</p> <p>S. 89°48' W., bet. secs. 28 and 33.</p> <p>Over rolling terrain.</p>
1.70	Approximate location of underground El Paso gas line in the right-of-way of Arizona State Route 70.
6.40	Arizona State Highway No. 70, asphalt surfaced, 34 ft. wide, bears S. 71° E. and N. 71° W.
40.00	<p>Point for the 1/4 sec. cor. of secs. 28 and 33.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center;"> <p>T 1 S R 18 E</p> <p>S 28</p> <p>1/4 ———</p> <p>S 33</p> <p>2010</p> </div> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p>
80.00	<p>The cor. of secs. 28, 29, 32 and 33.</p> <p>Terrain, rolling. Soil, rocky loam. Timber, mesquite; undergrowth, creosote and sotol.</p> <hr/> <p>N. 0°02' W., bet. secs. 28 and 29.</p> <p>Over rolling and broken terrain.</p>
27.25	Arizona State Highway No. 70, asphalt surfaced, 34 ft. wide, bears S. 68° E. and N. 68° W.
40.00	<p>Point for the 1/4 sec. cor. of secs. 28 and 29.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 27 ins. in the ground, with brass cap mkd.</p>

Survey of the Subdivisional Lines,
T. 1 S., R. 18 E., Gila and Salt River Meridian, Arizona

CHAINS	
	T 1 S R 18 E 1/4 S 29 S 28 2010
	Deposit a magnet, in a white plastic case, at the base of the stainless steel post.
	Raise an accessory mound of stone 2 ft. base, 2 ft. high, W. of the cor.
49.00	Underground El Paso gas line with two track road alongside, bears S. 58° E. and N. 58° W.
80.00	Point for the cor. of secs. 20, 21, 28 and 29. Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.
	T 1 S R 18 E S 20 S 21 S 29 S 28 2010
	Deposit a magnet, in a white plastic case, at the base of the stainless steel post.
	Set a steel "T-post" fence post near the cor.
	Terrain, rolling. Soil, sandy loam. Timber, mesquite; undergrowth, creosote, cats claw and sotol.
	<hr/> From the cor. of secs. 21, 22, 27 and 28. S. 89°48' W., bet. secs. 21 and 28. Over rolling and broken terrain.
40.00	Point for the 1/4 sec. cor. of secs. 21 and 28. Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., set flush with the ground, with brass cap mkd.
	T 1 S R 18 E S 21 1/4 ——— S 28 2010

Survey of the Subdivisional Lines,
T. 1 S., R. 18 E., Gila and Salt River Meridian, Arizona

CHAINS	
	<p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p> <p>Raise an accessory mound of stone 2 ft. base, 2 ft. high, N. of the cor.</p>
80.00	<p>The cor. of secs. 20, 21, 28 and 29.</p> <p>Terrain, rolling. Soil, sandy loam. Timber, mesquite; undergrowth, creosote, cats claw and sotol.</p> <hr/>
	<p>N. 0°02' W., bet. secs. 20 and 21.</p> <p>Over rolling terrain.</p>
40.00	<p>Point for the 1/4 sec. cor. of secs. 20 and 21.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 25 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T 1 S R 18 E 1/4 S 20 S 21 2010</p>
	<p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p> <p>Raise an accessory mound of stone 3 ft. base, 2 ft. high, W. of the cor.</p>
80.00	<p>Point for the cor. of secs. 16, 17, 20 and 21.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 14 ins. in the ground, in a supporting mound of stone, 4 ft. base, to top, with brass cap mkd.</p> <p style="text-align: center;">T 1 S R 18 E S 17 S 16 S 20 S 21 2010</p>
	<p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p>

Survey of the Subdivisional Lines,
T. 1 S., R. 18 E., Gila and Salt River Meridian, Arizona

CHAINS	
	<p>Terrain, rolling. Soil, gravelly loam. Timber, mesquite, ocotillo, saguaro and palo negro; undergrowth, creosote, sagebrush, prickly pear and grasses.</p> <hr/> <p>From the cor. of secs. 15, 16, 21 and 22.</p> <p>S. 89°48' W., bet. secs. 16 and 21.</p> <p>Over flat to rolling terrain.</p>
40.00	<p>Point for the 1/4 sec. cor. of secs. 16 and 21.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 27 ins. in the ground, underpinned with a steel "T-post" fence post, 5 ft. long, with brass cap mkd.</p> <div style="text-align: center;"> <p>T 1 S R 18 E S 16 1/4 ——— S 21</p> <p>2010</p> </div> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p> <p>Raise an accessory mound of stone 3 ft. base, 2 ft. high, N. of the cor.</p>
80.00	<p>The cor. of secs. 16, 17, 20 and 21.</p> <p>Terrain, rolling. Soil, sandy loam. Timber, mesquite; undergrowth, creosote, cats claw and yucca.</p> <hr/> <p>N. 0°02' W., bet. secs. 16 and 17.</p> <p>Over rolling terrain.</p>
40.00	<p>Point for the 1/4 sec. cor. of secs. 16 and 17.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 16 ins. in the ground, in a mound of stone, 3 ft. base, to top, with brass cap mkd.</p> <div style="text-align: center;"> <p>T 1 S R 18 E 1/4 S 17 S 16</p> <p>2010</p> </div>

Survey of the Subdivisional Lines,
T. 1 S., R. 18 E., Gila and Salt River Meridian, Arizona

CHAINS																									
	<p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p> <p>Cor. is located on the SW aspect of a spur ridge, bears S. 75° E. and N. 75° W., above deep cuts feeding a canyon.</p>																								
80.00	<p>Point for the cor. of secs. 8, 9, 16 and 17.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 12 ins. in the ground, in a mound of stone, 4 ft. base, to top, with brass cap mkd.</p> <div style="text-align: center;"> <table style="border-collapse: collapse; margin: auto;"> <tr> <td style="padding: 0 5px;">T</td> <td style="padding: 0 5px;">1</td> <td style="padding: 0 5px;">S</td> <td style="padding: 0 5px;">R</td> <td style="padding: 0 5px;">18</td> <td style="padding: 0 5px;">E</td> </tr> <tr> <td style="padding: 0 5px;"></td> <td style="padding: 0 5px;">S</td> <td style="padding: 0 5px;">8</td> <td style="padding: 0 5px;"> </td> <td style="padding: 0 5px;">S</td> <td style="padding: 0 5px;">9</td> </tr> <tr> <td style="padding: 0 5px;"></td> <td style="padding: 0 5px;">S</td> <td style="padding: 0 5px;">17</td> <td style="padding: 0 5px;"> </td> <td style="padding: 0 5px;">S</td> <td style="padding: 0 5px;">16</td> </tr> </table> <p>2010</p> </div> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p> <p>Cor. is located on the NW face of mesa ridge, bears N. 45° E. and S. 45° W..</p> <p>Terrain, rolling. Soil, sandy loam. Timber, mesquite; undergrowth, creosote, cats claw and yucca.</p> <hr/> <p>From the cor. of secs. 9, 10, 15 and 16.</p> <p>S. 89°48 W., bet. secs. 9 and 16.</p> <p>Over rolling and broken terrain.</p>	T	1	S	R	18	E		S	8		S	9		S	17		S	16						
T	1	S	R	18	E																				
	S	8		S	9																				
	S	17		S	16																				
8.15	<p>Center of Arizona Eastern railroad tracks, bears S. 82° E. and N. 82° W.</p>																								
40.00	<p>Point for the 1/4 sec. cor. of secs. 9 and 16.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, in a collar of stone, with brass cap mkd.</p> <div style="text-align: center;"> <table style="border-collapse: collapse; margin: auto;"> <tr> <td style="padding: 0 5px;">T</td> <td style="padding: 0 5px;">1</td> <td style="padding: 0 5px;">S</td> <td style="padding: 0 5px;">R</td> <td style="padding: 0 5px;">18</td> <td style="padding: 0 5px;">E</td> </tr> <tr> <td style="padding: 0 5px;"></td> <td style="padding: 0 5px;"></td> <td style="padding: 0 5px;">S</td> <td style="padding: 0 5px;">9</td> <td style="padding: 0 5px;">—</td> <td style="padding: 0 5px;"></td> </tr> <tr> <td style="padding: 0 5px;"></td> <td style="padding: 0 5px;">1/4</td> <td style="padding: 0 5px;"></td> <td style="padding: 0 5px;"></td> <td style="padding: 0 5px;"></td> <td style="padding: 0 5px;"></td> </tr> <tr> <td style="padding: 0 5px;"></td> <td style="padding: 0 5px;"></td> <td style="padding: 0 5px;"></td> <td style="padding: 0 5px;"></td> <td style="padding: 0 5px;">S</td> <td style="padding: 0 5px;">16</td> </tr> </table> <p>2010</p> </div> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p>	T	1	S	R	18	E			S	9	—			1/4									S	16
T	1	S	R	18	E																				
		S	9	—																					
	1/4																								
				S	16																				

Survey of the Subdivisional Lines,
T. 1 S., R. 18 E., Gila and Salt River Meridian, Arizona

CHAINS	
80.00	<p>The cor. of secs. 8, 9, 16 and 17.</p> <p>Terrain, rolling. Soil, silted sandy loam. Timber, mesquite; undergrowth, creosote and Mormon Tea.</p> <hr/> <p>N. 0°02' W., bet. secs. 8 and 9.</p> <p>Over rolling and broken terrain.</p>
13.25	Center of Arizona Eastern railroad tracks, bears N. 85° E. and S. 85° W.
38.80	Gilson Wash, 100 ft. wide, 4 ft. deep, drains S. 55° W. from N. 60° E.
40.00	<p>Point for the 1/4 sec. cor. of secs. 8 and 9.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, underpinned with a galvanized iron pipe, 1 1/2 ins. diam., 5 ft. long, with brass cap mkd.</p> <div style="text-align: center;"> <p>T 1 S R 18 E</p> <p>1/4</p> <p>S 8 S 9</p> <p>2010</p> </div> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p> <p>Raise an accessory mound of stone 2 ft. base, 2 ft. high, W. of the cor.</p>
61.40	Indian Route No. 6, asphalt surfaced, 26 ft. wide, bears N. 80° E. and S. 80° W.
80.00	<p>Point for the cor. of secs. 4, 5, 8 and 9.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, in a collar of stone, with brass cap mkd.</p> <div style="text-align: center;"> <p>T 1 S R 18 E</p> <p>S 5 S 4</p> <hr style="width: 50%; margin: 0 auto;"/> <p>S 8 S 9</p> <p>2010</p> </div> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p>

Survey of the Subdivisional Lines,
T. 1 S., R. 18 E., Gila and Salt River Meridian, Arizona

CHAINS	
	<p>Raise an accessory mound of stone 2 ft. base, 2 ft. high, W. of the cor.</p> <p>Terrain, rolling. Soil, sandy loam. Timber, mesquite; undergrowth, creosote, cats claw and yucca.</p> <hr/> <p>From the cor. of secs. 3, 4, 9 and 10.</p> <p>S. 89°48' W., bet. secs. 4 and 9.</p> <p>Over rolling terrain.</p>
39.35	Wash, 15 ft. wide, 3 ft. deep, drains S. 35° E. from N. 35° W.
40.00	<p>Point for the 1/4 sec. cor. of secs. 4 and 9.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, in a collar of stone, with brass cap mkd.</p> <div style="text-align: center;"> <p>T 1 S R 18 E</p> <p>S 4</p> <p>1/4 ———</p> <p>S 9</p> <p>2010</p> </div> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p> <p>Raise a mound of stone, 2 ft. base, 2 ft. high, N of cor.</p>
80.00	<p>The cor. of secs. 4, 5, 8 and 9.</p> <p>Terrain, rolling. Soil, sandy loam. Timber, mesquite; undergrowth, creosote, cats claw and yucca.</p> <hr/> <p>N. 0°02' W., bet. secs. 4 and 5.</p> <p>Over rolling terrain.</p>
40.00	<p>Point for the 1/4 sec. cor. of secs. 4 and 5.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, in a collar of stone, with brass cap mkd.</p> <div style="text-align: center;"> <p>T 1 S R 18 E</p> <p>1/4</p> <p>S 5 S 4</p> <p>2010</p> </div>

**Survey of the Subdivisional Lines,
T. 1 S., R. 18 E., Gila and Salt River Meridian, Arizona**

CHAINS							
61.47	<p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p> <p>Raise an accessory mound of stone 2 ft. base, 2 ft. high, W. of the cor.</p> <p>Point for the closing cor. of secs. 4 and 5, on the N. Tp. bdy., at intersection with the Gila and Salt River base line.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center;"> <table style="margin: auto;"> <tr><td>T 1 N R 17 E</td></tr> <tr><td style="border-bottom: 1px solid black;">S 36</td></tr> <tr><td style="border-left: 1px solid black; border-right: 1px solid black;">S 5</td></tr> <tr><td style="border-left: 1px solid black; border-right: 1px solid black;">C</td></tr> <tr><td style="border-left: 1px solid black; border-right: 1px solid black;">S 4</td></tr> <tr><td>T 1 S R 18 E</td></tr> </table> <p>2010</p> </div> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p> <p>Raise an accessory mound of stone, 3 ft. base, 2 ft. high, S. of the cor.</p> <p>From this cor. point, the stan. cor. of Tps. 1 N., Rs. 17 and 18 E., bears N. 89°59' E., 18.04 chs. dist., monumented with an iron pipe, 3 ins. diam., firmly set, projecting 27 ins. above ground, in a supporting mound of stone, 4 ft. base, to top, with brass cap mkd. SC T1N R17E R18E S36 S31 2010 1915.</p> <p>From this same cor. point, the stan. 1/4 sec. cor. of sec. 36 only, T. 1 N., R. 17 E., bears S. 89°59' W., 21.97 chs. dist., monumented with a stainless steel pipe, 2 1/2 ins. diam., firmly set, flush with the ground, in a collar of stone, with brass cap mkd. SC T1N R17E 1/4 S36 2010.</p> <p>Land, rolling. Soil, sandy loam. Timber, mesquite; undergrowth, creosote, Mormon Tea and grasses.</p> <hr/> <p>Point for the 1/4 sec. cor. of sec. 4 only, at midpoint on the N. bdy. of sec. 4.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 27 ins. in the ground, in a collar of stone, with brass cap mkd.</p>	T 1 N R 17 E	S 36	S 5	C	S 4	T 1 S R 18 E
T 1 N R 17 E							
S 36							
S 5							
C							
S 4							
T 1 S R 18 E							

Survey of the Subdivisional Lines,
T. 1 S., R. 18 E., Gila and Salt River Meridian, Arizona

CHAINS	
	T 1 N R 18 E <hr style="width: 10%; margin: auto;"/> 1/4 S 4 T 1 S R 18 E 2010
	<p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p> <p>Raise an accessory mound of stone, 3 ft. base, 3 ft. high, N. of the cor.</p> <p>From this cor. point, the stan. 1/4 sec. cor. of sec. 31 only, T. 1 N., R. 18 E., bears East, 18.065 chs. dist., hereinbefore described.</p> <p>From this same cor. point, the stan. cor. of Tps. 1 N., Rs. 17 and 18 E., bears West, 21.96 chs. dist., hereinbefore described.</p> <hr/> <p>From the cor. of secs. 5, 6, 31 and 32, on the S bdy. of the Tp., hereinbefore described.</p> <p>N. 0°03' W., bet. secs. 31 and 32.</p> <p>Over broken terrain.</p>
40.00	<p>Point for the 1/4 sec. cor. of secs. 31 and 32.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;"> T 1 S R 18 E 1/4 S 31 S 32 2010 </p> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p> <p>Raise an accessory mound of stone 3 ft. base, 2 ft. high, W. of the cor.</p>
80.00	<p>Point for the cor. of secs. 29, 30, 31 and 32.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p>

Survey of the Subdivisional Lines,
T. 1 S., R. 18 E., Gila and Salt River Meridian, Arizona

CHAINS	
	T 1 S R 18 E S 30 S 29 S 31 S 32 2010
	Deposit a magnet, in a white plastic case, at the base of the stainless steel post. Raise an accessory mound of stone 3 ft. base, 2 ft. high, W. of the cor. Terrain, broken. Soil, coarse loam. Timber, mesquite; undergrowth, creosote, cats claw and yucca.
	<hr/> From the cor. of secs. 28, 29, 32 and 33. S. 89°48' W., bet. secs. 29 and 32. Over rolling terrain.
40.00	Point for the 1/4 sec. cor. of secs. 29 and 32. Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, in a collar of stone, with brass cap mkd.
	T 1 S R 18 E S 29 1/4 ——— S 32 2010
80.00	Deposit a magnet, in a white plastic case, at the base of the stainless steel post. The cor. of secs. 29, 30, 31 and 32. Terrain, rolling. Soil, sandy loam. Timber, none; undergrowth, creosote, cats claw and yucca.
	<hr/> S. 89°47' W., bet. secs. 30 and 31. Over rolling terrain.
40.00	Point for the 1/4 sec. cor. of secs. 30 and 31.

Survey of the Subdivisional Lines,
T. 1 S., R. 18 E., Gila and Salt River Meridian, Arizona

CHAINS	
	<p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 27 ins. in the ground, in a collar of stone, underpinned with a steel "T-post" fence post, 5 ft. long, with brass cap mkd.</p> <p style="text-align: center;">T 1 S R 18 E S 30 1/4 ——— S 31</p> <p style="text-align: center;">2010</p> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p> <p>Cor. is located on left bank of small drainage, 130 ft. wide, drains W.</p>
78.34	<p>The cor. of secs. 25, 30, 31 and 36, on the W. bdy. of the Tp., monumented with a stainless steel post, 28 ins. long, 2 1/2 ins. diam., loosely set, projecting 10 ins. above ground, with brass cap mkd. T1S R17E R18E S25 S30 S36 S31 2001. Add the marks 2010 to the brass cap. Raise a mound of stone around monument, 4 ft. base, to top, to divert flow around cor.</p> <p>Cor. is located in small drainage, 13 ft. wide, 1 ft. deep, drains N. 50° E. from S. 70° W.</p> <p>Terrain, rolling. Soil, sandy loam. Timber, mesquite; undergrowth, creosote, cats claw and yucca.</p> <hr/> <p>From the cor. of secs. 29, 30, 31 and 32.</p> <p>N. 0°03' W., bet. secs. 29 and 30.</p> <p>Over rolling terrain.</p>
40.00	<p>Point for the 1/4 sec. cor. of secs. 29 and 30.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 21 ins. in the ground, in a collar of stone, with brass cap mkd.</p> <p style="text-align: center;">T 1 S R 18 E 1/4 S 30 S 29</p> <p style="text-align: center;">2010</p> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p>

Survey of the Subdivisional Lines,
T. 1 S., R. 18 E., Gila and Salt River Meridian, Arizona

CHAINS									
56.45	Arizona State Highway No. 70, asphalt surfaced, 34 ft. wide, bears S. 68° E. and N. 68° W.								
80.00	Point for the cor. of secs. 19, 20, 29 and 30. Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 27 ins. in the ground, with brass cap mkd. <div style="text-align: center;"> <table style="margin: auto;"> <tr><td>T 1 S</td><td>R 18 E</td></tr> <tr><td>S 19</td><td>S 20</td></tr> <tr><td>S 30</td><td>S 29</td></tr> </table> <p>2010</p> </div> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p> <p>Raise an accessory mound of stone 2 ft. base, 2 ft. high, W. of the cor.</p> <p>Terrain, rolling. Soil, sandy loam. Timber, none; undergrowth, creosote, cats claw and yucca.</p> <hr/> <p>From the cor. of secs. 20, 21, 28 and 29.</p> <p>S. 89°48' W., bet. secs. 20 and 29.</p> <p>Over rolling terrain.</p>	T 1 S	R 18 E	S 19	S 20	S 30	S 29		
T 1 S	R 18 E								
S 19	S 20								
S 30	S 29								
40.00	Point for the 1/4 sec. cor. of secs. 20 and 29. Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 23 ins. in the ground, in a collar of stone, with brass cap mkd. <div style="text-align: center;"> <table style="margin: auto;"> <tr><td>T 1 S</td><td>R 18 E</td></tr> <tr><td>S 20</td><td></td></tr> <tr><td>1/4</td><td>—</td></tr> <tr><td>S 29</td><td></td></tr> </table> <p>2010</p> </div> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p> <p>Cor. is located in N. track of abandoned 2 track trail, 9 ft. wide, bears S. and N. 20 W.</p>	T 1 S	R 18 E	S 20		1/4	—	S 29	
T 1 S	R 18 E								
S 20									
1/4	—								
S 29									
41.90	Underground El Paso gas line with two track road alongside, bears S. 58° E. and N. 58° W.								
80.00	The cor. of secs. 19, 20, 29 and 30.								

Survey of the Subdivisional Lines,
T. 1 S., R. 18 E., Gila and Salt River Meridian, Arizona

CHAINS	
	<p>Terrain, rolling. Soil, sandy loam. Timber, none; undergrowth, creosote, cats claw and yucca.</p> <hr/> <p>S. 89°47' W., bet. secs. 19 and 30.</p> <p>Over nearly level ground.</p>
40.00	<p>Point for the 1/4 sec. cor. of secs. 19 and 30.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center;"> <p>T 1 S R 18 E S 19 1/4 ——— S 30</p> <p>2010</p> </div> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p> <p>Raise an accessory mound of stone 2 ft. base, 2 ft. high, N. of the cor.</p>
59.75	<p>Arizona State Highway No. 70, asphalt surfaced, 34 ft. wide, bears S. 68° E. and N. 68° W.</p>
78.26	<p>The cor. of secs. 19, 24, 25 and 30, on the W. bdy. of the Tp., monumented with a stainless steel post, 28 ins. long, 2 1/2 ins. diam., firmly set, projecting 4 ins. above ground, in a collar of stone, with brass cap mkd. T1S R17E R18E S24 S19 S25 S30 2001. Add the marks 2010 to the brass cap.</p> <p>Terrain, rolling. Soil, sandy loam. Timber, mesquite; undergrowth, creosote, cats claw and yucca.</p> <hr/> <p>From the cor. of secs. 19, 20, 29 and 30.</p> <p>N. 0°03' W., bet. secs. 19 and 20.</p>
31.80	<p>Underground El Paso gas line with two track road alongside, bears S. 53° E. and N. 53° W.</p>
40.00	<p>Point for the 1/4 sec. cor. of secs. 19 and 20.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with brass cap mkd.</p>

Survey of the Subdivisional Lines,
T. 1 S., R. 18 E., Gila and Salt River Meridian, Arizona

CHAINS	
	T 1 S R 18 E 1/4 S 19 S 20 2010
	Deposit a magnet, in a white plastic case, at the base of the stainless steel post.
	Raise an accessory mound of stone 2 ft. base, 2 ft. high, W. of the cor.
80.00	Point for the cor. of secs. 17, 18, 19 and 20. Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 27 ins. in the ground, with brass cap mkd.
	T 1 S R 18 E S 18 S 17 S 19 S 20 2010
	Deposit a magnet, in a white plastic case, at the base of the stainless steel post.
	Raise an accessory mound of stone 3 ft. base, 2 ft. high, W. of the cor.
	Land, rolling. Soil, gravely loam. Timber, mesquite; undergrowth, creosote, cats claw, sotol and Mormon Tea.
	<hr/> From the cor. of secs. 16, 17, 20 and 21. S. 89°48' W., bet. secs. 17 and 20.
40.00	Point for the 1/4 sec. cor. of secs. 17 and 20. Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with brass cap mkd.
	T 1 S R 18 E S 17 1/4 ——— S 20 2010
	Deposit a magnet, in a white plastic case, at the base of the stainless steel post.

Survey of the Subdivisional Lines,
T. 1 S., R. 18 E., Gila and Salt River Meridian, Arizona

CHAINS	
	Raise an accessory mound of stone, 2 ft. base, 2 ft. high, N. of the cor.
80.00	The cor. of secs. 17, 18, 19 and 20. Terrain, rolling. Soil, sandy loam. Timber, mesquite; undergrowth, creosote, cats claw, sotol and yucca.

	S. 89°47' W., bet. secs. 18 and 19. Over rolling terrain.
40.00	Point for the 1/4 sec. cor. of secs. 18 and 19. Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 16 ins. in the ground, in a mound of stone, 3 ft. base, to top, with brass cap mkd.
	T 1 S R 18 E S 18 1/4 ——— S 19 2010
	Deposit a magnet, in a white plastic case, at the base of the stainless steel post.
67.50	Underground El Paso gas line with two track road alongside, bears S. 60° E. and N. 60° W.
78.18	The cor. of secs. 13, 18, 19 and 24, on the W. bdy. of the Tp., monumented with a stainless steel post, 28 ins. long, 2 1/2 ins. diam., loosely set, projecting 8 ins. above ground, with brass cap mkd. T1S R17E R18E S13 S18 S24 S19 2001. Add the marks 2010 to the brass cap. Encircle post with collar of stone. Terrain, rolling. Soil, gravelly sandy loam. Timber, palo negro and ocotillo; undergrowth, creosote, cats claw and grasses.

	From the cor. of secs. 17, 18, 19 and 20. N. 0°03' W., bet. secs. 17 and 18. Over rolling and broken terrain.
40.00	Point for the 1/4 sec. cor. of secs. 17 and 18.

Survey of the Subdivisional Lines,
T. 1 S., R. 18 E., Gila and Salt River Meridian, Arizona

CHAINS	
	<p>Set a brass tablet, 3 1/4 ins. diam., 3 1/2 ins. stem, cemented in a drill hole in solid rock, with top mkd.</p> <p style="text-align: center;">T 1 S R 18 E 1/4 S 18 S 17</p> <p style="text-align: center;">2010</p> <p>Deposit a magnet at the base of the brass tablet.</p> <p>Raise an accessory mound of stone 2 ft. base, 2 ft. high, W. of the cor.</p>
80.00	<p>Point for the cor. of secs. 7, 8, 17 and 18.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T 1 S R 18 E S 7 S 8 ----- S 18 S 17</p> <p style="text-align: center;">2010</p> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p> <p>Raise an accessory mound of stone 2 ft. base, 2 ft. high, W. of the cor.</p> <p>Terrain, rolling. Soil, sandy loam. Timber, mesquite; undergrowth, creosote, cats claw and yucca.</p> <hr/> <p>From the cor. of secs. 8, 9, 16 and 17.</p> <p>S. 89°48' W., bet. secs. 8 and 17.</p> <p>Over rolling terrain.</p>
40.00	<p>Point for the 1/4 sec. cor. of secs. 8 and 17.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T 1 S R 18 E S 8 1/4 ——— S 17</p> <p style="text-align: center;">2010</p>

Survey of the Subdivisional Lines,
T. 1 S., R. 18 E., Gila and Salt River Meridian, Arizona

CHAINS	
	<p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p> <p>Raise an accessory mound of stone 2 ft. base, 2 ft. high, N. of the cor.</p>
80.00	<p>The cor. of secs. 7, 8, 17 and 18.</p> <p>Terrain, rolling. Soil, sandy loam. Timber, saguaro, palo negro and ocotillo; undergrowth, creosote, prickly pear, sotol and Mormon Tea.</p> <hr/> <p>S. 89°47' W., bet. secs. 7 and 18.</p> <p>Over rolling and broken terrain.</p>
40.00	<p>Point for the 1/4 sec. cor. of secs. 7 and 18.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 12 ins. in the ground, in a mound of stone, 3 ft. base, to top, with brass cap mkd.</p> <div style="text-align: center;"> <p>T 1 S R 18 E S 7 1/4 ——— S 18</p> <p>2010</p> </div>
78.10	<p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p> <p>The cor. of secs. 7, 12, 13 and 18, on the W. bdy. of the Tp., monumented with a stainless steel post, 28 ins. long, 2 1/2 ins. diam., firmly set, projecting 3 ins. above ground, with brass cap mkd. T1S R17E R18E S12 S7 S13 S18 2001. Add the marks 2010 to the brass cap.</p> <p>Terrain, rolling to broken. Soil, rocky loam. Timber, palo negro and mesquite; undergrowth, creosote and cats claw.</p> <hr/> <p>From the cor. of secs. 7, 8, 17 and 18.</p> <p>N. 0°03' W., bet. secs. 7 and 8.</p> <p>Over rolling to broken terrain.</p>

Survey of the Subdivisional Lines,
T. 1 S., R. 18 E., Gila and Salt River Meridian, Arizona

CHAINS	
38.65	Center of Arizona Eastern railroad tracks, bears S. 85° E. and N. 85° W.
40.00	Point for the 1/4 sec. cor. of secs. 7 and 8. Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 27 ins. in the ground, with brass cap mkd. <div style="text-align: center;"> T 1 S R 18 E 1/4 S 7 S 8 2010 </div> Deposit a magnet, in a white plastic case, at the base of the stainless steel post. Raise an accessory mound of stone 2 ft. base, 2 ft. high, W. of the cor.
60.75	Indian Route No. 6, asphalt surfaced, 26 ft. wide, bears East and West.
80.00	Point for the cor. of secs. 5, 6, 7 and 8. Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 13 ins. in the ground, in a supporting mound of stone, 4 ft. base, to top, with brass cap mkd. <div style="text-align: center;"> T 1 S R 18 E S 6 S 5 S 7 S 8 2010 </div> Deposit a magnet, in a white plastic case, at the base of the stainless steel post. Cor. is located 17 lks. N. of drainage, between hills, drains S. 45° W. from N. 45° E. Terrain, rolling. Soil, sandy loam. Timber, mesquite; undergrowth, creosote, cats claw and yucca.
40.00	<hr/> From the cor. of secs. 4, 5, 8 and 9. S. 89°48' W., bet. secs. 5 and 8. Over rolling and broken terrain. Point for the cor. of secs. 5 and 8.

Survey of the Subdivisional Lines,
T. 1 S., R. 18 E., Gila and Salt River Meridian, Arizona

CHAINS	
	<p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 10 ins. in the ground to bedrock, mkd. "X" on bedrock, in a mound of stone, 4 ft. base, to top, with brass cap mkd.</p> <p style="text-align: center;">T 1 S R 18 E S 5 1/4 ——— S 8</p> <p style="text-align: center;">2010</p> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p> <p>Cor. is located on NE slope of exposed limestone ridge, bears S. 40° E. and N. 40° W.</p>
42.65	Trail road, bears S. 30° E. and N. 30° W.
80.00	The cor. of secs. 5, 6, 7 and 8.
	<p>Terrain, rolling. Soil, rocky loam and limestone. Timber, mesquite; undergrowth, creosote, cats claw and yucca.</p> <hr/> <p>S. 89°47' W., bet. secs. 6 and 7.</p> <p>Over rolling and broken terrain.</p>
40.00	<p>Point for the 1/4 sec. cor. of secs. 6 and 7.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 27 ins. in the ground, in a collar of stone, with brass cap mkd.</p> <p style="text-align: center;">T 1 S R 18 E S 6 1/4 ——— S 7</p> <p style="text-align: center;">2010</p> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p> <p>Raise an accessory mound of stone, 2 ft. base, 2 ft. high, N. of the cor.</p> <p>Cor. is located on small spur ridge, bears N. 60° E. and S. 60° W.</p>

Survey of the Subdivisional Lines,
T. 1 S., R. 18 E., Gila and Salt River Meridian, Arizona

CHAINS	
78.02	<p>The cor. of secs. 1, 6, 7 and 12, on the W. bdy. of the Tp., monumented with a stainless steel post, 28 ins. long, 2 1/2 ins. diam., firmly set, projecting 4 ins. above ground, with brass cap mkd. T1S R17E R18E S1 S6 S12 S7 2001. Add the marks 2010 to the brass cap.</p> <p>Terrain, rolling. Soil, sandy loam. Timber, mesquite.; undergrowth, creosote, cats claw and yucca.</p> <hr/> <p>From the cor. of secs. 5, 6, 7 and 8.</p> <p>N. 0°03' W., bet. secs. 5 and 6.</p> <p>Over rolling terrain.</p>
40.00	<p>Point for the 1/4 sec. cor. of secs. 5 and 6.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center;"> <p>T 1 S R 18 E 1/4 S 6 S 5 2010</p> </div> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p> <p>Raise an accessory mound of stone 2 ft. base, 1 ft. high, W. of the cor.</p>
61.74	<p>Point for the closing cor. of secs. 5 and 6, on the N. bdy. of the Tp., at intersection with the Gila and Salt River base line.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 23 ins. in the ground, in a collar of stone, with brass cap mkd.</p> <div style="text-align: center;"> <p>T 1 N R 17 E S 35 ----- S 6 S 5 C C T 1 S R 18 E 2010</p> </div> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p> <p>Cor. is located on N. aspect of small spur ridge, bears S. 70° E. from N. 10° W.</p>

Survey of the Subdivisional Lines,
T. 1 S., R. 18 E., Gila and Salt River Meridian, Arizona

CHAINS

From this cor. point, the stan. cor. of secs. 35 and 36, T. 1 N., R. 17 E., bears East, 18.02 chs. dist., monumented with an iron pipe, 3 ins. diam., firmly set, projecting 11 ins. above ground, with brass cap mkd. SC T1N R17E S35 S36 2010 1915.

From this same cor. point, the stan. 1/4 sec. cor. of sec. 35 only, T. 1 N., R. 17 E., bears West, 21.97 chs. dist., monumented with an iron pipe, 1 in. diam., firmly set, projecting 10 ins. above ground, in a collar of stone, 3 ft. base to top, with brass cap mkd. SC T1N R17E 1/4 S35 2010 1915.

Terrain, rolling to broken.

Soil, rocky loam and limestone.

Timber, saguaro and palo negro; undergrowth, creosote, sotol and Mormon Tea.

Point for the 1/4 sec. cor. of sec. 5 only, at midpoint on the N. bdy. of sec. 5.

Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 22 ins. in the ground, in a mound of stone, 3 ft. base, to top, with brass cap mkd.

T 1 N R 17 E

1/4 S 5

T 1 S R 18 E

2010

Deposit a magnet, in a white plastic case, at the base of the stainless steel post.

Set a steel "T-post" fence post near the cor.

From this cor. point, the stan. 1/4 sec. cor. of sec. 36 only, T. 1 N., R. 17 E., bears N. 89°59' E., 18.03 chs. dist., hereinbefore described.

From this same cor. point, the stan. cor. of secs. 35 and 36, T. 1 N., R. 17 E., bears S. 89°59' W., 21.98 chs. dist.. hereinbefore described.

Point for the 1/4 sec. cor. of sec. 6 only, at 40.00 chs. in westing from the closing cor. of secs. 5 and 6, on the N. bdy. of sec. 6.

Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, in a collar of stone, underpinned with a steel fence post, 5 ft. long, with brass cap mkd.

Survey of the Subdivisional Lines,
T. 1 S., R. 18 E., Gila and Salt River Meridian, Arizona

CHAINS

T 1 N R 17 E

1/4 S 6

T 1 S R 18 E

2010

Deposit a magnet, in a white plastic case, at the base of the stainless steel post.

Raise an accessory mound of stone 2 ft. base, 2 ft. high, S. of the cor.

From this cor. point, the stan. 1/4 sec. cor. of sec. 35 only, T. 1 N., R. 17 E., bears East, 18.03 chs. dist., hereinbefore described.

From this same cor. point, the stan. cor. of secs. 34 and 35, T. 1 N., R. 17 E., bears West, 21.96 chs. dist., monumented with an iron pipe, 3 ins. diam., firmly set, projecting 13 ins. above the ground, in a collar of stone, with brass cap mkd. SC T1N R17E S34 S35 2010 2001 1915.

T. 1 S., R. 18 E., Gila and Salt River Meridian, Arizona

CHAINS

GENERAL DESCRIPTION

This township is located within the San Carlos Apache Indian Reservation. The community of San Carlos is in the Northeast corner of the Township. The terrain is rolling and broken, with mesa's and ravines throughout. Access is primarily cross country with only small sections reached from various unimproved roads.

The elevation varies from 2,700 ft. to 3,500 ft. on top of the Mesa. The San Carlos river lays along the East end of the Township.

U. S. Highway 70 runs southeasterly and northwesterly through the township.

The mean magnetic declination of 10 1/2° E. was derived from the National Geophysical Data Center's magnetic declination calculator, GEOMAG v6.0, utilizing the International Geomagnetic Reference Field Model for years 2005 through 2010, for the dates of the survey.

**UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT**

FIELD ASSISTANTS

NAMES	CAPACITY
Christopher P. McDonald	Cadastral Surveyor
Blas J. Urena	Survey Technician
Mark R. Searles	Survey Technician
Robert C. Tessely	Survey Technician
Wilfred Dude	BIA Survey Technician
Oliver Russell	BIA Survey Technician
Malcolm Hooke	BIA Survey Technician
David Thompson	BIA Survey Technician
Robert Hetzler	BIA GIS Technician

CERTIFICATE OF SURVEY

I, Geoffrey A. Graham, Cadastral Surveyor, HEREBY CERTIFY upon honor, that in pursuance of special instructions bearing date of the 15th day of March, 2010, I have surveyed the south and east boundaries and the subdivisional lines, Township 1 South, Range 18 East, of the Gila and Salt River Meridian, in the State of Arizona, which are represented in the foregoing field notes as having been executed by me and under my direction. Said survey has been made in strict conformity with said special instructions, the Manual of Surveying Instructions for the Survey of the Public Lands of the United States, 2009, and in specific manner described in the foregoing field notes.

1/20/2012
(Date)

Geoffrey A. Graham
(Cadastral Surveyor)

CERTIFICATE OF APPROVAL

BUREAU OF LAND MANAGEMENT
Phoenix, Arizona

The foregoing field notes of the survey of the south and east boundaries and subdivisional lines, Township 1 South, Range 18 East, of the Gila and Salt River Meridian, in the State of Arizona, executed by Geoffrey A. Graham, Cadastral Surveyor, having been critically examined and found correct, are hereby approved.

1/26/2012
(Date)

Stephen K. Hansen
(Chief Cadastral Surveyor for Arizona)

~~CERTIFICATE OF TRANSCRIPT~~

~~I CERTIFY That the foregoing transcript of the field notes of the above described surveys in T. 1 S., R. 18 E., Gila and Salt River Meridian, Arizona, is a true copy of the original field notes.~~

~~(Date)~~

~~(Chief Cadastral Surveyor for Arizona)~~