

ORIGINAL

**UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT**

FIELD NOTES
OF THE
SURVEY OF THE SOUTH AND NORTH BOUNDARIES,
THE SUDIVISIONAL LINES
AND
THE SUBDIVISION OF CERTAIN SECTIONS,
TOWNSHIP 35 NORTH, RANGE 24 EAST,
OF THE GILA AND SALT RIVER MERIDIAN,
IN THE STATE OF ARIZONA.

EXECUTED BY

Alvina A. Begaye, Cadastral Surveyor

Under Special Instructions dated and approved August 23, 2010, which provided for the surveys included under Group No. 1079, and assignment instructions dated August 23, 2010.

Survey commenced September 13, 2010

Survey completed November 9, 2010

INDEX DIAGRAM

TOWNSHIP 35 NORTH RANGE 24 EAST
GILA AND SALT RIVER MERIDIAN, ARIZONA

14 6 57 56	13 5 46 56	12 4 37 45	11 3 29 37	10 2 22 29	9 1 21
7 55 54	8 44 54	9 36 44	10 28 35	11 20 27	12 20
18 53 52	17 43 52	16 35 42	15 27 34	14 19 26	13 18
19 51 50	20 41 50	21 33 41	22 25 33	23 18 25	24 17
30 49 48	29 40 47	28 32 39	27 24 31	26 16 23	25 16
31 47 8	32 38 8	33 30 7	34 22 6	35 15 5	36 4

Subdivision of Section 27Pages 57-58
 Subdivision of Section 28Pages 58-59
 Subdivision of Section 29Pages 59-60
 Subdivision of Section 30Pages 60-61
 Subdivision of Section 34Pages 61-62
 Subdivision of Section 35Page 63

T. 35 N., R. 24 E., Gila and Salt River Meridian, Arizona

CHAINS

The following field notes describe the survey of the south and north boundaries, the subdivisional lines and the subdivision of certain sections, Township 35 North, Range 24 East, Gila and Salt River Meridian, Arizona.

The history of surveys pertaining to this survey is as follows:

The Eighth Standard Parallel North (south boundary), Township 33 North, Range 24 East, was surveyed by Leonard R. Sandoval in 1989-90. The south, east and north boundaries, Township 35 North, Ranges 23 East, and the east boundary, Township 36 North, Range 23 East, were surveyed by Jones Curtiss in 1998. The survey of The Sixth Guide Meridian East (west boundary) and the north boundary, Township 34 North, Range 25 East, were surveyed by Leonard R. Sandoval in 1999. The survey of The Sixth Guide Meridian East (west boundary) and north boundary, Township 35 North, Range 25 East, and the survey of The Sixth Guide Meridian East (west boundary), Township 36 North, Range 25 East, were surveyed by Jones Curtiss in 1999.

The survey was executed in accordance with the specifications as set forth in the Manual of Surveying Instructions for the Survey of the Public Lands of the United States, 2009, and the Special Instructions dated August 23, 2010, for Group Number 1079, Arizona.

The true meridian direction and length of all lines were determined by real time kinematic global positioning system observations using Trimble Navigation 5700 model receivers.

Geodetic control was derived from Global Positioning System (GPS) static observations post processed by National Geodetic Survey, Online Positioning User Service (OPUS), utilizing Continuously Operating Reference Stations (CORS) SPIDERROCKAZ2005, MONTICELLOUT2006, CHACOCNHP_NM2005. The NAD 83 (CORS96) (EPOCH: 2002), geographic position of the southeast township corner, is as follows:

Latitude: 36°23'22.57" N. Longitude: 109°42'08.86" W.

The NAD 83 (CORS96) (EPOCH: 2002), geographic position of the northwest township corner, is as follows:

Latitude: 36°28'35.71" N. Longitude: 109°48'35.35" W.

The mean magnetic declination is 10 3/4° E.

Survey of the South Boundary
T. 35 N., R. 24 E., Gila and Salt River Meridian, Arizona

CHAINS	
	Beginning at the cor. of Tps. 34 and 35 N., Rs. 24 and 25 E., monumented with a stainless steel post, 2 1/2 ins diam., firmly set, projecting 2 ins. above ground, with brass cap mkd. T35N R24E R25E S36 S31 S1 S6 T34N 1999.
	Add the marks 2010 to the brass cap.
	West, bet. secs. 1 and 36.
	Over rolling land.
28.60	Trail road, bears East and West.
40.00	Point for the 1/4 sec. cor. of secs. 1 and 36.
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.
	T 35 N R 24 E S 36 1/4 ——— S 1 T 34 N 2010
	Deposit a magnet, in a white plastic case, at the base of the stainless steel post.
54.10	Trail road, bears N. 10° E. and S. 10° W.
64.65	Power line, bears S. 70° E. and N. 70° W.
68.95	Graded road, 20 ft. wide, bears East and West.
73.30	Power line, bears N. 40° E. and S. 40° W.
80.00	Point for the cor. of secs. 1, 2, 35 and 36.
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.
	T 35 N R 24 E S 35 S 36 S 2 S 1 T 34 N 2010
	Deposit a magnet, in a white plastic case, at the base of the stainless steel post.

Survey of the South Boundary
T. 35 N., R. 24 E., Gila and Salt River Meridian, Arizona

CHAINS	
	<p>Land, rolling. Soil, sand and sandy clay. No timber; undergrowth, scattered brush and native grasses.</p> <hr/> <p>West, bet. secs. 2 and 35.</p> <p>Over rolling land.</p>
5.10	Graded road, 20 ft. wide, bears N. 35° E. and S. 35° W.
16.90	Graded road, 30 ft. wide, bears S. 20° E. and N. 20° W.
29.60	E. right-of-way fence of BIA Route 59, 5 strand barbed wire, parallels highway.
32.10	BIA Route 59, asphalt surface, 50 ft. wide, bears S. 53° E. and N. 53° W.
34.60	W. right-of-way fence of BIA Route 59, 5 strand barbed wire, parallels highway.
40.00	Point for the 1/4 sec. cor. of secs. 2 and 35.
	<p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T 35 N R 24 E S 35 1/4 ——— S 2 T 34 N</p> <p style="text-align: center;">2010</p>
	<p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p>
51.55	High voltage transmission line, bears S. 45° E. and N. 45° W.
61.80	Earthen levee, 10 ft. wide, 30 ft. base, 10 ft. high, bears N. 40° E. and S. 40° W.
80.00	Point for the cor. of secs. 2, 3, 34 and 35.
	<p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p>

Survey of the South Boundary
T. 35 N., R. 24 E., Gila and Salt River Meridian, Arizona

CHAINS	
	T 35 N R 24 E S 34 S 35 S 3 S 2 T 34 N 2010 Deposit a magnet, in a white plastic case, at the base of the stainless steel post. Land, rolling. Soil, sand and sandy clay. No timber; undergrowth, scattered brush and native grasses.
	West bet. secs. 3 and 34. Over rolling land.
40.00	Point for the 1/4 sec. cor. of secs. 3 and 34. Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.
	T 35 N R 24 E S 34 1/4 ——— S 3 T 34 N 2010 Deposit a magnet, in a white plastic case, at the base of the stainless steel post.
80.00	Point for the cor. of secs. 3, 4, 33 and 34. Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.
	T 35 N R 24 E S 33 S 34 S 4 S 3 T 34 N 2010 Deposit a magnet, in a white plastic case, at the base of the stainless steel post.

Survey of the South Boundary
T. 35 N., R. 24 E., Gila and Salt River Meridian, Arizona

CHAINS	
	<p>Land, rolling. Soil, sand and sandy clay. No timber; undergrowth, scattered brush and native grasses.</p> <hr/> <p>West, bet. secs. 4 and 33. Over rolling land.</p>
40.00	<p>Point for the 1/4 sec. cor. of secs. 4 and 33. Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T 35 N R 24 E S 33 1/4 ——— S 4 T 34 N</p> <p style="text-align: center;">2010</p> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p> <p>Set a steel fence post nearby.</p> <p>Cor. is located 94 lks. W. of Apache County Road C571 a graded road, 30 ft. wide, bears N. 20° E. and S. 20° W.</p>
62.00	<p>Southeast cor. of house, 24 ft. X 40 ft., bears S., 19 lks. dist.</p>
73.10	<p>Trail road, bears S. 30° E. and N. 30° W.</p>
73.75	<p>Power line, bears S. 25° E. and N. 35° W.</p>
80.00	<p>Point for the cor. of secs. 4, 5, 32 and 33. Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T 35 N R 24 E S 32 S 33 S 5 S 4 T 34 N</p> <p style="text-align: center;">2010</p> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p> <p>Set a steel fence post nearby.</p>

Survey of the South Boundary
T. 35 N., R. 24 E., Gila and Salt River Meridian, Arizona

CHAINS	
	<p>From this cor., the SE cor. of a house, 24 X 38 ft., bears N. 71° W., 2.85 chs. dist.</p> <p>Land, rolling. Sand, sand and sandy clay. No timber; undergrowth, scattered brush and native grasses.</p> <hr/> <p>West, bet. secs. 5 and 32.</p> <p>Over rolling land.</p>
40.00	<p>Point for the 1/4 sec. cor. of secs. 5 and 32.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;"> T 35 N R 24 E S 32 1/4 ——— S 5 T 34 N 2010 </p> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p>
54.95	<p>Graded road, 25 ft. wide, bears N. 40° E. and S. 40° W.</p>
80.00	<p>Point for the cor. of secs. 5, 6, 31 and 32.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;"> T 35 N R 24 E S 31 S 32 ——— ——— S 6 S 5 T 34 N 2010 </p> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p> <p>Land, rolling. Soil, sand and sandy clay. No timber; undergrowth, scattered brush and native grasses.</p> <hr/> <p>West, bet. secs. 6 and 31.</p> <p>Over rolling land.</p>

Survey of the South Boundary
T. 35 N., R. 24 E., Gila and Salt River Meridian, Arizona

CHAINS	
10.40	Power line, bears N. 70° E. and S. 70° W.
24.05	Navajo Route 8090, a graded road, 25 ft. wide, bears S. 55° E. and N. 55° W.
30.95	Graded road, 25 ft. wide, bears N. 65° E. and S. 65° W.
40.00	Point for the 1/4 sec. cor. of secs. 6 and 31. Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd. <div style="text-align: center;"> T 35 N R 24 E S 31 1/4 ——— S 6 T 34 N 2010 </div>
	Deposit a magnet, in a white plastic case, at the base of the stainless steel post.
78.93	The cor. of Tps. 34 and 35 N., Rs. 23 and 24 E., monumented with a stainless steel post, 2 1/2 ins. diam., firmly set, projecting 1 in. above ground, with brass cap mkd. T35N R23E R24E S36 S31 S1 S6 T34N 1998. Add the marks 2010 to the brass cap. Land, rolling. Soil, sand and sandy clay. Timber, piñon and juniper; undergrowth, scattered brush and native grasses.
<hr/> Survey of the North Boundary, T. 35 N., R. 24 E., Gila and Salt River Meridian, Arizona <hr/>	
	From the cor. of Tps. 35 and 36 N., Rs. 24 and 25 E., Monumented with a stainless steel post, 2 1/2 ins. diam., firmly set, projecting 7 ins. above ground, with brass cap mkd. T36N R24E R25E S36 S31 S1 S6 T35N 1999. Add the marks 2010 to the brass cap.
	West, bet. secs. 1 and 36. Over rolling land.
20.90	Trail road, bears N. 45° E. and S. 45° W.
40.00	Point for the 1/4 sec. cor. of secs. 1 and 36.

Survey of the North Boundary,
T. 35 N., R. 24 E., Gila and Salt River Meridian, Arizona

CHAINS	
	<p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T 36 N R 24 E S 36 1/4 ——— S 1 T 35 N</p> <p style="text-align: center;">2010</p> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p>
44.40	Barbed wire fence, bears N. 40° E. and S. 40° W.
46.20	Navajo Route N-18 a graded road, 25 ft. wide, bears S. 50° E. and N. 50° W.
80.00	Point for the cor. of secs. 1, 2, 35 and 36.
	<p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T 36 N R 24 E S 35 S 36 S 2 S 1 T 35 N</p> <p style="text-align: center;">2010</p> <p>Land, rolling. Soil, sand and sandy clay. No timber; undergrowth, scattered brush and native grasses.</p> <hr/> <p>West, bet. secs. 2 and 35.</p> <p>Over rolling land.</p>
39.10	Power line, bears N. and S.
40.00	Point for the 1/4 sec. cor. of secs. 2 and 35.
	<p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p>

**Survey of the North Boundary,
T. 35 N., R. 24 E., Gila and Salt River Meridian, Arizona**

CHAINS	
	T 36 N R 24 E S 35 1/4 ——— S 2 T 35 N 2010
	Deposit a magnet, in a white plastic case, at the base of the stainless steel post.
80.00	Point for the cor. of secs. 2, 3, 34 and 35. Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24ins. in the ground, with brass cap mkd.
	T 36 N R 24 E S 34 S 35 S 3 S 2 T 35 N 2010
	Deposit a magnet, in a white plastic case, at the base of the stainless steel post.
	Land, rolling. Soil, sand and sandy clay. No timber; undergrowth, scattered brush and native grasses.
	West, bet. secs. 3 and 34. Over, rolling land.
22.00	Barbed wire fence, bears S. 25° E. and N. 25° W.
40.00	Point for the 1/4 sec. cor. of secs. 3 and 34. Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.
	T 36 N R 24 E S 34 1/4 ——— S 3 T 35 N 2010
	Deposit a magnet, in a white plastic case, at the base of the stainless steel post.

**Survey of the North Boundary,
T. 35 N., R. 24 E., Gila and Salt River Meridian, Arizona**

CHAINS											
72.00	Trail road, bears N. 30° E. and S. 30° E.										
80.00	<p>Point for the cor. of secs. 2, 3, 34 and 35.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center;"> <table style="margin: auto;"> <tr> <td>T 36 N</td> <td>R 24 E</td> </tr> <tr> <td>S 33</td> <td>S 34</td> </tr> <tr> <td style="border-left: 1px solid black;">S 4</td> <td style="border-left: 1px solid black;">S 3</td> </tr> <tr> <td colspan="2">T 35 N</td> </tr> </table> <p>2010</p> </div> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p> <p>Land, rolling. Soil, sand and sandy clay. No timber; undergrowth, scattered brush and native grasses.</p> <hr/> <p>West, bet. secs. 4 and 33.</p> <p>Over rolling land.</p>	T 36 N	R 24 E	S 33	S 34	S 4	S 3	T 35 N			
T 36 N	R 24 E										
S 33	S 34										
S 4	S 3										
T 35 N											
40.00	<p>Point for the 1/4 sec. cor. of secs. 4 and 33.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center;"> <table style="margin: auto;"> <tr> <td>T 36 N</td> <td>R 24 E</td> </tr> <tr> <td>S 33</td> <td></td> </tr> <tr> <td>1/4 ———</td> <td></td> </tr> <tr> <td>S 4</td> <td></td> </tr> <tr> <td colspan="2">T 35 N</td> </tr> </table> <p>2010</p> </div> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p>	T 36 N	R 24 E	S 33		1/4 ———		S 4		T 35 N	
T 36 N	R 24 E										
S 33											
1/4 ———											
S 4											
T 35 N											
80.00	<p>Point for the cor. of secs. 4, 5, 32 and 33.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p>										

**Survey of the North Boundary,
T. 35 N., R. 24 E., Gila and Salt River Meridian, Arizona**

CHAINS	
	T 36 N R 24 E S 32 S 33 S 5 S 4 T 35 N 2010
	Deposit a magnet, in a white plastic case, at the base of the stainless steel post. Land, rolling. Soil, sand and sandy clay. No timber; undergrowth, scattered brush and native grasses.
	<hr/> West, bet. secs. 5 and 32. Over rolling land.
8.60	Navajo Route 8090, graded road, 30 ft. wide, bears N. and S.
24.00	Trail road, bears S. 45° E. and N. 45° W.
28.45	Power line, bears S. 55° E. and N. 55° W.
40.00	Point for the 1/4 sec. cor. of secs. 5 and 32. Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.
	T 36 N R 24 E S 32 1/4 ——— S 5 T 35 N 2010
	Deposit a magnet, in a white plastic case, at the base of the stainless steel post.
64.75	Trail road, bears N. 30° E. and S. 30° W.
80.00	Point for the cor. of secs. 5, 6, 31 and 32. Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.

Survey of the North Boundary,
T. 35 N., R. 24 E., Gila and Salt River Meridian, Arizona

CHAINS	
	T 36 N R 24 E S 31 S 32 S 6 S 5 T 35 N 2010
	Deposit a magnet, in a white plastic case, at the base of the stainless steel post. Land, rolling. Soil, sand and sandy clay. No timber; undergrowth, scattered brush and native grasses.
	<hr/> West, bet. secs. 6 and 31. Over rolling land.
2.70	Trail road, bears S. 50° E. and N. 50° W.
7.80	Graded road, 30 ft. wide, bears N. 35° E. and S. 35° W.
9.40	Power line, bears N. 40° E. and S. 40° W.
40.00	Point for the 1/4 sec. cor. of secs. 6 and 31. Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.
	T 36 N R 24 E S 31 1/4 ——— S 6 T 35 N 2010
	Deposit a magnet, in a white plastic case, at the base of the stainless steel post.
78.39	The cor. of Tps. 35 and 36 N., Rs. 23 and 24 E., monumented with a stainless steel post, 2 1/2 ins. diam., firmly set, projecting 3 ins. above ground, with brass cap mkd. T36N R23E R24E S36 S31 S1 S6 T35N 1998. Add the marks 2010 to the brass cap. Land, rolling. Soil, sand and sandy clay. No timber; undergrowth, scattered brush and native grasses.
	<hr/>

**Survey of the Subdivisional Lines,
T. 35 N., R. 24 E., Gila and Salt River Meridian, Arizona**

CHAINS	
	<p>From the cor. of secs. 1, 2, 35 and 36, on the S. bdy. of the Tp., hereinbefore described.</p> <p>N. 0°01' W., bet. secs. 35 and 36.</p> <p>Over rolling land.</p>
40.00	<p>Point for the 1/4 sec. cor. of secs. 35 and 36.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center;"> <p>T 35 N R 24 E</p> <p>1/4</p> <p>S 35 S 36</p> <p>2010</p> </div> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p>
76.75	Trail road, bears S. 85° E. and N. 85° W.
79.60	Trail road, bears N. 70° E. and S. 70° W.
80.00	<p>Point for the cor. of secs. 25, 26, 35 and 36.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center;"> <p>T 35 N R 24 E</p> <p>S 26 S 25</p> <hr style="width: 50%; margin: 0 auto;"/> <p>S 35 S 36</p> <p>2010</p> </div> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p> <p>Set a steel fence post nearby.</p> <p>Land, rolling. Soil, sand and sandy clay. No timber; undergrowth, scattered brush and native grasses.</p> <hr style="width: 80%; margin: 10px auto;"/> <p>From the cor. of secs. 25, 30, 31 and 36, on the E. bdy. of the Tp., monumented with a stainless steel post, 2 1/2 ins. diam., firmly set, projecting 5 ins. above ground, with brass cap mkd. T35N R24E R25E S25 S30 S36 S31 1999.</p> <p>Add the marks 2010 to the brass cap.</p>

**Survey of the Subdivisional Lines,
T. 35 N., R. 24 E., Gila and Salt River Meridian, Arizona**

CHAINS	
	West, bet. secs. 25 and 36. Over rolling land.
27.15	Power line, bears N. 10° E. and S. 10° W.
40.00	The point for the 1/4 sec. cor. of secs. 25 and 36. Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd. <div style="text-align: center;"> T 35 N R 24 E S 25 1/4 ——— S 36 2010 </div>
	Deposit a magnet, in a white plastic case, at the base of the stainless steel post.
52.45	Trail road, bears N. 50° E. and S. 50° W.
80.00	The cor. of secs. 25, 26, 35 and 36. Land, rolling. Soil, sand and sandy clay. No timber; undergrowth, scattered brush and native grasses.

	N. 0°01' W., bet. secs. 25 and 26. Over rolling land.
40.00	Point for the 1/4 sec. cor. of secs. 25 and 25. Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd. <div style="text-align: center;"> T 35 N R 24 E 1/4 S 26 S 25 2010 </div>
	Deposit a magnet, in a white plastic case, at the base of the stainless steel post. Set a steel fence post nearby.
	Cor. is located 41 lks. dist., S. of a trail road, bears N. 35° E. and S. 35° W.
80.00	Point for the cor. of secs. 23, 24, 25 and 26.

**Survey of the Subdivisional Lines,
T. 35 N., R. 24 E., Gila and Salt River Meridian, Arizona**

CHAINS	
	<p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T 35 N R 24 E S 23 S 24 S 26 S 25</p> <p style="text-align: center;">2010</p> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p> <p>Land, rolling. Soil, sand and sandy clay. No timber; undergrowth, scattered brush and native grasses.</p> <hr/> <p>From the cor. of secs. 19, 24, 25 and 30. on the E. bdy. of the Tp., monumented with a stainless steel post, 2 1/2 ins. diam., firmly set, projecting 2 ins. above ground, with brass cap mkd. T35N R24E R25E S24 S19 S25 S30 1999.</p> <p>Add the marks 2010 to the brass cap.</p> <p>West, bet. secs. 24 and 25.</p> <p>Over rolling land.</p>
40.00	<p>Point for the 1/4 sec. cor. of secs. 24 and 25.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T 35 N R 24 E S 24 1/4 ——— S 25</p> <p style="text-align: center;">2010</p> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p> <p>Cor. is located 68 lks. dist., S. of a trail road, bears N. 45° E. and S. 45° W.</p>
80.00	<p>The cor. of secs. 23, 24, 25 and 26.</p> <p>Land, rolling. Soil, sand and sandy clay. No timber; undergrowth, scattered brush and native grasses.</p> <hr/>

**Survey of the Subdivisional Lines,
T. 35 N., R. 24 E., Gila and Salt River Meridian, Arizona**

CHAINS	
	N. 0°01' W., bet. secs. 23 and 24. Over rolling land.
40.00	Point for the 1/4 sec. cor. of secs. 23 and 24. Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd. <div style="text-align: center;"> T 35 N R 24 E 1/4 S 23 S 24 2010 </div>
80.00	Point for the cor. of secs. 13, 14, 23 and 24. Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd. <div style="text-align: center;"> T 35 N R 24 E S 14 S 13 S 23 S 24 2010 </div>
	Deposit a magnet, in a white plastic case, at the base of the stainless steel post.
	Land, rolling. Soil, sand and sandy clay. No timber; undergrowth, scattered brush and native grasses.
	From the cor. of secs. 13, 18, 19 and 24, on the E. bdy. of the Tp., monumented with a stainless steel post, 2 1/2 ins. diam., firmly set, flush with ground, with brass cap mkd. T35N R24E R25E S13 S18 S19 S24 1999.
	Add the marks 2010 to the brass cap.
	West, bet. secs. 13 and 24. Over rolling land.
21.25	Power line, bears N. 10° E. and S. 10° W.
29.70	Graded road, 30 ft. wide, bears N. 30° E. and S. 30° W.
40.00	Point for the 1/4 sec. cor. of secs. 13 and 24.

Survey of the Subdivisional Lines,
T. 35 N., R. 24 E., Gila and Salt River Meridian, Arizona

CHAINS	
	<p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T 35 N R 24 E S 13 1/4 ——— S 24</p> <p style="text-align: center;">2010</p> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p>
80.00	<p>The cor. of secs. 13, 14, 23 and 24.</p> <p>Land, rolling. Soil, sand and sandy clay. No timber; undergrowth, scattered brush and native grasses.</p> <hr/> <p>N. 0°01' W., bet. secs. 13 and 14.</p> <p>Over rolling land.</p>
40.00	<p>Point for the 1/4 sec. cor. of secs. 13 and 14.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T 35 N R 24 E 1/4 S 14 S 13</p> <p style="text-align: center;">2010</p> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p>
68.80	Trail road, bears N. 70° E. and S. 70° W.
76.80	Trail road, bears N. 45° E. and S. 45° W.
80.00	<p>Point for the cor. of secs. 11, 12, 13 and 14.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T 35 N R 24 E S 11 S 12 S 14 S 13</p> <p style="text-align: center;">2010</p>

**Survey of the Subdivisional Lines,
T. 35 N., R. 24 E., Gila and Salt River Meridian, Arizona**

CHAINS	
	<p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p> <p>Land, rolling. Soil, sand and sandy clay. No timber; undergrowth, scattered brush and native grasses.</p> <hr/> <p>From the cor. of secs. 7, 12, 13 and 18, on the E. bdy. of the Tp., monumented with a stainless steel post, firmly set, projecting 2 ins. above ground, with brass cap mkd. T35N R24E R25E S12 S7 S13 S18 1999.</p> <p>Add the marks 2010 to the brass cap.</p> <p>West, bet. 12 and 13.</p> <p>Over rolling land.</p>
40.00	<p>Point for the 1/4 sec. cor. of secs. 12 and 13.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T 35 N R 24 E S 12 1/4 ——— S 13</p> <p style="text-align: center;">2010</p> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p>
60.90	Trail road, bears N. 60° E. and S. 60° W.
64.00	Power line, bears S. 55° E. and N. 55° W.
77.35	Trail road, bears N. 40° E. and S. 40° W.
80.00	<p>The cor. of secs. 11, 12, 13 and 14.</p> <p>Land, rolling. Soil, sand and sandy clay. No timber; undergrowth, scattered brush and native grasses.</p> <hr/> <p>N. 0°01' W., bet. secs. 11 and 12.</p> <p>Over rolling land.</p>
1.70	Power line, bears N. 35° E. and S. 35° W.
40.00	Point for the 1/4 sec. cor. of secs. 11 and 12.

**Survey of the Subdivisional Lines,
T. 35 N., R. 24 E., Gila and Salt River Meridian, Arizona**

CHAINS	
	<p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T 35 N R 24 E 1/4 S 11 S 12</p> <p style="text-align: center;">2010</p> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p>
80.00	<p>Point for the cor. of secs. 1, 2, 11 and 12.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T 35 N R 24 E S 2 S 1 S 11 S 12</p> <p style="text-align: center;">2010</p> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p> <p>Land, rolling. Soil, sand and sandy clay. No timber; undergrowth, scattered brush and native grasses.</p> <hr/> <p>From the cor. of secs. 1, 6, 7 and 12, on the E. bdy. of Tp., monumented with a stainless steel post, 2 1/2 ins. diam., firmly set, projecting 1 in. above ground, with brass cap mkd. T35N R24E R25E S1 S6 S12 S7 1999.</p> <p>Add the marks 2010 to the brass cap.</p> <p>West, bet. secs. 1 and 12.</p> <p>Over rolling land.</p>
40.00	<p>Point for the 1/4 sec. cor. of secs. 1 and 12.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T 35 N R 24 E S 1 1/4 ——— S 12</p> <p style="text-align: center;">2010</p>

Survey of the Subdivisional Lines,
T. 35 N., R. 24 E., Gila and Salt River Meridian, Arizona

CHAINS	
	Deposit a magnet, in a white plastic case, at the base of the stainless steel post.
80.00	The cor. of secs. 1, 2, 11 and 12. Land, rolling. Soil, sand and sandy clay. No timber; undergrowth, scattered brush and native grasses.
	<hr/>
	N. 0°01' W., bet. secs. 1 and 2. Over rolling land.
8.10	Trail road, bears N. 60° E. and S. 60° W.
40.00	Point for the 1/4 sec. cor. of secs. 1 and 2. Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.
	T 35 N R 24 E 1/4 S 2 S 1 2010
	Deposit a magnet, in a white plastic case, at the base of the stainless steel post. Set a stainless steel post nearby. Cor. is located 88 lks. dist., N. of a trail road, bears N. 60° E. and S. 60° W. From this same cor. point, a fence line, 5 strand barbed wire, bears N. 80° E. and S. 80° W., 58 lks. dist.
44.15	Power line, bears S. 85° E. and N. 85° W.
80.00	The cor. of secs. 1, 2, 35 and 36, on the N. bdy. of the Tp., hereinbefore described. Land, rolling. Soil, sand and sandy clay. No timber; undergrowth, scattered brush and native grasses.
	<hr/>
	From the cor. of secs. 2, 3, 34 and 35, on the S. bdy. of the Tp., hereinbefore described. N. 0°01' W., bet. secs. 34 and 35. Over rolling land.

**Survey of the Subdivisional Lines,
T. 35 N., R. 24 E., Gila and Salt River Meridian, Arizona**

CHAINS	
24.65	Power line, 4 strand, bears S. 50° E. and N. 50° W.
34.20	S. right-of-way fence of BIA Route 59, barbed wire, 5 strand, parallels highway.
36.10	BIA Route 59, asphalt surface, 50 ft. wide, bears S. 53° E. and N. 53° W.
38.00	N. right-of-way fence of BIA Route 59, barbed wire, 5 strand, parallels highway.
40.00	Point of the 1/4 sec. cor. of secs. 34 and 35. Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd. <div style="text-align: center;"> T 35 N R 24 E 1/4 S 34 S 35 2010 </div> Deposit a magnet, in a white plastic case, at the base of the stainless steel post.
80.00	Point for the cor. of secs. 26, 27, 34 and 35. Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd. <div style="text-align: center;"> T 35 N R 24 E S 27 S 26 S 34 S 35 2010 </div> Deposit a magnet, in a white plastic case, at the base of the stainless steel post. Land, rolling. Soil, sand and sandy clay. No timber; undergrowth, scattered brush and native grasses.
	<hr/> From the cor. of secs. 25, 26, 35 and 36. West, bet. secs. 26 and 35. Over rolling land.
21.15	Graded road, 20 ft. wide, bears N. 10° E. and S. 10° W.
40.00	Point for the 1/4 sec. cor. of secs. 26 and 35.

Survey of the Subdivisional Lines,
T. 35 N., R. 24 E., Gila and Salt River Meridian, Arizona

CHAINS	
	<p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T 35 N R 24 E S 26 1/4 ——— S 35</p> <p style="text-align: center;">2010</p> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p>
80.00	<p>The cor. of secs. 26, 27, 34 and 35.</p> <p>Land, rolling. Soil, sand and sandy clay. No timber; undergrowth, scattered brush and native grasses.</p> <hr/> <p>N. 0°01' W., bet. secs. 26 and 27.</p> <p>Over rolling land.</p>
14.65	<p>Graded road, 20 ft. wide, bears N. 45° E. and S. 45° W.</p>
40.00	<p>Point for the 1/4 sec. cor. of secs. 26 and 27.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T 35 N R 24 E 1/4 S 27 S 26</p> <p style="text-align: center;">2010</p> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p>
80.00	<p>Point for the cor. of secs. 22, 23, 26 and 27.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T 35 N R 24 E S 22 S 23 S 27 S 26</p> <p style="text-align: center;">2010</p> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p>

Survey of the Subdivisional Lines,
T. 35 N., R. 24 E., Gila and Salt River Meridian, Arizona

CHAINS	
	<p>Land, rolling. Soil, sand and sandy clay. No timber; undergrowth, scattered brush and native grasses.</p> <hr/> <p>From the cor. of secs. 23, 24, 25 and 26. West, bet. secs. 23 and 26. Over rolling land.</p>
11.85	Graded road, 20 ft. wide, bears N. 50° E. and S. 50° W.
40.00	<p>Point for the 1/4 sec. cor. of secs. 23 and 26.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T 35 N R 24 E S 23 1/4 ——— S 26</p> <p style="text-align: center;">2010</p> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p>
60.50	Graded road, 20 ft. wide, bears S. 40° E. and N. 40° W.
80.00	<p>The cor. of secs. 22, 23, 26 and 27.</p> <p>Land, rolling. Soil, sand and sandy clay. No timber; undergrowth, scattered brush.</p> <hr/> <p>N. 0°01' W., bet. secs. 22 and 23. Over rolling land.</p>
40.00	<p>Point for the 1/4 sec. cor. of secs. 22 and 23.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T 35 N R 24 E 1/4 S 22 S 23</p> <p style="text-align: center;">2010</p> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p>

**Survey of the Subdivisional Lines,
T. 35 N., R. 24 E., Gila and Salt River Meridian, Arizona**

CHAINS									
	Set a stainless steel post nearby.								
45.85	Graded road, 30 ft. wide, bears S. 20° E. and N. 20° W.								
57.00	Graded road, 30 ft. wide, bears N. 45° E. and S. 45° W.								
62.35	Power line, bears N. 40° E. and S. 40° W.								
80.00	Point for the cor. of secs. 14, 15, 22 and 23.								
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.								
	<table style="margin: auto; border-collapse: collapse;"> <tr> <td style="padding: 0 10px;">T 35 N</td> <td style="padding: 0 10px;">R 24 E</td> </tr> <tr> <td style="padding: 0 10px; border-right: 1px solid black;">S 15</td> <td style="padding: 0 10px;">S 14</td> </tr> <tr> <td style="padding: 0 10px; border-right: 1px solid black;">S 22</td> <td style="padding: 0 10px;">S 23</td> </tr> </table>	T 35 N	R 24 E	S 15	S 14	S 22	S 23		
T 35 N	R 24 E								
S 15	S 14								
S 22	S 23								
	2010								
	Deposit a magnet, in a white plastic case, at the base of the stainless steel post.								
	Land rolling. Soil, sand and sandy clay. No timber; undergrowth, scattered brush and native grasses.								
	From the cor. of secs. 13, 14, 23 and 24.								
	West, bet. secs. 14 and 23.								
	Over rolling land.								
40.00	Point for the 1/4 sec. cor. of secs. 14 and 23.								
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.								
	<table style="margin: auto; border-collapse: collapse;"> <tr> <td style="padding: 0 10px;">T 35 N</td> <td style="padding: 0 10px;">R 24 E</td> </tr> <tr> <td style="padding: 0 10px;"></td> <td style="padding: 0 10px;">S 14</td> </tr> <tr> <td style="padding: 0 10px;">1/4</td> <td style="padding: 0 10px; border-top: 1px solid black;">_____</td> </tr> <tr> <td style="padding: 0 10px;"></td> <td style="padding: 0 10px;">S 23</td> </tr> </table>	T 35 N	R 24 E		S 14	1/4	_____		S 23
T 35 N	R 24 E								
	S 14								
1/4	_____								
	S 23								
	2010								
	Deposit a magnet, in a white plastic case, at the base of the stainless steel post.								
62.25	Graded road, 30 ft. wide, bears N. 15° E. and S. 15° W.								
65.75	Power line, bears N. 35° E. and S. 35° W.								
80.00	The cor. of secs. 14, 15, 22 and 23.								

Survey of the Subdivisional Lines,
T. 35 N., R. 24 E., Gila and Salt River Meridian, Arizona

CHAINS	
	<p>Land, rolling. Soil, sand and sandy clay. No timber; undergrowth, scattered brush and native grasses.</p> <hr/> <p>N. 0°01' W., bet. secs. 14 and 15.</p> <p>Over rolling land.</p> <p>Ascend White Hills.</p>
40.00	<p>Point for the 1/4 sec. cor. of secs. 14 and 15.</p> <p>Set a brass tablet, 3 1/2 ins. diam., 2 1/2 ins. stem, cemented in place, in drill hole, in sandstone bedrock, with top mkd.</p> <p style="text-align: center;">T 35 N R 24 E 1/4 S 15 S 14</p> <p style="text-align: center;">2010</p> <p>Deposit a magnet, in a white plastic case, at the base of the brass tablet.</p>
80.00	<p>Point for the cor. of secs. 10, 11, 14 and 15.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T 35 N R 24 E S 10 S 11 S 15 S 14</p> <p style="text-align: center;">2010</p> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p> <p>Land, rolling. Soil, sand and sandy clay. No timber; undergrowth, scattered brush and native grasses.</p> <hr/> <p>From the cor. of secs. 11, 12, 13 and 14.</p> <p>West, bet. secs. 11 and 14.</p> <p>Over rolling land.</p>
20.50	<p>Navajo Route 181, graded road, 30 ft. wide, bears S. 45° E. and N. 45° W.</p>

Survey of the Subdivisional Lines,
T. 35 N., R. 24 E., Gila and Salt River Meridian, Arizona

CHAINS	
40.00	<p>Point for the 1/4 sec. cor. of secs. 11 and 14.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T 35 N R 24 E S 11 1/4 ——— S 14</p> <p style="text-align: center;">2010</p> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p>
80.00	<p>The cor. of secs. 10, 11, 14 and 15.</p> <p>Land, rolling. Soil, sand and sandy clay. No timber; undergrowth, scattered brush and native grasses.</p> <hr/> <p>N. 0°01' W., bet. secs. 10 and 11.</p> <p>Over rolling land.</p> <p>Descend White Hills.</p>
40.00	<p>Point for the 1/4 sec. cor. of secs. 10 and 11.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T 35 N R 24 E 1/4 S 10 S 11</p> <p style="text-align: center;">2010</p> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p>
58.80	<p>Navajo Route 181, a graded road, 30 ft. wide, bears S. 45° E. and N. 45° W.</p>
80.00	<p>Point for the cor. of secs. 2, 3, 10 and 11.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p>

Survey of the Subdivisional Lines,
T. 35 N., R. 24 E., Gila and Salt River Meridian, Arizona

CHAINS							
	T 35 N R 24 E <table border="1" style="margin: auto;"> <tr> <td style="padding: 2px;">S 3</td> <td style="padding: 2px;">S 2</td> </tr> <tr> <td style="padding: 2px;">S 10</td> <td style="padding: 2px;">S 11</td> </tr> </table> 2010 Deposit a magnet, in a white plastic case, at the base of the stainless steel post. Land, rolling. Soil, sand and sandy clay. No timber; undergrowth, scattered brush and native grasses.	S 3	S 2	S 10	S 11		
S 3	S 2						
S 10	S 11						
	<hr/> From the cor. of secs. 1, 2, 11 and 12. West, bet. secs. 2 and 11. Over rolling land.						
24.20	Trail road, bears N. 80° E. and S. 80° W.						
40.00	Point for the 1/4 sec. cor. of secs. 2 and 11. Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.						
	T 35 N R 24 E <table style="margin: auto;"> <tr> <td style="padding: 2px;">S 2</td> <td style="padding: 2px;">1/4</td> <td style="padding: 2px;">—</td> </tr> <tr> <td style="padding: 2px;">S 11</td> <td></td> <td></td> </tr> </table> 2010 Deposit a magnet, in a white plastic case, at the base of the stainless steel post.	S 2	1/4	—	S 11		
S 2	1/4	—					
S 11							
43.20	Power line, bears N. and S.						
80.00	The cor. of secs. 2, 3, 10 and 11. Land, rolling. Soil, sand and sandy clay. No timber; undergrowth, scattered brush and native grasses.						
	<hr/> N. 0°01' W., bet. secs. 2 and 3. Over rolling land.						
23.15	Power line, bears E. and W.						
24.65	Trail road, bears N. 80° E. and S. 80° W.						

Survey of the Subdivisional Lines,
T. 35 N., R. 24 E., Gila and Salt River Meridian, Arizona

CHAINS	
28.95	Barbed wire fence, 5 strand, bears S. 25° E. and N. 25° W.
40.00	Point for the 1/4 sec. cor. of secs. 2 and 3. Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd. <div style="text-align: center;">T 35 N R 24 E 1/4 S 3 S 2 2010</div>
80.00	Deposit a magnet, in a white plastic case, at the base of the stainless steel post. The cor. of secs. 2, 3, 34 and 35, on the N. bdy. of the Tp., hereinbefore described. Land, rolling. Soil, sand and sandy clay. No timber; undergrowth, scattered brush and native grasses. <hr/> From the cor. of secs. 3, 4, 33 and 34, on the S. bdy. of the Tp., hereinbefore described. N. 0°02' W., bet. secs. 33 and 34. Over rolling land.
34.65	Graded road, 30 ft. wide, bears N. 60° E. and S. 60° W.
40.00	Point for the 1/4 sec. cor. of secs. 33 and 34. Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd. <div style="text-align: center;">T 35 N R 24 E 1/4 S 33 S 34 2010</div>
53.00	Deposit a magnet, in a white plastic case, at the base of the stainless steel post.
53.00	Trail road, bears S. 75° E. and N. 75° W.
53.85	Trail road, bears N. 55° E. and S. 55° W.
64.35	Wash, 10 ft. wide, 3 ft. deep, drains S. 50° E.
80.00	Point for the cor. of secs. 27, 28, 33 and 34.

**Survey of the Subdivisional Lines,
T. 35 N., R. 24 E., Gila and Salt River Meridian, Arizona**

CHAINS	
	<p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T 35 N R 24 E S 28 S 27 S 33 S 34</p> <p style="text-align: center;">2010</p> <p>Cor. is located 61 lks. dist., S. of power line, 4 strand, bears S. 80° E. and N. 80° W.</p> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p> <p>Land, rolling. Soil, sand and sandy clay. No timber; undergrowth, scattered brush and native grasses.</p> <hr/> <p>From the cor. of secs. 26, 27, 34 and 35.</p> <p>West, bet. secs. 27 and 34.</p> <p>Over rolling land.</p>
40.00	<p>Point for the 1/4 sec. cor. of secs. 27 and 34.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T 35 N R 24 E S 27 1/4 ——— S 34</p> <p style="text-align: center;">2010</p> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p>
63.35	E. right-of-way fence of BIA Route 59, 5 strand barbed wire, parallels highway.
67.20	BIA Route 59, asphalt surface, 40 ft. wide, bears S. 65° E., and N. 65° W.
71.10	W. right-of-way fence of BIA Route 59, 5 strand barbed wire, parallels highway.
77.15	Power line, bears S. 80° E. and N. 80° W.
80.00	The cor. of secs. 27, 28, 33 and 34.

Survey of the Subdivisional Lines,
T. 35 N., R. 24 E., Gila and Salt River Meridian, Arizona

CHAINS	
	<p>Land, rolling. Soil, sand and sandy clay. No timber; undergrowth, scattered brush and native grass.</p> <hr/> <p>N. 0°02' W., bet. secs. 27 and 28.</p> <p>Over rolling land.</p>
3.80	S. right-of-way fence of BIA Route 59, 5 strand barbed wire, parallels highway.
5.40	BIA Route 59, asphalt surface, 40 ft. wide, bears S. 65° E. and N. 65° W.
7.10	N. right-of-way fence line of BIA Route 59, 5 strand barbed wire, parallels highway.
40.00	<p>Point for the 1/4 sec. cor. of secs. 27 and 28.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center;"> <p>T 35 N R 24 E 1/4 S 28 S 27</p> <p>2010</p> </div> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p>
50.60	Power line, bears N. 50° E. and S. 50° W.
54.00	Trail road, bears N. 20° E. and S. 20° W.
80.00	<p>Point for the cor. of secs. 21, 22, 27 and 28.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center;"> <p>T 35 N R 24 E S 21 S 22 S 28 S 27</p> <p>2010</p> </div> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p>

Survey of the Subdivisional Lines,
T. 35 N., R. 24 E., Gila and Salt River Meridian, Arizona

CHAINS	
	<p>Land, rolling. Soil, sand and sandy clay. No timber; undergrowth, scattered brush and native grasses.</p> <hr/> <p>From the cor. of secs. 22, 23, 26, and 27.</p> <p>West, bet. secs. 22 and 27.</p> <p>Over rolling land.</p>
40.00	<p>Point for the 1/4 sec. cor. of secs. 22 and 27.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T 35 N R 24 E S 22 1/4 ——— S 27</p> <p style="text-align: center;">2010</p> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p>
44.90	Power line, bears N. 50° E. and S. 50° W.
74.70	Trail road, bears N. 5° E. and S. 5° W.
80.00	The cor. of secs. 21, 22, 27 and 28.
	<p>Land, rolling. Soil, sand and sandy clay. No timber; undergrowth, scattered brush and native grasses.</p> <hr/> <p>N. 0°02' W., bet. secs. 21 and 22.</p> <p>Over rolling land.</p> <p>Ascend White Hills.</p>
40.00	<p>Point for the 1/4 sec. cor. of secs. 21 and 22.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T 35 N R 24 E 1/4 S 21 S 22</p> <p style="text-align: center;">2010</p>

**Survey of the Subdivisional Lines,
T. 35 N., R. 24 E., Gila and Salt River Meridian, Arizona**

CHAINS	<p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p>								
80.00	<p>Point for the cor. of secs. 15, 16, 21 and 22.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center;"> <table style="margin: auto;"> <tr> <td>T 35 N</td> <td>R 24 E</td> </tr> <tr> <td style="border-right: 1px solid black;">S 16</td> <td>S 15</td> </tr> <tr> <td style="border-right: 1px solid black;">S 21</td> <td>S 22</td> </tr> </table> <p>2010</p> </div> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p> <p>Cor. is located 47 lks. E. of a trail road, bears N. 70° E. and S. 70° W., 16 lks. S. of a trail road, bears S. 60° E. and N. 60° W. and 31 lks. W. of the same trail road, bears S. 60° E. and N. 60° W.</p> <p>Land, rolling. Soil, sand and sandy clay. No timber; undergrowth, scattered brush and native grasses.</p> <hr/> <p>From the cor. of secs. 14, 15, 22 and 23.</p> <p>West, bet. secs. 15 and 22.</p> <p>Over rolling land.</p>	T 35 N	R 24 E	S 16	S 15	S 21	S 22		
T 35 N	R 24 E								
S 16	S 15								
S 21	S 22								
40.00	<p>Point for the 1/4 sec. cor. of secs. 15 and 22.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 21 ins. in the ground, in a mound of stone, 4 ft. base, to top, with brass cap mkd.</p> <div style="text-align: center;"> <table style="margin: auto;"> <tr> <td>T 35 N</td> <td>R 24 E</td> </tr> <tr> <td></td> <td>S 15</td> </tr> <tr> <td>1/4</td> <td style="border-top: 1px solid black;">———</td> </tr> <tr> <td></td> <td>S 22</td> </tr> </table> <p>2010</p> </div> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p> <p>Ascend White Hills.</p>	T 35 N	R 24 E		S 15	1/4	———		S 22
T 35 N	R 24 E								
	S 15								
1/4	———								
	S 22								
80.00	<p>The cor. of secs. 15, 16, 21 and 22.</p>								

Survey of the Subdivisional Lines,
T. 35 N., R. 24 E., Gila and Salt River Meridian, Arizona

CHAINS	
	<p>Land, rolling. Soil, sand and sandy clay. No timber; undergrowth, scattered brush and native grasses.</p> <hr/> <p>N. 0°02' W., bet. secs. 15 and 16.</p> <p>Over rolling land</p>
12.60	Trail road, bears S. 85° E. and N. 85° W.
38.55	Trail road, bears N. 60° E. and S. 60° W.
40.00	<p>Point for the 1/4 sec. cor. of secs. 15 and 16.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T 35 N R 24 E 1/4 S 16 S 15</p> <p style="text-align: center;">2010</p> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p>
48.00	Trail road, bears N. 55° E. and S. 55° W.
80.00	<p>Point for the cor. of secs. 9, 10, 15 and 16.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T 35 N R 24 E S 9 S 10 S 16 S 15</p> <p style="text-align: center;">2010</p> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p> <p>Set a steel fence post nearby.</p> <p>Land, rolling. Soil, sand and sandy clay. No timber; undergrowth, scattered brush and native grasses.</p> <hr/> <p>From the cor. of secs. 10, 11, 14 and 15.</p> <p>West, bet. secs. 10 and 15.</p>

Survey of the Subdivisional Lines,
T. 35 N., R. 24 E., Gila and Salt River Meridian, Arizona

CHAINS	
	Over rolling land.
33.20	Trail road, bears N. 45° E. and S. 45° W.
38.30	Trail road, bears S. 45° E. and N. 45° W.
40.00	Point for the 1/4 sec. cor. of secs. 10 and 15. Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd. <div style="text-align: center;"> T 35 N R 24 E S 10 1/4 ——— S 15 2010 </div>
	Deposit a magnet, in a white plastic case, at the base of the stainless steel post. Set a steel fence post nearby.
40.55	Wash, 10 ft. wide, 20 ft. deep, drains N. 25° W.
80.00	The cor. of secs. 9, 10, 15 and 16. Land, rolling. Soil, sand and sandy clay. No timber; undergrowth, scattered brush and native grasses.
	<hr/> N. 0°02' W., bet. secs. 9 and 10. Over rolling land.
31.90	Trail road, bears S. 60° E. and N. 60° W.
40.00	Point for the 1/4 sec. cor. of secs. 9 and 10. Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd. <div style="text-align: center;"> T 35 N R 24 E 1/4 S 9 S 10 2010 </div>
	Deposit a magnet, in a white plastic case, at the base of the stainless steel post.
41.80	Trail road, bears N. 40° E. and S. 40° W.

Survey of the Subdivisional Lines,
T. 35 N., R. 24 E., Gila and Salt River Meridian, Arizona

CHAINS 80.00	<p>Point for the cor. of secs. 3, 4, 9 and 10.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center;"> <table style="margin: auto;"> <tr> <td>T 35 N</td> <td>R 24 E</td> </tr> <tr> <td style="border-right: 1px solid black;">S 4</td> <td>S 3</td> </tr> <tr> <td style="border-right: 1px solid black;">S 9</td> <td>S 10</td> </tr> </table> <p>2010</p> </div> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p> <p>Land, rolling. Soil, sand and sandy clay. No timber; undergrowth, scattered brush and native grasses.</p> <hr/> <p>From the cor. of secs. 2, 3, 10 and 11.</p> <p>West, bet. secs. 3 and 10.</p> <p>Over rolling land.</p>	T 35 N	R 24 E	S 4	S 3	S 9	S 10		
T 35 N	R 24 E								
S 4	S 3								
S 9	S 10								
40.00	<p>Point for the 1/4 sec. cor. of secs. 3 and 10.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center;"> <table style="margin: auto;"> <tr> <td>T 35 N</td> <td>R 24 E</td> </tr> <tr> <td></td> <td>S 3</td> </tr> <tr> <td>1/4</td> <td>—</td> </tr> <tr> <td></td> <td>S 10</td> </tr> </table> <p>2010</p> </div> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p>	T 35 N	R 24 E		S 3	1/4	—		S 10
T 35 N	R 24 E								
	S 3								
1/4	—								
	S 10								
80.00	<p>The cor. of secs. 3, 4, 9 and 10.</p> <p>Land, rolling. Soil, sand and sandy clay. No timber; undergrowth, scattered brush and native grasses.</p> <hr/> <p>N. 0°02' W., bet. secs. 3 and 4.</p> <p>Over rolling land.</p>								
18.60	<p>Power line, bears N. 85° E. and S. 85° W.</p>								

**Survey of the Subdivisional Lines,
T. 35 N., R. 24 E., Gila and Salt River Meridian, Arizona**

CHAINS	
26.90	Graded road, 30 ft. wide, bears S. 85° E. and N. 85° W.
32.20	NE cor. of a brick house, 50 ft. X 30 ft., bears West, 2.52 chs. dist., long side bears N. 17° E.
40.00	Point for the 1/4 sec. cor. of secs. 3 and 4. Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd. <div style="text-align: center;"> T 35 N R 24 E 1/4 S 4 S 3 2010 </div> Deposit a magnet, in a white plastic case, at the base of the stainless steel post. Set a steel fence post nearby.
67.30	Trail road, bears N. 30° E. and S. 30° W.
80.00	The cor. of secs. 3, 4, 33 and 34, on the N. bdy. of Tp., hereinbefore described. Land, rolling. Soil, sand and sandy clay. No timber; undergrowth, scattered brush and native grasses.
	<hr/> From the cor. of secs. 4, 5, 32 and 33, on the S. bdy. of the Tp., hereinbefore described. N. 0°03' W., bet. secs. 32 and 33. Over rolling land.
0.55	Trail road, bears N. 85° E. and S. 85° W.
1.95	Power line, bears S. 70° E. and N. 70° W.
13.25	Trail road, bears S. 45° E. and N. 45° W.
25.40	Trail road, bears S. 75° E. and N. 75° W.
40.00	Point for the 1/4 sec. cor. of secs. 32 and 33. Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.

Survey of the Subdivisional Lines,
T. 35 N., R. 24 E., Gila and Salt River Meridian, Arizona

CHAINS	
	T 35 N R 24 E 1/4 S 32 S 33 2010
	Deposit a magnet, in a white plastic case, at the base of the stainless steel post.
80.00	Point for the cor. of secs. 28, 29, 32 and 33. Set a magnet in a white plastic case, 24 ins. below the surface of the ground. from which A stainless steel post, 28 ins. long, 2 1/2 ins. diam., set 24 ins. in the ground for a reference monument, bears S. 45°00' E., 198.0 ft. dist. with brass cap mkd. RM T35N R24E 198.0 FT TO COR S 33 2010 and an arrow pointing to the cor. Deposit a magnet, in a white plastic case, at the base of the stainless steel post. A stainless steel post, 28 ins. long, 2 1/2 ins. diam., set 24 ins. in the ground for a reference monument, bears N. 45°00' W., 122.0 ft. dist. with brass cap mkd. RM T35N R24E 122.0 FT TO COR S29 2010 and an arrow pointing to the cor. Deposit a magnet, in a white plastic case, at the base of the stainless steel post. Cor. is located in a wash, 30 ft. wide, 10 ft. deep, drains N. 55° E. Land, rolling. Soil, sand and sandy clay. No timber; undergrowth, scattered brush and native grasses.
	From the cor. of secs. 27, 28, 33 and 34.
	West, bet. secs. 28 and 33.
	Over rolling land.
34.15	Power line, 2 strand, bears N. 15° E. and S. 15° W.
40.00	Point for the 1/4 sec. cor. of secs. 28 and 33. Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.

Survey of the Subdivisional Lines,
T. 35 N., R. 24 E., Gila and Salt River Meridian, Arizona

CHAINS	T 35 N R 24 E S 28 1/4 ——— S 33 2010
	Deposit a magnet, in a white plastic case, at the base of the stainless steel post.
51.95	Wash, 30 ft. wide, 10 ft. deep, drains S. 45° E.
71.54	Northwesterly cor. of a eight sided Hogan, with a 10 x 14 ft. extension on easterly side, bears South, 1.87 chs. dist.
80.00	The cor. of secs. 28, 29, 32 and 33. Land, rolling. Soil, sand and sandy clay. No timber; undergrowth, scattered brush and native grasses.
	N. 0°03' W., bet. secs. 28 and 29. Over rolling land.
17.55	Power line, bears S. 75° E. and N. 75° W.
26.25	S. right-of-way fence of BIA Route 59, 5 strand barbed wire, parallels highway.
27.75	BIA Route 59, asphalt surface, 40 ft. wide, S. 85° E., and N. 85° W.
29.25	N. right-of-way fence of BIA Route 59, 5 strand barbed wire, parallels highway.
40.00	Point for the 1/4 sec. cor. of secs. 28 and 29. Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.
	T 35 N R 24 E 1/4 S 29 S 28 2010
	Deposit a magnet, in a white plastic case, at the base of the stainless steel post.
80.00	Point for the cor. of secs. 20, 21, 28 and 29. Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.

Survey of the Subdivisional Lines,
T. 35 N., R. 24 E., Gila and Salt River Meridian, Arizona

CHAINS									
	<table style="margin: auto; border-collapse: collapse;"> <tr> <td style="padding: 0 10px;">T 35 N</td> <td style="padding: 0 10px;">R 24 E</td> </tr> <tr> <td style="border-right: 1px solid black; padding: 0 5px;">S 20</td> <td style="padding: 0 5px;">S 21</td> </tr> <tr> <td style="border-right: 1px solid black; padding: 0 5px;">S 29</td> <td style="padding: 0 5px;">S 28</td> </tr> </table>	T 35 N	R 24 E	S 20	S 21	S 29	S 28		
T 35 N	R 24 E								
S 20	S 21								
S 29	S 28								
	2010								
	<p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p> <p>Land, rolling. Soil, sand and sandy clay. No timber; undergrowth, scattered brush and native grasses.</p> <hr/> <p>From the cor. of secs. 21, 22, 27 and 28.</p> <p>West, bet. secs. 21 and 28.</p> <p>Over rolling land.</p>								
40.00	<p>Point for the 1/4 sec. cor. of secs. 21 and 28.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p>								
	<table style="margin: auto; border-collapse: collapse;"> <tr> <td style="padding: 0 10px;">T 35 N</td> <td style="padding: 0 10px;">R 24 E</td> </tr> <tr> <td></td> <td style="padding: 0 5px;">S 21</td> </tr> <tr> <td style="padding: 0 5px;">1/4</td> <td style="border-bottom: 1px solid black; padding: 0 5px;"></td> </tr> <tr> <td></td> <td style="padding: 0 5px;">S 28</td> </tr> </table>	T 35 N	R 24 E		S 21	1/4			S 28
T 35 N	R 24 E								
	S 21								
1/4									
	S 28								
	2010								
80.00	<p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p> <p>The cor. of secs. 20, 21 28 and 29.</p> <p>Land, rolling. Soil, sand and sandy clay. No timber; undergrowth, scattered brush and native grasses.</p> <hr/> <p>N. 0°03' W., bet. secs. 20 and 21.</p> <p>Over, rolling land.</p>								
40.00	<p>Point for the 1/4 sec. cor. of secs. 20 and 21.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p>								

Survey of the Subdivisional Lines,
T. 35 N., R. 24 E., Gila and Salt River Meridian, Arizona

CHAINS	
	T 35 N R 24 E 1/4 S 20 S 21 2010
	Deposit a magnet, in a white plastic case, at the base of the stainless steel post.
	Cor. is located N. of a trail road, 73 lks. dist., bears N. 35° E. and S. 35° W.
	Set a steel fence post nearby.
58.80	Trail road, bears N. 55° E. and S. 55° W.
80.00	Point for the cor. of secs. 16, 17, 20 and 21.
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.
	T 35 N R 24 E S 17 S 16 S 20 S 21 2010
	Deposit a magnet, in a white plastic case, at the base of the stainless steel post.
	Land, rolling. Soil, sand and sandy clay. No timber; undergrowth, scattered brush and native grasses.
	<hr/> From the cor. of secs. 15, 16, 21 and 22.
	West, bet. secs. 16 and 21.
	Over rolling land.
40.00	Point for the 1/4 sec. cor. of secs. 16 and 21.
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 21 ins. in the ground, in a mound of stone, 4 ft. base, to top, with brass cap mkd.
	T 35 N R 24 E S 16 1/4 ——— S 21 2010

**Survey of the Subdivisional Lines,
T. 35 N., R. 24 E., Gila and Salt River Meridian, Arizona**

CHAINS	
	<p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p> <p>Cor. is located on the E. edge of a drainage, 2 ft. wide, 3 ft. deep, drains S.</p>
45.20	Trail road, bears S. 75° E. and N. 75° W.
52.75	Trail road, bears N. 55° E. and S. 55° W.
80.00	<p>The cor. of secs. 16, 17, 20 and 21.</p> <p>Land, rolling. Soil, sand and sandy clay. No timber; undergrowth, scattered brush and native grasses.</p> <hr/> <p>N. 0°03' W., bet. secs. 16 and 17.</p> <p>Over rolling land.</p>
40.00	<p>Point for the 1/4 sec. cor. of secs. 16 and 17.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T 35 N R 24 E 1/4 S 17 S 16</p> <p style="text-align: center;">2010</p> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p> <p>Set a steel fence post nearby.</p> <p>Cor. is located N. of a trail road, 47 lks. dist., bears N. 40° E. and S. 40° W.</p>
42.10	Trail road, bears N. 70° E. and S. 70° W.
54.65	Trail road, bears N. 60° E. and S. 60° W.
54.70	Power line, bears N. 20° E. and S. 20° W.
56.45	Intersect the S. side of a brick house, 40 X 30 ft., long side bears S. 9° E. and N. 9° W.
68.50	Trail road, bears S. 35° E. and N. 35° W.
75.25	Trail road, bears N. 65° E. and S. 65° W.
80.00	Point for the cor. of secs. 8, 9, 16 and 17.

Survey of the Subdivisional Lines,
T. 35 N., R. 24 E., Gila and Salt River Meridian, Arizona

CHAINS	
	<p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T 35 N R 24 E S 8 S 9 ----- S 17 S 16</p> <p style="text-align: center;">2010</p> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p> <p>Land, rolling. Soil, sand and sandy clay. No timber; undergrowth, scattered brush and native grasses.</p> <hr/> <p>From the cor. of secs. 9, 10, 15 and 16.</p> <p>West, bet. secs. 9 and 16.</p> <p>Over rolling land.</p>
40.00	<p>Point for the 1/4 sec. cor. of secs. 9 and 16.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T 35 N R 24 E S 9 1/4 ----- S 16</p> <p style="text-align: center;">2010</p> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p> <p>Cor. is located E. of a trail road, 68 lks. dist., bears S. 30° E. and N. 30° W.</p>
68.45	<p>Power line, bears N. 25° E. and S. 25° W.</p>
70.85	<p>Trail road, bears N. 60° E. and S. 60° W.</p>
80.00	<p>The cor. of secs. 8, 9, 16 and 17.</p> <p>Land, rolling. Soil, sand and sandy clay. No timber; undergrowth, scattered brush and native grasses.</p> <hr/> <p>N. 0°03' W., bet. secs. 8 and 9.</p>

Survey of the Subdivisional Lines,
T. 35 N., R. 24 E., Gila and Salt River Meridian, Arizona

CHAINS	
	Over rolling land.
40.00	Point for the 1/4 sec. cor. of secs. 8 and 9. Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd. <div style="text-align: center;"> T 35 N R 24 E 1/4 S 8 S 9 2010 </div> Deposit a magnet, in a white plastic case, at the base of the stainless steel post. Set a steel fence post nearby.
41.45	Graded road, 30 ft. wide, bears N. 50° E. and S. 50° W.
80.00	Point for the cor. of secs. 4, 5, 8 and 9. Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd. <div style="text-align: center;"> T 35 N R 24 E S 5 S 4 S 8 S 9 2010 </div> Deposit a magnet, in a white plastic case, at the base of the stainless steel post. Land, rolling. Soil, sand and sandy clay. No timber; undergrowth, scattered brush and native grasses. <hr/> From the cor. of secs. 3, 4, 9 and 10. West, bet. secs. 4 and 9. Over rolling land.
31.45	Power line, single phase, bears N. 25° E. and S. 25° W.
40.00	Point for the 1/4 sec. cor. of secs. 4 and 9. Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.

Survey of the Subdivisional Lines,
T. 35 N., R. 24 E., Gila and Salt River Meridian, Arizona

CHAINS	
	T 35 N R 24 E S 4 1/4 ——— S 9 2010
	Deposit a magnet, in a white plastic case, at the base of the stainless steel post. Set a steel fence post nearby.
42.35	Graded road, 30 ft. wide, bears N. 35° E. and S. 35° W.
80.00	The cor. of secs. 4, 5, 8 and 9. Land, rolling. Soil, sand and sandy clay. No timber; undergrowth, scattered brush and native grasses.
	N. 0°03' W., bet. secs. 4 and 5. Over rolling land.
40.00	Point for the 1/4 sec. cor. of secs. 4 and 5. Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.
	T 35 N R 24 E 1/4 S 5 S 4 2010
	Deposit a magnet, in a white plastic case, at the base of the stainless steel post.
59.05	Trail road, bears S. 55° E. and N. 55° W.
60.55	Power line, bears S. 55° E. and N. 55° W.
61.80	From this point, the pump shaft of a windmill marked 10R-119, bears West, 7.10 chs. dist.
80.00	The cor. of secs. 4, 5, 32 and 33, on the N. bdy. of the Tp., hereinbefore described. Land, rolling. Soil, sand and sandy clay. No timber; undergrowth, scattered brush and native grasses.

**Survey of the Subdivisional Lines,
T. 35 N., R. 24 E., Gila and Salt River Meridian, Arizona**

CHAINS	
	From the cor. of secs. 5, 6, 31 and 32, on the S. bdy. of the Tp., hereinbefore described.
	N. 0°03' W., bet. secs. 31 and 32.
	Over rolling land.
3.00	Power line, bears N. 75° E. and S. 75° W.
40.00	Point for the 1/4 sec. cor. of secs. 31 and 32.
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.
	T 35 N R 24 E 1/4 S 31 S 32 2010
	Deposit a magnet, in a white plastic case, at the base of the stainless steel post.
55.35	Navajo Route 8090, graded road, 30 ft. wide, bears S. 35° E. and N. 35° W.
80.00	Point for the cor. of secs. 29, 30, 31 and 32.
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.
	T 35 N R 24 E S 30 S 29 S 31 S 32 2010
	Deposit a magnet, in a white plastic case, at the base of the stainless steel post.
	Land, rolling.
	Soil, sand and sandy clay.
	No timber; undergrowth, scattered brush and native grasses.
	<hr/>
	From the cor. of secs. 28, 29, 32 and 33.
	West, bet. secs. 29 and 32.
	Over rolling land.
40.00	Point for the 1/4 sec. cor. of secs. 29 and 32.

Survey of the Subdivisional Lines,
T. 35 N., R. 24 E., Gila and Salt River Meridian, Arizona

CHAINS	
	<p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T 35 N R 24 E S 29 1/4 ——— S 32</p> <p style="text-align: center;">2010</p> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p>
80.00	<p>The cor. of secs. 29, 30, 31 and 32.</p> <p>Land, rolling. Soil, sand and sandy clay. No timber; undergrowth, scattered brush and native grasses.</p> <hr/> <p>West, bet. secs. 30 and 31.</p> <p>Over rolling land.</p>
8.30	<p>Navajo Route 8090, graded road, 30 ft. wide, bears N. and S.</p>
40.00	<p>Point for the 1/4 sec. cor. of secs. 30 and 31.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T 35 N R 24 E S 30 1/4 ——— S 31</p> <p style="text-align: center;">2010</p> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p>
55.20	<p>Wash, 20 ft. wide, 5 ft. deep, drains N. 65° W.</p>
78.84	<p>The cor. of secs. 25, 30, 31 and 36, on the W. bdy. of the TP., monumented with a stainless steel, 2 1/2 ins. diam., firmly set, projecting 3 ins. above ground, with brass cap mkd. T35N R23E R24E S25 S30 S36 S31 1998. Add the marks 2010 to the brass cap.</p> <p>Land, rolling. Soil, sand and sandy clay. Timber; piñon and juniper; undergrowth, scattered brush and native grasses.</p> <hr/>

**Survey of the Subdivisional Lines,
T. 35 N., R. 24 E., Gila and Salt River Meridian, Arizona**

CHAINS	
	From the cor. of secs. 29, 30, 31 and 32.
	N. 0°03' W., bet. secs. 29 and 30.
	Over rolling and broken land.
16.25	Navajo Route 8090, a graded road, 30 ft. wide, bears N. 35° E. and S. 35° W.
17.99	Pump shaft of a windmill, bears West, 63.13 ft. dist.
20.60	Wash, 35 ft. wide, 5 ft. deep, drains S. 80° E.
29.50	Power line, bears E. and W.
29.75	Trail road, bears N. 85° E. and S. 85° W.
31.45	S. right-of-way fence of BIA Route 59, 5 strand barbed wire, parallels highway.
33.00	BIA Route 59, asphalt surface, 40 ft. wide, S. 85° E., and N. 85° W.
34.50	N. right-of-way fence of BIA Route 59, 5 strand barbed wire, parallels highway.
34.95	Underground water line, bears S. 85° E. and N. 85° W.
40.00	Point for the 1/4 sec. cor. of secs. 29 and 30.
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.
	T 35 N R 24 E 1/4 S 30 S 29 2010
	Deposit a magnet, in a white plastic case, at the base of the stainless steel post.
	Set a steel fence post nearby.
80.00	Point for the cor. of secs. 19, 20, 29 and 30.
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.

**Survey of the Subdivisional Lines,
T. 35 N., R. 24 E., Gila and Salt River Meridian, Arizona**

CHAINS	
	T 35 N R 24 E S 19 S 20 S 30 S 29 2010
	Deposit a magnet, in a white plastic case, at the base of the stainless steel post. Land, rolling and broken. Soil, sand and sandy clay. No timber; undergrowth, scattered brush and native grasses.
	<hr/> From the cor. of secs. 20, 21, 28 and 29. West, bet. secs. 20 and 29. Over rolling land.
40.00	Point for the 1/4 sec. cor. of secs. 20 and 29. Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.
	T 35 N R 24 E S 20 1/4 ——— S 29 2010
	Deposit a magnet, in a white plastic case, at the base of the stainless steel post.
58.40	Navajo Route 8090, a graded road, 30 ft. wide, bears N. 20° E. and S. 20° W.
80.00	The cor. of secs. 19, 20, 29 and 30. Land, rolling. Soil, sand and sandy clay. No timber; undergrowth, scattered brush and native grasses.
	<hr/> West, bet. secs. 19 and 30. Over rolling land.
40.00	Point of the 1/4 sec. cor. of secs. 19 and 30. Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.

Survey of the Subdivisional Lines,
T. 35 N., R. 24 E., Gila and Salt River Meridian, Arizona

CHAINS	
	<p style="text-align: center;">T 35 N R 24 E S 19 1/4 ——— S 30</p> <p style="text-align: center;">2010</p> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p>
78.75	<p>The cor. of secs. 19, 24, 25 and 30, on the W. bdy. of the Tp., monumented with a stainless steel post, 2 1/2 ins. diam., firmly set, projecting 2 ins. above ground, with brass cap mkd., T35N R23E R24E S24 S19 S25 S30 1998. Add the marks 2010 to the brass cap.</p> <p>Land, rolling. Soil, sand and sandy clay. No timber; undergrowth, scattered brush and native grasses.</p>
	<hr/> <p>From the cor. of secs. 19, 20, 29 and 30.</p> <p>N. 0°03' W., bet. secs. 19 and 20.</p>
40.00	<p>The point for the 1/4 sec. cor. of secs. 19 and 20.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p>
	<p style="text-align: center;">T 35 N R 24 E 1/4 S 19 S 20</p> <p style="text-align: center;">2010</p>
	<p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p>
80.00	<p>Point for the cor. of secs. 17, 18, 19 and 20.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p>
	<p style="text-align: center;">T 35 N R 24 E S 18 S 17 S 19 S 20</p> <p style="text-align: center;">2010</p> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p>

Survey of the Subdivisional Lines,
T. 35 N., R. 24 E., Gila and Salt River Meridian, Arizona

CHAINS	
	<p>Land, rolling. Soil, sand and sandy clay. No timber; undergrowth, scattered brush and native grasses.</p> <hr/> <p>From the cor. of secs. 16, 17, 20 and 21.</p> <p>West, bet. secs. 17 and 20.</p> <p>Over rolling land.</p>
36.90	Navajo Route 8090, a graded road, 30 ft. wide, bears N. 15° E. and S. 15° W.
40.00	<p>Point for the 1/4 sec. cor. of secs. 17 and 20.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T 35 N R 24 E S 17 1/4 ——— S 20</p> <p style="text-align: center;">2010</p> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p> <p>Set a steel fence post nearby.</p>
80.00	<p>The cor. of secs. 17, 18, 19 and 20.</p> <p>Land, rolling. Soil, sand and sandy clay. No timber; undergrowth, scattered brush and native grasses.</p> <hr/> <p>West, bet. secs. 18 and 19.</p> <p>Over rolling land.</p>
40.00	<p>Point for the 1/4 sec. cor. of secs. 18 and 19.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T 35 N R 24 E S 18 1/4 ——— S 19</p> <p style="text-align: center;">2010</p>

Survey of the Subdivisional Lines,
T. 35 N., R. 24 E., Gila and Salt River Meridian, Arizona

CHAINS	
	<p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p>
78.66	<p>The cor. of secs. 13, 18, 19 and 24, on the W. bdy. of the Tp., monumented with a stainless steel post, 2 1/2 ins. diam., firmly set, 12 ins. below the surface of the ground, with brass cap mkd., T35N R23E R24E S13 S18 S24 S19 1998. Add the marks 2010 to the brass cap.</p> <p>Land, rolling. Soil, sand and sandy clay. No timber; undergrowth, scattered brush and native grasses.</p> <hr/> <p>From the cor. of secs. 17, 18, 19 and 20. N. 0°03' W., bet. secs. 17 and 18. Over rolling land.</p>
40.00	<p>Point for the 1/4 sec. cor. of secs. 17 and 18.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T 35 N R 24 E 1/4 S 18 S 17 2010</p>
	<p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p>
80.00	<p>Point for the cor. of secs. 7, 8, 17 and 18.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T 35 N R 24 E S 7 S 8 S 18 S 17 2010</p>
	<p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p> <p>Land, rolling. Soil, sand and sandy clay. No timber; undergrowth, scattered brush and native grasses.</p> <hr/>

Survey of the Subdivisional Lines,
T. 35 N., R. 24 E., Gila and Salt River Meridian, Arizona

CHAINS	
	From the cor. of secs. 8, 9, 16 and 17. West, bet. secs. 8 and 17. Over rolling land.
8.30	Trail road, bears S. 20° E. and N. 20° W.
26.45	Navajo Route 8090, graded road, 30 ft. wide, bears N. and S.
40.00	Point for the 1/4 sec.cor. of secs. 8 and 17. Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd. <div style="text-align: center;"> T 35 N R 24 E S 8 1/4 ——— S 17 2010 </div>
80.00	Deposit a magnet, in a white plastic case, at the base of the stainless steel post. The cor. of secs. 7, 8, 17 and 18. Land, rolling. Soil, sand and sandy clay. No timber; undergrowth, scattered brush and native grasses. <hr/>
40.00	West, bet. secs. 7 and 18. Over rolling land. Point for the 1/4 sec. cor. of secs. 7 and 18. Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd. <div style="text-align: center;"> T 35 N R 24 E S 7 1/4 ——— S 18 2010 </div>
53.30	Deposit a magnet, in a white plastic case, at the base of the stainless steel post. Graded road, 30 ft. wide, bears N. 15° E. and S. 15° W.

**Survey of the Subdivisional Lines,
T. 35 N., R. 24 E., Gila and Salt River Meridian, Arizona**

CHAINS	
78.57	<p>The cor. of secs. 7, 12, 13 and 18, on the W. bdy. of the Tp., monumented with a stainless steel post, 2 1/2 ins. diam., firmly set, projecting 4 ins. above ground, with brass cap mkd. T35N R23E R24E S12 S7 S13 S18 1998. Add the marks 2010 to the brass cap.</p> <p>Land, rolling. Soil, sand and sandy clay. No timber; undergrowth, scattered brush and native grasses.</p> <hr/> <p>From the cor. of secs. 7, 8, 17 and 18. N. 0°03' W., bet. secs. 7 and 8. Over rolling land.</p>
40.00	<p>Point for the 1/4 sec. cor. of secs. 7 and 8.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T 35 N R 24 E 1/4 S 7 S 8 2010</p> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p> <p>Set a steel fence post nearby.</p> <p>Cor. is located S. of a graded road, 42 lks. dist., bears S. 70° E. and N. 70° W.</p>
80.00	<p>Point for the cor. of secs. 5, 6, 7 and 8.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T 35 N R 24 E S 6 S 5 S 7 S 8 2010</p> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p>

Survey of the Subdivisional Lines,
T. 35 N., R. 24 E., Gila and Salt River Meridian, Arizona

CHAINS	
	<p>Land, rolling. Soil, sand and sandy clay. No timber; undergrowth, scattered brush and native grasses.</p> <hr/> <p>From the cor. of secs. 4, 5, 8 and 9.</p> <p>West, bet. secs. 5 and 8.</p>
22.30	Navajo Route 8090, graded road, 30 ft. wide, bears N. 5° E. and S. 5° W.
40.00	<p>Point for the 1/4 sec. cor. of secs. 5 and 8.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T 35 N R 24 E S 5 1/4 ——— S 8</p> <p style="text-align: center;">2010</p> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p>
80.00	<p>The cor. of secs. 5, 6, 7 and 8.</p> <p>Land, rolling. Soil, sand and sandy clay. No timber; undergrowth, scattered brush and native grasses.</p> <hr/> <p>West, bet. secs. 6 and 7.</p> <p>Over rolling land.</p>
25.65	Graded road, 30 ft. wide, bears N. 15° E. and S. 15° W.
40.00	<p>Point for the 1/4 sec. cor. of secs. 6 and 7.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T 35 N R 24 E S 6 1/4 ——— S 7</p> <p style="text-align: center;">2010</p> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p>

**Survey of the Subdivisional Lines,
T. 35 N., R. 24 E., Gila and Salt River Meridian, Arizona**

CHAINS	
78.49	<p>The cor. of secs. 1, 6, 7 and 12, on the W. bdy. of the Tp., monumented with a stainless steel post, 2 1/2 ins. diam., firmly set, projecting 2 ins. above ground, with brass cap mkd. T35N R23E R24E S1 S6 S12 S7 1998. Add the marks 2010 to the brass cap.</p> <p>Land, rolling. Soil, sand and sandy clay. No timber; undergrowth, scattered brush and native grasses.</p> <hr/> <p>From the cor. of secs. 5, 6, 7 and 8. N. 0°03' W., bet. secs. 5 and 6. Over rolling land.</p>
40.00	<p>Point for the 1/4 sec. cor. of secs. 5 and 6.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T 35 N R 24 E 1/4 S 6 S 5 2010</p> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p>
55.15	Graded road, 20 ft. wide, bears N. 30° E. and S. 30° W.
77.75	Graded road, 20 ft. wide, bears S. 45° E. and N. 45° W.
80.00	<p>The cor. of secs. 5, 6, 31 and 32, on the N. bdy. of the Tp., hereinbefore described.</p> <p>Land, rolling. Soil, sand and sandy clay. No timber; undergrowth, scattered brush and native grasses.</p> <hr/> <p style="text-align: center;">Subdivision of Section 27, T. 35 N., R. 24 E., Gila and Salt River Meridian, Arizona</p> <hr/> <p>From the 1/4 sec. cor. of secs. 27 and 34. N. 0°02' W., on the N. and S. center line of sec. 27. Over rolling land.</p>

**Subdivision of Section 27,
T. 35 N., R. 24 E., Gila and Salt River Meridian, Arizona**

CHAINS	
40.00	<p>Point for the center 1/4 sec. cor. of sec. 27, at intersection with the E. and W. center line.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T 35 N R 24 E C 1/4 S 27</p> <p style="text-align: center;">2010</p> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p> <p>Set a steel fence post nearby.</p>
80.00	<p>The 1/4 sec. cor. of secs. 22 and 27.</p> <hr/> <p>From the 1/4 sec. cor. of secs. 26 and 27.</p> <p>West, on the E. and W. center line of sec. 27.</p> <p>Over rolling land.</p>
40.00	<p>The center 1/4 sec. cor. of sec. 27.</p>
80.00	<p>The 1/4 sec. cor. of secs. 27 and 28.</p> <hr/> <p style="text-align: center;">Subdivision of Section 28, T. 35 N., R. 24 E., Gila and Salt River Meridian, Arizona</p> <hr/> <p>From the 1/4 sec. cor. of secs. 28 and 33.</p> <p>N. 0°02' W., on the N. and S. center line of sec. 28.</p> <p>Over rolling land.</p>
9.05	<p>Power line, bears S. 80° E. and N. 80° W.</p>
20.75	<p>S. right-of-way fence of BIA Route 59, 5 strand barbed wire, parallels highway.</p>
22.40	<p>BIA Route 59, asphalt surface, 40 ft. wide, S. 65° E., and N. 65° W.</p>
24.00	<p>N. right-of-way fence of BIA Route 59, 5 strand barbed wire, parallels highway.</p>
40.00	<p>Point for the center 1/4 sec. cor. of sec. 28, at intersection with the E. and W. center line.</p>

**Subdivision of Section 28,
T. 35 N., R. 24 E., Gila and Salt River Meridian, Arizona**

CHAINS	
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.
	T 35 N R 24 E C 1/4 S 28
	2010
	Deposit a magnet, in a white plastic case, at the base of the stainless steel post.
	Set steel fence post nearby.
80.00	The 1/4 sec. cor. of secs. 21 and 28.
	<hr/>
	From the 1/4 sec. cor. of secs. 27 and 28.
	West, on the E. and W. center line of sec. 28.
	Over rolling land.
40.00	The center 1/4 sec. cor. of sec. 28.
80.00	The 1/4 sec. cor. of secs. 28 and 29.
	<hr/>
	Subdivision of Section 29, T. 35 N., R. 24 E., Gila and Salt River Meridian, Arizona
	<hr/>
	From the 1/4 sec. cor. of secs. 29 and 32.
	N. 0°03' W., on the N. and S. center line of sec. 29.
	Over rolling land.
7.90	Wash, 25 ft. wide, 5 ft. deep, drains S. 65° E.
25.95	Power line, bears S. 75° E. and N. 75° W.
28.85	S. right-of-way fence of BIA Route 59, 5 strand barbed wire, parallels highway.
30.40	BIA Route 59, asphalt surface, 40 ft. wide, bears S. 85° E. and N. 85° W.
31.90	N. right-of-way fence of BIA Route 59, 5 strand barbed wire, parallels highway.
40.00	Point for the center 1/4 sec. cor. of sec. 29, at intersection with the E. and W. center line.

**Subdivision of Section 29,
T. 35 N., R. 24 E., Gila and Salt River Meridian, Arizona**

CHAINS	
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.
	T 35 N R 24 E C 1/4 S 29
	2010
	Deposit a magnet, in a white plastic case, at the base of the stainless steel post.
	Set a steel fence post nearby.
80.00	The 1/4 sec. cor. of secs. 20 and 29.

	From the 1/4 sec. cor. of secs. 28 and 29.
	West, on the E. and W. center line of sec. 29.
	Over rolling land.
40.00	The center 1/4 sec. cor. of sec. 29.
43.85	Graded road, 25 ft. wide, bears N. and S.
75.30	Navajo Route 8090, a graded road, 30 ft. wide, bears N. 25° E. and S. 25° W.
80.00	The 1/4 sec. cor. of secs. 29 and 30.

	Subdivision of Section 30, T. 35 N., R. 24 E., Gila and Salt River Meridian, Arizona

	From the 1/4 sec. cor. of secs. 30 and 31.
	N. 0°03' W., on the N. and S. center line of sec. 30.
	Over rolling land.
26.45	Graded road, 25 ft. wide, bears S. 30° E. and N. 30° W.
33.30	Power line, bears S. 85° E. and N. 85° W.
34.10	S. right-of-way fence of BIA Route 59, 5 strand barbed wire, parallels highway.
35.60	BIA Route 59, asphalt surface, 40 ft. wide, bears S. 85° E. and N. 85° W.
37.10	N. right-of-way fence of BIA Route 59, 5 strand barbed wire, parallels highway.

**Subdivision of Section 30,
T. 35 N., R. 24 E., Gila and Salt River Meridian, Arizona**

CHAINS	
40.00	<p>Point for the center 1/4 sec. cor. of sec. 30, at intersection with the E. and W. center line.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T 35 N R 24 E C 1/4 S 30</p> <p style="text-align: center;">2010</p> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p> <p>Set a steel fence post nearby.</p>
80.00	<p>The 1/4 sec. cor. of secs. 19 and 30.</p> <hr/> <p>From the 1/4 sec. cor. of secs. 29 and 30.</p> <p>West, on the E. and W. center line of sec. 30.</p> <p>Over rolling land.</p>
40.00	<p>The center 1/4 sec. cor. of sec. 30.</p>
66.65	<p>Apache County Road C580, a graded road, 30 ft. wide, bears S. 40° E. and N. 40° W.</p>
78.80	<p>The 1/4 sec. cor. of secs. 25 and 30, T. 35 N., Rs. 23 and 24 E., on the W. bdy. of the Tp., monumented with a stainless steel post, firmly set, projecting 4 ins. above ground, with brass cap mkd. T35N R23E R24E 1/4 S25 S30 1998. Add the marks 2010 to the brass cap.</p> <hr/> <p style="text-align: center;">Subdivision of Section 34, T. 35 N., R. 24 E., Gila and Salt River Meridian, Arizona</p> <hr/> <p>From the 1/4 sec. cor. of secs. 3 and 34, on the S. bdy. of the Tp., hereinbefore described.</p> <p>N. 0°02' W., on the N. and S. center line of sec. 34.</p> <p>Over rolling land.</p>
40.00	<p>Point for the center 1/4 sec. cor. of sec. 34, at intersection with the E. and W. center line.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p>

Subdivision of Section 34,
T. 35 N., R. 24 E., Gila and Salt River Meridian, Arizona

CHAINS	
	T 35 N R 24 E C 1/4 S 34
	2010
	Deposit a magnet, in a white plastic case, at the base of the stainless steel post.
	Set steel fence post nearby.
45.13	Northeasterly cor. of a Hogan, bears West, 80.0 lks. dist.
56.40	Wash, 15 ft. wide, 2 ft. deep, drains S. 80° E.
56.75	Graded road, 25 ft. wide, bears N. 10° E. and S. 10° W.
58.30	Power line, bears S. 55° E. and N. 55° W.
64.30	S. right-of-way fence of BIA Route 59, 5 strand barbed wire, parallels highway.
66.15	BIA Route 59, asphalt surface, 40 ft. wide, bears S. 55° E. and N. 55° W.
68.00	N. right-of-way fence of BIA Route 59, 5 strand barbed wire, parallels highway.
80.00	The 1/4 sec. cor. of secs. 27 and 34.
	<hr/>
	From the 1/4 sec. cor. of secs. 34 and 35.
	West, on the E. and W. center line of sec. 34.
	Over rolling land.
2.70	E. right-of-way fence of BIA Route 59, 5 strand barbed wire, parallels highway.
5.20	BIA Route 59, asphalt surface, 40 ft. wide, bears S. 50° E. and N. 50° W.
7.70	W. right-of-way fence of BIA Route 59, 5 strand barbed wire, parallels highway.
17.70	Power line, bears S. 50° E. and N. 50° W.
40.00	The center 1/4 sec. cor. of sec. 34.
80.00	The 1/4 sec. cor. of secs. 33 and 34.
	<hr/>

Subdivision of Section 35,
T. 35 N., R. 24 E., Gila and Salt River Meridian, Arizona

CHAINS	
	<p>From the 1/4 sec. cor. of secs. 2 and 35, on the S. bdy. of the Tp., hereinbefore described.</p> <p>N. 0°01' W., on the N. and S. center line of sec 35.</p> <p>Over rolling land.</p>
4.10	E. right-of-way fence of BIA Route 59, 5 strand barbed wire, parallels highway.
5.97	BIA Route 59, asphalt surface, 50 ft. wide, bears S. 53° E. and N. 53° W.
7.88	W. right-of-way fence of BIA Route 59, 5 strand barbed wire, parallels highway.
40.00	<p>Point for the center 1/4 sec. cor. of secs. 35, at intersection with the E. and W. center line.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T 35 N R 24 E C 1/4 S 35</p> <p style="text-align: center;">2010</p> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p> <p>Set a steel fence post nearby.</p>
80.00	<p>The 1/4 sec. cor. of secs. 26 and 35.</p> <hr/> <p>From the 1/4 sec. cor. of secs. 35 and 36.</p> <p>West, on the E. and W. center line of sec. 35.</p> <p>Over rolling land.</p>
40.00	The center 1/4 sec. cor. of sec. 35.
80.00	<p>The 1/4 sec. cor. of secs. 34 and 35.</p> <hr/>

T. 35 N., R. 24 E., Gila and Salt River Meridian, Arizona

CHAINS

GENERAL DESCRIPTION

The area surveyed is within the Navajo Indian Reservation and approximately 5 miles northwest of the community of Many Farms, Arizona. The terrain is mostly rolling to nearly level. The principal drainage is southwest.

The elevation varies from 5600 to 6000 feet above sea level. The soil is mostly sand and sandy clay. Vegetation principally consists of undergrowth, scattered brush and native grasses.

Principal access is provided by BIA Route 59, a paved highway, which enters the township in section 35 and exits in section 30. Navajo Route 8090 and Apache County Road C580, all graded roads provide additional access with numerous graded and trail roads. Much of the area is used for grazing livestock. There are permanent homesteads throughout the township. There is no current mining activity in the township.

The mean magnetic declination of $10\frac{3}{4}^{\circ}$ E. was derived from the United States Geological Survey computer program GEOMAG, utilizing the World Magnetic Model for Epoch 2005-2010 for the dates of survey.

CERTIFICATE OF SURVEY

I, Alvina A. Begaye, Cadastral Surveyor, HEREBY CERTIFY upon honor, that in pursuance of special instructions bearing date of the 23rd day of August, 2010, I have surveyed the south and north boundaries, the subdivisional lines and subdivided certain sections, T. 35 N., R. 24 E., of the Gila and Salt River Meridian, in the State of Arizona, which are represented in the foregoing field notes as having been executed by me and under my direction. Said survey has been made in strict conformity with said special instructions, the Manual of Surveying Instructions for the Survey of the Public Lands of the United States, 2009, and in specific manner described in the foregoing field notes.

2/23/2012
(Date)

Alvina A. Begaye
(Cadastral Surveyor)

CERTIFICATE OF APPROVAL

BUREAU OF LAND MANAGEMENT
Phoenix, Arizona

The foregoing field notes of the survey of the south and north boundaries, the subdivisional lines and the subdivision of certain sections, T. 35 N., R. 24 E., Gila and Salt River Meridian, in the State of Arizona, executed by Alvina A. Begaye, Cadastral Surveyor, having been critically examined and found correct, are hereby approved.

2/27/2012
(Date)

Stephen K. Hanna
(Chief Cadastral Surveyor of Arizona)

~~CERTIFICATE OF TRANSCRIPT~~

~~I CERTIFY That the foregoing transcript of the field notes of the above described surveys in T. 35 N., R. 24 E., Gila and Salt River Meridian, Arizona, is a true copy of the original field notes.~~

~~_____
(Date)~~

~~_____
(Chief Cadastral Surveyor of Arizona)~~