

ORIGINAL

**UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT**

FIELD NOTES

OF THE

DEPENDENT RESURVEY OF A PORTION OF THE
SIXTH STANDARD PARALLEL NORTH (SOUTH BOUNDARY),
TOWNSHIP 25 NORTH, RANGE 23 EAST,
THE SURVEY OF THE SOUTH AND WEST BOUNDARIES,
THE SUBDIVISIONAL LINES
AND THE SUBDIVISION OF CERTAIN SECTIONS,
TOWNSHIP 24 NORTH, RANGE 23 EAST,
OF THE GILA AND SALT RIVER MERIDIAN,
IN THE STATE OF ARIZONA.

EXECUTED BY

Fabian Yazzie, Cadastral Surveyor

Under Special Instructions dated November 9, 2010, approved November 9, 2010, which provided for the surveys included under Group No. 1087 and assignment instructions dated November 9, 2010.

Survey commenced November 16, 2010

Survey completed February 1, 2011

INDEX DIAGRAM

TOWNSHIP 24 NORTH RANGE 23 EAST
GILA AND SALT RIVER MERIDIAN, ARIZONA

				4	4	
16	67 6 66	67 5 54	55 4 44	46 3 35	36 2 25	26 1 24
	65	64	53	44	34	24
15	7 63	8 52	9 43	10 33	11 23	12 23
	63	62	52	43	32	23
14	18 61	17 51	16 42	15 31	14 22	13 21
	61	60	50	41	30	21
13	19 59	20 49	21 40	22 30	23 20	24 19
	58	58	49	39	29	19
12	30 57	29 48	28 38	27 28	26 18	25 18
	57	56	47	37	28	18
10	31 55	32 46	33 37	34 27	35 17	36 5
	9	8	7	6	6	5

Subdivision of Section 3Pages 68-69
 Subdivision of Section 4Pages 69-70
 Subdivision of Section 5Pages 70-71
 Subdivision of Section 7Pages 71-72
 Subdivision of Section 8Pages 72-73

T. 24 N., R. 23 E., Gila and Salt River Meridian, Arizona

CHAINS

The following field notes describe the dependent resurvey of a portion of the Sixth Standard Parallel North (South Boundary), Township 25 North, Range 23 East, the survey of the south and west boundaries, the subdivisional lines and the subdivision of certain sections, Township 24 North, Range 23 East, Gila and Salt River Meridian, Arizona.

The history of surveys pertaining to this survey is as follows:

Frank Follman surveyed the Sixth Standard Parallel North through Ranges 22 and 23 East, in 1883. Jones Curtiss dependently resurveyed the Sixth Standard Parallel North (south boundary), Township 25 North, Ranges 22 and 23 East, in 2001-02. Leonard R. Sandoval surveyed the west boundary, Township 24 North, Range 24 East, in 2004-05.

The survey was executed in accordance with the specifications as set forth in the Manual of Surveying Instructions for the Survey of the Public Lands of the United States, 2009 and the Special Instructions dated November 9, 2010, for Group Number 1087, Arizona.

The true meridian direction and length of all lines were determined by real time kinematic global positioning system observations using Trimble Navigation 5700 model receivers.

Preliminary to the resurvey, the lines of the prior surveys were retraced and search was made for all corners and other calls of record. Identified corners were remonumented in their original positions. Lost corners were reestablished and remonumented at proportionate positions based on the official record. The retracement data were thoroughly verified and only the true line field notes are given herein.

Geodetic control was derived from Global Positioning System (GPS) static observations post processed by National Geodetic Survey, Online Positioning User Service (OPUS), utilizing Continuously Operating Reference Stations (CORS) NAU FLAGSTAFF CORS ARP, DUECECLUBSAZ2005 CORS ARP, SPIDERROCKAZ2005 CORS ARP and TWIN. The NAD 83 (CORS96) (EPOCH: 2002), geographic position of the southeast township corner, is as follows:

Latitude: 35°25'52.69" N. Longitude: 109°50'36.85" W.

The NAD 83 (CORS96) (EPOCH: 2002), geographic position of the northwest township closing corner, is as follows:

Latitude: 35°31'04.90" N. Longitude: 109°56'56.81" W.

The mean magnetic declination is 10 1/2° E.

Dependent Resurvey of a Portion of the
Sixth Standard Parallel North (South Boundary),
T. 25 N., R. 23 E., Gila and Salt River Meridian, Arizona

CHAINS	<p style="text-align: center;">Restoring the resurvey executed by Jones Curtiss, in 2001-02</p> <hr style="width: 20%; margin: auto;"/> <p>Beginning at the stan. 1/4 sec. cor. of sec. 34, T. 25 N., R. 23 E., monumented with a stainless steel post, 2 1/2 ins. diam., firmly set, projecting 4 ins. above ground, with brass cap mkd. SC T25N R23E 1/4 S34 2001. Add the marks 2010 to the brass cap.</p> <p>S. 89°55' E., on the S. bdy. of sec. 34.</p> <p>Over rolling land.</p>
40.17	<p>Point for the stan. cor. of secs. 34 and 35, at proportionate dist.; there is no remaining evidence of the orig. stainless steel post.</p> <p>Set a magnet, in a white plastic case, 24 ins. below the surface of the ground.</p> <p>from which</p> <p style="padding-left: 40px;">A stainless steel post, 28 ins. long, 2 1/2 ins. diam., set flush with the surface of the ground for a reference monument, bears N. 45°00' E., 60.0 ft. dist. with brass cap mkd. RM SC T25N R23E S35 60.0 FT TO COR 2010 and an arrow pointing to the cor. Deposit a magnet, in a white plastic case, at the base of the stainless steel post. Set a steel fence post nearby.</p> <p style="padding-left: 40px;">A stainless steel post, 28 ins. long, 2 1/2 ins. diam., set 24 ins. in the ground for a reference monument, bears N. 45°00' W., 100.0 ft. dist. with brass cap mkd. RM SC T25N R23E S34 100.0 FT TO COR 2010 and an arrow pointing to the cor. Deposit a magnet, in a white plastic case, at the base of the stainless steel post. Set a steel fence post nearby.</p> <p>The stan. cor. is located in a manmade sandy drainage, 15 ft. wide, 4 ft. deep, drains ESE.</p> <hr style="width: 20%; margin: auto;"/> <p>S. 89°55' E., beginning new measurement.</p> <p>Over rolling land.</p>
40.17	<p>The stan. 1/4 sec. cor. of sec. 35, monumented with a stainless steel post, 2 1/2 ins. diam., firmly set, projecting 4 ins. above ground, with brass cap mkd. SC T25N R23E 1/4 S35 2002. Add the marks 2010 to the brass cap.</p> <hr style="width: 20%; margin: auto;"/>

Survey of the South Boundary,
T. 24 N., R. 23 E., Gila and Salt River Meridian, Arizona

CHAINS							
	<p>From the cor. of Tps. 23 and 24 N., Rs. 23 and 24 E., monumented with a stainless steel post, 2 1/2 ins. diam., firmly set, projecting 4 ins. above ground, with brass cap mkd. T24N R23E R24E S36 S31 S1 S6 T23N 2004.</p> <p>Add the marks 2010 to the brass cap.</p> <p>S. 89°54' W., bet. secs. 1 and 36.</p> <p>Over gently rolling land.</p>						
40.00	<p>Point for the 1/4 sec. cor. of secs. 1 and 36.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center;"> <p>T 24 N R 23 E</p> <p>S 36</p> <p>1/4 ———</p> <p>S 1</p> <p>T 23 N</p> <p>2010</p> </div> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p> <p>Cor. is located at the base of a sandy clay mesa.</p>						
41.05	Sandstone mesa rim, 60 ft. high, bears N. 35° E. and S. 35° W.						
68.50	Trail road, bears N. 5° E. and S. 5° W.						
80.00	<p>Point for the cor. of secs. 1, 2, 35 and 36.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center;"> <p>T 24 N R 23 E</p> <table style="margin: auto;"> <tr> <td style="border-right: 1px solid black; padding: 0 5px;">S 35</td> <td style="padding: 0 5px;">S 36</td> </tr> <tr> <td style="border-right: 1px solid black; padding: 0 5px;">S 2</td> <td style="padding: 0 5px;">S 1</td> </tr> <tr> <td colspan="2" style="text-align: center;">T 23 N</td> </tr> </table> <p>2010</p> </div> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p> <p>Land, gently rolling to nearly level. Soil, sandy clay. Vegetation, native grasses.</p> <hr style="width: 60%; margin-left: 0;"/>	S 35	S 36	S 2	S 1	T 23 N	
S 35	S 36						
S 2	S 1						
T 23 N							

Survey of the South Boundary,
T. 24 N., R. 23 E., Gila and Salt River Meridian, Arizona

CHAINS					
	<p>S. 89°54' W., bet. secs. 2 and 35.</p> <p>Over gently rolling land.</p>				
40.00	<p>Point for the 1/4 sec. cor. of secs. 2 and 35.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center;"> <p>T 24 N R 23 E</p> <p>S 35</p> <p>1/4 ———</p> <p>S 2</p> <p>T 23 N</p> <p>2010</p> </div> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p>				
73.70	<p>Barbed wire fence, 4 strand, bears N. 50° E. and S. 50° W.</p>				
80.00	<p>Point for the cor. of secs. 2, 3, 34 and 35.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center;"> <p>T 24 N R 23 E</p> <table style="margin: auto; border-collapse: collapse;"> <tr> <td style="border-right: 1px solid black; padding: 0 5px;">S 34</td> <td style="padding: 0 5px;">S 35</td> </tr> <tr> <td style="border-right: 1px solid black; padding: 0 5px;">S 3</td> <td style="padding: 0 5px;">S 2</td> </tr> </table> <p>T 23 N</p> <p>2010</p> </div> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p> <p>Land, gently rolling to nearly level. Soil, sandy clay. Vegetation, native grasses.</p> <hr style="width: 60%; margin: 10px auto;"/>	S 34	S 35	S 3	S 2
S 34	S 35				
S 3	S 2				
	<p>S. 89°54' W., bet. secs. 3 and 34.</p> <p>Over gently rolling land.</p>				
40.00	<p>Point for the 1/4 sec. cor. of secs. 3 and 34.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p>				

Survey of the South Boundary,
T. 24 N., R. 23 E., Gila and Salt River Meridian, Arizona

CHAINS	
	T 24 N R 23 E S 34 1/4 ——— S 3 T 23 N 2010 Deposit a magnet, in a white plastic case, at the base of the stainless steel post.
80.00	Point for the cor. of secs. 3, 4, 33 and 34. Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd. <div style="text-align: center;"> T 24 N R 23 E S 33 S 34 ———— S 4 S 3 T 23 N 2010 </div> Deposit a magnet, in a white plastic case, at the base of the stainless steel post. Land, gently rolling. Soil, sandy clay. Vegetation, native grasses.
	S. 89°54' W., bet. secs. 4 and 33. Over gently rolling land.
5.10	Barbed wire fence, 5 strand, bears N. 15° E. and S. 15° W.
11.20	Trail road, bears S. 75° E. and N. 75° W.
32.70	Pueblo Colorado Wash, 10 ft. wide, 1 ft. deep, drains S. 15° W.
34.35	BIA Route N157, graded road, 15 ft. wide, bears N. 10° E. and S. 10° W.
40.00	Point for the 1/4 sec. cor. of secs. 4 and 33. Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.

Survey of the South Boundary,
T. 24 N., R. 23 E., Gila and Salt River Meridian, Arizona

CHAINS	
	T 24 N R 23 E S 33 1/4 ——— S 4 T 23 N 2010
	Deposit a magnet, in a white plastic case, at the base of the stainless steel post. Cor. is located on the E. facing sandy slope of hill.
49.40	Power line, 2 strand, bears N. 30° E. and S. 30° W.
57.80	Graded road, 20 ft. wide, bears N. 15° E. and S. 15° W.
60.00	Trail road, bears N. 75° E. and S. 75° W.
77.60	Trail road, bears S. 25° E. and N. 25° W.
79.70	Power line, 2 strand, bears S. 40° E. and N. 35° W.
80.00	Point for the cor. of secs. 4, 5, 32 and 33.
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd. <div style="text-align: center;"> T 24 N R 23 E S 32 S 33 ———— S 5 S 4 T 23 N </div> 2010
	Deposit a magnet, in a white plastic case, at the base of the stainless steel post. Land, gently rolling. Soil, sandy clay. Vegetation, native grasses.
	<hr/> S. 89°54' W., bet. secs. 5 and 32. Over gently rolling land.
38.70	Graded road, 20 ft. wide, bears S. 60° E. and N. 60° W.
40.00	Point for the 1/4 sec. cor. of secs. 5 and 32.
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.

Survey of the South Boundary,
T. 24 N., R. 23 E., Gila and Salt River Meridian, Arizona

CHAINS	
	T 24 N R 23 E S 32 1/4 ——— S 5 T 23 N 2010 Deposit a magnet, in a white plastic case, at the base of the stainless steel post.
80.00	Point for the cor. of secs. 5, 6, 31 and 32. Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd. <div style="text-align: center;"> T 24 N R 23 E S 31 S 32 ———— S 6 S 5 T 23 N 2010 </div> Deposit a magnet, in a white plastic case, at the base of the stainless steel post. Land, gently rolling. Soil, sandy clay. Vegetation, native grasses.
	<hr/> S. 89°54' W., bet. secs. 6 and 31. Over gently rolling land.
38.80	Graded road, 20 ft. wide, bears N. 65° E. and S. 65° W.
40.00	Point for the 1/4 sec. cor. of secs. 6 and 31. Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd. <div style="text-align: center;"> T 24 N R 23 E S 31 1/4 ——— S 6 T 23 N 2010 Deposit a magnet, in a white plastic case, at the base of the stainless steel post. </div>

**Survey of the South Boundary,
T. 24 N., R. 23 E., Gila and Salt River Meridian, Arizona**

CHAINS

72.00 Barbed wire fence, 5 strand, bears N. 55° E. and S. 55° W.

76.35 Barbed wire fence, 5 strand, bears S. 35° E. and N. 35° W.

76.56 Point for the cor. of secs. 1, 6, 31 and 36, determined North from the cor. of Tps. 22 and 23 N., Rs. 22 and 23 E., at intersection with the line bet. the cor. of Tps. 23 and 24 N., Rs. 23 and 24 E. and Tps. 23 and 24 N., Rs. 21 and 22 E.

Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.

T 24 N	
R 22 E	R 23 E
S 36	S 31
S 1	S 6
T 23 N	

2010

Deposit a magnet, in a white plastic case, at the base of the stainless steel post.

From this cor., the cor. of Tps. 23 and 24 N., Rs. 21 and 22 E., bears S. 89°54' W., 477.63 chs. dist., monumented with a stainless steel post, 2 1/2 ins. diam., firmly set, projecting 7 ins. above ground, in a collar of stone, with brass cap mkd. T24N R21E R22E S36 S31 S1 S6 T23N 2004, with a mound of stone, 2 ft. base, 1 1/2 ft. high, S. of cor. Add the marks 2010 to the brass cap.

From this same cor., the point for the cor. of Tps. 22 and 23 N., Rs. 22 and 23 E., bears South, 478.09 chs. dist., determined at proportionate dist. longitudinally and record dist. latitudinally; there is no remaining evidence of the orig. cor.

Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.

T 23 N	
R 22 E	R 23 E
S 36	S 31
S 1	S 6
T 22 N	

2011

Deposit a magnet, in a white plastic case, at the base of the stainless steel post.

**Survey of the South Boundary,
T. 24 N., R. 23 E., Gila and Salt River Meridian, Arizona**

CHAINS

From this cor. of Tps. 22 and 23 N., Rs. 22 and 23 E., the cor. of Tps. 22 and 23 N., Rs. 23 and 24 E., bears S. 89°53' E., 477.07 chs. dist., monumented with a stainless steel post, 2 1/2 ins. diam., firmly set, projecting 5 ins. above ground, with brass cap mkd. T23N R23E R24E S36 S31 S1 S6 T22N 2004. Add the marks 2010 to the brass cap.

From this same cor. of Tps. 22 and 23 N., Rs. 22 and 23 E., the stan. cor. of Tps. 21 N., Rs. 22 and 23 E., bears S. 00°06' W., 960.00 chs. dist., monumented with a iron post, 2 1/2 ins. diam., firmly set, projecting 7 ins. above ground, with brass cap mkd. SC T21N R22E R23E S36 S31 1944, with a mound of stone, 2 ft. base, 4 ft. high, N. of cor. Add the marks 2010 to the brass cap.

From this same cor. of Tps. 22 and 23 N., Rs. 22 and 23 E., the cor. of Tps. 22 and 23 N., Rs. 21 and 22 E., bears S. 89°39' W., 478.36 chs. dist., monumented with a stainless steel post, 2 1/2 ins. diam., firmly set, projecting 3 ins. above ground, with brass cap mkd. T23N R21E R22E S36 S31 S1 S6 T22N 2009 2004, with a mound of stone, 3 ft. base, 2 ft. high, S. of cor. Add the marks 2010 to the brass cap.

Land, gently rolling.
Soil, sandy clay.
Vegetation, native grasses.

**Survey of the West Boundary,
T. 24 N., R. 23 E., Gila and Salt River Meridian, Arizona**

From the cor. of Tps. 23 and 24 N., Rs. 22 and 23 E., hereinbefore described.

North, bet. secs. 31 and 36.

Over gently rolling land.

0.30 Barbed wire fence, 5 strand, bears S. 35° E. and N. 35° W.
2.85 Barbed wire fence, 5 strand, bears N. 55° E. and S. 55° W.
40.00 Point for the 1/4 sec. cor. of secs. 31 and 36.

Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.

Survey of the West Boundary,
T. 24 N., R. 23 E., Gila and Salt River Meridian, Arizona

CHAINS	
	T 24 N 1/4 R 22 E R 23 E S 36 S 31 2010
	Deposit a magnet, in a white plastic case, at the base of the stainless steel post.
53.65	Power line, 4 strand, bears N. 35° E. and S. 35° W.
58.75	BIA Route 153, a graded road, 20 ft. wide, bears N. 40° E. and S. 40° W.
78.40	Trail road, bears S. 45° E. and N. 45° W.
80.00	Point for the cor. of secs. 25, 30, 31 and 36.
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.
	T 24 N R 22 E R 23 E S 25 S 30 S 36 S 31 2010
	Deposit a magnet, in a white plastic case, at the base of the stainless steel post.
	Land, gently rolling. Soil, sandy clay. Vegetation, native grasses.

	North, bet. secs. 25 and 30.
	Over gently rolling land.
40.00	Point for the 1/4 sec. cor. of secs. 25 and 30.
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.
	T 24 N 1/4 R 22 E R 23 E S 25 S 30 2010

Survey of the West Boundary,
T. 24 N., R. 23 E., Gila and Salt River Meridian, Arizona

CHAINS											
	Deposit a magnet, in a white plastic case, at the base of the stainless steel post.										
79.50	Trail road, bears N. 60° E. and S. 60° W.										
80.00	Point for the cor. of secs. 19, 24, 25 and 30.										
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.										
	<table style="margin: auto;"> <tr><td colspan="2">T 24 N</td></tr> <tr><td>R 22 E</td><td>R 23 E</td></tr> <tr><td>S 24</td><td>S 19</td></tr> <tr><td colspan="2"><hr/></td></tr> <tr><td>S 25</td><td>S 30</td></tr> </table>	T 24 N		R 22 E	R 23 E	S 24	S 19	<hr/>		S 25	S 30
T 24 N											
R 22 E	R 23 E										
S 24	S 19										
<hr/>											
S 25	S 30										
	2010										
	Deposit a magnet, in a white plastic case, at the base of the stainless steel post.										
	Set a steel fence post alongside the stainless steel post.										
	Land, gently rolling. Soil, sandy clay. Vegetation, native grasses.										
	<hr/>										
	North, bet. secs. 19 and 24.										
	Over gently rolling land.										
39.40	Trail road, bears S. 55° E. and N. 55° W.										
40.00	Point for the 1/4 sec. cor. of secs. 19 and 24.										
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.										
	<table style="margin: auto;"> <tr><td colspan="2">T 24 N</td></tr> <tr><td colspan="2">1/4</td></tr> <tr><td>R 22 E</td><td>R 23 E</td></tr> <tr><td>S 24</td><td>S 19</td></tr> </table>	T 24 N		1/4		R 22 E	R 23 E	S 24	S 19		
T 24 N											
1/4											
R 22 E	R 23 E										
S 24	S 19										
	2010										
	Deposit a magnet, in a white plastic case, at the base of the stainless steel post.										
72.50	Underground water line, bears S. 75° E. and N. 75° W.										
80.00	Point for the cor. of secs. 13, 18, 19 and 24.										

Survey of the West Boundary,
T. 24 N., R. 23 E., Gila and Salt River Meridian, Arizona

CHAINS																	
	<p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center; margin: 10px 0;"> <table style="margin: auto; border-collapse: collapse;"> <tr><td colspan="2">T 24 N</td></tr> <tr><td style="border-right: 1px solid black; padding: 0 5px;">R 22 E</td><td style="padding: 0 5px;">R 23 E</td></tr> <tr><td style="border-right: 1px solid black; padding: 0 5px;">S 13</td><td style="padding: 0 5px;">S 18</td></tr> <tr><td style="border-right: 1px solid black; padding: 0 5px;">S 24</td><td style="padding: 0 5px;">S 19</td></tr> </table> </div> <p style="text-align: center; margin: 10px 0;">2010</p> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p> <p>Land, gently rolling. Soil, sandy clay. Vegetation, native grasses.</p> <hr style="width: 80%; margin: 20px auto;"/> <p>North, bet. secs. 13 and 18.</p> <p>Over gently rolling land.</p> <p>1.60 Trail road, bears N. 35° E. and S. 35° W.</p> <p>10.75 Power line, 2 strand, bears E. and W.</p> <p>32.25 Underground gas pipeline, bears S. 75° E. and N. 75° W.</p> <p>34.00 Trail road, bears S. 35° E. and N. 35° W.</p> <p>40.00 Point for the 1/4 sec. cor. of secs. 13 and 18.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center; margin: 10px 0;"> <table style="margin: auto; border-collapse: collapse;"> <tr><td colspan="2">T 24 N</td></tr> <tr><td colspan="2">1/4</td></tr> <tr><td style="border-right: 1px solid black; padding: 0 5px;">R 22 E</td><td style="padding: 0 5px;">R 23 E</td></tr> <tr><td style="border-right: 1px solid black; padding: 0 5px;">S 13</td><td style="padding: 0 5px;">S 18</td></tr> </table> </div> <p style="text-align: center; margin: 10px 0;">2010</p> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p> <p>80.00 Point for the cor. of secs. 7, 12, 13 and 18.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p>	T 24 N		R 22 E	R 23 E	S 13	S 18	S 24	S 19	T 24 N		1/4		R 22 E	R 23 E	S 13	S 18
T 24 N																	
R 22 E	R 23 E																
S 13	S 18																
S 24	S 19																
T 24 N																	
1/4																	
R 22 E	R 23 E																
S 13	S 18																

Survey of the West Boundary,
T. 24 N., R. 23 E., Gila and Salt River Meridian, Arizona

CHAINS											
	<table style="margin: auto;"> <tr><td colspan="2">T 24 N</td></tr> <tr><td>R 22 E</td><td>R 23 E</td></tr> <tr><td>S 12</td><td>S 7</td></tr> <tr><td colspan="2"><hr/></td></tr> <tr><td>S 13</td><td>S 18</td></tr> </table>	T 24 N		R 22 E	R 23 E	S 12	S 7	<hr/>		S 13	S 18
T 24 N											
R 22 E	R 23 E										
S 12	S 7										
<hr/>											
S 13	S 18										
	2010										
	Deposit a magnet, in a white plastic case, at the base of the stainless steel post.										
	Land, gently rolling. Soil, sandy clay. Vegetation, native grasses.										
	<hr/>										
	North, bet. secs. 7 and 12.										
	Over gently rolling land.										
9.35	S. right-of-way fence of BIA Route 15, barbed wire, 5 strand, parallels highway.										
10.65	BIA Route 15, an asphalt road, 35 ft. wide, bears N. 70° E. and S. 70° W.										
11.95	N. right-of-way fence of BIA Route 15, barbed wire, 5 strand, parallels highway.										
38.35	Underground gas pipeline, bears N. 65° E. and S. 65° W.										
40.00	Point for the 1/4 sec. cor. of secs. 7 and 12.										
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.										
	<table style="margin: auto;"> <tr><td colspan="2">T 24 N</td></tr> <tr><td colspan="2">1/4</td></tr> <tr><td>R 22 E</td><td>R 23 E</td></tr> <tr><td>S 12</td><td>S 7</td></tr> </table>	T 24 N		1/4		R 22 E	R 23 E	S 12	S 7		
T 24 N											
1/4											
R 22 E	R 23 E										
S 12	S 7										
	2010										
	Deposit a magnet, in a white plastic case, at the base of the stainless steel post.										
80.00	Point for the cor. of secs. 1, 6, 7 and 12.										
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.										

Survey of the West Boundary,
T. 24 N., R. 23 E., Gila and Salt River Meridian, Arizona

CHAINS													
	<table style="margin: auto; border-collapse: collapse;"> <tr><td colspan="2" style="text-align: center;">T 24 N</td></tr> <tr><td style="text-align: center;">R 22 E</td><td style="text-align: center;">R 23 E</td></tr> <tr><td style="text-align: center;">S 1</td><td style="text-align: center;">S 6</td></tr> <tr><td style="text-align: center;">S 12</td><td style="text-align: center;">S 7</td></tr> </table>	T 24 N		R 22 E	R 23 E	S 1	S 6	S 12	S 7				
T 24 N													
R 22 E	R 23 E												
S 1	S 6												
S 12	S 7												
	2011												
	Deposit a magnet, in a white plastic case, at the base of the stainless steel post.												
	Land, gently rolling. Soil, sandy clay. Vegetation, native grasses.												
	North, bet. secs. 1 and 6.												
	Over gently rolling land.												
5.65	Trail road, bears N. 10° E. and S. 10° W.												
40.00	Point for the 1/4 sec. cor. of secs. 1 and 6.												
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.												
	<table style="margin: auto; border-collapse: collapse;"> <tr><td colspan="2" style="text-align: center;">T 24 N</td></tr> <tr><td colspan="2" style="text-align: center;">1/4</td></tr> <tr><td style="text-align: center;">R 22 E</td><td style="text-align: center;">R 23 E</td></tr> <tr><td style="text-align: center;">S 1</td><td style="text-align: center;">S 6</td></tr> </table>	T 24 N		1/4		R 22 E	R 23 E	S 1	S 6				
T 24 N													
1/4													
R 22 E	R 23 E												
S 1	S 6												
	2011												
	Deposit a magnet, in a white plastic case, at the base of the stainless steel post.												
79.33	Point for the closing cor. of Tps. 24 N., Rs. 22 and 23 E., at intersection with the Sixth Standard Parallel North, the N. bdy. of the Tp.												
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.												
	<table style="margin: auto; border-collapse: collapse;"> <tr><td style="text-align: center;">T 25 N</td><td style="text-align: center;">R 22 E</td></tr> <tr><td colspan="2" style="text-align: center;">S 36</td></tr> <tr><td style="text-align: center;">S 1</td><td style="text-align: center;">S 6</td></tr> <tr><td style="text-align: center;">R 22 E</td><td style="text-align: center;">R 23 E</td></tr> <tr><td colspan="2" style="text-align: center;">T 24 N</td></tr> <tr><td colspan="2" style="text-align: center;">CC</td></tr> </table>	T 25 N	R 22 E	S 36		S 1	S 6	R 22 E	R 23 E	T 24 N		CC	
T 25 N	R 22 E												
S 36													
S 1	S 6												
R 22 E	R 23 E												
T 24 N													
CC													
	2011												

**Survey of the West Boundary,
T. 24 N., R. 23 E., Gila and Salt River Meridian, Arizona**

CHAINS	<p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p> <p>From this cor. point, the stan. 1/4 sec. cor. of sec. 36, T. 25 N., R. 22 E., bears S. 89°55' E., 28.735 chs. dist., monumented with a stainless steel post, 2 1/2 ins. diam., firmly set, projecting 5 ins. above ground with brass cap mkd. SC T25N R22E 1/4 S36 2001. Add the marks 2010 to the brass cap.</p> <p>From this same cor. point, the stan. cor. of secs. 35 and 36, T. 25 N., R. 22 E., bears N. 89°55' W., 11.435 chs. dist., monumented with a stainless steel post, 2 1/2 ins. diam., firmly set, projecting 4 ins. above ground with brass cap mkd. SC T25N R22E S35 S36 2001. Add the marks 2010 to the brass cap.</p> <p>Land, gently rolling. Soil, sandy clay. Vegetation, native grasses.</p> <hr/> <p style="text-align: center;">Survey of the Subdivisional Lines, T. 24 N., R. 23 E., Gila and Salt River Meridian, Arizona</p> <hr/> <p>From the cor. of secs. 1, 2, 35 and 36, on the S. bdy. of the Tp., hereinbefore described.</p> <p>N. 0°01' W., bet. secs. 35 and 36.</p> <p>Over gently rolling land.</p> <p>36.10 Top of spur ridge, 60 ft. high, bears N. 45° E. and S. 45° W.</p> <p>40.00 Point for the 1/4 sec. cor. of secs. 35 and 36.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T 24 N R 23 E 1/4 S 35 S 36 2010</p> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p> <p>46.40 Mesa rim, 80 ft. high, bears N. 60° E. and S. 60° W.</p> <p>71.20 Base of mesa rim, bears N. 50° E. and S. 50° W.</p> <p>80.00 Point for the cor. of secs. 25, 26, 35 and 36.</p>
--------	--

Survey of the Subdivisional Lines,
T. 24 N., R. 23 E., Gila and Salt River Meridian, Arizona

CHAINS	
	<p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T 24 N R 23 E S 26 S 25 S 35 S 36</p> <p style="text-align: center;">2010</p> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p> <p>Land, gently rolling to broken. Soil, sandy clay. Vegetation, native grasses.</p> <hr/> <p>From the cor. of secs. 25, 30, 31 and 36, on the E. bdy. of the Tp., monumented with a stainless steel post, 2 1/2 ins. diam., firmly set, projecting 4 ins. above ground, with brass cap mkd. T24N R23E R24E S25 S30 S36 S31 2004. Add the marks 2010 to the brass cap.</p> <p>S. 89°54' W., bet. secs. 25 and 36.</p> <p>Over gently rolling land.</p>
40.00	<p>Point for the 1/4 sec. cor. of secs. 25 and 36.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T 24 N R 23 E S 25 1/4 ——— S 36</p> <p style="text-align: center;">2010</p> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p>
80.00	<p>The cor. of secs. 25, 26, 35 and 36.</p> <p>Land, gently rolling to broken. Soil, sandy clay. Vegetation, native grasses.</p> <hr/> <p>N. 0°01' W., bet. secs. 25 and 26.</p> <p>Over gently rolling land.</p>

Survey of the Subdivisional Lines,
T. 24 N., R. 23 E., Gila and Salt River Meridian, Arizona

CHAINS	
40.00	<p>Point for the 1/4 sec. cor. of secs. 25 and 26.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T 24 N R 23 E 1/4 S 26 S 25</p> <p style="text-align: center;">2010</p> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p>
80.00	<p>Point for the cor. of secs. 23, 24, 25 and 26.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T 24 N R 23 E S 23 S 24 S 26 S 25</p> <p style="text-align: center;">2010</p> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p> <p>Land, gently rolling. Soil, sandy clay. Vegetation, native grasses.</p> <hr/> <p>From the cor. of secs. 19, 24, 25 and 30, on the E. bdy. of the Tp., monumented with a stainless steel post, 2 1/2 ins. diam., firmly set, projecting 4 ins. above ground, with brass cap mkd. T24N R23E R24E S24 S19 S25 S30 2004. Add the marks 2010 to the brass cap.</p> <p>S. 89°54' W., bet. secs. 24 and 25.</p> <p>Over gently rolling land.</p>
40.00	<p>Point for the 1/4 sec. cor. of secs. 24 and 25.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p>

Survey of the Subdivisional Lines,
T. 24 N., R. 23 E., Gila and Salt River Meridian, Arizona

CHAINS	
	T 24 N R 23 E S 24 1/4 ——— S 25 2011
	Deposit a magnet, in a white plastic case, at the base of the stainless steel post.
80.00	The cor. of secs. 23, 24, 25 and 26. Land, gently rolling to nearly level. Soil, sandy clay. Vegetation, native grasses.

	N. 0°01' W., bet. secs. 23 and 24. Over gently rolling land.
40.00	Point for the 1/4 sec. cor. of secs. 23 and 24. Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.
	T 24 N R 23 E 1/4 S 23 S 24 2010
	Deposit a magnet, in a white plastic case, at the base of the stainless steel post.
45.15	Underground gas pipeline, bears E. and W.
80.00	Point for the cor. of secs. 13, 14, 23 and 24. Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.
	T 24 N R 23 E S 14 S 13 S 23 S 24 2010
	Deposit a magnet, in a white plastic case, at the base of the stainless steel post.

Survey of the Subdivisional Lines,
T. 24 N., R. 23 E., Gila and Salt River Meridian, Arizona

CHAINS	
	<p>Land, gently rolling to nearly level. Soil, sandy clay. Vegetation, native grasses.</p> <hr/> <p>From the cor. of secs. 13, 18, 19 and 24, on the E. bdy. of the Tp., monumented with a stainless steel post, 2 1/2 ins. diam., firmly set, 16 ins. below the surface of the ground, with brass cap mkd. T24N R23E R24E S13 S18 S24 S19 2004. Add the marks 2010 to the brass cap.</p> <p>from which the 2004 reference monuments</p> <p style="padding-left: 40px;">A stainless steel post, 2 1/2 ins. diam., bears N. 60°00' E., 100.0 ft. dist., firmly set, projecting 4 ins. above ground, with brass cap mkd. RM T24N R24E S18 100.0 FT TO COR 2004 and an arrow pointing to the cor. Add the marks 2010 to the brass cap.</p> <p style="padding-left: 40px;">A stainless steel post, 2 1/2 ins. diam., bears S. 60°00' W., 100.0 ft. dist., firmly set, projecting 3 ins. above ground, with brass cap mkd. RM T24N R23E 100.0 FT TO COR S24 2004 and an arrow pointing to the cor. Add the marks 2010 to the brass cap.</p> <p>S. 89°54' W., bet. secs. 13 and 24.</p> <p>Over gently rolling land.</p>
17.70	Trail road, bears N. 65° E. and S. 65° W.
40.00	Point for the 1/4 sec. cor. of secs. 13 and 24.
	<p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T 24 N R 23 E S 13 1/4 ——— S 24</p> <p style="text-align: center;">2011</p>
	Deposit a magnet, in a white plastic case, at the base of the stainless steel post.
78.55	Trail road, bears S. 70° E. and N. 70° W.
79.40	Underground water line, bears S. 50° E. and N. 50° W.
80.00	The cor. of secs. 13, 14, 23 and 24.

Survey of the Subdivisional Lines,
T. 24 N., R. 23 E., Gila and Salt River Meridian, Arizona

CHAINS	
	<p>Land, gently rolling to nearly level. Soil, sandy clay. Vegetation, native grasses.</p> <hr/> <p>N. 0°01' W., bet. secs. 13 and 14.</p> <p>Over gently rolling land.</p>
0.60	Trail road, bears S. 70° E. and N. 70° W.
0.60	Underground water line, bears S. 50° E. and N. 50° W.
11.60	Trail road, bears N. 75° E. and S. 75° W.
40.00	<p>Point for the 1/4 sec. cor. of secs. 13 and 14.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center;"> <p>T 24 N R 23 E 1/4 S 14 S 13</p> <p>2010</p> </div> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p>
74.70	From this point, the SW cor. of a square stucco house, 37 x 37 ft., bears East, 1.27 chs. dist., the W. wall bears N. 20° E.
75.65	Trail road, bears N. 75° E. and S. 75° W.
76.45	From this point, the S. cor. of an "L" shaped brick house, bears East, 2.36 chs. dist., the SE wall bears N. 65° E.
80.00	<p>Point for the cor. of secs. 11, 12, 13 and 14.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center;"> <p>T 24 N R 23 E S 11 S 12 S 14 S 13</p> <p>2010</p> </div> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p>

Survey of the Subdivisional Lines,
T. 24 N., R. 23 E., Gila and Salt River Meridian, Arizona

CHAINS	
	<p>Land, gently rolling to nearly level. Soil, sandy clay. Vegetation, native grasses.</p> <hr/> <p>From the cor. of secs. 7, 12, 13 and 18, on the E. bdy. of the Tp., monumented with a stainless steel post, 2 1/2 ins. diam., firmly set, projecting 5 ins. above ground, with brass cap mkd. T24N R23E R24E S12 S7 S13 S18 2004.</p> <p>Add the marks 2010 to the brass cap.</p> <p>S. 89°54' W., bet. secs. 12 and 13.</p> <p>Over gently rolling land.</p>
40.00	<p>Point for the 1/4 sec. cor. of secs. 12 and 13.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center;"> <p>T 24 N R 23 E</p> <p>S 12</p> <p>1/4 ———</p> <p>S 13</p> <p>2010</p> </div> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p>
45.25	Trail road, bears N. 20° E. and S. 20° W.
49.05	BIA Route N9003, a graded road, 20 ft. wide, bears S. 30° E. and N. 30° W.
75.50	Trail road, bears N. 30° E. and S. 30° W.
80.00	<p>The cor. of secs. 11, 12, 13 and 14.</p> <p>Land, gently rolling to nearly level. Soil, sandy clay. Vegetation, native grasses.</p> <hr/> <p>N. 0°01' W., bet. secs. 11 and 12.</p> <p>Over gently rolling land.</p>
0.45	BIA Route N15B, a graded road, 20 ft. wide, bears N. 45° E. and S. 45° W.
12.85	Power line, 2 strand, bears N. 10° E. and S. 10° W.

Survey of the Subdivisional Lines,
T. 24 N., R. 23 E., Gila and Salt River Meridian, Arizona

CHAINS

40.00

Point for the 1/4 sec. cor. of secs. 11 and 12.

Set a magnet, in a white plastic case, 18 ins. below the surface of the ground.

from which

A stainless steel post, 28 ins. long, 2 1/2 ins. diam., set 24 ins. in the ground for a reference monument, bears S. 45°00' E., 66.0 ft. dist. with brass cap mkd. RM T24N R23E 1/4 S12 66.0 FT TO COR 2010 and an arrow pointing to the cor. Deposit a magnet, in a white plastic case, at the base of the stainless steel post.

A stainless steel post, 28 ins. long, 2 1/2 ins. diam., set 24 ins. in the ground for a reference monument, bears N. 45°00' W., 132.0 ft. dist. with brass cap mkd. RM T24N R23E 1/4 S11 132.0 FT TO COR 2010 and an arrow pointing to the cor. Deposit a magnet, in a white plastic case, at the base of the stainless steel post.

The 1/4 sec. cor. is located against the E. bank of the Pueblo Colorado Wash, 5 ft. high, bears N. 65° E. and S. 65° W.

40.30

Pueblo Colorado Wash, 40 ft. wide, 5 ft. deep, drains S. 65° W.

80.00

Point for the cor. of secs. 1, 2, 11 and 12.

Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.

T 24 N	R 23 E
S 2	S 1
S 11	S 12

2010

Deposit a magnet, in a white plastic case, at the base of the stainless steel post.

Land, gently rolling to nearly level.

Soil, sandy clay.

Vegetation, native grasses.

From the cor. of secs. 1, 6, 7 and 12, on the E. bdy. of the Tp., monumented with a stainless steel post, 2 1/2 ins. diam., firmly set, projecting 4 ins. above ground, with brass cap mkd. T24N R23E R24E S1 S6 S12 S7 2004.

Add the marks 2010 to the brass cap.

S. 89°54' W., bet. secs. 1 and 12.

Survey of the Subdivisional Lines,
T. 24 N., R. 23 E., Gila and Salt River Meridian, Arizona

CHAINS	
	Over gently rolling land.
6.50	BIA Route N15B, a graded road, 30 ft. wide, bears N. 30° E. and S. 30° W.
8.90	Trail road, bears N. and S.
40.00	Point for the 1/4 sec. cor. of secs. 1 and 12.
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.
	<p style="text-align: center;">T 24 N R 23 E S 1 1/4 ——— S 12</p>
	<p style="text-align: center;">2010</p>
	Deposit a magnet, in a white plastic case, at the base of the stainless steel post.
80.00	The cor. of secs. 1, 2, 11 and 12.
	Land, gently rolling to nearly level.
	Soil, sandy clay.
	Vegetation, native grasses.
	<hr/> N. 0°01' W., bet. secs. 1 and 2.
	Over gently rolling land.
33.05	Trail road, bears S. 80° E. and N. 80° W.
40.00	Point for the 1/4 sec. cor. of secs. 1 and 2.
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.
	<p style="text-align: center;">T 24 N R 23 E 1/4 S 2 S 1</p>
	<p style="text-align: center;">2011</p>
	Deposit a magnet, in a white plastic case, at the base of the stainless steel post.
55.00	BIA Route N157, a graded road, 30 ft. wide, bears N. 20° E. and S. 20° W.

Survey of the Subdivisional Lines,
T. 24 N., R. 23 E., Gila and Salt River Meridian, Arizona

CHAINS

78.00

Point for the closing cor. of secs. 1 and 2, at intersection with the Sixth Standard Parallel North, the N. bdy. of the Tp.

Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.

$$\begin{array}{r} T\ 25\ N\ R\ 23\ E \\ \quad S\ 35 \\ \hline S\ 2\ | \ S\ 1 \\ T\ 24\ N\ R\ 23\ E \\ \quad CC \end{array}$$

2011

Deposit a magnet, in a white plastic case, at the base of the stainless steel post.

From this cor. point, the stan. 1/4 sec. cor. of sec. 35, T. 25 N., R. 23 E., bears S. 89°55' E., 34.37 chs. dist., hereinbefore described.

From this same cor. point, the stan. cor. of secs. 34 and 35, T. 25 N., R. 23 E., bears N. 89°55' W., 5.80 chs. dist., hereinbefore described.

Land, gently rolling to rolling.
Soil, sandy clay.
Vegetation, native grasses.

Point for the 1/4 sec. cor. of sec. 1 only, at midpoint on the N. bdy. of sec. 1.

Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.

$$\begin{array}{r} T\ 25\ N\ R\ 23\ E \\ \hline 1/4\ S\ 1 \\ T\ 24\ N\ R\ 23\ E \end{array}$$

2011

Deposit a magnet, in a white plastic case, at the base of the stainless steel post.

From this cor. point, the stan. cor. of secs. 35 and 36, T. 25 N., R. 23 E., bears S. 89°55' E., 34.54 chs. dist., monumented with only a memorial; a magnet, in a white plastic case, set 16 ins. below the surface of the ground.

There is no remaining evidence of the orig. stainless steel post.

Survey of the Subdivisional Lines,
T. 24 N., R. 23 E., Gila and Salt River Meridian, Arizona

CHAINS	
	<p>At the corner point</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">SC T 25 N R 23 E S 35 S 36</p> <p style="text-align: center;">2010</p> <p>Redeposit the magnet, in a white plastic case, at the base of the stainless steel post.</p> <p>From this same cor. point, the closing cor. of Tps. 24 N., Rs. 23 and 24 E., bears S. 89°55' E., 40.00 chs. dist., monumented with a stainless steel post, 2 1/2 ins. diam., firmly set, projecting 5 ins. above ground, with brass cap mkd. T25N R23E S36 S1 S6 R23E R24E T24N CC 2004. Add the marks 2010 to the brass cap.</p> <p>From this same cor. point, the stan. 1/4 sec. cor. of sec. 35, T. 25 N., R. 23 E., bears N. 89°55' W., 5.63 chs. dist., hereinbefore described.</p> <hr/> <p>From the cor. of secs. 2, 3, 34 and 35, on the S. bdy. of the Tp., hereinbefore described.</p> <p>N. 0°01' W., bet. secs. 34 and 35.</p> <p>Over rolling land.</p>
40.00	<p>Point for the 1/4 sec. cor. of secs. 34 and 35.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T 24 N R 23 E 1/4 S 34 S 35</p> <p style="text-align: center;">2010</p> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p>
80.00	<p>Point for the cor. of secs. 26, 27, 34 and 35.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p>

Survey of the Subdivisional Lines,
T. 24 N., R. 23 E., Gila and Salt River Meridian, Arizona

CHAINS									
	<table style="margin: auto;"> <tr> <td>T 24 N</td> <td>R 23 E</td> </tr> <tr> <td style="border-right: 1px solid black;">S 27</td> <td>S 26</td> </tr> <tr> <td style="border-right: 1px solid black;">S 34</td> <td>S 35</td> </tr> </table>	T 24 N	R 23 E	S 27	S 26	S 34	S 35		
T 24 N	R 23 E								
S 27	S 26								
S 34	S 35								
	2010								
	Deposit a magnet, in a white plastic case, at the base of the stainless steel post.								
	Land, rolling to gently rolling. Soil, sandy clay. Vegetation, native grasses.								
	<hr/>								
	From the cor. of secs. 25, 26, 35 and 36.								
	S. 89°54' W., bet. secs. 26 and 35.								
	Over gently rolling land.								
40.00	Point for the 1/4 sec. cor. of secs. 26 and 35.								
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.								
	<table style="margin: auto;"> <tr> <td>T 24 N</td> <td>R 23 E</td> </tr> <tr> <td></td> <td>S 26</td> </tr> <tr> <td></td> <td style="border-top: 1px solid black;">1/4</td> </tr> <tr> <td></td> <td>S 35</td> </tr> </table>	T 24 N	R 23 E		S 26		1/4		S 35
T 24 N	R 23 E								
	S 26								
	1/4								
	S 35								
	2010								
	Deposit a magnet, in a white plastic case, at the base of the stainless steel post.								
80.00	The cor. of secs. 26, 27, 34 and 35.								
	Land, gently rolling to nearly level. Soil, sandy clay. Vegetation, native grasses.								
	<hr/>								
	N. 0°01' W., bet. secs. 26 and 27.								
	Over gently rolling land.								
12.25	Barbed wire fence, 6 strand, bears S. 70° E. and N. 70° W.								
40.00	Point for the 1/4 sec. cor. of secs. 26 and 27.								
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.								

Survey of the Subdivisional Lines,
T. 24 N., R. 23 E., Gila and Salt River Meridian, Arizona

CHAINS	
	T 24 N R 23 E 1/4 S 27 S 26 2010 Deposit a magnet, in a white plastic case, at the base of the stainless steel post.
80.00	Point for the cor. of secs. 22, 23, 26 and 27. Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd. <div style="text-align: center;"> T 24 N R 23 E S 22 S 23 S 27 S 26 2010 </div> Deposit a magnet, in a white plastic case, at the base of the stainless steel post. Land, gently rolling. Soil, sandy clay. Vegetation, native grasses.
	<hr/> From the cor. of secs. 23, 24, 25 and 26. S. 89°54' W., bet. secs. 23 and 26. Over gently rolling land.
40.00	Point for the 1/4 sec. cor. of secs. 23 and 26. Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd. <div style="text-align: center;"> T 24 N R 23 E S 23 1/4 ——— S 26 2010 </div> Deposit a magnet, in a white plastic case, at the base of the stainless steel post.
55.00	Barbed wire fence, 4 strand, bears N. and S.
79.85	Barbed wire fence, 4 strand, bears S. 40° E. and N. 40° W.

Survey of the Subdivisional Lines,
T. 24 N., R. 23 E., Gila and Salt River Meridian, Arizona

CHAINS	
80.00	<p>The cor. of secs. 22, 23, 26 and 27.</p> <p>Land, gently rolling to nearly level. Soil, sandy clay. Vegetation, native grasses.</p> <hr/> <p>N. 0°01' W., bet. secs. 22 and 23.</p> <p>Over gently rolling land.</p>
0.20	Barbed wire fence, 4 strand, bears S. 40° E. and N. 40° W.
35.80	Barbed wire fence, 4 strand, bears S. 75° E. and N. 75° W.
40.00	<p>Point for the 1/4 sec. cor. of secs. 22 and 23.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center;"> <p>T 24 N R 23 E 1/4 S 22 S 23</p> <p>2010</p> </div> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p>
47.20	Underground gas pipeline, bears E. and W.
80.00	<p>Point for the cor. of secs. 14, 15, 22 and 23.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center;"> <p>T 24 N R 23 E S 15 S 14 S 22 S 23</p> <p>2010</p> </div> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p> <p>Land, gently rolling to nearly level. Soil, sandy clay. Vegetation, native grasses.</p> <hr/> <p>From the cor. of secs. 13, 14, 23 and 24.</p> <p>S. 89°54' W., bet. secs. 14 and 23.</p>

Survey of the Subdivisional Lines,
T. 24 N., R. 23 E., Gila and Salt River Meridian, Arizona

CHAINS	
	Over gently rolling land.
0.30	Trail road, bears N. 25° E. and S. 25° W.
27.30	Trail road, bears N. 10° E. and S. 10° W.
40.00	Point for the 1/4 sec. cor. of secs. 14 and 23. Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd. <div style="text-align: center;"> T 24 N R 23 E S 14 1/4 ——— S 23 2010 </div>
	Deposit a magnet, in a white plastic case, at the base of the stainless steel post.
80.00	The cor. of secs. 14, 15, 22 and 23. Land, gently rolling to nearly level. Soil, sandy clay. Vegetation, native grasses.
	<hr/> N. 0°01' W., bet. secs. 14 and 15. Over gently rolling land.
10.80	Pueblo Colorado Wash, 50 ft. wide, 5 ft. deep, drains S. 80° W.
37.80	BIA Route N157, a graded road, 30 ft. wide, bears N. 25° E. and S. 25° W.
39.50	Underground telephone line, bears N. 25° E. and S. 25° W.
40.00	Point for the 1/4 sec. cor. of secs. 14 and 15. Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd. <div style="text-align: center;"> T 24 N R 23 E 1/4 S 15 S 14 2010 </div>
	Deposit a magnet, in a white plastic case, at the base of the stainless steel post.

Survey of the Subdivisional Lines,
T. 24 N., R. 23 E., Gila and Salt River Meridian, Arizona

CHAINS									
40.80	Trail road, bears N. 60° E. and S. 60° W.								
60.65	Trail road, bears N. 75° E. and S. 75° W.								
76.85	Trail road, bears N. 75° E. and S. 75° W.								
80.00	<p>Point for the cor. of secs. 10, 11, 14 and 15.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center; margin: 10px 0;"> <table style="margin: auto; border-collapse: collapse;"> <tr> <td style="padding: 0 10px;">T 24 N</td> <td style="padding: 0 10px;">R 23 E</td> </tr> <tr> <td style="border-right: 1px solid black; padding: 0 5px;">S 10</td> <td style="padding: 0 5px;">S 11</td> </tr> <tr> <td style="border-right: 1px solid black; padding: 0 5px;">S 15</td> <td style="padding: 0 5px;">S 14</td> </tr> </table> <p style="margin: 5px 0;">2010</p> </div> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p> <p>Land, gently rolling to nearly level. Soil, sandy clay. Vegetation, native grasses and greasewood.</p> <hr style="width: 50%; margin: 10px auto;"/> <p>From the cor. of secs. 11, 12, 13 and 14.</p> <p>S. 89°54' W., bet. secs. 11 and 14.</p> <p>Over gently rolling land.</p>	T 24 N	R 23 E	S 10	S 11	S 15	S 14		
T 24 N	R 23 E								
S 10	S 11								
S 15	S 14								
16.25	Power line, 2 strand, bears N. 60° E. and S. 60° W.								
35.90	Pueblo Colorado Wash, 100 ft. wide, 5 ft. deep, drains S. 70° W.								
39.65	From this point, the pump shaft of a windmill, firmly set in a concrete pad 12 x 12 ft., bears North, 1.87 chs. dist. With a livestock tank alongside, 30 ft. diam., identified as 17-M-340.								
40.00	<p>Point for the 1/4 sec. cor. of secs. 11 and 14.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center; margin: 10px 0;"> <table style="margin: auto; border-collapse: collapse;"> <tr> <td style="padding: 0 10px;">T 24 N</td> <td style="padding: 0 10px;">R 23 E</td> </tr> <tr> <td style="padding: 0 10px;"></td> <td style="padding: 0 10px;">S 11</td> </tr> <tr> <td style="padding: 0 10px;">1/4</td> <td style="padding: 0 10px;">—</td> </tr> <tr> <td style="padding: 0 10px;"></td> <td style="padding: 0 10px;">S 14</td> </tr> </table> <p style="margin: 5px 0;">2010</p> </div> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p>	T 24 N	R 23 E		S 11	1/4	—		S 14
T 24 N	R 23 E								
	S 11								
1/4	—								
	S 14								

Survey of the Subdivisional Lines,
T. 24 N., R. 23 E., Gila and Salt River Meridian, Arizona

CHAINS	
	From this cor. point, the pump shaft of a windmill, hereinbefore described, bears N. 10°23' E., 1.90 chs. dist.
42.60	Trail road, bears S. 35° E. and N. 35° W.
55.90	From this point, the SE cor. of a brick house, 15 x 35 ft., bears North, 1.17 chs. dist., the short side bears N. 75° W.
56.85	Power line, 2 strand, bears N. 20° E. and S. 20° W.
56.90	From this point, the NW cor. of a house, 25 x 40 ft., bears South, 1.09 chs. dist., the short side bears S. 65° E.
58.50	From this point, the NE cor. of a brick house, 20 x 50 ft., bears South, 1.53 chs. dist., the short side bears N. 75° W.
59.55	BIA Route N157, a graded road, 30 ft. wide, bears N. 35° E. and S. 35° W.
60.00	Underground telephone line, bears N. 35° E. and S. 35° W.
60.30	Underground water line, bears N. 35° E. and S. 35° W.
69.90	Graded road, 30 ft. wide, bears S. 25° E. and N. 25° W.
74.60	Trail road, bears N. 60° E. and S. 60° W.
80.00	The cor. of secs. 10, 11, 14 and 15. Land, gently rolling to rolling. Soil, sandy clay. Vegetation, native grasses, greasewood and cottonwood.

	N. 0°01' W., bet. secs. 10 and 11. Over rolling land.
40.00	Point for the 1/4 sec. cor. of secs. 10 and 11. Point falls in a graded road, 40 ft. wide, bears S. 15° E. and N. 15° W. Drive a nail, 6 ins. long, to 2 ins. below surface of graded road. from which A stainless steel post, 28 ins. long, 2 1/2 ins. diam., set 24 ins. in the ground for a reference monument, bears N. 45°00' E., 100.0 ft. dist. with brass cap mkd. RM T24N R23E 1/4 S11 100.0 FT TO COR 2010 and an arrow pointing to the cor. Deposit a magnet, in a white plastic case, at the base of the stainless steel post.

Survey of the Subdivisional Lines,
T. 24 N., R. 23 E., Gila and Salt River Meridian, Arizona

CHAINS							
	A stainless steel post, 28 ins. long, 2 1/2 ins. diam., set 24 ins. in the ground for a reference monument, bears S. 45°00' W., 50.0 ft. dist. with brass cap mkd. RM T24N R23E 1/4 S10 50.0 FT TO COR 2010 and an arrow pointing to the cor. Deposit a magnet, in a white plastic case, at the base of the stainless steel post.						
41.05	Graded road, 40 ft. wide, bears S. 15° E. and N. 15° W.						
60.25	Power line, 4 strand, bears N. 50° E. and S. 50° W.						
62.65	BIA Route N153, a graded road, 20 ft. wide, bears N. 50° E. and S. 50° W.						
80.00	Point for the cor. of secs. 2, 3, 10 and 11. Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.						
	<table style="margin-left: auto; margin-right: auto;"> <tr> <td>T 24 N</td> <td>R 23 E</td> </tr> <tr> <td style="border-right: 1px solid black;">S 3</td> <td>S 2</td> </tr> <tr> <td style="border-right: 1px solid black;">S 10</td> <td>S 11</td> </tr> </table>	T 24 N	R 23 E	S 3	S 2	S 10	S 11
T 24 N	R 23 E						
S 3	S 2						
S 10	S 11						
	2010						
	Deposit a magnet, in a white plastic case, at the base of the stainless steel post.						
	Land, gently rolling. Soil, sandy clay. Vegetation, native grasses.						
	From the cor. of secs. 1, 2, 11 and 12. S. 89°54' W., bet. secs. 2 and 11. Over rolling land.						
8.25	Trail road, bears N. 15° E. and S. 15° W.						
9.65	Trail road, bears S. 50° E. and N. 50° W.						
25.50	BIA Route 157, a graded road, 40 ft. wide, bears N. 25° E. and S. 25° W.						
26.70	Underground telephone line, bears N. 20° E. and S. 20° W.						
36.00	Power line, 3 strand, bears N. 15° E. and S. 15° W.						
40.00	Point for the 1/4 sec. cor. of secs. 2 and 11.						

Survey of the Subdivisional Lines,
T. 24 N., R. 23 E., Gila and Salt River Meridian, Arizona

CHAINS	
	<p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T 24 N R 23 E S 2 1/4 ——— S 11</p> <p style="text-align: center;">2010</p> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p>
43.20	Underground water line, bears N. 30° E. and S. 30° W.
44.55	A graded road, 20 ft. wide, bears N. 25° E. and S. 25° W.
48.25	From this point, the N. cor. of a house, 44 x 44 ft., bears South, 1.67 chs. dist., walls extend S. 60° E. and S. 30° W.
57.60	Power line, 4 strand, bears N. 50° E. and S. 50° W.
60.05	BIA Route N153, a graded road, 50 ft. wide, bears N. 45° E. and S. 45° W.
80.00	<p>The cor. of secs. 2, 3, 10 and 11.</p> <p>Land, rolling. Soil, sandy clay. Vegetation, native grasses, greasewood and cottonwood.</p> <hr/> <p>N. 0°01' W., bet. secs. 2 and 3.</p> <p>Over rolling land.</p>
40.00	<p>Point for the 1/4 sec. cor. of secs. 2 and 3.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T 24 N R 23 E 1/4 S 3 S 2</p> <p style="text-align: center;">2010</p> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p>
40.40	Trail road, bears S. 35° E. and N. 35° W.
59.75	Trail road, bears N. 70° E. and S. 70° W.

Survey of the Subdivisional Lines,
T. 24 N., R. 23 E., Gila and Salt River Meridian, Arizona

CHAINS	
	<p>From this same cor. point, the stan. 1/4 cor. of sec. 34, T. 25 N., R. 23 E., bears N. 89°55' W., 5.97 chs. dist., hereinbefore described.</p> <hr/> <p>From the cor. of secs. 3, 4, 33 and 34, on the S. bdy. of the Tp., hereinbefore described.</p> <p>N. 0°02' W., bet. secs. 33 and 34.</p> <p>Over gently rolling land.</p>
20.55	Barbed wire fence, 5 strand, bears N. 15° E. and S. 15° W.
40.00	<p>Point for the 1/4 sec. cor. of secs. 33 and 34.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center;"> <p>T 24 N R 23 E 1/4 S 33 S 34</p> <p>2011</p> </div> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p>
80.00	<p>Point for the cor. of secs. 27, 28, 33 and 34.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center;"> <p>T 24 N R 23 E S 28 S 27 S 33 S 34</p> <p>2011</p> </div> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p> <p>Set a steel fence post nearby.</p> <p>Land, gently rolling. Soil, sandy clay. Vegetation, native grasses.</p> <hr/> <p>From the cor. of secs. 26, 27, 34 and 35.</p> <p>S. 89°54' W., bet. secs. 27 and 34.</p>

Survey of the Subdivisional Lines,
T. 24 N., R. 23 E., Gila and Salt River Meridian, Arizona

CHAINS	
	Over gently rolling land.
40.00	Point for the 1/4 sec. cor. of secs. 27 and 34. Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd. <div style="text-align: center;"> T 24 N R 23 E S 27 1/4 ——— S 34 2011 </div>
	Deposit a magnet, in a white plastic case, at the base of the stainless steel post.
69.15	Pueblo Colorado Wash, 25 ft. wide, 5 ft. deep, drains S. 45° W.
80.00	The cor. of secs. 27, 28, 33 and 34. Land, gently rolling. Soil, sandy clay. Vegetation, native grasses.
	----- N. 0°02' W., bet. secs. 27 and 28. Over rolling land.
3.45	Barbed wire fence, bears N. 15° E. and S. 15° W.
6.60	BIA Route N157, a graded road, 40 ft. wide, bears N. 20° E. and S. 20° W.
8.40	Trail road, bears N. 30° E. and S. 30° W.
8.45	Power line, 2 strand, bears N. 15° E. and S. 15° W.
40.00	Point for the 1/4 sec. cor. of secs. 27 and 28. Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd. <div style="text-align: center;"> T 24 N R 23 E 1/4 S 28 S 27 2011 </div>
	Deposit a magnet, in a white plastic case, at the base of the stainless steel post.

**Survey of the Subdivisional Lines,
T. 24 N., R. 23 E., Gila and Salt River Meridian, Arizona**

CHAINS									
59.45	A graded road, 30 ft. wide, bears N. 15° E. and S. 15° W.								
79.35	Trail road, bears N. 60° E. and S. 60° W.								
80.00	Point for the cor. of secs. 21, 22, 27 and 28. Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., flush with the surface of the ground, with brass cap mkd.								
	<table style="margin-left: auto; margin-right: auto;"> <tr> <td>T 24 N</td> <td>R 23 E</td> </tr> <tr> <td>S 21</td> <td>S 22</td> </tr> <tr> <td>S 28</td> <td>S 27</td> </tr> </table>	T 24 N	R 23 E	S 21	S 22	S 28	S 27		
T 24 N	R 23 E								
S 21	S 22								
S 28	S 27								
	2011								
	Deposit a magnet, in a white plastic case, at the base of the stainless steel post.								
	Set a steel fence post nearby.								
	Cor. is located in the center of a trail road, bears S. 20° E. and N. 20° W.								
	Land, rolling to gently rolling. Soil, sandy clay. Vegetation, native grasses and greasewood.								
	<hr/>								
	From the cor. of secs. 22, 23, 26 and 27.								
	S. 89°54' W., bet. secs. 22 and 27.								
	Over gently rolling land.								
30.25	Pueblo Colorado Wash, 15 ft. wide, 5 ft. deep, drains S.								
40.00	Point for the 1/4sec. cor. of secs. 22 and 27. Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.								
	<table style="margin-left: auto; margin-right: auto;"> <tr> <td>T 24 N</td> <td>R 23 E</td> </tr> <tr> <td></td> <td>S 22</td> </tr> <tr> <td>1/4</td> <td>—</td> </tr> <tr> <td></td> <td>S 27</td> </tr> </table>	T 24 N	R 23 E		S 22	1/4	—		S 27
T 24 N	R 23 E								
	S 22								
1/4	—								
	S 27								
	2011								
	Deposit a magnet, in a white plastic case, at the base of the stainless steel post.								
57.00	BIA Route N157, a graded road, 40 ft. wide, bears N. 20° E. and S. 20° W.								

Survey of the Subdivisional Lines,
T. 24 N., R. 23 E., Gila and Salt River Meridian, Arizona

CHAINS	
57.90	Underground telephone line, bears N. 25° E. and S. 25° W.
58.05	Power line, 2 strand, bears N. 30° E. and S. 30° W.
59.50	From this point, the NE cor. of a brick house, 25 x 40 ft., bears South, 1.92 chs. dist., long side bears S. 15° W.
60.05	From this point, the NE cor. of a brick house, 33 x 35 ft., bears South, 1.82 chs. dist., the short side bears N. 75° W.
62.00	From this point, the S. cor. of a brick house, 20 x 32 ft., bears North, 1.30 chs. dist., the long side bears N. 15° E.
62.95	From this point, the NE cor. of a stucco house, 25 x 35 ft., bears South, 0.55 chs. dist., the short side bears N. 70° W.
64.00	From this point, the S. cor. of a brick house, 20 x 35 ft., bears North, 0.40 chs. dist., the long side bears N. 20° E.
73.85	A graded road, 30 ft. wide, bears N. 15° E. and S. 15° W.
78.70	Trail road, bears N. 55° E. and S. 55° W.
80.00	The cor. of secs. 21, 22, 27 and 28. Land, gently rolling to rolling. Soil, sandy clay. Vegetation, native grasses and greasewood.
	N. 0°02' W., bet. secs. 21 and 22. Over gently rolling land.
40.00	Point for the 1/4 sec. cor. of secs. 21 and 22. Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd. T 24 N R 23 E 1/4 S 21 S 22 2011 Deposit a magnet, in a white plastic case, at the base of the stainless steel post.
56.25	Underground gas pipeline and trail road, bears S. 75° E. and N. 75° W.
77.95	Trail road, bears N. 75° E. and S. 75° W.

Survey of the Subdivisional Lines,
T. 24 N., R. 23 E., Gila and Salt River Meridian, Arizona

CHAINS									
80.00	<p>Point for the cor. of secs. 15, 16, 21 and 22.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center;"> <table style="margin: auto;"> <tr> <td>T 24 N</td> <td>R 23 E</td> </tr> <tr> <td style="border-right: 1px solid black;">S 16</td> <td>S 15</td> </tr> <tr> <td style="border-right: 1px solid black;">S 21</td> <td>S 22</td> </tr> </table> <p>2011</p> </div> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p> <p>Land, rolling to gently rolling. Soil, sandy clay. Vegetation, native grasses and greasewood.</p> <hr/> <p>From the cor. of secs. 14, 15, 22 and 23.</p> <p>S. 89°54' W., bet. secs. 15 and 22.</p> <p>Over gently rolling land.</p>	T 24 N	R 23 E	S 16	S 15	S 21	S 22		
T 24 N	R 23 E								
S 16	S 15								
S 21	S 22								
21.00	BIA Route N157, a graded road, 30 ft. wide, bears N. 20° E. and S. 20° W.								
40.00	<p>Point for the 1/4 sec. cor. of secs. 15 and 22.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center;"> <table style="margin: auto;"> <tr> <td>T 24 N</td> <td>R 23 E</td> </tr> <tr> <td></td> <td>S 15</td> </tr> <tr> <td>1/4</td> <td style="border-top: 1px solid black;">———</td> </tr> <tr> <td></td> <td>S 22</td> </tr> </table> <p>2011</p> </div> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p> <p>Set a steel fence post nearby.</p>	T 24 N	R 23 E		S 15	1/4	———		S 22
T 24 N	R 23 E								
	S 15								
1/4	———								
	S 22								
40.15	Underground water line, bears N. 20° E. and S. 20° W.								
41.05	A graded road, 30 ft. wide, bears N. 20° E. and S. 20° W.								
71.75	Trail road, bears N. 75° E. and S. 75° W.								
77.65	Trail road, bears N. 40° E. and S. 40° W.								

Survey of the Subdivisional Lines,
T. 24 N., R. 23 E., Gila and Salt River Meridian, Arizona

CHAINS	
80.00	<p>The cor. of secs. 15, 16, 21 and 22.</p> <p>Land, gently rolling to rolling. Soil, sandy clay. Vegetation, native grasses and greasewood.</p> <hr/> <p>N. 0°02' W., bet. secs. 15 and 16.</p> <p>Over gently rolling land.</p>
39.70	Trail road, bears S. 50° E. and N. 50° W.
40.00	<p>Point for the 1/4 sec. cor. of secs. 15 and 16.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T 24 N R 23 E 1/4 S 16 S 15</p> <p style="text-align: center;">2011</p> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p>
69.90	Power line, 4 strand, bears N. 50° E. and S. 50° W.
73.05	BIA Route N153, a graded road, 30 ft. wide, bears N. 50° E. and S. 50° W.
80.00	<p>Point for the cor. of secs. 9, 10, 15 and 16.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T 24 N R 23 E S 9 S 10 S 16 S 15</p> <p style="text-align: center;">2011</p> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p> <p>Land, gently rolling to nearly level. Soil, sandy clay. Vegetation, native grasses.</p> <hr/> <p>From the cor. of secs. 10, 11, 14 and 15.</p>

Survey of the Subdivisional Lines,
T. 24 N., R. 23 E., Gila and Salt River Meridian, Arizona

CHAINS	
	S. 89°54' W., bet. secs. 10 and 15. Over gently rolling land.
5.90	A graded road, 30 ft. wide, bears N. 25° E. and S. 25° W.
40.00	Point for the 1/4 sec. cor. of secs. 10 and 15. Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.
	T 24 N R 23 E S 10 1/4 ——— S 15 2011
	Deposit a magnet, in a white plastic case, at the base of the stainless steel post.
68.55	Power line, 4 strand, bears N. 45° E. and S. 45° W.
72.00	BIA Route N153, a graded road, 30 ft. wide, bears N. 50° E. and S. 50° W.
80.00	The cor. of secs. 9, 10, 15 and 16. Land, gently rolling to nearly level. Soil, sandy clay. Vegetation, native grasses.
	N. 0°02' W., bet. secs. 9 and 10. Over gently rolling land.
40.00	Point for the 1/4 sec. cor. of secs. 9 and 10. Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.
	T 24 N R 23 E 1/4 S 9 S 10 2011
	Deposit a magnet, in a white plastic case, at the base of the stainless steel post.
80.00	Point for the cor. of secs. 3, 4, 9 and 10.

Survey of the Subdivisional Lines,
T. 24 N., R. 23 E., Gila and Salt River Meridian, Arizona

CHAINS	
	<p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T 24 N R 23 E S 4 S 3 S 9 S 10</p> <p style="text-align: center;">2011</p> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p> <p>Land, gently rolling to nearly level. Soil, sandy clay. Vegetation, native grasses.</p> <hr/> <p>From the cor. of secs. 2, 3, 10 and 11.</p> <p>S. 89°54' W., bet. secs. 3 and 10.</p> <p>Over gently rolling land.</p>
40.00	<p>Point for the 1/4 sec. cor. of secs. 3 and 10.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T 24 N R 23 E S 3 1/4 ——— S 10</p> <p style="text-align: center;">2011</p> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p>
80.00	<p>The cor. of secs. 3, 4, 9 and 10.</p> <p>Land, gently rolling. Soil, sandy clay. Vegetation, native grasses.</p> <hr/> <p>N. 0°02' W., bet. secs. 3 and 4.</p> <p>Over gently rolling land.</p>
40.00	<p>Point for the 1/4 sec. cor. of secs. 3 and 4.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p>

Survey of the Subdivisional Lines,
T. 24 N., R. 23 E., Gila and Salt River Meridian, Arizona

CHAINS	
	T 24 N R 23 E 1/4 S 4 S 3 2011
	Deposit a magnet, in a white plastic case, at the base of the stainless steel post.
59.60	S. right-of-way fence of BIA Route 15, barbed wire, 5 strand, parallels highway.
60.80	BIA Route 15, an asphalt road, 36 ft. wide, bears N. 65° E. and S. 65° W.
62.00	N. right-of-way fence of BIA Route 15, barbed wire, 5 strand, parallels highway.
78.53	Point for the closing cor. of secs. 3 and 4, at intersection with the Sixth Standard Parallel North, the N. bdy. of the Tp.
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.
	T 25 N R 23 E S 33 ----- S 4 S 3 T 24 N R 23 E CC 2011
	Deposit a magnet, in a white plastic case, at the base of the stainless steel post.
	From this cor. point, the stan. 1/4 sec. cor. of sec. 33, T. 25 N., R. 23 E., bears S. 89°55' E., 33.69 chs. dist., monumented with a stainless steel post, 2 1/2 ins. diam., firmly set, projecting 8 ins. above ground, with brass cap mkd. SC T25N R23E 1/4 S33 2001. Add the marks 2010 to the brass cap.
	From this same cor. point, the stan. cor. of secs. 32 and 33, T. 25 N., R. 23 E., bears N. 89°55' W., 6.48 chs. dist., monumented with a stainless steel post, 2 1/2 ins. diam., firmly set, projecting 4 ins. above ground, with brass cap mkd. SC T25N R23E S32 S33 2001. Add the marks 2010 to the brass cap.
	Land, gently rolling to rolling. Soil, sandy clay. Vegetation, native grasses.

Survey of the Subdivisional Lines,
T. 24 N., R. 23 E., Gila and Salt River Meridian, Arizona

CHAINS

Point for the 1/4 sec. cor. of sec. 3 only, at midpoint on the N. bdy. of sec. 3.

Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., flush with the surface of the ground, with brass cap mkd.

T 25 N R 23 E

1/4 S 3

T 24 N R 23 E

2011

Deposit a magnet, in a white plastic case, at the base of the stainless steel post.

from which

A stainless steel post, 28 ins. long, 2 1/2 ins. diam., set 24 ins. in the ground for a reference monument, bears S. 10°00' E., 130.0 ft. dist. with brass cap mkd. RM T24N R23E 1/4 S3 130.0 FT TO COR 2011 and an arrow pointing to the cor. Deposit a magnet, in a white plastic case, at the base of the stainless steel post.

A stainless steel post, 28 ins. long, 2 1/2 ins. diam., set 24 ins. in the ground for a reference monument, bears S. 80°00' W., 120.0 ft. dist. with brass cap mkd. RM T24N R23E 1/4 S3 120.0 FT TO COR 2011 and an arrow pointing to the cor. Deposit a magnet, in a white plastic case, at the base of the stainless steel post.

Cor. is located in the right-of-way of BIA Route 15, N. of asphalt surface, 48 lks. dist.

From this cor. point, the stan. cor. of secs. 33 and 34, T. 25 N., R. 23 E., bears S. 89°55' E., 33.86 chs. dist., hereinbefore described.

From this same cor. point, the stan. 1/4 sec. cor. of sec. 33, T. 25 N., R. 23 E., bears N. 89°55' W., 6.31 chs. dist., hereinbefore described.

From the cor. of secs. 4, 5, 32 and 33, on the S. bdy. of the Tp., hereinbefore described.

N. 0°02' W., bet. secs. 32 and 33.

Over gently rolling land.

0.40

Power line, 2 strand, bears S. 35° E. and N. 35° W.

Survey of the Subdivisional Lines,
T. 24 N., R. 23 E., Gila and Salt River Meridian, Arizona

CHAINS	
3.40	Trail road, bears S. 45° E. and N. 45° W.
32.15	Trail road, bears N. 80° E. and S. 80° W.
36.40	Trail road, bears N. 60° E. and S. 60° W.
40.00	Point for the 1/4 sec. cor. of secs. 32 and 33. Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd. <div style="text-align: center;"> T 24 N R 23 E 1/4 S 32 S 33 2011 </div> Deposit a magnet, in a white plastic case, at the base of the stainless steel post.
80.00	Point for the cor. of secs. 28, 29, 32 and 33. Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd. <div style="text-align: center;"> T 24 N R 23 E S 29 S 28 S 32 S 33 2011 </div> Deposit a magnet, in a white plastic case, at the base of the stainless steel post. Land, gently rolling to nearly level. Soil, sandy clay. Vegetation, native grasses. <hr/>
	From the cor. of secs. 27, 28, 33 and 34. S. 89°54' W., bet. secs. 28 and 33. Over rolling land.
2.05	BIA Route N157, a graded road, 30 ft. wide, bears N. 15° E. and S. 15° W.
22.00	A graded road, 20 ft. wide, bears N. 25° E. and S. 25° W.
40.00	Point for the 1/4 sec. cor. of secs. 28 and 33.

Survey of the Subdivisional Lines,
T. 24 N., R. 23 E., Gila and Salt River Meridian, Arizona

CHAINS	
	<p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T 24 N R 23 E S 28 1/4 ——— S 33</p> <p style="text-align: center;">2011</p> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p>
50.05	Trail road, bears S. 65° E. and N. 65° W.
80.00	<p>The cor. of secs. 28, 29, 32 and 33.</p> <p>Land, rolling to nearly level. Soil, sandy clay. Vegetation, native grasses.</p> <hr/> <p>N. 0°02' W., bet. secs. 28 and 29.</p> <p>Over gently rolling land.</p>
20.95	Trail road, bears N. 30° E. and S. 30° W.
27.45	Trail road, bears N. 70° E. and S. 70° W.
40.00	<p>Point for the 1/4 sec. cor. of secs. 28 and 29.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T 24 N R 23 E 1/4 S 29 S 28</p> <p style="text-align: center;">2011</p> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p>
80.00	<p>Point for the cor. of secs. 20, 21, 28 and 29.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p>

Survey of the Subdivisional Lines,
T. 24 N., R. 23 E., Gila and Salt River Meridian, Arizona

CHAINS									
	<table style="margin-left: auto; margin-right: auto;"> <tr> <td>T 24 N</td> <td>R 23 E</td> </tr> <tr> <td style="border-right: 1px solid black;">S 20</td> <td>S 21</td> </tr> <tr> <td style="border-right: 1px solid black;">S 29</td> <td>S 28</td> </tr> </table>	T 24 N	R 23 E	S 20	S 21	S 29	S 28		
T 24 N	R 23 E								
S 20	S 21								
S 29	S 28								
	2011								
	Deposit a magnet, in a white plastic case, at the base of the stainless steel post.								
	Land, gently rolling to nearly level. Soil, sandy clay. Vegetation, native grasses.								
	<hr/>								
	From the cor. of secs. 21, 22, 27 and 28.								
	S. 89°54' W., bet. secs. 21 and 28.								
	Over gently rolling land.								
40.00	Point for the 1/4 sec. cor. of secs. 21 and 28.								
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.								
	<table style="margin-left: auto; margin-right: auto;"> <tr> <td>T 24 N</td> <td>R 23 E</td> </tr> <tr> <td></td> <td>S 21</td> </tr> <tr> <td>1/4</td> <td style="border-top: 1px solid black;">_____</td> </tr> <tr> <td></td> <td>S 28</td> </tr> </table>	T 24 N	R 23 E		S 21	1/4	_____		S 28
T 24 N	R 23 E								
	S 21								
1/4	_____								
	S 28								
	2011								
	Deposit a magnet, in a white plastic case, at the base of the stainless steel post.								
80.00	The cor. of secs. 20, 21, 28 and 29.								
	Land, nearly level. Soil, sandy clay. Vegetation, native grasses.								
	<hr/>								
	N. 0°02' W., bet. secs. 20 and 21.								
	Over nearly level land.								
2.20	Trail road, bears N. 50° E. and S. 50° W.								
17.50	Trail road, bears S. 85° E. and N. 85° W.								
40.00	Point for the 1/4 sec. cor. of secs. 20 and 21.								

Survey of the Subdivisional Lines,
T. 24 N., R. 23 E., Gila and Salt River Meridian, Arizona

CHAINS	
	<p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T 24 N R 23 E 1/4 S 20 S 21</p> <p style="text-align: center;">2011</p> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p>
44.90	Power line, 2 strand, bears S. 80° E. and N. 80° W.
45.05	Trail road, bears S. 80° E. and N. 80° W.
75.25	Underground gas pipeline, bears S. 85° E. and N. 85° W.
75.55	Trail road, bears S. 75° E. and N. 75° W.
79.55	Power line, 4 strand, bears N. 45° E. and S. 45° W.
80.00	Point for the cor. of secs. 16, 17, 20 and 21.
	<p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T 24 N R 23 E S 17 S 16 S 20 S 21</p> <p style="text-align: center;">2011</p> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p> <p>Land, gently rolling to nearly level. Soil, sandy clay. Vegetation, native grasses.</p> <hr/> <p>From the cor. of secs. 15, 16, 21 and 22.</p> <p>S. 89°54' W., bet. secs. 16 and 21.</p> <p>Over nearly level rolling land.</p>
40.00	Point for the 1/4 sec. cor. of secs. 16 and 21.
	<p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p>

Survey of the Subdivisional Lines,
T. 24 N., R. 23 E., Gila and Salt River Meridian, Arizona

CHAINS	
	T 24 N R 23 E S 16 1/4 ——— S 21 2011 Deposit a magnet, in a white plastic case, at the base of the stainless steel post.
43.55	Trail road, bears S. 35° E. and N. 35° W.
79.55	Power line, 4 strand, bears N. 45° E. and S. 45° W.
80.00	The cor. of secs. 16, 17, 20 and 21. Land, nearly level. Soil, sandy clay. Vegetation, native grasses.
	N. 0°02' W., bet. secs. 16 and 17. Over gently rolling land.
3.30	BIA Route N153, a graded road, 30 ft. wide, bears N. 50° E. and S. 50° W.
40.00	Point for the 1/4 sec. cor. of secs. 16 and 17. Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.
	T 24 N R 23 E 1/4 S 17 S 16 2011 Deposit a magnet, in a white plastic case, at the base of the stainless steel post.
80.00	Point for the cor. of secs. 8, 9, 16 and 17. Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.
	T 24 N R 23 E S 8 S 9 S 17 S 16 2010

Survey of the Subdivisional Lines,
T. 24 N., R. 23 E., Gila and Salt River Meridian, Arizona

CHAINS	
	<p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p> <p>Land, gently rolling to nearly level. Soil, sandy clay. Vegetation, native grasses.</p> <hr/> <p>From the cor. of secs. 9, 10, 15 and 16.</p> <p>S. 89°54' W., bet. secs. 9 and 16.</p> <p>Over gently rolling land.</p>
40.00	<p>Point for the 1/4 sec. cor. of secs. 9 and 16.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center;"> <p>T 24 N R 23 E</p> <p>S 9</p> <p>1/4 ———</p> <p>S 16</p> <p>2011</p> </div>
	<p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p>
51.15	<p>Barbed wire fence, 5 strand, bears S. 70° E. and N. 70° W.</p>
80.00	<p>The cor. of secs. 8, 9, 16 and 17.</p> <p>Land, gently rolling. Soil, sandy clay. Vegetation, native grasses.</p> <hr/> <p>N. 0°02' W., bet. secs. 8 and 9.</p> <p>Over gently rolling land.</p>
33.80	<p>Steamboat Wash, 25 ft. wide, 4 ft. deep, drains S. 25° W.</p>
40.00	<p>Point for the 1/4 sec. cor. of secs. 8 and 9.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p>

Survey of the Subdivisional Lines,
T. 24 N., R. 23 E., Gila and Salt River Meridian, Arizona

CHAINS	
	T 24 N R 23 E 1/4 S 8 S 9 2011
	Deposit a magnet, in a white plastic case, at the base of the stainless steel post.
70.80	Man-made dam, 15 ft. wide, 10 ft. high, bears N. 80° E. and S. 80° W.
80.00	Point for the cor. of secs. 4, 5, 8 and 9.
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.
	T 24 N R 23 E S 5 S 4 S 8 S 9 2011
	Deposit a magnet, in a white plastic case, at the base of the stainless steel post.
	Land, gently rolling. Soil, sandy clay. Vegetation, native grasses.
	From the cor. of secs. 3, 4, 9 and 10.
	S. 89°54' W., bet. secs. 4 and 9.
	Over rolling land.
40.00	Point for the 1/4 sec. cor. of secs. 4 and 9.
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.
	T 24 N R 23 E S 4 1/4 ——— S 9 2011
	Deposit a magnet, in a white plastic case, at the base of the stainless steel post.
	Cor. is located on a gentle N. hillside.

Survey of the Subdivisional Lines,
T. 24 N., R. 23 E., Gila and Salt River Meridian, Arizona

CHAINS	
69.00	Steamboat Wash, 10 ft. wide, 2 ft. deep, drains S. 25° W.
80.00	The cor. of secs. 4, 5, 8 and 9. Land, rolling to gently rolling. Soil, sandy clay. Vegetation, native grasses.
	N. 0°02' W., bet. secs. 4 and 5. Over gently rolling land.
23.75	Underground gas pipeline, bears N. 65° E. and S. 65° W.
26.00	S. right-of-way fence of BIA Route 15, barbed wire, 5 strand, parallels highway.
27.25	BIA Route 15, an asphalt road, 35 ft. wide, bears N. 70° E. and S. 70° W.
28.55	N. right-of-way fence of BIA Route 15, barbed wire, 5 strand, parallels highway.
40.00	Point for the 1/4 sec. cor. of secs. 4 and 5. Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd. <div style="text-align: center;"> T 24 N R 23 E 1/4 S 5 S 4 2011 </div>
	Deposit a magnet, in a white plastic case, at the base of the stainless steel post.
78.80	Point for the closing cor. of secs. 4 and 5, at intersection with the Sixth Standard Parallel North, the N. bdy. of the Tp. Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd. <div style="text-align: center;"> T 25 N R 23 E S 32 ----- S 5 S 4 T 24 N R 23 E CC 2011 </div>

**Survey of the Subdivisional Lines,
T. 24 N., R. 23 E., Gila and Salt River Meridian, Arizona**

CHAINS

Deposit a magnet, in a white plastic case, at the base of the stainless steel post.

From this cor. point, the stan. 1/4 sec. cor. of sec. 32, T. 25 N., R. 23 E., bears S. 89°55' E., 33.35 chs. dist., monumented with a stainless steel post, 2 1/2 ins. diam., firmly set, projecting 4 ins. above ground, with brass cap mkd. SC T25N R23E 1/4 S32 2001. Add the marks 2010 to the brass cap.

From this same cor. point, the stan. cor. of secs. 31 and 32, T. 25 N., R. 23 E., bears N. 89°55' W., 6.82 chs. dist., monumented with a stainless steel post, 2 1/2 ins. diam., firmly set, projecting 7 ins. above ground, with brass cap mkd. SC T25N R23E S31 S32 2001. Add the marks 2010 to the brass cap.

Land, gently rolling to rolling.
Soil, sandy clay.
Vegetation, native grasses.

Point for the 1/4 sec. cor. of sec. 4 only, at midpoint on the N. bdy. of sec. 4.

Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.

T 25 N R 23 E

1/4 S 4

T 24 N R 23 E

2011

Deposit a magnet, in a white plastic case, at the base of the stainless steel post.

From this cor. point, the stan. cor. of secs. 32 and 33, T. 25 N., R. 23 E., bears S. 89°55' E., 33.52 chs. dist., hereinbefore described.

From this same cor. point, the stan. 1/4 sec. cor. of sec. 32, T. 25 N., R. 23 E., bears N. 89°55' W., 6.65 chs. dist., hereinbefore described.

From the cor. of secs. 5, 6, 31 and 32, on the S. bdy. of the Tp., hereinbefore described.

N. 0°03' W., bet. secs. 31 and 32.

Over rolling land.

40.00

Point for the 1/4 sec. cor. of secs. 31 and 32.

Survey of the Subdivisional Lines,
T. 24 N., R. 23 E., Gila and Salt River Meridian, Arizona

CHAINS	
	<p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T 24 N R 23 E 1/4 S 31 S 32</p> <p style="text-align: center;">2011</p> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p>
80.00	<p>Point for the cor. of secs. 29, 30, 31 and 32.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T 24 N R 23 E S 30 S 29 S 31 S 32</p> <p style="text-align: center;">2011</p> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p> <p>Land, rolling. Soil, sandy clay. Vegetation, native grasses.</p> <hr/> <p>From the cor. of secs. 28, 29, 32 and 33.</p> <p>S. 89°54' W., bet. secs. 29 and 32.</p> <p>Over gently rolling land.</p>
40.00	<p>Point for the 1/4 sec. cor. of secs. 29 and 32.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T 24 N R 23 E S 29 1/4 ——— S 32</p> <p style="text-align: center;">2011</p> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p>
80.00	<p>The cor. of secs. 29, 30, 31 and 32.</p>

Survey of the Subdivisional Lines,
T. 24 N., R. 23 E., Gila and Salt River Meridian, Arizona

CHAINS	
	<p>Land, gently rolling to rolling. Soil, sandy clay. Vegetation, native grasses.</p> <hr/> <p>S. 89°54' W., bet. secs. 30 and 31.</p> <p>Over rolling land.</p>
40.00	<p>Point for the 1/4 sec. cor. of secs. 30 and 31.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T 24 N R 23 E S 30 1/4 ——— S 31</p> <p style="text-align: center;">2011</p> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p>
58.85	<p>BIA Route N153, a graded road, 20 ft. wide, bears N. 40° E. and S. 40° W.</p>
76.48	<p>The cor. of secs. 25, 30, 31 and 36 on the W. bdy. of the Tp., hereinbefore described.</p> <p>Land, rolling. Soil, sandy clay. Vegetation, native grasses.</p> <hr/> <p>From the cor. of secs. 29, 30, 31 and 32.</p> <p>N. 0°03' W., bet. secs. 29 and 30.</p> <p>Over rolling land.</p>
40.00	<p>Point for the 1/4 sec. cor. of secs. 29 and 30.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T 24 N R 23 E 1/4 S 30 S 29</p> <p style="text-align: center;">2011</p>

Survey of the Subdivisional Lines,
T. 24 N., R. 23 E., Gila and Salt River Meridian, Arizona

CHAINS	<p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p>								
72.60	<p>Power line, 4 strand, bears N. 35° E. and S. 35° W.</p>								
80.00	<p>Point for the cor. of secs. 19, 20, 29 and 30.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center; margin: 10px 0;"> <table style="margin: auto; border-collapse: collapse;"> <tr> <td style="padding: 0 10px;">T 24 N</td> <td style="padding: 0 10px;">R 23 E</td> </tr> <tr> <td style="padding: 0 10px; border-right: 1px solid black;">S 19</td> <td style="padding: 0 10px;">S 20</td> </tr> <tr> <td style="padding: 0 10px; border-right: 1px solid black;">S 30</td> <td style="padding: 0 10px;">S 29</td> </tr> </table> </div> <p style="text-align: center; margin: 5px 0;">2011</p> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p> <p>Land, rolling. Soil, sandy clay. Vegetation, native grasses.</p> <hr style="width: 60%; margin: 20px auto;"/> <p>From the cor. of secs. 20, 21, 28 and 29.</p> <p>S. 89°54' W., bet. secs. 20 and 29.</p> <p>Over nearly level land.</p>	T 24 N	R 23 E	S 19	S 20	S 30	S 29		
T 24 N	R 23 E								
S 19	S 20								
S 30	S 29								
40.00	<p>Point for the 1/4 sec. cor. of secs. 20 and 29.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center; margin: 10px 0;"> <table style="margin: auto; border-collapse: collapse;"> <tr> <td style="padding: 0 10px;">T 24 N</td> <td style="padding: 0 10px;">R 23 E</td> </tr> <tr> <td style="padding: 0 10px;"></td> <td style="padding: 0 10px;">S 20</td> </tr> <tr> <td style="padding: 0 10px;">1/4</td> <td style="padding: 0 10px; border-top: 1px solid black;">_____</td> </tr> <tr> <td style="padding: 0 10px;"></td> <td style="padding: 0 10px;">S 29</td> </tr> </table> </div> <p style="text-align: center; margin: 5px 0;">2011</p> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p>	T 24 N	R 23 E		S 20	1/4	_____		S 29
T 24 N	R 23 E								
	S 20								
1/4	_____								
	S 29								
80.00	<p>The cor. of secs. 19, 20, 29 and 30.</p> <p>Land, nearly level to gently rolling. Soil, sandy clay. Vegetation, native grasses.</p> <hr style="width: 60%; margin: 20px auto;"/> <p>S. 89°54' W., bet. secs. 19 and 30.</p>								

Survey of the Subdivisional Lines,
T. 24 N., R. 23 E., Gila and Salt River Meridian, Arizona

CHAINS	
	Over gently rolling land.
19.60	BIA Route N153, a graded road, 20 ft. wide, bears N. 20° E. and S. 20° W.
40.00	Point for the 1/4 sec. cor. of secs. 19 and 30. Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.
	T 24 N R 23 E S 19 1/4 ——— S 30 2011
	Deposit a magnet, in a white plastic case, at the base of the stainless steel post.
76.40	The cor. of secs. 19, 24, 25 and 30 on the W. bdy. of the Tp., hereinbefore described. Land, gently rolling. Soil, sandy clay. Vegetation, native grasses.
	From the cor. of secs. 19, 20, 29 and 30. N. 0°03' W., bet. secs. 19 and 20. Over gently rolling land.
18.45	BIA Route N153, a graded road, 20 ft. wide, bears N. 60° E. and S. 60° W.
40.00	True point for the 1/4 sec. cor. of secs. 19 and 20, falls in a reservoir, where it is impracticable to establish a permanent monument. From this true point, the point selected for a witness cor. to the 1/4 sec. cor. of secs. 19 and 20, bears S. 70°00' E., 1.00 ch. dist. Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.

Survey of the Subdivisional Lines,
T. 24 N., R. 23 E., Gila and Salt River Meridian, Arizona

CHAINS	
	WC T 24 N R 23 E ← 1/4 S 19 S 20 2011
	Deposit a magnet, in a white plastic case, at the base of the stainless steel post. Cor. is located on the E. bank, 60 lks. dist. from the reservoir.
80.00	True point for the cor. of secs. 17, 18, 19 and 20, falls in a drainage, the inlet for the reservoir, where it is impracticable to establish a permanent monument. From this true point, the point selected for a witness cor. to the cor. of secs. 17, 18, 19 and 20, bears N. 45°00' W., 2.00 chs. dist. Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.
	WC T 24 N R 23 E S 18 S 17 S 19 S 20 ↘ 2011
	Deposit a magnet, in a white plastic case, at the base of the stainless steel post. Set a steel fence post nearby. Land, rolling. Soil, sandy clay. Vegetation, native grasses.
	<hr/> From the cor. of secs. 16, 17, 20 and 21. S. 89°54' W., bet. secs. 17 and 20. Over gently rolling land.
3.80	BIA Route N153, a graded road, 30 ft. wide, bears N. 50° E. and S. 50° W.
18.90	Underground gas pipeline, bears S. 75° E. and N. 75° W.
40.00	Point for the 1/4 sec. cor. of secs. 17 and 20.

Survey of the Subdivisional Lines,
T. 24 N., R. 23 E., Gila and Salt River Meridian, Arizona

CHAINS	
	<p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T 24 N R 23 E S 17 1/4 ——— S 20</p> <p style="text-align: center;">2011</p> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p>
80.00	<p>True point for the cor. of secs. 17, 18, 19 and 20.</p> <p>Land, gently rolling to rolling. Soil, sandy clay. Vegetation, native grasses.</p> <hr/> <p>S. 89°54' W., bet. secs. 18 and 19.</p> <p>Over rolling land.</p>
40.00	<p>Point for the 1/4 sec. cor. of secs. 18 and 19.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T 24 N R 23 E S 18 1/4 ——— S 19</p> <p style="text-align: center;">2011</p> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p>
76.31	<p>The cor. of secs. 13, 18, 19 and 24 on the W. bdy. of the Tp., hereinbefore described.</p> <p>Land, rolling. Soil, sandy clay. Vegetation, native grasses.</p> <hr/> <p>From the cor. of secs. 17, 18, 19 and 20.</p> <p>N. 0°03' W., bet. secs. 17 and 18.</p> <p>Over rolling land.</p>

Survey of the Subdivisional Lines,
T. 24 N., R. 23 E., Gila and Salt River Meridian, Arizona

CHAINS	
14.50	Underground gas pipeline, bears S. 75° E. and N. 75° W.
40.00	Point for the 1/4 sec. cor. of secs. 17 and 18. Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd. <div style="text-align: center;"> T 24 N R 23 E 1/4 S 18 S 17 2011 </div> Deposit a magnet, in a white plastic case, at the base of the stainless steel post.
46.50	Steamboat Wash, 20 ft. wide, 6 ft. deep, drains S. 65° W.
80.00	Point for the cor. of secs. 7, 8, 17 and 18. Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd. <div style="text-align: center;"> T 24 N R 23 E S 7 S 8 S 18 S 17 2011 </div> Deposit a magnet, in a white plastic case, at the base of the stainless steel post. Land, gently rolling. Soil, sandy clay. Vegetation, native grasses. <hr/>
	From the cor. of secs. 8, 9, 16 and 17. S. 89°54' W., bet. secs. 8 and 17. Over gently rolling land.
39.10	Steamboat Wash, 30 ft. wide, 10 ft. deep, drains S. 70° W.
40.00	Point for the 1/4 sec. cor. of secs. 8 and 17. Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.

Survey of the Subdivisional Lines,
T. 24 N., R. 23 E., Gila and Salt River Meridian, Arizona

CHAINS	
	T 24 N R 23 E S 8 1/4 ——— S 17 2011
	Deposit a magnet, in a white plastic case, at the base of the stainless steel post. Cor. is located on the W. bank of Steamboat Wash.
80.00	The cor. of secs. 7, 8, 17 and 18. Land, gently rolling. Soil, sandy clay. Vegetation, native grasses.
	S. 89°54' W., bet. secs. 7 and 18. Over gently rolling land.
40.00	Point for the 1/4 sec. cor. of secs. 7 and 18. Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.
	T 24 N R 23 E S 7 1/4 ——— S 18 2011
76.23	Deposit a magnet, in a white plastic case, at the base of the stainless steel post. The cor. of secs. 7, 12, 13 and 18 on the W. bdy. of the Tp., hereinbefore described. Land, gently rolling to nearly level. Soil, sandy clay. Vegetation, native grasses.
	From the cor. of secs. 7, 8, 17 and 18. N. 0°03' W., bet. secs. 7 and 8. Over gently rolling land.
40.00	Point for the 1/4 sec. cor. of secs. 7 and 8.

Survey of the Subdivisional Lines,
T. 24 N., R. 23 E., Gila and Salt River Meridian, Arizona

CHAINS	
	<p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T 24 N R 23 E 1/4 S 7 S 8 2011</p> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p>
43.20	S. right-of-way fence of BIA Route 15, barbed wire, 5 strand, parallels highway.
44.85	BIA Route 15, an asphalt road, 35 ft. wide, bears N. 50° E. and S. 50° W.
46.55	N. right-of-way fence of BIA Route 15, barbed wire, 5 strand, parallels highway.
69.95	Underground gas pipeline, bears N. 65° E. and S. 65° W.
80.00	Point for the cor. of secs. 5, 6, 7 and 8.
	<p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T 24 N R 23 E S 6 S 5 S 7 S 8 2011</p> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p> <p>Land, gently rolling to nearly level. Soil, sandy clay. Vegetation, native grasses.</p> <hr/> <p>From the cor. of secs. 4, 5, 8 and 9.</p> <p>S. 89°54' W., bet. secs. 5 and 8.</p> <p>Over nearly level land.</p>
38.35	E. right-of-way fence of BIA Route 15, barbed wire, 5 strand, parallels highway.
40.00	Point for the 1/4 sec. cor. of secs. 5 and 8.

Survey of the Subdivisional Lines,
T. 24 N., R. 23 E., Gila and Salt River Meridian, Arizona

CHAINS	
	<p>Set a magnetic nail at the true point, flush with the asphalt surface.</p> <p>from which</p> <p style="padding-left: 40px;">A stainless steel post, 28 ins. long, 2 1/2 ins. diam., set 24 ins. in the ground for a reference monument, bears S. 40°00' E., 70.0 ft. dist. with brass cap mkd. RM T24N R23E 1/4 S8 70.0 FT TO COR 2011 and an arrow pointing to the cor. Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p> <p style="padding-left: 40px;">A stainless steel post, 28 ins. long, 2 1/2 ins. diam., set 24 ins. in the ground for a reference monument, bears N. 40°00' W., 84.0 ft. dist. with brass cap mkd. RM T24N R23E 1/4 S5 84.0 FT TO COR 2011 and an arrow pointing to the cor. Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p> <p>The 1/4 sec. cor. is located on BIA Route 15, hereinafter described, 15 lks. dist., from the S. edge of asphalt.</p>
40.15	BIA Route 15, an asphalt road, 35 ft. wide, bears N. 45° E. and S. 45° W.
41.95	W. right-of-way fence of BIA Route 15, barbed wire, 5 strand, parallels highway.
57.00	Underground gas pipeline, bears N. 65° E. and S. 65° W.
80.00	The cor. of secs. 5, 6, 7 and 8.
	<p>Land, nearly level to gently rolling. Soil, sandy clay. Vegetation, native grasses.</p> <hr/> <p>S. 89°54' W., bet. secs. 6 and 7.</p> <p>Over gently rolling land.</p>
40.00	<p>Point for the 1/4 sec. cor. of secs. 6 and 7.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T 24 N R 23 E S 6 1/4 ——— S 7</p> <p style="text-align: center;">2011</p>

Survey of the Subdivisional Lines,
T. 24 N., R. 23 E., Gila and Salt River Meridian, Arizona

CHAINS	
	<p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p>
76.14	<p>The cor. of secs. 1, 6, 7 and 12 on the W. bdy. of the Tp., hereinbefore described.</p> <p>Land, gently rolling to nearly level. Soil, sandy clay. Vegetation, native grasses.</p> <hr/> <p>From the cor. of secs. 5, 6, 7 and 8.</p> <p>N. 0°03' W., bet. secs. 5 and 6.</p> <p>Over gently rolling land.</p>
40.00	<p>Point for the 1/4 sec. cor. of secs. 5 and 6.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T 24 N R 23 E 1/4 S 6 S 5 2011</p>
	<p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p>
79.07	<p>Point for the closing cor. of secs. 5 and 6, at intersection with the Sixth Standard Parallel North, the N. bdy. of the Tp.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T 25 N R 23 E S 31 ----- S 6 S 5 T 24 N R 23 E CC 2011</p>
	<p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p> <p>From this cor. point, the stan. 1/4 sec. cor. of sec. 31, T. 25 N., R. 23 E., bears S. 89°55' E., 33.01 chs. dist., monumented with a stainless steel post, 2 1/2 ins. diam., firmly set, projecting 5 ins. above ground, with brass cap mkd. SC T25N R23E 1/4 S31 2001. Add the marks 2010 to the brass cap.</p>

Survey of the Subdivisional Lines,
T. 24 N., R. 23 E., Gila and Salt River Meridian, Arizona

CHAINS

From this same cor. point, the stan. cor. of Tps. 25 N., Rs. 22 and 23 E., bears N. 89°55' W., 7.16 chs. dist., monumented with a stainless steel post, 2 1/2 ins. diam., firmly set, projecting 4 ins. above ground, with brass cap mkd. SC T25N R22E R23E S36 S31 2001. Add the marks 2010 to the brass cap.

Land, gently rolling.
Soil, sandy clay.
Vegetation, native grasses.

Point for the 1/4 sec. cor. of sec. 5 only, at midpoint on the N. bdy. of sec. 5.

Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.

T 25 N R 23 E

1/4 S 5

T 24 N R 23 E

2011

Deposit a magnet, in a white plastic case, at the base of the stainless steel post.

From this cor. point, the stan. cor. of secs. 31 and 32, T. 25 N., R. 23 E., bears S. 89°55' E., 33.18 chs. dist., hereinbefore described.

From this same cor. point, the stan. 1/4 sec. cor. of sec. 31, T. 25 N., R. 23 E., bears N. 89°55' W., 6.99 chs. dist., hereinbefore described.

Point for the 1/4 sec. cor. of sec. 6 only, at 40.00 chs. westerly from the closing cor. of secs. 5 and 6, on the N. bdy. of sec. 6.

Set a rebar, 18 ins. long, 1/2 in. diam., 4 ins. below the surface of the ground.

from which

A stainless steel post, 28 ins. long, 2 1/2 ins. diam., set 24 ins. in the ground for a reference monument, bears S. 30°00' E., 80.0 ft. dist. with brass cap mkd. RM T24N R23E 1/4 S6 80.0 FT TO COR 2011 and an arrow pointing to the cor. Deposit a magnet, in a white plastic case, at the base of the stainless steel post.

**Survey of the Subdivisional Lines,
T. 24 N., R. 23 E., Gila and Salt River Meridian, Arizona**

CHAINS	
	<p>A stainless steel post, 28 ins. long, 2 1/2 ins. diam., set 24 ins. in the ground for a reference monument, bears S. 60°00' W., 40.0 ft. dist. with brass cap mkd. RM T24N R23E 1/4 S6 40.0 FT TO COR 2011 and an arrow pointing to the cor. Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p> <p>The 1/4 sec. cor. of sec 6 only, is located in a wash, 20 ft. wide, 3 ft. deep, drains S.</p> <p>From this cor. point, the stan. cor. of Tps. 25 N., Rs. 22 and 23 E., bears S. 89°55' E., 32.84 chs. dist., hereinbefore described.</p> <p>From this same cor. point, the stan. 1/4 sec. cor. of sec. 36, T. 25 N., R. 22 E., bears N. 89°55' W., 7.33 chs. dist., hereinbefore described.</p> <hr/> <p style="text-align: center;">Subdivision of Section 3, T. 24 N., R. 23 E., Gila and Salt River Meridian, Arizona</p> <hr/> <p>From the 1/4 sec. cor. of secs. 3 and 10.</p> <p>N. 0°02' W., on the N. and S. center line of sec. 3.</p> <p>Over gently rolling land.</p> <p>40.00 Point for the center 1/4 sec. cor. of sec. 3, at intersection with the E. and W. center line.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T 24 N R 23 E C 1/4 S 3</p> <p style="text-align: center;">2011</p> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p> <p>Set a steel fence post nearby.</p> <p>74.40 Underground gas pipeline, bears N. 65° E. and S. 65° W.</p> <p>76.25 S. right-of-way fence of BIA Route 15, barbed wire, 5 strand, parallels highway.</p> <p>77.60 BIA Route 15, an asphalt road, 35 ft. wide, bears N. 65° E. and S. 65° W.</p>

**Subdivision of Section 3,
T. 24 N., R. 23 E., Gila and Salt River Meridian, Arizona**

CHAINS	
78.40	<p>The 1/4 sec. cor. of sec. 3 only, on the N. bdy. of the Tp.</p> <hr/> <p>From the 1/4 sec. cor. of secs. 2 and 3.</p> <p>S. 89°54' W., on the E. and W. center line of sec. 3.</p> <p>Over gently rolling land.</p>
40.00	The center 1/4 sec. cor. of sec. 3.
80.00	The 1/4 sec. cor. of secs. 3 and 4.
<p>Subdivision of Section 4, T. 24 N., R. 23 E., Gila and Salt River Meridian, Arizona</p> <hr/>	
	<p>From the 1/4 sec. cor. of secs. 4 and 9.</p> <p>N. 0°02' W., on the N. and S. center line of sec. 4.</p> <p>Over gently rolling land.</p>
40.00	<p>Point for the center 1/4 sec. cor. of sec. 4, at intersection with the E. and W. center line.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T 24 N R 23 E C 1/4 S 4</p> <p style="text-align: center;">2011</p> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p> <p>Set a steel fence post nearby.</p>
40.60	Underground gas pipeline, bears N. 70° E. and S. 70° W.
42.70	S. right-of-way fence of BIA Route 15, barbed wire, 5 strand, parallels highway.
44.05	BIA Route 15, an asphalt road, 35 ft. wide, bears N. 65° E. and S. 65° W.
45.35	N. right-of-way fence of BIA Route 15, barbed wire, 5 strand, parallels highway.
78.67	The 1/4 sec. cor. of sec 4 only, on the N. bdy. of the Tp.

**Subdivision of Section 4,
T. 24 N., R. 23 E., Gila and Salt River Meridian, Arizona**

CHAINS	
	From the 1/4 sec. cor. of secs. 3 and 4.
	S. 89°54' W., on the E. and W. center line of sec. 4.
	Over rolling land.
40.00	The center 1/4 sec. cor. of sec. 4.
41.65	Underground gas pipeline, bears N. 70° E. and S. 70° W.
45.10	Steamboat Wash, 10 ft. wide, 4 ft. deep, drains S. 40° W.
46.25	E. right-of-way fence of BIA Route 15, barbed wire, 5 strand, parallels highway.
49.30	BIA Route 15, an asphalt road, 35 ft. wide, bears N. 65° E. and S. 65° W.
52.30	W. right-of-way fence of BIA Route 15, barbed wire, 5 strand, parallels highway.
80.00	The 1/4 sec. cor. of secs. 4 and 5.
<hr/> <p>Subdivision of Section 5, T. 24 N., R. 23 E., Gila and Salt River Meridian, Arizona</p> <hr/>	
	From the 1/4 sec. cor. of secs. 5 and 8.
	N. 0°03' W., on the N. and S. center line of sec. 5.
	Over gently rolling land.
0.15	BIA Route 15, an asphalt road, 40 ft. wide, bears N. 50° E. and S. 50° W.
1.80	N. right-of-way fence of BIA Route 15, barbed wire, 5 strand, parallels highway.
6.80	Underground gas pipeline, bears N. 65° E. and S. 65° W.
40.00	Point for the center 1/4 sec. cor. of sec. 5, at intersection with the E. and W. center line.
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.

Subdivision of Section 5,
T. 24 N., R. 23 E., Gila and Salt River Meridian, Arizona

CHAINS	
	T 24 N R 23 E C 1/4 S 5
	2011
	Deposit a magnet, in a white plastic case, at the base of the stainless steel post.
	Set a steel fence post nearby.
78.93	The 1/4 sec. cor. of sec. 5 only, on the N. bdy. of the Tp.
	<hr/>
	From the 1/4 sec. cor. of secs. 4 and 5.
	S. 89°54' W., on the E. and W. center line of sec. 5.
	Over gently rolling land.
40.00	The center 1/4 sec. cor. of sec. 5.
80.00	The 1/4 sec. cor. of secs. 5 and 6.
	<hr/>
	Subdivision of Section 7, T. 24 N., R. 23 E., Gila and Salt River Meridian, Arizona
	<hr/>
	From the 1/4 sec. cor. of secs. 7 and 18.
	N. 0°03' W., on the N. and S. center line of sec. 7.
	Over gently rolling land.
22.85	S. right-of-way fence of BIA Route 15, barbed wire, 5 strand, parallels highway.
24.15	BIA Route 15, an asphalt road, 40 ft. wide, bears N. 70° E. and S. 70° W.
25.45	N. right-of-way fence of BIA Route 15, barbed wire, 5 strand, parallels highway.
40.00	Point for the center 1/4 sec. cor. of sec. 7, at intersection with the E. and W. center line.
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.

**Subdivision of Section 7,
T. 24 N., R. 23 E., Gila and Salt River Meridian, Arizona**

CHAINS	
	T 24 N R 23 E C 1/4 S 7 2011
	Deposit a magnet, in a white plastic case, at the base of the stainless steel post. Set a steel fence post nearby.
53.70	Underground gas pipeline, bears N. 70° E. and S. 70° W.
80.00	The 1/4 sec. cor. of secs. 6 and 7.
	<hr/> From the 1/4 sec. cor. of secs. 7 and 8. S. 89°54' W., on the E. and W. center line of sec. 7. Over gently rolling land.
3.70	E. right-of-way fence of BIA Route 15, barbed wire, 5 strand, parallels highway.
5.60	BIA Route 15, an asphalt road, 40 ft. wide, bears N. 50° E. and S. 50° W.
7.45	W. right-of-way fence of BIA Route 15, barbed wire, 5 strand, parallels highway.
40.00	The center 1/4 sec. cor. of sec. 7.
72.15	Underground gas pipeline, bears N. 65° E. and S. 65° W.
76.19	The 1/4 sec. cor. of secs. 7 and 12, on the W. bdy. of the Tp.
	<hr/> Subdivision of Section 8, T. 24 N., R. 23 E., Gila and Salt River Meridian, Arizona <hr/>
	From the 1/4 sec. cor. of secs. 8 and 17. N. 0°03' W., on the N. and S. center line of sec. 8. Over gently rolling land.
40.00	Point for the center 1/4 sec. cor. of sec. 8, at intersection with the E. and W. center line. Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.

Subdivision of Section 8,
T. 24 N., R. 23 E., Gila and Salt River Meridian, Arizona

CHAINS	
	T 24 N R 23 E C 1/4 S 8
	2011
	Deposit a magnet, in a white plastic case, at the base of the stainless steel post.
	Set a steel fence post nearby.
78.50	S. right-of-way fence of BIA Route 15, barbed wire, 5 strand, bears N. 50° E. and S. 50° W.
80.00	The 1/4 sec. cor. of secs. 5 and 8.
	<hr/>
	From the 1/4 sec. cor. of secs. 8 and 9.
	S. 89°54' W., on the E. and W. center line of sec. 8.
	Over gently rolling land.
40.00	The center 1/4 sec. cor. of sec. 8.
80.00	The 1/4 sec. cor. of secs. 7 and 8.
	<hr/>

T. 24 N., R. 23 E., Gila and Salt River Meridian, Arizona

CHAINS

GENERAL DESCRIPTION

The area surveyed is within the Navajo Indian Reservation, approximately 1/4 miles south of Greasewood, Arizona. The terrain is mostly rolling land. Drainage is to the southwest.

The elevation varies from 5800 to 6100 feet above sea level. The soil is mostly sandy and sandy clay. Timber consists of sparse scattered juniper throughout the township and cottonwood along the Pueblo Colorado Wash; primarily in the northern part of the township. Undergrowth consists of scattered brush, greasewood and native grasses.


The principal access to the township is provided by BIA Routes N153 and N157, both graded roads, which enter the township in the northeast and exit to the south and southwest of the township. From these two main roads, there are numerous trail roads throughout the township to residential areas. BIA Route 15, an asphalt road, enters from the north boundary of the township and exits via the west boundary. Much of the area is used for grazing livestock. An underground gas pipeline enters the township in section 24 and exits in section 18 and another underground gas pipeline enters section 3 and exits in section 7. There is no evidence of any mining activity in the township.

The mean magnetic declination of 10 1/2° E. was derived from the NOAA National Geophysical Data Center computer program GEOMAG, utilizing the World Magnetic Model for Epoch 2005-2010 for the dates of survey.

CERTIFICATE OF SURVEY

I, Fabian Yazzie, Cadastral Surveyor, HEREBY CERTIFY upon honor, that in pursuance of special instructions bearing date of the 9th day of November, 2010, I have dependently resurveyed a portion of the Sixth Standard Parallel North (South Boundary), Township 25 North, Range 23 East, surveyed the south and west boundaries, the subdivisional lines and the subdivision of certain sections, T. 24 N., R. 23 E., of the Gila and Salt River Meridian, in the State of Arizona, which are represented in the foregoing field notes as having been executed by me and under my direction. Said survey has been made in strict conformity with said special instructions, the Manual of Surveying Instructions for the Survey of the Public Lands of the United States, 2009 and in specific manner described in the foregoing field notes.

5/01/2012
(Date)



(Cadastral Surveyor)

CERTIFICATE OF APPROVAL

BUREAU OF LAND MANAGEMENT
Phoenix, Arizona

The foregoing field notes of the dependently resurveyed portion of the Sixth Standard Parallel North (South Boundary), Township 25 North, Range 23 East, the survey of the south and west boundaries, the subdivisional lines and the subdivision of certain sections, T. 24 N., R. 23 E., Gila and Salt River Meridian, in the State of Arizona, executed by Fabian Yazzie, Cadastral Surveyor, having been critically examined and found correct, are hereby approved.

7/23/2012
(Date)


(Chief Cadastral Surveyor of Arizona)

~~CERTIFICATE OF TRANSCRIPT~~

~~I CERTIFY That the foregoing transcript of the field notes of the above described surveys in T. 24 N., R. 23 E., Gila and Salt River Meridian, Arizona, is a true copy of the original field notes.~~

~~_____
(Date)~~

~~_____
(Chief Cadastral Surveyor of Arizona)~~