

ORIGINAL

**UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT**

FIELD NOTES
OF THE DEPENDENT RESURVEY OF THE
WEST AND NORTH BOUNDARIES
AND
THE SURVEY OF THE SUBDIVISIONAL LINES
AND THE SUBDIVISION OF CERTAIN SECTIONS
TOWNSHIP 41 NORTH, RANGE 27 EAST,
OF THE GILA AND SALT RIVER MERIDIAN,
IN THE STATE OF ARIZONA.

EXECUTED BY

Craig S. Dukart, Cadastral Surveyor

Under Special Instructions dated April 28, 2011, approved April 28, 2011, which provided for the surveys included under Group No. 1095, and assignment instructions dated April 28, 2011.

Survey commenced May 4, 2011

Survey completed June 15, 2011

INDEX DIAGRAM

TOWNSHIP 41 NORTH RANGE 27 EAST
GILA AND SALT RIVER MERIDIAN, ARIZONA

11	10	10	10	9	9
8 6 47	5 38	4 32	3 25	2 19	1
46	46	37	31	25	18
7 7 45	8 37	9 31	10 24	11 17	12
45	44	36	30	24	17
6 18 43	17 35	16 29	15 23	14 16	13
43	43	35	29	22	15
6 19 42	20 34	21 28	22 22	23 14	24
41	41	34	28	21	14
5 30 40	29 33	28 27	27 20	26 13	25
40	39	33	27	20	13
4 31 38	32 32	33 26	34 19	35 12	36

Subdivision of Section 13	Pages 47-48
Subdivision of Section 14	Pages 48-49
Subdivision of Section 15	Pages 49-50
Subdivision of Section 16	Pages 50-51
Subdivision of Section 17	Pages 51-52
Subdivision of Section 18	Pages 52-53

T. 41 N., R. 27 E., Gila and Salt River Meridian, Arizona

CHAINS

The following field notes describe the dependent resurvey of the north and west boundaries and the survey of the subdivisional lines, and the subdivision of certain sections, Township 41 North, Range 27 East, Gila and Salt River Meridian, Arizona.

The history of surveys pertaining to this survey is as follows:

The Tenth Standard Parallel North (South boundary), the east, west and north boundaries, Township 41 North, Range 27 East, Gila and Salt River Meridian, were surveyed by Horace G. Parker, Cartographer Cadastral, in 1953.

The Tenth Standard Parallel North (South boundary), Township 41 North, Range 27 East, Gila and Salt River Meridian, was dependently resurveyed by Leonard R. Sandoval, Cadastral Surveyor, in 2000.

The west boundary, Township 41 North, Range 28 East, Gila and Salt River Meridian, was dependently resurveyed by Craig S. Dukart, Cadastral Surveyor, in 2008.

The survey was executed in accordance with the specifications as set forth in the Manual of Instructions (2009), and the Special Instructions dated April 28, 2011, for Group Number 1095, Arizona.

The true meridian direction and length of all lines were determined by real time kinematic global positioning system observations using Trimble Navigation 5700, 5800 and R8 model receivers.

Preliminary to the resurvey, the lines of the prior surveys were retraced and search was made for all corners. Identified corners were remonumented in their original positions. Lost corners were reestablished and remonumented at proportionate positions based on the official record.

The retracement data were thoroughly verified and only true line field notes are given herein.

The "standard monument" referred to in these notes is a stainless steel post, 28 ins. long, 2 1/2 ins. diam., with a brass cap. Unless otherwise indicated, a magnet in a white plastic case is deposited at the base of the stainless steel post.

T. 41 N., R. 27 E., Gila and Salt River Meridian, Arizona

CHAINS

Geodetic control was derived from Global Positioning System (GPS) static observations post processed by National Geodetic Survey, Online Positioning User Service (OPUS), utilizing Continuously Operating Reference Stations (CORS) DI2245 P011 SPIDERROCKAZ2005 CORS ARP, DI3419 P012 MONTICELLOUT2006 CORS ARP, AI0265 AZCN AZTEC CORS ARP and DL3642 MC09 NUCLA CORS ARP. The NAD 83 (CORS96) (EPOCH: 2002), geographic position of the following two corners.

The southeast corner of the township is as follows:

Latitude: 36°54'31.56" N. Longitude: 109°23'28.62" W.

The southwest corner of the township is as follows:

Latitude: 36°54'31.53" N. Longitude: 109°29'58.64" W.

The mean magnetic declination is 10 1/2° E.

**Dependent Resurvey of the West Boundary,
T. 41 N., R. 27 E., Gila and Salt River Meridian, Arizona**

Restoring the survey executed by
Horace G. Parker, in 1953

Beginning at the stan. cor. of T. 41 N., Rs. 26 and 27 E., monumented with an stainless steel post, 2 1/2 ins. diam., firmly set, projecting 5 ins. above the ground, with brass cap mkd. SC T41N R26E R27E S36 S31 2000, with a mound of stone, 2 ft. base, 1 ft. high, N. of cor.

Add the marks 2011 to the brass cap.

From this cor. point, the closing corner of T. 40 N., Rs. 26 and 27 E., bears S. 89°58' E., 1.99 chs. dist., monumented with a stainless steel post, firmly set, projecting 6 ins. above the ground, with brass cap mkd. T41N R27E S31 S1 S6 R26E R27E CC T40N 2000. Add the marks 2011 to the brass cap.

North, on the W. bdy. of sec. 36.

Over rolling terrain.

40.00

The point for the 1/4 sec. cor. of secs. 31 and 36, determined at proportionate dist.; there is no remaining evidence of the orig. cor.

Set a standard monument, 25 ins. in the ground, mkd.

Dependent Resurvey of the West Boundary
T. 41 N., R. 27 E., Gila and Salt River Meridian, Arizona

CHAINS	
	<p style="text-align: center;">T 41 N R 26 E R 27 E 1/4 S 36 S 31 2011</p> <p>Over rolling terrain.</p>
80.00	<p>The cor. of secs. 25, 30, 31 and 36, determined 1 lk. E. of a scattered mound of stone, and is accepted as the best available evidence of the orig. cor. position.</p> <p>At the corner point</p> <p>Set a standard monument, 25 ins. in the ground, mkd.</p>
	<p style="text-align: center;">T 41 N R 26 E R 27 E S 25 S 30 S 36 S 31 2011</p> <p>Rebuild the mound of stone, 3 ft. base, 2 ft. high, W. of cor.</p> <hr/>
	<p>N. 0°01' W., on the W. bdy. of sec. 30.</p> <p>Over rolling terrain.</p>
40.01	<p>Point for the 1/4 sec. cor. of secs. 25 and 30, determined 1 lk. E. of a mound of stone, 3 ft. base, 1 ft. high, and is accepted as the best available evidence of the orig. cor. position.</p> <p>At the corner point</p> <p>Set a standard monument, 24 ins. in the ground, mkd.</p>
	<p style="text-align: center;">T 41 N R 26 E R 27 E 1/4 S 25 S 30 2011</p> <p>In lieu of a magnet, deposit 4 eight inch long nails, at the base of the stainless steel post.</p> <hr/> <p>N. 0°05' W., beginning new measurement.</p>

Dependent Resurvey of the West Boundary
T. 41 N., R. 27 E., Gila and Salt River Meridian, Arizona

CHAINS											
	Over rolling terrain.										
39.99	Point for the cor. of secs. 19, 24, 25 and 30, determined 1 lk. E. of a mound of stone, 3 ft. base, 1 1/2 ft. high, and is accepted as the best available evidence of the orig. cor. position. At the corner point Set a standard monument, 24 ins. in the ground, mkd.										
	<table style="margin-left: auto; margin-right: auto;"> <tr><td colspan="2">T 41 N</td></tr> <tr><td>R 26 E</td><td>R 27 E</td></tr> <tr><td>S 24</td><td>S 19</td></tr> <tr><td colspan="2"><hr/></td></tr> <tr><td>S 25</td><td>S 30</td></tr> </table>	T 41 N		R 26 E	R 27 E	S 24	S 19	<hr/>		S 25	S 30
T 41 N											
R 26 E	R 27 E										
S 24	S 19										
<hr/>											
S 25	S 30										
	2011										
	Rebuild the mound of stone, 3 ft. base, 2 ft. high.										
	<hr/>										
	N. 0°04' E., on the W. bdy. of sec. 19.										
	Over rolling terrain.										
39.96	The 1/4 sec. cor. of secs. 19 and 24, monumented with an iron post, 2 1/2 ins. diam., firmly set, projecting 24 ins. above the ground, in a mound of stone, 4 ft. base, 1 1/2 ft. high, with brass cap mkd. 1/4 S24 S19 1953. Add the marks T41N R26E R27E 2011 to the brass cap.										
	<hr/>										
	N. 0°01' E., beginning new measurement.										
	Over rolling terrain.										
39.99	The cor. of secs. 13, 18, 19 and 24, monumented with an iron post, 2 1/2 ins. diam., firmly set, projecting 11 ins. above the ground, with brass cap mkd. T41N R26E R27E S13 S18 S24 S19 1953, with a scattered mound of stone, W. of the cor. Add the marks 2011 to the brass cap.										
	<hr/>										
	N. 0°01' W., on the W. bdy. of sec. 18.										
	Over rolling terrain.										
20.55	High voltage transmission line, bears N. 54° E. and S. 54° W.										

Dependent Resurvey of the West Boundary
T. 41 N., R. 27 E., Gila and Salt River Meridian, Arizona

CHAINS	
25.05	South Right-of-Way fence, barbed wire, bears N. 65° E. and S. 65° W.
26.70	U.S. Highway No. 160, asphalt surfaced, 30 ft. wide, bears N. 65° E. and S. 65° W.
30.05	North Right-of-Way fence, barbed wire, bears N. 65° E. and S. 65° W.
40.05	The 1/4 sec. cor. of secs. 13 and 18, monumented with an iron post, 2 1/2 ins. diam., firmly set, projecting 8 ins. above the ground, with brass cap mkd. 1/4 S13 S18 1953, with a mound of stone, 3 ft. diam., 1 1/2 ft. high, W. of cor. Add the marks T41N R26E R27E 2011 to the brass cap. <hr style="width: 20%; margin: auto;"/> North, beginning new measurement. Over rolling terrain.
40.03	The cor. of secs. 7, 12, 13 and 18, monumented with an iron post, 2 1/2 ins. diam., firmly set, 3 ins. below the ground, with brass cap mkd. T41N R26E R27E S12 S7 S13 S18 1953, with a mound of stone, 4 ft. base, 1 ft. high, W. of the cor. Add the marks 2011 to the brass cap. <hr style="width: 20%; margin: auto;"/> N. 0°02' W., on the W. bdy. of sec. 7. Over rolling terrain.
6.65	Graded road, 25 ft. wide, bears S. 40° E. and N. 40° W.
37.60	Trail road, bears N. 25° E. and S. 25° W.
40.02	Point for the 1/4 sec. cor. of secs. 7 and 12; determined by shards of clear broken glass. At the corner point Set a standard monument, 25 ins. in the ground, mkd. <div style="text-align: center;">T 41 N 1/4 R 26 E R 27 E S 12 S 7 2011</div> <hr style="width: 20%; margin: auto;"/>

**Dependent Resurvey of the West Boundary
T. 41 N., R. 27 E., Gila and Salt River Meridian, Arizona**

CHAINS	
	N. 0°02' E., beginning new measurement. Over rolling terrain.
40.02	The cor. of secs. 1, 6, 7 and 12, monumented with an iron post, 2 1/2 ins. diam., firmly set, leaning, projecting 11 ins. above the ground, with brass cap mkd. T41N R26E R27E S1 S6 S12 S7 1953. Reset the orig. concrete filled iron post, 30 ins. long, 25 ins. in the ground. Deposit a magnet, in a white plastic case, at the base of the stainless steel post. Add the marks 2011 to the brass cap. <hr/>
	N. 0°01' W., on the W. bdy. of sec. 6. Over rolling terrain.
38.85	Underground pipeline, bears N. 75° E. and S. 75° W.
39.10	Trail road, bears N. 75° E. and S. 75° W.
40.025	The 1/4 sec. cor. of secs. 1 and 6, monumented with an iron post, 2 1/2 ins. diam., firmly set, projecting 5 ins. above the ground, with brass cap mkd. 1/4 S1 S6 1953. Add the marks T41N R26E R27E 2011 to the brass cap. <hr/>
	North, beginning new measurement. Over rolling terrain.
14.55	Trail road, bears S. 65° E. and N. 65° W.
17.35	Trail road, bears N. 25° E. and S. 25° W.
40.02	The cor. of Tps. 41 and 42 N., Rs. 26 and 27 E., monumented with an iron post, 2 1/2 ins. diam., firmly set, projecting 11 ins. above the ground, with brass cap mkd. T42N R26E R27E S36 S31 S1 S6 T41N 1953. Add the marks 2011 to the brass cap. <hr/>
Dependent Resurvey of the North Boundary, T. 41 N., R. 27 E., Gila and Salt River Meridian, Arizona	

Dependent Resurvey of the North Boundary
T. 41 N., R. 27 E., Gila and Salt River Meridian, Arizona

CHAINS	
	<p style="text-align: center;">Restoring the survey executed by Horace G. Parker in 1953</p> <hr/> <p>From the cor. of Tps. 41 and 42 N., Rs. 27 and 28 E., monumented with an iron post, 2 1/2 ins. diam., firmly set, 14 ins. below the ground, with brass cap mkd. T42N R27E R28E S36 S31 S1 S6 T41N 1953 2008.</p> <p>Add the marks 2011 to the brass cap.</p> <p>West, bet. secs. 1 and 36.</p> <p>Over rolling terrain.</p>
40.005	<p>The 1/4 sec. cor. of secs. 1 and 36, monumented with an iron post, 2 1/2 ins. diam., firmly set, projecting 6 ins. above the ground, with brass cap mkd. 1/4 S36 S1 1953, with a mound of stone, 2 ft. base, 1 ft. high, N. of cor.</p> <p>Add the marks T42N R27E T41N 2011 to the brass cap.</p> <hr/> <p>West, beginning new measurement.</p>
40.015	<p>The cor. of secs. 1, 2, 35 and 36, monumented with an iron post, 2 1/2 ins. diam., firmly set, flush with the ground, with brass cap mkd. T42N R27E S35 S36 S2 S1 T41N 1953, with a mound of stone, 2 ft. base, 1 ft. high, N. of cor.</p> <p>Add the marks 2011 to the brass cap.</p> <hr/> <p>S. 89°59' W., bet. secs. 2 and 35.</p> <p>Over rolling terrain.</p>
40.02	<p>The 1/4 sec. cor. of secs. 2 and 35, monumented with an iron post, 2 1/2 ins. diam., firmly set, projecting 5 ins. above the ground, with brass cap mkd. 1/4 S35 S2 1953.</p> <p>Add the marks T42N R27E T41N 2011 to the brass cap.</p> <hr/> <p>S. 89°59' W., beginning new measurement.</p>
40.02	<p>The cor. of secs. 2, 3, 34 and 35, monumented with an iron post, 2 1/2 ins. diam., firmly set, projecting 1 in. above the ground, with brass cap mkd. T42N R27E S34 S35 S3 S2 T41N 1953.</p> <p>Add the marks 2011 to the brass cap.</p> <hr/>

**Dependent Resurvey of the North Boundary
T. 41 N., R. 27 E., Gila and Salt River Meridian, Arizona**

CHAINS	
	West, bet. secs. 3 and 34. Over rolling terrain.
39.97	The 1/4 sec. cor. of secs. 3 and 34, monumented with an iron post, 2 1/2 ins. diam., firmly set, projecting 1 in. above the ground, with brass cap mkd. 1/4 S34 S3 1953. Add the marks T42N R27E T41N 2011 to the brass cap. <hr/>
	West, beginning new measurement.
40.005	The cor. of secs. 3, 4, 33 and 34, monumented with an iron post, 2 1/2 ins. diam., firmly set, projecting 1 in. above the ground, with brass cap mkd. T42N R27E S33 S34 S4 S3 T41N 1953. Add the marks 2011 to the brass cap. <hr/>
	West, bet. secs. 4 and 33. Over rolling terrain.
2.05	Graded road, 25 ft. wide, bears S. 15° E. and N. 15° W.
40.02	The 1/4 sec. cor. of secs. 4 and 33, monumented with an iron post, 2 1/2 ins. diam., firmly set, projecting 8 ins. above the ground, with brass cap mkd. 1/4 S33 S4 1953. Add the marks T42N R27E T41N 2011 to the brass cap. <hr/>
	West, beginning new measurement.
40.015	The cor. of secs. 4, 5, 32 and 33, monumented with an iron post, 2 1/2 ins. diam., firmly set, leaning, projecting 18 ins. above the ground, with brass cap mkd. T42N R27E S32 S33 S5 S4 T41N 1953, with a scattered mound of stone, N. of cor. Reset the concrete filled iron post, 30 ins. long, 2 1/2 ins. diam., 25 ins. in the ground, in a collar of stone. Add the marks 2011 to the brass cap. <hr/>
	West, bet. secs. 5 and 32. Over rolling terrain.
1.35	Underground gas pipeline, bears N. 75° E. and S. 75° W.
2.00	Graded road, 10 ft. wide, bears N. 75° E. and S. 75° W.

**Dependent Resurvey of the North Boundary
T. 41 N., R. 27 E., Gila and Salt River Meridian, Arizona**

CHAINS	
29.40	Trail road, bears N. 15° E. and S. 20° W.
40.015	Point for the 1/4 sec. cor. of secs. 5 and 32; determined by shards of clear broken glass. The orig. iron post was found laying loose on the ground approximately 45 ft. away. At the corner point Set the orig., concrete filled iron post, 30 ins. long, 2 1/2 ins. diam., 27 ins. in the ground, with brass cap mkd. 1/4 S32 S5 1953. Deposit a magnet, in a white plastic case, at the base of the iron post. Add the marks T42N R27E T41N 2011 to the brass cap. <hr style="width: 20%; margin: auto;"/>
	West, beginning new measurement.
40.00	The cor. of secs. 5, 6, 31 and 32, monumented with an iron post, 2 1/2 ins. diam., firmly set, projecting 4 ins. above the ground, with brass cap mkd. T42N R27E S31 S32 S6 S5 1953, with a mound of stone, 3 ft. base, 1/2 ft. high, W. of cor. Add the marks 2011 to the brass cap. <hr style="width: 20%; margin: auto;"/>
	West, bet. secs. 6 and 31. Over rolling terrain.
40.025	The 1/4 sec. cor. of secs. 6 and 31, monumented with an iron post, 2 1/2 ins. diam., firmly set, projecting 11 ins. above the ground, with brass cap mkd. 1/4 S31 S6 1953. Add the marks T42N R27E T41N 2011 to the brass cap. <hr style="width: 20%; margin: auto;"/>
	S. 89°59' W., beginning new measurement. Over rolling terrain.
29.20	Trail road, bears N. 25° E. and S. 25° W.
39.45	The cor. of Tps. 41 and 42 N., Rs. 26 and 27 E., hereinbefore described. <hr style="width: 20%; margin: auto;"/>
	Survey of the Subdivisional Lines, T. 41 N., R. 27 E., Gila and Salt River Meridian, Arizona

Survey of the Subdivisional Lines,
T. 41 N., R. 27 E., Gila and Salt River Meridian, Arizona

CHAINS					
	<p>From the stan. cor. of secs. 35 and 36, monumented with a stainless steel post, 2 1/2 ins. diam., firmly set, projecting 5 ins. above the ground, with brass cap mkd. SC T41N R27E S35 S36 2000, with a mound of stone, 3 ft. base, 2 ft. high, N. of cor., from which the orig. bearing trees</p> <p style="padding-left: 40px;">A piñon pine, 8 ins. diam., bears N. 80 1/4° E., 1.02 chs. dist., with scribe marks 41N R 7 BT visible on a partially healed blaze. (record: N. 72°03' E., 1.03 chs.)</p> <p style="padding-left: 40px;">A piñon pine, 6 ins. diam., bears N. 7 1/4° W., 1.58 chs. dist., with scribe marks 41N R27E visible on a partially healed blaze. (record: N. 16°24' W., 1.56 chs.)</p> <p>Add the marks 2011 to the brass cap.</p> <p>North, bet. secs. 35 and 36.</p> <p>Over level terrain across the top of Toh Atin Mesa.</p>				
7.95	Abandoned trail road, bears S. 70° E. and N. 70° W.				
24.30	Northerly edge of Toh Atin Mesa, bears N. 85° E. and S. 85° W.; continue over rugged terrain.				
40.00	<p>Point for the 1/4 sec. cor. of secs. 35 and 36.</p> <p>Set a standard monument, 16 ins. in the ground, in a mound of stone, 4 ft. base, to brass cap mkd.</p> <div style="text-align: center;"> <p>T 41 N R 27 E</p> <p style="margin-left: 40px;">1/4</p> <p style="margin-left: 40px;">S 35 S 36</p> <p style="margin-left: 40px;">2011</p> </div>				
80.00	<p>Point for the cor. of secs. 25, 26, 35 and 36.</p> <p>Set a standard monument, 25 ins. in the ground, mkd.</p> <div style="text-align: center;"> <p>T 41 N R 27 E</p> <table style="margin-left: auto; margin-right: auto;"> <tr> <td style="border-right: 1px solid black; padding: 0 5px;">S 26</td> <td style="padding: 0 5px;">S 25</td> </tr> <tr> <td style="border-right: 1px solid black; padding: 0 5px;">S 35</td> <td style="padding: 0 5px;">S 36</td> </tr> </table> <p style="margin-left: 40px;">2011</p> </div> <p>Terrain, level to broken and rugged. Soil, sand and rock. Timber, occasional scattered juniper. Undergrowth, various desert vegetation.</p> <hr style="width: 60%; margin-left: 0;"/>	S 26	S 25	S 35	S 36
S 26	S 25				
S 35	S 36				

Survey of the Subdivisional Lines,
T. 41 N., R. 27 E., Gila and Salt River Meridian, Arizona

CHAINS	
	<p>From the cor. of secs. 25, 30, 31 and 36, on the E. bdy. of the Tp., monumented with an iron post, 2 1/2 ins. diam., firmly set, projecting 5 ins. above the ground, with brass cap mkd. T41N R27E R28E S25 S30 S36 S31 2008 1953, with a "T-Post" fence post nearby.</p> <p>Add the marks 2011 to the brass cap.</p> <p>West, bet. secs. 25 and 36.</p> <p>Over rugged terrain.</p>
39.995	<p>Point for the 1/4 sec. cor. of secs. 25 and 36.</p> <p>Set a standard monument, 25 ins. in the ground, mkd.</p> <div style="text-align: center;"> <p>T 41 N R 27 E</p> <p>S 25</p> <p>1/4 ———</p> <p>S 36</p> <p>2011</p> </div>
79.99	<p>The cor. of secs. 25, 26, 35 and 36.</p> <p>Terrain, broken and rugged: Soil, sand and rock. Timber, occasional scattered juniper. Undergrowth, various desert vegetation.</p> <hr/> <p>North, bet. secs. 25 and 26.</p> <p>Over rugged terrain.</p>
40.00	<p>Point for the 1/4 sec. cor. of secs. 25 and 26.</p> <p>Set a standard monument, 25 ins. in the ground, mkd.</p> <div style="text-align: center;"> <p>T 41 N R 27 E</p> <p>1/4</p> <p>S 26 S 25</p> <p>2011</p> </div>
80.00	<p>Point for the cor. of secs. 23, 24, 25 and 26.</p> <p>Set a standard monument, 25 ins. in the ground, mkd.</p>

Survey of the Subdivisional Lines,
T. 41 N., R. 27 E., Gila and Salt River Meridian, Arizona

CHAINS	
	<p style="text-align: center;">T 41 N R 27 E S 23 S 24 S 26 S 25</p> <p style="text-align: center;">2011</p> <p>Terrain, rugged to rolling. Soil, sand. Timber, none. Undergrowth, various desert vegetation.</p> <hr/> <p>From the cor. of secs. 19, 24, 25 and 30, on the E. bdy. of the Tp., monumented with a stainless steel post, 2 1/2 ins. diam., firmly set, projecting 6 ins. above the ground, with brass cap mkd. T41N R27E R28E S24 S19 S25 S30 2008, with a "T-Post" fence post nearby.</p> <p>Add the marks 2011 to the brass cap.</p> <p>S. 89°58' W., bet. secs. 24 and 25.</p> <p>Over rolling terrain.</p>
40.00	<p>Point for the 1/4 sec. cor. of secs. 24 and 25.</p> <p>Set a standard monument, 25 ins. in the ground, mkd.</p> <p style="text-align: center;">T 41 N R 27 E S 24 1/4 ——— S 25</p> <p style="text-align: center;">2011</p>
80.00	<p>The cor. of secs. 23, 24, 25 and 26.</p> <p>Terrain, rolling. Soil, sand. Timber, none. Undergrowth, various desert vegetation.</p> <hr/> <p>North, bet. secs. 23 and 24.</p> <p>Over rolling terrain.</p>
40.00	<p>Point for the 1/4 sec. cor. of secs. 23 and 24.</p> <p>Set a standard monument, 26 ins. in the ground, mkd.</p>

Survey of the Subdivisional Lines,
T. 41 N., R. 27 E., Gila and Salt River Meridian, Arizona

CHAINS	
	<p style="text-align: center;">T 41 N R 27 E 1/4 S 23 S 24</p> <p style="text-align: center;">2011</p>
80.00	<p>Point for the cor. of secs. 13, 14, 23 and 24.</p> <p>Set a standard monument, 27 ins. in the ground, mkd.</p> <p style="text-align: center;">T 41 N R 27 E S 14 S 13 S 23 S 24</p> <p style="text-align: center;">2011</p> <p>From this cor. point, a cor. set by persons unknown, bears N. 26°55' E., 6 1/2 lks. dist., monumented with an open ended iron pipe, 2 ins. diam., firmly set, projecting 8 ins. above the ground, mkd. T41N R27E 14 13 23 34 on southerly side of pipe.</p> <p>Terrain, rolling. Soil, sand. Timber, none. Undergrowth, various desert vegetation.</p> <hr/> <p>From the cor. of secs. 13, 18, 19 and 24, on the E. bdy. of the Tp., monumented with an iron post, 2 1/2 ins. diam., firmly set, projecting 4 ins. above the ground, with brass cap mkd. T41N R27E R28E S13 S18 S24 S19 1953 2008, with a "T-Post" fence post nearby.</p> <p>Add the marks 2011 to the brass cap.</p> <p>S. 89°58' W., bet. secs. 13 and 24.</p> <p>Over rolling terrain.</p>
14.20	<p>Trail road, bears N. 35° E. and S. 35° W.</p>
40.005	<p>Point for the 1/4 sec. cor. of secs. 13 and 24.</p> <p>Set a standard monument, 25 ins. in the ground, mkd.</p> <p style="text-align: center;">T 41 N R 27 E S 13 1/4 ——— S 24</p> <p style="text-align: center;">2011</p>

Survey of the Subdivisional Lines,
T. 41 N., R. 27 E., Gila and Salt River Meridian, Arizona

CHAINS	
	From this cor. point, the pump shaft of a windmill, bears S. 2°05' E., 30.87 chs. dist., with a water tank, approximately 25 ft. diam., nearby.
47.20	Graded road, 12 ft. wide, bears N. 15° E. and S. 15° W.
80.01	The cor. of secs. 13, 14, 23 and 24.
	Terrain, rolling. Soil, sand. Timber, none. Undergrowth, various desert vegetation.
	North, bet. secs. 13 and 14.
	Over rolling terrain.
26.20	High voltage transmission line, bears S. 85° E. and N. 85° W.
40.00	Point for the 1/4 sec. cor. of secs. 13 and 14.
	Set a standard monument, 25 ins. in the ground, mkd.
	T 41 N R 27 E 1/4 S 14 S 13 2011
50.30	Underground waterline, bears E. and W.
50.70	South Right-of-Way fence, barbed wire, bears S. 88° E. and N. 88° W.
52.20	U.S. Highway No. 160, asphalt surfaced, 35 ft. wide, bears S. 88° E. and N. 88° W.
55.25	North Right-of-Way fence, barbed wire, bears S. 88° E. and N. 88° W.
80.00	Point for the cor. of secs. 11, 12, 13 and 14.
	Set a standard monument, 26 ins. in the ground, mkd.
	T 41 N R 27 E S 11 S 12 S 14 S 13 2011

Survey of the Subdivisional Lines,
T. 41 N., R. 27 E., Gila and Salt River Meridian, Arizona

CHAINS	
	<p>Terrain, rolling. Soil, sand. Timber, none. Undergrowth, various desert vegetation.</p> <hr/> <p>From the cor. of secs. 7, 12, 13 and 18, on the E. bdy. of the Tp., monumented with a concrete filled iron post, 2 ins. diam., firmly set, projecting 7 ins. above the ground, with brass cap mkd. R41N 2007 T27E T28E S12 S7 S13 S18 LS15083.</p> <p>Add the marks 2011 to the brass cap.</p> <p>S. 89°57' W., bet. secs. 12 and 13.</p> <p>Over rolling terrain.</p>
16.10	Graded road, 12 ft. wide, bears N. 5° E. and S. 5° W.
31.45	Trail road, bears N. and S. 10° W.
40.005	Point for the 1/4 sec. cor. of secs. 12 and 13.
	Set a standard monument, 25 ins. in the ground, mkd.
	<p>T 41 N R 27 E S 12 1/4 ——— S 13</p> <p>2011</p>
80.01	The cor. of secs. 11, 12, 13 and 14.
	<p>Terrain, rolling. Soil, sand. Timber, none. Undergrowth, various desert vegetation.</p> <hr/> <p>North, bet. secs. 11 and 12.</p> <p>Over rolling terrain.</p>
40.00	Point for the 1/4 sec. cor. of secs. 11 and 12.
	Set a standard monument, 25 ins. in the ground, mkd.

Survey of the Subdivisional Lines,
T. 41 N., R. 27 E., Gila and Salt River Meridian, Arizona

CHAINS	
80.00	<p style="text-align: center;">T 41 N R 27 E 1/4 S 11 S 12</p> <p style="text-align: center;">2011</p> <p>Point for the cor. of secs. 1, 2, 11 and 12.</p> <p>Set a standard monument, 24 ins. in the ground, mkd.</p> <p style="text-align: center;">T 41 N R 27 E S 2 S 1 S 11 S 12</p> <p style="text-align: center;">2011</p> <p>Terrain, rolling. Soil, sand. Timber, none. Undergrowth, various desert vegetation.</p> <hr/> <p>From the cor. of secs. 1, 6, 7 and 12, on the E. bdy. of the Tp., monumented with an iron post, 2 1/2 ins. diam., firmly set, projecting 3 ins. above the ground, with brass cap mkd. T41N R27E R28E S1 S6 S12 S7 2008 1953, with a "T-Post" fence post nearby.</p> <p>Add the marks 2011 to the brass cap.</p> <p>S. 89°57' W., bet. secs. 1 and 12.</p> <p>Over rolling terrain.</p>
40.005	<p>Point for the 1/4 sec. cor. of secs. 1 and 12.</p> <p>Set a standard monument, 23 ins. in the ground, mkd.</p> <p style="text-align: center;">T 41 N R 27 E S 1 1/4 ——— S 12</p> <p style="text-align: center;">2011</p>
80.01	<p>The cor. of secs. 1, 2, 11 and 12.</p> <p>Terrain, rolling. Soil, sand. Timber, none. Undergrowth, various desert vegetation.</p> <hr/>

Survey of the Subdivisional Lines,
T. 41 N., R. 27 E., Gila and Salt River Meridian, Arizona

CHAINS	
	N. 0°02' W., bet. secs. 1 and 2. Over rolling terrain.
40.00	Point for the 1/4 sec. cor. of secs. 1 and 2. Set a standard monument, 25 ins. in the ground, mkd. <div style="text-align: center;"> T 41 N R 27 E 1/4 S 2 S 1 2011 </div>
80.08	The cor. of secs. 1, 2, 35 and 36, hereinbefore described. Terrain, rolling. Soil, sand. Timber, none. Undergrowth, various desert vegetation. <hr/> From the stan. cor. of secs. 34 and 35, monumented with an iron post, 2 1/2 ins. diam., firmly set, projecting 11 ins. above the ground, with brass cap mkd. SC T41N R27E S34 S35 2000 1953, with a mound of stone, 3 ft. base, 2 ft. high, N. of cor. Add the marks 2011 to the brass cap. N. 0°01' W., bet. secs. 34 and 35. Over rugged terrain.
32.25	Southerly edge of Toh Atin Mesa, bears S. 85° E. and N. 85° W.; continue over rugged terrain.
40.00	Point for the 1/4 sec. cor. of secs. 34 and 35. Set a standard monument, 25 ins. in the ground, mkd. <div style="text-align: center;"> T 41 N R 27 E 1/4 S 34 S 35 2011 </div>
46.60	Northerly edge of Toh Atin Mesa, bears N. 65° E. and S. 65° W.; continue over rugged terrain.
80.00	Point for the cor. of secs. 26, 27, 34 and 35. Set a standard monument, 25 ins. in the ground, mkd.

Survey of the Subdivisional Lines,
T. 41 N., R. 27 E., Gila and Salt River Meridian, Arizona

CHAINS									
	<table style="margin-left: auto; margin-right: auto;"> <tr><td>T 41 N</td><td>R 27 E</td></tr> <tr><td>S 27</td><td>S 26</td></tr> <tr><td>S 34</td><td>S 35</td></tr> </table>	T 41 N	R 27 E	S 27	S 26	S 34	S 35		
T 41 N	R 27 E								
S 27	S 26								
S 34	S 35								
	2011								
	<p>From this cor. point, a cor. set by persons unknown, bears N. 19°50' E., 12 1/2 lks. dist., monumented with an open ended iron pipe, 2 ins. diam., firmly set, projecting 12 ins. above the ground, mkd. T41N R27E 27 26 34 35 on southwesterly side of pipe.</p>								
	<p>From this same cor. point, a cor. set by persons unknown, bears N. 61°53' W., 17 1/2 lks. dist., monumented with a copperweld, firmly set, projecting 12 ins. above the ground, with cap mkd. 27 26 34 35.</p>								
	<p>Terrain, broken and rugged. Soil, sand and rock. Timber, occasional scattered juniper. Undergrowth, various desert vegetation.</p>								
	<hr/> <p>From the cor. of secs. 25, 26, 35 and 36.</p>								
	<p>N. 89°58' W., bet. secs. 26 and 35.</p>								
	<p>Over rugged terrain.</p>								
40.00	<p>Point for the 1/4 sec. cor. of secs. 26 and 35.</p> <p>Set a standard monument, 25 ins. in the ground, mkd.</p>								
	<table style="margin-left: auto; margin-right: auto;"> <tr><td>T 41 N</td><td>R 27 E</td></tr> <tr><td>S 26</td><td></td></tr> <tr><td>1/4</td><td>—</td></tr> <tr><td>S 35</td><td></td></tr> </table>	T 41 N	R 27 E	S 26		1/4	—	S 35	
T 41 N	R 27 E								
S 26									
1/4	—								
S 35									
	2011								
80.00	<p>The cor. of secs. 26, 27, 34 and 35.</p> <p>Terrain, broken and rugged. Soil, sand and rock. Timber, occasional scattered juniper. Undergrowth, various desert vegetation.</p>								
	<hr/> <p>N. 0°01' W., bet. secs. 26 and 27.</p>								
	<p>Over rugged terrain.</p>								
40.00	<p>Point for the 1/4 sec. cor. of secs. 26 and 27.</p>								

Survey of the Subdivisional Lines,
T. 41 N., R. 27 E., Gila and Salt River Meridian, Arizona

CHAINS	
	<p>Set a standard monument, 25 ins. in the ground, mkd.</p> <p style="text-align: center;">T 41 N R 27 E 1/4 S 27 S 26</p> <p style="text-align: center;">2011</p>
80.00	<p>Point for the cor. of secs. 22, 23, 26 and 27.</p> <p>Set a standard monument, 24 ins. in the ground, mkd.</p> <p style="text-align: center;">T 41 N R 27 E S 22 S 23 S 27 S 26</p> <p style="text-align: center;">2011</p> <p>From this cor. point, a cor. set by persons unknown, bears N. 70°38' E., 5 lks. dist., monumented with an open ended iron pipe, 2 ins. diam., firmly set, projecting 6 ins. above the ground, mkd. T41N R27E 22 23 27 26 on southeasterly side of pipe.</p> <p>Terrain, broken and rugged to rolling. Soil, sand and rock. Timber, none. Undergrowth, various desert vegetation.</p> <hr/> <p>From the cor. of secs. 23, 24, 25 and 26.</p> <p>N. 89°58' W., bet. secs. 23 and 26.</p> <p>Over rolling terrain.</p>
39.995	<p>Point for the 1/4 sec. cor. of secs. 23 and 26.</p> <p>Set a standard monument, 25 ins. in the ground, mkd.</p> <p style="text-align: center;">T 41 N R 27 E S 23 1/4 ——— S 26</p> <p style="text-align: center;">2011</p>
79.99	<p>The cor. of secs. 22, 23, 26 and 27.</p>

Survey of the Subdivisional Lines,
T. 41 N., R. 27 E., Gila and Salt River Meridian, Arizona

CHAINS	
	<p>Terrain, rolling. Soil, sand. Timber, none. Undergrowth, various desert vegetation.</p> <hr/> <p>N. 0°01' W., bet. secs. 22 and 23.</p> <p>Over rolling terrain.</p>
40.00	<p>Point for the 1/4 sec. cor. of secs. 22 and 23.</p> <p>Set a standard monument, 25 ins. in the ground, mkd.</p> <p style="text-align: center;">T 41 N R 27 E 1/4 S 22 S 23 2011</p>
80.00	<p>Point for the cor. of secs. 14, 15, 22 and 23.</p> <p>Set a standard monument, 22 ins. in the ground, mkd.</p> <p style="text-align: center;">T 41 N R 27 E S 15 S 14 S 22 S 23 2011</p> <p>From this cor. point, a cor. set by persons unknown, bears N. 81°06' E., 6 lks. dist., monumented with an open ended iron pipe, 2 ins. diam., firmly set, projecting 14 ins. above the ground, mkd. T41N R27E 15 14 22 23 on southeasterly side of pipe.</p> <p>Terrain, rolling. Soil, sand. Timber, none. Undergrowth, various desert vegetation.</p> <hr/> <p>From the cor. of secs. 13, 14, 23 and 24.</p> <p>N. 89°58' W., bet. secs. 14 and 23.</p> <p>Over rolling terrain.</p>
39.995	<p>Point for the 1/4 sec. cor. of secs. 14 and 23.</p> <p>Set a standard monument, 27 ins. in the ground, mkd.</p>

Survey of the Subdivisional Lines,
T. 41 N., R. 27 E., Gila and Salt River Meridian, Arizona

CHAINS	
	<p style="text-align: center;">T 41 N R 27 E S 14 1/4 ——— S 23</p> <p style="text-align: center;">2011</p>
79.99	<p>The cor. of secs. 14, 15, 22 and 23.</p> <p>Terrain, rolling. Soil, sand. Timber, none. Undergrowth, various desert vegetation.</p> <hr/>
	<p>N. 0°01' W., bet. secs. 14 and 15.</p> <p>Over rolling terrain.</p>
31.20	<p>High voltage transmission line, bears S. 86° E. and N. 86° W.</p>
40.00	<p>Point for the 1/4 sec. cor. of secs. 14 and 15.</p> <p>Set a standard monument, 25 ins. in the ground, mkd.</p>
	<p style="text-align: center;">T 41 N R 27 E 1/4 S 15 S 14</p> <p style="text-align: center;">2011</p>
53.90	<p>South Right-of-Way fence, barbed wire, bears S. 88° E. and N. 88° W.</p>
55.40	<p>U.S. Highway No. 160, asphalt surfaced, 35 ft. wide, bears S. 88° E. and N. 88° W.</p>
58.45	<p>North Right-of-Way fence, barbed wire, bears S. 88° E. and N. 88° W.</p>
80.00	<p>Point for the cor. of secs. 10, 11, 14 and 15.</p> <p>Set a standard monument, 25 ins. in the ground, mkd.</p>
	<p style="text-align: center;">T 41 N R 27 E S 10 S 11 ——— S 15 S 14</p> <p style="text-align: center;">2011</p>

Survey of the Subdivisional Lines,
T. 41 N., R. 27 E., Gila and Salt River Meridian, Arizona

CHAINS	
	<p>Terrain, rolling. Soil, sand. Timber, none. Undergrowth, various desert vegetation.</p> <hr/> <p>From the cor. of secs. 11, 12, 13 and 14. N. 89°58' W., bet. secs. 11 and 14. Over rolling terrain.</p>
39.995	<p>Point for the 1/4 sec. cor. of secs. 11 and 14. Set a standard monument, 25 ins. in the ground, mkd.</p> <p style="text-align: center;">T 41 N R 27 E S 11 1/4 ——— S 14 2011</p>
79.99	<p>The cor. of secs. 10, 11, 14 and 15. Terrain, rolling. Soil, sand. Timber, none. Undergrowth, various desert vegetation.</p> <hr/> <p>N. 0°01' W., bet. secs. 10 and 11. Over rolling terrain.</p>
40.00	<p>Point for the 1/4 sec. cor. of secs. 10 and 11. Set a standard monument, 25 ins. in the ground, mkd.</p> <p style="text-align: center;">T 41 N R 27 E 1/4 S 10 S 11 2011</p> <p>From this cor. point, the pump shaft of a windmill, bears S. 66°23' W., 24.66 chs. dist., with a water tank, approximately 25 ft. diam., nearby.</p>
80.00	<p>Point for the cor. of secs. 2, 3, 10 and 11. Set a standard monument, 24 ins. in the ground, mkd.</p>

Survey of the Subdivisional Lines,
T. 41 N., R. 27 E., Gila and Salt River Meridian, Arizona

CHAINS	
	T 41 N R 27 E S 3 S 2 S 10 S 11 2011
	Terrain, rolling. Soil, sand. Timber, none. Undergrowth, various desert vegetation.
	<hr/> From the cor. of secs. 1, 2, 11 and 12. N. 89°58' W., bet. secs. 2 and 11. Over rolling terrain.
39.50	Trail road, bears N. 50° E. and S. 50° W.
39.995	Point for the 1/4 sec. cor. of secs. 2 and 11. Set a standard monument, 25 ins. in the ground, mkd.
	T 41 N R 27 E S 2 1/4 ——— S 11 2011
79.99	The cor. of secs. 2, 3, 10 and 11. Terrain, rolling. Soil, sand. Timber, none. Undergrowth, various desert vegetation.
	<hr/> N. 0°05' W., bet. secs. 2 and 3. Over rolling terrain.
40.00	Point for the 1/4 sec. cor. of secs. 2 and 3. Set a standard monument, 25 ins. in the ground, mkd.
	T 41 N R 27 E 1/4 S 3 S 2 2011

Survey of the Subdivisional Lines,
T. 41 N., R. 27 E., Gila and Salt River Meridian, Arizona

CHAINS	
80.02	<p>The cor. of secs. 2, 3, 34 and 35, hereinbefore described.</p> <p>Terrain, rolling. Soil, sand. Timber, none. Undergrowth, various desert vegetation.</p> <hr/> <p>From the stan. cor. of secs. 33 and 34, monumented with a stainless steel post, 2 1/2 ins. diam., firmly set, projecting 4 ins. above the ground, with brass cap mkd. SC T41N R27E S33 S34 2000.</p> <p>Add the marks 2011 to the brass cap.</p> <p>N. 0°02' W., bet. secs. 33 and 34.</p> <p>Over rugged terrain.</p>
40.00	<p>Point for the 1/4 sec. cor. of secs. 33 and 34.</p> <p>Set a standard monument, 25 ins. in the ground, mkd.</p> <p style="text-align: center;">T 41 N R 27 E 1/4 S 33 S 34</p> <p style="text-align: center;">2011</p> <p>From this cor. point, National Geodetic Survey triangulation station "DINNE", bears N. 43°03' E., 7.398 chs. dist., monumented with a standard tablet, cemented in a rock, 2 x 3 1/2 ft., 1/2 ft. high, mkd. DINNE 1949, from which</p> <p style="padding-left: 40px;">A standard tablet, cemented in a rock, 3 x 4 ft., 1 1/2 ft. high, for a reference monument, bears S. 27°30' W., 28.5 ft. dist., with brass cap mkd. 1 and an arrow pointing to the cor.</p> <p style="padding-left: 40px;">A standard tablet, cemented in a rock, 3 x 5 ft., 1 1/2 ft. high, for a reference monument, bears N. 39°51' W., 13.5 ft. dist., with brass cap mkd. 2 and an arrow pointing to the cor.</p>
80.00	<p>Point for the cor. of secs. 27, 28, 33 and 34.</p> <p>Set a standard monument, 21 ins. in the ground, in a mound of sandstone, 3 ft. base, to brass cap mkd.</p>

Survey of the Subdivisional Lines,
T. 41 N., R. 27 E., Gila and Salt River Meridian, Arizona

CHAINS	
	<p style="text-align: center;">T 41 N R 27 E S 28 S 27 S 33 S 34</p> <p style="text-align: center;">2011</p>
	<p>Terrain, broken and rugged. Soil, sand and rock. Timber, occasional scattered juniper. Undergrowth, various desert vegetation.</p> <hr/>
	<p>From the cor. of secs. 26, 27, 34 and 35.</p> <p>S. 89°56' W., bet. secs. 27 and 34.</p> <p>Over rolling terrain.</p>
40.01	<p>Point for the 1/4 sec. cor. of secs. 27 and 34.</p> <p>Set a standard monument, 25 ins. in the ground, mkd.</p>
	<p style="text-align: center;">T 41 N R 27 E S 27 1/4 ——— S 34</p> <p style="text-align: center;">2011</p>
80.02	<p>The cor. of secs. 27, 28, 33 and 34.</p> <p>Terrain, broken and rugged. Soil, sand and rock. Timber, none. Undergrowth, various desert vegetation.</p> <hr/>
	<p>N. 0°02' W., bet. secs. 27 and 28.</p> <p>Over rugged terrain.</p>
40.00	<p>Point for the 1/4 sec. cor. of secs. 27 and 28.</p> <p>Set a standard monument, 25 ins. in the ground, mkd.</p>
	<p style="text-align: center;">T 41 N R 27 E 1/4 S 28 S 27</p> <p style="text-align: center;">2011</p>
80.00	<p>Point for the cor. of secs. 21, 22, 27 and 28.</p>

Survey of the Subdivisional Lines,
T. 41 N., R. 27 E., Gila and Salt River Meridian, Arizona

CHAINS	
	<p>Set a standard monument, 24 ins. in the ground, mkd.</p> <p style="text-align: center;">T 41 N R 27 E S 21 S 22 S 28 S 27</p> <p style="text-align: center;">2011</p> <p>Terrain, broken and rugged. Soil, sand and rock. Timber, none. Undergrowth, various desert vegetation.</p> <hr/> <p>From the cor. of secs. 22, 23, 26 and 27.</p> <p>S. 89°56' W., bet. secs. 22 and 27.</p> <p>Over rolling terrain.</p>
40.01	<p>Point for the 1/4 sec. cor. of secs. 22 and 27.</p> <p>Set a standard monument, 24 ins. in the ground, mkd.</p> <p style="text-align: center;">T 41 N R 27 E S 22 1/4 ——— S 27</p> <p style="text-align: center;">2011</p>
80.02	<p>The cor. of secs. 21, 22, 27 and 28.</p> <p>Terrain, rolling. Soil, sand. Timber, none. Undergrowth, various desert vegetation.</p> <hr/> <p>N. 0°02' W., bet. secs. 21 and 22.</p> <p>Over rolling terrain.</p>
40.00	<p>Point for the 1/4 sec. cor. of secs. 21 and 22.</p> <p>Set a standard monument, 24 ins. in the ground, mkd.</p> <p style="text-align: center;">T 41 N R 27 E 1/4 S 21 S 22</p> <p style="text-align: center;">2011</p>

Survey of the Subdivisional Lines,
T. 41 N., R. 27 E., Gila and Salt River Meridian, Arizona

CHAINS									
80.00	<p>Point for the cor. of secs. 15, 16, 21 and 22.</p> <p>Set a standard monument, 25 ins. in the ground, mkd.</p> <div style="text-align: center;"> <table border="1" style="margin: auto;"> <tr> <td>T 41 N</td> <td>R 27 E</td> </tr> <tr> <td>S 16</td> <td>S 15</td> </tr> <tr> <td>S 21</td> <td>S 22</td> </tr> </table> <p>2011</p> </div> <p>Terrain, rolling. Soil, sand. Timber, none. Undergrowth, various desert vegetation.</p> <hr/> <p>From the cor. of secs. 14, 15, 22 and 23.</p> <p>S. 89°56' W., bet. secs. 15 and 22.</p> <p>Over rolling terrain.</p>	T 41 N	R 27 E	S 16	S 15	S 21	S 22		
T 41 N	R 27 E								
S 16	S 15								
S 21	S 22								
40.01	<p>Point for the 1/4 sec. cor. of secs. 15 and 22.</p> <p>Set a standard monument, 24 ins. in the ground, mkd.</p> <div style="text-align: center;"> <table border="1" style="margin: auto;"> <tr> <td>T 41 N</td> <td>R 27 E</td> </tr> <tr> <td></td> <td>S 15</td> </tr> <tr> <td>1/4</td> <td>—</td> </tr> <tr> <td></td> <td>S 22</td> </tr> </table> <p>2011</p> </div>	T 41 N	R 27 E		S 15	1/4	—		S 22
T 41 N	R 27 E								
	S 15								
1/4	—								
	S 22								
80.02	<p>The cor. of secs. 15, 16, 21 and 22.</p> <p>Terrain, rolling. Soil, sand. Timber, none. Undergrowth, various desert vegetation.</p> <hr/> <p>N. 0°02' W., bet. secs. 15 and 16.</p> <p>Over rolling terrain.</p>								
36.35	<p>High voltage transmission line, bears S. 86° E. and N. 86° W.</p>								
40.00	<p>Point for the 1/4 sec. cor. of secs. 15 and 16.</p> <p>Set a standard monument, 24 ins. in the ground, mkd.</p>								

Survey of the Subdivisional Lines,
T. 41 N., R. 27 E., Gila and Salt River Meridian, Arizona

CHAINS	
	T 41 N R 27 E 1/4 S 16 S 15 2011
57.30	South Right-of-Way fence, barbed wire, bears S. 88° E. and N. 88° W.
58.80	U.S. Highway No. 160, asphalt surfaced, 35 ft. wide, bears S. 88° E. and N. 88° W.
61.80	North Right-of-Way fence, barbed wire, bears S. 88° E. and N. 88° W.
80.00	Point for the cor. of secs. 9, 10, 15 and 16. Set a standard monument, 26 ins. in the ground, mkd.
	T 41 N R 27 E S 9 S 10 S 16 S 15 2011
	Terrain, rolling. Soil, sand. Timber, none. Undergrowth, various desert vegetation.
	From the cor. of secs. 10, 11, 14 and 15. S. 89°56' W., bet. secs. 10 and 15. Over rolling terrain.
40.01	Point for the 1/4 sec. cor. of secs. 10 and 15. Set a standard monument, 25 ins. in the ground, mkd.
	T 41 N R 27 E S 10 1/4 ——— S 15 2011
80.02	The cor. of secs. 9, 10, 15 and 16.

Survey of the Subdivisional Lines,
T. 41 N., R. 27 E., Gila and Salt River Meridian, Arizona

CHAINS	
	<p>Terrain, rolling. Soil, sand. Timber, none. Undergrowth, various desert vegetation.</p> <hr/> <p>N. 0°02' W., bet. secs. 9 and 10. Over rolling terrain.</p>
40.00	<p>Point for the 1/4 sec. cor. of secs. 9 and 10. Set a standard monument, 26 ins. in the ground, mkd.</p> <p style="text-align: center;">T 41 N R 27 E 1/4 S 9 S 10 2011</p>
80.00	<p>Point for the cor. of secs. 3, 4, 9 and 10. Set a standard monument, 25 ins. in the ground, mkd.</p> <p style="text-align: center;">T 41 N R 27 E S 4 S 3 ----- S 9 S 10 2011</p> <p>Terrain, rolling. Soil, sand. Timber, none. Undergrowth, various desert vegetation.</p> <hr/> <p>From the cor. of secs. 2, 3, 10 and 11. S. 89°56' W., bet. secs. 3 and 10. Over rolling terrain.</p>
40.01	<p>Point for the 1/4 sec. cor. of secs. 3 and 10. Set a standard monument, 26 ins. in the ground, mkd.</p> <p style="text-align: center;">T 41 N R 27 E S 3 1/4 ——— S 10 2011</p>

Survey of the Subdivisional Lines,
T. 41 N., R. 27 E., Gila and Salt River Meridian, Arizona

CHAINS	
80.02	<p>The cor. of secs. 3, 4, 9 and 10.</p> <p>Terrain, rolling. Soil, sand. Timber, none. Undergrowth, various desert vegetation.</p> <hr/> <p>N. 0°04' W., bet. secs. 3 and 4.</p> <p>Over rolling terrain.</p>
40.00	<p>Point for the 1/4 sec. cor. of secs. 3 and 4.</p> <p>Set a standard monument, 25 ins. in the ground, mkd.</p> <p style="text-align: center;">T 41 N R 27 E 1/4 S 4 S 3 2011</p>
80.12	<p>The cor. of secs. 3, 4, 33 and 34, hereinbefore described.</p> <p>Terrain, rolling. Soil, sand. Timber, none. Undergrowth, various desert vegetation.</p> <hr/> <p>From the stan. cor. of secs. 32 and 33, monumented with an iron post, 2 1/2 ins. diam., firmly set, projecting 1 in. above the ground, with brass cap mkd. SC T41N R27E S32 S33 2000 1953.</p> <p>Add the marks 2011 to the brass cap.</p> <p>N. 0°02' W., bet. secs. 32 and 33.</p> <p>Over rugged terrain.</p>
40.00	<p>Point for the 1/4 sec. cor. of secs. 32 and 33.</p> <p>Set a standard monument, 24 ins. in the ground, mkd.</p> <p style="text-align: center;">T 41 N R 27 E 1/4 S 32 S 33 2011</p>
80.00	<p>Point for the cor. of secs. 28, 29, 32 and 33.</p> <p>Set a standard monument, 23 ins. in the ground, mkd.</p>

Survey of the Subdivisional Lines,
T. 41 N., R. 27 E., Gila and Salt River Meridian, Arizona

CHAINS							
	<table style="margin: auto; border-collapse: collapse;"> <tr> <td style="padding: 0 10px;">T 41 N</td> <td style="padding: 0 10px;">R 27 E</td> </tr> <tr> <td style="border-right: 1px solid black; padding: 0 5px;">S 29</td> <td style="padding: 0 5px;">S 28</td> </tr> <tr> <td style="border-right: 1px solid black; padding: 0 5px;">S 32</td> <td style="padding: 0 5px;">S 33</td> </tr> </table>	T 41 N	R 27 E	S 29	S 28	S 32	S 33
T 41 N	R 27 E						
S 29	S 28						
S 32	S 33						
	2011						
	Terrain, rugged. Soil, sand. Timber, none. Undergrowth, various desert vegetation.						
	From the cor. of secs. 27, 28, 33 and 34. West, bet. secs. 28 and 33. Over rugged terrain.						
40.005	Point for the 1/4 sec. cor. of secs. 28 and 33. Set a standard monument, 14 ins. in the ground, in a mound of stone, 3 1/2 ft. base, to brass cap mkd.						
	<table style="margin: auto; border-collapse: collapse;"> <tr> <td style="padding: 0 10px;">T 41 N</td> <td style="padding: 0 10px;">R 27 E</td> </tr> <tr> <td></td> <td style="padding: 0 5px;">S 28</td> </tr> <tr> <td style="padding: 0 5px;">1/4</td> <td style="border-top: 1px solid black; padding: 0 5px;">S 33</td> </tr> </table>	T 41 N	R 27 E		S 28	1/4	S 33
T 41 N	R 27 E						
	S 28						
1/4	S 33						
	2011						
80.01	The cor. of secs. 28, 29, 32 and 33. Terrain, rugged. Soil, sand. Timber, none. Undergrowth, various desert vegetation.						
	N. 0°02' W., bet. secs. 28 and 29. Over rugged terrain.						
40.00	Point for the 1/4 sec. cor. of secs. 28 and 29. Set a standard monument, 23 ins. in the ground, mkd.						
	<table style="margin: auto; border-collapse: collapse;"> <tr> <td style="padding: 0 10px;">T 41 N</td> <td style="padding: 0 10px;">R 27 E</td> </tr> <tr> <td></td> <td style="padding: 0 5px;">1/4</td> </tr> <tr> <td style="padding: 0 5px;">S 29</td> <td style="border-left: 1px solid black; padding: 0 5px;">S 28</td> </tr> </table>	T 41 N	R 27 E		1/4	S 29	S 28
T 41 N	R 27 E						
	1/4						
S 29	S 28						
	2011						

Survey of the Subdivisional Lines,
T. 41 N., R. 27 E., Gila and Salt River Meridian, Arizona

CHAINS									
80.00	<p>Point for the cor. of secs. 20, 21, 28 and 29.</p> <p>Set a standard monument, 25 ins. in the ground, mkd.</p> <div style="text-align: center;"> <table style="margin: auto;"> <tr> <td>T 41 N</td> <td>R 27 E</td> </tr> <tr> <td>S 20</td> <td>S 21</td> </tr> <tr> <td>S 29</td> <td>S 28</td> </tr> </table> <p>2011</p> </div> <p>Terrain, rugged. Soil, sand and rock. Timber, none. Undergrowth, various desert vegetation.</p> <hr/> <p>From the cor. of secs. 21, 22, 27 and 28.</p> <p>West, bet. secs. 21 and 28.</p> <p>Over rolling terrain.</p>	T 41 N	R 27 E	S 20	S 21	S 29	S 28		
T 41 N	R 27 E								
S 20	S 21								
S 29	S 28								
40.005	<p>Point for the 1/4 sec. cor. of secs. 21 and 28.</p> <p>Set a standard monument, 25 ins. in the ground, mkd.</p> <div style="text-align: center;"> <table style="margin: auto;"> <tr> <td>T 41 N</td> <td>R 27 E</td> </tr> <tr> <td></td> <td>S 21</td> </tr> <tr> <td>1/4</td> <td>—</td> </tr> <tr> <td></td> <td>S 28</td> </tr> </table> <p>2011</p> </div>	T 41 N	R 27 E		S 21	1/4	—		S 28
T 41 N	R 27 E								
	S 21								
1/4	—								
	S 28								
80.01	<p>The cor. of secs. 20, 21, 28 and 29.</p> <p>Terrain, rolling. Soil, sand. Timber, none. Undergrowth, various desert vegetation.</p> <hr/> <p>N. 0°02' W., bet. secs. 20 and 21.</p> <p>Over rolling terrain.</p>								
30.40	<p>Underground waterline, bears S. 65° E. and N. 65° W.</p>								
40.00	<p>Point for the 1/4 sec. cor. of secs. 20 and 21.</p> <p>Set a standard monument, 25 ins. in the ground, mkd.</p>								

Survey of the Subdivisional Lines,
T. 41 N., R. 27 E., Gila and Salt River Meridian, Arizona

CHAINS	
	T 41 N R 27 E 1/4 S 20 S 21 2011
80.00	Point for the cor. of secs. 16, 17, 20 and 21. Set a standard monument, 25 ins. in the ground, mkd. <div style="text-align: center;"> T 41 N R 27 E S 17 S 16 S 20 S 21 2011 </div> Terrain, rolling. Soil, sand. Timber, none. Undergrowth, various desert vegetation.
	<hr/> From the cor. of secs. 15, 16, 21 and 22. West, bet. secs. 16 and 21. Over rolling terrain.
40.005	Point for the 1/4 sec. cor. of secs. 16 and 21. Set a standard monument, 25 ins. in the ground, mkd. <div style="text-align: center;"> T 41 N R 27 E S 16 1/4 ——— S 21 2011 </div>
80.01	The cor. of secs. 16, 17, 20 and 21. Terrain, rolling. Soil, sand. Timber, none. Undergrowth, various desert vegetation.
	<hr/> N. 0°02' W., bet. secs. 16 and 17. Over rolling terrain.
17.00	Indian Route 5045, graded road, 20 ft. wide, bears N. 40° E. and S. 40° W.

Survey of the Subdivisional Lines,
T. 41 N., R. 27 E., Gila and Salt River Meridian, Arizona

CHAINS	
40.00	<p>Point for the 1/4 sec. cor. of secs. 16 and 17.</p> <p>Set a standard monument, 25 ins. in the ground, mkd.</p> <p style="text-align: center;">T 41 N R 27 E 1/4 S 17 S 16</p> <p style="text-align: center;">2011</p>
41.40	High voltage transmission line, bears S. 86° E. and N. 86° W.
60.50	South Right-of-Way fence, barbed wire, bears S. 88° E. and N. 88° W.
62.05	U.S. Highway No. 160, asphalt surfaced, 35 ft. wide, bears S. 88° E. and N. 88° W.
65.10	North Right-of-Way fence, barbed wire, bears S. 88° E. and N. 88° W.
80.00	<p>Point for the cor. of secs. 8, 9, 16 and 17.</p> <p>Set a standard monument, 24 ins. in the ground, mkd.</p> <p style="text-align: center;">T 41 N R 27 E S 8 S 9 S 17 S 16</p> <p style="text-align: center;">2011</p> <p>Terrain, rolling. Soil, sand. Timber, none. Undergrowth, various desert vegetation.</p> <hr/> <p>From the cor. of secs. 9, 10, 15 and 16.</p> <p>West, bet. secs. 9 and 16.</p> <p>Over rolling terrain.</p>
40.005	<p>Point for the 1/4 sec. cor. of secs. 9 and 16.</p> <p>Set a standard monument, 24 ins. in the ground, mkd.</p>

Survey of the Subdivisional Lines,
T. 41 N., R. 27 E., Gila and Salt River Meridian, Arizona

CHAINS	
	<p style="text-align: center;">T 41 N R 27 E S 9 1/4 ——— S 16</p> <p style="text-align: center;">2011</p>
80.01	<p>The cor. of secs. 8, 9, 16 and 17.</p> <p>Terrain, rolling. Soil, sand. Timber, none. Undergrowth, various desert vegetation.</p> <hr/>
	<p>N. 0°02' W., bet. secs. 8 and 9.</p> <p>Over rolling terrain.</p>
40.00	<p>Point for the 1/4 sec. cor. of secs. 8 and 9.</p> <p>Set a standard monument, 24 ins. in the ground, mkd.</p>
	<p style="text-align: center;">T 41 N R 27 E 1/4 S 8 S 9</p> <p style="text-align: center;">2011</p>
80.00	<p>Point for the cor. of secs. 4, 5, 8 and 9.</p> <p>Set a standard monument, 24 ins. in the ground, mkd.</p>
	<p style="text-align: center;">T 41 N R 27 E S 5 S 4 S 8 S 9</p> <p style="text-align: center;">2011</p> <p>Terrain, rolling. Soil, sand. Timber, none. Undergrowth, various desert vegetation.</p> <hr/>
	<p>From the cor. of secs. 3, 4, 9 and 10.</p> <p>West, bet. secs. 4 and 9.</p> <p>Over rolling terrain.</p>
40.005	<p>Point for the 1/4 sec. cor. of secs. 4 and 9.</p>

Survey of the Subdivisional Lines,
T. 41 N., R. 27 E., Gila and Salt River Meridian, Arizona

CHAINS	
	<p>Set a standard monument, 24 ins. in the ground, mkd.</p> <p style="text-align: center;">T 41 N R 27 E S 4 1/4 ——— S 9</p> <p style="text-align: center;">2011</p>
80.01	<p>The cor. of secs. 4, 5, 8 and 9.</p> <p>Terrain, rolling. Soil, sand. Timber, none. Undergrowth, various desert vegetation.</p> <hr/> <p>N. 0°05' W., bet. secs. 4 and 5.</p> <p>Over rolling terrain.</p>
40.00	<p>Point for the 1/4 sec. cor. of secs. 4 and 5.</p> <p>Set a standard monument, 24 ins. in the ground, mkd.</p> <p style="text-align: center;">T 41 N R 27 E 1/4 S 5 S 4</p> <p style="text-align: center;">2011</p>
80.10	<p>The cor. of secs. 4, 5, 32 and 33, hereinbefore described.</p> <p>Terrain, rolling. Soil, sand. Timber, none. Undergrowth, various desert vegetation.</p> <hr/> <p>From the stan. cor. of secs. 31 and 32, monumented with a stainless steel post, 2 1/2 ins. diam., firmly set, flush with the ground, with brass cap mkd. SC T41N R27E S31 S32 2000.</p> <p>Add the marks 2011 to the brass cap.</p> <p>N. 0°03' W., bet. secs. 31 and 32.</p> <p>Over rolling terrain.</p>
40.00	<p>Point for the 1/4 sec. cor. of secs. 31 and 32.</p> <p>Set a standard monument, 24 ins. in the ground, mkd.</p>

Survey of the Subdivisional Lines,
T. 41 N., R. 27 E., Gila and Salt River Meridian, Arizona

CHAINS	
	T 41 N R 27 E 1/4 S 31 S 32 2011
80.00	Point for the cor. of secs. 29, 30, 31 and 32. Set a standard monument, 22 ins. in the ground, with a rock collar, mkd. <div style="text-align: center;"> T 41 N R 27 E S 30 S 29 S 31 S 32 2011 </div> Terrain, rolling. Soil, sand. Timber, none. Undergrowth, various desert vegetation.
	<hr/> From the cor. of secs. 28, 29, 32 and 33. S. 89°59' W., bet. secs. 29 and 32. Over rolling terrain.
40.02	Point for the 1/4 sec. cor. of secs. 29 and 32. Set a standard monument, 18 ins. in the ground, with a mound of stone, 3 1/2 ft. base, to brass cap mkd. <div style="text-align: center;"> T 41 N R 27 E S 29 1/4 ——— S 32 2011 </div>
80.04	The cor. of secs. 29, 30, 31 and 32. Terrain, rolling. Soil, sand. Timber, none. Undergrowth, various desert vegetation.
	<hr/> S. 89°59' W., bet. secs. 30 and 31. Over rolling terrain.

Survey of the Subdivisional Lines,
T. 41 N., R. 27 E., Gila and Salt River Meridian, Arizona

CHAINS	
38.55	Indian Route 5045, a graded road, 20 ft. wide, bears S. 10° E. and N. 10° W.
40.00	Point for the 1/4 sec. cor. of secs. 30 and 31. Set a standard monument, 25 ins. in the ground, mkd. <div style="text-align: center;"> T 41 N R 27 E S 30 1/4 ——— S 31 2011 </div>
79.94	The cor. of secs. 25, 30, 31 and 36, on the W. bdy. of the Tp., hereinbefore described. Terrain, rolling. Soil, sand. Timber, none. Undergrowth, various desert vegetation. <hr/> From the cor. of secs. 29, 30, 31 and 32. N. 0°03' W., bet. secs. 29 and 30. Over rolling terrain.
40.00	Point for the 1/4 sec. cor. of secs. 29 and 30. Set a standard monument, 24 ins. in the ground, mkd. <div style="text-align: center;"> T 41 N R 27 E 1/4 S 30 S 29 2011 </div>
80.00	Point for the cor. of secs. 19, 20, 29 and 30, falls on edge of nearly vertical bank of wash, 4 ft. high; not monumented. From this point, the point selected for the witness cor., bears N. 48°01' E., 40 lks. dist. At the witness cor. point Set a standard monument, 22 ins. in the ground, with a sandstone collar, mkd.

Survey of the Subdivisional Lines,
T. 41 N., R. 27 E., Gila and Salt River Meridian, Arizona

CHAINS	
	WC T 41 N R 27 E S 19 S 20 S 30 S 29 ↙ 2011
	Terrain, rolling. Soil, sand. Timber, none. Undergrowth, various desert vegetation.
	<hr/> From the cor. of secs. 20, 21, 28 and 29. S. 89°59' W., bet. secs. 20 and 29. Over rolling terrain.
40.02	Point for the 1/4 sec. cor. of secs. 20 and 29. Set a standard monument, 24 ins. in the ground, mkd.
	T 41 N R 27 E S 20 1/4 ——— S 29 2011
80.04	The point for the cor. of secs. 19, 20, 29 and 30. Terrain, rolling. Soil, sand. Timber, none. Undergrowth, various desert vegetation.
	<hr/> S. 89°59' W., bet. secs. 19 and 30. Over rolling terrain.
18.80	Indian Route 5045, a graded road, 20 ft. wide, bears N. 40° E. and S. 40° W.
40.00	Point for the 1/4 sec. cor. of secs. 19 and 30. Set a standard monument, 18 ins. in the ground, with mound of stone, 3 ft. base to brass cap mkd.

Survey of the Subdivisional Lines,
T. 41 N., R. 27 E., Gila and Salt River Meridian, Arizona

CHAINS	
	T 41 N R 27 E S 19 1/4 ——— S 30 2011
79.915	<p>The cor. of secs. 19, 24, 25 and 30, on the W. bdy. of the Tp., hereinbefore described.</p> <p>Terrain, rolling. Soil, sand. Timber, none. Undergrowth, various desert vegetation.</p> <hr/> <p>From the point for the cor. of secs. 19, 20, 29 and 30.</p> <p>N. 0°03' W., bet. secs. 19 and 20.</p> <p>Over rolling terrain.</p>
10.70	Indian Route 5045, a graded road, 20 ft. wide, bears N. 75° E. and S. 85° W.
40.00	<p>Point for the 1/4 sec. cor. of secs. 19 and 20.</p> <p>Set a standard monument, 24 ins. in the ground, mkd.</p> <p style="text-align: center;"> T 41 N R 27 E 1/4 S 19 S 20 2011 </p>
80.00	<p>Point for the cor. of secs. 17, 18, 19 and 20.</p> <p>Set a standard monument, 25 ins. in the ground, mkd.</p> <p style="text-align: center;"> T 41 N R 27 E S 18 S 17 S 19 S 20 2011 </p> <p>Terrain, rolling. Soil, sand. Timber, none. Undergrowth, various desert vegetation.</p> <hr/> <p>From the cor. of secs. 16, 17, 20 and 21.</p>

Survey of the Subdivisional Lines,
T. 41 N., R. 27 E., Gila and Salt River Meridian, Arizona

CHAINS	
	<p>S. 89°59' W., bet. secs. 17 and 20.</p> <p>Over rolling terrain.</p>
40.02	<p>Point for the 1/4 sec. cor. of secs. 17 and 20.</p> <p>Set a standard monument, 25 ins. in the ground, mkd.</p> <p style="text-align: center;">T 41 N R 27 E S 17 1/4 ——— S 20</p> <p style="text-align: center;">2011</p>
80.04	<p>The cor. of secs. 17, 18, 19 and 20.</p> <p>Terrain, rolling. Soil, sand. Timber, none. Undergrowth, various desert vegetation.</p> <hr/> <p>S. 89°57' W., bet. secs. 18 and 19.</p> <p>Over rolling terrain.</p>
40.00	<p>Point for the 1/4 sec. cor. of secs. 18 and 19.</p> <p>Set a standard monument, 25 ins. in the ground, mkd.</p> <p style="text-align: center;">T 41 N R 27 E S 18 1/4 ——— S 19</p> <p style="text-align: center;">2011</p>
79.77	<p>The cor. of secs. 13, 18, 19 and 24, on the W. bdy. of the Tp., hereinbefore described.</p> <p>Terrain, rolling. Soil, sand. Timber, none. Undergrowth, various desert vegetation.</p> <hr/> <p>From the cor. of secs. 17, 18, 19 and 20.</p> <p>N. 0°03' W., bet. secs. 17 and 18.</p> <p>Over rolling terrain.</p>

Survey of the Subdivisional Lines,
T. 41 N., R. 27 E., Gila and Salt River Meridian, Arizona

CHAINS	
40.00	<p>Point for the 1/4 sec. cor. of secs. 17 and 18.</p> <p>Set a standard monument, 25 ins. in the ground, mkd.</p> <p style="text-align: center;">T 41 N R 27 E 1/4 S 18 S 17</p> <p style="text-align: center;">2011</p>
46.40	High voltage transmission line, bears S. 88° E. and N. 88° W.
59.65	South Right-of-Way fence, barbed wire, bears S. 75° E. and N. 75° W.
60.95	U.S. Highway No. 160, asphalt surfaced, 35 ft. wide, bears S. 75° E. and N. 75° W.
62.05	North Right-of-Way fence, barbed wire, bears S. 75° E. and N. 75° W.
80.00	<p>Point for the cor. of secs. 7, 8, 17 and 18.</p> <p>Set a standard monument, 25 ins. in the ground, mkd.</p> <p style="text-align: center;">T 41 N R 27 E S 7 S 8 S 18 S 17</p> <p style="text-align: center;">2011</p> <p>Terrain, rolling. Soil, sand. Timber, none. Undergrowth, various desert vegetation.</p> <hr/> <p>From the cor. of secs. 8, 9, 16 and 17.</p> <p>S. 89°59' W., bet. secs. 8 and 17.</p> <p>Over rolling terrain.</p>
40.02	<p>Point for the 1/4 sec. cor. of secs. 8 and 17.</p> <p>Set a standard monument, 25 ins. in the ground, mkd.</p>

Survey of the Subdivisional Lines,
T. 41 N., R. 27 E., Gila and Salt River Meridian, Arizona

CHAINS	
	T 41 N R 27 E S 8 1/4 ——— S 17 2011
80.04	The cor. of secs. 7, 8, 17 and 18. Terrain, rolling. Soil, sand. Timber, none. Undergrowth, various desert vegetation.
	<hr/> N. 89°59' W., bet. secs. 7 and 18. Over rolling terrain.
40.00	Point for the 1/4 sec. cor. of secs. 7 and 18. Set a standard monument, 24 ins. in the ground, mkd.
	T 41 N R 27 E S 7 1/4 ——— S 18 2011
73.90	Indian Route 5058, graded road, 25 ft. wide, bears S. 40° E. and N. 40° W.
79.695	The cor. of secs. 7, 12, 13 and 18, on the W. bdy. of the Tp., hereinbefore described. Terrain, rolling. Soil, sand. Timber, none. Undergrowth, various desert vegetation.
	<hr/> From the cor. of secs. 7, 8, 17 and 18. N. 0°03' W., bet. secs. 7 and 8. Over rolling terrain.
40.00	Point for the 1/4 sec. cor. of secs. 7 and 8. Set a standard monument, 24 ins. in the ground, mkd.

Survey of the Subdivisional Lines,
T. 41 N., R. 27 E., Gila and Salt River Meridian, Arizona

CHAINS	
	T 41 N R 27 E 1/4 S 7 S 8 2011
80.00	Point for the cor. of secs. 5, 6, 7 and 8. Set a standard monument, 24 ins. in the ground, mkd.
	T 41 N R 27 E S 6 S 5 S 7 S 8 2011
	Terrain, rolling. Soil, sand. Timber, none. Undergrowth, various desert vegetation.
	<hr/> From the cor. of secs. 4, 5, 8 and 9. S. 89°59' W., bet. secs. 5 and 8. Over rolling terrain.
40.02	Point for the 1/4 sec. cor. of secs. 5 and 8. Set a standard monument, 24 ins. in the ground, mkd.
	T 41 N R 27 E S 5 1/4 ——— S 8 2011
80.04	The cor. of secs. 5, 6, 7 and 8. Terrain, rolling. Soil, sand. Timber, none. Undergrowth, various desert vegetation.
	<hr/> N. 89°58' W., bet. secs. 6 and 7. Over rolling terrain.
40.00	Point for the 1/4 sec. cor. of secs. 6 and 7.

Survey of the Subdivisional Lines,
T. 41 N., R. 27 E., Gila and Salt River Meridian, Arizona

CHAINS	
	<p>Set a standard monument, 24 ins. in the ground, mkd.</p> <p style="text-align: center;">T 41 N R 27 E S 6 1/4 ——— S 7</p> <p style="text-align: center;">2011</p>
79.61	<p>The cor. of secs. 1, 6, 7 and 12, on the W. bdy. of the Tp., hereinbefore described.</p> <p>Terrain, rolling. Soil, sand. Timber, none. Undergrowth, various desert vegetation.</p> <hr/> <p>From the cor. of secs. 5, 6, 7 and 8.</p> <p>N. 0°05' W., bet. secs. 5 and 6.</p> <p>Over rolling terrain.</p>
40.00	<p>Point for the 1/4 sec. cor. of secs. 5 and 6.</p> <p>Set a standard monument, 25 ins. in the ground, mkd.</p> <p style="text-align: center;">T 41 N R 27 E 1/4 S 6 S 5</p> <p style="text-align: center;">2011</p>
80.10	<p>The cor. of secs. 5, 6, 31 and 32, hereinbefore described.</p> <p>Terrain, rolling. Soil, sand. Timber, none. Undergrowth, various desert vegetation.</p> <hr/> <p style="text-align: center;">Subdivision of Section 13, T. 41 N., R. 27 E., Gila and Salt River Meridian, Arizona</p> <hr/> <p>From the 1/4 sec. cor. of secs. 13 and 24.</p> <p>North, on the N. and S. center line of sec. 13.</p>
23.60	<p>High voltage transmission line, bears S. 86° E. and N. 86° W.</p>

Subdivision of Section 13,
T. 41 N., R. 27 E., Gila and Salt River Meridian, Arizona

CHAINS	
40.01	<p>Point for the center 1/4 sec. cor. of sec. 13, at intersection with the E. and W. center line.</p> <p>Set a standard monument, 25 ins. in the ground, mkd.</p> <p style="text-align: center;">T 41 N R 27 E</p> <p style="text-align: center;">C 1/4 S 13</p> <p style="text-align: center;">2011</p>
49.00	South Right-of-Way fence, barbed wire, bears S. 88° E. and N. 88° W.
50.50	U.S. Highway No. 160, asphalt surfaced, 35 ft. wide, bears S. 88° E. and N. 88° W.
53.55	North Right-of-Way fence, barbed wire, bears S. 88° E. and N. 88° W.
80.01	<p>The 1/4 sec. cor. of secs. 12 and 13.</p> <hr/> <p>From the 1/4 sec. cor. of secs. 13 and 18, on the E. bdy. of the Tp., monumented with an iron post, 2 1/2 ins. diam., firmly set, projecting 6 ins. above the ground, with brass cap mkd. T41N R27E 1/4 R28E S13 S18 2008 1953, with a "T-Post" fence post nearby.</p> <p>Add the marks 2011 to the brass cap.</p> <p>S. 89°57' W., on the E. and W. center line of sec. 13.</p>
40.01	The center 1/4 sec. cor. of sec. 13.
80.02	<p>The 1/4 sec. cor. of secs. 13 and 14.</p> <hr/> <p style="text-align: center;">Subdivision of Section 14, T. 41 N., R. 27 E., Gila and Salt River Meridian, Arizona</p> <hr/> <p>From the 1/4 sec. cor. of secs. 14 and 23.</p> <p>N. 0°01' W., on the N. and S. center line of sec. 14.</p>
28.70	High voltage transmission line, bears S. 86° E. and N. 86° W.
40.00	<p>Point for the center 1/4 sec. cor. of sec. 14, at intersection with the E. and W. center line.</p> <p>Set a standard monument, 25 ins. in the ground, mkd.</p>

**Subdivision of Section 14,
T. 41 N., R. 27 E., Gila and Salt River Meridian, Arizona**

CHAINS	
	T 41 N R 27 E
	C 1/4 S 14
	2011
52.30	South Right-of-Way fence, barbed wire, bears S. 88° E. and N. 88° W.
53.80	U.S. Highway No. 160, asphalt surfaced, 35 ft. wide, bears S. 88° E. and N. 88° W.
56.85	North Right-of-Way fence, barbed wire, bears S. 88° E. and N. 88° W.
80.00	The 1/4 sec. cor. of secs. 11 and 14.
	<hr/>
	From the 1/4 sec. cor. of secs. 13 and 14.
	N. 89°58' W., on the E. and W. center line of sec. 14.
39.995	The center 1/4 sec. cor. of sec. 14.
79.99	The 1/4 sec. cor. of secs. 14 and 15.
	<hr/>
	Subdivision of Section 15, T. 41 N., R. 27 E., Gila and Salt River Meridian, Arizona
	<hr/>
	From the 1/4 sec. cor. of secs. 15 and 22.
	N. 0°01' W., on the N. and S. center line of sec. 15.
33.80	High voltage transmission line, bears S. 86° E. and N. 86° W.
37.60	Graded road, 18 ft. wide, bears N. 15° E. and S. 15° W.
40.00	Point for the center 1/4 sec. cor. of sec. 15, at intersection with the E. and W. center line.
	Set a standard monument, 24 ins. in the ground, mkd.
	T 41 N R 27 E
	C 1/4 S 15
	2011
55.60	South Right-of-Way fence, barbed wire, bears S. 88° E. and N. 88° W.

Subdivision of Section 15,
T. 41 N., R. 27 E., Gila and Salt River Meridian, Arizona

CHAINS	
57.10	U.S. Highway No. 160, asphalt surfaced, 35 ft. wide, bears S. 88° E. and N. 88° W.
60.15	North Right-of-Way fence, barbed wire, bears S. 88° E. and N. 88° W.
80.00	The 1/4 sec. cor. of secs. 10 and 15.
	<hr/>
	From the 1/4 sec. cor. of secs. 14 and 15.
	S. 89°56' W., on the E. and W. center line of sec. 15.
39.45	Graded road, 18 ft. wide, bears N. 20° E. and S. 20° W.
40.01	The center 1/4 sec. cor. of sec. 15.
80.02	The 1/4 sec. cor. of secs. 15 and 16.
	<hr/>
	Subdivision of Section 16, T. 41 N., R. 27 E., Gila and Salt River Meridian, Arizona
	<hr/>
	From the 1/4 sec. cor. of secs. 16 and 21.
	N. 0°02' W., on the N. and S. center line of sec. 16.
38.85	High voltage transmission line, bears S. 86° E. and N. 86° W.
40.00	Point for the center 1/4 sec. cor. of sec. 16, at intersection with the E. and W. center line.
	Set a standard monument, 26 ins. in the ground, mkd.
	T 41 N R 27 E
	C 1/4 S 16
	2011
58.90	South Right-of-Way fence, barbed wire, bears S. 88° E. and N. 88° W.
60.40	U.S. Highway No. 160, asphalt surfaced, 35 ft. wide, bears S. 88° E. and N. 88° W.
63.45	North Right-of-Way fence, barbed wire, bears S. 88° E. and N. 88° W.
80.00	The 1/4 sec. cor. of secs. 9 and 16.
	<hr/>

Subdivision of Section 16,
T. 41 N., R. 27 E., Gila and Salt River Meridian, Arizona

CHAINS	
	From the 1/4 sec. cor. of secs. 15 and 16. West, on the E. and W. center line of sec. 16.
40.005	The center 1/4 sec. cor. of sec. 16.
57.95	High voltage transmission line, bears S. 86° E. and N. 86° W.
58.95	Indian Route 5045, graded road, 20 ft. wide, bears N. 40° E. and S. 40° W.
80.01	The 1/4 sec. cor. of secs. 16 and 17.
<hr/> Subdivision of Section 17, T. 41 N., R. 27 E., Gila and Salt River Meridian, Arizona <hr/>	
	From the 1/4 sec. cor. of secs. 17 and 20. N. 0°03' W., on the N. and S. center line of sec. 17.
40.00	Point for the center 1/4 sec. cor. of sec. 17, at intersection with the E. and W. center line. Set a standard monument, 25 ins. in the ground, mkd.
	T 41 N R 27 E C 1/4 S 17 2011
43.95	High voltage transmission line, bears S. 86° E. and N. 86° W.
62.15	South Right-of-Way fence, barbed wire, bears S. 88° E. and N. 88° W.
63.70	U.S. Highway No. 160, asphalt surfaced, 35 ft. wide, bears S. 88° E. and N. 88° W.
66.75	North Right-of-Way fence, barbed wire, bears S. 88° E. and N. 88° W.
80.00	The 1/4 sec. cor. of secs. 8 and 17.
	<hr/> From the 1/4 sec. cor. of secs. 16 and 17. S. 89°59' W., on the E. and W. center line of sec. 17.
40.02	The center 1/4 sec. cor. of sec. 17.

Subdivision of Section 17,
T. 41 N., R. 27 E., Gila and Salt River Meridian, Arizona

CHAINS	
80.04	The 1/4 sec. cor. of secs. 17 and 18.
<hr/> <p>Subdivision of Section 18, T. 41 N., R. 27 E., Gila and Salt River Meridian, Arizona</p> <hr/>	
	From the 1/4 sec. cor. of secs. 18 and 19.
	N. 0°03' W., on the N. and S. center line of sec. 18.
39.25	High voltage transmission line, bears N. 65° E. and S. 65° W.
40.025	Point for the center 1/4 sec. cor. of sec. 18, at intersection with the E. and W. center line.
	Set a standard monument, 25 ins. in the ground, mkd.
	T 41 N R 27 E
	C 1/4 S 18
	2011
	From this cor. point, a Department of Transportation (DOT) monument, bears N. 53°36' W., 2.69 chs. dist., monumented with a brass tablet, 3 ins. diam., set in a concrete cylinder, 6 ins. diam., firmly set, projecting 6 ins. above the ground, mkd. ELEV. + STA 19.
42.60	South Right-of-Way fence, barbed wire, bears N. 66° E. and S. 66° W.
44.25	U.S. Highway No. 160, asphalt surfaced, 35 ft. wide, bears N. 66° E. and S. 66° W.
47.55	North Right-of-Way fence, barbed wire, bears N. 66° E. and S. 66° W.
80.04	The 1/4 sec. cor. of secs. 7 and 18.
<hr/>	
	From the 1/4 sec. cor. of secs. 17 and 18.
	S. 89°59' W., on the E. and W. center line of sec. 18.
40.00	The center 1/4 sec. cor. of sec. 18.

Subdivision of Section 18,
T. 41 N., R. 27 E., Gila and Salt River Meridian, Arizona

CHAINS

79.74

The 1/4 sec. cor. of secs. 13 and 18.

GENERAL DESCRIPTION

The terrain is mostly level to rolling desert, with broken and rugged land across the southern 2 miles of the township. A portion of Toh Atin Mesa is located in the southeastern position of the township.

The elevation varies from 5,200 to 6,500 feet above sea level. The soil is mostly fine sand with areas of sandstone outcrops and ledges. There is scattered juniper at the higher elevations, with sagebrush, cacti, greasewood and native grasses undergrowth throughout the township.

Highway 160 runs easterly and westerly through the township, with multiple graded roads traversing throughout the township.

The mean magnetic declination of 10 1/2° E. was derived from the National Geophysical Data Center's magnetic declination calculator, for the dates of the survey.

CERTIFICATE OF SURVEY

I, Craig S. Dukart, Cadastral Surveyor, HEREBY CERTIFY upon honor, that in pursuance of special instructions bearing date of the 28th day of April, 2011, I have dependently resurveyed the north and west boundaries, and surveyed the subdivisional lines and the subdivision of certain sections, T. 41 N., R. 27 E., of the Gila and Salt River Meridian, in the State of Arizona, which are represented in the foregoing field notes as having been executed by me and under my direction. Said survey has been made in strict conformity with said special instructions, the Manual of Instructions for the Survey of the Public Lands of the United States, 2009, and in specific manner described in the foregoing field notes.

MARCH 25, 2013

(Date)

Craig S. Dukart

(Cadastral Surveyor)

CERTIFICATE OF APPROVAL

BUREAU OF LAND MANAGEMENT
Phoenix, Arizona

The foregoing field notes of the dependent resurvey of the the north and west boundaries, and the survey of the subdivisional lines and the subdivision of certain sections, T. 41 N., R. 27 E., of the Gila and Salt River Meridian, in the State of Arizona, executed by Craig S. Dukart, Cadastral Surveyor, having been critically examined and found correct, are hereby approved.

3/27/2013

(Date)

Stephen K. Hansen

(Chief Cadastral Surveyor of Arizona)

~~CERTIFICATE OF TRANSCRIPT~~

~~I CERTIFY That the foregoing transcript of the field notes of the above described surveys in T. 41 N., R. 27 E., of the Gila and Salt River Meridian, in the State of Arizona, is a true copy of the original field notes.~~

~~(Date)~~

~~(Chief Cadastral Surveyor of Arizona)~~