

ORIGINAL

**UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT**

FIELD NOTES
OF THE SURVEY OF
THE NINTH STANDARD PARALLEL NORTH (SOUTH BOUNDARY)
THE WEST AND NORTH BOUNDARIES
THE SUBDIVISIONAL LINES
AND
THE SUBDIVISION OF CERTAIN SECTIONS
TOWNSHIP 37 NORTH, RANGE 11 EAST,
OF THE GILA AND SALT RIVER MERIDIAN,
IN THE STATE OF ARIZONA.

EXECUTED BY

Fabian Yazzie, Cadastral Surveyor

Under Special Instructions dated March 28, 2012, approved March 28, 2012, which provided for the surveys included under Group No. 1105, and assignment instructions dated March 28, 2012 and September 5, 2012.

Survey commenced April 3, 2012

Survey completed October 17, 2012

INDEX DIAGRAM

TOWNSHIP 37 NORTH RANGE 11 EAST
 GILA & SALT RIVER MERIDIAN, ARIZONA

18	17	16	16	15	14
13 6	61 5	51 4	43 3	35 2	27 1
61	60	50	42	34	26
12 7	59 8	49 9	41 10	33 11	25 12
58	58	48	41	32	25
11 18	57 17	48 16	40 15	32 14	24 13
56	56	47	39	31	23
10 19	55 20	46 21	38 22	30 23	22 24
54	54	46	38	30	22
9 30	53 29	45 28	37 27	29 26	21 25
52	52	44	36	28	20
9 31	51 32	43 33	35 34	27 35	19 36
7	7	6	5	4	4

Subdivision of Section 3 Pages 62-63
 Subdivision of Section 4 Pages 63-64
 Subdivision of Section 10 Pages 64-65
 Subdivision of Section 11 Pages 65-66
 Subdivision of Section 13 Pages 66-67
 Subdivision of Section 14 Pages 67-68
 Subdivision of Section 24 Pages 68-69

T. 37 N., R. 11 E., Gila and Salt River Meridian, Arizona

CHAINS

The following field notes describe the survey of the Ninth Standard Parallel North (South Boundary), the West and North boundaries, the subdivisional lines, and the subdivision of certain sections, Township 37 North, Range 11 East, Gila and Salt River Meridian, Arizona.

The history of surveys pertaining to this survey is as follows:

Geoffrey A. Graham surveyed the west boundary of Township 37 North, Range 12 East in 2007-08. Joe R. Salazar established the closing corner of Townships 36 North, Ranges 10 and 11 East, on the Ninth Standard Parallel North, in a plat only survey, in 2009.

The survey was executed in accordance with the specifications as set forth in the Manual of Instructions for the Survey of the Public Lands of the United States, 2009, and the Special Instructions dated March 28, 2012, for Group Number 1105, Arizona.

The true meridian direction and length of all lines were determined by real time kinematic global positioning system observations using Trimble Navigation R8 model receivers.

Geodetic control was derived from Global Positioning System (GPS) static observations post processed by National Geodetic Survey, Online Positioning User Service (OPUS), utilizing Continuously Operating Reference Stations (CORS) DK8419 AZPG CITY OF PAGE CORS, AI8805 FRED FREDONIA CORS, DI2245 P011 SPIDERROCKAZ2005 CORS, DJ8981 FST5 FLAGSTAFF 5 CORS, DN7504 SGU1 ST GEORGE PUTIL CORS, DI2242 P009 MARYSVALE_UT2006 CORS, DI3419 P012 MONTICELLOUT2006 CORS, and DL1898 AZPS PRESCOTT CORS. The NAD 83 (2011) (EPOCH: 2010), geographic position of the standard corner of Township 37 North, Ranges 11 and 12 East, is as follows:

Latitude: 36°33'19.633" N. Longitude: 111°09'19.027" W.

The geographic position of the corner of Townships 37 and 38 North, Ranges 10 and 11 East, is as follows:

Latitude: 36°38'32.799" N. Longitude: 111°15'47.196" W.

The mean magnetic declination is 11° E.

Survey of the Ninth Standard Parallel North (S. Bdy.),
T. 37 N., R. 11 E., Gila and Salt River Meridian, Arizona

CHAINS	
	<p>Beginning at the stan. cor. of Tps. 37 N., Rs. 11 and 12 E., monumented with a stainless steel post, 2 1/2 ins. diam., firmly set, 3 ins. below the surface of the ground, with brass cap mkd. SC T37N R11E R12E S36 S31 2007.</p> <p>Add the marks 2012 to the brass cap.</p> <p>West, along the S. bdy. of sec. 36.</p> <p>Over rolling land.</p>
40.00	<p>Point for the stan. 1/4 sec. cor. of sec. 36.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 25 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">SC T 37 N R 11 E 1/4 S 36 -----</p> <p style="text-align: center;">2012</p> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p>
80.00	<p>Point for the stan. cor. of secs. 35 and 36.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">SC T 37 N R 11 E S 35 S 36 -----</p> <p style="text-align: center;">2012</p> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p> <p>Land, rolling. Soil, sandy loam. Timber, scattered juniper and pinon. Undergrowth, native grasses and Mormon tea.</p> <hr/> <p>West, along the S. bdy. of sec. 35.</p> <p>Over rolling land.</p>
40.00	<p>Point for the stan. 1/4 sec. cor. of sec. 35.</p>

Survey of the Ninth Standard Parallel North (S. Bdy.),
T. 37 N., R. 11 E., Gila and Salt River Meridian, Arizona

CHAINS	
	<p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 25 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">SC T 37 N R 11 E <u>1/4 S 35</u></p> <p style="text-align: center;">2012</p> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p>
80.00	<p>Point for the stan. cor. of secs. 34 and 35.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 25 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">SC T 37 N R 11 E <u>S 34 S 35</u></p> <p style="text-align: center;">2012</p> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p> <p>Land, rolling. Soil, sandy loam. Timber, juniper and pinon. Undergrowth, native grasses and Mormon tea.</p> <hr/> <p>West, along the S. bdy. of sec. 34.</p> <p>Over rolling land.</p>
40.00	<p>Point for the stan. 1/4 sec. cor. of sec. 34.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">SC T 37 N R 11 E <u>1/4 S 34</u></p> <p style="text-align: center;">2012</p> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p>
80.00	<p>Point for the stan. cor. of secs. 33 and 34.</p>

Survey of the Ninth Standard Parallel North (S. Bdy.),
T. 37 N., R. 11 E., Gila and Salt River Meridian, Arizona

CHAINS	
	<p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 23 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">SC T 37 N R 11 E <u>S 33 S 34</u></p> <p style="text-align: center;">2012</p> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p> <p>Land, rolling. Soil, sandy loam. Timber, juniper and pinon. Undergrowth, native grasses and Mormon tea.</p>
	<p>West, along the S. bdy. of sec. 33.</p> <p>Over rolling land.</p>
40.00	<p>Point for the stan. 1/4 sec. cor. of sec. 33.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 14 ins. in the ground to sandstone bedrock, in a supporting mound of stone, 3 ft. base, to top, with brass cap mkd.</p> <p style="text-align: center;">SC T 37 N R 11 E <u>1/4 S 33</u></p> <p style="text-align: center;">2012</p> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p>
80.00	<p>Point for the stan. cor. of secs. 32 and 33.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">SC T 37 N R 11 E <u>S 32 S 33</u></p> <p style="text-align: center;">2012</p> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p>

Survey of the Ninth Standard Parallel North (S. Bdy.),
T. 37 N., R. 11 E., Gila and Salt River Meridian, Arizona

CHAINS	
	<p>Land, rolling. Soil, sandy loam. Timber, juniper and pinon. Undergrowth, native grasses and Mormon tea.</p> <hr/>
	<p>West, along the S. bdy. of sec. 32. Over rolling land.</p>
40.00	<p>Point for the stan. 1/4 sec. cor. of sec. 32.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">SC T 37 N R 11 E 1/4 S 32 <hr/></p> <p style="text-align: center;">2012</p>
80.00	<p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p> <p>Point for the stan. cor. of secs. 31 and 32.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">SC T 37 N R 11 E S 31 S 32 <hr/></p> <p style="text-align: center;">2012</p>
40.00	<p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p> <p>Land, rolling. Soil, sandy loam. Timber, juniper and pinon. Undergrowth, native grasses and Mormon tea.</p> <hr/> <p>West, along the S. bdy. of sec. 31. Over gently rolling land.</p> <p>Point for the stan. 1/4 sec. cor. of sec. 31.</p>

Survey of the Ninth Standard Parallel North (S. Bdy.),
T. 37 N., R. 11 E., Gila and Salt River Meridian, Arizona

CHAINS

Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 16 ins. in the ground to sandstone bedrock, in a supporting mound of stone, 3 ft. base, to top, with brass cap mkd.

SC
T 37 N R 11 E
1/4 S 31

2012

Deposit a magnet, in a white plastic case, at the base of the stainless steel post.

67.36 The closing cor. of Tps. 36 N., Rs. 10 and 11 E., monumented with a stainless steel post, 2 1/2 ins. diam., firmly set, projecting 1 in. above ground, with a mound of stone, 4 ft. base, 1 1/2 ft. high, S. of cor., with brass cap mkd. T37N R11E S31 S1 S6 R10E R11E T36N CC 2009.

Add the marks 2012 to the brass cap.

80.00 Point for the stan. cor. of Tps. 37 N., Rs. 10 and 11 E.

Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.

SC
T 37 N
R 10 E | R 11 E
S 36 | S 31

T 36 N R 10 E
S1

2012

Deposit a magnet, in a white plastic case, at the base of the stainless steel post.

Land, gently rolling.

Soil, sandy loam.

Timber, juniper and pinon.

Undergrowth, native grasses and Mormon tea.

Survey of the West Boundary,
T. 37 N., R. 11 E., Gila and Salt River Meridian, Arizona

From the stan. cor. of Tps. 37 N., Rs. 10 and 11 E., hereinbefore described.

North, bet. secs. 31 and 36.

Survey of the West Boundary,
T. 37 N., R. 11 E., Gila and Salt River Meridian, Arizona

CHAINS	
	Over rolling land.
40.00	Point for the 1/4 sec. cor. of secs. 31 and 36. Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd. <div style="text-align: center;"> T 37 N R 10 E R 11 E 1/4 S 36 S 31 2012 </div>
80.00	Point for the cor. of secs. 25, 30, 31 and 36. Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with brass cap mkd. <div style="text-align: center;"> T 37 N R 10 E R 11 E S 25 S 30 S 36 S 31 2012 </div>
	Deposit a magnet, in a white plastic case, at the base of the stainless steel post.
	Deposit a magnet, in a white plastic case, at the base of the stainless steel post.
	Land, rolling. Soil, sandy loam. Timber, juniper and pinon. Undergrowth, native grasses, sage brush and Mormon tea.
	North, bet. secs. 25 and 30.
	Over rolling land.
40.00	Point for the 1/4 sec. cor. of secs. 25 and 30. Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.

Survey of the West Boundary,
T. 37 N., R. 11 E., Gila and Salt River Meridian, Arizona

CHAINS

T 37 N
R 10 E R 11 E
1/4
S 25 | S 30

2012

Deposit a magnet, in a white plastic case, at the base of the stainless steel post.

80.00

Point for the cor. of secs. 19, 24, 25 and 30.

Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 17 ins. in the ground to sandstone bedrock, in a supporting mound of stone, 3 ft. base, to top, with brass cap mkd.

T 37 N
R 10 E | R 11 E
S 24 | S 19
S 25 | S 30

2012

Deposit a magnet, in a white plastic case, at the base of the stainless steel post.

Land, rolling.

Soil, sandy loam and sandstone outcrops.

Timber, juniper and pinon.

Undergrowth, native grasses, sage brush and Mormon tea.

North, bet. secs. 19 and 24.

Over rolling land.

40.00

Point for the 1/4 sec. cor. of secs. 19 and 24.

Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 25 ins. in the ground, with brass cap mkd.

T 37 N
R 10 E R 11 E
1/4
S 24 | S 19

2012

Deposit a magnet, in a white plastic case, at the base of the stainless steel post.

Survey of the West Boundary,
T. 37 N., R. 11 E., Gila and Salt River Meridian, Arizona

CHAINS									
80.00	<p>Point for the cor. of secs. 13, 18, 19 and 24.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center;"> <table style="margin: auto;"> <tr><td colspan="2">T 37 N</td></tr> <tr><td>R 10 E</td><td>R 11 E</td></tr> <tr><td>S 13</td><td>S 18</td></tr> <tr><td>S 24</td><td>S 19</td></tr> </table> <p>2012</p> </div> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p> <p>Land, rolling. Soil, sandy loam. Timber, juniper and pinon. Undergrowth, native grasses, sage brush and Mormon tea.</p> <hr/> <p>North, bet. secs. 13 and 18.</p> <p>Over rolling land.</p>	T 37 N		R 10 E	R 11 E	S 13	S 18	S 24	S 19
T 37 N									
R 10 E	R 11 E								
S 13	S 18								
S 24	S 19								
40.00	<p>Point for the 1/4 sec. cor. of secs. 13 and 18.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center;"> <table style="margin: auto;"> <tr><td colspan="2">T 37 N</td></tr> <tr><td>R 10 E</td><td>R 11 E</td></tr> <tr><td colspan="2">1/4</td></tr> <tr><td>S 13</td><td>S 18</td></tr> </table> <p>2012</p> </div> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p>	T 37 N		R 10 E	R 11 E	1/4		S 13	S 18
T 37 N									
R 10 E	R 11 E								
1/4									
S 13	S 18								
80.00	<p>Point for the cor. of secs. 7, 12, 13 and 18.</p> <p>Set a brass tablet, 3 1/8 ins. diam., 2 1/2 ins. stem, cemented in a drill hole in solid sandstone bedrock, with top mkd.</p> <div style="text-align: center;"> <table style="margin: auto;"> <tr><td colspan="2">T 37 N</td></tr> <tr><td>R 10 E</td><td>R 11 E</td></tr> <tr><td>S 12</td><td>S 7</td></tr> <tr><td>S 13</td><td>S 18</td></tr> </table> <p>2012</p> </div>	T 37 N		R 10 E	R 11 E	S 12	S 7	S 13	S 18
T 37 N									
R 10 E	R 11 E								
S 12	S 7								
S 13	S 18								

Survey of the West Boundary,
T. 37 N., R. 11 E., Gila and Salt River Meridian, Arizona

CHAINS

Deposit a magnet, without plastic case, at the base of the brass tablet.

Raise a mound of stone, 2 ft. base, 2 ft. high, N. of cor.

Land, rolling.

Soil, sandy loam and sandstone outcrops.

Timber, juniper and pinon.

Undergrowth, native grasses and Mormon tea.

North, bet. secs. 7 and 12.

Over rolling land.

35.30 The centerline of power line right-of-way, bears N. 75° E. and S. 75° W.

40.00 Point for the 1/4 sec. cor. of secs. 7 and 12.

Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 7 ins. below the surface of the ground, with brass cap mkd.

T 37 N		
R 10 E	R 11 E	
1/4		
S 12		S 7

2012

Deposit a magnet, in a white plastic case, at the base of the stainless steel post.

Cor. is located in a trail road, bears N. 20° E. and S. 20° W.

80.00 Point for the cor. of secs. 1, 6, 7 and 12.

Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 25 ins. in the ground, with brass cap mkd.

T 37 N		
R 10 E		R 11 E
S 1		S 6
S 12		S 7

2012

Deposit a magnet, in a white plastic case, at the base of the stainless steel post.

Survey of the West Boundary,
T. 37 N., R. 11 E., Gila and Salt River Meridian, Arizona

CHAINS	
	<p>Land, rolling. Soil, sandy loam. Timber, juniper and pinon. Undergrowth, native grasses and Mormon tea.</p> <hr/>
	<p>North, bet. secs. 1 and 6.</p> <p>Over rolling land:</p>
40.00	<p>Point for the 1/4 sec. cor. of secs. 1 and 6.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 23 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center;"> <p>T 37 N R 10 E R 11 E 1/4 S 1 S 6 2012</p> </div> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p>
80.00	<p>Point for the cor. of Tps. 37 and 38 N., Rs. 10 and 11 E.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 25 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center;"> <p>T 38 N R 10 E R 11 E S 36 S 31 S 1 S 6 T 37 N 2012</p> </div> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p> <p>Land, rolling. Soil, sandy loam. Timber, juniper and pinon. Undergrowth, native grasses and Mormon tea.</p> <hr/>

Survey of the North Boundary,
T. 37 N., R. 11 E., Gila and Salt River Meridian, Arizona

CHAINS

From the cor. of Tps. 37 and 38 N., Rs. 11 and 12 E., monumented with a stainless steel post, 2 1/2 ins. diam., firmly set, projecting 4 ins. above ground, with brass cap mkd. T38N R11E R12E S36 S31 S1 S6 T37N 2007.

Add the marks 2012 to the brass cap.

West, bet. secs. 1 and 36.

Over rolling land.

40.00 Point for the 1/4 sec. cor. of secs. 1 and 36.

Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with brass cap mkd.

T 38 N R 11 E
S 36
1/4 ———
S 1
T 37 N

2012

Deposit a magnet, in a white plastic case, at the base of the stainless steel post.

80.00 Point for the cor. of secs. 1, 2, 35 and 36, located on steep edge of sandstone outcrop, where it is impracticable to set a permanent monument.

From this true point, the point selected for a witness cor. to the cor. of secs. 1, 2, 35 and 36, bears S. 44°57' E., 1.00 ch. dist.

Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 27 ins. in the ground, with brass cap mkd.

WC
T 38 N R 11 E
S 35 ↙ | S 36
S 2 | S 1
T 37 N

2012

Deposit a magnet, in a white plastic case, at the base of the stainless steel post.

Survey of the North Boundary,
T. 37 N., R. 11 E., Gila and Salt River Meridian, Arizona

CHAINS	
	<p>Land, rolling. Soil, sandy loam. Timber, juniper and pinon. Undergrowth, native grasses and Mormon tea.</p> <hr/>
	<p>West, bet. secs. 2 and 35.</p> <p>Over rolling land.</p>
40.00	<p>Point for the 1/4 sec. cor. of secs. 2 and 35.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 25 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T 38 N R 11 E S 35 1/4 ——— S 2 T 37 N</p> <p style="text-align: center;">2012</p> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p>
62.00	<p>Horsethief Mesa, top of E. rim, 160 ft. high, bears N. 50° E. and S. 50° W.</p>
80.00	<p>Point for the cor. of secs. 2, 3, 34 and 35.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 16 ins. in the ground to sandstone bedrock, in a supporting mound of stone, 3 ft. base, to top, with brass cap mkd.</p> <p style="text-align: center;">T 38 N R 11 E S 34 S 35 S 3 S 2 T 37 N</p> <p style="text-align: center;">2012</p> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p> <p>Cor. is located on top of Horsethief Mesa.</p> <p>Land, rolling and broken. Soil, sandy loam and sandstone outcrops. Timber, juniper and pinon. Undergrowth, native grasses and Mormon tea.</p> <hr/>

Survey of the North Boundary,
T. 37 N., R. 11 E., Gila and Salt River Meridian, Arizona

CHAINS	
	West, bet. secs. 3 and 34.
	Over Horsethief Mesa.
2.90	Horsethief Mesa, top of W. rim, 160 ft. high, bears N. 30° E. and S. 30° W.
40.00	Point for the 1/4 sec. cor. of secs. 3 and 34.
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with brass cap mkd.
	T 38 N R 11 E S 34 1/4 ——— S 3 T 37 N 2012
	Deposit a magnet, in a white plastic case, at the base of the stainless steel post.
80.00	Point for the cor. of secs. 3, 4, 33 and 34.
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 27 ins. in the ground, with brass cap mkd.
	T 38 N R 11 E S 33 S 34 S 4 S 3 T 37 N 2012
	Deposit a magnet, in a white plastic case, at the base of the stainless steel post.
	Land, rolling and broken. Soil, sandy loam and sandstone outcrops. Timber, juniper and pinon. Undergrowth, native grasses and Mormon tea.
	West, bet. secs. 4 and 33.
	Over rolling land.
2.65	Dirt road, 8 ft. wide, bears N. 35° E. and S. 35° W.
40.00	Point for the 1/4 sec. cor. of secs. 4 and 33.

Survey of the North Boundary,
T. 37 N., R. 11 E., Gila and Salt River Meridian, Arizona

CHAINS	
	<p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 25 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T 38 N R 11 E S 33 1/4 ——— S 4 T 37 N</p> <p style="text-align: center;">2012</p> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p>
44.80	E. right-of-way fence of State Highway 98, barbed wire, 4 strand, parallels highway.
47.05	State Highway 98, an asphalt surfaced road, 35 ft. wide, bears S. 45° E. and N. 45° W.
49.40	W. right-of-way fence of State Highway 98, barbed wire, 4 strand, parallels highway.
80.00	Point for the cor. of secs. 4, 5, 32 and 33.
	<p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T 38 N R 11 E S 32 S 33 S 5 S 4 T 37 N</p> <p style="text-align: center;">2012</p> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p> <p>Land, rolling. Soil, sandy loam and sandstone outcrops. Timber, juniper and pinon. Undergrowth, native grasses and Mormon tea.</p> <hr/> <p>West, bet. secs. 5 and 32.</p> <p>Over rolling land.</p>
9.45	The centerline of power line right-of-way, bears S. 45° E. and N. 45° W.
40.00	Point for the 1/4 sec. cor. of secs. 5 and 32.

Survey of the North Boundary,
T. 37 N., R. 11 E., Gila and Salt River Meridian, Arizona

CHAINS	
	<p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in solid sandstone bedrock, with brass cap mkd.</p> <p style="text-align: center;">T 38 N R 11 E S 32 1/4 ——— S 5 T 37 N</p> <p style="text-align: center;">2012</p> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p> <p>Raise a mound of stone, 3 ft. base, 1 1/2 ft. high, N. of cor.</p>
80.00	<p>Point for the cor. of secs. 5, 6, 31 and 32.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., flush with the surface of the ground, with brass cap mkd.</p> <p style="text-align: center;">T 38 N R 11 E S 31 S 32 S 6 S 5 T 37 N</p> <p style="text-align: center;">2012</p> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p> <p>Land, rolling. Soil, sandy loam and sandstone outcrops. Timber, juniper and pinon. Undergrowth, native grasses and Mormon tea.</p> <hr/> <p>West, bet. secs. 6 and 31.</p> <p>Over rolling land.</p>
35.40	<p>The centerline of power line right-of-way, bears N. 40° E. and S. 40° W.</p>
38.15	<p>E. right-of-way fence of Black Mesa and Lake Powell Railroad, woven and barbed wire, parallels railroad.</p>
39.45	<p>Black Mesa and Lake Powell Railroad, 5 ft. bet. rails, bears S. 30° E. and N. 30° W.</p>
40.00	<p>Point for the 1/4 sec. cor. of secs. 6 and 31.</p>

**Survey of the North Boundary,
T. 37 N., R. 11 E., Gila and Salt River Meridian, Arizona**

CHAINS	
	<p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with brass cap mkd.</p>
	<p>T 38 N R 11 E S 31 1/4 ——— S 6 T 37 N</p>
	<p>2012</p>
	<p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p>
	<p>Cor. is located within the Black Mesa and Lake Powell Railroad right-of-way.</p>
40.55	<p>W. right-of-way fence of Black Mesa and Lake Powell Railroad, woven and barbed wire, parallels railroad.</p>
79.45	<p>The cor. of Tps. 37 and 38 N., Rs. 10 and 11 E., hereinbefore described.</p>
	<p>Land, rolling. Soil, sandy loam. Timber, juniper and pinon. Undergrowth, native grasses and Mormon tea.</p>
<hr/> <p>Survey of the Subdivisional Lines, T. 37 N., R. 11 E., Gila and Salt River Meridian, Arizona</p> <hr/>	
	<p>From the stan. cor. of secs. 35 and 36, on the S. bdy. of the Tp., hereinbefore described.</p>
	<p>N. 0°01' W., bet. secs. 35 and 36.</p>
	<p>Over rolling land.</p>
40.00	<p>Point for the 1/4 sec. cor. of secs. 35 and 36.</p>
	<p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with brass cap mkd.</p>
	<p>T 37 N R 11 E 1/4 S 35 S 36</p>
	<p>2012</p>

Survey of the Subdivisional Lines,
T. 37 N., R. 11 E., Gila and Salt River Meridian, Arizona

CHAINS									
	Deposit a magnet, in a white plastic case, at the base of the stainless steel post.								
80.00	Point for the cor. of secs. 25, 26, 35 and 36. Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 25 ins. in the ground, with brass cap mkd. <div style="text-align: center;"> <table style="margin: auto;"> <tr> <td>T 37 N</td> <td>R 11 E</td> </tr> <tr> <td>S 26</td> <td>S 25</td> </tr> <tr> <td>S 35</td> <td>S 36</td> </tr> </table> <p>2012</p> </div>	T 37 N	R 11 E	S 26	S 25	S 35	S 36		
T 37 N	R 11 E								
S 26	S 25								
S 35	S 36								
	Deposit a magnet, in a white plastic case, at the base of the stainless steel post. Land, rolling. Soil, sandy loam. Timber, juniper and pinon. Undergrowth, native grasses and Mormon tea.								
	From the cor. of secs. 25, 30, 31 and 36 on the E. bdy. of the Tp., monumented with a stainless steel post, 2 1/2 ins. diam., firmly set, projecting 3 ins. above ground, with brass cap mkd. T37N R11E R12E S25 S30 S36 S31 2007. Add the marks 2012 to the brass cap. West, bet. secs. 25 and 36. Over gently rolling land.								
40.00	Point for the 1/4 sec. cor. of secs. 25 and 36. Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 25 ins. in the ground, with brass cap mkd. <div style="text-align: center;"> <table style="margin: auto;"> <tr> <td>T 37 N</td> <td>R 11 E</td> </tr> <tr> <td></td> <td>S 25</td> </tr> <tr> <td>1/4</td> <td>_____</td> </tr> <tr> <td></td> <td>S 36</td> </tr> </table> <p>2012</p> </div>	T 37 N	R 11 E		S 25	1/4	_____		S 36
T 37 N	R 11 E								
	S 25								
1/4	_____								
	S 36								
	Deposit a magnet, in a white plastic case, at the base of the stainless steel post.								
52.85	E. right-of-way fence of Black Mesa and Lake Powell Railroad, woven and barbed wire, parallels railroad.								

Survey of the Subdivisional Lines,
T. 37 N., R. 11 E., Gila and Salt River Meridian, Arizona

CHAINS	
53.75	Black Mesa and Lake Powell Railroad, 5 ft. bet. rails, bears S. 30° E., curving E., and N. 30° W., curving N.
54.85	W. right-of-way fence of Black Mesa and Lake Powell Railroad, woven and barbed wire, parallels railroad.
80.00	The cor. of secs. 25, 26, 35 and 36. Land, rolling to near level. Soil, sandy loam. Timber, juniper and pinon. Undergrowth, native grasses and Mormon tea.
	N. 0°01' W., bet. secs. 25 and 26. Over gently rolling land.
40.00	Point for the 1/4 sec. cor. of secs. 25 and 26. Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 27 ins. in the ground, with brass cap mkd. <div style="text-align: center;"> T 37 N R 11 E 1/4 S 26 S 25 2012 </div>
	Deposit a magnet, in a white plastic case, at the base of the stainless steel post.
49.90	S. right-of-way fence of Black Mesa and Lake Powell Railroad, woven and barbed wire, parallels railroad.
52.45	Black Mesa and Lake Powell Railroad, 5 ft. bet. rails, bears S. 35° E. and N. 35° W., curving W.
53.90	N. right-of-way fence of Black Mesa and Lake Powell Railroad, woven and barbed wire, parallels railroad.
80.00	Point for the cor. of secs. 23, 24, 25 and 26. Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 27 ins. in the ground, with brass cap mkd. <div style="text-align: center;"> T 37 N R 11 E S 23 S 24 S 26 S 25 2012 </div>

Survey of the Subdivisional Lines,
T. 37 N., R. 11 E., Gila and Salt River Meridian, Arizona

CHAINS	
	<p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p> <p>Land, gently rolling. Soil, sandy loam. Timber, juniper and pinon. Undergrowth, native grasses, sage brush and Mormon tea.</p> <hr/> <p>From the cor. of secs. 19, 24, 25 and 30 on the E. bdy. of the Tp., monumented with a stainless steel post, 2 1/2 ins. diam., firmly set, projecting 4 ins. above ground, with brass cap mkd. T37N R11E R12E S24 S19 S25 S30 2007.</p> <p>Add the marks 2012 to the brass cap.</p> <p>West, bet. secs. 24 and 25.</p> <p>Over rolling land.</p>
40.00	<p>Point for the 1/4 sec. cor. of secs. 24 and 25.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center;"> <p>T 37 N R 11 E</p> <p>S 24</p> <p>1/4 ———</p> <p>S 25</p> <p>2012</p> </div> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p>
80.00	<p>The cor. of secs. 23, 24, 25 and 26.</p> <p>Land, rolling. Soil, sandy loam. Timber, juniper and pinon. Undergrowth, native grasses and Mormon tea.</p> <hr/> <p>N. 0°01' W., bet. secs. 23 and 24.</p> <p>Over rolling land.</p>
40.00	<p>Point for the 1/4 sec. cor. of secs. 23 and 24.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 27 ins. in the ground, with brass cap mkd.</p>

Survey of the Subdivisional Lines,
T. 37 N., R. 11 E., Gila and Salt River Meridian, Arizona

CHAINS	
	<p style="text-align: center;">T 37 N R 11 E 1/4 S 23 S 24</p> <p style="text-align: center;">2012</p> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p>
80.00	<p>Point for the cor. of secs. 13, 14, 23 and 24.</p> <p>Set a brass tablet, 3 1/2 ins. diam., 2 1/4 ins. stem, cemented in a drill hole in solid sandstone bedrock, with top mkd.</p> <p style="text-align: center;">T 37 N R 11 E S 14 S 13 S 23 S 24</p> <p style="text-align: center;">2012</p> <p>Deposit a magnet, without plastic case, at the base of the brass tablet.</p> <p>Land, rolling. Soil, sandy loam and sandstone outcrops. Timber, juniper and pinon. Undergrowth, native grasses and Mormon tea.</p>
40.00	<hr/> <p>From the cor. of secs. 13, 18, 19 and 24 on the E. bdy. of the Tp., monumented with an aluminum rod, 3/4 ins. diam., firmly set, projecting 2 ins. above sandstone bedrock, with aluminum cap mkd. T37N R11E R12E S13 S18 S24 S19 2008.</p> <p>Add the marks 2012 to the brass cap.</p> <p>West, bet. secs. 13 and 24.</p> <p>Over rolling land.</p> <p>Point for the 1/4 sec. cor. of secs. 13 and 24.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 27 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T 37 N R 11 E S 13 1/4 ——— S 24</p> <p style="text-align: center;">2012</p>

Survey of the Subdivisional Lines,
T. 37 N., R. 11 E., Gila and Salt River Meridian, Arizona

CHAINS	
	Deposit a magnet, in a white plastic case, at the base of the stainless steel post.
57.30	E. right-of-way fence of State Highway 98, barbed wire, 4 strand, parallels highway.
59.50	State Highway 98, an asphalt surfaced road, 35 ft. wide, bears S. 45° E. and N. 45° W.
61.75	W. right-of-way fence of State Highway 98, barbed wire, 4 strand, parallels highway.
80.00	The cor. of secs. 13, 14, 23 and 24. Land, rolling. Soil, sandy loam. Timber, juniper and pinon. Undergrowth, native grasses, sage brush and Mormon tea.
	N. 0°01' W., bet. secs. 13 and 14. Over rolling land.
16.45	S. right-of-way fence of State Highway 98, barbed wire, 4 strand, parallels highway.
18.45	State Highway 98, an asphalt surfaced road, 35 ft. wide, bears S. 45° E. and N. 45° W.
20.50	N. right-of-way fence of State Highway 98, barbed wire, 4 strand, parallels highway.
40.00	Point for the 1/4 sec. cor. of secs. 13 and 14. Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 27 ins. in the ground, with brass cap mkd. <div style="text-align: center;"> T 37 N R 11 E 1/4 S 14 S 13 2012 </div>
	Deposit a magnet, in a white plastic case, at the base of the stainless steel post.
80.00	Point for the cor. of secs. 11, 12, 13 and 14. Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with brass cap mkd.

Survey of the Subdivisional Lines,
T. 37 N., R. 11 E., Gila and Salt River Meridian, Arizona

CHAINS

T 37 N	R 11 E
S 11	S 12
S 14	S 13

2012

Deposit a magnet, in a white plastic case, at the base of the stainless steel post.

Land, rolling.

Soil, sandy loam.

Timber, juniper and pinon.

Undergrowth, native grasses, sage brush and Mormon tea.

From the cor. of secs. 7, 12, 13 and 18 on the E. bdy. of the Tp., monumented with a stainless steel post, 2 1/2 ins. diam., firmly set, projecting 1 in. above ground, with brass cap mkd. T37N R11E R12E S12 S7 S13 S18 2007.

Add the marks 2012 to the brass cap.

West, bet. secs. 12 and 13.

Over rolling land.

40.00 Point for the 1/4 sec. cor. of secs. 12 and 13.

Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 27 ins. in the ground, with brass cap mkd.

T 37 N	R 11 E
	S 12
	1/4 ———
	S 13

2012

Deposit a magnet, in a white plastic case, at the base of the stainless steel post.

80.00 The cor. of secs. 11, 12, 13 and 14.

Land, rolling.

Soil, sandy loam.

Timber, juniper and pinon.

Undergrowth, native grasses, sage brush and Mormon tea.

N. 0°01' W., bet. secs. 11 and 12.

Over rolling land.

Survey of the Subdivisional Lines,
T. 37 N., R. 11 E., Gila and Salt River Meridian, Arizona

CHAINS	
40.00	<p>Point for the 1/4 sec. cor. of secs. 11 and 12.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 25 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T 37 N R 11 E 1/4 S 11 S 12</p> <p style="text-align: center;">2012</p> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p>
80.00	<p>Point for the cor. of secs. 1, 2, 11 and 12.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 25 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T 37 N R 11 E S 2 S 1 ----- S 11 S 12</p> <p style="text-align: center;">2012</p> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p> <p>Land, rolling. Soil, sandy loam. Timber, juniper and sparse pinon. Undergrowth, native grasses, sage brush and Mormon tea.</p> <hr/> <p>From the cor. of secs. 1, 6, 7 and 12 on the E. bdy. of the Tp., monumented with a stainless steel post, 2 1/2 ins. diam., firmly set, projecting 5 ins. above ground, with brass cap mkd. T37N R11E R12E S1 S6 S12 S7 2007.</p> <p>Add the marks 2012 to the brass cap.</p> <p>West, bet. secs. 1 and 12.</p> <p>Over rolling land.</p>
40.00	<p>Point for the 1/4 sec. cor. of secs. 1 and 12.</p> <p>Set a brass tablet, 3 1/8 ins. diam., 2 1/2 ins. stem, cemented in a drill hole in solid sandstone bedrock, with top mkd.</p>

Survey of the Subdivisional Lines,
T. 37 N., R. 11 E., Gila and Salt River Meridian, Arizona

CHAINS	
	T 37 N R 11 E S 1 1/4 ——— S 12 2012
	Deposit a magnet, without plastic case, at the base of the brass tablet.
80.00	The cor. of secs. 1, 2, 11 and 12. Land, rolling. Soil, sandy loam and sandstone outcrops. Timber, juniper and sparse pinon. Undergrowth, native grasses, sage brush and Mormon tea.
	N. 0°01' W., bet. secs. 1 and 2. Over rolling land.
40.00	Point for the 1/4 sec. cor. of secs. 1 and 2. Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with brass cap mkd.
	T 37 N R 11 E 1/4 S 2 S 1 2012
	Deposit a magnet, in a white plastic case, at the base of the stainless steel post.
80.00	The true point for the cor. of secs. 1, 2, 35 and 36, on the N. bdy. of the Tp. hereinbefore described. Land, rolling. Soil, sandy loam. Timber, juniper and sparse pinon. Undergrowth, native grasses, sage brush and Mormon tea.
	From the stan. cor. of secs. 34 and 35, on the S. bdy. of the Tp., hereinbefore described. N. 0°01' W., bet. secs. 34 and 35. Over rolling land.
40.00	Point for the 1/4 sec. cor. of secs. 34 and 35.

Survey of the Subdivisional Lines,
T. 37 N., R. 11 E., Gila and Salt River Meridian, Arizona

CHAINS

Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam.,
26 ins. in the ground, with brass cap mkd.

T 37 N R 11 E
1/4
S 34 | S 35

2012

Deposit a magnet, in a white plastic case, at the base of the
stainless steel post.

80.00 Point for the cor. of secs. 26, 27, 34 and 35.

Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam.,
26 ins. in the ground, with brass cap mkd.

T 37 N R 11 E
S 27 | S 26
S 34 | S 35

2012

Deposit a magnet, in a white plastic case, at the base of the
stainless steel post.

Land, rolling.
Soil, sandy loam.
Timber, juniper and pinon.
Undergrowth, native grasses and Mormon tea.

From the cor. of secs. 25, 26, 35 and 36.

West, bet. secs. 26 and 35.

Over rolling land.

40.00 Point for the 1/4 sec. cor. of secs. 26 and 35.

Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam.,
26 ins. in the ground, with brass cap mkd.

T 37 N R 11 E
S 26
1/4 ———
S 35

2012

Deposit a magnet, in a white plastic case, at the base of the
stainless steel post.

Survey of the Subdivisional Lines,
T. 37 N., R. 11 E., Gila and Salt River Meridian, Arizona

CHAINS	
80.00	<p>The cor. of secs. 26, 27, 34 and 35.</p> <p>Land, rolling. Soil, sandy loam. Timber, juniper and pinon. Undergrowth, native grasses and Mormon tea.</p> <hr/> <p>N. 0°01' W., bet. secs. 26 and 27.</p> <p>Over rolling land.</p>
40.00	<p>Point for the 1/4 sec. cor. of secs. 26 and 27.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center;"> <p>T 37 N R 11 E 1/4 S 27 S 26</p> <p>2012</p> </div> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p>
78.30	<p>S. right-of-way fence of Black Mesa and Lake Powell Railroad, woven and barbed wire, parallels railroad.</p>
79.25	<p>Black Mesa and Lake Powell Railroad, 5 ft. bet. rails, bears S. 85° E., curving N., and N. 85° W.</p>
80.00	<p>Point for the cor. of secs. 22, 23, 26 and 27.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center;"> <p>T 37 N R 11 E S 22 S 23 S 27 S 26</p> <p>2012</p> </div> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p> <p>Cor. is located 10 lks. S. and 96 lks. W. of the N. right-of-way fence of Black Mesa and Lake Powell Railroad, woven and barbed wire, parallels railroad.</p>

Survey of the Subdivisional Lines,
T. 37 N., R. 11 E., Gila and Salt River Meridian, Arizona

CHAINS	
	<p>Land, rolling. Soil, sandy loam. Timber, juniper and pinon. Undergrowth, native grasses, sage brush and Mormon tea.</p> <hr/> <p>From the cor. of secs. 23, 24, 25 and 26.</p> <p>West, bet. secs. 23 and 26.</p> <p>Over rolling land.</p>
40.00	<p>Point for the 1/4 sec. cor. of secs. 23 and 26.</p> <p>Set a brass tablet, 3 1/2 ins. diam., 2 1/4 ins. stem, cemented in a drill hole in solid sandstone rock outcrop, with top mkd.</p> <p style="text-align: center;">T 37 N R 11 E S 23 1/4 ——— S 26</p> <p style="text-align: center;">2012</p> <p>Deposit a magnet, without plastic case, at the base of the brass tablet.</p>
80.00	<p>The cor. of secs. 22, 23, 26 and 27.</p> <p>Land, rolling. Soil, sandy loam and sandstone outcrops. Timber, juniper and pinon. Undergrowth, native grasses and Mormon tea.</p> <hr/> <p>N. 0°01' W., bet. secs. 22 and 23.</p> <p>Over rolling land.</p>
30.10	<p>Dirt road, 8 ft. wide, bears N. 25° E. and S. 25° W.</p>
40.00	<p>Point for the 1/4 sec. cor. of secs. 22 and 23.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T 37 N R 11 E 1/4 S 22 S 23</p> <p style="text-align: center;">2012</p>

Survey of the Subdivisional Lines,
T. 37 N., R. 11 E., Gila and Salt River Meridian, Arizona

CHAINS									
	<p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p>								
80.00	<p>Point for the cor. of secs. 14, 15, 22 and 23, located on steep edge of sandstone outcrop, where it is impracticable to set a permanent monument.</p> <p>From this true point, the point selected for a witness cor. to the cor. of secs. 14, 15, 22 and 23, bears S. 45°03' E., 1.00 ch. dist.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center;"> <p>WC</p> <table style="margin: auto;"> <tr> <td>T 37 N</td> <td>R 11 E</td> </tr> <tr> <td>S 15</td> <td>S 14</td> </tr> <tr> <td>S 22</td> <td>S 23</td> </tr> </table> <p>2012</p> </div> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p> <p>Land, rolling. Soil, sandy loam and sandstone outcrops. Timber, juniper and pinon. Undergrowth, native grasses, sage brush and Mormon tea.</p> <hr/> <p>From the cor. of secs. 13, 14, 23 and 24.</p> <p>West, bet. secs. 14 and 23.</p> <p>Over rolling land.</p>	T 37 N	R 11 E	S 15	S 14	S 22	S 23		
T 37 N	R 11 E								
S 15	S 14								
S 22	S 23								
40.00	<p>Point for the 1/4sec. cor. of secs. 14 and 23.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 27 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center;"> <table style="margin: auto;"> <tr> <td>T 37 N</td> <td>R 11 E</td> </tr> <tr> <td></td> <td>S 14</td> </tr> <tr> <td>1/4</td> <td>—</td> </tr> <tr> <td></td> <td>S 23</td> </tr> </table> <p>2012</p> </div> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p>	T 37 N	R 11 E		S 14	1/4	—		S 23
T 37 N	R 11 E								
	S 14								
1/4	—								
	S 23								
59.10	<p>Dirt road, 8 ft. wide, bears N. 10° E. and S. 10° W.</p>								

Survey of the Subdivisional Lines,
T. 37 N., R. 11 E., Gila and Salt River Meridian, Arizona

CHAINS	
80.00	<p>The true point for the cor. of secs. 14, 15, 22 and 23.</p> <p>Land, rolling. Soil, sandy loam and sandstone outcrops. Timber, juniper and pinon. Undergrowth, native grasses, sage brush and Mormon tea.</p> <hr/> <p>N. 0°01' W., bet. secs. 14 and 15.</p> <p>Over rolling land.</p>
40.00	<p>Point for the 1/4 sec. cor. of secs. 14 and 15.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 16 ins. in the ground to sandstone bedrock, in a supporting mound of stone, 3 ft. base, to top, with brass cap mkd.</p> <p style="text-align: center;">T 37 N R 11 E 1/4 S 15 S 14</p> <p style="text-align: center;">2012</p> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p>
80.00	<p>Point for the cor. of secs. 10, 11, 14 and 15.</p> <p>Set a brass tablet, 3 1/8 ins. diam., 2 1/2 ins. stem, cemented in a drill hole in solid sandstone rock outcrop, with top mkd.</p> <p style="text-align: center;">T 37 N R 11 E S 10 S 11 S 15 S 14</p> <p style="text-align: center;">2012</p> <p>Deposit a magnet, without plastic case, at the base of the brass tablet.</p> <p>Land, rolling. Soil, sandy loam and sandstone outcrops. Timber, juniper and pinon. Undergrowth, native grasses, sage brush and Mormon tea.</p> <hr/> <p>From the cor. of secs. 11, 12, 13 and 14.</p> <p>West, bet. secs. 11 and 14.</p> <p>Over rolling land.</p>

Survey of the Subdivisional Lines,
T. 37 N., R. 11 E., Gila and Salt River Meridian, Arizona

CHAINS	
40.00	<p>Point for the 1/4 sec. cor. of secs. 11 and 14.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 25 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T 37 N R 11 E S 11 1/4 ——— S 14</p> <p style="text-align: center;">2012</p> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p>
65.95	E. right-of-way fence of State Highway 98, barbed wire, 4 strand, parallels highway.
68.20	State Highway 98, an asphalt surfaced road, 35 ft. wide, bears S. 45° E. and N. 45° W.
70.45	W. right-of-way fence of State Highway 98, barbed wire, 4 strand, parallels highway.
80.00	<p>The cor. of secs. 10, 11, 14 and 15.</p> <p>Land, rolling. Soil, sandy loam. Timber, juniper and pinon. Undergrowth, native grasses, sage brush and Mormon tea.</p> <hr/> <p>N. 0°01' W., bet. secs. 10 and 11.</p> <p>Over rolling land.</p>
8.60	S. right-of-way fence of State Highway 98, barbed wire, 4 strand, parallels highway.
10.65	State Highway 98, an asphalt surfaced road, 35 ft. wide, bears S. 45° E. and N. 45° W.
12.65	N. right-of-way fence of State Highway 98, barbed wire, 4 strand, parallels highway.
12.90	The centerline of power line right-of-way, bears N. 85° E. and S. 85° W.
40.00	<p>Point for the 1/4 sec. cor. of secs. 10 and 11.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with brass cap mkd.</p>

Survey of the Subdivisional Lines,
T. 37 N., R. 11 E., Gila and Salt River Meridian, Arizona

CHAINS	
	T 37 N R 11 E 1/4 S 10 S 11 2012
80.00	Deposit a magnet, in a white plastic case, at the base of the stainless steel post. Point for the cor. of secs. 2, 3, 10 and 11. Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 25 ins. in the ground, with brass cap mkd.
	T 37 N R 11 E S 3 S 2 S 10 S 11 2012
	Deposit a magnet, in a white plastic case, at the base of the stainless steel post. Land, rolling. Soil, sandy loam. Timber, juniper and pinon. Undergrowth, native grasses, sage brush and Mormon tea.
	From the cor. of secs. 1, 2, 11 and 12. West, bet. secs. 2 and 11. Over rolling land.
40.00	Point for the 1/4 sec. cor. of secs. 2 and 11. Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 17 ins. in the ground to sandstone bedrock, in a supporting mound of stone, 2 1/2 ft. base, to top, with brass cap mkd.
	T 37 N R 11 E S 2 1/4 ——— S 11 2012
80.00	Deposit a magnet, in a white plastic case, at the base of the stainless steel post. The cor. of secs. 2, 3, 10 and 11.

Survey of the Subdivisional Lines,
T. 37 N., R. 11 E., Gila and Salt River Meridian, Arizona

CHAINS	
	<p>Land, rolling. Soil, sandy loam and sandstone outcrops. Timber, juniper and pinon. Undergrowth, native grasses, sage brush and Mormon tea.</p> <hr/> <p>N. 0°01' W., bet. secs. 2 and 3.</p> <p>Over rolling land.</p>
40.00	<p>Point for the 1/4 sec. cor. of secs. 2 and 3.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 14 ins. in the ground to sandstone bedrock, in a supporting mound of stone, 3 1/2 ft. base, to top, with brass cap mkd.</p> <p style="text-align: center;">T 37 N R 11 E 1/4 S 3 S 2 2012</p> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p>
59.85	<p>Horsethief Mesa, top of S. rim, 160 ft. high, bears N. 75° E. and S. 75° W.</p>
80.00	<p>The cor. of secs. 2, 3, 34 and 35, on the N. bdy. of the Tp. hereinbefore described.</p> <p>Land, rolling and broken. Soil, sandy loam and sandstone outcrops. Timber, juniper and pinon. Undergrowth, native grasses, sage brush and Mormon tea.</p> <hr/> <p>From the stan. cor. of secs. 33 and 34, on the S. bdy. of the Tp., hereinbefore described.</p> <p>N. 0°02' W., bet. secs. 33 and 34.</p> <p>Over rolling land.</p>
40.00	<p>Point for the 1/4 sec. cor. of secs. 33 and 34.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with brass cap mkd.</p>

Survey of the Subdivisional Lines,
T. 37 N., R. 11 E., Gila and Salt River Meridian, Arizona

CHAINS	
	T 37 N R 11 E 1/4 S 33 S 34 2012 Deposit a magnet, in a white plastic case, at the base of the stainless steel post.
80.00	Point for the cor. of secs. 27, 28, 33 and 34. Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with brass cap mkd. T 37 N R 11 E S 28 S 27 S 33 S 34 2012 Deposit a magnet, in a white plastic case, at the base of the stainless steel post. Land, rolling. Soil, sandy loam. Timber, juniper and pinon. Undergrowth, native grasses and Mormon tea.
	<hr/> From the cor. of secs. 26, 27, 34 and 35. West, bet. secs. 27 and 34. Over rolling land.
40.00	Point for the 1/4 sec. cor. of secs. 27 and 34. Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with brass cap mkd. T 37 N R 11 E S 27 1/4 ——— S 34 2012 Deposit a magnet, in a white plastic case, at the base of the stainless steel post.
80.00	The cor. of secs. 27, 28, 33 and 34.

Survey of the Subdivisional Lines,
T. 37 N., R. 11 E., Gila and Salt River Meridian, Arizona

CHAINS	
	<p>Land, rolling. Soil, sandy loam. Timber, juniper and pinon. Undergrowth, native grasses and Mormon tea.</p> <hr/>
	<p>N. 0°02' W., bet. secs. 27 and 28. Over rolling land.</p>
27.60	Dirt road, 8 ft. wide, bears N. 65° E. and S. 65° W.
40.00	Point for the 1/4 sec. cor. of secs. 27 and 28. Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 27 ins. in the ground, with brass cap mkd.
	<p>T 37 N R 11 E 1/4 S 28 S 27 2012</p>
	Deposit a magnet, in a white plastic case, at the base of the stainless steel post.
80.00	Point for the cor. of secs. 21, 22, 27 and 28. Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 25 ins. in the ground, with brass cap mkd.
	<p>T 37 N R 11 E S 21 S 22 S 28 S 27 2012</p>
	Deposit a magnet, in a white plastic case, at the base of the stainless steel post.
	<p>Land, rolling. Soil, sandy loam. Timber, juniper and pinon. Undergrowth, native grasses and Mormon tea.</p> <hr/>
	<p>From the cor. of secs. 22, 23, 26 and 27. West, bet. secs. 22 and 27. Over gently rolling land.</p>

Survey of the Subdivisional Lines,
T. 37 N., R. 11 E., Gila and Salt River Meridian, Arizona

CHAINS	
7.20	Black Mesa and Lake Powell Railroad, 5 ft. bet. rails, bears S. 80° E. and N. 80° W., curving N.
11.35	S. right-of-way fence of Black Mesa and Lake Powell Railroad, woven and barbed wire, parallels railroad.
21.05	Dirt road, 8 ft. wide, bears N. 80° E. and S. 80° W.
24.20	From this point, the pump shaft of a windmill, 6 ins. diam., firmly set in a concrete pad, 2 ft. high, bears S., 14.65 chs. dist. There is a livestock tank alongside, 40 ft. diam., 7 ft. high, mkd. IT-526.
40.00	Point for the 1/4 sec. cor. of secs. 22 and 27. Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 27 ins. in the ground, with brass cap mkd. <div style="text-align: center;"> T 37 N R 11 E S 22 1/4 ——— S 27 2012 </div> Deposit a magnet, in a white plastic case, at the base of the stainless steel post.
80.00	The cor. of secs. 21, 22, 27 and 28. Land, rolling. Soil, sandy loam. Timber, juniper and pinon. Undergrowth, native grasses, sage brush and Mormon tea. <hr/>
40.00	N. 0°02' W., bet. secs. 21 and 22. Over rolling land. Point for the 1/4 sec. cor. of secs. 21 and 22. Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd. <div style="text-align: center;"> T 37 N R 11 E 1/4 S 21 S 22 2012 </div> Deposit a magnet, in a white plastic case, at the base of the stainless steel post.

Survey of the Subdivisional Lines,
T. 37 N., R. 11 E., Gila and Salt River Meridian, Arizona

CHAINS							
80.00	<p>Point for the cor. of secs. 15, 16, 21 and 22.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <table style="margin-left: auto; margin-right: auto; border-collapse: collapse;"> <tr> <td style="padding: 0 10px;">T 37 N</td> <td style="padding: 0 10px;">R 11 E</td> </tr> <tr> <td style="padding: 0 10px; border-right: 1px solid black;">S 16</td> <td style="padding: 0 10px;">S 15</td> </tr> <tr> <td style="padding: 0 10px; border-right: 1px solid black;">S 21</td> <td style="padding: 0 10px;">S 22</td> </tr> </table> <p style="text-align: center;">2012</p> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p> <p>Land, rolling. Soil, sandy loam. Timber, juniper and pinon. Undergrowth, native grasses and Mormon tea.</p> <hr/> <p>From the true point for the cor. of secs. 14, 15, 22 and 23.</p> <p>West, bet. secs. 15 and 22.</p> <p>Over rolling land.</p>	T 37 N	R 11 E	S 16	S 15	S 21	S 22
T 37 N	R 11 E						
S 16	S 15						
S 21	S 22						
40.00	<p>Point for the 1/4 sec. cor. of secs. 15 and 22.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <table style="margin-left: auto; margin-right: auto; border-collapse: collapse;"> <tr> <td style="padding: 0 10px;">T 37 N</td> <td style="padding: 0 10px;">R 11 E</td> </tr> <tr> <td style="padding: 0 10px;"></td> <td style="padding: 0 10px;">S 15</td> </tr> <tr> <td style="padding: 0 10px;">1/4</td> <td style="padding: 0 10px; border-top: 1px solid black;">S 22</td> </tr> </table> <p style="text-align: center;">2012</p> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p>	T 37 N	R 11 E		S 15	1/4	S 22
T 37 N	R 11 E						
	S 15						
1/4	S 22						
71.50	E. right-of-way fence of Black Mesa and Lake Powell Railroad, woven and barbed wire, parallels railroad.						
72.55	Black Mesa and Lake Powell Railroad, 5 ft. bet. rails, bears S. 30° E. and N. 30° W.						
73.75	W. right-of-way fence of Black Mesa and Lake Powell Railroad, woven and barbed wire, parallels railroad.						
80.00	The cor. of secs. 15, 16, 21 and 22.						

Survey of the Subdivisional Lines,
T. 37 N., R. 11 E., Gila and Salt River Meridian, Arizona

CHAINS	
	<p>Land, rolling. Soil, sandy loam. Timber, juniper and pinon. Undergrowth, native grasses and Mormon tea.</p> <hr/>
	<p>N. 0°02' W., bet. secs. 15 and 16.</p> <p>Over rolling land.</p>
10.05	S. right-of-way fence of Black Mesa and Lake Powell Railroad, woven and barbed wire, parallels railroad.
12.40	Black Mesa and Lake Powell Railroad, 5 ft. bet. rails, bears S. 30° E. and N. 30° W.
14.15	N. right-of-way fence of Black Mesa and Lake Powell Railroad, woven and barbed wire, parallels railroad.
40.00	<p>Point for the 1/4 sec. cor. of secs. 15 and 16.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center;"> <p>T 37 N R 11 E 1/4 S 16 S 15</p> <p>2012</p> </div> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p>
80.00	<p>Point for the cor. of secs. 9, 10, 15 and 16.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 25 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center;"> <p>T 37 N R 11 E S 9 S 10 S 16 S 15</p> <p>2012</p> </div> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p> <p>Land, rolling. Soil, sandy loam. Timber, juniper and pinon. Undergrowth, native grasses and Mormon tea.</p> <hr/>

Survey of the Subdivisional Lines,
T. 37 N., R. 11 E., Gila and Salt River Meridian, Arizona

CHAINS	
	<p>From the cor. of secs. 10, 11, 14 and 15.</p> <p>West, bet. secs. 10 and 15.</p> <p>Over rolling land.</p>
40.00	<p>Point for the 1/4 sec. cor. of secs. 10 and 15.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T 37 N R 11 E S 10 1/4 ——— S 15</p> <p style="text-align: center;">2012</p> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p>
80.00	<p>The cor. of secs. 9, 10, 15 and 16.</p> <p>Land, rolling. Soil, sandy loam. Timber, juniper and pinon. Undergrowth, native grasses and Mormon tea.</p> <hr/> <p>N. 0°02' W., bet. secs. 9 and 10.</p> <p>Over rolling land.</p>
40.00	<p>Point for the 1/4 sec. cor. of secs. 9 and 10.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T 37 N R 11 E 1/4 S 9 S 10</p> <p style="text-align: center;">2012</p> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p>
74.30	<p>The centerline of power line right-of-way, bears S. 65° E. and N. 65° W.</p>
80.00	<p>Point for the cor. of secs. 3, 4, 9 and 10.</p>

Survey of the Subdivisional Lines,
T. 37 N., R. 11 E., Gila and Salt River Meridian, Arizona

CHAINS	
	<p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 25 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T 37 N R 11 E S 4 S 3 S 9 S 10</p> <p style="text-align: center;">2012</p> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p> <p>Land, rolling. Soil, sandy loam. Timber, juniper and pinon. Undergrowth, native grasses, sage brush and Mormon tea.</p> <hr/> <p>From the cor. of secs. 2, 3, 10 and 11.</p> <p>West, bet. secs. 3 and 10.</p> <p>Over rolling land.</p>
40.00	<p>Point for the 1/4 sec. cor. of secs. 3 and 10.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 13 ins. in the ground to sandstone bedrock, in a supporting mound of stone, 3 ft. base, to top, with brass cap mkd.</p> <p style="text-align: center;">T 37 N R 11 E S 3 1/4 ——— S 10</p> <p style="text-align: center;">2012</p> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p>
58.75	<p>E. right-of-way fence of State Highway 98, barbed wire, 4 strand, parallels highway.</p>
60.50	<p>State Highway 98, an asphalt surfaced road, 35 ft. wide, bears S. 30° E. and N. 30° W.</p>
62.30	<p>W. right-of-way fence of State Highway 98, barbed wire, 4 strand, parallels highway.</p>
80.00	<p>The cor. of secs. 3, 4, 9 and 10.</p>

Survey of the Subdivisional Lines,
T. 37 N., R. 11 E., Gila and Salt River Meridian, Arizona

CHAINS	
	<p>Land, rolling. Soil, sandy loam and sandstone outcrops. Timber, juniper and pinon. Undergrowth, native grasses, sage brush and Mormon tea.</p> <hr/> <p>N. 0°02' W., bet. secs. 3 and 4.</p> <p>Over rolling land:</p>
22.35	S. right-of-way fence of State Highway 98, barbed wire, 4 strand, parallels highway.
24.65	State Highway 98, an asphalt surfaced road, 35 ft. wide, bears S. 40° E. and N. 40° W.
27.00	N. right-of-way fence of State Highway 98, barbed wire, 4 strand, parallels highway.
40.00	Point for the 1/4 sec. cor. of secs. 3 and 4.
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with brass cap mkd.
	<p>T 37 N R 11 E 1/4 S 4 S 3 2012</p>
	Deposit a magnet, in a white plastic case, at the base of the stainless steel post.
80.00	The cor. of secs. 3, 4, 33 and 34, on the N. bdy. of the Tp. hereinbefore described.
	<p>Land, rolling. Soil, sandy loam. Timber, juniper and pinon. Undergrowth, native grasses, sage brush and Mormon tea.</p> <hr/> <p>From the stan. cor. of secs. 32 and 33, on the S. bdy. of the Tp., hereinbefore described.</p> <p>N. 0°03' W., bet. secs. 32 and 33.</p> <p>Over rolling land.</p>
40.00	Point for the 1/4 sec. cor. of secs. 32 and 33.
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with brass cap mkd.

Survey of the Subdivisional Lines,
T. 37 N., R. 11 E., Gila and Salt River Meridian, Arizona

CHAINS	
	T 37 N R 11 E 1/4 S 32 S 33 2012
	Deposit a magnet, in a white plastic case, at the base of the stainless steel post.
55.50	Dirt road, 8 ft. wide, bears N. 45° E. and S. 45° W.
62.15	Dirt road, 8 ft. wide, bears N. 85° E. and S. 85° W.
80.00	Point for the cor. of secs. 28, 29, 32 and 33.
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.
	T 37 N R 11 E S 29 S 28 S 32 S 33 2012
	Deposit a magnet, in a white plastic case, at the base of the stainless steel post.
	Land, rolling. Soil, sandy loam. Timber, juniper and pinon. Undergrowth, native grasses, sage brush and Mormon tea.
	From the cor. of secs. 27, 28, 33 and 34.
	West, bet. secs. 28 and 33.
	Over rolling land.
40.00	Point for the 1/4 sec. cor. of secs. 28 and 33.
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.
	T 37 N R 11 E S 28 1/4 ——— S 33 2012

Survey of the Subdivisional Lines,
T. 37 N., R. 11 E., Gila and Salt River Meridian, Arizona

CHAINS	
	Deposit a magnet, in a white plastic case, at the base of the stainless steel post.
44.70	Dirt road, 8 ft. wide, bears N. 65° E. and S. 65° W.
51.40	From this point, the pump shaft of a windmill, 6 ins. diam., firmly set in a concrete pad, 2 ft. high, bears S., 6.30 chs. dist. There is a livestock tank alongside, 40 ft. diam., 7 ft. high, mkd. IK-221.
80.00	The cor. of secs. 28, 29, 32 and 33. Land, rolling. Soil, sandy loam. Timber, juniper and pinon. Undergrowth, native grasses, sage brush and Mormon tea.
	N. 0°03' W., bet. secs. 28 and 29. Over rolling land.
40.00	Point for the 1/4 sec. cor. of secs. 28 and 29. Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 25 ins. in the ground, with brass cap mkd. <div style="text-align: center;"> T 37 N R 11 E 1/4 S 29 S 28 2012 </div>
80.00	Deposit a magnet, in a white plastic case, at the base of the stainless steel post. Point for the cor. of secs. 20, 21, 28 and 29. Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 25 ins. in the ground, with brass cap mkd. <div style="text-align: center;"> T 37 N R 11 E S 20 S 21 S 29 S 28 2012 </div>
	Deposit a magnet, in a white plastic case, at the base of the stainless steel post.

Survey of the Subdivisional Lines,
T. 37 N., R. 11 E., Gila and Salt River Meridian, Arizona

CHAINS	
	<p>Land, rolling. Soil, sandy loam. Timber, juniper and pinon. Undergrowth, native grasses, sage brush and Mormon tea.</p> <hr/> <p>From the cor. of secs. 21, 22, 27 and 28.</p> <p>West, bet. secs. 21 and 28.</p> <p>Over rolling land.</p>
40.00	<p>Point for the 1/4 sec. cor. of secs. 21 and 28.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T 37 N R 11 E S 21 1/4 ——— S 28</p> <p style="text-align: center;">2012</p> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p>
80.00	<p>The cor. of secs. 20, 21, 28 and 29.</p> <p>Land, rolling. Soil, sandy loam and sandstone outcrops. Timber, juniper and pinon. Undergrowth, native grasses, sage brush and Mormon tea.</p> <hr/> <p>N. 0°03' W., bet. secs. 20 and 21.</p> <p>Over rolling land.</p>
40.00	<p>Point for the 1/4 sec. cor. of secs. 20 and 21.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in sandstone bedrock, with brass cap mkd.</p> <p style="text-align: center;">T 37 N R 11 E 1/4 S 20 S 21</p> <p style="text-align: center;">2012</p> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p>

Survey of the Subdivisional Lines,
T. 37 N., R. 11 E., Gila and Salt River Meridian, Arizona

CHAINS									
80.00	<p>Point for the cor. of secs. 16, 17, 20 and 21.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 25 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center;"> <table style="margin: auto;"> <tr> <td>T 37 N</td> <td>R 11 E</td> </tr> <tr> <td style="border-right: 1px solid black;">S 17</td> <td>S 16</td> </tr> <tr> <td style="border-right: 1px solid black;">S 20</td> <td>S 21</td> </tr> </table> <p>2012</p> </div> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p> <p>Land, rolling. Soil, sandy loam. Timber, juniper and pinon. Undergrowth, native grasses, sage brush and Mormon tea.</p> <hr/> <p>From the cor. of secs. 15, 16, 21 and 22.</p> <p>West, bet. secs. 16 and 21.</p> <p>Over rolling land.</p>	T 37 N	R 11 E	S 17	S 16	S 20	S 21		
T 37 N	R 11 E								
S 17	S 16								
S 20	S 21								
40.00	<p>Point for the 1/4 sec. cor. of secs. 16 and 21.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 25 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center;"> <table style="margin: auto;"> <tr> <td>T 37 N</td> <td>R 11 E</td> </tr> <tr> <td></td> <td>S 16</td> </tr> <tr> <td>1/4</td> <td style="border-top: 1px solid black;">———</td> </tr> <tr> <td></td> <td>S 21</td> </tr> </table> <p>2012</p> </div> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p>	T 37 N	R 11 E		S 16	1/4	———		S 21
T 37 N	R 11 E								
	S 16								
1/4	———								
	S 21								
80.00	<p>The cor. of secs. 16, 17, 20 and 21.</p> <p>Land, rolling. Soil, sandy loam. Timber, juniper and pinon. Undergrowth, native grasses, sage brush and Mormon tea.</p> <hr/> <p>N. 0°03' W., bet. secs. 16 and 17.</p> <p>Over rolling land.</p>								

Survey of the Subdivisional Lines,
T. 37 N., R. 11 E., Gila and Salt River Meridian, Arizona

CHAINS	
40.00	<p>Point for the 1/4 sec. cor. of secs. 16 and 17.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 20 ins. in sandstone bedrock, encircled with a collar of stone, with brass cap mkd.</p> <p style="text-align: center;">T 37 N R 11 E 1/4 S 17 S 16</p> <p style="text-align: center;">2012</p> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p>
80.00	<p>Point for the cor. of secs. 8, 9, 16 and 17.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T 37 N R 11 E S 8 S 9 S 17 S 16</p> <p style="text-align: center;">2012</p> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p> <p>Land, rolling. Soil, sandy loam and sandstone outcrops. Timber, juniper and pinon. Undergrowth, native grasses, sage and rabbit brush.</p> <hr/> <p>From the cor. of secs. 9, 10, 15 and 16.</p> <p>West, bet. secs. 9 and 16.</p> <p>Over rolling land.</p>
35.30	E. right-of-way fence of Black Mesa and Lake Powell Railroad, woven and barbed wire, parallels railroad.
36.95	Black Mesa and Lake Powell Railroad, 5 ft. bet. rails, bears S. 55° E., curving S., and N. 55° W.
38.60	W. right-of-way fence of Black Mesa and Lake Powell Railroad, woven and barbed wire, parallels railroad.
40.00	Point for the 1/4 sec. cor. of secs. 9 and 16.

Survey of the Subdivisional Lines,
T. 37 N., R. 11 E., Gila and Salt River Meridian, Arizona

CHAINS	
	<p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T 37 N R 11 E S 9 1/4 ——— S 16</p> <p style="text-align: center;">2012</p> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p>
80.00	<p>The cor. of secs. 8, 9, 16 and 17.</p> <p>Land, rolling. Soil, sandy loam. Timber, juniper and pinon. Undergrowth, native grasses, sage and rabbit brush.</p> <hr/> <p>N. 0°03' W., bet. secs. 8 and 9.</p> <p>Over rolling land.</p>
19.60	S. right-of-way fence of Black Mesa and Lake Powell Railroad, woven and barbed wire, parallels railroad.
21.00	Black Mesa and Lake Powell Railroad, 5 ft. bet. rails, bears S. 65° E. and N. 65° W.
22.20	N. right-of-way fence of Black Mesa and Lake Powell Railroad, woven and barbed wire, parallels railroad.
40.00	<p>Point for the 1/4 sec. cor. of secs. 8 and 9.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T 37 N R 11 E 1/4 S 8 S 9</p> <p style="text-align: center;">2012</p> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p>
80.00	<p>Point for the cor. of secs. 4, 5, 8 and 9.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p>

Survey of the Subdivisional Lines,
T. 37 N., R. 11 E., Gila and Salt River Meridian, Arizona

CHAINS									
	<table style="margin-left: auto; margin-right: auto;"> <tr><td>T 37 N</td><td>R 11 E</td></tr> <tr><td>S 5</td><td>S 4</td></tr> <tr><td>S 8</td><td>S 9</td></tr> </table>	T 37 N	R 11 E	S 5	S 4	S 8	S 9		
T 37 N	R 11 E								
S 5	S 4								
S 8	S 9								
	2012								
	Deposit a magnet, in a white plastic case, at the base of the stainless steel post.								
	Raise a mound of stone, 2 ft. base, 1 1/2 ft. high, W. of cor.								
	Land, rolling.								
	Soil, sandy loam and sandstone outcrops.								
	Timber, juniper.								
	Undergrowth, native grasses, sage and rabbit brush.								
	<hr/>								
	From the cor. of secs. 3, 4, 9 and 10.								
	West, bet. secs. 4 and 9.								
	Over rolling land.								
11.45	The centerline of power line right-of-way, bears S. 65° E. and N. 65° W.								
40.00	Point for the 1/4 sec. cor. of secs. 4 and 9.								
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.								
	<table style="margin-left: auto; margin-right: auto;"> <tr><td>T 37 N</td><td>R 11 E</td></tr> <tr><td>S 4</td><td></td></tr> <tr><td>1/4</td><td>—</td></tr> <tr><td>S 9</td><td></td></tr> </table>	T 37 N	R 11 E	S 4		1/4	—	S 9	
T 37 N	R 11 E								
S 4									
1/4	—								
S 9									
	2012								
	Deposit a magnet, in a white plastic case, at the base of the stainless steel post.								
80.00	The cor. of secs. 4, 5, 8 and 9.								
	Land, rolling.								
	Soil, sandy loam and sandstone outcrops.								
	Timber, juniper.								
	Undergrowth, native grasses, sage and rabbit brush.								
	<hr/>								
	N. 0°03' W., bet. secs. 4 and 5.								
	Over rolling land.								

Survey of the Subdivisional Lines,
T. 37 N., R. 11 E., Gila and Salt River Meridian, Arizona

CHAINS	
13.70	Dirt road, 8 ft. wide, bears N. 85° E. and S. 85° W.
40.00	Point for the 1/4 sec. cor. of secs. 4 and 5. Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd. T 37 N R 11 E 1/4 S 5 S 4 2012 Deposit a magnet, in a white plastic case, at the base of the stainless steel post.
69.70	The centerline of power line right-of-way, bears S. 45° E. and N. 45° W.
80.00	The cor. of secs. 4, 5, 32 and 33, on the N. bdy. of the Tp., hereinbefore described. Land, rolling. Soil, sandy loam and sandstone outcrops. Timber, juniper. Undergrowth, native grasses, sage and rabbit brush.
	<hr/>
	From the stan. cor. of secs. 31 and 32, on the S. bdy. of the Tp., hereinbefore described. N. 0°03' W., bet. secs. 31 and 32. Over rolling land.
40.00	Point for the 1/4 sec. cor. of secs. 31 and 32. Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd. T 37 N R 11 E 1/4 S 31 S 32 2012 Deposit a magnet, in a white plastic case, at the base of the stainless steel post.
80.00	Point for the cor. of secs. 29, 30, 31 and 32. Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 25 ins. in the ground, with brass cap mkd.

Survey of the Subdivisional Lines,
T. 37 N., R. 11 E., Gila and Salt River Meridian, Arizona

CHAINS									
	<table style="margin-left: auto; margin-right: auto;"> <tr> <td>T 37 N</td> <td>R 11 E</td> </tr> <tr> <td>S 30</td> <td>S 29</td> </tr> <tr> <td>S 31</td> <td>S 32</td> </tr> </table>	T 37 N	R 11 E	S 30	S 29	S 31	S 32		
T 37 N	R 11 E								
S 30	S 29								
S 31	S 32								
	2012								
	Deposit a magnet, in a white plastic case, at the base of the stainless steel post.								
	Land, rolling. Soil, sandy loam. Timber, juniper and pinon. Undergrowth, native grasses, sage brush and Mormon tea.								
	<hr/>								
	From the cor. of secs. 28, 29, 32 and 33.								
	West, bet. secs. 29 and 32.								
	Over rolling land.								
40.00	Point for the 1/4 sec. cor. of secs. 29 and 32.								
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.								
	<table style="margin-left: auto; margin-right: auto;"> <tr> <td>T 37 N</td> <td>R 11 E</td> </tr> <tr> <td></td> <td>S 29</td> </tr> <tr> <td>1/4</td> <td><hr/></td> </tr> <tr> <td></td> <td>S 32</td> </tr> </table>	T 37 N	R 11 E		S 29	1/4	<hr/>		S 32
T 37 N	R 11 E								
	S 29								
1/4	<hr/>								
	S 32								
	2012								
	Deposit a magnet, in a white plastic case, at the base of the stainless steel post.								
80.00	The cor. of secs. 29, 30, 31 and 32.								
	Land, rolling. Soil, sandy loam and sandstone outcrops. Timber, juniper and pinon. Undergrowth, native grasses, sage brush and Mormon tea.								
	<hr/>								
	West, bet. secs. 30 and 31.								
	Over rolling land.								
40.00	Point for the 1/4 sec. cor. of secs. 30 and 31.								
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.								

Survey of the Subdivisional Lines,
T. 37 N., R. 11 E., Gila and Salt River Meridian, Arizona

CHAINS	
	T 37 N R 11 E S 30 1/4 ——— S 31 2012
	Deposit a magnet, in a white plastic case, at the base of the stainless steel post.
79.91	The cor. of secs. 25, 30, 31 and 36, on the W. bdy. of the Tp., hereinbefore described. Land, rolling. Soil, sandy loam. Timber, juniper and pinon. Undergrowth, native grasses, sage brush and Mormon tea.
	From the cor. of secs. 29, 30, 31 and 32. N. 0°03' W., bet. secs. 29 and 30. Over rolling land.
40.00	Point for the 1/4 sec. cor. of secs. 29 and 30. Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in sandstone bedrock, with brass cap mkd.
	T 37 N R 11 E 1/4 S 30 S 29 2012
	Deposit a magnet, in a white plastic case, at the base of the stainless steel post.
80.00	Point for the cor. of secs. 19, 20, 29 and 30. Set a brass tablet, 3 1/2 ins. diam., 2 1/4 ins. stem, cemented in a drill hole in solid sandstone boulder, 5 ft x 4 ft. x 1 1/2 ft., with top mkd.
	T 37 N R 11 E S 19 S 20 S 30 S 29 2012

Survey of the Subdivisional Lines,
T. 37 N., R. 11 E., Gila and Salt River Meridian, Arizona

CHAINS	
	<p>Deposit a magnet, in a white plastic case, at the base of the brass tablet.</p> <p>Land, rolling. Soil, sandy loam and sandstone outcrops. Timber, juniper and pinon. Undergrowth, native grasses, sage brush and Mormon tea.</p> <hr/> <p>From the cor. of secs. 20, 21, 28 and 29.</p> <p>West, bet. secs. 20 and 29.</p> <p>Over rolling land.</p>
40.00	<p>Point for the 1/4 sec. cor. of secs. 20 and 29.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T 37 N R 11 E S 20 1/4 ——— S 29</p> <p style="text-align: center;">2012</p>
	<p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p>
80.00	<p>The cor. of secs. 19, 20, 29 and 30.</p> <p>Land, rolling. Soil, sandy loam and sandstone outcrops. Timber, juniper and pinon. Undergrowth, native grasses and Mormon tea.</p> <hr/> <p>West, bet. secs. 19 and 30.</p> <p>Over rolling land.</p>
40.00	<p>Point for the 1/4 sec. cor. of secs. 19 and 30.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T 37 N R 11 E S 19 1/4 ——— S 30</p> <p style="text-align: center;">2012</p>

Survey of the Subdivisional Lines,
T. 37 N., R. 11 E., Gila and Salt River Meridian, Arizona

CHAINS	
	<p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p>
79.82	<p>The cor. of secs. 19, 24, 25 and 30, on the W. bdy. of the Tp., hereinbefore described.</p> <p>Land, rolling. Soil, sandy loam. Timber, juniper and pinon. Undergrowth, native grasses, sage brush and Mormon tea.</p> <hr/> <p>From the cor. of secs. 19, 20, 29 and 30.</p> <p>N. 0°03' W., bet. secs. 19 and 20.</p> <p>Over rolling land.</p>
40.00	<p>Point for the 1/4 sec. cor. of secs. 19 and 20.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 25 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T 37 N R 11 E 1/4 S 19 S 20</p> <p style="text-align: center;">2012</p> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p>
80.00	<p>Point for the cor. of secs. 17, 18, 19 and 20.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 21 ins. in sandstone bedrock, with brass cap mkd.</p> <p style="text-align: center;">T 37 N R 11 E S 18 S 17 S 19 S 20</p> <p style="text-align: center;">2012</p> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p> <p>Land, rolling. Soil, sandy loam and sandstone outcrops Timber, juniper and pinon. Undergrowth, native grasses and Mormon tea.</p> <hr/>

Survey of the Subdivisional Lines,
T. 37 N., R. 11 E., Gila and Salt River Meridian, Arizona

CHAINS	
	<p>From the cor. of secs. 16, 17, 20 and 21.</p> <p>West, bet. secs. 17 and 20.</p> <p>Over rolling land.</p>
40.00	<p>Point for the 1/4 sec. cor. of secs. 17 and 20.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T 37 N R 11 E S 17 1/4 ——— S 20</p> <p style="text-align: center;">2012</p> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p>
80.00	<p>The cor. of secs. 17, 18, 19 and 20.</p> <p>Land, rolling. Soil, sandy loam. Timber, no timber. Undergrowth, native grasses, sage brush and Mormon tea.</p> <hr/> <p>West, bet. secs. 18 and 19.</p> <p>Over rolling land.</p>
40.00	<p>Point for the 1/4 sec. cor. of secs. 18 and 19.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 25 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T 37 N R 11 E S 18 1/4 ——— S 19</p> <p style="text-align: center;">2012</p> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p>
79.73	<p>The cor. of secs. 13, 18, 19 and 24, on the W. bdy. of the Tp., hereinbefore described.</p>

Survey of the Subdivisional Lines,
T. 37 N., R. 11 E., Gila and Salt River Meridian, Arizona

CHAINS	
	<p>Land, rolling. Soil, sandy loam. Timber, juniper and pinon. Undergrowth, native grasses, sage brush and Mormon tea.</p> <hr/> <p>From the cor. of secs. 17, 18, 19 and 20. N. 0°03' W., bet. secs. 17 and 18. Over rolling land.</p>
15.10	The centerline of power line right-of-way, bears S. 50° E. and N. 50° W.
40.00	<p>Point for the 1/4 sec. cor. of secs. 17 and 18.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 25 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T 37 N R 11 E 1/4 S 18 S 17</p> <p style="text-align: center;">2012</p> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p>
57.25	Dirt road, 8 ft. wide, bears S. 80° E. and N. 80° W.
80.00	<p>Point for the cor. of secs. 7, 8, 17 and 18, located on steep edge of sandstone outcrop, where it is impracticable to set a permanent monument.</p> <p>From this true point, the point selected for a witness cor. to the cor. of secs. 7, 8, 17 and 18, bears S. 70°00' E., 1.52 chs. dist.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">WC T 37 N R 11 E ← S 7 S 8 S 18 S 17</p> <p style="text-align: center;">2012</p> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p>

Survey of the Subdivisional Lines,
T. 37 N., R. 11 E., Gila and Salt River Meridian, Arizona

CHAINS	
	<p>Land, rolling. Soil, sandy loam. Timber, juniper and pinon. Undergrowth, native grasses, sage brush and Mormon tea.</p> <hr/> <p>From the cor. of secs. 8, 9, 16 and 17.</p> <p>West, bet. secs. 8 and 17.</p> <p>Over rolling land.</p>
36.30	Dirt road, 8 ft. wide, bears S. 15° E. and N. 15° W.
40.00	Point for the 1/4 sec. cor. of secs. 8 and 17.
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.
	<p>T 37 N R 11 E S 8 1/4 ——— S 17</p> <p>2012</p>
	Deposit a magnet, in a white plastic case, at the base of the stainless steel post.
80.00	The true point for the cor. of secs. 7, 8, 17 and 18.
	<p>Land, rolling. Soil, sandy loam. Timber, juniper and pinon. Undergrowth, native grasses, sage brush and Mormon tea.</p> <hr/> <p>West, bet. secs. 7 and 18.</p> <p>Over rolling land.</p>
26.30	The centerline of power line right-of-way, bears S. 20° E. and N. 20° W.
29.65	Dirt road, 8 ft. wide, bears S. 5° E. and N. 5° W.
40.00	Point for the 1/4 sec. cor. of secs. 7 and 18.
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.

Survey of the Subdivisional Lines,
T. 37 N., R. 11 E., Gila and Salt River Meridian, Arizona

CHAINS	
	T 37 N R 11 E S 7 1/4 ——— S 18 2012
	Deposit a magnet, in a white plastic case, at the base of the stainless steel post. Set a steel fence post nearby.
79.63	The cor. of secs. 7, 12, 13 and 18, on the W. bdy. of the Tp., hereinbefore described. Land, rolling. Soil, sandy loam. Timber, juniper and pinon. Undergrowth, native grasses, sage brush and Mormon tea.
	From the true point for the cor. of secs. 7, 8, 17 and 18. N. 0°03' W., bet. secs. 7 and 8. Over rolling land.
40.00	Point for the 1/4 sec. cor. of secs. 7 and 8. Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 25 ins. in the ground, with brass cap mkd.
	T 37 N R 11 E 1/4 S 7 S 8 2012
	Deposit a magnet, in a white plastic case, at the base of the stainless steel post.
80.00	Point for the cor. of secs. 5, 6, 7 and 8. Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.
	T 37 N R 11 E S 6 S 5 S 7 S 8 2012

Survey of the Subdivisional Lines,
T. 37 N., R. 11 E., Gila and Salt River Meridian, Arizona

CHAINS	
	<p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p> <p>Land, rolling. Soil, sandy loam. Timber, juniper and sparse pinon. Undergrowth, native grasses, sage brush and Mormon tea.</p> <hr/> <p>From the cor. of secs. 4, 5, 8 and 9.</p> <p>West, bet. secs. 5 and 8.</p> <p>Over rolling land.</p>
17.40	Dirt road, 8 ft. wide, bears N. 45° E. and S. 45° W.
40.00	<p>Point for the 1/4 sec. cor. of secs. 5 and 8.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 23 ins. in sandstone bedrock, with brass cap mkd.</p> <div style="text-align: center;"> <p>T 37 N R 11 E</p> <p>S 5</p> <p>1/4 ———</p> <p>S 8</p> <p>2012</p> </div>
	<p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p>
72.45	E. right-of-way fence of Black Mesa and Lake Powell Railroad, woven and barbed wire, parallels railroad.
73.35	Black Mesa and Lake Powell Railroad, 5 ft. bet. rails, bears S. 35° E. and N. 35° W.
74.30	W. right-of-way fence of Black Mesa and Lake Powell Railroad, woven and barbed wire, parallels railroad.
80.00	<p>The cor. of secs. 5, 6, 7 and 8.</p> <p>Land, rolling. Soil, sandy loam. Timber, juniper and sparse pinon. Undergrowth, native grasses, sage brush and Mormon tea.</p> <hr/> <p>West, bet. secs. 6 and 7.</p> <p>Over rolling land.</p>

Survey of the Subdivisional Lines,
T. 37 N., R. 11 E., Gila and Salt River Meridian, Arizona

CHAINS	
32.15	Dirt road, 8 ft. wide, bears S. 10° E. and N. 10° W.
40.00	Point for the 1/4 sec. cor. of secs. 6 and 7. Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 22 ins. in sandstone bedrock, encircled with a collar of stone with brass cap mkd. <div style="text-align: center;"> T 37 N R 11 E S 6 1/4 ——— S 7 2012 </div> Deposit a magnet, in a white plastic case, at the base of the stainless steel post. Set a steel fence post nearby.
51.55	The centerline of power line right-of-way, bears S. 20° E. and N. 20° W.
79.54	The cor. of secs. 1, 6, 7 and 12, on the W. bdy. of the Tp., hereinbefore described. Land, rolling. Soil, sandy loam. Timber, juniper and sparse pinon. Undergrowth, native grasses, sage brush and Mormon tea.
	<hr/> From the cor. of secs. 5, 6, 7 and 8. N. 0°03' W., bet. secs. 5 and 6. Over rolling land.
8.60	S. right-of-way fence of Black Mesa and Lake Powell Railroad, woven and barbed wire, parallels railroad.
10.05	Black Mesa and Lake Powell Railroad, 5 ft. bet. rails, bears S. 30° E. and N. 30° W.
11.60	N. right-of-way fence of Black Mesa and Lake Powell Railroad, woven and barbed wire, parallels railroad.
40.00	Point for the 1/4 sec. cor. of secs. 5 and 6. Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 22 ins. in the ground to sandstone bedrock, encircled with a collar of stone with brass cap mkd.

Survey of the Subdivisional Lines,
T. 37 N., R. 11 E., Gila and Salt River Meridian, Arizona

CHAINS	
	T 37 N R 11 E 1/4 S 6 S 5 2012
	Deposit a magnet, in a white plastic case, at the base of the stainless steel post.
80.00	The cor. of secs. 5, 6, 31 and 32, on the N. bdy. of the Tp. hereinbefore described.
	Land, rolling. Soil, sandy loam. Timber, juniper and sparse pinon. Undergrowth, native grasses, sage brush and Mormon tea.
	<hr/> Subdivision of Section 3, T. 37 N., R. 11 E., Gila and Salt River Meridian, Arizona <hr/>
	From the 1/4 sec. cor. of secs. 3 and 10.
	N. 0°02' W., on the N. and S. center line of sec. 3.
	Over rolling land.
40.00	Point for the center 1/4 sec. cor. of sec. 3, at intersection with the E. and W. center line of sec. 3.
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with brass cap mkd.
	T 37 N R 11 E C 1/4 S 3 2012
	Deposit a magnet, in a white plastic case, at the base of the stainless steel post.
80.00	The 1/4 sec. cor. of secs. 3 and 34, on the N. bdy. of the Tp.
	<hr/> From the 1/4 sec. cor. of secs. 2 and 3. West, on the E. and W. center line of sec. 3. Over rolling land.
40.00	The center 1/4 sec. cor. of sec. 3.

Subdivision of Section 3,
T. 37 N., R. 11 E., Gila and Salt River Meridian, Arizona

CHAINS	
80.00	The 1/4 sec. cor. of secs. 3 and 4.
<hr/> <p>Subdivision of Section 4, T. 37 N., R. 11 E., Gila and Salt River Meridian, Arizona</p> <hr/>	
	From the 1/4 sec. cor. of secs. 4 and 9.
	N. 0°02' W., on the N. and S. center line of sec. 4.
	Over rolling land.
26.25	The centerline of power line right-of-way, bears S. 45° E. and N. 45° W.
40.00	Point for the center 1/4 sec. cor. of sec. 4, at intersection with the E. and W. center line of sec. 4.
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground to sandstone bedrock, with brass cap mkd.
	T 37 N R 11 E C 1/4 S 4 2012
	Deposit a magnet, in a white plastic case, at the base of the stainless steel post.
70.05	S. right-of-way fence of State Highway 98, barbed wire, 4 strand, parallels highway.
72.45	State Highway 98, an asphalt surfaced road, 35 ft. wide, bears S. 40° E. and N. 40° W.
74.75	N. right-of-way fence of State Highway 98, barbed wire, 4 strand, parallels highway.
80.00	The 1/4 sec. cor. of secs. 4 and 33, on the N. bdy. of the Tp.
	From the 1/4 sec. cor. of secs. 3 and 4.
	West, on the E. and W. center line of sec. 4.
	Over rolling land.
10.90	E. right-of-way fence of State Highway 98, barbed wire, 4 strand, parallels highway.
12.85	State Highway 98, an asphalt surfaced road, 35 ft. wide, bears S. 40° E. and N. 40° W.

Subdivision of Section 4,
T. 37 N., R. 11 E., Gila and Salt River Meridian, Arizona

CHAINS	
14.80	W. right-of-way fence of State Highway 98, barbed wire, 4 strand, parallels highway.
40.00	The center 1/4 sec. cor. of sec. 4.
52.65	The centerline of power line right-of-way, bears S. 45° E. and N. 45° W.
62.40	Dirt road, 8 ft. wide, bears S. 35° E. and N. 35° W.
80.00	The 1/4 sec. cor. of secs. 4 and 5.
<hr/> <p>Subdivision of Section 10, T. 37 N., R. 11 E., Gila and Salt River Meridian, Arizona</p> <hr/>	
	From the 1/4 sec. cor. of secs. 10 and 15.
	N. 0°02' W., on the N. and S. center line of sec. 10.
	Over rolling land.
40.00	Point for the center 1/4 sec. cor. of sec. 10, at intersection with the E. and W. center line of sec. 10.
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground to sandstone bedrock, with brass cap mkd.
	T 37 N R 11 E C 1/4 S 10
	2012
	Deposit a magnet, in a white plastic case, at the base of the stainless steel post.
44.20	The centerline of power line right-of-way, bears S. 50° E. and N. 50° W.
44.75	S. right-of-way fence of State Highway 98, barbed wire, 4 strand, parallels highway.
46.90	State Highway 98, an asphalt surfaced road, 35 ft. wide, bears S. 45° E. and N. 45° W.
49.10	N. right-of-way fence of State Highway 98, barbed wire, 4 strand, parallels highway.
80.00	The 1/4 sec. cor. of secs. 3 and 10.

Subdivision of Section 10,
T. 37 N., R. 11 E., Gila and Salt River Meridian, Arizona

CHAINS	
	From the 1/4 sec. cor. of secs. 10 and 11. West, on the E. and W. center line of sec. 10. Over rolling land.
30.35	E. right-of-way fence of State Highway 98, barbed wire, 4 strand, parallels highway.
32.60	State Highway 98, an asphalt surfaced road, 35 ft. wide, bears S. 45° E. and N. 45° W.
34.85	W. right-of-way fence of State Highway 98, barbed wire, 4 strand, parallels highway.
35.35	The centerline of power line right-of-way, bears S. 50° E. and N. 50° W.
40.00	The center 1/4 sec. cor. of sec. 10.
80.00	The 1/4 sec. cor. of secs. 9 and 10.
<hr/> <p>Subdivision of Section 11, T. 37 N., R. 11 E., Gila and Salt River Meridian, Arizona</p> <hr/>	
	From the 1/4 sec. cor. of secs. 11 and 14. N. 0°01' W., on the N. and S. center line of sec. 11. Over rolling land.
9.51	From this point, the pump shaft of a windmill, 6 ins. diam., firmly set in a concrete pad, bears W., 6.32 chs. dist. There is a livestock tank alongside, 42 ft. diam., 5 ft. high, mkd. IK-220.
40.00	Point for the center 1/4 sec. cor. of sec. 11, at intersection with the E. and W. center line of sec. 11. Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with brass cap mkd.
	<p>T 37 N R 11 E C 1/4 S 11</p> <p>2012</p>
	Deposit a magnet, in a white plastic case, at the base of the stainless steel post.
80.00	The 1/4 sec. cor. of secs. 2 and 11.

Subdivision of Section 11,
T. 37 N., R. 11 E., Gila and Salt River Meridian, Arizona

CHAINS	
	<hr/> <p>From the 1/4 sec. cor. of secs. 11 and 12. West, on the E. and W. center line of sec. 11. Over rolling land.</p>
40.00	The center 1/4 sec. cor. of sec. 11.
80.00	The 1/4 sec. cor. of secs. 10 and 11.
	<hr/> <p style="text-align: center;">Subdivision of Section 13, T. 37 N., R. 11 E., Gila and Salt River Meridian, Arizona</p> <hr/>
	<p>From the 1/4 sec. cor. of secs. 13 and 24. North, on the N. and S. center line of sec. 13. Over rolling land.</p>
40.00	Point for the center 1/4 sec. cor. of sec. 13, at intersection with the E. and W. center line of sec. 13. Set a brass tablet, 3 1/8 ins. diam., 2 1/2 ins. stem, cemented in a drill hole in solid sandstone bedrock, with top mkd.
	<p>T 37 N R 11 E C 1/4 S 13</p> <p>2012</p>
	Deposit a magnet, without plastic case, at the base of the brass tablet.
80.00	The 1/4 sec. cor. of secs. 12 and 13.
	<hr/> <p>From the 1/4 sec. cor. of secs. 13 and 18, on the E. bdy. of the Tp., monumented with a stainless steel post, 2 1/2 ins. diam., firmly set, projecting 1 in. above the ground, with brass cap mkd. T37N R11E R12E 1/4 S13 S18 2007. Add the marks 2012 to the brass cap. West, on the E. and W. center line of sec. 13. Over rolling land.</p>
40.00	The center 1/4 sec. cor. of sec. 13.

Subdivision of Section 13,
T. 37 N., R. 11 E., Gila and Salt River Meridian, Arizona

CHAINS	
80.00	The 1/4 sec. cor. of secs. 13 and 14.
<hr/> Subdivision of Section 14, T. 37 N., R. 11 E., Gila and Salt River Meridian, Arizona <hr/>	
	From the 1/4 sec. cor. of secs. 14 and 23.
	N. 0°01' W., on the N. and S. center line of sec. 14.
	Over rolling land.
40.00	Point for the center 1/4 sec. cor. of sec. 14, at intersection with the E. and W. center line of sec. 14.
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 27 ins. in the ground, with brass cap mkd.
	T 37 N R 11 E C 1/4 S 14 2012
	Deposit a magnet, in a white plastic case, at the base of the stainless steel post.
52.55	S. right-of-way fence of State Highway 98, barbed wire, 4 strand, parallels highway.
54.55	State Highway 98, an asphalt surfaced road, 35 ft. wide, bears S. 45° E. and N. 45° W.
56.55	N. right-of-way fence of State Highway 98, barbed wire, 4 strand, parallels highway.
80.00	The 1/4 sec. cor. of secs. 11 and 14.
	From the 1/4 sec. cor. of secs. 13 and 14.
	West, on the E. and W. center line of sec. 14.
	Over rolling land.
21.60	E. right-of-way fence of State Highway 98, barbed wire, 4 strand, parallels highway.
23.85	State Highway 98, an asphalt surfaced road, 35 ft. wide, bears S. 45° E. and N. 45° W.
26.10	W. right-of-way fence of State Highway 98, barbed wire, 4 strand, parallels highway.

Subdivision of Section 14,
T. 37 N., R. 11 E., Gila and Salt River Meridian, Arizona

CHAINS	
40.00	The center 1/4 sec. cor. of sec. 14.
47.85	Dirt road, 8 ft. wide, bears N. and S.
80.00	The 1/4 sec. cor. of secs. 14 and 15.
<hr/> <p style="text-align: center;">Subdivision of Section 24, T. 37 N., R. 11 E., Gila and Salt River Meridian, Arizona</p> <hr/>	
	From the 1/4 sec. cor. of secs. 24 and 25.
	North, on the N. and S. center line of sec. 24.
	Over rolling land.
40.00	Point for the center 1/4 sec. cor. of sec. 24, at intersection with the E. and W. center line of sec. 24.
	Set a brass tablet, 3 1/8 ins. diam., 2 1/2 ins. stem, cemented in a drill hole in solid sandstone bedrock, with top mkd.
	<p>T 37 N R 11 E C 1/4 S 24</p> <p>2012</p>
	Deposit a magnet, without plastic case, at the base of the brass tablet.
60.35	S. right-of-way fence of State Highway 98, barbed wire, 4 strand, parallels highway.
62.40	State Highway 98, an asphalt surfaced road, 35 ft. wide, bears S. 45° E. and N. 45° W.
64.40	N. right-of-way fence of State Highway 98, barbed wire, 4 strand, parallels highway.
80.00	The 1/4 sec. cor. of secs. 13 and 24.
	<hr/> <p>From the 1/4 sec. cor. of secs. 19 and 24, on the E. bdy. of the Tp., monumented with a stainless steel post, 2 1/2 ins. diam., firmly set, 4 ins. below the ground, with brass cap mkd. T37N R11E R12E 1/4 S24 S19 2007.</p> <p>Add the marks 2012 to the brass cap.</p> <p>West, on the E. and W. center line of sec. 24.</p>


Subdivision of Section 24,
T. 37 N., R. 11 E., Gila and Salt River Meridian, Arizona

CHAINS	
	Over rolling land.
12.90	E. right-of-way fence of State Highway 98, barbed wire, 4 strand, parallels highway.
15.15	State Highway 98, an asphalt surfaced road, 35 ft. wide, bears S. 45° E. and N. 45° W.
17.40	W. right-of-way fence of State Highway 98, barbed wire, 4 strand, parallels highway.
40.00	The center 1/4 sec. cor. of sec. 24.
80.00	The 1/4 sec. cor. of secs. 23 and 24.
<hr/> GENERAL DESCRIPTION <hr/>	
<p>The area surveyed is within the Navajo Indian Reservation, is 9 miles northwest of the Kaibeto community, and 20 miles southeast of Page, Arizona. Primary access is along State Highway 98. Multiple unnamed main dirt roads and a series of track roads provide access throughout the township. ATV's were required to access the majority of the areas within the township.</p> <p>There are no major housing developments, only smaller housing clusters and single homes scattered throughout the township. During the course of this survey, construction of utility power lines were in place, particularly in the northern part of the township, and were not active lines as of yet. The Black Mesa and Lake Powell Railroad that supplies coal to the Navajo power plant in Page, meanders from the southeast to the northwest.</p> <p>The highest elevation of this survey, 6300 feet above sea level, is in the southern portion of the township, in the foothills. The lowest elevation, at 5500 feet is in the plains of the northeast portion of the project.</p> <p>The vegetation consists of scattered juniper and pinon in the higher elevations, and sparse in the lower elevation, where sages, Mormon tea and grasses, are more prominent. There is presence of grazing cattle, sheep and horses in the area. The soil is mostly sandy loam with areas of sandstone outcrops.</p> <p>The mean magnetic declination of 11° E. was derived from the United States Geological Survey computer program GEOMAG, utilizing the World Magnetic Model for Epoch 2010-2015 for the dates of survey.</p> <hr/>	

CERTIFICATE OF SURVEY

I, Fabian Yazzie, Cadastral Surveyor, HEREBY CERTIFY upon honor, that in pursuance of special instructions bearing date of the 28th day of March, 2012, I have surveyed the Ninth Standard Parallel North (South Boundary), the West and North boundaries, the subdivisional lines, and the subdivision of certain sections, T. 37 N., R. 11 E., of the Gila and Salt River Meridian, in the State of Arizona, which are represented in the foregoing field notes as having been executed by me and under my direction. Said survey has been made in strict conformity with said special instructions, the Manual of Instructions for the Survey of the Public Lands of the United States, 2009, and in specific manner described in the foregoing field notes.

3/25/2013
(Date)



(Cadastral Surveyor)

CERTIFICATE OF APPROVAL

BUREAU OF LAND MANAGEMENT
Phoenix, Arizona

The foregoing field notes of the survey of the Ninth Standard Parallel North (South Boundary), the West and North boundaries, the subdivisional lines, and the subdivision of certain sections, T. 37 N., R. 11 E., Gila and Salt River Meridian, in the State of Arizona, executed by Fabian Yazzie, Cadastral Surveyor, having been critically examined and found correct, are hereby approved.

4/22/2013
(Date)


(Chief Cadastral Surveyor of Arizona)

~~CERTIFICATE OF TRANSCRIPT~~

~~I CERTIFY That the foregoing transcript of the field notes of the above described surveys in T. 37 N., R. 11 E., Gila and Salt River Meridian, Arizona, is a true copy of the original field notes.~~

~~_____~~
(Date)

~~_____~~
(Chief Cadastral Surveyor of Arizona)