

**ORIGINAL**

**UNITED STATES  
DEPARTMENT OF THE INTERIOR  
BUREAU OF LAND MANAGEMENT**

FIELD NOTES  
OF THE  
SUBDIVISION OF  
CERTAIN SECTIONS  
**TOWNSHIP 34 NORTH, RANGE 8 EAST,**  
OF THE GILA AND SALT RIVER MERIDIAN,  
IN THE STATE OF ARIZONA.

**EXECUTED BY**

**Craig S. Dukart, Cadastral Surveyor**

Under Special Instructions dated May 3, 2012, approved May 3, 2012, and Supplemental Special Instructions dated August 7, 2012, approved August 7, 2012, which provided for the surveys included under Group No. 1107, and assignment instructions dated May 3 and May 24, 2012.

**Survey commenced July 13, 2012**

**Survey completed August 18, 2012**

**INDEX DIAGRAM**

TOWNSHIP 34 NORTH            RANGE 8 EAST  
GILA AND SALT RIVER MERIDIAN, ARIZONA

SUBDIVISION OF CERTAIN SECTIONS

Subdivision of Section 2 .....	Pages	4-5
Subdivision of Section 3 .....	Pages	5-6
Subdivision of Section 11 .....	Pages	6-7
Subdivision of Section 13 .....	Pages	7-9
Subdivision of Section 14 .....	Pages	9-10
Subdivision of Section 24 .....	Pages	10-13
Subdivision of Section 25 .....	Pages	13-14

## T. 34 N., R. 8 E., Gila and Salt River Meridian, Arizona

## CHAINS

The following field notes describe the survey of the subdivision of certain sections, Township 34 North, Range 8 East, Gila and Salt River Meridian, Arizona.

The history of surveys pertaining to this survey is as follows:

Craig S. Dukart surveyed the Second Guide Meridian East (east boundary), south, west and north boundaries and the subdivisional lines in 2010.

The survey was executed in accordance with the specifications as set forth in the Manual of Instructions (2009), and the Supplemental Special Instructions dated August 7, 2012, for Group Number 1107, Arizona.

The true meridian direction and length of all lines were determined by real time kinematic global positioning system observations using Trimble Navigation 5700, 5800 and R8 model receivers.

The "standard monument" referred to in these notes is a stainless steel post, 28 ins. long, 2 1/2 ins. diam., with a brass cap. Unless otherwise indicated, a magnet in a white plastic case is deposited at the base of the stainless steel post.

Geodetic control was derived from Global Positioning System (GPS) static observations post processed by National Geodetic Survey, Online Positioning User Service (OPUS), utilizing Continuously Operating Reference Stations (CORS) DK8419 AZPG CITY OF PAGE CORS ARP, DL1882 AZFL NAU FLAGSTAFF CORS ARP, and AI8805 FRED FREDONIA CORS ARP. The NAD 83 (2011) (EPOCH: 2010), geographic position of the following two corners.

The 1/4 section corner of sections 25 and 36, is as follows:

Latitude: 36°18'33.10" N.                      Longitude: 111°29'30.85" W.

The 1/4 section corner of sections 2 and 35 on the north boundary of the township is as follows:

Latitude: 36°22'54.08" N.                      Longitude: 111°30'35.46" W.

## T. 34 N., R. 8 E., Gila and Salt River Meridian, Arizona

CHAINS	
	The mean magnetic declination is 11° E.
	<p style="text-align: center;">Subdivision of Section 2, T. 34 N., R. 8 E., Gila and Salt River Meridian, Arizona</p>
	From the 1/4 sec. cor. of secs. 2 and 11, monumented with a stainless steel post, 2 1/2 ins. diam., firmly set, projecting 4 ins. above the ground, with brass cap mkd. T34N R8E S2 1/4 S11 2010, with a steel "T-post" nearby.
	Add the marks 2012 to the brass cap.
	N. 0°01' W., on the N. and S. center line of sec. 2.
40.00	Point for the center 1/4 sec. cor. of sec. 2, at intersection with the E. and W. center line.
	Set a standard monument, 25 ins. in the ground, encircled with a collar of sandstone, mkd.
	T 34 N R 8 E
	C 1/4 S 2
	2012
	Set a steel "T-post" fence post near the cor.
80.00	The 1/4 sec. cor. of secs. 2 and 35, monumented with a stainless steel post, 2 1/2 ins. diam., firmly set, projecting 4 ins. above the ground, with brass cap mkd. T35N R8E S35 1/4 S2 T34N 2010.
	Add the marks 2012 to the brass cap.
	From the 1/4 sec. cor. of secs. 1 and 2, monumented with a stainless steel post, 2 1/2 ins. diam., firmly set, projecting 1 in. above the ground, with brass cap mkd. T34N R8E 1/4 S2 S1 2010, with a steel "T-post" nearby.
	Add the marks 2012 to the brass cap.
	West, on the E. and W. center line of sec. 2.
40.00	The center 1/4 sec. cor. of sec. 2.
64.10	Underground waterline, bears S. 20° E. and N. 20° W.
66.05	Easterly right-of-way fence, bears S. 22° E. and N. 22° W.

**Subdivision of Section 2,  
T. 34 N., R. 8 E., Gila and Salt River Meridian, Arizona**

CHAINS	
67.35	Easterly edge of Highway No. 89, asphalt surfaced, 40 ft. wide, bears S. 22° E. and N. 22° W.
68.00	Westerly edge of Highway No. 89, bears S. 22° E. and N. 22° W.
69.30	Westerly right-of-way fence, bears S. 22° E. and N. 22° W.
73.20	Utility line, 9 strand, bears S. 23° E. and N. 23° W.
80.00	The 1/4 sec. cor. of secs. 2 and 3, monumented with a stainless steel post, 2 1/2 ins. diam., firmly set, projecting 5 ins. above the ground, with brass cap mkd. T34N R8E 1/4 S3 S2 2010, with a steel "T-post" nearby.
	Add the marks 2012 to the brass cap.
<hr/> <p><b>Subdivision of Section 3, T. 34 N., R. 8 E., Gila and Salt River Meridian, Arizona</b></p> <hr/>	
	From the 1/4 sec. cor. of secs. 3 and 10, monumented with a stainless steel post, 2 1/2 ins. diam., firmly set, projecting 3 ins. above the ground, with brass cap mkd. T34N R8E S3 1/4 S10 2010, with a steel "T-post" nearby.
	Add the marks 2012 to the brass cap.
	N. 0°02' W., on the N. and S. center line of sec. 3.
40.00	Point for the center 1/4 sec. cor. of sec. 3, at intersection with the E. and W. center line.
	Set a standard monument, flush with the ground, mkd.
	T 34 N R 8 E
	C 1/4 S 3
	2012
	Raise a mound of stone, 3 ft. base, 4 1/2 ft. high, W. of cor.
80.00	The 1/4 sec. cor. of secs. 3 and 34, monumented with a stainless steel post, 2 1/2 ins. diam., firmly set, projecting 12 ins. above the ground, in a mound of sandstone, 2 ft. base, to brass cap mkd. T35N R8E S34 1/4 S3 T34N 2010, with an accessory mound of stone 3 ft. base, 2 1/2 ft. high, N. of cor.
	Add the marks 2012 to the brass cap.
	<hr/> From the the 1/4 sec. cor. of secs. 2 and 3.

Subdivision of Section 3,  
T. 34 N., R. 8 E., Gila and Salt River Meridian, Arizona

CHAINS	
	West, on the E. and W. center line of sec. 3.
40.00	The center 1/4 sec. cor. of sec. 3.
80.00	The 1/4 sec. cor. of secs. 3 and 4, monumented with a stainless steel post, 2 1/2 ins. diam., firmly set, projecting 1 in. above the ground, with brass cap mkd. T34N R8E 1/4 S4 S3 2010, with a steel "T-post" nearby.
	Add the marks 2012 to the brass cap.
<hr/> Subdivision of Section 11, T. 34 N., R. 8 E., Gila and Salt River Meridian, Arizona <hr/>	
	From the 1/4 sec. cor. of secs. 11 and 14, monumented with a stainless steel post, 2 1/2 ins. diam., firmly set, projecting 15 ins. above the ground, in a mound of stone, 4 ft. base, to brass cap mkd. T34N R8E S11 1/4 S14 2010.
	Add the marks 2012 to the brass cap.
	N. 0°01' W., on the N. and S. center line of sec. 11.
40.00	Point for the center 1/4 sec. cor. of sec. 11, at intersection with the E. and W. center line.
	Set a standard monument, flush with the ground, mkd.
	T 34 N R 8 E
	C 1/4 S 11
	2012
	Raise a mound of stone, 4 ft. base, 3 1/2 ft. high, W. of cor.
49.05	Utility line, 10 strand, bears S. 20° E. and N. 20° W.
54.55	Southerly right-of-way fence, bears S. 23° E. and N. 30° W.
57.15	Southerly edge of Highway No. 89, asphalt surfaced, 40 ft. wide, bears S. 30° E. and N. 30° W.
58.55	Northerly edge of Highway No. 89, bears S. 30° E. and N. 30° W.
61.20	Northerly right-of-way fence, bears S. 30° E. and N. 30° W.
68.10	Abandoned highway, degrading asphalt, 25 ft. wide, bears S. 30° E. and N. 30° W.

**Subdivision of Section 11,  
T. 34 N., R. 8 E., Gila and Salt River Meridian, Arizona**

CHAINS	
80.00	<p>The 1/4 sec. cor. of secs. 2 and 11.</p> <hr/> <p>From the 1/4 sec. cor. of secs. 11 and 12, monumented with a stainless steel post, 2 1/2 ins. diam., firmly set, projecting 3 ins. above the ground, with brass cap mkd. T34N R8E 1/4 S11 S12 2010, with a steel "T-post" nearby.</p> <p>Add the marks 2012 to the brass cap.</p> <p>West, on the E. and W. center line of sec. 11.</p>
28.80	Trail road, 12 ft. wide, bears S. 30° E. and N. 25° W.
29.70	Utility line, 4 strand, bears N. 55° E. and S. 55° W.
30.65	Easterly right-of-way fence, bears S. 20° E. and N. 20° W.
31.90	Easterly edge of Highway No. 89, asphalt surfaced, 50 ft. wide, bears S. 22° E. and N. 24° W.
32.70	Westerly edge of Highway No. 89, bears S. 22° E. and N. 24° W.
33.80	Westerly right-of-way fence, bears S. 22° E. and N. 24° W.
36.85	Utility line, 10 strand, bears S. 20° E. and N. 20° W.
40.00	The center 1/4 sec. cor. of sec. 11.
80.00	<p>The 1/4 sec. cor. of secs. 10 and 11, monumented with a stainless steel post, 2 1/2 ins. diam., firmly set, projecting 5 ins. above the ground, with brass cap mkd. T34N R8E 1/4 S10 S11 2010, with a steel "T-post" nearby.</p> <p>Add the marks 2012 to the brass cap.</p> <hr/> <p style="text-align: center;"><b>Subdivision of Section 13, T. 34 N., R. 8 E., Gila and Salt River Meridian, Arizona</b></p> <hr/> <p>From the 1/4 sec. cor. of secs. 13 and 24, monumented with a stainless steel post, 2 1/2 ins. diam., firmly set, projecting 2 ins. above the ground, with a brass cap mkd. T34N R8E S13 1/4 S24 2010, with a steel "T-post" nearby.</p> <p>Add the marks 2012 to the brass cap.</p> <p>N. 0°01' W., on the N. and S. center line of sec. 13.</p>
40.00	Point for the center 1/4 sec. cor. of sec. 13, at intersection with the E. and W. center line.

Subdivision of Section 13,  
T. 34 N., R. 8 E., Gila and Salt River Meridian, Arizona

CHAINS	
	<p>Set a standard monument, 25 ins. in the ground, mkd.</p> <p style="text-align: center;">T 34 N R 8 E</p> <p style="text-align: center;">C 1/4 S 13</p> <p style="text-align: center;">2012</p> <p>Raise a mound of sandstone, 4 ft. base, 1 1/2 ft. high, W. of cor.</p> <p>Set a steel "T-post" fence post near the cor.</p> <p>Cor. is located on a shelf of Echo Cliff, 15 ft. wide, bears S. 15° E. and N. 30° W.</p>
80.00	<p>The 1/4 sec. cor. of secs. 12 and 13, monumented with a stainless steel post, 2 1/2 ins. diam., firmly set, projecting 7 ins. above the ground, encircled with a collar of stone, with brass cap mkd. T34N R8E S12 1/4 S13 2010, with a steel "T-post" nearby.</p> <p>Add the marks 2012 to the brass cap.</p> <hr/> <p>From the true point for the 80 1/16 sec. cor. of secs. 13 and 24, falls on steep SW face of Echo Cliffs, the witness cor. bears N. 1°30 E, 1.30 chs. dist., monumented with a stainless steel post, 2 1/2 ins. diam., firmly set, projecting 3 ins. above the ground, with a brass cap mkd. WC T34N R8E 80 S13 1/16 S24 2010 with an arrow pointing to the true point, with a steel "T-post" nearby.</p> <p>Add the marks 2012 to the brass cap.</p> <p>North, on the N. and S. 80 1/16 line of sec. 13.</p>
40.00	<p>Point for the center 80 1/16 sec. cor. of sec. 13, at intersection with the E. and W. center line.</p> <p>Set a standard monument, 21 ins. in the ground, and in a mound of stone, 3 ft. base, to brass cap mkd.</p> <p style="text-align: center;">T 34 N R 8 E</p> <p style="text-align: center;">1/16</p> <p style="text-align: center;">C ——— 80</p> <p style="text-align: center;">S 13</p> <p style="text-align: center;">2012</p> <p>Set a steel "T-post" fence post near the cor., in a mound of sandstone, 3 ft. base, 2 ft. high.</p>



**Subdivision of Section 13,  
T. 34 N., R. 8 E., Gila and Salt River Meridian, Arizona**

CHAINS	
80.00	<p>The 80 1/16 sec. cor. of secs. 12 and 13, monumented with a stainless steel post, 2 1/2 ins. diam., firmly set, projecting 1 in. above the ground, encircled with a collar of stone, with brass cap mkd. T34N R8E S12 80 1/16 S13 2010.</p> <p>Add the marks 2012 to the brass cap.</p> <hr/> <p>From the 1/4 sec. cor. of secs. 13 and 18, monumented with a stainless steel post, 2 1/2 ins. diam., firmly set, projecting 5 ins. above the ground, encircled with a collar of stone, with brass cap mkd. T34N R8E R9E 1/4 S13 S18 2010.</p> <p>Add the marks 2012 to the brass cap.</p> <p>West, on the E. and W. center line of sec. 13.</p>
32.00	The center 80 1/16 sec. cor. of sec. 13.
72.00	The center 1/4 sec. cor. of sec. 13.
112.00	<p>The 1/4 sec. cor. of secs. 13 and 14, monumented with a stainless steel post, 2 1/2 ins. diam., firmly set, projecting 4 ins. above the ground, with brass cap mkd. T34N R8E 1/4 S14 S13 2010, with a steel "T-post" nearby.</p> <p>Add the marks 2012 to the brass cap.</p> <hr/> <p style="text-align: center;"><b>Subdivision of Section 14, T. 34 N., R. 8 E., Gila and Salt River Meridian, Arizona</b></p> <hr/> <p>From the 1/4 sec. cor. of secs. 14 and 23, monumented with an alum. rod, 3/4 in. diam., firmly set, projecting 11 ins. above the ground, in a collar of stone, 1 1/2 ft. base, from which</p> <p style="padding-left: 40px;">A reference monument, bears S. 89°59' E., 99.0 ft. dist., monumented with a stainless steel post, 2 1/2 ins. diam., firmly set, projecting 6 ins. above the ground, with brass cap mkd. RM T34N R8E S14 99.0 FT. TO COR 2010 and an arrow pointing to the cor., with a steel "T-post" nearby. Add the marks 2012 to the brass cap.</p> <p style="padding-left: 40px;">A reference monument, bears S. 0°01' E., 99.0 ft. dist., monumented with a stainless steel post, 2 1/2 ins. diam., firmly set, projecting 4 ins. above the ground, with brass cap mkd. RM T34N R8E S23 99.0 FT. TO COR 2010 and an arrow pointing to the cor., with a steel "T-post" nearby. Add the marks 2012 to the brass cap.</p> <p>N. 0°01' W., on the N. and S. center line of sec. 14.</p>

**Subdivision of Section 14,  
T. 34 N., R. 8 E., Gila and Salt River Meridian, Arizona**

CHAINS	
40.00	<p>Point for the center 1/4 sec. cor. of sec. 14, at intersection with the E. and W. center line.</p> <p>Set a standard monument, 30 ins. in the ground, mkd.</p> <p style="text-align: center;">T 34 N R 8 E</p> <p style="text-align: center;">C 1/4 S 14</p> <p style="text-align: center;">2012</p> <p>A wood post, 6 ins. diam., 4 ft. high, bears S. 70° W., 11 lks. dist.</p> <p>Cor. is located in a natural sandstone corral, 85 ft. diam., 15 ft. high.</p>
80.00	<p>The 1/4 sec. cor. of secs. 11 and 14.</p> <hr/> <p>From the 1/4 sec. cor. of secs. 13 and 14.</p> <p>West, on the E. and W. center line of sec. 14.</p>
5.10	Easterly right-of-way fence, bears S. 43° E. and N. 43° W.
6.70	Easterly edge of Highway No. 89, asphalt surfaced, 50 ft. wide, bears S. 40° E. and N. 40° W.
7.75	Westerly edge of Highway No. 89, bears S. 40° E. and N. 40° W.
9.30	Westerly right-of-way fence, bears N. 10° E. and S. 10° W.
40.00	The center 1/4 sec. cor. of sec. 14.
80.00	<p>The 1/4 sec. cor. of secs. 14 and 15, monumented with a stainless steel post, 2 1/2 ins. diam., firmly set, projecting 11 ins. above the ground, and in a mound of stone, 3 1/2 ft. base, to brass cap mkd. 1/4 S15 S14 T34N R8E 2010.</p> <p>Add the marks 2012 to the brass cap.</p> <hr/> <p style="text-align: center;"><b>Subdivision of Section 24, T. 34 N., R. 8 E., Gila and Salt River Meridian, Arizona</b></p> <hr/> <p>From the 1/4 sec. cor. of secs. 24 and 25, monumented with a stainless steel post, 2 1/2 ins. diam., firmly set, projecting 1 in. above the ground, and in a downhill mound of stone, 8 ft. base, 2 ft. high, with 2 steel "T-post" fence posts supporting the mound of stone, with a brass cap mkd. T34N R8E S24 1/4 S25 2010.</p>

Subdivision of Section 24,  
T. 34 N., R. 8 E., Gila and Salt River Meridian, Arizona

CHAINS	
	Add the marks 2012 to the brass cap.
	N. 0°01' W., on the N. and S. center line of sec. 24.
40.00	Point for the center 1/4 sec. cor. of sec. 24, at intersection with the E. and W. center line.
	Set a standard monument, 27 ins. in the ground, mkd.
	T 34 N R 8 E
	C 1/4 S 24
	2012
	Set a steel "T-post" fence post near the cor.
50.40	Southerly right-of-way fence, bears S. 40° E. and N. 40° W.
52.10	Southerly edge of Highway No. 89, asphalt surfaced, 45 ft. wide, bears S. 40° E. and N. 40° W.
53.30	Northerly edge of Highway No. 89, bears S. 40° E. and N. 40° W.
55.55	Northerly right-of-way fence, bears S. 47° E. and N. 47° W.
76.55	Underground waterline, bears S. 30° E. and N. 30° W.
76.90	Abandoned highway, degrading asphalt, 20 ft. wide, bears S. 30° E. and N. 30° W.
80.00	The 1/4 sec. cor. of secs. 13 and 24.
	<hr/>
	From the 80 1/16 sec. cor. of secs. 24 and 25, monumented with a stainless steel post, 2 1/2 ins. diam., firmly set, projecting 4 ins. above the ground, with a brass cap mkd. T34N R8E S24 80 1/16 S25 2010, with a steel "T-post" nearby.
	Add the marks 2012 to the brass cap.
	North, on the N. and S. 80 1/16 line of sec. 24.
0.60	Southerly right-of-way fence, bears S. 40° E. and N. 40° W.
2.55	Southerly edge of Highway No. 89, asphalt surfaced, 40 ft. wide, bears S. 40° E. and N. 40° W.
3.50	Northerly edge of Highway No. 89, bears S. 40° E. and N. 40° W.
4.30	Northerly right-of-way fence, bears S. 55° E. and N. 55° W.

Subdivision of Section 24,  
T. 34 N., R. 8 E., Gila and Salt River Meridian, Arizona

CHAINS	
9.25	Abandoned highway, degrading asphalt, 25 ft. wide, bears S. 35° E. and N. 35° W.
40.00	Point for the center 80 1/16 sec. cor. of sec. 24, at intersection with the E. and W. center line.  Set a standard monument, 26 ins. in the ground, mkd.  <div style="text-align: center;">           T 34 N R 8 E                1/16            C ——— 80                S 24             2012         </div> Set a steel "T-post" fence post near the cor.
80.00	True point for the 80 1/16 sec. cor. of secs. 13 and 24. <hr/> From the 1/4 sec. cor. of secs. 19 and 24, monumented with a stainless steel post, 2 1/2 ins. diam., firmly set, projecting 4 ins. above the ground, with brass cap mkd. T34N R8E R9E 1/4 S24 S19 2010.  Add the marks 2012 to the brass cap.  West, on the E. and W. center line of sec. 24.
32.00	The center 80 1/16 sec. cor. of sec. 24.
50.40	Abandoned highway, degrading asphalt, 25 ft. wide, bears S. 30° E. and N. 30° W.
50.75	Underground waterline, bears S. 30° E. and N. 30° W.
59.75	Easterly right-of-way fence, bears S. 40° E. and N. 40° W.
61.35	Easterly edge of Highway No. 89, asphalt surfaced, 45 ft. wide, bears S. 40° E. and N. 40° W.
62.25	Westerly edge of Highway No. 89, bears S. 40° E. and N. 40° W.
63.65	Westerly right-of-way fence, bears S. 40° E. and N. 40° W.
72.00	The center 1/4 sec. cor. of sec. 24.
112.00	The 1/4 sec. cor. of secs. 23 and 24, monumented with a stainless steel post, 2 1/2 ins. diam., firmly set, projecting 4 ins. above the ground, with brass cap mkd. T34N R8E 1/4 S23 S24 2010, with a steel "T-post" nearby.

Subdivision of Section 24,  
T. 34 N., R. 8 E., Gila and Salt River Meridian, Arizona

CHAINS	<p>Add the marks 2012 to the brass cap.</p> <hr/> <p style="text-align: center;">Subdivision of Section 25, T. 34 N., R. 8 E., Gila and Salt River Meridian, Arizona</p> <hr/> <p>From the 1/4 sec. cor. of secs. 25 and 36, monumented with a stainless steel post, 2 1/2 ins. diam., firmly set, projecting 6 ins. above the ground, encircled with a collar of limestone, with a brass cap mkd. T34N R8E S25 1/4 S36 2010, with a steel "T-post" nearby.</p> <p>Add the marks 2012 to the brass cap.</p> <p>N. 0°01' W., on the N. and S. center line of sec. 25.</p>
40.00	<p>Point for the center 1/4 sec. cor. of sec. 25, at intersection with the E. and W. center line.</p> <p>Set a standard monument, 15 ins. in the ground, and in a mound of stone, 4 ft. base, to brass cap mkd.</p> <p style="text-align: center;">T 34 N R 8 E C 1/4 S 25 2012</p>
80.00	<p>Set a steel "T-post" fence post near the cor.</p> <p>The 1/4 sec. cor. of secs. 24 and 25.</p> <hr/>
40.00	<p>From the 80 1/16 sec. cor. of secs. 25 and 36, monumented with a stainless steel post, 2 1/2 ins. diam., firmly set, projecting 4 ins. above the ground, with a brass cap mkd. T34N R8E S25 80 1/16 S36 2010, with a steel "T-post" nearby.</p> <p>Add the marks 2012 to the brass cap.</p> <p>North, on the N. and S. 80 1/16 line of sec. 25.</p> <p>Point for the center 80 1/16 sec. cor. of sec. 25, at intersection with the E. and W. center line.</p> <p>Set a standard monument, flush with the ground, mkd.</p>

Subdivision of Section 25,  
T. 34 N., R. 8 E., Gila and Salt River Meridian, Arizona

CHAINS	
	T 34 N R 8 E 1/16 C ——— 80 S 25  2012
	Raise a mound of stone, 5 ft. base, 2 1/2 ft. high, W. of cor.
75.55	Utility line, 10 strand, bears S. 40° E. and N. 40° W.
80.00	The 80 1/16 sec. cor. of secs. 24 and 25.
	<hr/> From the 1/4 sec. cor. of secs. 25 and 30, monumented with a stainless steel post, 2 1/2 ins. diam., firmly set, projecting 2 ins. above the ground, with brass cap mkd. T34N R8E R9E 1/4 S25 S30 2010, with a steel "T-post" nearby.  Add the marks 2012 to the brass cap.  West, on the E. and W. center line of sec. 25.
0.35	Westerly right-of-way fence, bears S. 50° E. and N. 50° W.
0.75	Underground waterline, bears S. 45° E. and N. 45° W.
2.40	Utility line, 10 strand, bears S. 45° E. and N. 45° W.
32.00	The center 80 1/16 sec. cor. of sec. 25.
72.00	The center 1/4 sec. cor. of sec. 25.
112.00	True point for the 1/4 sec. cor. of secs. 25 and 26, falls in flood area of Hole Reservoir, got metal detector reading at location of magnet, from which  A reference monument, bears S. 24°59' E., 70.0 ft. dist., monumented with a stainless steel post, 2 1/2 ins. diam., firmly set, projecting 2 ins. above the ground, with brass cap mkd. RM T34N R8E 70.0 FT. TO COR S25 2010 and an arrow pointing to the cor. Add the marks 2012 to the brass cap.  A reference monument, bears S. 65°02' W., 80.0 ft. dist., monumented with a stainless steel post, 2 1/2 ins. diam., firmly set, projecting 3 ins. above the ground, with brass cap mkd. RM T34N R8E 80.0 FT. TO COR S26 2010 and an arrow pointing to the cor. Add the marks 2012 to the brass cap.

## T. 34 N., R. 8 E., Gila and Salt River Meridian, Arizona

CHAINS

## GENERAL DESCRIPTION

---

The intent of this survey is to monument the center 1/4 section corners of the sections that Highway 89 traverses through. Highway 89 runs northwesterly and southeasterly through the township. The terrain varies from level in the Hamblin Wash area, to broken and rugged land

The elevation varies from 4,600 to 5,000 feet above sea level. The soil is sand with areas of sandstone outcrops and ledges. The vegetation is salt brush, Mormon tea, rabbit brush and native grasses throughout the township, with some areas of scattered juniper trees.

The mean magnetic declination of 11° E. was derived from the National Geophysical Data Center's magnetic declination calculator, for the dates of the survey.

---

**UNITED STATES  
DEPARTMENT OF THE INTERIOR  
BUREAU OF LAND MANAGEMENT**

**FIELD ASSISTANTS**

NAMES	CAPACITY
Robert J. Lyle	Surveying Technician
Mark R. Searles	Surveying Technician
Daniel Bryon	Engineering Technician
Byron J. Shorty	Engineering Technician
Kevin Tso	Engineering Technician
Alyssa M. Little	Survey Aid
Luke R. Hullinger	Survey Aid
Rafael J. Tapaha	Survey Aid



## CERTIFICATE OF SURVEY

I, Craig S. Dukart, Cadastral Surveyor, HEREBY CERTIFY upon honor, that in pursuance of supplemental special instructions bearing date of the 7th day of August, 2012, I have surveyed the subdivision of certain sections, Township 34 North, Range 8 East, Gila and Salt River Meridian, Arizona, which are represented in the foregoing field notes as having been executed by me and under my direction. Said survey has been made in strict conformity with said special instructions, the Manual of Instructions (2009), and in specific manner described in the foregoing field notes.

5/5/13

(Date)

Craig S. Dukart

(Cadastral Surveyor)

## CERTIFICATE OF APPROVAL

BUREAU OF LAND MANAGEMENT  
Phoenix, Arizona

The foregoing field notes of the survey of the subdivision of certain sections, Township 34 North, Range 8 East, Gila and Salt River Meridian, Arizona, executed by Craig S. Dukart, Cadastral Surveyor, having been critically examined and found correct, are hereby approved.

5/9/2013

(Date)

Stephen H. Hansen

(Chief Cadastral Surveyor of Arizona)

~~CERTIFICATE OF TRANSCRIPT~~

~~I CERTIFY That the foregoing transcript of the field notes of the above described surveys in T. 34 N., R. 8 E., of the Gila and Salt River Meridian, in the State of Arizona, is a true copy of the original field notes.~~

~~(Date)~~

~~(Chief Cadastral Surveyor of Arizona)~~