**ORIGINAL** 

# UNITED STATES DEPARTMENT OF THE INTERIOR BUREAU OF LAND MANAGEMENT

FIELD NOTES

OF. THE

SURVEY OF THE EAST, WEST, AND NORTH BOUNDARIES

AND

THE SUBDIVISIONAL LINES

AND

THE SUBDIVISION OF CERTAIN SECTIONS

TOWNSHIP 39 NORTH, RANGE 10 EAST,

OF THE GILA AND SALT RIVER MERIDIAN,

IN THE STATE OF ARIZONA.

#### **EXECUTED BY**

#### Fabian Yazzie, Cadastral Surveyor

Under Special Instructions dated February 4, 2013, approved February 4, 2013, which provided for the surveys included under Group No. 1117, and assignment instructions dated February 4, 2013.

Survey commenced February 25, 2013

Survey completed April 24, 2013

#### INDEX DIAGRAM

# TOWNSHIP 39 NORTH RANGE 10 EAST GILA & SALT RIVER MERIDIAN, ARIZONA

	20		19		18		17		16		15	
14	6	67	5	55	4	47	3	37	2	28	1	8
	66		66		54		46		37		28	
13	7	65	8	53	9	45	10	36	11	27	12	7
	64		63		52		44		35		26	
12	18	62	17	52	16	43	15	34	14	25	13	6
	62		61		51		42		33		25	
11	19	60	20	50	21	41	22	32	23	24	24	5
	59		59		50		41		32		23	
10	30	58	29	49	28	40	27	31	26	23	25	5
	57		57		48		39		30		22	
								:				
9	31	56	32	47	33	38	34	29	35	21	36	4

Subdivision of Section 3 Pages	68-69
Subdivision of Section 10 Pages	69-70
Subdivision of Section 11 Pages	70-71
Subdivision of Section 14 Pages	71-72
Subdivision of Section 23 Pages	72-73
Subdivision of Section 26 Pages	73 - 74
Subdivision of Section 35 Pages	74-75

#### T. 39 N., R. 10 E., Gila and Salt River Meridian, Arizona

CHAINS

The following field notes describe the survey of the East, West, and North boundaries, and the subdivisional lines, and the subdivision of certain sections, Township 39 North, Range 10 East, Gila and Salt River Meridian, Arizona.

The history of surveys pertaining to this survey is as follows:

Leonard R. Sandoval performed a dependent resurvey and surveyed Township 40 North, Range 9 East, in 2005. Fabian Yazzie surveyed the North boundary (south boundary) of Township 38 North, Range 10 East, in 2012.

The survey was executed in accordance with the specifications as set forth in the  $\underline{\text{Manual of Instructions for the Survey of the}}$   $\underline{\text{Public Lands of the United States, 2009}}$ , and the Special Instructions dated February 4, 2013, for Group Number 1117, Arizona.

The true meridian direction and length of all lines were determined by real time kinematic global positioning system observations using Trimble Navigation R8 and 5700 model receivers.

Geodetic control was derived from Global Positioning System (GPS) static observations post processed by National Geodetic Survey, Online Positioning User Service (OPUS), utilizing Continuously Operating Reference Stations (CORS) AI8805 FRED FREDONIA CORS, DI2245 P011 SPIDERROCKAZ2005, DK8419 AZPG CITY OF PAGE CORS, and DL1882 AZFL NAU FLAGSTAFF CORS. The NAD 83 (2011) (EPOCH: 2010), geographic position of the corner of Townships 38 and 39 North, Ranges 10 and 11 East, is as follows:

Latitude: 36°43'45.962" N. Longitude: 111°15'47.196" W.

The geographic position of the corner of Townships 39 and 40 North, Ranges 9 and 10 East, is as follows:

Latitude: 36°48'59.119" N. Longitude: 111°22'15.362" W.

The mean magnetic declination is 11° E.

CHAINS

Beginning at the cor. of Tps. 38 and 39 N., Rs. 10 and 11 E., monumented with a stainless steel post, 2 1/2 ins. diam., firmly set, projecting 4 ins. above ground, with brass cap mkd. T39N R10E R11E S36 S31 S1 S6 T38N 2012.

North, bet. secs. 31 and 36.

Over gently rolling land.

40.00 | Point for the 1/4 sec. cor. of secs. 31 and 36.

Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.

Deposit a magnet, in a white plastic case, at the base of the stainless steel post.

Set a steel fence post nearby.

80.00 | Point for the cor. of secs. 25, 30, 31, and 36.

Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 25 ins. in the ground, with brass cap mkd.

2013

Deposit a magnet, in a white plastic case, at the base of the stainless steel post.

Set a steel fence post nearby.

Land, gently rolling.

Soil, sandy loam.

Timber, scattered juniper.

Undergrowth, native grasses, yucca, sage brush, and Mormon tea.

North, bet. secs. 25 and 30.

Over gently rolling land.

	T. 39 N., R. 10 E., Gila and Salt River Meridian, Arizona
CHAINS	
40.00	Point for the 1/4 sec. cor. of secs. 25 and 30.
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.
	T 39 N R 10 E R 11 E 1/4
	S 25   S 30
	2013
	Deposit a magnet, in a white plastic case, at the base of the stainless steel post.
	Set a steel fence post nearby.
80.00	Point for the cor. of secs. 19, 24, 25, and 30.
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 25 ins. in the ground, with brass cap mkd.
	T 39 N R 10 E   R 11 E S 24   S 19 S 25   S 30
	2013
	Deposit a magnet, in a white plastic case, at the base of the stainless steel post.
	Set a steel fence post nearby.
	Land, gently rolling.
	Soil, sandy loam. No timber. Undergrowth, native grasses, sage brush, and yucca.
	North, bet. secs. 19 and 24.
	Over gently rolling land.
15.10	Barbed wire fence, 4 strand, bears N. 45° E. and S. 45° W.
40.00	Point for the 1/4 sec. cor. of secs. 19 and 24.
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.

	T. 39 N., R. 10 E., Gila and Sait River Meridian, Arizona
CHAINS	
	T 39 N R 10 E R 11 E 1/4
	S 24   S 19
	2013
	Deposit a magnet, in a white plastic case, at the base of the stainless steel post.
	Set a steel fence post nearby.
80.00	Point for the cor. of secs. 13, 18, 19, and 24.
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.
	T 39 N R 10 E   R 11 E S 13   S 18 S 24   S 19
	2013
	Deposit a magnet, in a white plastic case, at the base of the stainless steel post.
	Land, gently rolling and sandstone rock outcrops. Soil, sandy loam and sandstone bedrock. No timber. Undergrowth, native grasses, sage brush, yucca, and Mormon tea.
	North, bet. secs. 13 and 18.
	Over gently rolling land.
22.10	High voltage transmission line, bears S. 60° E. and N. 60° W.
22.90	Trail road, bears S. 60° E. and N. 60° W.
40.00	Point for the 1/4 sec. cor. of secs. 13 and 18.
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 25 ins. in the ground, with brass cap mkd.

	T. 39 N., R. 10 E., Gila and Salt River Meridian, Arizona
CHAINS	
	T 39 N R 10 E R 11 E 1/4
	S 13   S 18
	2013
	Deposit a magnet, in a white plastic case, at the base of the stainless steel post.
	Set a steel fence post nearby.
73.20	Trail road, bears N. 40° E. and S. 40° W.
80.00	Point for the cor. of secs. 7, 12, 13, and 18.
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 25 ins. in the ground, with brass cap mkd.
	T 39 N  R 10 E   R 11 E  S 12   S 7  S 13   S 18
	2013
	Deposit a magnet, in a white plastic case, at the base of the stainless steel post.
	Set a steel fence post nearby.
	Land, gently rolling. Soil, sandy loam. No timber. Undergrowth, native grasses, sage brush, and Mormon tea.
	North, bet. secs. 7 and 12.
	Over nearly level land.
14.40	Trail road, bears S. 55° E. and N. 55° W.
18.20	Barbed wire fence, 4 strand, bears S. 40° E. and N. 40° W.
40.00	Point for the 1/4 sec. cor. of secs. 7 and 12.
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 23 ins. in the ground, with brass cap mkd.

CHAINS	
	T 39 N R 10 E R 11 E 1/4
	S 12   S 7
	2013
	Deposit a magnet, in a white plastic case, at the base of the stainless steel post.
	Cor. is located 86 lks. S. of wash, 30 ft. wide, 4 ft. deep drains N. 40° E.
80.00	Point for the cor. of secs. 1, 6, 7, and 12.
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam. 24 ins. in the ground, with brass cap mkd.
	T 39 N R 10 E   R 11 E S 1   S 6 S 12   S 7
	2013
	Deposit a magnet, in a white plastic case, at the base of the stainless steel post.
	Set a steel fence post nearby.
	Cor. is located on top of sandstone mesa ridge, 2.62 chs. S. of the N. rim, 75 ft. high, bears S. 40° E. and S. 80° W., and 2.30 chs. N. of the S. rim, 75 ft. high, bears N. 25° E. and S.
	Land, gently rolling. Soil, sandy loam and gravel. No timber. Undergrowth, native grasses and sage brush.
	North, bet. secs. 1 and 6.
	Over gently rolling valley.
40.00	Point for the 1/4 sec. cor. of secs. 1 and 6.
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam.,

CHAINS

T 39 N
R 10 E R 11 E
1/4
S 1 | S 6

Deposit a magnet, in a white plastic case, at the base of the stainless steel post.

Set a steel fence post nearby.

65.75 | Sandstone rim, 60 ft. high, bears N. 45° E. and S. 30° W.

80.00 | Point for the cor. of secs. 1, 6, 31, and 36.

Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.

2013

Deposit a magnet, in a white plastic case, at the base of the stainless steel post.

Set a steel fence post nearby.

Land, gently rolling and sandstone rock outcrops.

Soil, sandy loam and sandstone bedrock.

No timber.

Undergrowth, native grasses, salt brush, sage brush, and yucca.

#### Survey of the West Boundary, T. 39 N., R. 10 E., Gila and Salt River Meridian, Arizona

From the cor. of Tps. 38 and 39 N., Rs. 9 and 10 E., monumented with a stainless steel post, 2 1/2 ins. diam., firmly set, 4 ins. above ground, with brass cap mkd. T39N R9E R10E S36 S31 S1 S6 T38N 2013.

North, bet. secs. 31 and 36.

Over gently rolling land.

27.05 Barbed wire fence, 5 strand, bears S. 50° E. and N. 50° W.

	T. 39 N., R. 10 E., Gila and Sait River Meridian, Arizona
CHAINS	
27.50	Trail road, bears S. 50° E. and N. 50° W.
40.00	Point for the 1/4 sec. cor. of secs. 31 and 36.
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 25 ins. in the ground, with brass cap mkd.
	T 39 N R 9 E R 10 E 1/4 S 36   S 31
	2013
	Deposit a magnet, in a white plastic case, at the base of the stainless steel post.
	Set a steel fence post nearby.
	Cor. is located 2.80 chs. S. of trail road, bears N. 25° E. and S. 25° W.
80.00	Point for the cor. of secs. 25, 30, 31, and 36.
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.
	T 39 N R 9 E   R 10 E S 25   S 30 S 36   S 31
	2013
	Deposit a magnet, in a white plastic case, at the base of the stainless steel post.
	Set a steel fence post nearby.
	Land, gently rolling. Soil, sandy loam. Timber, scattered juniper. Undergrowth, native grasses, salt brush, yucca, and Mormon tea.
	North, bet. secs. 25 and 30.
	Over gently rolling land.
8.05	Trail road, bears N. 60° E. and S. 60° W.

	T. 39 N., R. 10 E., Gila and Salt River Meridian, Arizona
CHAINS	
40.00	Point for the 1/4 sec. cor. of secs. 25 and 30.
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 25 ins. in the ground, with brass cap mkd.
	T 39 N R 9 E R 10 E 1/4
	S 25   S 30
	2013
	Deposit a magnet, in a white plastic case, at the base of the stainless steel post.
	Set a steel fence post nearby.
80.00	Point for the cor. of secs. 19, 24, 25, and 30.
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.
	T 39 N R 9 E   R 10 E S 24   S 19 S 25   S 30
	2013
	Deposit a magnet, in a white plastic case, at the base of the stainless steel post.
	Set a steel fence post nearby.
	Land, gently rolling. Soil, sandy loam. Timber, sparse juniper. Undergrowth, native grasses, salt brush, yucca, and Mormon tea.
	North, bet. secs. 19 and 24.
	Over gently rolling land.
12.80	Barbed wire fence, 5 strand, bears N. 55° E. and S. 55° W.
40.00	Point for the 1/4 sec. cor. of secs. 19 and 24.
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 25 ins. in the ground, with brass cap mkd.

		T. 39 N., R. 10 E., Gila and Salt River Meridian, Arizona
	CHAINS	
d delated a control control of the c		T 39 N R 9 E R 10 E 1/4 S 24   S 19
		2013
		Deposit a magnet, in a white plastic case, at the base of the stainless steel post.
		Set a steel fence post nearby.
	80.00	Point for the cor. of secs. 13, 18, 19, and 24.
-		Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 25 ins. in the ground, with brass cap mkd.
		T 39 N R 9 E   R 10 E S 13   S 18 S 24   S 19
		2013
		Deposit a magnet, in a white plastic case, at the base of the stainless steel post.
		Set a steel fence post nearby.
		Land, gently rolling. Soil, sandy loam. No timber. Undergrowth, native grasses, greasewood, yucca, cholla grass, and Mormon tea.
		North, bet. secs. 13 and 18.
		Over gently rolling.
	40.00	Point for the 1/4 sec. cor. of secs. 13 and 18.
		Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 25 ins. in the ground, with brass cap mkd.
		T 39 N R 9 E R 10 E 1/4 S 13   S 18
- 1		

2013

	T. 39 N., R. 10 E., Gila and Salt River Meridian, Arizona
CHAINS	
	Deposit a magnet, in a white plastic case, at the base of the stainless steel post.
	Set a steel fence post nearby.
80.00	Point for the cor. of secs. 7, 12, 13, and 18.
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.
	T 39 N R 9 E   R 10 E S 12   S 7 S 13   S 18
	2013
	Deposit a magnet, in a white plastic case, at the base of the stainless steel post.
	Set a steel fence post nearby.
	Land, gently rolling. Soil, sandy loam. No timber. Undergrowth, native grasses, greasewood, yucca, cholla grass, and Mormon tea.
	North, bet. secs. 7 and 12.
	Gently descending into mesa valley.
15.75	Sandstone rim, 80 ft. high, bears N. 45° E. and S. 65° W.
40.00	Point for the 1/4 sec. cor. of secs. 7 and 12.
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 21 ins. in the ground, with brass cap mkd.
	T 39 N R 9 E R 10 E 1/4
	S 12   S 7
	2013
	Deposit a magnet, in a white plastic case, at the base of the stainless steel post.

	T. 39 N., R. 10 E., Gila and Salt River Meridian, Arizona
CHAINS	
	Cor. is located 2.40 chs. S. of wash, 79 ft. wide, 4 ft. deep, drains N. 45° E.
48.75	Wash, 36 ft. wide, 3 ft. deep, drains S. 75° E.
70.15	Sandstone rim, 60 ft. high, bears N. 10° E. and S. 65° W.
80.00	Point for the cor. of secs. 1, 6, 7, and 12.
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.
	T 39 N R 9 E   R 10 E S 1   S 6 S 12   S 7
	2013
	Deposit a magnet, in a white plastic case, at the base of the stainless steel post.
	Set a steel fence post nearby.
	Land, rolling and broken. Soil, sandy loam. No timber. Undergrowth, native grasses, greasewood, and cliff roses.
	North, bet. secs. 1 and 6.
	Over rolling land.
40.00	Point for the 1/4 sec. cor. of secs. 1 and 6.
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.
	T 39 N R 9 E R 10 E 1/4 S 1   S 6
	2012
	Deposit a magnet, in a white plastic case, at the base of the stainless steel post.
	Set a steel fence post nearby.

	T. 39 N., R. 10 E., Gila and Salt River Meridian, Arizona
CHAINS	
80.00	The cor. of Tps. 39 and 40 N., Rs. 9 and 10 E., monumented with a stainless steel post, 2 1/2 ins. diam., firmly set in sandstone bedrock, projecting 6 ins. above ground, with brass cap mkd. T40N R9E R10E S36 S31 S1 S6 T39N 2005 2012.
	Land, rolling and broken. Soil, sandy loam. Timber, juniper. Undergrowth, native grasses, yucca, and Mormon tea.
	Survey of the North Boundary, T. 39 N., R. 10 E., Gila and Salt River Meridian, Arizona
	From the cor. of Tps. 39 and 40 N., Rs. 10 and 11 E., hereinbefore described.
	West, bet. secs. 1 and 36.
	Over rolling land.
21.75	Trail road, bears N. 25° E. and S. 25° W.
40.00	Point for the 1/4 sec. cor. of secs. 1 and 36.
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 21 ins. in the ground, encircled with a collar of stone, with brass cap mkd.
	T 40 N R 10 E  S 36  1/4 S 1  T 39 N
	2013
	Deposit a magnet, in a white plastic case, at the base of the stainless steel post.
	Set a steel fence post nearby.
80.00	Point for the cor. of secs. 1, 2, 35, and 36.
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 25 ins. in the ground, with brass cap mkd.

CHAINS

T 40 N R 10 E S 35 S 36 S 2 S 1 T 39 N

2013

Deposit a magnet, in a white plastic case, at the base of the stainless steel post.

Land, rolling.

Soil, sandy loam.

No timber.

Undergrowth, native grasses, yucca, sage brush, and salt brush.

West, bet. secs. 2 and 35.

Over gently rolling land.

40.00 Point for the 1/4 sec. cor. of secs. 2 and 35.

Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 23 ins. in the ground, with brass cap mkd.

2013

from which

- A stainless steel post, 28 ins. long, 2 1/2 ins. diam., set 24 ins. in the ground for a reference monument, bears N. 10°00' E., 66.0 ft. dist., with brass cap mkd. RM T40N R10E 66.0 FT TO COR 1/4 S35 2013 and an arrow pointing to the cor. Deposit a magnet, in a white plastic case, at the base of the stainless steel post and set a steel fence post nearby.
- A stainless steel post, 28 ins. long, 2 1/2 ins. diam., set 24 ins. in the ground for a reference monument, bears S. 10°00' W., 66.0 ft. dist., with brass cap mkd. RM T39N R10E 66.0 FT TO COR 1/4 S2 2013 and an arrow pointing to the cor. Deposit a magnet, in a white plastic case, at the base of the stainless steel post.

Deposit a magnet, in a white plastic case, at the base of the stainless steel post.

GUA TNO	T. 39 N., R. 10 E., Gila and Salt River Meridian, Arizona
CHAINS	
	Cor. is located in S. slope of wash, 3 ft. wide, 1 ft. deep, drains N. 65° E.
46.85	Trail road, bears S. 50° E. and N. 50° W.
80.00	Point for the cor. of secs. 2, 3, 34, and 35.
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 25 ins. in the ground, with brass cap mkd.
	T 40 N R 10 E S 34   S 35 S 3   S 2 T 39 N
	2013
	Deposit a magnet, in a white plastic case, at the base of the stainless steel post.
	Set a steel fence post nearby.
	Land, gently rolling. Soil, sandy loam. No timber. Undergrowth, native grasses, yucca, sage brush, and Mormon tea.
	West, bet. secs. 3 and 34.
	Over gently rolling land.
31.65	E. right-of-way fence of State Highway 98, barbed wire, 4 strand, parallels highway.
33.15	State Highway 98, an asphalt surfaced road, 35 ft. wide, bears S. 10° E. and N. 10° W.
34.70	W. right-of-way fence of State Highway 98, barbed wire, 4 strand, parallels highway.
40.00	Point for the 1/4 sec. cor. of secs. 3 and 34.
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 25 ins. in the ground, with brass cap mkd.
	T 40 N R 10 E S 34
	1/4 —— S 3 T 39 N
	2013

	T. 39 N., R. 10 E., Gila and Salt River Melidian, Alizona
CHAINS	
	Deposit a magnet, in a white plastic case, at the base of the stainless steel post.
	Set a steel fence post nearby.
55.90	High voltage transmission line, bears S. 20° E. and N. 20° W.
56.45	Trail road, bears S. 25° E. and N. 25° W.
61.40	Graded road, 20 ft. wide, bears N. 45° E. and S. 45° W.
76.70	Trail road, bears N. 15° E. and S. 15° W.
80.00	Point for the cor. of secs. 3, 4, 33, and 34.
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 25 ins. in the ground, with brass cap mkd.
	T 40 N R 10 E S 33   S 34
	S 4   S 3 T 39 N
	2013
	Deposit a magnet, in a white plastic case, at the base of the stainless steel post.
	Set a steel fence post nearby.
	Land, gently rolling. Soil, sandy loam. No timber. Undergrowth, native grasses, sage brush, and Mormon tea.
	West, bet. secs. 4 and 33.
	Over gently rolling land.
40.00	Point for the 1/4 sec. cor. of secs. 4 and 33.
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.
	T 40 N R 10 E S 33 1/4 ——
	S 4 T 39 N
	2013

	T. 39 N., R. 10 E., Gila and Salt River Meridian, Arizona
CHAINS	
	Deposit a magnet, in a white plastic case, at the base of the stainless steel post.
	Set a steel fence post nearby.
45.10	Trail road, bears S. 30° E. and N. 30° W.
45.35	E. right-of-way fence of Black Mesa and Lake Powell Railroad, woven and barbed wire, parallels railroad.
46.40	Black Mesa and Lake Powell Railroad, 5 ft. bet. rails, bears S. 25° E. and N. 25° W.
47.35	W. right-of-way fence of Black Mesa and Lake Powell Railroad, woven and barbed wire, parallels railroad.
75.95	Trail road, bears S. 25° E. and N. 25° W.
80.00	Point for the cor. of secs. 4, 5, 32, and 33.
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.
	T 40 N R 10 E S 32   S 33 S 5   S 4 T 39 N
	2013
	Deposit a magnet, in a white plastic case, at the base of the stainless steel post.
	Set a steel fence post nearby.
	Land, gently rolling. Soil, sandy loam. No timber. Undergrowth, native grasses, yucca, sage brush, and Mormon tea.
	West, bet. secs. 5 and 32.
	Over gently rolling land.
20.10	Trail road, bears N. 10° E. and S. 10° W.
40.00	Point for the 1/4 sec. cor. of secs. 5 and 32.
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 20 ins. in solid sandstone bedrock, with brass cap mkd.

		T. 39 N., R. 10 E., Gila and Salt River Meridian, Arizona
CF	AAINS	T 40 N R 10 E S 32
		1/4 ————————————————————————————————————
		2013
		Deposit a magnet, in a white plastic case, at the base of the stainless steel post.
8	80.00	Point for the cor. of secs. 5, 6, 31, and 32.
		Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 23 ins. in solid sandstone bedrock, with brass cap mkd.
		T 40 N R 10 E S 31   S 32 S 6   S 5 T 39 N
		2013
		Deposit a magnet, in a white plastic case, at the base of the stainless steel post.
		Raise a mound of stone, 3 ft. base, 2 1/2 ft. high, S. of cor.
		Cor. is located 32 lks W. and 84 lks N. of the base of sandstone cliff, 15 ft. high, bears S. 20° W. and N. 15° W., and bears N. 20° E. and S. 20° E., respectively.
		Land, rolling and broken. Soil, sandstone bedrock.
		No timber. Undergrowth, native grasses, greasewood, cholla cactus, yucca, sage brush, and Mormon tea.
		West, bet. secs. 6 and 31.
		Over broken canyon land.
4	0.00	Point for the 1/4 sec. cor. of secs. 6 and 31.
		Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 23 ins. in the ground, with brass cap mkd.

	T. 39 N., R. 10 E., Gila and Salt River Meridian, Arizona
CHAINS	
	T 40 N R 10 E S 31 1/4 —— S 6
	T 39 N
	2013
	Deposit a magnet, in a white plastic case, at the base of the stainless steel post.
45.10	Sandstone rim, 90 ft. high, bears N. 20° E. and S. 20° W.
78.35	The cor. of Tps. 39 and 40 N., Rs. 9 and 10 E., hereinbefore described.
	Land, rolling and broken. Soil, sandy loam and sandstone bedrock. Timber, scattered juniper. Undergrowth, native grasses, salt brush, yucca, and Mormon tea.
	Survey of the Subdivisional Lines, T. 39 N., R. 10 E., Gila and Salt River Meridian, Arizona
	From the cor. of secs. 1, 2, 35 and 36, on the S. bdy. of the Tp., monumented with a stainless steel post, 2 1/2 ins. diam., firmly set, projecting 5 ins. above the ground, with brass cap mkd. T39N R10E S35 S36 S2 S1 T38N 2012.
	N. 0°01' W., bet. secs. 35 and 36.
	Over gently rolling land.
40.00	Point for the 1/4 sec. cor. of secs. 35 and 36.
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 25 ins. in the ground, with brass cap mkd.
	T 39 N R 10 E 1/4 S 35   S 36
	2013
	Deposit a magnet, in a white plastic case, at the base of the stainless steel post.
	Set a steel fence post nearby.
80.00	Point for the cor. of secs. 25, 26, 35, and 36.
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with brass cap mkd.

	T. 39 N., R. 10 E., Gila and Salt River Meridian, Arizona
CHAINS	
	T 39 N R 10 E S 26   S 25 S 35   S 36
	2013
	Deposit a magnet, in a white plastic case, at the base of the stainless steel post.
	Set a steel fence post nearby.
	Land, gently rolling. Soil, sandy loam. Timber, sparse juniper. Undergrowth, native grasses, salt brush, greasewood, yucca, and Mormon tea.
	From the cor. of secs. 25, 30, 31, and 36 on the E. bdy. of the Tp., hereinbefore described.
	West, bet. secs. 25 and 36.
	Over gently rolling land.
40.00	Point for the 1/4 sec. cor. of secs. 25 and 36.
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 25 ins. in the ground, with brass cap mkd.
	T 39 N R 10 E  S 25  1/4 —  S 36
	2013
	Deposit a magnet, in a white plastic case, at the base of the stainless steel post.
	Set a steel fence post nearby.
80.00	The cor. of secs. 25, 26, 35, and 36.
	Land, gently rolling. Soil, sandy loam. Timber, sparse juniper. Undergrowth, native grasses, greasewood, and yucca.
	N. 0°01' W., bet. secs. 25 and 26.

	1. 39 N., R. 10 E., Gila and Balt River Meridian, Arrzona
CHAINS	
	Over gently rolling land.
40.00	Point for the 1/4 sec. cor. of secs. 25 and 26.
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 25 ins. in the ground, with brass cap mkd.
	T 39 N R 10 E
	1/4 S 26   S 25
	2013
	Deposit a magnet, in a white plastic case, at the base of the stainless steel post.
	Set a steel fence post nearby.
	Cor. is located in the W. edge of trail road, bears N. 25° E. and S. 25° W.
80.00	Point for the cor. of secs. 23, 24, 25, and 26.
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 19 ins. in solid sandstone bedrock, in a supporting mound of stone, 3 ft. base, to top, with brass cap mkd.
	T 39 N R 10 E  S 23   S 24  S 26   S 25
	2013
	Deposit a magnet, in a white plastic case, at the base of the stainless steel post.
	Land, gently rolling. Soil, sandy loam and sandstone rock outcrops. No timber. Undergrowth, native grasses, greasewood, yucca, and Mormon tea.
	From the cor. of secs. 19, 24, 25, and 30 on the E. bdy. of the Tp., hereinbefore described.
	West, bet. secs. 24 and 25.
	Over gently rolling land.
40.00	Point for the 1/4 sec. cor. of secs. 24 and 25.
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with brass cap mkd.

	T. 39 N., R. 10 E., Gila and Salt River Meridian, Arizona
CHAINS	
	T 39 N R 10 E S 24 1/4
	2013
	Deposit a magnet, in a white plastic case, at the base of the stainless steel post.
	Set a steel fence post nearby.
80.00	The cor. of secs. 23, 24, 25, and 26.
	Land, rolling and broken. Soil, sandy loam and sandstone rock outcrops. Timber, sparse juniper. Undergrowth, native grasses, greasewood, and yucca.
	N. 0°01' W., bet. secs. 23 and 24.
	Over gently rolling land.
40.00	Point for the 1/4 sec. cor. of secs. 23 and 24.
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 25 ins. in the ground, with brass cap mkd.
	T 39 N R 10 E 1/4
	S 23   S 24
	2013
	Deposit a magnet, in a white plastic case, at the base of the stainless steel post.
	Set a steel fence post nearby.
80.00	Point for the cor. of secs. 13, 14, 23, and 24.
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.
	T 39 N R 10 E S 14   S 13 S 23   S 24
	2013

	T. 39 N., R. 10 E., Gila and Salt River Meridian, Arizona
CHAINS	
	Deposit a magnet, in a white plastic case, at the base of the stainless steel post.
	Set a steel fence post nearby.
	Land, gently rolling. Soil, sandy loam. No timber. Undergrowth, native grasses, greasewood, yucca, and Mormon tea.
	From the cor. of secs. 13, 18, 19, and 24 on the E. bdy. of the Tp., hereinbefore described.
	West, bet. secs. 13 and 24.
	Over gently rolling land.
40.00	Point for the 1/4 sec. cor. of secs. 13 and 24.
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 25 ins. in the ground, with brass cap mkd.
	T 39 N R 10 E  S 13  1/4 ——  S 24
	2013
	Deposit a magnet, in a white plastic case, at the base of the stainless steel post.
	Set a steel fence post nearby.
80.00	The cor. of secs. 13, 14, 23, and 24.
	Land, gently rolling. Soil, sandy loam.
	No timber. Undergrowth, native grasses, greasewood, and Mormon tea.
	N. 0°01' W., bet. secs. 13 and 14.
	Over gently rolling land.
40.00	Point for the 1/4 sec. cor. of secs. 13 and 14.
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.

	T. 39 N., R. 10 E., Gila and Salt River Meridian, Arizona
CHAINS	
	T 39 N R 10 E 1/4 S 14   S 13
	2013
	Deposit a magnet, in a white plastic case, at the base of the stainless steel post.
	Set a steel fence post nearby.
69.00	Trail road, bears S. 50° E. and N. 50° W.
69.80	High voltage transmission line, bears S. 50° E. and N. 50° W.
80.00	Point for the cor. of secs. 11, 12, 13, and 14.
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 25 ins. in the ground, with brass cap mkd.
	T 39 N R 10 E S 11   S 12
	S 11   S 12 S 14   S 13
	2013
	Deposit a magnet, in a white plastic case, at the base of the stainless steel post.
	Set a steel fence post nearby.
	Cor. is located 2.75 chs. S. and 3.05 chs. E. of trail road, bears N. 55° E. and S. 35° W.
	Land, gently rolling. Soil, sandy loam.
	No timber. Undergrowth, native grasses, greasewood, yucca, and Mormon tea.
	From the cor. of secs. 7, 12, 13, and 18 on the E. bdy. of the Tp., hereinbefore described.
	West, bet. secs. 12 and 13.
	Over gently rolling land.
40.00	Point for the 1/4 sec. cor. of secs. 12 and 13.
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.

CHAINS	
	T 39 N R 10 E
	S 12
	1/4 —— S 13
	2013
	Deposit a magnet, in a white plastic case, at the base of the stainless steel post.
	Set a steel fence post nearby.
80.00	The cor. of secs. 11, 12, 13, and 14.
	Land, gently rolling. Soil, sandy loam and sandstone rock outcrops. Timber, sparse juniper. Undergrowth, native grasses, greasewood, salt brush, and yucca.
	N. 0°01' W., bet. secs. 11 and 12.
	Over gently rolling land.
40.00	Point for the 1/4 sec. cor. of secs. 11 and 12.
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.
	T 39 N R 10 E 1/4 S 11   S 12
	2013
	Deposit a magnet, in a white plastic case, at the base of the stainless steel post.
	Set a steel fence post nearby.
	Cor. is located 1.60 chs. N. and 85 lks. W. of trail road, bears N. 20° E. and S. 20° W.
53.50	Barbed wire fence, 5 strand, bears S. 70° E. and N. 70° W.
80.00	Point for the cor. of secs. 1, 2, 11, and 12.
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 25 ins. in the ground, with brass cap mkd.
	T 39 N R 10 E  S 2   S 1  S 11   S 12
	2013

	T. 39 N., R. 10 E., Gila and Salt River Meridian, Arizona
CHAINS	
	Deposit a magnet, in a white plastic case, at the base of the stainless steel post.
	Set a steel fence post nearby.
	Land, gently rolling. Soil, sandy loam. No timber. Undergrowth, native grasses, greasewood, yucca, and Mormon tea.
	From the cor. of secs. 1, 6, 7, and 12 on the E. bdy. of the Tp., hereinbefore described.
	West, bet. secs. 1 and 12.
	Over gently rolling land.
40.00	Point for the 1/4 sec. cor. of secs. 1 and 12.
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with brass cap mkd.
	T 39 N R 10 E  S 1  1/4 ——  S 12
	2013
	Deposit a magnet, in a white plastic case, at the base of the stainless steel post.
	Set a steel fence post nearby.
80.00	The cor. of secs. 1, 2, 11, and 12.
	Land, gently rolling. Soil, sandy loam. No timber.
	Undergrowth, native grasses, greasewood, and Mormon tea.
	N. 0°01' W., bet. secs. 1 and 2.
	Over gently rolling land.
40.00	Point for the 1/4 sec. cor. of secs. 1 and 2.
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.

	T. 39 N., R. 10 E., Gila and Salt River Meridian, Arizona
CHAINS	
	T 39 N R 10 E 1/4 S 2   S 1
	2013
	Deposit a magnet, in a white plastic case, at the base of the stainless steel post.
	Set a steel fence post nearby.
80.00	The cor. of secs. 1, 2, 35, and 36, on the N. bdy. of the Tp., hereinbefore described.
	Land, gently rolling. Soil, sandy loam and sandstone rock outcrops. No timber. Undergrowth, native grasses, greasewood, yucca, and Mormon tea.
	From the cor. of secs. 2, 3, 34 and 35, on the S. bdy. of the Tp., monumented with a stainless steel post, 2 1/2 ins. diam., firmly set, projecting 2 ins. above the ground, with brass cap mkd. T39N R10E S34 S35 S3 S2 T38N 2013.
	N. 0°01' W., bet. secs. 34 and 35.
	Over gently rolling land.
40.00	Point for the 1/4 sec. cor. of secs. 34 and 35.
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.
	T 39 N R 10 E 1/4 S 34   S 35
	2013
	Deposit a magnet, in a white plastic case, at the base of the stainless steel post.
	Set a steel fence post nearby.
	Cor. is located on top of ridge, 30 ft. high, bears N. 30° E. and S. 25° W., and is 1.05 chs. W. and 2.05 chs. N. of trail road, bears N. 30° E. and S. 20° W.
56.50	Bladed dirt road, 20 ft. wide, bears N. 30° E. and S. 20° W.
74.20	Trail road, bears S. 75° E. and N. 75° W.
80.00	Point for the cor. of secs. 26, 27, 34, and 35.

### Survey of the Subdivisional Lines,

	Survey of the Subdivisional Lines, T. 39 N., R. 10 E., Gila and Salt River Meridian, Arizona
CHAINS	
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 23 ins. in the ground, with brass cap mkd.
	T 39 N R 10 E S 27 S 26 S 34 S 35
	2013
	Deposit a magnet, in a white plastic case, at the base of the stainless steel post.
	Set a steel fence post nearby.
	Cor. is located 71 lks. S. and 1.15 chs. E. of trail road, bears N. 55° E. and S. 50° W.
	Land, gently rolling. Soil, sandy loam and sandstone bedrock. No timber. Undergrowth, native grasses, sage brush, and Mormon tea.
	From the cor. of secs. 25, 26, 35, and 36.
	West, bet. secs. 26 and 35.
	Over gently rolling land.
14.35	E. right-of-way fence of State Highway 98, barbed wire, 4 strand, parallels highway.
15.85	State Highway 98, an asphalt surfaced road, 35 ft. wide, bears N. and S.
17.35	W. right-of-way fence of State Highway 98, barbed wire, 4 strand, parallels highway.
40.00	Point for the 1/4 sec. cor. of secs. 26 and 35.
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.
	T 39 N R 10 E S 26 1/4 S 35
	2013
	Deposit a magnet, in a white plastic case, at the base of the

stainless steel post.

	T. 39 N., R. 10 E., Gila and Salt River Meridian, Arizona
CHAINS	
	Set a steel fence post nearby.
80.00	The cor. of secs. 26, 27, 34, and 35.
	Land, gently rolling. Soil, sandy loam. No timber. Undergrowth, native grasses, sage brush, yucca, and Mormon tea.
	N. 0°01' W., bet. secs. 26 and 27.
	Over gently rolling land.
40.00	Point for the 1/4 sec. cor. of secs. 26 and 27.
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 25 ins. in the ground, with brass cap mkd.
	T 39 N R 10 E 1/4 S 27   S 26
	2013
	Deposit a magnet, in a white plastic case, at the base of the stainless steel post.
	Set a steel fence post nearby.
80.00	Point for the cor. of secs. 22, 23, 26, and 27.
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.
	T 39 N R 10 E S 22   S 23 S 27   S 26
	2013
	Deposit a magnet, in a white plastic case, at the base of the stainless steel post.
	Set a steel fence post nearby.
	Land, gently rolling. Soil, sandy loam. No timber. Undergrowth, native grasses, greasewood, cholla cactus, yucca, and Mormon tea.

	T. 39 N., R. 10 E., Gila and Salt River Meridian, Arizona
CHAINS	
	From the cor. of secs. 23, 24, 25, and 26.
	West, bet. secs. 23 and 26.
	Over gently rolling land.
15.95	E. right-of-way fence of State Highway 98, barbed wire, 4 strand, parallels highway.
17.45	State Highway 98, an asphalt surfaced road, 35 ft. wide, bears N. and S.
18.95	W. right-of-way fence of State Highway 98, barbed wire, 4 strand, parallels highway.
40.00	Point for the 1/4 sec. cor. of secs. 23 and 26.
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 25 ins. in the ground, with brass cap mkd.
	T 39 N R 10 E S 23 1/4 — S 26
	2013
	Deposit a magnet, in a white plastic case, at the base of the stainless steel post.
	Set a steel fence post nearby.
	Cor. is located 2.30 chs. S. and 1.70 chs. E. of trail road, bears N. 30° E. and S. 30° W.
80.00	The cor. of secs. 22, 23, 26, and 27.
	Land, gently rolling. Soil, sandy loam.
	No timber. Undergrowth, native grasses, greasewood, yucca, and Mormon tea.
	N. 0°01' W., bet. secs. 22 and 23.
	Over rolling land.
40.00	Point for the 1/4 sec. cor. of secs. 22 and 23.
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 25 ins. in the ground, with brass cap mkd.

	T. 39 N., R. 10 E., Gila and Salt River Meridian, Arizona
CHAINS	
	T 39 N R 10 E 1/4
	S 22   S 23
	2013
	Deposit a magnet, in a white plastic case, at the base of the stainless steel post.
	Set a steel fence post nearby.
55.70	Trail road, bears S. 75° E. and N. 75° W.
80.00	Point for the cor. of secs. 14, 15, 22, and 23.
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.
	T 39 N R 10 E S 15   S 14
	S 22 S 23
	2013
	Deposit a magnet, in a white plastic case, at the base of the stainless steel post.
	Set a steel fence post nearby.
	Land, gently rolling. Soil, sandy loam. No timber. Undergrowth, native grasses, greasewood, yucca, and Mormon tea.
	From the cor. of secs. 13, 14, 23, and 24.
	West, bet. secs. 14 and 23.
	Over gently rolling land.
17.90	E. right-of-way fence of State Highway 98, barbed wire, 4 strand, parallels highway.
19.45	State Highway 98, an asphalt surfaced road, 35 ft. wide, bears S. 10° E. and N. 10° W.
20.95	W. right-of-way fence of State Highway 98, barbed wire, 4 strand, parallels highway.
40.00	Point for the 1/4 sec. cor. of secs. 14 and 23.

	1. 59 N., R. 10 E., Gila and Balt Rivel Melidian, Alizona
CHAINS	
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 25 ins. in the ground, with brass cap mkd.
	T 39 N R 10 E
	S 14 1/4 ——
	S 23
	2013
	Deposit a magnet, in a white plastic case, at the base of the stainless steel post.
	Set a steel fence post nearby.
71.20	Trail road, bears S. 25° E. and N. 25° W.
80.00	The cor. of secs. 14, 15, 22, and 23.
	Land, gently rolling. Soil, sandy loam.
	No timber.
	Undergrowth, native grasses, greasewood, yucca, and Mormon tea.
	N. 0°01' W., bet. secs. 14 and 15.
	Over gently rolling land.
36.30	Trail road, bears N. 40° E. and S. 40° W.
40.00	Point for the 1/4 sec. cor. of secs. 14 and 15.
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.
	T 39 N R 10 E
	1/4 S 15   S 14
	'
	2013
	Deposit a magnet, in a white plastic case, at the base of the stainless steel post.
	Set a steel fence post nearby.
80.00	Point for the cor. of secs. 10, 11, 14, and 15.
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.

	1. 39 N., R. 10 E., Gila and Salt River Meridian, Arizona
CHAINS	
	T 39 N R 10 E
	<u>S 10   S 11</u>
	S 15   S 14
	2013
	Deposit a magnet, in a white plastic case, at the base of the stainless steel post.
	Set a steel fence post nearby.
	Cor. is located 1.30 chs. E. and 4.50 chs. N. of trail road, bears S. 15° E. and N. 15° W.
	Land, gently rolling. Soil, sandy loam. No timber.
	Undergrowth, native grasses, greasewood, yucca, and Mormon tea.
	From the cor. of secs. 11, 12, 13, and 14.
	West, bet. secs. 11 and 14.
	Over gently rolling land.
12.05	High voltage transmission line, bears S. 50° E. and N. 50° W.
13.30	Trail road, bears S. 50° E. and N. 50° W.
40.00	Point for the 1/4 sec. cor. of secs. 11 and 14.
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.
	T 39 N R 10 E S 11 1/4 — S 14
	2013
	Deposit a magnet, in a white plastic case, at the base of the stainless steel post.
	Set a steel fence post nearby.
56.60	E. right-of-way fence of State Highway 98, barbed wire, 4 strand, parallels highway.
58.30	State Highway 98, an asphalt surfaced road, 35 ft. wide, bears S. 30° E. and N. 30° W.

	T. 39 N., R. 10 E., Gila and Salt River Meridian, Arizona
CHAINS	
60.00	W. right-of-way fence of State Highway 98, barbed wire, 4 strand, parallels highway.
80.00	The cor. of secs. 10, 11, 14, and 15.
	Land, gently rolling. Soil, sandy loam. No timber. Undergrowth, native grasses, greasewood, salt brush, and Mormon tea.
	N. 0°01' W., bet. secs. 10 and 11.
	Over gently rolling broken land.
40.00	Point for the 1/4 sec. cor. of secs. 10 and 11.
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 25 ins. in the ground, with brass cap mkd.
	T 39 N R 10 E
	1/4 S 10   S 11
	· ·
	2013
	Deposit a magnet, in a white plastic case, at the base of the stainless steel post.
	Set a steel fence post nearby.
	Cor. is located 95 lks W. and 1.85 chs. S. of State Highway 98, an asphalt surfaced road, 35 ft. wide, bears S. 25° E. and N. 25° W., and 73 lks. E. and 1.40 chs. N. of the W. right-of-way fence, barbed wire, 4 strand, parallels highway.
45.10	E. right-of-way fence of State Highway 98, barbed wire, 4 strand, bears S. 25° E. and N. 25° W.
57.55	High voltage transmission line, bears S. 50° E. and N. 50° W.
80.00	Point for the cor. of secs. 2, 3, 10, and 11.
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.
	T 39 N R 10 E S 3 S 2
	S 10   S 11
	2013

CHAINS
--------

Deposit a magnet, in a white plastic case, at the base of the stainless steel post.

Set a steel fence post nearby.

Cor. is located 2.75 chs. W. of mesa rim, 50 ft. high, bears N. 25° E. and S. 70° W., and 1.30 chs. N. of the same mesa rim, 50 ft. high, bears N. 75° E. and W.

Land, gently rolling and broken.

Soil, sandy loam and sandstone rock outcrops.

No timber.

Undergrowth, native grasses and greasewood.

From the cor. of secs. 1, 2, 11, and 12.

West, bet. secs. 2 and 11.

Over gently rolling broken land.

40.00 Point for the 1/4 sec. cor. of secs. 2 and 11.

Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 25 ins. in solid limestone bedrock, with brass cap mkd.

2013

Deposit a magnet, in a white plastic case, at the base of the stainless steel post.

Set a steel fence post nearby.

Cor. is located halfway up the left bank of limestone bed rock, 8 ft. high, bears S. 20° E. and N. 20° W., and is 25 lks. E. of wash, 10 ft. wide, 2 ft. deep, drains N. 10° W.

80.00 The cor. of secs. 2, 3, 10, and 11.

Land, gently rolling and broken.

Soil, sandy loam, sandstone rock outcrops and limestone bedrock. Timber, sparse juniper.

Undergrowth, native grasses, greasewood, yucca, salt brush, and  ${\tt Mormon}$  tea.

N. 0°01' W., bet. secs. 2 and 3.

diam.,
of the
. deep,
the Tp.,
h, and
of the diam.,
ailroad,
, bears
ailroad,
diam., , 3 ft.
daras nail , ail

CHAINS

2013

Deposit a magnet, in a white plastic case, at the base of the stainless steel post.

Cor. is located 3.30 chs. S. of graded road, 17 ft. wide, bears N. 80° E. and S. 80° W.

80.00

Point for the cor. of secs. 27, 28, 33, and 34.

Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with brass cap mkd.

2013

Deposit a magnet, in a white plastic case, at the base of the stainless steel post.

Set a steel fence post nearby.

Land, gently rolling.

Soil, sandy loam.

No timber.

Undergrowth, native grasses, cholla cactus, yucca, and Mormon tea.

From the cor. of secs. 26, 27, 34, and 35.

West, bet. secs. 27 and 34.

Over gently rolling land.

40.00

Point for the 1/4 sec. cor. of secs. 27 and 34.

Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 25 ins. in the ground, with brass cap mkd.

2013

CHAINS	
	Deposit a magnet, in a white plastic case, at the base of the stainless steel post.
	Set a steel fence post nearby.
47.05	Sandstone rim, 40 ft. high, bears S. 65° E. and N. 80° W.
80.00	The cor. of secs. 27, 28, 33, and 34.
	Land, gently rolling and broken. Soil, sandy loam and sandstone rock outcrops. No timber. Undergrowth, native grasses, greasewood, yucca, and Mormon tea.
	N. 0°02' W., bet. secs. 27 and 28.
	Over gently rolling land through open valley.
40.00	Point for the 1/4 sec. cor. of secs. 27 and 28.
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.
	T 39 N R 10 E 1/4 S 28   S 27
	2013
	Deposit a magnet, in a white plastic case, at the base of the stainless steel post.
	Set a steel fence post nearby.
80.00	Point for the cor. of secs. 21, 22, 27, and 28.
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 25 ins. in the ground, with brass cap mkd.
	T 39 N R 10 E S 21   S 22 S 28   S 27
	2013
	Deposit a magnet, in a white plastic case, at the base of the stainless steel post.
	Set a steel fence post nearby.
	Cor. is located 2.60 chs. E. of Black Mesa and Lake Powell Railroad, 5 ft. bet. rails, bears N. 10° E. and S. 10° W.

CHAINS	
	Land, gently rolling. Soil, sandy loam. No timber. Undergrowth, native grasses, greasewood, cholla cactus, yucca, and Mormon tea.
	From the cor. of secs. 22, 23, 26, and 27.
	West, bet. secs. 22 and 27.
	Over gently rolling land.
40.00	Point for the 1/4 sec. cor. of secs. 22 and 27.
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam.,
	24 ins. in the ground, with brass cap mkd.
	T 39 N R 10 E S 22 1/4 —— S 27
	2013
	Deposit a magnet, in a white plastic case, at the base of the stainless steel post.
	Set a steel fence post nearby.
44.80	Wash, 15 ft. wide, 4 ft. deep, drains N. 20° W.
80.00	The cor. of secs. 21, 22, 27, and 28.
	Land, gently rolling. Soil, sandy loam and sandstone rock outcrops. No timber. Undergrowth, native grasses, greasewood, and Mormon tea.
	N. 0°02' W., bet. secs. 21 and 22.
	Over gently rolling land through open valley.
6.20	E. right-of-way fence of Black Mesa and Lake Powell Railroad, woven and barbed wire, parallels railroad.
12.10	Black Mesa and Lake Powell Railroad, 5 ft. bet. rails, bears N. 10° E. and S. 10° W.
16.60	W. right-of-way fence of Black Mesa and Lake Powell Railroad, woven and barbed wire, parallels railroad.

	T. 39 N., R. 10 E., Gila and Salt River Meridian, Arizona
CHAINS	
40.00	Point for the 1/4 sec. cor. of secs. 21 and 22.
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.
	T 39 N R 10 E 1/4 S 21   S 22
	2013
	Deposit a magnet, in a white plastic case, at the base of the stainless steel post.
	Set a steel fence post nearby.
48.73	From this point, the hand pump to water well, firmly set in a concrete pad 10 $\times$ 10 $\times$ 2 ft., mkd. BEEHOTEL WELL on top of concrete pad., bears W., 19.78 chs. dist.
80.00	Point for the cor. of secs. 15, 16, 21, and 22.
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.
	T 39 N R 10 E S 16   S 15 S 21   S 22
	2013
	Deposit a magnet, in a white plastic case, at the base of the stainless steel post.
	Set a steel fence post nearby.
	Land, gently rolling. Soil, sandy loam. No timber.
	Undergrowth, native grasses, greasewood, and Mormon tea.
	From the cor. of secs. 14, 15, 22, and 23.
	West, bet. secs. 15 and 22.
	Over gently rolling land.
36.60	Trail road, bears N. 75° W. and S. 75° W.
40.00	Point for the 1/4 sec. cor. of secs. 15 and 22.

	1. 39 N., R. 10 E., GITA AND SAIT RIVER METIDIAN, ATTZONA
CHAINS	
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 25 ins. in the ground, with brass cap mkd.
	T 39 N R 10 E
	S 15 1/4 ——
	S 22
	2013
	Deposit a magnet, in a white plastic case, at the base of the stainless steel post.
	Set a steel fence post nearby.
60.70	E. right-of-way fence of Black Mesa and Lake Powell Railroad, woven and barbed wire, parallels railroad.
62.05	Black Mesa and Lake Powell Railroad, 5 ft. bet. rails, bears N. 30° E. and S. 30° W.
63.40	W. right-of-way fence of Black Mesa and Lake Powell Railroad, woven and barbed wire, parallels railroad.
80.00	The cor. of secs. 15, 16, 21, and 22.
	Land, gently rolling. Soil, sandy loam. No timber. Undergrowth, native grasses, yucca, and Mormon tea.
	N. 0°02' W., bet. secs. 15 and 16.
	Over gently rolling land along the E. foothills.
40.00	Point for the 1/4 sec. cor. of secs. 15 and 16.
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.
	T 39 N R 10 E 1/4 S 16   S 15
	2013
	Deposit a magnet, in a white plastic case, at the base of the stainless steel post.
	Set a steel fence post nearby.
80.00	Point for the cor. of secs. 9, 10, 15, and 16.

<u> </u>	T. 39 N., R. 10 E., Gila and Salt River Meridian, Arizona
CHAINS	
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.
	T 39 N R 10 E S 9 S 10 S 16 S 15
	'
	2013
	Deposit a magnet, in a white plastic case, at the base of the stainless steel post.
	Land, gently rolling and broken. Soil, sandy loam and sandstone bedrock. No timber.
	Undergrowth, native grasses, greasewood, yucca, and Mormon tea.
	From the cor. of secs. 10, 11, 14, and 15.
	West, bet. secs. 10 and 15.
	Over gently rolling land.
34.45	Trail road, bears N. 20° E. and S. 20° W.
40.00	Point for the 1/4 sec. cor. of secs. 10 and 15.
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.
	T 39 N R 10 E
	S 10 1/4 ———
	S 15
	2013
	Deposit a magnet, in a white plastic case, at the base of the stainless steel post.
	Set a steel fence post nearby.
	Cor. is located 2.25 chs. E. of trail road, bears N and S.
55.65	E. right-of-way fence of Black Mesa and Lake Powell Railroad, woven and barbed wire, parallels railroad.
56.55	Black Mesa and Lake Powell Railroad, 5 ft. bet. rails, bears S. 35° E. and N. 35° W.

	T. 39 N., R. 10 E., Gila and Salt River Meridian, Arizona
CHAINS	
57.45	W. right-of-way fence of Black Mesa and Lake Powell Railroad, woven and barbed wire, parallels railroad.
80.00	The cor. of secs. 9, 10, 15, and 16.
	Land, gently rolling. Soil, sandy loam. No timber. Undergrowth, native grasses, greasewood, and Mormon tea.
	N. 0°02' W., bet. secs. 9 and 10.
	Over gently rolling land, ascending E. foothills.
35.05	W. right-of-way fence of Black Mesa and Lake Powell Railroad, woven and barbed wire, parallels railroad.
36.70	Black Mesa and Lake Powell Railroad, 5 ft. bet. rails, bears S. 35° E. and N. 35° W.
38.00	E. right-of-way fence of Black Mesa and Lake Powell Railroad, woven and barbed wire, parallels railroad.
40.00	Point for the 1/4 sec. cor. of secs. 9 and 10.
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with brass cap mkd.
	T 39 N R 10 E 1/4 S 9   S 10
	2013
	Deposit a magnet, in a white plastic case, at the base of the stainless steel post.
	Set a steel fence post nearby.
68.90	Bladed dirt road, 10 ft. wide, bears S. 25° E. and N. 25° W.
80.00	Point for the cor. of secs. 3, 4, 9, and 10.
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 25 ins. in the ground, with brass cap mkd.
	T 39 N R 10 E  S 4   S 3  S 9   S 10
	2013

CHAINS	
	Deposit a magnet, in a white plastic case, at the base of the stainless steel post.
	Set a steel fence post nearby.
	Cor. is located 2.95 chs. E. of bladed dirt road, 10 ft. wide, bears N. and S.
	Land, gently rolling. Soil, sandy loam. No timber. Undergrowth, native grasses, greasewood, cholla cactus, yucca, and Mormon tea.
	From the cor. of secs. 2, 3, 10, and 11.
	West, bet. secs. 3 and 10.
	Over gently rolling land.
14.25	High voltage transmission line, bears S. 25° E. and N. 25° W.
14.95	Trail road, bears S. 25° E. and N. 25° W.
18.05	E. right-of-way fence of State Highway 98, barbed wire,
10.03	4 strand, parallels highway.
19.80	State Highway 98, an asphalt surfaced road, 35 ft. wide, bears S. 30° E. and N. 30° W.
21.45	W. right-of-way fence of State Highway 98, barbed wire, 4 strand, parallels highway.
40.00	Point for the 1/4 sec. cor. of secs. 3 and 10.
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 25 ins. in the ground, with brass cap mkd.
	T 39 N R 10 E S 3
	1/4 <del></del>
	2013
	Deposit a magnet, in a white plastic case, at the base of the stainless steel post.
	Set a steel fence post nearby.
80.00	The cor. of secs. 3, 4, 9, and 10.

	T. 39 N., R. 10 E., Gila and Salt River Meridian, Arizona
CHAINS	
	Land, gently rolling. Soil, sandy loam. No timber. Undergrowth, native grasses, greasewood, cholla cactus, yucca and Mormon tea.
	N. 0°02' W., bet. secs. 3 and 4.
	Over gently rolling land.
40.00	Point for the 1/4 sec. cor. of secs. 3 and 4.
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam. 26 ins. in the ground, with brass cap mkd.
	T 39 N R 10 E
	1/4 S 4   S 3
	2013
	Deposit a magnet, in a white plastic case, at the base of th stainless steel post.
	Set a steel fence post nearby.
80.00	The cor. of secs. 3, 4, 33, and 34, on the N. bdy. of the Tp. hereinbefore described.
	Land, gently rolling. Soil, sandy loam. No timber. Undergrowth, native grasses, greasewood, cholla cactus, and yucca.
	From the cor. of secs. 4, 5, 32 and 33, on the S. bdy. of th Tp., monumented with a stainless steel post, 2 1/2 ins. diam. firmly set, projecting 3 ins. above the ground, with brass ca mkd. T39N R10E S32 S33 S5 S4 T38N 2013.
	N. 0°03' W., bet. secs. 32 and 33.
	Over gently rolling land through open valley.
40.00	Point for the 1/4 sec. cor. of secs. 32 and 33.
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam. 24 ins. in the ground, with brass cap mkd.

	1. 39 N., R. 10 E., GIIA and Sait River Meridian, Arizona
CHAINS	
	T 39 N R 10 E
	1/4 S 32   S 33
	2013
	Deposit a magnet, in a white plastic case, at the base of the stainless steel post.
56.05	Trail road, bears S. 75° E. and N. 75° W.
80.00	Point for the cor. of secs. 28, 29, 32, and 33.
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.
	T 39 N R 10 E
	S 29   S 28
	S 32   S 33
	2013
	Deposit a magnet, in a white plastic case, at the base of the stainless steel post.
	Land, gently rolling. Soil, sandy loam. No timber. Undergrowth, native grasses and greasewood.
	From the cor. of secs. 27, 28, 33, and 34.
	West, bet. secs. 28 and 33.
	Over gently rolling land.
7.15	E. right-of-way fence of Black Mesa and Lake Powell Railroad, woven and barbed wire, parallels railroad.
8.10	Black Mesa and Lake Powell Railroad, 5 ft. bet. rails, bears S. 5° E. and N. 5° W.
10.25	W. right-of-way fence of Black Mesa and Lake Powell Railroad, woven and barbed wire, parallels railroad.
40.00	Point for the 1/4 sec. cor. of secs. 28 and 33.
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.
1 1	ı

	T. 39 N., R. 10 E., Gila and Salt River Meridian, Arizona
CHAINS	
	T 39 N R 10 E S 28
	1/4 ——
	S 33
	2013
	Deposit a magnet, in a white plastic case, at the base of the stainless steel post.
80.00	The cor. of secs. 28, 29, 32, and 33.
	Land, gently rolling. Soil, sandy loam. No timber.
	Undergrowth, native grasses, sagebrush, yucca, and Mormon tea.
	N. 0°03' W., bet. secs. 28 and 29.
	Over gently rolling land through open valley.
40.00	Point for the 1/4 sec. cor. of secs. 28 and 29.
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.
	T 39 N R 10 E 1/4 S 29   S 28
	2013
	Deposit a magnet, in a white plastic case, at the base of the stainless steel post.
80.00	Point for the cor. of secs. 20, 21, 28, and 29.
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.
	T 39 N R 10 E S 20 S 21
	S 29   S 28
	2013
	Deposit a magnet, in a white plastic case, at the base of the stainless steel post.
	Set a steel fence post nearby.

CHAINS									
	Land, gently rolling. Soil, sandy loam. No timber. Undergrowth, native grasses, cholla cactus, yucca, and Mormon tea.								
	From the cor. of secs. 21, 22, 27, and 28.								
	West, bet. secs. 21 and 28.								
	Over gently rolling land.								
40.00	Point for the 1/4 sec. cor. of secs. 21 and 28.								
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 25 ins. in the ground, with brass cap mkd.								
	T 39 N R 10 E S 21 1/4 ——								
	S 28								
	2013								
	Deposit a magnet, in a white plastic case, at the base of the stainless steel post.								
	Set a steel fence post nearby.								
	Cor. is located 2.80 chs. E. of trail road, bears N. 30° E. and S. 30° W.								
80.00	The cor. of secs. 20, 21, 28, and 29.								
	Land, gently rolling. Soil, sandy loam. No timber. Undergrowth, native grasses, greasewood, cholla cactus, yucca,								
	and Mormon tea.								
	N. 0°03' W., bet. secs. 20 and 21.								
	Over rolling land.								
40.00	Point for the 1/4 sec. cor. of secs. 20 and 21.								
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with brass cap mkd.								

### Survey of the Subdivisional Lines

	Survey of the Subdivisional Lines, T. 39 N., R. 10 E., Gila and Salt River Meridian, Arizona
CHAINS	1. 39 N., R. 10 E., Gila and Sait River Meridian, Arizona
	T 39 N R 10 E  1/4  S 20   S 21
	2013
	Deposit a magnet, in a white plastic case, at the base of the stainless steel post.
	Set a steel fence post nearby.
80.00	Point for the cor. of secs. 16, 17, 20, and 21.
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 25 ins. in the ground, with brass cap mkd.
	T 39 N R 10 E  S 17   S 16  S 20   S 21
	2013
	Deposit a magnet, in a white plastic case, at the base of the stainless steel post.
	Set a steel fence post nearby.
	Land, rolling. Soil, sandy loam and sandstone rock outcrops. Timber, sparse juniper. Undergrowth, native grasses, greasewood, yucca, and Mormon tea.
	From the cor. of secs. 15, 16, 21, and 22.
	West, bet. secs. 16 and 21.
	Descending into Upper Antelope Canyon.
40.00	Point for the 1/4 sec. cor. of secs. 16 and 21.
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with brass cap mkd.
	T 39 N R 10 E S 16 1/4
	2013

Deposit a magnet, in a white plastic case, at the base of the stainless steel post.

	T. 39 N., R. 10 E., Gila and Salt River Meridian, Arizona							
CHAINS								
	Set a steel fence post nearby.							
80.00	The cor. of secs. 16, 17, 20, and 21.							
	Land, gently rolling and broken. Soil, sandy loam and sandstone bedrock. No timber. Undergrowth, native grasses, greasewood, cholla cactus, yucca, and Mormon tea.							
	N. 0°03' W., bet. secs. 16 and 17.							
	Bottom of descent of Upper Antelope Canyon.							
40.00	Point for the 1/4 sec. cor. of secs. 16 and 17.							
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.							
	T 39 N R 10 E							
	S 17   S 16							
	2013							
	Deposit a magnet, in a white plastic case, at the base of the stainless steel post.							
	Set a steel fence post nearby.							
80.00	Point for the cor. of secs. 8, 9, 16, and 17.							
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.							
	T 39 N R 10 E							
	S 8 S 9 S 17 S 16							
	2013							
	Deposit a magnet, in a white plastic case, at the base of the stainless steel post.							
	Set a steel fence post nearby.							
	Land, rolling and broken. Soil, sandy loam and sandstone rock outcrops. Timber, sparse juniper. Undergrowth, native grasses, greasewood, yucca, and Mormon tea.							
	From the cor. of secs. 9, 10, 15, and 16.							

	T. 39 N., R. 10 E., Gila and Salt River Meridian, Arizona								
CHAINS									
	West, bet. secs. 9 and 16.								
	Gently descending into Upper Antelope Canyon.								
34.05	Sandstone rim, 40 ft. high, bears N. 40° E. and S. 40° W.								
40.00	Point for the 1/4 sec. cor. of secs. 9 and 16.								
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 25 ins. in the ground, with brass cap mkd.								
	T 39 N R 10 E S 9 1/4 S 16								
	2013								
	Deposit a magnet, in a white plastic case, at the base of the stainless steel post.								
	Set a steel fence post nearby.								
	Cor. is located on the N. edge of ridge, bears N. 60° E. and S. 70° W.								
80.00	The cor. of secs. 8, 9, 16, and 17.								
	Land, gently rolling and broken. Soil, sandy loam and sandstone bedrock. No timber. Undergrowth, native grasses, greasewood, and Mormon tea.								
	N. 0°03' W., bet. secs. 8 and 9.								
	Bottom of descent of Upper Antelope Canyon.								
35.45	Antelope Creek, 15 ft. wide, 3 ft. deep, drains N. 50° W.								
40.00	Point for the 1/4 sec. cor. of secs. 8 and 9.								
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 25 ins. in the ground, with brass cap mkd.								
	T 39 N R 10 E  1/4  S 8   S 9								
	2013								

	T. 39 N., R. 10 E., Gila and Salt River Meridian, Arizona												
CHAINS													
	Deposit a magnet, in a white plastic case, at the base of the stainless steel post.												
	Set a steel fence post nearby.												
80.00	Point for the cor. of secs. 4, 5, 8, and 9.												
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 25 ins. in the ground, with brass cap mkd.												
	T 39 N R 10 E  S 5 S 4  S 8 S 9												
	2013												
	Deposit a magnet, in a white plastic case, at the base of the stainless steel post.												
	Set a steel fence post nearby.												
	Land, rolling and broken. Soil, sandy loam. No timber. Undergrowth, native grasses, greasewood, cholla cactus, yucca, and Mormon tea.												
	From the cor. of secs. 3, 4, 9, and 10.												
	West, bet. secs. 4 and 9.												
	Over gently rolling land.												
20.60	E. right-of-way fence of Black Mesa and Lake Powell Railroad, woven and barbed wire, parallels railroad.												
22.50	Black Mesa and Lake Powell Railroad, 5 ft. bet. rails, bears S. 15° E. and N. 15° W.												
24.35	W. right-of-way fence of Black Mesa and Lake Powell Railroad, woven and barbed wire, parallels railroad.												
40.00	Point for the 1/4 sec. cor. of secs. 4 and 9.												
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.												

	T. 39 N., R. 10 E., Gila and Salt River Meridian, Arizona							
CHAINS								
	T 39 N R 10 E S 4 1/4 —— S 9							
	2013							
	Deposit a magnet, in a white plastic case, at the base of the stainless steel post.							
	Set a steel fence post nearby.							
80.00	The cor. of secs. 4, 5, 8, and 9.							
	Land, gently rolling and broken. Soil, sandy loam and sandstone rock outcrops. No timber. Undergrowth, native grasses, greasewood, yucca, and Mormon tea.							
	N. 0°03' W., bet. secs. 4 and 5.							
	Over rolling land, along E. foothills of Upper Antelope Creek.							
40.00								
40.00	True point for the 1/4 sec. cor. of secs. 4 and 5, located on the steep edge of sandstone rock face, where it is impracticable to set a permanent monument.							
	From this true point, the point selected for a witness cor. to the 1/4 sec. cor. of secs. 4 and 5, bears N. 45°22' E., 1.20 ch. dist.							
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.							
	WC							
	T 39 N R 10 E 1/4							
	S 5   S 4							
	2013							
	Deposit a magnet, in a white plastic case, at the base of the stainless steel post.							
	Set a steel fence post nearby.							
	Witness cor. is located 41 lks. N. of sandstone rim, 25 ft. high, bears N. 80° E. and S. 40° W.							
80.00	The cor. of secs. 4, 5, 32, and 33, on the N. bdy. of the Tp., hereinbefore described.							

### Survey of the Subdivisional Lines,

	Survey of the Subdivisional Lines, T. 39 N., R. 10 E., Gila and Salt River Meridian, Arizona							
CHAINS								
	Land, rolling and broken.  Soil, sandy loam.  No timber.  Undergrowth, native grasses, greasewood, yucca, and Mormon tea.							
	From the cor. of secs. 5, 6, 31 and 32, on the S. bdy. of the Tp., monumented with a stainless steel post, 2 1/2 ins. diam., firmly set, projecting 4 ins. above the ground, with brass cap mkd. T39N R10E S31 S32 S6 S5 T38N 2013.							
	N. 0°03' W., bet. secs. 31 and 32.							
	Over rolling land.							
40.00	Point for the 1/4 sec. cor. of secs. 31 and 32.							
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 25 ins. in the ground, with brass cap mkd.							
	T 39 N R 10 E							
	1/4 S 31   S 32							
	2013							
	Deposit a magnet, in a white plastic case, at the base of the stainless steel post.							
	Set a steel fence post nearby.							
43.25	Wash, 13 ft. wide, 2 ft. deep, drains N. 55° E.							
76.60	Antelope Creek, 26 ft. wide, 3 ft. deep, drains N. 30° E.							
80.00	Point for the cor. of secs. 29, 30, 31, and 32.							
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in solid sandstone bedrock, with brass cap mkd.							
	T 39 N R 10 E S 30 S 29							
	S 31   S 32							
	2013							
	Deposit a magnet, in a white plastic case, at the base of the stainless steel post.							
	Set a steel fence post nearby.							
	Cor. is located 1.60 chs. W. of Antelope Creek, 46 ft. wide,							

3 ft. deep, drains N. 30° E.

	1. Jy N., K. 10 B., Gila and Balt Rivel Melidian, Alizona
CHAINS	
	Land, rolling and broken. Soil, sandy loam and sandstone rock outcrops. Timber, juniper.
	Undergrowth, native grasses, greasewood, yucca, and Mormon tea.
	From the cor. of secs. 28, 29, 32, and 33.
	West, bet. secs. 29 and 32.
	Over gently rolling land.
40.00	Point for the 1/4 sec. cor. of secs. 29 and 32.
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 25 ins. in the ground, with brass cap mkd.
	T 39 N R 10 E
	S 29
	1/4 ————————————————————————————————————
	2013
	Deposit a magnet, in a white plastic case, at the base of the stainless steel post.
	Set a steel fence post nearby.
80.00	The cor. of secs. 29, 30, 31, and 32.
	Land, gently rolling. Soil, sandy loam. Timber, scattered juniper. Undergrowth, native grasses, greasewood, cholla cactus, yucca, prickly pear, and Mormon tea.
	West, bet. secs. 30 and 31.
	Over gently rolling land.
40.00	Point for the 1/4 sec. cor. of secs. 30 and 31.
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.
	T 39 N R 10 E
	S 30 1/4 ——
	S 31
	2013

	T. 39 N., R. 10 E., Gila and Salt River Meridian, Arizona							
CHAINS								
	Deposit a magnet, in a white plastic case, at the base of the stainless steel post.							
	Set a steel fence post nearby.							
60.60	Trail road, bears N. 20° E. and S. 20° W.							
78.82	The cor. of secs. 25, 30, 31 and 36, on the W. bdy. of the Tp., hereinbefore described.							
	Land, gently rolling. Soil, sandy loam. Timber, scarce juniper. Undergrowth, native grasses, sage brush, yucca, and Mormon tea.							
	From the cor. of secs. 29, 30, 31, and 32.							
	N. 0°03' W., bet. secs. 29 and 30.							
	Over gently rolling land.							
40.00	Point for the 1/4 sec. cor. of secs. 29 and 30.							
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.							
	T 39 N R 10 E 1/4 S 30   S 29							
	2013							
	Deposit a magnet, in a white plastic case, at the base of the stainless steel post.							
	Set a steel fence post nearby.							
80.00	Point for the cor. of secs. 19, 20, 29, and 30.							
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.							
	T 39 N R 10 E S 19   S 20 S 30   S 29							
	2013							
	Deposit a magnet, in a white plastic case, at the base of the stainless steel post.							

	1. John, K. 10 I., Gila and Balt Rivel Melialan, Milbona							
CHAINS								
	Set a steel fence post nearby.							
	Land, gently rolling. Soil, sandy loam. Timber, scattered juniper. Undergrowth, native grasses, salt brush, sage brush, yucca, and Mormon tea.							
	From the cor. of secs. 20, 21, 28, and 29.							
	West, bet. secs. 20 and 29.							
	Over gently rolling land.							
40.00	Point for the 1/4 sec. cor. of secs. 20 and 29.							
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 25 ins. in the ground, with brass cap mkd.							
	T 39 N R 10 E S 20 1/4 —— S 29							
	2013							
	Deposit a magnet, in a white plastic case, at the base of the stainless steel post.							
	Set a steel fence post nearby.							
46.45	Sandstone rim, 60 ft. high, bears N. 20° E. and S. 5° W.							
80.00	The cor. of secs. 19, 20, 29, and 30.							
	Land, gently rolling and broken. Soil, sandy loam and sandstone bedrock. Timber, scattered juniper. Undergrowth, native grasses, greasewood and Mormon tea.							
	West, bet. secs. 19 and 30.							
	Over gently rolling land.							
33.65	Wash, 8 ft. wide, 4 ft. deep, drains N. 55° E.							
40.00	Point for the 1/4 sec. cor. of secs. 19 and 30.							
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 25 ins. in the ground, with brass cap mkd.							

	T. 39 N., R. 10 E., Gila and Salt River Meridian, Arizona												
CHAINS													
	T 39 N R 10 E  S 19  1/4 S 30												
	2013												
	Deposit a magnet, in a white plastic case, at the base of the stainless steel post.												
	Set a steel fence post nearby.												
78.73	The cor. of secs. 19, 24, 25, and 30, on the W. bdy. of the Tp., hereinbefore described.												
	Land, gently rolling. Soil, sandy loam. Timber, scattered juniper. Undergrowth, native grasses, salt brush, sage brush, and Mormon tea.												
	From the cor. of secs. 19, 20, 29, and 30.												
	N. 0°03' W., bet. secs. 19 and 20.												
	Over gently rolling land.												
23.25	S. rim of sandstone cliff, 45 ft. high, bears N. 40° E. and S. 40° W.												
29.55	N. rim of sandstone cliff, 45 ft. high, bears N. 60° E. and S. 60° W.												
40.00	Point for the 1/4 sec. cor. of secs. 19 and 20.												
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 25 ins. in the ground, with brass cap mkd.												
	T 39 N R 10 E												
	1/4 S 19   S 20												
	2013												
	Deposit a magnet, in a white plastic case, at the base of the stainless steel post.												
	Set a steel fence post nearby.												
80.00	Point for the cor. of secs. 17, 18, 19, and 20.												

	 	/	 	,	~ ·	WII.U	Darc	KIVEL	meridian,
CHAINS									

Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.

2013

Deposit a magnet, in a white plastic case, at the base of the stainless steel post.

Set a steel fence post nearby.

Cor. is located 68 lks. S. and 58 lks. E. of trail road, bears N. 40° E. and S. 30° W.

Land, gently rolling.

Soil, sandy loam.

No timber.

Undergrowth, native grasses, sage brush, and Mormon tea.

From the cor. of secs. 16, 17, 20, and 21.

West, bet. secs. 17 and 20.

Over gently rolling land, through Upper Antelope Canyon.

40.00 | Point for the 1/4 sec. cor. of secs. 17 and 20.

Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 25 ins. in the ground, with brass cap mkd.

T 39 N R 10 E 
$$\begin{array}{c} \text{S 17} \\ \text{1/4} \\ \hline \text{S 20} \end{array}$$

2013

Deposit a magnet, in a white plastic case, at the base of the stainless steel post.

Set a steel fence post nearby.

49.35 | Sandstone rim, 70 ft. high, bears S. 40° E. and N. 40° W.

80.00 The cor. of secs. 17, 18, 19, and 20.

	T. 39 N., R. 10 E., Gila and Salt River Meridian, Arizona
CHAINS	
	Land, gently rolling and broken. Soil, sandy loam. No scattered juniper. Undergrowth, native grasses, greasewood, yucca, and Mormon tea.
	West, bet. secs. 18 and 19.
	Over gently rolling land.
40.00	Point for the 1/4 sec. cor. of secs. 18 and 19.
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.
	T 39 N R 10 E  S 18  1/4 ——  S 19
	2013
	Deposit a magnet, in a white plastic case, at the base of the stainless steel post.
	Set a steel fence post nearby.
	Cor. is located 3.80 chs. W. of trail road, bears N. 55° E. and S. 55° W.
78.63	The cor. of secs. 13, 18, 19, and 24, on the W. bdy. of the Tp., hereinbefore described.
	Land, gently rolling. Soil, sandy loam. No timber. Undergrowth, native grasses, sage brush, yucca, and Mormon tea.
	From the cor. of secs. 17, 18, 19, and 20.
	N. 0°03' W., bet. secs. 17 and 18.
	Over gently rolling land.
40.00	Point for the 1/4 sec. cor. of secs. 17 and 18.
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.

	T. 39 N., R. 10 E., Gila and Salt River Meridian, Arizona
CHAINS	
	T 39 N R 10 E
	1/4 S 18   S 17
	2013
	Deposit a magnet, in a white plastic case, at the base of the stainless steel post.
	Set a steel fence post nearby.
52.40	Sandstone rim, 75 ft. high, bears S. 55° E. and N. 55° W.
76.40	Sandstone rim, 70 ft. high, bears N. 85° E. and S. 85° W.
80.00	Point for the cor. of secs. 7, 8, 17, and 18.
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 25 ins. in the ground, with brass cap mkd.
	T 39 N R 10 E  S 7   S 8  S 18   S 17
	2013
	Deposit a magnet, in a white plastic case, at the base of the stainless steel post.
	Cor. is located 69 lks. N. and 21 lks. E. of sandstone rim, 60 ft. high, bears S. 15° E. and N. 10° W.
	Land, gently rolling to broken. Soil, sandy loam and sandstone bedrock. No timber.
	Undergrowth, native grasses, sage brush, and Mormon tea.
	From the cor. of secs. 8, 9, 16, and 17.
	West, bet. secs. 8 and 17.
	Ascending W. slope of Upper Antelope Canyon.
4.15	Base of sandstone rim, 60 ft. high, bears S. 35° W. and N. 35° W.
6.15	Top of sandstone rim, 50 ft. high, bears N. 55° E. and S. 35° E.
35.25	Sandstone rim, 75 ft. high, bears N. 20° E. and S. 10° W.

	T. 39 N., R. 10 E., Gila and Salt River Meridian, Arizona
CHAINS	
40.00	Point for the 1/4 sec. cor. of secs. 8 and 17.
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.
	T 39 N R 10 E S 8
	1/4 <del>S 8</del> S 17
	2013
	Deposit a magnet, in a white plastic case, at the base of the stainless steel post.
	Set a steel fence post nearby.
80.00	The cor. of secs. 7, 8, 17, and 18.
	Land, rolling and broken. Soil, sandy loam. No timber.
	Undergrowth, native grasses, yucca, and Mormon tea.
	West, bet. secs. 7 and 18.
	Descending into canyon.
31.45	Sandstone rim, 50 ft. high, bears S. and N. 10° W.
40.00	Point for the 1/4 sec. cor. of secs. 7 and 18.
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.
	T 39 N R 10 E
	S 7 1/4 ——
	S 18
	2013
	Deposit a magnet, in a white plastic case, at the base of the stainless steel post.
	Set a steel fence post nearby.
	Cor. is located 3.90 chs. W. of trail road, bears N. 10° E. and S. 10° W.
46.45	Sandstone rim, 75 ft. high, bears S. 5° W. and N. 15° W.

	T. 39 N., R. 10 E., Gila and Salt River Meridian, Arizona
CHAINS	
61.20	Sandstone rim, 80 ft. high, bears N. 45° E. and S. 65° W.
78.54	The cor. of secs. 7, 12, 13, and 18, on the W. bdy. of the Tp., hereinbefore described.
	Land, rolling and broken. Soil, sandy loam and sandstone bedrock. No timber. Undergrowth, native grasses, sage brush, and Mormon tea.
	From the cor. of secs. 7, 8, 17, and 18.
	N. 0°03' W., bet. secs. 7 and 8.
	Gently rolling, on top of sandstone mesa.
40.00	Point for the 1/4 sec. cor. of secs. 7 and 8.
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.
	T 39 N R 10 E 1/4 S 7   S 8
	2013
	Deposit a magnet, in a white plastic case, at the base of the stainless steel post.
	Cor. is located 76 lks. S. of sandstone rim, 70 ft. high, bears S. 25° E. and N. 25° W.
80.00	Point for the cor. of secs. 5, 6, 7, and 8.
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with brass cap mkd.
	T 39 N R 10 E S 6   S 5 S 7   S 8
	2013
	Deposit a magnet, in a white plastic case, at the base of the stainless steel post.
	Set a steel fence post nearby.

	T. 39 N., R. 10 E., Gila and Salt River Meridian, Arizona
CHAINS	
	Land, gently rolling and broken. Soil, sandy loam and sandstone bedrock. No timber. Undergrowth, native grasses, greasewood, yucca, and Mormon tea.
	From the cor. of secs. 4, 5, 8, and 9.
	West, bet. secs. 5 and 8.
	Over gently rolling land.
40.00	Point for the 1/4 sec. cor. of secs. 5 and 8.
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 21 ins. in solid sandstone bedrock, with brass cap mkd.
	T 39 N R 10 E S 5 1/4 ——
	S 8
	2013
	Deposit a magnet, in a white plastic case, at the base of the stainless steel post.
	Cor. is located 15 lks. S. and 61 lks. W. of sandstone rim of Upper Antelope Canyon, 80 ft. high, bears E. and S. 40° E.
80.00	The cor. of secs. 5, 6, 7, and 8.
	Land, gently rolling and broken. Soil, sandy loam and sandstone bedrock.
	No timber. Undergrowth, native grasses, greasewood, yucca, and cholla cactus.
	West, bet. secs. 6 and 7.
	Over gently rolling land.
40.00	Point for the 1/4 sec. cor. of secs. 6 and 7.
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 21 ins. in solid sandstone bedrock, encircled with a collar of stone, 3 ft. base, to top, with brass cap mkd.
:	

	T. 39 N., R. 10 E., Gila and Salt River Meridian, Arizona
CHAINS	
	T 39 N R 10 E
	S 6
	1/4
	S 7
	2013
	Deposit a magnet, in a white plastic case, at the base of the stainless steel post.
	Cor. is located on a ridge, 165 ft. wide, bears N. 25° E. and S. 25° W., and is 70 lks. S. of sandstone rim, 70 ft. high, bears N. 80° E. and S. 60° W.
	Cor. is also 100 lks W. of sandstone rim, 130 ft. high, bears S. 20° W. and N. 35° W., and is 140 lks E. of sandstone rim, 60 ft. high, bears N. 10° E. and S. 60° W.
78.45	The cor. of secs. 1, 6, 7, and 12, on the W. bdy. of the Tp., hereinbefore described.
	Land, gently rolling and broken. Soil, sandy loam and sandstone bedrock. Timber, sparse juniper. Undergrowth, native grasses, greasewood, yucca, and Mormon tea.
	From the cor. of secs. 5, 6, 7, and 8.
	N. 0°03' W., bet. secs. 5 and 6.
	Over gently rolling land, through Upper Antelope Canyon.
38.80	W. bank of Antelope Creek, a sandstone bluff, 130 ft. high, bears S. 25° E. and N. 55° W.
40.00	True point for the 1/4 sec. cor. of secs. 5 and 6, located at the bottom of Antelope Creek, where it is prone to frequent flash flooding, it is impracticable to set a permanent monument.
	From this true point, the point selected for a witness cor. to the 1/4 sec. cor. of secs. 5 and 6, bears N. 32°00' W., 5.00 chs. dist.
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with brass cap mkd.
	WC T 39 N R 10 E 1/4
	S 6   S 5
	2013

	T. 39 N., R. 10 E., Gila and Salt River Meridian, Arizona
CHAINS	
	Deposit a magnet, in a white plastic case, at the base of the stainless steel post.
	Set a steel fence post nearby.
	From this cor. point, the W. bank of Antelope Creek, a sandstone bluff, 100 ft. high, extends N. 15° E. and S. 50° W., bears N. 80° E., 2.70 chs. dist.
80.00	The cor. of secs. 5, 6, 31, and 32, on the N. bdy. of the Tp., hereinbefore described.
	Land, gently rolling and broken. Soil, sandy loam and sandstone bedrock. Timber, sparse juniper. Undergrowth, native grasses, greasewood, yucca and Mormon tea.
	Subdivision of Section 3, T. 39 N., R. 10 E., Gila and Salt River Meridian, Arizona
	From the 1/4 sec. cor. of secs. 3 and 10.
	N. 00°02' W., on the N. and S. center line of sec. 3.
	Over gently rolling land.
33.70	Trail road, bears N. 55° E. and S. 55° W.
40.00	Point for the center 1/4 sec. cor. of sec. 3, at intersection with the E. and W. center line sec. 3.
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.
	T 39 N R 10 E C 1/4 S 3
	2013
	Deposit a magnet, in a white plastic case, at the base of the stainless steel post.
	Set a steel fence post nearby.
48.70	Trail road, bears S. 25° E. and N. 25° W.
49.65	High voltage transmission line, bears S. 25° E. and N. 25° W.
80.00	The 1/4 sec. cor. of secs. 3 and 34, on the N. bdy. of the Tp.

Subdivision of Section 3, T. 39 N., R. 10 E., Gila and Salt River Meridian, Arizona

	T. 39 N., R. 10 E., Gila and Salt River Meridian, Arizona
CHAINS	
	From the 1/4 sec. cor. of secs. 2 and 3.
	West, on the E. and W. center line of sec. 3.
	Over gently rolling land.
30.85	E. right-of-way fence of State Highway 98, barbed wire, 4 strand, parallels highway.
32.35	State Highway 98, an asphalt surfaced road, 35 ft. wide, bears N. 5° E. and S. 5° W.
33.85	W. right-of-way fence of State Highway 98, barbed wire, 4 strand, parallels highway.
35.05	High voltage transmission line, bears S. 25° E. and N. 25° W.
35.65	Trail road, bears S. 30° E. and N. 30° W.
40.00	The center 1/4 sec. cor. of sec. 3.
80.00	The 1/4 sec. cor. of secs. 3 and 4.
	T. 39 N., R. 10 E., Gila and Salt River Meridian, Arizona  From the 1/4 sec. cor. of secs. 10 and 15.
	N. 00°02' W., on the N. and S. center line of sec. 10.
22.25	Over gently rolling land.
33.25	Trail road, bears N. 75° E. and S. 75° W.
40.00	Point for the center 1/4 sec. cor. of sec. 10, at intersection with the E. and W. center line sec. 10.
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.
	T 39 N R 10 E C 1/4 S 10
	2013
	Deposit a magnet, in a white plastic case, at the base of the stainless steel post.
	Set a steel fence post nearby.
80.00	The 1/4 sec. cor. of secs. 3 and 10.
	1 ·

Subdivision of Section 10, T. 39 N., R. 10 E., Gila and Salt River Meridian, Arizona

	T. 39 N., R. 10 E., Gila and Salt River Meridian, Arizona
CHAINS	
	From the 1/4 sec. cor. of secs. 10 and 11.
	West, on the E. and W. center line of sec. 10.
	Over gently rolling land.
15.25	Trail road, bears N. 35° E. and S. 35° W.
40.00	The center 1/4 sec. cor. of sec. 10.
60.40	Trail road, bears S. 35° E. and N. 35° W.
80.00	The 1/4 sec. cor. of secs. 9 and 10.
	Subdivision of Section 11, T. 39 N., R. 10 E., Gila and Salt River Meridian, Arizona
	From the 1/4 sec. cor. of secs. 11 and 14.
	N. 00°01' W., on the N. and S. center line of sec. 11.
	Over gently rolling land.
22.75	Trail road, bears S. 50° E. and N. 50° W.
23.70	High voltage transmission line, bears S. 50° E. and N. 50° W.
36.65	Barbed wire fence, 5 strand, bears N. 65° E. and S. 65° W.
40.00	Point for the center 1/4 sec. cor. of sec. 11, at intersection with the E. and W. center line sec. 11.
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with brass cap mkd.
	T 39 N R 10 E C 1/4 S 11
	2013
	Deposit a magnet, in a white plastic case, at the base of the stainless steel post.
	Set a steel fence post nearby.
80.00	The 1/4 sec. cor. of secs. 2 and 11.
	From the 1/4 sec. cor. of secs. 11 and 12.  West, on the E. and W. center line of sec. 11.
1	

Subdivision of Section 11, T. 39 N., R. 10 E., Gila and Salt River Meridian, Arizona

	The state of the s
CHAINS	
	Over gently rolling land.
33.10	Barbed wire fence, 5 strand, bears N. 65° E. and S. 65° W.
40.00	The center 1/4 sec. cor. of sec. 11.
80.00	The 1/4 sec. cor. of secs. 10 and 11.
	Subdivision of Section 14, T. 39 N., R. 10 E., Gila and Salt River Meridian, Arizona
	From the 1/4 sec. cor. of secs. 14 and 23.
	N. 00°01' W., on the N. and S. center line of sec. 14.
	Over gently rolling land.
40.00	Point for the center 1/4 sec. cor. of sec. 14, at intersection with the E. and W. center line sec. 14.
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.
	T 39 N R 10 E C 1/4 S 14
	2013
	Deposit a magnet, in a white plastic case, at the base of the stainless steel post.
	Set a steel fence post nearby.
	Cor. is located within State Highway 98 right-of-way, 1.40 chs. S. and 72 lks. W. of the W. right-of-way fence of State Highway 98, barbed wire, 4 strand, parallels highway.
	Cor. is also located 2.40 chs. W. of State Highway 98, an asphalt surfaced road, 35 ft. wide, bears S. 25° E. and N. 25° W.
44.60	State Highway 98, an asphalt surfaced road, 35 ft. wide, bears S. 25° E. and N. 25° W.
47.90	E. right-of-way fence of State Highway 98, barbed wire, 4 strand, parallels highway.
80.00	The 1/4 sec. cor. of secs. 11 and 14.

Subdivision of Section 14,
T. 39 N., R. 10 E., Gila and Salt River Meridian, Arizona

	T. 39 N., R. 10 E., Gila and Salt River Meridian, Arizona
CHAINS	
	From the 1/4 sec. cor. of secs. 13 and 14.
	West, on the E. and W. center line of sec. 14.
	Over gently rolling land.
35.90	E. right-of-way fence of State Highway 98, barbed wire, 4 strand, bears S. 25° E. and N. 25° W.
40.00	The center 1/4 sec. cor. of sec. 14.
80.00	The 1/4 sec. cor. of secs. 14 and 15.
	Subdivision of Section 23, T. 39 N., R. 10 E., Gila and Salt River Meridian, Arizona
	From the 1/4 sec. cor. of secs. 23 and 26.
	N. 00°01' W., on the N. and S. center line of sec. 23.
	Over gently rolling land.
40.00	Point for the center 1/4 sec. cor. of sec. 23, at intersection with the E. and W. center line sec. 23.
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.
	T 39 N R 10 E C 1/4 S 23
	2013
	Deposit a magnet, in a white plastic case, at the base of the stainless steel post.
	Set a steel fence post nearby.
80.00	The 1/4 sec. cor. of secs. 14 and 23.
	From the 1/4 sec. cor. of secs. 23 and 24.
	West, on the E. and W. center line of sec. 23.
	Over gently rolling land.
16.75	E. right-of-way fence of State Highway 98, barbed wire, 4 strand, parallels highway.

### Subdivision of Section 23, T. 39 N., R. 10 E., Gila and Salt River Meridian, Arizona

	T. 39 N., R. 10 E., Gila and Salt River Meridian, Arizona
CHAINS	
18.25	State Highway 98, an asphalt surfaced road, 35 ft. wide, bears N. and S.
19.75	W. right-of-way fence of State Highway 98, barbed wire, 4 strand, parallels highway.
40.00	The center 1/4 sec. cor. of sec. 23.
80.00	The 1/4 sec. cor. of secs. 22 and 23.
	Subdivision of Section 26, T. 39 N., R. 10 E., Gila and Salt River Meridian, Arizona
	From the 1/4 sec. cor. of secs. 26 and 35.
	N. 00°01' W., on the N. and S. center line of sec. 26.
	Over gently rolling land.
40.00	Point for the center 1/4 sec. cor. of sec. 26, at intersection with the E. and W. center line sec. 26.
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.
	T 39 N R 10 E C 1/4 S 26
	2013
	Deposit a magnet, in a white plastic case, at the base of the stainless steel post.
	Cor. is located 1.60 chs. S. and 87 lks. W. of trail road, bears S. 5° W. and N. 30° W.
74.35	Trail road, bears S. 20° E. and N. 20° W.
80.00	The 1/4 sec. cor. of secs. 23 and 26.
	From the 1/4 sec. cor. of secs. 25 and 26.
	West, on the E. and W. center line of sec. 26.
	Over gently rolling land.
15.15	E. right-of-way fence of State Highway 98, barbed wire, 4 strand, parallels highway.

Subdivision of Section 26, T. 39 N., R. 10 E., Gila and Salt River Meridian, Arizona

	T. 39 N., R. 10 E., Gila and Salt River Meridian, Arizona		
CHAINS			
16.65	State Highway 98, an asphalt surfaced road, 35 ft. wide, bears N. and S.		
18.15	W. right-of-way fence of State Highway 98, barbed wire, 4 strand, parallels highway.		
40.00	The center 1/4 sec. cor. of sec. 26.		
80.00	The 1/4 sec. cor. of secs. 26 and 27.		
	Subdivision of Section 35, T. 39 N., R. 10 E., Gila and Salt River Meridian, Arizona		
	From the 1/4 sec. cor. of secs. 2 and 35, on the S. bdy. of the Tp.		
N. 00°01' W., on the N. and S. center line of sec. 35.			
	Over gently rolling land.		
36.05	Trail road, bears N. 50° E. and S. 50° W.		
40.00	Point for the center 1/4 sec. cor. of sec. 35, at intersection with the E. and W. center line sec. 35.		
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.		
	T 39 N R 10 E C 1/4 S 35		
	2013		
	Deposit a magnet, in a white plastic case, at the base of the stainless steel post.		
Set a steel fence post nearby.			
	From this cor. point, four-way intersection of trail roads, extending N. 50° E., S. 30° E., S. 40° W. and N. 30° W., bears N. 75° E., 5.35 chs. dist.		
49.55	Trail road, bears S. 30° E. and N. 30° W.		
60.65	Bladed dirt road, 25 ft. wide, bears E. and W.		
80.00	The 1/4 sec. cor. of secs. 26 and 35.		
	From the 1/4 sec. cor. of secs. 35 and 36.		

Subdivision of Section 35,
T. 39 N., R. 10 E., Gila and Salt River Meridian, Arizona

	T. 39 N., R. 10 E., Gila and Salt River Meridian, Arizona		
CHAINS			
	West, on the E. and W. center line of sec. 35.		
	Over gently rolling land.		
13.50	E. right-of-way fence of State Highway 98, barbed wire 4 strand, parallels highway.		
15.05	State Highway 98, an asphalt surfaced road, 35 ft. wide, bears N. and S.		
16.55	W. right-of-way fence of State Highway 98, barbed wire 4 strand, parallels highway.		
40.00	The center 1/4 sec. cor. of sec. 35.		
80.00	The 1/4 sec. cor. of secs. 34 and 35.		

#### T. 39 N., R. 10 E., Gila and Salt River Meridian, Arizona

CHAINS

#### GENERAL DESCRIPTION

The area surveyed is within the Navajo Indian Reservation, is 22 miles northwest of the Kaibeto community, 10 miles southeast of the Lechee community, and 15 miles southeast of Page, Arizona. Primary access is State Highway 98. An unnamed bladed dirt road is accessible from highway in section 35, and continues west exiting the township in section 31. From the bladed road, a series of trail roads provide access throughout the township. ATV's were required to access the majority of the areas within the township.

There are no major housing developments, only smaller housing clusters and single home units mainly in the east third portion of the township. The Black Mesa and Lake Powell Railroad that supplies coal to the Navajo power plant in Page, meanders through the east half of the township.

The highest elevation of this survey, 5700 feet above sea level, is in the southeast portion of the township; decreasing in elevation toward the northern portion of the township. The lowest elevation, at 4800 feet is in the northwest portion of the township, in Antelope Creek.

The vegetation consists of scattered and sparse juniper throughout the township and densely scattered in the Upper Antelope Canyon. Sage brush, salt brush, greasewood, yucca, cholla cactus, Mormon tea and other native grasses, are more prominent throughout the township. There is presence of grazing cattle, sheep and horses in the area. The soil is mostly sandy loam with sandstone rock bluffs and sandstone canyons near Upper Antelope Canyon.

The mean magnetic declination of 11 $^{\circ}$  E. was derived from the United States Geological Survey computer program GEOMAG, utilizing the World Magnetic Model for Epoch 2010-2005 for the dates of survey.

# UNITED STATES DEPARTMENT OF THE INTERIOR BUREAU OF LAND MANAGEMENT

#### FIELD ASSISTANTS

NAMES	CAPACITY			
Mark R. Searles	Surveying Technician			
Daniel Bryan	Engineering Technician			
Byron Shorty	Engineering Technician			
Kevin Tso	Engineering Technician			

#### CERTIFICATE OF SURVEY

I, Fabian Yazzie, Cadastral Surveyor, HEREBY CERTIFY upon honor, that in pursuance of special instructions bearing date of the 4th day of February, 2013, I have surveyed the East, West, and North boundaries, and the subdivisional lines, and the subdivision of certain sections, T. 39 N., R. 10 E., of the Gila and Salt River Meridian, in the State of Arizona, which are represented in the foregoing field notes as having been executed by me and under my direction. Said survey has been made in strict conformity with said special instructions, the Manual of Instructions for the Survey of the Public Lands of the United States, 2009, and in specific manner described in the foregoing field notes.

3/20/2014 (Cadastral Surveyor)

#### CERTIFICATE OF APPROVAL

#### BUREAU OF LAND MANAGEMENT Phoenix, Arizona

The foregoing field notes of the survey of the East, West, and North boundaries, and the subdivisional lines, and the subdivision of certain sections, T. 39 N., R. 10 E., Gila and Salt River Meridian, in the State of Arizona, executed by Fabian Yazzie, Cadastral Surveyor, having been critically examined and found correct, are hereby approved.

3/26/2014
(Date)

CERTIFICATE OF TRANSCRIPT

I CERTIFY That the foregoing transcript of the field notes of the above described surveys in T. 39 N., R. 19 E., Gila and Salt River Meridian, Arizona, is a true copy of the original field notes.

(Chief Cadastral Surveyor of Arizona)