

ORIGINAL

**UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT**

FIELD NOTES
OF A PORTION OF
THE SECOND GUIDE MERIDIAN EAST (WEST BOUNDARY),
THE NORTH BOUNDARY,
THE SUBDIVISIONAL LINES,
AND
THE SUBDIVISION OF CERTAIN SECTIONS
TOWNSHIP 38 NORTH, RANGE 9 EAST,
OF THE GILA AND SALT RIVER MERIDIAN,
IN THE STATE OF ARIZONA.

EXECUTED BY

Fabian Yazzie, Cadastral Surveyor

Under Special Instructions dated July 31, 2013, approved July 31, 2013, which provided for the surveys included under Group No. 1122, and assignment instructions dated July 31, 2013.

Survey commenced August 27, 2013

Survey completed November 5, 2013

INDEX DIAGRAM

TOWNSHIP 38 NORTH RANGE 09 EAST GILA & SALT RIVER MERIDIAN, ARIZONA

	15	14	13	12	11	10
8	6	63 5	50 4	40 3	32 2	24 1
	62	61	49	40	31	23
7	7	60 8	48 9	39 10	31 11	22 12
	60	59	47	38	30	21
6	18	58 17	46 16	37 15	29 14	21 13
	57	56	46	36	29	20
5	19	55 20	44 21	36 22	28 23	19 24
	55	54	44	35	27	18
5	30	53 29	43 28	34 27	26 26	17 25
	52	52	42	34	25	16
4	31	51 32	41 33	32 34	24 35	16 36

Subdivision of Section 4	Pages 63-64
Subdivision of Section 8	Pages 64-65
Subdivision of Section 9	Pages 66
Subdivision of Section 17	Pages 66-68
Subdivision of Section 20	Pages 68
Subdivision of Section 21	Pages 69
Subdivision of Section 28	Pages 69-70
Subdivision of Section 33	Pages 70-71

T. 38 N., R. 9 E., Gila and Salt River Meridian, Arizona

CHAINS

The following field notes describe the survey of a portion of the Second Guide Meridian East (west boundary), the North boundary, the subdivisional lines, and the subdivision of certain sections, Township 38 North, Range 9 East, Gila and Salt River Meridian, Arizona.

The history of surveys pertaining to this survey is as follows:

Leonard R. Sandoval established the true point for the corner of Townships 39 and 40 North, Ranges 8 and 9 East, during the survey of a portion the Second Guide Meridian East, Township 40 North, Range 9 East, under Group No. 950, in 2009. Fabian Yazzie surveyed the West boundary (east boundary), Township 38 North, Range 10 East, under Group No. 1114, in 2012-13. Blas Urena surveyed the North boundary (south boundary) of Township 37 North, Range 9 East, under Group No. 1121, in 2013.

The survey was executed in accordance with the specifications as set forth in the Manual of Instructions for the Survey of the Public Lands of the United States, 2009, and the Special Instructions dated July 31, 2013, for Group Number 1122, Arizona.

The true meridian direction and length of all lines were determined by real time kinematic global positioning system observations using Trimble Navigation R8 and 5700 model receivers.

Geodetic control was derived from Global Positioning System (GPS) static observations post processed by National Geodetic Survey, Online Positioning User Service (OPUS), utilizing Continuously Operating Reference Stations (CORS) AI8805 FRED FREDONIA CORS, DI2245 P011 SPIDERROCKAZ2005 CORS, DJ8981 FST5 FLAGSTAFF 5 CORS, DL1882 AZFL NAU FLAGSTAFF CORS, and DK8419 AZPG CITY OF PAGE CORS. The NAD 83 (2011) (EPOCH: 2010), geographic position of the corner of Townships 37 and 38 North, Ranges 9 and 10 East, is as follows:

Latitude: 36°38'32.795" N. Longitude: 111°22'15.365" W.

The geographic position of the corner of Townships 38 and 39 North, Ranges 8 and 9 East, is as follows:

Latitude: 36°43'45.955" N. Longitude: 111°28'43.533" W.

The mean magnetic declination is 11° E.

Survey of a Portion of the Second Guide Meridian East (W. Bdy.),
T. 38 N., R. 9 E., Gila and Salt River Meridian, Arizona

CHAINS	
	<p>Beginning at the cor. of Tps. 37 and 38 N., Rs. 8 and 9 E., monumented with a brass tablet, 3 1/2 ins. diam., firmly set, flush with the surface of sandstone bedrock, with top mkd. T38N R8E R9E S36 S31 S1 S6 T37N 2013.</p> <p>North, bet. secs. 31 and 36.</p> <p>Over gently rolling land.</p> <p>40.00 Point for the 1/4 sec. cor. of secs. 31 and 36.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center;"> <p>T 38 N R 8 E R 9 E 1/4 S 36 S 31 2013</p> </div> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p> <p>Set a steel fence post nearby.</p> <p>Cor. is located 20 lks. N. of trail road , bears E. and N. 80° W.</p>
80.00	<p>Point for the cor. of secs. 25, 30, 31, and 36.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center;"> <p>T 38 N R 8 E R 9 E S 25 S 30 S 36 S 31 2013</p> </div> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p> <p>Set a steel fence post nearby.</p> <p>Land, gently rolling. Soil, sandy loam. Timber, juniper. Undergrowth, native grasses, sage brush, and Mormon tea.</p> <hr/>

Survey of a Portion of the Second Guide Meridian East (W. Bdy.),
T. 38 N., R. 9 E., Gila and Salt River Meridian, Arizona

CHAINS	
	<p>North, bet. secs. 25 and 30.</p> <p>Over gently rolling land.</p>
40.00	<p>Point for the 1/4 sec. cor. of secs. 25 and 30.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center;"> <p>T 38 N R 8 E R 9 E 1/4 S 25 S 30 2013</p> </div> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p> <p>Set a steel fence post nearby.</p>
80.00	<p>Point for the cor. of secs. 19, 24, 25, and 30.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center;"> <p>T 38 N R 8 E R 9 E S 24 S 19 S 25 S 30 2013</p> </div> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p> <p>Set a steel fence post nearby.</p> <p>Land, gently rolling. Soil, sandy loam. Timber, scattered juniper. Undergrowth, native grasses and sage brush.</p>
16.60	<p>North, bet. secs. 19 and 24.</p> <p>Over gently rolling land.</p> <p>Power line, bears N. 85° E. and S. 85° W.</p>
18.25	<p>Underground water line, bears S. 80° E. and N. 80° W.</p>

Survey of a Portion of the Second Guide Meridian East (W. Bdy.),
T. 38 N., R. 9 E., Gila and Salt River Meridian, Arizona

CHAINS	
40.00	<p>Point for the 1/4 sec. cor. of secs. 19 and 24.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center;"> <p>T 38 N R 8 E R 9 E 1/4 S 24 S 19</p> <p>2013</p> </div> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p> <p>Set a steel fence post nearby.</p>
80.00	<p>Point for the cor. of secs. 13, 18, 19, and 24.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center;"> <p>T 38 N R 8 E R 9 E S 13 S 18 S 24 S 19</p> <p>2013</p> </div> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p> <p>Set a steel fence post nearby.</p> <p>Land, gently rolling. Soil, sandy loam. Timber, juniper. Undergrowth, native grasses and sage brush.</p>
40.00	<hr/> <p>North, bet. secs. 13 and 18.</p> <p>Over gently rolling land.</p> <p>Point for the 1/4 sec. cor. of secs. 13 and 18.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p>

Survey of a Portion of the Second Guide Meridian East (W. Bdy.),
T. 38 N., R. 9 E., Gila and Salt River Meridian, Arizona

CHAINS	
	<p style="text-align: center;">T 38 N R 8 E R 9 E 1/4 S 13 S 18 2013</p>
	<p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p> <p>Set a steel fence post nearby.</p>
75.35	<p>Trail road, bears N. 50° E. and S. 50° W.</p>
80.00	<p>Point for the cor. of secs. 7, 12, 13, and 18.</p>
	<p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p>
	<p style="text-align: center;">T 38 N R 8 E R 9 E S 12 S 7 S 13 S 18 2013</p>
	<p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p> <p>Set a steel fence post nearby.</p> <p>Land, gently rolling. Soil, sandy loam. Timber, juniper. Undergrowth, native grasses, sage brush, and Mormon tea.</p> <hr/> <p>North, bet. secs. 7 and 12.</p> <p>Over gently rolling land.</p>
40.00	<p>Point for the 1/4 sec. cor. of secs. 7 and 12.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p>

Survey of a Portion of the Second Guide Meridian East (W. Bdy.),
T. 38 N., R. 9 E., Gila and Salt River Meridian, Arizona

CHAINS	
	<p style="text-align: center;">T 38 N R 8 E R 9 E 1/4 S 12 S 7 2013</p> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p> <p>Set a steel fence post nearby.</p>
80.00	<p>Point for the cor. of secs. 1, 6, 7, and 12.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 25 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T 38 N R 8 E R 9 E S 1 S 6 S 12 S 7 2013</p> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p> <p>Set a steel fence post nearby.</p> <p>Cor. is located 2.10 chs. N. of trail road , bears S. 10° E. and N. 10° W.</p> <p>Land, gently rolling. Soil, sandy loam. No timber. Undergrowth, native grasses and sage brush.</p>
40.00	<hr/> <p>North, bet. secs. 1 and 6.</p> <p>Over gently rolling land.</p> <p>Point for the 1/4 sec. cor. of secs. 1 and 6.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p>

Survey of a Portion of the Second Guide Meridian East (W. Bdy.),
T. 38 N., R. 9 E., Gila and Salt River Meridian, Arizona

CHAINS

T 38 N
R 8 E R 9 E
1/4
S 1 | S 6

2013

Deposit a magnet, in a white plastic case, at the base of the stainless steel post.

Set a steel fence post nearby.

Cor. is located 75 lks. N. of BIA Route 6211, a graded road, 25 ft. wide, bears S. 35° E. and N. 35° W.

80.00

Point for the cor. of secs. 1, 6, 31, and 36.

Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.

T 39 N
R 8 E | R 9 E
S 36 | S 31
S 1 | S 6
T 38 N

2013

Deposit a magnet, in a white plastic case, at the base of the stainless steel post.

Set a steel fence post nearby.

From this cor. point, the true point of Tps. 39 and 40 N., Rs. 8 and 9 E., bears North, 480.00 chs. dist., from this true point, a witness cor. of Tps. 39 and 40 N., Rs. 8 and 9 E., bears N. 24°00' E., 50 lks. dist., monumented with a brass tablet, 3 1/4 ins. diam., firmly set, flush with the surface of sandstone bedrock, with top mkd. WC T40N R8E R9E S36 S31 S1 S6 T39N 2005 2012 2013.

Land, gently rolling.

Soil, sandy loam.

Timber, juniper.

Undergrowth, native grasses, sage brush, yucca, and cholla grass.

Survey of the North Boundary,
T. 38 N., R. 9 E., Gila and Salt River Meridian, Arizona

CHAINS							
	<p>From the cor. of Tps. 38 and 39 N., Rs. 9 and 10 E., monumented with a stainless steel post, 2 1/2 ins. diam., firmly set, projecting 3 ins. above ground, with brass cap mkd. T39N R9E R10E S36 S31 S1 S6 T38N 2013, with a steel fence post, firmly set, N. of cor.</p> <p>West, bet. secs. 1 and 36.</p> <p>Over gently rolling land.</p>						
40.00	<p>Point for the 1/4 sec. cor. of secs. 1 and 36.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center;"> <p>T 39 N R 9 E</p> <p>S 36</p> <p>1/4 ———</p> <p>S 1</p> <p>T 38 N</p> <p>2013</p> </div> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p> <p>Set a steel fence post nearby.</p>						
80.00	<p>Point for the cor. of secs. 1, 2, 35, and 36.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in solid sandstone bedrock, with brass cap mkd.</p> <div style="text-align: center;"> <p>T 39 N R 9 E</p> <table style="margin: auto; border-collapse: collapse;"> <tr> <td style="border-right: 1px solid black; padding: 0 5px;">S 35</td> <td style="padding: 0 5px;">S 36</td> </tr> <tr> <td style="border-right: 1px solid black; padding: 0 5px;">S 2</td> <td style="padding: 0 5px;">S 1</td> </tr> <tr> <td colspan="2" style="text-align: center;">T 38 N</td> </tr> </table> <p>2013</p> </div> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p> <p>Set a steel fence post nearby.</p> <p>Cor. is located 10 lks. W. of sandstone rim, 6 ft. high, bears N. 5° E. and S. 5° W.</p> <p>Land, gently rolling and broken. Soil, sandy loam and sandstone bedrock. Timber, scattered juniper. Undergrowth, native grasses, greasewood, and Mormon tea.</p> <hr style="width: 60%; margin-left: 0;"/>	S 35	S 36	S 2	S 1	T 38 N	
S 35	S 36						
S 2	S 1						
T 38 N							

Survey of the North Boundary,
T. 38 N., R. 9 E., Gila and Salt River Meridian, Arizona

CHAINS	
	West, bet. secs. 2 and 35.
	Over gently rolling land.
9.00	Barbed wire fence, 5 strand, bears N. 25° E. and S. 25° W.
40.00	Point for the 1/4 sec. cor. of secs. 2 and 35.
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.
	T 39 N R 9 E S 35 1/4 ——— S 2 T 38 N 2013
	Deposit a magnet, in a white plastic case, at the base of the stainless steel post.
	Set a steel fence post nearby.
80.00	Point for the cor. of secs. 2, 3, 34, and 35.
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., flush with the surface of the ground, with brass cap mkd.
	T 39 N R 9 E S 34 S 35 S 3 S 2 T 38 N 2013
	Deposit a magnet, in a white plastic case, at the base of the stainless steel post.
	Set a steel fence post nearby.
	Cor. is located on the E. edge of bladed dirt road, 10 ft. wide, bears N. 50° E. and S. 50° W., and 1.95 chs. N. and W. of barbed wire fence, 5 strand, bears N. 45° E. and S. 45° W.
	Land, gently rolling. Soil, sandy loam. Timber, scarce juniper. Undergrowth, native grasses, greasewood, and Mormon tea.

**Survey of the North Boundary,
T. 38 N., R. 9 E., Gila and Salt River Meridian, Arizona**

CHAINS	
	West, bet. secs. 3 and 34. Over gently rolling land.
17.85	East bank of canyon wash, 40 ft. high, bears S. 25° E. and N. 25° W.
23.35	West bank of canyon wash, 40 ft. high, bears S. 40° E. and N. 40° W.
28.25	High voltage transmission line, bears N. 5° E. and S. 5° W.
30.25	High voltage transmission line, bears N. 5° E. and S. 5° W.
30.85	Trail road, bears N. 15° E. and S. 15° W.
40.00	Point for the 1/4 sec. cor. of secs. 3 and 34. Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 23 ins. in solid sandstone bedrock, with brass cap mkd. <div style="text-align: center;"> T 39 N R 9 E S 34 1/4 ——— S 3 T 38 N 2013 </div> Deposit a magnet, in a white plastic case, at the base of the stainless steel post. Set a steel fence post nearby. Cor. is located 1.75 chs. W. of trail road , bears S. 45° E. and N. 45° W.
80.00	Point for the cor. of secs. 3, 4, 33, and 34. Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 25 ins. in the ground, with brass cap mkd. <div style="text-align: center;"> T 39 N R 9 E S 33 S 34 S 4 S 3 T 38 N 2013 </div> Deposit a magnet, in a white plastic case, at the base of the stainless steel post. Set a steel fence post nearby.

Survey of the North Boundary,
T. 38 N., R. 9 E., Gila and Salt River Meridian, Arizona

CHAINS	
	<p>Land, gently rolling. Soil, sandy loam. Timber, scattered juniper. Undergrowth, native grasses, sage brush, greasewood, and Mormon tea.</p> <hr/> <p>West, bet. secs. 4 and 33.</p> <p>Over gently rolling land.</p>
40.00	<p>Point for the 1/4 sec. cor. of secs. 4 and 33.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 23 ins. in solid sandstone bedrock, with brass cap mkd.</p> <p style="text-align: center;">T 39 N R 9 E S 33 1/4 ——— S 4 T 38 N</p> <p style="text-align: center;">2013</p> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p> <p>Set a steel fence post nearby.</p>
62.95	Underground water line, bears S. 10° E. and N. 10° W.
71.30	Power line, bears N. and S.
71.90	E. right-of-way fence of BIA Route 20, barbed wire, 4 strand, parallels highway.
73.45	BIA Route 20, an asphalt surfaced road, 33 ft. wide, bears N. and S.
74.95	W. right-of-way fence of BIA Route 20, barbed wire, 4 strand, parallels highway.
80.00	<p>Point for the cor. of secs. 4, 5, 32, and 33.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T 39 N R 9 E S 32 S 33 S 5 S 4 T 38 N</p> <p style="text-align: center;">2013</p>

Survey of the North Boundary,
T. 38 N., R. 9 E., Gila and Salt River Meridian, Arizona

CHAINS	
	<p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p> <p>Set a steel fence post nearby.</p> <p>Land, gently rolling. Soil, sandy loam. Timber, scattered juniper. Undergrowth, native grasses, sage brush, yucca, cholla grass, and Mormon tea.</p> <hr/> <p>West, bet. secs. 5 and 32.</p> <p>Over gently rolling land.</p>
4.60	Trail road, bears N. and S.
5.35	Power line, bears N. and S.
40.00	<p>Point for the 1/4 sec. cor. of secs. 5 and 32.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center;"> <p>T 39 N R 9 E S 32 1/4 ——— S 5 T 38 N</p> <p>2013</p> </div>
	<p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p> <p>Set a steel fence post nearby.</p>
65.15	High voltage transmission line, bears N. 5° E. and S.
66.05	Trail road, bears N. 20° E. and S. 15° W.
69.80	Trail road, bears S. 75° E. and W.
80.00	<p>Point for the cor. of secs. 5, 6, 31, and 32.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p>

Survey of the North Boundary,
T. 38 N., R. 9 E., Gila and Salt River Meridian, Arizona

CHAINS	
	T 39 N R 9 E S 31 S 32 ----- S 6 S 5 T 38 N 2013
	Deposit a magnet, in a white plastic case, at the base of the stainless steel post. Set a steel fence post nearby. Land, gently rolling. Soil, sandy loam. Timber, scattered juniper. Undergrowth, native grasses, yucca, sage brush, and Mormon tea.
	West, bet. secs. 6 and 31. Over gently rolling land.
40.00	Point for the 1/4 sec. cor. of secs. 6 and 31. Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.
	T 39 N R 9 E S 31 1/4 ——— S 6 T 38 N 2013
	Deposit a magnet, in a white plastic case, at the base of the stainless steel post. Set a steel fence post nearby.
56.60	Top of sandstone rim of Circular White Ridge, 40 ft. high, bears S. 25° E. and N. 55° W.
78.92	The cor. of Tps. 38 and 39 N., Rs. 8 and 9 E., hereinbefore described. Land, gently rolling. Soil, sandy loam. Timber, scattered juniper. Undergrowth, native grasses, yucca, sage brush, and Mormon tea.


Survey of the Subdivisional Lines,
T. 38 N., R. 9 E., Gila and Salt River Meridian, Arizona

CHAINS	
	<p>From the cor. of secs. 1, 2, 35, and 36, on the S. bdy. of the Tp., monumented with a stainless steel post, 2 1/2 ins. diam., firmly set, projecting 4 ins. above ground, with brass cap mkd. T38N R9E S35 S36 S2 S1 T37N 2013.</p> <p>N. 0°01' W., bet. secs. 35 and 36.</p> <p>Over gently rolling land.</p>
40.00	<p>Point for the 1/4 sec. cor. of secs. 35 and 36.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 23 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center;"> <p>T 38 N R 9 E</p> <p>1/4</p> <p>S 35 S 36</p> <p>2013</p> </div> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p> <p>Set a steel fence post nearby.</p>
80.00	<p>Point for the cor. of secs. 25, 26, 35, and 36.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center;"> <p>T 38 N R 9 E</p> <p>S 26 S 25</p> <p>S 35 S 36</p> <p>2013</p> </div> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p> <p>Set a steel fence post nearby.</p> <p>Land, rolling.</p> <p>Soil, sandy loam and sandstone bedrock.</p> <p>Timber, juniper.</p> <p>Undergrowth, native grasses, sage brush, yucca, and Mormon tea.</p> <hr/> <p>From the cor. of secs. 25, 30, 31, and 36 on the E. bdy. of the Tp., monumented with a stainless steel post, 2 1/2 ins. diam., firmly set, projecting 4 ins. above ground, with brass cap mkd. T38N R9E R10E S25 S30 S36 S31 2012, with a steel fence post, firmly set, nearby.</p>

Survey of the Subdivisional Lines,
T. 38 N., R. 9 E., Gila and Salt River Meridian, Arizona

CHAINS	
40.00	<p>West, bet. secs. 25 and 36.</p> <p>Over gently rolling land.</p> <p>Point for the 1/4 sec. cor. of secs. 25 and 36.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center;"> <p>T 38 N R 9 E</p> <p>S 25</p> <p>1/4 ———</p> <p>S 36</p> <p>2013</p> </div> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p> <p>Set a steel fence post nearby.</p> <p>Cor. is located 40 lks. W. of trail road , extending N. 40° E., to intersect a bladed dirt road, 14 ft. wide, bears S. 25° E. and N. 25° W.</p>
80.00	<p>The cor. of secs. 25, 26, 35, and 36.</p> <p>Land, nearly level and slightly rolling.</p> <p>Soil, sandy loam.</p> <p>Timber, juniper and piñon.</p> <p>Undergrowth, native grasses, sage brush, yucca, and Mormon tea.</p> <hr/> <p>N. 0°01' W., bet. secs. 25 and 26.</p> <p>Over gently rolling land.</p>
26.55	<p>BIA Route 201, a graded road, 34 ft. wide, bears N. 40° E. and S. 40° W.</p>
40.00	<p>Point for the 1/4 sec. cor. of secs. 25 and 26.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in solid sandstone bedrock, with brass cap mkd.</p> <div style="text-align: center;"> <p>T 38 N R 9 E</p> <p>1/4</p> <p>S 26 S 25</p> <p>2013</p> </div> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p>

**Survey of the Subdivisional Lines,
T. 38 N., R. 9 E., Gila and Salt River Meridian, Arizona**

CHAINS	<p>Set a steel fence post nearby.</p>								
48.00	<p>Power line, bears N. 85° E. and S. 85° W.</p>								
63.86	<p>From this point, third order bench mark DISTRICT, monumented with a brass tablet, 3 1/2 ins. diam., firmly set, flush with the surface of sandstone bedrock, mkd. U.S. GEOLOGICAL SURVEY BENCHMARK 1954 ELEVATION ABOVE SEA FEET DISTRICT, bears E., 2.07 chs. dist.</p>								
80.00	<p>True point for the cor. of secs. 23, 24, 25, and 26, located on steep sandstone cliff face of Circular White Ridge, 120 ft. high, where it is impracticable to set a permanent monument.</p> <p>From this true point, the point selected for a witness cor. to the cor. of secs. 23, 24, 25, and 26, bears S. 15°00' W., 1.10 chs. dist.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 22 ins. in solid sandstone bedrock, with brass cap mkd.</p> <div style="text-align: center; margin: 10px 0;"> <table style="margin: auto; border-collapse: collapse;"> <tr> <td colspan="2" style="padding: 0 10px;">WC</td> </tr> <tr> <td style="padding: 0 5px;">T 38 N</td> <td style="padding: 0 5px;">R 9 E</td> </tr> <tr> <td style="padding: 0 5px; border-right: 1px solid black;">S 23</td> <td style="padding: 0 5px;">S 24</td> </tr> <tr> <td style="padding: 0 5px; border-right: 1px solid black;">S 26</td> <td style="padding: 0 5px;">S 25</td> </tr> </table>  </div> <p style="text-align: center; margin: 10px 0;">2013</p> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p> <p>Cor. is located 70 lks. W., from top of sandstone rim of Circular White Ridge, 120 ft. high, bears N. 80° E. and S. 60° W.</p> <p>Land, gently rolling and broken. Soil, sandy loam and sandstone rock outcrops. Timber, scattered juniper. Undergrowth, native grasses, rabbit brush, and Mormon tea.</p> <hr style="width: 60%; margin: 10px auto;"/> <p>From the cor. of secs. 19, 24, 25, and 30 on the E. bdy. of the Tp., monumented with a stainless steel post, 2 1/2 ins. diam., firmly set, projecting 4 ins. above ground, with brass cap mkd. T38N R9E R10E S24 S19 S25 S30 2013.</p> <p>West, bet. secs. 24 and 25.</p> <p>Over gently rolling land, on top of Circular White Ridge Mesa.</p>	WC		T 38 N	R 9 E	S 23	S 24	S 26	S 25
WC									
T 38 N	R 9 E								
S 23	S 24								
S 26	S 25								
40.00	<p>Point for the 1/4 sec. cor. of secs. 24 and 25.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p>								

Survey of the Subdivisional Lines,
T. 38 N., R. 9 E., Gila and Salt River Meridian, Arizona

CHAINS	
	T 38 N R 9 E S 24 1/4 ——— S 25 2013
	Deposit a magnet, in a white plastic case, at the base of the stainless steel post. Set a steel fence post nearby.
80.00	True point for the cor. of secs. 23, 24, 25, and 26. Land, gently rolling. Soil, sandy loam. Timber, juniper. Undergrowth, native grasses and yucca.
	N. 0°01' W., bet. secs. 23 and 24. Over gently rolling land, descending Circular White Ridge.
40.00	Point for the 1/4 sec. cor. of secs. 23 and 24. Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 25 ins. in the ground, with brass cap mkd.
	T 38 N R 9 E 1/4 S 23 S 24 2013
	Deposit a magnet, in a white plastic case, at the base of the stainless steel post. Set a steel fence post nearby. Cor. is located 50 lks. S. of wash, 7 ft. wide, 6 ft. deep, drains S. 60° W., and 2.65 chs. S. of trail road, bears N. 25° E. and S. 25° W.
45.10	Top of sandstone rim of Circular White Ridge mesa, 40 ft. high, bears N. 45° E. and S. 45° W.
80.00	Point for the cor. of secs. 13, 14, 23, and 24. Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.

**Survey of the Subdivisional Lines,
T. 38 N., R. 9 E., Gila and Salt River Meridian, Arizona**

CHAINS	
	T 38 N R 9 E S 14 S 13 S 23 S 24 2013
	Deposit a magnet, in a white plastic case, at the base of the stainless steel post. Set a steel fence post nearby. Land, gently rolling and broken. Soil, sandy loam. Timber, juniper. Undergrowth, native grasses, cholla grass, yucca, and Mormon tea.
	<hr/> From the cor. of secs. 13, 18, 19, and 24 on the E. bdy. of the Tp., monumented with a stainless steel post, 2 1/2 ins. diam., firmly set, projecting 5 ins. above ground, with brass cap mkd. T38N R9E R10E S13 S18 S24 S19 2013. West, bet. secs. 13 and 24. Over gently rolling land.
40.00	Point for the 1/4 sec. cor. of secs. 13 and 24. Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.
	T 38 N R 9 E S 13 1/4 ——— S 24 2013
	Deposit a magnet, in a white plastic case, at the base of the stainless steel post. Set a steel fence post nearby.
80.00	The cor. of secs. 13, 14, 23, and 24. Land, gently rolling and nearly level. Soil, sandy loam and sandstone bedrock. Timber, juniper. Undergrowth, native grasses, salt brush, yucca, cholla grass, sage brush, and Mormon tea.

Survey of the Subdivisional Lines,
T. 38 N., R. 9 E., Gila and Salt River Meridian, Arizona

CHAINS	
	N. 0°01' W., bet. secs. 13 and 14. Over nearly level land.
40.00	Point for the 1/4 sec. cor. of secs. 13 and 14. Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd. <div style="text-align: center;"> T 38 N R 9 E 1/4 S 14 S 13 </div> <div style="text-align: center;">2013</div> Deposit a magnet, in a white plastic case, at the base of the stainless steel post. Set a steel fence post nearby.
80.00	Point for the cor. of secs. 11, 12, 13, and 14. Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 25 ins. in the ground, with brass cap mkd. <div style="text-align: center;"> T 38 N R 9 E S 11 S 12 S 14 S 13 </div> <div style="text-align: center;">2013</div> Deposit a magnet, in a white plastic case, at the base of the stainless steel post. Set a steel fence post nearby. Land, nearly level and gently rolling. Soil, sandy loam. Timber, juniper. Undergrowth, native grasses, salt brush, cholla grass, sage brush, and Mormon tea.
40.00	<hr/> From the cor. of secs. 7, 12, 13, and 18 on the E. bdy. of the Tp., monumented with a stainless steel post, 2 1/2 ins. diam., firmly set, projecting 4 ins. above ground, with brass cap mkd. T38N R9E R10E S12 S7 S13 S18 2013. West, bet. secs. 12 and 13. Over nearly level land. Point for the 1/4 sec. cor. of secs. 12 and 13.

Survey of the Subdivisional Lines,
T. 38 N., R. 9 E., Gila and Salt River Meridian, Arizona

CHAINS	
	<p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T 38 N R 9 E S 12 1/4 ——— S 13</p> <p style="text-align: center;">2013</p> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p> <p>Set a steel fence post nearby.</p>
80.00	<p>The cor. of secs. 11, 12, 13, and 14.</p> <p>Land, nearly level. Soil, sandy loam. Timber, juniper. Undergrowth, native grasses, salt brush, cholla grass, yucca, and Mormon tea.</p> <hr/> <p>N. 0°01' W., bet. secs. 11 and 12.</p> <p>Over gently rolling land.</p>
29.20	<p>Barbed wire fence, 5 strand, bears S. 25° E. and N. 25° W.</p>
40.00	<p>Point for the 1/4 sec. cor. of secs. 11 and 12.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 25 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T 38 N R 9 E 1/4 S 11 S 12</p> <p style="text-align: center;">2013</p> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p> <p>Set a steel fence post nearby.</p>
80.00	<p>Point for the cor. of secs. 1, 2, 11, and 12.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 25 ins. in the ground, with brass cap mkd.</p>

Survey of the Subdivisional Lines,
T. 38 N., R. 9 E., Gila and Salt River Meridian, Arizona

CHAINS	
	T 38 N R 9 E S 2 S 1 S 11 S 12 2013
	<p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p> <p>Set a steel fence post nearby.</p> <p>Land, gently rolling. Soil, sandy loam. Timber, juniper. Undergrowth, native grasses, salt brush, sage brush, cholla grass, and Mormon tea.</p> <hr/> <p>From the cor. of secs. 1, 6, 7, and 12 on the E. bdy. of the Tp., monumented with a stainless steel post, 2 1/2 ins. diam., firmly set, projecting 3 ins. above ground, with brass cap mkd. T38N R9E R10E S1 S6 S12 S7 2013.</p> <p>West, bet. secs. 1 and 12.</p> <p>Over gently rolling land.</p>
40.00	<p>Point for the 1/4 sec. cor. of secs. 1 and 12.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p>
	T 38 N R 9 E S 1 1/4 ——— S 12 2013
80.00	<p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p> <p>Set a steel fence post nearby.</p> <p>Cor. is located 50 lks. W. of wash, 13 ft. wide, 1 ft. deep, drains N. 20° E.</p> <p>The cor. of secs. 1, 2, 11, and 12.</p> <p>Land, gently rolling and broken. Soil, sandy loam and scattered sandstone rock outcrops. Timber, juniper.</p>

**Survey of the Subdivisional Lines,
T. 38 N., R. 9 E., Gila and Salt River Meridian, Arizona**

CHAINS	
	Undergrowth, native grasses, rabbit brush, salt brush, sage brush, yucca, and Mormon tea.
	N. 0°01' W., bet. secs. 1 and 2.
	Over gently rolling land.
17.10	From this point, a fiberglass livestock water tank, 16 ft. diam., 8 ft. high, bears E., 5.87 chs. dist., and from this fiberglass tank, a galvanized water tank, 24 ft. diam., 8 ft. high, bears N. 5° W., 2.65 chs. dist.
40.00	Point for the 1/4 sec. cor. of secs. 1 and 2.
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.
	T 38 N R 9 E 1/4 S 2 S 1 2013
	Deposit a magnet, in a white plastic case, at the base of the stainless steel post.
	Set a steel fence post nearby.
80.00	The cor. of secs. 1, 2, 35, and 36, on the N. bdy. of the Tp., hereinbefore described.
	Land, gently rolling. Soil, sandy loam. Timber, juniper. Undergrowth, native grasses, yucca, and Mormon tea.
	From the cor. of secs. 2, 3, 34, and 35, on the S. bdy. of the Tp., monumented with a stainless steel post, 2 1/2 ins. diam., firmly set, projecting 5 ins. above ground, with brass cap mkd. T38N R9E S34 S35 S3 S2 T37N 2013.
	N. 0°01' W., bet. secs. 34 and 35.
	Over gently rolling land.
38.20	BIA Route 201, a graded road, 34 ft. wide, bears N. 50° E. and S. 50° W.
40.00	Point for the 1/4 sec. cor. of secs. 34 and 35.

Survey of the Subdivisional Lines,
T. 38 N., R. 9 E., Gila and Salt River Meridian, Arizona

CHAINS	
	<p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T 38 N R 9 E 1/4 S 34 S 35</p> <p style="text-align: center;">2013</p> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p> <p>Set a steel fence post nearby.</p>
80.00	<p>Point for the cor. of secs. 26, 27, 34, and 35.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 25 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T 38 N R 9 E S 27 S 26 S 34 S 35</p> <p style="text-align: center;">2013</p> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p> <p>Set a steel fence post nearby.</p> <p>Land, gently rolling and scattered sandstone rock outcrops. Soil, sandy loam. Timber, juniper. Undergrowth, native grasses, sage brush, rabbit brush, yucca, and Mormon tea.</p> <hr/> <p>From the cor. of secs. 25, 26, 35, and 36.</p> <p>West, bet. secs. 26 and 35.</p> <p>Over gently rolling land.</p>
14.50	<p>BIA Route 201, a graded road, 34 ft. wide, bears N. 25° E. and S. 25° W.</p>
40.00	<p>Point for the 1/4 sec. cor. of secs. 26 and 35.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in solid sandstone bedrock, with brass cap mkd.</p>

Survey of the Subdivisional Lines,
T. 38 N., R. 9 E., Gila and Salt River Meridian, Arizona

CHAINS	
	T 38 N R 9 E S 26 1/4 ——— S 35 2013
	Deposit a magnet, in a white plastic case, at the base of the stainless steel post. Set a steel fence post nearby. Cor. is located 1.30 chs. W. of trail road , bears S. 20° E. and N. 20° W.
50.30	Power line, bears N. 15° E. and S. 15° W.
80.00	The cor. of secs. 26, 27, 34, and 35. Land, gently rolling and sandstone rock outcrops. Soil, sandy loam and sandstone bedrock. Timber, juniper. Undergrowth, native grasses, sage brush, rabbit brush, and yucca.
	<hr/> N. 0°01' W., bet. secs. 26 and 27. Over gently rolling land.
40.00	Point for the 1/4 sec. cor. of secs. 26 and 27. Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 25 ins. in the ground, with brass cap mkd.
	T 38 N R 9 E 1/4 S 27 S 26 2013
80.00	Deposit a magnet, in a white plastic case, at the base of the stainless steel post. Set a steel fence post nearby. Point for the cor. of secs. 22, 23, 26, and 27. Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 25 ins. in the ground, with brass cap mkd.

Survey of the Subdivisional Lines,
T. 38 N., R. 9 E., Gila and Salt River Meridian, Arizona

CHAINS	
	<p style="text-align: center;">T 38 N R 9 E S 22 S 23 S 27 S 26</p> <p style="text-align: center;">2013</p> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p> <p>Set a steel fence post nearby.</p> <p>Land, gently rolling. Soil, sandy loam. Timber, scattered juniper. Undergrowth, native grasses, yucca, and sage brush.</p> <hr/> <p>From the true point for the cor. of secs. 23, 24, 25, and 26.</p> <p>West, bet. secs. 23 and 26.</p> <p>Over gently rolling land.</p>
40.00	<p>Point for the 1/4 sec. cor. of secs. 23 and 26.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 25 ins. in the ground, with brass cap mkd.</p>
	<p style="text-align: center;">T 38 N R 9 E S 23 1/4 ——— S 26</p> <p style="text-align: center;">2013</p> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p> <p>Set a steel fence post nearby.</p> <p>Cor. is located 2.55 chs. W. of bladed dirt road, 15 ft. wide, bears S. 40° E. and N. 40° W.</p>
80.00	<p>The cor. of secs. 22, 23, 26, and 27.</p> <p>Land, gently rolling. Soil, sandy loam. Timber, scattered juniper. Undergrowth, native grasses, sage brush, rabbit brush, and Mormon tea.</p> <hr/>

**Survey of the Subdivisional Lines,
T. 38 N., R. 9 E., Gila and Salt River Meridian, Arizona**

CHAINS

N. 0°01' W., bet. secs. 22 and 23.

Over gently rolling land.

40.00

True point for the 1/4 sec. cor. of secs. 22 and 23, located on steep sandstone cliff face of Circular White Ridge, 120 ft. high, where it is impracticable to set a permanent monument.

From this true point, the point selected for a witness cor. to the 1/4 sec. cor. of secs. 22 and 23, bears N. 60°00' E., 20 lks. dist.

Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in solid sandstone bedrock, with brass cap mkd.

WC
T 38 N R 9 E
1/4
S 22 | S 23
↙
2013

Deposit a magnet, in a white plastic case, at the base of the stainless steel post.

Set a steel fence post nearby.

Cor. is located on top of sandstone rim of Circular White Ridge, 4 lks. E. of edge, 120 ft. high, bears S. 30° E. and N. 30° W.

80.00

Point for the cor. of secs. 14, 15, 22, and 23.

Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 25 ins. in the ground, with brass cap mkd.

T 38 N R 9 E
S 15 | S 14
S 22 | S 23

2013

Deposit a magnet, in a white plastic case, at the base of the stainless steel post.

Set a steel fence post nearby.

Cor. is located 45 lks. W. of trail road, bears N. 35° E. and S. 35° W.

Land, gently rolling and broken.

Soil, sandy loam.

Timber, juniper.

Undergrowth, native grasses, yucca, rabbit brush, sage brush, and Mormon tea.

Survey of the Subdivisional Lines,
T. 38 N., R. 9 E., Gila and Salt River Meridian, Arizona

CHAINS	
	<p>From the cor. of secs. 13, 14, 23, and 24.</p> <p>West, bet. secs. 14 and 23.</p> <p>Over nearly level land.</p>
40.00	<p>Point for the 1/4 sec. cor. of secs. 14 and 23.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 25 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T 38 N R 9 E S 14 1/4 ——— S 23</p> <p style="text-align: center;">2013</p> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p> <p>Set a steel fence post nearby.</p>
80.00	<p>The cor. of secs. 14, 15, 22, and 23.</p> <p>Land, gently rolling. Soil, sandy loam. Timber, juniper. Undergrowth, native grasses, yucca, sage brush, and Mormon tea.</p> <hr/> <p>N. 0°01' W., bet. secs. 14 and 15.</p> <p>Over gently rolling land.</p>
40.00	<p>Point for the 1/4 sec. cor. of secs. 14 and 15.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T 38 N R 9 E 1/4 S 15 S 14</p> <p style="text-align: center;">2013</p> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p> <p>Set a steel fence post nearby.</p>
80.00	<p>Point for the cor. of secs. 10, 11, 14, and 15.</p>

Survey of the Subdivisional Lines,
T. 38 N., R. 9 E., Gila and Salt River Meridian, Arizona

CHAINS	
	<p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T 38 N R 9 E S 10 S 11 S 15 S 14</p> <p style="text-align: center;">2013</p> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p> <p>Set a steel fence post nearby.</p> <p>Land, gently rolling. Soil, sandy loam. Timber, sparse juniper. Undergrowth, native grasses, yucca, and sage brush.</p> <hr/> <p>From the cor. of secs. 11, 12, 13, and 14.</p> <p>West, bet. secs. 11 and 14.</p> <p>Over gently rolling land.</p>
40.00	<p>Point for the 1/4 sec. cor. of secs. 11 and 14.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T 38 N R 9 E S 11 1/4 ——— S 14</p> <p style="text-align: center;">2013</p> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p> <p>Set a steel fence post nearby.</p>
80.00	<p>The cor. of secs. 10, 11, 14, and 15.</p> <p>Land, gently rolling. Soil, sandy loam. Timber, scattered juniper. Undergrowth, native grasses, yucca, and sage brush.</p> <hr/>

Survey of the Subdivisional Lines,
T. 38 N., R. 9 E., Gila and Salt River Meridian, Arizona

CHAINS	
	N. 0°01' W., bet. secs. 10 and 11. Over gently rolling land.
40.00	Point for the 1/4 sec. cor. of secs. 10 and 11. Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 22 ins. in the ground, with brass cap mkd. <div style="text-align: center;"> T 38 N R 9 E 1/4 S 10 S 11 </div> <div style="text-align: center;">2013</div> Deposit a magnet, in a white plastic case, at the base of the stainless steel post. Set a steel fence post nearby.
80.00	Point for the cor. of secs. 2, 3, 10, and 11. Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 25 ins. in the ground, with brass cap mkd. <div style="text-align: center;"> T 38 N R 9 E S 3 S 2 S 10 S 11 </div> <div style="text-align: center;">2013</div> Deposit a magnet, in a white plastic case, at the base of the stainless steel post. Set a steel fence post nearby. Land, gently rolling. Soil, sandy loam. Timber, juniper. Undergrowth, native grasses, sage brush, and Mormon tea.
40.00	<hr/> From the cor. of secs. 1, 2, 11, and 12. West, bet. secs. 2 and 11. Over gently rolling land. Point for the 1/4 sec. cor. of secs. 2 and 11. Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 25 ins. in the ground, with brass cap mkd.

Survey of the Subdivisional Lines,
T. 38 N., R. 9 E., Gila and Salt River Meridian, Arizona

CHAINS	
	T 38 N R 9 E S 2 1/4 ——— S 11 2013
	Deposit a magnet, in a white plastic case, at the base of the stainless steel post. Set a steel fence post nearby.
80.00	The cor. of secs. 2, 3, 10, and 11. Land, gently rolling. Soil, sandy loam. Timber, juniper. Undergrowth, native grasses, yucca, sage brush, and Mormon tea.
	N. 0°01' W., bet. secs. 2 and 3. Over gently rolling land.
40.00	Point for the 1/4 sec. cor. of secs. 2 and 3. Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with brass cap mkd.
	T 38 N R 9 E 1/4 S 3 S 2 2013
	Deposit a magnet, in a white plastic case, at the base of the stainless steel post. Set a steel fence post nearby.
64.85	Barbed wire fence, 5 strand, bears S. 30° E. and N. 30° W.
80.00	The cor. of secs. 2, 3, 34, and 35, on the N. bdy. of the Tp., hereinbefore described. Land, gently rolling. Soil, sandy loam and sandstone bedrock. Timber, juniper. Undergrowth, native grasses, rabbit brush, sage brush, and Mormon tea.

Survey of the Subdivisional Lines,
T. 38 N., R. 9 E., Gila and Salt River Meridian, Arizona

CHAINS	
	<p>From the cor. of secs. 3, 4, 33, and 34, on the S. bdy. of the Tp., monumented with a stainless steel post, 2 1/2 ins. diam., firmly set, projecting 4 ins. above ground, with brass cap mkd. T38N R9E S33 S34 S4 S3 T37N 2013.</p> <p>N. 0°02' W., bet. secs. 33 and 34.</p> <p>Over gently rolling land.</p>
11.55	High voltage transmission line, bears N. 10° E. and S. 10° W.
26.45	High voltage transmission line, bears N. 10° E. and S. 10° W.
40.00	<p>Point for the 1/4 sec. cor. of secs. 33 and 34.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in solid sandstone bedrock, with brass cap mkd.</p> <div style="text-align: center;"> <p>T 38 N R 9 E 1/4 S 33 S 34</p> <p>2013</p> </div> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p> <p>Set a steel fence post nearby.</p>
80.00	<p>Point for the cor. of secs. 27, 28, 33, and 34.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center;"> <p>T 38 N R 9 E S 28 S 27 S 33 S 34</p> <p>2013</p> </div> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p> <p>Set a steel fence post nearby.</p> <p>Land, gently rolling and rolling Soil, sandy loam and sandstone bedrock. Timber, scattered juniper. Undergrowth, native grasses and sage brush.</p> <hr/>

Survey of the Subdivisional Lines,
T. 38 N., R. 9 E., Gila and Salt River Meridian, Arizona

CHAINS	
	<p>From the cor. of secs. 26, 27, 34, and 35.</p> <p>West, bet. secs. 27 and 34.</p> <p>Over gently rolling land.</p>
40.00	<p>Point for the 1/4 sec. cor. of secs. 27 and 34.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 25 ins. in solid sandstone bedrock, with brass cap mkd.</p> <p style="text-align: center;">T 38 N R 9 E S 27 1/4 ——— S 34</p> <p style="text-align: center;">2013</p> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p> <p>Set a steel fence post nearby.</p>
70.85	High voltage transmission line, bears N. 10° E. and S. 10° W.
72.85	High voltage transmission line, bears N. 10° E. and S. 10° W.
80.00	<p>The cor. of secs. 27, 28, 33, and 34.</p> <p>Land, gently rolling and sandstone rock outcrops. Soil, sandy loam and sandstone bedrock. Timber, scattered juniper. Undergrowth, native grasses and yucca.</p> <hr/> <p>N. 0°02' W., bet. secs. 27 and 28.</p> <p>Over gently rolling land.</p>
40.00	<p>Point for the 1/4 sec. cor. of secs. 27 and 28.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T 38 N R 9 E 1/4 S 28 S 27</p> <p style="text-align: center;">2013</p> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p>


Survey of the Subdivisional Lines,
T. 38 N., R. 9 E., Gila and Salt River Meridian, Arizona

CHAINS									
80.00	<p>Set a steel fence post nearby.</p> <p>Point for the cor. of secs. 21, 22, 27, and 28.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in solid sandstone bedrock, with brass cap mkd.</p> <div style="text-align: center;"> <table style="margin: auto;"> <tr><td>T 38 N</td><td>R 9 E</td></tr> <tr><td>S 21</td><td>S 22</td></tr> <tr><td>S 28</td><td>S 27</td></tr> </table> <p>2013</p> </div> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p> <p>Set a steel fence post nearby.</p> <p>Land, rolling and sandstone rock outcrops. Soil, sandy loam and sandstone bedrock. Timber, juniper. Undergrowth, native grasses, yucca, and sage brush.</p> <hr/> <p>From the cor. of secs. 22, 23, 26, and 27.</p> <p>West, bet. secs. 22 and 27.</p> <p>Over gently rolling land.</p>	T 38 N	R 9 E	S 21	S 22	S 28	S 27		
T 38 N	R 9 E								
S 21	S 22								
S 28	S 27								
40.00	<p>Point for the 1/4 sec. cor. of secs. 22 and 27.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center;"> <table style="margin: auto;"> <tr><td>T 38 N</td><td>R 9 E</td></tr> <tr><td></td><td>S 22</td></tr> <tr><td>1/4</td><td>—</td></tr> <tr><td></td><td>S 27</td></tr> </table> <p>2013</p> </div> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p> <p>Set a steel fence post nearby.</p> <p>Cor. is located 1.30 chs. E. of trail road , bears S. 35° E. and N. 35° W.</p>	T 38 N	R 9 E		S 22	1/4	—		S 27
T 38 N	R 9 E								
	S 22								
1/4	—								
	S 27								
60.20	<p>High voltage transmission line, bears N. 10° E. and S. 10° W.</p>								
62.20	<p>High voltage transmission line, bears N. 10° E. and S. 10° W.</p>								

Survey of the Subdivisional Lines,
T. 38 N., R. 9 E., Gila and Salt River Meridian, Arizona

CHAINS	
80.00	<p>The cor. of secs. 21, 22, 27, and 28.</p> <p>Land, gently rolling. Soil, sandy loam. Timber, juniper. Undergrowth, native grasses and sage brush.</p> <hr/> <p>N. 0°02' W., bet. secs. 21 and 22.</p> <p>Over gently rolling land.</p>
40.00	<p>Point for the 1/4 sec. cor. of secs. 21 and 22.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T 38 N R 9 E 1/4 S 21 S 22</p> <p style="text-align: center;">2013</p> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p> <p>Set a steel fence post nearby.</p>
80.00	<p>Point for the cor. of secs. 15, 16, 21, and 22.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T 38 N R 9 E S 16 S 15 S 21 S 22</p> <p style="text-align: center;">2013</p> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p> <p>Set a steel fence post nearby.</p> <p>Land, gently rolling and rolling. Soil, sandy loam. Timber, juniper. Undergrowth, native grasses and sage brush.</p> <hr/> <p>From the cor. of secs. 14, 15, 22, and 23.</p> <p>West, bet. secs. 15 and 22.</p>

**Survey of the Subdivisional Lines,
T. 38 N., R. 9 E., Gila and Salt River Meridian, Arizona**

CHAINS	
	Over gently rolling land, on top of Circular White Ridge.
31.10	Top of sandstone rim of Circular White Ridge, 40 ft. high, bears N. 25° E. and S. 40° W.
40.00	<p>True point for the 1/4 sec. cor. of secs. 15 and 22., located on steep slope of sandstone boulder, 9 x 7 x 4 ft., where it is impracticable to set a permanent monument.</p> <p>From this true point, the point selected for a witness cor. to the 1/4 sec. cor. of secs. 15 and 22., bears S. 20°01' W., 55 lks. dist.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center;">  <p>WC ↗ T 38 N R 9 E S 15 1/4 ——— S 22</p> </div> <p>2013</p> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p> <p>Set a steel fence post nearby.</p> <p>Cor. is located 85 lks. W., from the top of sandstone rim of Circular White Ridge, 50 ft. high, bears N. 5° E. and S. 5° W.</p>
49.55	High voltage transmission line, bears N. 10° E. and S. 10° W.
51.55	High voltage transmission line, bears N. 10° E. and S. 10° W.
80.00	<p>The cor. of secs. 15, 16, 21, and 22.</p> <p>Land, gently rolling and broken. Soil, sandy loam and sandstone bedrock. Timber, scarce juniper. Undergrowth, native grasses and Mormon tea.</p> <hr/> <p>N. 0°02' W., bet. secs. 15 and 16.</p> <p>Over gently rolling land.</p>
40.00	<p>Point for the 1/4 sec. cor. of secs. 15 and 16.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p>

Survey of the Subdivisional Lines,
T. 38 N., R. 9 E., Gila and Salt River Meridian, Arizona

CHAINS	
	T 38 N R 9 E 1/4 S 16 S 15 2013
	Deposit a magnet, in a white plastic case, at the base of the stainless steel post. Set a steel fence post nearby.
49.05	Top of sandstone rim of Circular White Ridge, 50 ft. high, bears N. 75° E. and S. 60° W.
80.00	Point for the cor. of secs. 9, 10, 15, and 16. Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.
	T 38 N R 9 E S 9 S 10 S 16 S 15 2013
	Deposit a magnet, in a white plastic case, at the base of the stainless steel post. Set a steel fence post nearby. Land, gently rolling and broken Soil, sandy loam and sandstone bedrock. Timber, scattered juniper. Undergrowth, native grasses, sage brush, yucca, and Mormon tea.
	<hr/> From the cor. of secs. 10, 11, 14, and 15. West, bet. secs. 10 and 15. Over gently rolling land.
40.00	Point for the 1/4 sec. cor. of secs. 10 and 15. Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.
	T 38 N R 9 E S 10 1/4 ——— S 15 2013

Survey of the Subdivisional Lines,
T. 38 N., R. 9 E., Gila and Salt River Meridian, Arizona

CHAINS	
	<p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p> <p>Set a steel fence post nearby.</p> <p>Cor. is located 35 lks. W. and 1.60 chs. E. of high voltage transmission lines, both lines are parallel, and bears N. 5° E. and S. 5° W., and 1.15 chs. E. of trail road, bears N. 10° E. and S. 10° W.</p>
80.00	<p>The cor. of secs. 9, 10, 15, and 16.</p> <p>Land, gently rolling. Soil, sandy loam. Timber, scarce juniper. Undergrowth, native grasses, yucca, and sage brush.</p> <hr/> <p>N. 0°02' W., bet. secs. 9 and 10.</p> <p>Over gently rolling land.</p>
40.00	<p>Point for the 1/4 sec. cor. of secs. 9 and 10.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center;"> <p>T 38 N R 9 E</p> <p>1/4</p> <p>S 9 S 10</p> <p>2013</p> </div>
80.00	<p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p> <p>Set a steel fence post nearby.</p> <p>Point for the cor. of secs. 3, 4, 9, and 10.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center;"> <p>T 38 N R 9 E</p> <p>S 4 S 3</p> <hr style="width: 50%; margin: 0 auto;"/> <p>S 9 S 10</p> <p>2013</p> </div> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p> <p>Set a steel fence post nearby.</p>

Survey of the Subdivisional Lines,
T. 38 N., R. 9 E., Gila and Salt River Meridian, Arizona

CHAINS	
	<p>Land, gently rolling. Soil, sandy loam. Timber, scarce juniper. Undergrowth, native grasses, yucca, cholla grass, and sage brush.</p> <hr/> <p>From the cor. of secs. 2, 3, 10, and 11.</p> <p>West, bet. secs. 3 and 10.</p> <p>Over gently rolling land.</p>
33.95	High voltage transmission line, bears N. 5° E. and S. 5° W.
35.90	High voltage transmission line, bears N. 5° E. and S. 5° W.
40.00	Point for the 1/4 sec. cor. of secs. 3 and 10.
	<p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T 38 N R 9 E S 3 1/4 ——— S 10</p> <p style="text-align: center;">2013</p> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p> <p>Set a steel fence post nearby.</p>
80.00	<p>The cor. of secs. 3, 4, 9, and 10.</p> <p>Land, gently rolling. Soil, sandy loam. Timber, scarce juniper. Undergrowth, native grasses, yucca, sage brush, and Mormon tea.</p> <hr/> <p>N. 0°02' W., bet. secs. 3 and 4.</p> <p>Over gently rolling land.</p>
40.00	<p>Point for the 1/4 sec. cor. of secs. 3 and 4.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 22 ins. in the ground, with brass cap mkd.</p>

Survey of the Subdivisional Lines,
T. 38 N., R. 9 E., Gila and Salt River Meridian, Arizona

CHAINS	
	T 38 N R 9 E 1/4 S 4 S 3 2013
	Deposit a magnet, in a white plastic case, at the base of the stainless steel post. Set a steel fence post nearby.
43.70	Trail road, bears N. 55° E. and S. 55° W.
80.00	The cor. of secs. 3, 4, 33, and 34, on the N. bdy. of the Tp., hereinbefore described. Land, gently rolling. Soil, sandy loam and sandstone bedrock. Timber, juniper. Undergrowth, native grasses, yucca, cholla grass, and Mormon tea.
	<hr/> From the cor. of secs. 4, 5, 32, and 33, on the S. bdy. of the Tp., monumented with a stainless steel post, 2 1/2 ins. diam., firmly set, 4 ins. below ground, with brass cap mkd. T38N R9E S32 S33 S5 S4 T37N 2013. N. 0°03' W., bet. secs. 32 and 33. Over gently rolling land.
7.50	From this point, a fiberglass livestock water tank, 16 ft. diam., 8 ft. high, bears E., 3.53 chs. dist.
40.00	Point for the 1/4 sec. cor. of secs. 32 and 33. Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 25 ins. in the ground, with brass cap mkd.
	T 38 N R 9 E 1/4 S 32 S 33 2013
	Deposit a magnet, in a white plastic case, at the base of the stainless steel post. Set a steel fence post nearby.
80.00	Point for the cor. of secs. 28, 29, 32, and 33.

**Survey of the Subdivisional Lines,
T. 38 N., R. 9 E., Gila and Salt River Meridian, Arizona**

CHAINS	
	<p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 25 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T 38 N R 9 E S 29 S 28 ----- S 32 S 33</p> <p style="text-align: center;">2013</p> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p> <p>Set a steel fence post nearby.</p> <p>Land, gently rolling. Soil, sandy loam and sandstone rock outcrops. Timber, scattered juniper. Undergrowth, native grasses, yucca, and Mormon tea.</p> <hr/> <p>From the cor. of secs. 27, 28, 33, and 34.</p> <p>West, bet. secs. 28 and 33.</p> <p>Over gently rolling land.</p>
40.00	<p>Point for the 1/4 sec. cor. of secs. 28 and 33.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T 38 N R 9 E S 28 1/4 ——— S 33</p> <p style="text-align: center;">2013</p> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p> <p>Set a steel fence post nearby.</p>
56.80	<p>E. right-of-way fence of BIA Route 20, barbed wire, 4 strand, parallels highway.</p>
58.65	<p>BIA Route 20, an asphalt surfaced road, 33 ft. wide, bears S. 10° E. and N. 10° W.</p>
59.70	<p>W. right-of-way fence of BIA Route 20, barbed wire, 4 strand, parallels highway.</p>
59.95	<p>Underground water line, bears S. 10° E. and N. 10° W.</p>

Survey of the Subdivisional Lines,
T. 38 N., R. 9 E., Gila and Salt River Meridian, Arizona

CHAINS	
66.00	Power line, bears S. 5° E. and N. 5° W.
80.00	The cor. of secs. 28, 29, 32, and 33. Land, gently rolling. Soil, sandy loam. Timber, scarce juniper. Undergrowth, native grasses, sage brush, and Mormon tea.
	<hr/>
	N. 0°03' W., bet. secs. 28 and 29. Over rolling land.
37.45	Underground water line, bears N. 85° E. and S. 85° W.
40.00	Point for the 1/4 sec. cor. of secs. 28 and 29. Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd. <div style="text-align: center;"> T 38 N R 9 E 1/4 S 29 S 28 2013 </div>
	Deposit a magnet, in a white plastic case, at the base of the stainless steel post. Set a steel fence post nearby.
80.00	Point for the cor. of secs. 20, 21, 28, and 29. Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 25 ins. in the ground, with brass cap mkd. <div style="text-align: center;"> T 38 N R 9 E S 20 S 21 S 29 S 28 2013 </div>
	Deposit a magnet, in a white plastic case, at the base of the stainless steel post. Set a steel fence post nearby. Land, rolling with sandstone rock outcrops. Soil, sandy loam and sandstone bedrock. Timber, juniper. Undergrowth, native grasses, sage brush, rabbit brush, yucca, and Mormon tea.
	<hr/>

Survey of the Subdivisional Lines,
T. 38 N., R. 9 E., Gila and Salt River Meridian, Arizona

CHAINS	
	<p>From the cor. of secs. 21, 22, 27, and 28.</p> <p>West, bet. secs. 21 and 28.</p> <p>Over gently rolling land.</p>
40.00	<p>Point for the 1/4 sec. cor. of secs. 21 and 28.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 25 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T 38 N R 9 E S 21 1/4 ——— S 28</p> <p style="text-align: center;">2013</p> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p> <p>Set a steel fence post nearby.</p>
71.40	Power line, bears S. 5° E. and N. 5° W.
71.85	E. right-of-way fence of BIA Route 20, barbed wire, 4 strand, parallels highway.
73.65	BIA Route 20, an asphalt surfaced road, 33 ft. wide, bears S. 10° E. and N. 10° W.
74.80	W. right-of-way fence of BIA Route 20, barbed wire, 4 strand, parallels highway.
80.00	<p>The cor. of secs. 20, 21, 28, and 29.</p> <p>Land, gently rolling and scattered sandstone rock outcrops. Soil, sandy loam and sandstone bedrock. Timber, juniper. Undergrowth, native grasses, sage brush, and Mormon tea.</p> <hr/> <p>N. 0°03' W., bet. secs. 20 and 21.</p> <p>Over gently rolling land.</p>
40.00	<p>Point for the 1/4 sec. cor. of secs. 20 and 21.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 25 ins. in the ground, with brass cap mkd.</p>

Survey of the Subdivisional Lines,
T. 38 N., R. 9 E., Gila and Salt River Meridian, Arizona

CHAINS

T 38 N R 9 E
1/4
S 20 | S 21

2013

from which

A stainless steel post, 28 ins. long, 2 1/2 ins. diam., set 26 ins. in the ground for a reference monument, bears N. 88°59' E., 180.0 ft. dist. with brass cap mkd. RM T38N R9E 180.0 FT TO COR 1/4 S21 2013 and an arrow pointing to the cor. Deposit a magnet, in a white plastic case, at the base of the stainless steel post and set a steel fence post nearby.

A stainless steel post, 28 ins. long, 2 1/2 ins. diam., set 24 ins. in the ground for a reference monument, bears S. 88°59' W., 50.0 ft. dist. with brass cap mkd. RM T38N R9E 50.0 FT TO COR 1/4 S20 2013 and an arrow pointing to the cor. Deposit a magnet, in a white plastic case, at the base of the stainless steel post and set a steel fence post nearby.

Deposit a magnet, in a white plastic case, at the base of the stainless steel post.

Set a steel fence post nearby.

Cor. is located 85 lks. W. of BIA Route 20, an asphalt surfaced road, 33 ft. wide, bears N. and S., and 65 lks. E. of the W. right-of-way fence of BIA Route 20, barbed wire, 4 strand, parallels highway.

67.70 BIA Route 20, an asphalt surfaced road, 33 ft. wide, bears S. 5° E. and N. 5° W.

77.20 E. right-of-way fence of BIA Route 20, barbed wire, 4 strand, S. 5° E. and N. 5° W.

80.00 Point for the cor. of secs. 16, 17, 20, and 21.

Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.

T 38 N R 9 E
S 17 | S 16
S 20 | S 21

2013

Deposit a magnet, in a white plastic case, at the base of the stainless steel post.

Survey of the Subdivisional Lines,
T. 38 N., R. 9 E., Gila and Salt River Meridian, Arizona

CHAINS	
	<p>Set a steel fence post nearby.</p> <p>Cor. is located 65 lks. E. of the E. right-of-way fence of BIA Route 20, barbed wire, 4 strand, bears S. 10° E. and N. 10° W., and 2.25 chs. E. of BIA Route 20, an asphalt surfaced road, 33 ft. wide, bears S. 10° E. and N. 10° W.</p> <p>Land, gently rolling. Soil, sandy loam. Timber, scattered juniper. Undergrowth, native grasses, sage brush, and Mormon tea.</p> <hr/> <p>From the cor. of secs. 15, 16, 21, and 22.</p> <p>West, bet. secs. 16 and 21.</p> <p>Over gently rolling land.</p>
40.00	<p>Point for the 1/4 sec. cor. of secs. 16 and 21.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 25 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T 38 N R 9 E S 16 1/4 ——— S 21</p> <p style="text-align: center;">2013</p> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p> <p>Set a steel fence post nearby.</p>
76.75	<p>Power line, bears S. 5° E. and N. 5° W.</p>
80.00	<p>The cor. of secs. 16, 17, 20, and 21.</p> <p>Land, gently rolling. Soil, sandy loam. Timber, scattered juniper. Undergrowth, native grasses, yucca, sage brush, and Mormon tea.</p> <hr/> <p>N. 0°03' W., bet. secs. 16 and 17.</p> <p>Over gently rolling land.</p>
40.00	<p>Point for the 1/4 sec. cor. of secs. 16 and 17.</p>

**Survey of the Subdivisional Lines,
T. 38 N., R. 9 E., Gila and Salt River Meridian, Arizona**

CHAINS	
	<p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T 38 N R 9 E 1/4 S 17 S 16</p> <p style="text-align: center;">2013</p> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p> <p>Set a steel fence post nearby.</p>
48.30	Power line, bears S. 5° E. and N. 5° W.
80.00	Point for the cor. of secs. 8, 9, 16 and 17.
	<p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T 38 N R 9 E S 8 S 9 S 17 S 16</p> <p style="text-align: center;">2013</p> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p> <p>Set a steel fence post nearby.</p> <p>Cor. is located 2.10 chs. E. of power line, bears S. 5° E. and N. 5° W.</p> <p>Land, gently rolling. Soil, sandy loam. Timber, scattered juniper. Undergrowth, native grasses, sage brush, and Mormon tea.</p> <hr/> <p>From the cor. of secs. 9, 10, 15, and 16.</p> <p>West, bet. secs. 9 and 16.</p> <p>Over gently rolling land.</p>
40.00	Point for the 1/4 sec. cor. of secs. 9 and 16.
	<p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p>

Survey of the Subdivisional Lines,
T. 38 N., R. 9 E., Gila and Salt River Meridian, Arizona

CHAINS	
	T 38 N R 9 E S 9 1/4 ——— S 16 2013
	Deposit a magnet, in a white plastic case, at the base of the stainless steel post. Set a steel fence post nearby.
63.10	Top of Dead Monkey Ridge, a sandstone ridge, 70 ft. high, bears N. 45° E. and S. 40° W.
80.00	The cor. of secs. 8, 9, 16, and 17. Land, gently rolling. Soil, sandy loam. Timber, juniper. Undergrowth, native grasses and yucca.
	N. 0°03' W., bet. secs. 8 and 9. Over gently rolling land.
40.00	Point for the 1/4 sec. cor. of secs. 8 and 9. Set a magnetic nail, 1 in. long, 1/4 in. diam., with 7/16 in. nail head, flush with the surface of the asphalt road. from which <ul style="list-style-type: none"> A stainless steel post, 28 ins. long, 2 1/2 ins. diam., set 24 ins. in the ground for a reference monument, bears S. 80°00' E., 105.0 ft. dist. with brass cap mkd. RM T38N R9E 105.0 FT TO COR 1/4 S9 2013 and an arrow pointing to the cor. Deposit a magnet, in a white plastic case, at the base of the stainless steel post and set a steel fence post nearby. A stainless steel post, 28 ins. long, 2 1/2 ins. diam., set 25 ins. in the ground for a reference monument, bears N. 80°00' W., 100.0 ft. dist. with brass cap mkd. RM T38N R9E 100.0 FT TO COR 1/4 S8 2013 and an arrow pointing to the cor. Deposit a magnet, in a white plastic case, at the base of the stainless steel post and set a steel fence post nearby.

**Survey of the Subdivisional Lines,
T. 38 N., R. 9 E., Gila and Salt River Meridian, Arizona**

CHAINS									
	<p>The 1/4 sec. cor. of secs. 8 and 9, is located in BIA Route 20, an asphalt surfaced road, 33 ft. wide, bears N. 10° E. and S. 10° W., and 1.60 chs. W. of the E. right-of-way fence of BIA Route 20, barbed wire, 4 strand, parallels highway, and 1.50 chs. E. of the W. right-of-way fence of BIA Route 20, barbed wire, 4 strand, parallels highway.</p>								
53.25	Power line, bears N. 65° E. and S. 65° W.								
65.75	Underground water line, bears N. 25° E. and S. 25° W.								
80.00	<p>Point for the cor. of secs. 4, 5, 8, and 9.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 25 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center;"> <table style="margin: auto;"> <tr> <td>T 38 N</td> <td>R 9 E</td> </tr> <tr> <td>S 5</td> <td>S 4</td> </tr> <tr> <td>S 8</td> <td>S 9</td> </tr> </table> <p>2013</p> </div> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p> <p>Set a steel fence post nearby.</p> <p>Land, gently rolling. Soil, sandy loam. Timber, scarce juniper. Undergrowth, native grasses, sage brush, and yucca.</p> <hr/> <p>From the cor. of secs. 3, 4, 9, and 10.</p> <p>West, bet. secs. 4 and 9.</p> <p>Over gently rolling land.</p>	T 38 N	R 9 E	S 5	S 4	S 8	S 9		
T 38 N	R 9 E								
S 5	S 4								
S 8	S 9								
40.00	<p>Point for the 1/4 sec. cor. of secs. 4 and 9.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center;"> <table style="margin: auto;"> <tr> <td>T 38 N</td> <td>R 9 E</td> </tr> <tr> <td></td> <td>S 4</td> </tr> <tr> <td>1/4</td> <td>—</td> </tr> <tr> <td></td> <td>S 9</td> </tr> </table> <p>2013</p> </div> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p>	T 38 N	R 9 E		S 4	1/4	—		S 9
T 38 N	R 9 E								
	S 4								
1/4	—								
	S 9								

**Survey of the Subdivisional Lines,
T. 38 N., R. 9 E., Gila and Salt River Meridian, Arizona**

CHAINS	
	Set a steel fence post nearby.
64.45	Underground water line, bears N. and S.
69.40	Power line, bears N. 10° E. and S. 10° W.
71.05	E. right-of-way fence of BIA Route 20, barbed wire, 4 strand, parallels highway.
72.60	BIA Route 20, an asphalt surfaced road, 33 ft. wide, bears N. 5° E. and S. 5° W.
74.15	W. right-of-way fence of BIA Route 20, barbed wire, 4 strand, parallels highway.
76.15	Underground water line, bears N. 5° E. and S. 5° W.
80.00	The cor. of secs. 4, 5, 8, and 9.
	Land, gently rolling. Soil, sandy loam. No timber. Undergrowth, native grasses, yucca, sage brush, and Mormon tea.
	<hr/>
	N. 0°03' W., bet. secs. 4 and 5.
	Over gently rolling land.
40.00	Point for the 1/4 sec. cor. of secs. 4 and 5.
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.
	T 38 N R 9 E 1/4 S 5 S 4
	2013
	Deposit a magnet, in a white plastic case, at the base of the stainless steel post.
	Set a steel fence post nearby.
	Cor. is located 1.85 chs. W. and 2.60 chs. N. of trail road , bears N. 35° E. and S. 35° W.
80.00	The cor. of secs. 4, 5, 32, and 33, on the N. bdy. of the Tp., hereinbefore described.

**Survey of the Subdivisional Lines,
T. 38 N., R. 9 E., Gila and Salt River Meridian, Arizona**

CHAINS	
	<p>Land, gently rolling. Soil, sandy loam. Timber, scarce juniper. Undergrowth, native grasses, cholla grass, and sage brush.</p> <hr/> <p>From the cor. of secs. 5, 6, 31, and 32, on the S. bdy. of the Tp., monumented with a stainless steel post, 2 1/2 ins. diam., firmly set, projecting 4 ins. above ground, with brass cap mkd. T38N R9E S31 S32 S6 S5 T37N 2013.</p> <p>N. 0°03' W., bet. secs. 31 and 32.</p> <p>Over gently rolling land.</p>
25.85	High voltage transmission line, bears N. and S.
40.00	<p>Point for the 1/4 sec. cor. of secs. 31 and 32.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T 38 N R 9 E 1/4 S 31 S 32 2013</p> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p> <p>Set a steel fence post nearby.</p>
80.00	<p>Point for the cor. of secs. 29, 30, 31, and 32.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T 38 N R 9 E S 30 S 29 S 31 S 32 2013</p> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p> <p>Set a steel fence post nearby.</p> <p>Cor. is located 1.75 chs. W. of high voltage transmission line, bears N. and S.</p>

Survey of the Subdivisional Lines,
T. 38 N., R. 9 E., Gila and Salt River Meridian, Arizona

CHAINS	
	<p>Land, gently rolling. Soil, sandy loam. Timber, scattered juniper. Undergrowth, native grasses, sage brush, and Mormon Tea.</p> <hr/> <p>From the cor. of secs. 28, 29, 32, and 33.</p> <p>West, bet. secs. 29 and 32.</p> <p>Over gently rolling land.</p>
24.30	Power line, bears S. 10° E. and N. 10° W.
40.00	Point for the 1/4 sec. cor. of secs. 29 and 32.
	<p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in solid sandstone bedrock, with brass cap mkd.</p> <p style="text-align: center;">T 38 N R 9 E S 29 1/4 ——— S 32</p> <p style="text-align: center;">2013</p> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p> <p>Set a steel fence post nearby.</p>
77.60	High voltage transmission line, bears N. 5° E. and S. 5° W.
80.00	The cor. of secs. 29, 30, 31, and 32.
	<p>Land, gently rolling and sandstone rock outcrops. Soil, sandy loam and sandstone bedrock. Timber, scattered juniper. Undergrowth, native grasses and yucca.</p> <hr/> <p>West, bet. secs. 30 and 31.</p> <p>Over gently rolling land.</p>
40.00	Point for the 1/4 sec. cor. of secs. 30 and 31.
	<p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 23 ins. in the ground, with brass cap mkd.</p>

Survey of the Subdivisional Lines,
T. 38 N., R. 9 E., Gila and Salt River Meridian, Arizona

CHAINS	
	T 38 N R 9 E S 30 1/4 ——— S 31 2013
	Deposit a magnet, in a white plastic case, at the base of the stainless steel post. Set a steel fence post nearby. Cor. is located 45 lks. W. of trail road , bears S. 40° E. and N. 40° W.
79.37	The cor. of secs. 25, 30, 31, and 36, on the W. bdy. of the Tp., hereinbefore described. Land, gently rolling. Soil, sandy loam. Timber, juniper. Undergrowth, native grasses and sage brush.
	<hr/> From the cor. of secs. 29, 30, 31, and 32. N. 0°03' W., bet. secs. 29 and 30. Over gently rolling land.
40.00	Point for the 1/4 sec. cor. of secs. 29 and 30. Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.
	T 38 N R 9 E 1/4 S 30 S 29 2013
	Deposit a magnet, in a white plastic case, at the base of the stainless steel post. Set a steel fence post nearby. Cor. is located 1 ch. N. of power line, bears E. and W.
80.00	Point for the cor. of secs. 19, 20, 29, and 30. Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 23 ins. in solid sandstone bedrock, with brass cap mkd.

Survey of the Subdivisional Lines,
T. 38 N., R. 9 E., Gila and Salt River Meridian, Arizona

CHAINS							
	<table style="margin: auto; border-collapse: collapse;"> <tr> <td style="padding: 0 10px;">T 38 N</td> <td style="padding: 0 10px;">R 9 E</td> </tr> <tr> <td style="border-right: 1px solid black; padding: 0 5px;">S 19</td> <td style="padding: 0 5px;">S 20</td> </tr> <tr> <td style="border-right: 1px solid black; padding: 0 5px;">S 30</td> <td style="padding: 0 5px;">S 29</td> </tr> </table>	T 38 N	R 9 E	S 19	S 20	S 30	S 29
T 38 N	R 9 E						
S 19	S 20						
S 30	S 29						
	2013						
	<p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p> <p>Land, gently rolling. Soil, sandy loam and sandstone bedrock. No timber. Undergrowth, native grasses, sage brush, and Mormon tea.</p> <hr/> <p>From the cor. of secs. 20, 21, 28, and 29.</p> <p>West, bet. secs. 20 and 29.</p> <p>Over gently rolling land.</p>						
16.45	Underground water line, bears N. 5° E. and S. 5° W.						
33.60	Power line, bears N. 5° E. and S. 5° W.						
40.00	Point for the 1/4 sec. cor. of secs. 20 and 29.						
	<p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p>						
	<table style="margin: auto; border-collapse: collapse;"> <tr> <td style="padding: 0 10px;">T 38 N</td> <td style="padding: 0 10px;">R 9 E</td> </tr> <tr> <td></td> <td style="padding: 0 10px;">S 20</td> </tr> <tr> <td style="padding: 0 10px;">1/4</td> <td style="border-top: 1px solid black; padding: 0 10px;">S 29</td> </tr> </table>	T 38 N	R 9 E		S 20	1/4	S 29
T 38 N	R 9 E						
	S 20						
1/4	S 29						
	2013						
	<p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p> <p>Set a steel fence post nearby.</p> <p>Cor. is located 1.95 chs. S. and 2.55 chs. W. of trail road , bears S. 60° E. and N. 60° W.</p>						
75.15	High voltage transmission line, bears N. and S.						
80.00	The cor. of secs. 19, 20, 29, and 30.						
	<p>Land, gently rolling. Soil, sandy loam. Timber, scattered juniper. Undergrowth, native grasses, sage brush, and Mormon tea.</p> <hr/>						

Survey of the Subdivisional Lines,
T. 38 N., R. 9 E., Gila and Salt River Meridian, Arizona

CHAINS	
	West, bet. secs. 19 and 30. Over gently rolling land.
40.00	Point for the 1/4 sec. cor. of secs. 19 and 30. Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd. <div style="text-align: center;"> T 38 N R 9 E S 19 1/4 ——— S 30 2013 </div>
	Deposit a magnet, in a white plastic case, at the base of the stainless steel post. Set a steel fence post nearby.
69.10	Power line, bears S. 5° E. and N. 5° W.
69.50	Underground water line, bears S. 5° E. and N. 5° W.
79.28	The cor. of secs. 19, 24, 25, and 30, on the W. bdy. of the Tp., hereinbefore described. Land, gently rolling. Soil, sandy loam. Timber, scarce juniper. Undergrowth, native grasses, sage brush, and Mormon tea.
	From the cor. of secs. 19, 20, 29, and 30. N. 0°03' W., bet. secs. 19 and 20. Over gently rolling land.
38.40	Underground water line, bears N. 60° E. and S. 60° W.
40.00	Point for the 1/4 sec. cor. of secs. 19 and 20. Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 7 ins. below the surface of the ground, with brass cap mkd. <div style="text-align: center;"> T 38 N R 9 E 1/4 S 19 S 20 2013 </div>

Survey of the Subdivisional Lines,
T. 38 N., R. 9 E., Gila and Salt River Meridian, Arizona

CHAINS

from which

A stainless steel post, 28 ins. long, 2 1/2 ins. diam., set 23 ins. in the ground for a reference monument, bears N. 66°00' E., 132.0 ft. dist. with brass cap mkd. RM T38N R9E 132.0 FT TO COR 1/4 S20 2013 and an arrow pointing to the cor. Deposit a magnet, in a white plastic case, at the base of the stainless steel post and set a steel fence post nearby.

A stainless steel post, 28 ins. long, 2 1/2 ins. diam., set 24 ins. in the ground for a reference monument, bears S. 66°00' W., 66.0 ft. dist. with brass cap mkd. RM T38N R9E 66.0 FT TO COR 1/4 S19 2013 and an arrow pointing to the cor. Deposit a magnet, in a white plastic case, at the base of the stainless steel post and set a steel fence post nearby.

Deposit a magnet, in a white plastic case, at the base of the stainless steel post.

Cor. is located on the N. edge of a graded road, 20 ft. wide, bears N. 55° E. and S. 55° W., and 60 lks. S. of trail road, bears N. 70° E. and S. 70° W.

80.00

Point for the cor. of secs. 17, 18, 19, and 20.

Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in solid sandstone bedrock, with brass cap mkd.

T 38 N	R 9 E
S 18	S 17
S 19	S 20

2013

Deposit a magnet, in a white plastic case, at the base of the stainless steel post.

Set a steel fence post nearby.

Land, gently rolling.

Soil, sandy loam and sandstone bedrock.

Timber, scarce juniper.

Undergrowth, native grasses, yucca, sage brush, and Mormon tea.

From the cor. of secs. 16, 17, 20, and 21.

West, bet. secs. 17 and 20.

Over gently rolling land.

**Survey of the Subdivisional Lines,
T. 38 N., R. 9 E., Gila and Salt River Meridian, Arizona**

CHAINS	
2.35	BIA Route 20, an asphalt surfaced road, 33 ft. wide, bears N. 10° E. and S. 10° W.
3.70	W. right-of-way fence of BIA Route 20, barbed wire, 4 strand, parallels highway.
5.10	Underground water line, bears S. 15° E. and N. 15° W.
25.90	Power line, bears N. and S.
40.00	Point for the 1/4 sec. cor. of secs. 17 and 20. Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd. <div style="text-align: center;"> T 38 N R 9 E S 17 1/4 ——— S 20 2013 </div> Deposit a magnet, in a white plastic case, at the base of the stainless steel post. Set a steel fence post nearby.
73.00	High voltage transmission line, bears N. and S.
80.00	The cor. of secs. 17, 18, 19, and 20. Land, gently rolling. Soil, sandy loam. No timber. Undergrowth, native grasses, sage brush, and Mormon tea.
	<hr/> West, bet. secs. 18 and 19. Over gently rolling land.
40.00	Point for the 1/4 sec. cor. of secs. 18 and 19. Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd. <div style="text-align: center;"> T 38 N R 9 E S 18 1/4 ——— S 19 2013 </div>

Survey of the Subdivisional Lines,
T. 38 N., R. 9 E., Gila and Salt River Meridian, Arizona

CHAINS					
79.18	<p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p> <p>Set a steel fence post nearby.</p> <p>The cor. of secs. 13, 18, 19, and 24, on the W. bdy. of the Tp., hereinbefore described.</p> <p>Land, gently rolling. Soil, sandy loam. Timber, scarce juniper. Undergrowth, native grasses, sage brush, and Mormon tea.</p> <hr style="width: 80%; margin: 10px auto;"/>				
40.00	<p>From the cor. of secs. 17, 18, 19, and 20.</p> <p>N. 0°03' W., bet. secs. 17 and 18.</p> <p>Over gently rolling land.</p> <p>Point for the 1/4 sec. cor. of secs. 17 and 18.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center; margin: 10px 0;"> <p>T 38 N R 9 E</p> <p>1/4</p> <table style="margin: auto; border-collapse: collapse;"> <tr> <td style="border-right: 1px solid black; padding: 0 5px;">S 18</td> <td style="padding: 0 5px;">S 17</td> </tr> </table> <p>2013</p> </div> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p> <p>Set a steel fence post nearby.</p>	S 18	S 17		
S 18	S 17				
52.50	<p>Underground water line, bears N. 70° E. and S. 70° W.</p>				
52.95	<p>Power line, bears S. 80° E. and N. 80° W.</p>				
80.00	<p>Point for the cor. of secs. 7, 8, 17, and 18.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center; margin: 10px 0;"> <p>T 38 N R 9 E</p> <table style="margin: auto; border-collapse: collapse;"> <tr> <td style="border-right: 1px solid black; padding: 0 5px;">S 7</td> <td style="padding: 0 5px;">S 8</td> </tr> <tr> <td style="border-right: 1px solid black; padding: 0 5px;">S 18</td> <td style="padding: 0 5px;">S 17</td> </tr> </table> <p>2013</p> </div> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p>	S 7	S 8	S 18	S 17
S 7	S 8				
S 18	S 17				

Survey of the Subdivisional Lines,
T. 38 N., R. 9 E., Gila and Salt River Meridian, Arizona

CHAINS	
	<p>Set a steel fence post nearby.</p> <p>Land, gently rolling. Soil, sandy loam. No timber. Undergrowth, native grasses, sage brush, and Mormon tea.</p> <hr/> <p>From the cor. of secs. 8, 9, 16, and 17.</p> <p>West, bet. secs. 8 and 17.</p> <p>Over gently rolling land.</p>
6.30	E. right-of-way fence of BIA Route 20, barbed wire, 4 strand, parallels highway.
7.85	BIA Route 20, an asphalt surfaced road, 33 ft. wide, bears N. 10° E. and S. 10° W.
8.80	BIA Route 6211, a graded road, 30 ft. wide, bears S. 70° E. and N. 70° W.
9.35	W. right-of-way fence of BIA Route 20, barbed wire, 4 strand, parallels highway.
11.30	Underground water line, bears N. 10° E. and S. 10° W.
22.95	Power line, bears N. and S.
34.75	BIA Route 6211, a graded road, 30 ft. wide, bears N. 55° E. and S. 70° W.
40.00	<p>Point for the 1/4 sec. cor. of secs. 8 and 17.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T 38 N R 9 E S 8 1/4 ——— S 17</p> <p style="text-align: center;">2013</p> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p> <p>Set a steel fence post nearby.</p>
64.30	BIA Route 6211, a graded road, 30 ft. wide, bears S. 70° E. and N. 60° W.

Survey of the Subdivisional Lines,
T. 38 N., R. 9 E., Gila and Salt River Meridian, Arizona

CHAINS	
70.35	High voltage transmission line, bears N. and S.
80.00	The cor. of secs. 7, 8, 17, and 18. Land, gently rolling. Soil, sandy loam. No timber. Undergrowth, native grasses and sage brush.

	West, bet. secs. 7 and 18. Over gently rolling land.
40.00	Point for the 1/4 sec. cor. of secs. 7 and 18. Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd. <div style="text-align: center;"> T 38 N R 9 E S 7 1/4 ——— S 18 2013 </div> Deposit a magnet, in a white plastic case, at the base of the stainless steel post. Set a steel fence post nearby.
79.10	The cor. of secs. 7, 12, 13, and 18, on the W. bdy. of the Tp., hereinbefore described. Land, gently rolling. Soil, sandy loam. Timber, scarce juniper. Undergrowth, native grasses, sage brush, and Mormon tea.

	From the cor. of secs. 7, 8, 17, and 18. N. 0°03' W., bet. secs. 7 and 8. Over gently rolling land.
40.00	True point for the 1/4 sec. cor. of secs. 7 and 8, falls on the W. slope among loose sandstone boulders of Circular White Ridge, where it is impracticable to set a permanent monument. From this true point, the point selected for a witness cor. to the 1/4 sec. cor. of secs. 7 and 8, bears N. 64°58' W., 50 lks. dist.

Survey of the Subdivisional Lines,
T. 38 N., R. 9 E., Gila and Salt River Meridian, Arizona

CHAINS	
	<p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">WC T 38 N R 9 E 1/4 S 7 S 8 →</p> <p style="text-align: center;">2013</p> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p> <p>Set a steel fence post nearby.</p> <p>Cor. is located at the base of Circular White Ridge, 40 lks. W. of sandstone cliff face, 75 ft. high, bears N. 15° E. and S. 15° W.</p>
80.00	<p>Point for the cor. of secs. 5, 6, 7, and 8.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in solid sandstone bedrock, with brass cap mkd.</p> <p style="text-align: center;">T 38 N R 9 E S 6 S 5 S 7 S 8</p> <p style="text-align: center;">2013</p> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p> <p>Set a steel fence post nearby.</p> <p>Cor. is located 75 lks N. of Circular White Ridge, a sandstone rim, 70 ft. high, bears S. 80° E. and S. 65° W., and 2.50 chs. E. of Circular White Ridge, a sandstone rim, 70 ft. high, bears S. 45° E. and N. 5° W.</p> <p>Land, gently rolling and broken. Soil, sandy loam and sandstone bedrock. Timber, scattered juniper. Undergrowth, native grasses, sage brush, yucca, and Mormon tea.</p> <hr/> <p>From the cor. of secs. 4, 5, 8, and 9.</p> <p>West, bet. secs. 5 and 8.</p> <p>Over gently rolling land.</p>
4.70	<p>Trail road, bears N. and S.</p>

Survey of the Subdivisional Lines,
T. 38 N., R. 9 E., Gila and Salt River Meridian, Arizona

CHAINS	
5.55	Power line, bears N. and S.
40.00	Point for the 1/4 sec. cor. of secs. 5 and 8. Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd. <div style="text-align: center;"> T 38 N R 9 E S 5 1/4 ——— S 8 2013 </div> Deposit a magnet, in a white plastic case, at the base of the stainless steel post. Set a steel fence post nearby.
67.75	High voltage transmission line, bears N. and S.
80.00	The cor. of secs. 5, 6, 7, and 8. Land, gently rolling. Soil, sandy loam. No timber. Undergrowth, native grasses, sage brush, and Mormon tea.
	<hr/>
	West, bet. secs. 6 and 7. Over gently rolling land.
40.00	Point for the 1/4 sec. cor. of secs. 6 and 7. Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd. <div style="text-align: center;"> T 38 N R 9 E S 6 1/4 ——— S 7 2013 </div> Deposit a magnet, in a white plastic case, at the base of the stainless steel post. Set a steel fence post nearby.
48.35	BIA Route 6211, a graded road, 30 ft. wide, bears S. 40° E. and N. 40° W.

**Survey of the Subdivisional Lines,
T. 38 N., R. 9 E., Gila and Salt River Meridian, Arizona**

CHAINS	
79.01	<p>The cor. of secs. 1, 6, 7, and 12, on the W. bdy. of the Tp., hereinbefore described.</p> <p>Land, rolling. Soil, sandy loam. No timber. Undergrowth, native grasses, sage brush, and Mormon tea.</p> <hr/> <p>From the cor. of secs. 5, 6, 7, and 8. N. 0°03' W., bet. secs. 5 and 6. Over gently rolling land.</p>
40.00	<p>Point for the 1/4 sec. cor. of secs. 5 and 6.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T 38 N R 9 E 1/4 S 6 S 5 2013</p> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post. Set a steel fence post nearby.</p>
80.00	<p>The cor. of secs. 5, 6, 31 and 32, on the N. bdy. of the Tp., hereinbefore described.</p> <p>Land, gently rolling. Soil, sandy loam. Timber, scarce juniper. Undergrowth, native grasses, yucca, sage brush, and Mormon tea.</p> <hr/> <p style="text-align: center;">Subdivision of Section 4, T. 38 N., R. 9 E., Gila and Salt River Meridian, Arizona</p> <hr/> <p>From the 1/4 sec. cor. of secs. 4 and 9. N. 0°02' W., on the N. and S. center line of sec. 4. Over gently rolling land.</p>

**Subdivision of Section 4,
T. 38 N., R. 9 E., Gila and Salt River Meridian, Arizona**

CHAINS	
40.00	<p>Point for the center 1/4 sec. cor. of sec. 4, at intersection with the E. and W. center line sec. 4.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T 38 N R 9 E C 1/4 S 4</p> <p style="text-align: center;">2013</p> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p> <p>Set a steel fence post nearby.</p>
80.00	<p>The 1/4 sec. cor. of secs. 4 and 33, on the N. bdy. of the Tp.</p> <hr/> <p>From the 1/4 sec. cor. of secs. 3 and 4.</p> <p>West, on the E. and W. center line of sec. 4.</p> <p>Over gently rolling land.</p>
40.00	The center 1/4 sec. cor. of sec. 4.
59.50	Underground water line, bears N. and S.
63.75	Power line, bears N. 10° E. and S. 10° W.
69.90	Power line, bears N. and S.
70.50	E. right-of-way fence of BIA Route 20, barbed wire, 4 strand, parallels highway.
72.05	BIA Route 20, an asphalt surfaced road, 33 ft. wide, bears N. 5° E. and S. 5° W.
73.55	W. right-of-way fence of BIA Route 20, barbed wire, 4 strand, parallels highway.
80.00	<p>The 1/4 sec. cor. of secs. 4 and 5.</p> <hr/> <p style="text-align: center;">Subdivision of Section 8, T. 38 N., R. 9 E., Gila and Salt River Meridian, Arizona</p> <hr/> <p>From the 1/4 sec. cor. of secs. 8 and 17.</p> <p>N. 0°03' W., on the N. and S. center line of sec. 8.</p>

Subdivision of Section 8,
T. 38 N., R. 9 E., Gila and Salt River Meridian, Arizona

CHAINS	
	Over gently rolling land.
21.05	From this point, a fiberglass livestock water tank, 16 ft. diam., 8 ft. high, bears W., 15.13 chs. dist., and from this fiberglass tank, another livestock fiberglass water tank, 16 ft. diam., 8 ft. high, bears N. 75° W., 30 lks. dist.
29.05	Top of sandstone rim of Circular White Ridge, 40 ft. high, bears S. 50° E. and S. 65° W.
40.00	Point for the center 1/4 sec. cor. of sec. 8, at intersection with the E. and W. center line sec. 8. Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd. T 38 N R 9 E C 1/4 S 8 2013 Deposit a magnet, in a white plastic case, at the base of the stainless steel post. Cor. is located 1 ch. E. of trail road , bears N. 10° E. and S. 10° W.
80.00	The 1/4 sec. cor. of secs. 5 and 8. <hr/>
	From the 1/4 sec. cor. of secs. 8 and 9. West, on the E. and W. center line of sec. 8. Over gently rolling land.
3.20	Underground water line, bears N. 10° E. and S. 10° W.
4.80	Power line, bears S. 5° E. and N. 5° W.
11.70	Top of sandstone rim of Circular White Ridge, 30 ft. high, bears N. 45° E. and S. 45° W.
21.50	Power line, bears N. and S.
40.00	The center 1/4 sec. cor. of sec. 8.
69.05	High voltage transmission line, bears N. and S.
75.50	Top of sandstone rim of Circular White Ridge, 75 ft. high, bears N. 15° E. and S. 5° E.
80.00	True point for the 1/4 sec. cor. of secs. 7 and 8. <hr/>

**Subdivision of Section 9,
T. 38 N., R. 9 E., Gila and Salt River Meridian, Arizona**

CHAINS	<p>From the 1/4 sec. cor. of secs. 9 and 16.</p> <p>N. 0°02' W., on the N. and S. center line of sec. 9.</p> <p>Over gently rolling land.</p>
40.00	<p>Point for the center 1/4 sec. cor. of sec. 9, at intersection with the E. and W. center line sec. 9.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T 38 N R 9 E C 1/4 S 9</p> <p style="text-align: center;">2013</p> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p> <p>Set a steel fence post nearby.</p> <p>Cor. is located 90 lks. S. and 2.20 chs. E. of trail road , bears N. 65° E. and S. 65° W.</p>
80.00	<p>The 1/4 sec. cor. of secs. 4 and 9.</p> <hr/> <p>From the 1/4 sec. cor. of secs. 9 and 10.</p> <p>West, on the E. and W. center line of sec. 9.</p> <p>Over gently rolling land.</p>
40.00	<p>The center 1/4 sec. cor. of sec. 9.</p>
64.25	<p>Underground water line, bears N. and S.</p>
68.45	<p>Power line, bears N. 5° E. and S. 5° W.</p>
71.75	<p>Top of Dead Monkey Ridge, a sandstone ridge, 40 ft. high, bears N. 10° E. and S. 15° W.</p>
80.00	<p>The 1/4 sec. cor. of secs. 8 and 9.</p> <hr/> <p style="text-align: center;">Subdivision of Section 17, T. 38 N., R. 9 E., Gila and Salt River Meridian, Arizona</p> <hr/> <p>From the 1/4 sec. cor. of secs. 17 and 20.</p>

Subdivision of Section 17,
T. 38 N., R. 9 E., Gila and Salt River Meridian, Arizona

CHAINS	
	N. 0°03' W., on the N. and S. center line of sec. 17. Over gently rolling land.
40.00	Point for the center 1/4 sec. cor. of sec. 17, at intersection with the E. and W. center line sec. 17. Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd. T 38 N R 9 E C 1/4 S 17 2013 Deposit a magnet, in a white plastic case, at the base of the stainless steel post. Set a steel fence post nearby. Cor. is located 25 lks. S. and 20 lks. E. of trail road , bears N. 35° E. and S. 35° W.
45.20	Power line, bears S. 80° E. and N. 80° W.
45.90	Underground water line, bears S. 80° E. and N. 80° W.
78.20	BIA Route 6211, a graded road, 30 ft. wide, bears N. 70° E. and S. 70° W.
80.00	The 1/4 sec. cor. of secs. 8 and 17. <hr/>
	From the 1/4 sec. cor. of secs. 16 and 17. West, on the E. and W. center line of sec. 17. Over gently rolling land.
8.50	E. right-of-way fence of BIA Route 20, barbed wire, 4 strand, parallels highway.
10.05	BIA Route 20, an asphalt surfaced road, 33 ft. wide, bears N. and S.
11.55	W. right-of-way fence of BIA Route 20, barbed wire, 4 strand, parallels highway.
13.70	Underground water line, bears N. and S.
24.40	Power line, bears N. and S.
40.00	The center 1/4 sec. cor. of sec. 17.

Subdivision of Section 17,
T. 38 N., R. 9 E., Gila and Salt River Meridian, Arizona

CHAINS	
71.65	High voltage transmission line, bears N. and S.
80.00	The 1/4 sec. cor. of secs. 17 and 18
<hr/> <p style="text-align: center;">Subdivision of Section 20, T. 38 N., R. 9 E., Gila and Salt River Meridian, Arizona</p> <hr/>	
	From the 1/4 sec. cor. of secs. 20 and 29.
	N. 0°03' W., on the N. and S. center line of sec. 20.
	Over gently rolling land.
40.00	Point for the center 1/4 sec. cor. of sec. 20, at intersection with the E. and W. center line sec. 20.
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in solid sandstone bedrock, with brass cap mkd.
	T 38 N R 9 E C 1/4 S 20
	2013
	Deposit a magnet, in a white plastic case, at the base of the stainless steel post.
	Set a steel fence post nearby.
49.40	Underground water line, bears S. 85° E. and N. 85° W.
80.00	The 1/4 sec. cor. of secs. 17 and 20.
<hr/>	
	From the 1/4 sec. cor. of secs. 20 and 21.
	West, on the E. and W. center line of sec. 20.
	Over gently rolling land.
23.90	Underground water line, bears S. 20° E. and N. 20° W.
24.15	Power line, bears N. 15° E. and S. 15° W.
40.00	The center 1/4 sec. cor. of sec. 20.
74.30	High voltage transmission line, bears N. and S.
77.05	Underground water line, bears N. 60° E. and S. 60° W.
80.00	The 1/4 sec. cor. of secs. 19 and 20.
<hr/>	

**Subdivision of Section 21,
T. 38 N., R. 9 E., Gila and Salt River Meridian, Arizona**

CHAINS	<p>From the 1/4 sec. cor. of secs. 21 and 28.</p> <p>N. 0°02' W., on the N. and S. center line of sec. 21.</p> <p>Over gently rolling land.</p>
40.00	<p>Point for the center 1/4 sec. cor. of sec. 21, at intersection with the E. and W. center line sec. 21.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in solid sandstone bedrock, with brass cap mkd.</p> <p style="text-align: center;">T 38 N R 9 E C 1/4 S 21</p> <p style="text-align: center;">2013</p> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p> <p>Set a steel fence post nearby.</p>
80.00	<p>The 1/4 sec. cor. of secs. 16 and 21.</p> <hr/> <p>From the 1/4 sec. cor. of secs. 21 and 22.</p> <p>West, on the E. and W. center line of sec. 21.</p> <p>Over gently rolling land.</p>
40.00	<p>The center 1/4 sec. cor. of sec. 21.</p>
74.05	<p>Power line, bears S. 5° E. and N. 5° W.</p>
80.00	<p>The 1/4 sec. cor. of secs. 20 and 21.</p> <hr/> <p style="text-align: center;">Subdivision of Section 28, T. 38 N., R. 9 E., Gila and Salt River Meridian, Arizona</p> <hr/> <p>From the 1/4 sec. cor. of secs. 28 and 33.</p> <p>N. 0°02' W., on the N. and S. center line of sec. 28.</p> <p>Over gently rolling land.</p>
40.00	<p>Point for the center 1/4 sec. cor. of sec. 28, at intersection with the E. and W. center line sec. 28.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with brass cap mkd.</p>

**Subdivision of Section 28,
T. 38 N., R. 9 E., Gila and Salt River Meridian, Arizona**

CHAINS	
	T 38 N R 9 E C 1/4 S 28
	2013
	Deposit a magnet, in a white plastic case, at the base of the stainless steel post.
	Set a steel fence post nearby.
80.00	The 1/4 sec. cor. of secs. 21 and 28.
	<hr/>
	From the 1/4 sec. cor. of secs. 27 and 28.
	West, on the E. and W. center line of sec. 28.
	Over gently rolling land.
40.00	The center 1/4 sec. cor. of sec. 28.
64.60	E. right-of-way fence of BIA Route 20, barbed wire, 4 strand, parallels highway.
66.45	BIA Route 20, an asphalt surfaced road, 33 ft. wide, bears S. 10° E. and N. 10° W.
67.60	W. right-of-way fence of BIA Route 20, barbed wire, 4 strand, parallels highway.
68.70	Power line, bears S. 5° E. and N. 5° W.
80.00	The 1/4 sec. cor. of secs. 28 and 29.
	<hr/>
	Subdivision of Section 33, T. 38 N., R. 9 E., Gila and Salt River Meridian, Arizona
	<hr/>
	From the 1/4 sec. cor. of secs. 4 and 33, on the S. bdy. of the Tp.
	N. 0°02' W., on the N. and S. center line of sec. 33.
	Over gently rolling land.
40.00	Point for the center 1/4 sec. cor. of sec. 33, at intersection with the E. and W. center line sec. 33.
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.

Subdivision of Section 33,
T. 38 N., R. 9 E., Gila and Salt River Meridian, Arizona

CHAINS	
	T 38 N R 9 E C 1/4 S 33
	2013
	Deposit a magnet, in a white plastic case, at the base of the stainless steel post.
	Set a steel fence post nearby.
80.00	The 1/4 sec. cor. of secs. 28 and 33.
	<hr/>
	From the 1/4 sec. cor. of secs. 33 and 34.
	West, on the E. and W. center line of sec. 33.
	Over gently rolling land.
40.00	The center 1/4 sec. cor. of sec. 33.
50.90	Underground water line, bears S. 25° E. and N. 25° W.
58.95	E. right-of-way fence of BIA Route 20, barbed wire, 4 strand, parallels highway.
59.90	BIA Route 20, an asphalt surfaced road, 33 ft. wide, bears N. 10° E. and S. 10° W.
61.95	W. right-of-way fence of BIA Route 20, barbed wire, 4 strand, parallels highway.
63.35	Power line, bears S. 5° E. and N. 5° W.
80.00	The 1/4 sec. cor. of secs. 32 and 33.
	<hr/>

T. 38 N., R. 9 E., Gila and Salt River Meridian, Arizona

CHAINS	GENERAL DESCRIPTION
	<p>The area surveyed is within the Navajo Indian Reservation, 12 miles south of the Lechee community, 16 miles south of the City of Page, and 19 miles northwest of the Kaibeto community. Primary access is a paved road, BIA Route 20, bearing north and south in the west third portion of the township. A series of trail roads provide access throughout the township, and a graded road in the southeast, connects BIA Route 20 to State Highway 98. ATV's were required to access the majority of the areas within the township.</p> <p>There are no major housing developments, only smaller housing clusters and single home units scattered throughout the township.</p> <p>The highest approximate elevation of this survey, 6200 feet above sea level, is near the southeast portion of the township, atop Mormon Ridge. The lowest approximate elevation, at 5650 feet is in the open valley near Antelope Creek in the northeast portion of the township.</p> <p>The vegetation consists of scattered juniper throughout the entire township. Sage brush, salt brush, yucca, rabbit brush, Mormon tea and native grasses, are more prominent throughout the township. There is presence of grazing cattle, sheep and horses in the area. The soil is mostly sandy loam with scattered sandstone rock outcrops, and Circular White Ridge, a sandstone mesa, in the north and eastern portion of the township.</p> <p>The mean magnetic declination of 11° E. was derived from the United States Geological Survey computer program GEOMAG, utilizing the World Magnetic Model for Epoch 2010-2005 for the dates of survey.</p>

CERTIFICATE OF SURVEY

I, Fabian Yazzie, Cadastral Surveyor, HEREBY CERTIFY upon honor, that in pursuance of special instructions bearing date of the 31st day of July, 2013, I have surveyed a portion of the Second Guide Meridian East (west boundary), the North boundary, the subdivisional lines, and the subdivision of certain sections, T. 38 N., R. 9 E., of the Gila and Salt River Meridian, in the State of Arizona, which are represented in the foregoing field notes as having been executed by me and under my direction. Said survey has been made in strict conformity with said special instructions, the Manual of Instructions for the Survey of the Public Lands of the United States, 2009, and in specific manner described in the foregoing field notes.

6/02/2014
(Date)

[Signature]
(Cadastral Surveyor)

CERTIFICATE OF APPROVAL

BUREAU OF LAND MANAGEMENT
Phoenix, Arizona

The foregoing field notes of the survey of a portion of the Second Guide Meridian East (west boundary), the North boundary, the subdivisional lines, and the subdivision of certain sections, T. 38 N., R. 9 E., Gila and Salt River Meridian, in the State of Arizona, executed by Fabian Yazzie, Cadastral Surveyor, having been critically examined and found correct, are hereby approved.

6/11/2014
(Date)

[Signature]
(Chief Cadastral Surveyor of Arizona)

~~CERTIFICATE OF TRANSCRIPT~~

~~I CERTIFY That the foregoing transcript of the field notes of the above described surveys in T. 38 N., R. 9 E., Gila and Salt River Meridian, Arizona, is a true copy of the original field notes.~~

~~_____
(Date)~~

~~_____
(Chief Cadastral Surveyor of Arizona)~~