

ORIGINAL

**UNITED STATES  
DEPARTMENT OF THE INTERIOR  
BUREAU OF LAND MANAGEMENT**

FIELD NOTES

OF THE

DEPENDENT RESURVEY OF A PORTION OF  
HOPI-NAVAJO PARTITION LINE SEGMENT "D",  
THE SURVEY OF A PORTION OF  
THE THIRD GUIDE MERIDIAN EAST (WEST BOUNDARY),  
THE EAST AND NORTH BOUNDARIES,  
THE SUBDIVISIONAL LINES,  
AND  
THE SUBDIVISION OF CERTAIN SECTIONS  
TOWNSHIP 34 NORTH, RANGE 13 EAST,  
OF THE GILA AND SALT RIVER MERIDIAN,  
IN THE STATE OF ARIZONA.

**EXECUTED BY**

**Craig S. Dukart, Cadastral Surveyor**

**Blas J. Urena, Cadastral Surveyor**

Under Special Instructions dated October 21, 2013, approved October 21, 2013, which provided for the surveys included under Group No. 1125, and assignment instructions dated October 21, 2013.

**Survey commenced October 22, 2013**

**Survey completed November 26, 2013**

# INDEX DIAGRAM

TOWNSHIP 34 NORTH                      RANGE 13 EAST  
 GILA & SALT RIVER MERIDIAN, ARIZONA

25	24	23	22	21	20
13    6	68    5	57    4	49    3	41    2	33    1    19
68	67	57	48	40	32
13    7	66    8	56    9	48    10	40    11	31    12    18
66	65	56	47	39	30
12    18	65    17	55    16	47    15	38    14	29    13    17
64	64	54	46	37	29
11    19	63    20	53    21	45    22	36    23	28    24    16
62	61	53	44	36	27
10    30	60    29	51    28	43    27	35    26	27    25    16
60	59	51	42	34	26
9    31	58    32	50    33	41    34	33    35	25    36    15
		6	4		

Portion of the Hopi-Navajo  
 Partition Line, Segment "D" .....Pages 4-9  
 Subdivision of Section 1 .....Pages 69  
 Subdivision of Section 11 .....Pages 70  
 Subdivision of Section 12 .....Pages 70-71  
 Subdivision of Section 14 .....Pages 71-72  
 Subdivision of Section 19 .....Pages 73  
 Subdivision of Section 20 .....Pages 74  
 Subdivision of Section 22 .....Pages 74-75  
 Subdivision of Section 23 .....Pages 75-76  
 Subdivision of Section 27 .....Pages 76-77  
 Subdivision of Section 28 .....Pages 77-78  
 Subdivision of Section 29 .....Pages 78-79  
 Subdivision of Section 31 .....Pages 79-80  
 Subdivision of Section 32 .....Pages 80-81  
 Subdivision of Section 33 .....Pages 81-82

## T. 34 N., R. 13 E., Gila and Salt River Meridian, Arizona

## CHAINS

The following field notes describe the dependent resurvey of a portion of Hopi-Navajo partition line, segment "D", the survey of the Third Guide Meridian East (west boundary), the east and north boundaries, the subdivisional lines, and the subdivision of certain sections, Township 34 North, Range 13 East, Gila and Salt River Meridian, Arizona.

The history of surveys pertaining to this survey is as follows:

The survey of the Partition Line between the Hopi Reservation and the Navajo Reservation, Segment "D", was surveyed by Kenneth A. Krenke, Harry S. Pierce, Shirley B. Hjellum and Jerry L. Wahl, Supervisory Cadastral Surveyors, 1977 - 1981. (Book 5151)

The survey of the Eighth Standard Parallel North (South boundary) the Third Guide Meridian East (West boundary), the East and North boundaries and the subdivisional lines of Township 33 North, Range 13 East, Gila and Salt River Meridian, were surveyed by W. William Foster, Cadastral Surveyor, in 2002.

The northeast and northwest township corners and an electronic control monument, Township 34 North, Range 12 East, Gila and Salt River Meridian, in Plat Only Surveys, were established by, Joe R. Salazar, Cadastral Surveyor, in 2009.

The northeast township corner, Township 34 North, Range 12 1/2 East, Gila and Salt River Meridian, in Plat Only Surveys, were established by, Joe R. Salazar, Cadastral Surveyor, in 2010.

The survey was executed in accordance with the specifications as set forth in the Manual of Surveying Instructions, 2009, and the Special Instructions dated October 21, 2013, for Group No. 1125, Arizona.

The true meridian direction and length of all lines were determined by real time kinematic global positioning system observations using Trimble Navigation 5700 and 5800 model receivers.

The "standard monument" referred to in these notes is a stainless steel post, 28 ins. Long, 2 1/2 ins. diam., with a brass cap. A magnet in a white plastic case is deposited at the base of the stainless steel post.

## T. 34 N., R. 13 E., Gila and Salt River Meridian, Arizona

## CHAINS

Geodetic control was derived from Global Positioning System (GPS) static post observations processed by National Geodetic Survey, Online Positioning User Service (OPUS), utilizing Continuously Operating Reference Stations (CORS) DI2245 P011 SPIDERROCKAZ2005 CORS ARP, DL1882 AZFL NAU FLAGSTAFF CORS ARP and DL6010 AZSV STAR VALLEY CORS ARP. The NAD 83 (CORS96) (EPOCH:2010), geographic position of the following two corners:

The southeast cor. of the township, is as follows:

Latitude: 36°18'09.339" N.                      Longitude: 110°53'00.123" W.

The northwest cor. of the township, is as follows:

Latitude: 36°23'22.522" N.                      Longitude: 110°59'26.621" W.

The mean magnetic declination is 10 3/4° E.

---

**Dependent Resurvey of a portion  
of the Hopi-Navajo Partition Line, Segment "D"  
T. 34 N., R. 13 E., Gila and Salt River Meridian, Arizona**

---

Restoring the survey executed by  
Kenneth A. Krenke, Harry S. Pierce,  
Shirley B. Hjellum, and Jerry L. Wahl,  
1977 - 1981

---

Beginning at the crossing closing cor. at the intersection of the line APD 325 to APD 326, with the sec. line bet. secs. 3 and 34 on the S. bdy. of the Tp., monumented with a stainless steel post, 2 1/2 ins. diam., firmly set, projecting 2 ins. above the ground, with brass cap mkd. T34N R13E S34 NAVAJO CC S3 HOPI T33N 2002. Add the marks 2013 to the brass cap.

From this point the cor. of secs. 2, 3, 34, and 35, bears E., 14.47 chs. dist., monumented with a stainless steel post, 2 1/2 in. diam., firmly set, projecting 2 ins. above the ground, with brass cap mkd. T34N R13E S34 S35 S3 S2 T33N 2002. Add the marks 2013 to the brass cap.

From this same point APD 325 on the Hopi-Navajo partition line, segment "D", bears S. 57°20' E., 11.51 chs. dist., monumented with a copper coated steel stake, firmly set, 2 ins. below the ground, with a 1 1/2 in. diam. brass cap mkd. 2002 NAVAJO HOPI APD-325 1979. This cor. is located at the edge of a dirt road.

**Dependent Resurvey of a portion  
of the Hopi-Navajo Partition Line, Segment "D"  
T. 34 N., R. 13 E., Gila and Salt River Meridian, Arizona**

CHAINS	
	<p>from which</p> <p style="padding-left: 40px;">An iron post, 2 1/2 ins. diam., firmly set, 6 ins. below the ground, for a reference monument, bears S. 45°15' W., 74.7 ft. dist., with brass cap mkd. RM HIR APD-325 75.0 FT 1979 2002 and an arrow pointing to the cor. Add the marks 2013 to the brass cap.</p> <p>N. 57°21' W., along a portion of line APD-325 to APD-326, segment "D".</p> <p>Over rolling terrain.</p>
4.44	<p>APD 326 on the Hopi-Navajo partition line, segment "D", monumented with a copper coated steel stake, firmly set, 16 ins. below the ground, with a 1 1/2 in. diam. brass cap mkd. 2002 NAVAJO HOPI APD-326 1979.</p> <p>from which</p> <p style="padding-left: 40px;">An iron post, 2 1/2 ins. diam., firmly set, projecting 3 ins. above the ground, for a reference monument, bears N. 6°28' E., 75.0 ft. dist., with brass cap mkd. RM NIR APD-326 75.0 FT 1979 2002 and an arrow pointing to the cor. Add the marks 2013 to the brass cap.</p> <p style="padding-left: 40px;">An iron post, 2 1/2 ins. diam., firmly set, projecting 9 ins. above the ground, for a reference monument, bears S. 6°28' W., 74.5 ft. dist., with brass cap mkd. RM NIR APD-326 75.0 FT 1979 2002 and an arrow pointing to the cor. Add the marks 2013 to the brass cap.</p> <hr/> <p>S. 70°24' W., along a portion of line APD-326 to APD-327, segment "D".</p> <p>Over rolling terrain.</p>
7.14	<p>The crossing closing cor., on the sec. line bet. secs. 3 and 34, on the S. bdy., monumented with a stainless steel post, 2 1/2 ins. diam., firmly set, projecting 5 ins. above the ground, with a brass cap mkd. T34N R13E NAVAJO S34 CC S3 HOPI T33N 2002. Add the marks 2013 to the brass cap.</p> <p>From this point, the crossing closing cor. at the intersection of the line APD 325 to APD 326, with the sec. line bet. secs. 3 and 34 on the S. bdy. bears E., 10.465 chs. dist., hereinbefore described.</p>

Dependent Resurvey of a portion  
of the Hopi-Navajo Partition Line, Segment "D"  
T. 34 N., R. 13 E., Gila and Salt River Meridian, Arizona

## CHAINS

From this same point, APD 327 on the Hopi-Navajo partition line, segment "D", bears S. 70°23' W., 5.94 chs. dist., monumented with a copper coated steel stake, firmly set, 4 ins. below the ground, with a 1 1/2 in. diam. brass cap mkd. 2002 NAVAJO HOPI APD-327 1979.

from which

An iron post, 2 1/2 ins. diam., firmly set, projecting 3 ins. above the ground, for a reference monument, bears N. 20°40' W., 75.0 ft. dist., with brass cap mkd. RM NIR APD-327 75.0 FT 1979 2002 and an arrow pointing to the cor. Add the marks 2013 to the brass cap.

From this same point, the 1/4 sec. cor. of secs. 3 and 34, bears W., 15.065 chs. dist., monumented with a stainless steel post, 2 1/2 ins. diam., firmly set, projecting 4 ins. above the ground, with brass cap mkd. T34N R13E S34 1/4 S3 T33N 2002. Add the marks 2013 to the brass cap.

---

From the crossing closing cor. at the intersection of the line APD 336 to APD 337, with the sec. line bet. secs. 4 and 33 on the S. bdy. of the Tp., monumented with a stainless steel post, 2 1/2 ins. diam., firmly set, 5 ins. below the ground, with brass cap mkd. T34N R13E S33 NAVAJO HOPI CC S4 T33N 2002. Add the marks 2013 to the brass cap.

Cor. is located in a dirt road.

From this point the cor. of secs. 3, 4, 33, and 34, bears E., 1.31 chs. dist., monumented with a stainless steel post, 2 1/2 ins. diam., firmly set, projecting 5 ins. above the ground, with brass cap mkd. T34N R13E S33 S34 S4 S3 T33N 2002. Add the marks 2013 to the brass cap.

From this same point AP 336 on the Hopi-Navajo partition line, segment "D", bears S. 35°56' E., 3.60 chs. dist., monumented with a copper coated steel stake, firmly set, 11 ins. below the ground, with a 1 1/2 in. diam. brass cap mkd. NAVAJO HOPI 2002 APD-336 1979. Cor. is located in dirt road.

from which

An iron post, 2 1/2 ins. diam., firmly set, projecting 6 ins. above the ground, for a reference monument, bears N. 65°37' E., 75.0 ft. dist., with brass cap mkd. RM NIR APD-336 75.0 FT 2002 1979 and an arrow pointing to the cor. Add the marks 2013 to the brass cap.

**Dependent Resurvey of a portion  
of the Hopi-Navajo Partition Line, Segment "D"  
T. 34 N., R. 13 E., Gila and Salt River Meridian, Arizona**

CHAINS	
	<p>An iron post, 2 1/2 ins. diam., firmly set, flush with the ground, for a reference monument, bears S. 65°37' W., 74.6 ft. dist., with brass cap mkd. RM HIR APD-336 75.0 FT 2002 1979 and an arrow pointing to the cor. Add the marks 2013 to the brass cap.</p> <p>N. 35°56' W., along a portion of line APD-336 to APD-337, segment "D".</p> <p>Over rolling terrain.</p>
2.78	<p>APD 337 on the Hopi-Navajo partition line, segment "D", monumented with a copper coated steel stake, firmly set, 11 ins. below the ground, with a 1 1/2 in. diam. brass cap mkd. APD-337 NAVAJO HOPI 1979 2002.</p> <p>Cor. is located in a dirt road.</p> <p>from which</p> <p>An alum. post, 2 1/2 ins. diam., firmly set, flush with the ground, for a reference monument, bears N. 18°43' E., 75.0 ft. dist., with brass cap mkd. RM NIR APD-337 75.0 FT 1979 2002 and an arrow pointing to the cor. Add the marks 2013 to the brass cap.</p> <p>An iron post, 2 1/2 ins. diam., firmly set, projecting 9 ins. above the ground, for a reference monument, bears S. 18°30' W., 75.0 ft. dist., with brass cap mkd. RM HIR APD-337 75.0 FT 1979 2002 and an arrow pointing to the cor. Add the marks 2013 to the brass cap.</p> <hr/> <p>S. 73°13' W., along line APD-337 to APD-338, segment "D".</p> <p>Over rolling terrain.</p>
6.90	<p>APD 338 on the Hopi-Navajo partition line, segment "D", monumented with a copper coated steel stake, firmly set, 11 ins. below the ground, with a 1 1/2 in. diam. brass cap mkd. NAVAJO HOPI APD-338 1979 2002. Cor. is located at edge of a dirt road.</p> <p>from which</p> <p>An alum. post, 2 1/2 ins. diam., firmly set, flush with the ground, for a reference monument, bears S. 31°14' E., 75.0 ft. dist., with brass cap mkd. RM HIR APD-338 75.0 FT 1979 2002 and an arrow pointing to the cor. Add the marks 2013 to the brass cap.</p>

Dependent Resurvey of a portion  
of the Hopi-Navajo Partition Line, Segment "D"  
T. 34 N., R. 13 E., Gila and Salt River Meridian, Arizona

CHAINS	<p>An iron post, 2 1/2 ins. diam., firmly set, projecting 9 ins. above the ground, for a reference monument, bears N. 31°14' W., 75.0 ft. dist., with brass cap mkd. RM NIR APD-338 75.0 FT 1979 2002 and an arrow pointing to the cor. Add the marks 2013 to the brass cap.</p> <hr/> <p>S. 44°26' W., along a portion of line APD-338 to APD-339, segment "D".</p> <p>Over rolling terrain.</p>
0.37	<p>The crossing closing cor., on the sec. line bet. secs. 4 and 33, on the S. bdy., monumented with a stainless steel post, 2 1/2 ins. diam., firmly set, 5 ins. below the ground, with a brass cap mkd. T34N R13E NAVAJO S33 CC S4 HOPI T33N 2002. Add the marks 2013 to the brass cap.</p> <p>Cor. is located in a dirt road.</p> <p>from which</p> <p style="padding-left: 40px;">A stainless steel post, 2 1/2 ins. diam., firmly set, projecting 5 ins. above the ground, for a reference monument, bears S. 0°41' E., 101.3 ft. dist., with brass cap mkd. RM T33N R13E S4 101.3 FT. TO COR. 2002 and an arrow pointing to the cor. Add the marks 2013 to the brass cap. (Record, S. 1° E.)</p> <p style="padding-left: 40px;">A stainless steel post, 2 1/2 ins. diam., firmly set, projecting 5 ins. above the ground, for a reference monument, bears S. 88°46' W., 82.8 ft. dist., with brass cap mkd. RM T33N R13E S4 82.8 FT. TO COR. 2002 and an arrow pointing to the cor. Add the marks 2013 to the brass cap. (Record, S. 89° W.)</p> <p>From this point, the crossing closing cor. at the intersection of the line APD 336 to APD 337, with the sec. line bet. secs. 4 and 33 on the S. bdy., bears E., 8.495 chs. dist., hereinbefore described.</p> <p>From this same point, APD 339 on the Hopi-Navajo partition line, segment "D", bears S. 44°26' W., 3.90 chs. dist., monumented with a copper coated steel stake, firmly set, 4 ins. below the ground, with a 1 1/2 in. diam. brass cap mkd. 2002 NAVAJO HOPI APD-339 1979.</p> <p>from which</p> <p style="padding-left: 40px;">An iron post, 2 1/2 ins. diam., firmly set, projecting 3 ins. above the ground, for a reference monument, bears S. 26°03' E., 75.0 ft. dist., with brass cap mkd. RM HIR APD-339 75.0 FT 1979 2002 and an arrow pointing to the cor. Add the marks 2013 to the brass cap.</p>



**Dependent Resurvey of a portion  
of the Hopi-Navajo Partition Line, Segment "D"  
T. 34 N., R. 13 E., Gila and Salt River Meridian, Arizona**

CHAINS

An iron post, 2 1/2 ins. diam., firmly set, projecting 3 ins. above the ground, for a reference monument, bears S. 26°03' W., 75.0 ft. dist., with brass cap mkd. RM NIR APD-339 75.0 FT 1979 2002 and an arrow pointing to the cor. Add the marks 2013 to the brass cap.

From this same point, the 1/4 sec. cor. of secs. 4 and 33, bears W., 30.195 chs. dist., monumented with a brass tablet, 3 1/4 ins. diam., cemented in sandstone, mkd. T34N R13E S33 1/4 S4 T33N 2002, Add the marks 2013 to the brass cap.

---

**Survey of a Portion of the  
Third Guide Meridian East (West Boundary),  
T. 34 N., R. 13 E., Gila and Salt River Meridian, Arizona**

---

From the cor. of Tps. 33 and 34 N., R. 13 E. only, monumented with a stainless steel post, 2 1/2 ins. diam., firmly set, projecting 4 ins. above the ground, with brass cap mkd. T34N R12 1/2E R13E S31 S6 T33N 2002 2008. Add the marks S36 2013 to the brass cap.

From this point the 1/4 sec. cor. of sec. 6, T. 33 N., R. 13 E. only, bears South, 40.00 chs. dist., monumented with a stainless steel post, 2 1/2 ins. diam., firmly set, projecting 5 ins. above the ground, with brass cap mkd. T34N T33N R12 1/2E R13E 1/4 S6 2002. Add the marks 2013 to the brass cap.

From this same point the cor. of Tps. 34 and 35 N., R. 12 1/2 E. only, bears North, 436.40 chs. dist., monumented with a stainless steel post, 2 1/2 ins. diam., firmly set, projecting 3 ins. above the ground, with brass cap mkd. T35N T34N R12 1/2E R13E S36 S6 S1 T34N 2010. Add the marks 2013 to the brass cap, from which

A reference monument, bears S. 33°00' W., 33 ft. dist., monumented with a stainless steel post, 2 1/2 ins. diam., firmly set, flush with the ground, mkd. RM T34N R12 1/2E 33.0 FT. TO COR S1 2010 and an arrow pointing to the cor. Add the marks 2013 to the brass cap.

A reference monument, bears N. 53°51' W., 1590.1 ft. dist., monumented with a stainless steel post, 2 1/2 ins. diam., firmly set, flush with the ground, mkd. RM T35N R12 1/2E 1590.1 FT. TO COR S36 2010 and an arrow pointing to the cor. Add the marks 2013 to the brass cap.

North, on the W. bdy. of sec. 31.

Over rolling terrain

Survey of a Portion of the  
Third Guide Meridian East (West Boundary),  
T. 34 N., R. 13 E., Gila and Salt River Meridian, Arizona

CHAINS									
40.00	<p>Point for the 1/4 sec. cor. of sec. 31 only.</p> <p>Set a standard monument, 26 ins. in the ground, mkd.</p> <div style="text-align: center; margin: 10px 0;"> <table style="margin: auto; border-collapse: collapse;"> <tr><td colspan="2">T 34 N</td></tr> <tr><td>R 12 1/2 E</td><td>R 13 E</td></tr> <tr><td></td><td style="border-left: 1px solid black; padding-left: 5px;">1/4</td></tr> <tr><td></td><td style="border-left: 1px solid black; padding-left: 5px;">S 31</td></tr> </table> </div> <p style="text-align: center;">2013</p> <p>Set a steel "T-Post" fence post near cor.</p>	T 34 N		R 12 1/2 E	R 13 E		1/4		S 31
T 34 N									
R 12 1/2 E	R 13 E								
	1/4								
	S 31								
80.00	<p>Point for the cor. of secs. 30 and 31 only.</p> <p>Set a standard monument, 26 ins. in the ground, mkd.</p> <div style="text-align: center; margin: 10px 0;"> <table style="margin: auto; border-collapse: collapse;"> <tr><td colspan="2">T 34 N</td></tr> <tr><td>R 12 1/2 E</td><td>R 13 E</td></tr> <tr><td></td><td style="border-left: 1px solid black; padding-left: 5px;">S 30</td></tr> <tr><td></td><td style="border-left: 1px solid black; padding-left: 5px;">S 31</td></tr> </table> </div> <p style="text-align: center;">2013</p> <p>Set a steel "T-Post" fence post near cor.</p> <p>Land, rolling. Soil, sand. Timber, scattered juniper. Undergrowth, native grasses.</p> <hr style="border: 0.5px solid black; margin: 10px 0;"/> <p>North, on the W. bdy. of sec. 30.</p> <p>Over rolling terrain</p>	T 34 N		R 12 1/2 E	R 13 E		S 30		S 31
T 34 N									
R 12 1/2 E	R 13 E								
	S 30								
	S 31								
40.00	<p>Point for the 1/4 sec. cor. of sec. 30 only.</p> <p>Set a standard monument, 26 ins. in the ground, mkd.</p> <div style="text-align: center; margin: 10px 0;"> <table style="margin: auto; border-collapse: collapse;"> <tr><td colspan="2">T 34 N</td></tr> <tr><td>R 12 1/2 E</td><td>R 13 E</td></tr> <tr><td></td><td style="border-left: 1px solid black; padding-left: 5px;">1/4</td></tr> <tr><td></td><td style="border-left: 1px solid black; padding-left: 5px;">S 30</td></tr> </table> </div> <p style="text-align: center;">2013</p> <p>Set a steel "T-Post" fence post near cor.</p> <p>From this point the most southerly support of a windmill, bears N. 84°56' E., 16.04 chs. dist. The center of a water tank, 25 ft. diam., bears southeasterly, approx. 25 ft. dist. from this southerly support.</p>	T 34 N		R 12 1/2 E	R 13 E		1/4		S 30
T 34 N									
R 12 1/2 E	R 13 E								
	1/4								
	S 30								

Survey of a Portion of the  
Third Guide Meridian East (West Boundary),  
T. 34 N., R. 13 E., Gila and Salt River Meridian, Arizona

CHAINS	
	From this same point the northwest corner of a concrete pad, 6 x 18 ft., 4 ins. high, supporting a water trough, bears N. 86°48' E., 16.89 chs. dist.
80.00	Point for the cor. of secs. 19 and 30 only.  Set a standard monument, 23 ins. in the ground, mkd.  <div style="text-align: center;">           T 34 N            R 12 1/2 E    R 13 E                         S 19                         S 30         </div> 2013  Raise a mound of stone, 4 ft. base, 2 1/2 ft. high, W. of cor.  Land, rolling. Soil, sand and sandstone. Timber, scattered juniper. Undergrowth, native grasses.
	-----
	North, on the W. bdy. of sec. 19.  Over rolling terrain
40.00	Point for the 1/4 sec. cor. of sec. 19 only.  Set a standard monument, 26 ins. in the ground, mkd.  <div style="text-align: center;">           T 34 N            R 12 1/2 E    R 13 E                         1/4                         S 19         </div> 2013  Set a steel "T-Post" fence post near cor.
66.70	Utility line, 2 wire, bears S. 32° E. and N. 32° W.
73.03	Southwest right-of-way fence, bears S. 39° E. and N. 39° W.
75.06	Southwest edge of asphalt of Indian Route 21, 30 ft. wide, bears S. 39° E. and N. 39° W.
75.77	Northeast edge of asphalt of Indian Route 21, bears S. 39° E. and N. 39° W.
77.81	Guardrail near northeast right-of-way, bears S. 39° E. and N. 39° W.

Survey of a Portion of the  
Third Guide Meridian East (West Boundary),  
T. 34 N., R. 13 E., Gila and Salt River Meridian, Arizona

CHAINS									
80.00	<p>Point for the cor. of secs. 18 and 19 only.</p> <p>Set a standard monument, 24 ins. in the ground, mkd.</p> <div style="text-align: center;"> <table style="margin: auto;"> <tr><td colspan="2">T 34 N</td></tr> <tr><td>R 12 1/2 E</td><td>R 13 E</td></tr> <tr><td style="border-right: 1px solid black; border-bottom: 1px solid black;">S 18</td><td></td></tr> <tr><td style="border-right: 1px solid black;">S 19</td><td></td></tr> </table> <p>2013</p> </div> <p>Set a steel "T-Post" fence post near cor.</p> <p>Land, rolling. Soil, sand. Timber, none. Undergrowth, native grasses.</p> <hr/> <p>North, on the W. bdy. of sec. 18.</p> <p>Over rolling terrain</p>	T 34 N		R 12 1/2 E	R 13 E	S 18		S 19	
T 34 N									
R 12 1/2 E	R 13 E								
S 18									
S 19									
40.00	<p>Point for the 1/4 sec. cor. of sec. 18 only.</p> <p>Set a standard monument, 26 ins. in the ground, mkd.</p> <div style="text-align: center;"> <table style="margin: auto;"> <tr><td colspan="2">T 34 N</td></tr> <tr><td>R 12 1/2 E</td><td>R 13 E</td></tr> <tr><td style="border-right: 1px solid black; border-bottom: 1px solid black;">1/4</td><td></td></tr> <tr><td style="border-right: 1px solid black;">S 18</td><td></td></tr> </table> <p>2013</p> </div> <p>Set a steel "T-Post" fence post near cor.</p>	T 34 N		R 12 1/2 E	R 13 E	1/4		S 18	
T 34 N									
R 12 1/2 E	R 13 E								
1/4									
S 18									
58.70	Dirt road, 16 ft. wide, bears N. 60° E. and S. 60° W.								
59.80	Utility line, 2 wire, bears N. 62° E. and S. 62° W.								
80.00	<p>Point for the cor. of secs. 7 and 18 only.</p> <p>Set a standard monument, 28 ins. in the ground, mkd.</p> <div style="text-align: center;"> <table style="margin: auto;"> <tr><td colspan="2">T 34 N</td></tr> <tr><td>R 12 1/2 E</td><td>R 13 E</td></tr> <tr><td style="border-right: 1px solid black; border-bottom: 1px solid black;">S 7</td><td></td></tr> <tr><td style="border-right: 1px solid black;">S 18</td><td></td></tr> </table> <p>2013</p> </div> <p>Set a steel "T-Post" fence post near cor.</p>	T 34 N		R 12 1/2 E	R 13 E	S 7		S 18	
T 34 N									
R 12 1/2 E	R 13 E								
S 7									
S 18									

Survey of a Portion of the  
Third Guide Meridian East (West Boundary),  
T. 34 N., R. 13 E., Gila and Salt River Meridian, Arizona

CHAINS																	
	<p>Land, rolling. Soil, sand. Timber, none. Undergrowth, native grasses.</p> <hr/> <p>North, on the W. bdy. of sec. 7.</p> <p>Over rolling terrain</p>																
40.00	<p>Point for the 1/4 sec. cor. of sec. 7 only.</p> <p>Set a standard monument, 40 ins. in the ground, mkd.</p> <div style="text-align: center; margin: 10px 0;"> <table style="margin: auto; border-collapse: collapse;"> <tr><td colspan="4">T 34 N</td></tr> <tr><td>R 12</td><td>1/2 E</td><td>R 13</td><td>E</td></tr> <tr><td></td><td></td><td> </td><td>1/4</td></tr> <tr><td></td><td></td><td> </td><td>S 7</td></tr> </table> <p>2013</p> </div> <p>Cor. is located in parking area of a residence.</p>	T 34 N				R 12	1/2 E	R 13	E				1/4				S 7
T 34 N																	
R 12	1/2 E	R 13	E														
			1/4														
			S 7														
45.40	<p>Dirt road, 12 ft. wide, bears S. 80° E. and N. 80° W.</p>																
80.00	<p>Point for the cor. of secs. 6 and 7 only.</p> <p>Set a standard monument, 26 ins. in the ground, mkd.</p> <div style="text-align: center; margin: 10px 0;"> <table style="margin: auto; border-collapse: collapse;"> <tr><td colspan="2">T 34 N</td><td colspan="2">T 34 N</td></tr> <tr><td>R 12</td><td>1/2 E</td><td>R 13</td><td>E</td></tr> <tr><td></td><td></td><td> </td><td>S 6</td></tr> <tr><td></td><td></td><td> </td><td>S 7</td></tr> </table> <p>2013</p> </div> <p>Set a steel "T-Post" fence post near cor.</p> <p>Cor. is located S., 5 lks. of the south edge of dirt road, 8 ft. wide, bears E. and W.</p> <p>Land, rolling. Soil, sand. Timber, none. Undergrowth, native grasses.</p> <hr/> <p>North, on the W. bdy. of sec. 6.</p> <p>Over rolling terrain</p>	T 34 N		T 34 N		R 12	1/2 E	R 13	E				S 6				S 7
T 34 N		T 34 N															
R 12	1/2 E	R 13	E														
			S 6														
			S 7														
36.40	<p>The cor. of Tps. 34 and 35 N., R. 12 1/2 E. only</p>																

Survey of a Portion of the  
Third Guide Meridian East (West Boundary),  
T. 34 N., R. 13 E., Gila and Salt River Meridian, Arizona

CHAINS											
40.00	<p>Point for the 1/4 sec. cor. of sec. 6 only.</p> <p>Set a standard monument, 27 ins. in the ground, mkd.</p> <div style="text-align: center;"> <table style="margin: auto;"> <tr> <td>T 35 N</td> <td>T 34 N</td> </tr> <tr> <td>R 12 1/2 E</td> <td>R 13 E</td> </tr> <tr> <td></td> <td style="border-left: 1px solid black; padding-left: 5px;">1/4</td> </tr> <tr> <td></td> <td style="border-left: 1px solid black; padding-left: 5px;">S 6</td> </tr> </table> </div> <p style="text-align: center;">2013</p> <p>Set a steel "T-Post" fence post near cor.</p>	T 35 N	T 34 N	R 12 1/2 E	R 13 E		1/4		S 6		
T 35 N	T 34 N										
R 12 1/2 E	R 13 E										
	1/4										
	S 6										
75.50	Trail road, 8 ft. wide, bears N. 10° E. and S. 30° W.										
80.00	<p>Point for the cor. of Tps. 34 and 35 N., R. 13 E. only.</p> <p>Set a standard monument, 26 ins. in the ground, mkd.</p> <div style="text-align: center;"> <table style="margin: auto;"> <tr> <td>T 35 N</td> <td></td> </tr> <tr> <td>R 12 1/2 E</td> <td>R 13 E</td> </tr> <tr> <td style="border-right: 1px solid black; padding-right: 5px;">S 36</td> <td style="border-bottom: 1px solid black; padding-bottom: 5px;">S 31</td> </tr> <tr> <td></td> <td style="border-bottom: 1px solid black; padding-bottom: 5px;">S 6</td> </tr> <tr> <td>T 34 N</td> <td></td> </tr> </table> </div> <p style="text-align: center;">2013</p> <p>Set a steel "T-Post" fence post near cor.</p> <p>From this same point the cor. of Tps. 35 and 36 N., R. 12 1/2 E. only, bears North, 436.40 chs. dist., monumented with a stainless steel post, 2 1/2 ins. diam., firmly set, projecting 3 ins. above the ground, with brass cap mkd. T36N T35N R12 1/2E R13E S36 S6 S1 T35N 2010. Add the marks 2013 to the brass cap.</p> <p>from which.</p> <p style="padding-left: 40px;">A reference monument, bears S. 22°32' W., 228.7 ft. dist., monumented with a stainless steel post, 2 1/2 ins. diam., firmly set, flush with the ground, mkd. RM T35N R12 1/2E 228.7 FT. TO COR S1 2010 and an arrow pointing to the cor. Add the marks 2013 to the brass cap.</p> <p style="padding-left: 40px;">A reference monument, bears N. 58°41' W., 30.0 ft. dist., monumented with a stainless steel post, 2 1/2 ins. diam., firmly set, flush with the ground, mkd. RM T36N R12 1/2E 29.6 FT. TO COR S36 2010 and an arrow pointing to the cor. Add the marks 2013 to the brass cap.</p>	T 35 N		R 12 1/2 E	R 13 E	S 36	S 31		S 6	T 34 N	
T 35 N											
R 12 1/2 E	R 13 E										
S 36	S 31										
	S 6										
T 34 N											

Survey of a Portion of the  
Third Guide Meridian East (West Boundary),  
T. 34 N., R. 13 E., Gila and Salt River Meridian, Arizona

CHAINS	
	<p>Land, rolling. Soil, sand. Timber, none. Undergrowth, native grasses.</p> <hr/> <p style="text-align: center;">Survey of the East Boundary, T. 34 N., R. 13 E., Gila and Salt River Meridian, Arizona</p> <hr/> <p>From the cor. of Tps. 33 and 34 N., Rs. 13 and 14 E., monumented with a stainless steel post, 2 1/2 ins. diam., firmly set, projecting 1 in. above the ground, with brass cap mkd. T34N R13E R14E S36 S31 S1 S6 T33N 2002. Add the marks 2013 to the brass cap.</p> <p>Cor. is located at the N. edge of a trail road, 8 ft. wide, bears E. and W.</p> <p>North, bet. secs. 31 and 36, on the E. bdy. of the Tp.</p> <p>Over rolling terrain.</p>
40.00	<p>Point for the 1/4 sec. cor. of secs. 31 and 36.</p> <p>Set a standard monument, 34 ins. in the ground, underpinned with an alum. rod, 36 ins. long, 3/4 in. diam., 54 ins. in the ground, mkd.</p> <div style="text-align: center;"> <p>T 34 N R 13 E   R 14 E 1/4 S 36   S 31</p> <p>2013</p> </div> <p>Set a steel "T-Post" fence post near cor.</p> <p>Cor. falls on sand dune.</p>
80.00	<p>Point for the cor. of secs. 25, 30, 31, and 36.</p> <p>Set a standard monument, 26 ins. in the ground, mkd.</p> <div style="text-align: center;"> <p>T 34 N R 13 E   R 14 E S 25   S 30 S 36   S 31</p> <p>2013</p> </div> <p>Set a steel "T-Post" fence post near cor.</p>

Survey of the East Boundary,  
T. 34 N., R. 13 E., Gila and Salt River Meridian, Arizona

CHAINS	
	<p>Land, rolling. Soil, sand. Timber, none. Undergrowth, native grasses.</p> <hr/> <p>North, bet. secs. 25 and 30.</p> <p>Over rolling terrain.</p>
40.00	<p>Point for the 1/4 sec. cor. of secs. 25 and 30.</p> <p>Set a standard monument, 28 ins. in the ground, underpinned with an alum. rod, 36 ins. long, 3/4 in. diam., 50 ins. in the ground, mkd.</p> <div style="text-align: center;"> <p>T 34 N R 13 E R 14 E 1/4 S 25   S 30</p> <p>2013</p> </div> <p>Set a steel "T-Post" fence post near cor.</p> <p>Cor. falls on an easterly slope.</p>
80.00	<p>Point for the cor. of secs. 19, 24, 25, and 30.</p> <p>Set a standard monument, 28 ins. in the ground, mkd.</p> <div style="text-align: center;"> <p>T 34 N R 13 E   R 14 E S 24   S 19 S 25   S 30</p> <p>2013</p> </div> <p>Set a steel "T-Post" steel fence post near cor.</p> <p>Land, rolling. Soil, sand. Timber, none. Undergrowth, native grasses.</p> <hr/> <p>North, bet. secs. 19 and 24.</p> <p>Over rolling terrain.</p>
28.40	<p>Indian Route 6011, graded road, 20 ft. wide, bears N. 75° E. and S. 75° W.</p>



Survey of the East Boundary,  
T. 34 N., R. 13 E., Gila and Salt River Meridian, Arizona

CHAINS	
40.00	<p>Point for the 1/4 sec. cor. of secs. 19 and 24.</p> <p>Set a standard monument, 24 ins. in the ground, mkd.</p> <div style="text-align: center; margin: 10px 0;">                     T 34 N                      R 13 E   R 14 E                      1/4                      S 24   S 19                 </div> <p style="text-align: center; margin: 5px 0;">2013</p> <p>Set a steel "T-Post" fence post near cor.</p>
78.75	<p>Trail road, 9 ft. wide, bears S. 30° E. and N. 30° W.</p>
80.00	<p>Point for the cor. of secs. 13, 18, 19, and 24.</p> <p>Set a standard monument, 28 ins. in the ground, mkd.</p> <div style="text-align: center; margin: 10px 0;">                     T 34 N                      R 13 E   R 14 E                      S 13   S 18  <hr style="width: 50%; margin: 0 auto;"/>                     S 24   S 19                 </div> <p style="text-align: center; margin: 5px 0;">2013</p> <p>Set a steel "T-Post" steel fence post near cor.</p> <p>Land, rolling. Soil, sand. Timber, none. Undergrowth, native grasses.</p> <hr style="width: 80%; margin: 10px auto;"/> <p>North, bet. secs. 13 and 18.</p> <p>Over rolling terrain.</p>
40.00	<p>Point for the 1/4 sec. cor. of secs. 13 and 18.</p> <p>Set a standard monument, 27 ins. in the ground, mkd.</p> <div style="text-align: center; margin: 10px 0;">                     T 34 N                      R 13 E   R 14 E                      1/4                      S 13   S 18                 </div> <p style="text-align: center; margin: 5px 0;">2013</p> <p>Set a steel "T-Post" steel fence post near cor.</p> <p>Cor. is located S., 75 lks. of a wash, 5 ft. wide, drains W.</p>

Survey of the East Boundary,  
T. 34 N., R. 13 E., Gila and Salt River Meridian, Arizona

CHAINS	
77.80	Utility line, 2 wire, bears S. 61° E. and N. 61° W.
80.00	<p>Point for the cor. of secs. 7, 12, 13, and 18, falls in wash, 10 ft. wide, drains S. 40° W.</p> <p>Set a 60D nail.</p> <p>from which</p> <p style="padding-left: 40px;">A stainless steel post, 28 ins. long, 2 1/2 ins. diam., set 25 ins. in the ground, for a reference monument, bears S. 45°00' E., 120.0 ft. chs. dist., with brass cap mkd. RM T34N R14E 120.0 FT. TO COR S18 2013 and an arrow pointing to the cor. Deposit a magnet, in a white plastic case, at the base of the stainless steel post. Set a steel "T-Post" near the reference monument.</p> <p style="padding-left: 40px;">A stainless steel post, 28 ins. long, 2 1/2 ins. diam., set 26 ins. in the ground, for a reference monument, bears N. 45°00' W., 170.0 ft. chs. dist., with brass cap mkd. RM T34N R13E S12 170.0 FT. TO COR. 2013 with an arrow pointing to the cor. Deposit a magnet, in a white plastic case, at the base of the stainless steel post. Set a steel "T-Post" near the reference monument.</p> <p>Cor. is located E., 60 lks., of a trail road, 8 ft. wide, bears N. 10° E. and S. 10° W.</p> <p>Land, rolling. Soil, sand. Timber, none. Undergrowth, native grasses.</p> <hr/> <p>North, bet. secs. 7 and 12.</p> <p>Over rolling terrain.</p>
40.00	<p>Point for the 1/4 sec. cor. of secs. 7 and 12., falls in dirt road, 9 ft. wide, bears N. 15° E. and S. 15° W.</p> <p>Set a standard monument, 43 ins. in the ground, mkd.</p> <p style="text-align: center;">T 34 N R 13 E R 14 E 1/4 S 12   S 7 2013</p>

Survey of the East Boundary,  
T. 34 N., R. 13 E., Gila and Salt River Meridian, Arizona

CHAINS									
	<p>from which</p> <p style="padding-left: 40px;">A stainless steel post, 28 ins. long, 2 1/2 ins. diam., set 26 ins. in the ground, for a reference monument, bears S. 55°00' E., 30.0 ft. dist., with brass cap mkd. RM T34N R14E 30.0 FT. TO 1/4 COR S7 2013 and an arrow pointing to the cor. Deposit a magnet, in a white plastic case, at the base of the stainless steel post. Set a steel "T-Post" near the reference monument.</p> <p style="padding-left: 40px;">A stainless steel post, 28 ins. long, 2 1/2 ins. diam., set 24 ins. in the ground, for a reference monument, bears N. 55°00' W., 50.0 ft. dist., with brass cap mkd. RM T34N R13E S12 50.0 FT. TO 1/4 COR. 2013 with an arrow pointing to the cor. Deposit a magnet, in a white plastic case, at the base of the stainless steel post. Set a steel "T-Post" near the reference monument.</p>								
49.05	<p>Questar Southern Trails underground gas pipeline, bears N. 35° E. and S. 35° W.</p>								
80.00	<p>Point for the cor. of secs. 1, 6, 7, and 12.</p> <p>Set a standard monument, 28 ins. in the ground, underpinned with a steel "T-Post" fence post, 70 ins. long, 88 ins. in the ground, mkd.</p> <div style="text-align: center; margin: 20px 0;"> <table style="margin: auto; border-collapse: collapse;"> <tr> <td colspan="2" style="padding: 0 10px;">T 34 N</td> </tr> <tr> <td style="padding: 0 5px;">R 13 E</td> <td style="border-left: 1px solid black; padding: 0 5px;">R 14 E</td> </tr> <tr> <td style="padding: 0 5px;">S 1</td> <td style="border-left: 1px solid black; padding: 0 5px;">S 6</td> </tr> <tr> <td style="padding: 0 5px;">S 12</td> <td style="border-left: 1px solid black; padding: 0 5px;">S 7</td> </tr> </table> <p style="margin-top: 5px;">2013</p> </div> <p>Set steel "T-Post" fence post near cor.</p> <p>Land, rolling. Soil, sand. Timber, none. Undergrowth, native grasses.</p> <hr style="width: 60%; margin: 20px auto;"/> <p>North, bet. secs. 1 and 6.</p> <p>Over rolling terrain.</p>	T 34 N		R 13 E	R 14 E	S 1	S 6	S 12	S 7
T 34 N									
R 13 E	R 14 E								
S 1	S 6								
S 12	S 7								
40.00	<p>Point for the 1/4 sec. cor. of secs. 1 and 6.</p> <p>Set a standard monument, 28 ins. in the ground, underpinned with an alum. rod, 36 ins. long, 3/4 in. diam., 48 ins. in the ground, mkd.</p>								

**Survey of the East Boundary,  
T. 34 N., R. 13 E., Gila and Salt River Meridian, Arizona**

CHAINS	<p style="text-align: center;">T 34 N R 13 E R 14 E 1/4 S 1   S 6  2013</p> <p>Set a steel "T-Post" fence post near cor.</p> <p>From this point an Arizona DOT right-of-way monument, bears N. 2°21' W., 21.14 chs. dist., monumented with a brass tablet, 3 1/2 ins. diam., set in concrete, 8 ins. diam., projecting 6 ins. above the ground, with a 4 in. angle iron, projecting 15 ins. above the ground nearby.</p> <p>62.56 Southeast right-of-way fence, bears N. 30° E. and S. 30° W.</p> <p>64.97 Southeast edge of asphalt of Highway No. 160, 38 ft. wide, bears N. 30° E. and S. 30° W.</p> <p>66.09 Northwest edge of asphalt of Highway No. 160, bears N. 30° E. and S. 30° W.</p> <p>71.45 Northwest right-of-way fence, bears N. 30° E. and S. 30° W.</p> <p>80.00 Point for the cor. of Tps. 34 and 35 N., Rs. 13 and 14 E.</p> <p>Set a standard monument, 26 ins. in the ground, mkd.</p> <p style="text-align: center;">T 35 N R 13 E   R 14 E S 36   S 31 ----- S 1   S 6 T 34 N  2013</p> <p>Set steel "T-Post" fence post near cor.</p> <p>Land, level. Soil, sand. Timber, none. Undergrowth, native grasses.</p> <hr/> <p style="text-align: center;"><b>Survey of the North Boundary, T. 34 N., R. 13 E., Gila and Salt River Meridian, Arizona</b></p> <hr/> <p>From the cor. of Tps. 34 and 35 N., Rs. 13 and 14 E., hereinbefore described.</p> <p>West, bet. secs. 1 and 36.</p>
--------	--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------

Survey of the North Boundary,  
T. 34 N., R. 13 E., Gila and Salt River Meridian, Arizona

CHAINS									
	Over rolling terrain.								
40.00	<p>Point for the 1/4 sec. cor. of secs. 1 and 36, falls in wash, 6 ft. wide, drains S. 50° E.</p> <p>Set a rebar, 7 1/2 ins. long, 5/8 in. diam., 7 ins. in the ground.</p> <p>from which</p> <p style="padding-left: 40px;">A stainless steel post, 28 ins. long, 2 1/2 ins. diam., set 26 ins. in the ground, for a reference monument, bears N. 59°58' E., 85.0 ft. dist., with brass cap mkd. RM T35N R13E 85.0 FT. TO 1/4 COR S36 2013 and an arrow pointing to the cor. Deposit a magnet, in a white plastic case, at the base of the stainless steel post. Set a steel "T-Post" near the reference monument.</p> <p style="padding-left: 40px;">A stainless steel post, 28 ins. long, 2 1/2 ins. diam., set 28 ins. in the ground, for a reference monument, bears S. 30°00' E., 75.0 ft. dist., with brass cap mkd. RM T34N R13E S1 75.0 FT. TO 1/4 COR. 2013 with an arrow pointing to the cor. Deposit a magnet, in a white plastic case, at the base of the stainless steel post. Set a steel "T-Post" near the reference monument.</p>								
80.00	<p>Point for the cor. of secs. 1, 2, 35, and 36.</p> <p>Set a standard monument, 24 ins. in the ground, mkd.</p> <div style="text-align: center; margin: 10px 0;"> <table style="margin: auto; border-collapse: collapse;"> <tr> <td style="padding: 0 10px;">T 35 N</td> <td style="padding: 0 10px;">R 13 E</td> </tr> <tr> <td style="padding: 0 10px; border-right: 1px solid black;">S 35</td> <td style="padding: 0 10px;">S 36</td> </tr> <tr> <td style="padding: 0 10px; border-right: 1px solid black;">S 2</td> <td style="padding: 0 10px;">S 1</td> </tr> <tr> <td colspan="2" style="padding: 0 10px;">T 34 N</td> </tr> </table> <p style="margin-top: 5px;">2013</p> </div> <p>Set a steel "T-Post" fence post near cor.</p> <p>Land, rolling. Soil, sand. Timber, none. Undergrowth, native grasses.</p> <hr style="width: 60%; margin: 10px auto;"/> <p>West, bet. secs. 2 and 35.</p> <p>Over rolling terrain.</p>	T 35 N	R 13 E	S 35	S 36	S 2	S 1	T 34 N	
T 35 N	R 13 E								
S 35	S 36								
S 2	S 1								
T 34 N									
40.00	<p>Point for the 1/4 sec. cor. of secs. 2 and 35.</p>								

Survey of the North Boundary,  
T. 34 N., R. 13 E., Gila and Salt River Meridian, Arizona

CHAINS	<p>Set a standard monument, 28 ins. in the ground, underpinned with an alum. rod, 36 ins. long, 3/4 in. diam., 48 ins. in the ground, mkd.</p> <p style="text-align: center;">T 35 N R 13 E S 35 1/4 ——— S 2 T 34 N</p> <p style="text-align: center;">2013</p> <p>Set a steel "T-Post" fence post near cor.</p> <p>70.40 Utility line, 2 wire, bears S. 50° E. and N. 50° W.</p> <p>80.00 Point for the cor. of secs. 2, 3, 34, and 35, falls in the center of a dirt road, 8 ft. wide, bears S. 35° E. and N. 35° W.</p> <p>Set a standard monument, 36 ins. in the ground, mkd.</p> <p style="text-align: center;">T 35 N R 13 E S 34   S 35 S 3   S 2 T 34 N</p> <p style="text-align: center;">2013</p> <p>from which</p> <p style="padding-left: 40px;">A stainless steel post, 28 ins. long, 2 1/2 ins. diam., set 26 ins. in the ground, for a reference monument, bears S. 59°56' E., 35.0 ft. dist., with brass cap mkd. RM T34N R13E 35.0 FT. TO COR S2 2013 and an arrow pointing to the cor. Deposit a magnet, in a white plastic case, at the base of the stainless steel post. Set a steel "T-Post" near the reference monument.</p> <p style="padding-left: 40px;">A stainless steel post, 28 ins. long, 2 1/2 ins. diam., set 25 ins. in the ground, for a reference monument, bears S. 30°00' W., 34.0 ft. dist., with brass cap mkd. RM T34N R13E 34.0 FT. TO COR. S3 2013 with an arrow pointing to the cor. Deposit a magnet, in a white plastic case, at the base of the stainless steel post. Set a steel "T-Post" near the reference monument.</p> <p>Land, rolling. Soil, sand. Timber, none. Undergrowth, native grasses.</p> <hr style="width: 60%; margin-left: 0;"/> <p>West, bet. secs. 3 and 34.</p>
--------	-----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------

Survey of the North Boundary,  
T. 34 N., R. 13 E., Gila and Salt River Meridian, Arizona

CHAINS	
	Over rolling terrain.
40.00	Point for the 1/4 sec. cor. of secs. 3 and 34.  Set a standard monument, 28 ins. in the ground, mkd.  <div style="text-align: center;">           T 35 N R 13 E                  S 34              1/4 ———                  S 3            T 34 N             2013         </div>
80.00	Set a steel "T-Post" fence post near cor.  Point for the cor. of secs. 3, 4, 33, and 34.  Set a standard monument, 28 ins. in the ground, mkd.  <div style="text-align: center;">           T 35 N R 13 E            S 33   S 34            ——— ———            S 4   S 3            T 34 N             2013         </div>
	Set a steel "T-Post" fence post near cor.  Land, rolling. Soil, sand. Timber, none. Undergrowth, native grasses.
	West, bet. secs. 4 and 33.
	Over rolling terrain.
22.00	Dirt road, 10 ft. wide, bears N. 15° E. and S. 15° W.
40.00	Point for the 1/4 sec. cor. of secs. 4 and 33.  Set a standard monument, 26 ins. in the ground, mkd.  <div style="text-align: center;">           T 35 N R 13 E                  S 33              1/4 ———                  S 4            T 34 N             2013         </div>

Survey of the North Boundary,  
T. 34 N., R. 13 E., Gila and Salt River Meridian, Arizona

CHAINS											
80.00	<p>Set a steel "T-Post" fence post near cor.</p> <p>Point for the cor. of secs. 4, 5, 32, and 33.</p> <p>Set a standard monument, 28 ins. in the ground, mkd.</p> <div style="text-align: center; margin: 10px 0;"> <table style="margin: auto; border-collapse: collapse;"> <tr> <td style="padding: 0 5px;">T 35 N</td> <td style="padding: 0 5px;">R 13 E</td> </tr> <tr> <td style="padding: 0 5px; border-right: 1px solid black;">S 32</td> <td style="padding: 0 5px;">S 33</td> </tr> <tr> <td style="padding: 0 5px; border-right: 1px solid black;">S 5</td> <td style="padding: 0 5px;">S 4</td> </tr> <tr> <td colspan="2" style="padding: 0 5px;">T 34 N</td> </tr> </table> <p style="margin: 5px 0;">2013</p> </div> <p>Set a steel "T-Post" fence post near cor.</p> <p>Land, rolling. Soil, sand. Timber, none. Undergrowth, native grasses.</p> <hr style="border: 0.5px solid black; margin: 10px 0;"/> <p>West, bet. secs. 5 and 32.</p> <p>Over rolling terrain.</p>	T 35 N	R 13 E	S 32	S 33	S 5	S 4	T 34 N			
T 35 N	R 13 E										
S 32	S 33										
S 5	S 4										
T 34 N											
32.05	<p>Indian Route 6261, graded road, 27 ft. wide, bears S. 22° E. and N. 22° W.</p>										
40.00	<p>Point for the 1/4 sec. cor. of secs. 5 and 32.</p> <p>Set a standard monument, 25 ins. in the ground, mkd.</p> <div style="text-align: center; margin: 10px 0;"> <table style="margin: auto; border-collapse: collapse;"> <tr> <td style="padding: 0 5px;">T 35 N</td> <td style="padding: 0 5px;">R 13 E</td> </tr> <tr> <td style="padding: 0 5px;"></td> <td style="padding: 0 5px;">S 32</td> </tr> <tr> <td style="padding: 0 5px;">1/4</td> <td style="padding: 0 5px;">—</td> </tr> <tr> <td style="padding: 0 5px;"></td> <td style="padding: 0 5px;">S 5</td> </tr> <tr> <td colspan="2" style="padding: 0 5px;">T 34 N</td> </tr> </table> <p style="margin: 5px 0;">2013</p> </div> <p>Set a steel "T-Post" fence post near cor.</p>	T 35 N	R 13 E		S 32	1/4	—		S 5	T 34 N	
T 35 N	R 13 E										
	S 32										
1/4	—										
	S 5										
T 34 N											
42.95	<p>Trail road, 8 ft. wide, bears N. 40° E. and S. 35° W.</p>										
49.85	<p>Utility line, 2 wire, bears S. 17° E. and N. 17° W.</p>										
80.00	<p>Point for the cor. of secs. 5, 6, 31, and 32.</p> <p>Set a standard monument, 26 ins. in the ground, mkd.</p>										



**Survey of the North Boundary,  
T. 34 N., R. 13 E., Gila and Salt River Meridian, Arizona**

CHAINS	
	T 35 N R 13 E S 31   S 32 ----- S 6   S 5 T 34 N  2013
	Set a steel "T-Post" fence post near cor.
	Land, rolling. Soil, sand. Timber, none. Undergrowth, native grasses.
	-----
	West, bet. secs. 6 and 31.
	Over rolling terrain.
40.00	Point for the 1/4 sec. cor. of secs. 6 and 31.
	Set a standard monument, 26 ins. in the ground, mkd.
	T 35 N R 13 E S 31 1/4 ----- S 6 T 34 N  2013
	Set a steel "T-Post" fence post near cor.
76.25	Trail road, 9 ft. wide, bears S. 40° E. and N. 35° W.
76.95	Trail road, 8 ft. wide, bears N. 5° E. and S. 5° W.
78.945	The cor. of Tps. 34 and 35 N., R. 13 E. only, hereinbefore described.
	-----
	<b>Survey of the Subdivisional Lines, T. 34 N., R. 13 E., Gila and Salt River Meridian, Arizona</b>
	-----
	From the cor. of secs. 1, 2, 35, and 36, on the S. bdy. of the Tp., monumented with a stainless steel post, 2 1/2 ins. diam., firmly set, flush with the ground, with brass cap mkd. T34N R13E S35 S36 S2 S1 T33N 2002. Add the marks 2013 to the brass cap.
	Set a steel "T-Post" fence post near cor.

Survey of the Subdivisional Lines,  
T. 34 N., R. 13 E., Gila and Salt River Meridian, Arizona

CHAINS	
	N. 0°01' W., bet. secs. 35 and 36. Over rolling terrain.
39.85	Trail road, 8 ft. wide, bears N. 75° E. and S. 75° W.
40.00	Point for the 1/4 sec. cor. of secs. 35 and 36. Set a standard monument, 26 ins. in the ground, mkd.  <div style="text-align: center;">           T 34 N R 13 E                  1/4            S 35   S 36              2013         </div>
	Set a steel "T-Post" fence post near cor.
80.00	Point for the cor. of secs. 25, 26, 35, and 36. Set a standard monument, 26 ins. in the ground, mkd.  <div style="text-align: center;">           T 34 N R 13 E            S 26   S 25            S 35   S 36              2013         </div>
	Set a steel "T-Post" fence post near cor.  Land, rolling. Soil, sand. Timber, none. Undergrowth, native grasses.
	From the cor. of secs. 25, 30, 31, and 36, on the E. bdy of the Tp., hereinbefore described.  West, bet. secs. 25 and 36.  Over rolling terrain.
40.00	Point for the 1/4 sec. cor. of secs. 25 and 36. Set a standard monument, 26 ins. in the ground, mkd.  <div style="text-align: center;">           T 34 N R 13 E                  S 25            1/4 ———                  S 36              2013         </div>

Survey of the Subdivisional Lines,  
T. 34 N., R. 13 E., Gila and Salt River Meridian, Arizona

CHAINS	
	Set a steel "T-Post" fence post near cor.
60.60	Indian Route 214, graded road, 14 ft. wide, bears N. 20° E. and S. 25° W.
80.00	The cor. of secs. 25, 26, 35, and 36.
	Land, rolling. Soil, sand. Timber, none. Undergrowth, native grasses.
	<hr/>
	N. 0°01' W., bet. secs. 25 and 26.
	Over rolling terrain.
40.00	Point for the 1/4 sec. cor. of secs. 25 and 26.
	Set a standard monument, 26 ins. in the ground, mkd.
	T 34 N R 13 E 1/4 S 26   S 25  2013
	Set a steel "T-Post" fence post near cor.
80.00	Point for the cor. of secs. 23, 24, 25, and 26.
	Set a standard monument, 26 ins. in the ground, mkd.
	T 34 N R 13 E S 23   S 24 S 26   S 25  2013
	Set a steel "T-Post" fence post near cor.
	Land, rolling. Soil, sand. Timber, none. Undergrowth, native grasses.
	<hr/>
	From the cor. of secs. 19, 24, 25, and 30 on the E. bdy. of the Tp., hereinbefore described.
	West, bet. secs. 24 and 25.
	Over rolling terrain.

Survey of the Subdivisional Lines,  
T. 34 N., R. 13 E., Gila and Salt River Meridian, Arizona

CHAINS	
40.00	<p>Point for the 1/4 sec. cor. of secs. 24 and 25.</p> <p>Set a standard monument, 26 ins. in the ground, mkd.</p> <p style="text-align: center;">T 34 N R 13 E S 24 1/4 ——— S 25</p> <p style="text-align: center;">2013</p> <p>Set a steel "T-Post" fence post near cor.</p>
54.45	<p>Indian Route 214, graded road, 33 ft. wide, bears N. 20° E. and S. 20° W.</p>
80.00	<p>The cor. of secs. 23, 24, 25, and 26.</p> <p>Land, rolling. Soil, sand. Timber, none. Undergrowth, native grasses.</p> <hr/> <p>N. 0°01' W., bet. secs. 23 and 24.</p> <p>Over rolling terrain.</p>
1.55	<p>Wash, 6 ft. wide, drains S. 75° W.</p>
23.50	<p>Indian Route 6011, graded road, 20 ft. wide, bears S. 52° E. and N. 52° W.</p>
40.00	<p>Point for the 1/4 sec. cor. of secs. 23 and 24.</p> <p>Set a standard monument, 26 ins. in the ground, mkd.</p> <p style="text-align: center;">T 34 N R 13 E 1/4 S 23   S 24</p> <p style="text-align: center;">2013</p> <p>Set a steel "T-Post" fence post near cor.</p>
80.00	<p>Point for the cor. of secs. 13, 14, 23, and 24.</p> <p>Set a standard monument, 28 ins. in the ground, mkd.</p>

Survey of the Subdivisional Lines,  
T. 34 N., R. 13 E., Gila and Salt River Meridian, Arizona

CHAINS	
	T 34 N R 13 E S 14   S 13 S 23   S 24 2013
	Set a steel "T-Post" fence post near cor.  Land, rolling. Soil, sand. Timber, none. Undergrowth, native grasses.
	<hr/> From the cor. of secs. 13, 18, 19, and 24, on the E. bdy. of the Tp., hereinbefore described.  West bet. secs. 13 and 24.
0.85	Trail road, 8 ft. wide, bears S. 35° E. and N. 35° W.  Over rolling terrain.
40.00	Point for the 1/4 sec. cor. of secs. 13 and 24.  Set a standard monument, 26 ins. in the ground, encircled in a collar of stone, mkd.
	T 34 N R 13 E S 13 1/4 ——— S 24 2013
	Set a steel "T-Post" fence post near cor.  Cor. is located N., 83 lks. dist. of a trail road, 8 ft. wide, bears easterly and westerly.
77.65	Trail road, 9 ft. wide, bears S. 30° E. and N. 30° W.
80.00	The cor. of secs. 13, 14, 23, and 24.  Land, rolling. Soil, sand. Timber, none. Undergrowth, native grasses.
	<hr/> N. 0°01' W., bet. secs. 13 and 14.  Over rolling terrain.

Survey of the Subdivisional Lines,  
T. 34 N., R. 13 E., Gila and Salt River Meridian, Arizona

CHAINS	
14.00	<p>Questar Southern Trails underground gas pipeline, bears N. 35° E. and S. 35° W.</p>
40.00	<p>Point for the 1/4 sec. cor. of secs. 13 and 14.</p> <p>Set a standard monument, 26 ins. in the ground, underpinned with an alum. rod, 36 ins. long, 3/4 in. diam., 54 ins. in the ground mkd.</p> <p style="text-align: center;">T 34 N R 13 E 1/4 S 14   S 13</p> <p style="text-align: center;">2013</p> <p>Set a steel "T-Post" fence post near cor.</p> <p>Cor. is located in a flood plain.</p>
80.00	<p>Point for the cor. of secs. 11, 12, 13, and 14.</p> <p>Set a standard monument, 26 ins. in the ground, mkd.</p> <p style="text-align: center;">T 34 N R 13 E S 11   S 12 S 14   S 13</p> <p style="text-align: center;">2013</p> <p>Set a steel "T-Post" fence post near cor.</p> <p>From this point an Arizona DOT right-of-way monument, bears N. 13°11' E. 13.824 chs. dist., monumented with a brass tablet, 3 1/2 ins. diam., set in concrete, 8 ins. diam., projecting 6 ins. above the ground, with a 4 in. angle iron, projecting 15 ins. above the ground nearby.</p> <p>From this same point an Arizona DOT right-of-way monument, bears N. 02°41' W. 15.82 chs. dist., monumented with a brass tablet, 3 1/2 ins. diam., set in concrete, 8 ins. diam., projecting 6 ins. above the ground, with a 4 in. angle iron, projecting 15 ins. above the ground nearby.</p> <p>Land, rolling. Soil, sand. Timber, none. Undergrowth, native grasses.</p> <hr/> <p>From the cor. of secs. 7, 12, 13, and 18, on the E. bdy. of the Tp., hereinbefore described.</p> <p>West, bet. secs. 12 and 13.</p>

Survey of the Subdivisional Lines,  
T. 34 N., R. 13 E., Gila and Salt River Meridian, Arizona

CHAINS	
34.10	Questar Southern Trails underground gas pipeline, bears N. 35° E. and S. 35° W.
40.00	Point for the 1/4 sec. cor. of secs. 12 and 13. Set a standard monument, 26 ins. in the ground, mkd.  <div style="text-align: center;">           T 34 N R 13 E                      S 12                  1/4 ———                      S 13             2013         </div> Set a steel "T-Post" fence post near cor.
80.00	The cor. of secs. 11, 12, 13, and 14.  Land, rolling. Soil, sand. Timber, none. Undergrowth, native grasses. <hr/> N. 0°01' W., bet. secs. 11 and 12.  Over rolling terrain.
8.18	Southeast right-of-way fence, bears N. 30° E. and S. 30° W.
10.57	Southeast edge of asphalt of Highway No. 160, 38 ft. wide, bears N. 30° E. and S. 30° W.
11.67	Northwest edge of asphalt of Highway No. 160, bears N. 30° E. and S. 30° W.
17.04	Northwest right-of-way fence, bears N. 30° E. and S. 30° W.
40.00	Point for the 1/4 sec. cor. of secs. 11 and 12. Set a standard monument, 26 ins. in the ground, mkd.  <div style="text-align: center;">           T 34 N R 13 E                      1/4                  S 11   S 12             2013         </div> Set a steel "T-Post" fence post near cor.

**Survey of the Subdivisional Lines,  
T. 34 N., R. 13 E., Gila and Salt River Meridian, Arizona**

CHAINS									
	<p>From this point an Arizona DOT right-of-way monument, bears N. 87°47' E. 13.996 chs. dist., monumented with a brass tablet, 3 1/2 ins. diam., set in concrete, 8 ins. diam., projecting 6 ins. above the ground, with a 4 in. angle iron, projecting 15 ins. above the ground nearby.</p> <p>From this same point an Arizona DOT right-of-way monument, bears S. 84°17' E., 17.977 chs. dist., monumented with a brass tablet, 3 1/2 ins. diam., set in concrete, 8 ins. diam., projecting 6 ins. above the ground, with a 4 in. angle iron, projecting 15 ins. above the ground nearby.</p>								
80.00	<p>Point for the cor. of secs. 1, 2, 11, and 12.</p> <p>Set a standard monument, 26 ins. in the ground, mkd.</p> <div style="text-align: center;"> <table style="margin: auto;"> <tr> <td>T 34 N</td> <td>R 13 E</td> </tr> <tr> <td style="border-right: 1px solid black;">S 2</td> <td>S 1</td> </tr> <tr> <td style="border-right: 1px solid black;">S 11</td> <td>S 12</td> </tr> </table> <p>2013</p> </div> <p>Set a steel "T-Post" fence post near cor.</p> <p>Land, rolling. Soil, sand. Timber, none. Undergrowth, native grasses.</p> <hr/> <p>From the cor. of secs. 1, 6, 7, and 12, on the E. bdy. of the Tp., hereinbefore described.</p> <p>West, bet. secs. 1 and 12.</p>	T 34 N	R 13 E	S 2	S 1	S 11	S 12		
T 34 N	R 13 E								
S 2	S 1								
S 11	S 12								
37.22	Southeast right-of-way fence, bears N. 22° E. and S. 22° W.								
38.68	Southeast edge of asphalt of Highway No. 160, 42 ft. wide, bears N. 30° E. and S. 30° W.								
39.33	Northwest edge of asphalt of Highway No. 160, bears N. 30° E. and S. 30° W.								
40.00	<p>Point for the 1/4 sec. cor. of secs. 1 and 12.</p> <p>Set a standard monument, 26 ins. in the ground, mkd.</p> <div style="text-align: center;"> <table style="margin: auto;"> <tr> <td>T 34 N</td> <td>R 13 E</td> </tr> <tr> <td></td> <td>S 1</td> </tr> <tr> <td>1/4</td> <td>—</td> </tr> <tr> <td></td> <td>S 12</td> </tr> </table> <p>2013</p> </div>	T 34 N	R 13 E		S 1	1/4	—		S 12
T 34 N	R 13 E								
	S 1								
1/4	—								
	S 12								



Survey of the Subdivisional Lines,  
T. 34 N., R. 13 E., Gila and Salt River Meridian, Arizona

CHAINS	
	Set a steel "T-Post" fence post near cor.
	From this point, a Coast and Geodetic benchmark, bears N. 81°47' E., 3.18 chs. dist., monumented with a brass tablet set in concrete pad, 9 x 9 ins., 3 ins. high, mkd. U-49 1934.
42.51	Northwest right-of-way fence, bears N. 30° E. and S. 30° W.
80.00	The cor. of secs. 1, 2, 11, and 12.
	Land, rolling. Soil, sand. Timber, none. Undergrowth, native grasses.
	<hr/>
	N. 0°01' W., bet. secs. 1 and 2.
	Over rolling terrain.
2.10	Utility line, 2 wire, bears N. 21° E. and S. 21° W.
33.60	Utility line, 2 wire, bears S. 60° E. and N. 60° W.
40.00	Point for the 1/4 sec. cor. of secs. 1 and 2.
	Set a standard monument, 26 ins. in the ground, mkd.
	T 34 N R 13 E 1/4 S 2   S 1  2013
	Set a steel "T-Post" fence post near cor.
80.00	The cor. of secs. 1, 2, 35, and 36, on the N. bdy. Of the Tp., hereinbefore described.
	Land, rolling. Soil, sand. Timber, none. Undergrowth, native grasses.
	<hr/>
	From the cor. of secs. 2, 3, 34, and 35, on the S. bdy. of the Tp., hereinbefore described.
	Add the marks 2013 to the brass cap.
	N. 0°01' W., bet. secs. 34 and 35.

Survey of the Subdivisional Lines,  
T. 34 N., R. 13 E., Gila and Salt River Meridian, Arizona

CHAINS	<p>Over rolling terrain.</p>
40.00	<p>Point for the 1/4 sec. cor. of secs. 34 and 35.</p> <p>Set a standard monument, 26 ins. in the ground, underpinned with an alum. rod, 72 ins. long, 3/4 in. diam., 88 ins. in the ground, mkd.</p> <p style="text-align: center;">T 34 N R 13 E 1/4 S 34   S 35</p> <p style="text-align: center;">2013</p>
77.55	<p>Set a steel "T-Post" fence post near cor.</p> <p>Dirt road, 8 ft. wide, bears S. 40° E. and N. 40° W.</p>
80.00	<p>Point for the cor. of secs. 26, 27, 34, and 35.</p> <p>Set a standard monument, 26 ins. in the ground, mkd.</p> <p style="text-align: center;">T 34 N R 13 E S 27   S 26 S 34   S 35</p> <p style="text-align: center;">2013</p>
	<p>Set a steel "T-Post" fence post near cor.</p> <p>Land, rolling. Soil, sand. Timber, none. Undergrowth, native grasses.</p> <hr/> <p>From the cor. of secs. 25, 26, 35, and 36.</p> <p>West, bet. secs. 26 and 35.</p> <p>Over rolling terrain.</p>
40.00	<p>Point for the 1/4 sec. cor. of secs. 26 and 35.</p> <p>Set a standard monument, 24 ins. in the ground, encircled in a collar of stone, mkd.</p> <p style="text-align: center;">T 34 N R 13 E S 26 1/4 ——— S 35</p> <p style="text-align: center;">2013</p>

Survey of the Subdivisional Lines,  
T. 34 N., R. 13 E., Gila and Salt River Meridian, Arizona

CHAINS	
80.00	<p>Set a steel "T-Post" fence post near cor.</p> <p>The cor. of secs. 26, 27, 34, and 35.</p> <p>Land, rolling. Soil, sand. Timber, none. Undergrowth, native grasses.</p> <hr/> <p>N. 0°01' W., bet. secs. 26 and 27.</p> <p>Over rolling terrain.</p>
40.00	<p>Point for the 1/4 sec. cor. of secs. 26 and 27.</p> <p>Set a standard monument, 28 ins. in the ground, mkd.</p> <p style="text-align: center;">T 34 N R 13 E 1/4 S 27   S 26  2013</p> <p>Cor. is located W., 2 lks. dist. of a dirt road, 8 ft. wide, bears S. 10° E. and N. 10° W.</p>
58.95	<p>Questar Southern Trails underground gas pipeline, bears N. 35° E. and S. 35° W.</p>
80.00	<p>Point for the cor. of secs. 22, 23, 26, and 27, falls on W. edge of Indian Route 6011, a graded road, 33 ft. wide, bears S. 45° E. and N. 45° W.</p> <p>Set a standard monument, 48 ins. in the ground, mkd.</p> <p style="text-align: center;">T 34 N R 13 E S 22   S 23 S 27   S 26  2013</p> <p>from which</p> <p>A stainless steel post, 28 ins. long, 2 1/2 ins. diam., set 26 ins. in the ground, for a reference monument, bears S. 25°01' E., 90.0 ft. dist., with brass cap mkd. RM T34N R13E 90.0 FT. TO COR. S26 2013 with an arrow pointing to the cor. Deposit a magnet, in a white plastic case, at the base of the stainless steel post. Set a steel "T-Post" near the reference monument.</p>

**Survey of the Subdivisional Lines,  
T. 34 N., R. 13 E., Gila and Salt River Meridian, Arizona**

CHAINS	
	<p>A stainless steel post, 28 ins. long, 2 1/2 ins. diam., set 26 ins. in the ground, for a reference monument, bears S. 65°02' W., 89.0 ft. dist., with brass cap mkd. RM T34N R13E 89.0 FT. TO COR S27 2013 and an arrow pointing to the cor. Deposit a magnet, in a white plastic case, at the base of the stainless steel post. Set a steel "T-Post" near the reference monument.</p> <p>Land, rolling. Soil, sand. Timber, none. Undergrowth, native grasses.</p> <hr/> <p>From the cor. of secs. 23, 24, 25, and 26.</p> <p>West, bet. secs. 23 and 26.</p> <p>Over rolling terrain.</p>
1.35	Wash, 6 ft. wide, drains N. 55° W.
40.00	<p>Point for the 1/4 sec. cor. of secs. 23 and 26.</p> <p>Set a standard monument, 25 ins. in the ground, mkd.</p> <div style="text-align: center;"> <p>T 34 N R 13 E</p> <p>S 23</p> <p>1/4 ———</p> <p>S 26</p> <p>2013</p> </div> <p>Set a steel "T-Post" fence post near cor.</p>
57.15	Indian Route 6011, graded road, 30 ft. wide, bears N. 50° E. and S. 50° W.
65.35	Questar Southern Trails underground gas pipeline, bears N. 35° E. and S. 35° W.
79.30	Indian Route 6011, graded road, 30 ft. wide, bears S. 45° E. and N. 45° W.
80.00	<p>The cor. of secs. 22, 23, 26, and 27.</p> <p>Land, rolling. Soil, sand. Timber, none. Undergrowth, native grasses.</p> <hr/> <p>N. 0°01' W., bet. secs. 22 and 23.</p>

Survey of the Subdivisional Lines,  
T. 34 N., R. 13 E., Gila and Salt River Meridian, Arizona

CHAINS	
	Over rolling terrain.
0.25	Indian Route 6011, graded road, 30 ft. wide, bears S. 45° E. and N. 45° W.
33.70	Southeast right-of-way fence, bears N. 30° E. and S. 30° W.
36.15	Southeast edge of asphalt of Highway No. 160, 36 ft. wide, bears N. 30° E. and S. 30° W.
37.23	Northwest edge of asphalt of Highway No. 160, bears N. 30° E. and S. 30° W.
40.00	Point for the 1/4 sec. cor. of secs. 22 and 23.  Set a standard monument, 26 ins. in the ground, mkd.  <div style="text-align: center;">           T 34 N   R 13 E                  1/4            S 22   S 23              2013         </div>
	Set a steel "T-Post" fence post near cor.
42.60	Northwest right-of-way fence, bears N. 30° E. and S. 30° W.
80.00	Point for the cor. of secs. 14, 15, 22, and 23.  Set a standard monument, 26 ins. in the ground, mkd.  <div style="text-align: center;">           T 34 N   R 13 E            S 15   S 14            S 22   S 23              2013         </div>
	Set a steel "T-Post" fence post near cor.
	Land, rolling. Soil, sand. Timber, none. Undergrowth, native grasses.
	From the cor. of secs. 13, 14, 23, and 24.
	West, bet. secs. 14 and 23.
	Over rolling terrain.
9.70	Questar Southern Trails underground gas pipeline, bears N. 35° E. and S. 35° W.

Survey of the Subdivisional Lines,  
T. 34 N., R. 13 E., Gila and Salt River Meridian, Arizona

CHAINS	
40.00	<p>Point for the 1/4 sec. cor. of secs. 14 and 23.</p> <p>Set a standard monument, 26 ins. in the ground, mkd.</p> <p style="text-align: center;">T 34 N R 13 E S 14 1/4 ——— S 23</p> <p style="text-align: center;">2013</p> <p>Set a steel "T-Post" fence post near cor.</p>
52.45	Southeast right-of-way fence, bears N. 30° E. and S. 30° W.
53.90	Southeast edge of asphalt of Highway No. 160, 36 ft. wide, bears N. 30° E. and S. 30° W.
54.55	Northwest edge of asphalt of Highway No. 160, bears N. 30° E. and S. 30° W.
57.75	Northwest right-of-way fence, bears N. 30° E. and S. 30° W.
68.80	Utility line, 2 wire, bears N. 21° E. and S. 21° W.
80.00	<p>The cor. of secs. 14, 15, 22, and 23.</p> <p>Land, rolling. Soil, sand. Timber, none. Undergrowth, native grasses.</p> <hr/> <p>N. 0°01' W., bet. secs. 14 and 15.</p> <p>Over rolling terrain.</p>
40.00	<p>Point for the 1/4 sec. cor. of secs. 14 and 15.</p> <p>Set a standard monument, 26 ins. in the ground, mkd.</p> <p style="text-align: center;">T 34 N R 13 E 1/4 S 15   S 14</p> <p style="text-align: center;">2013</p> <p>Set a steel "T-Post" fence post near cor.</p>
80.00	<p>Point for the cor. of secs. 10, 11, 14, and 15.</p> <p>Set a standard monument, 26 ins. in the ground, mkd.</p>

Survey of the Subdivisional Lines,  
T. 34 N., R. 13 E., Gila and Salt River Meridian, Arizona

CHAINS	
	T 34 N R 13 E S 10   S 11 S 15   S 14  2013  Set a steel "T-Post" fence post near cor.  Land, rolling. Soil, sand. Timber, none. Undergrowth, native grasses.  <hr/> From the cor. of secs. 11, 12, 13, and 14.  West, bet. secs. 11 and 14.  Over rolling terrain.  4.90 Southeast right-of-way fence, bears N. 30° E. and S. 30° W.  6.30 Southeast edge of asphalt of Highway No. 160, 36 ft. wide, bears N. 30° E. and S. 30° W.  6.95 Northwest edge of asphalt of Highway No. 160, bears N. 30° E. and S. 30° W.  10.15 Northwest right-of-way fence, bears N. 30° E. and S. 30° W.  36.32 Utility line, 2 wire, bears N. 24° E. and S. 24° W.  40.00 Point for the 1/4 sec. cor. of secs. 11 and 14.  Set a standard monument, 26 ins. in the ground, mkd.  T 34 N R 13 E S 11 1/4 ——— S 14  2013  Set a steel "T-Post" fence post near cor.  80.00 The cor. of secs. 10, 11, 14, and 15.  Land, rolling. Soil, sand. Timber, none. Undergrowth, native grasses.  <hr/>

Survey of the Subdivisional Lines,  
T. 34 N., R. 13 E., Gila and Salt River Meridian, Arizona

CHAINS	
	N. 0°01' W., bet. secs. 10 and 11. Over rolling terrain.
35.20	Dirt road, 8 ft. wide, bears N. 80° E. and S. 80° W.
40.00	Point for the 1/4 sec. cor. bet. secs. 10 and 11. Set a standard monument, 26 ins. in the ground, mkd.  <div style="text-align: center;">           T 34 N R 13 E                  1/4            S 10   S 11              2013         </div>
	Set a steel "T-Post" fence post near cor.
41.75	Trail road, 8 ft. wide, bears S. 20° E. and N. 20° W.
80.00	Point for the cor. of secs. 2, 3, 10, and 11. Set a standard monument, 28 ins. in the ground, mkd.  <div style="text-align: center;">           T 34 N R 13 E            S 3   S 2            S 10   S 11              2013         </div>
	Set a steel "T-Post" fence post near cor.  Land, rolling. Soil, sand. Timber, none. Undergrowth, native grasses.
	From the cor. of secs. 1, 2, 11, and 12.  West, bet. secs. 2 and 11.  Over rolling terrain.
0.85	Utility line, 2 wire, bears N. 21° E. and S. 21° W.
40.00	Point for the 1/4 sec. cor. of secs. 2 and 11. Set a standard monument, 26 ins. in the ground, mkd.



Survey of the Subdivisional Lines,  
T. 34 N., R. 13 E., Gila and Salt River Meridian, Arizona

CHAINS	
	T 34 N R 13 E S 2 1/4 ——— S 11  2013
	Set a steel "T-Post" fence post near cor.
80.00	The cor. of secs. 2, 3, 10, and 11.  Land, rolling. Soil, sand. Timber, none. Undergrowth, native grasses.
	_____
	N. 0°01' W., bet. secs. 2 and 3.  Over rolling terrain.
40.00	Point for the 1/4 sec. cor. of secs. 2 and 3.  Set a standard monument, 25 ins. in the ground, mkd.
	T 34 N R 13 E 1/4 S 3   S 2  2013
	Set a steel "T-Post" fence post near cor.
80.00	The cor. of secs. 2, 3, 34, and 35, on the N. bdy. of the Tp., hereinbefore described.  Land, rolling. Soil, sand. Timber, none. Undergrowth, native grasses.
	_____
	From the cor. of secs. 3, 4, 33, and 34, on the S. bdy. of the Tp., hereinbefore described.  N. 0°02' W., bet. secs. 33 and 34.  Over rolling terrain.
1.95	Utility line, 2 wire, bears S. 80° E. and N. 80° W.
23.95	Questar Southern Trails underground gas pipeline, bears N. 35° E. and S. 35° W.

Survey of the Subdivisional Lines,  
T. 34 N., R. 13 E., Gila and Salt River Meridian, Arizona

CHAINS	
40.00	<p>Point for the 1/4 sec. cor. of secs. 33 and 34.</p> <p>Set a standard monument, 28 ins. in the ground, mkd.</p> <p style="text-align: center;">T 34 N R 13 E 1/4 S 33   S 34</p> <p style="text-align: center;">2013</p> <p>Set a steel "T-Post" fence post near cor.</p>
41.40	<p>Indian Route 21, graded road, 26 ft. wide, bears N. 10° E. and S. 10° W.</p>
80.00	<p>Point for the of secs. 27, 28, 33, and 34.</p> <p>Set a standard monument, 25 ins. in sandstone, mkd.</p> <p style="text-align: center;">T 34 N R 13 E S 28   S 27 ----- S 33   S 34</p> <p style="text-align: center;">2013</p> <p>Raised a mound of stone near cor.</p> <p>Land, rolling. Soil, sand and sandstone Timber, none. Undergrowth, native grasses.</p> <hr/> <p>From the cor. of secs. 26, 27, 34, and 35</p> <p>West, bet. secs. 27 and 34.</p> <p>Over rolling terrain.</p>
1.50	<p>Trail road, 8 ft. wide, bears N. and S. 5° E.</p>
2.45	<p>Dirt road, 8 ft. wide, bears S. 40° E. and N. 40° W.</p>
10.50	<p>East edge of Red Lake dry lake bed, bears N. 10° E. and S. 10° W.</p>
40.00	<p>Point for the 1/4 sec. cor. of secs. 27 and 34.</p> <p>Set a standard monument, 26 ins. in the ground, underpinned with an alum. rod, 36 ins. long, 3/4 in. diam., 36 ins. in the ground, mkd.</p>

Survey of the Subdivisional Lines,  
T. 34 N., R. 13 E., Gila and Salt River Meridian, Arizona

CHAINS	
	T 34 N R 13 E S 27 1/4 ——— S 34  2013
	Set a steel "T-Post" fence post near cor.
	Cor. is located in the dry lake bed of Red Lake, with scattered clumps of salt cedar.
41.00	Questar Southern Trails underground gas pipeline, bears N. 35° E. and S. 35° W.
70.45	West edge of Red Lake dry lake bed. bears S. 45° E. and N. 45° W.
74.30	Utility line, 2 wire, bears N. 30° E. and S. 30° W.
74.80	Dirt road, 10 ft. wide, bears S. 5° E. and N. 5° W.
77.20	Indian Route 21, graded road, 30 ft. wide, bears N. 25° E. and S. 25° W.
80.00	The cor. of secs. 27, 28, 33, and 34.
	Land, rolling. Soil, sand. Timber, none. Undergrowth, native grasses.
	-----
	N. 0°02' W., bet. secs. 27 and 28.
	Over rolling terrain.
9.70	Utility line, 2 wire, bears S. 51° E. and N. 51° W.
17.10	Indian Route 21, graded road, 25 ft. wide, bears S. 70° E. and N. 75° W.
28.35	Utility line, 5 wire, bears N. 61° E. and S. 61° W.
30.65	South right-of-way fence, bears N. 64° E. and S. 64° W.
32.00	South edge of asphalt of Highway No. 160, 36 ft. wide, bears N. 64° E. and S. 64° W.
32.75	North edge of asphalt of Highway No. 160, bears N. 64° E. and S. 64° W.
35.00	North right-of-way fence, bears N. 64° E. and S. 64° W.

Survey of the Subdivisional Lines,  
T. 34 N., R. 13 E., Gila and Salt River Meridian, Arizona

CHAINS	
40.00	<p>Point for the 1/4 sec. cor. of secs. 27 and 28.</p> <p>Set a standard monument, 26 ins. in the ground, mkd.</p> <p style="text-align: center;">T 34 N R 13 E 1/4 S 28   S 27</p> <p style="text-align: center;">2013</p> <p>Set a steel "T-Post" fence post near cor.</p> <p>Cor. falls on the northerly edge of a small strip of salt cedar.</p> <p>From this point the northwest cor. of the George Smith Historical Monument, bears N. 44°14' E. 11.10 chs. dist., monumented with a sandstone pillar, 3 x 5 ft. base. 2 x 5 ft. top, 7 ft. high, long side bears N. 89° E., with the placard missing.</p>
46.55	Dirt road, 8 ft. wide, bears N. 65° E. and S. 75° W.
49.80	Dirt road, 8 ft. wide, bears S. 55° E. and N. 50° W.
80.00	<p>Point for the cor. of secs. 21, 22, 27, and 28.</p> <p>Set a standard monument, 26 ins. in the ground, mkd.</p> <p style="text-align: center;">T 34 N R 13 E S 21   S 22 S 28   S 27</p> <p style="text-align: center;">2013</p> <p>Set a steel "T-Post" fence post near cor.</p> <p>Land, rolling. Soil, sand. Timber, none. Undergrowth, native grasses.</p> <hr/> <p>From the cor. of secs. 22, 23, 26, and 27</p> <p>West, bet. secs. 22 and 27.</p> <p>Over rolling terrain.</p>
20.05	Southeast right-of-way fence, bears N. 30° E. and S. 30° W.
21.50	Southeast edge of asphalt of Highway No. 160, 36 ft. wide, bears N. 30° E. and S. 30° W.

Survey of the Subdivisional Lines,  
T. 34 N., R. 13 E., Gila and Salt River Meridian, Arizona

CHAINS	
22.15	Northwest edge of asphalt of Highway No. 160, bears N. 30° E. and S. 30° W.
25.00	From this point, the most northerly "Elephant's Foot" (See page 82 for reference) bears S., approx. 30 lks. dist.
26.05	Northwest right-of-way fence, bears N. 30° E. and S. 30° W.
40.00	Point for the 1/4 sec. cor. of secs. 22 and 27.  Set a standard monument, 26 ins. in the ground, mkd.  <div style="text-align: center;">           T 34 N R 13 E                      S 22                  1/4 ———                      S 27             2013         </div> Set a steel "T-Post" fence post near cor.  From this point National Geodetic Survey station TONALEA, bears N. 24°49' E., 11.586 chs. dist., monumented with a brass tablet, 4 ins. diam., set in concrete, with a rock collar, with no marks legible, from which  <div style="margin-left: 40px;">             Reference monument No. 2, bears N. 21°57' E., 39.4 ft. dist., monumented with a brass tablet set concrete, projecting 2 ins. above the ground, mkd. NO2 1970 and an arrow pointing to the cor.               Reference monument No. 1, bears S. 69°19' W., 89.4 ft. dist., monumented with a brass tablet set in a sandstone outcrop, 6 x 9 ft., 1 1/2 ft. high, mkd. NO1 1970 and an arrow pointing to the cor.           </div> The 1/4 sec. cor. of secs. 22 and 27 is located in within a draw bet. sandstone ridges.
80.00	The cor. of secs. 21, 22, 27, and 28.  Land, rolling. Soil, sand. Timber, none. Undergrowth, native grasses.  <hr style="width: 60%; margin-left: 0;"/> N. 0°02' W., bet. secs. 21 and 22.  Over rolling terrain.
0.25	Wash, 8 ft. wide, drains S. 75° W.

Survey of the Subdivisional Lines,  
T. 34 N., R. 13 E., Gila and Salt River Meridian, Arizona

CHAINS	
40.00	<p>Point for the 1/4 sec. cor. of secs. 21 and 22.</p> <p>Set a standard monument, 21 ins. in sandstone, mkd.</p> <p style="text-align: center;">T 34 N R 13 E 1/4 S 21   S 22</p> <p style="text-align: center;">2013</p> <p>Cor. falls near the base of a sandstone bluff.</p>
74.45	<p>Wash, 12 ft. wide, drains S. 80° W.</p>
80.00	<p>Point for the cor. of secs. 15, 16, 21, and 22.</p> <p>Set a standard monument, 27 ins. in the ground, underpinned with an alum. rod, 36 ins. long, 3/4 in. diam., 46 ins. in the ground, mkd.</p> <p style="text-align: center;">T 34 N R 13 E S 16   S 15 S 21   S 22</p> <p style="text-align: center;">2013</p> <p>Set a steel "T-Post" fence post near cor.</p> <p>Land, rolling. Soil, sand. Timber, none. Undergrowth, native grasses.</p> <hr/> <p>From the cor. of secs. 14, 15, 22, and 23.</p> <p>West, bet. secs. 15 and 22.</p> <p>Over rolling terrain.</p>
40.00	<p>Point for the 1/4 sec. cor. of secs. 15 and 22.</p> <p>At the corner point</p> <p>Set a standard monument, 24 ins. in the ground, mkd.</p> <p style="text-align: center;">T 34 N R 13 E S 15 1/4 ——— S 22</p> <p style="text-align: center;">2013</p>

Survey of the Subdivisional Lines,  
T. 34 N., R. 13 E., Gila and Salt River Meridian, Arizona

CHAINS	
80.00	<p>Set a steel "T-Post" fence post near cor.</p> <p>The cor. of secs. 15, 16, 21, and 22.</p> <p>Land, rolling. Soil, sand. Timber, none. Undergrowth, native grasses.</p> <hr/> <p>N. 0°02' W., bet. secs. 15 and 16.</p> <p>Over rolling terrain.</p>
40.00	<p>Point for the 1/4 sec. cor. of secs. 15 and 16.</p> <p>Set a standard monument, 26 ins. in the ground, mkd.</p> <p style="text-align: center;">T 34 N R 13 E 1/4 S 16   S 15  2013</p>
80.00	<p>Set a steel "T-Post" fence post near cor.</p> <p>Point for the cor. of secs. 9, 10, 15, and 16.</p> <p>Set a standard monument, 26 ins. in the ground, mkd.</p> <p style="text-align: center;">T 34 N R 13 E S 9   S 10 S 16   S 15  2013</p>
40.00	<p>Set a steel "T-Post" fence post near cor.</p> <p>Land, rolling. Soil, sand. Timber, none. Undergrowth, native grasses.</p> <hr/> <p>From the cor. of secs. 10, 11, 14, and 15.</p> <p>West, bet. secs 10 and 15.</p> <p>Over rolling terrain.</p> <p>Point for the 1/4 sec. cor. of secs. 10 and 15.</p> <p>Set a standard monument, 26 ins. in the ground, mkd.</p>

Survey of the Subdivisional Lines,  
T. 34 N., R. 13 E., Gila and Salt River Meridian, Arizona

CHAINS	<p style="text-align: center;">T 34 N R 13 E S 10 1/4 ——— S 15</p> <p style="text-align: center;">2013</p> <p>Set a steel "T-Post" fence post near cor.</p> <p>80.00 The cor. of secs. 9, 10, 15, and 16.</p> <p>Land, rolling. Soil, sand. Timber, none. Undergrowth, native grasses.</p> <hr/> <p>N. 0°02' W., bet. secs. 9 and 10.</p> <p>Over rolling terrain.</p> <p>40.00 Point for the 1/4 sec. cor. of secs. 9 and 10.</p> <p>Set a standard monument, 26 ins. in the ground, mkd.</p> <p style="text-align: center;">T 34 N R 13 E 1/4 S 9   S 10</p> <p style="text-align: center;">2013</p> <p>Set a steel "T-Post" fence post near cor.</p> <p>80.00 Point for the cor. of secs. 3, 4, 9, and 10.</p> <p>Set a standard monument, 26 ins. in the ground, mkd.</p> <p style="text-align: center;">T 34 N R 13 E S 4   S 3 S 9   S 10</p> <p style="text-align: center;">2013</p> <p>Set a steel "T-Post" fence post near cor.</p> <p>Land, rolling. Soil, sand. Timber, none. Undergrowth, native grasses.</p> <hr/> <p>From the cor. of secs. 2, 3, 10, and 11.</p>
--------	-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------



Survey of the Subdivisional Lines,  
T. 34 N., R. 13 E., Gila and Salt River Meridian, Arizona

CHAINS	
	West, bet. secs. 3 and 10. Over rolling terrain.
40.00	Point for the 1/4 sec. cor. of secs. 3 and 10. Set a standard monument, 26 ins. in the ground, mkd.  <div style="text-align: center;">           T 34 N   R 13 E                      S   3                  1/4 ———                      S 10             2013         </div>
80.00	Set a steel "T-Post" fence post near cor. The cor. of secs. 3, 4, 9, and 10.  Land, rolling. Soil, sand. Timber, none. Undergrowth, native grasses.
	-----
	N. 0°02' W., bet. secs. 3 and 4. Over rolling terrain.
40.00	Point for the 1/4 sec. cor. of secs. 3 and 4. Set a standard monument, 26 ins. in the ground, mkd.  <div style="text-align: center;">           T 34 N   R 13 E                      1/4                  S 4   S 3             2013         </div>
76.35	Set a steel "T-Post" fence post near cor. Dirt road, 10 ft. wide, bears S. 85° E. and N. 85° W.
80.00	The cor. of secs. 3, 4, 33, and 34, on the N. bdy. of the Tp., hereinbefore described.  Land, rolling. Soil, sand. Timber, none. Undergrowth, native grasses.
	-----

Survey of the Subdivisional Lines,  
T. 34 N., R. 13 E., Gila and Salt River Meridian, Arizona

CHAINS	
	<p>From the cor. of secs. 4, 5, 32, and 33, on the S bdy. of the Tp., monumented with a brass tablet, 3 ins. diam., firmly set, flush in sandstone, mkd. T34N R13E S34 S35 S3 S2 T33N 2002.</p> <p>Add the marks 2013 to the brass cap.</p> <p>N. 0°03' W., bet. secs. 32 and 33.</p> <p>Over rolling terrain.</p>
40.00	<p>Point for the 1/4 sec. cor. of secs. 32 and 33.</p> <p>Set a standard monument, 24 ins. in the ground, mkd.</p> <div style="text-align: center;"> <p>T 34 N R 13 E</p> <p>1/4</p> <p>S 32   S 33</p> <p>2013</p> </div> <p>Set a steel "T-Post" fence post near cor.</p>
65.40	Southeast right-of-way fence, bears N. 50° E. and S. 50° W.
66.95	Southeast edge of asphalt of Highway No. 160, 46 ft. wide, bears N. 50° E. and S. 50° W.
67.65	Northwest edge of asphalt of Highway No. 160, bears N. 50° E. and S. 50° W.
71.20	Northwest right-of-way fence, bears N. 50° E. and S. 50° W.
80.00	<p>Point for the cor. of secs. 28, 29, 32, and 33.</p> <p>Set a standard monument, 28 ins. in the ground, mkd.</p> <div style="text-align: center;"> <p>T 34 N R 13 E</p> <p>S 29   S 28</p> <p>S 32   S 33</p> <p>2013</p> </div> <p>Set a steel "T-Post" fence post near cor.</p> <p>From this point an Arizona DOT right-of-way monument, bears S. 87°52' E. 17.27 chs. dist., monumented with a brass tablet, 3 1/2 ins. diam., set in concrete, 8 ins. diam., projecting 6 ins. above the ground, with a 4 in. angle iron, projecting 15 ins. above the ground nearby.</p> <p>Land, rolling.</p> <p>Soil, sand.</p> <p>Timber, none.</p> <p>Undergrowth, native grasses.</p> <hr/>

Survey of the Subdivisional Lines,  
T. 34 N., R. 13 E., Gila and Salt River Meridian, Arizona

CHAINS	
	<p>From the cor. of secs. 27, 28, 33, and 34. West, bet. secs. 28 and 33. Over rolling terrain.</p>
40.00	<p>Point for the 1/4 sec. cor. of secs. 28 and 33. Set a standard monument, 20 ins. in sandstone, mkd.</p> <p style="text-align: center;">T 34 N R 13 E S 28 1/4 ——— S 33</p> <p style="text-align: center;">2013</p> <p>From this point, a PK nail with a washer, set in concrete cylinder, 2 ins. diam., projecting 8 ins' above the ground mkd. AZ RLS 15083, set by Michael Daly, Arizona R.L.S. NO. 15083, bears N. 10°42' E., 13.38 chs. dist.</p> <p>From this same point, a PK nail with a washer, set in concrete cylinder, 2 ins. diam., projecting 8 ins' above the ground, mkd. AZ RLS 15083, set by Michael Daly, Arizona R.L.S. NO. 15083, bears N. 33°29' W., 10.97 chs. dist.</p> <p>From this same point a PK nail, set in concrete cylinder, 2 ins. diam., projecting 8 ins' above the ground, mkd. AZ RLS 15083, set by Michael Daly, Arizona R.L.S. NO. 15083, bears N. 11°22' W., 3.51 chs. dist.</p>
61.95	Southeast right-of-way fence, bears N. 50° E. and S. 50° W.
63.90	Southeast edge of asphalt of Highway No. 160, 46 ft. wide, bears N. 50° E. and S. 50° W.
64.80	Northwest edge of asphalt of Highway No. 160, bears N. 50° E. and S. 50° W.
69.20	Northwest right-of-way fence, bears N. 50° E. and S. 50° W.
80.00	<p>The cor. of secs. 28, 29, 32, and 33.</p> <p>Land, rolling. Soil, sand. Timber, none. Undergrowth, native grasses.</p> <hr/> <p>N. 0°03' W., bet. secs. 28 and 29. Over rolling terrain.</p>

Survey of the Subdivisional Lines,  
T. 34 N., R. 13 E., Gila and Salt River Meridian, Arizona

CHAINS	
40.00	<p>Point for the 1/4 sec. cor. of secs. 28 and 29.</p> <p>Set a standard monument, 26 ins. in the ground, mkd.</p> <p style="text-align: center;">T 34 N R 13 E 1/4 S 29   S 28</p> <p style="text-align: center;">2013</p> <p>Set a steel "T-Post" fence post near cor.</p> <p>From this point a Bureau of Indian Affairs right-of-way monument, bears N. 66°04' E. 9.435 chs. dist., monumented with an alum. cap, 3 ins. diam., set in concrete, 8 ins. diam., projecting 2 ins. above the ground, with a 4 in. angle iron nearby.</p> <p>From this same point a Bureau of Indian Affairs right-of-way monument, bears N. 77°49' E. 6.895 chs. dist., monumented with an alum. cap, 3 ins. diam., set in concrete, 8 ins. diam., projecting 2 ins. above the ground, with a 4 in. angle iron mkd. HWY R. of W. PC 0+849.879, nearby.</p> <p>From this same point, a NHA tract cor., bears S. 65°56' W. 8.94 chs. dist., monumented with a rebar, 5/8 in. diam., flush with the ground.</p> <p>From this same point, a NHA tract cor., bears N. 85°37' W. 23.24 chs. dist., monumented with a rebar, 5/8 in. diam., flush with the ground, with a plastic cap, 1 1/4 in. diam., mkd. NHA.</p> <p>From this same point, a NHA tract cor., bears N. 59°47' W. 17.725 chs. dist., monumented with a rebar, 1/2 in. diam., flush with the ground, in concrete, 1 ft. diam.</p> <p>From this same point, a NHA tract cor., bears N. 53°32' W. 5.66 chs. dist., monumented with a rebar, 5/8 in. diam., flush with the ground, with a plastic cap, 1 1/4 in. diam., mkd. NHA.</p> <p>From this same point, the most easterly cor. of a chain link fence surrounding the Chapter House Tract, approx. 680 x 700 ft., bears N. 63°59' E. 9.26 chs. dist.</p> <p>From this same point, the most southerly cor. of a chain link fence surrounding a Cemetery Tract, approx., 300 x 600 ft., bears N. 32°20' W. 17.01 chs. dist.</p>
45.50	South right-of-way fence, bears S. 65° E. and N. 65° W.
47.20	Centerline of Indian Route 21, paved road, 26 ft. wide, bears S. 65° E. and N. 65° W.

Survey of the Subdivisional Lines,  
T. 34 N., R. 13 E., Gila and Salt River Meridian, Arizona

CHAINS									
48.90	North right-of-way fence, bears S. 65° E. and N. 65° W.								
80.00	Point for the cor. of secs. 20, 21, 28, and 29.  Set a standard monument, 27 ins. in the ground, mkd.  <div style="text-align: center;"> <table style="margin: auto;"> <tr> <td>T 34 N</td> <td>R 13 E</td> </tr> <tr> <td style="border-right: 1px solid black;">S 20</td> <td>S 21</td> </tr> <tr> <td style="border-right: 1px solid black;">S 29</td> <td>S 28</td> </tr> </table> <p>2013</p> </div> Set a steel "T-Post" fence post near cor.  Land, rolling. Soil, sand. Timber, none. Undergrowth, native grasses. <hr/>	T 34 N	R 13 E	S 20	S 21	S 29	S 28		
T 34 N	R 13 E								
S 20	S 21								
S 29	S 28								
	From the cor. of secs. 21, 22, 27, and 28.  West, bet. secs. 21 and 28.  Over rolling terrain.								
40.00	Point for the 1/4 sec. cor. of secs. 21 and 28.  Set a standard monument, 28 ins. in the ground, mkd.  <div style="text-align: center;"> <table style="margin: auto;"> <tr> <td>T 34 N</td> <td>R 13 E</td> </tr> <tr> <td></td> <td>S 21</td> </tr> <tr> <td>1/4</td> <td style="border-top: 1px solid black;">———</td> </tr> <tr> <td></td> <td>S 28</td> </tr> </table> <p>2013</p> </div> Set a steel "T-Post" fence post near cor.	T 34 N	R 13 E		S 21	1/4	———		S 28
T 34 N	R 13 E								
	S 21								
1/4	———								
	S 28								
80.00	The cor. of secs. 20, 21, 28, and 29.  Land, rolling. Soil, sand. Timber, none. Undergrowth, native grasses. <hr/>								
	N. 0°03' W., bet. secs. 20 and 21.  Over rolling terrain.								
36.05	Dirt road, 10 ft. wide, bears S. 50° E. and N. 50° W.								

Survey of the Subdivisional Lines,  
T. 34 N., R. 13 E., Gila and Salt River Meridian, Arizona

CHAINS	
40.00	<p>Point for the 1/4 sec. cor. of secs. 20 and 21.</p> <p>Set a standard monument, 28 ins. in the ground, underpinned with an alum. rod, 36 ins. long, 3/4 in. diam., 50 ins. in the ground, mkd.</p> <p style="text-align: center;">T 34 N R 13 E 1/4 S 20   S 21</p> <p style="text-align: center;">2013</p> <p>Set a steel "T-Post" fence post near cor.</p>
69.65	<p>Indian Route 6261, graded road, 27 ft. wide, bears N. 30° E. and S. 30° W.</p>
80.00	<p>Point for the cor. of secs. 16, 17, 20, and 21.</p> <p>Set a standard monument, 28 ins. in the ground, mkd.</p> <p style="text-align: center;">T 34 N R 13 E S 17   S 16 S 20   S 21</p> <p style="text-align: center;">2013</p> <p>Set a steel "T-Post" fence post near cor.</p> <p>Land, rolling. Soil, sand. Timber, none. Undergrowth, native grasses.</p> <hr/> <p>From the cor. of secs. 15, 16, 21, and 22.</p> <p>West, bet. secs. 16 and 21.</p> <p>Over rolling terrain.</p>
40.00	<p>Point for the 1/4 sec. cor. of secs. 16 and 21.</p> <p>Set a standard monument, 28 ins. in the ground, underpinned with an alum. rod, 36 ins. long, 3/4 in. diam., 48 ins. in the ground, mkd.</p> <p style="text-align: center;">T 34 N R 13 E S 16 1/4 ——— S 21</p> <p style="text-align: center;">2013</p>

Survey of the Subdivisional Lines,  
T. 34 N., R. 13 E., Gila and Salt River Meridian, Arizona

CHAINS	
	Set a steel "T-Post" fence post near cor.
76.45	Indian Route 6261, graded road, 27 ft. wide, bears N. 15° E. and S. 15° W.
80.00	The cor. of secs. 16, 17, 20, and 21.
	Land, rolling. Soil, sand. Timber, none. Undergrowth, native grasses.
	<hr/>
	N. 0°03' W., bet. secs. 16 and 17.
	Over rolling terrain.
40.00	Point for the 1/4 sec. cor. of secs. 16 and 17.
	Set a standard monument, 27 ins. in the ground, underpinned with an alum. rod, 36 ins. long, 3/4 in. diam., 41 ins. in the ground, mkd.
	T 34 N R 13 E 1/4 S 17   S 16  2013
	Set a steel "T-Post" fence post near cor.
78.00	Dirt road, 10 ft. wide, bears S. 65° E. and N. 65° W.
80.00	Point for the cor. of secs. 8, 9, 16, and 17.
	Set a standard monument, 26 ins. in the ground, mkd.
	T 34 N R 13 E S 8   S 9 S 17   S 16  2013
	Set a steel "T-Post" fence post near cor.
	Land, rolling. Soil, sand. Timber, none. Undergrowth, native grasses.
	<hr/>

Survey of the Subdivisional Lines,  
T. 34 N., R. 13 E., Gila and Salt River Meridian, Arizona

CHAINS	
	<p>From the cor. of secs. 9, 10, 15, and 16.</p> <p>West, bet. secs. 9 and 16.</p> <p>Over rolling terrain.</p>
40.00	<p>Point for the 1/4 sec. cor. of secs. 9 and 16.</p> <p>Set a standard monument, 26 ins. in the ground, underpinned with an alum. rod, 36 ins. long, 3/4 in. diam., 48 ins. in the ground, mkd.</p> <p style="text-align: center;">T 34 N R 13 E S 9 1/4 ——— S 16</p> <p style="text-align: center;">2013</p> <p>Set a steel "T-Post" fence post near cor.</p>
77.00	<p>Indian Route, graded road, 27 ft. wide, bears S. 20° E. and N. 20° W.</p>
80.00	<p>The cor. of secs. 8, 9, 16, and 17.</p> <p>Land, rolling. Soil, sand. Timber, none. Undergrowth, native grasses.</p> <hr/> <p>N. 0°03' W., bet. secs. 8 and 9.</p> <p>Over Rolling terrain.</p>
40.00	<p>Point for the 1/4 sec. cor. of secs. 8 and 9.</p> <p>Set a standard monument, 26 ins. in the ground, mkd.</p> <p style="text-align: center;">T 34 N R 13 E 1/4 S 8   S 9</p> <p style="text-align: center;">2013</p> <p>Set a steel "T-Post" fence post near cor.</p>
78.50	<p>Indian Route 6261, graded road, 27 ft. wide, bears S. 50° E. and N. 50° W.</p>
80.00	<p>Point for the cor. of secs. 4, 5, 8, and 9.</p> <p>Set a standard monument, 26 ins. in the ground, mkd.</p>



Survey of the Subdivisional Lines,  
T. 34 N., R. 13 E., Gila and Salt River Meridian, Arizona

CHAINS									
	<div style="text-align: center;"> <table border="1"> <tr> <td>T 34 N</td> <td>R 13 E</td> </tr> <tr> <td>S 5</td> <td>S 4</td> </tr> <tr> <td>S 8</td> <td>S 9</td> </tr> </table> <p>2013</p> <p>Set a steel "T-Post" fence post near cor.</p> <p>Land, rolling. Soil, sand. Timber, none. Undergrowth, native grasses.</p> <hr/> <p>From the cor. of secs. 3, 4, 9, and 10.</p> <p>West, bet. secs. 4 and 9.</p> <p>Over rolling terrain.</p> </div>	T 34 N	R 13 E	S 5	S 4	S 8	S 9		
T 34 N	R 13 E								
S 5	S 4								
S 8	S 9								
40.00	<p>Point for the 1/4 sec. cor. of secs. 4 and 9.</p> <p>Set a standard monument, 25 ins. in the ground, with a small rock collar, mkd.</p>								
	<div style="text-align: center;"> <table border="1"> <tr> <td>T 34 N</td> <td>R 13 E</td> </tr> <tr> <td>S 4</td> <td></td> </tr> <tr> <td>1/4</td> <td>_____</td> </tr> <tr> <td>S 9</td> <td></td> </tr> </table> <p>2013</p> <p>Set a steel "T-Post" fence post near cor.</p> </div>	T 34 N	R 13 E	S 4		1/4	_____	S 9	
T 34 N	R 13 E								
S 4									
1/4	_____								
S 9									
80.00	<p>The cor. of secs. 3, 4, 9, and 10.</p> <p>Land, rolling. Soil, sand. Timber, none. Undergrowth, native grasses.</p> <hr/>								
	<p>N. 0°02' W., bet. secs. 4 and 5.</p> <p>Over Rolling terrain.</p>								
40.00	<p>Point for the 1/4 sec. cor. of secs. 4 and 5.</p> <p>Set a standard monument, 26 ins. in the ground, mkd.</p>								

Survey of the Subdivisional Lines,  
T. 34 N., R. 13 E., Gila and Salt River Meridian, Arizona

CHAINS	
	T 34 N R 13 E 1/4 S 5   S 4  2013
	Set a steel "T-Post" fence post near cor.
80.00	The cor. of secs. 4, 5, 32, and 33, on the N. bdy. of the Tp., hereinbefore described.
	Land, rolling. Soil, sand. Timber, none. Undergrowth, native grasses.
	<hr/> From the cor. of secs. 5, 6, 31, and 32, on the S. bdy. of the Tp., monumented with a stainless steel post, 2 1/2 in. diam., firmly set, projecting 6 ins. above the ground, with brass cap mkd. T34N R13E S31 S32 S6 S5 T33N 2002, Add the marks 2013 to the brass cap.  N. 0°03' W., bet. secs. 31 and 32.  Over rolling terrain.
0.50	Southeast right-of-way fence, bears N. 50° E. and S. 50° W.
2.05	Southeast edge of asphalt of Highway No. 160, 46 ft. wide, bears N. 50° E. and S. 50° W.
2.80	Northwest edge of asphalt of Highway No. 160, bears N. 50° E. and S. 50° W.
6.35	Northwest right-of-way fence, bears N. 50° E. and S. 50° W.
32.80	Dirt road, 10 ft. wide, bears S. 45° E. and N. 45° W.
33.05	Dirt road, 10 ft. wide, bears S. 30° E. and N. 30° W.
40.00	Point for the 1/4 sec. cor. of secs. 31 and 32.
	Set a standard monument, 28 ins. in the ground, mkd.
	T 34 N R 13 E 1/4 S 31   S 32  2013
	Set a steel "T-Post" fence post near cor.

Survey of the Subdivisional Lines,  
T. 34 N., R. 13 E., Gila and Salt River Meridian, Arizona

CHAINS									
41.70	Dirt road, 10 ft. wide, bears S. 10° E. and N. 10° W.								
61.35	Waterline, bears N. 10° E. and S. 10° W.								
80.00	Point for the cor. of secs. 29, 30, 31, and 32.  Set a standard monument, 27 ins. in the ground, underpinned with an alum. rod, 36 ins. long, 3/4 in. diam., 48 ins. in the ground, mkd.  <div style="text-align: center;"> <table style="margin: auto;"> <tr> <td>T 34 N</td> <td>R 13 E</td> </tr> <tr> <td>S 30</td> <td>S 29</td> </tr> <tr> <td>S 31</td> <td>S 32</td> </tr> </table> <p>2013</p> </div> Set a steel "T-Post" fence post near cor.  Land, rolling. Soil, sand. Timber, none. Undergrowth, native grasses. <hr/> From the cor. of secs. 28, 29, 32, and 33.  West, bet. secs. 29 and 32.	T 34 N	R 13 E	S 30	S 29	S 31	S 32		
T 34 N	R 13 E								
S 30	S 29								
S 31	S 32								
40.00	Point for the 1/4 sec. cor. of secs. 29 and 32.  Set a standard monument, 28 ins. in the ground, underpinned with an alum. rod, 36 ins. long, 3/4 in. diam., 48 ins. in the ground, mkd.  <div style="text-align: center;"> <table style="margin: auto;"> <tr> <td>T 34 N</td> <td>R 13 E</td> </tr> <tr> <td></td> <td>S 29</td> </tr> <tr> <td>1/4</td> <td>_____</td> </tr> <tr> <td></td> <td>S 32</td> </tr> </table> <p>2013</p> </div> Set a steel "T-Post" fence post near cor.	T 34 N	R 13 E		S 29	1/4	_____		S 32
T 34 N	R 13 E								
	S 29								
1/4	_____								
	S 32								
74.85	Indian Route 6262, graded road, 36 ft. wide, bears S. 30° E. and N. 30° W.								
75.60	Utility line, 5 wire, bears N. 15° E. and S. 15° W.								
80.00	The cor. of secs. 29, 30, 31, and 32.								

Survey of the Subdivisional Lines,  
T. 34 N., R. 13 E., Gila and Salt River Meridian, Arizona

CHAINS	
	<p>Land, rolling. Soil, sand. Timber, none. Undergrowth, native grasses.</p> <hr/> <p>West., bet. secs. 30 and 31.</p> <p>Over rolling terrain.</p>
5.25	Dirt road, 10 ft. wide, bears N. 50° E. and S. 50° W.
40.00	<p>Point for the 1/4 sec. cor. of secs. 30 and 31.</p> <p>Set a standard monument, 28 ins. in the ground, underpinned with an alum. rod, 36 ins. long, 3/4 in. diam., 56 ins. in the ground, mkd.</p> <div style="text-align: center;"> <p>T 34 N R 13 E</p> <p>S 30</p> <p>1/4 ———</p> <p>S 31</p> <p>2013</p> </div>
79.38	<p>Set a steel "T-Post" fence post near cor.</p> <p>The cor. of secs. 25, 30, 31, and 36, on the W. bdy. of the Tp., hereinbefore described.</p> <p>Land, rolling. Soil, sand. Timber, none. Undergrowth, native grasses.</p> <hr/> <p>From the cor. of secs. 29, 30, 31, and 32.</p> <p>N. 0°03' W., bet. secs. 29 and 30.</p> <p>Over rolling terrain.</p>
4.75	Dirt road, 10 ft. wide, bears N. 50° E. and S. 50° W.
9.25	Indian Route 6262, graded road, 36 ft. wide, bears S. 30° E. and N. 30° W.
40.00	<p>Point for the 1/4 sec. cor. of secs. 29 and 30.</p> <p>Set a standard monument, 26 ins. in the ground, underpinned with an alum. rod, 36 ins. long, 3/4 in. diam., 45 ins. in the ground, mkd.</p>

Survey of the Subdivisional Lines,  
T. 34 N., R. 13 E., Gila and Salt River Meridian, Arizona

CHAINS	
	T 34 N R 13 E 1/4 S 30   S 29  2013
	Set a steel "T-Post" fence post near cor.
58.00	Waterline, bears S. 65° E. and N. 65° W.
58.25	Dirt road, 12 ft. wide, bears S. 65° E. and N. 65° W.
77.55	Barbed wire fence, bears N. 30° E. and S. 30° W.
80.00	Point for the cor. of secs. 19, 20, 29, and 30.
	Set a standard monument, 25 ins. in the ground, mkd.
	T 34 N R 13 E S 19   S 20 S 30   S 29  2013
	Set a steel "T-Post" fence post near cor.
	Land, rolling.
	Soil, sand, sandstone, and limestone.
	Timber, none.
	Undergrowth, native grasses.
	<hr/>
	From the cor. of secs. 20, 21, 28, and 29.
	West, bet. secs. 20 and 29.
	Over rolling terrain.
25.20	Indian Route 6261, graded road, 27 ft. wide, bears N. 30° E. and S. 30° W.
40.00	Point for the 1/4 sec. cor. of secs. 20 and 29.
	Set a standard monument, 28 ins. in the ground, underpinned with an alum. rod, 36 ins. long, 3/4 in. diam., 47 ins. in the ground, mkd.
	T 34 N R 13 E S 20 1/4 ——— S 29  2013

Survey of the Subdivisional Lines,  
T. 34 N., R. 13 E., Gila and Salt River Meridian, Arizona

CHAINS	
	Set a steel "T-Post" fence post near cor.
61.62	Northeasterly right-of-way fence, bears S. 65° E. and N. 65° W.
64.95	Centerline of Indian Route 21, paved road, 26 ft. wide, bears S. 65° E. and N. 65° W.
68.25	Southwesterly right-of-way fence, bears S. 65° E. and N. 65° W.
72.40	Utility line, 2 wire, bears S. 65° E. and N. 65° W.
72.70	Barbed wire fence, bears S. 65° E. and N. 65° W.
78.55	Barbed wire fence, bears N. 30° E. and S. 30° W.
80.00	The cor. of secs. 19, 20, 29, and 30.
	Land, rolling. Soil, sand. Timber, none. Undergrowth, native grasses.
	West, bet. secs. 19 and 30.
	Over rolling terrain.
10.50	Indian Route 6262, graded road, 36 ft. wide, bears S. 10° E. and N. 10° W.
26.70	Waterline, bears S. 70° E. and N. 70° W.
40.00	Point for the 1/4 sec. cor. of secs. 19 and 30.
	Set a standard monument, 18 ins. in the ground, to sandstone, in a supporting mound of stone, 4 ft. base to cap, mkd.
	T 34 N    R 13 E S 19 1/4 ——— S 30
	2013
	From this point, the southerly cor. of a chain link fence, 60 x 60 ft., 6 ft. high, enclosing a water tank, bears N. 52°44' E., 8.90 chs. dist.
	From this same point, a water well, bears N. 55°04' E., 10.53 chs. dist.
79.29	The cor. of secs. 19, 24, 25, and 30, on the W. bdy. of the Tp., hereinbefore described.

Survey of the Subdivisional Lines,  
T. 34 N., R. 13 E., Gila and Salt River Meridian, Arizona

CHAINS	
	<p>Land, rolling. Soil, sand and sandstone. Timber, sparse juniper. Undergrowth, native grasses.</p> <hr/>
	<p>From the cor. of secs. 19, 20, 29, and 30.</p> <p>N. 0°03' W., bet. secs. 19 and 20.</p> <p>Over rolling terrain.</p>
4.30	Barbed wire fence, bears S. 65° E. and N. 65° W.
4.50	Utility line, 2 wire, bears S. 65° E. and N. 65° W.
6.15	Southwesterly right-of-way fence, bears S. 60° E. and N. 60° W.
7.85	Centerline of Indian Route 21, paved road, 26 ft. wide, bears S. 60° E. and N. 60° W.
9.60	Northeasterly right-of-way fence, bears S. 60° E. and N. 60° W.
40.00	Point for the 1/4 sec. cor. of secs. 19 and 20.
	Set a standard monument, 28 ins. in the ground, mkd.
	<p>T 34 N R 13 E 1/4 S 19   S 20</p> <p>2013</p>
	Set a steel "T-Post" fence post near cor.
80.00	Point for the cor. of secs. 17, 18, 19, and 20.
	Set a standard monument, 27 ins. in the ground, mkd.
	<p>T 34 N R 13 E S 18   S 17 S 19   S 20</p> <p>2013</p>
	Set a steel "T-Post" fence post near cor.
	<p>Land, rolling. Soil, sand and sandstone. Timber, sparse juniper. Undergrowth, native grasses.</p> <hr/>

Survey of the Subdivisional Lines,  
T. 34 N., R. 13 E., Gila and Salt River Meridian, Arizona

CHAINS	
	<p>From the cor. of secs. 16, 17, 20, and 21.</p> <p>West, bet. secs. 17 and 20.</p> <p>Over rolling terrain.</p>
40.00	<p>Point for the 1/4 sec. cor. of secs. 17 and 20.</p> <p>Set a standard monument, 28 ins. in the ground, mkd.</p> <p style="text-align: center;">T 34 N R 13 E S 17 1/4 ——— S 20</p> <p style="text-align: center;">2013</p> <p>Set a steel "T-Post" fence post near cor.</p>
80.00	<p>The cor. of secs. 17, 18, 19, and 20.</p> <p>Land, rolling. Soil, sand. Timber, sparse juniper. Undergrowth, native grasses.</p> <hr/> <p>West, bet. secs. 18 and 19.</p> <p>Over rolling terrain.</p>
40.00	<p>Point for the 1/4 sec. cor. of secs. 17 and 18.</p> <p>Set a standard monument, 25 ins. in the ground, mkd.</p> <p style="text-align: center;">T 34 N R 13 E S 18 1/4 ——— S 19</p> <p style="text-align: center;">2013</p> <p>Set a steel "T-Post" fence post near cor.</p>
79.20	<p>The cor. of secs. 13, 18, 19, and 24, on the W. bdy. of the Tp., hereinbefore described.</p> <p>Land, rolling. Soil, sand and sandstone. Timber, sparse juniper. Undergrowth, native grasses.</p> <hr/>



Survey of the Subdivisional Lines,  
T. 34 N., R. 13 E., Gila and Salt River Meridian, Arizona

CHAINS	
	<p>From the cor. of secs. 17, 18, 19 and 20.</p> <p>N. 0°03' W., bet. secs. 17 and 18.</p> <p>Over rolling terrain.</p>
40.00	<p>Point for the 1/4 sec. cor. of secs. 17 and 18.</p> <p>Set a standard monument, 28 ins. in the ground, mkd.</p> <p style="text-align: center;">T 34 N R 13 E 1/4 S 18   S 17</p> <p style="text-align: center;">2013</p> <p>Set a steel "T-Post" fence post near cor.</p>
80.00	<p>Point for the cor. of secs. 7, 8, 17, and 18.</p> <p>Set a standard monument, 19 ins. in the ground, to limestone, in a supporting mound of stone, 3 ft. base to cap, mkd.</p> <p style="text-align: center;">T 34 N R 13 E S 7   S 8 S 18   S 17</p> <p style="text-align: center;">2013</p> <p>Set a steel "T-Post" fence post near cor.</p> <p>Land, rolling. Soil, sand, sandstone, and limestone. Timber, sparse juniper. Undergrowth, native grasses.</p> <hr/> <p>From the cor. of secs. 8, 9, 16, and 17.</p> <p>West, bet. secs. 8 and 17.</p> <p>Over rolling terrain.</p>
40.00	<p>Point for the 1/4 sec. cor. of secs. 8 and 17.</p> <p>Set a standard monument, 26 ins. in the ground, mkd.</p> <p style="text-align: center;">T 34 N R 13 E S 8 1/4 ——— S 17</p> <p style="text-align: center;">2013</p>

Survey of the Subdivisional Lines,  
T. 34 N., R. 13 E., Gila and Salt River Meridian, Arizona

CHAINS	
	Set a steel "T-Post" fence post near cor.
80.00	The cor. of secs. 7, 8, 17, and 18.  Land, rolling. Soil, sand, sandstone, and limestone. Timber, none. Undergrowth, native grasses.
	<hr/>
	West, bet. secs. 7 and 18.  Over rolling terrain.
40.00	Point for the 1/4 sec. cor. of secs. 7 and 18.  Set a standard monument, 28 ins. in the ground, underpinned with an alum. rod, 36 ins. long, 3/4 in. diam., 56 ins. in the ground, mkd.
	T 34 N R 13 E S 7 1/4 ——— S 18  2013
	Set a steel "T-Post" fence post near cor.
42.20	Dirt road, 10 ft. wide, bears N. 10° E. and S. 10° W.
42.65	Utility line, 2 wire, bears S. 45° E. and N. 45° W.
79.12	The cor. of secs. 7, 12, 13, and 18, on the W. bdy. of the Tp., hereinbefore described.  Land, rolling. Soil, sand, sandstone, and limestone. Timber, none. Undergrowth, native grasses.
	<hr/>
	From the cor. of secs. 7, 8, 17, and 18.  N. 0°03' W., bet. secs. 7 and 8.  Over rolling terrain.
40.00	Point for the 1/4 sec. cor. of secs. 7 and 8.  Set a standard monument, 26 ins. in the ground, mkd.

Survey of the Subdivisional Lines,  
T. 34 N., R. 13 E., Gila and Salt River Meridian, Arizona

CHAINS	
	T 34 N R 13 E 1/4 S 7   S 8  2013
	Set a steel "T-Post" fence post near cor.
80.00	Point for the cor. of secs. 5, 6, 7, and 8.
	Set a standard monument, 26 ins. in the ground, mkd.
	T 34 N R 13 E S 6   S 5 S 7   S 8  2013
	Set a steel "T-Post" fence post near cor.
	Land, rolling to flat.
	Soil, sand.
	Timber, none.
	Undergrowth, native grasses.
	<hr/>
	From the cor. of secs. 4, 5, 8, and 9.
	West, bet. secs. 5 and 8.
	Over rolling terrain.
1.60	Indian Route 6261, graded road, 20 ft. wide, bears S. 50° E. and N. 50° W.
40.00	Point for the 1/4 sec. cor. of secs. 5 and 8.
	Set a standard monument, 25 ins. in the ground, mkd.
	T 34 N R 13 E S 5 1/4 ——— S 8  2013
	Set a steel "T-Post" fence post near cor.
78.45	Dirt road, 8 ft. wide, bears S. 30° E. and N. 30° W.
80.00	The cor. of secs. 5, 6, 7, and 8.

Survey of the Subdivisional Lines,  
T. 34 N., R. 13 E., Gila and Salt River Meridian, Arizona

CHAINS	
	<p>Land, rolling. Soil, sand. Timber, none. Undergrowth, native grasses.</p> <hr/> <p>West, bet. secs. 6 and 7.</p> <p>Over rolling terrain.</p>
38.90	Dirt road, 10 ft. wide, bears N. 35° E. and S. 35° W.
40.00	<p>Point for the 1/4 sec. cor. of secs. 6 and 7.</p> <p>Set a standard monument, 28 ins. in the ground, underpinned with an alum. rod., 36 ins. long, 3/4 in. diam., 48 ins. in the ground, mkd.</p> <div style="text-align: center;"> <p>T 34 N    R 13 E</p> <p>          S    6</p> <p>      1/4 ———</p> <p>          S    7</p> <p>          2013</p> </div> <p>Set a steel "T-Post" fence post near cor.</p>
79.03	<p>The cor. of secs. 1, 6, 7, and 12, on the W. bdy. of the Tp., hereinbefore described.</p> <p>Land, rolling to flat. Soil, sand. Timber, none. Undergrowth, native grasses.</p> <hr/> <p>From the cor. of secs. 5, 6, 7, and 8.</p> <p>N. 0°03' W., bet. secs. 5 and 6.</p> <p>Over rolling terrain.</p>
40.00	<p>Point for the 1/4 sec. cor. of secs. 5 and 6.</p> <p>Set a standard monument, 26 ins. in the ground, mkd.</p> <div style="text-align: center;"> <p>T 34 N    R 13 E</p> <p>          1/4</p> <p>      S 6   S 5</p> <p>          2013</p> </div> <p>Set a steel "T-Post" fence post near cor.</p>

Survey of the Subdivisional Lines,  
T. 34 N., R. 13 E., Gila and Salt River Meridian, Arizona

CHAINS	
80.00	<p>The cor. of secs. 5, 6, 31, and 32, on the N. bdy. of the Tp., hereinbefore described.</p> <p>Land, rolling. Soil, sand. Timber, none. Undergrowth, native grasses.</p> <hr/> <p style="text-align: center;">Subdivision of Section 1, T. 34 N., R. 13 E., Gila and Salt River Meridian, Arizona</p> <hr/> <p>From the 1/4 sec. cor. of secs. 1 and 12.</p> <p>North, on the N. and S. center line of sec. 1.</p>
4.20	Northwesterly right-of-way fence, bears N. 30° E. and S. 30° W.
40.00	<p>Point for the center 1/4 sec. cor. of sec. 1, at intersection with the E. and W. center line.</p> <p>Set a standard monument, 26 ins. in the ground, mkd.</p> <p style="text-align: center;">T 34 N R 13 E C 1/4 S 1</p> <p style="text-align: center;">2013</p> <p>Set a steel "T-Post" fence post near cor.</p>
80.00	<p>The 1/4 sec. cor. of secs. 1 and 36.</p> <hr/> <p>From the 1/4 sec. cor. of secs. 1 and 6.</p> <p>West, on the E. and W. center line of sec. 1.</p>
13.45	Southeast right-of-way fence, bears N. 30° E. and S. 30° W.
14.85	Southeast edge of asphalt of Highway No. 160, 36 ft. wide, bears N. 30° E. and S. 30° W.
15.50	Northwest edge of asphalt of Highway No. 160, bears N. 30° E. and S. 30° W.
18.75	Northwest right-of-way fence, bears N. 30° E. and S. 30° W.
40.00	The center 1/4 sec. cor. of sec. 1.
64.80	Utility line, 2 wire, bears S. 21° E. and N. 21° W.
80.00	<p>The 1/4 sec. cor. of secs. 1 and 2.</p> <hr/>

**Subdivision of Section 11,  
T. 34 N., R. 13 E., Gila and Salt River Meridian, Arizona**

CHAINS	
	From the 1/4 sec. cor. of secs. 11 and 14.
	N. 0°01' W., on the N. and S. center line of sec. 11.
40.00	Point for the center 1/4 sec. cor. of sec. 11, at intersection with the E. and W. center line.
	Set a standard monument, 26 ins. in the ground, underpinned with an alum. rod, 36 ins. long, 3/4 in. diam., 51 ins. in the ground, mkd.
	T 34 N R 13 E C 1/4 S 11
	2013
	Set a steel "T-Post" fence post near cor.
42.15	Dirt road, 8 ft. wide, bears S. 75° E. and N. 75° W.
80.00	The 1/4 sec. cor. of secs. 2 and 11.
<hr/>	
	From the 1/4 sec. cor. of secs. 11 and 12.
	West, on the E. and W. center line of sec. 11.
18.15	Utility line, 2 wire, bears N. 24° E. and S. 24° W.
40.00	The center 1/4 sec. cor. of sec. 11.
80.00	The 1/4 sec. cor. of secs. 10 and 11.
<hr/>	
<b>Subdivision of Section 12, T. 34 N., R. 13 E., Gila and Salt River Meridian, Arizona</b>	
<hr/>	
	From the 1/4 sec. cor. of secs. 12 and 13.
	North, on the N. and S. center line of sec. 12.
40.00	Point for the center 1/4 sec. cor. of sec. 12, at intersection with the E. and W. center line.
	Set a standard monument, 26 ins. in the ground, mkd.
	T 34 N R 13 E C 1/4 S 12
	2013
	Set a steel "T-Post" fence post near cor.

**Subdivision of Section 12,  
T. 34 N., R. 13 E., Gila and Salt River Meridian, Arizona**

CHAINS	
	Cor. is located E., 11 lks. dist., and S., 17 lks. dist., from a barbed wire fence. Fence bears N. 22° E. and S. 22° W.
75.35	Southeast right-of-way fence, bears N. 30° E. and S. 30° W.
77.80	Southeast edge of asphalt of Highway No. 160, 46 ft. wide, bears N. 30° E. and S. 30° W.
78.90	Northeast edge of asphalt of Highway No. 160, bears N. 30° E. and S. 30° W.
80.00	The 1/4 sec. cor. of secs. 1 and 12.
-----	
	From the 1/4 sec. cor. of secs. 7 and 12.
	West, on the E. and W. center line of sec. 12.
40.00	The center 1/4 sec. cor. of sec. 12.
61.05	Southeast right-of-way fence, bears N. 30° E. and S. 30° W.
62.50	Southeast edge of asphalt of Highway No. 160, 36 ft. wide, bears N. 30° E. and S. 30° W.
63.15	Northwest edge of asphalt of Highway No. 160, bears N. 30° E. and S. 30° W.
66.35	Northwest right-of-way fence, bears N. 30° E. and S. 30° W.
80.00	The 1/4 sec. cor. of secs. 11 and 12.
-----	
<b>Subdivision of Section 14, T. 34 N., R. 13 E., Gila and Salt River Meridian, Arizona</b>	
-----	
	From the 1/4 sec. cor. of secs. 14 and 23.
	N. 0°01' W., on the N. and S. center line of sec. 14.
11.45	Dirt road, 10 ft. wide, bears S. 45° E. and N. 50° W.
20.90	Southeast right-of-way fence, bears N. 30° E. and S. 30° W.
23.35	Southeast edge of asphalt of Highway No. 160, 36 ft. wide, bears N. 30° E. and S. 30° W.
24.05	Utility line, 2 wire, bears S. 68° E. and N. 68° W.
24.45	Northwest edge of asphalt of Highway No. 160, bears N. 30° E. and S. 30° W.

Subdivision of Section 14,  
T. 34 N., R. 13 E., Gila and Salt River Meridian, Arizona

CHAINS	
29.80	Northwest right-of-way fence, bears N. 30° E. and S. 30° W.
37.55	Dirt road, 8 ft. wide, bears N. 20° E. and S. 25° W.
40.00	Point for the center 1/4 sec. cor. of sec. 14, at intersection with the E. and W. center line.
	Set a standard monument, 26 ins. in the ground, mkd.
	T 34 N R 13 E C 1/4 S 14
	2013
	Set a steel "T-Post" fence post near cor.
	From this point an Arizona DOT right-of-way monument, bears S. 73°36' E. 5.37 chs. dist., monumented with a brass tablet, 3 1/2 ins. diam., set in concrete, 8 ins. diam., projecting 6 ins. above the ground, with a 4 in. angle iron, projecting 15 ins. above the ground nearby.
	From this same point an Arizona DOT right-of-way monument, bears S. 67°05' E. 9.84 chs. dist., monumented with a brass tablet, 3 1/2 ins. diam., set in concrete, 8 ins. diam., projecting 6 ins. above the ground, with a 4 in. angle iron, projecting 15 ins. above the ground nearby.
41.15	Dirt road, 8 ft. wide, bears S. 15° E. and N. 20° W.
80.00	The 1/4 sec. cor. of secs. 11 and 14.
	From the 1/4 sec. cor. of secs. 13 and 14.
	West, on the E. and W. center line of sec. 14.
28.65	Southeast right-of-way fence, bears N. 30° E. and S. 30° W.
30.10	Southeast edge of asphalt of Highway No. 160, 36 ft. wide, bears N. 30° E. and S. 30° W.
30.75	Northwest edge of asphalt of Highway No. 160, bears N. 30° E. and S. 30° W.
33.95	Northwest right-of-way fence, bears N. 30° E. and S. 30° W.
39.80	Dirt road, 8 ft. wide, bears N. and S.
40.00	The center 1/4 sec. cor. of sec. 14.
52.90	Utility line, 2 wire, bears N. 21° E. and S. 21° W.
80.00	The 1/4 sec. cor. of secs. 14 and 15.



Subdivision of Section 19,  
T. 34 N., R. 13 E., Gila and Salt River Meridian, Arizona

CHAINS	
	From the 1/4 sec. cor. of secs. 19 and 30.
	N. 0°04' W., on the N. and S. center line of sec. 19.
30.85	Southwest right-of-way fence, bears S. 50° E. and N. 50° W.
32.65	Centerline of Indian Route 21, paved road, 26 ft. wide, bears S. 50° E. and N. 50° W.
34.40	Northeast right-of-way fence, bears S. 50° E. and N. 50° W.
40.00	Point for the center 1/4 sec. cor. of sec. 19, at intersection with the E. and W. center line.
	Set a standard monument, 28 ins. in the ground, mkd.
	T 34 N R 13 E C 1/4 S 19
	2013
	Set a steel "T-Post" fence post near cor.
	From this point a B.I.A. Roads right-of-way monument, bears S. 7°12' W. 5.215 chs. dist., monumented with an alum. tablet, 3 ins. diam., set in concrete, with a 4 in. angle iron nearby.
	From this same point a B.I.A. Roads right-of-way monument, bears S. 16°13' W. 8.07 chs. dist., monumented with an alum. tablet, 3 ins. diam., set in concrete, with a 4 in. angle iron nearby.
80.00	The 1/4 sec. cor. of secs. 18 and 19.
	<hr/>
	From the 1/4 sec. cor. of secs. 19 and 20.
	West, on the E. and W. center line of sec. 19.
40.00	The center 1/4 sec. cor. of sec. 19.
47.75	Northeast right-of-way fence, bears S. 40° E. and N. 40° W.
50.00	Centerline of Indian Route 21, paved road, 26 ft. wide, bears S. 40° E. and N. 40° W.
52.15	Southwest right-of-way fence, bears S. 40° E. and N. 40° W.
79.25	The 1/4 sec. cor. of secs. 20 and 21.
	<hr/>

**Subdivision of Section 20,  
T. 34 N., R. 13 E., Gila and Salt River Meridian, Arizona**

CHAINS	
	From the 1/4 sec. cor. of secs. 20 and 29.
	N. 0°03' W., on the N. and S. center line of sec. 20.
40.00	Point for the center 1/4 sec. cor. of sec. 20, at intersection with the E. and W. center line.
	Set a standard monument, 26 ins. in the ground, mkd.
	T 34 N R 13 E C 1/4 S 20
	2013
	Set a steel "T-Post" fence post near cor.
80.00	The 1/4 sec. cor. of secs. 17 and 20.
	<hr/>
	From the 1/4 sec. cor. of secs 20 and 21.
	West, on the E. and W. centerline of sec. 20.
10.95	Graded road, 27 ft. wide, bears S. 2° E. and N. 2° W.
40.00	The center 1/4 sec. cor. of sec. 20.
80.00	The 1/4 sec. cor. of secs. 19 and 20.
	<hr/>
	<b>Subdivision of Section 22, T. 34 N., R. 13 E., Gila and Salt River Meridian, Arizona</b>
	<hr/>
	From the 1/4 sec. cor. of secs. 22 and 27.
	N. 0°02' W., on the N. and S. center line of sec. 22.
40.00	Point for the center 1/4 sec. cor. of sec. 22, at intersection with the E. and W. center line.
	Set a standard monument, 26 ins. in the ground, mkd.
	T 34 N R 13 E C 1/4 S 22
	2013
	Set a steel "T-Post" fence post near cor.
80.00	The 1/4 sec. cor. of secs. 15 and 22.
	<hr/>

Subdivision of Section 22,  
T. 34 N., R. 13 E., Gila and Salt River Meridian, Arizona

CHAINS	
	From the 1/4 sec. cor. of secs. 22 and 23.
	West, on the E. and W. center line of sec. 22.
1.55	Northwest right-of-way fence, bears N. 30° E. and S. 30° W.
40.00	The center 1/4 sec. cor. of sec. 22.
80.00	The 1/4 sec. cor. of secs. 21 and 22.
<hr/> <p>Subdivision of Section 23, T. 34 N., R. 13 E., Gila and Salt River Meridian, Arizona</p> <hr/>	
	From the 1/4 sec. cor. of secs. 23 and 26.
	N. 0°01' W., on the N. and S. center line of sec. 23.
16.05	Indian Route 6011, graded road, 30 ft. wide, bears N. 50° E. and S. 50° W.
36.15	Dirt road, 8 ft. wide, bears N. 60° E. and S. 60° W.
36.60	Questar Southern Trails underground gas pipeline, bears N. 35° E. and S. 35° W.
40.00	Point for the center 1/4 sec. cor. of sec. 23, at intersection with the E. and W. center line.
	Set a standard monument, 26 ins. in the ground, mkd.
	<p>T 34 N R 13 E C 1/4 S 23</p> <p>2013</p>
	Set a steel "T-Post" fence post near cor.
80.00	The 1/4 sec. cor. of secs. 14 and 23.
<hr/>	
	From the 1/4 sec. cor. of secs. 23 and 24.
	West, on the E. and W. center line of sec. 23.
37.55	Questar Southern Trails underground gas pipeline, bears N. 35° E. and S. 35° W.
40.00	The center 1/4 sec. cor. of sec. 23.
76.26	Southeast right-of-way fence, bears N. 30° E. and S. 30° W.

**Subdivision of Section 23,  
T. 34 N., R. 13 E., Gila and Salt River Meridian, Arizona**

CHAINS	
77.70	Southeast edge of asphalt of Highway No. 160, 36 ft. wide, bears N. 30° E. and S. 30° W.
78.35	Northwest edge of asphalt of Highway No. 160, bears N. 30° E. and S. 30° W.
80.00	The 1/4 sec. cor. of secs. 22 and 23.
<hr/> <p><b>Subdivision of Section 27, T. 34 N., R. 13 E., Gila and Salt River Meridian, Arizona</b></p> <hr/>	
	From the 1/4 sec. cor. of secs. 27 and 34.
	N. 0°02' W., on the N. and S. center line of sec. 27.
1.45	Questar Southern Trails underground gas pipeline, bears N. 35° E. and S. 35° W.
21.35	North bank of Red Lake dry lake bed, bears S. 50° E. and S. 70° W.
40.00	Point for the center 1/4 sec. cor. of sec. 27, at intersection with the E. and W. center line.
	Set a standard monument, 26 ins. in the ground, mkd.
	<p>T 34 N R 13 E C 1/4 S 27</p> <p>2013</p>
	Set a steel "T-Post" fence post near cor.
50.25	Utility line, 5 wire, bears N. 40° E. and S. 40° W.
51.20	Southeast right-of-way fence, bears N. 50° E. and S. 50° W.
52.90	Southeast edge of asphalt of Highway No. 160, 36 ft. wide, bears N. 50° E. and S. 50° W.
53.65	Northwest edge of asphalt of Highway No. 160, bears N. 50° E. and S. 50° W.
57.85	Northwest right-of-way fence, bears N. 40° E. and S. 40° W.
80.00	The 1/4 sec. cor. of secs. 22 and 27.
	<hr/> <p>From the 1/4 sec. cor. of secs. 26 and 27.</p> <p>West, on the E. and W. center line of sec. 27.</p>

**Subdivision of Section 27,  
T. 34 N., R. 13 E., Gila and Salt River Meridian, Arizona**

CHAINS	
13.15	Questar Southern Trails underground gas pipeline, bears N. 35° E. and S. 35° W.
40.00	The center 1/4 sec. cor. of sec. 27.
57.80	Utility line, 5 wire, bears N. 60° E. and S. 60° W.
60.20	Southeast right-of-way fence, bears N. 65° E. and S. 65° W.
63.05	Southeast edge of asphalt of Highway No. 160, 36 ft. wide, bears N. 65° E. and S. 65° W.
64.35	Northwest edge of asphalt of Highway No. 160, bears N. 65° E. and S. 65° W.
66.10	Northwest right-of-way fence, bears N. 65° E. and S. 65° W.
70.90	Barbed wire fence, bears N. 65° E. and S. 65° W.
80.00	The 1/4 sec. cor. of secs. 27 and 28.
<hr/> <p><b>Subdivision of Section 28, T. 34 N., R. 13 E., Gila and Salt River Meridian, Arizona</b></p> <hr/>	
	From the 1/4 sec. cor. of secs. 28 and 33.
	N. 0°02' W., on the N. and S. center line of sec. 28.
0.15	Utility line, 2 wire, bears N. 32° E. and S. 32° W.
3.75	Chain link fence, 6 ft. high, bears N. 65° E. and S. 65° W.
12.35	Paved road, 20 ft. wide, bears N. 65° E. and S. 65° W.
12.65	Southeast right-of-way fence, bears N. 65° E. and S. 65° W.
13.30	Southeast edge of asphalt of Highway No. 160, 46 ft. wide, bears N. 65° E. and S. 65° W.
14.05	Northwest edge of asphalt of Highway No. 160, bears N. 65° E. and S. 65° W.
16.60	Northwest right-of-way fence, bears N. 65° E. and S. 65° W.
20.60	Utility line, 5 wire, bears S. 63° E. and N. 63° W.
40.00	Point for the center 1/4 sec. cor. of sec. 28, at intersection with the E. and W. center line.
	Set a standard monument, 24 ins. in the ground, mkd.

**Subdivision of Section 28,  
T. 34 N., R. 13 E., Gila and Salt River Meridian, Arizona**

CHAINS	
	T 34 N R 13 E C 1/4 S 28
	2013
	Set a steel "T-Post" fence post near cor.
	From this point, the most easterly cor. of a chain link fence surrounding the School Tract, approx. 685 x 1345 ft., bears S. 7°39' W. 7.34 chs. dist.
80.00	The 1/4 sec. cor. of secs. 21 and 28.
	<hr/>
	From the 1/4 sec. cor. of secs. 27 and 28.
	West, on the E. and W. center line of sec. 28.
40.00	The center 1/4 sec. cor. of sec. 28.
66.35	Utility line, 2 wire, bears S. 60° E. and N. 60° W.
66.60	Northeast right-of-way fence, bears S. 45° E. and N. 45° W.
69.00	Centerline of Indian Route 21, paved road, 26 ft. wide, bears S. 45° E. and N. 45° W.
71.40	Southwest right-of-way fence, bears S. 45° E. and N. 45° W.
77.50	Utility line, 6 wire, bears S. 63° E. and N. 63° W.
80.00	The 1/4 sec. cor. of secs. 28 and 29.
	<hr/>
	<b>Subdivision of Section 29, T. 34 N., R. 13 E., Gila and Salt River Meridian, Arizona</b>
	<hr/>
	From the 1/4 sec. cor. of secs. 29 and 32.
	N. 0°03' W., on the N. and S. center line of sec. 29.
36.40	Waterline, bears S. 70° E. and S. 70° W.
36.65	Dirt road, 10 ft. wide, bears S. 70° E. and N. 70° W.
40.00	Point for the center 1/4 sec. cor. of sec. 29, at intersection with the E. and W. center line.
	Set a standard monument, 28 ins. in the ground, underpinned with an alum. rod, 36 ins. long, 3/4 in. diam., 54 ins. in the ground, mkd.

**Subdivision of Section 29,  
T. 34 N., R. 13 E., Gila and Salt River Meridian, Arizona**

CHAINS	
	T 34 N R 13 E C 1/4 S 29  2013
	Set a steel "T-Post" fence post near cor.
65.70	Southwest right-of-way fence, bears S. 70° E. and N. 70° W.
67.40	Centerline of Indian Route 21, paved road, 26 ft. wide, bears S. 70° E. and N. 70° W.
69.10	Northeast right-of-way fence, bears S. 70° E. and N. 70° W.
80.00	The 1/4 sec. cor. of secs. 20 and 29.
	<hr/>
	From the 1/4 sec. cor. of secs. 28 and 29.
	West, on the E. and W. center line of sec. 29.
40.00	The center 1/4 sec. cor. of sec. 29.
63.10	Utility line, 5 wire, bears N. 20° E. and S. 20° W.
80.00	The 1/4 sec. cor. of secs. 29 and 30.
	<hr/>
	<b>Subdivision of Section 31, T. 34 N., R. 13 E., Gila and Salt River Meridian, Arizona</b>
	From the 1/4 sec. cor. of secs. 6 and 31, on the S. bdy. Of the Tp., monumented with a stainless steel post, 2 1/2 ins. diam., firmly set, projecting 9 ins. above the ground, with brass cap mkd. T34N R13E S31 1/4 S6 T33N 2002. Set a steel "T-Post" fence post near cor. and add marks 2013 to brass cap.
	N. 0°04' W., on the N. and S. center line of sec. 31.
39.10	Utility line, 2 wire, bears S. 50° E. and N. 50° W.
40.00	Point for the center 1/4 sec. cor. of sec. 31, at intersection with the E. and W. center line.
	Set a standard monument, 28 ins. in the ground, mkd.
	T 34 N R 13 E C 1/4 S 31  2013
	Set a steel "T-Post" fence post near cor.

**Subdivision of Section 31,  
T. 34 N., R. 13 E., Gila and Salt River Meridian, Arizona**

CHAINS	
80.00	The 1/4 sec. cor. of secs. 30 and 31. <hr/>
	From the 1/4 sec. cor. of secs. 31 and 32. West, on the E. and W. center line of sec. 31.
4.55	Dirt road, 10 ft. wide, bears S. 40° E. and N. 40° W.
25.85	Utility line, 5 wire, bears N. 45° E. and S. 45° W.
28.25	Waterline, bears N. 55° E. and S. 55° W.
40.00	The center 1/4 sec. cor. of sec. 31.
79.425	The 1/4 sec. cor. of sec. 31 only. <hr/>
	<b>Subdivision of Section 32, T. 34 N., R. 13 E., Gila and Salt River Meridian, Arizona</b> <hr/>
	From the 1/4 sec. cor. of secs. 5 and 32, on the S. bdy. Of the Tp., monumented with a stainless steel post, 2 1/2 ins. diam., firmly set, projecting 14 ins. above the ground, with brass cap mkd. T34N R13E S32 1/4 S5 T33N 2002. Add marks 2013 to brass cap.
	N. 0°03' W., on the N. and S. center line of sec. 32.
32.95	Southeast right-of-way fence, bears N. 50° E. and S. 50° W.
34.55	Southeast edge of asphalt of Highway No. 160, 32 ft. wide, bears N. 50° E. and S. 50° W.
35.20	Northwest edge of asphalt of Highway No. 160, bears N. 50° E. and S. 50° W.
37.70	Paved road, 12 ft. wide, bears N. 50° E. and S. 50° W.
38.75	Northwest right-of-way fence, bears N. 50° E. and S. 50° W.
40.00	Point for the center 1/4 sec. cor. of sec. 32, at intersection with the E. and W. center line.  Set a standard monument, 28 ins. in the ground, underpinned with an alum. rod, 36 ins. long, 3/4 in. diam., 51 ins. in the ground, mkd.
	T 34 N R 13 E C 1/4 S 32  2013



**Subdivision of Section 32,  
T. 34 N., R. 13 E., Gila and Salt River Meridian, Arizona**

CHAINS	
	Set a steel "T-Post" fence post near cor.
80.00	The 1/4 sec. cor. of secs. 29 and 32.
<hr/>	
	From the 1/4 sec. cor. of secs. 32 and 33.
	West, on the E. and W. center line of sec. 32.
31.30	Southeast right-of-way fence, bears N. 50° E. and S. 50° W.
33.30	Southeast edge of asphalt of Highway No. 160, 32 ft. wide, bears N. 50° E. and S. 50° W.
34.05	Northwest edge of asphalt of Highway No. 160, bears N. 50° E. and S. 50° W.
38.50	Northwest right-of-way fence, bears N. 50° E. and S. 50° W.
40.00	The center 1/4 sec. cor. of sec. 32.
42.50	Graded road, 12 ft. wide, bears S. 50° E. and N. 50° W.
56.20	Utility line, 2 wire, bears N. 45° E. and S. 45° W.
60.75	Indian Route 6262, graded road, 36 ft. wide, bears N. and S.
61.30	Waterline, bears N. and S.
80.00	The 1/4 sec. cor. of secs. 31 and 32.
<hr/>	
<p><b>Subdivision of Section 33, T. 34 N., R. 13 E., Gila and Salt River Meridian, Arizona</b></p>	
<hr/>	
	From the 1/4 sec. cor. of secs. 4 and 33, on the S. bdy. of the Tp.
	N. 0°02' W., on the N. and S. center line of sec. 33.
40.00	Point for the center 1/4 sec. cor. of sec. 33, at intersection with the E. and W. center line.
	Set a standard monument, 26 ins. in the ground, mkd.
<p>T 34 N R 13 E C 1/4 S 33</p> <p>2013</p>	
	Set a steel "T-Post" fence post near cor.
80.00	The 1/4 sec. cor. of secs. 28 and 33.
<hr/>	

Subdivision of Section 33,  
T. 34 N., R. 13 E., Gila and Salt River Meridian, Arizona

CHAINS	<p>From the 1/4 sec. cor. of secs. 33 and 34.</p> <p>West, on the E. and W. center line of sec. 33.</p> <p>40.00 The center 1/4 sec. cor. of sec. 33.</p> <p>80.00 The 1/4 sec. cor. of secs. 29 and 30.</p> <hr/> <p style="text-align: center;">GENERAL DESCRIPTION</p> <hr/> <p>The community of Tonalea, also called Red Lake, lies in section 28, near the intersection of Highway 160 and Indian Route 21. Highway 160 runs northeasterly and southwesterly through the township and Indian Route 21 runs northwesterly from its intersection with Highway 160. Multiple graded and trail roads traverse through the township.</p> <p>The terrain is mostly rolling, with areas of sand dunes and sandstone outcrops.</p> <p>The elevation varies from 5,500 to 5,700 feet above sea level. The soil is mostly sand, with areas of sandstone outcrops and sand dunes, supporting a variety of native grasses. Salt cedar is abundant around the lake bed of Red Lake.</p> <p>According to the book "Native Roads: The Complete Motoring Guide to the Navajo and Hopi Nations, Newly Revised Edition", by Fran Kosik, the George Smith Historical Monument described in the tie from the 1/4 sec. cor. of secs. 27 and 28, was established by the Mormon Church in 1938 to mark the spot where George A. Smith, Jr., a member of Jacob Hamblin's party, was killed. The book also describes the "Elephant Feet", one of which was called out on the running of the sec. line bet. secs. 22 and 27, as "made of Cowsprings Sandstone, these giant formations look like a pair of elephant's legs and feet".</p> <p>The mean magnetic declination of 10 3/4° E. was derived from the United States Geological Survey computer program GEOMAG, utilizing the World Magnetic Model for the dates of survey.</p> <hr/>
--------	------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------




## CERTIFICATE OF SURVEY

We, Craig S. Dukart and Blas J. Urena, Cadastral Surveyors, HEREBY CERTIFY upon honor, that in pursuance of special instructions bearing date of the 21st day of October, 2013, we have dependently resurveyed a portion of Hopi-Navajo partition line segment "D", and surveyed a portion of the Third Guide Meridian East (West Boundary), the East and North Boundaries, the subdivisional lines, and the subdivision of certain sections, T. 34 N., R. 13 E., of the Gila and Salt River Meridian, in the State of Arizona, which are represented in the foregoing field notes as having been executed by us and under our direction. Said survey has been made in strict conformity with said special instructions, the Manual of Survey Instructions, 2009, and in specific manner described in the foregoing field notes.

9-8-2014

(Date)



(Cadastral Surveyor)

9-8-2014

(Date)



(Cadastral Surveyor)


## CERTIFICATE OF APPROVAL

BUREAU OF LAND MANAGEMENT  
Phoenix, Arizona

The foregoing field notes of the dependent resurvey of a portion of Hopi-Navajo partition line segment "D", and surveyed a portion of the Third Guide Meridian East (West Boundary), the East and North boundaries, the subdivisional lines, and the subdivision of certain sections, T. 34 N., R. 13 E., of the Gila and Salt River Meridian, in the State of Arizona, executed by Craig S. Dukart and Blas J. Urena, Cadastral Surveyors, having been critically examined and found correct, are hereby approved.

9/12/2014

(Date)



(Chief Cadastral Surveyor of Arizona)

~~CERTIFICATE OF TRANSCRIPT~~

~~I CERTIFY That the foregoing transcript of the field notes of the above described surveys in T. 34 N., R. 13 E., Gila and Salt River Meridian, Arizona, is a true copy of the original field notes.~~

~~(Date)~~

~~(Chief Cadastral Surveyor of Arizona)~~