

ORIGINAL

**UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT**

FIELD NOTES

OF THE SURVEY OF A PORTION OF THE
SECOND GUIDE MERIDIAN EAST (WEST BOUNDARY),

AND

THE SUBDIVISIONAL LINES,

AND

SUBDIVISION OF CERTAIN SECTIONS

TOWNSHIP 39 NORTH, RANGE 9 EAST,

OF THE GILA AND SALT RIVER MERIDIAN,

IN THE STATE OF ARIZONA.

EXECUTED BY

Fabian Yazzie, Cadastral Surveyor

Under Special Instructions dated August 4, 2014, approved August 4, 2014, which provided for the surveys included under Group No. 1136, and assignment instructions dated August 4, 2014.

Survey commenced August 7, 2014

Survey completed February 10, 2015

INDEX DIAGRAM

**TOWNSHIP 39 NORTH RANGE 9 EAST
GILA & SALT RIVER MERIDIAN, ARIZONA**

8	6	58	5	46	4	36	3	26	2	18	1
	58		57		45		35		26		17
7	7	56	8	44	9	34	10	25	11	16	12
	55		55		43		33		24		15
6	18	54	17	42	16	32	15	23	14	14	13
	53		52		41		31		22		14
6	19	51	20	40	21	31	22	22	23	13	24
	51		50		39		30		21		12
5	30	49	29	38	28	29	27	20	26	11	25
	48		48		37		28		19		10
4	31	47	32	36	33	27	34	18	35	9	36

Subdivision of Section 4 Pages 59-60
 Subdivision of Section 5 Pages 60-61
 Subdivision of Section 8 Pages 61-62
 Subdivision of Section 9 Pages 62-63
 Subdivision of Section 16 Pages 63-64
 Subdivision of Section 17 Pages 64-65
 Subdivision of Section 20 Pages 65-66
 Subdivision of Section 21 Pages 66-67
 Subdivision of Section 28 Pages 67-68
 Subdivision of Section 29 Pages 68-69
 Subdivision of Section 32 Page 69
 Subdivision of Section 33 Page 70

T. 39 N., R. 9 E., Gila and Salt River Meridian, Arizona

CHAINS

The following field notes describe the survey of a portion of the Second Guide Meridian East (West Boundary), and the subdivisional lines, and subdivision of certain sections, Township 39 North, Range 9 East, Gila and Salt River Meridian, Arizona.

The history of surveys pertaining to this survey is as follows:

Leonard R. Sandoval surveyed the north boundary during the survey of Township 40 North, Range 9 East in 2005. Fabian Yazzie surveyed the east boundary during the survey of Township 39 North, Range 10 East in 2013. Fabian Yazzie surveyed the south boundary during the survey of Township 38 North, Range 9 East in 2013.

The survey was executed in accordance with the specifications as set forth in the Manual of Surveying Instructions, (2009), and the Special Instructions dated August 4, 2014, for Group Number 1136, Arizona.

The true meridian direction and length of all lines were determined by real time kinematic global positioning system observations using Trimble Navigation R8 model receivers.

Geodetic control was derived from Global Positioning System (GPS) static observations post processed by National Geodetic Survey, Online Positioning User Service (OPUS), utilizing Continuously Operating Reference Stations (CORS) AI8805 FRED FREDONIA CORS, AI8820 FERN FERNO MESA CORS, DL1882 AZFL NAU FLAGSTAFF CORS, DJ8981 FST5 FLAGSTAFF 5 CORS, and DK8419 AZPG CITY OF PAGE CORS. The NAD 83 (2011) (EPOCH: 2010), geographic position of the corner of Townships 38 and 39 North, Ranges 8 and 9 East, is as follows:

Latitude: 36°43'45.954" N. Longitude: 111°28'43.531" W.

The geographic position of the corner of Townships 39 and 40 North, Ranges 9 and 10 East, is as follows:

Latitude: 36°48'59.118" N. Longitude: 111°22'15.363" W.

The mean magnetic declination is 11° E.

Survey of the Second Guide Meridian East (W. Bdy.),
T. 39 N., R. 9 E., Gila and Salt River Meridian, Arizona

CHAINS	
	<p>Beginning at the cor. of Tps. 38 and 39 N., Rs. 8 and 9 E., monumented with a stainless steel post, 2 1/2 ins. diam., firmly set, projecting 4 ins. above the ground, with brass cap mkd. T39N R8E R9E S36 S31 S1 S6 T38N 2013, with a steel fence post, firmly set nearby. Add the marks 2014 to the brass cap.</p> <p>North, on the 2nd Guide Meridian East, bet. secs. 31 and 36.</p> <p>Over gently rolling land, along the foothills of Circular White Ridge.</p>
31.55	Top of sandstone rim of Circular White Ridge, 80 ft. high, bears N. 25° E. and S. 30° W.
36.60	Base of sandstone rim of Circular White Ridge, 80 ft. high, bears N. 45° E. and S. 75° W.
40.00	Point for the 1/4 sec. cor. of secs. 31 and 36.
	<p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center;"> <p>T 39 N</p> <p>R 8 E R 9 E</p> <p>1/4</p> <p>S 36 S 31</p> <p>2014</p> </div> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p> <p>Set a steel fence post nearby.</p>
80.00	Point for the cor. of secs. 25, 30, 31, and 36.
	<p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 21 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center;"> <p>T 39 N</p> <p>R 8 E R 9 E</p> <p>S 25 S 30</p> <p>S 36 S 31</p> <p>2014</p> </div> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p> <p>Set a steel fence post nearby.</p>

Survey of the Second Guide Meridian East (W. Bdy.),
T. 39 N., R. 9 E., Gila and Salt River Meridian, Arizona

CHAINS	
	<p>Cor. is located 1.45 chs. E. of trail road, bears S. 20° E. and N. 25° W.</p> <p>Land, gently rolling. Soil, sandy loam, limestone, and sandstone outcrops. Timber, juniper. Undergrowth, native grasses, sage brush, and rabbit brush.</p> <hr/>
	<p>North, bet. secs. 25 and 30.</p> <p>Over gently rolling land, on top of Circular White Ridge mesa.</p>
40.00	<p>Point for the 1/4 sec. cor. of secs. 25 and 30.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center;"> <p>T 39 N R 8 E R 9 E 1/4 S 25 S 30</p> <p>2014</p> </div> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p> <p>Set a steel fence post nearby.</p>
80.00	<p>Point for the cor. of secs. 19, 24, 25, and 30.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 21 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center;"> <p>T 39 N R 8 E R 9 E S 24 S 19 S 25 S 30</p> <p>2014</p> </div> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p> <p>Raise a mound of stone, 3 ft. base, 1 1/2 ft. high, W. of cor.</p> <p>Land, gently rolling. Soil, sandy loam, limestone, and sandstone outcrops. Timber, scattered juniper. Undergrowth, native grasses, rabbit brush, and Mormon tea.</p> <hr/>

Survey of the Second Guide Meridian East (W. Bdy.),
T. 39 N., R. 9 E., Gila and Salt River Meridian, Arizona

CHAINS	
	<p>North, bet. secs. 19 and 24.</p> <p>Over gently rolling land.</p> <p>40.00 Point for the 1/4 sec. cor. of secs. 19 and 24.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 21 ins. in solid sandstone bedrock, with brass cap mkd.</p> <div style="text-align: center;"> <p>T 39 N R 8 E R 9 E 1/4 S 24 S 19</p> <p>2014</p> </div> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p> <p>Set a steel fence post nearby.</p>
80.00	<p>Point for the cor. of secs. 13, 18, 19, and 24.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center;"> <p>T 39 N R 8 E R 9 E S 13 S 18 S 24 S 19</p> <p>2014</p> </div> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p> <p>Set a steel fence post nearby.</p> <p>Land, gently rolling and slightly broken. Soil, sandy loam and sandstone bedrock. Timber, scattered juniper. Undergrowth, native grasses, rabbit brush, prickly pear, and yucca.</p>
40.00	<hr/> <p>North, bet. secs. 13 and 18.</p> <p>Descending over gently rolling land.</p> <p>Point for the 1/4 sec. cor. of secs. 13 and 18.</p>

Survey of the Second Guide Meridian East (W. Bdy.),
T. 39 N., R. 9 E., Gila and Salt River Meridian, Arizona

CHAINS	
	<p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T 39 N R 8 E R 9 E 1/4 S 13 S 18</p> <p style="text-align: center;">2014</p> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p> <p>Set a steel fence post nearby.</p>
80.00	<p>Point for the cor. of secs. 7, 12, 13, and 18.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 25 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T 39 N R 8 E R 9 E S 12 S 7 S 13 S 18</p> <p style="text-align: center;">2014</p> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p> <p>Set a steel fence post nearby.</p> <p>Land, gently rolling and broken. Soil, sandy loam and sandstone bedrock. Timber, sparse juniper. Undergrowth, native grasses, salt brush, prickly pear, yucca, cholla cactus, and Mormon tea.</p>
40.00	<p>North, bet. secs. 7 and 12.</p> <p>Descending over gently rolling land.</p> <p>Point for the 1/4 sec. cor. of secs. 7 and 12.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p>

Survey of the Second Guide Meridian East (W. Bdy.),
T. 39 N., R. 9 E., Gila and Salt River Meridian, Arizona

CHAINS	
	<p style="text-align: center;">T 39 N R 8 E R 9 E 1/4 S 12 S 7 2014</p> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p> <p>Set a steel fence post nearby.</p> <p>Cor. is located at the bottom of a canyon valley, 2.30 chs. N. of sandy ridge top, bears N. 25° E. and S. 25° W.</p>
47.45	Wash, 40 ft. wide, 8 ft. deep, drains N. 35° E.
80.00	Point for the cor. of secs. 1, 6, 7, and 12.
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 25 ins. in the ground, with brass cap mkd.
	<p style="text-align: center;">T 39 N R 8 E R 9 E S 1 S 6 S 12 S 7 2014</p> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p> <p>Set a steel fence post nearby.</p> <p>Cor. is located 2.55 chs. N. of wash, 40 ft. wide, 6 ft. deep, drains N. 60° E.</p> <p>Land, gently rolling and broken. Soil, sandy loam and sandstone bedrock. No timber. Undergrowth, native grasses, sage brush, and Mormon tea.</p> <hr/> <p>North, bet. secs. 1 and 6.</p> <p>Over rolling land, through Water Holes Canyon valley.</p>
40.00	Point for the 1/4 sec. cor. of secs. 1 and 6.
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.

Survey of the Second Guide Meridian East (W. Bdy.),
T. 39 N., R. 9 E., Gila and Salt River Meridian, Arizona

CHAINS	
	<p style="text-align: center;">T 39 N R 8 E R 9 E 1/4 S 1 S 6 2014</p> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p> <p>Set a steel fence post nearby, and raise a mound of stone, 3 ft. base, 1 ft. high, W. of cor.</p> <p>Cor. is located 35 lks. N. of sandstone cliff edge, 150 ft. high, bears N. 10° E. and S. 30° W.</p>
80.00	<p>The true point of Tps. 39 and 40 N., Rs. 8 and 9 E.</p> <p>from this true point</p> <p style="padding-left: 40px;">The witness cor. of Tps. 39 and 40 N., Rs. 8 and 9 E., bears N. 24°00' E., 50 lks. dist., monumented with a brass tablet, 3 1/4 ins. diam., firmly set, flush with the surface of sandstone bedrock, with top mkd. WC T40N R8E R9E S36 S31 S1 S6 T39N 2005 2013. Add the marks 2014 to the brass cap.</p> <p>Land, rolling and broken. Soil, sandy loam and sandstone bedrock. Timber, scattered juniper. Undergrowth, native grasses, greasewood, sage brush, and Mormon tea.</p> <hr/> <p style="text-align: center;">Survey of the Subdivisional Lines, T. 39 N., R. 9 E., Gila and Salt River Meridian, Arizona</p> <hr/> <p>From the cor. of secs. 1, 2, 35, and 36, on the S. bdy. of the Tp., monumented with a stainless steel post, 2 1/2 ins. diam., firmly set, projecting 4 ins. above the ground, with brass cap mkd. T39N R9E S35 S36 S2 S1 T38N 2013. Add the marks 2014 to the brass cap.</p> <p>N. 0°01' W., bet. secs. 35 and 36.</p> <p>Over gently rolling land.</p>
40.00	<p>Point for the 1/4 sec. cor. of secs. 35 and 36.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 25 ins. in the ground, with brass cap mkd.</p>

Survey of the Subdivisional Lines,
T. 39 N., R. 9 E., Gila and Salt River Meridian, Arizona

CHAINS	
	T 39 N R 9 E 1/4 S 35 S 36 2014
	Deposit a magnet, in a white plastic case, at the base of the stainless steel post. Set a steel fence post nearby.
49.20	Barbed wire fence, 5 strand, bears N. 80° E. and S. 80° W.
80.00	Point for the cor. of secs. 25, 26, 35, and 36. Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with brass cap mkd.
	T 39 N R 9 E S 26 S 25 S 35 S 36 2014
	Deposit a magnet, in a white plastic case, at the base of the stainless steel post. Set a steel fence post nearby. Cor. is located on the NE edge of an abandoned trail road, bears S. 50° E. and N. 50° W. Land, slightly rolling to flat. Soil, sandy loam. Timber, juniper. Undergrowth, native grasses, greasewood, salt brush, rabbit brush, yucca, and Mormon tea.
	<hr/> From the cor. of secs. 25, 30, 31, and 36, on the E. bdy. of the Tp., monumented with a stainless steel post, 2 1/2 ins. diam., firmly set, projecting 4 ins. above the ground, with a steel fence post, W. of cor., with brass cap mkd. T39N R9E R10E S25 S30 S36 S31 2013. Add the marks 2014 to the brass cap.
	West, bet. secs. 25 and 36. Over gently rolling land.
40.00	Point for the 1/4 sec. cor. of secs. 25 and 36. Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 25 ins. in the ground, with brass cap mkd.

Survey of the Subdivisional Lines,
T. 39 N., R. 9 E., Gila and Salt River Meridian, Arizona

CHAINS	
	T 39 N R 9 E S 25 1/4 ——— S 36 2014
	Deposit a magnet, in a white plastic case, at the base of the stainless steel post. Set a steel fence post nearby. Cor. is located 20 lks. N. of trail road, bears N. 70° E. and S. 75° W.
75.00	Barbed wire fence, 5 strand, bears N. 25° E. and S. 25° W.
80.00	The cor. of secs. 25, 26, 35, and 36. Land, slightly rolling. Soil, sandy loam. Timber, scattered juniper. Undergrowth, native grasses, salt brush, and prickly pear.
	N. 0°01' W., bet. secs. 25 and 26. Over gently rolling land.
36.80	Sandy finger ridge, 50 ft. high, 150 ft. wide, bears S. 20° E. and N. 25° W.
40.00	Point for the 1/4 sec. cor. of secs. 25 and 26. Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 23 ins. in the ground, with brass cap mkd.
	T 39 N R 9 E 1/4 S 26 S 25 2014
	Deposit a magnet, in a white plastic case, at the base of the stainless steel post. Set a steel fence post nearby. Cor. is located 1.30 chs. S. of wash, 15 ft. wide, 10 ft. deep, drains N. 20° W.
80.00	Point for the cor. of secs. 23, 24, 25, and 26.

Survey of the Subdivisional Lines,
T. 39 N., R. 9 E., Gila and Salt River Meridian, Arizona

<p>CHAINS</p>	<p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 23 ins. in solid sandstone bedrock, with brass cap mkd.</p> <p style="text-align: center;"> T 39 N R 9 E S 23 S 24 S 26 S 25 </p> <p style="text-align: center;">2014</p> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p> <p>Set a steel fence post nearby.</p> <p>Land, broken canyon land with sandstone cliffs. Soil, sandy loam and sandstone bedrock. Timber, juniper. Undergrowth, native grasses, cliff rose, salt brush, and Mormon tea.</p> <hr/> <p>From the cor. of secs. 19, 24, 25, and 30, on the E. bdy. of the Tp., monumented with a stainless steel post, 2 1/2 ins. diam., firmly set, projecting 4 ins. above the ground, with a steel fence post, W. of cor., with brass cap mkd. T39N R9E R10E S24 S19 S25 S30 2013. Add the marks 2014 to the brass cap.</p> <p>West, bet. secs. 24 and 25.</p> <p>Over gently rolling land.</p> <p>40.00 Point for the 1/4 sec. cor. of secs. 24 and 25.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;"> T 39 N R 9 E S 24 1/4 ——— S 25 </p> <p style="text-align: center;">2014</p> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p> <p>Cor. is located on E. edge of easterly trail road, and 35 lks. E. of westerly trail road, bears S. 45° E. and N. 5° W., and 75 lks. E. of sandstone shelf, 2 ft. high, bears N. 15° E. and S. 25° W.</p> <p>75.35 Wash, 30 ft. wide, 3 ft. deep, drains N. 50° E.</p>
---------------	---

Survey of the Subdivisional Lines,
T. 39 N., R. 9 E., Gila and Salt River Meridian, Arizona

CHAINS	
80.00	<p>The cor. of secs. 23, 24, 25, and 26.</p> <p>Land, gently rolling and broken. Soil, sandy loam. Timber, juniper. Undergrowth, native grasses, cliff rose, salt brush, and Mormon tea.</p> <hr/> <p>N. 0°01' W., bet. secs. 23 and 24.</p> <p>Over rolling land.</p>
40.00	<p>Point for the 1/4 sec. cor. of secs. 23 and 24.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 27 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center;"> <p>T 39 N R 9 E 1/4 S 23 S 24</p> <p>2014</p> </div> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p> <p>Set a steel fence post nearby.</p> <p>Cor. is located N. 25° E., 4.6 lks. dist. from a forked juniper, 14 ins. diam., and 32 ins. diam. at the crown, not marked, and is 85 lks. S. of wash, 30 ft. wide, 2 ft. deep, drains N. 50° W.</p>
80.00	<p>Point for the cor. of secs. 13, 14, 23, and 24.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 23 ins. in solid sandstone bedrock, with brass cap mkd.</p> <div style="text-align: center;"> <p>T 39 N R 9 E S 14 S 13 S 23 S 24</p> <p>2014</p> </div> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p> <p>Raise a mound of stone, 4 ft. base, 2 ft. high, W. of cor.</p>

Survey of the Subdivisional Lines,
T. 39 N., R. 9 E., Gila and Salt River Meridian, Arizona

CHAINS	
	<p>Cor. is located 27 lks. N. and 24 lks. W. of the northerly rim of box canyon, 10 ft. wide, 5 ft. high, bears N. 40° E. and S. 70° W., and 43 lks. N. of the southerly rim of the same box canyon, bears N. 70° E. and S. 85° W.</p> <p>Land, gently rolling and broken canyon land. Soil, sandy loam and sandstone bedrock. Timber, scattered juniper. Undergrowth, native grasses, cliff rose, salt brush, and Mormon tea.</p> <hr/> <p>From the cor. of secs. 13, 18, 19, and 24, on the E. bdy. of the Tp., monumented with a stainless steel post, 2 1/2 ins. diam., firmly set, projecting 3 ins. above the ground, with a steel fence post, W. of cor., with brass cap mkd. T39N R9E R10E S13 S18 S24 S19 2013. Add the marks 2014 to the brass cap.</p> <p>West, bet. secs. 13 and 24.</p> <p>Over gently rolling land.</p>
40.00	<p>Point for the 1/4 sec. cor. of secs. 13 and 24.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in solid sandstone bedrock, with brass cap mkd.</p> <p style="text-align: center;">T 39 N R 9 E S 13 1/4 ——— S 24 2014</p> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p> <p>Raise a mound of stone, 3 ft. base, 2 ft. high, N. of cor.</p> <p>Cor. is located 1.05 chs. E. of wash, 10 ft. wide, 4 ft. deep, drains N. 15° W.</p>
80.00	<p>The cor. of secs. 13, 14, 23, and 24.</p> <p>Land, gently rolling and slightly broken. Soil, sandy loam and sandstone bedrock. Timber, scattered juniper. Undergrowth, native grasses, salt brush, and Mormon tea.</p> <hr/> <p>N. 0°01' W., bet. secs. 13 and 14.</p> <p>Over rolling land.</p>

Survey of the Subdivisional Lines,
T. 39 N., R. 9 E., Gila and Salt River Meridian, Arizona

CHAINS	
40.00	<p>Point for the 1/4 sec. cor. of secs. 13 and 14.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center;"> <p>T 39 N R 9 E 1/4 S 14 S 13</p> <p>2015</p> </div> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p> <p>Set a steel fence post nearby.</p>
47.35	<p>Wash, 80 ft. wide, 4 ft. deep, drains N. 50° E.</p>
80.00	<p>Point for the cor. of secs. 11, 12, 13, and 14.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 17 ins. in the ground to sandstone bedrock, in a supporting mound of stone, 3 ft. base, to top, with brass cap mkd.</p> <div style="text-align: center;"> <p>T 39 N R 9 E S 11 S 12 S 14 S 13</p> <p>2015</p> </div> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p> <p>Set a steel fence post nearby.</p> <p>Cor. is located 15 lks. N. and 70 lks. E. of wash, 8 ft. wide, 2 ft. deep, drains S. 75° E.</p> <p>Land, gently rolling and broken canyon land. Soil, sandy loam and sandstone bedrock. Timber, scattered juniper. Undergrowth, native grasses, cliff rose, salt brush, black brush, sage brush, and Mormon tea.</p> <hr/> <p>From the cor. of secs. 7, 12, 13, and 18, on the E. bdy. of the Tp., monumented with a stainless steel post, 2 1/2 ins. diam., firmly set, projecting 4 ins. above the ground, with a steel fence post, W. of cor., with brass cap mkd. T39N R9E R10E S12 S7 S13 S18 2013. Add the marks 2014 to the brass cap.</p> <p>West, bet. secs. 12 and 13.</p>

Survey of the Subdivisional Lines,
T. 39 N., R. 9 E., Gila and Salt River Meridian, Arizona

CHAINS	
	Over gently rolling land.
40.00	Point for the 1/4 sec. cor. of secs. 12 and 13. Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd. <div style="text-align: center;"> T 39 N R 9 E S 12 1/4 ——— S 13 2015 </div>
	Deposit a magnet, in a white plastic case, at the base of the stainless steel post.
	Set a steel fence post nearby.
	Cor. is located on the N. facing slope of sandy finger ridge, 25 ft. high, bears E. and N. 70° W., and 30 lks. S. of wash, 2 ft. wide, 1 ft. deep, drains N. 80° W.
80.00	The cor. of secs. 11, 12, 13, and 14. Land, gently rolling and broken. Soil, sandy loam and sandstone bedrock. Timber, scattered juniper. Undergrowth, native grasses, salt brush, black brush, sage brush, and Mormon tea.
	————— N. 0°01' W., bet. secs. 11 and 12.
	Over gently rolling land.
40.00	Point for the 1/4 sec. cor. of secs. 11 and 12. Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in solid sandstone bedrock, encircled with an embedded collar of stone, with brass cap mkd. <div style="text-align: center;"> T 39 N R 9 E 1/4 S 11 S 12 2014 </div>
	Deposit a magnet, in a white plastic case, at the base of the stainless steel post.
	Set a steel fence post nearby.

Survey of the Subdivisional Lines,
T. 39 N., R. 9 E., Gila and Salt River Meridian, Arizona

CHAINS									
76.45	Base of sandstone cliff, 30 ft. high, bears N. 65° E. and S. 65° W.								
80.00	<p>Point for the cor. of secs. 1, 2, 11, and 12.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <table border="1" data-bbox="795 525 1006 630"> <tr> <td>T 39 N</td> <td>R 9 E</td> </tr> <tr> <td>S 2</td> <td>S 1</td> </tr> <tr> <td>S 11</td> <td>S 12</td> </tr> </table> <p>2014</p> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p> <p>Set a steel fence post nearby.</p> <p>Cor. is located 50 lks. E. of sandstone cliff edge, 10 ft. high, bears N. 35° E. and S. 30° W., and 1.50 chs. E. of wash, 6 ft. wide, 10 ft. deep, drains N. 10° E.</p> <p>Land, gently rolling and broken. Soil, sandy loam and sandstone bedrock. No timber. Undergrowth, native grasses, black brush, cliff rose, and Mormon tea.</p> <hr/> <p>From the cor. of secs. 1, 6, 7, and 12, on the E. bdy. of the Tp., monumented with a stainless steel post, 2 1/2 ins. diam., firmly set, projecting 3 ins. above the ground, with a steel fence post, W. of cor., with brass cap mkd. T39N R9E R10E S1 S6 S12 S7 2013. Add the marks 2014 to the brass cap.</p> <p>West, bet. secs. 1 and 12.</p> <p>Over gently rolling land.</p>	T 39 N	R 9 E	S 2	S 1	S 11	S 12		
T 39 N	R 9 E								
S 2	S 1								
S 11	S 12								
40.00	<p>Point for the 1/4 sec. cor. of secs. 1 and 12.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <table border="1" data-bbox="779 1638 1006 1764"> <tr> <td>T 39 N</td> <td>R 9 E</td> </tr> <tr> <td></td> <td>S 1</td> </tr> <tr> <td>1/4</td> <td>_____</td> </tr> <tr> <td></td> <td>S 12</td> </tr> </table> <p>2014</p>	T 39 N	R 9 E		S 1	1/4	_____		S 12
T 39 N	R 9 E								
	S 1								
1/4	_____								
	S 12								

Survey of the Subdivisional Lines,
T. 39 N., R. 9 E., Gila and Salt River Meridian, Arizona

CHAINS	
80.00	<p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p> <p>Set a steel fence post nearby.</p> <p>The cor. of secs. 1, 2, 11, and 12.</p> <p>Land, rolling and broken. Soil, sandy loam and sandstone bedrock. No timber. Undergrowth, native grasses, salt brush, yucca, cliff rose, and Mormon tea.</p> <hr/>
40.00	<p>N. 0°01' W., bet. secs. 1 and 2.</p> <p>Descending into canyon valley.</p> <p>Point for the 1/4 sec. cor. of secs. 1 and 2.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T 39 N R 9 E 1/4 S 2 S 1 2014</p>
80.00	<p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p> <p>Set a steel fence post nearby.</p> <p>The cor. of secs. 1, 2, 35, and 36, on the N. bdy. of the Tp., monumented with a stainless steel post, 2 1/2 ins. diam., firmly set, projecting 4 ins. above the ground, with brass cap mkd. T40N R9E S35 S36 S2 S1 T39N 2005. Add the marks 2014 to the brass cap.</p> <p>Land, rolling and broken. Soil, sandy loam and sandstone bedrock. No timber. Undergrowth, native grasses, greasewood, sage brush, yucca, cliff rose, and Mormon tea.</p> <hr/> <p>From the cor. of secs. 2, 3, 34, and 35, on the S. bdy. of the Tp., monumented with a stainless steel post, 2 1/2 ins. diam., firmly set, flush with the surface of the ground, with steel fence posts, E. and W. of cor., with brass cap mkd. T39N R9E S34 S35 S3 S2 T38N 2013. Add the marks 2014 to the brass cap.</p>

Survey of the Subdivisional Lines,
T. 39 N., R. 9 E., Gila and Salt River Meridian, Arizona

CHAINS	
	<p>N. 0°01' W., bet. secs. 34 and 35.</p> <p>Over gently rolling land.</p>
40.00	<p>Point for the 1/4 sec. cor. of secs. 34 and 35.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T 39 N R 9 E 1/4 S 34 S 35</p> <p style="text-align: center;">2014</p> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p> <p>Raise a mound of stone, 2 1/2 ft. base, 2 ft. high, W. of cor.</p>
80.00	<p>Point for the cor. of secs. 26, 27, 34, and 35.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 25 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T 39 N R 9 E S 27 S 26 S 34 S 35</p> <p style="text-align: center;">2014</p> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p> <p>Set a steel fence post nearby.</p> <p>Land, gently rolling to rolling. Soil, sandy loam and sandstone bedrock. Timber, juniper. Undergrowth, native grasses, prickly pear, salt brush, sage brush, and Mormon tea.</p> <hr/> <p>From the cor. of secs. 25, 26, 35, and 36.</p> <p>West, bet. secs. 26 and 35.</p> <p>Over rolling canyon land.</p>
40.00	<p>Point for the 1/4 sec. cor. of secs. 26 and 35.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with brass cap mkd.</p>

Survey of the Subdivisional Lines,
T. 39 N., R. 9 E., Gila and Salt River Meridian, Arizona

CHAINS	
	T 39 N R 9 E S 26 1/4 ——— S 35 2014
	Deposit a magnet, in a white plastic case, at the base of the stainless steel post. Set a steel fence post nearby. Cor. is located 40 lks. W. of sandstone cliff, 8 ft. high, bears N. 20° E. and S. 20° W., and 45 lks. E. of wash, 4 ft. wide, 1 ft. deep, drains N.
80.00	The cor. of secs. 26, 27, 34, and 35. Land, broken canyon land. Soil, sandy loam and sandstone bedrock. Timber, juniper. Undergrowth, native grasses, cliff rose, salt brush, yucca, and Mormon tea.
	<hr/> N. 0°01' W., bet. secs. 26 and 27. Over rolling canyon land.
40.00	Point for the 1/4 sec. cor. of secs. 26 and 27. Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 23 ins. in the ground, with brass cap mkd.
	T 39 N R 9 E 1/4 S 27 S 26 2014
	Deposit a magnet, in a white plastic case, at the base of the stainless steel post. Set a steel fence post nearby. Cor. is located 2.90 chs. S. of wash, 10 ft. wide, 1 ft. deep, drains N. 55° W.
80.00	Point for the cor. of secs. 22, 23, 26, and 27. Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.

Survey of the Subdivisional Lines,
T. 39 N., R. 9 E., Gila and Salt River Meridian, Arizona

CHAINS	
	T 39 N R 9 E S 22 S 23 S 27 S 26 2014
	Deposit a magnet, in a white plastic case, at the base of the stainless steel post. Set a steel fence post nearby. Cor. is located 1.35 chs. E. of trail road, bears S. 35° E. and N. 25° W. Land, broken canyon land. Soil, sandy loam and sandstone bedrock. Timber, juniper. Undergrowth, native grasses, salt brush, yucca, and Mormon tea.
	<hr/> From the cor. of secs. 23, 24, 25, and 26. West, bet. secs. 23 and 26. Over gently rolling canyon land.
5.50	Top of sandstone ridge, 5 ft. high, bears N. 5° E. and S. 20° W.
40.00	Point for the 1/4 sec. cor. of secs. 23 and 26. Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with brass cap mkd.
	T 39 N R 9 E S 23 1/4 ——— S 26 2014
	Deposit a magnet, in a white plastic case, at the base of the stainless steel post. Set a steel fence post nearby.
80.00	The cor. of secs. 22, 23, 26, and 27. Land, gently rolling canyon land. Soil, sandy loam and sandstone bedrock. Timber, juniper. Undergrowth, native grasses, salt brush, yucca, sage brush, and Mormon tea.

Survey of the Subdivisional Lines,
T. 39 N., R. 9 E., Gila and Salt River Meridian, Arizona

CHAINS	<p>N. 0°01' W., bet. secs. 22 and 23.</p> <p>Over gently rolling land.</p>
40.00	<p>Point for the 1/4 sec. cor. of secs. 22 and 23.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T 39 N R 9 E 1/4 S 22 S 23</p> <p style="text-align: center;">2014</p> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p> <p>Set a steel fence post nearby.</p>
80.00	<p>Point for the cor. of secs. 14, 15, 22, and 23.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 25 ins. in solid sandstone bedrock, with brass cap mkd.</p> <p style="text-align: center;">T 39 N R 9 E S 15 S 14 S 22 S 23</p> <p style="text-align: center;">2014</p> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p> <p>Set a steel fence post in a mound of stone, 3 ft. base, 1 1/2 ft. high, W. of cor.</p> <p>Cor. is located 1.10 chs. S. and 1.40 chs. E. of a barbed wire fence, 5 strand, bears N. 50° E. and S. 50° W.</p> <p>Land, gently rolling and broken canyon land. Soil, sandy loam and sandstone bedrock. Timber, scattered juniper. Undergrowth, native grasses, black brush, cliff rose, salt brush, and Mormon tea.</p> <hr/> <p>From the cor. of secs. 13, 14, 23, and 24.</p> <p>West, bet. secs. 14 and 23.</p> <p>Over rolling canyon land.</p>

Survey of the Subdivisional Lines,
T. 39 N., R. 9 E., Gila and Salt River Meridian, Arizona

CHAINS	
40.00	<p>Point for the 1/4 sec. cor. of secs. 14 and 23.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 20 ins. in sandstone shelf, with brass cap mkd.</p> <div style="text-align: center;"> <p>T 39 N R 9 E</p> <p>S 14</p> <p>1/4 ———</p> <p>S 23</p> <p>2014</p> </div> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p> <p>Set a steel fence post in solid sandstone bedrock, 3.79 lks. N. of cor.</p> <p>Cor. is located on top of west edge of sandstone shelf, 3 ft. high, bears N. 5° E. and S. 5° E., raised a supporting mound of stone, 3 ft. base, to top, on downhill side.</p> <p>Cor. is also located 80 lks. W. of sandstone shelf, 6 ft. high, bears N. 5° E. and S. 5° E., and 90 lks. E. of another sandstone shelf, 20 ft. high, bears N. 30° E. and S. 50° W.</p>
80.00	<p>The cor. of secs. 14, 15, 22, and 23.</p> <p>Land, canyon land.</p> <p>Soil, sandy loam and sandstone bedrock.</p> <p>Timber, scattered juniper.</p> <p>Undergrowth, native grasses, cliff rose, salt brush, and Mormon tea.</p> <hr/> <p>N. 0°01' W., bet. secs. 14 and 15.</p> <p>Over rolling land.</p>
40.00	<p>Point for the 1/4 sec. cor. of secs. 14 and 15.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 23 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center;"> <p>T 39 N R 9 E</p> <p>1/4</p> <p>S 15 S 14</p> <p>2015</p> </div> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p>

Survey of the Subdivisional Lines,
T. 39 N., R. 9 E., Gila and Salt River Meridian, Arizona

CHAINS									
	Set a steel fence post nearby.								
80.00	Point for the cor. of secs. 10, 11, 14, and 15. Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 27 ins. in solid sandstone bedrock, with brass cap mkd. <div style="text-align: center;"> <table border="1"> <tr><td>T 39 N</td><td>R 9 E</td></tr> <tr><td>S 10</td><td>S 11</td></tr> <tr><td>S 15</td><td>S 14</td></tr> </table> <p>2014</p> </div>	T 39 N	R 9 E	S 10	S 11	S 15	S 14		
T 39 N	R 9 E								
S 10	S 11								
S 15	S 14								
	Deposit a magnet, in a white plastic case, at the base of the stainless steel post.								
	Set a steel fence post nearby.								
	Cor. is located 1.05 chs. N. of sandstone cliff top, 25 ft. high, bears S. 80° E. and W.								
	Land, broken canyon land. Soil, sandy loam and sandstone bedrock. Timber, sparse juniper. Undergrowth, native grasses, cliff rose, black brush, sage brush, salt brush, and Mormon tea.								
	From the cor. of secs. 11, 12, 13, and 14.								
	West, bet. secs. 11 and 14.								
	Over rolling canyon land.								
40.00	Point for the 1/4 sec. cor. of secs. 11 and 14. Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 17 ins. in solid sandstone bedrock, in a supporting mound of stone, 3 ft. base, to top, with brass cap mkd. <div style="text-align: center;"> <table border="1"> <tr><td>T 39 N</td><td>R 9 E</td></tr> <tr><td></td><td>S 11</td></tr> <tr><td>1/4</td><td>—</td></tr> <tr><td></td><td>S 14</td></tr> </table> <p>2015</p> </div>	T 39 N	R 9 E		S 11	1/4	—		S 14
T 39 N	R 9 E								
	S 11								
1/4	—								
	S 14								
	Deposit a magnet, in a white plastic case, at the base of the stainless steel post.								
	Set a steel fence post, 18.5 lks. dist., S. 40° W. of cor.								
80.00	The cor. of secs. 10, 11, 14, and 15.								

Survey of the Subdivisional Lines,
T. 39 N., R. 9 E., Gila and Salt River Meridian, Arizona

CHAINS	
	<p>Land, broken canyon land. Soil, sandy loam and sandstone bedrock. Timber, sparse juniper. Undergrowth, native grasses, cliff rose, black brush, and Mormon tea.</p> <hr/> <p>N. 0°01' W., bet. secs. 10 and 11.</p> <p>Descending into canyon valley.</p>
3.40	Wash, 20 ft. wide, 1 ft. deep, drains N. 75° E.
40.00	<p>Point for the 1/4 sec. cor. of secs. 10 and 11.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center;"> <p>T 39 N R 9 E 1/4 S 10 S 11</p> <p>2014</p> </div> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p> <p>Set a steel fence post nearby.</p>
75.80	Most easterly of two, high voltage transmission lines, bears N. 5° E. and S. 5° W.
80.00	<p>Point for the cor. of secs. 2, 3, 10, and 11.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center;"> <p>T 39 N R 9 E S 3 S 2 ----- S 10 S 11</p> <p>2014</p> </div> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p> <p>Set a steel fence post nearby.</p> <p>Cor. is located 30 lks. W. of easterly high voltage transmission line, bears N. 5° E. and S. 5° W., and 1.70 chs. E. of westerly high voltage transmission line, bears N. 5° E. and S. 5° W.</p>

Survey of the Subdivisional Lines,
T. 39 N., R. 9 E., Gila and Salt River Meridian, Arizona

CHAINS	
	<p>Land, broken, and gently rolling. Soil, sandy loam. No timber. Undergrowth, native grasses, greasewood, yucca, and Mormon tea.</p> <hr/> <p>From the cor. of secs. 1, 2, 11, and 12.</p> <p>West, bet. secs. 2 and 11.</p> <p>Over broken canyon land.</p>
40.00	<p>Point for the 1/4 sec. cor. of secs. 2 and 11.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 22 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T 39 N R 9 E S 2 1/4 ——— S 11</p> <p style="text-align: center;">2014</p> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p> <p>Set a steel fence post nearby.</p>
80.00	<p>The cor. of secs. 2, 3, 10, and 11.</p> <p>Land, broken, and gently rolling. Soil, sandy loam. No timber. Undergrowth, native grasses, greasewood, and Mormon tea.</p> <hr/> <p>N. 0°01' W., bet. secs. 2 and 3.</p> <p>Over gently rolling land, on top of mesa plateau.</p>
23.40	<p>Most westerly of two, high voltage transmission lines, bears N. 5° E. and S. 5° W.</p>
40.00	<p>Point for the 1/4 sec. cor. of secs. 2 and 3.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 22 ins. in the ground, encircled with a collar of stone, with brass cap mkd.</p>

Survey of the Subdivisional Lines,
T. 39 N., R. 9 E., Gila and Salt River Meridian, Arizona

CHAINS	
	T 39 N R 9 E 1/4 S 3 S 2 2014
	Deposit a magnet, in a white plastic case, at the base of the stainless steel post. Set a steel fence post nearby. Cor. is located 85 lks. S. of the southerly rim of box canyon, 62 ft. wide, 18 ft. high, bears N. 75° E. and S. 75° W., and 1.80 chs. S. of the northerly rim of the same box canyon, bears N. 65° E. and S. 65° W.
80.00	The cor. of secs. 2, 3, 34, and 35, on the N. bdy. of the Tp., monumented with a stainless steel post, 2 1/2 ins. diam., firmly set, projecting 4 ins. above the ground, with brass cap mkd. T40N R9E S34 S35 S3 S2 T39N 2005. Add the marks 2014 to the brass cap. Land, gently rolling and broken. Soil, sandy loam and sandstone bedrock. No timber. Undergrowth, native grasses, greasewood, sage brush, and Mormon tea.
	<hr/> From the cor. of secs. 3, 4, 33, and 34, on the S. bdy. of the Tp., monumented with a stainless steel post, 2 1/2 ins. diam., firmly set, projecting 2 ins. above the ground, with a steel fence post nearby, with brass cap mkd. T39N R9E S33 S34 S4 S3 T38N 2013. Add the marks 2014 to the brass cap. N. 0°02' W., bet. secs. 33 and 34. Over gently rolling land.
40.00	Point for the 1/4 sec. cor. of secs. 33 and 34. Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 22 ins. in the ground, with brass cap mkd.
	T 39 N R 9 E 1/4 S 33 S 34 2015
	Deposit a magnet, in a white plastic case, at the base of the stainless steel post. Set a steel fence post nearby.

Survey of the Subdivisional Lines,
T. 39 N., R. 9 E., Gila and Salt River Meridian, Arizona

CHAINS									
76.10	Wash, 12 ft. wide, 2 ft. deep, drains N. 30° E.								
80.00	Point for the cor. of secs. 27, 28, 33, and 34. Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 22 ins. in the ground, with brass cap mkd. <table style="margin-left: auto; margin-right: auto; border-collapse: collapse;"> <tr> <td style="padding: 0 10px;">T 39 N</td> <td style="padding: 0 10px;">R 9 E</td> </tr> <tr> <td style="border-right: 1px solid black; padding: 0 5px;">S 28</td> <td style="padding: 0 5px;">S 27</td> </tr> <tr> <td style="border-right: 1px solid black; padding: 0 5px;">S 33</td> <td style="padding: 0 5px;">S 34</td> </tr> </table> <p style="text-align: center;">2015</p> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p> <p>Set a steel fence post nearby.</p> <p>Cor. is located 80 lks. W. of wash, 12 ft. wide, 2 ft. deep, drains N. 50° E.</p> <p>Land, rolling, and slightly broken. Soil, sandy loam and sandstone bedrock. Timber, juniper. Undergrowth, native grasses, greasewood, salt brush, cliff rose, black brush, yucca, and Mormon tea.</p> <hr/> <p>From the cor. of secs. 26, 27, 34, and 35.</p> <p>West, bet. secs. 27 and 34.</p> <p>Over rolling land.</p>	T 39 N	R 9 E	S 28	S 27	S 33	S 34		
T 39 N	R 9 E								
S 28	S 27								
S 33	S 34								
22.50	Most easterly of two, high voltage transmission lines, bears N. 5° E. and S. 5° W.								
24.50	Most westerly of two, high voltage transmission lines, bears N. 5° E. and S. 5° W.								
40.00	Point for the 1/4 sec. cor. of secs. 27 and 34. Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 23 ins. in the ground, with brass cap mkd. <table style="margin-left: auto; margin-right: auto; border-collapse: collapse;"> <tr> <td style="padding: 0 10px;">T 39 N</td> <td style="padding: 0 10px;">R 9 E</td> </tr> <tr> <td></td> <td style="padding: 0 10px;">S 27</td> </tr> <tr> <td style="padding: 0 10px;">1/4</td> <td style="border-top: 1px solid black; padding: 0 10px;"></td> </tr> <tr> <td></td> <td style="padding: 0 10px;">S 34</td> </tr> </table> <p style="text-align: center;">2015</p>	T 39 N	R 9 E		S 27	1/4			S 34
T 39 N	R 9 E								
	S 27								
1/4									
	S 34								

Survey of the Subdivisional Lines,
T. 39 N., R. 9 E., Gila and Salt River Meridian, Arizona

CHAINS					
80.00	<p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p> <p>Set a steel fence post nearby.</p> <p>Cor. is located 1.05 chs. W. of barbed wire fence, 5 strand, bears S. 15° E. and N. 15° W.</p> <p>The cor. of secs. 27, 28, 33, and 34.</p> <p>Land, rolling. Soil, sandy loam and sandstone bedrock. Timber, juniper. Undergrowth, native grasses, black brush, and Mormon tea.</p> <hr style="width: 80%; margin: 10px auto;"/> <p>N. 0°02' W., bet. secs. 27 and 28.</p> <p>Over rolling land.</p>				
40.00	<p>Point for the 1/4 sec. cor. of secs. 27 and 28.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 23 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center; margin: 10px 0;"> <p>T 39 N R 9 E</p> <p style="margin-left: 40px;">1/4</p> <p>S 28 S 27</p> <p style="margin-left: 40px;">2015</p> </div>				
80.00	<p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p> <p>Set a steel fence post nearby.</p> <p>Point for the cor. of secs. 21, 22, 27, and 28.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 25 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center; margin: 10px 0;"> <p>T 39 N R 9 E</p> <table style="margin: auto; border-collapse: collapse;"> <tr> <td style="border-right: 1px solid black; padding: 0 5px;">S 21</td> <td style="padding: 0 5px;">S 22</td> </tr> <tr> <td style="border-right: 1px solid black; padding: 0 5px;">S 28</td> <td style="padding: 0 5px;">S 27</td> </tr> </table> <p style="margin-left: 40px;">2014</p> </div> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p> <p>Set a steel fence post nearby.</p>	S 21	S 22	S 28	S 27
S 21	S 22				
S 28	S 27				

Survey of the Subdivisional Lines,
T. 39 N., R. 9 E., Gila and Salt River Meridian, Arizona

CHAINS	
	<p>Cor. is located 1.60 chs. W. and 1.05 chs. N. of sandy ridge top, 20 ft. high, bears N. 55° E. and S. 55° W., and 1.95 chs. E. and 1.75 chs. S. of wash, 20 ft. wide, 4 ft. deep, drains N. 45° E.</p> <p>Land, rolling and slightly broken. Soil, sandy loam and sandstone bedrock. Timber, scattered juniper. Undergrowth, native grasses, salt brush, black brush, yucca, prickly pear, cholla, and Mormon tea.</p> <hr/> <p>From the cor. of secs. 22, 23, 26, and 27.</p> <p>West, bet. secs. 22 and 27.</p> <p>Over rolling land.</p>
16.80	Most easterly of two, high voltage transmission lines, bears N. 5° E. and S. 5° W.
18.80	Most westerly of two, high voltage transmission lines, bears N. 5° E. and S. 5° W.
40.00	<p>Point for the 1/4 sec. cor. of secs. 22 and 27.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in solid sandstone bedrock, with brass cap mkd.</p> <p style="text-align: center;">T 39 N R 9 E S 22 1/4 ——— S 27</p> <p style="text-align: center;">2015</p> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p> <p>Set a steel fence post nearby.</p>
80.00	<p>Cor. is located 98 lks. N. of sandstone wash, 7 ft. wide, 2 ft. deep, drains N. 80° E.</p> <p>The cor. of secs. 21, 22, 27, and 28.</p> <p>Land, rolling, broken, and nearly level on mesa top. Soil, sandy loam and sandstone bedrock. Timber, sparse juniper. Undergrowth, native grasses, salt brush, black brush, yucca, and Mormon tea.</p> <hr/>

Survey of the Subdivisional Lines,
T. 39 N., R. 9 E., Gila and Salt River Meridian, Arizona

CHAINS							
	N. 0°02' W., bet. secs. 21 and 22.						
	Over gently rolling land.						
40.00	Point for the 1/4 sec. cor. of secs. 21 and 22.						
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 23 ins. in the ground, with brass cap mkd.						
	<table style="margin-left: auto; margin-right: auto;"> <tr><td>T 39 N</td><td>R 9 E</td></tr> <tr><td></td><td style="text-align: center;">1/4</td></tr> <tr><td>S 21</td><td style="border-left: 1px solid black;">S 22</td></tr> </table>	T 39 N	R 9 E		1/4	S 21	S 22
T 39 N	R 9 E						
	1/4						
S 21	S 22						
	2014						
	Deposit a magnet, in a white plastic case, at the base of the stainless steel post.						
	Set a steel fence post nearby.						
80.00	Point for the cor. of secs. 15, 16, 21, and 22.						
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 23 ins. in solid sandstone bedrock, with brass cap mkd.						
	<table style="margin-left: auto; margin-right: auto;"> <tr><td>T 39 N</td><td>R 9 E</td></tr> <tr><td>S 16</td><td style="border-left: 1px solid black;">S 15</td></tr> <tr><td>S 21</td><td style="border-left: 1px solid black;">S 22</td></tr> </table>	T 39 N	R 9 E	S 16	S 15	S 21	S 22
T 39 N	R 9 E						
S 16	S 15						
S 21	S 22						
	2014						
	Deposit a magnet, in a white plastic case, at the base of the stainless steel post.						
	Set a steel fence post nearby.						
	Cor. is located 1.70 chs. W. of wash, 4 ft. wide, 2 ft. deep, drains N. 35° E.						
	Land, gently rolling.						
	Soil, sandy loam and sandstone bedrock.						
	No timber.						
	Undergrowth, native grasses, salt brush, and yucca.						
	<hr/>						
	From the cor. of secs. 14, 15, 22, and 23.						
	West, bet. secs. 15 and 22.						
	Ascending E. slope of canyon.						

Survey of the Subdivisional Lines,
T. 39 N., R. 9 E., Gila and Salt River Meridian, Arizona

CHAINS	
11.10	Most easterly of two, high voltage transmission lines, bears N. 5° E. and S. 5° W.
13.10	Most westerly of two, high voltage transmission lines, bears N. 5° E. and S. 5° W.
40.00	Point for the 1/4 sec. cor. of secs. 15 and 22. Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd. <div style="text-align: center;"> T 39 N R 9 E S 15 1/4 ——— S 22 2015 </div> Deposit a magnet, in a white plastic case, at the base of the stainless steel post. Set a steel fence post nearby.
75.55	Wash, 15 ft. wide, 4 ft. deep, drains N. 45° E.
80.00	The cor. of secs. 15, 16, 21, and 22. Land, rolling to gently rolling. Soil, sandy loam and sandstone bedrock. No timber. Undergrowth, native grasses, black brush, salt brush, and Mormon tea.
	<hr/> N. 0°02' W., bet. secs. 15 and 16. Over gently rolling land.
40.00	Point for the 1/4 sec. cor. of secs. 15 and 16. Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd. <div style="text-align: center;"> T 39 N R 9 E 1/4 S 16 S 15 2014 </div> Deposit a magnet, in a white plastic case, at the base of the stainless steel post. Set a steel fence post nearby.

Survey of the Subdivisional Lines,
T. 39 N., R. 9 E., Gila and Salt River Meridian, Arizona

CHAINS 80.00	<p>Point for the cor. of secs. 9, 10, 15, and 16.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 19 ins. in the ground to sandstone bedrock, encircled with a collar of stone, 3 ft. base, to top, with brass cap mkd.</p> <table style="margin-left: auto; margin-right: auto;"> <tr> <td>T 39 N</td> <td>R 9 E</td> </tr> <tr> <td>S 9</td> <td>S 10</td> </tr> <tr> <td>S 16</td> <td>S 15</td> </tr> </table> <p style="text-align: center;">2014</p> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p> <p>Set a steel fence post nearby.</p> <p>Cor. is located 20 lks. S. of meandering wash, 4 ft. wide, 1 ft. deep, drains N. 45° W., and 60 lks. W. of the same meandering wash, 4 ft. wide, 1 ft. deep, drains W., and 45 lks. E. of the same meandering wash, 5 ft. wide, 1 ft. deep, drains S. 50° W.</p> <p>Land, rolling. Soil, sandy loam and sandstone bedrock. Timber, sparse juniper. Undergrowth, native grasses, rabbit brush, yucca, and Mormon tea.</p> <hr/> <p>From the cor. of secs. 10, 11, 14, and 15.</p> <p>West, bet. secs. 10 and 15.</p> <p>Over rolling land, along foothills of N. facing mesa slope.</p>	T 39 N	R 9 E	S 9	S 10	S 16	S 15		
T 39 N	R 9 E								
S 9	S 10								
S 16	S 15								
5.40	Most easterly of two, high voltage transmission lines, bears N. 5° E. and S. 5° W.								
7.40	Most westerly of two, high voltage transmission lines, bears N. 5° E. and S. 5° W.								
40.00	<p>Point for the 1/4 sec. cor. of secs. 10 and 15.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <table style="margin-left: auto; margin-right: auto;"> <tr> <td>T 39 N</td> <td>R 9 E</td> </tr> <tr> <td></td> <td>S 10</td> </tr> <tr> <td>1/4</td> <td>———</td> </tr> <tr> <td></td> <td>S 15</td> </tr> </table> <p style="text-align: center;">2014</p>	T 39 N	R 9 E		S 10	1/4	———		S 15
T 39 N	R 9 E								
	S 10								
1/4	———								
	S 15								

Survey of the Subdivisional Lines,
T. 39 N., R. 9 E., Gila and Salt River Meridian, Arizona

CHAINS	
	<p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p> <p>Set a steel fence post nearby.</p>
80.00	<p>The cor. of secs. 9, 10, 15, and 16.</p> <p>Land, rolling to gently rolling. Soil, sandy loam and sandstone bedrock. No timber. Undergrowth, native grasses, and greasewood.</p> <hr/> <p>N. 0°02' W., bet. secs. 9 and 10.</p> <p>Over gently rolling land.</p>
40.00	<p>Point for the 1/4 sec. cor. of secs. 9 and 10.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center;"> <p>T 39 N R 9 E 1/4 S 9 S 10</p> <p>2014</p> </div> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p> <p>Set a steel fence post nearby.</p> <p>Cor. is located on the NE face of sandy finger ridge, and is 15 lks. N. from the top of sandy finger ridge, 8 ft. high, bears S. 85° E. and N. 85° W., and 1.30 chs. S. of the same meandering sandy finger ridge top, 10 ft. high, bears N. and S.</p>
68.10	Bladed dirt road, 15 ft. wide, bears N. 40° E. and S. 40° W.
72.35	Power line, 2 strand, bears N. 40° E. and S. 40° W.
80.00	<p>Point for the cor. of secs. 3, 4, 9, and 10.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center;"> <p>T 39 N R 9 E S 4 S 3 S 9 S 10</p> <p>2014</p> </div>

Survey of the Subdivisional Lines,
T. 39 N., R. 9 E., Gila and Salt River Meridian, Arizona

CHAINS	
	<p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p> <p>Set a steel fence post nearby.</p> <p>Cor. is located 2.10 chs. W. of wash, 10 ft. wide, 2 ft. deep, drains N. 20° W.</p> <p>Land, gently rolling. Soil, sandy loam. Timber, scattered juniper. Undergrowth, native grasses, yucca, rabbit brush, and Mormon tea.</p> <hr/> <p>From the cor. of secs. 2, 3, 10, and 11.</p> <p>West, bet. secs. 3 and 10.</p> <p>Over rolling land.</p>
40.00	<p>Point for the 1/4 sec. cor. of secs. 3 and 10.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T 39 N R 9 E S 3 1/4 ——— S 10</p> <p style="text-align: center;">2014</p> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p> <p>Set a steel fence post nearby.</p> <p>Cor. is located 1.15 chs. W. of trail road, bears S. 20° E. and N. 40° W., and is 1.33 chs. S. 45°42' W., of a burgundy manhole cover, 22 ins. diam., projecting 8 ins. above ground, with a galvanized pipe, 4 1/4 ins. diam., projecting 18 ins. above ground, N. of the manhole.</p>
64.60	Wash, 30 ft. wide, 4 ft. deep, drains N. 40° W.
67.85	Power line, 2 strand, bears N. 70° E. and S. 70° W.
71.10	Bladed dirt road, 15 ft. wide, bears N. 40° E. and S. 40° W.
80.00	The cor. of secs. 3, 4, 9, and 10.

Survey of the Subdivisional Lines,
T. 39 N., R. 9 E., Gila and Salt River Meridian, Arizona

CHAINS	
	<p>Land, rolling. Soil, sandy loam. No timber. Undergrowth, native grasses, yucca, and rabbit brush.</p> <hr/> <p>N. 0°02' W., bet. secs. 3 and 4.</p> <p>Over gently rolling land.</p>
40.00	<p>Point for the 1/4 sec. cor. of secs. 3 and 4.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 21 ins. in solid sandstone bedrock, encircled with a collar of stone, 18 in. base, to top, with brass cap mkd.</p> <p style="text-align: center;">T 39 N R 9 E 1/4 S 4 S 3</p> <p style="text-align: center;">2014</p> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p> <p>Set a steel fence post, 37 lks. S. 33° W., of cor.</p> <p>Cor. is located on southwesterly facing gentle slope of sandstone bedrock, and is 4 chs. E. of sandstone rim, 50 ft. high, bears S. 55° W. and N. 65° W.</p>
80.00	<p>The cor. of secs. 3, 4, 33, and 34, on the N. bdy. of the Tp., monumented with a brass tablet, 3 1/8 ins. diam., firmly set, 2 ins. below loose soil, flush with sandstone bedrock, brass tablet mkd. T40N R9E S33 S34 S4 S3 T39N 2005. Add the marks 2014 to the brass tablet.</p> <p>Land, gently rolling and broken. Soil, sandy loam and sandstone bedrock. No timber. Undergrowth, native grasses, greasewood, cliff rose, and Mormon tea.</p> <hr/> <p>From the cor. of secs. 4, 5, 32, and 33, on the S. bdy. of the Tp., monumented with a stainless steel post, 2 1/2 ins. diam., firmly set, projecting 5 ins. above the ground, with a steel fence post nearby, with brass cap mkd. T39N R9E S32 S33 S5 S4 T38N 2013. Add the marks 2014 to the brass cap.</p> <p>N. 0°03' W., bet. secs. 32 and 33.</p> <p>Over nearly level land.</p>

Survey of the Subdivisional Lines,
T. 39 N., R. 9 E., Gila and Salt River Meridian, Arizona

CHAINS							
4.50	Power line, 2 strand, bears S. 85° E. and N. 85° W.						
7.10	Underground water line, bears S. 85° E. and N. 85° W.						
40.00	Point for the 1/4 sec. cor. of secs. 32 and 33. Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 27 ins. in the ground, with brass cap mkd. <div style="text-align: center;"> <table style="margin: auto;"> <tr><td>T 39 N</td><td>R 9 E</td></tr> <tr><td>1/4</td><td></td></tr> <tr><td>S 32</td><td> S 33</td></tr> </table> <p>2015</p> </div> Deposit a magnet, in a white plastic case, at the base of the stainless steel post. Set a steel fence post nearby.	T 39 N	R 9 E	1/4		S 32	S 33
T 39 N	R 9 E						
1/4							
S 32	S 33						
80.00	Point for the cor. of secs. 28, 29, 32, and 33. Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd. <div style="text-align: center;"> <table style="margin: auto;"> <tr><td>T 39 N</td><td>R 9 E</td></tr> <tr><td>S 29</td><td> S 28</td></tr> <tr><td>S 32</td><td> S 33</td></tr> </table> <p>2015</p> </div> Deposit a magnet, in a white plastic case, at the base of the stainless steel post. Set a steel fence post nearby. Cor. is located 2.30 chs. W. of the W. right-of-way fence of BIA Route 20, barbed wire, 4 strand, bears N. and S. Land, gently rolling. Soil, sandy loam. Timber, juniper. Undergrowth, native grasses, black brush, salt brush, yucca, and Mormon tea. <hr style="width: 50%; margin-left: 0;"/> From the cor. of secs. 27, 28, 33, and 34. West, bet. secs. 28 and 33. Over gently rolling land.	T 39 N	R 9 E	S 29	S 28	S 32	S 33
T 39 N	R 9 E						
S 29	S 28						
S 32	S 33						

Survey of the Subdivisional Lines,
T. 39 N., R. 9 E., Gila and Salt River Meridian, Arizona

CHAINS	
40.00	<p>Point for the 1/4 sec. cor. of secs. 28 and 33.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T 39 N R 9 E S 28 1/4 ——— S 33</p> <p style="text-align: center;">2015</p> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p> <p>Set a steel fence post nearby.</p>
74.70	E. right-of-way fence of BIA Route 20, barbed wire, 4 strand, parallels highway.
76.20	BIA Route 20, an asphalt surfaced road, 33 ft. wide, bears N. and S.
80.00	<p>The cor. of secs. 28, 29, 32, and 33.</p> <p>Land, gently rolling. Soil, sandy loam and sandstone outcrops. Timber, juniper. Undergrowth, native grasses, black brush, yucca, and Mormon tea.</p> <hr/> <p>N. 0°03' W., bet. secs. 28 and 29.</p> <p>Over gently rolling land.</p>
40.00	<p>Point for the 1/4 sec. cor. of secs. 28 and 29.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T 39 N R 9 E 1/4 S 29 S 28</p> <p style="text-align: center;">2015</p> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p> <p>Set a steel fence post nearby.</p>

Survey of the Subdivisional Lines,
T. 39 N., R. 9 E., Gila and Salt River Meridian, Arizona

CHAINS									
80.00	<p>Cor. is located 90 lks. W. of the W. right-of-way fence of BIA Route 20, barbed wire, 4 strand, parallels highway, and 2.40 chs. W. of BIA Route 20, an asphalt surfaced road, 33 ft. wide, bears N. and S.</p> <p>Point for the cor. of secs. 20, 21, 28, and 29.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center;"> <table style="border-collapse: collapse; margin: auto;"> <tr> <td style="padding: 0 10px;">T 39 N</td> <td style="padding: 0 10px;">R 9 E</td> </tr> <tr> <td style="border-right: 1px solid black; padding: 0 5px;">S 20</td> <td style="padding: 0 5px;">S 21</td> </tr> <tr> <td style="border-right: 1px solid black; padding: 0 5px;">S 29</td> <td style="padding: 0 5px;">S 28</td> </tr> </table> <p>2015</p> </div> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p> <p>Set a steel fence post nearby.</p> <p>Cor. is located 55 lks. S. and 40 lks. E. of the W. right-of-way fence of BIA Route 20, barbed wire, 4 strand, fenced around culvert, then parallels highway.</p> <p>Cor. is also located 1.00 ch. W. of BIA Route 20, an asphalt surfaced road, 33 ft. wide, bears N. and S., and 2.55 chs. W. of the E. right-of-way fence of BIA Route 20, barbed wire, 4 strand, parallels highway.</p> <p>Land, gently rolling. Soil, sandy loam. Timber, scattered juniper. Undergrowth, native grasses, black brush, salt brush, and rabbit brush.</p> <hr/> <p>From the cor. of secs. 21, 22, 27, and 28.</p> <p>West, bet. secs. 21 and 28.</p> <p>Over gently rolling land.</p>	T 39 N	R 9 E	S 20	S 21	S 29	S 28		
T 39 N	R 9 E								
S 20	S 21								
S 29	S 28								
40.00	<p>Point for the 1/4 sec. cor. of secs. 21 and 28.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 22 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center;"> <table style="border-collapse: collapse; margin: auto;"> <tr> <td style="padding: 0 10px;">T 39 N</td> <td style="padding: 0 10px;">R 9 E</td> </tr> <tr> <td style="padding: 0 10px;"></td> <td style="padding: 0 10px;">S 21</td> </tr> <tr> <td style="padding: 0 10px;">1/4</td> <td style="border-top: 1px solid black; padding: 0 10px;"></td> </tr> <tr> <td style="padding: 0 10px;"></td> <td style="padding: 0 10px;">S 28</td> </tr> </table> <p>2014</p> </div>	T 39 N	R 9 E		S 21	1/4			S 28
T 39 N	R 9 E								
	S 21								
1/4									
	S 28								

Survey of the Subdivisional Lines,
T. 39 N., R. 9 E., Gila and Salt River Meridian, Arizona

CHAINS	
	<p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p> <p>Set a steel fence post nearby.</p> <p>Cor. is located 1.30 chs. W. of trail road, bears N. 10° E. and S. 5° E.</p>
80.00	<p>The cor. of secs. 20, 21, 28, and 29.</p> <p>Land, gently rolling. Soil, sandy loam. Timber, sparse juniper. Undergrowth, native grasses, salt brush, yucca, and Mormon tea.</p> <hr/> <p>N. 0°03' W., bet. secs. 20 and 21.</p> <p>Over gently rolling land.</p>
40.00	<p>Point for the 1/4 sec. cor. of secs. 20 and 21.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 4 ins. below the surface of the ground, with brass cap mkd.</p> <p style="text-align: center;">T 39 N R 9 E 1/4 S 20 S 21 2015</p> <p>from which</p> <p style="padding-left: 40px;">A stainless steel post, 28 ins. long, 2 1/2 ins. diam., set 26 ins. in the ground, for a reference monument, bears N. 45°00' E., 100.0 ft. dist. with brass cap mkd. RM T39N R9E 100.0 FT TO COR 1/4 S21 2015 and an arrow pointing to the cor. Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p> <p style="padding-left: 40px;">A stainless steel post, 28 ins. long, 2 1/2 ins. diam., set 27 ins. in the ground, for a reference monument, bears S. 45°00' E., 100.0 ft. dist. with brass cap mkd. RM T39N R9E 100.0 FT TO COR 1/4 S21 2015 and an arrow pointing to the cor. Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p> <p>Cor. falls inside right-of-way of BIA Route 20.</p>

Survey of the Subdivisional Lines,
T. 39 N., R. 9 E., Gila and Salt River Meridian, Arizona

CHAINS									
80.00	<p>Cor. is located 1.20 chs. W. of the E. right-of-way fence of BIA Route 20, barbed wire, 4 strand, parallels highway, and 11 lks. E. of the easterly edge of BIA Route 20, an asphalt surfaced road, 33 ft. wide, bears N. and S., and 1.90 chs. E. of the W. right-of-way fence of BIA Route 20, barbed wire, 4 strand, parallels highway.</p> <p>Point for the cor. of secs. 16, 17, 20, and 21.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in solid sandstone bedrock, with brass cap mkd.</p> <div style="text-align: center;"> <table style="margin: auto; border-collapse: collapse;"> <tr> <td style="padding: 0 10px;">T 39 N</td> <td style="padding: 0 10px;">R 9 E</td> </tr> <tr> <td style="border-right: 1px solid black; padding: 0 5px;">S 17</td> <td style="padding: 0 5px;">S 16</td> </tr> <tr> <td style="border-right: 1px solid black; padding: 0 5px;">S 20</td> <td style="padding: 0 5px;">S 21</td> </tr> </table> <p>2014</p> </div> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p> <p>Set a steel fence post nearby.</p> <p>Cor. is located 20 lks. E. of the E. right-of-way fence of BIA Route 20, barbed wire, 4 strand, parallels highway, and 1.75 chs. E. of BIA Route 20, an asphalt surfaced road, 33 ft. wide, bears N. and S., and 3.25 chs. E. of the W. right-of-way fence of BIA Route 20, barbed wire, 4 strand, parallels highway.</p> <p>Land, gently rolling and nearly flat. Soil, sandy loam. Timber, sparse juniper. Undergrowth, native grasses, rabbit brush, salt brush, cholla, yucca, and Mormon tea.</p> <hr style="width: 50%; margin-left: 0;"/> <p>From the cor. of secs. 15, 16, 21, and 22.</p> <p>West, bet. secs. 16 and 21.</p> <p>Over gently rolling land.</p>	T 39 N	R 9 E	S 17	S 16	S 20	S 21		
T 39 N	R 9 E								
S 17	S 16								
S 20	S 21								
40.00	<p>Point for the 1/4 sec. cor. of secs. 16 and 21.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center;"> <table style="margin: auto; border-collapse: collapse;"> <tr> <td style="padding: 0 10px;">T 39 N</td> <td style="padding: 0 10px;">R 9 E</td> </tr> <tr> <td style="padding: 0 10px;"></td> <td style="padding: 0 10px;">S 16</td> </tr> <tr> <td style="padding: 0 10px;">1/4</td> <td style="border-top: 1px solid black; padding: 0 10px;"></td> </tr> <tr> <td style="padding: 0 10px;"></td> <td style="padding: 0 10px;">S 21</td> </tr> </table> <p>2014</p> </div>	T 39 N	R 9 E		S 16	1/4			S 21
T 39 N	R 9 E								
	S 16								
1/4									
	S 21								

Survey of the Subdivisional Lines,
T. 39 N., R. 9 E., Gila and Salt River Meridian, Arizona

CHAINS	
	<p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p> <p>Set a steel fence post nearby.</p> <p>Cor. is located 85 lks. W. and 90 lks. N. of trail road, bears N. 35° E. and S. 50° W.</p>
80.00	<p>The cor. of secs. 16, 17, 20, and 21.</p> <p>Land, nearly level. Soil, sandy loam. No timber. Undergrowth, native grasses, salt brush, rabbit brush, and Mormon tea.</p> <hr/> <p>N. 0°03' W., bet. secs. 16 and 17.</p> <p>Over gently rolling land.</p>
40.00	<p>Point for the 1/4 sec. cor. of secs. 16 and 17.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 25 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T 39 N R 9 E 1/4 S 17 S 16 2014</p>
43.16	<p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p> <p>Set a steel fence post nearby.</p> <p>Cor. is located 95 lks. E. of the E. right-of-way fence of BIA Route 20, barbed wire, 4 strand, parallels highway, and 2.50 chs. E. of BIA Route 20, an asphalt surfaced road, 33 ft. wide, bears N. 5° E. and S. 5° W.</p> <p>From this point, a right-of-way monument, bears W., 78.3 lks. dist., monumented with a brass tablet, 3 ins. diam., set flush in a concrete cylinder, 6 ins. diam., firmly set, projecting 3 ins. above ground, mkd. BIA ROADS 1975, with an angle iron nearby, firmly set, projecting 27 ins. above ground, mkd. HWY. R. OF W. P.T. 570+74.56.</p>

Survey of the Subdivisional Lines,
T. 39 N., R. 9 E., Gila and Salt River Meridian, Arizona

CHAINS	
43.37	<p>From this point, a right-of-way monument, bears W., 3.80 chs. dist., monumented with a brass tablet, 3 ins. diam., set flush in a concrete cylinder, 6 ins. diam., firmly set, flush with the surface of the ground, mkd. BIA ROADS 1975, with an angle iron nearby, firmly set, projecting 21 ins. above ground, mkd. HWY. R. OF W. P.T. 570+74.56.</p>
53.45	<p>Power line, 2 strand, bears S. 85° E. and N. 85° W.</p>
80.00	<p>Point for the cor. of secs. 8, 9, 16, and 17.</p> <p>Set a rail road spike, flush with the surface of the W. edge of asphalt pavement, of BIA Route 20.</p> <p>from which</p> <p style="padding-left: 40px;">A stainless steel post, 28 ins. long, 2 1/2 ins. diam., set 20 ins. in solid sandstone bedrock, in a collar of stone, 2 1/2 ft. base, to top, for a reference monument, bears N. 45°00' E., 180.0 ft. dist. with brass cap mkd. RM T39N R9E 180.0 FT TO COR S9 2014 and an arrow pointing to the cor. Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p> <p style="padding-left: 40px;">A stainless steel post, 28 ins. long, 2 1/2 ins. diam., set 25 ins. in the ground, for a reference monument, bears S. 45°00' W., 128.0 ft. dist. with brass cap mkd. RM T39N R9E 128.0 FT TO COR S17 2014 and an arrow pointing to the cor. Deposit a magnet, in a white plastic case, at the base of the stainless steel post, and set a steel fence post nearby.</p> <p>Cor. is located 26 lks. W. of BIA Route 20, an asphalt surfaced road, 33 ft. wide, bears N. 5° E. and S. 5° W., and 1.80 chs. W. of the E. right-of-way fence of BIA Route 20, barbed wire, 4 strand, parallels highway, and 2.95 chs. W. of power line, bears N. 5° E. and S. 5° W., and 1.25 chs. E. of the W. right-of-way fence of BIA Route 20, barbed wire, 4 strand, parallels highway.</p> <p>Land, gently rolling and nearly flat. Soil, sandy loam. Timber, sparse juniper. Undergrowth, native grasses, rabbit brush, salt brush, cholla, yucca, and Mormon tea.</p> <hr/> <p>From the cor. of secs. 9, 10, 15, and 16.</p> <p>West, bet. secs. 9 and 16.</p> <p>Over rolling land.</p>
40.00	<p>Point for the 1/4 sec. cor. of secs. 9 and 16.</p>

Survey of the Subdivisional Lines,
T. 39 N., R. 9 E., Gila and Salt River Meridian, Arizona

CHAINS	
	<p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T 39 N R 9 E S 9 1/4 ——— S 16</p> <p style="text-align: center;">2015</p> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p> <p>Set a steel fence post nearby.</p> <p>Cor. is located on westerly facing sandy gentle slope among scattered juniper.</p>
71.70	Bladed dirt road, 15 ft. wide, bears N. 60° E. and S. 60° W.
80.00	<p>The cor. of secs. 8, 9, 16, and 17.</p> <p>Land, rolling. Soil, sandy loam and gravel. Timber, scattered juniper. Undergrowth, native grasses, black brush, sage brush, and Mormon tea.</p> <hr/> <p>N. 0°03' W., bet. secs. 8 and 9.</p> <p>Over gently rolling land.</p>
40.00	<p>Point for the 1/4 sec. cor. of secs. 8 and 9.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T 39 N R 9 E 1/4 S 8 S 9</p> <p style="text-align: center;">2014</p> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p> <p>Set a steel fence post nearby.</p> <p>Cor. is located 1.50 chs. W. of the W. right-of-way fence of BIA Route 20, barbed wire, 4 strand, bears N. 5° E. and S. 5° W., and 60 lks. E. of trail road, bears N. 15° E. and S. 15° W.</p>

Survey of the Subdivisional Lines,
T. 39 N., R. 9 E., Gila and Salt River Meridian, Arizona

CHAINS 80.00	<p>Point for the cor. of secs. 4, 5, 8, and 9.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 21 ins. in solid sandstone bedrock, with brass cap mkd.</p> <table style="margin-left: auto; margin-right: auto;"> <tr> <td>T 39 N</td> <td>R 9 E</td> </tr> <tr> <td>S 5</td> <td>S 4</td> </tr> <tr> <td>S 8</td> <td>S 9</td> </tr> </table> <p style="text-align: center;">2014</p> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p> <p>Raise a mound of stone, 3 ft. base, 2 ft. high, E. of cor.</p> <p>Cor. is located 15 lks. N. of wash, 4 ft. wide, 3 ft. deep, drains N. 65° W., and 30 lks. E. of the same wash, 4 ft. wide, 3 ft. deep, drains N. 40° W.</p> <p>Land, gently rolling. Soil, sandy loam, gravel, and sandstone bedrock. No timber. Undergrowth, native grasses, rabbit brush, salt brush, sage brush, and yucca.</p> <hr/> <p>From the cor. of secs. 3, 4, 9, and 10.</p> <p>West, bet. secs. 4 and 9.</p> <p>Over gently rolling land.</p>	T 39 N	R 9 E	S 5	S 4	S 8	S 9		
T 39 N	R 9 E								
S 5	S 4								
S 8	S 9								
40.00	<p>Point for the 1/4 sec. cor. of secs. 4 and 9.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 19 ins. in the ground to sandstone bedrock, in a supporting mound of stone, 3 ft. base, to top, with brass cap mkd.</p> <table style="margin-left: auto; margin-right: auto;"> <tr> <td>T 39 N</td> <td>R 9 E</td> </tr> <tr> <td></td> <td>S 4</td> </tr> <tr> <td>1/4</td> <td>—</td> </tr> <tr> <td></td> <td>S 9</td> </tr> </table> <p style="text-align: center;">2015</p> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p> <p>Set a steel fence post, 3 lks. E. of cor.</p>	T 39 N	R 9 E		S 4	1/4	—		S 9
T 39 N	R 9 E								
	S 4								
1/4	—								
	S 9								

Survey of the Subdivisional Lines,
T. 39 N., R. 9 E., Gila and Salt River Meridian, Arizona

CHAINS	
	Cor. is located at the base of sandstone cliff, 30 ft. high, bears N. 65° E. and S. 65° W., and 1.45 chs. W. of sandstone cliff edge, 75 ft. high, bears N. 40° E. and S. 35° W.
71.50	Power line, 2 strand, bears N. 5° E. and S. 5° W.
72.65	E. right-of-way fence of BIA Route 20, barbed wire, 4 strand, parallels highway.
74.15	BIA Route 20, an asphalt surfaced road, 33 ft. wide, bears N. 5° E. and S. 5° W.
75.70	W. right-of-way fence of BIA Route 20, barbed wire, 4 strand, parallels highway.
80.00	The cor. of secs. 4, 5, 8, and 9. Land, gently rolling and broken. Soil, sandy loam and gravel. No timber. Undergrowth, native grasses, black brush, sage brush, and Mormon tea.
	N. 0°03' W., bet. secs. 4 and 5.
	Over rolling land.
40.00	Point for the 1/4 sec. cor. of secs. 4 and 5. Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 16 ins. the ground, 11 ins. in subsurface bedrock, in a supporting mound of stone, 4 ft. base, to top, with brass cap mkd. <div style="text-align: center;"> T 39 N R 9 E 1/4 S 5 S 4 2014 </div> Deposit a magnet, in a white plastic case, at the base of the stainless steel post. Set a steel fence post nearby. Cor. is located half way up the right bank of wash, 5 ft. high, bears S. 10° E. and N. 55° W., and 35 lks. N. of wash, 6 ft. wide, 2 ft. deep, drains N. 25° W., and 15 lks. E. of the same wash, 6 ft. wide, 2 ft. deep, drains N. 50° W., and 70 lks. E. of trail road, bears S. 5° E. and N. 5° W., and 2.35 chs. E. of sandstone rim, 5 ft. high, bears N. 35° E. and S. 85° W.

Survey of the Subdivisional Lines,
T. 39 N., R. 9 E., Gila and Salt River Meridian, Arizona

CHAINS	
42.55	Trail road, bears N. 55° E. and S. 55° W.
80.00	<p>The cor. of secs. 4, 5, 32, and 33, on the N. bdy. of the Tp., monumented with a stainless steel post, 2 1/2 ins. diam., firmly set, projecting 4 ins. above the ground, with brass cap mkd. T40N R9E S32 S33 S5 S4 T39N 2005. Add the marks 2014 to the brass cap.</p> <p>Land, rolling and broken canyon land. Soil, sandy loam and sandstone bedrock. No timber. Undergrowth, native grasses, sage brush, rabbit brush, salt brush, and cliff rose.</p> <hr/> <p>From the cor. of secs. 5, 6, 31, and 32, on the S. bdy. of the Tp., monumented with a stainless steel post, 2 1/2 ins. diam., firmly set, projecting 4 ins. above the ground, with a steel fence post nearby, with brass cap mkd. T39N R9E S31 S32 S6 S5 T38N 2013. Add the marks 2014 to the brass cap.</p> <p>N. 0°03' W., bet. secs. 31 and 32.</p> <p>Over gently rolling land.</p>
40.00	<p>Point for the 1/4 sec. cor. of secs. 31 and 32.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 25 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T 39 N R 9 E 1/4 S 31 S 32 2014</p> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p> <p>Set a steel fence post nearby.</p>
80.00	<p>Point for the cor. of secs. 29, 30, 31, and 32.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 25 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T 39 N R 9 E S 30 S 29 S 31 S 32 2014</p>

Survey of the Subdivisional Lines,
T. 39 N., R. 9 E., Gila and Salt River Meridian, Arizona

CHAINS	
	<p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p> <p>Set a steel fence post nearby.</p> <p>Cor. is located 90 lks. S. and 35 lks. E. of trail road, bears N. 20° E. and S. 20° W.</p> <p>Land, slightly rolling. Soil, sandy loam. Timber, scattered juniper. Undergrowth, native grasses, rabbit brush, salt brush, and Mormon tea.</p> <hr/> <p>From the cor. of secs. 28, 29, 32, and 33.</p> <p>West, bet. secs. 29 and 32.</p> <p>Over gently rolling land.</p>
5.20	Power line, 5 strand, bears N. and S.
40.00	<p>Point for the 1/4 sec. cor. of secs. 29 and 32.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 25 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center;"> <p>T 39 N R 9 E</p> <p>S 29</p> <p>1/4 ———</p> <p>S 32</p> <p>2015</p> </div>
62.50	<p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p> <p>Set a steel fence post nearby.</p> <p>High voltage transmission line, bears N. and S.</p>
80.00	<p>The cor. of secs. 29, 30, 31, and 32.</p> <p>Land, gently rolling and sandstone outcrops. Soil, sandy loam and sandstone bedrock. Timber, juniper. Undergrowth, native grasses, black brush, salt brush, cliff rose, and Mormon tea.</p> <hr/> <p>West, bet. secs. 30 and 31.</p> <p>Over gently rolling land.</p>

Survey of the Subdivisional Lines,
T. 39 N., R. 9 E., Gila and Salt River Meridian, Arizona

CHAINS	
40.00	<p>Point for the 1/4 sec. cor. of secs. 30 and 31.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T 39 N R 9 E S 30 1/4 ——— S 31</p> <p style="text-align: center;">2014</p> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p> <p>Set a steel fence post nearby.</p> <p>Cor. is located 2 lks. N. and 15 lks. E. of trail road, bears S. 55° E. and N. 60° W.</p>
78.82	<p>The cor. of secs. 25, 30, 31, and 36, on the W. bdy. of the Tp., hereinbefore described.</p> <p>Land, gently rolling. Soil, sandy loam. Timber, scattered juniper. Undergrowth, native grasses, sage brush, yucca, prickly pear, rabbit brush, and Mormon tea.</p> <hr/> <p>From the cor. of secs. 29, 30, 31, and 32.</p> <p>N. 0°03' W., bet. secs. 29 and 30.</p> <p>Over gently rolling land.</p>
40.00	<p>Point for the 1/4 sec. cor. of secs. 29 and 30.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in solid sandstone bedrock, with brass cap mkd.</p> <p style="text-align: center;">T 39 N R 9 E 1/4 S 30 S 29</p> <p style="text-align: center;">2014</p> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p> <p>Set a steel fence post nearby.</p>
80.00	<p>Point for the cor. of secs. 19, 20, 29, and 30.</p>

Survey of the Subdivisional Lines,
T. 39 N., R. 9 E., Gila and Salt River Meridian, Arizona

CHAINS									
	<p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p>								
	<table style="margin-left: auto; margin-right: auto;"> <tr> <td>T 39 N</td> <td>R 9 E</td> </tr> <tr> <td style="border-right: 1px solid black;">S 19</td> <td>S 20</td> </tr> <tr> <td style="border-right: 1px solid black;">S 30</td> <td>S 29</td> </tr> </table>	T 39 N	R 9 E	S 19	S 20	S 30	S 29		
T 39 N	R 9 E								
S 19	S 20								
S 30	S 29								
	2014								
	<p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p> <p>Set a steel fence post nearby.</p> <p>Cor. is located 65 lks. S. of trail road, bears N. 85° E. and S. 85° W., and 2.50 chs. W. of wash, 35 ft. wide, 3 ft. deep, drains N. 25° E., and 1.05 chs. N. of the same wash, 35 ft. wide, 3 ft. deep, drains N. 65° E.</p> <p>Land, gently rolling. Soil, sandy loam and sandstone bedrock. Timber, scattered juniper. Undergrowth, native grasses, rabbit brush, salt brush, sage brush, cliff rose, greasewood, and Mormon tea.</p>								
	<hr/> <p>From the cor. of secs. 20, 21, 28, and 29.</p> <p>West, bet. secs. 20 and 29.</p> <p>Over gently rolling land.</p>								
5.00	Power line, 5 strand, bears N. and S.								
34.10	Power line, 2 strand, bears N. 20° E. and S. 20° W.								
40.00	Point for the 1/4 sec. cor. of secs. 20 and 29.								
	<p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 23 ins. in solid sandstone bedrock, with brass cap mkd.</p>								
	<table style="margin-left: auto; margin-right: auto;"> <tr> <td>T 39 N</td> <td>R 9 E</td> </tr> <tr> <td></td> <td>S 20</td> </tr> <tr> <td></td> <td>1/4 ———</td> </tr> <tr> <td></td> <td>S 29</td> </tr> </table>	T 39 N	R 9 E		S 20		1/4 ———		S 29
T 39 N	R 9 E								
	S 20								
	1/4 ———								
	S 29								
	2015								
	<p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p> <p>Set a steel fence post nearby.</p>								

Survey of the Subdivisional Lines,
T. 39 N., R. 9 E., Gila and Salt River Meridian, Arizona

CHAINS	
59.90	High voltage transmission line, bears N. and S.
80.00	The cor. of secs. 19, 20, 29, and 30. Land, nearly level. Soil, sandy loam and sandstone bedrock. Timber, scattered juniper. Undergrowth, native grasses, black brush, salt brush, and Mormon tea.

	West, bet. secs. 19 and 30. Over gently rolling land.
3.70	Trail road, bears N. 50° E. and S. 50° W.
40.00	Point for the 1/4 sec. cor. of secs. 19 and 30. Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 25 ins. in the ground, with brass cap mkd.
	T 39 N R 9 E S 19 1/4 ——— S 30 2014
	Deposit a magnet, in a white plastic case, at the base of the stainless steel post. Set a steel fence post nearby.
78.73	The cor. of secs. 19, 24, 25, and 30, on the W. bdy. of the Tp., hereinbefore described. Land, gently rolling. Soil, sandy loam and sandstone bedrock. Timber, juniper. Undergrowth, native grasses, yucca, salt brush, sage brush, and Mormon tea.

	From the cor. of secs. 19, 20, 29, and 30. N. 0°03' W., bet. secs. 19 and 20. Over gently rolling land.
40.00	Point for the 1/4 sec. cor. of secs. 19 and 20. Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 25 ins. in the ground, with brass cap mkd.

Survey of the Subdivisional Lines,
T. 39 N., R. 9 E., Gila and Salt River Meridian, Arizona

CHAINS	
	T 39 N R 9 E 1/4 S 19 S 20 2014
	Deposit a magnet, in a white plastic case, at the base of the stainless steel post. Set a steel fence post nearby.
80.00	Point for the cor. of secs. 17, 18, 19, and 20. Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 21 ins. in solid sandstone bedrock, encircled with a collar of stone, 3 ft. base, to top, with brass cap mkd.
	T 39 N R 9 E S 18 S 17 S 19 S 20 2014
	Deposit a magnet, in a white plastic case, at the base of the stainless steel post. Set a steel fence post nearby. Cor. is located 1.05 chs. E. of sandstone cliff top, 15 ft. high, bears N. 25° E. and S. 15° W. Land, gently rolling and slightly broken. Soil, sandy loam and sandstone bedrock. Timber, scattered juniper. Undergrowth, native grasses, cholla, salt brush, rabbit brush, and Mormon tea.
	<hr/> From the cor. of secs. 16, 17, 20, and 21. West, bet. secs. 17 and 20. Over gently rolling land.
4.75	Power line, 5 strand, bears N. and S.
9.85	Power line, 2 strand, bears N. and S.
40.00	Point for the 1/4 sec. cor. of secs. 17 and 20. Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with brass cap mkd.

Survey of the Subdivisional Lines,
T. 39 N., R. 9 E., Gila and Salt River Meridian, Arizona

CHAINS	
	T 39 N R 9 E S 17 1/4 ——— S 20 2015
	Deposit a magnet, in a white plastic case, at the base of the stainless steel post. Set a steel fence post nearby.
57.25	High voltage transmission line, bears N. and S.
80.00	The cor. of secs. 17, 18, 19, and 20. Land, gently rolling and nearly level. Soil, sandy loam and sandstone bedrock. No timber. Undergrowth, native grasses, yucca, and black brush.
	West, bet. secs. 18 and 19. Descending into canyon land.
40.00	Point for the 1/4 sec. cor. of secs. 18 and 19. Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 25 ins. in the ground, with brass cap mkd.
	T 39 N R 9 E S 18 1/4 ——— S 19 2014
	Deposit a magnet, in a white plastic case, at the base of the stainless steel post. Set a steel fence post nearby.
	Cor. is located 1 1/2 lks. below top of left bank of wash, 6 ft. high, bears N. 55° E. and S. 50° W., and 50 lks. W. of the same wash, 7 ft. wide, 6 ft. deep, drains N. 20° E.
43.20	Wash, 12 ft. wide, 4 ft. deep, drains N. 45° E.
78.64	The cor. of secs. 13, 18, 19, and 24, on the W. bdy. of the Tp., hereinbefore described.

Survey of the Subdivisional Lines,
T. 39 N., R. 9 E., Gila and Salt River Meridian, Arizona

CHAINS	
	<p>Land, slightly broken with scattered sandstone outcrops. Soil, sandy loam and sandstone bedrock. Timber, juniper. Undergrowth, native grasses, salt brush, sage brush, and Mormon tea.</p> <hr/> <p>From the cor. of secs. 17, 18, 19, and 20.</p> <p>N. 0°03' W., bet. secs. 17 and 18.</p> <p>Over gently rolling land, on top of mesa plateau.</p>
40.00	<p>Point for the 1/4 sec. cor. of secs. 17 and 18.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 25 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T 39 N R 9 E 1/4 S 18 S 17</p> <p style="text-align: center;">2014</p> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p> <p>Set a steel fence post nearby.</p> <p>Cor. is located 40 lks. N. of wash, 5 ft. wide, 2 ft. deep, drains S. 25° E.</p>
80.00	<p>Point for the cor. of secs. 7, 8, 17, and 18.</p> <p>Set a brass tablet, 3 1/2 ins. diam., 2 1/4 ins. stem, cemented in a drill hole in solid sandstone bedrock, with top mkd.</p> <p style="text-align: center;">T 39 N R 9 E S 7 S 8 S 18 S 17</p> <p style="text-align: center;">2014</p> <p>Deposit a magnet, in a white plastic case, at the base of the brass tablet.</p> <p>Set a steel fence post nearby.</p> <p>Cor. is located on top of partially exposed sandstone boulder, 12 x 4 x 4 ft., and 90 lks. W. of wash, 4 ft. wide, 1 ft. deep, drains N. 35° E., and 80 lks. N. of sandstone cliff top, 5 ft. high, bears S. 25° W. and N. 20° W., and 70 lks. E. of the same sandstone cliff top, 15 ft. high, bears S. 75° E. and N. 65° W.</p>

Survey of the Subdivisional Lines,
T. 39 N., R. 9 E., Gila and Salt River Meridian, Arizona

CHAINS	
	<p>Land, gently rolling and broken. Soil, sandy loam and sandstone bedrock. Timber, scattered juniper. Undergrowth, native grasses, salt brush, yucca, and Mormon tea.</p> <hr/> <p>From the cor. of secs. 8, 9, 16, and 17.</p> <p>West, bet. secs. 8 and 17.</p> <p>Over gently rolling land.</p>
3.85	Trail road, bears N. and S.
4.55	Power line, 5 strand, bears N. and S.
40.00	Point for the 1/4 sec. cor. of secs. 8 and 17.
	<p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T 39 N R 9 E S 8 1/4 ——— S 17</p> <p style="text-align: center;">2014</p> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p> <p>Set a steel fence post nearby.</p>
54.60	High voltage transmission line, bears N. and S.
77.15	Wash, 20 ft. wide, 4 ft. deep, drains N. 45° W.
80.00	The cor. of secs. 7, 8, 17, and 18.
	<p>Land, gently rolling. Soil, sandy loam and sandstone bedrock. Timber, scattered juniper. Undergrowth, native grasses, cliff rose, yucca, and Mormon tea.</p> <hr/> <p>West, bet. secs. 7 and 18.</p> <p>Over rolling land.</p>
40.00	Point for the 1/4 sec. cor. of secs. 7 and 18.
	<p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p>

Survey of the Subdivisional Lines,
T. 39 N., R. 9 E., Gila and Salt River Meridian, Arizona

CHAINS	
	T 39 N R 9 E S 7 1/4 ——— S 18 2014
	Deposit a magnet, in a white plastic case, at the base of the stainless steel post. Set a steel fence post nearby. Cor. is located 55 lks. W. of sandstone cliff base, 12 ft. high, bears N. 25° E. and S. 25° W.
78.55	The cor. of secs. 7, 12, 13, and 18, on the W. bdy. of the Tp., hereinbefore described. Land, broken canyon land and scattered sandstone cliffs. Soil, sandy loam and sandstone bedrock. Timber, sparse juniper. Undergrowth, native grasses, salt brush, cliff rose, sage brush, and Mormon tea.
	<hr/> From the cor. of secs. 7, 8, 17, and 18. N. 0°03' W., bet. secs. 7 and 8. Descending into canyon valley.
40.00	Point for the 1/4 sec. cor. of secs. 7 and 8. Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.
	T 39 N R 9 E 1/4 S 7 S 8 2014
	Deposit a magnet, in a white plastic case, at the base of the stainless steel post. Set a steel fence post nearby.
80.00	Point for the cor. of secs. 5, 6, 7, and 8. Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with brass cap mkd.

Survey of the Subdivisional Lines,
T. 39 N., R. 9 E., Gila and Salt River Meridian, Arizona

CHAINS	<div style="text-align: center;"> <table border="1" style="margin: auto;"> <tr> <td>T 39 N</td> <td>R 9 E</td> </tr> <tr> <td>S 6</td> <td>S 5</td> </tr> <tr> <td>S 7</td> <td>S 8</td> </tr> </table> <p>2014</p> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p> <p>Set a steel fence post nearby.</p> <p>Cor. is located 95 lks. S. of sandstone cliff base, 80 ft. high, bears S. 55° E. and N. 55° W., and 65 lks. N. of cliff drainage, 12 ft. wide, 6 ft. deep, drains S. 60° W.</p> <p>Land, broken canyon land. Soil, sandy loam and sandstone bedrock. Timber, sparse juniper. Undergrowth, native grasses, salt brush, cliff rose, sage brush, and Mormon tea.</p> <hr/> <p>From the cor. of secs. 4, 5, 8, and 9.</p> <p>West, bet. secs. 5 and 8.</p> <p>Over rolling land.</p> <p>4.30 Power line, 5 strand, bears N. and S.</p> <p>4.65 Trail road, bears N. 15° E. and S. 15° W.</p> <p>40.00 Point for the 1/4 sec. cor. of secs. 5 and 8.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in solid sandstone bedrock, with brass cap mkd.</p> <div style="text-align: center;"> <table border="1" style="margin: auto;"> <tr> <td>T 39 N</td> <td>R 9 E</td> </tr> <tr> <td>S 5</td> <td></td> </tr> <tr> <td>1/4</td> <td>_____</td> </tr> <tr> <td>S 8</td> <td></td> </tr> </table> <p>2014</p> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p> <p>Set a steel fence post nearby.</p> <p>Cor. is located 2.65 chs. S. of sandstone rim, 10 ft. high, bears N. 15° E. and S. 45° W., and 2.35 chs. E. of sandstone rim, 10 ft. high, bears N. 25° E. and S. 30° E.</p> </div> </div>	T 39 N	R 9 E	S 6	S 5	S 7	S 8	T 39 N	R 9 E	S 5		1/4	_____	S 8	
T 39 N	R 9 E														
S 6	S 5														
S 7	S 8														
T 39 N	R 9 E														
S 5															
1/4	_____														
S 8															

Survey of the Subdivisional Lines,
T. 39 N., R. 9 E., Gila and Salt River Meridian, Arizona

CHAINS	
51.95	High voltage transmission line, bears N. and S.
80.00	The cor. of secs. 5, 6, 7, and 8. Land, rolling and broken canyon land. Soil, sandy loam and sandstone bedrock. No timber. Undergrowth, native grasses, salt brush, rabbit brush, cliff rose, sage brush, and Mormon tea.

	West, bet. secs. 6 and 7. Over rolling land, through Water Holes Canyon valley.
40.00	Point for the 1/4 sec. cor. of secs. 6 and 7. Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 22 ins. in solid sandstone bedrock, with brass cap mkd.
	T 39 N R 9 E S 6 1/4 ——— S 7 2014
	Deposit a magnet, in a white plastic case, at the base of the stainless steel post. Set a steel fence post, in a supporting mound of stone, 3 ft. base, 2 ft. high, N. of cor.
75.30	Wash, 40 ft. wide, 6 ft. deep, drains N. 35° E.
78.46	The cor. of secs. 1, 6, 7, and 12, on the W. bdy. of the Tp., hereinbefore described. Land, broken canyon land and gently rolling on mesa plateau. Soil, sandy loam and sandstone bedrock. Timber, sparse juniper. Undergrowth, native grasses, salt brush, cliff rose, prickly pear, and Mormon tea.

	From the cor. of secs. 5, 6, 7, and 8. N. 0°04' W., bet. secs. 5 and 6. Over rolling land.
40.00	Point for the 1/4 sec. cor. of secs. 5 and 6.

Survey of the Subdivisional Lines,
T. 39 N., R. 9 E., Gila and Salt River Meridian, Arizona

CHAINS	
	<p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 25 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T 39 N R 9 E 1/4 S 6 S 5 2014</p> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p> <p>Set a steel fence post nearby.</p>
80.00	<p>The cor. of secs. 5, 6, 31, and 32, on the N. bdy. of the Tp., monumented with a brass tablet, 3 1/8 ins. diam., firmly set, flush with the surface of sandstone bedrock, with brass cap mkd. T40N R9E S31 S32 S6 S5 T39N 2005. Add the marks 2014 to the brass tablet.</p> <p>Land, rolling and broken canyon land. Soil, sandy loam and sandstone bedrock. No timber. Undergrowth, native grasses, cliff rose, greasewood, and Mormon tea.</p> <hr/> <p style="text-align: center;">Subdivision of Section 4, T. 39 N., R. 9 E., Gila and Salt River Meridian, Arizona</p> <hr/> <p>From the 1/4 sec. cor. of secs. 4 and 9.</p> <p>N. 0°03' W., on the N. and S. center line of sec. 4.</p> <p>Over gently rolling land.</p>
40.00	<p>Point for the center 1/4 sec. cor. of sec. 4, at intersection with the E. and W. center line sec. 4.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 25 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T 39 N R 9 E C 1/4 S 4 2015</p> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p> <p>Set a steel fence post nearby.</p>
80.00	<p>The 1/4 sec. cor. of secs. 4 and 33, on the N. bdy. of the Tp.</p> <hr/>

**Subdivision of Section 4,
T. 39 N., R. 9 E., Gila and Salt River Meridian, Arizona**

CHAINS	
	From the 1/4 sec. cor. of secs. 3 and 4. West, on the E. and W. center line of sec. 4. Over rolling land.
40.00	The center 1/4 sec. cor. of sec. 4.
68.70	Power line, bears N. 5° E. and S. 5° W.
69.90	E. right-of-way fence of BIA Route 20, barbed wire, 4 strand, parallels highway.
71.40	BIA Route 20, an asphalt surfaced road, 33 ft. wide, bears N. 5° E. and S. 5° W.
72.90	W. right-of-way fence of BIA Route 20, barbed wire, 4 strand, parallels highway.
74.50	Trail road, bears N. 5° E. and S. 5° W.
76.90	Wash, 10 ft. wide, 1 ft. deep, drains N. 10° W.
80.00	The 1/4 sec. cor. of secs. 4 and 5.
<hr/> <p>Subdivision of Section 5, T. 39 N., R. 9 E., Gila and Salt River Meridian, Arizona</p> <hr/>	
	From the 1/4 sec. cor. of secs. 5 and 8. N. 0°03' W., on the N. and S. center line of sec. 5. Over rolling land.
40.00	Point for the center 1/4 sec. cor. of sec. 5, at intersection with the E. and W. center line sec. 5. Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in solid sandstone bedrock, with brass cap mkd.
	<p>T 39 N R 9 E C 1/4 S 5</p> <p>2014</p>
	Deposit a magnet, in a white plastic case, at the base of the stainless steel post. Raise a mound of stone, 2 1/2 ft. base, 2 ft. high, W. of cor. Cor. is located 1.75 chs. S. of sandstone rim, 5 ft. high, bears N. 75° E. and S. 75° W., and 1.70 chs. W. of sandstone rim, 5 ft. high, bears S. 55° E. and N. 20° W.

Subdivision of Section 5,
T. 39 N., R. 9 E., Gila and Salt River Meridian, Arizona

CHAINS	
80.00	<p>The 1/4 sec. cor. of secs. 5 and 32, on the N. bdy. of the Tp.</p> <hr/> <p>From the 1/4 sec. cor. of secs. 4 and 5. West, on the E. and W. center line of sec. 5. Over rolling land.</p>
4.20	Power line, 5 strand, bears N. and S.
40.00	The center 1/4 sec. cor. of sec. 5.
44.75	Sandstone shelf, 2 ft. high, bears N. 15° E. and S. 45° W.
50.65	High voltage transmission line, bears N. and S.
80.00	<p>The 1/4 sec. cor. of secs. 5 and 6.</p> <hr/> <p style="text-align: center;">Subdivision of Section 8, T. 39 N., R. 9 E., Gila and Salt River Meridian, Arizona</p> <hr/> <p>From the 1/4 sec. cor. of secs. 8 and 17. N. 0°03' W., on the N. and S. center line of sec. 8. Over rolling land.</p>
40.00	<p>Point for the center 1/4 sec. cor. of sec. 8, at intersection with the E. and W. center line sec. 8.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in solid sandstone bedrock, with brass cap mkd.</p> <p style="text-align: center;">T 39 N R 9 E C 1/4 S 8</p> <p style="text-align: center;">2014</p> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p> <p>Raise a mound of stone, 3 ft. base, 2 ft. high, W. of cor.</p> <p>Cor. is located 20 lks. E. of sandstone shelf, 3 ft. high, bears S. 20° E. and N. 15° W.</p>
80.00	<p>The 1/4 sec. cor. of secs. 5 and 8.</p> <hr/>

**Subdivision of Section 8,
T. 39 N., R. 9 E., Gila and Salt River Meridian, Arizona**

CHAINS	
	From the 1/4 sec. cor. of secs. 8 and 9. West, on the E. and W. center line of sec. 8. Over rolling land.
3.40	Trail road, bears N. and S.
4.45	Power line, 5 strand, bears N. and S.
35.75	Sandstone rim, 25 ft. high, bears S. 20° W. and N 50° W.
40.00	The center 1/4 sec. cor. of sec. 8.
53.30	High voltage transmission line, bears N. and S.
80.00	The 1/4 sec. cor. of secs. 7 and 8.
<hr/>	
Subdivision of Section 9, T. 39 N., R. 9 E., Gila and Salt River Meridian, Arizona	
<hr/>	
	From the 1/4 sec. cor. of secs. 9 and 16. N. 0°02' W., on the N. and S. center line of sec. 9. Over rolling land.
23.35	Bladed dirt road, 15 ft. wide, bears N. 40° E. and S. 40° W.
26.30	Power line, 2 strand, bears N. 40° E. and S. 40° W.
40.00	Point for the center 1/4 sec. cor. of sec. 9, at intersection with the E. and W. center line sec. 9. Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 23 ins. the ground, encircled with a collar of stone, 2 ft. base, to top, with brass cap mkd.
	T 39 N R 9 E C 1/4 S 9
	2014
	Deposit a magnet, in a white plastic case, at the base of the stainless steel post. Set a steel fence post nearby. Cor. is located 25 lks. N. of sandstone shelf, 1 ft. high, bears N. 30° E. and S. 40° W.
80.00	The 1/4 sec. cor. of secs. 4 and 9.
<hr/>	

**Subdivision of Section 9,
T. 39 N., R. 9 E., Gila and Salt River Meridian, Arizona**

CHAINS	
	From the 1/4 sec. cor. of secs. 9 and 10. West, on the E. and W. center line of sec. 9. Over rolling land.
26.15	Bladed dirt road, 15 ft. wide, bears N. 50° E. and S. 50° W.
28.10	Power line, 2 strand, bears N. 40° E. and S. 40° W.
40.00	The center 1/4 sec. cor. of sec. 9.
74.25	Power line, 2 strand, bears N. 5° E. and S. 5° W.
75.40	E. right-of-way fence of BIA Route 20, barbed wire, 4 strand, parallels highway.
76.95	BIA Route 20, an asphalt surfaced road, 33 ft. wide, bears N. 5° E. and S. 5° W.
78.45	W. right-of-way fence of BIA Route 20, barbed wire, 4 strand, parallels highway.
80.00	The 1/4 sec. cor. of secs. 8 and 9.
<hr/> Subdivision of Section 16, T. 39 N., R. 9 E., Gila and Salt River Meridian, Arizona <hr/>	
	From the 1/4 sec. cor. of secs. 16 and 21. N. 0°02' W., on the N. and S. center line of sec. 16. Over gently rolling land.
31.05	From this point, second order, National Geodetic Survey station KEAM 2, monumented with a brass tablet, 3 1/2 ins. diam., firmly set, in concrete, flush with the surface of limestone bedrock, mkd. KEAM 2 1947, bears E., 9.84 chs. dist. from which Reference monument No. 2, bears S. 33°25' E., 47.62 ft. dist., monumented with a brass tablet, 3 1/2 ins. diam., firmly set, in concrete, flush with the surface of limestone bedrock, mkd. KEAM NO 2 1934 and an arrow pointing to the cor.
40.00	Point for the center 1/4 sec. cor. of sec. 16, at intersection with the E. and W. center line sec. 16. Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 25 ins. in the ground, with brass cap mkd.

Subdivision of Section 16,
T. 39 N., R. 9 E., Gila and Salt River Meridian, Arizona

CHAINS	
	T 39 N R 9 E C 1/4 S 16
	2015
	Deposit a magnet, in a white plastic case, at the base of the stainless steel post.
	Set a steel fence post nearby.
	Cor. is located on westerly facing gentle slope.
80.00	The 1/4 sec. cor. of secs. 9 and 16.
	<hr/>
	From the 1/4 sec. cor. of secs. 15 and 16.
	West, on the E. and W. center line of sec. 16.
	Over rolling land.
40.00	The center 1/4 sec. cor. of sec. 16.
80.00	The 1/4 sec. cor. of secs. 16 and 17.
	<hr/>
	Subdivision of Section 17, T. 39 N., R. 9 E., Gila and Salt River Meridian, Arizona
	<hr/>
	From the 1/4 sec. cor. of secs. 17 and 20.
	N. 0°03' W., on the N. and S. center line of sec. 17.
	Over nearly level land.
40.00	Point for the center 1/4 sec. cor. of sec. 17, at intersection with the E. and W. center line sec. 17.
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.
	T 39 N R 9 E C 1/4 S 17
	2015
	Deposit a magnet, in a white plastic case, at the base of the stainless steel post.
	Set a steel fence post nearby.
80.00	The 1/4 sec. cor. of secs. 8 and 17.
	<hr/>

**Subdivision of Section 17,
T. 39 N., R. 9 E., Gila and Salt River Meridian, Arizona**

CHAINS	
	From the 1/4 sec. cor. of secs. 16 and 17. West, on the E. and W. center line of sec. 17. Over gently rolling land.
0.95	E. right-of-way fence of BIA Route 20, barbed wire, 4 strand, parallels highway.
2.50	BIA Route 20, an asphalt surfaced road, 33 ft. wide, bears N. 5° E. and S. 5° W.
4.00	W. right-of-way fence of BIA Route 20, barbed wire, 4 strand, parallels highway.
4.65	Power line, 5 strand, bears N. and S.
8.25	Power line, 2 strand, bears N. and S.
40.00	The center 1/4 sec. cor. of sec. 17.
55.90	High voltage transmission line, bears N. and S.
80.00	The 1/4 sec. cor. of secs. 17 and 18.
<hr/> Subdivision of Section 20, T. 39 N., R. 9 E., Gila and Salt River Meridian, Arizona <hr/>	
	From the 1/4 sec. cor. of secs. 20 and 29. N. 0°03' W., on the N. and S. center line of sec. 20. Over gently rolling land.
40.00	Point for the center 1/4 sec. cor. of sec. 20, at intersection with the E. and W. center line sec. 20. Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with brass cap mkd. T 39 N R 9 E C 1/4 S 20 2015
	Deposit a magnet, in a white plastic case, at the base of the stainless steel post. Set a steel fence post nearby.
80.00	The 1/4 sec. cor. of secs. 17 and 20.

Subdivision of Section 20,
T. 39 N., R. 9 E., Gila and Salt River Meridian, Arizona

CHAINS	
	<p>From the 1/4 sec. cor. of secs. 20 and 21.</p> <p>West, on the E. and W. center line of sec. 20.</p> <p>Over gently rolling land.</p>
0.35	BIA Route 20, an asphalt surfaced road, 33 ft. wide, bears N. and S.
1.90	W. right-of-way fence of BIA Route 20, barbed wire, 4 strand, parallels highway.
4.85	Power line, 5 strand, bears N. and S.
17.60	Power line, 2 strand, bears N. 20° E. and S. 20° W.
40.00	The center 1/4 sec. cor. of sec. 20.
58.55	High voltage transmission line, bears N. and S.
80.00	The 1/4 sec. cor. of secs. 19 and 20.
<hr/> <p>Subdivision of Section 21, T. 39 N., R. 9 E., Gila and Salt River Meridian, Arizona</p> <hr/>	
	<p>From the 1/4 sec. cor. of secs. 21 and 28.</p> <p>N. 0°02' W., on the N. and S. center line of sec. 21.</p> <p>Over gently rolling land.</p>
40.00	<p>Point for the center 1/4 sec. cor. of sec. 21, at intersection with the E. and W. center line sec. 21.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 25 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T 39 N R 9 E C 1/4 S 21</p> <p style="text-align: center;">2014</p> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p> <p>Set a steel fence post nearby.</p> <p>Cor. is located 1.75 chs. S. of wash, 5 ft. wide, 2 ft. deep, drains N. 60° E., and 55 lks. W. of trail road, bears N. 30° E. and S. 30° W., and 2.15 chs. E. of the same wash, 5 ft. wide, 2 ft. deep, drains N. 50° E.</p>

Subdivision of Section 21,
T. 39 N., R. 9 E., Gila and Salt River Meridian, Arizona

CHAINS	
80.00	<p>The 1/4 sec. cor. of secs. 16 and 21.</p> <hr/> <p>From the 1/4 sec. cor. of secs. 21 and 22. West, on the E. and W. center line of sec. 21. Over gently rolling land.</p>
40.00	The center 1/4 sec. cor. of sec. 21.
78.85	E. right-of-way fence of BIA Route 20, barbed wire, 4 strand, bears N. and S.
80.00	<p>The 1/4 sec. cor. of secs. 20 and 21.</p> <hr/> <p style="text-align: center;">Subdivision of Section 28, T. 39 N., R. 9 E., Gila and Salt River Meridian, Arizona</p> <hr/> <p>From the 1/4 sec. cor. of secs. 28 and 33. N. 0°02' W., on the N. and S. center line of sec. 28. Over rolling land.</p>
40.00	<p>Point for the center 1/4 sec. cor. of sec. 28, at intersection with the E. and W. center line sec. 28.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 27 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T 39 N R 9 E C 1/4 S 28</p> <p style="text-align: center;">2015</p> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p> <p>Set a steel fence post nearby.</p>
80.00	<p>The 1/4 sec. cor. of secs. 21 and 28.</p> <hr/> <p>From the 1/4 sec. cor. of secs. 27 and 28. West, on the E. and W. center line of sec. 28. Over rolling land.</p>
40.00	The center 1/4 sec. cor. of sec. 28.

Subdivision of Section 28,
T. 39 N., R. 9 E., Gila and Salt River Meridian, Arizona

CHAINS	
76.10	E. right-of-way fence of BIA Route 20, barbed wire, 4 strand, parallels highway.
77.60	BIA Route 20, an asphalt surfaced road, 33 ft. wide, bears N. and S.
79.10	W. right-of-way fence of BIA Route 20, barbed wire, 4 strand, parallels highway.
80.00	The 1/4 sec. cor. of secs. 28 and 29.
<hr/> <p style="text-align: center;">Subdivision of Section 29, T. 39 N., R. 9 E., Gila and Salt River Meridian, Arizona</p> <hr/>	
	From the 1/4 sec. cor. of secs. 29 and 32.
	N. 0°03' W., on the N. and S. center line of sec. 29.
	Over gently rolling land.
40.00	Point for the center 1/4 sec. cor. of sec. 29, at intersection with the E. and W. center line sec. 29.
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 25 ins. in the ground, with brass cap mkd.
	T 39 N R 9 E C 1/4 S 29
	2015
	Deposit a magnet, in a white plastic case, at the base of the stainless steel post.
	Set a steel fence post nearby.
65.70	Power line, 2 strand, bears N. 20° E. and S. 20° W.
80.00	The 1/4 sec. cor. of secs. 20 and 29.
<hr/>	
	From the 1/4 sec. cor. of secs. 28 and 29.
	West, on the E. and W. center line of sec. 29.
	Over gently rolling land.
5.10	Power line, 5 strand, bears N. and S.
40.00	The center 1/4 sec. cor. of sec. 29.

Subdivision of Section 29,
T. 39 N., R. 9 E., Gila and Salt River Meridian, Arizona

CHAINS	
61.20	High voltage transmission line, bears N. and S.
80.00	The 1/4 sec. cor. of secs. 29 and 30.
<hr/> <p style="text-align: center;">Subdivision of Section 32, T. 39 N., R. 9 E., Gila and Salt River Meridian, Arizona</p> <hr/>	
	From the 1/4 sec. cor. of secs. 5 and 32, on the S. bdy. of the Tp.
	N. 0°03' W., on the N. and S. center line of sec. 32.
	Over gently rolling land.
40.00	Point for the center 1/4 sec. cor. of sec. 32, at intersection with the E. and W. center line sec. 32.
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 27 ins. in the ground, with brass cap mkd.
	<p>T 39 N R 9 E C 1/4 S 32</p> <p>2015</p>
	Deposit a magnet, in a white plastic case, at the base of the stainless steel post.
	Set a steel fence post nearby.
80.00	The 1/4 sec. cor. of secs. 29 and 32.
<hr/>	
	From the 1/4 sec. cor. of secs. 32 and 33.
	West, on the E. and W. center line of sec. 32.
	Over gently rolling land.
5.30	Power line, 5 strand, bears N. and S.
11.05	Underground water line, bears S. 10° E. and N. 10° W.
16.05	Power line, 2 strand, bears N. 5° E. and S. 5° W.
40.00	The center 1/4 sec. cor. of sec. 32.
63.80	High voltage transmission line, bears N. and S.
80.00	The 1/4 sec. cor. of secs. 31 and 32.
<hr/>	

Subdivision of Section 33,
T. 39 N., R. 9 E., Gila and Salt River Meridian, Arizona

CHAINS	
	From the 1/4 sec. cor. of secs. 4 and 33, on the S. bdy. of the Tp.
	N. 0°02' W., on the N. and S. center line of sec. 33.
	Over gently rolling land.
28.25	Underground water line, bears N. 30° E. and S. 30° W.
40.00	Point for the center 1/4 sec. cor. of sec. 33, at intersection with the E. and W. center line sec. 33.
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with brass cap mkd.
	T 39 N R 9 E C 1/4 S 33
	2015
	Deposit a magnet, in a white plastic case, at the base of the stainless steel post.
	Set a steel fence post nearby.
	Cor. is located 1.80 chs. N. of bladed dirt road, 10 ft. wide, bears S. 75° E. and N. 75° W.
80.00	The 1/4 sec. cor. of secs. 28 and 33.

	From the 1/4 sec. cor. of secs. 33 and 34.
	West, on the E. and W. center line of sec. 33.
	Over gently rolling land.
40.00	The center 1/4 sec. cor. of sec. 33.
64.55	Underground water line, bears N. 5° E. and S. 5° W.
71.35	Power line, 2 strand, bears N. 25° E. and S. 25° W.
73.30	E. right-of-way fence of BIA Route 20, barbed wire, 4 strand, parallels highway.
74.80	BIA Route 20, an asphalt surfaced road, 33 ft. wide, bears N. and S.
76.35	W. right-of-way fence of BIA Route 20, barbed wire, 4 strand, parallels highway.
80.00	The 1/4 sec. cor. of secs. 32 and 33.

T. 39 N., R. 9 E., Gila and Salt River Meridian, Arizona

CHAINS	GENERAL DESCRIPTION
	<hr/> <p>The area surveyed is within the Navajo Indian Reservation, 7 miles south of the Lechee Community, and 10 miles south of the City of Page. Primary access is a paved road, BIA Route 20, bearing north and south in the western third of the township. A series of bladed dirt roads and trail roads provided access throughout the township. ATV's were required to access the majority of the areas within the township.</p> <p>There are no major housing developments, only smaller housing clusters and single home units scattered throughout the township.</p> <p>The highest elevation of this survey, 5800 feet above sea level, is near the southwest portion of the township atop Circular White Ridge. The lowest elevation, at 5000 feet, is in the canyon valley of Water Holes Canyon, in the northwest portion of the township.</p> <p>The vegetation consists of scattered juniper throughout the south half of the township, and is sparse in the northeast and northwest portions of the township. Sage brush, salt brush, black brush, rabbit brush, yucca, prickly pear, cliff rose, Mormon tea, and native grasses, are prominent throughout the township. There is presence of grazing cattle and horses in the area. The soil is mostly sandy loam with sandstone outcrops and bedrock. Canyon lands are more prominent in the north, east, and west portions of the township.</p> <p>The mean magnetic declination of 11° E. was derived from the United States Geological Survey computer program GEOMAG, utilizing the World Magnetic Model for Epoch 2010-2015 for the dates of survey.</p> <hr/>

CERTIFICATE OF SURVEY

I, Fabian Yazzie, Cadastral Surveyor, HEREBY CERTIFY upon honor, that in pursuance of special instructions bearing date of the 4th day of August, 2014, I have surveyed a portion of the Second Guide Meridian East (West Boundary), the subdivisional lines, and subdivision of certain sections, T. 39 N., R. 9 E., of the Gila and Salt River Meridian, in the State of Arizona, which are represented in the foregoing field notes as having been executed by me and under my direction. Said survey has been made in strict conformity with said special instructions, the Manual of Surveying Instructions, (2009), and in specific manner described in the foregoing field notes.

6/01/2015
(Date)

[Signature]
(Cadastral Surveyor)

CERTIFICATE OF APPROVAL

BUREAU OF LAND MANAGEMENT
Phoenix, Arizona

The foregoing field notes of the survey of a portion of the Second Guide Meridian East (West Boundary), the subdivisional lines, and subdivision of certain sections, T. 39 N., R. 9 E., Gila and Salt River Meridian, in the State of Arizona, executed by Fabian Yazzie, Cadastral Surveyor, having been critically examined and found correct, are hereby approved.

6/11/2015
(Date)

[Signature]
(Chief Cadastral Surveyor of Arizona)

~~CERTIFICATE OF TRANSCRIPT~~

~~I CERTIFY That the foregoing transcript of the field notes of the above described surveys in T. 39 N., R. 9 E., Gila and Salt River Meridian, Arizona, is a true copy of the original field notes.~~

~~_____
(Date)~~

~~_____
(Chief Cadastral Surveyor of Arizona)~~