

ORIGINAL

**UNITED STATES  
DEPARTMENT OF THE INTERIOR  
BUREAU OF LAND MANAGEMENT**

FIELD NOTES

OF THE

DEPENDENT RESURVEY OF PORTIONS OF THE SOUTH AND EAST BOUNDARIES  
AND PORTIONS OF THE SUBDIVISIONAL LINES,  
THE SUBDIVISION OF CERTAIN SECTIONS,  
METES-AND-BOUNDS SURVEYS IN SECTIONS 27 AND 35,  
AND THE RECOVERY OF CERTAIN CORNERS,  
TOWNSHIP 23 NORTH, RANGE 6 EAST,  
OF THE GILA AND SALT RIVER MERIDIAN,  
IN THE STATE OF ARIZONA.

**EXECUTED BY**

**Blas J. Urena, Cadastral Surveyor  
Christopher P. McDonald, Cadastral Surveyor**

Under Special Instructions dated November 4, 2013, approved November 4, 2013, which provided for the surveys included under Group No. 1123, and assignments instructions dated November 4, 2013 and April 3, 2014.

**Survey commenced November 4, 2013**

**Survey completed October 28, 2014**

# INDEX DIAGRAM

TOWNSHIP 23 NORTH                      RANGE 6 EAST  
 GILA & SALT RIVER MERIDIAN, ARIZONA

6	5	4 30	3 29	2	1
7	8	9 28	10	11 21	12 10
18	17	16	15 20	14	13 7
19	20	21	22 27 26	23 19	24
30	29	28 25	27 16 16 23	26 11 15	25
31	32	33 22	34 12 6	35 4	36

Subdivision of Section 3 ..... Pages 33-37  
 Subdivision of Section 10 ..... Pages 37-44  
 Subdivision of Section 13 ..... Pages 44-55  
 Subdivision of Section 15 ..... Pages 55-57  
 Subdivision of Section 26 ..... Pages 57-68  
 Subdivision of Section 27 ..... Pages 69-72  
 Metes-and-Bounds Survey in Section 27 ..... Pages 72-73  
 Subdivision of Section 34 ..... Pages 73-78  
 Subdivision of Section 35 ..... Pages 78-98  
 Metes-and-Bounds Survey in Section 35 ..... Pages 98-102  
 Recovery of Certain Corners ..... Pages 102-108

## T. 23 N., R. 6 E., Gila and Salt River Meridian, Arizona

## CHAINS

The following field notes describe the dependent resurvey of portions of the south and east boundaries and portions of the subdivisional lines, the subdivision of certain sections, metes-and-bounds surveys in sections 27 and 35, and the recovery of certain corners, Township 23 North, Range 6 East, Gila and Salt River Meridian, Arizona.

The history of surveys pertaining to this survey is as follows:

W. R. Fitzgerald surveyed the south, east and north boundaries and the subdivisional lines in 1883. Francis W. Oury resurveyed the east boundary in 1894. J. A. Lamport resurveyed part of the east boundary in 1903. Ty White and Bert E. Wakeman resurveyed the south, east and north boundaries and the subdivisional lines in 1943. Duane R. Garoutte resurveyed a portion of the south boundary and portions of the subdivisional lines and subdivided sections 14, 22, 23, 27, 34, and 35, in 1985.

The survey was executed in accordance with the specifications as set forth in the Manual of Surveying Instructions for the Survey of the Public Lands of the United States, 2009, and the Special Instructions dated November 4, 2013, for Group Number 1123, Arizona.

The true meridian direction and length of all lines were determined by static and real time kinematic global navigation satellite system observations using Trimble Navigation 5700, 5800 and R8-3 model receivers and a Sokkia Set 2B total station.

Preliminary to the resurvey, the lines of the prior surveys were retraced and search was made for all corners and other calls of record. Identified corners were remonumented in their original positions. Lost corners were reestablished and remonumented at proportionate positions based on the official record. The retracement data were thoroughly verified and only the true line field notes are given herein.

The survey was needed for the purpose of locating and identifying property boundaries between portions of the Coconino National Forest (CNF) System and other ownership lands necessary for the implementation of the Four Forest Restoration Initiative. Steel fence posts, with attached USFS sign # 54-2 were set on the forest boundary at intervals of 4 chains +/-.

## T. 23 N., R. 6 E., Gila and Salt River Meridian, Arizona

## CHAINS

The "USFS signs # 54-2" referred to in these notes are marked "PROPERTY BOUNDARY National Forest land behind this sign". The "USFS signs # 54-4" are marked "ATTENTION To willfully destroy, deface, change, or remove any Government Survey Corner or Monument, or to willfully cut down any Witness Tree or Blazed Tree marking the line of a Government Survey, is punishable by a Fine of \$250.00 or Six Months Imprisonment or both". The "USFS signs # 54-9" are marked "LAND SURVEY MONUMENT Please do not disturb". The "USFS signs Form 1505" are marked "PROPERTY BOUNDARY National Forest land behind this sign".

Geodetic control was derived from global navigation satellite system (GNSS) static observation post processed by National Geodetic Survey, Online Positioning User Service (OPUS), utilizing Continuously Operating Reference Stations DL1882 AZFL NAU FLAGSTAFF CORS, DL1898 AZPS PRESCOTT CORS, DL6010 AZSV STAR VALLEY CORS. The NAD 83 (CORS2011) (EPOCH: 2010.0000), geographic position of the 1/4 section corner of sections 2 and 35, Townships 22 and 23 North, Range 6 East, is as follows:

Latitude: 35°19'34.514" N. Longitude: 111°43'42.943" W.

The NAD 83 (CORS2011) (EPOCH 2010.0000), geographic position of the true point for the 1/4 section corner of sections 3 and 34, Townships 23 and 24 North, Range 6 East, is as follows:

Latitude: 35°24'47.847" N. Longitude: 111°44'47.866" W

The mean magnetic declination is 10 3/4° E.

---

**Dependent Resurvey of a Portion of the South Boundary,  
T. 23 N., R. 6 E., Gila and Salt River Meridian, Arizona**

---

Restoring the resurvey executed by  
Duane R. Garoutte, in 1985

---

Beginning at the 1/4 sec. cor. of secs. 2 and 35, Tps. 22 and 23 N., R. 6 E., on the S. bdy. of the Tp., monumented with an iron post, 1 in. diam., firmly set, projecting 8 ins. above ground, with brass cap mkd. 1/4 S35 S2 1943, with a mound of stone, 2 1/2 ft. base, 1 1/2 ft. high, N. of cor.

Add the marks T23N R6E T22N 2014 to the brass cap.

Set a steel fence post, with attached USFS sign # 54-9, S. of cor.

N. 89°55' W., bet. secs. 2 and 35, on the S. bdy. of the Tp.

Dependent Resurvey of a Portion of the South Boundary,  
T. 23 N., R. 6 E., Gila and Salt River Meridian, Arizona

## CHAINS

19.914

The W. 1/16 sec. cor. of secs. 2 and 35, monumented with a stainless steel post, 2 1/2 ins. diam., firmly set, projecting 10 ins. above ground, in a mound of stone, 3 ft. base, 6 ins. high, with brass cap mkd. T23N R6E W 1/16 S35 S2 T22N 1985.

from which the bearing trees mkd. in 1985

A ponderosa pine, 19 ins. diam., bears S. 88 1/2° E., 44 lks. dist., with a healed blaze and 1 BT tag.

A ponderosa pine, 19 ins. diam., bears S. 39 1/4° W., 75.5 lks. dist., with a healed blaze.

Add the marks 2014 to the brass cap.

Set a steel fence post, with attached USFS signs # 54-2 and # 52-9, SE of cor.

The cor. is located 4 lks. E. of a fence cor., barbed wire, bears N. and S. 80° W.

---

N. 89°54' W., beginning new measurement.

Continuing on the S. bdy. of the Tp.

19.914

The cor. of secs. 2, 3, 34, and 35, monumented with an iron post, 2 ins. diam., firmly set, projecting 4 ins. above ground, with brass cap mkd. T23N R6E S34 S35 S3 S2 T22N 1943, with a steel fence post, with attached USFS signs # 54-2 and # 52-9, W. of cor.

from which the original bearing tree

A ponderosa pine, 44 ins. diam., bears S. 47° E., 99 lks. dist., with a healed blaze and 1 BT tag. (Record: 97 lks.)

and the bearing trees mkd. in 1943

A ponderosa pine, 30 ins. diam., bears N. 45 1/2° E., 3.32 chs. dist., with a healed blaze and 1 BT tag. (Record: 3.33 chs.)

A ponderosa pine, 18 ins. diam., bears S. 39 1/4° W., 2.61 chs. dist., with a healed blaze and 1 BT tag. (Record: 2.63 chs.)

Add the marks 2014 to the brass cap.

The cor. is located 2 lks. S. of a fence cor., wood, bears N. and E.

---

Dependent Resurvey of a Portion of the South Boundary,  
T. 23 N., R. 6 E., Gila and Salt River Meridian, Arizona

CHAINS	
	<p>From the 1/4 sec. cor. of secs. 3 and 34, on the S. bdy. of the Tp., monumented with an iron post, 1 in. diam., firmly set, projecting 6 ins. above ground, with brass cap mkd. S34 1/4 S3 1943.</p> <p>from which the bearing trees mkd. in 1943</p> <p style="padding-left: 40px;">A ponderosa pine, 24 ins. diam., bears N. 30 1/4° E., 78 lks. dist., with a healed blaze.</p> <p style="padding-left: 40px;">A ponderosa pine, 31 ins. diam., bears S. 63 1/2° E., 1.58 chs. dist., with a healed blaze. (Record: 1.59 chs.)</p> <p>Set a steel fence post, with attached USFS signs # 54-2 and # 52-9, alongside of cor.</p> <p>S. 89°56' W., bet. secs. 3 and 34. on the S. bdy. of the Tp.</p>
40.02	<p>The cor. of secs. 3, 4, 33, and 34, monumented with an iron post, 2 in. diam., firmly set. projecting 16 ins. above ground, in a scattered mound of stone, with brass cap mkd. T23N R6E S33 S34 S4 S3 2014 1943.</p> <p>from which the bearing trees mkd. in 1943</p> <p style="padding-left: 40px;">A ponderosa pine, 18 ins. diam., bears N. 19 3/4° E., 1.65 chs. dist., with a healed blaze.</p> <p style="padding-left: 40px;">A ponderosa pine, 20 ins. diam., bears S. 34 3/4° E., 37 lks. dist., with a healed blaze. (Record 35 lks.)</p> <p style="padding-left: 40px;">A ponderosa pine, 22 ins. diam., bears S. 36 1/2° W., 1.15 chs. dist., with a healed blaze.</p> <p style="padding-left: 40px;">A ponderosa pine, 19 ins. diam., bears N. 28° W., 1.16 chs. dist., with a healed blaze.</p> <p>Reconstruct the mound of stone, 2 1/2 ft. base, to top of brass cap, utilizing the scattered mound of stone.</p> <p>Set a steel fence post, with attached USFS signs # 54-2 and # 52-9, alongside of cor.</p> <p>The cor. is located 4 lks. S. of a fence cor., barbed wire, from which fences extend N., S. 75° E., and W.</p> <hr/>

Dependent Resurvey of a Portion of the East Boundary,  
T. 23 N., R. 6 E., Gila and Salt River Meridian, Arizona

CHAINS	<p>Restoring the resurvey executed by Ty White and Bert E. Wakeman, in 1943</p> <hr/> <p>Beginning at the 1/4 sec. cor. of secs. 13 and 18, Tp. 23 N., Rs. 6 and 7 E., on the E. bdy. of the Tp., monumented with a brass tablet, 3 1/2 ins. diam., cemented in a drill hole in a lava stone, 30 x 24 ins., flush with ground, mkd. 1/4 S13 S18 1943.</p> <p>from which the bearing tree recovered in 1943</p> <p>A dead pine, 42 ins. diam., bears S. 86 1/2° W., 1.02 chs. dist., with scribe marks 1/4 S BT. Additionally marked on overgrowth, 1/4 S13.</p> <p>and the bearing tree mkd. in 1943</p> <p>A pine, 23 ins. diam., bears S. 24 3/4° E., 1.06 chs. dist., with no marks visible.</p> <p>and a new bearing tree</p> <p>A pine, 20 ins. diam., bears S. 60° W., 74 lks. dist., mkd. X at breast height and BT at base.</p> <p>Add the marks T23N R6E R7E 2014 to the brass tablet.</p> <p>Set a steel fence post, with attached USFS signs # 54-2 and # 52-9, SW of cor.</p> <p>N. 0°09' E., bet. secs. 13 and 18, on the E. bdy. of the Tp.</p>
20.01	<p>The N. 1/16 sec. cor. of secs. 13 and 18, established by Charles C. Doak, USFS Regional Land Surveyor, Southwest Region, Arizona R.L.S. No. 4476, in 1972, according to the plat titled "PLAT OF RIGHT OF WAY SURVEY ROAD NO. 4418B &amp; 4418.1 AND PARTIAL SUBDIVISION OF SECTION 13 A PORTION OF THE COCONINO NATIONAL FOREST PROPERTY LINE Situated in T. 23 N., R. 6 E.", on file with the Forest Land Surveyor at the headquarters of Coconino National Forest, monumented with an iron post, 2 1/2 ins. diam., firmly set, projecting 2 ins. above ground, with brass cap mkd. N 1/16 S13 S18 LS 4476 1972. This is accepted as a careful and faithful establishment of the cor. position.</p> <p>from which the bearing trees marked by Charles C. Doak in 1972</p> <p>A pine, 25 ins. diam., bears S. 24° W., 48 lks. dist., with a healed blaze and 1 BT tag.</p> <p>A pine, 21 ins. diam., bears N. 64° W., 26 lks. dist., with a healed blaze.</p>

Dependent Resurvey of a Portion of the East Boundary,  
T. 23 N., R. 6 E., Gila and Salt River Meridian, Arizona

CHAINS	
	<p>Set a steel fence post, with attached USFS signs # 54-2 and # 52-9, N. of cor.</p> <p>The cor. is located on the E. edge of a track road, 8 ft. wide, bears S. 15° E. and N. 15° W.</p> <hr/> <p>N. 0°09' E., beginning new measurement, continuing on the E. bdy. of the Tp.</p>
5.00	<p>The S-N-N 1/256 sec. cor. of secs. 13 and 18, established by Charles C. Doak, USFS Regional Land Surveyor, Southwest Region, Arizona R.L.S. No. 4476, in 1972, according to the plat titled "PLAT OF RIGHT OF WAY SURVEY ROAD NO. 4418B &amp; 4418.1 AND PARTIAL SUBDIVISION OF SECTION 13 A PORTION OF THE COCONINO NATIONAL FOREST PROPERTY LINE Situated in T. 23 N., R. 6 E.", on file with the Forest Land Surveyor at the headquarters of Coconino National Forest, monumented with an iron post, 2 1/2 ins. diam., firmly set, projecting 6 ins. above ground, with brass cap mkd. S-N-N 1/256 S13 S18 LS 4476 1972, with a steel fence post, E. of cor. This is accepted as a careful and faithful establishment of the cor. position.</p> <p>from which the bearing trees marked by Charles C. Doak in 1972</p> <p style="padding-left: 40px;">A pine, 11 ins. diam., bears S. 1° W., 1.20 chs. dist., with 2 healed blaze.</p> <p style="padding-left: 40px;">A pine, 33 ins. diam., bears S. 20° W., 22.5 lks. dist., with no marks visible.</p> <p>Set a steel fence post, with attached USFS signs # 54-2 and # 52-9, SW of cor.</p> <p>The cor. is located 2.5 lks. SE of a fence cor., barbed wire, bears N. and W.</p> <hr/> <p>N. 0°09' E., beginning new measurement, continuing on the E. bdy. of the Tp.</p> <p>Entering patented lands.</p>



Dependent Resurvey of a Portion of the East Boundary,  
T. 23 N., R. 6 E., Gila and Salt River Meridian, Arizona

CHAINS	
5.00	<p>The N-N 1/64 sec. cor. of secs. 13 and 18, established by Charles C. Doak, USFS Regional Land Surveyor, Southwest Region, Arizona R.L.S. No. 4476, in 1972, according to the plat titled "PLAT OF RIGHT OF WAY SURVEY ROAD NO. 4418B &amp; 4418.1 AND PARTIAL SUBDIVISION OF SECTION 13 A PORTION OF THE COCONINO NATIONAL FOREST PROPERTY LINE Situated in T. 23 N., R. 6 E.", on file with the Forest Land Surveyor at the headquarters of Coconino National Forest, monumented with an iron post, 2 1/2 ins. diam., firmly set, projecting 6 ins. above ground, with brass cap mkd. N-N 1/64 S13 S18 LS 4476 1972. This is accepted as a careful and faithful establishment of the cor. position.</p> <p>from which the bearing trees marked by Charles C. Doak in 1972</p> <p style="padding-left: 40px;">A pine, 20 ins. diam., bears N. 10° W., 13.5 lks. dist., with a healed blaze and 1 BT tag.</p> <p style="padding-left: 40px;">A pine, 16 ins. diam., bears N. 80° W., 19.5 lks. dist., with scribe marks N N 256 BT visible on partially open blaze and 1 BT tag.</p> <p>Set a steel fence post, with attached USFS signs # 54-2 and # 52-9, W. of cor.</p> <p>Cor. is located 3 lks. N. of a fence cor., barbed wire, bears S. and W.</p> <hr style="width: 20%; margin: 10px auto;"/> <p>N. 0°09' E., beginning new measurement, continuing on the E. bdy. of the Tp.</p> <p>Leaving patented lands.</p>
10.00	<p>The cor. of secs. 7, 12, 13, and 18, monumented with an iron post, 2 ins. diam., firmly set, projecting 5 ins. above ground, with brass cap mkd. T23N R6E R7E S12 S7 S13 S18 1943.</p> <p>from which the bearing tree recovered in 1943</p> <p style="padding-left: 40px;">A burned stump, 20 ins. diam., at base, 2 ft. height, bears S. 83 1/2° E., 32 lks. dist.</p> <p>and the remaining bearing tree mkd. in 1943</p> <p style="padding-left: 40px;">A stump, 6 ins. diam., in a stump hole, 12 ins. diam., bears N. 34 3/4° E., 95 lks. dist.</p> <p>and new bearing trees</p> <p style="padding-left: 40px;">A pine, 18 ins. diam., bears N. 20 3/4° E., 2.42 chs. dist., mkd. X at breast height and BT at base.</p>

**Dependent Resurvey of a Portion of the East Boundary,  
T. 23 N., R. 6 E., Gila and Salt River Meridian, Arizona**

CHAINS	
	<p>A pine, 13 ins. diam., bears N. 65 1/4° W., 1.78 chs. dist., mkd. X at breast height and BT at base.</p> <p>Add the marks 2014 to the brass cap.</p> <p>Set a steel fence post, with attached USFS sign # 52-9, E. of cor.</p>
	<p align="center"><b>Dependent Resurvey of a Portion of the Subdivisional Lines, T. 23 N., R. 6 E., Gila and Salt River Meridian, Arizona</b></p>
	<p align="center">Restoring the survey executed by Ty White and Bert E. Wakeman, in 1943</p> <hr/> <p>Beginning at the cor. of secs. 7, 12, 13, and 18, on the E. bdy. of the Tp.</p> <p>N. 89°47' W., bet. secs. 12 and 13.</p>
19.94	<p>Point for the E. 1/16 sec. cor. of secs. 12 and 13.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 16 ins. in the ground to bedrock, in a mound of stone, 3 1/2 ft. base, to top, with brass cap mkd.</p> <p align="center">T 23 N R 6 E S 12 E 1/16 ——— S 13</p> <p align="center">2014</p> <p>from which</p> <p>A pine, 10 ins. diam., bears North, 40.5 lks. dist., mkd. X at breast height and BT at base.</p> <p>A pine, 7 ins. diam., bears S. 30° W., 28.5 lks. dist., mkd. X at breast height and BT at base.</p> <p>Deposit a magnet, in a clear plastic case, at the base of the stainless steel post.</p> <p>Set a steel fence post, with attached USFS sign # 54-9, N. of cor.</p>
39.88	<p>The 1/4 sec. cor. of secs. 12 and 13, monumented with an iron post, 1 in. diam., firmly set, projecting 9 ins. above ground, in a mound of stone, 2 1/2 ft. base, to top, with brass cap mkd. 1/4 S12 S13 1943.</p>

Dependent Resurvey of a Portion of the Subdivisional Lines,  
T. 23 N., R. 6 E., Gila and Salt River Meridian, Arizona

CHAINS	
	<p>from which the remaining bearing tree recovered in 1943</p> <p style="padding-left: 40px;">A dead and partially burned pine, 32 ins. diam., bears N. 50° E., 32 lks. dist., with no marks visible.</p> <p>and the bearing trees mkd. in 1943</p> <p style="padding-left: 40px;">A pine, 15 ins. diam., bears S. 23 3/4° W., 24 lks. dist., with a healed blaze.</p> <p style="padding-left: 40px;">A pine, 12 ins. diam., bears N. 19° W., 48 lks. dist., with a healed blaze.</p> <p>Add the marks T23N R6E 2014 to the brass cap.</p> <p>Set a steel fence post, with attached USFS sign # 54-9, E. of cor.</p> <hr/> <p>From the 1/4 sec. cor. of secs. 25 and 26, monumented with an iron post, 1 in. diam., firmly set, projecting 10 ins. above ground, with brass cap mkd. 1/4 S26 S25 1943.</p> <p>from which the remaining bearing tree mkd. in 1943</p> <p style="padding-left: 40px;">A pine, 23 ins. diam., bears N. 1/2° W., 38 lks. dist., with no marks visible.</p> <p>Add the marks T23N R6E 2014 to the brass cap.</p> <p>Set a steel fence post, with attached USFS sign # 52-9, E. of cor.</p> <p>N. 0°26' E., bet. secs. 25 and 26.</p>
0.11	A downed barbed wire fence, bears E. and W.
20.005	<p>Point for the N. 1/16 sec. cor. of secs. 25 and 26.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 19 ins. in the ground, in a mound of stone, 3 1/2 ft. base, to top, with brass cap mkd.</p> <p style="text-align: center;">T 23 N R 6 E N 1/16 S 26   S 25</p> <p style="text-align: center;">2014</p> <p>from which</p> <p style="padding-left: 40px;">A ponderosa pine, 8 ins. diam., bears N. 42° E., 55.5 lks. dist., mkd. X at breast height and BT at base.</p>

Dependent Resurvey of a Portion of the Subdivisional Lines,  
T. 23 N., R. 6 E., Gila and Salt River Meridian, Arizona

CHAINS	<p>A ponderosa pine, 22 ins. diam., bears N. 75° W., 21 lks. dist., mkd. X at breast height and BT at base.</p> <p>Deposit a magnet, in a clear plastic case, at the base of the stainless steel post.</p> <p>Set a steel fence post, with attached USFS sign # 52-9, N. of cor.</p> <p>40.01 The cor. of secs. 23, 24, 25, and 26, monumented with an iron post, 2 ins. diam., firmly set, projecting 4 ins. above ground, in a scattered mound of stone, with brass cap mkd. T23N R6E S23 S24 S26 S25 1943.</p> <p>from which the bearing trees mkd. in 1943</p> <p>A double limber pine, 20 ins. diam., bears N. 36 1/2° E., 2.61 chs. dist., with a healed blaze on the S. trunk. (Record: 2.65 chs.)</p> <p>A ponderosa pine, 32 ins. diam., bears S. 26 3/4° E., 2.84 chs. dist., with a healed blaze and 1 BT tag. (Record: 2.86 chs.)</p> <p>A limber pine, 38 ins. diam., bears S. 45 1/4° W., 3.27 chs. dist., with a healed blaze, found a BT tag nearby.</p> <p>A limber pine, 20 ins. diam., bears N. 48 1/2° W., 2.84 chs. dist., with a healed blaze and 1 BT Tag on most westerly trunk. (Record: N. 47 3/4° W.)</p> <p>Add the marks 2014 to the brass cap.</p> <p>Set a steel fence post, with attached USFS sign # 52-9, E. of cor.</p> <hr/> <p style="text-align: center;">Restoring the resurvey executed by Duane R. Garoutte, in 1985</p> <hr/> <p>From the cor. of secs. 2, 3, 34, and 35, on the S. bdy. of the Tp.</p> <p>N. 0°06' W., bet. secs. 34 and 35.</p>
--------	-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------

Dependent Resurvey of a Portion of the Subdivisional Lines,  
T. 23 N., R. 6 E., Gila and Salt River Meridian, Arizona

CHAINS	
10.00	<p>The S-S 1/64 sec. cor. of secs. 34 and 35, established by Charles Dryden, Arizona R.L.S No. 13010, date unknown, monumented with a rebar, 1/2 in. diam., firmly set, projecting 2 ins. above ground, with aluminum cap, 1 1/2 in. diam., mkd. ARENCO PE 8218 LS 13010, with a steel fence post, with attached USFS sign # 54-2, N. of cor. This is accepted as a careful and faithful establishment of the cor. position.</p> <p>At the corner point</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 22 ins. in the ground, in a mound of stone, 2 1/2 ft. base, to top, with brass cap mkd.</p> <p style="text-align: center;">T 23 N R 6 E SS 1/64</p> <p style="text-align: center;">S 34   S 35</p> <p style="text-align: center;">2014</p> <p>Deposit a magnet, in a blue plastic case, at the base of the stainless steel post.</p> <p>Deposit the rebar, 12 ins. long with aluminum cap, inside the stainless steel post.</p> <p>Remove the steel fence post, with attached USFS sign # 54-2 from the field.</p> <p>Set a steel fence post, with attached USFS signs # 54-2 and # 54-9, NW of cor.</p> <p>The cor. is located 0.7 lk. NW of a fence cor. wood, bears E. and S. 10° E.</p> <hr style="width: 20%; margin: 10px auto;"/> <p>N. 0°06' W., beginning new measurement.</p>
10.00	<p>The S. 1/16 sec. cor. of secs. 34 and 35, monumented with an aluminum post, 3/4 in. diam., firmly set, 10 ins. below the surface of U. S. Forest Service Route 151, a gravel road, with an aluminum cap mkd. T23N R6E S 1/16 S34 S35 1985.</p> <p>from which the bearing trees mkd. in 1985</p> <p style="padding-left: 40px;">A ponderosa pine, 19 ins. diam., bears S. 46 1/2° E., 1.65 chs. dist., with a healed blaze, found a BT tag nearby.</p>

Dependent Resurvey of a Portion of the Subdivisional Lines,  
T. 23 N., R. 6 E., Gila and Salt River Meridian, Arizona

CHAINS	
	<p>A ponderosa pine, 20 ins. diam., bears S. 22 1/4° W., 2.40 chs. dist., with a healed blaze, found a BT tag nearby. (Record: 2.11 chs.)</p> <p>Add the marks 2014 to the brass cap.</p> <p>Deposit a magnet, in a white plastic case, on top of the aluminum cap.</p> <hr/> <p>N. 0°06' W., beginning new measurement.</p>
20.00	<p>The 1/4 sec. cor. of secs. 34 and 35, monumented with an iron post, 1 in. diam., firmly set, projecting 6 ins. above ground, in a scattered collar of stone, with brass cap mkd. 1/4 S34 S35 1943, with a mound of stone, 2 1/2 ft. base, 1 1/2 ft. high, W. of cor.</p> <p>Add the marks T23N R6E 2014 to the brass cap.</p> <p>Reconstruct the collar of stone, utilizing the scattered collar of stone, to top of brass cap.</p> <p>Set a steel fence post, with attached USFS signs # 54-2 and # 54-9, SE of cor.</p> <p>The cor. is located 1 lk. SE of a fence cor. barbed wire, with fences extend W. and irregularly N.</p> <hr/> <p>N. 0°25' E., beginning new measurement.</p>
20.42	<p>The N. 1/16 sec. cor. of secs. 34 and 35, monumented with a stainless steel post, 2 1/2 ins. diam., firmly set, projecting 3 ins. above ground, in a scattered collar of stone, with brass cap mkd. T23N R6E N 1/16 S34 S35 1985.</p> <p>from which the bearing trees mkd. in 1985</p> <p>A ponderosa pine, 18 ins. diam., bears S. 19° E., 45 lks. dist., with a healed blaze.</p> <p>A ponderosa pine, 22 ins. diam., bears S. 65 1/4° W., 1.135 chs. dist., with a healed blaze.</p> <p>Add the marks 2014 to the brass cap.</p> <p>Constructed a mound of stone, utilizing the scattered collar of stone, 2 1/2 ft. base, 1 1/2 ft. high, 1.5 lks. E. of cor.</p> <p>Set a Steel fence post, with attached USFS signs # 54-2 and # 54-9, N. of cor.</p>

Dependent Resurvey of a Portion of the Subdivisional Lines,  
T. 23 N., R. 6 E., Gila and Salt River Meridian, Arizona

CHAINS	
	<p>The cor. is located 1.5 lks. W. of a barbed wire fence, bears N. and S.</p> <hr/> <p>N. 0°25' E., beginning new measurement.</p>
20.42	<p>The cor. of secs. 26, 27, 34, and 35, monumented with an iron post, 2 ins. diam., firmly set, projecting 5 ins. above ground, in a scattered collar of stone, with brass cap mkd. T23N R6E S27 S26 S34 S35 1943.</p> <p>from which the bearing tress mkd. in 1943</p> <p style="padding-left: 40px;">A ponderosa pine, 18 ins. diam., bears S. 6 3/4° E., 1.55 chs. dist., with a healed blaze. (Record: 1.56 chs. and in 1985, 22 ins. diam.)</p> <p style="padding-left: 40px;">A ponderosa pine, 24 ins. diam., bears S. 68 3/4° W., 1.67 chs. dist., with a healed blaze.</p> <p>Reconstruct the collar of stone, 2 1/2 ft. base, to top of brass cap, utilizing the scattered collar of stone.</p> <p>Set a steel fence post, with attached USFS signs # 54-2 and # 54-9, alongside of cor.</p> <hr/> <p>From the 1/4 sec. cor. of secs. 26 and 35, monumented with an iron post, 1 in. diam., firmly set, projecting 4 ins. above ground, with brass cap mkd. 1/4 S26 S35 1943.</p> <p>Add the marks T23N R6E 2014 to the brass cap.</p> <p>Set a steel fence post, with attached USFS sign # 54-9, SE of cor.</p> <p>N. 89°09' W., bet. secs. 26 and 35.</p>
19.825	<p>The W. 1/16 sec. cor. of secs. 26 and 35, monumented with a stainless steel post, 2 1/2 ins. diam., firmly set, projecting 4 ins. above ground, with brass cap mkd. T23N R6E W 1/16 S26 S35 1985, with a steel fence post, with attached USFS sign # 54-9, E. of cor.</p> <p>from which the bearing trees mkd. in 1985</p> <p style="padding-left: 40px;">A ponderosa pine, 20 ins. diam., bears N. 84° E., 1.945 chs. dist., with 2 healed blazes and 1 BT tag.</p> <p style="padding-left: 40px;">A ponderosa pine, 21 ins. diam., bears S. 83° W., 46.5 lks. dist., with a healed blaze.</p>

Dependent Resurvey of a Portion of the Subdivisional Lines,  
T. 23 N., R. 6 E., Gila and Salt River Meridian, Arizona

CHAINS	
	<p>Add the marks 2014 to the brass cap.</p> <hr/>
	<p>From the S. 1/16 sec. cor. of secs. 26 and 27, monumented with an aluminum post, 3/4 in. diam., firmly set, projecting 6 ins. above ground, with aluminum cap mkd. T23N R6E S 1/16 S27 S26 1985.</p>
	<p>from which bearing objects mkd. in 1985</p>
	<p>A basalt boulder, 1 1/2 x 1 1/2 ft., projecting 6 ins. above ground, bears S. 20° W., 19.2 lks. dist., mkd. BXO on the NE face. Set a steel fence post, with attached USFS sign # 54-9, SW of boulder.</p>
	<p>A basalt boulder, 3 x 2 ft., projecting 6 ins. above ground, bears N. 69 1/2° W., 31.1 lks. dist., mkd. BXO on the top. Set a steel fence post, with attached USFS sign # 54-9, NW of boulder.</p>
	<p>Add the marks 2014 to the aluminum cap.</p>
	<p>Set a steel fence post, with attached USFS signs # 54-2 and # 54-9, SW of cor.</p>
	<p>From this cor., a fence corner, woven wire, 8 ft. high, bears N. 10 3/4° E., 8 lks. dist., from which fences extend N. and E., and S. 80° W., 20 lks. dist. to another fence corner, barbed wire, from which fences extend S. 25° E. and S. 80° W.</p>
	<p>N. 0°05' E., bet. secs. 26 and 27.</p>
<p>19.57</p>	<p>The 1/4 sec. cor. of secs. 26 and 27, monumented with an iron post, 1 in. diam., firmly set, projecting 10 ins. above ground, with brass cap mkd. 1/4 S27 S26 1943.</p>
	<p>Add the marks T23N R6E 2014 to the brass cap.</p>
	<p>Set a steel fence post, with attached USFS signs # 54-2 and # 54-9, N. of cor.</p>
	<p>The cor. is located at the N. end of a barbed wire fence extending S.</p>
	<p>From this cor., an open end pipe, of unknown origin, 1 in diam., projecting 12 ins. above ground, bears S. 23°07' E., 60.9 lks. dist. This pipe is located at W. end of a fence extending E.</p> <hr/>
	<p>N. 0°09' E., beginning new measurement.</p>
<p>17.14</p>	<p>Point for the 1/1024 sec. cor. of secs. 26 and 27.</p>



Dependent Resurvey of a Portion of the Subdivisional Lines,  
T. 23 N., R. 6 E., Gila and Salt River Meridian, Arizona

CHAINS	
	<p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T 23 N R 6 E</p> <p style="text-align: center;">1/1024</p> <p style="text-align: center;">2014</p> <p>from which</p> <p style="padding-left: 40px;">A ponderosa pine, 16 ins. diam., bears S. 25° W., 55.5 lks. dist., mkd. X at breast height and BT at base.</p> <p style="padding-left: 40px;">The SE cor. of a log cabin, 13 x 10 ft., bears N. 20° W., 70.2 lks. dist., the long side bears N. 10° W.</p> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p> <p>Set a steel fence post, with attached USFS signs # 54-2 and # 54-9, SW of cor.</p> <p>Entering patented lands.</p>
19.59	<p>The N. 1/16 sec. cor. of secs. 26 and 27, monumented with a stainless steel post, 2 1/2 ins. diam., firmly set, projecting 6 ins. above ground, with brass cap mkd. T23N R6E N 1/16 S27 S26 1985.</p> <p>from which the bearing trees mkd. in 1985</p> <p style="padding-left: 40px;">A limber pine, 14 ins. diam., bears S. 37 1/4° W., 81 lks. dist., with 2 healed blazes and 1 BT tag. (Record: 71 lks.)</p> <p style="padding-left: 40px;">A limber pine, 10 ins. diam., bears N. 38° W., 19 lks. dist., with a healed blaze and 1 BT tag.</p> <p>Add the marks 2014 to the brass cap.</p> <hr style="width: 20%; margin-left: auto; margin-right: auto;"/>
7.35	<p>N. 0°09' E., beginning new measurement.</p> <p>Continuing across patented lands.</p> <p>Point for the 1/1024 sec. cor. of secs. 26 and 27.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p>

Dependent Resurvey of a Portion of the Subdivisional Lines,  
T. 23 N., R. 6 E., Gila and Salt River Meridian, Arizona

CHAINS	<p style="text-align: center;">T 23 N R 6 E</p> <p style="text-align: center;">1/1024</p> <p style="text-align: center;">2014</p> <p>from which</p> <p style="padding-left: 40px;">An aspen, 12 ins. diam., bears N. 15° W., 87.5 lks. dist., mkd. X at breast height and BT at base.</p> <p style="padding-left: 40px;">A ponderosa pine, 16 ins. diam., bears N. 62° W., 1.205 chs. dist., mkd. X at breast height and BT at base.</p> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p> <p>Set a steel fence post, with attached USFS signs # 54-2 and # 54-9, NW of cor.</p> <p>Thence along a portion of the boundary of Coconino National Forest.</p> <p>19.60 The cor. of secs. 22, 23, 26, and 27, monumented with an iron post 2 ins. diam., firmly set, 6 ins. below the surface of the ground, with brass cap mkd. T23N R6E S22 S23 S27 S26 1985 1943.</p> <p>from which the remaining original bearing trees</p> <p style="padding-left: 40px;">A stump, 48 ins. diam., bears S. 2 3/4° E., 48 lks. dist., with a downed tree alongside, with a "T" post with attached BT tag. (Record: 46 lks.)</p> <p style="padding-left: 40px;">A ponderosa pine, 38 ins. diam., bears S. 49 1/4° W., 1.60 chs. dist., with scribe marks R visible on partially open blaze.</p> <p>and the bearing trees mkd. in 1985</p> <p style="padding-left: 40px;">A ponderosa pine, 18 ins. diam., bears S. 15 1/4° W., 85.5 lks. dist., with a healed blaze.</p> <p style="padding-left: 40px;">A ponderosa pine, 21 ins. diam., bears N. 84 3/4° W., 88 lks. dist., with a healed blaze.</p> <p>Add the marks 2014 to the brass cap.</p> <p>Set a steel fence post, with attached USFS signs # 54-2 and # 54-9, N. of cor.</p>
--------	------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------

Dependent Resurvey of a Portion of the Subdivisional Lines,  
T. 23 N., R. 6 E., Gila and Salt River Meridian, Arizona

CHAINS	
	<p>From this cor., the terminus of a barbed wire fence, 4 strand, bears S. 35° W., 6.5 lks. dist., from which the fence extends W., and N. 15° W., 5.2 lks. to the terminus of a wooden and metal fence, 6 ft. high, from which the fence extends N.</p> <hr/>
	<p>From the cor. of secs. 23, 24, 25, and 26.</p>
	<p>S. 89°38' W., bet. secs. 23 and 26.</p>
19.96	<p>The E. 1/16 sec. cor. of secs. 23 and 26, monumented with a stainless steel post, 2 1/2 ins. diam., firmly set, projecting 5 ins. above ground, with brass cap mkd. T23N R6E E 1/16 S23 S26 1985, with a steel fence post nearby.</p> <p>from which the bearing trees mkd. in 1985</p> <p style="padding-left: 40px;">A ponderosa pine, 14 ins. diam., bears N. 17 1/2° E., 1.22 chs. dist., with a healed blaze.</p> <p style="padding-left: 40px;">A ponderosa pine, 23 ins. diam., bears N. 52 1/2° W., 2.08 chs. dist., with a healed blaze.</p> <p>Add the marks 2014 to the brass cap.</p> <p>Set a steel fence post, with attached USFS signs # 54-2 and # 54-9, NE of cor.</p> <p>From this cor., an open end pipe of unknown origin, 1 in diam., projecting 12 ins. above ground, bears S. 89°46' W., 31.8 lks.</p> <hr/>
	<p>S. 89°37' W., beginning new measurement.</p>
9.976	<p>The W-E 1/64 sec. cor. of secs. 23 and 26, monumented with a stainless steel post, 2 1/2 ins. diam., firmly set, projecting 6 ins. above ground, with brass cap mkd. S23 W-E 1/64 S26 1985, with a steel fence post nearby.</p> <p>from which the bearing trees mkd. 1985</p> <p style="padding-left: 40px;">A ponderosa pine, 18 ins. diam., bears N. 40° E., 1.56 chs. dist., with a healed blaze.</p> <p style="padding-left: 40px;">A ponderosa pine, 16 ins. diam., bears N. 86 1/4° E., 2.59 chs. dist., with a healed blaze.</p> <p>Add the marks T23N R6E 2014 to the brass cap.</p> <p>Set a steel fence post, with attached USFS signs # 54-2 and # 54-9, NE of cor.</p>

Dependent Resurvey of a Portion of the Subdivisional Lines,  
T. 23 N., R. 6 E., Gila and Salt River Meridian, Arizona

CHAINS	
	<p>The cor. is located 3.5 lks. E. of the terminus of a wire fence, bears W.</p> <p>From this cor., an open end pipe of unknown origin, 1 in. diam., projecting 12 ins. above ground, bears N. 89°14' W., 27.5 lks. dist. This pipe is located in a fence extending N., and at N. end of gate extending S. 13° E., 24 lks. dist. to fence cor., from which fences extend W. and N. 13° W.</p> <hr/> <p>From the S. 1/16 sec. cor. of secs. 14 and 15, monumented with a stainless steel post, 2 1/2 ins. diam., firmly set, projecting 4 ins. above ground, with brass cap mkd. T23N R6E S 1/16 S15 S14 1985, with a steel fence post, with attached USFS sign # 54-9, W. of cor.</p> <p>from which the bearing tress mkd. in 1985</p> <p style="padding-left: 40px;">A ponderosa pine, 6 ins. diam., bears N. 56 1/4° E., 40.5 lks. dist., with a healed blaze.</p> <p style="padding-left: 40px;">A ponderosa pine, 17 ins. diam., bears N. 63 3/4° W., 46.5 lks. dist., with a healed blaze.</p> <p>Add the marks 2014 to the brass cap.</p> <p>Attach a USFS sign # 54-2 to the steel fence post.</p> <p>The cor. is located in a barbed wire fence, 5 strand, bears E. and W.</p> <p>N. 2°09' W., bet. secs. 14 and 15.</p>
19.82	<p>The 1/4 sec. cor. of secs. 14 and 15, monumented with an iron post, 1 in. diam., firmly set, projecting 1 in. above ground, with brass cap mkd. 1/4 S15 14 1943.</p> <p>from which the bearing tress mkd. in 1943</p> <p style="padding-left: 40px;">A white pine, 16 ins. diam., bears S. 14° E., 8 lks. dist., with scribe marks 1/4 S14 BT visible on partially open blaze.</p> <p style="padding-left: 40px;">A ponderosa pine, 9 ins. diam., bears N. 83 1/2° W., 38 lks. dist., with scribe marks 1/4 S15 BT visible on partially open blaze.</p> <p>Add the marks T23N R6E 2014 to the brass cap.</p> <p>Set a steel fence post, with attached USFS sign # 54-9, W. of cor.</p> <hr/>

Dependent Resurvey of a Portion of the Subdivisional Lines,  
T. 23 N., R. 6 E., Gila and Salt River Meridian, Arizona

CHAINS	<p>From the 1/4 sec. cor. of secs. 11 and 14, monumented with an iron post, 1 in. diam., firmly set, projecting 5 ins. above ground, with brass cap mkd. 1/4 S11 S14 1943.</p> <p>from which the remaining bearing tree mkd. in 1943</p> <p style="padding-left: 40px;">A ponderosa pine, 15 ins. diam., bears N. 43° E., 1.68 chs. dist., with scribe marks 1/4 visible on partially open blaze.</p> <p>Add the marks T23N R6E 2014 to the brass cap.</p> <p>Set a steel fence post, with attached USFS signs # 54-2 and # 54-9, N. of cor.</p> <p>The cor. is located alongside a fence corner, with wooden fences extending E. and S. and with wooden and rebar fence extending W.</p> <p>S. 89°29' W., bet. secs. 11 and 14.</p> <p>2.522 The 1/1024 sec. cor. of secs. 11 and 14, monumented with a rebar, 18 ins. long, 1/2 in. diam., firmly set, projecting 2 ins. above ground, with brass tag mkd. FOUND LS 29884, with a 60D nail alongside. Found and accepted by Stanley L. Nienhuser, Arizona R.L.S. No. 29884, in 2012, according to Instrument # 3636098, on file at Coconino County Recorder's Office. This is accepted as a careful and faithful determination of the cor. point.</p> <p>At the corner point</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T 23 N R 6 E</p> <p style="text-align: center;">1/1024</p> <p style="text-align: center;">2014</p> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p> <p>Deposit the rebar with brass tag and the 60D nail inside the stainless steel post</p> <p>Set a steel fence post, with attached USFS signs # 54-2 and # 54-9, NE of cor.</p> <p>The cor. is located 0.5 lk. N. of a fence, wooden and rebar, 5.5 ft. high, bears E. and W.</p> <p>Entering patented lands.</p>
--------	------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------

Dependent Resurvey of a Portion of the Subdivisional Lines,  
T. 23 N., R. 6 E., Gila and Salt River Meridian, Arizona

CHAINS	
2.974	A rebar, 1/2 in. diam., firmly set, flush with ground, this rebar is located in a fence corner, wooden and rebar, 5.5 ft. high, with fences extending E., S., and W.
9.168	A rebar, 1/2 in. diam., firmly set, projecting 6 ins. above ground, with a brass tag mkd. LS 2473, established by Wilfred P. Hanson, in 1969.
10.098	<p>The E-W 1/64 sec. cor. of secs. 11 and 14, monumented with an aluminum post, 12 ins. long, 3/4 in. diam., loosely set, in a drill hole, in bedrock, and in mound of stone, 2 ft. base, to top, with aluminum cap mkd. E-W 1/64 S11 S14 1985, with a steel fence post, with attached USFS signs # 54-2 and # 54-9, NE of cor.</p> <p>from which the bearing tree mkd. in 1985</p> <p style="padding-left: 40px;">A ponderosa pine, 21 ins. diam., bears N. 70 1/2° E., 34 lks. dist., with a healed blaze.</p> <p>Cement the aluminum post in drill hole.</p> <p>Deposit a magnet, without plastic case, at the base of the aluminum post.</p> <p>Add the marks T23N R6E 2014 to the aluminum cap.</p> <p>Rebuild mound of stone, 2 ft. base, to top of aluminum cap.</p> <p>Remove the USFS signs # 54-2 and # 54-9 from the steel fence post.</p> <p>Set a steel fence post, with attached USFS signs # 54-2 and # 54-9, NW of cor.</p> <p>The cor. is located 1.5 lks. N. of a wooden and wire fence, bears E. and W.</p>
40.87	<p>From the cor. of secs. 3, 4, 33, and 34, on the S. bdy. of the Tp.</p> <p>N. 0°19' W., bet. secs. 33 and 34.</p> <p>The 1/4 sec. cor. of secs. 33 and 34, monumented with an iron post, 1 in. diam., firmly set, projecting 12 ins. above ground, in a scattered collar of stone, with brass cap mkd. 1/4 S33 S34 1943.</p> <p>from which the bearing trees mkd. in 1943</p> <p style="padding-left: 40px;">A standing dead ponderosa pine, 43 ins. diam., bears S. 43° E., 55 lks. dist., with a healed blaze.</p>

Dependent Resurvey of a Portion of the Subdivisional Lines,  
T. 23 N., R. 6 E., Gila and Salt River Meridian, Arizona

CHAINS	
	<p>A standing dead ponderosa pine, 32 ins. diam., bears S. 1° W., 1.13 chs. dist., with a healed blaze.</p> <p>and the new bearing trees</p> <p>A pine, 17 ins. diam., bears N. 40° E., 85.5 lks. dist., mkd. 1/4 S34 BT.</p> <p>A pine, 23 ins. diam., bears N. 53° W., 1.07 chs. dist., mkd. 1/4 S33 BT.</p> <p>Reconstruct the collar of stone, 2 1/2 ft. base, to top of brass cap, utilizing the scattered collar of stone.</p> <p>Set a steel fence post, with attached USFS signs # 54-2 and # 54-9, alongside of cor.</p> <p>The cor. is located on east edge of dirt road extending N. and S.</p> <hr/>
10.07	<p>From the cor. of secs. 26, 27, 34, and 35.</p> <p>S. 89°16' W., bet. secs. 27 and 34.</p> <p>The E-E 1/64 sec. cor. of secs. 27 and 34, monumented with an aluminum post, 3/4 in. diam., firmly set, projecting 6 ins. above ground, with aluminum cap mkd. S27 E-E 1/64 S34 1985.</p> <p>from which the bearing tree mkd. in 1985</p> <p>A ponderosa pine, 25 ins. diam., bears N. 78° E., 67.5 lks. dist., with a healed blaze.</p> <p>Set a steel fence post, with attached USFS signs # 54-2 and # 54-9, alongside of cor.</p> <p>The cor. is located 17.5 lks. S. of down fence extending E. and W., and 87 lks. S. of another down fence extending E. and W.</p> <hr/> <p>S. 89°15' W., beginning new measurement.</p> <p>Entering patented lands.</p>
10.08	<p>The E. 1/16 sec. cor. of secs. 27 and 34, monumented with a stainless steel post, 2 1/2 ins. diam., firmly set, projecting 3 ins. above ground, with brass cap mkd. T23N R6E S27 E 1/16 S34 1985.</p>

Dependent Resurvey of a Portion of the Subdivisional Lines,  
T. 23 N., R. 6 E., Gila and Salt River Meridian, Arizona

CHAINS	
	<p>The cor. is located next to a wooden power pole, approximately 6 ft. tall.</p> <hr/> <p>S. 89°17' W., beginning new measurement. Continuing across patented lands.</p> <p>5.03 The E-W-E 1/256 sec. cor. of secs. 27 and 34, monumented with a stainless steel post, 2 1/2 ins. diam., firmly set, projecting 3 ins. above ground, with brass cap mkd. S27 E-W-E 1/256 S34 1985.</p> <p>from which the bearing tree mkd. in 1985</p> <p style="padding-left: 40px;">A ponderosa pine, 20 ins. diam., bears N. 60 1/2° W., 43 lks. dist., with a healed blaze.</p> <p>Set a steel fence post, with attached USFS signs # 54-2 and # 54-9, alongside of cor.</p> <hr/> <p>S. 89°18' W., beginning new measurement.</p> <p>Thence along a portion of the boundary of Coconino National Forest.</p>
5.03	<p>The W-E 1/64 sec. cor. of secs. 27 and 34, established by Donald L. Ziemba, Arizona R.L.S. No. 16218, date unknown, monumented with a rebar, 1/2 in. diam., firmly set, flush with the ground, with yellow plastic cap mkd. LS 16218. This is accepted as a careful and faithful establishment of the cor. position.</p> <p>At the corner point</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T 23 N R 6 E S 27 W-E 1/64 S 34 2013</p> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p> <p>Deposit the rebar with yellow plastic cap inside the stainless steel post.</p> <p>Set a steel fence post, with attached USFS signs # 54-2 and # 54-9, alongside of cor.</p> <hr/>



Dependent Resurvey of a Portion of the Subdivisional Lines,  
T. 23 N., R. 6 E., Gila and Salt River Meridian, Arizona

CHAINS	
	<p>S. 89°18' W., beginning new measurement.</p> <p>10.06 The 1/4 sec. cor. of secs. 27 and 34, monumented with an iron post, 1 in. diam., firmly set, flush with the ground, with brass cap mkd. S27 1/4 S34 1943, witnessed by a scattered mound of stone, N. of cor.</p> <p>Reconstruct mound of stone, utilizing the scattered mound of stone, 2 1/2 ft. base, 1 ft. high, N. of cor.</p> <p>Set a steel fence post, with attached USFS signs # 54-2 and # 54-9, alongside of cor.</p> <hr/> <p>From the S-N-N 1/256 sec. cor. of secs. 27 and 28, monumented with an aluminum post, 36 ins. long, 3/4 in. diam., projecting 6 ins. above ground, with the top 6 ins. bending to the E., with aluminum cap mkd. S-N-N 1/256 S28 S27 1985.</p> <p>from which the bearing trees mkd. in 1985</p> <p style="padding-left: 40px;">A ponderosa pine, 26 ins. diam., bears S. 1/2° E., 1.26 chs. dist., with a healed blaze and 1 BT tag.</p> <p style="padding-left: 40px;">A ponderosa pine, 23 ins. diam., bears S. 68 1/4° W., 1.10 chs. dist., with a healed blaze.</p> <p>Straighten the aluminum post and reset 11 ins. below the surface of the ground.</p> <p>Deposit a magnet, in a white plastic case, alongside the aluminum post.</p> <p>Add the marks T23N R6E 2014 to the aluminum cap.</p> <p>The cor. is located in an ATV trail, bears S 50° E. and N 35° W.</p> <p>From this cor., a fence cor., barbed wire, 4 strand, bears N. 8°48' W., 26 lks. dist., with fences extending N. 8° W. and S. 45° E.</p> <p>N. 0°22' W., bet. secs. 27 and 28.</p>
15.03	<p>The cor. of secs. 21, 22, 27, and 28, monumented with an iron post, 2 ins. diam., firmly set, projecting 8 ins. above ground, with brass cap mkd. T23N R6E S21 S22 S28 S27 1985 1943.</p> <p>from which the bearing trees mkd. in 1943</p> <p style="padding-left: 40px;">A limber pine, 26 ins. diam., bears N. 77 1/4° E., 52 lks. dist., with scribe marks N 6E S visible on partially open blaze and 1 BT tag. (Record: 51 lks.)</p>

Dependent Resurvey of a Portion of the Subdivisional Lines,  
T. 23 N., R. 6 E., Gila and Salt River Meridian, Arizona

CHAINS	
	<p>A ponderosa pine, 48 ins. diam., bears S. 74 3/4° E., 1.54 chs. dist., with scribe marks T23N R6E S2 BT visible on partially open blaze and 1 BT tag.</p> <p>A ponderosa pine, 32 ins. diam., bears S. 47 3/4° W., 2.33 chs. dist., with a healed blaze.</p> <p>and the bearing tree mkd. in 1985</p> <p>A ponderosa pine, 12 ins. diam., bears N. 57 1/2° W., 70.5 lks. dist., with a healed blaze.</p> <p>Add the marks 2014 to the brass cap.</p> <p>Set a steel fence post, with attached USFS signs # 54-2 and # 54-9, SW of cor.</p> <hr/> <p>From the cor. of secs. 22, 23, 26, and 27.</p> <p>N. 89°29' W., bet. secs. 22 and 27.</p>
20.244	<p>The E. 1/16 sec. cor. of secs. 22 and 27, monumented with a stainless steel post, 2 1/2 ins. diam., firmly set, projecting 4 ins. above ground, with brass cap mkd. T23N R6E S22 E 1/16 S27 1985.</p> <p>from which the bearing trees mkd. in 1985</p> <p>A limber pine, 9 ins. diam., bears S. 42 1/2° E., 98 lks. dist., with a healed blaze and 1 BT tag.</p> <p>A limber pine, 13 ins. diam., bears N. 75 3/4° W., 40.5 lks. dist., with a healed blaze and 1 BT tag.</p> <p>Add the marks 2014 to the brass cap.</p> <p>Set a steel fence post, with attached USFS sign # 54-2, E. of cor.</p> <hr/> <p>From the E-E-W 1/256 sec. cor. of secs. 22 and 27, monumented with an aluminum post, 3/4 in. diam., firmly set, projecting 8 ins. above ground, with aluminum cap mkd. S22 E-E-W 1/256 S27 1985, with a steel fence post, NE of cor.</p> <p>from which the bearing trees mkd. in 1985</p> <p>A ponderosa pine, 12 ins. diam., bears N. 46 1/4° E., 31 lks. dist., with scribe marks EEW 1/256 S22 BT visible on partially open blaze.</p>

Dependent Resurvey of a Portion of the Subdivisional Lines,  
T. 23 N., R. 6 E., Gila and Salt River Meridian, Arizona

CHAINS											
	<p>A ponderosa pine, 12 ins. diam., bears N. 89° W., 65 lks. dist., with a healed blaze.</p> <p>Add the marks T23N R6E 2014 to the aluminum cap.</p> <p>Attached USFS signs # 54-2 and # 54-9 to the steel fence post.</p> <p>N. 89°26' W., bet. secs. 22 and 27.</p> <p>Entering patented lands.</p> <p>8.808 AP 1, lot 1, sec. 27, established by Christopher J. Franks, Arizona R.L.S. No. 22258, date unknown, and accepted by Kenneth A. Krenke, Arizona R.L.S. No. 14671, in 1994, according to Book 12, Page 25, on file at Coconino County Recorder's Office. monumented with a rebar, 18 ins. long, 1/2 in. diam., firmly set, flush with ground, with plastic cap, 1 in. diam., mkd. C J F LS 22258. This is accepted as a careful and faithful establishment of the cor. position.</p> <p>At the corner point</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, in a collar of stone, with brass cap mkd.</p> <div style="text-align: center;"> <table border="0"> <tr><td>T 23 N</td><td>R 6 E</td></tr> <tr><td colspan="2">S 22</td></tr> <tr><td colspan="2">-----</td></tr> <tr><td>AP 1</td><td> </td></tr> <tr><td>L 1</td><td>  S 27</td></tr> </table> <p>2014</p> </div> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p> <p>Deposit the rebar with plastic cap inside the stainless steel post.</p> <p>Set a steel fence post, with attached USFS signs # 54-2 and # 54-9, SW of cor.</p> <p>The cor. is located in a wooden fence, bears E. and W.</p> <p>Thence along a portion of the boundary of Coconino National Forest.</p>	T 23 N	R 6 E	S 22		-----		AP 1		L 1	S 27
T 23 N	R 6 E										
S 22											
-----											
AP 1											
L 1	S 27										
15.206	<p>The W. 1/16 sec. cor. of secs. 22 and 27, monumented with an aluminum post, 3/4 in. diam., firmly set, projecting 3 ins. above ground, with aluminum cap mkd. T23N R6E W 1/16 S 22 S27 1985, with a steel fence post, N. of cor.</p> <p>Add the marks 2014 to the aluminum cap.</p>										

Dependent Resurvey of a Portion of the Subdivisional Lines,  
T. 23 N., R. 6 E., Gila and Salt River Meridian, Arizona

CHAINS	
	<p>Set a steel fence post, with attached USFS signs # 54-2 and # 54-9, W. of cor.</p> <p>The cor. is located 2 lks. S. of a wooden fence, bears E. and W.</p> <hr/> <p>N. 89°27' W., beginning new measurement.</p>
20.27	<p>The cor. of secs. 21, 22, 27 and 28.</p> <hr/> <p style="text-align: center;">Restoring the resurvey executed by Ty White and Bert E. Wakeman, in 1943</p> <hr/> <p>From the 1/4 sec. cor. of secs. 9 and 10, monumented with an iron post, 1 in. diam., firmly set, projecting 7 ins. above ground, with brass cap mkd. 1/4 S9 S10 1943.</p> <p>from which the remaining bearing tree recovered in 1943</p> <p style="padding-left: 40px;">A stump hole, bears S. 27° W., 86 lks. dist., with a downed tree alongside.</p> <p>and the remaining bearing tree mkd. in 1943</p> <p style="padding-left: 40px;">A pine, 17 ins. diam., bears N. 25 1/2° W., 48 lks. dist., with no marks visible.</p> <p>and a new bearing tree</p> <p style="padding-left: 40px;">A pine, 13 ins. diam., bears S. 5° E., 96.5 lks. dist., mkd. X at breast height and BT at base.</p> <p>Add the marks T23N R6E 2014 to the brass cap.</p> <p>Set a steel fence post, with attached USFS sign # 54-9, W. of cor.</p> <p>N. 0°55' W., bet. secs. 9 and 10.</p>
19.81	<p>Point for the N. 1/16 sec. cor. of secs. 9 and 10, not monumented.</p>
39.62	<p>The cor. of secs. 3, 4, 9, and 10, monumented with an iron post, 2 ins. diam., firmly set, 6 ins. below the surface of road, with brass cap mkd. T23N R6E S4 S3 S9 S10 1943.</p> <p>from which the remaining bearing trees recovered in 1943</p> <p style="padding-left: 40px;">A pine, 25 ins. diam., bears S. 48° E., 24 lks. dist., with scribe marks BT visible on partially open blaze and 1 BT tag.</p>

Dependent Resurvey of a Portion of the Subdivisional Lines,  
T. 23 N., R. 6 E., Gila and Salt River Meridian, Arizona

CHAINS	
	<p>A pine snag, 29 ins. diam., bears S. 55 3/4° W., 34 lks. dist., with scribe marks N R6 BT visible on partially open blaze and 1 BT tag.</p> <p>and the bearing trees mkd. in 1943</p> <p>A pine, 26 ins. diam., bears N. 32° E., 58 lks. dist., with scribe marks N R6E visible on partially open blaze, 1 BT tag and 1 USFS sign # 54-4.</p> <p>A pine, 18 ins. diam., bears N. 14 1/4° W., 1.18 chs. dist., with a healed blaze.</p> <p>Add the marks 2014 to the brass cap.</p> <p>The cor. is located in an abandoned graded road.</p> <hr/> <p>From the 1/4 sec. cor. of secs. 3 and 10, monumented with an iron post, 1 in. diam., firmly set, projecting 12 ins. above ground, in a mound of stone, 2 1/2 ft. base, 6 ins. high, with brass cap mkd. 1/4 S3 S10 1943.</p> <p>from which new bearing trees</p> <p>A pine, 20 ins. diam., bears N. 54° E., 92.5 lks. dist., mkd. 1/4 S3 BT.</p> <p>A pine, 21 ins. diam., bears South, 1.57 chs. dist., mkd. 1/4 S10 BT.</p> <p>Add the marks T23N R6E 2014 to the brass cap.</p> <p>Rebuild the mound of stone, 3 ft. base, to top of brass cap.</p> <p>Set a steel fence post, with attached USFS sign # 54-9, N. of cor.</p> <p>S. 89°54' W., bet. secs. 3 and 10.</p>
15.207	<p>Point for the W-E-W 1/256 sec. cor. of secs. 3 and 10.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T 23 N R 6 E S 3 W-E-W 1/256 S 10  2014</p> <p>from which</p>

Dependent Resurvey of a Portion of the Subdivisional Lines,  
T. 23 N., R. 6 E., Gila and Salt River Meridian, Arizona

CHAINS	
	<p>A pine, 18 ins. diam., bears N. 55° E., 1.31 chs. dist., mkd. X at breast height and BT at base.</p> <p>A pine, 25 ins. diam., bears S. 45° E., 1.53 lks. dist., mkd. X at breast height and BT at base.</p> <p>Deposit a magnet, in a pink plastic case, at the base of the stainless steel post.</p> <p>Set a steel fence post, with attached USFS signs # 54-2 and # 54-9, S. of cor.</p> <p>Entering patented lands.</p>
20.276	Point for the W. 1/16 sec. cor. of secs. 3 and 10, not monumented.
35.484	Point for the W-W-W 1/256 sec. cor. of secs. 3 and 10.
	<p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T 23 N R 6 E S 3 W-W-W 1/256 S 10</p> <p style="text-align: center;">2014</p> <p>from which</p> <p>A pine, 9 ins. diam., bears S. 77° W., 35.5 lks. dist., mkd. X at breast height and BT at base.</p> <p>A pine, 11 ins. diam., bears N. 45° W., 1.255 chs. dist., mkd. X at breast height and BT at base.</p> <p>Deposit a magnet, in a pink plastic case, at the base of the stainless steel post.</p> <p>Set a steel fence post, with attached USFS signs # 54-2 and # 54-9, N. of cor.</p> <p>Leaving patented lands.</p>
40.553	The cor. of secs. 3, 4, 9 and 10.
	<hr/> <p>N. 0°33' W., bet. secs. 3 and 4.</p>
5.10	Point for the S-S-S 1/256 sec. cor. of secs. 3 and 4.

Dependent Resurvey of a Portion of the Subdivisional Lines,  
T. 23 N., R. 6 E., Gila and Salt River Meridian, Arizona

CHAINS	<p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 23 ins. in the ground, in a collar of stone, with brass cap mkd.</p> <p style="text-align: center;">T 23 N R 6 E S-S-S 1/256 S 4   S 3 2014</p> <p>from which</p> <p style="padding-left: 40px;">A pine, 11 ins. diam., bears S. 45° E., 35 lks. dist., mkd. X at breast height and BT at base.</p> <p style="padding-left: 40px;">An aluminum cap, 3 ins. diam., in concrete cylinder, 8 ins. diam., flush with the ground for a reference monument, bears N. 0°54' W., 58.1 ft. dist. mkd. A.D.O.T. HIGHWAY DIV. 19, with an angle iron with no marks, 2.7 lks. S. of the cap. This cor. is located 1.5 lks. W. of the easterly right-of-way fence of Arizona Highway No. 180, barbed wire, 4 strand, bears S. 5° E. and N. 5° W.</p> <p>Deposit a magnet, in a pink plastic case, at the base of the stainless steel post.</p> <p>Set a steel fence post, with attached USFS signs # 54-2 and # 54-9, SE of cor.</p> <p>The cor. is located 0.5 lk. W. of the easterly right-of-way fence of Arizona Highway No. 180, barbed wire, 4 strand, bears S. 5° E. and N. 5° W.</p> <p>10.20 Point for the S-S 1/64 sec. cor. of secs. 3 and 4.</p> <p>Set a mag nail , 2 1/2 ins. long, flush with asphalt, with brass washer, 1 1/2 ins. diam., mkd. BLM 2014.</p> <p>from which</p> <p style="padding-left: 40px;">An aluminum cap, 3 ins. diam., in concrete cylinder, 12 ins. diam., flush with the ground for a reference monument, bears N. 70°31' E., 105.8 ft. dist. mkd. A.D.O.T. HIGHWAY DIV. 19, with an angle iron mkd. PT 1018+08.39, 2.3 lks. S. of the cap. This cor. is located 2.3 lks. E. of the easterly right-of-way fence of Arizona Highway No. 180, barbed wire, 4 strand, bears N. and S.</p>
--------	---------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------

Dependent Resurvey of a Portion of the Subdivisional Lines,  
T. 23 N., R. 6 E., Gila and Salt River Meridian, Arizona

CHAINS	
	<p>An aluminum cap. 3 ins. diam., in concrete cylinder, 12 ins. diam., flush with the ground for a reference monument, bears S. 74°59' E., 50.6 ft. dist. mkd. A.D.O.T. HIGHWAY DIV. 19, with an angle iron with no marks, 2.3 lks. S. of the cap. This cor. is located 3.9 lks. S 60° W. of a fence corner on the easterly right-of-way fence of Arizona Highway No. 180, barbed wire, 4 strand, bears E. and S.</p> <p>The cor. is located in the center line of Arizona Highway No. 180, asphalt surfaced, 26 ft. wide, along a curve concave to the E.</p> <p>Thence along Arizona Highway No. 180.</p>
20.40	<p>Point for the S. 1/16 sec. cor. of secs. 3 and 4, not monumented.</p>
40.80	<p>The 1/4 sec. cor. of secs. 3 and 4, monumented with brass cap, 3 ins. diam., in concrete, in a hand hole, 9 ins. below the surface of the highway, mkd. ARIZONA HWY DEPT. 19 ELEV + STA. This is accepted as the best available evidence of the orig. cor.</p>
	<p>from which</p> <p>A stainless steel post, 28 ins. long, 2 1/2 ins. diam., set 25 ins. in the ground for a reference monument, bears N. 45°00' E., 100.0 ft. dist., with brass cap mkd. RM T23N R6E 100.0 FT TO 1/4 COR S3 2014 and an arrow pointing to the cor. Deposit a magnet, in a white plastic case, at the base of the stainless steel post. Set a steel fence post, with attached USFS sign # 54-9, NE of cor.</p> <p>A stainless steel post, 28 ins. long, 2 1/2 ins. diam., set 28 ins. in the ground for a reference monument, bears N. 45°01' W., 100.0 ft. dist. with brass cap mkd. RM T23N R6E 100.0 FT TO 1/4 COR S4 2014 and an arrow pointing to the cor. Deposit a magnet, in a white plastic case, at the base of the stainless steel post. Set a steel fence post, with attached USFS sign # 54-9, NW of cor.</p> <p>The cor. is located in the center line of Arizona Highway No. 180, asphalt surfaced, 26 ft. wide, bears N. and S.</p> <p>The witness corner in the SW quadrant, set in 1943, found disturbed, laying horizontal. Remove from the field.</p> <hr/>



Subdivision of Section 3,  
T. 23 N., R. 6 E., Gila and Salt River Meridian, Arizona

CHAINS	
	<p>From the 1/4 sec. cor. of secs. 3 and 10.</p> <p>N. 0°28' W., on the N. and S. center line of sec. 3.</p>
20.287	Point for the center S. 1/16 sec. cor. of sec. 3, not monumented.
40.574	<p>Point for the center 1/4 sec. cor. of sec. 3, at the intersection with the E. and W. center line.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T 23 N R 6 E</p> <p style="text-align: center;">C 1/4 S 3</p> <p style="text-align: center;">2014</p> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p> <p>Set a steel fence post, with attached USFS sign # 54-9, W. of cor.</p>
81.312	<p>The 1/4 sec. cor. of secs. 3 and 34 on the N. bdy. of the Tp., monumented with an iron post, 1 in. diam., firmly set, 14 ins. below the surface of road, with brass cap mkd. 1/4 S34 S3 1943. Add the marks T24N R6E T23N 2014 to the brass cap, deposit a magnet, in a white plastic case, on top of the brass cap.</p> <p>from which the remaining witness corner set in 1943</p> <p style="padding-left: 40px;">An iron post, 1 in. diam., firmly set, leaning W., projecting 4 ins. above ground for a witness corner, bears N. 45° E., 65 lks. dist. with brass cap mkd. 1/4 S34 S3 WC 1943. Straighten the iron post, add the marks T24N R6E T23N 2014 to the brass cap. Witness corner is located 13.5 lks. E. of a fence corner, bears N. 45° E. and W.</p> <p>and a new reference monument</p> <p style="padding-left: 40px;">A stainless steel post, 28 ins. long, 2 1/2 ins. diam., set 24 ins. in the ground for a reference monument, bears S. 45°01' E., 100.0 ft. dist. with brass cap mkd. RM T23N R6E 100.0 FT TO 1/4 COR S3 2014 and an arrow pointing to the cor. Deposit a magnet, in a pink plastic case, at the base of the stainless steel post. Set a steel fence post, with attached USFS sign # 54-9, SE of cor.</p>

Subdivision of Section 3,  
T. 23 N., R. 6 E., Gila and Salt River Meridian, Arizona

CHAINS	
	<p>The cor. is located on Coconino County Road No. 514, graded road, 24 ft. wide, bears E. and W., and 1.50 chs. W. of the intersection with Condor Road, bears N., E. and W.</p> <hr/> <p>From the 1/4 sec. cor. of secs. 2 and 3, monumented with an iron post, 36 ins. long, 1 in. diam., filled with concrete, bent to the S., with brass cap mkd. 1/4 S3 S2 1943.</p> <p>At the corner point</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T 23 N R 6 E 1/4 S 3   S 2</p> <p style="text-align: center;">2014</p> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p> <p>Bury the iron post, horizontally alongside the stainless steel post.</p> <p>Raise a mound of stone, 3 ft. base, 2 ft. high, 1 lk. West of cor.</p> <p>Set a steel fence post, with attached USFS sign # 54-9, W. of cor.</p> <p>The cor. is located 47 lks. E. of a dirt road, 10.5 ft. wide, bears N. and S.</p> <p>N. 89°47' W., on the E. and W. center line of sec. 3.</p>
40.352	The center 1/4 sec. cor. of sec. 3.
60.656	Point for the center W. 1/16 sec. cor. of sec. 3, not monumented.
80.960	The 1/4 sec. cor. of secs. 3 and 4.
	<hr/> <p>SW 1/4</p> <hr/>
	<p>From the W. 1/16 sec. cor. of secs. 3 and 10.</p> <p>N. 0°31' W., on the N. and S. center line of the SW 1/4 of sec. 3.</p>

Subdivision of Section 3,  
T. 23 N., R. 6 E., Gila and Salt River Meridian, Arizona

CHAINS	
	On and across patented lands.
5.086	Point for the C-S-S-SW 1/256 sec. cor. of sec. 3, not monumented.
	Leaving patented lands.
20.343	Point for the SW 1/16 sec. cor. of sec. 3, at the intersection with the E. and W. center line of the SW 1/4, not monumented.
40.685	The center W. 1/16 sec. cor. of sec. 3.
	From the center S. 1/16 sec. cor. of sec. 3.
	N. 89°57' W., on the E. and W. center line of the SW 1/4 of sec. 3.
20.29	The SW 1/16 sec. cor. of sec. 3.
40.58	The S. 1/16 sec. cor. of secs. 3 and 4.
	From the W-E-W 1/256 sec. cor. of secs. 3 and 10.
	N. 0°30' W., on the N. and S. center line of the SW 1/4 of the SE 1/4 of the SW 1/4 of sec. 3.
4.75	Barbed wire fence, 4 strand, bears E. and W.
5.082	Point for the SW-SE-SW 1/256 sec. cor. of sec. 3.
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 25 ins. in the ground, with brass cap mkd.
	T 23 N R 6 E S 3 SW-SE-SW 1/256 2014
	from which
	A pine, 11 ins. diam., bears N. 55° E., 1.075 chs. dist., mkd. X at breast height and BT at base.
	A pine, 16 ins. diam., bears S. 37° E., 1.10 chs. dist., mkd. X at breast height and BT at base.
	Deposit a magnet, in a pink plastic case, at the base of the stainless steel post.

Subdivision of Section 3,  
T. 23 N., R. 6 E., Gila and Salt River Meridian, Arizona

CHAINS	
	<p>Set a steel fence post, with attached USFS signs # 54-2 and # 54-9, NE of cor.</p> <p>From this cor., a fence corner, barbed wire, 4 strands, bears S. 58°24' E., 64.5 lks. dist., with fences extending S. 5° E. and W.</p> <hr/> <p>S. 89°56' W., on the E. and W. center line of the SW 1/4 of the SE 1/4 of the SW 1/4 of sec. 3.</p>
5.07	<p>The C-S-S-SW 1/256 sec. cor. of sec. 3.</p> <hr/> <p>S. 89°56' W., on the E. and W. center line of the S. 1/2 of the SW 1/4 of the SW 1/4 of sec. 3.</p>
15.21	<p>Point for the SW-SW-SW 1/256 sec. cor. of sec. 3.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 28 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T 23 N R 6 E S 3 SW-SW-SW 1/256  2014</p> <p>from which</p> <p style="padding-left: 40px;">A pine, 20 ins. diam., bears S. 15° W., 1.275 chs. dist., mkd. X at breast height and BT at base.</p> <p style="padding-left: 40px;">A pine, 12 ins. diam., bears S. 75° W., 32.5 lks. dist., mkd. X at breast height and BT at base.</p> <p>Deposit a magnet, in a pink plastic case, at the base of the stainless steel post.</p> <p>Set a steel fence post, with attached USFS signs # 54-2 and # 54-9, SW of cor.</p>
20.28	<p>The S-S-S 1/256 sec. cor. of secs. 3 and 4.</p> <hr/> <p>From the W-W-W 1/256 sec. cor. of secs. 3 and 10.</p> <p>N. 0°32' W., on the N. and S. center line of the SW 1/4 of the SW 1/4 of the SW 1/4 of sec. 3.</p>
5.097	<p>The SW-SW-SW 1/256 sec. cor. of sec. 3.</p>

**Subdivision of Section 3,  
T. 23 N., R. 6 E., Gila and Salt River Meridian, Arizona**

CHAINS	
10.193	<p>Point for the C-W-SW-SW 1/256 sec. cor. of sec. 3.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T 23 N R 6 E S 3 C-W-SW-SW 1/256</p> <p style="text-align: center;">2014</p> <p>Deposit a magnet, in a pink plastic case, at the base of the stainless steel post.</p> <p>Set a steel fence post, with attached USFS signs # 54-2 and # 54-9, NE of cor.</p> <hr/> <p>S. 89°58' W., on the E. and W. center line of the SW 1/4 of the SW 1/4 of sec. 3.</p>
5.07	<p>The S-S 1/64 sec. cor. of secs. 3 and 4.</p> <hr/> <p style="text-align: center;"><b>Subdivision of Section 10, T. 23 N., R. 6 E., Gila and Salt River Meridian, Arizona</b></p> <hr/> <p>From the 1/4 sec. cor. of secs. 10 and 15, monumented with an iron post, 1 in. diam., firmly set, projecting 9 ins. above ground, with brass cap mkd. 1/4 S10 S15 1943.</p> <p>from which a new bearing tree</p> <p style="padding-left: 40px;">A pine, 16 ins. diam., bears S. 76° E., 1.455 chs. dist., mkd. X at breast height and BT at base.</p> <p>Add the marks T23N R6E 2014 to the brass cap.</p> <p>Set a steel fence post, with attached USFS sign 54-9, N. of cor.</p> <p>N. 0°15' E., on the N. and S. center line of sec. 10.</p>
40.377	<p>Point for the center 1/4 sec. cor. of sec. 10, at the intersection with the E. and W. center line.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with brass cap mkd.</p>

Subdivision of Section 10,  
T. 23 N., R. 6 E., Gila and Salt River Meridian, Arizona

CHAINS	
	T 23 N R 6 E C 1/4 S 10 2014
	from which
	A pine, 16 ins. diam., bears S. 76 3/4° E., 1.965 chs. dist., mkd. X at breast height and BT at base.
	A pine, 14 ins. diam., bears S. 34° E., 2.195 chs. dist., mkd. T23N R6E C1/4 S10 BT.
	Deposit a magnet, in a pink plastic case, at the base of the stainless steel post.
	Set a steel fence post, with attached USFS sign # 54-9, N. of cor.
44.94	U.S. Forest Service Route 151, graded road, 18 ft. wide, bears S. 80° E. and N. 80° W.
60.345	Point for the center N. 1/16 sec. cor. of sec. 10, not monumented.
80.313	The 1/4 sec. cor. of secs. 3 and 10.
	<hr/>
	From the 1/4 sec. cor. of secs. 10 and 11, monumented with an iron post, 36 ins. long, 1 in. diam., filled with concrete, bent to the S., with brass cap mkd. 1/4 S10 S11 1943.
	At the corner point
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with brass cap mkd.
	T 23 N R 6 E 1/4 S 10   S 11 2014
	from which new bearing trees
	A pine, 10 ins. diam., bears N. 73° E., 63 lks. dist., mkd. X BT at base.
	A pine, 27 ins. diam., bears N. 9° W., 1.40 chs. dist., mkd. 1/4 S10 BT.

Subdivision of Section 10,  
T. 23 N., R. 6 E., Gila and Salt River Meridian, Arizona

CHAINS	
	<p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p> <p>Remove the iron post from the field.</p> <p>Set a steel fence post, with attached USFS sign # 54-9, W. of cor.</p> <p>N. 89°39' W., on the E. and W. center line of sec. 10.</p>
40.059	The center 1/4 sec. cor. of sec. 10.
59.933	Point for the center W. 1/16 sec. cor. of sec. 10, not monumented.
79.807	The 1/4 sec. cor. of secs. 9 and 10.
	<hr/> NW 1/4 <hr/>
	<p>From the center W. 1/16 sec. cor. of sec. 10.</p> <p>N. 0°20' W., on the N. and S. center line of the NW 1/4 of sec. 10.</p>
19.888	<p>Point for the NW 1/16 sec. cor. of sec. 10, at the intersection with the E. and W. center line of the NW 1/4.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 28 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T 23 N R 6 E</p> <p style="text-align: center;">NW 1/16 S 10</p> <p style="text-align: center;">2014</p> <p>from which</p> <p style="padding-left: 40px;">A pine, 15 ins. diam., bears S. 15° E., 4.5 lks. dist., mkd. X at breast height and BT at base.</p> <p style="padding-left: 40px;">A pine, 16 ins. diam., bears S. 55° W., 1.165 chs. dist., mkd. X at breast height and BT at base.</p> <p>Deposit a magnet, in a pink plastic case, at the base of the stainless steel post.</p> <p>Set a steel fence post, with attached USFS signs # 54-2 and # 54-9, SE of cor.</p>

Subdivision of Section 10,  
T. 23 N., R. 6 E., Gila and Salt River Meridian, Arizona

CHAINS	
	The cor. is located 22 lks. N. of a fence, barbed wire, 5 strand, bears E. and W., and N. 40 1/2° W., 28.5 lks. dist. from the terminus of the same fence, bears W., and S. 67 1/2° W., 42 lks. dist. from the terminus of a downed fence, barbed wire, bears N. 5° E.
29.52	Barbed wire fence, bears N. 85° E. and S. 85° W.
29.834	Point for the C-N-NW 1/64 sec. cor. of sec. 10.  Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 27 ins. in the ground, with brass cap mkd.  <div style="text-align: center;">T 23 N R 6 E S 10 C-N-NW 1/64  2014</div> <p>from which</p> <p style="margin-left: 40px;">A pine, 31 ins. diam., bears S. 73° E., 4.05 chs. dist., mkd. X at breast height and BT at base.</p> <p style="margin-left: 40px;">A pine, 22 ins. diam., bears S. 30° E., 1.545 chs. dist., mkd. X at breast height and BT at base.</p> <p>Deposit a magnet, in a pink plastic case, at the base of the stainless steel post.</p> <p>Set a steel fence post, with attached USFS signs # 54-2 and # 54-9, SE of cor.</p> <p>From this cor., a fence corner, bears S. 65°27' E., 77 lks. dist., with barbed wire fences extending N. 85° E., S. and S. 85° W.</p> <p>Entering patented lands.</p>
39.776	The W. 1/16 sec. cor. of secs. 3 and 10. <hr/> From the center N. 1/16 sec. cor. of sec. 10.  N. 89°53' W., on the E. and W. center line of the NW 1/4 of sec. 10.
20.074	The NW 1/16 sec. cor. of sec. 10.
30.112	Point for the C-W-NW 1/64 sec. cor. of sec. 10.



Subdivision of Section 10,  
T. 23 N., R. 6 E., Gila and Salt River Meridian, Arizona

CHAINS	
	<p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 13 ins. in the ground to bedrock, in a mound of stone, 3 1/2 ft. base, to top, with brass cap mkd.</p> <p style="text-align: center;">T 23 N R 6 E S 10 C-W-NW 1/64  2014</p> <p>from which</p> <p style="padding-left: 40px;">A pine, 19 ins. diam., bears S. 50° E., 64 lks. dist., mkd. X at breast height and BT at base.</p> <p style="padding-left: 40px;">A pine, 11 ins. diam., bears S. 35° W., 71 lks. dist., mkd. X at breast height and BT at base.</p> <p>Deposit a magnet, in a pink plastic case, at the base of the stainless steel post.</p> <p>Set a steel fence post, with attached USFS signs # 54-2 and # 54-9, SW of cor.</p> <p>The cor. is located 32 lks. N. of a barbed wired fence, 4 strand, bears E. and W., and 47.5 lks. W. of a barbed wire fence, 4 strand, bears N. and S.</p>
40.150	<p>The N. 1/16 sec. cor. of secs. 9 and 10.</p> <hr/> <p>From the C-N-NW 1/64 sec. cor. of sec. 10.</p> <p>S. 89°59' E., on the E. and W. center line of the NE 1/4 of the NW 1/4 of sec. 10.</p>
10.09	<p>Point for the NE-NW 1/64 sec. cor. of sec. 10.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 27 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T 23 N R 6 E S 10 NE-NW 1/64  2014</p> <p>from which</p> <p style="padding-left: 40px;">A double pine, 16 ins. diam., bears N. 30° E., 1.295 chs. dist., mkd. X at breast height and BT at base.</p>

Subdivision of Section 10,  
T. 23 N., R. 6 E., Gila and Salt River Meridian, Arizona

CHAINS	
	<p>A pine, 18 ins. diam., bears S. 65° E., 1.56 chs. dist., mkd. X at breast height and BT at base.</p> <p>Deposit a magnet, in a pink plastic case, at the base of the stainless steel post.</p> <p>Set a steel fence post, with attached USFS signs # 54-2 and # 54-9, SE of cor.</p> <p>From this cor., a fence corner, bears S. 47°38' E., 69 lks. dist., with barbed wire fences extending S. 85° W. and N. 10° W.</p> <hr/> <p>N. 0°02' W., on the N. and S. center line of the NE 1/4 of the NW 1/4 of sec. 10.</p>
4.98	<p>Point for the C-N-NE-NW 1/256 sec. cor. of sec. 10.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T 23 N R 6 E S 10 C-N-NE-NW 1/256  2014</p> <p>from which</p> <p>A pine, 12 ins. diam., bears N. 52° E., 1.29 chs. dist., mkd. X at breast height and BT at base.</p> <p>A pine, 11 ins. diam., bears S. 45° E., 1.335 chs. dist., mkd. X at breast height and BT at base.</p> <p>Deposit a magnet, in a pink plastic case, at the base of the stainless steel post.</p> <p>Set a steel fence post, with attached USFS signs # 54-2 and # 54-9, NE of cor.</p> <p>The cor. is located 49 lks. W. of a barbed wire fence, 4 strand, bears N. and S.</p> <hr/> <p>S. 89°57' W., on the E. and W. center line of the NW 1/4 of the NE 1/4 of the NW 1/4 of sec. 10.</p>
5.06	<p>Point for the NW-NE-NW 1/256 sec. cor. of sec. 10.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with brass cap mkd.</p>

Subdivision of Section 10,  
T. 23 N., R. 6 E., Gila and Salt River Meridian, Arizona

CHAINS	
	T 23 N R 6 E S 10 NW-NE-NW 1/256  2014
	from which  A pine, 18 ins. diam., bears N. 25° E., 1.24 chs. dist., mkd. X at breast height and BT at base.  A pine, 14 ins. diam., bears N. 65° E., 1.46 chs. dist., mkd. X at breast height and BT at base.  Deposit a magnet, in a pink plastic case, at the base of the stainless steel post.  Set a steel fence post, with attached USFS signs # 54-2 and # 54-9, NE of cor.
4.98	<hr/> N. 0°11' W., on the N. and S. center line of the NW 1/4 of the NE 1/4 of the NW 1/4 of sec. 10.  The W-E-W 1/256 sec. cor. of secs 3 and 10.
14.89	<hr/> From the C-W-NW 1/64 sec. cor. of sec. 10.  N. 0°38' W., on the N. and S. center line of the NW 1/4 of the NW 1/4 of sec. 10.  Point for the C-N-NW-NW 1/256 sec. cor. of sec. 10.  Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.
	T 23 N R 6 E S 10 C-N-NW-NW 1/256  2014
	from which  A pine, 16 ins. diam., bears S. 30° W., 77 lks. dist., mkd. X at breast height and BT at base.  A pine, 22 ins. diam., bears S. 63° W., 1.59 chs. dist., mkd. X at breast height and BT at base.

Subdivision of Section 10,  
T. 23 N., R. 6 E., Gila and Salt River Meridian, Arizona

CHAINS	
5.06	<p>Deposit a magnet, in a pink plastic case, at the base of the stainless steel post.</p> <p>Set a steel fence post, with attached USFS signs # 54-2 and # 54-9, SW of cor.</p> <hr/> <p>S. 89°57' W., on the E. and W. center line of the NW 1/4 of the NW 1/4 of the NW 1/4 of sec. 10.</p> <p>Point for the NW-NW-NW 1/256 sec. cor. of sec. 10.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T 23 N R 6 E S 10 NW-NW-NW 1/256  2014</p> <p>from which</p> <p style="padding-left: 40px;">A pine, 8 ins. diam., bears S. 60° W., 1.22 chs. dist., mkd. X at breast height and BT at base.</p> <p style="padding-left: 40px;">A pine, 15 ins. diam., bears N. 45° W., 43 lks. dist., mkd. X at breast height and BT at base.</p> <p>Deposit a magnet, in a pink plastic case, at the base of the stainless steel post.</p> <p>Set a steel fence post, with attached USFS signs # 54-2 and # 54-9, SW of cor.</p> <hr/> <p>N. 0°47' W., on the N. and S. center line of the NW 1/4 of the NW 1/4 of the NW 1/4 of sec. 10.</p>
4.96	<p>The W-W-W 1/256 sec. cor. of secs. 3 and 10.</p> <hr/> <p style="text-align: center;">Subdivision of Section 13, T. 23 N., R. 6 E., Gila and Salt River Meridian, Arizona</p> <hr/> <p>From the 1/4 sec. cor. of secs. 13 and 24, monumented with an iron post, 1 in. diam., firmly set, projecting 4 ins. above ground, with brass cap mkd. 1/4 S13 S24 1943.</p> <p>from which the bearing trees mkd. in 1943</p>

Subdivision of Section 13,  
T. 23 N., R. 6 E., Gila and Salt River Meridian, Arizona

CHAINS	
	<p>A pine, 22 ins. diam., bears N. 10 1/4° E., 83 lks. dist., with no marks visible.</p> <p>A pine, 17 ins. diam., bears S. 71 1/4° E., 2.32 chs. dist., with scribe marks 1/4 S24 BT visible on partially open blaze.</p> <p>Add the marks T23N R6E 2014 to the brass cap.</p> <p>Set a steel fence post, with attached USFS sign # 54-9, N. of cor.</p> <p>N. 0°47' W., on the N. and S. center line of sec. 13.</p>
38.77	<p>The center 1/4 sec. cor. of sec. 13, established by Charles C. Doak, USFS Regional Land Surveyor, Southwest Region, Arizona R.L.S. No. 4476, in 1972, according to the plat titled "PLAT OF RIGHT OF WAY SURVEY ROAD NO. 4418B &amp; 4418.1 AND PARTIAL SUBDIVISION OF SECTION 13 A PORTION OF THE COCONINO NATIONAL FOREST PROPERTY LINE Situated in T. 23 N., R. 6 E.", on file with the Forest Land Surveyor at the headquarters of Coconino National Forest, monumented with an iron post, 2 1/2 ins. diam., firmly set, projecting 9 ins. above ground, with brass cap mkd. S13 C 1/4 LS 4476 1972. This is accepted as a careful and faithful determination of the cor. position.</p> <p>from which the bearing trees marked by Charles C. Doak in 1972</p> <p>A pine, 10 ins. diam., bears N. 18° E., 6 lks. dist., with 2 healed blaze and USFS sign 54-4.</p> <p>A pine, 16 ins. diam., bears N. 76° W., 19 lks. dist., with a healed blaze.</p> <hr style="width: 20%; margin: 10px auto;"/> <p>N. 0°47' W., beginning new measurement.</p>
14.95	<p>The C-N-S-N 1/256 sec. cor. of sec. 13, established by Charles C. Doak, USFS Regional Land Surveyor, Southwest Region, Arizona R.L.S. No. 4476, in 1972, according to the plat titled "PLAT OF RIGHT OF WAY SURVEY ROAD NO. 4418B &amp; 4418.1 AND PARTIAL SUBDIVISION OF SECTION 13 A PORTION OF THE COCONINO NATIONAL FOREST PROPERTY LINE Situated in T. 23 N., R. 6 E.", on file with the Forest Land Surveyor at the headquarters of Coconino National Forest, monumented with an iron post, 2 1/2 ins. diam., firmly set, projecting 12 ins. above ground, in a mound of stone, 1 1/2 ft. base, 6 ins. high, with brass cap mkd. S13 C-N-S-N 1/256 LS 4476 1972. This is accepted as a careful and faithful establishment of the cor. position.</p> <p>from which the bearing trees marked by Charles C. Doak in 1972</p>

Subdivision of Section 13,  
T. 23 N., R. 6 E., Gila and Salt River Meridian, Arizona

CHAINS	
	<p>A pine, 15 ins. diam., bears S. 38° E., 14 lks. dist., with a healed blaze, 1 BT tag and 1 USFS sign # 54-4.</p> <p>A fir, 18 ins. diam., bears S. 22° W., 19.7 lks. dist., with a healed blaze, 1 BT tag and 1 USFS sign form 1505.</p> <p>Set a steel fence post, with attached USFS sign # 54-9, W. of cor.</p>
19.93	<p>Point for the center N. 1/16 sec. cor. of sec. 13.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 23 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center;"> <p>T 23 N R 6 E</p> <p>    C</p> <p>N 1/16   S 13</p> <p>    C</p> <p>2014</p> </div> <p>from which</p> <p>A pine, 11 ins. diam., bears N. 15° E., 70 lks. dist., mkd. X at breast height and BT at base.</p> <p>A pine, 15 ins. diam., bears N. 85° W., 59.5 lks. dist., mkd. X at breast height and BT at base.</p> <p>Deposit a magnet, in a clear plastic case, at the base of the stainless steel post.</p> <p>Set a steel fence post, with attached USFS sign # 54-9, W. of cor.</p>
34.87	<p>The C-N-N-N 1/256 sec. cor. of sec. 13, established by Charles C. Doak, USFS Regional Land Surveyor, Southwest Region, Arizona R.L.S. No. 4476, in 1972, according to the plat titled "PLAT OF RIGHT OF WAY SURVEY ROAD NO. 4418B &amp; 4418.1 AND PARTIAL SUBDIVISION OF SECTION 13 A PORTION OF THE COCONINO NATIONAL FOREST PROPERTY LINE Situated in T. 23 N., R. 6 E.", on file with the Forest Land Surveyor at the headquarters of Coconino National Forest, monumented with an iron post, 2 1/2 ins. diam., firmly set, projecting 6 ins. above ground, with brass cap mkd. C-N-N-N 1/256 S13 LS 4476 1972. This is accepted as a careful and faithful establishment of the cor. position.</p> <p>from which the bearing trees marked by Charles C. Doak in 1972</p> <p>A pine, 24 ins. diam., bears N. 73° E., 27.5 lks. dist., with a healed blaze and 1 BT tag.</p>

Subdivision of Section 13,  
T. 23 N., R. 6 E., Gila and Salt River Meridian, Arizona

CHAINS	<p>A pine, 16 ins. diam., bears N. 6° W., 41 lks. dist., with a healed blaze.</p> <p>Set a steel fence post, with attached USFS sign # 54-9, N. of cor.</p> <p>From this cor., an iron post, 2 1/2 ins. diam., firmly set, projecting 4 ins. above ground, with brass cap mkd. ROAD 4418B STA 1+62.86 LS 4476 1972, bears N. 89°39' W., 1.117 chs. dist., with a steel fence post W. of cor., set a steel fence post with attached USFS sign # 54-9, N. of cor.</p>
39.86	<p>The 1/4 sec. cor. of secs. 12 and 13.</p> <hr/> <p>From the 1/4 sec. cor. of secs. 13 and 18, on the E. bdy. of the Tp.</p> <p>N. 89°33' W., on the E. and W. center line of sec. 13.</p>
19.62	<p>Point for the center E. 1/16 sec. cor. of sec. 13.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 22 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center; margin: 10px 0;"> <p>T 23 N R 6 E</p> <p>E 1/16</p> <p>C ——— C</p> <p>S 13</p> <p>2014</p> </div> <p>from which</p> <p>A pine, 15 ins. diam., bears East, 15 lks. dist., mkd. X at breast height and BT at base.</p> <p>A pine, 21 ins. diam., bears S. 15° W., 40 lks. dist., mkd. X at breast height and BT at base.</p> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p> <p>Set a steel fence post, with attached USFS sign # 54-9, S. of cor.</p>
39.24	<p>The center 1/4 sec. cor. of sec. 13.</p> <hr/> <p>N. 89°33' W., beginning new measurement.</p>

Subdivision of Section 13,  
T. 23 N., R. 6 E., Gila and Salt River Meridian, Arizona

CHAINS	
40.33	<p>The 1/4 sec. cor. of secs. 13 and 14, monumented with an iron post, 1 in. diam., firmly set, projecting 2 ins. above ground, with brass cap mkd. 1/4 S14 S13 1985 1943.</p> <p>from which the remaining bearing trees mkd. in 1943</p> <p style="padding-left: 40px;">A stump hole, 16 ins. diam., bears S. 35 1/2° E., 1.12 chs. dist.</p> <p style="padding-left: 40px;">A white pine, 20 ins. diam., bears S. 56 1/2° W., 44 lks. dist., with a healed blaze and 2 BT tags.</p> <p>and bearing tree mkd. in 1985</p> <p style="padding-left: 40px;">A ponderosa pine, 16 ins. diam., bears N. 51 3/4° E., 35.5 lks. dist., with a healed blaze and 2 BT tags.</p> <p>Add the marks T23N R6E 2014 to the brass cap.</p> <p>Set a steel fence post, with attached USFS sign # 54-9, E. of cor.</p> <p>The cor. is located along a downed fence corner, barbed wire, bears N. and W.</p> <hr style="width: 60%; margin: 20px auto;"/> <p style="text-align: center;">NE 1/4</p> <hr style="width: 60%; margin: 20px auto;"/> <p>From the center E. 1/16 sec. cor. of sec. 13.</p> <p>N. 0°19' W., on the N. and S. center line of the NE 1/4 of sec. 13.</p>
14.975	<p>Point for the C-N-S-NE 1/256 sec. cor. of sec. 13, not monumented.</p> <p>Entering patented lands.</p>
19.967	<p>Point for the NE 1/16 sec. cor. of sec. 13, at the intersection with the E. and W. center line of the NE 1/4, not monumented.</p>
29.950	<p>Point for the C-N-NE 1/64 sec. cor. of sec. 13, not monumented.</p> <p>Leaving patented lands.</p>
39.933	<p>The E. 1/16 sec. cor. of secs. 12 and 13.</p> <hr style="width: 60%; margin: 20px auto;"/> <p>From the N. 1/16 sec. cor. of secs. 13 and 18, on the E. bdy. of the Tp.</p>



Subdivision of Section 13,  
T. 23 N., R. 6 E., Gila and Salt River Meridian, Arizona

CHAINS	
4.947	<p>N. 89°40' W., on the E. and W. center line of the NE 1/4 of sec. 13.</p> <p>The C-E-E-NE 1/256 sec. cor. of sec. 13, established by Charles C. Doak, USFS Regional Land Surveyor, Southwest Region, Arizona R.L.S. No. 4476, in 1972, according to the plat titled "PLAT OF RIGHT OF WAY SURVEY ROAD NO. 4418B &amp; 4418.1 AND PARTIAL SUBDIVISION OF SECTION 13 A PORTION OF THE COCONINO NATIONAL FOREST PROPERTY LINE Situated in T. 23 N., R. 6 E.", on file with the Forest Land Surveyor at the headquarters of Coconino National Forest, monumented with an iron post, 2 1/2 ins. diam., firmly set, projecting 10 ins. above ground, in a mound of stone, 2 ft. base, to top of brass cap mkd. S13 C-E-E-NE 1/256 LS 4476 1972. This is accepted as a careful and faithful establishment of the cor. position.</p> <p>from which the bearing trees marked by Charles C. Doak in 1972</p> <p style="padding-left: 40px;">A pine, 14 ins. diam., bears N. 28° E., 19.5 lks. dist., with scribe marks NE visible on partially open blaze and 1 BT tag.</p> <p style="padding-left: 40px;">A pine, 18 ins. diam., bears S. 28° E., 11 lks. dist., with a healed blaze, 1 BT tag and 1 USFS sign # 54-4.</p> <p>Set a steel fence post, with attached USFS signs # 54-2 and # 54-9, SE. of cor.</p> <p>The cor. is located 5.5 lks. S. of a downed fence corner, barbed wire, with fences extending N. and W.</p> <hr style="width: 20%; margin: 10px auto;"/> <p>N. 89°40' W., beginning new measurement.</p>
4.946	<p>The C-E-NE 1/64 sec. cor. of sec. 13, established by Charles C. Doak, USFS Regional Land Surveyor, Southwest Region, Arizona R.L.S. No. 4476, in 1972, according to the plat titled "PLAT OF RIGHT OF WAY SURVEY ROAD NO. 4418B &amp; 4418.1 AND PARTIAL SUBDIVISION OF SECTION 13 A PORTION OF THE COCONINO NATIONAL FOREST PROPERTY LINE Situated in T. 23 N., R. 6 E.", on file with the Forest Land Surveyor at the headquarters of Coconino National Forest, monumented with an iron post, 2 1/2 ins. diam., firmly set, projecting 4 ins. above ground, with brass cap mkd. S13 C-E-NE 1/64 LS 4476 1972. This is accepted as a careful and faithful establishment of the cor. position.</p> <p>from which the bearing trees marked by Charles C. Doak in 1972</p> <p style="padding-left: 40px;">A pine, 18 ins. diam., bears S. 67° E., 9 lks. dist., with a healed blaze.</p> <p style="padding-left: 40px;">A pine, 16 ins. diam., bears S. 11° W., 14.5 lks. dist., with a healed blaze, 1 BT tag and 1 USFS sign # 54-4.</p>

Subdivision of Section 13,  
T. 23 N., R. 6 E., Gila and Salt River Meridian, Arizona

CHAINS	
	<p>Set a steel fence post, with attached USFS signs # 54-2 and # 54-9, SE. of cor.</p> <p>The cor. is located 1.5 lks. W. of a downed fence corner, barbed wire, with fences extending E. and S.</p> <hr style="width: 20%; margin: 10px auto;"/> <p>N. 89°40' W., beginning new measurement.</p> <p>Entering patented lands.</p>
9.89	The NE 1/16 sec. cor. of sec. 13.
19.78	Point for the C-W-NE 1/64 sec. cor. of sec. 13, not monumented.
	Leaving patented lands.
29.67	The center N. 1/16 sec. cor. of sec. 13.
	<hr style="width: 80%; margin: 10px auto;"/> <p>From the N-N 1/64 sec. cor. of secs. 13 and 18, on the E. bdy. of the Tp.</p> <p>N. 89°44' W., on the E. and W. center line of the NE 1/4 of the NE 1/4 of sec. 13.</p>
1.375	<p>An iron post, 2 1/2 ins. diam., firmly set, projecting 6 ins. above ground, with brass cap mkd. ROAD 4418.1 STA 18+14.49 LS 4476 1972, established by Charles C. Doak, USFS Regional Land Surveyor, Southwest Region, Arizona R.L.S. No. 4476, in 1972, according to the plat titled "PLAT OF RIGHT OF WAY SURVEY ROAD NO. 4418B &amp; 4418.1 AND PARTIAL SUBDIVISION OF SECTION 13 A PORTION OF THE COCONINO NATIONAL FOREST PROPERTY LINE Situated in T. 23 N., R. 6 E.", on file with the Forest Land Surveyor at the headquarters of Coconino National Forest. Set a steel fence post, with attached USFS signs # 54-2 and # 54-9, E. of cor.</p>
11.34	A rebar, 1/2 in. diam., firmly set, projecting 3 ins. above ground, with brass washer, 1 1/2 ins. diam., with no marks, bears North, 1 lk. dist.
13.15	A rebar, 1/2 in. diam., firmly set, projecting 2 ins. above ground, with plastic cap, 2 ins. diam., mkd. LS 18548 DO NOT DISTURB 928-526-0270 MARTIN LAND SURVEYS, established by Martin H. Martin, Arizona R.L.S. No. 18548, in 2014, according to Instrument # 3695303 on file at Coconino County Recorder's Office.
19.86	The C-N-NE 1/64 sec. cor. of sec. 13.
	<hr style="width: 80%; margin: 10px auto;"/> <p>From the C-E-E-NE 1/256 sec. cor. of sec. 13.</p>

Subdivision of Section 13,  
T. 23 N., R. 6 E., Gila and Salt River Meridian, Arizona

CHAINS	
	<p>N. 0°01' W., on the N. and S. center line of SE 1/4 of the NE 1/4 of the NE 1/4 of sec. 13.</p>
5.00	<p>The SE-NE-NE 1/256 sec. cor. of sec. 13, established by Charles C. Doak, USFS Regional Land Surveyor, Southwest Region, Arizona R.L.S. No. 4476, in 1972, according to the plat titled "PLAT OF RIGHT OF WAY SURVEY ROAD NO. 4418B &amp; 4418.1 AND PARTIAL SUBDIVISION OF SECTION 13 A PORTION OF THE COCONINO NATIONAL FOREST PROPERTY LINE Situated in T. 23 N., R. 6 E.", on file with the Forest Land Surveyor at the headquarters of Coconino National Forest, monumented with an iron post, 2 1/2 ins. diam., firmly set, projecting 12 ins. above ground, with brass cap mkd. S13 SE-NE-NE 1/256 LS 4476 1972. This is accepted as a careful and faithful establishment of the cor. position.</p> <p>from which the bearing trees marked by Charles C. Doak in 1972</p> <p style="padding-left: 40px;">A pine, 18 ins. diam., bears S. 62° E., 12.5 lks. dist., with a healed blaze, 1 BT tag and 1 USFS sign # 54-4.</p> <p style="padding-left: 40px;">A pine, 19 ins. diam., bears S. 27° E., 38 lks. dist., with a healed blaze and 1 BT tag.</p> <p>Set a steel fence post, with attached USFS signs # 54-2 and # 54-9, SE of cor.</p> <p>The cor. is located alongside of a downed fence corner, barbed wire, bears E. and S.</p> <hr/> <p>S. 89°41' E., on the E. and W. center line of SE 1/4 of the NE 1/4 of the NE 1/4 of sec. 13.</p>
4.96	<p>The S-N-N 1/256 sec. cor. of secs. 13 and 18, on the E. bdy. of the Tp.</p> <hr/> <p>From the C-N-S-NE 1/256 sec. cor. of sec. 13.</p> <p>S. 89°38' E., on the E. and W. center line of the NW 1/4 of the SE 1/4 of the NE 1/4 of sec. 13.</p>
6.618	<p>A rebar, 1/2 in. diam., firmly set, projecting 2 ins. above ground, with plastic cap, 2 ins. diam., mkd. LS 18548 DO NOT DISTURB 928-526-0270 MARTIN LAND SURVEYS, established by Martin H. Martin, Arizona R.L.S. No. 18548, in 2014, according to Instrument # 3695303, on file at Coconino County Recorder's Office.</p>

Subdivision of Section 13,  
T. 23 N., R. 6 E., Gila and Salt River Meridian, Arizona

CHAINS	
9.876	<p>The C-N-SE-NE 1/256 sec. cor. of sec. 13, established by Charles C. Doak, USFS Regional Land Surveyor, Southwest Region, Arizona R.L.S. No. 4476, in 1972, according to the plat titled "PLAT OF RIGHT OF WAY SURVEY ROAD NO. 4418B &amp; 4418.1 AND PARTIAL SUBDIVISION OF SECTION 13 A PORTION OF THE COCONINO NATIONAL FOREST PROPERTY LINE Situated in T. 23 N., R. 6 E.", on file with the Forest Land Surveyor at the headquarters of Coconino National Forest, monumented with an iron post, 2 1/2 ins. diam., firmly set, projecting 4 ins. above ground, with brass cap mkd. S13 C-N-SE-NE 1/256 LS 4476 1972. This is accepted as a careful and faithful establishment of the cor. position.</p> <p>from which the bearing trees marked by Charles C. Doak in 1972</p> <p style="padding-left: 40px;">A pine, 17 ins. diam., bears N. 15° E., 30.5 lks. dist., with a healed blaze, 1 BT tag and 1 USFS sign # 54-4.</p> <p style="padding-left: 40px;">A pine, 20 ins. diam., bears S. 75° E., 11 lks. dist., with a healed blaze and 1 BT tag.</p> <p>Set a steel fence post, with attached USFS signs # 54-2 and # 54-9, SE of cor.</p> <p>The cor. is located alongside of a downed fence corner, barbed wire, bears N. and W.</p> <hr/> <p>N. 0°08' W., on the N. and S. center line of the SE 1/4 of the NE 1/4 of sec. 13.</p>
4.995	<p>The C-E-NE 1/64 sec. cor. of sec. 13.</p> <hr/> <p>From the C-N-S-NE 1/256 sec. cor. of sec. 13.</p> <p>N. 89°38' W., on the E. and W. center line of NE 1/4 of the SW 1/4 of the NE 1/4 of sec. 13.</p>
0.088	<p>An iron post, 2 1/2 ins. diam., firmly set, projecting 6 ins. above ground, with brass cap mkd. ROAD 4418.1 STA 0+52.74 LS 4476 1972, established by Charles C. Doak, USFS Regional Land Surveyor, Southwest Region, Arizona R.L.S. No. 4476, in 1972, according to the plat titled "PLAT OF RIGHT OF WAY SURVEY ROAD NO. 4418B &amp; 4418.1 AND PARTIAL SUBDIVISION OF SECTION 13 A PORTION OF THE COCONINO NATIONAL FOREST PROPERTY LINE Situated in T. 23 N., R. 6 E.", on file with the Forest Land Surveyor at the headquarters of Coconino National Forest. Set a steel fence post, with attached USFS signs # 54-2 and # 54-9, W. of cor. This cor. is located alongside a barbed wire fence, 5 strand, bears E. and W.</p>

Subdivision of Section 13,  
T. 23 N., R. 6 E., Gila and Salt River Meridian, Arizona

CHAINS	
1.369	<p>An iron post, 2 1/2 ins. diam., firmly set, projecting 4 ins. above ground, with brass cap mkd. ROAD 4418.1 STA 0+00.00 LS 4476 1972, established by Charles C. Doak, USFS Regional Land Surveyor, Southwest Region, Arizona R.L.S. No. 4476, in 1972, according to the plat titled "PLAT OF RIGHT OF WAY SURVEY ROAD NO. 4418B &amp; 4418.1 AND PARTIAL SUBDIVISION OF SECTION 13 A PORTION OF THE COCONINO NATIONAL FOREST PROPERTY LINE Situated in T. 23 N., R. 6 E.", on file with the Forest Land Surveyor at the headquarters of Coconino National Forest.</p> <p>From this cor., a rebar, 1/2 in. diam., firmly set, projecting 2 ins. above ground, with plastic cap, 2 ins. diam., mkd. LS 18548 DO NOT DISTURB 928-526-0270 MARTIN LAND SURVEYS, bears Westerly, 13.5 lks. dist. This rebar is located at the S. edge of a pine tree, 15 ins. diam.</p>
9.86	<p>The C-N-SW-NE 1/256 sec. cor. of sec. 13, established by Christopher J. Franks, Arizona R.L.S. No. 22258, date unknown, and accepted by Martin H. Martin, Arizona R.L.S. No. 18548 in 2014, according to Instrument # 3695303, on file at Coconino County Recorder's Office, monumented with a rebar, 1/2 in. diam., 24 ins. long, firmly set, projecting 13 ins. above ground, with plastic cap, 1 in. diam., mkd. C J F LS 22258. This is accepted as careful and faithful establishment of the cor. position.</p> <p>At the corner point</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T 23 N R 6 E S 13 C-N-SW-NE 1/256  2014</p> <p>from which</p> <p style="padding-left: 40px;">A pine, 13 ins. diam., bears S. 28° W., 69 lks. dist., mkd. X at breast height and BT at base.</p> <p style="padding-left: 40px;">A pine, 14 ins. diam., bears N. 50° W., 46 lks. dist., mkd. X at breast height and BT at base.</p> <p>Deposit a magnet, in a clear plastic case, at the base of the stainless steel post.</p> <p>Deposit the rebar with plastic cap inside the stainless steel post.</p>

Subdivision of Section 13,  
T. 23 N., R. 6 E., Gila and Salt River Meridian, Arizona

CHAINS	
	<p>Set a steel fence post, with attached USFS signs # 54-2 and # 54-9, SW of cor.</p> <hr/> <p>N. 0°36' W., on the N. and S. center line of the SW 1/4 of the NE 1/4 of sec. 13.</p>
4.98	<p>The C-W-NE 1/64 sec. cor. of sec. 13.</p> <hr/> <p>N. 0°36' W., on the N. and S. center line of the NW 1/4 of the NE 1/4 of sec. 13.</p>
9.97	<p>The NW-NE 1/64 sec. cor. of sec. 13, established by Charles C. Doak, USFS Regional Land Surveyor, Southwest Region, Arizona R.L.S. No. 4476, in 1972, according to the plat titled "PLAT OF RIGHT OF WAY SURVEY ROAD NO. 4418B &amp; 4418.1 AND PARTIAL SUBDIVISION OF SECTION 13 A PORTION OF THE COCONINO NATIONAL FOREST PROPERTY LINE Situated in T. 23 N., R. 6 E.", on file with the Forest Land Surveyor at the headquarters of Coconino National Forest, monumented with an iron post, 2 1/2 ins. diam., firmly set, flush with the surface of the road and leaning W., with brass cap missing. This is accepted as a careful and faithful establishment of the cor. position. This cor. is located in Shank Flat Road (FS No. 4418B), a graded road, 12 ft. wide, bears S. 85° E. and S. 85° W.</p> <p>from which the bearing trees marked by Charles C. Doak in 1972</p> <p style="padding-left: 40px;">A stump hole, 15 ins. diam., bears N. 2° E., 67.5 lks. dist., with a downed tree alongside, with scribe marks NE 1/64 BT visible on partially open blaze and 1 BT tag. Set a steel fence post, with attached BT tag, at the center of the stump hole.</p> <p style="padding-left: 40px;">A dead tree, 15 ins. diam., bears N. 25° E., 40 lks. dist., with a healed blaze.</p> <p>and new reference monuments</p> <p style="padding-left: 40px;">A stainless steel post, 28 ins. long, 2 1/2 ins. diam., set 28 ins. in the ground for a reference monument, bears S. 56°07' W., 31.8 ft. dist. with brass cap mkd. RM T23N R6E S13 31.8 FT TO NW-NE 1/64 COR 2014 and an arrow pointing to the cor. Deposit a magnet, in a clear plastic case, at the base of the stainless steel post. Set a steel fence post, with attached USFS sign # 54-9, SW of cor.</p>

**Subdivision of Section 13,  
T. 23 N., R. 6 E., Gila and Salt River Meridian, Arizona**

CHAINS	
	<p>An iron post, 2 1/2 ins. diam., firmly set, projecting 8 ins. above ground for a reference monument, bears N. 0°16' W., 38.5 ft. dist. with brass cap mkd. ROAD 4418 B STA 9+68.96 LS 4476 1972. Set a steel fence post, with attached USFS sign # 54-9, N. of cor.</p> <hr/> <p>S. 89°44' E., on the E. and W. center line of the NW 1/4 of the NE 1/4 of sec. 13.</p>
8.36	<p>A rebar, 1/2 in. diam., firmly set, projecting 1 in. above ground, with plastic cap, 2 ins. diam., mkd. LS 18548 DO NOT DISTURB 928-526-0270 MARTIN LAND SURVEYS, established by Martin H. Martin, Arizona R.L.S. No. 18548, in 2014, according to Instrument # 3695303, on file at Coconino County Recorder's Office.</p>
9.934	<p>The C-N-NE 1/64 sec. cor. of sec. 13.</p> <hr/> <p style="text-align: center;"><b>Subdivision of Section 15, T. 23 N., R. 6 E., Gila and Salt River Meridian, Arizona</b></p> <hr/> <p>From the 1/4 sec. cor. of secs. 15 and 22, monumented with an iron post, 1 in. diam., firmly set, projecting 9 ins. above ground, with brass cap mkd. 1/4 S15 S22 1985 1943.</p> <p>from which the bearing tree recovered in 1943</p> <p style="padding-left: 40px;">A ponderosa pine snag, 28 ins. diam., bears N. 52° E., 36 lks. dist., with no marks visible on axed open blaze.</p> <p>and the bearing tree mkd. in 1943</p> <p style="padding-left: 40px;">A ponderosa pine, 18 ins. diam., bears S. 74 1/2° W., 36 lks. dist., with scribe marks 1/4 S22 visible on partially open blaze.</p> <p>and the bearing tree mkd. in 1985</p> <p style="padding-left: 40px;">A ponderosa pine, 12 ins. diam., bears S. 36° E., 26.5 lks. dist., with no marks visible.</p> <p>Add the marks T23N R6E 2014 to the brass cap.</p> <p>Set a steel fence post, with attached USFS signs # 54-2 and # 54-9, NE of cor.</p> <p>N. 2°23' W., on the N. and S. center line of sec. 15.</p>
19.78	<p>Point for center S. 1/16 sec. cor. of sec. 15, not monumented.</p>

Subdivision of Section 15,  
T. 23 N., R. 6 E., Gila and Salt River Meridian, Arizona

CHAINS	
39.56	Point for the center 1/4 sec. cor. of sec. 15, at the intersection with the E. and W. center line, not monumented.
79.46	The 1/4 sec. cor. of secs. 10 and 15. <hr/>
	From the 1/4 sec. cor. of secs. 14 and 15.  N. 89°40' W., on the E. and W. center line of sec. 15.
20.213	Point for the center E. 1/16 sec. cor. of sec. 15, not monumented.
40.425	The center 1/4 sec. cor. of sec. 15.
79.277	The 1/4 sec. cor. of secs. 15 and 16, monumented with an iron post, 1 in. diam., firmly set, projecting 8 ins. above ground, with brass cap mkd. 1/4 S16 S15 1943.  from which the bearing tree recovered in 1943  A dead tree, 32 ins. diam., bears S. 60° W., 30 lks. dist., with a healed blaze.  and the bearing tree mkd. in 1943  A downed tree, 12 ins. diam., bears S. 46 1/2° E., 43 lks. dist., with no marks visible.  and a new bearing tree  A pine, 13 ins. diam., bears N. 45° W., 31.5 lks. dist., mkd. X at breast height and BT at base. <hr/>
	SE 1/4 <hr/>
	From the E. 1/16 sec. cor. of secs. 15 and 22, monumented with a stainless steel post, 2 1/2 ins. diam., firmly set, projecting 6 ins. above ground, with brass cap mkd. T23N R6E E 1/16 S15 S22 1985, with a steel fence post nearby.  Add the marks 2014 to the brass cap.  Reset the steel fence post and attached USFS signs # 54-2 and # 54-9, S. of cor.  The cor. is located alongside a downed barbed wire fence, bears N. and S.  N. 2°15' W., on the N. and S. center line of the SE 1/4 of sec. 15.



Subdivision of Section 15,  
T. 23 N., R. 6 E., Gila and Salt River Meridian, Arizona

CHAINS	
19.80	<p>Point for the SE 1/16 sec. cor. of sec. 15, at the intersection with the E. and W. center line of the SE 1/4.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T 23 N R 6 E</p> <p style="text-align: center;">SE 1/16 S 15</p> <p style="text-align: center;">2014</p> <p>from which</p> <p style="padding-left: 40px;">A pine, 6 ins. diam., bears S. 45° W., 19.5 lks. dist., mkd. X at breast height and BT at base.</p> <p style="padding-left: 40px;">A pine, 16 ins. diam., bears N. 12° W., 74 lks. dist., mkd. X at breast height and BT at base.</p> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p> <p>Set a steel fence post, with attached USFS signs # 54-2 and # 54-9, NW of cor.</p> <p>The cor. is located 22.5 lks. S. of a firebreak line, bears N. 75° E. and S. 75° W.</p> <p>From this cor., a fence cor. barbed wire, 5 strand, bears S. 70° E., 1.08 chs. dist., from which fences extend E. and S. 5° E.</p>
39.60	<p>The center E. 1/16 sec. cor. of sec. 15.</p> <hr/> <p>From the S. 1/16 sec. cor. of secs. 14 and 15.</p> <p>N. 89°36' W., on the E. and W. center line of the SE 1/4 of sec. 15.</p>
20.178	<p>The SE 1/16 sec. cor. of sec. 15.</p>
40.351	<p>The center S. 1/16 sec. cor. of sec. 15.</p> <hr/> <p style="text-align: center;">Subdivision of Section 26, T. 23 N., R. 6 E., Gila and Salt River Meridian, Arizona</p> <hr/> <p>From the 1/4 sec. cor. of secs. 26 and 35.</p> <p>N. 0°16' E., on the N. and S. center line of sec. 26.</p>

Subdivision of Section 26,  
T. 23 N., R. 6 E., Gila and Salt River Meridian, Arizona

CHAINS	
19.783	<p>The center S. 1/16 sec. cor. of sec. 26, established by Charles Dryden, Arizona R.L.S. No. 13010, date unknown, monumented with rebar, 18 ins. long, 5/8 in. dia., firmly set, projecting 2 ins. above ground, with aluminum cap mkd. ARECO LS 13010. This is accepted as a careful and faithful establishment of the cor. position.</p> <p>At the corner point</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T 23 N R 6 E</p> <p style="text-align: center;">C-S 1/16 S26</p> <p style="text-align: center;">2014</p> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p> <p>Deposit the rebar with aluminum cap inside the stainless steel post.</p> <p>Set a steel fence post, with attached USFS signs # 54-2 and # 54-9, SE of cor.</p> <p>The cor. is located alongside of a downed barbed wire fence, bears N. and S.</p> <p>From this cor., a fence corner, bears North 6 lks. dist., with barbed wire and railroad tie fences extend N. and W.</p> <hr style="width: 20%; margin: 10px auto;"/> <p>N. 0°16' E., beginning new measurement.</p>
19.781	<p>The center 1/4 sec. cor. of sec. 26, established by Wilfred P. Hanson, Arizona R.L.S. No. 2473, date unknown. monumented with a rebar, 18 ins. long, 5/8 in. diam., firmly set, flush with ground, with brass tag mkd. LS 2473, with another rebar alongside of unknown origin, 18 ins. long, 5/8 in. diam., 2 ins. below the surface of the ground. This is accepted as a careful and faithful establishment of the cor. position.</p> <p>At the corner point</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 16 ins. in the ground to bedrock, in a mound of stone, 3 ft. base, to top, with brass cap mkd.</p>

Subdivision of Section 26,  
T. 23 N., R. 6 E., Gila and Salt River Meridian, Arizona

CHAINS	
	<p>T 23 N R 6 E</p> <p>C 1/4 S 26</p> <p>2014</p>
	<p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p> <p>Deposit the rebar with brass tag and the other rebar inside the stainless steel post.</p> <p>Set a steel fence post, with attached USFS signs # 54-2 and # 54-9, S. of cor.</p> <p>From this cor., an open end pipe, of unknown origin, 3/4 in. diam., firmly set, projecting 2 ins. above ground, bears South 1 lk. dist.</p> <p>From this same cor., a fence corner, bears S. 38°49' E., 31 lks. dist., from which fence extend N. and a gate extend W.</p> <p>From this same cor., a fence corner, bears S. 2°57' E., 25 lks. dist., from which a gate extend E. and fence extend S.</p>
	<hr style="width: 20%; margin: auto;"/> <p>N. 0°16' E., beginning new measurement.</p>
19.788	<p>Point for the center N. 1/16 sec. cor. of sec. 26.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p>
	<p>T 23 N R 6 E</p> <p style="margin-left: 100px;">C</p> <p>N 1/16   S 26</p> <p style="margin-left: 100px;">C</p> <p>2014</p>
	<p>from which</p> <p style="margin-left: 40px;">A ponderosa pine, 19 ins. diam., bears N. 45° E., 1.89 chs. dist., mkd. X at breast height and BT at base.</p> <p style="margin-left: 40px;">A ponderosa pine, 11 ins. diam., bears S. 70° E., 3.30 chs. dist., mkd. X at breast height and BT at base.</p> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p> <p>Set a steel fence post with attached USFS signs # 54-2 and # 54-9, N. of. cor.</p>

Subdivision of Section 26,  
T. 23 N., R. 6 E., Gila and Salt River Meridian, Arizona

CHAINS

The cor. is located 12 lks. W. of a barbed wire fence, bears S. 5° E. and N. 5° W.

---

N. 0°16' E., beginning new measurement.

14.846

The C-N-N-N 1/256 sec. cor. of sec. 26, established by John C. Anderson, Arizona R.L.S. No. 6450, date unknown, monumented with a rebar, 18 ins. long, 5/8 in. diam., firmly set, 2 ins. below the surface of the ground, with brass tag mkd. LS 6450. This is accepted as a careful and faithful establishment of the cor. position.

At the cor. point

Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 20 ins. in the ground, in a mound of stone, 2 1/2 ft. base, to top, with brass cap mkd.

T 23 N R 6 E  
S 26  
C-N-N-N  
1/256

2014

from which

A double ponderosa pine, 18 ins. diam., bears S. 50° E., 1.60 chs. dist., mkd. X at breast height and BT at base on the most northerly trunk.

A ponderosa pine, 10 ins. diam., bears S. 18° E., 1.535 chs. dist., mkd. X at breast height and BT at base.

Deposit a magnet, in a white plastic case, at the base of the stainless steel post.

Deposit the rebar with brass tag inside the stainless steel post.

Set a steel fence post, with attached USFS signs # 54-2 and # 54-9, SE of cor.

The cor. is located 5 lks. W. of a barbed wire fence, bears S. 5° E., and N. 5° W.

---

N. 0°16' E., beginning new measurement.

Entering patented lands.

Subdivision of Section 26,  
T. 23 N., R. 6 E., Gila and Salt River Meridian, Arizona

CHAINS	
4.947	<p>The 1/4 sec. cor. of secs. 23 and 26, monumented with an iron post, 1 in. diam., firmly set, projecting 7 ins. above ground, in a collar of stone, with brass cap mkd. 1/4 S23 S26 1943.</p> <p>from which the bearing trees mkd. in 1943</p> <p style="padding-left: 40px;">A ponderosa pine, 21 ins. diam., bears N. 58 1/2° E., 38 lks. dist., with a healed blaze, 1 BT tag and 1 no trespassing sign.</p> <p style="padding-left: 40px;">A ponderosa pine, 26 ins. diam., bears S. 9° E., 48 lks. dist., with a healed blaze and 1 BT tag.</p> <p>Add the marks T23N R6E 2014 to the brass cap.</p> <p>Set a steel fence post, with attached USFS sign # 54-9, S. of cor.</p> <p>The cor. is located 16.5 lks. S. of a dirt road, along a curve, concave to S.</p> <hr/> <p>From the 1/4 sec. cor. of secs. 25 and 26.</p> <p>N. 89°45' W., on the E. and W. center line of sec. 26.</p>
19.90	<p>Point for the center E. 1/16 sec. cor. of sec. 26.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 27 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center; margin: 10px 0;"> <p>T 23 N R 6 E</p> <p>E 1/16</p> <p>C ————— C</p> <p>S 26</p> <p>2014</p> </div> <p>from which</p> <p style="padding-left: 40px;">A 60D nail, on the top center of a stump, 15 ins. high on the S. edge, 28 ins. diam., for a reference monument, bears N. 71°22' E., 57.6 ft. dist. with brass washer 1 1/2 ins. diam., mkd. BLM 2014 and thru an USFS sign # 54-9. Set a steel fence post, with attached USFS sign # 54-9, NE of nail.</p> <p style="padding-left: 40px;">A 60D nail, on the top center of a stump, 4 ins. high on the S. edge, 18 ins. diam., for a reference monument, bears N. 64°22' W., 31.2 ft. dist. with brass washer, 1 1/2 ins. diam., mkd. BLM 2014 and thru an USFS sign # 54-9. Set a steel fence post, with attached USFS sign # 54-9, NW of nail.</p>

Subdivision of Section 26,  
T. 23 N., R. 6 E., Gila and Salt River Meridian, Arizona

CHAINS	
	<p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p> <p>Set a steel fence post, with attached USFS sign # 54-9, E. of cor.</p>
39.80	<p>The center 1/4 sec. cor. of sec. 26.</p> <hr style="width: 20%; margin: 0 auto;"/> <p>N. 89°46' W., beginning new measurement.</p> <p>Entering patented lands.</p>
19.886	<p>Point for the center W. 1/16 sec. cor. of sec. 26, not monumented.</p>
39.773	<p>The 1/4 sec. cor. of secs. 26 and 27.</p> <hr style="width: 20%; margin: 0 auto;"/> <p style="text-align: center;">NE 1/4</p> <hr style="width: 20%; margin: 0 auto;"/> <p>From the center E. 1/16 sec. cor. of sec. 26.</p> <p>N. 0°21' E., on the N. and S. center line of the NE 1/4 of sec. 26.</p>
19.90	<p>Point for the NE 1/16 of sec. of sec. 26, at the intersection with the E. and W. center line of the NE 1/4.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 25 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T 23 N R 6 E S 26 NE 1/16  2014</p> <p>from which</p> <p style="padding-left: 40px;">A ponderosa pine, 17 ins. diam., bears N. 22° E., 1.17 chs. dist., mkd. X at breast height and BT at base.</p> <p style="padding-left: 40px;">A ponderosa pine, 14 ins. diam., bears N. 40° E., 1.815 chs. dist., mkd. X at breast height and BT at base.</p> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p>

Subdivision of Section 26,  
T. 23 N., R. 6 E., Gila and Salt River Meridian, Arizona

CHAINS	
	<p>Set a steel fence post, with attached USFS sign # 54-9, W. of cor.</p> <p>The cor. is located 63.5 lks. W. of trail road, bears N. 65° E. and S. 55° W.</p>
34.83	<p>The C-N-N-NE 1/256 sec. cor. of sec. 26, monumented with a rebar, 18 ins. long, 5/8 in. diam., firmly set, 2 ins. below the surface of the ground, with some wire attached, no tag found. This is accepted as a careful and faithful establishment of the cor. position.</p> <p>At the corner point</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 23 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T 23 N R 6 E S 26 C-N-N-NE 1/256  2014</p> <p>from which</p> <p style="padding-left: 40px;">A ponderosa pine, 13 ins. diam., bears S. 80° E., 2.085 chs. dist., mkd. X at breast height and BT at base.</p> <p style="padding-left: 40px;">An aspen, 10 ins. diam., bears S. 25° W., 1.07 chs. dist., mkd. X at breast height and BT at base.</p> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p> <p>Deposit the rebar inside the stainless steel post.</p> <p>Set a steel fence post, with attached USFS signs # 54-2 and # 52-9, SE of cor.</p>
36.40	Dirt road, 10 ft. wide, bears N. 40° E. and S. 35° W.
39.80	The E. 1/16 sec. cor. of secs. 23 and 26.
	<hr/> <p>From the N. 1/16 sec. cor. of secs. 25 and 26.</p> <p>S. 89°56' W., on the E. and W. center line of the NE 1/4 of sec. 26.</p>
9.964	Point for the C-E-NE 1/64 sec. cor. of secs 26, not monumented.

Subdivision of Section 26,  
T. 23 N., R. 6 E., Gila and Salt River Meridian, Arizona

CHAINS	
	Entering patented lands.
14.945	Point for the C-W-E-NE 1/256 sec. cor. of sec. 26, not monumented.
	Leaving patented lands.
19.927	The NE 1/16 sec. cor. of sec. 26.
39.850	The center N. 1/16 sec. cor. of sec. 26.
	From the C-E-NE 1/64 sec. cor. of sec. 26.
	N. 0°32' E., on the N. and S. center line of the NE 1/4 of the NE 1/4 of sec. 26.
4.99	The C-S-NE-NE 1/256 sec. cor. of sec. 26, established by Joseph Costa, Arizona R.L.S. No. 9078, date unknown, monumented with a rebar, 18 ins. long, 1/2 in. diam., firmly set, projecting 4 ins. above ground, in a collar of stone, 2 ft. base, to top, with plastic cap, 1 in. diam., mkd. RLS 9078. This is accepted as a careful and faithful establishment of the cor. position.
	At the corner point
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 18 ins. in the ground to bedrock, in a mound of stone, 3 ft. base, to top, with brass cap mkd.
	T 23 N R 6 E S 26 C-S-NE-NE 1/256  2014
	from which
	A ponderosa pine, 11 ins. diam., bears N. 25° E., 77 lks. dist., mkd. X at breast height and BT at base.
	A ponderosa pine, 12 ins. diam., bears S. 65° E., 74 lks. dist., mkd. X at breast height and BT at base.
	Deposit a magnet, in a white plastic case, at the base of the stainless steel post.
	Deposit the rebar with plastic cap inside the stainless steel post.



Subdivision of Section 26,  
T. 23 N., R. 6 E., Gila and Salt River Meridian, Arizona

CHAINS	
4.98	<p>Set a steel fence post, with attached USFS signs # 54-2 and # 52-9, NE of cor.</p> <hr/> <p>From the C-W-E-NE 1/256 sec. cor. of sec. 26.</p> <p>N. 0°25' E., on the N. and S. center line of the SW 1/4 of the NE 1/4 of the NE 1/4 of sec. 26.</p> <p>Point for the SW-NE-NE 1/256 sec. cor. of sec. 26.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T 23 N R 6 E S 26 SW-NE-NE 1/256  2014</p> <p>from which</p> <p style="padding-left: 40px;">A ponderosa pine, 14 ins. diam., bears North, 34 lks. dist., mkd. X at breast height and BT at base.</p> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p> <p>Set a steel fence post, with attached USFS signs # 54-2 and # 54-9, NW of cor.</p> <p>From this cor., a rebar, 1/2 in. diam., firmly set, projecting 2 ins. above ground, in a collar of stone, 1 1/2 ft. base, 4 ins. high, with plastic cap mkd. RLS 9078, bears S. 50°48' W., 26 lks. dist., established by Joseph Costa, Arizona R.L.S. No. 9078, date unknown.</p> <hr/> <p>N. 89°50' E., on the E. and W. center line of the SW 1/4 of the NE 1/4 of the NE 1/4 of sec. 26.</p>
4.99	<p>The C-S-NE-NE sec. cor. of sec. 26.</p> <hr/> <p>From the C-E-NE 1/64 sec. cor. of sec. 26.</p> <p>S. 0°32' W., on the N. and S. center line of the SE 1/4 of the NE 1/4 of sec. 26.</p>

Subdivision of Section 26,  
T. 23 N., R. 6 E., Gila and Salt River Meridian, Arizona

CHAINS	
4.987	<p>The C-N-SE-NE 1/256 sec. cor. of sec. 26, established by John C. Anderson, Arizona R.L.S. No. 6450, date unknown, monumented with a rebar, 18 ins. long, 1/2 in. diam., firmly set, projecting 1 in. above ground, with brass tag mkd. LS 6450. This is accepted as a careful and faithful establishment of the cor. position.</p> <p>At the corner point</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T 23 N R 6 E S 26 C-N-SE-NE 1/256</p> <p style="text-align: center;">2014</p> <p>from which</p> <p style="padding-left: 40px;">A ponderosa pine, 7 ins. diam., bears S. 62° E., 75 lks. dist., mkd. X at breast height and BT at base.</p> <p style="padding-left: 40px;">A ponderosa pine, 14 ins. diam., bears S. 8° W., 39.5 lks. dist., mkd. X at breast height and BT at base.</p> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p> <p>Deposit the rebar with brass tag inside the stainless steel post.</p> <p>Set a steel fence post, with attached USFS signs # 54-2 and # 54-9, SE of cor.</p> <hr/> <p>N. 89°58' W., on the E. and W. center line of NW 1/4 of the SE 1/4 of the NE 1/4 of sec. 26.</p>
4.97	<p>The NW-SE-NE 1/256 sec. cor. of sec. 26, established by John C. Anderson, Arizona R.L.S. No. 6450, date unknown, monumented with a rebar, 18 ins. long, 1/2 in. diam., firmly set, flush with the surface of the ground, with brass tag mkd. LS 6450. This is accepted as a careful and faithful establishment of the cor. position.</p> <p>At the corner point</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p>

Subdivision of Section 26,  
T. 23 N., R. 6 E., Gila and Salt River Meridian, Arizona

CHAINS	
	T 23 N R 6 E S 26 NW-SE-NE 1/256  2014
	from which  A ponderosa pine, 21 ins. diam., bears S. 30° W., 54.5 lks. dist., mkd. X at breast height and BT at base.  Deposit a magnet, in a white plastic case, at the base of the stainless steel post.  Deposit the rebar with brass tag inside the stainless steel post.  Set a steel fence post, with attached USFS signs # 54-2 and # 54-9, SW of cor.  From this cor., a rebar, 1/2 in. diam., firmly set, projecting 1 in. above ground, in a collar of stone, 1 1/2 ft. base, 6 ins. high, with plastic cap mkd. RLS 9078, bears S. 67°21' E., 41 lks. dist., established by Joseph Costa, Arizona R.L.S. No. 9078, date unknown.
	<hr/> N. 0°25' E., on the N. and S. center line of NW 1/4 of the SE 1/4 of the NE 1/4 of sec. 26.
4.98	The C-W-E-NE 1/256 sec. cor. of sec. 26.  <hr/> From the C-N-N-NE 1/256 sec. cor. of sec. 26.  S. 89°42' W., on the E. and W. center line of the N 1/2 of the NW 1/4 of the NE 1/4 of sec. 26.
2.67	Dirt road, 10 ft. wide, bears N. 35° E. and S. 35° W.
5.07	Dirt road, 10 ft. wide, bears S. 40° E. and N. 40° W.
11.58	From this point, the NW cor. of a wooden shed 12.5 x 10.5 ft. bears S. 5 lks. dist., the long side bears S.
19.937	The C-N-N-N 1/256 sec. cor. of sec. 26.  <hr/> <div style="text-align: center;">SW 1/4</div> <hr/> From the W. 1/16 sec. cor. of secs. 26 and 35.

Subdivision of Section 26,  
T. 23 N., R. 6 E., Gila and Salt River Meridian, Arizona

CHAINS	
	N. 0°11' E., on the N. and S. center line of the SW 1/4 of sec. 26.
19.675	Point for the SW 1/16 sec. cor. of sec. 26, at the intersection with the E. and W. center line of the SW 1/4.  Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 23 ins. in the ground, with brass cap mkd.  <div style="text-align: center;">T 23 N R 6 E S 26 SW 1/16  2014</div> <p>from which</p> <p style="padding-left: 40px;">A 60D nail, on top of a wood fence post, railroad tie, 8 x 6 ins., for a reference monument, bears N. 75°08' E., 18.4 ft. dist. with brass washer, 1 1/2 ins. diam., mkd. BLM 2014. The fence, barbed wire, bears E. and W.</p> <p style="padding-left: 40px;">A double ponderosa pine, 10 ins. diam., bears S. 75° E., 1.44 chs. dist., mkd. X at breast height and BT at base on most northerly trunk.</p> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p> <p>Set a steel fence post with attached USFS signs # 54-2 and # 54-9, W. of cor.</p> <p>Entering patented lands.</p>
19.74	A downed barbed wire fence, bears E. and W.
39.351	The center W. 1/16 sec. cor. of sec. 26. <hr/>
	From the center S. 1/16 sec. cor. of sec. 26.  N. 89°27' W., on the E. and W. center line of the SW 1/4 of sec. 26.
19.856	The SW 1/16 sec. cor. of sec. 26.
39.713	The S. 1/16 sec. cor. of secs. 26 and 27. <hr/>

Subdivision of Section 27,  
T. 23 N., R. 6 E., Gila and Salt River Meridian, Arizona

CHAINS	
20.18	<p>From the 1/4 sec. cor. of secs. 26 and 27.</p> <p>S. 89°55' W., on the E. and W. center line of sec. 27</p> <p>The center E. 1/16 sec. cor. of sec. 27, monumented with an aluminum post, 3/4 in. diam., firmly set, projecting 6 ins. above ground, with aluminum cap mkd. T23N R6E E 1/16 S27 1985, with a steel fence post, NW of cor.</p> <p>Add the marks 2014 to the aluminum cap.</p> <p>Attached USFS sign # 54-9 to the steel fence post.</p> <hr/> <p style="text-align: center;">NE 1/4</p> <hr/> <p>From the center E. 1/16 sec. cor. of sec. 27.</p> <p>N. 0°03' E., on the N. and S. center line of the NE 1/4 of sec. 27.</p> <p>The NE 1/16 sec. cor. of sec. 27, monumented with an aluminum post, 3/4 in. diam., firmly set, projecting 6 ins. above ground, with aluminum cap mkd. T23N R6E NE 1/16 S27 1985, with a steel fence post, NE of cor.</p> <p>from which the bearing trees mkd. in 1985</p> <p style="padding-left: 40px;">A limber pine, 19 ins. diam., bears N. 2° E., 34.5 lks. dist., with 2 healed blaze and 1 BT tag.</p> <p style="padding-left: 40px;">A limber pine, 12 ins. diam., bears N. 79° W., 60.5 lks. dist., with a healed blaze and 1 BT tag.</p> <p>Add the marks 2014 to the aluminum cap.</p> <p>Set a steel fence post, with attached USFS sign # 54-9, SE of cor.</p> <hr/> <p>N. 0°03' E., beginning new measurement.</p>
19.70	<p>The E. 1/16 sec. cor. of secs. 22 and 27.</p> <hr/> <p>From the N. 1/16 sec. cor. of secs. 26 and 27.</p> <p>N. 89°47' W., on the E. and W. center line of the NE 1/4 of sec. 27.</p> <p>On and across patented lands.</p>
19.71	

Subdivision of Section 27,  
T. 23 N., R. 6 E., Gila and Salt River Meridian, Arizona

CHAINS	
5.053	Point for the C-E-E-NE 1/256 sec. cor. of sec. 27, not monumented.  Leaving patented lands.
20.212	The NE 1/16 sec. cor. of sec. 27. <hr/>
	From the C-E-E-NE 1/256 sec. cor. of sec. 27.  N. 0°07' E., on the N. and S. center line of the SE 1/4 of the NE 1/4 of the NE 1/4 of sec. 27.
7.36	Point for the 1/1024 sec. cor. of sec. 27.  Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with brass cap mkd.  T 23 N R 6 E  1/1024  2014  from which  An aspen, 6 ins. diam., bears North, 55 lks. dist., mkd. X at breast height and BT at base.  A ponderosa pine, 7 ins. diam., bears N. 65° W., 51.5 lks. dist., mkd. X at breast height and BT at base.  Deposit a magnet, in a white plastic case, at the base of the stainless steel post.  Set a steel fence post, with attached USFS signs # 54-4 and # 54-9, NW of cor. <hr/>
5.06	S. 89°40' E., on the E. and W. center line of the NE 1/4 of the SE 1/4 of the NE 1/4 of the NE 1/4 of sec. 27.  The 1/1024 sec. cor. of secs. 26 and 27, located 7.35 chs. N. 0°09' E. of the N. 1/16 sec. cor. of secs. 26 and 27. <hr/>
	From the 1/1024 sec. cor. of secs. 26 and 27, located 2.45 chs. S. 0°09' W. of the N. 1/16 sec. cor. of secs. 26 and 27.  N. 89°49' W., on the E. and W. center line of the NE 1/4 of the NE 1/4 of the SE 1/4 of the NE 1/4 of sec. 27.
5.05	Point for the 1/1024 sec. cor. of sec. 27.

Subdivision of Section 27,  
T. 23 N., R. 6 E., Gila and Salt River Meridian, Arizona

CHAINS	
	<p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T 23 N R 6 E</p> <p style="text-align: center;">1/1024</p> <p style="text-align: center;">2014</p> <p>from which</p> <p style="padding-left: 40px;">A ponderosa pine, 10 ins. diam., bears S. 28° W., 37 lks. dist., mkd. X at breast height and BT at base.</p> <p style="padding-left: 40px;">An aspen, 11 ins. diam., bears West, 60 lks. dist., mkd. X at breast height and BT at base.</p> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p> <p>Set a steel fence post, with attached USFS signs # 54-4 and # 54-9, SW of cor.</p> <hr/> <p>N. 0°07' E., on the N. and S. center line of the NE 1/4 of the SE 1/4 of the NE 1/4 of sec. 27.</p>
2.45	<p>The C-E-E-NE 1/256 sec. cor. of sec. 27.</p> <hr/> <p style="text-align: center;">NW 1/4</p> <hr/> <p>From the SE-NW-NW 1/256 sec. cor. of sec. 27, determined latitudinally by the bearing tree mkd. in 1985 and longitudinally by a barbed fence, bears S. 0°15' E.</p> <p>Set a brass tablet, 3 1/2 ins. diam., 2 1/2 ins. stem, cemented in a drill hole, in the concrete footing of a stainless steel fence post, with top mkd.</p> <p style="text-align: center;">T 23 N R 6 E</p> <p style="text-align: center;">S 27</p> <p style="text-align: center;">SE-NW-NW</p> <p style="text-align: center;">1/256</p> <p style="text-align: center;">2014</p> <p>from which the bearing tree mkd. in 1985</p> <p style="padding-left: 40px;">A ponderosa pine, 15 ins. diam., bears S. 6° W., 2.10 chs. dist., with a healed blaze and 1 BT tag. (Record: S. 16 1/4° W.)</p>

**Subdivision of Section 27,  
T. 23 N., R. 6 E., Gila and Salt River Meridian, Arizona**

## CHAINS

Deposit a magnet, without the white plastic case, at the base of the brass tablet.

Set a steel fence post, with attached USFS signs # 54-2 and # 54-9, NW of cor.

The cor. is located at the terminus of a barbed wire fence, bears S. 0°15' E.

N. 89°43' W., on the E. and W. center line of the S. 1/2 of the NW 1/4 of the NW 1/4 of sec. 27.

15.174 The S-N-N 1/256 sec. cor. of secs. 27 and 28.

---

**Metes-and-Bounds Survey in Section 27,  
T. 23 N., R. 6 E., Gila and Salt River Meridian, Arizona**

---

In the  
NW 1/4

---

From AP 1, lot 1, sec. 27, hereinbefore described.

S. 0°14' E., on the E. boundary of lot 1 of sec. 27.

15.00 AP 2, lot 1, sec. 27, established by Christopher J. Franks, Arizona R.L.S. No. 22258, date unknown, and accepted by Kenneth A. Krenke, Arizona R.L.S. No. 14671, in 1994, according to Book 12, Page 25, on file at Coconino County Recorder's Office, monumented with a rebar, 18 ins. long, 1/2 in. diam., firmly set, projecting 2 ins. above ground, with plastic cap, 1 in. diam., mkd. C J F LS 22258, with a "T" post nearby. This is accepted as a careful and faithful establishment of the cor. position.

At the corner point

Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.

T 23 N R 6 E

L 1
AP 2

S 27

2014

Deposit a magnet, in a white plastic case, at the base of the stainless steel post.



**Metes-and-Bounds Survey in Section 27,  
T. 23 N., R. 6 E., Gila and Salt River Meridian, Arizona**

CHAINS	
	<p>Deposit the rebar with plastic cap inside the stainless steel post.</p> <p>Set a steel fence post, with attached USFS signs # 54-2 and # 54-9, NW of cor.</p> <hr style="width: 20%; margin: 10px auto;"/> <p>N. 89°14' W., beginning new measurement.</p> <p>Thence on the S. boundary of lot 1 of sec. 27.</p>
11.46	<p>The SE-NW-NW 1/256 sec. cor. of sec. 27.</p> <hr/> <p style="text-align: center;"><b>Subdivision of Section 34, T. 23 N., R. 6 E., Gila and Salt River Meridian, Arizona</b></p> <hr/> <p>From the 1/4 sec. cor. of secs. 3 and 34, on the S. bdy. of the Tp.</p> <p>N. 0°04' E., on the N. and S. center line of sec. 34.</p>
40.44	<p>The center 1/4 sec. cor. of sec. 34, monumented with a stainless steel post, 2 1/2 ins. diam., firmly set, projecting 4 ins. above ground, with brass cap mkd. T23N R6E C 1/4 S34 1985, with a scattered mound of stone W. of cor.</p> <p>Reconstruct the mound of stone, utilizing the scattered mound of stone, 2 1/2 ft. base, 1 1/2 ft. high, W. of cor.</p> <p>Set a steel fence post, with attached USFS signs # 54-2 and # 54-9, alongside of cor.</p> <hr/> <p>N. 0°05' E., beginning new measurement.</p>
19.97	<p>The center N. 1/16 sec. cor. of sec. 34, established by Wilfred P. Hanson, Arizona R.L.S. No. 2473, date unknown, and accepted by James A. Folkers, Arizona R.L.S. No. 18215, in 2007, according to Official Record of Coconino County 3432556, on file at Coconino County Recorder's Office, monumented with a rebar, 1/2 diam., firmly set, flush with the ground, with brass tag mkd. LS 2473. This is accepted as a careful and faithful establishment of the cor. position.</p> <p>At the corner point</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p>

Subdivision of Section 34,  
T. 23 N., R. 6 E., Gila and Salt River Meridian, Arizona

CHAINS	
	T 23 N R 6 E C N 1/16   S 34 C
	2013
	<p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p> <p>Deposit the rebar with brass tag inside the stainless steel post.</p> <p>Set a steel fence post, with attached USFS signs # 54-2 and # 54-9, alongside of cor.</p> <p>The cor. is located in fence extending E. and W., 1.30 chs. dist. to fence cor., which fence extends N., E. and S.</p> <hr style="width: 20%; margin: 10px auto;"/> <p>N. 0°05' E., beginning new measurement.</p>
9.98	<p>The C-N-N 1/64 sec. cor. of sec. 34, established by Donald L. Ziemba, Arizona R.L.S. No. 16218, date unknown, and accepted by James A. Folkers, Arizona R.L.S. No. 18215, in 2007, according to Official Record of Coconino County 3432556, on file at Coconino County Recorder's Office, monumented with a rebar, 1/2 in. diam., firmly set, flush with the ground, with yellow plastic cap mkd. LS 16218. This is accepted as a careful and faithful establishment of the cor. position.</p> <p>At the corner point</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 22 ins. in the ground, in a collar of stone, 2 1/2 ft. base, to top, with brass cap mkd.</p>
	T 23 N R 6 E C N-N 1/64   S 34 C
	2013
	<p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p> <p>Deposit the rebar with yellow plastic cap inside the stainless steel post.</p> <p>Set a steel fence post, with attached USFS signs # 54-2 and # 54-9, alongside of cor.</p> <hr style="width: 20%; margin: 10px auto;"/>

Subdivision of Section 34,  
T. 23 N., R. 6 E., Gila and Salt River Meridian, Arizona

CHAINS	
	N. 0°05' E., beginning new measurement.
4.99	A local monument, a rebar, 1/2 in. diam., firmly set, flush with the ground, with a yellow plastic cap mkd. LS 18548, established by Martin H. Martin, Arizona R.L.S. No. 18548, in 2004, according to Book 23, Page 42, on file at Coconino County Recorder' Office.
9.99	The 1/4 sec. cor. of secs. 27 and 34. <hr/>
	From the 1/4 sec. cor. of secs. 34 and 35.
	N. 89°27' W., on the E. and W. center line of sec. 34.
20.01	The center E. 1/16 sec. cor. of sec. 34, established by Christopher J. Franks, Arizona R.L.S. No. 22258, date unknown, and accepted by James A. Folkers, Arizona R.L.S. No. 18215, in 2007, according to Official Record of Coconino County 3432556, on file at Coconino County Recorder's Office, monumented with a rebar, 1/2 diam., firmly set, projecting 3 ins. above ground, with yellow plastic cap mkd. C J F LS 22258. This is accepted as a careful and faithful establishment of the cor. position.  At the corner point  Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.  <div style="text-align: center;">           T 23 N R 6 E            E 1/16            C ——— C            S 34             2013         </div> Deposit a magnet, in a white plastic case, at the base of the stainless steel post.  Deposit the rebar with yellow cap inside the stainless steel post.  Set a steel fence post, with attached USFS signs # 54-2 and # 54-9, alongside of cor.  <hr/>
20.02	N. 89°27' W., beginning new measurement.  The center 1/4 sec. cor. of sec. 34. <hr/>
	N. 89°27' W., beginning new measurement.

Subdivision of Section 34,  
T. 23 N., R. 6 E., Gila and Salt River Meridian, Arizona

CHAINS	
40.29	<p>the 1/4 sec. cor. of secs. 33 and 34.</p> <hr/> <p style="text-align: center;">NE 1/4</p> <hr/> <p>From the center E. 1/16 sec. cor. of sec. 34.</p> <p>N. 0°13' E., on the N. and S. center line of the NE 1/4 of sec. 34.</p> <p>Entering patented lands.</p>
20.20	<p>The NE 1/16 sec. cor. of sec. 34, established by Christopher J. Franks, Arizona R.L.S. No. 22258, date unknown, and accepted by James A. Folkers, Arizona R.L.S. No. 18215, in 2007, according to Official Record of Coconino County 3432556, on file at Coconino County Recorder's Office, monumented with a rebar, 1/2 in. diam., firmly set, projecting 3 ins. above ground, with yellow plastic cap mkd. C J F LS 22258. This is accepted as a careful and faithful establishment of the cor. position.</p> <hr/> <p>N. 0°13' E., beginning new measurement.</p> <p>Continuing across patented lands.</p>
10.095	<p>The C-N-NE 1/64 sec. cor. of sec. 34, monumented with a rebar, 1/2 in. diam., firmly set, flush with the ground, Martin H. Franks, Arizona R.L.S. No. 18548, attached the an aluminum cap mkd. MARTIN LS 18548, in 2004, according to Book 23, Page 42, on file at Coconino County Recorder' Office. This is accepted as a careful and faithful determination of the cor. position.</p> <hr/> <p>N. 0°13' E., beginning new measurement.</p>
10.095	<p>The E. 1/16 sec. cor. of secs. 27 and 34.</p> <hr/> <p>From the N. 1/16 sec. cor. of secs. 34 and 35.</p> <p>S. 89°55' W., on the E. and W. center line of the NE 1/4 of sec. 34.</p> <p>Entering patented lands.</p>
20.07	<p>The NE 1/16 sec. cor. of sec. 34.</p> <hr/> <p>S. 89°55' W., beginning new measurement.</p> <p>Continuing across patented lands.</p>

Subdivision of Section 34,  
T. 23 N., R. 6 E., Gila and Salt River Meridian, Arizona

CHAINS	
10.04	<p>The C-W-NE 1/64 sec. cor. of sec. 34, established by Wilfred P. Hanson, R.L.S. No. 2473, date unknown, and accepted by James A. Folkers, Arizona R.L.S. No. 18215, in 2007, according to Official Record of Coconino County 3432556, on file at Coconino County Recorder's Office, monumented with rebar, 1/2 in. diam., firmly set, flush with the ground, with brass tag mkd. LS 2473. This is accepted as a careful and faithful establishment of the cor. position.</p> <p>At the corner point</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T 23 N R 6 E S 34 C-W-NE 1/64  2013</p> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p> <p>Deposit the rebar with brass tag inside the stainless steel post.</p> <p>Set a steel fence post, with attached USFS signs # 54-2 and # 54-9, alongside of cor.</p> <hr style="width: 25%; margin: 10px auto;"/> <p>S. 89°55' W., beginning new measurement.</p> <p>Thence along a portion of the boundary of Coconino National Forest.</p>
10.03	<p>The center N. 1/16 sec. cor. of sec. 34.</p> <hr style="width: 60%; margin: 10px auto;"/> <p>From the C-W-NE 1/64 sec. cor. of sec. 34.</p> <p>N. 0°09' E., on the N. and S. center line of the NW 1/4 of the NE 1/4 of sec. 34.</p>
10.04	<p>The NW-NE 1/64 sec. cor. of sec. 34, established by Donald L. Ziemba, Arizona R.L.S. No. 16218, date unknown, and accepted by Martin H. Martin, Arizona R.L.S. No. 18548, in 2007, according to Book 23, Page 42, on file at Coconino County Recorder's Office, monumented with a rebar, 1/2 in. diam., firmly set, flush with ground, with yellow plastic cap mkd. LS 16218. This is accepted as a careful and faithful establishment of the cor. position.</p>

Subdivision of Section 34,  
T. 23 N., R. 6 E., Gila and Salt River Meridian, Arizona

CHAINS	
	<p>At the corner point</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 28 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T 23 N R 6 E S 34 NW-NE 1/64</p> <p style="text-align: center;">2013</p> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p> <p>Deposit the rebar with yellow plastic cap inside the stainless steel post.</p> <p>Set a steel fence post, with attached USFS signs # 54-2 and # 54-9, alongside of cor.</p> <hr/> <p>N. 0°09' E., beginning new measurement.</p> <p>Entering patented lands.</p>
10.04	<p>The W-E 1/64 sec. cor. of secs. 27 and 34.</p> <hr/> <p>From the C-N-NE 1/64 sec. cor. of sec. 34.</p> <p>S. 89°36' W., on the E. and W. center line of the NW 1/4 of the NE 1/4 of sec. 34.</p> <p>On and across patented lands.</p>
10.047	<p>The NW-NE 1/64 sec. cor. of sec. 34.</p> <hr/> <p>S. 89°36' W., beginning new measurement.</p> <p>Thence along a portion of the boundary of Coconino National Forest.</p>
10.048	<p>The C-N-N 1/64 sec. cor. of sec. 34.</p> <hr/> <p style="text-align: center;">Subdivision of Section 35, T. 23 N., R. 6 E., Gila and Salt River Meridian, Arizona</p> <hr/> <p>From the 1/4 sec. cor. of secs. 2 and 35, on the S. bdy. of the Tp.</p>

Subdivision of Section 35,  
T. 23 N., R. 6 E., Gila and Salt River Meridian, Arizona

CHAINS	
	N. 0°03' E., on the N. and S. center line of sec. 35.
19.94	<p>The center S. 1/16 sec. cor. of sec. 35, monumented with a stainless steel post, 2 1/2 ins. diam., firmly set, projecting 5 ins. above ground, with brass cap mkd. S 1/16 S35 1985, with a steel fence post, W. of cor.</p> <p>from which the bearing trees mkd. in 1985</p> <p style="padding-left: 40px;">A dead tree, 14 ins. diam., bears S. 49 3/4° E., 61 lks. dist., with a healed blaze.</p> <p style="padding-left: 40px;">A ponderosa pine, 18 ins. diam., bears S. 12 1/2° E., 95 lks. dist., with a healed blaze.</p> <p>Add the marks 2014 to the brass cap.</p> <p>Attached USFS sign # 54-9 to the steel fence post.</p> <hr style="width: 20%; margin: 10px auto;"/> <p>N. 0°02' E., beginning new measurement.</p> <p>Continuing on the N. and S. center line of sec. 35.</p>
19.94	<p>The center 1/4 sec. cor. of sec. 35, monumented with a stainless steel post, 2 1/2 ins. diam., firmly set, projecting 4 ins. above ground, with brass cap mkd. T23N R6E C 1/4 S35 1985, with a steel fence post nearby.</p> <p>from which the bearing trees mkd. in 1985</p> <p style="padding-left: 40px;">A ponderosa pine, 27 ins. diam., bears S. 59° E., 77 lks. dist., with a healed blaze and 1 BT tag.</p> <p style="padding-left: 40px;">A ponderosa pine, 13 ins. diam., bears S. 63 1/4° W., 70 lks. dist., with 2 healed blaze.</p> <p>Add the marks 2014 to the brass cap.</p> <p>Set a steel fence post with attached USFS signs # 54-2 and # 54-9, E. of cor.</p> <hr style="width: 20%; margin: 10px auto;"/> <p>N. 0°02' E., beginning new measurement.</p> <p>Continuing on the N. and S. center line of sec. 35.</p> <p>Entering patented lands.</p>
10.110	Point for the C-S-N 1/64 sec. cor. of sec. 35, not monumented.

Subdivision of Section 35,  
T. 23 N., R. 6 E., Gila and Salt River Meridian, Arizona

CHAINS

10.566

AP 2, lot 2, sec. 35, identical with the SE cor. of parcel 4 of Snow Bowl Estates, established by Wilfred P. Hanson, Arizona R.L.S. No. 2473, in 1969, according to Case 2, Map 196, on file at Coconino County Recorder's Office, Martin H. Martin, Arizona R.L.S. No. 18548, attached an aluminum cap, in 2007, according to Official Records of Coconino County # 3445938, on file at Coconino County Recorder's Office, monumented with a rebar, 17 ins. long, 1/2 in. diam., firmly set, 1 in. below surface of the ground, with aluminum cap, 1 1/2 diam., mkd. MARTIN LS 18548, with a "T" post nearby.

At the corner point

Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.

T 23 N R 6 E

L 2
AP 2

S 35

2014

from which

A ponderosa pine, 23 ins. diam., bears N. 35° W., 2.505 chs. dist., mkd. X at breast height and BT at base.

A ponderosa pine, 24 ins. diam., bears N. 65° W., 1.125 chs. dist., mkd. X at breast height and BT at base.

Deposit a magnet, in a white plastic case, at the base of the stainless steel post.

Deposit the rebar with aluminum cap inside the stainless steel post.

Set a steel fence post, with attached USFS signs # 54-2 and # 54-9, NW of cor.

---

N. 0°02' E., beginning new measurement.

Continuing on the N. and S. center line of sec. 35, along a portion of the boundary of Coconino National Forest.



Subdivision of Section 35,  
T. 23 N., R. 6 E., Gila and Salt River Meridian, Arizona

CHAINS	
9.655	<p>The center N. 1/16 sec. cor. of sec. 35, monumented with a stainless steel post, 2 1/2 ins. diam., firmly set, projecting 4 ins. above ground, with brass cap mkd. T23N R6E N 1/16 S35 1985, with a steel fence post, NW of cor.</p> <p>from which the bearing tree mkd. in 1985</p> <p style="padding-left: 40px;">A ponderosa pine, 18 ins. diam., bears N. 61 1/2° E., 87.5 lks. dist., with no marks visible.</p> <p>Add the marks 2014 to the brass cap.</p> <p>Attached USFS signs # 54-2 and # 54-9 to the steel fence post.</p> <p>From this cor. an open end pipe of unknown origin, 3/4 in. diam., 1 in. below the surface of the ground, bears N. 30° W., 0.9 lk. dist.</p> <hr style="width: 20%; margin: 10px auto;"/> <p>N. 0°03' E., beginning new measurement.</p> <p>Continuing on the N. and S. center line of sec. 35.</p>
10.11	<p>The C-N-N 1/64 sec. cor. of sec. 35, monumented with a stainless steel post, 2 1/2 ins. diam., firmly set, projecting 6 ins. above ground, with brass cap mkd. S35 C-N-N 1/64 1985, with a steel fence post, NW of cor.</p> <p>from which the bearing tress mkd. in 1985</p> <p style="padding-left: 40px;">A ponderosa pine, 23 ins. diam., bears N. 34 1/2° E., 1.415 chs. dist., with 2 healed blaze and 1 BT tag.</p> <p style="padding-left: 40px;">A ponderosa pine, 27 ins. diam., bears N. 34 1/4° W., 98.5 lks. dist., with a healed blaze.</p> <p>Add the marks T23N R6E 2014 to the brass cap.</p> <p>Attached USFS sign # 54-9 to the steel fence post.</p> <hr style="width: 20%; margin: 10px auto;"/> <p>N. 0°02' E., beginning new measurement.</p>
10.117	<p>The 1/4 sec. cor. of secs. 26 and 35.</p> <hr style="width: 50%; margin: 10px auto;"/> <p>From the center 1/4 sec. cor. of sec. 35.</p> <p>N. 89°43' W., on the E. and W. center line of sec. 35, along the S. bdy. of Snow Bowl Estate.</p>

Subdivision of Section 35,  
T. 23 N., R. 6 E., Gila and Salt River Meridian, Arizona

CHAINS	
4.993	A local monument, a rebar, 1/2 in. diam., firmly set, projecting 1 in. above ground, established by Wilfred P. Hanson, Arizona R.L.S. No. 2473, in 1969, according to Case 2, Map 196, on file at Coconino County Recorder's Office.
9.987	A local monument, a rebar, 1/2 in. diam., firmly set, 1 in. below the surface of the ground, established by Wilfred P. Hanson, Arizona R.L.S. No. 2473, in 1969, according to Case 2, Map 196, on file at Coconino County Recorder's Office.
14.954	<p>The C-W-E-W 1/256 sec. cor. of sec. 35, established by Wilfred P. Hanson, Arizona R.L.S. No. 2473, in 1969, according to Case 2, Map 196, on file at Coconino County Recorder's Office, monumented with a rebar, 16 ins. long, 1/2 diam., firmly set, projecting 1 in. above ground. This is accepted as a careful and faithful establishment of the cor. position.</p> <p>At the corner point</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, in a collar of stone, with brass cap mkd.</p> <p style="text-align: center;">T 23 N R 6 E S 35 C-W-E-W 1/256</p> <p style="text-align: center;">2014</p> <p>from which</p> <p style="padding-left: 40px;">A ponderosa pine, 12 ins. diam., bears S. 40° W., 96.5 lks. dist., mkd. X at breast height and BT at base.</p> <p style="padding-left: 40px;">A ponderosa pine, 24 ins. diam., bears N. 65° W., 82 lks. dist., mkd. X at breast height and BT at base.</p> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p> <p>Deposit the rebar inside the stainless steel post.</p> <p>Set a steel fence post, with attached USFS signs # 54-2 and # 54-9, SW of cor.</p> <hr style="width: 20%; margin: 10px auto;"/> <p>N. 89°43' W., beginning new measurement.</p> <p>Continuing on the E. and W. center line of sec. 35.</p>

Subdivision of Section 35,  
T. 23 N., R. 6 E., Gila and Salt River Meridian, Arizona

CHAINS	
4.99	<p>The center W. 1/16 sec. cor. of sec. 35, monumented with a stainless steel post, 2 1/2 ins. diam., firmly set, projecting 6 ins. above ground, with brass cap mkd. T23N R6E W 1/16 S35 1985, with a steel fence post nearby.</p> <p>from which the bearing trees mkd. in 1985</p> <p style="padding-left: 40px;">A ponderosa pine, 22 ins. diam., bears S. 44° E., 50 lks. dist., with 2 healed blaze and 1 BT tag.</p> <p style="padding-left: 40px;">A double ponderosa pine, 20 ins. diam., sly. trunk, bears S. 20 1/2° W., 47.5 lks. dist., with a healed blaze.</p> <p>Add the marks 2014 to the brass cap.</p> <p>Set a steel fence post, with attached USFS sign # 54-9, W. of cor.</p> <hr style="width: 20%; margin: 10px auto;"/> <p>N. 89°44' W., beginning new measurement.</p> <p>Continuing on the E. and W. center line of sec. 35.</p>
10.00	<p>The C-W-W 1/64 sec. cor. of sec. 35, monumented with a stainless steel post, 2 1/2 ins. diam., firmly set, projecting 4 ins. above ground, with brass cap mkd. S35 C-W-W 1/64 1985, with a steel fence post nearby.</p> <p>from which the bearing trees mkd. in 1985</p> <p style="padding-left: 40px;">A ponderosa pine, 24 ins. diam., bears S. 65 1/2° E., 95 lks. dist., with 2 healed blaze and 1 BT tag.</p> <p style="padding-left: 40px;">A ponderosa pine, 22 ins. diam., bears S. 23° W., 66 lks. dist., with a healed blaze and 1 BT tag.</p> <p>Add the marks T23N R6E 2014 to the brass cap.</p> <p>Attached USFS sign # 54-9 to the steel fence post.</p> <hr style="width: 20%; margin: 10px auto;"/> <p>N. 89°44' W., beginning new measurement.</p> <p>Continuing on the E. and W. center line of sec. 35.</p>
9.978	<p>The 1/4 sec. cor. of secs. 34 and 35.</p> <hr style="width: 80%; margin: 10px auto;"/> <p style="text-align: center;">SW 1/4</p> <hr style="width: 20%; margin: 10px auto;"/> <p>From the W. 1/16 sec. cor. of secs. 2 and 35, on the S. bdy. of the Tp.</p>

Subdivision of Section 35,  
T. 23 N., R. 6 E., Gila and Salt River Meridian, Arizona

CHAINS	
7.713	<p>North, on the N. and S. center line of the SW 1/4 of sec. 35.</p> <p>Point for AP 1, lot 5, sec. 35.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 22 ins. in the ground to bedrock, with brass cap mkd.</p> <p style="text-align: center;">T 23 N R 6 E</p> <p style="text-align: center;">S 35</p> <div style="text-align: center; border-left: 1px solid black; border-bottom: 1px solid black; padding-left: 20px; padding-bottom: 20px;"> <p>AP 1 L 5</p> </div> <p style="text-align: center;">2014</p> <p>Deposit a magnet, in a pink plastic case, at the base of the stainless steel post.</p> <p>Set a steel fence post, with attached USFS signs # 54-2 and # 54-9, SE of cor.</p> <p>The cor. is located 6.5 lks. W. of a wire fence, bears N. and S.</p> <p>Entering patented lands.</p>
9.985	<p>The C-S-SW 1/64 sec. cor. of sec. 35, established by Charles Dryden, Arizona R.L.S. No. 13010, date unknown, monumented with rebar, 1/2 in. diam., firmly set, 3 ins. below the surface of the ground, with aluminum cap, 1 1/2 ins. diam., mkd. ARENCO PE 8218 LS 13010. This is accepted as a careful and faithful establishment of the cor. position.</p> <p>At the corner point</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, in a collar of stone, with brass cap mkd.</p> <p style="text-align: center;">T 23 N R 6 E</p> <p style="text-align: center;">S 35</p> <p style="text-align: center;">C-S-SW</p> <p style="text-align: center;">1/64</p> <p style="text-align: center;">2014</p> <p>Deposit a magnet, in a pink plastic case, at the base of the stainless steel post.</p> <p>Bury the rebar with the aluminum cap, inverted alongside the stainless steel post.</p> <p>Set a steel fence post, with attached USFS signs # 54-2 and # 54-9, NW of cor.</p>

Subdivision of Section 35,  
T. 23 N., R. 6 E., Gila and Salt River Meridian, Arizona

CHAINS	
	<p>The cor. is located 2.3 lks. N. 55° E. from a fence corner, wire, with fences extending irregularly S. 20° E. and N. 85° W. and 1.6 lks. S. 74° E. from a "T" post that is projecting 8 ins. above ground.</p> <hr style="width: 20%; margin: 10px auto;"/> <p>North, beginning new measurement.</p> <p>Continuing on the N. and S. center line of the SW 1/4 of sec. 35.</p> <p>Leaving patented lands.</p>
9.985	<p>The SW 1/16 sec. cor. of sec. 35, monumented with a stainless steel post, 2 1/2 ins. diam., firmly set, projecting 7 ins. above ground, with brass cap mkd. T23N R6E SW 1/16 S35 1985.</p> <p>from which the bearing trees mkd. in 1985</p> <p style="padding-left: 40px;">A ponderosa pine, 22 ins. diam., bears N. 54° E., 94 lks. dist., with no marks visible and 1 BT tag.</p> <p style="padding-left: 40px;">A ponderosa pine, 24 ins. diam., bears N. 40 1/4° W., 89.5 lks. dist., with a healed blaze and 1 BT tag.</p> <p>Add the marks 2014 to the brass cap.</p> <p>Set a steel fence post, with attached USFS sign # 54-9, N. of cor.</p> <hr style="width: 20%; margin: 10px auto;"/> <p>N. 0°01' W., beginning new measurement.</p> <p>Continuing on the N. and S. center line of the SW 1/4 of sec. 35.</p>
19.974	<p>The center W 1/16 sec. cor. of sec. 35.</p> <hr style="width: 20%; margin: 10px auto;"/> <p>From the center S. 1/16 sec. cor. of sec. 35.</p> <p>N. 89°49' W., on the E. and W. center line of the SW 1/4 of sec. 35.</p>
6.247	<p>Point for AP 3, lot 5, sec. 35.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 18 ins. in the ground, in a mound of stone, 2 1/2 ft. base, to top, with brass cap mkd.</p>

Subdivision of Section 35,  
T. 23 N., R. 6 E., Gila and Salt River Meridian, Arizona

CHAINS	
	T 23 N R 6 E  S 35 <span style="display: inline-block; border-left: 1px solid black; border-top: 1px solid black; padding-left: 5px; vertical-align: middle;">             AP 3 L 5           </span>  2014
	<p>from which</p> <p style="padding-left: 40px;">A ponderosa pine, 23 ins. diam., bears N. 25° E., 43 lks. dist., mkd. X at breast height and BT at base.</p> <p style="padding-left: 40px;">A ponderosa pine, 11 ins. diam., bears N. 30° W., 90.5 lks. dist., mkd. X at breast height and BT at base.</p> <p>Deposit a magnet, in a pink plastic case, at the base of the stainless steel post.</p> <p>Set a steel fence post, with attached USFS signs # 54-2 and # 54-9, NE of cor.</p> <p>From this cor., a 60D nail, of unknown origin, bears N. 22°38' E., 1.3 lks. dist.</p>
7.85	Wire fence, 4 ft. high, bears S. 35° E. and N. 35° W.
10.15	Wire fence, 3 strand, bears S. 25° E. and N. 25° W.
12.445	<p>Point for AP 1, lot 4, sec. 35.</p> <p>Chisel an X on the S. face a boulder, 3 x 2 ft., projecting 18 ins. above ground.</p> <p>from which</p> <p style="padding-left: 40px;">A 60D nail, 10 ins. long, set 10 ins. in the ground for a reference monument, bears N. 45°03' E., 32.9 ft. dist. with attached brass washer, 1 1/2 ins. diam., mkd. BLM 2014. Deposit a magnet, in a pink plastic case, alongside the nail. Set a steel fence post, with attached USFS sign # 54-9, NE of cor.</p> <p style="padding-left: 40px;">A stainless steel post, 28 ins. long, 2 1/2 ins. diam., set 21 ins. in the ground, in a mound of stone, 2 ft. base, to top of brass cap, for a reference monument, bears N. 44°56' W., 33.0 ft. dist. brass cap mkd. RM T23N R6E 33.0 FT TO AP 1 L4 S35 2014 and an arrow pointing to the cor. Deposit a magnet, in a pink plastic case, at the base of the stainless steel post. Set a steel fence post, with attached USFS sign # 54-9, NW of cor.</p>

Subdivision of Section 35,  
T. 23 N., R. 6 E., Gila and Salt River Meridian, Arizona

CHAINS	
	<p>Set a steel fence post with attached USFS signs # 54-2 and # 54-9, NW of cor.</p> <p>From this cor. a small X mark on the same boulder, of unknown origin, bears N. 1°38' E., 1.3 lks. dist.</p>
19.93	<p>The SW 1/16 sec. cor. of sec. 35.</p> <hr style="width: 20%; margin: 10px auto;"/> <p>N. 89°49' W., beginning new measurement.</p>
19.948	<p>The S. 1/16 sec. cor. of secs. 34 and 35.</p> <hr style="width: 60%; margin: 10px auto;"/> <p>From the C-S-SW 1/64 sec. cor. of sec. 35.</p> <p>N. 89°51' W., on the E. and W. of the SW 1/4 of the SW 1/4 of sec. 35.</p>
19.937	<p>The S-S 1/64 sec. cor. of secs. 34 and 35.</p> <hr style="width: 60%; margin: 10px auto;"/> <p style="text-align: center;">NW 1/4</p> <hr style="width: 20%; margin: 10px auto;"/> <p>From the center W. 1/16 sec. cor. of sec. 35.</p> <p>N. 0°10' E., on the N. and S. center line of the NW 1/4 of sec. 35.</p>
9.71	<p>Point for AP 1A, lot 3, sec. 35, not monumented.</p> <p>Entering patented lands.</p>
10.162	<p>Point for the C-S-NW 1/64 sec. cor. of sec. 35, not monumented.</p>
10.618	<p>A rebar, 1/2 diam., firmly set, 2 ins. below the surface of the ground, bears West, 2 lks. dist.</p>
20.324	<p>The NW 1/16 sec. cor. of sec. 35, monumented with a stainless steel post, 28 ins. long, 2 1/2 ins. diam., bent to NW, with a brass cap detached and nearby, mkd. T23N R6E NW 1/16 S35 1985, with a magnet, in a blue plastic case and a rebar 30 ins. long, 1/2 in. diam., with aluminum cap, 1 1/2 ins. diam., with marks illegible, at the base of the stainless steel post.</p> <p>At the corner point</p> <p>Set an aluminum post, 17 ins. long, 2 1/2 ins. diam., 9 ins. below the surface of gravel road, with alum. cap mkd.</p>

Subdivision of Section 35,  
T. 23 N., R. 6 E., Gila and Salt River Meridian, Arizona

CHAINS	
	T 23 N R 6 E NW 1/16 S 35 2014
	from which
	A ponderosa pine, 24 ins. diam., bears N. 55° E., 95 lks. dist., mkd. X at breast height and BT at base.
	A ponderosa pine, 26 ins. diam., bears N. 75° E., 85 lks. dist., mkd. X at breast height and BT at base.
	Redeposit the magnet, in a blue plastic case, at the base of the aluminum post.
	Remove the stainless steel post, the brass cap, and the rebar with the aluminum cap from the field.
	The cor. is located on the left edge of the gravel road.
	_____
	N. 0°14' E., beginning new measurement.
	Thence along a portion of the boundary of Coconino National Forest.
3.384	A rebar, 1/2 in. diam., firmly set, flush with the surface of the ground, with aluminum cap, 1 1/2 ins. diam., mkd. LS 14671, established by Kenneth Krenke, Arizona R.L.S. No. 14671, date unknown.
5.08	A rebar, 1/2 in. diam., firmly set, projecting 5 ins. above ground, with aluminum cap, 1 1/2 ins. diam., mkd. RLS 14671, with a "T" post nearby, established by Kenneth Krenke, Arizona R.L.S. No. 14671, date unknown.
6.765	A rebar, 1/2 in. diam., firmly set, flush with the surface of the ground, with aluminum cap, 1 1/2 ins. diam., mkd. MAR LS 14671, established by Kenneth Krenke, Arizona R.L.S. No. 14671, date unknown.
10.15	The C-N-NW 1/64 sec. cor. of sec. 35, monumented with a stainless steel post, 2 1/2 ins. diam., firmly set, projecting 6 ins. above ground, with brass cap mkd. S35 C-N-NW 1/64 1985, with a steel fence post nearby.
	from which the bearing trees mkd. in 1985
	A ponderosa pine, 22 ins. diam., bears N. 2 3/4° E., 95.5 lks. dist., with 2 healed blaze, found BT tag nearby.



Subdivision of Section 35,  
T. 23 N., R. 6 E., Gila and Salt River Meridian, Arizona

CHAINS	<p style="text-align: center;">A ponderosa pine, 29 ins. diam., bears N. 36 1/2° W., 1.445 chs. dist., with a healed blaze and 1 BT tag.</p> <p>Add the marks T23N R6E 2014 to the brass cap.</p> <p>Set a steel fence post, with attached USFS signs # 54-2 and # 54-9, NE of cor.</p> <hr style="width: 20%; margin: 10px auto;"/> <p>N. 0°15' E., beginning new measurement.</p> <p>Thence across Coconino National Forest.</p>
10.168	<p>The W. 1/16 sec. cor. of secs. 26 and 35.</p> <hr style="width: 80%; margin: 10px auto;"/> <p>From the center N. 1/16 sec. cor. of sec. 35.</p> <p>N. 89°25' W., on the E. and W. center line of the NW 1/4 of sec. 35.</p>
4.98	<p>The C-E-E-NW 1/256 sec. cor. of sec. 35, identical with the NW cor. of parcel 4 of Snow Bowl Estates, established by Wilfred P. Hanson, Arizona R.L.S. No. 2473, in 1969, according to Case 2, Map 196, on file at Coconino County Recorder's Office, monumented with rebar, 16 ins. long, 1/2 in. diam., firmly set, projecting 2 ins. above ground, This is accepted as a careful and faithful establishment of the cor. position.</p> <p>At the corner point</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, in a collar of stone, with brass cap mkd.</p> <p style="text-align: center;">T 23 N R 6 E S 35 C-E-E-NW 1/256  2014</p> <p>from which</p> <p style="padding-left: 40px;">A ponderosa pine, 26 ins. diam., bears N. 20° E., 80.5 lks. dist., mkd. X at breast height and BT at base.</p> <p style="padding-left: 40px;">A ponderosa pine, 23 ins. diam., bears S. 80° E., 67 lks. dist., mkd. X at breast height and BT at base.</p> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p> <p>Deposit the rebar inside the stainless steel post.</p>

Subdivision of Section 35,  
T. 23 N., R. 6 E., Gila and Salt River Meridian, Arizona

CHAINS

Set a steel fence post, with attached USFS signs # 54-2 and # 54-9, NE of cor.

---

N. 89°25' W., beginning new measurement.

Continuing on the E. and W. center line of the NW 1/4 of sec. 35, along a portion of the boundary of Coconino National Forest.

4.97 The C-E-N-NW 1/64 sec. cor. of sec. 35, identical with the NW cor. of parcel 3 of Snow Bowl Estates, at proportionate dist., 4 point intersection, using SW cor. of parcel 3 of Snow Bowl Estates, the NE-NW 1/64 sec. cor. of sec. 35, the NW 1/16 sec. cor. of sec. 35 and the center N. 1/16 sec. cor. of sec. 35, there is no remaining evidence of cor. established by Wilfred P. Hanson, Arizona R.L.S. No. 2473, in 1969.

Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.

T 23 N R 6 E

S 35

C-E-NW

1/64

2014

from which

A ponderosa pine, 24 ins. diam., bears N. 18° E., 2.02 chs. dist., mkd. X at breast height and BT at base.

A ponderosa pine, 10 ins. diam., bears N. 65° E., 1.69 chs, dist., mkd. X at breast height and BT at base.

Deposit a magnet, in a white plastic case, at the base of the stainless steel post.

Set a steel fence post, with attached USFS signs # 54-2 and # 54-9, NE of cor.

The cor. is located 20 lks. E. of gravel road, 8 ft. wide, bears S. 10° E. and N. 10° W.

From this cor., the SW cor. of parcel 3 of Snow Bowl Estates, bears S. 0°09' W., 9.678 chs. dist., established by Wilfred P. Hanson, Arizona R.L.S. No. 2473, in 1969, according to Case 2, Map 196, on file at Coconino County Recorder's Office. monumented with a rebar, 1/2 in. diam., firmly set, projecting 1 in. above ground.

---

Subdivision of Section 35,  
T. 23 N., R. 6 E., Gila and Salt River Meridian, Arizona

CHAINS	<p>N. 89°25' W., beginning new measurement.</p> <p>Continuing on the E. and W. center line of the NW 1/4 of sec. 35.</p> <p>Entering patented lands.</p> <p>4.974 The C-W-E-NW 1/256 sec. cor. of sec. 35, monumented with a rebar, 17 ins. long, 1/2 in. diam., firmly set, flush with the surface of the ground, with a "T" post nearby, found and accepted by Marilyn J. Weissman, Arizona R.L.S. No. 27254, in 2014, according Instrument # 3702774, on file at Coconino County Recorder's Office. This is accepted as a careful and faithful establishment of the cor. position.</p> <p>At the corner point</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, in a collar of stone, with brass cap mkd.</p> <p style="text-align: center;">T 23 N R 6 E S 35 C-W-E-NW 1/256 2014</p> <p>from which</p> <p style="padding-left: 40px;">A ponderosa pine, 24 ins. diam., bears N. 45° W., 1.57 chs. dist., mkd. X at breast height and BT at base.</p> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p> <p>Deposit the rebar inside the stainless steel post.</p> <p>Set a steel fence post, with attached USFS signs # 54-2 and # 54-9, NW of cor.</p> <p>From this cor., a rebar, 1/2 in. diam., firmly set, projecting 3 ins. above ground, with plastic cap, 1 in. diam., mkd. RLS 14657, bears S. 9°26' E. 1.8 lks, established by James Andrews, Arizona R.L.S. No, 14657, date unknown.</p> <hr style="width: 20%; margin: 10px auto;"/> <p>N. 89°25' W., beginning new measurement.</p> <p>Continuing on the E. and W. center line of the NW 1/4 of sec. 35, along a portion of the boundary of Coconino National Forest.</p>
--------	--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------

Subdivision of Section 35,  
T. 23 N., R. 6 E., Gila and Salt River Meridian, Arizona

CHAINS	
4.974	<p>The NW 1/16 sec. cor. of sec. 35.</p> <hr style="width: 20%; margin: 10px auto;"/> <p>N. 89°27' W., beginning new measurement.</p> <p>Continuing on the E. and W. center line of the NW 1/4 of sec. 35.</p> <p>Entering patented lands.</p>
4.971	<p>Point for the C-E-W-NW 1/256 sec. cor. of sec. 35.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T 23 N R 6 E S 35 C-E-W-NW 1/256  2014</p> <p>from which</p> <p style="padding-left: 40px;">A ponderosa pine, 18 ins. diam., bears S. 20° W., 1.455 chs. dist., mkd. X at breast height and BT at base.</p> <p style="padding-left: 40px;">A ponderosa pine, 18 ins. diam., bears S. 65° W., 65 lks. dist., mkd. X at breast height and BT at base.</p> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p> <p>Set a steel fence post, with attached USFS signs # 54-2 and # 54-9, SW of cor.</p> <p>Thence along a portion of the boundary of Coconino National Forest.</p>
9.942	<p>The C-W-NW 1/64 sec. cor. of sec. 35, monumented with a stainless steel post, 2 1/2 ins. diam., firmly set, projecting 5 ins. above ground, with brass cap mkd. S35 C-W-NW 1/64 1985, with a steel fence post nearby.</p> <p>from which</p> <p style="padding-left: 40px;">A ponderosa pine, 14 ins. diam., bears S. 35 1/4° W., 1.305 chs. dist., with 2 healed blaze and 1 BT Tag nearby.</p>

Subdivision of Section 35,  
T. 23 N., R. 6 E., Gila and Salt River Meridian, Arizona

CHAINS	
	<p style="text-align: center;">A ponderosa pine, 21 ins. diam., bears N. 46 1/2° W., 1.01 chs. dist., with a healed blaze.</p> <p>Add the marks T23N R6E 2014 to the brass cap.</p> <p>Set a steel fence post, with attached USFS signs # 54-2 and # 54-9, SW of cor.</p> <hr style="width: 20%; margin: 10px auto;"/> <p>N. 89°25' W., beginning new measurement.</p> <p>Continuing on the E. and W. center line of the NW 1/4 of sec. 35.</p>
9.946	<p>The N. 1/16 sec. cor. of secs. 34 and 35.</p> <hr style="width: 60%; margin: 10px auto;"/> <p>From the C-E-NW 1/64 sec. cor. of sec. 35.</p> <p>N. 0°09' E., on the N. and S. center line of the NE 1/4 of the NW 1/4 of sec. 35.</p>
3.387	<p>A rebar, 1/2 in. diam. firmly set, projecting 4 ins. above ground, with plastic cap, 1 in. diam., marks illegible.</p>
10.125	<p>The NE-NW 1/64 sec. cor. of sec. 35, monumented with a rebar, 18 ins. long, 1/2 in. diam., firmly set, leaning NW, flush with the surface of the ground, found and accepted by Marilyn J. Weissman, Arizona R.L.S. No. 27254, in 2014, according Instrument # 3702774, on file at Coconino County Recorder's Office. This is accepted as a careful and faithful establishment of the cor. position.</p> <p>At the corner point</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T 23 N R 6 E S 35 NE-NW 1/64  2014</p> <p>from which</p> <p style="text-align: center;">A ponderosa pine, 11 ins. diam., bears N. 30° E., 72.5 lks. dist., mkd. X at breast height and BT at base.</p> <p style="text-align: center;">A ponderosa pine, 15 ins. diam., bears N. 80° E., 98 lks. dist., mkd. X at breast height and BT at base.</p>

Subdivision of Section 35,  
T. 23 N., R. 6 E., Gila and Salt River Meridian, Arizona

CHAINS	
	<p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p> <p>Bury the rebar, horizontally alongside the stainless steel post.</p> <p>Set a steel fence post, with attached USFS signs # 54-2 and # 54-9, NE of cor.</p> <hr/> <p>From the C-N-N 1/64 sec. cor. of sec. 35.</p> <p>N. 89°18' W., on the E. and W. center line of the NE 1/4 of the NW 1/4 of sec. 35.</p>
9.931	<p>The NE-NW 1/64 sec. cor. of sec. 35.</p> <hr/> <p>N. 89°18' W., beginning new measurement.</p> <p>Continuing on the E. and W. center line of the NE 1/4 of the NW 1/4 of sec. 35, along a portion of the boundary of Coconino National Forest.</p>
0.019	<p>A rebar, 1/2 in. diam., firmly set, leaning S., projecting 2 ins. above ground, with plastic cap, 1 in. diam., mkd. RLS 14657, established by James Andrews, Arizona R.L.S. No, 14657, date unknown.</p>
2.491	<p>A rebar, 1/2 in. diam., firmly set, projecting 2 ins. above ground.</p>
4.964	<p>The C-W-NE-NW 1/256 sec. cor. of sec. 35, established by Kenneth Krenke, Arizona R.L.S. No. 14671, date unknown, monumented with a rebar, 27 ins. long, 1/2 in. diam., firmly set, flush with the surface of the ground, with aluminum cap, 1 1/2 ins. diam., mkd. LS 14671. This is accepted as a careful and faithful establishment of the cor. position.</p> <p>At the corner point</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 22 ins. in the ground, in a mound of stone, 2 1/2 ft. base, to top, with brass cap mkd.</p> <p style="text-align: center;">T 23 N R 6 E S 35 C-W-NE-NW 1/256  2014</p> <p>from which</p>

Subdivision of Section 35,  
T. 23 N., R. 6 E., Gila and Salt River Meridian, Arizona

CHAINS	
	<p>A ponderosa pine, 14 ins. diam., bears N. 15° E., 1.265 chs. dist., mkd. X at breast height and BT at base.</p> <p>A ponderosa pine, 18 ins. diam., bears N. 45° W., 1.105 chs. dist., mkd. X at breast height and BT at base.</p> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p> <p>Bury the rebar, horizontally alongside the stainless steel post.</p> <p>Set a steel fence post, with attached USFS signs # 54-2 and # 54-9, NW of cor.</p> <hr style="width: 20%; margin: 10px auto;"/> <p>N. 89°18' W., beginning new measurement.</p> <p>Continuing on the E. and W. center line of the NE 1/4 of the NW 1/4 of sec. 35, across Coconino National Forest.</p>
4.97	<p>The C-N-NW 1/64 sec. cor. of sec. 35.</p> <hr style="width: 80%; margin: 10px auto;"/> <p>From the C-W-E-NW 1/256 sec. cor. of sec. 35.</p> <p>N. 0°13' E., on the N. and S. center line of SW 1/4 of the NE 1/4 of the NW 1/4 of sec. 35.</p>
3.354	<p>A rebar, 1/2 in. diam., firmly set, projecting 2 ins. above ground, with plastic cap, 1 in. diam., mkd. RLS 14657, established by James Andrews, Arizona R.L.S. No, 14657, date unknown.</p>
3.375	<p>A rebar, 1/2 in. diam., firmly set, 2 ins. below the surface of the ground, with aluminum cap, 1 1/2 ins. diam., mkd. LS 14671. Established by Kenneth Krenke, Arizona R.L.S. No. 14671, date unknown.</p>
10.134	<p>The C-W-NE-NW 1/256 sec. cor. of sec. 35.</p> <hr style="width: 80%; margin: 10px auto;"/> <p>From the C-W-W 1/64 sec. cor. of sec. 35.</p> <p>N. 0°20' E., on the N. and S. center line of the SW 1/4 of the NW 1/4 of sec. 35.</p>

Subdivision of Section 35,  
T. 23 N., R. 6 E., Gila and Salt River Meridian, Arizona

CHAINS				
9.740	<p>AP 2, lot 3, sec. 35, identical with the NW cor. of parcel 2 of Snow Bowl Estates, established by Wilfred P. Hanson, Arizona R.L.S. No. 2473, in 1969, according to Case 2, Map 196, on file at Coconino County Recorder's Office, monumented with a rebar, 16 ins. long, 1/2 in. diam., firmly set, projecting 1 in. above ground, with brass tag mkd. LS 2473.</p> <p>At the corner point</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 20 ins. in the ground, in a mound of stone, 2 1/2 ft. base, to top, with brass cap mkd.</p> <p style="text-align: center;">T 23 N R 6 E</p> <table style="margin-left: auto; margin-right: auto; border-collapse: collapse;"> <tr> <td style="border-right: 1px solid black; padding: 2px 5px;">S 35</td> </tr> <tr> <td style="border-right: 1px solid black; padding: 2px 5px;">AP 2</td> </tr> <tr> <td style="border-right: 1px solid black; padding: 2px 5px;">L 3</td> </tr> </table> <p style="text-align: center;">2014</p> <p>Deposit a magnet, in a white plastic case and the, at the base of the stainless steel post.</p> <p>Deposit the rebar with brass tag inside the stainless steel post.</p> <p>Set a steel fence post, with attached USFS signs # 54-2 and # 54-9, SW of cor.</p> <hr style="width: 20%; margin: 10px auto;"/> <p>N. 0°20' E., beginning new measurement.</p> <p>Continuing on the N. and S. center line of the SW 1/4 of the NW 1/4 of sec. 35, along a portion of the boundary of Coconino National Forest.</p>	S 35	AP 2	L 3
S 35				
AP 2				
L 3				
0.447	Point for the SW-NW 1/64 sec. cor. of sec. 35, not monumented.			
0.907	<p>AP 1, lot 1, sec. 35, identical with the SW cor. of parcel 1 of Snow Bowl Estates, established by Wilfred P. Hanson, Arizona R.L.S. No. 2473, in 1969, according to Case 2, Map 196, on file at Coconino County Recorder's Office, monumented with a rebar, 16 ins. long, 1/2 in. diam., firmly set, projecting 2 ins. above ground, with a brass tag mkd. LS 2473.</p> <p>At the corner point</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, in a collar of stone, with brass cap mkd.</p>			



Subdivision of Section 35,  
T. 23 N., R. 6 E., Gila and Salt River Meridian, Arizona

CHAINS				
	<p>T 23 N R 6 E</p> <table style="margin-left: auto; margin-right: auto;"> <tr><td style="border-right: 1px solid black; padding-right: 5px;">L 1</td></tr> <tr><td style="border-right: 1px solid black; padding-right: 5px;">AP 2</td></tr> <tr><td style="border-right: 1px solid black; padding-right: 5px;">S 35</td></tr> </table> <p>2014</p>	L 1	AP 2	S 35
L 1				
AP 2				
S 35				
	<p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p> <p>Deposit the rebar with brass tag inside the stainless steel post.</p> <p>Set a steel fence post, with attached USFS signs # 54-2 and # 54-9, NW of cor.</p> <hr style="width: 20%; margin: 10px auto;"/> <p>N. 0°20' E., beginning new measurement.</p> <p>Continuing on the N. and S. center line of the SW 1/4 of the NW 1/4 of sec. 35.</p>			
9.724	<p>The C-W-NW 1/64 sec. cor. of sec. 35.</p> <hr style="width: 80%; margin: 10px auto;"/> <p>From the C-W-NW 1/64 sec. cor. of sec. 34.</p> <p>N. 0°20' E., on the N. and S. center line of the NW 1/4 of the NW 1/4 of sec. 35.</p>			
10.180	<p>The NW-NW 1/64 sec. cor. of sec. 35, monumented with a stainless steel post, 2 1/2 ins. diam., firmly set, projecting 4 ins. above ground, with brass cap mkd. S35 NW-NW 1/64 1985, with a steel fence post nearby.</p> <p>from which the bearing trees mkd. in 1985</p> <p style="padding-left: 40px;">A dead tree, 15 ins. diam., bears S. 82° W., 61 lks. dist., with scribe marks NW NW 1/64 S35 B visible on partially open blaze.</p> <p style="padding-left: 40px;">A ponderosa pine, 17 ins. diam., bears N. 16 3/4° W., 1.705 chs. dist., with a healed blaze.</p> <p>and a new bearing tree</p> <p style="padding-left: 40px;">A ponderosa pine, 12 ins. diam., bears S. 35° W., 1.525 chs. dist., mkd. X at breast height and BT at base.</p> <p>Add the marks T23N R6E 2014 to the brass cap.</p>			

Subdivision of Section 35,  
T. 23 N., R. 6 E., Gila and Salt River Meridian, Arizona

CHAINS										
	<p>Set a steel fence post, with attached USFS signs # 54-2 and # 54-9, NW of cor.</p> <hr/> <p>S. 89°17' E., on the E. and W. center line of the NW 1/4 of the NW 1/4 of sec. 35, along the N. bdy. of Snow Bowl Estates.</p>									
4.962	<p>The C-E-NW-NW 1/256 sec. cor. of sec. 35, established by Kenneth Krenke, Arizona R.L.S. No. 14671, date unknown, and accepted by Christopher J. Franks, Arizona R.L.S. No. 22258, in 1990, according to Book 8, Page 78, on file at Coconino County Recorder's Office, monumented with a rebar, 1/2 in. diam., firmly set, projecting 6 ins. above ground, with aluminum cap mkd. L.S. 14671. This is accepted as a careful and faithful establishment of the cor. position.</p>									
9.925	<p>The C-N-NW 1/64 sec. cor. of sec. 35.</p> <hr/> <p style="text-align: center;"><b>Metes-and-Bounds Survey in Section 35, T. 23 N., R. 6 E., Gila and Salt River Meridian, Arizona</b></p> <hr/> <p style="text-align: center;">In the SE 1/4 of the SW 1/4</p> <hr/> <p>From the C-S-SW 1/64 sec. cor. of sec. 35, hereinbefore described.</p> <p>N. 36°54' E., on the E. boundary of lot 4 of sec. 35.</p>									
12.46	<p>AP 1, lot 4, sec. 35.</p> <hr/> <p>From AP 1, lot 5, sec. 35, hereinbefore described.</p> <p>S. 89°49' E., on the N. boundary of lot 5 of sec. 35.</p>									
13.683	<p>Point for AP 2, lot 5, sec. 35.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center; margin-top: 20px;"> <p>T 23 N R 6 E</p> <table style="margin: auto; border-collapse: collapse;"> <tr> <td style="border: 1px solid black; padding: 2px 10px;">S 35</td> <td style="padding: 0 5px;"> </td> <td></td> </tr> <tr> <td style="border: 1px solid black; padding: 2px 10px;"></td> <td style="padding: 0 5px;"> </td> <td style="padding: 0 5px;">AP 2</td> </tr> <tr> <td style="border: 1px solid black; padding: 2px 10px;"></td> <td style="padding: 0 5px;"> </td> <td style="padding: 0 5px;">L 5</td> </tr> </table> </div> <p style="text-align: center; margin-top: 20px;">2014</p>	S 35					AP 2			L 5
S 35										
		AP 2								
		L 5								


Metes-and-Bounds Survey in Section 35,  
T. 23 N., R. 6 E., Gila and Salt River Meridian, Arizona

CHAINS	<p>A ponderosa pine, 18 ins. diam., bears N. 37° E., 2.36 chs. dist., mkd. X at breast height and BT at base.</p> <p>A ponderosa pine, 15 ins. diam., bears S. 83° E., 2.385 chs. dist., mkd. X at breast height and BT at base.</p> <p>Deposit a magnet, in a pink plastic case, at the base of the stainless steel post.</p> <p>Set a steel fence post, with attached USFS signs # 54-2 and # 54-9, SE of cor.</p> <hr style="width: 20%; margin: 10px auto;"/> <p>North, beginning new measurement.</p> <p>Thence on the W. boundary of lot 5 of sec. 35.</p>		
12.259	<p>AP 3, lot 5, sec. 35.</p> <hr style="width: 20%; margin: 10px auto;"/> <p style="text-align: center;">In the NE 1/4 of the SE 1/4 of the NW 1/4</p> <hr style="width: 20%; margin: 10px auto;"/> <p>From AP 2, lot 2, sec. 35, identical with the SE cor. of parcel 4 of Snow Bowl Estates, hereinbefore described.</p> <p>N. 89°34' W., on the S. boundary of lot 2 sec. 35, identical with the S. boundary of parcel 4 of Snow Bowl Estates.</p>		
4.985	<p>AP 1, lot 2, sec. 35, identical with SW cor. of parcel 4 of Snow Bowl Estates, established by Wilfred P. Hanson, Arizona R.L.S. No. 2473, in 1969, according to Case 2, Map 196, on file at Coconino County Recorder's Office, monumented with a rebar, 16 ins. long, 1/2 in. diam., firmly set, 1 in. below surface of the ground, with brass tag mkd. LS 2473.</p> <p>At the corner point</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 18 ins. in the ground to bedrock, in a mound of stone, 3 1/2 ft. base, to top, with brass cap mkd.</p> <p style="text-align: center;">T 23 N R 6 E</p> <div style="text-align: center; margin: 10px 0;"> <table style="border-collapse: collapse; margin: auto;"> <tr> <td style="border-right: 1px solid black; border-bottom: 1px solid black; padding: 2px 5px;">L 2</td> </tr> <tr> <td style="border-bottom: 1px solid black; padding: 2px 5px;">AP 1</td> </tr> </table> </div> <p style="text-align: center;">S 35</p> <p style="text-align: center;">2014</p> <p>from which</p>	L 2	AP 1
L 2			
AP 1			

**Metes-and-Bounds Survey in Section 35,  
T. 23 N., R. 6 E., Gila and Salt River Meridian, Arizona**

CHAINS	
	<p>A ponderosa pine, 25 ins. diam., bears N. 35° E., 60 lks. dist., mkd. X at breast height and BT at base.</p> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p> <p>Deposit the rebar with brass tag inside the stainless steel post.</p> <p>Set a steel fence post, with attached USFS signs # 54-2 and # 54-9, NE of cor.</p> <p>The cor. is located 29 lks. N. of Pine Mountain Road, asphalt road, 10 ft. wide, bears S. 85° E. and N. 85° W.</p> <p>From this cor., a rebar, 1/2 in. diam., firmly set, 5 ins. below the surface of the ground, bears S. 0°14' W., 90.8 lks. dist.</p> <hr/> <p>N. 0°03' E., beginning new measurement.</p> <p>On the W. boundary of lot 2, identical with the W. boundary of parcel 4 of Snow Bowl Estates.</p>
9.675	<p>The C-E-E-NW 1/256 sec. cor. of sec. 25.</p> <hr/> <p style="text-align: center;">In the SW 1/4 of the SE 1/4 of the NW 1/4</p> <hr/> <p>From the C-W-E-W 1/256 sec. cor. of sec. 35, hereinbefore described.</p> <p>N. 0°03' E., on the E. boundary of lot 3 of sec. 35.</p>
4.847	<p>A rebar, 1/2 in. diam., leaning N., projecting 6 ins. above ground, bears E. 3.5 lks. dist., with plastic cap mkd. C J F LS 22258.</p>
9.700	<p>AP 1, lot 3, sec. 35, monumented with a rebar, 16 ins. long, 1/2 in. diam., firmly set, 1 in. below the surface of the ground. This is accepted as careful and faithful determination of the cor. point.</p> <p>At the corner point</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 19 ins. in the ground to bedrock, in a mound of stone, 3 1/2 ft. base, to top, with brass cap mkd.</p>

Metes-and-Bounds Survey in Section 35,  
T. 23 N., R. 6 E., Gila and Salt River Meridian, Arizona

CHAINS	
	<p style="text-align: center;">T 23 N R 6 E</p> <div style="text-align: center;">  </div> <p style="text-align: center;">2014</p> <p>from which</p> <p style="padding-left: 40px;">A ponderosa pine, 26 ins. diam., bears S. 55° W., 1.93 chs. dist., mkd. X at breast height and BT at base.</p> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p> <p>Deposit the rebar inside the stainless steel post.</p> <p>Set a steel fence post, with attached USFS signs # 54-2 and # 54-9, SW of cor.</p> <p>From this cor., a rebar, 1/2 in diam., firmly set, projecting 2 ins. above ground, bears N. 0°4' W., 90.1 lks. dist., with plastic cap, 1 in. diam., mkd R. SCHILKE RLS 28230, established by Richard Schilke, Arizona R.L.S. No. 28230, date unknown.</p> <p>From the same cor., a rebar, 1/2 in. diam., firmly set, projecting 1 in. above ground, bears N. 0°6' W., 90.8 lks. dist., with plastic cap, 1 in. diam., mkd. RLS 9078, established by Joseph Costa, Arizona R.L.S. No. 9078, date unknown.</p> <hr style="width: 20%; margin: 10px auto;"/> <p>N. 89°34' W., beginning new measurement.</p> <p>Thence on the N. boundary of lot 3 of sec. 35, identical with the southern right-of-way of Pine Mountain Road.</p> <p>4.970 Point for AP 1A, lot 3, sec. 35.</p> <hr style="width: 80%; margin: 10px auto;"/> <p style="text-align: center;">In the NE 1/4 of the SW 1/4 of the NW 1/4</p> <hr style="width: 20%; margin: 10px auto;"/> <p>From AP 1, lot 1, sec. 35, hereinbefore described.</p> <p>S. 89°33' E., on the S. boundary of lot 1 of sec. 35, identical with the northern right-of-way of Pine Mountain Road.</p> <p>4.985 Point for AP 2, lot 1, sec. 35, falls in Pine Mountain Road, asphalt, 10 ft. wide, bears S. 65° E. and N. 75° W.</p>

**Metes-and-Bounds Survey in Section 35,  
T. 23 N., R. 6 E., Gila and Salt River Meridian, Arizona**

CHAINS	
	<p>Set a railroad spike, 1 in. below the surface of asphalt, with attached brass washer, 1 1/2 ins. diam., mkd. BLM 2014.</p> <p>from which</p> <p style="padding-left: 40px;">A stainless steel post, 28 ins. long, 2 1/2 ins. diam., set 24 ins. in the ground, in a collar of stone, for a reference monument, bears N. 44°58' W., 45.0 ft. dist. with brass cap mkd. RM T23N R6E 45.0 FT TO AP 2 LOT 1 S35 2014 and an arrow pointing to the cor. Deposit a magnet, in a white plastic case, at the base of the stainless steel post. Set a steel fence post, with attached USFS sign # 54-9, NE of cor.</p> <p style="padding-left: 40px;">A stainless steel post, 28 ins. long, 2 1/2 ins. diam., set 24 ins. in the ground, in a collar of stone, for a reference monument, bears N. 44°58' W., 90.0 ft. dist. with brass cap mkd. RM T23N R6E 90.0 FT TO AP 2 LOT 1 S35 2014 and an arrow pointing to the cor. Deposit a magnet, in a white plastic case, at the base of the stainless steel post. Set a steel fence post, with attached USFS sign # 54-9, NW of cor.</p> <hr style="width: 20%; margin: 20px auto;"/> <p>N. 0°15' E., on the E. boundary of lot 1 of sec. 35.</p>
9.716	<p>The C-E-W-NW 1/256 sec. cor. of sec. 35.</p> <hr style="width: 80%; margin: 10px auto;"/> <p style="text-align: center;">In the SE 1/4 of the SW 1/4 of the NW 1/4</p> <hr style="width: 20%; margin: 10px auto;"/> <p>From AP 1A, lot 3, sec. 35.</p> <p>N. 89°34' W., on the N. boundary of lot 3 of sec. 35, identical with the southern right-of-way of Pine Mountain Road.</p>
9.974	<p>AP 2, lot 3, sec. 35, hereinbefore described.</p> <hr style="width: 80%; margin: 10px auto;"/> <p style="text-align: center;"><b>Recovery of Certain Corners, T. 23 N., R. 6 E., Gila and Salt River Meridian, Arizona</b></p> <hr style="width: 80%; margin: 10px auto;"/> <p>The 1/1024 sec. cor. of secs. 14 and 15, located 27.245 chs. N. 2°10' W. of the 1/4 sec. cor. of secs. 14 and 15, monumented with a stainless steel post, 2 1/2 ins. diam., firmly set, projecting 4 ins. above ground, with brass cap mkd. 1/1024 1985, with a steel fence post, with attached USFS signs # 54-2 and # 54-9, SW of cor.</p> <p>from which the bearing trees mkd. in 1985</p>

**Recovery of Certain Corners,  
T. 23 N., R. 6 E., Gila and Salt River Meridian, Arizona**

## CHAINS

A Douglas fir, 9 ins. diam., bears S. 60 1/4° E., 20.5 lks. dist., with a healed blaze.

A stump hole, 18 ins. diam., bears N. 85 1/4 ° W., 34 lks. dist., with a downed Douglas fir alongside, with a healed blaze and 1 BT tag. Set a steel fence post, with attached BT tag, at the center of the stump hole.

---

The cor. of secs. 10, 11, 14, and 15, monumented with an iron post, 2 ins. diam., firmly set, projecting 6 ins. above ground, with brass cap mkd. T23N R6E S10 S11 S15 S14 1985 1943, with a steel fence post, with attached USFS signs # 54-2 and # 54-9, NW of cor.

from which the remains of the original bearing trees

A ponderosa pine stump, 24 ins. diam., bears S. 79° E., 46 lks. dist., with scribe marks 6E S14 BT and 1 BT tag.

The decayed remains of a pine stump, bears S. 62 1/4° W., 67 lks. dist., with a downed pine alongside, no marks remaining. (Record: 65 lks.) Set a steel fence post, with attached BT tag, at the center of the stump.

and the bearing trees mkd. in 1943

A ponderosa pine snag, 11 ins. diam., bears N. 79 1/4° E., 42 lks. dist., with scribe marks T23N R6E S11 BT visible on partially open blaze and 1 BT tag. (Record: 14 ins. diam., in 1985)

A ponderosa pine, 32 ins. diam., bears S. 75 1/2° W., 1.47 chs. dist., with scribe marks visible but no legible on partially open blaze and 1 BT tag.

A ponderosa pine stump, 24 ins. diam., bears N. 32° W., 64 lks. dist., with scribe marks S10 BT visible and 1 BT tag.

and the bearing trees mkd. in 1985

A ponderosa pine, 14 ins. diam., bears N. 24 3/4° E., 25.5 lks. dist., with a healed blaze and 1 BT tag.

A ponderosa pine, 8 ins. diam., bears N. 52° W., 1.055 chs. dist., with a healed blaze.

---

The E. 1/16 sec. cor. of secs. 11 and 14, monumented with a stainless steel post, 2 1/2 ins. diam., firmly set, 4 ins. below the surface of the ground and rotated 180°, with brass cap mkd. T23N R6E E 1/16 S11 S14 1985.

**Recovery of Certain Corners,  
T. 23 N., R. 6 E., Gila and Salt River Meridian, Arizona**

## CHAINS

from which the bearing trees mkd. in 1985

A ponderosa pine, 13 ins. diam., bears N. 29° E., 65.5 lks. dist., with 2 healed blaze and 1 BT tag. (Record: mkd. E 1/16 S11 BT)

A ponderosa pine, 11 ins. diam., bears N. 29° W., 54.5 lks. dist., with scribe marks S11 BT visible on partially open blaze and 1 BT tag. (Record: mkd. X BT)

Set a steel fence post, with attached USFS signs # 54-2 and # 54-9, W. of cor.

The witness point on line bet. secs 11 and 14, on the center of U.S. Forest Service Route 151, graded, bears N. and S., monumented with an aluminum post, 3/4 in. diam., firmly set, 4 ins. below the surface of the road, with aluminum cap mkd. WP S11 S14 1985.

from which the reference monuments set in 1985

An aluminum post, 3/4 in. diam., firmly set, projecting 3 ins. above ground for a reference monument, bears N. 21° E., 45 ft. dist. with aluminum cap incorrectly mkd. RM 45 FT WP S14 1985 and an arrow pointing to the witness point. Remark the aluminum cap to read RM 45 FT WP S11 1985. Set a steel fence post, with attached USFS sign # 54-9, NE of reference monument.

An aluminum post, 3/4 in. diam., firmly set, projecting 5 ins. above ground for a reference monument, bears N. 39° W., 45.2 ft. dist. with aluminum cap incorrectly mkd. RM 45.2 FT WP S14 1985 and an arrow pointing to the witness point. Remark the aluminum cap to read RM 45.2 FT WP S11 1985. Set a steel fence post, with attached USFS sign # 54-9, NW of reference monument.

The 1/4 sec. cor. of secs. 22 and 27, monumented with an iron post, 1 in. diam., firmly set, projecting 6 ins. above ground, in a mound of stone, 2 1/2 ft. base, to top, with brass cap mkd. 1/4 S22 S27 1985 1943.

from which the bearing trees mkd. in 1943

A downed ponderosa snag, 26 ins. diam., bears N. 1/2° E., 46 lks. dist., with no marks visible.

A limber pine, 18 ins. diam., bears S. 28 1/2° E., 28 lks. dist., with a healed blaze and 2 BT tags.

and a bearing tree mkd. by Reid Penland, L.S. No. 11755, in 1982



**Recovery of Certain Corners,  
T. 23 N., R. 6 E., Gila and Salt River Meridian, Arizona**

## CHAINS

A ponderosa pine, 19 ins. diam., bears N. 19 1/4° E., 1.09 chs. dist., with a healed blaze and 2 BT tags.

Set a steel fence post, with attached USFS signs # 54-2 and # 54-9, NE of cor.

---

The 1/1024 sec. cor. of sec. 14, on the N. and S. center line of the NE 1/4 of sec. 14, located 12.415 chs. S. 1°39' E. of the E. 1/16 sec. cor. of secs. 11 and 14, monumented with a stainless steel post, 2 1/2 ins. diam., firmly set, projecting 6 ins. above ground, with brass cap mkd. 1/1024 1985, with a steel fence post, with attached USFS signs # 54-2 and # 54-9, W. of cor.

from which the bearing trees mkd. in 1985

A ponderosa pine, 16 ins. diam., bears S. 66 1/4° E., 80.5 lks. dist., with a healed blaze and 1 BT tag.

A stump, 18 ins. diam., 8 ins. high, bears S. 20 1/4° W., 24 lks. dist., with a downed ponderosa pine alongside, with scribe marks visible, but not legible, on partially open blaze. Set a steel fence post, with attached BT tag, at the center of the stump.

---

The 1/1024 sec. cor. of sec. 14, on the N. and S. center line of the NW 1/4 of sec. 14, located 12.397 chs. S. 1°59' E. of the W. 1/16 sec. cor. of secs. 11 and 14, monumented with a stainless steel fence post, 2 1/2 ins. diam., firmly set, flush with the surface of the ground, with brass cap mkd. 1/1024 1985.

from which

A corner of fences extending N. 65° E. and S. 89°33' W., bears S. 89°33' W., 1.07 chs. dist.

The SE cor. of a stucco and wood-framed house, bears N. 10° W., 57 lks. dist.

Set a steel fence post with attached USFS signs # 54-2 and # 54-9, W. of cor.

---

The witness point on the E. and W. center line of the N. 1/2 of the S. 1/2 of the NW 1/4 of the NW 1/4 of sec. 14, on U.S. Forest Service Route 151, bears S. 20° E. and N. 10° W., monumented with an aluminum post, 3/4 in. diam., firmly set, 2 ins. below the surface of the road and bent to NW, with the aluminum cap missing.

from which the reference monuments set in 1985

**Recovery of Certain Corners,  
T. 23 N., R. 6 E., Gila and Salt River Meridian, Arizona**

## CHAINS

An aluminum post, 3/4 in. diam., firmly set, projecting 4 ins. above ground for a reference monument, bears S. 70 1/2° E., 25 ft. dist. with an aluminum cap mkd. RM 25 FT WP 1985 and an arrow pointing to the witness point, with a steel fence post, with attached USFS sign # 54-9, SE of reference monument. Add the marks S14 to the aluminum cap.

An aluminum post, 3/4 in. diam., firmly set, projecting 7 ins. above ground for a reference monument, bears S. 23 3/4° W., 32 ft. dist. with an aluminum cap mkd. RM 32 FT WP 1985 and an arrow pointing to the witness point, with a steel fence post, with attached USFS sign # 54-9, SW of reference monument. Add the marks S14 to the aluminum cap.

---

The SW 1/16 sec. cor. of sec. 14, monumented with a drill hole in a basalt outcrop 15 x 15 x 6 ft. high, with an aluminum post, 12 ins. long, 3/4 in. diam., with aluminum cap mkd. T23N R6E SW 1/16 S14 1985, laying loose nearby.

from which the bearing trees mkd. in 1985

A white pine, 9 ins. diam., bears N. 60° E., 32 lks. dist., with a healed blaze.

A white pine, 12 ins. diam., bears S. 11° E., 31.5 lks. dist., with scribe marks 1/16 S14 BT visible on partially open blaze and 1 BT tag.

At the corner point

Set a brass tablet, 3 1/4 ins. diam., 2 1/2 ins. stem, cemented in the drill hole in the basalt outcrop, with top mkd.

T 23 N R 6 E

SW 1/16 S 14

2014

Deposit fragments of a magnet, in the drill hole, at the base of the brass tablet.

Set a steel fence post, with attached USFS signs # 54-2 and # 54-9, NW of cor.

Remove the aluminum post with the aluminum cap from the field.

---

**Recovery of Certain Corners,  
T. 23 N., R. 6 E., Gila and Salt River Meridian, Arizona**

## CHAINS

The C-E-SW-SW 1/256 sec. cor. of sec. 23, monumented with a stainless steel post, 2 1/2 ins. diam., firmly set, projecting 4 ins. above ground, with brass cap mkd. S23 C-E-SW-SW 1/256 1986 1985. (Record: mkd. S23 CE-SW-SW 1/256 1985) with a steel fence post, N. of cor., and a "T" post, W. of cor.

Set a steel fence post, with attached USFS signs # 54-2 and # 54-9, NE of cor.

The cor. is located 2 lks. N. of a barbed wire fence, extending E. and W., 20 lks. dist. to fence cor., from which fences extend N. and E.

---

The NE-SW-SW 1/256 sec. cor. of sec. 23, monumented with a stainless steel post, 2 1/2 ins. diam., firmly set, projecting 20 ins. above ground, in a mound of stone 3 1/2 ft. base, to top, with brass cap mkd. S23 NE-SW-SW 1/256 1986 1985. (Record: mkd. S23 NE-SW-SW 1/256 1985) with a steel fence post, S. of cor.

Set a steel fence post, with attached USFS signs # 54-2 and # 54-9, NW of cor.

From this cor., a fence corner bears N. 85 1/2° W., 26 lks. dist., from which fences extend S. and W.

---

The NW 1/16 sec. cor. of sec. 23, monumented with a stainless steel post, 2 1/2 ins. diam., firmly set, projecting 10 ins. above ground, in a scattered mound of stone, with brass cap mkd. T23N R6E NW 1/16 S23 1985, with a steel fence post nearby.

from which the bearing trees mkd. in 1985

A Douglas fir, 14 ins. diam., bears N. 21 1/2° E., 48 lks. dist., with a healed blaze and 1 BT tag.

A downed Douglas fir, bears N. 68 1/2° W., 45 lks. dist., with scribe marks X at breast height and BT at base visible on 2 partially open blazes and 1 BT tag.

and a new bearing tree

A pine, 9 ins. diam., bears East, 18.5 lks. dist., mkd. X at breast height and BT at base.

Rebuilt the mound of stone, 2 ft. base, to top of brass cap.

From this cor., a fence corner bears N. 40° W., 6 lks. dist., from which barbed wire fences, 5 strand, extend S. 80° W. and N. 10° W.

---

**Recovery of Certain Corners,  
T. 23 N., R. 6 E., Gila and Salt River Meridian, Arizona**

## CHAINS

The C-S-N-S 1/256 sec. cor. of sec. 27, monumented with a stainless steel post, 2 1/2 ins. diam., firmly set, projecting 2 ins. above ground, with brass cap mkd. S27 C-S-N-S 1/256 1985.

from which the bearing trees mkd. in 1985

A stump, 16 ins. diam., 16 ins. high, bears N. 29 1/2° E., 76 lks. dist., with a healed blaze.

A ponderosa pine, 18 ins. diam., bears N. 61° W., 35 lks. dist., with a healed blaze and 1 BT tag.

Set a steel fence post, with attached USFS signs # 54-2 and # 54-9, W. of cor.

The witness point on the N. and S. center line of the SW 1/4 of the SW 1/4 of sec. 27, on the S. side of U.S. Forest Service Route 794. (Record: on the center of U.S. Forest Service Route 794) monumented with an aluminum post, 3/4 in. diam., firmly set, flush with the surface of the ground, with aluminum cap mkd. WP S27 1985.

from which the remaining reference monument set in 1985

An aluminum post, 3/4 in. diam., firmly set, projecting 8 ins. above ground for a reference monument, bears N. 46 3/4° W., 38.6 ft. dist. with brass cap mkd. RM WP 38.7 FT. TO COR. S27 1985 and an arrow pointing to the witness point. (Record: N. 35° W., 38.7 ft. dist.)

GENERAL DESCRIPTION

The area surveyed and resurveyed within T. 23 N., R. 6 E., is located on the boundaries of the Coconino National Forest, approximately 11 miles NW of Flagstaff, Arizona. The terrain varies from gently rolling to rolling to mountainous. The elevation ranges from 7850 to 9150 ft. above sea level.

Access to the boundaries surveyed and resurveyed is provided by Arizona Highway No. 180, U.S. Forest Service Roads 151, 418 and 794.

The mean magnetic declination of 10 3/4° E. was derived from the United States Geological Survey computer program GEOMAG, utilizing the World Magnetic Model for Epoch 2010-2015 for the dates of survey.

**UNITED STATES  
DEPARTMENT OF THE INTERIOR  
BUREAU OF LAND MANAGEMENT**

**FIELD ASSISTANTS**

NAMES	CAPACITY
Craig S. Dukart	Cadastral Surveyor
Philip Freiberg	Surveying Technician
Laura A. Munsterman	Surveying Technician
Luis M. Galvan	Surveying Technician
Rafael J. Tapaha	Student Trainee
Robert J. High	Student Trainee
Lucas Taber	Student Trainee

CERTIFICATE OF SURVEY

We, Blas J. Urena and Christopher P. McDonald, Cadastral Surveyors, HEREBY CERTIFY upon honor, that in pursuance of special instructions bearing the date of the 4th day of November, 2013, we have dependently resurveyed portions of the south and east boundaries, and portions of the subdivisional lines, subdivided certain sections, performed metes-and-bounds surveys in sections 27 and 35, and recovered certain corners, T. 23 N., R. 6 E., of the Gila and Salt River Meridian, in the State of Arizona, which are represented in the foregoing field notes as having been executed by us and under our direction. Said survey has been made in strict conformity with said special instructions, the Manual of Surveying Instructions for the Survey of the Public Lands of the United States, 2009, and in specific manner described in the foregoing field notes.

9/28/2015  
(Date)

Blas J. Urena  
(Cadastral Surveyor)

09/28/2015  
(Date)

Christopher P. McDonald  
(Cadastral Surveyor)

CERTIFICATE OF APPROVAL

BUREAU OF LAND MANAGEMENT  
Phoenix, Arizona

The foregoing field notes of the dependent resurvey of portions of the south and east boundaries, and portions of the subdivisional lines, the subdivision of certain sections, metes-and-bound surveys in sections 27 and 35, and the recovery of certain corners, T. 23 N., R. 6 E., Gila and Salt River Meridian, in the State of Arizona, executed by Blas J. Urena and Christopher P. McDonald, Cadastral Surveyors, having been critically examined and found correct, are hereby approved.

9/28/2015  
(Date)

[Signature]  
(Chief Cadastral Surveyor of Arizona)

~~CERTIFICATE OF TRANSCRIPT~~

~~I CERTIFY That the foregoing transcript of the field notes of the above described surveys in T. 23 N., R. 6 E., Gila and Salt River Meridian, Arizona, is a true copy of the original field notes.~~

~~(Date)~~

~~(Chief Cadastral Surveyor of Arizona)~~