

ORIGINAL

**UNITED STATES  
DEPARTMENT OF THE INTERIOR  
BUREAU OF LAND MANAGEMENT**

FIELD NOTES

OF THE

DEPENDENT RESURVEY

OF A PORTION OF THE ARIZONA-UTAH STATE LINE (NORTH BOUNDARY),

THE SURVEY OF THE SUBDIVISIONAL LINES

AND THE SUBDIVISION OF CERTAIN SECTIONS,

**TOWNSHIP 41 NORTH, RANGE 26 EAST,**

OF THE GILA AND SALT RIVER MERIDIAN,

IN THE STATE OF ARIZONA.

**EXECUTED BY**

**Fabian Yazzie, Cadastral Surveyor**

Under Special Instructions dated November 17, 2015, approved November 17, 2015, which provided for the surveys included under Group No. 1150, and assignment instructions dated November 17, 2015.

**Survey commenced December 15, 2015**

**Survey completed April 4, 2016**



## T. 41 N., R. 26 E., Gila and Salt River Meridian, Arizona

## CHAINS

The following field notes describe the dependent resurvey of a portion of the Arizona-Utah State Line (north boundary), the survey of the subdivisional lines and the subdivision of certain sections, Township 41 North, Range 26 East, Gila and Salt River Meridian, Arizona.

The history of surveys pertaining to this survey is as follows:

Howard B. Carpenter, U.S. Surveyor, surveyed the Arizona-Utah State Line in 1901. The Arizona-Utah State Line between the 243 mile post and the Four Corners Monument, was dependently resurveyed by Robert C. Yundt, Cartographer Cadastral, in 1953. The Tenth Standard Parallel North (south boundary), the east, west, and north boundaries, Township 41 North, Range 27 East, were surveyed by Horace G. Parker, Cartographer Cadastral, in 1953. The Tenth Standard Parallel North (south boundary), Township 41 North, Range 27 East, was dependently resurveyed by Leonard R. Sandoval, in 2000. The Tenth Standard Parallel North (south boundary), Township 41 North, Range 26 East, was surveyed by Jones Curtiss, in 2000. A portion of the Arizona-Utah State Line between the 238 mile and 250 mile post, unsurveyed Townships 41 North, Ranges 24, 25, and 26 East, was dependently resurveyed by Jones Curtiss, in 2000-02. A portion of the Tenth Standard Parallel North, the Sixth Guide Meridian East, the east boundary (west boundary), Township 41 North, Range 25 East, was surveyed by Jones Curtiss, in 2000-02. The east boundary and west boundaries, Township 42 North, Range 27 East, was dependently resurveyed by Craig S. Dukart, Cadastral Surveyor, in 2011.

The survey was executed in accordance with the specifications as set forth in the Manual of Instructions for the Survey of the Public Lands of the United States, 2009, and the Special Instructions dated November 17, 2015, for Group Number 1150, Arizona.

The true meridian direction and length of all lines were determined by real time kinematic global positioning system observations using Trimble Navigation R8 model receivers.

Preliminary to the resurvey, the lines of the prior surveys were retraced and search was made for all corners and other calls of record. Identified corners were remonumented in their original positions. Lost corners were reestablished and remonumented at proportionate positions based on the official record. The retracement data were thoroughly verified and only the true line field notes are given herein.

**T. 41 N., R. 26 E., Gila and Salt River Meridian, Arizona**

CHAINS	
	<p>Geodetic control was derived from Global Positioning System (GPS) static observations post processed by National Geodetic Survey, Online Positioning User Service (OPUS), utilizing Continuously Operating Reference Stations (CORS) DI3419 P012 MONTICELLOUT2006 CORS, DL3642 MC09 NUCLA CORS, DI2245 P011 SPIDERROCKAZ2005. The NAD 83 (2011) (EPOCH: 2010), geographic position of the two corners are as follows:</p> <p>The standard corner of sections 35 and 36, Township 41 North, Range 26 East.</p> <p>Latitude: 36°54'31.523" N.                      Longitude: 109°31'03.634" W.</p> <p>The closing corner of Townships 41 North, Ranges 25 and 26 East.</p> <p>Latitude: 36°59'54.303" N.                      Longitude: 109°36'28.609" W.</p> <p>The mean magnetic declination is 10° E.</p> <hr/> <p style="text-align: center;"><b>Dependent Resurvey of a Portion of the Arizona-Utah State Line (North Boundary), T. 41 N., R. 26 E., Gila and Salt River Meridian, Arizona</b></p> <hr/> <p style="text-align: center;">Restoring the survey executed by Howard B. Carpenter, in 1901 and the dependent resurveys by Robert C. Yundt, in 1953, and Jones Curtiss in 2000-02.</p> <hr/> <p>Beginning at the 250th mile post of the Arizona-Utah State Line, monumented with an iron post, 2 1/2 ins. diam., firmly set, projecting 7 ins. above the ground, with a mound of stone, 4 ft. base, 2 ft. high, E. of cor., with brass cap mkd. 250M UTAH ARIZ 2000 1953. Add the marks 2015 to the brass cap.</p> <p>S. 89°58' E., on the 251st mile of the Arizona-Utah State Line.</p> <p>Over gently rolling land.</p>
11.88	<p>The cor. of secs. 31 and 32 only, T. 43 S., R. 22 E., Salt Lake Meridian, Utah, monumented with an iron post, 2 1/2 ins. diam., firmly set, projecting 4 ins. above the ground, with brass cap mkd. T43S R22E S31 S32 ARIZ 1953.</p>
51.90	<p>The 1/4 sec. cor. of sec. 32 only, T. 43 S., R. 22 E., Salt Lake Meridian, Utah, monumented with an iron post, 2 1/2 ins. diam., firmly set, projecting 5 ins. above the ground, with brass cap mkd. 1/4 S32 ARIZ 1953.</p>
80.07	<p>Point for the 251st mile of the Arizona-Utah State Line, at proportionate dist., there is no remaining evidence of the original cor.</p>

Dependent Resurvey of a Portion of the Arizona-Utah State Line  
 (North Boundary),  
 T. 41 N., R. 26 E., Gila and Salt River Meridian, Arizona

CHAINS									
	<p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 25 ins. in the ground, underpinned with a steel fence post, 60 ins. long, with brass cap mkd.</p> <p style="text-align: center;">251M UTAH</p> <hr style="width: 20%; margin: auto;"/> <p style="text-align: center;">ARIZ</p> <p style="text-align: center;">2016</p> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p> <p>Set a steel fence post N. of cor.</p> <hr style="width: 80%; margin: auto;"/> <p>S. 89°58' E., on the 252nd mile of the Arizona-Utah State Line.</p> <p>Over gently rolling land.</p>								
11.84	<p>From this point the 1953 cor. of secs. 32 and 33 only, T. 43 S., R. 22 E., Salt Lake Meridian, Utah, bears North, .9 lks. dist., monumented with an iron post, 2 1/2 ins. diam., firmly set, 1 in. below the ground, with brass cap mkd. T43S R22E S32 S33 ARIZ 1953.</p>								
51.84	<p>From this point the 1953 1/4 sec. cor. of sec. 33 only, T. 43 S., R. 22 E., Salt Lake Meridian, Utah, bears North, .5 lks. dist., monumented with an iron post, 2 1/2 ins. diam., firmly set, projecting 12 ins. above the ground, with brass cap mkd. 1/4 S33 ARIZ 1953.</p>								
71.84	<p>The closing cor. of secs. 1 and 31 only, Tps. 41 and 42 N., Rs. 26 and 27 E., Gila and Salt River Meridian, Arizona, monumented with a stainless steel post, 2 1/2 ins. diam., firmly set, flush with the surface of the ground, with brass cap mkd. UTAH S36 S31 R26E R27E T42N CC 2011. Add the marks 2015 to the brass cap, and remark the brass cap to read.</p> <p style="text-align: center;">UTAH</p> <hr style="width: 20%; margin: auto;"/> <table style="margin: auto; border-collapse: collapse;"> <tr> <td style="border-right: 1px solid black; padding: 0 5px;">S 1</td> <td style="padding: 0 5px;">S 31</td> </tr> <tr> <td style="border-right: 1px solid black; padding: 0 5px;">T 41 N</td> <td style="padding: 0 5px;">T 42 N</td> </tr> <tr> <td style="border-right: 1px solid black; padding: 0 5px;">R 26 E</td> <td style="padding: 0 5px;">R 27 E</td> </tr> <tr> <td colspan="2" style="text-align: center; padding: 0 5px;">CC</td> </tr> </table> <p style="text-align: center;">2011</p> <p>Set a steel fence post N. of cor.</p>	S 1	S 31	T 41 N	T 42 N	R 26 E	R 27 E	CC	
S 1	S 31								
T 41 N	T 42 N								
R 26 E	R 27 E								
CC									

Dependent Resurvey of a Portion of the Arizona-Utah State Line  
 (North Boundary),  
 T. 41 N., R. 26 E., Gila and Salt River Meridian, Arizona

CHAINS													
	<p>From this cor. point, the cor. of Tps. 41 and 42 N., R. 27 E., Gila and Salt River Meridian, Arizona, bears S. 0°01' W., 18.79 chs. dist., monumented with an iron post, 2 1/2 ins. diam., firmly set, projecting 5 ins. above the ground, with brass cap mkd. T42N R26E R27E S36 S31 S1 S6 T41N 1953 2011. Add the marks 2016 to the brass cap, and remark the brass cap to read.</p> <table border="0" style="margin-left: auto; margin-right: auto;"> <tr> <td style="padding-right: 10px;">T 41 N</td> <td style="border-left: 1px solid black; padding-left: 10px;">T 42 N</td> </tr> <tr> <td style="padding-right: 10px;">R 26 E</td> <td style="border-left: 1px solid black; padding-left: 10px;">R 27 E</td> </tr> <tr> <td style="padding-right: 10px;">S 1</td> <td style="border-left: 1px solid black; padding-left: 10px;">S 31</td> </tr> <tr> <td></td> <td style="border-left: 1px solid black; padding-left: 10px;">S 6</td> </tr> <tr> <td></td> <td style="border-left: 1px solid black; padding-left: 10px;">T 41 N</td> </tr> <tr> <td></td> <td style="border-left: 1px solid black; padding-left: 10px;">R 27 E</td> </tr> </table> <p style="text-align: center;">1953 2011</p>	T 41 N	T 42 N	R 26 E	R 27 E	S 1	S 31		S 6		T 41 N		R 27 E
T 41 N	T 42 N												
R 26 E	R 27 E												
S 1	S 31												
	S 6												
	T 41 N												
	R 27 E												
80.07	<p>Point for the 252nd mile of the Arizona-Utah State Line, at proportionate dist., there is no remaining evidence of the original cor.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 25 ins. in the ground, underpinned with a steel fence post, 60 ins. long, with brass cap mkd.</p> <table border="0" style="margin-left: auto; margin-right: auto;"> <tr> <td style="text-align: center;">252M</td> </tr> <tr> <td style="text-align: center;">UTAH</td> </tr> <tr> <td style="text-align: center;">-----</td> </tr> <tr> <td style="text-align: center;">ARIZ</td> </tr> <tr> <td style="text-align: center;">2016</td> </tr> </table> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p> <p>Set a steel fence post N. of cor.</p>	252M	UTAH	-----	ARIZ	2016							
252M													
UTAH													
-----													
ARIZ													
2016													
	<p>S. 89°58' E., on the 253rd mile of the Arizona-Utah State Line.</p> <p>Over gently rolling land.</p>												
11.77	<p>From this point, the 1953 cor. of secs. 33 and 34 only, T. 43 S., R. 22 E., Salt Lake Meridian, Utah, bears North, 1.8 lks. dist., monumented with an iron post, 2 1/2 ins. diam., firmly set, projecting 6 ins. above the ground, with brass cap mkd. T43S R22E S33 S34 ARIZ 1953.</p>												
51.78	<p>From this point, the 1953 1/4 sec. cor. of sec. 34 only, T. 43 S., R. 22 E., Salt Lake Meridian, Utah, bears North, 1.2 lks. dist., monumented with an iron post, 2 1/2 ins. diam., firmly set, projecting 4 ins. above the ground, with brass cap mkd. 1/4 S34 ARIZ 1953.</p>												

**Dependent Resurvey of a Portion of the Arizona-Utah State Line  
(North Boundary),  
T. 41 N., R. 26 E., Gila and Salt River Meridian, Arizona**

CHAINS	
80.07	<p>Point for the 253rd mile of the Arizona-Utah State Line, at proportionate dist., there is no remaining evidence of the original cor.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, underpinned with a steel fence post, 60 ins. long, with brass cap mkd.</p> <p style="text-align: center;">253M UTAH</p> <hr style="width: 20%; margin: auto;"/> <p style="text-align: center;">ARIZ</p> <p style="text-align: center;">2016</p> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p> <p>Set a steel fence post N. of cor.</p> <hr/> <p>S. 89°58' E., on the 254th mile of the Arizona-Utah State Line.</p> <p>Over gently rolling land.</p>
11.75	<p>The cor. of secs. 34 and 35 only, T. 43 S., R. 22 E., Salt Lake Meridian, Utah, monumented with an iron post, 2 1/2 ins. diam., firmly set, projecting 4 ins. above the ground, with brass cap mkd. T43S R22E S34 S35 ARIZ 1953.</p>
51.75	<p>From this point the 1953 1/4 sec. cor. of sec. 35 only, T. 43 S., R. 22 E., Salt Lake Meridian, Utah, bears North, .6 lks. dist., monumented with an iron rod, 5/8 ins. diam., firmly set, projecting 3 ins. above sandstone bedrock, with faint scribe marks in sandstone bedrock, mkd. 1/4., immediately north of iron rod.</p>
80.07	<p>Point for the 254th mile of the Arizona-Utah State Line, at proportionate dist., there is no remaining evidence of the original cor.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 25 ins. in the ground, underpinned with a steel fence post, 60 ins. long, with brass cap mkd.</p> <p style="text-align: center;">254M UTAH</p> <hr style="width: 20%; margin: auto;"/> <p style="text-align: center;">ARIZ</p> <p style="text-align: center;">2016</p> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p>

**Dependent Resurvey of a Portion of the Arizona-Utah State Line  
(North Boundary),  
T. 41 N., R. 26 E., Gila and Salt River Meridian, Arizona**

CHAINS	
	<p>Set a steel fence post N. of cor.</p> <hr/> <p>S. 89°58' E., on the 255th mile of the Arizona-Utah State Line.</p> <p>Over gently rolling land.</p>
11.69	The cor. of secs. 35 and 36 only, T. 43 S., R. 22 E., Salt Lake Meridian, Utah, monumented with an iron post, 2 1/2 ins. diam., firmly set, projecting 9 ins. above the ground, with brass cap mkd. T43S R22E S35 S36 ARIZ 1953.
51.72	The 1/4 sec. cor. of sec. 36 only, T. 43 S., R. 22 E., Salt Lake Meridian, Utah, monumented with an iron post, 2 1/2 ins. diam., firmly set, projecting 12 ins. above the ground, with brass cap mkd. 1/4 S36 ARIZ 1953.
64.20	The intersection of BIA Route 5089, a graded road, 25 ft. wide, bears S. 10° E. and N. 40° W., and Questar Southern Trails Pipeline Co., underground gas line, bears N. 75° E. and S. 75° W.
70.20	Graded road, 28 ft. wide, bears N. 20° E. and S. 20° W.
80.07	<p>The 255th mile post of the Arizona-Utah State Line, monumented with an iron post, 2 1/2 ins. diam., firmly set, projecting 30 ins. above the ground, with brass cap mkd. with raised letters UTAH on the N., ARIZ on the S., and 255M stamped in the center. Add the marks 2015 to the brass cap.</p> <p>Set a steel fence post N. of cor.</p> <p>From this cor. point, the cor. of Tps. 43 S., Rs. 22 and 23 E., Salt Lake Meridian, Utah, bears S. 89°57' E., 11.65 chs. dist., monumented with an iron post, 2 1/2 ins. diam., firmly set, projecting 2 ins. above the ground, encircled with an embedded collar of stone, 2 ft. base, with a stone, 9 X 7 X 3 ins., mkd. X, lying loose, SE of cor., with brass cap mkd. T43S R22E R23E S36 S31 ARIZ 1953.</p> <hr/> <p style="text-align: center;"><b>Survey of the Subdivisional Lines, T. 41 N., R. 26 E., Gila and Salt River Meridian, Arizona</b></p> <hr/> <p>From the stan. cor. of secs. 35 and 36, monumented with a brass tablet, 3 1/4 ins. diam., firmly set, flush with the surface of a sandstone bedrock, mkd. SC T41N R26E S35 S36 2000. Add the marks 2016 to the brass cap.</p>



**Survey of the Subdivisional Lines,  
T. 41 N., R. 26 E., Gila and Salt River Meridian, Arizona**

CHAINS	
	<p>From this cor. point, the stan. cor. of Tps. 41 N., Rs. 26 and 27 E., monumented with a stainless steel post, 2 1/2 ins. diam., with brass cap, set mkd. and witnessed as described in the field notes of the dependent resurvey of the Tenth Standard Parallel North (south boundary), T. 41 N., R. 27 E., Gila and Salt River Meridian, Arizona, under Group 844, book 5641, page 10, bears East, 80.0 chs. dist.</p> <p>From this same cor. point, among scattered remnants of concrete and sandstone rocks, a drill hole, 3 ins. diam., 4 ins. deep, in solid sandstone bedrock, of unknown origin, bears S. 88°12' W., 1.49 chs. dist.</p> <p>N. 0°01' W., bet. secs. 35 and 36.</p> <p>Over gently rolling land.</p>
7.70	Power line, 2 strand, bears S. 80° E. and N. 80° W.
14.30	Underground water line, bears N. 75° E. and S. 75° W.
40.00	Point for the 1/4 sec. cor. of secs. 35 and 36.
	<p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 21 ins. in solid sandstone bedrock, encircled with a collar of stone, 2 ft. base, to top, with brass cap mkd.</p> <p style="text-align: center;">T 41 N R 26 E 1/4 S 35   S 36</p> <p style="text-align: center;">2016</p>
	<p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p>
80.00	Point for the cor. of secs. 25, 26, 35, and 36.
	<p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T 41 N R 26 E S 26   S 25 S 35   S 36</p> <p style="text-align: center;">2016</p>
	<p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p> <p>Set a steel fence post W. of cor.</p>

Survey of the Subdivisional Lines,  
T. 41 N., R. 26 E., Gila and Salt River Meridian, Arizona

CHAINS	
	<p>Land, gently rolling. Soil, sandy loam. No timber; native grasses, yucca, salt brush, rabbit brush, and Mormon tea.</p> <hr/> <p>From the cor. of secs. 25, 30, 31, and 36 on the E. bdy. of the Tp., monumented with a stainless steel post, 2 1/2 ins. diam., firmly set, projecting 3 ins. above the ground, with a mound of stone, 3 ft. base, 2 ft. high, W. of cor., with brass cap mkd. T41N R26E R27E S25 S30 S36 S31 2011. Add the marks 2016 to the brass cap.</p> <p>West, bet. secs. 25 and 36.</p> <p>Over gently rolling land.</p>
40.01	<p>Point for the 1/4 sec. cor. of secs. 25 and 36.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center;"> <p>T 41 N R 26 E S 25 1/4 ——— S 36</p> <p>2016</p> </div> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p> <p>Set a steel fence post N. of cor.</p>
80.01	<p>The cor. of secs. 25, 26, 35, and 36.</p> <p>Land, gently rolling. Soil, sandy loam. No timber; native grasses, and salt brush.</p> <hr/> <p>N. 0°01' W., bet. secs. 25 and 26.</p> <p>Over gently rolling land.</p>
40.00	<p>Point for the 1/4 sec. cor. of secs. 25 and 26.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p>

Survey of the Subdivisional Lines,  
T. 41 N., R. 26 E., Gila and Salt River Meridian, Arizona

CHAINS	
	T 41 N R 26 E 1/4 S 26   S 25  2016
	Deposit a magnet, in a white plastic case, at the base of the stainless steel post.  Set a steel fence post W. of cor.
80.00	Point for the cor. of secs. 23, 24, 25, and 26.  Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 25 ins. in the ground, with brass cap mkd.
	T 41 N R 26 E S 23   S 24 S 26   S 25  2016
	Deposit a magnet, in a white plastic case, at the base of the stainless steel post.  Set a steel fence post W. of cor.  Land, gently rolling. Soil, sandy loam. No timber; native grasses, yucca, salt brush, and Mormon tea.
	<hr/> From the cor. of secs. 19, 24, 25, and 30 on the E. bdy. of the Tp., monumented with a stainless steel post, 2 1/2 ins. diam., firmly set, projecting 2 ins. above the ground, with a mound of stone, 3 ft. base, 1 1/2 ft. high, W. of cor., with brass cap mkd. T41N R26E R27E S24 S19 S25 S30 2011. Add the marks 2016 to the brass cap.  West, bet. secs. 24 and 25.  Over gently rolling land.
39.97	Point for the 1/4 sec. cor. of secs. 24 and 25.  Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 25 ins. in the ground, with brass cap mkd.

**Survey of the Subdivisional Lines,  
T. 41 N., R. 26 E., Gila and Salt River Meridian, Arizona**

CHAINS	
	T 41 N R 26 E S 24 1/4 ——— S 25  2016
	Deposit a magnet, in a white plastic case, at the base of the stainless steel post.  Set a steel fence post N. of cor.
79.95	The cor. of secs. 23, 24, 25, and 26.  Land, gently rolling. Soil, sandy loam. No timber; native grasses, and Mormon tea.
	<hr/> N. 0°01' W., bet. secs. 23 and 24.  Over gently rolling land.
17.50	Power line, 2 strand, bears N. 25° E. and S. 25° W.
40.00	Point for the 1/4 sec. cor. of secs. 23 and 24.  Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.
	T 41 N R 26 E 1/4 S 23   S 24  2016
	Deposit a magnet, in a white plastic case, at the base of the stainless steel post.  Set a steel fence post W. of cor.
62.70	High voltage transmission line, bears N. 65° E. and S. 65° W.
69.65	S. right-of-way fence of U.S. Highway 160, barbed wire, 5 strand, parallels highway.
71.30	U.S. Highway 160, an asphalt surfaced road, 36 ft. wide, bears N. 65° E. and S. 65° W.
74.60	N. right-of-way fence of U.S. Highway 160, barbed wire, 5 strand, parallels highway.
80.00	Point for the cor. of secs. 13, 14, 23, and 24.

**Survey of the Subdivisional Lines,  
T. 41 N., R. 26 E., Gila and Salt River Meridian, Arizona**

CHAINS	
	<p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 27 ins. in the ground, with brass cap mkd.</p> <p align="center">                     T 41 N R 26 E                      S 14   S 13                      S 23   S 24                 </p> <p align="center">2016</p> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p> <p>Set a steel fence post W. of cor.</p> <p>Land, gently rolling. Soil, sandy loam. No timber; native grasses, salt brush, rabbit brush, and Mormon tea.</p>
	<p>From the cor. of secs. 13, 18, 19, and 24 on the E. bdy. of the Tp., monumented with an iron post, 2 1/2 ins. diam., firmly set, projecting 12 ins. above the ground, with a mound of stone, 3 ft. base, 1 ft. high, W. of cor., with brass cap mkd. T41N R26E R27E S13 S18 S24 S19 1953 2011. Add the marks 2016 to the brass cap.</p> <p>N. 89°58' W., bet. secs. 13 and 24.</p> <p>Over rolling land.</p>
40.005	<p>Point for the 1/4 sec. cor. of secs. 13 and 24.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with brass cap mkd.</p> <p align="center">                     T 41 N R 26 E                      S 13                      1/4 ———                      S 24                 </p> <p align="center">2016</p> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p> <p>Set a steel fence post N. of cor.</p> <p>Cor. is located 1.60 chs. S. of a high voltage transmission line, bears N. 65° E. and S. 65° W.</p>
43.40	<p>High voltage transmission line, bears N. 65° E. and S. 65° W.</p>

**Survey of the Subdivisional Lines,  
T. 41 N., R. 26 E., Gila and Salt River Meridian, Arizona**

CHAINS	
56.60	S. right-of-way fence of U.S. Highway 160, barbed wire, 5 strand, parallels highway.
60.30	U.S. Highway 160, an asphalt surfaced road, 36 ft. wide, bears N. 65° E. and S. 65° W.
67.85	N. right-of-way fence of U.S. Highway 160, barbed wire, 5 strand, parallels highway.
68.49	From this point, a right-of-way monument, bears S., 5.26 chs. dist., monumented with a brass tablet, 3 ins. diam., set flush in a concrete cylinder, 6 ins. diam., firmly set, projecting 10 ins. above the ground, mkd. ARIZONA HIGHWAY DEPT 1961, with an angle iron, firmly set, projecting 24 ins. above ground, to the E., faintly mkd. POT 2684+51.92.
70.33	From this point, a right-of-way monument, bears S., 1.10 chs. dist., monumented with a brass tablet, 3 ins. diam., set flush in a concrete cylinder, 6 ins. diam., firmly set, projecting 15 ins. above the ground, mkd. ARIZONA HIGHWAY DEPT ELEV. STA. 1961.
80.01	The cor. of secs. 13, 14, 23, and 24.  Land, rolling to gently rolling. Soil, sandy loam. No timber; native grasses, and Mormon tea.
	N. 0°01' W., bet. secs. 13 and 14.  Over gently rolling land.
40.00	Point for the 1/4 sec. cor. of secs. 13 and 14.  Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with brass cap mkd.  <div style="text-align: center;">           T 41 N R 26 E                1/4            S 14   S 13              2016         </div>
	Deposit a magnet, in a white plastic case, at the base of the stainless steel post.  Set a steel fence post W. of cor.
80.00	Point for the cor. of secs. 11, 12, 13, and 14.  Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 25 ins. in the ground, with brass cap mkd.

Survey of the Subdivisional Lines,  
T. 41 N., R. 26 E., Gila and Salt River Meridian, Arizona

CHAINS	
	T 41 N R 26 E S 11   S 12 S 14   S 13  2016
	Deposit a magnet, in a white plastic case, at the base of the stainless steel post.  Set a steel fence post W. of cor.  Land, gently rolling. Soil, sandy loam. No timber; native grasses, and Mormon tea.
	<hr/> From the cor. of secs. 7, 12, 13, and 18 on the E. bdy. of the Tp., monumented with an iron post, 2 1/2 ins. diam., firmly set, projecting 5 ins. above the ground, with brass cap mkd. T41N R26E R27E S12 S7 S13 S18 2011 1953. Add the marks 2016 to the brass cap.  S. 89°59' W., bet. secs. 12 and 13.  Over gently rolling land.
40.00	Point for the 1/4 sec. cor. of secs. 12 and 13.  Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.
	T 41 N R 26 E S 12 1/4 ——— S 13  2016
	Deposit a magnet, in a white plastic case, at the base of the stainless steel post.  Set a steel fence post N. of cor.
80.00	The cor. of secs. 11, 12, 13, and 14.  Land, gently rolling. Soil, sandy loam. No timber; native grasses, yucca, and Mormon tea.
	<hr/> N. 0°01' W., bet. secs. 11 and 12.  Over gently rolling land.

**Survey of the Subdivisional Lines,  
T. 41 N., R. 26 E., Gila and Salt River Meridian, Arizona**

CHAINS	
40.00	<p>Point for the 1/4 sec. cor. of secs. 11 and 12.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 25 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T 41 N R 26 E 1/4 S 11   S 12</p> <p style="text-align: center;">2016</p> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p> <p>Set a steel fence post W. of cor.</p>
80.00	<p>Point for the cor. of secs. 1, 2, 11, and 12.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 25 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T 41 N R 26 E S 2   S 1 S 11   S 12</p> <p style="text-align: center;">2016</p> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p> <p>Set a steel fence post W. of cor.</p> <p>Cor. is located 60 lks. N., and 85 lks. E. of BIA Route 5058, a bladed dirt road, 25 ft. wide, bears S. 55° E. and N. 55° W.</p> <p>From this cor. point, a rebar, 5/8 in. diam., firmly set, projecting 3 ins. above the ground, with 2 in. aluminum cap, mkd. QUESTAR 6.40 FL CP, bears N. 42°26' E., 30.97 chs. dist.</p> <p>Land, gently rolling. Soil, sandy loam. No timber; native grasses, and Mormon tea.</p> <hr/> <p>From the cor. of secs. 1, 6, 7, and 12 on the E. bdy. of the Tp., monumented with an iron post, 2 1/2 ins. diam., firmly set, projecting 4 ins. above the ground, with brass cap mkd. T41N R26E R27E S1 S6 S12 S7 1953 2011. Add the marks 2016 to the brass cap.</p> <p>S. 89°57' W., bet. secs. 1 and 12.</p> <p>Over nearly level land.</p>



Survey of the Subdivisional Lines,  
T. 41 N., R. 26 E., Gila and Salt River Meridian, Arizona

CHAINS	
40.00	<p>Point for the 1/4 sec. cor. of secs. 1 and 12.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T 41 N R 26 E S 1 1/4 ——— S 12</p> <p style="text-align: center;">2016</p> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p> <p>Set a steel fence post N. of cor.</p>
80.00	<p>The cor. of secs. 1, 2, 11, and 12.</p> <p>Land, nearly level, and gently rolling. Soil, sandy loam. No timber; native grasses, yucca, and Mormon tea.</p> <hr/> <p>N. 0°01' W., bet. secs. 1 and 2.</p> <p>Over nearly level land.</p>
17.30	<p>Questar Southern Trails Pipeline Co., underground gas line, bears N. 75° E. and S. 75° W.</p>
40.00	<p>Point for the 1/4 sec. cor. of secs. 1 and 2.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T 41 N R 26 E 1/4 S 2   S 1</p> <p style="text-align: center;">2016</p> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p> <p>Set a steel fence post W. of cor.</p>
80.00	<p>Point for the 80 1/16 sec. cor. of secs. 1 and 2.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p>

**Survey of the Subdivisional Lines,  
T. 41 N., R. 26 E., Gila and Salt River Meridian, Arizona**

CHAINS	
	T 41 N R 26 E 1/16 S 2   S 1 80  2016
	Deposit a magnet, in a white plastic case, at the base of the stainless steel post.  Set a steel fence post N. of cor.
98.95	Point for the closing cor. of secs. 1 and 2, at intersection with the Arizona-Utah State Line.  Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.
	UTAH ----- S 2   S 1 T 41 N   R 26 E CC  2016
	Deposit a magnet, in a white plastic case, at the base of the stainless steel post.  Set a steel fence post S. of cor.  From this cor. point, the 251st mile post of the Arizona-Utah State Line, bears S. 89°58' E., 8.15 chs. dist., hereinbefore described.  From this same cor. point, the 250th mile post of the Arizona-Utah State Line, bears N. 89°58' W., 71.92 chs. dist., hereinbefore described.  Land, nearly level, and gently rolling. Soil, sandy loam. No timber; native grasses, rabbit brush, and Mormon tea.
	Point for the 1/4 sec. cor. of sec. 1 only, T. 41 N., R. 26 E., at midpoint on the N. bdy. of sec. 1.  Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.

Survey of the Subdivisional Lines,  
T. 41 N., R. 26 E., Gila and Salt River Meridian, Arizona

CHAINS

UTAH

1/4 S 1  
T 41 N R 26 E

2016

Deposit a magnet, in a white plastic case, at the base of the stainless steel post.

Set a steel fence post S. of cor.

From this cor. point, the 252nd mile post of the Arizona-Utah State Line, bears S. 89°58' E., 48.225 chs. dist., hereinbefore described.

From this same cor. point, the 251st mile post of the Arizona-Utah State Line, bears N. 89°58' W., 31.845 chs. dist., hereinbefore described.

---

From the stan. cor. of secs. 34 and 35, on the S. bdy. of the Tp., monumented with a stainless steel post, 2 1/2 ins. diam., firmly set, projecting 2 ins. above the ground, with brass cap mkd. SC T41N R26E S34 S35 2000. Add the marks 2016 to the brass cap.

From this cor. point, a brass tablet, 2 ins. diam., recessed 1 1/2 ins. below top of a concrete collar, 6 ins. diam., firmly set, flush with the surface of the ground, established by Charles W. Dryden (deceased), AZ R.L.S. 4321, with a mound of stone, 2 ft. base, 2 ft. high, N. of cor., mkd. T41N CC S35 S3 S2 R26E T40N RLS 4321 1964, bears S. 89°55' E., 1.13 chs. dist. Note: There is no official 1964 survey recorded with the Apache County Recorder's Office, and no additional information in the group folder for Group Number 844. Similar ties to the aforementioned brass tablet are located in books 5658 and 5641.

From this same cor. point, an open-end iron pipe, 2 1/2 ins. diam., firmly set, projecting 20 ins. above the ground, of unknown origin, mkd. T41N R26E 3 2 T40N on the S. face, bears S. 86°42' W., 1.42 chs. dist. Note: Descriptions of the open-end iron pipe, hereinafter, are comparable to the ties made by Leo R. Sandoval, Cadastral Surveyor, in Group Number 844, the dependent resurvey of the Tenth Standard Parallel North (south boundary), T. 41 N, R. 27 E., book 5641, and by Jones Curtiss, Cadastral Surveyor, in Group Number 844, the survey of the Tenth Standard Parallel North (south boundary), T. 41 N., Rs. 25 through 26 E., books 5666 and 5658, respectively, in 2000.

N. 0°01' W., bet. secs. 34 and 35.

Over gently rolling land.

**Survey of the Subdivisional Lines,  
T. 41 N., R. 26 E., Gila and Salt River Meridian, Arizona**

CHAINS	
19.70	Underground water line, bears S. 80° E. and N. 80° W.
23.45	Power line, 2 strand, bears S. 80° E. and N. 80° W.
40.00	Point for the 1/4 sec. cor. of secs. 34 and 35.  Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 25 ins. in the ground, with brass cap mkd.  <div style="text-align: center;">           T 41 N R 26 E                1/4            S 34   S 35             2016         </div> Deposit a magnet, in a white plastic case, at the base of the stainless steel post.  Set a steel fence post W. of cor.
80.00	Point for the cor. of secs. 26, 27, 34, and 35.  Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 22 ins. in the ground, encircled with a collar of stone, 2 ft. base, to top, with brass cap mkd.  <div style="text-align: center;">           T 41 N R 26 E            S 27   S 26            S 34   S 35             2016         </div> Deposit a magnet, in a white plastic case, at the base of the stainless steel post.  From this cor. point, an open-end iron pipe, 2 1/2 ins. diam., 30 ins. long, lying loose, of unknown origin, mkd. T41N R26E 27 26 34 35 on the side, bears S. 43°55' E., 17.3 lks. dist.  Land, gently rolling. Soil, sandy loam, and sandstone bedrock. No timber; native grasses, rabbit brush, salt brush, yucca, and Mormon tea.
40.00	<hr/> From the cor. of secs. 25, 26, 35, and 36.  West, bet. secs. 26 and 35.  Over gently rolling land.  Point for the 1/4 sec. cor. of secs. 26 and 35.

Survey of the Subdivisional Lines,  
T. 41 N., R. 26 E., Gila and Salt River Meridian, Arizona

CHAINS	
	<p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T 41 N R 26 E S 26 1/4 ——— S 35</p> <p style="text-align: center;">2016</p> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p> <p>Set a steel fence post N. of cor.</p>
43.55	Power line, 2 strand, bears N. 25° E. and S. 25° W.
80.00	<p>The cor. of secs. 26, 27, 34, and 35.</p> <p>Land, gently rolling. Soil, sandy loam. No timber; native grasses, yucca, and Mormon tea.</p> <hr/> <p>N. 0°01' W., bet. secs. 26 and 27.</p> <p>Over exposed sandstone bedrock, and gently rolling land.</p>
40.00	<p>Point for the 1/4 sec. cor. of secs. 26 and 27.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T 41 N R 26 E 1/4 S 27   S 26</p> <p style="text-align: center;">2016</p> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p> <p>Set a steel fence post W. of cor.</p>
80.00	<p>Point for the cor. of secs. 22, 23, 26, and 27.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 25 ins. in the ground, with brass cap mkd.</p>

Survey of the Subdivisional Lines,  
T. 41 N., R. 26 E., Gila and Salt River Meridian, Arizona

CHAINS									
	<table border="1" style="margin: auto;"> <tr> <td>T 41 N</td> <td>R 26 E</td> </tr> <tr> <td>S 22</td> <td>S 23</td> </tr> <tr> <td>S 27</td> <td>S 26</td> </tr> </table>	T 41 N	R 26 E	S 22	S 23	S 27	S 26		
T 41 N	R 26 E								
S 22	S 23								
S 27	S 26								
	2016								
	Deposit a magnet, in a white plastic case, at the base of the stainless steel post.								
	Set a steel fence post W. of cor.								
	From this cor. point, an open-end iron pipe, 2 1/2 ins. diam., firmly set, projecting 6 ins. above the ground, of unknown origin, mkd. T41N R26E 22 23 27 26 on the S. face, bears S. 39°47' E., 23.9 lks. dist.								
	Land, gently rolling. Soil, sandy loam, and sandstone bedrock. No timber; native grasses, yucca, and Mormon tea.								
	<hr/>								
	From the cor. of secs. 23, 24, 25, and 26.								
	West, bet. secs. 23 and 26.								
	Over gently rolling land.								
7.80	Power line, 2 strand, bears N. 25° E. and S. 25° W.								
40.00	Point for the 1/4 sec. cor. of secs. 23 and 26.								
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with brass cap mkd.								
	<table border="1" style="margin: auto;"> <tr> <td>T 41 N</td> <td>R 26 E</td> </tr> <tr> <td></td> <td>S 23</td> </tr> <tr> <td>1/4</td> <td>_____</td> </tr> <tr> <td></td> <td>S 26</td> </tr> </table>	T 41 N	R 26 E		S 23	1/4	_____		S 26
T 41 N	R 26 E								
	S 23								
1/4	_____								
	S 26								
	2016								
	Deposit a magnet, in a white plastic case, at the base of the stainless steel post.								
	Set a steel fence post N. of cor.								
80.00	The cor. of secs. 22, 23, 26, and 27.								
	Land, gently rolling. Soil, sandy loam. No timber; native grasses, yucca, rabbit brush, and Mormon tea.								
	<hr/>								

**Survey of the Subdivisional Lines,  
T. 41 N., R. 26 E., Gila and Salt River Meridian, Arizona**

CHAINS	
	N. 0°01' W., bet. secs. 22 and 23.  Over gently rolling land.
34.30	S. right-of-way fence of U.S. Highway 160, barbed wire, 5 strand, parallels highway.
34.40	High voltage transmission line, bears E. and W.
35.90	U.S. Highway 160, an asphalt surfaced road, 36 ft. wide, bears N. 65° E. and S. 65° W.
40.00	Point for the 1/4 sec. cor. of secs. 22 and 23.  Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 25 ins. in the ground, with brass cap mkd.  <div style="text-align: center;">           T 41 N R 26 E                  1/4            S 22   S 23             2016         </div> Deposit a magnet, in a white plastic case, at the base of the stainless steel post.  Set a steel fence post W. of cor.  Cor. is located 1.70 chs. W., and 77 lks. N. of the N. right-of-way fence of U.S. Highway 160, barbed wire, 5 strand, bears N. 65° E. and S. 65° W.
80.00	Point for the cor. of secs. 14, 15, 22, and 23.  Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.  <div style="text-align: center;">           T 41 N R 26 E            S 15   S 14            S 22   S 23             2016         </div> Deposit a magnet, in a white plastic case, at the base of the stainless steel post.  Set a steel fence post N. of cor.  From this cor. point, an open-end iron pipe, 2 1/2 ins. diam., firmly set, projecting 6 ins. above the ground, of unknown origin, mkd. T41N R26E 15 14 22 23 on the S. face, bears S. 30°10' E., 35.5 lks. dist.

**Survey of the Subdivisional Lines,  
T. 41 N., R. 26 E., Gila and Salt River Meridian, Arizona**

CHAINS	
	<p>Land, gently rolling to rolling. Soil, sandy loam. No timber; native grasses, salt brush and Mormon tea.</p> <hr/> <p>From the cor. of secs. 13, 14, 23, and 24. West, bet. secs. 14 and 23. Over gently rolling land.</p>
40.00	<p>Point for the 1/4 sec. cor. of secs. 14 and 23.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T 41 N R 26 E S 14 1/4 ——— S 23</p> <p style="text-align: center;">2016</p> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p> <p>Set a steel fence post N. of cor.</p>
80.00	<p>The cor. of secs. 14, 15, 22, and 23.</p> <p>Land, gently rolling to rugged. Soil, sandy loam, and rock outcrops. No timber; native grasses, salt brush and Mormon tea.</p> <hr/> <p>N. 0°01' W., bet. secs. 14 and 15. Over rolling land.</p>
40.00	<p>Point for the 1/4 sec. cor. of secs. 14 and 15.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T 41 N R 26 E 1/4 S 15   S 14</p> <p style="text-align: center;">2016</p> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p> <p>Raise a mound of stone, 2 ft. base, 3 ft. high, N. of cor.</p>



Survey of the Subdivisional Lines,  
T. 41 N., R. 26 E., Gila and Salt River Meridian, Arizona

CHAINS 80.00	<p>Point for the cor. of secs. 10, 11, 14, and 15.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center;"> <table style="margin: auto;"> <tr><td>T 41 N</td><td>R 26 E</td></tr> <tr><td>S 10</td><td>S 11</td></tr> <tr><td>S 15</td><td>S 14</td></tr> </table> <p>2016</p> </div> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p> <p>Set a steel fence post N. of cor.</p> <p>Land, rolling to gently rolling. Soil, sandy loam, and rock outcrops. No timber; native grasses, yucca, salt brush and Mormon tea.</p> <hr/> <p>From the cor. of secs. 11, 12, 13, and 14.</p> <p>West, bet. secs. 11 and 14.</p> <p>Over gently rolling land.</p>	T 41 N	R 26 E	S 10	S 11	S 15	S 14		
T 41 N	R 26 E								
S 10	S 11								
S 15	S 14								
40.00	<p>Point for the 1/4 sec. cor. of secs. 11 and 14.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center;"> <table style="margin: auto;"> <tr><td>T 41 N</td><td>R 26 E</td></tr> <tr><td>S 11</td><td></td></tr> <tr><td>1/4</td><td>—</td></tr> <tr><td>S 14</td><td></td></tr> </table> <p>2016</p> </div> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p> <p>Set a steel fence post N. of cor.</p>	T 41 N	R 26 E	S 11		1/4	—	S 14	
T 41 N	R 26 E								
S 11									
1/4	—								
S 14									
80.00	<p>The cor. of secs. 10, 11, 14, and 15.</p> <p>Land, gently rolling to rugged. Soil, sandy loam, and rock outcrops. No timber; native grasses, salt brush and Mormon tea.</p> <hr/> <p>N. 0°01' W., bet. secs. 10 and 11.</p>								

**Survey of the Subdivisional Lines,  
T. 41 N., R. 26 E., Gila and Salt River Meridian, Arizona**

CHAINS	
	Over gently rolling land.
40.00	Point for the 1/4 sec. cor. of secs. 10 and 11.  Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.  <div style="text-align: center;">           T 41 N R 26 E                  1/4            S 10   S 11             2016         </div>
	Deposit a magnet, in a white plastic case, at the base of the stainless steel post.  Set a steel fence post W. of cor.
75.45	Questar Southern Trails Pipeline Co., underground gas line, bears N. 75° E. and S. 75° W.
80.00	Point for the cor. of secs. 2, 3, 10, and 11.  Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with brass cap mkd.  <div style="text-align: center;">           T 41 N R 26 E            S 3   S 2            S 10   S 11             2016         </div>
	Deposit a magnet, in a white plastic case, at the base of the stainless steel post.  Set a steel fence post N. of cor.  Land, gently rolling. Soil, sandy loam. No timber; native grasses, rabbit brush, salt brush and Mormon tea.
	From the cor. of secs. 1, 2, 11, and 12.  West, bet. secs. 2 and 11.  Over gently rolling land.
40.00	Point for the 1/4 sec. cor. of secs. 2 and 11.  Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 25 ins. in the ground, with brass cap mkd.

Survey of the Subdivisional Lines,  
T. 41 N., R. 26 E., Gila and Salt River Meridian, Arizona

CHAINS	
	T 41 N R 26 E S 2 1/4 ——— S 11  2016
	Deposit a magnet, in a white plastic case, at the base of the stainless steel post.  Set a steel fence post N. of cor.
63.30	Questar Southern Trails Pipeline Co., underground gas line, bears N. 75° E. and S. 75° W.
65.20	Power line, 2 strand, bears S. 10° E. and N. 10° W.
68.00	Underground water line, bears S. 20° E. and N. 20° W.
80.00	The cor. of secs. 2, 3, 10, and 11.  Land, gently rolling. Soil, sandy loam. No timber; native grasses, and Mormon tea.
	N. 0°01' W., bet. secs. 2 and 3.  Over gently rolling land.
30.40	Underground water line, bears S. 20° E. and N. 20° W.
40.00	Point for the 1/4 sec. cor. of secs. 2 and 3.  Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with brass cap mkd.
	T 41 N R 26 E 1/4 S 3   S 2  2016
	Deposit a magnet, in a white plastic case, at the base of the stainless steel post.  Set a steel fence post W. of cor.  Cor. is located 3.10 chs. E. of an underground water line, bears N. and S.
47.25	Power line, 2 strand, bears E. and W.
70.60	BIA Route 5058, a bladed dirt road, 25 ft. wide, bears E. and W.

**Survey of the Subdivisional Lines,  
T. 41 N., R. 26 E., Gila and Salt River Meridian, Arizona**

CHAINS	
80.00	<p>Point for the 80 1/16 sec. cor. of secs. 2 and 3.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center;"> <p>T 41 N R 26 E 1/16 S 3   S 2 80</p> <p>2016</p> </div> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p> <p>Set a steel fence post W. of cor.</p> <p>Cor. is located 2.50 chs. E. of an underground water line, bears N. and S.</p> <p>From this cor. point, a utility pole, 11 ins. diam., with power line, 2 strand, extending S. 10° E. and N. 10° W., bears S. 6° E., 44.7 lks. dist.</p>
98.89	<p>Point for the closing cor. of secs. 2 and 3, at intersection with the Arizona-Utah State Line.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center;"> <p>UTAH</p> <hr style="width: 10%; margin: 0 auto;"/> <p>S 3   S 2 T 41 N   R 26 E CC</p> <p>2016</p> </div> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p> <p>Set a steel fence post S. of cor.</p> <p>Cor. is located 2.25 chs. E. of an underground water line, bears N. and S., and 3.50 chs. E. of a power line, 2 strand, bears S. 10° E. and N. 10° W.</p> <p>From this cor. point, the 250th mile post of the Arizona-Utah State Line, bears N. 89°15.4' E., 8.082 chs. dist., hereinbefore described.</p>

**Survey of the Subdivisional Lines,  
T. 41 N., R. 26 E., Gila and Salt River Meridian, Arizona**

CHAINS	<p>From this same cor. point, the 249th mile post of the Arizona-Utah State Line, bears S. 89°15.4' W., 71.923 chs. dist., monumented with a stainless steel post, 2 1/2 ins. diam., firmly set, projecting 3 ins. above the ground, with a steel fence post, N. of cor., with brass cap mkd. 249M UTAH ARIZ 2002. Add the marks 2015 to the brass cap.</p> <p>Land, gently rolling. Soil, sandy loam. No timber; native grasses, rabbit brush, and Mormon tea.</p> <hr/> <p>Point for the 1/4 sec. cor. of sec. 2 only, T. 41 N., R. 26 E., at midpoint on the N. bdy. of sec. 2.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">UTAH ----- 1/4 S 2 T 41 N R 26 E</p> <p style="text-align: center;">2016</p> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p> <p>Set a steel fence post S. of cor.</p> <p>From this cor. point, the 251st mile post of the Arizona-Utah State Line, bears S. 89°58' E., 48.15 chs. dist., hereinbefore described.</p> <p>From this same cor. point, the 250th mile post of the Arizona-Utah State Line, bears N. 89°58' W., 31.92 chs. dist., hereinbefore described.</p> <hr/> <p>From the stan. cor. of secs. 33 and 34, on the S. bdy. of the Tp., monumented with a brass tablet, 3 1/4 ins. diam., firmly set, flush with the surface of a sandstone bedrock, mkd. SC T41N R26E S33 S34 2000. Add the marks 2016 to the brass cap.</p> <p>N. 0°02' W., bet. secs. 33 and 34.</p> <p>Over exposed sandstone bedrock, and gently rolling land.</p>
40.00	<p>Point for the 1/4 sec. cor. of secs. 33 and 34.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 27 ins. in the ground, with brass cap mkd.</p>

**Survey of the Subdivisional Lines,  
T. 41 N., R. 26 E., Gila and Salt River Meridian, Arizona**

CHAINS	
	T 41 N R 26 E 1/4 S 33   S 34  2016
	Deposit a magnet, in a white plastic case, at the base of the stainless steel post.  Set a steel fence post W. of cor.  Cor. is located 85 lks. S. of a power line, bears S. 80° E. and N. 80° W.  From this cor. point, the SW cor. of a residential house, 40 x 20 ft., bears N. 62°48' E., 87 lks. dist., long side bears N. 7° E., and short side bears S. 83° E.
54.55	Underground water line, bears S. 30° E. and N. 30° W.
80.00	Point for the cor. of secs. 27, 28, 33, and 34.  Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with brass cap mkd.
	T 41 N R 26 E S 28   S 27 S 33   S 34  2016
	Deposit a magnet, in a white plastic case, at the base of the stainless steel post.  Set a steel fence post N. of cor.  Land, gently rolling. Soil, sandy loam, and sandstone bedrock. No timber; native grasses, yucca, rabbit brush, and Mormon tea.
	<hr/> From the cor. of secs. 26, 27, 34, and 35.  West, bet. secs. 27 and 34.  Over exposed sandstone bedrock, and gently rolling land.
40.00	Point for the 1/4 sec. cor. of secs. 27 and 34.  Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with brass cap mkd.

Survey of the Subdivisional Lines,  
T. 41 N., R. 26 E., Gila and Salt River Meridian, Arizona

CHAINS	
	T 41 N R 26 E S 27 1/4 ——— S 34  2016
	Deposit a magnet, in a white plastic case, at the base of the stainless steel post.
	Set a steel fence post N. of cor.
80.00	The cor. of secs. 27, 28, 33, and 34.  Land, gently rolling. Soil, sandy loam, and sandstone bedrock. No timber; native grasses, yucca, rabbit brush, and Mormon tea.
	N. 0°02' W., bet. secs. 27 and 28.  Over gently rolling land.
31.00	Underground water line, bears N. 15° E. and S. 15° W.
40.00	Point for the 1/4 sec. cor. of secs. 27 and 28.  Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with brass cap mkd.
	T 41 N R 26 E 1/4 S 28   S 27  2016
	Deposit a magnet, in a white plastic case, at the base of the stainless steel post.
	Set a steel fence post W. of cor.
	Cor. is located 2.70 chs. W. of an underground water line, bears N. 15° E. and S. 15° W.
80.00	Point for the cor. of secs. 21, 22, 27, and 28.  Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.

Survey of the Subdivisional Lines,  
T. 41 N., R. 26 E., Gila and Salt River Meridian, Arizona

CHAINS

T 41 N	R 26 E
S 21	S 22
S 28	S 27

2016

from which

A stainless steel post, 28 ins. long, 2 1/2 ins. diam., set 24 ins. in the ground for a reference monument, bears S. 70°00' E., 100.0 ft. dist. with brass cap mkd. RM T41N R26E 100.0 FT TO COR S27 2016 and an arrow pointing to the cor. Deposit a magnet, in a white plastic case, at the base of the stainless steel post, and set a steel fence post nearby.

A stainless steel post, 28 ins. long, 2 1/2 ins. diam., set 24 ins. in the ground for a reference monument, bears S. 20°00' W., 100.0 ft. dist. with brass cap mkd. RM T41N R26E 100.0 FT TO COR S28 2016 and an arrow pointing to the cor. Deposit a magnet, in a white plastic case, at the base of the stainless steel post, and set a steel fence post nearby.

Deposit a magnet, in a white plastic case, at the base of the stainless steel post.

Set a steel fence post N. of cor.

Cor. is located 50 lks. S., and 1.15 chs. E. of U.S. Highway 160, an asphalt surfaced road, 36 ft. wide, bears N. 65° E. and S. 65° W.

Cor. is also located 2.50 chs. W., and 1.10 chs. N. of the S. right-of-way fence of U.S. Highway 160, barbed wire, 5 strand, parallels highway.

Land, gently rolling.

Soil, sandy loam.

No timber; native grasses, and Mormon tea.

---

From the cor. of secs. 22, 23, 26, and 27.

West, bet. secs. 22 and 27.

Over gently rolling land.

40.00

Point for the 1/4 sec. cor. of secs. 22 and 27.

Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with brass cap mkd.



Survey of the Subdivisional Lines,  
T. 41 N., R. 26 E., Gila and Salt River Meridian, Arizona

CHAINS	
	T 41 N R 26 E S 22 1/4 ——— S 27  2016
	Deposit a magnet, in a white plastic case, at the base of the stainless steel post.
	Set a steel fence post N. of cor.
65.10	Underground water line, bears N. 15° E. and S. 15° W.
77.50	S. right-of-way fence of U.S. Highway 160, barbed wire, 5 strand, bears N. 65° E. and S. 65° W.
80.00	The cor. of secs. 21, 22, 27, and 28.  Land, gently rolling. Soil, sandy loam. No timber; native grasses, and Mormon tea.
	N. 0°02' W., bet. secs. 21 and 22.  Crossing U.S. Highway 160, and over gently rolling land.
3.80	N. right-of-way fence of U.S. Highway 160, barbed wire, 5 strand, bears N. 65° E. and S. 65° W.
32.60	High voltage transmission line, bears E. and W.
40.00	Point for the 1/4 sec. cor. of secs. 21 and 22.  Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with brass cap mkd.
	T 41 N R 26 E 1/4 S 21   S 22  2016
	Deposit a magnet, in a white plastic case, at the base of the stainless steel post.
	Set a steel fence post N. of cor.
	Cor. is located 50 lks. N. of a power line, 2 strand, bears N. 85° E. and S. 85° W.

**Survey of the Subdivisional Lines,  
T. 41 N., R. 26 E., Gila and Salt River Meridian, Arizona**

CHAINS																	
	<p>From this cor. point, the center of a windmill tower, positioned on a concrete pad 7 x 7 ft., bears S. 14°46' E., 1.79 chs. dist., with a livestock water tank alongside, 25 ft. diam., 7 ft. high, mkd. 9T-603.</p>																
80.00	<p>Point for the cor. of secs. 15, 16, 21, and 22.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 25 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center;"> <table style="margin-left: auto; margin-right: auto;"> <tr> <td colspan="2">T 41 N</td> <td colspan="2">R 26 E</td> </tr> <tr> <td style="border-right: 1px solid black;">S 16</td> <td style="border-right: 1px solid black;"></td> <td style="border-right: 1px solid black;">S 15</td> <td></td> </tr> <tr> <td style="border-right: 1px solid black;">S 21</td> <td style="border-right: 1px solid black;"></td> <td style="border-right: 1px solid black;">S 22</td> <td></td> </tr> </table> <p>2016</p> </div> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p> <p>Set a steel fence post N. of cor.</p> <p>Cor. is located at the base of a sandstone cliff, 100 ft. high, bears E. and S. 60° W.</p> <p>Land, gently rolling to rolling. Soil, sandy loam. No timber; native grasses, rabbit brush, salt brush, and Mormon tea.</p>	T 41 N		R 26 E		S 16		S 15		S 21		S 22					
T 41 N		R 26 E															
S 16		S 15															
S 21		S 22															
40.00	<hr/> <p>From the cor. of secs. 14, 15, 22, and 23.</p> <p>West, bet. secs. 15 and 22.</p> <p>Over gently rolling land.</p> <p>Point for the 1/4 sec. cor. of secs. 15 and 22.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 20 ins. in the ground, encircled with a collar of stone, 2 ft. base, to top, with brass cap mkd.</p> <div style="text-align: center;"> <table style="margin-left: auto; margin-right: auto;"> <tr> <td colspan="2">T 41 N</td> <td colspan="2">R 26 E</td> </tr> <tr> <td colspan="2"></td> <td colspan="2">S 15</td> </tr> <tr> <td colspan="2"></td> <td colspan="2">1/4 ———</td> </tr> <tr> <td colspan="2"></td> <td colspan="2">S 22</td> </tr> </table> <p>2016</p> </div> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p> <p>Set a steel fence post N. of cor.</p>	T 41 N		R 26 E				S 15				1/4 ———				S 22	
T 41 N		R 26 E															
		S 15															
		1/4 ———															
		S 22															

Survey of the Subdivisional Lines,  
T. 41 N., R. 26 E., Gila and Salt River Meridian, Arizona

CHAINS	
80.00	<p>The cor. of secs. 15, 16, 21, and 22.</p> <p>Land, gently rolling to rolling. Soil, sandy loam, and sandstone bedrock. No timber; native grasses, and Mormon tea.</p> <hr/> <p>N. 0°02' W., bet. secs. 15 and 16.</p> <p>Over rugged land.</p>
40.00	<p>Point for the 1/4 sec. cor. of secs. 15 and 16.</p> <p>Set a rebar, 20 ins. long, 5/8 in. diam., 15 ins. in solid sandstone bedrock, cemented in place, with 2 in. diam. brass cap on top, mkd.</p> <p style="text-align: center;">T 41 N R 26 E 1/4 S 16   S 15</p> <p style="text-align: center;">2016</p> <p>from which</p> <p style="padding-left: 40px;">A stainless steel post, 28 ins. long, 2 1/2 ins. diam., set 25 ins. in the ground for a reference monument, bears N. 15°00' E., 50.0 ft. dist. with brass cap mkd. RM T41N R26E 1/4 S15 50.0 FT TO COR 2016 and an arrow pointing to the cor. Deposit a magnet, in a white plastic case, at the base of the stainless steel post, and set a steel fence post nearby.</p> <p style="padding-left: 40px;">A stainless steel post, 28 ins. long, 2 1/2 ins. diam., set 26 ins. in the ground for a reference monument, bears S. 15°00' W., 33.0 ft. dist. with brass cap mkd. RM T41N R26E 1/4 S16 33.0 FT TO COR 2016 and an arrow pointing to the cor. Deposit a magnet, in a white plastic case, at the base of the stainless steel post, and set a steel fence post nearby.</p> <p>Deposit a magnet, without plastic case, at the base of rebar.</p> <p>Cor. is located in a wash, 15 ft. wide, 4 ft. deep, drains W., and is in a canyon, 60 ft. deep, 150 ft. wide, bears S. 70° E. and W.</p>
80.00	<p>Point for the cor. of secs. 9, 10, 15, and 16.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p>

**Survey of the Subdivisional Lines,  
T. 41 N., R. 26 E., Gila and Salt River Meridian, Arizona**

CHAINS

T 41 N	R 26 E
S 9	S 10
S 16	S 15

2016

Deposit a magnet, in a white plastic case, at the base of the stainless steel post.

Set a steel fence post N. of cor.

From this cor. point, third order, National Geodetic Survey station PEAK, monumented with a brass tablet, 3 3/4 ins. diam., firmly set, cemented flush with the surface of a rock outcrop, 5 X 4 ft., projecting 3 ft. above the ground, mkd. PEAK 1949, bears S. 39°31' W., 23.35 chs. dist.

from which

Reference monument No. 2, bears S. 46°34' E., 20.26 ft. dist., monumented with a brass tablet, 3 1/2 ins. diam., firmly set, cemented flush with the surface of a rock outcrop, 15 X 8 ft., projecting 12 ft. above the ground, mkd. NO 2 and an arrow pointing to the cor.

Reference monument No. 1, bears N. 88°05' W., 41.93 ft. dist., monumented with a brass tablet, 3 1/2 ins. diam., firmly set, cemented flush with the surface of a rock outcrop, 3 X 2 ft., projecting 2 ft. above the ground, mkd. NO 1 and an arrow pointing to the cor.

Land, rugged and rolling, with sandstone rock outcrops.  
Soil, sandy loam, and sandstone bedrock.  
No timber; native grasses, salt brush, and Mormon tea.

From the cor. of secs. 10, 11, 14, and 15.

West, bet. secs. 10 and 15.

Over gently rolling land.

40.00 Point for the 1/4 sec. cor. of secs. 10 and 15.

Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.

T 41 N	R 26 E
S 10	
1/4	—
S 15	

2016

Survey of the Subdivisional Lines,  
T. 41 N., R. 26 E., Gila and Salt River Meridian, Arizona

CHAINS	
80.00	<p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p> <p>Raise a mound of stone, 2 ft. base, 1 ft. high, N. of cor.</p> <p>The cor. of secs. 9, 10, 15, and 16.</p> <p>Land, gently rolling to rolling along foothills of N slope. Soil, sandy loam, and sandstone bedrock. No timber; native grasses, salt brush, and Mormon tea.</p> <hr/> <p>N. 0°02' W., bet. secs. 9 and 10.</p> <p>Over gently rolling land.</p>
40.00	<p>Point for the 1/4 sec. cor. of secs. 9 and 10.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 25 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center;"> <p>T 41 N R 26 E</p> <p>1/4</p> <p>S 9   S 10</p> <p>2016</p> </div> <p>from which</p> <p style="padding-left: 40px;">A stainless steel post, 28 ins. long, 2 1/2 ins. diam., set 26 ins. in the ground for a reference monument, bears S. 45°00' E., 30.0 ft. dist. with brass cap mkd. RM T41N R26E 30.0 FT TO COR 1/4 S10 2016 and an arrow pointing to the cor. Deposit a magnet, in a white plastic case, at the base of the stainless steel post, and set a steel fence post nearby.</p> <p style="padding-left: 40px;">A stainless steel post, 28 ins. long, 2 1/2 ins. diam., set 26 ins. in the ground for a reference monument, bears N. 45°00' W., 55.0 ft. dist. with brass cap mkd. RM T41N R26E 55.0 FT TO COR 1/4 S9 2016 and an arrow pointing to the cor. Deposit a magnet, in a white plastic case, at the base of the stainless steel post, and set a steel fence post nearby.</p> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p> <p>Set a steel fence post W. of cor.</p> <p>Cor. is located in a wash, 15 ft. wide, 1 ft. deep, drains N. 25° E.</p>

**Survey of the Subdivisional Lines,  
T. 41 N., R. 26 E., Gila and Salt River Meridian, Arizona**

CHAINS									
53.80	Questar Southern Trails Pipeline Co., underground gas line, bears N. 75° E. and S. 75° W.								
80.00	Point for the cor. of secs. 3, 4, 9, and 10.  Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with brass cap mkd.  <div style="text-align: center;"> <table border="1"> <tr><td>T 41 N</td><td>R 26 E</td></tr> <tr><td>S 4</td><td>S 3</td></tr> <tr><td>S 9</td><td>S 10</td></tr> </table> <p>2016</p> </div> Deposit a magnet, in a white plastic case, at the base of the stainless steel post.  Set a steel fence post N. of cor.  Land, gently rolling. Soil, sandy loam. No timber; native grasses, yucca, and Mormon tea.  <hr/> From the cor. of secs. 2, 3, 10, and 11.  West, bet. secs. 3 and 10.  Over gently rolling land.	T 41 N	R 26 E	S 4	S 3	S 9	S 10		
T 41 N	R 26 E								
S 4	S 3								
S 9	S 10								
40.00	Point for the 1/4 sec. cor. of secs. 3 and 10.  Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.  <div style="text-align: center;"> <table border="1"> <tr><td>T 41 N</td><td>R 26 E</td></tr> <tr><td>S 3</td><td></td></tr> <tr><td>1/4</td><td>—</td></tr> <tr><td>S 10</td><td></td></tr> </table> <p>2016</p> </div> Deposit a magnet, in a white plastic case, at the base of the stainless steel post.  Set a steel fence post N. of cor.	T 41 N	R 26 E	S 3		1/4	—	S 10	
T 41 N	R 26 E								
S 3									
1/4	—								
S 10									
80.00	The cor. of secs. 3, 4, 9, and 10.  Land, gently rolling. Soil, sandy loam. No timber; native grasses, rabbit brush, and Mormon tea.  <hr/>								

Survey of the Subdivisional Lines,  
T. 41 N., R. 26 E., Gila and Salt River Meridian, Arizona

CHAINS	
	N. 0°02' W., bet. secs. 3 and 4. Over gently rolling land.
40.00	Point for the 1/4 sec. cor. of secs. 3 and 4. Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with brass cap mkd.  <div style="text-align: center;">T 41 N R 26 E 1/4 S 4   S 3  2016</div>
	Deposit a magnet, in a white plastic case, at the base of the stainless steel post. Set a steel fence post W. of cor.
48.40	Power line, 2 strand, bears E. and W.
73.50	BIA Route 5058, a bladed dirt road, 25 ft. wide, bears S. 85° E. and N. 85° W.
80.00	Point for the 80 1/16 sec. cor. of secs. 3 and 4. Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with brass cap mkd.  <div style="text-align: center;">T 41 N R 26 E 1/16 S 4   S 3 80  2016</div>
	Deposit a magnet, in a white plastic case, at the base of the stainless steel post. Set a steel fence post W. of cor.
97.85	Point for the closing cor. of secs. 3 and 4, at intersection with the Arizona-Utah State Line. Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with brass cap mkd.

Survey of the Subdivisional Lines,  
T. 41 N., R. 26 E., Gila and Salt River Meridian, Arizona

CHAINS

UTAH

S 4	S 3
T 41 N	R 26 E

CC

2016

Deposit a magnet, in a white plastic case, at the base of the stainless steel post.

Set a steel fence post S. of cor.

From this cor. point, the 249th mile post of the Arizona-Utah State Line, bears N. 89°15.4' E., 8.083 chs. dist., hereinbefore described.

From this same cor. point, the 248th mile post of the Arizona-Utah State Line, bears S. 89°15.4' W., 71.924 chs. dist., monumented with a stainless steel post, 2 1/2 ins. diam., firmly set, projecting 3 ins. above the ground, with a steel fence post, N. of cor., with brass cap mkd. 248M UTAH ARIZ 2002. Add the marks 2015 to the brass cap.

Land, gently rolling.

Soil, sandy loam.

No timber; native grasses, rabbit brush, and Mormon tea.

Point for the 1/4 sec. cor. of sec. 3 only, T. 41 N., R. 26 E., at midpoint on the N. bdy. of sec. 3.

Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with brass cap mkd.

UTAH

1/4	S 3
T 41 N	R 26 E

2016

Deposit a magnet, in a white plastic case, at the base of the stainless steel post.

Set a steel fence post S. of cor.

From this cor. point, the 250th mile post of the Arizona-Utah State Line, bears N. 89°15.4' E., 48.085 chs. dist., hereinbefore described.



**Survey of the Subdivisional Lines,  
T. 41 N., R. 26 E., Gila and Salt River Meridian, Arizona**

CHAINS					
	<p>From this same cor. point, the 249th mile post of the Arizona-Utah State Line, bears S. 89°15.4' W., 31.920 chs. dist., hereinbefore described.</p> <hr style="width: 50%; margin: 10px auto;"/> <p>From the stan. cor. of secs. 32 and 33, on the S. bdy. of the Tp., monumented with a stainless steel post, 2 1/2 ins. diam., firmly set, projecting 2 ins. above the ground, mkd. SC T41N R26E S32 S33 2000. Add the marks 2016 to the brass cap.</p> <p>From this cor. point, a brass tablet, 2 ins. diam., recessed 1 1/2 ins. below top of a concrete collar, 8 ins. diam., firmly set, flush with the surface of the ground, established by Charles W. Dryden (deceased), AZ R.L.S. 4321, with a mound of stone, 1 ft. base, 1/2 ft. high, N. of cor., mkd. T41N CC S33 S5 S4 R26E T40N RLS 4321 1964, bears N. 88°40' E., 1.08 chs. dist.</p> <p>N. 0°03' W., bet. secs. 32 and 33.</p> <p>Over gently rolling land.</p>				
40.00	<p>Point for the 1/4 sec. cor. of secs. 32 and 33.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center; margin: 10px 0;"> <p>T 41 N R 26 E</p> <p style="margin-left: 40px;">1/4</p> <p style="margin-left: 20px;">S 32   S 33</p> <p style="margin-left: 40px;">2016</p> </div> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p> <p>Set a steel fence post NW of cor.</p>				
80.00	<p>Point for the cor. of secs. 28, 29, 32, and 33.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 20 ins. in the ground, encircled with a collar of stone, 2 ft. base, to top, with brass cap mkd.</p> <div style="text-align: center; margin: 10px 0;"> <p>T 41 N R 26 E</p> <table style="margin-left: auto; margin-right: auto; border-collapse: collapse;"> <tr> <td style="border-right: 1px solid black; padding: 0 5px;">S 29</td> <td style="padding: 0 5px;">S 28</td> </tr> <tr> <td style="border-right: 1px solid black; padding: 0 5px;">S 32</td> <td style="padding: 0 5px;">S 33</td> </tr> </table> <p style="margin-left: 40px;">2016</p> </div> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p>	S 29	S 28	S 32	S 33
S 29	S 28				
S 32	S 33				

**Survey of the Subdivisional Lines,  
T. 41 N., R. 26 E., Gila and Salt River Meridian, Arizona**

CHAINS	
	<p>From this cor. point, an open-end iron pipe, 2 1/2 ins. diam., firmly set, projecting 24 ins. above the ground, of unknown origin, mkd. T41N R26E 29 28 32 33 on the S. face, bears S. 34°09' E., 25 lks. dist.</p> <p>Land, gently rolling. Soil, sandy loam, and sandstone bedrock. No timber; native grasses, rabbit brush, salt brush, and Mormon tea.</p> <hr/> <p>From the cor. of secs. 27, 28, 33, and 34. West, bet. secs. 28 and 33. Over gently rolling land.</p>
9.45	Underground water line, bears N. 15° E. and S. 15° W.
40.00	<p>Point for the 1/4 sec. cor. of secs. 28 and 33.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., flush with the surface of the ground, with brass cap mkd.</p> <div style="text-align: center; margin: 10px 0;"> <p>T 41 N R 26 E</p> <p>S 28</p> <p>1/4 ———</p> <p>S 33</p> <p>2016</p> </div> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p> <p>Set a steel fence post N. of cor.</p> <p>Cor. is located 2 lks. S., and 8 lks. W. of an underground water line, bears S. 75° E. and N. 75° W.</p>
46.60	Power line, 2 strand, bears N. 20° E. and S. 20° W.
47.80	BIA Route 5055, a bladed dirt road, 25 ft. wide, bears N. 20° E. and S. 20° W.
56.80	Power line, 2 strand, bears S. 50° E. and N. 50° W.
80.00	<p>The cor. of secs. 28, 29, 32, and 33.</p> <p>Land, gently rolling. Soil, sandy loam. No timber; native grasses, rabbit brush, salt brush, and Mormon tea.</p> <hr/>

**Survey of the Subdivisional Lines,  
T. 41 N., R. 26 E., Gila and Salt River Meridian, Arizona**

CHAINS	
	N. 0°03' W., bet. secs. 28 and 29.
	Over gently rolling land.
6.70	Power line, 2 strand, bears N. 75° E. and S. 75° W.
7.50	Underground water line, bears N. 75° E. and S. 75° W.
40.00	Point for the 1/4 sec. cor. of secs. 28 and 29.
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with brass cap mkd.
	T 41 N R 26 E 1/4 S 29   S 28
	2016
	Deposit a magnet, in a white plastic case, at the base of the stainless steel post.
	Set a steel fence post W. of cor.
	Cor. is located 40 lks. N., and 70 lks. E. of BIA Route 5055, a bladed dirt road, 25 ft. wide, bears S. 60° E. and N. 60° W.
	From this cor. point, the intersection of U.S. Highway 160, bearing N. 65° E. and S. 65° W., and U.S. Highway 191, extending N. 20° W., bears West, 12.15 chs. dist.
43.50	S. right-of-way fence of U.S. Highway 160, barbed wire, 5 strand, parallels highway.
45.10	U.S. Highway 160, an asphalt surfaced road, 36 ft. wide, bears N. 65° E. and S. 65° W.
48.40	N. right-of-way fence of U.S. Highway 160, barbed wire, 5 strand, parallels highway.
80.00	Point for the cor. of secs. 20, 21, 28, and 29.
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.
	T 41 N R 26 E S 20   S 21 S 29   S 28
	2016
	Deposit a magnet, in a white plastic case, at the base of the stainless steel post.

**Survey of the Subdivisional Lines,  
T. 41 N., R. 26 E., Gila and Salt River Meridian, Arizona**

CHAINS	
	<p>Set a steel fence post N. of cor.</p> <p>Land, gently rolling. Soil, sandy loam. No timber; native grasses, salt brush, and Mormon tea.</p> <hr/> <p>From the cor. of secs. 21, 22, 27, and 28.</p> <p>West, bet. secs. 21 and 28.</p> <p>Over gently rolling land.</p>
8.65	N. right-of-way fence of U.S. Highway 160, barbed wire, 5 strand, bears N. 65° E. and S. 65° W.
24.10	Power line, 2 strand, bears N. and S.
40.00	Point for the 1/4 sec. cor. of secs. 21 and 28.
	<p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T 41 N R 26 E S 21 1/4 ——— S 28</p> <p style="text-align: center;">2016</p> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p>
80.00	<p>Set a steel fence post N. of cor.</p> <p>The cor. of secs. 20, 21, 28, and 29.</p> <p>Land, gently rolling. Soil, sandy loam. No timber; native grasses, salt brush, rabbit brush, yucca, and Mormon tea.</p> <hr/> <p>N. 0°03' W., bet. secs. 20 and 21.</p> <p>Over gently rolling land.</p>
30.80	High voltage transmission line, bears E. and W.
40.00	Point for the 1/4 sec. cor. of secs. 20 and 21.
	<p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 25 ins. in the ground, with brass cap mkd.</p>

Survey of the Subdivisional Lines,  
T. 41 N., R. 26 E., Gila and Salt River Meridian, Arizona

CHAINS	
	T 41 N R 26 E 1/4 S 20   S 21  2016
	Deposit a magnet, in a white plastic case, at the base of the stainless steel post.  Set a steel fence post W. of cor.
46.10	Power line, 2 strand, bears S. 85° E. and N. 85° W.
75.20	Wash, 5 ft. wide, 1 ft. deep, drains S. 70° W.
80.00	Point for the cor. of secs. 16, 17, 20, and 21.  Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 19 ins. in the ground, encircled with a collar of stone, 1 ft. base, to top, with brass cap mkd.
	T 41 N R 26 E S 17   S 16 S 20   S 21  2016
	Deposit a magnet, in a white plastic case, at the base of the stainless steel post.  Land, gently rolling, and broken. Soil, sandy loam. No timber; native grasses, salt brush, sage brush, rabbit brush, yucca, and Mormon tea.
	<hr/> From the cor. of secs. 15, 16, 21, and 22.  West, bet. secs. 16 and 21.  Over rolling land.
40.00	Point for the 1/4 sec. cor. of secs. 16 and 21.  Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.

Survey of the Subdivisional Lines,  
T. 41 N., R. 26 E., Gila and Salt River Meridian, Arizona

CHAINS	
	T 41 N R 26 E S 16 1/4 ——— S 21  2016
	Deposit a magnet, in a white plastic case, at the base of the stainless steel post.  Set a steel fence post N. of cor.  Cor. is located 60 lks. W. of a wash, 5 ft. wide, 1 ft. deep, drains S. 25° W.
80.00	The cor. of secs. 16, 17, 20, and 21.  Land, rolling. Soil, sandy loam. No timber; native grasses, salt brush, and Mormon tea.
	N. 0°03' W., bet. secs. 16 and 17.  Over rolling land.
40.00	Point for the 1/4 sec. cor. of secs. 16 and 17.  Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.
	T 41 N R 26 E 1/4 S 17   S 16  2016
	Deposit a magnet, in a white plastic case, at the base of the stainless steel post.  Set a steel fence post W. of cor.
80.00	Point for the cor. of secs. 8, 9, 16, and 17.  Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with brass cap mkd.
	T 41 N R 26 E S 8   S 9 S 17   S 16  2016

**Survey of the Subdivisional Lines,  
T. 41 N., R. 26 E., Gila and Salt River Meridian, Arizona**

CHAINS	
	<p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p> <p>Set a steel fence post N. of cor.</p> <p>Land, rolling. Soil, sandy loam. No timber; native grasses, salt brush, yucca, and Mormon tea.</p> <hr/> <p>From the cor. of secs. 9, 10, 15, and 16.</p> <p>West, bet. secs. 9 and 16.</p> <p>Gently ascending NE slope of rocky ridge.</p>
40.00	<p>Point for the 1/4 sec. cor. of secs. 9 and 16.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center;"> <p>T 41 N R 26 E</p> <p>S 9</p> <p>1/4 ———</p> <p>S 16</p> <p>2016</p> </div>
80.00	<p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p> <p>The cor. of secs. 8, 9, 16, and 17.</p> <p>Land, rolling, and rock outcrops. Soil, sandy loam. No timber; native grasses, and Mormon tea.</p> <hr/> <p>N. 0°03' W., bet. secs. 8 and 9.</p> <p>Gently ascending SW sandy slope of rocky ridge.</p>
30.40	<p>Questar Southern Trails Pipeline Co., underground gas line, bears N. 70° E. and S. 70° W.</p>
40.00	<p>Point for the 1/4 sec. cor. of secs. 8 and 9.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p>

Survey of the Subdivisional Lines,  
T. 41 N., R. 26 E., Gila and Salt River Meridian, Arizona

CHAINS	
	T 41 N R 26 E 1/4 S 8   S 9  2016
	Deposit a magnet, in a white plastic case, at the base of the stainless steel post.
	Set a steel fence post W. of cor.
80.00	Point for the cor. of secs. 4, 5, 8, and 9.  Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with brass cap mkd.
	T 41 N R 26 E S 5   S 4 S 8   S 9  2016
	Deposit a magnet, in a white plastic case, at the base of the stainless steel post.
	Set a steel fence post N. of cor.
	Land, rolling, and rock outcrops. Soil, sandy loam. No timber; native grasses, salt brush, and Mormon tea.
	<hr/> From the cor. of secs. 3, 4, 9, and 10.  West, bet. secs. 4 and 9.  Over nearly level land.
40.00	Point for the 1/4 sec. cor. of secs. 4 and 9.  Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.
	T 41 N R 26 E S 4 1/4 ——— S 9  2016
	Deposit a magnet, in a white plastic case, at the base of the stainless steel post.



**Survey of the Subdivisional Lines,  
T. 41 N., R. 26 E., Gila and Salt River Meridian, Arizona**

CHAINS	
80.00	<p>Set a steel fence post N. of cor.</p> <p>The cor. of secs. 4, 5, 8, and 9.</p> <p>Land, nearly level, and gently rolling. Soil, sandy loam. No timber; native grasses, salt brush, and Mormon tea.</p> <hr/> <p>N. 0°03' W., bet. secs. 4 and 5.</p> <p>Over gently rolling land.</p>
40.00	<p>Point for the 1/4 sec. cor. of secs. 4 and 5.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T 41 N R 26 E 1/4 S 5   S 4  2016</p> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p>
49.60	<p>Set a steel fence post W. of cor.</p> <p>Power line, 2 strand, bears E. and W.</p>
80.00	<p>Point for the 80 1/16 sec. cor. of secs. 4 and 5.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T 41 N R 26 E 1/16 S 5   S 4 80  2016</p> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p>
96.81	<p>Set a steel fence post W. of cor.</p> <p>Point for the closing cor. of secs. 4 and 5, at intersection with the Arizona-Utah State Line.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with brass cap mkd.</p>

Survey of the Subdivisional Lines,  
T. 41 N., R. 26 E., Gila and Salt River Meridian, Arizona

CHAINS

UTAH  
-----  
S 5 | S 4  
T 41 N | R 26 E  
CC

2016

Deposit a magnet, in a white plastic case, at the base of the stainless steel post.

Set a steel fence post S. of cor.

From this cor. point, the 248th mile post of the Arizona-Utah State Line, bears N. 89°15.4' E., 8.082 chs. dist., hereinbefore described.

From this same cor. point, the 247th mile post of the Arizona-Utah State Line, bears S. 89°15.4' W., 71.925 chs. dist., monumented with a stainless steel post, 2 1/2 ins. diam., firmly set, projecting 2 ins. above the ground, with a steel fence post, N. of cor., with brass cap mkd. 247M UTAH ARIZ 2002. Add the marks 2015 to the brass cap.

Land, gently rolling.

Soil, sandy loam.

No timber; native grasses, rabbit brush, and Mormon tea.

Point for the 1/4 sec. cor. of sec. 4 only, T. 41 N., R. 26 E., at midpoint on the N. bdy. of sec. 4.

Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with brass cap mkd.

UTAH  
-----  
1/4 S 4  
T 41 N R 26 E

2016

Deposit a magnet, in a white plastic case, at the base of the stainless steel post.

Set a steel fence post S. of cor.

From this cor. point, the 249th mile post of the Arizona-Utah State Line, bears N. 89°15.4' E., 48.086 chs. dist., hereinbefore described.

Survey of the Subdivisional Lines,  
T. 41 N., R. 26 E., Gila and Salt River Meridian, Arizona

CHAINS	
	<p>From this same cor. point, the 248th mile post of the Arizona-Utah State Line, bears S. 89°15.4' W., 31.921 chs. dist., hereinbefore described.</p> <hr/> <p>From the stan. cor. of secs. 31 and 32, on the S. bdy. of the Tp., monumented with a brass tablet, 3 1/4 ins. diam., firmly set, cemented flush with the surface of a sandstone bedrock, mkd. SC T41N R26E S31 S32 2000. Add the marks 2016 to the brass cap.</p> <p>From this cor. point, the stan. cor. of Tps. 41 N., Rs. 25 and 26 E., monumented with a stainless steel post, 2 1/2 ins. diam., with brass cap, set mkd. and witnessed as described in the field notes of the survey of the Tenth Standard Parallel North (south boundary), T. 41 N., R. 26 E., Gila and Salt River Meridian, Arizona, under group 844, book 5658, page 9, bears East, 80.0 chs. dist.</p> <p>N. 0°03' W., bet. secs. 31 and 32.</p> <p>Over sandstone bluffs.</p>
40.00	<p>Point for the 1/4 sec. cor. of secs. 31 and 32.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 25 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T 41 N R 26 E 1/4 S 31   S 32  2016</p> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p> <p>Set a steel fence post W. of cor.</p> <p>Cor. is located 2.20 chs. S. of base of S. facing sandstone bluff, 60 ft. high, bears S. 80° E. and S. 80° W.</p>
80.00	<p>Point for the cor. of secs. 29, 30, 31, and 32.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T 41 N R 26 E S 30   S 29 S 31   S 32  2016</p>

**Survey of the Subdivisional Lines,  
T. 41 N., R. 26 E., Gila and Salt River Meridian, Arizona**

CHAINS	
	<p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p> <p>Set a steel fence post W. of cor.</p> <p>Land, broken with sandstone outcrops, canyon bluffs. Soil, sandy loam, and rocky. No timber; native grasses, and scattered brush.</p> <hr/> <p>From the cor. of secs. 28, 29, 32, and 33.</p> <p>West, bet. secs. 29 and 32.</p> <p>Over gently rolling land.</p>
24.10	Power line, 2 strand, bears N. 75° E. and S. 75° W.
26.95	Underground water line, bears N. 75° E. and S. 75° W.
40.00	Point for the 1/4 sec. cor. of secs. 29 and 32.
	<p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T 41 N R 26 E S 29 1/4 ——— S 32</p> <p style="text-align: center;">2016</p>
	<p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p> <p>Set a steel fence post N. of cor.</p>
48.60	Underground water line, bears S. 45° E. and N. 45° W.
55.60	Power line, 2 strand, bears S. 40° E. and N. 40° W.
80.00	The cor. of secs. 29, 30, 31, and 32.
	<p>Land, gently rolling. Soil, sandy loam, and sandstone bedrock. No timber; native grasses, and scattered brush.</p> <hr/> <p>West, bet. secs. 30 and 31.</p> <p>Over gently rolling land.</p>
40.00	Point for the 1/4 sec. cor. of secs. 30 and 31.

**Survey of the Subdivisional Lines,  
T. 41 N., R. 26 E., Gila and Salt River Meridian, Arizona**

CHAINS	
	<p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 20 ins. in the ground to sandstone bedrock, in a mound of stone, 3 ft. base, to top, with brass cap mkd.</p> <p style="text-align: center;">T 41 N R 26 E S 30 1/4 ——— S 31</p> <p style="text-align: center;">2016</p> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p> <p>Set a steel fence post N. of cor.</p>
52.03	Entering Mexican Water Trading Post Site, novated to Navajo Nation Business Site Lease #SR-03-173 (Navajo Nation Trust Land) on February 24, 2003. Intersect barbed wire fence for E. bdy., 5 strand, bears N. 4° E. and S. 4° W.
63.78	Intersect interior fence to Mexican Water Trading Post, barbed wire, 5 strand, bears S. 41° E. and N. 41° W.
65.15	Entering Mexican Water Trading Post sewer lagoon, woven and barbed wire fence, bears S. 11° E. and N. 11° W.
67.94	Leaving Mexican Water Trading Post sewer lagoon, and W. bdy. of Mexican Water Trading Post Site, woven and barbed wire fence, bears S. 6° E. and N. 6° W.
70.70	Walker Creek, a wash, 20 ft. wide, 15 ft. deep, drains N. 30° E.
73.59	From this point, a right-of-way monument, bears N., 2.69 chs. dist., monumented with a brass tablet, 3 ins. diam., set flush in a concrete cylinder, 6 ins. diam., firmly set, projecting 23 ins. above the ground, mkd. ARIZONA HIGHWAY DEPT 2971+74.5 1962.
79.91	<p>The cor. of secs. 25, 30, 31, and 36 on the W. bdy. of the Tp., monumented with a stainless steel post, 2 1/2 ins. diam., firmly set, projecting 6 ins. above the ground, with brass cap mkd. T41N R25E R26E S25 S30 S36 S31 2000. Add the marks 2016 to the brass cap.</p> <p>Land, gently rolling, and rocky. Soil, sandy loam, and sandstone bedrock. Timber, Russian olive trees in Walker Creek. Undergrowth, native grasses, and scattered brush.</p> <hr/> <p>From the cor. of secs. 29, 30, 31, and 32.</p> <p>N. 0°03' W., bet. secs. 29 and 30.</p>

**Survey of the Subdivisional Lines,  
T. 41 N., R. 26 E., Gila and Salt River Meridian, Arizona**

CHAINS	
	Over gently rolling land.
9.70	From this point, a right-of-way monument, bears W., 6.82 chs. dist., monumented with a brass tablet, 3 ins. diam., set flush in a concrete cylinder, 6 ins. diam., firmly set, projecting 4 ins. above the ground, mkd. ARIZONA HIGHWAY DEPT ELEV. + STA. 19, with an angle iron, firmly set, projecting 19 ins. above ground, to the E., mkd. P.T. 2927+38.21, and HWY. R. OF W. on the other side.
10.70	S. right-of-way fence of U.S. Highway 160, barbed wire, 5 strand, parallels highway.
12.25	U.S. Highway 160, an asphalt surfaced road, 36 ft. wide, bears N. 80° E. and S. 80° W.
15.40	N. right-of-way fence of U.S. Highway 160, barbed wire, 5 strand, parallels highway.
26.60	Power line, 2 strand, bears S. 50° E. and N. 50° W.
40.00	Point for the 1/4 sec. cor. of secs. 29 and 30.  Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 27 ins. in the ground, with brass cap mkd.  <div style="text-align: center;">                     T 41 N R 26 E                            1/4                      S 30   S 29                        2016                 </div> Deposit a magnet, in a white plastic case, at the base of the stainless steel post.  Set a steel fence post W. of cor.
80.00	Point for the cor. of secs. 19, 20, 29, and 30.  Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 20 ins. in solid sandstone bedrock, encircled with a collar of stone, with brass cap mkd.  <div style="text-align: center;">                     T 41 N R 26 E                      S 19   S 20                      S 30   S 29                        2016                 </div> Deposit a magnet, in a white plastic case, at the base of the stainless steel post.

**Survey of the Subdivisional Lines,  
T. 41 N., R. 26 E., Gila and Salt River Meridian, Arizona**

CHAINS	
	<p>Raise a mound of stone, 2 1/2 ft. base, 2 1/2 ft. high, nearby cor.</p> <p>Land, gently rolling. Soil, sandy loam, and sandstone bedrock. No timber; native grasses, yucca, salt brush, cactus, and Mormon tea.</p> <hr/> <p>From the cor. of secs. 20, 21, 28, and 29.</p> <p>West, bet. secs. 20 and 29.</p> <p>Over nearly level land.</p>
24.30	E. right-of-way fence of U.S. Highway 191, barbed wire, 5 strand, parallels highway.
26.25	U.S. Highway 191, an asphalt surfaced road, 36 ft. wide, bears S. 20° E. and N. 20° W.
28.25	W. right-of-way fence of U.S. Highway 191, barbed wire, 5 strand, parallels highway.
40.00	<p>Point for the 1/4 sec. cor. of secs. 20 and 29.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T 41 N R 26 E S 20 1/4 ——— S 29</p> <p style="text-align: center;">2016</p> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p> <p>Set a steel fence post N. of cor.</p>
80.00	<p>The cor. of secs. 19, 20, 29, and 30.</p> <p>Land, nearly level to gently rolling. Soil, sandy loam. No timber; native grasses, salt brush, and Mormon tea.</p> <hr/> <p>West, bet. secs. 19 and 30.</p> <p>Over exposed sandstone bedrock, and gently rolling land.</p>
40.00	Point for the 1/4 sec. cor. of secs. 19 and 30.

**Survey of the Subdivisional Lines,  
T. 41 N., R. 26 E., Gila and Salt River Meridian, Arizona**

CHAINS	
	<p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 22 ins. in solid sandstone bedrock, with brass cap mkd.</p> <p style="text-align: center;">T 41 N R 26 E S 19 1/4 ——— S 30</p> <p style="text-align: center;">2016</p> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p>
68.25	Walker Creek, a wash, 20 ft. wide, 10 ft. deep, drains N. 20° E.
79.82	<p>The cor. of secs. 19, 24, 25, and 30 on the W. bdy. of the Tp., monumented with a stainless steel post, 2 1/2 ins. diam., firmly set, 47 ins. below the ground, with brass cap mkd. T41N R25E R26E S24 S19 S25 S30 2000. Impracticable to add date. Due to constant shifting of blow sand, left the original cor. in place.</p> <p>At the corner point, above the original stainless steel post</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T 41 N R 25 E   R 26 E S 24   S 19 S 25   S 30</p> <p style="text-align: center;">2016</p> <p>from which</p> <p>A stainless steel post, 28 ins. long, 2 1/2 ins. diam., set 27 ins. in the ground for a reference monument, bears N. 45°00' E., 90.0 ft. dist. with brass cap mkd. RM T41N R26E 90.0 FT TO COR S19 2016 and an arrow pointing to the cor. Deposit a magnet, in a white plastic case, at the base of the stainless steel post, and set a steel fence post nearby.</p> <p>A stainless steel post, 28 ins. long, 2 1/2 ins. diam., set 26 ins. in the ground for a reference monument, bears S. 45°00' E., 75.0 ft. dist. with brass cap mkd. RM T41N R26E 75.0 FT TO COR S30 2016 and an arrow pointing to the cor. Deposit a magnet, in a white plastic case, at the base of the stainless steel post, and set a steel fence post nearby.</p> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p>



**Survey of the Subdivisional Lines,  
T. 41 N., R. 26 E., Gila and Salt River Meridian, Arizona**

CHAINS	
	<p>Set a steel fence post W. of cor.</p> <p>Land, rocky, and gently rolling. Soil, sandstone bedrock, and sandy loam. No timber; native grasses, and rabbit brush.</p> <hr/> <p>From the cor. of secs. 19, 20, 29, and 30.</p> <p>N. 0°03' W., bet. secs. 19 and 20.</p> <p>Over exposed sandstone bedrock, and gently rolling land.</p>
29.00	High voltage transmission line, bears E. and W.
40.00	Point for the 1/4 sec. cor. of secs. 19 and 20.
	<p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p align="center">T 41 N R 26 E 1/4 S 19   S 20</p> <p align="center">2016</p> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p> <p>Set a steel fence post W. of cor.</p> <p>Cor. is located 45 lks. S. of a two track road, bears N. 85° E. and S. 85° W.</p>
59.80	Power line, 2 strand, bears S. 70° E. and N. 70° W.
74.30	Underground water line, bears N. 65° E. and S. 65° W.
80.00	Point for the cor. of secs. 17, 18, 19, and 20.
	<p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p align="center">T 41 N R 26 E S 18   S 17 S 19   S 20</p> <p align="center">2016</p> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p> <p>Set a steel fence post W. of cor.</p>

**Survey of the Subdivisional Lines,  
T. 41 N., R. 26 E., Gila and Salt River Meridian, Arizona**

CHAINS	
	<p>Cor. is located 50 lks. S. of a wash, 10 ft. wide, 5 ft. deep, drains N. 85° W.</p> <p>Land, gently rolling. Soil, sandstone bedrock, and sandy loam. No timber; native grasses, cactus, salt brush, yucca, and Mormon tea.</p> <hr/> <p>From the cor. of secs. 16, 17, 20, and 21.</p> <p>West, bet. secs. 17 and 20.</p> <p>Over rolling land.</p>
40.00	<p>Point for the 1/4 sec. cor. of secs. 17 and 20.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center;"> <p>T 41 N R 26 E</p> <p>S 17</p> <p>1/4 ———</p> <p>S 20</p> <p>2016</p> </div> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p> <p>Set a steel fence post N. of cor.</p> <p>Cor. is located 90 lks. E. of a wash, 5 ft. wide, 1 ft. deep, drains S. 25° W.</p>
43.90	<p>Wash, 10 ft. wide, 3 ft. deep, drains N. 45° W.</p>
62.50	<p>E. right-of-way fence of U.S. Highway 191, barbed wire, 5 strand, parallels highway.</p>
64.70	<p>U.S. Highway 191, an asphalt surfaced road, 36 ft. wide, bears S. 30° E. and N. 30° W.</p>
66.80	<p>W. right-of-way fence of U.S. Highway 191, barbed wire, 5 strand, parallels highway.</p>
68.35	<p>Underground water line, bears S. 30° E. and N. 30° W.</p>
68.70	<p>Underground water line, bears N. 65° E. and S. 65° W.</p>
80.00	<p>The cor. of secs. 17, 18, 19, and 20.</p>

**Survey of the Subdivisional Lines,  
T. 41 N., R. 26 E., Gila and Salt River Meridian, Arizona**

CHAINS	
	<p>Land, rolling. Soil, sandy loam. No timber; native grasses, salt brush, and Mormon tea.</p> <hr/> <p>West, bet. secs. 18 and 19.</p> <p>Over gently rolling land.</p>
24.85	Power line, 2 strand, bears S. 45° E. and N. 45° W.
40.00	<p>Point for the 1/4 sec. cor. of secs. 18 and 19.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 25 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T 41 N R 26 E S 18 1/4 ——— S 19</p> <p style="text-align: center;">2016</p> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p> <p>Set a steel fence post N. of cor.</p>
79.72	<p>The cor. of secs. 13, 18, 19, and 24 on the W. bdy. of the Tp., monumented with a brass tablet, 3 1/4 ins. diam., firmly set, cemented flush with the surface of a sandstone finger ridge, 25 ft. wide, 8 ft. high, bears S. 70° E. and N. 85° W., mkd. T41N R25E R26E S13 S18 S24 S19 2000. Add the marks 2016 to the brass cap.</p> <p>Land, gently rolling. Soil, sandy loam, and sandstone bedrock. No timber; native grasses, and greasewood.</p> <hr/> <p>From the cor. of secs. 17, 18, 19, and 20.</p> <p>N. 0°03' W., bet. secs. 17 and 18.</p> <p>Over gently rolling land.</p>
23.95	Underground water line, bears S. 30° E. and N. 30° W.
24.90	W. right-of-way fence of U.S. Highway 191, barbed wire, 5 strand, parallels highway.
29.20	U.S. Highway 191, an asphalt surfaced road, 36 ft. wide, bears S. 25° E. and N. 25° W.

**Survey of the Subdivisional Lines,  
T. 41 N., R. 26 E., Gila and Salt River Meridian, Arizona**

CHAINS	
33.50	E. right-of-way fence of U.S. Highway 191, barbed wire, 5 strand, parallels highway.
40.00	Point for the 1/4 sec. cor. of secs. 17 and 18.  Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.  <div style="text-align: center;">           T 41 N R 26 E                  1/4            S 18   S 17              2016         </div> Deposit a magnet, in a white plastic case, at the base of the stainless steel post.  Set a steel fence post W. of cor.
74.60	Questar Southern Trails Pipeline Co., underground gas line, bears N. 65° E. and S. 65° W.
80.00	Point for the cor. of secs. 7, 8, 17, and 18.  Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.  <div style="text-align: center;">           T 41 N R 26 E            S 7   S 8            S 18   S 17              2016         </div> Deposit a magnet, in a white plastic case, at the base of the stainless steel post.  Set a steel fence post W. of cor.  Land, gently rolling. Soil, sandy loam. No timber; native grasses, yucca, and Mormon tea.
40.00	<hr/> From the cor. of secs. 8, 9, 16, and 17.  West, bet. secs. 8 and 17.  Over gently rolling land.  Point for the 1/4 sec. cor. of secs. 8 and 17.  Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 25 ins. in the ground, with brass cap mkd.

Survey of the Subdivisional Lines,  
T. 41 N., R. 26 E., Gila and Salt River Meridian, Arizona

CHAINS	
	T 41 N R 26 E S 8 1/4 ——— S 17  2016
	Deposit a magnet, in a white plastic case, at the base of the stainless steel post.
	Set a steel fence post N. of cor.
67.90	Questar Southern Trails Pipeline Co., underground gas line, bears N. 65° E. and S. 65° W.
80.00	The cor. of secs. 7, 8, 17, and 18.  Land, gently rolling. Soil, sandy loam. No timber; native grasses, yucca, and Mormon tea.
	West, bet. secs. 7 and 18.  Over gently rolling land.
22.50	E. right-of-way fence of U.S. Highway 191, barbed wire, 5 strand, parallels highway.
24.60	U.S. Highway 191, an asphalt surfaced road, 36 ft. wide, bears S. 25° E. and N. 25° W.
26.70	W. right-of-way fence of U.S. Highway 191, barbed wire, 5 strand, parallels highway.
27.30	Underground water line, bears S. 30° E. and N. 30° W.
40.00	Point for the 1/4 sec. cor. of secs. 7 and 18.  Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.
	T 41 N R 26 E S 7 1/4 ——— S 18  2016
	Deposit a magnet, in a white plastic case, at the base of the stainless steel post.
	Set a steel fence post N. of cor.

**Survey of the Subdivisional Lines,  
T. 41 N., R. 26 E., Gila and Salt River Meridian, Arizona**

CHAINS	
79.63	<p>The cor. of secs. 7, 12, 13, and 18 on the W. bdy. of the Tp., monumented with a stainless steel post, 2 1/2 ins. diam., firmly set, projecting 4 ins. above the ground, mkd. T41N R25E R26E S12 S7 S13 S18 2000. Add the marks 2016 to the brass cap.</p> <p>Land, gently rolling to rolling. Soil, sandy loam. No timber; native grasses, salt brush, and Mormon tea.</p> <hr/> <p>From the cor. of secs. 7, 8, 17, and 18. N. 0°03' W., bet. secs. 7 and 8. Gently ascending SW sandy slope.</p>
40.00	<p>Point for the 1/4 sec. cor. of secs. 7 and 8.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T 41 N R 26 E 1/4 S 7   S 8  2016</p> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p> <p>Set a steel fence post N. of cor.</p>
80.00	<p>Point for the cor. of secs. 5, 6, 7, and 8.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., flush with the surface of the ground, with brass cap mkd.</p> <p style="text-align: center;">T 41 N R 26 E S 6   S 5 S 7   S 8  2016</p> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p> <p>Set a steel fence post W. of cor.</p> <p>Cor. is located 10 lks. W. of a two track road, bears S. 10° E. and N. 5° W.</p>

Survey of the Subdivisional Lines,  
T. 41 N., R. 26 E., Gila and Salt River Meridian, Arizona

CHAINS	
	<p>Land, gently rolling. Soil, sandy loam, and rocky. No timber; native grasses, salt brush, and Mormon tea.</p> <hr/> <p>From the cor. of secs. 4, 5, 8, and 9.</p> <p>West, bet. secs. 5 and 8.</p> <p>Over gently rolling land.</p>
40.00	<p>Point for the 1/4 sec. cor. of secs. 5 and 8.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center;"> <p>T 41 N R 26 E</p> <p>S 5</p> <p>1/4 ———</p> <p>S 8</p> </div> <p style="text-align: center;">2016</p> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p> <p>Set a steel fence post N. of cor.</p>
80.00	<p>The cor. of secs. 5, 6, 7, and 8.</p> <p>Land, gently rolling. Soil, sandy loam, and rocky. No timber; native grasses, salt brush, yucca, and Mormon tea.</p> <hr/> <p>West, bet. secs. 6 and 7.</p> <p>Over gently rolling land.</p>
40.00	<p>True point for the 1/4 sec. cor. of secs. 6 and 7, falls on the steep cliff face, where it is impracticable to establish a monument.</p> <p>From this true point, the point selected for a witness cor. to the 1/4 sec. cor. of secs. 6 and 7, bears N. 45°00' W., 2.07 chs. dist.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 19 ins. in the ground to bedrock, encircled with a collar of stone, 3 ft. base, to top, with brass cap mkd.</p>

Survey of the Subdivisional Lines,  
T. 41 N., R. 26 E., Gila and Salt River Meridian, Arizona

CHAINS	
	WC T 41 N R 26 E S 6 1/4 ——— S 7 ↘  2016
	Deposit a magnet, in a white plastic case, at the base of the stainless steel post.
	Cor. is located on the N. facing slope of a sandstone bluff, among scattered rock outcrops.
61.10	E. right-of-way fence of U.S. Highway 191, barbed wire, 5 strand, parallels highway.
63.10	U.S. Highway 191, an asphalt surfaced road, 36 ft. wide, bears S. 25° E. and N. 25° W.
65.20	W. right-of-way fence of U.S. Highway 191, barbed wire, 5 strand, parallels highway.
68.35	Underground water line, bears N. 5° E. to turning point, extending N. 70° E., and S. 5° W.
69.35	Power line, 2 strand, bears N. 35° E. and S. 35° W.
79.54	The cor. of secs. 1, 6, 7, and 12 on the W. bdy. of the Tp., monumented with a stainless steel post, 2 1/2 ins. diam., firmly set, projecting 4 ins. above the ground, mkd. T41N R25E R26E S1 S6 S12 S7 2000. Add the marks 2016 to the brass cap.  Land, gently rolling, and broken. Soil, sandy loam, and rocky. No timber; native grasses, brush, and Mormon tea.
	<hr/> From the cor. of secs. 5, 6, 7, and 8.  N. 0°03' W., bet. secs. 5 and 6.  Over gently rolling land.
32.97	From this point, a rebar, 5/8 in. diam., firmly set, projecting 1 in. above the surface of the ground, with NE chain link fence cor. to a Radio Tower, located nearby, with orange plastic cap mkd. NORTHERN SURVEYS PLS 22290, established by Gerald Woods, P.L.S. 22290, unknown date, bears E., 19.65 chs. dist. Radio Tower, 250 ft. high, enclosed with chain link fence, 8 ft. high, 100 x 100 ft., with same rebar as described, at each fence cor. location.



**Survey of the Subdivisional Lines,  
T. 41 N., R. 26 E., Gila and Salt River Meridian, Arizona**

CHAINS	
36.00	Base of sandstone bluff, 150 ft. high, bears S. 55° E. and N. 10° W.
40.00	Point for the 1/4 sec. cor. of secs. 5 and 6.  Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.  <div style="text-align: center;">           T 41 N R 26 E                  1/4            S 6   S 5              2016         </div> Deposit a magnet, in a white plastic case, at the base of the stainless steel post.  Set a steel fence post W. of cor.
62.70	Power line, 2 strand, bears N. 50° E. and S. 50° W.
80.00	Point for the 80 1/16 sec. cor. of secs. 5 and 6.  Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.  <div style="text-align: center;">           T 41 N R 26 E                  1/16            S 6   S 5                  80              2016         </div> Deposit a magnet, in a white plastic case, at the base of the stainless steel post.  Set a steel fence post W. of cor.  Cor. is located 50 lks. N. of a wash, 10 ft. wide, 3 ft. deep, drains S. 45° W.
95.77	Point for the closing cor. of secs. 5 and 6, at intersection with the Arizona-Utah State Line.  Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.  <div style="text-align: center;">           UTAH            -----            S 6   S 5            T 41 N   R 26 E                  CC              2016         </div>

**Survey of the Subdivisional Lines,  
T. 41 N., R. 26 E., Gila and Salt River Meridian, Arizona**

CHAINS

Deposit a magnet, in a white plastic case, at the base of the stainless steel post.

Raise a mound of stone, 3 ft. base, 2 ft. high, S. of cor.

Cor. is located 80 lks. W. of a wash, 6 ft. wide, 2 ft. deep, drains S. 50° W.

From this cor. point, the 247th mile post of the Arizona-Utah State Line, bears N. 89°15.4' E., 8.081 chs. dist., hereinbefore described.

From this same cor. point, the 246th mile post of the Arizona-Utah State Line, bears S. 89°15.4' W., 71.926 chs. dist., monumented with a stainless steel post, 2 1/2 ins. diam., firmly set, flush with the surface of the ground, with a steel fence post, N. of cor., with brass cap mkd. 246M UTAH ARIZ 2002. Add the marks 2015 to the brass cap.

Land, broken, and gently rolling.

Soil, sandy loam, and rocky.

No timber; native grasses, rabbit brush, black brush, and Mormon tea.

---

Point for the 1/4 sec. cor. of sec. 5 only, T. 41 N., R. 26 E., at midpoint on the N. bdy. of sec. 5.

Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with brass cap mkd.

UTAH

1/4 S 5  
T 41 N R 26 E

2016

Deposit a magnet, in a white plastic case, at the base of the stainless steel post.

Set a steel fence post S. of cor.

Cor. is located 90 lks. W. of a wash, 10 ft. wide, 3 ft. deep, drains N. 30° W., and is 1.40 chs. E. of the same meandering wash, drains S. 30° W.

From this cor. point, the 248th mile post of the Arizona-Utah State Line, bears N. 89°15.4' E., 48.085 chs. dist., hereinbefore described.

**Survey of the Subdivisional Lines,  
T. 41 N., R. 26 E., Gila and Salt River Meridian, Arizona**

CHAINS	<p>From this same cor. point, the 247th mile post of the Arizona-Utah State Line, bears S. 89°15.4' W., 31.922 chs. dist., hereinbefore described.</p> <hr/> <p>Point for the 1/4 sec. cor. of sec. 6 only, T. 41 N., R. 26 E., at midpoint on the N. bdy. of sec. 6.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., flush with the surface of the ground, with brass cap mkd.</p> <p align="center">UTAH</p> <hr/> <p align="center">1/4 S 6 T 41 N R 26 E</p> <p align="center">2016</p> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p> <p>Set a steel fence post S. of cor.</p> <p>From this cor. point, the 247th mile post of the Arizona-Utah State Line, bears N. 89°15.4' E., 48.084 chs. dist., hereinbefore described.</p> <p>From this same cor. point, the 246th mile post of the Arizona-Utah State Line, bears S. 89°15.4' W., 31.923 chs. dist., hereinbefore described.</p> <p>From this same cor. point, the closing cor. of secs. 1 and 6 only, Tps. 41 N., Rs. 25 and 26 E., Gila and Salt River Meridian, Arizona, monumented with a stainless steel post, 2 1/2 ins. diam., firmly set, 6 ins. above the ground, with brass cap mkd. S1 S6 R25E R26E T41N CC 2000. Add the marks 2015 to the brass cap, and set a steel fence post N. of cor., bears S. 89°15.4' E., 39.439 chs. dist.</p> <hr/> <p align="center"><b>Subdivision of Section 6, T. 41 N., R. 26 E., Gila and Salt River Meridian, Arizona</b></p> <hr/> <p>From the true point of the 1/4 sec. cor. of secs. 6 and 7. N. 0°04' W., on the N. and S. center line of sec. 6.</p> <p>Over gently rolling land.</p> <p>27.10 Power line, bears N. 50° E. and S. 50° W.</p> <p>40.00 Point for the center 1/4 sec. cor. of sec. 6, at intersection with the E. and W. center line sec. 6.</p>
--------	---

Subdivision of Section 6,  
T. 41 N., R. 26 E., Gila and Salt River Meridian, Arizona

CHAINS	
	<p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T 41 N R 26 E C 1/4 S 6</p> <p style="text-align: center;">2016</p> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p> <p>Set a steel fence post W. of cor.</p>
53.10	Underground water line, bears N. 25° E. and S. 25° W.
71.40	BIA Route 5058, a bladed dirt road, 25 ft. wide, bears N. 45° E. and S. 45° W.
80.00	Point for the center 80 1/16 sec. cor. of sec. 6.
	<p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T 41 N R 26 E C 1/16   S 6 80</p> <p style="text-align: center;">2016</p> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p> <p>Set a steel fence post W. of cor.</p> <p>Cor. is located 10 lks. S. of a wash, 6 ft. wide, 2 ft. deep, drains S. 45° W.</p>
95.25	The 1/4 sec. cor. of sec. 6 only.
	<hr/> <p>From the 1/4 sec. cor. of secs. 5 and 6.</p> <p>West, on the E. and W. center line of sec. 6.</p> <p>Over gently rolling land.</p>
25.50	Power line, bears N. 50° E. and S. 50° W.
40.00	The center 1/4 sec. cor. of sec. 6.
45.70	Underground water line, bears N. 25° E. and S. 25° W.

**Subdivision of Section 6,  
T. 41 N., R. 26 E., Gila and Salt River Meridian, Arizona**

CHAINS	
71.70	E. right-of-way fence of U.S. Highway 191, barbed wire, 5 strand, parallels highway.
73.60	U.S. Highway 191, an asphalt surfaced road, 36 ft. wide, bears S. 10° E. and N. 10° W.
75.50	W. right-of-way fence of U.S. Highway 191, barbed wire, 5 strand, parallels highway.
79.50	The 1/4 sec. cor. of secs. 1 and 6 on the W. bdy. of the Tp., monumented with a stainless steel post, 2 1/2 ins. diam., firmly set, projecting 2 ins. above the ground, with brass cap mkd. T41N R25E R26E 1/4 S1 S6 2000. Add the marks 2016 to the brass cap.
	<hr/> <p>From the 80 1/16 sec. cor. of secs. 5 and 6.</p> <p>West, on the E. and W. center line of the 80 1/16 sec. cor. of sec. 6.</p> <p>Over gently rolling land.</p>
15.80	Power line, 2 strand, bears S. 25° E. and N. 25° W.
29.10	Underground water line, bears N. 30° E. and S. 30° W.
31.55	BIA Route 5058, a bladed dirt road, 25 ft. wide, bears N. 50° E. and S. 50° W.
40.00	The center 80 1/16 sec. cor. of sec. 6.
79.45	The 80 1/16 sec. cor. of secs. 1 and 6 on the W. bdy. of the Tp., monumented with a stainless steel post, 2 1/2 ins. diam., firmly set, projecting 2 ins. above the ground, with brass cap mkd. T41N R25E R26E 80 1/16 S1 S6 2000. Add the marks 2016 to the brass cap.
	<p>Cor. is located 20 lks. E. of the E. right-of-way fence of U.S. Highway 191, barbed wire, 5 strand, bears S. 10° E. and N. 10° W.</p> <hr/> <p style="text-align: center;"><b>Subdivision of Section 7, T. 41 N., R. 26 E., Gila and Salt River Meridian, Arizona</b></p> <hr/> <p>From the 1/4 sec. cor. of secs. 7 and 18.</p> <p>N. 0°04' W., on the N. and S. center line of sec. 7.</p> <p>Over gently rolling land.</p>
22.60	Underground water line, bears S. 40° E. and N. 40° W.

**Subdivision of Section 7,  
T. 41 N., R. 26 E., Gila and Salt River Meridian, Arizona**

CHAINS	
27.50	W. right-of-way fence of U.S. Highway 191, barbed wire, 5 strand, parallels highway.
31.85	U.S. Highway 191, an asphalt surfaced road, 36 ft. wide, bears S. 25° E. and N. 25° W.
36.15	E. right-of-way fence of U.S. Highway 191, barbed wire, 5 strand, parallels highway.
40.00	Point for the center 1/4 sec. cor. of sec. 7, at intersection with the E. and W. center line sec. 7.  Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.  T 41 N R 26 E C 1/4 S 7  2016  Deposit a magnet, in a white plastic case, at the base of the stainless steel post.  Set a steel fence post W. of cor.  Cor. is located 1.90 chs. E. of the E. right-of-way fence of U.S. Highway 191, barbed wire, 5 strand, bears S. 25° E. and N. 25° W.
80.00	The true point of the 1/4 sec. cor. of secs. 6 and 7. <hr/> From the 1/4 sec. cor. of secs. 7 and 8.  West, on the E. and W. center line of sec. 7.  Over gently rolling land.
40.00	The center 1/4 sec. cor. of sec. 7.
41.90	E. right-of-way fence of U.S. Highway 191, barbed wire, 5 strand, parallels highway.
43.95	U.S. Highway 191, an asphalt surfaced road, 36 ft. wide, bears S. 25° E. and N. 25° W.
46.05	W. right-of-way fence of U.S. Highway 191, barbed wire, 5 strand, parallels highway.
52.50	Underground water line, bears N. 25° E. and S. 25° W.

**Subdivision of Section 7,  
T. 41 N., R. 26 E., Gila and Salt River Meridian, Arizona**

CHAINS	
79.59	<p>The 1/4 sec. cor. of secs. 7 and 12 on the W. bdy. of the Tp., monumented with a stainless steel post, 2 1/2 ins. diam., firmly set, projecting 3 ins. above the ground, with brass cap mkd. T41N R26E R26E 1/4 S12 S7 2000. Add the marks 2016 to the brass cap.</p> <hr/> <p style="text-align: center;"><b>Subdivision of Section 13, T. 41 N., R. 26 E., Gila and Salt River Meridian, Arizona</b></p> <hr/> <p>From the 1/4 sec. cor. of secs. 13 and 24.</p> <p>N. 0°01' W., on the N. and S. center line of sec. 13.</p> <p>Over gently rolling land.</p>
7.35	S. right-of-way fence of U.S. Highway 160, barbed wire, 5 strand, parallels highway.
9.00	U.S. Highway 160, an asphalt surfaced road, 36 ft. wide, bears N. 65° E. and S. 65° W.
12.30	N. right-of-way fence of U.S. Highway 160, barbed wire, 5 strand, parallels highway.
40.03	<p>Point for the center 1/4 sec. cor. of sec. 13, at intersection with the E. and W. center line sec. 13.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 25 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T 41 N R 26 E C 1/4 S 13</p> <p style="text-align: center;">2016</p> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p> <p>Set a steel fence post N. of cor.</p>
80.04	<p>The 1/4 sec. cor. of secs. 12 and 13.</p> <hr/> <p>From the 1/4 sec. cor. of secs. 13 and 18 on the W. bdy. of the Tp., monumented with an iron post, 2 1/2 ins. diam., firmly set, projecting 6 ins. above the ground, with a mound of stone, 2 ft. base, 2 ft. high, W. of cor., with brass cap mkd. T41N R26E R27E 1/4 S13 S18 1953 2011. Add the marks 2016 to the brass cap.</p> <p>West, on the E. and W. center line of sec. 13.</p> <p>Over gently rolling land.</p>

Subdivision of Section 13,  
T. 41 N., R. 26 E., Gila and Salt River Meridian, Arizona

CHAINS	
40.00	The center 1/4 sec. cor. of sec. 13.
80.00	The 1/4 sec. cor. of secs. 13 and 14.
<hr/> <p style="text-align: center;">Subdivision of Section 17, T. 41 N., R. 26 E., Gila and Salt River Meridian, Arizona</p> <hr/>	
	From the 1/4 sec. cor. of secs. 17 and 20.
	N. 0°03' W., on the N. and S. center line of sec. 17.
	Over rolling land.
40.00	Point for the center 1/4 sec. cor. of sec. 17, at intersection with the E. and W. center line sec. 17.
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.
	T 41 N R 26 E C 1/4 S 17
	2016
	Deposit a magnet, in a white plastic case, at the base of the stainless steel post.
	Set a steel fence post W. of cor.
80.00	The 1/4 sec. cor. of secs. 8 and 17.
<hr/>	
	From the 1/4 sec. cor. of secs. 16 and 17.
	West, on the E. and W. center line of sec. 17.
	Over rolling land.
40.00	The center 1/4 sec. cor. of sec. 17.
80.00	The 1/4 sec. cor. of secs. 17 and 18.
<hr/> <p style="text-align: center;">Subdivision of Section 18, T. 41 N., R. 26 E., Gila and Salt River Meridian, Arizona</p> <hr/>	
	From the 1/4 sec. cor. of secs. 18 and 19.
	N. 0°04' W., on the N. and S. center line of sec. 18.
	Over gently rolling land.



Subdivision of Section 18,  
T. 41 N., R. 26 E., Gila and Salt River Meridian, Arizona

CHAINS	
15.90	Power line, 2 strand, bears S. 45° E. and N. 45° W.
40.00	Point for the center 1/4 sec. cor. of sec. 18, at intersection with the E. and W. center line sec. 18.  Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 25 ins. in the ground, with brass cap mkd.  T 41 N R 26 E C 1/4 S 18  2016  Deposit a magnet, in a white plastic case, at the base of the stainless steel post.  Set a steel fence post N. of cor.
53.30	Underground water line, bears N. 65° E. and S. 65° W.
56.60	Questar Southern Trails Pipeline Co., underground gas line, bears N. 65° E. and S. 65° W.
80.00	The 1/4 sec. cor. of secs. 7 and 18. <hr/>
	From the 1/4 sec. cor. of secs. 17 and 18.  West, on the E. and W. center line of sec. 18.  Over gently rolling land.
3.15	E. right-of-way fence of U.S. Highway 191, barbed wire, 5 strand, parallels highway.
5.20	U.S. Highway 191, an asphalt surfaced road, 36 ft. wide, bears S. 25° E. and N. 25° W.
7.30	W. right-of-way fence of U.S. Highway 191, barbed wire, 5 strand, parallels highway.
7.80	Underground water line, bears S. 25° E. and N. 25° W.
40.00	The center 1/4 sec. cor. of sec. 18.
63.00	Power line, 2 strand, bears S. 45° E. and N. 45° W.
72.75	Underground water line, bears N. 65° E. and S. 65° W.
74.10	Power line, 2 strand, bears N. 25° E. and S. 25° W.
77.20	Questar Southern Trails Pipeline Co., underground gas line, bears N. 65° E. and S. 65° W.

**Subdivision of Section 18,  
T. 41 N., R. 26 E., Gila and Salt River Meridian, Arizona**

CHAINS	
79.68	<p>The 1/4 sec. cor. of secs. 13 and 18 on the W. bdy. of the Tp., monumented with a stainless steel post, 2 1/2 ins. diam., firmly set, projecting 2 ins. above the ground, with brass cap mkd. T41N R25E R26E 1/4 S13 S18 2000. Add the marks 2016 to the brass cap.</p> <hr/> <p style="text-align: center;"><b>Subdivision of Section 20, T. 41 N., R. 26 E., Gila and Salt River Meridian, Arizona</b></p> <hr/> <p>From the 1/4 sec. cor. of secs. 20 and 29.</p> <p>N. 0°03' W., on the N. and S. center line of sec. 20.</p> <p>Over gently rolling land.</p>
29.90	High voltage transmission line, bears E. and W.
30.80	W. right-of-way fence of U.S. Highway 191, barbed wire, 5 strand, parallels highway.
35.15	U.S. Highway 191, an asphalt surfaced road, 36 ft. wide, bears S. 25° E. and N. 25° W.
40.00	<p>Point for the center 1/4 sec. cor. of sec. 20, at intersection with the E. and W. center line sec. 20.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T 41 N R 26 E C 1/4 S 20</p> <p style="text-align: center;">2016</p> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p> <p>Set a steel fence post W. of cor.</p> <p>Cor. is located 80 lks. N., and 40 lks. E. of the E. right-of-way fence of U.S. Highway 191, barbed wire, 5 strand, parallels highway, and 2.50 chs. E. of U.S. Highway 191, an asphalt surfaced road, 36 ft. wide, bears S. 25° E. and N. 25° W.</p>
42.88	From this point, a right-of-way monument, bears W., 1.94 chs. dist., monumented with a brass tablet, 3 ins. diam., set flush in a concrete cylinder, 6 ins. diam., firmly set, projecting 2 ins. above the ground, mkd. 5052.23 BIA ROADS 1980, with an angle iron, firmly set, nearby, mkd. PC 210+54.63.
50.15	Power line, 2 strand, bears S. 85° E. and N. 85° W.

**Subdivision of Section 20,  
T. 41 N., R. 26 E., Gila and Salt River Meridian, Arizona**

CHAINS	
80.00	<p>The 1/4 sec. cor. of secs. 17 and 20.</p> <hr/> <p>From the 1/4 sec. cor. of secs. 20 and 21. West, on the E. and W. center line of sec. 20. Over nearly level land.</p>
40.00	The center 1/4 sec. cor. of sec. 20.
42.50	U.S. Highway 191, an asphalt surfaced road, 36 ft. wide, bears S. 25° E. and N. 25° W.
44.70	W. right-of-way fence of U.S. Highway 191, barbed wire, 5 strand, parallels highway.
45.26	From this point, a right-of-way monument, bears N., 1.04 chs. dist., monumented with a brass tablet, 3 ins. diam., set flush in a concrete cylinder, 6 ins. diam., firmly set, projecting 2 ins. above the ground, mkd. 5052.23 BIA ROADS 1980, with an angle iron, firmly set, nearby, mkd. PC 210+54.63.
55.70	Underground water line, bears N. 60° E. and S. 60° W.
80.00	The 1/4 sec. cor. of secs. 19 and 20.
<p><b>Subdivision of Section 21, T. 41 N., R. 26 E., Gila and Salt River Meridian, Arizona</b></p> <hr/>	
	<p>From the 1/4 sec. cor. of secs. 21 and 28. N. 0°02' W., on the N. and S. center line of sec. 21. Over gently rolling land.</p>
31.70	High voltage transmission line, bears E. and W.
40.00	<p>Point for the center 1/4 sec. cor. of sec. 21, at intersection with the E. and W. center line sec. 21.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T 41 N R 26 E C 1/4 S 21</p> <p style="text-align: center;">2016</p> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p>

**Subdivision of Section 21,  
T. 41 N., R. 26 E., Gila and Salt River Meridian, Arizona**

CHAINS	
	Set a steel fence post N. of cor.
	Cor. is located 2 chs. S. of a power line, 2 strand, bears S. 85° E. and N. 85° W.
80.00	The 1/4 sec. cor. of secs. 16 and 21.
<hr/>	
	From the 1/4 sec. cor. of secs. 21 and 22.
	West, on the E. and W. center line of sec. 21.
	Over gently rolling land.
20.70	Power line, 2 strand, bears S. 85° E. and N. 85° W.
24.40	Power line, 2 strand, bears S. and terminates 40 lks. N., at intersecting power line, 2 strand, bears S. 85° E. and N. 85° W.
40.00	The center 1/4 sec. cor. of sec. 21.
80.00	The 1/4 sec. cor. of secs. 20 and 21.
<hr/>	
<p><b>Subdivision of Section 22, T. 41 N., R. 26 E., Gila and Salt River Meridian, Arizona</b></p>	
<hr/>	
	From the 1/4 sec. cor. of secs. 22 and 27.
	N. 0°02' W., on the N. and S. center line of sec. 22.
	Over gently rolling land.
16.55	S. right-of-way fence of U.S. Highway 160, barbed wire, 5 strand, parallels highway.
18.20	U.S. Highway 160, an asphalt surfaced road, 36 ft. wide, bears N. 65° E. and S. 65° W.
21.45	N. right-of-way fence of U.S. Highway 160, barbed wire, 5 strand, parallels highway.
33.50	High voltage transmission line, bears E. and W.
40.00	Point for the center 1/4 sec. cor. of sec. 22, at intersection with the E. and W. center line sec. 22.
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.

**Subdivision of Section 22,  
T. 41 N., R. 26 E., Gila and Salt River Meridian, Arizona**

CHAINS	
	T 41 N R 26 E C 1/4 S 22
	2016
	Deposit a magnet, in a white plastic case, at the base of the stainless steel post.
	Set a steel fence post W. of cor.
80.00	The 1/4 sec. cor. of secs. 15 and 22.
	<hr/>
	From the 1/4 sec. cor. of secs. 22 and 23.
	West, on the E. and W. center line of sec. 22.
	Over gently rolling land.
40.00	The center 1/4 sec. cor. of sec. 22.
66.70	Underground water line, bears N. and S.
75.55	Power line, 2 strand, bears N. 85° E. and S. 85° W.
80.00	The 1/4 sec. cor. of secs. 21 and 22.
	<hr/>
	<b>Subdivision of Section 23, T. 41 N., R. 26 E., Gila and Salt River Meridian, Arizona</b>
	<hr/>
	From the 1/4 sec. cor. of secs. 23 and 26.
	N. 0°01' W., on the N. and S. center line of sec. 23.
	Over gently rolling land.
40.00	Point for the center 1/4 sec. cor. of sec. 23, at intersection with the E. and W. center line sec. 23.
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.
	T 41 N R 26 E C 1/4 S 23
	2016
	Deposit a magnet, in a white plastic case, at the base of the stainless steel post.
	Set a steel fence post N. of cor.

**Subdivision of Section 23,  
T. 41 N., R. 26 E., Gila and Salt River Meridian, Arizona**

CHAINS	
43.85	High voltage transmission line, bears N. 65° E. and S. 65° W.
52.00	S. right-of-way fence of U.S. Highway 160, barbed wire, 5 strand, parallels highway.
53.60	U.S. Highway 160, an asphalt surfaced road, 36 ft. wide, bears N. 65° E. and S. 65° W.
56.90	N. right-of-way fence of U.S. Highway 160, barbed wire, 5 strand, parallels highway.
80.00	The 1/4 sec. cor. of secs. 14 and 23.
<hr/>	
	From the 1/4 sec. cor. of secs. 23 and 24.
	West, on the E. and W. center line of sec. 23.
	Over gently rolling land.
40.00	The center 1/4 sec. cor. of sec. 23.
48.10	High voltage transmission line, bears N. 65° E. and S. 65° W.
67.05	S. right-of-way fence of U.S. Highway 160, barbed wire, 5 strand, parallels highway.
70.75	U.S. Highway 160, an asphalt surfaced road, 36 ft. wide, bears N. 65° E. and S. 65° W.
78.30	N. right-of-way fence of U.S. Highway 160, barbed wire, 5 strand, parallels highway.
80.00	The 1/4 sec. cor. of secs. 22 and 23.
<hr/>	
<b>Subdivision of Section 24, T. 41 N., R. 26 E., Gila and Salt River Meridian, Arizona</b>	
<hr/>	
	From the 1/4 sec. cor. of secs. 24 and 25.
	N. 0°01' E., on the N. and S. center line of sec. 24.
	Over gently rolling land.
39.98	Point for the center 1/4 sec. cor. of sec. 24, at intersection with the E. and W. center line sec. 24.
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 16 ins. in the ground to bedrock, in a supporting mound of stone, 4 ft. base, to top, with brass cap mkd.

Subdivision of Section 24,  
T. 41 N., R. 26 E., Gila and Salt River Meridian, Arizona

CHAINS	
	T 41 N R 26 E C 1/4 S 24
	2016
	Deposit a magnet, in a white plastic case, at the base of the stainless steel post.
	Set a steel fence post N. of cor.
	Cor. is located on the W. slope of a rocky and sandy hilltop.
79.98	The 1/4 sec. cor. of secs. 13 and 24.
	<hr/>
	From the 1/4 sec. cor. of secs. 19 and 24 on the E. bdy. of the Tp., monumented with an iron post, 2 1/2 ins. diam., firmly set, projecting 3 ins. above the mound of stone, 4 ft. base, 2 ft. high, with brass cap mkd. T41N R26E R27E 1/4 S24 S19 1953 2011. Add the marks 2016 to the brass cap.
	N. 89°58' W., on the E. and W. center line of sec. 24.
	Over rolling land.
40.01	The center 1/4 sec. cor. of sec. 24.
70.00	Power line, 2 strand, bears N. 25° E. and S. 25° W.
80.00	The 1/4 sec. cor. of secs. 23 and 24.
	<hr/>
	<b>Subdivision of Section 28, T. 41 N., R. 26 E., Gila and Salt River Meridian, Arizona</b>
	<hr/>
	From the 1/4 sec. cor. of secs. 28 and 33.
	N. 0°02' W., on the N. and S. center line of sec. 28.
	Over gently rolling land.
19.90	Power line, 2 strand, bears N. 20° E. and S. 20° W.
40.00	Point for the center 1/4 sec. cor. of sec. 28, at intersection with the E. and W. center line sec. 28.
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.
	T 41 N R 26 E C 1/4 S 28
	2016

**Subdivision of Section 28,  
T. 41 N., R. 26 E., Gila and Salt River Meridian, Arizona**

CHAINS	
	Deposit a magnet, in a white plastic case, at the base of the stainless steel post.
	Set a steel fence post N. of cor.
61.20	S. right-of-way fence of U.S. Highway 160, barbed wire, 5 strand, parallels highway.
61.30	From this point, a right-of-way monument, bears E., 31 lks. dist., monumented with a brass tablet, 3 ins. diam., set flush in a concrete cylinder, 6 ins. diam., firmly set, projecting 10 ins. above the ground, mkd. ARIZONA HIGHWAY DEPT 1961, with an angle iron, firmly set, projecting 24 ins. above ground, to the E., mkd. 2836+91.90, and HWY. R. OF W. on the other side.
62.80	U.S. Highway 160, an asphalt surfaced road, 36 ft. wide, bears N. 65° E. and S. 65° W.
65.45	From this point, a right-of-way monument, bears W., 1.53 chs. dist., monumented with a brass tablet, 3 ins. diam., set flush in a concrete cylinder, 6 ins. diam., firmly set, projecting 10 ins. above the ground, mkd. ARIZONA HIGHWAY DEPT 1961, with an angle iron, firmly set, projecting 24 ins. above ground, to the E., mkd. 2836+91.90, and HWY. R. OF W. on the other side.
66.10	N. right-of-way fence of U.S. Highway 160, barbed wire, 5 strand, parallels highway.
80.00	The 1/4 sec. cor. of secs. 21 and 28.
<hr/>	
	From the 1/4 sec. cor. of secs. 27 and 28.
	West, on the E. and W. center line of sec. 28.
	Over gently rolling land.
33.30	Power line, 2 strand, bears N. 20° E. and S. 20° W.
40.00	The center 1/4 sec. cor. of sec. 28.
80.00	The 1/4 sec. cor. of secs. 28 and 29.
<hr/>	
<b>Subdivision of Section 29, T. 41 N., R. 26 E., Gila and Salt River Meridian, Arizona</b>	
<hr/>	
	From the 1/4 sec. cor. of secs. 29 and 32.
	N. 0°03' W., on the N. and S. center line of sec. 29.
	Over gently rolling land.



Subdivision of Section 29,  
T. 41 N., R. 26 E., Gila and Salt River Meridian, Arizona

CHAINS	
25.36	From this point, a right-of-way monument, bears W., 88 lks. dist., monumented with a brass tablet, 3 ins. diam., set flush in a concrete cylinder, 6 ins. diam., firmly set, projecting 7 ins. above the ground, mkd. ARIZONA HIGHWAY DEPT 1961, with an angle iron, firmly set, to the E., mkd. POT 2895+50.
25.75	S. right-of-way fence of U.S. Highway 160, barbed wire, 5 strand, parallels highway.
27.40	U.S. Highway 160, an asphalt surfaced road, 36 ft. wide, bears N. 65° E. and S. 65° W.
29.52	From this point, a right-of-way monument, bears W., 2.72 chs. dist., monumented with a brass tablet, 3 ins. diam., set flush in a concrete cylinder, 6 ins. diam., firmly set, projecting 6 ins. above the ground, mkd. ARIZONA HIGHWAY DEPT 1961, with an angle iron, firmly set, to the E., mkd. POT 2895+50.
30.70	N. right-of-way fence of U.S. Highway 160, barbed wire, 5 strand, parallels highway.
40.00	Point for the center 1/4 sec. cor. of sec. 29, at intersection with the E. and W. center line sec. 29.  Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with brass cap mkd.  T 41 N R 26 E C 1/4 S 29  2016  Deposit a magnet, in a white plastic case, at the base of the stainless steel post.  Set a steel fence post W. of cor.  Cor. is located 45 lks. W., and 15 lks. N. of a trail road, bears N. 75° E. and S. 75° W.
80.00	The 1/4 sec. cor. of secs. 20 and 29. <hr/> From the 1/4 sec. cor. of secs. 28 and 29.  West, on the E. and W. center line of sec. 29.  Over gently rolling land.
7.80	S. right-of-way fence of U.S. Highway 160, barbed wire, 5 strand, parallels highway.
11.45	U.S. Highway 160, an asphalt surfaced road, 36 ft. wide, bears N. 65° E. and S. 65° W.

**Subdivision of Section 29,  
T. 41 N., R. 26 E., Gila and Salt River Meridian, Arizona**

CHAINS	
12.15	The intersection of U.S. Highway 160, an asphalt surfaced road, bears N. 65° E. and S. 65° W., and U.S. Highway 191, an asphalt surfaced road, bears and N. 20° W.
18.90	N. right-of-way fence of U.S. Highway 160, barbed wire, 5 strand, bears N. 65° E. and S. 65° W.
40.00	The center 1/4 sec. cor. of sec. 29.
80.00	The 1/4 sec. cor. of secs. 29 and 30.
<hr/> <p><b>Subdivision of Section 30, T. 41 N., R. 26 E., Gila and Salt River Meridian, Arizona</b></p> <hr/>	
	From the 1/4 sec. cor. of secs. 30 and 31.
	N. 0°04' W., on the N. and S. center line of sec. 30.
	Over sandstone rock outcrop.
6.25	S. right-of-way fence of U.S. Highway 160, barbed wire, 5 strand, parallels highway.
7.75	U.S. Highway 160, an asphalt surfaced road, 36 ft. wide, bears N. 85° E. and S. 85° W.
10.50	N. right-of-way fence of U.S. Highway 160, barbed wire, 5 strand, parallels highway.
11.30	Underground water line, bears N. 85° E. and S. 85° W.
40.00	Point for the center 1/4 sec. cor. of sec. 30, at intersection with the E. and W. center line sec. 30.
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with brass cap mkd.
	<p>T 41 N R 26 E C 1/4 S 30</p> <p>2016</p>
	Deposit a magnet, in a white plastic case, at the base of the stainless steel post.
	Set a steel fence post W. of cor.
80.00	The 1/4 sec. cor. of secs. 19 and 30.
	<hr/> <p>From the 1/4 sec. cor. of secs. 29 and 30.</p>

Subdivision of Section 30,  
T. 41 N., R. 26 E., Gila and Salt River Meridian, Arizona

CHAINS	<p>West, on the E. and W. center line of sec. 30.</p> <p>Over sandstone rock outcrop.</p> <p>40.00 The center 1/4 sec. cor. of sec. 30.</p> <p>74.00 Walker Creek, a wash, 20 ft. wide, 15 ft. deep, drains N. 30° E.</p> <p>79.86 The 1/4 sec. cor. of secs. 25 and 30 on the W. bdy. of the Tp., monumented with a stainless steel post, 2 1/2 ins. diam., firmly set, projecting 7 ins. above the ground, with brass cap mkd. T41N R25E R26E 1/4 S25 S30 2000. Add the marks 2016 to the brass cap.</p>
	<hr/> <p>GENERAL DESCRIPTION</p> <hr/>
	<p>The area surveyed is within the Navajo Indian Reservation, the north boundary of the township being the Arizona-Utah State Line. The township is in the vicinity of the Mexican Water community. U.S. Highway 160 runs northeasterly and southwesterly through the township, with U.S. Highway 191, also known as BIA Route 12, intersecting in section 29, running northwesterly into the State of Utah. The major graded road, BIA Route 5058, loops around the rocky peaks connecting U.S. Highway 160 and U.S. Highway 191 within the township. BIA Route 5055 runs southerly from U.S. Highway 160 in the east half of section 29. A series of two track roads provide access throughout the township. ATV's were used extensively.</p> <p>Most of the township consists of gently rolling, and rocky terrain, with rocky peaks and sandstone bluffs in the northwest, and southwest portion. Occupancy is scattered throughout the township, and Mexican Water Trading Post falls in the southwest quarter of section 30, and a portion in the northwest quarter of section 31, along U.S. Highway 160.</p> <p>Elevation varies from 4900 to 5850 ft. above sea level. Walker Creek is the principle water course, entering the township in section 31, draining northwesterly into sections 19 and 30. Vegetation is consistent of rabbit brush, salt brush, Mormon tea, and native grasses. Timber is nonexistent throughout the entire township. There is presence of grazing cattle, sheep, and horses in the area. The soil is mostly sandy loam with coverage of sandstone outcrops.</p> <p>The mean magnetic declination of 10° E. was derived from the United States Geological Survey computer program GEOMAG, utilizing the World Magnetic Model for the dates of survey.</p> <hr/>



CERTIFICATE OF SURVEY

I, Fabian Yazzie, Cadastral Surveyor, HEREBY CERTIFY upon honor, that in pursuance of special instructions bearing date of the 17th day of November, 2015, I have dependently resurveyed a portion of the Arizona-Utah State Line (north boundary), surveyed the subdivisional lines and subdivided certain sections, T. 41 N., R. 26 E., of the Gila and Salt River Meridian, in the State of Arizona, which are represented in the foregoing field notes as having been executed by me and under my direction. Said survey has been made in strict conformity with said special instructions, the Manual of Instructions for the Survey of the Public Lands of the United States, 2009, and in specific manner described in the foregoing field notes.

9/14/2016  
\_\_\_\_\_  
(Date)

[Signature]  
\_\_\_\_\_  
(Cadastral Surveyor)

CERTIFICATE OF APPROVAL

BUREAU OF LAND MANAGEMENT  
Phoenix, Arizona

The foregoing field notes of the dependent resurvey a portion of the Arizona-Utah State Line (north boundary), the survey of the subdivisional lines and the subdivision of certain sections, T. 41 N., R. 26 E., Gila and Salt River Meridian, in the State of Arizona, executed by Fabian Yazzie, Cadastral Surveyor, having been critically examined and found correct, are hereby approved.

9/20/2016  
\_\_\_\_\_  
(Date)

[Signature]  
\_\_\_\_\_  
(Chief Cadastral Surveyor of Arizona)

~~CERTIFICATE OF TRANSCRIPT~~

~~I CERTIFY That the foregoing transcript of the field notes of the above described surveys in T. 41 N., R. 26 E., Gila and Salt River Meridian, Arizona, is a true copy of the original field notes.~~

~~\_\_\_\_\_  
(Date)~~

~~\_\_\_\_\_  
(Chief Cadastral Surveyor of Arizona)~~