

ORIGINAL

**UNITED STATES  
DEPARTMENT OF THE INTERIOR  
BUREAU OF LAND MANAGEMENT**

FIELD NOTES  
OF THE  
DEPENDENT RESURVEY OF A PORTION OF THE  
FIFTH STANDARD PARALLEL NORTH (SOUTH BOUNDARY),  
THE INDEPENDENT RESURVEY OF  
A PORTION OF THE FIFTH GUIDE MERIDIAN EAST (WEST BOUNDARY),  
THE EAST BOUNDARY,  
THE SUBDIVISIONAL LINES,  
AND THE SUBDIVISION OF CERTAIN SECTIONS  
**TOWNSHIP 21 NORTH, RANGE 21 EAST,**  
OF THE GILA AND SALT RIVER MERIDIAN,  
IN THE STATE OF ARIZONA.

**EXECUTED BY**

**Fabian Yazzie, Cadastral Surveyor**

Under Special Instructions dated April 28, 2016, approved April 28, 2016, and Supplemental Special Instructions dated September 20, 2016, approved September 20, 2016, which provided for the surveys included under Group No. 1158, and assignment instructions dated April 28, 2016.

**Survey commenced May 10, 2016**

**Survey completed October 18, 2016**

# INDEX DIAGRAM

TOWNSHIP 21 NORTH                      RANGE 21 EAST  
 GILA & SALT RIVER MERIDIAN, ARIZONA

13	6	65	5	54	4	46	3	38	2	29	1	19
	65		64		54		45		37		29	
13	7	63	8	53	9	44	10	36	11	28	12	18
	63		62		53		44		35		27	
12	18	62	17	52	16	43	15	34	14	26	13	17
	61		60		52		42		34		25	
11	19	60	20	50	21	41	22	33	23	24	24	16
	59		58		50		41		32		23	
10	30	57	29	49	28	40	27	31	26	22	25	15
	57		56		48		39		31		21	
9	31	55	32	47	33	38	34	30	35	20	36	14
	8		8		7		6		5		4	

Subdivision of Section 13 ..... Pages 66-67  
 Subdivision of Section 24 ..... Pages 67-68  
 Subdivision of Section 25 ..... Page 69  
 Subdivision of Section 35 ..... Page 70  
 Subdivision of Section 36 ..... Page 71

**T. 21 N., R. 21 E., Gila and Salt River Meridian, Arizona**

## CHAINS

The following field notes describe the dependent resurvey of a portion of the Fifth Standard Parallel North (south boundary), the independent resurvey of a portion of the Fifth Guide Meridian East (west boundary), the east boundary, the subdivisional lines, and the subdivision of certain sections, Township 21 North, Range 21 East, Gila and Salt River Meridian, Arizona.

The history of surveys pertaining to this survey is as follows:

The Fifth Standard Parallel North (south boundary), and east boundary, were surveyed by Frank Follman in 1882. The Fifth Auxiliary Guide Meridian East (west boundary), the north boundary, and the subdivisional lines, were surveyed by A.P. Johnson in 1883. The Fifth Standard Parallel North (south boundary), was dependently resurveyed by Ty White in 1947. The south boundary of T. 22 N., R. 21 E., (north boundary), was dependently resurveyed by Gordon R. Bubel in 2009.

The survey was executed in accordance with the specifications as set forth in the Manual of Survey Instructions for the Public Lands of the United States, 2009, and the Special Instructions dated April 28, 2016, and Supplemental Special Instructions dated September 20, 2016, for Group Number 1158, Arizona.

The true meridian direction and length of all lines were determined by real-time kinematic global positioning system observations using Trimble Navigation R8 model receivers.

Preliminary to the resurvey, the lines of the prior surveys were retraced and the search was made for evidence of all corners and other calls of record. Identified corners were remonumented in their original positions. Lost corners were reestablished and remonumented at proportionate positions based on the official record. No evidence of the original survey was recovered on the East Boundary, West Boundary, and the Subdivisional Lines, therefore these lines have been Independently Resurveyed and the Original survey has been cancelled. Fabian Yazzie's letter to this group, dated August 15, 2016, explainins additional information related to the Independent Resurveys of these lines. The retracement data were thoroughly verified and only the true line field notes are given herein.

Geodetic control was derived from Global Positioning System (GPS) static observations post processed by National Geodetic Survey, Online Positioning User Service (OPUS), utilizing Continuously Operating Reference Stations (CORS) DM4629 AZRV ROUNDVALLEY CORS, DL1882 AZFL NAU FLAGSTAFF CORS, AND DP9946 P008 TUBA\_CITY\_AZ2007 CORS.

**T. 21 N., R. 21 E., Gila and Salt River Meridian, Arizona**

CHAINS

The NAD 83 (2011) (EPOCH: 2010), geographic position of the Standard Corner of Township 21 North, Ranges 21 and 22 East, is as follows:

Latitude: 35°10'13.712" N.                      Longitude: 110°03'19.630" W.

The geographic position of the Standard Corner of Townships 21 and 22 North, Ranges 20 and 21 East, is as follows:

Latitude: 35°15'24.828" N.                      Longitude: 110°09'40.025" W.

The mean magnetic declination is 10° E.

---

**Dependent Resurvey of a portion of the  
Fifth Standard Parallel North (south boundary),  
T. 21 N., R. 21 E., Gila and Salt River Meridian, Arizona**

---

Restoring the dependent resurvey executed by  
Ty White, in 1947

---

Beginning at the stan. cor. of Tp. 21 N., Rs. 21 and 22 E., monumented with an iron post, 3 ins. diam., firmly set, projecting 4 ins. above ground, with brass cap mkd. SC T21N R21E R22E S36 S31 1947. Add the marks 2016 to the brass cap, and set a steel fence post N. of cor.

Cor. is located 56.5 lks. S. of barbed wire fence, 5 strand, bears N. 89°50' E. and S. 89°50' W.

From this cor. point, first order bench mark LEROUX, monumented with a brass tablet, 3 1/2 ins. diam., firmly set, flush in a leaning concrete pillar, 17 x 16 ins., projecting 21 ins. above ground, mkd. U.S. COAST & GEODETIC SURVEY TRIANGULATION STATION LEROUX 1936, bears N. 89°17' W., 14.00 chs. dist.

N. 89°57' W., on the S. bdy. of sec. 36, T. 21 N., R. 21 E.

Gently ascending E. slope of badlands.

7.25            Top of ascension, 30 ft. high, leaving badlands, bears N. 45° E. and S. 45° W.

39.955        The stan. 1/4 sec. cor. of sec. 36, monumented with an iron post, 1 in. diam., firmly set, projecting 5 ins. above ground, with brass cap mkd. SC 1/4 S36 1947. Add the marks T21N R21E 2016 to the brass cap, and set a steel fence post N. of cor.

Cor. is located 33 lks. S. of barbed wire fence, 5 strand, bears N. 89°40' E. and S. 89°40' W.

---

Dependent Resurvey of a portion of the  
Fifth Standard Parallel North (south boundary),  
T. 21 N., R. 21 E., Gila and Salt River Meridian, Arizona

CHAINS	
	N. 89°58' W., beginning new measurement.
	Over gently rolling land.
33.00	Most easterly of two, high voltage transmission lines, bears N. 40° E. and S. 40° W.
35.50	Most westerly of two, high voltage transmission lines, bears N. 40° E. and S. 40° W.
40.00	The stan. cor. of secs. 35 and 36, monumented with an iron post, 2 ins. diam., firmly set, projecting 7 ins. above ground, with brass cap mkd. SC T21N R21E S35 S36 1947. Add the marks 2016 to the brass cap, and set a steel fence post N. of cor.
	Cor. is located 6.5 lks. S. of barbed wire fence, 5 strand, bears N. 89°50' E. and S. 89°50' W.
	<hr/>
	N. 89°58' W., on the S. bdy. of sec. 35, T. 21 N., R. 21 E.
	Over gently rolling land.
5.00	Intersect barbed wire fence, 5 strand, bears N. 89°40' E. and S. 89°40' W.
18.45	Power line, 4 strand, bears N. 20° E. and S. 20° W.
19.65	E. right-of-way fence of BIA Route 6, barbed wire, 5 strand, parallels highway.
21.25	State Highway 77 ending, BIA Route 6 begins, an asphalt surfaced road, 30 ft. wide, bears N. 20° E. and S. 20° W.
22.80	W. right-of-way fence of BIA Route 6, barbed wire, 5 strand, parallels highway.
22.90	Underground fiber optic line, bears N. 20° E. and S. 20° W.
40.00	Point for the stan. 1/4 sec. cor. of sec. 35, at proportionate dist.; there is no remaining evidence of the orig. cor.
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 25 ins. in the ground, with brass cap mkd.
	SC T 21 N R 21 E 1/4 S 35 <hr/>
	2016
	Deposit a magnet, in a white plastic case, at the base of the stainless steel post.

Dependent Resurvey of a portion of the  
Fifth Standard Parallel North (south boundary),  
T. 21 N., R. 21 E., Gila and Salt River Meridian, Arizona

CHAINS	
	<p>Set a steel fence post N. of cor.</p> <p>Cor. is 10 lks. S. of a two-track road, bears E. and W., and 20.5 lks. N. of barbed wire fence, 5 strand, bears N. 89°35' E. and S. 89°35' W.</p>
80.00	<p>The stan. cor. of secs. 34 and 35, monumented with an iron post, 2 ins. diam., firmly set, projecting 17 ins. above ground, with a heavy lean to the N., with brass cap mkd. SC T21N R21E S34 S35 1947.</p> <p>At the corner point</p> <p>Reset the original iron post, 36 ins. long, 31 ins. in the ground, in place, plumbing it.</p> <p>Deposit a magnet, in a white plastic case, at the base of the iron post.</p> <p>Add the marks 2016 to the brass cap, and set a steel fence post N. of cor.</p> <p>Cor. is located 46 lks. N. of barbed wire fence, 5 strand, bears N. 89°43' E. and S. 89°43' W.</p> <hr/> <p>N. 89°57' W., on the S. bdy. of sec. 34, T. 21 N., R. 21 E.</p> <p>Over gently rolling land.</p>
39.96	<p>The stan. 1/4 sec. cor. of sec. 34, monumented with an iron post, 1 in. diam., firmly set, 2 ins. below the surface of the ground, with a bend in the iron post, with brass cap mkd. SC 1/4 S34 1947.</p> <p>At the corner point</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 25 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">SC T 21 N R 21 E 1/4 S 34</p> <hr style="width: 10%; margin: auto;"/> <p style="text-align: center;">2016</p> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p> <p>Deposit orig. iron post, 36 ins. long, horizontally alongside, S. of stainless steel post.</p> <p>Set a steel fence post N. of cor.</p>

Dependent Resurvey of a portion of the  
Fifth Standard Parallel North (south boundary),  
T. 21 N., R. 21 E., Gila and Salt River Meridian, Arizona

CHAINS	
	<p>Cor. is located 72 lks. N. of barbed wire fence, 5 strand, bears N. 89°39' E. and S. 89°39' W.</p> <hr style="width: 20%; margin: 10px auto;"/> <p>N. 89°58' W., beginning new measurement.</p> <p>Over gently rolling land.</p>
39.99	<p>The stan. cor. of secs. 33 and 34, monumented with an iron post, 2 ins. diam., firmly set, projecting 10 ins. above ground, with a heavy lean to the W., with a scattered mound of stone, 1 1/2 ft. base, 1/2 ft. high, N. of cor., with brass cap mkd. SC T21N R21E S33 S34 1947.</p> <p>At the corner point</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 25 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center; margin: 10px 0;"> <p>SC</p> <p>T 21 N R 21 E</p> <p><u>S 33   S 34</u></p> </div> <p style="text-align: center;">2016</p> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p> <p>Deposit orig. iron post, 36 ins. long, horizontally alongside, S. of stainless steel post.</p> <p>Rebuild the mound of stone, 1 1/2 ft. base, 1/2 ft. high, N. of cor.</p> <p>Set a steel fence post N. of cor., and S. of mound of stone.</p> <p>Cor. is located 91 lks. N. of barbed wire fence, 5 strand, bears N. 89°45' E. and S. 89°45' W.</p> <hr style="width: 20%; margin: 10px auto;"/> <p>S. 89°59' W., on the S. bdy. of sec. 33, T. 21 N., R. 21 E.</p> <p>Over gently rolling land.</p>
40.01	<p>The stan. 1/4 sec. cor. of sec. 33, monumented with an iron post, 1 in. diam., firmly set, projecting 7 ins. above ground, with brass cap mkd. SC 1/4 S33 1947. Add the marks T21N R21E 2016 to the brass cap, and set a steel fence post N. of cor.</p> <p>Cor. is located 1.04 chs. N. of barbed wire fence, 5 strand, bears N. 89°57' E. and S. 89°57' W.</p> <hr style="width: 20%; margin: 10px auto;"/>

**Dependent Resurvey of a portion of the  
Fifth Standard Parallel North (south boundary),  
T. 21 N., R. 21 E., Gila and Salt River Meridian, Arizona**

CHAINS	
	<p>N. 89°57' W., beginning new measurement.</p> <p>Over gently rolling land.</p>
39.99	<p>The stan. cor. of secs. 32 and 33, monumented with an iron post, 2 ins. diam., firmly set, projecting 8 ins. above ground, with brass cap mkd. SC T21N R21E S32 S33 1947. Add the marks 2016 to the brass cap, and set a steel fence post N. of cor.</p> <p>From this cor. point, a wood fence cor. post among steel fence posts of barbed wire fences, extending N. 89°38' E., S. 0°55' W., and S. 89°59' W., bears S. 1°50' W., 1.20 chs. dist.</p> <hr/> <p>West, on the S. bdy. of sec. 32, T. 21 N., R. 21 E.</p> <p>Over gently rolling land.</p>
34.30	<p>Top of ascension, 50 ft. high, entering badlands, bears N. 40° E. and S. 40° W.</p>
39.99	<p>The stan. 1/4 sec. cor. of sec. 32, monumented with an iron post, 1 in. diam., firmly set, 18 ins. above ground, with brass cap mkd. SC 1/4 S32 1947.</p> <p>At the corner point</p> <p>Reset the original iron post, 36 ins. long, 30 ins. in the ground, in place.</p> <p>Deposit a magnet, in a white plastic case, at the base of the iron post.</p> <p>Add the marks T21N R21E 2016 to the brass cap, and set a steel fence post N. of cor.</p> <p>Cor. is located 1.33 chs. N. of barbed wire fence, 5 strand, bears S. 89°23' E. and N. 89°23' W.</p> <hr/> <p>N. 89°59' W., beginning new measurement.</p> <p>Over rolling land.</p>
39.97	<p>The stan. cor. of secs. 31 and 32, monumented with an iron post, 2 ins. diam., firmly set, projecting 8 ins. above ground, with brass cap mkd. SC T21N R21E S31 S32 1947. Add the marks 2016 to the brass cap, and set a steel fence post N. of cor.</p> <p>Cor. is located 50 lks. W. of a wash, 10 ft. wide, 3 ft. deep, drains N. 20° W.</p> <p>Cor. is located 1.34 chs. N. of barbed wire fence, 5 strand, bears N. 89°53' E. and S. 89°53' W.</p> <hr/>



**Dependent Resurvey of a portion of the  
Fifth Standard Parallel North (south boundary),  
T. 21 N., R. 21 E., Gila and Salt River Meridian, Arizona**

CHAINS	
	<p>N. 89°58' W., on the S. bdy. of sec. 31, T. 21 N., R. 21 E.</p> <p>At the bottom of ascension, over gently rolling land.</p>
39.97	<p>The stan. 1/4 sec. cor. of sec. 31, monumented with an iron post, 1 in. diam., firmly set, 2 ins. below the surface of the ground, with brass cap mkd. SC 1/4 S31 1947. Add the marks T21N R21E 2016 to the brass cap, and set a steel fence post N. of cor.</p> <p>Cor. is located 1.42 chs. N. of barbed wire fence, 5 strand, bears N. 89°51' E. and S. 89°51' W.</p> <p>Cor. is also located 1.55 chs. E. of a wash, 15 ft. wide, 2 ft. deep, drains N. 50° W.</p> <hr style="width: 20%; margin: 10px auto;"/> <p>N. 89°59' W., beginning new measurement.</p> <p>Over gently rolling land.</p>
40.01	<p>The stan. cor. of Tp. 21 N., Rs. 20 and 21 E., monumented with an iron post, 3 ins. diam., firmly set, projecting 9 ins. above ground, with brass cap mkd. SC T21N R20E R21E S36 S31 2006 1947. Add the marks 2016 to the brass cap.</p> <p>A steel fence post is located alongside, NW of cor.</p> <p>Cor. is located 1.48 chs. N. of barbed wire fence, 5 strand, bears N. 89°53' E. and S. 89°53' W.</p> <hr style="width: 50%; margin: 10px auto;"/> <p style="text-align: center;"><b>Independent Resurvey of a portion of the Fifth Guide Meridian East (west boundary), T. 21 N., R. 21 E., Gila and Salt River Meridian, Arizona</b></p> <hr style="width: 50%; margin: 10px auto;"/> <p>Memorandum: See page 3 for justification of the use of Independent Resurvey method.</p> <hr style="width: 50%; margin: 10px auto;"/> <p>From the stan. cor. of Tp. 21 N., Rs. 20 and 21 E., hereinbefore described.</p> <p>N. 0°09' E., bet. secs. 31 and 36.</p> <p>Over gently rolling land.</p>
40.00	<p>Point for the 1/4 sec. cor. of secs. 31 and 36.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p>

Independent Resurvey of a portion of the  
Fifth Guide Meridian East (west boundary),  
T. 21 N., R. 21 E., Gila and Salt River Meridian, Arizona

CHAINS	
	T 21 N R 20 E   R 21 E 1/4   S 36   S 31  2016
	Deposit a magnet, in a white plastic case, at the base of the stainless steel post.  Set a steel fence post W. of cor.  Cor. is located 2.70 chs. S. of Salt Seeps Wash, 90 ft. wide, with the left cut bank at 4 ft. high, and right bank at 2 ft. high, drains N. 85° W.
72.70	BIA Route 9861, a bladed dirt road, 20 ft. wide, bears S. 85° E. and N. 85° W.
80.00	Point for the cor. of secs. 25, 30, 31, and 36.  Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.
	T 21 N R 20 E   R 21 E S 25   S 30   S 36   S 31  2016
	Deposit a magnet, in a white plastic case, at the base of the stainless steel post.  Set a steel fence post N. of cor.
	N. 0°09' E., bet. secs. 25 and 30.  Over gently rolling land.
40.00	Point for the 1/4 sec. cor. of secs. 25 and 30.  Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.
	T 21 N R 20 E   R 21 E 1/4   S 25   S 30  2016

Independent Resurvey of a portion of the  
Fifth Guide Meridian East (west boundary),  
T. 21 N., R. 21 E., Gila and Salt River Meridian, Arizona

CHAINS									
	Deposit a magnet, in a white plastic case, at the base of the stainless steel post.  Set a steel fence post W. of cor.								
65.20	Entering badlands, bottom of ascension, 40 ft. high, bears N. 30° E. and N. 80° W.								
80.00	Point for the cor. of secs. 19, 24, 25.  Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.								
	<table style="margin: auto; border-collapse: collapse;"> <tr><td colspan="2">T 21 N</td></tr> <tr><td style="border-right: 1px solid black; padding: 0 5px;">R 20 E</td><td style="padding: 0 5px;">R 21 E</td></tr> <tr><td style="border-right: 1px solid black; padding: 0 5px;">S 24</td><td style="padding: 0 5px;">S 19</td></tr> <tr><td style="border-right: 1px solid black; padding: 0 5px;">S 25</td><td style="padding: 0 5px;">S 30</td></tr> </table>	T 21 N		R 20 E	R 21 E	S 24	S 19	S 25	S 30
T 21 N									
R 20 E	R 21 E								
S 24	S 19								
S 25	S 30								
	2016								
	Deposit a magnet, in a white plastic case, at the base of the stainless steel post.								
	<hr style="width: 80%; margin: 10px auto;"/> N. 0°09' E., bet. secs. 24 and 19.  Over rolling badlands.								
40.00	Point for the 1/4 sec. cor. of secs. 24 and 19.  Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with brass cap mkd.								
	<table style="margin: auto; border-collapse: collapse;"> <tr><td colspan="2">T 21 N</td></tr> <tr><td style="border-right: 1px solid black; padding: 0 5px;">R 20 E</td><td style="padding: 0 5px;">R 21 E</td></tr> <tr><td style="border-right: 1px solid black; padding: 0 5px;">1/4</td><td style="padding: 0 5px;"></td></tr> <tr><td style="border-right: 1px solid black; padding: 0 5px;">S 24</td><td style="padding: 0 5px;">S 19</td></tr> </table>	T 21 N		R 20 E	R 21 E	1/4		S 24	S 19
T 21 N									
R 20 E	R 21 E								
1/4									
S 24	S 19								
	2016								
	Deposit a magnet, in a white plastic case, at the base of the stainless steel post.  Set a steel fence post W. of cor.								
	Cor. is located 35 lks. N. of top ridge of badlands, 15 ft. wide, 40 ft. high, bears N. 35° E. and S. 50° W.								
71.30	Leaving badlands, bottom of ascension, 30 ft. high, bears N. 45° E. and S. 85° W. Entering nearly level land.								
80.00	Point for the cor. of secs. 13, 18, 19, and 24.  Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.								

Independent Resurvey of a portion of the  
 Fifth Guide Meridian East (west boundary),  
 T. 21 N., R. 21 E., Gila and Salt River Meridian, Arizona

CHAINS											
	<table border="1" style="margin: auto;"> <tr><td colspan="2">T 21 N</td></tr> <tr><td>R 20 E</td><td>R 21 E</td></tr> <tr><td>S 13</td><td>S 18</td></tr> <tr><td colspan="2"><hr/></td></tr> <tr><td>S 24</td><td>S 19</td></tr> </table>	T 21 N		R 20 E	R 21 E	S 13	S 18	<hr/>		S 24	S 19
T 21 N											
R 20 E	R 21 E										
S 13	S 18										
<hr/>											
S 24	S 19										
	2016										
	Deposit a magnet, in a white plastic case, at the base of the stainless steel post.										
	Set a steel fence post W. of cor.										
	<hr/>										
	N. 0°09' E., bet. secs. 13 and 18.										
	Over nearly level land.										
28.00	Wash, 20 ft. wide, 4 ft. deep, drains S. 80° W.										
40.00	Point for the 1/4 sec. cor. of secs. 13 and 18.										
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.										
	<table border="1" style="margin: auto;"> <tr><td colspan="2">T 21 N</td></tr> <tr><td>R 20 E</td><td>R 21 E</td></tr> <tr><td colspan="2" style="text-align: center;">1/4</td></tr> <tr><td>S 13</td><td>S 18</td></tr> </table>	T 21 N		R 20 E	R 21 E	1/4		S 13	S 18		
T 21 N											
R 20 E	R 21 E										
1/4											
S 13	S 18										
	2016										
	Deposit a magnet, in a white plastic case, at the base of the stainless steel post.										
	Set a steel fence post W. of cor.										
80.00	Point for the cor. of secs. 7, 12, 13, and 18.										
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with brass cap mkd.										
	<table border="1" style="margin: auto;"> <tr><td colspan="2">T 21 N</td></tr> <tr><td>R 20 E</td><td>R 21 E</td></tr> <tr><td>S 12</td><td>S 7</td></tr> <tr><td colspan="2"><hr/></td></tr> <tr><td>S 13</td><td>S 18</td></tr> </table>	T 21 N		R 20 E	R 21 E	S 12	S 7	<hr/>		S 13	S 18
T 21 N											
R 20 E	R 21 E										
S 12	S 7										
<hr/>											
S 13	S 18										
	2016										
	Deposit a magnet, in a white plastic case, at the base of the stainless steel post.										
	Set a steel fence post W. of cor.										
	<hr/>										

Independent Resurvey of a portion of the  
Fifth Guide Meridian East (west boundary),  
T. 21 N., R. 21 E., Gila and Salt River Meridian, Arizona

CHAINS									
	N. 0°09' E., bet. secs. 7 and 12.  Over nearly level land.								
40.00	Point for the 1/4 sec. cor. of secs. 7 and 12. Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.  <div style="text-align: center;"> <table style="margin: auto;"> <tr><td colspan="2">T 21 N</td></tr> <tr><td>R 20 E</td><td>R 21 E</td></tr> <tr><td colspan="2" style="text-align: center;">1/4</td></tr> <tr><td style="border-right: 1px solid black;">S 12</td><td>S 7</td></tr> </table> <p>2016</p> </div>	T 21 N		R 20 E	R 21 E	1/4		S 12	S 7
T 21 N									
R 20 E	R 21 E								
1/4									
S 12	S 7								
	Deposit a magnet, in a white plastic case, at the base of the stainless steel post.  Set a steel fence post W. of cor.								
80.00	Point for the cor. of secs. 1, 6, 7, and 12. Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 25 ins. in the ground, with brass cap mkd.  <div style="text-align: center;"> <table style="margin: auto;"> <tr><td colspan="2">T 21 N</td></tr> <tr><td>R 20 E</td><td>R 21 E</td></tr> <tr><td style="border-right: 1px solid black;">S 1</td><td>S 6</td></tr> <tr><td style="border-right: 1px solid black;">S 12</td><td>S 7</td></tr> </table> <p>2016</p> </div>	T 21 N		R 20 E	R 21 E	S 1	S 6	S 12	S 7
T 21 N									
R 20 E	R 21 E								
S 1	S 6								
S 12	S 7								
	Deposit a magnet, in a white plastic case, at the base of the stainless steel post.  Set a steel fence post W. of cor.  Cor. is located 2.45 chs. S. of BIA Route 9860, a bladed dirt road, 25 ft. wide, bears S. 75° E. and N. 75° W.								
40.00	N. 0°09' E., bet. secs. 1 and 6.  Over nearly level land.  Point for the 1/4 sec. cor. of secs. 1 and 6.  Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with brass cap mkd.								

**Independent Resurvey of a portion of the  
Fifth Guide Meridian East (west boundary),  
T. 21 N., R. 21 E., Gila and Salt River Meridian, Arizona**

CHAINS	
	T 21 N R 20 E R 21 E 1/4 S 1   S 6 2016
	Deposit a magnet, in a white plastic case, at the base of the stainless steel post.  Set a steel fence post W. of cor.
48.20	Left bank of Cottonwood Wash, 4 ft. high, bears N. 75° E. and S. 75° W.
53.75	Center of main channel, within Cottonwood Wash, 30 ft. wide, 5 ft. deep, drains N. 75° W.
55.40	Right bank of Cottonwood Wash, 10 ft. high, bears S. 70° E. and N. 85° W.
76.51	The cor. of Tps. 21 and 22 N., Rs. 20 and 21 E., monumented with a stainless steel post, 2 1/2 ins. diam., firmly set, projecting 4 ins. above ground, with a steel fence post, N. of cor., with brass cap mkd. T22N R20E R21E S36 S31 S1 S6 T21N 2006 2009. Add the marks 2016 to the brass cap.
<hr/> <b>Independent Resurvey of the East Boundary, T. 21 N., R. 21 E., Gila and Salt River Meridian, Arizona</b> <hr/>	
Memorandum: See page 3 for justification of the use of Independent Resurvey method.	
<hr/> From the stan. cor. of Tp. 21 N., Rs. 21 and 22 E., hereinbefore described.  N. 0°02' E., bet. secs. 31 and 36.  Over gently rolling land.	
40.00	Point for the 1/4 sec. cor. of secs. 31 and 36.  Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.
	T 21 N R 21 E R 22 E 1/4 S 36   S 31 2016

**Independent Resurvey of the East Boundary,  
T. 21 N., R. 21 E., Gila and Salt River Meridian, Arizona**

CHAINS											
80.00	<p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p> <p>Set a steel fence post W. of cor.</p> <p>Point for the cor. of secs. 25, 30, 31, and 36.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center;"> <table style="margin: auto;"> <tr><td colspan="2">T 21 N</td></tr> <tr><td>R 21 E</td><td>R 22 E</td></tr> <tr><td>S 25</td><td>S 30</td></tr> <tr><td colspan="2"><hr/></td></tr> <tr><td>S 36</td><td>S 31</td></tr> </table> <p>2016</p> </div> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p> <p>Set a steel fence post N. of cor.</p> <p>Cor. is located 15 lks. S. and 13 lks. E. of most easterly of two, high voltage transmission lines, bears N. 40° E. and S. 40° W.</p> <p>Cor. is also located 2.85 chs. S. and 2.60 chs. E. of most westerly of two, high voltage transmission lines, bears N. 40° E. and S. 40° W.</p> <hr/> <p>N. 0°02' E., bet. secs. 25 and 30.</p> <p>Over gently rolling land.</p>	T 21 N		R 21 E	R 22 E	S 25	S 30	<hr/>		S 36	S 31
T 21 N											
R 21 E	R 22 E										
S 25	S 30										
<hr/>											
S 36	S 31										
40.00	<p>Point for the 1/4 sec. cor. of secs. 25 and 30.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center;"> <table style="margin: auto;"> <tr><td colspan="2">T 21 N</td></tr> <tr><td>R 21 E</td><td>R 22 E</td></tr> <tr><td colspan="2">1/4</td></tr> <tr><td colspan="2"><hr/></td></tr> <tr><td>S 25</td><td>S 30</td></tr> </table> <p>2016</p> </div> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p> <p>Set a steel fence post W. of cor.</p>	T 21 N		R 21 E	R 22 E	1/4		<hr/>		S 25	S 30
T 21 N											
R 21 E	R 22 E										
1/4											
<hr/>											
S 25	S 30										

**Independent Resurvey of the East Boundary,  
T. 21 N., R. 21 E., Gila and Salt River Meridian, Arizona**

CHAINS									
	Cor. is located 1.90 chs. S. of a two track road, bears N. 45° E. and S. 45° W.								
45.25	BIA Route 9068, a graded dirt road, 20 ft. wide, bears S. 55° E. and N. 55° W.								
64.85	Power line, 2 strand, bears S. 65° E. and N. 65° W.								
80.00	Point for the cor. of secs. 19, 24, 25, and 30.  Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.  <div style="text-align: center; margin: 10px 0;"> <table style="margin: auto; border-collapse: collapse;"> <tr><td colspan="2" style="padding: 0 10px;">T 21 N</td></tr> <tr><td style="padding: 0 5px;">R 21 E</td><td style="border-left: 1px solid black; padding: 0 5px;">R 22 E</td></tr> <tr><td style="padding: 0 5px;">S 24</td><td style="border-left: 1px solid black; padding: 0 5px;">S 19</td></tr> <tr><td style="padding: 0 5px;">S 25</td><td style="border-left: 1px solid black; padding: 0 5px;">S 30</td></tr> </table> <p style="margin: 5px 0;">2016</p> </div> Deposit a magnet, in a white plastic case, at the base of the stainless steel post.  Set a steel fence post S. of cor. as a guard post.  Cor. is located in center of two track road, bears N. 5° E. and S. 5° W.  <hr style="width: 80%; margin: 10px auto;"/> N. 0°02' E., bet. secs. 19 and 24.  Over gently rolling land.	T 21 N		R 21 E	R 22 E	S 24	S 19	S 25	S 30
T 21 N									
R 21 E	R 22 E								
S 24	S 19								
S 25	S 30								
40.00	Point for the 1/4 sec. cor. of secs. 19 and 24.  Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.  <div style="text-align: center; margin: 10px 0;"> <table style="margin: auto; border-collapse: collapse;"> <tr><td colspan="2" style="padding: 0 10px;">T 21 N</td></tr> <tr><td style="padding: 0 5px;">R 21 E</td><td style="border-left: 1px solid black; padding: 0 5px;">R 22 E</td></tr> <tr><td colspan="2" style="padding: 0 10px;">1/4</td></tr> <tr><td style="padding: 0 5px;">S 24</td><td style="border-left: 1px solid black; padding: 0 5px;">S 19</td></tr> </table> <p style="margin: 5px 0;">2016</p> </div> Deposit a magnet, in a white plastic case, at the base of the stainless steel post.  Set a steel fence post W. of cor.	T 21 N		R 21 E	R 22 E	1/4		S 24	S 19
T 21 N									
R 21 E	R 22 E								
1/4									
S 24	S 19								
80.00	Point for the cor. of secs. 13, 18, 19, and 24.								



Independent Resurvey of the East Boundary,  
T. 21 N., R. 21 E., Gila and Salt River Meridian, Arizona

CHAINS																					
	<p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 25 ins. in the ground, with brass cap mkd.</p> <table border="0" style="margin-left: auto; margin-right: auto;"> <tr><td colspan="4" style="text-align: center;">T 21 N</td></tr> <tr><td style="text-align: center;">R 21 E</td><td style="border-left: 1px solid black; border-right: 1px solid black; text-align: center;"> </td><td style="text-align: center;">R 22 E</td><td></td></tr> <tr><td style="text-align: center;">S 13</td><td style="border-left: 1px solid black; border-right: 1px solid black; text-align: center;"> </td><td style="text-align: center;">S 18</td><td></td></tr> <tr><td colspan="4" style="text-align: center;">-----</td></tr> <tr><td style="text-align: center;">S 24</td><td style="border-left: 1px solid black; border-right: 1px solid black; text-align: center;"> </td><td style="text-align: center;">S 19</td><td></td></tr> </table> <p style="text-align: center;">2016</p> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p> <p>Set a steel fence post W. of cor.</p> <hr style="width: 50%; margin-left: auto; margin-right: auto;"/> <p>N. 0°02' E., bet. secs. 13 and 18.</p> <p>Over gently rolling land.</p>	T 21 N				R 21 E		R 22 E		S 13		S 18		-----				S 24		S 19	
T 21 N																					
R 21 E		R 22 E																			
S 13		S 18																			
-----																					
S 24		S 19																			
40.00	<p>Point for the 1/4 sec. cor. of secs. 13 and 18.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 25 ins. in the ground, with brass cap mkd.</p> <table border="0" style="margin-left: auto; margin-right: auto;"> <tr><td colspan="4" style="text-align: center;">T 21 N</td></tr> <tr><td style="text-align: center;">R 21 E</td><td style="border-left: 1px solid black; border-right: 1px solid black; text-align: center;"> </td><td style="text-align: center;">R 22 E</td><td></td></tr> <tr><td colspan="4" style="text-align: center;">1/4</td></tr> <tr><td style="text-align: center;">S 13</td><td style="border-left: 1px solid black; border-right: 1px solid black; text-align: center;"> </td><td style="text-align: center;">S 18</td><td></td></tr> </table> <p style="text-align: center;">2016</p> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p> <p>Set a steel fence post W. of cor.</p>	T 21 N				R 21 E		R 22 E		1/4				S 13		S 18					
T 21 N																					
R 21 E		R 22 E																			
1/4																					
S 13		S 18																			
60.10	<p>E. right-of-way fence of BIA Route 6, barbed wire, 5 strand, parallels highway.</p>																				
65.45	<p>BIA Route 6, an asphalt surfaced road, 30 ft. wide, bears N. 15° E. and S. 15° W.</p>																				
70.85	<p>W. right-of-way fence of BIA Route 6, barbed wire, 5 strand, parallels highway.</p>																				
70.90	<p>Underground fiber optic line, bears N. 15° E. and S. 15° W.</p>																				
76.80	<p>Intersect remnants of wooden post hubs, once served as a fence line to grazing ranch, no longer exists, bears S. 89° E. and N. 89° W.</p>																				

**Independent Resurvey of the East Boundary,  
T. 21 N., R. 21 E., Gila and Salt River Meridian, Arizona**

CHAINS									
80.00	<p>Point for the cor. of secs. 7, 12, 13, and 18.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <table style="margin-left: auto; margin-right: auto; border-collapse: collapse;"> <tr> <td colspan="2" style="text-align: center;">T 21 N</td> </tr> <tr> <td style="text-align: center;">R 21 E</td> <td style="text-align: center;">R 22 E</td> </tr> <tr> <td style="text-align: center;">S 12</td> <td style="text-align: center;">S 7</td> </tr> <tr> <td style="text-align: center;">S 13</td> <td style="text-align: center;">S 18</td> </tr> </table> <p style="text-align: center;">2016</p> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p> <p>Set a steel fence post W. of cor.</p> <hr style="width: 50%; margin-left: auto; margin-right: auto;"/> <p>N. 0°02' E., bet. secs. 7 and 12.</p> <p>Over rolling land.</p>	T 21 N		R 21 E	R 22 E	S 12	S 7	S 13	S 18
T 21 N									
R 21 E	R 22 E								
S 12	S 7								
S 13	S 18								
22.75	BIA Route 9860, a bladed dirt road, 25 ft. wide, bears N. 85° E. and S. 85° W.								
40.00	<p>Point for the 1/4 sec. cor. of secs. 7 and 12.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <table style="margin-left: auto; margin-right: auto; border-collapse: collapse;"> <tr> <td colspan="2" style="text-align: center;">T 21 N</td> </tr> <tr> <td style="text-align: center;">R 21 E</td> <td style="text-align: center;">R 22 E</td> </tr> <tr> <td colspan="2" style="text-align: center;">1/4</td> </tr> <tr> <td style="text-align: center;">S 12</td> <td style="text-align: center;">S 7</td> </tr> </table> <p style="text-align: center;">2016</p> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p> <p>Set a steel fence post W. of cor.</p>	T 21 N		R 21 E	R 22 E	1/4		S 12	S 7
T 21 N									
R 21 E	R 22 E								
1/4									
S 12	S 7								
46.75	Top of ascension, 40 ft. high, entering badlands, bears N. 60° E. and S. 65° W.								
53.50	Wash, 4 ft. wide, 1 ft. deep, drains N. 60° W.								
80.00	<p>Point for the cor. of secs. 1, 6, 7, and 12.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p>								

Independent Resurvey of the East Boundary,  
T. 21 N., R. 21 E., Gila and Salt River Meridian, Arizona

CHAINS	<div style="text-align: center; margin-bottom: 20px;"> <table style="margin: auto; border-collapse: collapse;"> <tr><td colspan="2">T 21 N</td></tr> <tr><td style="border-right: 1px solid black; padding: 0 5px;">R 21 E</td><td style="padding: 0 5px;">R 22 E</td></tr> <tr><td style="border-right: 1px solid black; padding: 0 5px;">S 1</td><td style="padding: 0 5px;">S 6</td></tr> <tr><td style="border-right: 1px solid black; padding: 0 5px;">S 12</td><td style="padding: 0 5px;">S 7</td></tr> </table> <p style="margin-top: 5px;">2016</p> </div> <p>from which</p> <p style="margin-left: 40px;">A stainless steel post, 28 ins. long, 2 1/2 ins. diam., set 26 ins. in the ground for a reference monument, bears S. 45°00' W., 50.0 ft. dist. with brass cap mkd. RM T21N R21E S12 50.0 FT TO COR 2016 and an arrow pointing to the cor. Deposit a magnet, in a white plastic case, at the base of the stainless steel post, and set a steel fence post SW of cor.</p> <p style="margin-left: 40px;">A stainless steel post, 28 ins. long, 2 1/2 ins. diam., set 25 ins. in the ground for a reference monument, bears N. 45°00' W., 34.0 ft. dist. with brass cap mkd. RM T21N R21E S1 34.0 FT TO COR 2016 and an arrow pointing to the cor. Deposit a magnet, in a white plastic case, at the base of the stainless steel post, and set a steel fence post NW of cor.</p> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p> <p>Set a steel fence post W. of cor.</p> <p>Cor. is located on the NW slope of small spur ridge, 8 ft. high, bears E. and W.</p> <hr style="width: 60%; margin-left: 0;"/> <p>N. 0°02' E., bet. secs. 1 and 6.</p> <p>Over rolling land.</p> <p>30.65 Power line, 2 strand, bears N. 85° E. and S. 85° W.</p> <p>40.00 Point for the 1/4 sec. cor. of secs. 1 and 6.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 25 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center; margin-top: 20px;"> <table style="margin: auto; border-collapse: collapse;"> <tr><td colspan="2">T 21 N</td></tr> <tr><td style="border-right: 1px solid black; padding: 0 5px;">R 21 E</td><td style="padding: 0 5px;">R 22 E</td></tr> <tr><td colspan="2" style="text-align: center;">1/4</td></tr> <tr><td style="border-right: 1px solid black; padding: 0 5px;">S 1</td><td style="padding: 0 5px;">S 6</td></tr> </table> <p style="margin-top: 5px;">2016</p> </div>	T 21 N		R 21 E	R 22 E	S 1	S 6	S 12	S 7	T 21 N		R 21 E	R 22 E	1/4		S 1	S 6
T 21 N																	
R 21 E	R 22 E																
S 1	S 6																
S 12	S 7																
T 21 N																	
R 21 E	R 22 E																
1/4																	
S 1	S 6																

**Independent Resurvey of the East Boundary,  
T. 21 N., R. 21 E., Gila and Salt River Meridian, Arizona**

CHAINS	
	<p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p> <p>Set a steel fence post W. of cor.</p> <p>Cor. is located on top of nearly flat plateau.</p>
43.50	Bladed dirt road, 12 ft. wide, bears N. 65° E. and S. 65° W.
45.70	Top of ascension, 150 ft. high, descend into badlands, bears N. 45° E. and S. 65° W.
71.10	Power line, 2 strand, bears N. 10° E. and S. 10° W.
79.77	<p>The cor. of Tps. 21 and 22 N., Rs. 21 and 22 E., monumented with a stainless steel post, 2 1/2 ins. diam., firmly set, projecting 1 in. above ground, with a mound of stone, 4 ft. base, 1 1/2 ft. high, S. of cor., with brass cap mkd. T22N R21E R22E S36 S31 S1 S6 T21N 2006 2009. Add the marks 2016 to the brass cap.</p> <hr/> <p style="text-align: center;"><b>Independent Resurvey of the Subdivisional Lines, T. 21 N., R. 21 E., Gila and Salt River Meridian, Arizona</b></p> <hr/> <p>Memorandum: See page 3 for justification of the use of Independent Resurvey method.</p> <hr/> <p>From the stan. cor. of secs. 35 and 36, on the S. bdy. of the Tp., hereinbefore described.</p> <p>N. 0°01' W., bet. secs. 35 and 36.</p> <p>Over gently rolling land.</p>
40.00	<p>Point for the 1/4 sec. cor. of secs. 35 and 36.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T 21 N R 21 E 1/4 S 35   S 36 2016</p> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p> <p>Set a steel fence post W. of cor.</p>
50.00	Power line, 4 strand, bears N. 20° E. and S. 20° W.

**Independent Resurvey of the Subdivisional Lines,  
T. 21 N., R. 21 E., Gila and Salt River Meridian, Arizona**

CHAINS									
52.00	E. right-of-way fence of BIA Route 6, barbed wire, 5 strand, parallels highway.								
56.10	BIA Route 6, an asphalt surfaced road, 30 ft. wide, bears N. 20° E. and S. 20° W.								
60.25	W. right-of-way fence of BIA Route 6, barbed wire, 5 strand, parallels highway.								
60.30	Underground fiber optic line, bears N. 20° E. and S. 20° W.								
80.00	<p>Point for the cor. of secs. 25, 26, 35, and 36.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 25 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center; margin: 10px 0;"> <table style="margin: auto; border-collapse: collapse;"> <tr> <td style="padding: 0 10px;">T 21 N</td> <td style="padding: 0 10px;">R 21 E</td> </tr> <tr> <td style="border-right: 1px solid black; padding: 0 5px;">S 26</td> <td style="padding: 0 5px;">S 25</td> </tr> <tr> <td style="border-right: 1px solid black; padding: 0 5px;">S 35</td> <td style="padding: 0 5px;">S 36</td> </tr> </table> </div> <p style="text-align: center; margin: 10px 0;">2016</p> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p> <p>Set a steel fence post W. of cor.</p> <p>Land, gently rolling. Soil, sandy loam. No timber; native grasses, cactus, yucca, and Mormon tea.</p> <hr style="width: 50%; margin: 20px auto;"/> <p>From the cor. of secs. 25, 30, 31, and 36, on the E. bdy. of the Tp., hereinbefore described.</p> <p>N. 89°58' W., bet. secs. 25 and 36.</p> <p>Over gently rolling land.</p>	T 21 N	R 21 E	S 26	S 25	S 35	S 36		
T 21 N	R 21 E								
S 26	S 25								
S 35	S 36								
40.00	<p>Point for the 1/4 sec. cor. of secs. 25 and 36.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 25 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center; margin: 10px 0;"> <table style="margin: auto; border-collapse: collapse;"> <tr> <td style="padding: 0 10px;">T 21 N</td> <td style="padding: 0 10px;">R 21 E</td> </tr> <tr> <td style="padding: 0 5px;"></td> <td style="padding: 0 5px;">S 25</td> </tr> <tr> <td style="padding: 0 5px;">1/4</td> <td style="padding: 0 5px;">—</td> </tr> <tr> <td style="padding: 0 5px;"></td> <td style="padding: 0 5px;">S 36</td> </tr> </table> </div> <p style="text-align: center; margin: 10px 0;">2016</p> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p>	T 21 N	R 21 E		S 25	1/4	—		S 36
T 21 N	R 21 E								
	S 25								
1/4	—								
	S 36								

**Independent Resurvey of the Subdivisional Lines,  
T. 21 N., R. 21 E., Gila and Salt River Meridian, Arizona**

CHAINS	
	Set a steel fence post N. of cor.
68.25	Power line, 2 strand, bears N. 20° E. and S. 20° W.
69.00	E. right-of-way fence of BIA Route 6, barbed wire, 5 strand, parallels highway.
70.60	BIA Route 6, an asphalt surfaced road, 30 ft. wide, bears N. 20° E. and S. 20° W.
72.25	W. right-of-way fence of BIA Route 6, barbed wire, 5 strand, parallels highway.
72.30	Underground fiber optic line, bears N. 20° E. and S. 20° W.
80.00	Point for the cor. of secs. 25, 26, 35, and 36.
	Land, gently rolling. Soil, sandy loam. No timber; native grasses, cactus, yucca, and Mormon tea.
	<hr/>
	N. 0°01' W., bet. secs. 25 and 26.
	Over gently rolling land.
40.00	Point for the 1/4 sec. cor. of secs. 25 and 26.
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with brass cap mkd.
	T 21 N R 21 E 1/4 S 26   S 25  2016
	Deposit a magnet, in a white plastic case, at the base of the stainless steel post.
	Set a steel fence post W. of cor.
58.00	Power line, 2 strand, bears N. 55° E. and S. 55° W.
68.75	Intersect fence to enclosed field, barbed wire, 4 strand, bears N. 55° E. and S. 55° W.
80.00	Point for the cor. of secs. 23, 24, 25, and 26.
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 27 ins. in the ground, with brass cap mkd.

Independent Resurvey of the Subdivisional Lines,  
T. 21 N., R. 21 E., Gila and Salt River Meridian, Arizona

CHAINS									
	<table border="0"> <tr> <td>T 21 N</td> <td>R 21 E</td> </tr> <tr> <td>S 23</td> <td>S 24</td> </tr> <tr> <td>S 26</td> <td>S 25</td> </tr> </table>	T 21 N	R 21 E	S 23	S 24	S 26	S 25		
T 21 N	R 21 E								
S 23	S 24								
S 26	S 25								
	2016								
	<p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p> <p>Set a steel fence post W. of cor.</p> <p>Land, gently rolling. Soil, sandy loam. No timber; native grasses, cactus, cholla, rabbit brush, and yucca.</p> <hr/> <p>From the cor. of secs. 19, 24, 25, and 30, on the E. bdy. of the Tp., hereinbefore described.</p> <p>N. 89°58' W., bet. secs. 24 and 25.</p> <p>Over gently rolling land.</p>								
33.10	Power line, 2 strand, bears S. 65° E. and N. 65° W.								
40.02	Point for the 1/4 sec. cor. of secs. 24 and 25.								
	<p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 27 ins. in the ground, with brass cap mkd.</p>								
	<table border="0"> <tr> <td>T 21 N</td> <td>R 21 E</td> </tr> <tr> <td></td> <td>S 24</td> </tr> <tr> <td>1/4</td> <td>—</td> </tr> <tr> <td></td> <td>S 25</td> </tr> </table>	T 21 N	R 21 E		S 24	1/4	—		S 25
T 21 N	R 21 E								
	S 24								
1/4	—								
	S 25								
	2016								
	<p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p> <p>Set a steel fence post W. of cor.</p> <p>From this cor. point, a Department of Interior Geological Survey bench mark, monumented with a brass tablet, 3 3/4 ins. diam., firmly set, flush in a square concrete pillar, 10 x 10 ins., projecting 7 ins. above ground, located 5.5 lks. W. of the W. right-of-way fence of BIA Route 6, barbed wire, 5 strand, bears N. 15° E. and S. 15° W., mkd. ELEV. 5637 FT ABOVE SEA 3 MPS 1972, bears S. 50°31' W., 6.77 chs. dist.</p> <p>Cor. is located 2.55 chs. S. and 75 lks. E. of the E. right-of-way fence of BIA Route 6, barbed wire, 5 strand, bears N. 15° E. and S. 15° W.</p>								

**Independent Resurvey of the Subdivisional Lines,  
T. 21 N., R. 21 E., Gila and Salt River Meridian, Arizona**

CHAINS	
42.35	BIA Route 6, an asphalt surfaced road, 30 ft. wide, bears N. 15° E. and S. 15° W.
43.90	W. right-of-way fence of BIA Route 6, barbed wire, 5 strand, parallels highway.
43.95	Underground fiber optic line, bears N. 15° E. and S. 15° W.
44.55	Power line, 2 strand, bears N. 60° E. and S. 60° W.
45.70	Power line, 4 strand, bears N. 5° E. and S. 5° W.
64.20	Intersect fence to enclosed field, barbed wire, 4 strand, bears N. 55° E. and S. 55° W.
80.04	Point for the cor. of secs. 23, 24, 25, and 26.  Land, gently rolling. Soil, sandy loam. No timber; native grasses, cactus, yucca, and Mormon tea.
	N. 0°01' W., bet. secs. 23 and 24.
	Over gently rolling land.
17.40	Intersect fence to enclosed field, barbed wire, 4 strand, bears S. 45° E. and N. 45° W.
40.00	Point for the 1/4 sec. cor. of secs. 23 and 24.  Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with brass cap mkd.
	T 21 N R 21 E 1/4 S 23   S 24  2016
	Deposit a magnet, in a white plastic case, at the base of the stainless steel post.
	Set a steel fence post W. of cor.
80.00	Point for the cor. of secs. 13, 14, 23, and 24.  Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 28 ins. in the ground, with brass cap mkd.



Independent Resurvey of the Subdivisional Lines,  
T. 21 N., R. 21 E., Gila and Salt River Meridian, Arizona

CHAINS															
	<table border="1" style="margin: auto;"> <tr> <td>T 21 N</td> <td>R 21 E</td> </tr> <tr> <td>S 14</td> <td>S 13</td> </tr> <tr> <td>S 23</td> <td>S 24</td> </tr> </table> <p>2016</p> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p> <p>Set a steel fence post W. of cor.</p> <p>Land, gently rolling. Soil, sandy loam. No timber; native grasses, cactus, rabbit brush, yucca, and Mormon tea.</p> <hr/> <p>From the cor. of secs. 13, 18, 19, and 24, on the E. bdy. of the Tp., hereinbefore described.</p> <p>N. 89°58' W., bet. secs. 13 and 24.</p> <p>Over gently rolling land.</p> <p>17.45 E. right-of-way fence of BIA Route 6, barbed wire, 5 strand, parallels highway.</p> <p>19.05 BIA Route 6, an asphalt surfaced road, 30 ft. wide, bears N. 15° E. and S. 15° W.</p> <p>20.65 W. right-of-way fence of BIA Route 6, barbed wire, 5 strand, and an underground fiber optic line alongside, both parallel the highway.</p> <p>31.70 Power line, 2 strand, bears N. 10° E. and S. 10° W.</p> <p>37.70 Power line, 4 strand, bears N. 5° E. and S. 5° W.</p> <p>40.04 Point for the 1/4 sec. cor. of secs. 13 and 24.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;"> <table border="1" style="margin: auto;"> <tr> <td>T 21 N</td> <td>R 21 E</td> </tr> <tr> <td></td> <td>S 13</td> </tr> <tr> <td>1/4</td> <td>—</td> </tr> <tr> <td></td> <td>S 24</td> </tr> </table> <p>2016</p> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p> </p>	T 21 N	R 21 E	S 14	S 13	S 23	S 24	T 21 N	R 21 E		S 13	1/4	—		S 24
T 21 N	R 21 E														
S 14	S 13														
S 23	S 24														
T 21 N	R 21 E														
	S 13														
1/4	—														
	S 24														

Independent Resurvey of the Subdivisional Lines,  
T. 21 N., R. 21 E., Gila and Salt River Meridian, Arizona

CHAINS	
	Set a steel fence post N. of cor.
80.08	Point for the cor. of secs. 13, 14, 23, and 24.  Land, gently rolling. Soil, sandy loam. No timber; native grasses, cactus, rabbit brush, and Mormon tea.
	-----
	N. 0°01' W., bet. secs. 13 and 14.  Over gently rolling land.
37.30	Two track road, bears N. 65° E. and S. 70° W.
40.00	Point for the 1/4 sec. cor. of secs. 13 and 14.  Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 28 ins. in the ground, with brass cap mkd.
	T 21 N R 21 E 1/4 S 14   S 13  2016
	from which
	A stainless steel post, 28 ins. long, 2 1/2 ins. diam., set 24 ins. in the ground for a reference monument, bears S. 45°00' E., 115.0 ft. dist. with brass cap mkd. RM T21N R21E 115.0 FT TO COR 1/4 S13 2016 and an arrow pointing to the cor. Deposit a magnet, in a white plastic case, at the base of the stainless steel post, and set a steel fence post SE of cor.
	A stainless steel post, 28 ins. long, 2 1/2 ins. diam., set 24 ins. in the ground for a reference monument, bears S. 45°00' W., 170.0 ft. dist. with brass cap mkd. RM T21N R21E 170.0 FT TO COR 1/4 S14 2016 and an arrow pointing to the cor. Deposit a magnet, in a white plastic case, at the base of the stainless steel post, and set a steel fence post SW of cor.
	Deposit a magnet, in a white plastic case, at the base of the stainless steel post.
	Set a steel fence post W. of cor.
	Cor. is located on the N. slope of badlands, and is 85 lks. N. of top ascension, 60 ft. high, descending into badlands, bears N. 75° E. and S. 80° W.

**Independent Resurvey of the Subdivisional Lines,  
T. 21 N., R. 21 E., Gila and Salt River Meridian, Arizona**

CHAINS									
76.90	Intersect remnants of wooden post hubs, once served as a fence line to grazing ranch, no longer exists, bears N. 89° E. and S. 89° W.								
80.00	<p>Point for the cor. of secs. 11, 12, 13, and 14.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center;"> <table style="margin: auto;"> <tr> <td>T 21 N</td> <td>R 21 E</td> </tr> <tr> <td>S 11</td> <td>S 12</td> </tr> <tr> <td>S 14</td> <td>S 13</td> </tr> </table> <p>2016</p> </div> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p> <p>Set a steel fence post W. of cor.</p> <p>Land, gently rolling to rolling. Soil, sandy loam and clay. No timber; native grasses, rabbit brush, and salt brush.</p> <hr/> <p>From the cor. of secs. 7, 12, 13, and 18, on the E. bdy. of the Tp., hereinbefore described.</p> <p>N. 89°58' W., bet. secs. 12 and 13.</p> <p>Over gently rolling land.</p>	T 21 N	R 21 E	S 11	S 12	S 14	S 13		
T 21 N	R 21 E								
S 11	S 12								
S 14	S 13								
8.63	From this point, center of dilapidated windmill, 8 x 8 ft. base, 35 ft. high, with a steel water tank, 26 ft. diam., 8 ft. high, alongside, bears N., 3.97 chs. dist.								
19.10	Power line, 2 strand, bears N. 10° E. and S. 10° W.								
29.70	Power line, 4 strand, bears N. 5° E. and S. 5° W.								
40.06	<p>Point for the 1/4 sec. cor. of secs. 12 and 13.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 25 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center;"> <table style="margin: auto;"> <tr> <td>T 21 N</td> <td>R 21 E</td> </tr> <tr> <td></td> <td>S 12</td> </tr> <tr> <td>1/4</td> <td>—</td> </tr> <tr> <td></td> <td>S 13</td> </tr> </table> <p>2016</p> </div>	T 21 N	R 21 E		S 12	1/4	—		S 13
T 21 N	R 21 E								
	S 12								
1/4	—								
	S 13								

Independent Resurvey of the Subdivisional Lines,  
T. 21 N., R. 21 E., Gila and Salt River Meridian, Arizona

CHAINS	
	<p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p>
	<p>Set a steel fence post N. of cor.</p>
80.12	<p>Point for the cor. of secs. 11, 12, 13, and 14.</p>
	<p>Land, gently rolling and slightly broken. Soil, sandy loam and gravel. No timber; native grasses, yucca, rabbit brush, and Mormon tea.</p> <hr/>
	<p>N. 0°01' W., bet. secs. 11 and 12.</p>
	<p>Over rolling land.</p>
18.25	<p>BIA Route 9860, a bladed dirt road, 25 ft. wide, bears S. 85° E. and N. 85° W.</p>
40.00	<p>Point for the 1/4 sec. cor. of secs. 11 and 12.</p>
	<p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with brass cap mkd.</p>
	<p style="text-align: center;">T 21 N R 21 E 1/4 S 11   S 12</p>
	<p style="text-align: center;">2016</p>
	<p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p>
	<p>Set a steel fence post W. of cor.</p>
80.00	<p>Point for the cor. of secs. 1, 2, 11, and 12.</p>
	<p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 25 ins. in the ground, with brass cap mkd.</p>
	<p style="text-align: center;">T 21 N R 21 E S 2   S 1 S 11   S 12</p>
	<p style="text-align: center;">2016</p>
	<p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p>
	<p>Set a steel fence post W. of cor.</p>
	<p>Land, slightly broken badlands. Soil, sandy loam and gravel. No timber; native grasses, salt brush, and yucca.</p> <hr/>

Independent Resurvey of the Subdivisional Lines,  
T. 21 N., R. 21 E., Gila and Salt River Meridian, Arizona

CHAINS	
	<p>From the cor. of secs. 1, 6, 7, and 12, on the E. bdy. of the Tp., hereinbefore described.</p> <p>N. 89°58' W., bet. secs. 1 and 12.</p> <p>Over rolling land.</p>
10.40	Power line, 2 strand, bears N. 10° E. and S. 10° W.
21.65	Power line, 4 strand, bears N. 5° E. and S. 5° W.
40.08	<p>Point for the 1/4 sec. cor. of secs. 1 and 12.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 25 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center;"> <p>T 21 N R 21 E</p> <p>S 1</p> <p>1/4 ———</p> <p>S 12</p> <p>2016</p> </div> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p> <p>Set a steel fence post N. of cor.</p>
80.16	<p>Point for the cor. of secs. 1, 2, 11, and 12.</p> <p>Land, rolling.</p> <p>Soil, sandy loam and gravel.</p> <p>No timber; native grasses, rabbit brush, and yucca.</p> <hr/> <p>N. 0°02' E., bet. secs. 1 and 2.</p> <p>Over rolling land.</p>
33.95	Salt Seeps Wash, 65 ft. wide, 5 ft. deep, drains S. 50° W.
40.00	<p>Point for the 1/4 sec. cor. of secs. 1 and 2.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 25 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center;"> <p>T 21 N R 21 E</p> <p>1/4</p> <p>S 2   S 1</p> <p>2016</p> </div> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p>

**Independent Resurvey of the Subdivisional Lines,  
T. 21 N., R. 21 E., Gila and Salt River Meridian, Arizona**

CHAINS	
	<p>Set a steel fence post W. of cor.</p> <p>Cor. is located 90 lks. W. of right bank of Salt Seeps Wash, 5 ft. high, bears N. and S.</p>
79.20	<p>The cor. of secs. 1, 2, 35, and 36, on the N. bdy. of the Tp., monumented with a stainless steel post, 2 1/2 ins. diam., firmly set, projecting 8 ins. above ground, encircled with a collar of stone, with brass cap mkd. T22N R21E S35 S36 S2 S1 T21N 2009. Add the marks 2016 to the brass cap, and rebuild the collar of stone, 3 ft. base, to top.</p> <p>Land, rolling and slightly broken. Soil, sandy loam. No timber; native grasses, and salt brush.</p> <hr/> <p>From the stan. cor. of secs. 34 and 35, on the S. bdy. of the Tp., hereinbefore described.</p> <p>N. 0°01' W., bet. secs. 34 and 35.</p> <p>Over gently rolling land.</p>
16.45	<p>BIA Route 9861, a bladed dirt road, 25 ft. wide, bears S. 75° E. and N. 75° W.</p>
40.00	<p>Point for the 1/4 sec. cor. of secs. 34 and 35.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T 21 N   R 21 E           1/4 S 34   S 35  2016</p> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p> <p>Set a steel fence post W. of cor.</p>
80.00	<p>Point for the cor. of secs. 26, 27, 34, and 35.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T 21 N   R 21 E S 27   S 26 ----- S 34   S 35  2016</p>

Independent Resurvey of the Subdivisional Lines,  
T. 21 N., R. 21 E., Gila and Salt River Meridian, Arizona

CHAINS	
	<p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p> <p>Set a steel fence post W. of cor.</p> <p>Land, gently rolling. Soil, sandy loam. No timber; native grasses, yucca, rabbit brush, and Mormon tea.</p> <hr/> <p>From the cor. of secs. 25, 26, 35, and 36.</p> <p>N. 89°58' W., bet. secs. 26 and 35.</p> <p>Over gently rolling land.</p>
40.00	<p>Point for the 1/4 sec. cor. of secs. 26 and 35.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center;"> <p>T 21 N R 21 E</p> <p>S 26</p> <p>1/4 ———</p> <p>S 35</p> <p>2016</p> </div>
80.00	<p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p> <p>Set a steel fence post W. of cor.</p> <p>The cor. of secs. 26, 27, 34, and 35.</p> <p>Land, gently rolling and nearly level. Soil, sandy loam. No timber; native grasses, yucca, rabbit brush, and Mormon tea.</p> <hr/> <p>N. 0°01' W., bet. secs. 26 and 27.</p> <p>Over gently rolling land.</p>
8.40	<p>Power line, 2 strand, bears N. 60° E. and S. 60° W.</p>
40.00	<p>Point for the 1/4 sec. cor. of secs. 26 and 27.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p>

Independent Resurvey of the Subdivisional Lines,  
T. 21 N., R. 21 E., Gila and Salt River Meridian, Arizona

CHAINS	
	T 21 N R 21 E 1/4 S 27   S 26  2016
	Deposit a magnet, in a white plastic case, at the base of the stainless steel post.  Set a steel fence post W. of cor.
65.10	From this point, a fiberglass livestock water tank, 17 ft. diam., 8 ft. high, bears W., 2.10 chs. dist.
73.40	Power line, 2 strand, bears S. 70° E. and N. 70° W.
80.00	Point for the cor. of secs. 22, 23, 26, and 27.  Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.
	T 21 N R 21 E S 22   S 23 S 27   S 26  2016
	Deposit a magnet, in a white plastic case, at the base of the stainless steel post.  Set a steel fence post W. of cor.  Land, gently rolling. Soil, sandy loam. No timber; native grasses, cholla, and rabbit brush.
	<hr/> From the cor. of secs. 23, 24, 25, and 26.  N. 89°58' W., bet. secs. 23 and 26.  Over gently rolling land.
29.50	Intersect fence to enclosed field, barbed wire, 4 strand, bears N. 50° E. and S. 50° W.
40.00	Point for the 1/4 sec. cor. of secs. 23 and 26.  Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.



**Independent Resurvey of the Subdivisional Lines,  
T. 21 N., R. 21 E., Gila and Salt River Meridian, Arizona**

CHAINS	
	T 21 N R 21 E S 23 1/4 ——— S 26  2016
	Deposit a magnet, in a white plastic case, at the base of the stainless steel post.  Set a steel fence post N. of cor.  From this cor. point, a fiberglass livestock water tank, 16 ft. diam., 8 ft. high, bears N. 7° E., 2.95 chs. dist.
42.20	Two track road, bears N. 45° E. and S. 55° W.
80.00	The cor. of secs. 22, 23, 26, and 27.  Land, gently rolling. Soil, sandy loam. No timber; native grasses, yucca, cholla, rabbit brush, and Mormon tea.
	—————
	N. 0°01' W., bet. secs. 22 and 23.  Over gently rolling land.
40.00	Point for the 1/4 sec. cor. of secs. 22 and 23.  Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.
	T 21 N R 21 E 1/4 S 22   S 23  2016
	Deposit a magnet, in a white plastic case, at the base of the stainless steel post.  Set a steel fence post W. of cor.
80.00	Point for the cor. of secs. 14, 15, 22, and 23.  Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.

**Independent Resurvey of the Subdivisional Lines,  
T. 21 N., R. 21 E., Gila and Salt River Meridian, Arizona**

CHAINS									
	<table style="margin: auto; border-collapse: collapse;"> <tr> <td style="padding: 0 10px;">T 21 N</td> <td style="border-left: 1px solid black; padding: 0 10px;">R 21 E</td> </tr> <tr> <td style="padding: 0 10px;">S 15</td> <td style="border-left: 1px solid black; padding: 0 10px;">S 14</td> </tr> <tr> <td style="padding: 0 10px;">S 22</td> <td style="border-left: 1px solid black; padding: 0 10px;">S 23</td> </tr> </table>	T 21 N	R 21 E	S 15	S 14	S 22	S 23		
T 21 N	R 21 E								
S 15	S 14								
S 22	S 23								
	2016								
	<p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p> <p>Set a steel fence post W. of cor.</p> <p>Land, gently rolling. Soil, sandy loam. No timber; native grasses, yucca, cactus, and Mormon tea.</p> <hr/> <p>From the cor. of secs. 13, 14, 23, and 24.</p> <p>N. 89°58' W., bet. secs. 14 and 23.</p> <p>Over gently rolling land.</p>								
40.00	<p>Point for the 1/4 sec. cor. of secs. 14 and 23.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p>								
	<table style="margin: auto; border-collapse: collapse;"> <tr> <td style="padding: 0 10px;">T 21 N</td> <td style="border-left: 1px solid black; padding: 0 10px;">R 21 E</td> </tr> <tr> <td style="padding: 0 10px;"></td> <td style="border-left: 1px solid black; padding: 0 10px;">S 14</td> </tr> <tr> <td style="padding: 0 10px;">1/4</td> <td style="border-left: 1px solid black; padding: 0 10px;">—</td> </tr> <tr> <td style="padding: 0 10px;"></td> <td style="border-left: 1px solid black; padding: 0 10px;">S 23</td> </tr> </table>	T 21 N	R 21 E		S 14	1/4	—		S 23
T 21 N	R 21 E								
	S 14								
1/4	—								
	S 23								
	2016								
	<p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p> <p>Set a steel fence post N. of cor.</p>								
80.00	<p>The cor. of secs. 14, 15, 22, and 23.</p> <p>Land, gently rolling. Soil, sandy loam. No timber; native grasses, cactus, rabbit brush, and Mormon tea.</p> <hr/> <p>N. 0°01' W., bet. secs. 14 and 15.</p> <p>Over gently rolling land.</p>								
40.00	<p>Point for the 1/4 sec. cor. of secs. 14 and 15.</p>								

**Independent Resurvey of the Subdivisional Lines,  
T. 21 N., R. 21 E., Gila and Salt River Meridian, Arizona**

CHAINS	
80.00	<p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T 21 N R 21 E 1/4 S 15   S 14</p> <p style="text-align: center;">2016</p> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p> <p>Set a steel fence post W. of cor.</p> <p>Point for the cor. of secs. 10, 11, 14, and 15.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 25 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T 21 N R 21 E S 10   S 11 ----- S 15   S 14</p> <p style="text-align: center;">2016</p> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p> <p>Set a steel fence post W. of cor.</p> <p>Land, gently rolling. Soil, sandy loam and gravel. No timber; native grasses, and salt brush.</p> <hr/> <p>From the cor. of secs. 11, 12, 13, and 14.</p> <p>N. 89°58' W., bet. secs. 11 and 14.</p> <p>Over gently rolling land.</p>
40.00	<p>Point for the 1/4 sec. cor. of secs. 11 and 14.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 25 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T 21 N R 21 E S 11 1/4 ——— S 14</p> <p style="text-align: center;">2016</p>

**Independent Resurvey of the Subdivisional Lines,  
T. 21 N., R. 21 E., Gila and Salt River Meridian, Arizona**

CHAINS	
	<p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p> <p>Set a steel fence post N. of cor.</p>
48.15	Intersect remnants of wooden post hubs, once served as a fence line to grazing ranch, no longer exists, bears S. 5° E. and N. 5° W.
80.00	<p>The cor. of secs. 10, 11, 14, and 15.</p> <p>Land, gently rolling and nearly level. Soil, sandy loam. No timber; native grasses, cholla, rabbit, and salt brush.</p> <hr/> <p>N. 0°01' W., bet. secs. 10 and 11.</p> <p>Over gently rolling land.</p>
20.55	Salt Seeps Wash, 110 ft. wide, 2 ft. deep, drains S. 35° W.
21.90	From this point, the center of windmill, 7 x 7 ft. base, 35 ft. high, with a steel water tank, 8 ft. diam., 12 ft. high, alongside, bears W., 3.05 chs. dist.
40.00	<p>Point for the 1/4 sec. cor. of secs. 10 and 11.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center;"> <p>T 21 N R 21 E</p> <p>1/4</p> <p>S 10   S 11</p> <p>2016</p> </div> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p> <p>Set a steel fence post W. of cor.</p> <p>Cor. is located 70 lks. N. of BIA Route 9860, a bladed dirt road, 25 ft. wide, bears S. 75° E. and N. 75° W.</p>
80.00	<p>Point for the cor. of secs. 2, 3, 10, and 11.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 25 ins. in the ground, with brass cap mkd.</p>

Independent Resurvey of the Subdivisional Lines,  
T. 21 N., R. 21 E., Gila and Salt River Meridian, Arizona

CHAINS									
	<table border="1" style="margin: auto;"> <tr> <td>T 21 N</td> <td>R 21 E</td> </tr> <tr> <td>S 3</td> <td>S 2</td> </tr> <tr> <td>S 10</td> <td>S 11</td> </tr> </table> <p>2016</p> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p> <p>Set a steel fence post W. of cor.</p> <p>Land, gently rolling and slightly broken. Soil, sandy loam and gravel. No timber; native grasses, rabbit brush, and salt brush.</p> <hr/> <p>From the cor. of secs. 1, 2, 11, and 12.</p> <p>N. 89°58' W., bet. secs. 2 and 11.</p> <p>Over rolling badlands.</p>	T 21 N	R 21 E	S 3	S 2	S 10	S 11		
T 21 N	R 21 E								
S 3	S 2								
S 10	S 11								
24.55	Salt Seeps Wash, 160 ft. wide, 4 ft. deep, drains S. 60° W.								
40.00	Point for the 1/4 sec. cor. of secs. 2 and 11.								
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with brass cap mkd.								
	<table border="1" style="margin: auto;"> <tr> <td>T 21 N</td> <td>R 21 E</td> </tr> <tr> <td>S 2</td> <td></td> </tr> <tr> <td>1/4</td> <td>—</td> </tr> <tr> <td>S 11</td> <td></td> </tr> </table> <p>2016</p> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p> <p>Set a steel fence post N. of cor.</p> <p>Cor. is located 2.90 chs. W. of a wash, 20 ft. wide, 4 ft. deep, drains S. 10° W.</p>	T 21 N	R 21 E	S 2		1/4	—	S 11	
T 21 N	R 21 E								
S 2									
1/4	—								
S 11									
80.00	The cor. of secs. 2, 3, 10, and 11.								
	Land, gently rolling and slightly broken. Soil, sandy loam and gravel. No timber; native grasses and salt brush.								

Independent Resurvey of the Subdivisional Lines,  
T. 21 N., R. 21 E., Gila and Salt River Meridian, Arizona

CHAINS	
	<p>N. 0°04' W., bet. secs. 2 and 3.</p> <p>Over rolling badlands.</p>
40.00	<p>Point for the 1/4 sec. cor. of secs. 2 and 3.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 25 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T 21 N R 21 E 1/4 S 3   S 2</p> <p style="text-align: center;">2016</p> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p> <p>Set a steel fence post W. of cor.</p> <p>Cor. is located on top of and on E. edge of finger ridge, 15 ft. wide, 10 ft. high, bears N. and S. 20° W., and 1.20 chs. S. of a wash, 15 ft. wide, 1 ft. deep, drains S. 70° W.</p>
78.64	<p>The cor. of secs. 2, 3, 34, and 35, on the N. bdy. of the Tp., monumented with a stainless steel post, 2 1/2 ins. diam., firmly set, projecting 4 ins. above ground, with a steel fence post, N. of cor., with brass cap mkd. T22N R21E S34 S35 S3 S2 T21N 2009. Add the marks 2016 to the brass cap.</p> <p>Land, rolling and slightly broken badlands. Soil, sandy loam and gravel. No timber; native grasses, salt brush, rabbit brush, yucca, and Mormon tea.</p> <hr/> <p>From the stan. cor. of secs. 33 and 34, on the S. bdy. of the Tp., hereinbefore described.</p> <p>N. 0°02' W., bet. secs. 33 and 34.</p> <p>Over gently rolling land.</p>
31.15	<p>Intersect fence to enclosed field, barbed wire, 5 strand, bears N. 35° E. and S. 35° W.</p>
40.00	<p>Point for the 1/4 sec. cor. of secs. 33 and 34.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 27 ins. in the ground, with brass cap mkd.</p>

Independent Resurvey of the Subdivisional Lines,  
T. 21 N., R. 21 E., Gila and Salt River Meridian, Arizona

CHAINS	
	T 21 N R 21 E 1/4 S 33   S 34  2016
	Deposit a magnet, in a white plastic case, at the base of the stainless steel post.  Set a steel fence post W. of cor.  Cor. is located 12 lks. N. of fence to enclosed field, barbed wire, 5 strand, bears S. 60° E. and N. 60° W.
51.30	Power line, 2 strand, bears S. 85° E. and N. 85° W.
72.30	BIA Route 9861, a bladed dirt road, 25 ft. wide, bears S. 70° E. and N. 70° W.
80.00	Point for the cor. of secs. 27, 28, 33, and 34.  Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 25 ins. in the ground, with brass cap mkd.
	T 21 N R 21 E S 28   S 27 S 33   S 34  2016
	Deposit a magnet, in a white plastic case, at the base of the stainless steel post.  Set a steel fence post W. of cor.  Land, gently rolling. Soil, sandy loam. No timber; native grasses, yucca, rabbit brush, and Mormon tea.
	<hr/> From the cor. of secs. 26, 27, 34, and 35.  N. 89°58' W., bet. secs. 27 and 34.  Over gently rolling land.
13.50	Power line, 2 strand, bears N. 60° E. and S. 60° W.
39.975	Point for the 1/4 sec. cor. of secs. 27 and 34.  Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.

Independent Resurvey of the Subdivisional Lines,  
T. 21 N., R. 21 E., Gila and Salt River Meridian, Arizona

CHAINS	
	T 21 N R 21 E S 27 1/4 ——— S 34  2016
	Deposit a magnet, in a white plastic case, at the base of the stainless steel post.  Set a steel fence post N. of cor.
79.95	The cor. of secs. 27, 28, 33, and 34.  Land, gently rolling. Soil, sandy loam. No timber; native grasses, yucca, cactus, cholla, rabbit brush, and Mormon tea.
	<hr/> N. 0°02' W., bet. secs. 27 and 28.  Over gently rolling land.
40.00	Point for the 1/4 sec. cor. of secs. 27 and 28.  Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with brass cap mkd.
	T 21 N R 21 E 1/4 S 28   S 27  2016
	Deposit a magnet, in a white plastic case, at the base of the stainless steel post.  Set a steel fence post W. of cor.
80.00	Point for the cor. of secs. 21, 22, 27, and 28.  Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with brass cap mkd.
	T 21 N R 21 E S 21   S 22 S 28   S 27  2016
	Deposit a magnet, in a white plastic case, at the base of the stainless steel post.



Independent Resurvey of the Subdivisional Lines,  
T. 21 N., R. 21 E., Gila and Salt River Meridian, Arizona

CHAINS	
	<p>Set a steel fence post W. of cor.</p> <p>Land, gently rolling. Soil, sandy loam. No timber; native grasses, cactus, cholla, rabbit brush, and Mormon tea.</p> <hr/> <p>From the cor. of secs. 22, 23, 26, and 27.</p> <p>N. 89°58' W., bet. secs. 22 and 27.</p> <p>Over gently rolling land.</p>
39.975	<p>Point for the 1/4 sec. cor. of secs. 22 and 27.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center;"> <p>T 21 N R 21 E</p> <p>S 22</p> <p>1/4 <u>        </u></p> <p>S 27</p> <p>2016</p> </div> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p> <p>Set a steel fence post N. of cor.</p>
79.95	<p>The cor. of secs. 21, 22, 27, and 28.</p> <p>Land, gently rolling. Soil, sandy loam. No timber; native grasses, cactus, cholla, yucca, rabbit brush, and Mormon tea.</p> <hr/> <p>N. 0°02' W., bet. secs. 21 and 22.</p> <p>Over gently rolling land.</p>
12.70	<p>Intersect fence to enclosed 1,075 +/- acre field, barbed wire, 5 strand, bears N. 70° E. and S. 75° W.</p>
40.00	<p>Point for the 1/4 sec. cor. of secs. 21 and 22.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with brass cap mkd.</p>

Independent Resurvey of the Subdivisional Lines,  
T. 21 N., R. 21 E., Gila and Salt River Meridian, Arizona

CHAINS	
	T 21 N R 21 E 1/4 S 21   S 22  2016
	Deposit a magnet, in a white plastic case, at the base of the stainless steel post.
	Set a steel fence post W. of cor.
80.00	Point for the cor. of secs. 15, 16, 21, and 22.
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 27 ins. in the ground, with brass cap mkd.
	T 21 N R 21 E S 16   S 15 S 21   S 22  2016
	Deposit a magnet, in a white plastic case, at the base of the stainless steel post.
	Set a steel fence post W. of cor.
	From this cor. point, an enclosed concrete well, 9 x 9 x 11 ft. deep, with a square opening on top, 16 x 16 ins., known as Spencer Well, bears N. 11°05' E., 18.04 chs. dist.
	From this same cor. point, a fiberglass livestock water tank, 10 ft. diam., 10 ft. high, bears N. 14°17' E., 15.98 chs. dist.
	Land, gently rolling. Soil, sandy loam. No timber; native grasses, yucca, rabbit brush, and Mormon tea.
	<hr/> From the cor. of secs. 14, 15, 22, and 23.
	N. 89°58' W., bet. secs. 15 and 22.
	Over gently rolling land.
39.975	Point for the 1/4 sec. cor. of secs. 15 and 22.
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with brass cap mkd.

Independent Resurvey of the Subdivisional Lines,  
T. 21 N., R. 21 E., Gila and Salt River Meridian, Arizona

CHAINS	
	T 21 N R 21 E S 15 1/4 ——— S 22  2016
	Deposit a magnet, in a white plastic case, at the base of the stainless steel post.  Set a steel fence post N. of cor.
67.00	Intersect fence to enclosed 1,075 +/- acre field, barbed wire, 5 strand, bears S. 40° E. and N. 40° W.
79.95	The cor. of secs. 15, 16, 21, and 22.  Land, gently rolling. Soil, sandy loam. No timber; native grasses, yucca, and Mormon tea.
	N. 0°02' W., bet. secs. 15 and 16.  Over gently rolling land.
16.15	Intersect fence to enclosed 1,075 +/- acre field, barbed wire, 5 strand, bears S. 40° E. and N. 40° W.
20.10	Salt Seeps Wash, 20 ft. wide, 4 ft. deep, drains S. 75° W.
40.00	Point for the 1/4 sec. cor. of secs. 15 and 16.  Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with brass cap mkd.
	T 21 N R 21 E 1/4 S 16   S 15  2016
	Deposit a magnet, in a white plastic case, at the base of the stainless steel post.  Set a steel fence post W. of cor.
80.00	Point for the cor. of secs. 9, 10, 15, and 16.  Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with brass cap mkd.

Independent Resurvey of the Subdivisional Lines,  
T. 21 N., R. 21 E., Gila and Salt River Meridian, Arizona

CHAINS	
	T 21 N R 21 E S 9   S 10 S 16   S 15  2016
	Deposit a magnet, in a white plastic case, at the base of the stainless steel post.  Set a steel fence post W. of cor.  Land, gently rolling, to rolling in the badlands. Soil, sandy loam and clay. No timber; native grasses, and rabbit brush.
	<hr/> From the cor. of secs. 10, 11, 14, and 15.  N. 89°58' W., bet. secs. 10 and 15.  Over rolling badlands.
22.10	Salt Seeps Wash, 55 ft. wide, 3 ft. deep, drains S. 10° E.
39.975	Point for the 1/4 sec. cor. of secs. 10 and 15.  Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with brass cap mkd.
	T 21 N R 21 E S 10 1/4 ——— S 15  2016
	Deposit a magnet, in a white plastic case, at the base of the stainless steel post.  Set a steel fence post N. of cor.
79.95	The cor. of secs. 9, 10, 15, and 16.  Land, gently rolling, to rolling in the badlands. Soil, clay. No timber; native grasses, cactus, and salt brush.
	<hr/> N. 0°02' W., bet. secs. 9 and 10.  Over rolling badlands.
40.00	Point for the 1/4 sec. cor. of secs. 9 and 10.

**Independent Resurvey of the Subdivisional Lines,  
T. 21 N., R. 21 E., Gila and Salt River Meridian, Arizona**

CHAINS	
	<p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T 21 N R 21 E 1/4 S 9   S 10</p> <p style="text-align: center;">2016</p> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p> <p>Set a steel fence post W. of cor.</p>
53.20	BIA Route 9860, a bladed dirt road, 25 ft. wide, bears S. 40° E. and N. 30° W.
80.00	<p>Point for the cor. of secs. 3, 4, 9, and 10.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 22 ins. in solid sandstone bedrock, with brass cap mkd.</p> <p style="text-align: center;">T 21 N R 21 E S 4   S 3 S 9   S 10</p> <p style="text-align: center;">2016</p> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p> <p>Set a steel fence post W. of cor.</p> <p>Cor. falls on finger ridge of badlands, 40 ft. high, bears N. 40° E. and S. 40° W.</p> <p>Land, rolling badlands. Soil, clay. No timber; native grasses, yucca, salt brush, and rabbit brush.</p> <hr/> <p>From the cor. of secs. 2, 3, 10, and 11.</p> <p>N. 89°58' W., bet. secs. 3 and 10.</p> <p>Over rolling badlands.</p>
39.975	<p>Point for the 1/4 sec. cor. of secs. 3 and 10.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 15 ins. in the ground, with brass cap mkd.</p>

Independent Resurvey of the Subdivisional Lines,  
T. 21 N., R. 21 E., Gila and Salt River Meridian, Arizona

CHAINS	
	<p style="text-align: center;">T 21 N R 21 E S 3 1/4 ——— S 10</p> <p style="text-align: center;">2016</p>
	<p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p> <p>Set a steel fence post N. of cor.</p> <p>Cor. is located 2.50 chs. E. of a wash, 30 ft. wide, 3 ft. deep, drains S. 20° W.</p>
79.95	<p>The cor. of secs. 3, 4, 9, and 10.</p> <p>Land, rolling badlands. Soil, clay. No timber; native grasses, salt brush, and rabbit brush.</p> <hr/>
	<p>N. 0°12' W., bet. secs. 3 and 4.</p> <p>Over rolling badlands.</p>
40.00	<p>Point for the 1/4 sec. cor. of secs. 3 and 4.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, underpinned with a steel fence post, 60 ins. long, with brass cap mkd.</p>
	<p style="text-align: center;">T 21 N R 21 E 1/4 S 4   S 3</p> <p style="text-align: center;">2016</p>
	<p>from which</p> <p style="text-align: center;">A stainless steel post, 28 ins. long, 2 1/2 ins. diam., set 26 ins. in the ground for a reference monument, bears S. 45°00' E., 190.0 ft. dist. with brass cap mkd. RM T21N R21E 190.0 FT TO COR 1/4 S3 2016 and an arrow pointing to the cor. Deposit a magnet, in a white plastic case, at the base of the stainless steel post, and set a steel fence post SE of cor.</p>

**Independent Resurvey of the Subdivisional Lines,  
T. 21 N., R. 21 E., Gila and Salt River Meridian, Arizona**

CHAINS	
	<p>A stainless steel post, 28 ins. long, 2 1/2 ins. diam., set 27 ins. in the ground for a reference monument, bears N. 45°00' W., 112.0 ft. dist. with brass cap mkd. RM T21N R21E 112.0 FT TO COR 1/4 S4 2016 and an arrow pointing to the cor. Deposit a magnet, in a white plastic case, at the base of the stainless steel post, and set a steel fence post NW of cor.</p> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p> <p>Set a steel fence post W. of cor.</p> <p>Cor. is located in the floodplain of a wash, 200 ft. wide, 4 ft. deep, drains S. 20° W.</p>
78.08	<p>The cor. of secs. 3, 4, 33, and 34, on the N. bdy. of the Tp., monumented with a stainless steel post, 2 1/2 ins. diam., firmly set, projecting 12 ins. above ground, encircled with a collar of stone, with brass cap mkd. T22N R21E S33 S34 S4 S3 T21N 2009. Add the marks 2016 to the brass cap.</p> <p>Land, rolling and broken badlands. Soil, sandy loam and gravel. No timber; native grasses, salt brush, and rabbit brush.</p> <hr/> <p>From the stan. cor. of secs. 32 and 33, on the S. bdy. of the Tp., hereinbefore described.</p> <p>N. 0°02' W., bet. secs. 32 and 33.</p> <p>Over nearly level land.</p>
40.00	<p>Point for the 1/4 sec. cor. of secs. 32 and 33.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T 21 N R 21 E 1/4 S 32   S 33  2016</p> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p> <p>Set a steel fence post W. of cor.</p>
59.60	<p>Power line, 2 strand, bears S. 85° E. and N. 85° W.</p>
80.00	<p>Point for the cor. of secs. 28, 29, 32, and 33.</p>

Independent Resurvey of the Subdivisional Lines,  
T. 21 N., R. 21 E., Gila and Salt River Meridian, Arizona

CHAINS									
	<p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 27 ins. in the ground, with brass cap mkd.</p> <table style="margin-left: auto; margin-right: auto;"> <tr> <td>T 21 N</td> <td>R 21 E</td> </tr> <tr> <td>S 29</td> <td>S 28</td> </tr> <tr> <td>S 32</td> <td>S 33</td> </tr> </table> <p style="text-align: center;">2016</p> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p> <p>Set a steel fence post W. of cor.</p> <p>Cor. is located 1.80 chs. S. of BIA Route 9861, a bladed dirt road, 20 ft. wide, bears S. 85° E. and N. 85° W.</p> <p>Land, nearly level to broken badlands. Soil, sandy loam. No timber; native grasses, yucca, sage brush, rabbit brush, and Mormon tea.</p> <hr/>	T 21 N	R 21 E	S 29	S 28	S 32	S 33		
T 21 N	R 21 E								
S 29	S 28								
S 32	S 33								
	<p>From the cor. of secs. 27, 28, 33, and 34.</p> <p>N. 89°59' W., bet. secs. 28 and 33.</p> <p>Over gently rolling land.</p>								
<p>34.20</p>	<p>BIA Route 9861, a bladed dirt road, 20 ft. wide, bears S. 80° E. and N. 80° W.</p>								
<p>40.00</p>	<p>Point for the 1/4 sec. cor. of secs. 28 and 33.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with brass cap mkd.</p> <table style="margin-left: auto; margin-right: auto;"> <tr> <td>T 21 N</td> <td>R 21 E</td> </tr> <tr> <td></td> <td>S 28</td> </tr> <tr> <td>1/4</td> <td>_____</td> </tr> <tr> <td></td> <td>S 33</td> </tr> </table> <p style="text-align: center;">2016</p> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p> <p>Set a steel fence post W. of cor.</p> <p>Cor. is located 90 lks. S. of BIA Route 9861, a bladed dirt road, 20 ft. wide, bears S. 80° E. and N. 80° W.</p>	T 21 N	R 21 E		S 28	1/4	_____		S 33
T 21 N	R 21 E								
	S 28								
1/4	_____								
	S 33								



Independent Resurvey of the Subdivisional Lines,  
T. 21 N., R. 21 E., Gila and Salt River Meridian, Arizona

CHAINS	
80.00	<p>The cor. of secs. 28, 29, 32, and 33.</p> <p>Land, gently rolling. Soil, sandy loam. No timber; native grasses, cholla, and rabbit brush.</p> <hr/> <p>N. 0°02' W., bet. secs. 28 and 29.</p> <p>Over gently rolling land.</p>
40.00	<p>Point for the 1/4 sec. cor. of secs. 28 and 29.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center;"> <p>T 21 N R 21 E 1/4 S 29   S 28</p> <p>2016</p> </div> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p> <p>Set a steel fence post W. of cor.</p>
72.55	<p>Intersect fence to enclosed 1,075 +/- acre field, barbed wire, 5 strand, bears N. 80° E. and S. 80° W.</p>
80.00	<p>Point for the cor. of secs. 20, 21, 28, and 29.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center;"> <p>T 21 N R 21 E S 20   S 21 S 29   S 28</p> <p>2016</p> </div> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p> <p>Set a steel fence post W. of cor.</p> <p>Land, gently rolling. Soil, sandy loam. No timber; native grasses, cholla, rabbit brush, yucca, and Mormon tea.</p> <hr/>

**Independent Resurvey of the Subdivisional Lines,  
T. 21 N., R. 21 E., Gila and Salt River Meridian, Arizona**

CHAINS	
	<p>From the cor. of secs. 21, 22, 27, and 28.</p> <p>N. 89°59' W., bet. secs. 21 and 28.</p> <p>Over gently rolling land.</p>
40.00	<p>Point for the 1/4 sec. cor. of secs. 21 and 28.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 25 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T 21 N R 21 E S 21 1/4 ——— S 28</p> <p style="text-align: center;">2016</p> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p> <p>Set a steel fence post N. of cor.</p>
43.30	<p>Intersect fence to enclosed 1,075 +/- acre field, barbed wire, 5 strand, bears N. 75° E. and S. 80° W.</p>
80.00	<p>The cor. of secs. 20, 21, 28, and 29.</p> <p>Land, gently rolling in partial badlands. Soil, sandy loam. No timber; native grasses, yucca, rabbit brush, and Mormon tea.</p> <hr/> <p>N. 0°02' W., bet. secs. 20 and 21.</p> <p>Over gently rolling land.</p>
32.00	<p>Salt Seeps Wash, 20 ft. wide, 1 ft. deep, drains S. 30° W.</p>
40.00	<p>Point for the 1/4 sec. cor. of secs. 20 and 21.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 27 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T 21 N R 21 E 1/4 S 20   S 21</p> <p style="text-align: center;">2016</p> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p> <p>Set a steel fence post W. of cor.</p>

**Independent Resurvey of the Subdivisional Lines,  
T. 21 N., R. 21 E., Gila and Salt River Meridian, Arizona**

CHAINS									
63.75	Intersect fence to enclosed 1,075 +/- acre field, barbed wire, 5 strand, bears N. 40° E. and S. 40° W.								
80.00	<p>Point for the cor. of secs. 16, 17, 20, and 21.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 25 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center;"> <table style="margin: auto;"> <tr> <td>T 21 N</td> <td>R 21 E</td> </tr> <tr> <td>S 17</td> <td>S 16</td> </tr> <tr> <td>S 20</td> <td>S 21</td> </tr> </table> <p>2016</p> </div> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p> <p>Set a steel fence post W. of cor.</p> <p>Land, gently rolling in partial badlands. Soil, sandy loam and gravel. No timber; native grasses, yucca, rabbit brush, and salt brush.</p> <hr/> <p>From the cor. of secs. 15, 16, 21, and 22.</p> <p>N. 89°59' W., bet. secs. 16 and 21.</p> <p>Over gently rolling land.</p>	T 21 N	R 21 E	S 17	S 16	S 20	S 21		
T 21 N	R 21 E								
S 17	S 16								
S 20	S 21								
40.00	<p>Point for the 1/4 sec. cor. of secs. 16 and 21.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 25 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center;"> <table style="margin: auto;"> <tr> <td>T 21 N</td> <td>R 21 E</td> </tr> <tr> <td></td> <td>S 16</td> </tr> <tr> <td>1/4</td> <td>————</td> </tr> <tr> <td></td> <td>S 21</td> </tr> </table> <p>2016</p> </div> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p> <p>Set a steel fence post N. of cor.</p> <p>Cor. is located 2.60 chs. E. of Salt Seeps Wash, 20 ft. wide, 3 ft. deep, drains S. 5° E.</p>	T 21 N	R 21 E		S 16	1/4	————		S 21
T 21 N	R 21 E								
	S 16								
1/4	————								
	S 21								
67.45	Intersect fence to enclosed 1,075 +/- acre field, barbed wire, 5 strand, bears N. 40° E. and S. 40° W.								

Independent Resurvey of the Subdivisional Lines,  
T. 21 N., R. 21 E., Gila and Salt River Meridian, Arizona

CHAINS	
80.00	<p>The cor. of secs. 16, 17, 20, and 21.</p> <p>Land, gently rolling to nearly level in partial badlands. Soil, sandy loam. Timber, salt cedar along the wash. Undergrowth, native grasses, rabbit brush, and salt brush.</p> <hr/> <p>N. 0°02' W., bet. secs. 16 and 17.</p> <p>Entering rolling badlands.</p>
40.00	<p>Point for the 1/4 sec. cor. of secs. 16 and 17.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center;"> <p>T 21 N R 21 E 1/4 S 17   S 16</p> <p>2016</p> </div> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p> <p>Set a steel fence post W. of cor.</p>
80.00	<p>Point for the cor. of secs. 8, 9, 16, and 17.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center;"> <p>T 21 N R 21 E S 8   S 9 S 17   S 16</p> <p>2016</p> </div> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p> <p>Set a steel fence post W. of cor.</p> <p>Land, rolling badlands to nearly level land. Soil, sandy loam, clay, and gravel. No timber; native grasses and salt brush.</p> <hr/> <p>From the cor. of secs. 9, 10, 15, and 16.</p> <p>N. 89°59' W., bet. secs. 9 and 16.</p>

**Independent Resurvey of the Subdivisional Lines,  
T. 21 N., R. 21 E., Gila and Salt River Meridian, Arizona**

CHAINS	
	Gently ascending badlands.
40.00	Point for the 1/4 sec. cor. of secs. 9 and 16.  Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with brass cap mkd.  <div style="text-align: center;">           T 21 N R 21 E                      S 9                  1/4 ———                      S 16             2016         </div>
	Deposit a magnet, in a white plastic case, at the base of the stainless steel post.
	Set a steel fence post N. of cor.
80.00	The cor. of secs. 8, 9, 16, and 17.  Land, scattered badlands to nearly level land. Soil, sandy loam. No timber; native grasses and salt brush.
	-----
	N. 0°02' W., bet. secs. 8 and 9.
	Through scattered badlands, over nearly level land.
40.00	Point for the 1/4 sec. cor. of secs. 8 and 9.  Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.  <div style="text-align: center;">           T 21 N R 21 E                      1/4                  S 8   S 9             2016         </div>
	Deposit a magnet, in a white plastic case, at the base of the stainless steel post.
	Set a steel fence post W. of cor.
65.40	BIA Route 9860, a bladed dirt road, 25 ft. wide, bears S. 80° E. and N. 85° W.
80.00	Point for the cor. of secs. 4, 5, 8, and 9.  Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.

Independent Resurvey of the Subdivisional Lines,  
T. 21 N., R. 21 E., Gila and Salt River Meridian, Arizona

CHAINS	
	<p style="text-align: center;">T 21 N R 21 E S 5   S 4 S 8   S 9</p>
	<p style="text-align: center;">2016</p>
	<p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p>
	<p>Set a steel fence post W. of cor.</p>
	<p>Land, scattered badlands and gently rolling land. Soil, sandy loam and clay. No timber; native grasses and salt brush.</p>
	<hr/>
	<p>From the cor. of secs. 3, 4, 9, and 10.</p>
	<p>N. 89°59' W., bet. secs. 4 and 9.</p>
	<p>Over rolling badlands.</p>
<p>40.00</p>	<p>Point for the 1/4 sec. cor. of secs. 4 and 9.</p>
	<p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p>
	<p style="text-align: center;">T 21 N R 21 E S 4 1/4 ——— S 9</p>
	<p style="text-align: center;">2016</p>
	<p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p>
	<p>Set a steel fence post N. of cor.</p>
	<p>Cor. is located 2.30 chs. W. of Salt Seeps Wash, 30 ft. wide, 3 ft. deep, drains S. 20° W., and is 1.70 chs. N. of the same meandering wash, 30 ft. wide, 3 ft. deep, drains N. 80° W.</p>
<p>80.00</p>	<p>The cor. of secs. 4, 5, 8, and 9.</p>
	<p>Land, scattered badlands and gently rolling land. Soil, sandy loam. No timber; native grasses, rabbit brush, and salt brush.</p>
	<hr/>
	<p>N. 0°18' W., bet. secs. 4 and 5.</p>
	<p>Over rolling badlands.</p>

**Independent Resurvey of the Subdivisional Lines,  
T. 21 N., R. 21 E., Gila and Salt River Meridian, Arizona**

CHAINS	
40.00	<p>Point for the 1/4 sec. cor. of secs. 4 and 5.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T 21 N R 21 E 1/4 S 5   S 4</p> <p style="text-align: center;">2016</p> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p> <p>Set a steel fence post W. of cor.</p>
77.55	<p>The true point of the cor. of secs. 4, 5, 32, and 33, on the N. bdy. of the Tp., from this true point, a witness cor. of secs. 4, 5, 32, and 33, bears S. 45°00' E., 1 ch. dist., monumented with a stainless steel post, 2 1/2 ins. diam., firmly set, projecting 2 ins. above ground, encircled with an embedded collar of stone, with brass cap mkd. WC S32 S33 S5 S4 T21N 2009. Add the marks T22N R21E 2016 to the brass cap.</p> <p>Land, rolling badlands. Soil, sandy loam and clay. No timber; native grasses, rabbit brush, and salt brush.</p> <hr/> <p>From the stan. cor. of secs. 31 and 32, on the S. bdy. of the Tp., hereinbefore described.</p> <p>N. 0°03' W., bet. secs. 31 and 32.</p> <p>Over gently rolling land.</p>
40.00	<p>Point for the 1/4 sec. cor. of secs. 31 and 32.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T 21 N R 21 E 1/4 S 31   S 32</p> <p style="text-align: center;">2016</p> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p> <p>Set a steel fence post W. of cor.</p>
71.10	<p>BIA Route 9861, a bladed dirt road, 20 ft. wide, bears E. and W.</p>

**Independent Resurvey of the Subdivisional Lines,  
T. 21 N., R. 21 E., Gila and Salt River Meridian, Arizona**

CHAINS									
80.00	<p>Point for the cor. of secs. 29, 30, 31, and 32.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <table style="margin-left: auto; margin-right: auto; border-collapse: collapse;"> <tr> <td style="padding: 0 10px;">T 21 N</td> <td style="border-left: 1px solid black; padding: 0 10px;">R 21 E</td> </tr> <tr> <td style="padding: 0 10px; border-bottom: 1px solid black;">S 30</td> <td style="border-left: 1px solid black; padding: 0 10px; border-bottom: 1px solid black;">S 29</td> </tr> <tr> <td style="padding: 0 10px;">S 31</td> <td style="border-left: 1px solid black; padding: 0 10px;">S 32</td> </tr> </table> <p style="text-align: center;">2016</p> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p> <p>Set a steel fence post W. of cor.</p> <p>Land, gently rolling. Soil, clay. No timber; native grasses.</p> <hr/> <p>From the cor. of secs. 28, 29, 32, and 33.</p> <p>West, bet. secs. 29 and 32.</p> <p>Over gently rolling land.</p>	T 21 N	R 21 E	S 30	S 29	S 31	S 32		
T 21 N	R 21 E								
S 30	S 29								
S 31	S 32								
10.90	<p>BIA Route 9861, a bladed dirt road, 20 ft. wide, bears N. 75° E. and S. 75° W.</p>								
39.98	<p>Point for the 1/4 sec. cor. of secs. 29 and 32.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with brass cap mkd.</p> <table style="margin-left: auto; margin-right: auto; border-collapse: collapse;"> <tr> <td style="padding: 0 10px;">T 21 N</td> <td style="border-left: 1px solid black; padding: 0 10px;">R 21 E</td> </tr> <tr> <td style="padding: 0 10px;"></td> <td style="border-left: 1px solid black; padding: 0 10px;">S 29</td> </tr> <tr> <td style="padding: 0 10px;">1/4</td> <td style="border-left: 1px solid black; padding: 0 10px;">———</td> </tr> <tr> <td style="padding: 0 10px;"></td> <td style="border-left: 1px solid black; padding: 0 10px;">S 32</td> </tr> </table> <p style="text-align: center;">2016</p> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p> <p>Set a steel fence post N. of cor.</p>	T 21 N	R 21 E		S 29	1/4	———		S 32
T 21 N	R 21 E								
	S 29								
1/4	———								
	S 32								
79.96	<p>The cor. of secs. 29, 30, 31, and 32.</p> <p>Land, gently rolling sand hills. Soil, sandy loam. No timber; native grasses, rabbit brush, yucca, and Mormon tea.</p> <hr/>								



**Independent Resurvey of the Subdivisional Lines,  
T. 21 N., R. 21 E., Gila and Salt River Meridian, Arizona**

CHAINS	
	N. 89°58' W., bet. secs. 30 and 31.  Over gently rolling land.
40.00	Point for the 1/4 sec. cor. of secs. 30 and 31.  Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 25 ins. in the ground, with brass cap mkd.  <div style="text-align: center;">           T 21 N R 21 E                      S 30            1/4 ———                      S 31             2016         </div>
	Deposit a magnet, in a white plastic case, at the base of the stainless steel post.  Set a steel fence post N. of cor.  Cor. is located 70 lks. N. of a wash, 8 ft. wide, 4 ft. deep, drains N. 65° W. into Salt Seeps Wash, and is 1.70 chs. N. of Salt Seeps Wash, 40 ft. wide, with left cut bank at 6 ft. high, and right bank at 1 ft. high, drains S. 10° W.
47.45	Salt Seeps Wash, 40 ft. wide, 2 ft. deep, drains S. 85° E.
79.68	The cor. of secs. 25, 30, 31, and 36, on the W. bdy. of the Tp., hereinbefore described.  Land, gently rolling. Soil, sandy loam. Timber, salt cedar along the wash. Undergrowth, native grasses and yucca.
	From the cor. of secs. 29, 30, 31, and 32.  N. 0°03' W., bet. secs. 29 and 30.  Over rolling land.
40.00	Point for the 1/4 sec. cor. of secs. 29 and 30.  Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 25 ins. in the ground, with brass cap mkd.  <div style="text-align: center;">           T 21 N R 21 E                      1/4            S 30   S 29             2016         </div>

**Independent Resurvey of the Subdivisional Lines,  
T. 21 N., R. 21 E., Gila and Salt River Meridian, Arizona**

CHAINS							
	<p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p> <p>Set a steel fence post W. of cor.</p>						
47.90	Left bank of the Salt Seeps Wash, 4 ft. high, bears S. 75° W. and N. 75° E.						
49.20	Center of the main channel, within Salt Seeps Wash, 158 ft. wide, drains S. 70° W.						
50.30	Right bank of the Salt Seeps Wash, 3 ft. high, bears S. 75° W. and N. 75° E.						
80.00	<p>Point for the cor. of secs. 19, 20, 29, and 30.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center;"> <table border="1"> <tr> <td>T 21 N</td> <td>R 21 E</td> </tr> <tr> <td>S 19</td> <td>S 20</td> </tr> <tr> <td>S 30</td> <td>S 29</td> </tr> </table> <p>2016</p> </div> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p> <p>Set a steel fence post W. of cor.</p> <p>Land, rolling to gently rolling. Soil, clay. No timber; native grasses, salt brush, and yucca.</p> <hr/> <p>From the cor. of secs. 20, 21, 28, and 29.</p> <p>West, bet. secs. 20 and 29.</p> <p>Over gently rolling land.</p>	T 21 N	R 21 E	S 19	S 20	S 30	S 29
T 21 N	R 21 E						
S 19	S 20						
S 30	S 29						
15.85	Intersect fence to enclosed 1,075 +/- acre field, barbed wire, 5 strand, bears S. 20° E. and N. 20° W.						
36.70	Center of the main channel, within Salt Seeps Wash, 35 ft. wide, left cut bank, 4 ft. high, drains N. 20° W.						
39.98	<p>Point for the 1/4 sec. cor. of secs. 20 and 29.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p>						

**Independent Resurvey of the Subdivisional Lines,  
T. 21 N., R. 21 E., Gila and Salt River Meridian, Arizona**

CHAINS	
	T 21 N R 21 E S 20 1/4 ——— S 29  2016
	Deposit a magnet, in a white plastic case, at the base of the stainless steel post.  Set a steel fence post N. of cor.  Cor. is located 2.15 chs. E. of Salt Seeps Wash, 50 ft. wide, left cut bank, 6 ft. high, drains S. 5° W.
79.96	The cor. of secs. 19, 20, 29, and 30.  Land, gently rolling. Soil, sandy loam. Timber, salt cedar along the wash. Undergrowth, native grasses, salt brush, and greasewood.
	N. 89°58' W., bet. secs. 19 and 30.  Over gently rolling land.
40.00	Point for the 1/4 sec. cor. of secs. 19 and 30.  Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.
	T 21 N R 21 E S 19 1/4 ——— S 30  2016
	Deposit a magnet, in a white plastic case, at the base of the stainless steel post.  Set a steel fence post N. of cor.
79.39	The cor. of secs. 19, 24, 25, and 30, on the W. bdy. of the Tp., hereinbefore described.  Land, gently rolling. Soil, clay. No timber; native grasses and salt brush.

**Independent Resurvey of the Subdivisional Lines,  
T. 21 N., R. 21 E., Gila and Salt River Meridian, Arizona**

CHAINS	
	<p>From the cor. of secs. 19, 20, 29, and 30.</p> <p>N. 0°03' W., bet. secs. 19 and 20.</p> <p>Over gently rolling land.</p>
40.00	<p>Point for the 1/4 sec. cor. of secs. 19 and 20.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in subsurface sandstone bedrock, with brass cap mkd.</p> <div style="text-align: center;"> <p>T 21 N R 21 E</p> <p>1/4</p> <p>S 19   S 20</p> <p>2016</p> </div> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p>
80.00	<p>Point for the cor. of secs. 17, 18, 19, and 20.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in subsurface sandstone bedrock, with brass cap mkd.</p> <div style="text-align: center;"> <p>T 21 N R 21 E</p> <p>S 18   S 17</p> <hr style="width: 50%; margin: 0 auto;"/> <p>S 19   S 20</p> <p>2016</p> </div> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p> <p>Set a steel fence post NW of cor.</p> <p>Land, gently rolling in partial badlands. Soil, clay, sandy loam, and gravel. No timber; native grasses and salt brush.</p> <hr style="width: 80%; margin: 10px auto;"/> <p>From the cor. of secs. 16, 17, 20, and 21.</p> <p>West, bet. secs. 17 and 20.</p> <p>Ascending E. slope of badlands.</p>
39.98	<p>Point for the 1/4 sec. cor. of secs. 17 and 20.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 25 ins. in the ground, with brass cap mkd.</p>

**Independent Resurvey of the Subdivisional Lines,  
T. 21 N., R. 21 E., Gila and Salt River Meridian, Arizona**

CHAINS	
	T 21 N R 21 E S 17 1/4 ——— S 20  2016
	Deposit a magnet, in a white plastic case, at the base of the stainless steel post.  Set a steel fence post N. of cor.  Cor. is located on top of a bad land ridge, 20 ft. high, 15 ft. wide, bears S. 20° W. and N. 30° W., and is 1.30 chs., N. 25° E., from the highest point of badland hills, 30 ft. high, with a ridge extending N. 30° E. and S. 10° W.
79.96	The cor. of secs. 17, 18, 19, and 20.  Land, rugged badlands. Soil, clay. No timber. No undergrowth.
	N. 89°58' W., bet. secs. 18 and 19.  Through scattered badlands, over gently rolling land.
40.00	Point for the 1/4 sec. cor. of secs. 18 and 19.  Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 25 ins. in the ground, with brass cap mkd.
	T 21 N R 21 E S 18 1/4 ——— S 19  2016
	Deposit a magnet, in a white plastic case, at the base of the stainless steel post.  Set a steel fence post N. of cor.
79.10	The cor. of secs. 13, 18, 19, and 24, on the W. bdy. of the Tp., hereinbefore described.  Land, gently rolling, and nearly level, in partial badlands. Soil, sandy loam. No timber; native grasses and salt brush.

**Independent Resurvey of the Subdivisional Lines,  
T. 21 N., R. 21 E., Gila and Salt River Meridian, Arizona**

CHAINS	
	<p>From the cor. of secs. 17, 18, 19, and 20.</p> <p>N. 0°03' W., bet. secs. 17 and 18.</p> <p>Over nearly level land.</p>
40.00	<p>Point for the 1/4 sec. cor. of secs. 17 and 18.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center;"> <p>T 21 N R 21 E 1/4 S 18   S 17</p> <p>2016</p> </div> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p> <p>Set a steel fence post W. of cor.</p>
80.00	<p>Point for the cor. of secs. 7, 8, 17, and 18.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 25 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center;"> <p>T 21 N R 21 E S 7   S 8 S 18   S 17</p> <p>2016</p> </div> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p> <p>Set a steel fence post W. of cor.</p> <p>Land, gently rolling. Soil, sandy loam. No timber; native grasses and salt brush.</p> <hr/> <p>From the cor. of secs. 8, 9, 16, and 17.</p> <p>West, bet. secs. 8 and 17.</p> <p>Over nearly level land.</p>
39.98	<p>Point for the 1/4 sec. cor. of secs. 8 and 17.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with brass cap mkd.</p>

Independent Resurvey of the Subdivisional Lines,  
T. 21 N., R. 21 E., Gila and Salt River Meridian, Arizona

CHAINS	
	T 21 N R 21 E S 8 1/4 ——— S 17  2016
	Deposit a magnet, in a white plastic case, at the base of the stainless steel post.
	Set a steel fence post N. of cor.
79.96	The cor. of secs. 7, 8, 17, and 18.  Land, gently rolling. Soil, sandy loam. No timber; native grasses, yucca, rabbit brush, and salt brush.
	N. 89°58' W., bet. secs. 7 and 18.  Through scattered badlands, over nearly level land.
40.00	Point for the 1/4 sec. cor. of secs. 7 and 18.  Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 25 ins. in the ground, with brass cap mkd.
	T 21 N R 21 E S 7 1/4 ——— S 18  2016
	Deposit a magnet, in a white plastic case, at the base of the stainless steel post.
	Set a steel fence post N. of cor.
78.81	The cor. of secs. 7, 12, 13, and 18, on the W. bdy. of the Tp., hereinbefore described.  Land, nearly level, in partial badlands. Soil, sandy loam. No timber; native grasses and salt brush.
	From the cor. of secs. 7, 8, 17, and 18.  N. 0°03' W., bet. secs. 7 and 8.  Over nearly level land.

Independent Resurvey of the Subdivisional Lines,  
T. 21 N., R. 21 E., Gila and Salt River Meridian, Arizona

CHAINS							
40.00	<p>Point for the 1/4 sec. cor. of secs. 7 and 8.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center;"> <table style="margin: auto;"> <tr><td>T 21 N</td><td>R 21 E</td></tr> <tr><td></td><td>1/4</td></tr> <tr><td>S 7</td><td>  S 8</td></tr> </table> <p>2016</p> </div> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p> <p>Set a steel fence post W. of cor.</p> <p>Cor. is located in a badlands cove, 300 x 80 ft., bears S. 70° E. and W.</p>	T 21 N	R 21 E		1/4	S 7	S 8
T 21 N	R 21 E						
	1/4						
S 7	S 8						
64.60	<p>BIA Route 9860, a bladed dirt road, 25 ft. wide, bears S. 80° E. and N. 85° W.</p>						
80.00	<p>Point for the cor. of secs. 5, 6, 7, and 8.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center;"> <table style="margin: auto;"> <tr><td>T 21 N</td><td>R 21 E</td></tr> <tr><td>S 6</td><td>  S 5</td></tr> <tr><td>S 7</td><td>  S 8</td></tr> </table> <p>2016</p> </div> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p> <p>Set a steel fence post W. of cor.</p> <p>Land, nearly level, in rolling badlands. Soil, sandy loam and clay. No timber; native grasses, rabbit brush, and salt brush.</p> <hr/> <p>From the cor. of secs. 4, 5, 8, and 9.</p> <p>West, bet. secs. 5 and 8.</p> <p>Ascending E. slope of badlands.</p>	T 21 N	R 21 E	S 6	S 5	S 7	S 8
T 21 N	R 21 E						
S 6	S 5						
S 7	S 8						
39.98	<p>Point for the 1/4 sec. cor. of secs. 5 and 8.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p>						



Independent Resurvey of the Subdivisional Lines,  
T. 21 N., R. 21 E., Gila and Salt River Meridian, Arizona

CHAINS	
	T 21 N R 21 E S 5 1/4 ——— S 8  2016
	Deposit a magnet, in a white plastic case, at the base of the stainless steel post.
	Set a steel fence post W. of cor.
79.96	The cor. of secs. 5, 6, 7, and 8.  Land, rolling badlands to gently rolling. Soil, sandy loam and clay. No timber; native grasses and salt brush.
	N. 89°58' W., bet. secs. 6 and 7.  Over nearly level land.
40.00	Point for the 1/4 sec. cor. of secs. 6 and 7.  Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 25 ins. in the ground, with brass cap mkd.
	T 21 N R 21 E S 6 1/4 ——— S 7  2016
	Deposit a magnet, in a white plastic case, at the base of the stainless steel post.
	Set a steel fence post N. of cor.
67.80	BIA Route 9860, a bladed dirt road, 25 ft. wide, bears S. 80° E. and N. 80° W.
78.52	The cor. of secs. 1, 6, 7, and 12, on the W. bdy. of the Tp., hereinbefore described.  Land, nearly level. Soil, sandy loam. No timber; native grasses, rabbit brush, and salt brush.
	From the cor. of secs. 5, 6, 7, and 8.

**Independent Resurvey of the Subdivisional Lines,  
T. 21 N., R. 21 E., Gila and Salt River Meridian, Arizona**

CHAINS	
	<p>N. 0°26' W., bet. secs. 5 and 6.</p> <p>Over nearly level land.</p>
40.00	<p>Point for the 1/4 sec. cor. of secs. 5 and 6.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T 21 N R 21 E 1/4 S 6   S 5</p> <p style="text-align: center;">2016</p> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p> <p>Set a steel fence post W. of cor.</p>
77.04	<p>The cor. of secs. 5, 6, 31, and 32, on the N. bdy. of the Tp., monumented with a stainless steel post, 2 1/2 ins. diam., firmly set, projecting 8 ins. above ground, with a steel fence post, N. of cor., with brass cap mkd. T22N R21E S31 S32 S6 S5 T21N 2009. Add the marks 2016 to the brass cap.</p> <p>Land, nearly level and scattered badlands. Soil, sandy loam. No timber; native grasses, rabbit brush, and salt brush.</p> <hr/> <p style="text-align: center;"><b>Subdivision of Section 13, T. 21 N., R. 21 E., Gila and Salt River Meridian, Arizona</b></p> <hr/> <p>From the 1/4 sec. cor. of secs. 13 and 24.</p> <p>N. 0°01' E., on the N. and S. center line of sec. 13.</p> <p>Over gently rolling land.</p>
40.00	<p>Point for the center 1/4 sec. cor. of sec. 13, at intersection with the E. and W. center line sec. 13.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 25 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T 21 N R 21 E C 1/4 S 13</p> <p style="text-align: center;">2016</p> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p>

**Subdivision of Section 13,  
T. 21 N., R. 21 E., Gila and Salt River Meridian, Arizona**

CHAINS	
	Set a steel fence post W. of cor.
80.00	The 1/4 sec. cor. of secs. 12 and 13.
<hr/>	
	From the 1/4 sec. cor. of secs. 13 and 18, on the E. bdy. of the Tp.
	N. 89°58' W., on the E. and W. center line of sec. 13.
	Over gently rolling land.
5.85	E. right-of-way fence of BIA Route 6, barbed wire, 5 strand, parallels highway.
7.40	BIA Route 6, an asphalt surfaced road, 30 ft. wide, bears N. 15° E. and S. 15° W.
9.00	W. right-of-way fence of BIA Route 6, barbed wire, 5 strand, and an underground fiber optic line alongside, both parallel the highway.
25.40	Power line, 2 strand, bears N. 10° E. and S. 10° W.
33.70	Power line, 4 strand, bears N. 5° E. and S. 5° W.
40.05	The center 1/4 sec. cor. of sec. 13.
80.10	The 1/4 sec. cor. of secs. 13 and 14.
<hr/>	
<p><b>Subdivision of Section 24, T. 21 N., R. 21 E., Gila and Salt River Meridian, Arizona</b></p>	
<hr/>	
	From the 1/4 sec. cor. of secs. 24 and 25.
	N. 0°01' E., on the N. and S. center line of sec. 24.
	Over gently rolling land.
2.55	E. right-of-way fence of BIA Route 6, barbed wire, 5 strand, bears N. 15° E. and S. 15° W.
3.20	Power line, 2 strand, bears S. 65° E. and N. 65° W.
8.00	BIA Route 6, an asphalt surfaced road, 30 ft. wide, bears N. 15° E. and S. 15° W.
13.45	W. right-of-way fence of BIA Route 6, barbed wire, 5 strand, parallels highway.
13.65	Underground fiber optic line, bears N. 15° E. and S. 15° W.

Subdivision of Section 24,  
T. 21 N., R. 21 E., Gila and Salt River Meridian, Arizona

CHAINS	
26.85	Power line, 2 strand, bears N. 10° E. and S. 10° W.
40.00	Point for the center 1/4 sec. cor. of sec. 24, at the intersection with the E. and W. center line sec. 24.  Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 25 ins. in the ground, with brass cap mkd.  T 21 N R 21 E C 1/4 S 24  2016  Deposit a magnet, in a white plastic case, at the base of the stainless steel post.  Set a steel fence post W. of cor.  Cor. is located 2.10 chs. W. of a power line, 2 strand, bears N. 10° E. and S. 10° W., and is 1.70 chs. E. of a power line, 4 strand, bears N. 5° E. and S. 5° W.
56.60	Power line, 4 strand, bears N. 5° E. and S. 5° W.
80.00	The 1/4 sec. cor. of secs. 13 and 24. <hr/>
	From the 1/4 sec. cor. of secs. 19 and 24, on the E. bdy. of the Tp.  N. 89°58' W., on the E. and W. center line of sec. 24.  Over gently rolling land.
29.10	E. right-of-way fence of BIA Route 6, barbed wire, 5 strand, parallels highway.
30.70	BIA Route 6, an asphalt surfaced road, 30 ft. wide, bears N. 15° E. and S. 15° W.
32.30	W. right-of-way fence of BIA Route 6, barbed wire, 5 strand, and an underground fiber optic line alongside, both parallel the highway.
40.03	The center 1/4 sec. cor. of sec. 24.
80.06	The 1/4 sec. cor. of secs. 23 and 24. <hr/>

Subdivision of Section 25,  
T. 21 N., R. 21 E., Gila and Salt River Meridian, Arizona

CHAINS	
	<p>From the 1/4 sec. cor. of secs. 25 and 36.</p> <p>N. 0°01' E., on the N. and S. center line of sec. 25.</p> <p>Over gently rolling land.</p>
40.00	<p>Point for the center 1/4 sec. cor. of sec. 25, at the intersection with the E. and W. center line sec. 25.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 25 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T 21 N R 21 E C 1/4 S 25</p> <p style="text-align: center;">2016</p> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p> <p>Set a steel fence post W. of cor.</p>
57.30	BIA Route 9068, a bladed dirt road, 25 ft. wide, bears S. 75° E. and N. 75° W.
80.00	The 1/4 sec. cor. of secs. 24 and 25.
	<hr/> <p>From the 1/4 sec. cor. of secs. 25 and 30, on the E. bdy. of the Tp.</p> <p>N. 89°58' W., on the E. and W. center line of sec. 25.</p> <p>Over gently rolling land.</p>
40.01	The center 1/4 sec. cor. of sec. 25.
52.55	Power line, 4 strand, bears N. 20° E. and S. 20° W.
53.35	E. right-of-way fence of BIA Route 6, barbed wire, 5 strand, bears N. 15° E. and S. 15° W.
54.95	BIA Route 6, an asphalt surfaced road, 30 ft. wide, bears N. 20° E. and S. 20° W.
56.60	W. right-of-way fence of BIA Route 6, barbed wire, 5 strand, and an underground fiber optic line alongside, both parallel the highway.
80.02	The 1/4 sec. cor. of secs. 25 and 26.
	<hr/>

Subdivision of Section 35,  
T. 21 N., R. 21 E., Gila and Salt River Meridian, Arizona

CHAINS	
	From the stan. 1/4 sec. cor. of sec. 35 only, on the S. bdy. of the Tp.
	N. 0°01' W., on the N. and S. center line of sec. 35.
	Over gently rolling land.
3.60	BIA Route 9861, a bladed dirt road, 25 ft. wide, bears S. 75° E. and N. 70° W.
40.00	Point for the center 1/4 sec. cor. of sec. 35, at the intersection with the E. and W. center line sec. 35.
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.
	T 21 N R 21 E C 1/4 S 35
	2016
	Deposit a magnet, in a white plastic case, at the base of the stainless steel post.
	Set a steel fence post W. of cor.
80.00	The 1/4 sec. cor. of secs. 26 and 35.
	<hr/>
	From the 1/4 sec. cor. of secs. 35 and 36.
	N. 89°58' W., on the E. and W. center line of sec. 35.
	Over gently rolling land.
3.95	Power line, 4 strand, bears N. 20° E. and S. 20° W.
4.70	E. right-of-way fence of BIA Route 6, barbed wire, 5 strand, parallels highway.
6.30	BIA Route 6, an asphalt surfaced road, 30 ft. wide, bears N. 20° E. and S. 20° W.
7.95	W. right-of-way fence of BIA Route 6, barbed wire, 5 strand, and an underground fiber optic line alongside, both parallel the highway.
40.00	The center 1/4 sec. cor. of sec. 35.
80.00	The 1/4 sec. cor. of secs. 34 and 35.
	<hr/>

Subdivision of Section 36,  
T. 21 N., R. 21 E., Gila and Salt River Meridian, Arizona

CHAINS	
	<p>From the stan. 1/4 sec. cor. of sec. 36 only, on the S. bdy. of the Tp.</p> <p>North, on the N. and S. center line of sec. 36.</p> <p>Over gently rolling land.</p>
36.30	Most easterly of two, high voltage transmission lines, bears N. 40° E. and S. 40° W.
39.99	<p>Point for the center 1/4 sec. cor. of sec. 36, at the intersection with the E. and W. center line sec. 36.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 25 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T 21 N R 21 E C 1/4 S 36</p> <p style="text-align: center;">2016</p> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p> <p>Set a steel fence post W. of cor.</p> <p>Cor. is located 90 lks. W. and 1 ch. N. of most westerly of two, high voltage transmission lines, bears N. 40° E. and S. 40° W.</p>
79.99	<p>The 1/4 sec. cor. of secs. 25 and 36.</p> <hr/> <p>From the 1/4 sec. cor. of secs. 31 and 36, on the E. bdy. of the Tp.</p> <p>N. 89°58' W., on the E. and W. center line of sec. 36.</p> <p>Over gently rolling land.</p>
36.60	Most easterly of two, high voltage transmission lines, bears N. 40° E. and S. 40° W.
39.98	The center 1/4 sec. cor. of sec. 36.
79.98	<p>The 1/4 sec. cor. of secs. 35 and 36.</p> <hr/>

## T. 21 N., R. 21 E., Gila and Salt River Meridian, Arizona

CHAINS

## GENERAL DESCRIPTION

---

The area surveyed is within the Navajo Indian Reservation, 20 miles north of Holbrook, AZ, and 12 miles south of Indian Wells, AZ. The Navajo Indian Reservation boundary is identical with the south boundary of the township. Access is by way of U.S. Interstate Highway 77, which becomes BIA Route 6, at the south boundary of the Navajo Indian Reservation. A series of two track roads provide access throughout the township from numerous named bladed dirt roads which run longitudinally from BIA Route 6. ATV's were required to access the majority of the areas within the township.

The terrain consists of gently rolling to rolling badlands, with numerous areas of floodplains. Cottonwood Wash enters the township in the northwest portion of section 6, drains southwesterly. Salt Seeps Wash, is the principal watercourse. It enters the township in section 1, and meanders and drains southwesterly, exiting in the northwest portion of section 31. The vegetation is abundant in the low areas of the floodplain and consists of native grasses, salt brush, rabbit brush, yucca, cholla, Mormon tea, and salt cedar along the wash. There is the presence of grazing cattle and horses in the area. The soil is mostly sandy loam throughout the township, and clay is more prominent near the areas of the badlands.

There are no major housing developments. The mean elevation is 5400 ft. above sea level.

The mean magnetic declination of 10° E. was derived from the United States Geological Survey computer program GEOMAG, utilizing the World Magnetic Model for Epoch 2010-2015 for the dates of the survey.

---






CERTIFICATE OF SURVEY

I, Fabian Yazzie, Cadastral Surveyor, HEREBY CERTIFY upon honor, that in pursuance of special instructions bearing date of the 28th day of April, 2016, and Supplemental Special Instructions bearing the date of the 20th day of September, 2016, I have dependently resurveyed a portion of the Fifth Standard Parallel North (south boundary), independently resurveyed a portion of the Fifth Guide Meridian East (west boundary), the east boundary, subdivisional lines, and the subdivision of certain sections, T. 21 N., R. 21 E., of the Gila and Salt River Meridian, in the State of Arizona, which are represented in the foregoing field notes as having been executed by me and under my direction. Said survey has been made in strict conformity with said special instructions, the Manual of Instructions for the Survey of the Public Lands of the United States, 2009, and in the specific manner described in the foregoing field notes.

7/28/2017  
(Date)


  
(Cadastral Surveyor)

CERTIFICATE OF APPROVAL

BUREAU OF LAND MANAGEMENT  
Phoenix, Arizona

The foregoing field notes of the dependent resurvey of a portion of the Fifth Standard Parallel North (south boundary), independent resurvey of a portion of the Fifth Guide Meridian East (west boundary), the east boundary, the subdivisional lines, and the subdivision of certain sections, T. 21 N., R. 21 E., Gila and Salt River Meridian, in the State of Arizona, executed by Fabian Yazzie, Cadastral Surveyor, having been critically examined and found correct, are hereby approved.

8/16/2017  
(Date)

  
(Chief Cadastral Surveyor of Arizona)

~~CERTIFICATE OF TRANSCRIPT~~

~~I CERTIFY that the foregoing transcript of the field notes of the above-described surveys in T. 21 N., R. 21 E., Gila and Salt River Meridian, Arizona, is a true copy of the original field notes.~~

~~\_\_\_\_\_~~  
~~(Date)~~

~~\_\_\_\_\_~~  
~~(Chief Cadastral Surveyor of Arizona)~~