

ORIGINAL

**UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT**

FIELD NOTES
OF THE SURVEY OF
THE
SOUTH AND EAST BOUNDARIES
AND THE SUBDIVISIONAL LINES
AND
THE SUBDIVISION OF CERTAIN SECTIONS,
TOWNSHIP 40 NORTH, RANGE 25 EAST,
OF THE GILA AND SALT RIVER MERIDIAN,
IN THE STATE OF ARIZONA.

EXECUTED BY

Rosendo Ramos Serrano, Cadastral Surveyor

Under Special Instructions, dated May 09, 2017 approved May 09, 2017, which provided for the surveys included under Group No. 1173, and assignment instructions dated May 09, 2017.

Survey commenced May 15, 2017

Survey completed September 07, 2017

INDEX DIAGRAM

TOWNSHIP 40 NORTH RANGE 25 EAST
GILA & SALT RIVER MERIDIAN, ARIZONA

62 6 60 60	61 5 49 59	50 4 41 48	42 3 32 40	33 2 22 31	23 1 14 21
7 58 58	8 47 57	9 39 47	10 30 39	11 21 30	12 13 20
18 56 56	17 46 55	16 38 46	15 29 37	14 19 28	13 12 19
19 54 54	20 45 53	21 36 44	22 27 36	23 18 27	24 11 17
30 52 52	29 44 51	28 35 43	27 26 34	26 16 25	25 10 16
31 50 9	32 42 8	33 34 6	34 24 6	35 15 5	36 9 4

Subdivision of Section 1 Pages 62-63
 Subdivision of Section 2 Pages 63-64
 Subdivision of Section 11 Pages 64-65
 Subdivision of Section 14 Pages 65-66
 Subdivision of Section 23 Pages 66-67
 Subdivision of Section 26 Pages 67-68
 Subdivision of Section 34 Pages 68-69
 Subdivision of Section 35 Pages 69-70

T. 40 N., R. 25 E., Gila and Salt River Meridian, Arizona

CHAINS

The following field notes describe the survey of the south and east boundaries and the subdivisional lines and the subdivision of certain sections, Township 40 North, Range 25 East, Gila and Salt River Meridian, Arizona.

The history of surveys pertaining to this survey is as follows:

Leonard R. Sandoval surveyed the South, East and West boundaries of Township 40 North, Range 27 East, in 2000 (Book 8642). Jones Curtiss surveyed a portion of the Tenth Standard Parallel North thru Township 41 North, Range 25 East, and the Sixth Guide Meridian East thru Township 41 North, Range 25 East, in 2000-02 (Book 5658). Alvina A. Begaye surveyed the South and East Boundaries of Township 40 North, Range 24 East, in 2011 (Book 5964). In addition, Fabian Yazzie Dependently Resurveyed a portion of the Arizona-Utah State Line thru Township 41 North, Range 26 East, in 2015 (Book 6059).

The survey was executed in accordance with the specifications as set forth in the Manual of Surveying Instructions, (2009), and the Special Instructions dated May 09, 2017 for Group No. 1173, Arizona.

The true meridian direction and length of all lines were determined by real time kinematic Global Navigation Satellite System (GNSS), observations using Trimble Navigation R8-3, R8-4, R8S and terrestrial observations using a Trimble Navigation S6 model 3" total station.

Preliminary to the resurvey, the lines of the prior surveys were retraced and search was made for all corners and other calls of record. The retracement data were thoroughly verified and only the true line field notes are given herein.

Geodetic control was derived from Global Navigation Satellite System (GNSS) static observations post processed by National Geodetic Survey, Online Positioning User Service (OPUS), utilizing Continuously Operating Reference Stations DI3419 P012 MONTICELLOUT 2006 CORS ARP, DO2634 CTI4 COMPASSTOOLS4CRNR CORS ARP DL3642 MC09 NUCLA CORS ARP. NAD_83 (2011) (EPOCH:2010.0000). The geographic position of the corner of Townships 39 and 40 North, Ranges 25 and 26 East is as follows:

Latitude: 36°49'26.914"N. Longitude: 109°36'26.436"W.

The geographic position of the corner of Townships 40 and 41 North, Ranges 24 and 25 East, is as follows:

Latitude: 36°54'31.526"N. Longitude: 109°42'56.095" W.

The mean magnetic declination is 10° E.

Survey of the South Boundary,
T. 40 N., R. 25 E., Gila and Salt River Meridian, Arizona

CHAINS							
	<p>Beginning at the cor. of Tps. 40 N., Rs. 25 and 26 E., determined West, 480 chs., from the cor. of Tp. 40 N., Rs. 26 and 27 E., monumented with a stainless steel post, 2 1/2 ins. diam., firmly set, projecting 3 ins. above ground, with brass cap mkd. T40N R26E R27E S36 S31 2000 2011. Add the marks 2017 to the brass cap.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center;"> <table style="margin: auto;"> <tr><td colspan="2">T 40 N</td></tr> <tr><td>R 25 E</td><td>R 26 E</td></tr> <tr><td><u>S 36</u></td><td><u>S 31</u></td></tr> </table> <p>2017</p> </div> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p> <p>Set a steel fence post nearby.</p> <p>Cor. is located on gently, rolling, sandy terrain, through natural grass, rabbit brush and Mormon tea.</p> <p>From this cor., an iron pipe, 2 1/2 ins. diam., firmly set, projecting 15 ins. above ground, bears S. 51°04' E., 88.7 ft. dist., with brass cap mkd. T40N S36 S31 R25E S1 S6 R26E T39N G.&S.R.M 1961 F.S.O.S.</p> <p>West, on the S. bdy. of sec. 36.</p> <p>Over gently rolling sand dunes, through native brush.</p>	T 40 N		R 25 E	R 26 E	<u>S 36</u>	<u>S 31</u>
T 40 N							
R 25 E	R 26 E						
<u>S 36</u>	<u>S 31</u>						
39.99	<p>Point for the 1/4 sec. cor. of sec. 36.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center;"> <table style="margin: auto;"> <tr><td>T 40 N</td><td>R 25 E</td></tr> <tr><td>1/4</td><td><u>S 36</u></td></tr> </table> <p>2017</p> </div> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p> <p>Set a steel fence post nearby.</p>	T 40 N	R 25 E	1/4	<u>S 36</u>		
T 40 N	R 25 E						
1/4	<u>S 36</u>						
79.98	<p>Point for the cor. of secs. 35 and 36.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p>						

Survey of the South Boundary,
T. 40 N., R. 25 E., Gila and Salt River Meridian, Arizona

CHAINS	
	T 40 N R 25 E <u>S 35 S 36</u>
	2017
	Deposit a magnet, in a white plastic case, at the base of the stainless steel post. Set a steel fence post nearby. From this cor., an iron pipe, 2 1/2 ins. diam., firmly set, projecting 12 ins. above ground, bears S. 50°26' E., 88.1 ft. dist., iron pipe mkd. T40N R25E 35 36 2 1 T39N.

	West, along the S. bdy. of sec. 35. Over gently rolling sandy terrain, through rabbit brush, Yucca, greasewood and Mormon tea.
39.99	Point for the 1/4 sec. cor. of sec. 35. Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.
	T 40 N R 25 E <u>1/4 S 35</u>
	2017
	Deposit a magnet, in a white plastic case, at the base of the stainless steel post. Set a steel fence post nearby.
79.97	Point for the cor. of sec. 34 and 35 only. Set a brass tablet, 3 1/2 ins. diam., flush in sandstone bedrock, with brass cap mkd.
	T 40 N R 25 E <u>S 34 S 35</u>
	2017
	Deposit a magnet, in a white plastic case, at the base of the brass tablet. Raise a mound of stone, 2 1/2 ft. base, 2 ft. high, S. of cor.

Survey of the South Boundary,
T. 40 N., R. 25 E., Gila and Salt River Meridian, Arizona

CHAINS	
	<p>From this cor. an iron pipe, 2 1/2 ins. diam., firmly set in concrete, projecting 18 ins. above ground, bears S. 50°19' E., 90.1 ft. dist., mkd. T40N R25E 34 35 3 2 T39N.</p> <hr/> <p>West, along the S. bdy. of sec. 34.</p> <p>Over gently rolling sandstone terrain, through rabbit brush and Yucca.</p>
4.53	Intersect the E. right-of-way fence of U.S. Highway No. 191, parallels the highway.
6.07	U.S. Highway No. 191, asphalt surfaced, 27 ft. wide, bears N. 8° E. and S. 8° W.
7.59	Intersect the W. right-of-way fence of U.S. Highway No. 191, parallels the highway.
9.11	Power line, 4 strands, bears N. 8° E. and S. 8° W.
39.99	<p>Point for the 1/4 sec. cor. of sec. 34.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 19 ins. in the ground, in a collar of stone, with brass cap mkd.</p> <p style="text-align: center;">T 40 N R 25 E 1/4 S 34</p> <hr style="width: 10%; margin: auto;"/> <p style="text-align: center;">2017</p> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p>
79.98	<p>Point for the cor. of secs. 33 and 34.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T 40 N R 25 E S 33 S 34</p> <hr style="width: 10%; margin: auto;"/> <p style="text-align: center;">2017</p> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p> <p>Set a steel fence post nearby.</p> <hr/> <p>West, along the S. bdy. of sec. 33.</p>

Survey of the South Boundary,
T. 40 N., R. 25 E., Gila and Salt River Meridian, Arizona

CHAINS	
	Over gently rolling sandy terrain, through rabbit brush, Mormon Tea and Yucca.
39.99	Point for the 1/4 sec. cor. of sec. 33. Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd. <div style="text-align: center;"> T 40 N R 25 E 1/4 S 33 <hr style="width: 10%; margin: auto;"/> 2017 </div> Deposit a magnet, in a white plastic case, at the base of the stainless steel post. Set a steel fence post nearby.
79.97	Point for the cor. of sec. 32 and 33. Set a stainless steel post, 15 ins. long, 2 1/2 ins. diam., 21 ins. in the ground, in BIA Road No. 5023, with brass cap, 6 ins. below ground, mkd. <div style="text-align: center;"> T 40 N R 25 E S 32 S 33 <hr style="width: 10%; margin: auto;"/> 2017 </div> Deposit a magnet, in a white plastic case, at the base of the stainless steel post. Set a steel fence post nearby. from which A stainless steel post, 28 ins. long, 2 1/2 ins. diam., set 24 ins. in the ground for a reference monument, bears S. 45°00' E., 75.0 ft. dist. with brass cap mkd. RM T39N R25E 75.00FT TO COR. S6 2017 and an arrow pointing to the cor. Deposit a magnet, in a white plastic case, at the base of the stainless steel post. Set a steel fence post nearby.

Survey of the South Boundary,
T. 40 N., R. 25 E., Gila and Salt River Meridian, Arizona

CHAINS	
	<p>A stainless steel post, 28 ins. long, 2 1/2 ins. diam., set 24 ins. in the ground for a reference monument, bears N. 45°00' W., 75.0 ft. dist. with brass cap mkd. RM T40N R25E 75.00FT TO COR. S32 2017 and an arrow pointing to the cor. Deposit a magnet, in a white plastic case, at the base of the stainless steel post. Set a steel fence post nearby.</p> <hr/> <p>West, along the S. bdy. of sec. 32.</p> <p>Over gently rolling sandy terrain, through natural grasses and rabbit brush.</p>
0.02	BIA Road No. 5057, graded road, 45 ft. wide, bears N. 67° E. and S. 67° W.
2.25	Underground water line, bears S. 20° E. and N. 20° W.
39.99	<p>Point for the 1/4 sec. cor. of sec. 32.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T 40 N R 25 E 1/4 S 32 _____</p> <p style="text-align: center;">2017</p> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p> <p>Set a steel fence post nearby.</p>
67.17	BIA road No. 5057, graded road, 45 ft. wide, bears S. 13° E. and N. 13° W.
74.40	Power line, 2 strands, bears S. 8° E. and N. 8° W.
75.12	Underground water line, bears S. 9° E. and N. 9° W.
77.78	Wash, 30 ft. wide, 4 ft. deep, drains N. 47° W.
79.97	<p>Point for the cor. of sec. 31 and 32.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T 40 N R 25 E S 31 S 32 _____</p> <p style="text-align: center;">2017</p>

**Survey of the South Boundary,
T. 40 N., R. 25 E., Gila and Salt River Meridian, Arizona**

CHAINS	
	<p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p> <p>Set a steel fence post nearby.</p> <hr/> <p>West, along the S. bdy. of sec. 31.</p> <p>Over gently rolling sandy terrain, through greasewood and natural grasses.</p>
1.12	Trail road, bears S. 52° E. and N. 52° W.
39.99	<p>Point for the 1/4 sec. cor. of sec. 31.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T 40 N R 25 E 1/4 S 31</p> <hr style="width: 10%; margin: auto;"/> <p style="text-align: center;">2017</p> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p> <p>Set a steel fence post nearby.</p>
80.27	<p>The cor. of Tp. 40 N., Rs. 24 and 25 E., monumented with a stainless steel post, 2 1/2 ins. diam., firmly set, projecting 3 ins. above ground, with brass cap mkd. T40N R24E R25E S36 S31 2011, add the marks 2017 to the brass cap.</p> <hr/> <p style="text-align: center;">Survey of the East Boundary, T. 40 N., R. 25 E., Gila and Salt River Meridian, Arizona</p> <hr/> <p>From the cor. of Tps. 40 N., Rs. 25 and 26 E., hereinbefore described.</p> <p>North, along the E. bdy. of the Tp., bet. secs. 31 and 36.</p> <p>Over gently rolling sandy terrain, through Mormon Tea, Yucca and natural grasses.</p>
39.99	<p>Point for the 1/4 sec. cor. of secs. 31 and 36, on the E. bdy. of the Tp.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p>

Survey of the East Boundary,
T. 40 N., R. 25 E., Gila and Salt River Meridian, Arizona

CHAINS	
	T 40 N R 25 E R 26 E 1/4 S 36 S 31 2017
	Deposit a magnet, in a white plastic case, at the base of the stainless steel post. Set a steel fence post nearby.
79.98	Point for the cor. of secs. 25, 30, 31 and 36, on the E. bdy. of the Tp. Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.
	T 40 N R 25 E R 26 E S 25 S 30 S 36 S 31 2017
	Deposit a magnet, in a white plastic case, at the base of the stainless steel post. Set a steel fence post nearby.
	<hr/> North, along the E. bdy. of the Tp., bet. secs. 25 and 30. Over gently rolling ground with approximately 3 ins. of sandy top soil and underlying sandstone bedrock.
39.99	Point for the 1/4 sec. cor. of secs. 25 and 30, on the E. bdy. of the Tp. Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.
	T 40 N R 25 E R 26 E 1/4 S 25 S 30 2017
	Deposit a magnet, in a white plastic case, at the base of the stainless steel post. Set a steel fence post nearby.

Survey of the East Boundary,
T. 40 N., R. 25 E., Gila and Salt River Meridian, Arizona

CHAINS									
79.97	<p>Point for the cor. of secs. 19, 24, 25 and 30, on the E. bdy. of the Tp.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <table style="margin-left: auto; margin-right: auto; border-collapse: collapse;"> <tr> <td colspan="2" style="text-align: center;">T 40 N</td> </tr> <tr> <td style="text-align: center;">R 25 E</td> <td style="text-align: center;">R 26 E</td> </tr> <tr> <td style="text-align: center;">S 24</td> <td style="text-align: center;">S 19</td> </tr> <tr> <td style="text-align: center;">S 25</td> <td style="text-align: center;">S 30</td> </tr> </table> <p style="text-align: center;">2017</p> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p> <p>Set a steel fence post nearby.</p> <p>From this cor. an iron pipe, 2 1/2 ins. diam., firmly set, projecting 12 ins. above ground, bears S. 51°22' E., 89.7 ft. dist., with brass cap mkd. T40N R25E R26E S24 S19 S25 S30 G.&.S.R.M 1968 F.S.O.S.</p> <hr/> <p>North, along the E. bdy. of the Tp., bet. secs. 24 and 19.</p> <p>Over gently rolling terrain, through Mormon tea, rabbit brush, Yucca and natural grasses.</p>	T 40 N		R 25 E	R 26 E	S 24	S 19	S 25	S 30
T 40 N									
R 25 E	R 26 E								
S 24	S 19								
S 25	S 30								
39.99	<p>Point for the 1/4 sec. cor. of secs. 19 and 24, on the E. bdy. of the Tp.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <table style="margin-left: auto; margin-right: auto; border-collapse: collapse;"> <tr> <td colspan="2" style="text-align: center;">T 40 N</td> </tr> <tr> <td style="text-align: center;">R 25 E</td> <td style="text-align: center;">R 26 E</td> </tr> <tr> <td colspan="2" style="text-align: center;">1/4</td> </tr> <tr> <td style="text-align: center;">S 24</td> <td style="text-align: center;">S 19</td> </tr> </table> <p style="text-align: center;">2017</p> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p> <p>Set a steel fence post nearby.</p>	T 40 N		R 25 E	R 26 E	1/4		S 24	S 19
T 40 N									
R 25 E	R 26 E								
1/4									
S 24	S 19								
79.98	<p>Point for the cor. of secs. 13, 18, 19 and 24, on the E. bdy. of the Tp.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p>								

Survey of the East Boundary,
T. 40 N., R. 25 E., Gila and Salt River Meridian, Arizona

CHAINS									
	<table style="margin: auto;"> <tr><td colspan="2">T 40 N</td></tr> <tr><td>R 25 E</td><td>R 26 E</td></tr> <tr><td>S 13</td><td>S 18</td></tr> <tr><td>S 24</td><td>S 19</td></tr> </table>	T 40 N		R 25 E	R 26 E	S 13	S 18	S 24	S 19
T 40 N									
R 25 E	R 26 E								
S 13	S 18								
S 24	S 19								
	2017								
	<p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p> <p>Set a steel fence post nearby.</p> <p>From this cor. an iron pipe, 2 1/2 ins. diam., firmly set, projecting 18 ins. above ground, bears S. 43° E., 85.3 ft. dist., with brass cap mkd. T40N R25E R26E 13 18 24 19.</p> <hr/> <p>North, along the E. bdy. of the Tp., bet. secs. 13 and 18.</p> <p>Over gently rolling sandstone terrain.</p>								
39.99	<p>Point for the 1/4 sec. cor. of secs. 13 and 18, on the E. bdy. of the Tp.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 19 ins. in the ground, in a mound of stone, 2 ft. base, 6 ins. high, with brass cap mkd.</p>								
	<table style="margin: auto;"> <tr><td colspan="2">T 40 N</td></tr> <tr><td>R 25 E</td><td>R 26 E</td></tr> <tr><td colspan="2">1/4</td></tr> <tr><td>S 13</td><td>S 18</td></tr> </table>	T 40 N		R 25 E	R 26 E	1/4		S 13	S 18
T 40 N									
R 25 E	R 26 E								
1/4									
S 13	S 18								
	2017								
	<p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p> <p>Set a steel fence post nearby.</p>								
77.23	<p>Power line, 2 strands, bears S. 70° E. and N. 70° W.</p>								
79.97	<p>Point for the cor. of secs. 7, 12, 13 and 18, on the E. bdy. of the Tp.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 25 ins. in the ground, in a collar of stone, with brass cap mkd.</p>								

Survey of the East Boundary,
T. 40 N., R. 25 E., Gila and Salt River Meridian, Arizona

CHAINS									
	<table style="margin: auto;"> <tr><td colspan="2">T 40 N</td></tr> <tr><td>R 25 E</td><td>R 26 E</td></tr> <tr><td>S 12</td><td>S 7</td></tr> <tr><td>S 13</td><td>S 18</td></tr> </table>	T 40 N		R 25 E	R 26 E	S 12	S 7	S 13	S 18
T 40 N									
R 25 E	R 26 E								
S 12	S 7								
S 13	S 18								
	2017								
	Deposit a magnet, in a white plastic case, at the base of the stainless steel post.								
	Set a steel fence post nearby.								
	From this cor., an iron pipe, 2 1/2 ins. diam., firmly set, projecting 10 ins. above ground, in a collar of stone, bears S. 52° E., 91.9 ft. dist., iron pipe mkd. T40N R25E R26E 12 7 13 8.								

	North, along the E. bdy. of the Tp., bet. secs. 12 and 7.								
	Over gently rolling terrain.								
2.77	BIA road No. 5054, graded road, 25 ft. wide, bears S. 70° E. and N. 69° W.								
39.99	Point for the 1/4 sec. cor. of secs. 7 and 12, on the E. bdy. of the Tp.								
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.								
	<table style="margin: auto;"> <tr><td colspan="2">T 40 N</td></tr> <tr><td>R 25 E</td><td>R 26 E</td></tr> <tr><td colspan="2" style="text-align: center;">1/4</td></tr> <tr><td>S 12</td><td>S 7</td></tr> </table>	T 40 N		R 25 E	R 26 E	1/4		S 12	S 7
T 40 N									
R 25 E	R 26 E								
1/4									
S 12	S 7								
	2017								
	Deposit a magnet, in a white plastic case, at the base of the stainless steel post.								
	Set a steel fence post nearby.								
79.98	Point for the cor. of secs. 1, 6, 7 and 12, on the E. bdy. of the Tp.								
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.								

Survey of the East Boundary,
T. 40 N., R. 25 E., Gila and Salt River Meridian, Arizona

CHAINS									
	<table style="margin-left: auto; margin-right: auto;"> <tr><td colspan="2">T 40 N</td></tr> <tr><td>R 25 E</td><td>R 26 E</td></tr> <tr><td>S 1</td><td>S 6</td></tr> <tr><td>S 12</td><td>S 7</td></tr> </table>	T 40 N		R 25 E	R 26 E	S 1	S 6	S 12	S 7
T 40 N									
R 25 E	R 26 E								
S 1	S 6								
S 12	S 7								
	2017								
	<p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p> <p>Set a steel fence post nearby.</p> <p>From this cor., an iron pipe, 2 1/2 ins. diam., firmly set, projecting 14 ins. above ground, with mound of stone 2 ft. base, 1 ft. high, W. of cor., bears S. 53° E., 91.7 ft. dist., mkd. T40N R25E R26E 1 6 2 7.</p> <hr/> <p>North, along the E. bdy. of the Tp., bet. secs. 1 and 6.</p> <p>Over rolling, sandy terrain, with sandstone bedrock, through black brush, rabbit brush and Yucca.</p>								
39.99	<p>Point for the 1/4 sec. cor. of secs. 1 and 6, on the E. bdy. of the Tp.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 25 ins. in the ground, with brass cap mkd.</p>								
	<table style="margin-left: auto; margin-right: auto;"> <tr><td colspan="2">T 40 N</td></tr> <tr><td>R 25 E</td><td>R 26 E</td></tr> <tr><td colspan="2" style="text-align: center;">1/4</td></tr> <tr><td>S 1</td><td>S 6</td></tr> </table>	T 40 N		R 25 E	R 26 E	1/4		S 1	S 6
T 40 N									
R 25 E	R 26 E								
1/4									
S 1	S 6								
	2017								
	<p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p> <p>Set a steel fence post nearby.</p> <p>From this cor., the intersection of trail roads, bears S. 5° W., 52 ft. dist., with trail roads, 8 ft. wide, extending S. 87° E., N 82° W. and N. 32° W.</p>								
67.02	<p>Point for the closing cor. of Tps. 40 N., Rs. 25 and 26 E., at intersection with the Tenth Standard Parallel North, on the N. bdy. of the Tp.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p>								

Survey of the East Boundary,
T. 40 N., R. 25 E., Gila and Salt River Meridian, Arizona

CHAINS

T 41 N R 26 E
S 31

S 1 | S 6
R 25 E | R 26 E
T 40 N
CC

2017

Deposit a magnet, in a white plastic case, at the base of the stainless steel post.

Set a steel fence post nearby.

From this cor. point, the Standard 1/4 sec. cor. of sec. 31, T. 41 N., R 26 E., bears East, 37.33 chs. dist., monumented with a stainless steel post, 2 1/2 ins. diam., firmly set, projecting 2 ins. above ground, with brass cap mkd. SC T41N R26E 2000.

From this same cor. point, the Standard cor. of Tps. 41 N., Rs. 25 and 26 E., bears West., 2.67 chs. dist., monumented with a stainless steel post, 2 1/2 ins. diam., firmly set, projecting 3 ins. above ground, with brass cap mkd. SC T41N R25E R26E S36 S31 2000. Add the marks 2017 to the brass cap.

From this cor., a two track road, 8 ft. wide, bears W., 59 lks. dist., road bears S. 10° E. and N. 10° W., on a gently NE slope.

Survey of the Subdivisional Lines,
T. 40 N., R. 25 E., Gila and Salt River Meridian, Arizona

From the cor. of secs. 35 and 36 on the S. bdy. of the Tp., hereinbefore described.

N. 0°01' W., bet. secs. 35 and 36.

Over gently rolling, sandy terrain.

39.98

Point for the 1/4 sec. cor. of secs. 35 and 36.

Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.

T 40 N R 25 E
1/4
S 35 | S 36

2017

Deposit a magnet, in a white plastic case, at the base of the stainless steel post.

Survey of the Subdivisional Lines,
T. 40 N., R. 25 E., Gila and Salt River Meridian, Arizona

CHAINS									
	Set a steel fence post nearby.								
79.98	Point for the cor. of secs. 25, 26, 35 and 36. Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd. <div style="text-align: center;"> <table border="1"> <tr> <td>T 40 N</td> <td>R 25 E</td> </tr> <tr> <td>S 26</td> <td>S 25</td> </tr> <tr> <td>S 35</td> <td>S 36</td> </tr> </table> <p>2017</p> </div>	T 40 N	R 25 E	S 26	S 25	S 35	S 36		
T 40 N	R 25 E								
S 26	S 25								
S 35	S 36								
	Deposit a magnet, in a white plastic case, at the base of the stainless steel post.								
	<hr/> From the cor. of secs. 25, 30, 31 and 36, on the E. bdy. of the Tp., hereinbefore described. West, bet. secs. 25 and 36. Over gently rolling, sandy terrain.								
39.99	Point for the 1/4 sec. cor. of secs. 25 and 36. Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd. <div style="text-align: center;"> <table border="1"> <tr> <td>T 40 N</td> <td>R 25 E</td> </tr> <tr> <td></td> <td>S 25</td> </tr> <tr> <td>1/4</td> <td>—</td> </tr> <tr> <td></td> <td>S 36</td> </tr> </table> <p>2017</p> </div>	T 40 N	R 25 E		S 25	1/4	—		S 36
T 40 N	R 25 E								
	S 25								
1/4	—								
	S 36								
	Deposit a magnet, in a white plastic case, at the base of the stainless steel post.								
	Set a steel fence post nearby.								
79.98	The cor. of secs. 25, 26, 35 and 36. <hr/> N. 0°01' W., bet. secs. 25 and 26. Over slightly rolling, sandy terrain, with sandstone bedrock, through Mormon Tea, sage, rabbit brush and natural grasses.								
39.99	Point for the 1/4 sec. cor. of secs. 25 and 26.								

Survey of the Subdivisional Lines,
T. 40 N., R. 25 E., Gila and Salt River Meridian, Arizona

CHAINS	
	<p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T 40 N R 25 E 1/4 S 26 S 25</p> <p style="text-align: center;">2017</p> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p> <p>Set a steel fence post nearby.</p>
78.30	Barbed wire fence, bears S. 87° E. and N. 87° W.
79.98	Point for the cor. of secs. 23, 24, 25 and 26.
	<p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T 40 N R 25 E R 26 E S 23 S 24 S 26 S 25</p> <p style="text-align: center;">2017</p> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p> <p>Set a steel fence post nearby.</p> <p>From this cor., a open ended iron pipe, 2 1/2 ins. diam., firmly set in sandstone, projecting 20 ins. above ground, filled with cement, bears S. 53° E., 83.4 ft. dist., mkd. T40N R25E 23 24 26 25.</p> <hr/> <p>From the cor. of secs. 19, 24, 25 and 30, on the E. bdy. of the Tp., hereinbefore described.</p> <p>West, bet. secs. 24 and 25.</p> <p>Through gently rolling, sandy terrain.</p>
39.99	Point for the 1/4 sec. cor. of secs. 24 and 25.
	<p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p>

Survey of the Subdivisional Lines,
T. 40 N., R. 25 E., Gila and Salt River Meridian, Arizona

<p>CHAINS</p>	<p style="text-align: center;">T 40 N R 25 E S 24 1/4 ——— S 25</p> <p style="text-align: center;">2017</p> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p> <p>Set a steel fence post nearby.</p> <p>79.98 The cor. of secs. 23, 24, 25 and 26.</p> <hr/> <p>N. 0°01' W., bet. secs. 23 and 24.</p> <p>Over the top of flat, sandy, limestone mesa.</p> <p>39.99 Point for the 1/4 sec. cor. of secs. 23 and 24.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T 40 N R 25 E 1/4 S 23 S 24</p> <p style="text-align: center;">2017</p> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p> <p>Set a steel fence post nearby.</p> <p>79.97 Point for the cor. of secs. 13, 14, 23 and 24.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T 40 N R 25 E S 14 S 13 ————— S 23 S 24</p> <p style="text-align: center;">2017</p> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p> <p>Set a steel fence post nearby.</p> <p>Cor. falls on the top of the eastern edge of a mesa.</p> <hr/>
---------------	--

Survey of the Subdivisional Lines,
T. 40 N., R. 25 E., Gila and Salt River Meridian, Arizona

CHAINS	
	<p>From the cor. of secs. 13, 18, 19 and 24 on the E. bdy. of Tp. hereinbefore described.</p> <p>West, bet. secs. 13 and 24.</p> <p>Over slightly rolling terrain, blow sand and sandstone outcrops, through Mormon Tea, sage, rabbit brush and natural grasses.</p>
39.99	<p>Point for the 1/4 sec. cor. of secs. 13 and 24.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 21 ins. in the ground, in a collar of stone, with brass cap mkd.</p> <p style="text-align: center;">T 40 N R 25 E S 13 1/4 ——— S 24</p> <p style="text-align: center;">2017</p> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p> <p>Set a steel fence post nearby.</p>
79.97	<p>The cor. of secs. 13, 14 , 23 and 24.</p> <hr/> <p>N. 0°01' W., bet. secs. 13 and 14.</p> <p>Over gently rolling, sandy terrain.</p>
39.99	<p>Point for the 1/4 sec. cor. of secs. 13 and 14.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T 40 N R 25 E 1/4 S 14 S 13</p> <p style="text-align: center;">2017</p> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p> <p>Set a steel fence post nearby.</p>
46.16	<p>Power line, 2 strands, bears S. 88° E. and N. 88° W.</p>
79.98	<p>Point for the cor. of secs. 11, 12, 13 and 14.</p>

Survey of the Subdivisional Lines,
T. 40 N., R. 25 E., Gila and Salt River Meridian, Arizona

CHAINS									
	<p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p>								
	<table style="margin: auto;"> <tr> <td>T 40 N</td> <td>R 25 E</td> </tr> <tr> <td>S 11</td> <td>S 12</td> </tr> <tr> <td>S 14</td> <td>S 13</td> </tr> </table>	T 40 N	R 25 E	S 11	S 12	S 14	S 13		
T 40 N	R 25 E								
S 11	S 12								
S 14	S 13								
	2017								
	<p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p>								
	<p>Set a steel fence post nearby.</p> <hr/>								
	<p>From the cor. of secs. 7, 12, 13 and 18, on the E. bdy. of the Tp., hereinbefore described.</p>								
	<p>West, bet. secs. 12 and 13.</p>								
	<p>Over gently rolling terrain, blow sand and sandstone bedrock.</p>								
7.41	<p>Power line, 2 strands, bears S. 70° E. and N. 70° W.</p>								
37.23	<p>Trail road, bears N. 45° E. and S. 45° W.</p>								
39.99	<p>Point for the 1/4 sec. cor. of secs. 12 and 13.</p>								
	<p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 25 ins. in the ground, in a collar of stone, with brass cap mkd.</p>								
	<table style="margin: auto;"> <tr> <td>T 40 N</td> <td>R 25 E</td> </tr> <tr> <td></td> <td>S 12</td> </tr> <tr> <td></td> <td>1/4 ———</td> </tr> <tr> <td></td> <td>S 13</td> </tr> </table>	T 40 N	R 25 E		S 12		1/4 ———		S 13
T 40 N	R 25 E								
	S 12								
	1/4 ———								
	S 13								
	2017								
	<p>from which</p>								
	<p>A wooden power pole, supporting 2 strands power line, 9 ins. diam., bears N. 40°25' E., 110.6 ft. dist.</p>								
	<p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p>								
	<p>Set a steel fence post nearby.</p>								
40.10	<p>Power line, 2 strands, bears N. 43° E. and S. 43° W.</p>								
79.97	<p>The cor. of secs. 11, 12, 13 and 14.</p> <hr/>								

Survey of the Subdivisional Lines,
T. 40 N., R. 25 E., Gila and Salt River Meridian, Arizona

CHAINS							
	N. 0°01' W., bet. secs. 11 and 12. Over moderately rolling, sandy terrain and sandstone bedrock, through black brush, oak brush, sage, Mormon tea, rabbit brush and Yucca.						
24.37	Underground water line, bears S. 54° E. and N. 54° W.						
38.12	BIA road No. 5054, graded road, 25 ft. wide, bears S. 89° E. and N. 85° W.						
39.99	Point for the 1/4 sec. cor. of secs. 11 and 12. Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd. <div style="text-align: center;"> <table style="margin: auto;"> <tr><td>T 40 N</td><td>R 25 E</td></tr> <tr><td>1/4</td><td></td></tr> <tr><td>S 11</td><td> S 12</td></tr> </table> <p>2017</p> </div> Deposit a magnet, in a white plastic case, at the base of the stainless steel post. Set a steel fence post nearby.	T 40 N	R 25 E	1/4		S 11	S 12
T 40 N	R 25 E						
1/4							
S 11	S 12						
79.98	Point for the cor. of secs. 1, 2, 11 and 12. Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd. <div style="text-align: center;"> <table style="margin: auto;"> <tr><td>T 40 N</td><td>R 25 E</td></tr> <tr><td>S 2</td><td> S 1</td></tr> <tr><td>S 11</td><td> S 12</td></tr> </table> <p>2017</p> </div> Deposit a magnet, in a white plastic case, at the base of the stainless steel post. Set a steel fence post nearby. <hr/> From the cor. of secs. 1, 6, 7 and 12, on the E. bdy. of the Tp., hereinbefore described. West, bet. secs. 1 and 12. Over moderately rolling, sandstone terrain, through Mormon tea, natural grasses and rabbit brush.	T 40 N	R 25 E	S 2	S 1	S 11	S 12
T 40 N	R 25 E						
S 2	S 1						
S 11	S 12						

Survey of the Subdivisional Lines,
T. 40 N., R. 25 E., Gila and Salt River Meridian, Arizona

CHAINS	
39.99	<p>Point for the 1/4 sec. cor. of secs. 1 and 12.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, in a collar of stone, with brass cap mkd.</p> <p style="text-align: center;">T 40 N R 25 E S 1 1/4 ——— S 12</p> <p style="text-align: center;">2017</p> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p> <p>Set a steel fence post nearby.</p>
79.97	<p>The cor. of secs. 1, 2, 11 and 12.</p> <hr/> <p>N. 0°01' W., bet. secs. 1 and 2.</p> <p>Over gently rolling, sandy terrain, through, sage brush, Mormon tea, rabbit brush and natural grasses.</p>
7.80	<p>Intersect the E. right-of-way fence of U.S. Highway No. 191, parallels the highway.</p>
19.23	<p>U.S. Highway No. 191, asphalt surfaced, 27 ft. wide, bears N. 8° E. and S. 8° W.</p>
30.40	<p>Intersect the W. right-of-way fence of U.S. Highway No. 191, parallels the highway.</p>
39.99	<p>Point for the 1/4 sec. cor. of secs. 1 and 2.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T 40 N R 25 E 1/4 S 2 S 1</p> <p style="text-align: center;">2017</p> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p> <p>Set a steel fence post nearby.</p>
67.02	<p>Point for the closing cor. of secs. 1 and 2, at intersection with the Tenth Standard Parallel North, on the N. bdy. of the Tp.</p>

Survey of the Subdivisional Lines,
T. 40 N., R. 25 E., Gila and Salt River Meridian, Arizona

CHAINS

Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.

T 41 N R 25 E
S 36

S 2 | S 1
T 40 N R 25 E
CC

2017

Deposit a magnet, in a white plastic case, at the base of the stainless steel post.

Set a steel fence post nearby.

From this cor. point an iron pipe, 2 1/2 ins. diam., firmly set, projecting 12 ins. above ground, filled with cement, bears S. 86°58' E., 74.8 ft. dist., mkd. T41N R25E 2 1 T40N.

From this same cor. point, the Standard 1/4 sec. cor. of sec. 36, T. 41 N., R. 25 E., bears East, 37.30 chs. dist., monumented with a stainless steel post, 2 1/2 ins. diam., firmly set, projecting 2 ins. above ground, with brass cap mkd. SC T41N R25E 1/4 S36 2000. Add the marks 2017 to the brass cap.

From this same cor. point, the Standard sec. cor. of sec. 35, T. 41 N., R. 25 E., bears West, 2.70 chs. dist., monumented with a brass cap tablet, 3 1/2 ins. diam., firmly cemented in exposed sandstone, mkd. SC T41N R25E S35 S36 2000. Add the marks 2017 to the brass cap tablet. Raise a mound of stone W. of the cor., 3 ft. base, 2 ft. high.

Point for the 1/4 sec. cor. of sec. 1 only, at midpoint on the N. bdy. of sec. 1, on the Tenth Standard Parallel North.

Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.

T 41 N R 25 E
S 36

1/4 S 1
T 40 N R 25 E

2017

Deposit a magnet, in a white plastic case, at the base of the stainless steel post.

Set a steel fence post nearby.

Survey of the Subdivisional Lines,
T. 40 N., R. 25 E., Gila and Salt River Meridian, Arizona

CHAINS	
	<p>From this cor. point, the Standard Tp. cor. of Tps. 41 N., Rs. 25 and 26 E., bears East, 37.315 chs. dist., hereinbefore described.</p> <p>From this same cor. point, the Standard 1/4 sec. cor. of sec. 36, T. 41 N., R. 25 E., bears West, 2.685 chs. dist.</p> <hr/> <p>From the cor. of secs. 34 and 35 on the S. bdy. of the Tp., hereinbefore described.</p> <p>N. 0°01' W., bet. secs. 34 and 35.</p> <p>Over nearly flat terrain.</p>
32.64	Intersect the W. right-of-way fence of U.S. Highway No. 191, parallels the highway.
39.99	<p>Point for the 1/4 sec. cor. of secs. 34 and 35.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center;"> <p>T 40 N R 25 E</p> <p>1/4</p> <p>S 34 S 35</p> <p>2017</p> </div> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p> <p>Set a steel fence post nearby.</p> <p>from which</p> <p style="padding-left: 40px;">A stainless steel post, 28 ins. long, 2 1/2 ins. diam., set 24 ins. in the ground for a reference monument, bears S. 56°0' E., 76 ft. dist. with brass cap mkd. RM T40N R25E 76.0FT TO COR. S35 and an arrow pointing to the cor. Deposit a magnet, in a white plastic case, at the base of the stainless steel post. Set a steel fence post nearby.</p> <p style="padding-left: 40px;">A stainless steel post, 28 ins. long, 2 1/2 ins. diam., set 24 ins. in the ground for a reference monument, bears S. 56°0' E., 76 ft. dist. with brass cap mkd. with brass cap mkd. RM T40NR25E 154.0 FT TO COR. S34 and an arrow pointing to the cor. Set a steel fence post nearby.</p>
44.04	<p>From this cor., the easterly edge of U.S. Highway No. 191, bears West, 21.4 ft. dist., 30 ft. wide, bears N. 8° E. and S. 8° W.</p> <p>U.S. Highway No. 191, asphalt surfaced, 30 ft. wide, bears N. 8° E. and S. 8° W.</p>

Survey of the Subdivisional Lines,
T. 40 N., R. 25 E., Gila and Salt River Meridian, Arizona

CHAINS									
55.28	Intersect the E. right-of-way fence of U.S. Highway No. 191, parallels the highway.								
66.28	Power line, 4 strands, bears N. 8° E. and S. 8° W.								
79.98	Point for the cor. of secs. 26, 27, 34 and 35. Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd. <div style="text-align: center;"> <table style="margin: auto;"> <tr><td>T 40 N</td><td>R 25 E</td></tr> <tr><td>S 27</td><td>S 26</td></tr> <tr><td>S 34</td><td>S 35</td></tr> </table> <p>2017</p> </div> Deposit a magnet, in a white plastic case, at the base of the stainless steel post. Set a steel fence post nearby. <hr style="width: 50%; margin-left: 0;"/> From the cor. of secs. 26, 27, 34 and 35. West. bet. secs. 26 and 35. Over slightly rolling, sandy terrain, with blow sand and sandstone rock outcrops.	T 40 N	R 25 E	S 27	S 26	S 34	S 35		
T 40 N	R 25 E								
S 27	S 26								
S 34	S 35								
39.99	Point for the 1/4 sec. cor. of secs. 26 and 35. Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd. <div style="text-align: center;"> <table style="margin: auto;"> <tr><td>T 40 N</td><td>R 25 E</td></tr> <tr><td></td><td>S 26</td></tr> <tr><td>1/4</td><td>_____</td></tr> <tr><td></td><td>S 35</td></tr> </table> <p>2017</p> </div> Deposit a magnet, in a white plastic case, at the base of the stainless steel post. Set a steel fence post nearby.	T 40 N	R 25 E		S 26	1/4	_____		S 35
T 40 N	R 25 E								
	S 26								
1/4	_____								
	S 35								
72.83	Intersect the E. right-of-way fence of U.S. Highway No. 191, parallels the highway.								
74.43	U.S. Highway No. 191, asphalt surfaced, 30 ft. wide, bears N. 13° E. and S. 11° W.								

Survey of the Subdivisional Lines,
T. 40 N., R. 25 E., Gila and Salt River Meridian, Arizona

CHAINS	
76.00	Intersect the W. right-of-way fence of U.S. Highway No. 191, parallels the highway.
77.60	Power line, 4 strands, bears N. 14° E. and S. 14° W.
79.98	The cor. of secs. 26, 27, 34 and 35.

	N. 0°01' W., bet. secs. 26 and 27.
	Over moderately rolling, sandy terrain.
16.47	BIA road No. 5023, graded road, 45 ft. wide, bears S. 75° E. and N. 70° W.
39.99	Point for the 1/4 sec. cor. of secs. 26 and 27.
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 22 ins. in the ground, with brass cap mkd.
	T 40 N R 25 E 1/4 S 27 S 26
	2017
	Deposit a magnet, in a white plastic case, at the base of the stainless steel post.
	Set a steel fence post nearby.
79.98	Point for the cor. of secs. 22, 23, 26 and 27.
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.
	T 40 N R 25 E S 22 S 23 S 27 S 26
	2017
	Deposit a magnet, in a white plastic case, at the base of the stainless steel post.
	Set a steel fence post nearby.
	From this cor. point an iron pipe, 2 1/2 ins. diam., firmly set, projecting 21 1/2 ins. above ground, with concrete base, bears S. 53°38' E., 94.9 ft. dist. mkd. T40N R25E 22 23 27 26.

Survey of the Subdivisional Lines,
T. 40 N., R. 25 E., Gila and Salt River Meridian, Arizona

CHAINS	
	<p>From this same cor. point a galvanized pipe, 1 1/2 ins. diam., firmly set, projecting 8 ins. above ground, with collar of stone 3 1/2 ft. base, bears S. 56°13' E., 13.1 ft. dist., mkd. 36-109-3-B1.</p> <hr/> <p>From the cor. of secs. 23, 24, 25 and 26.</p> <p>West, bet. secs. 23 and 26.</p> <p>Over slightly rolling, sandy terrain, through sage, Mormon tea, Yucca, black brush and rabbit brush.</p>
39.99	<p>Point for the 1/4 sec. cor. of secs. 23 and 26.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T 40 N R 25 E S 23 1/4 ——— S 26</p> <p style="text-align: center;">2017</p> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p> <p>Set a steel fence post nearby.</p>
53.17	Intersect the E. right-of-way fence of U.S. Highway No. 191, parallels the highway.
54.73	U.S. Highway No. 191, asphalt surfaced, 27 ft. wide, bears N. 14° E. and S. 14° W.
56.26	Intersect the W. right-of-way fence of U.S. Highway No. 191, parallel the highway.
57.86	Power line, 4 strands, bears N. 14° E. and S. 14° W.
79.98	The cor. of secs. 22, 23, 26 and 27.
	<hr/> <p>N. 0°01' W., bet. secs. 22 and 23.</p> <p>Over rolling, sand hill terrain, through Mormon tea, natural grasses and rabbit brush.</p>
32.92	Power line, 2 strands bears N. 14° E. and S. 14° W.
39.99	Point for the 1/4 sec. cor. of secs. 22 and 23.

Survey of the Subdivisional Lines,
T. 40 N., R. 25 E., Gila and Salt River Meridian, Arizona

CHAINS	
	<p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T 40 N R 25 E 1/4 S 22 S 23</p> <p style="text-align: center;">2017</p> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p> <p>Set a steel fence post nearby.</p>
79.98	<p>Point for the cor. of secs. 14, 15, 22 and 23.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 21 ins. in the ground, in a collar of stone, with brass cap mkd.</p> <p style="text-align: center;">T 40 N R 25 E S 15 S 14 S 22 S 23</p> <p style="text-align: center;">2017</p> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p> <p>Set a steel fence post nearby.</p> <p>From this cor., an iron pipe, 2 1/2 ins. diam., firmly set in sandstone bedrock, projecting 16 ins. above ground, filled with concrete, bears S. 53°28' E., 98.6 ft. dist., mkd. T40N R25E 15 14 22 23.</p> <hr/> <p>From the cor. of secs. 13, 14, 23 and 24.</p> <p>West, bet. secs. 14 and 23.</p> <p>Over gently rolling, sandy terrain, through sage brush, Mormon tea, Yucca and rabbit brush.</p>
33.39	<p>Intersect the E. right-of-way fence of U.S. Highway No. 191, parallels the highway.</p>
34.96	<p>U.S. Highway No. 191, asphalt surfaced, 27 ft. wide, bears N. 14° E. and S. 14° W.</p>
36.53	<p>Intersect the W. right-of-way fence of U.S. Highway No. 191, parallels the highway.</p>
37.15	<p>Power line, 2 strands, bears N. 14° E. and S. 14° W.</p>

Survey of the Subdivisional Lines,
T. 40 N., R. 25 E., Gila and Salt River Meridian, Arizona

CHAINS	
38.10	Power line, 4 strands, bears N. 14° E. and S. 14° W.
39.99	<p>Point for the 1/4 sec. cor. of secs. 14 and 23.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T 40 N R 25 E S 14 1/4 ——— S 23</p> <p style="text-align: center;">2017</p> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p> <p>Set a steel fence post nearby.</p> <p>From this cor. point, a water tank, approximately 8 ft. dia., 6 ft. high, bears N. 51°19' E., 19.82 chs. dist., with a windmill nearby.</p> <p>From this same cor. point, a water tank, approximately 25 ft. dia., 7 1/2 ft. high, bears N. 51°38' E., 20.12 chs. dist.</p>
79.98	<p>The cor. of secs. 14, 15, 22 and 23.</p> <hr/> <p>N. 0°01' W., bet. secs. 14 and 15.</p> <p>Over slightly rolling, sandy terrain, with sandstone outcroppings, through Mormon tea, black brush and sage brush.</p>
39.99	<p>Point for the 1/4 sec. cor. of secs. 14 and 15.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T 40 N R 25 E 1/4 S 15 S 14</p> <p style="text-align: center;">2017</p> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p> <p>Set a steel fence post nearby.</p>
79.98	<p>Point for the cor. of secs. 10, 11, 14 and 15.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p>

Survey of the Subdivisional Lines,
T. 40 N., R. 25 E., Gila and Salt River Meridian, Arizona

CHAINS	T 40 N R 25 E S 10 S 11 S 15 S 14 2017
	<p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p> <p>Set a steel fence post nearby.</p> <hr/> <p>From the cor. of secs. 11, 12, 13 and 14.</p> <p>West, bet. secs. 11 and 14.</p> <p>Over slightly rolling to nearly flat, sandy terrain, with sandstone outcroppings, through sage and Mormon tea.</p>
13.66	Intersect the E. right-of-way fence of U.S. Highway No. 191, parallel the highway.
15.22	U.S. Highway No. 191, asphalt surfaced, 27 ft. wide, bears N. 14° E. and S. 14° W.
16.77	Intersect the W. right-of-way fence of U.S. Highway No. 191, parallel the highway.
23.75	Power line, 2 strands, bears N. 14° E. and S. 14° W.
24.92	Power line, 4 strands, bears N. 14° E. and S. 14° W.
39.99	Point for the 1/4 sec. cor. of secs. 11 and 14.
	<p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 25 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T 40 N R 25 E S 11 1/4 ——— S 14 2017</p> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p> <p>Set a steel fence post nearby.</p>
79.98	The cor. of secs. 10, 11, 14 and 15.
	<hr/> <p>N. 0°01' W., bet. secs. 10 and 11.</p>

Survey of the Subdivisional Lines,
T. 40 N., R. 25 E., Gila and Salt River Meridian, Arizona

CHAINS	
	Over slightly rolling to nearly flat, sandy terrain, with sandstone outcroppings, through black brush, oak brush and Mormon tea.
7.34	BIA road No. 5052, graded road, 25 ft. wide, bears N. 76° E. and S. 76° W.
39.99	Point for the 1/4 sec. cor. of secs. 10 and 11. Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd. <div style="text-align: center;"> T 40 N R 25 E 1/4 S 10 S 11 2017 </div> Deposit a magnet, in a white plastic case, at the base of the stainless steel post. Set a steel fence post nearby.
79.98	Point for the cor. of secs. 2, 3, 10 and 11. Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 21 ins. in the ground, with brass cap mkd. <div style="text-align: center;"> T 40 N R 25 E S 3 S 2 --- S 10 S 11 2017 </div> Deposit a magnet, in a white plastic case, at the base of the stainless steel post. Set a steel fence post nearby. <hr/> From the cor. of secs. 1, 2, 11 and 12. West, bet. secs. 2 and 11. Over a gentle, sandy W. slope.
1.05	Intersect the E. right-of-way fence of U.S. Highway No. 191, parallel the highway.
2.60	U.S. Highway No. 191, asphalt surfaced, 27 ft. wide, bears N. 8° E. and S. 8° W.
4.14	Intersect the W. right-of-way fence of U.S. Highway No. 191, parallel the highway.

Survey of the Subdivisional Lines,
T. 40 N., R. 25 E., Gila and Salt River Meridian, Arizona

CHAINS	
17.90	Power line, 2 strands, bears N. 8° E. and S. 8° W.
23.12	Power line, 4 strands, bears N. 2° E. and S. 2° W.
39.99	Point for the 1/4 sec. cor. of secs. 2 and 11. Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd. <div style="text-align: center;"> T 40 N R 25 E S 2 1/4 ——— S 11 2017 </div> Deposit a magnet, in a white plastic case, at the base of the stainless steel post. Set a steel fence post nearby.
79.98	The cor. of secs. 2, 3, 10 and 11. <hr/> N. 0°01' W., bet. secs. 2 and 3. Over moderately rolling sandstone terrain.
39.99	Point for the 1/4 sec. cor. of secs. 2 and 3. Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 23 ins. in the ground, with brass cap mkd. <div style="text-align: center;"> T 40 N R 25 E 1/4 S 3 S 2 2017 </div> Deposit a magnet, in a white plastic case, at the base of the stainless steel post. Set a steel fence post nearby.
67.02	Point for the closing cor. of secs. 2 and 3, at intersection with the Tenth Standard Parallel North, on the N. bdy. of the Tp. Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 17 ins. in the ground, with brass cap mkd.

Survey of the Subdivisional Lines,
T. 40 N., R. 25 E., Gila and Salt River Meridian, Arizona

CHAINS

T 41 N R 25 E
S 35

S 3 | S 2
T 40 N R 25 E
CC

2017

Deposit a magnet, in a white plastic case, at the base of the stainless steel post.

Set a steel fence post nearby.

From this cor. point, an iron pipe, 2 1/2 ins. diam., firmly set, cemented in sandstone, projecting 23 ins. above ground, bears N. 86°21' W., 82.6 ft. dist., iron pipe mkd. T41N R25E 2 1 T40N.

From this same cor. point, the Standard 1/4 sec. cor. of sec. 35, Tp. 41 N., R. 25 E., bears East, 37.27 chs. dist., monumented with a brass tablet, 3 1/2 ins. diam., firmly set, cemented flush, in exposed sandstone, mkd. SC T41N R25E 1/4 S35 2000. Add the marks 2017 to the brass cap.

From this same cor. point, the Standard cor. of secs. 34 and 35, Tp. 41 N., R. 25 E., bears West, 2.73 chs. dist., monumented with a brass tablet, 3 1/2 ins. diam., firmly set, cemented flush, exposed in sandstone, mkd. SC T41N R25E S34 S35 2000. Add the marks 2017 to the brass cap.

Point for the 1/4 sec. cor. of sec. 2 only, at midpoint on the N. bdy. of sec. 2, on the Tenth Standard Parallel North.

Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 21 ins. in the ground, with brass cap mkd.

T 41 N R 25 E
S 35

1/4 S 2
T 40 N R 25 E

2017

Deposit a magnet, in a white plastic case, at the base of the stainless steel post.

Set a steel fence post nearby.

From this cor. point, the Standard sec. cor. of secs. 35 and 36, T. 41 N., R. 25 E., bears East, 37.285 chs. dist.

Survey of the Subdivisional Lines,
T. 40 N., R. 25 E., Gila and Salt River Meridian, Arizona

CHAINS							
	<p>From this same cor. point, the Standard 1/4 sec. cor. of sec. 35, T. 41 N., R. 25 E., bears West, 2.715 chs. dist.</p> <hr/> <p>From the cor. of secs. 33 and 34 on the S. bdy. of Tp. hereinbefore described.</p> <p>N. 0°02' W., bet. secs. 33 and 34.</p> <p>Over gently rolling, sandy terrain.</p>						
39.99	<p>Point for the 1/4 sec. cor. of secs. 33 and 34.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center;"> <table style="margin: auto;"> <tr><td>T 40 N</td><td>R 25 E</td></tr> <tr><td>1/4</td><td></td></tr> <tr><td>S 33</td><td> S 34</td></tr> </table> <p>2017</p> </div> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p> <p>Set a steel fence post nearby.</p>	T 40 N	R 25 E	1/4		S 33	S 34
T 40 N	R 25 E						
1/4							
S 33	S 34						
43.84	<p>BIA road No. 5057, graded road, 45 ft. wide, bears N. 53° E. and S. 54° W.</p>						
79.98	<p>Point for the cor. of secs. 27, 28, 33 and 34.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center;"> <table style="margin: auto;"> <tr><td>T 40 N</td><td>R 25 E</td></tr> <tr><td>S 28</td><td> S 27</td></tr> <tr><td>S 33</td><td> S 34</td></tr> </table> <p>2017</p> </div> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p> <p>Set a steel fence post nearby.</p> <hr/> <p>From the cor. of secs. 26, 27, 34 and 35.</p> <p>West, bet. secs. 27 and 34.</p> <p>Over gently rolling, sandy terrain.</p>	T 40 N	R 25 E	S 28	S 27	S 33	S 34
T 40 N	R 25 E						
S 28	S 27						
S 33	S 34						

Survey of the Subdivisional Lines,
T. 40 N., R. 25 E., Gila and Salt River Meridian, Arizona

CHAINS	
32.11	BIA road No. 5057, graded road, 45 ft. wide, bears N. 52° E. and S. 52° W.
39.99	Point for the 1/4 sec. cor. of secs. 27 and 34. Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd. <div style="text-align: center;"> T 40 N R 25 E S 27 1/4 ——— S 34 2017 </div> Deposit a magnet, in a white plastic case, at the base of the stainless steel post. Set a steel fence post nearby.
79.98	The cor. of secs. 27, 28, 33 and 34. <hr/> N. 0°02' W., bet. secs. 27 and 28. Over gently rolling, sandy terrain.
11.95	BIA road No. 5023, graded road, 45 ft. wide, bears N. 84° E. and S. 84° W.
39.99	Point for the 1/4 sec. cor. of secs. 28 and 27. Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd. <div style="text-align: center;"> T 40 N R 25 E 1/4 S 28 S 27 2017 </div> Deposit a magnet, in a white plastic case, at the base of the stainless steel post. Set a steel fence post nearby.
52.61	Power line, 2 strands, bears N. 53° E. and S. 53° W.
79.98	Point for the cor. of secs. 21, 22, 27 and 28. Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.

Survey of the Subdivisional Lines,
T. 40 N., R. 25 E., Gila and Salt River Meridian, Arizona

CHAINS	T 40 N R 25 E S 21 S 22 S 28 S 27
	2017
	Deposit a magnet, in a white plastic case, at the base of the stainless steel post.
	Set a steel fence post nearby.
	<hr/>
	From the cor. secs. of 22, 23, 26 and 27.
	West, bet. secs. 22 and 27.
	Over slightly rolling, sandy terrain, through Mormon tea, Yucca, black brush and rabbit brush.
21.10	Power line, 2 strands, bears S. 35° E. and N. 35° W.
39.99	Point for the 1/4 sec. cor. of secs. 22 and 27.
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.
	T 40 N R 25 E S 22 1/4 ——— S 27
	2017
	Deposit a magnet, in a white plastic case, at the base of the stainless steel post.
	Set a steel fence post nearby.
43.68	Power line, 2 strands, bears N. 53° E. and S. 53° W.
79.98	The cor. of secs. 21, 22, 27 and 28.
	<hr/>
	N. 0°02' W., bet. secs. 21 and 22.
39.99	Point for the 1/4 sec. cor. of secs. 21 and 22.
	Over rolling sandstone hills.
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.

Survey of the Subdivisional Lines,
T. 40 N., R. 25 E., Gila and Salt River Meridian, Arizona

CHAINS	
	T 40 N R 25 E 1/4 S 21 S 22 2017
	Deposit a magnet, in a white plastic case, at the base of the stainless steel post. Set a steel fence post nearby. from which A cotton spindle, 4 3/4 ins. long, 1/2 ins. diam., set flush in sandstone crevice, for a reference monument, bears N. 62°24' W., 64.2 ft. dist. Cor. falls on a NE facing sandstone slope, 20 ft. high, bears N. 10 E. and S. 10 W.
79.98	Point for the cor. of secs. 15, 16, 21 and 22. Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd. <div style="text-align: center;"> T 40 N R 25 E S 16 S 15 S 21 S 22 2017 </div> Deposit a magnet, in a white plastic case, at the base of the stainless steel post. Set a steel fence post nearby. <hr/> From the cor. secs. of 14, 15, 22 and 23. West, bet. secs. 15 and 22. Over gently rolling, sandy terrain, through scattered brush.
39.99	Point for the 1/4 sec. cor. of secs. 15 and 22. Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 23 ins. in the ground, with brass cap mkd.

Survey of the Subdivisional Lines,
T. 40 N., R. 25 E., Gila and Salt River Meridian, Arizona

CHAINS	
	T 40 N R 25 E S 15 1/4 ——— S 22 2017
	Deposit a magnet, in a white plastic case, at the base of the stainless steel post. Set a steel fence post nearby. From this cor. point, a two track road bears N. 23° E., 1.03 chs. dist., 10 ft. wide, bears S. 68° E. and N. 68° W
79.98	The cor. of secs. 15, 16, 27 and 28. <hr/> N. 0°02' W., bet. secs. 15 and 16. Over gently rolling, sandy terrain.
39.99	Point for the 1/4 sec. cor. of secs. 15 and 16. Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.
	T 40 N R 25 E 1/4 S 16 S 15 2017
	Deposit a magnet, in a white plastic case, at the base of the stainless steel post. Set a steel fence post nearby. From this cor. point, an iron pipe water well casing, 6 ins. diam., projecting 36 ins. above ground, inside a barbed wire fence enclosure, powered by a solar panel, bears S. 87°19' E., 34.84 chs. dist.
79.98	Point for the cor. of secs. 9, 10, 15 and 16. Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 23 ins. in the ground, with brass cap mkd.
	T 40 N R 25 E S 9 S 10 S 16 S 15 2017

Survey of the Subdivisional Lines,
T. 40 N., R. 25 E., Gila and Salt River Meridian, Arizona

CHAINS	
	<p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p> <p>Set a steel fence post nearby.</p> <p>From this cor. point, an iron pipe, 2 1/2 ins. diam., firmly set, projecting 15 ins. above ground, filled with cement, bears N. 55°12' W., 100.9 ft. dist., iron pipe mkd. T40N R25E 9 10 16 15.</p> <hr/> <p>From the cor. secs. of 10, 11, 14 and 16.</p> <p>West, bet. secs. 10 and 15.</p> <p>Over slightly rolling, sandy and sandstone terrain.</p>
30.19	BIA road No. 5052, graded road, 25 ft. wide, bears N. 77° E. and S. 76° W.
39.99	<p>Point for the 1/4 sec. cor. of secs. 10 and 15.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center;"> <p>T 40 N R 25 E</p> <p>S 10</p> <p>1/4 ———</p> <p>S 15</p> <p>2017</p> </div>
	<p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p> <p>Set a steel fence post nearby.</p>
67.61	BIA road No. 5052 ,graded road, 25 ft. wide, bears S. 49° E. and N. 49° W.
79.98	The cor. of secs. 9, 10, 15 and 16.
	<hr/> <p>N. 0°02' W., bet. secs. 9 and 10.</p> <p>Over gently rolling sandstone terrain.</p>
10.91	BIA road No. 5052, graded road, 25 ft. wide, bears S. 49° E. and N. 49° W.
39.99	<p>Point for the 1/4 sec. cor. of secs. 9 and 10.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 28 ins. in the ground, with brass cap mkd.</p>

Survey of the Subdivisional Lines,
T. 40 N., R. 25 E., Gila and Salt River Meridian, Arizona

CHAINS	
	T 40 N R 25 E 1/4 S 9 S 10 2017
	Deposit a magnet, in a white plastic case, at the base of the stainless steel post. Set a steel fence post nearby.
79.98	Point for the cor. of secs. 3, 4, 9 and 10. Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 16 ins. in the ground, in a mound of stone, 3 ft. base, to top, with brass cap mkd.
	T 40 N R 25 E S 4 S 3 S 9 S 10 2017
	Deposit a magnet, in a white plastic case, at the base of the stainless steel post. Set a steel fence post nearby.
	<hr/> From the cor. secs. of 2, 3, 10 and 11. West, bet. secs. 3 and 10. Over a gently rolling, sandy terrain, along a descending northerly slope, through black bush, Mormon tea and sage brush.
39.99	Point for the 1/4 sec. cor. of secs. 3 and 10. Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.
	T 40 N R 25 E S 3 1/4 ——— S 10 2017
	Deposit a magnet, in a white plastic case, at the base of the stainless steel post. Set a steel fence post nearby.

Survey of the Subdivisional Lines,
T. 40 N., R. 25 E., Gila and Salt River Meridian, Arizona

CHAINS	
79.98	<p>The cor. of secs. 3, 4, 9 and 10.</p> <hr/> <p>N. 0°02' W., bet. secs. 3 and 4.</p> <p>Over gently rolling sandstone terrain.</p>
39.99	<p>Point for the 1/4 sec. cor. of secs. 3 and 4.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T 40 N R 25 E 1/4 S 4 S 3 2017</p> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p> <p>Set a steel fence post nearby.</p>
67.02	<p>Point for the closing cor. of secs. 3 and 4, at intersection with the Tenth Standard Parallel North, on the N. bdy. of the Tp.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, in a collar of stone, with brass cap mkd.</p> <p style="text-align: center;">T 41 N R 25 E S 34 <hr/>S 4 S 3 T 40 N R 25 E CC 2017</p> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p> <p>Set a steel fence post nearby.</p> <p>Over a gently rolling sand terrain.</p> <p>From this cor. point, the Standard 1/4 sec. cor. of sec. 34, T. 41 N., R 25 E., bears East, 37.25 chs. dist., monumented with a stainless steel post, 2 1/2 ins. diam., firmly set, projecting 1 in. above ground, with brass cap mkd. SC T41N R25E 1/4 S34 2000. Add the marks 2017 to the brass cap.</p>

Survey of the Subdivisional Lines,
T. 40 N., R. 25 E., Gila and Salt River Meridian, Arizona

CHAINS	
	<p>From this same cor. point, the Standard cor. of secs. 33 and 34, T. 41 N., R. 25 E., bears West., 2.75 chs. dist., monumented with a stainless steel post, 2 1/2 ins. diam., firmly set, projecting 2 ins. above ground, with brass cap mkd. SC T41N R25E S33 S34 2000. Add the marks 2017 to the brass cap.</p> <hr/> <p>Point for the 1/4 sec. cor. of sec. 3 only, at midpoint on the N. bdy. of sec. 3, on the Tenth Standard Parallel North.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 20 ins. in the ground, in a mound of stone, 2 1/2 ft. base, to top, with brass cap mkd.</p> <p style="text-align: center;">T 41 N R 25 E S 34</p> <hr style="width: 20%; margin: auto;"/> <p style="text-align: center;">1/4 S 3 T 40 N R 25 E</p> <p style="text-align: center;">2017</p> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p> <p>Set a steel fence post nearby.</p> <p>From this cor. point, the Standard sec. cor. of secs. 34 and 35, T. 41 N., R. 25 E., bears East, 37.26 chs. dist.</p> <p>From this same cor. point, the Standard 1/4 sec. cor. of sec. 34, T. 41 N., R. 25 E., bears West, 2.74 chs. dist.</p> <hr/> <p>From the cor. of secs. 32 and 33 on the S. bdy. of Tp. hereinbefore described.</p> <p>N. 0°03' W., bet. secs. 32 and 33.</p> <p>Over rolling sandstone terrain.</p>
6.27	Underground water line, bears N. 21° E. and N. 21° E.
39.99	<p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 22 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T 40 N R 25 E 1/4 S 32 S 33</p> <p style="text-align: center;">2017</p> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p>

Survey of the Subdivisional Lines,
T. 40 N., R. 25 E., Gila and Salt River Meridian, Arizona

CHAINS																	
	Set a steel fence post nearby.																
67.49	BIA road No. 5023, graded road, 45 ft. wide, bears S. 85° E. and N. 75° W.																
74.94	Power line, 2 strands, bears N. 55° E. and S. 55° W.																
79.98	Point for the cor. of secs. 28, 29, 30 and 31.																
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 21 ins. in the ground, with brass cap mkd.																
	<table style="margin-left: auto; margin-right: auto;"> <tr> <td colspan="2">T 40 N</td> <td colspan="2">R 25 E</td> </tr> <tr> <td style="border-right: 1px solid black;">S 29</td> <td style="border-right: 1px solid black;"></td> <td style="border-right: 1px solid black;">S 28</td> <td></td> </tr> <tr> <td style="border-right: 1px solid black;">S 32</td> <td style="border-right: 1px solid black;"></td> <td style="border-right: 1px solid black;">S 33</td> <td></td> </tr> </table>	T 40 N		R 25 E		S 29		S 28		S 32		S 33					
T 40 N		R 25 E															
S 29		S 28															
S 32		S 33															
	2017																
	Deposit a magnet, in a white plastic case, at the base of the stainless steel post.																
	Set a steel fence post nearby.																
	<hr/>																
	From the cor. secs. of 27, 28, 33 and 34.																
	West, bet. secs. 28 and 33.																
	Over moderately rolling, sandy terrain.																
30.18	BIA road No. 5053, graded road, 45 ft. wide, bears N. 59° E. and S. 53° W.																
39.99	Point for the 1/4 sec. cor. of secs. 28 and 33.																
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.																
	<table style="margin-left: auto; margin-right: auto;"> <tr> <td colspan="2">T 40 N</td> <td colspan="2">R 25 E</td> </tr> <tr> <td colspan="2"></td> <td colspan="2">S 28</td> </tr> <tr> <td colspan="2"></td> <td colspan="2">1/4 ———</td> </tr> <tr> <td colspan="2"></td> <td colspan="2">S 33</td> </tr> </table>	T 40 N		R 25 E				S 28				1/4 ———				S 33	
T 40 N		R 25 E															
		S 28															
		1/4 ———															
		S 33															
	2017																
	Deposit a magnet, in a white plastic case, at the base of the stainless steel post.																
	Set a steel fence post nearby.																
42.14	Power line, 2 strands, bears S. 25° E. and N. 25° W.																
72.84	Power line, 2 strands, bears N. 55° E. and S. 55° W.																

Survey of the Subdivisional Lines,
T. 40 N., R. 25 E., Gila and Salt River Meridian, Arizona

CHAINS	
79.98	<p>The cor. of secs. 28, 29, 32 and 33.</p> <hr/> <p>N. 0°03' W., bet. secs. 29 and 28.</p> <p>Over slightly rolling, sandy terrain.</p>
39.99	<p>Point for the 1/4 sec. cor. of secs. 28 and 29.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center;"> <p>T 40 N R 25 E</p> <p>1/4</p> <p>S 29 S 28</p> <p>2017</p> </div> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p> <p>Set a steel fence post nearby.</p>
79.98	<p>Point for the cor. of secs. 20, 21, 28 and 29.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center;"> <p>T 40 N R 25 E</p> <p>S 20 S 21</p> <hr style="width: 50%; margin: 0 auto;"/> <p>S 29 S 28</p> <p>2017</p> </div> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p> <p>Set a steel fence post nearby.</p> <hr/> <p>From the cor. secs. of 21, 22, 27 and 28.</p> <p>West, bet. secs. 21 and 28</p> <p>Over gently rolling, sandstone terrain</p>
39.99	<p>Point for the 1/4 sec. cor. of secs. 21 and 28.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 23 ins. in the ground, with brass cap mkd.</p>

Survey of the Subdivisional Lines,
T. 40 N., R. 25 E., Gila and Salt River Meridian, Arizona

CHAINS	
	T 40 N R 25 E S 21 1/4 ——— S 28 2017
	Deposit a magnet, in a white plastic case, at the base of the stainless steel post. Set a steel fence post nearby.
79.98	The cor. of secs. 20, 21, 28 and 29. <hr/> N. 0°03' W., bet. secs. 20 and 21. Over gently rolling, sandstone terrain.
39.99	Point for the 1/4 sec. cor. of secs. 33 and 34. Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 21 ins. in the ground, with brass cap mkd.
	T 40 N R 25 E 1/4 S 20 S 21 2017
	Deposit a magnet, in a white plastic case, at the base of the stainless steel post. Set a steel fence post nearby.
76.23	Trail road, 8 ft. wide, bears S. 35° E. and N. 60° W.
79.98	Point for the cor. of secs. 16, 17, 20 and 21. Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 25 ins. in the ground, with brass cap mkd.
	T 40 N R 25 E S 17 S 16 S 20 S 21 2017
	Deposit a magnet, in a white plastic case, at the base of the stainless steel post. Set a steel fence post nearby.

Survey of the Subdivisional Lines,
T. 40 N., R. 25 E., Gila and Salt River Meridian, Arizona

CHAINS	
	<p>From this cor. point, the intersection of trail roads, bears S. 55° W., 191 ft. dist., 8 ft. wide, bears N. 30° E., S 40° E., S. 30° W. and N. 15° W.</p> <hr/> <p>From the cor. secs. of 15, 16, 21 and 22.</p> <p>West, bet. secs. 16 and 21.</p> <p>Over slightly rolling, sandy terrain.</p>
39.99	<p>Point for the 1/4 sec. cor. of secs. 16 and 21.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T 40 N R 25 E S 16 1/4 ——— S 21</p> <p style="text-align: center;">2017</p> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p> <p>Set a steel fence post nearby.</p>
79.98	<p>The cor. of secs. 16, 17, 20 and 21.</p> <hr/> <p>N. 0°03' W., bet. secs. 16 and 17.</p> <p>Over gently rolling, sandstone terrain.</p>
2.38	<p>Trail road, 8 ft. wide, bears N. 30° E. and S. 30° W.</p>
39.99	<p>Point for the 1/4 sec. cor. of secs. 16 and 17.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 21 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T 40 N R 25 E 1/4 S 17 S 16</p> <p style="text-align: center;">2017</p> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p> <p>Set a steel fence post nearby.</p>
40.62	<p>Trail road, 8 ft. wide, bears S. 67° E. and N. 67° W.</p>

Survey of the Subdivisional Lines,
T. 40 N., R. 25 E., Gila and Salt River Meridian, Arizona

CHAINS									
79.98	<p>Point for the cor. of secs. 8, 9, 16 and 17.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 21 ins. in the ground, in a collar of stone, with brass cap mkd.</p> <div style="text-align: center;"> <table style="margin: auto;"> <tr> <td>T 40 N</td> <td>R 25 E</td> </tr> <tr> <td style="border-right: 1px solid black;">S 8</td> <td>S 9</td> </tr> <tr> <td style="border-right: 1px solid black;">S 17</td> <td>S 16</td> </tr> </table> <p>2017</p> </div> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p> <p>Set a steel fence post nearby.</p> <p>From this cor. point, an iron pipe, 2 1/2 ins. diam., firmly set, projecting 19 ins. above ground, filled with cement, bears N. 54°58' W., 103.9 ft. dist., iron pipe mkd. T40N R25E 8 9 17 16.</p> <hr/> <p>From the cor. secs. of 9, 10, 15 and 16.</p> <p>West, bet. secs. 9 and 16.</p> <p>Over gently rolling, sandy terrain, through scattered brush.</p>	T 40 N	R 25 E	S 8	S 9	S 17	S 16		
T 40 N	R 25 E								
S 8	S 9								
S 17	S 16								
39.99	<p>Point for the 1/4 sec. cor. of secs. 9 and 16.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center;"> <table style="margin: auto;"> <tr> <td>T 40 N</td> <td>R 25 E</td> </tr> <tr> <td></td> <td>S 9</td> </tr> <tr> <td></td> <td>1/4 ———</td> </tr> <tr> <td></td> <td>S 16</td> </tr> </table> <p>2017</p> </div> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p> <p>Set a steel fence post nearby.</p>	T 40 N	R 25 E		S 9		1/4 ———		S 16
T 40 N	R 25 E								
	S 9								
	1/4 ———								
	S 16								
79.97	<p>The cor. of secs. 8, 9, 16 and 17.</p> <hr/> <p>N. 0°03' W., bet. secs. 8 and 9.</p> <p>Over rolling, sand dune terrain.</p>								
19.56	<p>BIA road No. 5052, graded road, 25 ft. wide, bears N. 83° E. and S. 82° W.</p>								

Survey of the Subdivisional Lines,
T. 40 N., R. 25 E., Gila and Salt River Meridian, Arizona

CHAINS	
39.99	<p>Point for the 1/4 sec. cor. of secs. 8 and 9.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T 40 N R 25 E 1/4 S 8 S 9</p> <p style="text-align: center;">2017</p> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p> <p>Set a steel fence post nearby.</p> <p>Over rolling, sand dune terrain.</p>
79.98	<p>Point for the cor. of secs. 4, 5, 8 and 9.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T 40 N R 25 E S 5 S 4 S 8 S 9</p> <p style="text-align: center;">2017</p> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p> <p>Set a steel fence post nearby.</p> <hr/> <p>From the cor. secs. of 3, 4, 9 and 10.</p> <p>West, bet. secs. 4 and 9.</p> <p>Over slightly rolling to nearly flat, sandy terrain with sandstone outcroppings, through black brush and Mormon tea.</p>
39.99	<p>Point for the 1/4 sec. cor. of secs. 4 and 9.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 22 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T 40 N R 25 E S 4 1/4 ——— S 9</p> <p style="text-align: center;">2017</p>

Survey of the Subdivisional Lines,
T. 40 N., R. 25 E., Gila and Salt River Meridian, Arizona

CHAINS	
	<p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p> <p>Set a steel fence post nearby.</p>
79.97	<p>The cor. of secs. 4, 5, 8 and 9.</p> <hr/> <p>N. 0°03' W., bet. secs. 4 and 5.</p> <p>Over gently rolling, sandy terrain and sandstone bedrock.</p>
39.99	<p>Point for the 1/4 sec. cor. of secs. 4 and 5.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T 40 N R 25 E 1/4 S 5 S 4 2017</p> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p> <p>Set a steel fence post nearby.</p>
65.97	<p>Trail road, 8 ft. wide, bears N. 58° E. and S. 66° W.</p>
67.02	<p>Point for the closing cor. of secs. 4 and 5, at intersection with the Tenth Standard Parallel North, on the N. bdy. of the Tp.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, in a collar of stone, with brass cap mkd.</p> <p style="text-align: center;">T 41 N R 25 E S 33 ----- S 5 S 4 T 40 N R 25 E CC 2017</p> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p> <p>Set a steel fence post nearby.</p>

Survey of the Subdivisional Lines,
T. 40 N., R. 25 E., Gila and Salt River Meridian, Arizona

CHAINS

From this cor. point, the Standard 1/4 sec. cor. of sec. 33, T. 41 N., R 25 E., bears East, 37.22 chs. dist., monumented with a stainless steel post, 2 1/2 ins. diam., firmly set, projecting 3 in. above ground, with brass cap mkd. SC T41N R25E 1/4 S33 2000. Add the marks 2017 to the brass cap.

From this same cor. point, the Standard cor. of sec. 32, T. 41 N., R. 25 E., bears West., 2.78 chs. dist., monumented with a stainless steel post, 2 1/2 ins. diam., firmly set, projecting 2 ins. above ground, with brass cap mkd. SC T41N R25E S32 S33 2000. Add the marks 2017 to the brass cap.

From this cor. point, the intersection of two track roads, 8 ft. wide, bears N. 81° E., 135 ft. dist., roads extend N. 18° E., S. 66° E. and S. 48° W.

Point for the 1/4 sec. cor. of sec. 4 only, at midpoint on the N. bdy. of sec. 4, on the Tenth Standard Parallel North.

Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.

T 41 N R 25 E
S 33

1/4 S 4
T 40 N R 25 E

2017

Deposit a magnet, in a white plastic case, at the base of the stainless steel post.

Set a steel fence post nearby.

From this cor. point, the top NW cor. of a concrete pad, 6 x 6 ft., supporting a windmill, bears S. 52°54' E., 2.50 chs. dist., with a water tank, approximately 8 ft. diam., 12 ft. high., nearby.

From this cor. point, the Standard sec. cor. of secs. 33 and 34, T. 41 N., R. 25 E., bears East, 37.235 chs. dist.

From this same cor. point, the Standard 1/4 sec. cor. of sec. 33, T. 41 N., R. 25 E., bears West, 2.765 chs. dist.

From the cor. of secs. 31 and 32 on the S. bdy. of Tp., hereinbefore described.

N. 0°03' W., bet. secs. 31 and 32.

Survey of the Subdivisional Lines,
T. 40 N., R. 25 E., Gila and Salt River Meridian, Arizona

CHAINS	
	Over slightly rolling, sandstone terrain, through black brush, sage brush and Mormon tea.
20.49	Power line, 2 strands, bears S. 30° E. and N. 30° W.
21.89	Underground water line, bears S. 30° E. and N. 30° W.
27.59	BIA road No. 5057, graded road, 45 ft. wide, bears S. 46° E. and N. 39° W.
39.99	Point for the 1/4 sec. cor. of secs. 31 and 32. Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd. <div style="text-align: center;"> T 40 N R 25 E 1/4 S 31 S 32 2017 </div> Deposit a magnet, in a white plastic case, at the base of the stainless steel post. Set a steel fence post nearby.
56.57	BIA road No. 5023, graded road, 45 ft. wide, bears S. 80° E. and N. 70° W.
79.98	Point for the cor. of secs. 29, 30, 31 and 32. Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd. <div style="text-align: center;"> T 40 N R 25 E S 30 S 29 S 31 S 32 2017 </div> Deposit a magnet, in a white plastic case, at the base of the stainless steel post. Set a steel fence post nearby.
32.49	<hr/> From the cor. secs. of 28, 29, 32 and 33. West, bet. secs. 29 and 32. Over sandy terrain, across a gentle SE slope. Underground water line, bears S. 20° E. and N. 20° W.

Survey of the Subdivisional Lines,
T. 40 N., R. 25 E., Gila and Salt River Meridian, Arizona

CHAINS	
39.99	<p>Point for the 1/4 sec. cor. of secs. 29 and 32.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T 40 N R 25 E S 29 1/4 ——— S 32</p> <p style="text-align: center;">2017</p> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p> <p>Set a steel fence post nearby.</p>
79.97	<p>The cor. of secs. 29, 30, 31 and 32.</p> <hr/> <p>N. 89°59' W., bet. secs. 30 and 31.</p> <p>Over gently rolling, sandy terrain.</p>
18.79	<p>BIA road No. 5053, graded road, 25 ft. wide, bears S. 17° E. and N. 23° W.</p>
39.99	<p>Point for the 1/4 sec. cor. of secs. 30 and 31.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T 40 N R 25 E S 30 1/4 ——— S 31</p> <p style="text-align: center;">2017</p> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p> <p>Set a steel fence post nearby.</p>
80.18	<p>The cor. of secs. 25, 30, 31 and 36, on the W. bdy. of the Tp., monumented with a brass tablet, 3 1/2 ins. diam., firmly cemented in a drill hole in sandstone, mkd. T40N R24E R25E S25 S30 S36 S31 2011. Add the marks 2017 to the brass tablet. Raise a mound of stone, 3 ft. high, W. of the tablet.</p> <hr/> <p>N. 0°03' W., bet. secs. 30 and 29.</p> <p>Over slightly rolling, sandstone terrain.</p>

Survey of the Subdivisional Lines,
T. 40 N., R. 25 E., Gila and Salt River Meridian, Arizona

CHAINS	
39.99	<p>Point for the 1/4 sec. cor. of secs. 29 and 30.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 22 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T 40 N R 25 E 1/4 S 30 S 29</p> <p style="text-align: center;">2017</p> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p> <p>Set a steel fence post nearby.</p>
78.22	Trail road, 12 ft. wide, bears N. 40° E. and S. 20° W.
79.98	<p>Point for the cor. of secs. 19, 20, 29 and 30.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 21 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T 40 N R 25 E S 19 S 20 S 30 S 29</p> <p style="text-align: center;">2017</p> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p> <p>Set a steel fence post nearby.</p> <p>From this cor., a "T" intersection of trail roads, bears N. 47° W., 66.78 ft. dist., 8 ft. wide, bears N. 30° E., with dirt road, 12 ft. wide, bears, N. 40° E., S. 20° W.</p> <hr/> <p>From the cor. secs. of 16, 17, 20 and 21.</p> <p>West, bet. secs. 20 and 29.</p> <p>Over nearly flat, sandstone terrain.</p>
39.99	<p>Point for the 1/4 sec. cor. of secs. 20 and 29.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 21 ins. in the ground, with brass cap mkd.</p>

Survey of the Subdivisional Lines,
T. 40 N., R. 25 E., Gila and Salt River Meridian, Arizona

CHAINS	
	T 40 N R 25 E S 20 1/4 ——— S 29 2017
	Deposit a magnet, in a white plastic case, at the base of the stainless steel post. Set a steel fence post nearby.
78.65	Trail road, 12 ft. wide, bears N. 40° E. and S. 20° W.
79.58	Trail road, 8 ft. wide, bears S. 30° E. and N. 30° W.
79.97	The cor. of secs. 19, 20, 29 and 30.
	<hr/> N. 89°58' W., bet. secs. 19 and 30. Over moderately rolling, sandstone terrain, with loose rocky topsoil.
23.24	BIA road No. 5053, graded road, 25 ft. wide, bears N. 18° E. and S. 17° W.
39.99	Point for the 1/4 sec. cor. of secs. 19 and 30. Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 22 ins. in the ground, with brass cap mkd.
	T 40 N R 25 E S 19 1/4 ——— S 30 2017
	Deposit a magnet, in a white plastic case, at the base of the stainless steel post. Set a steel fence post nearby.
80.09	The cor. of secs. 19, 24, 25 and 30, on the W. bdy. of the Tp., monumented with a stainless steel post, 2 1/2 ins. diam., projecting 1 in. above ground, with brass cap mkd. T40N R24E R25E S24 S19 S25 S30 2011. Add the marks 2017 to the brass cap.
	<hr/> N. 0°03' W., bet. secs. 19 and 20. Over slightly rolling, sandstone terrain.

Survey of the Subdivisional Lines,
T. 40 N., R. 25 E., Gila and Salt River Meridian, Arizona

CHAINS	
0.72	Trail road, 8 ft. wide, bears S. 25° E. and N. 25° W.
39.99	<p>Point for the 1/4 sec. cor. of secs. 19 and 20.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T 40 N R 25 E 1/4 S 19 S 20</p> <p style="text-align: center;">2017</p> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p> <p>Set a steel fence post nearby.</p> <p>From this cor. point, a water tank, approximately 9 ft. diam., 13.5 ft. high, bears N. 86°47' E., 11.03 chs. dist., with a windmill, nearby.</p>
79.98	<p>Point for the cor. of secs. 17, 18, 19 and 20.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 21 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T 40 N R 25 E S 18 S 17 S 19 S 20</p> <p style="text-align: center;">2017</p> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p> <p>Set a steel fence post nearby.</p> <hr/> <p>From the cor. secs. of 16, 17, 20 and 21.</p> <p>West, bet. secs. 17 and 20.</p> <p>Over slightly rolling, sandy terrain, with sandstone outcroppings.</p>
1.33	Trail road, 8 ft. wide, bears N. 30° E. and S. 30° W.
39.99	<p>Point for the 1/4 sec. cor. of secs. 17 and 20.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 23 ins. in the ground, with brass cap mkd.</p>

Survey of the Subdivisional Lines,
T. 40 N., R. 25 E., Gila and Salt River Meridian, Arizona

CHAINS	
	T 40 N R 25 E S 17 1/4 ——— S 20 2017
	Deposit a magnet, in a white plastic case, at the base of the stainless steel post. Set a steel fence post nearby.
79.97	The cor. of secs. 17, 18, 19 and 20. <hr/> N. 89°57' W., bet. secs. 18 and 19. Over moderately rolling, sandy terrain, with sandstone outcroppings, through oak brush, rabbit brush and sage brush.
17.75	BIA road No. 5053, graded road, 25 ft. wide, bears N. 16° E. and S. 25° W.
39.99	Point for the 1/4 sec. cor. of secs. 18 and 19. Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 25 ins. in the ground, with brass cap mkd.
	T 40 N R 25 E S 18 1/4 ——— S 19 2017
	Deposit a magnet, in a white plastic case, at the base of the stainless steel post. Set a steel fence post nearby.
80.00	The cor. of secs. 13, 18, 19 and 24, on the W. bdy. of the Tp., monumented with brass tablet, 3 1/2 ins. diam., flush in a sandstone outcrop, mkd. T40N R24E R25E S13 S18 S24 S19 2011. Add the marks 2017 to the brass tablet. <hr/> N. 0°03' W., bet. secs. 17 and 18. Over nearly flat to slightly rolling terrain, with sandstone outcroppings, through salt brush, Yucca and Mormon tea.
23.71	BIA road No. 5053, graded road, 25 ft. wide, bears N. 54° E. and S. 45° W.

Survey of the Subdivisional Lines,
T. 40 N., R. 25 E., Gila and Salt River Meridian, Arizona

CHAINS					
39.99	<p>Point for the 1/4 sec. cor. of secs. 17 and 18.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 25 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center;"> <p>T 40 N R 25 E</p> <p>1/4</p> <p>S 18 S 17</p> <p>2017</p> </div> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p> <p>Set a steel fence post nearby.</p>				
79.97	<p>Point for the cor. of secs. 7, 8, 17 and 18.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center;"> <p>T 40 N R 25 E</p> <table style="margin: auto; border-collapse: collapse;"> <tr> <td style="border-right: 1px solid black; padding: 0 5px;">S 7</td> <td style="padding: 0 5px;">S 8</td> </tr> <tr> <td style="border-right: 1px solid black; padding: 0 5px;">S 18</td> <td style="padding: 0 5px;">S 17</td> </tr> </table> <p>2017</p> </div> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p> <p>Set a steel fence post nearby.</p> <hr style="width: 60%; margin-left: 0;"/> <p>From the cor. secs. of 8, 9, 16 and 17.</p> <p>West, bet. secs. 8 and 17.</p> <p>Over gently rolling, sandy terrain, through salt brush.</p>	S 7	S 8	S 18	S 17
S 7	S 8				
S 18	S 17				
39.99	<p>Point for the 1/4 sec. cor. of secs. 8 and 17.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 25 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center;"> <p>T 40 N R 25 E</p> <p>S 8</p> <p>1/4 ———</p> <p>S 17</p> <p>2017</p> </div> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p>				

Survey of the Subdivisional Lines,
T. 40 N., R. 25 E., Gila and Salt River Meridian, Arizona

CHAINS	
	Set a steel fence post nearby.
74.24	BIA road No. 5053, graded road, 25 ft. wide, bears N. 15° E. and S. 2° W.
79.98	The cor. of secs. 7, 8, 17 and 18. <hr/>
	N. 89°56' W., bet. secs. 7 and 18. Over gently rolling, sandy terrain, through salt brush.
13.68	BIA road No. 5051, graded road, 30 ft. wide, bears N. 52° E. and S. 52° W.
37.16	Power line, 2 strands, bears N. 53° E. and S. 53° W.
39.99	Point for the 1/4 sec. cor. of secs. 7 and 18. Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd. <div style="text-align: center;"> T 40 N R 25 E S 7 1/4 ——— S 18 2017 </div>
	Deposit a magnet, in a white plastic case, at the base of the stainless steel post. Set a steel fence post nearby. From this cor. point, the head of an undeveloped spring, bears S. 47°50' W., 43.51 chs. dist., located in bottom of wash, 20 ft. wide, 6 ft. deep, bears N. 70° E., and flows S. 80° W.
79.91	The cor. of secs. 7, 12, 13 and 18, on the W. bdy. of the Tp., monumented with stainless steel post, 2 1/2 ins. diam. projecting 2 ins. above ground, with brass cap mkd. T40N R24E R25E S12 S7 S13 S18 2011. Add the marks 2017 to the brass tablet. <hr/>
	N. 0°03' W., bet. secs. 7 and 8. Over nearly flat to slightly rolling terrain, with sandstone outcroppings, through salt brush, Yucca and Mormon tea.
14.29	BIA road No. 5051, graded road, 30 ft. wide, bears N. 32° E. and S. 32° W.
28.42	Power line, 2 strands, bears N. 53° E. and S. 53° W.

Survey of the Subdivisional Lines,
T. 40 N., R. 25 E., Gila and Salt River Meridian, Arizona

CHAINS	
39.99	<p>Point for the 1/4 sec. cor. of secs. 7 and 8.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T 40 N R 25 E 1/4 S 7 S 8</p> <p style="text-align: center;">2017</p> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p> <p>Set a steel fence post nearby.</p>
79.98	<p>Point for the cor. of secs. 5, 6, 7 and 8.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T 40 N R 25 E S 6 S 5 S 7 S 8</p> <p style="text-align: center;">2017</p> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p> <p>Set a steel fence post nearby.</p> <hr/> <p>From the cor. secs. of 4, 5, 8 and 9.</p> <p>West, bet. secs. 5 and 8.</p> <p>Over nearly flat to slightly rolling terrain, with sandstone outcroppings, through salt brush, Yucca and Mormon tea.</p>
39.99	<p>Point for the 1/4 sec. cor. of secs. 5 and 8.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T 40 N R 25 E S 5 1/4 ——— S 8</p> <p style="text-align: center;">2017</p>

Survey of the Subdivisional Lines,
T. 40 N., R. 25 E., Gila and Salt River Meridian, Arizona

CHAINS	
	<p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p> <p>Set a steel fence post nearby.</p>
63.39	BIA road No. 5053, graded road, 30 ft. wide, bears S. 9° E. and N. 17° W.
71.02	Power line, 2 strands, bears N. and S.
79.97	The cor. of secs. 5, 6, 7 and 8.
	<hr/> <p>N. 89°55' W.; bet. secs. 6 and 7.</p> <p>Over a moderate NE slope, across sandstone terrain.</p>
39.99	<p>Point for the 1/4 sec. cor. of secs. 6 and 7.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T 40 N R 25 E S 6 1/4 ——— S 7</p> <p style="text-align: center;">2017</p>
	<p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p> <p>Set a steel fence post nearby.</p>
79.82	<p>The cor. of secs. 1, 6, 7 and 12, on the W. bdy. of the Tp., monumented with brass tablet, 3 1/2 ins. diam., firmly cemented flush in sandstone outcrop, mkd. T40N R24E R25E S1 S6 S12 S7 2011. Add the marks 2017 to the brass tablet.</p> <hr/> <p>N. 0°03' W., bet. secs. 5 and 6.</p> <p>Over moderately rolling, sandy terrain, with sandstone outcroppings.</p>
39.99	<p>Point for the 1/4 sec. cor. of secs. 5 and 6.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 22 ins. in the ground, with brass cap mkd.</p>

Survey of the Subdivisional Lines,
T. 40 N., R. 25 E., Gila and Salt River Meridian, Arizona

CHAINS	
	T 40 N R 25 E 1/4 S 6 S 5 2017
	Deposit a magnet, in a white plastic case, at the base of the stainless steel post. Set a steel fence post nearby.
67.02	Point for the closing cor. of secs. 5 and 8, at intersection with the Tenth Standard Parallel North, on the N. bdy. of the Tp. Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 22 ins. in the ground, in a collar of stone, with brass cap mkd. T 41 N R 25 E S 32 ----- S 6 S 5 T 40 N R 25 E CC 2017
	Deposit a magnet, in a white plastic case, at the base of the stainless steel post. Set a steel fence post nearby. From this cor. point, the Standard 1/4 sec. cor. of sec. 32, T. 41 N., R 25 E., bears East, 37.20 chs. dist., monumented with a stainless steel post, 2 1/2 ins. diam., firmly set, projecting 3 ins. above ground, with brass cap mkd. SC T41N R25E 1/4 S32 2000. Add the marks 2017 to the brass cap. From this same cor. point, the Standard sec. cor. of sec. 31, T. 41 N., R. 25 E., bears West., 2.80 chs. dist., monumented with a stainless steel post, 2 1/2 ins. diam., firmly set, projecting 5 ins. above ground, with brass cap mkd. SC T41N R25E S31 S32 2000. Add the marks 2017 to the brass cap. From this same cor. point, the SW cor. of a concrete pad, 6 x 7 ft., supporting a windmill, bears S. 73°29' W., 16.71 chs. dist., with a water tank, approximately 3 1/2 ft. diam., nearby.
	<hr/> Point for the 1/4 sec. cor. of sec. 5 only, at midpoint on the N. bdy. of sec. 5, on the Tenth Standard Parallel North. Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with brass cap mkd.

Survey of the Subdivisional Lines,
T. 40 N., R. 25 E., Gila and Salt River Meridian, Arizona

CHAINS

T 41 N R 25 E
S 32

1/4 S 5

T 40 N R 25 E

2017

Deposit a magnet, in a white plastic case, at the base of the stainless steel post.

From this cor. point, the Standard sec. cor. of secs. 32 and 33, T. 41 N., R. 25 E., bears East, 37.21 chs. dist.

From this same cor. point, the Standard 1/4 sec. cor. of sec. 32, T. 41 N., R. 25 E., bears West, 2.79 chs. dist.

Set a steel fence post nearby.

Point for the 1/4 sec. cor. of sec. 6 only, determined West, 39.99 chs. dist., from the closing cor. of secs. 5 and 6, on the N. bdy. sec. 6, on the Tenth Standard Parallel North.

Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.

T 41 N R 25 E
S 31

1/4 S 6

T 40 N R 25 E

2017

Deposit a magnet, in a white plastic case, at the base of the stainless steel post.

Set a steel fence post nearby.

From this cor. point, the Standard 1/4 sec. cor. of sec. 31, T. 41 N., R. 25 E., bears West, 2.81 chs. dist.

Subdivision of Section 1,
T. 40 N., R. 25 E., Gila and Salt River Meridian, Arizona

From the 1/4 sec. cor. of secs. 1 and 12.

North, on the N. and S. center line of sec. 1.

Over rolling sand dunes.

Subdivision of Section 1,
T. 40 N., R. 10 E., Gila and Salt River Meridian, Arizona

CHAINS	
39.19	Trail road, 8 ft. wide, bears E. and S. 75° W.
39.99	Point for the center 1/4 sec. cor. of sec. 1, at intersection with the E. and W. center line. Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd. T 40 N R 25 E C 1/4 S 1 2017 Deposit a magnet, in a white plastic case, at the base of the stainless steel post. Set a steel fence post nearby.
67.02	The 1/4 sec. cor. of sec. 1 only, on the N. bdy. of the Tp. <hr/> From the 1/4 sec. cor. of secs. 1 and 6, on the E. bdy. of the Tp. West, on the E. and W. center line of sec. 1.
39.99	The center 1/4 sec. cor. of sec. 1.
75.61	Intersect the E. right-of-way fence of U.S. Highway No. 191, parallels the highway.
77.16	U.S. Highway No. 191, asphalt surfaced, 27 ft. wide, bears N. 8° E. and S. 8° W.
78.66	Intersect the W. right-of-way fence of U.S. Highway No. 191, parallels the highway.
79.97	The 1/4 sec. cor. of secs. 1 and 2. <hr/> <p style="text-align: center;">Subdivision of Section 2, T. 40 N., R. 25 E., Gila and Salt River Meridian, Arizona</p> <hr/> From the 1/4 sec. cor. of secs. 2 and 11. N. 0°01' W., on the N. and S. center line of sec. 2. Over moderately rolling sandstone terrain.
39.19	Trail road, 8 ft. wide, bears E. and S. 75° W.

**Subdivision of Section 2,
T. 40 N., R. 10 E., Gila and Salt River Meridian, Arizona**

CHAINS	
39.99	<p>Point for the center 1/4 sec. cor. of sec. 2, at intersection with the E. and W. center line.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 23 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T 40 N R 25 E C 1/4 S 2</p> <p style="text-align: center;">2017</p> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p> <p>Set a steel fence post nearby.</p>
67.02	<p>The 1/4 sec. cor. of sec. 2 only, on the N. bdy. of the Tp.</p> <hr/> <p>From the 1/4 sec. cor. of secs. 1 and 2.</p> <p>West, on the E. and W. center line of sec. 2.</p>
12.41	Power line, 2 strands, bears N. 8° E. and S. 8° W.
13.09	Underground water line, bears N. 8° E. and S. 8° W.
39.99	The center 1/4 sec. cor. of sec. 1.
79.98	The 1/4 sec. cor. of secs. 2 and 3.
<hr/> <p>Subdivision of Section 11, T. 40 N., R. 25 E., Gila and Salt River Meridian, Arizona</p> <hr/>	
	<p>From the 1/4 sec. cor. of secs. 11 and 14.</p> <p>N. 0°01' W., on the N. and S. center line of sec. 11.</p> <p>Over a gentle NW slope</p>
21.01	BIA road No. 5052, graded road, 25 ft. wide, bears N. 75° E. and S. 74° W.
39.99	<p>Point for the center 1/4 sec. cor. of sec. 11, at intersection with the E. and W. center line.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 18 ins. in the ground, in a mound of stone, 4 ft. base, to top, with brass cap mkd.</p>

Subdivision of Section 11,
T. 40 N., R. 10 E., Gila and Salt River Meridian, Arizona

CHAINS	
	T 40 N R 25 E C 1/4 S 11 2017
	Deposit a magnet, in a white plastic case, at the base of the stainless steel post.
	Set a steel fence post nearby.
79.97	The 1/4 sec. cor. of secs. 2 and 11. <hr/>
	From the 1/4 sec. cor. of secs. 11 and 12.
	West, on the E. and W. center line of sec. 11.
3.50	BIA road No. 5054, graded road, 25 ft. wide, bears S. 46° E. and N. 41° W.
6.54	Intersect the E. right-of-way fence of U.S. Highway No. 191, parallel the highway.
8.07	U.S. Highway No. 191, asphalt surfaced, 27 ft. wide, bears N. 8° E. and S. 8° W.
9.57	Intersect the W. right-of-way fence of U.S. Highway No. 191, parallel the highway.
18.94	Underground water line, bears S. 35° E. and N. 35° W.
23.04	Power line, 2 strands, bears N. 1° E. and S. 1° W.
39.99	The center 1/4 sec. cor. of sec. 11.
79.98	The 1/4 sec. cor. of secs. 10 and 11. <hr/>
	Subdivision of Section 14, T. 40 N., R. 25 E., Gila and Salt River Meridian, Arizona <hr/>
	From the 1/4 sec. cor. of secs. 14 and 23.
	N. 0°01' W., on the N. and S. center line of sec. 14.
	Over rough terrain with sandstone outcroppings.
39.99	Point for the center 1/4 sec. cor. of sec. 14, at intersection with the E. and W. center line.
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 22 ins. in the ground, with brass cap mkd.

Subdivision of Section 14,
T. 40 N., R. 10 E., Gila and Salt River Meridian, Arizona

CHAINS	
	T 40 N R 25 E C 1/4 S 14 2017
	Deposit a magnet, in a white plastic case, at the base of the stainless steel post.
	Set a steel fence post nearby.
79.97	The 1/4 sec. cor. of secs. 11 and 14. <hr/>
	From the 1/4 sec. cor. of secs. 13 and 14.
	West, on the E. and W. center line of sec. 14.
23.52	Intersect the E. right-of-way fence of U.S. Highway No. 191, parallels the highway.
25.09	U.S. Highway No. 191, asphalt surfaced, 27 ft. wide, bears N. 14° E. and S. 14° W.
26.67	Intersect the W. right-of-way fence of U.S. Highway No. 191, parallels the highway.
27.80	Power line, 2 strands, bears N. 1° E. and S. 1° W.
39.99	The center 1/4 sec. cor. of sec. 14.
79.98	The 1/4 sec. cor. of secs. 14 and 15. <hr/>
	Subdivision of Section 23, T. 40 N., R. 25 E., Gila and Salt River Meridian, Arizona <hr/>
	From the 1/4 sec. cor. of secs. 23 and 26.
	N. 0°01' W., on the N. and S. center line of sec. 23.
	Over slightly rolling, sandy terrain.
39.99	Point for the center 1/4 sec. cor. of sec. 23, at intersection with the E. and W. center line.
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with brass cap mkd.
	T 40 N R 25 E C 1/4 S 23 2017

Subdivision of Section 23,
T. 40 N., R. 10 E., Gila and Salt River Meridian, Arizona

CHAINS	
	Deposit a magnet, in a white plastic case, at the base of the stainless steel post.
	Set a steel fence post nearby.
39.99	The center 1/4 sec. cor. of sec. 23.
53.35	Intersect the E. right-of-way fence of U.S. Highway No. 191, parallels the highway.
59.68	U.S. Highway No. 191, asphalt surfaced, 27 ft. wide, bears N. 14° E. and S. 14° W.
66.00	Intersect the W. right-of-way fence of U.S. Highway No. 191, parallels the highway.
68.49	Power line, 2 strands, bears N. 14° E. and S. 14° W.
72.33	Power line, 4 strands, bears N. 14° E. and S. 14° W.
79.97	The 1/4 sec. cor. of secs. 14 and 23.
<hr/>	
	From the 1/4 sec. cor. of secs. 23 and 24.
	West, on the E. and W. center line of sec. 23.
39.99	The center 1/4 sec. cor. of sec. 23.
43.29	Intersect the E. right-of-way fence of U.S. Highway No. 191, parallels the highway.
44.86	U.S. Highway No. 191, asphalt surfaced, 27 ft. wide, bears N. 14° E. and S. 14° W.
46.40	Intersect the W. right-of-way fence of U.S. Highway No. 191, parallels the highway.
47.98	Power line, 4 strands, bears N. 14° E. and S. 14° W.
70.64	Power line, 2 strands, bears N. 53° E. and S. 53° W.
79.98	The 1/4 sec. cor. of secs. 22 and 23.
<hr/>	
Subdivision of Section 26, T. 40 N., R. 25 E., Gila and Salt River Meridian, Arizona	
<hr/>	
	From the 1/4 sec. cor. of secs. 23 and 26.
	N. 0°01' W., on the N. and S. center line of sec. 26.

Subdivision of Section 26,
T. 40 N., R. 10 E., Gila and Salt River Meridian, Arizona

CHAINS	
	Over slightly rolling, sandy terrain.
39.99	Point for the center 1/4 sec. cor. of sec. 26, at intersection with the E. and W. center line. Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd. T 40 N R 25 E C 1/4 S 26 2017 Deposit a magnet, in a white plastic case, at the base of the stainless steel post. Set a steel fence post nearby.
79.97	The 1/4 sec. cor. of secs. 23 and 26. <hr/>
	From the 1/4 sec. cor. of secs. 25 and 26. West, on the E. and W. center line of sec. 26.
39.99	The center 1/4 sec. cor. of sec. 26.
63.05	Intersect the E. right-of-way fence of U.S. Highway No. 191, parallels the highway.
64.62	U.S. Highway No. 191, asphalt surfaced, 27 ft. wide, bears N. 14° E. and S. 14° W.
66.17	Intersect the W. right-of-way fence of U.S. Highway No. 191, parallels the highway.
67.73	Power line, 4 strands, bears N. 14° E. and S. 14° W.
79.98	The 1/4 sec. cor. of secs. 26 and 27. <hr/>
	Subdivision of Section 34, T. 40 N., R. 25 E., Gila and Salt River Meridian, Arizona <hr/>
	From the 1/4 sec. cor. of sec. 34 only, on the S. bdy. of the Tp. N. 0°01' W., on the N. and S. center line of sec. 34 Over slightly rolling, sandy terrain, with sandstone outcroppings.
39.99	Point for the center 1/4 sec. cor. of sec. 34, at intersection with the E. and W. center line.

Subdivision of Section 34,
T. 40 N., R. 10 E., Gila and Salt River Meridian, Arizona

CHAINS	
	<p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 27 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T 40 N R 25 E C 1/4 S 34</p> <p style="text-align: center;">2017</p> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p> <p>Set a steel fence post nearby.</p>
73.96	BIA road No. 5057, graded road, 45 ft. wide, bears N. 53° E. and S. 50° W.
79.98	The 1/4 sec. cor. of secs. 27 and 34.
	<hr/> <p>From the 1/4 sec. cor. of secs. 34 and 35.</p> <p>West, on the E. and W. center line of sec. 34.</p>
0.56	U.S. Highway No. 191, asphalt surfaced, 27 ft. wide, bears N. 8° E. and S. 8° W.
2.06	Intersect the W. right-of-way fence of U.S. Highway No. 191, parallels the highway.
39.99	The center 1/4 sec. cor. of sec. 34.
79.98	The 1/4 sec. cor. of secs. 33 and 34.
	<hr/> <p style="text-align: center;">Subdivision of Section 35, T. 40 N., R. 25 E., Gila and Salt River Meridian, Arizona</p> <hr/> <p>From the 1/4 sec. cor. of secs. 23 and 26.</p> <p>N. 0°01' W., on the N. and S. center line of sec. 35.</p> <p>Over slightly rolling, sandy terrain, with sandstone outcroppings.</p>
39.99	Point for the center 1/4 sec. cor. of sec. 35, at intersection with the E. and W. center line.
	<p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 22 ins. in the ground, with brass cap mkd.</p>

Subdivision of Section 35,
T. 40 N., R. 10 E., Gila and Salt River Meridian, Arizona

CHAINS	
	T 40 N R 25 E C 1/4 S 35
	2017
	Deposit a magnet, in a white plastic case, at the base of the stainless steel post.
	Set a steel fence post nearby.
79.98	The 1/4 sec. cor. of secs. 26 and 35. <hr/>
	From the 1/4 sec. cor. of secs. 36 and 35.
	West, on the E. and W. center line of sec. 35.
39.99	The center 1/4 sec. cor. of sec. 35.
78.96	Intersect the E. right-of-way fence of U.S. Highway No. 191, bears N. 8° E. and S. 8° W.
79.98	The 1/4 sec. cor. of secs. 34 and 35. <hr/>

T. 40 N., R. 10 E., Gila and Salt River Meridian, Arizona

CHAINS

GENERAL DESCRIPTION

The area surveyed is within the Navajo Indian Reservation, approximately 8 miles northwest of the community of Rock Point. The elevation varies from 4900 to 5400 feet above sea level. Multiple trail roads provide access throughout the township. Main roads; BIA 5051, runs through sections 7, 8 and 18; BIA 5052 runs through sections 8, 9, 10, 11 and 15; BIA 5053, runs through the West portion of the township; BIA 5054, runs through sections 11 and 12. Primary access is along U.S. Highway No. 191, which runs through the eastern portion of the Tp.

The terrain is predominantly rolling, with sandy soil and sandstone outcroppings. Vegetation consists of black brush, rabbit brush, sage brush, Mormon tea, Yucca and natural grasses.

Water wells are present in sections 2, 4, 6, 14, 15 and 20. An undeveloped spring is present in section 18. Utility power lines roughly parallel U.S. Highway 191. Utility power lines and underground water lines traverse the southwest portion of the Township.

No mineral deposits or activity was noted during the course of the survey.

The mean magnetic declination of 10° E. was derived from the, United States Geological Survey computer program GEOMAG, utilizing the World Magnetic Model for 2015 for the dates of survey.

CERTIFICATE OF SURVEY

I, Rosendo Ramos Serrano, Cadastral Surveyor, HEREBY CERTIFY upon honor, that in pursuance of special instructions bearing date of the 9th day of May, 2017, I have surveyed the south and east boundaries and the subdivisional lines and subdivided certain sections, T. 40 N., R. 25 E., Gila and Salt River Meridian, in the State of Arizona, which are represented in the foregoing field notes as having been executed by me and under my direction. Said survey has been made in strict conformity with said special instructions, the Manual of Surveying Instructions (2009), and in specific manner described in the foregoing field notes.

4/12/2018
(Date)



(Cadastral Surveyor)

CERTIFICATE OF APPROVAL

BUREAU OF LAND MANAGEMENT
Phoenix, Arizona

The foregoing field notes of the survey of the south and east boundaries and the subdivisional lines and the subdivision of certain sections, T. 40 N., R. 25 E., Gila and Salt River Meridian, in the State of Arizona, executed by Rosendo Ramos Serrano, Cadastral Surveyor, having been critically examined and found correct, are hereby approved.

4/26/2018
(Date)


(Chief Cadastral Surveyor of Arizona)

~~CERTIFICATE OF TRANSCRIPT~~

~~I CERTIFY That the foregoing transcript of the field notes of the above described surveys in T. 40 N., R. 25 E., Gila and Salt River Meridian, Arizona, is a true copy of the original field notes.~~

~~_____
(Date)~~

~~_____
(Chief Cadastral Surveyor of Arizona)~~