

ORIGINAL

**UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT**

FIELD NOTES
OF THE
THE RESURVEY OF THE NORTH BOUNDARY,
TOWNSHIP 26 NORTH, RANGE 29 EAST,
AND THE SURVEY OF
THE NORTH BOUNDARY,
GOVERNING SECTION LINE,
A PORTION OF THE SUBDIVSIONAL LINES,
AND THE SUBDIVISION OF CERTAIN SECTIONS
TOWNSHIP 27 NORTH, RANGE 29 EAST,
OF THE GILA AND SALT RIVER MERIDIAN,
IN THE STATE OF ARIZONA.

EXECUTED BY

Fabian Yazzie, Cadastral Surveyor

Under Special Instructions dated September 11, 2017, approved September 11, 2017, which provided for the surveys included under Group No. 1178, and assignment instructions dated September 11, 2017.

Survey commenced September 19, 2017

Survey completed November 29, 2017

INDEX DIAGRAM

TOWNSHIP 27 NORTH RANGE 29 EAST
 GILA & SALT RIVER MERIDIAN, ARIZONA

17	17	16	15	14	13
6	5	4	3	2	32 1
7	8	9	10	11	30 12
18	17	16	15	14	28 13
19	20	21	22	23	27 24
30	29	28	27	26	25 25
23	22	21	20	19	19
31	37 32	35 33	34 34	32 35	23 36
39	38	36	35	33	26
12	10	9	7	6	4
6	5	4	3	2	1

TOWNSHIP 26 NORTH RANGE 29 EAST
 GILA & SALT RIVER MERIDIAN, ARIZONA

Subdivision of Section 1 Pages 39-40
 Subdivision of Section 12 Pages 40-41
 Subdivision of Section 24 Pages 41-42
 Subdivision of Section 25 Pages 43-44
 Subdivision of Section 31 Pages 44-45
 Subdivision of Section 32 Pages 45-46
 Subdivision of Section 36 Pages 46-47

T. 27 N., R. 29 E., Gila and Salt River Meridian, Arizona

CHAINS

The following field notes describe the resurvey of the north boundary, Township 26 North, Range 29 East, and the survey of the north boundary, governing section line, a portion of the subdivisional lines, and the subdivision of certain sections, Township 27 North, Range 29 East, Gila and Salt River Meridian, Arizona.

The history of surveys pertaining to this survey is as follows:

Frank Follman, surveyed the north boundary (south boundary) T. 26 N., R. 29 E., in 1883 (Book 1308). Jack A. Savlan, dependently resurveyed the north boundary (south boundary), T. 26 N., R. 29 E., in 1984 (Book 5269). Robin T. Mathews and Olian T. Shockley, surveyed the west boundary (east boundary), T. 27 N., R. 30 E., in 1989-1990 (Book 5328). Leonard R. Sandoval, surveyed the Seventh Guide Meridian East (west boundary) T. 27 N., R. 28 E., in 2003-2004 (Book 5757).

The survey was executed in accordance with the specifications as set forth in the Manual of Instructions for the Survey of the Public Lands of the United States, 2009, and the Special Instructions dated September 11, 2017, for Group Number 1178, Arizona.

The true meridian direction and length of all lines were determined by real time kinematic global positioning system observations using Trimble Navigation R8 model receivers.

Geodetic control was derived from Global Positioning System (GPS) static observations post processed by National Geodetic Survey, Online Positioning User Service (OPUS), utilizing Continuously Operating Reference Stations (CORS) DI0438 NMGR GRANTS NMDOT CORS ARP, DI2266 P107 GRANTS_NM2006 CORS ARP, DH4513 P015 DEUCECLUBSAZ2005 CORS ARP, DM4629 AZRV ROUND VALLEY CORS ARP, DH5816 P028 CHACOCNHP_NM2005 CORS ARP, DO2634 CT14 COMPASSTOOLS4CRNR CORS ARP, AND DL1882 AZFL NAU FLAGSTAFF CORS ARP. The NAD 83 (2011) (EPOCH: 2010), geographic position of the corner of Townships 26 and 27 North, Ranges 29 and 30 East, is as follows:

Latitude: 35°41'32.404" N. Longitude: 109°11'19.597" W.

The geographic position of the corner of Townships 27 and 28 North, Ranges 28 and 29 East:, is as follows:

Latitude: 35°46'47.003" N. Longitude: 109°17'45.488" W.

The mean magnetic declination is 9 3/4° E.

**Resurvey of the North Boundary,
T. 26 N., R. 29 E., Gila and Salt River Meridian, Arizona**

CHAINS	
	<p>NOTE: During the 1883 original survey of the N. bdy., the corners were designated to be common to Tps. 26 and 27 N. The resurvey under Group 1178 determined that the limits for rectangularity for alignment were exceeded if the corners are utilized to control the subdivision of T. 27 N., R. 29 E. Therefore, the corners on the N. bdy. were redesignated to refer to corners in T. 26 N. only. The corners on the S. bdy. of T. 27 N., R. 29 E., will be designated to refer to corners in T. 27 N. only.</p> <p>Beginning at the cor. of Tps. 26 and 27 N., Rs. 29 and 30 E., monumented with a stainless steel post, 2 1/2 ins. diam., firmly set, projecting 3 ins. above ground, with a steel fence post, N. of cor., with brass cap mkd. T27N R29E R30E S36 S31 S1 S6 T26N 1984.</p> <p>from which the remaining orig. bearing tree</p> <p style="padding-left: 40px;">A ponderosa pine, 28 ins. diam., bears N. 49 1/4° E., 142 lks. dist., with illegible scribing on a nearly healed blaze. (1984 Record: 143 lks.)</p> <p>and from which the 1984 bearing trees</p> <p style="padding-left: 40px;">A ponderosa pine, 26 ins. diam., bears S. 25° E., 116 lks. dist., with scribe marks T26N R30E S6 BT visible on partially open blaze.</p> <p style="padding-left: 40px;">A ponderosa pine, 22 ins. diam., bears S. 78° W., 99 lks. dist., with scribe marks T26N R29E S1 BT visible on partially open blaze. (Record: S. 78 1/4° W.)</p> <p style="padding-left: 40px;">A ponderosa pine, 24 ins. diam., bears N. 16 3/4° W., 121 lks. dist., with scribe marks T27N R29E S36 BT visible on partially open blaze.</p> <p>Add the marks 2017 to the brass cap.</p> <p>N. 89°58' W., on the N. bdy. of sec. 1.</p> <p>Through gently rolling, forested land.</p>
40.39	<p>The 1/4 sec. cor. of secs. 1 and 36, monumented with a stainless steel post, 2 1/2 ins. diam., firmly set, projecting 16 ins. above ground, in a supporting mound of stone, 4 ft. base, 1 ft. high, with brass cap mkd. T27N R29E 1/4 S36 S1 T26N 1984.</p> <p>from which the 1984 bearing trees</p> <p style="padding-left: 40px;">A ponderosa pine, 21 ins. diam., bears N. 9 1/4° E., 99 lks. dist., with scribe marks 1/4 S36 BT visible on partially open blaze. (Record: 98 lks.)</p>

Resurvey of the North Boundary,
T. 26 N., R. 29 E., Gila and Salt River Meridian, Arizona

CHAINS	
	<p>A ponderosa pine, 20 ins. diam., bears S. 6 1/2° E., 185 lks. dist., with scribe marks 1/4 S1 BT visible on partially open blaze.</p> <p>This cor. now functions as the 1/4 sec. cor. of sec. 1 only.</p> <p>Remark the brass cap to read:</p> <p style="text-align: center;">T 27 N R 29 E S 36</p> <hr style="width: 10%; margin: auto;"/> <p style="text-align: center;">1/4 S 1 T 26 N</p> <p style="text-align: center;">2017 1984</p> <p>Rebuild supporting mound of stone, 4 ft. base, to top.</p> <hr style="width: 20%; margin: auto;"/> <p>N. 89°57' W., beginning new measurement.</p>
12.15	BIA Route 201, Sawmill Road, a bladed dirt road, 25 ft. wide, bears N. 15° E. and S. 15° W.
40.33	<p>The sec. cor. of secs. 1, 2, 35, and 36, monumented with a stainless steel post, 2 1/2 ins. diam., firmly set, projecting 4 ins. above ground, with a scattered accessory mound of stone to the N., with brass cap mkd. T27N R29E S35 S36 S2 S1 T26N 1984.</p> <p>from which the remaining orig. bearing trees</p> <p style="padding-left: 40px;">A charred ponderosa pine, 33 ins. diam., bears N. 36° E., 57 lks. dist., with no visible scribe marks on partially visible blaze. (1984 Record: 55 lks.)</p> <p style="padding-left: 40px;">A ponderosa pine, 29 ins. diam., bears S. 71° W., 84 lks. dist., with illegible scribing on a nearly healed blaze. (1984 Record: 85 lks.)</p> <p>and from which the 1984 bearing trees</p> <p style="padding-left: 40px;">A ponderosa pine, 20 ins. diam., bears S. 75 1/2° E., 214 lks. dist., with scribe marks 1 BT on a partially open blaze.</p> <p style="padding-left: 40px;">A ponderosa pine, 25 ins. diam., bears N. 22 1/2° W., 133 lks. dist., with scribe marks T27N R29E S35 BT visible on partially open blaze.</p> <p>This cor. now functions as the cor. of secs. 1 and 2 only.</p> <p>Remark the brass cap to read:</p>

Resurvey of the North Boundary,
T. 26 N., R. 29 E., Gila and Salt River Meridian, Arizona

CHAINS	T 27 N R 29 E S 35 <hr style="width: 50%; margin: 0 auto;"/> S 2 S 1 T 26 N 2017 1984
40.18	<p>Rebuild mound of stone, 3 ft. base, 2 ft. high, S. of cor.</p> <hr style="width: 80%; margin: 10px auto;"/> <p>N. 89°13' W., on the N. bdy. of sec. 2.</p> <p>Through rolling, forested land.</p> <p>The 1/4 sec. cor. of secs. 2 and 35, monumented with an aluminum drive rod, 1 in. diam., firmly set, projecting 3 ins. above ground, with a mound of stone, 3 1/2 ft. base, 2 ft. high, N. of cor., with 3 1/2 in. diam. alum. cap mkd. T27N R29E 1/4 S35 S2 T26N 1984.</p> <p>from which the orig. bearing tree</p> <p style="padding-left: 40px;">A decomposed ponderosa pine stump, 12 ins. diam., 22 ins. high, bears N. 4° W., 13 lks. dist., with illegible scribing on open blaze. (1984 Record: 12 lks.)</p> <p>and from which the 1984 accessories</p> <p style="padding-left: 40px;">A sandstone rock outcrop, 10 x 5 x 1 ft., bears N. 3 1/4° E., 34 lks. dist., mkd. B X O. (Record: N. 3 1/4° W.)</p> <p style="padding-left: 40px;">A ponderosa pine, 27 ins. diam., bears N. 15 1/2° W., 128 lks. dist., with scribe marks 1/4 S35 BT visible on partially open blaze. (Record: 130 lks.)</p> <p>This cor. now functions as the 1/4 sec. cor. of sec. 2 only.</p> <p>Remark the brass cap to read:</p> <div style="text-align: center; padding: 10px 0 10px 40px;"> T 27 N R 29 E S 35 <hr style="width: 50%; margin: 0 auto;"/> 1/4 S 2 T 26 N 2017 1984 </div> <hr style="width: 80%; margin: 10px auto;"/> <p>N. 89°21' W., beginning new measurement.</p> <p>Through rolling, forested land.</p>

Resurvey of the North Boundary,
T. 26 N., R. 29 E., Gila and Salt River Meridian, Arizona

CHAINS									
39.71	<p>The sec. cor. of secs. 2, 3, 34, and 35, monumented with a stainless steel post, 2 1/2 ins. diam., firmly set, projecting 2 ins. above ground, with a steel fence post, NW of cor., with brass cap mkd. T27N R29E S34 S35 S3 S2 T26N 1984.</p> <p>from which the remaining orig. bearing tree</p> <p style="padding-left: 40px;">A ponderosa pine stump, 32 ins. diam., 18 ins. high, bears N. 29 1/2° W., 120 lks. dist., with no visible scribe marks on partially visible blaze.</p> <p>and from which the 1984 bearing trees</p> <p style="padding-left: 40px;">A ponderosa pine, 32 ins. diam., bears N. 1° E., 93 lks. dist., with a nearly healed blaze. (Record: 94 lks.) Expose partially healed blaze to reveal marks and remark S35 to S34.</p> <p style="padding-left: 40px;">A ponderosa pine, 29 ins. diam., bears S. 54 1/2° E., 296 lks. dist., with scribe marks T26N R29E S2 BT visible on partially open blaze. (Record: 295 lks.)</p> <p style="padding-left: 40px;">A stump hole to dead and downed piñon, 7 ins. diam., bears S. 82 1/2° W., 113 lks. dist., with scribe marks T26N R29E S3 BT visible on partially open blaze. (Record: 114 lks.)</p> <p>This cor. now functions as the cor. of secs. 2 and 3 only.</p> <p>Remark the brass cap to read:</p> <div style="text-align: center; margin: 10px 0;"> <table style="margin: auto;"> <tr><td>T 27 N</td><td>R 29 E</td></tr> <tr><td colspan="2" style="border-top: 1px solid black;">S 34</td></tr> <tr><td>S 3</td><td>S 2</td></tr> <tr><td colspan="2" style="border-top: 1px solid black;">T 26 N</td></tr> </table> <p style="margin: 5px 0;">2017 1984</p> </div> <hr style="width: 60%; margin: 10px auto;"/> <p>N. 89°59' W., on the N. bdy. of sec. 3.</p> <p>Through rolling, forested land.</p>	T 27 N	R 29 E	S 34		S 3	S 2	T 26 N	
T 27 N	R 29 E								
S 34									
S 3	S 2								
T 26 N									
40.36	<p>The 1/4 sec. cor. of secs. 3 and 34, monumented with a stainless steel post, 2 1/2 ins. diam., firmly set, projecting 2 ins. above ground, with a steel fence post, NW of cor., with brass cap mkd. T27N R29E 1/4 S34 S3 T26N 1984.</p> <p>from which the orig. bearing tree</p> <p style="padding-left: 40px;">A ponderosa pine, 31 ins. diam., bears S. 35 3/4° W., 36 lks. dist., with a healed blaze.</p>								

Resurvey of the North Boundary,
T. 26 N., R. 29 E., Gila and Salt River Meridian, Arizona

CHAINS	
	<p style="text-align: center;">A ponderosa pine, 30 ins. diam., bears N. 61 1/2° W., 17 lks. dist., with a healed blaze.</p> <p>This cor. now functions as the 1/4 sec. cor. of sec. 3 only.</p> <p>Remark the brass cap to read:</p> <div style="text-align: center;"> <p>T 27 N R 29 E</p> <p>S 34</p> <hr style="width: 10%; margin: auto;"/> <p>1/4 S 3</p> <p>T 26 N</p> <p>2017</p> <p>1984</p> </div> <hr style="width: 30%; margin: 20px auto;"/> <p>S. 89°59' W., beginning new measurement.</p> <p>Through rolling, forested land.</p>
40.33	<p>The sec. cor. of secs. 3, 4, 33, and 34, monumented with a stainless steel post, 2 1/2 ins. diam., firmly set, projecting 4 ins. above ground, with brass cap mkd. T27N R29E S33 S34 S4 S3 T26N 1984.</p> <p>from which the 1984 bearing trees</p> <p style="padding-left: 40px;">A ponderosa pine, 27 ins. diam., bears N. 16 1/4° E., 193 lks. dist., with scribe marks T27N R29E S34 BT visible on partially open blaze. (Record: 192 lks.) Remark S34 to S33.</p> <p style="padding-left: 40px;">A decomposed ponderosa pine stump, 24 ins. diam., 18 ins. high, bears S. 18 1/2° W., 168 lks. dist., BT visible on partially visible blaze.</p> <p style="padding-left: 40px;">A ponderosa pine, 23 ins. diam., bears N. 32 1/4° W., 46 lks. dist., with scribe marks T27N R29E S33 BT visible on partially open blaze.</p> <p>This cor. now functions as the cor. of secs. 3 and 4 only.</p> <p>Remark the brass cap to read:</p> <div style="text-align: center;"> <p>T 27 N R 29 E</p> <p>S 33</p> <hr style="width: 10%; margin: auto;"/> <p>S 4 S 3</p> <p>T 26 N</p> <p>2017</p> <p>1984</p> </div>

**Resurvey of the North Boundary,
T. 26 N., R. 29 E., Gila and Salt River Meridian, Arizona**

CHAINS	
40.33	<p>Set a steel fence post alongside and N. of cor.</p> <hr/> <p>S. 89°59' W., on the N. bdy. of sec. 4.</p> <p>Through rolling, forested land.</p> <p>The 1/4 sec. cor. of secs. 4 and 33, monumented with a stainless steel post, 2 1/2 ins. diam., firmly set, projecting 6 ins. above ground, with brass cap mkd. T27N R29E 1/4 S33 S4 T26N 1984.</p> <p>from which the 1984 bearing trees</p> <p style="padding-left: 40px;">A ponderosa pine, 22 ins. diam., bears S. 64 1/4° E., 389 lks. dist., with a healed blaze.</p> <p style="padding-left: 40px;">A ponderosa pine, 27 ins. diam., bears N. 37 1/2° W., 267 lks. dist., with scribe marks 1/4 S33 BT visible on partially open blaze. (1984 Record: 266 lks.)</p> <p>This cor. now functions as the 1/4 sec. cor. of sec. 4 only.</p> <p>Remark the brass cap to read:</p> <div style="text-align: center; margin-left: 100px;"> <p>T 27 N R 29 E</p> <p>S 33</p> <hr style="width: 50px; margin: 0 auto;"/> <p>1/4 S 4</p> <p>T 26 N</p> <p>2017</p> <p>1984</p> </div> <p>Set a steel fence post alongside and N. of cor.</p> <hr/> <p>N. 89°43' W., beginning new measurement.</p> <p>Through rolling, forested land.</p>
40.27	<p>The sec. cor. of secs. 4, 5, 32, and 33, monumented with a stainless steel post, 2 1/2 ins. diam., firmly set, projecting 6 ins. above ground, with a steel fence post set alongside, with brass cap mkd. T27N R29E S32 S33 S5 S4 T26N 1984.</p> <p>from which the remaining orig. bearing tree</p> <p style="padding-left: 40px;">A decomposed ponderosa pine stump, 37 ins. diam., bears N. 56° E., 53 lks. dist., with no visible blaze.</p> <p>and from which the 1984 bearing trees</p>

**Resurvey of the North Boundary,
T. 26 N., R. 29 E., Gila and Salt River Meridian, Arizona**

CHAINS															
	<p>A ponderosa pine, 25 ins. diam., bears N. 52° E., 225 lks. dist., with scribe marks T27N R29E S33 BT visible on partially open blaze. (Record: 226 lks.) Remark S33 to S32</p> <p>A ponderosa pine, 21 ins. diam., bears S. 85 1/2° W., 150 lks. dist., with scribe marks T26N R29E S5 BT visible on partially open blaze.</p> <p>A ponderosa pine, 26 ins. diam., bears N. 27 1/2° W., 133 lks. dist., with illegible scribing on a nearly healed blaze.</p> <p>This cor. now functions as the cor. of secs. 4 and 5 only.</p> <p>Remark the brass cap to read:</p> <div style="text-align: center; margin: 10px 0;"> <table style="margin: auto;"> <tr><td>T 27 N</td><td>R 29 E</td></tr> <tr><td colspan="2">S 32</td></tr> <tr><td colspan="2"><hr style="width: 100%;"/></td></tr> <tr><td>S 5</td><td>S 4</td></tr> <tr><td colspan="2">T 26 N</td></tr> <tr><td colspan="2">2017</td></tr> <tr><td colspan="2">1984</td></tr> </table> </div> <hr style="width: 100%;"/> <p>N. 89°40' W., on the N. bdy. of sec. 5.</p> <p>Through rolling, forested land.</p> <p>6.50 N. right-of-way fence of Arizona State Highway 264, barbed wire, 5 strand, parallels highway.</p> <p>11.00 Arizona State Highway 264, asphalt surfaced, 39 ft. wide, bears S. 70° E. and N. 70° W.</p> <p>15.50 S. right-of-way fence of Arizona State Highway 264, barbed wire, 5 strand, parallels highway.</p> <p>40.34 The 1/4 sec. cor. of secs. 5 and 32, monumented with a stainless steel post, 2 1/2 ins. diam., firmly set, projecting 12 ins. above ground, in a mound of stone, 4 1/2 ft. base, to top, with a steel fence post, N. of cor., with brass cap mkd. T27N R29E 1/4 S32 S5 T26N 1984.</p> <p>from which the 1984 bearing trees</p> <p>A ponderosa pine, 21 ins. diam., bears S. 28 1/4° W., 179 lks. dist., with a healed blaze.</p> <p>A ponderosa pine, 20 ins. diam., bears N. 17 1/4° W., 219 lks. dist., with scribe marks 1/4 S32 BT visible on partially open blaze.</p>	T 27 N	R 29 E	S 32		<hr style="width: 100%;"/>		S 5	S 4	T 26 N		2017		1984	
T 27 N	R 29 E														
S 32															
<hr style="width: 100%;"/>															
S 5	S 4														
T 26 N															
2017															
1984															

Resurvey of the North Boundary,
T. 26 N., R. 29 E., Gila and Salt River Meridian, Arizona

CHAINS

This cor. now functions as the 1/4 sec. cor. of sec. 5 only.

Remark the brass cap to read:

T 27 N R 29 E
S 32

1/4 S 5
T 26 N

2017
1984

N. 89°40' W., beginning new measurement.

Through rolling, forested land.

40.33

Point for the cor. of secs. 5, 6, 31, and 32, monumented with a stainless steel post, 2 1/2 ins. diam., firmly set, projecting 1 in. above ground, with a mound of stone, 2 ft. base, 1 ft. high, W. of cor., with a steel fence post, W. of cor., with brass cap mkd. T27N R29E S31 S32 S6 S5 T26N 1984.

from which the 1984 bearing trees

A ponderosa pine, 27 ins. diam., bears N. 21 1/2° E., 161 lks. dist., with a healed blaze. Remark S32 to S31 by exposing part of healed blaze.

A ponderosa pine, 27 ins. diam., bears S. 77° E., 191 lks. dist., with scribe marks T26N R29E S5 BT visible on partially open blaze.

A ponderosa pine, 24 ins. diam., bears S. 13 1/2° W., 226 lks. dist., with scribe marks T26N R29E S6 BT visible on partially open blaze.

A piñon, 14 ins. diam., bears N. 48° W., 101 lks. dist., with scribe marks T27N R29E S31 BT visible on partially open blaze. (Record: 100 lks.)

This cor. now functions as the cor. of secs. 5 and 6 only.

Remark the brass cap to read:

Resurvey of the North Boundary,
T. 26 N., R. 29 E., Gila and Salt River Meridian, Arizona

CHAINS	
40.33	<p>T 27 N R 29 E S 31</p> <hr style="width: 50%; margin: auto;"/> <p>S 6 S 5 T 26 N</p> <p>2017 1984</p> <hr style="width: 80%; margin: auto;"/> <p>N. 89°40' W., on the N. bdy. of sec. 6.</p> <p>Through rolling, forested land.</p> <p>The 1/4 sec. cor. of secs. 6 and 31, monumented with a stainless steel post, 2 1/2 ins. diam., firmly set, projecting 6 ins. above ground, with a steel fence post nearby, with brass cap mkd. T27N R29E 1/4 S31 S6 T26N 1984.</p> <p>from which the 1984 bearing trees</p> <p style="padding-left: 40px;">A ponderosa pine, 30 ins. diam., bears S. 14° E., 111 lks. dist., with scribe marks 1/4 S6 BT visible on partially open blaze. (Record: S. 14 1/4° E.)</p> <p style="padding-left: 40px;">A piñon, 14 ins. diam., bears N. 28° W., 161 lks. dist., with scribe marks 1/4 S31 BT visible on partially open blaze. (Record: 162 lks.)</p> <p>This cor. now functions as the 1/4 sec. cor. of sec. 6 only.</p> <p>Remark the brass cap to read:</p> <p style="text-align: center;"> <p>T 27 N R 29 E S 31</p> <hr style="width: 50%; margin: auto;"/> <p>1/4 S 6 T 26 N</p> <p>2017 1984</p> <hr style="width: 80%; margin: auto;"/> </p> <p>N. 89°40' W., beginning new measurement.</p> <p>Through rolling, forested land.</p>
39.58	<p>The cor. of Tps. 26 and 27 N., Rs. 28 and 29 E., monumented with a stainless steel post, 2 1/2 ins. diam., firmly set, projecting 3 ins. above ground, with brass cap mkd. T27N R28E R29E S36 S31 S1 S6 T26N 1984.</p> <p>from which the 1984 bearing trees</p>

**Resurvey of the North Boundary,
T. 26 N., R. 29 E., Gila and Salt River Meridian, Arizona**

CHAINS	<p>A piñon, 6 ins. diam., bears N. 41 1/2° E., 14 lks. dist., with scribe marks T27N R29E S31 BT visible on partially open blaze. (Record: N. 42 1/2° E.)</p> <p>A piñon, 9 ins. diam., bears S. 9 1/4° E., 44 lks. dist., with scribe marks T26N R29E S6 BT visible on partially open blaze.</p> <p>A piñon, 9 ins. diam., bears S. 29 3/4° W., 29 lks. dist., with scribe marks T26N R28E S1 BT visible on partially open blaze.</p> <p>A ponderosa pine, 25 ins. diam., bears N. 9 1/4° W., 96 lks. dist., with scribe marks T27N R28E S36 BT visible on partially open blaze.</p> <p>Add the marks 2017 to the brass cap.</p> <hr/> <p style="text-align: center;">Survey of the North Boundary, T. 27 N., R. 29 E., Gila and Salt River Meridian, Arizona</p> <hr/> <p>From the cor. of Tps. 27 and 28 N., Rs. 29 and 30 E., monumented with a stainless steel post, 2 1/2 ins. diam., firmly set, projecting 4 ins. above ground, with brass cap mkd. T28N R29E R30E S36 S31 S1 S6 T27N 1989.</p> <p>from which the 1989 bearing trees</p> <p>A ponderosa pine, 19 ins. diam., bears N. 51 3/4° E., 94 1/2 lks. dist., with illegible scribe marks on nearly healed blazed.</p> <p>A ponderosa pine, 18 ins. diam., bears S. 81 1/4° E., 19 1/2 lks. dist., with a healed blaze. (Record: S. 79 1/2° E.)</p> <p>A ponderosa pine, 27 ins. diam., bears S. 45 3/4° W., 33 lks. dist., with scribe marks T27N R29E S1 BT visible on partially open blaze.</p> <p>A dead standing ponderosa pine, 13 ins. diam., bears N. 13 1/2° W., 74 lks. dist., with scribe marks T28N R29E S36 BT visible on partially open blaze.</p> <p>Add the marks 2017 to the brass cap.</p> <p>N. 89°44' W., bet. secs. 1 and 36.</p> <p>Through gently rolling, forested land.</p> <p>37.70 BIA Route 201, Sawmill Road, a bladed dirt road, 25 ft. wide, bears N. 5° E. and S. 5° W.</p>
--------	---

Survey of the North Boundary,
T. 27 N., R. 29 E., Gila and Salt River Meridian, Arizona

CHAINS	
40.00	<p>Point for the 1/4 sec. cor. of secs. 1 and 36.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T 28 N R 29 E S 36 1/4 ——— S 1 T 27 N</p> <p style="text-align: center;">2017</p> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p> <p>Set a steel fence post alongside and N. of cor.</p>
80.00	<p>Point for the cor. of secs. 1, 2, 35, and 36.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 22 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T 28 N R 29 E S 35 S 36 S 2 S 1 T 27 N</p> <p style="text-align: center;">2017</p> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p> <p>Set a steel fence post alongside and N. of cor.</p> <hr/> <p>N. 89°44' W., bet. secs. 2 and 35.</p> <p>Through gently rolling, forested land.</p>
40.00	<p>Point for the 1/4 sec. cor. of secs. 2 and 35.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 11 ins. in the ground to sandstone bedrock, in a supporting mound of stone, 4 1/2 ft. base, to top, with brass cap mkd.</p> <p style="text-align: center;">T 28 N R 29 E S 35 1/4 ——— S 2 T 27 N</p> <p style="text-align: center;">2017</p>

Survey of the North Boundary,
T. 27 N., R. 29 E., Gila and Salt River Meridian, Arizona

CHAINS											
80.00	<p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p> <p>Set a steel fence post alongside and N. of cor.</p> <p>Point for the cor. of secs. 2, 3, 34, and 35.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center; margin: 10px 0;"> <table style="margin: auto; border-collapse: collapse;"> <tr> <td style="padding: 0 10px;">T 28 N</td> <td style="padding: 0 10px;">R 29 E</td> </tr> <tr> <td style="padding: 0 10px;">S 34</td> <td style="padding: 0 10px;">S 35</td> </tr> <tr> <td style="padding: 0 10px;">S 3</td> <td style="padding: 0 10px;">S 2</td> </tr> <tr> <td colspan="2" style="padding: 0 10px;">T 27 N</td> </tr> </table> <p>2017</p> </div> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p> <p>Set a steel fence post alongside and N. of cor.</p> <hr style="width: 50%; margin: 10px auto;"/> <p>N. 89°44' W., bet. secs. 3 and 34.</p> <p>Through gently rolling, forested land.</p>	T 28 N	R 29 E	S 34	S 35	S 3	S 2	T 27 N			
T 28 N	R 29 E										
S 34	S 35										
S 3	S 2										
T 27 N											
40.00	<p>Point for the 1/4 sec. cor. of secs. 3 and 34.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 17 ins. in the ground to sandstone bedrock, in a mound of stone, 4 ft. base, to top, with brass cap mkd.</p> <div style="text-align: center; margin: 10px 0;"> <table style="margin: auto; border-collapse: collapse;"> <tr> <td style="padding: 0 10px;">T 28 N</td> <td style="padding: 0 10px;">R 29 E</td> </tr> <tr> <td colspan="2" style="padding: 0 10px;">S 34</td> </tr> <tr> <td colspan="2" style="padding: 0 10px;">1/4 ———</td> </tr> <tr> <td colspan="2" style="padding: 0 10px;">S 3</td> </tr> <tr> <td colspan="2" style="padding: 0 10px;">T 27 N</td> </tr> </table> <p>2017</p> </div>	T 28 N	R 29 E	S 34		1/4 ———		S 3		T 27 N	
T 28 N	R 29 E										
S 34											
1/4 ———											
S 3											
T 27 N											
80.00	<p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p> <p>Set a steel fence post alongside and N. of cor.</p> <p>Point for the cor. of secs. 3, 4, 33, and 34.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 20 ins. in the ground through subsurface sandstone bedrock, encircled with a collar of stone, 3 ft. base, to top, with brass cap mkd.</p>										

Survey of the North Boundary,
T. 27 N., R. 29 E., Gila and Salt River Meridian, Arizona

CHAINS	
	T 28 N R 29 E S 33 S 34 S 4 S 3 T 27 N 2017
	Deposit a magnet, in a white plastic case, at the base of the stainless steel post. Set a steel fence post alongside and N. of cor. <hr/> N. 89°44' W., bet. secs. 4 and 33. Through gently rolling, forested land.
40.00	Point for the 1/4 sec. cor. of secs. 4 and 33. Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd. T 28 N R 29 E S 33 1/4 ——— S 4 T 27 N 2017
	Deposit a magnet, in a white plastic case, at the base of the stainless steel post. Set a steel fence post alongside and N. of cor.
80.00	Point for the cor. of secs. 4, 5, 32, and 33. Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 23 ins. in the ground, with brass cap mkd. T 28 N R 29 E S 32 S 33 S 5 S 4 T 27 N 2017
	Deposit a magnet, in a white plastic case, at the base of the stainless steel post. Set a steel fence post alongside and N. of cor. <hr/>

Survey of the North Boundary,
T. 27 N., R. 29 E., Gila and Salt River Meridian, Arizona

CHAINS					
40.00	<p>N. 89°44' W., bet. secs. 5 and 32.</p> <p>Through gently rolling, forested land.</p> <p>Point for the 1/4 sec. cor. of secs. 5 and 32.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 25 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center;"> <p>T 28 N R 29 E</p> <p>S 32</p> <p>1/4 ———</p> <p>S 5</p> <p>T 27 N</p> <p>2017</p> </div> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p> <p>Set a steel fence post alongside and N. of cor.</p>				
80.00	<p>Point for the cor. of secs. 5, 6, 31, and 32.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center;"> <p>T 28 N R 29 E</p> <table style="margin: auto; border-collapse: collapse;"> <tr> <td style="border-right: 1px solid black; padding: 0 5px;">S 31</td> <td style="padding: 0 5px;">S 32</td> </tr> <tr> <td style="border-right: 1px solid black; padding: 0 5px;">S 6</td> <td style="padding: 0 5px;">S 5</td> </tr> </table> <p>T 27 N</p> <p>2017</p> </div> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p> <p>Set a steel fence post alongside and N. of cor.</p> <hr style="width: 60%; margin-left: 0;"/>	S 31	S 32	S 6	S 5
S 31	S 32				
S 6	S 5				
40.00	<p>N. 89°44' W., bet. secs. 6 and 31.</p> <p>Through gently rolling, forested land.</p> <p>Point for the 1/4 sec. cor. of secs. 6 and 31.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 25 ins. in the ground, with brass cap mkd.</p>				

Survey of the North Boundary,
T. 27 N., R. 29 E., Gila and Salt River Meridian, Arizona

CHAINS	
	T 28 N R 29 E S 31 1/4 ——— S 6 T 27 N 2017
	Deposit a magnet, in a white plastic case, at the base of the stainless steel post. Set a steel fence post alongside and N. of cor.
81.91	The cor. of Tps. 27 and 28 N., Rs. 28 and 29 E., monumented with a stainless steel post, 2 1/2 ins. diam., firmly set, projecting 5 ins. above ground, with brass cap mkd. T28N R28E R29E S36 S31 S1 S6 T27N 2003. Add the marks 2017 to the brass cap.
	<hr/> Survey of Governing Section Line, T. 27 N., R. 29 E., Gila and Salt River Meridian, Arizona <hr/>
	NOTE: The results of the resurvey of the north boundary, under Group 1178, T. 26 N., R. 29 E., exceeds the specified rectangular limits for alignment to control the subdivision of this township. This necessitates the need for the establishment of a governing section line. From the cor. of secs. 25, 30, 31, and 36, on the E. bdy. of the Tp., monumented with a stainless steel post, 2 1/2 ins. diam., firmly set, projecting 4 ins. above ground, with brass cap mkd. T27N R29E R30E S25 S30 S36 S31 1989. from which the 1989 bearing trees <ul style="list-style-type: none"> A ponderosa pine, 20 ins. diam., bears N. 74 1/4° E., 157 lks. dist., with scribe marks T27N R30E S30 BT visible on partially open blaze. A ponderosa pine, 14 ins. diam., bears S. 85 3/4° E., 66 lks. dist., with scribe marks T27N R30E S31 BT visible on open blaze. (Record: S. 86 1/4° E.) A ponderosa pine, 17 ins. diam., bears S. 56 3/4° W., 178 lks. dist., with scribe marks T27N R29E S36 BT visible on partially open blaze. A ponderosa pine, 15 ins. diam., bears N. 15° W., 68 lks. dist., with scribe marks T27N R29E S25 BT visible on partially open blaze. (Record: 69 lks.) Add the marks 2017 to the brass cap.

Survey of Governing Section Line,
T. 27 N., R. 29 E., Gila and Salt River Meridian, Arizona

CHAINS	
	N. 89°45' W., bet. secs. 25 and 36. Through gently rolling, forested land.
33.30	BIA Route 201, Sawmill Road, a bladed dirt road, 25 ft. wide, bears N. 15° E. and S. 15° W.
40.00	Point for the 1/4 sec. cor. of secs. 25 and 36. Set a brass tablet, 3 1/2 ins. diam., 2 1/4 ins. stem, cemented in a drill hole in solid sandstone bedrock, with top mkd. <div style="text-align: center;"> T 27 N R 29 E S 25 1/4 ——— S 36 2017 </div>
	Deposit a magnet, in a white plastic case, at the base of the brass tablet. Set a steel fence post alongside and N. of cor.
80.00	Point for the cor. of secs. 25, 26, 35, and 36. Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 23 ins. in the ground, with brass cap mkd. <div style="text-align: center;"> T 27 N R 29 E S 26 S 25 S 35 S 36 2017 </div>
	Deposit a magnet, in a white plastic case, at the base of the stainless steel post. Set a steel fence post alongside and W. of cor. <hr style="width: 60%; margin-left: 0;"/>
	N. 89°45' W., bet. secs. 26 and 35. Through gently rolling, forested land.
40.00	Point for the 1/4 sec. cor. of secs. 26 and 35. Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.

Survey of Governing Section Line,
T. 27 N., R. 29 E., Gila and Salt River Meridian, Arizona

CHAINS	
	T 27 N R 29 E S 26 1/4 ——— S 35 2017
	Deposit a magnet, in a white plastic case, at the base of the stainless steel post. Set a steel fence post alongside and N. of cor.
80.00	Point for the cor. of secs. 26, 27, 34, and 35. Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 23 ins. in the ground, with brass cap mkd.
	T 27 N R 29 E S 27 S 26 S 34 S 35 2017
	Deposit a magnet, in a white plastic case, at the base of the stainless steel post. Set a steel fence post alongside and W. of cor.
	<hr/> N. 89°45' W., bet. secs. 27 and 34. Through gently rolling, forested land.
40.00	Point for the 1/4 sec. cor. of secs. 27 and 34. Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 21 ins. in the ground, encircled with a collar of stone, 2 1/2 ft. base, to top, with brass cap mkd.
	T 27 N R 29 E S 27 1/4 ——— S 34 2017
	Deposit a magnet, in a white plastic case, at the base of the stainless steel post. Set a steel fence post alongside and N. of cor.
80.00	Point for the cor. of secs. 27, 28, 33, and 34.

Survey of Governing Section Line,
T. 27 N., R. 29 E., Gila and Salt River Meridian, Arizona

CHAINS	
	<p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 25 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T 27 N R 29 E S 28 S 27 S 33 S 34</p> <p style="text-align: center;">2017</p> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p> <p>Set a steel fence post alongside and W. of cor.</p> <hr/> <p>N. 89°45' W., bet. secs. 28 and 33.</p> <p>Through gently rolling, forested land.</p>
40.00	<p>Point for the 1/4 sec. cor. of secs. 28 and 33.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 12 ins. in the ground to sandstone bedrock, in a supporting mound of stone, 5 ft. base, to top, with brass cap mkd.</p> <p style="text-align: center;">T 27 N R 29 E S 28 1/4 ——— S 33</p> <p style="text-align: center;">2017</p> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p> <p>Set a steel fence post alongside and NW of cor.</p> <p>From this point, a cast iron hand pump to water well, firmly set in a concrete pad 5 x 5 x 3 ft., mkd. Nellie James Dug Well Project No. 17-4-22 6-25-65, on top of concrete pad., bears S. 43°06' E., 18.0 chs. dist.</p>
80.00	<p>Point for the cor. of secs. 28, 29, 32, and 33.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 14 ins. in sandstone bedrock, in a supporting mound of stone, 5 ft. base, to top, with brass cap mkd.</p> <p style="text-align: center;">T 27 N R 29 E S 29 S 28 S 32 S 33</p> <p style="text-align: center;">2017</p>

Survey of Governing Section Line,
T. 27 N., R. 29 E., Gila and Salt River Meridian, Arizona

CHAINS	
	<p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p> <p>Set a steel fence post alongside and W. of cor.</p> <hr/> <p>N. 89°45' W., bet. secs. 29 and 32.</p> <p>Through gently rolling, forested land.</p>
40.00	<p>Point for the 1/4 sec. cor. of secs. 29 and 32.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center;"> <p>T 27 N R 29 E</p> <p>S 29</p> <p>1/4 ———</p> <p>S 32</p> <p>2017</p> </div> <p>from which</p> <p style="padding-left: 40px;">A stainless steel post, 28 ins. long, 2 1/2 ins. diam., set 24 ins. in the ground for a reference monument, bears N. 10°00' E., 80.0 ft. dist. with brass cap mkd. RM T27N R29E 80.0 FT TO COR 1/4 S29 2017 and an arrow pointing to the cor. Deposit a magnet, in a white plastic case, at the base of the stainless steel post, and set a steel fence post alongside and NW of cor.</p> <p style="padding-left: 40px;">A stainless steel post, 28 ins. long, 2 1/2 ins. diam., set 24 ins. in the ground for a reference monument, bears S. 10°00' W., 40.0 ft. dist. with brass cap mkd. RM T27N R29E 40.0 FT TO COR 1/4 S32 2017 and an arrow pointing to the cor. Deposit a magnet, in a white plastic case, at the base of the stainless steel post, and set a steel fence post alongside and SW of cor.</p> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p> <p>Set a steel fence post alongside and N. of cor.</p> <p>Cor. is located in center of Kinlichee Canyon Creek, Bear Canyon, 25 ft. wide, 2 ft. deep, drains N. 70° W.</p>
80.00	<p>Point for the cor. of secs. 29, 30, 31, and 32.</p> <p>Set a brass tablet, 3 1/2 ins. diam., with 18 in. stainless steel stem, cemented in a drill hole, flush with the surface of solid sandstone bedrock, with top mkd.</p>

Survey of Governing Section Line,
T. 27 N., R. 29 E., Gila and Salt River Meridian, Arizona

CHAINS	
	T 27 N R 29 E S 30 S 29 S 31 S 32 2017
	Deposit a magnet, in a white plastic case, at the base of the stainless steel stem.
	Set a steel fence post alongside and W. of cor. in center of an accessory mound of stone, 3 ft. base, 3 ft. high.
	<hr/> N. 89°45' W., bet. secs. 30 and 31.
	Through gently rolling, forested land.
40.00	Point for the 1/4 sec. cor. of secs. 30 and 31.
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in sandstone bedrock, encircled with a collar of stone, 2 ft. base, with brass cap mkd.
	T 27 N R 29 E S 30 1/4 ——— S 31 2017
	Deposit a magnet, in a white plastic case, at the base of the stainless steel post.
	Set a steel fence post alongside and N. of cor.
82.38	The cor. of secs. 25, 30, 31, and 36, on the W. bdy. of the Tp., monumented with a stainless steel post, 2 1/2 ins. diam., firmly set, projecting 4 ins. above ground, with brass cap mkd. T27N R28E R29E S25 S30 S36 S31 2003. Add the marks 2017 to the brass cap.
	From this cor. point, the cor. of Tps. 27 and 28 N., Rs. 28 and 29 E., bears North, 400.0 chs. dist., hereinbefore described.
	<hr/> Survey of a Portion of the Subdivisional Lines, T. 27 N., R. 29 E., Gila and Salt River Meridian, Arizona
	From the cor. of secs. 25, 26, 35, and 36, on the governing section line, hereinbefore described.
	S. 0°01' E., bet. secs. 35 and 36.

Survey of a Portion of the Subdivisional Lines,
T. 27 N., R. 29 E., Gila and Salt River Meridian, Arizona

CHAINS	
	Through gently rolling, forested land.
40.00	<p>Point for the 1/4 sec. cor. of secs. 35 and 36.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., flush with the surface of the ground, with brass cap mkd.</p> <p style="text-align: center;">T 27 N R 29 E 1/4 S 35 S 36</p> <p style="text-align: center;">2017</p> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p> <p>Set a steel fence post alongside and E. of cor.</p>
80.30	<p>Point for the cor. of secs. 35 and 36 only, at intersection with the N. bdy. of T. 26 N., R. 29 E.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 18 ins. in the ground to sandstone bedrock, in a mound of stone, 3 ft. base, to top, with brass cap mkd.</p> <p style="text-align: center;">T 27 N R 29 E S 35 S 36 S 1 T 26 N</p> <p style="text-align: center;">2017</p> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p> <p>Set a steel fence post alongside and N. of cor.</p> <p>From this cor. point, the 1/4 sec. cor. of sec. 1 only, T. 26 N., R. 29 E., bears S. 89°57' E., 39.62 chs. dist., hereinbefore described.</p> <p>From this same cor. point, the cor. of secs. 1 and 2 only, T. 26 N., R. 29 E., bears N. 89°57' W., 71 lks. dist., hereinbefore described.</p> <hr/> <p>Point for the 1/4 sec. cor. of sec. 36 only, T. 27 N., R. 29 E., at midpoint on the S. bdy. of sec. 36.</p> <p>Set a stainless steel stem, 17 ins. long, 9/16 ins. diam., 13 ins. in the ground, cemented in a drill hole, in sandstone bedrock, encircled with a collar of stone, with 3 1/2 ins. diam. brass tablet mkd.</p>

Survey of a Portion of the Subdivisional Lines,
T. 27 N., R. 29 E., Gila and Salt River Meridian, Arizona

CHAINS	
	T 27 N R 29 E 1/4 S 36 <hr style="width: 20%; margin: auto;"/> S 1 T 26 N 2017
	<p>Deposit a magnet, in a white plastic case, at the base of the stainless steel stem.</p> <p>Set a steel fence post alongside and N. of cor.</p> <p>From this cor. point, the cor. of Tps. 26 and 27 N., Rs. 29 and 30 E., bears S. 89°58' E., 40.0 chs. dist., hereinbefore described.</p> <p>From this same cor. point, the 1/4 sec. cor. of sec. 1 only, T. 26 N., R. 29 E., bears N. 89°58' W., 39 lks. dist., hereinbefore described.</p> <hr/> <p>From the cor. of secs. 25, 26, 35, and 36, on the governing section line, hereinbefore described.</p> <p>N. 0°01' W., bet. secs. 25 and 26.</p> <p>Through gently rolling, forested land.</p>
40.00	<p>Point for the 1/4 sec. cor. of secs. 25 and 26.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 12 ins. in the ground, in a supporting mound of stone, 5 ft. base, to top, with brass cap mkd.</p>
	T 27 N R 29 E 1/4 S 26 S 25 2017
80.00	<p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p> <p>Set a steel fence post, in the same supporting mound of stone, alongside, W. of cor.</p> <p>Point for the cor. of secs. 23, 24, 25, and 26.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 18 ins. in the ground to bedrock, in a mound of stone, 4 ft. base, to top, with brass cap mkd.</p>

Survey of a Portion of the Subdivisional Lines,
T. 27 N., R. 29 E., Gila and Salt River Meridian, Arizona

CHAINS							
	<table style="margin: auto;"> <tr> <td>T 27 N</td> <td>R 29 E</td> </tr> <tr> <td>S 23</td> <td>S 24</td> </tr> <tr> <td>S 26</td> <td>S 25</td> </tr> </table>	T 27 N	R 29 E	S 23	S 24	S 26	S 25
T 27 N	R 29 E						
S 23	S 24						
S 26	S 25						
	2017						
	<p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p> <p>Set a steel fence post, in the same mound of stone, alongside, W. of cor.</p> <hr/> <p>From the cor. of secs. 19, 24, 25, and 30, on the E. bdy. of the Tp., monumented with a stainless steel post, 2 1/2 ins. diam., firmly set, projecting 3 ins. above ground, with brass cap mkd. T27N R29E R30E S24 S19 S25 S30 1989.</p> <p>from which the 1989 bearing trees</p> <p style="padding-left: 40px;">A ponderosa pine, 16 ins. diam., bears N. 54 3/4° E., 157 lks. dist., with scribe marks T27N R30E S19 BT visible on partially open blaze. (Record: 157 1/2 lks.)</p> <p style="padding-left: 40px;">A ponderosa pine, 18 ins. diam., bears S. 87° E., 140 lks. dist., with scribe marks T27N R30E S30 BT visible on open blaze. (Record: 139 1/2 lks.)</p> <p style="padding-left: 40px;">A ponderosa pine, 19 ins. diam., bears S. 16 3/4° W., 92 lks. dist., with scribe marks T27N R29E S25 BT visible on partially open blaze. (Record: 90 1/2 lks.)</p> <p style="padding-left: 40px;">A ponderosa pine, 22 ins. diam., bears N. 9° W., 82 lks. dist., with scribe marks T27N R29E S24 BT visible on partially open blaze. (Record: N. 8 3/4° W., 83 lks.)</p> <p>Add the marks 2017 to the brass cap.</p> <p>N. 89°44' W., bet. secs. 24 and 25.</p> <p>Through gently rolling, forested land.</p>						
14.15	BIA Route 201, Sawmill Road, a bladed dirt road, 25 ft. wide, bears N. 15° E. and S. 15° W.						
39.99	<p>Point for the 1/4 sec. cor. of secs. 24 and 25.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 25 ins. in the ground, with brass cap mkd.</p>						

Survey of a Portion of the Subdivisional Lines,
T. 27 N., R. 29 E., Gila and Salt River Meridian, Arizona

CHAINS	
	<p style="text-align: center;">T 27 N R 29 E S 24 1/4 ——— S 25</p> <p style="text-align: center;">2017</p>
	<p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p>
	<p>Set a steel fence post alongside and N. of cor.</p>
79.98	<p>The cor. of secs. 23, 24, 25, and 26.</p> <hr/>
	<p>N. 0°01' W., bet. secs. 23 and 24.</p>
	<p>Through gently rolling, forested land.</p>
40.00	<p>Point for the 1/4 sec. cor. of secs. 23 and 24.</p>
	<p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 20 ins. in the ground to bedrock, in a mound of stone, 3 ft. base, to top, with brass cap mkd.</p>
	<p style="text-align: center;">T 27 N R 29 E 1/4 S 23 S 24</p> <p style="text-align: center;">2017</p>
	<p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p>
	<p>Set a steel fence post, in the same mound of stone, alongside, W. of cor.</p>
80.00	<p>Point for the cor. of secs. 13, 14, 23, and 24.</p>
	<p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with brass cap mkd.</p>
	<p style="text-align: center;">T 27 N R 29 E S 14 S 13 S 23 S 24</p> <p style="text-align: center;">2017</p>
	<p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p>

Survey of a Portion of the Subdivisional Lines,
T. 27 N., R. 29 E., Gila and Salt River Meridian, Arizona

CHAINS	
	<p>Set a steel fence post alongside and W. of cor.</p> <hr/> <p>From the cor. of secs. 13, 18, 19, and 24, on the E. bdy. of the Tp., monumented with a stainless steel post, 2 1/2 ins. diam., firmly set, projecting 3 ins. above ground, with brass cap mkd. T27N R29E R30E S13 S18 S24 S19 1989.</p> <p>from which the 1989 bearing trees</p> <p>A ponderosa pine, 18 ins. diam., bears N. 36 3/4° E., 104 lks. dist., with scribe marks T27N R30E S18 BT visible on partially open blaze.</p> <p>A ponderosa pine, 15 ins. diam., bears S. 47 1/2° E., 140 lks. dist., with scribe marks T27N R30E S19 BT visible on open blaze. (Record: 140 1/2 lks.)</p> <p>A charred living ponderosa pine, 10 ins. diam., bears S. 54 3/4° W., 48 lks. dist., with scribe marks T27N R29E S24 BT visible on partially open blaze. (Record: 49 1/2 lks.)</p> <p>A ponderosa pine, 28 ins. diam., bears N. 6° W., 107 lks. dist., with scribe marks T27N R29E S13 BT visible on partially open blaze.</p> <p>Add the marks 2017 to the brass cap.</p> <p>N. 89°44' W., bet. secs. 13 and 24.</p> <p>Through gently rolling, forested land.</p>
39.98	<p>Point for the 1/4 sec. cor. of secs. 13 and 24.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center;"> <p>T 27 N R 29 E</p> <p>S 13</p> <p>1/4 ———</p> <p>S 24</p> <p>2017</p> </div> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p> <p>Set a steel fence post alongside and N. of cor.</p>
79.97	<p>The cor. of secs. 13, 14, 23, and 24.</p> <hr/> <p>N. 0°01' W., bet. secs. 13 and 14.</p>

Survey of a Portion of the Subdivisional Lines,
T. 27 N., R. 29 E., Gila and Salt River Meridian, Arizona

CHAINS	
	Through gently rolling, forested land.
40.00	Point for the 1/4 sec. cor. of secs. 13 and 14. Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd. <div style="text-align: center;"> T 27 N R 29 E 1/4 S 14 S 13 2017 </div>
	Deposit a magnet, in a white plastic case, at the base of the stainless steel post.
	Set a steel fence post alongside and W. of cor.
80.00	Point for the cor. of secs. 11, 12, 13, and 14. Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 21 ins. in the ground, encircled with a collar of stone, with brass cap mkd. <div style="text-align: center;"> T 27 N R 29 E S 11 S 12 S 14 S 13 2017 </div>
	Deposit a magnet, in a white plastic case, at the base of the stainless steel post.
	Set a steel fence post alongside and W. of cor.
	<hr/> From the cor. of secs. 7, 12, 13, and 18, on the E. bdy. of the Tp., monumented with a stainless steel post, 2 1/2 ins. diam., firmly set, projecting 3 ins. above ground, with brass cap mkd. T27N R29E R30E S12 S7 S13 S18 1989. from which the 1989 bearing trees
	<div style="padding-left: 40px;"> A ponderosa pine, 25 ins. diam., bears N. 34 1/4° E., 258 lks. dist., with scribe marks 27N R30E S7 BT visible on partially open blaze. </div>
	<div style="padding-left: 40px;"> A stump hole to dead and downed ponderosa pine, 11 ins. diam., bears S. 39 1/4° E., 68 lks. dist., with scribe marks T27N R30E S18 BT visible on open blaze. (Record: 67 lks.) </div>

Survey of a Portion of the Subdivisional Lines,
T. 27 N., R. 29 E., Gila and Salt River Meridian, Arizona

CHAINS	
	<p>A ponderosa pine, 12 ins. diam., bears S. 55 1/2° W., 150 lks. dist., with a healed blaze.</p> <p>A ponderosa pine, 15 ins. diam., bears N. 78 1/4° W., 96 lks. dist., with a healed blaze.</p> <p>Add the marks 2017 to the brass cap.</p> <p>N. 89°44' W., bet. secs. 12 and 13.</p> <p>Through gently rolling, forested land.</p>
39.98	<p>Point for the 1/4 sec. cor. of secs. 12 and 13.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 19 ins. in the ground to bedrock, in a mound of stone, 5 ft. base, to top, with brass cap mkd.</p> <div style="text-align: center;"> <p>T 27 N R 29 E</p> <p>S 12</p> <p>1/4 ———</p> <p>S 13</p> <p>2017</p> </div> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p> <p>Set a steel fence post, in the same mound of stone, alongside, N. of cor.</p>
79.97	<p>The cor. of secs. 11, 12, 13, and 14.</p> <hr/> <p>N. 0°01' W., bet. secs. 11 and 12.</p> <p>Through gently rolling, forested land.</p>
40.00	<p>Point for the 1/4 sec. cor. of secs. 11 and 12.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 23 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center;"> <p>T 27 N R 29 E</p> <p>1/4</p> <p>S 11 S 12</p> <p>2017</p> </div> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p> <p>Set a steel fence post alongside and W. of cor.</p>

Survey of a Portion of the Subdivisional Lines,
T. 27 N., R. 29 E., Gila and Salt River Meridian, Arizona

CHAINS							
80.00	<p>Point for the cor. of secs. 1, 2, 11, and 12.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 23 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center;"> <table style="border-collapse: collapse; margin: auto;"> <tr> <td style="padding: 0 10px;">T 27 N</td> <td style="border-left: 1px solid black; padding: 0 10px;">R 29 E</td> </tr> <tr> <td style="border-bottom: 1px solid black; padding: 0 10px;">S 2</td> <td style="border-left: 1px solid black; border-bottom: 1px solid black; padding: 0 10px;">S 1</td> </tr> <tr> <td style="padding: 0 10px;">S 11</td> <td style="border-left: 1px solid black; padding: 0 10px;">S 12</td> </tr> </table> </div> <p style="text-align: center;">2017</p> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p> <p>Set a steel fence post alongside and W. of cor.</p> <hr style="width: 50%; margin: 10px auto;"/> <p>From the cor. of secs. 1, 6, 7, and 12, on the E. bdy. of the Tp., monumented with a stainless steel post, 2 1/2 ins. diam., firmly set, projecting 3 ins. above ground, with brass cap mkd. T27N R29E R30E S1 S6 S12 S7 1989.</p> <p>from which the 1989 bearing trees</p> <ul style="list-style-type: none"> A ponderosa pine, 18 ins. diam., bears N. 48° E., 112 lks. dist., with a healed blaze. A ponderosa pine, 21 ins. diam., bears S. 64 1/2° E., 144 lks. dist., with scribe marks T27N R30E S7 BT visible on open blaze. (Record: S. 65° E., 143 1/2 lks.) A ponderosa pine, 25 ins. diam., bears S. 38 3/4° W., 113 lks. dist., with scribe marks T27N R29E S12 BT visible on partially open blaze. A ponderosa pine, 30 ins. diam., bears N. 20 1/2° W., 67 lks. dist., with scribe marks T27N R29E S1 BT visible on partially open blaze. (Record: N. 21° W., 66 lks.) <p>Add the marks 2017 to the brass cap.</p> <p>N. 89°44' W., bet. secs. 1 and 12.</p> <p>Through gently rolling, forested land.</p>	T 27 N	R 29 E	S 2	S 1	S 11	S 12
T 27 N	R 29 E						
S 2	S 1						
S 11	S 12						
23.30	<p>BIA Route 201, Sawmill Road, a bladed dirt road, 25 ft. wide, bears S. 15° E. and N. 15° W.</p>						
39.98	<p>Point for the 1/4 sec. cor. of secs. 1 and 12.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with brass cap mkd.</p>						

Survey of a Portion of the Subdivisional Lines,
T. 27 N., R. 29 E., Gila and Salt River Meridian, Arizona

CHAINS	
	T 27 N R 29 E S 1 1/4 ——— S 12 2017
	Deposit a magnet, in a white plastic case, at the base of the stainless steel post. Set a steel fence post alongside and N. of cor.
79.96	The cor. of secs. 1, 2, 11, and 12. <hr/> N. 0°02' W., bet. secs. 1 and 2. Through gently rolling, forested land.
40.00	Point for the 1/4 sec. cor. of secs. 1 and 2. Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 23 ins. in the ground, with brass cap mkd.
	T 27 N R 29 E 1/4 S 2 S 1 2017
	Deposit a magnet, in a white plastic case, at the base of the stainless steel post. Set a steel fence post alongside and W. of cor.
79.98	The cor. of secs. 1, 2, 35, and 36, on the N. bdy. of the Tp., hereinbefore described. <hr/> From the cor. of secs. 26, 27, 34, and 35, on the governing section line, hereinbefore described. S. 0°01' E., bet. secs. 34 and 35. Through gently rolling, forested land.
40.00	Point for the 1/4 sec. cor. of secs. 34 and 35. Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 23 ins. in the ground, with brass cap mkd.

Survey of a Portion of the Subdivisional Lines,
T. 27 N., R. 29 E., Gila and Salt River Meridian, Arizona

CHAINS	
	T 27 N R 29 E 1/4 S 34 S 35 2017
	Deposit a magnet, in a white plastic case, at the base of the stainless steel post.
	Set a steel fence post alongside and W. of cor.
79.68	Point for the cor. of secs. 34 and 35 only, at intersection with the N. bdy. of T. 26 N., R. 29 E.
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.
	T 27 N R 29 E S 34 S 35 ----- S 2 T 26 N 2017
	Deposit a magnet, in a white plastic case, at the base of the stainless steel post.
	Set a steel fence post alongside and N. of cor.
	From this cor. point, the 1/4 sec. cor. of sec. 2 only, T. 26 N., R. 29 E., bears S. 89°21' E., 39.11 chs. dist., hereinbefore described.
	From this same cor. point, the cor. of secs. 2 and 3 only, T. 26 N., R. 29 E., bears N. 89°21' W., 59.5 lks. dist., hereinbefore described.
	<hr/> Point for the 1/4 sec. cor. of sec. 35 only, T. 27 N., R. 29 E., at midpoint on the S. bdy. of sec. 35.
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 23 ins. in the ground, with brass cap mkd.
	T 27 N R 29 E 1/4 S 35 ----- S 2 T 26 N 2017

Survey of a Portion of the Subdivisional Lines,
T. 27 N., R. 29 E., Gila and Salt River Meridian, Arizona

CHAINS	
	<p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p> <p>Set a steel fence post alongside and N. of cor.</p> <p>From this cor. point, the cor. of secs. 1 and 2 only, T. 26 N., R. 29 E., bears S. 89°13' E., 39.3 chs. dist., hereinbefore described.</p> <p>From this same cor. point, the 1/4 sec. cor. of sec. 2 only, T. 26 N., R. 29 E., bears N. 89°13' W., 89 lks. dist., hereinbefore described.</p> <hr/> <p>From the cor. of secs. 27, 28, 33, and 34, on the governing section line, hereinbefore described.</p> <p>S. 0°02' E., bet. secs. 33 and 34.</p> <p>Through gently rolling, forested land.</p>
40.00	<p>Point for the 1/4 sec. cor. of secs. 33 and 34.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T 27 N R 29 E 1/4 S 33 S 34 2017</p>
80.03	<p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p> <p>Set a steel fence post alongside and W. of cor.</p> <p>Point for the cor. of secs. 33 and 34 only, at intersection with the N. bdy. of T. 26 N., R. 29 E.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T 27 N R 29 E S 33 S 34 <hr/>S 3 T 26 N 2017</p> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p>

Survey of a Portion of the Subdivisional Lines,
T. 27 N., R. 29 E., Gila and Salt River Meridian, Arizona

CHAINS	
	<p>Set a steel fence post alongside and N. of cor.</p> <p>From this cor. point, the 1/4 sec. cor. of sec. 3 only, T. 26 N., R. 29 E., bears N. 89°59' E., 39.04 chs. dist., hereinbefore described.</p> <p>From this same cor. point, the cor. of secs. 3 and 4 only, T. 26 N., R. 29 E., bears S. 89°59' W., 1.28 chs. dist., hereinbefore described.</p> <hr/> <p>Point for the 1/4 sec. cor. of sec. 34 only, T. 27 N., R. 29 E., at midpoint on the S. bdy. of sec. 34.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 21 ins. in the ground to bedrock, in a mound of stone, 4 ft. base, to top, with brass cap mkd.</p> <p style="text-align: center;">T 27 N R 29 E 1/4 S 34</p> <hr style="width: 20%; margin: auto;"/> <p style="text-align: center;">S 3 T 26 N</p> <p style="text-align: center;">2017</p> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p> <p>Set a steel fence post alongside and N. of cor.</p> <p>From this cor. point, the cor. of secs. 2 and 3 only, T. 26 N., R. 29 E., bears S. 89°59' E., 39.4 chs. dist., hereinbefore described.</p> <p>From this same cor. point, the 1/4 sec. cor. of sec. 3 only, T. 26 N., R. 29 E., bears N. 89°59' W., 96 lks. dist., hereinbefore described.</p> <hr/> <p>From the cor. of secs. 28, 29, 32, and 33, on the governing section line, hereinbefore described.</p> <p>S. 0°03' E., bet. secs. 32 and 33.</p> <p>Through gently rolling, forested land.</p>
4.50	Kinlichee Canyon Creek, Bear Canyon, 30 ft. wide, 1 ft. deep, drains N. 65° W.
40.00	Point for the 1/4 sec. cor. of secs. 32 and 33.

Survey of a Portion of the Subdivisional Lines,
T. 27 N., R. 29 E., Gila and Salt River Meridian, Arizona

CHAINS	
80.22	<p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 14 ins. in the ground to bedrock, in a supporting mound of stone, 4 ft. base, to top, with brass cap mkd.</p> <p style="text-align: center;">T 27 N R 29 E 1/4 S 32 S 33</p> <p style="text-align: center;">2017</p> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p> <p>Set a steel fence post alongside and NE of cor.</p> <p>Point for the cor. of secs. 33 and 34 only, at intersection with the N. bdy. of T. 26 N., R. 29 E.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 22 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T 27 N R 29 E S 32 S 33 S 4 T 26 N</p> <p style="text-align: center;">2017</p> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p> <p>Set a steel fence post alongside and N. of cor.</p> <p>From this cor. point, the 1/4 sec. cor. of sec. 4 only, T. 26 N., R. 29 E., bears S. 89°43' E., 38.39 chs. dist., hereinbefore described.</p> <p>From this same cor. point, the cor. of secs. 4 and 5 only, T. 26 N., R. 29 E., bears N. 89°43' W., 1.89 chs. dist., hereinbefore described.</p> <hr/> <p>Point for the 1/4 sec. cor. of sec. 33 only, T. 27 N., R. 29 E., at midpoint on the S. bdy. of sec. 33.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 25 ins. in the ground, with brass cap mkd.</p>

Survey of a Portion of the Subdivisional Lines,
T. 27 N., R. 29 E., Gila and Salt River Meridian, Arizona

CHAINS	
	T 27 N R 29 E 1/4 S 33 <hr style="width: 20%; margin: auto;"/> S 4 T 26 N 2017
	Deposit a magnet, in a white plastic case, at the base of the stainless steel post. Set a steel fence post alongside and N. of cor. From this cor. point, the cor. of secs. 3 and 4 only, T. 26 N., R. 29 E., bears N. 89°59' E., 38.72 chs. dist., hereinbefore described. From this same cor. point, the 1/4 sec. cor. of sec. 4 only, T. 26 N., R. 29 E., bears S. 89°59' W., 1.61 chs. dist., hereinbefore described.
	<hr/> From the cor. of secs. 29, 30, 31, and 32, on the governing section line, hereinbefore described. S. 0°03' E., bet. secs. 31 and 32. Through gently rolling, forested land.
40.00	Point for the 1/4 sec. cor. of secs. 31 and 32. Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd. <div style="text-align: center;"> T 27 N R 29 E 1/4 S 31 S 32 2017 </div>
	Deposit a magnet, in a white plastic case, at the base of the stainless steel post. Set a steel fence post alongside and W. of cor.
54.70	N. right-of-way fence of Arizona State Highway 264, barbed wire, 5 strand, parallels highway.
56.30	Arizona State Highway 264, asphalt surfaced, 39 ft. wide, bears S. 70° E. and N. 70° W.
57.90	S. right-of-way fence of Arizona State Highway 264, barbed wire, 5 strand, parallels highway.

Survey of a Portion of the Subdivisional Lines,
T. 27 N., R. 29 E., Gila and Salt River Meridian, Arizona

CHAINS																					
80.10	<p>Point for the cor. of secs. 31 and 32 only, at intersection with the N. bdy. of T. 26 N., R. 29 E.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 20 ins. in the ground to bedrock, in a mound of stone, 3 ft. base, to top, with brass cap mkd.</p> <div style="text-align: center;"> <table style="margin: auto;"> <tr> <td>T 27 N</td> <td>R 29 E</td> </tr> <tr> <td>S 31</td> <td>S 32</td> </tr> <tr> <td colspan="2" style="border-top: 1px solid black;"></td> </tr> <tr> <td colspan="2" style="text-align: center;">S 5</td> </tr> <tr> <td colspan="2" style="text-align: center;">T 26 N</td> </tr> </table> <p>2017</p> </div> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p> <p>Set a steel fence post alongside and N. of cor.</p> <p>From this cor. point, the 1/4 sec. cor. of sec. 5 only, T. 26 N., R. 29 E., bears S. 89°40' E., 37.78 chs. dist., hereinbefore described.</p> <p>From this same cor. point, the cor. of secs. 5 and 6 only, T. 26 N., R. 29 E., bears N. 89°40' W., 2.56 chs. dist., hereinbefore described.</p> <hr/> <p>Point for the 1/4 sec. cor. of sec. 32 only, T. 27 N., R. 29 E., at midpoint on the S. bdy. of sec. 32.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center;"> <table style="margin: auto;"> <tr> <td>T 27 N</td> <td>R 29 E</td> </tr> <tr> <td>1/4</td> <td>S 32</td> </tr> <tr> <td colspan="2" style="border-top: 1px solid black;"></td> </tr> <tr> <td colspan="2" style="text-align: center;">S 5</td> </tr> <tr> <td colspan="2" style="text-align: center;">T 26 N</td> </tr> </table> <p>2017</p> </div> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p> <p>Set a steel fence post alongside and N. of cor.</p> <p>From this cor. point, the cor. of secs. 4 and 5 only, T. 26 N., R. 29 E., bears S. 89°40' E., 38.11 chs. dist., hereinbefore described.</p>	T 27 N	R 29 E	S 31	S 32			S 5		T 26 N		T 27 N	R 29 E	1/4	S 32			S 5		T 26 N	
T 27 N	R 29 E																				
S 31	S 32																				
S 5																					
T 26 N																					
T 27 N	R 29 E																				
1/4	S 32																				
S 5																					
T 26 N																					

**Survey of a Portion of the Subdivisional Lines,
T. 27 N., R. 29 E., Gila and Salt River Meridian, Arizona**

CHAINS	
	<p>From this same cor. point, the 1/4 sec. cor. of sec. 5 only, T. 26 N., R. 29 E., bears N. 89°40' W., 2.22 chs. dist., hereinbefore described.</p> <hr/> <p>Point for the 1/4 sec. cor. of sec. 31 only, T. 27 N., R. 29 E., at midpoint on the S. bdy. of sec. 31.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T 27 N R 29 E 1/4 S 31</p> <hr style="width: 20%; margin: auto;"/> <p style="text-align: center;">S 6 T 26 N</p> <p style="text-align: center;">2017</p> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p> <p>Set a steel fence post alongside and N. of cor.</p> <p>Cor. is located 50 lks. E. of two track road, bears N. 65° E. and S. 65° W.</p> <p>From this cor. point, the cor. of secs. 5 and 6 only, T. 26 N., R. 29 E., bears S. 89°40' E., 37.44 chs. dist., hereinbefore described.</p> <p>From this same cor. point, the 1/4 sec. cor. of sec. 6 only, T. 26 N., R. 29 E., bears N. 89°40' W., 2.89 chs. dist., hereinbefore described.</p> <hr/> <p style="text-align: center;">Subdivision of Section 1, T. 27 N., R. 29 E., Gila and Salt River Meridian, Arizona</p> <hr/> <p>From the 1/4 sec. cor. of secs. 1 and 12.</p> <p>N. 0°01' W., on the N. and S. center line of sec. 1.</p> <p>Through gently rolling, forested land.</p>
40.00	<p>Point for the center 1/4 sec. cor. of sec. 1, at intersection with the E. and W. center line.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 22 ins. in the ground, encircled with a collar of stone, with brass cap mkd.</p>

Subdivision of Section 1,
T. 27 N., R. 29 E., Gila and Salt River Meridian, Arizona

CHAINS	
	T 27 N R 29 E C 1/4 S 1 2017
	Deposit a magnet, in a white plastic case, at the base of the stainless steel post. Set a steel fence post alongside and W. of cor.
79.98	The 1/4 sec. cor. of secs. 1 and 36, on the N. bdy. of the Tp. <hr/> From the 1/4 sec. cor. of secs. 1 and 6, on the E. bdy. of the Tp., monumented with a stainless steel post, 2 1/2 ins. diam., firmly set, projecting 4 ins. above ground, with brass cap mkd. T27N R29E R30E 1/4 S1 S6 1989. from which the 1989 bearing trees A ponderosa pine, 16 ins. diam., bears N. 77 1/2° E., 95 lks. dist., with a healed blaze. A partially decomposed ponderosa pine stump, 22 ins. diam., 38 ins. high, bears S. 88 1/2° W., 107 lks. dist., with no visible blaze. Add the marks 2017 to the brass cap. N. 89°44' W., on the E. and W. center line of sec. 1. Through gently rolling, forested land.
35.75	BIA Route 201, Sawmill Road, a bladed dirt road, 25 ft. wide, bears S. 15° E. and N. 15° W.
39.99	The center 1/4 sec. cor. of sec. 1.
79.98	The 1/4 sec. cor. of secs. 1 and 2. <hr/> <p style="text-align: center;">Subdivision of Section 12, T. 27 N., R. 29 E., Gila and Salt River Meridian, Arizona</p> <hr/> From the 1/4 sec. cor. of secs. 12 and 13. North, on the N. and S. center line of sec. 12. Through gently rolling, forested land.
40.00	Point for the center 1/4 sec. cor. of sec. 12, at intersection with the E. and W. center line.

Subdivision of Section 12,
T. 27 N., R. 29 E., Gila and Salt River Meridian, Arizona

CHAINS	
	<p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 18 ins. in the ground to bedrock, in a mound of stone, 5 ft. base, to top, with brass cap mkd.</p> <p style="text-align: center;">T 27 N R 29 E C 1/4 S 12</p> <p style="text-align: center;">2017</p> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p> <p>Set a steel fence post, in the same mound of stone, alongside, W. of cor.</p>
80.00	<p>The 1/4 sec. cor. of secs. 1 and 12.</p> <hr/> <p>From the 1/4 sec. cor. of secs. 7 and 12, on the E. bdy. of the Tp., monumented with a stainless steel post, 2 1/2 ins. diam., firmly set, projecting 4 ins. above ground, with brass cap mkd. T27N R29E R30E 1/4 S12 S7 1989.</p> <p>from which the 1989 bearing trees</p> <p style="padding-left: 40px;">A ponderosa pine, 17 ins. diam., bears S. 51 1/2° E., 158 1/2 lks. dist., with scribe marks 1/4 S7 BT visible on partially open blaze.</p> <p style="padding-left: 40px;">A ponderosa pine, 18 ins. diam., bears S. 25° W., 63 lks. dist., with scribe marks 1/4 S12 BT visible on partially open blaze. (Record: 62 lks.)</p> <p>Add the marks 2017 to the brass cap.</p> <p>N. 89°44' W., on the E. and W. center line of sec. 12.</p> <p>Through gently rolling, forested land.</p>
10.55	<p>BIA Route 201, Sawmill Road, a bladed dirt road, 25 ft. wide, bears S. 20° E. and N. 20° W.</p>
39.98	<p>The center 1/4 sec. cor. of sec. 12.</p>
79.97	<p>The 1/4 sec. cor. of secs. 11 and 12.</p> <hr/> <p style="text-align: center;">Subdivision of Section 24, T. 27 N., R. 29 E., Gila and Salt River Meridian, Arizona</p> <hr/> <p>From the 1/4 sec. cor. of secs. 24 and 25.</p> <p>N. 0°01' W., on the N. and S. center line of sec. 24.</p>

Subdivision of Section 24,
T. 27 N., R. 29 E., Gila and Salt River Meridian, Arizona

CHAINS	
	Through gently rolling, forested land.
40.00	Point for the center 1/4 sec. cor. of sec. 24, at intersection with the E. and W. center line. Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 19 ins. in sandstone bedrock, in a mound of stone, 5 ft. base, to top, with brass cap mkd. T 27 N R 29 E C 1/4 S 24 2017 Deposit a magnet, in a white plastic case, at the base of the stainless steel post. Set a steel fence post, in the same mound of stone, alongside, W. of cor.
80.00	The 1/4 sec. cor. of secs. 13 and 24. <hr/> From the 1/4 sec. cor. of secs. 19 and 24, on the E. bdy. of the Tp., monumented with a stainless steel post, 2 1/2 ins. diam., firmly set, projecting 4 ins. above ground, with brass cap mkd. T27N R29E R30E 1/4 S24 S19 1989. from which the 1989 bearing trees A decomposed ponderosa pine stump, 20 ins. diam., bears N. 72 1/2° E., 109 1/2 lks. dist., with no visible blaze. A ponderosa pine, 22 ins. diam., bears N. 77° W., 27 lks. dist., with a healed blaze. (Record: N. 78 1/4° W., 27 1/2 lks.) Add the marks 2017 to the brass cap. N. 89°44' W., on the E. and W. center line of sec. 24. Through gently rolling, forested land.
3.65	BIA Route 201, Sawmill Road, a bladed dirt road, 25 ft. wide, bears N. 15° E. and S. 15° W.
39.98	The center 1/4 sec. cor. of sec. 24.
79.97	The 1/4 sec. cor. of secs. 23 and 24. <hr/>

Subdivision of Section 25,
T. 27 N., R. 29 E., Gila and Salt River Meridian, Arizona

CHAINS	
	<p>From the 1/4 sec. cor. of secs. 25 and 36.</p> <p>N. 0°01' W., on the N. and S. center line of sec. 25.</p> <p>Through gently rolling, forested land.</p>
40.00	<p>Point for the center 1/4 sec. cor. of sec. 25, at intersection with the E. and W. center line.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 25 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T 27 N R 29 E C 1/4 S 25</p> <p style="text-align: center;">2017</p> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p> <p>Set a steel fence post alongside and W. of cor. in center of an accessory mound of stone, 4 ft. base, 2 ft. high.</p>
80.00	<p>The 1/4 sec. cor. of secs. 24 and 25.</p> <hr/> <p>From the 1/4 sec. cor. of secs. 25 and 30, on the E. bdy. of the Tp., monumented with a stainless steel post, 2 1/2 ins. diam., firmly set, projecting 3 ins. above ground, with brass cap mkd. T27N R29E R30E 1/4 S25 S30 1989.</p> <p>from which the 1989 bearing trees</p> <p style="padding-left: 40px;">A ponderosa pine, 23 ins. diam., bears N. 41 3/4° E., 61 1/2 lks. dist., with a healed blaze. (Record: N. 41 1/4° E.)</p> <p style="padding-left: 40px;">A ponderosa pine, 18 ins. diam., bears N. 69 1/4° W., 91 1/2 lks. dist., with scribe marks 1/4 S25 BT visible on partially open blaze. (Record: 92 lks.)</p> <p>Add the marks 2017 to the brass cap.</p> <p>N. 89°44' W., on the E. and W. center line of sec. 25.</p> <p>Through gently rolling, forested land.</p>
23.70	<p>BIA Route 201, Sawmill Road, a bladed dirt road, 25 ft. wide, bears N. 15° E. and S. 15° W.</p>
40.00	<p>The center 1/4 sec. cor. of sec. 24.</p>

Subdivision of Section 25,
T. 27 N., R. 29 E., Gila and Salt River Meridian, Arizona

CHAINS	
79.99	<p>The 1/4 sec. cor. of secs. 25 and 26.</p> <hr/> <p style="text-align: center;">Subdivision of Section 31, T. 27 N., R. 29 E., Gila and Salt River Meridian, Arizona</p> <hr/> <p>From the 1/4 sec. cor. of sec. 31 only, on the S. bdy. of the Tp.</p> <p>N. 0°03' W., on the N. and S. center line of sec. 31.</p> <p>Through gently rolling, forested land.</p>
35.10	S. right-of-way fence of Arizona State Highway 264, barbed wire, 5 strand, parallels highway.
36.70	Arizona State Highway 264, asphalt surfaced, 39 ft. wide, bears S. 70° E. and N. 70° W.
38.25	N. right-of-way fence of Arizona State Highway 264, barbed wire, 5 strand, parallels highway.
40.06	<p>Point for the center 1/4 sec. cor. of sec. 31, at intersection with the E. and W. center line.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T 27 N R 29 E C 1/4 S 31</p> <p style="text-align: center;">2017</p> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p> <p>Set a steel fence post alongside and N. of cor.</p> <p>Cor. is located 1.81 chs. S. of the N. right-of-way fence of Arizona State Highway 264, barbed wire, 5 strand, bears S. 70° E. and N. 70° W.</p>
80.06	<p>The 1/4 sec. cor. of secs. 30 and 31.</p> <hr/> <p>From the 1/4 sec. cor. of secs. 31 and 32.</p> <p>N. 89°44' W., on the E. and W. center line of sec. 31.</p> <p>Through gently rolling, forested land.</p>
40.00	The center 1/4 sec. cor. of sec. 31.

Subdivision of Section 31,
T. 27 N., R. 29 E., Gila and Salt River Meridian, Arizona

CHAINS	
45.70	N. right-of-way fence of Arizona State Highway 264, barbed wire, 5 strand, parallels highway.
50.75	Arizona State Highway 264, asphalt surfaced, 39 ft. wide, bears S. 70° E. and N. 70° W.
55.75	S. right-of-way fence of Arizona State Highway 264, barbed wire, 5 strand, parallels highway.
82.42	The 1/4 sec. cor. of secs. 31 and 36, on the W. bdy. of the Tp., monumented with a stainless steel post, 2 1/2 ins. diam., firmly set, projecting 5 ins. above ground, with brass cap mkd. T27N R28E R29E 1/4 S36 S31 2003. Add the marks 2017 to the brass cap.
<hr/> <p style="text-align: center;">Subdivision of Section 32, T. 27 N., R. 29 E., Gila and Salt River Meridian, Arizona</p> <hr/>	
	From the 1/4 sec. cor. of sec. 32 only, on the S. bdy. of the Tp.
	N. 0°03' W., on the N. and S. center line of sec. 32.
	Through gently rolling, forested land.
8.00	S. right-of-way fence of Arizona State Highway 264, barbed wire, 5 strand, parallels highway.
9.60	Arizona State Highway 264, asphalt surfaced, 39 ft. wide, bears S. 70° E. and N. 70° W.
11.20	N. right-of-way fence of Arizona State Highway 264, barbed wire, 5 strand, parallels highway.
40.16	Point for the center 1/4 sec. cor. of sec. 32, at intersection with the E. and W. center line.
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 17 ins. in the ground to bedrock, in a supporting mound of stone, 4 ft. base, to top, with brass cap mkd.
	T 27 N R 29 E C 1/4 S 32
	2017
	Deposit a magnet, in a white plastic case, at the base of the stainless steel post.
	Set a steel fence post, in the same mound of stone, alongside, N. of cor.

Subdivision of Section 32,
T. 27 N., R. 29 E., Gila and Salt River Meridian, Arizona

CHAINS	
80.16	<p>The 1/4 sec. cor. of secs. 29 and 32.</p> <hr/> <p>From the 1/4 sec. cor. of secs. 32 and 33.</p> <p>N. 89°45' W., on the E. and W. center line of sec. 32.</p> <p>Through gently rolling, forested land.</p>
40.00	The center 1/4 sec. cor. of sec. 32.
80.00	<p>The 1/4 sec. cor. of secs. 31 and 32.</p> <hr/> <p style="text-align: center;">Subdivision of Section 36, T. 27 N., R. 29 E., Gila and Salt River Meridian, Arizona</p> <hr/> <p>From the 1/4 sec. cor. of sec. 36 only, on the S. bdy. of the Tp.</p> <p>North, on the N. and S. center line of sec. 36.</p> <p>Through gently rolling, forested land.</p>
40.16	<p>Point for the center 1/4 sec. cor. of sec. 36, at intersection with the E. and W. center line.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 11 ins. in the ground to bedrock, in a supporting mound of stone, 4 1/2 ft. base, to top, with brass cap mkd.</p> <p style="text-align: center;">T 27 N R 29 E C 1/4 S 36</p> <p style="text-align: center;">2017</p> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p> <p>Set a steel fence post, in the same mound of stone, alongside, W. of cor.</p> <p>Cor. is located 2.85 chs. E. of BIA Route 201, Sawmill Road, a bladed dirt road, 25 ft. wide, bears N. 15° E. and S. 15° W.</p>
52.05	BIA Route 201, Sawmill Road, a bladed dirt road, 25 ft. wide, bears N. 15° E. and S. 15° W.
80.16	<p>The 1/4 sec. cor. of secs. 25 and 36.</p> <hr/>

Subdivision of Section 36,
T. 27 N., R. 29 E., Gila and Salt River Meridian, Arizona

CHAINS	
	<p>From the 1/4 sec. cor. of secs. 31 and 36, on the E. bdy. of the Tp., monumented with a stainless steel post, 2 1/2 ins. diam., firmly set, projecting 5 ins. above ground, with brass cap mkd. T27N R29E R30E 1/4 S36 S31 1989.</p> <p>from which the 1989 bearing trees</p> <p style="padding-left: 40px;">A ponderosa pine, 22 ins. diam., bears S. 66 3/4° E., 159 lks. dist., with a healed blaze. (Record: 160 lks.)</p> <p style="padding-left: 40px;">A ponderosa pine, 19 ins. diam., bears S. 48 3/4° W., 146 lks. dist., with scribe marks 1/4 S36 BT visible on partially open blaze. (Record: 145 1/2 lks.)</p> <p>Add the marks 2017 to the brass cap.</p> <p>Set a steel fence post alongside and W. of cor.</p> <p>N. 89°44' W., on the E. and W. center line of sec. 36.</p> <p>Through gently rolling, forested land.</p>
40.00	The center 1/4 sec. cor. of sec. 36.
80.00	The 1/4 sec. cor. of secs. 35 and 36.
	<hr/>

T. 27 N., R. 29 E., Gila and Salt River Meridian, Arizona

CHAINS

GENERAL DESCRIPTION

The area surveyed is approximately 9 miles northwest of St. Michaels, Arizona, within the Navajo Indian Reservation. The terrain is mostly gently rolling forested land. The main drainage is Kinlichee Canyon Creek, also known as Bear Canyon, which drains westerly through the southern portion of the township.

The elevation ranges from 7,425 to 8,025 feet above sea level, the soil is predominately rocky clay with sandstone bedrock. Timber consists of ponderosa pine, piñon, juniper, and Gambel oak. The undergrowth predominately consists of native grasses and yucca.

Arizona State Highway 264, an asphalt road, provides access through the southwestern portion of the township. In sections 31 and 32. BIA Route 201, also known as Sawmill Road, a bladed dirt road, runs northerly, through the last tier of the township, providing access to the rest of the township via two track roads branching throughout the township. ATV's were required to access the exterior township lines, and portions of the interior township.

Much of the area is utilized for grazing livestock. There is no underground gas pipelines or high voltage transmission lines in the township. There are no major housing developments, only a few clustered residential houses along Arizona State Highway 264.

The mean magnetic declination of $9 \frac{3}{4}^{\circ}$ E. was derived from the United States Geological Survey computer program GEOMAG, utilizing the World Magnetic Model for Epoch 2010-2015 for the dates of survey.

CERTIFICATE OF SURVEY

I, Fabian Yazzie, Cadastral Surveyor, HEREBY CERTIFY upon honor, that in pursuance of special instructions bearing date of the 11th day of September, 2017, I have resurveyed the north boundary, Township 26 North, Range 29 East, and surveyed the north boundary, governing section line, and a portion of the subdivisional lines, and subdivided certain sections, T. 27 N., R. 29 E., of the Gila and Salt River Meridian, in the State of Arizona, which are represented in the foregoing field notes as having been executed by me and under my direction. Said survey has been made in strict conformity with said special instructions, the Manual of Instructions for the Survey of the Public Lands of the United States, 2009, and in specific manner described in the foregoing field notes.

6/07/2018
(Date)

[Signature]
(Cadastral Surveyor)

CERTIFICATE OF APPROVAL

BUREAU OF LAND MANAGEMENT
Phoenix, Arizona

The foregoing field notes of the resurvey of the north boundary, Township 26 North, Range 29 East, and the survey of the north boundary, governing section line, and a portion of the subdivisional lines, and the subdivision of certain sections, T. 27 N., R. 29 E., Gila and Salt River Meridian, in the State of Arizona, executed by Fabian Yazzie, Cadastral Surveyor, having been critically examined and found correct, are hereby approved.

6/11/2018
(Date)

[Signature]
(Chief Cadastral Surveyor of Arizona)

CERTIFICATE OF TRANSCRIPT

I CERTIFY That the foregoing transcript of the field notes of the above described surveys in T. 27 N., R. 29 E., Gila and Salt River Meridian, Arizona, is a true copy of the original field notes.

(Date)

(Chief Cadastral Surveyor of Arizona)