

ORIGINAL

**UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT**

FIELD NOTES
OF THE
DEPENDENT RESURVEY OF A PORTION OF THE NORTH BOUNDARY,
AND
THE CORRECTIVE RESURVEY OF THE
EAST BOUNDARY,
PORTIONS OF THE SUBDIVISIONAL LINES,
AND
THE SUBDIVISION OF CERTAIN SECTIONS,
TOWNSHIP 22 NORTH, RANGE 29 EAST,
OF THE GILA AND SALT RIVER MERIDIAN,
IN THE STATE OF ARIZONA.

EXECUTED BY

Fabian Yazzie, Supervisory Cadastral Surveyor

Under Special Instructions dated May 3, 2017, approved May 3, 2017, which provided for the surveys included under Group No. 1170, and assignment instructions dated May 3, 2017.

Survey commenced July 6, 2017

Survey completed January 31, 2018

INDEX DIAGRAM

TOWNSHIP 22 NORTH RANGE 29 EAST
 GILA & SALT RIVER MERIDIAN, ARIZONA

R30E

						21	
6	5	4	3	2	1	19	20
7	8	9	10	11	12	16	18
18	17	16	15	41	14	34	15
					42	34	
					41	13	14
19	20	21	22	23	31	24	11
					39	27	
30	29	28	27	37	26	25	7
					36	23	
31	32	33	34	35	36	4	5

Subdivision of Section 14 Pages 42-43
 Subdivision of Section 24 Pages 44-75
 Subdivision of Section 25 Pages 75-83
 Subdivision of Section 26 Pages 83-90

T. 22 N., R. 29 E., Gila and Salt River Meridian, Arizona

CHAINS

The following field notes describe the dependent resurvey of a portion of the north boundary, and the corrective resurvey of the east boundary, portions of the subdivisional lines, and the subdivision of certain sections, Township 22 North, Range 29 East, Gila and Salt River Meridian, Arizona.

The history of surveys pertaining to this survey is as follows:

The Seventh Auxiliary Guide Meridian East (west boundary), the south, east, and north boundaries, and the subdivisional lines, were surveyed by W.R. Fitzgerald, in 1882. The Indian Allotments in this township, were surveyed by W.M. Peterson and A.W. Simington, in 1909-1910. The north boundary was dependently resurveyed by Sidney E. Blout, in 1920. A portion of the east boundary was dependently resurveyed, by Stephen J. Malloy, in 1987-1993. The Seventh Auxiliary Guide Meridian East (west boundary), the south, and east boundaries, a portion of the subdivisional lines, and subdivision of certain sections, were dependently resurveyed, and metes-and-bounds surveys were executed, by Adrien J. Rodriguez, in 2004-2005. A portion of the east boundary was dependently resurveyed, by Adrien J. Rodriguez and Leonard R. Sandoval, in 2005-2007. The corrective resurvey of portions of the south boundary, by Fabian Yazzie, in 2015.

Existing monuments were recovered and clearly have been long relied upon by the residents of the area. Research conclusively identifies these monuments were established as a result of surveys conducted by the Indian Service, under the federal authority of the act of February 8, 1887. No official records of the actual surveys have been recovered. This research is detailed in a letter to Group No. 957, dated September 23, 2015, and the basis for a corrective resurvey is detailed in a letter to this group file, dated May 2, 2017.

The extent of the examinations and retracements made in the execution of this survey are limited in scope to those detailed within this volume of field notes. Within this township, and others, there may exist other similar situations which have yet to be examined and/or addressed.

The survey was executed in accordance with the specifications as set forth in the Manual of Instructions for the Survey of the Public Lands of the United States, 2009, and the Special Instructions dated May 3, 2017, for Group Number 1170, Arizona.

The true meridian direction and length of all lines were determined by real time kinematic global positioning system observations using Trimble Navigation R8 model receivers.

T. 22 N., R. 29 E., Gila and Salt River Meridian, Arizona

CHAINS

Preliminary to the resurvey, the lines of the prior surveys were retraced and search was made for all corners and other calls of record. Identified corners were remonumented in their original positions. Due to the differences between the General Land Office records and the recovered monuments of the Indian Service surveys, lost corners were reestablished and remonumented in accordance with the best available evidence of the lines actually run on the ground, having been relied upon by allottees and their descendants in good faith. All evidence of the 2004-2007 corners were removed, and remonumented to protect the bona fide rights of the patentees, relying on long standing occupation lines and evidence of the Indian Service surveys. The retracement data were thoroughly verified and only the true line field notes are given herein.

Geodetic control was derived from Global Positioning System (GPS) static observations post processed by National Geodetic Survey, Online Positioning User Service (OPUS), utilizing Continuously Operating Reference Stations (CORS) DH4513 P015 DUECECLUBSAZ2005 CORS ARP, DI0438 NMGR GRANTS NMDOT CORS ARP, AND DI2266 P107 GRANTS_NM2006 CORS ARP. The NAD 83 (2011) (EPOCH: 2010), geographic position of the corner of Townships 21 and 22 North, Range 29 East only, is as follows:

Latitude: 35°15'15.277" N. Longitude: 109°12'38.584" W.

The geographic position of the corner of secs. 10, 11, 14, and 15, is as follows:

Latitude: 35°18'43.443" N. Longitude: 109°14'41.378" W.

The mean magnetic declination is 9 1/2° E.

**Corrective Resurvey of the East Boundary,
T. 22 N., R. 29 E., Gila and Salt River Meridian, Arizona**

Restoring the survey executed by
W.M. Peterson and A.W. Simington, in 1909-1910,
and correcting and amending the dependent resurvey
executed by A.J. Rodriguez in 2004-2005

Beginning at the cor. of Tps. 21 and 22 N., R. 29 E. only, monumented with a stainless steel post, 2 1/2 ins. diam., firmly set, projecting 2 ins. above ground, with brass cap mkd. T22N T21N R29E R30E S36 S6 S1 T21N 2015. Add the marks 2017 to the brass cap.

Cor. is located in a barbed wire fence, 3 strand, bears N. and S.

N. 0°02' E., over gently rolling land.

Corrective Resurvey of the East Boundary,
T. 22 N., R. 29 E., Gila and Salt River Meridian, Arizona

CHAINS	
3.93	<p>The cor. of Tps. 21 and 22 N., R. 30 E. only, monumented with a stainless steel post, 2 1/2 ins. diam., firmly set, projecting 4 ins. above ground, with brass cap mkd. T22N T22N R29E R30E S36 S31 S6 T21N 2004 1993 2015. Add the marks 2017 to the brass cap.</p> <p>Cor. is located at the base of wood fence cor. post of fences, barbed wire, 4 strand, extending E. and S.</p> <hr/> <p>N. 0°02' W., beginning new measurement.</p> <p>Over gently rolling land.</p>
35.88	<p>Point for the 1/4 sec. cor. of sec. 36 only, T. 22 N., R. 29 E., determined latitudinally at mid-point between the cor. of Tps. 21 and 22 N., R. 29 E. only, and the cor. of secs. 25 and 36 only, T. 22 N., R. 29 E., established in this survey, and longitudinally on the E. bdy. of the Tp.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center;"> <p>T 22 N R 29 E R 30 E 1/4 S 36 S 31</p> <p>2017</p> </div> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p> <p>Set a steel fence post alongside and N. of cor.</p>
40.15	<p>The 1/4 sec. cor. of secs. 31 and 36, T. 22 N., Rs. 29 and 30 E., established in 1993, monumented with a stainless steel post, 2 1/2 ins. diam., firmly set, projecting 3 ins. above ground, with a steel fence post alongside, with brass cap mkd. T22N 1/4 R29E R30E S36 S31 1993 2004.</p> <p>This cor. now functions as the 1/4 sec. cor. of sec. 31 only, T. 22 N., R. 30 E.</p> <p>Remark the brass cap to read</p> <div style="text-align: center;"> <p>T 22 N R 29 E R 30 E 1/4 S 36 S 31</p> <p>2017</p> </div> <hr/> <p>N. 0°01' W., beginning new measurement.</p>

**Corrective Resurvey of the East Boundary,
T. 22 N., R. 29 E., Gila and Salt River Meridian, Arizona**

CHAINS	
17.55	Apache County Road No. 7240, Allentown Road, a graded road, 25 ft. wide, bears S. 80° E. and N. 80° W.
35.55	<p>Point for the cor. of secs. 25 and 36 only, T. 22 N., R. 29 E., at intersection with the E. bdy., determined east from the cor. of secs. 25, 26, 35, and 36, T. 22 N., R. 29 E., hereinafter described.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center;"> <pre> T 22 N R 29 E R 30 E S 25 --- S 31 S 36 2017 </pre> </div> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p> <p>Set a steel fence post alongside and W. of cor.</p> <p>Cor. is located 22 lks. W. of a series of wood posts in a dilapidated fence, with barbed wire strands on the ground, bears N. and S.</p> <p>From this cor. point, the terminus to a series of wooden hubs, extends S., parallel to the aforementioned wood fence posts, bears S. 02°47' E., 1.20 chs. dist.</p> <hr/> <p>N. 0°01' W., bet. secs. 25 and 31.</p> <p>Over nearly level land.</p>
4.64	<p>The cor. of secs. 25, 30, 31, and 36, T. 22 N., Rs. 29 and 30 E., established in 2004, monumented with a stainless steel post, 2 1/2 ins. diam., firmly set, projecting 3 ins. above ground, with a steel fence post alongside, with brass cap mkd. T22N R29E R30E S25 S30 S36 S31 2004.</p> <p>This cor. now functions as the cor. of secs. 30 and 31 only, T. 22 N., R. 30 E.</p> <p>Remark the brass cap to read</p>

Corrective Resurvey of the East Boundary,
T. 22 N., R. 29 E., Gila and Salt River Meridian, Arizona

CHAINS													
	<table style="margin: auto;"> <tr><td></td><td style="text-align: center;">T 22 N</td><td></td></tr> <tr><td style="text-align: center;">R 29 E</td><td style="border-left: 1px solid black; border-right: 1px solid black; text-align: center;">R 30 E</td><td></td></tr> <tr><td></td><td style="border-left: 1px solid black; border-right: 1px solid black; text-align: center;">S 30</td><td></td></tr> <tr><td style="text-align: center;">S 25</td><td style="border-left: 1px solid black; border-right: 1px solid black; text-align: center;">S 31</td><td></td></tr> </table>		T 22 N		R 29 E	R 30 E			S 30		S 25	S 31	
	T 22 N												
R 29 E	R 30 E												
	S 30												
S 25	S 31												
	2017												
	Cor. is located 23 lks. S. of left bank of the Puerco River, 15 ft. high, bears N. 45° E. and S. 45° W.												
	From this cor. point, the wood fence cor. post of dilapidated fences, extends E. and S., bears S. 72°11' E., 24.7 lks. dist.												

	N. 0°27' E., beginning new measurement.												
	Crossing the oxbow of the Puerco River.												
19.50	Right bank of the Puerco River, 15 ft. high, bears N. 80° E. and S. 80° W.												
21.65	S. right-of-way fence of the Burlington Northern Santa Fe Rail Road, barbed wire, 4 strand, bears N. 85° E. and S. 85° W.												
27.75	N. right-of-way fence of the Burlington Northern Santa Fe Rail Road, at wood fence cor. post of barbed wire fences, 4 strand, bears N. 01° E., N. 85° E., and S. 85° W.												
34.62	The 1/4 sec. cor. of sec. 25 only, T. 22 N., R. 29 E., monumented with a juniper post, 43 ins. long, 3 1/2 ins. diam., firmly set, projecting 13 ins. above ground, faintly mkd. 1/4 on west face. Accepted as the best available evidence of the orig. cor. position.												
	At the corner point												
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.												
	<table style="margin: auto;"> <tr><td></td><td style="text-align: center;">T 22 N</td><td></td></tr> <tr><td style="text-align: center;">R 29 E</td><td style="border-left: 1px solid black; border-right: 1px solid black; text-align: center;">1/4</td><td></td></tr> <tr><td></td><td style="border-left: 1px solid black; border-right: 1px solid black; text-align: center;">S 25</td><td></td></tr> </table>		T 22 N		R 29 E	1/4			S 25				
	T 22 N												
R 29 E	1/4												
	S 25												
	2017												
	Deposit a magnet, in a white plastic case, at the base of, and bury the juniper post, alongside the stainless steel post.												
	Cor. is located 5 lks. E. of a woven and barbed wire fence, bears N. and S.												


	N. 0°48' W., beginning new measurement.												

**Corrective Resurvey of the East Boundary,
T. 22 N., R. 29 E., Gila and Salt River Meridian, Arizona**

CHAINS	
	Over gently rolling land.
5.35	<p>The 1/4 sec. cor. of secs. 25 and 30, T. 22 N., Rs. 29 and 30 E., established in 2004, monumented with a stainless steel post, 2 1/2 ins. diam., firmly set, projecting 5 ins. above ground, with brass cap mkd. T22N R29E R30E 1/4 S25 S30 2004.</p> <p>This cor. now functions as the 1/4 sec. cor. of sec. 30 only, T. 22 N., R. 30 E.</p> <p>Remark the brass cap to read</p> <div style="text-align: center;"> <pre> T 22 N R 30 E 1/4 S 30 </pre> </div> <p style="text-align: center;">2017</p> <p>Cor. is located at the base of wood fence cor. post of fences, barbed wire, 4 strand, extending N. 01° E., E., and S.</p> <hr style="width: 20%; margin: 10px auto;"/> <p>N. 0°07' W., beginning new measurement.</p> <p>Over gently rolling land.</p>
24.35	S. right-of-way fence of S. Frontage Road to Interstate 40, barbed wire, 5 strand, bears N. 60° E. and S. 60° W.
25.90	S. Frontage Road to Interstate 40, an asphalt surfaced road, 30 ft. wide, bears N. 60° E. and S. 60° W.
27.35	S. right-of-way fence of Interstate 40, barbed wire, 5 strand, bears N. 65° E. and S. 65° W.
30.70	Interstate 40 east bound lane, an asphalt surfaced road, bears N. 89° E. and S. 89° W.
34.43	<p>The cor. of secs. 24 and 25 only, T. 22 N., R. 29 E., monumented with a rebar, 18 ins. long, 5/8 ins. diam., firmly set, flush with the surface of the ground, with orange flagging around the top. Accepted as the best available evidence and perpetuation of the orig. cor. position and a perpetuation of the monument shown on the 1962 Arizona Highway Department Right-of-Way Map of Holbrook-Lupton Interstate HWY. 40, Drawing Number A-I-T-222A.</p> <p>At the corner point</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 9 ins. below the surface of the ground, with brass cap mkd.</p>

Corrective Resurvey of the East Boundary,
T. 22 N., R. 29 E., Gila and Salt River Meridian, Arizona

CHAINS



from which

A galvanized PK nail, 2 1/2 ins. long, 1/4 in. diam., set flush in the NE cemented embankment of St. Anselm Road overpass, for a reference monument, bears N. 83°21' W., 228.1 ft. dist. with 1 1/2 in. diam. brass washer mkd. BLM 2017.

Deposit a magnet, in a white plastic case, and the rebar, at the base of the stainless steel post.

Set an orange carsonite post alongside and W. of cor.

Cor. is located 13.6 lks. N. of the N. asphalt edge of Interstate 40 west bound lane, bears E. and W.

N. 0°12' E., bet. secs. 24 and 30.

Through Houck Interchange and Interstate 40 exit ramp.

4.55 Interstate 40 west bound exit ramp, an asphalt surfaced road, 22 ft. wide, bears S. 55° E. and N. 55° W.

4.90 N. right-of-way fence of Interstate 40, barbed wire, 5 strand, bears S. 50° E. and N. 50° W.

5.50 N. Frontage Road to Interstate 40, an asphalt surfaced road, 25 ft. wide, bears S. 50° E. and N. 50° W.

5.76 Point for the cor. of secs. 19 and 30 only, T. 22 N., R. 30 E., at the intersection of the W. bdy., determined by the extension of bearing from the cors. of secs. 19, 20, 29, and 30, T. 22 N., R. 30 E., and the 1/4 sec. cor. of secs. 19 and 30, T. 22 N., R. 30 E., both described in the official record of the corrective resurvey of a portion of the subdivisional lines, T. 22 N., R. 30 E., executed concurrently under this same group. There is no remaining evidence of the 2004 cor.

Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 6 ins. below the surface of the ground, with brass cap mkd.

**Corrective Resurvey of the East Boundary,
T. 22 N., R. 29 E., Gila and Salt River Meridian, Arizona**

CHAINS

T 22 N	
R 29 E	R 30 E
	S 19
S 24	S 30

2017

from which

A rebar, 24 ins. long, 5/8 ins. diam., set 23 ins. in the ground for a reference monument, bears N. 45°00' E., 40.0 ft. dist. with 2 in. diam. brass cap mkd. RM T22N R30E 40.0 FT TO COR S19 2017 and an arrow pointing to the cor.

A rebar, 24 ins. long, 5/8 ins. diam., set flush with the surface of the ground for a reference monument, bears S. 45°00' E., 288.0 ft. dist. with 2 in. diam. brass cap mkd. RM T22N R30E 288.0 FT TO COR S30 2017 and an arrow pointing to the cor.

Deposit a magnet, in a white plastic case, at the base of the stainless steel post.

Cor. is located at the N. edge of N. Frontage Road to Interstate 40, an asphalt surfaced road, 25 ft. wide, bears S. 50° E. and N. 50° W.

From this cor. point, the wood fence cor. post of barbed wire fences for the N. right-of-way of the N. Frontage Road to Interstate 40, 4 strand fence extends N. and 5 strand fence extends E., bears N. 01°56' E., 1.14 chs. dist.

From this same cor. point, a rebar, 1/2 in. diam., firmly set, projecting 2 ins. above ground, at the base of chain link fence cor. post of enclosed fencing to Houck Chapter House, extends N. and W., with yellow plastic cap mkd., RLS 48459, bears N. 69°03' W., 7.76 chs. dist.

20.01

Point for the S. 1/16 sec. cor. of sec. 24 only, T. 22 N., R. 29 E., determined at proportionate distance between the cor. of secs. 24 and 25 only, T. 22 N., R. 29 E., and the 1/4 sec. cor. of sec. 24 only, T. 22 N., R. 29 E., established in this survey. Remove 2004 cor. and reset at the true point.

Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.

Corrective Resurvey of the East Boundary,
T. 22 N., R. 29 E., Gila and Salt River Meridian, Arizona

CHAINS	
	<p style="text-align: center;">T 22 N R 29 E S 1/16 S 24 </p> <p style="text-align: center;">2017</p> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p> <p>Cor. is located 16 lks. W. of a dilapidated barbed wire fence, 4 strand, bears N. and S. 01° W.</p>
40.49	<p>The 1/4 sec. cor. of sec. 24 only, T. 22 N., R. 29 E., monumented with a sandstone, 17 x 15 x 4 ins., firmly set, projecting 10 ins. above ground, with illegible marks on west face. Accepted as the best available evidence of the orig. cor. position.</p> <p>At the corner point</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 19 ins. in the ground to bedrock, encircled with a collar of stone, 2 ft. base, to top, with brass cap mkd.</p>
	<p style="text-align: center;">T 22 N R 29 E 1/4 S 24 </p> <p style="text-align: center;">2017</p> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post, and incorporate stone into collar of stone.</p> <p>Cor. is located in barbed wire fence, 4 strand, bears. N. and S.</p> <hr style="width: 20%; margin: 10px auto;"/> <p>N. 0°04' E., beginning new measurement.</p> <p>Over rolling land, through juniper and pine.</p>
5.21	<p>Point for the 1/4 sec. cor. of sec. 19 only, T. 22 N., R. 30 E., determined latitudinally at mid-point between cor. of secs. 19 and 30 only, T. 22 N., R. 30 E. and the cor. of secs. 18 and 19 only, T. 22 N., R. 30 E., established in this survey, and longitudinally on the W. bdy. of the Tp. Remove 2004 cor. and reset at the true point.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 25 ins. in the ground, with brass cap mkd.</p>

Corrective Resurvey of the East Boundary,
T. 22 N., R. 29 E., Gila and Salt River Meridian, Arizona

CHAINS	
	<p style="text-align: center;">T 22 N R 30 E 1/4 S 19</p> <p style="text-align: center;">2017</p> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p> <p>Cor. is located 3 lks. E. of barbed wire fence, 4 strand, bears N. and S.</p> <p>8.45 Barbed wire fence, 4 strand, bears N. 85° E. and S. 85° W. to wood fence cor. post of terminating N. and S. fence.</p> <p>18.53 Point for AP 2, sec. 19 only, T. 22 N., R. 30 E., determined on the W. bdy. of the Tp., and at two thirds of a distance, as stated in the warranty deed description, Parcel No. 2, Docket 390, pages 376-377, dated June 6, 1982, filed in Apache County, Arizona. Remove 2007 cor. and reset at the true point.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 23 ins. in the ground, with brass cap mkd.</p>
	<p style="text-align: center;">T 22 N R 30 E S 19 AP 2</p> <p style="text-align: center;">2017</p> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p> <p>19.97 Point for the N. 1/16 sec. cor. of sec. 24 only, T. 22 N., R. 29 E., determined at mid-point distance between the 1/4 sec. cor. of sec. 24 only, T. 22 N., R. 29 E., and the cor. of secs. 13 and 24 only, T. 22 N., R. 29 E., established in this survey. Remove 2004 cor. and reset at the true point.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 25 ins. in the ground, with brass cap mkd.</p>
	<p style="text-align: center;">T 22 N R 29 E N 1/16 S 24 </p> <p style="text-align: center;">2017</p> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p>

Corrective Resurvey of the East Boundary,
T. 22 N., R. 29 E., Gila and Salt River Meridian, Arizona

CHAINS									
	Set a steel fence post alongside and W. of cor.								
25.18	<p>Point for the N. 1/16 sec. cor. of sec. 19 only, T. 22 N., R. 30 E., determined at mid-point distance between the 1/4 sec. cor. of sec. 19 only, T. 22 N., R. 30 E., and the cor. of secs. 18 and 19 only, T. 22 N., R. 30 E., established in this survey.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center;"> <table style="border-collapse: collapse; margin: auto;"> <tr><td colspan="2">T 22 N</td></tr> <tr><td style="border-right: 1px solid black; padding-right: 5px;">R 30 E</td><td></td></tr> <tr><td style="border-right: 1px solid black; padding-right: 5px;">N 1/16</td><td></td></tr> <tr><td style="border-right: 1px solid black; padding-right: 5px;">S 19</td><td></td></tr> </table> <p>2017</p> </div> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p>	T 22 N		R 30 E		N 1/16		S 19	
T 22 N									
R 30 E									
N 1/16									
S 19									
39.945	<p>Point for the cor. of secs. 13 and 24 only, T. 22 N., R. 29 E., determined at proportionate distance between the 1/4 sec. cor. of sec. 24 only, T. 22 N., R. 29 E., and the cor. of secs. 12 and 13 only, T. 22 N., R. 29 E., established in this survey. Remove 2004 cor. and reset at the true point.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center;"> <table style="border-collapse: collapse; margin: auto;"> <tr><td colspan="2">T 22 N</td></tr> <tr><td style="border-right: 1px solid black; padding-right: 5px;">R 29 E</td><td style="padding-left: 5px;">R 30 E</td></tr> <tr><td style="border-right: 1px solid black; padding-right: 5px;">S 13</td><td></td></tr> <tr><td style="border-right: 1px solid black; padding-right: 5px;">S 24</td><td style="padding-left: 5px;">S 19</td></tr> </table> <p>2017</p> </div> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p> <p>Set a steel fence post alongside and W. of cor.</p> <p>Obliterate the markings on the 2004 accessory.</p> <p>Cor. is located 60 lks. N. and 25 lks. E. of St. Anselm Road, a graded road, 16 ft. wide, bears S. 25° E. and N. 25° W.</p> <p>From this cor. point, an embedded mound of stones, scattered to a 5 ft. diam., with no visible marks, and is not utilized in the course of this corrective resurvey, bears S. 61°52' E., 7.18 chs. dist.</p>	T 22 N		R 29 E	R 30 E	S 13		S 24	S 19
T 22 N									
R 29 E	R 30 E								
S 13									
S 24	S 19								

Corrective Resurvey of the East Boundary,
T. 22 N., R. 29 E., Gila and Salt River Meridian, Arizona

CHAINS							
	<p>From this same cor. point, an embedded mound of stones, 4 ft. diam., with no visible marks, and is not utilized in the course of this corrective resurvey, bears S. 65°30' W., 3.49 chs. dist.</p> <hr/> <p>N. 0°04' E., bet. secs. 13 and 19.</p> <p>Over rolling land, through juniper and pine.</p>						
5.21	<p>Point for the cor. of secs. 18 and 19 only, T. 22 N., R. 30 E., at intersection with the W. bdy., determined west from the cor. of secs. 17, 18, 19, and 20, T. 22 N., R. 30 E., described in the official record of the corrective resurvey of a portion of the subdivisional lines, T. 22 N., R. 30 E., executed concurrently under this same group.</p> <p>Set a brass tablet, 3 1/2 ins. diam., 2 1/4 ins. stem, cemented in a drill hole in a sandstone boulder, 5 x 5 x 3 ft., with top mkd.</p> <div style="text-align: center;"> <p>T 22 N</p> <table style="margin: auto;"> <tr> <td style="border-right: 1px solid black; padding-right: 5px;">R 29 E</td> <td style="padding-left: 5px;">R 30 E</td> </tr> <tr> <td style="border-right: 1px solid black; padding-right: 5px;"></td> <td style="padding-left: 5px;">S 18</td> </tr> <tr> <td style="border-right: 1px solid black; padding-right: 5px;"></td> <td style="padding-left: 5px;">S 19</td> </tr> </table> <p>2017</p> </div> <p>Deposit a magnet, in a white plastic case, at the base of the brass tablet.</p> <p>Cor. is located in the cut shelf of the aforementioned sandstone boulder, on the NW slope of hill, among sandstone rock outcrops.</p>	R 29 E	R 30 E		S 18		S 19
R 29 E	R 30 E						
	S 18						
	S 19						
19.85	<p>Barbed wire fence with leaning posts, not maintained, 2 strand, bears S. 55° E. and N. 55° W.</p>						
39.94	<p>Point for the 1/4 sec. cor. of sec. 13 only, T. 22 N., R. 29 E., determined at proportionate distance between the 1/4 sec. cor. of sec. 24 only, T. 22 N., R. 29 E., and the cor. of secs. 12 and 13 only, T. 22 N., R. 29 E., established in this survey. Remove 2004 cor. and reset at the true point.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 27 ins. in the ground, underpinned with a steel fence post, 60 ins. long, with brass cap mkd.</p> <div style="text-align: center;"> <p>T 22 N</p> <table style="margin: auto;"> <tr> <td style="border-right: 1px solid black; padding-right: 5px;">R 29 E</td> <td style="padding-left: 5px;">1/4</td> </tr> <tr> <td style="border-right: 1px solid black; padding-right: 5px;"></td> <td style="padding-left: 5px;">S 13</td> </tr> </table> <p>2017</p> </div>	R 29 E	1/4		S 13		
R 29 E	1/4						
	S 13						

Corrective Resurvey of the East Boundary,
T. 22 N., R. 29 E., Gila and Salt River Meridian, Arizona

CHAINS	
	<p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p> <p>Set a steel fence post alongside and W. of cor.</p> <p>Cor. is located 1.30 chs. S. of the main channel to Black Creek, 20 ft. wide, 15 ft. deep at left cut bank, drains S. 40° E., and is located 65 lks. W. and 1.30 chs. N. of the same main channel wash, 20 ft. wide, 15 ft. deep at left cut bank, drains S. 25° W.</p>
45.24	<p>Point for the 1/4 sec. cor. of sec. 18 only, T. 22 N., R. 30 E., determined latitudinally at mid-point between the cor. of secs. 18 and 19 only, T. 22 N., R. 30 E., and the cor. of secs. 7 and 18 only, T. 22 N., R. 30 E., established in this survey, and longitudinally on the W. bdy. of the Tp.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center;"> <p>T 22 N</p> <p style="margin-left: 40px;"> R 30 E</p> <p style="margin-left: 40px;"> 1/4</p> <p style="margin-left: 40px;"> S 18</p> </div> <p style="text-align: center;">2017</p> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p> <p>Set a steel fence post alongside and W. of cor.</p>
62.15	<p>Series of wood fence posts, no barbed wire, bears N. 70° E. and S. 70° W.</p>
62.94	<p>From this point, an embedded mound of stones, 5 ft. base, with a sandstone, firmly set in center of mound, projecting 9 ins. above ground, with no visible marks, is not utilized in the course of this corrective resurvey, bears W., 1.65 chs. dist.</p>
79.89	<p>The cor. of secs. 12 and 13 only, T. 22 N., R. 29 E., monumented with a juniper post, 38 ins. long, 4 x 4 ins. squared, firmly set, projecting 6 ins. above ground, with a rusted finishing nail on top center, encircled with scattered stones, mkd. 2 grooves on one face, and other faces partially decomposed. Accepted as the best available evidence of the orig. cor. position.</p> <p>At the corner point</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with brass cap mkd.</p>

Corrective Resurvey of the East Boundary,
T. 22 N., R. 29 E., Gila and Salt River Meridian, Arizona

CHAINS																																	
	<div style="text-align: center;"> <table border="0"> <tr><td></td><td>T 22 N</td><td></td></tr> <tr><td>R 29 E</td><td> </td><td>R 30 E</td></tr> <tr><td>S 12</td><td> </td><td></td></tr> <tr><td colspan="3"><hr/></td></tr> <tr><td>S 13</td><td> </td><td>S 18</td></tr> </table> <p>2017</p> </div> <p>Deposit a magnet, in a white plastic case, at the base of, and bury the juniper post, alongside the stainless steel post.</p> <p>Set a steel fence post alongside and W. of cor.</p> <p>Cor. is located 3 lks. N. of the N. edge of wash, 2 ft. wide, 1 ft. deep, drains N. 50° W., and is located 33 lks. S. and 32 lks. E. of two track road, bears N. 40° E. and S. 35° W.</p> <p>From this cor. point, the amended cor. of secs. 7, 12, 13, and 18, T. 22 N., Rs. 29 and 30 E, bears S. 75°01' E., 4.82 chs. dist., monumented with a stainless steel post, 2 1/2 ins. diam., firmly set, projecting 5 ins. above ground, with brass cap mkd. T22N R29E R30E S12 S7 S13 S18 2004. Add the marks AM to brass cap. No accessories to deface.</p> <hr/> <p>N. 0°04' E., bet. secs. 12 and 18.</p> <p>Over rolling land, through juniper and pine.</p> <p>2.90 Main channel of Black Creek, 10 ft. wide, 5 ft. deep, drains S. 65° W.</p> <p>5.38 Point for the cor. of secs. 7 and 18 only, T. 22 N., R. 30 E., at intersection with the W. bdy., determined west from the cor. of secs. 7, 8, 17, and 18, T. 22 N., R. 30 E., described in the official record of the corrective resurvey of a portion of the subdivisional lines, T. 22 N., R. 30 E., executed concurrently under this same group.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center;"> <table border="0"> <tr><td></td><td>T 22 N</td><td></td></tr> <tr><td>R 29 E</td><td> </td><td>R 30 E</td></tr> <tr><td></td><td> </td><td>S 7</td></tr> <tr><td>S 12</td><td> </td><td colspan="2"><hr/></td></tr> <tr><td></td><td> </td><td>S 18</td><td></td></tr> </table> <p>2017</p> </div> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p> <p>Set a steel fence post alongside and W. of cor.</p>		T 22 N		R 29 E		R 30 E	S 12			<hr/>			S 13		S 18		T 22 N		R 29 E		R 30 E			S 7	S 12		<hr/>				S 18	
	T 22 N																																
R 29 E		R 30 E																															
S 12																																	
<hr/>																																	
S 13		S 18																															
	T 22 N																																
R 29 E		R 30 E																															
		S 7																															
S 12		<hr/>																															
		S 18																															

Corrective Resurvey of the East Boundary,
T. 22 N., R. 29 E., Gila and Salt River Meridian, Arizona

CHAINS	
	<p style="text-align: center;">T 22 N R 30 E 1/4 S 7</p> <p style="text-align: center;">2017</p>
	<p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p>
	<p>Set a steel fence post alongside and E. of cor.</p>
39.70	<p>Right bank of Black Creek canyon, 20 ft. high, bears N. 25° E. and S. 20° W.</p>
41.01	<p>The cor. of secs. 1 and 12 only, T. 22 N., R. 29 E., monumented with a sandstone, 26 x 14 x 4 ins., firmly set in the upright position, projecting 24 ins. above ground, encircled with an embedded mound of stones, 5 ft. base, mkd. 1 groove on N. face, 5 grooves on S. face, and AI on E. face. Accepted as the best available evidence of the orig. cor. position.</p>
	<p>At the corner point</p>
	<p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 15 ins. in the ground to bedrock, in a supporting mound of stone, 5 ft. base, to top, with brass cap mkd.</p>
	<p style="text-align: center;">T 22 N R 29 E R 30 E S 1 ----- S 7 S 12 </p> <p style="text-align: center;">2017</p>
	<p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post, and incorporate found stone in the mound of stone.</p>
	<p>Set a steel fence post alongside and W. of cor., in the same mound of stone.</p>
	<p>Cor. is located 55 lks. W. of right bank of Black Creek canyon, 20 ft. high, bears N. 25° E. and S. 25° W.</p>
	<p>From this cor. point, the amended cor. of secs. 1, 6, 7, and 12, T. 22 N., Rs. 29 and 30 E., bears N. 77°58' E., 4.10 chs. dist., monumented with a brass tablet, 3 1/8 ins. diam., firmly set, 11 ins. below loose soil, flush with sandstone bedrock, with brass cap mkd. T22N R29E R30E S1 S6 S12 S7 2004. Add the marks AM to brass cap. No accessories to deface.</p> <hr/>

Corrective Resurvey of the East Boundary,
T. 22 N., R. 29 E., Gila and Salt River Meridian, Arizona

CHAINS											
	<p>N. 0°04' E., bet. secs. 1 and 7.</p> <p>Over rugged land, through juniper and pine.</p>										
6.14	<p>Point for the cor. of secs. 6 and 7 only, T. 22 N., R. 30 E., at intersection with the W. bdy., determined west from the cor. of secs. 5, 6, 7, and 8, T. 22 N., R. 30 E., described in the official record of the corrective resurvey of a portion of the subdivisional lines, T. 22 N., R. 30 E., executed concurrently under this same group.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center;"> <table style="margin: auto;"> <tr><td colspan="2">T 22 N</td></tr> <tr><td>R 29 E</td><td>R 30 E</td></tr> <tr><td></td><td>S 6</td></tr> <tr><td>S 1</td><td>_____</td></tr> <tr><td></td><td>S 7</td></tr> </table> <p>2017</p> </div> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p> <p>Set a steel fence post alongside and E. of cor.</p> <p>Cor. is located 2.25 chs. W. of right bank of Black Creek canyon, 10 ft. high, bears S. 10° W. and N. 05° W.</p>	T 22 N		R 29 E	R 30 E		S 6	S 1	_____		S 7
T 22 N											
R 29 E	R 30 E										
	S 6										
S 1	_____										
	S 7										
40.04	<p>Point for the 1/4 sec. cor. of sec. 1 only, T. 22 N., R. 29 E., determined at mid-point distance between the cor. of secs. 1 and 12 only, T. 22 N., R. 29 E., and the cor. of Tps. 22 N., Rs. 29 and 30 E., established in this survey.</p> <p>Set a rebar, 18 ins. long, 5/8 ins. diam., 14 ins. in the ground, with 2 in. diam. brass cap mkd.</p> <div style="text-align: center;"> <table style="margin: auto;"> <tr><td colspan="2">T 22 N</td></tr> <tr><td>R 29 E</td><td> </td></tr> <tr><td>1/4</td><td> </td></tr> <tr><td>S 1</td><td> </td></tr> </table> <p>2017</p> </div> <p>from which</p> <p style="margin-left: 40px;">A stainless steel post, 28 ins. long, 2 1/2 ins. diam., set 24 ins. in the ground for a reference monument, bears S. 60°00' W., 45.0 ft. dist. with brass cap mkd. RM T22N R29E 45.0 FT TO COR. 1/4 S1 2017 and an arrow pointing to the cor. Deposit a magnet, in a white plastic case, at the base of the stainless steel post, and set a steel fence post alongside and SW of cor.</p>	T 22 N		R 29 E		1/4		S 1			
T 22 N											
R 29 E											
1/4											
S 1											

**Corrective Resurvey of the East Boundary,
T. 22 N., R. 29 E., Gila and Salt River Meridian, Arizona**

CHAINS	
	<p>A stainless steel post, 28 ins. long, 2 1/2 ins. diam., set 23 ins. in the ground for a reference monument, bears N. 30°00' W., 55.0 ft. dist. with brass cap mkd. RM T22N R29E 55.0 FT TO COR. 1/4 S1 2017 and an arrow pointing to the cor. Deposit a magnet, in a white plastic case, at the base of the stainless steel post, and set a steel fence post alongside and NW of cor.</p> <p>Set a steel fence post alongside and W. of cor.</p> <p>Cor. is located in center of a wash, 6 ft. wide, 2 ft. deep, drains S. 15° W.</p> <p>From this cor. point, the amended 1/4 sec. cor. of secs. 1 and 6, T. 22 N., Rs. 29 and 30 E, bears N. 85°55' E., 4.57 chs. dist., monumented with a stainless steel post, 2 1/2 ins. diam., firmly set, projecting 4 ins. above mound of stone, 6 ft. base, 2 ft. high, with brass cap mkd. T22N R29E R30E 1/4 S1 S6 2004. Add the marks AM to brass cap. No accessories to deface.</p>
43.11	<p>Point for the 1/4 sec. cor. of sec. 6 only, T. 22 N., R. 30 E., determined latitudinally at mid-point between the cor. of secs. 6 and 7 only, T. 22 N., R. 30 E., and the cor. of Tps. 22 N., Rs. 29 and 30 E., established in this survey, and longitudinally on the W. bdy. of the Tp.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 27 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center;"> <p>T 22 N</p> <p> R 30 E</p> <p> 1/4</p> <p> S 6</p> <p>2017</p> </div> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p> <p>Set a steel fence post alongside and E. of cor.</p>
80.08	<p>Point for the cor. of Tps. 22 N., Rs. 29 and 30 E., at intersection with the N. bdy. of the Tp.</p> <p>At the true point of intersection</p> <p>Set a rebar, 22 ins. long, 5/8 ins. diam., 16 ins. cemented in a drill hole in a sandstone boulder, 16 x 6 x 6 ft., with 2 in. diam. brass cap mkd.</p>

**Corrective Resurvey of the East Boundary,
T. 22 N., R. 29 E., Gila and Salt River Meridian, Arizona**

CHAINS

T 23 N	R 29 E
S 36	

S 1	S 6
R 29 E	R 30 E
T 22 N	

2017

Deposit a magnet, without plastic case, at the base of rebar.

Set a steel fence post alongside and NW of cor.

Cor. is located on the W. face, uphill side of sandstone boulder.

From this cor. point, the cor. of Tps. 22 and 23 N., Rs. 29 and 30 E., bears S. 89°53' E., 4.28 chs. dist., established in 1920, monumented in 2004 with a stainless steel post, 2 1/2 ins. diam., firmly set, projecting 6 ins. above ground, encircled with a collar of stone, 4 ft. base, to top, with brass cap mkd. T23N R29E R30E S36 S31 S1 S6 T22N 2004.

This cor. now functions as the cor. of Tps. 23 N. only, Rs. 29 and 30 E.

Remark the brass cap to read

T 23 N	
R 29 E	R 30 E
S 36	S 31

S 6	
T 22 N	

2017

**Dependent Resurvey of a portion of the North Boundary,
T. 22 N., R. 29 E., Gila and Salt River Meridian, Arizona**

Restoring the resurvey executed by
Sidney E. Blout, in 1920

From the cor. of Tps. 22 N., Rs. 29 and 30 E., hereinbefore described.

N. 89°53' W., on the N. bdy. of the Tp.

Dependent Resurvey of a portion of the North Boundary,
T. 22 N., R. 29 E., Gila and Salt River Meridian, Arizona

CHAINS

35.85

The 1/4 sec. cor. of secs. 1 and 36, Tps. 22 and 23 N., R. 29 E., established in 1920, monumented with an iron post, 1 in. diam., firmly set, projecting 17 ins. above ground, in a supporting mound of stone, 2 1/2 ft. base, 2 ft. high, with brass cap mkd. T23N R29E S36 1/4 S1 T22N 1920.

This cor. now functions as the 1/4 sec. cor. of sec. 36 only, T. 23 N., R. 29 E.

Remark the brass cap to read

T 23 N R 29 E
1/4 S 36

S 1
T 22 N

2017

from which the 1920 bearing tree

A leaning forked juniper, 8 ins. diam., bears S. 5° E., 4 lks. dist., with scribe marks 1/4 S36 BT visible on partially open blaze.

Obliterate the markings S36 on the 1920 bearing tree.

S. 89°46' W., beginning new measurement.

1.85

Point for the 1/4 sec. cor. of sec. 1 only, T. 22 N., R. 29 E., determined longitudinally at midpoint between the newly established cor. of Tps. 22 N., Rs. 29 and 30 E., and the cor. of secs. 1, 2, 35, and 36, Tps. 22 and 23 N., R. 29 E., hereinafter described, and latitudinally on the N. bdy. of the Tp.

Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 25 ins. in the ground, with brass cap mkd.

T 23 N R 29 E
S 36

1/4 S 1
T 22 N

2017

Deposit a magnet, in a white plastic case, at the base of the stainless steel post.

Set a steel fence post alongside and S. of cor.

Dependent Resurvey of a portion of the North Boundary,
T. 22 N., R. 29 E., Gila and Salt River Meridian, Arizona

CHAINS

39.56

The cor. of secs. 1, 2, 35, and 36, Tps. 22 and 23 N., R. 29 E., established in 1920, monumented with an iron post, 2 ins. diam., firmly set, projecting 23 ins. above ground, in a supporting mound of stone, 2 ft. base, 1 1/2 ft. high, with brass cap mkd. T23N R29E S35 S36 S2 S1 T22N 2004 1920. Add the marks 2017 to the brass cap.

from which the 1920 bearing trees

A forked juniper, 16 ins. diam., bears N. 56° E., 1.37 chs. dist., with scribe marks on westerly limb T23NR29ES36BT visible on partially open blaze. (1920 Record: N. 55 1/4° E., 138 lks.)

A forked juniper, 10 ins. diam., bears S. 30° W., 68 lks. dist., with faint scribe marks T22NR29ES2BT visible on partially open blaze.

A forked juniper, 10 ins. diam., bears N. 39° W., 60 lks. dist., with faint scribe marks T23NR29ES35BT visible on partially open blaze. (1920 Record: N. 39 3/4° W., 59 lks.)

Corrective Resurvey of a Portion of the Subdivisional Lines,
T. 22 N., R. 29 E., Gila and Salt River Meridian, Arizona

Restoring the survey executed by
W.M. Peterson and A.W. Simington, in 1909-1910,
and correcting the dependent resurvey
executed by A.J. Rodriguez in 2004-2005

From the cor. of secs. 25 and 36 only, T. 22 N., R. 29 E., hereinbefore described.

West, over nearly level land.

18.31

Point for the E. 1/16 sec. cor. of secs. 25 and 36, determined at the intersection of the E-W sec. line of secs. 25 and 36, and the extension of bearing of the N-S barbed wire fence from the N. Remove 2004 cor. and reset at the true point.

Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 25 ins. in the ground, with brass cap mkd.

T 22 N R 29 E
S 25
E 1/16 ———
S 36

2017

Corrective Resurvey of a Portion of the Subdivisional Lines,
T. 22 N., R. 29 E., Gila and Salt River Meridian, Arizona

CHAINS	
	<p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p> <p>Set a steel fence post alongside and N. of cor.</p>
37.07	<p>Point for the 1/4 sec. cor. of secs. 25 and 36, determined at the intersection of the E-W sec. line of secs. 25 and 36, and the extension of bearing of the N-S barbed wire fence from the N. Remove 2004 cor. and reset at the true point.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T 22 N R 29 E S 25 1/4 ——— S 36</p> <p style="text-align: center;">2017</p> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p> <p>Set a steel fence post alongside and N. of cor.</p>
46.98	<p>Point for the E-W 1/64 sec. cor. of secs. 25 and 36, determined at the intersection of the E-W sec. line of secs. 25 and 36, and the extension of bearing of the N-S barbed wire fence from the N. Remove 2004 cor. and reset at the true point.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 25 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T 22 N R 29 E S 25 E-W 1/64 S 36</p> <p style="text-align: center;">2017</p> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p> <p>Set a steel fence post alongside and N. of cor.</p>
56.42	<p>Point for the W 1/16 sec. cor. of secs. 25 and 36, determined at the intersection of the E-W sec. line of secs. 25 and 36, and the extension of bearing of the N-S barbed wire fence from the N. Remove 2004 cor. and reset at the true point.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with brass cap mkd.</p>

Corrective Resurvey of a Portion of the Subdivisional Lines,
T. 22 N., R. 29 E., Gila and Salt River Meridian, Arizona


CHAINS	
	<p style="text-align: center;">T 22 N R 29 E S 25 W 1/16 ——— S 36</p> <p style="text-align: center;">2017</p>
	<p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p> <p>Set a steel fence post 10 lks. S. of cor., off of two track road.</p> <p>Cor. is located on the S. edge of two track road, bears S. 50° E. and N. 50° W.</p>
74.72	<p>The cor. of secs. 25, 26, 35, and 36, established in 2004, monumented with a stainless steel post, 2 1/2 ins. diam., firmly set, projecting 2 ins. above ground, with a steel fence post alongside to the N., with brass cap mkd. T22N R29E S26 S25 S35 S36 2004. The position of this cor. is consistent with recovered evidence described in the original 1882 survey of T. 29 N., R. 29 E., Book 449, P. 13, and reference to ties made to the J.W. Bennett Store, hereinafter described. Accepted as a careful and faithful reestablishment of the orig. cor. position.</p> <p>Add the marks 2017 to the brass cap.</p> <hr/>
	<p>N. 0°08' W., bet. secs. 25 and 26.</p> <p>Over nearly level land, through dense sage brush.</p>
19.89	<p>True point for the S. 1/16 sec. cor. of secs. 25 and 26, from this true point, a witness cor. for the S. 1/16 sec. cor. of secs. 25 and 26, bears N. 63°17' W., 4.69 chs. dist., established in 2004, monumented with a stainless steel post, 2 1/2 ins. diam., firmly set, projecting 3 ins. above ground, with a steel fence post alongside to the N., with brass cap mkd. WC T22N R29E S 1/16 S26 S25 2004.</p> <hr/>
19.89	<p>N. 0°08' W., beginning new measurement.</p> <p>The 1/4 sec. cor. of secs. 25 and 26, monumented in 2004 with a stainless steel post, 2 1/2 ins. diam., firmly set, projecting 4 ins. above ground, with a steel fence post alongside to the S., with brass cap mkd. T22N R29E 1/4 S26 S25 2004. Add the marks 2017 to the brass cap. Accepted as the best available evidence of the orig. cor. position.</p> <p>Cor. is located 1.60 chs. S. of a telephone line, bears S. 88° E. and N. 88° W.</p> <hr/>

Corrective Resurvey of a Portion of the Subdivisional Lines,
T. 22 N., R. 29 E., Gila and Salt River Meridian, Arizona

CHAINS	
	<p>N. 0°01' W., beginning new measurement.</p> <p>Over gently rolling land.</p>
19.91	<p>Point for the N. 1/16 sec. cor. of secs. 25 and 26, determined at the intersection of the N-S sec. line of secs. 25 and 26, and the extension of bearing of the E-W barbed wire fence from the W. Remove 2004 cor. and reset at the true point.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T 22 N R 29 E N 1/16 S 26 S 25</p> <p style="text-align: center;">2017</p> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p> <p>Set a steel fence post alongside and W. of cor.</p>
30.30	Power line, 4 strand, bears S. 88° E. and N. 88° W.
36.20	S. right-of-way fence of S. Frontage Road to Interstate 40, woven and barbed wire fence, bears E. and W.
36.65	S. Frontage Road to Interstate 40, an asphalt surfaced road, 20 ft. wide, bears S. 89° E. and N. 89° W.
37.10	S. right-of-way fence of Interstate 40, woven and barbed wire fence, bears E. and W.
37.60	Interstate 40 east bound lane, an asphalt surfaced road, bears E. and W.
39.46	<p>True point for the cor. of secs. 23, 24, 25, and 26, determined at the intersection of W. bound lane of Interstate 40, bears S. 89°52' E. and N. 89°52' W., based on the 1962 Arizona Highway Department Right-of-Way Map of Holbrook-Lupton Interstate HWY. 40, Drawing Number A-I-T-222A. Accepted as the best available evidence of the orig. cor. position. Monument not set, cor. falls in W. bound lane of Interstate 40, where it is impracticable to set a permanent monument. Remove 2004 cor.</p> <p>From this true point, the point selected for an online witness cor. to the cor. of secs. 23, 24, 25, and 26, bears N. 0°01' W., 1.50 chs. dist.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p>

Corrective Resurvey of a Portion of the Subdivisional Lines,
T. 22 N., R. 29 E., Gila and Salt River Meridian, Arizona

CHAINS



Deposit a magnet, in a white plastic case, at the base of the stainless steel post.

Set an orange carsonite post nearby cor.

Cor. is located in N. right-of-way fence of Interstate 40, woven and barbed wire fence, bears E. and W.

From the cor. of secs. 24 and 25 only, on the E. bdy. of the Tp., hereinbefore described.

N. 89°51' W., bet. secs. 24 and 25.


Along the W. bound lane of Interstate 40.

17.38

Point for the E. 1/16 sec. cor. of sec. 24 only, determined at the intersection of the E-W sec. line of secs. 24 and 25, and the extension of bearing of the N-S barbed wire fence from the N. Monument not set. Cor. falls in W. bound lane of Interstate 40, where it is impracticable to set a permanent monument. Remove 2004 cor.

From this true point, the point selected for an online witness cor. to the E. 1/16 sec. cor. of sec. 24 only, bears N. 0°05' W., 1.17 chs. dist.

Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., flush with the surface of the ground, with brass cap mkd.



Deposit a magnet, in a white plastic case, at the base of the stainless steel post.

Set a steel fence post alongside and W. of cor.

Cor. is located in N. right-of-way fence of Interstate 40, woven and barbed wire fence, bears S. 88° E. and N. 89° W.

Corrective Resurvey of a Portion of the Subdivisional Lines,
T. 22 N., R. 29 E., Gila and Salt River Meridian, Arizona

CHAINS	
18.61	<p>Point for the E. 1/16 sec. cor. of sec. 25 only, determined at the intersection of the E-W sec. line of secs. 24 and 25, and the extension of bearing of the N-S barbed wire fence from the S. Monument not set. Cor. falls in W. bound lane of Interstate 40, where it is impracticable to set a permanent monument. Remove 2004 cor.</p> <p>From this true point, the point selected for an online witness cor. to the E. 1/16 sec. cor. of sec. 25 only, bears S. 0°09' E., 3.16 chs. dist.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., flush with the surface of the ground, with brass cap mkd.</p> <div style="text-align: center;"> <p>WC T 22 N R 29 E ↑ E 1/16 S 25 2017</p> </div> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p> <p>Set a steel fence post alongside and W. of cor.</p> <p>Cor. is located 2 lks. N. of S. right-of-way fence of S. Frontage Road to Interstate 40, barbed wire, 5 strand, bears E. and W., and at the terminus of woven and barbed wire fence, extending S. 0°08' E.</p> <p>Cor. is also located 40 lks. S. of the S. Frontage Road to Interstate 40, an asphalt surfaced road, 20 ft. wide, bears S. 89° E. and bears N. 89° W.</p>
27.52	<p>Point for the W-E 1/64 sec. cor. of secs. 24 and 25, determined at the intersection of the E-W sec. line of secs. 24 and 25, and the extension of bearing from the cors. of the SW-SE 1/64 sec. cor. of sec. 24, and the C-S-SW-SE 1/256 sec. cor. of sec. 24, both established in this survey. Monument not set, cor. falls in W. bound lane of Interstate 40, where it is impracticable to set a permanent monument. Remove 2004 cor.</p> <p>From this true point, the point selected for an online witness cor. to the W-E 1/64 sec. cor. of secs. 24 and 25, bears N. 0°29' E., 1.52 chs. dist.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., flush with the surface of the ground, with brass cap mkd.</p>

Corrective Resurvey of a Portion of the Subdivisional Lines,
T. 22 N., R. 29 E., Gila and Salt River Meridian, Arizona


CHAINS	
	<p style="text-align: center;">WC T 22 N R 29 E S 24 W-E 1/64 S 24 ↓ 2017</p> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p> <p>Set a steel fence post alongside and W. of cor.</p> <p>Cor. is located in N. right-of-way fence of Interstate 40, woven and barbed wire fence, bears E. and W.</p>
37.47	<p>Point for the 1/4 sec. cor. of secs. 24 and 25, determined at the intersection of the E-W sec. line of secs. 24 and 25, and the extension of bearing of the N-S barbed wire fence from the N. Monument not set, cor. falls in W. bound lane of Interstate 40, where it is impracticable to set a permanent monument. Remove 2004 cor.</p> <p>From this true point, the point selected for an online witness cor. to the 1/4 sec. cor. of secs. 24 and 25, bears N. 0°03' W., 1.50 chs. dist.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with brass cap mkd.</p>
	<p style="text-align: center;">WC T 22 N R 29 E 1/4 S 24 ↓ ↓ 2017</p> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p> <p>Set a steel fence post alongside and E. of cor.</p> <p>Cor. is located in N. right-of-way fence of Interstate 40, woven and barbed wire fence, bears E. and W.</p>
46.83	<p>Point for the E-W 1/64 sec. cor. of secs. 24 and 25, determined at the intersection of the E-W sec. line of secs. 24 and 25, and the extension of bearing of the N-S bladed dirt road from the N. Monument not set, cor. falls in W. bound lane of Interstate 40, where it is impracticable to set a permanent monument. Remove 2004 cors.</p>

Corrective Resurvey of a Portion of the Subdivisional Lines,
T. 22 N., R. 29 E., Gila and Salt River Meridian, Arizona

CHAINS

From this true point, the point selected for an online witness cor. to the E-W 1/64 sec. cor. of secs. 24 and 25, bears N. 0°45' W., 1.50 chs. dist.

Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., flush with the surface of the ground, with brass cap mkd.



Deposit a magnet, in a white plastic case, at the base of the stainless steel post.

Set an orange carsonite post nearby cor.


Cor. is located in N. right-of-way fence of Interstate 40, woven and barbed wire fence, bears E. and W.

56.30

Point for the W. 1/16 sec. cor. of secs. 24 and 25, determined at the intersection of the E-W sec. line of secs. 24 and 25, and the extension of bearing of the N-S graded dirt road from the N. Monument not set, cor. falls in W. bound lane of Interstate 40, where it is impracticable to set a permanent monument. Remove 2004 cor.

From this true point, the point selected for an online witness cor. to the W. 1/16 sec. cor. of secs. 24 and 25, bears N. 0°13' W., 1.50 chs. dist.

Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with brass cap mkd.



Deposit a magnet, in a white plastic case, at the base of the stainless steel post.

Set an orange carsonite post nearby cor.

Corrective Resurvey of a Portion of the Subdivisional Lines,
T. 22 N., R. 29 E., Gila and Salt River Meridian, Arizona

CHAINS	
	Cor. is located in N. right-of-way fence of Interstate 40, woven and barbed wire fence, bears E. and W., and is 7.5 lks. S. of the S. edge of the N. Frontage Road to Interstate 40, an asphalt surfaced road, 24 ft. wide, bears E. and W.
74.94	The true point for the cor. of secs. 23, 24, 25, and 26.
	<hr/> N. 0°01' W., bet. secs. 23 and 24. Gently ascending, along N-S barbed wire fence.
1.50	N. right-of-way fence of Interstate 40, woven and barbed wire fence, bears E. and W.
1.80	N. Frontage Road to Interstate 40, an asphalt surfaced road, 24 ft. wide, bears E. and W.
2.20	N. right-of-way fence of N. Frontage Road to Interstate 40, barbed wire, 5 strand, bears E. and W.
9.90	From this point, barbed wire fence terminates, and a series of wood fence posts to the same dilapidated fence, with barbed wire strands on the ground, continues northerly.
19.96	The S. 1/16 sec. cor. of secs. 23 and 24, monumented with an iron rod, 19 ins. long, 1/2 ins. diam., firmly set, bent over, projecting 11 ins. above ground. As per a conversation with Robert Smith, on November 20, 2017, this iron rod has been in place and relied on by local residents for as long as he remembers. Mr. Smith is a long time resident of Indian allotment #02413. The testimony of Mr. Smith is documented in the field tablet, a copy of which has been made a part of the record in the group file. The iron rod is accepted as a careful and faithful determination of the corner point. At the corner point Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.
	<div style="text-align: center;"> <p>T 22 N R 29 E S 1/16 S 23 S 24</p> <p>2017</p> </div>
	Deposit a magnet, in a white plastic case, and the iron rod, at the base of the stainless steel post.
	Set a steel fence post alongside and W. of cor.

Corrective Resurvey of a Portion of the Subdivisional Lines,
T. 22 N., R. 29 E., Gila and Salt River Meridian, Arizona

CHAINS	
	<p>Cor. is located on top of hill, near remains of barbed wire strands on the ground, extending N. and S., and a series of rock piles, to a once fence, extending down the hillside at a bearing of S. 89°51' E., where it would meet with a well maintained fence separating the Indian Allotment tracts, continuing easterly, in sec. 24.</p> <hr/> <p>N. 0°02' E., beginning new measurement.</p> <p>Over gently rolling land covered with juniper.</p>
20.03	<p>Point for the 1/4 sec. cor. of secs. 23 and 24, determined at proportionate distance between S. 1/16 sec. cor. of secs. 23 and 24, and the cor. of secs. 11, 12, 13, and 14, hereinafter described. Remove 2004 cor. and reset at the true point.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 27 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T 22 N R 29 E 1/4 S 23 S 24</p> <p style="text-align: center;">2017</p> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p> <p>Set a steel fence post alongside and W. of cor.</p> <p>Cor. is located in barbed wire fence, 5 strand, bears N. 70° E. and S. 65° W.</p>
30.53	<p>From this point, a wood fence cor. post of barbed wire fences to enclosed residential area, extends N. 4 chs. dist. and W. 4 chs. dist., bears W., 100 lks. dist.</p>
40.02	<p>Point for the N. 1/16 sec. cor. of secs. 23 and 24, occupied by a sandstone, 11 x 9 x 2 ins., loosely set, on top of ground, mkd. 1/16 on flat face towards ground. Accepted as a careful and faithful determination of the cor. point.</p> <p>At the corner point</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T 22 N R 29 E N 1/16 S 23 S 24</p> <p style="text-align: center;">2017</p>

Corrective Resurvey of a Portion of the Subdivisional Lines,
T. 22 N., R. 29 E., Gila and Salt River Meridian, Arizona

CHAINS									
60.02	<p>Deposit a magnet, in a white plastic case, at the base of, and bury the sandstone, alongside the stainless steel post.</p> <p>Set a steel fence post alongside and W. of cor.</p> <p>Point for the cor. of secs. 13, 14, 23, and 24, determined at proportionate distance between S. 1/16 sec. cor. of secs. 23 and 24, and the cor. of secs. 11, 12, 13, and 14, hereinafter described. Remove 2004 cor. and reset at the true point.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with brass cap mkd.</p> <table style="margin-left: auto; margin-right: auto;"> <tr><td>T 22 N</td><td>R 29 E</td></tr> <tr><td>S 14</td><td>S 13</td></tr> <tr><td>S 23</td><td>S 24</td></tr> </table> <p style="text-align: center;">2017</p> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p> <p>Set a steel fence post alongside and W. of cor.</p>	T 22 N	R 29 E	S 14	S 13	S 23	S 24		
T 22 N	R 29 E								
S 14	S 13								
S 23	S 24								
37.54	<p>From the cor. of secs. 13 and 24 only, on the E. bdy. of the Tp., hereinbefore described.</p> <p>S. 89°48' W., bet. secs. 13 and 24.</p> <p>Over gently rolling land.</p> <p>Point for the 1/4 sec. cor. of secs. 13 and 24, determined at mid-point distance between the cor. of secs. 13 and 24 only, T. 22 N., R. 29 E., and the cor. of secs. 13, 14, 23, and 24. Remove 2004 cor. and reset at the true point.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with brass cap mkd.</p> <table style="margin-left: auto; margin-right: auto;"> <tr><td>T 22 N</td><td>R 29 E</td></tr> <tr><td>S 13</td><td></td></tr> <tr><td>1/4</td><td>—</td></tr> <tr><td>S 24</td><td></td></tr> </table> <p style="text-align: center;">2017</p> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p> <p>Set a steel fence post nearby cor.</p>	T 22 N	R 29 E	S 13		1/4	—	S 24	
T 22 N	R 29 E								
S 13									
1/4	—								
S 24									

Corrective Resurvey of a Portion of the Subdivisional Lines,
T. 22 N., R. 29 E., Gila and Salt River Meridian, Arizona

CHAINS	
56.30	<p>From this cor. point, the pump shaft of a windmill, in a concrete pad, bears S. 38°03' W., 1.13 chs. dist., with a livestock tank alongside, 26 ft. diam., 7 ft. high, labeled 18K- 324.</p> <p>Point for the W. 1/16 sec. cor. of secs. 13 and 24, determined at mid-point distance between the 1/4 sec. cor. of secs. 13 and 24, and the cor. of secs. 13, 14, 23, and 24. Remove 2004 cor. and reset at the true point.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T 22 N R 29 E S 13 W 1/16 ——— S 24</p> <p style="text-align: center;">2017</p> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p> <p>Cor. is located on E. slope of hill.</p>
75.07	<p>The cor. of secs. 13, 14, 23, and 24.</p> <hr/> <p>N. 0°02' E., bet. secs. 13 and 14.</p> <p>Over mountainous land covered with juniper and piñon.</p>
40.01	<p>Point for the 1/4 sec. cor. of secs. 13 and 14, determined at proportionate distance between S. 1/16 sec. cor. of secs. 23 and 24, and the cor. of secs. 11, 12, 13, and 14, hereinafter described. Remove 2004 cor. and reset at the true point.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T 22 N R 29 E 1/4 S 14 S 13</p> <p style="text-align: center;">2017</p> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p>
80.02	<p>The cor. of secs. 11, 12, 13, and 14, established in 2004, monumented with a stainless steel post, 2 1/2 ins. diam., firmly set, projecting 6 ins. above ground, with brass cap mkd. T22N R29E S11 S12 S14 S13 2004. Add the marks 2017 to the brass cap.</p>

Corrective Resurvey of a Portion of the Subdivisional Lines,
T. 22 N., R. 29 E., Gila and Salt River Meridian, Arizona

CHAINS	
	<p>Cor. is located at the SE base of wood fence cor. post of barbed wire fences, 4 strand, extending N. and W.</p> <hr/> <p>From the cor. of secs. 12 and 13 only, on the E. bdy. of the Tp., hereinbefore described.</p> <p>S. 89°54' W., bet. secs. 12 and 13.</p> <p>Over mountainous land covered with juniper and piñon.</p> <p>37.54 Point for the 1/4 sec. cor. of secs. 12 and 13, determined at mid-point distance between the cor. of secs. 12 and 13 only, T. 22 N., R. 29 E., and the cor. of secs. 11, 12, 13, and 14. Remove 2004 cor. and reset at the true point.</p> <p>Set a rebar, 24 ins. long, 5/8 ins. diam., 18 ins. cemented in a drill hole in sandstone bedrock, with 2 in. diam. brass cap mkd.</p> <div style="text-align: center;"> <p>T 22 N R 29 E</p> <p>S 12</p> <p>1/4 ———</p> <p>S 13</p> <p>2017</p> </div> <p>Impracticable to set a steel fence post.</p> <p>Cor. is located 8 lks. S. of sandstone cliff edge, 11 ft. high.</p> <p>75.09 The cor. of secs. 11, 12, 13, and 14.</p> <hr/>
	<p>From the cor. of secs. 1 and 12 only, on the E. bdy. of the Tp., hereinbefore described.</p> <p>N. 89°47' W., bet. secs. 1 and 12.</p> <p>Over mountainous land covered with juniper and piñon.</p> <p>37.51 Point for the 1/4 sec. cor. of secs. 1 and 12, determined at mid-point distance between the cor. of secs. 1 and 12 only, T. 22N., R. 29 E., and the cor. of secs. 1, 2, 11, and 12. Remove 2004 cor. and reset at the true point.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with brass cap mkd.</p>

Corrective Resurvey of a Portion of the Subdivisional Lines,
T. 22 N., R. 29 E., Gila and Salt River Meridian, Arizona

CHAINS	
	<p style="text-align: center;">T 22 N R 29 E S 1 1/4 ——— S 12 2017</p>
	<p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p> <p>Set a steel fence post alongside and N. of cor.</p> <p>75.02 The cor. of secs. 1, 2, 11, and 12, established in 2004, monumented with a stainless steel post, 2 1/2 ins. diam., firmly set, projecting 4 ins. above ground, with brass cap mkd. T22N R29E S2 S1 S11 S12 2004. Add the marks 2017 to the brass cap.</p> <p>From this cor. point, the cor. of secs. 1, 2, 35, and 36, Tps. 22 and 23 N., R. 29 E., bears N. 0°13' W., 79.70 chs. dist., hereinbefore described.</p> <p>From this same cor. point, the cor. of secs. 11, 12, 13, and 14, bears S. 0°07' W., 79.54 chs. dist., hereinbefore described.</p> <hr/> <p>From the cor. of secs. 25, 26, 35, and 36, hereinbefore described.</p> <p>N. 89°36' W., bet. secs. 26 and 35.</p> <p>Over nearly level land.</p>
	<p>19.965 True point for the E. 1/16 sec. cor. of secs. 26 and 35, from this true point, a witness cor. for the E. 1/16 sec. cor. of secs. 26 and 35, bears S. 45°00' W., 3.0 chs. dist., established in 2004, monumented with a stainless steel post, 2 1/2 ins. diam., firmly set, projecting 4 ins. above ground, with brass cap mkd. WC T22N R29E E 1/16 S26 S35 2004.</p> <hr/> <p>N. 89°36' W., beginning new measurement.</p> <p>Ascending left bank of the Puerco River.</p>
	<p>16.99 From this point, the NE cor. of the foundation of the J.W. Bennette Store, tied by W.R. Fitzgerald in 1882, as Bennette Store and Dwelling, in Book 449, P. 13, currently an outline of embedded sandstone blocks, bears S., 1 lk. dist., E. wall is 93 lks. long, bears S. 08°20' E., and N. wall is 81 lks. long, bears S. 78°56' W.</p> <p>Alongside the foundation of the J.W. Bennette Store, is the aforementioned sandstone dwelling, 47 x 34 ft., currently occupied by residents, located 48 lks. S. of the SE foundation cor. of the J.W. Bennette Store.</p>

Corrective Resurvey of a Portion of the Subdivisional Lines,
T. 22 N., R. 29 E., Gila and Salt River Meridian, Arizona

CHAINS	
19.965	<p>The 1/4 sec. cor. of secs. 26 and 35, established in 2004, monumented with a brass tablet, 3 1/4 ins. diam., firmly set, 3 ins. below loose soil, flush with sandstone bedrock, with brass cap mkd. T22N R29E 1/4 S26 S35 2004. Add the marks 2017 to the brass cap.</p>
	<p>From this cor. point, the NW cor. of the foundation of the J.W. Bennette Store, bears S. 85°05' E., 2.18 chs. dist., and the SW cor. of the sandstone dwelling, bears S. 57°18' E., 3.54 chs. dist.</p>
	<hr/> <p>N. 89°36' W., beginning new measurement.</p>
	<p>Over gently rolling land.</p>
19.965	<p>The W. 1/16 sec. cor. of secs. 26 and 35, established in 2004, monumented with a stainless steel post, 2 1/2 ins. diam., firmly set, projecting 4 ins. above ground, with brass cap mkd. T22N R29E W 1/16 S26 S35 2004.</p>
	<hr/> <p>N. 89°36' W., beginning new measurement.</p>
	<p>Over gently rolling land.</p>
19.965	<p>True point for the cor. of secs. 26, 27, 34, and 35, from this true point, a witness cor. for the cor. of secs. 26, 27, 34, and 35, bears N. 45°00' W., 2.0 chs. dist., established in 2004, monumented with a stainless steel post, 2 1/2 ins. diam., firmly set, projecting 4 ins. above ground, with a steel fence post alongside to the N., with brass cap mkd. WC T22N R29E S27 S26 S34 S35 2004. Add the marks 2017 to the brass cap.</p>
	<hr/> <p>N. 0°13' W., bet. secs. 26 and 27.</p>
	<p>Over gently rolling land.</p>
1.20	<p>N. right-of-way fence of the Burlington Northern Santa Fe Rail Road, barbed wire, 3 strand, bears N. 65° E. and S. 65° W.</p>
6.40	<p>Intersect abandoned rail road berm, 40 ft. wide, bears N. 80° E. and S. 80° W.</p>
20.01	<p>The S. 1/16 sec. cor. of secs. 26 and 27, established in 2004, monumented with a stainless steel post, 2 1/2 ins. diam., firmly set, projecting 7 ins. above ground, encircled with a collar of stone, 3 ft. base, to top, with brass cap mkd. T22N R29E S 1/16 S27 S26 2004. Add the marks 2017 to the brass cap.</p>
	<hr/> <p>N. 0°13' W., beginning new measurement.</p>

Corrective Resurvey of a Portion of the Subdivisional Lines,
T. 22 N., R. 29 E., Gila and Salt River Meridian, Arizona

CHAINS	
	Gently descending finger ridge.
20.01	<p>The 1/4 sec. cor. of secs. 26 and 27, established in 2004, monumented with a stainless steel post, 2 1/2 ins. diam., firmly set, flush with the surface of the ground, encircled with an embedded collar of stone, 3 ft. base, with a steel fence post alongside to the S., with brass cap mkd. T22N R29E 1/4 S27 S26 2004. Add the marks 2017 to the brass cap.</p> <p>Cor. is located at the SE base of wood fence cor. post of barbed wire fences, 4 strand, extending W. and N. 01° W.</p> <hr/> <p>N. 0°09' W., beginning new measurement.</p> <p>Over gently rolling land.</p>
20.50	S. right-of-way fence of S. Frontage Road to Interstate 40, woven and barbed wire fence, bears N. 75° E. and S. 75° W.
20.90	S. Frontage Road to Interstate 40, an asphalt surfaced road, 22 ft. wide, bears N. 70° E. and S. 70° W.
21.55	S. right-of-way fence of Interstate 40, woven and barbed wire fence, bears N. 70° E. and S. 70° W.
22.15	Interstate 40 east bound lane, an asphalt surfaced road, bears N. 70° E. and S. 70° W.
27.25	Interstate 40 west bound lane, an asphalt surfaced road, bears N. 70° E. and S. 70° W.
38.92	<p>The cor. of secs. 22, 23, 26, and 27, established in 2004, monumented with a stainless steel post, 2 1/2 ins. diam., firmly set, projecting 5 ins. above mound of stone, 8 ft. base, 14 ins. high, with a steel fence post alongside to the N., with brass cap mkd. T22N R29E R30E S22 S23 S27 S26 2004. Add the marks 2017 to the brass cap.</p> <p>Cor. is located 1.25 chs. S. of N. Frontage Road to Interstate 40, an asphalt surfaced road, 25 ft. wide, bears S. 89° E. and N. 89° W.</p> <p>From this cor. point, wood fence cor. post serves as the terminus to a barbed wire fence, 5 strand, extends S. 88° E., bears S. 29°57' E., 1.5 lks. dist.</p> <p>From this same cor. point, third order, National Geodetic Survey station GOOD NEWS, monumented with a brass tablet, 3 5/8 ins. diam., firmly set, flush with sandstone bedrock, mkd. GOODNEWS 1959, bears S. 61°32' E., 9.98 chs. dist.</p> <p>from which</p>

Corrective Resurvey of a Portion of the Subdivisional Lines,
T. 22 N., R. 29 E., Gila and Salt River Meridian, Arizona

CHAINS	<p>Reference monument No. 1, bears S. 49°01' W., 28.51 ft. dist., monumented with brass tablet, 3 5/8 ins. diam., firmly set, flush with sandstone bedrock, mkd. NO 1 GOODNEWS 1959 and an arrow pointing to the cor.</p> <p>Reference monument No. 2, bears N. 42°39' W., 15.77 ft. dist., monumented with a brass tablet, 3 5/8 ins. diam., firmly set, flush with sandstone bedrock, mkd. NO 2 GOODNEWS 1959 and an arrow pointing to the cor.</p> <hr/> <p>From the true point for the cor. of secs. 23, 24, 25, and 26.</p> <p>N. 89°48' W., bet. secs. 23 and 26.</p> <p>Along W. bound lane of Interstate 40.</p>
19.84	<p>Point for the E. 1/16 sec. cor. of secs. 23 and 26, determined at the intersection of the E-W sec. line of secs. 23 and 26, and the extension of bearing from the center E. 1/16 sec. cor. of sec. 26, established in this survey, and the wood fence cor. post serving as the terminus to a N-S barbed wire fence on the S. right-of-way fence of Interstate 40. Monument not set, cor. falls in W. bound lane of Interstate 40, where it is impracticable to set a permanent monument. Remove 2004 cor.</p> <p>From this true point, the point selected for an online witness cor. to the E. 1/16 sec. cor. of secs. 23 and 26, bears N. 0°09' E., 1.50 chs. dist.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., flush with the surface of the ground, with brass cap mkd.</p> <div style="text-align: center; margin: 10px 0;"> <p>WC</p> <p>T 22 N R 29 E</p> <p style="margin-left: 100px;">S 23</p> <p style="margin-left: 100px;">E 1/16 ———</p> <p style="margin-left: 100px;">↓ S 26</p> <p style="margin-left: 100px;">2017</p> </div> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p> <p>Set an orange carsonite post alongside and E. of cor.</p> <p>Cor. is located 3.8 lks. N. of the N. right-of-way fence of Interstate 40, woven and barbed wire fence, bears E. and W., and is 13 lks. S. of the S. pavement edge of N. Frontage Road to Interstate 40, an asphalt surfaced road, 26 ft. wide, bears E. and W.</p>
24.50	<p>Interstate 40 west bound lane, begins to curve southwesterly, bears E. and S. 89°55' W.</p>

Corrective Resurvey of a Portion of the Subdivisional Lines,
T. 22 N., R. 29 E., Gila and Salt River Meridian, Arizona

CHAINS	
40.18	<p>Point for the 1/4 sec. cor. of secs. 23 and 26, determined at the intersection of the E-W sec. line of secs. 23 and 26, and the extension of bearing from the cors. of the 1/4 sec. cor. of secs. 26 and 35, and the center 1/4 sec. cor. of sec. 26, established in this survey. Remove 2004 cor. and reset at the true point.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 22 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T 22 N R 29 E S 23 1/4 ——— S 26</p> <p style="text-align: center;">2017</p> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p> <p>Set an orange carsonite post alongside and W. of cor.</p> <p>Cor. is located 45 lks. S. of the N. right-of-way fence of Interstate 40, woven and barbed wire fence, bears S. 89° E. and N. 89° W., and is 35 lks. N. of the N. pavement edge of Interstate 40 west bound lane, an asphalt surfaced road, bears N. 85° E. and S. 85° W.</p> <p>From this cor. point, a right-of-way monument, bears N. 72°43' W., 1.14 chs. dist., monumented with a brass tablet, 3 ins. diam., set flush in a concrete headwall, 12 ft. long, 1 ft. wide, mkd. ARIZONA HIGHWAY DEPT. ELEV. 6001.75 + STA 2196+13 1931 2-17-1931.</p>
60.10	<p>Point for the W. 1/16 sec. cor. of secs. 23 and 26, determined at the intersection of the E-W sec. line of secs. 23 and 26, and the extension of bearing of the N-S barbed wire fence from the S. Remove 2004 cor. and reset at the true point.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T 22 N R 29 E S 23 W 1/16 ——— S 26</p> <p style="text-align: center;">2017</p> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p> <p>Set an orange carsonite post nearby cor.</p>

Corrective Resurvey of a Portion of the Subdivisional Lines,
T. 22 N., R. 29 E., Gila and Salt River Meridian, Arizona

CHAINS	
	<p>Cor. is located 60 lks. W. of an interchange road, asphalt surfaced, 26 ft. wide, bears S. 15° E. and N. 15° W., and is 35 lks. N. of the N. right-of-way fence of Interstate 40, woven and barbed wire fence, bears N. 75° E. and S. 75° W.</p> <p>From this cor. point, a right-of-way monument, bears S. 79°10' E., 85 lks. dist., monumented with a brass tablet, 3 ins. diam., set flush in a concrete headwall, 12 ft. long, 8 ins. wide, at the E. end of cattle guard, mkd. ARIZONA HIGHWAY DEPT. 6006.38 1966.</p> <p>From this same cor. point, a right-of-way monument, bears S. 64°03' W., 1.22 chs. dist., monumented with a brass tablet, 3 ins. diam., set flush in a concrete cylinder, 6 ins. diam., firmly, projecting 4 ins. above ground, mkd. ARIZONA HIGHWAY DEPT. 19, with an angle iron, firmly set, projecting 23 ins. above ground, 3 lks. to the W., with no visible markings.</p>
79.99	<p>The cor. of secs. 22, 23, 26, and 27.</p> <hr/>
	<p>From the cor. of secs. 13, 14, 23, and 24.</p> <p>N. 88°49' W., bet. secs. 14 and 23.</p> <p>Over mountainous land covered with juniper and piñon.</p>
39.28	<p>Point for the 1/4 sec. cor. of secs. 14 and 23, determined at proportionate distance between the cors. of secs. 13, 14, 23, and 24, and the cor. of secs. 14, 15, 22, and 23, hereinafter described. Remove 2004 cor. and reset at the true point.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., flush with the surface of the ground, with brass cap mkd.</p> <div style="text-align: center;"> <p>T 22 N R 29 E</p> <p>S 14</p> <p>1/4 ———</p> <p>S 23</p> <p>2017</p> </div> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p> <p>Set a steel fence post alongside and N. of cor.</p>
78.55	<p>The cor. of secs. 14, 15, 22, and 23, established in 1993, monumented with a stainless steel post, 2 1/2 ins. diam., firmly set, projecting 3 ins. above ground, with a steel fence post alongside to the N., with brass cap mkd. T22N R29E S15 S14 S22 S23 1993 2004. Add the marks 2017 to the brass cap.</p> <hr/> <p>N. 0°41' W., bet. secs. 14 and 15.</p>

Corrective Resurvey of a Portion of the Subdivisional Lines,
T. 22 N., R. 29 E., Gila and Salt River Meridian, Arizona

CHAINS	
	<p>Over mountainous land covered with juniper and piñon.</p> <p>39.27 The 1/4 sec. cor. of secs. 14 and 15, established in 2004, monumented with a stainless steel post, 2 1/2 ins. diam., firmly set, projecting 7 ins. above ground, with a steel fence post alongside to the N., with brass cap mkd. T22N R29E 1/4 S15 S14 2004. Add the marks 2017 to the brass cap.</p> <p>Cor. is located at the NW base of a multi trunk juniper, 30 ins. diam. at the base.</p> <hr/> <p>N. 0°41' W., beginning new measurement.</p>
	<p>Over mountainous land covered with juniper and piñon.</p> <p>39.27 The cor. of secs. 10, 11, 14, and 15, established in 1993, monumented with a stainless steel post, 2 1/2 ins. diam., firmly set, flush with the surface of the ground, with a steel fence post alongside to the S., with brass cap mkd. T22N R29E S10 S11 S15 S14 1993 2004. Add the marks 2017 to the brass cap.</p> <p>Cor. is located at the S. base of wood fence cor. post of woven and barbed wire fences, extending N., N. 89° E., and W.</p> <hr/> <p>From the cor. of secs. 11, 12, 13, and 14.</p> <p>N. 89°50' W., bet. secs. 11 and 14.</p>
	<p>Over mountainous land covered with juniper and piñon.</p> <p>39.76 The 1/4 sec. cor. of secs. 11 and 14, established in 2004, monumented with a stainless steel post, 2 1/2 ins. diam., firmly set, projecting 5 ins. above ground, with a steel fence post alongside to the S., with brass cap mkd. T22N R29E 1/4 S11 S14 2004. Add the marks 2017 to the brass cap.</p> <p>Cor. is located at the S. base of wood fence cor. post of woven and barbed wire fences, extending N., E., and W.</p> <hr/> <p>N. 89°58' W., beginning new measurement.</p>
	<p>Over mountainous land covered with juniper and piñon.</p> <p>39.75 The cor. of secs. 10, 11, 14, and 15.</p> <hr/>
	<p style="text-align: center;">Subdivision of Section 14, T. 22 N., R. 29 E., Gila and Salt River Meridian, Arizona</p> <hr/> <p>From the 1/4 sec. cor. of secs. 14 and 23.</p>

Subdivision of Section 14,
T. 22 N., R. 29 E., Gila and Salt River Meridian, Arizona

CHAINS	
	<p>N. 0°45' W., on the N. and S. center line of sec. 14.</p> <p>Over mountainous land covered with juniper and piñon.</p>
40.05	<p>The center 1/4 sec. cor. of sec. 14, monumented with a sandstone, 26 x 12 x 4 ins., firmly set in the upright position, projecting 14 ins. above ground, mkd. C on weathered W. face, with partially visible 4 on the same W. face. Accepted as a careful and faithful determination of the cor. point.</p> <p>At the corner point</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, encircled with a collar of stone, 2 1/2 ft. base, to top, with brass cap mkd.</p> <p style="text-align: center;">T 22 N R 29 E C 1/4 S 14</p> <p style="text-align: center;">2017</p> <p>Deposit a magnet, in a white plastic case, at the base of, and bury the sandstone, alongside to the W. of the stainless steel post, incorporating the exposed top portion of the sandstone into collar of stone.</p> <p>Set a steel fence post alongside and N. of cor.</p> <hr style="width: 20%; margin: 10px auto;"/> <p>N. 0°07' E., beginning new measurement.</p> <p>Over mountainous land covered with juniper and piñon.</p>
39.28	<p>The 1/4 sec. cor. of secs. 11 and 14.</p> <hr style="width: 80%; margin: 10px auto;"/> <p>From the 1/4 sec. cor. of secs. 13 and 14.</p> <p>N. 88°47' W., on the E. and W. center line of sec. 14.</p> <p>Over mountainous land covered with juniper and piñon.</p>
39.83	<p>The center 1/4 sec. cor. of sec. 14.</p> <hr style="width: 20%; margin: 10px auto;"/> <p>N. 89°57' W., beginning new measurement.</p> <p>Over mountainous land covered with juniper and piñon.</p>
39.20	<p>The 1/4 sec. cor. of secs. 14 and 15.</p> <hr style="width: 80%; margin: 10px auto;"/>

Subdivision of Section 24,
T. 22 N., R. 29 E., Gila and Salt River Meridian, Arizona

CHAINS	
	<p>From the true point of the 1/4 sec. cor. of secs. 24 and 25.</p> <p>N. 0°03' W., on the N. and S. center line of sec. 24.</p> <p>Over nearly level land.</p>
1.50	<p>N. right-of-way fence of Interstate 40, woven and barbed wire fence, bears E. and W.</p>
1.80	<p>N. Frontage Road to Interstate 40, an asphalt surfaced road, 25 ft. wide, bears E. and W.</p>
2.20	<p>N. right-of-way fence of N. Frontage Road to Interstate 40, barbed wire, 5 strand, bears E. and W., and access gate, two track road extends N., parallel to barbed wire fence, 5 strand.</p>
5.00	<p>The center S-S-S 1/256 sec. cor. of sec. 24, determined at the corner of barbed wire fences, extending N., S., and W. The fence cor. post is accepted as a careful and faithful determination of the cor. point. Remove 2004 cor. and reset at the true point.</p> <p>At the corner point</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T 22 N R 29 E S 24 C-S-S-S 1/256 2017</p> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p> <p>Set a steel fence post alongside and N. of cor.</p> <hr style="width: 20%; margin: 10px auto;"/> <p>N. 0°10' W., beginning new measurement.</p> <p>On the N. and S. center line of sec. 24.</p>
5.16	<p>The center S-S 1/64 sec. cor. of sec. 24, determined at the corner of barbed wire fences, extending N. 01° E., S. 89° E., S., and S. 89° W. The fence cor. post is accepted as a careful and faithful determination of the cor. point. Remove 2004 cor. and reset at the true point.</p> <p>At the corner point</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 25 ins. in the ground, with brass cap mkd.</p>

Subdivision of Section 24,
T. 22 N., R. 29 E., Gila and Salt River Meridian, Arizona

CHAINS	
	T 22 N R 29 E S 24 C-S-S 1/64 2017
	Deposit a magnet, in a white plastic case, at the base of the stainless steel post. Set a steel fence post alongside and N. of cor. <hr style="width: 20%; margin: auto;"/> N. 0°54' E., beginning new measurement. On the N. and S. center line of sec. 24.
4.90	The center N-S-S 1/256 sec. cor. of sec. 24, determined at the corner of barbed wire fences, extending S. 01° W. and W. The fence cor. post is accepted as a careful and faithful determination of the cor. point. Remove 2004 cor. and reset at the true point. At the corner point Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 27 ins. in the ground, with brass cap mkd.
	T 22 N R 29 E S 24 C-N-S-S 1/256 2017
	Deposit a magnet, in a white plastic case, at the base of the stainless steel post. Set a steel fence post alongside and N. of cor. <hr style="width: 20%; margin: auto;"/> N. 0°40' E., beginning new measurement. On the N. and S. center line of sec. 24.
1.90	Series of wood fence posts, no barbed wire, extends N., and terminates at 1.40 chs. dist.
4.99	The center S. 1/16 sec. cor. of sec. 24, determined at the corner of barbed wire fences, extending N. and W. The fence cor. post is accepted as a careful and faithful determination of the cor. point. Remove 2004 cor. and reset at the true point. At the corner point

Subdivision of Section 24,
T. 22 N., R. 29 E., Gila and Salt River Meridian, Arizona

CHAINS	
	<p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., flush with the surface of the ground, with brass cap mkd.</p> <p style="text-align: center;">T 22 N R 29 E C S 1/16 S 24 C</p> <p style="text-align: center;">2017</p> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p> <p>Set a steel fence post alongside and S. of cor.</p> <hr style="width: 20%; margin: 10px auto;"/> <p>N. 0°02' E., beginning new measurement.</p> <p>On the N. and S. center line of sec. 24.</p>
5.02	<p>Point for the center S-N-S. 1/256 sec. cor. of sec. 24, determined at the center of abandoned two track road, and at mid-point distance between two fence corner posts of fences, parallel to each other, extending E. and W. The two fence cor. posts of fences is accepted as a careful and faithful determination of the cor. point. Remove 2004 cor. and reset at the true point.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T 22 N R 29 E S 24 C-S-N-S 1/256</p> <p style="text-align: center;">2017</p> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p> <p>Set a steel fence post alongside and N. of cor.</p> <p>Cor. is located in abandoned two track road, extending E. and W., and is located 9.5 lks. S. of barbed wire fence, bears S. 85° E. and W., and is 9.5 lks. N. of wood fence cor. post of fences, bears S. and W.</p> <hr style="width: 20%; margin: 10px auto;"/> <p>N. 0°15' W., beginning new measurement.</p> <p>On the N. and S. center line of sec. 24.</p>

Subdivision of Section 24,
T. 22 N., R. 29 E., Gila and Salt River Meridian, Arizona

CHAINS	
5.13	<p>Point for the center N-S. 1/64 sec. cor. of sec. 24, determined at mid-point distance on the N. and S. center line of sec. 24, between the center S-N-S. 1/256 sec. cor. of sec. 24, and center N-N-S. 1/256 sec. cor. of sec. 24, established in this survey. Remove 2004 cor. and reset at the true point.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., flush with the surface of the ground, with brass cap mkd.</p> <p style="text-align: center;">T 22 N R 29 E S 24 C-N-S 1/64 2017</p> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p> <p>Set a steel fence post alongside and N. of cor.</p> <p>Cor. is located 70 lks. S. and 1.15 chs. E. of a graded road, 15 ft. wide, bears N. 60° E. and S. 60° W.</p>
10.25	<p>Point for the center N-N-S. 1/256 sec. cor. of sec. 24, determined at the intersection of the N. and S. center line of sec. 24, and the extension of bearing of the E-W barbed wire fence from the W. Remove 2004 cor. and reset at the true point.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 8 ins. below the surface of the ground, with brass cap mkd.</p> <p style="text-align: center;">T 22 N R 29 E S 24 C-N-N-S 1/256 2017</p> <p>from which</p> <p style="padding-left: 40px;">A rebar, 24 ins. long, 5/8 ins. diam., set flush with the surface of the ground for a reference monument, bears S. 89°22' E., 70.0 ft. dist. with 2 in. diam. brass cap mkd. RM S24 C-N-N-S 70.0 FT TO COR 1/256 2017 and an arrow pointing to the cor.</p> <p style="padding-left: 40px;">A rebar, 24 ins. long, 5/8 ins. diam., set flush with the surface of the ground for a reference monument, bears S. 89°54' W., 117.0 ft. dist. with 2 in. diam. brass cap mkd. RM S24 C-N-N-S 117.0 FT TO COR 1/256 2017 and an arrow pointing to the cor.</p>

Subdivision of Section 24,
T. 22 N., R. 29 E., Gila and Salt River Meridian, Arizona

CHAINS	
	<p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p> <p>Cor. is located at the S. edge of graded road, 10 ft. wide, bears S. 70° E. and N. 70° W.</p>
15.16	<p>The center 1/4 sec. cor. of sec. 24, determined at the intersection with the E. and W. center line of sec. 24, and the N. and S. center line of sec. 24, from the center S-N-S 1/256 sec. cor. of sec. 24. Remove 2004 cor. and reset at the true point.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, underpinned with a rebar, 1/2 in. diam., 48 ins. long, with brass cap mkd.</p> <p style="text-align: center;">T 22 N R 29 E C 1/4 S 24</p> <p style="text-align: center;">2017</p> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p> <p>Set a steel fence post alongside and N. of cor.</p> <hr style="width: 20%; margin: 10px auto;"/> <p>N. 0°05' E., beginning new measurement.</p> <p>On the N. and S. center line of sec. 24.</p>
19.98	<p>Point for the center N. 1/16 sec. cor. of sec. 24, determined at mid-point distance on the N. and S. center line of sec. 24. Remove 2004 cor. and reset at the true point.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 22 ins. in the ground, encircled with a collar of stone, with brass cap mkd.</p> <p style="text-align: center;">T 22 N R 29 E C N 1/16 S 24 C</p> <p style="text-align: center;">2017</p> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p> <p>Set a steel fence post alongside and N. of cor.</p>
39.97	<p>The 1/4 sec. cor. of secs. 13 and 24.</p> <hr style="width: 20%; margin: 10px auto;"/> <p>From the 1/4 sec. cor. of sec. 24 only, on the E. bdy. of the Tp.</p>

Subdivision of Section 24,
T. 22 N., R. 29 E., Gila and Salt River Meridian, Arizona

CHAINS	
	<p>S. 89°46' W., on the E. and W. center line of sec. 24.</p> <p>Over gently rolling land.</p>
17.48	<p>Point for the center E. 1/16 sec. cor. of sec. 24, determined at the intersection with the E. and W. center line of sec. 24, and the extension of bearing of the N-S barbed wire fence from the S. Remove 2004 cor. and reset at the true point.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T 22 N R 29 E E 1/16 C———C S 24 2017</p> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p> <p>Set a steel fence post alongside and W. of cor.</p> <p>Cor. is located 22 lks. N. of a series of wood fence posts to a once enclosed cultivated field, bears E. and W.</p>
27.51	<p>Point for the center W-E 1/64 sec. cor. of sec. 24, determined at mid-point distance on the E. and W. center line of sec. 24. Remove 2004 cor. and reset at the true point.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T 22 N R 29 E S 24 C-W-E 1/64 2017</p> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p> <p>Set a steel fence post alongside and N. of cor.</p>
37.55	<p>The center 1/4 sec. cor. of sec. 24.</p>
46.74	<p>Point for the center E-W 1/64 sec. cor. of sec. 24, determined at the intersection with the E. and W. center line of sec. 24, and the N-S abandoned two track road from the S. Remove 2004 cor. and reset at the true point.</p>

Subdivision of Section 24,
T. 22 N., R. 29 E., Gila and Salt River Meridian, Arizona

CHAINS	
	<p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T 22 N R 29 E S 24 C-E-W 1/64 2017</p> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p> <p>Set a steel fence post alongside and N. of cor.</p> <p>Cor. is located 13 lks. E. of woven and barbed wire fence, 3 strand, bears N. and S., and is 16 lks. E. of a series of wood fence posts, extends S. 02° E.</p>
56.52	<p>Point for the center W. 1/16 sec. cor. of sec. 24, determined at the intersection with the E. and W. center line of sec. 24, and the N-S partially paved road. Remove 2004 cor. and reset at the true point.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 10 ins. below the surface of the ground, with brass cap mkd.</p> <p style="text-align: center;">T 22 N R 29 E W 1/16 C———C S 24 2017</p> <p>from which</p> <p style="padding-left: 40px;">A rebar, 24 ins. long, 5/8 ins. diam., set 26 ins. in the ground for a reference monument, bears N. 89°44' E., 17.0 ft. dist. with 2 in. diam. brass cap mkd. RM C-W 1/16 17.0 FT TO COR S24 2017 and an arrow pointing to the cor. Cor. is located in woven and barbed wire fence, bears N. and S.</p> <p style="padding-left: 40px;">A rebar, 24 ins. long, 5/8 ins. diam., set 24 ins. in the ground for a reference monument, bears S. 89°41' W., 25.0 ft. dist. with 2 in. diam. brass cap mkd. RM C-W 1/16 25.0 FT TO COR S24 2017 and an arrow pointing to the cor. Set a steel fence post alongside and W. of cor. Cor. is located 24 lks. W. of the W. edge of partially paved road.</p> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p>

Subdivision of Section 24,
T. 22 N., R. 29 E., Gila and Salt River Meridian, Arizona

CHAINS	
	Cor. is located in center of partially paved road, asphalt patches and dirt, 20 ft. wide, bears N. 0°06' E. and S. 0°15' E.
75.07	The 1/4 sec. cor. of secs. 23 and 24.
	<hr/> SE 1/4 Section 24 <hr/>
	From the true point of the E. 1/16 sec. cor. of sec. 24 only.
	N. 0°05' W., on the N. and S. center line of the SE 1/4 of sec. 24.
1.20	N. right-of-way fence of Interstate 40, woven and barbed wire fence, bears E. and W.
1.40	N. Frontage Road to Interstate 40, an asphalt surfaced road, 25 ft. wide, bears S. 85° E. and N. 85° W.
1.90	N. right-of-way fence of N. Frontage Road to Interstate 40, barbed wire, 5 strand, bears S. 85° E. and N. 85° W.
5.02	Point for the center S-S-SE 1/256 sec. cor. of sec. 24, determined at the intersection with the N. and S. center line of the SE 1/4 of sec. 24, and the extension of bearing of the E-W barbed wire fence from the W. Remove 2004 cor. and reset at the true point.
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.
	T 22 N R 29 E S 24 C-S-S-SE 1/256 2017
	Deposit a magnet, in a white plastic case, at the base of the stainless steel post.
	Set a steel fence post alongside and N. of cor.
	<hr/>
	N. 0°05' E., beginning new measurement.
	On the N. and S. center line of the SE 1/4 of sec. 24.
3.45	From this point, an open end galvanized pipe, 7/8 in. diam., of unknown origin, firmly set, projecting 1 in. above ground, is located at SW base of wood fence cor. post of woven and barbed wire fences, to enclosed property of Houck Chapter House, extending N. and E., bears E., 1 lk. dist.

Subdivision of Section 24,
T. 22 N., R. 29 E., Gila and Salt River Meridian, Arizona

CHAINS	
5.01	<p>The center S-SE 1/64 sec. cor. of sec. 24, determined at the corner of barbed wire fences, extending N., S., and W. The fence cor. post is accepted as a careful and faithful determination of the cor. point. Remove 2004 cor. At the corner point</p> <p>Set a rebar, 24 ins. long, 5/8 ins. diam., set 20 ins. in the ground, with 2 in. diam. brass cap mkd.</p> <p style="text-align: center;">T 22 N R 29 E S 24 C-S-SE 1/64 2017</p> <p>Cor. is located at the S. base of wood fence cor. post of woven and barbed wire fences, extending N., S., and W.</p> <hr style="width: 20%; margin: 10px auto;"/> <p>N. 0°05' E., beginning new measurement.</p> <p>On the N. and S. center line of the SE 1/4 of sec. 24.</p>
5.15	<p>Point for the center N-S-SE 1/256 sec. cor. of sec. 24, determined at the intersection with the N. and S. center line of the SE 1/4 of sec. 24, and the extension of bearing of the E-W barbed wire fence from the W. Remove 2004 cor. and reset at the true point.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T 22 N R 29 E S 24 C-N-S-SE 1/256 2017</p> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p> <p>Cor. is located in woven and barbed wire fence, to enclosed property of Houck Chapter House, bears N. and S.</p> <hr style="width: 20%; margin: 10px auto;"/> <p>N. 0°05' E., beginning new measurement.</p> <p>On the N. and S. center line of the SE 1/4 of sec. 24.</p>
2.70	<p>Intersect SE fence cor. post of fences to residential home sites, located to the NW, adjacent to enclosed Houck Chapter House, woven and barbed wire fence extends N., S., and W.</p>

Subdivision of Section 24,
T. 22 N., R. 29 E., Gila and Salt River Meridian, Arizona

CHAINS

4.83

The SE 1/16 sec. cor. of sec. 24, determined at the corner of barbed wire fences, extending E. and S., with a rebar, 18 ins. long, 1/2 in. diam., with decomposing yellow cap and illegible marks, laying loose nearby. The fence cor. post is accepted as a careful and faithful determination of the cor. point. Remove 2004 cor. and reset at the true point.

At the corner point

Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with brass cap mkd.

T 22 N R 29 E
SE 1/16 S 24

2017

Deposit a magnet, in a white plastic case, and the rebar, at the base of the stainless steel post.

Cor. is located at the NW base of wood fence cor. post of fences, woven and barbed wire, serving as the NW fence cor. to enclosed property of Houck Chapter House, extending E. and S., and chain link fence to sewage lagoon extending N. 45° W.

From this cor. point, a rebar, 5/8 in. diam., firmly set, projecting 1 in. above ground, at the base of fence cor. post of enclosed fencing to Home Site property, extends E. and S., bears S. 88°38' W., 4.99 chs. dist.

N. 0°05' E., beginning new measurement.

On the N. and S. center line of the SE 1/4 of sec. 24.

10.18

Point for the center N-SE 1/64 sec. cor. of sec. 24, determined at mid-point distance on the N. and S. center line of the SE 1/4 of sec. 24, between the SE 1/16 sec. cor. of sec. 24, and center E. 1/16 sec. cor. of sec. 24. Remove 2004 cor. and reset at the true point.

Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 27 ins. in the ground, with brass cap mkd.

T 22 N R 29 E
S 24
C-N-SE
1/64

2017

Deposit a magnet, in a white plastic case, at the base of the stainless steel post.

Subdivision of Section 24,
T. 22 N., R. 29 E., Gila and Salt River Meridian, Arizona

CHAINS	
	Set a steel fence post alongside and W. of cor.
20.37	The center E. 1/16 sec. cor. of sec. 24. <hr/>
	From the S. 1/16 sec. cor. of sec. 24 only, on the E. bdy. of the Tp., hereinbefore described.
	N. 89°52' W., on the E. and W. center line of the SE 1/4 of sec. 24.
7.25	Intersect wood fence cor. post of fences, woven and barbed wire, serving as the NE fence cor. to enclosed property of Houck Chapter House, extending S. and W.
17.44	The SE 1/16 sec. cor. of sec. 24. <hr/>
	N. 89°43' W., beginning new measurement.
	On the E. and W. center line of the SE 1/4 of sec. 24.
7.25	From this point, a series of wood fence posts, no barbed wire, extends W., bears N., 9.5 lks. dist.
9.98	Point for the center W-SE 1/64 sec. cor. of sec. 24, determined at the intersection of the E. and W. center line of the SE 1/4 of sec. 24, and the extension of bearing from the center SW- SE 1/64 sec. cor. of sec. 24, and the center N-SW-SE 1/256 of sec. 24, both established in this survey. Remove 2004 cor. and reset at the true point.
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 22 ins. in the ground, with brass cap mkd.
	T 22 N R 29 E S 24 C-W-SE 1/64 2017
	Deposit a magnet, in a white plastic case, at the base of the stainless steel post.
	Set a steel fence post alongside and W. of cor.
	From this cor. point, an iron pipe to an abandoned water well, 7 ins. diam., firmly set, projecting 6.5 ft. above ground, bears N. 13°41' E., 2.63 chs. dist.
19.985	The center S. 1/16 sec. cor. of sec. 24. <hr/>

Subdivision of Section 24,
T. 22 N., R. 29 E., Gila and Salt River Meridian, Arizona

CHAINS	
	From the W-E 1/64 sec. cor. of sec. 24 and 25.
	N. 0°29' E., on the N. and S. center line of the SW 1/4 of the SE 1/4 of sec. 24.
1.50	N. right-of-way fence of Interstate 40, woven and barbed wire fence, bears E. and W.
1.80	N. Frontage Road to Interstate 40, an asphalt surfaced road, 25 ft. wide, bears E. and W.
2.20	N. right-of-way fence of N. Frontage Road to Interstate 40, barbed wire, 5 strand, bears E. and W.
5.01	Point for the center S-SW-SE 1/256 sec. cor. of sec. 24, determined at the intersection with the N. and S. center line of the SW 1/4 of the SE 1/4 of sec. 24, and the extension of bearing of the E-W barbed wire fence from the W.
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.
	T 22 N R 29 E S 24 C-S-SW-SE 1/256 2017
	Deposit a magnet, in a white plastic case, at the base of the stainless steel post.
	Set a steel fence post alongside and W. of cor.
10.08	Point for the center SW-SE 1/64 sec. cor. of sec. 24, determined longitudinally at mid-point on the E. and W. center line of the SW 1/4 of the SE 1/4 of sec. 24, and latitudinally by the E-W barbed wire fence. Remove 2004 cor. and reset at the true point.
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.
	T 22 N R 29 E S 24 SW-SE 1/64 2017
	Deposit a magnet, in a white plastic case, at the base of the stainless steel post.
	Set a steel fence post alongside and W. of cor.

Subdivision of Section 24,
T. 22 N., R. 29 E., Gila and Salt River Meridian, Arizona

CHAINS	
	Cor. is located in a barbed wire fence, 4 strand, bears E. and W.
15.12	<p>Point for the center N-SW-SE 1/256 sec. cor. of sec. 24, determined at mid-point distance on the E. and W. center line of the N 1/2 of the SW 1/4 of the SE 1/4 of sec. 24. Remove 2004 cor. and reset as a reference monument.</p> <p>Set a steel fence post, 72 ins. long, 2 ins. below the surface of the ground.</p> <p>from which</p> <p style="padding-left: 40px;">A stainless steel post, 28 ins. long, 2 1/2 ins. diam., set 25 ins. in the ground for a reference monument, bears N. 0°29' E., 50.0 ft. dist. with brass cap mkd. RM T22N R29E 50.0 FT TO COR. 2017 and an arrow pointing to the cor. Deposit a magnet, in a white plastic case, at the base of the stainless steel post, and set a steel fence post alongside and N. of cor.</p> <p style="padding-left: 40px;">A stainless steel post, 28 ins. long, 2 1/2 ins. diam., set 25 ins. in the ground for a reference monument, bears S. 0°29' W., 70.0 ft. dist. with brass cap mkd. RM T22N R29E 70.0 FT TO COR. 2017 and an arrow pointing to the cor. Deposit a magnet, in a white plastic case, at the base of the stainless steel post, and set a steel fence post alongside and S. of cor.</p> <p>Cor. is located in center of Black Creek, 35 ft. wide, 2 ft. deep, drains N. 30° E.</p>
20.03	<p>The center W-SE 1/64 sec. cor. of sec. 24.</p> <hr/> <p>From the S-SE 1/64 sec. cor. of sec. 24.</p> <p>N. 89°33' W., on the E. and W. center line of the SW 1/4 of the SE 1/4 of sec. 24.</p>
10.05	<p>The SW-SE 1/64 sec. cor. of sec. 24.</p> <hr/> <p>N. 89°22' W., beginning new measurement.</p> <p>On the E. and W. center line of the SW 1/4 of the SE 1/4 of sec. 24.</p>
10.05	<p>The center S-S 1/64 sec. cor. of sec. 24.</p> <hr/> <p>From the center N-S-SE 1/256 sec. cor. of sec. 24.</p> <p>S. 89°50' W., on the E. and W. center line of the NE 1/4 of the SW 1/4 of the SE 1/4 of sec. 24.</p>

Subdivision of Section 24,
T. 22 N., R. 29 E., Gila and Salt River Meridian, Arizona

CHAINS	
2.05	From this point, a wood fence cor. post of broken barbed wire fences to enclosed uncultivated field, extends N. and W., bears N., 1 lk. dist.
2.30	From this point, a wood fence cor. post of broken barbed wire fences to enclosed uncultivated field, extends N. and E., bears N., 2.5 lks. dist.
4.80	Point selected for an online witness cor., on the left bank of Black Creek. Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 25 ins. in the ground, with brass cap mkd. <div style="text-align: center;"> WC T 22 N R 29 E ← S 24 C-N-SW-SE 1/256 2017 </div> Deposit a magnet, in a white plastic case, at the base of the stainless steel post. Set a steel fence post alongside and E. of cor. Cor. is located 5 lks. W. of wood fence cor. post of woven and barbed wire fences, extending S. 15° E. and N. 10° W.
10.02	The center N-SW-SE 1/256 sec. cor. of sec. 24. <hr/> From the center S-S-SE 1/256 sec. cor. of sec. 24. N. 89°53' W., on the E. and W. center line of the SE 1/4 of the SW 1/4 of the SE 1/4 of sec. 24.
3.20	Chain link fence, entering enclosed fence to utility water pump station, 28 x 25 ft., 6 ft. high, bears S. 1° E., and W.
3.25	From this point, a red fire hydrant in an enclosed metal guard post bears N., 60 lks. dist.
3.65	Chain link fence, leaving enclosed fence to utility water pump station, 28 x 25 ft., 6 ft. high, bears S. 2° E., and E.
3.95	From this point, a protruding iron water valve, blue in color, bears S., 20 lks. dist.
10.09	The point for the center S-SW-SE 1/256 sec. cor. of sec. 24. <hr/>

Subdivision of Section 24,
T. 22 N., R. 29 E., Gila and Salt River Meridian, Arizona

CHAINS	
	N. 89°54' W., beginning new measurement, on the E. and W. center line of the SW 1/4 of the SW 1/4 of the SE 1/4 of sec. 24.
10.00	The center S-S-S 1/256 sec. cor. of sec. 24. <hr/>
	From the center W-SE 1/64 sec. cor. of sec. 24.
	N. 0°04' W., on the N. and S. center line of the NW 1/4 of the SE 1/4 of sec. 24.
5.08	Point for the center S-NW-SE 1/256 sec. cor. of sec. 24, determined at mid-point distance on the N. and S. center line of the NW 1/4 of the SE 1/4 of sec. 24, between the center W-SE 1/64 sec. cor. of sec. 24, and the NW-SE 1/64 sec. cor. of sec. 24. Remove 2004 cor. and reset at the true point.
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 22 ins. in the ground, encircled with a collar of stone, 2 ft. base, to top, with brass cap mkd.
	T 22 N R 29 E S 24 C-S-NW-SE 1/256 2017
	Deposit a magnet, in a white plastic case, at the base of the stainless steel post.
	Set a steel fence post alongside and W. of cor.
	Cor. is located 23 lks. E. of left bank of Black Creek, 40 ft. wide, 2 ft. high, bears S. 20° W. and N. 20° E.
10.17	Point for the NW-SE 1/64 sec. cor. of sec. 24, at intersection with the E. and W. center line of the NW 1/4 of the SE 1/4 of sec. 24.
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.
	T 22 N R 29 E S 24 NW-SE 1/64 2017
	Deposit a magnet, in a white plastic case, at the base of the stainless steel post.
	Set a steel fence post alongside and N. of cor.

Subdivision of Section 24,
T. 22 N., R. 29 E., Gila and Salt River Meridian, Arizona

CHAINS	
	<p>Raise a mound of stone, 2 ft. base, 1 ft. high, W. of cor.</p> <p>Cor. is located 8 lks. E. of left bank of Black Creek, 30 ft. wide, 4 ft. high, bears S. 20° E. and N. 20° W.</p>
12.60	<p>From this point, the W. cor. to beige residential house, a stucco building, 38 x 35 ft., bears E., 45 lks. dist., long side bears S. 65° E.</p>
15.22	<p>Point for the center N-NW-SE 1/256 sec. cor. of sec. 24, determined at mid-point distance on the N. and S. center line of the NW 1/4 of the SE 1/4 of sec. 24, between the NW-SE 1/64 sec. cor. of sec. 24, and the center W-E 1/64 sec. cor. of sec. 24. Remove 2004 cor. and reset at the true point.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T 22 N R 29 E S 24 C-N-NW-SE 1/256 2017</p> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p> <p>Set a steel fence post alongside and W. of cor.</p> <p>From this cor. point, the SW cor. to horse corral, 65 x 58 ft., bears S. 80° E., 1.10 chs. dist., long side bears N. 5° W.</p>
20.28	<p>The center W-E 1/64 sec. cor. of sec. 24.</p> <hr/> <p>From the center N-SE 1/64 sec. cor. of sec. 24.</p> <p>N. 89°48' W., on the E. and W. center line of the NW 1/4 of the SE 1/4 of sec. 24.</p>
10.01	<p>The NW-SE 1/64 sec. cor. of sec. 24.</p>
20.02	<p>The center N-S 1/64 sec. cor. of sec. 24.</p> <hr/> <p>From the center S-NW-SE 1/256 sec. cor. of sec. 24.</p> <p>S. 89°57' W., on the E. and W. center line of the SW 1/4 of the NW 1/4 of the SE 1/4 of sec. 24.</p>
9.99	<p>The center S-N-S 1/256 sec. cor. of sec. 24.</p> <hr/>

Subdivision of Section 24,
T. 22 N., R. 29 E., Gila and Salt River Meridian, Arizona

CHAINS	
	From the center N-NW-SE 1/256 sec. cor. of sec. 24.
	N. 89°23' W., on the E. and W. center line of the NW 1/4 of the NW 1/4 of the SE 1/4 of sec. 24.
10.02	The center N-N-S 1/256 sec. cor. of sec. 24.
	<hr/> SW 1/4 Section 24 <hr/>
	From the true point for the W. 1/16 sec. cor. of sec. 24 and 25.
	N. 0°13' W., on the N. and S. center line of the SW 1/4 of sec. 24.
1.50	N. right-of-way fence of Interstate 40, woven and barbed wire fence, bears E. and W.
1.75	N. Frontage Road to Interstate 40, an asphalt surfaced road, 25 ft. wide, bears E. and W.
2.20	N. right-of-way fence of N. Frontage Road to Interstate 40, barbed wire, 5 strand, bears E. and W., and access to graded road, 30 ft. wide, extends N.
5.02	Point for the center S-S-W 1/256 sec. cor. of sec. 24, determined at the intersection with the N. and S. center line of a partially paved road, and the extension of bearing of the E-W barbed wire fence from the E. Remove 2004 cor. and reset at the true point.
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 6 ins. below partially asphalt surfaced road, with brass cap mkd.
	T 22 N R 29 E S 24 C-S-S-SW 1/256 2017
	from which
	A rebar, 24 ins. long, 5/8 ins. diam., set 23 ins. in the ground for a reference monument, bears S. 89°50' E., 17.2 ft. dist. with 2 in. diam. brass cap mkd. RM 17.2 FT TO COR 2017 and an arrow pointing to the cor. Cor. is located at fence cor. post of barbed wire fences, bears E. and S.

Subdivision of Section 24,
T. 22 N., R. 29 E., Gila and Salt River Meridian, Arizona

CHAINS

A rebar, 24 ins. long, 5/8 ins. diam., set 23 ins. in the ground for a reference monument, bears N. 89°43' W., 21.0 ft. dist. with 2 in. diam. brass cap mkd. RM 21.0 FT TO COR 2017 and an arrow pointing to the cor. Cor. is located 14 lks. W. of the W. edge of partially paved road, bears N. and S.

Deposit a magnet, in a white plastic case, at the base of the stainless steel post.

Cor. is located in center of partially paved road, asphalt patches and dirt, 22 ft. wide, bears N. 0°13' W. and S. 01°21' E.

N. 0°13' W., beginning new measurement, on the N. and S. center line of the SW 1/4 of sec. 24.

4.97

Point for the center S-SW 1/64 sec. cor. of sec. 24, determined at the intersection with the N. and S. center line of a partially paved road, and the extension of bearing of the E-W barbed wire fence from the E. Remove 2004 cor. and reset at the true point.

Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 7 ins. below partially asphalt surfaced road, with brass cap mkd.

T 22 N R 29 E
S 24
C-S-SW
1/64
2017

from which

A rebar, 24 ins. long, 5/8 ins. diam., set 23 ins. in the ground for a reference monument, bears N. 89°50' E., 20.4 ft. dist. with 2 in. diam. brass cap mkd. RM 20.4 FT TO COR 2017 and an arrow pointing to the cor. Cor. is located at fence cor. post of barbed wire fences, bears N., E., and S. Cor. is also located 15 lks. E. of the E. edge of partially paved road, bears N. and S.

A rebar, 24 ins. long, 5/8 ins. diam., set 23 ins. in the ground for a reference monument, bears S. 89°51' W., 20.4 ft. dist. with 2 in. diam. brass cap mkd. RM 20.4 FT TO COR 2017 and an arrow pointing to the cor. Cor. is located 14 lks. W. of the W. edge of partially paved road, bears N. and S.

Deposit a magnet, in a white plastic case, at the base of the stainless steel post.

Subdivision of Section 24,
T. 22 N., R. 29 E., Gila and Salt River Meridian, Arizona

CHAINS	
	<p>Cor. is located in center of partially paved road, asphalt patches and dirt, 22 ft. wide, bears N. and S. 0°13' E.</p> <hr style="width: 20%; margin: 10px auto;"/> <p>NORTH, beginning new measurement, on the N. and S. center line of the SW 1/4 of sec. 24.</p>
5.01	<p>Point for the center N-S-SW 1/256 sec. cor. of sec. 24, determined at the intersection with the N. and S. center line of a partially paved road, and the extension of bearing of the E-W barbed wire fence from the E. Remove 2004 cor. and reset at the true point.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 9 ins. below partially asphalt surfaced road, with brass cap mkd.</p> <p style="text-align: center;">T 22 N R 29 E S 24 C-N-S-SW 1/256 2017</p> <p>from which</p> <p style="padding-left: 40px;">A rebar, 24 ins. long, 5/8 ins. diam., set flush with the surface of the ground for a reference monument, bears N. 89°55' E., 20.2 ft. dist. with 2 in. diam. brass cap mkd. RM 20.2 FT TO COR 2017 and an arrow pointing to the cor. Cor. is located at fence cor. post of barbed wire fences, bears N., E., and S. Cor. is also located 14 lks. E. of the E. edge of partially paved road, bears N. and S.</p> <p style="padding-left: 40px;">A rebar, 24 ins. long, 5/8 ins. diam., set 23 ins. in the ground for a reference monument, bears S. 89°50' W., 20.2 ft. dist. with 2 in. diam. brass cap mkd. RM 20.2 FT TO COR 2017 and an arrow pointing to the cor. Cor. is located 15 lks. W. of the W. edge of partially paved road, bears N. and S.</p> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p> <p>Cor. is located in center of partially paved road, asphalt patches and dirt, 21 ft. wide, bears N. 0°14' E. and S.</p> <hr style="width: 20%; margin: 10px auto;"/> <p>N. 0°14' E., beginning new measurement, on the N. and S. center line of the SW 1/4 of sec. 24.</p>
4.99	<p>Point for the SW 1/16 sec. cor. of sec. 24, determined at the intersection with the N. and S. center line of a partially paved road, and the extension of bearing of the E-W barbed wire fence from the E. Remove 2004 cor. and reset at the true point.</p>

Subdivision of Section 24,
T. 22 N., R. 29 E., Gila and Salt River Meridian, Arizona

CHAINS	<p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 8 ins. below partially asphalt surfaced road, with brass cap mkd.</p> <p style="text-align: center;">T 22 N R 29 E SW 1/16 S 24</p> <p style="text-align: center;">2017</p> <p>from which</p> <p style="padding-left: 40px;">A rebar, 24 ins. long, 5/8 ins. diam., set flush with the surface of the ground for a reference monument, bears N. 89°31' E., 21.2 ft. dist. with 2 in. diam. brass cap mkd. RM 21.2 FT TO COR 2017 and an arrow pointing to the cor. Cor. is located at fence cor. post of barbed wire fences, bears N., E., and S. Cor. is also located 15 lks. E. of the E. edge of partially paved road, bears N. and S.</p> <p style="padding-left: 40px;">A rebar, 24 ins. long, 5/8 ins. diam., set 23 ins. in the ground for a reference monument, bears S. 89°30' W., 21.2 ft. dist. with 2 in. diam. brass cap mkd. RM 21.2 FT TO COR 2017 and an arrow pointing to the cor. Cor. is located 17 lks. W. of the W. edge of partially paved road, bears N. and S.</p> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p> <p>Cor. is located in center of partially paved road, asphalt patches and dirt, 21 ft. wide, bears N. and S. 0°14' W.</p> <hr style="width: 20%; margin: 10px auto;"/> <p>N. 0°01' E., beginning new measurement, on the N. and S. center line of the SW 1/4 of sec. 24.</p> <p>5.08 Point for the center S-N-SW 1/256 sec. cor. of sec. 24, determined at the intersection with the N. and S. center line of a partially paved road, and the extension of bearing of the E-W two track road from the E. Remove 2004 cor. and reset at the true point.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 13 ins. below partially asphalt surfaced road, with brass cap mkd.</p> <p style="text-align: center;">T 22 N R 29 E S 24 C-S-N-SW 1/256</p> <p style="text-align: center;">2017</p> <p>from which</p>
--------	--

Subdivision of Section 24,
T. 22 N., R. 29 E., Gila and Salt River Meridian, Arizona

CHAINS

A rebar, 24 ins. long, 5/8 ins. diam., set flush with the surface of the ground for a reference monument, bears N. 67°33' E., 22.7 ft. dist. with 2 in. diam. brass cap mkd. RM 22.7 FT TO COR 2017 and an arrow pointing to the cor. Cor. is located at fence cor. post of woven and barbed wire fences, bears N. and E. Cor. is also located 17 lks. E. of the E. edge of partially paved road, bears N. and S.

A rebar, 24 ins. long, 5/8 ins. diam., set flush with the surface of the ground for a reference monument, bears S. 67°17' E., 22.8 ft. dist. with 2 in. diam. brass cap mkd. RM 22.8 FT TO COR 2017 and an arrow pointing to the cor. Cor. is located at fence cor. post of woven and barbed wire fences, bears S. and E. Cor. is also located 17 lks. E. of the E. edge of partially paved road, bears N. and S.

Deposit a magnet, in a white plastic case, at the base of the stainless steel post.

Cor. is located in center of partially paved road, asphalt patches and dirt, 23 ft. wide, and at the intersection of a two track road, bears N. 0°15' W., S. 89°51' E., and S.

N. 0°15' W., beginning new measurement, on the N. and S. center line of the SW 1/4 of sec. 24.

5.09

Point for the center N-SW 1/64 sec. cor. of sec. 24, determined at mid-point distance on the N. and S. center line of a partially paved road, between the center S-N-SW 1/256 sec. cor. of sec. 24, and the center N-N-SW 1/256 sec. cor. of sec. 24, established in this survey. Remove 2004 cor. and reset at the true point. Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 8 ins. below partially asphalt surfaced road, with brass cap mkd.

T 22 N R 29 E
S 24
C-N-SW
1/64

2017

from which

A rebar, 24 ins. long, 5/8 ins. diam., set flush with the surface of the ground for a reference monument, bears N. 89°53' E., 20.0 ft. dist. with 2 in. diam. brass cap mkd. RM C-N-SW 1/64 21.2 FT TO COR S24 2017 and an arrow pointing to the cor. Cor. is located in woven and barbed wire fence, bears N. and S. Cor. is also located 13 lks. E. of the E. edge of partially paved road, bears N. and S.

Subdivision of Section 24,
T. 22 N., R. 29 E., Gila and Salt River Meridian, Arizona

CHAINS

A rebar, 24 ins. long, 5/8 ins. diam., set flush with the surface of the ground for a reference monument, bears S. 89°57' W., 25.0 ft. dist. with 2 in. diam. brass cap mkd. RM C-N-SW 1/64 25.0 FT TO COR S24 2017 and an arrow pointing to the cor. Set a steel fence post alongside and W. of cor. Cor. is located 24 lks. W. of the W. edge of partially paved road, bears N. and S.

Deposit a magnet, in a white plastic case, at the base of the stainless steel post.

Cor. is located in center of partially paved road, asphalt patches and dirt, 21 ft. wide, bears N. 0°15' W. and S. 0°16' E.

N. 0°15' W., beginning new measurement, on the N. and S. center line of the SW 1/4 of sec. 24.

5.09 Point for the center N-N-SW 1/256 sec. cor. of sec. 24, determined at the intersection with the N. and S. center line of a partially paved road, and the extension of bearing of the E-W barbed wire fence from the E. Remove 2004 cor. and reset at the true point.

Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 10 ins. below partially asphalt surfaced road, with brass cap mkd.

T 22 N R 29 E
S 24
C-N-N-SW
1/256
2017

from which

A rebar, 24 ins. long, 5/8 ins. diam., set flush with the surface of the ground for a reference monument, bears N. 89°53' E., 17.9 ft. dist. with 2 in. diam. brass cap mkd. RM C-N-N-SW 1/256 17.9 FT TO COR S24 2017 and an arrow pointing to the cor. Cor. is located at fence cor. post of barbed wire fences, bears N. and E. Cor. is also located 12 lks. E. of the E. edge of partially paved road, bears N. and S.

A rebar, 24 ins. long, 5/8 ins. diam., set flush with the surface of the ground for a reference monument, bears N. 89°59' W., 30.0 ft. dist. with 2 in. diam. brass cap mkd. RM C-N-N-SW 1/256 30.0 FT TO COR S24 2017 and an arrow pointing to the cor. Set a steel fence post alongside and W. of cor. Cor. is located 30 lks. W. of the W. edge of partially paved road, bears N. and S.

Deposit a magnet, in a white plastic case, at the base of the stainless steel post.

Subdivision of Section 24,
T. 22 N., R. 29 E., Gila and Salt River Meridian, Arizona

CHAINS	
	<p>Cor. is located in center of partially paved road, asphalt patches and dirt, 21 ft. wide, bears S. 0°15' E. and N. 0°15' W.</p> <hr style="width: 20%; margin: 10px auto;"/> <p>N. 0°15' W., beginning new measurement, on the N. and S. center line of the SW 1/4 of sec. 24.</p>
4.85	<p>The center W. 1/16 sec. cor. of sec. 24.</p> <hr style="width: 20%; margin: 10px auto;"/> <p>From the center S. 1/16 sec. cor. of sec. 24.</p> <p>N. 89°34' W., on the E. and W. center line of the SW 1/4 of sec. 24.</p>
9.45	<p>Point for the center E-SW 1/64 sec. cor. of sec. 24, determined at the center of a bladed dirt road, and at mid-point distance between two fence corner post of fences, opposite of each other, extending N., E., and S., and N., S., and W. Remove 2004 cor. and reset at the true point.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 2 ins. below bladed dirt road, with brass cap mkd.</p> <p style="text-align: center;">T 22 N R 29 E S 24 C-E-SW 1/64 2017</p> <p>from which</p> <p style="padding-left: 40px;">A rebar, 24 ins. long, 5/8 ins. diam., set flush with the surface of the ground for a reference monument, bears S. 84°06' E., 8.2 ft. dist. with 2 in. diam. brass cap mkd. RM S24 C-E-SW 8.2 FT TO COR 1/64 2017 and an arrow pointing to the cor. Cor. is located at fence cor. post of woven and barbed wire fences, bears N., E., and S.</p> <p style="padding-left: 40px;">A rebar, 24 ins. long, 5/8 ins. diam., set flush with the surface of the ground for a reference monument, bears N. 84°36' W., 8.1 ft. dist. with 2 in. diam. brass cap mkd. RM S24 C-E-SW 8.1 FT TO COR 1/64 2017 and an arrow pointing to the cor. Cor. is located at fence cor. post of woven and barbed wire fences, bears N., S., and W.</p> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p> <p>Cor. is located in center of bladed dirt road, 13 ft. wide, bears N. 0°26' E. and S. 0°11' W.</p> <hr style="width: 20%; margin: 10px auto;"/>

Subdivision of Section 24,
T. 22 N., R. 29 E., Gila and Salt River Meridian, Arizona

CHAINS	
	S. 89°32' W., beginning new measurement, on the E. and W. center line of the SW 1/4 of sec. 24.
9.51	The SW 1/16 sec. cor. of sec. 24. <hr/>
	N. 89°59' W., beginning new measurement, on the E. and W. center line of the SW 1/4 of sec. 24.
18.63	The S. 1/16 sec. cor. of secs. 23 and 24. <hr/>
	From the E-SW 1/64 sec. cor. of sec. 24.
	N. 0°10' W., on the N. and S. center line of the NE 1/4 of the SW 1/4 of sec. 24.
4.98	Point for the center S-NE-SW 1/256 sec. cor. of sec. 24, determined at the intersection with the E. and W. center line of a two track road, and the extension of bearing of the N-S bladed dirt road from the S. Remove 2004 cor. and reset at the true point. Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 6 ins. below two track road, with brass cap mkd. <div style="text-align: center;"> T 22 N R 29 E S 24 C-S-NE-SW 1/256 2017 </div> from which <div style="text-align: center;"> A rebar, 24 ins. long, 5/8 ins. diam., set flush with the surface of the ground for a reference monument, bears S. 22°03' W., 10.1 ft. dist. with 2 in. diam. brass cap mkd. RM S24 C-S-NE-SW 10.1 FT TO COR 1/256 2017 and an arrow pointing to the cor. Cor. is located at fence cor. post of woven and barbed wire fences, bears S. and W. </div> Deposit a magnet, in a white plastic case, at the base of the stainless steel post. Cor. is located in two track road, near intersection of 5-way cross roads, extending N. 4° E., N. 51° E., E., S. and W. <hr/> N. 0°48' E., beginning new measurement.

Subdivision of Section 24,
T. 22 N., R. 29 E., Gila and Salt River Meridian, Arizona

CHAINS	
5.11	<p>Point for the NE-SW 1/64 sec. cor. of sec. 24, determined at mid-point distance on the N. and S. center line of the NE 1/4 of the SW 1/4 of sec. 24, between the center S-NE-SW 1/256 sec. cor. of sec. 24, and the center N-NE-SW 1/256 sec. cor. of sec. 24, established in this survey. Remove 2004 cor. and reset at the true point.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., flush with the surface of the ground, with brass cap mkd.</p> <p style="text-align: center;">T 22 N R 29 E S 24 NE-SW 1/64 2017</p> <p>from which</p> <p style="padding-left: 40px;">A rebar, 24 ins. long, 5/8 ins. diam., set flush with the surface of the ground for a reference monument, bears N. 89°58' E., 21.2 ft. dist. with 2 in. diam. brass cap mkd. RM S24 NE-SW 21.2 FT TO COR 1/64 2017 and an arrow pointing to the cor. Cor. is located 1 lk. W. of chain link fence to enclosed residential property, bears N. and S.</p> <p style="padding-left: 40px;">A rebar, 24 ins. long, 5/8 ins. diam., set flush with the surface of the ground for a reference monument, bears N. 89°48' W., 8.3 ft. dist. with 2 in. diam. brass cap mkd. RM S24 NE-SW 8.3 FT TO COR 1/64 2017 and an arrow pointing to the cor. Cor. is located 1 lk. E. of barbed wire fence to enclosed uncultivated field, bears N. and S.</p> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p> <p>Cor. is located 13 lks. E. from center of bladed dirt road, 12 ft. wide, bears N. 1°39' E. and S. 1°39' W.</p>
10.22	<p>Point for the center N-NE-SW 1/256 sec. cor. of sec. 24, determined at the intersection with the E. and W. woven and barbed wire fence, and the extension of bearing of the N-S dilapidated two track road from the N. Remove 2004 cor. and reset at the true point.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 23 ins. in the ground, underpinned with a steel fence post, 60 ins. long, with brass cap mkd.</p>

Subdivision of Section 24,
T. 22 N., R. 29 E., Gila and Salt River Meridian, Arizona

CHAINS	
	<p style="text-align: center;">T 22 N R 29 E S 24 C-N-NE-SW 1/256</p> <p style="text-align: center;">2017</p> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p> <p>Cor. is located in broken woven and barbed wire fence to uncultivated field, bears E. and W., and is also located in center of an dilapidated two track road, extending N.</p> <p>Cor. is also located 11 lks. W. of wood fence cor. post of woven and barbed wire fences, extending N. 01° E. and W., and is 50 lks. W. of a bladed dirt road, 15 ft. wide, curving N. 40° E. and S. 40° W.</p>
15.10	<p>The center E-W 1/64 sec. cor. of sec. 24.</p> <hr/> <p>From the center N-S 1/64 sec. cor. of sec. 24.</p> <p>N. 89°57' W., on the E. and W. center line of the NE 1/4 of the SW 1/4 of sec. 24.</p>
1.15	Blade dirt road, 15 ft. wide, bears N. 60° E. and S. 60° W.
9.25	Blade dirt road, 12 ft. wide, bears N. 1°39' E. and S. 1°39' W.
9.37	The NE-SW 1/64 sec. cor. of sec. 24.
18.96	<p>The center N-SW 1/64 sec. cor. of sec. 24.</p> <hr/> <p>From the center N-N-S 1/256 sec. cor. of sec. 24.</p> <p>S. 89°56' W., on the E. and W. center line of the NE 1/4 of the NE 1/4 of the SW 1/4 of sec. 24.</p>
8.80	Blade dirt road, 15 ft. wide, bears N. 40° E. and S. 40° W.
9.28	<p>The center N-NE-SW 1/256 sec. cor. of sec. 24.</p> <hr/> <p>From the center S-N-S 1/256 sec. cor. of sec. 24.</p> <p>N. 89°51' W., on the E. and W. center line of the SE 1/4 of the NE 1/4 of the SW 1/4 of sec. 24.</p>
9.47	<p>The center S-NE-SW 1/256 sec. cor. of sec. 24.</p> <hr/>

Subdivision of Section 24,
T. 22 N., R. 29 E., Gila and Salt River Meridian, Arizona

CHAINS	
	N. 89°51' W., on the E. and W. center line of the SW 1/4 of the NE 1/4 of the SW 1/4 of sec. 24.
9.50	The center S-N-SW 1/256 sec. cor. of sec. 24.
	From the center N-NE-SW 1/256 sec. cor. of sec. 24.
	S. 89°56' W., on the E. and W. center line of the NW 1/4 of the NE 1/4 of the SW 1/4 of sec. 24.
9.69	The center N-N-SW 1/256 sec. cor. of sec. 24.
	From the true point for the E-W 1/64 sec. cor. of sec. 24 and 25.
	N. 0°45' W., on the N. and S. center line of the SE 1/4 of the SW 1/4 of sec. 24.
1.50	N. right-of-way fence of Interstate 40, woven and barbed wire fence, bears E. and W.
1.80	N. Frontage Road to Interstate 40, an asphalt surfaced road, 25 ft. wide, bears E. and W.
2.20	N. right-of-way fence of N. Frontage Road to Interstate 40, barbed wire, 5 strand, bears E. and W., and access to bladed dirt road, 22 ft. wide, extends N.
5.01	Point for the center S-SE-SW 1/256 sec. cor. of sec. 24, determined at the center of a bladed dirt road, and at mid-point distance between two fence corner post of fences, opposite of each other, extending N., E., and S., and W. Remove 2004 cor. and reset at the true point.
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 4 ins. below bladed dirt road, with brass cap mkd.
	T 22 N R 29 E S 24 C-S-SE-SW 1/256 2017
	from which
	A rebar, 24 ins. long, 5/8 ins. diam., set flush with the surface of the ground for a reference monument, bears S. 87°04' E., 15.2 ft. dist. with 2 in. diam. brass cap mkd. RM S24 C-S-SE-SW 15.2 FT TO COR 1/256 2017 and an arrow pointing to the cor. Cor. is located at fence cor. post of barbed wire fences, bears N., E., and S.

Subdivision of Section 24,
T. 22 N., R. 29 E., Gila and Salt River Meridian, Arizona

CHAINS	<p>A rebar, 24 ins. long, 5/8 ins. diam., set flush with the surface of the ground for a reference monument, bears N. 87°15' W., 15.2 ft. dist. with 2 in. diam. brass cap mkd. RM S24 C-S-SE-SW 15.2 FT TO COR 1/256 2017 and an arrow pointing to the cor. Cor. is located at the terminus of remnants of a fence cor. post of barbed wire fence, extending W.</p> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p> <p>Cor. is located in center of bladed dirt road, 20 ft. wide, bears N. 01° E. and S. 01° W.</p> <p>From this cor. point, a rebar, 5/8 in. diam., of unknown origin, firmly set, projecting 3 1/2 ins. above ground, bears S. 89°49' W., 2.41 lks. dist.</p> <hr style="width: 20%; margin: 10px auto;"/> <p>N. 01°00' E., beginning new measurement, on the N. and S. center line of the SE 1/4 of the SW 1/4 of sec. 24.</p>
5.04	<p>Point for the SE-SW 1/64 sec. cor. of sec. 24, determined at the center of a bladed dirt road, and at mid-point distance between two fence corner post of fences, opposite of each other, extending N., E., and S., and N. and W. Remove 2004 cor. and reset at the true point.</p> <p>Set a stainless steel post, 28 ins. long, cut to 24 ins., 2 1/2 ins. diam., 3 ins. below bladed dirt road, with brass cap mkd.</p> <p style="text-align: center;">T 22 N R 29 E S 24 SE-SW 1/64 2017</p> <p>from which</p> <p>A rebar, 24 ins. long, 5/8 ins. diam., set 2 ins. below the surface of the ground for a reference monument, bears N. 89°23' E., 9.1 ft. dist. with 2 in. diam. brass cap mkd. RM S24 SE-SW 9.1 FT TO COR 1/64 2017 and an arrow pointing to the cor. Cor. is located in driveway entrance to enclosed residential property, and at the extension of bearing of the N., E., and S. barbed wire fences.</p> <p>A rebar, 24 ins. long, 5/8 ins. diam., set flush with the surface of the ground for a reference monument, bears S. 89°42' W., 9.1 ft. dist. with 2 in. diam. brass cap mkd. RM S24 SE-SW 9.1 FT TO COR 1/64 2017 and an arrow pointing to the cor. Cor. is located at fence cor. post of barbed wire fences, bears N. and W.</p>

Subdivision of Section 24,
T. 22 N., R. 29 E., Gila and Salt River Meridian, Arizona

CHAINS	
5.01	<p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p> <p>Cor. is located in center of bladed dirt road, 14 ft. wide, bears N. and S. 01° W.</p> <hr style="width: 20%; margin: 10px auto;"/> <p>N. 0°06' W., beginning new measurement, on the N. and S. center line of the SE 1/4 of the SW 1/4 of sec. 24.</p> <p>Point for the center N-SE-SW 1/256 sec. cor. of sec. 24, determined at the center of a bladed dirt road, and at mid-point distance between two fence corner post of fences, opposite of each other, extending E. and S., and N., S., and W. Remove 2004 cor. and reset at the true point.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 2 ins. below bladed dirt road, with brass cap mkd.</p> <p style="text-align: center;">T 22 N R 29 E S 24 C-N-SE-SW 1/256 2017</p> <p>from which</p> <p style="padding-left: 40px;">A rebar, 24 ins. long, 5/8 ins. diam., set flush with the surface of the ground for a reference monument, bears S. 89°20' E., 9.4 ft. dist. with 2 in. diam. brass cap mkd. RM S24 C-N-SE-SW 9.4 FT TO COR 1/256 2017 and an arrow pointing to the cor. Cor. is located at fence cor. post of barbed wire fences, bears E. and S.</p> <p style="padding-left: 40px;">A rebar, 24 ins. long, 5/8 ins. diam., set flush with the surface of the ground for a reference monument, bears N. 89°01' W., 9.4 ft. dist. with 2 in. diam. brass cap mkd. RM S24 C-N-SE-SW 9.4 FT TO COR 1/256 2017 and an arrow pointing to the cor. Cor. is located at fence cor. post of barbed wire fences, bears N., S., and W.</p> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p> <p>Cor. is located in center of bladed dirt road, 13 ft. wide, bears N. and S.</p> <hr style="width: 20%; margin: 10px auto;"/> <p>N. 0°11' E., beginning new measurement, on the N. and S. center line of the SE 1/4 of the SW 1/4 of sec. 24.</p>
5.05	<p>The center E-SW 1/64 sec. cor. of sec. 24.</p> <hr style="width: 20%; margin: 10px auto;"/>

Subdivision of Section 24,
T. 22 N., R. 29 E., Gila and Salt River Meridian, Arizona

CHAINS	
	From the center S-S 1/64 sec. cor. of sec. 24.
	S. 89°25' W., on the E. and W. center line of the SE 1/4 of the SW 1/4 of sec. 24.
9.32	The SE-SW 1/64 sec. cor. of sec. 24.

	S. 89°51' W., beginning new measurement, on the E. and W. center line of the SE 1/4 of the SW 1/4 of sec. 24.
9.53	The center S-SW 1/64 sec. cor. of sec. 24.

	From the center N-S-S 1/256 sec. cor. of sec. 24.
	N. 89°55' W., on the E. and W. center line of the NE 1/4 of the SE 1/4 of the SW 1/4 of sec. 24.
9.41	The center N-SE-SW 1/256 sec. cor. of sec. 24.

	From the center S-S-S 1/256 sec. cor. of sec. 24.
	N. 89°49' W., on the E. and W. center line of the SE 1/4 of the SE 1/4 of the SW 1/4 of sec. 24.
9.42	The center S-SE-SW 1/256 sec. cor. of sec. 24.

	N. 89°45' W., on the E. and W. center line of the SW 1/4 of the SE 1/4 of the SW 1/4 of sec. 24.
9.42	The center S-S-SW 1/256 sec. cor. of sec. 24.

	From the center N-SE-SW 1/256 sec. cor. of sec. 24.
	S. 89°52' W., on the E. and W. center line of the NW 1/4 of the SE 1/4 of the SW 1/4 of sec. 24.
9.52	The center N-S-SW 1/256 sec. cor. of sec. 24.

	NW 1/4 Section 24

	From the center W. 1/16 sec. cor. of sec. 24.
	N. 0°21' E., on the N. and S. center line of the NW 1/4 of sec. 24.
19.99	Point for the NW 1/16 sec. cor. of sec. 24, at intersection with the E. and W. center line of the NW 1/4 of sec. 24. Remove 2004 cor.

Subdivision of Section 24,
T. 22 N., R. 29 E., Gila and Salt River Meridian, Arizona

CHAINS	
	<p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 11 ins. below partially asphalt surfaced road, with brass cap mkd.</p> <p style="text-align: center;">T 22 N R 29 E NW 1/16 S 24</p> <p style="text-align: center;">2017</p> <p>from which</p> <p>A stainless steel post, 28 ins. long, 2 1/2 ins. diam., set 24 ins. in the ground for a reference monument, bears N. 89°56' E., 10.0 ft. dist. with brass cap mkd. RM T22N R29E NW 1/16 10.0 FT TO COR S24 2017 and an arrow pointing to the cor. Deposit a magnet, in a white plastic case, at the base of the stainless steel post. Cor. is located in woven and barbed wire fence to enclosed uncultivated field, bears N. 5° E. and S. Cor. is also located 9 lks. E. of the E. edge of partially paved road, bears N. 10° E. and S.</p> <p>A stainless steel post, 28 ins. long, 2 1/2 ins. diam., set 26 ins. in the ground for a reference monument, bears S. 89°52' W., 25.0 ft. dist. with brass cap mkd. RM T22N R29E NW 1/16 25.0 FT TO COR S24 2017 and an arrow pointing to the cor. Deposit a magnet, in a white plastic case, at the base of the stainless steel post, and set a steel fence post alongside and W. of cor. Cor. is also located 17 lks. W. of the W. edge of partially paved road, bears N. 10° E. and S.</p> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p> <p>Cor. is located 7 lks. E. of center of partially paved road, asphalt patches and dirt, 20 ft. wide, bears N. 10° E. and S.</p>
39.98	<p>The W. 1/16 sec. cor. of secs. 13 and 24.</p> <hr/> <p>From the center N. 1/16 sec. cor. of sec. 24.</p> <p>S. 89°47' W., on the E. and W. center line of the NW 1/4 of sec. 24.</p>
12.00	<p>Intersect barbed wire fence to enclosed uncultivated field, bears N. 05° E. and S. 05° W.</p>
18.87	<p>The NW 1/16 sec. cor. of sec. 24.</p>
18.95	<p>Partially paved road, asphalt patches and dirt, 20 ft. wide, bears N. 10° E. and S.</p>

Subdivision of Section 24,
T. 22 N., R. 29 E., Gila and Salt River Meridian, Arizona

CHAINS 37.52	<p>The N. 1/16 sec. cor. of secs. 23 and 24.</p> <hr/> <p style="text-align: center;">Subdivision of Section 25, T. 22 N., R. 29 E., Gila and Salt River Meridian, Arizona</p> <hr/> <p>From the 1/4 sec. cor. of secs. 25 and 36.</p> <p>N. 0°12' W., on the N. and S. center line of sec. 25.</p> <p>Over gently rolling land.</p>
35.00	Northern most fence to Sand Quarry, broken fence, 2 strand, bears E. and W.
39.52	<p>Point for the center 1/4 sec. cor. of sec. 25, determined at the intersection with the E. and W. center line of sec. 25, and the extension of bearing of the N-S barbed wire fence from the N. Remove 2004 cor. and reset at the true point.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 10 ins. in sandstone bedrock, in a supporting mound of stone, 4 ft. base, to top, with brass cap mkd.</p> <p style="text-align: center;">T 22 N R 29 E C 1/4 S 25</p> <p style="text-align: center;">2017</p> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post. Cor. is located 7.5 lks. E. of a series of wood posts, bears N. and S.</p>
40.70	Telephone line, bears N. 85° E. and S. 85° W.
47.50	Wood fence cor. post of barbed wire fences, bears S. 75° E. and N. 0°12' W.
59.35	<p>Point for the center N. 1/16 sec. cor. of sec. 25, determined at the intersection of the N. and S. center line of sec. 25, and the extension of bearing of the E-W barbed wire fence from the W. Remove 2004 cor., and reset at the true point.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T 22 N R 29 E C N 1/16 S 25 C</p> <p style="text-align: center;">2017</p>

Subdivision of Section 25,
T. 22 N., R. 29 E., Gila and Salt River Meridian, Arizona

CHAINS	
	<p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p> <p>Cor. is located 5 lks. W. of a woven and barbed wire fence, bears N. and S.</p>
67.55	Intersect meandering woven and barbed wire fence, parallels right bank of Black Creek, bears N. 10° E.
68.90	Power line, 4 strand, bears N. 85° W. and S. 85° E.
69.245	<p>Point for the center N-N 1/64 sec. cor. of sec. 25, determined at mid-point distance on the N. and S. center line of sec. 25, between the center N. 1/16 sec. cor. of sec. 25, and the true point for the 1/4 sec. cor. of secs. 24 and 25. Remove 2004 cor., and reset at the true point.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T 22 N R 29 E S 25 C-N-N 1/64 2017</p> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p> <p>Set a steel fence post alongside and N. of cor. Cor. is located 13 lks. W. of a meandering woven and barbed wire fence, bears N. and S.</p> <p>From this cor. point, a wood fence cor. post of woven and barbed wire fences, extending N., and S. 10° E., bears N. 08°10' E., 46 lks. dist.</p>
75.95	S. right-of-way fence of S. Frontage Road to Interstate 40, barbed wire, 5 strand, bears E. and W.
76.40	S. Frontage Road to Interstate 40, an asphalt surfaced road, 20 ft. wide, bears E. and W.
76.80	S. right-of-way fence of Interstate 40, barbed wire, 5 strand, bears E. and W.
77.35	Interstate 40 east bound lane, an asphalt surfaced road, bears N. 89°52' E. and S. 89°52' W.
79.14	The true point for the 1/4 sec. cor. of secs. 24 and 25.

Subdivision of Section 25,
T. 22 N., R. 29 E., Gila and Salt River Meridian, Arizona

CHAINS	
	<p>From the 1/4 sec. cor. of sec. 25 only, on the E. bdy. of the Tp., hereinbefore described.</p> <p>N. 89°37' W., on the E. and W. center line of sec. 25.</p> <p>Over gently rolling land.</p>
18.67	<p>Point for the center E. 1/16 sec. cor. of sec. 25, determined at the E. and W. center line of sec. 25, and the extension of bearing of the N-S barbed wire fence from the N. Remove 2004 cor. and reset at the true point.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T 22 N R 29 E E 1/16 C———C S 25</p> <p style="text-align: center;">2017</p> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p> <p>Set a steel fence post alongside and N. of cor.</p> <p>Cor. is located 1.85 chs. E. of a meandering barbed wire fence, 4 strand, bears S. 5° E. and N. 5° W.</p>
37.48	<p>The center 1/4 sec. cor. of sec. 25.</p>
47.12	<p>Point for the center E-W 1/64 sec. cor. of sec. 25, determined at the intersection of the E. and W. center line of sec. 25, and the extension of bearing of the N-S barbed wire fence from the N. Remove 2004 cor. and reset at the true point.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T 22 N R 29 E S 25 C-E-W 1/64</p> <p style="text-align: center;">2017</p> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p> <p>Set a steel fence post alongside and N. of cor.</p> <p>Cor. is located 8 lks. W. of barbed wire fence, 4 strand, bears N. and S.</p>

Subdivision of Section 25,
T. 22 N., R. 29 E., Gila and Salt River Meridian, Arizona

CHAINS	
56.57	<p>Point for the center W. 1/16 sec. cor. of sec. 25, determined at the intersection of the E. and W. center line of sec. 25, and the extension of bearing of the N-S main bladed dirt road from the N. Remove 2004 cor. and reset at the true point.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 21 ins. in the ground to bedrock, encircled with a collar of stone, 3 ft. base, to top, with brass cap mkd.</p> <div style="text-align: center;"> <p>T 22 N R 29 E W 1/16 C-----C S 25</p> <p>2017</p> </div> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p> <p>Set a steel fence post alongside and N. of cor.</p> <p>Cor. is located 11 lks. E. of barbed wire fence, 4 strand, bears N. and S.</p>
75.08	<p>The 1/4 sec. cor. of secs. 25 and 26.</p> <hr style="width: 50%; margin: 10px auto;"/> <div style="text-align: center;"> <p>NE 1/4 Section 25</p> <hr style="width: 50%; margin: 10px auto;"/> </div> <p>From the center E. 1/16 sec. cor. of sec. 25. N. 0°08' W., on the N. and S. center line of the NE 1/4 of sec. 25.</p>
10.60	<p>Wood fence cor. post of barbed wire fences, bears S. 70° W. and N. 0°08' W.</p>
36.54	<p>The witness cor. to the E. 1/16 sec. cor. of sec. 25 only, at the S. right-of-way fence of S. Frontage Road to Interstate 40, barbed wire, 5 strand, bears E. and W.</p>
36.95	<p>S. Frontage Road to Interstate 40, an asphalt surfaced road, 20 ft. wide, bears S. 89° E. and N. 89° W.</p>
37.30	<p>S. right-of-way fence of Interstate 40, barbed wire, 5 strand, bears S. 88° E. and W.</p>
37.95	<p>Interstate 40 east bound lane, an asphalt surfaced road, bears N. 89°48' E. and S. 89°48' W.</p>
39.70	<p>The true point for the E. 1/16 sec. cor. of sec. 25 only.</p> <hr style="width: 50%; margin: 10px auto;"/> <div style="text-align: center;"> <p>SE 1/4 Section 25</p> <hr style="width: 50%; margin: 10px auto;"/> </div>

Subdivision of Section 25,
T. 22 N., R. 29 E., Gila and Salt River Meridian, Arizona

CHAINS	
	From the E. 1/16 sec. cor. of secs. 25 and 36.
	N. 0°08' W., on the N. and S. center line of the SE 1/4 of sec. 25.
30.55	N. right-of-way fence of the Burlington Northern Santa Fe Rail Road, a woven wire fence, bears N. 85° E. and S. 85° W.
39.39	The center E. 1/16 sec. cor. of sec. 25.
<hr/> SW 1/4 Section 25 <hr/>	
	From the W. 1/16 sec. cor. of secs. 25 and 36.
	N. 0°10' E., on the N. and S. center line of the SW 1/4 of sec. 25.
35.15	Series of wood fence posts to Sand Quarry, no barbed wire, bears E. and W.
39.65	The center W. 1/16 sec. cor. of sec. 25.
<hr/>	
	From the E-W 1/64 sec. cor. of sec. 25 and 36.
	N. 0°11' E., on the N. and S. center line of the E 1/2 of the SW 1/4 of sec. 25.
39.58	The center E-W 1/64 sec. cor. of sec. 25.
<hr/> NW 1/4 Section 25 <hr/>	
	From the center W. 1/16 sec. cor. of sec. 25.
	N. 0°10' E., on the N. and S. center line of the NW 1/4 of sec. 25.
1.30	Telephone line, bears E. and W.
9.65	Wood fence cor. post of barbed wire fences, bears N. 01° E., S. 85° E., S. 01° W., and N. 85° W.
19.87	Point for the NW 1/16 sec. cor. of sec. 25, determined at the intersection of the E. and W. center line of the NW 1/4 of sec. 25, and the extension of bearing of the N-S main bladed dirt road from the N. Remove 2004 cor. and reset at the true point.
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, encircled with a collar of stone, 1 1/2 ft. base, to top, with brass cap mkd.

Subdivision of Section 25,
T. 22 N., R. 29 E., Gila and Salt River Meridian, Arizona

CHAINS	
	T 22 N R 29 E NW 1/16 S 25 2017
	Deposit a magnet, in a white plastic case, at the base of the stainless steel post. Set a steel fence post alongside and N. of cor. Cor. is located 11 lks. W. of barbed wire fence, 4 strand, bears N. and S. From this cor. point, a rebar, 1/2 in. diam., of unknown origin, firmly set, projecting 2 ins. above ground, with a steel fence post alongside and SW of cor., bears S. 25°07' W., 4.06 chs. dist.
29.70	Point for the center N-NW 1/64 sec. cor. of sec. 25, determined at the intersection of the center of main bladed dirt road, and at mid-point distance on the N. and S. center line of the NW 1/4 of sec. 25, between the NW 1/16 sec. cor. of sec. 25, and the true point for the W. 1/16 sec. cor. of secs. 24 and 25. Remove 2004 cor. and reset at the true point. Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 3 ins. below bladed dirt road, with brass cap mkd.
	T 22 N R 29 E C-N-NW 1/64 S 25 2017
	from which A rebar, 24 ins. long, 5/8 ins. diam., set flush with the surface of the ground for a reference monument, bears S. 89°20' E., 9.0 ft. dist. with 2 in. diam. brass cap mkd. RM S25 C-N-NW 9.0 FT TO COR 1/64 2017 and an arrow pointing to the cor. Cor. is located 1 lk. W. of barbed wire fence, 4 strand, bears N. and S. Deposit a magnet, in a white plastic case, at the base of the stainless steel post. Cor. is located in center of bladed dirt road, 13 ft. wide, bears N. and S. From this cor. point, a utility pole to power line, 4 strand, extends S. 88° E. and N. 88° W., bears N. 68°13' W., 42 lks. dist.
36.30	S. right-of-way fence of S. Frontage Road to Interstate 40, barbed wire, 5 strand, bears E. and W.

Subdivision of Section 25,
T. 22 N., R. 29 E., Gila and Salt River Meridian, Arizona

CHAINS	
36.80	S. Frontage Road to Interstate 40, an asphalt surfaced road, 20 ft. wide, bears E. and W.
37.20	S. right-of-way fence of Interstate 40, barbed wire, 5 strand, bears E. and W.
37.75	Interstate 40 east bound lane, an asphalt surfaced road, bears E. and W.
39.54	The true point for the W. 1/16 sec. cor. of secs. 24 and 25.
	<hr/>
	From the center N. 1/16 sec. cor. of sec. 25.
	N. 89°30' W., on the E. and W. center line of the NW 1/4 of sec. 25.
9.50	Point for the center E-NW 1/64 sec. cor. of sec. 25, determined at the intersection of the E. and W. center line of the NW 1/4 of sec. 25, and the extension of bearing of the remnants of a N-S barbed wire fence from the N. Remove 2004 cor. and reset at the true point.
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.
	T 22 N R 29 E S 25 C-E-NW 1/64 2017
	Deposit a magnet, in a white plastic case, at the base of the stainless steel post.
	Cor. is located in barbed wire fence, 5 strand, bears N. and S.
18.96	The NW 1/16 sec. cor. of sec. 25.
37.54	The N. 1/16 sec. cor. of secs. 25 and 26.
	<hr/>
	From the center E-NW 1/64 sec. cor. of sec. 25.
	N. 0°11' E., on the N. and S. center line of the NE 1/4 of the NW 1/4 of sec. 25.
9.86	Point for the NE-NW 1/64 sec. cor. of sec. 25, determined at the intersection of the remains of the N-S barbed wire fence, now a series of wood posts, and the E. and W. center line of the NE 1/4 of the NW 1/4 of sec. 25. Remove 2004 cor. and reset at the true point.

Subdivision of Section 25,
T. 22 N., R. 29 E., Gila and Salt River Meridian, Arizona

CHAINS	
	<p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T 22 N R 29 E S 25 NE-NW 1/64 2017</p> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p> <p>Set a steel fence post alongside and N. of cor.</p> <p>Cor. is located in a series of wood posts, once serving as the original fence boundary to Navajo Trust land to the W., and Indian Allotment to the E. Chris Nelson, a long time resident of the Indian Allotment to the E., testified that he is a descendent of Ralph Nelson Sr. and Ralph Nelson Jr., and that he witnessed the removal and relocation of the original fence line, further west, to the 2004 survey monuments. Based on evidence of the continuation of the original fence line to the south, across Black Creek, the series of wood posts are in substantial agreement with the N. and S. center line of the NE 1/4 of the NW 1/4 of sec. 25, with an overall bearing of N. 0°11' E. and S. 0°11' W.</p> <p>From this cor. point, a utility pole to power line, 4 strand, extends S. 88° E. and N. 88° W., bears S. 86°39' W., 1.25 chs. dist.</p>
16.50	S. right-of-way fence of S. Frontage Road to Interstate 40, barbed wire, 5 strand, bears E. and W.
17.00	S. Frontage Road to Interstate 40, an asphalt surfaced road, 20 ft. wide, bears E. and W.
17.40	S. right-of-way fence of Interstate 40, barbed wire, 5 strand, bears E. and W.
17.90	Interstate 40 east bound lane, an asphalt surfaced road, bears E. and W.
19.72	The true point for the E-W 1/64 sec. cor. of secs. 24 and 25.
	<hr/> <p>From the center N-N 1/64 sec. cor. of sec. 25.</p> <p>N. 89°41' W., on the E. and W. center line of the NE 1/4 of the NW 1/4 of sec. 25.</p>
9.43	The NE-NW 1/64 sec. cor. of sec. 25.
13.60	Power line, 4 strand, bears S. 88° E. and N. 88° W.

Subdivision of Section 25,
T. 22 N., R. 29 E., Gila and Salt River Meridian, Arizona

CHAINS	
18.90	<p>The center N-NW 1/64 sec. cor. of sec. 25.</p> <hr/> <p>From the center E-W 1/64 sec. cor. of sec. 25.</p> <p>N. 0°11' E., on the N. and S. center line of the SE 1/4 of the NW 1/4 of sec. 25.</p>
1.10	Telephone line, bears E. and W.
16.00	Wood fence cor. post of barbed wire fences, 5 strand, bears N. and N. 80° W.
19.85	The center E-NW 1/64 sec. cor. of sec. 25.
<hr/> <p>Subdivision of Section 26, T. 22 N., R. 29 E., Gila and Salt River Meridian, Arizona</p> <hr/>	
	<p>From the 1/4 sec. cor. of secs. 26 and 35.</p> <p>N. 0°16' W., on the N. and S. center line of sec. 26.</p> <p>Over gently rolling land.</p>
20.00	<p>Point for the center S. 1/16 sec. cor. of sec. 26, determined by bearing-bearing intersection between the cors. of the SE 1/4 sec. cor. of sec. 26 and the SW 1/4 sec. cor. of sec. 26, on the N. and S. center line of sec. 26. Remove 2004 cor. and reset at the true point.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 25 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center;"> <p>T 22 N R 29 E</p> <p style="margin-left: 100px;">C</p> <p>S 1/16 S 26</p> <p style="margin-left: 100px;">C</p> <p>2017</p> </div> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p> <p>Set a steel fence post alongside and W. of cor.</p> <p>Cor. is located 21 lks. N. and 20 lks. E. of a woven and barbed wire fence, bears S. 30° E. and N. 30° W.</p> <p>From this cor. point, wood fence cor. post serves as the terminus to a barbed wire fence, 4 strand, extends N., bears N. 2°52' E., 1.17 chs. dist.</p>

Subdivision of Section 26,
T. 22 N., R. 29 E., Gila and Salt River Meridian, Arizona

CHAINS	
39.82	<p>Point for the center 1/4 sec. cor. of sec. 26, determined at the corner of barbed wire fences. The fence cor. post is accepted as a careful and faithful determination of the cor. point. Remove 2004 cor. and reset at the true point.</p> <p>At the corner point</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 25 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T 22 N R 29 E C 1/4 S 26</p> <p style="text-align: center;">2017</p> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p> <p>Cor. is located at the N. base of wood fence cor. post of woven and barbed wire fences, extending S. 89° E. and W., and barbed wire fence, 4 strand, extends S. 01° E.</p> <hr style="width: 20%; margin: 10px auto;"/> <p>N. 0°16' W., beginning new measurement, on the N. and S. center line of sec. 26.</p>
19.93	<p>Point for the center N. 1/16 sec. cor. of sec. 26, determined at the intersection of the N. and S. center line of sec. 26, and the extension of bearing of the E-W barbed wire fence from the E.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T 22 N R 29 E C N 1/16 S 26 C</p> <p style="text-align: center;">2017</p> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p> <p>Set a steel fence post nearby.</p>
32.45	<p>S. right-of-way fence of S. Frontage Road to Interstate 40, barbed wire, 5 strand, bears N. 70° E. and S. 70° W.</p>
33.55	<p>S. Frontage Road to Interstate 40, an asphalt surfaced road, 20 ft. wide, bears N. 75° E. and S. 75° W.</p>
34.00	<p>S. right-of-way fence of Interstate 40, barbed wire, 5 strand, bears N. 70° E. and S. 70° W.</p>

Subdivision of Section 26,
T. 22 N., R. 29 E., Gila and Salt River Meridian, Arizona

CHAINS	
34.45	Interstate 40 east bound exit ramp, an asphalt surfaced road, bears N. 70° E. and S. 70° W.
35.00	Interstate 40 east bound lane, an asphalt surfaced road, bears N. 80° E. and S. 80° W.
38.65	Interstate 40 west bound lane, an asphalt surfaced road, bears N. 85° E. and S. 85° W.
39.27	The 1/4 sec. cor. of secs. 23 and 26. <hr/>
	From the 1/4 sec. cor. of secs. 25 and 26. N. 89°31' W., on the E. and W. center line of sec. 26. Over gently rolling land.
19.965	The center E. 1/16 sec. cor. of sec. 26, monumented with a rebar, 24 ins. long, 5/8 ins. diam., firmly set, projecting 5 ins. above ground, with 1 1/2 in. aluminum cap mkd. MARTINEZ LS5873, no record found. Accepted as a careful and faithful determination of the cor. point. Remove 2004 cor. and reset at the true point. At the corner point Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd. <div style="text-align: center;"> <p>T 22 N R 29 E E 1/16 C———C S 26 2017</p> </div> Deposit a magnet, in a white plastic case, at the base, and the rebar inside, the stainless steel post. Set a steel fence post alongside and N. of cor. Cor. is located 9 lks. W. of a meandering barbed wire fence, 4 strand, bears N. and S. From this cor. point, a wood fence cor. post of meandering barbed wire fences, extending N. 3° W. and N. 89° W., bears N. 53°41' E., 31 lks. dist. Ruth Thompson, a resident of the adjacent 80 acre allotment and a descendent of Joe Thompson Sr. (deceased), stated the fences along the right bank of Black Creek were constructed to keep the livestock away from the wash and segregate livestock, and were not intended to be an indication of the allotment boundary. <hr/>

Subdivision of Section 26,
T. 22 N., R. 29 E., Gila and Salt River Meridian, Arizona

CHAINS	
	N. 89°33' W., beginning new measurement, on the E. and W. center line of sec. 26.
20.05	The center 1/4 sec. cor. of sec. 26. <hr style="width: 20%; margin: 10px auto;"/>
	N. 89°18' W., beginning new measurement, on the E. and W. center line of sec. 26.
19.93	Point for the center W. 1/16 sec. cor. of sec. 26, determined by bearing-bearing intersection between the cors. of the center 1/4 sec. cor. of sec. 26 and the 1/4 sec. cor. of secs. 26 and 27, and at intersection with the N-S barbed wire fence on the N. and S. center line of the NW 1/4 of sec. 26. Remove 2004 cor. and reset at the true point. Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd. <div style="text-align: center;"> T 22 N R 29 E W 1/16 C———C S 26 2017 </div> Deposit a magnet, in a white plastic case, at the base, and the rebar inside, the stainless steel post. Cor. is located in N. and S. barbed wire fence between two fence cor. posts of fences, 10 lks. S. of fence cor. post of fences, extending N. and W., and 11 lks. N. of fence cor. post of fences, extending N. and E.
39.90	The 1/4 sec. cor. of secs. 26 and 27. <hr style="width: 80%; margin: 10px auto;"/>
	NE 1/4 Section 26 <hr style="width: 30%; margin: 10px auto;"/>
	From the center E. 1/16 sec. cor. of sec. 26. N. 0°10' E., on the N. and S. center line of the NE 1/4 of sec. 26.
19.91	Point for the NE 1/16 sec. cor. of sec. 26, determined at the intersection of the N. and S. center line of the NE 1/4 of sec. 26, and the extension of bearing of the E-W barbed wire fence from the E. Remove 2004 cor. and reset at the true point. Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.

Subdivision of Section 26,
T. 22 N., R. 29 E., Gila and Salt River Meridian, Arizona

CHAINS	T 22 N R 29 E NE 1/16 S 26 2017
	Deposit a magnet, in a white plastic case, at the base, and the rebar inside, the stainless steel post.
	Set a steel fence post alongside and N. of cor.
	Cor. is located 5 lks. W. of fence cor. post of barbed wire fences, 4 strand, bears N., E., and S. 15° E. to entrance gate fence post.
	Cor. is also located 8 lks. E. of two track access road, bears N. and S.
36.05	E. fence cor. post of main access gate, and the S. right-of-way fence of S. Frontage Road to Interstate 40, barbed wire, 5 strand, bears S. 89° E. and S. 88° W.
36.50	S. Frontage Road to Interstate 40, an asphalt surfaced road, 20 ft. wide, bears E. and W.
36.90	S. right-of-way fence of Interstate 40, barbed wire, 5 strand, bears N. 89° E. and S. 89° W.
37.45	Interstate 40 east bound lane, an asphalt surfaced road, bears N. 89° E. and S. 89° W.
39.36	True point for the E. 1/16 sec. cor. of secs. 23 and 26.
	<hr/>
	From the N. 1/16 sec. cor. of sec. 25 and 26.
	N. 89°30' W., on the E. and W. center line of the NE 1/4 of sec. 26.
8.70	Fence cor. post serving as the terminus to a barbed wire fence, 4 strand, at the edge of right bank to Black Creek, 10 ft. high, bears N. 89°30' W.
19.90	The NE 1/16 sec. cor. of sec. 26.
40.10	The center N. 1/16 sec. cor. of sec. 26.
	<hr/>
	SE 1/4 Section 26
	<hr/>
	From the E. 1/16 sec. cor. of secs. 26 and 35.
	N. 0°20' W., on the N. and S. center line of the SE 1/4 of sec. 26.

Subdivision of Section 26,
T. 22 N., R. 29 E., Gila and Salt River Meridian, Arizona

CHAINS	
18.90	N. right-of-way fence of the Burlington Northern Santa Fe Rail Road, 5 strand, bears N. 80° E. and S. 80° W.
20.02	Point for the SE 1/16 sec. cor. of sec. 26, determined at the corner of barbed wire fences. The fence cor. post is accepted as a careful and faithful determination of the cor. point. Remove 2004 cor. and reset at the true point. At the corner point Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with brass cap mkd. <div style="text-align: center;">T 22 N R 29 E SE 1/16 S 26 2017</div> Deposit a magnet, in a white plastic case, at the base of the stainless steel post. Set a steel fence post alongside and N. of cor. Cor. is located at the SE base of wood fence cor. post of barbed wire fences, 5 strand, bears N. and W. <hr style="width: 20%; margin: 10px auto;"/> N. 0°03' W., beginning new measurement, on the N. and S. center line of the SE 1/4 of sec. 26. Over gently rolling land, parallel to N-S barbed wire fence.
10.30	From this point, a wood fence cor. post of barbed wire fences, extends N., S., and N. 40° W., bears W., 5 lks. dist.
19.78	The center E. 1/16 sec. cor. of sec. 26. <hr style="width: 20%; margin: 10px auto;"/> From the true point for the W. 1/16 sec. cor. of secs. 26 and 35. N. 89°13' W., on the E. and W. center line of the SE 1/4 of sec. 26.
20.03	The SE 1/16 sec. cor. of sec. 26. <hr style="width: 20%; margin: 10px auto;"/> N. 89°39' W., beginning new measurement, on the E. and W. center line of the SE 1/4 of sec. 26.
14.30	Fence cor. post serving as the terminus to a barbed wire fence, 5 strand, at the edge of left bank to Black Creek, 15 ft. high, bears E.

Subdivision of Section 26,
T. 22 N., R. 29 E., Gila and Salt River Meridian, Arizona

CHAINS	
19.94	The center S. 1/16 sec. cor. of sec. 26. <hr/>
	SW 1/4 Section 26 <hr/>
	From the W. 1/16 sec. cor. of secs. 26 and 35. N. 0°36' W., on the N. and S. center line of the SW 1/4 of sec. 26.
18.00	Right bank of the Puerco River, a dry wash bed, 20 ft. high, bears S. 60° E. and N. 80° W.
19.98	The SW 1/16 sec. cor. of sec. 26, established in 2004, where a stone was recovered, monumented with a stainless steel post, 2 1/2 ins. diam., firmly set, projecting 2 ins. above ground, with a steel fence post alongside to the N., with brass cap mkd. T22N R29E SW 1/16 S26 2004. Add the marks 2017 to the brass cap. <hr/>
	N. 0°09' E., beginning new measurement, on the N. and S. center line of the SW 1/4 of sec. 26.
19.94	The center W. 1/16 sec. cor. of sec. 26. <hr/>
	From the center S. 1/16 sec. cor. of sec. 26. N. 89°39' W., on the E. and W. center line of the SW 1/4 of sec. 26.
20.08	The SW 1/16 sec. cor. of sec. 26. <hr/>
	N. 89°31' W., beginning new measurement, on the E. and W. center line of the SW 1/4 of sec. 26.
19.84	The S. 1/16 sec. cor. of secs. 26 and 27. <hr/>
	NW 1/4 Section 26 <hr/>
	From the center W. 1/16 sec. cor. of sec. 26. N. 0°15' W., on the N. and S. center line of the NW 1/4 of sec. 26.
25.40	S. right-of-way fence of S. Frontage Road to Interstate 40, barbed wire, 5 strand, bears N. 89° E. and S. 89° W.
25.55	S. Frontage Road to Interstate 40, an asphalt surfaced road, 20 ft. wide, bears N. 85° E. and S. 85° W.

Subdivision of Section 26,
T. 22 N., R. 29 E., Gila and Salt River Meridian, Arizona

CHAINS	
27.20	S. right-of-way fence of Interstate 40, barbed wire, 5 strand, bears N. 80° E. and S. 80° W.
27.65	Interstate 40 east bound exit ramp, an asphalt surfaced road, 15 ft. wide, bears N. 75° E. and S. 75° W.
29.05	Interstate 40 east bound lane, an asphalt surfaced road, bears N. 70° E. and S. 70° W.
34.65	Interstate 40 west bound lane, an asphalt surfaced road, bears N. 75° E. and S. 75° W.
36.35	Interstate 40 west bound exit ramp, an asphalt surfaced road, 20 ft. wide, bears N. 75° E. and S. 75° W.
39.10	True point for the W. 1/16 sec. cor. of secs. 23 and 26.
	<hr/>

T. 22 N., R. 29 E., Gila and Salt River Meridian, Arizona

CHAINS

GENERAL DESCRIPTION

The area surveyed is within the Navajo Indian Reservation, 8 miles east of Sanders, AZ, and within the community of Houck, AZ. Access is provided by the north and south frontage roads to Interstate 40, from the Houck interchange exit ramp, where numerous bladed dirt roads and two track roads were accessible to areas of sections 24, 25, and 26. ATV's were required to access the majority of the areas for the south half of sections 25 and 26, and along the range line to the north boundary.

The elevation near the southwest portion of section 26, is 5940 feet above sea level, and the northeastern portion of the township is 6290 feet above sea level. The terrain consists of nearly level land along Interstate 40, to gently rolling land south of the interstate. Terrain is rolling to broken, and rugged, north of section 24, along the range line to the north boundary of the township. Vegetation consists of scattered juniper and piñon further north and south of the interstate, and becomes thick north of section 24. Sage brush, rabbit brush, cactus, and native grasses, are prominent throughout sections 24, 25, 26, and along the range line to the north boundary.

Black Creek drains the northeastern portion of the township, meandering southwest, and near the north half of the range line, and enters through the center of section 24, the northwest portion of section 25, and exits the south half of section 26, draining into the Puerco River. There is presence of grazing livestock throughout the area. The soil is mostly clay in section 24, and sandy loam in sections 25 and 26.

There are major housing developments, and communities in sections 24, 25, and 26.

The mean magnetic declination of $9\ 1/2^\circ$ E. was derived from the United States Geological Survey computer program GEOMAG, utilizing the World Magnetic Model for Epoch 2010-2015 for the dates of survey.

