

ORIGINAL

**UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT**

FIELD NOTES
OF THE SURVEY OF
THE NINTH STANDARD PARALLEL NORTH (SOUTH BOUNDARY),
THE NORTH BOUNDARY,
AND THE SUBDIVISIONAL LINES,
AND
THE SUBDIVISION OF CERTAIN SECTIONS
TOWNSHIP 37 NORTH, RANGE 15 EAST,
OF THE GILA AND SALT RIVER MERIDIAN,
IN THE STATE OF ARIZONA.

EXECUTED BY

Marshall Steele Wixom, Cadastral Surveyor

Under Special Instructions dated January 17, 2018, approved January 17, 2018, which provided for the surveys included under Group No. 1184, and assignment instructions dated January 17, 2018.

Survey commenced March 06, 2018

Survey completed May 23, 2018

INDEX DIAGRAM

**TOWNSHIP 37 NORTH RANGE 15 EAST
GILA AND SALT RIVER MERIDIAN, ARIZONA**

14 6 57 56	13 5 46 55	12 4 38 45	11 3 30 37	10 2 22 29	9 1 22
7 55 54	8 44 53	9 36 44	10 28 36	11 21 28	12 21
18 53 52	17 43 51	16 35 42	15 27 35	14 19 26	13 20
19 50 50	20 41 49	21 34 40	22 25 33	23 18 25	24 17
30 48 48	29 40 47	28 32 39	27 24 32	26 16 24	25 16
31 46 8	32 38 7	33 30 6	34 23 6	35 15 5	36 4

Subdivision of Sec. 6 Pages 57-59
 Subdivision of Sec. 7 Pages 59-60
 Subdivision of Sec. 31 Pages 60-61
 Subdivision of Sec. 32 Pages 61-62
 Subdivision of Sec. 36 Pages 62-63

T. 37 N., R. 15 E., Gila and Salt River Meridian, Arizona

CHAINS

The following field notes describe the survey of the Ninth Standard Parallel North (south boundary), the north boundary, and the subdivisional lines, and the subdivision of certain sections, Township 37 North, Range 15 East, Gila and Salt River Meridian, Arizona.

The history of surveys pertaining to this survey is as follows:

Jones Curtiss, Cadastral Surveyor, surveyed the East Boundary, Township 37 North, Range 15 East, Gila and Salt River Meridian, in 1996. (Book 5535) Sereyna C. Cagle, Cadastral Surveyor, surveyed the West Boundary, Township 37 North, Range 15 East, Gila and Salt River Meridian, in 2005. (Book 5775)

The survey was executed in accordance with the specifications as set forth in the Manual of Surveying Instructions, (2009), and the Special Instructions dated January 17, 2018, for Group No. 1184, Arizona.

The true meridian direction and length of all lines were determined by real time kinematic global positioning system observations using Trimble Navigation R8 and R10 model receivers.

Preliminary to the resurvey, the lines of the prior surveys were retraced and search was made for all corners and other calls of record. Identified corners were remonumented in their original positions. Lost corners were reestablished and remonumented at proportionate positions based on the official record. The retracement data were thoroughly verified and only the true line field notes are given herein.

Geodetic control was derived from Global Positioning System (GPS) static observations post processed by National Geodetic Survey, Online Positioning User Service (OPUS), utilizing Continuously Operating Reference Stations (CORS) DL1882 AZFL NAU FLAGSTAFF CORS ARP, DL3642 MC09 NUCLA CORS ARP, and DI3419 P012 MONTICELLOUT2006 CORS ARP.

The NAD 83 (2011) (EPOCH: 2010), geographic position of the standard corner of Township 37 North, Ranges 15 and 16 East, is as follows:

Latitude: 36°33'48.860" N. Longitude: 110°40'02.007" W.

The NAD 83 (2011) (EPOCH: 2010), geographic position of the corner of Townships 37 and 38 North, Ranges 14 and 15, is as follows:

Latitude: 36°39'02.018" N. Longitude: 110°46'30.214" W.

The mean magnetic declination is 10 1/3° E.

Survey of the Ninth Standard Parallel (south boundary),
T. 37 N., R. 15 E., Gila and Salt River Meridian, Arizona

CHAINS	
	<p>Beginning at the standard cor. of secs. 31 and 36, on the E. bdy. of the Tp., monumented with a stainless steel post, 2 1/2 ins. diam., firmly set, projecting 5 ins. above the ground, with brass cap mkd., SC T37N R15E R16E S36 S31 S1 S6 2005 1996. Add the marks 2018 to the brass cap. Remove marks S1 S6 from brass cap. Set a steel fence post N. of the stainless steel post.</p> <p>from which the original bearing tree</p> <p style="padding-left: 40px;">A piñon, 14 ins. diam., bears N. 33 1/2° E. 1.735 chs. dist., with scribe marks T37N R16E S31 SC BT visible on partially open blaze. (Record: N. 32 3/4° E.)</p> <p>and a bearing tree not of record</p> <p style="padding-left: 40px;">A forked piñon, 17 ins. diam. at a point 2 ft. above ground, bears S. 79° W., 1.749 chs. dist., with an open blaze, no visible marks.</p> <p>West, along the Standard Parallel.</p> <p>Over rolling land.</p>
18.10	Underground water line, bears N. 10° E. and S. 10° W.
24.20	Underground water line, bears N. 70° E. and S. 70° W.
40.00	Point for the standard 1/4 sec. cor. of sec. 36.
	<p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 22 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">SC T 37 N R 15 E 1/4 S 36 ----- 2018</p> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p> <p>Set a steel fence post N. of the stainless steel post.</p>
49.50	Graded road, 20 ft. wide, bears S. 65° E. and N. 65° W.
58.25	Barbed wire fence, 4 strands, bears N. 45° E. and S. 45° W.
59.48	BIA Route No. 6320, southeasterly edge of asphalt surface, bears N. 45° E. and S. 45° W.
60.14	BIA Route No. 6320, northwesterly edge of asphalt surface, bears N. 45° E. and S. 45° W.

Survey of the Ninth Standard Parallel (south boundary),
T. 37 N., R. 15 E., Gila and Salt River Meridian, Arizona

CHAINS	
61.35	Barbed wire fence, 4 strands, bears N. 45° E. and S. 45° W.
80.00	Point for the standard cor. of secs. 35 and 36.
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with brass cap mkd.
	<p style="text-align: center;">SC T 37 N R 15 E <u>S 35 S 36</u></p>
	2018
	Deposit a magnet, in a white plastic case, at the base of the stainless steel post.
	Set a steel fence post N. of the stainless steel post.
	<hr/>
	West, along the Standard Parallel.
	Over rolling land.
1.60	Graded road, 13 ft. wide, bears S. 15° E. and N. 15° W.
40.00	Point for the standard 1/4 sec. cor. of sec. 35.
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 25 ins. in the ground, with brass cap mkd.
	<p style="text-align: center;">SC T 37 N R 15 E <u>1/4 S 35</u></p>
	2018
	Deposit a magnet, in a white plastic case, at the base of the stainless steel post.
	Set a steel fence post N. of the stainless steel post.
80.00	Point for the standard cor. of secs. 34 and 35.
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with brass cap mkd.
	<p style="text-align: center;">SC T 37 N R 15 E <u>S 34 S 35</u></p>
	2018

Survey of the Ninth Standard Parallel (south boundary),
T. 37 N., R. 15 E., Gila and Salt River Meridian, Arizona

CHAINS	
	Deposit a magnet, in a white plastic case, at the base of the stainless steel post.
	Set a steel fence post N. of the stainless steel post.
	<hr/> West, along the Standard Parallel.
	Over rolling land.
40.00	Point for the standard 1/4 sec. cor. of sec. 34. Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with brass cap mkd.
	SC T 37 N R 15 E <u>1/4 S 34</u>
	2018
	Set a steel fence post N. of the stainless steel post.
	Deposit a magnet, in a white plastic case, at the base of the stainless steel post.
80.00	Point for the standard cor. of secs. 33 and 34, falls on a large sandstone outcrop, near the NE edge.
	Drill hole, 1 3/8 ins. diam., 18 ins. deep, in sandstone. Deposit a magnet, in a white plastic case, in drilled hole.
	Cement a stainless steel drive rod, 20 ins. long, 9/16 ins. diam., 15 ins. in the drilled hole, with brass cap mkd.
	SC T 37 N R 15 E <u>S 33 S 34</u>
	2018
	Drill a second hole, 1 3/8 ins. diam., 18 ins. deep, in sandstone, S. of the stainless steel drive rod.
	Set a steel fence post in the second drilled hole.
	Encircle brass cap in collar of stone.
	<hr/> West, along the Standard Parallel.
	Over rolling land.

Survey of the Ninth Standard Parallel (south boundary),
T. 37 N., R. 15 E., Gila and Salt River Meridian, Arizona

CHAINS	
5.80	BIA route 6322, a graded road, 20 ft. wide, bears N. 50° E. and S. 50° W.
40.00	<p>Point for the standard 1/4 sec. cor. of sec. 33.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 25 ins. in the ground, with brass cap mkd.</p>
	<p style="text-align: center;">SC T 37 N R 15 E <u>1/4 S 33</u></p>
	2018
	Deposit a magnet, in a white plastic case, at the base of the stainless steel post.
	Set a steel fence post NE. of the stainless steel post.
	A high sandstone ridge is NW of the stainless steel post.
80.00	<p>Point for the standard cor. of secs. 32 and 33.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 25 ins. in the ground, with brass cap mkd.</p>
	<p style="text-align: center;">SC T 37 N R 15 E <u>S 32 S 33</u></p>
	2018
	Deposit a magnet, in a white plastic case, at the base of the stainless steel post.
	Set a steel fence post N. of the stainless steel post.
	<hr/> <p>West, along the Standard Parallel.</p>
	Over rolling land.
6.30	Enter gorge and descend approx. 60 ft.
9.10	Begashibito Wash, 50 ft. wide, 10 ft. deep, drains S. 5° E.
21.70	Ascend approx. 90 ft. and leave gorge.
40.00	<p>Point for the standard 1/4 sec. cor. of sec. 32.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 25 ins. in the ground, with brass cap mkd.</p>

Survey of the Ninth Standard Parallel (south boundary),
T. 37 N., R. 15 E., Gila and Salt River Meridian, Arizona

CHAINS	
	SC T 37 N R 15 E 1/4 S 32 <hr style="width: 10%; margin: auto;"/>
	2018
	Deposit a magnet, in a white plastic case, at the base of the stainless steel post.
	Set a steel fence post N. of the stainless steel post.
45.00	Graded road, 20 ft. wide, bears N. 30° E. and S. 30° W.
68.90	Barbed wire fence, 4 strands, bears S. 45° E. and N. 45° W.
70.71	Arizona State Highway No. 98, northeasterly edge of asphalt surface, bears S. 45° E. and N. 45° W.
71.50	Arizona State Highway No. 98, southwesterly edge of asphalt surface, bears S. 45° E. and N. 45° W.
73.30	Barbed wire fence, 4 strands, bears S. 45° E. and N. 45° W.
80.00	Point for the standard cor. of secs. 31 and 32, falls on sandstone outcrop.
	Drill hole, 1 3/8 ins. diam., 18 ins. deep, in sandstone. Deposit a magnet, in a white plastic case, in drilled hole.
	Cement a stainless steel drive rod, 18 ins. long, 9/16 ins. diam., 14 ins. in the drilled hole, with brass cap mkd.
	SC T 37 N R 15 E S 31 S 32 <hr style="width: 10%; margin: auto;"/>
	2018
	Drill a second hole, 1 3/8 ins. diam., 18 ins. deep, in sandstone, N. of the stainless steel drive rod.
	Set a steel fence post in the second drilled hole.
	<hr style="width: 80%; margin-left: 0;"/>
	West, along the Standard Parallel.
	Over rolling land.
40.00	Point for the standard 1/4 sec. cor. of sec. 31, falls on sandstone outcrop.

Survey of the Ninth Standard Parallel (south boundary),
T. 37 N., R. 15 E., Gila and Salt River Meridian, Arizona

CHAINS	
	<p>Drill hole, 1 3/8 ins. diam., 18 ins. deep, in sandstone. Deposit a magnet, in a white plastic case, in drilled hole.</p> <p>Cement a stainless steel drive rod, 20 ins. long, 9/16 ins. diam., 11 ins. in the drilled hole, with brass cap mkd.</p> <p style="text-align: center;">SC T 37 N R 15 E <u>1/4 S 31</u></p> <p style="text-align: center;">2018</p> <p>Encircle drive rod in supporting mound of stone, 2 1/2 ft. base, to top.</p>
44.80	Wash, 35 ft. wide, 8 ft. deep, drains S. 10° W.
80.00	<p>The cor. of secs. 31 and 36, on the W. bdy. of the Tp., monumented with a stainless steel post, firmly set, projecting 5 ins. above ground, with brass cap mkd. SC T37N R14E R15E S36 S31 2005. Add the marks 2018 to the brass cap. Set a steel fence post N. of the stainless steel post.</p> <hr/> <p style="text-align: center;">Survey of the North Boundary, T. 37 N., R. 15 E., Gila and Salt River Meridian, Arizona</p> <hr/> <p>From the cor. of secs. 1, 6, 31 and 36, on the E. bdy. of the Tp., monumented with a stainless steel post, firmly set, projecting 3 ins. above ground, with brass cap mkd. T38N R15E R16E S36 S31 S1 S6 T37N 1996. Add the marks 2018 to the brass cap. Set a steel fence post N. of the stainless steel post.</p> <p>from which the original bearing tree</p> <p style="padding-left: 40px;">A piñon, 8 ins. diam., bears N. 74° E., 77 1/2 lks. dist., with scribe marks T38N R16E S31 BT visible on partially open blaze.</p> <p>West, bet. secs. 1 and 36.</p> <p>Over rolling land.</p>
34.80	Enter gorge and descend approx. 25 ft.
35.40	Last End Wash, 65 ft. wide, 15 ft. deep, drains S. 10° W.
37.50	Ascend approx. 100 ft. and leave gorge.
40.00	Point for the 1/4 sec. cor. of secs. 1 and 36.

Survey of the North Boundary,
T. 37 N., R. 15 E., Gila and Salt River Meridian, Arizona

CHAINS	
	<p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T 38 N R 15 E S 36 1/4 ——— S 1 T 37 N</p> <p style="text-align: center;">2018</p> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p> <p>Set a steel fence post N. of the stainless steel post.</p>
80.00	<p>Point for the cor. of secs. 1, 2, 35 and 36.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T 38 N R 15 E S 35 S 36 S 2 S 1 T 37 N</p> <p style="text-align: center;">2018</p> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p> <p>Set a steel fence post N. of the stainless steel post.</p> <hr/> <p>West, between secs. 2 and 35.</p> <p>Over rolling land.</p>
40.00	<p>Point for the 1/4 sec. cor. of secs. 2 and 35, falls on sandstone outcrop, sloped down to the SE, approx. 40 ft. dist. from the top of bank.</p> <p>Drill hole, 1 3/8 ins. diam., 18 ins. deep, in sandstone. Deposit a magnet, in a white plastic case, in drilled hole.</p> <p>Set a stainless steel drive rod, 20 ins. long, 9/16 ins. diam., 15 ins. in the drilled hole, with brass cap mkd.</p>

Survey of the North Boundary,
T. 37 N., R. 15 E., Gila and Salt River Meridian, Arizona

CHAINS	
	T 38 N R 15 E S 35 1/4 ——— S 2 T 37 N 2018
45.10	Enter gorge and descend approx. 95 ft.
48.00	Begashibito Wash, 60 ft. wide, 10 ft. deep, drains S. 45° W.
50.20	Ascend approx. 65 ft. and leave gorge.
80.00	Point for the cor. of secs. 2, 3, 34 and 35. Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd. <div style="text-align: center;"> T 38 N R 15 E S 34 S 35 ———— S 3 S 2 T 37 N 2018 </div> Deposit a magnet, in a white plastic case, at the base of the stainless steel post. Set a steel fence post N. of the stainless steel post. <hr/> West, bet. secs. 3 and 34. Over rolling land.
39.25	Trail road, 10 ft. wide, bears S. 30° E. and N. 45° W.
40.00	Point for the 1/4 sec. cor. of secs. 3 and 34. Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with brass cap mkd. <div style="text-align: center;"> T 38 N R 15 E S 34 1/4 ——— S 3 T 37 N 2018 </div>

Survey of the North Boundary,
T. 37 N., R. 15 E., Gila and Salt River Meridian, Arizona

CHAINS											
	<p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p> <p>Set a steel fence post N. of the stainless steel post.</p>										
80.00	<p>Point for the cor. of secs. 3, 4, 33 and 34.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center;"> <table style="margin: auto;"> <tr><td>T 38 N</td><td>R 15 E</td></tr> <tr><td>S 33</td><td>S 34</td></tr> <tr><td>S 4</td><td>S 3</td></tr> <tr><td colspan="2">T 37 N</td></tr> </table> <p>2018</p> </div> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p> <p>Set a steel fence post N. of the stainless steel post.</p> <hr/> <p>West, between secs. 4 and 33.</p> <p>Over rolling land.</p>	T 38 N	R 15 E	S 33	S 34	S 4	S 3	T 37 N			
T 38 N	R 15 E										
S 33	S 34										
S 4	S 3										
T 37 N											
40.00	<p>Point for the 1/4 sec. cor. of secs. 4 and 33.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center;"> <table style="margin: auto;"> <tr><td>T 38 N</td><td>R 15 E</td></tr> <tr><td>S 33</td><td></td></tr> <tr><td>1/4</td><td>—</td></tr> <tr><td>S 4</td><td></td></tr> <tr><td colspan="2">T 37 N</td></tr> </table> <p>2018</p> </div> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p> <p>Set a steel fence post N. of the stainless steel post.</p>	T 38 N	R 15 E	S 33		1/4	—	S 4		T 37 N	
T 38 N	R 15 E										
S 33											
1/4	—										
S 4											
T 37 N											
42.10	<p>Graded road, 9 ft. wide, bears S. 15° E. and N. 20° W.</p>										
80.00	<p>Point for the cor. of secs. 4, 5, 32 and 33.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 25 ins. in the ground, with brass cap mkd.</p>										

Survey of the North Boundary,
T. 37 N., R. 15 E., Gila and Salt River Meridian, Arizona

CHAINS					
	<p>T 38 N R 15 E <table style="margin: auto; border-collapse: collapse;"> <tr> <td style="border-right: 1px solid black; padding: 2px 10px;">S 32</td> <td style="padding: 2px 10px;">S 33</td> </tr> <tr> <td style="border-right: 1px solid black; padding: 2px 10px;">S 5</td> <td style="padding: 2px 10px;">S 4</td> </tr> </table> <p>T 37 N</p> <p>2018</p> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p> <p>Set a steel fence post N. of the stainless steel post.</p> <hr style="width: 50%; margin: 10px auto;"/> <p>West, between secs. 5 and 32.</p> <p>Over rolling land.</p> <p>9.00 Wash, 15 ft. wide, 3 ft. deep, drains S. 40° W.</p> <p>23.10 Wash, 10 ft. wide, 4 ft. deep, drains S. 15° W.</p> <p>40.00 Point for the 1/4 sec. cor. of secs. 5 and 32.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T 38 N R 15 E S 32 1/4 ——— S 5 T 37 N</p> <p style="text-align: center;">2018</p> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p> <p>The westerly edge of a large sandstone outcrop is approx. 45 ft. dist. E. of the stainless steel post.</p> <p>41.50 Begin ascending approx. 100 ft.</p> <p>47.50 Top of ascent.</p> <p>80.00 Point for the cor. of secs. 5, 6, 31 and 32.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> </p>	S 32	S 33	S 5	S 4
S 32	S 33				
S 5	S 4				

Survey of the North Boundary,
T. 37 N., R. 15 E., Gila and Salt River Meridian, Arizona

CHAINS	<table style="margin: auto; border-collapse: collapse;"> <tr> <td colspan="2">T 38 N</td> <td colspan="2">R 15 E</td> </tr> <tr> <td style="border-right: 1px solid black; padding: 2px 5px;">S 31</td> <td style="padding: 2px 5px;"></td> <td style="padding: 2px 5px;">S 32</td> <td style="padding: 2px 5px;"></td> </tr> <tr> <td style="border-right: 1px solid black; padding: 2px 5px;">S 6</td> <td style="padding: 2px 5px;"></td> <td style="padding: 2px 5px;">S 5</td> <td style="padding: 2px 5px;"></td> </tr> <tr> <td colspan="4" style="text-align: center;">T 37 N</td> </tr> </table>	T 38 N		R 15 E		S 31		S 32		S 6		S 5		T 37 N							
T 38 N		R 15 E																			
S 31		S 32																			
S 6		S 5																			
T 37 N																					
	2018																				
	Deposit a magnet, in a white plastic case, at the base of the stainless steel post.																				
	Set a steel fence post N. of the stainless steel post.																				
	<hr style="border: 0.5px solid black;"/>																				
	West, between secs. 6 and 31.																				
	Over rolling land.																				
10.75	Woven wire fence, with sign labelled Contaminated Water Keep Out bears N. 30° E. and S. 30° W.																				
	Cross dry water retention pond.																				
14.70	Woven wire fence, bears S. 5° E. and N. 5° W.																				
	Leave dry water retention pond.																				
15.40	Barbed wire fence, 4 strands, bears N. 35° E. and S. 35° W.																				
16.92	BIA Route No. 16, southeasterly edge of asphalt surface, bears N. 35° E. and S. 35° W.																				
17.47	BIA Route No. 16, northwesterly edge of asphalt surface, bears N. 35° E. and S. 35° W.																				
18.40	Barbed wire fence, 4 strands, bears N. 35° E. and S. 35° W.																				
40.00	Point for the 1/4 sec. cor. of secs. 6 and 31.																				
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 23 ins. in the ground, with brass cap mkd.																				
	<table style="margin: auto; border-collapse: collapse;"> <tr> <td colspan="2">T 38 N</td> <td colspan="2">R 15 E</td> </tr> <tr> <td colspan="2"></td> <td colspan="2" style="text-align: center;">S 31</td> </tr> <tr> <td colspan="2"></td> <td colspan="2" style="text-align: center;">1/4 ———</td> </tr> <tr> <td colspan="2"></td> <td colspan="2" style="text-align: center;">S 6</td> </tr> <tr> <td colspan="4" style="text-align: center;">T 37 N</td> </tr> </table>	T 38 N		R 15 E				S 31				1/4 ———				S 6		T 37 N			
T 38 N		R 15 E																			
		S 31																			
		1/4 ———																			
		S 6																			
T 37 N																					
	2018																				
	Deposit a magnet, in a white plastic case, at the base of the stainless steel post.																				
	Set a steel fence post N. of the stainless steel post.																				

Survey of the North Boundary,
T. 37 N., R. 15 E., Gila and Salt River Meridian, Arizona

CHAINS	
71.00	<p>Barbed wire fence, bears N. 25° E. and S. 25° W.</p> <p>Enter livestock coral.</p>
79.49	<p>The cor. of secs. 1, 6, 31 and 36, on the W. bdy. of the Tp., monumented with a stainless steel post, firmly set, projecting 3 ins. above ground, with brass cap mkd. T38N R14E R15E S36 S31 S1 S6 T37N 2005. Add the marks 2018 to the brass cap. Set a steel fence post S. of the stainless steel fence post.</p> <hr/> <p style="text-align: center;">Survey of the Subdivisional Lines, T. 37 N., R. 15 E., Gila and Salt River Meridian, Arizona</p> <hr/> <p>From the standard cor. of secs. 35 and 36, on the S. bdy. of the Tp., hereinbefore described.</p> <p>N. 0°01' W., bet. secs. 35 and 36.</p> <p>Over rolling land.</p>
40.00	<p>Point for the 1/4 sec. cor. of secs. 35 and 36.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 23 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T 37 N R 15 E 1/4 S 35 S 36</p> <p style="text-align: center;">2018</p> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p> <p>Set a steel fence post W. of the stainless steel post.</p>
40.35	<p>Trail road, 9 ft. wide, bears N. 70° E. and S. 70° W.</p>
80.00	<p>Point for the cor. of secs. 25, 26, 35 and 36, SE of a large rock pillar.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T 37 N R 15 E S 26 S 25 S 35 S 36</p> <p style="text-align: center;">2018</p>

Survey of the Subdivisional Lines,
T. 37 N., R. 15 E., Gila and Salt River Meridian, Arizona

CHAINS	
	<p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p> <p>Set a steel fence post N. of the stainless steel post.</p> <hr/> <p>From the cor. of secs. 25, 30, 31 and 36, on the E. bdy. of the Tp., monumented with a brass tablet, 3 1/4 ins. diam., loosely set, in cracked cement, 1 in. above the ground, with top mkd., T37N R15E R16E S25 S30 S36 S31 1996. With X's cut in rock face, 1.0 ft. W. and S. of brass tablet. Reset the brass tablet in fresh cement and add marks 2018 to the top.</p> <p>West, bet. secs. 25 and 36.</p> <p>Over rolling land.</p>
16.00	Underground water line, bears N. 25° E. and S. 25° W.
40.00	Point for the 1/4 sec. cor. of secs. 25 and 36.
	<p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 23 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center;"> <p>T 37 N R 15 E</p> <p>S 25</p> <p>1/4 ———</p> <p>S 36</p> <p>2018</p> </div>
	<p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p> <p>Set a steel fence post N. of the stainless steel post.</p>
49.20	Underground water line, bears S. 20° E. and N. 20° W.
80.00	The cor. of secs. 25, 26, 35 and 36.
	<hr/> <p>N. 0°01' W., bet. secs. 25 and 26.</p> <p>Over rolling land.</p>
35.20	BIA Route 6322, a graded road, 28 ft. wide, bears N. 85° E. and S. 85° W.
40.00	Point for the 1/4 sec. cor. of secs. 25 and 26.
	<p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p>

Survey of the Subdivisional Lines,
T. 37 N., R. 15 E., Gila and Salt River Meridian, Arizona

CHAINS	
	T 37 N R 15 E 1/4 S 26 S 25 2018
	Deposit a magnet, in a white plastic case, at the base of the stainless steel post. Set a steel fence post W. of the stainless steel post.
80.00	Point for the cor. of secs. 23, 24, 25 and 26. Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with brass cap mkd. <div style="text-align: center;"> T 37 N R 15 E S 23 S 24 S 26 S 25 2018 </div> Deposit a magnet, in a white plastic case, at the base of the stainless steel post. Set a steel fence post N. of the stainless steel post.
	<hr/> From the cor. of secs. 19, 24, 25 and 30, on the E. bdy. of the Tp., monumented with a stainless steel post, firmly set, projecting 3 ins. above ground, with brass cap mkd., T37N R15E R16E S24 S19 S25 S30 1996. Add marks 2018 to brass cap. Set a steel fence post W. of the stainless steel post. from which the original bearing tree <div style="padding-left: 40px;"> A piñon, 15 ins. diam., bears N. 52 3/4° E., 65 1/2 lks. dist., with scribe marks T37N R16E S19 BT visible on partially open blaze. </div> and on the same sandstone outcrop <div style="padding-left: 40px;"> The marks BXO, chiseled on sandstone bedrock, bear S. 57 3/4 E., 34 1/2 lks. dist. </div> West, bet. secs. 24 and 25. Over rolling land.
40.00	Point for the 1/4 sec. cor. of secs. 24 and 25. Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 25 ins. in the ground, with brass cap mkd.

Survey of the Subdivisional Lines,
T. 37 N., R. 15 E., Gila and Salt River Meridian, Arizona

CHAINS	
	<p style="text-align: center;">T 37 N R 15 E S 24 1/4 ——— S 25</p> <p style="text-align: center;">2018</p> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p> <p>Set a steel fence post N. of the stainless steel post.</p>
79.99	<p>The cor. of secs. 23, 24, 25 and 26.</p> <hr/> <p>N. 0°01' W., bet. secs. 23 and 24.</p> <p>Over rolling land.</p>
40.00	<p>Point for the 1/4 sec. cor. of secs. 23 and 24.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p>
	<p style="text-align: center;">T 37 N R 15 E 1/4 S 23 S 24</p> <p style="text-align: center;">2018</p> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p> <p>Set steel fence post W. of stainless steel post.</p>
61.00	<p>Graded road, 18 ft. wide, bears N. 65° E. and S. 65° W.</p>
66.75	<p>Power line, bears East and West.</p>
73.35	<p>High voltage transmission line, bears East and West.</p>
80.00	<p>Point for the cor. of secs. 13, 14, 23 and 24.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 25 ins. in the ground, with brass cap mkd.</p>
	<p style="text-align: center;">T 37 N R 15 E S 14 S 13 ————— S 23 S 24</p> <p style="text-align: center;">2018</p>

Survey of the Subdivisional Lines,
T. 37 N., R. 15 E., Gila and Salt River Meridian, Arizona

CHAINS

Deposit a magnet, in a white plastic case, at the base of the stainless steel post.

Set a steel fence post W. of the stainless steel post.

From the cor. of secs. 13, 18, 19 and 24, on the E. bdy. of the Tp., monumented with a drilled hole, with X's cut in sandstone outcrop to the N. and W., at 1.0 ft. dist. from the drilled hole. There is no evidence of the 1996-97 brass tablet.

from which on the same sandstone outcrop

The marks BXO, chiseled on sandstone bedrock, bear N. 26 1/4 ° E., 50 lks. dist.

and the original bearing tree

A piñon, 8 ins. diam., bears S. 44° E., 1.37 lks. dist., with scribe marks T37N R16E S19 BT visible on partially open blaze.

Set a brass tablet, 3 1/4 ins. diam., 2 1/2 ins. stem, cemented in place in the drilled hole, flush with rock face, with top mkd.

T 37 N			
R 15 E	R 16 E		
S 13	S 18		
S 24	S 19		

2018

West, bet. secs. 13 and 24.

Over rolling land.

27.85 Graded road, 15 ft. wide, bears S. 25° E. and N. 30° W.

39.99 Point for the 1/4 sec. cor. of secs. 13 and 24.

Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.

T 37 N		R 15 E
S 13		
1/4	—	
S 24		

2018

Deposit a magnet, in a white plastic case, at the base of the stainless steel post.

Survey of the Subdivisional Lines,
T. 37 N., R. 15 E., Gila and Salt River Meridian, Arizona

CHAINS							
	Set a steel fence post N. of the stainless steel post.						
79.98	The cor. of secs. 13, 14, 23 and 24.						
	<hr/>						
	N. 0°01' W., bet. secs. 13 and 14.						
	Over rolling land.						
40.00	Point for the 1/4 sec. cor. of secs. 13 and 14.						
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.						
	<table style="margin-left: auto; margin-right: auto;"> <tr><td>T 37 N</td><td>R 15 E</td></tr> <tr><td>1/4</td><td></td></tr> <tr><td>S 14</td><td> S 13</td></tr> </table>	T 37 N	R 15 E	1/4		S 14	S 13
T 37 N	R 15 E						
1/4							
S 14	S 13						
	2018						
	Deposit a magnet, in a white plastic case, at the base of the stainless steel post.						
	Set a steel fence post W. of the stainless steel post.						
80.00	Point for the cor. of secs. 11, 12, 13 and 14.						
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.						
	<table style="margin-left: auto; margin-right: auto;"> <tr><td>T 37 N</td><td>R 15 E</td></tr> <tr><td>S 11</td><td> S 12</td></tr> <tr><td>S 14</td><td> S 13</td></tr> </table>	T 37 N	R 15 E	S 11	S 12	S 14	S 13
T 37 N	R 15 E						
S 11	S 12						
S 14	S 13						
	2018						
	Deposit a magnet, in a white plastic case, at the base of the stainless steel post.						
	Set a steel fence post W. of the stainless steel post.						
	<hr/>						
	From the cor. of sec. 7, 12, 13 and 18, on the E. bdy. of the Tp., monumented with a stainless steel post, firmly set, projecting 2 ins. above ground, with brass cap mkd., T37N R15E R16E S12 S7 S13 S18 1996. Add the marks 2018 to the brass cap. Set a steel fence post W. of the stainless steel post.						
	from which the original bearing tree						
	A piñon, 14 ins. diam., bears S. 51° E., 69 lks. dist., with scribe marks T37N R16E S18 BT visible on partially open blaze.						

Survey of the Subdivisional Lines,
T. 37 N., R. 15 E., Gila and Salt River Meridian, Arizona

CHAINS	
	N. 89°59' W., bet. secs. 12 and 13. Over rolling land.
38.75	Graded road, 12 ft. wide, bears N. 20° E. and S. 20° W.
39.99	Point for the 1/4 sec. cor. of secs. 12 and 13. Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 25 ins. in the ground, with brass cap mkd. <div style="text-align: center;"> T 37 N R 15 E S 12 1/4 ——— S 13 2018 </div>
	Deposit a magnet, in a white plastic case, at the base of the stainless steel post. Set a steel fence post N. of the stainless steel post.
79.99	The cor. of secs. 11, 12, 13 and 14. <hr/>
	N. 0°01' W., bet. secs. 11 and 12. Over rolling land.
40.00	Point for the 1/4 sec. cor. of secs. 11 and 12. Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd. <div style="text-align: center;"> T 37 N R 15 E 1/4 S 11 S 12 2018 </div>
	Deposit a magnet, in a white plastic case, at the base of the stainless steel post. Set a steel fence post W. of the stainless steel post.
80.00	Point for the cor. of secs. 1, 2, 11 and 12. Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.

Survey of the Subdivisional Lines,
T. 37 N., R. 15 E., Gila and Salt River Meridian, Arizona

CHAINS	
	T 37 N R 15 E S 2 S 1 S 11 S 12 2018
	Deposit a magnet, in a white plastic case, at the base of the stainless steel post. Set a steel fence post N. of the stainless steel post.
	<hr/> From the cor. of secs. 1, 6, 7 and 12, on the E. bdy. of the Tp., monumented with a stainless steel post, firmly set, projecting 3 ins. above ground, with brass cap mkd. T37N R15E R16E S1 S6 S12 S7 1996. Add the marks 2018 to the brass cap. Set a steel fence post W. of the stainless steel post. N. 89°59' W., bet. secs. 1 and 12. Over rolling land.
40.00	Point for the 1/4 sec. cor. of secs. 1 and 12 falls in sandstone outcrop. Drill hole, 1 3/8 ins. diam., 18 ins. deep, in sandstone. Deposit a magnet, in a white plastic case, in drilled hole. Cement a stainless steel drive rod, 20 ins. long, 9/16 ins. diam., 14 ins. in the drilled hole, with brass cap mkd.
	T 37 N R 15 E S 1 1/4 ——— S 12 2018
	Drill a second hole, 1 3/8 ins. diam., 18 ins. deep, in sandstone, N. of the stainless steel drive rod. Set a steel fence post in the second drilled hole.
79.99	The cor. of secs. 1, 2, 11 and 12. <hr/> North, bet. secs. 1 and 2. Over rolling land.
32.30	Enter gorge and descend approx. 40 ft.
33.60	Last End Wash, 40 ft. wide, 10 ft. deep, drains S. 75° W.

Survey of the Subdivisional Lines,
T. 37 N., R. 15 E., Gila and Salt River Meridian, Arizona

CHAINS	
35.60	Ascend approx. 55 ft. and leave gorge.
40.00	Point for the 1/4 sec. cor. of secs. 1 and 2 falls on sandstone outcrop. Drill hole, 1 3/8 ins. diam., 18 ins. deep, in sandstone. Deposit a magnet, in a white plastic case, in drilled hole. Set a stainless steel drive rod, 20 ins. long, 9/16 ins. diam., 14 ins. in the drilled hole, with brass cap mkd. <div style="text-align: center;"> T 37 N R 15 E 1/4 S 2 S 1 2018 </div> Drill a second hole, 1 3/8 ins. diam., 18 ins. deep, in sandstone, W. of the stainless steel drive rod. Set a steel fence post in the second drilled hole.
79.98	The cor. of secs. 1, 2, 35 and 36, on the N. bdy. of the Tp. <hr/> From the standard cor. of secs. 34 and 35, on the S. bdy. of the Tp., hereinbefore described. N. 0°01' W., bet. secs. 34 and 35. Over rolling land.
40.00	Point for the 1/4 sec. cor. of secs. 34 and 35. Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd. <div style="text-align: center;"> T 37 N R 15 E 1/4 S 34 S 35 2018 </div> Deposit a magnet, in a white plastic case, at the base of the stainless steel post. Set a steel fence post W. of the stainless steel post.
77.30	Navajo Hogan, approx. 24 ft. by 24 ft.
80.00	Point for the cor. of secs. 26, 27, 34, and 35. Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.

Survey of the Subdivisional Lines,
T. 37 N., R. 15 E., Gila and Salt River Meridian, Arizona

CHAINS	
	T 37 N R 15 E S 27 S 26 S 34 S 35 2018 Deposit a magnet, in a white plastic case, at the base of the stainless steel post. Set a steel fence post W. of the stainless steel post. <hr/> From the cor. of secs. 25, 26, 35 and 36. West, bet. secs. 26 and 35. Over rolling land.
40.00	Point for the 1/4 sec. cor. of secs. 26 and 35. Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 23 ins. in the ground, with brass cap mkd. <div style="text-align: center;"> T 37 N R 15 E S 26 1/4 ——— S 35 2018 </div> Deposit a magnet, in a white plastic case, at the base of the stainless steel post. Set a steel fence post N. of the stainless steel post.
80.00	The cor. of secs. 26, 27, 34, and 35. <hr/> N. 0°01' W., bet. secs. 26 and 27. Over rolling land.
2.50	BIA Route 6322, a graded road, 30 ft. wide, bears N. 60° E. and S. 60° W.
40.00	Point for the 1/4 sec. cor. of secs. 26 and 27 falls on sandstone outcrop. Drill hole, 1 3/8 ins. diam., 18 ins. deep, in sandstone. Deposit a magnet, in a white plastic case, in drilled hole. Cement a stainless steel drive rod, 20 ins. long, 9/16 ins. diam., 15 ins. in drilled hole, with brass cap mkd.

Survey of the Subdivisional Lines,
T. 37 N., R. 15 E., Gila and Salt River Meridian, Arizona

CHAINS	
	T 37 N R 15 E 1/4 S 27 S 26 2018
80.00	<p>Point for the cor. of secs. 22, 23, 26 and 27, E. of a large sandstone outcrop.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 25 ins. in the ground, with brass cap mkd.</p>
	T 37 N R 15 E S 22 S 23 S 27 S 26 2018
	<p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p> <p>Set a steel fence post N. of the stainless steel post.</p> <hr/> <p>From the cor. of secs. 22, 23, 26 and 27.</p> <p>West, bet. secs. 23 and 26.</p> <p>Over rolling land.</p>
40.00	<p>Point for the 1/4 sec. cor. of secs. 23 and 26, SW of the westerly edge of a large sandstone outcrop.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p>
	T 37 N R 15 E S 23 1/4 ——— S 26 2018
	<p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p> <p>Set a steel fence post N. of the stainless steel post.</p>
80.00	<p>The cor. of secs. 22, 23, 26 and 27.</p> <hr/> <p>N. 0°01' W., bet. secs. 22 and 23.</p>

Survey of the Subdivisional Lines,
T. 37 N., R. 15 E., Gila and Salt River Meridian, Arizona

CHAINS	
	Over rolling land.
11.00	Enter gorge and descend approx. 90 ft.
16.00	Ascend approx. 85 ft. and leave gorge.
40.00	Point for the 1/4 sec. cor. of secs. 22 and 23.
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with brass cap mkd.
	T 37 N R 15 E 1/4 S 22 S 23 2018
	Deposit a magnet, in a white plastic case, at the base of the stainless steel post.
	Set a steel fence post W. of the stainless steel post.
	A large sandstone outcrop is NW of the stainless steel post.
66.40	Power line, bears East and West.
72.50	High voltage transmission line, bears East and West.
80.00	Point for the cor. of secs. 14, 15, 22 and 23.
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.
	T 37 N R 15 E S 15 S 14 S 22 S 23 2018
	Deposit a magnet, in a white plastic case, at the base of the stainless steel post.
	Set a steel fence post W. of the stainless steel post.

	From the cor. of secs. 13, 14, 23 and 24.
	West, bet. secs. 14 and 23.
	Over rolling land.
40.00	Point for the 1/4 sec. cor. of secs. 14 and 23 falls on sandstone outcrop.

Survey of the Subdivisional Lines,
T. 37 N., R. 15 E., Gila and Salt River Meridian, Arizona

CHAINS	
	<p>Drill hole, 1 3/8 ins. diam., 15 ins. deep, in sandstone. Deposit a magnet, in a white plastic case, in drilled hole.</p> <p>Cement a stainless steel drive rod, 23 ins. long, 9/16 ins. diam., 12 ins. in the drilled hole, with brass cap mkd.</p> <p style="text-align: center;">T 37 N R 15 E S 14 1/4 ——— S 23</p> <p style="text-align: center;">2018</p> <p>Encircle drive rod in collar of sandstone.</p>
80.00	<p>The cor. of secs. 14, 15, 22 and 23.</p> <hr/> <p>N. 0°01' W., bet. secs. 14 and 15.</p> <p>Over rolling land.</p>
39.60	<p>Enter gorge and descend approx. 20 ft.</p>
40.00	<p>Point for the 1/4 sec. cor. of secs. 14 and 15 falls on sandstone outcrop, sloped down to the N.</p> <p>Drill hole, 1 3/8 ins. diam., 18 ins. deep, in sandstone. Deposit a magnet, in a white plastic case, in drilled hole.</p> <p>Cement a stainless steel drive rod, 23 ins. long, 9/16 ins. diam., 18 ins. in the drilled hole, with brass cap mkd.</p> <p style="text-align: center;">T 37 N R 15 E 1/4 S 15 S 14</p> <p style="text-align: center;">2018</p> <p>Encircled drive rod in collar of sandstone.</p> <p>Cor. falls along the top of a ridge, bears E. and W., approx. 4 ft. dist. S. of the edge.</p>
50.50	<p>Ascend approx. 90 ft. and leave gorge.</p>
80.00	<p>Point for the cor. of secs. 10, 11, 14 and 15.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p>

Survey of the Subdivisional Lines,
T. 37 N., R. 15 E., Gila and Salt River Meridian, Arizona

CHAINS	
	T 37 N R 15 E S 10 S 11 S 15 S 14
	2018
	Deposit a magnet, in a white plastic case, at the base of the stainless steel post.
	Set a steel fence post W. of the stainless steel post.
	<hr/>
	From the cor. of secs. 11, 12, 13 and 14.
	West, bet. secs. 11 and 14.
	Over rolling land.
40.00	Point for the 1/4 sec. cor. of secs. 11 and 14.
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 25 ins. in the ground, with brass cap mkd.
	T 37 N R 15 E S 11 1/4 ——— S 14
	2018
	Deposit a magnet, in a white plastic case, at the base of the stainless steel post.
	Set a steel fence post N. of the stainless steel post.
80.00	The cor. of secs. 10, 11, 14 and 15.
	<hr/>
	N. 0°01' W., bet. secs. 10 and 11.
	Over rolling land.
15.90	Enter gorge and descend approx. 70 ft.
26.80	Ascend approx. 90 ft. to an area of high ground within the gorge.
40.00	Point for the 1/4 sec. cor. of secs. 10 and 11.
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.

Survey of the Subdivisional Lines,
T. 37 N., R. 15 E., Gila and Salt River Meridian, Arizona

CHAINS	
	T 37 N R 15 E 1/4 S 10 S 11 2018
	Deposit a magnet, in a white plastic case, at the base of the stainless steel post.
44.30	Leave the area of high ground and descend approx. 80 ft.
46.00	Begashibito Wash, 70 ft. wide, 7 ft. deep, drains S. 45° W.
79.30	Ascend approx. 40 ft. and leave gorge.
80.00	Point for the cor. of secs. 2, 3, 10 and 11, falls on sandstone, along a narrow outcrop, sloped down to the SE and into the gorge.
	Drill hole, 1 3/8 ins. diam., 15 ins. deep, in sandstone. Deposit a magnet, in a white plastic case, in drilled hole.
	Set a stainless steel drive rod, 20 ins. long, 9/16 ins. diam., 12 ins. in the drilled hole, with brass cap mkd.
	T 37 N R 15 E S 3 S 2 S 10 S 11 2018
	Encircle stainless steel drive rod in collar of stone.
	From the cor. of secs. 1, 2, 11 and 12.
	West, bet. secs. 2 and 11.
	Over rolling land.
0.95	Barbed wire fence, bears N. 20° E. and S. 20° W.
19.60	Enter gorge and descend approx. 40 ft.
24.45	Wash, 20 ft. wide, 5 ft. deep, drains S. 35° W.
29.50	Ascend approx. 55 ft. and leave gorge.
40.00	Point for the 1/4 sec. cor. of secs. 2 and 11.
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.

Survey of the Subdivisional Lines,
T. 37 N., R. 15 E., Gila and Salt River Meridian, Arizona

CHAINS	
	T 37 N R 15 E S 2 1/4 ——— S 11 2018
	Deposit a magnet, in a white plastic case, at the base of the stainless steel post. Set a steel fence post N. of the stainless steel post.
45.40	Enter gorge and descend approx. 35 ft.
49.30	Last End Wash, 40 ft. wide, 5 ft. deep, drains S. 45° W.
52.10	Ascend approx. 25 ft. and leave gorge.
74.40	Enter gorge and descend approx. 50 ft.
75.50	Begashibito Wash, 40 ft. wide, 15 ft. deep, drains S. 45° W.
78.50	Ascend approx. 35 ft. and leave gorge.
80.00	The cor. of secs. 2, 3, 10 and 11.
	<hr/> N. 0°01' W., bet. secs. 2 and 3. Over rolling land.
3.40	Enter gorge and descend approx. 60 ft.
18.50	Ascend approx. 65 ft. and leave gorge.
40.00	Point for the 1/4 sec. cor. of secs. 2 and 3.
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 25 ins. in the ground, with brass cap mkd.
	T 37 N R 15 E 1/4 S 3 S 2 2018
	Deposit a magnet, in a white plastic case, at the base of the stainless steel post. Set a steel fence post W. of the stainless steel post.
79.99	The cor. of secs. 2, 3, 34 and 35, on the N. bdy. of the Tp.

Survey of the Subdivisional Lines,
T. 37 N., R. 15 E., Gila and Salt River Meridian, Arizona

CHAINS	
	<p>From the standard cor. of secs. 33 and 34, on the S. bdy. of the Tp., hereinbefore described.</p> <p>N. 0°02' W., bet. secs. 33 and 34.</p> <p>Over rolling land.</p>
4.80	BIA Route 6322, a graded road, 27 ft. wide, bears N. 50° E. and S. 50° W.
16.90	Underground water line, bears N. 40° E. and S. 40° W.
40.00	<p>Point for the 1/4 sec. cor. of secs. 33 and 34, approx. 145 ft. dist. W. of an underground water line, bears North and South.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center;"> <p>T 37 N R 15 E 1/4 S 33 S 34</p> <p>2018</p> </div> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p> <p>Set a steel fence post W. of the stainless steel post.</p>
80.00	<p>Point for the cor. of secs. 27, 28, 33 and 34, falls on sandstone outcrop.</p> <p>Clear 0.5 ft. of sand from surface and drill hole, 1 3/8 ins. diam., 22 ins. deep, in sandstone. Deposit a magnet, in a white plastic case, in drilled hole.</p> <p>Cement a stainless steel drive rod, 20 ins. long, 9/16 ins. diam., 19 ins. in the drilled hole, with brass cap mkd.</p> <div style="text-align: center;"> <p>T 37 N R 15 E S 28 S 27 ----- S 33 S 34</p> <p>2018</p> </div> <p>Drill a second hole, 1 3/8 ins. diam., 18 ins. deep, in sandstone, N. of the stainless steel drive rod.</p> <p>Set a steel fence post in the second drilled hole.</p> <hr/> <p>From the cor. of secs. 26, 27, 34 and 35.</p>

Survey of the Subdivisional Lines,
T. 37 N., R. 15 E., Gila and Salt River Meridian, Arizona

CHAINS	
	West, bet. secs. 27 and 34.
	Over rolling land.
4.55	BIA Route 6322, a graded road, 20 ft. wide, bears N. 60° E. and S. 60° W.
40.00	Point for the 1/4 sec. cor. of secs. 27 and 34.
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.
	T 37 N R 15 E S 27 1/4 ——— S 34 2018
	Deposit a magnet, in a white plastic case, at the base of the stainless steel post.
	Set a steel fence post N. of the stainless steel post.
42.90	Underground water line, bears N. 35° E. and S. 35° W.
49.30	Underground water line, bears S. 50° E. and N. 50° W.
80.00	The cor. of secs. 27, 28, 33 and 34.

	N. 0°02' W., bet. secs. 27 and 28.
	Over rolling land.
24.20	Enter gorge and descend approx. 60 ft.
32.00	Ascend approx. 45 ft. and leave gorge.
40.00	Point for the 1/4 sec. cor. of secs. 27 and 28.
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.
	T 37 N R 15 E 1/4 S 28 S 27 2018
	Deposit a magnet, in a white plastic case, at the base of the stainless steel post.
	Set a steel fence post W. of the stainless steel post.

Survey of the Subdivisional Lines,
T. 37 N., R. 15 E., Gila and Salt River Meridian, Arizona

CHAINS									
47.90	Enter gorge and descend approx. 125 ft.								
61.60	Begashibito Wash, 100 ft. wide, 15 ft. deep, drains S. 55° W.								
66.90	Ascend approx. 125 ft. and leave gorge.								
80.00	Point for the cor. of secs. 21, 22, 26 and 27. Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 25 ins. in the ground, with brass cap mkd. <div style="text-align: center;"> <table border="1"> <tr> <td>T 37 N</td> <td>R 15 E</td> </tr> <tr> <td>S 21</td> <td>S 22</td> </tr> <tr> <td>S 28</td> <td>S 27</td> </tr> </table> <p>2018</p> </div> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p> <p>Set a steel fence post W. of the stainless steel post.</p> <hr/> <p>From the cor. of secs. 22, 23, 26 and 27.</p> <p>West, bet. secs. 22 and 27.</p> <p>Over rolling land.</p>	T 37 N	R 15 E	S 21	S 22	S 28	S 27		
T 37 N	R 15 E								
S 21	S 22								
S 28	S 27								
40.00	Point for the 1/4 sec. cor. of secs. 22 and 27 falls on sandstone outcrop, sloped down to the SW, approx. 40 ft. dist. from the top of bank. Drill hole, 1 3/8 ins. diam., 18 ins. deep, in sandstone. Deposit a magnet, in a white plastic case, in drilled hole. Cement a stainless steel drive rod, 20 ins. long, 9/16 ins. diam., 10 ins. in the drilled hole, with brass cap mkd. <div style="text-align: center;"> <table border="1"> <tr> <td>T 37 N</td> <td>R 15 E</td> </tr> <tr> <td></td> <td>S 22</td> </tr> <tr> <td>1/4</td> <td>_____</td> </tr> <tr> <td></td> <td>S 27</td> </tr> </table> <p>2018</p> </div> <p>Drill a second hole, 1 3/8 ins. diam., 18 ins. deep, in sandstone, N. of the stainless steel drive rod.</p> <p>Set a steel fence post in the second drilled hole.</p> <p>Raise supporting mound of stone, 2 1/2 ft. base, to top.</p>	T 37 N	R 15 E		S 22	1/4	_____		S 27
T 37 N	R 15 E								
	S 22								
1/4	_____								
	S 27								

Survey of the Subdivisional Lines,
T. 37 N., R. 15 E., Gila and Salt River Meridian, Arizona

CHAINS	
43.10	Enter gorge and descend approx. 165 ft.
58.30	Begashibito Wash, 170 ft. wide, 30 ft. deep, drains S. 20° E.
64.10	Ascend approx. 135 ft. and leave gorge.
80.00	The cor. of secs. 21, 22, 27 and 28.
	<hr/>
	N. 0°02' W., bet. secs. 21 and 22.
	Over rolling land.
40.00	Point for the 1/4 sec. cor. of secs. 21 and 22.
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.
	T 37 N R 15 E 1/4 S 21 S 22
	2018
	Deposit a magnet, in a white plastic case, at the base of the stainless steel post.
	Encircle brass cap in collar of stone.
	Set a steel fence post W. of the stainless steel post.
66.00	Power line, bears East and West.
71.65	High voltage transmission line, bears East and West.
80.00	Point for the cor. of secs. 15, 16, 21 and 22 falls in sandstone outcrop.
	Clear 1 ft. of sand and drill hole, 1 3/8 ins. diam., 18 ins. deep, in sandstone. Deposit a magnet, in a white plastic case, in drilled hole.
	Cement a stainless steel drive rod, 16 ins. long, 9/16 ins. diam., 15 ins. in the drilled hole, with brass cap mkd.
	T 37 N R 15 E S 16 S 15 S 21 S 22
	2018
	<hr/>
	From the cor. of secs. 14, 15, 22 and 23.

Survey of the Subdivisional Lines,
T. 37 N., R. 15 E., Gila and Salt River Meridian, Arizona

CHAINS	
	West, bet. secs. 15 and 22.
	Over rolling land.
28.50	Enter gorge and descend approx. 160 ft.
33.10	Begashibito Wash, 200 ft. wide, 30 ft. deep, drains S. 40° W.
36.10	Ascend approx. 140 ft. and leave gorge.
40.00	Point for the 1/4 sec. cor. of secs. 15 and 22.
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with brass cap mkd.
	T 37 N R 15 E S 15 1/4 ——— S 22 2018
	Deposit a magnet, in a white plastic case, at the base of the stainless steel post.
	Encircle brass cap in a collar of stone.
	Set a steel fence post N. of the stainless steel post.
80.00	The cor. of secs. 15, 16, 21 and 22.

	N. 0°02' W., bet. secs. 15 and 16.
	Over rolling land.
40.00	Point for the 1/4 sec. cor. of secs. 15 and 16.
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 25 ins. in the ground, with brass cap mkd.
	T 37 N R 15 E 1/4 S 16 S 15 2018
	Deposit a magnet, in a white plastic case, at the base of the stainless steel post.
	Set a steel fence post W. of the stainless steel post.
80.00	Point for the cor. of secs. 9, 10, 15 and 16.

Survey of the Subdivisional Lines,
T. 37 N., R. 15 E., Gila and Salt River Meridian, Arizona

CHAINS									
	<p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with brass cap mkd.</p>								
	<table style="margin-left: auto; margin-right: auto;"> <tr> <td>T 37 N</td> <td>R 15 E</td> </tr> <tr> <td>S 9</td> <td>S 10</td> </tr> <tr> <td>S 16</td> <td>S 15</td> </tr> </table>	T 37 N	R 15 E	S 9	S 10	S 16	S 15		
T 37 N	R 15 E								
S 9	S 10								
S 16	S 15								
	2018								
	<p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p>								
	<p>Set a steel fence post W. of the stainless steel post.</p> <hr/>								
	<p>From the cor. of secs. 10, 11, 14 and 15.</p>								
	<p>West, bet. secs. 10 and 15.</p>								
	<p>Over rolling land.</p>								
2.40	Enter gorge and descend approx. 185 ft.								
9.10	Begashibito Wash, 65 ft. wide, 35 ft. deep, drains S. 45° E.								
21.60	Ascend approx. 160 ft. and leave gorge.								
40.00	Point for the 1/4 sec. cor. of secs. 10 and 15.								
	<p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 27 ins. in the ground, with brass cap mkd.</p>								
	<table style="margin-left: auto; margin-right: auto;"> <tr> <td>T 37 N</td> <td>R 15 E</td> </tr> <tr> <td>S 10</td> <td></td> </tr> <tr> <td>1/4</td> <td>—</td> </tr> <tr> <td>S 15</td> <td></td> </tr> </table>	T 37 N	R 15 E	S 10		1/4	—	S 15	
T 37 N	R 15 E								
S 10									
1/4	—								
S 15									
	2018								
	<p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p>								
	<p>Set a steel fence post N. of the stainless steel post.</p>								
80.00	<p>The cor. of secs. 9, 10, 15 and 16.</p> <hr/>								
	<p>N. 0°02' W., bet. secs. 9 and 10.</p>								
	<p>Over rolling land.</p>								
38.00	Trail road, 8 ft. wide, bears N. 15° E. and S. 15° W.								

Survey of the Subdivisional Lines,
T. 37 N., R. 15 E., Gila and Salt River Meridian, Arizona

CHAINS	
40.00	<p>Point for the 1/4 sec. cor. of secs. 9 and 10.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 25 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T 37 N R 15 E 1/4 S 9 S 10</p> <p style="text-align: center;">2018</p> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p> <p>Set a steel fence post W. of the stainless steel post.</p>
80.00	<p>Point for the cor. of secs. 3, 4, 9, 10.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T 37 N R 15 E S 4 S 3 ----- S 9 S 10</p> <p style="text-align: center;">2018</p> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p> <p>Set a steel fence post W. of the stainless steel post.</p> <hr/> <p>From the cor. of secs. 2, 3, 10 and 11.</p> <p>West, bet. secs. 3 and 10.</p> <p>Over rolling land.</p>
3.10	Enter gorge and descend approx. 15 ft.
6.60	Ascend approx. 100 ft. and leave gorge.
40.00	<p>Point for the 1/4 sec. cor. of secs. 3 and 10.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 25 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T 37 N R 15 E S 3 1/4 ——— S 10</p> <p style="text-align: center;">2018</p>

Survey of the Subdivisional Lines,
T. 37 N., R. 15 E., Gila and Salt River Meridian, Arizona

CHAINS	
	Deposit a magnet, in a white plastic case, at the base of the stainless steel post.
	Set a steel fence post N. of the stainless steel post.
80.00	The cor. of secs. 3, 4, 9 and 10.
	<hr/>
	N. 0°02' W., bet. secs. 3 and 4.
	Over rolling land.
40.00	Point for the 1/4 sec. cor. of secs. 3 and 4.
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 23 ins. in the ground, with brass cap mkd.
	T 37 N R 15 E 1/4 S 4 S 3 2018
	Deposit a magnet, in a white plastic case, at the base of the stainless steel post.
	Set a steel fence post W. of the stainless steel post.
79.99	The cor. of secs. 3, 4, 33 and 34, on the N. bdy. of the Tp.
	<hr/>
	From the standard cor. of secs. 32 and 33, on the S. bdy. of the Tp., hereinbefore described.
	N. 0°02' W., bet. secs. 32 and 33.
	Over rolling land.
4.80	Enter gorge and descend approx. 50 ft.
16.50	Begashibito Wash, 100 ft. wide, 10 ft. deep, drains S. 50° W.
27.90	Ascend approx. 90 ft. and leave gorge.
40.00	Point for the 1/4 sec. cor. of secs. 32 and 33.
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.

Survey of the Subdivisional Lines,
T. 37 N., R. 15 E., Gila and Salt River Meridian, Arizona

CHAINS	
	T 37 N R 15 E 1/4 S 32 S 33 2018
	Deposit a magnet, in a white plastic case, at the base of the stainless steel post.
	Set a steel fence post W. of the stainless steel post.
80.00	Point for the cor. of secs. 28, 29, 32 and 33. Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.
	T 37 N R 15 E S 29 S 28 S 32 S 33 2018
	Deposit a magnet, in a white plastic case, at the base of the stainless steel post.
	Set a steel fence post N. of the stainless steel post.
	<hr/> From the cor. of secs. 27, 28, 33 and 34. West, bet. secs. 28 and 33. Over rolling land.
28.90	Enter gorge and descend approx. 75 ft.
36.85	Point selected for the witness cor. of the 1/4 sec. cor. of secs. 28 and 33. Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 27 ins. in the ground, with brass cap mkd.
	WC T 37 N R 15 E S 28 1/4 ← S 33 2018
	Deposit a magnet, in a white plastic case, at the base of the stainless steel post.
	Set a steel fence post NW. of the stainless steel post.

Survey of the Subdivisional Lines,
T. 37 N., R. 15 E., Gila and Salt River Meridian, Arizona

CHAINS	
40.00	True point for the 1/4 sec. cor. of secs. 28 and 33 falls in Begashibito Wash where it is impractical to establish a permanent monument.
40.80	Begashibito Wash, 120 ft. wide, 8 ft. deep, drains S. 15° W.
48.10	Ascend approx. 100 ft. and leave gorge.
80.00	The cor. of secs. 28, 29, 32 and 33.

	N. 0°02' W., bet. secs. 28 and 29.
	Over rolling land
40.00	Point for the 1/4 sec. cor. of secs. 28 and 29.
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.
	T 37 N R 15 E 1/4 S 29 S 28
	2018
	Deposit a magnet, in a white plastic case, at the base of the stainless steel post.
	Set a steel fence post W. of the stainless steel post.
80.00	Point for the cor. of secs. 20, 21, 28 and 29.
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.
	T 37 N R 15 E S 20 S 21 S 29 S 28
	2018
	Deposit a magnet, in a white plastic case, at the base of the stainless steel post.
	Set a steel fence post W. of the stainless steel post.

	From the cor. of secs. 28, 29, 32 and 33.
	West, bet. secs. 21 and 28.
	Over rolling land.

Survey of the Subdivisional Lines,
T. 37 N., R. 15 E., Gila and Salt River Meridian, Arizona

CHAINS	
40.00	<p>Point for the 1/4 sec. cor. of secs. 21 and 28.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T 37 N R 15 E S 21 1/4 ——— S 28</p> <p style="text-align: center;">2018</p> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p> <p>Set a steel fence post N. of the stainless steel post.</p>
80.00	<p>The cor. of secs. 20, 21, 28 and 29.</p> <hr/> <p>N. 0°02' W., bet. secs. 20 and 21.</p> <p>Over rolling land.</p>
39.10	<p>Graded road, 22 ft. wide, bears N. 75° E. and S. 75° W.</p>
40.00	<p>Point for the 1/4 sec. cor. of secs. 20 and 21.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 23 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T 37 N R 15 E 1/4 S 20 S 21</p> <p style="text-align: center;">2018</p> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p> <p>Set a steel fence post W. of the stainless steel post.</p>
46.90	<p>Graded road, 15 ft. wide, bears N. 25° E. and S. 25° W.</p>
65.65	<p>Power line, bears East and West.</p>
70.75	<p>High voltage transmission line, bears East and West.</p>
78.72	<p>Intersect the southerly line of a home site.</p> <p>From this point the SE cor. of the home site bears N. 86°28' E., 0.661 chs. dist., monumented with a rebar, 5/8 ins. diam., firmly set, flush with the ground, with a plastic cap mkd. GPS RLS 42048.</p>

Survey of the Subdivisional Lines,
T. 37 N., R. 15 E., Gila and Salt River Meridian, Arizona

CHAINS	<p>A second rebar, 1/2 ins. diameter, firmly set, projecting 35 ins. above ground, is SE of the capped rebar.</p> <p>From this same point the SW cor. of the home site bears S. 86°28' W., 2.500 chs. dist., monumented with a rebar, 5/8 ins. diam., firmly set, flush with the ground, with a plastic cap mkd. GPS RLS 42048. A second rebar, 1/2 ins. diameter, firmly set, projecting 27 ins. above ground, is SW of the capped rebar.</p> <p>80.00 Point for the cor. of secs. 16, 17, 20 and 21 falls in the root of a piñon tree, NE of one single story house, and E. of another single story house.</p> <p>Set a stainless steel drive rod, 20 ins. long, 9/16 ins. diam., 18 ins. in the ground, through the tree root, with brass cap mkd.</p> <div style="text-align: center;"> <p>T 37 N R 15 E</p> <table border="1" style="margin: auto;"> <tr> <td>S 17</td> <td>S 16</td> </tr> <tr> <td>S 20</td> <td>S 21</td> </tr> </table> <p>2018</p> </div> <hr/> <p>From the cor. of secs. 15, 16, 21 and 22</p> <p>West, bet. secs. 16 and 21.</p> <p>Over rolling land.</p> <p>6.70 Navajo Hogan, approx. 24 ft. by 24 ft.</p> <p>39.80 Point selected for the witness cor. of the 1/4 sec. cor. of secs. 16 and 21.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 28 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center;"> <p>WC</p> <p>T 37 N R 15 E</p> <p>S 16</p> <p>1/4 ←</p> <p>S 21</p> <p>2018</p> </div> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p> <p>40.00 True point for the 1/4 sec. cor. of secs. 16 and 21, falls in developing wash, 10 ft. wide, 3 ft. deep, drains N. 45 E., where it is impractical to establish a permanent monument.</p> <p>60.40 Graded road, 10 ft. wide, bears N. 5° E. and S. 5° W.</p>	S 17	S 16	S 20	S 21
S 17	S 16				
S 20	S 21				

Survey of the Subdivisional Lines,
T. 37 N., R. 15 E., Gila and Salt River Meridian, Arizona

CHAINS	
77.90	Barbed wire fence, bears N. 15° E. and S. 15° W.
79.10	Barbed wire fence, bears N. 15° E. and S. 15° W.
79.42	Intersect the easterly line of a home site. From this point, the NE cor. of the home site, bears N. 3°31' W., 1.924 chs. dist., monumented with a rebar, 5/8 ins. diam., firmly set, projecting 1 in. above ground, with a plastic cap mkd. GPS RLS 42048. A second rebar, 1/2 ins. diameter, firmly set, projecting 26 ins. above ground, is NE of the capped rebar. From this same point, the SE cor. of the home site bears S. 3°31' E., 1.237 chs. dist., monumented with a rebar, 5/8 ins. diam., firmly set, flush with the ground, with a plastic cap mkd. GPS RLS 42048. A second rebar, 1/2 ins. diameter, firmly set, projecting 35 ins. above ground, is SE of the capped rebar.
80.00	The cor. of secs. 16, 17, 20 and 21. ----- N. 0°02' W., bet. secs. 16 and 17. Over rolling land.
1.89	Intersect the northerly line of a home site. From this point, the NE cor. of the home site bears N. 86°28' E., 0.469 chs. dist., monumented with a rebar, 5/8 ins. diam., firmly set, projecting 1 in. above ground, with a plastic cap mkd. GPS RLS 42048. A second rebar, 1/2 ins. diameter, firmly set, projecting 26 ins. above ground, is NE of the capped rebar. From this same point the NW cor. of the home site bears S. 86°28' W., 2.695 chs. dist., monumented with a rebar, 5/8 ins. diam., firmly set, projecting 1 in. above ground, with a plastic cap mkd. GPS RLS 42048. A second rebar, 1/2 ins. diameter, firmly set, projecting 31 ins. above ground, is NW of the capped rebar.
40.00	Point for the 1/4 sec. cor. of secs. 16 and 17. Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd. <div style="text-align: center;"> T 37 N R 15 E 1/4 S 17 S 16 2018 </div> Deposit a magnet, in a white plastic case, at the base of the stainless steel post. Set a steel fence post W. of the stainless steel post.

Survey of the Subdivisional Lines,
T. 37 N., R. 15 E., Gila and Salt River Meridian, Arizona

CHAINS									
71.20	Graded road, 17 ft. wide, bears S. 10° E. and N. 10° W.								
80.00	Point for the cor. of secs. 8, 9, 16 and 17. Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd. <div style="text-align: center;"> <table style="margin: auto;"> <tr><td>T 37 N</td><td>R 15 E</td></tr> <tr><td>S 8</td><td>S 9</td></tr> <tr><td>S 17</td><td>S 16</td></tr> </table> <p>2018</p> </div> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p> <p>Set a steel fence post W. of the stainless steel post.</p> <hr/> <p>From the cor. of secs. 9, 10, 15 and 16 West, bet. secs. 9 and 16. Over rolling land.</p>	T 37 N	R 15 E	S 8	S 9	S 17	S 16		
T 37 N	R 15 E								
S 8	S 9								
S 17	S 16								
40.00	Point for the 1/4 sec. cor. of secs. 9 and 16 Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd. <div style="text-align: center;"> <table style="margin: auto;"> <tr><td>T 37 N</td><td>R 15 E</td></tr> <tr><td>S 9</td><td></td></tr> <tr><td>1/4</td><td>—</td></tr> <tr><td>S 16</td><td></td></tr> </table> <p>2018</p> </div> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p>	T 37 N	R 15 E	S 9		1/4	—	S 16	
T 37 N	R 15 E								
S 9									
1/4	—								
S 16									
80.00	The cor. of secs. 8, 9, 16 and 17. <hr/> <p>N. 0°02' W., bet. secs. 8 and 9. Over rolling land.</p>								
40.00	Point for the 1/4 sec. cor. of secs. 8 and 9. Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.								

Survey of the Subdivisional Lines,
T. 37 N., R. 15 E., Gila and Salt River Meridian, Arizona

CHAINS	
	T 37 N R 15 E 1/4 S 8 S 9 2018
	Deposit a magnet, in a white plastic case, at the base of the stainless steel post.
	Set a steel fence post W. of the stainless steel post.
80.00	Point for the cor. of secs. 4, 5, 8 and 9. Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 25 ins. in the ground, with brass cap mkd.
	T 37 N R 15 E S 5 S 4 S 8 S 9 2018
	Deposit a magnet, in a white plastic case, at the base of the stainless steel post.
	Set a steel fence post W. of the stainless steel post.
	<hr/> From the cor. of secs. 3, 4, 9 and 10. West, bet. secs. 4 and 9. Over rolling land.
40.00	Point for the 1/4 sec. cor. of secs. 4 and 9. Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with brass cap mkd.
	T 37 N R 15 E S 4 1/4 ——— S 9 2018
	Deposit a magnet, in a white plastic case, at the base of the stainless steel post.
	Set a steel fence post N. of the stainless steel post.
80.00	The cor. of secs. 4, 5, 8 and 9. <hr/>

Survey of the Subdivisional Lines,
T. 37 N., R. 15 E., Gila and Salt River Meridian, Arizona

CHAINS	
	N. 0°02' W., bet. secs. 4 and 5. Over rolling land.
40.00	Point for the 1/4 sec. cor. of secs. 4 and 5. Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 25 ins. in the ground, with brass cap mkd. <div style="text-align: center;"> T 37 N R 15 E 1/4 S 5 S 4 2018 </div>
	Deposit a magnet, in a white plastic case, at the base of the stainless steel post. Set a steel fence post W. of the stainless steel post.
79.99	The cor. of secs. 4, 5, 32 and 33, on the N. bdy. of the Tp. <hr style="width: 50%; margin-left: 0;"/> From the standard cor. of secs. 31 and 32, on the S. bdy. of the Tp., hereinbefore described. N. 0°03' W., bet. secs. 31 and 32. Over rolling land.
6.20	Barbed wire fence, 4 strands, bears S. 45° E. and N. 45° W.
7.89	Arizona State Highway No. 98, southwesterly edge of asphalt surface, bears S. 45° E. and N. 45° W.
8.62	Arizona State Highway No. 98, northeasterly edge of asphalt surface, bears S. 45° E. and N. 45° W.
10.30	Barbed wire fence, 4 strands, bears S. 45° E. and N. 45° W.
37.70	Trail road, 9 ft. wide, bears S. 65° E. and N. 65° W.
38.10	Trail road, 8 ft. wide, bears S. 65° E. and N. 75° W.
40.00	Point for the 1/4 sec. cor. of secs. 31 and 32. Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd. <div style="text-align: center;"> T 37 N R 15 E 1/4 S 31 S 32 2018 </div>

Survey of the Subdivisional Lines,
T. 37 N., R. 15 E., Gila and Salt River Meridian, Arizona

CHAINS																	
	<p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p> <p>Set a steel fence post E. of the stainless steel post.</p>																
40.20	Trail road, 7 ft. wide, bears S. 25° E. and N. 25° W.																
47.60	Underground water line, bears S. 25° E. and N. 25° W.																
57.30	Underground water line, bears S. 70° E. and N. 70° W.																
72.80	Graded road, 27 ft. wide, bears N. 20° E. and S. 20° W.																
80.00	Point for the cor. of secs. 29, 30, 31 and 32.																
	<p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center; margin: 10px 0;"> <table style="margin: auto; border-collapse: collapse;"> <tr> <td colspan="2">T 37 N</td> <td colspan="2">R 15 E</td> </tr> <tr> <td style="border-right: 1px solid black; padding: 0 5px;">S 30</td> <td style="padding: 0 5px;"> </td> <td style="padding: 0 5px;">S 29</td> <td></td> </tr> <tr> <td style="border-right: 1px solid black; padding: 0 5px;">S 31</td> <td style="padding: 0 5px;"> </td> <td style="padding: 0 5px;">S 32</td> <td></td> </tr> </table> <p style="margin: 5px 0;">2018</p> </div> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p> <p>Set a steel fence post N. of the stainless steel post.</p> <hr style="width: 60%; margin: 10px auto;"/> <p>From the cor. of secs. 28, 29, 32 and 33.</p> <p>West, bet. secs. 29 and 32.</p> <p>Over rolling land.</p>	T 37 N		R 15 E		S 30		S 29		S 31		S 32					
T 37 N		R 15 E															
S 30		S 29															
S 31		S 32															
27.20	Graded road, 27 ft. wide, bears S. 15° E. and N. 25° W.																
40.00	Point for the 1/4 sec. cor. of secs. 29 and 32.																
	<p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center; margin: 10px 0;"> <table style="margin: auto; border-collapse: collapse;"> <tr> <td colspan="2">T 37 N</td> <td colspan="2">R 15 E</td> </tr> <tr> <td colspan="2"></td> <td colspan="2" style="text-align: center;">S 29</td> </tr> <tr> <td colspan="2"></td> <td colspan="2" style="text-align: center;">1/4 ———</td> </tr> <tr> <td colspan="2"></td> <td colspan="2" style="text-align: center;">S 32</td> </tr> </table> <p style="margin: 5px 0;">2018</p> </div> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p>	T 37 N		R 15 E				S 29				1/4 ———				S 32	
T 37 N		R 15 E															
		S 29															
		1/4 ———															
		S 32															

Survey of the Subdivisional Lines,
T. 37 N., R. 15 E., Gila and Salt River Meridian, Arizona

CHAINS	
	Set a steel fence post N. of the stainless steel post.
77.30	Graded road, 30 ft. wide, bears N. 20° E. and S. 20° W.
80.00	The cor. of secs. 29, 30, 31 and 32.

	West, bet. secs. 30 and 31.
	Over rolling land.
40.00	Point for the 1/4 sec. cor. of secs. 30 and 31 falls in sandstone outcrop.
	Drill hole, 1 3/8 ins. diam., 18 ins. deep, in sandstone. Deposit a magnet, in a white plastic case, in drilled hole.
	Cement a stainless steel drive rod, 20 ins. long, 9/16 ins. diam., 16 ins. in the ground, with brass cap mkd.
	T 37 N R 15 E S 30 1/4 _____ S 31 2018
65.60	Underground water line, bears S. 50° E. and N. 50° W.
79.91	The cor. of secs. 25, 30, 31 and 36, on the W. bdy. of the Tp., monumented with a stainless steel post, firmly set, projecting 3 ins. above ground, with brass cap mkd. T37N R14E R15E S25 S30 S36 S31 2005. Add the marks 2018 to the brass cap. Set a steel fence post N. of the stainless steel post.
	from which the original bearing tree
	A piñon, 9 ins. diam., bears S. 21 3/4° W., 79 lks. dist., with scribe marks T37N R14E S36 BT visible on partially open blaze.

	From the cor. of secs. 29, 30, 31 and 32.
	N. 0°03' W., bet. secs. 29 and 30.
	Over rolling land.
20.80	Graded road, 17 ft. wide, bears S. 70° E. and N. 70° W.
40.00	Point for the 1/4 sec. cor. of secs. 29 and 30.
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 25 ins. in the ground, with brass cap mkd.

Survey of the Subdivisional Lines,
T. 37 N., R. 15 E., Gila and Salt River Meridian, Arizona

CHAINS	
	T 37 N R 15 E 1/4 S 30 S 29 2018
	Deposit a magnet, in a white plastic case, at the base of the stainless steel post.
	Set a steel fence post W. of the stainless steel post.
80.00	Point for the cor. of secs. 19, 20, 29 and 30. Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.
	T 37 N R 15 E S 19 S 20 S 30 S 29 2018
	Deposit a magnet, in a white plastic case, at the base of the stainless steel post.
	Set a steel fence post N. of the stainless steel post.
	<hr/> From the cor. of secs. 20, 21, 28 and 29. West, bet. secs. 20 and 29. Over rolling land.
40.00	Point for the 1/4 sec. cor. of secs. 20 and 29. Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 22 ins. in the ground, with brass cap mkd.
	T 37 N R 15 E S 20 1/4 ——— S 29 2018
	Deposit a magnet, in a white plastic case, at the base of the stainless steel post.
	Encircle brass cap in a collar of stone.
	Set a steel fence post N. of the stainless steel post.

Survey of the Subdivisional Lines,
T. 37 N., R. 15 E., Gila and Salt River Meridian, Arizona

CHAINS	
46.60	Graded road, 15 ft. wide, bears N. 25° E. and S. 65° W.
80.00	The cor. of secs. 19, 20, 29 and 30.
<hr style="border: 0.5px solid black;"/>	
	West, bet. secs. 19 and 30.
	Over rolling land.
40.00	Point for the 1/4 sec. cor. of secs. 19 and 30.
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.
	T 37 N R 15 E S 19 1/4 ——— S 30 2018
	Deposit a magnet, in a white plastic case, at the base of the stainless steel post.
	Set a steel fence post N. of the stainless steel post.
79.83	The cor. of secs. 19, 24, 25 and 30, on the W. bdy. of the Tp., monumented with a stainless steel post, firmly set, projecting 1 in. above ground, with brass cap mkd. T37N R14E R15E S24 S19 S25 S30 2005. Add the marks 2018 to the brass cap. Set a steel fence post N. of the stainless steel post.
<hr style="border: 0.5px solid black;"/>	
	From the cor. of secs. 19, 20, 29 and 30.
	N. 0°03' W., bet. secs. 19 and 20.
	Over rolling land.
40.00	Point for the 1/4 sec. cor. of secs. 19 and 20.
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.
	T 37 N R 15 E 1/4 S 19 S 20 2018
	Deposit a magnet, in a white plastic case, at the base of the stainless steel post.
	Set a steel fence post W. of the stainless steel post.

Survey of the Subdivisional Lines,
T. 37 N., R. 15 E., Gila and Salt River Meridian, Arizona

CHAINS							
65.20	Power line, bears East and West.						
69.85	High voltage transmission line, bears East and West.						
80.00	Point for the cor. of secs. 17, 18, 19 and 20. Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 25 ins. in the ground, with brass cap mkd. <div style="text-align: center;"> <table border="1"> <tr> <td>T 37 N</td> <td>R 15 E</td> </tr> <tr> <td>S 18</td> <td>S 17</td> </tr> <tr> <td>S 19</td> <td>S 20</td> </tr> </table> <p>2018</p> </div> Deposit a magnet, in a white plastic case, at the base of the stainless steel post. Set a steel fence post N. of the stainless steel post. <hr/> From the cor. of secs. 16, 17, 20 and 21. West, bet. secs. 17 and 20. Over rolling land.	T 37 N	R 15 E	S 18	S 17	S 19	S 20
T 37 N	R 15 E						
S 18	S 17						
S 19	S 20						
2.58	Intersect the westerly line of a home site. from which the SW cor. of the home site <div style="text-align: center;"> A rebar, 5/8 ins. diam., firmly set, flush with the ground, bears S. 3°34' E., 1.433 chs. dist. with a plastic cap mkd. GPS RLS 42048. A second rebar, 1/2 ins. diameter, firmly set, projecting 27 ins. above ground, is SW of the capped rebar. </div> and the NW cor. of the home site <div style="text-align: center;"> A rebar, 5/8 ins. diam., firmly set, projecting 1 in. above ground, bears N. 3°34' W., 1.729 chs. dist. with a plastic cap mkd. GPS RLS 42048. A second rebar, 1/2 ins. diameter, firmly set, projecting 31 ins. above ground, is NW of the capped rebar. </div>						
40.00	Point for the 1/4 sec. cor. of secs. 17 and 20. Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.						

Survey of the Subdivisional Lines,
T. 37 N., R. 15 E., Gila and Salt River Meridian, Arizona

CHAINS	
	T 37 N R 15 E S 17 1/4 ——— S 20 2018
	Deposit a magnet, in a white plastic case, at the base of the stainless steel post.
	Set a steel fence post N. of the stainless steel post.
80.00	The cor. of secs. 17, 18, 19 and 20. <hr/> West, bet. secs. 18 and 19. Over rolling land.
40.00	Point for the 1/4 sec. cor. of secs. 18 and 19. Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 25 ins. in the ground, with brass cap mkd.
	T 37 N R 15 E S 18 1/4 ——— S 19 2018
	Deposit a magnet, in a white plastic case, at the base of the stainless steel post.
	Set a steel fence post N. of the stainless steel post.
40.05	Mesh wire fence, partially collapsed, bears N. 25° E. and S. 25° W.
79.74	The cor. of secs. 13, 18, 19 and 24, on the W. bdy. of the Tp., monumented with a stainless steel post, firmly set, projecting 2 ins. above ground, with brass cap mkd. T37N R14E R15E S13 S18 S24 S19 2005. Metal tag, wired to stainless steel post, mkd. WHPACIFIC LS33318 KAM 11/08. Add the marks 2018 to the brass cap. Set a steel fence post N. of the stainless steel post. from which the original bearing tree A juniper, 12 ins. diam., bears N. 56 1/2° W., 17.5 lks. dist., with scribe marks T37N R14E S13 BT visible on partially open blaze.
	<hr/> From the cor. of secs. 17, 18, 19 and 20.

Survey of the Subdivisional Lines,
T. 37 N., R. 15 E., Gila and Salt River Meridian, Arizona

CHAINS							
	N. 0°03' W., bet. secs. 17 and 18. Over rolling land.						
40.00	Point for the 1/4 sec. cor. of secs. 17 and 18. Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd. <div style="text-align: center;"> <table style="margin: auto;"> <tr><td>T 37 N</td><td>R 15 E</td></tr> <tr><td>1/4</td><td></td></tr> <tr><td>S 18</td><td> S 17</td></tr> </table> <p>2018</p> </div> Deposit a magnet, in a white plastic case, at the base of the stainless steel post. Set a steel fence post W. of the stainless steel post.	T 37 N	R 15 E	1/4		S 18	S 17
T 37 N	R 15 E						
1/4							
S 18	S 17						
80.00	Point for the cor. of secs. 7, 8, 17 and 18. Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 25 ins. in the ground, with brass cap mkd. <div style="text-align: center;"> <table style="margin: auto;"> <tr><td>T 37 N</td><td>R 15 E</td></tr> <tr><td>S 7</td><td> S 8</td></tr> <tr><td>S 18</td><td> S 17</td></tr> </table> <p>2018</p> </div> Deposit a magnet, in a white plastic case, at the base of the stainless steel post. Set a steel fence post N. of the stainless steel post. <hr/>	T 37 N	R 15 E	S 7	S 8	S 18	S 17
T 37 N	R 15 E						
S 7	S 8						
S 18	S 17						
	From the cor. of secs. 8, 9, 16 and 17. West, bet. secs. 8 and 17. Over rolling land.						
1.25	Graded road, 17 ft. wide, bears S. 30° E. and N. 30° W.						
40.00	Point for the 1/4 sec. cor. of secs. 8 and 17. Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 25 ins. in the ground, with brass cap mkd.						

Survey of the Subdivisional Lines,
T. 37 N., R. 15 E., Gila and Salt River Meridian, Arizona

CHAINS	
	T 37 N R 15 E S 8 1/4 ——— S 17 2018
	Deposit a magnet, in a white plastic case, at the base of the stainless steel post.
	Set a steel fence post N. of the stainless steel post.
80.00	The cor. of secs. 7, 8, 17 and 18. <hr/> West, bet. secs. 7 and 18. Over rolling land.
0.95	Trail road, 7 ft. wide, bears N. 25° E. and S. 25° W.
40.00	Point for the 1/4 sec. cor. of secs. 7 and 18. Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.
	T 37 N R 15 E S 7 1/4 ——— S 18 2018
	Deposit a magnet, in a white plastic case, at the base of the stainless steel post.
	Set a steel fence post N. of the stainless steel post.
44.95	Graded road, 12 ft. wide, bears N. 5° E. and S. 20° W.
79.65	The cor. of secs. 7, 12, 13 and 18, on the W. bdy. of the Tp., monumented with a stainless steel post, firmly set, projecting 2 ins. above ground, with brass cap mkd. T37N R14E R15E S12 S7 S13 S18 2005. Add the marks 2018 to the brass cap. Set a steel fence post N. of the stainless steel post. from which the original bearing trees A triple juniper, the NE. trunk of which is 12 ins. diam., bears S. 76° W., 57 1/2 lks. dist., with scribe marks T37N R14E S13 BT visible on partially open blaze. (Record: 59 lks. dist.)

Survey of the Subdivisional Lines,
T. 37 N., R. 15 E., Gila and Salt River Meridian, Arizona

CHAINS	
	<p style="text-align: center;">A juniper, 14 ins. diam., bears N. 9 1/2° W., 27.5 lks. dist., with scribe marks T37N R14E S12 BT visible on partially open blaze.</p> <hr/> <p>From the cor. of secs. 7, 8, 17 and 18.</p> <p>N. 0°03' W., bet. secs. 7 and 8.</p> <p>Over rolling land.</p>
2.00	Trail road, 8 ft. wide, bears N. 25° E., S. 60° E., and S. 25° W.
40.00	<p>Point for the 1/4 sec. cor. of secs. 7 and 8.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 25 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center;"> <p>T 37 N R 15 E</p> <p style="margin-left: 40px;">1/4</p> <p style="margin-left: 20px;">S 7 S 8</p> <p>2018</p> </div> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p> <p>Set a steel fence post W. of the stainless steel post.</p>
73.30	Graded road, 12 ft. wide, bears N. 65° E. and S. 85° W.
80.00	<p>Point for the cor. of secs. 5, 6, 7 and 8.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center;"> <p>T 37 N R 15 E</p> <p style="margin-left: 20px;">S 6 S 5</p> <p style="margin-left: 20px;">S 7 S 8</p> <p>2018</p> </div> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p> <p>Set a steel fence post N. of the stainless steel post.</p> <hr/> <p>From the cor. of secs. 4, 5, 8 and 9.</p> <p>West, bet. secs. 5 and 8.</p> <p>Over rolling land.</p>

Survey of the Subdivisional Lines,
T. 37 N., R. 15 E., Gila and Salt River Meridian, Arizona

CHAINS	
39.40	Wash, 11 ft. wide, 2 ft. deep, drains S. 10° W.
40.00	Point for the 1/4 sec. cor. of secs. 5 and 8. Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with brass cap mkd. <div style="text-align: center;"> T 37 N R 15 E S 5 1/4 ——— S 8 2018 </div>
	Deposit a magnet, in a white plastic case, at the base of the stainless steel post. Set a steel fence post N. of the stainless steel post.
48.00	Graded road, 15 ft. wide, bears S. 30° E. and N. 30° W.
75.50	Graded road, 12 ft. wide, bears N. 35° E. and S. 30° W.
80.00	The cor. of secs. 5, 6, 7 and 8. <hr/>
	West, bet. secs. 6 and 7. Over rolling land.
40.00	Point for the 1/4 sec. cor. of secs. 6 and 7. Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with brass cap mkd. <div style="text-align: center;"> T 37 N R 15 E S 6 1/4 ——— S 7 2018 </div>
	Deposit a magnet, in a white plastic case, at the base of the stainless steel post. Set a steel fence post N. of the stainless steel post.
62.25	Barbed wire fence, 4 strands, bears N. 30° E. and S. 30° W.
63.70	BIA Route No. 16, southeasterly edge of asphalt surface, bears N. 30° E. and S. 30° W.
64.18	BIA Route No. 16, northwesterly edge of asphalt surface, bears N. 30° E. and S. 30° W.

**Survey of the Subdivisional Lines,
T. 37 N., R. 15 E., Gila and Salt River Meridian, Arizona**

CHAINS	
65.75	Barbed wire fence, 4 strands, bears N. 30° E. and S. 30° W.
79.57	<p>The cor. of secs. 1, 6, 7 and 12, on the W. bdy. of the Tp., monumented with a stainless steel post, firmly set, projecting 2 ins. above ground, with brass cap mkd. T37N R14E R15E S1 S6 S12 S7 2005. Add the marks 2018 to the brass cap. Set a steel fence post W. of the stainless steel post.</p> <p>from which the original bearing tree</p> <p style="padding-left: 40px;">A juniper, 11 ins. diam. at base of trunk, bears N. 29 1/4° E., 93.5 lks. dist., with scribe marks T37N R15E S6 BT visible on partially open blaze.</p> <hr/> <p>From the cor. of secs. 5, 6, 7 and 8.</p> <p>N. 0°03' W., bet. secs. 5 and 6.</p> <p>Over rolling land.</p>
40.00	<p>Point for the 1/4 sec. cor. of secs. 5 and 6 falls along a hillside, sloped down to the S.</p> <p>Scattered pieces of old clay pottery are present near the cor.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 25 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center;"> <p>T 37 N R 15 E</p> <p style="margin-left: 40px;">1/4</p> <p style="margin-left: 40px;">S 6 S 5</p> <p style="margin-left: 40px;">2018</p> </div> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p> <p>Set a steel fence post W. of the stainless steel post.</p>
48.00	Graded road, 19 ft. wide, bears S. 50° E. and N. 40° W.
80.00	The cor. of secs. 5, 6, 31 and 32, on the N. bdy. of the Tp.
<p>Subdivision of Section 6, T. 37 N., R. 15 E., Gila and Salt River Meridian, Arizona</p> <hr/>	
	<p>From the 1/4 sec. cor. of secs. 6 and 7.</p> <p>N. 0°03' W., along the N. and S. center line of sec. 6.</p> <p>Over rolling land.</p>

Subdivision of Section 6,
T. 37 N., R. 15 E., Gila and Salt River Meridian, Arizona

CHAINS	
36.95	Barbed wire fence, 4 strands, bears N. 30° E. and S. 30° W.
39.63	BIA Route No. 16, southeasterly edge of asphalt surface, bears N. 30° E. and S. 30° W.
40.00	The center 1/4 sec. cor. of sec. 6.
40.60	BIA Route No. 16, northwesterly edge of asphalt surface, bears N. 30° E. and S. 30° W.
43.30	Barbed wire fence, 4 strands, bears N. 30° E. and S. 30° W.
80.00	The 1/4 sec. cor. of secs. 6 and 31, on the N. bdy. of the Tp.
	<hr/> <p>From the 1/4 sec. cor. of secs. 5 and 6.</p> <p>West, along the E. and W. center line of sec. 6.</p> <p>Over rolling land.</p>
38.40	Barbed wire fence, 4 strands, bears N. 30° E. and S. 30° W.
39.80	BIA Route No. 16, southeasterly edge of asphalt surface, bears N. 30° E. and S. 30° W.
40.00	Point for the center 1/4 sec. cor. of sec. 6.
	<p>Set PK nail, with steel washer, 1 1/2 ins. diam., mkd. BLM 2018, in asphalt.</p> <p>from which</p> <p style="padding-left: 40px;">A stainless steel post, 28 ins. long, 2 1/2 ins. diam., set 27 ins. in the ground for a reference monument, bears S. 89°59' E., 106.0 ft. dist. with brass cap mkd. RM T37N R15E 106.0 FT. TO COR. C 1/4 S6 2018 with an arrow pointing to the cor. Set a steel fence post N. of the reference monument.</p> <p style="padding-left: 40px;">A stainless steel post, 28 ins. long, 2 1/2 ins. diam., set 27 ins. in the ground for a reference monument, bears S. 89°58' W., 119.0 ft. dist. with brass cap mkd. RM T37N R15E 119.0 FT. TO COR. C 1/4 S6 2018 with an arrow pointing to the cor. Set a steel fence post N. of the reference monument.</p>
40.32	BIA Route No. 16, northwesterly edge of asphalt surface, bears N. 30° E. and S. 30° W.
41.80	Barbed wire fence, 4 strands, bears N. 30° E. and S. 30° W.

Subdivision of Section 6,
T. 37 N., R. 15 E., Gila and Salt River Meridian, Arizona

CHAINS	
79.53	<p>The 1/4 sec. cor. of secs. 1 and 6, on the W. bdy. of the Tp., monumented with a stainless steel post, firmly set, projecting 1 in. above ground, with brass cap mkd. T37N R14E R15E S1 S6 2005. Add the marks 2018 to the brass cap. Set a steel fence post W. of the stainless steel post.</p> <hr/> <p style="text-align: center;">Subdivision of Section 7, T. 37 N., R. 15 E., Gila and Salt River Meridian, Arizona</p> <hr/> <p>From the 1/4 sec. cor. of secs. 7 and 18.</p> <p>N. 0°03' W., along the N. and S. center line of sec. 7.</p> <p>Over rolling land.</p>
25.20	Graded road, 12 ft. wide, bears N. 50° E. and S. 40° W.
40.00	The center 1/4 sec. cor. of sec. 7.
80.00	The 1/4 sec. cor. of secs. 6 and 7.
	<hr/> <p>From the 1/4 sec. cor. of secs. 7 and 8.</p> <p>West, along the E. and W. center line of sec. 7.</p> <p>Over rolling land.</p>
20.10	Graded road, 12 ft. wide, bears N. 50° E. and S. 40° W.
40.00	Point for the center 1/4 sec. cor. of sec. 7.
	<p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 25 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T 37 N R 15 E C 1/4 S 7</p> <p style="text-align: center;">2018</p> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p> <p>Set a steel fence post N. of the stainless steel post.</p>
79.61	<p>The 1/4 sec. cor. of secs. 7 and 12, on the W. bdy. of the Tp., monumented with a stainless steel post, firmly set, projecting 4 ins. above ground, with brass cap mkd. T37N R14E R15E 1/4 S12 S7 2005. Add the marks 2018 to the brass cap. Set a steel fence post E. of the stainless steel post.</p> <p>from which the original bearing tree</p>

Subdivision of Section 7,
T. 37 N., R. 15 E., Gila and Salt River Meridian, Arizona

CHAINS	
	A juniper, 11 ins. diam. at base of trunk, bears S. 62 1/2° W., 1.725 chs. dist., with scribe marks 1/4 S12 BT visible on partially open blaze.
	Subdivision of Section 31, T. 37 N., R. 15 E., Gila and Salt River Meridian, Arizona
	From the Standard 1/4 sec. cor. of sec. 31, on the S. bdy. of the Tp.
	N. 0°03' W., along the N. and S. center line of sec. 31.
	Over rolling land.
40.00	The center 1/4 sec. cor. of sec. 31.
43.35	Barbed wire fence, 4 strands, bears S. 45° E. and N. 45° W.
45.02	Arizona State Highway No. 98, southwesterly edge of asphalt surface, bears S. 45° E. and N. 45° W.
45.75	Arizona State Highway No. 98, northeasterly edge of asphalt surface, bears S. 45° E. and N. 45° W.
47.45	Barbed wire fence, 4 strands, bears S. 45° E. and N. 45° W.
70.20	Underground water line, bears S. 70° E. and N. 70° W.
80.00	The 1/4 sec. cor. of secs. 30 and 31.
	From the 1/4 sec. cor. of secs. 31 and 32.
	West, along the E. and W. center line of sec. 31.
	Over rolling land.
12.30	Graded road, 25 ft. wide, bears N. 20° E. and S. 20° W.
32.00	Barbed wire fence, 4 strands, bears S. 45° E. and N. 45° W.
33.81	Arizona State Highway No. 98, northeasterly edge of asphalt surface, bears S. 45° E. and N. 45° W.
34.59	Arizona State Highway No. 98, southwesterly edge of asphalt surface, bears S. 45° E. and N. 45° W.
36.40	Barbed wire fence, 4 strands, bears S. 45° E. and N. 45° W.
40.00	Point for the center 1/4 sec. cor. of sec. 31 falls in sandstone outcrop.

Subdivision of Section 31,
T. 37 N., R. 15 E., Gila and Salt River Meridian, Arizona

CHAINS	
	<p>Drill hole, 1 3/8 ins. diam., 18 ins. deep, in sandstone. Deposit a magnet, in a white plastic case, in drilled hole.</p> <p>Cement a stainless steel drive rod, 20 ins. long, 9/16 ins. diam., 14 ins. in the drilled hole, with brass cap mkd.</p> <p style="text-align: center;">T 37 N R 15 E C 1/4 S 31</p> <p style="text-align: center;">2018</p>
25.70	Wash, 40 ft. wide, 10 ft. deep, drains S. 35° E.
79.96	The 1/4 sec. cor. of secs. 31 and 36, on the W. bdy. of the Tp., monumented with a stainless steel post, firmly set, projecting 1 in. above ground, with brass cap mkd. T37N R14E R15E 1/4 S36 S31 2005. Add the marks 2018 to the brass cap. Set a steel fence post E. of the stainless steel post.
<hr/> <p>Subdivision of Section 32, T. 37 N., R. 15 E., Gila and Salt River Meridian, Arizona</p> <hr/>	
	<p>From the standard 1/4 sec. cor. of sec. 32, on the S. bdy. of the Tp.</p> <p>N. 0°03' W., along the N. and S. center line of sec. 32.</p> <p>Over rolling land.</p>
9.40	Graded road, 23 ft. wide, bears N. 25° E. and S. 25° W.
40.00	The center 1/4 sec. cor. of sec. 32.
66.30	Underground water line, bears N. 75° E. and S. 25° W.
80.00	The 1/4 sec. cor. of secs. 29 and 32.
	<p>From the 1/4 sec. cor. of secs. 32 and 33.</p> <p>West, along the E. and W. center line of sec. 32.</p> <p>Over rolling land.</p>
28.10	Graded road, 26 ft. wide, bears N. 10° E. and S. 10° W.
40.00	Point for the center 1/4 sec. cor. of sec. 32.
	<p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 25 ins. in the ground, with brass cap mkd.</p>

**Subdivision of Section 32,
T. 37 N., R. 15 E., Gila and Salt River Meridian, Arizona**

CHAINS	
	<p>T 37 N R 15 E C 1/4 S 32</p> <p>2018</p>
	Deposit a magnet, in a white plastic case, at the base of the stainless steel post.
	Set a steel fence post W. of the stainless steel post.
76.70	Underground water line, bears S. 25° E. and N. 25° W.
79.90	Trail road, 7 ft. wide, bears S. 30° E. and N. 30° W.
80.00	The 1/4 sec. cor. of secs. 31 and 32.
<hr/> <p>Subdivision of Section 36, T. 37 N., R. 15 E., Gila and Salt River Meridian, Arizona</p> <hr/>	
	From the standard 1/4 sec. cor. of sec. 36, on the S. bdy. of the Tp.
	North, along the N. and S. center line of sec. 36.
	Over rolling land.
19.75	Barbed wire fence, 4 strands, bears N. 45° E. and S. 45° W.
21.06	BIA Route No. 6320, southeasterly edge of asphalt surface, bears N. 45° E. and S. 45° W.
21.76	BIA Route No. 6320, northwesterly edge of asphalt surface, bears N. 45° E. and S. 45° W.
23.10	Barbed wire fence, 4 strands, bears N. 45° E. and S. 45° W.
39.60	Barbed wire fence, 3 strands, bears S. 55° E. and N. 55° W.
40.00	The center 1/4 sec. cor. of sec. 36.
41.80	Barbed wire fence, 3 strands, bears N. 35° E. and S. 35° W.
54.80	Underground water line, bears N. 65° E. and S. 65° W.
63.80	Underground water line, bears S. 40° E. and N. 40° W.
80.00	The 1/4 sec. cor. of secs. 25 and 36.

Subdivision of Section 36,
T. 37 N., R. 15 E., Gila and Salt River Meridian, Arizona

CHAINS	
	<p>From the 1/4 sec. cor. of secs. 1 and 36, on the E. bdy. of the Tp., monumented with a stainless steel post, 2 1/2 ins. diam., firmly set, projecting 1 in. above the ground, with brass cap mkd., T37N R15E R16E 1/4 S36 S31 1996. Brass cap encircled in collar of stone. Add the marks 2018 to the brass cap. Set a steel fence post W. of the stainless steel post.</p> <p>from which</p> <p style="padding-left: 40px;">A water valve, 9 ins. diam., firmly set in concrete 2 ft. by 2 ft., projecting 3 ins. above ground, bears S. 54 3/4° E., 1.725 chs. dist.</p> <p>West, along the E. and W. center line of sec. 36.</p> <p>Over rolling land.</p>
2.60	Underground water line, bears North and South.
21.25	Barbed wire fence, 4 strands, bears N. 45° E. and S. 45° W.
22.47	BIA Route No. 6320, southeasterly edge of asphalt surface, bears N. 45° E. and S. 45° W.
23.13	BIA Route No. 6320, northwesterly edge of asphalt surface, bears N. 45° E. and S. 45° W.
24.35	Barbed wire fence, 4 strands, bears N. 45° E. and S. 45° W.
36.70	Barbed wire fence, 3 strands, bears N. 40° E. and S. 40° W.
40.00	<p>Point for the center 1/4 sec. cor. of sec. 36.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T 37 N R 15 E C 1/4 S 36</p> <p style="text-align: center;">2018</p> <p>Set steel fence post N. of stainless steel post.</p>
40.55	Barbed wire fence, 3 strands, bears S. 55° E. and N. 55° W.
80.00	The 1/4 sec. cor. of secs. 35 and 36.

T. 37 N., R. 15 E., Gila and Salt River Meridian, Arizona

CHAINS

GENERAL DESCRIPTION

The area surveyed is located within the Navajo Nation, approximately 0.5 miles east of the community of Shonto, and approximately 7 miles north of the intersection of U.S. Highway No. 160 and Arizona State Highway No. 98. The elevation varies from about 6,100 to 6,600 feet above sea level.

Primary access to the township is provided by paved roads including Arizona State Highway No. 98 which runs through sections 31 and 32; BIA Route 16 which runs through sections 6 and 7; and BIA Route 6320 which runs through section 36. Numerous graded and trail roads allow additional access to the remainder of the township.

The terrain is predominantly rolling, with sandy soil and scattered sandstone outcroppings. A deep gorge runs northeasterly and southwesterly through sections 1, 2, 10, 11, 15, 22, 27, 28, 32, and 33 effectively dividing the township in two. Timber is characterized by piñon trees throughout most of the township and includes some juniper trees which are present mostly in the northern portion. Vegetation consists of sage brush, rabbit brush, and native grasses.

Water wells are located in sections 5 and 29. Water lines were found within sections 25, 27, 30, 31, 32, 33, 34, and 36. A high voltage transmission line and a second smaller power line run parallel to one another, bearing east and west across the entire township through sections 19, 20, 21, 22, 23, and 24. No mineral deposits or related activity were encountered during the course of this survey.

The mean magnetic declination of $10 \frac{1}{3}^{\circ}$ E. was derived from the United States Geological Survey computer program GEOMAG, utilizing the World Magnetic Model for Epoch 2015 for the dates of survey.

**UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT**

FIELD ASSISTANTS

NAMES	CAPACITY
Geoffrey A. Graham	Supervisory Land Surveyor
Blas J. Urena	Land Surveyor
Rosendo Ramos Serrano	Land Surveyor
Craig S. Dukart	Land Surveyor
Charles E. Besancon III	Surveying Technician
Mark R. Searles	Surveying Technician
Daniel R. Bryan	Engineering Technician
Daven E. Tagaban	Engineering Technician

CERTIFICATE OF SURVEY

I, Marshall S. Wixom, Cadastral Surveyor, HEREBY CERTIFY upon honor, that in pursuance of special instructions bearing date of the 17th day of January, 2018, I have surveyed the Ninth Standard Parallel North (south boundary), the north boundary, and the subdivisional lines, and subdivided certain sections, T. 37 N., R. 15 E., of the Gila and Salt River Meridian, in the State of Arizona, which are represented in the foregoing field notes as having been executed by me and under my direction. Said survey has been made in strict conformity with said special instructions, the Manual of Surveying Instructions (2009), and in the specific manner described in the foregoing field notes.

10/29/2018

(Date)

Marshall S. Wixom

(Cadastral Surveyor)

CERTIFICATE OF APPROVAL

BUREAU OF LAND MANAGEMENT
Phoenix, Arizona

The foregoing field notes of the survey of the Ninth Standard Parallel North (south boundary), the north boundary, and the subdivisional lines, and the subdivision of certain sections, T. 37 N., R. 15 E., Gila and Salt River Meridian, in the State of Arizona, executed by Marshall S. Wixom, Cadastral Surveyor, having been critically examined and found correct, are hereby approved.

11/8/2018

(Date)

[Signature]
(Chief Cadastral Surveyor of Arizona)

~~CERTIFICATE OF TRANSCRIPT~~

~~I CERTIFY That the foregoing transcript of the field notes of the above described surveys in T. 37 N., R. 15 E., Gila and Salt River Meridian, Arizona, is a true copy of the original field notes.~~

~~_____~~
(Date)

~~_____~~
(Chief Cadastral Surveyor of Arizona)