

ORIGINAL

**UNITED STATES  
DEPARTMENT OF THE INTERIOR  
BUREAU OF LAND MANAGEMENT**

FIELD NOTES

OF THE DEPENDENT RESURVEY OF  
A PORTION OF THE EAST BOUNDARY, PORTIONS OF THE SUBDIVISIONAL LINES,  
PORTIONS OF MINERAL SURVEY NUMBERS 4352, 4360, 4417A, 4417B, 4448, 4449,

AND

THE SUBDIVISION OF SECTIONS 11, 12, 13, 14, AND 24,

TOWNSHIP 11 NORTH, RANGE 14 EAST,

OF THE GILA AND SALT RIVER MERIDIAN,

IN THE STATE OF ARIZONA.

**EXECUTED BY**

**Gordon R. Bubel, Cadastral Surveyor**

Under Special Instructions dated July 5, 2018, approved July 6, 2018, which provided for the surveys included under Group No. 1188, and assignment instructions dated July 6, 2018.

**Survey commenced July 12, 2018**

**Survey completed November 15, 2018**

## INDEX DIAGRAM

TOWNSHIP 11 NORTH                      RANGE 14 EAST  
GILA & SALT RIVER MERIDIAN, ARIZONA

6	5	4	3	2	1
7	8	9	10	11 11	12 10 10
18	17	16	15	14	9    13    6 8
19	20	21	22	23	24    5
30	29	28	27	26	25
31	32	33	34	35	36

Subdivision of Section 11 ..... Pages 12-14  
 Subdivision of Section 12 ..... Pages 14-15  
 Subdivision of Section 13 ..... Pages 15-16  
 Subdivision of Section 14 ..... Pages 16-19  
 Subdivision of Section 24 ..... Pages 19-20  
 Dep. Resurvey, Por. M.S.4417B ..... Pages 20-25  
 Dep. Resurvey, Por. M.S.4360 ..... Pages 25-28, Pages 61-67  
 Dep. Resurvey, Por. M.S.4352 ..... Pages 28-30, Pages 46-60  
 Dep. Resurvey, Por. M.S.4417A ..... Pages 30-46  
 Dep. Resurvey, Por. M.S.4449 ..... Pages 60-61  
 Dep. Resurvey, Por. M.S.4448 ..... Pages 67-68

## T. 11 N., R. 14 E., Gila and Salt River Meridian, Arizona

## CHAINS

The following field notes describe the dependent resurvey of a portion of the east boundary, portions of the subdivisional lines, portions of Mineral Survey numbers 4352, 4360, 4417A, 4417B, 4448, 4449, and the subdivision of sections 11, 12, 13, 14, and 24, Township 11 North, Range 14 East, Gila and Salt River Meridian, Arizona.

**History:**

Horace M. Muscott and Claude F. Warner, surveyed the east boundary in 1937. Horace M. Muscott, John Boggs, Claude F. Warner and Thornton Fitzhugh surveyed the subdivisional lines in 1937.

**Patented Mineral Surveys:**

Richard L. Merritt surveyed: Mineral Survey numbers 4352 and 4360 in 1951, Mineral Survey numbers 4417A and 4417B in 1956, and Mineral Survey numbers 4448 and 4449, in 1958.

**Unpatented Mineral Surveys:**

Portions of the following unpatented mineral surveys have a common boundary with the above stated patented mineral surveys. The areas occupied by these surveys are within the Apache Sitgreaves National Forest. Mineral Survey number 4462 was surveyed by Richard L. Merritt in 1958. Mineral Survey number 4497 was surveyed by Harvey W. Smith in 1959.

**Platted Subdivisions**, within Mineral Survey numbers 4352, 4360, 4417A, 4448 and 4449:

Subdivision Title	Recording Date	Filed in Coconino County Recorder @
Forest Lakes Estates Unit Three	Aug. 20, 1964	Case 2, Map 52 & Map 52A
Forest Lakes Estates Unit Four	May 3, 1965	Case 2, Map 65 & Map 65A
Forest Lakes Estates Unit Five	Sept. 2, 1965	Case 2, Map 72
Forest Lakes Estates Unit Six	June 30, 1966	Case 2, Map 101
Forest Lakes Estates Unit Seven	Sept. 19, 1966	Case 2, Map 104
Forest Lakes Estates Unit Eight	July 14, 1967	Case 2, Map 127

## T. 11 N., R. 14 E., Gila and Salt River Meridian, Arizona

CHAINS		
Forest Lakes Estates Unit Nine	Nov. 6, 1967	Case 2, Map 138
Forest Lake Estates Unit Ten	June 3, 1968	Case 2, Map 157
Forest Lakes	Aug. 5, 1968	Case 2, Map 162
Forest Lakes Estates Unit Eleven	June 2, 1969	Case 2, Map 198
<b>Arizona Department of Transportation</b>		
Right of Way Map No. D-3-T-566		
<p>The survey was executed in accordance with the specifications as set forth in the <u>Manual of Instructions for the Survey of the Public Lands of the United States, 2009</u>, and the <u>Special Instructions</u> dated July 5, 2018, for Group Number 1188, Arizona.</p>		
<p>The true meridian direction and length of all lines were determined by real time kinematic global positioning system observations using Trimble Navigation R8 model receivers.</p>		
<p>Preliminary to the resurvey, the lines of the prior surveys were retraced and search was made for all corners and other calls of record. Identified corners were remonumented in their original positions. Lost corners were reestablished and remonumented at proportionate positions based on the official record. The retracement data were thoroughly verified and only the true line field notes are given herein.</p>		
<p>The original mineral surveys herein cited, measured to the face of the bearing trees and bearings were returned to the nearest minute and the distances to 0.01 ft. This resurvey measures to the bearing tree center based upon the record diameter, reporting bearings to 1/4°, and distances to a 1/2 lk.</p>		
<p>The United States Forest Service (hereinafter USFS), signs Nos. 54-2, 54-4 and 54-9, cited in this document, are sheet metal, 7 ins. x 9 ins. Sign 54-2, is labeled "PROPERTY BOUNDARY National Forest land behind this sign". Sign 54-4, is labeled "ATTENTION To willfully destroy, deface, change, or remove any Government Survey Corner or Monument, or to willfully cut down any Witness Tree or Blazed Tree marking the line of a Government Survey, is punishable by a Fine of \$250.00 or Six Months Imprisonment or both." Sign 54-9, is labeled "LAND SURVEY MONUMENT Please Do not disturb."</p>		
<p>Geodetic control was derived from Global Positioning System (GPS) static observations post processed by National Geodetic Survey, Online Positioning User Service (OPUS), utilizing Continuously Operating Reference Stations (CORS) DH4513 P015 DUECECLUBSAZ2005</p>		

## T. 11 N., R. 14 E., Gila and Salt River Meridian, Arizona

CHAINS

CORS ARP, DN4496 AZUP USERY MOUNTAIN PK CORS ARP, and DF5763 AZGB GILA COUNTY CORS ARP. The NAD 83 (2011) (EPOCH: 2010), horizontal position of the 1/4 section corner of sections 19 and 24, on the east boundary of the township is as follows:

Latitude: 34°19'27.557" N.                      Longitude: 110°47'35.457" W.

The NAD 83 (2011) (EPOCH: 2010), horizontal position of the 1/4 section corner of sections 10 and 11 is as follows:

Latitude: 34°21'11.842" N.                      Longitude: 110°49'41.350" W.

The mean magnetic declination is 10° E.

---

**Dependent Resurvey of a Portion of the East Boundary,  
T. 11 N., R. 14 E., Gila and Salt River Meridian, Arizona**

---

Restoring the survey executed  
by Horace M. Muscott, et. al. in 1937.

---

Beginning at the 1/4 sec. cor. of secs. 19 and 24, on the E. bdy. of the Tp., determined at the center of the original supporting mound of stone, 5 ft. diam., 1 ft. high.

from which a bearing tree, established by the Apache-Sitgreaves National Forest (hereinafter abbreviated ASNF), in 1968.

A pine, 24 ins. diam., bears S. 12° E., 1.415 chs. dist., with a healed blaze.

At the corner point

Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 16 ins. in the ground, in the original mound of stone, 5 ft. base, to top, with brass cap mkd.

T 11 N  
R 14 E R 15 E  
1/4  
S 24 | S 19

2018

Deposit a magnet, in a white plastic case, at the base of the stainless steel post.

North, bet. secs. 19 and 24, within the ASNF.

Over gently rolling land, through pine timber.

Dependent Resurvey of a Portion of the East Boundary,  
T. 11 N., R. 14 E., Gila and Salt River Meridian, Arizona

CHAINS	
24.85	ASNF road No. 260B, graded, 15 ft. wide, bears S. 35° E. and N. 35° W.
34.65	Intersect the southerly right-of-way of Arizona State Highway No. 260, on the arc of a circular curve to the right, having a central angle of 6°28', a radius of 14900.0 ft.
	From this point, the point of tangency, at sta. 1728+21.72 (Back), 100 ft. right, 1728+22.00 (Ahead), 100 ft. right, bears S. 88°52' E., 32.60 chs. dist., monumented with a rebar, 5/8 in. diam., as shown on ADOT highway plan project 2-309-602, firmly set projecting 1 in. above ground.
	From this same point, the point of curvature, at sta. 1689+73.27, 100 ft. right, bears S. 83°26' W., 25.28 chs. dist., monumented with a rebar, 5/8 in. diam., as shown on ADOT highway plan project 2-309-602, projecting 1 in. above ground.
	Continuing measurement, across Arizona State Highway No. 260.
37.69	Intersect the northerly right-of-way of Arizona State Highway No. 260, on the arc of a circular curve to the right, having a central angle of 6°28', a radius of 15100.0 ft.
	From this point, the point of tangency, at sta. 1728+21.72 (Back), 100 ft. left, 1728+22.00 (Ahead), 100 ft. left, bears S. 88°58' E., 32.85 chs. dist., monumented with a rebar, 5/8 in. diam., as shown on ADOT highway plan project 2-309-602, projecting 1 in. above ground.
	From this same point, the calculated point of curvature, at sta. 1689+73.27, 100 ft. left, bears S. 83°27' W., 25.81 chs. dist.
38.16	Intersect line 4-1, Little Pine # 3 lode, M.S. No. 4448, hereinafter described.
	Continuing measurement across patented lands.
39.92	The cor. of secs. 13, 18, 19 and 24, monumented with an iron post, 2 ins. diam., firmly set, projecting 2 ins. above ground, encircled with a collar of stone, with brass cap mkd. T11N R14E R15E S13 S18 S24 S19 1937.
	from which the remaining original bearing trees
	A rotting pine stump, 14 ins. diam., 14 ins. high, bears S. 26 3/4° W., 1.28 chs. dist., with scribe marks 24 BT visible on an open blaze.
	A pine, 23 ins. diam., bears N. 37° W., 1.10 chs. dist., with a healed blaze.

Dependent Resurvey of a Portion of the East Boundary,  
T. 11 N., R. 14 E., Gila and Salt River Meridian, Arizona

CHAINS	
39.97	<p>Add the marks 2018 to the brass cap.</p> <hr/> <p>N. 0°03' E., bet. secs. 13 and 18.</p> <p>Across patented land, through pine timber.</p> <p>The 1/4 sec. cor. of secs. 13 and 18, monumented with an iron post, 1 in. diam., firmly set, projecting 7 ins. above ground, with brass cap mkd. 1/4 S13 S18 1937.</p> <p>from which</p> <p style="padding-left: 40px;">A pine, 27 ins. diam., bears N. 30° E., 38 lks. dist., with a healed blaze.</p> <p style="padding-left: 40px;">A pine, 24 ins. diam., bears S. 23 3/4° W., 1.21 chs. dist., with a healed blaze.</p> <p>Add the marks 2018 to the brass cap.</p> <hr/>
23.28	<p>N. 0°01' E., beginning new measurement.</p> <p>Across patented land, through pine timber.</p> <p>Intersect line 3-4, Hillcrest No. 4 lode, M.S. No. 4360.</p> <p>From this point, cor. 4, Hillcrest No. 4 lode, bears S. 30°21' E., 13.61 chs. dist., hereinafter described.</p> <p>From this same point, cor. 3, Hillcrest No. 4 lode, bears N. 30°21' W., 9.10 chs. dist., hereinafter described.</p> <p>Continuing measurement across ASNF.</p>
36.60	<p>ASNF road no. 99, graded, 25 ft. wide, bears S. 12° E. and N. 12° W.</p>
40.02	<p>The cor. of secs. 7, 12, 13 and 18, monumented with an iron post, 2 ins. diam., firmly set, projecting 8 ins. above ground, in a mound of stone, 2 1/2 ft. base, to top, with brass cap mkd. T11N R14E R15E S12 S7 S13 S18 1937.</p> <p>from which the remaining original bearing trees</p> <p style="padding-left: 40px;">A pine, 17 ins. diam., bears N. 20 1/4° E., 17 lks. dist., with a healed blaze. (Record: 18 lks.)</p> <p style="padding-left: 40px;">A pine, 28 ins. diam., bears S. 14 1/4° W., 54 lks. dist., with a healed blaze.</p>

Dependent Resurvey of a Portion of the East Boundary,  
T. 11 N., R. 14 E., Gila and Salt River Meridian, Arizona

CHAINS	
	<p>A pine, 28 ins. diam., bears N. 30° W., 25 lks. dist., with a healed blaze.</p> <p>Add the marks 2018 to the brass cap.</p>
	<hr/> <p>Dependent Resurvey of a Portion of the Subdivisional Lines, T. 11 N., R. 14 E., Gila and Salt River Meridian, Arizona</p> <hr/>
	<p>Restoring the survey executed by Horace M. Muscott, et. al. in 1937.</p> <hr/>
5.08	<p>From the corner of secs. 13, 18, 19 and 24, on the E. bdy. of the Tp., hereinbefore described.</p> <p>N. 89°59' W., bet. secs. 13 and 24.</p> <p>Over rolling land, through pine timber, across patented lands.</p> <p>Intersect line 1-2, Little Pine # 3 lode, M.S. No. 4448.</p>
	<p>From this point, cor. 1, Little Pine # 3 lode, bears S. 30°23' E., 4.09 chs. dist., hereinafter described.</p> <p>From this same point, cor. 3, Hillcrest No. 9 lode, M.S. No. 4360, bears N. 30°23' W., 6.96 chs. dist., hereinafter described.</p> <p>Continuing measurement across ASNF.</p>
10.37	<p>Intersect line 1-4, Hillcrest No. 11 lode, M.S. No. 4360.</p> <p>From this point, Arizona State Highway No. 260, point on curve, sta. 1700+95.86, at the intersection of the northerly right-of-way with line 1-4, Hillcrest No. 11 lode, bears S. 30°26' E., 3.41 chs. dist., hereinafter described.</p> <p>From this same point cor. No. 4, Hillcrest No. 11 lode, bears N. 30°26' W., 4.29 chs. dist., hereinafter described.</p> <p>Continuing measurement across patented lands.</p>
40.10	<p>The 1/4 sec. cor. of secs. 13 and 24, monumented with an iron post, 1 in. diam., firmly set, bent over 12 ins. to the SW. Brass cap is mkd. 1/4 S13 S24 1937. Observed at base of bend.</p> <p>Add the marks 2018 to the brass cap.</p> <hr/> <p>N. 89°58' W., beginning new measurement.</p> <p>Over rolling land, through pine timber, across patented lands.</p>



Dependent Resurvey of a Portion of the Subdivisional Lines,  
T. 11 N., R. 14 E., Gila and Salt River Meridian, Arizona

CHAINS	
17.69	<p>Intersect line 2-3, Little Pine # 5 lode, M.S. No. 4449.</p> <p>From this point, cor. 3, Little Pine # 5 lode, identical with cor. 4, Campbell and Denison No. 7 lode, identical with cor. 4, Campbell and Denison No. 8 lode, both of M.S. No. 4352, bears N. 30°21' W., 12.15 chs. dist., hereinafter described.</p> <p>From this same point, cor. 2, Little Pine # 5 lode, identical with cor. 4, Campbell and Denison No. 7 lode, identical with cor. 4, Campbell and Denison No. 8 lode, both of M.S. No. 4352, bears S. 30°21' E., 22.74 chs. dist., hereinafter described.</p> <p>Continuing measurement across ASNF.</p>
40.06	<p>The cor. of secs. 13, 14, 23 and 24, monumented with an iron post, 2 ins. diam., firmly set, projecting 8 ins. above ground, in a mound of stone, 3 1/2 ft. base, to top, with brass cap mkd. T11N R14E S14 S13 S24 S23 1937.</p> <p>from which the remaining original bearing tree</p> <p style="padding-left: 40px;">A pine, 17 ins. diam., bears N. 36 1/4° W., 1.20 chs. dist., with a healed blaze.</p> <p>Add the marks 2018 to the brass cap.</p> <hr/>
	<p>N. 0°01' E., bet. secs. 13 and 14.</p> <p>Over rolling land, through pine timber, across ASNF.</p>
2.17	<p>Intersect line 1-2, Campbell and Denison No. 9 lode, M.S. No. 4352.</p> <p>From this point, cor. 1, Campbell and Denison No. 9 lode, bears S. 30°19' E., 1.02 chs. dist., hereinafter described.</p> <p>From this same point, cor. 2, Campbell and Denison No. 9 lode, identical with cor. 2, Campbell and Denison No. 9 ext. lode, identical with cor. 1, Campbell and Denison No. 10 lode, all of M.S. No. 4352, bears N. 30°19' W., 21.72 chs. dist., hereinafter described.</p> <p>Continuing measurement across patented lands.</p>
39.99	<p>Point for the 1/4 sec. cor. of secs. 13 and 14, at proportionate dist., there is no remaining evidence of the orig. cor.</p> <p>Not monumented.</p>
79.97	<p>The cor. of secs. 11, 12, 13 and 14, monumented with an iron post, 2 ins. diam., firmly set, projecting 21 ins. above ground, with brass cap mkd. T11N R14E S11 S12 S13 S14 1937.</p>

Dependent Resurvey of a Portion of the Subdivisional Lines,  
T. 11 N., R. 14 E., Gila and Salt River Meridian, Arizona

CHAINS	
	<p>from which the remaining original bearing tree</p> <p style="padding-left: 40px;">A pine, 22 ins. diam., bears N. 32 1/2° W., 91 lks. dist., with a healed blaze.</p> <p>Add the marks 2018 to the brass cap.</p> <hr/>
	<p>From the 1/4 sec. cor. of secs. 12 and 13, monumented with an iron post, 1 in. diam., firmly set, projecting 3 ins. above ground, encircled with a collar of stone, with brass cap mkd. 1/4 S12 S13 1937.</p> <p>from which the remains of an original bearing tree</p> <p style="padding-left: 40px;">A pine stump, 16 ins. diam., 5 ins. high, bears N. 21 1/2° E., 43 lks. dist., no marks visible.</p> <p>Add the marks T11N R14E 2018 to the brass cap.</p> <p>S. 89°59' W., bet. secs. 12 and 13.</p> <p>Over rolling land, through burnt pine timber, within ASNF.</p>
17.15	<p>Intersect line 2-3, The Boss' # 4 lode, M.S. No. 4417A.</p> <p>From this point, cor. 3, The Boss' # 4 lode, bears S. 30°17' E., 11.09 chs. dist., hereinafter described.</p> <p>From this same point, cor. 2, The Boss' # 4 lode, bears N. 30°17' W., 11.64 chs. dist., hereinafter described.</p> <p>Continuing measurement across patented lands.</p>
40.10	<p>The cor. of secs. 11, 12, 13 and 14.</p> <hr/> <p>N. 0°02' E., bet. secs. 11 and 12.</p> <p>Over rolling land, through pine timber, across patented lands.</p>
21.23	<p>Intersect line 3-4, Miss Lottie # 2 lode, M.S. No. 4417A.</p> <p>From this point, cor. 4, Miss Lottie # 2 lode, identical with cor. 1, The Boss' # 4 lode, M.S. 4417A, identical with cor. 2, Campbell and Denison No. 15 lode, M.S. No. 4352, bears S. 30°18' E., 18.27 chs. dist., hereinafter described.</p> <p>From this same point, cor. 3, Miss Lottie # 2 lode, identical with cor. 2, Miss Lottie #3 lode, M.S. 4417A, bears N. 30°18' W., 4.47 chs. dist., hereinafter described.</p> <p>Continuing measurement across ASNF.</p>

Dependent Resurvey of a Portion of the Subdivisional Lines,  
T. 11 N., R. 14 E., Gila and Salt River Meridian, Arizona

CHAINS	
32.35	USFS road 99Z, graded, 25 ft. wide, bears N. 50° E. and S. 50° W.
39.97	<p>The 1/4 sec. cor. of secs. 11 and 12, monumented with an iron post, 1 in. diam., firmly set, projecting 4 ins. above ground, witnessed by a mound of stone, 3 ft. base, 1 1/2 ft. high, alongside and to the N. Brass cap is mkd. 1/4 S11 S12 1937.</p> <p>from which the remaining original bearing tree</p> <p style="padding-left: 40px;">A burnt pine, 18 ins. diam., bears N. 50 1/2° E., 51 lks. dist., with a healed blaze.</p> <p>Add the marks T11N R14E 2018 to the brass cap.</p> <hr/> <p>From the 1/4 sec. cor. of secs. 11 and 14, monumented with an iron post, 1 in. diam., firmly set, projecting 4 ins. above ground, with brass cap mkd. 1/4 S11 S14 1937.</p> <p>from which the remains of an original bearing tree</p> <p style="padding-left: 40px;">A pine stump, 26 ins. diam., 6 ins. high, bears S. 22 3/4° E., 1.65 chs. dist., no marks visible.</p> <p>Add the marks T11N R14E 2018 to the brass cap.</p> <p>S. 89°56' W., bet. secs. 11 and 14.</p> <p>Through pine timber, across patented land.</p>
5.50	<p>Intersect line 1-2, D&amp;W # 6 lode, M.S. No. 4417A.</p> <p>From this point, cor. 2, D&amp;W # 6 lode, bears N. 59°45' E., 22.68 chs. dist., hereinafter described.</p> <p>From this same point, cor. 1, D&amp;W # 6 lode, bears S. 59°45' W., 0.045 chs. dist., hereinafter described.</p> <p>Continuing measurement across ASNF.</p>
5.555	<p>Intersect line 1-2, Hillcrest Mill Site # 1, M.S. No. 4417B.</p> <p>From this point, cor. 1, Hillcrest Mill Site # 1, bears N. 59°45' E., 0.004 chs. dist., hereinafter described.</p> <p>From this same point, a lot cor. on line 1-2, Hillcrest Mill Site # 1, bears S. 59°45' W., 4.805 chs. dist., hereinafter described.</p> <p>Continuing measurement across patented lands.</p>
16.51	Intersect line 3-4, The Boss' Mill Site # 1, M.S. No. 4417B.

Dependent Resurvey of a Portion of the Subdivisional Lines,  
T. 11 N., R. 14 E., Gila and Salt River Meridian, Arizona

CHAINS							
	<p>From this point, cor. 4, The Boss' Mill Site # 1, identical with cor. 3, Hillcrest Mill Site # 1, bears N. 59°41' E., 0.38 chs. dist., hereinafter described.</p> <p>From this same point, cor. 3, The Boss' Mill Site # 1, bears S. 59°41' W., 8.73 chs. dist., hereinafter described.</p> <p>Continuing measurement across ASNF.</p>						
39.94	<p>The cor. of secs. 10, 11, 14 and 15, monumented with an iron post, 2 ins. diam., firmly set, bent over 16 ins. to the E., with brass cap mkd. T11N R14E S10 S11 S14 S15 1937.</p> <p>from which the remaining original bearing tree</p> <p style="padding-left: 40px;">A pine, 28 ins. diam., bears N. 16 3/4° W., 89 lks. dist., no marks visible on an opened blaze.</p> <p>At the corner point</p> <p>Excavate the bent pipe, and replace with a stainless steel post, 28 ins. long, 2 1/2 ins. diam., set 22 ins. in the ground, in a collar of stone, with brass cap mkd.</p> <div style="text-align: center;"> <table border="0"> <tr> <td>T 11 N</td> <td>R 14 E</td> </tr> <tr> <td>S 10</td> <td>S 11</td> </tr> <tr> <td>S 15</td> <td>S 14</td> </tr> </table> <p>2018</p> </div> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post, and bury the bent pipe alongside.</p>	T 11 N	R 14 E	S 10	S 11	S 15	S 14
T 11 N	R 14 E						
S 10	S 11						
S 15	S 14						
3.20	<hr/> <p style="text-align: center;"><b>Subdivision of Section 11, T. 11 N., R. 14 E., Gila and Salt River Meridian, Arizona</b></p> <hr/> <p>From the 1/4 sec. cor. of secs. 11 and 14, hereinbefore described.</p> <p>N. 0°02' W., on the N. and S. center line of sec. 11</p> <p>Over rolling land, through pine timber, across patented land.</p> <p>Intersect line 1-2, D&amp;W # 6 lode, M.S. No. 4417A.</p> <p>From this point, cor. 2, D&amp;W # 6 lode, bears N. 59°45' E., 16.32 chs. dist., hereinafter described.</p> <p>From this same point, cor. 1, D&amp;W # 6 lode, bears S. 59°45' W., 6.41 chs. dist., hereinafter described.</p> <p>Continuing measurement across ASNF.</p>						

Subdivision of Section 11,  
T. 11 N., R. 14 E., Gila and Salt River Meridian, Arizona

CHAINS	
40.01	<p>Point for the center 1/4 sec. cor. of sec. 11, at intersection with E. and W. center line of sec. 11.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 19 ins. in the ground, in a mound of stone, 2 1/2 ft. base, to top, with brass cap mkd.</p> <p style="text-align: center;">T 11 N R 14 E C 1/4 S 11</p> <p style="text-align: center;">2018</p> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p>
67.90	<p>USFS road no. 99A, graded, 15 ft. wide, bears N. 85° E. and S. 85° W.</p>
80.01	<p>The 1/4 sec. cor. of secs. 2 and 11, monumented with an iron post, 1 in. diam., firmly set, projecting 8 ins. above ground, in a mound of stone, 3 ft. base, to top, with brass cap mkd. 1/4 S2 S11 1937.</p> <p>from which</p> <p style="padding-left: 40px;">A pine, 24 ins. diam., bears N. 21 1/2° E., 78 lks. dist., with a healed blaze.</p> <p style="padding-left: 40px;">A rotted pine stump, 24 ins. diam., 6 ins. high, bears S. 73 3/4° E., 58 lks. dist.</p> <p>Add the marks T11N R14E 2018 to the brass cap.</p> <hr/> <p>From the 1/4 sec. cor. of secs. 11 and 12, hereinbefore described. S. 89°56' W., on the E. and W. center line of sec. 11.</p> <p>Through pine timber, within the ASNF.</p>
10.94	<p>Intersect line 1-2, Miss Lottie # 3 lode, M.S. No. 4417A.</p> <p>From this point, cor. 2, Miss Lottie # 3 lode, identical with cor. 3, Miss Lottie # 2 lode, M.S. 4417A, bears S. 30°16' E., 17.21 chs. dist., hereinafter described.</p> <p>From this same point, cor. 1, Miss Lottie # 3 lode, bears N. 30°16' W., 5.54 chs. dist., hereinafter described. Continuing measurement across patented lands.</p>
21.47	<p>Intersect line 3-4, Miss Lottie # 3 lode, M.S. No. 4417A.</p>

**Subdivision of Section 11,  
T. 11 N., R. 14 E., Gila and Salt River Meridian, Arizona**

CHAINS	
	<p>From this point, cor. 4, Miss Lottie # 1 lode, M.S. 4417A, on line 3-4, Miss Lottie # 3 lode, bears S. 30°15' E., 13.40 chs. dist., hereinafter described.</p> <p>From this same point, cor. 4, Miss Lottie # 3 lode, bears N. 30°15' W., 0.24 chs. dist., hereinafter described.</p> <p>Continuing measurement across ASNF.</p>
39.94	The center 1/4 sec. cor. of sec. 11.
79.90	<p>The 1/4 sec. cor. of secs. 10 and 11, monumented with an iron post, 1 in. diam., firmly set, projecting 12 ins. above ground, with brass cap mkd. 1/4 S10 S11 1937.</p> <p>from which</p> <p style="padding-left: 40px;">A root hole, 24 ins. diam., 6 ins. deep, bears S. 87 3/4° E., 13 lks. dist.</p> <p style="padding-left: 40px;">A burnt pine, 33 ins. diam., bears S. 51 1/4° W., 9 lks. dist., with a healed blaze.</p> <p>Add the marks T11N R14E 2018 to the brass cap.</p> <p>Raise a mound of stone, 2 1/2 ft. base, to top, around the iron post.</p>
<hr/> <p><b>Subdivision of Section 12, T. 11 N., R. 14 E., Gila and Salt River Meridian, Arizona</b></p> <hr/>	
	<p>From the 1/4 sec. cor. of secs. 12 and 13, hereinbefore described.</p> <p>N. 0°01' E., on the N. and S. center line of sec. 12.</p> <p>Over heavily rolling land, through pine timber, within the ASNF.</p>
15.25	ASNF road no. 99A, graded, 25 ft. wide, bears S. 80° E. and N. 80° W.
39.94	<p>Point for the center 1/4 sec. cor. of sec. 12, at intersection with E. and W. center line of sec. 12.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 20 ins. in the ground, in a mound of stone, 2 1/2 ft. base, to top, with brass cap mkd.</p>
<p>T 11 N R 14 E C 1/4 S 12</p> <p>2018</p>	

**Subdivision of Section 12,  
T. 11 N., R. 14 E., Gila and Salt River Meridian, Arizona**

CHAINS	
	Deposit a magnet, in a white plastic case, at the base of the stainless steel post.
79.93	<p>The 1/4 sec. cor. of secs. 1 and 12, monumented with an iron post, 1 in. diam., firmly set, projecting 8 ins. above ground, in a mound of stone, 3 1/2 ft. base, to top, with brass cap mkd. 1/4 S1 S12 1937.</p> <p>from which the remains of an original bearing tree</p> <p style="padding-left: 40px;">A rotted pine stump, 30 ins. diam., 6 ins. high, bears S. 50 1/2° E., 1.12 chs. dist.</p> <p>Add the marks T11N R14E 2018 to the brass cap.</p> <hr/> <p>From the 1/4 of secs. 7 and 12, on the E. bdy. of the Tp., monumented with an iron post, 1 in. diam., firmly set, projecting 18 ins. above ground, in a mound of stone, 4 1/2 ft. base, to top. Brass cap is marked 1/4 S12 S7 1937.</p> <p>from which a bearing tree established by the USFS in 1988</p> <p style="padding-left: 40px;">A pine, 17 ins. diam., bears N. 62° E., 91 lks. dist., mkd. 1/4 S7 BT, on a partially healed blaze.</p> <p>Add the marks T11N R14E R15E 2018 to the brass cap.</p> <p>N. 89°59' W., on the E. and W. center line of sec. 12.</p> <p>Over heavily rolling land, through pine timber, within the ASNF.</p>
40.07	The center 1/4 sec. cor. of sec. 12.
67.75	USFS road 99, graded, 25 ft. wide, bears N. 5° E. and S. 5° W.
72.65	USFS road 99Z, graded, 20 ft. wide, bears N. 50° E. and S. 50° W.
80.16	The 1/4 sec. cor. of secs. 11 and 12, hereinbefore described.
	<p><b>Subdivision of Section 13, T. 11 N., R. 14 E., Gila and Salt River Meridian, Arizona</b></p> <hr/>
	<p>From the 1/4 sec. cor. of secs. 13 and 24, hereinbefore described.</p> <p>N. 0°04' E., on the N. and S. center line of sec. 13.</p> <p>Over rolling land, through pine timber, across patented land.</p>
39.99	Point for the center 1/4 sec. cor. of sec. 13, at intersection with E. and W. center line of sec. 13.

**Subdivision of Section 13,  
T. 11 N., R. 14 E., Gila and Salt River Meridian, Arizona**

CHAINS	
	Not monumented.
59.71	Intersect line 1-2, The Boss' # 2 lode, M.S. No. 4417A.  From this point, cor. 3, Campbell and Denison No. 2 lode, M.S. 4352, on line 1-2, The Boss' # 2 lode, bears S. 30°21' E., 5.07 chs. dist., hereinafter described.  From this same point, cor. 1, The Boss' # 2 lode, bears N. 30°21' W., 15.07 chs. dist., hereinafter described.  Continuing measurement across ASNF.
80.01	The 1/4 sec. cor. of secs. 12 and 13, hereinbefore described. <hr/> From the 1/4 sec. cor. of secs. 13 and 18, on the E. bdy. of the Tp., hereinbefore described.  N. 89°58' W., on the E. and W. center line of sec. 13.  Over rolling land, through pine timber, across patented land.
40.09	The point for the center 1/4 sec. cor. of sec. 13.
80.17	The point for the 1/4 sec. cor. of secs. 13 and 14, hereinbefore described. <hr/> <p style="text-align: center;"><b>Subdivision of Section 14, T. 11 N., R. 14 E., Gila and Salt River Meridian, Arizona</b></p> <hr/> From the 1/4 sec. cor. of secs. 14 and 23, located at the center of the original supporting mound of stone, 5 1/2 ft. base, 2 ft. high.  from which the remaining orig. bearing tree.  A pine, 24 ins. diam., bears S. 64 3/4° W., 84 lks. dist., no marks visible, on an opened blaze.  At the corner point,  Atop bedrock, within the supporting mound of stone. Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., seated in 10 lbs. of concrete, anchored in a 1 gallon plastic bucket. Brass cap is mkd.



Subdivision of Section 14,  
T. 11 N., R. 14 E., Gila and Salt River Meridian, Arizona

CHAINS	
	T 11 N R 14 E S 14 1/4 ——— S 23  2018
	from which
	A pine, 16 ins. diam., bears N. 15° E., with a 60d spike, driven into the W. side, 38.5 lks. dist.
	Deposit a magnet, in a white plastic case, chiseled into bedrock, at the base of the stainless steel post.
	N. 0°01' E., on the N. and S. center line of sec. 14.
	Over gently rolling land, through pine timber, within the ASNF.
8.95	Old rim road, graded 30 ft. wide, bears N. 75° E. and S. 75° W.
9.10	Power line, bears N. 75° E. and S. 75° W.
16.41	Intersect line 1-2, Campbell and Denison No. 12 lode, M.S. No. 4352.
	From this point, cor. 1, Campbell and Denison No. 12 lode, bears S. 30°21' E., 4.57 chs. dist., hereinafter described.
	From this same point, cor. 2, Campbell and Denison No. 12 lode, bears N. 30°21' W., 18.18 chs. dist., hereinafter described.
	Continuing measurement across patented lands.
37.47	Intersect line 2-3, Campbell and Denison No. 11 lode, M.S. No. 4352.
	From this point, cor. 3, Campbell and Denison No. 11 lode, bears N. 59°41' E., 7.55 chs. dist., hereinafter described.
	From this same point, cor. 2, Campbell and Denison No. 11 lode, identical with cor. cor. 3, Campbell and Denison No. 12 lode bears S. 59°41' W., 1.55 chs. dist., hereinafter described.
	Continuing measurement across ASNF.
40.01	Point for the center 1/4 sec. cor. of sec. 14, at intersection with E. and W. center line of sec. 14.
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 22 ins. in the ground, in a mound of stone, 2 ft. base, to top, with brass cap mkd.

Subdivision of Section 14,  
T. 11 N., R. 14 E., Gila and Salt River Meridian, Arizona

CHAINS	
	T 11 N R 14 E C 1/4 S 14
	2018
	Deposit a magnet, in a white plastic case, at the base of the stainless steel post.
70.49	Intersect line 4-1, D&W # 1 lode, M.S. No. 4417A.  From this point, cor. 4, D&W # 1 lode, bears S. 30°13' E., 7.22 chs. dist., hereinafter described.  From this same point, cor. 1, D&W # 1 lode, identical with cor. 4, D&W # 6 lode, M.S. No. 4417A, bears N. 30°13' W., 1.88 chs. dist., hereinafter described.  Continuing measurement across patented lands.
79.99	The 1/4 sec. cor. of secs. 11 and 14, hereinbefore described. <hr/> From the point for the 1/4 sec. cor. of secs. 13 and 14, hereinbefore described.  S. 89°53' W., on the E. and W. center line of sec. 14.  Over rolling land, through pine timber, across patented land.
23.53	Intersect line 3-4, Campbell and Denison No. 10 lode, M.S. No. 4352.  From this point, cor. 4, Campbell and Denison No. 10 lode, identical with cor. 3, Campbell and Denison Ext. No. 9 lode, M.S. No. 4352, bears N. 59°39' E., 1.22 chs. dist., hereinafter described.  From this same point, cor. 3, Campbell and Denison No. 10 lode, bears S. 59°39' W., 7.89 chs. dist., hereinafter described. Continuing measurement across ASNF.
32.65.	Intersect line 3-4, Campbell and Denison No. 11 lode, M.S. No. 4352.  From this point, cor. 3, Campbell and Denison No. 10 lode, on line 3-4, Campbell and Denison No. 11 lode, bears S. 30°16' E., 4.59 chs. dist., hereinafter described.  From this same point, cor. 3, Campbell and Denison No. 11 lode, bears N. 30°16' W., 1.46 chs. dist., hereinafter described.  Continuing measurement across patented lands.


**Subdivision of Section 14,  
T. 11 N., R. 14 E., Gila and Salt River Meridian, Arizona**

CHAINS	
35.55	<p>Intersect line 2-3, Campbell and Denison No. 11 lode, M.S. No. 4352.</p> <p>From this point, cor. 3, Campbell and Denison No. 11 lode, bears N. 59°41' E., 2.51 chs. dist., hereinafter described.</p> <p>From this same point, cor. 2, Campbell and Denison No. 11 lode, identical with cor. 3, Campbell and Denison No. 12 lode, bears S. 59°41' W., 6.59 chs. dist., hereinafter described.</p> <p>Continuing measurement across ASNF.</p>
39.90	The center 1/4 sec. cor. of sec. 14.
79.80	<p>The 1/4 sec. cor. of secs. 14 and 15, monumented with an iron post, 1 in. diam., firmly set, projecting 11 ins. above ground, in a mound of stone, 2 1/2 ft. base, to top, with brass cap mkd. 1/4 S15 S14 1937.</p> <p>from which the remaining bearing tree</p> <p style="padding-left: 40px;">A pine, 18 ins. diam., bears N. 56° E., 13 lks. dist., with a healed blaze.</p> <p>and a new bearing tree</p> <p style="padding-left: 40px;">A pine, 18 ins. diam., bears S. 88° W., with a 60d spike, driven into the S. side, 35.5 lks. dist.</p> <p>Add the marks T11N R14E 2018 to the brass cap.</p> <hr/> <p style="text-align: center;"><b>Subdivision of Section 24, T. 11 N., R. 14 E., Gila and Salt River Meridian, Arizona</b></p> <hr/> <p>From the 1/4 sec. cor. of secs. 24 and 25, monumented with an iron post, 1 in. diam., firmly set, projecting 8 ins. above ground, in a fallen mound of stone, with brass cap mkd. 1/4 S24 S25 1937.</p> <p>from which the remaining bearing tree</p> <p style="padding-left: 40px;">A spruce, 24 ins. diam., bears N. 56 1/2° W., 10 lks. dist., with a healed blaze.</p> <p>and a bearing tree established by the USFS in 1968</p> <p style="padding-left: 40px;">A pine, 14 ins. diam., bears S. 8° E., 50 lks. dist., with a healed blaze.</p> <p>Add the marks T11N R14E 2018 to the brass cap.</p>

Subdivision of Section 24,  
T. 11 N., R. 14 E., Gila and Salt River Meridian, Arizona

CHAINS	<p>Rebuild the fallen mound of stone, around the iron post, 3 ft. base, to top.</p> <p>Cor. located on E. side of canyon, 2 chs. E. of bottom, course S. 5° W.</p> <p>N. 0°02' W., on the N. and S. center line of sec. 24. Ascending out of canyon, within ASNF.</p>
40.06	<p>Point for the center 1/4 sec. cor. of sec. 24, at intersection with the E. and W. center line of sec. 24.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 20 ins. in the ground, in a mound of stone, 3 1/2 ft. base, to top, with brass cap mkd.</p> <p style="text-align: center;">T 11 N R 14 E C 1/4 S 24</p> <p style="text-align: center;">2018</p>
67.58	<p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p> <p>Intersect line 2-3, Hillcrest No. 12 lode, M.S. No. 4360.</p> <p>From this point, Arizona State Highway No. 260, point on tangent sta. 1682+48.74, at the intersection of line 2-3, Hillcrest No. 12 lode, with the southerly right-of-way, bears N. 59°39' E., 4.81 chs. dist., hereinafter described.</p> <p>From this same point, cor. 3, Hillcrest No. 12 lode, bears S. 59°39' W., 8.99 chs. dist., hereinafter described.</p> <p>Continuing measurement, over patented land, within right-of-way of Arizona State Highway No. 260.</p>
80.01	<p>The 1/4 sec. cor. of secs. 13 and 24, hereinbefore described.</p> <hr/> <p style="text-align: center;"><b>Dependent Resurvey of a Portion of Mineral Survey Number 4417B, T. 11 N., R. 14 E., Gila and Salt River Meridian, Arizona</b></p> <hr/> <p style="text-align: center;">Restoring a portion of the survey executed by Richard L. Merritt, in 1956</p> <hr/> <p>From cor. 1, Hill Crest Mill Site # 1, M.S. No. 4417B, monumented with a sandstone, 6 ins. x 9 ins., firmly set, projecting 12 ins. above ground, mkd. with an X on top, and 1HMS1 4417B on the WNW face.</p>

Dependent Resurvey of a Portion of Mineral Survey Number 4417B,  
T. 11 N., R. 14 E., Gila and Salt River Meridian, Arizona

CHAINS	
	<p>from which</p>
	<p>A pine snag, 24 ins. diam., 66 ins. high, bears N. 7 3/4° E., 29 lks. dist., with faint illegible marks.</p>
	<p>At the corner point</p>
	<p>Excavate the mkd. stone, 30 x 9 x 6 ins. and replace with a stainless steel post, 28 ins. long, 2 1/2 ins. diam., set 20 ins. in the ground, in a mound of stone, 2 1/2 ft. base, to top, with brass cap mkd.</p>
	
	<p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p>
	<p>Break the mkd. stone into pieces and incorporate within the mound of stone.</p>
	<p>From this cor., cor. 1, D&amp;W # 6 lode, M.S. No. 4417A, bears S. 26°57' E., 2.8 lks. dist., hereinafter described.</p>
	<p>S. 59°45' W., on line 1-2, Hillcrest Mill Site #1, along the ASNF boundary.</p>
0.004	<p>Intersect the line bet. secs. 11 and 14.</p>
	<p>From this point, the 1/4 sec. cor. of secs. 11 and 12, bears N. 89°56' E., 5.56 chs. dist., hereinbefore described.</p>
	<p>From this same point, the cor. of secs. 10, 11, 14 and 15, bears S. 89°56' W., 34.38 chs. dist., hereinbefore described.</p>
	<p>Continuing measurement in sec. 14.</p>
4.81	<p>A rebar, 1/2 in. diam., firmly set, projecting 2 ins. above ground, with attached brass washer, stamped RLS 21791, monumented by Michael Stoll, Arizona Registered Land Surveyor No. 21791, date unknown. Accepted as a bona fide establishment of the SW cor. of Coconino County Assessor's parcel 403-30-001L.</p>
	<p>S. 59°38' W., beginning new measurement.</p>
0.75	<p>Graded road, 20 ft. wide, bears S. 40° E. and N. 40° W.</p>


Dependent Resurvey of a Portion of Mineral Survey Number 4417B,  
T. 11 N., R. 14 E., Gila and Salt River Meridian, Arizona

CHAINS

4.28

Point for cor. 2, Hill Crest Mill Site #1, identical to cor. 1, The Boss' # 1 Mill Site, M.S. No. 4417B, at proportionate dist., there is no remaining evidence of the orig. cor.

Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 22 ins. in the ground, with brass cap mkd.



Deposit a magnet, in a white plastic case, at the base of the stainless steel post.

Set a steel fence post, alongside and SSE of the cor.

S. 59°40' W., on line 1-2, The Boss' # 1 Mill Site, along the ASNF boundary.

9.09


Cor. 2, The Boss' # 1 Mill Site, monumented with a sandstone, 6 ins. x 5 ins., firmly set, projecting 14 ins. above ground, mkd. with an X on top, and 2BMS1 4417B on the N. face.

from which

A pine 29 ins. diam., bears S. 64 3/4° W., 40 lks. dist., with a healed blaze.

At the corner point

Excavate the mkd. stone, 32 x 14 x 5 ins. and replace with a stainless steel post, 28 ins. long, 2 1/2 ins. diam., set 22 ins. in the ground, encircled with a collar of stone, with brass cap mkd.



Deposit a magnet, in a white plastic case, at the base of the stainless steel post.

Dependent Resurvey of a Portion of Mineral Survey Number 4417B,  
T. 11 N., R. 14 E., Gila and Salt River Meridian, Arizona

CHAINS	<p>Break the mkd. stone into pieces and use as backfill around the stainless steel post.</p> <p>USFS sign Nos. 54-2 and 54-4, riveted to a steel fence post, are set alongside the cor.</p> <hr style="width: 20%; margin: 10px auto;"/> <p>N. 30°28' W., on line 2-3, The Boss' # 1 Mill Site, along the ASNF boundary.</p>
5.52	<p>Cor. 3, The Boss' # 1 Mill Site, monumented with a sandstone, 10 ins. x 6 ins., firmly set, projecting 9 ins. above ground, mkd. with an X on top, and 3BMS1 4417B on the ESE face.</p> <p>from which</p> <p style="padding-left: 40px;">A pine snag, 30 ins. diam., 60 ins. high, bears S. 4 1/4° W., 62.5 lks. dist., mkd. X BT 3BMS1 4417B, on an open blaze.</p> <p>At the corner point</p> <p>Excavate the mkd. stone, 30 x 9 x 6 ins. and replace with a stainless steel post, 28 ins. long, 2 1/2 ins. diam., set 24 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center; margin: 10px 0;"> </div> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p> <p>Break the mkd. stone into pieces and use as backfill around the stainless steel post.</p> <p>USFS sign Nos. 54-2 and 54-4, riveted to a steel fence post, are set alongside and N. of the cor.</p> <hr style="width: 20%; margin: 10px auto;"/> <p>N. 59°41' E., on line 3-4, The Boss' # 1 Mill Site, along the ASNF boundary.</p>
8.73	<p>Intersect the line bet. secs. 11 and 14.</p> <p>From this point, the 1/4 sec. cor. of secs. 11 and 12, bears N. 89°56' E., 16.51 chs. dist., hereinbefore described.</p> <p>From this same point, the cor. of secs. 10, 11, 14 and 15, bears S. 89°56' W., 23.43 chs. dist., hereinbefore described.</p>

Dependent Resurvey of a Portion of Mineral Survey Number 4417B,  
T. 11 N., R. 14 E., Gila and Salt River Meridian, Arizona

CHAINS	
	<p>Continuing measurement in sec. 11.</p> <p>9.11 Cor. 4, The Boss' # 1 Mill Site, identical with cor. 3, Hill Crest Mill Site # 1, monumented with a sandstone, 14 ins. x 7 ins., firmly set, projecting 10 ins. above ground, mkd. with an X on top, 4BMS1 4417B on the S. face and 3HMS1 on the E. face.</p> <p>from which</p> <p style="padding-left: 40px;">A stump hole, 48 ins. diam., bears S. 88 1/2° W., 98 lks. dist., with a rotted pine, 48 ins. diam. alongside.</p> <p>At the corner point</p> <p>Excavate the mkd. stone, 26 x 14 x 7 ins. and replace with a stainless steel post, 28 ins. long, 2 1/2 ins. diam., set 20 ins. in the ground, in a mound of stone, 2 1/2 ft. base, to top, with brass cap mkd.</p> <div style="text-align: center; margin: 20px 0;"> <p style="margin: 0;">T 11 N R 14 E</p> <p style="margin: 0;">S11</p> <p style="margin: 0;">ASNF C3</p> <p style="margin: 0;">C4 HCMS1</p> <p style="margin: 0;">B1MS</p> <p style="margin: 0;">MS4417B MS4417B</p> <p style="margin: 0;">2018</p> </div> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p> <p>Break the mkd. stone into pieces and use as backfill around the stainless steel post.</p> <hr style="width: 30%; margin: 20px auto;"/> <p>N. 59°54' E., on line 3-4, Hillcrest Mill Site # 1, along the ASNF boundary.</p>
4.26	<p>A rebar, 1/2 in. diam., firmly set, projecting 1 ins. above ground, with attached brass wafer, stamped RLS 21791. Monumented by Michael Stoll, Arizona Registered Land Surveyor No. 21791, date unknown. Accepted as a bona fide establishment of the NW cor. of Coconino County Assessor's parcel 403-30-001L.</p> <hr style="width: 30%; margin: 20px auto;"/> <p>N. 60°01' E., beginning new measurement.</p>
4.81	<p>Cor. 4, Hillcrest Mill Site # 1, perpetuated by Michael Stoll, Arizona Registered Land Surveyor No. 21791, monumented with a rebar, 1/2 in. diam., firmly set, projecting 1 in. above ground, with attached brass washer, stamped RLS 21791.</p> <p>from which</p>




Dependent Resurvey of a Portion of Mineral Survey Number 4417B,  
T. 11 N., R. 14 E., Gila and Salt River Meridian, Arizona

## CHAINS

A pine snag, 23 ins. diam., bears S. 68 1/4° W., 55 lks. dist., with a healed blaze.

At the corner point

Excavate the rebar, 18 ins. long and replace with a stainless steel post, 28 ins. long, 2 1/2 ins. diam., set 20 ins. in the ground, in a mound of stone, 2 1/2 ft. base, to top, with brass cap mkd.



Deposit a magnet, in a white plastic case, at the base of the stainless steel post. Insert the rebar, inside the stainless steel post.

The original stone, 30 x 14 x 5 ins., mkd. 4HMS1 4417B on a face, was found lying loose nearby. Break the stone into pieces and incorporate within the mound of stone.

USFS sign Nos. 54-2 and 54-9, riveted to a steel fence post, are set alongside the cor.

---

S. 30°30' E., on line 4-1, Hillcrest Mill Site # 1, along the ASNF boundary.

2.63 Intersect an abandoned and fallen metal water tank, 15 ft. long, 4 ft. diam. The center of the top, bears N. 43° E., 14 ft. dist. The center of the bottom, bears S. 43° W., 1 ft. dist.

5.48 Cor. 1, Hill Crest Mill Site # 1.

---

Dependent Resurvey of a Portion of Mineral Survey Number 4360,  
T. 11 N., R. 14 E., Gila and Salt River Meridian, Arizona

---

Restoring a portion of the survey executed by  
Richard L. Merritt, in 1951

---

From the intersection of the line bet. secs. 13 and 18, on the E. bdy. of the Tp., with line 3-4, Hillcrest No. 4 lode, M.S. No. 4360, hereinbefore described.

Dependent Resurvey of a Portion of Mineral Survey Number 4360,  
T. 11 N., R. 14 E., Gila and Salt River Meridian, Arizona

CHAINS	
	<p>From this point, the cor. of secs. 7, 12, 13 and 18, on the E. bdy. of the Tp., bears N. 0°01' E., 16.74 chs. dist., hereinbefore described.</p> <p>From this same point, the 1/4 sec. cor. of secs. 13 and 18, on the E. bdy. of the Tp., bears S. 0°01' W., 23.28 chs. dist., hereinbefore described.</p> <p>From this same point, cor. 4, Hillcrest No. 4 lode, bears S. 30°21' E., 13.61 chs. dist., as described in the dependent resurvey of certain mineral surveys, in T. 11 N., R. 15 E., executed concurrently with this same group.</p> <p>N. 30°21' W., on a portion of line 4-3, Hillcrest No. 4 lode.</p>
9.10	<p>Cor. 3, Hillcrest No. 4 lode, monumented with a sandstone, 12 ins. x 4 ins., firmly set, projecting 6 ins. above ground, mkd. with an X on top, and 3H4 4360 on the S. face.</p> <p>At the corner point</p> <p>Excavate the mkd. stone, 24 x 12 x 4 ins. and replace with a stainless steel post, 28 ins. long, 2 1/2 ins. diam., set 26 ins. in the ground, with brass cap mkd.</p> <div data-bbox="787 1039 1015 1270" style="text-align: center;"> <p>T 11 N R 14 E</p> <p>S13</p> <p>ASNF</p> <p>C3</p> <p>HC4</p> <p>MS4360</p> <p>2018</p> </div> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p> <p>Break the mkd. stone into pieces and use as backfill around the stainless steel post.</p> <p>The original location monument, a 4 x 4 ins. wood post, projecting 42 ins. above ground, supported by a mound of stone, 3 ft. base, 1 ft. high, is located ENE, 2 ft.</p> <p>USFS sign Nos. 54-2 and 54-4, riveted to a steel fence post, are set alongside and N. of the cor.</p> <hr style="width: 20%; margin: 10px auto;"/> <p>S. 59°39' W., on line 3-2, Hillcrest No. 4 lode.</p>
9.10	<p>Cor. 2, Hillcrest No. 4 lode, identical with cor. 4, Hillcrest No. 3 lode, M.S. 4360, monumented with a sandstone, 12 ins. x 4 ins.,</p>

Dependent Resurvey of a Portion of Mineral Survey Number 4360,  
T. 11 N., R. 14 E., Gila and Salt River Meridian, Arizona

CHAINS


firmly set, projecting 10 ins. above ground, mkd. with an X on top, 4H3 4360 on the S. face and 2H4 on the E. face.

from which

A pine snag, 30 ins. diam., bears S. 55 1/2° W., 69 lks. dist., mkd. X 4H3 2H4 4360 BT, on an open blaze.

At the corner point

Excavate the mkd. stone, 30 x 12 x 4 ins. and replace with a stainless steel post, 28 ins. long, 2 1/2 ins. diam., set 22 ins. in the ground, encircled with a collar of stone, with brass cap mkd.



Deposit a magnet, in a white plastic case, at the base of the stainless steel post.

Break the mkd. stone into pieces and use as backfill around the stainless steel post.


S. 59°41' W., on line 4-3, Hillcrest No. 3 lode.

9.08

Cor. 3, Hillcrest No. 3 lode, on line 4-1, Campbell and Denison No. 1 lode, M.S. No. 4352, monumented with a sandstone, 10 ins. x 6 ins., firmly set, projecting 10 ins. above ground, mkd. with an X on top, and 3H3 4360 on the E. face.

At the corner point

Excavate the mkd. stone, 29 x 11 x 6 ins. and replace with a stainless steel post, 28 ins. long, 2 1/2 ins. diam., set 23 ins. in the ground, encircled with a collar of stone, with brass cap mkd.



Dependent Resurvey of a Portion of Mineral Survey Number 4360,  
T. 11 N., R. 14 E., Gila and Salt River Meridian, Arizona

CHAINS

Deposit a magnet, in a white plastic case, at the base of the stainless steel post.

Break the mkd. stone into pieces and use as backfill around the stainless steel post.

Remnants of the original location monument, a mound of stone, 4 ft. base, 1 ft. high, is located WSW, 1.5 ft.

USFS sign Nos. 54-2 and 54-4, riveted to a steel fence post, are set alongside and NE of the cor.

---

Dependent Resurvey of a Portion of Mineral Survey Number 4352,  
T. 11 N., R. 14 E., Gila and Salt River Meridian, Arizona

---

Restoring a portion of the survey executed by  
Richard L. Merritt, in 1951

---

N. 30°24' W., on a portion of line 1-4, Campbell and Denison No. 1 lode, M.S. No. 4352.

3.03


Cor. 4, Campbell and Denison No. 1 lode, monumented with a sandstone, 14 ins. x 4 ins., firmly set, projecting 9 ins. above ground, mkd. with an X on top, and 4CD1 4352 on the SW face.

from which

A pine, 34 ins. diam., bears N. 15 1/4° W., 38 lks. dist., mkd. X BT 4CD1 4352, on an open blaze.

At the corner point

Excavate the mkd. stone, 28 x 15 x 4 ins. and replace with a stainless steel post, 28 ins. long, 2 1/2 ins. diam., set 23 ins. in the ground, encircled with a collar of stone, with brass cap mkd.




Deposit a magnet, in a white plastic case, at the base of the stainless steel post.

Break the mkd. stone into pieces and use as backfill around the stainless steel post.


Dependent Resurvey of a Portion of Mineral Survey Number 4352,  
T. 11 N., R. 14 E., Gila and Salt River Meridian, Arizona

CHAINS	<p>USFS sign Nos. 54-2 and 54-4, riveted to a steel fence post, are set alongside and N. of the cor.</p> <hr/> <p>S. 59°37' W., on line 4-3, Campbell and Denison No. 1 lode.</p>						
9.09	<p>Cor. 3, Campbell and Denison No. 1 lode, identical with cor. 4, Campbell and Denison No. 2 lode, M.S. No. 4352, identical with cor. 2, The Boss' # 3 lode, M.S. No. 4417A, monumented with a sandstone, 18 ins. x 8 ins., firmly set, projecting 9 ins. above ground, mkd. with an X on top, 3CD1 4352 on the SE face, 4CD2 on the SW face and 2B3 4417A on the NW face.</p> <p>Note: The Boss' # 3 lode, M.S. No. 4417A, was excluded from the patent granted to M.S. 4417A.</p> <p>from which</p> <p style="padding-left: 40px;">A pine stump, 18 ins. diam., 54 ins. high, bears S. 53 1/2° W., 57.5 lks. dist., mkd. 2B3 4417A X BT 4CD2 3CD1 4352, on an open blaze.</p> <p>At the corner point</p> <p>Excavate the mkd. stone, 27 x 19 x 8 ins. and replace with a stainless steel post, 28 ins. long, 2 1/2 ins. diam., set 24 ins. in the ground, encircled with a collar of stone, with brass cap mkd.</p> <div style="text-align: center;"> <p>T 11 N R 14 E</p> <p>S13</p> <p>ASNF</p> <hr style="width: 10%; margin: 0 auto;"/> <table style="margin: 0 auto; border-collapse: collapse;"> <tr> <td style="padding: 0 5px;">C4</td> <td style="border-left: 1px solid black; padding: 0 5px;">C3</td> </tr> <tr> <td style="padding: 0 5px;">CD2</td> <td style="border-left: 1px solid black; padding: 0 5px;">CD1</td> </tr> <tr> <td style="padding: 0 5px;">MS4352</td> <td style="border-left: 1px solid black; padding: 0 5px;">MS 4352</td> </tr> </table> <p>2018</p> </div> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p> <p>Break the mkd. stone into pieces and use as backfill around the stainless steel post.</p> <p>Remnants of the original location monument, a mound of stone, 3 ft. base, 1 ft. high, with a wood post, 4 x 4 x 48 ins., lying loose nearby, is located SSE, 2.5 ft.</p> <p>USFS sign Nos. 54-2 and 54-4, riveted to a steel fence post, are set alongside and N. of the cor.</p> <hr/> <p>S. 59°38' W., on line 4-3, Campbell and Denison No. 2 lode.</p>	C4	C3	CD2	CD1	MS4352	MS 4352
C4	C3						
CD2	CD1						
MS4352	MS 4352						


Dependent Resurvey of a Portion of Mineral Survey Number 4352,  
T. 11 N., R. 14 E., Gila and Salt River Meridian, Arizona

CHAINS	
4.30	Merzville Loop road, graded 25 ft. wide, bears S. 30° E. and N. 30° W., for about 50 ft. to a locked gate, at closed ASNF road.
9.09	<p>Cor. 3, Campbell and Denison No. 2 lode, on line 1-2, The Boss' # 2, M.S. No. 4417A, monumented with a sandstone, 11 ins. x 11 ins., firmly set, projecting 9 ins. above ground, mkd. with an X on top, 3CD2 4352 on SE face and 4417A on the NW face.</p> <p>from which</p> <p style="padding-left: 40px;">A pine stump, 16 ins. diam., 24 ins. high, bears N. 51 3/4° W., 13 lks. dist., with a fallen, 16 in. diam. pine, alongside mkd. B3 417A X BT 3CD2 4352, on a partially healed blaze.</p> <p>At the corner point</p> <p>Excavate the mkd. stone, 24 x 11 x 11 ins. and replace with a stainless steel post, 28 ins. long, 2 1/2 ins. diam., set 20 ins. in the ground, in a mound of stone, 2 1/2 ft. base, to top, with brass cap mkd.</p> <div style="text-align: center; margin: 20px 0;">  </div> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p> <p>Break the mkd. stone into pieces and incorporate within the mound of stone.</p> <p>USFS sign Nos. 54-2 and 54-4, riveted to a steel fence post, are set alongside and N. of the cor.</p> <hr/> <p style="text-align: center;"><b>Dependent Resurvey of a portion of M.S. No. 4417A, T. 11 N., R. 14 E., Gila and Salt River Meridian, Arizona</b></p> <hr/> <p style="text-align: center;">Restoring the Survey executed by Richard L. Merritt in 1956</p> <hr/> <p>N. 30°21' W., on a portion of line 2-1, The Boss' # 2 lode.</p>
5.07	Intersect the N. and S. center line of sec. 13.

Restoring a portion of M.S. No. 4417A,  
T. 11 N., R. 14 E., Gila and Salt River Meridian, Arizona

CHAINS	
	<p>From this point, the 1/4 sec. cor. of secs. 12 and 13, bears N. 0°04' E., 20.30 chs. dist., hereinbefore described.</p>
	<p>From this same point, the point for the center 1/4 sec. cor. of sec. 13, bears S. 0°04' W., 19.72 chs. dist., hereinbefore described.</p>
14.12	<p>Intersect the southerly side of a concrete stair case. From this point, the southeasterly cor. of same staircase, bears N. 63 1/2° E., 6.4 lks. dist. The long side bears N. 26 1/2° W.,</p>
14.27	<p>Intersect the northerly side of same concrete staircase.</p> <p>From this point, the northeasterly cor. of same staircase, bears N. 63 1/2° E., 7.5 lks. dist.</p>
20.14	<p>Cor. 1, The Boss' # 2 lode, monumented with a sandstone, 9 ins. x 8 ins., firmly set, projecting 12 ins. above ground, mkd. with an X on top, and 1B2 4417A on the SE face.</p>
	<p>from which</p>
	<p>A pine snag, 36 ins. diam., bears S. 72 3/4° E., 28.5 lks. dist., mkd. X B2 7, on a partially healed over blaze.</p>
	<p>At the corner point</p>
	<p>Excavate the mkd. stone, 28 x 9 x 8 ins. and replace with a stainless steel post, 28 ins. long, 2 1/2 ins. diam., set 22 ins. in the ground, in a mound of stone, 2 1/2 ft. base, to top, with brass cap mkd.</p>
	<div style="text-align: center;"> <p>T 11 N R 14 E</p> <p>S13</p> <p>ASNF</p>  <p>2018</p> </div>
	<p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p>
	<p>Break the mkd. stone into pieces and incorporate within the mound of stone.</p>
	<p>USFS sign Nos. 54-2 and 54-4, riveted to a steel fence post, are set alongside and NE of the cor.</p>
	<hr style="width: 20%; margin: auto;"/> <p>S. 59°41' W., on a portion of line 1-4, The Boss' # 2 lode.</p>

Restoring a portion of M.S. No. 4417A,  
T. 11 N., R. 14 E., Gila and Salt River Meridian, Arizona

CHAINS	
4.55	<p>Cor. 3, The Boss' # 4 lode, M.S. 4417A, identical with cor. 2, The Boss' # 5 lode, M.S. No. 4417A, monumented with a sandstone, 10 ins. x 7 ins., firmly set, projecting 14 ins. above ground, mkd. with an X on top, 2B5 on the N. face and 3B4 4417A on the W face.</p> <p><u>Note:</u> The Boss' # 5 lode, M.S. No. 4417A, was excluded from the patent granted to M.S. 4417A.</p> <p>At the corner point</p> <p>Excavate the mkd. stone, 34 x 11 x 7 ins. and replace with a stainless steel post, 28 ins. long, 2 1/2 ins. diam., set 24 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center;"> <p>T 11 N R 14 E</p> <p>S13</p> <p>BOSS 4 ASNF</p> <p>MS 4417A</p> <p>C3</p> <p>BOSS 2</p> <p>MS 4417A</p> <p>2018</p>  </div> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p> <p>Break the mkd. stone into 4 pieces and bury alongside the cor.</p> <p>Remnants of the original location monument, a mound of stone, 3 ft. base, 1 ft. high, is located SSW, 4 ft.</p> <p>USFS sign Nos. 54-2 and 54-4, riveted to a steel fence post, are set alongside and NE of the cor.</p> <hr style="width: 20%; margin: 10px auto;"/> <p>N. 30°17' W., on a portion of line 3-2, The Boss' # 4 lode.</p>
3.25	<p>Joe Springs road, graded 30 ft. wide, bears S. 55° W. and bears N. 55° E. onto ASNF and designated an off road vehicle trail.</p>
11.09	<p>Intersect the line bet. secs. 12 and 13.</p> <p>From this point, the 1/4 sec. cor. of secs. 12 and 13, bears N. 89°59' E., 17.15 chs. dist., hereinbefore described.</p> <p>From this same point, the cor. of secs. 11, 12, 13 and 14, bears S. 89°59' W., 22.95 chs. dist., hereinbefore described.</p> <p>Continuing measurement in sec. 12.</p>



Restoring a portion of M.S. No. 4417A,  
T. 11 N., R. 14 E., Gila and Salt River Meridian, Arizona

## CHAINS

22.73

Cor. 2, Boss' # 4 lode, identical with cor. 3, The Boss' # 5 lode, M.S. No. 4417A, monumented with a sandstone, 10 ins. x 9 ins., firmly set, projecting 13 ins. above ground, mkd. with an X on top, 2B4 on the SW face and 3B5 4417A on the SE face.


Note: The Boss' # 5 lode, M.S. No. 4417A, was excluded from the patent granted to M.S. 4417A.

from which

A pine, 28 ins. diam., bears S. 33 1/4° E., 44.5 lks. dist., with a healed blaze.

At the corner point

Excavate the mkd. stone, 26 x 10 x 9 ins. and replace with a stainless steel post, 28 ins. long, 2 1/2 ins. diam., set 20 ins. in the ground, in a mound of stone, 3 ft. base, to top, with brass cap mkd.



Deposit a magnet, in a white plastic case, at the base of the stainless steel post.

Break the mkd. stone into 3 pieces and bury alongside the cor.

Remnants of the original location monument, a scattered and fallen mound of stone, N. of the cor. Utilize this mound, for the mound of stone surrounding the stainless steel post.

USFS sign Nos. 54-2 and 54-4, riveted to a steel fence post, are set alongside and N. of the cor.

---

S. 59°41' W., on line 2-1, The Boss' # 4 lode.

9.10

Cor. 1, The Boss' # 4 lode, identical with cor. 4, Miss Lottie # 2 lode, M.S. 4417A, identical with cor. 2, Campbell and Denison No. 15 lode, M.S. No. 4352, monumented with a sandstone, 19 ins. x 9 ins., firmly set, projecting 11 ins. above ground, mkd. with a faint X on top, 2CD15 4352 on the SSW face, other marks on the stone are faint and illegible.

from which


Restoring a portion of M.S. No. 4417A,  
T. 11 N., R. 14 E., Gila and Salt River Meridian, Arizona

## CHAINS

A rotting pine stump, 12 ins. diam., 12 ins. high, bears  
N. 83 3/4° W., 15.5 lks. dist.

At the corner point

Excavate the mkd. stone, 24 x 20 x 12 ins. and replace with a  
stainless steel post, 28 ins. long, 2 1/2 ins. diam., set 20 ins.  
in the ground, in a mound of stone, 3 ft. base, to top, with brass  
cap mkd.



Deposit a magnet, in a white plastic case, at the base of the  
stainless steel post.

Incorporate the marked stone within the mound of stone.

N. 30°18' W., on line 4-3, Miss Lottie # 2 lode.

18.27 Intersect the line bet. secs. 11 and 12.

From this point, the 1/4 sec. cor. of secs. 11 and 12, bears  
N. 0°02' E., 18.74 chs. dist., hereinbefore described.

From this same point, the cor. of secs. 11, 12, 13 and 14, bears  
S. 0°02' W., 21.23 chs. dist., hereinbefore described.

Continuing measurement in sec. 11.

22.74 Cor. 3, Miss Lottie # 2 lode, identical with cor. 2, Miss Lottie  
# 3 lode, M.S. 4417A, determined from the remains of the orig.  
bearing tree

A rotting pine stump, 24 ins. diam., 24 ins. high, bears  
S. 42 1/4° E., 1.275 chs. dist.

At the cor. point

Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 27 ins.  
in the ground, with brass cap mkd.

Restoring a portion of M.S. No. 4417A,  
T. 11 N., R. 14 E., Gila and Salt River Meridian, Arizona

CHAINS	
	<div style="text-align: center;"> <p>T 11 N R 14 E ML3 MS4417A C2 ASNF S11 C3 MS4417A ML2 2018</p> </div> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p> <p>Set a steel fence post, alongside and ENE of cor.</p> <hr style="width: 20%; margin: 10px auto;"/> <p>N. 30°16' W., on line 2-1, Miss Lottie # 3, lode.</p> <p>0.40 Wildcat road, 20 ft. wide, bears N., curving E. and S., curving W.</p> <p>17.21 Intersect the E. and W. center line of sec. 11.</p> <p>From this point, the 1/4 sec. cor. of secs. 11 and 12, bears N. 89°56' E., 10.94 chs. dist., hereinbefore described.</p> <p>From this same point, the center 1/4 sec. cor. of sec. 11, bears S. 89°56' W., 29.00 chs. dist., hereinbefore described.</p> <p>22.75 Cor. 1, Miss Lottie # 3 lode, monumented with a sandstone, 10 ins. x 5 ins., firmly set, projecting 8 ins. above ground, mkd. with an X on top, and 1ML3 4417A on the SE face.</p> <p>At the corner point</p> <p>Excavate the mkd. stone, 24 x 10 x 8 ins. and replace with a stainless steel post, 28 ins. long, 2 1/2 ins. diam., set 20 ins. in the ground, in a mound of stone, 2 1/2 ft. base, to top, with brass cap mkd.</p> <div style="text-align: center;"> <p>T 11 N R 14 E S 11 ASNF C1 ML3 MS4417A 2018</p> </div> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p> <p>Incorporate the marked stone within the mound of stone.</p>

Restoring a portion of M.S. No. 4417A,  
T. 11 N., R. 14 E., Gila and Salt River Meridian, Arizona

CHAINS	<p>USFS sign Nos. 54-2 and 54-9, riveted to a steel fence post, are set alongside and N. of the cor.</p> <hr/> <p>S. 59°43' W., on line 1-4, Miss Lottie # 3 lode.</p> <p>9.10 Cor. 4, Miss Lottie # 3 lode, monumented with a sandstone, 14 ins. x 4 ins., firmly set, projecting 13 ins. above ground, mkd. with an X on top, and 4ML3 4417A on the E. face.</p> <p>from which</p> <p style="padding-left: 40px;">A pine, 19 ins. diam., bears N. 71 1/2° W., 59 lks. dist., with a healed blaze.</p> <p>At the corner point</p> <p>Excavate the mkd. stone, 27 x 14 x 6 ins. and replace with a stainless steel post, 28 ins. long, 2 1/2 ins. diam., set 22 ins. in the ground, in a mound of stone, 3 ft. base, to top, with brass cap mkd.</p> <div style="text-align: center;"> <p>T 11 N R 14 E</p> <p>S11 ML3</p> <p>ASNF C4</p> <p>MS4417A</p> <p>2018</p> </div> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p> <p>Incorporate the marked stone within the mound of stone.</p> <p>Remnants of the original location monument, a mound of stone, 3 ft. base, 1 1/2 ft. high, is located NNW, 3 ft.</p> <p>USFS sign Nos. 54-2 and 54-9, riveted to a steel fence post, are set alongside and N. of the cor.</p> <hr/> <p>S. 30°15' E., on a portion of line 4-3, Miss Lottie # 3, lode.</p> <p>0.24 Intersect the E. and W. center line of sec. 11.</p> <p>From this point, the 1/4 sec. cor. of secs. 11 and 12, bears N. 89°56' E., 21.47 chs. dist., hereinbefore described.</p> <p>From this same point, the center 1/4 sec. cor. of sec. 11, bears S. 89°56' W., 18.47 chs. dist., hereinbefore described.</p>
--------	---


Restoring a portion of M.S. No. 4417A,  
T. 11 N., R. 14 E., Gila and Salt River Meridian, Arizona

<p>CHAINS</p> <p>13.64</p>	<p>Cor. 4, Miss Lottie # 1 lode, M.S. 4417A, on line 3-4, Miss Lottie # 3 lode, monumented with a sandstone, 13 ins. x 6 ins., firmly set, projecting 16 ins. above ground, mkd. with an X on top, and 4ML1 4417A on the S. face.</p> <p>At the corner point</p> <p>Excavate the mkd. stone, 28 x 13 x 6 ins. and replace with a stainless steel post, 28 ins. long, 2 1/2 ins. diam., set 22 ins. in the ground, encircled with a collar of stone, with brass cap mkd.</p> <div style="text-align: center; margin: 10px 0;"> <p>T 11 N R 14 E</p> <p>S11 ML3</p> <p>ASNF MS4417A</p> <p>C4 ML1 MS4417A 2018</p> </div> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p> <p>Remnants of the original location monument, a mound of stone, 4 ft. base, 2 ft. high, is located ENE, 4 ft.</p> <p>Incorporate the mkd. stone within the location monument mound of stone.</p> <hr style="width: 20%; margin: 10px auto;"/> <p>S. 59°44' W., on line 4-3, Miss Lottie # 1 lode.</p>
<p>9.10</p>	<p>Cor. 3, Miss Lottie # 1 lode, monumented with a sandstone, 8 ins. x 6 ins., firmly set, projecting 8 ins. above ground, mkd. with an X on top, and 3ML1 4417A on the E. face. from which</p> <p style="margin-left: 40px;">A pine, 27 ins. diam., bears S., 6 lks. dist., with marks X BT visible on a mostly healed over blaze.</p> <p>At the corner point</p> <p>Excavate the mkd. stone, 27 x 8 x 8 ins. and replace with a stainless steel post, 28 ins. long, 2 1/2 ins. diam., set 20 ins. in the ground, in a mound of stone, 2 1/2 ft. base, to top, with brass cap mkd.</p> <div style="text-align: center; margin: 10px 0;"> <p>T 11 N R 14 E</p> <p>ML1</p> <p>S11 C3</p> <p>ASNF MS4417A</p> <p>2018</p> </div>

Restoring a portion of M.S. No. 4417A,  
T. 11 N., R. 14 E., Gila and Salt River Meridian, Arizona

CHAINS	
	<p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p> <p>Incorporate the marked stone within the mound of stone.</p> <p>USFS sign Nos. 54-2 and 54-9, riveted to a steel fence post, are set alongside and WNW of the cor.</p> <hr/> <p>S. 30°18' E., on a portion of line 3-2, Miss Lottie # 1 lode.</p>
1.29	<p>From this point, the NE cor. of a raised bed garden, 8 x 16 ft., enclosed with a 3 1/2 ft. high wire fence, bears S. 59°42' W., 6.1 lks. dist., the long side bears S. 35 1/2° E., the short side bears S. 54 1/2° W.</p>
1.53	<p>From this point, the SE cor. of same raised bed garden, bears S. 59°42' W., 3.9 lks. dist.</p>
3.29	<p>The cor. of lots 570 and 571, Forest Lake Estates Unit Seven, on line 2-3, Miss Lottie # 1 lode, monumented with a rebar, 5/8 in. diam., firmly set, projecting 2 ins. above ground, with attached 1 1/2 ins. diam., aluminum cap, stamped US 570 571.</p> <hr/> <p>S. 30°24' E., beginning new measurement.</p>
1.27	<p>Cor. 4, Campbell and Denison No. 13 lode, M.S. No. 4352, on line 2-3, Miss Lottie # 1 lode, monumented with a sandstone, 30 x 13 x 8 ins., loosely set, mkd. with an X on top and 4CD13 4352 on SE face.</p> <p>from which the remains of the original bearing tree</p> <p style="padding-left: 40px;">A rotting pine stump, 24 ins. diam., 18 ins. high, bears S. 27 1/4° E., 23.5 lks. dist., with no visible marks.</p> <p>and a bearing tree mkd. by the USFS</p> <p style="padding-left: 40px;">A pine, 26 ins. diam., bears W., 54.5 lks. dist., mkd BT 4CD13 4352</p> <p>At the corner point.</p> <p>Remove the marked stone, and replace with a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 20 ins. in the ground, in a mound of stone, 3 ft. base, to top, with brass cap mkd.</p>

Restoring a portion of M.S. No. 4417A,  
T. 11 N., R. 14 E., Gila and Salt River Meridian, Arizona

CHAINS	
	 <p>T 11 N R 14 E S11 ML1 ASN F MS4417A C4 MS4352 CD13 2018</p>
	<p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p> <p>Incorporate the marked stone within the mound of stone.</p> <p>From this cor., on line 2-3, Miss Lottie # 1 Lode, a rebar, 1/2 in. diam., firmly set, projecting 1 ins. above ground, with attached brass washer, stamped RLS 23955, bears S. 30°24' E., 2.29 chs. dist.</p>
	<p>From cor. No. 2, D &amp; W #6 lode.</p> <p>S. 59°45' W., on line 2-1, D &amp; W #6 lode.</p>
16.32	<p>Intersect the N. and S. center line of sec. 11.</p> <p>From this point, the 1/4 sec. cor. of secs. 11 and 14, bears S. 0°02' E., 3.20 chs. dist., hereinbefore described.</p> <p>From this same point, the center 1/4 sec. cor. of sec. 11, bears N. 0°02' W., 36.81 chs. dist., hereinbefore described.</p>
22.68	<p>Intersect the line bet. secs. 11 and 14.</p> <p>From this point, the 1/4 sec. cor. of secs. 11 and 14, bears N. 89°56' E., 5.50 chs. dist., hereinbefore described.</p> <p>From this same point, the cor. of secs. 10, 11, 14 and 15, bears S. 89°56' W., 34.44 chs. dist., hereinbefore described.</p> <p>Continuing measurement in sec. 14.</p>
22.73	<p>Cor. 1, D &amp; W # 6 lode, identical with cor. 1, D &amp; W # 5 lode, M.S. No. 4462, not patented, monumented with a sandstone, 12 ins. x 6 ins., firmly set, projecting 9 ins. above ground, mkd. with an X on top, 1DW6 4417A on the E. face and 1DW5 4462 on the S. face.</p> <p>from which</p> <p style="padding-left: 40px;">A pine stump, 24 ins. diam., 66 ins. high, bears N. 4 1/4° E., 31.5 lks. dist., with faint illegible marks.</p>

Restoring a portion of M.S. No. 4417A,  
T. 11 N., R. 14 E., Gila and Salt River Meridian, Arizona

CHAINS

At the corner point

Excavate the mkd. stone, 24 x 12 x 7 ins. and replace with a stainless steel post, 28 ins. long, 2 1/2 ins. diam., set 24 ins. in the ground, with brass cap mkd.

T 11 N R. 14 E  
 S14      DW6  
           C1  
 ASNF      MS4417A  
 2018

Deposit a magnet, in a white plastic case, at the base of the stainless steel post.

Bury the mkd. stone alongside the stainless steel post.

Remnants of the original location monument, a mound of stone, 3 ft. base, 1 ft. high, is located N., 3 ft.

USFS sign Nos. 54-2 and 54-4, riveted to a steel fence post, are set alongside the cor.

From this cor., cor. 1, Hillcrest Mill Site # 1, M.S. No. 4417B, bears N. 26°57' W., 3 lks. dist., hereinbefore described.

---

S. 30°20' E., on line 1-4, D & W # 6 lode.

9.09

Cor. 4, D & W # 6 lode, identical with cor. 1, D & W # 1 lode, M.S. No. 4417A, monumented with a sandstone, 9 ins. x 9 ins., firmly set, projecting 16 ins. above ground, mkd. with an X on top, 4DW6 4417A on the NE face and 1DW1 on the SE face.

from which

A pine, 26 ins. diam., bears S. 5 3/4° E., 34.5 lks. dist., with a lone scribe mark visible on a mostly healed over blaze.

At the corner point

Excavate the mkd. stone, 30 x 9 x 9 ins. and replace with a stainless steel post, 28 ins. long, 2 1/2 ins. diam., set 19 ins. in the ground, in a mound of stone, 2 1/2 ft. base, to top, with brass cap mkd.



Restoring a portion of M.S. No. 4417A,  
T. 11 N., R. 14 E., Gila and Salt River Meridian, Arizona

CHAINS	<div data-bbox="782 279 1092 546" data-label="Diagram"> </div> <div data-bbox="386 579 1416 636" data-label="Text"> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p> </div> <div data-bbox="386 667 1416 724" data-label="Text"> <p>Break the marked stone into pieces and incorporate within the mound of stone.</p> </div> <div data-bbox="386 756 1416 812" data-label="Text"> <p>Remnants of the original location monument, an embedded mound of stone, 3 ft. base, 1/2 ft. high, is located E., 2 ft.</p> </div> <hr data-bbox="646 844 1166 850"/> <div data-bbox="386 877 1052 905" data-label="Text"> <p>S. 30°13' E., on line 1-4, D &amp; W # 1 lode.</p> </div> <div data-bbox="245 940 1130 968" data-label="Text"> <p>1.88 Intersect the N. and S. center line of sec. 14.</p> </div> <div data-bbox="386 999 1416 1056" data-label="Text"> <p>From this point, the 1/4 sec. cor. of secs. 11 and 14, bears N. 0°01' E., 9.50 chs. dist., hereinbefore described.</p> </div> <div data-bbox="386 1087 1416 1144" data-label="Text"> <p>From this same point, the center 1/4 sec. cor. of sec. 14, bears S. 0°01' W., 30.48 chs. dist., hereinbefore described.</p> </div> <div data-bbox="245 1178 1383 1205" data-label="Text"> <p>8.30 Canyon Drive, graded 20 ft. wide, bears N. 60° E. and S. 60° W.</p> </div> <div data-bbox="245 1239 1416 1381" data-label="Text"> <p>9.10 Cor. 4, D &amp; W # 1 lode, identical with cor. 4, D &amp; W # 3 lode, M.S. No. 4462, not patented, monumented with a sandstone, 9 ins. x 8 ins., firmly set, projecting 18 ins. above ground, mkd. with an X on top, 4DW1 4417A on the N. face and DW3-4 4462 on the E. face.</p> </div> <div data-bbox="386 1415 548 1442" data-label="Text"> <p>from which</p> </div> <div data-bbox="477 1476 1416 1566" data-label="Text"> <p>A pine, 26 ins. diam., bears S. 14 3/4° E., 20 lks. dist., with an X and other illegible scribe marks visible on a partially healed over blaze.</p> </div> <div data-bbox="386 1600 688 1627" data-label="Text"> <p>At the corner point</p> </div> <div data-bbox="386 1661 1416 1776" data-label="Text"> <p>Excavate the mkd. stone, 36 x 9 x 8 ins. and replace with a stainless steel post, 28 ins. long, 2 1/2 ins. diam., set 20 ins. in the ground, in a mound of stone, 2 1/2 ft. base, to top, with brass cap mkd.</p> </div>
--------	---

Restoring a portion of M.S. No. 4417A,  
T. 11 N., R. 14 E., Gila and Salt River Meridian, Arizona

CHAINS

T 11 N R 14 E  
 DW1  
 S14 MS4417A  
 C4  
 ASNF  
 2018

Deposit a magnet, in a white plastic case, at the base of the stainless steel post.

Break the marked stone into pieces and incorporate within the mound of stone.

USFS sign Nos. 54-2 and 54-4, riveted to a steel fence post, are set alongside and S. of the cor.

---

N. 59°40' E., on a portion of line 4-3, D & W # 1 lode.

9.09

Point accepted as cor. 3, D & W # 2 lode, M.S. No. 4417A, identical with cor. 1, D & W # 3 lode, M.S. No. 4462, not patented, monumented with a rebar, 1/2 in. diam., firmly set, 4 ins. below the surface, origin unknown.

from which

A rotting pine stump, 36 ins. diam., 18 ins. high, bears S. 17° W., 93 lks. dist.

At the corner point

Excavate the rebar, 18 ins. long and replace with a stainless steel post, 28 ins. long, 2 1/2 ins. diam., set 27 ins. in the ground, encircled with a collar of stone, with brass cap mkd.

T 11 N R 14 E  
 DW1  
 MS4417A  
 ASNF C3  
 S14 DW2  
 MS4417A  
 2018

Deposit a magnet, in a white plastic case, at the base of the stainless steel post.

Insert the rebar inside the stainless steel post.

---

S. 30°17' E., on line 3-2, D & W # 2 lode.

Restoring a portion of M.S. No. 4417A,  
T. 11 N., R. 14 E., Gila and Salt River Meridian, Arizona

## CHAINS

9.11


Cor. 2, D & W # 2 lode, identical with cor. 4 Hillcrest # 26 lode, M.S. No. 4417A, monumented with a sandstone, 11 ins. x 5 ins., firmly set, projecting 14 ins. above ground, mkd. with an X on top, 2DW2 4417A on the N. face and 4H26 on the E. face.

from which

A pine, 22 ins. diam., bears S. 30 1/4° W., 37 lks. dist., with the marks X D2 visible on a mostly healed over blaze.

At the corner point

Excavate the mkd. stone, 32 x 11 x 5 ins. and replace with a stainless steel post, 28 ins. long, 2 1/2 ins. diam., set 20 ins. in the ground, in a mound of stone, 2 1/2 ft. base, to top, with brass cap mkd.



Deposit a magnet, in a white plastic case, at the base of the stainless steel post.

Break the marked stone into pieces and incorporate within the mound of stone.

---

S. 30°16' E., on line 4-3, Hillcrest # 26 lode.

9.10

Cor. 3, Hillcrest # 26 lode, identical with cor. 2, D & W # 3 lode, M.S. No. 4462, not patented, monumented with a sandstone, 16 ins. x 6 ins., firmly set, projecting 12 ins. above ground, mkd. with an X on top, 3H26 4417A on the N. face and 4462 DW3-2 on the E. face.

from which


A pine, 40 ins. diam., bears S. 79 1/4° E., 32 lks. dist., with the scribe marks X-2 4417 3-4, visible on a partially healed over blaze.

At the corner point

Restoring a portion of M.S. No. 4417A,  
T. 11 N., R. 14 E., Gila and Salt River Meridian, Arizona

## CHAINS

Excavate the mkd. stone, 30 x 16 x 6 ins. and replace with a stainless steel post, 28 ins. long, 2 1/2 ins. diam., set 20 ins. in the ground, in a mound of stone, 2 1/2 ft. base, to top, with brass cap mkd.



2018

Deposit a magnet, in a white plastic case, at the base of the stainless steel post.

Break the marked stone into pieces and incorporate within the mound of stone.

The original location monument, a 4 x 4 ins. wood post, projecting 60 ins. above ground, supported by a mound of stone, 3 ft. base, 1 ft. high, is located SSE, 2 1/2 ft.

USFS sign Nos. 54-2 and 54-9, riveted to a steel fence post, are set alongside and S. of the cor.

---

N. 59°57' E., on a portion of line 3-2, Hillcrest # 26 lode.

9.10

Cor. 2, Hillcrest # 25 lode, M.S. 4417A, identical with cor. 4, D & W # 4 lode, M.S. No. 4462, not patented, monumented with a sandstone, 9 ins. x 7 ins., firmly set, projecting 14 ins. above ground, mkd. with an X on top, 2H25 4417A on the ESE. face and 4462 with other illegible weathered marks on the SSW face.

from which

A rotting pine stump, 19 ins. diam., 19 ins. high, bears S. 80° W., 31 lks. dist.

At the corner point

Excavate the mkd. stone, 33 x 9 x 7 ins. and replace with a stainless steel post, 28 ins. long, 2 1/2 ins. diam., set 20 ins. in the ground, in a mound of stone, 2 1/2 ft. base, to top, with brass cap mkd.

Restoring a portion of M.S. No. 4417A,  
T. 11 N., R. 14 E., Gila and Salt River Meridian, Arizona

CHAINS

T 11 N R 14 E  
HC26  
MS4417A

ASNF	C2
S14	HC25
	MS4417A
2018	

Deposit a magnet, in a white plastic case, at the base of the stainless steel post.

Break the marked stone into pieces and incorporate within the mound of stone.

USFS sign Nos. 54-2 and 54-9, riveted to a steel fence post, are set alongside and S. of the cor.

S. 30°22' E., on line 2-1, Hillcrest # 25 lode.

9.08

Cor. 1, Hillcrest # 25 lode, identical with cor. 2, Campbell and Denison No. 7 ext. lode, M.S. No. 4352, identical with cor. 4, Campbell and Denison No. 8 ext. lode, M.S. 4352, identical with cor. 1, D & W # 4 lode, M.S. No. 4462, not patented, monumented with a sandstone, 12 ins. x 8 ins., firmly set, projecting 12 ins. above ground, mkd. with an X on top, 2CD7E on the ESE face, 4CD8E 4352 on the SSW face and 1H25 4417A on the WNW face.

from which

A pine, 20 ins. diam., bears S. 82 1/4° W., 30 lks. dist., with the scribe marks 4417A X BT 2CDE7E 4CDE8E 4352 4462 visible on an open blaze.

At the corner point

Excavate the mkd. stone, 30 x 17 x 8 ins. and replace with a stainless steel post, 28 ins. long, 2 1/2 ins. diam., set 18 ins. in the ground, in a mound of stone, 3 1/2 ft. base, to top, with brass cap mkd.

T 11 N	R 14 E
S14	HC25
ANSF	MS4417A
	C1
C4	C2
CDEXT8	CDEXT7
MS4352	MS4352
2018	

Deposit a magnet, in a white plastic case, at the base of the stainless steel post.

**Restoring a portion of M.S. No. 4417A,  
T. 11 N., R. 14 E., Gila and Salt River Meridian, Arizona**

CHAINS

break the marked stone into pieces and incorporate within the mound of stone.

Remnants of the original location monument, an embedded mound of stone, 4 ft. base, 1/2 ft. high, is located NNW, 5 ft.

USFS sign Nos. 54-2 and 54-9, riveted to a steel fence post, are set alongside and W. of the cor.

---

**Dependent Resurvey of a Portion of Mineral Survey Number 4352,  
T. 11 N., R. 14 E., Gila and Salt River Meridian, Arizona**

---

Restoring a portion of M.S. No. 4352,  
executed by Richard L. Merritt, in 1951

---

S. 59°49' W., on line 4-3, Campbell and Denison No. 13 lode, M.S. No. 4352.

9.09

Cor. 3, Campbell and Denison No. 13 lode, monumented with a sandstone, 9 ins. x 8 ins., firmly set, projecting 6 ins. above ground, mkd. with an X on top, and 3CD13 4352 on the ENE face.

from which a bearing tree established by the USFS

A pine, 30 ins. diam., bears S. 82° W., 32.5 lks. dist., with scribe marks D 35 visible on mostly healed over blaze.

At the corner point

Excavate the mkd. stone, 24 x 9 x 8 ins. and replace with a stainless steel post, 28 ins. long, 2 1/2 ins. diam., set 24 ins. in the ground, with brass cap mkd.

```

T 11 N   R 14 E
  S11    /  CD13
  ASNF  /   C3
        /    MS 4352
        /
      2018
  
```

Deposit a magnet, in a white plastic case, at the base of the stainless steel post.

Bury the mkd. stone alongside the stainless steel post.

The original location monument, a 4 x 4 ins. sq. wood post, projecting 42 ins. above ground, supported by a mound of stone, 3 ft. base, 1 ft. high, is located NW, 3 ft.

Dependent Resurvey of a Portion of Mineral Survey Number 4352,  
T. 11 N., R. 14 E., Gila and Salt River Meridian, Arizona

CHAINS	
4.56	<p>USFS sign Nos. 54-2 and 54-4, riveted to a steel fence post, are set alongside and N. of the cor.</p> <hr/> <p>S. 30°13' E., on a portion of line 3-2, Campbell and Denison No. 13 lode.</p> <p>Cor. 2, D and W # 6 lode, M.S. No. 4417A, monumented with a sandstone, 12 ins. x 8 ins., firmly set, projecting 16 ins. above ground, mkd. with an X on top, and 2DW6 4417A on the SW face.</p> <p>At the corner point</p> <p>Excavate the mkd. stone, 36 x 12 x 8 ins. and replace with a stainless steel post, 28 ins. long, 2 1/2 ins. diam., set 24 ins. in the ground, with brass cap mkd.</p> <div data-bbox="747 787 1039 1039" style="text-align: center;"> <p>T 11 N R 14 E S11 CD13 ASNF MS4352 C2 DW6 MS4417A 2018</p> </div> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p> <p>The original location monument, a 4 x 4 ins. wood post, projecting 48 ins. above ground, supported by a mound of stone, 2 1/2 ft. base, 1 ft. high, is located ENE, 2 1/2 ft.</p> <p>Incorporate the mkd. stone within the location monument mound of stone.</p> <p>USFS sign Nos. 54-2 and 54-4, riveted to a steel fence post, are set alongside the cor.</p> <hr/> <p>From cor. No. 4. Campbell and Dennison No. 8 ext. lode.</p> <p>S. 59°41' W., on line 4-3, Campbell and Dennison No. 8 ext. lode.</p>
9.10	<p>Cor. 3, Campbell and Denison No. 8 ext. lode, identical with cor. 4, Campbell and Denison No. 9 ext. lode, M.S. No.4352, monumented with a sandstone, 16 ins. x 6 ins., firmly set, projecting 9 ins. above ground, mkd. with an X on top, 3CD8E 4352 on the SE face and 4CD9E on the SW face.</p> <p>At the corner point</p>

Dependent Resurvey of a Portion of Mineral Survey Number 4352,  
T. 11 N., R. 14 E., Gila and Salt River Meridian, Arizona

CHAINS

Excavate the mkd. stone, 20 x 16 x 7 ins. and replace with a stainless steel post, 28 ins. long, 2 1/2 ins. diam., set 20 ins. in the ground, in a mound of stone, 2 1/2 ft. base, to top, with brass cap mkd.

T 11 N R 14 E	
ASN	
S14	
-----	
C4	C3
CDEXT9	CDEXT8
MS4352	MS 4352
2018	

Deposit a magnet, in a white plastic case, at the base of the stainless steel post.

Break the marked stone into pieces and incorporate within the mound of stone.

S. 59°42' W., on line 4-3, Campbell and Denison No. 9 ext. lode.

9.09

Cor. 3, Campbell and Denison No. 9 Ext. lode, identical with cor. 4, Campbell and Denison No. 10 lode, M.S. 4352, identical with cor. 2, D & W # 4 lode, M.S. No. 4462, not patented, identical with cor. 2, Miss Lottie # 4 lode, M.S. No. 4462, not patented, monumented with a sandstone, 11 ins. x 6 ins., firmly set, projecting 9 ins. above ground, mkd. with an X on top, DW4 4462 on the N. face, 3CDE9 on the E. face, and 3CD10 on the S. face.

from which

A twin pine, 34 ins. diam., bears S. 59 1/4° E., 82.5 lks. dist., with illegible scribe marks visible on a mostly healed over blaze.

At the corner point

Excavate the mkd. stone, 28 x 12 x 6 ins. and replace with a stainless steel post, 28 ins. long, 2 1/2 ins. diam., set 20 ins. in the ground, in a mound of stone, 2 ft. base, to top, with brass cap mkd.

T 11 N R 14 E	
ASN	
S14	
-----	
C4	C3
CD10	CDEXT9
MS4352	MS4352
2018	


Deposit a magnet, in a white plastic case, at the base of the stainless steel post.



Dependent Resurvey of a Portion of Mineral Survey Number 4352,  
T. 11 N., R. 14 E., Gila and Salt River Meridian, Arizona

CHAINS	<p>Break the marked stone into pieces and incorporate within the mound of stone.</p> <p>The original location monument, a 5 x 5 ins. wood post, projecting 40 ins. above ground, supported by a mound of stone, 3 1/2 ft. base, 1 ft. high, is located NNW, 3 1/2 ft.</p> <hr style="width: 20%; margin: 10px auto;"/> <p>S. 59°39' W., on line 4-3, Campbell and Denison No. 10 lode.</p>										
1.22	<p>Intersect the E. and W. center line of sec. 14.</p> <p>From this point, the calculated 1/4 sec. cor. of secs. 13 and 14, bears N. 89°53' E., 23.53 chs. dist., hereinbefore described.</p> <p>From this same point, the center 1/4 sec. cor. of sec. 14, bears S. 89°53' W., 16.37 chs. dist., hereinbefore described.</p>										
9.11	<p>Cor. 3, Campbell and Denison No. 10 lode, identical with cor. 3, Miss Lottie # 4 lode, not patented, on line 3-4, Campbell and Denison No. 11 lode, M.S. No. 4352, remonumented in M.S. No. 4462, not patented, with a sandstone, 15 ins. x 4 ins., firmly set, projecting 5 ins. above ground, mkd. with an X on top, CD103 4352 on the SE face, 4463 ML4-3 on the NE face.</p> <p>from which</p> <p style="padding-left: 40px;">A pine, 36 ins. diam., bears S. 34 3/4° E., 23.5 lks. dist., with the scribe marks X BT 3CD10 4352 visible, and other illegible scribe marks on an open blaze.</p> <p>At the corner point</p> <p>Excavate the mkd. stone, 24 x 15 x 4 ins. and replace with a stainless steel post, 28 ins. long, 2 1/2 ins. diam., set 20 ins. in the ground, in a mound of stone, 2 1/2 ft. base, to top, with brass cap mkd.</p> <div style="text-align: center; margin: 20px 0;"> <p>T 11 N    R 14 E</p> <table style="margin: auto; border-collapse: collapse;"> <tr> <td style="border-right: 1px solid black; padding: 5px;"></td> <td style="padding: 5px;">S14</td> </tr> <tr> <td style="border-right: 1px solid black; padding: 5px;"></td> <td style="padding: 5px;">ASNF</td> </tr> <tr> <td style="border-right: 1px solid black; padding: 5px;">CD11</td> <td style="padding: 5px;">C3</td> </tr> <tr> <td style="border-right: 1px solid black; padding: 5px;">MS4352</td> <td style="padding: 5px;">CD10</td> </tr> <tr> <td style="border-right: 1px solid black; padding: 5px;"></td> <td style="padding: 5px;">MS4352</td> </tr> </table> <p>2018</p> </div> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p> <p>Break the marked stone into pieces and incorporate within the mound of stone.</p>		S14		ASNF	CD11	C3	MS4352	CD10		MS4352
	S14										
	ASNF										
CD11	C3										
MS4352	CD10										
	MS4352										


Dependent Resurvey of a Portion of Mineral Survey Number 4352,  
T. 11 N., R. 14 E., Gila and Salt River Meridian, Arizona

CHAINS	
	<p>USFS sign Nos. 54-2 and 54-9, riveted to a steel fence post, are set alongside and NNE of the cor.</p> <hr/>
	<p>N. 30°16' W., on a portion of line 4-3, Campbell and Denison No. 11 lode.</p>
4.59	<p>Intersect the E. and W. center line of sec. 14.</p> <p>From this point, the calculated 1/4 sec. cor. of secs. 13 and 14, bears N. 89°53' E., 32.65 chs. dist., hereinbefore described.</p> <p>From this same point, the center 1/4 sec. cor. of sec. 14, bears S. 89°53' W., 7.25 chs. dist., hereinbefore described.</p>
6.05	<p>Cor. 3, Campbell and Denison No. 11, identical with cor. 2, Miss Lottie # 5, M.S. No. 4462, not patented, monumented with a sandstone, 12 ins. x 8 ins., firmly set, projecting 8 ins. above ground, mkd. with an X on top, 3CD11 4352 on the SW face, and other shallow illegible marks on the NE face.</p> <p>from which</p> <p style="padding-left: 40px;">A pine, 34 ins. diam., bears N. 8° E., 29 lks. dist., with illegible scribe marks visible on a mostly healed over blaze.</p>
	<p>At the corner point</p> <p>Excavate the mkd. stone, 24 x 12 x 10 ins. and replace with a stainless steel post, 28 ins. long, 2 1/2 ins. diam., set 26 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center;"> <p>T 11 N R 14 E</p> <p>S14</p> <p>ASNF</p>  <p>2018</p> </div>
	<p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p> <p>Bury the mkd. stone alongside the stainless steel post.</p> <p>Remnants of the original location monument, an embedded mound of stone, 4 ft. base, 1/2 ft. high, is located NNW, 4 ft.</p>
	<p>USFS sign Nos. 54-2 and 54-9, riveted to a steel fence post, are set alongside and NE of the cor.</p> <hr/>

Dependent Resurvey of a Portion of Mineral Survey Number 4352,  
T. 11 N., R. 14 E., Gila and Salt River Meridian, Arizona

CHAINS							
	S. 59°41' W., on line 3-2, Campbell and Denison No. 11 lode.						
2.51	<p>Intersect the E. and W. center line of sec. 14.</p> <p>From this point, the calculated 1/4 sec. cor. of secs. 13 and 14, bears N. 89°53' E., 35.55 chs. dist., hereinbefore described.</p> <p>From this same point, the center 1/4 sec. cor. of sec. 14, bears S. 89°53' W., 4.35 chs. dist., hereinbefore described.</p>						
7.55	<p>Intersect the N. and S. center line of sec. 14.</p> <p>From this point, the center 1/4 sec. cor. of sec. 14, bears N. 0°01' E., 2.54 chs. dist., hereinbefore described.</p> <p>From this same point, the 1/4 sec. cor. of secs. 14 and 23, bears S. 0°01' W., 37.47 chs. dist., hereinbefore described.</p>						
9.10	<p>Cor. 2, Campbell and Denison No. 11 lode, identical with cor. 3, Campbell and Denison No. 12 lode, M.S. No. 4352, identical with cor. 3, Miss Lottie # 5 lode, not patented, identical with cor. 3, Miss Lottie # 6 lode, M.S. No. 4462, not patented, determined from the remains of the original bearing tree.</p> <p style="padding-left: 40px;">A rotting pine stump, 28 ins. diam., 6 ins. high, bears S. 72° E., 72 lks. dist.</p> <p>At the corner point.</p> <p>Recover the original stone, 26 x 16 x 9 ins., lying flat, 12 ins. below the surface, marked 4462 ML-3 on a face, ML-5 and other illegible marks on a face, and CD11 and other illegible marks on a face.</p> <p>Excavate the mkd. stone, and replace with a stainless steel post, 28 ins. long, 2 1/2 ins. diam., set 24 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center; margin: 20px 0;"> <p>T 11 N R 14 E</p> <p>S14</p> <p>ASNF</p> <table style="margin: auto; border-collapse: collapse;"> <tr> <td style="border-right: 1px solid black; padding: 2px 5px;">C3</td> <td style="padding: 2px 5px;">C2</td> </tr> <tr> <td style="border-right: 1px solid black; padding: 2px 5px;">CD12</td> <td style="padding: 2px 5px;">CD11</td> </tr> <tr> <td style="border-right: 1px solid black; padding: 2px 5px;">MS4352</td> <td style="padding: 2px 5px;">MS4352</td> </tr> </table> <p>2018</p> </div> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p> <p>Break the mkd. stone into pieces and bury alongside the stainless steel post.</p> <hr style="width: 20%; margin: 20px auto;"/>	C3	C2	CD12	CD11	MS4352	MS4352
C3	C2						
CD12	CD11						
MS4352	MS4352						

Dependent Resurvey of a Portion of Mineral Survey Number 4352,  
T. 11 N., R. 14 E., Gila and Salt River Meridian, Arizona

CHAINS	
9.10	<p>S. 59°40' W., on line 3-2, Campbell and Denison No. 12 lode.</p> <p>Cor. 2, Campbell and Denison No. 12, identical with cor. 4, Miss Lottie # 6, not patented, monumented with a sandstone, 16 ins. x 5 ins., firmly set, projecting 12 ins. above ground, mkd. ML6 4462 X on top, and 2CD12 4352 on the E. face.</p> <p>from which</p> <p style="padding-left: 40px;">A pine, 30 ins. diam., bears S. 65 1/2° W., 29.5 lks. dist., with the marks D 35, visible on a mostly healed over blaze.</p> <p>At the corner point</p> <p>Excavate the mkd. stone, 24 x 16 x 5 ins. and replace with a stainless steel post, 28 ins. long, 2 1/2 ins. diam., set 20 ins. in the ground, in a mound of stone, 2 1/2 ft. base, to top, with brass cap mkd.</p> <div style="text-align: center; margin: 20px 0;"> <p>T 11 N R 14 E</p>  </div> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p> <p>Break the marked stone into pieces and incorporate within the mound of stone.</p> <p>USFS sign Nos. 54-2 and 54-4, riveted to a steel fence post, are set alongside and W. of the cor.</p>
18.18	<p>S. 30°21' E., on line 4-1, Campbell and Denison No. 12 lode.</p> <p>Intersect the N. and S. center line of sec. 14.</p> <p>From this point, the center 1/4 sec. cor. of sec. 14, bears N. 0°01' E., 23.60 chs. dist., hereinbefore described.</p> <p>From this same point, the 1/4 sec. cor. of secs. 14 and 23, bears S. 0°01' W., 16.41 chs. dist., hereinbefore described.</p>
22.75	<p>Cor. 1, Campbell and Denison No. 12 lode, monumented with a sandstone, 14 ins. x 7 ins., firmly set, projecting 8 ins. above ground, mkd. with an X on top and 1CD12 4352 on the NNE face.</p> <p>from which</p>


Dependent Resurvey of a Portion of Mineral Survey Number 4352,  
T. 11 N., R. 14 E., Gila and Salt River Meridian, Arizona

## CHAINS

A pine, 32 ins. diam., bears S. 65 1/4° E., 40 lks. dist.,  
mkd. X BT CD12 4352 on an open blaze.

At the corner point

Excavate the mkd. stone, 24 x 14 x 7 ins. and replace with a  
stainless steel post, 28 ins. long, 2 1/2 ins. diam., set 20 ins.  
in the ground, in a mound of stone, 2 1/2 ft. base, to top, with  
brass cap mkd.



Deposit a magnet, in a white plastic case, at the base of the  
stainless steel post.

Break the marked stone into two pieces and incorporate within the  
mound of stone.

The original location monument, a 4 x 4 ins. wood post, projecting  
36 ins. above ground, supported by a mound of stone, 4 ft. base,  
1 ft. high, is located SE, 3 1/4 ft.

USFS sign Nos. 54-2 and 54-4, riveted to a steel fence post, are  
set alongside and S. of the cor.

From this cor., cor., 3, Kinder # 3 lode, M.S. No. 4497, not  
patented, bears N. 61° E., 2 lks. dist. Monumented with an iron  
post, 3/4 in. diam., set in concrete, projecting 4 ins. above  
ground, with 2 ins. diam. brass cap mkd MS 4497 3K3.

N. 59°38' E., on line 1-4, Campbell and Dennison No. 12 lode.

7.70 Stellar Drive, graded, 20 ft. wide, bears N. 10° E., curving E.,  
and S. 10° W., onto closed USFS road.

9.10 Cor. 4, Campbell and Denison No. 12 lode, identical with cor. 1,  
Campbell and Denison No. 11 lode, M.S. 4352, monumented with a  
sandstone, 13 ins. x 5 ins., firmly set, projecting 7 ins. above  
ground, mkd. with an X on top, 1CD11 on NNW face and 4CD12 4352  
on the WNW face.

from which

A rotted pine stump, 12 ins. diam., 12 ins. high, bears  
S. 76 3/4° W., 59.5 lks. dist.

Dependent Resurvey of a Portion of Mineral Survey Number 4352,  
T. 11 N., R. 14 E., Gila and Salt River Meridian, Arizona

CHAINS

At the corner point

Excavate the mkd. stone, 24 x 13 x 8 ins. and replace with a stainless steel post, 28 ins. long, 2 1/2 ins. diam., set 20 ins. in the ground, in a mound of stone, 2 1/2 ft. base, to top, with brass cap mkd.

T 11 N	R 14 E
CD12	CD11
MS4352	MS4352
C4	C1

S14  
ASNF  
2018

Deposit a magnet, in a white plastic case, at the base of the stainless steel post.

Break the marked stone into two pieces and incorporate within the mound of stone.

The original location monument, a 6 x 6 ins. wood post, projecting 36 ins. above ground, supported by a mound of stone, 3 ft. base, 1 ft. high, is located SE, 4 ft.

USFS sign Nos. 54-2 and 54-4, riveted to a steel fence post, are set alongside and S. of the cor.

From this cor., cor., 3, Kinder # 2 lode, identical with cor. 4, Kinder # 3 lode, both of M.S. No. 4497, not patented, bears N. 60° E., 1 lks. dist. Monumented with an iron post, 3/4 in. diam., set in concrete, projecting 3 ins. above ground, with 2 ins. diam. brass cap mkd MS 4497 4K3 3K2.

N. 59°43' E., on line 1-4, Campbell and Denison No. 11 lode.

7.50 From this point, woven wire fence, attached to lot 783, Forest Lakes Estates Unit Ten, drifts onto ASNF.

9.10 Cor. 4, Campbell and Denison No. 11 lode, identical with cor. 4, Kinder # 2 lode, not patented, on line 2-3, Campbell and Denison No. 10 lode, M.S. No. 4352., monumented with a sandstone, 12 ins. x 9 ins., firmly set, projecting 16 ins. above ground, mkd. with an X on top and 4CD11 4352 4497 on the N. face.

from which


A pine, 36 ins. diam., bears S. 82 3/4° E., 72 lks. dist.,  
mkd. X BT 4CD11 4352 on an open blaze.

At the corner point

Dependent Resurvey of a Portion of Mineral Survey Number 4352,  
T. 11 N., R. 14 E., Gila and Salt River Meridian, Arizona

## CHAINS

Excavate the mkd. stone, 32 x 12 x 9 ins. and replace with a stainless steel post, 28 ins. long, 2 1/2 ins. diam., set 20 ins. in the ground, in a mound of stone, 3 ft. base, to top, with brass cap mkd.



Deposit a magnet, in a white plastic case, at the base of the stainless steel post.

Break the marked stone into pieces and incorporate within the mound of stone.

The original location monument, a 4 x 2 ins. wood post, projecting 36 ins. above ground, supported by a mound of stone, 3 1/2 ft. base, 1 ft. high, is located SSE, 3 ft.

USFS sign Nos. 54-2 and 54-4, riveted to a steel fence post, are set alongside and WSW. of the cor.

Cor. is located on the NNW side (in yard), of a woven wire fence, extends N. 60° E. and S. 60° W.

S. 30°19' E., on a portion of line 3-2, Campbell and Denison No. 10 lode.

6.06

Cor. 2, Campbell and Denison No. 10 lode, identical with cor. 3, Kinder # 1 lode, M.S. No. 4497, not patented, monumented with a sandstone, 16 ins. x 8 ins., firmly set, projecting 10 ins. above ground, mkd. with an X on top, and 2CD10 4352 on ENE face.

from which


A pine stump, 22 ins. diam., 48 ins. high, bears N. 62 3/4° W., 31.5 lks. dist., mkd. X BT 2CD10 4352 on an open blaze.

At the corner point

Excavate the mkd. stone, 30 x 16 x 8 ins. and replace with a stainless steel post, 28 ins. long, 2 1/2 ins. diam., set 24 ins. in the ground, encircled with a collar of stone, with brass cap mkd.

Dependent Resurvey of a Portion of Mineral Survey Number 4352,  
T. 11 N., R. 14 E., Gila and Salt River Meridian, Arizona

CHAINS

T 11 N R 14 E  
  
 S14  
 ASNF  
 2018

Deposit a magnet, in a white plastic case, at the base of the stainless steel post.

Break the mkd. stone into pieces and bury alongside the cor.

USFS sign Nos. 54-2 and 54-4, riveted to a steel fence post, are set alongside and S. of the cor.

From this cor., an iron pipe 1 in. diam., firmly set, projecting 2 ins. above ground, bears S. 60° E., 2 lks. dist., origin unknown.

From this same point, a 1/2 in. diam. rebar, with blank 1 1/2 ins. diam., aluminum cap, firmly set, projecting 1 in. above ground, bears S. 75° W., 7 lks. dist., origin unknown.

---

N. 59°40' E., on line 2-1, Campbell and Denison No. 10 lode.

9.10

Cor. 1, Campbell and Denison No. 10 lode, identical with cor. 2, Campbell and Denison Ext. No. 9 lode, M.S. No. 4352, identical with cor. 2, Campbell and Denison No. 9 lode, M.S. No. 4352, identical with cor. 4, Kinder # 1 lode, not patented, monumented with a sandstone, 14 ins. x 6 ins., firmly set, projecting 14 ins. above ground, mkd. X K14 on top, 2CD9E on the NNE face, 1CD10 on the WSW face, 4497 on the SSW, 2CD9 4352 on the ESE face.

from which

A pine stump, 23 ins. diam., 12 ins. high, bears S. 52° W., 38.5 lks. dist.

At the corner point

Excavate the mkd. stone, 30 x 14 x 6 ins. and replace with a stainless steel post, 28 ins. long, 2 1/2 ins. diam., set 20 ins. in the ground, in a mound of stone, 2 1/2 ft. base, to top, with brass cap mkd.



Dependent Resurvey of a Portion of Mineral Survey Number 4352,  
T. 11 N., R. 14 E., Gila and Salt River Meridian, Arizona

CHAINS																			
	<table border="0"> <tr> <td>T 11 N</td> <td>R 14 E</td> </tr> <tr> <td>CD10</td> <td>CDEXT9</td> </tr> <tr> <td>MS4352</td> <td>MS4352</td> </tr> <tr> <td>C1</td> <td>C2</td> </tr> <tr> <td colspan="2"><hr/></td> </tr> <tr> <td>ASNF</td> <td>C2</td> </tr> <tr> <td>S14</td> <td>CD9</td> </tr> <tr> <td></td> <td>MS4352</td> </tr> <tr> <td></td> <td>2018</td> </tr> </table>	T 11 N	R 14 E	CD10	CDEXT9	MS4352	MS4352	C1	C2	<hr/>		ASNF	C2	S14	CD9		MS4352		2018
T 11 N	R 14 E																		
CD10	CDEXT9																		
MS4352	MS4352																		
C1	C2																		
<hr/>																			
ASNF	C2																		
S14	CD9																		
	MS4352																		
	2018																		
	<p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p> <p>Break the marked stone into pieces and incorporate within the mound of stone.</p> <p>USFS sign Nos. 54-2 and 54-4, riveted to a steel fence post, are set alongside and WSW. of the cor.</p> <hr style="width: 20%; margin: 10px auto;"/> <p>S. 30°19' E., on line 2-1, Campbell and Denison No. 9 lode.</p>																		
2.75	Old Rim road, graded, 20 ft. wide, bears N. 75° E. and S. 75° W.																		
3.00	Power line, bears N. 75° E. and S. 75° W.																		
21.25	From this point, the northerly end of a 10 ft. long, 3 ft. diam., cylindrical propane tank, bears S. 59°41' W., 1.5 lks. dist. The long axis of the tank bears S. 25° E.																		
21.40	From this point, the southerly end of same cylindrical propane tank, bears S. 59°41' W., 3.0 lks. dist.																		
21.72	Intersect the line bet. secs. 13 and 14.																		
	<p>From this point, the calculated 1/4 sec. cor. of secs. 13 and 14, bears N. 0°01' E., 37.82 chs. dist.</p> <p>From this same point, the cor. of secs. 13, 14, 23 and 24, bears S. 0°01' W., 2.17 chs. dist., hereinbefore described.</p> <p>Continuing measurement in sec. 13.</p>																		
22.74	<p>Cor. 1, Campbell and Denison No. 9 lode, identical with cor. 1, Kinder # 1 lode, not patented, monumented with a sandstone, 11 ins. x 6 ins., firmly set, projecting 12 ins. above ground, mkd. K11 X on top and 1CD9 4352 on the NNE face.</p> <p>from which</p> <p style="padding-left: 40px;">A pine, 21 ins. diam., bears S. 41 1/2° W., 54 lks. dist., mkd. X BT 1CD9 4352, on an open blaze.</p> <p>At the corner point</p>																		

Dependent Resurvey of a Portion of Mineral Survey Number 4352,  
T. 11 N., R. 14 E., Gila and Salt River Meridian, Arizona

## CHAINS

Excavate the mkd. stone, 27 x 12 x 6 ins. and replace with a stainless steel post, 28 ins. long, 2 1/2 ins. diam., set 20 ins. in the ground, in a mound of stone, 3 ft. base, to top, with brass cap mkd.

T 11 N R 14 E  
CD9  
MS 4352  
C1  
ASNF  
S13  
2018

Deposit a magnet, in a white plastic case, at the base of the stainless steel post.

Break the mkd. stone into 4 pieces and bury alongside the cor.

The original location monument, a 4 x 4 ins. sq. wood post, projecting 48 ins. above ground, supported by a mound of stone, 3 1/2 ft. base, 1 ft. high, is located WSW, 2 ft.

USFS sign Nos. 54-2 and 54-4, riveted to a steel fence post, are set alongside and S. of the cor.

From this cor., a 1 in. diam., iron pipe, flush with the ground, bears N. 65° W., 1.26 lks. dist., origin unknown.

N. 59°42' E., on line 1-4, Campbell and Denison No. 9 lode.

9.11 Cor. 4, Campbell and Denison No. 9 lode, identical with cor. 1, Campbell and Denison No. 8 lode, M.S. No. 4352, identical with cor. 1, Little Pine # 6 lode, M.S. No. 4449, monumented with a sandstone, 13 ins. x 4 ins., firmly set, projecting 15 ins. above ground, mkd. with an X on top, 1CD8 4352 on the NE face, 1LP6 4449 on the SW face, and 4CD9 on the NNW face.

Note: Little Pine # 6 lode, was excluded from the patent granted to M.S. 4449.

from which

A pine, 26 ins. diam., bears S. 7 3/4° E., 32 lks. dist., mkd. X BT 4CD9 1CD8 4352 LP6 4449, on an open blaze.

At the corner point

Excavate the mkd. stone, 31 x 13 x 5 ins. and replace with a stainless steel post, 28 ins. long, 2 1/2 ins. diam., set 20 ins. in the ground, in a mound of stone, 2 1/2 ft. base, to top, with brass cap mkd.

Dependent Resurvey of a Portion of Mineral Survey Number 4352,  
T. 11 N., R. 14 E., Gila and Salt River Meridian, Arizona

CHAINS

T 11 N	R 14 E
CD9	CD8
MS 4352	MS 4352
C4	C1
S13	
ANSF	
2018	

Deposit a magnet, in a white plastic case, at the base of the stainless steel post.

Break the mkd. stone into pieces and incorporate into the mound of stone.

Remnants of the original location monument, a mound of stone, 3 ft. base, 1 ft. high, is located S., 4 ft.

N. 59°43' E., on line 1-4, Campbell and Denison No. 8 lode.

9.09

Cor. 4, Campbell and Denison No. 8 lode, identical with cor. 4, Campbell and Denison No. 7 lode, M.S. 4352, identical with cor. 3, Little Pine # 5 lode, M.S. No. 4449, identical with cor. 2, Little Pine # 6 lode, monumented with a sandstone, 14 ins. x 5 ins., firmly set, projecting 14 ins. above ground, mkd. with an X on top, 4CD7 4352 on the N. face, 2LP6 on the S. face and 4CD8 on the W. face.

Note: Little Pine # 6 lode, was excluded from the patent granted to M.S. 4449.

from which

A pine, 26 ins. diam., bears S. 23 1/4° E., 42.5 lks. dist., with the marks CD CD 435, visible on a partially healed blaze.

At the corner point

Excavate the mkd. stone, 30 x 14 x 5 ins. and replace with a stainless steel post, 28 ins. long, 2 1/2 ins. diam., set 24 ins. in the ground, encircled with a collar of stone, with brass cap mkd.


T 11 N	R 14 E
CD8	CD7
MS 4352	MS 4352
C4	C4
ANSF	
S13	C2
	LP5
	MS 4449
2018	

Dependent Resurvey of a Portion of Mineral Survey Number 4352,  
T. 11 N., R. 14 E., Gila and Salt River Meridian, Arizona

CHAINS	
	<p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p> <p>Break the mkd. stone into pieces and use as backfill around the stainless steel post.</p> <p>USFS sign Nos. 54-2 and 54-4, riveted to a steel fence post, are set alongside and SW of the cor.</p>
	<hr/> <p style="text-align: center;"><b>Dependent Resurvey of a Portion of Mineral Survey No. 4449, T. 11 N., R. 14 E., Gila and Salt River Meridian</b></p> <hr/>
	<p style="text-align: center;">Restoring a portion of M.S. No. 4449 executed by Richard L. Merritt, in 1958</p> <hr/>
	<p>S. 30°22' E., on a portion of line 2-3, Little Pine # 5 lode.</p>
12.15	<p>Intersect the line bet. secs. 13 and 24.</p> <p>From this point, the 1/4 sec. cor. of secs. 13 and 24, bears S. 89°58' E., 17.69 chs. dist., hereinbefore described.</p> <p>From this same point, the cor. of secs. 13, 14, 23 and 24, bears N. 89°58' W., 22.37 chs. dist., hereinbefore described.</p> <p>From this point, Arizona State Highway No. 260, point on curve, sta. 1705+97.81, at the intersection of the northerly right-of-way with line 4-1, Little Pine # 3 lode, bears S. 59°35' W., 1.17 chs. dist., hereinafter described.</p> <p>Continuing measurement in sec. 24.</p>
16.26	<p>A rebar 5/8 in. diam., firmly set, projecting 4 ins. above ground, with attached 1 1/2 ins. diam., aluminum cap, mkd US 323 324, as shown on Forest Lakes Estates Unit Five.</p>
22.74	<p>Cor. 2, Little Pine # 5 lode, identical with cor. 3, Little Pine # 6 lode, not patented, identical with cor. 4, Hillcrest No. 12 lode, M.S. No. 4360, determined from the remains of the orig. bearing tree.</p> <p style="text-align: center;">A rotting pine stump, 30 ins. diam., 96 ins. high, bears S. 78 1/4° W., 37 lks. dist.</p> <p>At the corner point</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p>

Dependent Resurvey of a Portion of Mineral Survey No. 4449,  
T. 11 N., R. 14 E., Gila and Salt River Meridian

CHAINS



Deposit a magnet, in a white plastic case, at the base of the stainless steel post.

Set a steel fence post, 1 lk. SSE of the cor.

Remnants of the original location monument, an embedded mound of stone, 3 ft. base, 1/2 ft. high, with a 42 x 6 x 3 ins. wood post lying loose alongside, is located WSW, 3 ft.

The original cor., was found lying loose alongside the bearing tree. A sandstone 25 x 5 x 5 ins., mkd. 3LP6 4449 on a face, 4H12 4360 on the opposite face and 2LP5 on an adjacent face. Removed from area, impracticable to bury alongside.

---

Dependent Resurvey of a Portion of Mineral Survey No. 4360,  
T. 11 N., R. 14 E., Gila and Salt River Meridian

---

Restoring a portion of M.S. No. 4360 executed by  
Richard L. Merritt, in 1951

---

S. 30°22' E., on line 4-3, Hillcrest No. 12 lode.

0.63 Arizona State Highway No. 260, POT station 1671+99.04, at intersection with the northerly right-of-way, monumented with a rebar, 5/8 in. diam., flush with the surface as shown on the plat of Forest Lakes Estates Unit Eleven.

---

S. 30°10' E., beginning new measurement.

1.18 Northerly edge of shoulder, Arizona State Highway No. 260, bears N. 80° E. and S. 80° W.


1.99 Southerly edge of shoulder, Arizona State Highway No. 260, bears N. 80° E. and S. 80° W.

3.24 Arizona State Highway No. 260, POT station 1672+74.62, at intersection with the southerly right-of-way, identical with the NW cor. of lot 887, Forest Lakes Estates Unit Eleven, monumented with a rebar, 5/8 in. diam., firmly set, projecting 2 ins. above ground, with attached 1 1/2 ins. diam. aluminum cap, mkd. US ROW 887, as shown on the plat of Forest Lakes Estates Unit Eleven.

Dependent Resurvey of a Portion of Mineral Survey No. 4360,  
T. 11 N., R. 14 E., Gila and Salt River Meridian

CHAINS	
5.22	<p>S. 30°24' E., beginning new measurement.</p> <p>Cor. 3, Hillcrest No. 12 lode, monumented with a sandstone, 11 ins. x 5 ins., firmly set, projecting 12 ins. above ground, mkd. with an X on top and 3H12 4360 on the NNE face.</p> <p>At the corner point</p> <p>Excavate the mkd. stone, 28 x 11 x 5 ins. and replace with a stainless steel post, 28 ins. long, 2 1/2 ins. diam., set 20 ins. in the ground, in a mound of stone, 2 1/2 ft. base, to top, with brass cap mkd.</p> <div data-bbox="787 730 1068 913" style="text-align: center;"> <p>T 11 N R 14 E</p> <p>HC12</p> <p>MS4360</p> <p>S24 C3</p> <p>ASNF</p> <p>2018</p> </div> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p> <p>Break the mkd. stone into pieces and incorporate into the mound of stone.</p> <p>Remnants of the original location monument, a mound of stone, 2 ft. base, 1 ft. high, is located alongside and E. of the cor.</p> <p>USFS sign Nos. 54-2 and 54-9, riveted to a steel fence post, are set alongside and S. of the cor.</p>
8.99	<p>N. 59°39' E., on a portion of line 3-2, Hillcrest No. 12 lode.</p> <p>Intersect the N. and S. center line of sec. 24.</p> <p>From this point, the center 1/4 sec. cor. of sec. 24, bears S. 0°02' E., 27.52 chs. dist., hereinbefore described.</p> <p>From this same point, the 1/4 sec. cor. of secs. 13 and 24, bears N. 0°02' W., 12.43 chs. dist., hereinbefore described.</p>
13.797	<p>Arizona State Highway No. 260, POT station 1682+48.74, at intersection with the southerly right-of-way, monumented with a rebar, 5/8 in. diam., firmly set, projecting 1 ins. above ground, with attached 1 1/2 ins. diam. aluminum cap, mkd. RW 889 US, as shown on the plat of Forest Lakes Estates Unit Eleven. A 1 in. diam., iron pipe, firmly set, projecting 24 ins. above ground, is SSE, 1 lk.</p>

Dependent Resurvey of a Portion of Mineral Survey No. 4360,  
T. 11 N., R. 14 E., Gila and Salt River Meridian



CHAINS	
	<p>This cor., now functions as a witness cor., to cor. 3, Hillcrest No. 11 lode, M.S. 4360. Add the marks WC BLM 2018, to the aluminum cap.</p>
17.13	<p>Southerly edge of shoulder, Arizona State Highway No. 260, bears N. 80° E. and S. 80° W.</p>
18.20	<p>Point for cor. 3, Hillcrest No. 11 lode, on line 3-4, Hillcrest No. 12 lode. Reestablished at the extension of the line from cor. 3, Hillcrest No. 12 lode thru POT station 1682+48.74, intersecting with the extension of the line from cor. 2, Hillcrest No. 11, hereinafter described, thru POT sta. 1685+58.44, hereinafter described. There is no remaining evidence of the orig. cor. Point lands within the pavement of Arizona State Highway No. 260, where a permanent monument is impracticable.</p> <hr/> <p>S. 30°23' E., on line 3-2, Hillcrest No. 11 lode.</p> <p>Across pavement of Arizona State Highway No. 260.</p>
1.668	<p>Arizona State Highway No. 260, POT station 1685+58.44, at intersection with the southerly right-of-way. Monumented with a rebar, 5/8 in. diam., firmly set, projecting 2 ins. above ground, with attached 1 1/2 ins. diam. aluminum cap, mkd. RW US 890, as shown on the plat of Forest Lakes Estates Unit Eleven.</p> <p>This cor., now functions as a witness cor., to cor. 3, Hillcrest No. 11 lode, hereinbefore described. Add the marks WC BLM 2018, to the aluminum cap, and encircle with a collar of stone.</p>
9.100	<p>Cor. 2, Hillcrest No. 11 lode, monumented with a sandstone, 7 x 3 ins., firmly set, projecting 3 ins. above ground, mkd. with an X on top and 2H11 4360 on the NNE face. from which</p> <p style="padding-left: 40px;">A pine stump, 24 ins. diam., 20 ins. high, bears S. 44 1/2° E., 53 lks. dist.</p> <p>At the corner point</p> <p>Excavate the mkd. stone, 23 x 16 x 4 ins. and replace with a stainless steel post, 28 ins. long, 2 1/2 ins. diam., set 21 ins. in the ground, encircled with a collar of stone, with brass cap mkd.</p> <div style="text-align: center; margin-top: 20px;"> <p>T 11 N R 14 E</p> <p>S24      HC11</p> <p>            MS4360</p> <p>            C2</p> <p>            ASNF</p> <p>            2018</p>  </div>

Dependent Resurvey of a Portion of Mineral Survey No. 4360,  
T. 11 N., R. 14 E., Gila and Salt River Meridian


CHAINS	
	<p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p>
	<p>The marked stone was taken by the adjacent property owner as a memento.</p>
	<p>USFS sign Nos. 54-2 and 54-9, riveted to a steel fence post, are set alongside and SSW of the cor.</p>
	<hr/> <p>N. 59°37' E., on line 2-1, Hillcrest No. 11 lode.</p>
18.466	<p>Arizona State Highway No. 260, POC station 1698+77.86, at intersection with the southerly right-of-way, monumented with a rebar, 5/8 in. diam., firmly set, projecting 3 ins. above ground, with attached 1 1/2 ins. diam. aluminum cap, mkd. RW 895 US, as shown on the plat of Forest Lakes Estates Unit Eleven. USFS sign Nos. 54-2 and 54-4, riveted to a steel fence post, are set alongside and SSE of the cor.</p>
	<p>This cor., now functions as a witness cor., to cor. 1, Hillcrest No. 11 lode, Add the marks WC BLM 2018, to the aluminum cap. Raise a mound of stone, 2 ft. base, 1 ft. high SSE of cor.</p>
21.25	<p>Southerly edge of shoulder, Arizona State Highway No. 260, in curve, tangents bear E. and S. 80° W.</p>
22.724	<p>Point for cor. 1, Hillcrest No. 11 lode, Reestablished at the extension of the line from cor. 2, Hillcrest No. 11 lode, thru POC station 1698+77.86, intersecting with the extension of the line from cor. 4, Hillcrest No. 11 lode, hereinafter described, thru POC station 1700+95.86, hereinafter described. There is no remaining evidence of the orig. cor. Point lands within the shoulder of Arizona State Highway No. 260, where a permanent monument is impracticable.</p>
	<hr/> <p>N. 30°26' W., on line 1-4, Hillcrest No. 11 lode.</p>
1.379	<p>Arizona State Highway No. 260, POC station 1700+95.86, at intersection with the northerly right-of-way, monumented with a rebar, 5/8 in. diam., firmly set, projecting 3 ins. above ground, as shown on the plat of Forest Lakes Estates Unit Eleven, with a rebar 1/2 in. diam., projecting 11 ins. above ground, set alongside.</p> <p>At the corner point.</p> <p>Attach a 2 ins. diam. brass cap, to the 5/8 diam. rebar, encircle with a collar of stone, set a steel fence post, 1 lk. ENE, brass cap mkd.</p>



Dependent Resurvey of a Portion of Mineral Survey No. 4360,  
T. 11 N., R. 14 E., Gila and Salt River Meridian

CHAINS	
	
	<p>This cor., now functions as a witness cor., to cor. 1, Hillcrest No. 11 lode.</p>
<p>4.79</p>	<p>Intersect the line bet. secs. 13 and 24.</p> <p>From this point, the cor. of secs. 13, 18, 19 and 24, on the E. bdy. of the Tp., bears S. 89°59' E., 10.37 chs. dist., hereinbefore described.</p> <p>From this same point, the 1/4 sec. cor. of secs. 13 and 24, bears N. 89°59' W., 29.73 chs. dist., hereinbefore described.</p> <p>Continuing measurement in sec. 13.</p>
<p>9.08</p>	<p>Cor. 4, Hillcrest No. 11 lode, on line 3-4, Hillcrest No. 9 lode, M.S. No. 4360, monumented with a sandstone, 14 ins. x 4 ins., firmly set, projecting 14 ins. above ground, mkd. with an X on top and 4H11 4360 on the S. face.</p> <p>from which</p> <p style="padding-left: 40px;">A pine, 32 ins. diam., bears N. 9 1/2° W., 36.5 lks. dist., with a healed blaze.</p> <p>At the corner point</p> <p>Excavate the mkd. stone, 32 x 14 x 4 ins. and replace with a stainless steel post, 28 ins. long, 2 1/2 ins. diam., set 24 ins. in the ground, with brass cap mkd.</p>  <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p> <p>Break the mkd. stone into pieces and bury alongside the cor.</p>

Dependent Resurvey of a Portion of Mineral Survey No. 4360,  
T. 11 N., R. 14 E., Gila and Salt River Meridian

CHAINS	
	<p>Remnants of the original location monument, a mound of stone, 3 ft. base, 1 ft. high, is located alongside and N. of cor.</p>
	<p>USFS sign Nos. 54-2 and 54-9, riveted to a steel fence post, are set SSE, 2 ft. dist.</p>
	<p>N. 59°41' E., on a portion of line 4-3, Hillcrest No. 9 lode.</p>
4.00	<p>Merzville Road, graded, 25 ft. wide, bears N. 35° E. and S. 35° W.</p>
4.56	<p>Cor. 3, Hillcrest No. 9 lode, on line 1-2, Little Pine # 3 lode, M.S. No. 4448, monumented with a sandstone, 10 ins. x 4 ins., firmly set, projecting 15 ins. above ground, mkd. with an X on top and 3H9 4360 on the NW face.</p>
	<p>from which</p>
	<p>A pine stump, 18 ins. diam., 12 ins. high, bears N. 30° E., 54 lks. dist.</p>
	<p>At the corner point</p>
	<p>Excavate the mkd. stone, 30 x 10 x 4 ins. and replace with a stainless steel post, 28 ins. long, 2 1/2 ins. diam., set 20 ins. in the ground, in a mound of stone, 2 1/2 ft. base, to top, with brass cap mkd.</p>
	
	<p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p>
	<p>Break the mkd. stone into pieces and incorporate into the mound of stone.</p>
	<p>Remnants of the original location monument, a mound of stone, 3 ft. base, 1 ft. high, with a 6 x 4 ins. wood post, 48 ins. long, lying loose nearby, is located alongside and ENE of the cor.</p>
	<p>USFS sign Nos. 54-2 and 54-4, riveted to a steel fence post, are set alongside and S. of the cor.</p>
	<p>From this cor. point, cor. 2, Hillcrest No. 9 lode, monumented with a sandstone, 10 ins. x 5 ins., firmly set, projecting 5 ins.</p>

Dependent Resurvey of a Portion of Mineral Survey No. 4360,  
T. 11 N., R. 14 E., Gila and Salt River Meridian

CHAINS	
	<p>above ground, mkd. with an X on top and 2H9 4360 on the NW face, bears N. 30°23' W., 9.09 chs. dist.</p> <hr/> <p style="text-align: center;"><b>Dependent Resurvey of a Portion of Mineral Survey No. 4448, T. 11 N., R. 14 E., Gila and Salt River Meridian</b></p> <hr/> <p style="text-align: center;">Restoring a portion of M.S. No. 4448, executed by Richard L. Merritt, in 1958</p> <hr/> <p>S. 30°23' E., on a portion of Little Pine # 3 lode.</p>
6.96	<p>Intersect the line bet. secs. 13 and 24.</p> <p>From this point, the cor. of secs. 13, 18, 19 and 24, on the E. bdy. of the Tp., bears S. 89°59' E., 5.08 chs. dist., hereinbefore described.</p> <p>From this same point, the 1/4 sec. cor. of secs. 13 and 24, bears N. 89°59' W., 35.02 chs. dist., hereinbefore described.</p> <p>Continuing measurement in sec. 24.</p>
7.71	<p>Merzville Road, 28 ft. wide, in curve, tangents extend S. 43° E. and N. 37° W.</p>
9.89	<p>Intersect the northerly right-of-way of Arizona State Highway No. 260, at POC sta. 1704+27.35. On the arc of a circular to the right, having a central angle of 5°33'38", a radius of 15100.0 ft. The point of tangency bears S. 89°26' E., 36.44 chs. dist. The calculated point of curvature bears S. 83°10' W., 22.20 chs. dist.</p>
11.05	<p>Point for cor. 1, Little Pine # 3 lode. Reestablished at the extension of the line from cor. 2, Hillcrest No. 9 lode, on line 1-2, Little Pine # 3 lode, thru cor. 3, Hillcrest No. 9 lode, intersecting with the extension of the line from cor. 4, Little Pine # 3, identical with cor. 1, Little Pine # 2 lode, M.S. No. 4448, thru POC station 1705+97.81. There is no remaining evidence of the cor. established in the survey of Forest Lakes Estates Unit Four.</p> <p>Set a cotton picker spindle flush with the pavement.</p> <p>Cor. is located within the Arizona State Highway No. 260, right of way, at the intersection of the N. shoulder of Arizona State Highway No. 260, with the right turn lane of Merzville road.</p> <hr/> <p>N. 59°35' E., on a portion of line 1-4, Little Pine # 3 lode, within Arizona State Highway No. 260, right-of-way.</p>

Dependent Resurvey of a portion of M.S. No. 4448,  
T. 11 N., R. 14 E., Gila and Salt River Meridian, Arizona

<p>CHAINS</p> <p>2.30</p> <p>3.49</p>	<p>Intersect the northerly right-of-way of Arizona State Highway No. 260, at POC sta. 1705+97.81, monumented with a rebar, 5/8 in. diam., firmly set, projecting 2 ins. above ground, with attached brass washer, stamped LS 34555. Reestablished by William Ingram, Arizona RLS No. 34555, date unknown. Accepted as a bona fide reestablishment of the original cor.</p> <p>Exit, Arizona State Highway No. 260, right-of-way.</p> <p>Intersect the line bet. secs. 19 and 24, on the E. bdy. of the Tp.</p> <p>From this point, the cor. of secs. 13, 18, 19 and 24, bears North, 1.76 chs. dist., hereinbefore described.</p> <p>From this same point, the 1/4 sec. cor. of secs. 19 and 24, bears South, 38.16 chs. dist., hereinbefore described.</p> <p>From this same point, cor. 4, Little Pine # 3 lode, identical with cor. 1, Little Pine # 2 lode, M.S. No. 4448, bears N. 59°35' E., 5.59 chs. dist., as described in the dependent resurvey of certain mineral surveys, in T. 11 N., R. 15 E., executed concurrently under this same group.</p> <hr/> <p style="text-align: center;"><b>GENERAL DESCRIPTION</b></p> <hr/> <p>The area surveyed and resurveyed is located about 30 miles ENE of Payson Arizona. Access is provided by Arizona State Highway No. 260, Coconino County roads within the Forest Lakes platted subdivisions and U.S. Forest Service roads numbers 99 and 179.</p> <p>The elevation ranges from 7400 to 7700 ft. above sea level. The entire area surveyed is within Ponderosa Pine forest, with pinyon pine and oak subspecies. The terrain is rolling, with two canyons of note: St. Joes Canyon and Long Tom Canyon.</p> <p>The mean magnetic declination 10° E., was derived from the National Oceanic and Atmospheric Administration, magnetic field calculator, using the World Magnetic Model 2014-2019.</p> <hr/>
---------------------------------------	--



CERTIFICATE OF SURVEY

I, Gordon R. Bubel, Cadastral Surveyor, HEREBY CERTIFY upon honor, that in pursuance of special instructions bearing date of the 5th day of July, 2017. I have dependently resurveyed a portion of the east boundary, portions of the subdivisional lines, portions of Mineral Survey numbers 4352, 4360, 4417A, 4417B, 4448, 4449, and subdivided sections 11, 12, 13, 14 and 24, in Township 11 North, Range 14 East, of the Gila and Salt River Meridian, in the State of Arizona. Represented in the foregoing field notes as having been executed by me and under my direction. Said survey has been made in strict conformity with said special instructions, the Manual of Instructions for the Survey of the Public Lands of the United States, 2009, and in specific manner described in the foregoing field notes.

4/27/2020  
(Date)

Gordon R. Bubel  
(Cadastral Surveyor)

CERTIFICATE OF APPROVAL

BUREAU OF LAND MANAGEMENT  
Phoenix, Arizona

The foregoing field notes of the dependent resurvey of a portion of the east boundary, portions of the subdivisional lines, portions of Mineral Survey numbers 4352, 4360, 4417A, 4417B, 4448, 4449, and the subdivision of sections 11, 12, 13, 14 and 24, in T. 11 N., R. 14 E., Gila and Salt River Meridian, in the State of Arizona, executed by Gordon R. Bubel, Cadastral Surveyor, having been critically examined and found correct, are hereby approved.

4/27/2020  
(Date)

William A. [Signature]  
(Chief Cadastral Surveyor of Arizona)

CERTIFICATE OF TRANSCRIPT

I CERTIFY that the foregoing transcript of the field notes of the above described surveys in T. 11 N., R. 14 E., Gila and Salt River Meridian, in the state of Arizona, is a true copy of the original field notes.

\_\_\_\_\_  
(Date)

\_\_\_\_\_  
(Chief Cadastral Surveyor of Arizona)