

ORIGINAL

**UNITED STATES  
DEPARTMENT OF THE INTERIOR  
BUREAU OF LAND MANAGEMENT**

FIELD NOTES

OF THE DEPENDENT RESURVEY

OF A PORTION OF THE WEST BOUNDARY,

AND PORTIONS OF THE SUBDIVISIONAL LINES

AND

THE SUBDIVISION OF SECTIONS 18, 19 AND 30,

**TOWNSHIP 6 SOUTH, RANGE 4 WEST,**

OF THE GILA AND SALT RIVER MERIDIAN,

IN THE STATE OF ARIZONA.

**EXECUTED BY**

**Gordon R. Bubel, Cadastral Surveyor**

Under Special Instructions dated September 21, 2020, approved September 21, 2020, which provided for the surveys included under Group No. 1210, and assignment instructions dated September 21, 2020.

**Survey commenced September 22, 2020**

**Survey completed October 21, 2020**

# INDEX DIAGRAM

TOWNSHIP 6 SOUTH                      RANGE 4 WEST  
GILA & SALT RIVER MERIDIAN, ARIZONA

6	5	4	3	2	1
7	8	9	10	11	12
4 18	17	16	15	14	13
12 5 19 11 10	20	21	22	23	24
6 30 9 9	29	28	27	26	25
31	32	33	34	35	36

Subdivision of Section 18..... Pages 13-15  
Subdivision of Section 19..... Pages 15-16  
Subdivision of Section 30..... Pages 16-17

## T. 6 S., R. 4 W., Gila and Salt River Meridian, Arizona

## CHAINS

The following field notes describe the dependent resurvey of a portion of the west boundary. The dependent resurvey of portions of the subdivisional lines. The subdivision of sections 18, 19 and 30, Township 6 South, Range 4 West, Gila and Salt River Meridian, Arizona.

The history pertaining to this survey and resurvey is as follows: Daniel Drummond, U.S. Deputy Surveyor, surveyed the west boundary and subdivisional lines in 1891.

The following aliquot parts, in T. 6 S., R. 4 W., were acquired by the U.S. (1) Lots 1 and 2, and the E 1/2 of the NW 1/4, section 30, conveyed via quit claim deed, recorded in the Maricopa County Recorder's Office in book 375, page 255, on January 26, 1943. (2) Lots 3 and 4, and the E 1/2 of the SW 1/4, section 18. Conveyed via warranty deed, recorded in the Maricopa County Recorder's Office in book 379, page 425, on Feb. 4, 1943. (3) Lots 1 and 2, and the E 1/2 of the NW 1/4, section 19. Conveyed via declaration of taking, recorded in the Maricopa County Recorder's in book 393, page 477, on Nov. 15, 1943.

The survey was executed in accordance with the specifications as set forth in the Manual of Instructions for the Survey of the Public Lands of the United States, 2009, and the Special Instructions dated September 21, 2020 for Group Number 1210, Arizona.

The true meridian direction and length of all lines were determined by real time kinematic global positioning system observations using Trimble Navigation R10-2 model receivers.

Preliminary to the resurvey, the lines of the prior surveys were retraced and search was made for all corners and other calls of record. Identified corners were remonumented in their original positions. Lost corners were reestablished and remonumented at proportionate positions based on the official record. The retracement data were thoroughly verified and only the true line field notes are given herein.

Geodetic control was derived from first order U.S. Coast and Geodetic Survey control station RUBY 1977, as published by the National Geodetic Survey, NAD 83 (1992).

The horizontal position of the section corner of sections 29, 30, 31 and 32, is as follows:

Latitude: 32°52'08.746" N.                      Longitude: 112°41'55.975" W.

The horizontal position of the 1/4 section corner of sections 13 and 18, on the west boundary of the township, is as follows:

Latitude: 32°54'19.911" N.                      Longitude: 112°42'56.328" W.

## T. 6 S., R. 4 W., Gila and Salt River Meridian, Arizona

## CHAINS

The mean magnetic declination is 10 1/4° E.

**Dependent Resurvey of Portions of the West Boundary,  
T. 6 S., R. 4 W., Gila and Salt River Meridian, Arizona**

Restoring the survey executed by  
Daniel Drummond, in 1891

Beginning at the 1/4 sec. cor. of secs. 13 and 18, on the W. bdy. of the Tp., reestablished by James A. Yanez, Arizona R.L.S. No. 4968, date unknown. Monumented with an iron pipe, 1 3/4 ins. diam., firmly set, projecting 8 ins. above ground, with attached 2 ins. diam. brass cap, mkd. T6S R5W 1/4 13 18 R4W LS 4968. Accepted as the best available evidence of the original cor.

Wire a brass washer, 1 1/2 ins. diam., mkd BLM 2020 to the iron pipe.

A fiberglass survey marker sign, 2 ins. wide, projecting 48 ins. above ground, is located 1.5 lks. SW of the cor.

Cor. is located on the NNW side of a 2 in. angle iron fence cor., cemented in place, with 4 strand barbed wire fences extend S. and W.

S. 0°06' W., bet. secs. 13 and 18, on the W. bdy. of the Tp. Identical with the E. bdy. of the Gila Bend Air Force Auxiliary Field, (hereinafter abbreviated GBAFAF).

In and along a rusted 4 strand barbed wire fence.

39.99 4 strand barbed wire fence, transitions to woven wire fence, topped with 2 strands of barbed wire.

40.15 The cor. of secs. 13, 18, 19 and 24, reestablished by Vernen Kalani Lee, Arizona R.L.S. No. 47302 in 2011. Monumented with a rebar, 30 ins. long, 3/4 in. diam., firmly set, 25 ins. in the ground, with attached 3 1/4 ins. diam. aluminum cap mkd. T6S R5W R4W S13 S18 S24 S19 2011 RLS 47302. Accepted as a careful and faithful reestablishment of the orig. cor. position. The record of survey that includes this cor., is recorded in the Maricopa County Recorder's Office in book 1088, page 49.

At the corner point

Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 20 ins. in the ground, in a mound of stone, 2 1/2 ft. base, to top, with brass cap mkd.

**Dependent Resurvey of Portions of the West Boundary,  
T. 6 S., R. 4 W., Gila and Salt River Meridian, Arizona**

CHAINS

T 6 S	
R 5 W	R 4 W
S 13	S 18
S 24	S 19

2020

Deposit a magnet, in a white plastic case, at the base of the stainless steel post.

Deposit the aluminum cap at the base of the stainless steel post, bury the rebar alongside.

A fiberglass survey marker sign, 2 ins. wide, projecting 48 ins. above ground, is located 1 lks. W of the cor.

Cor. is located alongside and E. of a 4 strand barbed wire fence.

From this cor. point, 1st order, U.S. Coast and Geodetic Survey triangulation station RUBY 1971, bears N. 15°00' E., 16.62 chs. dist. Monumented with a brass disk, 3 1/2 ins. diam., set in a 12 ins. diam., concrete cylinder, projecting 3 ins. above ground. Top is marked U.S. COAST & GEODETIC SURVEY RUBY 1971 TRIANGULATION STATION and a triangle.

---

S. 0°07' W., bet. secs. 19 and 24, on the E. bdy. of the GBAFAF.

In and along a woven wire fence, topped with 2 strands of barbed wire.

40.15

The 1/4 sec. cor. of secs. 19 and 24, reestablished by Vernen Kalani Lee, Arizona R.L.S. No. 47302 in 2011. Monumented with a rebar, 30 ins. long, 3/4 in. diam., firmly set, 25 ins. in the ground, with attached 3 1/4 ins. diam. aluminum cap mkd. T6S R5W R4W 1/4 S24 S19 2011 RLS 47302. Accepted as a careful and faithful reestablishment of the orig. cor. position. The record of survey that includes this cor., is recorded in the Maricopa County Recorder's Office in book 1088, page 49.

At the corner point

Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, in a collar of stone, with brass cap mkd.

T 6 S	
1/4	
R 5 W	R 4 W
S 24	S 19

2020

**Dependent Resurvey of Portions of the West Boundary,  
T. 6 S., R. 4 W., Gila and Salt River Meridian, Arizona**

CHAINS

Deposit a magnet, in a white plastic case, at the base of the stainless steel post.

Deposit the aluminum cap at the base of the stainless steel post, bury the rebar alongside.

A fiberglass survey marker sign, 2 ins. wide, projecting 48 ins. above ground, is located 1 lks. W of the cor.

Cor. is located alongside and E. of a woven wire fence, topped with 2 strands of barbed wire.

---

S. 0°08' W., beginning new measurement, on the E. bdy. of the GBAFAF.

40.10 Woven wire fence, topped with 2 strands of barbed wire, transitions to 4 strand barbed wire fence.

40.15 Point for the cor. of secs. 19, 24, 25 and 30, reestablished latitudinally at proportionate dist. and longitudinally utilizing a long standing fence.

Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.

T 6 S	
R 5 W	R 4 W
S 24	S 19
S 25	S 30

2020

Deposit a magnet, in a white plastic case, at the base of the stainless steel post.

Cor. is located within a 4 strand barbed wire fence.

From this cor. point, a rebar, 3/4 in. diam., firmly set, projecting 3 ins. above ground, bears E., 2.6 lks. dist. An attached 3 1/4 ins. diam., aluminum cap is mkd. T6S R5W R4W S24 S19 S25 S30 2011 RLS 47302. Witnessed by a fiberglass survey marker sign, 2 ins. wide, projecting 48 ins. above ground, set 1.5 lks. W. of the rebar. Cor. was established by Vernen Kalani Lee, Arizona R.L.S. No. 47302 in 2011 and disregarded the long established fence, as evidence of the original survey. Not utilized in the course of this resurvey. The record of survey that includes this cor., is recorded in the Maricopa County Recorder's Office in book 1088, page 49.

---

S. 0°07' W., bet. secs. 25 and 30, on the E. bdy. of the GBAFAF.

**Dependent Resurvey of Portions of the West Boundary,  
T. 6 S., R. 4 W., Gila and Salt River Meridian, Arizona**

CHAINS	
	In and along a 4 strand barbed wire fence.
2.05	An iron pipe, 1 1/2 ins. diam., firmly set, projecting 10 ins. above ground, located alongside and E. of 4 strand barbed wire fence, origin unknown,
40.15	Point for the 1/4 sec. cor. of secs. 25 and 30, reestablished latitudinally at proportionate dist. and longitudinally utilizing a long standing fence.  Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 22 ins. in the ground, in a collar of stone, with brass cap mkd.  <div style="text-align: center;"> <p>T 6 S 1/4 R 5 W   R 4 W S 25   S 30</p> <p>2020</p> </div> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p> <p>Cor. is located within a 4 strand barbed wire fence.</p> <p>From this cor. point, a rebar, 3/4 in. diam., firmly set, projecting 2 ins. above ground, bears E., 3.8 lks. dist. An attached 3 1/4 ins. diam., aluminum cap is mkd. T6S R5W R4W 1/4 S25 S30 2011 RLS 47302. Witnessed by a fiberglass survey marker sign, 2 ins. wide, projecting 48 ins. above ground, set 1.5 lks. W. of the rebar. Cor. was established by Vernen Kalani Lee, Arizona R.L.S. No. 47302 in 2011 and disregarded the long established fence, as evidence of the original survey. Not utilized in the course of this resurvey. The record of survey that includes this cor., is recorded in the Maricopa County Recorder's Office in book 1088, page 49.</p> <hr style="width: 20%; margin: 10px auto;"/> <p>S. 0°08' W., beginning new measurement.</p>
25.43	An angle point, marking the SE cor. of the GBAFAF, at the intersection of 4 strand barbed wire fences, extending N., S. and W. Witnessed by a 2 ins. angle iron fence corner set in concrete, slightly off plumb.  At the corner point  Wire a brass washer, 1 1/2 ins. diam., mkd BLM 2020 to the angle iron fence corner.  from which

**Dependent Resurvey of Portions of the West Boundary,  
T. 6 S., R. 4 W., Gila and Salt River Meridian, Arizona**

CHAINS

A stainless steel post, 28 ins. long, 2 1/2 ins. diam., set 27 ins. in the ground for a reference monument, bears N. 0°08' E., 10.0 ft. dist. with brass cap mkd. RM T6S R5W R4W S25 S30 10.0 FT TO COR. 2020 and an arrow pointing to the cor. Deposit a magnet, in a white plastic case, at the base of the stainless steel post. Located in 4 strand barbed wire fence, extends N. and S.

A stainless steel post, 28 ins. long, 2 1/2 ins. diam., set 23 ins. in the ground for a reference monument, bears S. 89°45' W., 10.0 ft. dist. with brass cap mkd. RM T6N R5W 10.0 FT TO COR. S25 2020 and an arrow pointing to the cor. Deposit a magnet, in a white plastic case, at the base of the stainless steel post. Located in a 4 strand barbed wire fence, extends E. and W.

From this cor. point, a rebar, 3/4 in. diam., firmly set, projecting 2 ins. above ground, bears S. 64 1/4° E., 5.2 lks. dist. An attached 3 1/4 ins. diam., aluminum cap is mkd. GBAF 2011 RLS 47302. Witnessed by fiberglass survey marker sign, 2 ins. wide, projecting 48 ins. above ground, set 1 lks. W. of the rebar. Cor. was established by Vernen Kalani Lee, Arizona R.L.S. No. 47302 in 2011 and disregarded the long established fence, as evidence of the original survey. Not utilized in the course of this resurvey. The record of survey that includes this cor., is recorded in the Maricopa County Recorder's Office in book 1088, page 49.

---

S. 0°04' E., beginning new measurement.

In and along a 4 strand barbed wire fence, on the E. bdy of the Barry M. Goldwater Air Force Range.

14.72

Point accepted for the cor. of secs. 25, 30, 31 and 36. Monumented with an iron pipe, 2 ins. diam., firmly set, projecting 2 ins. above ground. An attached 2 ins. diam. brass cap is mkd. T6S R5W R4W 25 30 + 36 31 LS 13554. Remonumented by Scott T. Burden, Arizona R.L.S. No. 13554, in 1980. Burden accepted a steel fence post, set in a mound of stone, within a 4 strand barbed wire fence. Accepted as the best available evidence of the original corner. The record of survey that includes this cor., is recorded in the Maricopa County Recorder's Office in book 326, page 27.

---

**Dependent Resurvey of a Portion of the Subdivisional Lines,  
T. 6 S., R. 4 W., Gila and Salt River Meridian, Arizona**

---

Restoring the survey executed by  
Daniel Drummond, in 1891

---



Dependent Resurvey of a Portion of the Subdivisional Lines,  
T. 6 S., R. 4 W., Gila and Salt River Meridian, Arizona

CHAINS	
	<p>From the cor. of secs. 29, 30, 31 and 32, reestablished Scott T. Burden, Arizona R.L.S. No. 13554 in 1988. Monumented with a galvanized iron pipe, 1 1/2 ins. diam., firmly set, projecting 7 ins. above ground. An attached 2 ins. diam. brass cap is mkd. T6S R4W 30 29 + 31 32 LS 13554. Accepted as a careful and faithful reestablishment of the orig. cor. position. The record of survey that includes this cor., is recorded in the Maricopa County Recorder's Office in book 326, page 27.</p> <p>Set a steel fence post, 1 lk. W. of the cor.</p> <p>N. 89°53' W., bet. secs. 30 and 31, on the N. bdy. of public lands.</p> <p>Over nearly level land, cut with northerly draining washes, through creosote with widely scattered palo verde and ironwood timber.</p> <p>40.17 The 1/4 sec. cor. of secs. 30 and 31. Monumented with a granite stone, 11 x 7 x 6 ins., firmly set, projecting 6 ins. above ground, mkd. 1/4 on the N. face.</p> <p>At the corner point</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T 6 S R 4 W S 30 1/4 ——— S 31</p> <p style="text-align: center;">2020</p> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p> <p>Bury the orig. stone alongside the stainless steel post.</p> <p>Set a steel fence post, alongside and N. of the cor.</p> <hr style="width: 20%; margin: 10px auto;"/> <p>N. 89°58' W., beginning new measurement.</p>
38.21	<p>The cor. of secs. 25, 30, 31 and 36, on the W. bdy. of the Tp., hereinbefore described.</p> <hr style="width: 80%; margin: 10px auto;"/> <p>From the cor. of secs. 29, 30, 31 and 32.</p> <p>N. 0°20' E., bet. secs. 29 and 30, within patented land.</p> <p>Over nearly level land, cut with northerly draining washes, through creosote with widely scattered palo verde and ironwood timber.</p>

Dependent Resurvey of a Portion of the Subdivisional Lines,  
T. 6 S., R. 4 W., Gila and Salt River Meridian, Arizona

CHAINS									
40.205	<p>Point for the 1/4 sec. cor. of secs. 29 and 30, at proportionate dist., there is no remaining evidence of the orig. cor.</p> <p>Not monumented.</p>								
80.41	<p>The cor. of secs. 19, 20, 29 and 30. Monumented with a granite stone, 22 x 12 x 10 ins., firmly set, 14 ins. in the ground, mkd. with 5 grooves on the E. face and 2 grooves on the S. face. Witnessed by a 1 in. wide angle iron, projecting 48 ins. above ground, set alongside.</p> <p>At the corner point</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 27 ins. in the ground, with brass cap mkd.</p> <table border="1" data-bbox="803 787 998 892"> <tr> <td>T 6 S</td> <td>R 4 W</td> </tr> <tr> <td>S 19</td> <td>S 20</td> </tr> <tr> <td>S 30</td> <td>S 29</td> </tr> </table> <p>2020</p> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p> <p>Bury the orig. stone alongside the stainless steel post.</p> <hr/> <p>N. 89°58' W., bet. secs. 19 and 30, on the S. bdy. of public lands.</p> <p>Over nearly level land, cut with northerly draining washes, through creosote with widely scattered palo verde and ironwood timber.</p>	T 6 S	R 4 W	S 19	S 20	S 30	S 29		
T 6 S	R 4 W								
S 19	S 20								
S 30	S 29								
40.70	<p>The 1/4 sec. cor. of secs. 19 and 30. Monumented with a granite stone, 16 x 10 x 8 ins., no marks visible, lying loose in a small mound of stones, alongside a weathered steel fence post.</p> <p>At the center of the mound of stones.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, in a collar of stone, with brass cap mkd.</p> <table border="1" data-bbox="803 1585 998 1711"> <tr> <td>T 6 S</td> <td>R 4 W</td> </tr> <tr> <td>S 19</td> <td></td> </tr> <tr> <td>1/4</td> <td>—</td> </tr> <tr> <td>S 30</td> <td></td> </tr> </table> <p>2020</p> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p>	T 6 S	R 4 W	S 19		1/4	—	S 30	
T 6 S	R 4 W								
S 19									
1/4	—								
S 30									

Dependent Resurvey of a Portion of the Subdivisional Lines,  
T. 6 S., R. 4 W., Gila and Salt River Meridian, Arizona

<p>CHAINS</p>	<p>Bury the orig. stone alongside the stainless steel post.</p> <p>Relocate the steel fence post, alongside and N. of the cor.</p> <hr/> <p>S. 89°58' W., beginning new measurement, on the N. bdy. of land reacquired by the U.S. Conveyed via quit claim deed, perfected in 1943.</p> <p>38.01 The cor. of secs. 19, 24, 25 and 30, on the W. bdy. of the Tp., hereinbefore described.</p> <hr/> <p>From the cor. of secs. 19, 20, 29 and 30.</p> <p>N. 0°06' E., bet. secs. 19 and 20, on the E. bdy. of public lands.</p> <p>Over nearly level land, cut with northerly draining washes, through creosote with widely scattered palo verde and ironwood timber.</p> <p>40.38 The 1/4 sec. cor. of secs. 19 and 20, reestablished by Elmer McDonie, retired Arizona P.E.(civil) No. 08790, date unknown. Monumented with a rebar, 18 ins. long, 3/8 in. diam., firmly set, 14 ins. in the ground, with attached brass tag mkd. PE 879. Accepted as a careful and faithful reestablishment of the orig. cor. position.</p> <p>At the corner point</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 23 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center;"> <p>T 6 S R 4 W</p> <p>1/4</p> <p>S 19   S 20</p> <p>2020</p> </div> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p> <p>Deposit the rebar and tag inside the stainless steel post.</p> <p>Set a steel fence post, alongside and W. of the cor.</p> <p>Cor. is located 25 lks. W. of a track road, bears S. 10° E. and N. 10° W.</p> <hr/> <p>N. 0°06' E., beginning new measurement.</p>
---------------	--

Dependent Resurvey of a Portion of the Subdivisional Lines,  
T. 6 S., R. 4 W., Gila and Salt River Meridian, Arizona

CHAINS	
40.38	<p>Point accepted for the cor. of secs. 17, 18, 19 and 20. Monumented with a rebar, 5/8 in. diam., with attached 1 1/2 diam. aluminum cap, damaged and unreadable. Set in concrete, 6 ins. below the surface of ground. Utilized by William J. Norman, Arizona R.L.S. No. 16588, in 2006, as described in Norman's record of survey, recorded in the Maricopa County Recorder's in book 855, page 50. Set, by James A. Yanez, Arizona R.L.S. No. 4968, date unknown. Accepted as the best available evidence of the original corner position.</p> <p>Cor. is located on the S. edge of a graded road, 20 ft. wide, bears E. and W.</p> <hr/> <p>S. 89°54' W., bet. secs. 18 and 19, on the N. bdy. of public land.</p> <p>In and along, a graded road, 20 ft. wide.</p>
10.04	A 60D nail, set in graded road, unknown origin.
30.12	A rebar, 1/2 in. diam., set 1 in. below the surface of graded road, unknown origin.
35.14	A rebar, 1/2 in. diam., set 2 in. below the surface of graded road, unknown origin.
40.16	<p>Point accepted for the 1/4 sec. cor. of secs. 18 and 19. Monumented with the rusted remains of an iron rod 1/2 in. diam., set 4 ins. below the surface. An aluminum rod, 18 ins. long, 1/2 in. diam., set 3 ins. below the surface, is set alongside the iron rod. An attached 3 ins. diam. aluminum cap is mkd. RLS 11062 T6S R4W 1/4 S18 S19 19. Perpetuated by Stephen Slyder, Arizona R.L.S. No. 11062, date unknown. Accepted as the best available evidence of the original corner.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 34 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center;"> <p>T 6 S R 4 W</p> <p>S 18</p> <p>1/4 ———</p> <p>S 19</p> <p>2020</p> </div> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post, insert the iron rod and aluminum rod, within the stainless steel post, bury the aluminum cap alongside the corner.</p> <p>from which</p>

**Dependent Resurvey of a Portion of the Subdivisional Lines,  
T. 6 S., R. 4 W., Gila and Salt River Meridian, Arizona**

CHAINS	
	<p>A rebar, 24 ins. long, 5/8 ins. diam., set 21 ins. in the ground for a reference monument, bears S. 45°' W., 99.0 ft. dist. An attached 2 ins. diam. brass cap is mkd. RM T6S R4W 99.0 FT TO COR. 1/4 S19 2020 and an arrow pointing to the cor.</p> <p>A rebar, 24 ins. long, 5/8 ins. diam., set 21 ins. in the ground for a reference monument, bears N. 45°' W., 66.0 ft. dist. An attached 2 ins. diam. brass cap is mkd. RM T6S R4W 66.0 FT TO COR. 1/4 S18 2020 and an arrow pointing to the cor.</p> <p>Cor. is located on the N. edge of a graded road, 20 ft. wide, bears E. and W.</p> <hr/> <p>S. 89°13' W., beginning new measurement, on the S. bdy of the land acquired by the U.S., conveyed via warranty deed, perfected in 1943. Identical with the N. bdy. of land acquired by the U.S., conveyed via declaration of taking, perfected in 1943.</p>
22.45	Center of graded road, bears S. 89° E. and N. 89° W., curving N.
38.50	The cor. of secs. 13, 18, 19 and 24, on the W. bdy. of the Tp., hereinbefore described.
	<hr/> <p><b>Subdivision of Section 18, T. 6 S., R. 4 W., Gila and Salt River Meridian, Arizona</b></p> <hr/>
	<p>From the 1/4 sec. cor. of secs. 18 and 19, hereinbefore described.</p> <p>N. 0°13' E., on the N. and S. center line of sec. 18.</p> <p>On the E. bdy of the land acquired by the U.S., conveyed via warranty deed, perfected in 1943.</p>
9.97	Fence cor., with woven wire fences extending N. and E.
19.91	Fence cor., with woven wire fences extending S. and E.
39.82	The center 1/4 sec. cor. of sec. 18, established by Dale Stone, (retired) Arizona R.L.S. No. 12218, date unknown. Monumented with a rebar, 18 ins. long, 1/2 in. diam., firmly set, 17 ins. in the ground, with attached brass tag mkd. 12218 RLS. Accepted as a careful and faithful establishment of the cor. position.
	At the corner point

Subdivision of Section 18,  
T. 6 S., R. 4 W., Gila and Salt River Meridian, Arizona

CHAINS	
	<p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 27 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T 6 S R 4 W C 1/4 S 18</p> <p style="text-align: center;">2020</p> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post, insert the rebar and tag, inside the stainless steel post.</p> <p>Set a steel fence post, alongside and W. of the cor.</p> <hr style="width: 20%; margin: 10px auto;"/> <p>N. 0°13' E., beginning new measurement.</p> <p>Over patented lands.</p>
39.82	<p>The 1/4 sec. cor. of secs. 7 and 18. Perpetuated by person(s) unknown. Accepted and enhanced by James A. Yanez, Arizona R.L.S. No. 4968, in 1999. Monumented with an iron pipe, 1 1/2 ins. diam., set in concrete, with a 2 ins. diam. brass cap mkd. T6S R4W 1/4 7 18 LS 4968, cemented to the pipe. Accepted as the best available evidence of the orig. cor. position. The record of survey that includes this cor., is recorded in the Maricopa County Recorder's Office in book 916, page 46.</p> <hr style="width: 80%; margin: 10px auto;"/> <p>From the 1/4 sec. cor. of secs. 17 and 18. Monumented with a 3 ins. diam., brass tablet, set in a 12 ins. diam., concrete cylinder, projecting 1 in. above ground. Brass tablet is mkd. FLOOD CONTROL DISTRICT E 1/4 + SEC 18 MARICOPA COUNTY. Via a conversation with survey personal at Maricopa County Flood Control District, no records of this cor. was available. Accepted as the best available evidence of the original cor. position.</p> <p>S. 89°44' W., on the E. and W. center line of sec. 18.</p> <p>Over patented lands.</p>
40.10	<p>The center 1/4 sec. cor. of sec. 18.</p> <hr style="width: 20%; margin: 10px auto;"/> <p>S. 89°43' W., beginning new measurement.</p> <p>On the N. bdy. of the land reacquired by the U.S., conveyed via warranty deed, perfected in 1943.</p>
20.16	<p>The center W. 1/16 sec. cor. of sec. 18, established by Thomas Rope, Arizona R.L.S. No. 21081, date unknown. Monumented with a rebar, 1/2 in. diam., firmly set, projecting 4 in. above ground,</p>

Subdivision of Section 18,  
T. 6 S., R. 4 W., Gila and Salt River Meridian, Arizona

CHAINS	<p>with attached brass tag mkd. RLS 21081. Accepted as a careful and faithful establishment of the cor. position.</p> <p>Cor. is located, 1 lk. SSE of a fence cor., with barbed wire fences extending N. and W.</p> <hr style="width: 20%; margin: 10px auto;"/> <p>S. 89°43' W., beginning new measurement.</p> <p>Along a barbed wire fence.</p> <p>17.89 From this point, the corner of barbed wire fences, extending E. and N., bears N. 1.5 lks. dist.</p> <p>18.10 Graded road, 20 ft. wide, bears N. and S. 15° E.</p> <p>18.41 The 1/4 sec. cor. of secs. 13 and 18, on the W. bdy. of the Tp., hereinbefore described.</p> <hr style="width: 80%; margin: 10px auto;"/> <p style="text-align: center;"><b>Subdivision of Section 19, T. 6 S., R. 4 W., Gila and Salt River Meridian, Arizona</b></p> <hr style="width: 80%; margin: 10px auto;"/> <p>From the 1/4 sec. cor. of secs. 19 and 30, hereinbefore described.</p> <p>N. 0°29' E., on the N. and S. center line of sec. 19.</p> <p>Within public lands, over nearly level land.</p> <p>40.24 Point for the center 1/4 sec. cor. of sec. 19, at intersection with the E. and W. center line of sec. 19.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 27 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T 6 S R 4 W C 1/4 S 19</p> <p style="text-align: center;">2020</p> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p> <p>Set a steel fence post, 1 lk. N. of the cor.</p> <p>Continuing measurement, on the E. bdy. of the land acquired by the U.S., conveyed via declaration of taking, perfected in 1943.</p> <p>80.81 The 1/4 sec. cor. of secs. 18 and 19, hereinbefore described.</p> <hr style="width: 80%; margin: 10px auto;"/>
--------	---

**Subdivision of Section 19,  
T. 6 S., R. 4 W., Gila and Salt River Meridian, Arizona**

CHAINS	
	<p>From the 1/4 sec. cor. of secs. 19 and 20, hereinbefore described.</p> <p>S. 89°50' W., on the E. and W. center line of sec. 19. Within public lands.</p>
40.43	<p>The center 1/4 sec. cor. of sec. 19.</p> <p>Continuing measurement, on the S. bdy. of the land reacquired by the U.S. Conveyed via declaration of taking, perfected in 1943.</p>
78.68	<p>The 1/4 sec. cor. of secs. 19 and 24, on the W. bdy. of the Tp., hereinbefore described.</p> <hr/> <p style="text-align: center;"><b>Subdivision of Section 30, T. 6 S., R. 4 W., Gila and Salt River Meridian, Arizona</b></p> <hr/> <p>From the 1/4 sec. cor. of secs. 30 and 31, hereinbefore described.</p> <p>N. 0°03' W., on the N. and S. center line of sec. 30.</p> <p>Over patented lands.</p>
40.15	<p>Point for the center 1/4 sec. cor. of sec. 30, at intersection with the E. and W. center line of sec. 30.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 23 ins. in the ground, in a collar of stone, with brass cap mkd.</p> <p style="text-align: center;">T 6 S R 4 W C 1/4 S 30</p> <p style="text-align: center;">2020</p> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p> <p>Set a steel fence post, alongside and W. of the cor.</p> <p>Continuing measurement, on the E. bdy. of the land reacquired by the U.S. Conveyed via quit claim deed, perfected in 1943.</p>
80.35	<p>The 1/4 sec. cor. of secs. 19 and 30, hereinbefore described.</p> <hr/> <p>From the point for the 1/4 sec. cor. of secs. 29 and 30, hereinbefore described.</p> <p>N. 89°58' W., on the E. and W. center line of sec. 30.</p> <p>Over patented lands.</p>



Subdivision of Section 30,  
T. 6 S., R. 4 W., Gila and Salt River Meridian, Arizona

CHAINS	
40.44	<p>The center 1/4 sec. cor. of sec. 30.</p> <p>Continuing measurement, on the S. bdy. of the land reacquired by the U.S. Conveyed via quit claim deed, perfected in 1943.</p>
78.57	<p>The 1/4 sec. cor. of secs. 25 and 30, on the E. bdy. of the Tp., hereinbefore described.</p> <hr/> <p style="text-align: center;">GENERAL DESCRIPTION</p> <hr/> <p>The area surveyed is located about 5 miles SSE from the Town of Gila Bend Municipal Building. Access is provided by Az. State Highway No. 85, to Gila Bend. Thence to Martin Road, a graveled and improved road, within the corporate boundaries of the Town of Gila Bend.</p> <p>The terrain is nearly level, cut with many, small northerly draining washes. Vegetation is predominantly creosote. Palo verde and ironwood timber is found in and near the washes. The soils are alluvial deposits of loam and sandy loam. Several placer claim stakes were located, no active mining was observed. Several residence exist in section 18. Sections 19 and 30 are vacant.</p> <p>The mean magnetic declination of 10 1/4° E. was derived from National Oceanic and Atmospheric Administration, on line Magnetic Field Calculator program, utilizing the World Magnetic Model (2019-2024), for the dates of the survey.</p>



CERTIFICATE OF SURVEY

I, Gordon R. Bubel, Cadastral Surveyor, HEREBY CERTIFY upon honor, that in pursuance of special instructions bearing date of the 21st day of September, 2020. I have dependently resurveyed a portion of the west boundary. Dependently resurveyed portions of the subdivisional lines. Subdivided sections 18, 19 and 30, in Township 6 South, Range 4 West, of the Gila and Salt River Meridian, in the State of Arizona, which are represented in the foregoing field notes as having been executed by me and under my direction. Said survey has been made in strict conformity with said special instructions, the Manual of Instructions for the Survey of the Public Lands of the United States, 2009, and in specific manner described in the foregoing field notes.

April 2, 2021  
(Date)

Gordon R. Bubel  
(Cadastral Surveyor)

CERTIFICATE OF APPROVAL

BUREAU OF LAND MANAGEMENT  
Phoenix, Arizona

The foregoing field notes of the dependent resurvey of a portion of the west boundary. The dependent resurvey of portions of the subdivisional lines. The subdivision of sections 18, 19 and 30, T. 6 S., R. 4 W., Gila and Salt River Meridian, in the State of Arizona, executed by Gordon R. Bubel, Cadastral Surveyor, having been critically examined and found correct, are hereby approved.

4/14/2021  
(Date)

Wade Mackay  
(Chief Cadastral Surveyor of )

~~CERTIFICATE OF TRANSCRIPT~~

~~I CERTIFY that the foregoing transcript of the field notes of the above described surveys in T. 6 S., R. 4 W., Gila and Salt River Meridian, in the state of Arizona, is a true copy of the original field notes.~~

~~\_\_\_\_\_~~  
~~(Date)~~

~~\_\_\_\_\_~~  
~~(Chief Cadastral Surveyor of )~~